



US010639047B2

(12) **United States Patent**
Amanatullah

(10) **Patent No.:** **US 10,639,047 B2**
(45) **Date of Patent:** ***May 5, 2020**

(54) **MODULAR TOTAL KNEE ARTHROPLASTY SYSTEM AND METHOD**

(2013.01); *A61F 2002/30616* (2013.01); *A61F 2002/30878* (2013.01); *A61F 2002/4619* (2013.01)

(71) Applicant: **Arthrology Consulting, LLC**, Palo Alto, CA (US)

(58) **Field of Classification Search**
CPC *A61F 2/3859*; *A61F 2/389*; *A61F 2/461*; *A61F 2/4684*; *A61F 2002/30616*; *A61B 17/1675*; *A61B 17/164*; *A61B 17/164*; *A61B 17/1659*; *A61B 17/1602*

(72) Inventor: **Derek Amanatullah**, Palo Alto, CA (US)

See application file for complete search history.

(73) Assignee: **Arthrology Consulting, LLC**, Palo Alto, CA (US)

(56) **References Cited**

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

U.S. PATENT DOCUMENTS

This patent is subject to a terminal disclaimer.

4,479,271 A 10/1984 Bolesky et al.
4,936,853 A 6/1990 Fabian et al.

(Continued)

(21) Appl. No.: **16/209,888**

Primary Examiner — Brian A Dukert

(22) Filed: **Dec. 4, 2018**

(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson & Bear LLP

(65) **Prior Publication Data**

US 2019/0167279 A1 Jun. 6, 2019

Related U.S. Application Data

(63) Continuation of application No. 15/477,578, filed on Apr. 3, 2017.

(Continued)

(57) **ABSTRACT**

(51) **Int. Cl.**

A61B 17/16 (2006.01)

A61F 2/38 (2006.01)



(Continued)

A modular system for total knee arthroplasty includes a modular trial implant assembly. The modular implant assembly includes an elongate shaft configured for insertion into an elongate cavity in a bone, a reamer removably coupleable to the elongate shaft via a connection that allows the reamer to rotate while the elongate shaft remains in a substantially fixed angular orientation. The reamer has an outer surface that tapers toward the distal end configured to form a tapered cavity in an end of a bone in which the reamer is inserted and rotated. The modular trial implant assembly further includes a trial implant removably coupleable to a proximal end of the reamer. A modular final implant assembly includes an elongate stem, a tapered body and an implant body, each having a size and shape that can substantially correspond to a size and shape of the elongate shaft, the reamer and the trial implant, respectively.

(52) **U.S. Cl.**

CPC *A61B 17/1675* (2013.01); *A61B 17/1764* (2013.01); *A61F 2/389* (2013.01); *A61F 2/3859* (2013.01); *A61F 2/461* (2013.01); *A61F 2/4684* (2013.01); *A61F 2002/30205*

23 Claims, 15 Drawing Sheets



Related U.S. Application Data

(60) Provisional application No. 62/318,684, filed on Apr. 5, 2016.

(51) **Int. Cl.**

A61F 2/46 (2006.01)

A61B 17/17 (2006.01)

A61F 2/30 (2006.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,938,769	A	7/1990	Shaw	
5,100,407	A	3/1992	Conrad et al.	
5,290,313	A	3/1994	Heldreth	
5,413,605	A	5/1995	Ashby et al.	
6,139,581	A	10/2000	Engl et al.	
6,146,424	A	11/2000	Gray, Jr. et al.	
6,214,052	B1	4/2001	Burkinshaw	
6,447,549	B1	9/2002	Taft	
6,869,447	B2	3/2005	Lee et al.	
7,294,149	B2	11/2007	Hozack et al.	
7,618,451	B2	11/2009	Berez et al.	
7,727,281	B2	6/2010	Ensign	
8,366,782	B2	2/2013	Wright	
8,496,666	B2	7/2013	Ries et al.	
8,758,444	B2	6/2014	Wentorf et al.	
8,845,745	B2	9/2014	Dees, Jr. et al.	
9,101,476	B2	8/2015	Deruntz et al.	
2009/0149963	A1	6/2009	Sekel	
2010/0217267	A1*	8/2010	Bergin	A61F 2/3609 606/80
2011/0112540	A1*	5/2011	McLean	A61B 17/164 606/80
2013/0289731	A1	10/2013	Katerberg et al.	

* cited by examiner




FIG. 1




FIG. 2







FIG. 3








FIG. 6A




FIG. 6B




FIG. 7




FIG. 8




FIG. 9







FIG. 10






FIG. 13




FIG. 14





FIG. 16




FIG. 17




FIG. 18

1

MODULAR TOTAL KNEE ARTHROPLASTY SYSTEM AND METHOD

CROSS-REFERENCE TO RELATED APPLICATIONS

Any and all applications for which a foreign or domestic priority claim is identified in the Application Data Sheet as filed with the present application are hereby incorporated by reference under 37 CFR 1.57 and should be considered a part of this specification.

BACKGROUND

Field

The present invention relates to a system and method for knee replacement surgery and more particularly to a modular total knee arthroplasty system and method for use in primary and revision knee replacement.

Description of the Related Art

Total or partial knee replacement is very common, for example to treat conditions such as arthritis or treat injuries to the knee joint (e.g., from trauma, accidents, sport injuries, etc.). Total knee arthroplasty involves implanting a first prosthetic device on the distal end of the femur and a second prosthetic device on the proximal end of the tibia, where the first and second prosthetic devices replace the natural articulating bone surfaces of the knee joint (e.g., femoral condyles). Such surgical procedures involve cutting sections of the femur and tibia to accommodate the prosthetic devices in proper alignment, and can be complex and time consuming.

In some cases, it is necessary to perform a knee replacement revision surgery to replace the previously implanted knee prosthetic devices. For example, the previously implanted knee prosthetic devices may loosen over time, for example, from the production of wear debris, infection, or fracture. Revision surgery is typically more complicated and time consuming than an initial knee replacement surgery because the surgeon must remove the previously implanted device, which was cemented into the bone or has existing bone into the device. In addition, once the surgeon remove the implant, there is less bone remaining for fixation of the revision implant.

SUMMARY

In accordance with one aspect of the invention, an improved total knee arthroplasty system and method is provided that simplifies the process of delivering a primary or revision knee replacement implant, as well as to replace an existing knee replacement implant, and makes such processes less time consuming.

In accordance with one aspect, a modular system for total knee arthroplasty is provided. The system comprises a modular trial implant assembly. The modular implant assembly comprises an elongate shaft configured for insertion into an elongate cavity in a bone. The modular trial implant assembly also comprises a reamer that extends between a proximal end and a distal end, the reamer being removably coupleable to a proximal end of the elongate shaft via a connection that allows the reamer to rotate while the elongate shaft remains in a substantially fixed angular orientation. The reamer has an outer surface that tapers toward the distal end of the reamer. The outer surface further has a

2

plurality milling elements extending between the proximal and distal ends of the reamer about the circumference of the reamer, the milling elements configured to form a tapered cavity in an end of a bone in which the reamer is inserted and rotated. The modular trial implant assembly further comprises a trial implant removably coupleable to a proximal end of the reamer. The elongate shaft is configured to provide angular orientation but not rotational stability when inserted into the elongate cavity, and wherein the reamer is configured to provide rotational and axial stability in the tapered cavity.

In accordance with another aspect, a modular system for total knee arthroplasty is provided. The system comprises a modular trial implant assembly. The modular implant assembly comprises an elongate shaft configured for insertion into an elongate cavity in a bone. The modular trial implant assembly also comprises a reamer that extends between a proximal end and a distal end, the reamer being removably coupleable to a proximal end of the elongate shaft via a connection that allows the reamer to rotate while the elongate shaft remains in a substantially fixed angular orientation. The reamer has an outer surface that tapers toward the distal end. The reamer comprises a plurality of sequentially nestable portions releasably coupleable with each other to define a tapered shape, where a maximum outer diameter of the tapered shape is defined by the last of the sequentially nestable portions that are coupled to each other. The plurality of sequentially nestable portions are configured to rotate as a single unit when assembled together. The outer surface further has a plurality milling elements extending between the proximal and distal ends of the reamer about the circumference of the reamer, the milling elements configured to form a tapered cavity in an end of a bone in which the reamer is inserted and rotated. The modular trial implant assembly further comprises a trial implant removably coupleable to a proximal end of the reamer. The elongate shaft is configured to provide angular orientation but not rotational stability when inserted into the elongate cavity, and wherein the reamer is configured to provide rotational and axial stability in the tapered cavity.

In accordance with another aspect, a modular kit for total knee arthroplasty is provided. The kit comprises a plurality of elongate shafts configured for insertion into an elongate cavity in a femur or tibia bone, each of the elongate shafts differing in one or both of length and outer diameter. The kit also comprises a plurality of tapered reamers differing in one or both of length and maximum outer diameter, the reamer having an outer surface with a plurality milling elements extending about the circumference of the reamer. The kit also comprises a plurality of trial implants of different sizes, wherein each of the trial implants is coupleable to a proximal end of each of the tapered reamers, which is coupleable to a proximal end of each of the elongate shafts to assemble a trial implant assembly.

In accordance with another aspect, the modular kit further comprises a plurality of elongate stems configured for insertion into an elongate cavity in a femur or tibia bone, each of the elongate shafts differing in one or both of length and outer diameter, a plurality of tapered cone bodies differing in one or both of length and maximum outer diameter and a plurality of implants of different sizes. Each of the implants is coupleable to a proximal end of each of the tapered cone bodies, which is coupleable to a proximal end of each of the elongate stems to assemble a final implant assembly. Optionally, the plurality of elongate stems, plurality of tapered cone bodies and plurality of implants substantially correspond in size and shape with the plurality

of elongate shafts, plurality of tapered reamers and plurality of trial implants, respectively. Optionally, at least one of the plurality of tapered cone bodies has an outer surface with a plurality of flute elements extending about the circumference of the tapered conical body to define a tapered fluted conical body. Optionally, at least one of the plurality of tapered cone bodies has an outer surface that is porous. Optionally, at least one of the plurality of tapered cone bodies has an outer surface that is rough.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic view of a side view of a knee joint.

FIG. 2 is a schematic view of a front view of a knee joint.

FIG. 3 is a schematic side view of one embodiment of a reaming assembly.

FIG. 4 is a schematic side view of another embodiment of a reaming assembly.

FIG. 5A is a schematic side view of one embodiment of a reaming cone.

FIG. 5B is a schematic top view of the reaming cone of FIG. 5A.

FIG. 6A is a schematic side view of another embodiment of a reaming cone.

FIG. 6B is a schematic top view of the reaming cone of FIG. 6A.

FIG. 7 is a schematic side view of another embodiment of a reaming cone.

FIG. 8 is a schematic side view of another embodiment of a reaming cone.

FIG. 9 is a schematic proximal end view of a cut tibia bone with a reaming cone therein.

FIG. 10 is a schematic distal end view of a cut femur bone with a reaming cone therein.

FIG. 11A is a schematic side view of a cut distal end of the femur bone with the reaming cone therein prior to installation of a trial femoral knee implant.

FIG. 11B is a schematic side view of a cutting guide disposed at the distal end of the femur to cut one or more planar surfaces to accommodate an implant.

FIG. 12 is a schematic side view of the assembly in FIG. 12 after installation of the trial femoral knee implant.

FIG. 13 is a front view of the assembly in FIG. 12 after installation of the trial femoral knee implant.

FIG. 14 is a schematic side view of a cut proximal end of the tibia bone with the reaming cone therein after installation of the trial tibial knee implant.

FIG. 15 is a schematic side view of a device for removing a knee implant.

FIG. 16 is a schematic block diagram of a kit for a trial implant assembly and kit for a final implant assembly.

FIG. 17 is a block diagram showing a method of installing a knee implant.

FIG. 18 is a block diagram showing a method of removing a knee implant.

DETAILED DESCRIPTION

FIGS. 1-2 shows a schematic side and front view, respectively of a human knee joint 100, which includes a distal end 12 of a femur 10, a proximal end 22 of a tibia 20, and a patella 30. Total knee arthroplasty (TKA) involves removal of at least a portion of the distal end 12 of the femur 10 and at least a portion of the proximal end 22 of the tibia 20 and implantation of prosthetic femoral and tibial components, as described further below.

FIG. 3 shows one embodiment of an assembly 300 that can be used during a total knee replacement or total knee revision surgical procedure, as further discussed below. The assembly 300 can include an elongate shaft or stem 310 that can be inserted into the bone. In the illustrated embodiment, the assembly 300 is schematically shown disposed in the tibia 20. However, the assembly 300 can also be used in femur 10. The elongate shaft 310 extends between a proximal end 312 and a distal end 314 and has an outer surface 316. Optionally, the elongate shaft 310 can be cylindrical in shape (e.g., have a circular transverse cross-section), conical (e.g., circular in transverse cross-section but with decreasing cross-sectional area as to create a taper in the orthogonal plane), or splined/fluted (e.g., have a star-like transverse cross-section). The outer surface 316 can optionally be a smooth surface. As used herein, "smooth" is intended to have its ordinary meaning (e.g., free from perceptible projections, lumps or indentations); in connection with orthopedic components, "smooth" is meant to refer, for example, to a surface that is not fluted or has ridges protruding from it, so the component does not provide rotational stability. In the illustrated embodiment, the elongate shaft 310 extends along an axis X that generally coincides with (e.g., is parallel to, is coaxial with) a central axis of the tibia 20 (e.g., where the tibia 20 extends in a normally linear manner such that the axis X of the elongate shaft 310 intersects a transverse plane at an ankle A at the distal end of the tibia 20 substantially at a 90 degree angle). With respect to the femoral implant, elongate shaft 310 extends along an axis X that generally coincides with (e.g., is parallel to, is coaxial with) a central axis of the femur 10 (e.g., where the femur 10 extends in a normally linear manner such that the axis X of the elongate shaft 310 intersects a transverse plane at a hip at the proximal end of the femur 10 substantially at a 90 degree angle). In one embodiment, the elongate shaft or stem 310 is substantially fixed within the bone (e.g., within the tibia 20) so that it does not rotate within the bone during the procedure. Optionally, the elongate shaft 310 can have a length of between about 25 mm and about 200 mm and a diameter of between about 10 mm and about 30 mm. However, the elongate shaft 310 can have other suitable dimensions. The elongate shaft 310 can define a majority (e.g., greater than 50%, greater than 60%, greater than 75%, greater than 80%, etc.) of the length of the assembly 300.

With continued reference to FIG. 3, the proximal end 312 of the elongate shaft 310 can removably couple with a reamer component 320, optionally via a bearing connection 323 (e.g., rolling element bearing, such as one with an inner race that couples with the proximal end 312 of the elongate shaft 310 and an outer race that couples with the reamer 320, where the inner and outer races rotate relative to each other). In another embodiment, the connection 323 can be a boss that allows rotational movement between the reamer component 320 and the elongate shaft 310, so that the reamer 320 can rotate while the elongate shaft 310 remains in a substantially fixed angular orientation. In one embodiment, the proximal end 312 of the elongate shaft 310 can have a cross-sectional shape (e.g., hexagonal, pentagonal, square) that substantially matches a shape of an opening in the bearing connection that receives the proximal end 312. Accordingly, the reamer 320 can rotate without rotating the elongate shaft 310. The reamer 320 can extend between a proximal end 324 and a distal end 322. In the illustrated embodiment, the reamer 320 has a tapered cone shape so that the outer surface 326 of the reamer 320 tapers from the proximal end 324 toward the distal end 322. The outer surface 326 of the reamer 320 can have one or more milling

elements **327** (e.g., ridges) that allow the reamer **320** to create a cavity in the bone having a corresponding shape as the reamer **320**. In the illustrated embodiment, the tapered cone shaped reamer **320** can be rotated to form a tapered cone shaped cavity in the proximal end **22** of the tibia **20**.

The proximal end **324** of the reamer **320** can have a connector **328** shaped to couple with a corresponding end of a shaft **410** that can be chucked to an orthopedic tool (manual or electric), such as a drill **400**. In one embodiment, the connector **328** is a female connector having an opening shaped (e.g., with a cross-sectional shape that is square, hexagonal, pentagonal, etc.) to receive a similarly shaped end of the shaft **410**. In another embodiment, the connector **328** is a male connector having a cross-sectional shape (e.g., square, hexagonal, pentagonal, etc.) corresponding to a shape of an opening in the shaft **410** that receives the connector **328**. Once chucked to the drill **400**, the shaft **410** can be rotated, which can in turn rotate the reamer **320** via the connector **328** to form the cavity in the bone without rotating the elongate shaft **310**, which remains in a fixed orientation in the bone.

FIG. 4 shows an embodiment of an assembly **300B** that is similar to the assembly **300** in FIG. 3, except as described below. The assembly **300B** is constructed similar to the assembly **300** shown in FIG. 3, except as noted below. Therefore, the references numerals used to designate the various components of the assembly **300B** are identical to those used for identifying the corresponding components of the assembly **300** in FIG. 3, except that a "B" has been added to the reference numerals.

In the illustrated embodiment, the elongate shaft or stem **310B** extends at an angle α relative to an axis of the femur **10** or tibia **20** (e.g., relative to a central axis X of the bone), where the bone (e.g., tibia) is s-shaped or to account for normal anatomy of the distal femur including variations of the anatomic axis in the coronal plane and femoral bow in the sagittal plane. In one embodiment the angle α can be between about 3 degrees and about 5 degrees. In other embodiments, the angle α can have other values, such as between about 1 degree and about 12 degrees. The proximal end **312B** of the elongate shaft **310B** extends along a vertical axis, while the portion of the elongate shaft **310B** distal of the proximal end **312B** extends at said offset angle α relative to the vertical axis X. As with the assembly **300**, the assembly **300B** has a reamer **320B** that removably couples to the proximal end **312B** of the elongate shaft **310B** via a rotatable connection **323B** (e.g., a bearing connection, such as rolling element bearing, a boss, etc.) that allows the elongate shaft **310B** to remain in a fixed orientation while the reamer **320B** is rotated to ream a cavity into the end of the bone (e.g., the proximal end **22** of the tibia **20**). The reamer **320B** is similar to the reamer **320** and operates in the same manner, can have a tapered cone shape, and can be coupled to a drill **400** via a shaft **410** that can be chucked to the drill **400** and that can couple to a connector **328B** in the proximal end **324B** of the reamer **320**.

FIGS. 5A and 5B show a schematic side view and top view of the reamer **320**, **320B** shown in FIGS. 3-4. The proximal end **324**, **324B** of the reamer **320**, **320B** can have a surface **325**, **325B** that in one embodiment is generally planar. In other embodiments, the surface **325**, **325B** can have other suitable shapes, such as concave, convex, etc. The connector **328**, **328B** at the proximal end **324**, **324B** of the reamer **320**, **320B** in FIG. 5B can be female and have a generally circular shape (e.g., a cylindrical recess) that receives the shaft **410**. In other embodiments, the connector **328**, **328B** can have other shapes (e.g., square, pentagonal,

hexagonal) that mates with a similarly shaped end of the shaft **410** to allow rotation of the shaft **410** (e.g., via the drill **400**) to cause rotation of the reamer **320**, **320B**. In the illustrated embodiment, the proximal end **324**, **324B** and the distal end **322**, **322B** of the reamer **320**, **320B** can extend along substantially parallel planes, with the outer diameter of the proximal end **324**, **324B** being greater than the outer diameter of the distal end **322**, **322B** to thereby define the tapered cone shape.

FIGS. 6A-6B show an embodiment of a reamer **320C** that is similar to the reamer **320**, **320B** in FIGS. 5A-5B, except as described below. The reamer **320C** is constructed similar to the reamer **320**, **320B** shown in FIGS. 5A-5B, except as noted below. Therefore, the references numerals used to designate the various features of the reamer **320C** are identical to those used for identifying the corresponding features of the reamer **320**, **320B** in FIGS. 5A-5B, except that a "C" has been added to the reference numerals.

In the illustrated embodiment, a proximal end **324C** of the reamer **320C** has a cutout **321C** so that the shape of the reamer **320C** is not a complete tapered cone. The cutout **321C** defines a vertical surface **321C1** and a horizontal surface **321C2** that are optionally substantially perpendicular to each other. The reamer **320C** has a height **329C1** between the distal end **322C** and the horizontal surface **321C2** of the cutout **321C**. The reamer **320C** has a height **329C2** between the distal end **322C** and the proximal end **324C**. In one embodiment, the height **329C1** can be approximately one half the height **329C2**. However, in other embodiments the ratio between the height **329C1** and the height **329C2** can have other suitable values (e.g., $\frac{1}{4}^{th}$, $\frac{1}{3}^{rd}$, $\frac{3}{4}^{th}$, etc.). The cutout **321C** in the reamer **320C** allows the reamer **320C** to accommodate (e.g., to not impinge on) the implant (e.g., the femoral knee implant) when implant is coupled to the reamer **320C** component, as further discussed below. The reamer **320C** is otherwise similar to the reamer **320**, **320B** and operates in the same manner, can have a generally tapered cone shape, and can be coupled to a drill **400** via a shaft **410** that can be chucked to the drill **400** and that can couple to a connector **328C** in the proximal end **324C** of the reamer **320C**. The distal end **322C** of the reamer can couple to a proximal end **312**, **312B** of an elongate shaft or stem **310**, **310B** via a rotatable connector **323**, **323B** (e.g., a bearing connector, boss, etc.) that allows the reamer **320C** to rotate (e.g., to create the tapered cavity in the femur) while the shaft **310**, **310B** remains in a fixed orientation (e.g., the elongate shaft **310**, **310B** does not rotate with the reamer **320C**).

FIG. 7 shows an embodiment of a reamer **320D** that is similar to the reamer **320**, **320B** in FIGS. 3-5B, except as described below. The reamer **320D** is constructed similar to the reamer **320**, **320B** shown in FIGS. 3-5B, except as noted below. Therefore, the references numerals used to designate the various features of the reamer **320D** are identical to those used for identifying the corresponding features of the reamer **320**, **320B** in FIGS. 3-5B, except that a "D" has been added to the reference numerals.

In the illustrated embodiment, the reamer **320D** can include one or more nested reamer portions A-D that can be sequentially coupled to each other to define the reamer body **320D**. Though FIG. 7 shows the reamer **320D** with four reamer portions A-D, one of skill in the art will recognize that the reamer **320D** can have any number of reamer portions A-D, where at least a subset of the plurality of reamer portions A-D can be fixedly coupled to each other to define the reamer **320D** body. The distal reamer portion A can have a rotatable coupling **323D** (e.g., a bearing connec-

tion, such as a rolling element bearing, a boss, etc.) at the distal end **322D** that can engage an elongate element, such as the elongate element **310**, **310B** in FIGS. **3-4**. Each of the plurality of reamer portions A-D can have a connector (e.g., female coupling) **328D** at its proximal end, which can receive a similarly shaped end of the shaft **410** that can be chucked to a driving element (e.g., a drill). Each of the reamer portions A-D can have a tapered cone outer surface **326D** so that when two or more of the reamer portions A-D are sequentially nested, the outer surface of the reamer **320D** defines a tapered cone surface. Each of the reamer portions A-D can also have milling elements **327D** (e.g., ridges, edges) that align with each other when two or more of the plurality of reamer portions A-D are sequentially stacked together.

The plurality of reamer portions A-D advantageously fixedly couple to each other so that when two or more of the plurality of reamer portions A-D are nested together to define the reamer **320D** structure they move as one piece (e.g., they rotate together). For example, the plurality of reamer portions A-D can each have one or more pins at a distal end that extend into one or more holes in a proximal end of an adjacent reamer portion. In another embodiment, each of the reamer portions A-D can each have one or more holes at a distal end that receive corresponding one or more pins in a proximal end of an adjacent reamer portion.

In use, the orthopedic surgeon could begin by using a first reamer portion (e.g., reamer portion A) to ream a cavity in a bone (e.g., in the proximal end **22** of the tibia **20**). If the surgeon determined that a cavity needed to be larger, the surgeon could couple a second reamer portion (e.g., reamer portion B) onto the proximal end of the previously used reamer portion A to increase the size of the reamer **320D**, and operate the reamer **320D** (e.g., via a drill that operatively drives the reamer **320D**) to create the larger cavity size. The surgeon could continue the process of nesting additional reamer portions onto the previously delivered reamer portions A-B, to create a cavity of the desired size in the bone.

FIG. **8** shows an embodiment of a reamer **320E** that is similar to the reamer **320C**, in FIGS. **6A-6B**, except as described below. The reamer **320E** is constructed similar to the reamer **320C** shown in FIGS. **6A-6B**, except as noted below. Therefore, the references numerals used to designate the various features of the reamer **320E** are identical to those used for identifying the corresponding features of the reamer **320C** in FIGS. **6A-6B**, except that an "E" has been added to the reference numerals. FIG. **8** shows a reamer **320E** that has a tapered cone shape from the proximal end to the distal end. Once the drill **400** is disconnected from the reamer **320E**, a top segment of the proximal end can be removed to define the tapered cone with the cutout **321E**. Additionally, the top segment can be textured or colored, so the user can see where the cut-out is on each cut-out cone reamer.

In the illustrated embodiment, the reamer **320E** can include one or more nested reamer portions A'-D', each having a proximal cutout portion A1'-D1' that can be sequentially coupled to each other to define the reamer body **320E** with a proximal cutout **321E**. Though FIG. **8** shows the reamer **320E** with four reamer portions A'-D', one of skill in the art will recognize that the reamer **320E** can have any number of reamer portions A'-D', where at least a subset of the plurality of reamer portions A'-D' can be fixedly coupled to each other to define the reamer **320E** body. The distal reamer portion A' can have a rotatable coupling **323E** (e.g., a bearing connection, such as a rolling element bearing, a boss, etc.) at the distal end **322E** that can engage an elongate element, such as the elongate element **310**, **310B** in FIGS.

3-4. Each of the plurality of reamer portions A'-D' can have a connector (e.g., female coupling) **328E** at its proximal end, which can receive a similarly shaped end of the shaft **410** that can be chucked to a driving element (e.g., a drill). Each of the reamer portions A'-D' can define a portion of a tapered cone outer surface **326E** (except where the reamer portion A'-D' has the cutout) so that when two or more of the reamer portions A'-D' are sequentially nested, the outer surface of the reamer **320E** defines a tapered cone surface with a proximal cutout. Each of the reamer portions A'-D' can also have milling elements **327E** (e.g., ridges, edges) that align with each other when two or more of the plurality of reamer portions A'-D' are sequentially stacked together.

The plurality of reamer portions A'-D' advantageously fixedly couple to each other so that when two or more of the plurality of reamer portions A'-D' are nested together to define the reamer **320E** structure they move as one piece (e.g., they rotate together). For example, the plurality of reamer portions A'-D' can each have one or more pins at a distal end that extend into one or more holes in a proximal end of an adjacent reamer portion. In another embodiment, each of the reamer portions A'-D' can each have one or more holes at a distal end that receive corresponding one or more pins in a proximal end of an adjacent reamer portion.

In use, the orthopedic surgeon could begin by using a first reamer portion (e.g., reamer portion A') to ream a cavity in a bone (e.g., in the distal end **12** of the femur **10**). If the surgeon determined that a cavity needed to be larger, the surgeon could couple a second reamer portion (e.g., reamer portion B') onto the proximal end of the previously used reamer portion A' to increase the size of the reamer **320E**, and operate the reamer **320E** (e.g., via a drill that operatively drives the reamer **320E**) to create the larger cavity size. The surgeon could continue the process of nesting additional reamer portions onto the previously delivered reamer portions A'-B', to create a cavity of the desired size in the bone.

As with the reamer **320C**, the cutout **321E** of the reamer **320E** allows it to accommodate (e.g., to not impinge on) the implant (e.g., the femoral knee implant) when implant is coupled to the reamer **320E** component.

FIG. **9** is an end view of a cut proximal end **22'** of the tibia **20** into which the reamer **320**, **320B**, **320D** has been inserted. In one embodiment, the proximal end **324**, **324B**, **324D** of the reamer **320**, **320B**, **320D** can be generally flush with the proximal surface of the cut tibia **20**. Advantageously, the outer perimeter O of the reamer **320**, **320B**, **320D** is generally circular and bounded by an outer boundary of cut proximal end **22'** of the tibia **20**.

FIG. **10** is an end view of a cut distal end **12'** of the femur **10** into which the reamer **320C**, **320E** has been inserted. In one embodiment, the proximal end **324C**, **324E** of the reamer **320C**, **320E** can be generally flush with the distal surface **12'** of the cut femur **10**. Advantageously, the outer perimeter O of the reamer **320C**, **320E** is generally bounded by an outer boundary of cut distal end **12'** of the tibia **20**. In the illustrated embodiment, the vertical surface **321C1** of the cutout **321C**, **321E** faces the anterior side of the distal end **12** of the femur **10**.

FIG. **11A** shows a schematic exploded view of a distal end **12** of the femur **10** with the reamer **320C**, **320E** inserted therein, prior to attachment of a trial implant **500** on the distal end **12**. Once the reamer **320C**, **320E** has been inserted into the distal end **12** of the femur to form the desired cavity (e.g., conical cavity), a cutting guide **600** (see FIG. **11B**) can be attached to the proximal end **324C**, **324E** of the reamer **320C**, **320E** to cut the femur **10** flush with one or more surfaces of the reamer **320C**, **320E**. The trial implant **500** can

then be attached to the reamer 320C, 320E to define the trial implant assembly 500', as shown in FIG. 12. The trial implant 500' can be coupled with the reamer 320C, 320E in any suitable manner (e.g., with bone cement, with one or more screws, with a spline or other mechanical attachment, slot-key connection, tapered connection, etc.). Advantageously, as seen in FIGS. 11A, 12, the cut out portion 321C, 321E of the reamer 320C, 320E allows the trial implant 500 to be coupled with the proximal end 324C, 324E of the reamer 320C, 320E without impinging on the trial implant 500.

FIG. 13 shows a schematic front view of the distal end 12 of the femur 10 with the trial implant assembly 500', which includes the trial implant 500, the reamer 320C, 320E and the elongate shaft or stem 310, 310B. The trial implant 500 for the femur 10 can define a pair of condyle surfaces 502, 504 and an anterior surface 506 that extends in front of at least a portion of the cut distal end 12 of the femur 10. As discussed above, the trial implant 500 can couple to the reamer 320C, 320E in any suitable manner (e.g., using screws, a spline connection, tapered connection, cement, slot and key connection, press-fit connection, etc.).

FIG. 14 shows a schematic front view of the distal end 22 of the tibia 20 with a trial implant assembly 510', which includes a trial implant 510, the reamer 320A, 320B, 320D and the elongate shaft or stem 310, 310B. The trial implant 510 for the tibia 20 can extend over at least a portion of the cut proximal end 22 of the tibia 20 and can define an articulating surface 512 that can contact the condyle surfaces 502, 504 of the trial implant 500 of the femur 10. As discussed above, the trial implant 510 can couple to the reamer 320A, 320B, 320D in any suitable manner (e.g., using screws, a spline connection, a tapered connection, cement, slot and key connection, press-fit connection, etc.).

FIG. 15 shows one embodiment of an assembly 700 for removing an implant assembly, as further discussed below. For simplicity, the elongate shaft and implant body, as well as the bone (e.g., femur 10, tibia 20) that the implant is located in is not shown in FIG. 15. The implant assembly includes a tapered cone body 820 similar in shape to the reamer 320A, 320B, 320D described above. In one embodiment, the tool 710 is a drill bit. In another embodiment, the tool 710 is a burr. In still another embodiment, the tool 710 is a router. The distal end 712 can have a length L that is at least as great as a height X of the tapered cone body 820. The tool 710 can be inserted between the outer surface 826 of the tapered cone body 820 and the bone, and the tool 710 can be operated (e.g., rotated about its axis) to detach or pry loose the tapered cone body 820 from the bone.

With continued reference to FIG. 15, the tool 710 can be inserted at an angle α_1 that substantially coincides (e.g., is identical to) the angle α_2 of the tapered cone body 820. A proximal end 716 of the tool 710 can be supported at the angle α_1 by a support 730 that connects the tool 710 to a shaft S attached to a proximal end 824 of the tapered cone body 820 by a connector 828. The tool 710 can optionally be operated manually. In another embodiment, the tool 710 can be operated by a power tool such as a drill 410 that couples to the proximal end 716 of the tool 710.

Though FIG. 15 shows a tapered cone body 820 that is generally similar in size and shape with the reamer 320A, 320B, 320D, the implant assembly can instead have a tapered cone body with a cutout 820' that is similar in size and shape as the reamer 320C, 320E described above.

FIG. 16 shows an embodiment of a kit K1 for assembling a tibial trial implant assembly 510' and a femoral trial implant assembly 500'. The kit K1 can include a plurality of

elongate members 310, 310B of various sizes S1-S4, a plurality of tapered cone reamers 320-320E of different sizes A-D, and a plurality of tibial trial implants 510 and femoral trial implants 500 of different sizes I1-I4. The surgeon would utilize the kit K1 to assemble the desired trial implant assembly 500', 510' for the femur and tibia, using different sized components, as needed to achieve the desired fit for the trial implant, as described further below in connection with FIG. 17. Once the surgeon obtained the desired trial implant assembly 500', 510', the surgeon could then assemble the final implant assemblies 900', 910' for the femur and tibia utilizing a similar kit K2 with similarly sized components for the elongate shaft 810, tapered cone body 820 and implant 900,910. Accordingly the different sizes of the components of the trial implant assembly 500, 510' correlate with the different sizes of the components of the final implant assembly 900, 910', simplifying the process of assembling the final implant assembly based on the trial implant assembly 500, 510' the surgeon determined was the appropriate one for the patient.

FIG. 17 is a block diagram of a method 1000 of installing a total knee implant. The knee implant can include a femoral implant assembly 900 and a tibial implant assembly 910 that are implanted into the distal femur and the proximal tibia, respectively. The process below is described with respect to implanting the tibial implant assembly 910 on the tibia 20. However, a similar process is used to implant the femoral implant assembly 910, except that the tapered cone reamer with the cutout 320C, 320E is used, and a similarly shaped tapered cone body 820' is implanted once the trial implant assembly is removed.

At block 1010, the surgeon could use a straight reamer to ream a straight cavity in the bone (e.g., the tibia 20 or femur) and then it is taken out. If the straight reamer does not point at the ankle for the tibial implant or hip for the femoral implant (e.g., has an offset of 1 to 12 degrees from vertical), the surgeon would utilize a 1 to 12 degree adapter with the straight reamer to orient the proximal tibia to the ankle or distal femur to the hip.

At block 1020, the surgeon assembles the elongate shaft 310, 310B to the reamer 320A, 320B, 320D and inserts it into the straight cavity formed by the straight reamer. The elongate shaft 310, 310B provides angular orientation, while the reamer 320A, 320B, 320D provides rotational and axial stability (e.g., via the ridges 327A, 327B, 327D on its outer surface 326A, 326B, 326D). The elongate shaft 310 in one embodiment has a smaller outer diameter (e.g., 1-2 mm smaller) than the straight reamer to ensure the elongate shaft 310 is easily delivered into the straight cavity (e.g., does not get caught in the bone during insertion). The surgeon then proceeds to ream the proximal end 22 of the tibia 20 to ream the tapered cone shape cavity so that it points perpendicular to the ankle, or ream the distal end 12 of the femur 10 to ream the tapered cone shape cavity so that it points substantially perpendicular to the hip. The surgeon would continue to ream the cavity in the tibia 20 or femur until the desired size cavity was obtained (e.g., when sufficient bony opposition and cortical contact is obtained). For example, if using the modular reamer 320D, the surgeon can continue to sequentially nest reamer portions A-D of increasing size to obtain a larger tapered cone reamer body and form a larger tapered cone cavity in the tibia 20. As discussed above, the proximal end of the reamer 310A, 310B, 310D can be coupled to a shaft that is chucked to a drill 400, which can be operated to rotate the reamer 310A, 310B, 310D, without

rotating the elongate shaft **310**, **310B** due to the rotatable (e.g., bearing) connection between the elongate shaft **310**, **310B**, **310D** and the reamer.

At block **1030**, the surgeon can disconnect the drill **400** from the proximal end **324A**, **324B**, **324C** of the reamer **320A**, **320B**, **320D** once the desired tapered cavity is achieved in the tibia **20**, leaving the elongate shaft **310**, **310B** and the reamer **320A**, **320B**, **320D** in place in the tibia **20**.

At block **1040**, the surgeon can connect a cutting guide **600** to the reamer **320A**, **320B**, **320D** and cut the tibia **20** flush to the proximal end **324A**, **324B**, **324D** of the reamer **320A**, **320B**, **320D**.

At block **1050**, the surgeon can disconnect the cutting guide **600** from the reamer **320A**, **320B**, **320D** and connect the tibial trial implant **510** to define the trial implant assembly **510'**. The surgeon would then determine if the trial implant assembly **510'** meets his or her requirements for the tibial portion of the knee implant or requires further changes (e.g., requires a larger sized trial tibial implant **510**). For example, the position and size of the trial implant assembly **510'** can be adjusted until a well-balanced knee joint is achieved.

At block **1060**, once the surgeon determines that the tibial trial implant assembly **510'** meets the requirements for the tibial portion of the knee implant, the surgeon would remove the trial implant assembly **510'** (e.g., the tibial trial implant **510**, reamer **320A**, **320B**, **320D** and elongate shaft **310**, **310B**) from the tibia **20**.

At block **1070**, the surgeon would assemble the final tibial implant assembly **910'**, which would have an elongate shaft **810**, a tapered cone **820**, and a tibial implant **910**. The final tibial implant assembly **910'** can be assembled in multiple pieces but is inserted into the cavity in the tibia **20** in one piece. The elongate shaft **810** would provide axial stability, while the tapered fluted or porous cone **820** can provide rotational stability (e.g., via one or more ridges that engage the bone in the cavity, such as the diaphysis).

The final tibial implant assembly **910'** is similar (e.g. identical) in shape and size as the tibial trial implant assembly **510'**. For example, the elongate shaft **810** can be similar (e.g. identical) in size and shape to the elongate shaft **310**, **310B**. Similarly, the tapered cone **820** can be similar (e.g. identical) in shape and size as the reamer **320A**, **320B**, **320C**. Finally, the tibial implant **910** can be similar (e.g., identical) in size and shape as the tibial trial implant **510**. The final tibial implant assembly **910'** can differ from the tibial trial implant assembly **510'** in the quality of the materials used. The surgeon can fix the final implant assembly **910'** in the tibia **20** utilizing any suitable method (e.g., cementing the implant assembly **910'** in the bone).

Advantageously, the size of each of the elongate shaft **310**, **310B**, the reamer **320A**, **320B**, **320D** and the tibial implant **510** correspond to similarly sized elongate shaft **810**, tapered cone **820** and tibial implant **910**. Moreover, the elongate shaft **310**, **310B**, reamer **320A**, **320B**, **320D** and tibial implant **510** can be provided in multiple sizes, allowing the surgeon to assemble a trial implant assembly **510'** with different sized components to achieve the desired operation from the trial implant assembly **510'**. Accordingly, utilizing the trial implant assembly **510'** to determine the desired implant arrangement simplifies the implantation process as the surgeon can then assemble the final implant with a similarly sized elongate shaft, tapered cone and implant body as the trial implant assembly **510'**.

Though the method **1000** described in the steps of FIG. **16** has been described with respect to the tibial implant assembly **910'** one or skill in the art will recognize that substan-

tially the same process can be used for the implantation of the femoral implant assembly **900'**. However, for the femoral implant, the reamer **320C**, **320E** is used instead of the reamer **320A**, **320B**, **320D** to provide the cutout **321C**, **321E** to accommodate the femoral trial implant **500** thereon, as previously described.

FIG. **18** shows one embodiment of a method **1100** for removing a pre-existing implant assembly. To simplify the description, the method **1100** will be described for the removal of a previously implanted tibial implant assembly **910'** having a shape and size as described herein. However, one of skill in the art will recognize that a substantially similar process can be utilized to remove a previously implanted femoral implant assembly **900'** having a shape and size as described herein.

At step **1110**, the surgeon could decouple the tibial implant **910** from the tapered cone **820**.

At step **1120**, the surgeon could attach the tool **710** of the removal assembly **700** to a shaft **S** and couple the shaft **S** to the tapered cone **820** so that the tool **710** extends at substantially the same angle as the angle of the tapered cone.

At step **1130**, the surgeon could introduce the tool **710** between the outer surface **826** of the tapered cone **820** and the bone, as illustrated in FIG. **15**.

At step **1140**, the surgeon could operate the tool **710** (e.g. with a drill **400**) and rotate the tool **710** about the circumference of the tapered cone **820** to disengage it from the bone about its periphery.

At step **1150**, the surgeon could remove the tapered cone **820** and the elongate shaft **810** from the tibia **20**, and proceed to prepare the cavity for the implantation of a new tibial implant assembly **910'**.

Advantageously, because it is only the tapered cone **820** that provides rotational stability to the tibial implant assembly **910'**, is the portion of the implant assembly **910'** that is rotationally fixed to the tibia, and sits at the proximal portion of the tibial implant assembly **910'**, the tool **710** does not need to be inserted to the distal end of the tibial implant assembly **910'**, but rather only needs to be extended to the distal end **822** of the tapered cone **820**, which makes removal of the previously implanted tibial implant assembly **910'** much easier and efficient to perform, and takes less time than if the rotational stability was also provided along a stem portion of the implant.

Accordingly, in the embodiments described herein, the height of the reamer **320-320E** in the trial implant assembly **500'**, **510'** and corresponding tapered cone **820** in the final implant assembly **900'**, **910'** are the only portions that are rotationally fixed in the bone (femur **10**, tibia **20**). The elongate shaft **310**, **310B** in the trial implant assembly **500'**, **510'** and elongate shaft **810** in the final implant assembly **900'**, **910'** is not rotationally fixed in the bone (rather, it provides axial stability), so that the elongate shaft **310**, **310B**, **820** need not be dislodged from the bone by inserting a tool **710** to the distal end of the elongate shaft **310**, **310B**, **820**. Accordingly, the tapered cone reamer **320-320E** and tapered cone body **820** only define a proximal portion of the trial implant assembly **500'**, **510'** and final implant assembly **900'**, **910'**. That is, the height or length of the tapered cone reamer **320-320E** of the trial implant assembly **500'**, **510'** and tapered cone body **820** of the final implant assembly **900'**, **910'** provide a relatively small amount to the length of the trial implant assembly **500'**, **510'** and final implant assembly **900'**, **910'** relative to the length of the other components (e.g., elongate shaft **310**, **310B**, **810**). In one embodiment, the height or length of the tapered cone reamer **320-320E** of the trial implant assembly **500'**, **510'** and tapered

cone body **820** of the final implant assembly **900'**, **910'** is less than $\frac{1}{2}$ the length of the trial implant assembly **500'**, **510'** and final implant assembly **900'**, **910'**, respectively. In another embodiment, the height or length of the tapered cone reamer **320-320E** of the trial implant assembly **500'**, **510'** and tapered cone body **820** of the final implant assembly **900'**, **910'** is less than $\frac{1}{3}$ the length of the trial implant assembly **500'**, **510'** and final implant assembly **900'**, **910'**, respectively. In still another embodiment, the height or length of the tapered cone reamer **320-320E** of the trial implant assembly **500'**, **510'** and tapered cone body **820** of the final implant assembly **900'**, **910'** is less than $\frac{1}{4}$ the length of the trial implant assembly **500'**, **510'** and final implant assembly **900'**, **910'**, respectively.

While certain embodiments of the inventions have been described, these embodiments have been presented by way of example only, and are not intended to limit the scope of the disclosure. Indeed, the novel methods and systems described herein may be embodied in a variety of other forms. Furthermore, various omissions, substitutions and changes in the systems and methods described herein may be made without departing from the spirit of the disclosure. For example, one portion of one of the embodiments described herein can be substituted for another portion in another embodiment described herein. The accompanying claims and their equivalents are intended to cover such forms or modifications as would fall within the scope and spirit of the disclosure. Accordingly, the scope of the present inventions is defined only by reference to the appended claims.

Features, materials, characteristics, or groups described in conjunction with a particular aspect, embodiment, or example are to be understood to be applicable to any other aspect, embodiment or example described in this section or elsewhere in this specification unless incompatible therewith. All of the features disclosed in this specification (including any accompanying claims, abstract and drawings), and/or all of the steps of any method or process so disclosed, may be combined in any combination, except combinations where at least some of such features and/or steps are mutually exclusive. The protection is not restricted to the details of any foregoing embodiments. The protection extends to any novel one, or any novel combination, of the features disclosed in this specification (including any accompanying claims, abstract and drawings), or to any novel one, or any novel combination, of the steps of any method or process so disclosed.

Furthermore, certain features that are described in this disclosure in the context of separate implementations can also be implemented in combination in a single implementation. Conversely, various features that are described in the context of a single implementation can also be implemented in multiple implementations separately or in any suitable subcombination. Moreover, although features may be described above as acting in certain combinations, one or more features from a claimed combination can, in some cases, be excised from the combination, and the combination may be claimed as a subcombination or variation of a subcombination.

Moreover, while operations may be depicted in the drawings or described in the specification in a particular order, such operations need not be performed in the particular order shown or in sequential order, or that all operations be performed, to achieve desirable results. Other operations that are not depicted or described can be incorporated in the example methods and processes. For example, one or more additional operations can be performed before, after, simul-

taneously, or between any of the described operations. Further, the operations may be rearranged or reordered in other implementations. Those skilled in the art will appreciate that in some embodiments, the actual steps taken in the processes illustrated and/or disclosed may differ from those shown in the figures. Depending on the embodiment, certain of the steps described above may be removed, others may be added. Furthermore, the features and attributes of the specific embodiments disclosed above may be combined in different ways to form additional embodiments, all of which fall within the scope of the present disclosure. Also, the separation of various system components in the implementations described above should not be understood as requiring such separation in all implementations, and it should be understood that the described components and systems can generally be integrated together in a single product or packaged into multiple products.

For purposes of this disclosure, certain aspects, advantages, and novel features are described herein. Not necessarily all such advantages may be achieved in accordance with any particular embodiment. Thus, for example, those skilled in the art will recognize that the disclosure may be embodied or carried out in a manner that achieves one advantage or a group of advantages as taught herein without necessarily achieving other advantages as may be taught or suggested herein.

Conditional language, such as “can,” “could,” “might,” or “may,” unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include, while other embodiments do not include, certain features, elements, and/or steps. Thus, such conditional language is not generally intended to imply that features, elements, and/or steps are in any way required for one or more embodiments or that one or more embodiments necessarily include logic for deciding, with or without user input or prompting, whether these features, elements, and/or steps are included or are to be performed in any particular embodiment.

Conjunctive language such as the phrase “at least one of X, Y, and Z,” unless specifically stated otherwise, is otherwise understood with the context as used in general to convey that an item, term, etc. may be either X, Y, or Z. Thus, such conjunctive language is not generally intended to imply that certain embodiments require the presence of at least one of X, at least one of Y, and at least one of Z.

Language of degree used herein, such as the terms “approximately,” “about,” “generally,” and “substantially” as used herein represent a value, amount, or characteristic close to the stated value, amount, or characteristic that still performs a desired function or achieves a desired result. For example, the terms “approximately,” “about,” “generally,” and “substantially” may refer to an amount that is within less than 10% of, within less than 5% of, within less than 1% of, within less than 0.1% of, and within less than 0.01% of the stated amount. As another example, in certain embodiments, the terms “generally parallel” and “substantially parallel” refer to a value, amount, or characteristic that departs from exactly parallel by less than or equal to 15 degrees, 10 degrees, 5 degrees, 3 degrees, 1 degree, or 0.1 degree.

The scope of the present disclosure is not intended to be limited by the specific disclosures of preferred embodiments in this section or elsewhere in this specification, and may be defined by claims as presented in this section or elsewhere in this specification or as presented in the future. The language of the claims is to be interpreted broadly based on the language employed in the claims and not limited to the

15

examples described in the present specification or during the prosecution of the application, which examples are to be construed as non-exclusive.

What is claimed is:

1. A modular system for total knee arthroplasty, comprising:

a modular trial implant assembly comprising

an elongate shaft configured for insertion into an elongate cavity in a bone;

a reamer that extends between a proximal end and a distal end, the reamer being removably coupleable to a proximal end of the elongate shaft via a connection that allows the reamer to rotate relative to the elongate shaft while the elongate shaft remains in a substantially fixed angular orientation, the reamer having an outer surface that tapers toward the distal end of the reamer, the outer surface further having a plurality of milling elements extending between the proximal and distal ends of the reamer about the circumference of the reamer, the milling elements configured to form a tapered cavity in an end of a bone in which the reamer is inserted and rotated; and a trial implant removably coupleable to a proximal end of the reamer,

wherein the elongate shaft comprises a smooth outer surface to provide angular orientation but not rotational stability when inserted into the elongate cavity, and wherein the plurality of milling elements of the outer surface of the reamer is configured to provide rotational and axial stability in the tapered cavity.

2. The system of claim 1, wherein the elongate shaft has a shape consisting of one of a cylindrical shape with a circular transverse cross-section, a conical shape with a circular transverse cross-section with decreasing area toward a distal end of the elongate shaft.

3. The system of claim 1, wherein the reamer has a tapered cone shape.

4. The system of claim 1, wherein the reamer comprises a cutout at the proximal end to accommodate the coupling of the trial implant onto the proximal end of the reamer without impinging on the trial implant, the reamer defining a tapered cone shape with a proximal cutout.

5. The system of claim 1, wherein the connection comprises a bearing.

6. The system of claim 1, wherein the elongate shaft is configured to extend substantially parallel to an axis of the femur or tibia in which it is inserted.

7. The system of claim 1, wherein the elongate shaft is configured to extend at an angle relative to an axis of the femur or tibia bone in which it is inserted, where the bone is s-shaped or to account for normal anatomy of the distal femur including variations of the anatomic axis in the coronal plane and femoral bow in the sagittal plane.

8. The system of claim 1, further comprising a final implant assembly, at least a portion of the final implant assembly comprising at least a portion of a tapered conical body.

9. The system of claim 8, wherein the final implant assembly further comprises an elongate stem, and wherein one or both of the elongate stem and the tapered conical body has an outer surface that consists of one of a fluted surface and a porous surface.

10. A modular kit for total knee arthroplasty, comprising: a plurality of elongate shafts configured for insertion into an elongate cavity in a femur or tibia bone, each of the

16

elongate shafts differing in one or both of length and outer diameter, each of the elongate shafts comprising a smooth outer surface;

a plurality of tapered conical reamers differing in one or both of length and maximum outer diameter, each of the tapered conical reamers having an outer surface with a plurality of milling elements extending about the circumference of the tapered conical reamer; and

a plurality of trial implants of different sizes,

wherein each of the trial implants is coupleable to a proximal end of each of the tapered conical reamers, which is coupleable to a proximal end of each of the elongate shafts to assemble a trial implant assembly, the reamer being removably coupleable to the proximal end of the elongate shafts via a connection that allows the tapered conical reamer to rotate relative to the elongate shaft while the elongate shaft remains in a substantially fixed angular orientation.

11. The modular kit of claim 10, wherein each of the elongate shafts has a shape consisting of one of: a cylindrical shape with a circular transverse cross-section, a conical shape with a circular transverse cross-section with decreasing area toward a distal end of the elongate shaft.

12. The modular kit of claim 10, further comprising:

a plurality of elongate stems having a circular transverse cross-section, each of the elongate stems differing in one or both of length and outer diameter;

a plurality of tapered cone bodies differing in one or both of length and maximum outer diameter; and

a plurality of implants of different sizes, wherein each of the implants is coupleable to a proximal end of each of the tapered cone bodies, which is coupleable to a proximal end of each of the elongate stems, and wherein a final implant assembly is defined by one of the plurality of implants assembled together with one or more of one of the plurality of elongate stems or at least a portion of one of the plurality of tapered cone bodies.

13. The modular kit of claim 12, wherein the plurality of elongate stems, plurality of tapered cone bodies and plurality of implants substantially correspond in size and shape with the plurality of elongate shafts, plurality of tapered reamers and plurality of trial implants, respectively.

14. The modular kit of claim 12, wherein at least one of the plurality of tapered cone bodies and at least one of the plurality of elongate stems has an outer surface that consists of one of a fluted surface and a porous surface.

15. The modular kit of claim 10, wherein each of the reamers comprises a cutout at the proximal end of each of the reamers to accommodate the coupling of each of the trial implants onto the proximal ends of each of the reamers without impinging on each of the trial implants, each of the reamers defining at least in part a tapered cone shape with a proximal cutout.

16. The modular kit of claim 12, wherein each of the tapered cone bodies comprises a cutout at a proximal end to accommodate the coupling of each of the implants onto the proximal end of each of the tapered cone bodies without impinging on each of the implants.

17. The modular kit of claim 10, wherein each of the reamers comprises a plurality of sequentially nestable portions releasably coupleable with each other to define the tapered shape, where a maximum outer diameter of the tapered shape is defined by the last of the sequentially nestable portions that are coupled to each other, the plurality of sequentially nestable portions configured to rotate as a single unit when assembled together.

18. The modular kit of claim 17, wherein each of the sequentially nestable portions has a tapered cone shape with a proximal cutout so that each of the assembled reamer defines a tapered cone shape with a proximal cutout.

19. The modular kit of claim 10, wherein the connection 5 comprises a bearing.

20. The modular kit of claim 10, wherein each of the elongate shafts is configured to extend substantially parallel to an axis of the femur or tibia in which it is inserted.

21. The modular kit of claim 10, wherein each of the 10 elongate shafts is configured to extend at an angle relative to an axis of the femur or tibia bone in which it is inserted, where the bone is s-shaped or to account for normal anatomy of the distal femur including variations of the anatomic axis in the coronal plane and femoral bow in the sagittal plane. 15

22. In combination with a modular trial implant assembly including an elongate shaft with a smooth outer surface, a tapered conical reamer rotatably coupleable to the shaft, an outer surface of the tapered conical reamer comprising 20 milling elements, and a trial implant removably coupleable to the reamer, a final implant assembly comprising:

an implant body, and

a tapered body, at least a portion of the tapered body having a conical shape substantially corresponding to a conical shape of the tapered conical reamer. 25

23. The system of claim 22, wherein the final implant assembly further comprises an elongate stem.

* * * * *