

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 898 771 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:

04.09.2002 Bulletin 2002/36

(21) Application number: **97935552.6**

(22) Date of filing: **30.07.1997**

(51) Int Cl.7: **G08B 29/18**

(86) International application number:
PCT/EP97/04142

(87) International publication number:
WO 98/028724 (02.07.1998 Gazette 1998/26)

(54) **AN ELECTRONIC INTRUSION DETECTION SYSTEM FOR MONITORED ENVIRONMENTS**

ELEKTRONISCHES EINDRINGALARMSYSTEM FÜR ÜBERWACHTE UMGEBUNGEN

SYSTEME ELECTRONIQUE DE DETECTION D'INTRUSION DESTINE A DES ENVIRONNEMENTS
SURVEILLES

(84) Designated Contracting States:

**AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC
NL PT SE**

(30) Priority: **24.12.1996 IT TO961080**

(43) Date of publication of application:
03.03.1999 Bulletin 1999/09

(73) Proprietor: **Tecno Alarm S.N.C.**
I-10156, Torino (IT)

(72) Inventors:

- **TRUCCHI, Luciano**
I-10156 Torino (IT)
- **NEGRO, Giovanni**
I-10156 Torino (IT)

(74) Representative: **Robba, Pierpaolo et al**
Interpatent,
Via Caboto 35
10129 Torino (IT)

(56) References cited:
FR-A- 2 611 290

GB-A- 2 064 189

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

Technical Field

[0001] The present invention relates to an electronic intrusion detection system for environments to be monitored.

[0002] More particularly the invention is concerned with an electronic remote surveillance device adapted to be employed in combination with monitoring apparatuses, alarm systems, fire alarm devices, antitheft systems, etc.

[0003] In the field of the alarm and antitheft systems for protecting civil dwellings and industrial premises there are known monitoring systems that use Doppler or infrared volumetric sensors.

[0004] The volumetric sensors based on Doppler effect are substantially small-size radar devices operating in the microwaves spectrum, typically 1-10 GHz, capable of detecting a person moving even at an extremely low speed.

[0005] On the other hand the infrared volumetric sensors are sensors capable of detecting a temperature difference caused by the passage of a human body in the environment in which the sensors are located, but these sensors cannot detect mechanical vibrations.

[0006] In presence of a body moving inside the environment or the space to be monitored, the above mentioned volumetric sensors generate an electric signal that can be applied to a control circuit that in turn actuates alarm warning devices or other devices that draw attention to the event by means of acoustic and/or optical (visual) alarm messages.

Background Art

[0007] In remotely manned monitoring systems, the acoustic and/or visual signal generated by the sensor (s) is converted into an alarm message and generally transmitted through a radio link or on a telephone line, either public or private, to a receiving device that can be located far away from the monitored place at which the event detection occurred.

[0008] As an example, the alarm message can be sent either to a receiving device located in a central control unit manned by private personnel or by policemen, or to a fixed or mobile telephone set, furnished to the surveillance personnel or even to the owner of a house.

[0009] The alarm message received through said devices can incorporate information relating to the place at which the event took place, such as for example a predetermined recorded vocal message.

[0010] When the person in charge of the surveillance receives such alarm message from a monitored environment, he/she can either directly intervene or arrange for proper actions, such as for example the request for a police intervention.

[0011] One of the main inconveniences of the known

alarm systems using volumetric sensors that transmit alarm messages to a remote control unit is that the surveillance personnel - or more generally the person that receives such alarm message - is not in condition to discriminate a false alarm caused by a disturbance from a real alarm situation in which a quick intervention is required.

[0012] The likelihood of a false alarm is not an infrequent event in spite of the technical improvements to the conventional antitheft systems.

[0013] When infrared sensors are used in a monitoring system, many disturbing sources such as natural or artificial light sources, quick changes of temperature, e.g. caused by room convectors, sudden raise of the environment lighting due for example to the front lights of a passing car, are all capable of being detected by the sensors and generating (false) alarm signals. Moreover, the sensibility of infrared sensors decreases when the environment temperature increases.

[0014] When Doppler sensors are used, false alarms can be triggered by electromagnetic disturbs and by accidental movements of objects like a banging door or a falling flowerpot.

[0015] Because the alarm message received at the remote location does not contain information allowing the personnel in charge to decide with certainty whether it is due to a real or a false alarm, such monitoring systems suffer from several drawbacks, such as delayed interventions, or unnecessary interventions, with a reduction of the system reliability.

[0016] For example, upon receiving an alarm message through his mobile phone, the owner of a dwelling that is far from home has to decide whether to ask for an intervention, or inform the police, or simply disregard the message as a false alarm, only on the base of a generic alarm message he/she has received.

[0017] In the past several suggestions have been made in order to reduce the risk of false alarms, while attempting to still maintain the sensibility of the sensors high.

[0018] One of the suggestions was to adjust the threshold level of the sensors to different conditions of the environment disturbances, another provided for pulse counters that actuated an alarm signal only after receiving a predetermined number the sensor detections, more likely to be caused by the presence of an intruder moving within the protected enclosure.

[0019] Still another device provided for using a combination of Doppler and infrared sensors both of which had to be activated before an alarm message was generated.

[0020] However the above mentioned devices have not solved the problem of eliminating in the person receiving the alarm signal the uncertainty about its causes.

[0021] Namely it is known that alarm device are not free from faults and malfunctions that can generate false alarms. Therefore, in the useful life of any alarm system

a number of false alarms is to be considered as unavoidable.

[0022] Still with the aim of eliminating the uncertainty deriving from receiving an alarm signal, in the past there have been proposed devices that monitor the environment through a microphone or a television camera.

[0023] One of such devices is disclosed in FR-A-2 611 290 concerning an alarm device capable of transmitting an alarm message. The device illustrated and described in FR-A-2 611 290 comprises a volumetric sensor that upon being activated actuates a telephone dialing device the emits a predetermined stored number and transmits an alarm message through a telephone line.

[0024] At the end of the alarm message an environment hearing is started through a microphone that allows the remote listening of the sounds and noises within the monitored space.

[0025] However, the remote listening through microphones requires the installation of additional devices in the rooms to be monitored and does not allow the listening of low intensity noises, such as those caused by slow movements.

[0026] Moreover the background noise - due for example to the street traffic or to sound diffusing devices, such as radio and TV sets - is a strong source of disturbance to the remote listening through microphones, and can make impossible to distinguish between such noises and low intensity sounds caused by an intruder moving in the environment to be monitored.

[0027] A severe drawback to using microphones is set by law restrictions to environmental listening in force in some countries such as France, and anyhow such listening can be prolonged beyond given time limits.

[0028] The use of television cameras for visually monitoring at distance provides for a good perception of what is happening within the camera field of view, but at a very high cost, since at least one camera has to be installed in each of the rooms to be monitored, and the system further requires a receiving apparatus equipped with monitor(s) to display the images.

Objects of the Invention

[0029] It is therefore an object of the present invention to realize an intrusion detection system capable of solving the technical problem of the uncertainty about the nature of an alarm message, such system being free from the above mentioned shortcomings of the prior art devices.

[0030] A further object of the present invention is to realize an intrusion detection system that is both reliable and easy and inexpensive to install and to use.

Disclosure of the Invention

[0031] The above objects of the present invention are achieved through an intrusion detection system as claimed in claim 1.

[0032] Further objects of the invention are accomplished through an intrusion detection system as claimed in the dependent claims.

5 Brief description of the Drawing

[0033] The intrusion detection system of the present invention will be disclosed in detail with reference to the attached Figure that shows a block diagram illustrating a preferred but non limiting embodiment of the invention.

Detailed Description of Preferred Embodiments

[0034] In the block diagram of the attached Figure there are illustrated the main components of an intrusion detection system in accordance with the teachings of the present invention. The system generally comprises a number of volumetric sensors 1a, 1b, 1c that can be positioned in the environment(s) to be monitored in accordance with different patterns, such as one sensor for each room or two or more properly arranged sensors inside each (or a single) room to be monitored to increase the area kept under surveillance, in accordance with known techniques.

[0035] The volumetric sensors 1a, 1b and 1c can be either infrared sensors or sensors detecting the frequency shift caused by Doppler effect, hereinafter referred to as Doppler sensors.

[0036] When a human body passes through their detection range, infrared sensors generates a change in their output voltage signal, whereas Doppler sensors generates a frequency change in the reflected signal (generated by a not shown source) that is proportional to the speed and to the direction of the movement.

[0037] The output signals from the volumetric sensors 1a, 1b and 1c are amplified by the analogical amplifiers 2a, 2b and 2c, the outputs of which are applied for further processing to the nodes or junction points 3a, 3b, 3c, respectively. More precisely, each node 3a, 3b, 3c is connected both to the input of an alarm generating circuit 10a, 10b and 10c, enclosed in a dashed box in the Figure, and to the input of a transducer or conversion circuit 20a, 20b and 20c, enclosed in a dash-and-point box in the Figure.

[0038] Each of the alarm circuits 10a, 10b and 10c outputs an alarm signal ALARM having a suitable voltage level when a predetermined alarm condition is met. In the illustrated embodiment of the invention, each of the alarm circuits 10a, 10b and 10c comprises a threshold detector (11a, 11b, 11c) connected a trigger circuit (12a, 12b, 12c) that actuates a relay (13a, 13b, 13c) or similar device that generates the alarm signal.

[0039] In the illustrated embodiment of the invention, the corresponding relay 13a (13b, 13c) that is actuated by the trigger circuit 12a (12b, 12c) driven by the threshold detector 11a (11b, 11c) supplies the alarm signal from said alarm circuit 10a (10b, 10c).

[0040] More precisely, when the signal level applied

to the alarm circuit 10a, 10b and 10c is higher than a predetermined threshold level, then the corresponding relay 13a, 13b and 13c switches from a rest condition to an alarm condition and enables an alarm signal or message to be transmitted to the respective alarm input 31a, 31b, 31c of an alarm control unit 30 through an alarm signal transmission line 14a, 14b, 14c.

[0041] Through the alarm inputs 31a, 31b, 31c, a multiplexer or switch 32, provided in the alarm control unit 30, receives an ALARM signal having a proper logic level, e.g. 5 V for indicating a logic one, and about 0 V for indicating a logic zero, this signal representing the state of the sensor 1a or 1b or 1c that generated the alarm signal.

[0042] In the illustrated embodiment the conversion or transducer circuit 20a, 20b and 20c comprises a voltage controlled oscillator or VCO 21a, 21b, 21c respectively, whose oscillation range is maintained in the (audio) frequency band from 300 Hz to 3,000 Hz corresponding to the telephone speech band, and a modulating circuit 22a, 22b, 22c respectively.

[0043] In such conversion circuit 20a (20b, 20c), the amplified signal from the volumetric sensor 1a (1b, 1c) is used to drive the voltage controlled oscillator or VCO 21a (21b, 21c) and the output audio-frequency signal from the VCO is modulated in a modulating circuit 22a (22b, 22c) before being transmitted, on a transmission line for audio signals 23a (23b, 23c), to a demodulator 33a (33b, 33c) provided in the control unit 30.

[0044] This way any modification of the electric output from the sensors 1a, 1b, 1c is continuously converted into an audio signal, i.e. a signal that can be perceived (in the present case, heard) by a human being. This audible signal is correlated with the monitored environment, i.e. contains information about what's happening within the monitored space. When the sensors are infrared sensors this audible signal is a sort of "audio" picture of the thermal pattern changing in the monitored space. When the sensors are Doppler sensors, this audible signal "represents" the motions occurring within the monitored space. In both cases the listener can easily distinguish the audio signals caused by an intrusion from those caused by disturbances, such as temporary phenomena or periodic sounds such as those produced by a banging door.

[0045] In the alarm control unit 30 the output (audio) signal from demodulator 33a, 33b, 33c is applied to a corresponding input channels 34 of the multiplexer 32 the output of which is connected to an audio amplifier 40.

[0046] Each of the input channels 34 to the multiplexer 32 can be enabled to reach the audio amplifier 40 by a logic address fed to one of the addressing inputs 35 of the multiplexer 32, connected to the outputs of the relay 13a, 13b, 13c, respectively.

[0047] Through the multiplexer 32, one or more of the multiplexed audio signals are applied to the audio amplifier 40 the output of which feeds a telephone dialing device 41 (actuated by the alarm message) for the trans-

mission on a public telephone line 43.

[0048] Through the public telephone network (not shown) the audio signals signal can be received by any selected telephone set 42 or equivalent receiving device available to the surveillance personnel.

[0049] More precisely, the alarm signal ALARM activates the telephone dialing device 41 for the setting up the connection with the receiving telephone set 42, and then the same signal enables the transmission along the telephone line 43 of an audio signal that is proportional to the activity detected by the volumetric sensor 1a, 1b, 1c.

[0050] This way it is possible to obtain a continuous monitoring of the movements that might occur in the environments under surveillance, regardless of the (background) noise generated therein.

[0051] According to an alternative embodiment, the above audio signal can be directly applied to a (not shown) loudspeaker disposed in the audible range of the surveillance personnel, such as for example the caretaker of a museum or other premises.

[0052] In accordance with another embodiment of the invention, not shown in the drawing, each signal generated by the volumetric sensors is converted into a form adapted to drive a display visible to the surveillance personnel, such as a CRT monitor, e.g. connected to the other end of the telephone line 43 and capable of visually representing the movements taking place in the monitored space, e.g. by changing the images shown. This way the watcher could get a graphic representation of the movements occurring in the monitored space. Such representation is not the visual display of a television camera, but is nevertheless capable of allowing an easy and positive discrimination between an intrusion and other phenomena.

[0053] In accordance with another embodiment of the invention, the signal generated by the volumetric (Doppler or infrared) sensor 1a (1b, 1c) is directly applied to the relay 13a (13b, 13c) which relay is generally incorporated in the same housing of the sensor. This embodiment is schematically shown in Fig. 1 by the dashed line connection between the output of amplifier 2a (2b, 2c) and the relay.

[0054] This way the signal to be modulated will be generated by the opening and closing in succession of the relay 13a (13b, 13c) driven by the volumetric sensor 1a (1b, 1c). The so obtained pulse signal has a period that is proportional to the relay opening/closing cycle, and therefore is representative of the detection activity of the volumetric sensor, but is more "clean" (that is contains less spurious signals) in respect of a signal directly coming from the sensor.

[0055] The above embodiment of the invention has further the advantage of a simpler construction since the transmission line 14a, 14b, 14c - provided for sending the ALARM signal - can be used also for transmitting the signal from the unit containing the volumetric sensor and the relay to the alarm control unit 30. The analysis

for detecting when the threshold has been exceeded (i. e. an alarm condition) will be carried out downward of the relays 13a, 13b, 13c, and more precisely in the alarm control unit 30, by verifying the signal from the volumetric sensor as mediated by the solid state relay 13. In this embodiment the relays 13a, 13b, 13c are advantageously formed by solid state relays that are more suitable to be continuously closed and opened at a high rate.

[0056] According to still another embodiment of the invention, the signal transmitted on audio transmission line 23a (23b, 23c) to the control unit 30 is continuously stored in a memory device provided for in this unit. Preferably, such memory device is a solid state memory capable of continuously storing an interval or "frame" of the signal. Preferably unit 30 will contain a plurality of memory devices, each one for storing the signal from one of the sensors located in the monitored environment.

[0057] According to this embodiment, the stored signal can be transmitted along the telephone line to the surveillance personnel immediately after the transmission of an ALARM signal that has warned the personnel of a possible alarm condition. Since the signal that caused the alarm has been stored, the surveillance personnel will have the additional possibility of listening to the signal - converted into audible form - that caused the alarm. However, once the stored signal has been transmitted, the system will start to transmit the current or real time signal so that the personnel can monitor what is happening in the monitored environment.

[0058] Through the disclosed device, the movements can be displayed even without triggering any alerting signal, by sequentially enabling the channels of multiplexer 32, either manually or electronically.

[0059] This way the surveillance personnel can listen to or look at the movements occurring in the monitored rooms, regardless of an alerting signal being generated or not, and regardless of the noise generated in the monitored room.

Industrial Applicability

[0060] The invention is applicable in the field of the alarm and antitheft systems for protecting civil dwellings and industrial premises from intrusion through a remote surveillance.

Claims

1. An electronic intrusion detection system for at least one monitored environment, comprising:

at least one electronic sensor (1a, 1b, 1c) responsive to movements occurring in said environment and capable of modifying at least one of the significant characteristics of its output

electric signal in response to the presence of a moving body in said monitored environment:

at least a first alarm circuit (10a, 10b, 10c) connected to said sensor and capable of generating an alarm signal (ALARM) when said modification meets a predetermined condition;
and an alarm control unit (30) adapted to receive said alarm signal (ALARM);

characterized in that said system comprises additional transducer means (20a, 20b, 20c) for continuously converting said modification of the output from said electric sensor (1a, 1b, 1c) into a signal that can be perceived by a human being, said perceivable signal being transmitted to said alarm control unit (30).

2. A system as claimed in claim 1, **characterized in that** said transducer means (20a, 20b, 20c) for continuously converting said modification of the output from the electric sensor (1a, 1b, 1c) into a signal that can be perceived by a human being comprises a frequency generator (21a, 21b, 21c) controlled by said modified characteristics of the electric output signal from said sensor (1a, 1b, 1c), and an acoustic transducer disposed in the audible range of the surveillance personnel.
3. A system as claimed in claim 2, **characterized in that** said frequency generator (21a, 21b, 21c) comprises an audio-frequency generator.
4. A system as claimed in claim 3, **characterized in that** said audio-frequency generator (21a, 21b, 21c) comprises a voltage controlled oscillator or VCO with the frequency of the signal generated by said oscillator (21a, 21b, 21c) being comprised between 300 and 3,000 Hz.
5. A system as claimed in the preceding claims, **characterized in that** said transducer means (20a, 20b, 20c) further comprises a modulating circuit 22a (22b, 22c).
6. A system as claimed in the preceding claims, **characterized in that** said alarm circuits (10a, 10b, 10c) are connected to said alarm control unit (30) by signal transmission lines (14a, 14b, 14c), and **in that** said said alarm control unit (30) comprises demodulating means (33a, 33b, 33c) and alarm inputs (31a, 31b, 31c).
7. A system as claimed in the preceding claims, **characterized in that** said alarm control unit (30) comprises a switching device or a multiplexer (32) having a plurality of input channels (34) each carrying

the audio-frequency signal obtained from one of said transducer means (20a, 20b, 20c), and a plurality of addressing inputs (35), each connected to one of said alarm inputs (31a, 31b, 31c) for enabling said switching means (32) to output the audio-frequency signals associated with an alarm signal.

8. A system as claimed in the preceding claims, **characterized in that** the output of said switching device (32) is connected to an amplifier (40) the output of which feeds a telephone dialing device (41) for the transmission of the alarm signals and the audio-frequency signals through a telephone line (43) to a receiving telephone set (42). 10
9. A system as claimed in the preceding claims, **characterized in that** said at least one sensor (1a, 1b, 1c) is selected from the group of infrared sensors, Doppler effect sensors or a combination thereof. 15
10. A system as claimed in the preceding claims, **characterized in that** the output of said the volumetric sensor (1a, 1b, 1c) is directly coupled to said relay (13a, 13b, 13c), whereby the signal to be modulated is generated by the opening and closing in succession of said relay (13a, 13b, 13c) driven by the signal from said volumetric sensor (1a, 1b, 1c). 20 25
11. A system as claimed in claim claim 10, **characterized in that** said relay (13a, 13b, 13c) is enclosed in the same unit housing said sensor (1a, 1b, 1c) and the signal from said unit is transmitted to the alarm control unit (30) along the same transmission line (14a, 14b, 14c) provided for sending said alarm signal (ALARM). 30 35
12. A system as claimed in the preceding claims, **characterized in that** the signal transmitted on said audio transmission line (23a (23b, 23c) to the control unit (30) is continuously stored in at least one memory device in said control unit (30). 40
13. A system as claimed in claim claim 12, **characterized in that** each of such memory devices is a solid state memory capable of continuously storing an interval or "frame" of the signal, and there is provided one memory device for storing the signal from each sensor located in the monitored environment. 45
14. A system as claimed in claim 1, **characterized in that** said transducer means (20a, 20b, 20c) for continuously converting said modification of the output from the electric sensor (1a, 1b, 1c) into a signal that can be perceived by a human being comprises a frequency generator (21a, 21b, 21c) controlled by said modified characteristics of the electric output signal from said sensor (1a, 1b, 1c), and a display visible to the surveillance personnel. 50 55

Patentansprüche

1. Elektronisches Intrusionsmeldesystem für zumindest eine überwachte Umgebung, umfassend:
 - zumindest einen elektronischen Sensor (1a, 1b, 1c), der auf Bewegungen reagiert, die in der Umgebung stattfinden, und der imstande ist, zumindest eines der signifikanten Merkmale seines elektrischen Ausgabesignals als Reaktion auf die Anwesenheit eines sich bewegendes Körpers in der Umgebung zu modifizieren;
 - zumindest eine erste Alarmschaltung (10a, 10b, 10c), die mit dem Sensor verbunden ist und imstande ist, ein Alarmsignal (ALARM) zu erzeugen, wenn die Modifikation einer vorher bestimmten Bedingung entspricht;
 - und eine Alarmsteuereinheit (30), die geeignet ist, das Alarmsignal (ALARM) zu empfangen;**dadurch gekennzeichnet, daß** das System zusätzliche Umformermittel (20a, 20b, 20c) zum fortlaufenden Umwandeln der Modifikation der Ausgabe aus dem elektrischen Sensor (1a, 1b, 1c) in ein Signal aufweist, das vom Menschen wahrgenommen werden kann, wobei das wahrnehmbare Signal an die Alarmsteuereinheit (30) übertragen wird.
2. System nach Anspruch 1, **dadurch gekennzeichnet, daß** das Umformermittel (20a, 20b, 20c) zum fortlaufenden Umwandeln der Modifikation der Ausgabe aus dem elektrischen Sensor (1a, 1b, 1c) in ein Signal, das vom Menschen wahrgenommen werden kann, einen Frequenzgenerator (21a, 21b, 21c) umfaßt, der durch die modifizierten Merkmale des elektrischen Ausgabesignals aus dem Sensor (1a, 1b, 1c) gesteuert wird, und einen akustischen Umformer umfaßt, der im Hörbereich des Überwachungspersonals angeordnet ist.
3. System nach Anspruch 2, **dadurch gekennzeichnet, daß** der Frequenzgenerator (21a, 21b, 21c) einen Tonfrequenzgenerator umfaßt.
4. System nach Anspruch 3, **dadurch gekennzeichnet, daß** der Tonfrequenzgenerator (21a, 21b, 21c) einen spannungsgesteuerten Oszillator oder VCO umfaßt, wobei die Frequenz des Signals, das der Oszillator (21a, 21b, 21c) erzeugt, zwischen 300 und 3.000 Hz enthalten ist.
5. System nach einem der vorhergehenden Ansprüche, **dadurch gekennzeichnet, daß** das Umformermittel (20a, 20b, 20c) ferner eine Modulationschaltung (22a (22b, 22c) umfaßt.

6. System nach einem der vorhergehenden Ansprüche, **dadurch gekennzeichnet, daß** die Alarmschaltungen (10a, 10b, 10c) über Signalübertragungsleitungen (14a, 14b, 14c) mit der Alarmsteuereinheit (30) verbunden sind, und daß die Alarmsteuereinheit (30) Demodulationsmittel (33a, 33b, 33c) und Alarmeingänge (31a, 31b, 31c) umfaßt.
7. System nach einem der vorhergehenden Ansprüche, **dadurch gekennzeichnet, daß** die Alarmsteuereinheit (30) eine Schaltvorrichtung oder einen Multiplexer (32) umfaßt, der eine Mehrzahl von Eingangskanälen (34), welche jeweils das Tonfrequenzsignal führen, das von einem der Umformermittel (20a, 20b, 20c) erhalten wird, und eine Mehrzahl von Ansteuerungseingängen (35) aufweist, die jeweils mit einem der Alarmeingänge (31a, 31b, 31c) verbunden sind, um es der Schaltvorrichtung (32) zu ermöglichen, die Tonfrequenzsignale auszugeben, die einem Alarmsignal zugeordnet sind.
8. System nach einem der vorhergehenden Ansprüche, **dadurch gekennzeichnet, daß** der Ausgang der Schaltvorrichtung (32) mit einem Verstärker (40) verbunden ist, dessen Ausgang ein Telephonanrufgerät (41) zur Übertragung der Alarmsignale und der Tonfrequenz-Signale über eine Telephonleitung (43) an ein Telephonempfangsgerät (42) speist.
9. System nach einem der vorhergehenden Ansprüche, **dadurch gekennzeichnet, daß** der zumindest eine Sensor (1a, 1b, 1c) aus der Gruppe der Infrarotsensoren, Doppler-Effekt-Sensoren oder einer Kombination daraus ausgewählt ist.
10. System nach einem der vorhergehenden Ansprüche, **dadurch gekennzeichnet, daß** der Ausgang des volumetrischen Sensors (1a, 1b, 1c) unmittelbar mit dem Relais (13a, 13b, 13c) gekoppelt ist, wobei das Signal, das moduliert werden soll, durch hintereinander abfolgendes Öffnen und Schließen des Relais (13a, 13b, 13c) erzeugt wird, welches durch das Signal von dem volumetrischen Sensor (1a, 1b, 1c) betrieben wird.
11. System nach Anspruch 10, **dadurch gekennzeichnet, daß** das Relais (13a, 13b, 13c) in derselben Einheit, die den Sensor (1a, 1b, 1c) beinhaltet, enthalten ist und das Signal aus der Vorrichtung über dieselbe Übertragungsleitung (14a, 14b, 14c) an die Alarmsteuereinheit (30) übertragen wird, die für das Senden des Alarmsignals (ALARM) vorgesehen ist.
12. System nach einem der vorhergehenden Ansprüche, **dadurch gekennzeichnet, daß** das Signal, das über die Tonübertragungsleitung (23a, 23b,

23c) an die Steuereinheit (30) übertragen wird, fortlaufend in zumindest einer Speichervorrichtung in der Steuereinheit (30) gespeichert wird.

13. System nach Anspruch 12, **dadurch gekennzeichnet, daß** jede der Speichervorrichtungen ein Festkörperspeicher ist, der imstande ist, fortlaufend ein Intervall oder "Rahmen" des Signals zu speichern, und daß eine Speichervorrichtung zum Speichern des Signals von jedem Sensor vorgesehen ist, der in der überwachten Umgebung angeordnet ist.
14. System nach Anspruch 1, **dadurch gekennzeichnet, daß** das Umformermittel (20a, 20b, 20c) zum fortlaufenden Umwandeln der Modifikation der Ausgabe aus dem elektrischen Sensor (1a, 1b, 1c) in ein Signal, das vom Menschen wahrgenommen werden kann, einen Frequenzgenerator (21a, 21b, 21c) umfaßt, der durch die modifizierten Merkmale des elektrischen Ausgabesignals aus dem Sensor (1a, 1b, 1c) gesteuert wird, und eine Anzeige umfaßt, die für das Überwachungspersonal sichtbar ist.

Revendications

1. Système électronique de détection d'intrusion destiné à au moins un environnement surveillé, comprenant :

au moins un capteur électronique (1a, 1b, 1c) sensible aux mouvements se produisant dans ledit environnement et capable de modifier au moins une des caractéristiques significatives de son signal électrique de sortie en réponse à la présence d'un corps se déplaçant dans ledit environnement surveillé ;

au moins un premier circuit d'alarme (10a, 10b, 10c) connecté audit capteur et capable de générer un signal d'alarme (ALARM) lorsque ladite modification remplit une condition prédéterminée.

et une unité de commande du système d'alarme (30) conçue pour recevoir ledit signal d'alarme (ALARM) ;

caractérisé en ce que ledit système comprend des moyens formant transducteur supplémentaires (20a, 20b, 20c) pour convertir de manière continue ladite modification de la sortie dudit capteur électrique (1a, 1b, 1c) en un signal qui peut être perçu par un être humain, ledit signal perceptible étant transmis à l'unité de commande du système d'alarme (30).

2. Système selon la revendication 1, **caractérisé en ce que** lesdits moyens formant transducteur (20a,

- 20b, 20c) permettant d'assurer la conversion continue de ladite modification de la sortie provenant du capteur électrique (1a, 1b, 1c) en un signal qui peut être perçu par un être humain comprennent un générateur de fréquence (21a, 21b, 21c) commandé par lesdites caractéristiques modifiées du signal électrique de sortie provenant dudit capteur (1a, 1b, 1c) et un transducteur acoustique situé dans la gamme des fréquences audibles pour le personnel de surveillance.
3. Système selon la revendication 2, **caractérisé en ce que** ledit générateur de fréquence (21a, 21b, 21c) comprend un générateur audiofréquence.
4. Système selon la revendication 3, **caractérisé en ce que** ledit générateur audiofréquence (21a, 21b, 21c) comprend un oscillateur commandé par tension ou VCO, la fréquence du signal généré par ledit oscillateur (21a, 21b, 21c) étant comprise entre 300 et 3 000 Hz.
5. Système selon les revendications précédentes, **caractérisé en ce que** lesdits moyens formant transducteur (20a, 20b, 20c) comprennent en outre un circuit de démodulation (22a, 22b, 22c).
6. Système selon les revendications précédentes, **caractérisé en ce que** lesdits circuits d'alarme (10a, 10b, 10c) sont connectés à ladite unité de commande du système d'alarme (30) par des lignes de transmission de signaux (14a, 14b, 14c) et **en ce que** ladite unité de commande du système d'alarme (30) comprend des moyens de démodulation (33a, 33b, 33c) et des entrées d'alarme (31a, 31b, 31c).
7. Système selon les revendications précédentes, **caractérisé en ce que** ladite unité de commande du système d'alarme (30) comprend un dispositif de commutation ou un multiplexeur (32) possédant une pluralité de canaux d'entrée (34), chacun transportant le signal audiofréquence obtenu à partir de l'un desdits moyens transducteurs (20a, 20b, 20c) et une pluralité d'entrées d'adresse (35), chacune étant reliée à l'une desdites entrées d'alarme (31a, 31b, 31c) pour permettre auxdits moyens de commutation (32) de produire les signaux audiofréquence associés à un signal d'alarme.
8. Système selon les revendications précédentes, **caractérisé en ce que** la sortie dudit dispositif de commutation (32) est connectée à un amplificateur (40), dont la sortie alimente un dispositif de téléphone automatique (41) pour la transmission des signaux d'alarme et des signaux audiofréquence via une ligne téléphonique (43) vers un poste téléphonique récepteur (42).
9. Système selon les revendications précédentes, **caractérisé en ce que** ledit au moins un capteur (1a, 1b, 1c) est sélectionné parmi le groupe de capteurs infrarouge, de capteurs d'effet Doppler ou une combinaison de ceux-ci.
10. Système selon les revendications précédentes, **caractérisé en ce que** la sortie dudit capteur volumétrique (1a, 1b, 1c) est directement couplée audit relais (13a, 13b, 13c), moyennant quoi le signal devant être modulé est généré par les ouvertures et fermetures successives dudit relais (13a, 13b, 13c) entraînées par le signal provenant dudit capteur volumétrique (1a, 1b, 1c).
11. Système selon la revendication 10, **caractérisé en ce que** ledit relais (13a, 13b, 13c) est enfermé dans la même unité logeant ledit capteur (1a, 1b, 1c) et le signal de ladite unité est transmis à l'unité de commande du système d'alarme (30) le long de la même ligne de transmission (14a, 14b, 14c) prévue pour envoyer ledit signal d'alarme (ALARM).
12. Système selon les revendications précédentes, **caractérisé en ce que** le signal transmis sur ladite ligne de transmission audio (23a, 23b, 23c) vers ladite unité de commande (30) est stocké en continu dans au moins une mémoire dans ladite unité de commande (30).
13. Système selon la revendication 12, **caractérisé en ce que** chacune desdites mémoires est une mémoire à semi-conducteurs capable de stocker en continu un intervalle ou une "trame" du signal, et il est prévu une mémoire pour stocker le signal de chaque capteur situé dans l'environnement surveillé.
14. Système selon la revendication 1, **caractérisé en ce que** lesdits moyens formant transducteur (20a, 20b, 20c) servant à convertir en continu ladite modification de la sortie provenant du capteur électrique (1a, 1b, 1c) en un signal qui peut être perçu par un être humain comprennent un générateur de fréquence (21a, 21b, 21c) commandé par lesdites caractéristiques modifiées du signal électrique de sortie provenant dudit capteur (1a, 1b, 1c) et une unité d'affichage destinée au personnel de surveillance.

