



(12) **United States Patent**  
**LeBeau et al.**

(10) **Patent No.:** **US 9,549,769 B2**  
(45) **Date of Patent:** **Jan. 24, 2017**

(54) **FLEXIBLE DEPTH PROBE**

USPC .. 606/102, 79, 80, 86 R, 138, 139, 144, 148  
See application file for complete search history.

(71) Applicant: **Smith & Nephew, Inc.**, Memphis, TN (US)

(56) **References Cited**

(72) Inventors: **Jason Roch LeBeau**, Bridgewater, MA (US); **Carmel Ilka Bijoux**, Boston, MA (US); **Steven Mark Bowman**, Sherborn, MA (US)

U.S. PATENT DOCUMENTS

4,779,349 A 10/1988 Odensten et al.  
5,013,318 A \* 5/1991 Spranza, III ..... A61B 5/1076  
33/512

(73) Assignee: **Smith & Nephew, Inc.**, Memphis, TN (US)

5,306,301 A 4/1994 Graf et al.  
6,156,056 A \* 12/2000 Kearns ..... A61B 17/0469  
606/232

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

6,729,037 B2 5/2004 White  
6,729,307 B2 5/2004 Dong  
(Continued)

(21) Appl. No.: **14/246,300**

OTHER PUBLICATIONS

(22) Filed: **Apr. 7, 2014**

Silver, A.G., et al., "Comparison between Rigid and Flexible Systems for Drilling the Femoral Tunnel through an 1 Anteromedial Portal in Anterior Cruciate Ligament Reconstruction," *Arthroscopy: The Journal of Arthroscopic and Related Surgery*, vol. 26, Issue 6, pp. 790-795, Jun. 2010.

(65) **Prior Publication Data**

US 2014/0222010 A1 Aug. 7, 2014

**Related U.S. Application Data**

(63) Continuation of application No. 13/234,636, filed on Sep. 16, 2011, now Pat. No. 8,728,088.

Andrews, James R., "ACL Reconstruction: Bone-Tendon-Bone Surgical Protocol," from "ToggleLoc Fixation Device with Zip Loop Technology," *Biomet Sports Medicine*, Mar. 2009, 12 pages. "Game Plan: Strategies to Help Surgeons Get Patients Back in the Game" Fall 2009, vol. 2, No. 1, *Biomet Sports Medicine*, 4 pages.  
(Continued)

(51) **Int. Cl.**

**A61B 17/58** (2006.01)  
**A61B 17/60** (2006.01)  
**A61F 2/00** (2006.01)  
**A61B 17/88** (2006.01)  
**A61B 17/17** (2006.01)  
**A61B 17/00** (2006.01)

*Primary Examiner* — Kevin T Truong  
*Assistant Examiner* — Si Ming Ku  
(74) *Attorney, Agent, or Firm* — Burns & Levinson LLP; Joseph M. Maraia

(52) **U.S. Cl.**

CPC ..... **A61B 17/88** (2013.01); **A61B 90/06** (2016.02); **A61B 17/1714** (2013.01); **A61B 2017/00455** (2013.01); **A61B 2090/062** (2016.02)


(57) **ABSTRACT**

An instrument includes a flexible shaft portion and a hook portion. The flexible shaft portion has a proximal end and a distal end and includes markings along an outer surface of the shaft portion. The hook portion is located at the distal end of the shaft portion. The shaft portion and the hook portion define a lumen that terminates in an opening at the hook portion.

(58) **Field of Classification Search**

CPC . A61B 19/46; A61B 2019/461; A61B 5/1072; A61B 17/1714; A61B 2017/00455; A61F 2/4657; A61F 2002/4662; A61F 2/4684; A61F 2/0805

**25 Claims, 9 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

7,299,561	B2	11/2007	Castaneda	
7,485,119	B2	2/2009	Thelen et al.	
7,559,150	B2 *	7/2009	Fernandez	..... A61B 5/103
				33/512
2002/0143234	A1 *	10/2002	LoVuolo	..... A61B 17/06109
				600/30
2009/0049705	A1	2/2009	Kim	
2009/0151181	A1	6/2009	Kim et al.	
2009/0272001	A1	11/2009	Dell Oca	
2011/0208194	A1 *	8/2011	Steiner	..... A61B 17/1631
				606/80
2012/0053641	A1	3/2012	Meridew	
2012/0221007	A1 *	8/2012	Batten et al.	..... 606/80

OTHER PUBLICATIONS

“Anatomic ACL Reconstruction Using the Clancy Anatomic Cruciate Guide/Flexible Drill System,” JointIntelligence, vol. 1, Issue 2, Nov. 2009, 5 pages.

“Symmetry Medical: Acetabular Screw Preparation System,” brochure from Symmetry Medical Othy, 2005, 2 pages.

“Salvin Dental Specialties: Flexible Tip Implant Depth Gauge with Ergonon,” reprinted from <http://salvin.com/Flexible-Tip-Implant-Depth-Gauge-With-Ergonomic-Handle-pluD> . . . on Jun. 22, 2011, 1 page.

“Bullseye Anatomic Cruciate Reconstruction System,” brochure from ConMed Linvatec, 2009, 16 pages.

“VersiTomic Flexible Reaming System,” brochure from Stryker, 2010, 6 pages.

\* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C









FIG. 1D








FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 4A






FIG. 4B






FIG. 4E




FIG. 4F

1

**FLEXIBLE DEPTH PROBE****CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of and claims priority to U.S. patent application Ser. No. 13/234,636, filed Sep. 16, 2011, entitled "FLEXIBLE DEPTH PROBE," the entire teachings of all of the above are incorporated herein by reference as though fully set forth herein.

**TECHNICAL FIELD**

This document relates to determining bone tunnel depth.

**BACKGROUND**

An anterior cruciate ligament (ACL) that has ruptured and is non-repairable is generally replaced arthroscopically by a tissue graft. The tissue graft can be harvested from a portion of a patellar tendon having so called "bone blocks" at each end, and from the semitendons and gracilis. Alternatively, the tissue graft can be formed from synthetic materials or from a combination of synthetic and natural materials. The replacement tissue graft is implanted by securing one end of the tissue graft in a socket formed in a passage within the femur, and passing the other end of the graft through a passage formed in the tibia.

**SUMMARY**

According to one aspect, an instrument includes a flexible shaft portion and a hook portion. The flexible shaft portion has a proximal end and a distal end and includes markings along an outer surface of the shaft portion. The hook portion is located at the distal end of the shaft portion. The shaft portion and the hook portion define a lumen that terminates in an opening at the hook portion.

Implementations of this aspect may include one or more of the following features.

For example, the hook portion may include a tip. The tip may extend beyond an outer diameter of the flexible shaft portion. The hook portion may include a chamfer on a surface opposite the tip. The instrument may further include a chamfered connecting portion connecting the hook portion and the flexible shaft portion. The chamfered portion may also define the lumen. The hook portion may include a tip, and the chamfered connecting portion may include a chamfer along a tip-facing side of the chamfered portion. The shaft portion may include multiple, spaced apart voids along a length of the shaft portion. The voids may be configured to provide the shaft with flexibility. The voids may be configured to provide the shaft with flexibility sufficient to allow the shaft to flex at least 40 degrees without damage. The proximal end of the shaft may include an orientation indicator that indicates the orientation of the hook portion.

According to another aspect, a method of determining a length of a bone tunnel using an instrument includes placing the instrument onto a curved guide wire that passes through the bone tunnel, moving the instrument along the curved guide wire until a hook portion passes through a first opening of the bone tunnel, through the bone tunnel, and out a second opening of the bone tunnel, orienting the instrument such that a tip of the hook portion substantially faces an outer curvature of the guide wire, retracting the instrument until the hook portion engages a cortical surface of the bone, and determining the length of the bone tunnel based on

2

markings along an outer surface of a flexible shaft portion. The instrument includes a flexible shaft portion and a hook portion at a distal end of the shaft.

Implementations of this aspect may include one or more of the following features.

For example, the shaft portion and the hook portion may define a lumen that terminates in an opening at the hook portion. Placing the instrument onto the curved guide wire may include threading the hole and lumen over the guide wire. The instrument may be oriented such that the tip of the hook portion substantially faces an inner curvature of the guide wire while the hook portion passes through the first opening of the bone tunnel, through the bone tunnel, and out the second opening of the bone tunnel. Orienting the instrument such that the tip of the hook portion substantially faces the outer curvature of the guide wire may include rotating the instrument around the guide wire until the tip of the hook portion substantially faces the outer curvature of the guide wire. The method of determining the length of a bone tunnel using the instrument may include disengaging the hook portion from the cortical surface, orienting the instrument such that the tip of the hook portion substantially faces an inner curvature of the guide wire, and moving the device along the curved guide wire until the hook portion passes through the second opening of the bone tunnel, through the bone tunnel, and out the first opening of the bone tunnel. The bone tunnel may be a femoral tunnel. The guide wire may be curved at least 40 degrees such that moving the instrument along the curved guide wire causes the flexible shaft to flex at least 40 degrees. The method of determining the length of a bone tunnel using the instrument may include determining an orientation of the hook portion based on an orientation indicator that indicates the orientation of the hook portion. The orientation indicator may be located at the proximal end of the shaft.

The details of one or more implementations are set forth in the accompanying drawings and the description below. Other features, aspects, and advantages will become apparent from the description, the drawings, and the claims.

**BRIEF DESCRIPTION OF THE DRAWINGS**

FIG. 1A is a perspective view of a flexible depth probe.

FIG. 1B is an enlarged perspective view of a hook portion of the flexible depth probe.

FIG. 1C is a partial side view of the flexible depth probe.

FIG. 1D is a cross-sectional view of the probe.

FIG. 1E is a side view of the flexible depth probe.

FIG. 1F is a cross-sectional view of the flexible depth probe of FIG. 1E taken along the line 1F-1F in the direction of the arrows.

FIG. 1G is a cross-sectional view of the flexible depth probe of FIG. 1E taken along the line 1G-1G in the direction of the arrows.

FIG. 2A is a side view of the flexible depth probe placed onto a guide wire with a tip of the hook portion facing an inner curvature of the guide wire.

FIG. 2B is a side view of the flexible depth probe placed onto a curved guide wire with a tip of the hook portion facing an outer curvature of the guide wire.

FIGS. 3A-3D illustrate a procedure for forming a femoral tunnel.

FIGS. 4A-4F illustrate a procedure using the flexible depth probe to determine the depth or length of the femoral tunnel.

Like reference numbers and designations in the various drawings indicate like elements.

#### DETAILED DESCRIPTION

This document describes an example of a flexible depth probe for determining the depth or length of a bone tunnel. The flexible depth probe can, for example, be used to determine the length of a bone tunnel within a femur. In some implementations, the flexible depth probe can bend beyond 40 degrees, for example, to 42 degrees.

FIGS. 1A-1G illustrate an example of an implementation of a flexible depth probe **100**. The probe **100** may be used as an instrument, for example, in determining the length of a bone tunnel in the femur, or femoral tunnel, during anterior cruciate ligament (ACL) surgery. The probe **100** includes a hook portion **102**, a flexible shaft portion **104**, and a chamfered connecting portion **106**. Flexible depth probe **100** defines a lumen **110** that starts at the proximal end **118** and terminates in an opening **103** at the distal end **116** (as best seen in FIG. 1B). The overall length of the flexible depth probe **100** can be, for example, 30 cm. The diameter of the flexible shaft portion **104** can be 3 mm, and the diameter of lumen **110**, which allows a guide wire to fit within it, can be 2.7 mm. The probe wall **109** surrounds the lumen **110** and can be 0.24 mm in wall thickness (as best seen in FIG. 1D). The flexible depth probe **100** can be made from various materials including, but not limited to, metals and alloys including titanium, stainless steel, anodized aluminum, and nickel titanium (nitinol), as well as different types of plastics and polymers. In some cases, the flexible depth probe **100** can be made from a combination of different materials.

The flexible shaft portion **104** of depth probe **100** includes multiple, spaced apart voids **108** configured to provide the shaft with flexibility, such that the flexible shaft portion **104** can bend beyond, for example, 40 degrees. The spaced apart voids **108** are in the form of slices cut into alternating sides of the flexible shaft portion **104**. The slices can be 0.3 mm in width and can be spaced 2 mm apart from each other. The spaced apart voids **108** can alternatively, or additionally, be in the form of a continuous spiral cut, interlocking cut, puzzle cut, or other appropriate cut arrangement that provides the shaft with flexibility and can be formed, for example, through electric discharge machining (EDM) or laser cutting. Alternatively, or additionally, inherent flexibility of the material used in constructing the flexible shaft portion **104**, for example nitinol, can provide flexibility to the section.

Hook portion **102** has a tip **102a** configured to engage or latch onto a cortical surface of the bone and a chamfer **112**, on the side opposite the tip **102a**, configured to allow the depth probe **100** to slide smoothly inside, for example, a bone tunnel without damaging the tunnel wall. The chamfer **112** forms an angle A of, for example, 35 degrees, or more generally about 20 to about 85 degrees, with respect to the longitudinal axis **101** of the depth probe **100** and can be, for example, 4.4 mm in length when viewed from the side. A lower portion of the opening **103** includes a semi-cylindrical portion while the chamfer **112** defines an upper curved portion of the opening **103** (as best seen in FIG. 1B), the lower and upper portions of opening **103** defining a circular perimeter around longitudinal axis **101** when viewed axially from the distal end **116**. Alternatively, or additionally, the opening **103** may be entirely cylindrical. The chamfer **112** may or may not expose the interior lumen **110**. The chamfer **112** may be replaced with a radius in some cases.

The tip **102a** is in the shape of an oblique semi-cylinder. The distal face **113** and the proximal face **111** of the semi-cylinder are angled towards the proximal end **118**. The distal face **113** is angled to help the hook portion **102** slide into the bone tunnel. The proximal face **111** is angled to help the tip **102a** more easily latch onto the cortical surface of the bone. Alternatively, or additionally, the tip **102a** can be textured or include additional materials, such as rubber, to more easily engage the cortical surface. The tip **102a** can further be in the shape of other geometric forms, such as spheres, prisms, and pyramids, that allow the tip **102a** to latch onto the cortical surface of the bone. As shown in FIGS. 1C-1G, the outermost surface of the tip **102a** extends beyond the outer surface of the flexible shaft portion **104**, for example, by 6 mm, and the proximal face of tip **102a** forms an angle B, for example, of 110 degrees with respect to the longitudinal axis **101**.

The chamfered connecting portion **106** connects the hook portion **102** to the flexible shaft portion **104** and includes a chamfer **107** along the same side as the tip **102a**. The chamfered connecting portion **106** is configured to provide a smooth transition between the interface region **115** and the outer surface of the flexible shaft portion **104**. The chamfer **107** can form an angle C of about 1 to about 30 degrees with respect to the longitudinal axis **101** of the depth probe **100** and can be, for example, 15 mm in length. The chamfer **107** may expose the interior lumen **110**. As described further below, the chamfer **107** can provide a more secure engagement of the hook portion **102** to the cortical surface of the bone.

The orientation indicator **120** located proximal to the flexible shaft portion **104** indicates the rotational orientation of the hook portion **102** around the longitudinal axis **101** and can be, for example, a straight line 20 mm in length running parallel to longitudinal axis **101** on the side of the flexible depth probe **100** opposite the tip **102a**. Markings **114** are placed along the outer surface of the flexible depth probe **100** to indicate the length of the object, for example a bone tunnel, and can include a plurality of numerical as well as line markings. The numerical markings indicate the distance along the outer wall of the flexible shaft portion **104**, on the side of the tip **102a** and the chamfer **107**, between the interface region **115** and the respective numerical marking. The numerical markings can be placed every 10 mm on the same and/or opposite side of **102a**. The line markings can be placed every 2 mm and can run along the entire circumference of the probe **100** at each marking location. Alternatively, or additionally, the spaced apart voids **108** can serve as the line markings.

In another implementation, numerical markings can be located further proximally, by a known distance, on the flexible depth probe **100** in relation to their corresponding line markings such that the distance along the outer wall of flexible shaft portion **104** may be determined by observing the numerical markings that are located further down proximally. The orientation indicator **120** and markings **114** can be painted or engraved using a variety of techniques, for example laser etching.

FIGS. 2A-2B show side views of the flexible depth probe **100** placed onto a guide wire **200**. The guide wire **200** is generally straight and can be bent, reversibly or irreversibly, to a desired curvature. The guide wire **200** can be made from any appropriate materials, such as, but not limited to, materials used in making the flexible depth probe **100**. Additionally, the guide wire **200** can be an existing guide wire or passing pin of a flexible drill system, such as the Clancy Flexible System by Smith & Nephew.

The guide wire **200** slidably fits within the lumen **110** of the flexible depth probe **100**, as best seen in FIGS. 2A-2B. The length of the guide wire **200** can be 34 cm, and its diameter can be 2.4 mm. As the flexible depth probe **100** is inserted or threaded over the guide wire **200**, the flexibility of the flexible shaft portion **104** allows the shaft portion **104** to conform to the shape of guide wire **200**. For example, if the guide wire **200** is curved at least 40 degrees, moving the flexible depth probe **100** along the curved guide wire **200** causes the flexible shaft portion **104** of the depth probe **100** to flex at least 40 degrees. FIG. 2A shows the flexible depth probe **100** slidably threaded over the guide wire **200** and oriented such that the tip **102a** of the hook portion **102** faces an inner curvature **202** of the guide wire **200**. As described further below, this rotational orientation of the flexible depth probe **100** can be used for engaging or latching onto, for example, the cortical surface of a bone.

FIGS. 3A-3D illustrate a process for drilling a femoral tunnel **306** in a femur **300** via, for example, an anteromedial portal (not shown). The diameter of the femoral tunnel can be 9 mm and is larger than the largest diameter found along the hook portion **102**. Referring to FIG. 3A, with the patient's knee bent to approximately 90 degrees, a curved endoscopic femoral guide **302** is introduced through the anteromedial portal. With the femoral guide **302** in position, the guide wire **200** (which may also be referred to as a drill tip passing pin) is inserted through the femoral guide **302** and advanced through the femur **300** (as best seen in FIGS. 3A-3B) and, in some cases, through the skin. Due to axial misalignment between an entry point into the anteromedial portal and a first femoral opening **308**, the guide wire **200** is curved beyond 40 degrees in most cases. At this point in the process, the femoral guide **302** is removed, leaving the guide wire **200** in place.

Referring to FIGS. 3C-3D, a flexible cannulated drill **304** is inserted over the guide wire **200** and advanced until the desired depth of the femoral tunnel **306** is achieved. The shape of the resulting femoral tunnel **306** follows the trajectory of the guide wire **200** and is generally straight. Additionally, the femoral tunnel **306** terminates in a second femoral opening **310** on the opposite side of the femur **300**. The guide wire **200** may or may not extend beyond the second femoral opening **310**.

After drilling the femoral tunnel **306** and removing the flexible cannulated drill **304**, as shown in FIG. 3D, the guide wire **200** will try to straighten out by springing back, in the direction of its outer curvature **204**, to its initial shape. This will result in a convex side of the flexible depth probe **100** coming in contact with an interior wall of the bone tunnel **306**. In some cases, the convex side of the probe **100** may come in contact with the interior wall of the bone tunnel **306** regardless of the shape of the guide wire **200** within the femoral tunnel **306**.

Referring to FIGS. 4A-4F, the flexible depth probe **100** is used to determine the length of the femoral tunnel **306**. In some cases, the guide wire **200** remains in place following the drilling steps outlined in FIGS. 3A-3D. Alternatively, the

guide wire **200** may be replaced with another guide wire or repositioned within the bone tunnel prior to the depth determining step. Due to axial misalignment between the anteromedial portal, where the guide wire **200** first enters the patient's body, and the first femoral opening **308**, where the guide wire **200** first enters the femur **300**, the guide wire **200** can be curved beyond 40 degrees.

As shown in FIG. 4A, the flexible depth probe **100** is threaded over the guide wire **200** and advanced into the femoral tunnel **306** through the first femoral opening **308**. By observing the orientation indicator **120**, which may be inside or outside of the patient's body, the rotational orientation of the flexible depth probe **100** can be controlled such that the tip **102a** of the hook portion **102** substantially faces the inner curvature **202** of the guide wire **200**. Due to the tendency of the guide wire **200** and/or the flexible depth probe **100** to straighten out while in a curved state, the probe **100** will tend to push out towards the direction of the outer curvature **204** and make contact with the interior wall of the femoral tunnel **306**. Because of the chamfer **112**, the hook portion **102** is able to pass through the first femoral opening **308** without getting stuck and is further able to slide smoothly within the femoral tunnel **306** without snagging on or damaging the interior wall of the femoral tunnel **306**. Additionally, because the diameter of the femoral tunnel is larger than the largest diameter found along the hook portion **102**, the tip **102a** of the hook portion **102** will not come in contact with the interior wall of the femoral tunnel **306**. As shown in FIG. 4B, the flexible depth probe **100** is advanced until the hook portion **102** comes out of the femoral tunnel **306** through the second femoral opening **310**.

FIGS. 4C-4F illustrate the process by which the tip **102a** latches on to the cortical surface of the bone **400**. After the hook portion **102** is advanced past the second femoral opening **310**, the proximal end **118** of the flexible depth probe **100** is rotated by approximately 180 degrees around the guide wire **200**, as indicated by arrow D in FIG. 4C. As a result, the hook portion **102** rotates approximately 180 degrees about the guide wire **200**, and the tip **102a** substantially faces the outer curvature **204** of the guide wire **200**. Due to the tendency of the guide wire **200** and/or the flexible depth probe **100** to straighten out while in a curved state, the probe **100** will tend to push out towards the direction of the outer curvature **204** and make contact with the interior wall of the femoral tunnel **306**. Because of the chamfer **107**, the rotation of the flexible depth probe **100** may cause the hook portion **102** to move radially outwards in the direction of the outer curvature **204**. This outward movement can provide a more secure engagement of the hook portion **102** to the cortical surface of the bone **400** by maximizing the amount of cortical surface **400** that is engaged by the tip **102a**. Once the tip **102a** substantially faces the outer curvature **204** of the guide wire **200**, the proximal end **118** is retracted in the direction indicated by arrow E in FIG. 4D. This pulling action causes the tip **102a** to engage or latch onto the cortical surface of the bone **400**. Once the cortical surface of the bone **400** has been engaged by the hook portion **102**, the distance between the interface region **115** and a marking **114** adjacent the first femoral opening **308** indicates the length of the femoral tunnel **306**.

The above-mentioned features of the flexible depth probe **100** may enable easy removal of the probe **100** from the femoral tunnel **306** after a length has been determined, for example, by reversing the order of steps indicated in FIGS. 4A-4D. The hook portion **102** is disengaged from the cortical surface of the bone **400**, for example, by pushing the proximal end **118** of the probe **100** in a direction opposite the

direction indicated by arrow E. Once the hook portion 102 has been disengaged from the cortical surface 400, rotating the proximal end 118 of the probe 100 by approximately 180 degrees results in the hook portion 102 rotating by approximately 180 degrees and substantially facing the inner curvature 202 of the guide wire 200. Because of the tendency of the guide wire 200 to straighten out, the convex side of the probe 100 will push against the inner wall of the femoral tunnel 306. At this point in the process, the proximal end 118 of the probe 100 is pulled until the hook portion 102 of the probe 100, moving along the guide wire 200, passes sequentially through the second femoral opening 310, the femoral tunnel 306, the first femoral opening 308, and eventually out of the patient's body. Since the diameter of the femoral tunnel 306 is larger than the largest diameter of the hook portion 102, the tip 102a of the hook portion 102 will not snag on or damage the interior wall of the femoral tunnel 306.

While this document contains many specific implementation details, these should not be construed as limitations on the scope of any implementations or of what may be claimed, but rather as descriptions of features specific to particular implementations of particular implementations. Certain features that are described in this document in the context of separate implementations can also be implemented in combination in a single implementation. Conversely, various features that are described in the context of a single implementation can also be implemented in multiple implementations separately or in any suitable subcombination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination may be directed to a subcombination or variation of a subcombination. Thus, particular implementations of the subject matter have been described. Other implementations are within the scope of the following claims.

The invention claimed is:

1. A measurement instrument comprising:

a flexible shaft portion having a proximal end and a distal end, the flexible shaft portion including measurement markings along an outer surface of the flexible shaft portion; and

a hook portion at the distal end of the flexible shaft portion;

wherein the flexible shaft portion and the hook portion define a lumen that terminates in an opening at the hook portion,

wherein the flexible shaft portion includes multiple, spaced apart voids along a length of the flexible shaft portion, the voids configured to provide the flexible shaft portion with flexibility,

wherein the hook portion includes a tip extending radially outward beyond an outer diameter surface of the flexible shaft portion and a terminal end of the hook portion furthest from the flexible shaft portion angled relative to the tip in a direction back towards the proximal end of the shaft,

wherein the tip and terminal end are substantially coplanar with respect to a plane parallel to a longitudinal axis of the shaft, and

wherein a portion of an inner engagement surface of the hook extends back toward a proximal portion of the shaft at an acute angle relative to the shaft.

2. The instrument of claim 1, wherein the hook portion includes a first chamfer cutaway, the first chamfer cutaway

disposed on a surface of the flexible shaft portion opposite the tip; and wherein the hook portion includes a second chamfer cutaway on the tip opposite the first chamfer cutaway.

3. The instrument of claim 1 further comprising a chamfered connecting portion connecting the hook portion and the flexible shaft portion, the chamfered connecting portion also defining a lumen.

4. The instrument of claim 3 wherein the chamfered connecting portion includes a chamfer along a tip-facing side of the chamfered connecting portion.

5. The instrument of claim 3, wherein the flexible shaft portion includes an orientation marking indicating a rotational orientation of the flexible shaft portion, the orientation marking aligning with the chamfered connecting portion.

6. The instrument of claim 1 wherein the voids are configured to provide the flexible shaft portion with flexibility sufficient to allow the flexible shaft portion to flex at least 40 degrees without damage.

7. The instrument of claim 1, wherein the multiple spaced apart voids are slices cut into alternating sides of the shaft portion.

8. The instrument of claim 7, wherein the multiple spaced apart voids includes a first void and a second void disposed on a particular side of the shaft portion;

wherein the markings are measurement marking including a first measurement marking and a second measurement marking; and

wherein the first measurement marking is disposed on the side of the shaft between the first void and the second void.

9. The instrument of claim 1, wherein the shaft includes an orientation marking indicating a rotation orientation of the shaft.

10. The instrument of claim 1, wherein the angling of the terminal end of the hook portion relative to the tip defines a cavity.

11. The instrument of claim 10, wherein the hook portion includes a chamfered cutaway on a surface of the flexible shaft portion opposite the tip, the chamfered cutaway on the surface of the flexible shaft portion opposite the tip exposing the lumen on a side wall along an axial length of the flexible shaft portion.

12. The instrument of claim 11, wherein the cavity includes a chamfered connecting portion connecting the hook portion and the flexible shaft portion, the chamfered connection portion in the cavity providing an opening to the lumen.

13. The instrument of claim 12, wherein the flexible shaft portion includes multiple spaced-apart voids along a length of the flexible shaft portion, the multiple spaced-apart voids configured to provide the flexible shaft portion with flexibility.

14. The instrument of claim 13, wherein the proximal end of the flexible shaft portion includes an orientation indicator that indicates a rotational orientation of the tip disposed on the hook portion.

15. The instrument of claim 14, wherein the proximal end of the flexible shaft portion includes an outer circumferential surface region on which the orientation indicator resides.

16. A measurement instrument comprising:

a flexible shaft portion having a proximal end and a distal end, the flexible shaft portion including measurement markings along an outer surface of the flexible shaft portion;

a hook portion at the distal end of the flexible shaft portion;

wherein the flexible shaft portion and the hook portion define a lumen that terminates in an opening at the hook portion;

wherein the hook portion includes a tip, the tip extending radially outward beyond an outer diameter surface of the flexible shaft portion, a terminal end of the hook portion furthest from the flexible shaft portion angled in a direction back towards the proximal end to form a cavity;

wherein the hook portion includes a chamfered cutaway on a surface of the flexible shaft portion opposite the tip, the chamfered cutaway on the surface of the flexible shaft portion opposite the tip exposing the lumen on a side wall along an axial length of the flexible shaft portion;

wherein the cavity includes a chamfered connecting portion connecting the hook portion and the flexible shaft portion, the chamfered connection portion in the cavity providing an opening to the lumen; and

wherein the proximal end of the flexible shaft portion includes an orientation indicator that indicates a rotational orientation of the hook portion disposed on the distal end of the flexible shaft portion.

**17.** A method of determining a length of a bone tunnel in a respective bone using a measurement instrument that includes a flexible shaft portion and a hook portion at a distal end of the flexible shaft portion, the method comprising:

- placing the instrument into a curved guide wire that passes through the bone tunnel;
- moving the flexible shaft portion of the instrument along the curved guide wire until the hook portion passes through a first opening of the bone tunnel, through the bone tunnel, and out a second opening of the bone tunnel;
- orienting the flexible shaft portion of the instrument such that a tip of the hook portion faces an outer curvature of the guide wire;
- maintaining the orientation of the flexible shaft portion with the tip of the hook portion facing the outer curvature of the guide wire while retracing the instrument until the tip of the hook portion facing the outer curvature of the guide wire engages a cortical surface of the respective bone; and
- determining the length of the bone tunnel based on measurement markings along an outer surface of the flexible shaft portion.

**18.** The method of claim **17** wherein the flexible shaft portion and the hook portion define a lumen that terminates in an opening at the hook portion; and

- wherein placing the instrument into the curved guide wire includes threading the opening and lumen over the guide wire.

**19.** The method of claim **17** wherein the instrument is oriented such that the tip of the hook portion faces an inner curvature of the guide wire while the hook portion passes through the first opening of the bone tunnel, through the bone tunnel, and out the second opening of the bone tunnel.

**20.** The method of claim **17** wherein orienting the instrument such that the tip of the hook portion faces the outer curvature of the guide wire includes rotating the instrument around the guide wire until the tip of the hook portion faces the outer curvature of the guide wire.

**21.** The method of claim **17** further comprising:

- disengaging the hook portion from the cortical surface;
- orienting the instrument such that the tip of the hook portion faces an inner curvature of the guide wire; and
- moving the instrument along the curved guide wire until the hook portion passes through the second opening of the bone tunnel, through the bone tunnel, and out the first opening of the bone tunnel.

**22.** The method of claim **17** further comprising determining an orientation of the hook portion based on the orientation indicator that indicates the orientation of the hook portion, the orientation indicator being located at a proximal end of the flexible shaft portion.

**23.** The method as in claim **17**, wherein the flexible shaft portion has a tendency to straighten out, facilitating engagement of the tip of the hook portion with the cortical surface of the respective bone.

**24.** The method as in claim **17**, wherein the bone tunnel has a larger diameter than a diameter of the hook portion disposed at the distal end of the flexible shaft portion.

**25.** The method as in claim **23** further comprising:

- orientating the flexible shaft portion such that a tip of the hook portion faces an inner curvature of the guide wire to disengage the tip of the hook portion from the cortical surface of the bone; and
- retracting the flexible shaft portion from the bone tunnel.

\* \* \* \* \*