

(19) **DANMARK**

(10) **DK/EP 3195991 T3**



Patent- og
Varemærkestyrelsen

(12) Oversættelse af
europæisk patentskrift

-
- (51) Int.Cl.: **B 25 J 15/00 (2006.01)** **B 23 P 19/06 (2006.01)** **B 25 J 11/00 (2006.01)**
- (45) Oversættelsen bekendtgjort den: **2019-06-11**
- (80) Dato for Den Europæiske Patentmyndigheds bekendtgørelse om meddelelse af patentet: **2019-03-06**
- (86) Europæisk ansøgning nr.: **16152186.9**
- (86) Europæisk indleveringsdag: **2016-01-21**
- (87) Den europæiske ansøgnings publiceringsdag: **2017-07-26**
- (84) Designerede stater: **AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR**
- (73) Patenthaver: **ADMEDE AB, Postbox 4424, 203 25 Malmö, Sverige**
- (72) Opfinder: **Johst, Kenneth, Rosenoms alle 32 2 tv, 1970 Frederiksberg C, Danmark**
JAGD, Lars, Jörgen Ankersgatan 20, 211 45 Malmö, Sverige
Marinitsch, Gerald, Buchengasse 5, 8401 Kalsdorf, Østrig
- (74) Fuldmægtig i Danmark: **Zacco Denmark A/S, Arne Jacobsens Allé 15, 2300 København S, Danmark**
- (54) Benævnelse: **ROBOT MED POSITIONERINGSMIDLER TIL BEVÆGELSE AF ET VÆRKTØJ LANGS EN FLANGEFORBINDELSE**
- (56) Fremdragne publikationer:
EP-A1- 2 671 673
EP-B1- 2 607 685
WO-A1-2015/152728
US-A- 4 879 927

DESCRIPTION

[0001] The present invention is related to a robot to tighten a series of nuts pre-screwed on bolts arranged in a linear or in a particular curved flange connection, which bolts project from the nuts pre-screwed in substantially a nut plane by a projection length, which robot comprises a drive to move the robot along the curved flange connection and a tool to tighten the nuts with a predefined torque both connected to a support platform.

[0002] The present invention is furthermore related to a method to tighten a series of nuts pre-screwed on bolts arranged in a linear or in a particular curved flange connection with a robot, which bolts project from the nuts pre-screwed in substantially a nut plane by a projection length and which robot comprises a drive to move the robot along the curved flange connection and a tool to tighten the nuts with a predefined torque both connected to a support platform.

[0003] During the erection of buildings, machines, facilities, plants or similar structures large amounts of bolt connections, especially such ones arranged in curved flange connections involving large quantities of bolts of large size, need to be tightened. Often this has to be done in places difficult or dangerous to access, as for example during the erection of wind turbines, oil platforms, pipelines, etc. In addition, a high level of quality is needed in order to ensure the stiffness and strength of such connections.

[0004] Today, in such bolt connections the pre-screwed nuts are typically tightened on the bolts manually. Hereby, this procedure applies a specified preload, usually a predefined torque, to the pre-screwed nuts. In general, two different methods are used to tighten the nuts with such a predefined torque: In the bolt stretching method, tension is applied to the bolt by stretching the bolt by a physical elongation and tightening the nut with a predefined torque; in the torque wrench method, tension is applied to the bolt by applying the predefined torque to the nut with a torque wrench. The bolt stretching method is regarded to provide a higher quality and is therefore preferred. Nevertheless, in order to obtain a physical elongation of the bolt in a pre-screwed flange connection, the bolt needs to be clamped or fixed at its threaded portion and pulled away from the flange such that the nut can be tightened. Since the engagement of a tool with the threaded portion of the bolt demands very high accuracy and caution, the tightening procedure is done manually. Hence, such manual tightening processes are very risky, time-consuming, expensive, and moreover, difficult to be automated.

[0005] EP 2 607 685 B1 discloses a robot to bolt down a series of nut bolts in a joint circular flange connection of a wind turbine. The robot can carry a tool to bolt down nut bolts with a predefined torque and a position sensor to position the tool above the nut bolt to be bolted down.

[0006] This known robot has the disadvantage that it is not able to automatically align a tool with the bolts in such a precise way that it may perform the bolt stretching method in order to tighten nuts pre-screwed on bolts arranged in a curved flange connection.

[0007] EP 2 671 673 A1 discloses a robot according to the preamble of claim 1. US 4 879 927 A also discloses a robot related to screwing and unscrewing a nut.

[0008] It is an objective of the presented invention to provide a robot to automatically align a tool, which is able to elongate a bolt and tighten a pre-screwed nut, with the bolt in such a precise way that it avoids the drawback of the known robot.

[0009] This objective is achieved with a robot according to claim 1. Such a robot comprises a tool that is built to screw a tension nut onto the bolt and to elongate the bolt and to tighten the pre-screwed nut with a predefined torque with a tightening wheel, and with a robot that comprises positioning means to substantially align the axis of the tension nut with the axis of the bolt to screw the tension nut onto the bolt.

[0010] It is furthermore an objective of the presented invention to provide a method to automatically align such a tool, which is able to elongate a bolt and tighten a pre-screwed nut, with the bolt in such a precise way that it avoids the drawback of the known robot.

[0011] This objective is achieved with a method according to claim 11 that comprises the following steps:

Position the tool in a way to substantially align the axis of a tension nut of the tool with the axis of the bolt;

Screw the tension nut onto the bolt;

Elongate the bolt;

Tighten the nut with the predefined torque with a tightening wheel of the tool.

[0012] The robot according to the invention comprises the advantage that the tool is pin-ended by connection means on a movable mounting platform supported by the support platform and movable substantially along the axis of the tension nut. Since the connection means comprise at least one rounded element to enable tipping of the tool, the axis of the tension nut can be aligned with the axis of the bolt very precisely and smoothly. Thus, the tool can be lowered onto the bolt in a well-controlled and fully automated way.

[0013] In an advantageous embodiment the first turn of the thread of the tension nut is formed to ease the insertion of the thread of the bolt. In this context, the first turn of the thread of the tension nut compared with a standard metric thread comprises a larger chamfer with a steep angle to ease the insertion of the thread of the bolt. In addition, at least the first turn of the thread of the tension nut compared with a standard metric thread may comprise a reduced cross section by a parallel offset of one of the walls of the thread to create more clearance. Thus, when lowering the tool onto the bolt, the thread of the bolt can be inserted into the

tension nut more easily and with reduced risk of thread damage.

[0014] These and further advantageous embodiments of the invention will be explained based on the following description and the accompanying drawings. The person skilled in the art will understand that various embodiments may be combined.

Figure 1 shows in a perspective view a robot according to a first embodiment of the invention.

Figure 2 shows in a perspective view the robot according to a second embodiment of the invention.

Figure 3A shows detail A of figure 2.

Figure 3B shows detail B of figure 2.

Figure 4 shows in a top view a section parallel to the nut plane of figure 2.

Figure 5A shows in a cross section parallel to a bolt axis an inversely U-shaped guiding bracket in a first embodiment.

Figure 5B shows in a cross section parallel to a bolt axis an inversely U-shaped guiding bracket in a second embodiment.

Figure 6 shows in a perspective view the robot according to a third embodiment of the invention.

Figure 7 shows detail C of figure 6.

Figure 8 shows in a cross section parallel to a bolt axis the robot of figure 6.

Figure 9 shows detail D of figure 8.

Figure 10 shows in a cross section along E-E (figure 11B) a tension nut.

Figure 11A shows in a longitudinal section along F-F the tension nut of figure 10.

Figure 11B shows in a longitudinal section along G-G the tension nut of figure 10.

Figure 12A shows detail H of figure 11B.

Figure 12A shows detail I of figure 11B.

[0015] Figure 1 shows a robot 1 according to a first embodiment of the invention. In this embodiment the robot 1 is used to tighten nuts 2 pre-screwed on bolts 3 arranged in a curved flange connection 4. The curved flange connection 4 is situated closely next to a wall 5. This wall 5 could for example be a wall of a tube segment of a wind turbine tower. The robot 1 comprises a support platform 6, a drive to move the robot 1 along the curved flange connection 4, a movable mounting platform 7, a top plate 8, whereas the movable mounting

platform 7 and the top plate 8 are supported by the support platform 6. The robot 1 furthermore comprises a robot control system 9 to control the tightening procedure and to store and document parameters, and a tool 10 to stretch each bolt 3 with a predefined force and subsequently tighten the corresponding nut 2 with a predefined torque.

[0016] Figure 2 shows the robot 1 according to a second embodiment of the invention. For clarity reasons the curved flange connection 4 is not shown. In this embodiment robot 1 comprises the support platform 6 and the drive. The drive comprises holding means 11, shown in more detail in figure 3A, and a drive element 12, shown in more detail in figure 3B. In addition, figure 4 shows in a top view a section parallel to a nut plane 13. Nut plane 13 is substantially perpendicular to bolt axes 14. In figure 4 the nut plane 13 coincidences with the image plane. Nuts 2 are pre-screwed in substantially the nut plane 13 and the bolts 3 project from the nuts 2 by a projection length 15. Substantially in the nut plane 13 means that there is a particular tolerance that allows some or the nuts 2 to be pre-screwed onto the bolts 3 a bit more than others.

[0017] In the second embodiment holding means 11 of robot 1 comprise two pairs of guiding rails 16 and 17, both connected to the support platform 6 and spaced apart from each other. In principle robot 1 works with any number of pairs of guiding rails 16 and 17. At each pair of guiding rails 16, 17 an inner guiding rail 16 and an outer guiding rail 17 are connected to the support platform 6 in a distance from each other of more than the diameter D of the bolts 3 and less than the width across flat AF of the nuts 2 and they project downwards, substantially parallel to the axes 14 of the bolts 3, more than the projection length 15 from the support platform 6. Hereby, the outer guiding rail 17 is in a radial direction 21 situated further away from a center of the curved flange connection 4 as the inner guiding rail 16. The inner guiding rail 16 holds the robot 1 against forces in the radial direction 21 and the outer guiding rail 17 holds the robot against forces against the radial direction 21. Consequently, the holding means 11 hold the robot 1 on a cover surface 22 of the nuts 2 and ensure that platform 6 does not touch the bolts 3. This enables a save movement of robot 1 along the curved flange connection 4 without much friction.

[0018] To better guide robot 1 along the curved flange connection 4 guiding rails 16 and 17 may be tiltable connected to the support platform 6 in order to tilt them around an axis A essentially parallel to the axes 14 of the bolts 3. In addition, the inner guiding rail 16 and the outer guiding rail 17 according to the second embodiment of the invention comprise inner safety means 23 and outer safety means 24 in order to secure robot 1 from falling or tilting. Falling or tilting may appear if the resulting center of gravity M of robot 1 creates a to big turning moment.

[0019] In order to improve the structural stability of the guiding rails 16 and 17, holding means 11 may be realized as inversely U-shaped guiding brackets, which are tiltable connected to the support platform 6. Such inversely U-shaped guiding brackets are shown in figures 5A and 5B. The inversely U-shaped guiding brackets may be assumed to be formed from three legs, whereas an inner leg forms the inner guiding rail 16 and an outer leg forms the outer guiding

rail 17 and whereas the inner leg and the outer leg are connected by a connection leg 25. The inner leg and the outer leg have an inner length greater than the projection length 15, and the connecting leg 25 has an inner length greater than the diameter D of the bolts 3 and an outer length less than the width across flat AF of the nuts 2. Figure 5A shows the inversely U-shaped guiding bracket in a first embodiment, whereas the center of gravity M acts along an axis that in the radial direction 21 is situated closer to the center of the curved flange connection 4 as the axes 14 of the bolts 3. This enables to realize holding means 11 with outer guiding rail 17 shorter than inner guiding rail 16 what may help to ease the process to tighten nuts 3. Figure 5B shows the inversely U-shaped guiding bracket in a second embodiment, whereas the center of gravity M acts along an axis that in the radial direction 21 is situated nearby or at the same distance to the center of the curved flange connection 4 as the axes 14 of the bolts 3.

[0020] Advantageously, drive element 12 is mounted at the support platform 6 before the holding means 11 along a primary drive direction 18 of the robot 1. Alternatively, the drive element 12 may be mounted at the support platform 6 after or in-between the holding means 11 along the primary drive direction 18. The drive element 12 comprises a motor, not shown in the figures, built to drive engage means that engage into a space between neighboring bolts 3 of the curved flange connection 4. The engage means advantageously comprise a star-shaped radial plate 20, which may comprise at least two, preferably five, arms that gear in-between the space between neighboring bolts 3 in the radial direction 21 of the curved flange connection 4. By engagement of the arms and simultaneous rotation of the radial plate 20 the support platform 6, and consequently the robot 1, is pulled by the drive element 12 and guided by the holding means 11 in order to move along the curved flange connection 4.

[0021] The drive element 12 according to the invention may be realized in different ways. For example the engage means may engage at the curved flange connection 4 by adhesion, friction or other physical and/or chemical forces or mechanisms. The motor may be an electric or pneumatic or hydraulic motor that directly transmits its rotation to the engage means or that transmits its rotation by gears, belts or similar elements. The holding means 11 may move the robot 1 without the drive element 12, for example by a clamp-and-release mechanism of each pair of guiding rails 16, 17.

[0022] Figures 6 to 9 show the robot 1 according to a third embodiment of the invention. The robot 1 comprises the support platform 6, the movable mounting platform 7, the top plate 8, which mounting platform 7 is supported by the support platform 6, and the tool 10. For clarity reasons the drive and the curved flange connection 4 are being omitted. The tool 10 comprises a tension nut 26 and a tightening wheel 35. The robot 1 comprises positioning means to substantially align the axis 28 of the tension nut 26 with the axes 14 of the bolts 3 to screw the tension 26 nut onto the bolts 3.

[0023] In the third embodiment of the invention positioning means of the robot 1 comprise three connection means 27, which are attached to the tool 10. By these connection means 27 the tool 10 is pin-ended on the movable mounting platform 7, whereas rotation within the plane of the mounting platform 7 is prohibited due to this threefold bearing. The connection means

27 comprise a rounded element 29 which acts as the pin of the pin-ended bearing and enables tipping of the tool 10 to align the axis 28 of the tension nut 26 with the axis 14 of the bolt 3 while the tool 10 is lowered and the tension 26 nut is screwed onto the bolt 3.

[0024] Since the movable mounting platform 7 is movable substantially along the axis 28 of the tension nut 26, also the tool 10 is movable substantially along this axis 28. The movable mounting platform 7 may be moved by two axial ball bushings on a rod mounted on the support platform 6, and it may be actuated by using a spindle driven by an electric motor, not shown in the figures. The movable mounting platform 7 can be moved to an upmost resting position. The movable mounting platform 7 is moved into the resting position during the movement of the robot 1 along the curved flange connection 4 and/or if the tool 10 is realigned. The top plate 8 comprises locking means 30 to lock the tool 10 in the resting position. In addition, the connection means 27 comprise an angled surface 31 that interacts with the locking means 30 in order to force the tool 10 into a zero position. Hence, the zero position realigns the tool 10 and is automatically taken as soon as the movable mounting platform 7 is in its resting position. This allows the tool 10 to self-align to the bolts 3 without straining the robot 1 and loosening accuracy demands.

[0025] As soon as the movable mounting platform 7 is moved out of the resting position, the tool 10 is able to tip. Hence, by lowering the tool 10 onto the bolt 3, the axis 28 of the tension nut 26 is able to align with the axis 14 of the bolt 3. The connection means 27 may comprise securing means 32 in order to confine the tipping of the tool 10 and prevent the tool 10 from excessive tilting, rotating or from falling off the robot 1. The securing means 32 may have a female - female or a male - male interface between the tool 10 and the mounting platform 7.

[0026] The positioning means may additionally comprise one or all of the following four features of the tension nut 26 helping to precisely align the axis 28 of the tension nut 26 to the axis 14 of the bolt 3 when lowering the tool 10 onto the bolt 3 as shown in figures 10 to 12B:

1. 1) An angled surface section 33 as introductory part before the turns of thread 34 on the tension nut 26 start.
2. 2) A first turn of the thread 34 of the tension nut 26 that is formed to ease the insertion of the thread of the bolt 3, wherein the first turn of the thread 34 of the tension nut 26 compared with a standard metric thread comprises a larger chamfer with a steep angle W to ease the insertion of the thread of the bolt 3 as shown in figure 12A.
3. 3) The first one or two turns of the thread 34 of the tension nut 26 that compared with the full cross section C_F of a standard metric thread have a reduced cross section C_R by a parallel offset of one of the walls of the thread 34 to create more clearance as shown in figure 12B. Gravity ensures that always the lower side of the thread 34 is in contact with the bolt 3, and that there is no notable contact on the upper side of the thread 34. After the first one or two turns of the thread 34 the full cross section of the thread 34 is being obtained by a slow transition at the upper side of the thread 34. Hereby, there is no noticeable transition between reduced cross section C_R and the full cross section C_F .
4. 4) The first turn of the thread 34 of the tension nut 26 compared with a standard metric

thread that is built in a way to avoid forces onto the first turn of the thread 34 along the axis 28 of the tension nut 26 during elongation of the bolt 3 after more than two turns have been screwed onto the bolt 3. Hereby, a possible deformation of the first turn of the thread 34 is prohibited, improving the possibility of thread engagement between the tension nut 26 and the bolt 3.

[0027] A robot 1 according to the first embodiment and the third embodiment of the invention is suited to automatically tighten a series of nuts 2 pre-screwed on bolts 3 arranged in a curved flange connection 4. Such a method may be characterized in that the following steps are processed:

1. 1) After the robot 1 is positioned on the curved flange connection 4 the robot 1 itself positions the tool 10 in a way to substantially align the axis 28 of the tension nut 26 of the tool 10 with the axis 14 of the bolt 3. This first coarse positioning of the tool 10 may be done by a position sensor or by a software routine, whereas the robot 1 is moved along the curved flange connection 4 by the drive. Subsequently, the fine positioning of the tool 10 is done by the positioning means as described before.
2. 2) The tool 10 screws the tension nut 26 onto only a part or all of the thread of the projection length 15 of the bolt 3, wherein the axis 28 of the tension nut 26 is tipped in order to match with the thread of the projection length 15 of the bolt 3. The rotation of the tension nut 26 may be done by a motor.
3. 3) The tool 10 pulls the bolt 3 along the axis 28 of the tension nut 26. This causes a stretching and physical elongation of the bolt 3, in practice for example in excess of 2 mm. This stretching causes the bolt 3 to lift off of the curved flange connection 4. For pulling the bolt 3 a hydraulic device may be used, wherein hydraulic oil from a small pump acts upon a piston connected to the tension nut 26. Thus, the stretching or physical elongation in the bolt 3 is effectively controlled by hydraulic pressure, if the tension is proportional to the hydraulic pressure.
4. 4) The corresponding nut 2, which is simultaneously lifted of the curved flange connection 4 with the bolt 3, is rotated and tightened by the tightening wheel 35 until it again has contact with the curved flange connection 4 and a predefined torque is achieved. The tightening wheel 35 may be rotated by gears driven by a motor.

[0028] As soon as the pull on the bolt 3 is relaxed, the bolt 3 carries the same load as the tool 10 previously exerted on the bolt 3 and the physical elongation and tension remains. The robot 1 may now be moved to the next bolt 3.

[0029] The robot 1 works similar, if the nuts 2 are to be loosened. In this case, the nut 2 is turned by the tightening wheel 35 away from the curved flange connection 4 by a controlled amount that is larger than the physical elongation of the bolt 3.

[0030] The term tighten or tightening in the claims and description should be understood to cover the meaning of the terms bolt down or torqueing or preload or pre-stress or screw down.

[0031] The robot 1 according to the invention may also carry a tool comprising a bolt tightening tool, torque wrench, a robot control system, a camera, a position sensor, measuring instrument, or combinations thereof. Thereby, robot 1 may also be used for inspection or service purposes. Robot 1 may be used for any kind of flange connection in any kind of technical building, machines, facility, plant or any similar structure. Robot 1 for instance could be used to flange connections of tube segments of oil platforms, pipelines, wind turbines, windmills, or towers used as antenna mast or look-out.

[0032] A robot according to a further embodiment of the invention could be adopted to move a support platform along a series of nuts arranged in a linear flange connection or a rectangular flange connection. This has the advantage that nuts of a linear flange connection to e.g. mount a large motor to concrete in the ground could be tightened by the robot.

[0033] The term "nut" does not only include elements as standardized with an internal screw thread and a hexagonal outer surface, but does include any element with an internal screw thread and an outer surface of any form. This includes for instance an element with an internal screw thread and a cylindrical outer surface. The tightening wheel could for instance comprise a rubber surface to tighten the pre-screwed nut with the cylindrical outer surface with a predefined torque. The term "bolt" also includes elements that only for part of their length comprise an external thread to enable the tightening of the nuts. Such a bolt could also be a step shaped cylindrical shaft with a threaded end.

[0034] The mast of a wind turbine may have elements of conical shape with a diameter that reduces the higher the mast gets. In this case walls 5 would be slightly inclined towards the center and bolt axes 14 would be slightly inclined as well. As a result the nut plane would still be substantially perpendicular to bolt axes 14 close by, but not a complete flat plane.

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- EP2607685B1 **[0005]**

- EP2671673A1 [0007]
- US4879927A [0007]

Patentkrav

1. Robot (1) til fastspænding af en række af møtrikker (2), som på forhånd er påskruet bolte (3), der er anbragt i en lineær eller en særligt krum flangeforbindelse (4), hvilke bolte (3) rager ud fra møtrikkerne (2), som på forhånd er skruet i det væsentlige i et møtrikplan (13) med en udragningslængde (15), hvilken robot (1) omfatter en drivindretning til at bevæge robotten (1) langs den krumme flangeforbindelse (4) og et værktøj (10) til fastspænding af møtrikkerne (2) med et foruddefineret tilspændingsmoment, som begge er forbundet med en støtteplatform (6), **kendetegnet ved, at** værktøjet (10) er konstrueret til at skrue en strammemøtrik (26) på bolten (3) for at udvide bolten (3) og til at fastspænde den på forhånd påskruede møtrik (2) med det foruddefinerede tilspændingsmoment med et fastspændingshjul (35), hvilken robot (1) omfatter positioneringsmidler til i det væsentlige at bringe aksens (28) af strammemøtrikken (26) til at flygte med aksens (14) af bolten (3) ved at nedsænke værktøjet (10) på bolten (3) for at skrue strammemøtrikken (26) på bolten (3).
2. Robot (1) ifølge krav 1, hvor værktøjet (10) ved hjælp af forbindelsesmidler (27) er påhængslet en bevægelig monteringsplatform (7), som er understøttet af støtteplatformen (6) og er bevægelig i det væsentlige langs aksens (28) af strammemøtrikken (26), hvilke forbindelsesmidler (27) omfatter mindst et afrundet element (29) for at gøre det muligt at tippe værktøjet (10) for at bringe aksens (28) af strammemøtrikken (26) til at flygte med aksens (14) af bolten (3).
3. Robot (1) ifølge et af kravene 1 eller 2, hvor mindst den første omdrejning af strammemøtrikkens (26) gevind (34) er udformet til at lette indsætningen af boltens (3) gevind.
4. Robot (1) ifølge krav 3, hvor den første omdrejning af strammemøtrikkens (26) gevind (34) sammenlignet med et metrisk standardgevind omfatter en større affasning med en trinvinkel (W) for at lette indsætningen af boltens (3) gevind.
5. Robot (1) ifølge et af kravene 3 eller 4, hvor mindst den første omdrejning af strammemøtrikkens (26) gevind (34) sammenlignet med et metrisk standardgevind omfatter et reduceret tværsnit (C_R) ved en parallel forskydning af

en af væggene af gevindet (34) for at skabe mere mellemrum.

5 **6.** Robot (1) ifølge et af kravene 3 til 5, hvor mindst den første omdrejning af strammemøtrikkens (26) gevind (34) sammenlignet med et metrisk standard-gevind er konstrueret på en sådan måde, at der undgås kræfter på den første omdrejning af gevindet (34) langs akse (28) af strammemøtrikken (26) under udvidelsen af bolten (3), efter at mere end to omdrejninger er blevet påskruet bolten (3).

10 **7.** Robot (1) ifølge et af kravene 2 til 6, hvor støtteplatformen (6) understøtter en topplade (8) med fastlåsningsmidler (30) til fastlåsning af værktøjet (10) i en hvileposition af den bevægelige monteringsplatform (7).

15 **8.** Robot (1) ifølge krav 7, hvor forbindelsesmidlerne (27) omfatter mindst en vinklet overflade (31), som er konstrueret til at samvirke med fastlåsningsmidlerne (30) og til at tvinge værktøjet (10) til en nulposition, hvor den bevægelige monteringsplatform (7) er i hvilepositionen.

20 **9.** Robot (1) ifølge et af kravene 2 til 8, hvor forbindelsesmidlerne (27) omfatter fastgøringsmidler (32) for at begrænse værktøjets (10) tipning.

25 **10.** System af en lineær eller en særligt krum flangeforbindelse (4) og en robot (1) til fastspænding af en række af møtrikker (2), som på forhånd er påskruet bolte (3), som er anbragt i en krum flangeforbindelse (4), hvilke bolte (3) rager ud fra møtrikkerne (2), som på forhånd er skruet i det væsentlige i et møtrikplan (13) med en udragningslængde (15), hvilken robot (1) omfatter en drivindretning til at bevæge robotten (1) langs den krumme flangeforbindelse (4) og et værktøj (10) til fastspænding af møtrikkerne (2) med et foruddefineret tilspændingsmoment, som begge er forbundet med en støtteplatform (6), **kendeteg-**
30 **net ved, at** robotten (1) omfatter elementerne ifølge et af kravene 1 til 9.

35 **11.** Fremgangsmåde til fastspænding af en række af møtrikker (2), som på forhånd er påskruet bolte (3), som er anbragt i en lineær eller en særligt krum flangeforbindelse (4) med en robot (1), hvilke bolte (3) rager ud fra møtrikkerne (2), som på forhånd er skruet i det væsentlige i et møtrikplan (13) med en udragningslængde (15), og hvilken robot (1) omfatter en drivindretning til at



bevæge robotten (1) langs den krumme flangeforbindelse (4) og et værktøj (10) til fastspænding af møtrikkerne (2) med et foruddefineret tilspændingsmoment, som begge er forbundet med en støtteplatform (6), **kendetegnet ved, at** de følgende trin udføres:

- 5 Positioner værktøjet (10) på en sådan måde, at aksens (28) af en strammemøtrik (26) af værktøjet (10) bringes i det væsentlige til at flugte med aksens (14) af bolten (3) ved at nedsænke værktøjet (10) på bolten (3);
Skrue strammemøtrikken (26) på bolten (3);
Udvid bolten (3);

- 10 Fastspænd møtrikken (2) med det foruddefinerede tilspændingsmoment med et fastspændingshjul (35) af værktøjet (10).

- 15 **12.** Fremgangsmåde ifølge krav 11, hvor aksens (28) af værktøjets (10) strammemøtrik (26) tippes, mens strammemøtrikken (26) påskrues bolten (3).

DRAWINGS






FIG. 3A




FIG. 3B




FIG. 4




FIG. 5A




FIG. 5B




FIG. 6




FIG. 7






FIG. 8






FIG. 11A




FIG. 11B




FIG. 12A




FIG. 12B