

(19) **DANMARK**



Patent- og
Varemærkestyrelsen

(10) **DK/EP 2663254 T3**

(12) Oversættelse af
europæisk patentskrift

-
- (51) Int.Cl.: **A 61 C 8/00 (2006.01)** **A 61 C 13/00 (2006.01)**
- (45) Oversættelsen bekendtgjort den: **2020-08-31**
- (80) Dato for Den Europæiske Patentmyndigheds
bekendtgørelse om meddelelse af patentet: **2020-07-29**
- (86) Europæisk ansøgning nr.: **12703590.5**
- (86) Europæisk indleveringsdag: **2012-01-12**
- (87) Den europæiske ansøgnings publiceringsdag: **2013-11-20**
- (86) International ansøgning nr.: **IL2012050011**
- (87) Internationalt publikationsnr.: **WO2012095851**
- (30) Prioritet: **2011-01-13 US 201161432247 P**
- (84) Designerede stater: **AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV
MC MK MT NL NO PL PT RO RS SE SI SK SM TR**
- (73) Patenthaver: **Align Technology, Inc., 2820 Orchard Parkway, San Jose, CA 95134, USA**
- (72) Opfinder: **KOPELMAN, Avi, 776 Josina Avenue, Palo Alto, California 94306, USA**
- (74) Fuldmægtig i Danmark: **Zacco Denmark A/S, Arne Jacobsens Allé 15, 2300 København S, Danmark**
- (54) Benævnelse: **Fremgangsmåder, systemer og tilbehør, der kan anvendes til procedurer vedrørende
tandimplantater**
- (56) Fremdragne publikationer:
WO-A1-2009/027316
WO-A1-2009/146164
DE-U1-202006 017 574
US-A- 5 527 182
US-A1- 2007 224 576

DESCRIPTION

[0001] The presently disclosed subject matter relates to dental implants and to dental models, in particular to methods, systems and accessories useful in procedures relating to dental implants. In particular, the presently disclosed subject matter relates to methods, systems and accessories for preparing a physical dental model for use with an analog of a dental implant, to physical models prepared in this manner, and to dental analogs for use with such physical models.

BACKGROUND

[0002] Dental implants are widely used as artificial substitutes for the root portion of missing teeth, and allow a tooth prosthesis to be securely anchored to the jaw, for example via a permanent abutment mounted to the implant. Endosseous implants generally comprise an externally threaded body, often self-taping into the bone tissues, and further comprise an internal chamber that is configured, typically internally threaded, for receiving and securing therein the anchoring stem of a permanent abutment therein.

[0003] Also well known in the art are dental analogs, each of which is a replica of a corresponding dental implant. A dental analog has an internal passage and an interface structure that are respectively identical to the internal passage and interface structure of the implant that is designed to receive, engage and secure the prosthesis and permanent abutment; however, in contrast to the dental implant, the dental analog is not intended for implantation in a human, but rather for use with a physical model of the intraoral cavity or part thereof.

[0004] Conventionally, following implantation of a dental implant in the intra oral cavity and healing of the surrounding tissues, a physical model of the intra oral cavity is often produced for facilitating design and manufacture of the permanent abutment and the prosthesis or other restoration that is to be eventually mounted onto the implant. In one procedure, an impression abutment is mounted to the implant so that it projects into the intra oral cavity, and an impression is then obtained of the intraoral cavity using well known techniques (for example, as are known in the art regarding fixture level impressions) and impression materials, for example PVS. The impression abutment can be of the pick-up type, to be embedded with the impression material and retained therein after the impression tray is removed. Alternatively the impression tray is removed without the impression abutment attached thereto, but nevertheless having a recess formed therein complementary to the outer shape of the impression abutment, enabling the transfer-type impression abutment to be mounted therein at a later time. Subsequently an analog, corresponding to the particular implant that is implanted in the patient, is attached to the impression abutment, which is in situ in the impression material, and plaster is poured into the impression tray including the analog to produce a positive plaster model of the intraoral cavity with the analog embedded. The analog is in a

spatial disposition, i.e., at a position and orientation, in the plaster model corresponding to the spatial disposition of the implant in the patient's intra oral cavity. The dental technician can now attach a permanent abutment, or custom design a permanent abutment to fit the implant, and build a coping or bridge framework or prosthesis to fit into the intraoral cavity of the patient.

[0005] US 2010/0021859, assigned to the present Assignee, discloses a method and system for manufacturing a physical dental model. A virtual model is provided representative of at least a portion of the intra-oral cavity including at least one dental implant implanted therein, and the virtual model includes a virtual portion representative of each dental implant. A physical model is then manufactured based on the virtual model, the physical model including a physical analog corresponding to each implant at a respective physical spatial disposition with respect to the physical model corresponding to the respective virtual spatial disposition of the respective virtual portion with respect to the first virtual model

[0006] WO 2009/146164 A1 discloses a method for creating a virtual model usable for making a physical model of a physical dental structure of a patient.

[0007] By way of general background, the following publications relate to implants, analogs or to dental procedures relating to dental implants or analogs: US 6,358,052, US 2010/0112527, US 2008/032262, US 2007/0092854, US 2006/183078, US 2003/0162148, WO 2010/108919, US 2011/294093.

[0008] Herein the "the coronal direction" with respect to a tooth refers to the direction originating from the region of the tooth root below the jaw towards the region of the crown above the jaw, while "the apical direction", refers to the direction opposite to the coronal direction.

SUMMARY

[0009] Herein "operating on" with respect to a virtual entity, for example a virtual model of the dental structure, a virtual analog installation structure, and so on, refers to conducting one or more of the following operations on the virtual entity with respect to any spatial coordinate system: translating, rotating, scaling, transforming, modifying, adding spatial data (for example adding virtual components), subtracting spatial data (for example removing, deleting or replacing virtual components).

[0010] The invention pertains to a method for creating a virtual model usable for making a physical model of a physical dental structure that includes a dental implant at an implant site as defined in claim 1. Further embodiments are set out in the appended dependent claims.

[0011] According to a first aspect of the presently disclosed subject matter a system and a method are provided for manufacturing a physical model of a dental structure that includes a dental implant, in which a dental analog can be inserted into the physical model in a general

coronal direction.

[0012] According to the first aspect of the presently disclosed subject matter there is also provided a method for creating a virtual model usable for making a physical model of a physical dental structure that includes a dental implant at an implant site, the method comprising:

using a computer system:

1. (a) receiving a virtual representation of dental surfaces of the physical dental structure with dental implant data representing a location and orientation of the dental implant with respect to the dental surfaces;
2. (b) receiving a virtual analog structure, the virtual analog structure being based on said dental implant; and
3. (c) creating the virtual model based on:
 - said virtual representation of dental surfaces; and
 - a virtual analog socket structure based on said virtual analog structure and said dental implant data, and having an virtual analog insertion opening that is spaced from parts of the virtual model corresponding to dental surfaces and the implant site.

[0013] According to this aspect of the presently disclosed subject matter there is also provided a method for manufacturing a physical model of a physical dental structure that includes dental surfaces and a dental implant at an implant site, for use with a dental analog corresponding to the dental implant, the method comprising:

receiving a virtual model of the physical dental structure and a virtual analog installation structure in association with said virtual model, said virtual analog installation structure being based on the dental analog;

using said virtual model, manufacturing a physical model corresponding to said virtual model, the physical model being provided with an analog installation structure based on said virtual analog installation structure and thereby configured for enabling the dental analog to be inserted into said physical model through an insertion opening,

wherein said insertion opening is spaced from a location in the physical model corresponding to the implant site in the physical dental structure.

[0014] According to this aspect of the presently disclosed subject matter there is also provided a physical model of a dental structure, the dental structure including a dental implant at an implant site, the physical model being configured for enabling insertion therein of a dental analog corresponding to the dental implant via an insertion opening that is spaced from a model implant site location on the physical model corresponding to the implant site.

[0015] According to this aspect of the presently disclosed subject matter there is also provided a dental analog configured for being inserted into a passageway of a physical model of a dental structure, which dental structure includes a dental implant at an implant site, the passageway including an insertion opening and a second opening corresponding to the implant site, said second opening having a smaller maximum width than a maximum width of said insertion opening. For example, the dental analog comprises a first analog end corresponding to said insertion opening and a second analog end corresponding to said second opening, wherein said second analog end has a smaller maximum width than a maximum width of said first analog end.

[0016] According to the first aspect of the presently disclosed subject matter a system and a method are provided for manufacturing a physical model of a dental structure that includes a dental implant, in which the physical model comprises a dental surface portion representative of the dental surfaces of the dental structure and a base portion, the physical model being configured for enabling insertion of a dental analog into the physical model via the base portion. According to the first aspect of the presently disclosed subject matter there is also provided a physical model of a dental structure that includes a dental implant, the physical model comprising a dental surface portion representative of the dental surfaces of the dental structure and a base portion, and the physical model being configured for enabling insertion of a dental analog into the physical model via the base portion.

[0017] According to a second aspect of the presently disclosed subject matter there is provided a system and method for manufacturing a composite physical dental model of a dental structure, the method comprising:

1. (a) providing a virtual model of the dental structure;
2. (b) using said virtual model, manufacturing a composite physical model corresponding to said virtual model, the physical model including a first model part and a second model part having at least one physical property different from a physical property of said first model part, wherein said first model part and said second model part are previously defined in said virtual model, and wherein said at least one physical property excludes a surface topology.

[0018] A feature of at least one example according to the first aspect and/or second aspect of the presently disclosed subject matter is that the insertion path of the physical analog is substantially independent of the topology of the dental surfaces in the vicinity of the implant site. This can facilitate installation of the respective analog for example in cases where trying to insert the analog in the physical model in an apical direction would be difficult or impossible because of potential collision with surrounding dental structures, for example, where the respective dental implant is at an awkward or shallow angle with respect to the gums and the surrounding teeth.

[0019] Another feature of at least one example according to the first aspect and/or second aspect of the presently disclosed subject matter is that the physical model in the vicinity of the opening around the analog can be defined with relatively high accuracy, since the method of installation of the analog does not require any surface detail in this part of the physical model to be disturbed, which can sometimes be the case if the analog were to be installed instead in the physical model in an apical direction.

[0020] In at least one example the physical model thus prepared according to the first aspect and/or second aspect of the presently disclosed subject matter can assist the dental technician in the design and/or preparation of the permanent abutment, coping, prosthesis and so on, in a manner known in the art. Such a prosthesis can include, for example, a custom abutment and a crown, a custom abutment and a bridge, a complete crown mounted directly to the implant, a complete bridge mounted directly to the implant, a denture, or a partial denture.

[0021] Optionally, the physical model or the composite model can be configured for mounting onto any dental articulator.

BRIEF DESCRIPTION OF THE DRAWINGS

[0022] In order to understand the presently disclosed subject matter and to see how it may be carried out in practice, examples will now be described, by way of non-limiting example only, with reference to the accompanying drawings, in which:

Fig. 1 illustrates in cross-sectional side view a dental structure including an example of a dental implant implanted therein in the place of a removed tooth; **Fig. 1(a)** illustrates in exploded view an example of prosthesis set including an abutment, prosthesis and retainer screw for the example of the dental implant of Fig. 1.

Fig. 2 schematically illustrates an example of a general coronal direction with respect to a spatial coordinate system referenced to the removed tooth and dental structure of Fig. 1.

Fig. 3 is a schematic illustration of an example of a system according to a first aspect of the presently disclosed subject matter.

Fig. 4 is a schematic illustration of an example of a method according to a first aspect of the presently disclosed subject matter; **Fig. 4(a)** is a schematic illustration of an example of step 450 of Fig. 4; **Fig. 4(b)** is a schematic illustration of a variation of the example of Fig. 4; **Fig. 4(c)** is a schematic illustration of an example of a method for creating a virtual model according to a first aspect of the presently disclosed subject matter.

Fig. 5 illustrates in cross-sectional side view an example of a dental model corresponding to the dental structure of Fig. 1 and including a corresponding example of a dental analog inserted therein.

Fig. 6(a) illustrates in isometric view the dental analog example of Fig. 5; **Fig. 6(b) to 6(d)**

respectively illustrate in isometric view alternative variations of the dental analog example of Fig. 6(a); **Fig. 6(e)** illustrates in cross-sectional side view the dental analog example of Fig. 6(a) used in a variation of the example of a physical model of Fig. 5; **Fig. 6(f)** illustrates in cross-sectional side view another variation of the dental analog example of Fig. 6(a) inserted into another variation of the example of the physical model of Fig. 5; **Fig. 6(g)** illustrates in cross-sectional side view another variation of the dental analog example of Fig. 6(a) inserted into another variation of the example of the physical model of Fig. 5; **Fig. 6(h)** illustrates in cross-sectional side view another variation of the dental analog example of Fig. 6(a) inserted into another variation of the example of the physical model of Fig. 5; **Fig. 6(g)** illustrates in cross-sectional front view another variation of the dental analog example of Fig. 6(a) inserted into another variation of the example of the physical model of Fig. 5.

Fig. 7 illustrates in cross-sectional side view another example of a dental model corresponding to the dental structure of Fig. 1 and including a corresponding example of a dental analog inserted therein.

Fig. 8 illustrates in cross-sectional side view another example of a dental model corresponding to the dental structure of Fig. 1 and including a corresponding example of a dental analog inserted therein; **Fig. 8(a)** illustrates in isometric view the dental analog example of Fig. 8; **Fig. 8(b)** illustrates in isometric view a variation of the dental analog example of Fig. 8(a).

Fig. 9 illustrates in cross-sectional side view another example of a dental model corresponding to the dental structure of Fig. 1 and including a corresponding example of a dental analog inserted therein.

Fig. 10 illustrates in cross-sectional side view an example of a virtual model corresponding to the physical dental model of Fig. 5 and including a corresponding example of a virtual dental analog virtually inserted therein.

Fig. 11 illustrates in cross-sectional side view another example of a dental model corresponding to the dental structure of Fig. 1 and including a corresponding example of a dental analog inserted therein.

Fig. 12 illustrates in cross-sectional side view another example of a dental model corresponding to the dental structure of Fig. 1 and including a corresponding example of a dental analog inserted therein using a jig.

Fig. 13 is a schematic illustration of an example of a method according to a second aspect of the presently disclosed subject matter; **Fig. 13(a)** is a schematic illustration of an example of step 950 of Fig. 11.

Figs. 14(a) to 14(c) illustrate in side view a number of stages associated with providing a composite physical model example according to the second aspect of the presently disclosed subject matter; **Fig. 14(a)** illustrates in cross-sectional side view a virtual model example according to this aspect of the presently disclosed subject matter; **Fig. 14(b)** separately illustrates in cross-sectional side view a hard part and a soft part of composite physical model corresponding to the virtual model example of Fig. 14(a); **Fig. 14(c)** illustrates in cross-

sectional side view the example of Fig. 14(b) with the soft part engaged with the hard part of the composite physical model example, and with the analog of the example of Fig. 6(a) accommodated at the installed position in the composite physical model example.

DETAILED DESCRIPTION

[0023] According to a first aspect of the presently disclosed subject matter there is provided a system and method for use in dental implant procedures, in particular for designing and manufacturing a physical dental model (also referred to interchangeably herein as a physical model) of a dental structure, based on and corresponding to a virtual dental model (also referred to interchangeably herein as a virtual model) of the dental structure.

[0024] Referring to Fig. 1, there is illustrated an example of such a dental structure, designated in this figure with the reference numeral **100**. The dental structure **100** is part of the intra-oral cavity of a patient, in particular a visually exposed part of the intra-oral cavity of the patient, and can include partial or the full mandibular or maxillary arches, or both arches. Furthermore, the dental structure **100** includes a dental implant **240** implanted therein at a particular implant site **150**, and which replaces, in part, a tooth **T** (Fig. 2) that was previously removed. The dental structure **100** comprises dental surfaces **115**, including hard dental surfaces **110** and soft dental surfaces **120** thereof. Such hard surfaces **110** can include, for example, teeth and/or dental prostheses that are mounted to the intra-oral cavity of the patient in the vicinity of the dental implant site **150**, while such soft dental surfaces **120** can include the gum, for example gingival surfaces that surround the implant. As will become clearer herein, the term "dental structure" can also refer, *mutatis mutandis*, to an existing physical model of the aforesaid part of the intra-oral cavity of the patient, in which a portion of the existing physical model is shaped to represent the exposed surfaces of the dental implant that is implanted in the intra-oral cavity of the patient. For example, such an existing physical model can be produced using conventional impression and casting techniques, which are well known in the art. In such an example of the dental structure **100** in the form of an existing physical model, the hard dental surfaces **110** and soft dental surfaces **120** thereof are surfaces of the existing physical model that represent the respective hard dental surfaces and soft dental surfaces of the intraoral cavity of the patient.

[0025] Referring again to Fig. 1, the dental implant **240** is illustrated in the implanted position with respect to the dental structure **100**, i.e., at a particular and fixed spatial disposition **P** with respect to dental structure **100**.

[0026] Herein, by spatial disposition **P** is meant the orientation and the spatial position, or the orientation and the spatial location, in 3D space of the dental implant **240** with respect to the dental structure **100**, in particular with respect to some or all of the dental surfaces **115**.

[0027] The dental implant **240** can comprise any suitable implant configuration that is commercially available or alternatively that is custom made. The dental implant **240** in this example comprises a prosthesis interface implant part **248** and a prosthesis engaging implant part **241**, and is engaged to the dental structure **100** via an anchoring structure such as external screw threads **242**. For example, prosthesis interface implant part **248** can comprise a hexagonal counter-bored configuration and the prosthesis engaging implant part **241** can comprise an internally threaded well, compatible with many types of commercially available prostheses; other configurations for these components can of course be comprised, instead, in the dental implant. For example the dental implant can comprise a Morse taper connection; and/or can be configured for use with a screw retained crown or a cemented crown; and/or can be configured for straight or angulated abutments.

[0028] Referring to Fig. 1(a), an example of a prosthesis system **991** is illustrated for use with dental implant **240**. In this example, the prosthesis system **991** includes a dental prosthesis **990** that can be mounted to the dental implant **240** via a permanent abutment **995** and retainer screw **996**. The prosthesis interface implant part **248** and the prosthesis engaging implant part **241** mate with and engage to a complementary structure in the dental prosthesis **990** and/or permanent abutment **995**.

[0029] While the following examples are each directed to a case of a single implant implanted in the dental structure, it is readily appreciated that the system and method are readily applicable in a similar manner, *mutatis mutandis*, to cases in which there is a plurality of implants that can be implanted in the intraoral cavity of a patient, whether the implants are independent from one another, each being used for a separate prosthesis, or whether at least some of the implants are to be coupled to be used together for a single bridge prosthesis or other multiple tooth prostheses, dentures, etc., for example.

[0030] As will become readily apparent, corresponding to the dental structure **100**, a physical dental model is manufactured according to the first aspect of the presently disclosed subject matter including physical model surfaces that are representative of at least some of the hard dental surfaces **110** and soft dental surfaces **120** of the dental structure **100**.

[0031] As will also become readily apparent, in at least some examples of the physical model, the physical model includes a passageway having an analog insertion opening in the physical model, for example at a base thereof. The passageway and analog insertion opening are configured to allow a dental analog, corresponding to the dental implant, to be installed into the physical model in an insertion path along an insertion direction, to an installed position in the model.

[0032] In at least some examples, the insertion direction is referred to herein as the respective general coronal direction **K**, as defined below, and is fixed for a particular set of: (a) a physical model and (b) the form or design of the corresponding analog. Referring again to Fig. 1, in some cases, where the dental implant is implanted having its axis **A1** parallel or close to the coronal direction **CO**, the insertion direction for the corresponding implant, i.e., the respective

general coronal direction, can also be parallel or near parallel to coronal direction CO. On the other hand, there are specific cases where the implant has been implanted in a spatial disposition with respect to the dental structure where the axis AI is inclined at a relatively large acute angle to the coronal direction CO. In such cases, and depending on the design of the dental implant, the insertion direction for the implant, i.e., the respective general coronal direction, can also be relatively large acute angle to coronal direction CO.

[0033] In the installed position, the analog is coupled to the physical model in a relative spatial disposition (i.e., at a spatial position/location and orientation in 3D space) with respect to the physical model that corresponds to and replicates the relative spatial disposition between the dental implant and the dental structure. As will become readily apparent, the passageway is first modeled in the corresponding virtual dental model of the dental structure, which in turn enables the physical passageway in the physical model to be manufactured.

[0034] Referring to Fig. 2, an example of a general coronal direction **K** is illustrated with respect to six directions along three orthogonal axes x, y, z of a spatial coordinate system. The spatial coordinate system is, in this example, Cartesian coordinate system XYZ, and is referenced to the removed tooth **T** and with respect to the original location of tooth **T** in the dental structure **100**. The aforesaid six directions include: the true coronal direction CO and the true apical direction AP the removed tooth **T**, along the z-axis; the mesial direction ME and the distal direction DI the removed tooth **T**, along the x-axis; and the buccal direction BU and the lingual direction LI the removed tooth **T**, along the y-axis.

[0035] The "true coronal direction", used herein synonymously with "the coronal direction", refers to the direction originating from the region of the tooth root within the jaw and extending towards the region of the crown above the jaw, with reference to the tooth **T** and with respect to the original location of tooth **T** in the dental structure **100**, at or near the current implant site **150**. Since teeth are sometimes crooked, the true coronal direction CO (and thus the orientation of the respective Cartesian coordinate system XYZ) relative to the jaw can vary between one tooth and another in the same jaw. The "true apical direction", used herein synonymously with "the apical direction", refers to the direction opposite to the true coronal direction.

[0036] A mesial-buccal plane MB can be defined, aligned with the mesial direction ME and the distal direction DI on the one hand, and the buccal direction BU and lingual direction LI on the other hand, i.e., the x-y plane.

[0037] Similarly, a coronal-buccal plane CB can be defined, aligned with the true coronal direction CO and true apical direction AP on the one hand, and the buccal direction BU and lingual direction LI on the other hand, i.e., the z-y plane.

[0038] Similarly, a coronal-mesial plane CM can be defined, aligned with the true coronal direction CO and true apical direction AP on the one hand, and the mesial direction ME and distal direction DI on the other hand, i.e., the z-x plane.

[0039] It is to be noted that by "general coronal direction" **K** is meant any direction having a directional vector that can be angularly displaced from the true coronal direction CO in 3D space by a total angular displacement with respect to the true coronal direction CO not greater than 90°. The term "general coronal direction" thus includes any direction having a directional vector including at least one directional component thereof aligned with true coronal direction CO. Additionally or alternatively, "general coronal direction" is meant any direction having a directional vector that excludes having any directional component thereof aligned with true apical direction AP, i.e., along a non-apical direction.

[0040] The aforesaid total angular displacement, designated as angle θ in Fig. 2, can have a first angular component, angle α , and/or a second angular component, angle β .

[0041] For example, the first angular component, angle α , can be defined as the angular disposition of a first projection **K1** of the general coronal direction **K** on the coronal-mesial plane CM, taken with respect to the true coronal direction CO and towards the mesial direction ME (or instead taken with respect to the true coronal direction CO and towards the distal direction DI).

[0042] For example, the second angular component, angle β , can be defined as the angular disposition of a second projection **K2** of the general coronal direction **K** on the coronal-buccal plane CB, taken with respect to the true coronal direction CO and towards the lingual direction LI (or instead taken with respect to the true coronal direction CO and towards the buccal direction BU).

[0043] Alternatively, one or the other of the first angular component and the second angular component can be replaced with a third angular component, angle φ . Angle φ can be defined as the angular disposition of a third projection **K3** of the general coronal direction **K** on the mesial-buccal plane MB, taken with respect to the mesial direction ME and towards the lingual direction LE (or towards the buccal direction BU), or indeed taken with respect to the distal direction DI and towards the lingual direction LI or towards the buccal direction BU.

[0044] In at least one example, angle α can be zero, so that the general coronal direction **K** lies on the coronal-buccal plane CB. In at least one example angle β can be zero, so that the general coronal direction **K** lies on coronal-mesial plane CM. In at least one example, angle α and angle β can both be zero, so that the general coronal direction **K** is parallel or aligned with the true coronal direction CO.

[0045] It is readily apparent that the first angular component, angle α , and the second angular component, angle β , can be defined on any desired first and second different but mutually-orthogonal planes that include the coronal direction CO, such planes being optionally different from the coronal-mesial plane CM or the coronal-buccal plane CB. This automatically defines a third angular component of the absolute angular displacement along a third plane orthogonal to the first and second planes.

[0046] It is also readily apparent that the total angular displacement, angle θ , between the general coronal direction **K** and the true coronal direction **CO** can be defined with respect to any suitable spatial coordinate system other than the Cartesian coordinate system **XYZ**. For example, the total angular displacement, angle θ , can be defined with respect to a spherical coordinate system, referenced to the coronal-apical z-axis and the mesial-buccal plane **MB**, and thus via a respective elevation and a respective azimuth corresponding to the general coronal direction **K**.

[0047] By way of non-limiting example, the total angular displacement, angle θ , between the general coronal direction **K** and the true coronal direction **CO** is fixed for a particular physical model and corresponding analog to be used therewith, and can be any specific angle in the range from 0° to 90° , or in the range from 0° to about 60° , or in the range from 0° to about 45° , or in the range from 0° to about 30° , or in the range from 0° to about 20° , or in the range from 0° to about 10° , or in the range from 0° to about 5° , or in any other range between 0° and 90° .

[0048] Thus, as will become readily apparent, in at least some examples the general coronal insertion direction **K** of the dental analog with respect to the physical model can be such as to provide an insertion path into the physical model that is aligned with a longitudinal axis of the dental analog, for example, even in cases where the corresponding longitudinal axis of the respective dental implant is severely displaced angularly from the true coronal direction **CO**.

[0049] As will become readily apparent, in at least some examples, the respective analog is inserted into the corresponding physical model in a direction opposite to the direction in which the dental implant is installed in the corresponding dental structure.

[0050] As will also become readily apparent, in at least some examples, the respective analog is inserted into the corresponding physical model in a direction passing through a part of the physical model representative of dental surfaces **115**, from a first location with respect to the physical model corresponding to an inside of the dental structure to a second location with respect to the physical model corresponding to an outside of the dental structure.

[0051] As will also become readily apparent, in at least some examples of the aforesaid method and system, the general coronal insertion direction **K** for an analog with respect to the respective physical model provides an insertion path into the physical model for the implant that inherently avoids collision with at least model dental surface parts of the physical model that represent the real dental surfaces of the dental structure **100**. In particular, such collision is avoided with respect to model dental surface parts that represent the hard dental surfaces in proximity to the dental implant, for example the teeth adjacent to the implant. Furthermore the insertion path can be such as to avoid having to disturb other parts of the physical model, for example the model dental surface parts thereof that reproduce the soft dental surfaces **120** of the dental structure **100** that are in abutting relationship with the dental implant **240**, for example the gingival surfaces that surround the implant.

[0052] Referring again to Fig. 1, the spatial disposition **P** of the implant **240**, i.e., the spatial position and orientation in 3D space, with respect to the dental structure **100**, can be defined in many different ways. For example, spatial disposition **P** can be defined via the spatial orientation of longitudinal axis **AI** of the dental implant **240** with respect to any chosen coordinate system, together with the spatial position of a point **Q** associated with the dental implant **240** (i.e., having a defined spatial relationship to the dental implant **240**) and which is at a fixed spatial relationship to the longitudinal axis **AI**. For example, point **Q** may be the intersection point between a plane **S** and longitudinal axis **AI**, wherein plane **S** is coplanar with the coronal-facing face **248A** of prosthesis interface implant part **248**. Such a chosen coordinate system is the same coordinate system as may be used for the dental structure **100**, or alternatively has a known and fixed spatial relationship with another coordinate system used for the dental structure **100**.

[0053] Referring to Fig. 5, there is illustrated a first example of a physical model **600**, configured for enabling a first example of the analog **230** to be installed therein via an analog insertion opening **607** (in a respective general coronal direction **K**) to an installed position at a spatial disposition **P'** with respect to the physical model **600**. As will be disclosed in greater detail below, and referring to Figs. 4 and 3, physical model **600** is manufactured according to method **400**, for example using system **200**.

[0054] In Fig. 5, the dental analog **230** is illustrated in the installed position with respect to physical model **600**, at a spatial disposition **P'**, the dental analog **230** corresponding to and essentially being, in a functional sense with respect to the respective prosthesis system **991**, for example, a replica of the dental implant **240**. Referring also to Fig. 6(a), the dental analog **230** comprises, at a coronal end thereof, a prosthesis interface analog part **238** having coronal-facing face **269**, and a prosthesis engaging analog part **231** that correspond to and are essentially identical to the prosthesis interface implant part **248**, coronal-facing face **248A** and the prosthesis engaging implant part **241**, respectively. The dental analog **230** also comprises a longitudinal axis **AA** corresponding to longitudinal axis **AI** of the dental implant **240**, wherein longitudinal axis **AA** has the same spatial relationship with respect to prosthesis interface analog part **238** and to the prosthesis engaging analog part **231** as longitudinal axis **AI** has with respect to the prosthesis interface implant part **248** and the prosthesis engaging implant part **241**, respectively. Thus, the longitudinal axis **AA** is aligned with respect to the prosthesis interface analog part **238** and the prosthesis engaging analog part **231** of the analog **230**, i.e., aligned with the centerline of the prosthesis engaging analog part **231**, and not necessarily with a centerline referenced to the external form **270** of the dental analog **230**.

[0055] Spatial disposition **P'** with respect to the installed analog **230** at the installed position in the physical model **600** can be defined in any suitable manner, for example in a similar manner to spatial disposition **P**, *mutatis mutandis*. For example, spatial disposition **P'** can be defined via the spatial orientation of longitudinal axis **AA** with respect to any chosen spatial coordinate system, together with the spatial position of a point **Q'** associated with the analog **230** and which is at a fixed spatial relationship to the longitudinal axis **AA**. For example, point **Q'** can correspond to point **Q** of the dental implant **240**, and can be the intersection point between a

plane **S'** and longitudinal axis **AA**, wherein plane **S** is coplanar with the coronal-facing face **269** of prosthesis interface analog part **238**. Such a chosen coordinate system is the same coordinate system as may be used for the physical model **600**, or has a known and fixed spatial relationship with another coordinate system used for the physical model **600**.

[0056] The external form **270** of the dental analog **230** is not configured for implantation in a human, but rather for coupling with the corresponding physical model **600**, at a spatial disposition **P'** with respect thereto that replicates the spatial disposition **P** of the dental implant **240** with respect to dental structure **100** (see also Fig. 1). In particular, in this example, and referring again to Figs. 5 and 6(a), the external form **270** of the dental analog **230** comprises a coronal portion **262** adjacent an enlarged apical portion **264**. The coronal portion **262** has a maximum width that is smaller than a maximum width of the enlarged apical portion **264**. In this example, the enlarged apical portion **264** having a larger cross-sectional area than a cross-sectional area of the coronal portion **262**. In at least some alternative variations of this example, the enlarged apical portion **264** can instead have a portion thereof that projects laterally with respect to the outer surface of the coronal portion **262**.

[0057] Referring in particular to Fig. 6(a), the coronal portion **262** comprises a generally cylindrical outer surface **263** about axis **AA** and that is made asymmetrical via a flat portion **261**. The flat portion **261** extends along the longitudinal length of the coronal portion **262** from coronal-facing face **269** to the coronal face **265** of enlarged apical portion **264**, the coronal face **265** being defined on a plane substantially orthogonal to axis **AA**. The enlarged apical portion **264** acts as mechanical stop arrangement which abuts shoulder **657** formed in the physical model **600** to define the limit of penetration of the analog **230** into the physical model **600** in the respective general coronal direction **K** to the installed position. The enlarged apical portion **264**, in this example, is generally cylindrical and symmetrical about axis **AA**, but can instead have any other symmetrical shape about axis **AA** or any other axis, or can have an asymmetrical shape if desired.

[0058] Referring again to Fig. 5, the first example of physical model **600** comprises a model dental surface part, also referred to as first model part **630**, including an outer model surface **661** representing dental surfaces of the dental structure **100** that are exposed in the dental structure **100**, and a second model part **640** including an analog installation structure **690**. Herein, "analog installation structure" is used interchangeably with "physical analog socket structure".

[0059] Referring to Fig. 1 and Fig. 5, the first model part **630**, and in particular the outer model surface **661**, includes parts **610** that correspond to the hard surfaces **110**, and parts **620** that correspond to the soft surfaces **120**. The first model part **630** also comprises a coronal opening **650** having a perimeter **655** corresponding to the interface **155** between the soft surface **120** and the implant **240** at implant zone **150** of the dental structure **100**.

[0060] Referring to the second model part **640**, the analog installation structure **690** is configured for enabling the analog **230** to be inserted into the model **600** in a respective

general coronal direction **K** to an installed position at spatial disposition **P'** with respect to the model **600** that replicates the spatial disposition **P** of the dental implant **240** with respect to the dental structure **100**. In the installed position, all or part of coronal-facing face **269**, prosthesis interface analog part **238**, and prosthesis engaging analog part **231** of the analog **230** are exposed via the coronal opening **650**. This allows a prosthesis system (e.g., comprising dental prosthesis **990**, permanent abutment **995** and retainer screw **996**, see Fig. 1(a)) to be mounted to the analog **230** with respect to the physical model **600**, in a manner comparable to that intended for the dental implant **240** in the dental structure **100**.

[0061] The second model part **640** further comprises a physical model base **609** having a base surface **603** and defining an apical portion **606**. In this example the base **609** has a length and breadth greater than the overall length and breadth, respectively, of the outer model surface **661**, though in alternative variations of this example the length and/or the breadth of the model base **609** can be the same as or less than the respective length and/or breadth of the outer model surface **661**.

[0062] In this example the base **609** has a height extending in an apical direction away from the outer model surface **661**. In this connection the length and breadth dimensions can be taken along directions orthogonal to the apical-coronal (height) direction. In alternative variations of this example, the model base can be relatively thin or nominal, for example formed by a projection of the outer model surface **661** to a plane, for example orthogonal to the apical direction.

[0063] Analog installation structure **690** comprises a passageway **608** extending in a general coronal direction **K** from analog insertion opening **607**, formed in apical portion **606**, to coronal opening **650**. The coronal opening **650** is also referred to herein as an access opening to the installation structure **690**, located at a location in the physical model corresponding to the location of the implant site **150**. The coronal opening **650** is also referred to herein as an auxiliary opening.

[0064] The passageway **608** is elongate, defining a passageway longitudinal axis aligned with said general coronal direction, and in this example of the analog **230**, the passageway longitudinal axis **BB** is co-axial with a longitudinal axis **AA** of analog **230** when the analog **230** is in the installed position therein. It is to be noted that in other examples of the analog **230**, the passageway longitudinal axis is not necessarily co-axial or even parallel with a longitudinal axis **AA** of the analog when the analog is in the installed position therein.

[0065] It is readily apparent that analog insertion opening **607** is spaced from the parts of the physical model corresponding to the implant site **150**, in particular that analog insertion opening **607** is spaced from coronal opening **650**. It is also readily apparent that analog insertion opening **607** is different from coronal opening **650**.

[0066] In at least some examples the analog insertion opening **607** is spaced from the outer model surface **661**. In at least some examples the analog insertion opening **607** is at a location

other than the outer model surface **661**. In at least some examples the analog insertion opening **607** excludes a location in parts of the physical model corresponding to the implant site **150**.

[0067] In particular, the passageway **608** is configured, for example via the shape of its internal walls **666**, for enabling the analog **230** to be inserted into the physical model **600** in the respective general coronal direction **K** to the respective installed position, and defines an analog chamber **665** at the coronal end of passageway **608** for accommodating the analog **240** at the installed position, at spatial disposition **P'** with respect to the physical model **600**. The precise form of the second model part **640**, and in particular of the analog installation structure **690**, thus depends on the particular external configuration of the analog **230**, i.e., the external form **270** thereof. Thus, in this example, passageway **608** comprises: a first passageway portion **656** having an internal surface that is complementary to the outer surface **263** and including a corresponding passageway flat portion (not shown) that is complementary to analog flat portion **261**; a shoulder **657** that is complementary to face **265**; and a second passageway portion **658** having an internal surface that is complementary to the outer surface of enlarged apical portion **264** and extends in a general apical direction **A** to opening **607**.

[0068] In the installed position, analog **230** forms a tight fit with passageway **608**, and in particular with analog chamber **665**, and this fixes the position of the analog **230** in the physical model **600** in four degrees of freedom, preventing translation along, or rotation about, two orthogonal axes that are also orthogonal to the respective general coronal direction **K**, and thus also to the longitudinal axis **BB**, and in this example also with respect to the longitudinal axis **AA**.

[0069] The asymmetry of coronal portion **262**, in particular the analog flat portion **261**, ensures that the analog **230** can be inserted into passageway **608**, and in particular into analog chamber **665**, in only one angular disposition about the respective general coronal direction **K**, and thus also about longitudinal axis **BB** with respect to the passageway **608**. In this installed position the analog flat portion **261** is in contact with the corresponding passageway flat portion, and furthermore such contact further prevents rotation between the analog **230** and the physical model **600** about the respective general coronal direction **K**, and thus also about longitudinal axis **BB**. Furthermore, abutment between the coronal face **265** and the shoulder **657** provides a mechanical stop in the general coronal direction **K**, and thus ensures that the analog **230** can be inserted into passageway **608** to a particular depth along the respective general coronal direction **K**, and such contact prevents further coronal translation by the analog **230** into the physical model **600** along the respective general coronal direction **K**, and thus also along longitudinal axis **BB**. The analog **230** can be prevented from translating in the general apical direction out of the installed position in any number of ways, for example by providing a suitable adhesive or a friction fit between the analog **230** and passageway **608**, or filling the apical end **602** of the passageway with a suitable filler or plug, and so on.

[0070] In at least this example, the insertion path into passageway **608** passageway **608** is

defined by (and aligned with) the desired spatial orientation of the axis **AA** of the analog **230** at the installed position with respect to the physical model **600**, which in turn matches the spatial orientation of the axis **AA** of the dental implant **240** with respect to the dental structure **100**. It is also readily evident that the longitudinal position of the shoulder **657** with respect to the outer model surface **661** and with respect to longitudinal axis **AA** is such as to ensure that point **Q'** of the analog **230** (in the installed position) is at a position with respect to the outer model surface **661** that replicates point **Q** of the dental implant **240** with respect to the dental structure **100**.

[0071] With the dental analog **230** thus fixed in six degrees of freedom with respect to the physical model **600** in spatial disposition **P'** replicating the geometrical relationship between the dental implant **240** and the dental structure **100**, a prosthesis system (e.g., prosthesis system **991**, see Fig. 1(a)) can be designed and/or tested using the dental analog **230** while coupled to the physical model **600**, and enabling the prosthesis system to be subsequently mounted to the patient via the dental implant **240**.

[0072] In this example, the implant site **150**, in particular the perimeter **655** of coronal opening **650** has a shape and dimension complementary to the shape and outer diameter of the coronal-facing face **269**. Alternatively, the coronal opening **650** may laterally overlap the periphery of the coronal-facing face **269** but it is not desired for this overlap to act as a mechanical stop and thus limit or define the relative position between the analog **230** and the passageway **608**: for example, and as will be described in greater detail below, the physical model may be manufactured as a composite model in which part of the physical model in the vicinity of and overlapping the periphery of the coronal-facing face **269** may be made of a soft material, unsuitable or undesirable for acting as a mechanical stop in the general coronal direction for the analog **230**.

[0073] In the example illustrated in Fig. 5 and Fig. 6(a), the respective general coronal direction **K** is shown as being oriented close to the orientation of the respective coronal direction **CO** of the removed tooth. Nevertheless, the example of dental analog **230** illustrated in these figures can also be used in situations wherein the dental implant **240** is implanted in the dental structure **100** at a spatial disposition **P** having a relatively large angular displacement with respect to the respective coronal direction. Fig. 6(e) illustrates an example of such a situation in which the analog **230** is at a corresponding angular disposition **P'**, where the respective general coronal direction **K** and the passageway axis **BB** are angularly displaced from the respective coronal direction **CO** of the removed tooth by a correspondingly (though not necessarily identical) relatively large acute angle, marked λ in this figure. In cases such as illustrated in Fig., 6(e), the analog and corresponding implant can be configured for use with an angulated abutment and prosthesis (marked **990'**) to match the orientation of the prosthesis to the adjacent teeth and to provide the correct occlusion with the teeth of the opposite jaw. On the other hand, and as illustrated in Fig. 6(f), an alternative design for the analog can be provided with respect to the case of Fig. 6(e), in which, the spatial disposition **P'** of the analog **230** represents the spatial disposition of the implant with respect to the dental structure having a relatively large angular displacement with respect to the respective coronal direction **CO**. In the example of Fig. 6(f), the respective dental analog is configured to be

inserted into the physical model along a respective general coronal direction **K** that is parallel or close to parallel with respect to the coronal direction, with the analog having a reference longitudinal axis that is parallel to the passageway longitudinal axis **BB**, and parallel with the general coronal direction **K**, but angularly displaced with respect to the corresponding axis **AA** of the analog.

[0074] It is therefore apparent that for any given configuration of a dental implant, implanted at a particular spatial disposition **P**, a variety of different analogs can be provided, all such analogs having the same prosthesis-engaging configuration corresponding to the prosthesis engaging interface of the implant, but having different external forms **270** which are, in turn, configured for different configuration of the respective installation structure **690** of the respective physical model **600**. Thus, in alternative variations of these examples, the analog **230** and the analog installation structure **690** of the physical model **600** may have different configurations to ensure that dental analog **230** is fixed in six degrees of freedom with respect to the physical model **600** in spatial disposition **P'**, while enabling insertion of the analog **230** into the physical model **600** in the general coronal direction **K** for example..

[0075] For example, referring to Fig. 6(b), the enlarged apical portion **265** of the example of Fig. 6(a) is omitted from the analog **230**, and the analog flat portion **261** does not extend to the apical end of the coronal portion **262**, but rather to a location coronally displaced therefrom, thus forming a coronal face **268** displaced from the apical end **267** of the coronal portion **262**. Correspondingly, passageway **608** is formed in physical model **600** with a shoulder complementary to coronal face **268** (and can thus omit shoulder **657**), and thus defines the longitudinal position of the implant **230** in the passageway **608** and thus with respect to the physical model **600** in a manner similar to that provided by the coronal face **265** and the shoulder **657** of the example illustrated in Figs. 5 and 6(a), *mutatis mutandis*.

[0076] In another example, referring to Fig. 6(c), the analog flat portion **261** of the example of Fig. 6(a) can be omitted from the analog **230**, and the enlarged apical portion **264** comprises instead a coronal face having two portions **265A**, **265B** both orthogonal to respective general coronal direction **K**, and thus also to longitudinal axis **AA**, but axially displaced from one another via joining walls **265C**. Correspondingly, passageway **608** is formed with a stepped shoulder configuration (rather than shoulder **657**), comprising two shoulders complementary to portions **265A**, **265B**, and which thus defines the longitudinal position of the implant **230** in the passageway **608** and the angular orientation of the implant with respect to the physical model **600** about respective general coronal direction **K**, and thus also about longitudinal axis **AA**.

[0077] In another example, referring to Fig. 6(d), the analog flat portion **261** of the example of Fig. 6(a) can be omitted from the analog **230**, and the enlarged apical portion **264** comprises instead a coronal face **265D** that is not orthogonal to respective general coronal direction **K**, and thus also not orthogonal to longitudinal axis **AA**. Rather coronal face **265D** is defined on a plane inclined to respective general coronal direction **K**, and thus also to longitudinal axis **AA**. Correspondingly, passageway **608** is formed with an inclined shoulder complementary to inclined coronal face **265D** (rather than shoulder **657**), which thus defines the longitudinal

position of the implant **230** in the passageway **608** and the angular orientation of the implant with respect to the physical model **600** about respective general coronal direction **K**, and thus also about longitudinal axis **AA**.

[0078] As is also evident from the examples in Figs. 6(a), 6(c) and 6(d), the relative longitudinal lengths between the coronal portion **262** and the apical portion **264** can be varied as desired, and the passageway **608** is correspondingly formed to receive the implant in the general coronal direction **K**.

[0079] In another variation of the example of Fig. 6(a) the coronal portion **262** can be axisymmetrical about longitudinal axis **AA**, and instead the apical portion **264** is asymmetrical (the passageway **608** being complementarily shaped) to fix the angular disposition between the analog **230** and the physical model **600** about longitudinal axis **AA**.

[0080] In yet another variation of the example of Fig. 6(a), at least the coronal portion **262** can be externally threaded, and the passageway **608** can be complementarily internally threaded, to fix the angular disposition between the analog **230** and the physical model **600** about longitudinal axis **AA**.

[0081] In yet another variation of the example of Fig. 6(a), and referring to Fig. 6(g), the passageway **608** has a longitudinal axis **BB** that is angularly displaced with respect to the corresponding axis **AA** of the analog, which has an insertion reference axis parallel to longitudinal axis **BB**. Thus, the passageway in the physical model is complementarily shaped to the analog, and the respective insertion direction **K** is parallel to axis **BB**. In this example, while axis **AA** may be parallel or have an origination close to that of the coronal direction **CO**, the respective general coronal direction **K** can be significantly angularly displaced with respect to the coronal direction **CO**.

[0082] In yet another variation of the example of Fig. 6(a), and referring to Fig. 6(h), the passageway **608** has a longitudinal axis **BB** that is orthogonal or near orthogonal to the true occlusal direction **OC**, and has an analog insertion opening **607A** on a side of the physical model **600** rather than on the base. The passageway in the physical model is complementarily shaped to the analog, and the respective insertion direction **K** is parallel to axis **BB**. In this example, the analog insertion opening **607A** can be formed on parts of the physical model **600** representing some of the dental surfaces **115**, but not any of the dental surfaces in the vicinity of and defining opening **650**.

[0083] A variation of the example of Fig. 6(h) is illustrated in Fig. 6(i), which shows a cross-section of the respective physical model **600** along a coronal-buccal plane, and in which occlusal model surfaces **117'** and side model surfaces **116'** respectively represent occlusal facing dental surfaces and adjacent dental side surfaces of the dental surfaces **115** of the dental structure **100**. In this example, the respective analog insertion opening **607B** is wholly located on a side model surfaces **116'** of the physical model **600**, representing the gingival surfaces, for example, of the dental structure **100**.

[0084] In yet other examples, the insertion path may include a change of direction. For example, referring to Fig. 5, another analog insertion opening (not shown) may be provided on the side of the physical model to enable the analog to be laterally inserted into passageway 608, for example in a buccal or lingual direction (i.e., into or out of the paper, for example), but at a position still axially displaced along axis **BB** from the implanted position, and then the analog is pushed along the axis **BB** to the implanted position.

[0085] In yet another example, and referring to Fig. 7, the enlarged apical portion 264 of the example of Fig. 6(a) can be omitted from the analog 230, and, instead, coronal-facing face 269 abuts a shoulder 657B formed in passageway 608 complementary thereto, the shoulder 657B being coplanar with the installed position of the coronal-facing face 269. This arrangement limits the coronal translation of the implant 230 along passageway 608 to the installed position with respect to the physical model 600 in a manner similar to that provided by the coronal face 265 and the shoulder 657 of the example illustrated in Figs. 5 and 6(a), *mutatis mutandis*. In this example, while the analog itself may be of uniform cross-section, it is evident that the exposed part of the coronal-facing face 269 has a maximum width dimension that is smaller than a maximum width dimension of another portion of the analog.

[0086] In yet another example, and referring to Figs. 8 and 8(a), the enlarged apical portion 264 of the example of Fig. 6(a) can be omitted from the analog 230, and coronal portion 262 comprises visual markings 266 which are configured to facilitate longitudinal alignment of the analog 230 with the installation structure 690. For example, visual markings 266 can comprise a mark that can be manually aligned with shoulder 657 or any other suitable datum formed or marked in passageway 608. Alternatively, visual markings 266 can comprise a graduated scale provided along the side of the analog 230 that allows the depth of penetration of the analog 230 into the physical model 600 to be visually gauged. In use, the implant 230 can be inserted into passageway 608 until this alignment occurs, and the implant 230 is then cemented in place in its installed position with respect to the physical model 600.

[0087] In yet another example, and referring to Fig. 8(b), the analog 230 of the example of Fig. 6(a) can include the enlarged apical portion 264, but the analog is axisymmetric enabling free rotation within the passageway 608 about respective general coronal direction **K**, and thus also about axis **AA**. Apical portion 264 comprises visual markings 266' which are configured to facilitate rotational alignment of the analog 230 with respect to the installation structure 690 about respective general coronal direction **K**, and thus also about axis **AA**. For example, visual markings 266' can comprise a mark that can be manually aligned with a corresponding mark or other datum provided in the passageway 608, while the shoulder 657 acts as a mechanical stop. In use, the implant 230 can be inserted into passageway 608 until the enlarged apical end 264 is in abutment with shoulder 657, and then rotated therein about axis **AA** until this rotational alignment occurs, and the implant 230 can then be cemented in place in its installed position with respect to the physical model 600. Alternatively, the enlarged apical portion 264 of the example of Fig. 6(a) can be omitted from the analog 230, the visual markings 266' being provided, instead, on an apical end of the coronal portion 262, and in addition, visual markings

266 are also provided, in a similar manner to that of the example of Figs. 8 and 8(a), *mutatis mutandis*, to also facilitate longitudinal alignment of the analog **230** with the installation structure **690**. In use, the implant **230** can be inserted into passageway **608** and rotated therein until this longitudinal and rotational alignment occurs, and the implant **230** is then cemented in place in its installed position with respect to the physical model **600**.

[0088] It is to be noted that in the above examples and in other examples of the analog **230** and of the corresponding physical model **600**, the asymmetry of the coronal portion **262** may be achieved in a different manner to that illustrated with respect thereto to define the angular disposition **P'** of the analog **230** with respect to the passageway **608**, and thus with respect to the physical model **600**. For example, additional flat portions, similar to flat portion **261** but angularly displaced therefrom about longitudinal axis **AA** may be provided on the coronal portion **262**. Alternatively, one or both of the coronal portion **262** and apical portion **264** can be formed having a non-axisymmetric cross-section, for example as a respective prismatic member having a polygonal cross-section (corresponding to a regular or irregular polygon), or having an oval cross-section, for example. In each case the passageway **608** is complementarily shaped to allow insertion of the analog in the general coronal direction to its installed position. Additionally or alternatively, a keyway may be formed in each one of the analog **230** and the passageway **608** of the physical model **600**, and a corresponding key inserted when both keyways are aligned to fix the relative disposition between the analog **230** and physical model **600** in at least five degrees of freedom.

[0089] It is also to be noted that in the above examples and in other examples of the analog **230** and of the corresponding physical model **600**, one or both of the coronal portion **262** and apical portion **264** are each formed having a generally uniform cross-sectional form along the longitudinal axis **AA**. Alternatively, and as illustrated in Fig. 9, in at least one variation of these examples or in at least another example, the coronal portion **262** may have a cross-section **262A** that tapers in the general coronal direction, and the passageway **608** is complementarily tapered, to thereby define the longitudinal position of the implant **230** in the passageway **608** and thus with respect to the physical model **600**; it is readily evident that additionally or alternatively, the apical portion **264** can be omitted, or the apical portion **264** can be formed with coronally tapering cross-section.

[0090] It is also to be noted that in at least some of the above examples and in other examples of the analog **230** and of the corresponding physical model **600**, at least the exposed part of the respective coronal-facing face **269** (when the analog is in the respective installed position in the physical model **600**) has a maximum width dimension that is smaller than a maximum width dimension of another portion of the analog. This ensures that these examples of the analog can be inserted into the physical model **600** in a direction that does not penetrate into the external surface **661**, for example along a particular general coronal direction **K**, and at the same time limits penetration of the analog into the model to ensure that it is at the installed position at the end of penetration. The other portion of the analog having a greater maximum width than at least the exposed part of the respective coronal-facing face **269** can be at any desired location along the analog, for example at the opposed end thereof with respect to the

coronal-facing face **269**, or inbetween. It is readily evident that the maximum width differential can be achieved by providing this part with a larger cross-sectional shape or with a protrusion, as compared with the at least the exposed part of the respective coronal-facing face **269**.

[0091] Referring to Fig. 3, an example of a system **200** for manufacturing a physical model, such as for example physical model **600**, comprises a first subsystem **260** for generating a virtual (three-dimensional) model of the patient's dental structure **100** that includes the dental implant **240**, operatively connected to a second subsystem **280** for manufacturing physical model **600** based on and corresponding to the virtual model, the physical model **600** being configured for enabling a physical analog **230** (corresponding to the dental implant **240**) to be coupled, as already described in greater detail above.

[0092] The first subsystem **260** comprises a microprocessor or any other suitable computer system suitably programmed for operating on a virtual model of the aforesaid dental structure **100** to provide suitable manufacturing data to second subsystem **28**, as will be disclosed in greater detail below with respect to the method **400**. In this example, the computer system **260** comprises an input interface **210** such as a keyboard, mouse, tablet, and so on, an output device such as display **220**, a processing unit **230**, and a memory **235**. Herein "display" refers to any device or system for delivering a presentation, which can include one or more of any information, data, images, sounds, etc, and thus the delivery can be in visual and/or audio form.

[0093] In this example, the subsystem **260** also comprises a scanner **250** that is configured for providing 3D surface data of surfaces, in particular of the dental structure **100** (or alternatively of an already existing physical model of the dental structure **100**), including the hard dental surfaces **110** and soft dental surfaces **120** thereof, and also including the dental implant site **150**. The scanner **250** is also configured for providing data relating to the spatial disposition **P** of the implant **240** with respect to the dental structure **100**.

[0094] The scanner **250** is operatively connected to the computer system **260** and interacts therewith, and the subsystem **260** and/or the scanner **250** are suitably programmed for reconstructing such surfaces from the surface data provided, to provide a virtual model **500** of the dental structure **100**. Suitable examples of such scanners are well known, and can include, for example, an intra-oral scanner marketed under the name of iTero (by Cadent Ltd., USA) which uses a hand held probe for determining three dimensional surface data based on confocal focusing of an array of light beams, and may optionally provide color data of the intraoral cavity in addition to the 3D surface data.

[0095] A scanning abutment **246** can be provided, which in use can be mounted to the dental implant **240** via the prosthesis interface part **248** and the prosthesis engaging part **241**, and subsequently scanned directly or indirectly by the scanner **250**. The scanning abutment **246** is characterized in having suitable 3D attributes, for example the scanning abutment **246** is shaped, and/or comprises suitable markers or other positional indicators on the visually exposed part thereof when mounted to the implanted implant **240**, that provide information to

enable the spatial disposition **P** of the dental implant **240** with respect to the dental structure **100** to be determined. In some cases, an impression abutment or a healing abutment can be used as a scanning abutment.

[0096] In alternative variations of this example of system **200**, the scanner **250** can be omitted and the virtual model **500** can be provided to the subsystem **260** in any other suitable manner, for example via external virtual model source **290**, which includes virtual model **500** having been generated in any suitable manner, including *inter alia* using suitable other scanning techniques, for example based on optical methods, direct contact methods, X-ray scanning, CT scanning, MRI scanning, ultrasound-based scanning, or any other type of scanning can be used, applied directly to the patient's dentition or to an impression or other negative model of the patient's dentition, or to an existing physical model thereof, as appropriate.

[0097] In any case, the subsystem **260** manipulates and operates on the virtual model **500** of the aforesaid dental structure **100** as disclosed below in the context of method **400** to generate manufacturing data for manufacturing the respective physical model **600**, and this manufacturing data is provided to second subsystem **280**.

[0098] The second subsystem **280** comprises a computer controlled manufacturing system configured for manufacturing the physical model **600** from the manufacturing data, which for example may be referenced to a machine coordinate system **C**. While in this example, the manufacturing process itself is a material removing process, such as CNC milling for example, in alternative variations of this example part or all of the manufacturing process can include a material additive process, for example a rapid prototyping process, for example using a 3D system stereo lithography machine, or can include any other suitable computer-controlled manufacturing process.

[0099] Referring to Fig. **4**, an example of a method **400** for manufacturing a physical model, such as for example physical model **600**, and which can be carried out using system **200**, for example, broadly includes the following steps **420** and **450**:

Step **420** - receiving a virtual model of the physical dental structure and a virtual analog installation structure (also referred to herein interchangeably as a virtual analog socket structure) in association with said virtual model, said virtual analog installation structure being based on the dental analog;

Step **450** using said virtual model, manufacturing a physical model corresponding to said virtual model, the physical model being provided with an analog installation structure based on said virtual analog installation structure and thereby configured for enabling the dental analog to be inserted into said physical model through an analog insertion opening, wherein said analog insertion opening is spaced from a location in the physical model corresponding to the implant site in the physical dental structure.

[0100] In at least one variation of this example, and referring to Fig. 4(b), steps **420** and **450** can be as follows:

Step **420** - providing a virtual model of the physical dental structure including a virtual implant spatial disposition with respect to said virtual model corresponding to a physical implant spatial disposition of the dental implant with respect to the physical dental structure;

Step **450** - using said virtual model, manufacturing a physical model corresponding to said virtual model, the physical model being provided with an analog installation structure configured for enabling a physical analog, corresponding to the dental implant, to be inserted in a general coronal direction with respect to said physical model to an installed position therein having an analog spatial disposition with respect to said physical model corresponding to said physical implant spatial disposition, wherein said analog installation structure is previously defined in said virtual model.

[0101] In any case, the method **400** assumes that implant **240** has already been implanted in the dental structure **100** of the patient, and it is to be noted that implantation of implants in the intra oral cavity of patients is well known in the art. The method **400** also assumes that a particular type of analog **230** according to the first aspect of the presently disclosed subject matter, and corresponding to the dental implant **240**, has been chosen, having a known or determinable external form **270**.

[0102] Referring to each step in turn, step **420** comprises initially receiving, for example acquiring, an accurate three dimensional virtual model **500** of the dental structure **100**, which as already stated includes the implant **240** and thus forms the focus of the particular implant procedure for a particular patient. Herein the term "virtual model" is synonymous with, and can be referred to interchangeably as, "three-dimensional model", "3D model", "virtual model", "3D representation", "3D digitized data", and the like. Referring also to Fig. 3, the virtual model **500** can be provided by scanning the intra-oral cavity dental structure directly in-vivo using the scanner **250** of system **200**. Alternatively the virtual model **500** can be provided in any other any other suitable manner, for example via external virtual model source **290**, i.e., including *inter alia* using suitable other scanning techniques, for example based on optical methods, direct contact methods, X-ray scanning, CT scanning, MRI scanning, ultrasound-based scanning, or any other type of scanning can be used, applied directly to the patient's dentition or indirectly thereto, for example applied instead to an existing physical model thereof, as appropriate.

[0103] The virtual model **500** includes, in addition to a virtual representation of dental surfaces **150** of the dental structure **100** (i.e., 3D information of the soft dental surfaces **120** and hard dental surfaces **110** at least in the vicinity of the implant zone **150**), sufficient spatial (3D) data regarding the implanted implant **240** so that its spatial disposition **P** with respect to the dental structure **100**, can be also be modeled with respect to the virtual model **500**. The spatial disposition **P** of the implant **240** can be determined using at least two different scanning

methods, to provide virtual implant spatial disposition data.

[0104] In a first scanning method, a first scanning procedure is applied directly to the dental structure **100** (the dental implant **240** being exposed to the intra-oral cavity) to enable creation of the virtual model **500** of the dental structure **100**, to thereby provide an accurate virtual representation of dental surfaces **150** of the dental structure **100**. Then, scanning abutment **246** is mounted to the dental implant **240** and a second scanning procedure is applied to the dental structure **100** with the scanning abutment **246** in situ, generating an auxiliary virtual model which includes a virtual portion thereof corresponding to the scanning abutment **246**. Since the scanning abutment **246** has known 3D attributes, and the geometric relationship between the scanning abutment and the dental implant **240** is also fixed and known, analysis of this portion of the auxiliary virtual model provides information about the spatial disposition **P** of the dental implant **240** with respect to the dental structure **100**, and thus enables this spatial disposition **P** to be modeled with respect to the first auxiliary virtual model to provide corresponding virtual spatial disposition data **VP**. Of course, the second scanning procedure can instead precede the first scanning procedure, in which case the scanning abutment **246** is removed from the dental implant **240** prior to proceeding with the first scanning procedure. In any case, a registration step can then be performed between the auxiliary virtual model and the virtual model **500**, for example by matching corresponding virtual dental surfaces thereof, in particular by matching corresponding external hard virtual dental surfaces thereof, to provide the relative virtual disposition data **VP** of the implant with respect to the virtual model **500** from the virtual disposition already determined for the auxiliary virtual model.

[0105] Thus, the first scanning procedure provides the virtual representation of dental surfaces **150** of the dental structure **100** with unobscured surface details of the soft tissues in the vicinity of and around the periphery of the prosthesis engaging part **248**, i.e., at interface **155**, while the second scanning procedure provides the necessary information to determine the spatial disposition **P** of the implanted implant **240** with respect to the dental structure **100**. This two-step scanning procedure can be of particular benefit when the details of the implant **240** are at least partially obscured by the soft tissues in the vicinity of the prosthesis engaging part **248**, and/or, where the scanning abutment **246** mechanically interferes with (for example presses against and deforms) the soft tissues in the vicinity of the prosthesis engaging part **248**.

[0106] In a second scanning method, only a single scanning procedure is applied directly to the dental structure **100** (i.e., without any scanning abutment **246** being mounted thereto). In this scanning procedure at least a portion of the prosthesis engaging part **248** is exposed and captured during the scanning procedure, this portion being uniquely identifiable with respect to the dental implant **240**. Analysis of a virtual portion of the virtual model **500** corresponding to the exposed prosthesis engaging part **248** enables this virtual portion to be matched to the geometry of the dental implant **240**, which thus provides information about the spatial disposition **P** of the dental implant **240** with respect to the dental structure **100**. In turn, this enables this spatial disposition **P** to be modeled with respect to the virtual model **500** to provide a corresponding virtual spatial disposition data **VP** of the virtual equivalent of the dental implant **240** with respect to the virtual model **500**.

[0107] The virtual spatial disposition data **VP** thus includes dental implant data representing the location and orientation of the dental implant **240** with respect to the dental surfaces **115**.

[0108] Alternatively, an indirect scanning technique can be used if a first prior physical model of the dental structure **100** (i.e., with the dental implant **240** already implanted in the dental structure **100**) already exists, the aforementioned first scanning procedure of the first scanning method, or the second scanning method, may be applied to this first prior physical model rather than to the dental structure **100** i.e., instead of scanning the actual intraoral cavity of the patient. Furthermore, if there also exists a second prior physical model of the dental structure **100**, obtained when the scanning abutment **246** was mounted thereto, the aforementioned first scanning procedure of the first scanning method may be applied to this second prior physical model rather than to the intraoral cavity of the patient. The first prior physical model can be provided, for example, in a conventional manner via a first physical impression of the dental structure **100**, including the exposed implant **240** and subsequently casting the first physical impression with paste. The second prior physical model can be provided in a similar manner, for example via a second physical impression of the dental structure **100** taken with the scanning abutment **246** mounted to the implant **240** and subsequently casting the second impression with paste.

[0109] Thus, with respect to the virtual model **500**, virtual spatial disposition data **VP** is determined, representative of the physical spatial disposition **P** of the dental implant **240** with respect to the dental structure **100**.

[0110] For example, virtual spatial disposition data **VP** can be defined with respect to virtual model **500** in a similar manner to spatial disposition **P** or spatial disposition **P'**, *mutatis mutandis*, i.e., can include the virtual spatial orientation of a virtual longitudinal axis **VA**, and the spatial position of a point **VQ** associated with a virtual analog **730** (corresponding to the physical analog **230**), point **VQ** being at a fixed spatial relationship with respect to the axis **VA**.

[0111] Referring to Fig. 10, virtual model **500** comprises a first external surface **561** virtually representative of dental surfaces **115** of said dental structure **100**, including first virtual portions **509** corresponding to the hard dental surfaces **110**, second virtual portions **508** corresponding to the soft dental surfaces **120**, and a third virtual portion **502** corresponding to the interface **155** between exposed part of prosthesis engaging part **248** and soft dental surfaces **120**.

[0112] Additionally, the virtual model **500** is operated on and modified to define a fully enclosed virtual volume corresponding to the enclosed volume of the respective physical model **600** that is to be manufactured. For example, and also referring again to Fig. 5, the virtual model **500** can be modified to include a virtual model base **506** corresponding to the desired physical model base **609**, and comprising a respective external base surface **507** corresponding to the desired physical base surface **603**. The virtual model base **506** can be generated in any number of ways. For example, a rectangular parallelepiped, or other prismatic shape or any other suitable shape, can be defined having a length and breadth greater, for example about

10% greater, than the overall length and breadth, respectively, of the first external surface **561**, and a height for example about the same as the overall height of the first external surface **561**. The base surface **507** thus generated is displaced in an apical direction **A** away from the first external surface **561**, and the first external surface **561** is smoothly joined to the external base surface **507** in a virtual manner to create the enclosed virtual volume. The external base surface **507** is thus different from first external surface **561** and does not correspond to physiological surfaces, including dental surfaces, of said dental structure **100**.

[0113] At least a part of the external base surface **507** is displaced from the aforesaid first external surface **561** in an apical direction **A** with respect thereto and away from the third virtual portion **502**, and defines a virtual apical portion **501** corresponding to the desired physical apical portion **606** of the physical model **600**.

[0114] Referring to Fig. 4(a), step **450** comprises a number of sub-steps, as follows:

Step **470** - defining in said virtual model **500** a virtual analog socket structure (i.e., the virtual analog installation structure **590**), for virtually accommodating therein a virtual analog (corresponding to the physical analog) in a virtual installed position (corresponding to the desired installed position of the physical analog in the physical model). In other words, the virtual analog installation structure **590** corresponds to the desired physical installation structure **690**.

Step **480** - generating machine instructions for manufacturing the physical model **600** based on said virtual model **500** and the virtual analog installation structure **590**.

Step **490** - using the machine instructions, manufacturing the physical model **600**.

[0115] Herein, "virtual analog" is used interchangeably with "virtual analog structure".

[0116] Referring to step **470**, this can include three sub-steps: step **470A**, step **470B**, and step **470C**. In step **470A**, and referring again to Fig. 10, the geometry of the appropriate virtual analog installation structure **590** corresponding to the desired physical installation structure **690**, is provided, having corresponding 3D characteristics such as to ensure that virtual analog **730** can be virtually installed in the virtual analog installation structure **590** to a virtual installed position with respect thereto corresponding to the installed position of the dental analog **230** with respect to the corresponding physical installation structure **690**, i.e. at virtual spatial disposition data **VP**, to define their relative positions in six degrees of freedom. The virtual analog installation structure **590** includes virtual passageway **708** having virtual internal walls **766** configured for allowing virtual insertion of the respective virtual implant **730** along the respective insertion direction to a virtual installed position, corresponding to the desired physical passageway **608** and internal walls **666**, *mutatis mutandis*. Thus, and referring to the example of dental analog **230** and physical model **600** illustrated in Fig. 5 and Fig. 6(a), the virtual internal walls **766** define a virtual analog chamber **765**, and passageway **708** comprises

a first passageway portion **756**, a shoulder **757**, and a second passageway portion **758**, corresponding to and having virtual 3D characteristics corresponding to the physical 3D characteristics required for the first passageway portion **656**, shoulder **657**, and second passageway portion **658**. It is to be noted that at this point the second passageway portion **758** can have a different axial length than that of the eventual second passageway portion **658**. These virtual components of passageway **708** are thus determined from the virtual external form **770** of the respective analog **730** in a manner similar to that described above for the passageway **608** of physical model **600** of Fig. 5 in the context of the external form **270** of the analog **230**, *mutatis mutandis*.

[0117] Thus, the virtual analog installation structure **590** can be modeled for any type of implant **230**, *mutatis mutandis*, having any external form **270**, for example as illustrated in the figures, comprising a virtual passageway **708** having virtual internal walls **766** configured for allowing coronal insertion of the respective virtual implant **730** to a virtual installed position based on the external form **270** of the respective analog **230**.

[0118] Thus, for example, it is possible for the first subsystem **260** to include in memory **235** (or in another memory operatively connected to the first subsystem **260**) a library of virtual analog installation structures **590**, each corresponding to one of a plurality of different types of dental analogs **230**, in particular of the respective external forms **270** thereof, and the appropriate virtual analog installation structure **590** can be retrieved and operated on in steps **470B** and step **470C** below by identifying the corresponding virtual analog **770**, which in turn corresponds to the actual dental analog **230** that has been chosen corresponding to the dental implant **240**.

[0119] Alternatively, the appropriate virtual analog installation structure **590** can be imported to the first subsystem **260** from another external source.

[0120] In step **470B**, the virtual analog installation structure **590** provided in step **470A** is virtually aligned with respect to the virtual model **500** at virtual spatial disposition data **VP** to ensure that a virtual analog **730** can be virtually inserted to a virtual installed position therein corresponding to the installed position of the dental analog **230** in the physical model **600**, the spatial disposition **P'**, and which in turn corresponds to the spatial disposition **P**. This virtual alignment is relatively straightforward since the virtual spatial disposition of the virtual analog **730** with respect to the virtual analog installation structure **590** is fixed in six degrees of freedom at the virtual installed position, and since in the virtual installed position the virtual analog **730** will be at the already determined virtual disposition **VP** with respect to the first model **500**. For example, the virtual analog **730** can be registered with respect to the virtual model **500** by aligning the virtual analog **730** at virtual spatial disposition data **VP**, and then registering the virtual analog installation structure **590** with the virtual analog **730**, after which the virtual analog **730** can be removed.

[0121] In any case, the result is that the aligned virtual analog installation structure **590** is referenced to the same spatial/coordinate system as the virtual model **500**.

[0122] Optionally, the aligned virtual analog installation structure **590** can be further modified, as necessary to ensure compatibility with the virtual model base **506**, in particular to define virtual analog insertion opening **707** formed in virtual apical portion **706**, corresponding to analog insertion opening **607** formed in apical portion **606**. Thus, if necessary, the virtual passageway **758** can be extended in a general apical direction aligned with the virtual longitudinal axis **VA**, or shortened, to ensure such compatibility, and the virtual analog insertion opening **707** can be virtually defined as the intersection of virtual passageway **758** with virtual apical portion **706**.

[0123] It is readily apparent that virtual analog insertion opening **707** is spaced from the parts of the virtual model corresponding to the implant site **150**, in particular that virtual analog insertion opening **707** is spaced from virtual coronal opening **503**. It is also readily apparent that virtual analog insertion opening **707** is different from virtual coronal opening **503**.

[0124] In at least some examples the virtual analog insertion opening **707** is spaced from the outer model surface **661**. In at least some examples the analog insertion opening **607** is at a location other than the first external surface **561**. In at least some examples the virtual analog insertion opening **707** excludes a location in parts of the virtual model corresponding to the implant site **150**.

[0125] Finally, a part of the virtual model **500** circumscribed by third virtual portion **502** is removed to provide virtual coronal opening **503**, and the coronal end of the virtual analog installation structure **590** is virtually joined to the third virtual portion **502**. The virtual analog installation structure **590** is thus open in a virtual sense at its coronal end via coronal opening **503**, and at its apical end via virtual analog insertion opening **707**.

[0126] In step **470C** the virtual analog installation structure **590** can be virtually combined with the virtual model **500** to generate a modified virtual model **500'**.

[0127] Referring to Fig. 4(c), it is thus readily apparent that the virtual model **500** can be created using a computer system, and implementing the following broad steps:

Step 472 - receiving a virtual representation of dental surfaces of the physical dental structure with dental implant data representing a location and orientation of the dental implant with respect to the dental surfaces;

Step 474 - receiving a virtual analog structure, the virtual analog structure being based on said dental implant; and

Step 476 - creating the virtual model based on:

- said virtual representation of dental surfaces; and
- a virtual analog socket structure based on said virtual analog structure and said dental implant data, and having an virtual analog insertion opening that is spaced from parts of the virtual model corresponding to dental surfaces and the implant site.

[0128] It is also readily apparent that the virtual analog socket structure, i.e., the virtual analog installation structure **590**, is configured for virtually receiving therein the analog virtual model **730** via the virtual analog insertion opening **707** and along an insertion path, wherein the insertion path is along an insertion direction including at least one of:

- a general coronal direction **K**;
- a non-apical direction;
- a direction passing through the virtual representation of dental surfaces, i.e., first external surface **561**, from a first location **F1** with respect to the virtual model **500** corresponding to an inside **D1** of the dental structure **100** to a second location **F2** with respect to the virtual model **500** corresponding to an outside **D2** of the dental structure (see Fig. 5 and Fig. 10).

[0129] Referring again to Fig. 4(a), in step **480** the modified virtual model **500'** is suitably operated on to provide suitable machine instructions **M** to enable in step **490** computer controlled manufacture of the physical model **600** including the physical installation structure **690** corresponding to the virtual analog installation structure **590**, for example using subsystem **280** (Fig. 3).

[0130] Alternatively, and referring again to Fig. 3, manufacturing step **490** has two stages. In this case, step **470C** can optionally be omitted, and in step **480** the virtual model **500** is suitably operated on to provide a first set of machine instructions **M1** for computer controlled manufacture of part of the physical model **600** excluding the physical installation structure **690**. The virtual analog installation structure **590** is also suitably operated on to provide a second set of machine instructions **M2** to finish the physical model **600** by the computer controlled manufacture of the physical installation structure **690** therein.

[0131] The exact nature of the machine instructions will depend, *inter alia*, on the type of computer controlled manufacture being used in step **490**, for example CNC machining or rapid prototyping, and can be carried out using the second subsystem **280**, for example.

[0132] A feature of CNC controlled manufacturing process of the model **600** according to this and at least some other examples of the presently disclosed subject matter is that the machine instructions for producing both, the external surface **661**, base **609**, chamber **665**, passageway **608** and opening **607** of the model **600**, are derived from the same virtual model **500** and are thus referenced to the same machine coordinate system **C**. This enables the same CNC controlled manufacturing system to be used for machining the external surface **661** and base **609** of the physical model **600**, either in parallel or in series, with chamber **665**, passageway **608** and opening **607** of the model **600**, in an accurate and consistent manner, and in one machining operation or procedure. Further, there is no need for an intervening scanning

operation or procedure to determine the 3D shape of the outer surface 661 or base 609, and then attempt to align the CNC machining of the cavity thereto, as can be required if the outer surface 661 on the one hand, and chamber 665, passageway 608 and opening 607 of the model 600, on the other hand, are manufactured using different methods or which are not based on the same virtual model. The manufacturing process according to at least this example can thus also be relatively quick and efficient.

[0133] The aforesaid computer controlled machining process can thus provide a high degree of dimensional accuracy at least in terms of the position and alignment of the chamber 665, passageway 608 and opening 607 of the model 600, with respect to the outer surfaces 661, and thus in terms of the position and alignment of analog 230 with respect to the model 600 when affixed therein, as the machining process for both the cavity 665 and chamber 665 on the one hand, and the passageway 608 and opening 607 of the model 600 on the other hand, are based on the same coordinate system.

[0134] In alternative variations of this example, the model 600, including the external surface 661, base 609, chamber 665, passageway 608 and opening 607 can be concurrently manufactured using any suitable manufacturing methods, for example rapid prototyping manufacturing methods.

[0135] In yet other alternative variations of this example, the model 600, including the external surface 661 and base 609 can be manufactured using a first manufacturing method, for example rapid prototyping manufacturing methods, while chamber 665, passageway 608 and opening 607 can be subsequently manufactured on this model using a second manufacturing method, for example CNC material removal manufacturing methods. Alternatively, model 600, can be produced using any other suitable computer-controlled manufacturing technique based on the virtual model 500.

[0136] The physical model 600, produced by CNC material removal methods and/or rapid prototyping methods, can be formed entirely of a hard material (or at least external surface 661 is formed entirely of a hard material), for example from a suitable hard machinable plastic or polymeric material or from hard materials commonly used in rapid prototyping manufacturing processes.

[0137] The physical model 600 can thus be made having uniform hardness. Alternatively the physical model can be formed as a composite physical model, for example as disclosed below regarding the second aspect of the presently disclosed subject matter for composite physical model 800, *mutatis mutandis*.

[0138] Once the physical model 600 with its respective installation structure 690 is completed, the analog 230 can be inserted into the physical model 600 in a general coronal direction K to the respective installed position, via apical base opening 607.

[0139] It is to be noted that the physical model 600 can optionally be formed with alignment

features that allow the physical model **600** to be aligned with a physical model of the opposite jaw to provide proper occlusion, and the alignment features are first defined in a virtual manner in the virtual model **500**, for example as disclosed in US 7,220,124, US 2007/0077537 and US 2007/0154867, co-assigned to the present Assignee. Such a physical model **600** with alignment features can be provided according to the following method, for example:

1. (a) using a computer system:
 - providing a three dimensional (3D) virtual dentition model of a patient's dentition including virtual model components corresponding to at least a part of each jaw thereof, and including the dental structure **100**;
 - providing 3D data representative of at least the spatial relationship between said jaws in occlusion;
 - incorporating in said 3D virtual dentition model, one or more digitally created structural reference components defining an alignment arrangement for said 3D virtual dentition model based on said 3D data so as to define an updated 3D virtual dentition model, said one or more structural reference components configured to provide virtual occlusion alignment between said model components according to the spatial relationship; and
2. (b) following step (a), preparing a physical three dimensional (3D) model including said physical model **600** and physical model components that respectively represent said virtual model components, based on said updated 3D virtual dentition model obtained in step (a), wherein said physical model components are produced incorporating one or more physical structural reference components respectively corresponding to one or more digitally created structural reference components to enable selectively providing physical occlusion alignment between said physical model components corresponding to said virtual occlusion alignment.

[0140] Alternatively, the physical model **600** can be configured for mounting onto any dental articulator.

[0141] According to the first aspect of the presently disclosed subject matter, a family of analogs may be conceived and provided, wherein each analog **230** of the family has the same external form **270**, but wherein the analogs **230** in the family differ from one another in having a respective prosthesis interface analog part **238** and corresponding prosthesis engaging analog part **231** that is implant-specific, i.e., that correspond to the prosthesis interface implant part **248** and the prosthesis engaging implant part **241** of a specific type of dental implant, for compatibility with a particular type or make of prosthesis/permanent abutment configuration. For example, each of the analogs **230** in the family may correspond to a different one of a plurality of commercially available dental implants **240**. This allows the method **400** to be effectively applied to a wide range of cases where the dental implant **240** can be chosen for compatibility with any one of a range of such prosthesis/permanent abutment configuration, while the external form **270** of the analog **230** is effectively standardised, enabling the form of the opening **607**, passageway **608** and chamber **665** formed in the physical model **600** can be

standardized, and likewise the virtual equivalents of these components can also be standardized.

[0142] In another example according to the first aspect of the presently disclosed subject matter, a particular desired analog is not originally suitable for, or is unable to be, press-fitted into a complementarily-shaped chamber, formed in the physical model, in a general coronal direction. For example, and referring to Fig. 11, the desired analog **230'** can be a commercially available analog that can comprise laterally projecting protrusions designed for anchoring the analog in a plaster model when the model is cast using prior art methods, in which the analog is first aligned in the mold prior to casting. The system and method according to the first aspect of the presently disclosed subject matter can be applied in at least two different ways, for example as follows.

[0143] In a first such application of system and method according to the first aspect of the presently disclosed subject matter, and referring to Fig. 11, the physical analog **230'** is embedded in a jacket **300** to form a composite analog **310**. For example, the jacket **300** is made from a machinable material, which is milled or otherwise machined in situ on the analog **230'** to have a relative smooth external shape **315** that is readily insertable in the general coronal direction **K**, into the in the physical model, referred to herein by the reference numeral **601**, and which enables the composite analog **310** to be fixed therein in six degrees of freedom at spatial disposition **P'**. Thus, the external shape **315** can correspond to or be similar to the external form **270** as described above to any one of the examples of analog **230**, for example. On the other hand, the physical model **601** has a respective analog physical installation structure **690**, for example including passageway **321** and chamber **320**, and model base opening **322**.

[0144] The shape and relative position of the outer surface **315** of the jacket **300** that is to mate against the internal surface **325** of chamber **320** can be predefined, for example. The shape and relative position of the outer surface **315** of the jacket **300** that is to mate against the internal surface **325** of chamber **320** can be predefined. The jacket **300** is formed on the analog **230'** - for example the analog **230'** is cast or otherwise embedded in a blank of material, and the jacket **300** is machined until a desired form is provided for outer surface **315**. Alternatively, a cast material can be poured into a precision mold of a predefined internal shape, while analog **230'** is being held in a predefined spatial relationship with respect thereto by an accessory such as a suitable jig or the like.

[0145] The method steps as disclosed above and with reference to Fig. 4 are applicable to this example of physical model **601**, *mutatis mutandis*, with the main difference that in general at least some of the steps therein relating to the analog **230**, chamber **665**, passageway **608** and opening **607**, and their virtual equivalents, can be applied, in this example, to the composite analog **310**, respective chamber **320**, respective passageway **321** and respective opening **322** instead, *mutatis mutandis*, while step **420** for the second example is substantially the same as for the first example relating to physical model **600** *mutatis mutandis*.

[0146] In step 470, though, the virtual analog 730, while now representative of the physical analog 230' rather than analog 230, is further representative of the jacket 300, and thus in particular corresponds to the composite analog 310. In any case, in step 470, the resulting composite analog 310 can be scanned, for example, to generate the corresponding virtual analog 730.

[0147] In step 450, the outer surface and the chamber 320 of the physical model 601 are manufactured in a similar manner to that for physical model 600, *mutatis mutandis*, and the composite analog 310 can then be installed into the chamber 320 via opening 322 and passageway 321 in a general coronal direction K such that the analog 230' is aligned with the model 601 in spatial disposition P'. The physical model 601 can be made having uniform hardness, for example as disclosed herein for physical model 600, *mutatis mutandis*, or can be formed as a composite physical model, for example as disclosed below for composite physical model 800, *mutatis mutandis*. In any case, once the physical model has been manufactured, the composite analog 310 is inserted into chamber 320 via opening 322 and passageway 321.

[0148] Alternatively, and in a second such application of system and method according to the first aspect of the presently disclosed subject matter, a physical model of the dental structure 100 is provided in a similar manner to that disclosed herein for the above examples, *mutatis mutandis*, with some differences. Referring to Fig. 12, the first difference is that the respective chamber 665" and respective passageway 608" are provided being significantly larger (i.e., having larger cross-section) than required for accommodating the analog 230' in a tight fit configuration, and the respective chamber 665" and respective passageway 608" can be of any desired shape so long as the analog 230' can be inserted therein in a general coronal direction, with a lateral clearance 662 therebetween, to the installed position at spatial disposition P'. In this case, the virtual analog installation structure is generated to provide a corresponding clearance for the virtual analog corresponding to the analog 230'. Once the physical model 603 is manufactured, an accessory in the form of an accessory in the form jig 700 is used for holding the analog 230' within the chamber 665", via opening 607" and passageway 608" in the desired position and orientation therein, i.e., in spatial disposition P' having been inserted therein in a general coronal direction K. A filling and fixing material, for example epoxy resin, is then introduced in the clearance gap 662 and allowed to set, cementing the analog 230' in place, after which the jig 700 can be disengaged from the analog 230' and from the model 603.

[0149] The jig 700, according to a first example thereof, comprises a base 710, and a substantially rigid, inverted U-shaped strut 720, having one arm 722 rigidly attached to the base 710 and a second arm 724 having a free end 725 onto which an analog 230' can be mounted at apical end thereof 239" (opposed to the abutment receiving end thereof) in a known and unique spatial relationship with respect thereto. There is thus a unique and fixed spatial relationship between the end 725 and the base 710. The shape of the jig is only illustrative, and any suitable arrangement can be used that has a fixed geometrical relationship between the model-engaging base and the analog apical end. Furthermore, the mating platform 670 is attached to the model base, in a unique mating spatial position (or indeed to

another structure in a known fixed relationship to the model **603**) remote from parts of the model **603** representing dental surfaces, and thus facilitates the cementing procedure for the user as there is a minimum or zero obfuscation of the chamber **665**" and analog **230**' by the jig.

[0150] The physical model **603** according to this example can be made having uniform hardness, for example as disclosed herein for physical model **600**, *mutatis mutandis*, or can be formed as a composite physical model, for example as disclosed below for composite physical model **800**, *mutatis mutandis*.

[0151] It is to be noted that the first subsystem **260** in which virtual models are created and operated on according to any of the examples of the presently disclosed subject matter does not necessarily need to be located in the same geographical location as the scanner **250** and patient. Thus, while the scanning of the patient is usually done at a dental clinic by the dentist or other dental practitioner, the dental clinic can instead or additionally be linked to one or more dental labs, and possibly also to a dental service center via a communication system or network such as for example the Internet or other suitable communications medium such as an intranet, local access network, public switched telephone network, cable network, satellite communication system, and the like. Additionally or alternatively, the communication system can include postal or courier services, the data being communicated via a transportable medium such as an optical disc, magnetic disc and so on. In any case, once the virtual model is created, the physical dental model, and other dental procedures not carried out on the actual patient, can be carried out by the dental lab which receives the required data generated by the method **400** via the communications system. Additionally or alternatively, the physical dental model can be manufactured in one location, and sent to another location in which the analog is implanted in the physical dental model.

[0152] Referring to Fig. 13, an example of method **900** for providing a composite physical model of a dental structure according to the second aspect of the presently disclosed subject matter broadly includes the following steps **920** and **950**:

Step **920** - providing a virtual model of the physical dental structure;

Step **950** - using said virtual model, manufacturing a composite physical model corresponding to said virtual model, the physical model including a first physical model part and a second physical model part having at least one physical property different from a physical property of said first physical model part.

[0153] In the following example, the dental structure is the aforesaid dental structure **100** which includes a dental implant **240** implanted therein at a particular implant site **150**, and includes hard dental surfaces **110** and soft dental surfaces **120** thereof. Thus step **920** can correspond to step **420** according to the first aspect of the presently disclosed subject matter, *mutatis mutandis*, wherein virtual model **500** of the dental structure **100** is generated. However,

it is to be noted that method **900** is not limited to such a dental structure, and can thus also be applicable be applicable for the manufacture of other dental physical composite models in a similar manner to that disclosed herein, *mutatis mutandis*, whether configured for having an analog installed therein in any suitable manner, or whether the physical composite model is not configured for incorporating an analog - for example a regular dental model, or one used for manufacturing and fitting a prosthesis on a preparation.

[0154] In other words, the method **900** is also applicable, *mutatis mutandis*, to other dental structures having hard dental structures (for example optionally including a tooth preparation) and soft dental structures, and optionally having an absence of any implants in the dental structure. For example, where the dental structure lacks a dental implant, step **920** can be similar to step **420**, but can exclude any activity directed to determining the spatial disposition of the implant, *mutatis mutandis*, and similarly step **950** excludes manufacturing an analog installation structure, *mutatis mutandis*.

[0155] Referring to Fig. 13(a), and to Figs 14(a) to 14(c), step **950** can include the following substeps:

Step **952** - identifying at least some virtual surfaces of virtual model **500** corresponding to some or all of the soft dental surfaces **120** of the dental structure **100**;

Step **954** - modifying virtual model **500** to create a virtual soft model part **580** corresponding to at least some of the soft dental surfaces **120**, and a virtual hard model part **560** corresponding to at least some of the hard dental surfaces **110**.

[0156] In step **952**, a zone or surface **910** is defined on the second virtual portions **508**, around the virtual coronal opening **503** corresponding to the zone of soft dental surfaces **120** of the original dental structure **100** that surrounds the implant site **150** and that is to be represented in the composite model **800** by the soft model part. For example, surface **910** can extend up to the virtual gingival margins **915** of the virtual teeth **917** (of the virtual portions **509**) that are adjacent the virtual coronal opening **503**.

[0157] The particular second virtual portions **508** can be identified by, and surface **910** can be defined by, the user, in an interactive manner using the first subsystem **260** of system **200** (Fig. 3), for example. Alternatively, second virtual portions **508** can be identified and/or surface **910** can be defined in an automated or semi-automated manner. For example, the computer system **260** can be programmed to automatically identify the virtual coronal opening **503** and then identify and define surface **910** by radiating outwardly along the second virtual portions **508** of the virtual model **500** by a fixed spacing, for example, or until the curvature of the virtual model **500** indicates that the surface is curving in an upward direction, which is indicative of the first virtual portions **509**.

[0158] It is evident that for at least this particular application of method **900**, it is only desired

for a relatively small area around the implant site **150** to be reproduced in the composite model **800** using a relatively soft material, while the remainder of the composite model **800**, including other parts thereof that correspond to other soft dental surfaces **120**, may be included in the hard model part. In other applications of method **900**, other parts or all of the parts of the virtual model **500** that represent the soft dental surfaces **120** may be included in the soft model part.

[0159] In step **954**, once surface **910** is defined, a second virtual surface **920** is defined, for example by displacing a copy of surface **910** in an inwardly or apical direction by a predefined displacement "**d**". For example, displacement "**d**" can correspond to spacing between the most coronal part of surface **910** and the position of third virtual portion **502** (corresponding to the position of the exposed part of prosthesis engaging part **248**), or may be some percentage greater than this spacing, for example 105%, 110%, 125, 150% or 200% or more of this spacing. Then, an additional outer lateral virtual surface **930** is defined, joining together the outer edges **911** and **921** of surfaces **910** and **920**, respectively, and where necessary an additional inner lateral virtual surface **940** is defined, joining together the inner edges **912** and **922** of surfaces **910** and **920**, respectively.

[0160] Alternatively, second surface **920** can be defined in any other suitable manner - for example by defining a plane (or any other surface, e.g. a part-cylindrical surface) at a desired orientation (for example parallel to the occlusal plane or to any other suitable reference plane), displacing this plane in an apical direction **AP** from the position of portion **502** by a suitable displacement or maintaining the plane at portion **502**, and then intersecting the plane with second virtual portions **508**, for example.

[0161] The virtual hard model part **560** is then created by removing surface **910** and inner lateral virtual surface **940** from the virtual model **500**, and adding surface **920** and outer lateral virtual surface **930**. The virtual hard model part **560** corresponds to the hard model part **860** of the composite physical model **800** that is to be manufactured.

[0162] A virtual soft model part **580**, separate from the virtual hard model part **560**, is also created by joining surface **910** and inner lateral virtual surface **940** to surface **920** and outer lateral virtual surface **930**, and the virtual soft model part **580** corresponds to the soft model part **880** of the physical composite model **800**. In at least some variations of this example, a small spacing may be desired between the soft model part **880** and the hard model part **860**, for example for introducing an adhesive therebetween, and in such cases the virtual soft model part **580** or the virtual hard model part **560** is correspondingly modified by displacement of the corresponding surface **920** thereof.

[0163] Referring again to Fig. 13(a), step **950** can further include the following substeps:

Step **956** - generating machine instructions for manufacturing the physical composite model **800** including physical soft model part **880** based on and corresponding to virtual soft model part **580** and a physical hard model part **860**, based on and corresponding to said virtual hard

model part **560**.

Step **958** - using the machine instructions, manufacturing the physical composite model **800**.

[0164] In step **956** the virtual soft model part **580** and the virtual hard model part **560** (which optionally may be combined in to a single virtual model while retaining their characteristics) are suitably operated on, for example via subsystem **260**, to provide suitable machine instructions to enable in step **958** computer controlled manufacture of the physical composite model **800** (which in this particular application of method **900** also includes the physical installation structure **690** corresponding to the virtual analog installation structure **590**), for example using subsystem **280** (Fig. 3).

[0165] The exact nature of the machine instructions will depend, *inter alia*, on the type of computer controlled manufacture being used in step **958**, for example CNC machining or any type of rapid prototyping (for example stereo lithography, printing, sintering, etc.), and can be carried out using the second subsystem **280**, for example.

[0166] In the example illustrated in Figs. 14(b) and 14(c), the hard model part **860** and the soft model part **880** are separately manufactured and then coupled together. The hard model part **860** can be manufactured based on and corresponding to the virtual hard model part **560**, in a similar manner to that disclosed above for the manufacture of physical model **600** based on virtual model **500**, *mutatis mutandis*. Thus, for example, a CNC material removal operation or procedure can be conducted on a suitable hard material blank, or a suitable rapid prototyping method can be used, or a combination of both, or any other suitable computer-controlled manufacturing technique based on the virtual hard model part **560**.

[0167] The soft model part **880** can be formed from suitable relatively soft material and can be manufactured based on and corresponding to the virtual soft model part **580** using the corresponding machine instructions, in a similar manner to that disclosed above for the manufacture of physical model **600** based on virtual model **500**, *mutatis mutandis*. Preferably, the soft material is similar in at least one of texture, resilience, color and softness to the natural gums, but other materials which are non-rigid can also be suitable, or that are at least softer than the material of the hard model part, and/or have different colors to the natural gums. For example, the soft material can be rubber, silicone, or any other soft tissue material used in the art to create composite dental models.

[0168] The soft model part **880** can be formed in a number of different ways, based on the virtual hard model part **560** and using the appropriate machine instructions derived therefrom. For example, soft model part **880** can be formed via a rapid prototyping manufacturing method, using a suitably soft material - for example using an Objet rapid prototyping machine (for example as disclosed in website www.object.com), and a suitable material, for example as marketed under "TANGO", which can be selectively provided with different levels of rigidity. Alternatively, and depending on the actual hardness of the soft model part, a CNC material

removal operation or procedure can be conducted on a suitable soft material blank, or any other suitable computer-controlled manufacturing technique based on the virtual hard model part **560** and using the appropriate machine instructions derived therefrom.

[0169] Alternatively, a mold can be manufactured (in the form of a negative physical model), also based on the virtual soft model part **580**, to provide mold surfaces that are substantially complementary to the outer-facing surfaces of the required soft model part **880**. The mold can be manufactured using, for example via CNC material removal methods on a blank of suitable mold material and/or via a material additive process, for example a rapid prototyping manufacturing method, or any other suitable manufacturing method, using a suitably mold material, and using the appropriate machine instructions derived based on the virtual soft model part **580**. The soft model part **880** can then be formed by casting or injecting suitable soft material into the mold and allowing to set. It is to be noted that the hard model part **860** can also be manufactured in a similar manner from a mold in the form of negative physical model that is based on the virtual hard model part **560** and manufactured based on and corresponding to the virtual hard model part **560**, and using the appropriate machine instructions derived based thereon.

[0170] Alternatively, the soft model part **880** can be produced any other suitable computer-controlled manufacturing technique based on the virtual soft model part **580** and suitable relatively soft materials.

[0171] Referring to Fig. 14(c), the soft model part **880** is affixed onto the hard model part **860** to complete the composite physical model **800**.

[0172] The soft model part **880** can be affixed onto the hard model part **860** in a number of different ways, for example via a mechanical arrangement, adhesives, welding and so on. For example, an interlocking mechanical arrangement can be provided, which is first modeled in the virtual soft model part **580** and/or the virtual hard model part **560**.

[0173] For example, and as illustrated in Figs. 14(b) and 14(c), in one such interlocking mechanical arrangement the soft model part **880** can be formed with a number of holes **885** that are configured for receiving complementary projections **865** formed on the hard model part **860** in corresponding locations, so that when thus received, the soft model part **880** is in the correct relative spatial relationship with respect to the hard model part **860**. For example, the projections and holes can be formed integrally with the soft model part **880** and hard model part **860**, and the corresponding virtual soft model part **580** and virtual hard model part **560** are correspondingly modified to include virtual of projections **585** and complementary virtual holes **565'**, respectively, in step **954** or in step **956**, prior to manufacture. The projections and holes may have any cross-sectional shapes, so long as they are complementary to one another, and the projections may be formed as pins, tabs, and so on.

[0174] In alternative variations of this example, the holes can be formed on the hard model part **860** and the projections in the soft model part **880**, or there can be a combination of

projections and holes formed on the hard model part **860** that are paired to complementary holes and projections formed in the soft model part **880**. Alternatively, holes can be formed on the hard model part **860** and in the soft model part **880**, in mutual registry, and a plurality of pins used to connect paired holes in the hard model part **860** and the soft model part **880**.

[0175] Alternatively, for example, suitable wells can be formed in corresponding parts of the soft model part **880** and hard model part **860**, and suitable magnets placed in these wells so that the soft model part **880** and hard model part **860** can be engaged magnetically; the wells are first modeled in the corresponding virtual soft model part **580** and virtual hard model part **560**.

[0176] Alternatively, for example, the soft model part **880** can be overlaid on hard model part **860**, and affixed therein using spikes traversing the soft model part **880** and penetrating the hard model part **860**, for example.

[0177] Alternatively, a suitable adhesive can be used for fixing the soft model part **880** on hard model part **860**. In such a case, the soft model part **880** and/or hard model part **860**, can be formed with a small clearance therebetween to allow room for the adhesive, and this clearance is first modeled in the virtual soft model part **580** and/or the virtual hard model part **560**.

[0178] Alternatively, any other suitable means can be used for affixing the soft model part **880** to the hard model part **860**, and modeled as appropriate in the virtual soft model part **580** and/or the virtual hard model part **560**.

[0179] In any case, where appropriate, the virtual hard model part **560** and the virtual soft model part **580**, can be formed with spatial virtual features that ensure that the corresponding physical features, formed on the hard model part **860** and the soft model part **880**, respectively, provide (when aligned) the correct spatial disposition between the hard model part **860** and the soft model part **880**. Such features may comprise suitable markings, for example.

[0180] Alternatively, in another example of steps **956** and **958**, the composite physical model **800** can be made by first manufacturing the hard model part **860**, for example as disclosed above, *mutatis mutandis*, and then the soft model part **880** can be subsequently formed in situ on the hard model part **860** of the composite physical model **800**. For example, the virtual model **500** can be used to create a physical negative model of the composite physical model **800** to be used as a mold. The hard model part **860** is mounted in the physical negative model, and this results in a gap being created inbetween these two components, the gap corresponding to the soft model part **880**. The soft model part **880** can then be formed by casting or injecting suitable soft material into this gap via suitable injection channels formed in the mold, for example, allowing the soft material to set as appropriate, and subsequently removing the physical negative model.

[0181] Alternatively, in another example of steps **956** and **958**, a suitable rapid prototyping

technique can be used for integrally forming the composite model **800**, based on machine instructions derived from the virtual soft model part **580** and/or the virtual hard model part **560**. For example an Objet rapid prototyping machine (for example as disclosed in website www.object.com) can be used with two materials of different hardnesses, for example as marketed under "TANGO", which can be provided with different levels of rigidity. For parts of the composite physical model **800** corresponding to the virtual hard model part **560**, the rapid prototyping machine uses a relatively hard material, while for parts of the composite physical model **800** corresponding to the virtual soft model part **580**, the rapid prototyping machine uses a relatively soft material.

[0182] In at least this particular application of method **900** directed to the dental structure **100**, and referring to Fig. 14(c), once the composite physical model **800** is ready, the analog **230** can be inserted into the composite model **800** in a general coronal direction **K** in a similar manner to that disclosed above for physical model **600**, *mutatis mutandis*, to assume a spatial disposition **P'** that is fixed in six degrees of freedom with respect to the composite model **800**, corresponding to the spatial disposition **P** of the implant **240** with respect to the dental structure **100**. The prosthesis engaging part **238** of the analog **230** is thus surrounded by relatively soft material, for example in a similar manner to the implant **240** in the dental structure **100**. In the installed position, the prosthesis engaging part **238** of the analog **230** is in abutment with the coronal opening **573'** of the composite model **800**, and thus the exposed part of the prosthesis engaging part **238** is visible and accessible via the coronal opening **573'**.

[0183] In the above examples of implementation of method **900** with reference to dental model **100**, step **950** also includes manufacturing the corresponding analog installation structure, as described herein with reference to the first aspect of the presently disclosed subject matter, *mutatis mutandis*.

[0184] It is to be noted that the composite physical model **800** can be formed with alignment features that allow the composite physical model **800** to be aligned with a physical model of the opposite jaw to provide proper occlusion, and/or be configured for mounting onto any dental articulator, in a similar manner to that described herein for physical model **600**, *mutatis mutandis*.

[0185] According to the first aspect of the presently disclosed subject matter there is provided a system and method for manufacturing a physical model of a physical dental structure that includes a dental implant.

[0186] According to the first aspect of the presently disclosed subject matter there is also provided a method for creating a virtual model usable for making a physical model of a physical dental structure that includes a dental implant at an implant site, the method comprising:

using a computer system:

1. (a) receiving a virtual representation of dental surfaces of the physical dental structure

- with dental implant data representing a location and orientation of the dental implant with respect to the dental surfaces;
2. (b) receiving a virtual analog structure, the virtual analog structure being based on said dental implant; and
 3. (c) creating the virtual model based on:
 - said virtual representation of dental surfaces; and
 - a virtual analog socket structure based on said virtual analog structure and said dental implant data, and having an virtual analog insertion opening that is spaced from parts of the virtual model corresponding to dental surfaces and the implant site.

[0187] The above method for creating a virtual model usable for making a physical model of a physical dental structure that includes a dental implant at an implant site, can optionally comprise one or more of the following features, in any desired combination or permutation:

1. (A) For example, said virtual analog structure is representative of a desired dental analog that corresponds to the dental implant, and wherein said virtual analog socket structure is configured for virtually receiving therein said analog virtual structure via said virtual analog insertion opening.
2. (B) Additionally or alternatively for example, said virtual analog socket structure is configured for virtually receiving therein said analog virtual structure at a virtual installed position with respect to said virtual representation of dental surfaces corresponding to said implant data.
3. (C) Additionally or alternatively for example, said virtual analog insertion opening is at a location other than at said virtual representation of dental surfaces.
4. (D) Additionally or alternatively for example, said virtual analog insertion opening excludes a location in said virtual representation of dental surfaces corresponding to a location of the implant site in the physical dental structure.
5. (E) Additionally or alternatively for example, said virtual analog insertion opening is different from an access opening to the virtual analog socket structure that is located at a location in said virtual representation of dental surfaces corresponding to a location of the implant site in the physical dental structure. For example, said access opening has a smaller maximum width than a maximum width of said virtual analog insertion opening.
6. (F) Additionally or alternatively for example, step (a) further comprises receiving an auxiliary virtual representation of a base structure having base surfaces unrepresentative of said dental surfaces.
7. (G) Alternatively for example, step (a) further comprises receiving an auxiliary virtual representation of a base structure having base surfaces unrepresentative of said dental surfaces, and for example, said virtual analog insertion opening is at a location in said virtual representation of dental surfaces corresponding to said base surface.
8. (H) Additionally or alternatively for example, said virtual analog socket structure is configured for virtually receiving therein said analog virtual structure via said virtual analog insertion opening and along an insertion path, wherein said insertion path is

along an insertion direction including at least one of:

- a general coronal direction;
- a non-apical direction;
- a direction passing through said virtual representation of dental surfaces from a first location with respect to the virtual model corresponding to an inside of the dental structure to a second location with respect to the virtual model corresponding to an outside of the dental structure.

9. (I) Additionally or alternatively for example, step (a) comprises scanning the dental structure to generate said virtual representation of dental surfaces, and using a virtual implant part in said virtual representation of dental surfaces corresponding to an exposed part of the dental implant to obtain said dental implant data. For example, step (a) comprises comparing said virtual implant part to an implant virtual model representative of the dental implant, and operating on said virtual representation of dental surfaces to determine said dental implant data based on a location and orientation of said virtual implant part with respect to a remainder of said virtual representation of dental surfaces.
10. (J) Alternatively, for example, step (a) comprises:
 - performing a first scanning procedure of said dental structure with the dental implant exposed to generate said virtual representation of dental surfaces;
 - mounting a scanning abutment to the dental implant in an abutment spatial disposition with respect to the dental implant, performing a second scanning procedure of said dental structure including said scanning abutment to generate an auxiliary virtual model, and using a virtual scanning abutment part of the auxiliary virtual model corresponding to the scanning abutment to obtain said dental implant data.
11. (K) Additionally or alternatively for example, said virtual analog installation structure comprises a virtual passageway including said virtual analog insertion opening at one end thereof and an auxiliary opening at an opposed end thereof, said auxiliary opening corresponding to an interface between the dental implant and exposed dental surfaces of the dental structure in contact therewith. For example, said virtual passageway is elongate defining a virtual passageway longitudinal axis aligned with an insertion direction into said virtual passageway. Additionally or alternatively for example, said virtual passageway is formed comprising a virtual chamber having a form generally complementary to an external form of at least a part of the dental analog. Additionally or alternatively for example, at least a part of said virtual passageway is non-axisymmetric. Additionally or alternatively for example, said virtual passageway comprises a virtual stop configured for virtually abutting a corresponding part of said virtual analog structure for limiting virtual penetration of the virtual analog structure with respect to said virtual model. Additionally or alternatively for example, a significant virtual clearance gap is provided between said virtual passageway and said external form of at least a part of the dental analog.
12. (L) Additionally or alternatively for example, said virtual model is operated on to generate a virtual hard model part and a virtual soft model part, wherein said virtual hard model part corresponds to at least some hard tissues of the dental structure and wherein said

virtual soft model part corresponds to at least some soft tissues of the dental structure. For example, said virtual soft model part corresponds to an area of the dental structure immediately adjacent the dental implant.

13. (M) Additionally or alternatively for example, the implant site is defined as an area enclosed by a perimeter defined as the interface between the dental surfaces and the dental implant.
14. (N) Additionally or alternatively for example, the method further comprises:
 - generating machine instructions for manufacturing the physical model based on said virtual model;
 - using the machine instructions, manufacturing the physical model, the physical model comprising a physical analog socket structure based on said virtual analog socket structure.
15. (O) Said differently, there is provided a method for making a physical model of a physical dental structure that includes a dental implant at an implant site, the method comprising:
 - providing a virtual model as defined above optionally including one or more of features (A) to (M) in any combination or combination;
 - generating machine instructions for manufacturing a physical model based on said virtual model;
 - using the machine instructions, manufacturing the physical model, the physical model comprising a physical analog socket structure based on said virtual analog socket structure.
16. (P) For example, said physical model is manufactured using one of a computer controlled material removal process and a computer controlled material additive process. For example: said computer controlled material removal process can be a CNC machining process; said computer controlled material additive process can be a rapid prototyping process.
17. (Q) For example, said physical model is manufactured having a substantially uniform hardness.
18. (R) Alternatively, for example, the physical model is manufactured having a hard model part and a soft model part. For example, said soft model part includes an area of said physical model immediately adjacent a opening thereof corresponding to said implant site and configured for exposing therethrough a prosthesis system engaging end of said dental analog when said dental analog is installed in the physical model. Additionally or alternatively for example, said soft model part corresponds to at least some soft tissues of said dental structure. Additionally or alternatively for example, said hard model part corresponds to at least some hard dental surfaces of said dental structure.
19. (S) For example, prior to manufacturing said physical model, said hard model part and said soft model part are first defined in said virtual model as a corresponding virtual hard model part and a corresponding virtual soft model part.
20. (T) Additionally or alternatively for example, the method for making a physical model of a physical dental structure that includes a dental implant at an implant site optionally further comprises:
 - providing the dental analog; and
 - inserting the dental analog into said physical model via said physical analog

socket structure.

21. (U) A physical model, manufactured according to the method for making a physical model of a physical dental structure that includes a dental implant at an implant site
22. (V) A kit comprising a physical model as defined above and at least one dental analog configured for use therewith by insertion into the physical model via said physical analog socket structure.

[0188] According to the first aspect of the presently disclosed subject matter there is also provided a method for creating a virtual model usable for making a physical model of a physical dental structure that includes a dental implant, the method comprising:
using a computer system:

1. (a) receiving a virtual representation of dental surfaces of the physical dental structure with dental implant data representing a location and orientation of the dental implant with respect to the dental surfaces, said dental surfaces including occlusal facing dental surfaces and adjacent dental side surfaces;
2. (b) receiving a virtual analog structure, the virtual analog structure being based on said dental implant; and
3. (c) creating the virtual model based on:
 - said virtual representation of dental surfaces; and
 - a virtual socket analog structure based on said virtual analog structure and said dental implant data, and having a virtual analog insertion opening at a location in said virtual representation of dental surfaces corresponding to said adjacent dental side surfaces of the dental surfaces.

[0189] For example, said adjacent dental side surfaces of the dental surfaces correspond to gingival tissues of the dental structure, and/or, said adjacent dental side surfaces of the dental surfaces correspond to tooth or prosthetic surfaces of the dental structure. Additionally or alternatively the method for creating a virtual model usable for making a physical model of a physical dental structure that includes a dental implant according to this aspect of the presently disclosed subject matter can optionally comprise one or more of features (A) to (F) and/or (H) to (V), *mutatis mutandis*, in any desired combination or permutation.

[0190] According to the first aspect of the presently disclosed subject matter there is also provided a method for creating a virtual model usable for making a physical model of a physical dental structure that includes a dental implant at an implant site, the method comprising:

using a computer system:

1. (a) receiving a virtual representation of dental surfaces of the physical dental structure with dental implant data representing a location and orientation of the dental implant with

- respect to the dental surfaces;
2. (b) receiving a virtual analog structure, the virtual analog structure being based on said dental implant; and
 3. (c) creating the virtual model based on:
 - said first virtual representation of dental surfaces; and
 - a virtual analog socket structure based on said virtual analog structure and said dental implant data, said virtual analog socket structure having a virtual analog insertion opening and an access opening at a location corresponding to the implant site, said access opening being different from said virtual analog insertion opening, wherein said access opening has a smaller maximum width than a maximum width of said virtual analog insertion opening.

[0191] For example, the virtual analog insertion opening is spaced from parts of the virtual model corresponding to dental surfaces and the implant site. Additionally or alternatively the method for creating a virtual model usable for making a physical model of a physical dental structure that includes a dental implant according to this aspect of the presently disclosed subject matter can optionally comprise one or more of features (A) to (D) and/or (F) to (V), *mutatis mutandis*, in any desired combination or permutation.

[0192] According to this aspect of the presently disclosed subject matter there is also provided a method for manufacturing a physical model of a physical dental structure that includes dental surfaces and a dental implant at an implant site, for use with a dental analog corresponding to the dental implant, the method comprising:

receiving a virtual model of the physical dental structure and a virtual analog installation structure in association with said virtual model, said virtual analog installation structure being based on the dental analog;

using said virtual model, manufacturing a physical model corresponding to said virtual model, the physical model being provided with an analog installation structure based on said virtual analog installation structure and thereby configured for enabling the dental analog to be inserted into said physical model through an insertion opening,

wherein said insertion opening is spaced from a location in the physical model corresponding to the implant site in the physical dental structure.

[0193] The method optionally further comprises:

providing the dental analog; and

inserting said dental analog into said physical model via said analog installation structure, and fixing said dental analog therein at said analog spatial disposition.

[0194] Additionally or alternatively, for example, step (a) comprises scanning the dental structure to generate said virtual representation of dental surfaces, and using a virtual implant part in said virtual representation of dental surfaces corresponding to an exposed part of the dental implant to obtain said dental implant data. For example, step (a) comprises comparing said virtual implant part to an implant virtual model representative of the dental implant, and operating on said virtual representation of dental surfaces to determine said dental implant data based on a location and orientation of said virtual implant part with respect to a remainder of said virtual representation of dental surfaces.

[0195] Alternatively, for example, step (a) comprises:

performing a first scanning procedure of said dental structure with the dental implant exposed to generate said virtual representation of dental surfaces;

mounting a scanning abutment to the dental implant in an abutment spatial disposition with respect to the dental implant, performing a second scanning procedure of said dental structure including said scanning abutment to generate an auxiliary virtual model, and using a virtual scanning abutment part of the auxiliary virtual model corresponding to the scanning abutment to obtain said dental implant data.

[0196] Additionally or alternatively, for example, said virtual model comprises a virtual external surface corresponding to dental surfaces of said dental structure, and further comprising modifying said virtual model to include a virtual model base comprising a respective virtual external base surface. For example, said virtual external base surface excludes any representation of said dental surfaces of said dental structure. Additionally or alternatively, for example, in step (b) said analog installation structure is first defined in said virtual model as a virtual analog installation structure, said virtual analog installation structure comprising a virtual passageway having a first virtual opening provided in said virtual model base, and a second virtual opening corresponding to an interface between said dental implant and exposed dental tissues of said dental structure in contact therewith. For example, said virtual passageway is elongate defining a virtual passageway longitudinal axis aligned with said general coronal direction. Additionally or alternatively, for example, said virtual passageway is formed comprising a virtual chamber having a form generally complementary to an external form of at least a coronal part of said dental analog, such that a physical chamber corresponding to said virtual chamber and formed in said physical model provides a close fit with respect to at least said coronal part of said dental analog to accommodate said dental analog at said analog spatial disposition with respect to the physical model. Additionally or alternatively, for example, at least a part of said virtual passageway is non-axisymmetric. Additionally or alternatively, for example, said virtual passageway comprises a virtual stop corresponding to a mechanical stop in said physical model configured for limiting penetration of the dental analog to said installed position. Additionally or alternatively, for example, step (b) comprises aligning the virtual analog

installation structure with said virtual model based on said virtual implant spatial disposition to ensure that said analog installation structure allows said analog to attain said analog spatial disposition in the physical model.

[0197] Additionally or alternatively, for example, said virtual passageway is formed comprising a virtual chamber having a form generally complementary to an external form of at least a coronal part of the dental analog, such that said chamber formed in said physical model provides a significant clearance gap with respect to said dental analog, wherein said dental analog comprises a jacket formed of suitable model material, said jacket having an external form substantially complementary to that of said chamber, to enable a composite analog comprising said dental analog including said jacket to be accommodated in said chamber at said analog spatial disposition.

[0198] Additionally or alternatively, for example, said virtual passageway comprises a virtual chamber having a form generally complementary to an external form of at least a coronal part of said dental analog, such that said chamber formed in said physical model provides a significant clearance gap with respect to said dental analog, and further comprising:

maintaining said analog spatial disposition between said dental analog and said chamber using a jig at least until the dental analog is affixed therein;

introducing a suitable filler into said clearance gap to fix said dental analog in said chamber at said analog spatial disposition.

[0199] Additionally or alternatively, for example, said insertion opening is at a location other than at physical model dental surfaces corresponding to said dental surfaces.

[0200] Additionally or alternatively, for example, said insertion opening excludes a location in said physical model corresponding to a location of the implant site in the dental structure.

[0201] Additionally or alternatively, for example, said insertion opening is different from an access opening to the analog installation structure that is located at a location in said physical model corresponding to a location of the implant site in the physical dental structure. For example, said access opening has a smaller maximum width than a maximum width of said insertion opening.

[0202] Additionally or alternatively, for example, herein said insertion path is along an insertion direction is at least one of:

a general coronal direction;

a non-apical direction;

a direction passing through a representation of said dental surfaces in the physical model, from

a first location inside the physical model to a second location outside of the physical model.

[0203] Additionally or alternatively, for example, step (b) comprises:

generating machine instructions for manufacturing the physical model based on said virtual model and the virtual analog installation structure;

using the machine instructions, manufacturing the physical model.

[0204] Additionally or alternatively, for example, step (b) wherein said physical model is manufactured using one of a computer controlled material removal process and a computer controlled material additive process. For example: said computer controlled material removal process can be a CNC machining process; said computer controlled material additive process can be a rapid prototyping process.

[0205] Additionally or alternatively, for example, said physical model is manufactured having a substantially uniform hardness.

[0206] Alternatively, for example, the physical model is manufactured having a hard model part and a soft model part. For example, said soft model part includes an area of said physical model immediately adjacent a coronal opening thereof configured for exposing therethrough a coronal end of said dental analog when installed in the physical model. Additionally or alternatively, for example, said soft model part corresponds to at least some soft tissues of said dental structure. Additionally or alternatively, for example, said hard model part corresponds to at least some hard dental surfaces of said dental structure. Additionally or alternatively, for example, prior to manufacturing said physical model, said hard model part and said soft model part are first defined in said virtual model as a corresponding virtual hard model part and a corresponding virtual soft model part.

[0207] According to this aspect of the presently disclosed subject matter there is also provided a physical model, manufactured according to the method for making a physical model of a physical dental structure that includes a dental implant at an implant site

[0208] According to this aspect of the presently disclosed subject matter there is also provided a kit comprising a physical model as defined above and at least one dental analog configured for use therewith by insertion into the physical model via said physical analog socket structure.

[0209] According to this aspect of the presently disclosed subject matter there is also provided a physical model of a dental structure, the dental structure including a dental implant at an implant site, the physical model being configured for enabling insertion therein of a dental analog corresponding to the dental implant via an insertion opening that is spaced from a

model implant site location on the physical model corresponding to the implant site.

[0210] For example, the physical model is configured for enabling insertion therein of the dental analog to an installed position in a manner ensuring that a surface topology of said physical model in proximity to the dental analog in the installed position remain representative of the respective surface topology of the dental structure in the vicinity of the dental implant at least during said insertion. Additionally or alternatively, for example, the physical model comprises an analog installation structure configured for enabling the dental analog to be inserted therein via said insertion opening to said installed position therein having an analog spatial disposition with respect to said physical model corresponding to a physical implant spatial disposition of the dental implant with respect to the dental structure.

[0211] According to this aspect of the presently disclosed subject matter there is also provided a said physical model comprises an external surface corresponding to dental surfaces of the dental structure, and further comprises a model base comprising a respective external base surface. For example, said external base surface excludes any representation of the dental surfaces of the dental structure. Additionally or alternatively, for example, said analog installation structure comprising a passageway extending from said insertion opening provided in said model base, and a second opening on said external surface at said model implant site location. For example, said passageway is elongate defining a passageway longitudinal axis aligned with a general coronal direction. For example, said passageway longitudinal axis is co-axial with a longitudinal axis of the dental analog when the dental analog is in said installed position. Additionally or alternatively, for example, said passageway comprises a chamber having a form generally complementary to an external form of at least a coronal part of the dental analog, such that said physical chamber provides a close fit with respect to at least said coronal part of the dental analog to accommodate the dental analog at said analog spatial disposition with respect to the physical model. Additionally or alternatively, for example, said passageway comprises a chamber having a form generally complementary to an external form of at least a coronal part of said dental analog, such that said chamber formed provides a significant clearance gap with respect to said dental analog. Additionally or alternatively, for example, at least a part of said passageway is non-axisymmetric. Additionally or alternatively, for example, said passageway comprises a mechanical stop configured for limiting penetration of the dental analog to said installed position.

[0212] Additionally or alternatively, for example, said physical model comprises a uniform hardness.

[0213] Alternatively, for example, the physical model comprises a hard model part and a soft model part. For example, said soft model part includes an area of said physical model adjacent a second opening thereof configured for exposing therethrough a coronal end of said dental analog when installed in the physical model. Additionally or alternatively, for example, said soft model part corresponds to at least some soft tissues of the dental structure. Additionally or alternatively, for example, said hard model part corresponds to at least some hard dental surfaces of the dental structure.

[0214] Additionally or alternatively, for example, the implant site corresponds to an interface between the dental implant and exposed dental tissues of the dental structure in contact therewith

[0215] Additionally or alternatively, for example, said second opening has a smaller maximum width than a maximum width of said insertion opening.

[0216] According to this aspect of the presently disclosed subject matter there is also provided a dental analog configured for being inserted into a passageway of a physical model of a dental structure, which dental structure includes a dental implant at an implant site, the passageway including an insertion opening and a second opening corresponding to the implant site, said second opening having a smaller maximum width than a maximum width of said insertion opening. For example, the dental analog comprises a first analog end corresponding to said insertion opening and a second analog end corresponding to said second opening, wherein said second analog end has a smaller maximum width than a maximum width of said first analog end.

[0217] Additionally or alternatively, for example, the dental analog has a coronal portion and an enlarged apical portion, wherein in use said dental analog is implanted in a physical model of a dental structure in an installed position such that said coronal portion and said enlarged apical portion are within the physical model.

[0218] Additionally or alternatively, for example, the dental analog comprises a longitudinal axis, and wherein at least a longitudinal portion of one of said coronal portion and an apical portion is non-axisymmetric about said longitudinal axis.

[0219] Additionally or alternatively, for example, the dental analog comprises an external form configured for being inserted into the physical dental model in a general coronal direction to the installed position via the passageway formed in the physical model, wherein at least a portion of said external form is non-axisymmetric with respect to said general coronal direction. For example, at least one of said coronal portion and said apical portion is configured for fixing a spatial disposition of the dental analog with respect to the passageway in up to four degrees of freedom associated with axes orthogonal to the general coronal direction.

[0220] Additionally or alternatively, for example, said enlarged apical portion acts as a mechanical stop with respect to a corresponding part of the passageway to define the longitudinal position of said dental analog with respect to the passageway.

[0221] Additionally or alternatively, for example, said dental analog comprises a prosthesis interface analog part and a prosthesis engaging analog part respectively corresponding to a prosthesis interface implant part and prosthesis engaging implant part of respective dental implant, wherein the dental implant is chosen from a plurality of dental implant configurations having different configurations for the respective said prosthesis interface implant part and said

prosthesis engaging implant part.

[0222] According to this aspect of the presently disclosed subject matter there is also provided a kit comprising a physical model of a dental structure that includes a dental implant at an implant site, the physical model having a passageway, an insertion opening and a second opening corresponding to the implant site, said second opening smaller maximum width than a maximum width of said insertion opening and at least one dental analog as defined above.

[0223] According to the first aspect of the presently disclosed subject matter there is also provided a system and method for manufacturing a physical model of a dental structure that includes a dental implant. In at least one example, the physical model is configured to allow a dental analog can be inserted into the physical model in a general coronal direction. A virtual model of the dental structure is provided including a virtual implant spatial disposition with respect to the virtual model corresponding to a physical implant spatial disposition of the dental implant with respect to the physical dental structure. A virtual analog installation structure is defined in the virtual model. Using the virtual model, a physical model corresponding to the virtual model is manufactured, the physical model being provided with a physical analog installation structure corresponding to the virtual analog installation structure. The physical analog installation structure is configured for enabling a dental analog, corresponding to the dental implant, to be inserted in a general coronal direction with respect to the physical model to an installed position in the physical model. In the installed position, the dental analog has an analog spatial disposition with respect to the physical model corresponding to the physical implant spatial disposition of the dental implant with respect to the physical dental structure.

[0224] According to the second aspect of the presently disclosed subject matter there is provided a system and method for manufacturing a composite physical dental model of a dental structure, the method broadly comprising:

1. (a) providing a virtual model of the dental structure;
2. (b) using said virtual model, manufacturing a composite physical model corresponding to said virtual model, the physical model including a first model part and a second model part having at least one physical property different from a physical property of said first model part, wherein said first model part and said second model part are previously defined in said virtual model, and wherein said at least one physical property excludes a surface topology.

[0225] For example said physical property is a mechanical property.

[0226] For example, step (b) comprises:

(b1) identifying at least some virtual surfaces of said virtual model corresponding to at least a part of the soft dental surfaces of the dental structure;

(b2) modifying said virtual model to create a first virtual model part corresponding to said at least part of the soft dental surfaces, and a second virtual model part corresponding to at least a part of the hard dental surfaces of the dental structure.

[0227] For example, step (b) further comprises:

(b3) generating machine instructions for manufacturing the physical composite model including said first model part based on and corresponding to said first virtual model part and said second model part based on and corresponding to said second virtual model part;

(b4) using the machine instructions, manufacturing the physical composite model.

[0228] Additionally or alternatively, said virtual model comprises a virtual surface corresponding to a dental surface of said dental structure, wherein said first virtual model part includes a first virtual surface part of said virtual surface and wherein said second virtual model part includes a second virtual surface part of said virtual surface. For example, said first virtual surface part is in virtual abutment with said second virtual surface part.

[0229] Additionally or alternatively, in step (b4), said first model part is produced separately from said second model part, and wherein said first model part and model part are joined together in said composite model. For example, said second physical model part is produced using one of a computer controlled material removal process and a computer controlled material additive process: for example, the computer controlled material removal process is a CNC machining process; for example the computer controlled material additive process is a rapid prototyping procedure.. For example, said first physical model part is produced by a separate casting procedure or via a rapid prototyping procedure.

[0230] For example, said first physical model part and said second physical model part are produced with affixing features configured for enabling the first physical model part to be affixed with respect to the second physical model part in a relative spatial disposition therewith corresponding to the relative spatial disposition of the respective real parts of the real dental structure. For example, said affixing features correspond to virtual affixing features previously defined in said first virtual model part and said second virtual model part in step (b).

[0231] Alternatively, in step (b4), said second model part is produced first, and said first model part is produced in situ on said second model part. For example, said second physical model part is produced using one of a computer controlled material removal process and a computer controlled material additive process, and wherein said first physical model part is produced by a casting procedure

[0232] Alternatively, in step (b4), said first model part is produced integrally with said second

model part. For example, said first model part and said second model part are integrally produced via a computer controlled material additive process, for example a rapid prototyping procedure.. For example, said rapid prototyping procedure employs a first material for producing said first model part, and a second material for producing said second model part, said first material and said second material being of a different said property one from another. For example, said first material is relatively softer than said second material.

[0233] Additionally or alternatively, said at least one physical property is chosen from texture, resilience, color and softness.

[0234] Additionally or alternatively, said composite model is further configured with alignment features for enabling occlusal alignment of the composite physical model with a physical dental model of an opposite jaw.

[0235] Additionally or alternatively, the dental structure includes a dental implant, and wherein said composite model is configured for installing therein a corresponding dental analog. For example, said first model part includes an area of said composite model adjacent a coronal opening thereof configured for exposing therethrough a coronal end of the dental analog when installed in the composite model. For example such a composite model can further assist a dental technician in the design and/or preparation of the permanent abutment, coping, prosthesis and so on.

[0236] A composite physical dental model is also provided, produced with the respective method as defined above.

[0237] According to this aspect of the presently disclosed subject matter, before manufacturing the composite model, the soft model part and the hard model part are defined as virtual models.

[0238] In the method claims that follow, alphanumeric characters and Roman numerals used to designate claim steps are provided for convenience only and do not imply any particular order of performing the steps.

[0239] Finally, it should be noted that the word "comprising" as used throughout the appended claims is to be interpreted to mean "including but not limited to".

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US20100021859A [0005]
- WO2009146164A1 [0006]
- US6358052B [0007]
- US20100112527A [0007]
- US2008032262A [0007]
- US20070092854A [0007]
- US2006183078A [0007]
- US20030162148A [0007]
- WO2010108919A [0007]
- US2011294093A [0007]
- US7220124B [0139]
- US20070077537A [0139]
- US20070154867A [0139]

P a t e n t k r a v

5 1. Fremgangsmåde til at skabe en virtuel model (500), der kan bruges til at fremstille en fysisk model (600) af en fysisk tandstruktur (100), der inkluderer et tandimplantat (240) ved et implantatsted (150), hvor fremgangsmåden omfatter:

- 10 (a) modtagelse på et computersystem (260) af en virtuel repræsentation af tandoverflader (110) af den fysiske tandstruktur (100) og tandimplantatdata, der repræsenterer en placering og orientering af det tandimplantat (240), der er implanteret ved implantatstedet (150) i forhold til tandoverfladerne (110);
- (b) modtagelse på computersystemet (260) af en virtuel, analog struktur, hvor den virtuelle, analoge struktur er baseret på tandimplantatet (240); og
- (c) dannelselse på computersystemet (260) af den virtuelle model baseret på:
- 15 - den virtuelle repræsentation af tandoverflader (110); og
- en virtuel, analog sokkelstruktur, der er baseret på den virtuelle, analoge struktur og tandimplantatdataene, og som har en virtuel, analog indsættelsesåbning, der er anbragt i afstand fra dele af den virtuelle model (500), der svarer til tandoverflader (110) og implantatstedet (150).

20 2. Fremgangsmåde ifølge krav 1, hvor den virtuelle, analoge struktur er repræsentativ for en ønsket tandanalog, der svarer til tandimplantatet, og hvor den virtuelle, analoge sokkelstruktur er konfigureret til at modtage den analoge, virtuelle struktur virtuelt via den virtuelle, analoge indsættelsesåbning, og/eller hvor den virtuelle, analoge sokkelstruktur er konfigureret til at modtage den

25 analoge, virtuelle struktur virtuelt i en virtuelt installeret position med hensyn til den virtuelle repræsentation af tandoverflader, svarende til implantatdataene, eller via den virtuelle, analoge indsættelsesåbning og langs en indsættelsessti, hvor indsættelsesstien er langs en indsættelsesretning, der omfatter mindst én af:

- 30 - en generel, koronal retning;

- en ikke-apikal retning; og
- en retning, der passerer gennem den virtuelle repræsentation af tandoverflader, fra en første placering i forhold til den virtuelle model, der svarer til en indvendig del af tandstrukturen, til en anden placering i forhold til den virtuelle model, der svarer til en udvendig side af tandstrukturen.

5

3. Fremgangsmåde ifølge krav 1, hvor den virtuelle, analoge indsættelsesåbning er ved et andet sted end den virtuelle repræsentation af tandoverflader, og/eller

10

hvor den virtuelle, analoge indsættelsesåbning udelukker en placering i den virtuelle repræsentation af tandoverflader, der svarer til en placering af implantatstedet i den fysiske tandstruktur, og/eller

15

hvor den virtuelle, analoge indsættelsesåbning adskiller sig fra en adgangsåbning til den virtuelle, analoge sokkelstruktur, der er placeret ved et sted i den virtuelle repræsentation af tandflader, der svarer til en placering af implantatstedet i den fysiske tandstruktur.

20

4. Fremgangsmåde ifølge krav 3, hvor adgangsåbningen har en mindre maksimal bredde end en maksimal bredde af den virtuelle, analoge indsættelsesåbning.

25

5. Fremgangsmåde ifølge krav 1, hvor trin (a) endvidere omfatter modtagelse af en virtuel hjælpepræsentation af en basisstruktur, der har basisoverflader, der ikke repræsenterer tandoverfladerne.

6. Fremgangsmåde ifølge krav 5, hvor den virtuelle, analoge indsættelsesåbning er ved et sted i den virtuelle repræsentation af tandoverflader, der svarer til basisoverfladen.

- 5 **7.** Fremgangsmåde ifølge krav 1, hvor fremgangsmåden omfatter modtagelse af scanningsdata af tandstrukturen til generering af den virtuelle repræsentation af tandoverflader, og anvendelse af en virtuel implantatdel i den virtuelle repræsentation af tandflader, der svarer til en eksponeret del af tandimplantatet, til at få tandimplantatdataene, og/eller
- modtagelse af scanningsdata fra en første scanningsprocedure af tandstrukturen, hvor tandimplantatet udsættes for at generere den virtuelle repræsentation af tandoverflader;
 - montering af et scanningsanlæg til tandimplantatet i en rumlig anlægsanbringelse i forhold til tandimplantatet, modtagelse af scanningsdata fra en anden scanningsprocedure af tandstrukturen, hvor scanningsdataene fra den anden scanningsprocedure omfatter et scanningsanlæg, der er monteret på tandimplantatet i rumlig anlægsanbringelse i forhold til tandimplantatet, hvorved der genereres en virtuel hjælpemodel, og anvendelse af en virtuel scanningsanlægsdel af den virtuelle hjælpemodel, der svarer til scanningsanlægget til opnåelse af tandimplantatdataene.
- 10
- 15
- 20 **8.** Fremgangsmåde ifølge krav 7, omfattende sammenligning af den virtuelle implantatdel med en virtuel implantatmodel, der er repræsentativ for tandimplantatet, og behandling af den virtuelle repræsentation af tandflader til bestemmelse af tandimplantatdataene baseret på en placering og orientering af den virtuelle implantatdel med hensyn til en rest af den virtuelle repræsentation af tandoverflader.
- 25 **9.** Fremgangsmåde ifølge krav 1, hvor en virtuel, analog installationskonstruktion omfatter en virtuel passage, der indbefatter den virtuelle, analoge indsættelsesåbning i den ene ende deraf og en hjælpeåbning i en modsat ende deraf, hvor hjælpeåbningen svarer til en grænseflade mellem tandimplantatet og eksponerede tandoverflader i tandstrukturen i kontakt dermed.

- 5 **10.** Fremgangsmåde ifølge krav 9, hvor den virtuelle passage er aflang og definerer en virtuel, langsgående passageakse, der er på linje med en indsættelsesretning i nævnte virtuelle passage, og/eller
- 10 hvor den virtuelle passage er dannet og omfatter et virtuelt kammer, der har en form, der generelt er komplementær til en ekstern form af mindst en del af tandanalogen, og/eller
- 10 hvor mindst en del af den virtuelle passage er ikke-aksymmetrisk, og/eller
- 10 hvor den virtuelle passage omfatter en virtuelt passage, der er konfigureret til at støde virtuelt op til en tilsvarende del af den virtuelle, analoge struktur til at begrænse virtuel penetration af den virtuelle, analoge struktur i forhold til den virtuelle model.
- 15 **11.** Fremgangsmåde ifølge krav 10, hvor der er tilvejebragt et virtuelt spillerum mellem den virtuelle passage og den ydre form af mindst en del af tandanalogen.
- 20 **12.** Fremgangsmåde ifølge krav 1, hvor den virtuelle model indbefatter en virtuel, hård modeldel og en virtuel, blød modeldel, hvor den virtuelle, hårde modeldel svarer til mindst nogle hårde væv af tandstrukturen, og hvor den virtuelle, bløde modeldel svarer til mindst nogle bløde væv af tandstrukturen.
- 13.** Fremgangsmåde ifølge krav 12, hvor den virtuelle, bløde modeldel svarer til et område af tandstrukturen umiddelbart ved siden af tandimplantatet.
- 25 **14.** Fremgangsmåde ifølge krav 1, hvor implantatstedet er defineret som et område, der er omgivet af en omkreds, som er defineret som grænsefladen mellem tandoverfladerne og tandimplantatet.
- 15.** Fremgangsmåde ifølge krav 1, endvidere omfattende:

- generering af maskininstruktioner til fremstilling af den fysiske model baseret på den virtuelle model;
- udlæsning af maskininstruktionerne til fremstilling af den fysiske model, hvor den fysiske model omfatter en fysisk, analog sokkelstruktur baseret på den virtuelle, analoge sokkelstruktur.

DRAWINGS




Fig. 1




Fig. 1(a)




Fig. 3




Fig. 4




Fig. 4(a)




Fig. 4(b)




Fig. 4(c)




Fig. 5




Fig. 6(a)




Fig. 6(b)




Fig. 6(c)




Fig. 6(d)




Fig. 6(e)




Fig. 6(f)




Fig. 6(g)




Fig. 6(h)




Fig. 6(i)




Fig. 7




Fig. 8




Fig. 8(a)




Fig. 8(b)




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 13(a)




Fig. 14(a)




Fig. 14(b)




Fig. 14(c)