

(19)



LE GOUVERNEMENT  
DU GRAND-DUCHÉ DE LUXEMBOURG  
Ministère de l'Économie

(11)

N° de publication :

92958

(12)

**BREVET D'INVENTION****B1**

(21)

N° de dépôt: 92958

(51)

Int. Cl.:  
F16K 15/18, F16K 17/08

(22)

Date de dépôt: 25/01/2016

(30)

Priorité:

(72)

Inventeur(s):  
ANDREAS THOMAS – 54441 TEMMELS (Allemagne),  
SCHMITZ PHILIPPE – 7303 STEINSEL (Luxembourg),  
SELLEN STEPHAN – 66693 WEHINGEN (Allemagne)

(43)

Date de mise à disposition du public: 07/08/2017

(47)

Date de délivrance: 07/08/2017

(74)

Mandataire(s):  
LECOMTE & PARTNERS SÀRL –  
1016 LUXEMBOURG (Luxembourg)

(73)


Titulaire(s):  
LUXEMBOURG PATENT COMPANY S.A. –  
7440 LINTGEN (Luxembourg)

(54)

**High pressure valve with telescopic piston.**

(57)

Abstract: The invention is directed to a valve (2) for pressurized gas or chemical agent. The valve (2) comprises: a body (4) with: an inlet (8), an outlet (10), and a passage (6) which connects the inlet (8) with the outlet (10) and which includes a seat (16). The valve (2) further comprises a sliding piston (18) able to engage with the seat (16) in order to close the passage (6) and a telescopic extension (30) sliding against the passage in order to guide the piston (18) in the passage (6) at least between the open position and the closed position. The pressure difference between opposite faces of the piston pulls away the piston (18) and the telescopic extension (30) from the seat (16) in order to open the passage, the passage (6) remaining closed under pressure equilibrium. The invention is also directed to a fire extinguishing system. (figure 1) 92958

**FIG. 1**

**Description****HIGH PRESSURE VALVE WITH TELESCOPIC PISTON****Technical field**

[0001] The invention is directed to a valve opened by the fluid pressure. More particularly, the invention is directed to a valve for a high pressure gas. The invention is also directed to a fire extinguishing system with a valve.

**Background art**

[0002] Prior art patent document published US3862738A discloses a shutoff valve comprising a passageway with a seat, and a perforated valve piston urged against with said seat by means of a spring. The passageway exhibits a pressure balancing chamber, the valve piston being arranged between the seat and the balancing chamber. A three way pilot valve connects the exhaust to the pressure balancing chamber in order to reduce the pressure therein. In such a way, the fluid pressure opposing the spring action moves the valve piston in order to open the shutoff valve. The latter operates in both ways, however this design remains bulky. More specifically, increasing the outlet diameter requires to increase the valve height.

**Summary of invention****Technical Problem**

[0003] The invention aims at providing a valve solving at least one of the problems stated in the prior art. The invention has for technical problem to improve the compactness of a valve. The invention also aims at providing a cost saving solution which also prevents leakage.

**Technical solution**

[0004] The invention is directed to a valve, notably for pressurized gas, comprising : a body with: an inlet, an outlet, and a passage which connects the inlet with the outlet and which includes a seat; and a sliding piston with two opposite faces, which is able to engage with the seat in order to close the passage; the valve being adapted in such a way that a

differential pressure on opposite faces of the piston pulls away the piston from the seat in order to open the passage; wherein the piston is equipped with a telescopic extension sliding against the passage in order to guide the piston in the passage at least between the open position and the closed position.

- [0005] According to a preferred embodiment, the piston slides within the telescopic extension, preferably the telescopic extension is essentially a tube around the piston.
- [0006] According to a preferred embodiment, the piston comprises a sealing element at the sliding interface with the telescopic extension, said sealing element is arranged at the level of the outlet when the piston is in the closed state, preferably the distance X between the sealing element and the seat is smaller than the outlet height Y.
- [0007] According to a preferred embodiment, the piston comprises a through hole in fluid communication with the inlet, preferably the valve comprises a pin closing the through hole when the piston is in the open position more preferably the pin is mounted on a handwheel, and/or the position of the pin is turned by a handwheel.
- [0008] According to a preferred embodiment, in the closed position, the piston is mainly or essentially arranged at the level of the outlet; preferentially arranged within the extension of the outlet inner surface.
- [0009] According to a preferred embodiment, the piston comprises an upper portion sliding against the inner surface of the extension, said upper portion sliding along the majority of, or essentially the whole length of the extension.
- [0010] According to a preferred embodiment, the piston comprises a conical portion, preferably with a hollow base arranged toward the seat.
- [0011] According to a preferred embodiment, the inner diameter of the outlet is equal to or greater than the length of the piston measured between the seat and the upper face of the piston, preferably the piston diameter is at least 50 mm, preferably at least 75 mm.
- [0012] According to a preferred embodiment, the passage comprises a chamber with two halves, namely a first half connecting the inlet with the outlet and

wherein the piston stands in the closed position; and a second half where the piston stands in the open position.

- [0013] According to a preferred embodiment, the body comprises an axial abutment intended to contact the telescopic extension when the piston is in the closed position, preferably the axial abutment is situated at the level of the outlet.
- [0014] According to a preferred embodiment, the valve comprises a resilient member urging the piston in the closed position, preferably the valve is arranged in such a way that the pressure at the inlet urges the extension toward the seat, notably against the axial abutments.
- [0015] According to a preferred embodiment, the telescopic extension comprises a portion shutting at least partially the outlet when the piston is in the closed position.
- [0016] According to a preferred embodiment, the valve comprises a vent connected to the passage in order to create a pressure drop in the passage in order to open the piston, preferentially the vent comprises a pilot device.
- [0017] According to a preferred embodiment, the passage comprises a release chamber with an upper bottom, preferably the release chamber is situated on the opposite of the seat with respect to the piston, preferably the piston and/or the extension abuts the upper bottom in the open state.
- [0018] According to a preferred embodiment, the piston comprises a closing surface which is perpendicular to the closure and to the opening motions.
- [0019] According to a preferred embodiment, the piston comprises a sealing part engaging with the seat; preferably the piston comprises a support maintaining the sealing part.
- [0020] According to a preferred embodiment, the piston is essentially hollow and/or tubular.
- [0021] According to a preferred embodiment, the extension comprises a sealing piece spaced from the gas outlet with respect to the sliding direction, preferably in the closed state at least one or each sealing piece of the telescopic extension is remote from the piston.

- [0022] According to a preferred embodiment, the axial abutment forms at least a semi-circle; preferably the axial abutment is flat, and/or cut by the gas outlet.
- [0023] According to a preferred embodiment, the outer diameter of the piston is greater than its length.
- [0024] According to a preferred embodiment, the inner and/or outer diameter of the extension is greater than its length.
- [0025] According to a preferred embodiment, the sliding stroke of the piston is greater than the extension length and/or greater than the half of its own length.
- [0026] According to a preferred embodiment, the extension comprises a tight wall around the piston in order to close tightly the passage in combination with the piston.
- [0027] According to a preferred embodiment, the first half of the chamber is a lower half, and/or the second half of the chamber is an upper half.
- [0028] According to a preferred embodiment, in the closed state the extension projects over both halves, preferentially the extension is axially centred in the passage chamber.
- [0029] According to a preferred embodiment, the extension forms an annular interface between the piston and the passage preferably a tight and moving interface; and/or the telescopic extension is a sliding guide.
- [0030] According to a preferred embodiment, the piston generally comprises a constant outer diameter, preferably its outer diameter changes of less than 15%, more preferably less than 5%.
- [0031] According to a preferred embodiment, the body comprises an integrally formed portion comprising the passage, the inlet and the outlet.
- [0032] According to a preferred embodiment, in the opened state, the piston and/or the extension are axially remote from the outlet level.
- [0033] According to a preferred embodiment, the piston is longer than the telescopic extension.
- [0034] According to a preferred embodiment, the handwheel is adapted to move the pin axially with respect to the body, preferably between a discharge position and a filling position.

- [0035] According to a preferred embodiment, the valve comprises an upper lid with a substantially free and/or flat upper surface.
- [0036] According to a preferred embodiment, the lid comprises an embossment, where the pilot device is optionally fixed.
- [0037] According to a preferred embodiment, the valve is free of handwheel.
- [0038] The invention is also directed to a fire extinguishing system comprising a fluid storage, notably a gas cylinder, with a high pressure fire extinguishing fluid; and a valve; wherein the valve is in accordance with the invention; preferably the fire extinguishing fluid is a gas or gas mixture.

#### Advantages of the invention

- [0039] The invention is particularly interesting in that it provides a compact design. The height of the valve body above the outlet is reduced, and independent from the diameter of said outlet. This implies a weight reduction and costs savings. The valve may be integrated in narrower place of a fire extinguishing system. The length of the piston is not dictated by the inner diameter of the outlet, which has to be swept in order to ensure a full opening. As a matter of fact, the piston may be provided with several extensions, and arranged in a telescopic cylinder manner.
- [0040] The invention keeps reliable. It is actuated by the inlet gas pressure, said pressure maintaining the piston and the telescopic extension in the open state. The valve is stable by discharge and during refilling. Since the telescopic extension is autonomous, it does not require to be pulled by the piston. This prevents wear. The invention also reduces the weight of the piston. In this way the opening becomes faster and more reliable. The invention is of first interest for wide valve passages with pressures of 42 bars for instance.

#### Brief description of the drawings

- [0041] Figure 1 is a sectional view of a valve in accordance with the first embodiment of the invention, said valve being in a shut-off state and ready for discharge.

- [0042] Figure 2 is a sectional view of the valve of figure 1, wherein the valve is in an intermediate state during discharge.
- [0043] Figure 3 is a sectional view of the valve of figures 1 and 2, the valve being in an open state during discharge.
- [0044] Figure 4 is a sectional view of the valve of figures 1 to 3, the valve being in a shut-off state and ready for filling.
- [0045] Figure 5 is a sectional view of the valve of figures 1 to 4, the valve being in an intermediate state during filling.
- [0046] Figure 6 is a sectional view of the valve of figures 1 to 5, the valve being in an open state during filling.
- [0047] Figure 7 is a sectional view of a valve in accordance with the second embodiment of the invention, said valve being in a shut-off state.
- [0048] Figure 8 is a sectional view of the valve of figure 7, wherein the valve is in an intermediate state.
- [0049] Figure 9 is a sectional view of the valve along the axis 9-9 drawn in figure 8, the valve being in an open state.

#### Description of an embodiment

- [0050] In the following description, the height and the length are measured along the sliding direction of the piston, also called axial direction. The levels are considered with respect to said sliding direction. The up side is considered in accordance with the lift direction of the piston from the seat, the down side is toward the closing direction. The lateral direction is perpendicular to the sliding direction.
- [0051] Figures 1, 2 and 3 are sectional views of a valve during discharge. Figure 1 illustrates the valve 2 in a shut-off state whereas figure 3 illustrates the valve in an open state. Figure 2 illustrates the valve 2 in an intermediate state; between the closed state and the open state.
- [0052] As visible in figure 1, the valve has a main body 4 with a cylindrical shape. It is essentially hollow, and may be tubular. The body 4 includes a passage 6 connecting the inlet 8 to the outlet 10. The body 4 may be manufactured of metal, as brass or a brass alloy for instance. The valve 2 may comprise an upper cap 14 closing the passage 6. The upper cap 14

may include several devices 15, notably a handwheel 15. Said handwheel 15 may be arranged in central position of the upper cap 14.

- [0053] The inlet 8 is arranged downward, at the lower end of the valve. The outlet 10 is arranged laterally and perpendicularly to the opening direction of the valve 2. There, the outlet 10 is dotted with a cap 12 which is removed when the valve is assembled in a fire extinguishing system. The inlet 8 and the outlet 10 both show an inner tubular surface. Their inner diameters may substantially be equal. Other apertures may be provided in the body, each of them may be closed with a plug.
- [0054] The valve 2 is a lift valve, it comprises a seat 16 closed by a piston 18. The valve is opened by lifting the closure member 18 from the seat 16. The piston 18 comprises a lower face intended to engage with the seat 16, and an upper face opposed to the lower face and which faces the upper cap 14. The faces are considered with respect to the sliding direction of the piston. A resilient member 20, as a coil spring 20, maintains the piston in the closed state. The resilient member 20 projects between the piston 18 and the upper cap 14, and may be preloaded. The piston 18 essentially has a cylindrical shape or tubular shape since it is hollow. It may include a tubular outer wall and a lower wall. The latter may comprise a conical portion 22, optionally hollow. The inner diameter of the piston 16 is generally equal to the inner diameter of the inlet 8, preferentially the diameter difference is less than 20%, more preferentially less than 10%.
- [0055] The piston 18 may comprise a through hole 24, for instance across the top of the conical portion 22. The through hole 24 affords pressure equilibrium between the opposed faces of the piston 18, and between the inlet 8 and the upper portion of the passage 6. The piston may carry a sealing part 25 in contact with the seat 16 in order to improve the sealing and to reduce the leaks between the inlet 8 and the outlet 10. The through hole is not an essential feature, for instance the resilient member may be preloaded enough for maintaining the piston in the closed position.
- [0056] The passage 6 may comprise a chamber, optionally a main chamber in the body 4. The chamber may essentially be cylindrical and project along the opening direction of the piston. The chamber may comprise two halves,

namely a first half 26 and a second half 28, for instance a lower half 26 and an upper half 28 respectively. The latter may be a release chamber 28. The first half 26 starts from the inlet 8, preferably from the seat 16, and projects along the outlet 10. The piston 18 may mainly be within the first half 26 in its closed position. The second half 28 extends from the upper cap 14 and ends before the outlet 10. The piston 18 may essentially stand outside the second half 28 in the closed state.

- [0057] The valve also comprises a telescopic extension 30 equipping the piston 18. In the closed state, the telescopic extension 30 is extended, or stretched out from the piston 18. The telescopic extension 30 may slide with respect to the piston 18 and to the passage 6. It may slide against the inner surface 32 of the chamber. The telescopic extension is represented outside the piston, it is however practicable to arrange it inside said piston.
- [0058] The piston 18 and the telescopic extension 30 may both comprise seals (34; 36), ring seals for instance that are arranged in outer annular grooves. The piston 18 comprises a seal element 34 in tight contact with the telescopic extension 30 and sliding therein. The telescopic extension 30 is dotted with a sealing piece 36 sliding against the chamber inner surface 32, and cooperating therewith in a tight fashion. The piston 18, the telescopic extension 30 and the seat 16 form a shut-off device tightly shutting the passage 6 in the closed state. The piston 18 may close the passage alone or in combination with the telescopic extension 30.
- [0059] The body 4 may comprise an abutment 38, engaging axially with the telescopic extension 30 in the closed state. There, the telescopic extension 30 may be equally shared between the halves (34; 36). It may form an arcuate bead protruding from the inner surface 32. The abutment 38 forms an opened loop, which is interrupted by the outlet 10. In the closed state, the inlet pressure acts on the telescopic extension 30, and pushes it against the axial abutment 38.
- [0060] The valve 2 may be used with a gas or with a liquid, for instance a wet chemical agent. The fluid can be a gas mixture, eventually with liquid droplets. The valve inlet may be in fluid communication with a fluid storage in order to form a fixed fire extinguishing system. The fluid storage can be

a tank or a gas cylinder comprising a fire extinguishing fluid. The latter can be at a pressure comprised between 10 bars and 100 bars, preferentially between 40 bars and 50 bars.

- [0061] Figure 2 shows the valve 2 in the intermediate state. The upper cap 14 may comprise a vent 40 in communication with the passage 6, preferably with the second half 28. The vent 40 may become in fluid communication with the environment of the valve 2, which is preferentially at the atmospheric pressure, roughly 1 bar. A pilot device 42, for instance a pilot valve, opens the vent 40 by means of an actuator.
- [0062] The pilot device 42 may be electrically piloted. It may act directly or indirectly. The pilot device 42 may be an electromagnetic valve, which opens when it is electrically powered, and which remains closed without power. The pilot device 42 may comprise a permanent magnet. It may be bistable. The pilot device 42 changes of position in response to an electric power supply, and remains stable in each position even when the power supply is off. Then, the valve may be kept open without external electric power, independently from a closing pin 46. Then, the risks linked to the heating phenomenon of the pilot device 42 are avoided.
- [0063] Then, a pressure drop is triggered. The piston 18 is then subjected to a pressure difference, for instance of at least 40 bars due to the inlet pressure. This differential pressure implies a mechanical load overcoming the effect of the resilient member 20. The inner diameter of the through hole 24 allows to control the flow therethrough under pressure difference. By way of consequence, the piston moves away from the seat 16 and the valve 2 becomes opened. Since the telescopic extension 30 is subjected to the same pressure difference, it also moves toward the cap 14. It leaves the abutment 38, and its outer surface 44 progressively opens the outlet 10.
- [0064] Figure 3 illustrates the valve 2 in the opened state. The telescopic extension 30 and the piston 18 are collapsed in each other. They are plated against the upper cap 14, compressing then the resilient member 20 thereon. The valve 2 is fully opened. The telescopic extension 30, as the piston 18, is away from the outlet 10. This ensures a broad

passageway between the inlet 8 and the outlet 10. This effect is interesting in that it affords a maximum flow, and reduces the pressure losses. In a fire extinguishing system, this improves the safety by fostering the maximal flow of a fire extinguishing fluid at a given inlet pressure.

- [0065] Moreover, the upper cap 14 may support the pin 46 closing the through hole 24 arranged in the piston 18. Consequently, the fluid loss through the vent 40 is controlled. It is limited to the piston opening stroke. Further, this phenomenon is reliable and independent of the pilot device 42 or of its electrical powering.
- [0066] The handwheel 15 is linked to the upper lid 14 by means of a threaded portion 48. This portion 48 engages with a corresponding portion 50 of the upper lid 14. The corresponding portion 50 encircles an annular space 52 receiving the threaded portion 48. In the opened state, the annular space 52 may be arranged inside the sliding piston 16 and/or inside the telescopic extension 30. The lid 14 may comprise a guiding portion 54 for the pin 46. It may be substantially tubular. It may enclose a seal ring 56 around the pin 46. The seal ring 56 may be directly in contact of the pin and of the upper lip 14. Alternatively, the seal ring may be carried by the pin. Turning the handwheel 15 affords to slide the pin 46 vertically, toward or away from the seat 24 by way of example.
- [0067] During discharge, the gas pressure decreases in the gas cylinder. The corresponding mechanical force acting against the lower face of the piston 18 also reduces. The pressure will decrease until the mechanical force exerted by the resilient member 20 overcomes the force of the pressure. Then, the resilient member 20 will push the piston 18 downward, toward the seat 16. The piston 18 will be in the closed state, as illustrated in figure 1. The valve 2 may be configured in order to close the piston 18 when the pressure falls to 2 or 3 bars. This means that the valve 2 shuts-off before it is empty. This phenomenon is of prior interest since it keeps a residual pressure in the gas cylinder. It prevents impurities from entering in the gas cylinder. Remaining gas, for instance NOVEC, also protects the gas cylinder inner surface from corrosion.

- [0068] The figures 4, 5 and 6 illustrate the filling of the gas cylinder through the valve 2. In the filling state, the handwheel 15 carrying the pin 46 is raised. Then, the pin 46 is retracted within the cap 14.
- [0069] During filling, the pressure at the outlet 10 is greater than the pressure at the inlet 8. As shown in figure 4, the pressure at the outlet 10 is greater than the pressure on the upper face of the piston 18 and on the telescopic extension 30. Since in the shut-off state the piston 18 and the telescopic extension 30 close the passage 6, a pressure difference applies on them. Said pressure difference overcomes the force of the resilient member 20, and lifts the piston 18 from the seat 16. This also lifts the telescopic extension 30 from the axial abutment 38. The corresponding state is illustrated at figure 5. Due to dynamic pressure, the piston 18 and the telescopic extension 30 keep rising, and move upward.
- [0070] As illustrated in figure 6, the piston 18 and the telescopic extension 30 are lifted until abutting against the cap 14. There, the pin 46 is remote from the piston 18, and more peculiarly from the through hole 24. The tip of the pin 46 remains away from the O-ring in the through hole 24 in order to keep open the fluid communication through the piston 18.
- [0071] The filling is operated until the gas cylinder is full, or sufficiently filled. Then the pressure at the outlet 10 comes close to the pressure at the inlet 8. Since the filling flow through the passage 6 reduces consequently, the dynamic pressure acting on the piston 18 and on the telescopic extension 30 diminishes. It diminishes until the resilient member 20 overcomes the mechanical force of the dynamic pressure. Finally, the resilient member 20 closes back the piston 18 and the telescopic extension 30 as illustrated in figure 4. It is noteworthy that the filling may occur without electric power, it may be hand-controlled by means of the handwheel 15. After filling, an operator may actuate the handwheel 15 in order to sink the pin 46 at its lower position as drawn in figure 1. By now, the valve becomes ready for a new discharge.
- [0072] Figures 7, 8 and 9 represent the valve 102 according to the second embodiment of the invention. These figures 7, 8 and 9 keep the reference signs of the first embodiment of the invention for identical or similar

elements, said reference signs being increase of 100 however. Specific reference signs are used for the specific elements of this embodiment.

- [0073] Figure 7 represent the valve 102 in a closed state, figure 8 represents the valve 102 in an intermediate open state, and figure 9 represents the valve 102 in the open state. Each of the figures 7, 8 and 9 may correspond to discharge or to filling. Figure 9 is a sectional view taken along the axis 9-9 illustrated in figure 8 in order to expose the pilot device 142.
- [0074] The second embodiment is similar to the first embodiment; it substantially differs in that the handwheel is removed from the upper cap 114. The pilot device 142 may replace the pin. It may maintain the pressure drop above the piston 118 by standing open. The position of the pilot device 142 has been turned of 90° with respect to the cap 114 central axis.
- [0075] The cap 114 comprises an upper surface 160, also designated as outer surface 160, which is substantially free. The upper surface 160 may be generally flat. Yet, the cap 114 optionally shows two embossments 162 useful for assembling the cap 114. The central portion of the cap 114 is closed. Then, the valve 102 is essentially piloted by the pilot valve 142.
- [0076] As appear in figure 9, the pilot device 142 may be situated on a border of the cap 114. Then, its exhaust 164 will be shorter.
- [0077] The pilot device 142 may be arranged on the top of an embossment 162. It may also be fixed on a flat portion of the cap as well. The pilot device 142 may be a pilot valve. It may comprise a plunger 166 actuated by a magnetic field. Said magnetic field may be produced by a magnetic coil (non illustrated) in order to pull away the plunger 166 from the vent 140. This upward move opens the vent 140 and triggers the opening move of the piston 118 and of the telescopic extension 130.
- [0078] The through hole 124 may be kept. Optionally, the through hole is suppressed, its place is clogged. Then, the piston is tight. The cone portion may be replaced by a flat plate, essentially continuous. The piston may be free of through hole.

1. Robinet (2; 102), notamment pour gaz pressurisé, comprenant:

- un corps (4) avec: une entrée (8), une sortie (10), et un passage (6) qui relie l'entrée (8) avec la sortie (10), et qui comprend un siège (16); et
- un piston coulissant (18; 118) avec deux faces opposées, qui est apte à coopérer avec le siège (16) afin de fermer le passage (6);

le robinet (2; 102) étant adapté de manière qu'une pression différentielle agissant sur des faces opposées du piston (18; 118) écarte le piston (18; 118) du siège (16) afin d'ouvrir le passage (6);

caractérisé en ce que

le piston (18; 118) est équipé d'une extension télescopique (30; 130) coulissant contre le passage (6) afin de guider le piston (18; 118) dans le passage (6) au moins entre la position ouverte et la position fermée.

2. Robinet (2; 102) selon la revendication 1, caractérisé en ce que le piston (18; 118) coulisse à l'intérieur de l'extension télescopique (30; 130), de préférence l'extension télescopique (30; 130) est essentiellement un tube autour du piston (18; 118).

3. Robinet (2; 102) selon l'une quelconque des revendications 1 et 2, caractérisé en ce que le piston (18; 118) comprend un élément d'étanchéité (34) à l'interface de glissement avec l'extension télescopique (30; 130), ledit élément d'étanchéité (34) étant disposé au niveau de la sortie (10) lorsque le piston (18; 118) est dans l'état fermé ; de préférence, la distance X entre l'élément d'étanchéité (34) et le siège (16) est plus petite que la hauteur de la sortie Y.

4. Robinet (2; 102) selon l'une quelconque des revendications 1 à 3, caractérisé en ce que le piston (18; 118) comprend un trou traversant (24; 124) en communication de fluide avec l'entrée (8), de préférence le robinet (2; 102) comprend une tige (46) fermant le trou traversant (24; 124) lorsque le piston (18; 118) est dans la position ouverte, de préférence la tige (46) est montée sur un volant (15).

5. Robinet (2; 102) selon l'une quelconque des revendications 1 à 4, caractérisé en ce que dans la position fermée, le piston (18; 118) est principalement ou essentiellement disposé au niveau de la sortie (10); de préférence disposé dans le prolongement de la surface interne de la sortie (10).

6. Robinet (2; 102) selon l'une quelconque des revendications 1 à 5, caractérisé en ce que le piston (18; 118) comprend une partie supérieure glissant contre la surface intérieure de l'extension télescopique (30; 130), ladite partie supérieure coulissant le long de la majorité de, ou sensiblement sur toute la longueur de l'extension télescopique (30; 130).

7. Robinet (2; 102) selon l'une quelconque des revendications 1 à 6, caractérisé en ce que le piston (18; 118) comprend une partie conique (22), de préférence avec une base creuse disposée en direction du siège (16).

8. Robinet (2; 102) selon l'une quelconque des revendications 1 à 7, caractérisé en ce que le diamètre intérieur de la sortie (10) est supérieur ou égal à la longueur du piston (18; 118), mesuré entre le siège (16) et la face supérieure du piston (18; 118), de préférence le diamètre du piston (18; 118) est d'au moins 50 mm, de préférence d'au moins 75 mm.

9. Robinet (2; 102) selon l'une quelconque des revendications 1 à 8, caractérisé en ce que le passage (6) comprend une chambre avec deux moitiés (26; 28), à savoir une première moitié (26) reliant l'entrée (8) à la sortie (10), et dans laquelle le piston (18; 118) se trouve en position fermée; et une seconde moitié (28) dans laquelle se trouve le piston (18; 118) lorsqu'il est en position ouverte.

10. Robinet (2; 102) selon l'une quelconque des revendications 1 à 9, caractérisé en ce que le corps (4) comprend une butée axiale (38) destinée à coopérer avec l'extension télescopique (30; 130) lorsque le piston (18; 118) est dans la position fermée, de préférence la butée axiale (38) est situé au niveau de la sortie (10).

11. Robinet (2; 102) selon l'une quelconque des revendications 1 à 10, caractérisé en ce qu'il comprend un élément élastique (20) poussant le piston (18; 118) vers la position fermée, de préférence le robinet (2; 102) est agencé de telle sorte que la pression à l'entrée (8) pousse l'extension télescopique (30; 130) vers le siège (16), notamment contre la butée axiale (38).

12. Robinet (2; 102) selon l'une quelconque des revendications 1 à 11, caractérisé en ce que l'extension télescopique (30; 130) comprend une partie fermant au moins partiellement la sortie (10) lorsque le piston (18; 118) est dans la position fermée.

13. Robinet (2; 102) selon l'une quelconque des revendications 1 à 12, caractérisé en ce qu'il comprend un évent (40; 140) en communication avec le passage (6) afin de créer une chute de pression dans le passage (6) de manière à ouvrir le piston (18; 118); de préférence l'évent (40; 140) comprend un dispositif de pilotage (42; 142).

14. Robinet (2; 102) selon l'une quelconque des revendications 1 à 13, caractérisé en ce que le passage (6) comprend une chambre de décharge (28) avec une extrémité supérieure, de préférence la chambre de décharge (28) est situé à l'opposé du siège (16) par rapport au piston (18; 118), de préférence le piston (18; 118) et/ou l'extension télescopique (30; 130) viennent en butée contre l'extrémité supérieure en configuration ouverte.

15. Robinet (102) selon l'une quelconque des revendications 1 à 14, caractérisé en ce qu'il comprend un couvercle supérieur (114) avec une surface supérieure sensiblement libre.

16. Système d'extinction d'incendie comprenant un stockage de fluide, notamment une bouteille de gaz, avec un fluide haute pression pour l'extinction d'incendie ; et un robinet (2; 102); caractérisé en ce que le robinet (2; 102) est conforme à l'une quelconque des revendications 1 à 15; de préférence le fluide pour l'extinction d'incendie est un gaz ou mélange de gaz.



FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8





FIG. 9





**Abstract****HIGH PRESSURE VALVE WITH TELESCOPIC PISTON**

The invention is directed to a valve (2) for pressurized gas or chemical agent. The valve (2) comprises: a body (4) with: an inlet (8), an outlet (10), and a passage (6) which connects the inlet (8) with the outlet (10) and which includes a seat (16). The valve (2) further comprises a sliding piston (18) able to engage with the seat (16) in order to close the passage (6) and a telescopic extension (30) sliding against the passage in order to guide the piston (18) in the passage (6) at least between the open position and the closed position. The pressure difference between opposite faces of the piston pulls away the piston (18) and the telescopic extension (30) from the seat (16) in order to open the passage, the passage (6) remaining closed under pressure equilibrium. The invention is also directed to a fire extinguishing system.

(figure 1)



**SEARCH REPORT**  
in accordance with Article 35.1 a)  
of the Luxembourg law on patents  
dated 20 July 1992

LO 1281  
LU 92958

| DOCUMENTS CONSIDERED TO BE RELEVANT                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                         |                   |                                         |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|-----------------------------------------|
| Category                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Citation of document with indication, where appropriate, of relevant passages                                                                                           | Relevant to claim | CLASSIFICATION OF THE APPLICATION (IPC) |
| X                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | GB 751 393 A (TSUNETARO OHTA)<br>27 June 1956 (1956-06-27)<br>* page 1, line 82 - page 3, line 28;<br>figures *                                                         | 1-16              | INV.<br>F16K15/18<br>F16K17/08          |
| X                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | DE 83 01 494 U1 (MANNESMANN REXROTH GMBH)<br>13 February 1986 (1986-02-13)<br>* page 1, paragraph 1 - page 6, paragraph 3;<br>figure 1 *                                | 1-9,11,<br>15,16  |                                         |
| A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | US 4 520 843 A (DEBRUNNER JR PAUL E [US])<br>4 June 1985 (1985-06-04)<br>* compare reference signs 24,32,50;<br>column 3, line 38 - column 5, line 27;<br>figures 1,2 * | 1-16              |                                         |
| A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | EP 1 120 590 A2 (LUXEMBOURG PATENT CO [LU])<br>1 August 2001 (2001-08-01)<br>* figures 2,3 *                                                                            | 1-16              |                                         |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                                                         |                   | TECHNICAL FIELDS SEARCHED (IPC)         |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                                                         |                   | F16K                                    |
| The present search report has been drawn up for all claims                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                                                                                                                                         |                   |                                         |
| Date of completion of the search                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                         | Examiner          |                                         |
| 19 September 2016                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                                                         | Hatzenbichler, C  |                                         |
| CATEGORY OF CITED DOCUMENTS                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                         |                   |                                         |
| X : particularly relevant if taken alone<br>Y : particularly relevant if combined with another document of the same category<br>A : technological background<br>O : non-written disclosure<br>P : intermediate document<br>T : theory or principle underlying the invention<br>E : earlier patent document, but published on, or after the filing date<br>D : document cited in the application<br>L : document cited for other reasons<br>& : member of the same patent family, corresponding document |                                                                                                                                                                         |                   |                                         |

**ANNEX TO THE SEARCH REPORT  
ON LUXEMBOURG PATENT APPLICATION NO.**

L0 1281  
LU 92958

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

19-09-2016

| Patent document<br>cited in search report |    | Publication<br>date | Patent family<br>member(s) | Publication<br>date |
|-------------------------------------------|----|---------------------|----------------------------|---------------------|
| GB 751393                                 | A  | 27-06-1956          | NONE                       |                     |
| -----                                     |    |                     |                            |                     |
| DE 8301494                                | U1 | 13-02-1986          | NONE                       |                     |
| -----                                     |    |                     |                            |                     |
| US 4520843                                | A  | 04-06-1985          | NONE                       |                     |
| -----                                     |    |                     |                            |                     |
| EP 1120590                                | A2 | 01-08-2001          | AT 249593 T                | 15-09-2003          |
|                                           |    |                     | DE 60100713 D1             | 16-10-2003          |
|                                           |    |                     | EP 1120590 A2              | 01-08-2001          |
|                                           |    |                     | JP 2001248798 A            | 14-09-2001          |
|                                           |    |                     | US 2001022351 A1           | 20-09-2001          |
| -----                                     |    |                     |                            |                     |



WRITTEN OPINION

|                                                                       |                                            |                                |                            |
|-----------------------------------------------------------------------|--------------------------------------------|--------------------------------|----------------------------|
| File No.<br>LO1281                                                    | Filing date (day/month/year)<br>25.01.2016 | Priority date (day/month/year) | Application No.<br>LU92958 |
| International Patent Classification (IPC)<br>INV. F16K15/18 F16K17/08 |                                            |                                |                            |
| Applicant<br>LUXEMBOURG PATENT COMPANY S.A.                           |                                            |                                |                            |

This report contains indications relating to the following items:

- ☒ Box No. I Basis of the opinion
- ☐ Box No. II Priority
- ☐ Box No. III Non-establishment of opinion with regard to novelty, inventive step and industrial applicability
- ☐ Box No. IV Lack of unity of invention
- ☒ Box No. V Reasoned statement with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement
- ☐ Box No. VI Certain documents cited
- ☐ Box No. VII Certain defects in the application
- ☒ Box No. VIII Certain observations on the application

|                                          |                              |
|------------------------------------------|------------------------------|
| Form LU237A (Cover Sheet) (January 2007) | Examiner<br>Hatzenbichler, C |
|------------------------------------------|------------------------------|

## WRITTEN OPINION

Application No.

LU92958

---

### Box No. I Basis of the opinion

---

1. This opinion has been established on the basis of the latest set of claims filed before the start of the search.
2. With regard to any **nucleotide and/or amino acid sequence** disclosed in the application and necessary to the claimed invention, this opinion has been established on the basis of:
  - a. type of material:
    - ☐ a sequence listing
    - ☐ table(s) related to the sequence listing
  - b. format of material:
    - ☐ on paper
    - ☐ in electronic form
  - c. time of filing/furnishing:
    - ☐ contained in the application as filed.
    - ☐ filed together with the application in electronic form.
    - ☐ furnished subsequently.
3. ☐ In addition, in the case that more than one version or copy of a sequence listing and/or table relating thereto has been filed or furnished, the required statements that the information in the subsequent or additional copies is identical to that in the application as filed or does not go beyond the application as filed, as appropriate, were furnished.
4. Additional comments:

---

### Box No. V Reasoned statement with regard to novelty, inventive step and industrial applicability; citations and explanations supporting such statement

---

#### 1. Statement

|                          |             |                        |
|--------------------------|-------------|------------------------|
| Novelty                  | Yes: Claims | 3, 8, 12, 16           |
|                          | No: Claims  | 1, 2, 4-7, 9-11, 13-15 |
| Inventive step           | Yes: Claims |                        |
|                          | No: Claims  | 1-16                   |
| Industrial applicability | Yes: Claims | 1-16                   |
|                          | No: Claims  |                        |

#### 2. Citations and explanations

**see separate sheet**

**WRITTEN OPINION**

Application No.  
LU92958

---

**Box No. VIII    Certain observations on the application**

---

see separate sheet

**Re Item V:**

**Independent claim 1:**

- 1 From document **GB-A-751 393 (D1)** is known a valve comprising (see especially page 2 and the figures):
- a body with an inlet **10**, an outlet **12** and a passage which connects the inlet with the outlet and which includes a seat **r**; and
  - a sliding piston **b** with two opposite faces, which is able to engage with the seat **r** in order to close the passage,
- wherein:
- the valve is adapted in such a way that a differential pressure on opposite faces of the piston pulls away the piston **b** from the seat **r** in order to open the passage; and
  - the piston **b** is equipped with a telescopic extension **o** sliding against the passage in order to guide the piston in the passage at least between the open position and the closed position (compare page 2, lines 12-16).
- 2 Consequently, the subject-matter defined in claim 1 lacks novelty.
- 3 Also the valve discloses in document **DE-U-83 01 494 (D2)** is completely readable on the subject-matter defined in claim 1, see thereto especially figure 1 and the corresponding description: body 2 with inlet 7, outlet 5 and seat 6; sliding piston 14; slidable telescopic extension 20

**Dependent claims 2-16:**

- 4 The features of dependent claims 2-16 are either already known or at least obvious from one or more of the documents involved in the procedure and/or relate merely to well-known options and do not appear to contain matter, which goes beyond the technical knowledge of the person skilled in the art or which would indicate the use of inventive ability.

Re Item VIII:

- 5      At least the following passages in the claims have to be objected for lack of clarity:
- Claim 1: 'the piston is equipped with a telescopic extension **sliding against (?)** the passage in order to guide the piston'
  - Claim 5: 'the piston is ... preferentially arranged within the extension **of the outlet inner surface (?)**'
  - Claim 11: preferably the valve is arranged in such a way that the pressure at the inlet at the inlet urges the extension **toward the seat (?), notably against the axial abutments (?)**
- 6      Additional remark: It is not quite understandable what exactly is the actual purpose of the telescopic extension as defined in the characterising portion respectively how this feature helps to overcome the problems of the prior art as stated in paragraphs [0002 and 0003] of the description of the application, viz. bulky design (due to increased valve height), costs and leakage.