



US010698434B2

(12) **United States Patent**
Weaver et al.

(10) **Patent No.:** **US 10,698,434 B2**

(45) **Date of Patent:** ***Jun. 30, 2020**

(54) **INTELLIGENT TEMPERATURE
MANAGEMENT BASED ON ENERGY
USAGE PROFILES AND OUTSIDE
WEATHER CONDITIONS**

(58) **Field of Classification Search**

CPC ... G05F 1/66; F24F 11/62; F24F 11/30; F24F
2110/12; F24F 11/52; F24F 11/46;
(Continued)

(71) Applicant: **Google LLC**, Mountain View, CA (US)

(56) **References Cited**

(72) Inventors: **Jason C. Weaver**, Austin, TX (US);
Bradley A. Kayton, Hollis, NH (US)

U.S. PATENT DOCUMENTS

3,991,357 A 11/1976 Kaminski
4,117,537 A 9/1978 Muench
(Continued)

(73) Assignee: **Google LLC**, Mountain View, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 424 days.

This patent is subject to a terminal dis-
claimer.

FOREIGN PATENT DOCUMENTS

CA 2202008 2/2000
EP 196069 12/1991
(Continued)

(21) Appl. No.: **15/351,217**

OTHER PUBLICATIONS

(22) Filed: **Nov. 14, 2016**

Applicant-Initiated Interview Summary dated Jul. 15, 2015, for U.S.
Appl. No. 14/473,906, 4 pages.

(65) **Prior Publication Data**

US 2017/0059195 A1 Mar. 2, 2017

(Continued)

Related U.S. Application Data

(63) Continuation of application No. 14/473,906, filed on
Aug. 29, 2014, now Pat. No. 9,600,011, which is a
(Continued)

Primary Examiner — Zhipeng Wang

(74) *Attorney, Agent, or Firm* — Kilpatrick Townsend &
Stockton LLP

(51) **Int. Cl.**
G05D 3/12 (2006.01)
G05D 5/00 (2006.01)


(Continued)

(57) **ABSTRACT**

Accessing an energy management policy for a plurality of
devices is described, wherein the devices are coupled with a
first structure. The energy usage of the devices is moni-
tored. An energy usage rule and energy usage is then
compared. The energy management policy and energy usage
is also compared. Based on the comparing, an instruction is
generated to modify an energy usage profile of said device
to correlate with the energy usage rule associated with the
devices and the energy management policy, thereby enabling
efficient energy management.

(52) **U.S. Cl.**
CPC **G05F 1/66** (2013.01); **F24F 11/30**
(2018.01); **F24F 11/62** (2018.01); **G05B 15/02**
(2013.01);
(Continued)

20 Claims, 6 Drawing Sheets



Related U.S. Application Data

continuation of application No. 13/327,459, filed on Dec. 15, 2011, now Pat. No. 9,500,385, which is a continuation of application No. 12/241,588, filed on Sep. 30, 2008, now Pat. No. 8,160,752.

(51) **Int. Cl.**

G05D 9/00 (2006.01)
G05D 11/00 (2006.01)
G05D 17/00 (2006.01)
G05F 1/66 (2006.01)
H02J 3/14 (2006.01)
H04L 12/12 (2006.01)
H04L 12/28 (2006.01)
H04Q 9/00 (2006.01)
F24F 11/30 (2018.01)
F24F 11/62 (2018.01)
G06Q 50/06 (2012.01)
H04L 29/08 (2006.01)
H04W 4/12 (2009.01)
G05D 23/19 (2006.01)
H04L 12/24 (2006.01)
H04W 74/00 (2009.01)
G06Q 10/06 (2012.01)
G05B 15/02 (2006.01)
H02J 3/00 (2006.01)
G09B 19/00 (2006.01)
G06Q 30/02 (2012.01)
G09B 5/02 (2006.01)
F24F 110/10 (2018.01)
F24F 110/12 (2018.01)
F24F 110/20 (2018.01)
F24F 140/60 (2018.01)
F24F 130/20 (2018.01)
F24F 130/00 (2018.01)
F24F 130/10 (2018.01)
F24F 11/64 (2018.01)
F24F 11/56 (2018.01)
F24F 11/46 (2018.01)
F24F 11/52 (2018.01)

(52) **U.S. Cl.**

CPC **G05D 23/1917** (2013.01); **G05D 23/1927** (2013.01); **G06Q 10/06314** (2013.01); **G06Q 30/0257** (2013.01); **G06Q 50/06** (2013.01); **G09B 5/02** (2013.01); **G09B 19/00** (2013.01); **H02J 3/00** (2013.01); **H02J 3/14** (2013.01); **H04L 12/12** (2013.01); **H04L 12/2816** (2013.01); **H04L 12/2827** (2013.01); **H04L 12/2829** (2013.01); **H04L 41/22** (2013.01); **H04L 67/10** (2013.01); **H04Q 9/00** (2013.01); **H04W 4/12** (2013.01); **H04W 74/00** (2013.01); **F24F 11/46** (2018.01); **F24F 11/52** (2018.01); **F24F 11/56** (2018.01); **F24F 11/64** (2018.01); **F24F 2110/10** (2018.01); **F24F 2110/12** (2018.01); **F24F 2110/20** (2018.01); **F24F 2130/00** (2018.01); **F24F 2130/10** (2018.01); **F24F 2130/20** (2018.01); **F24F 2140/60** (2018.01); **G05B 2219/34306** (2013.01); **H02J 2310/14** (2020.01); **H04L 67/12** (2013.01); **H04Q 2209/30** (2013.01); **H04Q 2209/43** (2013.01); **H04Q 2209/60** (2013.01); **Y02D 70/325** (2013.01); **Y02D 70/00** (2018.01); **Y02D 70/142** (2018.01);

Y02D 70/162 (2018.01); **Y02P 90/82** (2015.11); **Y04S 20/228** (2013.01); **Y04S 50/14** (2013.01)

(58) **Field of Classification Search**

CPC **F24F 11/56**; **F24F 11/64**; **F24F 2130/10**; **F24F 2130/00**; **F24F 2110/10**; **F24F 2130/20**; **F24F 2110/20**; **F24F 2140/60**; **G09B 19/00**; **G09B 5/02**; **H02J 3/00**; **H02J 3/14**; **H02J 2003/143**; **G05B 2219/34306**; **G05B 15/02**; **G05B 2219/34366**; **G06Q 30/0257**; **G06Q 10/06314**; **G06Q 50/06**; **H04L 41/22**; **H04L 12/2827**; **H04L 12/2829**; **H04L 12/12**; **H04L 12/2816**; **H04L 67/12**; **H04L 67/10**; **H04W 4/12**; **H04W 74/00**; **G05D 23/1917**; **G05D 23/1927**; **H04Q 9/00**; **H04Q 2209/43**; **H04Q 2209/60**; **H04Q 2209/30**; **Y02P 90/82**; **Y02D 70/00**; **Y02D 70/142**; **Y02D 70/162**; **Y04S 50/14**; **Y04S 20/228**; **Y02B 70/325**

USPC **700/278**, **295**
 See application file for complete search history.

(56)

References Cited

U.S. PATENT DOCUMENTS

4,183,290	A	1/1980	Kucharczyk
4,223,831	A	9/1980	Szarka
4,261,037	A	4/1981	Hicks
4,324,987	A	4/1982	Sullivan et al.
4,335,847	A	6/1982	Levine
4,408,711	A	10/1983	Levine
4,567,557	A	1/1986	Bums
4,615,380	A	10/1986	Beckey
4,644,320	A	2/1987	Carr et al.
4,674,027	A	6/1987	Beckey
4,682,473	A	7/1987	Rogers, III
4,685,614	A	8/1987	Levine
4,751,961	A	6/1988	Levine et al.
4,897,798	A	1/1990	Cler
5,086,385	A	2/1992	Launey et al.
5,088,645	A	2/1992	Bell
5,211,332	A	5/1993	Adams
5,240,178	A	8/1993	Dewolf et al.
5,244,146	A	9/1993	Jefferson et al.
5,289,362	A	2/1994	Liebl et al.
5,386,491	A	1/1995	Mewissen et al.
5,395,042	A	3/1995	Riley et al.
5,436,510	A	7/1995	Gilbert
5,476,221	A	12/1995	Seymour
5,481,140	A	1/1996	Maruyama et al.
5,499,196	A	3/1996	Pacheco
5,544,036	A	8/1996	Brown et al.
5,555,927	A	9/1996	Shah
5,611,484	A	3/1997	Uhrich
5,684,710	A	11/1997	Ehlers et al.
5,729,474	A *	3/1998	Hildebrand G05D 23/1917 700/276
5,778,683	A	7/1998	Drees et al.
5,808,294	A	9/1998	Neumann
5,833,134	A	11/1998	Ho et al.
5,875,430	A	2/1999	Koether
5,902,183	A	5/1999	D'Souza
5,909,378	A	6/1999	De Milleville
5,918,474	A	7/1999	Khanpara et al.
5,924,072	A	7/1999	Havens
5,924,486	A	7/1999	Ehlers et al.
5,962,989	A	10/1999	Baker
5,971,597	A	10/1999	Baldwin et al.
5,977,964	A	11/1999	Williams et al.
6,062,482	A	5/2000	Gauthier et al.
6,066,843	A	5/2000	Scheremeta
6,072,784	A	6/2000	Agrawal et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,095,427 A	8/2000	Hoiium et al.	8,042,048 B2	10/2011	Wilson et al.
6,098,893 A	8/2000	Berglund et al.	8,078,330 B2	12/2011	Brickfield
6,108,685 A	8/2000	Kutzik et al.	8,090,477 B1	1/2012	Steinberg
6,121,593 A	9/2000	Mansbery et al.	8,091,375 B2	1/2012	Crawford
6,122,603 A	9/2000	Budike, Jr.	8,095,233 B1	1/2012	Shankar et al.
6,134,511 A	10/2000	Subbarao	8,131,497 B2	3/2012	Steinberg et al.
6,178,362 B1	1/2001	Woolard et al.	8,160,752 B2	4/2012	Weaver et al.
6,216,956 B1	4/2001	Ehlers et al.	8,174,381 B2	5/2012	Imes et al.
6,349,883 B1	2/2002	Simmons et al.	8,180,492 B2	5/2012	Steinberg
6,356,204 B1	3/2002	Guindi et al.	8,219,249 B2	7/2012	Harrod et al.
6,370,894 B1	4/2002	Thompson et al.	8,423,322 B2	4/2013	Steinberg et al.
6,385,510 B1	5/2002	Hoog et al.	8,450,995 B2	5/2013	Wagner
6,396,531 B1	5/2002	Gerszberg et al.	8,457,796 B2	6/2013	Thind
6,415,205 B1	7/2002	Myron et al.	9,081,405 B2	7/2015	Weaver et al.
6,448,896 B1	9/2002	Bankus et al.	9,322,565 B2	4/2016	Weaver et al.
6,478,233 B1	11/2002	Shah	9,500,385 B2	11/2016	Weaver et al.
6,480,803 B1	11/2002	Pierret	9,507,362 B2	11/2016	Weaver et al.
6,528,957 B1	3/2003	Luchaco	9,507,363 B2	11/2016	Weaver et al.
6,591,620 B2	7/2003	Kikuchi et al.	9,523,993 B2	12/2016	Weaver et al.
6,645,066 B2	11/2003	Gutta et al.	9,600,011 B2	3/2017	Weaver et al.
6,654,689 B1	11/2003	Kelley et al.	10,048,712 B2	8/2018	Weaver et al.
6,704,742 B1	3/2004	Huth et al.	10,108,217 B2	10/2018	Weaver et al.
6,769,482 B2	8/2004	Wagner et al.	2001/0013123 A1	8/2001	Freeman et al.
6,772,096 B2	8/2004	Murakami et al.	2001/0025209 A1	9/2001	Fukui et al.
6,782,294 B2	8/2004	Reich et al.	2001/0034569 A1	10/2001	Yamamoto et al.
6,785,592 B1	8/2004	Smith et al.	2002/0013689 A1	1/2002	Hunton
6,789,739 B2	9/2004	Rosen	2002/0024332 A1	2/2002	Gardner
6,868,293 B1	3/2005	Schurr et al.	2002/0059617 A1	5/2002	Terakado et al.
6,874,691 B1	4/2005	Hildebrand et al.	2002/0124992 A1	9/2002	Rainer et al.
6,983,210 B2	1/2006	Matsubayashi et al.	2002/0178047 A1	11/2002	Or et al.
6,990,821 B2	1/2006	Singh et al.	2002/0198629 A1	12/2002	Ellis
7,024,336 B2	4/2006	Salsbury et al.	2003/0009401 A1	1/2003	Ellis
7,043,341 B2	5/2006	Gaullupe	2003/0036810 A1	2/2003	Petite
7,055,759 B2	6/2006	Wacker et al.	2003/0036822 A1*	2/2003	Davis H02J 3/14 700/295
7,062,361 B1	6/2006	Lane	2003/0050738 A1	3/2003	Masticola et al.
7,092,794 B1	8/2006	Hill et al.	2003/0066897 A1	4/2003	Carner et al.
7,130,719 B2	10/2006	Ehlers et al.	2003/0070438 A1	4/2003	Kikuchi et al.
7,149,605 B2	12/2006	Chassin et al.	2003/0150927 A1	8/2003	Rosen
7,149,727 B1	12/2006	Nicholls et al.	2003/0167150 A1	9/2003	Shimura et al.
7,149,729 B2	12/2006	Kaasten et al.	2003/0171851 A1	9/2003	Brickfield et al.
7,185,504 B2	3/2007	Kasai et al.	2003/0187549 A1	10/2003	Bohrer et al.
7,188,482 B2	3/2007	Sadegh et al.	2003/0192328 A1	10/2003	Kikuchi et al.
7,197,365 B2	3/2007	Hori et al.	2003/0193405 A1	10/2003	Hunt et al.
7,218,998 B1	5/2007	Neale	2003/0216837 A1	11/2003	Reich et al.
7,225,171 B2	5/2007	Kikuchi et al.	2003/0216971 A1	11/2003	Sick et al.
7,232,075 B1	6/2007	Rosen	2003/0233172 A1	12/2003	Granqvist et al.
7,243,044 B2	7/2007	McCalla	2003/0233201 A1	12/2003	Horst et al.
7,274,975 B2	9/2007	Miller	2004/0002792 A1	1/2004	Hoffknecht
7,317,404 B2	1/2008	Cumeralto et al.	2004/0010561 A1	1/2004	Kim et al.
7,353,121 B2	4/2008	Baraty	2004/0034484 A1	2/2004	Solomita et al.
7,364,093 B2	4/2008	Garozzo	2004/0088082 A1	5/2004	Ahmed
7,379,791 B2	5/2008	Tamarkin et al.	2004/0095237 A1	5/2004	Chen et al.
RE40,437 E	7/2008	Rosen	2004/0117330 A1	6/2004	Ehlers et al.
7,434,742 B2	10/2008	Mueller et al.	2004/0133314 A1*	7/2004	Ehlers G06Q 10/10 700/276
7,451,937 B2	11/2008	Flood et al.	2004/0192329 A1	9/2004	Barbosa et al.
7,469,550 B2	12/2008	Chapman, Jr. et al.	2004/0225649 A1	11/2004	Yeo et al.
7,496,430 B2	2/2009	Mak	2004/0230344 A1	11/2004	Gaullupe et al.
7,565,227 B2	7/2009	Richard et al.	2004/0238653 A1	12/2004	Alles
7,636,666 B2	12/2009	van Putten et al.	2004/0249479 A1	12/2004	Shorrock
7,644,869 B2	1/2010	Hoglund et al.	2004/0260490 A1	12/2004	Matsubayashi et al.
7,702,424 B2	4/2010	Cannon et al.	2005/0038571 A1	2/2005	Brickfield et al.
7,706,928 B1	4/2010	Howell et al.	2005/0040943 A1	2/2005	Winick
7,738,972 B2	6/2010	Pouchak	2005/0043862 A1	2/2005	Brickfield et al.
7,747,399 B2	6/2010	Smith et al.	2005/0043907 A1*	2/2005	Eckel G01K 1/045 702/62
7,784,704 B2	8/2010	Harter	2005/0049789 A1	3/2005	Kelly et al.
7,802,618 B2	9/2010	Simon et al.	2005/0090915 A1	4/2005	Geirwitz
7,839,275 B2	11/2010	Spalink et al.	2005/0096797 A1	5/2005	Matsubara et al.
7,848,900 B2	12/2010	Steinberg et al.	2005/0103874 A1	5/2005	Erdman, Jr.
7,849,698 B2	12/2010	Harrod et al.	2005/0119793 A1	6/2005	Amundson et al.
7,854,389 B2	12/2010	Ahmed	2005/0120012 A1	6/2005	Poth et al.
7,894,943 B2	2/2011	Sloup et al.	2005/0128067 A1	6/2005	Zakrewski
8,010,237 B2	8/2011	Cheung et al.	2005/0150968 A1	7/2005	Shearer
8,019,567 B2	9/2011	Steinberg et al.	2005/0154495 A1	7/2005	Shah
8,021,618 B1	9/2011	Cooper	2005/0171645 A1	8/2005	Oswald et al.
8,037,022 B2	10/2011	Rahman et al.	2005/0189429 A1	9/2005	Breeden
			2005/0192727 A1	9/2005	Shostak et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0192915	A1	9/2005	Ahmed et al.
2005/0194455	A1	9/2005	Alles
2005/0194456	A1	9/2005	Tessier et al.
2005/0234596	A1	10/2005	Rietschel
2005/0234600	A1	10/2005	Boucher et al.
2005/0245839	A1	11/2005	Stivoric et al.
2005/0270151	A1	12/2005	Winick
2005/0280421	A1	12/2005	Yomoda et al.
2006/0030954	A1	2/2006	Bergman et al.
2006/0065750	A1	3/2006	Fairless
2006/0080246	A1	4/2006	Wyckoff
2006/0106741	A1	5/2006	Janarthanan
2006/0111816	A1	5/2006	Spalink et al.
2006/0142900	A1	6/2006	Rothman et al.
2006/0149395	A1	7/2006	Archacki et al.
2006/0149414	A1	7/2006	Archacki et al.
2006/0167591	A1	7/2006	McNally
2006/0186214	A1	8/2006	Simon et al.
2006/0196953	A1	9/2006	Simon et al.
2006/0206220	A1	9/2006	Amundson
2006/0259199	A1	11/2006	Gjerde et al.
2006/0259332	A1	11/2006	Brown
2006/0267574	A1	11/2006	Howard
2006/0276938	A1	12/2006	Miller
2007/0043477	A1	2/2007	Ehlers et al.
2007/0045431	A1	3/2007	Chapman, Jr. et al.
2007/0067068	A1	3/2007	Havlena et al.
2007/0114295	A1	5/2007	Jenkins
2007/0115902	A1	5/2007	Shamoon et al.
2007/0118831	A1	5/2007	Kondo
2007/0138307	A1*	6/2007	Khoo F24F 11/30 236/1 C
2007/0155349	A1	7/2007	Nelson et al.
2007/0155379	A1	7/2007	Shamoon et al.
2007/0199336	A1	8/2007	Tantot
2007/0203860	A1	8/2007	Golden et al.
2007/0205297	A1	9/2007	Finkam et al.
2007/0214368	A1	9/2007	Ota et al.
2007/0227721	A1	10/2007	Springer et al.
2007/0239317	A1	10/2007	Bogolea et al.
2007/0250386	A1	10/2007	Wyckoff
2007/0276547	A1	11/2007	Miller
2008/0004725	A1	1/2008	Wacker et al.
2008/0011864	A1	1/2008	Tessier et al.
2008/0015740	A1	1/2008	Osann
2008/0015742	A1	1/2008	Kulyk et al.
2008/0147205	A1	6/2008	Ollis et al.
2008/0167756	A1	7/2008	Golden et al.
2008/0177423	A1	7/2008	Brickfield et al.
2008/0183335	A1	7/2008	Poth et al.
2008/0191045	A1	8/2008	Harter
2008/0221737	A1	9/2008	Josephson et al.
2008/0229226	A1	9/2008	Rowbottom et al.
2008/0273754	A1	11/2008	Hick et al.
2008/0277486	A1	11/2008	Seem et al.
2008/0281473	A1	11/2008	Pitt
2008/0282182	A1	11/2008	Oosaka
2008/0313021	A1	12/2008	Nagafuchi et al.
2008/0317292	A1	12/2008	Baker et al.
2009/0006873	A1	1/2009	Bellofatto et al.
2009/0018706	A1	1/2009	Wittner
2009/0021993	A1	1/2009	Nakazawa
2009/0043548	A1	2/2009	Beekhuis
2009/0045804	A1	2/2009	Durling et al.
2009/0050703	A1	2/2009	Lifson et al.
2009/0062970	A1	3/2009	Forbes et al.
2009/0076748	A1	3/2009	Robertson et al.
2009/0083167	A1*	3/2009	Subbloie G06Q 30/04 705/34
2009/0099699	A1	4/2009	Steinberg et al.
2009/0171862	A1	7/2009	Harrod et al.
2009/0177294	A1	7/2009	Baraty
2009/0229288	A1	9/2009	Alston et al.
2009/0240381	A1	9/2009	Lane
2009/0254225	A1	10/2009	Boucher et al.

2009/0259713	A1	10/2009	Blumrich et al.
2009/0297901	A1	12/2009	Kilian et al.
2009/0307573	A1	12/2009	Lavelle et al.
2009/0309541	A1	12/2009	Walrath
2009/0327354	A1	12/2009	Resnick et al.
2010/0019051	A1	1/2010	Rosen
2010/0025483	A1	2/2010	Hoeynck et al.
2010/0063832	A1	3/2010	Brown
2010/0070084	A1	3/2010	Steinberg et al.
2010/0070086	A1	3/2010	Harrod et al.
2010/0070234	A1*	3/2010	Steinberg G01K 13/00 702/130
2010/0082174	A1	4/2010	Weaver
2010/0084482	A1	4/2010	Kennedy et al.
2010/0167783	A1	7/2010	Alameh et al.
2010/0168924	A1	7/2010	Tessier et al.
2010/0179704	A1	7/2010	Ozog
2010/0198713	A1	8/2010	Forbes, Jr. et al.
2010/0211224	A1	8/2010	Keeling et al.
2010/0222935	A1	9/2010	Forbes et al.
2010/0228601	A1	9/2010	Vaswani et al.
2010/0235004	A1	9/2010	Thind
2010/0262298	A1	10/2010	Johnson et al.
2010/0262299	A1	10/2010	Cheung et al.
2010/0280667	A1	11/2010	Steinberg
2010/0289643	A1	11/2010	Trundle et al.
2010/0308119	A1	12/2010	Steinberg et al.
2010/0318227	A1	12/2010	Steinberg et al.
2010/0324962	A1	12/2010	Nesler et al.
2011/0035060	A1	2/2011	Oswald
2011/0046792	A1	2/2011	Imes et al.
2011/0046805	A1	2/2011	Bedros et al.
2011/0046806	A1	2/2011	Nagel et al.
2011/0077758	A1	3/2011	Tran et al.
2011/0077896	A1	3/2011	Steinberg et al.
2011/0130887	A1	6/2011	Ehlers, Sr.
2011/0151837	A1	6/2011	Winbush, III
2011/0160913	A1	6/2011	Parker et al.
2011/0161251	A1	6/2011	Carey et al.
2011/0172841	A1	7/2011	Forbes, Jr.
2011/0185895	A1	8/2011	Freen
2011/0307103	A1	12/2011	Cheung et al.
2011/0307112	A1	12/2011	Barrilleaux
2012/0017611	A1	1/2012	Coffel et al.
2012/0065935	A1	3/2012	Steinberg et al.
2012/0085831	A1	4/2012	Kopp
2012/0089269	A1	4/2012	Weaver et al.
2012/0101637	A1	4/2012	Imes et al.
2012/0158350	A1	6/2012	Steinberg et al.
2012/0221151	A1	8/2012	Steinberg
2012/0252430	A1	10/2012	Imes et al.
2013/0151012	A1	6/2013	Shetty et al.
2015/0295408	A1	10/2015	Weaver et al.
2015/0301549	A1	10/2015	Weaver et al.

FOREIGN PATENT DOCUMENTS

JP	59106311	6/1984
JP	01252850	10/1989
JP	2008092681	4/2008
WO	200249310	6/2002
WO	2007-117245	A1 10/2007

OTHER PUBLICATIONS

Applicant-Initiated Interview Summary dated Sep. 9, 2015, for U.S. Appl. No. 14/473,906, 3 pages.

Applicant-Initiated Summary dated Apr. 18, 2016, for U.S. Appl. No. 14/473,906, 4 pages.

Final Office Action dated Jul. 8, 2015, for U.S. Appl. No. 13/327,459, 25 pages.

Final Office Action dated Mar. 30, 2011, for U.S. Appl. No. 12/241,588, 16 pages.

Final Office Action dated May 1, 2015, for U.S. Appl. No. 14/473,906, 31 pages.

Final Office Action dated Sep. 29, 2015, for U.S. Appl. No. 14/473,925, 40 pages.

(56)

References Cited**OTHER PUBLICATIONS**

First Action Interview Pilot Program Pre-Interview Communication dated Jan. 2, 2015, for U.S. Appl. No. 14/473,925, 7 pages.

Marceau, et al., titled, "Nonintrusive Load Disaggregation Computer Program to Estimate Energy Consumption of Major End Uses in Residential Buildings", IEEE, 1999, pp. 1389-1403.

Non-Final Office Action dated Apr. 21, 2015, for U.S. Appl. No. 14/473,925, 40 pages.

Non-Final Office Action dated Dec. 21, 2015, for U.S. Appl. No. 14/473,906, 34 pages.

Non-Final Office Action dated Dec. 29, 2014, for U.S. Appl. No. 14/473,906, 29 pages.

Non-Final Office Action dated Jan. 15, 2016, for U.S. Appl. No. 14/789,716, 8 pages.

Non-Final Office Action dated Jan. 9, 2015, for U.S. Appl. No. 13/327,459, 26 pages.

Non-Final Office Action dated Mar. 1, 2016, for U.S. Appl. No. 13/327,459, 21 pages.

Non-Final Office Action dated Mar. 16, 2016, for U.S. Appl. No. 14/473,925, 39 pages.

Non-Final Office Action dated Oct. 13, 2010, for U.S. Appl. No. 12/241,588, 12 pages.

Notice of Allowance and Fee(s) due dated Sep. 16, 2011, for U.S. Appl. No. 12/241,588, 9 pages.

Notice of Publication dated Apr. 12, 2012, for U.S. Appl. No. 13/327,459.

Notice of Publication dated Dec. 18, 2014, for U.S. Appl. No. 14/473,893.

Notice of Publication dated Dec. 18, 2014, for U.S. Appl. No. 14/473,906.

Notice of Publication dated Dec. 18, 2014, for U.S. Appl. No. 14/473,925.

Notice of Publication dated Oct. 22, 2015, for U.S. Appl. No. 14/789,716.

Preinterview First Office Action dated Dec. 24, 2014, for U.S. Appl. No. 14/473,893, 5 pages.

Preinterview First Office Action dated Dec. 3, 2014, for U.S. Appl. No. 14/473,906, 31 pages.

U.S. Appl. No. 14/752,453, filed Jun. 26, 2015, 31 pages.

First Action Interview Office Action Summary dated Feb. 4, 2015, for U.S. Appl. No. 14/473,893, 5 pages.

Notice of Allowance and Fee(s) due dated Apr. 24, 2015, for U.S. Appl. No. 14/473,893, 11 pages.

Notice of Publication dated Dec. 18, 2014, for U.S. Appl. No. 14/475,274.

Notice of Publication dated Mar. 5, 2015, for U.S. Appl. No. 14/542,252.

Notice of Publication dated Dec. 18, 2014, for U.S. Appl. No. 14/475,029.

Non-Final Office Action dated Dec. 24, 2014, for U.S. Appl. No. 14/475,029, 12 pages.

First Action Interview Pilot Program Pre-Interview Communication dated Mar. 24, 2015, for U.S. Appl. No. 14/475,029, 4 pages.

Non-Final Office Action dated May 18, 2015, for U.S. Appl. No. 14/475,029, 10 pages.

Final Office Action dated Sep. 1, 2015, for U.S. Appl. No. 14/475,029, 10 pages.

Examiner-Initiated Interview Summary dated Dec. 18, 2015, for U.S. Appl. No. 14/475,029, 2 pages.

Notice of Publication dated Feb. 26, 2015, for U.S. Appl. No. 14/528,995.

Aprilaire Electronic Thermostats Model 8355 User's Manual, Research Products Corporation, Revised Dec. 2000, 16 pages.

Braeburn 5300 Installer Guide, Braeburn Systems, LLC, 2009, 10 pages.

Braeburn Model 5200, Braeburn Systems, LLC, 2011, 11 pages.

Ecobee Smart Si Thermostat Installation Manual, Ecobee, 2012, 40 pages.

Ecobee Smart Si Thermostat User Manual, Ecobee, 2012, 44 pages.

Ecobee Smart Thermostat Installation Manual, 2011, 20 pages.

Ecobee Smart Thermostat User Manual, 2010, 20 pages.

Electric Heat Lock Out on Heat Pumps, Washington State University Extension Energy Program, Apr. 2010, pp. 1-3.

Honeywell Installation Guide FocusPRO TH6000 Series, Honeywell International, Inc., 2012, 24 pages.

Honeywell Operating Manual FocusPRO TH6000 Series, Honeywell International, Inc., 2011, 80 pages.

Honeywell Prestige IAQ Product Data 2, Honeywell International, Inc., 2012, 126 pages.

Honeywell Prestige THX9321 and TXH9421 Product Data, Honeywell International, Inc., 68/0311, 2012, 126 pages.

Honeywell Prestige THX9321-9421 Operating Manual, Honeywell International, Inc., 2011, 120 pages.

Hunter Internet Thermostat Installation Guide, Hunter Fan Co., Aug. 14, 2012, 8 pages.

Introducing the New Smart Si Thermostat, Datasheet [online]. Ecobee, [retrieved on Feb. 25, 2013]. Retrieved from the Internet: <URL: <https://www.ecobee.com/solutions/home/smart-si/>>, 4 pages.

Lennox ComfortSense 5000 Owners Guide, Lennox Industries, Inc., Feb. 2008, 32 pages.

Lennox ComfortSense 7000 Owners Guide, Lennox Industries, Inc., May 2009, 15 pages.

Lennox iComfort Manual, Lennox Industries, Inc., Dec. 2010, 20 pages.

Lux PSPU7323T Manual, LUX Products Corporation, 2009, 48 pages.

NetX RP32-WIFI Network Thermostat Consumer Brochures, Network Thermostat, 2011, 2 pages.

NetX RP32-WIFI Network Thermostat Specification Sheet, Network Thermostat, 2012, 2 pages.

RobertShaw Product Manual 9620, Maple Chase Company, 2001, 14 pages.

RobertShaw Product Manual 9825i2, Maple Chase Company, Jul. 17, 2006, 36 pages.

SYSTXCCUIZ01-V Infinity Control Installation Instructions, Carrier Corp, May 31, 2012, 20 pages.

T8611G Chronotherm IV Deluxe Programmable Heat Pump Thermostat Product Data, Honeywell International Inc., 1997, 24 pages.

TB-PAC, TB-PHP, Base Series Programmable Thermostats, Carrier Corp, May 14, 2012, 8 pages.

The Perfect Climate Comfort Center PC8900A W8900A-C Product Data Sheet, Honeywell International Inc., Revised Apr. 2001, 44 pages.

TP-PAC, TP-PHP, TP-NAC, TP-NHP Performance Series AC/HP Thermostat Installation Instructions, Carrier Corp, 2007, Edition Date: Sep. 2007, 56 pages.

Trane Communicating Thermostats for Fan Coil, Trane, May 2011, 32 pages.

Trane Communicating Thermostats for Heat Pump Control, Trane, May 2011, 32 pages.

Trane Install XL600 Installation Manual, Trane, Mar. 2006, 16 pages.

Trane XL950 Installation Guide, Trane, Mar. 2011, 20 pages.

Venstar T2900 Manual, Venstar, Inc., 2008, 113 pages.

Venstar T5800 Manual, Venstar, Inc., 7, 2011, 63 pages.

Vision PRO TH8000 Series Installation Guide, Honeywell International, Inc., 2012, 12 pages.

Vision PRO TH8000 Series Operating Manual, Honeywell International, Inc., 2011, 96 pages.

VisionPRO Wi-Fi Programmable Thermostat, Honeywell International, Inc., Operating Manual, Aug. 2012, 48 pages.

White Rodgers (Emerson) Model 1F81-261 Installation and Operating Instructions, White Rodgers, 2010, 8 pages.

White Rodgers (Emerson) Model 1F98EZ-1621 Homeowner's User Guide, White Rodgers, 2012, 28 pages.

Akhlaghinia et al., "Occupancy Monitoring in Intelligent Environment through Integrated Wireless Localizing Agents", IEEE, 2009, 7 pages.

Akhlaghinia et al., "Occupant Behaviour Prediction in Ambient Intelligence Computing Environment", Journal of Uncertain Systems, vol. 2, No. 2, 2008, pp. 85-100.

(56)

References Cited**OTHER PUBLICATIONS**

Allen et al., "Real-Time Earthquake Detection and Hazard Assessment by ElarmS Across California", *Geophysical Research Letters*, vol. 36, L00B08, Mar. 2009, pp. 1-6.

Chatzigiannakis et al., "Priority Based Adaptive Coordination of Wireless Sensors and Actors", [online] Q2SWinet '06, Oct. 2, 2006 [Retrieved on Mar. 12, 2012]. Retrieved from the Internet: <URL: <http://dl.acm.org/citation.cfm?id=1163681>>.

Deleeuw, "Ecobee WiFi Enabled Smart Thermostat Part 2: The Features Review", Retrieved from <URL: <http://www.homenetworkenabled.com/content.php?136-ecobee-WiFi-enabled-Smart-Thermostat-Part-2-The-Features-review>>, Dec. 2, 2011, 5 pages.

Gao et al., "The Self-Programming Thermostat: Optimizing Setback Schedules Based on Home Occupancy Patterns", In *Proceedings of the First ACM Workshop on Embedded Sensing Systems for Energy-Efficiency in Buildings*, Nov. 3, 2009, 6 pages.

Loisos et al., "Buildings End-Use Energy Efficiency: Alternatives to Compressor Cooling", *California Energy Commission, Public Interest Energy Research*, Jan. 2000, 80 pages.

Lu et al., "The Smart Thermostat: Using Occupancy Sensors to Save Energy in Homes", In *Proceedings of the 8th ACM Conference on Embedded Networked Sensor Systems*, Nov. 3-5, 2010, pp. 211-224.

Mozer, "The Neural Network House: An Environmental that Adapts to its Inhabitants", *AAAI Technical Report SS-98-02*, 1998, pp. 110-114.

Ros et al., "Multi-Sensor Human Tracking with the Bayesian Occupancy Filter", *IEEE*, 2009, 8 pages.

Wong et al., "Maximum Likelihood Estimation of ARMA Model with Error Processes for Replicated Observations", *National University of Singapore, Department of Economics, Working Paper No. 0217*, 2002, 19 pages.

Lien et al., "Remote-Controllable Power Outlet System for Home Power Management", *IEEE*, Nov. 2007, pp. 1634-1641.

Final office action dated Sep. 19, 2018 in related U.S. Appl. No. 15/351,202, all pages.

U.S. Appl. No. 14/528,995, filed Oct. 30, 2014, Final Office Action dated May 22, 2017, all pages.

Daryanian et al., "An Experiment in Real Time Pricing for Control of Electric Thermal Storage Systems", *Transactions of Power Systems*, vol. 6, No. 4, Nov. 1991, pp. 1356-1365.

U.S. Appl. No. 14/475,274, filed Sep. 2, 2014, First Action Interview Pilot Program Pre-Interview Communication dated Mar. 1, 2017, all pages.

U.S. Appl. No. 14/475,274, filed Sep. 2, 2014, Non-Final Office Action dated Apr. 19, 2017, all pages.

U.S. Appl. No. 14/542,252, filed Nov. 14, 2014, Final Office Action dated Jul. 14, 2017, all pages.

Notice of Publication dated Oct. 15, 2015 in U.S. Appl. No. 14/752,453, 1 page.

Non-Final Office action dated Jan. 15, 2016 in U.S. Appl. No. 14/752,453, 1 page.

Notice of Allowance dated Jul. 25, 2016 in U.S. Appl. No. 14/752,453, 1 page.

First Action Interview, Pre-interview communication dated Dec. 24, 2014 in U.S. Appl. No. 14/473,893, all pages.

Notice of Publication dated Dec. 18, 2014 in U.S. Appl. No. 14/475,274, 1 page.

Final Office action dated Nov. 28, 2017 in U.S. Appl. No. 14/475,274, 1 page.

Nesler-C., "Adaptive Control of Thermal Process in Buildings," *IEEE*, 1986, pp. 9-13.

Final Office action dated Jul. 15, 2016 in U.S. Appl. No. 14/473,906, all pages.

Advisory action dated Sep. 4, 2015 in U.S. Appl. No. 14/473,906, all pages.

Notice of Allowance and Fee(s) Due dated Jul. 25, 2016 in U.S. Appl. No. 14/789,716, all pages.

Notice of Publication dated Oct. 22, 2015 in U.S. Appl. No. 14/789,716, all pages.

Notice of Allowance and Fee(s) Due dated Aug. 4, 2016 in U.S. Appl. No. 14/473,925, all pages.

Non-Final Office action dated Jan. 12, 2017 in U.S. Appl. No. 14/542,252, all pages.

Non-Final Office action dated Nov. 17, 2017 in U.S. Appl. No. 14/542,252, all pages.

Non-Final Office action dated Jan. 12, 2017 in U.S. Appl. No. 14/528,995, all pages.


Non-Final Office action dated Nov. 16, 2017 in U.S. Appl. No. 14/528,995, all pages.

Notice of Allowance and Fee(s) Due dated Jul. 11, 2016 in U.S. Appl. No. 13/327,459, all pages.

Non-Final Office action dated Dec. 5, 2017 in U.S. Appl. No. 15/351,188, all pages.

Final Office action dated Sep. 19, 2018 in U.S. Appl. No. 15/351,202, all pages.

* cited by examiner

**FIG. 1**





FIG. 2

300**FIG. 3**






FIG. 4

500**FIG. 5**

600**FIG. 6**

1

INTELLIGENT TEMPERATURE MANAGEMENT BASED ON ENERGY USAGE PROFILES AND OUTSIDE WEATHER CONDITIONS

CROSS REFERENCES

This application is a continuation of U.S. patent application Ser. No. 14/473,906 filed Aug. 29, 2014, which is incorporated herein by reference. U.S. patent application Ser. No. 14/473,906 is a continuation of U.S. patent application Ser. No. 13/327,459 filed on Dec. 15, 2011, which is incorporated herein by reference. U.S. patent application Ser. No. 13/327,459 is a continuation of U.S. patent application Ser. No. 12/241,588 filed on Sep. 30, 2008 (now U.S. Pat. No. 8,160,752), which is incorporated herein by reference.

Furthermore, the subject matter of this application relates to the subject matter of the commonly assigned U.S. Provisional Application No. 60/977,015, filed on Oct. 2, 2007, entitled: "ENERGY MANAGEMENT PLATFORM," which is incorporated by reference herein.

FIELD

The field of the present invention relates to computer systems. More particularly, embodiments of the present invention relate to energy management systems.

BACKGROUND

Consumers experiment with different ways of reducing household energy usage. For example, consumers may turn off air conditioning during certain parts of the day, run certain appliances only during the early morning hours, and replace large inefficient appliances with smaller energy efficient ones. Additionally, consumers may use measuring devices to calculate the energy usage rate of a particular device. Then, depending upon the measured energy usage, a consumer may decide to turn the device on and off to adjust the home's overall energy usage.

However, there exist limitations as to the current system for measuring the energy usage of a particular device. While a device's energy usage may be determined for a given point in time, it is unclear what this determination means. For example, an energy usage measurement might specify that a device is using 2 kilowatts per hour. While this information may be useful to a scientist, the average consumer is not well acquainted with the kilowatt. Furthermore, it is not clear to the consumer what the 2 kilowatts per hour static measurement means in context with the energy usage of a possible new device, other devices, and/or the entire household of devices. Thus, current energy usage measurements are cryptic and not very useful to the average consumer.

BRIEF SUMMARY

Accessing an energy management policy for a plurality of devices is described, wherein the devices are coupled with a first structure. The energy usage of the devices is monitored. An energy usage rule and energy usage is then compared. The energy management policy and energy usage is also compared. Based on the comparing, an instruction is generated to modify an energy usage profile of said device to correlate with the energy usage rule associated with the devices and the energy management policy, thereby enabling efficient energy management.

2

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and form a part of this specification, illustrate embodiments of the present invention for managing energy usage and, together with the description, serve to explain principles discussed below:

FIG. 1 is a block diagram of an example system for managing energy usage in accordance with embodiments of the present invention.

FIG. 2 is a block diagram of an example system for managing energy usage in accordance with embodiments of the present invention.

FIG. 3 is a flowchart of an example method of managing energy usage in accordance with embodiments of the present invention.

FIG. 4 is a diagram of an example computer system used for managing energy usage in accordance with embodiments of the present invention.

FIG. 5 is a flowchart of an example method of managing energy usage in accordance with embodiments of the present invention.

FIG. 6 is a flowchart of an example method of managing energy usage in accordance with embodiments of the present invention.

The drawings referred to in this description should not be understood as being drawn to scale unless specifically noted.

DESCRIPTION OF EMBODIMENTS

Reference will now be made in detail to embodiments of the present invention, examples of which are illustrated in the accompanying drawings. While the invention will be described in conjunction with various embodiment(s), it will be understood that they are not intended to limit the present invention to these embodiments. On the contrary, the present invention is intended to cover alternatives, modifications and equivalents, which may be included within the spirit and scope of the various embodiments as defined by the appended claims.

Furthermore, in the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of the present invention. However, the present invention may be practiced without these specific details. In other instances, well known methods, procedures, components, and circuits have not been described in detail as not to unnecessarily obscure aspects of the present embodiments.

Unless specifically stated otherwise as apparent from the following discussions, it is appreciated that throughout the present detailed description, discussions utilizing terms such as "accessing", "monitoring", "comparing", "modifying", "enabling", "tracking", "generating", "estimating", "alerting", or the like, refer to the actions and processes of a computer system, or similar electronic computing device. The computer system or similar electronic computing device manipulates and transforms data represented as physical (electronic) quantities within the computer system's registers and memories into other data similarly represented as physical quantities within the computer system memories or registers or other such information storage, transmission, or display devices. The present invention is also well suited to the use of other computer systems such as, for example, optical and mechanical computers.

Overview of Discussion

Embodiments in accordance with the present invention pertain to a system for managing energy usage. In one

embodiment, the system described herein enables conservation of household energy by advising a user to modify the household's energy usage to correlate to a desired energy usage for that household.

More particularly, one embodiment of the present invention functions as a household energy manager. For example, the energy manager attaches to a household wall and replaces the typical heating-cooling thermostat controller. The energy manager then utilizes an energy-measuring module coupled with a household device to monitor the energy usage of the household device. For example, an energy-measuring module coupled with a dishwasher may measure a dishwasher utilizing 1.20 kilowatts per hour of electricity.

In addition to monitoring individual appliances, the energy manager may utilize an energy-measuring module, such as a smart meter, coupled with the house to monitor the total household's energy usage. For example, a smart meter may measure the overall energy usage of all appliances within a household, including the dishwasher, to be 21 kilowatts per hour of electricity.

The energy manager then may access an energy usage rule describing a desired energy usage for a device and/or the household. This energy usage rule may be preprogrammed and internal to the energy manager or may be accessed at a server positioned external to the energy manager. This server in turn may receive a demand-response call from an energy utility company. For example, a demand-response call may indicate that it is desirable that the aforementioned dishwasher is to use up to a maximum of 1.00 kilowatt per hour of electricity at any given time. Furthermore, an overall energy management policy may specify that the household may use up to a maximum of 20 kilowatts per hour of energy at any point in time.

Based on the comparison between the measured energy usage of a household device and that device's desired energy usage, the energy manager may modify the device's energy usage to conform with the overall desired energy usage. For example, based on the comparison between the dishwasher's measured 1.20 kilowatts per hour of energy usage, and the household's use of 21 kilowatts per hour of electricity, the energy manager may modify the dishwasher's energy usage by turning it off and on at time periods separate from other high energy usage appliances, to keep the overall household energy use below 20 kilowatts per hour at any given point in time.

Thus, an energy manager may utilize an internally preprogrammed energy usage rule and/or a demand-response call received via a server from an energy utility company to advise a user to modify a device's energy usage.

The following discussion will begin with a detailed description of the structure of components herein in accordance with the present invention. This discussion will then be followed by a detailed description of the operation and function of the components herein.

Energy Manager

FIG. 1 is a block diagram of an example energy manager 100 in accordance with embodiments of the present invention. Energy manager 100, coupled with first structure 140, comprises energy usage rule accessor 105, energy usage rule comparator 125, and energy usage profile generator 135.

Continuing with FIG. 2, a block diagram is shown of an example energy manager 100 in which energy usage rule accessor 105 comprises server accessor 220 and user instruction accessor 230. In another embodiment, energy usage rule comparator 125 comprises passive power consumption tracker 235. In one embodiment, energy manager

100 further comprising interface compatibility module 205 and graphical display module 215.

Energy manager 100 is shown coupled wirelessly with device 204 via energy-measuring module 250a and compatible communication module 210. Of note, energy-measuring module 250a may be coupled with energy manager 100 in such a way as to be part of energy manager 100. Energy-measuring module 250a operates as an inductive donut surrounding the electrical cord that couples device 204 with an electrical outlet of first structure 140. As will be described herein, energy-measuring module 250a listens for information such as energy usage signatures specific to device 204. This information is communicated wirelessly to energy manager 100 via a wireless transmitter and receiver coupled with energy measuring module 250a and compatible communication module 210, such as but not limited to the wireless Ethernet, ZigBee, X10, or some other suitable wireless protocol.

In another embodiment, energy manager 100 is shown coupled wirelessly with energy-measuring module 250b. Energy-measuring module 250b may be a digital meter coupled with the outside of the home. Energy utility 240 has access to this digital meter. The digital meter provides information regarding the total energy usage of the household. This information is communicated wirelessly to energy manager 100 via a wireless transmitter and receiver coupled with energy-measuring module 250b and energy manager 100, such as such as but not limited to the wireless Ethernet, ZigBee, X10, or some other suitable wireless protocol.

In one embodiment, energy manager 100 is shown coupled wirelessly with energy-measuring modules 250c1 and 250c2 of a group of energy-measuring modules denoted as 250c, that are themselves coupled with subpanels positioned on the side wall and ceiling of first structure 140. Of note, in another embodiment, energy manager 100 may also be coupled with energy-measuring modules 250c1 and 250c2 via a wire. Additionally, energy manager 100 is well suited to being coupled with a plurality of more than two energy-measuring modules of energy-measuring module group 250c at any number of locations within first structure 140.

Energy-measuring modules 250c1 and 250c2 that are coupled with the subpanels and positioned in the proximity of device 204 listen for information such as energy usage signatures specific to device 204. For example, a certain amount of signal noise flows between and through energy-measuring modules 250c1 and 250c2. By identifying and comparing said signal noise received at energy-measuring modules 250c1 and 250c2, better granularity in reading the energy signature of device 204 can be obtained. The more 250c energy-measuring modules that are positioned at first structure 140, the more data that can be collected. The more data that can be collected, the more accurate is the determination of energy usage per device 204.

Of note, energy usage rule 202 may be any recommendation or instruction for energy usage as it relates to device 204, either alone, or as part of an energy management policy for one or more devices. In one embodiment, an energy management policy may designate the overall desired household energy usage as well as the desired energy usage for individual devices therein.

In one embodiment, energy usage rule 202 is preprogrammed within energy manager 100. In another embodiment, energy usage rule 202 is external to energy manager 100, located at server 225, and provided to server 225 via energy utility 240 or other Internet hosted servers. In one embodiment, server 225 acts as a central management

server. Energy utility **240** is coupled with energy manager **100** via Internet **245** and server **225**, and is coupled with first structure **140** via energy-measuring module **250b**.

In another embodiment, unit **260** is coupled with device **204** and electrical outlet **265** with which device **204** is also coupled. Additionally, the present invention is well suited to having any number of units **260** coupled with any number of devices and any number of electrical outlets. Unit **260** is configured to receive an instruction to modify an energy usage profile of device **204** to correlate with device **204**'s energy usage rule. In essence, unit **260** may control the power to device **204**. Of note, unit **260** may receive instructions to modify the energy usage profile of device **204** from any device capable of sending receivable instructions.

In one embodiment, an energy manager **100** coupled with a subpanel within first structure **140** wirelessly transmits an instruction to unit **260** to modify the energy usage profile of device **204**. In another embodiment, user **255** may email an instruction to unit **260** to modify device **204** coupled therewith. More particularly, in one example, unit **260** is coupled with a lamp. Energy manager **100** sends a message to unit **260** that the lamp is utilizing too many kilowatts per hour of energy and needs to be turned down. Unit **260** then dims the lamp's lighting, thus decreasing the lamp's energy usage according to the instructions.

Continuing with FIG. 2, device **204** may be any device that may be coupled with first structure **140**. Of note, device **204** may be any device capable of utilizing energy within first structure **140**. However, for purposes of brevity and clarity, device **204** is sometimes referred to herein as "household device". For example, device **204** may be a washer, a dryer, a refrigerator, a dishwasher, a toaster, etc. Furthermore, first structure **140** may be any structure with which one or more devices may be coupled and within which one or more devices may use electricity. However, for purposes of brevity and clarity, first structure **140** is sometimes referred to herein as "household".

Operation

More generally, in embodiments in accordance with the present invention, energy manager **100** is used to monitor and instruct a user to modify the energy usage profile of one or more devices within a household to correlate to a desired energy usage for that device and/or household. In another embodiment, energy manager **100** is used to monitor and automatically modify the energy usage profile of one or more devices within a household to correlate to a desired energy usage for that device and/or household. Desired energy usage may be based on energy usage rules internal to energy manager **100** and/or energy usage rules ultimately received from an energy utility. Such an instruction and/or modification are particularly useful to conserve household energy usage.

More particularly, and referring to FIG. 2, in one embodiment, energy usage rule accessor **105** accesses an energy usage rule **202** of device **204**, wherein device **204** is coupled with first structure **140**. Then, energy usage rule comparator **125** receives an energy usage measurement of device **204** and compares energy usage rule **202** with the energy usage measurement. Next, energy usage profile generator **135** generates an instruction to modify an energy usage profile of device **204** to correlate with the energy usage, thereby enabling efficient energy management.

An energy usage measurement of one or more devices refers to the total amount of energy measured for each device and/or for cumulative devices within first structure **140**. For example, energy-measuring module **250a** measures energy through a study of a device's energy usage signature

that vacillates with its energy usage. For example, every device that plugs into an electrical system has a unique energy usage signature. In other words, every device exhibits its unique signal patterns during its electrical usage. These signals are used to calculate a total amount of energy being used at any given time by device **204**.

An energy usage profile of device **204** refers to the overall energy usage of device **204** and device's **204** interaction with other devices within first structure **140**, taking into account all available input, such as user **255** input, energy utility **240** input, and/or other input received via Internet **245** and server **225**. Additionally, an energy usage profile of device **204** may be integrated with an energy usage profile of a device located within one or more structures other than first structure **140**.

In one embodiment, energy usage rule accessor **105** comprises server accessor **220**, configured for accessing an energy management instruction at server **225**, wherein server **225** is positioned apart from first structure **140**. Server **225** holds instructions received from energy utility **240**. These instructions, for example, may command energy manager **100** to conserve energy relating to one or more structures that are subscribed to a demand response program. This command to conserve energy may take the form of an instruction to turn down a thermostat's set-point in the summer and to turn up the thermostat's set-point in the winter during critical peak energy draw situations. In essence, the instructions provide that the AC is to be turned down in the summer and that the heater is to be turned down in the winter at certain critical points in time.

However, "cheaters" could put a local heat source such as a match (in the summer) or a local cold source such as an ice-cube (in the winter) to attempt to trick the thermostat that the adjustment being made will have a positive effect on the energy load. Energy manager **100** may then profile the actual energy load reduction vs. the projected energy load reduction. If it is determined that the difference between the actual energy load reduction vs. the projected energy load reduction is too great, then a demand response situation may be triggered.

In a demand response situation, energy manager **100** may ignore the actual temperature reading and may alert authorities of the cheating. For example, when the demand response situation has been triggered and using sophisticated algorithms, energy manager **100** may determine the appropriate actions in proceeding with an energy load reduction, regardless of the energy manager **100**'s local temperature reading. Energy manager **100** may also flag a server **225** as to suspicious behavior for later follow-up by authorities.

In another embodiment, user instruction accessor **230** is configured for accessing an instruction from user **255**, wherein the instruction provides guidance as to user's **255** desired energy usage for device **204**. For example, in one embodiment, user **255** may input information into energy manager **100** such as to what temperature user **255** would like a room to remain for the next five hours.

In one embodiment, the user instruction is a result of a dialogue generated by energy manager **100** with user **255**. For example, energy manager **100** may create a dialogue with user **255** via text and/or sound to learn how and when to automatically modify the in-home environment taking into account the comfort of user **255**. Energy manager **100**, for example, may interview user **255** to improve user's personal satisfaction with the HVAC and energy automation effectiveness. One or all of the available energy manager **100**'s available user interfaces may query, "Are you cold, hot, or just right now?" or "We made the assumption due to

the time of day and day-in-the-month not to turn the heat on at this time to save you money . . . did you like the decision?" The answers to these queries may be used to create an energy usage profile of user **255** and the household.

After establishing a home owner's preference in temperature and pattern of usage, energy manager **100** may also factor in local weather conditions into pro-active plans for heating and cooling. For example, an Internet hosted server (coupled with server **225** via Internet **245**) may provide forecasted weather data for the home in neighborhood, identifiable by zip code. Energy manager **100** may use the anticipation of a coming weather pattern, user preference knowledge, and scheduled or critical peak energy rates (actual or expected) to take pro-active steps. For example, these pro-active steps may include gradually cooling down the house to 65 degrees throughout the morning until 11 am, while taking into account that user's **255** disregard for the cold in the morning as well as taking advantage of cheaper energy rates.

In another embodiment, an instruction is generated to modify an energy usage profile of first device **204** coupled with first structure **140** according to an energy usage profile of a second device coupled with a second structure, such that the energy usage associated with first structure **140** and the energy usage associated with the second structure does not occur at the same time. For example, two different homes both have an energy manager **100**, are coupled with server **225**, and enter into a local grid "balancing algorithm". Home #1 wants to use its compressor. Home #2 wants to heat its swimming pool. If both homes use this type of energy at the same time, the power grid will be taxed with a cumulative amount of power usage. However, if the two homes stagger its energy usage, then the power grid's average usage will remain the same. In other words, when home #1 is done with using its compressor, the pool heater of home #2 will be recommended to be powered on.

For example, energy manager **100** of home #1 generates an instruction to the effect that home #1 should power on its compressor between the hours of 2 p.m. and 4 p.m. Energy manager **100** of home #2 generates an instruction to the effect that home #2 should power on its pool heater between the hours of 4 p.m. and 6 p.m. The residents of home #1 may then follow its energy manager **100**'s instructions. The residents of home #2 may also then follow its energy manager **100**'s instructions.

In another embodiment of the present invention, when home #1 is done with using its compressor, the pool heater of home #2 will automatically power on.

In other words, energy manager **100** causes "peak load management" to occur, in which some or all devices within a home may be turned off in critical peak power situations. This peak load management can be performed based on geography, such as but not limited to peak load management per house and peak load management per neighborhood.

In one embodiment of the present invention, energy manager **100** comprises interface compatibility module **205**, configured for enabling coupling of energy manager **100** with compatible communication module **210**, wherein energy manager **100** utilizes compatible communication module **210** to access an energy usage measurement. For example, interface compatibility module **205** provides a means of choosing the best method of Internet connectivity for user **255**. It comprises a compatible communication module **210** that allows user **255** to buy a compatible wireless networking module, a household-wiring module, or other appropriate module that allows for further customization by user **255** to match user's **255** existing home network.

For example, compatible communication module **210** enables the coupling of wireless connector 802.11 with energy manager **100**. Wireless connector 802.11 then enables communication with energy measuring module **250a**.

In another embodiment of the present invention, energy manager **100** comprises graphical display module **215**, configured for enabling communication with user **255**. For example, graphical display module **215** may include various aesthetic properties relating to color, texture, shape, and lighting. In one embodiment, graphical display module **215** may be a glass touch screen panel. The panel may be color and incorporate graphics. The panel may enable communication via icons, graphs, pie charts, etc.

In one embodiment, energy manager **100** generates an instruction that is receivable by a human user **255** of device **204**. This instruction may be receivable through any number of mediums, including graphical display module **215** positioned as shown in FIG. **2** or positioned anywhere that enables coupling wired or wireless coupling with first structure **140**. Additionally, human user **255** of device **204** may access the generated instruction at any device within first structure **140** that is configured to transmit the instruction, such as but not limited to a desktop computer and/or portable electronic device. Further, human user **255** of device **204** may access the generated instruction as an email message, SMS message, or other electronic message via a device capable of supporting the transmission and display of the message. In another embodiment, energy manager **100** generates an instruction that is receivable by device **204**. The instruction enables device **204** to alter its energy usage profile based on the comparing of the energy usage rule for device **204** and device **204**'s energy usage.

In one embodiment, energy manager **100** comprises passive power consumption tracker **235**, configured for tracking a difference between the sum of energy usage of all devices, wherein all these devices are in an active state and coupled with first structure **140**, and a total energy used within first structure **140** to generate a passive power consumption analysis. For example, energy manager **100** may provide calculated estimates of passive power consumption. The difference between the sum of each appliance's energy usage and the total energy usage is per household is passive power consumption and untracked power usage. This untracked power usage is un-optimizable usage. Passive power consumption is considered to be the most significant drain of power on a power grid. Wall nuts and other passive power drains are undocumented and yet pull more current than any other sink. Even though an appliance is "off" doesn't mean that the appliance isn't consuming power. Tracking this passive power usage increases the user's **255** awareness of energy usage and creates opportunities to conserve overall energy.

In one embodiment of the present invention, an upgrade to energy manager **100** is accessed. For example, energy manager **100** may access, via server **225**, upgrades to its functionalities and interoperability capacity with devices. In one embodiment, device **204** is upgraded within the home. Energy manager **100** may then access, via server **225**, device **204**'s manufacturer to receive upgraded energy standards for device **204**.

It is important to note that energy manager **100** may be a direct replacement for the heating-cooling thermostat controller that connects to the home air conditioner/heater. For example, a consumer may purchase energy manager **100**, pull their current thermostat off their household wall, and mount energy manager **100** in its place. Energy manager **100**

then performs all of the air conditioner/heater operations that would be expected from the displaced heating-cooling thermostat as well as the operations attributable to energy manager 100 described herein. Furthermore, a new face plate may include, but is not limited to, an increased display size, a faster processor within, added features to make energy manager 100 more user friendly.

FIG. 3 is a flowchart 300 of an example method of managing energy usage. With reference now to 305 of FIG. 3, an energy usage rule 202 for device 204 is accessed, wherein device 204 is coupled with first structure 140.

With reference to 310 of FIG. 3, in another embodiment energy usage of device 204 is monitored. This monitoring may be automatically performed or upon command by user 255, energy utility 240, or some other authorized monitor. For example, a device's 204 energy usage may be monitored by energy utility 240 via energy measuring module 250b for inconsistencies in thermostat readings.

With reference to 315 of FIG. 3, in one embodiment, energy usage rule 202 is compared with the energy usage of device 202. Finally, with reference to 320 of FIG. 3, in one embodiment, based on 315 comparing of energy usage rule 202 and the energy usage of device 204, an instruction is generated to modify an energy usage profile of device 204 to correlate with energy usage rule 202, thereby enabling efficient energy management.

Thus, embodiments of the present invention enable the generation of an instruction for a user to modify an energy usage profile of one or more devices within a household to correlate to a desired energy usage for that device and/or household. Additionally, embodiments of the present invention enable the generation of an instruction to automatically modify an energy usage profile of one or more devices within a household to correlate to a desired energy usage for that device and/or household. Furthermore, an instruction to modify an energy usage profile for a device and/or household may be based on instructions from a user and instructions from a utility company via a server.

Example Computer System Environment

With reference now to FIG. 4, portions of the invention for generating a pre-recorded quick response are composed of computer-readable and computer-executable instructions that reside, for example, in computer-usable media of a computer system. That is, FIG. 4 illustrates one example of a type of computer that can be used to implement embodiments, which are discussed below, of the present invention.

FIG. 4 illustrates an example computer system 400 used in accordance with embodiments of the present invention. It is appreciated that system 400 of FIG. 4 is an example only and that the present invention can operate on or within a number of different computer systems including general purpose networked computer systems, embedded computer systems, routers, switches, server devices, user devices, various intermediate devices/artifacts, stand alone computer systems, and the like. As shown in FIG. 4, computer system 400 of FIG. 4 is well adapted to having peripheral computer readable media 402 such as, for example, a floppy disk, a compact disc, and the like coupled thereto.

System 400 of FIG. 4 includes an address/data bus 404 for communicating information, and a processor 406A coupled to bus 404 for processing information and instructions. As depicted in FIG. 4, system 400 is also well suited to a multi-processor environment in which a plurality of processors 406A, 406B, and 406C are present. Conversely, system 400 is also well suited to having a single processor such as, for example, processor 406A. Processors 406A, 406B, and 406C may be any of various types of microprocessors.

System 400 also includes data storage features such as a computer usable volatile memory 408, e.g. random access memory (RAM), coupled to bus 404 for storing information and instructions for processors 406A, 406B, and 406C.

System 400 also includes computer usable non-volatile memory 410, e.g. read only memory (ROM), coupled to bus 404 for storing static information and instructions for processors 406A, 406B, and 406C. Also present in system 400 is a data storage unit 412 (e.g., a magnetic or optical disk and disk drive) coupled to bus 404 for storing information and instructions. System 400 also includes an optional alphanumeric input device 414 including alphanumeric and function keys coupled to bus 404 for communicating information and command selections to processor 406A or processors 406A, 406B, and 406C. System 400 also includes an optional cursor control device 416 coupled to bus 404 for communicating user input information and command selections to processor 406A or processors 406A, 406B, and 406C. System 400 of the present embodiment also includes an optional display device 418 coupled to bus 404 for displaying information.

Referring still to FIG. 4, optional display device 418 of FIG. 4 may be a liquid crystal device, cathode ray tube, plasma display device or other display device suitable for creating graphic images and alpha-numeric characters recognizable to a user. Optional cursor control device 416 allows the computer user to dynamically signal the movement of a visible symbol (cursor) on a display screen of display device 418. Many implementations of cursor control device 416 are known in the art including a trackball, mouse, touch pad, joystick or special keys on alpha-numeric input device 414 capable of signaling movement of a given direction or manner of displacement. Alternatively, it will be appreciated that a cursor can be directed and/or activated via input from alpha-numeric input device 414 using special keys and key sequence commands.

System 400 is also well suited to having a cursor directed by other means such as, for example, voice commands. System 400 also includes an I/O device 420 for coupling system 400 with external entities.

Referring still to FIG. 4, various other components are depicted for system 400. Specifically, when present, an operating system 422, applications 424, modules 426, and data 428 are shown as typically residing in one or some combination of computer usable volatile memory 408, e.g. random access memory (RAM), and data storage unit 412. However, it is appreciated that in some embodiments, operating system 422 may be stored in other locations such as on a network or on a flash drive; and that further, operating system 422 may be accessed from a remote location via, for example, a coupling to the internet. In one embodiment, the present invention, for example, is stored as an application 424 or module 426 in memory locations within RAM 408 and memory areas within data storage unit 412. System 400 is also well suited to having a temperature sensor 430, an ambient light sensor 432, and a relative humidity sensor 434.

Computing system 400 is only one example of a suitable computing environment and is not intended to suggest any limitation as to the scope of use or functionality of the present invention. Neither should the computing environment 400 be interpreted as having any dependency or requirement relating to any one or combination of components illustrated in the example computing system 400.

The present invention may be described in the general context of computer-executable instructions, such as program modules, being executed by a computer. Generally, program modules include routines, programs, objects, com-

11

ponents, data structures, etc., that perform particular tasks or implement particular abstract data types. The present invention may also be practiced in distributed computing environments where tasks are performed by remote processing devices that are linked through a communications network. In a distributed computing environment, program modules may be located in both local and remote computer-storage media including memory-storage devices.

FIG. 5 is a flowchart illustrating a process 500 for managing energy usage, in accordance with one embodiment of the present invention. In one embodiment, process 500 is carried out by processors and electrical components under the control of computer readable and computer executable instructions. The computer readable and computer executable instructions reside, for example, in data storage features such as computer usable volatile and non-volatile memory. However, the computer readable and computer executable instructions may reside in any type of computer readable medium. In one embodiment, process 500 is performed by energy manager 100 of FIG. 1.

With reference to 505 of FIG. 5, a signal of device 204 is monitored, wherein the signal is an energy usage signature specific to device 204 and device 204 is coupled with first structure 140. With reference to 510 of FIG. 5, an analysis of energy usage of device 204 is generated based on the monitoring of a signal of device 204. The analysis describes an energy usage profile of device 204.

In one embodiment, method 500 further comprises estimating savings with regards to replacing device 204 with a new device, wherein the estimating is based on the analysis described herein of method 500. For example, by installing energy manager 100, user 255 can get contextual advice on how to efficiently and affordably upgrade user's 255 current HVAC unit. Energy manager 100 estimates how much money would be saved by installing a new HVAC unit based on algorithms that do the following: measure, store, and analyze energy usage history; utilize a Seasonal Energy Efficiency Rating (SEER) of a new HVAC unit and how it would profile in the current household; and measure current HVAC unit run time and the temperature drop rate over various time intervals.

Energy manager 100 may, through its back-end server 225 connection in Internet 245, enable partnerships with local (or national) HVAC companies. Energy manager 100 may change its line-up of eligible replacement HVAC units based on factors such as pricing and availability in real-time. Energy manager 100 may provide contextual advertisement for HVAC unit vendors, or for any other product or service. The messaging from energy manager's 100 face-plate, connected PC interface, or connected mobile interface provides such useful information as, "You would save \$130 per month if you upgraded to a Y SEER AC."

In yet another embodiment of the present invention, method 500 further comprises generating an analysis that informs user 255 of the costs associated with changing the settings of device 204. For example, energy manager 100 may generate an analysis that informs user 255 that changing the dishwasher to run at half power instead of at full power may save user 255 \$20 per month.

In another embodiment, method 500 further comprises comparing the energy usage of first structure 140 with an energy usage of a second structure based on the analysis described herein of method 500. For example, with energy managers 100 in different homes, comparisons may be made between and among homes. A home in neighborhood N1 can compare its energy usage to a friend's home in neighborhood N2. Energy manager 100 may then relay to user 255

12

the following, "Your friend, Jim Smith, is spending \$500 per month to heat/cool their house." Or, energy manager 100 may relay to user 255, "Your sister's fridge is costing \$50 per month to keep the food cold, which is in the top 10% of homes in the nation in terms of effectiveness and efficiency." This neighbor comparison functionality works on competitive psychology. This functionality enables more sales of new and energy efficient units and overall electricity conservation for the power energy grid.

In another embodiment, method 500 further comprises alerting user 255 to specific maintenance tasks for device 204 that are recommended based on an analysis of energy usage of device 204 described herein. For example, method 500 comprises alerting user 255 that a new filter for device 204 is needed based on the analysis described herein of method 500. For example, energy manager 100 may estimate when enough time has passed based on overall usage to determine that a new filter for the HVAC unit is needed. Energy manager 100 may show reminders for replacing these HVAC filters. Energy manager 100 may show statistics on how much money is saved or lost by replacing or waiting to replace HVAC filters.

In another embodiment, method 500 further comprises calculating the efficiency of the HVAC correlated to the energy efficiency of the home (including insulation and air leakage through ducts, under doors, and around windows). For example, based on the duration that it takes to drop the temperature of the home to the desired temperature while taking into consideration the cost of electricity, energy manager 100 calculates the efficiency of the HVAC correlated to the energy efficiency of the home.

Similarly, energy manager 100 may calculate the current efficiency of an appliance such as a refrigerator. Utilizing an energy-measuring module 250a between the refrigerator and the electrical outlet, energy manager 100 can make algorithmic conclusions based on the setting and the history of the refrigerator. Thus, energy manager 100 may generate an analysis on the estimated energy efficiency of the refrigerator.

In another embodiment, method 500 further comprises alerting user 255 of a possible failure of device 204 based on an analysis of historical data or data on a remote server. This historical data includes the monitored energy usage data for device 204 described herein. Method 500 further comprises alerting user 255 of possible device 204 failure based on device's 204 history. For example, circuits sometimes begin to eat up larger and larger amounts of current or show erratic current draw before they fail. A "healthy history" of current usage per device 204 may be compared to current spikes or other erratic current draw to predict the failure of device 204.

In another embodiment, method 500 further comprises calculating the break even date of a replacement product. For example, energy manager 100 monitors the energy usage history for device 204. Then, after device 204 is replaced, energy manager 100 marks the replacement date. Energy manager 100 may then calculate the break even date and any realized savings based off of electric rate data. Energy manager 100 may then communicate these calculations to user 255 via graphical display module 215. Energy manager 100 may also communicate a victory notification to user 255.

In another embodiment, method 500 further comprises assisting user 255 with achieving a money savings goal by managing user's 255 energy usage. For example, a user's 255 financial savings goal and an interaction between user 255 and user's 255 device(s) 204 may result in a dialogue

13

with device(s) 204 or even with the whole house. Energy manager 100 may also keep user 255 current on user's 255 financial savings. Energy manager 100 may tie its energy usage management of device(s) 204 with an incentive, such as, "By turning the AC up to 89 degrees, we are saving for our Fiji vacation."

In another embodiment, method 500 further comprises querying and negotiating with user 255 to assist user 255 in meeting an energy budget target. For example, energy manager 100 may both interview and negotiate with user 255. The interviews may be periodic questions, posed through user-interfaces. These question posed may relate to personal comfort, and preferences on HVAC and energy automation effectiveness. For example, one question might be, "Are you cold, hot, or just right at this time?" The answer to this question will inform energy manager 100 of the threshold of environmental comfort for user 255 based on a registered temperature reading. Energy manager 100 may also poll user 255 if user 255 is the only one home or if other friends or relatives are at home to determine what actions should be taken.

Another possible question may be, "We made the assumption due to the time of day and the day in the month not to turn the heat on at this time in order to save you money . . . did you like this decision?" A positive response from user 255 will reinforce the algorithmic decision made. Whereas a negative response will provide the initiative to make a change.

The negotiation (via email, SMS, Instant Messaging, or directly accessing the interface of energy manager 100) of user 255 with energy manager 100 relates to trying to help user 255 hit a pre-set energy budget target. For example, if after 20 days into the month the user's 255 trend line is above the forecasted month end bill and/or energy usage, energy manager 100 may send user 255 an SMS messaging requesting permission to turn the heat down three degrees.

In another embodiment, method 500 further comprises profiling a device 204 based on the history of device 204 and environmental factors. For example, energy manager 100 may support the use of one energy-measuring module 250a used to connect device 204 to energy manager 100. Based on the energy consumption over time and against assorted environmental factors energy manager 100 will profile device 100 as to its energy consumption, energy costs, and as a percentage of room device class, and whole-home totals. This one energy-measuring module 250a may be rotated around the home to eventually construct a whole home energy profile, with or without the presence of energy-measuring module 250b.

Furthermore, this device-level energy audit can be conducted over varying levels of time and report to user 255 its higher level of confidence on its estimates based on the variable of time allowed to measure a particular device 204. Energy manager 100 may compare similar devices of its class via information on Internet hosted servers. Moreover, energy manager 100 may compare similar devices for the home via historical information from one or more energy utility 240. Energy manager may also make a forecast regarding device 204 based on company trends and forecasts.

In another embodiment, method 500 further comprises managing an energy co-op of a pool of energy manager 100 user(s) 255. For example, energy manager(s) 100 is able to aggregate homes within and across neighborhoods, grouping them into a logical large single pool. A logical large single pool of houses might be homes located geographically near each other. Energy manager 100 thus provides a distributed

14

"buying block" of energy user's 255. This "buying block", having purchased from energy wholesalers, is able to act in a cooperative capacity as energy manager 100 user(s) 255. Beneficially, user(s) 255 would experience reduced energy costs. Server 225 may manage this co-op.

In yet another embodiment of the present technology, a plurality of energy usage signatures is aggregated by remote server 225. This plurality of energy usage signatures is compiled for comparison with subsequently received energy usage signatures. One or more of the energy usage signatures may be identified by user 255 of the device(s). In one embodiment, remote server 225 receives from user 255 of device 204 the identification information, including but not limited to device type, manufacturer, and model information to be associated with its energy usage signature. The server then aggregates this identification of device 204 in a database at server 225.

More particularly, energy manager 100 may detect a new energy usage signature within first structure 140. Energy manager 100 may notify user 255 that a new energy usage signature (device 204) exists and prompt user 255 for the device's identification. User 255 then may identify device 204 as washer model #4305. Energy manager 100 then sends this energy usage signature along with its identification to server 225. Remote server 225 stores this identification in a database that is accessible to users of device 204 and devices other than device 204. In this way, a database of energy usage signatures and related identifications is built and accessible by, but not limited to, users of various devices, manufacturers, and energy utility companies.

In another embodiment, the plurality of energy usage signatures of first structure 140 received by server 225 are provided for use and comparison of one or more energy usage signatures by an energy manager 100 in a second structure. For example, the energy usage signatures detected in structure 140 and their identification that is stored in a database at server 225 are provided to an energy manager 100 of a second structure for use and comparison with one or more energy usage signatures therein.

For example, energy manager 100 of a second structure uses the identified energy usage signatures associated with the devices in first structure 140 to identify the energy usage signatures detected in the second structure. In this manner, energy manager 100 takes advantage of a database of identifications of energy usage signatures located at a remote server in order to more quickly identify the devices within a household with which it is coupled. Of note, users of devices coupled with different structures provide assistance in the collection and identification of energy usage signatures for any number of devices.

FIG. 6 is a flowchart illustrating a process for managing energy usage in accordance with embodiments of the present invention is shown. With reference now to 605 of FIG. 6, an energy usage rule 202 for device 204 is accessed, wherein device 204 is coupled with first structure 140.

With reference to 610 of FIG. 6, in another embodiment energy usage of device 204 is monitored. This monitoring may be automatically performed or upon command by user 255, energy utility 240, or some other authorized monitor. For example, a device's 204 energy usage may be monitored by energy utility 240 via energy measuring module 250b for inconsistencies in thermostat readings.

User 255 may access these instructions at, but not limited to, energy manager 100, at a device coupled with first structure 140, at a server 225 coupled with energy manager

15

100 and/or first structure 140, and/or at a device at a second structure coupled wired or wirelessly with first structure 140.

With reference to 615 of FIG. 6, in one embodiment, energy usage rule 202 is compared with the energy usage of device 202. Finally, with reference to 620 of FIG. 6, in one embodiment, based on 615 comparing of energy usage rule 202 and the energy usage of device 204, an instruction is generated to modify an energy usage profile of device 204 to correlate with energy usage rule 202, wherein the instruction is formatted for interpretation by a human user, thereby enabling efficient energy management. An instruction is formatted for interpretation by a human user if the instruction is transmitted in such a way that it could be understood by a human user.

Thus, embodiments of the present invention enable the generation of an instruction for a human user to modify an energy usage profile of one or more devices within a household to correlate to a desired energy usage for that device and/or household. Additionally, embodiments of the present invention enable the generation of an instruction to automatically modify an energy usage profile of one or more devices within a household to correlate to a desired energy usage for that device and/or household.

Thus, embodiments of the present invention increase consumer awareness as to conservation of energy by enabling the generation of an analysis of a device's energy usage. In one embodiment, the analysis informs a consumer of estimated savings with regards to replacing a device with a new device. In another embodiment, the analysis provides a comparison of the energy usage and energy costs of two different households. Furthermore, embodiments of the present invention inform a consumer when a new filter for a device is needed based on a generated analysis. Thus, embodiments of the present invention are beneficial by increasing a consumer's awareness of energy conservation opportunities.

Although the subject matter has been described in a language specific to structural features and/or methodological acts, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described above. Rather, the specific features and acts described above are disclosed as example forms of implementing the claims.

What is claimed is:

1. A method of controlling a temperature of an enclosure, comprising:
 - wirelessly receiving, at a thermostat associated with the enclosure, at least one setpoint temperature from a user, the setpoint temperature indicating a desired temperature of the enclosure;
 - operating the thermostat in accordance with the setpoint temperature;
 - monitoring energy consumption associated with the thermostat;
 - comparing the monitored energy consumption to an energy usage rule;
 - receiving weather information from an Internet-based host server, the weather information indicating weather near the enclosure;
 - based on the comparing, making at least one adjustment to the operation of the thermostat that will reduce energy consumption associated with the thermostat as compared to the energy consumption associated with operating the thermostat in accordance with the setpoint temperature, wherein:

16

the adjustment comprises decreasing the temperature set by the thermostat below the setpoint temperature prior to a forecasted outside temperature increase according to the received weather information when an air conditioner of an HVAC (heating, ventilation, and air conditioning) system is enabled; or

the adjustment comprises increasing the temperature set by the thermostat above the setpoint temperature prior to a forecasted outside temperature decrease according to the received weather information when a heater of the HVAC system controlled by the thermostat is enabled; and

operating the thermostat in accordance with the at least one adjustment.

2. The method of claim 1, further comprising:
 - receiving a command from a remote server to conserve energy; and

- operating the thermostat in accordance with the command.

3. The method of claim 1, wherein operating the thermostat in accordance with the setpoint temperature includes taking into consideration a user's perception of temperature.

4. The method of claim 3, wherein taking into consideration a user's subject perception of temperature includes querying the user as to whether they feel hot or cold.

5. The method of claim 1, further comprising:
 - determining an address of the enclosure, wherein the weather outside of the enclosure is determined based on the address of the enclosure and is acquired over an Internet.

6. The method of claim 1, further comprising:
 - tracking an operation history of a heating, ventilation, and air conditioning (HVAC) unit associated with the thermostat;

- determining that a total operation time of the HVAC unit has exceeded a predetermined threshold; and

- communicating advice to the user regarding an upgrade to the HVAC unit in response to determining that the total operation time has exceeded the predetermined threshold.

7. The method of claim 6, wherein communicating advice includes alerting the user to replace a filter of the HVAC unit.

8. The method of claim 1, further comprising:
 - receiving user input to configure operation of the thermostat.

9. The method of claim 1, further comprising:
 - receiving from the user a specific period of time during which the setpoint temperature is the desired temperature of the enclosure.

10. The method of claim 1, further comprising:
 - communicating, to the user, an advertisement for a product and/or a service that is contextual to temperature management.

11. The method of claim 1, further comprising:
 - in response to the at least one adjustment, calculating a difference between an actual energy load reduction of the HVAC system and a projected energy load reduction of the HVAC system; and
 - determining a demand response situation is triggered based on the calculated difference.

12. The method of claim 11, further comprising:
 - in response to determining that the demand response situation is triggered based on the calculated difference, operating the HVAC system while ignoring a temperature measured by the thermostat.

17

13. The method of claim 11, further comprising:
in response to determining that the demand response
situation is triggered based on the calculated difference,
transmitting an indication of suspicious behavior to a
remote server.

14. A system comprising:

a wireless transceiver configured to transmit and receive
data through a wireless network that receives at least
one setpoint temperature from a user, the setpoint
temperature indicating a desired temperature of the
enclosure;

an electrical terminal operatively coupled to an HVAC
unit within the enclosure; and

one or more processors coupled to the wireless transceiver
and the electrical terminal and configured to perform
operations comprising:

operating a thermostat in accordance with the setpoint
temperature;

monitoring energy consumption associated with the
thermostat;

comparing the monitored energy consumption to an
energy usage rule;

receiving weather information from an Internet-based
host server, the weather information indicating
weather near the enclosure;

based on the comparing, making at least one adjust-
ment to the operation of the thermostat that will
reduce energy consumption associated with the ther-
mostat as compared to the energy consumption asso-
ciated with operating the thermostat in accordance
with the setpoint temperature, wherein the at least
one adjustment comprises:

decreasing the temperature set by the thermostat
below the setpoint temperature prior to a fore-
casted outside temperature increase according to
the received weather information when an air
conditioner of an HVAC (heating, ventilation, and
air conditioning) system is enabled, or

increasing the temperature set by the thermostat
above the setpoint temperature prior to a fore-
casted outside temperature decrease according to
the received weather information when a heater of
the HVAC system controlled by the thermostat is
enabled; and

operating the thermostat in accordance with the at
least one adjustment.

15. The system of claim 14, further comprising:

a humidity sensor coupled to the one or more processors,
wherein the one or more processors are further configured
to receive a humidity reading from the humidity sensor.

16. The system of claim 14, further comprising:

an ambient light sensor coupled to the one or more
processors,

wherein the one or more processors are further configured
to receive a reading from the ambient light sensor.

17. A non-transitory, computer-readable medium com-
prising instructions that, when executed by one or more
processors, cause the one or more processors to perform
operations comprising:

18

wirelessly receiving, at a thermostat associated with the
enclosure, at least one setpoint temperature from a user,
the setpoint temperature indicating a desired tempera-
ture of the enclosure;

operating the thermostat in accordance with the setpoint
temperature;

monitoring energy consumption associated with the ther-
mostat;

comparing the monitored energy consumption to an
energy usage rule;

receiving weather information from an Internet-based
host server, the weather information indicating weather
near the enclosure;

based on the comparing, making at least one adjustment
to the operation of the thermostat that will reduce
energy consumption associated with the thermostat as
compared to the energy consumption associated with
operating the thermostat in accordance with the set-
point temperature, wherein the at least one adjustment
comprises:

decreasing the temperature set by the thermostat below
the setpoint temperature prior to a forecasted outside
temperature increase according to the received
weather information when an air conditioner of an
HVAC (heating, ventilation, and air conditioning)
system is enabled; or

increasing the temperature set by the thermostat above
the setpoint temperature prior to a forecasted outside
temperature decrease according to the received
weather information when a heater of the HVAC
system controlled by the thermostat is enabled; and
operating the thermostat in accordance with the at least
one adjustment.

18. The non-transitory, computer-readable medium of
claim 17, comprising additional instructions that cause the
one or more processors to perform additional operations
comprising:

storing time information relating to an operation interval
of an HVAC unit;

storing a first measurement of temperature associated with
a beginning of the operation interval;

storing a second measurement of temperature associated
with an end of the operating interval; and

calculating a temperature drop rate over the operating
interval.

19. The non-transitory, computer-readable medium of
claim 18, comprising additional instructions that cause the
one or more processors to perform additional operations
comprising:

calculating an efficiency for the enclosure based on the
temperature drop rate.

20. The non-transitory, computer-readable medium of
claim 18, comprising additional instructions that cause the
one or more processors to perform additional operations
comprising:

calculating an efficiency for the HVAC unit based on the
temperature drop rate.

* * * * *