



(12) **United States Patent**
Park et al.

(10) **Patent No.:** **US 9,959,107 B2**
(45) **Date of Patent:** **May 1, 2018**

(54) **METHOD AND APPARATUS FOR UPDATING APPLICATION**

(56) **References Cited**

(71) Applicant: **Samsung Electronics Co., Ltd.**,
Gyeonggi-do (KR)
(72) Inventors: **Sunmin Park**, Seoul (KR); **Sangho Kim**,
Gyeonggi-do (KR); **Boseok Moon**, Gyeonggi-do (KR); **Jaehyun Park**,
Gyeonggi-do (KR)
(73) Assignee: **Samsung Electronics Co., Ltd.** (KR)
(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 33 days.

U.S. PATENT DOCUMENTS
5,907,617 A * 5/1999 Ronning G06F 21/121
705/52
6,049,671 A * 4/2000 Slivka G06F 8/65
717/173
6,167,567 A * 12/2000 Chiles G06F 9/4448
709/221
6,738,801 B1 * 5/2004 Kawaguchi G06F 8/65
709/208
6,820,259 B1 * 11/2004 Kawamata G06F 8/61
717/173
6,976,062 B1 * 12/2005 Denby G06F 8/65
709/203

(Continued)

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **14/319,935**
(22) Filed: **Jun. 30, 2014**

KR 10-1083189 11/2011
KR 1020130022488 3/2013
KR 1020130066421 6/2013

(65) **Prior Publication Data**
US 2015/0007157 A1 Jan. 1, 2015

OTHER PUBLICATIONS

“Android 2.3.4 User’s Guide”, Android Mobile Technology Plat-
form 2.3.4, XP055178792, May 20, 2011, 17 pages.

(Continued)

(30) **Foreign Application Priority Data**
Jun. 28, 2013 (KR) 10-2013-0075239

Primary Examiner — Tuan Q. Dam
Assistant Examiner — Zheng Wei
(74) *Attorney, Agent, or Firm* — The Farrell Law Firm,
P.C.


(51) **Int. Cl.**
G06F 8/65 (2018.01)
G06F 9/445 (2018.01)
H04M 1/725 (2006.01)
(52) **U.S. Cl.**
CPC **G06F 8/65** (2013.01); **H04M 1/72525**
(2013.01)

ABSTRACT

(57) A method and an apparatus for updating an application are provided. An electronic device activates an automatic update of an installed application, designates the application as one group of one or more groups distinguished according to an update period. The electronic device controls to update the application after a time point of an update period corresponding to the designated group.

(58) **Field of Classification Search**
CPC G06F 8/60–8/68
See application file for complete search history.

18 Claims, 22 Drawing Sheets



(56)	References Cited	2006/0020943 A1 *	1/2006	Boutcher	G06F 9/5077
	U.S. PATENT DOCUMENTS				718/104
		2006/0037014 A1 *	2/2006	Ersek	G06F 9/44505
6,990,656 B2 *	1/2006 Ersek				717/168
					717/151
7,376,870 B2 *	5/2008 Kataria	2006/0053416 A1 *	3/2006	Watanabe	G06F 9/44557
					717/173
7,555,551 B1 *	6/2009 McCorkendale	2006/0059481 A1 *	3/2006	Smith	G06F 8/65
					714/47.1
7,584,467 B2 *	9/2009 Wickham	2006/0075276 A1 *	4/2006	Kataria	G06F 8/65
					717/174
7,730,475 B2 *	6/2010 Ersek	2006/0080656 A1 *	4/2006	Cain	G06F 8/65
					717/174
7,765,538 B2 *	7/2010 Zweifel	2006/0101457 A1 *	5/2006	Zweifel	G06F 8/65
					717/168
7,770,165 B2 *	8/2010 Olson	2006/0106806 A1 *	5/2006	Sperling	G06F 8/65
		2006/0106826 A1 *	5/2006	Butt	G06F 8/65
7,904,608 B2 *	3/2011 Price	2006/0168574 A1 *	7/2006	Giannini	G06F 8/65
					717/168
7,971,215 B1 *	6/2011 Strasman	2007/0021116 A1 *	1/2007	Okita	G06F 8/65
					455/428
8,010,991 B2 *	8/2011 Sarukkai	2007/0169081 A1 *	7/2007	Zhao	G06F 8/65
					717/168
8,074,213 B1 *	12/2011 Holtz	2007/0188507 A1 *	8/2007	Mannen	G06F 3/0607
					345/532
8,266,260 B2 *	9/2012 Pathak	2007/0192763 A1 *	8/2007	Helvick	G06F 8/65
					717/168
8,271,971 B2 *	9/2012 Thayer	2007/0250370 A1 *	10/2007	Partridge	G06Q 10/063112
					705/7.14
8,516,477 B1 *	8/2013 Kearns	2007/0256069 A1 *	11/2007	Blackman	G06F 8/433
					717/170
8,677,343 B2 *	3/2014 Averbuch	2008/0052698 A1 *	2/2008	Olson	G06F 8/68
					717/168
8,707,292 B2 *	4/2014 Little	2008/0148220 A1 *	6/2008	Tabaru	G06Q 10/06
					717/103
8,713,535 B2 *	4/2014 Malhotra	2008/0148248 A1 *	6/2008	Volkmer	G06F 8/65
					717/168
8,776,068 B2 *	7/2014 Ax	2008/0189693 A1 *	8/2008	Pathak	G06F 8/65
					717/168
8,819,661 B2 *	8/2014 Kakos	2008/0263439 A1 *	10/2008	Oz	G06F 17/3089
					715/235
8,819,662 B2 *	8/2014 Aoyagi	2009/0075641 A1 *	3/2009	Guyen	G06F 8/65
					455/419
8,819,703 B2 *	8/2014 Pasupathilingam ..	2009/0089775 A1 *	4/2009	Zusman	G06F 8/65
					717/173
8,875,123 B2 *	10/2014 Shiba	2009/0119657 A1 *	5/2009	Link, II	G06F 8/64
					717/171
8,910,140 B1 *	12/2014 Giannini	2009/0150878 A1 *	6/2009	Pathak	G06F 8/65
					717/172
9,069,554 B2 *	6/2015 Liyo	2009/0240791 A1 *	9/2009	Sakurai	G06F 8/65
					709/221
9,075,993 B2 *	7/2015 Bhargava	2009/0265699 A1 *	10/2009	Toeroe	G06F 8/65
					717/168
9,112,891 B2 *	8/2015 Pathak	2010/0070962 A1 *	3/2010	Sinn	G06F 8/65
2004/0002982 A1 *	1/2004 Ersek				717/171
2004/0010786 A1	1/2004 Cool et al.	2010/0083243 A1 *	4/2010	Mincarelli	G06F 8/61
2004/0024917 A1 *	2/2004 Kennedy				717/173
					710/1
2004/0031029 A1 *	2/2004 Lee	2010/0107150 A1	4/2010	Kamada et al.	
		2010/0175104 A1 *	7/2010	Khalid	G06F 9/545
					726/1
2004/0103411 A1 *	5/2004 Thayer	2010/0192120 A1 *	7/2010	Raleigh	G06Q 10/06375
					717/101
2004/0147253 A1 *	7/2004 Fukuzato	2010/0218187 A1 *	8/2010	Pasupathilingam ..	G06F 9/4443
					718/100
2004/0187103 A1 *	9/2004 Wickham	2010/0262960 A1 *	10/2010	Oshiumi	G06F 8/65
					717/171
2004/0210893 A1 *	10/2004 Chamberlain	2011/0004678 A1 *	1/2011	Rothrock	G06F 8/65
					709/223
2005/0050538 A1 *	3/2005 Kawamata	2011/0145811 A1 *	6/2011	Middendorf	F03D 7/047
					717/178
2005/0066019 A1 *	3/2005 Egan	2011/0307879 A1 *	12/2011	Ishida	G06F 8/68
					717/170
2005/0203968 A1 *	9/2005 Dehghan	2011/0307882 A1 *	12/2011	Shiba	G06F 8/65
2005/0210459 A1 *	9/2005 Henderson				717/173
					717/168
2005/0228798 A1 *	10/2005 Shepard	2012/0099024 A1 *	4/2012	Ryu	G06F 8/67
					348/730

(56)

References Cited

U.S. PATENT DOCUMENTS

2012/0102481 A1* 4/2012 Mani G06F 11/0757
717/172
2012/0130725 A1* 5/2012 Cooper G06Q 10/10
705/1.1
2012/0210310 A1* 8/2012 Cooley G06F 8/65
717/168
2012/0291022 A1* 11/2012 Mehta G06F 8/60
717/176
2013/0042227 A1* 2/2013 Little G06F 8/65
717/168
2013/0042230 A1* 2/2013 Little G06F 8/65
717/173
2013/0055271 A1 2/2013 Yoo et al.
2013/0074061 A1* 3/2013 Averbuch G06F 8/665
717/171
2013/0139138 A1* 5/2013 Kakos G06F 8/65
717/168
2013/0205289 A1* 8/2013 Unno G06F 8/65
717/171
2013/0246423 A1* 9/2013 Bhargava G06F 21/56
707/737
2013/0263107 A1* 10/2013 Hamakawa G06F 8/65
717/168
2013/0326493 A1* 12/2013 Poonamalli G06F 8/65
717/168

2013/0332918 A1* 12/2013 Aoyagi G06F 8/65
717/172
2014/0025974 A1* 1/2014 Suwabe G06F 1/3234
713/323
2014/0047425 A1* 2/2014 Thapar G06F 8/65
717/168
2014/0047426 A1* 2/2014 Raje G06F 8/65
717/168
2014/0052702 A1* 2/2014 Fierro G06F 8/65
707/695
2014/0053148 A1* 2/2014 Chan G06F 8/41
717/174
2014/0059534 A1* 2/2014 Daum G06F 8/65
717/172
2014/0089933 A1* 3/2014 Liroy G06F 9/4893
718/104
2014/0173084 A1* 6/2014 Boivin G06F 8/65
709/223
2014/0223423 A1* 8/2014 Alsina G06F 8/65
717/173
2014/0359596 A1* 12/2014 Cohen G06F 8/65
717/173

OTHER PUBLICATIONS

European Search Report dated Feb. 17, 2017 issued in counterpart application No. 14816837.0-1954, 7 pages.

* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16A




FIG. 16B




FIG. 16C




FIG. 16D




FIG. 17A





FIG. 17B



1

METHOD AND APPARATUS FOR UPDATING APPLICATION

PRIORITY

This application claims priority under 35 U.S.C. § 119(a) to Korean Patent Application No. 10-2013-0075239, filed in the Korean Intellectual Property Office on Jun. 28, 2013, the entire content of which is incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates generally to a method and an apparatus for updating an application, and more particularly, to a method and an apparatus for updating an application according to an update period.

2. Description of the Related Art

Electronic devices provide various and many applications. A user may download a new version of an application after identifying an online market to install latest versions of applications or configure an electronic device to be automatically updated.

When the user manually updates an application, the user may miss a latest update of the application which the user desires. Further, when the application is configured to be automatically updated, a version information notice event of the application is frequently generated in the electronic device, or application data of a new version is received or installed in the electronic device regardless of a user's intention whenever a version of the application is changed.

For example, when a particular application which is used by the user once or twice a month is automatically updated twice or more a month, an application of a version which the user has not used is installed in the electronic device and then the version may be changed into a higher version. In this event, the electronic device may consume communication data and power in order to perform an unnecessary application update. Further, a battery use time of a portable terminal such as a smart phone or a tablet Personal Computer (PC) may be reduced due to a frequent application update.

Accordingly, research on an application update considering both the convenience of the user and energy efficiency is required.

SUMMARY OF THE INVENTION

The present invention has been made to address at least the problems and disadvantages described above, and to provide at least the advantages described below. Accordingly, an aspect of present invention is to provide a method and an apparatus for updating an application according to an update period designated for the application when the application is updated.

Another aspect of the present invention is to provide a method and an apparatus for updating an application which can designate an update period of the application in consideration of a user pattern when the application is updated.

Another aspect of the present invention is to provide a method and an apparatus for updating an application which can configure and control an update period for each of groups distinguished according to the update period.

2

Another aspect of the present invention is to provide a method and an apparatus for updating an application which can control an automatic update based on an update period while not changing a conventional framework for updating the application or minimizing the change of the conventional framework.

In accordance with an aspect of the present invention, a method of updating an application by an electronic device is provided. The method includes activating an automatic update of an application installed in the electronic device; designating the application as one group of one or more groups distinguished according to an update period; and postponing an update of the application before a time point of an update period corresponding to the designated group and updating the application after the time point.

In accordance with another aspect of the present invention, an electronic device updating an application is provided. The electronic device includes a memory for storing an application designated as one group of one or more groups distinguished according to an update period; a communication unit for receiving new version information of the application pushed from an update server and transmitting an update request of the application to the update server; and a controller for controlling to activate an automatic update of the application, and controlling to transmit the update request after a time point of an update period corresponding to the designated group when the new version information is received.

In accordance with another aspect of the present invention, a method of updating an application by an electronic device is provided. The method includes detecting a use pattern of an application installed in the electronic device; designating an update period of the application based on the use pattern; receiving new version information of the application pushed from an update server; and transmitting an update request of the application to the update server after a time point of the designated update period in response to reception of the new version information.

In accordance with another aspect of the present invention, an electronic device updating an application is provided. The electronic device includes a memory for storing an update period of an application; a communication unit for receiving new version information of the application pushed from an update server; and a controller for designating the update period based on a use pattern of the application, and controlling to transmit an update request of the application to the update server after a time point of the update period when the new version information is received.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other aspects, features and advantages of the present invention will be more apparent from the following detailed description in conjunction with the accompanying drawings, in which:

FIG. 1 illustrates an application update system according to the present invention;

FIG. 2 illustrates an update server according to an embodiment of the present invention;

FIG. 3 illustrates an electronic device according to an embodiment of the present invention;

FIG. 4 illustrates electronic device in more detail according to an embodiment of the present invention;

FIG. 5 illustrates a software module for updating an application in the electronic device according to an embodiment of the present invention;

3

FIGS. 6A and 6B illustrate an application update process according to an embodiment of the present invention;

FIG. 7 illustrates a user interface configuring an automatic update of an application according to an embodiment of the present invention;

FIG. 8 illustrates a user interface configuring an application update function based on an update period according to an embodiment of the present invention;

FIG. 9 illustrates a user interface configuring an update period according to an embodiment of the present invention;

FIG. 10 illustrates a user interface configuring an update condition according to an embodiment of the present invention;

FIG. 11 is a flowchart illustrating a method of updating an application in the electronic device according to an embodiment of the present invention;

FIG. 12 is a flowchart illustrating in more detail the method of updating the application in the electronic device according to an embodiment of the present invention;

FIG. 13 is a flowchart illustrating the method of updating the application in the electronic device according to another embodiment of the present invention;

FIG. 14 is a flowchart illustrating the method of updating the application by an update server according to another embodiment of the present invention; and

FIG. 15 is a flowchart illustrating the method of updating the application in the electronic device according to another embodiment of the present invention.

FIGS. 16A-16D illustrate examples of a user interface for manually configuring an application group in an electronic device according to another embodiment of the present invention; and

FIGS. 17A and 17B illustrate examples of a user interface for limiting a data capacity allocated to an application update in an electronic device according to another embodiment of the present invention.

DETAILED DESCRIPTION OF EMBODIMENTS OF THE PRESENT INVENTION

Hereinafter, a method of manufacturing and using the present invention will be described in detail. The terms "unit", "module" and the like used in this specification refer to units processing at least one function or operation and may be implemented by hardware, software, or a combination thereof.

An electronic device according to an embodiment of the present invention may be implemented in various forms. For example, the electronic device described in this specification may include various devices including a portable terminal, a computer, a user interface, a controller, and the like. The portable terminal may be a mobile phone, a smart phone, a laptop computer, a tablet Personal Computer (PC), an e-book terminal, a digital broadcasting terminal, a Personal Digital Assistant (PDA), a Portable Multimedia Player (PMP), a navigation device, a wearable PC, a wrist watch phone, and the like, but is not limited thereto.

Hereinafter, an embodiment of the present invention will be described in more detail with reference to the accompanying drawings to allow those skilled in the art to easily implement the present invention. However, the present invention may be implemented in various different forms and is not limited to embodiments described herein. Further, parts irrelevant to the present invention are omitted in the drawings to make the present invention clear and the same reference numerals are designated to the same or similar components throughout this specification.

4

Hereinafter, it will be described as an example that an electronic device updating an application according to an embodiment of the present invention is a portable terminal, but the present invention is not limited thereto.

FIG. 1 illustrates an application update system according to an embodiment of the present invention. A system for updating an application may include electronic devices 100 and 101 and an update server 200.

The electronic devices 100 and 101 may communicate with the update server 200 through a communication network 105 such as the Internet. A communication line in various mobile communication types may be formed between the communication network 105 and the electronic device 100. Further, the electronic device 101 may be connected to a network 102 managed by an office, home, or public facility through a short-range wireless communication scheme. A gateway 103 may operate to form a communication link between the electronic device 101 included in the network 102 and the communication network 105. For example, the gateway 103 may be an access point which can form a home network.

For example, the electronic devices 100 and 101 may be a smart phone or a tablet Personal Computer (PC). The electronic devices 100 and 101 receive version information from the update server 200 and transmit an update request of an application to the update server 200. The electronic devices 100 and 101 may receive application data corresponding to a new version. Further, the electronic devices 100 and 101 may receive version information of an application from the update server 200 through an application managing application or download an application designated by a user input.

The update server 200 may provide application data (or an application file) and information on the application to the electronic devices 100 and 101. The update server 200 may access an application installed in the electronic devices 100 and 101 or a user account of the electronic devices 100 and 101 to manage information on installed applications. The application server 200 may transmit version information of applications installed in the electronic devices 100 and 101 and receives an update request from the electronic devices 100 and 101. Further, the update server 200 may receive updated (or new) application data from an application provider and store the application data in an application database, so as to manage the application data. The update server 200 may transmit the application data to the electronic devices 100 and 101 according to requests of the electronic devices 100 and 101.

For example, the system for updating the application according to the embodiment of the present invention may include electronic devices based on various platforms, such as an Android platform of Google, an iOS platform of Apple, a Bada platform or a TIZEN platform of Samsung, and a Windows platform of Microsoft. Further, the system may include an update server which can be operated in various types by a service provider, an application provider, or a device manufacturer such as Google, Apple, and Samsung like an application market.

The system according to the embodiment of the present invention is not limited to the above described electronic device or update server and may include an electronic device based on various platforms or an update server operating in various types. Further, even when a platform provider of the electronic device and an operator of the update server are different, the system for updating the application according to the embodiment of the present invention can still operate.

FIG. 2 illustrates an update server according to an embodiment of the present invention.

The update server **200** may include an application database **210**, a server communication unit **220**, and an update controller **230**.

The application database **210** may store information on applications installed in each of electronic devices including the electronic device **100**. Further, the application database **210** may store information on applications corresponding to user accounts including a user account of the electronic device **100**. The user account may be an ID, a password, a phone number, an address, or an e-mail address of the user for an access to the update server **200**. Information on applications corresponding to electronic devices or user accounts may include identification information, version information and the like for distinguishing the applications.

Version information of the application corresponding to the electronic device or the user account managed by the server may include a connection state by the corresponding user account, a version of application data most recently transmitted to the corresponding electronic device, or a past history of transmission (or download) of the application data.

Further, version information of the application corresponding to the electronic device or the user account managed by the server may be received from at least one electronic device registered by the corresponding electronic device or the corresponding user account. For example, the version information may be version information of an installed application reported by the electronic device.

The application database **210** may store application data (or a file) of a new version received from an application producer, a service provider, or a database manager, identification information or version information of the corresponding application, and the like.

When the update controller **230** receives data of an application of a new version, identification information, or version information from the server communication unit **220**, the update controller **230** may control to store the received data or information in the application database **210**.

A method in which the update server **200** transmits version information of the corresponding application to the electronic device **100** to update the application according to an embodiment of the present invention may include a push mode, a pull mode, or a hybrid mode of selectively using the push mode and the pull mode, but the present invention is not limited thereto, and it is noted that various transmission methods can be used. For convenience of the description, the push mode and the pull mode will be described.

In the push mode, the update server **200** may unsolicitedly transmit new version information of the application installed in the electronic device **100** to the electronic device **100** without any request from the electronic device **100**. In the pull mode, the electronic device **100** may make a request for the latest version information of a particular application managed by the update server **200** to the update server **200** and the update server **200** may transmit the latest version information to the electronic device **100** in response to the request.

For example, in the push mode, the update controller **230** may generate new version information of an application of a new version and control the new version information to be pushed to the electronic device corresponding to the corresponding application or at least one electronic device corresponding to a user account. A time point when the update server **200** pushes the new version information to the electronic device **100** after receiving application data of the

new version may be determined by a design of a manager of the update server **200**, a manufacturer or a service provider regardless of a configuration or a condition of the electronic device **100**. For example, the update controller **230** may transmit the new version information to the electronic device immediately whenever the update controller **230** receives application data of a new version.

The server communication unit **220** may transmit new version information (or latest version information) of the application to the electronic device **100** having the corresponding application installed therein. The server communication unit **220** receives an update request of the application from the electronic device **100**. The server communication unit **220** may transmit application data of the new version to the electronic device **100** in response to the update request. Further, before transmitting the latest version information in the pull mode, the server communication unit **220** may receive a version information request of at least one application.

Further, the application database **210** of the update server **200** may record the version of the application data recently transmitted to the electronic device **100** as information on the application installed in the electronic device **100**. The server communication unit **220** may receive information on a group designated for the application from the electronic device **100**. The update controller **230** may determine that the application installed in the electronic device **100** is designated as a particular group among one or more groups based on the information on the designated group. The one or more groups refer to one or more application groups distinguished according to an update period. Each of the groups has an update period. When the update controller **230** may receive a new version of the application from an application producer or a service provider, the update controller **230** may generate new version information of the application. The update controller **230** may control the new version information to be transmitted to the electronic device **100** after a time point of the update period corresponding to the designated group. The server communication unit **220** may receive an update request of the application from the electronic device **100** after the new version information is transmitted. The server communication unit **220** may transmit application data corresponding to the new version information to the electronic device **100**. The update controller **230** may update a version of the application data corresponding to the new version information as information on the application installed in the electronic device **100**.

FIG. 3 illustrates the electronic device according to an embodiment of the present invention. The electronic device **100** may include a memory **110**, a communication unit **120**, and a controller **130**.

The memory **110** may store an application designated as one group among one or more groups distinguished according to an update period. For example, the one or more groups may have different update periods. Further, the update periods corresponding to the one or more groups may be changed through a user interface.

The communication unit **120** may receive new version information of the pushed application from the update server **200** and transmits an update request of the application to the update server **200**.

The controller **130** may control an activation of an automatic update of the application. When new version information is received, the controller **130** may control to transmit an update request after a time point of an update period corresponding to the designated group. Further, the controller **130** may postpone an update of the application before the

time point of the update period corresponding to the designated group. In addition, the controller **130** may detect a use pattern of the application and designate the application as one group of the one or more groups based on the use pattern. The use pattern may refer to at least one of a use frequency and a use time of the application. Further, instead of an operation of the controller **130** designating the application as a particular group based on the use pattern, the group of the application may be designated according to a user's selection input through a user interface unit.

FIG. 4 illustrates another example of the electronic device according to an embodiment of the present invention in more detail. The electronic device **100** may include the memory **110**, the communication unit **120**, and the controller **130**. The electronic device **100** may further include a user interface unit **140**, a sensor unit **150**, and a power supplier **160**.

The memory **110** may store an application designated as one group among one or more groups distinguished according to an update period. Further, the memory **110** may store installed applications distinguished as at least one group. At least one group may correspond to an update period of at least one application included in the corresponding group. At least one application included in a particular group may have a particular update period.

Further, the memory **110** may include a use pattern analysis engine **111** and an update control module **115**. The update control module **115** may include an update policy manager **112**, a download manager **113**, and an update configuration module **114**.

The controller **130** may access the use pattern analysis engine **111** and the update control module **115** from the memory **110** and load an execution task of the controller **130** to perform a calculation and control. The use pattern analysis engine **111** and the update control module **115** operating under a control of the controller **130** will be described in more detail with reference to FIG. 5.

Further, the memory **110** may store a signal or data input/output in accordance with and operation of the communication unit **120**, the user interface unit **140**, or the sensor unit **150** according to a control of the controller **130**. The memory **110** may store a control program and an application for controlling the overall operation of the electronic device **100** or for controlling the controller **130**.

The memory **110** may include a Read Only Memory (ROM), Random Access Memory (RAM), or a memory card (for example, an SD card, a memory stick, or the like) installed in the electronic device **100**. The memory **110** may include a non-volatile memory, a volatile memory, or a Hard Disk Drive (HDD) or a Solid State Drive (SSD).

Further, the memory **110** may store an application configuring an update, applications having various functions such as a navigation function and a game function, images for providing a Graphical User Interface (GUI) related to the applications, databases or data related to a method of processing user information, a document, and a touch input, background images (a menu screen, an idle screen, or the like) or operating programs required for driving the electronic device **100**, and data acquired by the sensor unit **150**.

The memory **110** may include a machine (for example, a computer)-readable medium. The memory **110** may access information from the machine-readable medium and stores the accessed information according to a control of the controller **130**. The machine-readable medium may be a medium providing data to a machine to allow the machine to perform a particular function. For example, the machine-readable medium may be a storage medium. The machine-

readable medium includes at least one of a floppy disk, a flexible disk, a hard disk, a magnetic tape, a magnetic tape, a Compact Disc Read-Only Memory (CD-ROM), an optical disk, a punch card, a paper tape, a Random Access Memory (RAM), a Programmable Read-Only Memory (PROM), an Erasable PROM (EPROM), and a flash-EPROM, but is not limited thereto.

The communication unit **120** may receive new version information on the application pushed from the update server **200**. Also, the communication unit **120** may transmit an update request of the application to the update server **200**, whereby the communication unit **120** may receive application data corresponding to the new version information from the update server **200** in response to the update request.

The communication unit **120** may include a mobile communication module **121** and a short-range communication module **122** for forming a communication link with the update server **200** through the communication network **105**.

The mobile communication module **121** may include a communication module based on a standard such as GSM, WCDMA, HSDPA, LTE, WiMAX, and the like, using a technique such as TDM, TDMA, FDM, FDMA, CDM, COMA, OFDM, OFDMA, MIMO, a smart antenna, and the like.

The short-range communication module **122** may include a communication module of a short-range communication scheme such as WiFi, Bluetooth, Zigbee, Infrared Data Association (IrDA), RFID, or Near Field Communication (NFC). The communication module of the Bluetooth scheme may operate based on a Bluetooth Low Energy (BLE) communication scheme or a Bluetooth Classic communication scheme. The communication module of the WiFi scheme may operate as an access point based on the IEEE 802.11 communication standard or provide access to the access point to form a short-range wireless LAN.

Further, the communication unit **120** may include various communication modules such as a sound wave communication module (not shown) and a visible ray communication module, but is not limited thereto.

The controller **130** may control an activation of an automatic update of the application. The controller **130** may postpone an update of the application before the time point of the update period corresponding to the designated group. The controller **130** may control to transmit an update request after the time point of the update period corresponding to the designated group when receiving new version information.

When receiving application data corresponding to the new version information from the update server **200** in response to the update request, the controller **130** controls to install the received application data.

The controller **130** compares the received new version information with an installed version of the application installed in the electronic device **100**. When the new version information is a higher level version than the installed version, the controller **130** may control to transmit the update request of the application to the update server **200** after the time point of the update period corresponding to the designated group.

In addition, when the application is designated as one group of the one or more groups, the controller **130** may drive a timer for identifying an update time point of the application. The timer may expire when it has the same value as that of the update period corresponding to the designated group. The time point of the update period corresponding to the designated group may be a time point when the timer expires.

Before the time point of the update period corresponding to the designated group, the controller **130** may filter an update request event generated in response to reception of the new version information and controls an update schedule to update the application after the time point of the update period corresponding to the designated group. This will be described in more detail with reference to FIG. 5.

Further, when an update condition is satisfied after the time point of the update period corresponding to the designated group, the controller **130** may control to transmit the update request. For example, the update condition may be at least one of a state where the electronic device **100** is in a WiFi connection, a state where the electronic device **100** is being charged, a state where the electronic device **100** is connected to a designated access point, a state where the electronic device **100** enters a designated time zone, and a state where the electronic device enters a time zone in which the electronic device **100** is not being used for a long time (for example, at bedtime). Further, the controller **130** may receive sensed data from the sensor unit **150** to determine whether the state of the electronic device **100** satisfies the update condition.

For example, the controller **130** may identify the WiFi connection state according to an operation state of the short-range communication module **122** of the communication unit **120** or receive information on whether the electronic device **100** is being charged from the power supplier **160**. In order to determine whether the electronic device **100** is a sleeping state, the controller **130** may record the existence or nonexistence of a user interaction in each time zone to statistically determine whether the electronic device **100** is in the sleeping state or to detect a state of the electronic device **100** or a surrounding environment by using the sensor unit **150** to predict the sleeping state. The controller **130** may determine an intensity of light received by the electronic device **100** by using a camera **151** or an illumination sensor **153** of the sensor unit **150**, or measure a change in light or an image received for a predetermined time to determine whether the electronic device **100** is in the sleeping state or a control intention of the user with respect to a terminal. Further, the controller **130** may detect whether the electronic device **100** has not been used for a long time by using motion data of the electronic device **100** received from a motion sensor **152** of the sensor unit **150** or control intention of the user with respect to the terminal.

In addition, the controller **130** may detect a use pattern of the application. The controller **130** may designate the application as one of the one or more groups based on the use pattern. The use pattern may refer to at least one of a use frequency and a use time of the application.

For example, the use frequency may be a number of user inputs or controls of the application for a predetermined time or a number of executions of the application according to a user input. The use time may be an execution time from an execution of the application to a termination of the application for a predetermined time, or an estimated time during which there is an actual user input or an interaction providing an output. During execution, there are various applications, such as an application requiring a user's control, an application being executed in a background, and an application of which a result is not displayed, so that the use frequency and the use time may be considered together in detecting the user pattern. In a case of an application requiring a user interaction, the controller **130** may estimate a use time based on a use state (for example, whether the user looks at the screen of the electronic device **100** and

whether the user grasps the electronic device **100**) of the electronic device **100** of the user based on data measured by the sensor unit **150**.

Further, the controller **130** may include a Central Processing Unit (CPU), a Read Only Memory (ROM) storing a control program for controlling the electronic device **100**, and a Random Access Memory (RAM) used as a storage area for storing a signal or data input from the outside of the electronic device **100** or for work performed in the electronic device **100**. The CPU may include a multi core such as a dual core, a quadruple core, or an octa core. The CPU, the ROM, and the RAM may be connected to each other through internal buses or implemented in a module form.

The user interface unit **140** may receive a user input for executing and terminating the application. Further, the user interface unit **140** may provide a user interface for changing an update period or configuring an update condition through an update configuration application (or widget).

In addition, the user interface unit **140** may provide a user interface for designating the application installed in the electronic device **100** as a particular group. A group corresponding to the application may be designated according to a user's selection input through the user interface. For example, a function for selecting the update period corresponding to the application may be provided by the user interface. In this case, the controller **130** may generate a group corresponding to the selected update period, update information on the group such that the corresponding application is included in the group corresponding to the selected update period, and control the updated information to be stored in the memory **110**.

The user interface unit **140** may include a display module **141**, a touch panel **142**, and a button **143**.

The display unit **141** may be at least one of a Liquid Crystal Display (LCD), a Thin Film Transistor-Liquid Crystal Display (TFT-LCD), an Organic Light-Emitting Diode (OLED), a flexible display, a 3D display, and an Electro-Phoretic Display (EPD).

The touch panel **142** may be implemented in a resistive type, a capacitive type, an Electro-Magnetic Resonance (EMR) type, an infrared type, or an acoustic wave type.

The display module **141** and the touch panel **142** may be combined to operate as a touch screen. At this time, the user interface unit **140** may further include a touch screen controller. The touch screen may receive at least one touch through a user's body (for example, fingers) or a touchable input unit. Further, the touch screen may include a pen recognition panel which can recognize an input through a pen such as a stylus pen or an electronic pen. In addition, the touch screen may be formed in a structure where a panel detecting an input through a finger or an input unit by a change in induced electromotive force, a display panel, and a panel detecting a contact between the touch screen and a finger or an input unit by a change in resistance or capacitance adhere to each other or are sequentially deposited while some of the panels are spaced apart from each other. The touch screen controller may convert an analog signal received from the touch screen to a digital signal (for example, X and Y coordinates) and transmit the converted digital signal to the controller **130**. The controller **130** may control the touch screen by using the digital signal received from the touch screen controller. Further, the touch screen controller may be included in the controller **130**.

The button **143** may receive a button (key) input from the user for the control of the electronic device **100**. The button **143** may include a physical button (or key) formed on the electronic device **100**, or a virtual button or virtual keypad

displayed on the touch screen. The physical keypad formed in the electronic device 100 may be excluded according to a structure of the electronic device 100.

The sensor unit 150 may include the camera 151, the motion sensor 152, and the illumination sensor 153.

The camera 151 may photograph surroundings of the electronic device 100 or the user. The camera 151 may include a lens system and an image sensor photographing a still image or a video according to a control of the controller 130. Further, a plurality of cameras 151 may be disposed on a front surface and a rear surface of the electronic device 100. The camera 151 may convert an optical signal input through the lens system to an electrical image signal and transmit the electrical image signal to the controller 130 or the display module 141.

The motion sensor 152 may detect a motion of the electronic device 100 (for example, a rotation of the electronic device 100 or an acceleration or vibration applied to the electronic device 100). The motion sensor 152 may include a gyro sensor and an acceleration sensor.

The illumination sensor 153 may detect an amount of ambient light of the electronic device 100.

The sensor unit 150 may further include various sensors such as a proximity sensor detecting whether the user approaches the electronic device 100, a geo-magnetic sensor detecting a point of the compass by using the Earth's magnetic field, and a Global Positioning System (GPS) module. The GPS module may receive radio waves from a plurality of GPS satellites in the Earth's orbit and calculates a position of the electronic device 100 by using Time of Arrival from the GPS satellites to the electronic device 100.

The power supplier 160 may include at least one battery, a power supply circuit, or a battery charging circuit arranged at the housing of the electronic device 100 according to a control of the controller 130. The power supplier 160 may supply power to the electronic device 100. Further, the power supplier 160 may supply power input from an external power source through a wired cable connected to a connector to component modules of the electronic device 100 or a battery. In addition, the power supplier 160 may supply power wirelessly input from an external power source through a wireless charging technology to component modules of the electronic device 100 or control a battery to be charged.

In the electronic device 100 according to another embodiment of the present invention, the controller 130 may detect a use pattern of the installed application. The controller 130 may designate the application as one of the one or more groups based on the use pattern. The communication unit 120 may transmit information on the group designated for the application to the update server 200. For example, the information on the designated group may be a value or an index indicating a group identifier or an update period. Further, the communication unit 120 may receive new version information of the application from the update server 200. The controller 130 may determine whether the new version information is a higher level version than an installed version. When the new version information is a higher level version than the installed version, the communication unit 120 may transmit an update request of the application to the update server 200. The communication unit 120 may receive application data corresponding to the new version information from the update server 200 in response to the update request. The controller 130 may control to install the received application data.

FIG. 5 illustrates a software module for updating the application in the electronic device according to an embodi-

ment of the present invention. The software module illustrated in FIG. 5 may be included in the memory 100 of the electronic device 100 and loaded to the controller 130 of the electronic device 100 to perform a processing operation for updating the application. It can be understood by those skilled in the art that the software module is implemented by a function module of the controller 130.

The controller 130 of the electronic device 100 may access the use pattern analysis engine 111 and the update control module 115 from the memory 110 and load an execution task of the controller 130 to perform a calculation and control for updating the application. The update control module 115 may include the update policy manager 112, the download manager 113, and the update configuration module 114.

The software module may include a kernel 510, a framework 501, and an application 530. The software module may further include a library (not shown) located between the kernel 510 and the framework 501 a runtime module (or a virtual machine) (not shown) for driving an operating system.

The kernel 510 may include device drivers. For example, the device driver of the kernel 510 may include a display driver, a camera driver, a memory driver, and a power management driver. The kernel 510 manages and secures a background thread and a memory and manages the hardware of various devices. For example, the kernel 510 may be a LINUX kernel.

The framework 501 may include the use pattern analysis engine 111, the update policy manager 112, the update configuration module 114, and a framework 520 of a native operating system.

The framework 520 of the native operating system may include an Application Programming Interface (API). For example, the native operating system may be an Android operating system of Google.

Further, the use pattern analysis engine 111, the update policy manager 112, and the update configuration module 114 included in the framework 501 may be the API or include at least one API. For example, the application 530 including the update configuration application (or update configuration widget) may call a kernel or a library through the API of the framework.

The framework 520 of the native operating system includes the download manager 113 generating an update request event in response to new version information received from the update server 200. The framework 501 can access the download manager 113 or includes an update request filter 523 which can transmit/receive an update request event or a control signal generated in the download manager 113. Further, the download manager 113 may include the update request filter 523.

Before the time point of the update period corresponding to the designated group, the update request filter 523 filters the update request event generated in the download manager 113 in response to reception of the new version information, so as to postpone transmission of the update request to the update server 200.

The update policy manager 112 may receive an update request from the update request filter 523 and perform an update request analysis 525. The update policy manager 112 may identify a group including the application corresponding to the update request event through the update request analysis 525. Further, the update policy manager 112 may perform an update policy application and control 526 by controlling the update request filter 523 to update the

corresponding application after the time point of the update period corresponding to the group.

The use pattern analysis engine **111** may detect a use pattern of the application installed in the electronic device **100**. The use pattern analysis engine **111** may determine that an application is included in a particular application group corresponding to a particular update period by analyzing the detected use pattern. That is, the use pattern analysis engine **111** may classify the application as one of the one or more groups. For example, the one or more groups may include an always update group (hereinafter referred to as an “always group”), a sometimes update group (hereinafter referred to as a “sometimes group”), and a rarely update group (hereinafter referred to as a “rarely group”). For example, an application included in the always group may be updated all the time whenever new version information is received, an application included in the sometimes group may have an update period of three days, and an application included in the rarely group may have an update period of seven days.

The update policy manager **112** may perform an update schedule generation **524** according to an update period corresponding to information on the group designated for the application received from the use pattern analysis engine **111**. Further, the update policy manager **112** may perform the update policy application and control **526** to update the application according to the generated update schedule.

An update configuration application (or widget) included in the application **530** may operate while being connected to the update policy manager **112** or the update configuration module **114**. The electronic device **100** may be configured to determine whether to activate an automatic update, whether to activate a smart update considering an update period, an update period, or an update condition through the update configuration application.

For example, referring to FIG. 7, the update configuration application may provide a user interface **710** for determining whether to activate the automatic update of the application on the screen of the electronic device **100**. The user interface **710** may include interaction objects such as radio buttons **711** and **713**, a check box, and the like for receiving a user input. The user interface **710** may provide a function of activating the automatic update of all installed applications. Further, a user interface for selecting whether to activate the automatic update of each of the installed applications may be provided. In addition, an application to be updated in consideration of the update period may be an application of which the automatic update is activated.

Referring to FIG. 8, the electronic device **100** may provide a user interface **810** for configuring whether to automatically or manually configure the update period of the application by using the update configuration application. A smart update **811** refers to an update considering the update period in the automatic update, and information on whether to consider the update period may be expressed by an interaction object such as a check box **813** or a radio button, and a designated matter may be displayed according to an input of the user. Further, the user interface **810** may include an object for selecting an automatic configuration **815** of the update period or a manual configuration **817** by the user.

Referring to FIG. 9, when the manual configuration **817** of FIG. 8 is selected, the electronic device **100** may provide a user interface **910** for the manual configuration of the update period of the application by using the update configuration application. For example, the one or more groups distinguished according to the update period may include a frequently used application group (“always group”) **911**, a sometimes used application group (“sometimes group”) **913**,

and a hardly used application group (“rarely group”) **915**. The user interface **910** may include interaction objects such as radio buttons **921**, **923**, and **925** receiving an update period corresponding to each group from the user or displaying the configured update period.

Further, the electronic device **100** may provide a user interface **950** for configuring an update condition by using the update configuration application. For example, items of an update condition **951** may include a no condition **953** indicating that there is no restrictive condition to perform an update except for the update period, an automatic condition **955** configured by default or having an automatically configured condition as a restrictive condition, and a manual condition **957** having a manually configured restrictive condition according to a user’s selection. Further, when the manual condition **957** is selected, an item of an update manual condition configuration **961** may be displayed.

For example, referring to FIG. 10, when the update manual condition configuration **961** is selected, the electronic device **100** may provide a user interface **1010** for the update manual condition configuration by using the update configuration application. The update condition may include items corresponding to a case **1011** where the electronic device **100** is connected through WiFi, a case **1013** where the electronic device **100** is being charged, a case **1015** wherein the electronic device **100** has not been used for a long time (for example, at bedtime), a case (not shown) where the electronic device **100** is connected to a designated access point, and a case (not shown) where the electronic device **100** enters a designated time zone. Only when a state of the electronic device **100** satisfies an item selected through interaction objects such as check boxes **1021**, **1023**, and **1025**, the application can be updated.

Referring back to FIG. 5, the update configuration module **114** may transmit an automatically or manually configured update period **522** or an update automatic condition configured or update manual condition configured update condition **521** to the update policy manager **112** through the update configuration application (or widget). Further, the update configuration module **114** may control the configured update period **522** to be reflected in the update schedule generation **524** or the configured update condition **521** to be reflected in the update policy application and control **526**.

Based on the update period according to the embodiment of the present invention, the software module for performing the update of the application may be configured in various forms as well as the above described structure. For example, it can be understood by those skilled in the art that at least some of the components included in the software module may be changed or omitted, at least two of the components may be combined, or a new component module may be added or combined to make a reconfiguration.

FIGS. 6A and 6B illustrate an application update process according to an embodiment of the present invention.

The electronic device **100** may include the update control module **115** and the use pattern analysis engine **111** operating according to a control of the controller **130**.

In step **601**, the update control module **115** of the electronic device **100** may control to activate the automatic update.

In step **603**, the use pattern analysis engine **111** of the electronic device **100** may designate the installed application as one of the one or more groups.

In step **605**, the use pattern analysis engine **111** may transmit information on the group designated for the application to the update control module **115**.

15

In step 607, the update control module 115 may maintain at least one application group. For example, the “always group” may include application 1 (hereinafter referred to as “App 1”), the “sometimes group” may include App 2 and App 3, and the “rarely group” may include App 4 and App 6. The application included in the “always group” may be configured to be always updated, an update period of the “sometimes group” may be three days, and an update period of the “rarely group” may be seven days. Further, the update control module 115 may drive a timer for identifying an update period.

In step 609, the update server 200 may transmit new version information to the electronic device 100. For example, the new version information may be version information of App 1, App 2, App 3, and App 4.

In step 611, the update control module 115 may compare the received new version information with installed versions of the applications installed in the electronic device 100. Further, when the new version information is a higher level version than the installed version, the update control module 115 may manage the update such that an update request of the application is transmitted to the update server 200 after the time point of the update period corresponding to the designated group. For example, the update control module 115 may control the update schedule such that the “always group” is updated and updates of other groups are postponed to be updated after the time point of the corresponding update periods. The updates of App 2, App 3, App 4 and App 6 which are not included in the “always group” may be postponed even though new version information is received.

In step 613, the electronic device 100 may transmit an update request to the update server 200. For example, the update request may include information on App 1 which is an application included in an intersection of the new version information and the “always group”.

In step 615, the update server 200 may transmit application data in response to the update request. For example, the application data may be data (or file) of a new version for App 1.

In step 617, the update control module 115 may update the application by controlling the received application data to be installed. For example, App 1 data of the new version may be installed.

Further, in step 621, an application may be additionally installed in the electronic device 100. For example, the added application may be App 7. The use pattern analysis engine 111 may detect a use pattern of the added application.

In step 623, the use pattern analysis engine 111 may designate a group corresponding to the added application based on the detected use pattern. For example, the use pattern analysis engine 111 may designate App 7 as being in the “sometimes group”.

In step 625, the use pattern analysis engine 111 may transmit information on the group designated for the added application to the update control module 115.

In step 627, the update control module 115 may maintain at least one application group. For example, the update control module 115 may add App 7 to the “sometimes group” and manage the “sometimes group”.

In step 629, the update server 200 may transmit new version information to the electronic device 100. For example, the new version information may be version information of App 5, App 6, and App 7.

In step 631, the update control module 115 may compare the received new version information with installed versions of the applications installed in the electronic device 100. Further, when the new version information is a higher level

16

version than the installed version, the update control module 115 may manage the update such that an update request of the application is transmitted to the update server 200 after the time point of the update period corresponding to the designated group. For example, the update control module 115 may control the update schedule such that the “always group” is updated and updates of other groups are postponed to be updated after the time point of the corresponding update periods.

In step 633, the electronic device 100 may transmit an update request to the update server 200. For example, the update request may include information on App 5 which is an application included in an intersection of the new version information and the “always group”.

In step 635, the update server 200 may transmit application data in response to the update request. For example, the application data may be data (or a file) of a new version for App 5.

In step 637, the update control module 115 may update the application by controlling the received application data to be installed. For example, App 5 data of the new version may be installed.

Further, in step 641, after the time point of the update period corresponding to a particular group, the update control module 115 may manage the update such that an update of the particular group is performed. For example, after three days corresponding to the update period of the “sometimes group”, the update control module 115 may control to update App 2, App 3, and App 7 which are applications included in the new version information received in steps 609 and 629 and the sometimes group.

In step 643, the electronic device 100 may transmit an update request to the update server 200. For example, the update request may include information on App 2, App 3, and App 7.

In step 645, the update server 200 may transmit application data in response to the update request. For example, the application data may be data (or file) of new versions for App 2, App 3, and App 7.

In step 647, the update control module 115 may update the application by controlling the received application data to be installed. For example, App 2 data, App 3 data, and App 7 data of the new versions may be installed.

Further, in step 651, after the time point of the update period corresponding to another particular group, the update control module 115 may manage the update such that an update of another particular group is performed. For example, after seven days corresponding to the update period of the “rarely group”, the update control module 115 may control to update App 4 and App 6 which are applications included in the new version information received in steps 609 and 629 and the “sometimes group”.

In step 653, the electronic device 100 may transmit an update request to the update server 200. For example, the update request may include information on App 4 and App 6.

In step 655, the update server 200 may transmit application data in response to the update request. For example, the application data may be data (or file) of new versions for App 4 and App 6.

In step 657, the update control module 115 may update the application by controlling the received application data to be installed. For example, App 4 data and App 6 data of the new versions may be installed.

FIG. 11 is a flowchart illustrating a method of updating the application in the electronic device according to an embodiment of the present invention.

In step **1105**, the electronic device **100** may activate an automatic update of the application installed in the electronic device **100**.

In step **1110**, the electronic device **100** may designate the application as one of the one or more groups distinguished according to the update period. For example, the designation of the application as a particular group may be automatically made by the electronic device **100** based on the use pattern of the application or a group corresponding to the application may be designated according to a user's selection input through the user interface.

In step **1115**, the electronic device **100** may postpone the update of the application until the time point of the update period corresponding to the designated group and updates the application after the time point of the update period corresponding to the designated group.

FIG. **12** is a flowchart illustrating in more detail the method of updating the application in the electronic device according to an embodiment of the present invention.

In step **1205**, the electronic device **100** may activate an automatic update of the application installed in the electronic device **100**.

In step **1210**, the electronic device **100** may detect a use pattern of the application. The use pattern may refer to at least one of a use frequency and a use time of the application.

In step **1215**, the electronic device **100** may designate the application as one of the one or more groups distinguished according to the update period based on the use pattern. For example, the one or more groups may have different update periods and the update periods corresponding to the one or more groups may be changed through the user interface. Further, the electronic device **100** may drive a timer for identifying the update period.

In step **1220**, the electronic device **100** may receive new version information of the application pushed from the update server **200**.

In step **1225**, the electronic device **100** may determine whether the new version information is a higher level version than an installed version. When the level of the new version information is lower than or equal to the level of the installed version, the update of the application is terminated.

When the level of the new version information is higher than the level of the installed version, the electronic device **100** may determine whether a timer corresponding to a designated group has expired to determine whether the time point of the update period corresponding to the designated group has arrived in step **1230**.

When the timer has not expired, the electronic device **100** controls the update schedule such that the application is updated after the timer expires by filtering an update request event generated in response to reception of the new version information in step **1235**.

When the timer has expired, the electronic device **100** determines whether an update condition is satisfied if the update condition is configured other than for a condition that the update period corresponding to the designated group has passed in step **1240**. The update condition may be a state where the electronic device **100** is connected through WiFi, a state where the electronic device **100** is being charged, a state where the electronic device **100** is connected to a designated access point, and a state where the electronic device **100** enters a designated time zone or a state where the electronic device **100** enters a time zone where the electronic device **100** is not used for a long time. Further, when the update condition is not configured, step **1240** may be omitted.

When the update condition is not satisfied, the update may be postponed until the update condition is satisfied in step **1240**. Further, when other new version information is received from the update server **200** before the update condition is satisfied, the electronic device **100** may control the schedule such that the update into other new version information is made when the update condition is satisfied.

When the update condition is satisfied, the electronic device **100** may transmit an update request of the application to the update server **200** in step **1245**. Further, the electronic device **100** may re-drive a timer corresponding to the update period corresponding to the designated group. The time point when the timer is re-driven may be a time point equal to a time point when the update period ends, a time point when application data of a new version is received, or a time point when application data is installed in the electronic device **100** according to a selection by a service provider, a producer, or a user. In addition to a method of managing the update period in the unit of groups, a method of managing the update period according to the timer corresponding to each of the applications may be applied.

In step **1250**, the electronic device **100** may receive application data corresponding to the new version information from the update server **200**.

In step **1255**, the electronic device **100** may install the received application data.

In FIG. **12**, the method of updating the application may correspond to the push mode of the method in which the update server **200** transmits version information of the corresponding application to the electronic device **100**.

Hereinafter, a case where the electronic device **100** operates in accordance with the pull mode will be briefly described.

After performing steps **1205** to **1215**, the electronic device **100** may determine whether the update period corresponding to the designated group has passed by determining whether the timer has expired in step **1230**. When the timer has expired, the electronic device **100** may transmit a version information request of the application to the update server **200** after the time point when the timer expires.

The electronic device **100** may receive version information of the application from the update server **200** in response to the version information request. In step **1225**, the electronic device **100** may determine whether the level of the new version information is a higher level version than a level of an installed version. When the level of the new version information is higher than the installed version, the electronic device **100** transmits an update request of the application to the update server in step **1245**. Thereafter, the electronic device **100** may perform steps **1250** to **1255**.

FIG. **13** is a flowchart illustrating the method of updating the application in the electronic device according to another embodiment of the present invention.

In step **1305**, the electronic device **100** may detect a use pattern of the application installed in the electronic device **100**. The use pattern may refer to at least one of a use frequency and a use time of the application.

In step **1310**, the electronic device **100** may designate an update period of the application based on the use pattern. For example, each application may have an update period independently managed regardless of another application, and the update period of the application may be managed by using a timer corresponding to the update period.

In step **1315**, the electronic device **100** may receive new version information of the application pushed from the update server **200**.

In step 1320, the electronic device may control the update request of the application to be transmitted to the update server 200 after the time point of the designated update period in response to reception of the new version information. Before the time point of the designated update period, the electronic device 100 may postpone transmission of the update request of the application.

FIG. 14 is a flowchart illustrating the method of updating the application by the update server according to another embodiment of the present invention.

In step 1405, the update server 200 may record version information of the application data recently transmitted to the electronic device 100 as information on the application installed in the electronic device 100.

In step 1410, the update server 200 may receive information on a group designated for the application from the electronic device 100. The update server 200 may manage one or more groups and stores information on applications included in each of the groups. Each of the groups corresponds to an update period. The information on the designated group may include Identification information of the application, information on a group, or update period information.

When a new version of the application is received from an application producer or a service provider, the update server 200 may generate new version information of the application in step 1415.

In step 1420, the update server 200 may control the new version information to be transmitted to the electronic device 100 after the time point of the update period corresponding to the designated group. Even though the new version is received in step 1415, the update server 200 may postpone transmission of the new version information.

After the time point of the update period corresponding to the designated group, the update server 200 may transmit the new version information to the electronic device 100.

After transmitting the new version information, the update server 200 may receive an update request of the application from the electronic device 100 in step 1425.

In step 1430, the update server may transmit application data corresponding to the new version information to the electronic device 100.

In step 1435, the update server 200 may record or updates the new version information as information on the application installed in the electronic device 100.

FIG. 15 is a flowchart illustrating the method of updating the application in the electronic device according to another embodiment of the present invention.

In step 1505, the electronic device 100 may detect a use pattern of the application installed in the electronic device 100.

In step 1510, the electronic device 100 may designate the application as one of the one or more groups based on the use pattern.

In step 1515, the electronic device 100 may transmit information on a group designated for the application to the update server 200. The information on the designated group may include identification information of the application, information on a group, or update period information. The update server 200 may manage one or more groups and stores information on applications included in each of the groups. Each of the groups corresponds to an update period.

In step 1520, the electronic device 100 may receive new version information of the application pushed from the update server 100. A time point when the new version information is pushed may be after a time point of the update period corresponding to the designated group.

In step 1525, the electronic device 100 may determine whether the level of the new version information is higher than a level version of an installed version.

When the level of the new version information is higher than the level of the installed version, the electronic device 100 may transmit an update request of the application to the update server 200 in step 1530.

In step 1535, the electronic device 100 may receive application data corresponding to the new version information from the update server 200.

In step 1540, the electronic device 100 may install the received application data.

Referring to FIGS. 16A and 16B, in the electronic device 100 according to another embodiment of the present invention, the user may directly configure an application group by using an update configuration application and manually configure an update period of the configured application group.

Referring to FIG. 16A, the electronic device 100 may provide a user interface 1610 by which the user can directly configure an application group by using an update configuration application. The user may manually generate one or more application groups 1611, 1613, and 1615 on the user interface 160. Whether to insert the application groups 1611, 1613, and 1615 generated by the user into a group list may be displayed by interaction objects, for example, check boxes 1612, 1614, and 1616, a radio button and the like, or displayed in a manner designated according to an input by the user. As described above, with respect to an application included in the application group directly configured by the user, the controller 130 may not perform an operation for detecting a use pattern of the application.

Referring to FIG. 16B, when one update group 1613 is designated from the update groups directly configured by the user, the electronic device 100 may provide a user interface 1620 for configuring an application included in a designated application group by using an update configuration application. Further, whether to perform an automatic update on the corresponding application group may be displayed by interaction objects such as a check box 1621, a radio button and the like, or displayed in a manner designated according to an input by the user. The user may select one or more applications 1622, 1624, and 1626 included in the corresponding application group on the user interface 1620. Whether to insert the applications 1622, 1624, and 1626 selected by the user into the corresponding application group may be displayed by interaction objects, for example, check boxes 1623, 1625, and 1627, a radio button and the like, or displayed in a manner designated according to an input by the user.

Referring to FIG. 16C, when an automatic update is configured for one update group 1613 of the update groups directly configured by the user, the electronic device 100 may provide a user interface 1630 which can make a configuration of whether to automatically or manually configure an application update period of the corresponding update group by using an update configuration application. In the automatic update, whether to perform the update in consideration of the period may be displayed by interaction objects such as a check box 1631, a radio button and the like, or displayed in a manner designated according to an input by the user. Further, the user interface 1630 may include an object for selecting an automatic configuration 1362 of the update period or a manual configuration 1633 by the user.

Referring to FIG. 16D, when the manual configuration 1633 is selected, the electronic device 100 may provide a user interface 1640 for an application update period manual

configuration by using an update configuration application. For example, the user may make a designation of whether to allow the application to always perform a latest update **1641** or perform a regular update **1642** according to a configured period through the user interface **1640**. When the regular update **1642** is designated, the user interface **1640** may display selectable update periods **1643**, **1644**, **1645**, **1646**, and **1647** to allow the user to select one and allow the user to receive an update period.

Referring to FIGS. **17A** and **17B**, the electronic device **100** according to another embodiment of the present invention may limit a data capacity allocated to an application update to a desired size by using an update configuration application. For example, when a manual update is configured, the electronic device **100** may limit the data capacity allocated to the application update in order to allow the user to intentionally determine whether to perform the update according to a memory space. The configuration of the manual update may be commonly applied to all application groups or applied to a designated application group. When the manual update configuration is applied to the designated application group, the user may actively control whether to perform the update in consideration of a memory space when updating the corresponding application group.

Referring to FIG. **17A**, the electronic device **100** may provide a user interface **1711** which can select whether to limit a data capacity allocated to an application update by using an update configuration application. The user interface **1710** may provide an item **1711** for limiting the data capacity allocated to the update, and whether to limit the data capacity may be displayed by interaction objects such as a check box **1712**, a radio button and the like, or displayed in a manner designated according to an input by the user. The user interface **1711** may provide the user with a currently allocated memory space **1713** to allow the user to determine whether to limit the data capacity allocated to the update with reference to the provided memory space **1713**.

Referring to FIG. **17B**, when the limit on the data capacity allocated to the update is designated, the electronic device **100** may provide a user interface **1720** for configuring the data capacity allocated to the application update by using an update configuration application. The user may designate data capacities **1721**, **1722**, **1723**, **1724**, and **1725** allocated to the application update on the user interface **1720**. Alternatively, the user may input a desired data capacity into the user interface **1720**.

According to an embodiment, when the data capacity allocated to the update is exceeded while the application update is manually performed, the update configuration application may provide a notification thereof to the user through a sound, a vibration, or a message. In this case, the electronic device **100** may stop or end the application update automatically or according to a control of the user.

According to another embodiment, when the application update is manually performed and a size of a corresponding update file exceeds the remaining data capacity allocated to the update through the identification of the update file, the update configuration application may provide a notification thereof to the user through a sound, a vibration, or a message. In this case, the electronic device **100** may stop or end the application update automatically or according to a control of the user.

The user interface described with reference to FIGS. **7** to **10** may be randomly changed by a producer, a service provider, or a user, and various user interfaces may be provided according to convenience and use purposes.

Further, orders of operations described as the process or method of updating the application with reference to FIGS. **6A** and **6B** and FIGS. **11** to **15** may be randomly changed or some of the operations may be omitted. Further, the operations may be performed by complexly combining some of the above described embodiments. It can be understood by those skilled in the art that the user interface may be changed in various forms according to the change or the omission of the operations.

Further, it can be understood by those skilled in the art that programs in the embodiment described through FIG. **5** and FIGS. **11** to **17** may be implemented by software, hardware, or a combination thereof. In addition, the program according to the embodiment may be recorded in a recording medium or may be downloaded to the electronic device or the update server from a server or a computer through a communication network.

While the present invention has been shown and described with reference to certain embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the present invention as defined by the appended claims.

What is claimed is:

1. A method of updating an application by an electronic device, the method comprising:
 - activating an automatic update of an application installed in the electronic device;
 - designating the application as one group of a plurality of groups based on at least one of a use frequency of the application and a use time of the application, which are determined based on a user interaction, which includes one of whether the user approaches a screen of the electronic device and whether the user interacts with the electronic device, detected by a sensor of the electronic device, each group of the plurality of groups corresponding to a different recurring update period;
 - receiving new version information of the application pushed from an update server;
 - controlling an update schedule such that the application is updated after a time point by filtering an update request event generated in response to reception of the new version information; and
 - postponing the automatic update of the application until the time point of the recurring update period corresponding to the designated group of the application and updating the application after the time point by transmitting the filtered update request of the application to the update server.
2. The method of claim 1, wherein designating the application as the one group comprises at least one of:
 - detecting a use pattern of the application and designating the application as the one group of the plurality of groups based on the detected use pattern; and
 - designating the application as the one group of the plurality of groups based on a user input, wherein the use pattern indicates at least one of the use frequency of the application and the use time of the application.
3. The method of claim 1, wherein the recurring update period corresponding to the designated group can be changed through a user interface.
4. The method of claim 1, wherein updating the application comprises updating the application when an update condition is satisfied after the time point.
5. The method of claim 4, wherein the update condition is at least one of a state where the electronic device is con-

23

ected through WiFi, a state where the electronic device is being charged, a state where the electronic device is connected to a designated access point, and a state where the electronic device enters a designated time zone, and a state where the electronic device enters a time zone and the electronic device is not used for a long time.

6. The method of claim 1, wherein designating the application as the one group comprises:

driving a timer for identifying an update time point of the application,

wherein the timer expires when the timer has a value equal to the recurring update period corresponding to the designated group, and the time point of the recurring update period corresponding to the designated group is a time point when the timer expires.

7. The method of claim 1, wherein updating the application comprises:

transmitting a version information request of the application to an update server after the time point of the recurring update period corresponding to the designated group; and

receiving version information of the application from the update server.

8. The method of claim 1, further comprising:

activating a manual update of the application installed in the electronic device;

limiting a data capacity allocated to the manual application update to a predetermined capacity in a memory of the electronic device;

updating the application based on a user's command; and

providing a notification when the data capacity allocated to the manual application update is exceeded during the manual application update based on the user's command or when an update file exceeds a remaining update allocation space.

9. An electronic device updating an application, the electronic device comprising:

memory for storing an application designated as one group of a plurality of groups based on at least one of a use frequency of the application and a use time of the application, which are determined based on a user interaction, which includes one of whether the user approaches a screen of the electronic device and whether the user interacts with the electronic device, detected by a sensor of the electronic device, each group of the plurality of groups corresponding to a different recurring update period;

a communication unit configured to receive new version information of the application pushed from an update server, and to transmit an update request of the application to the update server; and

a controller configured to control to activate an automatic update of the application, to control to filter the update request generated in response to reception of the new version information, and to control to transmit the filtered update request after a time point of the recurring update period corresponding to the designated group of the application, in response to receiving the new version information.

10. The electronic device of claim 9, wherein the controller detects a use pattern of the application and designates the application as the one group of the plurality of groups based on the detected use pattern or based on a user input, and

wherein the use pattern indicates at least one of the use frequency of the application and the use time of the application.

24

11. The electronic device of claim 9, wherein the recurring update period corresponding to the designated group can be changed through a user interface.

12. The electronic device of claim 9, wherein the controller is configured to control to transmit the update request when an update condition is satisfied after the time point.

13. The electronic device of claim 12, wherein the update condition is at least one of a state where the electronic device is connected through WiFi, a state where the electronic device is being charged, a state where the electronic device is connected to a designated access point, and a state where the electronic device enters a designated time zone, and a state where the electronic device enters a time zone and the electronic device is not used for a long time.

14. The electronic device of claim 9, wherein the controller is configured to drive a timer for identifying an update time point of the application when the application is designated as the one group of the plurality of groups, the timer expires when the timer has a value equal to the recurring update period corresponding to the designated group, and the time point of the recurring update period corresponding to the designated group is a time point when the timer expires.

15. The electronic device of claim 9, wherein, before the time point of the recurring update period corresponding to the designated group, the controller is configured to control an update schedule such that the application is updated after the time point by filtering an update request event generated in response to reception of the new version information.

16. The electronic device of claim 9, wherein the controller is configured to activate a manual update of the application installed in the electronic device, limit a data capacity allocated to the manual application update to a predetermined capacity in the memory of the electronic device, and, when the application is updated based on a user's command, providing a notification if the data capacity allocated to the manual application update is exceeded during the manual application update based on the user's command or an update file exceeds a remaining update allocation space.

17. A method of updating an application by an electronic device, the method comprising:

identifying at least one of a use frequency of an application installed in the electronic device and a use time of the application, which are determined based on a user interaction, which includes one of whether the user approaches a screen of the electronic device and whether the user interacts with the electronic device, detected by a sensor of the electronic device;

designating a recurring update period of the application based on at least one of the use frequency of the application and the use time of the application;

receiving new version information of the application pushed from an update server;

controlling an update schedule such that the application is updated until a time point of the designated recurring update period by filtering an update request generated in response to reception of the new version information; and

transmitting the filtered update request of the application to the update server until the time point of the designated recurring update period, in response to reception of the new version information.

18. An electronic device updating an application, the electronic device comprising:

a memory for storing a recurring update period of the application;

a communication unit configured to receive new version information of the application pushed from an update server; and
controller configured to designate the recurring update period based on at least one of a use frequency of the application and a use time of the application, which are determined based on a user interaction, which includes one of whether the user approaches a screen of the electronic device and whether the user interacts with the electronic device, detected by a sensor of the electronic device, to control to filter the update request generated in response to reception of the new version information, and to control to transmit the filtered update request of the application to the update server after a time point of the recurring update period, in response to receiving the new version information.

* * * * *