

(51) International Patent Classification:
G02B 3/14 (2006.01)(21) International Application Number:
PCT/US2010/052905(22) International Filing Date:
15 October 2010 (15.10.2010)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/251,819 15 October 2009 (15.10.2009) US
12/904,736 14 October 2010 (14.10.2010) US(71) Applicant (for all designated States except US):
ADLENS BEACON, INC. [US/US]; 33 Wood Avenue
South, Suite 600, Iselin, NJ 08830 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **GUPTA, Amitava** [US/US]; 5322 Fox Den Road, Roanoke, VA 24018 (US). **EGAN, William** [US/US]; 2105 North Nowlin Trail, Jackson, WY 83001 (US). **NIBAUER, Lisa** [US/US]; 1 Crescent Place, Short Hills, NJ 07078 (US). **DECKER, Bruce** [US/US]; 6645 Upper York Road, Solebury, PA 18963 (US). **SCHNELL, Urban** [CH/CH]; Eichgutweg 16, CH-3053 Munchenbuchsee (CH). **HAROUD, Karim** [CH/CH]; Bourg Du Village 6, CH-1512 Chavannes-sur-moudon (CH). **LOSER, Pascal** [CH/CH]; Gerechtigkeitsgasse 8, CH-3011 Bern (CH). **SAINT-GHISLAIN, Michel** [CH/CH]; Brugerastrasse 54, CH-3186 Dudingén (CH). **SENATORE, Daniel** [US/US]; 260 Bay, Apt. 101, San Francisco, CA 94133 (US).**PETERSON, Matthew, Wallace** [US/US]; 115 Nevada,
San Francisco, CA 94110 (US).(74) Agents: **RAY, Michael, B.** et al.; Sterne, Kessler, Gold-
stein & Fox, P.L.L.C., 1100 New York Avenue, N.W.,
Washington, DC 20005-3934 (US).(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,
CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO,
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP,
KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD,
ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI,
NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD,
SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG,
ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).**Published:**

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments (Rule 48.2(h))

(54) Title: FLUID FILLED LENS RESERVOIR SYSTEM AND MANUFACTURING METHOD OF THE RESERVOIR SYSTEM




FIG. 2

(57) Abstract: Disclosed are apparatuses and manufacturing methods for a fluid filled lens reservoir system. The eyeglass reservoir system includes a temple piece having a cavity, a bladder positioned within the cavity and configured to repeatedly compress and relax, the bladder being made of a flexible material, and a connecting tube coupled to an inlet port of a lens module and to the bladder, configured to carry a fluid between the bladder and a fluid filled lens cavity of the lens module. The eyeglass reservoir system further comprises a compression arm contacting the bladder and configured to transmit force from an actuator to the bladder to cause movement of the fluid between the bladder and the connecting tube. The bladder and connecting tube are made of a flexible material such as polyvinylidene difluoride. The connecting tube further comprises a flared end configured to couple to the inlet port of the lens module.

FLUID FILLED LENS RESERVOIR SYSTEM AND MANUFACTURING METHOD OF THE RESERVOIR SYSTEM

CROSS REFERENCE TO RELATED APPLICATIONS

- [0001] This application claims priority to U.S. Provisional Patent Application No. 61/251,819, filed October 15, 2009, which is incorporated herein by reference in its entirety.

BACKGROUND

Field

- [0002] Embodiments of the present invention relate to fluid-filled lenses and in particular to a reservoir for storing and supplying a fluid.

Background Art

- [0003] Basic fluid lenses have been known since about 1958, as described in U.S. Pat. No. 2,836,101, incorporated herein by reference in its entirety. More recent examples may be found in “Dynamically Reconfigurable Fluid Core Fluid Cladding Lens in a Microfluidic Channel” by Tang et al., Lab Chip, 2008, vol. 8, p. 395, and in WIPO publication WO2008/063442, each of which is incorporated herein by reference in its entirety. These applications of fluid lenses are directed towards photonics, digital phone and camera technology and microelectronics.
- [0004] Fluid lenses have also been proposed for ophthalmic applications (see, e.g., U.S. Patent No. 7,085,065, which is incorporated herein by reference in its entirety). In all cases, the advantages of fluid lenses including a wide dynamic range, ability to provide adaptive correction, robustness and low cost have to be balanced against limitations in aperture size, possibility of leakage, and consistency in performance. The '065 patent, for example, has disclosed several improvements and embodiments directed towards effective containment of the fluid in the fluid lens to be used in ophthalmic applications, although not limited to them (see, e.g., U.S. Patent No. 6,618,208, which is incorporated by reference in its entirety). Power adjustment in fluid lenses has been effected by injecting additional fluid into a lens cavity, by electrowetting, by application of ultrasonic

impulse, and by utilizing swelling forces in a cross-linked polymer upon introduction of a swelling agent such as water.

SUMMARY

- [0005] In one embodiment of the present invention, the state of inflation of a sealed fluid filled lens is controllably altered by compressing a fluid filled reservoir that is sealed at one end and is connected to the cavity of the fluid filled lens on the other.
- [0006] In an embodiment, the fluid filled reservoir includes two sections, a wider section providing the space for storage of excess fluid, while a narrower section functions as a connecting tube between said wider section and an inlet to the sealed lens cavity being threaded through the hinge. The reservoir may be fabricated of a polymer that is impermeable to the fluid and formed to accommodate the bending and unbending of a hinge.
- [0007] An embodiment of the present invention includes an eyeglass reservoir system for storing fluid to supply a fluid filled lens of a pair of eyeglasses. The eyeglass reservoir system may include a temple piece having a cavity, a bladder positioned within the cavity and configured to repeatedly compress and relax, the bladder being made of a flexible material, and a connecting tube coupled to an inlet port of a lens module and to the bladder, configured to carry a fluid between the bladder and a fluid filled lens cavity of the lens module. The eyeglass reservoir system may further include a compression arm contacting the bladder and configured to transmit force from an actuator to the bladder. The bladder and connecting tube may be separately formed and joined together or may be two portions of a single tube. The shape of the bladder may be cylindrical or ellipsoidal with the bladder being wider, respectively, than the connecting tube. The bladder and connecting tube are made of a flexible material such as polyvinylidene difluoride. The connecting tube may further include a flared end configured to couple to the inlet port of the lens module.
- [0008] An embodiment of the present invention additionally includes an apparatus, including a flexible bladder configured to repeatedly compress and relax, a flexible connecting tube having a flared end and a non-flared end, the non-flared end coupled to the bladder, the connecting tube configured to narrow and extend a passage length of the

bladder, wherein the connecting tube is further configured to carry a fluid from and to the bladder; and a compression arm contacting the bladder and configured to apply pressure to the bladder.

[0009] Additionally, an embodiment of the present invention includes a device manufacturing method, including placing a first unprocessed tube of a first processable material having a first diameter and first and second openings at opposite ends over a tubular reservoir profile having a cylindrical or elliptical cross-section, such that one end of the first unprocessed tube associated with the first opening and one end of the tubular reservoir profile are approximately even. The device manufacturing method further includes processing the first processable material such that a first processed tube forms around the tubular reservoir profile and contracts, at the end associated with the second opening, smaller than the tubular reservoir profile to create a reduced diameter opening. Another step of the device manufacturing method includes removing the tubular reservoir profile from the first processed tube and sealing the first opening. Additionally, the device manufacturing method includes placing a first opening of a second unprocessed tube of a second diameter over the reduced diameter opening of the first processed tube, the second unprocessed tube being made of a second processable material. Still another step of the device manufacturing method includes placing an inlet profile in a second opening of the second unprocessed tube and processing the second processable material such that a second processed tube forms around the reduced opening of the first tube and the inlet profile to form a flared opening. The device manufacturing method further includes placing a first adhesive around an inside rim of the first opening of the first processed tube and placing a second adhesive around an outside rim of the reduced diameter opening, or an inside rim of the first opening of the second processed tube, or both.

[0010] Further features and advantages of the invention, as well as the structure and operation of various embodiments of the present invention, are described in detail below with reference to the accompanying drawings. It is noted that the invention is not limited to the specific embodiments described herein. Such embodiments are presented herein for illustrative purposes only. Additional embodiments will be apparent to persons skilled in the relevant art(s) based on the teachings contained herein.

BRIEF DESCRIPTION OF THE DRAWINGS/FIGURES

- [0011] The accompanying drawings, which are incorporated herein and form a part of the specification, illustrate the present invention and, together with the description, further serve to explain the principles of the invention and to enable a person skilled in the pertinent art to make and use the invention.
- [0012] Figure 1 partially depicts an exemplary pair of fluid-filled eyeglasses, according to an embodiment of the invention.
- [0013] Figure 2 illustrates an exploded view of one of the temple pieces of the fluid-filled eyeglasses shown in Figure 1, according to an embodiment.
- [0014] Figure 3 illustrates a three dimensional view of a reservoir according to an embodiment, showing a relatively wide section and a relatively narrow section.
- [0015] Figures 4A-4D are dimensioned drawings of a reservoir such as the reservoir shown in Figure 3, according to an embodiment of the present invention.
- [0016] Figure 5 depicts the reservoir in an exploded view of the sealed lens module, showing connecting ends of a narrow section of a reservoir and an inlet port located on a rigid lens of a sealed lens module, according to an embodiment of the present invention.
- [0017] Figures 6A-6D illustrate an exemplary method for fabricating a reservoir, according to an embodiment.
- [0018] Figures 7A-7D illustrate another exemplary method of reservoir fabrication, according to an embodiment.
- [0019] Figure 8 shows results of optical tests performed to calculate the volume of a wide section of a reservoir that is in contact with a compressing means, according to an embodiment of the present invention. The data have been used to calculate the volume of the fluid required to be injected into the fluid filled lens cavity for each diopter of power increase, given a fluid filled lens of geometry shown in Figure 5.

DETAILED DESCRIPTION

- [0020] Although specific configurations and arrangements are discussed, it should be understood that this is done for illustrative purposes only. A person skilled in the pertinent art will recognize that other configurations and arrangements can be used

without departing from the spirit and scope of the present invention. It will be apparent to a person skilled in the pertinent art that this invention can also be employed in a variety of other applications.

[0021] It is noted that references in the specification to "one embodiment," "an embodiment," "an example embodiment," etc., indicate that the embodiment described can include a particular feature, structure, or characteristic, but every embodiment may not necessarily include the particular feature, structure, or characteristic. Moreover, such phrases do not necessarily refer to the same embodiment. Further, when a particular feature, structure or characteristic is described in connection with an embodiment, it would be within the knowledge of one skilled in the art to effect such feature, structure or characteristic in connection with other embodiments whether or not explicitly described.

[0022] Design of a pair of eyeglasses including fluid filled lenses may utilize seamless integration of all of the components of the fluid filled lens into an eyeglass frame without compromising either the adjustability of optical power of the fluid filled lens or the frame and temple designs, both from the ergonomic and aesthetic perspectives.

[0023] A pair of eyeglasses having fluid filled lenses may include, for example and without limitation: (1) two fluid filled lens modules; (2) two connecting tubes, each connecting the inlet port of a lens module to a corresponding reservoir to form a sealed system and threaded through a hinge; (3) two fluid filled reservoirs made of a flexible material that can be compressed and relaxed reversibly for a large number of cycles, connected to the lens modules by means of the connecting tubes; (4) hinges that provide a channel that houses the connecting tube and allows it to flex during the operation of the hinge without causing the connecting tube to crimp; and (5) two actuators that compress the respective reservoirs reversibly and controllably by means of movement of, for example and without limitation, a wheel or a screw, located on the side of each temple piece.

[0024] A design that provides the ability to separately adjust the right and the left optic by the wearer is deemed ergonomically superior than a design that requires adjustment of the optics in tandem, since it leads to direct tactile connection between the extent of adjustment of the actuator position and the clarity and magnification of the retinal image formed by the fluid filled lenses.

[0025] Figure 1 is a partial illustration of an exemplary eyeglass assembly 100 with a fluid-filled lens, according to an embodiment of the present invention. The eyeglasses 100 include first and second temple pieces 120, a lens frame 140, hinges 160 coupling the temple pieces 120 to the frame 140, and at least one liquid-filled lens assembly 180.

[0026] Figure 2 illustrates an exploded detail of one of the temple pieces 120, according to an embodiment of the present invention. Temple piece 120 includes two outer shell pieces 220a and 220b. When the two outer shell pieces 220a and 220b are fitted together, they create a cavity 230 within the body of temple piece 120. A reservoir assembly 240 can be sized, shaped, and placed within cavity 230. In an embodiment, temple piece 120 also includes an assembly of a compression arm 260, a flexible tab 270, a pin 272 holding tab 270 in place, and an actuator 280. In one example, this assembly movably contacts a wider portion of reservoir assembly 240. In an embodiment, compression arm 260 is shaped such that in the confined environment of cavity 230 of the assembled temple piece 120, the contact with the wider portion of reservoir assembly 240 causes compression of the reservoir assembly 240 and pushes fluid out of said reservoir assembly. Conversely, in an embodiment, lessening of the contact between compression arm 260 and reservoir assembly 240 decompresses reservoir assembly 240 and causes fluid to be drawn into reservoir assembly 240.

[0027] Figure 3 illustrates an exemplary reservoir assembly 240 from multiple perspectives, according to an embodiment of the present invention. Reservoir assembly 240 includes a bladder 310, a connecting tube 320, a joint 330, a sealed end 340, and an open end 350. In one embodiment, reservoir 240 is typically of a bladder configuration 310, shaped to fit within temple piece 120 of an eyeglass assembly. Bladder 310 is positioned in cavity 230 inside temple piece 120. In an embodiment, bladder 310 contacts a thin, stiff movable metal plate, referred to herein as compression arm 260 (shown in Figure 2), along its length. In an embodiment, bladder 310 may be cylindrical or ellipsoidal, to better fit the tapered shape of temple piece 120. In one example, the inner diameter may be 5.0 mm or less, such as 2.0 to 4.5 mm along the major axis and between 1.0 mm to 3.0 mm along the minor axis. In another example, the upper limit of the dimensions of bladder 310 is controlled by the size of temple piece 120 to be used with eyeglasses 100 and also by the maximum amount of force that may reasonably be generated by the mechanical action of an actuator (for example, the assembly in Figure 2

including 260, 270, 272, and 280), and transmitted to compression arm 260 in contact with bladder 310. If this force is too high, it may cause bending of compression arm 260, thus dissipating some of the force. In an embodiment, there is also a direct correlation between the wall thickness of bladder 310, its stiffness under tensile and shear forces, and the dimensions of bladder 310.

[0028] Bladder 310 of reservoir assembly 240 is connected to a narrower portion, referred to herein as connecting tube 320, that carries the fluid from bladder 310 to fluid filled lens assembly 180 (as shown in Figure 1). In an embodiment, bladder 310 and connecting tube 320 may be separately formed and joined together. In another embodiment, bladder 310 and connecting tube 320 are formed from a single tube of the reservoir material. Several processes may be developed to form the reservoir as a single unit and avoid having to form a joint 330, including, for example and without limitation, heat shrinking provided that the reservoir material is made of a heat shrinkable material; blow or injection molding, for example when the reservoir material is a thermoplastic; or machining, such as for prototype production.

[0029] In one example embodiment, connecting tube 320 has an inner diameter between 1.0 mm to 2.5 mm, such as between 1.0 mm and 1.5 mm. The lower limit controls the time required for the fluid to pass through connecting tube 320. For example, an inner diameter of the connecting tube of 1.2 mm allows the optical response to an adjustment of the actuator to be completed in less than 5 seconds, and, in an embodiment, less than 2 seconds. Since the wall thickness of connecting tube 320 is between 0.1 mm and 0.5 mm in this embodiment, the outer diameter may be between 3.5 mm and 1.2 mm. The upper limit is controlled by the maximum amount of bend allowance that can be provided by the hinge section, disclosed in U.S. Patent Application No. 12/904,769 incorporated herein by reference in its entirety, and the end piece without making eyeglasses 100 too bulky and stiff, as well as the bend radius that connecting tube 320 can achieve without developing a kink or a blockage.

[0030] Figures 4A-4D provided detailed views and dimensions of an exemplary reservoir assembly 240, according to an embodiment of the present invention. The top portion of Figure 4A illustrates a side view of reservoir assembly 240, while the bottom portion of Figure 4A illustrates a top view of reservoir assembly 240. Figures 4B-4D illustrate cross-sectional views of reservoir assembly 240 along its length. Figure 4B illustrates a

cross-sectional view of open end 350 of connecting tube 320 (without a flared end). Figure 4C illustrates a cross-sectional view of bladder 310 at or near joint 330. Figure 4D illustrates a cross-sectional view of bladder 310 near sealed end 340. In this exemplary embodiment, the length from sealed end 340 to joint 330 is 32 mm, the length from joint 330 to open end 350 is 20.5 mm, the length of the joint is 1 mm, and the length of the sealed end 340 is 1.5 mm. Also in this exemplary embodiment, the diameter of cross-section A-A is 1.6 mm and the wall thickness is 0.3 mm. The major axis of elliptical cross-section B-B is 3.75 mm and the minor axis is 2.5 mm with a wall thickness of 0.1 mm. The major axis of elliptical cross-section C-C is 4.5 mm and the minor axis is 1.12 mm with a wall thickness of 0.1 mm.

[0031] Figure 5 illustrates the reservoir with an exploded view of the sealed lens module according to an embodiment, showing the connecting ends (e.g., flared end 520) of connecting tube 320 of reservoir 240 and an inlet port 530 located on rigid lens 550 of sealed lens module 180. As shown in Figure 5, open end 350 of connecting tube 320 is flared to create flared end 520, and then fit over inlet port 530 of the fluid filled lens assembly, so that connecting tube 320 may be welded to inlet port 530 prior to any filling operation.

[0032] In each of these embodiments, it is important to select an appropriate material for the reservoir assembly. In an embodiment, this material is chemically inert, with minimum permeability to the fluid being used (e.g., silicone oil), so that no fluid is lost during 2-3 years of use. In an embodiment, the material is processable and highly flexible, because it may undergo tight bends along its length, particularly when the hinge is closed. In one example, the radius of curvature may be as little as 3.0 mm, or as low as 2.5 times the outer diameter of the connecting tube.

[0033] The following Table 1 shows exemplary materials that may be considered for reservoir 240.

Plastic	Thermal Properties				Strength		Density
Abbreviation (chemical name) Brand name	Tm	Tg	Td	Cte	Tensile	Compressive	
	°C	°C	°C	ppm/°C	psi	psi	g/cc
ECTFE (ethylene chlorotrifluoro ethylene copolymer)	220 245		116	80	6000 7000		1.68 1.69
ETFE (ethylene tetrafluoro- ethylene copolymer) Tefzel	270		104	59	6500	7100	1.7
FEP (fluorinated ethylene- propylene copolymer) Teflon FEP	275		70		2700 3100	2200	2.12 2.17

PFA (perfluoroalkoxy) Teflon PFA	310		74		4000 4300		2.12 2.17
PCTFE (polychlorotrifluoro- ethylene)	220		125	36 70	4500 6000	4600 7400	2.08 2.2
PTFE (polytetrafluoroethylene) Teflon	327		121	70 120	2000 5000	1700	2.14 2.20
PVF (polyvinylfluoride) Tedlar						7000 18000	1.38 1.57
PVDF (polyvinylidene fluoride) Kynar	174 178		138	70 142	5200 7250	10900 14000	1.77 1.78
(polycaprolactam) Nylon6	210 220		185 190	80 83	7400	13000 16000	1.12 1.14
PC (polycarbonate) Lexan		150	138	68	9500	12500	1.2
PET (polyethyleneterephthalate) Mylar	245 265	73 80	21 38	65	7000 10500	11000 15000	1.29 1.40
LDPE (low density polyethylene)	98 115	-25	40 44	100 220	1200 4550		0.917 0.932
LLDPE (linear low density polyethylene)	122 124				1900 4000	0	0.918 0.940
HDPE (high density polyethylene)	130 137		79 91	59 110	3200 4500	2700 3600	0.952 0.965
UHMWPE (ultra high molecular weight polyethylene)	125 135		68 82	130	5600		0.940
PI (polyimide)		310 365	277 360	45 56	10500 17100	30000 40000	1.36 1.43
PMMA (polymethylmethacrylate) Plexiglas		85 105	79 107	50 90	7000 11000	10500 18000	1.17 1.20
PP (polypropylene)	168 175	-20	107 121	81 100	4500 6000	5500 8000	0.900 0.910
PS (polystyrene) Styron		74 105	68 96	50 83	5200 7500	12000 13000	1.04 1.05
PVC (polyvinylchloride)		75 105	57 82	50 100	5900 7500	8000 13000	1.30 1.58
PVDC (polyvinylidenechloride) Saran	172	-15	54 66	190	3500 5000	2000 2700	1.65 1.72

Table 1

[0034] In an embodiment, fluorocarbon material may be used instead of a chlorofluorocarbon or other halocarbon materials in terms of a combination of impermeability, elasticity, and stiffness. For example, for a given embodiment, TYGON (polyvinyl chloride) is superior in terms of elasticity and stiffness but is not sufficiently impermeable to silicone oil such as DC 702 and DC 704 produced by Dow Corning Corp. of Midland, MI. For a given embodiment, polyvinylidene difluoride (PVDF) may be used, because it has an optimal combination of elasticity, stiffness, and impermeability. It is also highly processable, and may be heat shrunk, heat sealed, thermoformed, and injection molded. PVDF possesses excellent resistance to uptake of silicone oil both in heat shrunk and non heat shrunk forms.

[0035] Figures 6A-6D illustrate a reservoir fabrication method according to an embodiment of the present invention. Figure 6A illustrates an initial step of fabricating a two piece reservoir. Initially, in an embodiment, a tubular profile 610 is formed with a cylindrical or elliptical cross-section. The cross-section of this tubular profile 610 is shaped and sized to fit within the cavity of a temple piece of the fluid-filled lens eyeglasses. Then, a first tubular piece of material 620, having a length somewhat longer than tubular profile 610, is placed over tubular profile 610 from one open end 612 of first tubular piece of material 620. Material 620 may be, for example, PVDF. Tubular profile 610 may be made from, for example, metal.

[0036] As seen in Figure 6B, material 620 is then processed. In an embodiment, material 620 is processed using a heat treatment. During such a processing, material 620 shrinks and contracts around tubular profile 610, except where tubular profile 610 is not supporting material 620, in which case material 620 continues to contract, forming a small coupling and opening 632 relative to the cross-section of metal profile 610. The first processed material 630 is the base formation of a bladder.

[0037] Figure 6C illustrates another step of fabricating a two piece reservoir, according to an embodiment. Initially, in an embodiment, a second tubular piece of material 640 having a diameter smaller than first tubular piece of material 620 but larger than coupling 632, is placed over a flare profile 660. Flare profile may be made from, for example, metal. Flare profile 660 is shaped and sized to create a flared end of the connecting tube such that it will fit over an inlet port of a fluid-filled lens assembly. The other end of second tubular piece of material 640 is placed over coupling 632. Coupling 632 and the opening of second tubular piece of material 640 may have an adhesive applied to their inside and outside surfaces to connect first and second tubular pieces of material 620 and 640 together. The adhesive may be, for example and without limitation, DELO Duopox 01 Rapid or Duopox AD821 produced by DELO Industrie Klebstoffe GmbH of Windach, Germany.

[0038] As seen in Figure 6D, material 640 is then processed, e.g. by heat treatment, such that material 640 shrinks and contracts to form the connecting tube, except where the flare profile 660 is supporting material 640, in which case material 640 does not fully contract and forms a flared end 670, relative to the cross-section of processed connecting tube 650. Processed connecting tube 650 is also now permanently joined to bladder base

630 at joint 680. As previously stated, joint 680 may be further connected with an adhesive, may be sealed by only the contraction of the processed materials, or both. The final step of this reservoir fabrication method is to remove flare profile 660 and seal, e.g., with a heat treatment, open end 612 of the first tubular piece of material 620, now the processed base 630 for a bladder. Upon sealing of open end 612, the bladder becomes fully functional.

[0039] Figures 7A-7D illustrate another reservoir fabrication method, according to an embodiment of the present invention. Figure 7A illustrates an initial step of fabricating a two piece reservoir. Initially, in an embodiment, a tubular section of a material 740 is placed over an inlet profile 760. Material 740 may be, for example, PVDF. Inlet profile 760 may be made from, for example, metal. Inlet profile 760 may be shaped and sized to create a flared end of material 740, such that material 740 will fit over the inlet port of the fluid-filled lens assembly once it has been processed.

[0040] As seen in Figure 7B, material 740 is then processed. In an embodiment, material 740 is processed by heat treatment, such that material 740 shrinks and contracts, except where inlet profile 760 is supporting material 740. In that case, material 740 does not fully contract and forms a flared end 770, relative to the cross-section of processed connecting tube 750.

[0041] Figure 7C illustrates another step of fabricating a two piece reservoir, according to an embodiment. In an embodiment, a tubular profile 710 is formed with a cylindrical or elliptical cross-section. Tubular profile 710 may be made from, for example, metal. The cross-section of tubular profile 710 may be shaped and sized to fit within the cavity of a temple piece of the fluid-filled lens eyeglasses. Then a tubular piece of material 720, having a length that is somewhat longer than tubular profile 710, is placed over tubular profile 710 from one open end 712 of the tubular piece of material 720. Material 720 may be, for example, VITON®, produced by DuPont Performance Elastomers of Wilmington, DE. The other end of the tubular piece of material 720 is placed over the non-flared end of processed connecting tube 750. The non-flared end of processed connecting tube 750 and the opening of the other end of the tubular piece of material 720 may have an adhesive, such as, but not limited to DELO Duopox 01 Rapid or Duopox AD821, applied to their inside and outside surfaces to connect the two tubular pieces of material 720 and material 740 together.

[0042] As seen in Figure 7D, material 720 is then processed. In an embodiment, material 720 is processed by heat treatment. In such an embodiment, such that material 720 shrinks and contracts around the tubular profile 710, except where tubular profile 710 is not supporting material 720, in which case material 720 continues to contract, forming a joint 780 with connecting tube 750. The processed material 730 is the base formation of a bladder. Processed connecting tube 750 is also now permanently joined to bladder base 730 at joint 780. As previously stated, joint 780 may be further connected with an adhesive, may be sealed by only the contraction of the processed materials, or both. The final step of this reservoir fabrication method is to remove tubular profile 710 and seal open end 712 of tubular piece of material 720. This turns the now-processed material 730 into a base for a bladder. The open end may be sealed, for example, with a heat treatment. Upon sealing of the open end 712, the bladder becomes fully functional.

[0043] While Figures 6A-6D and 7A-7D are illustrative of two methods to fabricate the fluid-filled lens reservoir, they should not be seen as limiting examples. For example, the two portions of the reservoir can be formed as a single unit. Several processes may be developed to form the reservoir as a single unit and avoid having to form a joint, including heat shrinking provided that the reservoir material is made of a heat shrinkable material; blow or injection molding, when the reservoir material is, for example, a thermoplastic; or machining, for example in prototype production.

[0044] Figure 8 shows the results of a test performed to compute the dimensions of the reservoir for one eyeglass design according to an embodiment. This test measured the volume of silicone oil required to create one diopter (1.0D) increase in optical power of the fluid filled lens. This measurement used a prototype fluid filled lens assembly placed on a lensometer capable of measuring lens power. The fluid filled lens was connected and sealed to a reservoir shaped as shown in Figure 3, by means of a connecting tube of appropriate length and diameter.

[0045] The data shows that fluid is indeed transferred from the reservoir to the lens cavity causing the membrane of the fluid lens to inflate and lens power to increase as predicted. The increase in power was linear with respect to the fluid volume, indicative of a linear response to the movement of the actuator means, such as a wheel or a screw. For this design, about 30 microliters of silicone oil was used to increase the optical power of the fluid filled lens by 1.0D. Since a full power range of about 2.5D may be desirable,

the reservoir may be sized, in an embodiment, to deliver this amount of fluid without having to squeeze the reservoir out of its elastic zone, leaving approximately 60% of the fluid in the reservoir at the highest point of the power range.

[0046] Although various embodiments of the present invention have been described above, it should be understood that they have been presented by way of example only, and not limitation. It will be apparent to persons skilled in the relevant art that various changes in form and detail can be made therein without departing from the spirit and scope of the invention. Thus, the breadth and scope of the present invention should not be limited by any of the above-described exemplary embodiments, but should be defined only in accordance with the following claims and their equivalents.

[0047] Further, the purpose of the foregoing Abstract is to enable the U.S. Patent and Trademark Office and the public generally, and especially the scientists, engineers and practitioners in the art who are not familiar with patent or legal terms or phraseology, to determine quickly from a cursory inspection the nature and essence of the technical disclosure of the application. The Abstract is not intended to be limiting as to the scope of the present invention in any way.

We claim:

1. An eyeglass reservoir system for storing fluid to supply a fluid filled lens of a pair of eyeglasses, comprising:
 - a temple piece having a cavity;
 - a bladder positioned within the cavity and configured to repeatedly compress and relax, the bladder being made of a flexible material; and
 - a connecting tube coupled to an inlet port of a lens module and to the bladder, configured to carry a fluid between the bladder and a fluid filled lens cavity of the lens module.
2. The eyeglass reservoir system of claim 1, further comprising:
 - a compression arm contacting the bladder and configured to transmit force from an actuator to the bladder to cause movement of the fluid between the bladder and the connecting tube.
3. The eyeglass reservoir system of claim 1, wherein the bladder and connecting tube are separately formed portions that have been joined together.
4. The eyeglass reservoir system of claim 1, wherein the bladder and connecting tube are two portions of a single continuous tube.
5. The eyeglass reservoir system of claim 1, wherein a shape of the bladder is cylindrical or ellipsoidal and the bladder is wider, respectively, than the connecting tube.
6. The eyeglass reservoir system of claim 5, wherein an inner diameter of the bladder is 5.0 mm or less.
7. The eyeglass reservoir system of claim 6, wherein an inner diameter of the bladder is between 2.0 and 4.5 mm along a major axis and 1.0 and 3.0 mm along a minor axis.

8. The eyeglass reservoir system of claim 1, wherein the material is polyvinylidene difluoride.
9. The eyeglass reservoir system of claim 1, wherein the connecting tube is made of polyvinylidene difluoride.
10. The eyeglass reservoir system of claim 1, wherein an inner diameter of the connecting tube is between 1.0 and 2.5 mm.
11. The eyeglass reservoir system of claim 1, wherein an outer diameter of the connecting tube is between 1.2 and 3.5 mm.
12. The eyeglass reservoir system of claim 1, wherein the connecting tube further comprises:
a flared end configured to couple to the inlet port of the lens module.
13. The eyeglass reservoir system of claim 12, wherein the flared end of the connecting tube facilitates connection and permanent affixation to the inlet port of the lens module.
14. An apparatus, comprising:
a flexible bladder configured to repeatedly compress and relax;
a flexible connecting tube having a flared end and a non-flared end, the non-flared end coupled to the bladder, the connecting tube configured to narrow and extend along a passage length of the bladder, wherein the connecting tube is further configured to carry a fluid from and to the bladder; and
a compression arm contacting the bladder and configured to apply pressure to the bladder.
15. The apparatus of claim 14, wherein the bladder and connecting tube are separately formed portions that have been joined together.
16. The apparatus of claim 14, wherein the bladder and connecting tube are two portions of a single continuous tube.

17. The apparatus of claim 14, wherein a shape of the bladder is cylindrical or ellipsoidal and the bladder is wider, respectively, than the connecting tube.
18. The apparatus of claim 14, wherein the bladder and the connecting tube are made of polyvinylidene difluoride.
19. The apparatus of claim 14, wherein the flared end of the connecting tube facilitates connection and permanent affixation to an inlet port of a fluid lens module.
20. A device manufacturing method, comprising:
 - placing a first unprocessed tube of a first processable material having a first diameter and first and second openings at opposite ends over a tubular reservoir profile having a cylindrical or elliptical cross-section, such that one end of the first unprocessed tube associated with the first opening and one end of the tubular reservoir profile are even;
 - processing the first processable material such that a first processed tube forms around the tubular reservoir profile and contracts, at the end associated with the second opening, smaller than the tubular reservoir profile to create a reduced diameter opening;
 - removing the tubular reservoir profile from the first processed tube;
 - sealing the first opening;
 - placing a first opening of a second unprocessed tube of a second diameter over the reduced diameter opening of the first processed tube, the second unprocessed tube being made of a second processable material;
 - placing an inlet profile in a second opening of the second unprocessed tube; and
 - processing the second processable material such that a second processed tube forms around the reduced opening of the first tube and the inlet profile to form a flared opening.
21. The device manufacturing method of claim 20, wherein the tubular reservoir profile fits within a cavity of an eyeglass temple piece.

22. The device manufacturing method of claim 20, wherein the first processable material and the second processable material are identical.
23. The device manufacturing method of claim 20, wherein the first processable material is polyvinylidene difluoride.
24. The device manufacturing method of claim 20, wherein the first processable material and the second processable material are different.
25. The device manufacturing method of claim 20, wherein a cross-section of the tubular reservoir profile has an outer diameter of between 2.0 and 4.5 mm along a major axis and 1.0 and 3.0 mm along a minor axis.
26. The device manufacturing method of claim 20, wherein the first opening of the first processed tube is sealed with an adhesive.
27. The device manufacturing method of claim 20, wherein the first opening of the first processed tube is sealed with heat.
28. The device manufacturing method of claim 20, wherein the second diameter is smaller than the first diameter, and the second diameter is larger than a diameter of the reduced diameter opening.
29. The device manufacturing method of claim 20, further comprising:
 - placing a first adhesive around an inside rim of the first opening of the first processed tube; and
 - placing a second adhesive around an outside rim of the reduced diameter opening, an inside rim of the first opening of the second processed tube, or both.
30. The device manufacturing method of claim 29, wherein the first adhesive and the second adhesive are identical.

31. The device manufacturing method of claim 29, wherein the first adhesive and the second adhesive are different.

1/9




FIG. 1




FIG. 2

3/9




FIG. 3

4/9







FIG. 4A



SECTION A-A
SCALE 16.000
FIG. 4B



SECTION B-B
SCALE 16.000
FIG. 4C



SECTION C-C
SCALE 16.000
FIG. 4D

5/9




FIG. 5

6/9




FIG. 6A




FIG. 6B









FIG. 6C

7/9



8/9



9/9




FIG. 8

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US2010/052905

A. CLASSIFICATION OF SUBJECT MATTER

IPC(8) - G02B 3/14 (2011.01)

USPC - 359/666

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC(8) - G02B 3/12, 3/14 (2011.01)

USPC - 359/665, 666

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

PatBase

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2,576,581 A (EDWARDS) 27 November 1951 (27.11.1951) entire document	1-19
A	GB 258,325 A (MITCHELL) 15 September 1926 (15.09.1926) entire document	1-19
A	US 3,614,215 A (MACKTA) 19 October 1971 (19.10.1971) entire document	1-19

☐ Further documents are listed in the continuation of Box C.



* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

24 January 2011

Date of mailing of the international search report

08 FEB 2011

Name and mailing address of the ISA/US

Mail Stop PCT, Attn: ISA/US, Commissioner for Patents
P.O. Box 1450, Alexandria, Virginia 22313-1450

Facsimile No. 571-273-3201

Authorized officer:

Blaine R. Copenheaver

PCT Helpdesk: 571-272-4300

PCT OSP: 571-272-7774

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US2010/052905

Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

See extra sheet.

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying additional fees, this Authority did not invite payment of additional fees.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☒ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:
1-19

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.
- ☐ The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.
- ☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US2010/052905

This application contains the following inventions or groups of inventions which are not so linked as to form a single general inventive concept under PCT Rule 13.1. In order for all inventions to be examined, the appropriate additional examination fees must be paid.

Group I, claims 1-19, is drawn to an eyeglass reservoir system for storing fluid to supply a fluid filled lens.

Group II, claims 20-31, is drawn to a device manufacturing method comprising sealing and contracting processing material around profiles.

The inventions listed as Groups I and II do not relate to a single general inventive concept under PCT Rule 13.1 because, under PCT Rule 13.2, they lack the same or corresponding special technical features for the following reasons: the special technical feature of the Group I invention is an eyeglass reservoir system for storing fluid to supply a fluid filled lens comprising a fluid lens, bladder, and inlet port of the fluid lens as claimed therein and is not present in the invention of Group II; the special technical feature of the Group II invention is device manufacturing method comprising a first processed tube formed around a tubular reservoir profile and contracted and sealed, and a second processed tube formed around a reduced opening of the first tube and an inlet profile to form a flared opening and is not present in the invention of Group I.

Since none of the special technical features of the Groups I and II inventions is found in more than one of the inventions, unity of invention is lacking.