




US 20250202203A1

(19) **United States**(12) **Patent Application Publication**  
**Lindquist et al.**(10) **Pub. No.: US 2025/0202203 A1**(43) **Pub. Date: Jun. 19, 2025**(54) **CROSS-ARM PHASE-LIFTER****Publication Classification**(71) Applicant: **Altec Industries, Inc.**, Birmingham, AL  
(US)(51) **Int. Cl.**  
**H02G 1/04** (2006.01)(72) Inventors: **David Lindquist**, Cameron, MO (US);  
**Timothy J. Mourlam**, Shawnee, KS  
(US)(52) **U.S. Cl.**  
CPC ..... **H02G 1/04** (2013.01)(21) Appl. No.: **19/071,410**(57) **ABSTRACT**(22) Filed: **Mar. 5, 2025****Related U.S. Application Data**(63) Continuation of application No. 18/224,278, filed on  
Jul. 20, 2023, now Pat. No. 12,272,933, which is a  
continuation of application No. 17/875,990, filed on  
Jul. 28, 2022, now Pat. No. 11,749,978.

Disclosed embodiments provide a cross-arm phase-lifter for lifting and maneuvering a utility pole cross-arm without the need to remove the energized power lines from the cross-arm. A first embodiment of the cross-arm phase-lifter may comprise a set of clamps, clamping members, and actuators. When the actuators are driven, the clamping members may secure the clamps onto the cross-arm. Once the clamps are secured, the cross-arm may be lifted and suspended in air. A second embodiment may comprise a lifting plate comprising a plurality of pegs configured to interface with brackets on the cross-arm. When the pegs are engaged with the brackets, the cross-arm may be lifted and suspended in air.







FIG. 1






FIG. 3




FIG. 4A





FIG. 4B



**FIG. 5A**




FIG. 5B






FIG. 6A





FIG. 6B



**FIG. 7**

**CROSS-ARM PHASE-LIFTER****SUMMARY****RELATED APPLICATIONS**

**[0001]** This patent application is a continuation application claiming priority benefit, with regard to all common subject matter, of U.S. patent application Ser. No. 18/224,278, filed Jul. 20, 2023, and entitled “CROSS-ARM PHASE-LIFTER” (“the ‘278 Application”). The ‘278 Application is a continuation application claiming priority benefit, with regard to all common subject matter, of U.S. patent application Ser. No. 17/875,990, filed Jul. 28, 2022, now U.S. Pat. No. 11,749,978, issued Sep. 5, 2023, and entitled “CROSS-ARM PHASE-LIFTER.” The above referenced patent application and patent are hereby incorporated by reference in their entirety into the present application.

**BACKGROUND****1. Field**

**[0002]** Embodiments of the present teachings relate to operating on energized power lines. More specifically, embodiments of the present teachings relate to a phase-lifter for manipulating cross-arms on utility poles.

**2. Related Art**

**[0003]** Utility workers commonly utilize an aerial device to reach remote locations, such as overhead power lines, for installation, repair, and/or maintenance of electric power components. Due to the inherent dangers with operating on live power lines and at high heights, it is desired to perform power line maintenance in a safer manner by removing the lineman from near the power line to a safe location away from the power line. For example, robotics may be used to operate on live lines. The robotics may be controlled remotely by the operator, such as from within a utility truck cabin, thereby eliminating fall and electrocution danger for the operator.

**[0004]** Typically, when a utility pole needs maintenance, such as the replacement of a cross-arm, energized power lines thereon (often referred to as phases) must be carefully and individually removed and placed onto a temporary phase-holder to avoid interfering with the maintenance process. The temporary phase-holder is housed on a machine (e.g., aerial device or derrick) that is oftentimes separate from the vehicle that supports the boom and utility bucket from which the lineman works. In other cases, the temporary phase holding is performed from the aerial device from which the lineman is working. After maintenance has been completed, the phases must be placed back onto the cross-arm. Because energized power lines are dangerous to work with due to high voltages, decreasing the number of interactions with energized power lines can increase the safety for lineman.

**[0005]** What is needed is a cross-arm phase-lifter for manipulating cross-arms. Further, what is needed is a cross-arm phase-lifter for lifting cross-arms without needing to remove power lines off insulators atop the cross-arms. Further still, what is needed are systems and methods for working on energized power lines that can be performed with less equipment than existing systems.

**[0006]** Embodiments of the present teachings solve the above-mentioned problems by providing cross-arm phase-lifters for manipulating utility pole cross-arms. The cross-arm phase lifter may manipulate cross-arms without the need to remove the energized power lines therefrom. In some embodiments, insulators that do not require wire ties to couple the conductor line thereto are used to facilitate the movement of the cross-arm along the conductors. For example, clamp-style insulators may be used. The cross-arm phase-lifter may be operated by a lineman or a remotely-operated robot unit. In some embodiments, the cross-arm phase-lifter comprises a plurality of clamping members for clamping onto the cross-arm. In some embodiments, the cross-arm phase-lifter comprises a lifting plate comprising a plurality of pegs that engage with a respective plurality of brackets that are mounted onto the cross-arm. Once coupled to the cross-arm, the cross-arm phase-lifter may be driven to raise the cross-arm off the pole and hold the cross-arm in suspension to allow for maintenance to be performed on the utility pole.

**[0007]** The cross-arm phase-lifter may be used when replacing an existing cross-arm with a new cross-arm. Because the cross-arm phase-lifter may suspend a cross-arm in air, the energized power lines may be transferred directly onto the suspended, new cross-arm without the need of a temporary phase-holder and the extra equipment associated therewith. The new cross-arm may then be installed directly onto the utility pole, without the lineman or robot unit having to transfer the energized power lines to and from a temporary phase holder.

**[0008]** In a first embodiment, the techniques described herein relate to a phase-lifter for manipulating utility pole cross-arms coupled to energized power lines, including: a structural member including a first end and a second end; a first clamping member including a first clamp; a second clamping member including a second clamp, wherein the first clamping member and the second clamping member are coupled to the first end of the structural member; a third clamping member including a third clamp; and a fourth clamping member including a fourth clamp, wherein the third clamping member and the fourth clamping member are coupled to the second end of the structural member; a first actuator for actuating the first clamp and the second clamp to couple the first clamp and the second clamp to the cross-arm; and a second actuator for actuating the third clamp and the fourth clamp to couple the third clamp and the fourth clamp to the cross-arm.

**[0009]** In a second embodiment, the techniques described herein relate to the phase-lifter of embodiment one, wherein the first actuator includes: a threaded stud received within a first actuator block and a second actuator block, wherein the first actuator block is coupled to the first clamping member and the second actuator block is coupled to the second clamping member, and wherein rotation of the threaded stud causes the first actuator block to move towards the second actuator block, thereby moving the second clamp towards the first clamp.

**[0010]** In a third embodiment, the techniques described herein relate to the phase-lifter described in embodiments one and two, wherein the wherein at least one of first actuator or the second actuator comprises one of an electric actuator, a hydraulic actuator, or a pneumatic actuator,

wherein the first actuator and the second actuator comprise one of a linear actuator or a rotary actuator.

**[0011]** In a fourth embodiment, the techniques described herein relate to the phase-lifter described in any of embodiments one through three, further including: a bracket protruding from the structural member, wherein the bracket is configured to connect the phase-lifter to a supporting structure, wherein the supporting structure is configured to move the phase-lifter to manipulate the cross-arm.

**[0012]** In a fifth embodiment, the techniques described herein relate to the phase-lifter described in any of embodiments one through four, wherein the supporting structure is a boom assembly.

**[0013]** In a sixth embodiment, the techniques described herein relate to the phase-lifter described in any of embodiments one through four, wherein the supporting structure is a pole clamp configured to couple to a utility pole.

**[0014]** In a seventh embodiment, the techniques described herein relate to the phase-lifter described in any of embodiments one through six, wherein the first clamping member is pivotally coupled to the second clamping member, and wherein the third clamping member is pivotally coupled to the fourth clamping member.

**[0015]** In an eighth embodiment, the techniques described herein relate to the phase-lifter described in any of embodiments one through seven, wherein at least one of the first clamp, the second clamp, the third clamp, or the fourth clamp is spring-loaded to align the clamps to the cross-arm.

**[0016]** In a ninth embodiment, the techniques described herein relate to a system for manipulating utility pole cross-arms coupled to energized power lines, including: an aerial device including a boom assembly; a robot unit at a distal end of the boom assembly; and the phase-lifter, including: at least one engaging member for coupling to the cross-arm; a structural member coupled to the at least one engaging member; and a connecting member configured to couple the phase-lifter to a supporting structure, wherein the phase-lifter is driven by the supporting structure to lift the cross-arm off a utility pole and holds the cross-arm in suspension to allow maintenance to be performed on the utility pole.

**[0017]** In a tenth embodiment, the techniques described herein relate to the system described in embodiment ten, wherein the phase-lifter holds the cross-arm without removing the energized power lines therefrom.

**[0018]** In an eleventh embodiment, the techniques described herein relate to the system described in embodiments nine and ten, wherein the supporting structure is supported by a high-capacity manipulator of a robot unit, the robot unit disposed on a distal end of a boom on an aerial device.

**[0019]** In a twelfth embodiment, the techniques described herein relate to the system described in any of embodiments nine through eleven, wherein the cross-arm is a new cross-arm, wherein at least one robotic arm of the robot unit is configured to transfer the energized power lines from an old cross-arm to the new cross-arm, and wherein the high-capacity manipulator lifts the phase-lifter to install the new cross-arm onto the utility pole.

**[0020]** In a thirteenth embodiment, the techniques described herein relate to the system described in any of embodiments nine through twelve, wherein the at least one engaging member includes a first clamping member pair and a second clamping member pair, and wherein a robotic arm

of the robot unit actuates the first clamping member pair and the second clamping member pair to clamp the first clamping member pair and the second clamping member pair onto the cross-arm.

**[0021]** In a fourteenth embodiment, the techniques described herein relate to the system described in any of embodiments nine through thirteen, wherein the first clamping member pair and the second clamping member pair are actuated using an impact drill operated by the robotic arm.

**[0022]** In a fifteenth embodiment, the techniques described herein relate to the system described in any of embodiments nine through fourteen, wherein the at least one engaging member includes a lifting arm including a first peg and a second peg on a face of the structural member, and wherein the first peg engages with a first bracket on the cross-arm and the second peg engages with a second bracket on the cross-arm.

**[0023]** In a sixteenth embodiment, the techniques described herein relate to the system described in any of embodiments nine through fifteen, wherein the first bracket and the second bracket are attached by a robotic arm of the robot unit.

**[0024]** In a seventeenth embodiment, the techniques described herein relate to a system for manipulating utility pole cross-arms coupled to energized power lines, including: an aerial device including a boom; a robot unit disposed on a distal end of a boom, including: at least one robotic arm; and a high-capacity manipulator; and a phase-lifter coupled to the high-capacity manipulator, including: a first pair of clamping members and a second pair of clamping members for coupling to a cross arm; and at least one actuator for actuating the first pair of clamping members and the second pair of clamping members.

**[0025]** In an eighteenth embodiment, the techniques described herein relate to the system described in embodiment seventeen, wherein the high-capacity manipulator lifts the phase-lifter to remove the cross-arm from a utility pole.

**[0026]** In a nineteenth embodiment, the techniques described herein relate to the system described in embodiments seventeen and eighteen, wherein the at least one robotic arm is configured to detach the cross-arm from the phase-lifter.

**[0027]** In a twentieth embodiment, the techniques described herein relate to the system described in any of embodiments seventeen through nineteen, wherein the at least one actuator is a motor.

**[0028]** This summary is provided to introduce a selection of concepts in a simplified form that are further described below in the detailed description. This summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used to limit the scope of the claimed subject matter. Other aspects and advantages of the present teachings will be apparent from the following detailed description of the embodiments and the accompanying drawing figures.

#### BRIEF DESCRIPTION OF THE DRAWING FIGURES

**[0029]** Embodiments of the present teachings are described in detail below with reference to the attached drawing figures, wherein:

**[0030]** FIG. 1 is an aerial device for some embodiments;

**[0031]** FIG. 2 is an exemplary system architecture of a robot unit and manual controls for some embodiments;

[0032] FIG. 3 is a remote assembly system for some embodiments;

[0033] FIG. 4A depicts a first perspective view of a cross-arm phase-lifter for some embodiments;

[0034] FIG. 4B depicts a second perspective view of the cross-arm phase-lifter for some embodiments;

[0035] FIG. 5A depicts a clamping member pair of the cross-arm phase-lifter for some embodiments;

[0036] FIG. 5B depicts a stud for actuating the clamping member pair for some embodiments;

[0037] FIG. 6A depicts a first perspective view of a second embodiment of the cross-arm phase-lifter for some embodiments;

[0038] FIG. 6B depicts a second perspective view of the second embodiment of the cross-arm phase-lifter for some embodiments; and

[0039] FIG. 7 depicts an exemplary method of performing utility pole maintenance using the cross-arm phase-lifter for some embodiments.

[0040] The drawing figures do not limit the present teachings to the specific embodiments disclosed and described herein. The drawings are not necessarily to scale, emphasis instead being placed upon clearly illustrating the principles of the present teachings.

#### DETAILED DESCRIPTION

[0041] The following detailed description references the accompanying drawings that illustrate specific embodiments in which the present teachings can be practiced. The embodiments are intended to describe aspects of the present teachings in sufficient detail to enable those skilled in the art to practice the present teachings. Other embodiments can be utilized, and changes can be made without departing from the scope of the present teachings. The following detailed description is, therefore, not to be taken in a limiting sense. The scope of the present teachings is defined only by the appended claims, along with the full scope of equivalents to which such claims are entitled.

[0042] In this description, references to “one embodiment,” “an embodiment,” or “embodiments” mean that the feature or features being referred to are included in at least one embodiment of the technology. Separate references to “one embodiment,” “an embodiment,” or “embodiments” in this description do not necessarily refer to the same embodiment and are also not mutually exclusive unless so stated and/or except as will be readily apparent to those skilled in the art from the description. For example, a feature, structure, act, etc. described in one embodiment may also be included in other embodiments but is not necessarily included. Thus, the technology can include a variety of combinations and/or integrations of the embodiments described herein.

[0043] Generally, embodiments of the current disclosure relate to a cross-arm phase-lifter for manipulating a cross-arm without needing to remove energized power lines therefrom. The phase-lifter may comprise a first pair and a second pair of clamping members disposed on a respective first end and second ends of a crossbar. Each clamping member may comprise a clamp for engaging with the cross-arm. The clamping members may be driven by an actuator to clamp onto the cross-arm. In some embodiments, the cross-arm phase-lifter comprises a lifting plate that comprises one or

more pegs. The one or more pegs may engage with one or more brackets mounted onto the cross-arm to couple the phase-lifter thereto.

[0044] Once the phase-lifter is coupled to the cross-arm, the phase-lifter may be lifted to suspend the cross-arm, allowing for maintenance to be performed on the utility pole. Once the maintenance is complete, the phase-lifter may be lowered to place the cross-arm back on to the utility pole. In some embodiments, the cross-arm phase-lifter is coupled to a distal end of a boom assembly. To lift the cross-arm, the phase-lifter may couple to the cross-arm, and the boom assembly may be actuated to lift the phase-lifter and the cross-arm therewith. The cross-arm phase-lifter may be used to replace a cross-arm without having to transfer the energized power lines to and from a temporary phase-holder. Instead, the energized power lines may be transferred from an existing cross-arm and attached directly onto a new cross-arm held by the phase-lifter. The cross-arm phase-lifter may be coupled to and powered by a supporting structure, such as a robot unit, high capacity lifting-arm, or jib extension.

#### Exemplary Aerial Device

[0045] FIG. 1 depicts an aerial device 100 of some embodiments. The aerial device 100 comprises a utility vehicle 112, a boom assembly 114, and a remote assembly system 300. The boom assembly 114 comprises a boom 118 having a boom proximal end 120 and a boom distal end 122. In some embodiments, the boom 118 is one of a telescoping boom 118 or an articulating boom 118. The boom assembly 114 may be attached to the utility vehicle 112 at the boom proximal end 120. The remote assembly system 300 may be secured to the boom distal end 122, such that the remote assembly system 300 is supported by the boom assembly 114. In some embodiments, and as described in greater detail below, the remote assembly system 300 may comprise at least a robot unit adapted for performing telecommunications repair, power line repair, general repair work, or other actions that may be performed by a robot. The robot unit may comprise utility tools for sawing, cutting, screwing, wiring, or other actions associated with repair work. In some embodiments, the boom 118 is used to position the remote assembly system 300 in a remote location, such as, for example adjacent to an energized power line.

[0046] As described herein, the robot unit may be controlled remotely by an operator to perform actions, such as power line repair work. For example, the robot unit may control the phase-lifter described in embodiments herein. Through such remote control, the operator is removed from any potentially dangerous situations. To provide the operator with visual, sensory, and other information, the robot unit may further comprise a sensory capturing system comprising at least a camera and a three-dimensional depth camera. Video information may be provided to the operator through a virtual reality (“VR”) headset and the operator may issue commands through joysticks or other controllers to instruct the robot unit to perform an action. To aid the operator and/or the robot unit in performing actions efficiently and correctly, three-dimensional depth information may be captured by the three-dimensional depth camera for generating a three-dimensional representation of the field of view at a computer. Accordingly, the computer can receive instructions, compare the instructions to the three-dimensional representation, and cause the robot unit to perform an action

based on the instructions and the three-dimensional representation. To further aid in providing a realistic and immersive experience to the operator, the robot unit may comprise a six degree-of-freedom (“DOF”) camera mount for mimicking or replicating the movement of the operator. Accordingly, in addition to movement in the x, y, and z planes, the robot unit can further control pitch, yaw, and roll of the camera mount. However, it will be appreciated that particular embodiments and applications of the present teachings may vary, including any of the examples provided herein. For example, the present teachings may be utilized in a variety of applications, including but not limited to military applications, construction applications, rescue applications, health and safety applications or other applications that robotics may be utilized. Accordingly, it will be appreciated that specific embodiments or details provided herein are intended to be illustrative, rather than limiting.

#### Exemplary System Architecture

**[0047]** FIG. 2 depicts an exemplary block diagram 200 related to embodiments of the present teachings. In some embodiments, the remote assembly system 300 comprises various assemblies, sub-assemblies, parts, or components for capturing sensory information and/or for performing actions, such as repair work in a telecommunication setting. The remote assembly system 300 may comprise various circuitry, parts, or other components for capturing sensory information, including video, three-dimensional depth information, audio, and other sensory data. Further, the remote assembly system 300 may comprise a manually controlled or autonomous robot unit that may be positioned at the end of the boom assembly 114 for interacting with a work site to perform one or more tasks. For example, as described above, in many real-life scenarios, tasks to be performed may not be discovered until reaching the job site, and accordingly, the robot unit may comprise a variety of tools, features, or functions to respond to a variety of different tasks. Additionally, as described in greater detail below, the remote robot assembly may further comprise one or more parts, components, or features for providing an operator with sensory information, providing the operator with additional information about the job site to improve efficiency, efficacy, and/or safety of both the remote assembly system 300 and the operator.

**[0048]** As depicted in the block diagram 200, a remote assembly 202 comprises at least a remote capture device 210, a computer 260, and a control system 280. In some embodiments, and as described in greater detail herein, the remote capture device 210 may be a device configured and adapted for the capturing of sensory information and may be positioned on a robot unit for the capturing of sensory information that may be utilized by computer 260, to present information to an operator via control system 280, among other purposes. FIG. 2 depicts exemplary sensors, cameras, and other apparatuses that may be utilized by remote capture device 210 for the capturing of sensory information. As described in greater detail below, remote capture device 210 may be mounted or positioned on a selectively movable mount or portion of a robot unit. For example, the robot unit may be a robot unit positioned at the end of a boom assembly for aerial applications. However, remote capture device 210 may also be used with a robot unit that is not attached on a boom assembly, and for example, may be utilized with a robot unit for ground application or attached to a mechanical

arm or an aerial drone. Accordingly, via the robot unit, sensory information may be captured by remote capture device 210.

**[0049]** Through selective inputs, including both manually inputted instructions and/or automated instructions, remote capture device 210 may capture video, still images, three-dimensional depth information, audio, electrical conductivity, voltage, among other information that may be captured by a sensor or recording device. For example, remote capture device 210 may comprise at least one camera 212 for the capturing of video or still images (collectively, “video”). The at least one camera 212 may be a camera positioned on remote capture device 210 for the capturing of video within a selected field of view. The resolution of the video captured by camera 212 may vary, but in some embodiments, camera 212 may be a camera configured for capturing in at least 720p resolution but may capture in higher resolution including but not limited to 1080p, 2K, 3K, 4K, or 8K resolution. However, it will be appreciated that the camera 212 may be any currently known or yet to be discovered camera for capturing video. Video captured from camera 212 may be stored locally at remote capture device 210 at a local memory 214. The storing of video at local memory 214 may aid in providing a failsafe or backup storage of captured video in the event of a transmission or upload failure. Further, the storing of video at local memory 214 may aid in situations of poor wireless connection or if a direct line becomes loose or interrupted, preventing the immediate transmission of captured video. Optionally or additionally, video captured from camera 212 may be transmitted to computer 260 for processing, analyzing, storage, and/or for later transmitting to control system 280. In further embodiments, video captured from camera 212 may be directly transmitted to control system 280 for processing.

**[0050]** In some embodiments, remote capture device 210 may further comprise at least one three-dimensional camera 216 or other device configured for capturing three-dimensional depth information. As described in greater detail below, the three-dimensional depth camera 216 may be utilized for capturing three-dimensional depth information within a field of view for creating a point cloud, 3-D model, or other digital representation of an object or area scanned or viewed by the three-dimensional camera 216. Three-dimensional camera 216 may be operated in conjunction with, or independent from camera 212 or other components or parts of remote assembly 202 and/or remote capture device 210. As described in greater detail below, in response to instructions or an input, three-dimensional camera 216 may begin capturing three-dimensional depth information about an object or area within a field of view. Like the captured video with respect to camera 212, the three-dimensional depth information captured by three-dimensional camera 216 may be saved locally at memory 214. In some embodiments, remote capture device 210 may comprise a separate memory 214 for video captured by camera 212 and a separate memory 214 for three-dimensional information captured by three-dimensional camera 216. As described in greater detail below, remote capture device 210 may comprise a microphone 218 and/or at least one sensor 220 for capturing additional sensory information. Accordingly, in some embodiments, a separate and distinct memory 214 may be used for each sensory capture device (i.e., camera 212, three-dimensional camera 216, microphone 218, and/or sensor 220). In further embodiments, remote

capture device **210** may comprise a single memory **214** for the storing of all captured sensory information. As described above and in further embodiments, three-dimensional information may be directly sent to computer **260** in addition to or instead of storing locally at memory **214**.

**[0051]** In addition to capturing video and/or three-dimensional information, it may also be advantageous for remote capture device **210** to capture additional sensory information that may be presented to an operator or processed by computer **260**. For example, in certain scenarios it may be advantageous for remote capture device **210** to capture audio via at least one microphone **218**. Continuing with the running example, a remote assembly **202** for use with telecommunications repair may utilize audio information for diagnostic or safety purposes. For example, audio information may capture the sounds of the job site and the audio information may be processed to determine if a job site is safe. Accordingly, in some embodiments, remote capture device **210** may comprise at least one microphone **218** for the capturing of audio information. Similar to the video and three-dimensional information as described above, captured audio information may be stored locally at a memory **214** and/or transmitted to a computer **260** and/or control system **280**.

**[0052]** Similar to audio information, remote capture device **210** may further comprise one or more sensors **220** for the capturing of additional sensory information, metrics, or data. For example, continuing with the running example, the remote capture device **210** may be used with a remote assembly **202** positioned at the end of boom assembly **114** for telecommunication or power line work. In such a work application, the remote assembly **202** may be working on or near live power lines or other conductive lines transferring electricity. Accordingly, in some embodiments, remote capture device **210** may comprise at least one sensor **220** configured as an electricity sensor for determining whether a cable or power line has electricity running through it. However, it will be appreciated that remote capture device **210** may comprise additional sensors **220** configured and adapted for providing remote capture device and/or remote assembly **202** with additional information. By way of a non-limiting example, sensor **220** may comprise any of the following sensors: a gyroscope, an accelerometer, a thermometer, a barometer, a light emitter, a voltage detector, a weight-detection sensor, a QR reader, magnetometers, pose sensors, rotary encoders, among other sensors that may be utilized in various applications of remote assembly **202**.

**[0053]** For example, in some embodiments, at least one sensor **220** may be adapted and configured as a sensor for estimating the weight of an object. As described in greater detail below with respect to FIG. 3, in some embodiments, comprises a remote assembly comprising a robot unit to perform fine tuning or other dexterous actions and a heavy load bearing utility arm for holding and moving heavy loads. To aid an operator in determining whether the robot unit for fine tuning work can safely hold or manipulate an object, at least one sensor **220** may be a weight estimator. For example, the weight estimator may utilize point cloud weight estimation to estimate the weight of an object. The weight estimator may capture various images of an object for the generation of a point cloud based on the object. By way of non-limiting example, the weight estimator may capture an image of a powerline transformer. The generated point cloud image may determine the transformer comprises

a diameter of 13.4" and a height of 15.8." Based on this information, a determination may be made that the transformer comprises a weight of 472.9 Lbs. This information may be presented to computer **260** or an operator in the manner described below, and the computer **260** and/or the operator may make a determination as to whether the robot unit or the heavy load bearing utility arm can safely hold and move an object.

**[0054]** Further, in some embodiments, at least one sensor **220** may be a quick response ("QR") reader for reading QR codes. For example, in some applications, remote assembly **202** may be applied in a scenario in which objects or assets may be applied with or comprise a QR code. Through utilization of a QR reader, information about the object or asset may be quickly ascertained and provided to computer **260** and/or an operator. Non-limiting examples of information that may be obtained through a QR reader may be the BIM specifications of an object, such as weight, size, lifting points, ratings, etc. It should be understood however, that any information about the object or asset may be ascertained through QR reading.

**[0055]** It should be understood that in some embodiments, remote assembly **202** may comprise a plurality of remote capture devices **210**. Further, each of the remote capture devices **210** in the plurality of remote capture devices **210** may comprise varying components (i.e., camera **212**, three-dimensional camera **216**, sensor **220**, etc.). Even further, each remote capture device **210** in the plurality of remote capture devices **210** may comprise uniform components. For example, as described above, remote capture device **210** may be used with a boom-mounted robot unit comprising a camera mount and at least one utility arm. A remote capture device **210** comprising camera **212**, three-dimensional camera **216**, and microphone **218** may be paired or positioned on the camera mount. Simultaneously, a second remote capture device **210** comprising a sensor **220** for detecting an electric voltage and a microphone **218** may be paired or incorporated into the utility arm.

**[0056]** In some embodiments, the remote assembly **202** further comprises at least one digital Hub **222**. The digital Hub **222** may receive the captured sensory information from remote capture device **210** and convert the captured sensory information into a format suitable for transmitting to computer **260** and/or control system **280**. In some embodiments, the digital Hub **222** is a USB Hub, such as, for example, a USB 3.0. In further embodiments, sensory information may be captured using Ethernet cameras or Ethernet coupled capture devices. Accordingly, in some embodiments, digital hub **222** may be replaced, substituted, or used in conjunction with an ethernet switch. It should be understood that sensory information may be captured in a variety of different formats. Accordingly, remote assembly **202** may utilize any hardware or software for receiving, analyzing, and/or transmitting sensory information.

**[0057]** As further depicted in FIG. 2, remote assembly **202** may further comprise a controller **224**. In some embodiments, controller **224** may be a processor or other circuitry or computer hardware for receiving commands or instructions from control system **280** and/or computer **260** and for relaying or providing commands to remote capture device **210** and/or motion controls **230**. Accordingly, in some embodiments, instructions, or commands from controller **224** may be sent to remote capture device **210**. For example, instructions sent from controller **224** to remote capture



device 210 may include instructions to begin recording video via camera 212. However, it will be appreciated that instructions sent from controller 224 may cause any of the components of remote capture device 210 to begin capturing sensory information, including but not limited to three-dimensional information, audio information, or other sensory information captured by any of the sensors 220 of remote capture device 210. Additionally, controller 224 may be used to send instructions to cause remote assembly 202, remote capture device 210, and/or motion controls 230 to perform other actions corresponding to the instructions. For example, instructions from controller 224 may instruct remote capture device 210 to store captured sensory information on memory 214. Additionally, instructions from controller 224 may be sent to motion controls 230 to instruct remote assembly 202 to perform a movement. Further, controller 224 may be in communication with transceiver 244 for communicating with computer 260 and/or control system 280 to send sensory information or other data or information to computer 260 and/or control system 280. Similarly, controller 224 may further be configured for receiving instructions, commands, or other information from computer 260 and/or control system 280. It should be understood that in further embodiments, controller 224 is not required to be directly coupled or incorporated into remote assembly 202. For example, remote assembly 202 may be incorporated into or be a component of a computer 260 and/or control system 280. Accordingly, in some embodiments, controller 224 may be incorporated into or directly paired with computer 260 and/or control system 280. In such embodiments, instructions, commands, or other communications may be sent from controller 224 to remote assembly 202. Remote assembly 202 may comprise computer hardware capable of receiving the transmitted instructions, commands, or communications from controller 224. For example, in some embodiments, it may be advantageous for controller 224 to be incorporated into a high-powered computing system that can transmit information to remote assembly 202.

**[0058]** As further depicted in the block diagram of FIG. 2 and in some embodiments, remote assembly 202 may further comprise motion controls 230. Motion controls 230 may be configured and adapted for controlling the movement of remote assembly 202, including any utility arms or camera mounts as described in greater detail below. In some embodiments, remote assembly 202 may comprise a 6 DOF robot unit configured with utility arms and/or camera mounts that can move with 6 DOF. Accordingly, motion controls 230 may be configured to provide instructions or commands to remote assembly 202 to move in 6 DOF. In some embodiments, motion controls may comprise x-axis control 232, y-axis control 234, z-axis control 236, pitch control 238, yaw control 240, and/or roll control 242 for moving remote assembly 202 with 6 DOF. It will be appreciated however, that remote assembly 202 may comprise varying designs, and in some embodiments, may move in fewer than 6 DOF. Accordingly, in further embodiments, motion controls 230 may comprise controls configured and adapted for moving remote assembly 202 in an appropriate number of planes.

**[0059]** As described above, motion controls 230 may be in communication with controller 224. Instructions or commands from controller 224 may be sent to motion controls 230. Upon receipt of the instructions, the corresponding

controls 232, 234, 236, 238, 240, and/or 242 may be instructed to cause movement of the remote assembly 202 based on the received instructions. As described above, one or more arms or limbs of remote assembly 202 may be configured to move with 6 DOF. Based on the instructions, the corresponding motion controls 230 may cause movement of the remote assembly 202 to correspond to the instructions.

**[0060]** As described above, remote assembly 202 may be communicatively coupled to computer 260. In some embodiments, computer 260 may be directly coupled to remote assembly 202, such that computer 260 and remote assembly 202 are a combined system. For example, computer 260 may be directly installed into a frame or body of remote assembly 202. Accordingly, remote assembly 202 and computer 260 may be in direct communication through cables or other direct methods. In further embodiments, computer 260 may be located external to remote assembly 202. When located externally, remote assembly 202 and computer 260 may nevertheless be communicatively coupled. For example, in some embodiments, remote assembly 202 and computer 260 may be coupled through a physical connection such as an Ethernet cable or USB cable. In further embodiments, remote assembly 202 and computer 260 may be coupled through a wireless connection, such as Wi-Fi, BLUETOOTH®, cellular connection, or another wireless connection. In embodiments in which computer 260 and remote assembly 202 are connected through a wireless connection, transceiver 244 may communicate with another transceiver 250 coupled or otherwise in communication with computer 260.

**[0061]** In some embodiments, computer 260 may receive and process sensory information captured by remote capture device 210 of remote assembly 202. Accordingly, computer 260 may comprise at least a processor 262 for executing commands, which may include instructions for processing, analyzing, or utilizing captured sensory information. For example, as described in greater detail below, computer 260 may utilize captured three-dimensional information to generate a point-cloud, three-dimensional model, or other digital representation of an object or area captured by remote capture device 210. In further embodiments, computer 260 may be in communication with one or more databases or data storages. For example, computer 260 may be in communication with a database comprising information directed to product or object information in a telecommunication or powerline setting. This may be particularly beneficial for obtaining information about particular objects or products that may be encountered in the application of various embodiments. For example, described above, remote assembly 202 may comprise a weight estimator utilizing a point cloud for estimating weight of an object. Computer 260 may utilize the data obtained by weight estimator in making an estimation about the weight of the object. In further embodiments and as described above, remote assembly 202 may comprise a QR reader for identifying assets or objects. Once a QR code is scanned, computer 260 may access the storage or database to identify information about the asset or object.

**[0062]** In some embodiments, control system 280 may be an interface, apparatus, or system providing a user with an interactive medium for interacting with computer 260 and/or remote assembly 202. For example, in some embodiments, control system 280 may comprise at least a processor 282, at least one controller 284, at least one display 288, at least

one sensor 290, and at least one transceiver 292. As described in greater detail below, some embodiments of the present teachings provide for a method of controlling remote assembly 202 from a remote location. Continuing with the running example, telecommunications repair or power line repair sometimes occurs during or immediately after a severe weather storm. This type of scenario can be wrought with dangers such as exposed and live power lines, high winds, lightning, and other dangers that pose a risk to human workers. Accordingly, it may be advantageous for an operator of remote assembly 202 to control remote assembly 202 in a safe location, such as in a work truck or building away from the job site. Accordingly, control system 280 may comprise at least one interfacing controller 284, providing an interactive means for a user to input commands or instructions for controlling or manipulating remote assembly 202. Controller 284 may be any interface for inputting commands or instructions that can be transmitted and processed by a computer or other hardware. By way of non-limiting example, controller 284 may comprise hand-held motion control controllers. As described in greater detail below, the motion control controllers may be beneficial for an operator to perform specific movements or actions that can be captured and relayed to remote assembly 202 to perform. Through the use of motion-control controllers, an operator may be provided with a sensory effect similar to being at the job site and performing the actions themselves. However, controller 284 is not limited to motion controls and instead, controller 284 may be any interface for an operator to input instructions or commands for remote assembly 202. For example, in further embodiments, controller 284 may be a handheld controller, similar to that of a video game controller comprising thumb sticks, buttons, triggers, and/or other interfacing inputs. In further embodiments, controller 284 may comprise a joystick and button design. In even further embodiments, controller 284 may be a mouse and keyboard. In even further embodiments, controller 284 may be configured as a glove or interactive model of a hand, allowing an operator to perform native hand manipulations which may be captured and transmitted to remote assembly 202. In even further embodiments, controller 284 may comprise a camera component or other motion capture component for capturing the movement of an operator. For example, in addition to, or in place of a physical controller handled by the operator, a camera component may capture the movement of the operator. The captured movement may be transmitted to computer 260 for translation or mapping movement of remote assembly 202. Optionally, or additionally, motion capture aids, such as motion capture dots, may also be used for capturing movement of the operator. In further embodiments, operator inputs may further be captured through AC electromagnetic tracking. In even further embodiments, operator inputs may further be captured through an active force feedback imitative control. In even further embodiments, operator inputs may be further captured through a passive force feedback imitative control. It will be appreciated that the examples provided herein are intended to be illustrative, rather than limiting, and that controller 284 may be any apparatus or method of receiving instructions or an input from an operator or computer for autonomous control.

[0063] In some embodiments, control system 280 may further comprise a power medium 286 for powering one or more parts or components of control system, including for

example controller 284, display 288, or the at least one sensor 290, or any combination thereof. In some embodiments, a single power medium may power all parts or components of control system 280. In further embodiments, individual parts, or components of control system 280 may comprise a separate and distinct power medium 286. For example, a first power medium 286 may be used for powering controller 284 and a second power medium 286 may be used for powering display 288. Power medium 286 may be any conventionally known power source for providing power to an electrical device, including but not limited to an internal power source such as a battery, or an external battery source such as an electrical outlet.

[0064] As further depicted in FIG. 2, control system 280 may further comprise at least one display 288. In some embodiments, display 288 may be a monitor, touchscreen, television screen, or any other display. In some embodiments, at least a portion of the captured sensory information from remote capture device 210 may be displayed on display 288 for an operator to view. For example, captured video may be displayed on display 288. Providing sensory information on display 288 may provide an operator with a more immersive feel when remotely operating remote assembly 202. Through a real-time video feed, an operator may experience the job site as if the operator is physically present, even if the operator is in a safe location miles away. Additionally, providing sensory information to an operator via display 288 may aid the operator in inputting instructions or commands via controller 284.

[0065] In some embodiments, control system 280 may further comprise at least one sensor 290, which may provide additional sensory affect to the operator and/or capture additional inputs that may be used by computer 260 to provide instructions to remote assembly 202. In some embodiments, one or more sensors may be combined with controller 284 and/or one or more sensors may be combined with display 288. For example, in some embodiments, sensor 290 may be at least one speaker or sound emitting device to provide the operator with audio information captured from remote capture device 210 or pre-recorded or pre-rendered audio. In further embodiments, the at least one sensor 290 may be one of an inclinometer, an accelerometer, a gyroscope, a light sensor, magnetometers, pose sensors, rotary encoders, or any other type of sensor 290 suitable to detect the viewing angle of the user or the movement, position, or angle of the operator's body.

[0066] In some embodiments, and as described in greater detail below, an operator may utilize controller 284, display 288, and the at least one sensor 290 to provide instructions to remote assembly 202, which may be analyzed and translated into instructions to cause remote assembly 202 to move or perform an action. As also described in greater detail below, an operator may input instructions or commands through control system 280. In some embodiments, inputs may be inputted or captured by a combination of controller 284 and display 288. For example, display 288 may be coupled to a head-mounted unit as described in greater detail below. An operator may move their head or torso with sensor 290 capturing the movement and/or viewing angle of the operator. The captured movement data or viewing angle may be sent to computer 260 via transceiver 292, and computer 260 may take the captured movement data or viewing angle and translate into instructions for causing remote assembly

**202** to move and mimic or replicate the operator's movement and match the viewing angle of the operator.

#### Exemplary Hardware

**[0067]** FIG. 3 is an exemplary embodiment of a remote assembly system **300**. In some embodiments, the remote assembly system **300** may comprise various assemblies, sub-assemblies, parts, or components, including but not limited to a robot unit **302** affixed at the end of a boom assembly **114**. Further, the remote assembly system **300** may correspond to the remote assembly **202** as described above with respect to FIG. 2 and may comprise any and all of the components or parts as described above. In some embodiments, robot unit **302** may be configured and adapted to receive instructions from a computer or operator to perform a corresponding movement or action. In some embodiments, robot unit **302** may be a fully manually controlled robot, wherein the robot unit **302** will not perform a movement or action absent an instruction provided from an operator. In further embodiments, robot unit **302** may be a fully automated robot, wherein the robot unit **302** performs actions or movements based on pre-programmed instructions for automation. In even further embodiments, robot unit **302** may be a robot configured to respond to both manually inputted instructions and automated programming. The various movements or actions performed by robot unit **302** and described herein may be performed based on manually provided instructions and/or automated programming. Accordingly, embodiments of the present technology are anticipated to support fully autonomous control, fully manual control, or a hybrid (semi-autonomous) control wherein the operator is interacting with and providing manually-provided inputs along with automated inputs to control remote assembly system **300**.

**[0068]** As described above and as illustrated in FIG. 3, in some embodiments remote assembly system **300** may be positioned at the distal end **122** of boom assembly **114**. As used herein, remote assembly system **300** and system **300** may be used interchangeably. As depicted, in some embodiments, distal end **122** of boom assembly **114** may comprise a pivot joint **130** comprising a motor **132**. In some embodiments, pivot joint **130** may be used to change an angle or position of remote assembly system **300**. In further embodiments, pivot joint **130** may be paired with a sensor, such as an inclinometer paired with a rotary encoder for closed-loop feedback, to aid in maintaining a leveled position of remote assembly system **300**. However, pivot joint **130** may comprise any sensor, including but not limited to magnetometers, pose sensors, rotary encoders, among other sensors. As further depicted in FIG. 3, pivot joint **130** may further act as an attachment point between remote assembly system **300** and boom assembly **114**. For example, base **150** may be coupled to pivot joint **130**. Base **150** may be adapted and configured for receiving and coupling remote assembly system **300**. Accordingly, through such coupling, remote assembly system **300** may be secured and attached to boom assembly **114**. In some embodiments, base **150** may comprise a generally planar design for accepting and securing one or more assemblies, sub-assemblies, parts, or components of remote assembly system **300**. Further, the size and shape of base **150** may vary, and may be dependent on the design of remote assembly system **300**. Further, in some embodiments, base **150** may further comprise a motorized turntable **152**. Motorized turntable **152** may be a power

motor train system for rotating base **150**. The rotation of base **150** may be advantageous for positioning remote assembly system **300** during use. In some embodiments, the various assemblies, sub-assemblies, parts, and/or components of system **300** may be adapted and configured to be selectively and removably attached to boom assembly **114**. For example, utility vehicle **112** may be driven to a job location with a bare boom assembly **114**, with the various assemblies, sub-assemblies, parts, and/or components of system **300** stored in or on utility vehicle **112**. Once at the job site, system **300** may be assembled for use. This may be advantageous for protecting aspects of system **300** during transit.

**[0069]** In some embodiments, remote assembly system **300** may generally comprise a robot unit **302**. Robot unit **302** may be a controllable robotics unit that can perform a range of movements and actions, such as performing repair work in a telecommunications setting. In some embodiments, and as described in greater detail below, robot unit **302** may be a 6 DOF robotics assembly, configured and adapted for mimicking the movement of an operator utilizing a VR controller. Particularly, through a 6-DOF configuration, robot unit **302** may substantially mimic the torso, neck, and arm movements of the operator. Through such movement, robot unit **302** may perform a greater range of movements and/or provide a more immersive experience to an operator than pre-existing systems.

**[0070]** In some embodiments, robot unit **302** may comprise a central hub **304**. Central hub **304** may be a central housing or base, which may house a processor, a power source, circuitry, a wireless communication means among other electronics for robot unit **302**, including the components described above with respect to FIG. 2. Additionally, central hub **304** may act as a coupling or attachment member, securing robot unit **302** to base **150**. Even further, central hub **304** may also act as a receiving point for one or more parts or components of robot unit **302**. For example, and as described below, robot unit **302** may comprise at least one utility arm and at least one camera mount. Accordingly, central hub **304** may receive and couple with the at least one utility arm and the at least one camera arm.

**[0071]** To collect sensory information, including but not limited to video and three-dimensional depth information, robot unit **302** may comprise at least one camera mount **310**. Camera mount **310** may be a 6 DOF, selectively controllable robotic arm, that may couple to central hub **304**. As described in greater detail below, robot unit **302** may receive movement instructions or commands from computer **260** that may cause camera mount **310** to move or change position. For example, camera mount **310** may correspond to a head mount or other capture apparatus to capture the viewing angle of an operator. Instructions or commands may be communicated to robot unit **302** causing camera mount **310** to move in a corresponding manner to match the viewing angle of the operator. To enhance the operator experience, camera mount **310** may comprise a plurality of camera mount segments **312** that may be separated by motorized pivotable joints **314**. The number and size of camera mount segments and pivotable joints **314** may vary depending on the embodiments and application of robot unit **302**. Generally, in response to an instruction or commands, one or more of the pivotable joints **314** may activate to rotate or move camera mount **310**. In some embodiments, the pivotable joints **314** may be used to move camera mount **310**

in the X-axis, Y-axis, Z-axis as well as control the roll, pitch, and yaw of the camera mount **310**. Accordingly, through movement in the 6 DOF, camera mount **310** may mimic or replicate the viewing angle of the operator. As further depicted in FIG. 3, a distal end of camera mount **310** may further comprise a sensory capture device.

[0072] As described above, robot unit **302** may be adapted for performing repair work, maintenance work, or other similar situations, tasks, or actions. To perform these actions, robot unit **302** may comprise at least one utility arm. The depicted embodiment as illustrated in FIG. 3 illustrates an exemplary embodiment of robot unit **302** comprising two utility arms **330a**, **330b**. Like camera mount **310** as described above, each of utility arms **330a**, **330b** may comprise a plurality of utility arm segments **332** that may be separated by motorized pivotable joints **334**. The number and size of utility arm segments **332** and pivotable joints **334** may vary depending on the embodiments and application of robot unit **302**. Generally, in response to an instruction or commands, one or more of the pivotable joints **334** may activate to rotate or move utility arms **330a**, **330b**. In some embodiments, the pivotable joints **334** may be used to move utility arms **330a**, **330b** in the X-axis, Y-axis, Z-axis as well as control the roll, pitch, and yaw of the utility arms **330a**, **330b**. Accordingly, through movement in the 6 DOF, each utility arm **330a**, **330b** may mimic or replicate the movement of an operator's arms and hands. In some embodiments, the distal ends **336** of utility arms **330a**, **330b** may comprise one or more tools, flanges, or other apparatus for performing an action such as repair work. In some embodiments, distal ends **336** may comprise an adapter or may be otherwise configured for accepting a tool.

[0073] Remote assembly system **300** may further comprise a remote power source **350**. In some embodiments, the remote power source **350** may be secured to the base **150**. In further embodiments, remote power source **350** may be located within central hub **304**. The remote power source **350** may be used to power camera mount **310**, utility arm **330a**, utility arm **330b**, manipulator **390**, or any combination thereof. Remote power source **350** may be an electric generator, batteries, or any other known power source.

[0074] In further embodiments, robot unit **302** may comprise one or more additional capture devices or sensors **360** for capturing additional information that may be analyzed and/or presented to a user or operator. For example, in some embodiments, robot unit **302** may comprise a thermometer or heat sensor for capturing heat information. In some embodiments, robot unit **302** may comprise an electrical sensor for capturing electrical data. For example, robot unit **302** may be used to work on power lines or in other scenarios involving live power lines or other electrically charged wires or circuitry. accordingly, to avoid damage to the robot unit **302**, the boom assembly **114**, or the utility vehicle **112**, at least one sensor **360** may be a sensor for detecting an electrical current. Additionally, robot unit **302** may comprise at least one sensor **360** that is at least one of an accelerometer, gyroscope, light sensor, or other sensors for detecting the positioning of camera mount **310**, utility arm **330a**, and/or utility arm **330b**. As described in greater detail below, a sensor for detecting the positioning of robot unit **302** may aid in replicating or mimicking movement of an operator using motion controls.

[0075] In some embodiments, and as depicted in FIG. 3, in addition to robot unit **302**, remote assembly system **300** may

further comprise at least one high capacity manipulator **390** or additional robotics assembly that may operate separately or in conjunction with robot unit **302**. For example, in many robotics applications, a delicate balance is often considered when designing the features and capabilities of a robot. Typically, robotics adapted and configured for delicate work and fine adjustments are typically not capable of transporting or holding heavy loads. Conversely, robotics adapted and configured for holding or transporting heavy loads typically lack the structural components to perform delicate or fine-tuned actions. By way of non-limiting example, in telecommunication repairs, heavy parts may need to be lifted from the ground to a telecommunication pole. Lifting a heavy part may require a robotic system configured for transporting heavy loads. However, once in position, the part may need a robotic system configured for delicate or sophisticated operations to install the part in position. In some embodiments, robot unit **302** may be configured and adapted for performing movements or actions directed to sophisticated, delicate, or fine-tuning work, such as cutting wire, loosening screws and bolts. In some embodiments, remote assembly system **300** may comprise at least one high-capacity manipulator **390** for holding or transporting heavy loads that may be too heavy for robot unit **302** to safely hold and transport. Accordingly, through the combination of robot unit **302** and high-capacity manipulator **390**, remote assembly system **300** may perform both dexterous actions and load-bearing actions. In some embodiments, the below-described phase-lifters **400**, **600** may be supported by at least one high capacity manipulator **390**.

#### Cross-Arm Phase-Lifter

[0076] FIGS. 4A and 4B illustrate a first perspective view and a second perspective view, respectively, of a phase-lifter **400** for some embodiments. As discussed above, phase-lifter **400** may be used to grasp onto a cross-arm **402** for manipulation thereof. For example, phase-lifter **400** may clamp onto cross-arm **402** and may be driven to lift the cross-arm to remove the cross-arm from a utility pole (not shown) to allow for maintenance to be performed thereon with a reduced risk of electrical shock.

[0077] Cross-arm **402** comprises a mounting bracket **404** and one or more phase insulators **406**. Cross-arm **402** may be coupled to a utility pole via mounting bracket **404**. Prior to removing cross-arm **402** from the utility pole, mounting bracket **404** may be detached from the utility pole. For example, robot unit **302** may be operated to detach mounting bracket **404** from the utility pole. Insulators **406** may be mounted on top of the cross-arm **402**, and energized power lines **408** may be coupled thereto. Insulators **406** may be tie top insulators, as shown, clamp insulators, vice insulators, or any other type of pole top insulators. In some embodiments, clamp insulators may be used to reduce the stress on the energized power lines **408** when lifting cross-arm **402** as discussed further below. As discussed above, when maintenance needs to be performed, energized power lines **408** are typically removed from insulators **406** and placed onto a temporary phase-holder. The use of the temporary phase-holder requires extra equipment to be brought to a worksite and involves extra steps to perform maintenance.

[0078] Phase-lifter **400** may comprise a structural member **410** coupled at a first end to a first clamping member **412a** and a second clamping member **412b** and coupled at a second end to a third clamping member **412c** and a fourth

clamping member **412d**. In some embodiments, structural member **410** is a crossbar. First clamping member **412a** may comprise a first clamp **414a**, second clamping member **412b** may comprise a second clamp **414b**, third clamping member **412c** may comprise a third clamp **414c** (FIG. 4B), and fourth clamping member **412d** may comprise a fourth clamp **414d** (FIG. 4B). Clamps **414a**, **414c** may be positioned to about a top face and a front face of cross-arm **402**, with clamps **414b**, **414d** positioned to clamp onto a bottom face and a back face of cross-arm **402**. In some embodiments, clamps **414a**, **414b**, **414c**, **414d** are spring-loaded and configured to self-align on cross-arm **402**. In some embodiments, clamps **414a**, **414b**, **414c**, **414d** comprise rubber or plastic padding to protect cross-arm **402** from potential damage due the force applied by clamps **414a**, **414b**, **414c**, **414d**. Clamping members **412a**, **412b** form a first clamping member pair **416a**, and clamping members **412c**, **412d** form a second clamping member pair **416b**. In some embodiments, first clamping member pair **416a** is driven by a first actuator **418a**, and second clamping member pair **416b** is driven by a second actuator **418b**, as discussed further below with respect to FIGS. 5A and 5B.

[0079] Structural member **410** may comprise a bracket **420** protruding therefrom and configured coupled to a sleeve **422**. In some embodiments, bracket **420** extends from near a center of structural member **410**. In some embodiments, sleeve **422** is substantially cylindrical. In some embodiments, sleeve **422** is pivotally coupled to bracket **420**. In some embodiments, sleeve **422** is coupled substantially perpendicular to bracket **420**. Thus, boom extension **424** may be substantially parallel to crossbar **410**. Broadly, sleeve **422** may couple to bracket **420** at any angle. Sleeve **422** may connect structural member **410** to a distal end of a boom extension **424**. For example, boom extension **424** may be received within the sleeve **422**. The boom extension **424** may be coupled to an aerial device extending from a truck or other weighted base (e.g., aerial device **100**). In some embodiments, boom extension **424** is electrically insulating and may be made from fiberglass, for example. Boom extension **424** may also be coupled to a clasp or other pole-top structure fastened around a utility pole, providing stability for the cross-arm phase-lifter. For example, a pole-top structure, such as the below-described pole-clamp, may be coupled to the utility pole below an existing cross-arm. Phase-lifter **400** may then be coupled to the pole-top structure such that a new cross-arm can be attached to phase-lifter **400** and the phases easily transferred from the existing cross-arm to the new cross-arm on phase-lifter **400** disposed proximal to the existing cross-arm. Additionally, high capacity manipulator **390** of robot unit **302** may couple to the boom extension **424**, allowing for the remote operation of the utility pole maintenance by a lineman. Thus, for example, high capacity manipulator **390** may drive phase-lifter **400** to lift cross-arm **402** and hold cross-arm **402** suspended while the dexterous arms are controlled by a remote operator to perform maintenance on the utility pole. Once maintenance is complete, the remote operator can lower cross-arm **402** back onto the utility pole, and the dexterous arms may couple cross-arm **402** back to the utility pole via mounting bracket **404**. In some embodiments, boom extension **424** is an insulating dielectric structure to provide additional electric isolation between energized power lines **408** and the supporting structure (e.g., aerial device, remote assembly system **300**, etc.).

[0080] In some embodiments, high-capacity manipulator **390** may provide over-the-shoulder assistance to robot unit **302**. High-capacity manipulator **390** may reach over, around, or under robot unit **302** to lift and support objects (e.g., phase-lifter **400**) that may be too heavy or large for the high-dexterity arms **330a**, **330b** of robot unit **302**. As discussed above, high-capacity manipulator **390** may support large and heavy structures while arms **330a**, **330b** of robot unit **302** perform repair, attachment, maintenance, as well as any other high-dexterity tasks that may be required by robot unit **302**. High capacity manipulator **390** is discussed further in detail in U.S. application Ser. No. 17/875,743, titled “COOPERATIVE HIGH-CAPACITY AND HIGH-DEXTERITY MANIPULATORS”, the entirety of which is hereby incorporated by reference.

[0081] FIG. 5A illustrates a clamping member pair **416a** formed by clamping members **412a**, **412b** for some embodiments. Clamping member pair **416a** may be substantially similar to clamping member pair **416b** formed by clamping members **412c**, **412d**. Clamping members **412a**, **412b** may be pivotally coupled at a respective first center **502a** and a second center **502b** thereof. For example, clamping members **412a**, **412b** may be coupled using a screw, a bolt, or other like fasteners. In some embodiments, structural member **410** comprises a hole on an end thereof for receiving a fastener therein to couple clamping member pair **416a** thereto.

[0082] First clamping member **412a** may comprise a first end **504a** and a second end **504b** opposite first end **504a**. First end **504a** may be coupled to first clamp **414a** via a bracket **506**, and second end **504b** may be coupled to a first actuator block **508a**. Similarly, second clamping member **412b** may comprise a first end **510a** coupled to second clamp **414b** via a bracket **506**, and a second end **510b** opposite the first end **510a** may be coupled to a second actuator block **508b**. A stud **512** may be received in actuator blocks **508a**, **508b** and may be driven to engage clamping members pair **416a** with the cross-arm **402**.

[0083] FIG. 5B illustrates stud **512** for driving clamping member pairs **416a**, **416b** for some embodiments. Stud **512** may comprise a proximal end **514a**, a distal end **514b**, and a threaded section **514c**. Proximal end **514a** may be unthreaded and configured to couple to a drill or other driving mechanism, such as a motor. For example, robot unit **302** may operate an impact drill and couple the impact drill with proximal end **514a** to drive clamping member pair **416a** to clamp onto cross-arm **402**. In some embodiments, threaded section **514c** engages with a set of internal threads (not shown) within second actuator block **508b**. As such, when stud **512** is driven, the internal threads of second actuator block **508b** and the external threads of threaded section **514c** may engage to thread second actuator block **508b** distally towards first actuator block **508a**, thereby driving first end **510a** of second clamping member **412b** towards first end **504a** of first clamping member **412a**.

[0084] Distal end **514b** may comprise a first stop **516a** and a second stop **516b**, which may be received within first actuator block **508a**. Stops **516a**, **516b** may prevent translation of first clamping member **412a**, thereby allowing second clamping member **412b** to be driven down threaded section **514c** for coupling to cross-arm **402**. Therefore, to grasp onto cross-arm **402**, the operator can operate robot unit **302** to position first clamp **414a** onto a top surface of cross-arm **402** and drive stud **512** to grasp onto cross-arm

**402** with second clamp **414b**. In some embodiments, phase-lifter **400** is configured for clamps **414a**, **414b**, **414c**, **414d** to apply substantially even pressure to the cross-arm. As discussed above, clamps **414a**, **414b**, **414c**, **414d** may comprise a pad (e.g., rubber or plastic) thereon to reduce damage to cross-arm **402** from the force applied thereon. Additionally, the pads may increase the frictional force between clamps **414a**, **414b**, **414c**, **414d** and the cross-arm **402**.

[0085] As illustrated in FIGS. 4A and 4B, clamping member pairs **416a**, **416b** may be driven by distinct actuators **418a**, **418b**. In other embodiments, a singular actuator mechanism may simultaneously drive both clamping pairs **416a**, **416b**. In some embodiments, each clamping pair **416a**, **416b** may be driven by a separate integrated motor. For example, an integrated motor housed between the clamping member pairs **416a**, **416b** may drive the stud **512** in each actuator **418a**, **418b**. The motor may be coupled to a worm gear, for example, to self-lock clamping member pairs **416a**, **416b** when clamped in the desired position.

[0086] It will be appreciated that clamping member pairs **416a**, **416b** may be driven by various actuators without departing from the scope hereof. For example, hydraulic, and/or pneumatic cylinders may be used as actuators **418a**, **418b**. In some embodiments, the actuators are linear actuators. Alternatively, or additionally, in some embodiments, rotary actuators (e.g., hydraulic or pneumatic) may be employed to drive clamping member pairs **416a**, **416b**. Generally, any actuator configured to drive clamping member pairs **416a**, **416b** is contemplated to be within the scope hereof.

[0087] FIGS. 6A and 6B illustrate a second embodiment of the cross-arm phase-lifter, designated as phase-lifter **600** for some embodiments. Phase-lifter **600** may comprise a structural member **602** configured to engage with one or more brackets **604** on cross-arm **402**. In some embodiments, structural member **602** is a plate, and may be substantially rectangular. In some embodiments, brackets **604** are installed onto a front face of the utility pole cross-arm **402**. For example, prior to coupling to cross-arm **402**, brackets **604** may be installed by a lineman or robot unit **302**. For example, brackets **604** may be installed on the ground prior to lifting phase-lifter **600** into the air. As another example, prior to engaging cross-arm **402** with phase-lifter **600**, the arms **330a**, **330b** may install brackets **604** onto cross-arm **402**. Structural member **602** may be oriented substantially parallel to brackets **604**. In some embodiments, structural member **602** comprises one or more pegs **606** (FIG. 6B) that engage within the one or more brackets **604**. Structural member **602** may comprise additional or fewer mounting pegs **606** without departing from the scope hereof. Structural member **602** may comprise various other engaging means for coupling to cross-arm **402**, such as, hooks or magnets, without departing from the scope hereof. In some embodiments, brackets **604** may comprise a slot **608** in which pegs **606** may be received. In some embodiments, slot **608** is tapered. Additionally, a locking mechanism may be implemented to ensure a positive engagement of mounting pegs **606** to brackets **604**.

[0088] Once engaged with cross-arm **402**, phase-lifter **600** may be driven to lift cross-arm **402** off the utility pole, with energized power lines **408** still attached. As described above, phase-lifter **600** may hold cross-arm **402** in suspension to allow for the robot and/or the lineman to operate on the utility pole. Thereafter, phase-lifter **600** may place cross-arm

**402** back onto the pole. In some embodiments, a four-bar mechanism (or other actuator mechanism) may be used to adjust the orientation of structural member **602** relative to sleeve **422**. For example, a four-bar mechanism may be coupled to a proximal end of boom extension **424** (opposite sleeve **422**), and drive boom extension **424** to allow for structural member **602** to be adjusted. The four-bar mechanism may be housed at utility vehicle **112**, for example.

[0089] Phase-lifter **600** may comprise a bracket **420** coupled to the sleeve **422** as discussed above with respect to FIGS. 4A and 4B to connect phase-lifter **600** to boom extension **424**. In some embodiments, high capacity manipulator **390** couples to sleeve **422** to support and drive phase-lifter **400**, **600**. Alternatively high capacity manipulator **390** may couple directly to structural member **410**.

[0090] As discussed above, phase-lifter **400**, **600** may be coupled to a supporting structure. The supporting structure may lift phase-lifter **400**, **600** and hold phase-lifter **400**, **600** to suspend cross-arm **402**. The supporting structure may be a distal end of an aerial device **100** or high capacity manipulator **390**, for example. In some embodiments, the supporting structure is a pole clamp, as discussed further in U.S. application Ser. No. 17/875,674, titled "MANUAL OPERATION OF A REMOTE ROBOT ASSEMBLY", the entirety of which is hereby incorporated by reference. The pole clamp may comprise a first arm and a second arm, and each arm may comprise a clamp to grasp a pole. A four bar linkage may be coupled to arms, and a drive system may be coupled to the four bar linkage. The drive system may comprise a proximal end and a distal end connected by a threaded rod. A motor may be disposed on the proximal end and may be coupled to the threaded rod. The rod may be threadedly engaged with the distal end such that, when the rod is driven by the motor, the distal end moves proximally along the rod and towards the proximal end. As the distal end moves towards the proximal end, the arms may separate and decouple from the pole. As such, to grasp onto a pole, the rod may be threaded in a first direction to move distal end distally away from the proximal end. To detach from the pole, the rod may be threaded in a second direction, opposite from the first direction, to move the distal end towards the proximal end.

[0091] FIG. 7 depicts a method **700** of using phase-lifter **400**, **600** to manipulate cross-arm **402** for some embodiments. As discussed above, in some embodiments, phase-lifter **400**, **600** may be driven and/or supported by a boom assembly, a robot unit, a pole clamp.

[0092] In step **702**, phase-lifter **400**, **600** may be coupled to cross-arm **402**. As described above, in some embodiments, phase-lifter **400** may couple to cross-arm **402** by actuating clamping member pairs **416a**, **416b** to secure cross-arm **402** between clamps **414a**, **414b**, **414c**, and **414d**. In other embodiments, such as when using phase-lifter **600**, coupling to cross-arm **402** may be performed by engaging pegs **606** of the structural member **602** with the brackets **604** of the cross-arm.

[0093] In optional step **704**, energized power lines **408** are moved off insulators **406** of the existing cross-arm **402** and onto the insulators **406** of the new cross-arm **402**. Step **704** may be performed when the cross-arm maintenance includes replacing an existing cross-arm with a new cross-arm, for example. As such, a new cross-arm **402** may be coupled to phase-lifter **400**, **600** at step **702**, and phase-lifter **400**, **600** can be raised to the top of the utility pole. The energized

power lines 408 and insulators 406 may then be removed from the old cross-arm (e.g., using the robot) and installed onto the new cross-arm 402. Thereafter, the old cross-arm may be removed from the utility pole

[0094] In step 706, cross-arm phase-lifter 400, 600 may be lifted to suspend cross-arm 402. Phase-lifter 400, supported by either an aerial boom or robot unit, may be driven to lift up the body of the cross-arm, decoupling the cross-arm mounting bracket 404 from the utility pole (not pictured). In some embodiments, phase-lifters 400, 600 can be manually lifted by a lineman. The lineman or robot unit may interact with phase-lifter 600 at the boom extension 424. The maintenance operations can be performed by a lineman or a dexterous robot assembly.

[0095] Lastly, at step 708, the cross-arm 402 can be re-installed onto the utility pole by lowering cross-arm 402 back onto the utility pole using phase-lifter 400, 600. Utility pole mounting bracket 404 may be used to engage the new cross-arm with the utility pole after maintenance is complete. In some embodiments, robot unit 302 reattaches mounting bracket 404 to cross-arm 402.

[0096] In some embodiments, operations of phase-lifter 400, 600 are performed automatically by robot unit 302. For example, remote assembly system 300 may be programmed to perform the above-described actions of coupling to cross-arm 402, lifting cross-arm 402 an appropriate distance off the utility pole so that operations can be performed thereon, and reinstalling cross-arm 402 onto the pole once operations are complete.

[0097] The following U.S. patent applications, each filed Jul. 28, 2022, are each hereby incorporated by reference in their entirety as if set forth herein verbatim: U.S. Application Ser. No. 63/392,927, titled “REDUCING LATENCY IN HEAD-MOUNTED DISPLAY FOR THE REMOTE OPERATION OF MACHINERY”; U.S. application Ser. No. 17/875,674, titled “MANUAL OPERATION OF A REMOTE ROBOT ASSEMBLY”; U.S. application Ser. No. 17/875,710, titled “AUTONOMOUS AND SEMI-AUTONOMOUS CONTROL OF AERIAL ROBOTIC SYSTEMS”; U.S. application Ser. No. 17/875,743, titled “COOPERATIVE HIGH-CAPACITY AND HIGH-DEXTERITY MANIPULATORS”; U.S. application Ser. No. 17/875,796, titled “ROTARY TOOL FOR REMOTE POWER LINE OPERATIONS”; U.S. application Ser. No. 17/875,821, titled “OPERATION AND INSULATION TECHNIQUES”; U.S. application Ser. No. 17/875,893, titled “COORDINATE MAPPING FOR MOTION CONTROL”; U.S. application Ser. No. 17/875,943, titled “WIRE TENSIONING SYSTEM”; and U.S. Application Ser. No. 63/393,047, titled “ELECTRICALLY INSULATING BLANKET WITH MEMORY SET”. The subject matter described in the foregoing U.S. patent applications may be combined with the subject matter of the present disclosure. For example, one or more embodiments, features, structures, acts, etc. described in any one or more of the foregoing U.S. patent applications may be combined with one or more embodiments, features, structures, acts, etc. described in the present disclosure.

[0098] Although the present teachings have been described with reference to the embodiments illustrated in the attached drawing figures, it is noted that equivalents may be employed, and substitutions made herein without departing from the scope of the present teachings as recited in the claims.

Having thus described various embodiments of the disclosure, what is claimed as new and desired to be protected by Letters Patent includes the following:

1. A system for remotely operating on energized power lines, comprising:

a robotically controlled phase-lifter, comprising:

a boom extension comprising a distal end and proximal end configured to be coupled to a robotic unit;

a cross bar coupled to the distal end of the boom extension, the cross bar comprising a first end and a second end;

a first clamping pair coupled to the first end; and

a second clamping pair coupled to the second end,

the first clamping pair and the second clamping pair providing coupling points for coupling the robotically controlled phase-lifter to a cross-arm of an energized power line.

2. The system of claim 1, further comprising at least one actuator for actuating at least one of the first clamping pair or the second clamping pair to clamp onto the cross-arm.

3. The system of claim 2, wherein the first clamping pair and the second clamping pair comprise:

a first clamping member pivotally coupled to and opposing a second clamping member,

wherein the first clamping member comprises a first proximal end coupled to a first actuator block and the second clamping member comprises a second proximal end coupled to a second actuator block.

4. The system of claim 3, wherein the first clamping pair and the second clamping pair further comprise:

a threaded stud received within the first actuator block and the second actuator block and configured to move the first actuator block towards the second actuator block, thereby reducing a distance between the first clamping member and the second clamping member.

5. The system of claim 4,

wherein the threaded stud comprises an unthreaded section configured to couple to a driver to rotate the threaded stud to move the first actuator block towards the second actuator block.

6. The system of claim 5, wherein the driver is an impact drill operable by the robotic unit.

7. The system of claim 1, further comprising the robotic unit comprising:

a first robotic arm is configured to hold the robotically controlled phase-lifter in a suspended state; and

at least one second robotic arm is configured to actuate the robotically controlled phase-lifter.

8. A system for remotely operating on energized power lines, comprising:

a robotically controlled phase-lifter, comprising:

a boom extension comprising a distal end and proximal end configured to be coupled to a robotic unit;

a structural member disposed at the distal end of the boom extension and having a first side configured to be oriented towards a cross-arm of an energized power line; and

at least one peg disposed on the first side of the structural member, the at least one peg configured to be coupled to a bracket located on the cross-arm.

9. The system of claim 8,

wherein the bracket is a first bracket and the cross-arm further comprises a second bracket,

wherein the at least one peg comprises a first peg and a second peg, and

wherein the first peg is configured to couple to the first bracket and the second peg is configured to couple to the second bracket.

**10.** The system of claim **8**, further comprising a four-bar mechanism for adjusting an orientation of the structural member.

**11.** The system of claim **8**, further comprising the robotic unit, the robotic unit comprising:

a first robotic arm configured to drive the robotically controlled phase-lifter to lift the cross-arm off the energized power line.

**12.** The system of claim **11**, wherein the robotic unit further comprises:

a second robotic arm configured to perform maintenance while the first robotic arm lifts the cross-arm.

**13.** A method for remotely operating on energized power lines, comprising:

providing a robotically controlled phase-lifter, comprising:

a boom extension comprising a distal end and proximal end configured to be coupled to a robotic unit; and

a coupling assembly, comprising:

at least one clamping pair for clamping onto a cross-arm of an energized power line, the cross-arm coupled to a utility pole of the energized power line; or

at least one peg configured to couple to a bracket disposed on the cross-arm;

coupling the robotically controlled phase-lifter to the cross-arm; and

lifting the cross-arm from the utility pole.

**14.** The method of claim **13**, wherein coupling the robotically controlled phase-lifter to the cross-arm comprises:

clamping the at least one clamping pair to the cross-arm using the robotic unit.

**15.** The method of claim **14**, wherein the robotic unit is configured to operate at least one tool to actuate the at least one clamping pair.

**16.** The method of claim **13**, wherein coupling the robotically controlled phase-lifter to the cross-arm comprises:

moving, via the robotic unit, the robotically controlled phase-lifter to engage the at least one peg with the bracket.

**17.** The method of claim **13**, wherein the cross-arm comprises insulators supporting the energized power lines and the method further comprises:

removing, using the robotic unit, the energized power lines from the insulators.

**18.** The method of claim **17**, wherein the robotic unit comprises a first robotic arm configured to lift the cross-arm and a second robotic arm configured to remove the energized power lines.

**19.** The method of claim **17**, wherein the cross-arm is an existing cross-arm and the method further comprises:

installing, using the robotic unit, the insulators onto a new cross-arm; and

transferring, using the robotic unit, the energized power lines from the existing cross-arm to the insulators.

**20.** The method of claim **19**, further comprising:

installing the new cross-arm onto the utility pole.

\* \* \* \* \*