




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A46B 7/06, 9/04		A1	(11) International Publication Number: WO 96/38069
			(43) International Publication Date: 5 December 1996 (05.12.96)
(21) International Application Number: PCT/US96/08045 (22) International Filing Date: 30 May 1996 (30.05.96) (30) Priority Data: 08/454,697 31 May 1995 (31.05.95) US (60) Parent Application or Grant (63) Related by Continuation US 08/454,697 (CON) Filed on 31 May 1995 (31.05.95)		(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>	
(71) Applicant (for all designated States except US): BERNSTEIN, David [US/IL]; 1 Weiselberger Street, 42400 Netanya (IL). (71)(72) Applicant and Inventor: AVIDOR, Joseph [IL/IL]; 20 Hapardes Street, 47405 Ramat Hasharon (IL). (74) Agents: WEST, Paul, B.; Ladas & Parry, 26 West 61st Street, New York, NY 10023 (US) et al.			

(54) Title: TOOTHBRUSH HAVING SPRING-MOUNTED BRISTLE HOLDERS

(57) Abstract

A toothbrush includes a brush head (3) formed with a plurality of cavities (4), and an assembly of bristle holders (5) received in the cavities (4), the bristle holders (5) being fixed to and interconnected together by spring elements (8) engageable with the bottoms of the cavities (4) and normally urging the bristle holders (5) to a projected position outwardly of the brush head (3), but permitting the bristle holders (5) to be displaced inwardly to a retracted position within their respective cavities (4).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

TOOTHBRUSH HAVING SPRING-MOUNTED BRISTLE HOLDERS

The present invention relates to toothbrushes, and particularly to toothbrushes having spring-mounted bristle holders.

A large number of different types of toothbrushes having spring mountings for the bristle holders have been designed and are described in the patent literature, for example in US Patents 5,184,368, 4,694,844 and 2,935,755. However, one of the drawbacks in such constructions is the relatively large number of parts which must be produced and assembled, so that the cost for such toothbrushes is generally very high as compared to conventional toothbrush. Despite the advantages of toothbrushes with spring-mounted bristles, their high cost substantially limits the ability of the public to purchase and use them.

An object of the present invention is to provide a toothbrush which includes spring-mounted bristle holders, but which can be produced in volume and at relatively low cost as compared to other toothbrushes of this type.

According to one aspect of the present invention, there is provided a toothbrush comprising: an elongated handle; a brush at an end of the handle and including a retractable-bristle section having a longitudinal axis and formed with a plurality of cavities; a plurality of bristle holders, each holding a bunch of bristles and each displaceably mounted in a respective one of the cavities; and spring elements urging the bristle holders to a projecting position outwardly of their respective cavities, but permitting the bristle holders to be displaced to a retracted position inwardly of their respective cavities; characterized in that each of the cavities, and its respective bristle holder, extends for substantially the complete width of the retractable-bristle section of the brush head transversely of the longitudinal axis and is spaced from each other along the longitudinal axis; and in that the spring elements interconnect the bristle holders and support them in their respective cavities of the retractable-bristle section of the brush head.

According to a further feature in the described preferred embodiments, the spring elements are integrally formed with the bristle holders as a unitary assembly of plastic material.

According to a further aspect of the present invention, there is provided a toothbrush comprising: a handle having a brush head at an end thereof; the brush head including a top wall and a bottom wall extending longitudinally of the brush head in parallel spaced relation; a plurality of displaceable bristle holders displaceably mounted in the brush head between the top and bottom walls, and being spring-urged towards the top wall to a projected position but being displaceable

towards the bottom wall to a retracted position; each of the displaceable bristle holders including at least one bunch of bristles; and at least one further bunch of bristles fixed to the brush head.

A toothbrush constructed in accordance with the foregoing features permits the toothbrush to be built of relatively few parts which can be produced and assembled at relatively low cost. In addition, when the toothbrush is properly used by applying up-and-down motions parallel to the bristle holders, the bristles better penetrate the spaces between the teeth for more efficient cleaning.

Further features and advantages of the invention will be apparent from the description below.

The invention is herein described, by way of example only, with reference to the accompanying drawings, wherein:

Fig. 1 is an exploded three-dimensional view illustrating the main components of a toothbrush constructed in accordance with the present invention;

Fig. 2 is a top plan view of the brush head illustrated in Fig. 1;

Fig. 3 is a longitudinal sectional view of the brush head of Fig. 2 illustrating the normal condition of the bristle holder;

Fig. 4 is a view corresponding to that of Fig. 3 but illustrating the depressed condition of some of the bristle holders;

Fig. 5 is a three-dimensional view illustrating a modification in the construction of the brush head;

Fig. 6 is a three-dimensional view illustrating a modification in the construction of the leaf springs connecting the bristle holders;

Fig. 7 is a view similar to that of Fig. 3 but illustrating another construction of the leaf springs connecting the bristle holders; and

Fig. 8 is a three-dimensional view illustrating a further toothbrush constructed in accordance with the present invention.

The toothbrush illustrated in Figs. 1 and 2 comprises a handle 2 at one end integrally formed at its opposite end with a brush head 3. The brush head 3 is formed with a retractable bristle section including a plurality of rectangular cavities 4 each extending transversely to the longitudinal axis LA (Fig. 2) of the toothbrush and spaced longitudinally of the toothbrush.

Each of the cavities 4 is adapted to receive a bristle holder 5 of complementary shape as the respective cavity. Each bristle holder 5 is formed with a plurality of cylindrical pockets 6 along its length (i.e., along the width of the toothbrush), with each pocket filled with an individual

bunch of bristles 7. All the bristle holders 5 are joined and interconnected together into a common assembly by a plurality of elastic sections defining spring elements 8 each fixed between a pair of adjacent bristle holders.

Preferably, the bristle holders 5 are produced as an integral unit, e.g., by injection molding, with the spring elements 8 of the same material as the bristle holders and formed as integral hinges interconnecting the bristle holders. The cavities 4 are preferably formed through the complete thickness of the brush head 3 permitting the assembly of the bristle holders 5 and their integrally-formed spring elements 8 to be inserted into the cavities 4 via the bottom side of the brush head 3, with the lower edges of the partitions 9 between the cavities 4 engageable with the bends of the spring elements 8, as shown in Fig. 3. The cavities of the brushhead 3 are closed by a common bottom wall 10 fitted into the bottom of the brush head.

The interconnecting spring elements 8 are each formed with a pair of legs 8a, 8b fixed at their outer ends to the respective pair of bristle holders 5 and joined at their inner ends by a U-shaped bend 8c. The upper faces of the bends 8c engage the lower surface of the respective partition wall 9, whereas the lower faces of the bends 8c engage the upper surface of the bottom wall 10.

As shown in Figs. 3 and 4, the spring elements 8 normally urge their respective bristle holders 5 to their projected positions, shown in Fig. 3, wherein the upper surfaces of the bristle holders engage limit shoulders 11 formed in the brush head 3, and particularly in the partition walls 9 between the cavities 4. Spring elements 8, however, permit the individual bristle holders 5 to be displaced inwardly to a retracted position within their respective cavities 4 at the time of brushing, as shown in Fig. 4.

The closure plate 10 is formed with a plurality of drain openings 12, as seen particularly in Fig. 1, to permit the water to drain from the brush head. In addition the outer walls of the brush head 3, and also its partition walls 9 between the cavities 4, are similarly formed with drain openings 13 and 14, respectively.

It will thus be seen that the toothbrush illustrated in Figs. 1 and 2 may be constructed of but a few parts, namely, the handle 2 and the brush head 3, the assembly of bristle holders 5 integrally formed with the interconnecting spring elements 8, and the bottom wall 10, and that these parts may be assembled in a quick and simple manner. Such an arrangement, wherein the bristle holders 5 extend transversely of the brush head 3, tends to encourage the user to brush the teeth parallel to the bristle holders, i.e., with an up-and-down motion, such that the bristles 7

carried by the holders 5 move parallel to the direction of the teeth and therefore better enter the spaces between the teeth for more efficient cleaning.

Fig. 5 illustrates another toothbrush construction including a handle 22 and a brush head 23 formed with a plurality of transversely-extending cavities 24 each receiving a bristle holder 25 of a bristle holder assembly. In the modification of Fig. 5, however, the bristle holders 25 are not formed with a plurality of individual cylindrical pockets (6, Fig. 1) for receiving the bristles, but rather are formed with a single elongated pocket 26 extending the length of the bristle holder and filled with the bristles 27. Such a construction not only reduces the number of operations required for applying the bristles to their respective holders, but also permits a larger quantity of bristles to be carried by the brush head. In all other respects, the construction illustrated in Fig. 5 may be the same as described above with respect to Figs. 1-4.

Fig. 6 illustrates a modification in the construction of the interconnecting spring elements 8'. In this modification, the legs 8a', 8b' of each spring element are formed with a plurality of interruptions 8d' spaced along their lengths, with the interruptions of one spring element being staggered with respect to the interruptions of the adjacent spring elements. Such a construction increases the flexibility of the interconnecting spring elements and permits larger displacement magnitudes of the bristle holders.

Fig. 7 illustrates a further modification wherein each leg of each spring element 8'' is of zigzag configuration, as shown at 8a'' and 8b'' in Fig. 7, to better accommodate the deflection of the spring elements during use.

In the above-described constructions, all the bristle holders of the brush head are retractable. Fig. 8 illustrates another construction wherein the brush head includes fixed bristle holders in addition to retractable-bristle holders.

Thus, the toothbrush illustrated in Fig. 8 includes a handle 32 and a brush head 33 at one end. The brush head is formed with a retractable-bristle section including a plurality of cavities 34 extending transversely for substantially the complete width of the respective section and spaced longitudinally of the brush head. A bristle holder 35 is displaceably mounted in each cavity 34. Each bristle holder is formed with a plurality of cylindrical pockets 36 receiving a bunch of bristles 37.

The retractable-bristle section of brush head 33 is flanked on each of its opposite sides by an additional bristle holder 38, 39, fixed in the brush head 33 in alignment with each of the displaceable bristle holders 35. Preferably, the fixed bristle holders 38 hold bristles slightly diverging from the bristles 37 carried by the displaceable bristle holders 35.

While the invention has been described with respect to several preferred embodiments, it will be appreciated that these are set forth merely for purposes of example, and that many other variations may be made. For example, in order to reduce the initial tooling costs, the interconnecting spring elements 8, may be produced as a separate unit and assembled with the bristle holders 5 into a common assembly before being assembled into the brush head. Further, the assembly of bristle holders 5 and interconnecting spring elements 8 may be inserted via the top of the brush head 3, in which case the bottom wall 10 could be integrally formed with the brush head 3 and the handle 2, and could be retained within the brush head by a retainer member formed with the partition walls 9 applied over the insert assembly.

Many other variations, modifications and applications of the invention will be apparent.

CLAIMS

1. A toothbrush, comprising:
 - an elongated handle;
 - a brush head at an end of the handle and including a retractable-bristle section having a longitudinal axis and formed with a plurality of cavities;
 - a plurality of bristle holders, each holding a bunch of bristles and each displaceably mounted in a respective one of said cavities;
 - and spring elements urging said bristle holders to a projecting position outwardly of their respective cavities, but permitting the bristle holders to be displaced to a retracted position inwardly of their respective cavities;characterized in that each of said cavities, and its respective bristle holder, extends for substantially the complete width of said retractable-bristle section of the brush head transversely of said longitudinal axis and is spaced from each other along said longitudinal axis; and in that said spring elements interconnect said bristle holders and support them in their respective cavities of said retractable-bristle section of the brush head.
2. The toothbrush according to claim 1, wherein said spring elements are integrally formed with said bristle holders as a unitary assembly of plastic material.
3. The toothbrush according to claim 1, wherein said retractable-bristle section of the brush head is closed by a bottom wall, and said spring elements engage said bottom wall.
4. The toothbrush according to claim 3, wherein said bottom wall is formed with a plurality of drain openings.
5. The toothbrush according to claim 3, wherein said spring elements include U-shaped bends having lower faces engaging said bottom wall.
6. The toothbrush according to claim 5, wherein said cavities are defined by partition walls integrally formed with said brush head and engageable with said U-shaped bends.
7. The toothbrush according to claim 6, wherein said partition walls are formed with a plurality of drain openings.
8. The toothbrush according to claim 7, wherein each of said spring elements further includes a pair of legs connected together at respective inner ends thereof by said U-shaped bends, and connected to the bristle holders at respective outer ends thereof.
9. The toothbrush according to claim 8, wherein each of said legs of each spring element has a plurality of interruptions spaced along its length.

10. The toothbrush according to claim 9, wherein the interruptions of one pair of legs are staggered with respect to the interruptions of the adjacent pair of legs.

11. The toothbrush according to claim 9, wherein each of said legs of each spring element is of a zigzag configuration.

12. The toothbrush according to claim 1, wherein said retractable bristle section extends for substantially the complete width of the brush head.

13. The toothbrush according to claim 1, wherein said retractable bristle section is flanked on each of its opposite sides widthwise thereof by a bunch of bristles fixed in the brush head in alignment with each of said displaceable bristle holders.

14. A toothbrush comprising:

a handle having a brush head at an end thereof carrying a plurality of bristles;

said brush head having a longitudinal axis and being formed with a plurality of cavities;

said bristles being carried by an assembly of a plurality of bristle holders received in said cavities and interconnected together as a common assembly by spring elements fixed to and between said bristle holders.

15. The toothbrush according to claim 14, wherein each of said cavities, and each of said bristle holders therein, extends substantially for the complete width transversely of said longitudinal axis of the brush head.

16. The toothbrush according to claim 14, wherein each of said spring elements includes a pair of legs joined together at respective inner ends and fixed at respective outer ends to the bristle holders.

17. The toothbrush according to claim 16, wherein said pair of legs of each of said spring elements are joined together at respective inner ends by a U-shaped bend engageable with a bottom wall of the brush head.

18. The toothbrush according to claim 17, wherein said cavities are defined by partition walls integrally formed with said brush head and engageable with said U-shaped bends.

19. The toothbrush according to claim 14, wherein said spring elements are integrally formed with and of the same material as said bristle holders.

20. A toothbrush comprising:

a handle having a brush head at an end thereof;

said brush head including a top wall and a bottom wall extending longitudinally of the brush head in parallel spaced relation;

a plurality of displaceable bristle holders displaceably mounted in said brush head between said top and bottom walls, and being spring-urged towards said top wall to a projected position but being displaceable towards said bottom wall to a retracted position;

each of said displaceable bristle holders including at least one bunch of bristles;

and at least one further bunch of bristles fixed to the brush head.

21. The toothbrush according to claim 20, wherein each of said bristle holders extends transversely across the brush head and said bristle holders are spaced from each other longitudinally of the brush head; and wherein said fixed bunch of bristles is fixed to the brush head laterally of said displaceable bristle holders along at least one longitudinal side of the brush head.

22. The toothbrush according to claim 21, wherein there is at least one fixed bunch of bristles fixed to the brush head laterally of and aligned with each of said bristle holders.

23. The toothbrush according to claim 22, wherein there are two of said fixed bunches of bristles fixed to the brush head laterally on opposite longitudinal sides of and aligned with each of said bristle holders.

24. The toothbrush according to claim 20, wherein each of said displaceable bristle holders extends substantially for the complete width transversely of the brush head.




FIG.1

2/4




FIG. 2




FIG. 3




FIG. 4

3/4

FIG.5




FIG.6





FIG 7

4/4




FIG. 8

INTERNATIONAL SEARCH REPORT

 International application No.
PCT/US96/08045

A. CLASSIFICATION OF SUBJECT MATTER IPC(6) :A46B 7/06, 9/04 US CL :15/167.1, 201 According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) U.S. : 15/167.1, 201 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched NONE Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) NONE		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US, A, 2,882,544 (HADIDIAN) 21 APRIL 1959.	1-24
A	US, A, 2,935,755 (LEIRA ET AL) 10 MAY 1960.	1-24
A	US, A, 3,683,442 (HOLLY) 15 AUGUST 1972.	1-24
A	US, A, 4,691,405 (REED) 08 SEPTEMBER 1987.	1-24
A	US, A, 4,694,844 (BERL ET AL) 22 SEPTEMBER 1987.	1-24
A	US, A, 5,138,734 (CHUNG) 18 AUGUST 1992.	1-24
A	US, A, 5,184,368 (HOLLAND) 09 FEBRUARY 1993.	1-24
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family	
Date of the actual completion of the international search 26 JUNE 1996		Date of mailing of the international search report 12 JUL 1996
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 Facsimile No. (703) 305-3230		Authorized officer MARK SPISICH <i>Stacia Sinuit for</i> Telephone No. (703) 308-0861