



- (51) **International Patent Classification:**
E04F 15/02 (2006.01) *E04F 13/08* (2006.01)
- (21) **International Application Number:**
PCT/EP2020/050442
- (22) **International Filing Date:**
09 January 2020 (09.01.2020)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
19199234.6 24 September 2019 (24.09.2019) EP
- (71) **Applicant: VÄLINGE INNOVATION AB [SE/SE];**
Prästavägen 513, SE-263 64 VIKEN (SE).
- (72) **Inventors: YLIKANGAS, Roger;** Rapsvägen 112, 263 54 LERBERGET (SE). **NILSSON, Anders;** Byalagsgatan 30, 256 56 HELSINGBORG (SE). **QUIST, Karl;** Polhemsgatan 8, 263 37 HÖGANÄS (SE).
- (74) **Agent: ENGSTRAND, Ola;** Välinge Innovation AB, Prästavägen 513, 263 65 VIKEN (SE).
- (81) **Designated States** (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN,

HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW.

(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*

Published:

— *with international search report (Art. 21(3))*



WO 2021/058136 A1

(54) **Title:** BUILDING PANEL




FIG. 6
A-A




FIG. 7
B-B

(57) **Abstract:** Building panels, such as a floor panels or wall panels. The panels comprising a first mechanical locking system at respective parallel and opposite third and fourth edges (13, 14), such as long edges, configured to cooperate for horizontal and vertical locking between two adjacent building panels (10, 20), preferably by means of a folding motion. The panels further comprising a second locking system at respective parallel and opposite first and second edges (11, 12), such as short edges, configured to cooperate for horizontal and vertical locking of two adjacent building panels (10, 30). An upper edge portion of one of the third edge or fourth edge (13, 14), preferably the third edge (13), comprises a first lower lip portion (139) configured to cooperate with a first upper lip portion (149) of an upper edge portion of the other of the third and fourth edge of an adjacent panel (20) when the third and fourth edges are arranged in locking engagement.

BUILDING PANEL

TECHNICAL FIELD

The disclosure generally relates to the field of building panels.

BACKGROUND OF INVENTION

5 Laminate flooring usually comprise a core of a 6-12 mm fibre board, a 0.2-0.8 mm thick upper decorative surface layer of laminate and a 0.1-0.6 mm thick lower balancing layer of laminate, plastic, paper or like material. A laminate surface comprises melamine-impregnated paper. The most common core material is fibreboard with high density and good stability usually called
10 HDF – High Density Fibreboard. Sometimes also MDF – Medium Density Fibreboard – is used as core.

 Laminate floor panels of this type have been joined mechanically by means of so-called mechanical locking systems. These systems comprise locking means, which lock the panels horizontally and vertically. The mechanical
15 locking systems are usually formed by machining of the core of the panel. Alternatively, parts of the locking system may be formed of a separate material, for instance aluminium or HDF, which are integrated with the floor panel, i.e. joined with the floor panel in connection with the manufacture thereof.

 The main advantages of floating floors with mechanical locking systems
20 are that they are easy to install. They may also easily be taken up again and used once more at a different location. However, know systems suffer from drawbacks, for example in respect moisture control. As such, there is room for improvements in the technical field.

SUMMARY

25 An overall objective of the present disclosure is to provide a building panel which facilitates improved control of moisture, such as water. Improved moisture control may include not limited to improved sealing between assembled

building panels, improved resistance to water penetration through a surface comprising assembled building panels.

It is a further object to provide a building panel which facilitates alignment of assembled such building panels.

5 It is thus a further object of the present invention to provide a building panel which facilitates improved moisture control of a lay of building panels, such as a floating floor. In particular, it is an object to provide a building panel for improving moisture control and/or at least reduce the possibility of water penetration of the T-joints of such floor lay.

10 The above objects of embodiments of the invention may be achieved wholly or partly by locking systems and floor panels according to the disclosure. Embodiments of the invention are evident from the description and drawings.

DEFINITION OF SOME TERMS

15 In the following text, the visible surface of the installed floor panel is called "*front surface*", while the opposite side of the floor panel facing the subfloor is called "*rear surface*". "*Horizontal plane*" relates to a plane, which is parallel to the *front side*. Directly adjoining upper parts of two neighboring joint edges of two joined floor panels together define a "*vertical plane*" perpendicular to the *horizontal plane*. The outer parts of the floor panel at the edge of the floor
20 panel between the *front surface* and the rear surface are called "*joint edge*". As a rule, the *joint edge* has several "*joint surfaces*" which can be vertical, horizontal, angled, rounded, beveled, etc. These *joint surfaces* exist on different materials, for instance laminate, fiberboard, wood, plastic, metal (in particular aluminum) or sealing materials.

25 By "vertical locking" is meant locking parallel to the vertical plane. By "horizontal locking" is meant locking parallel to the horizontal plane.

By "up" is meant towards the front surface, by "down" towards the rear surface, by "inwardly" mainly horizontally towards an inner and centre part of the panel and by "outwardly" mainly horizontally away from the centre part of the
30 panel.

By "*locking*" or "*locking system*" are meant cooperating connecting means which interconnect the floor panels vertically and/ or horizontally. By "*mechanical locking system*" is meant that locking can take place without glue. *Mechanical locking systems* can in many cases also be joined by glue.

5 By "*decorative surface layer*" is meant a surface layer, which is mainly intended to give the floor its decorative appearance. "*Wear resistant surface layer*" relates to a high abrasive surface layer, which is mainly adapted to improve the durability of the front side. This conclude in that a "*decorative wear resistant surface layer*" is a layer, which is intended to give the floor its
10 decorative appearance as well as improve the durability of the front side. A surface layer is typically applied to the core.

Embodiments of the present invention are particularly suitable for use in floating floors, which are formed of floor panels which are joined mechanically with a locking system integrated with the floor panel, i.e. mounted at the factory,
15 are made up of one or more upper layers of wood or wood veneer, decorative laminate, powder based surfaces or decorative plastic material, an intermediate core of wood-fibre-based material or plastic material and preferably a lower balancing layer on the rear side of the core. Floor panels of solid wood or with a surface layer of cork, linoleum, rubber or soft wear layers, for instance needle felt
20 glued to a board, printed and preferably also varnished surface and floors with hard surfaces such as stone, tile and similar materials are included.

The following description of known technique, problems of known systems and objects and features of embodiments of the invention will therefore, as a non-restrictive example, be aimed above all at this field of application and in
25 particular at panels formed as rectangular floor panels with long and shorts edges intended to be mechanically joined to each other on both long and short edges.

The long and short edges are mainly used to simplify the description of embodiments of the invention. The panels may be square. It should
30 be emphasised that embodiments of the invention may be used in any floor panel and it may be combined with all types of known locking system formed on the long edges and/or short edges, where the floor panels are intended to be

joined using a mechanical locking system connecting the panels in the horizontal and/or vertical directions on at least two adjacent edges.

In one aspect of the invention there is provided a set of similar or essentially identical building panels, such as a floor panels or wall panels. The panels comprise a first mechanical locking system at respective parallel and opposite third and fourth edges being long edges of the panel. The first mechanical locking system comprises at the third edge a locking groove configured to receive a first locking tongue of a fourth edge of an adjacent panel by means of a folding displacement of the adjacent panel for vertical locking between two adjacent building panels. A second locking system is at respective parallel and opposite first and second edges, such as short edges of the panel. The second locking system being configured to cooperate for horizontal and vertical locking of two adjacent building panels, preferably by means of a vertical motion, such as vertical folding. An upper edge portion of one of the third edge or fourth edge, preferably the third edge, comprises a first lower lip portion configured to cooperate with a first upper lip portion of an upper edge portion of the other of the third and fourth edge of an adjacent panel when said third and fourth edges are assembled in locking position. The first upper lip portion of the fourth edge is configured to form a tight fit around the first lower lip portion when the first lower lip portion is received under the first upper lip portion in response to said folding displacement. Further advantages and embodiments being set forth in the appended dependent claims and detailed description.

BRIEF DESCRIPTION OF DRAWINGS

The disclosure will in the following be described in connection to exemplary embodiments and in greater detail with reference to the appended schematic drawings, wherein:

FIG. 1 shows a schematic illustration of a floor board comprising locking systems according to known technology.

FIG.2 shows a schematic illustration of the floor board of FIG.1 in locked position with an adjacent building panel.

FIG. 3 shows a schematic illustration of a further floor board being assembled to the floorboards of FIG.2 by means of a vertical motion (vertical folding).

FIGS 4A-4B show schematic illustrations of a cross sectional views of locking systems according to known technology.

FIGS 5A-5C show schematic illustrations a locking system according to embodiments of the invention.

FIG. 6 shows a schematic cross-sectional view of the first locking system at the section A-A of FIG. 5A according to an embodiment of the disclosure.

FIG. 7 shows a schematic cross-sectional view of the second locking system at the section B-B of FIG. 5C according to an embodiment of the disclosure.

FIG. 8 is a schematic cross-sectional view of the first locking system at the section C-C of FIG.12 according to an embodiment assembled as a wall.

FIG. 9 is a schematic cross-sectional view of the first locking system at the section D-D of FIG.12 according to an embodiment assembled as a wall.

FIG. 10 shows a schematic illustration of the second locking system according to an embodiment being assembled by means of a vertical motion.

FIG. 11 shows a further schematic illustration of the second locking system of FIG. 10 being assembled by means of a vertical motion.

FIG. 12 is a schematic illustration of an exemplary embodiment assembled as a wall.

FIG. 13 is a schematic illustration of an exemplary embodiment assembled as a floor.

FIGS 14A-14B show cross cuts of a panel comprising a pocket according to an embodiment.

FIGS 15A-15B show cross cuts of a panel comprising a pocket according to an embodiment.

5 FIGS 16A-16B show cross cuts of a panel comprising a pocket according to an embodiment.

FIGS 17A-17B show cross cuts of a panel comprising a pocket according to an embodiment.

10 FIGS 18A-18B show cross cuts of a panel comprising a pocket according to an embodiment.

FIGS 19A-19B show cross cuts of a panel comprising a pocket according to an embodiment.

FIG. 20A shows a panel according to an embodiment comprising respective lower lip portions provided in displaced planes.

15 FIG. 20B shows cross cuts of a first edge and a second edge of two assembled panels according to the embodiment of FIG.20A.

FIG. 20C shows a cross cut of a third edge and a fourth edge of two assembled panels according to the embodiment of FIG.20A.

20 DETAILED DESCRIPTION

Embodiments of the disclosure will now be described with reference to the appended schematic drawings. It should be emphasised that improved or different functions may be achieved using combinations of the embodiments.

25 All embodiments may be used separately or in combinations. Angles, dimensions, rounded parts, spaces between surfaces, etc. are only examples and may be adjusted within the basic principles of the invention.

A known building panel comprising mechanical locking systems is illustrated in FIG. 1.

A mechanical locking system typically comprises a tongue and a tongue groove for vertical locking and a locking element and a locking groove for horizontal locking. It typically has at least four pairs of active cooperating locking surfaces, two pairs for vertical locking and two pairs for horizontal locking. The locking system comprises several other surfaces, which generally are not in contact with each other and can therefore be produced with considerably larger tolerance than the cooperating locking surfaces.

Laminate floorings are usually composed of a core consisting of a 6 - 9 mm fiberboard, a 0.20 mm thick upper surface layer and a lower balancing layer. The surface layer provides appearance and durability to the floor panels. The core provides stability and the balancing layer keeps the board level when the relative humidity (RH) varies during the year.

FIGS. 4A illustrates, according to known art, a typical first mechanical locking system (strip lock), which can be locked with angling (see FIG. 3) and which is widely used on the market, in particular for assembling respective long edges of panels to each other. FIG. 4A shows a vertical cross section of the floor panel is shown of a part of a long side 13' of the floor panel 20', as well as a part of a long side 14' of the floor panel 10'. The bodies of the floor panels 10', 20' can be composed of a fiberboard body or core, which supports here, a wear resistant and decorative surface layer on its front side and a balancing layer on its rear side (underside). The locking system has a tongue 14h' and a tongue groove 13j' which locks the panels in a vertical direction V with upper 53 and lower 56 tongue surfaces that cooperate with upper 43 and lower 46 tongue grooves surfaces. A locking strip 13a' is formed from the body and supports a locking element 13b'. Therefore the locking strip 13a' and the locking element 13b' in a way constitute an extension of the lower part of the tongue groove 13j'. The locking element 13b' formed on the strip 13a' has an operative locking element surface 13m' which cooperates with an operative locking groove surface 14m' in a locking groove 14g' in the opposite locking groove side of the floor panel 10'. By the engagement between the horizontal operative locking surfaces

13m', 14m' a horizontal locking of the floor panels 10', 20' transversely of the joint edge is obtained if the panels are pulled apart.

A known second locking system, shown in FIGS 4B, can also be formed with a flexible tongue 11i' (fold lock) typically used at short edges 11', 12' as shown in FIGS 4B, which can be displaced during locking. Such a locking system can be locked with a vertical movement as shown in FIG.3 where the first edge 11' of panel 10' is assembled to the second edge 12' of panel 30' by means of a vertical motion.

The displaceable tongue 11i' is configured to cooperate with the second tongue groove 12j' for locking in a vertical direction. The displaceable tongue 11i' is a separate part and is made of, e.g., plastic, and inserted in a displacement groove 11k' at the first edge 11' of the first panel 10'. The tongue 11i' is pushed into a displacement groove 11k' during a vertical assembling of the first and the second edge of the first and the second panel. The displaceable tongue 11i' springs back and into the second tongue groove 12j' at the second edge 12' of the panel 30' when the panels have reached a locked position.

A third 13' and a fourth edge 14' of the respective panels are provided with the first locking system, which enables assembling to an adjacent panel 20' by an angling movement to obtain a simultaneous assembling of the first 11' and the second 12' edges and the third 13' and the fourth edges 14' as shown in FIG.3.

FIGS. 4A-B show cross sections of different embodiments of the known locking systems during assembling of a first and a second panel 10', 20'.

Exemplary embodiments of the invention are shown in FIGS 5A-5C and FIGS 6 through 11.

Referring to FIGS 5A-C, 6 and 7, a first mechanical locking system shown in FIG.6 is formed with tongue 14h and groove 13j and configured to be assembled by means of an angling movement. The fourth edge 14 may comprise a first locking protrusion 14e in the shape of a locking tongue, provided with a first lower edge surface 14f. An embodiment of the second locking system

is shown in FIG. 7, wherein the second edge 12 is provided with a second locking protrusion 12e which may be a locking tongue 12h, provided with a second lower edge surface 12f, preferably the first and second lower edge surfaces 12f, 14f are configured to cooperate with a respective of the first and second upper surfaces 11c, 13c of a first and a second locking strip 13a, 11a of adjacent panels, such as the second 20 panel shown in FIG.6 and the third panel 30 as shown for instance in FIG.7.

The first mechanical locking system may comprise a first tongue groove 13j at one of a third edge 13 or fourth 14 edge, for example the third edge 13, and a first locking tongue 14h at the other of the third or fourth edge, for example the fourth edge 14. The first locking tongue 14h and the first tongue groove 13j are configured to cooperate for locking of the third and the fourth edge 13, 14 in a vertical V direction. The first mechanical locking system may typically further comprise a first locking strip 13a at the third edge 13, provided with a vertically protruding first locking element 13b, a first locking groove 14g at a fourth edge 14. The first locking element 13b is configured to cooperate with the first locking groove 14g for locking of the third 13 and the fourth edge 14 in a horizontal direction, in particular away from each other and perpendicular said third and fourth edge.

The second mechanical locking system is preferably formed at one of a first 11 or second 12 short edge, such as a first edge, of similar, preferably essentially identical panels 10, 20, 30, 40, 50. The second mechanical locking system may be configured for locking the first edge 11 of the a first panel 10 to the second edge of an adjacent panel 30, in a plane, and in a vertical and/or in horizontal directions perpendicular said first and second edge towards and away from each other. An embodiment of the second mechanical locking system enables assembling of the first and the second panels by a vertical motion of the second edge of the adjacent panel 30 relative the first edge 11 of the first panel 10. Such vertical motion is shown for instance in FIGS 10 and 11. The first and second mechanical locking systems are preferably formed by mechanical cutting, such as milling, drilling and/or sawing, of the edges of the panels and the second mechanical locking system may be provided with a displaceable tongue 11i, preferably of plastic. The displaceable tongue may be bendable and

provided with protruding bendable parts, such as the displaceable tongues disclosed in WO2006/043893 and WO2007/015669. The displaceable tongue may also be configured to be locked by a movement along the first and the second edge, such as the displaceable tongues disclosed in WO2009/116926 and WO200/8004960.

Referring to FIG. 7. Embodiments of a second locking system may comprise a second locking tongue, which may be provided in the shape of a displaceable tongue 11i arranged in a displacement groove 11k for example at the first edge 11 of the first panel 10. The displaceable tongue 11i is configured to cooperate with a first tongue groove 12j formed at the other of the first 11 or second edge 12, for locking of the first and the second edge 11, 12 in a vertical V direction.

A further embodiment of the second locking system in shape of a one-piece solution combinable with the first locking system is shown in FIGS 10 and 11.

As derivable from FIG.6, an upper edge portion of one of a third or fourth edge 13, 14, which may be opposite parallel edges, such as the third edge 13, may comprise a planar surface portion, which may be provided in the shape of a first lower lip portion 139 configured to cooperate, including not limited to, to receive or mate with a complementary planar surface portion, which may be provided in the shape of a first upper lip portion 149, of an upper edge portion of the other of the third or fourth edge of an adjacent panel.

As derivable from FIG.7, an upper edge portion of one of a first or second edge 11, 12, which may be opposite parallel edges, such as the first edge 11, may comprise a planar surface portion, which may be in the shape of a second lower lip portion 119 configured to cooperate, including not limited to, to receive or mate with a complementary planar surface portion, which may be provided in the shape of a second upper lip portion 129, of an upper edge portion of the other of the first or second edge of an adjacent panel.

An outermost portion of first upper lip portion 149 may be disposed inboard of outermost portion of first locking tongue 14h, as shown in FIG.6.

An outermost portion of first lower lip portion 139 may be disposed inboard of outermost portion of first locking strip 13a, as shown in FIG.6.

An outermost portion of first lower lip portion 139 may be disposed outboard of innermost portion of first tongue groove 13j, as shown in FIG.6.

5 An upper edge portion of the fourth edge 14, preferably a long edge, may comprise a vertically extending edge portion extending from the front surface 15 followed by a bend, preferably a right-angle bend, inwards. Said bend followed by a horizontal planar surface, wherein said first upper lip portion 149 may comprise said horizontal planar surface. The vertically extending edge
10 portion and the first upper lip portion may be perpendicular to each other, while the corner connecting the two portions may be rounded or beveled. Optionally, the horizontal planar surface may additionally form a datum surface. A datum surface may be a surface that contacts the adjacent panel, in locked position, and serves as a basis or guide to alignment of the panels to each other.

15 An upper edge portion of the third edge 13, preferably a long edge, may comprise a vertically extending edge portion extending from the front surface followed by a bend, preferably a right-angle bend, outwards. Said bend followed by a horizontal planar surface, wherein said first lower lip portion 139 may
20 comprise said horizontal planar surface. The vertically extending edge portion and the first lower lip portion may be perpendicular to each other, while the corner connecting the two portions may be rounded. Optionally, the horizontal planar surface may additionally form a datum surface.

An upper edge portion of the second edge 12, preferably a short edge, may comprise a vertically extending edge portion extending from the front
25 surface 15 followed by a bend, preferably a right-angle bend, inwards. Said bend followed by a horizontal planar surface, wherein said second upper lip portion 129 may comprise said horizontal planar surface. The vertically extending edge portion and the second upper lip portion may be perpendicular to each other, while the corner connecting the two portions may be rounded or beveled.
30 Optionally, the horizontal planar surface may additionally form a datum surface.

An upper edge portion of the first edge 11, preferably a short edge, may comprise a vertically extending edge portion extending from the front surface 15 followed by a bend, preferably a right-angle bend, outwards. Said bend followed by a horizontal planar surface, wherein said second lower lip portion 119 may
5 comprise said horizontal planar surface. The vertically extending edge portion and the second lower lip portion may be perpendicular to each other, while the corner connecting the two portions may be rounded. Optionally, the horizontal planar surface may additionally form a datum surface.

Outermost portion of second lower lip portion 119 may be disposed
10 inboard of an outermost portion of second locking strip 11a, as shown in FIG.7.

The second lower lip portion 119 may have an extension inboard of an innermost portion of the second tongue groove 11j, as shown in FIG. 11.

The second upper lip portion 129 may have an extension outboard of an outermost portion of the second locking tongue 12h, as shown in FIG. 11.

15 An outermost portion of second lower lip portion 119 may be disposed inboard of outermost portion of second locking tongue 11i, as shown in FIG.7.

An outermost portion of second lower lip portion 119 may be disposed at least partially inboard of an opening of the second displacement groove 11k, as shown in FIG.7.

20 Inboard may be synonymous with inwards of, in a direction towards the centre of the panel. Outboard may be synonymous with outwards of, in a direction away from the centre of the panel.

The upper and lower lips may each comprise a datum surface configured for aligning the front surface 15 of the panel with respective front surfaces 15 of
25 adjacent panels to become flush with each other when assembled in locking position.

The upper and lower lips may be planar, in particular the lip portions may be planar and may extend in parallel. The lip portions may preferably extend in a

plane parallel the front surface 15 of the panel. However, other configurations are perceivable, such as inclined in relation to the front surface 15.

5 The first upper lip portion 149 of the panel may be configured to bear and/or rest on the first lower lip portion 139 when adjacent panels are assembled in locking engagement. Thereby, improved sealing function is facilitated when the panel is assembled in locking position to one or more further panels by means of the first locking system.

10 The second upper lip portion 129 of the panel may be configured to bear and/or rest on the second lower lip portion 119 when adjacent panels are assembled in locking engagement. Thereby, improved sealing function is facilitated when the panel is assembled in locking position to one or more further panels by means of the second locking system.

15 The first and second lower lip portions 119, 139 may form a continuous right-angle with each other. The first and second upper lip portions 129, 149 may form the shape of a continuous right-angle with each other. The continuous right-angles may extend around respective diagonally opposite corners of the panel. The first and second lower and upper lip portions may form the shape of a continuous rectangle. The rectangle may extend along a circumference of the panel as shown in FIG.5A.

20 The first and second lower lip portions 119, 139 may be configured to be underlying when engaging with a respective upper lip portion 129, 149. The first and second upper lip portions 129, 149 may be configured to be overlying when engaging with a respective lower lip portion 119, 139.

25 Accordingly, at least a portion of the lower lip portions 119, 139 may face in a direction upwards and at least a portion of the upper lip portions 129, 149 may face in a direction downwards.

The first edge 11 and the third edge 13 may each comprise a vertically extending surface extending from the front surface 15 of the panel. The lower lip portions 119, 139 may in combination with the respective vertically extending

surface form an inwards recessing shape, such as right-angled surface which recesses inwards.

The second edge 12 and the fourth edge 14 may each comprise a vertically extending surface extending from the front surface 15 of the panel. The upper lip portions 129, 149 may in combination with the respective vertically extending surface form an outwards recessing shape, such as a right-angled surface which complements the respective inwards recessing lower lip portions, as shown in FIGS 6-11.

The respective upper and/or lower lip portions may comprise a material which facilitates sealing, including, but not limited to, a polymer, rubber, silicone, adhesives, wax or like.

In a preferred embodiment, the respective first and second lower lip portions 119 and 139 are provided on the short first edge 11 and the long third edge 13 of the panel 10, and the respective first and second upper lip portions 129, 149 are provided on the short second edge 12 and the long fourth edge 14 respectively, as shown for instance in FIGS 6, 7, 10 and 11.

Accordingly, by courtesy of that the respective first and second upper lip portions 129, 149 may cooperate with, including to bear on, the respective first and second lower lip portions 119, 139, the configuration may bring about the technical advantage that the weight of the panel urges the respective first and second upper lip portions 129, 149 towards the respective first and second lower lip portions 119, 139 thereby the weight of the panel may contribute to the sealing function and thus improved sealing may be facilitated.

This entails that in some embodiments, the first lower edge surface 14f and the first upper surface 13c of two adjacent panel may in some embodiments not abut each other when the two adjacent panels are in assembled in locking position. Thus, a gap may extend between at least part of the first lower edge surface 14f and the first upper surface 13c of two adjacent panels when assembled in locking position.

However, in some embodiments, the first lower edge surface 14f and the first upper surface 13c of two adjacent panel may abut each other when the two adjacent panels are in assembled in locking position by means of the first locking system.

5 Referring to FIG. 6, the first locking tongue 14h, the first tongue groove 13j and the first lip portions 139, 149 may be configured to bias the first upper lip portion 149 towards the first lower lip portion 139 when a respective third edge 13 and fourth edge 14 are assembled in locking position. This configuration may facilitate that the first upper lip portion 149 is always biased towards the first
10 lower lip portion 139 when one or more panels are assembled in locking position.

The first locking system may comprise a first locking tongue 14h and a first tongue groove 13j. The first lower lip portion 139 is preferably disposed between the first tongue groove 13j and the front surface 15 of the panel. The first upper lip portion 149 is preferably disposed between the first locking tongue
15 14h and the front surface 15 of the panel.

Referring to FIG.7, one of the first or second edge 11, 12, for example the first edge 11 may in some embodiments comprise a displaceable, preferably flexible tongue 11i configured to enable assembling of panels by means of vertical folding. The displaceable tongue 11i may be configured to cooperate with
20 the second tongue groove 12j to thereby bias the second upper lip portion 129 against the second lower lip portion 119, thereby facilitating an improved sealing function.

The second locking system may comprise a second locking tongue 11i, 12h and a second tongue groove 12j, 11j. The second lower lip portion 119 is preferably disposed between the second tongue groove 12j, 11j and the front
25 surface 15 of the panel. The second upper lip portion 129 is preferably disposed between the second locking tongue 11i, 12h and the front surface 15 of the panel.

As derivable for instance from FIGS 6-11, the provision of a pair of lip
30 portions, such as the first lower and upper lip portions 139, 149 and/or the second lower and upper lip portions 119, 129, each pair 119, 129; 139, 149 may

respectively form a mechanical labyrinth seal. Thus, this configuration may particularly advantageous for preventing moisture penetration between the edges 11, 12 and/or between edges 13, 14 respectively, such as between the front surface 15 to the locking tongue 11i, 12h or 14h or tongue groove 11j, 12j, 13j or from the front surface 15 to the rear surface 16.

Referring to FIG. 8 and 12 showing an exemplary embodiment where the panels are assembled as a wall, i.e. the panels are utilized as wall panels. The provision of the lip portions 119, 129 139, 149 between the locking tongue 11i, 12h, 14h and/or locking groove 11j, 12j, 13j and the front surface 15 may facilitate that one or more of the pair lip portions i.e. 119, 129; 139, 149, may provide mechanical obstacles e.g. for a fluid such as water. Thereby, a fluid such as water which flow along the front surface 15 in a vertically downwards direction, when acted upon by gravitational force, may be hindered from flowing passed the lip portions, such as the first lower lip portion 139 in a direction from the front surface 15 to the rear surface 16.

In particular the first lower lip portion 139, may provide, e.g. for a fluid such as water, a mechanical obstacle extending in a direction counter the direction of the gravitational force. Thereby, a fluid such as water which flow along the front surface 15 in a vertically downwards direction, when acted upon by gravitational force, will be hindered from flowing upwards and over the first lower lip portion 139.

The first lower lip portion 139 and the first upper lip portion 149 may mutually define a datum plane D_p as illustrated in FIG. 10.

The second lower lip portion 119 and the second upper lip portion 129 may respectively define a datum plane D_p as illustrated in FIG. 7.

The first, second, third and fourth lip portions 119, 129, 139, 149 may be configured to define a datum plane D_p .

The first, second, third and fourth lip portions 119, 129, 139, 149 may essentially extend in a common plane, which may be the datum plane D_p .

The datum plane Dp may facilitate alignment of the respective front surface 15 of adjacent panels when assembled in locking position such that the respective front surfaces 15 of adjacent panels are arranged flush with each other.

5 The first lower lip portion 139 may preferably be disposed between first tongue groove 13j and the front surface 15 of the panel. The first upper lip portion 149 may preferably be disposed between first locking tongue 14h and the front surface 15 of the panel.

10 As explained above and shown in FIG.7, one of the first or second edges may according to embodiments comprise a second locking tongue 11i, such as a displaceable locking tongue configured to linearly translate in a displacement groove 11k, and the other of the first and second edges comprises a second tongue groove 12j for receiving said second locking tongue.

15 The second lower lip portion 119 may preferably be disposed at a vertical V position between second locking tongue 11i and the front surface 15 of the panel. The second upper lip portion 129 may preferably be disposed at a vertical V position between second tongue groove 12j and the front surface 15 of the panel.

20 Alternatively, as shown in FIGS 10 and 11, the second lower lip portion 119 may be disposed at a vertical V position between a second tongue groove 11j of the first edge 11 and the front surface 15 of the panel. The second upper lip portion 129 may be disposed at a vertical V position between a second tongue 12h of the second edge 12 and the front surface 15 of the panel.

25 The first lower lip portion 139 may be contiguous with the second lower lip portion 119.

The first upper lip portion 149 may be contiguous with, preferably continuous with, the second upper lip portion 129.

The lip portions 119, 129, 139, 149 may be contiguous with each other such as to extend continuously along the first, second, third and fourth edges.

Courtesy of the lip portions 119, 129, 139, 149 being overlaying and underlying respectively in a complementary manner, they may continuously define the datum plane Dp along the first, second, third and fourth edges when a panel is assembled with similar panels in locking position along all edges 11, 12, 13, 14. Thereby, improved sealing may be facilitated.

The function of the lip portions may thus be twofold; having the function of aligning the respective front surfaces of the panels and and/or providing the continuous seal along the circumference of the panel together with respective mating lip portions of adjacent panels when assembled in locking position on all four edges of the panel.

The lip portions may be formed contiguous with each other to thereby continuously define the datum plane Dp along the circumference of the panel. It is thereby achieved that when a panel is assembled in locking position with further essentially similar panels along all four edges, there is obtained continuous contact provided by mating or closed lip portions 119, 129; 139, 149 along essentially the entire, or the entire circumference of the panel. A continuous seal along the circumference of the panel may thus be facilitated.

Referring to FIG.7, preferably, the edges of the panel which comprises a locking strip may comprise a respective lower lip portion i.e. the first edge 11 and the third edge 13.

Referring e.g. to FIGS 6-7 and 10-11, preferably, the edges of the panel which comprises a locking strip may comprise a respective lower lip portion i.e. the first edge 11 and the third edge 13.

The panel 10 may comprise a surface layer 15a provided at the front surface 15 and preferably a backing layer 16a provided at the rear surface 16. Typically, the surface layer comprises a decorative layer configured to be visible when the panels are assembled to a flooring. Such decorative layer is well known in the art and may be provided in different forms, including but not limited to printed paper, powder, printed powder or veneer, such as wood veneer. The surface layer, which may also provide a protective layer, typically comprising a binder resin, such as a thermosetting resin, which facilitates bonding, i.e.,

adhesion between, i.a., the decorative layer and the core of the panel. The binder may also facilitate bonding of one or more additives such as surface hardening particles and/or pigments in order to provide the surface layer with various properties. The binder may comprise for example Melamine

5 Formaldehyde. The binder may penetrate into the core of the panel during manufacture of the panel, typically the binder is provided in powder form whereby it becomes liquid in response to exposure to heat. The binder may therefore penetrate into the core of the building panel. The core may for example comprise one of MDF, HDF, wood, stone, ceramics, PVC, plastics, other

10 materials are contemplatable.

The binder may have a depth of penetration into the core of the panel, in the thickness direction Z, from the front surface 15 of the panel and into the core. This feature provides for improved sealing between the respective upper and lower lip portions.

15 The depth of penetration may be at least into the first lower and upper lip portions 139, 149. This provides for a more water-tight first locking system.

The depth of penetration may be at least into the second lower and upper lip portions 119, 129. This provides for a more water-tight second locking system.

20 Consequently, aspects of the present disclosure may be particularly suitable for use in wet spaces, such as bath rooms, kitchens or like.

Consequently, aspects of the present disclosure may be suitable for use as floor panels, as illustrated for instance in FIGS 6-7, 10-11 and 13.

25 Consequently, aspects of the present disclosure may be suitable for use as wall panels, as illustrated for instance in FIGS 8-9 and 12.

It should be appreciated that the provision and configuration of the upper and lower lip portions 119, 129, 139, 149, as described herein, in particular configured to continuously along all the edges of a panel, is not limited to use in combination with a particular locking system, but may rather be implemented in

30 combination with virtually any mechanical locking system and in building panels

of any material. The above described locking system serving merely as exemplary embodiments of possible implementation forms.

Referring to FIGS. 12-13, a panel, such as the first panel 10 may be assembled to an adjacent second panel 20 along its long fourth edge 14 by means of the first locking system, e.g. by an angling motion, thereby creating a long-side to long-side joint. The panel 10 may be further assembled with one of its short edges 11 to an adjacent third panel 30 by means of the second locking system, e.g., by vertical folding, thereby creating a short-side to short-side joint, and further assembled with its long third edge 13 to a further fourth panel 40 by means of the first locking system, e.g. by an angling motion, thereby creating a further long-side to long-side joint. The two further panels 20, 40 being arranged on opposite sides of the short-side joint. The resulting configuration of panels is a typical floor lay when assembling e.g. a floating floor as shown in FIG. 13 or a wall, as shown in FIG. 12. As derivable, the configuration comprises two T-joints. Each T-joint comprising a long-side to long-side joint (between a third edge 13 and a fourth edge 14) and a short-side to short-side joint (between a first edge 11 and a second edge 12). Thus, the set of similar or essentially identical panels can be assembled in locking position to comprise a first T-joint T1 and a second T-joint T2, as shown for instance in FIG. 13.

In order to improve the sealing between assembled lay of panels comprising a panel assembled in locking position on all four sides i.e. all four edges, such as a floor lay (see FIG. 13), it would be desirable to improve the water protection of both T-joints.

Thanks to the building panel having the features set forth herein, and in the appended claims, it may be facilitated that the sealing of both T-joints T1 and T2 is improved.

FIGS 14A-14B, 15A-15B, 16A-16B, 17A-17B, 18A-18B and 19A-19B illustrate different embodiments of pockets which may be combined with any one of the embodiments disclosed herein. The pockets may be configured to receive a sealant, such as a fluid or wax. The provision of one or more pockets may facilitate improved sealing of the joint between adjacent panels when configured in assembled position. The wax pockets may cooperate to control the flow of

sealant through the joint when adjacent panels are assembled, such as from the pocket in a direction through the joint towards the front surface 15 and/or back surface 16.

In FIGS 14A-14B, an upper edge portion of the fourth edge 14, such as a long edge, comprises a vertically extending edge portion 184 extending from the front surface 15 followed by a bend, preferably a right-angle bend, inwards towards the centre of the panel. The bend may be a chamfered, right-angle bend as shown in FIGS 14A-14B. The bend is followed by a horizontal planar surface, wherein the first upper lip portion 149 may comprise said horizontal planar surface.

An upper edge portion of the third edge 13, such a long edge, may comprise a vertically extending edge portion 182 extending from the front surface 15 followed by a bend, preferably a right-angle bend, outwards in a direction from the centre of the panel. The bend is followed by a horizontal planar surface, the first lower lip portion 139 may comprise said horizontal planar surface. A pocket 111 is provided in the third edge 13 between the vertically extending edge portion 182 and the planar surface. The pocket 111 extends downwards in a vertical direction towards the back surface 16. The pocket 111 extends below the horizontal planar surface. The pocket 111 opens upwards in a direction towards the front surface 15.

In FIGS 15A-15B, an upper edge portion of the fourth edge 14, such as a long edge, comprises a vertically extending edge portion 184 extending from the front surface 15 followed by a bend, preferably a right-angle bend, inwards towards the centre of the panel. The bend may be a chamfered, right-angle bend. The bend is followed by a horizontal planar surface, wherein the first upper lip portion 149 may comprise said horizontal planar surface.

An upper edge portion of the third edge 13, such a long edge, may comprise a vertically extending edge portion 182 extending from the front surface 15 followed by a bend, preferably a right-angle bend, outwards in a direction from the centre of the panel. The bend is followed by a horizontal planar surface, the first lower lip portion 139 may comprise said horizontal planar surface. A pocket 112 is provided in the third edge 13 between the vertically extending edge

portion 182 and the horizontal planar surface. The pocket 112 extends sideways in a horizontal direction towards the centre of the panel 20 comprising the third edge 13. The pocket 112 preferably does not extend below the horizontal planar surface. The pocket 112 opens sideways in a direction away from the third edge 13.

In FIGS 16A-16B, an upper edge portion of the fourth edge 14, such as a long edge, comprises a vertically extending edge portion 184 extending from the front surface 15 followed by a bend, preferably a right-angle bend, inwards towards the centre of the panel. The bend may be a chamfered, right angle bend. The bend is followed by a horizontal planar surface, wherein the first upper lip portion 149 may comprise said horizontal planar surface.

An upper edge portion of the third edge 13, such a long edge, may comprise a vertically extending edge portion 182 extending from the front surface 15 followed by a bend, preferably a right-angle bend, outwards in a direction from the centre of the panel. The bend is followed by a horizontal planar surface, the first lower lip portion 139 may comprise said horizontal planar surface. A pocket 113 is provided in the third edge 13 between the vertically extending edge portion 182 and the horizontal planar surface. The pocket 113 extends into the third edge in a direction having an angle relative the vertically extending edge portion 182, such as an angle between 15-75 degrees, such as a 45-degree angle. The pocket 113 may extend below the horizontal planar surface. The pocket 113 opens at least partially sideways in a direction away from the third edge 13. The pocket 113 may have an opening that corresponds to the length (in the side view of FIG 16B) of a chamfer.

In FIGS 17A-17B, an upper edge portion of the fourth edge 14, such as a long edge, comprises a vertically extending edge portion 184 extending from the front surface 15 followed by a bend, preferably a right-angle bend, inwards towards the centre of the panel comprising the fourth edge 14. The bend may be a chamfered, right-angle bend. The bend is followed by a horizontal planar surface, wherein the first upper lip portion 149 may comprise said horizontal planar surface.

An upper edge portion of the third edge 13, such a long edge, may comprise a vertically extending edge portion 182 extending from the front surface 15 followed by a contiguous first bend inwards into the third edge 13, such as a 10-20 degree bend. The first bend is followed by a contiguous second bend, 5 such as an acute bend, outwards in a direction from the centre of the panel. The second bend is followed by a contiguous horizontal planar surface, the first lower lip portion 139 may comprise said horizontal planar surface. A pocket 114 is thereby provided in the third edge 13 between the vertically extending edge portion 182 and the horizontal planar surface. The pocket 114 extends into the 10 third edge. The pocket 114 preferably does not extend below the horizontal planar surface. The pocket 114 opens at least partially sideways in a direction away from the third edge 13. The pocket 114 may have an opening that is larger than the length (in the side view of FIG 17B) of a chamfer.

In FIGS 18A-18B, an upper edge portion of the fourth edge 14, such as a 15 long edge, comprises a vertically extending edge portion 184 extending from the front surface 15 followed by a bend, preferably a right-angle bend, inwards towards the centre of the panel comprising the fourth edge 14. The bend may be a chamfered, right-angle bend. The bend is followed by a horizontal planar surface, wherein the first upper lip portion 149 may comprise said horizontal 20 planar surface.

An upper edge portion of the third edge 13, such a long edge, may comprise a vertically extending edge portion 182 extending from the front surface 15 followed by a contiguous acute bend outwards in a direction from the centre of the panel. The bend is followed by a contiguous planar surface, the first lower 25 lip portion 139 may comprise said horizontal planar surface. The planar surface may form an angle with a horizontal plane H. A pocket 115 is thereby provided in the third edge 13 between the contiguous planar surface and the first upper lip portion 149. The pocket 115 opens at least partially sideways in a direction away from the third edge 13. The pocket 115 may have an opening that is larger than 30 the length (in the side view of FIG 18B) of a chamfer.

In 19A-19B, an upper edge portion of the fourth edge 14, such as a long edge, comprises a vertically extending edge portion 184 extending from the front

surface 15 followed by a bend, preferably a right-angle bend, inwards towards the centre of the panel. The bend is a chamfered edge between the vertically extending edge portion 184 and the first upper lip portion 149. The chamfered edge providing a first pocket 116 between the third edge 13 and the fourth edge 14. The bend is followed by a horizontal planar surface, wherein the first upper lip portion 149 may comprise said horizontal planar surface.

An upper edge portion of the third edge 13, such a long edge, may comprise a vertically extending edge portion 182 extending from the front surface 15 followed by a bend, preferably a right-angle bend, outwards in a direction from the centre of the panel. The bend is followed by a horizontal planar surface, the first lower lip portion 139 may comprise said horizontal planar surface. A second pocket 116' is provided in the vertically extending edge portion 182. Then second pocket 116' extends sideways in a horizontal direction towards the centre of the panel 20 comprising the third edge 13. The second pocket 116' may not extend below the horizontal planar surface. The second pocket 116' opens sideways in a direction away from the third edge 13. The second pocket 116' at least partially opens to the first pocket 116 and is thus at least partially in direct fluid communication with the first pocket 116 when the third edge 13 is configured in assembled position with the fourth edge 14.

Although the pockets 111, 112, 113, 114, 115, 116, 116' have been explained in relation to the third edge 13 and fourth edge 14 of the panel, such as long edges, it should be appreciated that corresponding pockets may be formed between the first edge 11 and second edge of the panel, such as short edges.

FIG. 20A shows an embodiment wherein the first lower lip portion 139 is disposed in a first plane H1 and the second lower lip portion 119 being disposed in a second plane H2 being displaced from the first plane H1. Preferably the first plane H1 is disposed 0.2 to 0.5 mm below the second plane H2, preferably about 0.3 mm, more preferably 0.3 mm. Thereby, the second lower lip portion 119 is disposed above the first lower lip portion 139 and closer to the front surface 15 than the first lower lip portion 139.

By configuring the second lower lip portion 119 in a second plane H2 being disposed above the plane of the first lower lip portion 139, it may be facilitated that a fluid, such as water, may flow from the second lower lip portion 119 to the first lower lip portion 139. The fluid may flow under the action of gravity.

By configuring the second lower lip portion 119 in a second plane H2 being disposed above the plane of the first lower lip portion 139, improved resistance to water penetration may be facilitated in a floor comprising a plurality of panels according the embodiment configured in assembled position.

FIG. 20B shows an embodiment wherein the second upper lip portion 129 and the second lower lip portion 119 are arranged in a second plane H2 when the panels are configured in assembled position, such as when a first edge 11 is configured in assembled position with a second edge 12.

FIG. 20C shows an embodiment wherein the first upper lip portion 149 and the first lower lip portion 139 are arranged in a first plane H1 when the panels are configured in assembled position, such as when a third edge 13 is configured in assembled position with a fourth edge 14.

ITEMS

ITEM 1. A set of similar or essentially identical building panels, such as a floor panels or wall panels, comprising

a first mechanical locking system at respective parallel and opposite third and fourth edges 13, 14, such as long edges, configured to cooperate for locking between two adjacent building panels 10, 20, preferably by means of a folding motion, and

a second locking system at respective parallel and opposite first and second edges 11, 12, such as short edges, configured to cooperate for locking of two adjacent building panels 10, 30,

wherein an upper edge portion of one of the long edges of the panel, such as a third edge or fourth edge 13, 14, preferably the third edge 13,

comprises a first lower lip portion 139 configured to cooperate with a first upper lip portion 149 of an upper edge portion of the other of the third and fourth edge of an adjacent panel 20 when said third and fourth edges are assembled in locking position.

5 ITEM 2. The set according to item 1, wherein the first locking system is configured to cooperate for horizontal and vertical locking between two adjacent building panels 10, 20, preferably by means of a folding motion.

10 ITEM 3. The set according to item 1 or 2, wherein the second locking system is configured to cooperate for horizontal and/or vertical locking of two adjacent building panels 10, 30, preferably by means of a vertical motion, such as vertical folding.

15 ITEM 4. The set according to any one of items 1 to 3, wherein an upper edge portion of one of the short edges of the panel, such as the first or the second edge, comprises a second lower lip portion 119 configured to cooperate with a second upper lip portion 129 of an upper edge portion of the other of the first and second edge of an adjacent panel 30 when said first and second edges are assembled in locking position.

ITEM 5. The set according to the preceding item 4, wherein the lip portions 119, 129, 139, 149 each of comprises a planar horizontal surface.

20 ITEM 6. The set according to any one of the preceding items 4 to 5, wherein the first lower lip portion 139 is continuous with the second lower lip portion 119, preferably the first upper lip portion 149 is continuous with the second upper lip portion 129.

25 ITEM 7. The set according to any one of the preceding items 4 to 6, wherein said lip portions 119, 129, 139, 149 continuously define a datum plane Dp, preferably along the first, second, third and fourth edges when a panel is assembled with similar panels in locking position along all edges 11, 12, 13, 14.

ITEM 8. The set according to any one of the preceding items 4 to 7, wherein said lip portions 119, 129, 139, 149 are contiguous with each other such as to extend continuously along the first, second, third and fourth edges.

5 ITEM 9. The set according to any one of the preceding items 4 to 8, wherein the first upper lip portion 149 is configured to bear on the first lower lip portion 139 when adjacent panels are assembled in locking position by means of the first locking system.

10 ITEM 10. The set according to any one of the preceding items 4 to 9, wherein the second upper lip portion 129 is configured to bear on the second lower lip portion 119 when adjacent panels are assembled in locking position by means of the second locking system.

15 ITEM 11. The set according to any one of the preceding items 4 to 10, wherein the first and locking systems each comprises a locking tongue 11i, 12h, 14h and a tongue groove 11j, 12j, 13j, wherein said lip portions 119, 129, 139, 149 are disposed between a respective of said locking tongue or tongue groove and the front surface 15 of the panel.

20 ITEM 12. The set according to any one of the preceding items 4 to 11, wherein an upper edge portion of the second edge 12 and/or fourth edge 14, comprises a vertically extending edge portion extending from the front surface 15 followed by a contiguous bend inwards towards a centre of the panel, preferably said bend is followed by a horizontal planar surface.

25 ITEM 13. The set according to any one of the preceding items 4 to 12, wherein an upper edge portion of the first edge 11 and/or third edge 13 comprises a vertically extending edge portion extending from the front surface 15 followed by a contiguous bend outwards away from the centre of the panel, preferably said bend is followed by a horizontal planar surface.

ITEM 14. The set according to any one of the preceding items 12 or 13, wherein said bend comprises a right-angle bend.

- ITEM 15. The set according to any one of the preceding items 4 to 14,
wherein the first lower lip portion 139 is continuous with the second lower
lip portion 119.
- 5 ITEM 16. The set according to any one of the preceding items 4 to 15,
wherein the first upper lip portion 149 is continuous with the second upper
lip portion 129.
- ITEM 17. The set according to any one of the preceding items 4 to 16,
wherein the second lower lip portion 119 is contiguous the first upper lip
portion 149.
- 10 ITEM 18. The set according to any one of the preceding items 4 to 17,
wherein the second upper lip portion 129 is contiguous with the first lower
lip portion 139.
- ITEM 19. The set according to any one of the preceding items 4 to 18,
wherein said first and second upper and lower lip portions 119, 129, 139,
15 149 defines a datum plane Dp for aligning the front surface 15 of the
building panel with the front surface (15) of an adjacent building panel.
- ITEM 20. The set according to any one of the preceding items 4 to 19,
wherein one of the first or second edges comprises a second locking
tongue 11i, such as a displaceable locking tongue configured to linearly
20 translate in a displacement groove 11k, and the other of the first and
second edges comprises a second tongue groove 12j for receiving said
second locking tongue, wherein the lip portions (119, 129, 139, 149 are
disposed between first tongue groove the front surface 15 of the panel.
- ITEM 21. The set according to any one of the preceding items 4 to 20,
25 wherein said lip portions 119, 129, 139, 149 are contiguous with each
other, preferably continuously extending along the first, second, third and
fourth edges and/or continuously define the datum plane Dp along the
first, second, third and fourth edges when a panel is assembled with
similar panels in locking position along all edges 11, 12, 13, 14.

- ITEM 22. The set according to any one of the preceding items 4 to 21, wherein the first, second, third and fourth lip portions essentially extend in a common plane.
- 5 ITEM 23. The set according to any one of the preceding items 1 to 22, wherein the panel comprises a surface layer 15a, said surface layer comprising a binder, such as a thermosetting resin.
- ITEM 24. The set according to the preceding item, wherein said binder 18 has a penetration depth into a core 17 of the panel in a direction transverse the front surface 15.
- 10 ITEM 25. The set according to the preceding item, wherein said penetration depth extends to and including at least part of the lip portions.
- ITEM 26. The set according to any one of the preceding claims 23 to 25, wherein the surface layer 15a is a protective surface layer and/or a decorative surface layer.
- 15 ITEM 27. The set according to any one of the preceding items 23 to 26, wherein the surface layer 15a comprises one or more of a veneer, pigments, cellulose fiber.
- ITEM 28. The set according to any one of the preceding items 23 to 27, wherein the binder comprises a thermosetting, such as melamine
20 formaldehyde.
- ITEM 29. The set according to any one of the preceding claims 24 to 28, wherein said core 17 comprises one or more of MDF, HDF, wood, stone, ceramics, PVC, plastics.
- 25 ITEM 30. The set according to any one of the preceding claims 1 to 29, wherein the first lower lip portion 139 is disposed in a first plane H1 and the second lower lip portion 119 is disposed in a second plane H2 being displaced from the first plane H1.

ITEM 31. The set according to any one of the preceding claims 1 to 30, wherein the first plane H1 is disposed 0.2 to 0.5 mm below the second plane H2, preferably about 0.3 mm, more preferably 0.3 mm.

5 ITEM 32. The set according to any one of the preceding claims 1 to 33, wherein an upper edge portion of the second 12 and/or fourth edge 14, such as a long edge, comprises a vertically extending edge portion 184 extending from the front surface 15 followed by a first bend, preferably a right-angle bend, inwards towards the centre of the panel, preferably the bend comprises a chamfered edge between the vertically extending edge
10 portion 184 and the first upper lip portion 149, 139, wherein the bend is followed by a horizontal planar surface, preferably the first upper lip portion 149, 129 comprises said horizontal planar surface, and wherein an upper edge portion of the third edge 13 and/or first edge 11, such a long edge, comprises a vertically extending edge portion 182
15 extending from the front surface 15 followed by a second bend, preferably a right-angle bend, outwards in a direction from the centre of the panel, wherein the second bend is followed by a horizontal planar surface, preferably the first lower lip portion 139, 119 comprises said horizontal planar surface, and wherein a pocket 111, 112, 113 is provided in the third
20 edge 13 and/or first edge 11 between the vertically extending edge portion 182 and the planar surface.

ITEM 33. The set according to ITEM 32, wherein the pocket 111 extends downwards in a vertical direction towards the back surface 16, preferably the pocket 111 extends below the horizontal planar surface; the pocket
25 111 opens upwards in a direction towards the front surface 15.

ITEM 34. The set according to ITEM 32, wherein the pocket 112 is extending sideways in a horizontal direction towards the centre of the panel 20 comprising the third edge 13 and/or first edge 11, preferably the second pocket 112 does not extend below the horizontal planar surface; the
30 pocket 112 opens sideways in a direction away from the third edge 13 and/or first edge 11.

5 ITEM 35. The set according to ITEM 32, wherein the pocket 113 extends into the third edge in a direction having an angle relative the vertically extending edge portion 182, such as angle between 15-75 degrees, such as a 45-degree angle; the pocket 113 extends below the horizontal planar surface; the pocket 113 opens at least partially sideways in a direction away from the third edge 13 and/or first edge 11.

10 ITEM 36. The set according to any one of the preceding items 1 to 31, wherein an upper edge portion of the fourth edge 14 and/or second edge 12, such as a long edge, comprises a vertically extending edge portion 184 extending from the front surface 15 followed by a bend, preferably a right-angle bend, inwards towards the centre of the panel; the bend is preferably a chamfered, right-angle edge between the vertically extending edge portion 184 and the first upper lip portion 149, 129; the chamfered edge forming a first pocket 116 between the third edge 13 and the fourth edge 14 and/or first edge 11 and second edge 12; the first bend is followed by a horizontal planar surface, wherein the first upper lip portion 149, 129 comprise said horizontal planar surface, and

15 wherein an upper edge portion of the third edge 13 and/or first edge 11, such a long edge, comprises a vertically extending edge portion 182 extending from the front surface 15 followed by a second bend, preferably a right-angle bend, outwards in a direction from the centre of the panel; the bend is followed by a horizontal planar surface, the first lower lip portion 139, 119 comprising said horizontal planar surface; a second pocket 116' is provided in the vertically extending edge portion 182; the second pocket 116' extends sideways in a horizontal direction towards the centre of the panel 20 comprising the third edge 13 and/or first edge 11; preferably the second pocket 116' does not extend below the horizontal planar surface, preferably the second pocket 116' opens sideways in a direction away from the third edge 13 and/or first edge 11, preferably the second pocket 116' at least partially opens to the first pocket 116 and is at least partially in direct fluid communication with the first pocket 116' when the third edge 13 is configured in assembled position with the fourth edge

14 and/or the first edge 11 is configured in assembled position with the second edge 12.

5 ITEM 37. The set according to any one of the preceding items 1 to 31, wherein an upper edge portion of the fourth edge 14 and/or second edge 12, such as a long edge, comprises a vertically extending edge portion 184 extending from the front surface 15 followed by a bend, preferably a right-angle bend, inwards towards the centre of the panel comprising the fourth edge 14 and/or second edge 12; preferably the bend is a chamfered, right-angle bend; the first bend is followed by a horizontal planar surface, wherein the first upper lip portion 149, 129 comprises said horizontal planar surface, and

15 wherein an upper edge portion of the third edge 13 and/or first edge 11, such a long edge, comprises a vertically extending edge portion 182 extending from the front surface 15 followed by a contiguous first bend inwards into the third edge 13 and/or first edge 11, such as a 10-20 degree bend; the first bend is followed by a contiguous second bend, such as an acute bend, outwards in a direction from the centre of the panel; the second bend is followed by a contiguous horizontal planar surface, the first lower lip portion 139, 119 comprises said horizontal planar surface, 20 whereby a pocket 114 is thereby provided in the third edge 13 and/or first edge 11 between the vertically extending edge portion 182 and the horizontal planar surface; the pocket 114 extends into the third edge 13 and/or first edge 11; the pocket 114 preferably do not extend below the horizontal planar surface; the pocket 114 opens at least partially sideways 25 in a direction away from the third edge 13 and/or first edge 11.

ITEM 38. The set according to any one of the preceding items 1 to 31, wherein an upper edge portion of the fourth edge 14 and/or second edge 12, such as a long edge, comprises a vertically extending edge portion 184 extending from the front surface 15 followed by a bend, preferably a right-angle bend, inwards towards the centre of the panel comprising the fourth edge 14 and/or second edge 12; preferably the bend is a chamfered, right-angle bend; the bend is followed by a horizontal planar

30

surface, wherein the first upper lip portion 149, 129 comprises said horizontal planar surface, and

5 wherein an upper edge portion of the third edge 13 and/or first edge 11, such a long edge, may comprise a vertically extending edge portion 182 extending from the front surface 15 followed by a contiguous acute bend outwards in a direction from the centre of the panel; the bend is followed by a contiguous planar surface; the first lower lip portion 139, 119
10 comprises said horizontal planar surface, wherein the contiguous planar surface forms an angle with a front surface 15, whereby a pocket 115 is provided in the third edge 13 and/or first edge 11 between the planar surface and the first upper lip portion 149, 129; the pocket 115 opens at least partially sideways in a direction away from the third edge 13 and/or first edge 11.

15

CLAIMS

1. A set of similar or essentially identical building panels, such as a floor panels or wall panels, comprising
5 a first mechanical locking system at respective parallel and opposite third and fourth edges (13, 14) being long edges of the panel, the first mechanical locking system configured to cooperate for horizontal and vertical locking between two adjacent building panels (10, 20), preferably by means of a folding motion, and
a second locking system at respective parallel and opposite first and second edges (11, 12), such as short edges, configured to cooperate for horizontal and
10 vertical locking of two adjacent building panels (10, 30), preferably by means of a vertical motion, such as vertical folding,
wherein an upper edge portion of one of the third edge or fourth edge (13, 14), preferably the third edge (13), comprises a first lower lip portion (139) configured to cooperate with a first upper lip portion (149) of an upper edge portion of the
15 other of the third and fourth edge of an adjacent panel (20) when said third and fourth edges are assembled in locking position.
2. The set according to claim 1, wherein an upper edge portion of one of the first or the second edge comprises a second lower lip portion (119) configured to cooperate which a second upper lip portion (129) of an upper edge portion of the
20 other of the first and second edge of an adjacent panel (30) when said first and second edges are assembled in locking position.
3. The set according to any one of the preceding claims 1 or 2, wherein the lip portions (119, 129, 139, 149) each of comprises a planar horizontal surface.
4. The set according to any one of the preceding claims 1 to 3, wherein the
25 first lower lip portion (139) is continuous with the second lower lip portion (119), preferably the first upper lip portion (149) is continuous with the second upper lip portion (129).
5. The set according to any one of the preceding claims 1 to 4, wherein said lip portions (119, 129, 139, 149) continuously define a datum plane (Dp),

preferably along the first, second, third and fourth edges when a panel is assembled with similar panels in locking position along all edges (11, 12, 13, 14).

6. The set according to any one of the preceding claims 1 to 5, wherein said lip portions (119, 129, 139, 149) are contiguous with each other such as to
5 extend continuously along the first, second, third and fourth edges.

7. The set according to any one of the preceding claims, wherein the first upper lip portion (149) is configured to bear on the first lower lip portion (139) when adjacent panels are assembled in locking position by means of the first locking system.

10 8. The set according to any one of the preceding claims, wherein the second upper lip portion (129) is configured to bear on the second lower lip portion (119) when adjacent panels are assembled in locking position by means of the second locking system.

15 9. The set according to any one of the preceding claims, wherein the first and locking systems each comprises a locking tongue (11i, 12i, 14h) and a tongue groove (11j, 12j, 13j), wherein said lip portions (119, 129, 139, 149) are disposed between a respective of said locking tongue or tongue groove and the front surface (15) of the panel.

20 10. The set according to any one of the preceding claims, wherein said upper edge portion of the second edge (12) and/or fourth edge (14), each comprises a vertically extending edge portion extending from the front surface (15) followed by a contiguous bend inwards towards a centre of the panel, preferably said bend is followed by a horizontal planar surface of the first upper lip portion (149) and/or a planar surface of the second upper lip portion (129).

25 11. The set according to any one of the preceding claims, wherein said upper edge portion of the first edge (11) and/or third edge (13) each comprises a vertically extending edge portion extending from the front surface (15) followed by a contiguous bend outwards away from the centre of the panel, preferably said bend is followed by a horizontal planar surface of the first lower lip portion
30 (139) and/or a planar surface of the second lower lip portion (119).

12. The set according to any one of the preceding claims 10 or 11, wherein said bend comprises a right-angle bend.
13. The set according to any one of the preceding claims, wherein the panel comprises a surface layer (15a), said surface layer comprising a binder, such as
5 a thermosetting resin.
14. The set according to the preceding claim, wherein said binder (18) has a penetration depth into a core (17) of the panel in a direction transverse the front surface (15).
15. The set according to the preceding claims 13 or 14, wherein said
10 penetration depth extends to and including at least part of the lip portions.
16. The set according to any one of the preceding claims 1 to 15, wherein the first lower lip portion (139) is disposed in a first plane (H1) and the second lower lip portion (119) is disposed in a second plane (H2) being displaced from the first plane (H1).
- 15 17. The set according to any one of the preceding claims 1 to 16, wherein the first plane (H1) is disposed 0.2 to 0.5 mm below the second plane (H2), preferably about 0.3 mm, more preferably 0.3 mm.
18. The set according to any one of the preceding claims 1 to 17, wherein at
20 least one pocket (111, 112, 113, 114, 115, 116, 116') is formed adjacent the first and/or second lower lip portion (119, 139) between the third edge (13) of a panel and the fourth edge (14) of adjacent panels or between the first edge (11) of a panel and the second edge (12) of an adjacent panel when the panels are configured in assembled position, said pocket configured to receive a sealant, such as a wax, said pocket preferably configured to distribute said sealant
25 between said third (13) and fourth edge (14) or first edge (11) and second edge (12) in response to said assembling of said panels.




FIG. 1




FIG. 2




FIG. 3




FIG. 4A







FIG. 4B






FIG. 6
A-A




FIG. 7
B-B




FIG. 8
C-C




FIG. 9
D-D




FIG. 10






FIG. 11









FIG. 14A




FIG. 14B





FIG. 15A




FIG. 15B





FIG. 16A




FIG. 16B

16





FIG. 17A




FIG. 17B





FIG. 18A




FIG. 18B





FIG. 19A




FIG. 19B

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2020/050442

A. CLASSIFICATION OF SUBJECT MATTER
INV. E04F15/02 E04F13/08
ADD.
According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED
Minimum documentation searched (classification system followed by classification symbols)
E04F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 20 2015 101572 U1 (SCHULTE GUIDO [DE]) 21 April 2015 (2015-04-21)	1-12, 16-18
Y	figures 1-2 paragraph [0043] - paragraph [0044] paragraph [0047] - paragraph [0049] -----	13-15
Y	US 7 762 293 B2 (VALINGE INNOVATION AB [SE]) 27 July 2010 (2010-07-27) figures 3b,3e column 11, line 29 - line 36 -----	13-15

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

28 May 2020

Date of mailing of the international search report

08/06/2020

Name and mailing address of the ISA/
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Estorgues, Marlène

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2020/050442

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 202015101572 U1	21-04-2015	DE 112016001420 A5	04-01-2018
		DE 202015101572 U1	21-04-2015
		EP 3298212 A1	28-03-2018
		US 2018119429 A1	03-05-2018
		WO 2016155696 A1	06-10-2016

US 7762293 B2	27-07-2010	US 2005166514 A1	04-08-2005
		US 2008005999 A1	10-01-2008
