



US011877761B2

(12) **United States Patent**
Batchelder et al.

(10) **Patent No.:** **US 11,877,761 B2**

(45) **Date of Patent:** **Jan. 23, 2024**

(54) **SYSTEMS, DEVICES AND METHODS FOR MONITORING VOLTAGE AND CURRENT AND CONTROLLING VOLTAGE OF VOLTAGE PULSE GENERATORS**

(58) **Field of Classification Search**
CPC A61B 2017/22098; A61B 2017/22025;
A61B 2017/2202; A61B 2017/00557;
A61B 17/225; A61M 25/104
See application file for complete search history.

(71) Applicant: **Nextern Innovation, LLC**, White Bear Township, MN (US)

(56) **References Cited**

(72) Inventors: **Sam Batchelder**, Somers, NY (US);
John R. Ballard, Waconia, MN (US);
Robert D'Agostino, Minneapolis, MN (US);
Michael P. Brenzel, St. Paul, MN (US);
Jason W. Staab, Apple Valley, MN (US)

U.S. PATENT DOCUMENTS

4,445,509 A 5/1984 Auth
4,990,134 A 2/1991 Auth

(Continued)

FOREIGN PATENT DOCUMENTS

CN 110811761 A 2/2020
DE 3038445 A1 5/1982

(Continued)

OTHER PUBLICATIONS

Touya, G., et al., "Development of subsonic electrical discharges in water and measurements of the associated pressure waves", Journal of Physics D: Applied Physics, 39 (2006), pp. 5236-5244.

(Continued)

Primary Examiner — Anh T Dang

(74) Attorney, Agent, or Firm — BARNES & THORNBURG LLP; Jeffrey R. Stone

(57) **ABSTRACT**

Various embodiments of the systems, methods and devices are provided for breaking up calcified lesions in an anatomical conduit. More specifically, an electrical arc is generated between two spaced-apart electrodes disposed within a fluid-filled balloon, creating a subsonic pressure wave. In some embodiments, the electrodes comprise a plurality of points that allow the electrical arc to form at any one of the plurality of points to, among other things, extend the electrode life.

17 Claims, 7 Drawing Sheets

(21) Appl. No.: **17/454,721**

(22) Filed: **Nov. 12, 2021**

(65) **Prior Publication Data**

US 2023/0041407 A1 Feb. 9, 2023


Related U.S. Application Data

(63) Continuation of application No. 17/449,883, filed on Oct. 4, 2021.

(Continued)

(51) **Int. Cl.**
A61B 17/22 (2006.01)

(52) **U.S. Cl.**
CPC **A61B 17/22022** (2013.01); **A61B 2017/22001** (2013.01); **A61B 2017/22025** (2013.01); **A61B 2017/22062** (2013.01)



Related U.S. Application Data

(60) Provisional application No. 63/229,737, filed on Aug. 5, 2021.

(56) References Cited

U.S. PATENT DOCUMENTS

5,116,227 A 5/1992 Levy
 5,152,768 A 10/1992 Bhatta
 5,454,809 A 10/1995 Janssen
 5,584,843 A 12/1996 Wulfman et al.
 5,891,089 A 4/1999 Katz et al.
 6,132,444 A 10/2000 Shturman et al.
 6,364,894 B1 4/2002 Healy et al.
 6,456,888 B1 9/2002 Skinner et al.
 6,494,890 B1 12/2002 Shturman et al.
 7,309,324 B2 12/2007 Hayes et al.
 7,569,032 B2 8/2009 Naimark et al.
 7,850,685 B2 12/2010 Kunis et al.
 8,177,801 B2 5/2012 Kallok et al.
 8,353,923 B2 1/2013 Shturman
 8,728,091 B2 5/2014 Hakala et al.
 8,956,371 B2 2/2015 Hawkins et al.
 9,642,673 B2 5/2017 Adams et al.
 9,867,629 B2 1/2018 Hawkins
 2002/0082553 A1 6/2002 Duchamp
 2003/0014047 A1 1/2003 Woloszko et al.
 2003/0176873 A1 9/2003 Chernenko et al.
 2005/0194583 A1 9/2005 Taylor et al.
 2005/0251131 A1 11/2005 Lesh
 2006/0190022 A1 8/2006 Beyar et al.
 2006/0221528 A1 10/2006 Li et al.
 2007/0005053 A1 1/2007 Dando
 2007/0239082 A1 10/2007 Schultheiss et al.
 2007/0239182 A1 10/2007 Glines et al.
 2008/0200896 A1 8/2008 Shmulewitz et al.
 2008/0249595 A1 10/2008 McDaniel
 2009/0312768 A1 12/2009 Hawkins et al.
 2010/0036294 A1 2/2010 Mantell et al.
 2010/0114020 A1 5/2010 Hawkins et al.
 2010/0229792 A1 9/2010 Yamasaki et al.
 2011/0196412 A1 8/2011 Levit et al.
 2012/0071889 A1 3/2012 Mantell et al.
 2012/0221013 A1 8/2012 Hawkins
 2013/0041355 A1 2/2013 Heeren et al.
 2014/0005576 A1 1/2014 Adams et al.
 2014/0039513 A1 2/2014 Hakala et al.
 2014/0039514 A1 2/2014 Adams et al.
 2014/0046229 A1 2/2014 Hawkins et al.
 2014/0046353 A1 2/2014 Adams
 2014/0052145 A1 2/2014 Adams et al.
 2014/0052146 A1 2/2014 Curtis et al.
 2014/0052147 A1 2/2014 Hakala et al.
 2014/0074111 A1 3/2014 Hakala et al.
 2014/0074113 A1 3/2014 Hakala et al.
 2014/0163592 A1 6/2014 Hawkins et al.
 2014/0214061 A1 7/2014 Adams et al.
 2014/0243820 A1 8/2014 Adams et al.
 2014/0243847 A1 8/2014 Hakala et al.
 2014/0288570 A1 9/2014 Adams
 2015/0039002 A1 2/2015 Hawkins
 2015/0073430 A1 3/2015 Hakala et al.
 2015/0080995 A1 3/2015 Seeley et al.
 2015/0238208 A1 8/2015 Adams et al.
 2015/0238209 A1 8/2015 Hawkins et al.
 2015/0320432 A1 11/2015 Adams
 2016/0101280 A1 4/2016 Thakkar et al.
 2016/0135828 A1 5/2016 Hawkins et al.
 2016/0151081 A1 6/2016 Adams et al.
 2016/0183957 A1 6/2016 Hakala et al.
 2016/0324534 A1 11/2016 Hawkins et al.
 2016/0331389 A1 11/2016 Hakala et al.
 2016/0354144 A1 12/2016 Caplan et al.
 2017/0056035 A1 3/2017 Adams
 2017/0086867 A1 3/2017 Adams
 2017/0135709 A1 5/2017 Nguyen et al.

2017/0258523 A1 9/2017 Adams et al.
 2017/0303946 A1 10/2017 Ku et al.
 2017/0311965 A1 11/2017 Adams
 2018/0028208 A1 2/2018 Adams et al.
 2018/0098779 A1 4/2018 Betelia et al.
 2018/0153568 A1 6/2018 Kat-Kuoy
 2018/0256250 A1 9/2018 Adams et al.
 2018/0303501 A1 10/2018 Hawkins
 2018/0304053 A1 10/2018 Eggert et al.
 2018/0317946 A1 11/2018 Adams et al.
 2018/0360482 A1 12/2018 Nguyen et al.
 2019/0069916 A1 3/2019 Hawkins et al.
 2019/0150960 A1 5/2019 Nguyen et al.
 2019/0175198 A1 6/2019 Ku et al.
 2019/0254692 A1 8/2019 Hakala et al.
 2019/0269426 A1 9/2019 Hakala et al.
 2019/0365400 A1 12/2019 Adams et al.
 2019/0388110 A1 12/2019 Nguyen et al.
 2020/0000484 A1 1/2020 Hawkins
 2020/0022716 A1 1/2020 Hakala et al.
 2020/0085458 A1 3/2020 Nguyen et al.
 2020/0085459 A1 3/2020 Adams
 2020/0129742 A1 4/2020 Cope et al.
 2020/0246032 A1 8/2020 Betelia et al.
 2020/0297366 A1 9/2020 Nguyen et al.
 2020/0383724 A1 12/2020 Adams et al.
 2021/0038237 A1 2/2021 Adams
 2021/0085347 A1 3/2021 Phan et al.
 2021/0085348 A1 3/2021 Nguyen
 2021/0085383 A1 3/2021 Vo et al.
 2021/0177445 A1 6/2021 Nguyen
 2021/0282792 A1 9/2021 Adams et al.
 2021/0290259 A1 9/2021 Hakala et al.
 2021/0338258 A1 11/2021 Hawkins et al.
 2022/0015785 A1 1/2022 Hakala et al.

FOREIGN PATENT DOCUMENTS

EP 0571306 A1 11/1993
 JP 62-275446 11/1987
 WO 2015/167360 A1 11/2015
 WO 2019/174625 A1 9/2019
 WO 2021/025624 A1 2/2021

OTHER PUBLICATIONS

Extended European Search Report dated Jul. 19, 2022 in European Patent Application No. 22168990.4.

International Search Report and Written Opinion issued in PCT application No. PCT/US2022/71341, dated Aug. 11, 2022.

Petition for Inter Partes Review of U.S. Pat. No. 9,642,673 Under 35 U.S.C. Section 312 and 37 C.F.R. Section 42.104, filed Dec. 7, 2018.

Petition for Inter Partes Review of U.S. Pat. No. 8,728,091, filed Dec. 7, 2018.

Petition for Inter Partes Review of U.S. Pat. No. 8,956,371 Under 35 U.S.C. Section 312 and 37 C.F.R. Section 42.104, filed Dec. 7, 2018.

Judgment, Final Written Decision Determining All Challenged Claims Unpatentable Denying Petitioner's Motion to Exclude Denying Petitioner's Motion to Exclude Denying Patent Owner's Motion to Exclude 35 U.S.C. Section 318(a), 37 C.F.R. Section 42.64, Paper 70, IPR2019-00408, in U.S. Pat. No. 9,642,673 B2, Entered Jul. 20, 2020.

Judgment, Final Written Decision Determining Some Challenged Claims Unpatentable Denying Petitioner's Motion to Exclude 35 U.S.C. Section 318(a), 37 C.F.R. Section 42.64, Paper 75, IPR2019-00405, in U.S. Pat. No. 8,956,371 32, dated Jul. 8, 2020.

Judgment, Final Written Decision Determining All Challenged Claims Unpatentable Denying Petitioner's Motion to Exclude Denying Patent Owner's Motion to Exclude, 35 U.S.C. Section 318(a); 37 C.F.R. Section 42.64, Paper 75, PR2019-00409, in U.S. Pat. No. 8,728,091 B2, dated Jul. 8, 2020.

International Search Report and Written Opinion issued in PCT/US2021/71726, dated Feb. 7, 2022.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13

**SYSTEMS, DEVICES AND METHODS FOR
MONITORING VOLTAGE AND CURRENT
AND CONTROLLING VOLTAGE OF
VOLTAGE PULSE GENERATORS**

**CROSS-REFERENCE TO RELATED
APPLICATIONS**

This application is a continuation of U.S. patent application Ser. No. 17/449,883, filed Oct. 4, 2021 and entitled SYSTEMS, DEVICES AND METHODS FOR GENERATING SUBSONIC PRESSURE WAVES IN INTRAVASCULAR LITHOTRIPSY and further claims the benefit of U.S. Provisional Patent Application Ser. No. 63/229,737, filed Aug. 5, 2021, entitled SYSTEMS, DEVICES AND METHODS FOR GENERATING SUBSONIC PRESSURE WAVES IN INTRAVASCULAR LITHOTRIPSY, the entire contents of which are incorporated herein by reference.

**STATEMENT REGARDING FEDERALLY
SPONSORED RESEARCH OR DEVELOPMENT**

None

BACKGROUND OF THE INVENTION

Field of the Invention

The invention relates to systems, devices and methods for breaking up calcified lesions in an anatomical conduit. More specifically, an electrical arc is generated between two electrodes disposed within a fluid-filled balloon, creating a subsonic pressure wave.

Description of the Related Art

A variety of techniques and instruments have been developed for use in the removal or repair of tissue in arteries and similar body passageways, including removal and/or cracking of calcified lesions within the passageway and/or formed within the wall defining the passageway. A frequent objective of such techniques and instruments is the removal of atherosclerotic plaque in a patient's arteries. Atherosclerosis is characterized by the buildup of fatty deposits (atheromas) in the intimal layer (i.e., under the endothelium) of a patient's blood vessels. Very often over time what initially is deposited as relatively soft, cholesterol-rich atheromatous material hardens into a calcified atherosclerotic plaque, often within the vessel wall. Such atheromas restrict the flow of blood, cause the vessel to be less compliant than normal, and therefore often are referred to as stenotic lesions or stenoses, the blocking material being referred to as stenotic material. If left untreated, such stenoses can cause angina, hypertension, myocardial infarction, strokes and the like.

Angioplasty, or balloon angioplasty, is an endovascular procedure to treat by widening narrowed or obstructed arteries or veins, typically to treat arterial atherosclerosis. A collapsed balloon is typically passed through a pre-positioned catheter and over a guide wire into the narrowed occlusion and then inflated to a fixed size. The balloon forces expansion of the occlusion within the vessel and the surrounding muscular wall until the occlusion yields from the radial force applied by the expanding balloon, opening up the blood vessel with a lumen inner diameter that is similar to the native vessel in the occlusion area and, thereby, improving blood flow.

The angioplasty procedure presents some risks and complications, including but not limited to: arterial rupture or other damage to the vessel wall tissue from over-inflation of the balloon catheter, the use of an inappropriately large or stiff balloon, the presence of a calcified target vessel; and/or hematoma or pseudoaneurysm formation at the access site. Generally, the pressures produced by traditional balloon angioplasty systems is in the range of 10-15 atm, but pressures may at times be higher. As described above, the primary problem with known angioplasty systems and methods is that the occlusion yields over a relatively short time period at high stress and strain rate, often resulting in damage or dissection of the conduit, e.g., blood vessel, wall tissue.

Shockwave Medical, Inc., markets an alternative to traditional relatively high pressure balloon angioplasty. The Shockwave Medical, Inc., intravascular lithotripsy system generates "shock waves" within a fluid-filled balloon. Shockwave Medical claims that generated "shock waves" travel at supersonic speed through the balloon fluid, through the balloon material to interact with the vessel wall tissue, stenosis and/or calcification. The Shockwave Medical, Inc., system requires a relatively close spacing between electrodes in an electrode pair wherein the spark gap is disposed. Shockwave Medical's currently known systems provides relatively small axial coverage of lesions. The structure of Shockwave Medical's electrode pairs thus requires additional electrode pairs spaced apart axially from each other and/or a translatable, slidable electrode pair carrier that may be used to translate the electrode pair(s) to better cover an elongated lesion.

Various embodiments of the present invention address these issues, among others, discussed above.

**BRIEF DESCRIPTION OF THE SEVERAL
VIEWS OF THE DRAWINGS**

These drawings are exemplary illustrations of certain embodiments and, as such, are not intended to limit the disclosure.

FIG. 1 illustrates a perspective and partial cutaway view of a distal region of one embodiment of the present invention.

FIG. 2 illustrates a perspective view of a distal region of one embodiment of the present invention.

FIG. 3 illustrates a perspective view of a distal region of one embodiment of the present invention.

FIG. 4 illustrates a side, cutaway view of a distal region of one embodiment of the present invention.

FIG. 5 illustrates a perspective, cutaway view of a portion of a distal region of one embodiment of the present invention.

FIG. 6 illustrates a side cutaway view of a portion of a distal region of one embodiment of the present invention.

FIG. 7 illustrates a perspective, cutaway view of a portion of a distal region of one embodiment of the present invention.

FIG. 8 illustrates a perspective, cutaway view of a portion of a distal region of one embodiment of the present invention.

FIG. 9 illustrates perspective views of ring electrodes of one embodiment of the present invention.

FIG. 10 illustrates a side cutaway view of two intermediary electrodes with an operative electrical communication therebetween.

FIG. 11 illustrates a side cutaway view of two intermediary electrodes with an operative electrical communication therebetween.

FIG. 12 illustrates a side cutaway view of two intermediary electrodes with an operative electrical communication therebetween.

FIG. 13 illustrates a side view of simultaneous arcs and a side view with one arc delayed relative to the other arc.

DETAILED DESCRIPTION OF THE INVENTION

Generally, embodiments of the present invention comprises methods and devices for generating subsonic waves for disrupting or cracking calcified regions within a blood vessel, though the disruptive effects of the generated subsonic waves may extend to partially or non-calcified occluding material. More specifically, with reference to the Figures, an exemplary embodiment 100 comprises an elongated member or carrier 102 such as a catheter with a known inflatable angioplasty balloon 104 mounted on or near the distal end 103 of the elongated carrier 102 which in certain embodiments may comprise a laser cut polyimide tube. The distal end 105 of the balloon 104 may be sealed against or around the elongated carrier 102 to create a watertight barrier and further comprises a fluid inflating/deflating channel 106 in fluid communication with the interior of the balloon 104 and in fluid communication with a fluid-containing reservoir (not shown) that is located external to the patient, and as is well-known in the art, for inflating the balloon 104 with fluid F and deflating balloon 104. A guide wire lumen (not shown but as is well-known in the art) configured to allow translation of a guide wire extends through the elongated carrier and distally out therefrom, an arrangement also well known to the skilled artisan.

It is to be understood that the various embodiments of the present invention are also effective within a fluid-filled environment, e.g., a bodily cavity and/or a blood vessel, i.e., without requiring a fluid-filled balloon. The various embodiments are described in relation to a fluid-filled balloon, but will also apply to an elongated catheter disposed within a fluid-filled environment wherein the subsonic pressure wave generators described infra may be disposed along the elongated carrier within the fluid-filled environment. All such embodiments are within the scope of the present invention.

Therefore, at least one subsonic pressure wave generator 200 is provided, wherein each subsonic pressure wave generator comprises a proximal ring electrode and a distal ring electrode, with a spark gap defined therebetween. In some embodiments, two subsonic pressure wave generators 200, 200' may be provided. In still other embodiments, more than one subsonic pressure wave generator, i.e., two or more, may be provided.

As referred to herein, subsonic pressure wave generator is defined as a mechanism that, when actuated, generates a wave(s) of energy within a fluid-filled environment such as an angioplasty balloon. The generated wave(s) thus travel through the balloon material at subsonic speed and also interact with tissue and/or calcified material located outside of the balloon at subsonic speed. In other words, the wave(s) generated by the subsonic pressure wave generators do not travel through the balloon material or impact tissue or calcified material outside of the balloon at the speed of sound or greater. Further, the term "wave" is not intended to be limiting to a "wave" per se. Instead, a traveling front of energy is generated and that moves through the fluid within the balloon, generally away from the subsonic pressure

wave generator from which it emanates. This traveling front of energy may comprise a symmetrical expansion shape around the elongated catheter 102, or may expand and travel in an asymmetric shape relative to the elongated catheter 102. In each embodiment, the traveling front of energy, i.e., the "wave" as referred to herein, travels through the balloon material and impacts materials outside of the balloon at subsonic speeds.

Alternatively, the subsonic pressure wave generator may comprise a resistive heater or a pulse heater as is known in the art.

If a single subsonic pressure wave generator 200 is provided, it may be substantially axially centered within the balloon 104. In other embodiments, the single subsonic pressure wave generator 200 may be biased to the proximal or to the distal end of the balloon's interior.

When two or more subsonic pressure wave generators are provided, 200, 200', adjacent subsonic pressure wave generators, e.g., 200, 200', may be spaced axially apart from each other, wherein the resultant spark gaps defined by each subsonic pressure wave generator 200, 200', are axially spaced apart from each other. In cases wherein three or more subsonic pressure wave generators are provided, the resultant spark gap between adjacent subsonic pressure wave generators may be substantially equal, or one or more spark gaps may be longer or shorter than other subsonic pressure wave generators.

As further seen in the Figures, a first, proximal, subsonic pressure wave generator 200 may comprise a proximal ring electrode 201 and an axially spaced apart distal ring electrode 202, defining a spark gap therebetween. Next, a second, more distal, subsonic pressure wave generator 200' may comprise a proximal ring electrode 203 and an axially spaced apart distal ring electrode 204, also defining a spark gap therebetween. As will be discussed further, the distal ring electrode 202 of subsonic pressure wave generator 200 and the proximal ring electrode 203 of subsonic pressure wave generator 200' may be in electrical communication with each other to enable current to flow therebetween.

As will be understood by skilled artisan, the electrical communication may be effectively reversed. First, e.g., with a proximal electrode electrically coupled or in electrical communication with a "high" power side of a circuit and pulse generator connected therein, and a distal electrode electrically coupled or in electrical communication with a "ground" or "return" side of the circuit and pulse generator connected therein. Second, a distal electrode may be electrically coupled or in electrical communication with a "high" power side of a circuit and pulse generator while a proximal electrode may be electrically coupled or in electrical communication with a ground or return side of the circuit and pulse generator. In either case, once the subsonic pressure wave generator(s) is/are actuated, the circuit is completed and current will flow through the circuit.

At least one of the subsonic pressure wave generators, e.g., 200 may be in direct electrical connection and communication with an externally located power source or pulse generator 300, wherein the pulse generator may be configured to provide voltage pulses of a predetermined magnitude and pulse length along an electrical conductor to a proximal ring electrode of a proximal-most subsonic pressure wave generator 200. Alternatively, the voltage pulses may be delivered without a predetermined magnitude or pulse length. In some embodiments, a collapsing field in an inductor, e.g., a well-known car ignition mechanism), or

decaying voltage from a capacitor may be employed, neither of which comprise or require a predetermined voltage or pulse length.

Each subsonic pressure wave generator **200**, **200'**, etc., comprises a pair of axially spaced-apart ring electrodes. Electrode pairs **201**, **202** and **203**, **204** are shown in axially spaced-apart disposition and mounted around the elongated carrier **102**, e.g., by crimping or other attachment means and are immersed within the fluid F in the inflated balloon **104**. Accordingly, spark gaps are defined between electrode pair **201** and **202**, and between electrode pair **203** and **204**, wherein electrodes **202** and **203** are in operative electrical communication or connection. As discussed above, the spark gaps may be of equivalent length or may comprise differing lengths. In some embodiments, a single subsonic pressure wave generator **200** may be provided, while in other embodiments, more than one subsonic pressure wave generator **200**, **200'**, etc., may be provided.

Thus, in some embodiments, first and proximal-most ring electrode **201** may be electrically coupled or in electrical communication or connection, via an electrical conductor, with a power source, e.g., the pulse generator **300**, that is configured for supplying voltage pulses to the electrode pair(s) comprising the subsonic pressure wave generator(s) **200**. The distal-most ring electrode, e.g., **204**, may also be electrically coupled or in electrical communication or connection, via a second electrical conductor, with the power source, e.g., pulse generator **300**.

The fluid F within the inflated balloon **104** is ionically conductive, e.g., saline, to facilitate arcs, or current flow, between the spaced-apart ring electrodes in each electrode pair **201**, **202** and **203**, **204** comprising the subsonic pressure wave generators **200** and **200'**. Thus, upon application of sufficient voltage generated by the pulse generator **300** to the proximal-most electrode, e.g., **201**, via a conductor in electrical connection or communication between pulse generator **300** and electrode **201**, may cause current to flow between electrode **201** and electrode **202** and wherein an arc is generated across the defined spark gap between electrodes **201**, **202**. A return conductor in operative electrical connection or communication with electrode **202** completes the circuit back to the pulse generator **300**. In this manner, the circuit may complete or close during the arcing between ring electrodes **201**, **202** in an embodiment having a single electrode pair comprising a single subsonic pressure wave generator **200**.

It is known that current can flow between the electrodes without an arc. Current generally flows in an electrolyte by ion diffusion. An arc or spark is present when electrons or ions can accelerate past the ionization energies of the local molecule, creating a cascade. Often, this is a plasma and may occur through the bulk fluid, e.g., the conducting fluid F, but is more likely to occur along a fluid-surface interface, e.g., along the outer surface of the catheter **102**. These conditions may also result in generation of subsonic pressure waves as described above.

In an embodiment comprising more than one subsonic pressure wave generator **200**, **200'** such as illustrated, upon application of sufficient voltage by the pulse generator **300**, the current flow (arcing) may proceed from electrode **201** to electrode **202** across the defined spark gap therebetween. Next, electrode **202**, being in operative electrical communication with electrode **203**, enables current to flow from electrode **202** to electrode **203** which, in turn, results in current flow from electrode **203** to electrode **204**, across the spark gap defined therebetween. A return conductor in

operative communication with electrode **204** completes the circuit back to the pulse generator **300**.

The flow discussed above comprises a "current" passing from electrode **201** to **202** is initially ion diffusion as discussed above (before the arc is established), followed by streamers initiating from one or more points **206** of electrode **201**, followed by plasma channels being formed either through the fluid F and/or at, or along, the fluid F surface interface. The fluid F surface interface may comprise the outer surface of catheter **102** and/or the inner surface of angioplasty balloon **104**.

FIG. 1 illustrates the fluid-filled balloon **104** in an inflated state wherein a conductive fluid F such as saline fills the balloon's interior space, with the spaced-apart ring electrodes **201**, **202** and **203**, **204** disposed therein and immersed in fluid F. Electrodes **201**, **202**, **203** and **204** are arranged generally symmetrically around the elongated carrier **102** and generally symmetrically along a center line of the inflated balloon **104**. However, in a preferred embodiment, as shown in at least FIG. 6, a channel **208** may be defined through or along the ring electrodes along a longitudinal plane to allow the insulated conductor(s) to be disposed at least partially therein so as to reduce crossing profile of the system. Thus, the channel **208** may be formed by carving out a portion of ring electrode wherein the ring electrode does extend circumferentially around the elongated carrier **102**. Alternatively, as illustrated in FIG. 6, channel **208** may comprise a void or space between two spaced-apart ends of the ring electrode, wherein the ring electrode extends partially circumferentially around the elongated carrier **102** and wherein the conductor may extend along the outer surface of elongated carrier **102**. With the exception of the interruption of the channel **208** in the ring electrode(s), the preferred structure is symmetrical as discussed above, though asymmetrical electrode(s) may also be employed.

FIGS. 2-12 illustrate possible arrangements and embodiments of the spaced-apart ring electrodes that form each electrode pair as well as the conductive wire connections thereto.

FIG. 2 thus illustrates the elongated carrier **102**, which may comprise a laser cut tube and may comprise polyimide or other material. Two exemplary subsonic pressure wave generators **200**, **200'** are shown in axially spaced-apart relation relative to each other along the elongated carrier **102**. Each subsonic pressure wave generator, e.g., **200**, **200'**, comprise spaced-apart exemplary ring electrodes, respectively **201**, **202** and **203**, **204**, each defining a spark gap between the relevant spaced-apart ring electrodes of a predetermined length, that is the spacing distance between the spaced-apart ring electrodes **201** to **202**, and **203** to **204**. The distal ring electrode, e.g., **202**, of the proximal subsonic pressure wave generator **200** and the proximal ring electrode **203** of the distal subsonic pressure wave generator **200'** are shown in relatively close disposition forming an interface I therebetween, the interface defining and comprising an electrical communication between the two ring electrodes defining the interface I.

The various forms and types of electrical connections between these intermediary ring electrodes **202**, **203** defining an interface I are described further herein, but generally comprise a physical or operative electrical connection between surfaces of the two intermediary ring electrodes that may comprise a touching relationship, a weld bead, or a jumper wire or other conductive interconnection element, or mechanism, between the two intermediary ring electrodes **202**, **203**, or other conducting connection. The skilled artisan will readily recognize alternative mechanisms for creating

the required electrical connection between the intermediary ring electrodes, **202**, **203** i.e., between adjacent subsonic pressure wave generators **200**, **200'**, each of which is within the scope of the present invention. In this arrangement, the two or more subsonic pressure wave generators **200**, **200'**, etc., may be electrically connected in what effectively becomes a series circuit. The number of subsonic pressure wave generators used in certain embodiments may be one, or two, or more than two.

As discussed further herein, the ring electrodes described herein are exemplary, other electrodes shapes and structures are within the scope of the present invention. In certain embodiments, and as discussed further infra, at least one of the electrodes in an electrode pair comprising a subsonic pressure wave generator may comprise a plurality of points or extensions that extend toward the spark gap defined between the electrode pair.

Still further, certain embodiments may comprise a plurality of electrode pairs, at east one electrode pair comprising a proximal-most ring electrode in wired, or other, electrical communication with the pulse generator **300**. In some embodiments, more than one electrode pair in the plurality may comprise a proximal-most ring electrode in wired, or other, electrical communication with the pulse generator **300**, wherein at least one of the electrode pairs in the plurality may be separately and individually energized by the pulse generator **300**. Thus, certain embodiments may comprise a parallel connection arrangement of at least some electrode pairs, or may comprise a combination of series connected sets of electrode pairs with one or more sets of electrode pairs comprising a parallel connection back to pulse generator.

The skilled artisan will recognize that the reference to an operative electrical connection or communication with a proximal-most ring electrode of an electrode pair and the pulse generator **300** is merely illustrative. It is within the scope of the present invention to simply switch the operative electrical connection to be between a distal-most ring electrode of an electrode pair and the pulse generator **300**.

In certain configurations, individual subsonic pressure wave generators, **200**, **200'** may be controlled regarding the magnitude of voltage applied, the magnitude of current flow resulting in an arc between the ring electrodes comprising the subsonic pressure wave generators, the time duration of current flow and arcing between the ring electrodes comprising the subsonic pressure wave generators, the current in the primary of a discharge inductor, the charge in a discharge capacitor and/or the initiation time of the current flow or arcing between the ring electrodes comprising the subsonic pressure wave generators.

For example, and with reference now to FIG. **13** and application of the related detailed description infra, is possible to axially translate or shift a central node between generated pressure waves by slightly delaying generation of one pressure wave by one or more adjacent subsonic pressure wave generators, e.g., **200** or **200'**, relative to the timing of generation of a pressure wave by an adjacent subsonic pressure wave generator, such variable gap spacing may also provide an alternative, or supplemental, mechanism for moving the resulting pressure waves, and nodes disposed therebetween, axially along the catheter **102** within balloon **104**. The delay in pressure wave generation may be used alone, or in combination with the axial spacing differentials between adjacent subsonic pressure wave generators **200**, **200'**.

As shown in FIG. **13**, two (or more) pairs of ring electrodes, **201/202** and **203/204** may be provided within the

fluid-filled balloon. The arcing for each pair **201/202** and **203/204** may be generated substantially simultaneously, resulting in equal-sized bubbles at any given time and subsonic pressure waves P with a central node C generally in the middle of the generated subsonic pressure waves P.

Alternatively, one arc (and resultant subsonic pressure wave P) may be slightly delayed which is used to shift the central node C proximally or distally to enable treating along the axial length of the balloon. FIG. **13** illustrates the axial offset Δ of the central node C vs C' as a result of this delay technique. Such a delay in arcing, and resulting subsonic pressure wave P' which is slightly delayed relative to subsonic pressure wave P, may be timed and used to create a sweeping effect of a axially translating pressure wave through the length of the balloon and along the length of the lesion. A processor may be provided as well-known in the art to execute a pre-programmed set of instructions comprising various timing sequences of the pulses and resulting arcs and pressure waves to optimize focus of the waves including, but not limited to sweeping the lesion in axial directions. As shown, the pairs of interacting ring electrodes **201/202** and **203/204** are adjacent each other along the elongated carrier. In other embodiments, non-adjacent ring electrode pairs may interact as discussed above.

Catheter and Electrodes

As provided above, an exemplary laser-etched polyimide tube **102** may be provided with ring electrodes **201**, **202** and **203**, **204**, wherein the ring electrodes are crimped around the tube, with insulated wires connecting the ring electrodes back to the external pulse generator **300**.

In the two-wire configuration shown, the gap between the electrodes may be decreased by opening the distance between the two adjacent center, intermediary electrodes (**202** and **203**) in the electrode pairs while electrically connecting them with an additional wire.

FIG. **9** provides an exemplary ring electrode E having a body portion B defining a central aperture A configured to securely engage the catheter **102**, channel **208**, a front surface defining a plurality of points **206** and a flat rear surface. Points **206'** illustrate exemplary effects of corrosion on one of the points caused by arcing between adjacent ring electrodes. One or more of the remaining points **206** may engage to generate the arc across the spark gap.

The points **206** may comprise a substantially triangular profile as illustrated. However, other profiles are also contemplated. The underlying functionality of the points **206** is to enable arcs to initiate from different locations on the electrode. Therefore, any shape that extends away from the main body of the electrode generally toward the distal-most electrode in an electrode pair, and generally toward the spark gap defined therebetween, comprising a subsonic pressure wave generator will be sufficient. The tip regions of adjacent ones of the plurality of points are in certain embodiments, spaced apart from each other.

Multiple points **206** on the exemplary ring electrodes facing the spark gap region defined between ring electrodes, e.g., **201**, **202**, allow electrical breakdown streamers to initiate from several different locations or points **206** disposed on and/or around the ring electrode, so viable points **206** remain when some are corroded by the arc. This extends the effectiveness and life of the ring electrode. In addition, the path of the arc may comprise debris, so originating arcs from different locations, i.e., points **206**, on the electrode(s) aids in reducing the debris, making it less likely that a short is formed. In this way, the environment surrounding the

electrodes and within the spark gap therebetween is maintained as uniformly as possible throughout the treatment session comprising a plurality of pulses.

Accordingly, as illustrated in the Figures, and as the skilled artisan will readily understand, the uncorroded point(s) **206** involved in electrical arcs, begin to corrode as electrical arcing proceeds. As shown in FIGS. **5** and **9**, points **206** corrode to shorten to form degraded or corroded points **206'**. In turn, as will be understood and illustrated, the spark gap between corroding, or corroded, points **206'** will lengthen, creating a greater length of fluid and distance, and resistance, therebetween. Thus, the current flow streamers may continually seek out a shorter, less resistant, spark gap formed or defined by, or between one or more uncorroded points **206** that are longer in length that corroded point(s) **206'**. Relatedly, in some embodiments, as best shown in FIG. **5**, one or more of the uncorroded points **206** may have a length that is longer than one or more of the other points **206**, as measured by the point(s) **206** relative length of extension toward the spark gap. The longer point(s) **206** thus comprise a spark gap length that is shorter, and less resistant, than the spark gap length of other point(s) **206** that are shorter, or the spark gap length of points **206'** that are corroded and, therefore, shortened to define a longer spark gap length therebetween. FIG. **5** shows an exemplary set of points **206** wherein one point **206** is "longer" than an adjacent "shorter" point **206** and a still shorter point **206'** that has been shortened by corrosion by electrical arcing. As the skilled artisan will readily understand, current flow streamers may preferably seek out a shorter, less resistant, spark gap, i.e., a spark gap comprising one or more "longer" points **206**.

The electrodes, including exemplary ring electrodes **201**, **202**, **203**, **204**, may be metal or semiconductor, and can be plated with a secondary alloy. The base metal may comprise copper or beryllium copper. The plating may comprise platinum, gold, tungsten, osmium, silver, nickel, or other electrochemically low-activity metal. Carbon surfaces such as graphite, graphene, and diamond may also be used. Still further, stainless steel and steel alloys may be used.

The connection between electrode pairs, e.g., **201**, **202** and **203**, **204**, may be achieved in many embodiments. As discussed above and as shown in FIG. **10**, in one embodiment, the two intermediary ring electrodes, e.g., **202** and **203**, may be placed in a physically touching relationship wherein the electrical connection effectively comprises a short between the touching electrodes **202**, **203**, allowing current to flow therebetween. The electrode rings **201**, **202**, **203**, **204** may comprise a rear surface (shown in FIG. **9**) that may be substantially flattened, wherein the rear surfaces of intermediary ring electrodes **202**, **203** may be in a physically touching engagement. Alternatively, the rear surfaces of exemplary intermediary ring electrodes **202**, **203** may be spaced apart as further discussed here. Still more alternatively, the rear surfaces of the intermediary ring electrodes may comprise complementary shapes, e.g., one convex and the other concave, wherein one rear surface fits within the other rear surface to comprise a fuller physically touching engagement between the intermediary ring electrodes, e.g., **202**, **203**. The rear surface which may be relatively flattened comprises the side opposite the plurality of points **206** which form and define a front surface of each exemplary ring electrode **201**, **202**, **203** and **204**.

As shown in FIG. **12**, rear surfaces of intermediary electrodes **202**, **203** may be configured in an adjacent but spaced, apart and non-touching engagement, wherein a jumper conductive wire is disposed between the intermediary electrodes **202**, **203** across interface I, or, as in FIG. **11**,

a welded bead interconnects the electrodes **202**, **203** at the interface I. Alternative means to achieve the required electrical connection at the interface I between intermediary ring electrodes **202**, **203** may appear to the skilled artisan, each such electrical connection means is within the scope of the present invention.

Alternative electrode embodiments comprise at least some non-ring electrodes attached or mounted or connected with the elongated catheter **102**, wherein pairs of the non-ring electrodes are arranged in spaced-apart configurations to form subsonic pressure wave generators as described above in connection with the ring electrode embodiments. Ring and non-ring electrodes may be combined in a given system.

Still more alternatively, at least some of the electrodes may be disposed along the inner surface of the balloon **104**. In certain embodiments a proximal electrode, e.g., a ring electrode such as **201** may be provided and mounted on or along catheter **102**, and paired with an electrode disposed along the inner surface of balloon **104**. As voltage pulses are applied, an arc may generate between the catheter-mounted electrode and the balloon-mounted electrode, generating in turn subsonic pressure wave(s). Still further, a distal catheter-mounted electrode, e.g., ring electrode **202**, may be spaced away from both the proximal catheter-mounted electrode and from the balloon-mounted electrode. In this embodiment, a first subsonic pressure wave may result from an arc between the proximal catheter-mounted electrode and the balloon-mounted electrode. A second subsonic pressure wave may then result from an arc between the balloon-mounted electrode and the distal catheter-mounted electrode. A heat shield may be disposed along and/or around the region where the balloon-mounted electrode is positioned to aid in heat dissipation and conduction of generated heat away from the balloon material.

Finally, the subsonic pressure wave generators may all be mounted along the inner surface of the balloon, with arcs and resulting subsonic pressure wave generation as described herein.

Electrodes mounted on the inner balloon surface may comprise a carbon filament in operative communication with a pulse generator and which may also affect, e.g., limit, the expansion radius of the balloon.

In all of the cases, a plurality of points **206** may be provided on at least one of the electrodes in an electrode pair comprising a subsonic pressure wave generator.

The plurality of points **206** will also help in cases where the elongated catheter **102** is in a curved disposition due to the tortuosity of the subject vessel. In this situation, the points **206** of the subject electrodes in an electrode pair that are on an inner radius of the curved catheter **102** are in closer proximity to each other than the points **206** on an outer or intermediary radius. Thus, these points **206** that are in closer/closest proximity will be likely to generate the arc and resultant subsonic pressure wave.

Further, it is possible to create a preformed curvature in the catheter **102** in order to effectively select which points **206** are likely to generate the arc and resulting subsonic pressure wave. Such a preformed curvature may be built into the catheter **102** using a mandrel and heat setting or other known techniques and/or shaping metal alloys such as Nitinol. One of more of these preformed curvature region(s) may be located along the section inside the balloon **104**. This deformation or curvature may be straightened by translation over the guide wire, and subsequent withdrawal of the guide wire allows the subject preformed curvature region to successively move from a deformed straightened configuration

to a non-deformed and curved configuration. As will now be apparent, more than one of these preformed curved regions may be provided within the balloon and may be positioned adjacent to electrodes, within or along electrode pairs and/or subsonic pressure wave generators. The preformed curved regions may take curved excursion paths that are in a same direction, or in different directions and may be interposed with straight non-curved sections. In this way, the operator may effectively change the direction of the pressure wave to create more effective disruption of the targeted region.

In certain embodiments, individual points **206** may be specifically energized with individual wired connection(s) and/or individual points **206** may be de-energized in order to ensure they do not participate in current flow, for at least a period of time and/or during treatment of a certain region of the subject vessel.

In other embodiments, the points **206** may be selectively and intentionally degraded (or not degraded) based on material selection and/or relative length of the tip of certain of the points **206** relative to the other points **206**.

Wiring/Cabling

The disposable catheter assembly may comprise two or more insulated conductors connecting the system of electrodes, electrode pair(s) and/or subsonic pressure wave generator(s) to the power supply. A typical excitation pulse is 50 A @ 2 KV for 5 usec, requiring a load impedance of 40 ohms. The round trip cable length in the disposable catheter is approximately 10 feet, so the maximum resistance of the cable is 2 ohms/foot for each trace.

Twisted wire pairs may form transmission lines whose characteristics change with the wire diameter and spacing. If, for example, 40 ga copper wire is spaced 0.25 mm (10 mils) apart (for 5 mil thick insulation), the twisted wire pair may form a 1.1 uH inductor which may, in turn, cause the rise time of an ideal 50 A 2 KV source to be about 25 nsec. Alternatively, larger, more conductive wire may be used and a resistance may be added to the circuit to accommodate the ideal resistance in the system.

The Figures illustrate electrical conductors comprising insulation that are operatively connected with the pulse generator **300** and wherein one of the electrical conductors is in electrical communication with the proximal-most ring electrode **201**, an electrical structure well-known to the artisan. FIG. 4 provides an exemplary connection embodiment wherein a distal end of conductor is stripped of insulation exposing a length of distal conductor portion **212** that is operatively connected with ring electrode **201**. A similar connection mechanism may be employed for the connection between the other electrical conductor and the distal-most ring electrode, e.g., element **204**.

Alternatively, a conductor may comprise a distal conductor portion **214** that is stripped of insulation and that is connected with the relevant ring electrode by a weld bead **216** as shown in FIG. 8. Any of the electrical conductors may be connected to the relevant ring electrode in this manner.

In order to minimize outer diameter and crossing profile of the system, the electrical conductors may be run within a lumen defined in catheter **102**, wherein the distal conductor portion is operatively connected with the relevant ring electrode through an aperture in the catheter **102** and/or via a weld bead as described above.

Alternatively and as shown in the Figures, the ring electrodes **201**, **202**, **203**, **204**, may comprise a channel **208** sized for the electrical conductor(s) to reside within. The

channel **208** may provide the connection point for one or more of the ring electrodes as is shown in, e.g., FIG. 8. Channel **208** may allow the electrical conductor(s) to slide there along to accommodate changes in the attitude of the catheter **102** during advancement of the device **100** through a patient's vasculature.

Still more alternatively, a longitudinal channel or a spiral or other shaped channel may be defined in the wall of elongated catheter **102**. The conductor(s) may be at least partially disposed in the channel to assist in minimizing crossing profile of the system.

Power Supply/Pulse Generator

In some embodiments, a capacitor bank may be provided and may be charged during an exemplary 1-minute off period, followed by a short or connection of the capacitors to the electrodes for the discharge and arc generation. The charging period may be less than 1-minute in preferred embodiments. In other embodiments, a current may be established in a transformer primary, wherein that current is halted to generate a large voltage across the secondary.

As noted, the charging period may be much less than 1 minute as a pulse may be delivered to the electrodes at least once a second. The pulse rate may be limited with sensed temperature of the conductive fluid F and/or balloon material so that the temperature of surrounding tissue is not increased beyond a predetermined threshold, e.g., 1 degree C. of temperature increase for cardiac tissue. The temperature may be monitored using a temperature sensor mounted along the outside surface of the catheter **102** within the conductive fluid F and/or on an inner surface of the balloon, or other location. The temperature sensor may be in operative communication with an externally located processor having operational communication with the predetermined heat threshold(s) and wherein an alert is provided via a display or other mean. In some embodiments, the voltage pulses may be locked out, with no further pulses allowed. In other embodiments, no further voltage pulses are allowed when the predetermined heat threshold is met or exceeded, but the voltage pulses may proceed when the sensed temperature drops below the predetermined heat threshold.

The capacitor bank may be charged from either direction and FETs are controlled to allow the capacitor banks to discharge between the electrodes in an H-bridge configuration. In some embodiments, the current sign may be configured to flip. Phase shaping may be executed to reduce EMI in some embodiments. In some embodiments, both the current and voltage may be monitored to inform what the voltage setting should be for the next pulse delivery. In some embodiments, the voltage may be terminated on a pulse-by-pulse basis and in other embodiments the voltage is not terminated on a pulse-by-pulse basis. Similarly, the electrical arc across a given set of electrodes comprising a subsonic pressure wave generator may be terminated on a pulse-by-pulse basis in some embodiments, while in other embodiments, said electrical arc may not be terminated on a pulse-by-pulse basis.

Because the treatment scales with the cube root of the deposited energy, casual control of voltage and current suffices. The current may flip sign between pulses, droop or exponentially decay during the pulse, and ring or oscillate during the pulse. It is most efficient that the electrical energy be delivered to the electrodes comprising the subsonic pressure wave generator(s) while the balloon fluid F comprises a mass density that is relatively high, roughly in the first 1-20 usec.

The current and voltage output may be monitored for proper operation. Measuring opens or shorts may produce a prompt or alert to change a catheter assembly for a new catheter assembly. Monitoring the DC impedance between the electrodes, e.g., **201** and **202**, and the patient allows catheter insulation leaks to be sensed and corrected. As further described herein, monitoring the DC resistance between the electrodes may provide a temperature monitor. Still further, if the vessel is successfully being opened by treatment, the DC resistance between the electrodes decreases because of the larger cross section of saline conducting between the electrodes. It is further understood that as gas is produced from the arcs, the resistance will change.

Further, sensing and/or monitoring the conductivity of the conducting fluid F within the balloon alone, or comparing same with the conductivity of fluid, e.g., blood, outside of the balloon provides alternative mechanisms for determining whether the balloon has been compromised, e.g., a rupture or tear.

The patient's heart rhythm may be monitored, and that these pulses are synchronized to an inactive phase. That synchronization precludes some standard methods, such as a spark gap that closes when the capacitor bank reaches a target voltage. Relatedly, the balloon **104** will expand and contract with a characteristic time and frequency. Voltage pulses may be timed to take advantage of the natural expansion/contraction cycle and frequency. For example, voltage pulses may be timed to the natural expansion of the balloon and/or to the natural contraction of the balloon. The force of the subsonic pressure waves will impact the target tissue and/or occluding material, e.g., calcification, at slightly different angles depending on the balloon's expansion state, because, *inter alia*, the subsonic pressure wave generators position will change with expansion/contraction of the balloon.

Temperature Sensor

As discussed above, certain embodiments may comprise a small temperature sensor embedded near the electrodes and/or within the conductive fluid F which may increase the treatment pulse rate up to the limit of a safe rise in tissue temperature—generally local tissue temperature should not be increased more than about 1 degree C. Heat diffusion on the order of 5 mm from the electrodes is required for the heat to be convected by blood circulation. The thermal diffusion time for water at in conduits of relevant radius range is $(5 \text{ mm})^2/k=167$ seconds. However, a 0.5 J pulse raises a 5 mm radius sphere of water approximately 0.23 degrees C., so a 1-pulse/spark-per-minute rate may be increased to 2-pulses/sparks-per minute in certain embodiments.

The temperature sensor may be optical fiber based, or a micro-thermocouple. Since saline increases conductivity with temperature, the current produced by a DC bias applied to the electrodes will increase monotonically with temperature, allowing the temperature of the warmest region to be measured directly. As described above, a predetermined heat or temperature increase threshold may be provided with subsequent alerts and/or corrective or remedial actions implemented by programmed instructions implemented by a processor.

Balloon and Inflation Liquid

Angioplasty balloons are developed and nuanced. Embodiments of the present invention comprise standard

angioplasty balloons and related, and known, basic inflation/deflation mechanisms. A typical balloon length may be 12 mm and may be used with 0.14-0.35 in guide wires. The inflated balloon size may comprise about 90% of the nominal vessel size.

Varying the salinity of the water used to inflate the balloon has an impact on the breakdown voltage between the electrodes similar to their spacing. Thus, electrode spacing to form a subsonic pressure wave generator may be selected to be appropriate for standard saline, or when a lower-than-saline salt concentration used to inflate the balloon, the electrode spacing may be increased past that used for standard saline. The current density prior to arc formation may be 50 A through 0.1 cm^2 , or about 500 A/cm^2 at 2,000V, so an initial saline concentration should be at least 2.0 E-4M NaCl. Standard saline is 0.9% NaCl, or 1.5 E-1M, approximately 1000× more concentrated than required to initiate an arc.

The voltage pulse generated by the pulse generator **300** generates streamers in the fluid F interposed between, e.g., the proximal ring electrode **201** and the next more distal ring electrode **202** that comprise a subsonic pressure wave generator **200**. As described above, the distal-most ring electrode is also operatively connected with the pulse generator **300**. Sufficient voltage applied to the proximal ring electrode **201** results in streamers and ultimately current flowing between the two ring electrodes of the electrode pair **201, 202**, generating an arc and a resultant subsonic pressure wave as a bubble forms and expands in the fluid F, and another subsonic pressure wave as the bubble collapses. Generally, the expansion time for the bubble expansion may be measured in terms of microseconds, e.g., approximately 30 microseconds. This expansion time is slow compared to the transit time of sound across the bubble. "Shock waves" require generation of pressure waves that travel at or greater than the speed of sound.

We note here that this relatively slow expansion time, *inter alia*, ensures that the pressure wave generated is subsonic. In contrast, an actual shock wave, i.e., traveling at or greater than the speed of sound, is generated with a much shorter voltage pulse, on the order of tens of nanoseconds.

The distance between ring electrodes of an electrode pair, e.g., **201, 202** may be relatively long, e.g., 5 mm or longer. In this case, the generated bubble and resulting pressure wave may comprise cylindrical shapes, with the end portions of each more spherical in shape.

The description of the invention and its applications as set forth herein is illustrative and is not intended to limit the scope of the invention. Features of various embodiments may be combined with other embodiments within the contemplation of this invention. Variations and modifications of the embodiments disclosed herein are possible, and practical alternatives to and equivalents of the various elements of the embodiments would be understood to those of ordinary skill in the art upon study of this patent document. These and other variations and modifications of the embodiments disclosed herein may be made without departing from the scope and spirit of the invention.

Having described the invention, we claim:

1. A balloon catheter comprising:
 - an elongated carrier;
 - a flexible balloon disposed near a distal end of the elongated catheter, wherein a distal end of the angioplasty balloon is sealed against the elongated catheter, the angioplasty balloon defining an interior region;

15

a fluid channel in fluid communication with the interior region of the angioplasty balloon and a conductive fluid reservoir, configured to inflate the balloon with the conductive fluid;

a proximal electrode disposed along the elongated carrier and a distal electrode disposed along the elongated carrier and spaced an axial distance from the proximal electrode, the axial distance therebetween comprising a spark gap;

a pulse generator in electrical communication with the proximal electrode and the distal electrode; and

a processor operatively connected to the pulse generator and comprising programmed instructions configured to control and operate the pulse generator, the processor in operative communication with a voltage monitor and a current monitor;

wherein application of voltage pulse with an applied voltage magnitude from the pulse generator to one of the proximal electrode and the distal electrode is configured to generate current flow and an electrical arc through the conductive fluid across the spark gap,

wherein the voltage monitor is configured to monitor the voltage applied to one of the proximal electrode and distal electrode,

wherein the current monitor is configured to monitor the current flowing across the spark gap, and

wherein the processor is configured to determine the magnitude of voltage to be applied as the next voltage pulse based on the monitored voltage and the monitored current.

2. The balloon catheter of claim 1, wherein the processor is configured to terminate the voltage applied by the pulse generator.

3. The balloon catheter of claim 2, wherein the processor is configured to terminate the voltage applied by the pulse generator on a pulse-by-pulse basis.

4. The balloon catheter of claim 1, wherein the processor is configured to terminate the generated electrical arc.

5. The balloon catheter of claim 4, wherein the processor is configured to terminate the generated electrical arc on a pulse-by-pulse basis.

6. The balloon catheter of claim 1, wherein the electrical arc generates a pressure wave that travels through the conductive fluid at subsonic speed.

7. The balloon catheter of claim 6, wherein the pressure wave travels through the balloon at subsonic speed.

8. A method for delivering subsonic pressure waves to a calcified lesion comprising: advancing a balloon catheter to a calcified lesion, wherein the balloon catheter comprises: an elongated carrier;

a flexible balloon disposed near a distal end of the elongated catheter, wherein a distal end of the angioplasty balloon is sealed against the elongated catheter,

16

a fluid channel in fluid communication with the interior region of the angioplasty balloon and a conductive fluid reservoir;

a proximal electrode disposed along the elongated carrier and a distal electrode disposed along the elongated carrier and spaced an axial distance from the proximal electrode, the axial distance therebetween comprising a spark gap;

a pulse generator in electrical communication with the proximal electrode and the distal electrode; and

a processor operatively connected to the pulse generator and comprising programmed instructions configured to control and operate the pulse generator, the processor in operative communication with a voltage monitor and a current monitor;

actuating the pulse generator to apply at least one voltage pulse with a voltage magnitude to the proximal electrode or the distal electrode to cause current to flow between the proximal electrode and the distal electrode; generating a pressure wave within the conductive fluid; monitoring the voltage applied by the pulse generator for each of the at least one voltage pulses;

monitoring the current flowing between the proximal electrode and the distal electrode for each of the at least one voltage pulses; and

determining the voltage magnitude to be applied for the next voltage pulse based on the monitored voltage and monitored current.

9. The method of claim 8, further comprising executing the programmed instructions of the processor to determine the voltage magnitude to be applied for the next voltage pulse based on the monitored voltage and monitored current.

10. The balloon catheter of claim 9, further comprising terminating the generated electrical arc on a pulse-by-pulse basis.

11. The method of claim 8, further comprising terminating a generated electrical arc.

12. The method of claim 8, further comprising terminating the voltage applied by the pulse generator.

13. The method of claim 12, further comprising terminating the voltage applied by the pulse generator on a pulse-by-pulse basis.

14. The method of claim 8, further comprising generating a pressure wave that travels through the conductive fluid at subsonic speed.

15. The method of claim 8, further comprising generating a pressure wave that travels through the balloon at subsonic speed.

16. The method of claim 15, further comprising generating a pressure wave that travels toward the calcified lesion at subsonic speed.

17. The method of claim 16, further comprising generating a pressure wave that impacts the calcified lesion at subsonic speed.

* * * * *