

(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. **AU 2012257207 B2**

(54) Title
Parallel bit interleaver

(51) International Patent Classification(s)
H03M 13/27 (2006.01) **H03M 13/19** (2006.01)

(21) Application No: **2012257207** (22) Date of Filing: **2012.05.18**

(87) WIPO No: **WO12/157283**

(30) Priority Data

(31) Number	(32) Date	(33) Country
11004124.1	2011.05.18	EP

(43) Publication Date: **2012.11.22**

(44) Accepted Journal Date: **2017.01.05**

(71) Applicant(s)
Panasonic Corporation

(72) Inventor(s)
Petrov, Mihail

(74) Agent / Attorney
Griffith Hack, GPO Box 1285, Melbourne, VIC, 3001

(56) Related Art
KIENLE, F. et al., "Macro Interleaver Design for Bit Interleaved Coded Modulation with Low-Density Parity-Check Codes", IEEE Vehicular Technology Conference, VTC, Spring 2008, 11-14 May 2008, pages 763 - 766

(12) 特許協力条約に基づいて公開された国際出願

(19) 世界知的所有権機関
国際事務局

(43) 国際公開日
2012年11月22日(22.11.2012)



(10) 国際公開番号
WO 2012/157283 A1

- (51) 国際特許分類:
H03M 13/27 (2006.01) *H03M 13/19* (2006.01)
- (21) 国際出願番号: PCT/JP2012/003263
- (22) 国際出願日: 2012年5月18日(18.05.2012)
- (25) 国際出願の言語: 日本語
- (26) 国際公開の言語: 日本語
- (30) 優先権データ:
11004124.1 2011年5月18日(18.05.2011) EP
- (71) 出願人 (米国を除く全ての指定国について): パナソニック株式会社 (PANASONIC CORPORATION) [JP/JP]; 〒5718501 大阪府門真市大字門真1006番地 Osaka (JP).
- (72) 発明者; および
- (75) 発明者/出願人 (米国についてのみ): ペトロフ ミハイル (PETROV, Mihail).
- (74) 代理人: 中島 司朗, 外 (NAKAJIMA, Shiro et al.); 〒5310072 大阪府大阪市北区豊崎三丁目2番1号淀川5番館6F Osaka (JP).
- (81) 指定国 (表示のない限り、全ての種類の国内保護が可能): AE, AG, AL, AM, AO, AT, AU, AZ, BA,

BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) 指定国 (表示のない限り、全ての種類の広域保護が可能): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), ユーラシア (AM, AZ, BY, KG, KZ, RU, TJ, TM), ユーロッパ (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


添付公開書類:

- 国際調査報告 (条約第21条(3))
- 補正された請求の範囲 (条約第19条(1))

(54) Title: PARALLEL BIT INTERLEAVER

(54) 発明の名称: 並列ビットインターリーバ

【図32】



(57) Abstract: This bit interleave method performs bit permutation on QC LDPC code words consisting of N cyclic blocks of Q bits, and partitions said processed code words into multiple constellation words consisting of M bits. The code words are partitioned into $F \times N/M$ folding sections, and each constellation word is associated with one of the $F \times N/M$ folding sections. The bit permutation processing is performed such that the constellation words consist of F bits from each of M/F different cyclic blocks in the associated folding section.

(57) 要約: ビットインターリーブ方法は、Qビットの巡回ブロックN個で構成されるQC LDPC符号語に対してビットパーミュテーション処理を施し、処理が施された符号語をM個のビットよりなり複数のコンステレーション語に分割する方法であり、符号語は $F \times N/M$ 個のフォルディングセクションに分割され、各コンステレーション語は $F \times N/M$ 個のフォルディングセクションのいずれかと関連付けられており、ビットパーミュテーション処理は、コンステレーション語が、関連付けられているフォルディングセクション中の M/F 個の異なる巡回ブロックそれぞれのFビットからなるように行われる。

[Title of Invention]

PARALLEL BIT INTERLEAVER

[Technical Field]

[0001]

The present disclosure relates to the field of digital communications, and more specifically to a bit interleaver for a bit-interleaved coding and modulation system with quasi-cyclic low-density parity-check codes.

[Background Art]

[0002]

In recent years, bit-interleaved coding and modulation (hereinafter, BICM) systems have been used in the field of digital communications (see, for example, Non-Patent Literature 1).

[0003]

BICM systems generally incorporate the following three steps.

- (1) Encoding data blocks into codewords using, for example, quasi-cyclic low-density parity check (hereinafter, QC LDPC) code or similar.
- (2) Performing bit interleaving on the bits of each codeword.
- (3) Dividing each bit interleaved codeword into constellation words having a number of constellation bits, and mapping the constellation words to constellations.

[Citation List]

[0004]

[Non-Patent Literature 1]

ETSI EN 302 755 V1.2.1 (DVB-T2 standards)

[Summary of the Invention]

[0005]

According to a first broad aspect of the present invention, there is provided a bit interleaving method for interleaving bits of a codeword generated based on a quasi-cyclic low-density parity check coding scheme, including a repeat-accumulate

quasi-cyclic low-density parity check coding scheme, the bit interleaving method comprising:

a cyclic block permutation step of applying a cyclic block permutation process to a codeword made up of N cyclic blocks each consisting of Q bits, to reorder the cyclic blocks in accordance with a cyclic block permutation rule defining a reordering of the cyclic blocks;

a bit permutation step of applying a bit permutation process to the codeword after the cyclic block permutation process, to reorder the bits of the codeword in accordance with a bit permutation rule defining a reordering of the bits; and

a dividing step of dividing the codeword after the bit permutation process into a plurality of constellation words, each of the constellation words being made up of M bits, wherein

N is not a multiple of M ,

the bit permutation rule defines the reordering of the bits of the codeword after the cyclic block permutation process, such that the Q bits in each of $N' = N - X$ cyclic blocks of the N cyclic blocks are each allocated to a bit of an identical bit index in Q constellation words and the Q constellation words are each made up of one bit in each of M cyclic blocks, the M cyclic blocks being common to the Q constellation words, where X is a remainder of N divided by M , and

the bit index of the bit in each of the Q constellation words to which the bits in each of the $N' = N - X$ cyclic blocks are each allocated is determined in accordance with the cyclic block permutation rule.

[0006]

According to a second broad aspect of the present invention, there is provided a bit interleaver for interleaving bits of a codeword generated based on a quasi-cyclic low-density parity check coding scheme, including repeat-accumulate quasi-cyclic low-density parity check coding scheme, the bit interleaver comprising:

a cyclic block permutator applying a cyclic block permutation process to a

codeword made up of N cyclic blocks each consisting of Q bits, to reorder the cyclic blocks in accordance with a cyclic block permutation rule defining a reordering of the cyclic blocks;

a bit permutator applying a bit permutation process to the codeword after the cyclic block permutation process, to reorder the bits of the codeword in accordance with a bit permutation rule defining a reordering of the bits; and

a divider dividing the codeword after the bit permutation process into a plurality of constellation words, each of the constellation words being made up of M bits, wherein

N is not a multiple of M ,

the bit permutation rule defines the reordering of the bits of the codeword after the cyclic block permutation process, such that the Q bits in each of $N' = N - X$ cyclic blocks of the N cyclic blocks are each allocated to a bit of an identical bit index in Q constellation words and the Q constellation words are each made up of one bit in each of M cyclic blocks, the M cyclic blocks being common to the Q constellation words, where X is a remainder of N divided by M , and the bit index of the bit in each of the Q constellation words to which the bits in each of the $N' = N - X$ cyclic blocks are each allocated is determined in accordance with the cyclic block permutation rule.

[0007]

According to a third broad aspect of the present invention, there is provided a signal processing method for processing a signal transmitted by modulating $N \times Q/M$ constellation words, the constellation words being generated by applying a bit reordering process to a codeword generated based on a quasi-cyclic low-density parity check coding scheme, including a repeat-accumulate quasi-cyclic low-density parity check coding scheme, and dividing bits of the codeword for each M bits, the codeword being made up of N cyclic blocks each including Q bits,

the bit reordering process comprising:

a cyclic block permutation process of reordering the cyclic blocks of the codeword in accordance with a cyclic block permutation rule defining a reordering of the cyclic blocks; and

a bit permutation process of reordering the bits of the codeword after the cyclic block permutation process in accordance with a bit permutation rule defining a reordering of the bits, wherein

N is not a multiple of M ,

the bit permutation rule defines the reordering of the bits of the codeword after the cyclic block permutation process, such that the Q bits in each of $N' = N - X$ cyclic blocks of the N cyclic blocks are each allocated to a bit of an identical bit index in Q constellation words and the Q constellation words are each made up of one bit in each of M cyclic blocks, the M cyclic blocks being common to the Q constellation words, where X is a remainder of N divided by M , and

the bit index of the bit in each of the Q constellation words to which the bits in each of the $N' = N - X$ cyclic blocks are each allocated is determined in accordance with the cyclic block permutation rule,

the signal processing method comprising:

a demodulating step of generating a demodulated signal by demodulating the signal, which has been transmitted by modulating the $N \times Q/M$ constellation words;

and

a decoding step of decoding the demodulated signal in accordance with the cyclic block permutation rule and the bit permutation rule to generate data before coding according to the quasi-cyclic low-density parity check coding scheme.

[0008]

According to a fourth broad aspect of the present invention, there is provided a signal processor for processing a signal transmitted by modulating $N \times Q/M$ constellation words, the constellation words being generated by applying a bit reordering process to a codeword generated based on a quasi-cyclic low-density

parity check coding scheme, including a repeat-accumulate quasi-cyclic low-density parity check coding scheme, and dividing bits of the codeword for each M bits, the codeword being made up of N cyclic blocks each including Q bits,

the bit reordering process comprising:

5 a cyclic block permutation process of reordering the cyclic blocks of the codeword in accordance with a cyclic block permutation rule defining a reordering of the cyclic blocks; and

a bit permutation process of reordering the bits of the codeword after the cyclic block permutation process in accordance with a bit permutation rule defining a reordering of the bits, wherein

N is not a multiple of M ,

the bit permutation rule defines the reordering of the bits of the codeword after the cyclic block permutation process, such that the Q bits in each of $N' = N - X$ cyclic blocks of the N cyclic blocks are each allocated to a bit of an identical bit index in Q constellation words and the Q constellation words are each made up of one bit in each of M cyclic blocks, the M cyclic blocks being common to the Q constellation words, where X is a remainder of N divided by M , and

the bit index of the bit in each of the Q constellation words to which the bits in each of the $N' = N - X$ cyclic blocks are each allocated is determined in accordance with the cyclic block permutation rule,

the signal processor comprising:

a demodulator generating a demodulated signal by demodulating the signal, which has been transmitted by modulating the $N \times Q/M$ constellation words; and

a decoder decoding the demodulated signal in accordance with the cyclic block permutation rule and the bit permutation rule to generate data before coding according to the quasi-cyclic low-density parity check coding scheme.

[0009]

According to a fifth broad aspect of the present invention, there is provided a

computer program configured to control a computer to perform a method according to either the first or third aspect. According to this aspect, there is also provided a computer readable medium comprising such a computer program.

[Advantageous Effects of Invention]

5 [0010]

The bit interleaving method of the present invention enables effective interleaving to be applied to the codewords generated based on the quasi-cyclic low-density parity-check coding scheme.

[Brief Description of Drawings]

10 [0011]

In order that the invention may be more clearly ascertained, embodiments will now be described, by way of example, with reference to the accompanying drawing, in which:

[0012]

15 Fig. 1 is a block diagram showing the configuration of a transmitter that includes a typical BICM encoder.

Fig. 2 illustrates an example of a parity-check matrix for quasi-cyclic low-density parity check codes having a coding rate of $1/2$.

20 Fig. 3 illustrates an example of a parity-check matrix for repeat-accumulate quasi-cyclic low-density parity check codes having a coding rate of $2/3$.

Fig. 4 illustrates a parity-check matrix for the repeat-accumulate quasi-cyclic low-density parity check codes of Fig. 3 after a row permutation.

25 Fig. 5 illustrates a parity-check matrix for the repeat-accumulate quasi-cyclic low-density parity check codes of Fig. 3 after a row permutation and a parity permutation.

Fig. 6 describes different robustness levels of the bits encoded in eight PAM symbols.

Fig. 7 is a block diagram showing the configuration of a typical bit interleaver

where the cyclic factor Q is 8, the number of cyclic blocks per low-density parity check codeword N is 12, and the number of bits per constellation M is 4.

Fig. 8A is a block diagram showing the configuration of a DVB-T2 modulator used in the DVB-T2 standard, and Fig. 8B is a block diagram showing the configuration of a BICM encoder for the DVB-T2 modulator of Fig. 8A.

Fig. 9A illustrates a write process for the bits of a 16K codeword (i.e., an LDPC code where the LDPC codeword length is 16200 bits) as performed by a column-row interleaver having twelve columns, and Fig. 9B illustrates a read process for the bits of the codeword written in the manner indicated by Fig. 9A as performed by the column-row interleaver.

Fig. 10A illustrates a write process for the bits of a 16K codeword as performed by a column-row interleaver having eight columns, and Fig. 10B illustrates a read process for the bits of the codeword written in the manner indicated by Fig. 10A as performed by the column-row interleaver.

Fig. 11 is a block diagram showing the configuration of a bit-to-cell demultiplexer used for 16K codes of 16-QAM in the DVB-T2 standard.

Fig. 12 is a block diagram showing the configuration of a bit-to-cell demultiplexer used for 16K codes of 64-QAM in the DVB-T2 standard.

Fig. 13 is a block diagram showing the configuration of a bit-to-cell demultiplexer used for 16K codes of 256-QAM in the DVB-T2 standard.

Fig. 14 illustrates a problem occurring for 16K codes with an eight-column DVB-T2 bit interleaver.

Fig. 15 illustrates a problem occurring for 16K codes with a twelve-column DVB-T2 bit interleaver.

Fig. 16 illustrates a problem occurring for 16K codes with an eight-column DVB-T2 bit interleaver when column twisting is applied.

Fig. 17 illustrates a problem occurring for 16K codes with a twelve-column DVB-T2 bit interleaver when column twisting is applied.

Figs. 18A and 18B respectively illustrate a first and second condition discovered by the inventors enabling an extremely effective interleaver to be provided.

Fig. 19 illustrates a mapping function by an interleaver pertaining to an Embodiment.

5 Fig. 20 is a block diagram showing the configuration of an interleaver pertaining to an Embodiment.

Fig. 21A is a block diagram showing the configuration of a section permutator performing the section permutation illustrated in Fig. 20, and Fig. 21B illustrates a mapping function of the section permutator shown in Fig. 21A.

10 Fig. 22A is a block diagram showing an alternate configuration of a section permutator performing the section permutation illustrated in Fig. 20, and Fig. 22B illustrates a mapping function of the section permutator shown in Fig. 22A.

Fig. 23 is a block diagram showing the configuration of an interleaver pertaining to another Embodiment.

15 Fig. 24 is a block diagram showing the configuration of the bit interleaver shown in Fig. 23.

Fig. 25 is a block diagram showing the configuration of a transmitter pertaining to a further Embodiment.

20 Fig. 26 is a block diagram showing the configuration of a BICM encoder pertaining to a further Embodiment.

Fig. 27 is a block diagram showing the configuration of a receiver including a non-iterative BICM decoder, pertaining to a further Embodiment.

Fig. 28 is a block diagram showing the configuration of a receiver including an iterative BICM decoder, pertaining to a further Embodiment.

25 Fig. 29 is a block diagram showing the configuration of an iterative BICM decoder pertaining to a further Embodiment.

Fig. 30 illustrates an example of cyclic blocks included in and excluded from a parallel interleaver process.

Figs. 31A and 31B respectively illustrate a first and second condition discovered by the inventors enabling an extremely effective interleaver to be provided.

Fig. 32 is a block diagram showing the configuration of an interleaver pertaining to another Embodiment.

5 Fig. 33A illustrates a mapping function for a situation without folding ($F = 1$), and fig. 33B illustrates a mapping function for a situation with folding ($F = 2$).

Fig. 34A is a block diagram showing the configuration of a (folding) section permutator for the situation without folding ($F = 1$), and Fig. 34B is a block diagram showing the configuration of a folding section permutator for the situation with folding
10 ($F = 2$).

Fig. 35 is a block diagram showing the configuration of an interleaver pertaining to another Embodiment.

Fig. 36 is a block diagram showing the configuration of the bit interleaver shown in Fig. 35.

15 Fig. 37 is a block diagram showing the configuration of a transmitter pertaining to a further Embodiment.

Fig. 38 is a block diagram of a receiver including a non-iterative BICM decoder, pertaining to a further Embodiment.

Fig. 39 is a block diagram of a receiver including an iterative BICM decoder,
20 pertaining to a further Embodiment.

Fig. 40 illustrates LLR memory locations for folding with $F = 2$, and bit positions for the first constellation word.

Fig. 41 schematically represents mapping of constellation blocks pertaining to hybrid QPSK+16QAM codes.

25 Fig. 42 is a block diagram showing the configuration of an interleaver pertaining to another Embodiment.

Fig. 43 is a block diagram showing the configuration of an interleaver pertaining to another Embodiment.

[Description of Embodiments]

[0013]

(Background Information)

Fig. 1 is a block diagram showing the configuration of a transmitter 100 that includes a typical bit-interleaved coding and modulation (hereinafter, BICM) encoder. As shown, the transmitter 100 includes an input processor 110, a BICM encoder (in turn including a low-density parity check (hereinafter, LDPC) encoder 120, a bit interleaver 130, and a constellation mapper 140), and a modulator 150.

[0014]

The input processor 110 converts an input bitstream into blocks of a predetermined length. The LDPC encoder 120 encodes the blocks into codewords using LDPC codes, and then transmits the codewords to the bit interleaver 130. The bit interleaver 130 applies an interleaving process to each LDPC codeword, then divides each interleaved codeword into a sequence of cell words (i.e., constellation words). The constellation mapper 140 maps each cell word (i.e., constellation word) to a sequence of constellations (e.g., using QAM). The generic modulator 150 at the output includes all processing blocks from the output of the BICM encoder to a radio frequency (hereinafter, RF) power amplifier.

[0015]

An LDPC code is a linear error correcting code that is fully defined by a parity-check matrix (hereinafter, PCM). A PCM is a binary sparse matrix that represents the connection of codeword bits (hereinafter also termed variable nodes) to the parity checks (hereinafter also termed check nodes). The columns and the rows of the PCM respectively correspond to the variable nodes and the check nodes. In the PCM, a connection between a variable node and a check node is represented by a one-element.

[0016]

Quasi-cyclic low-density parity check (hereinafter, QC LDPC) codes are one

variety of LDPC codes. QC LDPC codes have a structure that is particularly suited to hardware implementation. In fact, most standards in use today employ QC LDPC codes. The PCM of a QC LDPC code has a special configuration made up of a plurality of circulant matrices. A circulant matrix is a square matrix in which each row is a cyclic shift of the elements in the previous row, and has one, two, or more folded diagonals. Each circulant matrix has a size of $Q \times Q$. Here, Q represents the cyclic factor of the QC LDPC. The above-described quasi-cyclic configuration allows Q check nodes to be processed in parallel, which is clearly beneficial for efficient hardware implementation.

[0017]

Fig. 2 shows the PCM of a QC LDPC code having a cyclic factor Q of eight, as an example. In Fig.2, as well as in later-described Figs. 3 and 5, the smallest squares each represent one element of the PCM, where the black squares are one-elements and all other squares are zero-elements. The PCM shown has circulant matrices with one or two folded diagonals apiece. This QC LDPC code encodes a block of $8 \times 6 = 48$ bits into a codeword of $8 \times 12 = 96$ bits. Accordingly, the coding rate of the QC LDPC is $48/96 = 1/2$. The codeword bits are divided into a plurality of blocks of Q bits each. The Q bit blocks are hereinafter termed cyclic blocks (or cyclic groups) for this relation to the cyclic factor of Q .

[0018]

A special variety of QC LDPC codes are repeat-accumulate quasi-cyclic low-density parity check (hereinafter, RA QC LDPC) codes. RA QC LDPC codes are well known as being easy to encode, and are therefore used in a wide variety of standards (e.g., in second-generation DVB standards, including DVB-S2, DVB-T2, and DVB-C2). The right-hand side of the PCM corresponds to the parity bits. The one-elements therein are arranged in a staircase structure. Fig. 3 shows an example of a PCM for a RA QC LDPC having a coding rate of $2/3$.

[0019]

Above, and throughout, DVB-T is an abbreviation of Digital Video Broadcasting - Terrestrial, DVB-S2 is an abbreviation of Digital Video Broadcasting - Second Generation Satellite, DVB-T2 is an abbreviation of Digital Video Broadcasting - Second Generation Terrestrial, and DVB-C2 is an abbreviation of Digital Video Broadcasting - Second Generation Cable.

[0020]

By applying a simple row permutation to the PCM shown in Fig. 3, the quasi-cyclic structure of the RA QC LDPC codes is revealed, with the exception of the parity portion, shown in Fig. 4. The row permutation is a simple change of the graphical representation having no influence on the code definition.

[0021]

The quasi-cyclic structure of the PCM parity portion is imparted by applying a suitable row permutation to only the parity bits of the PCM shown in Fig. 4. This technique is widely known in the field and is used in standards such as DVB-T2, under the name of parity interleaving or of parity permutation. Fig. 5 shows the PCM obtained as a result of applying such parity permutation to the PCM shown in Fig. 4.

[0022]

Typically, the bits of an LDPC codeword vary in importance, and the bits of a constellation vary in robustness level. Mapping the bits of an LDPC codeword to a constellation directly, i.e., without interleaving, leads to suboptimal performance. Thus, the bits of the LDPC codeword require interleaving prior to mapping onto constellations.

[0023]

For this purpose, the bit interleaver 130 is provided between the LDPC encoder 120 and the constellation mapper 140, as shown in Fig. 1. By carefully designing the bit interleaver 130, the association between the bits of the LDPC codeword and the bits encoded by the constellation is improved, leading to improved receiver performance. Performance is typically measured using the bit-error rate

(hereinafter, BER) as a function of the signal-to-noise ratio (hereinafter, SNR).

[0024]

The bits of the LDPC codeword differ in importance primarily because not all bits are necessarily involved in the same number of parity checks. The more parity checks (check nodes) a given codeword bit (variable node) is involved in, the more important the given codeword bit is in an iterative LDPC decoding process. A further reason is that the variable nodes each have different connectivity to the cycles of a Tanner graph representing the LDPC codes. Therefore, the codeword bits are likely to differ in importance despite being involved in the same number of parity checks.

These ideas are well understood in the field. As a rule, the importance of the variable nodes increases as the number of check nodes connected therewith increases.

[0025]

In the particular case of QC LDPC codes, all bits included in a cyclic block of Q bits have the same number of parity checks applied thereto, and have the same connectivity to the cycles of the Tanner graph. Thus, all bits have the same importance.

[0026]

Similarly, the encoded bits of a constellation are widely known to have different levels of robustness. For example, a quadrature amplitude modulation (hereinafter, QAM) constellation is made up of two independent pulse amplitude modulation (hereinafter, PAM) symbols, one symbol corresponding to the real part and the other symbol corresponding to the imaginary part. The two PAM symbols each encode M bits. Fig. 6 shows 8-PAM symbols using Gray encoding. As shown, the bits encoded by in each PAM symbol vary in terms of level of robustness. The difference in robustness is a result of the distance between two subsets defined by each bit (e.g., 0 or 1) being different for each of the bits. The greater the distance, the more robust and reliable the bit. Fig. 6 indicates that bit b3 has the highest robustness level, while bit b1 has the lowest robustness level.

[0027]

Thus, a 16-QAM constellation encodes four bits and has two robustness levels. Also, a 64-QAM constellation encodes six bits and has three robustness levels. Likewise, a 256-QAM constellation encodes eight bits and has four robustness levels.

5 [0028]

The following parameters are hereinafter used throughout the present description.

[0029]

Cyclic factor: $Q = 8$

10 Number of cyclic blocks per LDPC codeword: $N = 12$

Number of bits per constellation: $M = 4$ (i.e., 16-QAM)

Given the above parameters, the number of constellations to which each LDPC codeword is mapped is equal to $Q \times N / M = 24$. Typically, the parameters Q and N are selected such that $Q \times N$ is equal to a multiple of M for all constellations supported by
15 the system.

[0030]

Fig. 7 is a block diagram showing the configuration of a typical interleaver when the above parameters are applied. In Fig. 7, the 12 cyclic blocks are labeled QB1, ..., QB 12, and the 24 constellations are labeled C1, ..., C24. A bit interleaver
20 interleaves the 96 bits of the LDPC codeword.

[0031]

A conventional bit interleaver is known from the DVB-T2 standard (see ETSI EN 302 755). The DVB-T2 standard is a television standard presenting improvements over the DVB-T standard, and describes a second-generation baseline
25 transmission system for digital television broadcasting. The DVB-T2 standard gives the details of a channel coding and modulation system for broadcast television services and generic data.

[0032]

Fig. 8A is a block diagram showing the structure of a modulator used in the DVB-T2 standard (i.e., a DVB-T2 modulator). The DVB-T2 modulator 800 includes an input processor 810, a BICM encoder 820, a frame builder 830, and an OFDM generator 840.

5 [0033]

The input processor 810 converts an input bitstream into blocks of a predetermined length. The BICM encoder 820 applies BICM processing to the input. The frame builder 830 uses input from the BICM encoder 820 and the like to generate a distribution frame structure in the DVB-T2 format. The OFDM generator 840 performs pilot addition, fast Fourier transform application, guard interval insertion, and the like on the distribution frame structure, then outputs a transmission signal in the DVB-T2 format.

[0034]

The BICM used in the DVB-T2 standard is described in chapter 6 of the ETSI EN 302 755 standard. The aforementioned standard is incorporated herein by reference and explained below.

[0035]

Fig. 8B is a block diagram showing the structure of the BICM encoder 820 in the DVB-T2 modulator 800 illustrated in Fig. 8A. Fig. 8B omits outer BCH encoding, constellation rotation, the cell interleaver, the time interleaver, and the like.

[0036]

The BICM encoder 820 includes an LDPC encoder 821, a bit interleaver (in turn including a parity interleaver 822 and a column-row interleaver 823), a bit-to-cell demultiplexer 824, and a QAM mapper 825.

25 [0037]

The LDPC encoder 821 encodes the blocks into codewords using LDPC codes. The bit interleaver (which includes the parity interleaver 822 and the column-row interleaver 823) performs interleaving on the bits of the codewords. The bit-to-cell

demultiplexer 824 demultiplexes the interleaved bits of the codewords into cell words (constellation words). The QAM mapper 825 maps the cell words (constellation words) to complex QAM symbols. The complex QAM symbols are also termed cells. In fact, the bit-to-cell demultiplexer 824 may also be considered a part of the bit interleaver. In such situations, the BICM encoder conforming to the DVB-T2 standard may be considered to have the basic structure shown in Fig. 1.

[0038]

The LDPC codes used in the DVB-T2 standard are RA QC LDPC codes having a cyclic factor of $Q = 360$. Two codeword lengths are defined for the DVB-T2 standard, one being 16200 bits and the other being 64800 bits. In the present document, LDPC codes using a codeword length of 16200 bits are referred to as 16K codes (or as 16K LDPC codes), and LDPC codes having a codeword length of 64800 bits are referred to as 64K codes (or as 64K LDPC codes). The number of cyclic blocks per codeword is 45 for the 16K codes and 180 for the 64K codes. The available codes corresponding to each block length (codeword length) are given in Tables A1 through A6 of ETSI EN 302 755 for the DVB-T2 standard.

[0039]

The bit interleaver is used only for constellations larger than quadrature phase-shift keying constellations (hereinafter, QPSK), and includes the parity interleaver 822, the column-row interleaver 823, and the bit-to-cell demultiplexer 824. According to the DVB-T2 standard, the bit interleaver does not include the bit-to-cell demultiplexer 824. However, the present document pertains to interleaving as applied to LDPC codes prior to constellation mapping. As such, the bit-to-cell demultiplexer 824 is treated as a part of the bit interleaver.

[0040]

The parity interleaver 822 performs parity permutation on the parity bits of each codeword so as to clarify the quasi-cyclic structure thereof, as described above (see Figs. 4 and 5).

[0041]

Conceptually, the column-row interleaver 823 operates by writing the bits of each LDPC codeword column-wise in an interleaver matrix, then reading the bits row-wise. The first bit of the LDPC codeword is written first, and is read first.

After writing and before reading the LDPC codeword bits, the column-row interleaver 823 cyclically shifts the columns of bits by a predetermined number of positions. This is termed column twisting in the DVB-T2 standard. The number of columns N_c and the number of rows N_r in the interleaver matrix are given in Table 1 for several constellation sizes, according to the two aforementioned LDPC codeword lengths.

[0042]

[Table 1]

LDPC codeword length	Constellation size	No. of columns: N_c	No. of rows: N_r
16200	16-QAM	8	2025
	64-QAM	12	1350
	256-QAM	8	2025
64800	16-QAM	8	8100
	64-QAM	12	5400
	256-QAM	16	4050

The number of columns N_c is twice the number of bits per constellation, with the exception of 16K codes with a 256-QAM constellation. This exception occurs because the LDPC codeword length of 16200 is not a multiple of 16, i.e., is not twice the number of bits per 256-QAM constellation.

[0043]

The codeword bit writing process and bit reading process for 16K codes performed by the column-row interleaver 823 is illustrated in Figs. 9A and 9B for twelve columns, and in Figs. 10A and 10B for eight columns. Each of the small squares corresponds to one bit of the LDPC codeword. The blackened square represents the first bit of the LDPC codeword. The arrows indicate the order in which the bits are written to and read from the interleaver matrix. For example, when the interleaver matrix has twelve columns, the codeword bits of the 16K code are written in

the order given in Fig. 9A, namely (Row 1, Column 1), (Row 2, Column 1), ..., (Row 1350, Column 1), (Row 1, Column 2), ..., (Row 1350, Column 12), then read in the order given in Fig. 9B, namely (Row 1, Column 1), (Row 1, Column 2), ..., (Row 1, Column 12), (Row 2, Column 1), ..., (Row 1350, Column 12). Figs. 9A, 9B, 10A, and 10B do not illustrate the column twisting process.

[0044]

Prior to QAM mapping, the bit-to-cell demultiplexer 824 demultiplexes the LDPC codewords to obtain a plurality of parallel bit streams. The number of streams is twice the number of encoded bits M per QAM constellation, i.e., $2 \times M$, with the exception of 16K LDPC codes with a 256-QAM constellation. For 16K LDPC codes with a 256-QAM constellation, the number of streams equal to the number of encoded bits M per QAM constellation. The M encoded bits per constellation are referred to as one cell word (constellation word). For the 16K LDPC codes, the number of cell words per codeword is $16200/M$, as given below.

[0045]

8100 cells for QPSK,
4050 cells for 16-QAM,
2700 cells for 64-QAM, and
2025 cells for 256-QAM.

According to Table 1, given above, the number of parallel streams is equal to the number of columns in the column-row interleaver for constellations larger than QPSK. The bit-to-cell demultiplexers corresponding to 16-QAM constellations, 64-QAM constellations, and 256-QAM constellations for 16K LDPC codes are respectively shown in Figs. 11, 12, and 13. The bit notation used is that of the DVB-T2 standard.

[0046]

As shown in Fig. 11 (and Figs. 12 and 13), the bit-to-cell demultiplexer 824 includes a simple demultiplexer 1110 (also 1210, 1310) and a demux permutator 1120

(also 1220, 1320).

[0047]

In addition to having the simple demultiplexer 1110 (1210, 1310) simply demultiplex the LDPC codewords, to which interleaving has been applied, the bit-to-cell demultiplexer 824 also has the demux permutator 1120 (1220, 1320) perform a permutation on the demultiplexed parallel bit streams.

[0048]

However, when the column-row interleaver is used (i.e., for 16-QAM constellations or larger), the permutation applied to the bit streams is identical to a permutation applied to the columns of the column-row interleaver due to the number of parallel bit streams being equal to the number of columns. Therefore, the permutation performed by the bit-to-cell demultiplexer 824 is regarded as a part of the bit interleaver.

[0049]

The bit interleaver used in the DVB-T2 standard essentially has two problems.

[0050]

The first problem is that parallelism is impaired when the number of cyclic blocks in the LDPC codeword is not a multiple of the number of columns in the bit interleaver matrix. Reduced parallelism leads to increased latency. This is especially problematic when iterative BICM decoding is used by the receiver. This situation occurs for several combinations of LDPC codeword length and constellation size in the DVB-T2 standard.

[0051]

Figs. 14 and 15 illustrate the aforementioned situation for 16K LDPC code cases where the interleaver matrix has eight and twelve columns, respectively. Eight columns are used in the interleaver matrix for 16-QAM constellations and 256-QAM constellations. Twelve columns are used in the interleaver matrix for 64-QAM constellations. In Figs. 14 and 15, the grid represents an LDPC codeword, the small

squares each represent one bit of the LDPC codeword, the rows correspond to the cyclic blocks, and the columns correspond to bits of the same bit index within a cyclic block. The blackened squares represent eighth and twelfth bits of the first row in the interleaver matrix. For ease of comprehension, the number of bits per cyclic block

has been reduced from 360 to 72. However, this does not affect the understanding.

[0052]

The second problem is that, in the DVB-T2 standard, the number of possible bit interleaver configurations is limited by the number of columns in the bit interleaver matrix.

[0053]

A further problem of the DVB-T2 bit interleaver is that the regularity and parallelism of the permutation is impaired by the column twisting process. Figs. 16 and 17 respectively illustrate the same situations as Figs. 14 and 15, with the addition of the column twisting process. When the interleaver matrix has eight columns for the 16K LDPC codes, the column twisting values for the columns of the DVB-T2 bit interleaver are (0, 0, 0, 1, 7, 20, 20, 21). Similarly, when the interleaver matrix has twelve columns for the 16K LDPC codes, the column twisting values for the columns of the DVB-T2 bit interleaver are (0, 0, 0, 2, 2, 2, 3, 3, 3, 6, 7, 7).

[0054]

Accordingly, a bit interleaver that reduces latency while improving parallelism is desired. These properties are particularly important in iterative BICM decoding.

[0055]

(Experimenter Discoveries)

The inventor has discovered, as the fruit of prolonged experimentation, that an interleaver satisfying the following two conditions is extremely efficient.

[0056]

(Condition 1)

The M bits of each constellation are each mapped to one of M different cyclic

blocks of the LDPC codeword. This is equivalent to mapping one bit from M different cyclic blocks of the LDPC codeword to a constellation word. This is schematically illustrated in Fig. 18A.

[0057]

5 (Condition 2)

All constellation words mapped to the M cyclic blocks are mapped only to that particular cyclic block. This is equivalent to mapping all $M \times Q$ bits of the M different cyclic blocks each made up of Q bits to exactly Q constellations. This is schematically illustrated in Fig. 18B.

10 [0058]

The above conditions imply that exactly Q constellations are mapped to each set of M cyclic blocks.

[0059]

(Embodiment 1)

15 The following describes the details of a bit interleaver (i.e., a parallel bit interleaver) that satisfies conditions 1 and 2 given above. In the following description, processing and the units performing such processing are labeled with the same reference numbers wherever applicable.

[0060]

20 In the present document, each group of M cyclic blocks and each group of Q constellation words is referred to as a section (or as an interleaver section).

[0061]

25 Figs. 19 and 20 are block diagrams respectively illustrating the mapping function of a bit interleaver satisfying Conditions 1 and 2 and corresponding to the aforementioned parameters (i.e., $Q = 8$, $M = 4$, $N = 12$), and a sample configuration for such a bit interleaver.

[0062]

In Figs. 19 and 20, the QC-LDPC codewords are made up of $N = 12$ cyclic

block, each in turn made up of $Q = 8$ bits. Each of the 24 constellation words is made up of $M = 4$ bits. Each constellation word indicates one of $2^M = 16$ constellation points. The bit interleaver is divided into $N/M = 3$ sections. The 24 constellation words are each associated one of the three sections.

5 [0063]

A bit interleaver 2000 includes a bit permutator 2010, which in turn includes $N/M (= 3)$ section permutators 2021, 2022, and 2023, each operating independently. However, rather than providing three section permutators, a single section permutator may, for example, be provided so as to perform the three section permutation processes described below, switching therebetween over time.

10

[0064]

The section permutators (2021, 2022, and 2023) each independently perform a section permutation on the 32 bits making up each of 4 cyclic blocks, such that one bit from every four cyclic blocks (i.e., QB1 through QB4, QB5 through QB8, and QB9 through QB12) is mapped to each group of eight constellation words (i.e., C1 through C8, C9 through C16, and C17 through C24).

15

[0065]

Conditions 1 and 2, described above, ensure that the bit interleaver is divisible into N/M parallel sections. The section permutations applied to the parallel sections may all apply the same permutation rules, may each apply different permutation rules, or may involve a subset of the sections applying identical permutation rules while other differ.

20

[0066]

For example, the section permutators may map the Q bits of a cyclic block (which each have the same importance in LDPC decoding) to bits having the same bit index (i.e., having the same robustness level) in the Q constellation words. For each cyclic block, the Q bits may be in sequential or in permuted order. The latter case is described with reference to Figs. 21A and 21B, while the former case is described with

25

reference to Figs. 22A and 22B.

[0067]

Fig. 21A structurally illustrates the section permutator of Fig. 20.

[0068]

The section permutator 2101 includes intra-cyclic-block permutators 2111 through 2114 and a column-row permutator 2131. Rather than providing four intra-cyclic-block permutators, for example, a single intra-cyclic-block permutator may be provided and perform the four intra-cyclic-block permutation processes, described later, switching therebetween over time.

[0069]

The intra-cyclic-block permutators (2111–2114) each perform an intra-cyclic-block permutation on the Q -bit (8-bit) cyclic blocks (QB1–QB4). The intra-cyclic-block permutations applied to the cyclic blocks in each section may all apply the same permutation rules, may each apply different permutation rules, or may involve a subset of the sections applying identical permutation rules while other differ.

[0070]

The column-row permutator 2131 performs a column-row permutation on each group of $M \times Q$ ($= 32$) bits. Specifically, the column-row permutator 2131 writes the $M \times Q$ bits row-wise into a $M \times Q$ (8×4) matrix, then reads the $M \times Q$ bits column-wise therefrom, thus applying the column-row permutation. The column-row permutation applied by the column-row permutator 2131 resembles the permutation applied to the 12×1350 matrix shown in Figs. 9A and 9B, where Q columns and M rows are used, the writing process occurs column-wise, and the reading process occurs row-wise.

[0071]

Figs. 21B is a structural representation of the section permutator shown in Fig. 21A. In Fig. 21B, the constellation words of $M = 4$ bits are each denoted b1 through b4.

[0072]

However, a variation in which the intra-cyclic-block permutation process is not part of the section permutation process is also plausible.

[0073]

For example, a section permutation implemented without executing the intra-cyclic-block permutation and a structure of mapping by the section permutator are shown in Figs. 22A and 22B. The section permutator 2201 includes a column-row permutator 2131 and performs a simple column-row permutation. In Fig. 22B, the constellation words of $M = 4$ bits are each denoted b1 through b4.

[0074]

The section permutation described in Figs. 21A, 21B, 22A and 22B may be applied to cyclic blocks QB5–QB8 and QB9–QB12.

[0075]

Advantageously, an additional cyclic block permutation may be applied to the N cyclic blocks before the bit interleaver performs the section permutation. Fig. 23 is a structural diagram of the additional cyclic block permutation applied by the bit interleaver. In this context, the cyclic block permutation plays a role similar to that of the permutation performed by the bit-to-cell demultiplexer in the DVB-T2 standard.

[0076]

The bit interleaver 2300 shown in Fig. 23 includes a cyclic block permutator 2310 and a bit permutator 2010 (which in turn includes section permutators 2021–2023).

[0077]

The cyclic block permutator 2310 performs cyclic block permutations 2311–2318 on the cyclic blocks QB1–QB12. Here, the cyclic block permutations 2311–2318 all follow the same permutation rules.

[0078]

The cyclic block permutation performed on the N cyclic blocks is particularly advantageous in enabling optimized mapping of the LDPC codeword bits onto the

constellation bits, resulting in optimized performance.

[0079]

Fig. 24 is a schematic block diagram of the bit interleaver 2300 shown in Fig. 23. The bit interleaver 2400 shown in Fig. 24 includes three stages, A, B, and C.

[0080]

Stage A: (inter) cyclic block permutation

Stage B: intra-cyclic-block permutation

Stage C: column-row permutation

The (inter) cyclic block permutation is applied to the N cyclic blocks making up the codeword, the intra-cyclic-block permutation is applied to the Q bits of each cyclic block, and the column-row permutation is applied to the $M \times Q$ sections.

[0081]

The bit interleaver 2400 shown in Fig. 24 includes the cyclic block permutator 2310 and the bit permutator 2010 (which in turn includes the section permutators 2101–2103). The section permutator 2101 (2102, 2103) includes the intra-cyclic-block permutators 2111–2114 (2115–2118, 2119–2122) and the column-row permutator 2131 (2132, 2133).

[0082]

In the bit interleaver 2400, the (inter) cyclic block permutation is performed by the cyclic block permutator 2310 (stage A), the intra-cyclic-block permutation is performed by the intra-cyclic-block permutators 2111–2122 (stage B), and the column-row permutation is performed by the column-row permutators 2131–2133 (stage C).

[0083]

The intra-cyclic-block permutators 2111–2122 may be removed from the bit interleaver 2400 shown in Fig. 24, such that the bit interleaver is configured not to perform the intra-cyclic-block permutation. Also, the bit interleaver 2400 may perform the (inter) cyclic block permutation before the intra-cyclic-block permutation

rather than after the intra-cyclic-block permutation, or may perform the (inter) cyclic block permutation before and after the intra-cyclic-block permutation.

[0084]

The intra-cyclic-block permutators may have similar structures. This is advantageous in that the intra-cyclic-block permutators are thus implementable using identical resources (e.g., hardware blocks). Alternatively, the intra-cyclic-block permutations may consist of cyclical shifts, which allow for efficient hardware implementation using barrel shifters. An implementation using the barrel shifters in the LDPC decoder is also possible.

[0085]

The following describes a transmitter that includes the bit interleaver performing a bit interleaving process that satisfies Conditions 1 and 2, with reference to Fig. 25.

[0086]

Fig. 25 is a block diagram of a transmitter pertaining to a further Embodiment of the present disclosure. As shown in Fig. 25, a transmitter 2500 includes a BICM encoder (which in turn includes an LDPC encoder 2510, a bit interleaver 2520, and a constellation mapper 2530) and a modulator 2540.

[0087]

The LDPC encoder 2510 encodes input blocks into codewords using QC-LDPC codes, and then transmits the codewords to the bit interleaver 2520.

[0088]

The bit interleaver 2520 receives the codeword in QC-LDPC code from the LDPC encoder 2510. The codeword is made up of $N = 12$ cyclic blocks, each cyclic block including $Q = 8$ bits. The bit interleaver 2520 performs interleaving on the bits of the codewords so as to permute the bits of each of the codewords. The bit interleaver 2520 divides the interleaved codeword into a plurality of constellation words, each made up of $M = 4$ bits and indicating one of $2^M = 16$ constellation points ,

then outputs the constellation words to the constellation mapper 2530. The bit interleaver 2520 may apply the bit interleaving process discussed with reference to Figs. 19 through 22A and 22B, or may apply a variant bit permutation process. Also, the bit interleaver 2520 may apply an additional cyclic block permutation process, such as the process discussed with reference to Figs. 23 and 24 or a variation thereof.

[0089]

The constellation mapper 2530 receives the constellation words from the bit interleaver 2520 and performs constellation mapping on the constellation words so received.

[0090]

The modulator 2740 generates a transmission signal using orthogonal frequency division multiplexing (hereinafter, OFDM) or similar.

[0091]

The following describes a BICM encoder that includes the bit interleaver performing a bit interleaving process that satisfies Conditions 1 and 2, with reference to Fig. 26.

[0092]

Fig. 26 is a block diagram of an example BICM encoder pertaining to a further Embodiment of the disclosure. In Fig. 26, the BICM encoder 2600 corresponds to the above-given parameters (i.e., $Q = 8$, $N = 12$, $M = 4$).

[0093]

The BICM encoder 2600 shown in Fig. 26 includes a main memory 2601, an LDPC controller 2611, a rotator 2612, a check node processor group 2613, a de-rotator 2614, a QB counter 2631, table A 2632, interleaver B 2633, a register group 2634, interleaver C 2635, and a mapper group 2651.

[0094]

In Fig. 26, given that $Q = 8$, the main memory 2601 reads eight bits at a time, the check node processor group 2613 includes eight check node processors, and the

mapper group 2651 includes eight mappers. Also, given that $M = 4$, the register group 2634 includes four registers.

[0095]

The main memory 2601 receives a sequence of bits for transmission from, for example, the (non-diagrammed) input processor, and stores the received bit sequence.

[0096]

The LDPC controller 2611 outputs a read address to the main memory 2601. The main memory 2601 accordingly outputs the bit sequence, eight bits at a time beginning with the lead bit, to the rotator 2612. The rotator 2612 is controlled by the LDPC controller 2611 to perform a predetermined number of cyclical shifts on the eight bits supplied thereto by the main memory 2601, and then outputs the eight cyclically-shifted bits to the check node processors of the check node processor group 2613, one bit at a time, the bits and the check node processors being in one-to-one correspondence. Each check node processor of the check node processor group 2613 is controlled by the LDPC controller 2611 to perform check node processing on each bit input thereto, then outputs the results to the de-rotator 2614. The de-rotator 2614 is controlled by the LDPC controller 2611 to perform a predetermined number of cyclic shifts on the eight bits received from the check node processor group 2613 so as to cancel the cyclic shift applied by the rotator 2612, and then outputs the eight shifted bits to the main memory 2601. The LDPC controller 2611 outputs a write address to the main memory 2601. The main memory 2601 accordingly stores the eight bits supplied thereto by the de-rotator 2614. The LDPC controller 2611, the rotator 2612, the check node processor group 2613, and the de-rotator 2614 make up the BICM encoder in the LDPC encoder 2510 shown in Fig. 25.

[0097]

The QB counter 2631 counts from 0 to 11 and outputs the counter value to table A 2632. The count operation of the QB counter 2631 is defined in consideration of $N = 12$.

[0098]

Table A 2632 is a simple look-up table in which the cyclic block permutation rules are stored. That is, table A 2632 stores $N = 12$ pieces of cyclic block read order information (information associating a different cyclic block with each of the 12 counter values from the QB counter 2631). Table A 2632 outputs a read address to the main memory 2601 such that the bits of one cyclic block (i.e., $Q = 8$ bits) corresponding to the counter value supplied by the QB counter 2631 are supplied from the main memory 2601 to interleaver B 2633. Thus, the main memory 2601 outputs the bits of one cyclic block corresponding to the counter value of the QB counter 2631 to interleaver B 2633. The processing using table A 2632 is executed as the cyclic block permutation process (stage A).

[0099]

Interleaver B 2633 performs a predetermined number of cyclical shifts on the bits of the cyclic block supplied by the main memory 2601, and outputs the results to a first tier register of the register group 2634. The processing by interleaver B 2633 is executed as the intra-cyclic-block permutation process (stage B). Each register in the register group 2634 stores one cyclic block of bits with timing matching the reception of a control pulse, and outputs the cyclic block of bits before receiving the next control pulse.

[0100]

When the QB counter 2631 performs the aforementioned process for counter values 0 through 3, the bits of four cyclic blocks (i.e., 32 bits) are input to interleaver C 2635. At this time, interleaver C 2635 interleaves the bits of the four cyclic blocks input thereto, and the mappers of the mapper group 2651 output one constellation word of bits (i.e., $M = 4$ bits). Through the interleaving process, four bits, i.e., one from each of the four registers in the register group 2634, are supplied to each mapper. This processing by interleaver C 2635 is executed as the column-row permutation process (stage C).

[0101]

The QB counter 2631, table A 2632, interleaver B 2633, the register group 2634, and interleaver C 2635 make up the bit interleaver 2520 of the BICM encoder shown in Fig. 25.

5 [0102]

The mappers of the mapper group 2651 each map four bits supplied thereto from interleaver C 2635 to a constellation, then output the results. The mapper group 2651 makes up the constellation mapper 2530 of the BICM encoder shown in Fig. 25.

[0103]

10 For each codeword, the above-described set of processes is applied three times, once each for counter values 0–3, 4–7, and 8–11 of the QB counter 2631.

[0104]

The Embodiment depicted in Fig. 26 includes Q mappers operating in parallel. However, the mappers are also realizable as a BICM encoder so as to decrease or
 15 increase the parallelism. For example, the number of parallel interleaver sections in the bit interleaver, i.e., the quotient of N/M , obviously may be increased so as to easily enhance parallelism. Such methods enable the parallelism to be optimized by parallelizing the $Q \times N/M$ mappers. Implementing such parallelism, without drawbacks, in the bit interleaver is beneficial.

20 [0105]

The following describes a receiver receiving signals from a transmitter that includes the bit interleaver performing a bit interleaving process that satisfies Conditions 1 and 2, with reference to Fig. 27.

[0106]

25 Fig. 27 is a block diagram of an example receiver, including a non-iterative BICM decoder, pertaining to a further Embodiment of the disclosure. The receiver performs the transmitter operations in reverse.

[0107]

The receiver 2700 shown in Fig. 27 includes a demodulator 2710 and a non-iterative BICM decoder (which in turn includes a constellation demapper 2720, a bit deinterleaver 2730, and an LDPC decoder 2740).

[0108]

5 The demodulator 2710 performs a demodulation process through OFDM, for example, and outputs the demodulated results.

[0109]

The constellation demapper 2720 of the non-iterative BICM decoder generates a soft bit sequence by applying a demapping process to the input from the demodulator 2710, and outputs the soft bit sequence so generated to the constellation demapper 2730. The soft bits are a measure of probability that a given bit is a zero-bit or a one-bit. Typically, the soft bits are represented as log-likelihood ratios (hereinafter, LLRs), defined as follows.

[0110]

$$15 \quad \text{LLR}(b) = \ln [p(b = 0)/p(b = 1)]$$

where $p(b = 0)$ indicates the probability of the given bit b being a zero-bit, and $p(b = 1)$ represents the probability of the given bit b being a one-bit. Of course, $p(b = 0) + p(b = 1) = 1$.

[0111]

20 The bit deinterleaver 2730 performs an interleaving process (i.e., a bit de-interleaving process) on the soft bit sequence output from the constellation demapper 2720 so as to cancel the bit interleaving process applied to the bit sequence by the bit interleaver 2730 in the transmitter illustrated in Fig. 25.

[0112]

25 The LDPC decoder 2740 receives the soft bit sequence deinterleaved by the bit deinterleaver 2730, and performs an LDPC decoding process using the soft bit sequence so received.

[0113]

One improved technique offering significant performance gains is iterative BICM decoding. Fig. 28 illustrates an iterative BICM decoder.

[0114]

Fig. 28 is a block diagram of an example receiver, including an iterative BICM decoder, pertaining to a further Embodiment of the disclosure. The receiver performs the transmitter operations in reverse.

[0115]

As shown in Fig. 28, a receiver 2800 includes the demodulator 2710 and an iterative BICM decoder (which in turn includes the constellation demapper 2720, the bit deinterleaver 2730, the LDPC decoder 2740, a subtractor 2760, and a bit interleaver 2750).

[0116]

The receiver 2800 of Fig. 28 has the constellation demapper 2720 performing a constellation demapping process, the bit deinterleaver 2730 performing a bit deinterleaving process, and the LDPC decoder 2740 performing an LDPC decoding process.

[0117]

After one or more LDPC decoding iterations, extrinsic information, obtained by the subtractor 2760 subtracting the input to the LDPC decoder 2740 from the output of the LDPC decoder 2740, is output to the bit interleaver 2750. The bit interleaver 2750 performs an interleaving process on the extrinsic information using the same interleaving rules as those applied to the bit sequence by the bit interleaver of the transmitter depicted in Fig. 25. The bit interleaver 2750 then feeds back the interleaved extrinsic information to the constellation demapper 2720. The constellation demapper 2720 uses the extrinsic information so fed back as a-priori information to compute more reliable LLR values. The bit deinterleaver 2730 then performs an interleaving process on the newly computed LLR values (i.e., a bit de-interleaving process) so as to cancel the bit interleaving process applied to the bit

sequence by the bit interleaver in the transmitter depicted in Fig. 25 and restore the original order of the bit sequence. The LDPC decoder 2740 uses the LLR values so de-interleaved in the LDPC decoding process.

[0118]

As shown in Fig. 28, an iterative decoding loop is made up of four elements, namely the constellation demapper 2720, the bit deinterleaver 2730, the LDPC decoder 2740, and the bit interleaver 2750. The bit deinterleaver 2730 and the bit interleaver 2750 have beneficially very low latency, ideally zero, and low complexity. This results in a more efficient receiver implementation. The bit deinterleaver 2730 and the bit interleaver 2750 described above satisfy both of these conditions.

[0119]

Fig. 29 illustrates an iterative BICM decoder realizing very efficient parallel implementation.

[0120]

Fig. 29 is a block diagram of an example BICM decoder pertaining to a further Embodiment of the disclosure. In Fig. 29, the BICM decoder 2900 corresponds to the above-given parameters (i.e., $Q = 8$, $N = 12$, $M = 4$).

[0121]

As shown, the BICM decoder 2900 includes a main LLR memory 2901, a buffer LLR memory 2902, an LDPC controller 2911, a rotator 2912, a check node processor group 2913, a de-rotator 2914, a QB counter 2931, table A 2932, a subtractor group 2933, interleaver B 2934, register group 2935, interleaver C 2936, a demapper group 2937, deinterleaver C 2938, register group 2939, deinterleaver B 2940, and a delay 2941.

[0122]

In Fig. 29, given that $Q = 8$, the main LLR memory 2901 and the buffer LLR memory 2902 each read eight LLR values at a time, the check node processor group 2913 includes eight check node processors, and the demapper group 2951 includes

eight demappers. Also, given that $M = 4$, the register groups 2935 and 2972 each include four registers.

[0123]

The demappers in the demapper group 2937 each perform a demapping process on the output of a demodulator (not diagrammed), then outputs the LLR values so obtained to deinterleaver C 2938. The demapper group 2937 makes up the constellation demapper 2720 of the iterative BICM decoder shown in Fig. 28.

[0124]

Deinterleaver C 2938 applies a deinterleaving process to the LLR values (i.e., a new interleaving process cancelling the interleaving process applied by the transmitter during stage C), then outputs the deinterleaved LLR values to the registers of the register group 2939. Each register stores one cyclic block of LLR values (i.e., eight LLR values). In register group 2939, the cyclic block of LLR values stored by each register is sequentially output to a later tier such that the content of each register is sequentially updated. Deinterleaver B 2940 applies a deinterleaving process to the cyclic block of (eight) LLR values (i.e., a new interleaving process cancelling the interleaving process applied by the transmitter during stage B), then writes the results to the main LLR memory 2901 and the buffer LLR memory 2902 in accordance with table A 2932 (discussed later). An interleaving process cancelling the interleaving process applied by the transmitter during stage A is achieved by this writing to the main LLR memory 2901 and the buffer LLR memory 2902 in accordance with the content of Table A 2932.

[0125]

Thus, the main LLR memory 2901 stores the post-deinterleaving LLR values, and is also used by the LDPC decoder (i.e., the LDPC controller 2911, the rotator 2912, the check node processor group 2913, and the de-rotator 2914). The LDPC decoding process is an iterative process involving one or more iterations. In each LDPC decoding iteration, the LLR values in the main LLR memory 2901 are updated. In

order to compute the extrinsic information needed for iterative BICM decoding, the old LLR values are saved in the buffer LLR memory 2902.

[0126]

The following describes the LDPC decoder operations.

5 [0127]

The LDPC controller 2911 outputs the read address to the main LLR memory 2901 in accordance with the parity-check matrix of the LDPC codes. Thus, the main LLR memory 2901 sequentially outputs one cyclic block of LLR values to the rotator 2912. The rotator 2912 is controlled by the LDPC controller 2911 to perform a
10 predetermined number of cyclical shifts on the cyclic block of LLR values supplied sequentially by the main LLR memory 2901, then outputs the LLR values so shifted to the check node processors of the check node processor group 2913 one at a time. The check node processors of the check node processor group 2913 are controlled by the LDPC controller 2911 to perform a check node process on the sequence of LLR values
15 sequentially input thereto. Next, the check node processors of the check node processor group 2913 are controlled by the LDPC controller 2911 to sequentially output the LLR values resulting from the check node process. The de-rotator 2914 is controlled by the LDPC controller 2911 to performs a predetermined number of cyclic shifts cancelling the cyclic shift applied to the cyclic block sequentially received from
20 the check node processor group 2913 by the rotator 2912, then sequentially outputs the shifted results to the main LLR memory 2901. The LDPC controller 2911 outputs the write address to the main LLR memory 2901 in accordance with the parity-check matrix of the LDPC codes. Thus, the main LLR memory 2901 stores the cyclic block of results sequentially supplied thereto by the de-rotator 2914. The LDPC controller
25 2911 repeatedly executes the above-described processing in accordance with the parity-check matrix of the LDPC codes.

[0128]

After a predetermined number of LDPC iterations, a BICM iteration is

performed. The LDPC and BICM iterations are also respectively referred to as inner and outer iterations. These two types of iterative may also overlap in some implementations. This enables the speed of convergence to be increased. The BICM and LDPC decoding processes are well known in the field, and the details thereof are thus omitted.

[0129]

The QB counter 2931 counts from 0 to 11 and outputs the counter value to table A 2932. The count operation of the QB counter 2931 is defined in consideration of $N = 12$.

[0130]

Table A 2932 is a simple look-up table in which the cyclic block permutation rules are stored. That is, table A 2932 stores $N = 12$ pieces of cyclic block read (and write) order information (i.e., with information associating a different cyclic block with each of the 12 counter values from the QB counter 2631). Table A 2932 outputs the read address to the main LLR memory 2901 and to the buffer LLR memory 2902 such that one cyclic block of LLR values corresponding to the counter value supplied by the QB counter 2931 are supplied to the subtractor group 2933 by the main LLR memory 2901 and to the buffer LLR memory 2902. Thus, the main LLR memory 2901 and the buffer LLR memory 2902 each output a cyclic block of LLR values corresponding to the counter value of the QB counter 2931 to the subtractor 2933. The delayer 2941 makes a delay adjustment such that the position of the LLR value read from the main LLR memory 2901 and the buffer LLR memory 2902 match the write position of the same LLR values to the main LLR memory 2901 and the buffer LLR memory 2902. The processing using table A 2932 is executed as the cyclic block permutation process (stage A).

[0131]

The subtractor 2933 in the subtractor group subtracts the output of the buffer LLR memory 2902 from the output of the main LLR memory 2901, then outputs the

extrinsic information for one cyclic block thus obtained (i.e., eight pieces of extrinsic information) to interleaver B 2934.

[0132]

Interleaver B 2634 performs a predetermined number of cyclical shifts on the pieces of extrinsic information for one of the cyclic blocks supplied by the subtractor 2933, and outputs the results to a first tier register of the register group 2935. The processing performed by interleaver B 2934 corresponds to the intra-cyclic-block permutation (stage B). Each register in the register group 2935 stores eight bits with timing matching the reception of a control pulse, and outputs the eight bits before receiving the next control pulse.

[0133]

When the QB counter 2631 performs the aforementioned process for counter values 0 through 3, the extrinsic information for four cyclic blocks (i.e., 32 pieces of extrinsic information) are input to interleaver C 2936. At this time, interleaver C 2936 performs an interleaving process on the extrinsic information input thereto for four cyclic blocks, then outputs one constellation word of extrinsic information (i.e., $M = 4$ pieces of extrinsic information) to each demapper of the demapper group 2937. Through the interleaving process, the four pieces of extrinsic information are supplied to the demappers of the demapper group 2951 from the four registers in register group 2935, one at a time. This processing by interleaver C 2936 is executed as the column-row permutation process (stage C).

[0134]

The QB counter 2931, table A 2932, interleaver B 2934, the register group 2935, and interleaver C 2936 make up the bit interleaver 2750 of the BICM decoder shown in Fig. 28.

[0135]

The demappers of the demapper group 2937 uses the four pieces of extrinsic information supplied by interleaver C 2936 as a-priori information to perform a

demapping process, then output the resulting LLR values to deinterleaver C 2938.

[0136]

Deinterleaver C 2938 applies a deinterleaving process to the LLR values (i.e., a new interleaving process cancelling the interleaving process applied by the transmitter during stage C), then outputs the deinterleaved LLR values to the registers of the register group 2939. Each register stores one cyclic block of LLR values (i.e., eight LLR values). In register group 2939, the cyclic block of LLR values stored by each register is sequentially output to a later tier such that the content of each register is sequentially updated. Deinterleaver B 2940 applies a deinterleaving process to the cyclic block of (eight) LLR values (i.e., a new interleaving process cancelling the interleaving process applied by the transmitter during stage B), then writes the results to the main LLR memory 2901 and the buffer LLR memory 2902. The main LLR memory 2901 and the buffer LLR memory 2902 receive the write address from table A 2932 via the delayer 2941, then store one cyclic block of LLR values (i.e., eight LLR values) received from the deinterleaver 2940 in accordance with the received write address. An interleaving process cancelling the interleaving process applied by the transmitter during stage A (i.e., a deinterleaving process) is achieved by this writing in accordance with the content of table A 2932.

[0137]

For each codeword, the above-described set of processes is applied three times, once each for counter values 0–3, 4–7, and 8–11 of the QB counter 2931.

[0138]

The QB counter 2931, table A 2932, deinterleaver B 26938, the register group 2939, and interleaver C 2940 make up the bit interleaver 2730 of the BICM decoder shown in Fig. 28.

[0139]

Interleaver B 2934 and deinterleaver B 2940 are reconfigurable. This requires a certain hardware cost, but this cost is minimized by attentive design.

Interleaver C 2936 and deinterleaver 2938 implement the column-row permutation. This permutation is uniform for a predetermined constellation size. Thus, the cost of implementation is reduced.

[0140]

5 The Embodiment depicted in Fig. 29 includes Q demappers operating in parallel. However, the demappers are also realizable as an iterative BICM decoder by decreasing or increasing the parallelism. For example, the number of parallel interleaver sections in the bit interleaver, i.e., the quotient of N/M , obviously may be increased so as to easily enhance parallelism. Such methods enable the parallelism to be optimized by parallelizing the $Q \times N/M$ demappers. The above-described bit interleaver has the merit of being implementable with such parallelism without trouble.

[0141]

(Further Experimenter Discoveries)

15 The interleavers satisfying Conditions 1 and 2 given above (i.e., parallel interleavers) assume that the number of bits per constellation word M is a divisor of the number of cyclic blocks N . However, M is not typically a divisor of N . For example, the 16K LDPC codes used in the DVB-T2 standard has $N = 45$ cyclic blocks per 16K LDPC codeword. When M is not a divisor of N , the mapping of square constellations, such as QAM constellations where M is even, is not straightforward.

20 [0142]

Thus, a particular solution is proposed that involves excluding one or more of the N cyclic blocks and implementing the interleaver discussed in Embodiment 1 (i.e. the parallel interleaver), above, only to the remaining cyclic blocks.

[0143]

25 In other words, N' cyclic blocks are selected from among the N cyclic blocks such that N' is a multiple of the number of bits per constellation words M in the bit interleaver. The bit interleaver divides the N' selected cyclic blocks into N'/M sections such that each section includes M cyclic blocks, then performs a section

permutation on each section. The bits of the excluded (i.e., not selected) cyclic block may or may not be interleaved.

[0144]

For example, the excluded cyclic blocks may be the cyclic blocks having a variable node of the lowest weight. For the example RA QC LDPC codes (see Fig. 5), the excluded cyclic blocks are the cyclic block of the parity section (having a variable node weight of two), and are beneficially the last one or more cyclic blocks of the codeword.

[0145]

Fig. 30 illustrates a cyclic block subject to and a cyclic block excluded from (i.e., an excluded block of) the interleaving process described above (i.e., Embodiment 1). In Fig. 30, the code is 16K LDPC code conforming to the DVB-T2 standard, and the constellation is a 16-QAM constellation. As shown, 44 of the cyclic blocks are subject to interleaving (i.e., blocks 1 through 44), and cyclic block 45, in the last row, is the one cyclic block not subject to interleaving (i.e., the excluded block). The four blackened squares represent the four bits of the first constellation.

[0146]

In general, the number of interleaver sections (each made up of M cyclic blocks) is given by $\text{floor}(N/M)$, and the number of excluded cyclic blocks is given by $\text{rem}(N, M)$. Here, $\text{floor}(N/M)$ is a function that returns the largest integer smaller than or equal to N/M , and $\text{rem}(N, M)$ is a function that returns the remainder of dividing N by M .

[0147]

Table 2 indicates the number of sections and the number of excluded cyclic blocks for various constellation sizes (i.e., number of bits per constellation M), for the 16K LDPC codes of the DVB-T2 standard (where $N = 45$ cyclic blocks are used).

[0148]

[Table 2]

Constellation size	M	No. of sections	No. of excluded blocks
QPSK	2	22	1
16-QAM	4	11	1
64-QAM	6	7	3
256-QAM	8	5	5

According to the interleaving method satisfying Conditions 1 and 2 as described above, each constellation word is mapped onto M cyclic blocks. However, for large constellations (i.e., constellations having many constellation points), an interleaving method satisfying Conditions 1 and 2 requires an extremely large amount of delay registers (see the implementation described with reference to Figs. 26 through 29). Using an extremely large amount of registers leads to an increase in circuit area and electric power consumption. In addition, reducing the number of cyclic blocks onto which each constellation word is mapped is beneficial for increasing the overlap between the outer (BICM) iterations and the inner (LDPC) iterations, in turn reducing overall BICM decoding latency.

[0149]

By mapping two or more bits of each constellation word onto the same cyclic block, the number of cyclic blocks onto which each constellation word is mapped is reduced. The number of constellation word bits mapped onto the same cyclic block is termed the folding factor and is denoted F . For example, when $F = 2$ for a 16-QAM constellation, each constellation word is mapped onto four cyclic blocks rather than two. The only constraint is that the folding factor F (which is an integer greater than one) must be a divisor of both M and Q . When $F = 1$, no folding is involved, i.e., the situation corresponds to Embodiment 1, described above.

[0150]

A complex QAM constellation symbol is decomposed into two identical real PAM symbols. Thus, the M bits of the QAM constellation are divided into two identical real PAM symbols, which are sets of $M/2$ bits. The bits of each constellation word are then mapped onto the same number $M/2$ of cyclic blocks. A folding factor of $F = 2$ is advantageous for QAM constellation.

[0151]

For complex constellations that cannot be decomposed into real numbers, such as 8-PSK (phase shift keying), 16-APSK (amplitude phase shift keying), 32-APSK and so on in the DVB-S2 standard, the folding method is not easily applicable. However, the folding method is usable when F is a divisor of M . Unfortunately, this prevents any guarantee that each cyclic block has only bits of the same robustness level from the constellations mapped thereto.

[0152]

Beneficially, the folding method is, for example, applied such that only bits of the same robustness level in the constellations are mapped to the cyclic blocks.

[0153]

Folding is also beneficial in reducing the number of excluded cyclic blocks, or even eliminating the need to exclude any cyclic blocks. As described above, a certain number of cyclic blocks making up the codeword must be excluded when the interleaver described in Embodiment 1 (i.e., a parallel interleaver) is used.

[0154]

Without folding (i.e., when $F = 1$), the number of groups of M cyclic blocks (i.e., the number of sections) is $\text{floor}(N/M)$, and the number of excluded cyclic blocks is $\text{rem}(N, M)$. With folding, the number of groups of M/F cyclic blocks is $\text{floor}(N/(M/F))$, and the number of excluded cyclic blocks is $\text{rem}(N, M/F)$. Specific example of these numbers are given in Table 3, for the LDPC codes used in the DVB-T2 standard.

[0155]

[Table 3]

LDPC codeword length	Constellation size	M	Without folding		With folding	
			No. of sections	No. of excluded blocks	No. of sections	No. of excluded blocks

16K (N = 45, Q = 360)	QPSK	2	22	1	44	1
	16-QAM	4	11	1	22	1
	64-QAM	6	7	3	15	0
	256-QAM	8	5	5	11	1
64K (N = 180, Q = 360)	QPSK	2	90	0	180	0
	16-QAM	4	45	0	90	0
	64-QAM	6	30	0	60	0
	256-QAM	8	22	4	45	0

The inventor discovered that, in order to perform folding (where F is an integer equal to or greater than two), Conditions 1 and 2 must be modified into Conditions 1A and 2A, as given below.

[0156]

5 (Condition 1A)

The M bits of each constellation word are each mapped to one of M/F different cyclic blocks of the LDPC codeword. This is equivalent to mapping one bit from M/F different cyclic blocks of the LDPC codeword to a constellation word. This is schematically illustrated in Fig. 31A.

10 [0157]

(Condition 2A)

All constellation words mapped to the M/F cyclic blocks are mapped only to that particular cyclic block. This is equivalent to mapping all $M \times Q/F$ bits of the M/F different cyclic blocks each made up of Q bits to exactly Q/F constellations. This is

15 schematically illustrated in Fig. 31B.

[0158]

When $F = 1$, no folding is involved, and thus Conditions 1A and 2A are equivalent to Conditions 1 and 2.

[0159]

20 (Embodiment 2)

The following describes the details of a bit interleaver (i.e., a parallel bit interleaver) that satisfies conditions 1A and 2A, given above. In the following description, processing and the units performing such processing are labeled with the

same reference numbers wherever applicable.

[0160]

In the present document, each group of M/F cyclic blocks or of Q/F constellation words is referred to as a folding section (or as a folding interleaver section).

[0161]

When $F = 1$ (i.e., no folding), the folding interleaver sections match the interleaver sections and the bit interleaver is configured identically to the bit interleaver from Embodiment 1.

[0162]

Folding occurs when F is an integer greater than one. Embodiment 2 describes an example of folding where $F = 2$.

[0163]

Fig. 32 is a block diagram illustrating the configuration of a bit interleaver satisfying Conditions 1A and 2A, when $Q = 8$, $M = 4$, $N = 12$, and $F = 2$, as another Embodiment of the disclosure.

[0164]

In Fig. 32, the QC-LDPC codewords are made up of $N = 12$ cyclic blocks QB1 through QB12, each in turn made up of $Q = 8$ bits. Each of the 24 constellation words is made up of $M = 4$ bits. Each constellation word indicates one of $2^M = 16$ constellation points. The bit interleaver is divided into $F \times N/M = 6$ folding sections, and 24 constellation words are each associated with one of the $F \times N/M = 6$ folding sections.

[0165]

The bit interleaver 2000A includes a bit permutator 2010A. The bit permutator 2010A includes $F \times N/M = 6$ folding section permutators 2021A–2026A each operating independently. Rather than providing six folding section permutators, a single folding section permutator may be provided so as to performs six (later

described) folding section permutation processes, switching therebetween over time.

[0166]

The folding section permutators (2021A, 2022A, 2023A, 2024A, 2025A, 2026A) are independent and each apply a folding section permutation process to the 16 bits of two cyclic blocks such that $F = 2$ bits from each of $M/F = 2$ cyclic blocks (QB1–QB2, QB3–QB4, QB5–QB6, QB7–QB8, QB9–QB10, QB11–QB12) are mapped to a given set of four constellation words (C1–C4, C5–C8, C9–C12, C13–C16, C17–C20, C21–C24).

[0167]

Conditions 1A and 2A, described above, simply ensure that the bit interleaver is divisible into $F \times N/M$ parallel folding sections. The folding section permutations applied to the parallel folding sections may all apply the same permutation rules, may each apply different permutation rules, or may involve a subset of the sections applying identical permutation rules while other differ.

[0168]

For example, the folding section permutators may map Q bits from each cyclic block to bits of Q/F constellation words having the same robustness level. This is illustrated in Figs. 33A, 33B, 34A, and 34B for a situation where $Q = 8$ and $M = 4$.

[0169]

Fig. 34A is a block diagram of a (folding) section permutator when $F = 1$ (i.e., without folding), and is similar to Fig. 22A.

[0170]

Fig. 34B is a block diagram of two folding section permutators from Fig. 32 where $F = 2$ (i.e., with folding).

[0171]

However, in the example of Fig. 34B, the constellations are 16-QAM constellations. Thus, the bits of the constellations have two robustness levels. Bits b1 and b3 have the same robustness level, and bits b2 and b4 have the same robustness

level, the former robustness level being different from the latter robustness level.

[0172]

The folding section permutators 2201A (and 2202A) each include a column-row permutator 2131A (or 2132A).

5 [0173]

The column-row permutators 2131A (and 2132A) each perform a column-row permutation process on $Q \times M/F = 16$ cyclic blocks QB1 and QB2 (or QB3 and QB4). To be exact, the column-row permutators 2131A (and 2132A) write $Q \times M/F = 16$ bits row-wise into a $Q \times M/F$ (8×2) matrix, then read the 16 bits so written column-wise to perform the column-row permutation process. The column-row permutation applied by the column-row permutators 2131A and 2132A resembles the permutation applied to the 12×1350 matrix shown in Figs. 9A and 9B, where Q columns and M/F rows are used, the writing process occurs row-wise, and the reading process occurs column-wise.

10 [0174]

Folding with a folding factor of F reduces the number of cyclic blocks mapped to a single constellation word. Thus, the matrix used in the column-row permutation is reduced in size, from M rows to M/F rows.

[0175]

20 Fig. 33A illustrates the mapping function performed by the (folding) section permutator from Fig. 34A. Fig. 33B illustrates the mapping function performed by the two folding section permutators from Fig. 34B. In Figs. 33A and 33B, each constellation word of $M = 4$ bits is denoted b1 through b4. The portions outlined in thicker lines represent the portions mapped to constellation C1.

25 [0176]

As shown in Figs. 33A and 34A, the eight bits of a cyclic block (being of equal importance) are each mapped to the bits of eight constellation words having the same bit index (i.e., having the same robustness level). Also, in Figs. 33B and 34B, the

eight bits of a cyclic block (being of equal importance) are mapped to the bits of four constellation words having the same robustness level.

[0177]

The folding section permutation described in Fig. 34B may be applied to cyclic blocks QB5–QB6, QB7–QB8, QB9–QB10, and QB11–QB12.

[0178]

The folding section permutators of Figs. 34A and 34B may also include a subunit performing an intra-cyclic-block permutation on the bits of cyclic blocks QB1–QB4 prior to the column-row permutation.

[0179]

Advantageously, an additional cyclic block permutation may be applied to the N cyclic blocks before the bit interleaver performs the folding section permutation. Fig. 35 is a structural diagram of the additional cyclic block permutation applied by the bit interleaver.

[0180]

The bit interleaver 2300A shown in Fig. 35 includes the cyclic block permutator 2310 and a bit permutator 2010A (which in turn includes folding section permutators 2021A–2026A).

[0181]

Fig. 36 is a schematic block diagram of the bit interleaver 3500 shown in Fig. 23.

[0182]

The bit interleaver 2400A shown in Fig. 36 includes the cyclic block permutator 2310 and a bit permutator 2200A (which in turn includes folding section permutators 2201A–2206A).

[0183]

The folding section permutators 2201A–2206A each include a column-row permutator 2131A–2136A. The folding section permutators 2133A–2136A each

perform substantially identical permutations with the column-row permutators 2131A–2132A.

[0184]

The bit interleavers shown in Figs. 35 and 36 may each include an additional subunit performing an intra-cyclic-block permutation on the bits of cyclic blocks QB1–QB12 before or after the cyclic block permutation.

[0185]

The following describes a transmitter that includes the bit interleaver performing a bit interleaving process that satisfies Conditions 1A and 2A, with reference to Fig. 37.

[0186]

Fig. 37 is a block diagram of a transmitter pertaining to a further Embodiment of the present disclosure. The transmitter 2500A shown in Fig. 37 is configured similarly to the transmitter 2500 of Fig. 25, differing in that the bit interleaver 2520 is replaced with a bit interleaver 2520A.

[0187]

The bit interleaver 2520A receives the codeword in QC-LDPC code from the LDPC encoder 2510. The codeword is made up of $N = 12$ cyclic blocks, each cyclic block including $Q = 8$ bits. The bit interleaver 2520A performs interleaving on the bits of the codewords. The bit interleaver 2520A divides the interleaved codeword into a plurality of constellation words, each made up of $M = 4$ bits and indicating one of $2^M = 16$ constellation points, then outputs the constellation words to the constellation mapper 2530. The bit interleaver 2520A may apply the bit interleaving process discussed with reference to Figs. 32 through 34, or may apply a variant bit permutation process (excluding cases where $F = 1$). Also, the bit interleaver 2520A may apply an additional cyclic block permutation process (excluding cases where $F = 1$), such as the process discussed with reference to Figs. 35 and 36 or a variation thereof.

[0188]

The following describes a receiver receiving signals from a transmitter that includes the bit interleaver performing a bit interleaving process that satisfies Conditions 1A and 2A.

[0189]

Fig. 38 is a block diagram of an example receiver, including a non-iterative BICM decoder, pertaining to a further Embodiment of the disclosure. The receiver performs the transmitter operations in reverse. The receiver 2700A shown in Fig. 38 is configured similarly to the receiver 2700 of Fig. 27, differing in that the bit deinterleaver 2730 is replaced by a bit deinterleaver 2730A.

[0190]

The bit deinterleaver 2730A performs an interleaving process on the soft bit sequence output from the constellation demapper 2720 so as to cancel the bit interleaving process applied to the bit sequence by the bit interleaver 2520A in the transmitter 2500A.

[0191]

Fig. 39 is a block diagram of an example receiver, including a non-iterative BICM decoder, pertaining to a further Embodiment of the disclosure. The receiver performs the transmitter operations in reverse. The receiver 2800A shown in Fig. 39 is configured similarly to the receiver 2800 of Fig. 28, differing in that the bit deinterleaver 2730 and the bit interleaver 2750 are replaced by a bit deinterleaver 2730A and a bit deinterleaver 2750A.

[0192]

The bit interleaver 2750A performs an interleaving process on the extrinsic information using the same interleaving rules as the interleaving process applied to the bit sequence by the bit interleaver 2520A in the transmitter 2500A.

[0193]

From a hardware implementation perspective, folding is desirable in that, for example, the bits of a constellation are thereby located in fewer LLR memory locations.

Typically, the LLR memory in the decoder includes $G \times N$ addressable memory locations, each location being capable of storing Q/G LLR values. Here, G is an implementation parameter that is a divisor of Q and is hereinafter referred to as memory granularity. The LLR memory locations in the decoder and the LLR values of the first constellation are shown in Fig. 40, where $M = 4$, $F = 2$, $Q = 12$, and $G = 1-12$.

[0194]

The number of LLR values per memory location, i.e., the value of Q/G , is necessarily a multiple of F . The LLR values of each constellation are thus stored at the same position in all memory locations. This ensures that the LLR values of any constellation word are stored in M/F memory locations. A counter-example is given in Fig. 40 where $G = 4$, and $12/4 = 3$ LLR values are stores at each memory location. The LLR values of the second and fifth constellation words are each stored at four memory locations rather than at two memory locations.

[0195]

In addition to simple QAM constellations where folding with $F = 2$ is applicable, folding is even more useful when two or more constellation symbols are jointly decoded. Joint decoding is necessary, for instance, for the maximum-likelihood decoding of block codes (e.g., space-time codes, space-frequency codes, and the like), and for rotated constellations in two or more dimensions.

[0196]

In general, a block code encodes two or more input symbols (e.g., $x_1, \dots, x_K$) onto two or more output symbols (e.g., $y_1, \dots, y_L$). Here, L is at least equal to K . The block codes are modeled on an $L \times K$ generator matrix. Here, the output signal vector Y is obtained as a result of left-multiplying the input signal vector X by the generator matrix G (i.e., $Y = GX$).

[0197]

The elements of the input signal vector X and the output signal vector Y , as

well as the elements of the generator matrix G , may be real or complex. Depending on the type of code, the output signal vector Y may be transmitted in different time slots or in different frequency slots, may be transmitted over different antennas, or may be transmitted using a variety of different time slots, frequency slots, and antennas.

5 [0198]

In the receiver, maximum-likelihood decoding is required in order to decode all elements of the input signal vector X . Examples of block codes for multiple-input multiple-output (hereinafter, MIMO) systems include Alamouti codes, Golden codes, and spatial multiplexing.

10 [0199]

When K symbols are encoded in the same block, a folding factor of up to K is obviously useable. Further, provided that the symbols are QAM symbols (including two divisible PAM symbols), then the folding factor may be increased to $2K$.

[0200]

15 According to a further aspect of the present disclosure, when constellations of different sizes, i.e., hybrid constellations, are jointly encoded, the two constellations have different robustness levels. Thus, for example, the cyclic block to which the bits of one constellation word are mapped is distinct from the cyclic block to which the bits of the other constellation word are mapped.

20 [0201]

The following describes an example of a coded spatial-multiplexing MIMO system using two transmit antennas. The complex signal prior to coding is $X = [x_1 \ x_2]$. Here, x_1 is a signal to which QPSK has been applied, and x_2 is a signal to which 16-QAM has been applied. The complex signal after decoding is $Y = [y_1 \ y_2]$. Here, 25 y_1 and y_2 are signals respectively transmitted by a first antenna and a second antenna. Y is obtained through a left-multiplication of X with a 2×2 generator matrix G (where the elements of G may be either real or complex) (i.e., $Y = GX$).

[0202]

Fig. 41 illustrates an example of mapping with a folding factor of $F = 2$, when multiplexing QPSK symbols with 16-QAM symbols in a single block code. Fig. 41 indicates only the first seven bits of the cyclic blocks. The two complex symbols x_1 and x_2 are configured as follows.

5 [0203]

x_1 is a QPSK symbol having a real part b_1 and an imaginary part b_2 .

[0204]

x_2 is a 16-QAM symbol having real part b_3 and b_4 and having imaginary parts b_5 and b_6 .

10 [0205]

The two symbols are jointly decoded by the receiver and thus form a constellation block or generated block.

[0206]

The entire 6-bit constellation block has three robustness levels.

15 [0207]

Level 1: 1: QPSK bits b_1 and b_2 are mapped to QB1

[0208]

Level 2: 16-QAM bits b_3 and b_5 are mapped to QB2

[0209]

20 Level 3: 16-QAM bits b_4 and b_6 are mapped to QB3

[0210]

When one of the constellations has M_1 bits and the other constellation has M_2 bits, the N cyclic groups are divided into one or more groups of M_1 cyclic block and one or more groups of M_2 cyclic blocks in order to perform the bit interleaving process.

25

[0211]

(Embodiment 3)

The following describes an example of an interleaver performing folding in a

situation where N is not a multiple of M .

[0212]

Fig. 42 illustrates a cyclic block subject to and a cyclic block excluded from (i.e., an excluded block) the interleaving process where $F = 2$, described above. In Fig. 42, the code is 16K LDPC code conforming to the DVB-T2 standard, and the constellation is a 16-QAM constellation. As shown, 44 of the cyclic blocks are subject to interleaving (i.e., blocks 1 through 44), and cyclic block 45, in the last row, is the one cyclic block not subject to interleaving (i.e., the excluded block). The four blackened squares represent the four bits of the first constellation.

[0213]

Fig. 43 is a schematic block diagram of a bit interleaver performing folding when N is not a multiple of M . For simplicity, the following values hold: $N = 13$, $Q = 8$, $M = 4$, and $F = 2$.

[0214]

The number of folding sections is $\text{floor}(N/(M/F)) = 6$, and the number of excluded cyclic blocks is $\text{rem}(N, M/F) = 1$.

[0215]

The bit interleaver 2000B selects $13-1 = 12$ cyclic blocks from among cyclic blocks QB1–QB13, such that the selected cyclic blocks QB1–QB12 satisfy conditions A1 and A2 and are subject to interleaving. The bit permutator 2010A in the bit interleaver 2000B performs the permutation process described with reference to Fig. 32 on the twelve selected cyclic blocks. Although the bits of cyclic block QB13 are here mapped to a constellation word without interleaving, interleaving may also be applied prior to mapping to the constellation word.

[0216]

As an example of an interleaver not performing folding when N is not a multiple of M , the bit permutator 2010A shown in Fig. 43 may be replaced by the permutator 2010 shown in Fig. 20.

[0217]

(Supplement 1)

The present disclosure is not limited to the Embodiments described above. Provided that the aims of the invention and accompanying aims are achieved, other variations are also possible, such as the following.

[0218]

(1) Embodiment 1 is described above using the parameters $N = 12$, $Q = 8$, and $M = 4$. However, no limitation to the parameters N , M , and Q is intended. Here, N may be any multiple of M . When N is two or more times M , the processing by the bit interleaver is divisible into a plurality of sections.

[0219]

(2) In Embodiment 2, when folding is used, i.e., when F is two or greater, the parameters given for the example are $N = 12$, $Q = 8$, $M = 4$, and a folding factor of $F = 2$. However, no limitation to the parameters N , M , Q , and F is intended. Here, F is a divisor of M and Q , and N is a multiple of M/F .

[0220]

(3) In Embodiment 2, when folding is used, the value of F is given as two, which is the number of bits having the same robustness level in a single 16-QAM constellation. However, no limitation is intended. The value of F need not be equal to the number of bits having the same robustness level in a constellation, and may indeed be other than the number of bits having the same robustness level in a constellation.

[0221]

(4) In Embodiment 2, when folding is used, the example describes a folding factor of $F = 2$, and QAM constellations being 16-QAM constellations. However, no limitation is intended. When $F = 2$, the QAM constellations may be other than 16-QAM constellations (e.g., 64-QAM constellations or 256-QAM constellations).

[0222]

(5) In the above-described Embodiments, the constellations are described as 16-QAM (i.e., $M = 4$). However, the constellations may be specified by other modulation methods such as QPSK and QAM, such as the circular constellations employed in the DVB-S2 standard, higher-dimensional constellations, and so on.

5 [0223]

(6) The methods and devices discussed in the above Embodiments may be implemented as software or as hardware. No particular limitation is intended in this regard. Specifically, the above-described Embodiments may be implemented as a computer-readable medium having embodied thereon computer-executable instructions that are adapted for allowing a computer, a microprocessor, a microcontroller, and the like to execute the above-described methods. Also, the above-described Embodiments may be implemented as an Application-Specific Integrated Circuit (ASIC) or as an Field Programmable Gate Array (FPGA).

[0224]

15 (Supplement 2)

The bit interleaving method, bit interleaver, bit deinterleaving method, bit deinterleaver, and decoder of the present disclosure, and the effects thereof, are described below.

[0225]

20 In a first aspect of a bit interleaving method, a bit interleaving method for a communication system using quasi-cyclic low-density parity check codes comprises: a reception step of receiving a codeword of the quasi-cyclic low-density parity check codes made up of N cyclic blocks each including Q bits; a bit permutation step of applying a bit permutation process to the codeword so as to permute the bits in the
25 codeword; and a division step of dividing the codeword, after the bit permutation process, into a plurality of constellation words, each of the constellation words being made up of M bits and indicating one of 2^M constellation points in a predetermined constellation, wherein prior to the bit permutation process, the codeword is divided into

$F \times N/M$ folding sections, F being an integer greater than one, each of the folding sections including M/F of the cyclic blocks, and each of the constellation words being associated with one of the $F \times N/M$ folding sections, and in the bit permutation step, the bit permutation process is applied such that the M bits in each of the constellation words include F bits from each of M/F different cyclic blocks in a given folding section associated with a given constellation word, and such that all bits in the given folding section are mapped to only Q/F of the constellation words associated with the given folding section.

[0226]

In another aspect, a first bit interleaver for a communication system using quasi-cyclic low-density parity check codes comprises: a bit permutation unit receiving a codeword of the quasi-cyclic low-density parity check codes made up of N cyclic blocks each including Q bits, applying a bit permutation process to the codeword so as to permute the bits in the codeword, and dividing the codeword, for output after the bit permutation process, into a plurality of constellation words, each of the constellation words being made up of M bits and indicating one of 2^M constellation points in a predetermined constellation, wherein prior to the bit permutation process, the codeword is divided into $F \times N/M$ folding sections, F being an integer greater than one, each of the folding sections including M/F of the cyclic blocks, and each of the constellation words being associated with one of the $F \times N/M$ folding sections, and the bit permutation unit applies the bit permutation process such that the M bits in each of the constellation words include F bits from each of M/F different cyclic blocks in a given folding section associated with a given constellation word, and such that all bits in the given folding section are mapped to only Q/F of the constellation words associated with the given folding section.

[0227]

Accordingly, reductions in circuit surface area and in electric power consumption are achieved, in addition to enabling the realization of a bit interleaving

process having high parallelism.

[0228]

In a second aspect of the bit interleaving method, the bit permutation step includes a folding section permutation step of independently applying a folding section permutation process to each of the $F \times N/M$ folding sections so as to permute the bits in each of the folding sections.

[0229]

Also, in a second aspect of a bit interleaver, the bit permutation unit includes a folding section permutation unit independently applying a folding section permutation process to each of the $F \times N/M$ folding sections so as to permute the bits in each of the folding sections.

[0230]

Accordingly, a plurality of folding section permutation processes are executable in parallel.

[0231]

In a third aspect of the bit interleaving method, in the folding section permutation step, the folding section permutation process is performed such that the Q bits in a given cyclic block are each mapped to a bit of an identical robustness level in the Q/F constellation words associated with one of the folding sections that corresponds to the given cyclic block.

[0232]

Also, in a third aspect of a bit interleaver, the folding section permutation unit applies the folding section permutation process such that the Q bits in a given cyclic block are each mapped to a bit of an identical robustness level in the Q/F constellation words associated with one of the folding sections that corresponds to the given cyclic block.

[0233]

Accordingly, bits of the codeword having the same importance are mapped to

bits of the constellation word having the same robustness level, allowing a matching of importance and robustness level. For example, the bit of the codeword having the highest importance may be mapped to a bit of the constellation word having the highest robustness level. In such a case, high reliability is achieved at reception time for the bit of the codeword having the highest importance, resulting in greater reception capability.

[0234]

In a fourth aspect of the bit interleaving method, F is equal to a number of bits of an identical robustness level in one of the constellation words .

[0235]

Also, in a fourth aspect of a bit interleaver, F is equal to a number of bits of an identical robustness level in one of the constellation words.

[0236]

Accordingly, an effective hardware implementation is realized.

[0237]

In a fifth aspect of the bit interleaving method, $F = 2$, and the constellation words are QAM constellations.

[0238]

Also, in a fifth aspect of a bit interleaver, $F = 2$, and the constellation words are QAM constellations.

[0239]

Accordingly, an effective hardware implementation is realized.

[0240]

In a sixth aspect of the bit interleaving method, the folding section permutation step includes a column-row permutation step of applying a column-row permutation process to the $M/F \times Q$ bits in each of the folding sections so as permute the $M/F \times Q$ bits.

[0241]

In a seventh aspect of the bit interleaving method, the column-row permutation process is equivalent to writing the $M/F \times Q$ bits row-wise into a matrix having Q columns and M/F rows, then reading the $M/F \times Q$ bits column-wise.

[0242]

Also, in a sixth aspect of a bit interleaver, the folding section permutation unit applies a column-row permutation process to the $M/F \times Q$ bits in each of the folding sections so as to permute the $M/F \times Q$ bits.

[0243]

Accordingly, a column-row permutation is used in the folding section permutation process, thus enabling the realization of an extremely efficient folding section permutation process.

[0244]

In a further aspect, a bit deinterleaving method for deinterleaving a bit stream in a communication system using quasi-cyclic low-density parity check codes comprises: a reception step of receiving a bit sequence made up of $N \times Q$ bits; and a reverse bit permutation step of applying a reverse bit permutation process to the received bit sequence so as to permute the bits in the bit sequence in order to restore the codeword of the quasi-cyclic low-density parity check codes, wherein the reverse bit permutation process reverses the bit permutation process in the bit interleaving method of the first aspect.

[0245]

In an alternate aspect, a bit deinterleaver for deinterleaving a bit stream in a communication system using quasi-cyclic low-density parity check codes comprises: a reverse bit permutation unit receiving a bit sequence made up of $N \times Q$ bits, and applying a reverse bit permutation process to the received bit sequence so as to permute the bits in the bit sequence in order to restore a codeword of the quasi-cyclic low-density parity check codes, wherein the reverse bit permutation process reverses the bit permutation process applied by the bit interleaver of the first aspect.

[0246]

In another aspect, a decoder for a bit interleaving and demodulating system using quasi-cyclic low-density parity check codes, comprising: a constellation demapper generating a soft bit sequence indicating a probability of a corresponding bit being one of a zero-bit and a one-bit; the bit deinterleaver of the alternate aspect deinterleaving the soft bit sequence; and a low-density parity check decoder decoding the deinterleaved soft bit sequence.

[0247]

In yet another aspect, the decoder of the other aspect further comprises: a subtraction unit subtracting input to the low-density parity check decoder from output of the low-density parity check decoder; and the bit interleaver of the first aspect, providing the difference from the subtraction unit to the constellation demapper as feedback.

[0248]

Accordingly, a bit interleaving process having high parallelism is realizable.

[Industrial Applicability]

[0249]

The present invention is applicable to a bit interleaver in a bit-interleaved coding and modulation system used for quasi-cyclic low-density parity codes, and to a bit deinterleaver corresponding to such a bit interleaver.

[Reference Signs List]

[0250]

2000A	Bit interleaver
2010A	Bit permutator
2021A	Folding section permutator
2131A, 2132A	Column-row permutator
2500A	Transmitter
2510	LDPC encoder

2520A	Bit interleaver
2530	Constellation mapper
2700A, 2800A	Receiver
2710	Constellation demapper
5 2720A	Bit deinterleaver
2730	LDPC decoder
2740	Subtractor
2750A	Bit interleaver

10 [0251]

Modifications within the scope of the invention may be readily effected by those skilled in the art. It is to be understood, therefore, that this invention is not limited to the particular embodiments described by way of example hereinabove.

[0252]

15 In the claims that follow and in the preceding description of the invention, except where the context requires otherwise owing to express language or necessary implication, the word “comprise” or variations such as “comprises” or “comprising” is used in an inclusive sense, that is, to specify the presence of the stated features but not to preclude the presence or addition of further features in various embodiments of the
20 invention.

[0253]

Further, any reference herein to prior art is not intended to imply that such prior art forms or formed a part of the common general knowledge in any country.

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. A bit interleaving method for interleaving bits of a codeword generated based on a quasi-cyclic low-density parity check coding scheme, including a repeat-accumulate quasi-cyclic low-density parity check coding scheme, the bit interleaving method comprising:

a cyclic block permutation step of applying a cyclic block permutation process to a codeword made up of N cyclic blocks each consisting of Q bits, to reorder the cyclic blocks in accordance with a cyclic block permutation rule defining a reordering of the cyclic blocks;

a bit permutation step of applying a bit permutation process to the codeword after the cyclic block permutation process, to reorder the bits of the codeword in accordance with a bit permutation rule defining a reordering of the bits; and

a dividing step of dividing the codeword after the bit permutation process into a plurality of constellation words, each of the constellation words being made up of M bits, wherein

N is not a multiple of M ,

the bit permutation rule defines the reordering of the bits of the codeword after the cyclic block permutation process, such that the Q bits in each of $N' = N - X$ cyclic blocks of the N cyclic blocks are each allocated to a bit of an identical bit index in Q constellation words and the Q constellation words are each made up of one bit in each of M cyclic blocks, the M cyclic blocks being common to the Q constellation words, where X is a remainder of N divided by M , and

the bit index of the bit in each of the Q constellation words to which the bits in each of the $N' = N - X$ cyclic blocks are each allocated is determined in accordance with the cyclic block permutation rule.

2. A bit interleaver for interleaving bits of a codeword generated based on a quasi-cyclic low-density parity check coding scheme, including repeat-accumulate

quasi-cyclic low-density parity check coding scheme, the bit interleaver comprising:

a cyclic block permutator applying a cyclic block permutation process to a codeword made up of N cyclic blocks each consisting of Q bits, to reorder the cyclic blocks in accordance with a cyclic block permutation rule defining a reordering of the cyclic blocks;

a bit permutator applying a bit permutation process to the codeword after the cyclic block permutation process, to reorder the bits of the codeword in accordance with a bit permutation rule defining a reordering of the bits; and

a divider dividing the codeword after the bit permutation process into a plurality of constellation words, each of the constellation words being made up of M bits, wherein

N is not a multiple of M ,

the bit permutation rule defines the reordering of the bits of the codeword after the cyclic block permutation process, such that the Q bits in each of $N' = N - X$ cyclic blocks of the N cyclic blocks are each allocated to a bit of an identical bit index in Q constellation words and the Q constellation words are each made up of one bit in each of M cyclic blocks, the M cyclic blocks being common to the Q constellation words, where X is a remainder of N divided by M , and

the bit index of the bit in each of the Q constellation words to which the bits in each of the $N' = N - X$ cyclic blocks are each allocated is determined in accordance with the cyclic block permutation rule.

3. A signal processing method for processing a signal transmitted by modulating $N \times Q/M$ constellation words, the constellation words being generated by applying a bit reordering process to a codeword generated based on a quasi-cyclic low-density parity check coding scheme, including a repeat-accumulate quasi-cyclic low-density parity check coding scheme, and dividing bits of the codeword for each M bits, the codeword being made up of N cyclic blocks each including Q bits,

the bit reordering process comprising:

a cyclic block permutation process of reordering the cyclic blocks of the codeword in accordance with a cyclic block permutation rule defining a reordering of the cyclic blocks; and

a bit permutation process of reordering the bits of the codeword after the cyclic block permutation process in accordance with a bit permutation rule defining a reordering of the bits, wherein

N is not a multiple of M ,

the bit permutation rule defines the reordering of the bits of the codeword after the cyclic block permutation process, such that the Q bits in each of $N' = N - X$ cyclic blocks of the N cyclic blocks are each allocated to a bit of an identical bit index in Q constellation words and the Q constellation words are each made up of one bit in each of M cyclic blocks, the M cyclic blocks being common to the Q constellation words, where X is a remainder of N divided by M , and

the bit index of the bit in each of the Q constellation words to which the bits in each of the $N' = N - X$ cyclic blocks are each allocated is determined in accordance with the cyclic block permutation rule,

the signal processing method comprising:

a demodulating step of generating a demodulated signal by demodulating the signal, which has been transmitted by modulating the $N \times Q/M$ constellation words; and

a decoding step of decoding the demodulated signal in accordance with the cyclic block permutation rule and the bit permutation rule to generate data before coding according to the quasi-cyclic low-density parity check coding scheme.

4. A signal processor for processing a signal transmitted by modulating $N \times Q/M$ constellation words, the constellation words being generated by applying a bit reordering process to a codeword generated based on a quasi-cyclic low-density parity check coding scheme, including a repeat-accumulate quasi-cyclic low-density parity check coding scheme, and dividing bits of the codeword for each M bits, the

codeword being made up of N cyclic blocks each including Q bits,

the bit reordering process comprising:

a cyclic block permutation process of reordering the cyclic blocks of the codeword in accordance with a cyclic block permutation rule defining a reordering of the cyclic blocks; and

a bit permutation process of reordering the bits of the codeword after the cyclic block permutation process in accordance with a bit permutation rule defining a reordering of the bits, wherein

N is not a multiple of M ,

the bit permutation rule defines the reordering of the bits of the codeword after the cyclic block permutation process, such that the Q bits in each of $N' = N - X$ cyclic blocks of the N cyclic blocks are each allocated to a bit of an identical bit index in Q constellation words and the Q constellation words are each made up of one bit in each of M cyclic blocks, the M cyclic blocks being common to the Q constellation words, where X is a remainder of N divided by M , and

the bit index of the bit in each of the Q constellation words to which the bits in each of the $N' = N - X$ cyclic blocks are each allocated is determined in accordance with the cyclic block permutation rule,

the signal processor comprising:

a demodulator generating a demodulated signal by demodulating the signal, which has been transmitted by modulating the $N \times Q / M$ constellation words; and

a decoder decoding the demodulated signal in accordance with the cyclic block permutation rule and the bit permutation rule to generate data before coding according to the quasi-cyclic low-density parity check coding scheme.

5. A computer program configured to control a computer to perform a method according to either claim 1 or 3.

6. A computer readable medium comprising a computer program as claimed in claim 5.

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8A




FIG. 8B




FIG. 9A




FIG. 9B




FIG. 10A




FIG. 10B




FIG. 11




FIG. 12




FIG. 13




Figure 1 is a grid diagram illustrating the distribution of cyclic blocks across eight columns. The grid is 45 rows high and 8 columns wide. The columns are labeled "Column 1" through "Column 8". The rows are labeled "Cyclic blocks (1, ..., 45)" on the left and "Bits in cyclic block (1, ..., 72)" on the right. The grid contains black squares representing the distribution of cyclic blocks across columns. The squares are located at the following (Column, Row) coordinates: (1, 1), (2, 10), (3, 20), (4, 30), (5, 40), (6, 50), (7, 60), (8, 70).

FIG. 15





FIG. 16



Bits in cyclic block (1, ..., 72)

FIG. 18A




FIG. 18B




FIG. 19




FIG. 20

2000




FIG. 21A




FIG. 21B




FIG. 23




FIG. 24





FIG. 25






FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31A




FIG. 31B




FIG. 32




FIG. 33A

Without folding	QB1	b1 c1	b1 c2	b1 c3	b1 c4	b1 c5	b1 c6	b1 c7	b1 c8	Folding section 1 (Section 1)
	QB2	b2 c1	b2 c2	b2 c3	b2 c4	b2 c5	b2 c6	b2 c7	b2 c8	
	QB3	b3 c1	b3 c2	b3 c3	b3 c4	b3 c5	b3 c6	b3 c7	b3 c8	
	QB4	b4 c1	b4 c2	b4 c3	b4 c4	b4 c5	b4 c6	b4 c7	b4 c8	

FIG. 33B

With folding (F = 2)	QB1	b1 c1	b3 c1	b1 c2	b3 c2	b1 c3	b3 c3	b1 c4	b3 c4	Folding section 1
	QB2	b2 c1	b4 c1	b2 c2	b4 c2	b2 c3	b4 c3	b2 c4	b4 c4	
	QB3	b1 c5	b3 c5	b1 c6	b3 c6	b1 c7	b3 c7	b1 c8	b3 c8	Folding section 2
	QB4	b2 c5	b4 c5	b2 c6	b4 c6	b2 c7	b4 c7	b2 c8	b4 c8	

FIG. 34A




FIG. 34B




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43

2000B

