



- (51) **International Patent Classification:**
G02B 27/01 (2006.01) *G02B 27/00* (2006.01)
- (21) **International Application Number:**
PCT/FI2016/050072
- (22) **International Filing Date:**
5 February 2016 (05.02.2016)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
15156666.8 26 February 2015 (26.02.2015) EP
- (71) **Applicant:** NOKIA TECHNOLOGIES OY [FI/FI];
Karaportti 3, 02610 Espoo (FI).
- (72) **Inventor:** JÄRVENPÄÄ, Toni; Haapalantie 19, 37800
Akaa (FI).
- (74) **Agents:** NOKIA TECHNOLOGIES OY et al.; Ari
Aarnio, IPR Department, Karakaari 7, 02610 Espoo (FI).
- (81) **Designated States** (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG,
MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM,
PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC,
SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) **Designated States** (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ,
TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU,
TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,
DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))


(54) **Title:** APPARATUS FOR A NEAR-EYE DISPLAY

FIG. 1

(57) **Abstract:** Certain examples of the present disclosure relate to an apparatus for providing gaze tracking in a near-eye display. Certain examples provide an apparatus comprising: a light modulator configured to receive light of a first range of wavelengths and generate an image beam therefrom. The light modulator is further configured to receive light of a second range of wavelengths and generate a probe beam therefrom. The apparatus also comprises one or more light guides comprising: one or more in-coupling diffractive element areas, and one or more out-coupling diffractive element areas. The one or more in-coupling diffractive element areas are configured to receive and in-couple the image beam and the probe beam into the one or more light guides. The one or more out-coupling diffractive element areas are configured to out-couple, from the one or more light guides: the image beam to a user's eye for user viewing, and the probe beam to the user's eye for detection of reflection therefrom.

APPARATUS FOR A NEAR-EYE DISPLAY

TECHNOLOGICAL FIELD

Examples of the present disclosure relate to an apparatus for a near-eye display. Some examples, though without prejudice to the foregoing, relate to an apparatus for providing gaze tracking in a near-eye display.

BACKGROUND

Gaze tracking, namely the process of determining a point of gaze of a user's eye so as to determine a line of sight associated with the user's eye or to determine where the user is looking (and thus determining what the user is looking at), typically relies on capturing video images from a user's eye(s). Such video based gaze tracking typically uses infrared (IR) LEDs or infrared lasers for illuminating the eye and detecting reflections/glints of the infrared light from the eye (e.g. its cornea/surface). A determination of a user's gaze may be calculated based on the detected IR reflections and detected eye features such as detected pupil position. Conventional near-eye displays with integrated gaze tracking functionality systems are not always optimal, not least for example in view of the additional components as well as increased complexity, size and weight necessary to incorporate both gaze tracking functionality as well as display functionality in a near-eye display.

The listing or discussion of any prior-published document or any background in this specification should not necessarily be taken as an acknowledgement that the document or background is part of the state of the art or is common general knowledge. One or more aspects/examples of the present disclosure may or may not address one or more of the background issues.

BRIEF SUMMARY

30

An aspect of the present invention is set out in the claims.

According to at least some but not necessarily all examples of the disclosure there is provided an apparatus comprising:

- 5 a light modulator configured to receive light of a first range of wavelengths and generate an image beam therefrom, wherein the light modulator is further configured to receive light of a second range of wavelengths and generate a probe beam therefrom;
- one or more light guides comprising:
- 10 one or more in-coupling diffractive element areas, and
one or more out-coupling diffractive element areas;
- wherein the one or more in-coupling diffractive element areas are configured to receive and in-couple the image beam and the probe beam into the one or more light guides; and
- 15 wherein the one or more out-coupling diffractive element areas are configured to out-couple, from the one or more light guides:
- the image beam to a user's eye for user viewing, and
the probe beam to the user's eye for detection of reflection therefrom.

- 20 According to at least some but not necessarily all examples of the disclosure there is provided an apparatus comprising:
- means configured to receive light of a first range of wavelengths and generate an image beam therefrom, wherein the means is further configured to receive light of a second range of wavelengths and
- 25 generate a probe beam therefrom;
- one or more means for guiding light comprising:
- one or more in-coupling diffractive means, and
one or more out-coupling diffractive means;
- wherein the one or more in-coupling diffractive means are
- 30 configured to receive and in-couple the image beam and the probe beam into the one or more means for guiding light; and

wherein the one or more out-coupling diffractive means are configured to out-couple, from the one or more means for guiding light:

- 5 the image beam to a user's eye for user viewing, and
 the probe beam to the user's eye for detection of reflection therefrom.

According to at least some but not necessarily all examples of the disclosure there is provided an apparatus comprising:

- 10 means configured to generate an image beam of light at a first range of wavelengths, wherein the means is further configured to generate a probe beam of light of a second range of wavelengths;
 one or more means for guiding light comprising:
 one or more in-coupling diffractive means, and
15 one or more out-coupling diffractive means;
 wherein the one or more in-coupling diffractive means are configured to receive and in-couple the image beam and the probe beam into the one or more means for guiding light; and
 wherein the one or more out-coupling diffractive means are
20 configured to out-couple, from the one or more means for guiding light:
 the image beam to a user's eye for user viewing, and
 the probe beam to the user's eye for detection of reflection therefrom.

- 25 Certain examples of the apparatus may be provided as a module for a device or as a device itself. The device may be configured for at least one of: portable use, wearable use, head mountable use. Certain examples of the apparatus are configured for use with a Near Eye Display (NED) for
30 providing both display and gaze tracking functionality.

The examples of the present disclosure and the accompanying claims may be suitably combined in any manner apparent to one of ordinary skill in the art.

5 BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding of various examples of the present disclosure that are useful for understanding the detailed description and certain embodiments of the invention, reference will now be made by way of example only to the accompanying drawings in which:

10 Figure 1 schematically illustrates an example of an apparatus according to the present disclosure;

Figure 2 schematically illustrates a further example of an apparatus according to the present disclosure;

15 Figure 3 schematically illustrates an example of diffractive light guides suitable for use with examples of the present disclosure;

Figure 4 schematically illustrates a yet further example of an apparatus according to the present disclosure; and

Figures 5A and 5B schematically illustrate examples of light modulators suitable for use with examples of the present disclosure.

20

DETAILED DESCRIPTION

Examples of apparatuses according to the present disclosure will now be described with reference to the Figures. Similar reference numerals are used in the Figures to designate similar features. For clarity, all reference numerals
25 are not necessarily displayed in all figures.

Figure 1 schematically illustrates a block diagram of an apparatus 100 according to an example of the present disclosure. Figure 1 focuses on the functional components necessary for describing the operation of the
30 apparatus.

The apparatus 100 comprises a light modulator 101 configured to receive light of a first range of wavelengths 102, and generate an image beam 103 therefrom. The light modulator 101 is further configured so as to receive light of a second range of wavelengths 104 and generate a probe beam 105
5 therefrom.

The apparatus 100 further comprises one or more light guides 106 comprising one or more in-coupling diffractive element areas 107, and one or more out-coupling diffractive element areas 108. The one or more in-coupling
10 diffractive element areas 107 are configured to receive and in-couple the image beam 103 and the probe beam 105 into the one or more light guides 106. The one or more out-coupling diffractive element areas 108 are configured to out-couple, from the one or more light guides 106:

the image beam 109 to a user's eye 110 for user viewing, and
15 the probe beam 111 to the user's eye 110 for detection of reflection therefrom.

Each of the components described above may be one or more of any element, device, mechanism or means configured to perform the
20 corresponding functions of the respective components as described in greater detail below. The component blocks of Figure 1 are functional and the functions described may or may not be performed by a single physical entity for example the light modulator 101 may correspond to an assembly/arrangement of components, not least for example as shown in
25 Figures 5A or Figure 5B. Accordingly, the blocks support: combinations of means for performing the specified functions.

The light modulator 101 may comprise a light modulating/modifying means configured to modulate/modify the incident light 102, 104 of first and
30 second ranges of wavelengths so as to impart an image or pattern thereon and generate one or more collimated beams 103, 105 comprising a variable

image or pattern. The light modulator 101 may comprise one or more of: an optical engine, a light engine, a micro display, optics (e.g. enlarging optics and collimating optics), a projector, a digital light processing (DLP) system, a liquid crystal on silicon (LCoS), a retinal scan display, a laser scanning system, a microelectromechanical (MEM) system (e.g. for providing scanning/raster scanning). The light modulator 101, in certain examples, may be: a reflective based display, a transmissive based display or an emissive based display.

10 In some examples, instead of receiving light of a first and a second range of wavelengths and generating an image beam and probe beam therefrom, the light modulator may be configured to be able to generate for itself an image beam of light of a first range of wavelengths and a probe beam of light of a second range of wavelengths. For example the light modulator
15 may comprise one or more display elements which itself creates a pixelated image / probe pattern that is then projected through an optical setup, e.g. an OLED display or an LED array display, for in-coupling to the one or more light guides.

20 The image beam 103 may comprise a collimated beam of light that may be expanded and guided to user's eye 110 for viewing and perceiving the image which is imparted to the light 102 that forms the image beam 103 by the light modulator 101. Where the light 102 of the first range of wavelengths comprises one or more colour channels of visible light, e.g. one or more of
25 red (R), green (G) and blue (B), the image beam 103 may correspondingly comprise light within the visible range of the electromagnetic spectrum, e.g. one or more of R, G and B. In certain examples, one or more image beams may be generated corresponding to the image in differing colour channels, e.g. one or more of R, G and B, from light received in the respective colour
30 channels.

The probe beam 105 may comprise a collimated beam of light that may be expanded and guided to user's eye 110 for reflection therefrom. In certain examples (see Figure 2), such reflection is detected and used in part to determine a gaze or direction of view of the eye 110. The light modulator
5 101 may impart a variable pattern, image, shape or size to light 104 that forms the probe beam 105. Where the light of the second range of wavelengths comprises infrared light the probe beam may correspondingly comprise light within the infrared part of the electromagnetic spectrum.

10 The one or more light guides 106 may comprise light guiding means comprising one or more means for diffracting beams into and out of the light guide, for example a diffractive optical element. The light guides may, for example, be a one or more substantially planar substrates comprising one or more areas or diffractive elements / gratings / grooves that are disposed on
15 lower or upper surfaces of the substrate or even located internally of the substrate. The light guide may be an exit pupil expander configured to expand an incident beam of light 103, 105 in one or more directions. The light guides may be transparent and the apparatus may be configured such that the user can see the real world through the apparatus/light guides whilst
20 also seeing a virtual image/world via the apparatus/light guides.

Certain examples of the apparatus: may reduce the complexity of a combined display and gaze tracking device, may provide improved integration and require fewer components, and may thus also reduce the
25 weight and size of the apparatus by enabling the sharing/reutilisation of various components. This may enable the provision of a miniaturised and efficient apparatus for integrated NED and Gaze tracking. For example, the light modulator 101 which generates the image beam 103 is also used to generate the probe beam 105. In other examples, a light source for emitting
30 the light for the image beam 103 is also used to generate the light for the probe beam 105.

The use of the light modulator 101 to generate the probe beam 105 may enable a pattern, shape or size of the probe beam to be dynamically varied. Such control of the probe beam may enable the creation of complex variable shapes, sizes, patterns/images of the probe beam. Moreover, the probe beam could be dynamically adjusted during use so as to achieve optimal detection and measurement results thereby enabling more robust gaze tracking as well as simpler gaze tracking calibration.

Furthermore, certain examples (e.g. figure 1) provide the ability to share/utilise one or more of in-coupling diffractive elements 107 and/or one or more of the out-coupling diffractive elements 108 to in-couple and/or out-couple both the image beam 103 and the probe beam 105 and may thereby reduce the number of optical components and the complexity of the arrangements of such components that may otherwise have been required to direct each of the image beam and probe beam separately and independently.

Furthermore, certain examples (see e.g. Figure 5A) may enable the use of a combined light source 512 which simultaneously generates both the light 102 for the image beam 103 as well as light 104 for the probe beam 105 and may thereby reduce the number of components (and thus the weight, size and complexity) of the apparatus.

In the example of Figure 1, the light guide 106 comprises a substrate of an optical material having first and second opposing surfaces. The substrate comprises an area of in-coupling diffractive elements 107 and an area of out-coupling diffractive elements 108 which may be laterally spaced apart from one another on the planar substrate for example at either end of the substrate. The in-coupling diffractive element area is configured to receive one or more input optical beams, i.e. either the image beam 103 ("image

display beam") or the probe beam 105 ("gaze tracking probe beam"), and diffract the input optical beam substantially within the first and second surfaces to provide a diffracted optical beam within the substrate which is coupled via total internal reflection to the out-coupling diffractive element area 108. The out-coupling diffractive element area is configured to further diffract the diffracted optical beam out of the substrate to provide an output optical beam, namely an output of the image display beam 109 or the output gaze tracking probe beam 111.

- 10 The out-coupling diffractive element 108 may be configured so as to not only just output the diffracted optical beam from the substrate but also to expand the diffracted optical beam in one direction. Further diffractive elements may be provided (for example 316a as shown in Figure 3) for expanding the diffracted optical beam in another direction so as to provide an output beam 109, 111 that can be expanded beam in two directions.

In certain examples, the in-coupling and out-coupling elements may be based on other optical methods than diffraction gratings and groves, for example volume holograms or gratings, or semi-transparent mirror structures.

20

- The apparatus of Figure 1 shows a schematic illustration of a monocular apparatus. However, it is to be appreciated that the apparatus could be configured in a binocular form. Such a binocular form could correspond to providing two apparatuses 100 one for each of the user's eyes. For example, providing apparatus 100 shown in Figure 1 for a user's right eye and a mirror image version of the apparatus 100 for the user's left eye (similar to that of Figure 2). As an alternative to using two such laterally adjacent light guides, a single light guide could be provided having an in-coupling diffractive element area between two out-coupling diffractive element areas located at either end of the light guide wherein the in-coupling diffractive element area is configured to provide two diffracted input optical beams, one

coupled to one of the out-coupling diffractive element areas, for example at a left hand end of the light guide, and the other diffracted input optical beam coupled to the other of the out-coupling diffractive element areas at the other end, e.g. a right hand end of the light guide.

5

Figure 1 shows a single diffractive light guide 106 provided with one in-coupling diffractive element area 107 which is configured to diffract light at the first range of wavelengths (e.g. in the visible part of the electromagnetic spectrum) as well as light at the second range of wavelengths (e.g. the IR part of the electromagnetic spectrum). Thus, the diffractive element area 107 may be configured to in-couple both the image display beam as well as the gaze tracking probe beam, i.e. the diffractive element may be configured so as to diffract (or at least have an acceptable efficiency for diffracting) each of infrared, red, green and blue colour channels regions of the electromagnetic spectrum or to diffract a portion of a colour channel. It should be appreciated that other colour channels / apportionment of the visible spectrum may also be envisaged. Likewise, the single out-coupling diffractive element 108 may be similarly configured to diffract and out-couple a corresponding wide range of wavelengths.

10

15

20

As an alternative to using a single in-coupling diffractive element area for in-coupling a wide range of wavelengths of input beams 103, 105, a plurality of in-coupling diffractive element areas could be provided on a light guide, each area spatially distinct from another and each being configured and optimised to diffract a particular/narrower range of wavelengths, for example one or more colour channels, infrared, red, green or blue, to provide one or more diffractive optical beams of such wavelengths of light within the substrate for out-coupling from the substrate by one or more out-coupling diffractive element areas.

25

30

Likewise, a plurality of out-coupling diffractive elements could be provided on the light guide each configured and optimised to diffract a particular narrow range of wavelengths of light and out-couple them from the light guide.

5

Yet further alternatively, instead of having a single light guide (with one or more in-coupling diffractive element areas and one or more out-coupling diffractive element areas) a plurality of light guides may be provided, e.g. vertically aligned and stacked on top of each other. Each of the stacked

10

light guides could be provided with one or more in/out-coupling diffractive element areas configured and optimised to in-couple and out-couple one or more particular colour channels. Thus, it is to be appreciated that a variety of possible combinations of: numbers of in- and out-coupling diffractive element areas per light guide, as well as number of stacked light

15

guides are envisaged.

Figure 2 shows an apparatus 200 in a binocular form comprising a right hand side set of stacked light guides 106a and 106a' along with a left hand side set of stacked light guides 106b and 106b'. For the sake of simplicity, the below discussion focuses just on the right hand side components of the apparatus. It is to be appreciated that similar components may be provided on the left hand side of the apparatus (with equivalent reference numerals but designated with a "b" instead of "a").

20

Of the two stacked light guides 106a and 106a', one is configured and optimised to in-couple, expand and out-couple visible light for example in the green and blue parts of the spectrum, whereas the other light guide is configured and optimised to in-couple, expand and out-couple infrared light and red light.

25

30

It is to be appreciated that other permutations may readily be envisaged, not least for example a plurality of stacked light guides each optimised for one of: blue, green, red and infrared respectively, or, similarly to Figure 1, a single light guide may be provided for in- and out-coupling all of IR, R, G and B wavelengths of light beams. Also, one light guide optimised for RGB could be provided with another optimised for IR. Such an IR optimised light guide could be made to be thinner than an RGB light guide. It could further be configured for other integrated uses, such as: being used as a protective element, or a capacitive measurement surface for face/eye movement detection as well as an LC shutter and hot mirror as discussed in further details below.

A single light source 212a emits light 102, 104 for both the image display beam 103 (i.e. visible light) as well as light for the gaze tracking probe beam 105, (i.e. infrared light). Such a light source generating simultaneously both visible light and infrared light may correspond to a laser crystal on silicone based light source as discussed further with respect to Figure 5A. Alternatively, instead of having a light source that generates simultaneously both the visible and infrared light, separate light sources may be provided which generate independently visible light and infrared, for example separate light sources configured to emit each of visible light and infrared light, not least for example separate red, green, blue and infrared LEDs positioned adjacent to one another which can be separately and independently controlled/switched on such that only visible light is emitted and received by the light modulator when generating the display imaging and likewise only infrared light is emitted and received at the light modulator when generating the gaze tracking probe beam.

The light source 212a generates the light of the first range of wavelengths 102 and also generates the light of the second range of wavelengths 104, each of which are incident to a light modulator 201a which generates an

image display beam 103 and a gaze tracking probe beam 105 from such incident light respectively. Additional optics, e.g. lenses, mirrors or MEM system may be provided as well as other mechanisms for focusing, collimating the source of light into beams of light that may further be
5 scanned / rastered into the in-coupling diffractive element.

The image display beam from the light modulator 201a is incident to a first in-coupling diffractive element area 107a and in-coupled into the first light guide 106a and then out-coupled via out-coupling diffractive element 108a
10 (propagating through the underlying light guide 106a') so as to be directed towards a user's eye 110. The first light guide may be configured and optimised so as to in-couple, expand and out-couple light of the image display beam in green and blue parts of the visible spectrum. The further light guide 106a' may be provided with an in-coupling diffractive element
15 area 107a' and an out-coupling diffractive element area 108a' configured and optimised to in-couple, expand and diffract out visible light of the image display beam in the red part of the spectrum. The second light guide 106a' may further be configured to in-couple, expand and out-couple infrared light to provide an output gaze tracking probe beam 111 which is incident
20 to the user's eye to be reflected therefrom.

A detector 213, such as an IR detector/sensor or camera, may be provided to detect reflections 214 of the gaze tracking probe beam from the user's eye, i.e. images/video of the user's eye in IR. The detection and
25 measurement of such reflections 214 of the infrared gaze tracking probe beam may be used in part by a controller 215 to calculate and determine a user's gaze.

In some examples, other features of the eye are also measured and
30 captured, for example related to a location of the user's eye pupil. In some examples, the IR detector / eye camera is used to capture and measure not

only the reference reflections/glints 214 but is also used to capture and measure a location of the eye pupil. A determination may be made of the detected location of the reference reflection 214 relative to the detected location of the pupil. Differences of the relative movement between the pupil and the reference reflections 214 can be used for detecting changes in the gaze direction.

The determination of the gaze may also be dependent on the generated gaze tracking probe beam, i.e. taking into account one or more characteristics of the generated infrared probe beam outputted such as its initial shape, size and intensity prior to being reflected from the user's eye as compared to the shape, size and intensity of the detected reflected gaze tracking probe beam.

Implementation of the controller 215 can be in hardware alone (e.g. circuitry such as processing circuitry comprising one or more processors and memory circuitry comprising one or more memory elements), have certain aspects in software including firmware alone or can be a combination of hardware and software (including firmware).

The controller 215 may be used to control one or more of the light source 212a and the light modulator 201a so as to control each of the image display beam and the gaze tracking probe beam. The generated gaze tracking probe beam may be modified, e.g. its size or shape or intensity, depended upon the detected reflected gaze tracking probe beam. Such feedback from the detection of the reflected gaze tracking probe beam can assist in the calibration of the apparatus and enable for the gaze tracking probe beam's pattern, shape or size to be optimised for the prevailing circumstances of use.

Whilst Figure 2 shows a single detector 213 for detecting the gaze of one eye, i.e. the user's right eye, the arrangement could be modified to, alternatively or additionally, determine the gaze of the user's other eye. Whilst Figure 2 shows a single detector 213 for detecting the gaze of one eye, i.e. the user's right eye, the arrangement could be modified to determine the gaze of the eye using two or more detectors. Whilst Figure 2 shows two light sources 212a and 212b, and two modulators 201a and 201b, a single light source and/or a single light modulator could be provided for generate image display and probe beams that are incident to each of the two in-coupling diffractive element areas 107a and 107b.

In the apparatus of Figure 2, where a combined visible and infrared light source is used, i.e. that simultaneously generates both visible and infrared light (as opposed to separately and independently generating visible and IR light such that the emission of visible and IR light can be separately and independently controlled), the apparatus may further comprise a selectively controllable filter to selectively filter out one of: the visible light (or a sub colour channel thereof) or the infrared light.

In some examples, e.g. where the IR optimised light guide is below (and disposed closer to the eye than) the RGB optimised light guide, a passive IR pass filter could be placed between the in-coupling area of the RGB optimised light guide and the in-coupling area of the IR optimised light guide, e.g. so as to reduce in-coupling of RGB light to the IR light guide. Alternatively, in other examples, e.g. where the RGB optimised light guide is below (and placed closer to the eye than) the IR optimised light guide, an IR blocking filter could be placed between the respective in-coupling areas, e.g. so as to reduce in-coupling of IR light to the RGB light guide.

In some examples a Liquid Crystal (LC) shutter could be placed between the light guides and the outside environment/world/reality. For example the LC

shutter could form part of a selectively transparent part of the external housing of the apparatus which is configured to selectively enable a real world view through the apparatus. Adjusting the shutter's transmissivity would control how much ambient light gets to the eye through the shutter and through the transparent light guides. The LC shutter could, in some examples, be integrated into an IR optimised light guide, in which case such a light guide may be placed between the RGB optimised light guide(s) and the outside environment/world/reality so that it would not block the RGB light from the light guide reaching the eye.

In some examples, the light guide 106a' which in-couples, expands and out-couples the infrared gaze tracking probe beam may be configured so as to selectively filter the transmission of infrared light therethrough. The light guide 106a' may be configured to act as a liquid crystal shutter that can selectively block the transmission of infrared light therethrough whilst still permitting the transmission of visible light therethrough.

When an image display beam is being generated and outputted, a selectively controllable filter may be used to block infrared light such that only visible light is incident to the user's eye during periods of outputting the image display beam output for user viewing. Likewise, in other examples, visible light may be selectively filtered / blocked / switched off such that only infrared gaze tracking light probe beam may be generated and incident to the user's eye when outputting an infrared gaze tracking probe beam.

Figure 3 schematically illustrates an example of light guides 306a and 306b suitable for use with examples of the present disclosure. For example, the light guides 306a and 306b may be configured for use as light guides 106a and 106b, or 106a' and 106b' of Figure 2.

The light guide 306a comprises in-coupling diffractive area 307a which in-couples an input beam 305a to the substrate, which beam is then expanded via diffractive element area 316a in a y direction and then expanded in an x direction and out-coupled out of the light guide via an out-coupling diffractive element 308a so as to produce output beam 311a. The input optical beam 305a may correspond to an image display beam (or a component of the image display beam such as a red, green or blue component thereof) or an infrared gaze tracking probe beam.

10 In the apparatus of Figure 2, the reflected gaze tracking probe beam 214 needs to propagate through each of the stacked light guides 106a' and 106a to reach the detector for detection. Figure 4 schematically shows an apparatus 400 that avoids such issues.

15 Figure 4 schematically shows an apparatus in the form of glasses/goggles with support members/arms 418 for holding the apparatus in place on a user's head. In this example, the detector 413 is not disposed on the light guides. Instead, a reflector element 417, such as a mirror or hot mirror configured to reflect infrared light, is provided e.g. on in the light guide, namely an inner/lower surface of the lower light guide. It is to be appreciated that the reflector element could be located almost anywhere in front of the eye, even on an opposite side of the light guide stack.

25 The reflector is configured to further reflect 419 the reflected gaze tracking beam to a detector 413, thereby providing increased flexibility as to the location of the detector. In this example, the detector is disposed on a part of a housing of the apparatus such as support arm 418. The reflector 417 may be further configured so as to provide optical power so as to focus the reflected infrared gaze tracking probe beam 214 towards the detector 413.

Figure 5A schematically illustrates an example of an apparatus 500 comprising a combined/highly integrated visible and infrared light source 512 which may be used as a laser projector engine. A laser diode 521 generates infrared light which is focused by lens 522 into a non-linear crystal 523, such as periodically poled lithium niobate (PPLN), comprising a surface bragg grating whereby the infrared light is converted into red, green and blue visible wavelengths. However, some infrared light will pass through the non-linear crystal without undergoing such conversion. A conventional laser projection engine would typically block such non-converted infrared light deeming it to be an undesired noise signal. However, such non-converted infrared light may advantageously be used in examples of the present application as a source of infrared illumination. Thus, the light source 512 provides the simultaneous generation of both visible light as well as infrared light that can be incident to a light modulator 501, under control of a controller 515, so as to sequentially generate an image display beam and a gaze tracking probe beam from the incident visible and infrared beams respectively. A selectively controllable filter or shutter may be used to selectively filter/block IR light when the image display beam is being generated and likewise selectively filter/block visible light when the gaze tracking probe beam is being generated.

The light modulator 501 comprises a two axis scanning mirror which can be used to impart an image to the visible light from the light source to generate the image display beam. Also, the light modulator can be used to impart a pattern on the infrared light from the light source to generate the gaze tracking probe beam.

Figure 5B schematically illustrates an apparatus 530 with an alternative light source 512 and an alternative light modulator 501. The light source 512 is configured to independently and separately generate visible light (and/or sub component colour channels thereof) and infrared light. The light source

512 may corresponds to one or more separate light sources, e.g. LEDs, such as: red, green, blue and infrared LEDs which are independently operable under control of a controller 515. Light from the LEDs is directed to a reflective microdisplay 531 via beam splitter 532. The modulated/modified light
5 reflected from the microdisplay is then guided to a prism 533 and reflected therefrom to an in-coupling diffractive element area 507 of a light guide 506 to be out-coupled to a user's eye 110 via out-coupling diffractive element area 508. A detector 513 is provided that is configured to detect the out-coupled light which is reflected from the user's eye.

10

The apparatuses as variously described above may be provided in a module. As used here 'module' refers to a unit or apparatus that excludes certain parts/components that would be added by an end manufacturer or a user.

15

In certain examples, the apparatus may be provided as a device, wherein a device is configured for at least one of portable use, wearable use and head mountable use. The device may also be configured to provide functionality in addition to display and gaze tracking. For example, the
20 device may additionally be configured to provide one or more of: audio/text/video communication functions (e.g. tele-communication, video-communication, and/or text transmission (Short Message Service (SMS)/ Multimedia Message Service (MMS)/emailing) functions), interactive/non-interactive viewing functions (e.g. web-browsing,
25 navigation, TV/program viewing functions), music recording/playing functions (e.g. Moving Picture Experts Group-1 Audio Layer 3 (MP3) or other format and/or (frequency modulation/amplitude modulation) radio broadcast recording/playing), downloading/sending of data functions, image capture function (e.g. using a (e.g. in-built) digital camera), and
30 gaming functions.

The apparatus may be a part of a NED device, for example, glasses or goggles. It should be understood, however, that glasses or goggles are merely illustrative of an NED device that would benefit from examples of implementations of the present disclosure and, therefore, should not be taken to limit the scope of the present disclosure to the same. For example the apparatus may take other forms such as a visor or helmet or may be implemented in other electronic devices not least hand devices, or portable devices.

Although examples of the apparatus have been described above in terms of comprising various components, it should be understood that the components may be embodied as or otherwise controlled by a corresponding processing element, processor or circuitry of the apparatus.

As used in this application, the term 'circuitry' refers to all of the following:

- (a) hardware-only circuit implementations (such as implementations in only analogue and/or digital circuitry) and
- (b) to combinations of circuits and software (and/or firmware), such as (as applicable): (i) to a combination of processor(s) or (ii) to portions of processor(s)/software (including digital signal processor(s)), software, and memory(ies) that work together to cause an apparatus, such as a mobile phone or server, to perform various functions) and
- (c) to circuits, such as a microprocessor(s) or a portion of a microprocessor(s), that require software or firmware for operation, even if the software or firmware is not physically present.

This definition of 'circuitry' applies to all uses of this term in this application, including in any claims. As a further example, as used in this application, the term "circuitry" would also cover an implementation of merely a processor (or multiple processors) or portion of a processor and its (or their) accompanying software and/or firmware.

Features described in the preceding description may be used in combinations other than the combinations explicitly described.

Although functions have been described with reference to certain features,
5 those functions may be performable by other features whether described or not. Although features have been described with reference to certain examples, those features may also be present in other examples whether described or not. Although various examples of the present disclosure have been described in the preceding paragraphs, it should be appreciated that
10 modifications to the examples given can be made without departing from the scope of the invention as set out in the claims.

The term 'comprise' is used in this document with an inclusive not an exclusive meaning. That is any reference to X comprising Y indicates that X
15 may comprise only one Y or may comprise more than one Y. If it is intended to use 'comprise' with an exclusive meaning then it will be made clear in the context by referring to "comprising only one ..." or by using "consisting".

In this description, wording such as 'couple', 'connect' and
20 'communication' and their derivatives mean operationally coupled/connected/in communication. It should be appreciated that any number or combination of intervening components can exist (including no intervening components).

25 In this description, reference has been made to various examples. The description of features or functions in relation to an example indicates that those features or functions are present in that example. The use of the term 'example' or 'for example' or 'may' in the text denotes, whether explicitly stated or not, that such features or functions are present in at least the
30 described example, whether described as an example or not, and that they can be, but are not necessarily, present in some or all other examples. Thus

'example', 'for example' or 'may' refers to a particular instance in a class of examples. A property of the instance can be a property of only that instance or a property of the class or a property of a sub-class of the class that includes some but not all of the instances in the class.

5

In this description, references to "a/an/the" [feature, element, component, means ...] are to be interpreted as "at least one" [feature, element, component, means ...] unless explicitly stated otherwise.

- 10 The above description describes some examples of the present disclosure however those of ordinary skill in the art will be aware of possible alternative structures and method features which offer equivalent functionality to the specific examples of such structures and features described herein above and which for the sake of brevity and clarity have been omitted from the
- 15 above description. Nonetheless, the above description should be read as implicitly including reference to such alternative structures and method features which provide equivalent functionality unless such alternative structures or method features are explicitly excluded in the above description of the examples of the present disclosure.

20

Whilst endeavouring in the foregoing specification to draw attention to those features of examples of the present disclosure believed to be of particular importance it should be understood that the applicant claims protection in respect of any patentable feature or combination of features hereinbefore

25 referred to and/or shown in the drawings whether or not particular emphasis has been placed thereon.

CLAIMS

We claim:


- 5 1. An apparatus comprising:
a light modulator configured to receive light of a first range of wavelengths
and generate an image beam therefrom, wherein the light modulator is
further configured to receive light of a second range of wavelengths and
generate a probe beam therefrom;
- 10 one or more light guides comprising:
one or more in-coupling diffractive element areas, and
one or more out-coupling diffractive element areas;
wherein the one or more in-coupling diffractive element areas are
configured to receive and in-couple the image beam and the probe
15 beam into the one or more light guides; and
wherein the one or more out-coupling diffractive element areas are
configured to out-couple, from the one or more light guides:
the image beam to a user's eye for user viewing, and
the probe beam to the user's eye for detection of reflection
20 therefrom.
2. An apparatus as claimed in claim 1, wherein the light modulator is
further configured to:
control a pattern, shape and/or size of the probe beam;
25 and/or
dynamically vary a pattern of the probe beam.
3. An apparatus as claimed in any one or more of the previous claims,
further comprising a detector configured to detect reflections of the
30 probe beam.

4. An apparatus as claimed of claim 3, further comprising a controller to modify the probe beam dependent upon the detection of the reflected probe beam.
- 5 5. An apparatus as claimed in any one or more of the previous claims 3 or 4, further comprising a reflector configured to further reflect the reflected probe beam to the detector.
- 10 6. An apparatus as claimed in claim 3, further comprising a controller to determine a user's gaze based on the detected reflected probe beam.
- 15 7. An apparatus as claimed in any one or more of the previous claims, wherein the light of the first range of wavelengths comprises visible light and the light of the second range of wavelengths comprises Infrared light.
- 20 8. An apparatus as claimed in any one or more of the previous claims, further comprising one or more of:
a light source configured to generate simultaneously the light of the first range of wavelengths and the light of the second range of wavelengths.
- 25 9. An apparatus as claimed in any one or more of the previous claims, further comprising a selectively controllable filter to selectively filter one of: the light of the first range of wavelengths and the light of the second range of wavelengths.
- 30 10. An apparatus as claimed in any one or more of the previous claims, further comprising a light source configured to generate sequentially

the light of the first range of wavelengths and the light of the second range of wavelengths.

- 5 11. An apparatus as claimed in any one or more of the previous claims, wherein the one or more in-coupling diffractive element areas and one or more out-coupling diffractive element areas are comprised in a single light guide.
- 10 12. An apparatus as claimed in any one or more of the previous claims, wherein the one or more light guides is configured as an exit pupil expander.
- 15 13. An apparatus as claimed in any one or more of the previous claims, wherein the apparatus is configured for use as a near eye display and a gaze tracker.
14. A module comprising the apparatus of any one or more of previous claims.
- 20 15. A device comprising the apparatus of any one or more of previous claims 1 to 13 or the module of claim 14, wherein the device is configured for at least one of:
portable use, wearable use, head mountable use, wireless
communications.

1/5



2/5




FIG. 2




FIG. 3

3/5




FIG. 4

4/5




FIG. 5A

5/5




FIG. 5B

INTERNATIONAL SEARCH REPORT

International application No
PCT/FI2016/050072

A. CLASSIFICATION OF SUBJECT MATTER
INV. G02B27/01 G02B27/00
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
G02B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, COMPENDEX, INSPEC, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 2007/085682 A1 (NOKIA CORP [FI]; NUMMELA VILLE [FI]) 2 August 2007 (2007-08-02) figures 13,14,18,22 page 14, line 18 - line 33 page 17, line 16 - page 18, line 20 abstract page 21, line 1 - line 12 -----	1-15
X	WO 2013/049012 A1 (BOHN DAVID D [US]) 4 April 2013 (2013-04-04) paragraphs [0028], [0043] - [0045], [0062], [0069], [0070], [0075], [0076], [0079]; figures 1,2B,5A,5B,7A ----- -/--	1-15



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

6 April 2016

Date of mailing of the international search report

20/04/2016

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Girardin, François

INTERNATIONAL SEARCH REPORT

International application No

PCT/FI2016/050072

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 1 012 655 B1 (MICROOPTICAL CORP [US]) 2 May 2007 (2007-05-02) paragraphs [0051], [0071], [0072] abstract	2,4,10
A	----- JP 2010 134051 A (BROTHER IND LTD) 17 June 2010 (2010-06-17) abstract paragraphs [0033], [0034] -----	2,4

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/FI2016/050072

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 2007085682	A1	02-08-2007	CN 101336089 A	31-12-2008
			EP 1983884 A1	29-10-2008
			US 2011109880 A1	12-05-2011
			WO 2007085682 A1	02-08-2007

WO 2013049012	A1	04-04-2013	CN 102955255 A	06-03-2013
			HK 1180771 A1	22-01-2016
			TW 201314263 A	01-04-2013
			US 2013077049 A1	28-03-2013
			WO 2013049012 A1	04-04-2013

EP 1012655	B1	02-05-2007	CA 2268196 A1	16-04-1998
			DE 69737700 T2	10-01-2008
			EP 1012655 A1	28-06-2000
			JP 3429320 B2	22-07-2003
			JP 2000511306 A	29-08-2000
			US 5886822 A	23-03-1999
			WO 9815868 A1	16-04-1998

JP 2010134051	A	17-06-2010	NONE	
