




US 20170296786A1

(19) **United States**(12) **Patent Application Publication**
PACHECO et al.(10) **Pub. No.: US 2017/0296786 A1**(43) **Pub. Date: Oct. 19, 2017**(54) **COMPONENTS AND METHODS FOR
BALANCING A CATHETER CONTROLLER
SYSTEM WITH A COUNTERWEIGHT**(71) Applicant: **Catheter Precision, Inc.**, Ledgewood,
NJ (US)(72) Inventors: **Robert PACHECO**, Bayside, NY (US);
Steve FOLEY, Kerrville, TX (US);
David JENKINS, Budd Lake, NJ (US)(21) Appl. No.: **15/640,879**(22) Filed: **Jul. 3, 2017****Related U.S. Application Data**(62) Division of application No. 14/468,437, filed on Aug.
26, 2014, now Pat. No. 9,724,493.(60) Provisional application No. 61/870,311, filed on Aug.
27, 2013.**Publication Classification**(51) **Int. Cl.**
A61M 25/01 (2006.01)
A61B 34/30 (2006.01)*A61B 90/50* (2006.01)*A61B 90/50* (2006.01)*A61B 90/00* (2006.01)*A61B 34/30* (2006.01)*A61B 90/00* (2006.01)(52) **U.S. Cl.**CPC **A61M 25/0113** (2013.01); **A61B 34/30**
(2016.02); **A61M 2205/332** (2013.01); **A61B**
2090/504 (2016.02); **A61B 2090/067**
(2016.02); **A61B 2090/064** (2016.02); **A61B**
2034/301 (2016.02); **A61M 2205/3331**
(2013.01); **A61B 2090/5025** (2016.02)

(57)

ABSTRACT

Various embodiments provide systems and methods for controlling a catheter with a catheter positioning device by using a remote controller. The catheter positioning device may include a sled member, sled base, counterweight, and passive damping system. The sled member may be configured to accept a handle of the catheter. The sled base may be configured to move the sled member along a length of the sled base in order to position the catheter within a patient. The counterweight may be moveably coupled to the sled base. The passive damping system may be coupled to the sled base and configured to resist movement of the sled base.






FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5




FIG. 6A




FIG. 6B

COMPONENTS AND METHODS FOR BALANCING A CATHETER CONTROLLER SYSTEM WITH A COUNTERWEIGHT

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a divisional application of U.S. Non-Provisional application Ser. No. 14/468,437, entitled “COMPONENTS AND METHODS FOR BALANCING A CATHETER CONTROLLER SYSTEM WITH A COUNTERWEIGHT,” filed on Aug. 26, 2014, which claims the benefit of priority to U.S. Provisional Patent Application No. 61/870,311, entitled “COMPONENTS AND METHODS FOR BALANCING A CATHETER CONTROLLER SYSTEM WITH A COUNTERWEIGHT,” filed Aug. 27, 2013, the entire contents of both of which are incorporated herein by reference.

BACKGROUND

[0002] Many invasive medical procedures require the use of radiation to visualize and track the location of an inserted device. For example, procedures involving catheter insertion, such as invasive electrophysiology procedures, rely on fluoroscopy or other radioactive imaging techniques to help navigate and position the catheter within a patient's body at a particular site, such as in the heart or inside a blood vessel in the circulatory system.

[0003] High dosages of radiation may have long term adverse health effects. A patient may be directly exposed only once or twice to radiation during such procedures and avoid such adverse effects. However, physicians, medical technicians and staff can experience a large cumulative radiation dosage over time, both directly and indirectly, from conducting many procedures.

[0004] To protect the operator and staff from this radiation, shielding such as lead aprons, gowns, glasses, skirts, etc., is worn. Such lead clothing, especially a lead apron, is quite heavy and uncomfortable, and its use has been associated with cervical and lumbar spine injury or degradation.

SUMMARY OF THE INVENTION

[0005] The various embodiments include a catheter positioning system having a sled member configured to accept a handle of a catheter and a sled base configured to move the sled member along a length of the sled base in order to position the catheter within a patient, that also features a counterweight moveably coupled to the sled base by a drive mechanism that is configured to move the counterweight in order to reduce shifting of the center of mass of the sled member, sled base and counterweight as the sled member is moved along the sled base. In an embodiment, the counterweight is moveably coupled to the sled base and the drive mechanism is configured so that the counterweight moves along the length of the sled base. In an embodiment, the drive mechanism includes a cable coupled between the counterweight and the sled member and passing around at least one pulley that is configured so that the counterweight moves in a direction opposite to that of the sled member. In an embodiment in which the counterweight has a weight substantially similar to that of the sled member the drive mechanism may be configured so that the counterweight moves the same distance as the sled member, though in the opposite direction. If the counterweight has a weight sub-

stantially different from that of the sled member, the drive mechanism may be configured so that the counterweight moves a distance that is approximately equal to the distance moved by the sled member times the ratio of the weight of the sled member divided by the weight of the counterweight. In an embodiment, the drive mechanism may include a drive motor and at least one gear coupled to the drive motor.

[0006] In a further embodiment, the catheter positioning system may include a sensor coupled to the catheter positioning system, and a control system coupled to the sensor that is configured to control the drive mechanism to move the counterweight based on data from the sensor. In this embodiment, the sensor may be any one or more of a tilt sensor, a pressure sensor, a stress sensor, and a strain sensor. Overall, the counterweight may be configured on the catheter positioning system to move in response to movements of the sled member so that a bending moment applied to a support structure supporting the sled base remains approximately constant.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] The accompanying drawings, which are incorporated herein and constitute part of this specification, illustrate exemplary embodiments of the invention, and together with the general description given above and the detailed description given below, serve to explain the features of the invention.

[0008] FIG. 1 is a system diagram illustrating a remote controller, a remotely controlled catheter system, and a programmable control system.

[0009] FIG. 2A is a system diagram illustrating a catheter positioning system, a slide member and a bending moment generated by the slide member on a support structure.

[0010] FIG. 2B is a system diagram illustrating an embodiment catheter positioning system with a counterweight

[0011] FIG. 2C is a system diagram illustrating an embodiment catheter positioning system with a series of counterweights.

[0012] FIG. 2D is a system diagram illustrating an embodiment catheter positioning system with a distributed liquid counterweight.

[0013] FIG. 3A is a system diagram illustrating an embodiment system with a sled member coupled to a counterweight by a pulley.

[0014] FIG. 3B is a system diagram illustrating an embodiment system with a sled member coupled to a counterweight by pulleys of different sizes.

[0015] FIG. 3C is a system diagram illustrating an embodiment system with a sled member coupled to a counterweight by a gear.

[0016] FIG. 3D is a system diagram illustrating an embodiment system with a sled member coupled to a counterweight by gears of different sizes.

[0017] FIGS. 4A-4C are diagrams illustrating a sequence of relative motions of a sled member and a counterweight in an embodiment catheter positioning system.

[0018] FIG. 5 is a system diagram illustrating an embodiment system with a counterweight and drive assembly controlled by a control system based on sensor inputs.

[0019] FIG. 6A is a system diagram illustrating an embodiment system with a passive damping system.

[0020] FIG. 6B is a system diagram of an embodiment system with an active damping system controlled by a control system based on sensor inputs.

DETAILED DESCRIPTION

[0021] Various embodiments will be described in detail with reference to the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts. References made to particular examples and implementations are for illustrative purposes and are not intended to limit the scope of the invention or the claims.

[0022] Various embodiments provide systems and methods for reducing bending moments in a catheter positioning system during catheterization procedures. The embodiment systems allow a physician to remotely control a catheter position within a patient while being positioned away from sources of radiation used for imaging, thereby avoiding harm associated with repeated exposure to radiation or caused by heavy protective gear. A catheter positioning device provides a telerobotic capability to advance and rotate an attached catheter within a patient's body. The catheter positioning device may also be used to actuate the catheter, such as by controlling an actuator on a catheter's handle to deflect a tip to help in navigation. An example of a catheter positioning device is disclosed in PCT Application PCT/US2009/0311357, which published as WO 1009/092059 and is incorporated herein by reference in its entirety for details of the catheter positioning device.

[0023] A catheter positioning system such as disclosed in WO 1009/092059 functions to advance or withdraw the catheter longitudinally in order to advance or withdraw the catheter within the patient's body. Since the catheter enters the patient's body at a single point, the catheter positioning system may include a rail or sled base along which a sled member holding the catheter handle advances, and a support structure that holds the rail or sled base in a fixed orientation with respect to the patient. For example, the support structure may be a bridge or arm that extends over a table to hold the catheter positioning system rail or sled base at a fixed elevation an angle with respect to the patient.

[0024] The sled member may itself include drive motors for rotating the catheter handle, and thus may be heavy. As the sled member advances along the rail or sled base, the distance between the sled member and the support structure holding the rail or sled base will change. As a result, a bending moment applied to the support structure will change as the moment arm (i.e., the distance between the sled member and the support structure) changes. For example, when the catheter is fully withdrawn from the patient and the sled member near a distal end of the rail or sled base, the bending moment applied to the support structure may be significantly greater than when the catheter is partially inserted such that the sled member is positioned near the support structure. Patient safety requires that the angle of insertion of the catheter remain as steady as possible, so the support structure must be sufficiently rigid as to accommodate this change in bending moment without deflecting during a procedure. However, this requirement may add substantial mass and cost to the support structure, and limit the types of support structures that may be implemented.

[0025] In various embodiments the catheter positioning device address the problem of changes in the bending moment applied to a support structure by including a coun-

terweight system configured to maintain a consistent center of mass of the system as a catheter is positioned. In overview, the counterweight may be of sufficient mass and coupled to a drive mechanism that moves the mass in conjunction with movement of the sled member so as to at least partially overcome changes in the bending moment applied to a support structure. By functioning to maintain an approximately consistent center of mass system, embodiment counterweight systems may help to keep the catheter positioning device stable during catheterization procedures, while reducing the strength and weight of the device support structures.

[0026] In an embodiment, the counterweight may be moved by various mechanical mechanisms, such as a pulley system or gear drive, in response to the motion of the sled member of the catheter positioning system. In further embodiments, a control system may control movement of the counterweight based on one or more sensors for detecting the position of the sled member along the rail or sled base, bending stress applied to the support structure, and/or strain in various parts of the catheter positioning device or support structure.

[0027] FIG. 1 illustrates an embodiment catheter positioning device 100 with a remote controller 124. The catheter positioning device 100 may include a sled base 102 coupled with a sled member 104. The sled base 102 may be configured to advance the sled member 104 along the sled base 102 towards the body of the patient or back away from the patient. For example, the sled member may be moved with a motor at one end of the sled base 102. The sled member 104 may be driven along a rail or sled base 102 by a drive mechanism, such as a worm drive, in order to advance or withdraw the catheter.

[0028] The sled base may be held in position above a patient or operating table 120 by a bridge (not shown) or support arm 112 that includes a sled base support structure 114 that holds the sled base 102 in a fixed position and orientation. The arm 112 may be extended or rotated to position the sled base 102 relative to a patient on the operating table 120. The sled base may also include a nose cone 116 that supports insertion of the catheter into a patient. A catheter may be advanced along the sled base 102 by the sled member 104 so that it passes through the nose cone 116 and into the patient.

[0029] The sled base 102 may include a sterile barrier configured to support and protect the catheter. The sterile barrier may include a resealable delivery channel configured to receive and guide the catheter along the sled base as it is advanced by the sled member 104. For example, the catheter may be inserted into the delivery channel and then the catheter handle 118 may be connected to the sled member 104 (such as by using the modular plate 106 discussed below) such that the catheter is driven forward by translation of the sled member 104 along the resealable delivery channel in the sled base 102 and through the nose cone 116 into the patient.

[0030] The sled member 104 may be coupled to a modular plate 106 to which a catheter handle 118 may be attached. Many alternate modular plates 106 that may be swapped out so that the catheter positioning system may be used with many different types of catheters. Depending on the kind of catheter that is desired for a procedure, an appropriate modular plate 106 may be attached to the sled member 104 and the catheter may be attached to the module plate 106.

The modular plate **106** may also integrate with any actuators on the catheter handle **118** thereby allowing an operator to control the actuators via the remote controller **124**.

[0031] The sled member **104** may be rotated by a drive mechanism in order to rotate a catheter connected to the modular plate **106**. This rotation may be controlled remotely via the remote controller **124**. By controlling translation along the sled base **102**, rotation of the sled member **104**, and actuation of the catheter's handle via the modular plate **106**, an operator may position or use the catheter in any way necessary for a desired operation. Further, an operator may control each of these degrees of freedom (i.e., translation, rotation, and actuation) remotely with the remote controller **124**.

[0032] A remote controller **124** may be connected to a programmable control system **132** by a wired connector **136** or a wireless data link (not shown). The programmable control system **132** may also be connected to the catheter positioning device **100** by a wired connector **134** or a wireless data link (not shown). The programmable control system **132** may output command signals to the positioning device **100** based on training or programming, such as programmed movements for automatic positioning of the catheter.

[0033] FIG. 2A illustrates a catheter positioning device without a counterweight in order to illustrate the problem of the changing bending moment applied to a sled base support structure **114** as the sled member **104** moves along the rail or sled base, such as from position A to position B. As a sled member **104** advances down a sled base **102**, the system's center of mass will shift, such as from CG_{sysA} to CG_{sysB} , and the sled base **102** will apply a bending moment to the sled base support structure **114**, which will apply a torque to a support arm **112**, in the direction of the arrow **200** shown in FIG. 2A. Generally, a torque or bending moment "M" equals the vector cross product of a force vector "F" and a distance vector "r" (e.g., $M=F \times r$). For example, the torque or bending moment M is the value or magnitude of a force vector F, in this case the downward force of the weight of the sled member **104**, times its moment arm r, which is the distance from the weight (e.g., the center of mass) to the point of analysis, such as approximately the center of the support structure **114**. Thus, the further sled member **104** is from the support structure **114**, the greater the bending moment applied to the sled base **102** (e.g., and torque applied to the support structure **114**). Deflection of the sled base **102** (e.g., deflection D) due to bending moments generated from movement of the sled member **104**, may shift the introducer and/or catheter at the point of entry into the patient thereby potentially disrupting an ongoing operation or procedure. Various embodiments avoid these potential problems by using a moveable counterweight to compensate for movement of the sled member **104** on the sled base **102**, and to thereby maintain a relatively constant center of mass of the system and reduce or eliminate deflection. The various respective centers of mass throughout the figures of sled members, counter weights, sled base support structures and positioning systems are shown for illustrative purposes only. One of skill in the art will recognize that the placement of the centers may not be to scale and may not accurately represent the actual locations or positions of these centers of mass in an actual system.

[0034] FIG. 2B illustrates an embodiment system with a counterweight **202** coupled to the sled base **102** and con-

figured to counter balance the sled member **104** about the support structure **114**. As the sled member **104** moves along the sled base **102** to position the catheter, a bending moment M1 is applied. The counterweight **202** may be moved in the opposite direction in an amount that will apply a compensating bending moment M2. Because of the action of the counterweight **202**, the center of mass of the system, including the support structure **114** will remain relatively constant and deflection of the sled base **102** may be reduced or eliminated.

[0035] The counterweight **202** creates a bending moment M2, which may be applied as a torque about the support structure **114** that is approximately equal to the bending moment M1. Because the bending moment M2 is applied on the opposite side of the support structure **114**, the bending moment M2 applies a force in the opposite direction of the bending moment M1 applied by sled member **104** (e.g., due to the support structure **114** acting as a fulcrum). The moment arm **210** of the counterweight **202** extends from the center of mass of the counterweight **202** to the center of the support structure **114**. The moment arm **208** of the sled member **104** extends from the center of mass of the sled member **104** to the center of the support structure **114**. Thus, the support structure **114** may translate downward forces applied from the counterweight **202** side of the sled base **102** to an upward force on the sled member **104** side of the sled base **102**.

[0036] As the sled member **104** advances on the sled base **102** to position the catheter, its moment arm **208** changes. For example, the moment arm **208** may decrease as it approaches a mid-point of the support structure **114**. The moment arm **208** may increase as it approaches full travel in a direction away from the support structure **114**. Thus, because the force of the sled member **104** (e.g., mass or weight) remains constant, the bending moment M1 applied to the support structure **114** from the sled member **104** changes in direct proportion to the length of the moment arm **208**, such as r1.

[0037] To counter this change in the bending moment M1 applied due to the sled member **104** and to help prevent deflection and tilting of the sled base **102**, a bending moment M2 may be exerted by the counterweight **202** that counters the bending moment M1. As the position of the sled base **102** changes, the position of the counterweight **202** may be changed in the opposite direction by moving the counterweight **202** towards or away from the support structure **114** to increase or decrease its moment arm **210**. If the counterweight **202** and sled member **104** are on opposite sides of the support structure **114**, the moments may act about the same axis (i.e., the support structure **114**) but in opposite directions with the support structure **114** acting as a fulcrum (e.g., similar to children balancing on a seesaw).

[0038] In embodiments in which the sled member **104** and counterweight **202** weigh the same, then the counterweight **202** may be moved a distance equal to the distance of travel of the sled member **104** (though in an opposite direction). In other embodiments, the mass of the counterweight **202** may be different from that of the sled member **104**. In such embodiments, the amount of travel of the counterweight **202** may be equal to the distance of travel of the sled member times the ratio of the masses of the sled member to the counterweight. Again, this is because bending moment is equal to the weight times the moment arm. In examples, such as when the support structure is located toward one end

of the sled base **102**, an insufficient amount of distance on the counterweight **202** side of the sled base **102** may exist between the end of the sled base **102** and the support structure **114**. Limiting the range of movement of the counterweight **202**. Thus, the limited range of movement of the counterweight **202** may be compensated for by increasing its mass compared to the sled member **104**. Thus, a relatively shorter moment arm **210** may nevertheless produce a sufficient bending moment **M2** to compensate for the bending moment **M2** when the mass of the counterweight **202** is increased.

[0039] In the various embodiments, any of a number of drive mechanisms may be used to move the counterweight **202** in response to movements of the sled member **104**.

[0040] In further embodiments, as illustrated in FIG. 2C, a series of counterweights (e.g., **202a**, **202b**, . . .) may be used to provide a balancing for the movement of the sled member **104** on the sled base **102**. For example, a first counterweight **202a** may be positioned at a distance **r2 210a** from the support structure **114** and a second counterweight **202b** may be positioned at a distance **r3 210b** from the support structure **114**. In some embodiments, the first and second counterweights **202a** and **202b** may be smaller than the counterweight **202** illustrated in FIGS. 2A and 2B. Also, additional counterweights may be used on either side of the support structure **114**. The first counterweight **202a** may produce a first moment **M2** that is the cross product of the force vector **F2** and the distance **r2**. The second counterweight **202b** may produce a second moment **M3** that is the cross product of the force vector **F3** and the distance **r3**. The positions of the first and second counterweights **202a** and **202b** may be controlled individually to provide fine control over the counterbalancing action. For example, when acceleration components are present in the movement of the sled member **104**, the use of additional counterweights may provide a greater degree of control over the movement of the first and second counterweights **202a** and **202b** or additional counterweights to compensate for complex bending forces.

[0041] In a further embodiment illustrated in FIG. 2D, a liquid counterbalancing mechanism **204** may be used to provide counterbalancing. In a liquid counterbalancing mechanism **204a**, a series of chambers **206** may contain a liquid, such as water, oil, or mercury. The counterbalancing mechanism **204a** may be configured such that the liquid is pumped back and forth between the chambers **206**, either passively or actively, in order to provide a compensating counterweight. In a passive embodiment, such as the liquid counterbalancing mechanism **204a** illustrated in FIG. 2D, the liquid may be flow between the chambers **206** as the sled member **104** moves on the sled base **102**. In active embodiments, liquid may be pumped between the chambers **206**, or to and from an external reservoir (not shown) using control mechanisms **208a** and **208b** (e.g., pumps or a gravity feed system) to provide an active counterbalancing system **204b**, the levels of the liquid in the chambers **206** may be controlled. In such embodiments, the movement of the liquid into and out of the various chambers **206** may function to shift the center of gravity of the system similar to movement of counterweights as described herein. Using such a liquid counterbalance mechanism may also serve to dampen some vibrations or jitter in the system due to viscosity effects.

[0042] FIG. 3A illustrates an embodiment in which the counterweight **202a** is linked with the sled member **104** by a cable **304** about a pulley **302**. The cable **304a** may thereby

directly link the movement of the sled member **104** to the movement of the counterweight **202a**. The configuration of the cable **304a** and the pulley **302** may also translate the directional movement of the counterweight **202a** relative to the sled member **104**, such that when the sled member **104** moves in one direction on a first side of the sled base **102**, the counterweight **202** moves in an opposite direction on a second side of the sled base **102**. In this embodiment, as the sled member **104** moves along the sled base **102**, the sled member **104** (or a drive mechanism coupled to the sled member **104**) may cause the cable **304a** to be taken in or let out. The cable **104** may be guided or redirected by one or more pulleys **302** or cable guides (not shown). The cable **304a** may be attached to the counterweight **202a**. In this configuration, movement of the sled member **104** will result in a corresponding proportional movement of the counterweight **202a**. By the movement of the cable **304a**, changes in the moment arm of the sled member **104** may be balanced by changes in the moment arm of the counterweight **202** such that the overall center of mass does not change significantly. In embodiments in which the cable **304** is directly coupled to the sled member **104** on one end, and coupled to the counterweight **202a** on the other end through a single pulley **302**, displacements in movement may be directly proportional. Thus, such embodiments may be implemented with a counterweight **202a** having approximately the same mass as the sled member **104**. In this manner, the counterbalancing movement of the counterweight **202** may produce proportional forces (e.g., **M2**) to counteract changes in the bending moment **M1** applied to the support structure **114** by the sled **104** during a catheter positioning procedure.

[0043] In another embodiment illustrated in FIG. 3B, one or more additional pulleys **302**, such as spools or pulleys **302a** and **302b** of different sizes, may be arranged on a common axis and may be coupled to respective cables **304b** and **304c**. The common axis may cause rotation of both of the spools or pulleys **302a** and **302b** together. By using different sized spools or pulleys **302a** and **302b**, a translating drive effect may be achieved between the movement of one pulley, and the movement of a different sized spool or pulley. Such translating drive effect may provide a ratiometric relationship between the movement of the sled member **104** and the movement of the counterweight **202b**, which may be of a different (e.g., larger) mass than the sled member **104**. For example, the ratiometric relationship may be based on the ratios of the respective diameters of the spools or pulleys. In an example in which the counterweight **202b** is of a greater mass than the sled member **104**, the sled member **104** may be coupled to the larger spool or pulley **302a** and the counterweight **202b** may be coupled to the smaller spool or pulley **302b**. The cables **304b** and **304c** may be individually controlled.

[0044] In a further embodiment, a cable linkage between the sled member **104** and counterweight **202** may include a block and tackle arrangement to enable use of a counterweight that is different from the weight of the sled member. For example, instead of a direct linkage, the counterweight **202** may be coupled to a pulley and the cable fixed to the sled base after passing through the pulley. In this configuration the counterweight will move half as far as the sled member **104** in either direction, so the counterweight may weigh twice as much as the sled member **104**.

[0045] In further embodiments, the counterweight may be coupled with a retrieval mechanism configured to move the

counterweight in the opposite direction. For example, as the sled member **104** moves backwards, a retrieval mechanism may move the counterweight **202** in the opposite direction and draw up any slack in the cable **304**. Various retrieval mechanisms may be used, such as a second cable and pulley connected to a motor or the front of the sled member.

[0046] FIG. 3C illustrates an alternate embodiment for moving the counterweight **202a** in response to movements of the sled member **104**. In this embodiment, the sled member **104** may be attached to a first toothed arm **314** that is advanced or retracted by a drive gear **312**. Similarly, the counterweight **202a** may be attached to a second toothed arm **316** that engages the same or a different drive gear **312**. If the first arm **314** and second arm **316** are coupled to the same drive gear **312**, such that as the sled member **104** advances, the first arm **314** turns the gear **312** that moves the second arm **316** and counterweight **202** an equal distance but opposite in the opposite direction. In this configuration, the counterweight **202** may weigh the same as the sled member **104**.

[0047] In a further embodiment, the counterweight **202b** and sled member **104** may have different weights, as illustrated in FIG. 3D. A first gear **312a** may be coupled to the arm **314** and the sled member **104**. A second gear **312b**, having a different tooth size (e.g., smaller) may be coupled to the arm **316** and the counterweight **202b**. The gear **312a** and **312b** may be coupled to a common axis so that each gear rotates together with the other through a common drive. The arm **316** may be configured to move the counterweight **202b** a different distance than the sled member **104** due to the ratiometric relationship between the gears **312a** and **312b**. In various embodiments, the gears **312a** and **312b** may have a different ratio or number of teeth. For example, if the counterweight **202b** has a greater mass than the sled member **104**, that counterweight may be driven by a coaxial gear **312b** that has a smaller radius so that the coaxial gear **312b** drives the second arm **316** a shorter distance than the first arm **314**. Since the counterweight **202** is heavier, such a shorter travel may exert the same or similar moment to balance changes in the bending moment of the sled member **104**.

[0048] FIGS. 4A-4C illustrate an alternate configuration in which the counterweight **402** is configured to maintain a constant bending moment on the same side of the support structure **114**, rather than balancing against the moment applied by sled member **104** on an opposite side of the support structure **114**. In this configuration the sled base **102** may be attached to a support structure **114** at a position removed from a center point of the sled base **102**. The total bending moment or torque exerted on the support structure **114** (i.e., the sum of the moment of the counterweight **402**, the moment of the sled member **104**, and the moment of the sled base **102**) may be kept constant by moving the counterweight **202** back as the sled member **104** advances as illustrated in FIGS. 4b and 4C. In this configuration, counterweight **402** may be moved in response to movement of the sled member **104** by one or more pulleys, gears or other devices to control movement similar to the embodiments illustrated in FIGS. 3A through 3D.

[0049] In a further embodiment, a counterweight may be moved by a drive system (e.g., an electric motor) controlled by a control system in response to sensors that detect a need for balancing. For example, one or more sensors may detect weight, pressure, bending stress, strain, deflection of the sled

base or other parameters of one or more components of the catheter positioning system. Based on data from the sensors, the control system may reposition the counterweight accordingly to adjust the magnitude of force applied to the system by the counterweight. The control system may continue making adjustments based on feedback from the sensors until the desired state (e.g., a balanced total moment, zero total moment, a desired steady state response, etc.) is achieved.

[0050] Such an embodiment is illustrated in FIG. 5. A catheter positioning system **500** may include a level sensor **502** and a stress sensor **504** coupled to a control system **506** that controls a counterweight drive mechanism **508**, **510**, **512**. In this example embodiment, a stress sensor **504** capable of detecting when a bending stress is applied to the support structure **114** and/or a level sensor **502** capable of detecting when the sled base **102** is beginning to change its angle of orientation provide sensor data into a control system **506**. The control system **506** may include a processor configured with processor executable instructions or hard-wired control logic to generate a control signal for a drive motor **508** that is configured to reposition the counterweight **202** in order to compensate for the detected bending stress or tilt of the sled base **102**. In the illustrated example, control signals from the control system **506** cause the drive motor **508** to turn a lead screw nut **510** to advance or retract a lead screw **512** coupled to the counterweight **202**; however, any of a variety of drive mechanisms (e.g., wires and pulleys, linear actuators, a motor and drive gear on the counterweight, etc.) may be used in various embodiments.

[0051] In various embodiments, one or more damping systems may be used to stabilize the catheter positioning system. The damping systems may resist motion of the catheter positioning system, thereby preventing any sudden or jerky movements of the sled base, nose cone, or introducer that may cause deflections and interfere with catheter positioning procedures. Damping systems may help counter movement even when the sled member and counterweight are stationary, such as by resisting unintentional movement from bumps or snags.

[0052] In various embodiments a passive damping system may include one or more shock absorbers or dashpots. For example, FIG. 6A illustrates an embodiment system **600** with a passive damping system **602** illustrated as a dashpot. The passive damping system **602** may be coupled to the sled base **102** and a secure surface **604**, such as the operating table **120**, the floor, or any other surface that will remain stationary during the operation and can resist any forces applied to it by the damping system **602** as the damping system resists motion by the sled base **102**. The passive damping system **602** shown in FIG. 6A is linear and directly opposes deflection of the sled base **102**. In alternate embodiments the passive damping system may be a rotational passive damping system configured to resist rotation of the sled base **102** about the support structure **114**. Combinations of linear and rotational passive damping systems may also be used.

[0053] Alternate embodiments include active damping systems featuring motion compensating mechanisms coupled to a control system with sensors. FIG. 6B illustrates an embodiment catheter positioning system **650** with an active damping system **652** securely coupled to a base or surface **604**, such as a secure mounting surface. The active damping system **652** may be or may include a linear actuator

or motor, a rotational actuator or motor, a piezoelectric device, or other electromechanical transducer configured to apply a force to the sled base **102** (or other structure) to resist motions. The active damping system **652** may be controlled by a control system **506** configured to receive movement sensor data from a stress sensor **504** and a level sensor **502**, for example. The control system **506** may include a processor configured with processor executable instructions or hardwired control logic to generate control signals for the active damping system **652** in response to motion/movement sensor data, with the control signals configured to cause the active damping system **652** to push or pull in the opposite direction of any motion/movement detected by the sensors **502**, **504**. The active damping system **652** is shown in FIG. 6B as a linear actuator that directly opposes deflection of the sled base **102**. However, in alternate embodiments the active damping system **652** may be a rotational active damping system, such as a rotational actuator configured to resist rotation of the sled base **102** about the support structure **114**. Combinations of linear and rotational active damping systems may also be used.

[0054] While various embodiments, including preferred embodiments, have been described, the invention is only limited by the scope of the claims. Those skilled in the art will recognize that the methods and systems of the present invention have many applications, may be implemented in many manners and, as such, is not to be limited by the preceding exemplary embodiments and examples. Additionally, the functionality of the components of the preceding embodiments may be implemented in different manners. Further, it is to be understood that the steps in the embodiments may be performed in any suitable order, combined into fewer steps or divided into more steps. Thus, the scope of the present invention covers conventionally known and future developed variations and modifications to the system components described herein, as would be understood by those skilled in the art.

What is claimed is:

1. A catheter positioning device, comprising:
 - a sled member configured to accept a handle of a catheter;
 - a sled base configured to move the sled member along a length of the sled base in order to position the catheter within a patient; and
 - a counterweight moveably coupled to the sled base; and
 - a passive damping system coupled to the sled base and configured to resist movement of the sled base.

2. The catheter positioning device of claim 1, further comprising a drive mechanism coupled to the sled member, the counterweight and the sled base, wherein the counterweight is moveably coupled to the sled base and the drive mechanism is configured so that the counterweight moves along the length of the sled base.

3. The catheter positioning device of claim 2, further comprising:

- a sensor; and

- a control system coupled to the sensor and configured to control the drive mechanism to move the counterweight based on data from the sensor.

4. The catheter positioning device of claim 3, further comprising an active damping system coupled with the control system, and wherein the control system is configured to control the active damping system based on data from the sensor.

5. The catheter positioning device of claim 4, wherein the active damping system comprises a series of liquid filled chambers, an amount of liquid in each chamber of the series of liquid filled chambers is actively controlled based on data from the sensor.

6. The catheter positioning device of claim 2, wherein:
 - the counterweight comprises a series of counterweights moveably coupled to the sled base; and

- the drive mechanism is coupled to the series of counterweights and configured to move the series of counterweights in order to reduce shifting of a center of mass of the sled member, sled base, and the series of counterweights as the sled member is moved along the sled base.

7. The catheter positioning device of claim 2, wherein:
 - the counterweight comprises a series of liquid filled chambers coupled to the sled base; and
 - an amount of a liquid in each of the series of liquid filled chambers is changed in order to reduce shifting of a center of mass of the sled member, sled base, and the series of liquid filled chambers as the sled member is moved along the sled base.

8. The catheter positioning device of claim 2, wherein:
 - the passive damping system comprises a series of liquid filled chambers coupled to the sled base; and
 - an amount of a liquid in each of the series of liquid filled chambers is passively changed for resisting movement of the sled base.

* * * * *