



(51) **International Patent Classification:**
H04J 3/16 (2006.01) **H04W 88/08** (2009.01)
H04L 29/06 (2006.01)

(21) **International Application Number:**
PCT/EP2013/061815

(22) **International Filing Date:**
7 June 2013 (07.06.2013)

(25) **Filing Language:** English

(26) **Publication Language:** English

(30) **Priority Data:**
12175600.1 9 July 2012 (09.07.2012) EP

(71) **Applicant:** ALCATEL LUCENT [FR/FR]; 3 Avenue
Octave Gréard, F-75007 Paris (FR).

(72) **Inventors:** JAMOND, Jean-François; c/o Alcatel-Lucent
France, Centre de Villardaux, Route de Villejust, F-91620
Nozay (FR). FROGER, Emmanuel; c/o Alcatel-Lucent
France, Centre de Villardaux, Route de Villejust, F-91620
Nozay (FR). KLEIN, Olivier; c/o Alcatel-Lucent France,
Centre de Villardaux, Route de Villejust, F-91620 Nozay
(FR). THOMANN, Olivier; c/o Alcatel-Lucent France,
Centre de Villardaux, Route de Villejust, F-91620 Nozay
(FR).

(74) **Agent:** THERIAS, Philippe; 32 Avenue Kléber, F-92700
Colombes (FR).

(81) **Designated States** (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME,
MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ,
OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC,
SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) **Designated States** (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) **Title:** METHODS AND DEVICE FOR PROCESSING DIGITAL DATA FRAMES AND TRANSPORT FRAMES FOR RE-
DUCTION OF TRANSPORT BANDWIDTH




FIG.1

(57) **Abstract:** A device (D1) is intended for processing digital data frames to be transmitted by a transport network (TN), and comprises i) a first processing means (PM1) comprising ports for receiving digital data frames and arranged for downsizing, then compressing, if necessary, and then compacting each one of these received digital data frames to produce reduced digital data frames, ii) a second processing means (PM2) arranged for aggregating at least some of these reduced digital data frames together according to aggregation information to produce frame groups, and iii) a third processing means (PM3) arranged for grouping these frame groups together with a group descriptor, defining initial arrangements of the digital data frames, according to grouping information, to produce a transport frame to be transmitted by the transport network (TN).

METHODS AND DEVICE FOR PROCESSING DIGITAL DATA FRAMES AND TRANSPORT FRAMES FOR REDUCTION OF TRANSPORT BANDWIDTH

5 **Technical field**

The present invention relates to telecommunications, and more precisely to process of digital data frames to be transmitted by a transport network and of transport frames that have been transmitted by a transport network.

10

Background of the invention

Many telecommunication systems comprises base band units (or BBUs), also named remote equipment controllers (or RECs) in the CPRI (Common Public Radio Interface) terminology, that are coupled to remote radio-heads (or RRHs), also named remote equipments (or REs) in the CPRI
15 terminology, via a (digital) transport network. Digitised base band complex in-phase (I) and quadrature phase (Q) samples defining data are transported over this transport network.

More precisely, these IQ samples are into (AxC) containers of digital
20 data frames, for instance of the CPRI type and generated by the remote equipment controllers and the remote equipments. These digital data frames are processed before being integrated into transport frames that a transport network is able to transport. This process usually consists in a bandwidth requirement optimisation and a rate adaptation between the IQ sampling rate
25 and the transport network rate. For instance, in case where the transport network is an optical transport network (or OTN), the CPRI digital data frames are encapsulated into transport frames named optical transport units (or OTUs).

The OTN may be, for example, a Passive Optical Network (PON), for example a 10 Gigabit Passive Optical Network (10GPON), a Wave Division
30 Multiplex Passive Optical Network (WDM PON), a WDM overlay to a 10GPON, a CDWM optical ring, or a DWDM optical ring.

In an optical transport network, optical fibres can be used as point-to-point links between remote radio-heads and base band units. Typically, when a base band unit controls N remote radio-heads, there may be N optical fibres coupling this base band unit to these remote radio-heads.

5 As it is not always possible to daisy-chain the remote radio-heads and to share the physical links used, more and more dedicated links are required and the available bandwidth is not used efficiently.

Moreover, the CPRI bit stream is carried as a constant bit rate stream, and there is no solution that optimizes either the line coding and/or the
10 bandwidth required to carry the payloads of the CPRI digital data frames and that enables aggregation and multiplexing of CPRI links.

Summary of the invention

So, an objective of the invention is to improve the situation, and notably
15 to allow links aggregation and multiplexing in an efficient and transparent manner (for instance with a small overhead and/or with adaptation of bandwidth requirements to the actual link usage but not to its maximum capacity).

More precisely, the invention provides a first method, intended for processing digital data frames to be transmitted by a transport network, and
20 comprising:

- a step (i) during which these digital data frames are downsized, then compressed if necessary and then compacted to produce reduced digital data frames,
- a step (ii) during which at least some of these reduced digital data frames are
25 aggregated together according to aggregation information to produce frame groups, and
- a step (iii) during which these frame groups are grouped together with a group descriptor, defining initial arrangements of the digital data frames, according to grouping information, to produce a transport frame to be
30 transmitted by the transport network.

The first method according to the invention may include additional characteristics considered separately or combined, and notably:

- the downsizing may comprise reducing the line coding overhead of each digital data frame, while keeping errors of transmission;
- 5 - the optional compression may comprise scaling blocks of samples by a scaling factor and quantising these scaled blocks of samples to produce compressed samples;
- the compacting may comprise clearing from unused data bytes each one of the digital data frames;
- 10 - in step (i), in case where the digital data frames have been encoded according to a 8B/10B line coding, one may transform each one of these digital data frames into a couple of 8 data bits plus 2 control bits (8+2B);
- in step (ii) one may apply a 64B/65B encoding to data containers contained into the frame groups before aggregating them into the transport frame;
- 15 - the digital data frames may be common public radio interface (CPRI) data frames;
- the transport frame may be an optical data unit configured for transport by an optical transport network (OTN).

The invention also provides a second method, intended for processing
20 a transport frame transmitted by a transport network, and comprising:

- a step (a) during which, after having received a transport frame produced by the first method above introduced, one de-groups frame groups it comprises,
- a step (b) during which one de-aggregates each of these frame groups to get reduced digital data frames they comprise, and
- 25 - a step (c) during which one un-compacts, then de-compresses (if compressed), and then upsizes each one of these reduced digital data frames according to information contained into a group descriptor of the transport frame to get digital data frames.

The second method according to the invention may include additional
30 characteristics considered separately or combined, and notably:

- in step (b), in case where the de-grouped frame groups contain data containers encoded by means of a 64B/65B encoding, one may apply a 64B/65B decoding to these data containers;
- in step (c), in case where the digital data frames are 8+2B digital data frames, one may transform them into 8B/10B digital data frames;
- the transport frame may be an optical data unit transported by an optical transport network (OTN);
- the digital data frames may be common public radio interface data frames.

The invention also provides a device, intended for processing digital data frames to be transmitted by a transport network, and comprising:

- a first processing means comprising ports for receiving digital data frames and arranged for downsizing, then compressing (if needed) and then compacting each one of these received digital data frames to produce reduced digital data frames,
- a second processing means arranged for aggregating at least some of these reduced digital data frames together according to aggregation information to produce frame groups, and
- a third processing means arranged for grouping these frame groups together with a group descriptor, defining initial arrangements of the digital data frames, according to grouping information, to produce a transport frame to be transmitted by the transport network.

This third processing means may be arranged, after having received a transport frame, for de-grouping the frame groups it comprises, and this second processing means may be arranged for de-aggregating each of these frame groups to get reduced digital data frames they comprise. Moreover, the first processing means may be arranged for un-compacting, then de-compressing, and then un-downsizing each one of the reduced digital data frames according to information contained into the group descriptor of the transport frame to get digital data frames.

Brief description of the figures

Other features and advantages of the invention will become apparent on examining the detailed specifications hereafter and the appended drawings, wherein:

- 5 - figure 1 schematically and functionally illustrates an example of telecommunication system comprising two processing devices according to the invention,
- figure 2 schematically and functionally illustrates an example of embodiment of a processing device according to the invention,
- 10 - figure 3 schematically illustrates a first example of a CPRI digital data frame before any processing,
- figure 4 schematically illustrates the CPRI digital data frame of figure 3 after downsizing and compression,
- figure 5 schematically illustrates the CPRI digital data frame of figure 4 after compacting (which forms a reduced CPRI digital data frame),
- 15 - figure 6 schematically illustrates a second example of a reduced CPRI digital data frame (i.e. after processing (downsizing, compression and compacting)),
- figure 7 schematically illustrates a third example of a reduced CPRI digital data frame,
- 20 - figure 8 schematically illustrates an example of frame group comprising the reduced CPRI digital data frames of figures 5 and 6,
- figure 9 schematically illustrates an example of transport frame comprising the frame group of figure 8 and other frame groups,
- 25 - figure 10 schematically illustrates the CPRI digital data frame of figure 4 after an auxiliary transformation into a 8+2B frame, and
- figure 11 schematically illustrates an example of a corresponding 64B/65B encoding issued of a 8 + 2B encoded data frame.

Detailed description of the preferred embodiment

The appended drawings may serve not only to complete the invention, but also to contribute to its understanding, if need be.

The invention aims, notably, at offering first and second processing
5 methods, and an associated processing device D_i ($i = 1$ or 2), intended for processing digital data frames F_m to be transmitted by a transport network TN and transport frames TF that have been transmitted by a transport network TN .

In the following description it will be considered that the transport
network TN is an optical transport network (OTN). For instance, it may be a
10 Passive Optical Network (or PON - for instance a 10 Gigabit Passive Optical Network (10GPON)), a Wave Division Multiplex Passive Optical Network (WDM PON), a WDM overlay to a 10GPON, a CDWM optical ring, or a DWDM optical ring. But the invention is not limited to this type of transport network (point to point wireless connection).

15 An example of telecommunication system capable of implementing the invention is illustrated in figure 1. This (telecommunication) system comprises a transport network TN (here of the OTN type) to which are coupled first D_1 and second D_2 processing devices according to the invention. The first processing device D_1 is coupled to M remote radio-heads (or RRHs) RE_m (with $m = 1$ to M)
20 through M links L_m . For instance and as illustrated, at least one of these remote radio-heads RE_m (here RE_1) can be also coupled to another remote radio-head RE' . The second processing device D_2 is coupled to one or more base band units (or BBUs) EC through at least M links L_m . These processing device D_i ($i = 1$ or 2) can be seen as communication interfaces or link aggregators.

25 The base band unit EC and the remote radio-heads RE_m are capable of generating and using digital data frames F_m containing (AxC) containers C_n , made of IQ samples (compressed or uncompressed). So they deliver on their respective ports (connected to the links L_m) digital data frames F_m that must be transported by the transport network TN into transport frames TF after
30 processing according to a first method, and they receive on their respective ports digital data frames F_m resulting from processing according to a second

method of transport frames TF that have been transported by the transport network TN.

In the following description it will be considered that the digital data frames Fm are CPRI digital data frames. But the invention is not limited to this type of digital data frames. Indeed it also concerns Ethernet frames and HDLC frames, for instance (it could be effectively a packet link encapsulated in a switched link such as an ODU frame). So, the base band unit EC is a remote equipment controller, and the remote radio-heads REm are remote equipments.

The first processing method, according to the invention, comprises three steps (i), (ii) and (iii), which may be implemented by a processing device Di (i = 1 or 2).

The first step (i) begins when the device Di receives digital data frames Fm on its ports connected respectively to the M links Lm.

A non-limiting example of a first digital data frame BF1 is illustrated in figure 3. In this example, the first digital data frame F1 comprises, notably and classically, a control word CW and a payload DB comprising IQ data contained into AxC containers (here C1, C2 and C3, n= 1 to 3) of different sizes.

In this first step (i), downsizing (i.e. removing line code) and compression of the IQ samples, if needed, is performed (figure 4) for each digital data frame Fm, and then each frame Fm is compacted (figure 5) to produce a reduced digital data frame RFm. Two other examples F2 and F3 of reduced digital data frames are respectively illustrated in figures 6 and 7.

This first step (i) may be carried out by a first processing means PM1 of the (processing) device Di. To this effect, this first processing means PM1 may comprise M sub processing means SM1m respectively connected to the M ports of the device Di that are connected respectively to the M links Lm.

As illustrated, each sub processing means SM1m may comprise a pre-processing means PPM arranged, at least, for downsizing (removal of line code) each digital data frame Fm it receives. For instance, this downsizing may comprise removing overhead of each digital data frame Fm, while keeping errors of transmission by decoding the digital data frame Fm when a digital data frame Fm has been encoded according to a line coding such as a 8B/10B. In

this case, for each decoded byte, control bits will be forwarded by the pre-processing means PPM to the other processing means (PM2 and PM3). These control bits will characterize the actual decoded byte: valid data byte, invalid data byte, or special character. These control bits will be used by the 64B/65B encoder.

Each sub processing means SM1m may also comprise a size reduction means SRM arranged, at least, for compressing the content of each downsized digital sample container (or block of samples) it receives to produce a compressed digital data frame CFm (see figure 4, C1, C2 compressed, C3 unchanged). For instance, this compression may comprise frequency down-sampling, scaling blocks of samples by a scaling factor and quantising these scaled blocks of samples to produce compressed samples and therefore generate a compressed digital data frame CFm.

Each sub processing means SM1m may further comprise a packing/unpacking means UPM arranged for compacting (or packing) each compressed digital data frame CFm it receives to produce a reduced digital data frame RFm (see figure 5, 6 or 7). For instance, this compacting comprises clearing from unused data bytes in every data frame CFm (rounded to an integer number of bytes), and therefore generates reduced digital data frames RFm.

It is important to note that, when a digital data frame Fm has been encoded according to a 8B/10B (or 8 bits/10 bits) encoding, it can be advantageously transformed into a 8+2B digital data frame after downsizing and before compression. Here, the expression "8+2B" means a couple of 8 bits of data plus 2 control bits characterizing the actual decoded byte: valid data byte, invalid data byte due to transmission error (EI : Error Indicator), or special character (e.g. CPRI Sync byte/K28.5, indicator KCI). These control bits will be forwarded by the pre-processing means PPM to the other processing means (PM2 and PM3) and will be used by the 64B/65B encoder.

CPRI specifications use of 8B/10B line coding because it provides sufficient transition density within the bit stream for the data clock recovery and ensures a good DC (Direct Current) balance (i.e. the ratio of "0" and "1" on the

line is the same). Indeed 8B/10B encoding allows to carry special characters and to provide transmission error detection. This is required to not disturb the CPRI layer 1 synchronization procedures (i.e. line rate auto-negotiation and LOS (Loss Of Signal) and LOF (Loss Of Frame) detection).

5 In the second step (ii) of the first method, at least some of the reduced digital data frames RF_m are aggregated together according to aggregation information in order to produce frame groups FG_k ($k = 1$ to K or $K+1$, where K depends on the output bitrate and the choice of K or $K+1$ depends if or if not the input bitrate is an integer multiple of the output bitrate).

10 A first example of frame group FG₁ is illustrated in figure 8. As illustrated, in this first example the frame group FG₁ comprises the first RF₁ and second RF₂ reduced digital data frames illustrated in figures 5 and 6. It is important to note that a frame group FG_k may comprise one or more aggregated reduced digital data frames RF_m. Each frame group FG_k comprises
15 the same set of aggregated reduced digital data frames RF_m. The sequence made of K or $K+1$ frame group FG_k is the basic frame sent on the transport network to a common destination device D_i through the same physical link.

This second step (ii) may be carried out by a second processing means PM₂ of the (processing) device D_i. To this effect and as illustrated in figure 2,
20 this second processing means PM₂ may comprise an aggregation means AM arranged for aggregating together reduced digital data frames RF_m it receives to produce a frame group FG_k according to grouping information it comprises or to which it has access (see figure 8).

Preferably, during the second step (ii) a 64B/65B encoding is applied to
25 the AxC data containers contained into the frame groups FG_k before they are aggregated into a transport frame TF.

As illustrated in figure 11, an 8B/10B encoded sequence of 8 given bytes (6 valid data bytes, 1 control character and 1 invalid data byte), requiring 80 bits using 8B/10B, can be described in only 65 bits using 64B/65B coding.
30 The leading bit L indicates that there is at least one special character describe in the following bytes. The first bit value (1) of the first byte indicates that there is at least one more special character described after this one. The following 3

bits of the first byte indicate the offset (001) of this special character in the initial byte sequence. The last 4 bits are the encoded value of the 8B/10B special character. For the second byte, the first bit value (0) indicates that there is no more special character described after this one. The following 3 bits of the second byte indicate the offset (100) of this special character in the initial byte sequence. The last 4 bits are the encoded value of the 8B/10B special character. As the second byte indicated that there is no more special characters in this 8 bytes sequence, the following 6 bytes are the 6 remaining bytes of the original sequence given in chronological order.

10 As illustrated in figure 2, this auxiliary 64B/65B encoding may be carried out by encoding/decoding means EDM_j ($j = 1$ to J) of the second processing means PM2.

In the third step (iii) of the first method, K or $K+1$ frame groups FG_k are grouped together with a group descriptor GD according to grouping information, to produce a transport frame TF that must be transmitted by the transport network TN. This group descriptor GD defines initial arrangements of the initial digital data frames F_m that a frame group FG_k comprises in a reduced format. In other words a group descriptor GD contains any information useful to a device Di to recover initial digital data frames F_m from a frame group FG_k de-
20 grouped from a transport frame TF. A transport frame TF is an optical data unit (ODU).

An example of transport frame TF is illustrated in figure 9. It comprises a group descriptor GD followed by the first frame group FG1 (here RF1 + RF2), which is followed by stuffing bits SB, which are followed by the second frame group FG2, which is followed by stuffing bits SB, and so on till the last frame group FGK (but it could be also FGK+1). But it is possible to have several types of frame groups FG_k on the same link (by the way one for CPRI and another one for Ethernet) with their own K values and their own group descriptor GD.

This third step (iii) may be carried out by a third processing means PM3 of the (processing) device Di. To this effect and as illustrated in figure 2, this
30 third processing means PM3 may comprise at least one grouping means GM_j (j

= 1 to J). Each one of the grouping means GMj ($j = 1$ to J) offers an access to a part of the transport network TN (one grouping means GMj per physical link).

The second method according to the invention can be seen as a reverse method of the first method, i.e. a method allowing recovering of initial
5 digital data frames Fm from a received transport frame TF.

More precisely, this second method comprises three steps (a), (b) and (c).

The first step (a) begins when the device Di receives a transport frame TF on a port connected to the transport network TN.

10 In this first step (a) the received transport frame TF (produced by a first method) is processed to de-group frame groups FGk it comprises.

This de-grouping being the reverse function of the frame group grouping, it can be carried out by the third processing means PM3 of the (processing) device Di, and more precisely by its grouping means GMj ($j = 1$ to
15 J).

In the second step (b) of the second method, each de-grouped frame group FGk is de-aggregated to get the reduced digital data frames RFm it comprises.

This de-aggregation being the reverse function of the reduced digital data frame aggregation, it can be carried out by the second processing means PM2 of the (processing) device Di, and more precisely by its aggregation means AM.
20

In case where the de-grouped frame groups FGk contain AxC containers encoded by means of the 64B/65B encoding, a 64B/65B decoding is applied to these AxC containers by the second processing means PM2 of the (processing) device Di, and more precisely by its encoding/decoding means EDMj, before the de-aggregation.
25

In the third step (c) of the second method, each de-aggregated reduced digital data frame RFm is un-compacted, then de-compressed if needed, and then upsized according to information contained into the group descriptor GD that was initially contained into the received transport frame TF to get (or
30 recover) the initial digital data frames Fm.

This un-compacting being the reverse function of the compressed digital data frame compacting, it can be carried out by the first processing means PM1 of the (processing) device Di, and more precisely by its packing/unpacking means PUM. Moreover, the de-compression being the reverse function of the downsized digital data frame compression, it can be carried out by the first processing means PM1 of the (processing) device Di, and more precisely by its size reduction means SRM. More, the un-downsizing being the reverse function of the digital data frame downsizing, it can be carried out by the first processing means PM1 of the (processing) device Di, and more precisely by its pre-processing means PPM.

In case where the de-compressed digital data frames F'm are 8+2B digital data frames, a 8B/10B decoding is applied to them by the first processing means PM1 of the (processing) device Di, and more precisely by its pre-processing means PPM, before the un-downsizing.

The first PM1, second PM2 and third PM3 processing means of the device Di can be made of software modules, or of a combination of hardware and software modules. So, a device Di can be a computer program product that can be stored or used into a communication interface (or equipment).

The invention allows saving some connectivity (mainly optical fibers) and reducing transport bandwidth in the deployment of a transport network. Moreover, it allows reuse of an existing optical transport network instead of deploying new optical fibres.

The invention is not limited to the embodiments of processing methods and processing device described above, only as examples, but it encompasses all alternative embodiments which may be considered by one skilled in the art within the scope of the claims hereafter.

CLAIMS

1. Method for processing digital data frames to be transmitted by a transport network (TN), said method comprising a step (i) during which digital data frames are downsized, then compressed if necessary and then compacted to produce reduced digital data frames, a step (ii) during which at least some of said reduced digital data frames are aggregated together according to aggregation information to produce frame groups, and a step (iii) during which said frame groups are grouped together with a group descriptor, defining initial arrangements of said digital data frames, according to grouping information, to produce a transport frame to be transmitted by said transport network (TN).

2. Method according to claim 1, wherein said downsizing comprises reducing the line coding overhead of each digital data frame, while keeping errors of transmission.

3. Method according to one of claims 1 and 2, wherein said optional compression comprises scaling blocks of samples by a scaling factor and quantising said scaled blocks of samples to produce compressed samples.

4. Method according to one of claims 1 to 3, wherein said compacting comprises clearing from unused data bytes each one of said digital data frames.

5. Method according to one of claims 1 to 4, wherein in step (i), in case where said digital data frames have been encoded according to a 8B/10B line coding, one transforms each one of said digital data frames into a couple of 8 data bits plus 2 control bits.

6. Method according to one of claims 1 to 5, wherein in step (ii) one applies a 64B/65B encoding to data containers contained into said frame groups before aggregating them into said transport frame.

7. Method according to one of claims 1 to 6, wherein said digital data frames are common public radio interface data frames.

8. Method according to one of claims 1 to 7, wherein said transport frame is an optical data unit configured for transport by an optical transport network.

9. Method for processing a transport frame transmitted by a transport network (TN), said method comprising a step (a) during which, after having received a transport frame produced by a method according to one of claims 1 to 8, one de-groups frame groups it comprises, a step (b) during which one de-aggregates each of said frame groups to get reduced digital data frames they comprise, and a step (c) during which one un-compacts, then de-compresses if compressed, and then upsizes each one of said reduced digital data frames according to information contained into a group descriptor of said transport frame to get digital data frames.

10. Method according to claim 9, wherein in step (b), in case where said de-grouped frame groups contain data containers encoded by means of a 64B/65B encoding, one applies a 64B/65B decoding to said data containers.

11. Method according to one of claims 9 and 10, wherein in step (c), in case where said digital data frames are 8+2B digital data frames, one transforms them into 8B/10B digital data frames after having de-compressed them.

12. Method according to one of claims 9 to 11, wherein said transport frame is an optical data unit transported by an optical transport network.

13. Method according to one of claims 9 to 12, wherein said digital data frames are common public radio interface data frames.

14. Device (Di) for processing digital data frames to be transmitted by a transport network (TN), said processing device (Di) comprising i) a first processing means (PM1) comprising ports for receiving digital data frames and arranged for downsizing, then compressing, if needed, and then compacting said received digital data frames to produce reduced digital data frames, ii) a second processing means (PM2) arranged for aggregating at least some of said reduced digital data frames together according to aggregation information to produce frame groups, and iii) a third processing means (PM3) arranged for grouping said frame groups together with a group descriptor, defining initial arrangements of said digital data frames, according to grouping information, to produce a transport frame to be transmitted by said transport network (TN).

15. Device according to claim 14, wherein said third processing means (PM3) is arranged, after having received a transport frame, for de-grouping the frame groups it comprises, said second processing means (PM2) is arranged for de-aggregating each of said frame groups to get reduced digital data frames they comprise, and said first processing means (PM1) is arranged for un-compacting, then de-compressing, and then un-downsizing each one of said reduced digital data frames according to information contained into the group descriptor of said transport frame to get digital data frames.




FIG.1








FIG.2







FIG.8




FIG.9




FIG.10

octet	000	001	010	011	100	101	110	111
client byte stream	D1	K28.5	D2	D3	8B/10B Error	D4	D5	D6

octet	L	000	001	010	011	100	101	110	111
65B code stream	1	1,001, K285	0,100, KERR	D1	D2	D3	D4	D5	D6

FIG.11

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2013/061815

A. CLASSIFICATION OF SUBJECT MATTER
INV. H04J3/16 H04L29/06 H04W88/08
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
H04J H04L H04W

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2007/116046 A1 (LIU SHENG [CN] ET AL) 24 May 2007 (2007-05-24) paragraph [0006] - paragraph [0008]; figure 12a paragraph [0032] - paragraph [0033] paragraph [0035] - paragraph [0036] paragraph [0044] - paragraph [0045] paragraph [0050]	1-15
X	WO 2009/151893 A2 (SAMPLIFY SYSTEMS INC [US]; WEGENER ALBERT W [US]) 17 December 2009 (2009-12-17) paragraph [0051] - paragraph [0052] paragraph [0058] paragraph [0054]; figure 6 ----- -/-	1-15



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

17 July 2013

Date of mailing of the international search report

23/07/2013

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Huber, Oliver

INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2013/061815

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 2 373 116 A1 (HUAWEI TECH CO LTD [CN]) 5 October 2011 (2011-10-05) abstract paragraph [0058] - paragraph [0059] -----	1-15

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2013/061815

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2007116046 A1	24-05-2007	CN 1960231 A US 2007116046 A1	09-05-2007 24-05-2007
WO 2009151893 A2	17-12-2009	CN 102037694 A EP 2281373 A2 JP 2011526095 A KR 20110030474 A US 2011135013 A1 US 2011280209 A1 US 2012008696 A1 US 2012014421 A1 US 2012014422 A1 WO 2009151893 A2	27-04-2011 09-02-2011 29-09-2011 23-03-2011 09-06-2011 17-11-2011 12-01-2012 19-01-2012 19-01-2012 17-12-2009
EP 2373116 A1	05-10-2011	CN 101489156 A EP 2373116 A1 US 2011243071 A1 WO 2010069241 A1	22-07-2009 05-10-2011 06-10-2011 24-06-2010