



US007258430B2

(12) **United States Patent**  
**Silverbrook**

(10) **Patent No.:** **US 7,258,430 B2**  
(45) **Date of Patent:** **\*Aug. 21, 2007**

(54) **INKJET PRINTING MECHANISM WITH A DISPLACEABLE PLATEN ASSEMBLY**

5,412,411 A	5/1995	Anderson et al.
5,757,398 A	5/1998	Anderson et al.
6,172,691 B1	1/2001	Belon et al.
6,318,920 B1	11/2001	Silverbrook
6,488,422 B1 *	12/2002	Silverbrook ..... 400/56
6,966,625 B2 *	11/2005	Silverbrook ..... 347/29

(75) Inventor: **Kia Silverbrook**, Balmain (AU)

(73) Assignee: **Silverbrook Research Pty Ltd**,  
Balmain, New South Wales (AU)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 49 days.

This patent is subject to a terminal disclaimer.

FOREIGN PATENT DOCUMENTS

EP	0598701 A	5/1994
EP	0936077 A	8/1999

(21) Appl. No.: **11/227,240**

(22) Filed: **Sep. 16, 2005**

(65) **Prior Publication Data**

US 2006/0007269 A1 Jan. 12, 2006

**Related U.S. Application Data**

(63) Continuation of application No. 10/974,751, filed on Oct. 28, 2004, now Pat. No. 6,966,625, which is a continuation of application No. 10/296,438, filed as application No. PCT/AU00/00597 on May 24, 2000, now Pat. No. 6,824,242.

(51) **Int. Cl.**

**B41J 2/175** (2006.01)  
**B41J 2/155** (2006.01)

(52) **U.S. Cl.** ..... **347/85; 347/42**

(58) **Field of Classification Search** ..... **347/85, 347/50, 42, 44, 47, 29, 31**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,316,395 A 5/1994 Imai


\* cited by examiner

Primary Examiner—Shih-Wen Hsieh

(57) **ABSTRACT**

An inkjet printing mechanism includes an elongate chassis that spans a print area. An elongate ink distribution assembly is mounted on and extends a length of the chassis. The assembly has an inlet side, an outlet side, a plurality of ink paths that converge laterally to a longitudinally extending central region and a plurality of printhead chip mounting formations in fluid communication with the ink paths. A plurality of printhead chips is mounted in respective mounting formations to receive ink from the ink paths. An elongate platen assembly is mounted on the chassis such that the platen assembly spans the print area. A rotating mechanism rotates the platen assembly with respect to the chassis. A lateral displacement mechanism displaces the body towards and away from the printhead chips.

**7 Claims, 22 Drawing Sheets**






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9a




FIG. 9b




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 22




FIG. 21




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27

**INKJET PRINTING MECHANISM WITH A  
DISPLACEABLE PLATEN ASSEMBLY**

CROSS-REFERENCE TO RELATED  
APPLICATIONS

This application is a Continuation Application of U.S. Ser. No. 10/974,751 filed on Oct. 28, 2004 now U.S. Pat. No. 6,966,625 which is a Continuation Application of U.S. Ser. No. 10/296,438, filed on Nov. 23, 2002, now issued U.S. Pat. No. 6,824,242 which is a 371 of PCT/AU00/00597 filed May 24, 2000, the entire contents of which are herein incorporated by reference.

BACKGROUND OF THE INVENTION

The following invention relates to a rotating platen member for a printer.

More particularly, though not exclusively, the invention relates to a rotating platen member incorporating a platen surface, a capping device and a test print blotter for an A4 pagewidth drop on demand printhead in a printer.

The overall design of a printer in which the rotating platen member can be utilized revolves around the use of replaceable printhead modules in an array approximately 8 inches (20 cm) long. An advantage of such a system is the ability to easily remove and replace any defective modules in a printhead array. This would eliminate having to scrap an entire printhead if only one chip is defective.

A printhead module in such a printer can be comprised of a "Memjet" chip, being a chip having mounted thereon a vast number of thermo-actuators in micro-mechanics and micro-electromechanical systems (MEMS). Such actuators might be those as disclosed in U.S. Pat. No. 6,044,646 to the present applicant, however, there might be other MEMS print chips.

The printhead, being the environment within which the rotating platen member of the present invention is to be situated, might typically have six ink chambers and be capable of printing four color process (CMYK) as well as infra-red ink and fixative. An air pump would supply filtered air to the printhead, which could be used to keep foreign particles away from its ink nozzles. The printhead module is typically to be connected to a replaceable cassette which contains the ink supply and an air filter.

Each printhead module receives ink via a distribution molding that transfers the ink. Typically, ten modules butt together to form a complete eight inch printhead assembly suitable for printing A4 paper without the need for scanning movement of the printhead across the paper width.

The printheads themselves are modular, so complete eight inch printhead arrays can be configured to form printheads of arbitrary width.

Additionally, a second printhead assembly can be mounted on the opposite side of a paper feed path to enable double-sided high speed printing.

CO-PENDING APPLICATIONS

Various methods, systems and apparatus relating to the present invention are disclosed in the following co-pending applications filed by the applicant or assignee of the present invention simultaneously with the present application:

- PCT/AU00/00518, PCT/AU00/00519, PCT/AU00/00520, PCT/AU00/00521,
- PCT/AU00/00522, PCT/AU00/00523, PCT/AU00/00524, PCT/AU00/00525,

- PCT/AU00/00526, PCT/AU00/00527, PCT/AU00/00528, PCT/AU00/00529,
- PCT/AU00/00530, PCT/AU00/00531, PCT/AU00/00532, PCT/AU00/00533,
- 5 PCT/AU00/00534, PCT/AU00/00535, PCT/AU00/00536, PCT/AU00/00537,
- PCT/AU00/00538, PCT/AU00/00539, PCT/AU00/00540, PCT/AU00/00541,
- 10 PCT/AU00/00542, PCT/AU00/00543, PCT/AU00/00544, PCT/AU00/00545,
- PCT/AU00/00547, PCT/AU00/00546, PCT/AU00/00554, PCT/AU00/00556,
- PCT/AU00/00557, PCT/AU00/00558, PCT/AU00/00559, PCT/AU00/00560,
- 15 PCT/AU00/00561, PCT/AU00/00562, PCT/AU00/00563, PCT/AU00/00564,
- PCT/AU00/00565, PCT/AU00/00566, PCT/AU00/00567, PCT/AU00/00568,
- PCT/AU00/00569,
- 20 PCT/AU00/00570, PCT/AU00/00571, PCT/AU00/00572, PCT/AU00/00573,
- PCT/AU00/00574,
- PCT/AU00/00575, PCT/AU00/00576, PCT/AU00/00577, PCT/AU00/00578,
- 25 PCT/AU00/00579, PCT/AU00/00581, PCT/AU00/00580, PCT/AU00/00582,
- PCT/AU00/00587, PCT/AU00/00588, PCT/AU00/00589, PCT/AU00/00583,
- 30 PCT/AU00/00593, PCT/AU00/00590, PCT/AU00/00591, PCT/AU00/00592,
- PCT/AU00/00584, PCT/AU00/00585, PCT/AU00/00586, PCT/AU00/00594,
- 35 PCT/AU00/00595, PCT/AU00/00596, PCT/AU00/00597, PCT/AU00/00598,
- PCT/AU00/00516, PCT/AU00/00517, PCT/AU00/00511, PCT/AU00/00501,
- PCT/AU00/00502, PCT/AU00/00503, PCT/AU00/00504, PCT/AU00/00505,
- 40 PCT/AU00/00506, PCT/AU00/00507, PCT/AU00/00508, PCT/AU00/00509,
- PCT/AU00/005010, PCT/AU00/00512, PCT/AU00/00513, PCT/AU00/00514,
- 45 PCT/AU00/00515

The disclosures of these co-pending applications are incorporated herein by cross-reference.

OBJECTS OF THE INVENTION

50 It is an object of the present invention to provide a rotating platen member incorporating a platen surface, a capping device and a test print blotter for a printer.

It is another object of the present invention to provide a rotating platen member incorporating a platen surface, a capping device and a test print blotter suitable for the pagewidth printhead assembly as broadly described herein.

It is another object of the present invention to provide a rotating platen member incorporating a platen surface, a capping device and a test print blotter for a printhead assembly on which there is mounted a plurality of print chips, each comprising a plurality of MEMS printing devices.

65 It is yet another object of the present invention to provide a method of rotating a platen member incorporating a platen surface, a capping device and a test print blotter in a printer without damaging the printing devices in the printer.

## SUMMARY OF THE INVENTION

According to the invention, there is provided an inkjet printing mechanism which comprises

an elongate chassis which spans a print area;  
 a printhead assembly that is mounted on the elongate chassis, the printhead assembly including an ink distribution assembly and an array of printhead chips mounted on the ink distribution assembly to span the print area; and  
 an elongate platen assembly mounted on the chassis such that the platen assembly spans the print area, the platen assembly comprising

an elongate body that defines a longitudinal platen surface for supporting a print medium during a printing operation carried out on the print medium;

an elongate ink blotting member arranged on the body;  
 a rotating mechanism to rotate the elongate body such that either the platen surface or the ink blotting member is aligned with the array of printhead chips; and

a lateral displacement mechanism to displace the body towards the printhead chips when the blotting member is aligned with the printhead chips and to displace the body away from the printhead when the platen surface is aligned with the printhead chips.

The elongate body may be hollow and may define a longitudinally extending slot, the elongate blotting member being received in the body with a portion extending from the slot.

The platen assembly may include a longitudinally extending capping assembly arranged on the body, the rotating and lateral displacement mechanisms being configured to displace the body towards the printhead chips when the capping assembly is aligned with the printhead chips.

The capping assembly may include a capper housing, a peripheral capper member positioned on the housing and a foam member positioned in the housing to bear against the printhead chips when the body is displaced towards the printhead chips.

The rotating and lateral displacement mechanisms may include a pair of cams on respective ends of the body and a pair of complementary cam follower formations on the chassis to provide necessary lateral movement as the body is rotated into operative positions.

A pair of opposed rail assemblies may be arranged on the chassis and may engage the platen assembly to maintain linear lateral displacement of the platen assembly.

The present invention provides a platen assembly for a printer, comprising:

a chassis to which there is mounted a printhead,  
 a pair of bearing members supported by the chassis and movable toward and away from the printhead,

a body rotatably mounted between said bearing members, the body having a platen surface extending therealong and a capping device extending therealong, the platen surface and capping device being selectively aligned with the printhead upon rotation of the body from one angular orientation to another, and

means to move said bearing members toward and away from said printhead during said rotation of the body so that the body does not damage the printhead.

Preferably the means to move said bearing members toward and away from said printhead comprise a pair of end caps upon the body, each end cap having a cam surface or surfaces that engage with a protrusion affixed to or formed integrally with the chassis.

Preferably the body also includes a blotting device extending therealong.

Preferably the capping device and the blotting device are offset from one another by 120 degrees about the body.

Preferably the bearing members are bearing moldings, each riding upon one or more tracks affixed to the chassis.

Preferably the tracks are straight and parallel so as to allow linear movement of the bearing members and body toward and away from the printhead.

Preferably the bearing members are resiliently biased in a direction toward the printhead.

Preferably the said resilient bias is by means of a spring extending between the respective bearing member and the chassis.

Preferably the body includes a flat portion forming a base for attachment of a capping member, the capping member having a capper house and capper seal member for sealing a nozzle guard of said printhead.

Preferably the blotting device includes a shaped body of blotting material housed within the body and including a part projecting through a longitudinal slot in the body to form an exposed blotting surface.

The present invention also provides a method of capping a printhead in a printer in which there is provided a chassis to which the printhead is mounted, the method comprising:

providing a selectively rotatable platen body alongside the printhead, which platen body includes a platen surface extending therealong and a capping device also extending therealong,

rotating the platen body from an orientation wherein the platen surface is aligned with the printhead to an orientation wherein the capping device is aligned with the printhead, and

causing movement of the platen body away from the printhead during rotation thereof, such that the body does not damage the printhead during rotation.

Preferably the method also serves to absorb ink during a test print phase, wherein said platen body also incorporates a blotting device extending therealong and the method includes rotating the platen body into a position wherein the blotting device is aligned with the printhead.

Preferably the method also includes the step of moving the platen body toward and/or away from the printhead during rotation thereof so as to bring said blotting device into alignment with said printhead.

As used herein, the term "ink" is intended to mean any fluid which flows through the printhead to be delivered to a sheet. The fluid may be one of many different coloured inks, infra-red ink, a fixative or the like.

## BRIEF DESCRIPTION OF THE DRAWINGS

A preferred form of the present invention will now be described by way of example with reference to the accompanying drawings wherein:

FIG. 1 is a front perspective view of a print engine assembly

FIG. 2 is a rear perspective view of the print engine assembly of FIG. 1

FIG. 3 is an exploded perspective view of the print engine assembly of FIG. 1.

FIG. 4 is a schematic front perspective view of a printhead assembly.

FIG. 5 is a rear schematic perspective view of the printhead assembly of FIG. 4.

FIG. 6 is an exploded perspective illustration of the printhead assembly.

FIG. 7 is a cross-sectional end elevational view of the printhead assembly of FIGS. 4 to 6 with the section taken through the centre of the printhead.

FIG. 8 is a schematic cross-sectional end elevational view of the printhead assembly of FIGS. 4 to 6 taken near the left end of FIG. 4.

FIG. 9A is a schematic end elevational view of mounting of the print chip and nozzle guard in the laminated stack structure of the printhead

FIG. 9B is an enlarged end elevational cross section of FIG. 9A

FIG. 10 is an exploded perspective illustration of a printhead cover assembly.

FIG. 11 is a schematic perspective illustration of an ink distribution molding.

FIG. 12 is an exploded perspective illustration showing the layers forming part of a laminated ink distribution structure according to the present invention.

FIG. 13 is a stepped sectional view from above of the structure depicted in FIGS. 9A and 9B,

FIG. 14 is a stepped sectional view from below of the structure depicted in FIG. 13.

FIG. 15 is a schematic perspective illustration of a first laminate layer.

FIG. 16 is a schematic perspective illustration of a second laminate layer.

FIG. 17 is a schematic perspective illustration of a third laminate layer.

FIG. 18 is a schematic perspective illustration of a fourth laminate layer.

FIG. 19 is a schematic perspective illustration of a fifth laminate layer.

FIG. 20 is a perspective view of the air valve molding

FIG. 21 is a rear perspective view of the right hand end of the platen

FIG. 22 is a rear perspective view of the left hand end of the platen

FIG. 23 is an exploded view of the platen

FIG. 24 is a transverse cross-sectional view of the platen

FIG. 25 is a front perspective view of the optical paper sensor arrangement

FIG. 26 is a schematic perspective illustration of a printhead assembly and ink lines attached to an ink reservoir cassette.

FIG. 27 is a partly exploded view of FIG. 26.

#### DETAILED DESCRIPTION OF THE INVENTION

In FIGS. 1 to 3 of the accompanying drawings there is schematically depicted the core components of a print engine assembly, showing the general environment in which the laminated ink distribution structure of the present invention can be located. The print engine assembly includes a chassis 10 fabricated from pressed steel, aluminium, plastics or other rigid material. Chassis 10 is intended to be mounted within the body of a printer and serves to mount a printhead assembly 11, a paper feed mechanism and other related components within the external plastics casing of a printer.

In general terms, the chassis 10 supports the printhead assembly 11 such that ink is ejected therefrom and onto a sheet of paper or other print medium being transported below the printhead then through exit slot 19 by the feed mechanism. The paper feed mechanism includes a feed roller 12, feed idler rollers 13, a platen generally designated as 14, exit rollers 15 and a pin wheel assembly 16, all driven by a stepper motor 17. These paper feed components are

mounted between a pair of bearing moldings 18, which are in turn mounted to the chassis 10 at each respective end thereof.

A printhead assembly 11 is mounted to the chassis 10 by means of respective printhead spacers 20 mounted to the chassis 10. The spacer moldings 20 increase the printhead assembly length to 220 mm allowing clearance on either side of 210 mm wide paper.

The printhead construction is shown generally in FIGS. 4 to 8.

The printhead assembly 11 includes a printed circuit board (PCB) 21 having mounted thereon various electronic components including a 64 MB DRAM 22, a PEC chip 23, a QA chip connector 24, a microcontroller 25, and a dual motor driver chip 26. The printhead is typically 203 mm long and has ten print chips 27 (FIG. 13), each typically 21 mm long. These print chips 27 are each disposed at a slight angle to the longitudinal axis of the printhead (see FIG. 12), with a slight overlap between each print chip which enables continuous transmission of ink over the entire length of the array. Each print chip 27 is electronically connected to an end of one of the tape automated bond (TAB) films 28, the other end of which is maintained in electrical contact with the undersurface of the printed circuit board 21 by means of a TAB film backing pad 29.

The preferred print chip construction is as described in U.S. Pat. No. 6,044,646 by the present applicant. Each such print chip 27 is approximately 21 mm long, less than 1 mm wide and about 0.3 mm high, and has on its lower surface thousands of MEMS inkjet nozzles 30, shown schematically in FIGS. 9A and 9B, arranged generally in six lines—one for each ink type to be applied. Each line of nozzles may follow a staggered pattern to allow closer dot spacing. Six corresponding lines of ink passages 31 extend through from the rear of the print chip to transport ink to the rear of each nozzle. To protect the delicate nozzles on the surface of the print chip each print chip has a nozzle guard 43, best seen in FIG. 9A, with microapertures 44 aligned with the nozzles 30, so that the ink drops ejected at high speed from the nozzles pass through these microapertures to be deposited on the paper passing over the platen 14.

Ink is delivered to the print chips via a distribution molding 35 and laminated stack 36 arrangement forming part of the printhead 11. Ink from an ink cassette 37 (FIGS. 26 and 27) is relayed via individual ink hoses 38 to individual ink inlet ports 34 integrally molded with a plastics duct cover 39 which forms a lid over the plastics distribution molding 35. The distribution molding 35 includes six individual longitudinal ink ducts 40 and an air duct 41 which extend throughout the length of the array. Ink is transferred from the inlet ports 34 to respective ink ducts 40 via individual cross-flow ink channels 42, as best seen with reference to FIG. 7. It should be noted in this regard that although there are six ducts depicted, a different number of ducts might be provided. Six ducts are suitable for a printer capable of printing four color process (CMYK) as well as infra-red ink and fixative.

Air is delivered to the air duct 41 via an air inlet port 61, to supply air to each print chip 27, as described later with reference to FIGS. 6 to 8, 20 and 21.

Situated within a longitudinally extending stack recess 45 formed in the underside of distribution molding 35 are a number of laminated layers forming a laminated ink distribution stack 36. The layers of the laminate are typically formed of micro-molded plastics material. The TAB film 28 extends from the undersurface of the printhead PCB 21, around the rear of the distribution molding 35 to be received

within a respective TAB film recess 46 (FIG. 21), a number of which are situated along a chip housing layer 47 of the laminated stack 36. The TAB film relays electrical signals from the printed circuit board 21 to individual print chips 27 supported by the laminated structure.

The distribution molding, laminated stack 36 and associated components are best described with reference to FIGS. 7 to 19.

FIG. 10 depicts the distribution molding cover 39 formed as a plastics molding and including a number of positioning spigots 48 which serve to locate the upper printhead cover 49 thereon.

As shown in FIG. 7, an ink transfer port 50 connects one of the ink ducts 39 (the fourth duct from the left) down to one of six lower ink ducts or transitional ducts 51 in the underside of the distribution molding. All of the ink ducts 40 have corresponding transfer ports 50 communicating with respective ones of the transitional ducts 51. The transitional ducts 51 are parallel with each other but angled acutely with respect to the ink ducts 40 so as to line up with the rows of ink holes of the first layer 52 of the laminated stack 36 to be described below.

The first layer 52 incorporates twenty four individual ink holes 53 for each of ten print chips 27. That is, where ten such print chips are provided, the first layer 52 includes two hundred and forty ink holes 53. The first layer 52 also includes a row of air holes 54 alongside one longitudinal edge thereof.

The individual groups of twenty four ink holes 53 are formed generally in a rectangular array with aligned rows of ink holes. Each row of four ink holes is aligned with a transitional duct 51 and is parallel to a respective print chip.

The underside of the first layer 52 includes underside recesses 55. Each recess 55 communicates with one of the ink holes of the two centre-most rows of four holes 53 (considered in the direction transversely across the layer 52). That is, holes 53a (FIG. 13) deliver ink to the right hand recess 55a shown in FIG. 14, whereas the holes 53b deliver ink to the left most underside recesses 55b shown in FIG. 14.

The second layer 56 includes a pair of slots 57, each receiving ink from one of the underside recesses 55 of the first layer.

The second layer 56 also includes ink holes 53 which are aligned with the outer two sets of ink holes 53 of the first layer 52. That is, ink passing through the outer sixteen ink holes 53 of the first layer 52 for each print chip pass directly through corresponding holes 53 passing through the second layer 56.

The underside of the second layer 56 has formed therein a number of transversely extending channels 58 to relay ink passing through ink holes 53c and 53d toward the centre. These channels extend to align with a pair of slots 59 formed through a third layer 60 of the laminate. It should be noted in this regard that the third layer 60 of the laminate includes four slots 59 corresponding with each print chip, with two inner slots being aligned with the pair of slots formed in the second layer 56 and outer slots between which the inner slots reside.

The third layer 60 also includes an array of air holes 54 aligned with the corresponding air hole arrays 54 provided in the first and second layers 52 and 56.

The third layer 60 has only eight remaining ink holes 53 corresponding with each print chip. These outermost holes 53 are aligned with the outermost holes 53 provided in the first and second laminate layers. As shown in FIGS. 9A and 9B, the third layer 60 includes in its underside surface a transversely extending channel 61 corresponding to each

hole 53. These channels 61 deliver ink from the corresponding hole 53 to a position just outside the alignment of slots 59 therethrough.

As best seen in FIGS. 9A and 9B, the top three layers of the laminated stack 36 thus serve to direct the ink (shown by broken hatched lines in FIG. 9B) from the more widely spaced ink ducts 40 of the distribution molding to slots aligned with the ink passages 31 through the upper surface of each print chip 27.

As shown in FIG. 13, which is a view from above the laminated stack, the slots 57 and 59 can in fact be comprised of discrete co-linear spaced slot segments.

The fourth layer 62 of the laminated stack 36 includes an array of ten chip-slots 65 each receiving the upper portion of a respective print chip 27.

The fifth and final layer 64 also includes an array of chip-slots 65 which receive the chip and nozzle guard assembly 43.

The TAB film 28 is sandwiched between the fourth and fifth layers 62 and 64, one or both of which can be provided with recesses to accommodate the thickness of the TAB film.

The laminated stack is formed as a precision micro-molding, injection molded in an Acetal type material. It accommodates the array of print chips 27 with the TAB film already attached and mates with the cover molding 39 described earlier.

Rib details in the underside of the micro-molding provides support for the TAB film when they are bonded together. The TAB film forms the underside wall of the printhead module, as there is sufficient structural integrity between the pitch of the ribs to support a flexible film. The edges of the TAB film seal on the underside wall of the cover molding 39. The chip is bonded onto one hundred micron wide ribs that run the length of the micro-molding, providing a final ink feed to the print nozzles.

The design of the micro-molding allow for a physical overlap of the print chips when they are butted in a line. Because the printhead chips now form a continuous strip with a generous tolerance, they can be adjusted digitally to produce a near perfect print pattern rather than relying on very close toleranced moldings and exotic materials to perform the same function. The pitch of the modules is typically 20.33 mm.

The individual layers of the laminated stack as well as the cover molding 39 and distribution molding can be glued or otherwise bonded together to provide a sealed unit. The ink paths can be sealed by a bonded transparent plastic film serving to indicate when inks are in the ink paths, so they can be fully capped off when the upper part of the adhesive film is folded over. Ink charging is then complete.

The four upper layers 52, 56, 60, 62 of the laminated stack 36 have aligned air holes 54 which communicate with air passages 63 formed as channels formed in the bottom surface of the fourth layer 62, as shown in FIGS. 9b and 13. These passages provide pressurised air to the space between the print chip surface and the nozzle guard 43 whilst the printer is in operation. Air from this pressurised zone passes through the micro-apertures 44 in the nozzle guard, thus preventing the build-up of any dust or unwanted contaminants at those apertures. This supply of pressurised air can be turned off to prevent ink drying on the nozzle surfaces during periods of non-use of the printer, control of this air supply being by means of the air valve assembly shown in FIGS. 6 to 8, 20 and 21.

With reference to FIGS. 6 to 8, within the air duct 41 of the printhead there is located an air valve molding 66 formed as a channel with a series of apertures 67 in its base. The

spacing of these apertures corresponds to air passages **68** formed in the base of the air duct **41** (see FIG. 6), the air valve molding being movable longitudinally within the air duct so that the apertures **67** can be brought into alignment with passages **68** to allow supply the pressurized air through the laminated stack to the cavity between the print chip and the nozzle guard, or moved out of alignment to close off the air supply. Compression springs **69** maintain a sealing inter-engagement of the bottom of the air valve molding **66** with the base of the air duct **41** to prevent leakage when the valve is closed.

The air valve molding **66** has a cam follower **70** extending from one end thereof, which engages an air valve cam surface **71** on an end cap **74** of the platen **14** so as to selectively move the air valve molding longitudinally within the air duct **41** according to the rotational positional of the multi-function platen **14**, which may be rotated between printing, capping and blotting positions depending on the operational status of the printer, as will be described below in more detail with reference to FIGS. **21** to **24**. When the platen **14** is in its rotational position for printing, the cam holds the air valve in its open position to supply air to the print chip surface, whereas when the platen is rotated to the non-printing position in which it caps off the micro-apertures of the nozzle guard, the cam moves the air valve molding to the valve closed position.

With reference to FIGS. **21** to **24**, the platen member **14** extends parallel to the printhead, supported by a rotary shaft **73** mounted in bearing molding **18** and rotatable by means of gear **79** (see FIG. 3). The shaft is provided with a right hand end cap **74** and left hand end cap **75** at respective ends, having cams **76**, **77**.

The platen member **14** has a platen surface **78**, a capping portion **80** and an exposed blotting portion **81** extending along its length, each separated by 120°. During printing, the platen member is rotated so that the platen surface **78** is positioned opposite the printhead so that the platen surface acts as a support for that portion of the paper being printed at the time. When the printer is not in use, the platen member is rotated so that the capping portion **80** contacts the bottom of the printhead, sealing in a locus surrounding the microapertures **44**. This, in combination with the closure of the air valve by means of the air valve arrangement when the platen **14** is in its capping position, maintains a closed atmosphere at the print nozzle surface. This serves to reduce evaporation of the ink solvent (usually water) and thus reduce drying of ink on the print nozzles while the printer is not in use.

The third function of the rotary platen member is as an ink blotter to receive ink from priming of the print nozzles at printer start up or maintenance operations of the printer. During this printer mode, the platen member **14** is rotated so that the exposed blotting portion **81** is located in the ink ejection path opposite the nozzle guard **43**. The exposed blotting portion **81** is an exposed part of a body of blotting material **82** inside the platen member **14**, so that the ink received on the exposed portion **81** is drawn into the body of the platen member.

Further details of the platen member construction may be seen from FIGS. **23** and **24**. The platen member consists generally of an extruded or molded hollow platen body **83** which forms the platen surface **78** and receives the shaped body of blotting material **82** of which a part projects through a longitudinal slot in the platen body to form the exposed blotting surface **81**. A flat portion **84** of the platen body **83** serves as a base for attachment of the capping member **80**,

which consists of a capper housing **85**, a capper seal member **86** and a foam member **87** for contacting the nozzle guard **43**.

With reference again to FIG. 1, each bearing molding **18** rides on a pair of vertical rails **101**. That is, the capping assembly is mounted to four vertical rails **101** enabling the assembly to move vertically. A spring **102** under either end of the capping assembly biases the assembly into a raised position, maintaining cams **76,77** in contact with the spacer projections **100**.

The printhead **11** is capped when not in use by the full-width capping member **80** using the elastomeric (or similar) seal **86**. In order to rotate the platen assembly **14**, the main roller drive motor is reversed. This brings a reversing gear into contact with the gear **79** on the end of the platen assembly and rotates it into one of its three functional positions, each separated by 120°.

The cams **76**, **77** on the platen end caps **74**, **75** co-operate with projections **100** on the respective printhead spacers **20** to control the spacing between the platen member and the printhead depending on the rotary position of the platen member. In this manner, the platen is moved away from the printhead during the transition between platen positions to provide sufficient clearance from the printhead and moved back to the appropriate distances for its respective paper support, capping and blotting functions.

In addition, the cam arrangement for the rotary platen provides a mechanism for fine adjustment of the distance between the platen surface and the printer nozzles by slight rotation of the platen **14**. This allows compensation of the nozzle-platen distance in response to the thickness of the paper or other material being printed, as detected by the optical paper thickness sensor arrangement illustrated in FIG. **25**.

The optical paper sensor includes an optical sensor **88** mounted on the lower surface of the PCB **21** and a sensor flag arrangement mounted on the arms **89** protruding from the distribution molding. The flag arrangement comprises a sensor flag member **90** mounted on a shaft **91** which is biased by torsion spring **92**. As paper enters the feed rollers, the lowermost portion of the flag member contacts the paper and rotates against the bias of the spring **92** by an amount dependent on the paper thickness. The optical sensor detects this movement of the flag member and the PCB responds to the detected paper thickness by causing compensatory rotation of the platen **14** to optimize the distance between the paper surface and the nozzles.

FIGS. **26** and **27** show attachment of the illustrated printhead assembly to a replaceable ink cassette **93**. Six different inks are supplied to the printhead through hoses **94** leading from an array of female ink valves **95** located inside the printer body. The replaceable cassette **93** containing a six compartment ink bladder and corresponding male valve array is inserted into the printer and mated to the valves **95**. The cassette also contains an air inlet **96** and air filter (not shown), and mates to the air intake connector **97** situated beside the ink valves, leading to the air pump **98** supplying filtered air to the printhead. A QA chip is included in the cassette. The QA chip meets with a contact **99** located between the ink valves **95** and air intake connector **96** in the printer as the cassette is inserted to provide communication to the QA chip connector **24** on the PCB.

The invention claimed is:

1. An inkjet printing mechanism which comprises an elongate chassis that spans a print area; an elongate ink distribution assembly mounted on and extending a length of the chassis and having an inlet

11

side, an outlet side, a plurality of ink paths that converge laterally to a longitudinally extending central region and a plurality of printhead integrated circuit mounting formations in fluid communication with the ink paths, a plurality of printhead integrated circuits mounted in respective mounting formations to receive ink from the ink paths;

an elongate platen assembly mounted on the chassis such that the platen assembly spans the print area;

a rotating mechanism to rotate the platen assembly with respect to the chassis; and

a lateral displacement mechanism to displace the platen assembly towards and away from the printhead integrated circuits.

2. An inkjet printing mechanism as claimed in claim 1, in which a control circuitry component is mounted on the inlet side of the ink distribution assembly and includes control circuitry connected to the printhead integrated circuits to control operation of the printhead integrated circuits.

3. An inkjet printing mechanism as claimed in claim 2, which includes a number of tape automated bond films interposed between respective printhead integrated circuits and said control circuitry components to provide data and control signals to the printhead integrated circuits.

4. An inkjet printing mechanism as claimed in claim 1, in which the elongate platen assembly includes an elongate

12

body that defines a longitudinal platen surface for supporting a print medium during a printing operation carried out on the print medium, the rotating mechanism being configured to rotate the platen surface into and out of an operative position.

5. An inkjet printing mechanism as claimed in claim 4, in which an elongate ink blotting member is arranged on the body such that the blotting member can be brought into and out of alignment with the printhead integrated circuits on rotation of the elongate body by the rotating mechanism.

6. An inkjet printing mechanism as claimed in claim 5, in which the elongate body is hollow and defines a longitudinally extending slot, the elongate blotting member being received in the body with a portion extending from the slot.

7. An inkjet printing mechanism as claimed in claim 4, in which the platen assembly includes a longitudinally extending capping assembly arranged on the body, the rotating and lateral displacement mechanisms being configured to displace the body towards the printhead integrated circuits when the capping assembly is aligned with the printhead integrated circuits.

\* \* \* \* \*