



US012067229B2

(12) **United States Patent**  
**Bernstein et al.**

(10) **Patent No.:** **US 12,067,229 B2**  
(45) **Date of Patent:** **Aug. 20, 2024**

(54) **DEVICE, METHOD, AND GRAPHICAL USER INTERFACE FOR PROVIDING FEEDBACK FOR CHANGING ACTIVATION STATES OF A USER INTERFACE OBJECT**

(71) Applicant: **Apple Inc.**, Cupertino, CA (US)

(72) Inventors: **Jeffrey Traer Bernstein**, San Francisco, CA (US); **Julian K. Missig**, Burlingame, CA (US); **Avi E. Cieplinski**, San Francisco, CA (US); **B. Michael Victor**, Castro Valley, CA (US)

(73) Assignee: **APPLE INC.**, Cupertino, CA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **17/728,909**

(22) Filed: **Apr. 25, 2022**

(65) **Prior Publication Data**

US 2022/0261131 A1 Aug. 18, 2022

**Related U.S. Application Data**

(63) Continuation of application No. 16/921,083, filed on Jul. 6, 2020, now Pat. No. 11,314,407, which is a (Continued)

(51) **Int. Cl.**  
**G06F 3/0484** (2022.01)  
**G06F 3/01** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **G06F 3/0488** (2013.01); **G06F 3/016** (2013.01); **G06F 3/03547** (2013.01);  
(Continued)

(58) **Field of Classification Search**  
CPC ..... G06F 3/0488; G06F 3/016; G06F 3/03547  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,864,520 A 9/1989 Setoguchi et al.  
5,184,120 A 2/1993 Schultz  
(Continued)

FOREIGN PATENT DOCUMENTS

CA 2780765 A1 5/2011  
CN 1356493 A 7/2002  
(Continued)

OTHER PUBLICATIONS

Agarwal, "How to Copy and Paste Text on Windows Phone 8," Guiding Tech, <http://web.archive.org/web/20130709204246/http://www.guidingtech.com/20280/copy-paste-text-windows-phone-8/>, Jul. 9, 2013, 10 pages.

(Continued)


*Primary Examiner* — Linh K Pham

(74) *Attorney, Agent, or Firm* — Morgan, Lewis & Bockius LLP

(57) **ABSTRACT**

An electronic device detects a contact on a touch-sensitive surface of the electronic device, including a first portion of a gesture made with the contact, a second portion of the gesture that follows the first portion, and lift-off of the contact from the touch-sensitive surface during or after the second portion of the gesture. In response to detecting the second portion of the gesture, if a modifier input was detected while detecting the first portion of the gesture made with the contact, the electronic device performs a first operation and generates a first tactile output on the touch-sensitive surface. If the modifier input was not detected while detecting the first portion of the gesture, the electronic device performs a second operation different from the first operation and generates a second tactile output on the touch-sensitive surface, wherein the second tactile output is different from the first tactile output.

**39 Claims, 89 Drawing Sheets**



**Related U.S. Application Data**

continuation of application No. 15/889,115, filed on Feb. 5, 2018, now Pat. No. 10,782,871, which is a continuation of application No. 14/536,141, filed on Nov. 7, 2014, now Pat. No. 9,886,184, which is a continuation of application No. PCT/US2013/040072, filed on May 8, 2013.

(60) Provisional application No. 61/778,287, filed on Mar. 12, 2013, provisional application No. 61/747,278, filed on Dec. 29, 2012, provisional application No. 61/688,227, filed on May 9, 2012.

(51) **Int. Cl.**

- G06F 3/0354** (2013.01)
- G06F 3/0482** (2013.01)
- G06F 3/04842** (2022.01)
- G06F 3/04847** (2022.01)
- G06F 3/0486** (2013.01)
- G06F 3/0488** (2022.01)
- G06F 3/04883** (2022.01)

(52) **U.S. Cl.**

CPC ..... **G06F 3/0482** (2013.01); **G06F 3/04842** (2013.01); **G06F 3/04847** (2013.01); **G06F 3/0486** (2013.01); **G06F 3/04883** (2013.01); **G06F 2203/014** (2013.01)

(56)

**References Cited**

U.S. PATENT DOCUMENTS

5,374,787 A 12/1994 Miller et al.  
 5,428,730 A 6/1995 Baker et al.  
 5,463,722 A 10/1995 Venolia  
 5,510,813 A 4/1996 Makinwa et al.  
 5,555,354 A 9/1996 Strasnick et al.  
 5,559,301 A 9/1996 Bryan, Jr. et al.  
 5,589,855 A 12/1996 Blumstein et al.  
 5,664,210 A 9/1997 Fleming et al.  
 5,710,896 A 1/1998 Seidl  
 5,717,438 A 2/1998 Kim et al.  
 5,793,360 A 8/1998 Fleck et al.  
 5,793,377 A 8/1998 Moore  
 5,801,692 A 9/1998 Muzio et al.  
 5,805,144 A 9/1998 Scholder et al.  
 5,805,167 A 9/1998 Van Cruyningen  
 5,809,267 A 9/1998 Moran et al.  
 5,819,293 A 10/1998 Comer et al.  
 5,825,352 A 10/1998 Bisset et al.  
 5,844,560 A 12/1998 Crutcher et al.  
 5,870,683 A 2/1999 Wells et al.  
 5,872,922 A 2/1999 Hogan et al.  
 5,946,647 A 8/1999 Miller et al.  
 5,956,032 A 9/1999 Argiolas  
 5,973,670 A 10/1999 Barber et al.  
 6,002,397 A 12/1999 Kolawa et al.  
 6,031,989 A 2/2000 Cordell  
 6,088,019 A 7/2000 Rosenberg  
 6,088,027 A 7/2000 Konar et al.  
 6,111,575 A 8/2000 Martinez et al.  
 6,121,960 A 9/2000 Carroll et al.  
 6,208,329 B1 3/2001 Ballare  
 6,208,340 B1 3/2001 Amin et al.  
 6,219,034 B1 4/2001 Elbing et al.  
 6,223,188 B1 4/2001 Albers et al.  
 6,232,891 B1 5/2001 Rosenberg  
 6,243,080 B1 6/2001 Molne  
 6,252,594 B1 6/2001 Xia et al.  
 6,292,233 B1 9/2001 Erba et al.  
 6,300,936 B1 10/2001 Braun et al.  
 6,313,836 B1 11/2001 Russell, Jr. et al.  
 6,396,523 B1 5/2002 Segal et al.  
 6,429,846 B2 8/2002 Rosenberg et al.

6,448,977 B1 9/2002 Braun et al.  
 6,459,442 B1 10/2002 Edwards et al.  
 6,489,978 B1 12/2002 Gong et al.  
 6,512,530 B1 1/2003 Rzepkowski et al.  
 6,563,487 B2 5/2003 Martin et al.  
 6,567,102 B2 5/2003 Kung  
 6,583,798 B1 6/2003 Hoek et al.  
 6,590,568 B1 7/2003 Astala et al.  
 6,661,438 B1 12/2003 Shiraiishi et al.  
 6,734,882 B1 5/2004 Becker  
 6,735,307 B1 5/2004 Volckers  
 6,750,890 B1 6/2004 Sugimoto  
 6,806,893 B1 10/2004 Kolawa et al.  
 6,822,635 B2 11/2004 Shahoian et al.  
 6,906,697 B2 6/2005 Rosenberg  
 6,919,927 B1 7/2005 Hyodo  
 6,943,778 B1 9/2005 Astala et al.  
 7,036,088 B2 4/2006 Tunney  
 7,138,983 B2 11/2006 Wakai et al.  
 7,312,791 B2 12/2007 Hoshino et al.  
 7,411,575 B2 8/2008 Hill et al.  
 7,434,177 B1 10/2008 Ording et al.  
 7,453,439 B1 11/2008 Kushler et al.  
 7,471,284 B2 12/2008 Bathiche et al.  
 7,479,949 B2 1/2009 Jobs et al.  
 7,500,127 B2 3/2009 Fleck et al.  
 7,516,404 B1 4/2009 Colby et al.  
 7,533,352 B2 5/2009 Chew et al.  
 7,552,397 B2 6/2009 Holecek et al.  
 7,577,530 B2 8/2009 Vignalou-Marche  
 7,614,008 B2 11/2009 Ording  
 7,619,616 B2 11/2009 Rimas Ribikauskas et al.  
 7,629,966 B2 12/2009 Anson  
 7,656,413 B2 2/2010 Khan et al.  
 7,683,889 B2 3/2010 Rimas Ribikauskas et al.  
 7,702,733 B2 4/2010 Fleck et al.  
 7,743,348 B2 6/2010 Robbins et al.  
 7,760,187 B2 7/2010 Kennedy  
 7,787,026 B1 8/2010 Flory et al.  
 7,797,642 B1 9/2010 Karam et al.  
 7,801,950 B2 9/2010 Eisenstadt et al.  
 7,812,826 B2 10/2010 Ording et al.  
 7,890,862 B2 2/2011 Kompe et al.  
 7,903,090 B2 3/2011 Soss et al.  
 7,952,566 B2 5/2011 Poupyrev et al.  
 7,956,847 B2 6/2011 Christie  
 7,973,778 B2 7/2011 Chen  
 8,000,694 B2 8/2011 Labidi et al.  
 8,040,142 B1 10/2011 Bokma et al.  
 8,059,104 B2 11/2011 Shahoian et al.  
 8,059,105 B2 11/2011 Rosenberg et al.  
 8,106,856 B2 1/2012 Matas et al.  
 8,125,440 B2 2/2012 Guyot-Sionnest et al.  
 8,125,492 B1 2/2012 Wainwright et al.  
 RE43,448 E 6/2012 Kimoto et al.  
 8,209,628 B1 6/2012 Davidson  
 8,271,900 B2 9/2012 Walizaka et al.  
 8,300,005 B2 10/2012 Tateuchi et al.  
 8,311,514 B2 11/2012 Bandyopadhyay et al.  
 8,325,398 B2 12/2012 Satomi et al.  
 8,363,020 B2 1/2013 Li et al.  
 8,390,583 B2 3/2013 Forutanpour et al.  
 8,423,089 B2 4/2013 Song et al.  
 8,446,376 B2 5/2013 Levy et al.  
 8,446,382 B2 5/2013 Goto et al.  
 8,453,057 B2 5/2013 Stallings et al.  
 8,456,431 B2 6/2013 Victor  
 8,466,889 B2 6/2013 Tong et al.  
 8,482,535 B2 7/2013 Pryor  
 8,499,243 B2 7/2013 Yuki  
 8,504,946 B2 8/2013 Williamson et al.  
 8,508,494 B2 8/2013 Moore  
 8,542,205 B1 9/2013 Keller  
 8,553,092 B2 10/2013 Tezuka et al.  
 8,570,296 B2 10/2013 Birnbaum et al.  
 8,581,870 B2 11/2013 Bokma et al.  
 8,587,542 B2 11/2013 Moore  
 8,593,415 B2 11/2013 Han et al.  
 8,593,420 B1 11/2013 Buuck

(56)

## References Cited

## U.S. PATENT DOCUMENTS

8,625,882 B2	1/2014	Backlund et al.	9,389,722 B2	7/2016	Matsuki et al.
8,638,311 B2	1/2014	Kang et al.	9,395,800 B2	7/2016	Liu et al.
8,665,227 B2	3/2014	Gunawan	9,400,581 B2	7/2016	Bokma et al.
8,669,945 B2	3/2014	Coddington	9,405,367 B2	8/2016	Jung et al.
8,698,765 B1	4/2014	Keller	9,405,428 B2	8/2016	Roh et al.
8,706,172 B2	4/2014	Priyantha et al.	9,417,754 B2	8/2016	Smith
8,713,471 B1	4/2014	Rowley et al.	9,423,938 B1	8/2016	Morris
8,717,305 B2	5/2014	Williamson et al.	9,436,344 B2	9/2016	Kuwabara et al.
8,726,198 B2	5/2014	Rydenhag et al.	9,448,694 B2	9/2016	Sharma et al.
8,743,069 B2	6/2014	Morton et al.	9,451,230 B1	9/2016	Henderson et al.
8,760,425 B2	6/2014	Crisan	9,471,145 B2	10/2016	Langlois et al.
8,769,431 B1	7/2014	Prasad	9,477,393 B2	10/2016	Zambetti et al.
8,773,389 B1	7/2014	Freed	9,542,013 B2	1/2017	Dearman et al.
8,788,964 B2	7/2014	Shin et al.	9,547,436 B2	1/2017	Ohki et al.
8,793,577 B2	7/2014	Schellingerhout et al.	9,569,093 B2	2/2017	Lipman et al.
8,799,816 B2	8/2014	Wells et al.	9,582,178 B2	2/2017	Grant et al.
8,816,989 B2	8/2014	Nicholson et al.	9,600,114 B2	3/2017	Milam et al.
8,830,188 B2*	9/2014	Verthein ..... G06F 3/04847 340/407.1	9,600,116 B2	3/2017	Tao et al.
8,854,316 B2	10/2014	Shenfield	9,612,741 B2	4/2017	Brown et al.
8,872,729 B2	10/2014	Lyons et al.	9,619,076 B2	4/2017	Bernstein et al.
8,872,773 B2	10/2014	Mak et al.	9,619,113 B2	4/2017	Mark
8,875,044 B2	10/2014	Ozawa et al.	9,625,987 B1	4/2017	LaPenna et al.
8,881,062 B2	11/2014	Kim et al.	9,645,722 B1	5/2017	Stasior et al.
8,914,732 B2	12/2014	Jun et al.	9,665,762 B2	5/2017	Thompson et al.
8,932,412 B2	1/2015	Ferragut, II et al.	9,671,943 B2	6/2017	Van Der Velden
8,952,987 B2	2/2015	Momeyer et al.	9,678,571 B1	6/2017	Robert et al.
8,954,889 B2	2/2015	Fujibayashi	9,733,716 B2	8/2017	Shaffer
8,959,430 B1	2/2015	Spivak et al.	9,740,381 B1	8/2017	Chaudhri et al.
8,963,853 B2	2/2015	Sirpal et al.	9,753,527 B2	9/2017	Connell et al.
8,976,128 B2	3/2015	Moore	9,760,241 B1	9/2017	Lewbel
9,026,932 B1	5/2015	Dixon	9,785,305 B2	10/2017	Alonso Ruiz et al.
9,030,419 B1	5/2015	Freed	9,798,443 B1	10/2017	Gray
9,030,436 B2	5/2015	Ikeda	9,804,665 B2	10/2017	DeBates et al.
9,032,321 B1	5/2015	Cohen et al.	9,829,980 B2	11/2017	Lisseman et al.
9,043,732 B2	5/2015	Nurmi et al.	9,891,747 B2	2/2018	Jang et al.
9,046,999 B1	6/2015	Teller et al.	10,037,138 B2	7/2018	Bernstein et al.
9,052,820 B2	6/2015	Jarrett et al.	10,055,066 B2	8/2018	Lynn et al.
9,052,925 B2	6/2015	Chaudhri	10,057,490 B2	8/2018	Shin et al.
9,063,563 B1	6/2015	Gray et al.	10,095,396 B2	10/2018	Kudershian et al.
9,063,731 B2	6/2015	Heo et al.	10,133,388 B2	11/2018	Sudou
9,069,460 B2	6/2015	Moore	10,133,397 B1	11/2018	Smith
9,078,208 B1	7/2015	Dutta et al.	10,180,722 B2	1/2019	Lu
9,086,755 B2	7/2015	Cho et al.	10,222,980 B2	3/2019	Alonso Ruiz et al.
9,086,757 B1	7/2015	Desai et al.	10,235,023 B2*	3/2019	Gustafsson ..... G06F 3/04842
9,086,875 B2	7/2015	Harrat et al.	10,275,087 B1	4/2019	Smith
9,092,058 B2	7/2015	Kasahara et al.	10,331,769 B1	6/2019	Hill et al.
9,098,188 B2	8/2015	Kim	10,386,960 B1	8/2019	Smith
9,104,260 B2	8/2015	Marsden et al.	10,469,767 B2	11/2019	Shikata
9,111,076 B2	8/2015	Park et al.	10,496,151 B2	12/2019	Kim et al.
9,116,569 B2	8/2015	Stacy et al.	10,547,895 B1	1/2020	Morris
9,116,571 B2	8/2015	Zeliff et al.	10,564,792 B2*	2/2020	Kim ..... G06F 3/0488
9,122,364 B2	9/2015	Kuwabara et al.	10,739,896 B2	8/2020	Kim et al.
9,128,605 B2	9/2015	Nan et al.	10,771,274 B2	9/2020	Reimann et al.
9,141,262 B2	9/2015	Nan et al.	10,782,871 B2	9/2020	Bernstein et al.
9,146,914 B1	9/2015	Dhaundiyal	11,112,961 B2*	9/2021	Ikeda ..... G06F 3/0488
9,164,779 B2	10/2015	Brakensiek et al.	2001/0024195 A1	9/2001	Hayakawa et al.
9,170,607 B2	10/2015	Bose et al.	2001/0045965 A1	11/2001	Orbanes et al.
9,170,649 B2	10/2015	Ronkainen	2002/0006822 A1	1/2002	Krintzman
9,178,971 B2	11/2015	Nemoto	2002/0008691 A1	1/2002	Hanajima et al.
9,218,105 B2	12/2015	Mansson et al.	2002/0015064 A1	2/2002	Robotham et al.
9,230,393 B1*	1/2016	Davies ..... G06F 3/016	2002/0042925 A1	4/2002	Ebisu et al.
9,244,562 B1	1/2016	Rosenberg et al.	2002/0054011 A1	5/2002	Bruneau et al.
9,244,576 B1	1/2016	Vadagave et al.	2002/0057256 A1	5/2002	Flack
9,244,601 B2	1/2016	Kim et al.	2002/0101447 A1*	8/2002	Carro ..... G06Q 10/10 715/205
9,244,606 B2	1/2016	Kocienda et al.	2002/0109668 A1	8/2002	Rosenberg et al.
9,246,487 B2	1/2016	Casparian et al.	2002/0109678 A1	8/2002	Marmolin et al.
9,262,002 B2	2/2016	Momeyer et al.	2002/0128036 A1	9/2002	Yach et al.
9,280,286 B2	3/2016	Commarford et al.	2002/0140680 A1	10/2002	Lu
9,304,668 B2	4/2016	Rezende et al.	2002/0140740 A1	10/2002	Chen
9,307,112 B2	4/2016	Molgaard et al.	2002/0163498 A1	11/2002	Chang et al.
9,349,552 B2	5/2016	Huska et al.	2002/0180763 A1	12/2002	Kung
9,361,018 B2	6/2016	Defazio et al.	2002/0186257 A1	12/2002	Cadiz et al.
9,383,887 B1	7/2016	Khafizov et al.	2003/0001869 A1	1/2003	Nissen
9,389,718 B1	7/2016	Letourneur	2003/0013492 A1	1/2003	Bokhari et al.
			2003/0058241 A1	3/2003	Hsu
			2003/0068053 A1	4/2003	Chu
			2003/0086496 A1	5/2003	Zhang et al.
			2003/0112269 A1	6/2003	Lentz et al.

(56)		References Cited			
U.S. PATENT DOCUMENTS					
2003/0117440	A1	6/2003	Hellyar et al.	2006/0224989	A1
2003/0122779	A1	7/2003	Martin et al.	2006/0233248	A1
2003/0128242	A1	7/2003	Gordon	2006/0236263	A1
2003/0151589	A1	8/2003	Bensen et al.	2006/0274042	A1
2003/0184574	A1	10/2003	Phillips et al.	2006/0274086	A1
2003/0189552	A1	10/2003	Chuang et al.	2006/0277469	A1
2003/0189647	A1	10/2003	Kang	2006/0282778	A1
2003/0201914	A1	10/2003	Fujiwara et al.	2006/0284858	A1
2003/0206169	A1	11/2003	Springer et al.	2006/0290681	A1
2003/0222915	A1	12/2003	Marion et al.	2007/0003134	A1
2004/0015662	A1	1/2004	Cummings	2007/0024595	A1
2004/0021643	A1	2/2004	Hoshino et al.	2007/0024646	A1
2004/0056849	A1	3/2004	Lohbihler et al.	2007/0036456	A1
2004/0108995	A1	6/2004	Hoshino et al.	2007/0080953	A1
2004/0138849	A1	7/2004	Schmidt et al.	2007/0113681	A1
2004/0141010	A1	7/2004	Fitzmaurice et al.	2007/0120834	A1
2004/0150631	A1	8/2004	Fleck et al.	2007/0120835	A1
2004/0150644	A1	8/2004	Kincaid et al.	2007/0124699	A1
2004/0155752	A1	8/2004	Radke	2007/0152959	A1
2004/0155869	A1	8/2004	Robinson et al.	2007/0157089	A1
2004/0168131	A1	8/2004	Blumberg	2007/0157173	A1
2004/0174399	A1	9/2004	Wu et al.	2007/0168369	A1
2004/0219969	A1	11/2004	Casey et al.	2007/0168890	A1
2004/0267877	A1	12/2004	Shiparo et al.	2007/0176904	A1
2005/0012723	A1	1/2005	Pallakoff	2007/0182999	A1
2005/0039141	A1	2/2005	Burke et al.	2007/0186178	A1*
2005/0064911	A1	3/2005	Chen et al.	2007/0200713	A1*
2005/0066207	A1	3/2005	Fleck et al.		
2005/0076256	A1	4/2005	Fleck et al.	2007/0222768	A1
2005/0078093	A1	4/2005	Peterson, Jr. et al.	2007/0229455	A1
2005/0091604	A1	4/2005	Davis	2007/0229464	A1
2005/0110769	A1	5/2005	DaCosta et al.	2007/0236450	A1
2005/0114785	A1	5/2005	Finnigan et al.	2007/0236477	A1
2005/0125742	A1	6/2005	Grotjohn et al.	2007/0245241	A1
2005/0134578	A1	6/2005	Chambers et al.	2007/0257821	A1
2005/0156892	A1	7/2005	Grant	2007/0270182	A1
2005/0183017	A1	8/2005	Cain	2007/0271513	A1
2005/0190280	A1	9/2005	Haas et al.	2007/0288862	A1
2005/0204295	A1	9/2005	Voorhees et al.	2007/0294295	A1
2005/0223338	A1	10/2005	Partanen	2007/0299923	A1
2005/0229112	A1	10/2005	Clay et al.	2008/0001924	A1
2005/0283726	A1	12/2005	Lunati	2008/0010610	A1
2005/0289476	A1	12/2005	Tokkonen	2008/0024459	A1
2006/0001650	A1	1/2006	Robbins et al.	2008/0034306	A1
2006/0001657	A1	1/2006	Monney et al.	2008/0034331	A1
2006/0012577	A1	1/2006	Kyrola	2008/0036743	A1
2006/0022955	A1	2/2006	Kennedy	2008/0051989	A1
2006/0026536	A1	2/2006	Hotelling et al.	2008/0052945	A1
2006/0031776	A1	2/2006	Glein et al.	2008/0066010	A1
2006/0036945	A1	2/2006	Radtke et al.	2008/0094367	A1
2006/0036971	A1	2/2006	Mendel et al.	2008/0094368	A1
2006/0059436	A1	3/2006	Nurmi	2008/0094398	A1
2006/0067677	A1	3/2006	Tokiwa et al.	2008/0106523	A1
2006/0101347	A1	5/2006	Runov et al.	2008/0109753	A1
2006/0101581	A1	5/2006	Blanchard et al.	2008/0136790	A1
2006/0109252	A1	5/2006	Kolmykov-Zotov et al.	2008/0155415	A1
2006/0109256	A1	5/2006	Grant et al.	2008/0163119	A1
2006/0119586	A1	6/2006	Grant et al.	2008/0165141	A1
2006/0132455	A1*	6/2006	Rimas-Ribikauskas	2008/0165160	A1
				2008/0168379	A1
				2008/0168395	A1
				2008/0168403	A1
				2008/0168404	A1
				2008/0189605	A1
				2008/0202824	A1
				2008/0204427	A1
				2008/0219493	A1
				2008/0222569	A1
				2008/0225007	A1
				2008/0244448	A1
				2008/0259046	A1
				2008/0263452	A1
				2008/0284866	A1
				2008/0294984	A1
				2008/0297475	A1
				2008/0303795	A1
				2008/0303799	A1
				2008/0307335	A1
2006/0132456	A1	6/2006	Anson	10/2006	Pettiross et al.
2006/0132457	A1	6/2006	Rimas-Ribikauskas et al.	10/2006	Rynderman et al.
2006/0136834	A1	6/2006	Cao et al.	10/2006	Bathiche et al.
2006/0136845	A1	6/2006	Rimas-Ribikauskas et al.	12/2006	Krah et al.
2006/0161861	A1	7/2006	Holecek et al.	12/2006	Forstall et al.
2006/0161870	A1	7/2006	Hotelling et al.	12/2006	Chaudhri et al.
2006/0187215	A1*	8/2006	Rosenberg	12/2006	Barsness et al.
				12/2006	Rekimoto
				12/2006	Ho et al.
				1/2007	Song et al.
				2/2007	Baker et al.
				2/2007	Saarinen et al.
				2/2007	Hooper
				4/2007	Lii
				5/2007	Nishimura et al.
				5/2007	Boillot
				5/2007	Sato
				5/2007	Michaels
				7/2007	Peters
				7/2007	Van Os et al.
				7/2007	Klein et al.
				7/2007	Bruns
				7/2007	Zhao et al.
				8/2007	Russo
				8/2007	Anthony et al.
				8/2007	Schiller
					G06F 3/0486
					715/838
					H04L 67/52
					340/539.13
				9/2007	Geurts et al.
				10/2007	Martin et al.
				10/2007	Hotelling et al.
				10/2007	Colgate et al.
				10/2007	Ryu et al.
				10/2007	Bertram et al.
				11/2007	Son et al.
				11/2007	Gulliksson et al.
				11/2007	Andren et al.
				12/2007	Ording
				12/2007	Finkelstein et al.
				12/2007	Skelly et al.
				1/2008	dos los Reyes et al.
				1/2008	Lim et al.
				1/2008	Poupyrev et al.
				2/2008	Ording
				2/2008	Josephsoon et al.
				2/2008	Westerman et al.
				2/2008	Welsh
				3/2008	Matas et al.
				3/2008	Brodersen et al.
				4/2008	Van De Ven et al.
				4/2008	Ording et al.
				4/2008	Ng et al.
				5/2008	Conrad
				5/2008	Karstens
				6/2008	Hio
				6/2008	Yoon et al.
				7/2008	Kim et al.
				7/2008	Christie
				7/2008	Kocienda et al.
				7/2008	Forstall et al.
				7/2008	Ording et al.
				7/2008	Westerman et al.
				7/2008	Ording
				8/2008	Kay et al.
				8/2008	Philipp et al.
				8/2008	Heesemans et al.
				9/2008	Tadmor
				9/2008	Champion et al.
				9/2008	Nakadaira et al.
				10/2008	Goering et al.
				10/2008	Carsanaro
				10/2008	Tomkins
				11/2008	Mizutani
				11/2008	Ramsay et al.
				12/2008	Woolf et al.
				12/2008	Lowles et al.
				12/2008	Schwesig et al.
				12/2008	Chaudhri et al.

(56)		References Cited					
		U.S. PATENT DOCUMENTS					
2008/0307359	A1	12/2008	Louch et al.	2010/0007926	A1	1/2010	Imaizumi et al.
2008/0307361	A1	12/2008	Louch et al.	2010/0011304	A1	1/2010	Van Os
2008/0317378	A1	12/2008	Steinberg et al.	2010/0013613	A1	1/2010	Weston
2008/0320419	A1	12/2008	Matas et al.	2010/0013777	A1	1/2010	Baudisch et al.
2009/0007017	A1	1/2009	Anzures et al.	2010/0017710	A1	1/2010	Kim et al.
2009/0016645	A1	1/2009	Sako et al.	2010/0020035	A1	1/2010	Ryu et al.
2009/0028359	A1	1/2009	Terada et al.	2010/0020221	A1	1/2010	Tupman et al.
2009/0046110	A1	2/2009	Sadler et al.	2010/0026640	A1	2/2010	Kim et al.
2009/0058828	A1	3/2009	Jiang et al.	2010/0026647	A1	2/2010	Abe et al.
2009/0061837	A1	3/2009	Chaudhri et al.	2010/0039446	A1	2/2010	Hillis et al.
2009/0064031	A1	3/2009	Bull et al.	2010/0044121	A1	2/2010	Simon et al.
2009/0066668	A1	3/2009	Kim et al.	2010/0045619	A1	2/2010	Birnbaum et al.
2009/0073118	A1	3/2009	Yamaji et al.	2010/0057235	A1	3/2010	Wang et al.
2009/0075738	A1	3/2009	Pearce	2010/0058231	A1	3/2010	Duarte et al.
2009/0083665	A1	3/2009	Anttila et al.	2010/0060548	A1	3/2010	Choi et al.
2009/0085878	A1	4/2009	Heubel et al.	2010/0060605	A1	3/2010	Rimas-Ribikauskas et al.
2009/0085881	A1	4/2009	Keam	2010/0061637	A1	3/2010	Mochizuki et al.
2009/0085886	A1	4/2009	Huang et al.	2010/0062803	A1	3/2010	Yun et al.
2009/0089293	A1	4/2009	Garritano et al.	2010/0070908	A1	3/2010	Mori et al.
2009/0100343	A1	4/2009	Lee et al.	2010/0073329	A1	3/2010	Raman et al.
2009/0102804	A1	4/2009	Wong et al.	2010/0083116	A1	4/2010	Akifusa et al.
2009/0102805	A1	4/2009	Meijer et al.	2010/0085302	A1	4/2010	Fairweather et al.
2009/0140985	A1	6/2009	Liu	2010/0085314	A1	4/2010	Kwok
2009/0150775	A1	6/2009	Miyazaki et al.	2010/0085317	A1	4/2010	Park et al.
2009/0158198	A1	6/2009	Hayter et al.	2010/0088596	A1	4/2010	Griffin et al.
2009/0160793	A1	6/2009	Rekimoto	2010/0088634	A1*	4/2010	Tsuruta ..... G06F 3/0481 715/788
2009/0160814	A1	6/2009	Li et al.	2010/0088654	A1	4/2010	Henhoefter
2009/0164905	A1	6/2009	Ko	2010/0102832	A1	4/2010	Bartling et al.
2009/0167507	A1	7/2009	Maenpaa	2010/0110082	A1	5/2010	Myrick et al.
2009/0167508	A1	7/2009	Fadell et al.	2010/0111434	A1	5/2010	Madden
2009/0167509	A1	7/2009	Fadell et al.	2010/0127983	A1	5/2010	Irani et al.
2009/0167701	A1	7/2009	Ronkainen	2010/0128002	A1	5/2010	Stacy et al.
2009/0167704	A1	7/2009	Terlizzi et al.	2010/0138776	A1	6/2010	Korhonen
2009/0169061	A1	7/2009	Anderson et al.	2010/0141606	A1*	6/2010	Bae ..... G06F 3/016 345/173
2009/0178008	A1*	7/2009	Herz ..... G06F 9/542 715/840	2010/0148999	A1	6/2010	Casparian et al.
2009/0187824	A1	7/2009	Hinckley et al.	2010/0149096	A1	6/2010	Migos et al.
2009/0189866	A1	7/2009	Haffenden et al.	2010/0153879	A1	6/2010	Rimas-Ribikauskas et al.
2009/0195959	A1	8/2009	Ladouceur et al.	2010/0156807	A1	6/2010	Stallings et al.
2009/0198767	A1	8/2009	Jakobson et al.	2010/0156809	A1*	6/2010	Nutaro ..... G06F 3/0488 340/407.1
2009/0201260	A1	8/2009	Lee et al.	2010/0156813	A1	6/2010	Duarte et al.
2009/0219294	A1	9/2009	Young et al.	2010/0156818	A1*	6/2010	Burrough ..... G06F 3/04883 345/173
2009/0225037	A1	9/2009	Williamson et al.	2010/0156823	A1	6/2010	Paleczny et al.
2009/0228842	A1	9/2009	Westerman et al.	2010/0156825	A1	6/2010	Sohn et al.
2009/0231453	A1	9/2009	Huang	2010/0156830	A1	6/2010	Homma et al.
2009/0237374	A1	9/2009	Li et al.	2010/0159995	A1	6/2010	Stallings et al.
2009/0244357	A1	10/2009	Huang	2010/0171713	A1	7/2010	Kwok et al.
2009/0247112	A1	10/2009	Lundy et al.	2010/0175023	A1	7/2010	Gatlin et al.
2009/0247230	A1*	10/2009	Lundy ..... G06F 3/0237 455/566	2010/0180136	A1	7/2010	Thompson et al.
2009/0251410	A1	10/2009	Mori et al.	2010/0180225	A1	7/2010	Chiba et al.
2009/0251421	A1	10/2009	Bloebaum	2010/0188327	A1*	7/2010	Frid ..... G06F 3/0483 340/407.2
2009/0256947	A1	10/2009	Ciurea et al.	2010/0199227	A1	8/2010	Xiao et al.
2009/0259975	A1	10/2009	Asai et al.	2010/0211872	A1	8/2010	Rolston et al.
2009/0267906	A1	10/2009	Schroderus	2010/0214135	A1	8/2010	Bathiche et al.
2009/0273563	A1*	11/2009	Pryor ..... G06F 3/016 345/157	2010/0214239	A1	8/2010	Wu
2009/0276730	A1	11/2009	Aybes et al.	2010/0218663	A1	9/2010	Choi
2009/0280860	A1	11/2009	Dahlke	2010/0220065	A1	9/2010	Ma
2009/0282360	A1	11/2009	Park et al.	2010/0225456	A1	9/2010	Eldering
2009/0284478	A1	11/2009	De la Torre Baltierra et al.	2010/0225604	A1	9/2010	Homma et al.
2009/0288032	A1	11/2009	Chang et al.	2010/0231533	A1	9/2010	Chaudhri
2009/0289779	A1	11/2009	Braun et al.	2010/0231534	A1	9/2010	Chaudhri et al.
2009/0293009	A1	11/2009	Meserth et al.	2010/0231539	A1	9/2010	Cruz-Hernandez et al.
2009/0295713	A1	12/2009	Piot et al.	2010/0235118	A1	9/2010	Moore et al.
2009/0295739	A1	12/2009	Nagara	2010/0235726	A1	9/2010	Ording et al.
2009/0295943	A1	12/2009	Kim et al.	2010/0235733	A1	9/2010	Drislane et al.
2009/0298546	A1	12/2009	Kim et al.	2010/0235746	A1	9/2010	Anzures
2009/0303187	A1	12/2009	Pallakoff	2010/0240415	A1	9/2010	Kim et al.
2009/0307583	A1	12/2009	Tonisson	2010/0241955	A1	9/2010	Price et al.
2009/0307633	A1	12/2009	Haughay, Jr. et al.	2010/0248787	A1	9/2010	Smuga et al.
2009/0322893	A1	12/2009	Stallings et al.	2010/0251168	A1	9/2010	Fujita et al.
2009/0325566	A1	12/2009	Bell et al.	2010/0259500	A1	10/2010	Kennedy
2010/0005390	A1*	1/2010	Bong ..... G06F 3/0482 715/702	2010/0271312	A1	10/2010	Alameh et al.
				2010/0271500	A1	10/2010	Park et al.
				2010/0277419	A1	11/2010	Ganey et al.
				2010/0277496	A1	11/2010	Kawanishi et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2010/0281379	A1	11/2010	Meaney et al.	2011/0138295	A1	6/2011	Momchilov et al.
2010/0281385	A1	11/2010	Meaney et al.	2011/0141031	A1	6/2011	McCullough et al.
2010/0287486	A1	11/2010	Coddington	2011/0141052	A1	6/2011	Bernstein et al.
2010/0289807	A1	11/2010	Yu et al.	2011/0144777	A1	6/2011	Firkins et al.
2010/0293460	A1	11/2010	Budelli	2011/0145752	A1	6/2011	Fagans
2010/0295789	A1	11/2010	Shin et al.	2011/0145753	A1	6/2011	Prakash
2010/0295805	A1	11/2010	Shin et al.	2011/0145759	A1	6/2011	Leffert et al.
2010/0302177	A1	12/2010	Kim et al.	2011/0145764	A1	6/2011	Higuchi et al.
2010/0302179	A1	12/2010	Ahn et al.	2011/0149138	A1	6/2011	Watkins
2010/0306702	A1	12/2010	Warner	2011/0154199	A1	6/2011	Maffitt et al.
2010/0308983	A1	12/2010	Conte et al.	2011/0159469	A1	6/2011	Hwang et al.
2010/0309147	A1	12/2010	Fleizach et al.	2011/0163971	A1	7/2011	Wagner et al.
2010/0313050	A1	12/2010	Harrat et al.	2011/0163978	A1	7/2011	Park et al.
2010/0313124	A1	12/2010	Privault et al.	2011/0169765	A1	7/2011	Aono
2010/0313146	A1	12/2010	Nielsen et al.	2011/0175826	A1	7/2011	Moore et al.
2010/0313156	A1	12/2010	Louch et al.	2011/0175832	A1	7/2011	Miyazawa et al.
2010/0313158	A1	12/2010	Lee et al.	2011/0181521	A1	7/2011	Reid et al.
2010/0313166	A1	12/2010	Nakayama et al.	2011/0181526	A1	7/2011	Shaffer et al.
2010/0315417	A1	12/2010	Cho et al.	2011/0181538	A1	7/2011	Aono
2010/0315438	A1	12/2010	Horodezky et al.	2011/0181751	A1	7/2011	Mizumori
2010/0317410	A1	12/2010	Song et al.	2011/0185299	A1	7/2011	Hinckley et al.
2010/0321301	A1	12/2010	Casparian et al.	2011/0185300	A1	7/2011	Hinckley et al.
2010/0321312	A1	12/2010	Han et al.	2011/0185316	A1	7/2011	Reid et al.
2010/0325578	A1	12/2010	Mital et al.	2011/0191675	A1	8/2011	Kauranen
2010/0328229	A1	12/2010	Weber et al.	2011/0193788	A1	8/2011	King et al.
2011/0010626	A1	1/2011	Fino et al.	2011/0193809	A1	8/2011	Walley et al.
2011/0012851	A1	1/2011	Ciesla et al.	2011/0193881	A1	8/2011	Rydenhag
2011/0016390	A1	1/2011	Oh et al.	2011/0197160	A1	8/2011	Kim et al.
2011/0018695	A1	1/2011	Bells et al.	2011/0201387	A1	8/2011	Paek et al.
2011/0026099	A1	2/2011	Kwon et al.	2011/0202834	A1	8/2011	Mandryk et al.
2011/0035145	A1	2/2011	Yamasaki	2011/0202853	A1	8/2011	Mujkic
2011/0037706	A1	2/2011	Pasquero et al.	2011/0202879	A1	8/2011	Stovicek et al.
2011/0038552	A1	2/2011	Lam	2011/0205163	A1	8/2011	Hinckley et al.
2011/0039602	A1	2/2011	McNamara et al.	2011/0209088	A1	8/2011	Hinckley et al.
2011/0047368	A1	2/2011	Sundaramurthy et al.	2011/0209093	A1	8/2011	Hinckley et al.
2011/0047459	A1*	2/2011	Van Der Westhuizen	2011/0209097	A1	8/2011	Hinckley et al.
			G06F 3/04883	2011/0209099	A1	8/2011	Hinckley et al.
			345/173	2011/0209104	A1	8/2011	Hinckley et al.
2011/0050576	A1	3/2011	Forutanpour et al.	2011/0210834	A1	9/2011	Pasquero et al.
2011/0050588	A1	3/2011	Li et al.	2011/0210926	A1	9/2011	Pasquero et al.
2011/0050591	A1	3/2011	Kim et al.	2011/0210931	A1	9/2011	Shai
2011/0050594	A1	3/2011	Kim et al.	2011/0215914	A1	9/2011	Edwards
2011/0050628	A1	3/2011	Homma et al.	2011/0221684	A1	9/2011	Rydenhag
2011/0050629	A1	3/2011	Homma et al.	2011/0221776	A1	9/2011	Shimotani et al.
2011/0050630	A1*	3/2011	Ikeda	2011/0231789	A1	9/2011	Bukurak et al.
			G06F 3/0488	2011/0234491	A1*	9/2011	Nurmi
			345/174				G06F 3/0488
2011/0050653	A1	3/2011	Miyazawa et al.	2011/0234639	A1	9/2011	Shimotani et al.
2011/0050687	A1	3/2011	Alyshev et al.	2011/0238690	A1	9/2011	Arrasvouri et al.
2011/0054837	A1	3/2011	Ikeda	2011/0239110	A1	9/2011	Garrett et al.
2011/0055135	A1	3/2011	Dawson et al.	2011/0242029	A1	10/2011	Kasahara et al.
2011/0055741	A1	3/2011	Jeon et al.	2011/0246801	A1	10/2011	Seethaler et al.
2011/0057886	A1	3/2011	Ng et al.	2011/0246877	A1	10/2011	Kwak et al.
2011/0057903	A1	3/2011	Yamano et al.	2011/0248916	A1	10/2011	Griffin et al.
2011/0061021	A1	3/2011	Kang et al.	2011/0248930	A1*	10/2011	Kwok
2011/0061029	A1	3/2011	Yeh et al.				G06F 3/0488
2011/0063236	A1	3/2011	Arai et al.	2011/0248942	A1	10/2011	Yana et al.
2011/0063248	A1	3/2011	Yoon	2011/0248948	A1	10/2011	Griffin et al.
2011/0069012	A1	3/2011	Martensson	2011/0252346	A1	10/2011	Chaudhri
2011/0069016	A1	3/2011	Victor	2011/0252357	A1	10/2011	Chaudhri
2011/0074697	A1	3/2011	Rapp et al.	2011/0252362	A1	10/2011	Cho et al.
2011/0080349	A1	4/2011	Holbein et al.	2011/0252369	A1	10/2011	Chaudhri
2011/0080350	A1*	4/2011	Almalki	2011/0252380	A1	10/2011	Chaudhri
			G06F 3/0488	2011/0258537	A1	10/2011	Rives et al.
			345/173	2011/0260994	A1	10/2011	Saynac et al.
2011/0080367	A1	4/2011	Marchand et al.	2011/0263298	A1	10/2011	Park
2011/0084910	A1	4/2011	Almalki et al.	2011/0265035	A1	10/2011	Lepage et al.
2011/0087982	A1	4/2011	McCann et al.	2011/0265045	A1	10/2011	Hsieh
2011/0087983	A1	4/2011	Shim	2011/0267530	A1	11/2011	Chun
2011/0093815	A1	4/2011	Gobeil	2011/0279380	A1	11/2011	Weber et al.
2011/0093817	A1	4/2011	Song et al.	2011/0279381	A1	11/2011	Tong et al.
2011/0102829	A1	5/2011	Jourdan	2011/0279395	A1	11/2011	Kuwabara et al.
2011/0107272	A1	5/2011	Aquilar	2011/0279852	A1	11/2011	Oda et al.
2011/0109617	A1	5/2011	Snook et al.	2011/0285656	A1	11/2011	Yaksick et al.
2011/0116716	A1	5/2011	Kwon et al.	2011/0285659	A1	11/2011	Kuwabara et al.
2011/0119610	A1	5/2011	Hackborn et al.	2011/0291945	A1	12/2011	Ewing, Jr. et al.
2011/0126139	A1	5/2011	Jeong et al.	2011/0291951	A1	12/2011	Tong
				2011/0296334	A1	12/2011	Ryu et al.
				2011/0296351	A1	12/2011	Ewing, Jr. et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2011/0304559	A1	12/2011	Pasquero	2012/0192114	A1	7/2012	DeLuca	
2011/0304577	A1	12/2011	Brown et al.	2012/0200528	A1	8/2012	Ciesla et al.	
2011/0310049	A1	12/2011	Homma et al.	2012/0206393	A1	8/2012	Hillis et al.	
2011/0319136	A1	12/2011	Labowicz et al.	2012/0216114	A1	8/2012	Privault et al.	
2012/0001856	A1	1/2012	Davidson	2012/0218203	A1	8/2012	Kanki	
2012/0005622	A1	1/2012	Park et al.	2012/0235912	A1	9/2012	Laubach	
2012/0007857	A1	1/2012	Noda et al.	2012/0236037	A1	9/2012	Lessing et al.	
2012/0011437	A1	1/2012	James et al.	2012/0240044	A1	9/2012	Johnson et al.	
2012/0013541	A1	1/2012	Boka et al.	2012/0242584	A1	9/2012	Tuli	
2012/0013542	A1	1/2012	Shenfield	2012/0242599	A1*	9/2012	Seo .....	G06F 3/04847 345/173
2012/0013607	A1	1/2012	Lee	2012/0245922	A1	9/2012	Koslova et al.	
2012/0019448	A1	1/2012	Pitkanen et al.	2012/0249575	A1	10/2012	Krolczyk et al.	
2012/0023591	A1	1/2012	Sahita et al.	2012/0249853	A1	10/2012	Krolczyk et al.	
2012/0026110	A1	2/2012	Yamano	2012/0250598	A1	10/2012	Lonnfors et al.	
2012/0030623	A1	2/2012	Hoellwarth	2012/0256829	A1	10/2012	Dodge	
2012/0032979	A1	2/2012	Blow et al.	2012/0256846	A1	10/2012	Mak	
2012/0036441	A1	2/2012	Basir et al.	2012/0256847	A1	10/2012	Mak et al.	
2012/0036556	A1	2/2012	LeBeau et al.	2012/0256857	A1	10/2012	Mak	
2012/0038580	A1	2/2012	Sasaki	2012/0257071	A1	10/2012	Prentice	
2012/0044153	A1	2/2012	Arrasvouri et al.	2012/0260208	A1	10/2012	Jung	
2012/0047380	A1	2/2012	Nurmi	2012/0260219	A1	10/2012	Piccolotto	
2012/0056837	A1	3/2012	Park et al.	2012/0260220	A1	10/2012	Griffin	
2012/0056848	A1	3/2012	Yamano et al.	2012/0274578	A1	11/2012	Snow et al.	
2012/0057039	A1	3/2012	Gardiner et al.	2012/0274591	A1	11/2012	Rimas-Ribikauskas et al.	
2012/0060123	A1	3/2012	Smith	2012/0274662	A1	11/2012	Kim et al.	
2012/0062470	A1	3/2012	Chang	2012/0278744	A1	11/2012	Kozitsyn et al.	
2012/0062564	A1	3/2012	Miyashita et al.	2012/0284673	A1	11/2012	Lamb et al.	
2012/0062604	A1	3/2012	Lobo	2012/0293449	A1	11/2012	Dietz	
2012/0062732	A1	3/2012	Marman et al.	2012/0293551	A1	11/2012	Momeyer et al.	
2012/0066630	A1	3/2012	Kim et al.	2012/0297041	A1	11/2012	Momchilov	
2012/0066636	A1*	3/2012	Kaprani .....	2012/0303548	A1	11/2012	Johnson et al.	
			G06F 9/48	2012/0304108	A1	11/2012	Jarrett et al.	
			715/779	2012/0304132	A1	11/2012	Sareen et al.	
2012/0066648	A1	3/2012	Rolleston et al.	2012/0304133	A1	11/2012	Nan et al.	
2012/0081326	A1	4/2012	Heubel et al.	2012/0306632	A1	12/2012	Fleizach et al.	
2012/0081375	A1	4/2012	Robert et al.	2012/0306748	A1	12/2012	Fleizach et al.	
2012/0084644	A1	4/2012	Robert et al.	2012/0306764	A1	12/2012	Kamibeppu	
2012/0084689	A1	4/2012	Ledet et al.	2012/0306765	A1	12/2012	Moore	
2012/0084713	A1	4/2012	Desai et al.	2012/0306766	A1	12/2012	Moore	
2012/0089932	A1	4/2012	Kano et al.	2012/0306772	A1	12/2012	Tan et al.	
2012/0089942	A1	4/2012	Gammon	2012/0306778	A1	12/2012	Wheeldreyer et al.	
2012/0089951	A1	4/2012	Cassidy	2012/0306927	A1	12/2012	Lee et al.	
2012/0092381	A1	4/2012	Hoover et al.	2012/0311429	A1	12/2012	Decker et al.	
2012/0096393	A1	4/2012	Shim et al.	2012/0311437	A1	12/2012	Weeldreyer et al.	
2012/0096400	A1	4/2012	Cho	2012/0311498	A1	12/2012	Kluttz et al.	
2012/0098780	A1	4/2012	Fujisawa et al.	2012/0311504	A1	12/2012	van Os et al.	
2012/0102437	A1	4/2012	Worley et al.	2012/0313847	A1	12/2012	Boda et al.	
2012/0105358	A1	5/2012	Momeyer et al.	2013/0002561	A1	1/2013	Wakasa	
2012/0105367	A1	5/2012	Son et al.	2013/0011065	A1*	1/2013	Yoshida .....	G06F 3/0304 382/187
2012/0106852	A1	5/2012	Khawand et al.	2013/0014057	A1	1/2013	Reinpoldt et al.	
2012/0113007	A1	5/2012	Koch et al.	2013/0016042	A1	1/2013	Makinen et al.	
2012/0113023	A1	5/2012	Koch et al.	2013/0016056	A1	1/2013	Shinozaki et al.	
2012/0126962	A1	5/2012	Ujii et al.	2013/0016122	A1	1/2013	Bhatt et al.	
2012/0131495	A1	5/2012	Goossens et al.	2013/0019158	A1	1/2013	Watanabe	
2012/0139844	A1	6/2012	Ramstein et al.	2013/0019174	A1	1/2013	Gil et al.	
2012/0139864	A1	6/2012	Sleeman et al.	2013/0031514	A1	1/2013	Gabbert	
2012/0144330	A1	6/2012	Flint	2013/0036386	A1	2/2013	Park et al.	
2012/0146945	A1	6/2012	Miyazawa et al.	2013/0042199	A1	2/2013	Fong et al.	
2012/0147052	A1	6/2012	Homma et al.	2013/0044062	A1	2/2013	Bose et al.	
2012/0154303	A1	6/2012	Lazaridis et al.	2013/0047100	A1	2/2013	Kroeger et al.	
2012/0154328	A1	6/2012	Kono	2013/0050131	A1	2/2013	Lee et al.	
2012/0158629	A1	6/2012	Hinckley et al.	2013/0050143	A1	2/2013	Kim et al.	
2012/0159380	A1	6/2012	Kocienda et al.	2013/0050518	A1	2/2013	Takemura et al.	
2012/0162093	A1*	6/2012	Buxton .....	2013/0061172	A1	3/2013	Huang et al.	
			G06F 3/0482	2013/0063364	A1	3/2013	Moore	
			345/173	2013/0063389	A1	3/2013	Moore	
2012/0174042	A1	6/2012	Chang	2013/0067383	A1	3/2013	Kataoka et al.	
2012/0169646	A1	7/2012	Berkes et al.	2013/0067513	A1	3/2013	Takami	
2012/0169716	A1	7/2012	Mihara	2013/0067527	A1	3/2013	Ashbook et al.	
2012/0169768	A1*	7/2012	Roth .....	2013/0069889	A1	3/2013	Pearce et al.	
			G06F 3/0486	2013/0069991	A1	3/2013	Davidson	
			345/629	2013/0074003	A1	3/2013	Dolenc	
2012/0176403	A1	7/2012	Cha et al.	2013/0076649	A1	3/2013	Myers et al.	
2012/0179967	A1	7/2012	Hayes	2013/0076676	A1	3/2013	Gan	
2012/0180001	A1	7/2012	Griffen et al.	2013/0077804	A1	3/2013	Glebe et al.	
2012/0182226	A1	7/2012	Tuli	2013/0082824	A1	4/2013	Colley	
2012/0183271	A1	7/2012	Forutanpour et al.	2013/0082937	A1	4/2013	Liu et al.	
2012/0192108	A1	7/2012	Kolb					

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2013/0086056	A1	4/2013	Dyor et al.	2013/0268875	A1	10/2013	Han et al.
2013/0088455	A1	4/2013	Jeong	2013/0271395	A1	10/2013	Tsai et al.
2013/0093691	A1	4/2013	Moosavi	2013/0275422	A1	10/2013	Silber et al.
2013/0093764	A1	4/2013	Andersson et al.	2013/0278520	A1	10/2013	Weng et al.
2013/0097520	A1	4/2013	Lewin et al.	2013/0293496	A1	11/2013	Takamoto
2013/0097521	A1	4/2013	Lewin et al.	2013/0305184	A1	11/2013	Kim et al.
2013/0097534	A1	4/2013	Lewin et al.	2013/0307790	A1	11/2013	Konttori et al.
2013/0097539	A1	4/2013	Mansson et al.	2013/0307792	A1	11/2013	Andres et al.
2013/0097556	A1	4/2013	Louch	2013/0314359	A1	11/2013	Sudou
2013/0097562	A1	4/2013	Kermoian et al.	2013/0314434	A1	11/2013	Shetterly et al.
2013/0102366	A1	4/2013	Teng et al.	2013/0321340	A1	12/2013	Seo et al.
2013/0111345	A1	5/2013	Newman et al.	2013/0321457	A1	12/2013	Bauermeister et al.
2013/0111378	A1	5/2013	Newman et al.	2013/0325342	A1	12/2013	Pylappan et al.
2013/0111398	A1	5/2013	Lu et al.	2013/0326420	A1	12/2013	Liu et al.
2013/0111415	A1	5/2013	Newman et al.	2013/0326421	A1	12/2013	Jo
2013/0111579	A1	5/2013	Newman et al.	2013/0326583	A1	12/2013	Freihold et al.
2013/0113715	A1	5/2013	Grant et al.	2013/0328770	A1	12/2013	Parham
2013/0113720	A1	5/2013	Van Eerd et al.	2013/0328793	A1	12/2013	Chowdhury
2013/0113760	A1	5/2013	Gossweiler, III et al.	2013/0328796	A1	12/2013	Al-Dahle et al.
2013/0120278	A1	5/2013	Cantrell	2013/0332836	A1	12/2013	Cho
2013/0120280	A1	5/2013	Kukulski	2013/0332892	A1	12/2013	Matsuki
2013/0120295	A1	5/2013	Kim et al.	2013/0335373	A1	12/2013	Tomiyasu
2013/0120306	A1	5/2013	Furukawa	2013/0338847	A1	12/2013	Lissemann et al.
2013/0125039	A1	5/2013	Murata	2013/0339001	A1	12/2013	Craswell et al.
2013/0127755	A1	5/2013	Lynn et al.	2013/0339909	A1	12/2013	Ha
2013/0135243	A1	5/2013	Hirsch et al.	2014/0002355	A1	1/2014	Lee et al.
2013/0135288	A1	5/2013	King et al.	2014/0002374	A1	1/2014	Hunt et al.
2013/0135499	A1	5/2013	Song	2014/0002386	A1	1/2014	Rosenberg et al.
2013/0141364	A1	6/2013	Lynn et al.	2014/0013271	A1	1/2014	Moore et al.
2013/0141396	A1	6/2013	Lynn et al.	2014/0015784	A1	1/2014	Oonishi
2013/0145290	A1	6/2013	Weber et al.	2014/0019786	A1	1/2014	Green et al.
2013/0145313	A1	6/2013	Roh et al.	2014/0024414	A1	1/2014	Fuji
2013/0154948	A1	6/2013	Schediwiy et al.	2014/0026098	A1	1/2014	Gilman
2013/0154959	A1	6/2013	Lindsay et al.	2014/0026099	A1	1/2014	Andersson Reimer et al.
2013/0155018	A1	6/2013	Dagdeviren	2014/0028554	A1	1/2014	De Los Reyes et al.
2013/0159893	A1	6/2013	Lewis et al.	2014/0028571	A1	1/2014	St. Clair
2013/0159930	A1	6/2013	Paretti et al.	2014/0028601	A1	1/2014	Moore
2013/0162603	A1	6/2013	Peng et al.	2014/0028606	A1	1/2014	Giannetta
2013/0162667	A1	6/2013	Eskolin et al.	2014/0035804	A1	2/2014	Dearman
2013/0169549	A1	7/2013	Seymour et al.	2014/0035826	A1	2/2014	Frazier et al.
2013/0174049	A1	7/2013	Townsend et al.	2014/0049491	A1	2/2014	Nagar et al.
2013/0174089	A1	7/2013	Ki	2014/0053116	A1	2/2014	Smith et al.
2013/0174094	A1	7/2013	Heo et al.	2014/0055367	A1	2/2014	Dearman et al.
2013/0174179	A1	7/2013	Park et al.	2014/0055377	A1	2/2014	Kim
2013/0179840	A1	7/2013	Fisher et al.	2014/0059460	A1	2/2014	Ho
2013/0185642	A1	7/2013	Gammons	2014/0059485	A1	2/2014	Lehrian et al.
2013/0187869	A1	7/2013	Rydenhag et al.	2014/0063316	A1	3/2014	Lee et al.
2013/0191791	A1	7/2013	Rydenhag et al.	2014/0063541	A1	3/2014	Yamazaki
2013/0194217	A1	8/2013	Lee et al.	2014/0067293	A1	3/2014	Parivar et al.
2013/0194480	A1	8/2013	Fukata et al.	2014/0068475	A1	3/2014	Li et al.
2013/0198690	A1	8/2013	Barsoum et al.	2014/0071060	A1	3/2014	Santos-Gomez
2013/0201139	A1	8/2013	Tanaka	2014/0072281	A1	3/2014	Cho et al.
2013/0212515	A1	8/2013	Eleftheriou	2014/0072283	A1	3/2014	Cho et al.
2013/0212541	A1	8/2013	Dolenc et al.	2014/0078318	A1	3/2014	Alameh
2013/0215079	A1	8/2013	Johnson et al.	2014/0078343	A1	3/2014	Dai et al.
2013/0222274	A1	8/2013	Mori et al.	2014/0082536	A1	3/2014	Costa et al.
2013/0222323	A1	8/2013	McKenzie	2014/0092025	A1	4/2014	Pala et al.
2013/0222333	A1	8/2013	Miles et al.	2014/0092030	A1	4/2014	Van der Velden
2013/0222671	A1	8/2013	Tseng et al.	2014/0092031	A1	4/2014	Schwartz et al.
2013/0225238	A1	8/2013	He	2014/0108936	A1	4/2014	Khosropour et al.
2013/0227413	A1	8/2013	Thorsander et al.	2014/0109016	A1	4/2014	Ouyang et al.
2013/0227419	A1	8/2013	Lee et al.	2014/0111456	A1	4/2014	Kashiwa et al.
2013/0227450	A1	8/2013	Na et al.	2014/0111480	A1	4/2014	Kim et al.
2013/0228023	A1	9/2013	Drasnin et al.	2014/0111670	A1	4/2014	Lord et al.
2013/0232353	A1	9/2013	Belesiu et al.	2014/0118268	A1	5/2014	Kuscher
2013/0232402	A1	9/2013	Lu et al.	2014/0123080	A1	5/2014	Gan
2013/0234929	A1	9/2013	Libin	2014/0139456	A1	5/2014	Wigdor et al.
2013/0239057	A1	9/2013	Ubillos et al.	2014/0139471	A1	5/2014	Matsuki
2013/0246954	A1	9/2013	Gray et al.	2014/0145970	A1	5/2014	Cho
2013/0249814	A1	9/2013	Zeng	2014/0152581	A1	6/2014	Case et al.
2013/0257793	A1	10/2013	Zeliff et al.	2014/0157203	A1	6/2014	Jeon et al.
2013/0257817	A1	10/2013	Yliaho	2014/0160063	A1	6/2014	Yairi et al.
2013/0263252	A1	10/2013	Lien et al.	2014/0160073	A1	6/2014	Matsuki
2013/0265246	A1	10/2013	Tae	2014/0160168	A1	6/2014	Ogle
2013/0265452	A1	10/2013	Shin et al.	2014/0164955	A1	6/2014	Thiruvidam et al.
				2014/0164966	A1	6/2014	Kim et al.
				2014/0165006	A1	6/2014	Chaudhri et al.
				2014/0168093	A1	6/2014	Lawrence
				2014/0168110	A1	6/2014	Araki et al.



(56)

## References Cited

## U.S. PATENT DOCUMENTS

2016/0196028	A1	7/2016	Kenney et al.
2016/0210025	A1	7/2016	Bernstein et al.
2016/0246478	A1	8/2016	Davis et al.
2016/0259412	A1	9/2016	Flint et al.
2016/0259413	A1	9/2016	Anzures et al.
2016/0259495	A1	9/2016	Butcher et al.
2016/0259496	A1	9/2016	Butcher et al.
2016/0259498	A1	9/2016	Foss et al.
2016/0259499	A1	9/2016	Kocienda et al.
2016/0259516	A1	9/2016	Kudurshian et al.
2016/0259517	A1	9/2016	Butcher et al.
2016/0259518	A1	9/2016	King et al.
2016/0259519	A1	9/2016	Foss et al.
2016/0259527	A1	9/2016	Kocienda et al.
2016/0259528	A1	9/2016	Foss et al.
2016/0259536	A1	9/2016	Kudurshian et al.
2016/0259548	A1	9/2016	Ma
2016/0274686	A1	9/2016	Ruiz et al.
2016/0274728	A1	9/2016	Luo et al.
2016/0274761	A1	9/2016	Ruiz et al.
2016/0283054	A1	9/2016	Suzuki
2016/0306507	A1	10/2016	Defazio et al.
2016/0320906	A1	11/2016	Bokma et al.
2016/0357368	A1	12/2016	Federighi et al.
2016/0357389	A1	12/2016	Dakin et al.
2016/0357390	A1	12/2016	Federighi et al.
2016/0357404	A1	12/2016	Alonso Ruiz et al.
2016/0360116	A1	12/2016	Penha et al.
2017/0045981	A1	2/2017	Karunamuni et al.
2017/0046039	A1	2/2017	Karunamuni et al.
2017/0046058	A1	2/2017	Karunamuni et al.
2017/0046059	A1	2/2017	Karunamuni et al.
2017/0046060	A1	2/2017	Karunamuni et al.
2017/0075520	A1	3/2017	Bauer et al.
2017/0075562	A1	3/2017	Bauer et al.
2017/0075563	A1	3/2017	Bauer et al.
2017/0090617	A1	3/2017	Jang et al.
2017/0090699	A1	3/2017	Pennington et al.
2017/0091153	A1	3/2017	Thimbleby
2017/0109011	A1	4/2017	Jiang
2017/0115867	A1	4/2017	Bargmann
2017/0123497	A1	5/2017	Yonezawa
2017/0124699	A1	5/2017	Lane
2017/0139565	A1	5/2017	Choi
2017/0315694	A1	11/2017	Alonso Ruiz et al.
2017/0357403	A1	12/2017	Geary et al.
2018/0024681	A1	1/2018	Bernstein et al.
2018/0059866	A1	3/2018	Drake et al.
2018/0082522	A1	3/2018	Bartosik
2018/0188920	A1	7/2018	Bernstein et al.
2018/0342103	A1	11/2018	Schwartz et al.
2018/0349362	A1	12/2018	Sharp et al.
2018/0364898	A1	12/2018	Chen
2019/0012059	A1	1/2019	Kwon et al.
2019/0018562	A1	1/2019	Bernstein et al.
2019/0042075	A1	2/2019	Bernstein et al.
2019/0042078	A1	2/2019	Bernstein et al.
2019/0065043	A1	2/2019	Zambetti et al.
2019/0121493	A1	4/2019	Bernstein et al.
2019/0121520	A1	4/2019	Cieplinski et al.
2019/0138101	A1	5/2019	Bernstein
2019/0138102	A1	5/2019	Missig
2019/0138189	A1	5/2019	Missig
2019/0146643	A1	5/2019	Foss et al.
2019/0155503	A1	5/2019	Alonso Ruiz et al.
2019/0158727	A1	5/2019	Penha et al.
2019/0163358	A1	5/2019	Dascola et al.
2019/0171353	A1	6/2019	Missig et al.
2019/0171354	A1	6/2019	Dascola et al.
2019/0212896	A1	7/2019	Karunamuni et al.
2019/0332257	A1	10/2019	Kudurshian et al.
2019/0364194	A1	11/2019	Penha et al.
2019/0391658	A1	12/2019	Missig et al.
2020/0081614	A1	3/2020	Zambetti
2020/0142548	A1	5/2020	Karunamuni et al.
2020/0201472	A1	6/2020	Bernstein et al.
2020/0210059	A1	7/2020	Hu et al.
2020/0218445	A1	7/2020	Alonso Ruiz et al.
2020/0301556	A1	9/2020	Alonso Ruiz et al.
2020/0333936	A1	10/2020	Khoe et al.
2020/0371683	A1	11/2020	Zambetti et al.
2020/0394413	A1	12/2020	Bhanu et al.
2020/0396375	A1	12/2020	Penha et al.
2021/0081082	A1	3/2021	Dascola et al.
2021/0117054	A1	4/2021	Karunamuni et al.
2021/0191602	A1	6/2021	Brown et al.
2021/0191975	A1	6/2021	Lu et al.
2021/0311598	A1	10/2021	Bernstein et al.
2021/0326039	A1	10/2021	Alonso Ruiz et al.
2021/0382613	A1	12/2021	Kudurshian et al.
2022/0011932	A1	1/2022	Khoe et al.
2022/0070359	A1	3/2022	Clarke et al.
2022/0187985	A1	6/2022	Dascola et al.
2022/0365671	A1	11/2022	Bernstein et al.
2023/0133870	A1	5/2023	Penha et al.
2024/0019999	A1	1/2024	Dascola et al.
2024/0103694	A1	3/2024	Foss et al.

## FOREIGN PATENT DOCUMENTS

CN	1534991	A	6/2004
CN	1620327	A	5/2005
CN	1808362	A	7/2006
CN	101068310	A	7/2007
CN	101118469	A	2/2008
CN	101192097	A	6/2008
CN	101202866	A	6/2008
CN	101222704	A	7/2008
CN	101227764	A	7/2008
CN	101241397	A	8/2008
CN	101320303	A	12/2008
CN	101356493	A	1/2009
CN	101384977	A	3/2009
CN	101390039	A	3/2009
CN	101421707	A	4/2009
CN	101464777	A	6/2009
CN	101498979	A	8/2009
CN	101526876	A	9/2009
CN	101527745	A	9/2009
CN	101562703	A	10/2009
CN	101593077	A	12/2009
CN	101609380	A	12/2009
CN	101620507	A	1/2010
CN	101627359	A	1/2010
CN	101630230	A	1/2010
CN	101685370	A	3/2010
CN	101692194	A	4/2010
CN	101727179	A	6/2010
CN	101739206	A	6/2010
CN	101763193	A	6/2010
CN	101784981	A	7/2010
CN	101809526	A	8/2010
CN	101840299	A	9/2010
CN	101896962	A	11/2010
CN	101937304	A	1/2011
CN	101945212	A	1/2011
CN	101952796	A	1/2011
CN	101971603	A	2/2011
CN	101998052	A	3/2011
CN	102004575	A	4/2011
CN	102004576	A	4/2011
CN	102004577	A	4/2011
CN	102004593	A	4/2011
CN	102004602	A	4/2011
CN	102004604	A	4/2011
CN	102016777	A	4/2011
CN	102053790	A	5/2011
CN	102067068	A	5/2011
CN	102112946	A	6/2011
CN	102150018	A	8/2011
CN	102160021	A	8/2011
CN	102171629	A	8/2011
CN	102195514	A	9/2011
CN	102203702	A	9/2011



(56)

## References Cited

## FOREIGN PATENT DOCUMENTS

JP	2005-102106	A	4/2005	JP	2012-053687	A	3/2012
JP	2005-135106	A	5/2005	JP	2012-053754	A	3/2012
JP	2005-157842	A	6/2005	JP	2012-053926	A	3/2012
JP	2005-196810	A	7/2005	JP	2012-073785	A	4/2012
JP	2005-317041	A	11/2005	JP	2012-073873	A	4/2012
JP	2005-352927		12/2005	JP	2012-509605	A	4/2012
JP	2006-059238	A	3/2006	JP	2012-093820	A	5/2012
JP	2006-185443	A	7/2006	JP	2012-118825	A	6/2012
JP	2007-116384	A	5/2007	JP	2012-118993	A	6/2012
JP	2007-148104	A	6/2007	JP	2012-123564	A	6/2012
JP	2007-264808	A	10/2007	JP	2012-128825	A	7/2012
JP	2008-009759	A	1/2008	JP	2012-168620	A	9/2012
JP	2008-015890	A	1/2008	JP	2012-212473	A	11/2012
JP	2008-033739	A	2/2008	JP	2012-527685	A	11/2012
JP	2008-516348	A	5/2008	JP	2013-025357	A	2/2013
JP	2008-146453	A	6/2008	JP	2013-030050	A	2/2013
JP	2008-191086	A	8/2008	JP	2013-058149	A	3/2013
JP	2008-537615	A	9/2008	JP	2013-077270	A	4/2013
JP	2008-305174	A	12/2008	JP	2013-080521	A	5/2013
JP	2009-500761	A	1/2009	JP	2013-093020	A	5/2013
JP	2009-110243	A	5/2009	JP	2013-098826	A	5/2013
JP	2009-129171	A	6/2009	JP	2013-101465	A	5/2013
JP	2009-129443	A	6/2009	JP	2013-105410	A	5/2013
JP	2009-169452	A	7/2009	JP	2013-520727	A	6/2013
JP	2009-211704	A	9/2009	JP	2013-131185	A	7/2013
JP	2009-217543	A	9/2009	JP	2013-529339	A	7/2013
JP	2009-294688	A	12/2009	JP	2013-200879	A	10/2013
JP	2009-545805	A	12/2009	JP	2013-236298	A	11/2013
JP	2010-009321	A	1/2010	JP	2013-542488	A	11/2013
JP	2010-503126	A	1/2010	JP	2013-250602	A	12/2013
JP	2010-503130	A	1/2010	JP	2014-504419		2/2014
JP	2010-055274	A	3/2010	JP	2014-052852	A	3/2014
JP	2010-097353	A	4/2010	JP	2014-130567	A	7/2014
JP	2010-146507	A	7/2010	JP	2014-140112	A	7/2014
JP	2010-152716	A	7/2010	JP	2014-149833	A	8/2014
JP	2010-176174	A	8/2010	JP	2014-519109	A	8/2014
JP	2010-176337	A	8/2010	JP	2014-529137	A	10/2014
JP	2010-181934	A	8/2010	JP	2014-232347	A	12/2014
JP	2010-181940	A	8/2010	JP	2015-099555	A	5/2015
JP	2010-198385	A	9/2010	JP	2015-521315	A	7/2015
JP	2010-536077	A	11/2010	JP	2015-153420	A	8/2015
JP	2010-541071	A	12/2010	JP	2015-185161	A	10/2015
JP	2011-501307	A	1/2011	KR	20020041828	A	6/2002
JP	2011-028635	A	2/2011	KR	2006-0071353	A	6/2006
JP	2011-048023	A	3/2011	KR	2006-0117870	A	11/2006
JP	2011-048666	A	3/2011	KR	100807738	B1	2/2008
JP	2011-048686	A	3/2011	KR	20080026138	A	3/2008
JP	2011-048762	A	3/2011	KR	2008-0045143	A	4/2008
JP	2011-048832	A	3/2011	KR	100823871	B1	4/2008
JP	2011-053831	A	3/2011	KR	2008-0054346	A	6/2008
JP	2011-053972	A	3/2011	KR	2009-0066319	A	6/2009
JP	2011-053973	A	3/2011	KR	2009-0108065	A	10/2009
JP	2011-053974	A	3/2011	KR	2010-0010860	A	2/2010
JP	2011-054196	A	3/2011	KR	2010-0014095	A	2/2010
JP	2011-059821	A	3/2011	KR	2010 0133246	A	12/2010
JP	2011-070342	A	4/2011	KR	2011 0026176	A	3/2011
JP	2011-100290	A	5/2011	KR	2011 0086501	A	7/2011
JP	2011-107823	A	6/2011	KR	20120130972	A	1/2012
JP	2011-123773	A	6/2011	KR	2012 0103670	A	9/2012
JP	2011-141868	A	7/2011	KR	20120135488	A	12/2012
JP	2011-170538	A	9/2011	KR	20120135723	A	12/2012
JP	2011-192179	A	9/2011	KR	20130027017	A	3/2013
JP	2011-192215	A	9/2011	KR	20130076397	A	7/2013
JP	2011-197848	A	10/2011	KR	2013 0099647	A	9/2013
JP	2011-221640	A	11/2011	KR	20130135871	A	12/2013
JP	2011-232947	A	11/2011	KR	2014 0016495	A	2/2014
JP	2011-242386	A	12/2011	KR	2014 0029720	A	3/2014
JP	2011-250004	A	12/2011	KR	2014 0043760	A	4/2014
JP	2011-253556	A	12/2011	KR	2014 0067965	A	6/2014
JP	2011-257941	A	12/2011	KR	2014 0079110	A	6/2014
JP	2011-530101	A	12/2011	KR	2014 0122000	A	10/2014
JP	2012-027940	A	2/2012	KR	20150013263	A	2/2015
JP	2012-033061	A	2/2012	KR	20150021977	A	3/2015
JP	2012-043266	A	3/2012	RU	2007145218	A	7/2009
JP	2012-043267	A	3/2012	RU	2503989	C2	1/2014
				TW	201447740	A	12/2014
				WO	WO 2005/106637	A2	11/2005
				WO	WO 2006/013485	A2	2/2006
				WO	WO 2006/042309	A1	4/2006

(56)

## References Cited

## FOREIGN PATENT DOCUMENTS

WO	WO 2006/094308	A2	9/2006
WO	WO 2007/121557	A1	11/2007
WO	WO 2008/030976	A2	3/2008
WO	WO 2008/064142	A2	5/2008
WO	WO 2009/155981	A1	12/2009
WO	WO 2009/158549	A2	12/2009
WO	WO 2010/013876	A1	2/2010
WO	WO 2010/032598	A1	3/2010
WO	WO 2010/090010	A1	8/2010
WO	WO 2010/122813	A1	10/2010
WO	WO 2010/134729	A2	11/2010
WO	WO 2011/024389	A1	3/2011
WO	WO 2011/024465	A1	3/2011
WO	WO 2011/024521	A1	3/2011
WO	WO 2011/093045	A1	8/2011
WO	WO 2011/105009	A1	9/2011
WO	WO 2011/108190	A1	9/2011
WO	WO 2011/115187	A1	9/2011
WO	WO 2011/121375	A1	10/2011
WO	WO 2012/021417	A1	2/2012
WO	WO 2012/037664	A1	3/2012
WO	WO 2012/096804	A2	7/2012
WO	WO 2012/108213	A1	8/2012
WO	WO 2012/114760	A1	8/2012
WO	WO 2012/137946	A1	10/2012
WO	WO 2012/150540	A2	11/2012
WO	WO 2012/153555	A1	11/2012
WO	WO 2013/022486	A1	2/2013
WO	WO 2013/035725	A1	3/2013
WO	WO 2013/112453	A1	8/2013
WO	WO 2013/127055	A1	9/2013
WO	WO 2013/169302	A1	11/2013
WO	WO 2013/169845	A1	11/2013
WO	WO 2013/169846	A1	11/2013
WO	WO 2013/169849	A2	11/2013
WO	WO 2013/169851	A2	11/2013
WO	WO 2013/169853	A1	11/2013
WO	WO 2013/169854	A2	11/2013
WO	WO 2013/169870	A1	11/2013
WO	WO 2013/169875	A2	11/2013
WO	WO 2013/169877	A2	11/2013
WO	WO 2013/169882	A2	11/2013
WO	WO 2013/173838	A2	11/2013
WO	WO 2014/034706	A1	3/2014
WO	WO 2014/105275	A1	7/2014
WO	WO 2014/105276	A1	7/2014
WO	WO 2014/105277	A2	7/2014
WO	WO 2014/105278	A1	7/2014
WO	WO 2014/105279	A1	7/2014
WO	WO 2014/129655	A1	8/2014
WO	WO 2014/149473	A1	9/2014
WO	WO 2014/152601	A1	9/2014
WO	WO 2014/200733	A1	12/2014
WO	WO 2013/145804		12/2015
WO	WO 2016/200584	A2	12/2016

## OTHER PUBLICATIONS

Angelov, "Sponsor Flip Wall with JQuery & CSS", Tutorialzine. N.p., Mar. 24, 2010. Web. <http://tutorialzine.com/2010/03/sponsor-wall-slip-jquery-css/>, Mar. 24, 2010, 8 pages.

Anonymous, "1-Click Installer for Windows Media Taskbar Mini-Player for Windows 7, 8, 8.1 10", <http://metadataconsulting.blogspot.de/2014/05/installer-for-windows-media-taskbar.htm>, May 5, 2014, 6 pages.

Anonymous, "Acer Liquid Z5 Duo User's Manual", <https://global-download.acer.com>, Feb. 21, 2014, 65 pages.

Anonymous, "Android—What Should Status Bar Toggle Button Behavior Be?", <https://ux.stackexchange.com/questions/34814>, Jan. 15, 2015, 2 pages.

Anonymous, "Google Android 5.0 Release Date, Specs and Editors Hands on Review—CNET", <http://www.cnet.com/products/google-an-android-5-0-lollipop/>, Mar. 12, 2015, 10 pages.

Anonymous, "How Do I Add Contextual Menu to My Apple Watch App?", <http://www.tech-recipes.com/rx/52578/how-do-i-add-contextual-menu-to-my-apple-watch-app>, Jan. 13, 2015, 3 pages.

Anonymous, "[new] WMP12 with Taskbar Toolbar for Windows 7—Windows Customization—WinMatrix", <http://www.winmatrix.com/forums/index/php?topic/25528-new-wmp12-with-taskbar-toolbar-for-windows-7>, Jan. 27, 2013, 6 pages.

Anonymous, "Nokia 808 PureView screenshots", retrieved from Internet; no URL, Nov. 12, 2012, 8 pages.

Anonymous, "Nokia 808 PureView User Guide," [http://download-fds.webapps.microsoft.com/supportFiles/phones/files/pdf\\_guides/devices/808/Nokia\\_808\\_UG\\_en\\_APAC.pdf](http://download-fds.webapps.microsoft.com/supportFiles/phones/files/pdf_guides/devices/808/Nokia_808_UG_en_APAC.pdf), Jan. 1, 2012, 144 pages.

Anonymous, "Notifications, Android 4.4 and Lower", Android Developers, [https://developer.android.com/design/patterns/notifications\\_k.html](https://developer.android.com/design/patterns/notifications_k.html), May 24, 2015, 9 pages.

Anonymous, "Taskbar Extensions", [https://web.archive.org/web/20141228124434/http://msdn.microsoft.com:80/en-us/library/windows/desktop/dd378460\(v=vs.85\).aspx](https://web.archive.org/web/20141228124434/http://msdn.microsoft.com:80/en-us/library/windows/desktop/dd378460(v=vs.85).aspx), Dec. 28, 2014, 8 pages.

Apple, "Final Cut Express 4 User Manual", <https://wsli.li.dl/mBGZWEQ8fh556f/>, Jan. 1, 2007, 1,152 pages.

Apple, "Apple—September Event 2014", <https://www.youtube.com/watch?v=38lqQpwwPe7s>, Sep. 10, 2014, 5 pages.

Azundrix, "A Fire in the Pie," <http://web.archive.org/web/20140722062639/http://blog.azundrix.com/archives/168-A-fire-in-the-sky.html>, Jul. 22, 2014, 8 pages.

Billibi, "Android 5.0 Lollipop", <https://www.bilibili.com/video/av1636046?from=search&seid=3128140235778895126>, Oct. 19, 2014, 6 pages.

b-log—betriebsraum weblog, "Extremely Efficient Menu Selection: Marking Menus for the Flash Platform," <http://www.betriebsraum.de/blog/2009/12/11/extremely-efficient-menu-selection-marking-for-the-flash-platform>, Dec. 11, 2009, 9 pages.

Bolluyt, "5 Apple Watch Revelations from Apple's New WatchKit", <http://www.cheatsheet.com/technology/5-apple-watch-revelations-from-apples-new-watchkit.html?a=viewall>, Nov. 22, 2014, 3 pages.

Boring, "The Fat Thumb: Using the Thumb's Contact Size for Single-Handed Mobile Interaction", <https://www.youtube.com/watch?v=E9vGU5R8nsc&feature=youtu.be>, Jun. 14, 2012, 2 pages.

Borowska, "6 Types of Digital Affordance that Impact Your UX", <https://www.webdesignerdepot.com/2015/04/6-types-of-digital-affordance-that-impact-your-ux>, Apr. 7, 2015, 6 pages.

Brewster, "The Design and Evaluation of a Vibrotactile Progress Bar", Glasgow Interactive Systems Group, University of Glasgow, Glasgow, G12 8QQ, UK, 2005, 2 pages.

Brownlee, "Android 5.0 Lollipop Feature Review!", <https://www.youtube.com/watch?v=pEDQ1z1-PvU>, Oct. 27, 2014, 5 pages.

Cheng, "iPhone 5: a little bit taller, a little bit baller", <https://arstechnica.com/gadgets/2012/09/iphone-5-a-little-bit-taller-a-little-bit-baller>, Oct. 14, 2021, 22 pages.

Clark, "Global Moxie, Touch Means a Renaissance for Radial Menus," <http://globalmoxie.com/blog/radial-menus-for-touch-ui-print.shtml>, Jul. 17, 2012, 7 pages.

Cohen, Cinemagraphs are Animated Gifs for Adults, <http://www.tubefilter.com/2011/07/10/cinemagraph>, Jul. 10, 2011, 3 pages.

CrackBerry Forums, Windows 8 Bezel Control and Gestures, <http://wwwforums.crackberry.com/blackberry-playbook-f222/windows-8-bezel-control-gestures-705129/>, Mar. 1, 2012, 8 pages.

Crook, "Microsoft Patenting Multi-Screen, Multi-Touch Gestures," <http://techcrunch.com/2011/08/25/microsoft-awarded-patents-for-multi-screen-multi-touch-gestures/>, Aug. 25, 2011, 8 pages.

civil.ly—a design blog, Interesting Touch Interactions on Windows 8, <http://civil.ly/2011/06/04/interesting-touch-interactions-on-windows-8/>, Jun. 4, 2011, 3 pages.

Davidson, et al., "Extending 2D Object Arrangement with Pressure-Sensitive Layering Cues", Proceedings of the 21st Annual ACM Symposium on User Interface Software and Technology, Oct. 19, 2008, 4 pages.

Dinwiddie, et al., "Combined-User Interface for Computers, Television, Video Recorders, and Telephone, Etc", *ip.com Journal*, Aug. 1, 1990, 3 Pages.

Drinkwater, "Glossary: Pre/Post Alarm Image Buffer," <http://www.networkwebcams.com/ip-camera-learning-center/2008/07/17/glossary-prepost-alarm-image-buffer/>, Jul. 17, 2008, 1 page.

(56)

## References Cited

## OTHER PUBLICATIONS

- Dzyre, "10 Android Notification Features You Can Fiddle With", <http://www.hongkiat.com/blog/android-notification-features>, Mar. 10, 2014, 10 pages.
- Easton-Ellett, "Three Free Cydia Utilities to Remove iOS Notification Badges", <http://www.ijailbreak.com/cydia/three-free-cydia-utilities-to-remove-ios-notification-badges>, Apr. 14, 2012, 2 pages.
- Elliot, "Mac System 7", YouTube. Web. Mar. 8, 2017, <http://www.youtube.com/watch?v=XLv22hfuiik>, Aug. 3, 2011, 1 page.
- Farshad, "SageThumbs-Preview And Convert Pictures From Windows Context Menu", <https://web.addictivetips.com/windows-tips/sagethumbs-preview-and-convert-photos-from-windows-context-menu>, Aug. 8, 2011, 5 pages.
- Fenlon, "The Case for Bezel Touch Gestures on Apple's iPad," <http://www.tested.com/tech/tablets/3104-the-case-for-bezel-touch-gestures-on-apples-ipad/>, Nov. 2, 2011, 6 pages.
- Flaherty, "Is Apple Watch's Pressure-Sensitive Screen a Bigger Deal Than The Gadget Itself?", <http://www.wired.com/2014/09/apple-watches-pressure-sensitive-screen-bigger-deal-gadget>, Sep. 15, 2014, 3 pages.
- Flixel, "Cinemagraph Pro for Mac", <https://flixel.com/products/mac/cinemagraph-pro>, 2014, 7 pages.
- Flowplayer, "Slowmotion: Flowplayer," <https://web.archive.org/web/20150226191526/http://flash.flowplayer.org/plugins/streaming/slowmotion.html>, Feb. 26, 2015, 4 pages.
- Garcia-Hernandez et al., "Orientation Discrimination of Patterned Surfaces through an Actuated and Non-Actuated Tactile Display", 2011 IEEE World Haptics Conference, Istanbul, Jun. 21-24, 2011, 3 pages.
- Forlines, et al., "Glimpse: a Novel Input Model for Multi-level Devices", Chi '05 Extended Abstracts on Human Factors in Computing Systems, Apr. 2, 2005, 4 pages.
- Gardner, "Recenz—Recent Apps in One Tap", YouTube, <https://www.youtube.com/watch?v=qailSHRgsTo>, May 15, 2015, 1 page.
- Geisler, "Enriched Links: A Framework for Improving Web Navigation Using Pop-Up Views", Journal of the American Society for Information Science, Chapel Hill, NC, Jan. 1, 2000, 13 pages.
- Gonzalo et al., "Zliding: Fluid Zooming and Sliding for High Precision Parameter Manipulation", Department of Computer Science, University of Toronto, Seattle, Washington, Oct. 23, 2005, 10 pages.
- Google-Chrome, "Android 5.0 Lollipop", <http://androidlover.net/android-os/android-5-0-lollipop/android-5-0-lollipop-recent-apps-card-google-search.html>, Oct. 19, 2014, 10 pages.
- Grant, "Android's Notification Center", <https://www.objc.io/issues/11-android/android-notifications>, Apr. 30, 2014, 26 pages.
- Gurman, "Force Touch on iPhone 6S Revealed: Expect Shortcuts, Faster Actions, iOS", 9To5Mac Aug. 10, 2015, 31 pages.
- Henderson et al., "Opportunistic User Interfaces for Augmented Reality", Department of Computer Science, New York, NY, Jan. 2010, 13 pages.
- IBM et al., "Pressure-Sensitive Icons", IBM Technical Disclosure Bulletin, vol. 33, No. 1B, Jun. 1, 1990, 3 pages.
- iCIMS Recruiting Software, "Blackberry Playbook Review," <http://www.tested.com/tech/tablets/5749-blackberry-playbook-review/>, 2015, 11 pages.
- iPhoneHacksTV, "Confero allows you to easily manage your Badge notifications—iPhone Hacks", youtube, <https://www.youtube.com/watch?v=JCK61pnL4SU>, Dec. 26, 2014, 3 pages.
- iPhoneOperator, "Wasser Liveeffekt für Homescreen & Lockscreen—AquaBoard (Cydia)", <http://www.youtube.com/watch?v=fG9YMFmB0Q>, Sep. 22, 2012, 3 pages.
- iPodHacks 142: "Water Ripple Effects on the Home and Lock Screen: AquaBoard Cydia Tweak Review", YouTube, [https://www.youtube.com/watch?v=Auu\\_uRaYHJs](https://www.youtube.com/watch?v=Auu_uRaYHJs), Sep. 24, 2012, 3 pages.
- Jauregui, "Design and Evaluation of 3D Cursors and Motion Parallax for the Exploration of Desktop Virtual Environments", IEEE Symposium on 3D User Interfaces 2012, Mar. 4, 2012, 8 pages.
- Jones, "Touch Screen with Feeling", IEEE Spectrum, spectrum.ieee.org/commuting/hardware/touch-screens-with-feeling, May 1, 2009, 2 pages.
- Kaaresoja, "Snap-Crackle-Pop: Tactile Feedback for Mobile Touch Screens," Nokia Research Center, Helsinki, Finland, Proceedings of Eurohaptics vol. 2006, Jul. 3, 2006, 2 pages.
- Kiener, "Force Touch on iPhone", <https://www.youtube.com/watch?v=CEMmnsU5fC8>, Aug. 4, 2015, 4 pages.
- Kleinman, "iPhone 6s Said to Sport Force Touch Display, 2GB of RAM", <https://www.technobuffalo.com/2015/01/15/iphone-6s-said-to-sport-force-touch-display-2gb-of-ram>, Jan. 15, 2015, 2 pages.
- Kost, "LR3-Deselect All Images But One", Julianne Kost's Blog, [blogs.adobe.com/jkost/2011/12/lr3-deselect-all-images-but-one.html](https://blogs.adobe.com/jkost/2011/12/lr3-deselect-all-images-but-one.html), Dec. 22, 2011, 1 page.
- Kronfli, "HTC Zoe Comes to Google Play, Here's Everything You Need to Know," Know Your Mobile, <http://www.knowyourmobile.com/htc/htc-one/19550/what-htc-zoe>, Aug. 14, 2014, 5 pages.
- Kumar, "How to Enable Ripple Effect on Lock Screen of Galaxy S2", YouTube, <http://www.youtube.com/watch?v=B9-4M5abLXA>, Feb. 12, 2013, 3 pages.
- Kurdi, "XnView Shell Extension: A Powerful Image Utility Inside The Context Menu", <http://www.freewaregenius.com/xnview-shell-extension-a-powerful-image-utility-inside-the-context-menu>, Jul. 30, 2008, 4 pages.
- Laurie, "The Power of the Right Click," <http://vlaurie.com/right-click/customize-context-menu.html>, 2002-2016, 3 pages.
- MacKenzie et al., "The Tactile Touchpad", Chi '97 Extended Abstracts on Human Factors in Computing Systems Looking to the Future, Chi '97, Mar. 22, 1997, 5 pages.
- Mahdi, Confero now available in Cydia, brings a new way to manage Notification badges [Jailbreak Tweak], <http://www.iphonehacks.com/2015/01/confero/tweak-manage-notification-badges.html>, Jan. 1, 2015, 2 pages.
- Matthew, "How to Preview Photos and Images From Right-Click Context Menu in Windows [Tip]", <http://www.dottech.org/159009/add-image-preview-in-windows-context-menu-tip>, Jul. 4, 2014, 5 pages.
- McGarry, "Everything You Can Do With Force Touch on Apple Watch", Macworld, [www.macworld.com](http://www.macworld.com), May 6, 2015, 4 pages.
- McRitchie, "Internet Explorer Right-Click Menus," <http://web.archive.org/web/201405020/http://dmcritchie.mvps.org/ie/rightie6.htm>, May 2, 2014, 10 pages.
- Microsoft, "Lumia—How to Personalize Your Start Screen", <https://www.youtube.com/watch?v=6GI5Z3TrSEs>, Nov. 11, 2014, 3 pages.
- Microsoft, "Use Radial Menus to Display Commands in OneNote for Windows 8," <https://support.office.com/en-us/article/Use-radial-menus-to-display-OneNote-commands-Od75f03f-cde7-493a-a8a0b2ed6f99f2e>, 2016, 5 pages.
- Minsky, "Computational Haptics the *Sandpaper* System for Synthesizing Texture for a Force-Feedback Display," Massachusetts Institute of Technology, Jun. 1978, 217 pages.
- Mitroff, "Google Android 5.0 Lollipop," <http://www.cnet.com/products/google-android-5-0-lollipop>, Mar. 12, 2015, 5 pages.
- Mohr, "Do Not Disturb—The iPhone Feature You Should Be Using", <http://www.wonderoftech.com/do-not-disturb-iphone>, Jul. 14, 2014, 30 pages.
- Nacca, "NiLS Lock Screen Notifications / Floating Panel—Review", <https://www.youtube.com/watch?v=McT4QnS9TDY>, Feb. 3, 2014, 4 pages.
- Neuburg, "Detailed Explanation iOS SDK", Oreilly Japan, Dec. 22, 2014, vol. 4, P175-186, 15 pages.
- Nickinson, How to Use Do Not Disturb on the HTC One M8, <https://www.androidcentral.com/how-to-use-do-not-disturb-htc-one-m8>, Apr. 7, 2014, 9 pages.
- Nickinson, "Inside Android 4.2: Notifications and Quick Settings", <https://www.androidcentral.com/inside-android-42-notifications-and-quick-settings>, Nov. 3, 2012, 3 pages.
- Nikon, "Scene Recognition System and Advanced SRS," <http://www.nikonusa.com/en.Learn-And-Explore/Article/flzi4rr/Scene-Recognition-System.html>, Jul. 22, 2015, 2 pages.
- Nishino, "A Touch Screen Interface Design with Tactile Feedback", Computer Science, 2011 International Conference on Complex, Intelligent, and Software Intensive Systems, 2011, 4 pages.

(56)

## References Cited

## OTHER PUBLICATIONS

- Ogino, "iOS 7 Design Standard", Japan, Impress Japan Corporation, 1st edition, Nov. 21, 2013, 2 pages.
- Oh, et al., "Moving Objects with 2D Input Devices in CAD Systems and Desktop Virtual Environments", Proceedings of Graphics Interface 2005, 8 pages, May 2005.
- O'Hara, et al., "Pressure-Sensitive Icons", ip.com Journal, ip.com Inc., West Henrietta, NY, US, Jun. 1, 1990, 2 Pages.
- Pallenberg, "Wow, the new iPad had gestures." <https://plus.google.com/+SaschaPallenberg/posts/aaJtJogu8ac>, Mar. 7, 2012, 2 pages.
- Phonebuff, "How to Pair Bluetooth on the iPhone", <https://www.youtube.com/watch?v=LudNwEar9A8>, Feb. 8, 2012, 3 pages.
- Plaisant et al., "Touchscreen Toggle Design", Proceedings of CHI '92, pp. 667-668, May 3-7, 1992, 2 pages.
- PoliceOne.com, "COBAN Technologies Pre-Event Buffer & Fail Safe Feature," <http://www.policeone.com/police-products/police-technology/mobile-computers/videos/5955587-COBAN-Technologies-Pre-Event>, Nov. 11, 2010, 2 pages.
- Pradeep, "Android App Development—Microsoft Awarded With Patents on Gestures Supported on Windows 8," <http://mspoweruser.com/microsoft-awarded-with-patents-on-gestures-supported-on-windows-8/>, Aug. 25, 2011, 16 pages.
- "Quickly Preview Songs in Windows Media Player 12 in Windows 7," Quickly Preview Songs in Windows Media Player 12 in Windows 7. How-to Geek, Apr. 28, 2010, Web. May 8, 2010, <http://web.archive.org/web/20100502013134/http://www.howtogeek.com/howto/16157/quickly-preview-songs-in-windows-media-center-12-in-windows-7/>, 6 pages.
- Quinn, et al., "Zoofing! Faster List Selections with Pressure-Zoom-Flick-Scrolling", Proceedings of the 21st Annual Conference of the Australian Computer-Human Interaction Special Interest Group on Design, Nov. 23, 2009, ACM Press, vol. 411, 8 pages.
- Rekimoto, et al., "PreSense: Interaction Techniques for Finger Sensing Input Devices", Proceedings of the 16th Annual ACM Symposium on User Interface Software and Technology, Nov. 30, 2003, 10 pages.
- Rekimoto, et al., "PreSensell: Bi-directional Touch and Pressure Sensing Interactions with Tactile Feedback", Conference on Human Factors in Computing Systems Archive, ACM, Apr. 22, 2006, 6 pages.
- Rekimoto, et al., "SmartPad: A Finger-Sensing Keypad for Mobile Interaction", CHI 2003, Ft. Lauderdale, Florida, ACM 1-58113-637-Apr. 5-10, 2003, 2 pages.
- Ritchie, "How to see all the unread message notifications on your iPhone, all at once, all in the same place | iMore", <https://www.imore.com/how-see-all-unread-message-notifications-your-iphone-all-at-once-all-same-place>, Feb. 22, 2014, 2 pages.
- Roth et al., "Bezel Swipe: Conflict-Free Scrolling and Multiple Selection on Mobile Touch Screen Devices," Chi 2009, Boston, Massachusetts, USA, Apr. 4-9, 2009, 4 pages.
- Rubino et al., "How to Enable 'Living Images' on your Nokia Lumia with Windows Phone 8.1", <https://www.youtube.com/watch?v=RX7vpoFy1Dg>, Jun. 6, 2014, 5 pages.
- Sleepfreaks, "How to Easily Play/Loop an Event Range in Cubase", <https://sleepfreaks-dtm.com/for-advance-cubase/position-3/>, Apr. 4, 2011, 14 pages.
- Sony, "Intelligent Scene Recognition," <https://www.sony-asia.com/article/252999/section/product/product/dsc-t77>, downloaded on May 20, 2016, 5 pages.
- Sood, "Multitasking Gestures", <http://cydia.saurik.com/package/org.thebigboxx.multitaskinggestures/>, Mar. 3, 2014, 2 pages.
- Stewart, et al., "Characteristics of Pressure-Based Input for Mobile Devices", Proceedings of the SIGCHI Conference on Human Factors in Computing Systems, Apr. 2010, 10 pages.
- Stross, "Wearing a Badge, and a Video Camera," The New York Times, <http://www.nytimes.com/2013/04/07/business/wearable-video-cameras-for-police-offers.html?R=0>, Apr. 6, 2013, 4 pages.
- Taser, "Taser Axon Body Camera User Manual," [https://www.taser.com/images/support/downloads/product-resources/axon\\_body\\_product\\_manual.pdf](https://www.taser.com/images/support/downloads/product-resources/axon_body_product_manual.pdf), Oct. 1, 2013, 24 pages.
- Tidwell, "Designing Interfaces," O'Reilly Media, Inc., USA, Nov. 2005, 348 pages.
- Tweak, "QuickCenter—Add 3D-Touch Shortcuts to Control Center", <https://www.youtube.com/watch?v=8rHOFpGvZFM>, Mar. 22, 2016, 2 pages.
- Tweak, "iOS 10 Tweak on iOS 9.0.2 Jailbreak & 9.2.1—9.3 Support: QuickCenter 3D, Touch Cydia Tweak!" [https://www.youtube.com/watch?v=opOBr30\\_Fkl](https://www.youtube.com/watch?v=opOBr30_Fkl), Mar. 6, 2016, 3 pages.
- UpDown-G, "Using Multiple Selection Mode in Android 4.0 / Getting Started", <https://techbooster.org/android/13946>, Mar. 7, 2012, 7 pages.
- VGJFeliz, "How to Master Android Lollipop Notifications in Four Minutes!", <https://www.youtube.com/watch?v=S-zBRG7GJgs>, Feb. 8, 2015, 5 pages.
- VisioGuy, "Getting a Handle on Selecting and Subselecting Visio Shapes", <http://www.visguy.com/2009/10/13/getting-a-handle-on-selecting-and-subselecting-visio-shapes/>, Oct. 13, 2009, 18 pages.
- Vitucci, "Apple Watch: Our Complete Overview—MacStories", <https://www.macstories.net>, Sep. 10, 2014, 21 pages.
- Wikipedia, "AirDrop," Wikipedia, the free encyclopedia, <http://en.wikipedia.org/wiki/AirDrop>, May 17, 2016, 5 pages.
- Wikipedia, "Cinemagraph," Wikipedia, the free encyclopedia, <http://en.wikipedia.org/wiki/Cinemagraph>, Last Modified Mar. 16, 2016, 2 pages.
- Wikipedia, "Context Menu," Wikipedia, the free encyclopedia [https://en.wikipedia.org/wiki/Context\\_menu](https://en.wikipedia.org/wiki/Context_menu), Last Modified May 15, 2016, 4 pages.
- Wikipedia, "HTC One (M7)," Wikipedia, the free encyclopedia, [https://en.wikipedia.org/wiki/HTC\\_One\\_\(M7\)](https://en.wikipedia.org/wiki/HTC_One_(M7)), Mar. 2013, 20 pages.
- Wikipedia, "Mobile Ad Hoc Network," Wikipedia, the free encyclopedia, [http://en.wikipedia.org/wiki/Mobile\\_ad\\_hoc\\_network](http://en.wikipedia.org/wiki/Mobile_ad_hoc_network), May 20, 2016, 4 pages.
- Wikipedia, "Pie Menu," Wikipedia, the free encyclopedia, [http://en.wikipedia.org/wiki/Pie\\_menu](http://en.wikipedia.org/wiki/Pie_menu), Last Modified Jun. 4, 2016, 3 pages.
- Wikipedia, "Quick Look," from Wikipedia, the free encyclopedia, [https://en.wikipedia.org/wiki/Quick\\_Look](https://en.wikipedia.org/wiki/Quick_Look), Last Modified Jan. 15, 2016, 3 pages.
- Wikipedia, "Sony Xperia Z1", Wikipedia, the free encyclopedia, [https://en.wikipedia.org/wiki/Sony\\_Experia\\_Z1](https://en.wikipedia.org/wiki/Sony_Experia_Z1), Sep. 2013, 10 pages.
- Wilson, et al., "Augmenting Tactile Interaction with Pressure-Based Input", School of Computing Science, Glasgow, UK, Nov. 15-17, 2011, 2 pages.
- Yang, et al., "Affordance Application on Visual Interface Design of Desk-Top Virtual Experiments", 2014 International Conference on Information Science, Electronics and Electrical Engineering, IEEE, vol. 1, Apr. 26, 2014, 5 pages.
- Yatani, et al., SemFeel: A User Interface with Semantic Tactile Feedback for Mobile Touch-Screen Devices, Proceedings of the 22nd annual ACM symposium on user interface software and technology (UIST '09), Oct. 2009, 10 pages.
- YouTube, "Android Lollipop Lock-Screen Notification Tips", <https://www.youtube.com/watch?v=LZTxHBOwzIU>, Nov. 13, 2014, 3 pages.
- YouTube, "Blackberry Playbook bezel interaction," <https://www.youtube.com/watch?v=YGkzFqnOwXI>, Jan. 10, 2011, 2 pages.
- YouTube, "How to Master Android Lollipop Notifications in Four Minutes!", Video Gadgets Journal (VGJFelix), <https://www.youtube.com/watch?v=S-zBRG7GJgs>, Feb. 8, 2015, 4 pages.
- YouTube, "HTC One Favorite Camera Features", <http://www.youtube.com/watch?v=sUYHfcj14RU>, Apr. 28, 2013, 3 pages.
- YouTube, "Multitasking Gestures: Zephyr Like Gestures on iOS", <https://www.youtube.com/watch?v=Jcod-f7Lw0I>, Jan. 27, 2014, 3 pages.
- YouTube, "Recentz—Recent Apps in a Tap", <https://www.youtube.com/watch?v=gailSHRgsTo>, May 15, 2015, 1 page.
- Zylom, "House Secrets", <http://game.zylom.com/servlet/Entry?g=38&s=19521&nocache=1438641323066>, Aug. 3, 2015, 1 page.
- Office Action, dated Mar. 15, 2017, received in U.S. Appl. No. 14/535,671, 13 pages.
- Office Action, dated Nov. 30, 2017, received in U.S. Appl. No. 14/535,671, 21 pages.
- Notice of Allowance, dated Sep. 5, 2018, received in U.S. Appl. No. 14/535,671, 5 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Office Action, dated Jun. 29, 2017, received in U.S. Appl. No. 14/608,895, 30 pages.

Final Office Action, dated Feb. 22, 2018, received in U.S. Appl. No. 14/608,895, 20 pages.

Notice of Allowance, dated Jun. 26, 2018, received in U.S. Appl. No. 14/608,895, 9 pages.

Office Action, dated Dec. 18, 2015, received in Australian Patent Application No. 2013368440, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Office Action, dated Oct. 18, 2016, received in Australian Patent Application No. 2013368440, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Notice of Allowance, dated Dec. 20, 2016, received in Australian Patent Application No. 2013368440, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Certificate of Grant, dated Apr. 29, 2017, received in Australian Patent Application No. 2013368440, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Office Action, dated Nov. 6, 2017, received in Chinese Patent Application No. 201380068493.6, which corresponds with U.S. Appl. No. 14/608,895, 5 pages.

Office Action, dated Oct. 9, 2018, received in Chinese Patent Application No. 201380068493.6, which corresponds with U.S. Appl. No. 14/608,895, 3 pages.

Patent, dated Dec. 25, 2018, received in Chinese Patent Application No. 201380068493.6, which corresponds with U.S. Appl. No. 14/608,895, 4 pages.

Office Action, dated Jul. 21, 2016, received in European Patent Application No. 13795391.5, which corresponds with U.S. Appl. No. 14/536,426, 9 pages.

Office Action, dated Mar. 9, 2018, received in European Patent Application No. 13795391.5, which corresponds with U.S. Appl. No. 14/536,426, 4 pages.

Intention to Grant, dated Jul. 6, 2018, received in European Patent Application No. 13795391.5, which corresponds with U.S. Appl. No. 14/536,426, 5 pages.

Certificate of Grant, dated Dec. 26, 2018, received in European Patent Application No. 13795391.5, which corresponds with U.S. Appl. No. 14/536,426, 4 pages.

Office Action, dated Sep. 13, 2016, received in Japanese Patent Application No. 2015-547948, which corresponds with U.S. Appl. No. 14/536,426, 5 pages.

Patent, dated May 12, 2017, received in Japanese Patent Application No. 2015-547948, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Office Action, dated Apr. 5, 2016, received in Korean Patent Application No. 10-2015-7018851, which corresponds with U.S. Appl. No. 14/536,426, 7 pages.

Office Action, dated Feb. 24, 2017, received in Korean Patent Application No. 10-2015-7018851, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Patent, dated May 26, 2017, received in Korean Patent Application No. 2015-7018851, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Office Action, dated Oct. 5, 2018, received in Korean Patent Application No. 2018-7028236, which corresponds with U.S. Appl. No. 14/608,895, 6 pages.

Notice of Allowance, dated May 24, 2019, received in Korean Patent Application No. 2018-7028236, which corresponds with U.S. Appl. No. 14/608,895, 4 pages.

Patent, dated Jul. 9, 2019, received in Korean Patent Application No. 2018-7028236, which corresponds with U.S. Appl. No. 14/608,895, 4 pages.

Office Action, dated Jul. 26, 2017, received in U.S. Appl. No. 14/536,235, 14 pages.

Final Office Action, dated Feb. 26, 2018, received in U.S. Appl. No. 14/536,235, 13 pages.

Notice of Allowance, dated Aug. 15, 2018, received in U.S. Appl. No. 14/536,235, 5 pages.

Office Action, dated Apr. 5, 2017, received in U.S. Appl. No. 14/536,367, 16 pages.

Notice of Allowance, dated Nov. 30, 2017, received in U.S. Appl. No. 14/536,367, 9 pages.

Notice of Allowance, dated May 16, 2018, received in U.S. Appl. No. 14/536,367, 5 pages.

Office Action, dated Dec. 17, 2015, received in U.S. Appl. No. 14/536,426, 28 pages.

Final Office Action, dated May 6, 2016, received in U.S. Appl. No. 14/536,426, 23 pages.

Office action, dated Aug. 3, 2017, received in U.S. Appl. No. 14/536,426, 10 pages.

Office Action, dated Jul. 15, 2015, received in Australian Patent Application No. 2013259606, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Notice of Allowance, dated May 23, 2016, received in Australian Patent Application No. 2013259606, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Certificate of Grant, dated Sep. 15, 2016, received in Australian Patent Australian Patent Application No. 20133259606, which corresponds with U.S. Appl. No. 14/536,426, 1 page.

Office Action, dated Nov. 18, 2015, received in Australian Patent Application No. 2015101231, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Office Action, dated May 15, 2017, received in Australian Patent Application No. 2016216580, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Office Action, dated May 8, 2018, received in Australian Patent Application No. 2016216580, which corresponds with U.S. Appl. No. 14/536,426, 5 pages.

Notice of Allowance, dated May 17, 2018, received in Australian Patent Application No. 2016216580, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Certificate of Grant, dated Sep. 13, 2018, received in Australian Patent Application No. 2016216580, which corresponds with U.S. Appl. No. 14/536,426, 1 page.

Office Action, dated Apr. 12, 2019, received in Australian Patent Application No. 2018223021, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Office Action, dated Nov. 18, 2019, received in Australian Patent Application No. 2018223021, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Office Action, dated Feb. 18, 2020, received in Australian Patent Application No. 2018223021, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Notice of Allowance, dated Mar. 27, 2020, received in Australian Patent Application No. 2018223021, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Certificate of Grant, dated Jul. 23, 2020, received in Australian Patent Application No. 2018223021, which corresponds with U.S. Appl. No. 14/536,426, 4 pages.

Office Action, dated Sep. 19, 2017, received in Chinese Patent Application No. 201380035982.1, which corresponds with U.S. Appl. No. 14/536,426, 5 pages.

Notice of Allowance, dated May 10, 2018, received in Chinese Patent Application No. 201380035982.1, which corresponds with U.S. Appl. No. 14/536,426, 2 pages.

Patent, dated Aug. 17, 2018, received in Chinese Patent Application No. 201380035982.1, which corresponds with U.S. Appl. No. 14/536,426, 4 pages.

Office Action, dated Sep. 20, 2017, received in Chinese Patent Application No. 201510566550.4, which corresponds with U.S. Appl. No. 14/536,426, 11 pages.

Notice of Allowance, dated Aug. 8, 2018, received in Chinese Patent Application No. 201510566550.4, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Patent, dated Oct. 23, 2018, received in Chinese Patent Application No. 20151056650.4, which corresponds with U.S. Appl. No. 14/536,426, 4 pages.

Office Action, dated Jan. 4, 2021, received in Chinese Patent Application No. 201810826224.6, which corresponds with U.S. Appl. No. 14/536,426, 6 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Office Action, dated Jun. 24, 2021, received in Chinese Patent Application No. 201810826224.6, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Notice of Allowance, dated Oct. 11, 2021, received in Chinese Patent Application No. 201810826224.6, which corresponds with U.S. Appl. No. 14/536,426, 1 page.

Patent, dated Nov. 12, 2021, received in Chinese Patent Application No. 201810826224.6, which corresponds with U.S. Appl. No. 14/536,426, 7 pages.

Decision to Grant, dated Jul. 14, 2016, received in European Patent Application No. 13724100.6, which corresponds with U.S. Appl. No. 14/536,426, 1 page.

Letters Patent, dated Aug. 10, 2016, received in European Patent Application No. 13724100.6, which corresponds with U.S. Appl. No. 14/536,426, 1 page.

Office Action, dated Jan. 20, 2017, received in European Patent Application No. 15183980.0, which corresponds with U.S. Appl. No. 14/536,426, 5 pages.

Office Action, dated Aug. 21, 2017, received in European Patent Application No. 15183980.0, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Intention to Grant, dated Mar. 9, 2018, received in European Patent Application No. 15183980.0, which corresponds with U.S. Appl. No. 14/536,426, 5 pages.

Intention to Grant, dated Aug. 14, 2018, received in European Patent Application No. 15183980.0, which corresponds with U.S. Appl. No. 14/536,426, 5 pages.

Decision to Grant, dated Jan. 10, 2019, received in European Patent Application No. 15183980.0, which corresponds with U.S. Appl. No. 14/536,426, 4 pages.

Patent, dated Feb. 6, 2019, received in European Patent Application No. 15183980.0, which corresponds with U.S. Appl. No. 14/536,426, 4 pages.

Office Action, dated Sep. 6, 2019, received in European Patent Application No. 18180503.7, which corresponds with U.S. Appl. No. 14/536,426, 5 pages.

Certificate of Grant, dated Nov. 10, 2017, received in Hong Kong Patent Application No. 15107535.0, which corresponds with U.S. Appl. No. 14/536,426, 2 pages.

Certificate of Grant, dated Jul. 5, 2019, received in Hong Kong Patent Application No. 15108892.5, which corresponds with U.S. Appl. No. 14/536,426, 5 pages.

Patent, dated Nov. 22, 2019, received in Hong Kong Patent Application No. 16107033.6, which corresponds with U.S. Appl. No. 14/536,426, 6 pages.

Office Action, dated Mar. 4, 2016, received in Japanese Patent Application No. 2015-511644, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Office Action, dated Feb. 6, 2017, received in Japanese Patent Application No. 2015-511644, which corresponds with U.S. Appl. No. 14/536,426, 6 pages.

Notice of Allowance, dated Dec. 8, 2017, received in Japanese Patent Application No. 2015-511644, which corresponds with U.S. Appl. No. 14/536,426, 6 pages.

Patent, dated Jan. 12, 2018, received in Japanese Patent Application No. 2015-511644, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Office Action, dated Nov. 6, 2018, received in Japanese Patent Application No. 2018-000753, which corresponds with U.S. Appl. No. 14/536,426, 8 pages.

Office Action, dated Oct. 7, 2019, received in Japanese Patent Application No. 2018-000753, which corresponds with U.S. Appl. No. 14/536,426, 5 pages.

Office Action, dated Feb. 8, 2021, received in Japanese Patent Application No. 2018-000753, which corresponds with U.S. Appl. No. 14/536,426, 2 pages.

Office Action, dated Mar. 9, 2017, received in U.S. Appl. No. 14/536,464, 21 pages.

Final Office Action, dated Aug. 25, 2017, received in U.S. Appl. No. 14/536,464, 30 pages.

Office Action, dated Feb. 12, 2018, received in U.S. Appl. No. 14/536,464, 33 pages.

Final Office Action, dated Jun. 22, 2018, received in U.S. Appl. No. 14/536,464, 32 pages.

Notice of Allowance, dated Jan. 25, 2021, received in U.S. Appl. No. 14/536,464, 5 pages.

Notice of Allowance, dated Feb. 23, 2021, received in U.S. Appl. No. 14/536,464, 5 pages.

Office Action, dated Sep. 25, 2017, received in U.S. Appl. No. 14/536,644, 29 pages.

Final Office Action, dated May 3, 2018, received in U.S. Appl. No. 14/536,644, 28 pages.

Office Action, dated Nov. 2, 2018, received in U.S. Appl. No. 14/536,644, 24 pages.

Notice of Allowance, dated Jul. 2, 2019, received in U.S. Appl. No. 14/536,644, 5 pages.

Office Action, dated Oct. 19, 2017, received in U.S. Appl. No. 14/608,926, 14 pages.

Final Office Action, dated Jun. 6, 2018, received in U.S. Appl. No. 14/608,926, 19 pages.

Notice of Allowance, dated Apr. 10, 2019, received in U.S. Appl. No. 14/608,926, 16 pages.

Notice of Allowance, dated May 21, 2019, received in U.S. Appl. No. 14/608,926, 5 pages.

Office Action, dated Feb. 1, 2016, received in Australian Patent Application No. 2013368441, which corresponds with U.S. Appl. No. 14/608,926, 3 pages.

Notice of Allowance, dated Mar. 30, 2016, received in Australian Patent Application No. 2013368441, which corresponds with U.S. Appl. No. 14/608,926, 1 page.

Certificate of Grant, dated Jul. 29, 2016, received in Australian Patent Application No. 2013368441, which corresponds with U.S. Appl. No. 14/608,926, 1 page.

Office Action, dated Jan. 3, 2017, received in Australian Patent Application No. 2016201451, which corresponds with U.S. Appl. No. 14/608,926, 3 pages.

Notice of Acceptance, dated Dec. 20, 2017, received in Australian Patent Application No. 2016201451, which corresponds with U.S. Appl. No. 14/608,926, 3 pages.

Certificate of Grant, dated May 3, 2018, received in Australian Patent Application No. 2016201451, which corresponds with U.S. Appl. No. 14/608,926, 1 page.

Office Action, dated May 4, 2017, received in Chinese Patent Application No. 201380068414.1, which corresponds with U.S. Appl. No. 14/608,926, 5 pages.

Notice of Allowance, dated Feb. 8, 2018, received in Chinese Patent Application No. 201380068414.1, which corresponds with U.S. Appl. No. 14/608,926, 2 pages.

Patent, dated May 4, 2018, received in Chinese Patent Application No. 201380068414.1, which corresponds with U.S. Appl. No. 14/608,926, 4 pages.

Office Action, dated Dec. 1, 2020, received in Chinese Patent Application No. 201810369259.1, which corresponds with U.S. Appl. No. 14/608,926, 14 pages.

Office Action, dated Jul. 14, 2021, received in Chinese Patent Application No. 201810369259.1, which corresponds with U.S. Appl. No. 14/608,926, 5 pages.

Office Action, dated Apr. 21, 2016, received in European Patent Application No. 13795392.3, which corresponds with U.S. Appl. No. 14/608,926, 6 pages.

Office Action, dated May 6, 2016, received in European Patent Application No. 13795392.3, which corresponds with U.S. Appl. No. 14/608,926, 6 pages.

Office Action, dated Nov. 11, 2016, received in European Patent Application No. 13795392.3, which corresponds with U.S. Appl. No. 14/608,926, 6 pages.

Office Action, dated Jul. 4, 2017, received in European Patent Application No. 13795392.3, which corresponds with U.S. Appl. No. 14/608,926, 4 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Oral Summons, dated Feb. 13, 2017, received in European Patent Application No. 13795392.3, which corresponds with U.S. Appl. No. 14/608,926, 11 pages.

Office Action, dated Mar. 14, 2016, received in Japanese Patent Application No. 2015-549392, which corresponds with U.S. Appl. No. 14/608,926, 4 pages.

Notice of Allowance, dated Jan. 17, 2017, received in Japanese Patent Application No. 2015-549392, which corresponds with U.S. Appl. No. 14/608,926, 2 pages.

Patent, dated Feb. 17, 2017, received in Japanese Patent Application No. 2015-549392, which corresponds with U.S. Appl. No. 14/608,926, 3 pages.

Patent, dated Apr. 27, 2018, received in Japanese Patent Application No. 2017-024234, which corresponds with U.S. Appl. No. 14/608,926, 3 pages.

Office Action, dated Feb. 22, 2019, received in Japanese Patent Application No. 2018-079290, which corresponds with U.S. Appl. No. 14/608,926, 7 pages.

Office Action, dated Sep. 30, 2019, received in Japanese Patent Application No. 2018-079290, which corresponds with U.S. Appl. No. 14/608,926, 5 pages.

Notice of Allowance, dated Apr. 3, 2020, received in Japanese Patent Application No. 2018-079290, which corresponds with U.S. Appl. No. 14/608,926, 5 pages.

Patent, dated Apr. 14, 2020, received in Japanese Patent Application No. 2018-079290, which corresponds with U.S. Appl. No. 14/608,926, 5 pages.

Office Action, dated May 12, 2016, received in Korean Patent Application No. 10-2015-7018853, which corresponds with U.S. Appl. No. 14/608,926, 4 pages.

Notice of Allowance, dated Mar. 31, 2017, received in Korean Patent Application No. 2015-7018853, which corresponds with U.S. Appl. No. 14/608,926, 4 pages.

Patent, dated Jun. 30, 2017, received in Korean Patent Application No. 2015-7018853, which corresponds with U.S. Appl. No. 14/608,926, 3 pages.

Office Action, dated Aug. 22, 2017, received in Korean Patent Application No. 2017-7018250, which corresponds with U.S. Appl. No. 14/608,926, 2 pages.

Notice of Allowance, dated Dec. 29, 2017, received in Korean Patent Application No. 2017-7018250, which corresponds with U.S. Appl. No. 14/608,926, 3 pages.

Office Action, dated Oct. 19, 2017, received in U.S. Appl. No. 14/536,646, 21 pages.

Notice of Allowance, dated Aug. 9, 2018, received in U.S. Appl. No. 14/536,646, 5 pages.

Office Action, dated Jul. 17, 2015, received in Australian Patent Application No. 2013259613, which corresponds with U.S. Appl. No. 14/536,646, 5 pages.

Office Action, dated May 31, 2016, received in Australian Patent Application No. 2013259613, which corresponds with U.S. Appl. No. 14/536,646, 4 pages.

Notice of Allowance, dated Jul. 5, 2016, received in Australian Patent Application No. 2013259613, which corresponds with U.S. Appl. No. 14/536,646, 3 pages.

Office Action, dated Jun. 6, 2019, received in Australian Patent Application No. 2018256626, which corresponds with U.S. Appl. No. 14/536,646, 3 pages.

Notice of Acceptance, dated Aug. 1, 2019, received in Australian Patent Application No. 2018256626, which corresponds with U.S. Appl. No. 14/536,646, 3 pages.

Certificate of Grant, dated Dec. 5, 2019, received in Australian Patent Application No. 2018256626, which corresponds with U.S. Appl. No. 14/536,646, 3 pages.

Office Action, dated Dec. 1, 2016, received in Chinese Patent Application No. 2013800362059, which corresponds with U.S. Appl. No. 14/536,646, 3 pages.

Notice of Allowance, dated Oct. 9, 2017, received in Chinese Patent Application No. 2013800362059, which corresponds with U.S. Appl. No. 14/536,646, 3 pages.

Office Action, dated Jul. 3, 2020, received in Chinese Patent Application No. 201711425148.X, which corresponds with U.S. Appl. No. 14/536,646, 13 pages.

Office Action, dated Jun. 10, 2021, received in Chinese Patent Application No. 201711425148.X, which corresponds with U.S. Appl. No. 14/536,646, 2 pages.

Notice of Allowance, dated Oct. 9, 2021, received in Chinese Patent Application No. 201711425148.X, which corresponds with U.S. Appl. No. 14/536,646, 2 pages.

Office Action, dated Oct. 26, 2020, received in Chinese Patent Application No. 201711422092.2, which corresponds with U.S. Appl. No. 14/536,646, 20 pages.

Notice of Allowance, dated Mar. 22, 2021, received in Chinese Patent Application No. 201711422092.2, which corresponds with U.S. Appl. No. 14/536,646, 2 pages.

Certificate of Grant, dated Apr. 13, 2021, received in Chinese Patent Application No. 201711422092.2, which corresponds with U.S. Appl. No. 14/536,646, 8 pages.

Office Action, dated Nov. 12, 2015, received in European Patent Application No. 13724102.2, which corresponds with U.S. Appl. No. 14/536,646, 6 pages.

Office Action, dated May 31, 2016, received in European Patent Application No. 13724102.2, which corresponds with U.S. Appl. No. 14/536,646, 5 pages.

Notice of Allowance, dated Jan. 4, 2017, received in European Patent Application No. 13724102.2, which corresponds with U.S. Pat. No. 14,536,646, 5 pages.

Patent, dated May 26, 2017, received in European Patent Application No. 13724102.2, which corresponds with U.S. Pat. No. 14,536,646, 1 page.

Office Action, dated Feb. 29, 2016, received in Japanese Patent Application No. 2015-511645, which corresponds with U.S. Appl. No. 14/536,646, 5 pages.

Notice of Allowance, dated Dec. 22, 2016, received in Japanese Patent Application No. 2015-511645, which corresponds with U.S. Appl. No. 14/536,646, 2 pages.

Certificate of Grant, dated Jan. 25, 2019, received in Hong Kong Patent Application No. 2015-511645, which corresponds with U.S. Appl. No. 14/536,646, 4 pages.

Office Action, dated Apr. 3, 2017, received in U.S. Appl. No. 14/536,141, 11 pages.

Notice of Allowance, dated Sep. 20, 2017, received in U.S. Appl. No. 14/536,141, 10 pages.

Office Action, dated Aug. 27, 2015, received in Australian Patent Application No. 2013259614, which corresponds with U.S. Appl. No. 14/536,141, 4 pages.

Notice of Allowance, dated Aug. 15, 2016, received in Australian Patent Application No. 2013259614, which corresponds with U.S. Appl. No. 14/536,141, 1 page.

Office Action, dated Jul. 21, 2017, received in Australian Patent Application No. 2016262773, which corresponds with U.S. Appl. No. 14/536,141, 3 pages.

Notice of Acceptance, dated Jul. 19, 2018, received in Australian Patent Application No. 2016262773, which corresponds with U.S. Appl. No. 14/536,141, 3 pages.

Office Action, dated Jun. 5, 2019, received in Australian Patent Application No. 2018256616, which corresponds with U.S. Appl. No. 14/536,141, 3 pages.

Notice of Acceptance, dated Jan. 22, 2020, received in Australian Patent Application No. 2018256616, which corresponds with U.S. Appl. No. 14/536,141, 3 pages.

Certificate of Grant, dated May 21, 2020, received in Australian Patent Application No. 2018256616, which corresponds with U.S. Appl. No. 14/536,141, 3 pages.

Office Action, dated Mar. 3, 2017, received in Chinese Patent Application No. 201380035893.7, which corresponds with U.S. Appl. No. 14/536,141, 8 pages.

Office Action, dated Feb. 2, 2018, received in Chinese Patent Application No. 201380035893.7, which corresponds with U.S. Appl. No. 14/536,141, 5 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Notice of Allowance, dated Aug. 31, 2018, received in Chinese Patent Application No. 201380035893.7, which corresponds with U.S. Appl. No. 14/536,141, 6 pages.

Office Action, dated Mar. 10, 2021, received in Chinese Patent Application No. 201811142423.1, which corresponds with U.S. Appl. No. 14/536,141, 6 pages.

Office Action, dated Aug. 12, 2021, received in Chinese Patent Application No. 201811142423.1, which corresponds with U.S. Appl. No. 14/536,141, 6 pages.

Notice of Allowance, dated Oct. 26, 2021, received in Chinese Patent Application No. 201811142423.1, which corresponds with U.S. Appl. No. 14/536,141, 2 pages.

Patent, dated Dec. 31, 2021, received in Chinese Patent Application No. 201811142423.1, which corresponds with U.S. Appl. No. 14/536,141, 6 pages.

Patent, dated Oct. 23, 2018, received in Chinese Patent Application No. 201380035893.7, which corresponds with U.S. Appl. No. 14/536,141, 4 pages.

Office Action, dated Jan. 7, 2016, received in European Patent Application No. 13726053.5, which corresponds with U.S. Appl. No. 14/536,141, 10 pages.

Office Action, dated Aug. 31, 2016, received in European Patent Application No. 13726053.5, which corresponds with U.S. Appl. No. 14/536,141, 10 pages.

Office Action, dated Apr. 9, 2018, received in European Patent Application No. 13726053.5, which corresponds with U.S. Appl. No. 14/536,141, 9 pages.

Office Action, dated Mar. 7, 2019, received in European Patent Application No. 13726053.5, which corresponds with U.S. Appl. No. 14/536,141, 5 pages.

Intention to Grant, dated Sep. 6, 2019, received in European Patent Application No. 13726053.5, which corresponds with U.S. Appl. No. 14/536,141, 7 pages.

Decision to Grant, dated Jan. 23, 2020, received in European Patent Application No. 13726053.5, which corresponds with U.S. Appl. No. 14/536,141, 1 page.

Patent, dated Feb. 19, 2020, received in European Patent Application No. 13726053.5, which corresponds with U.S. Appl. No. 14/536,141, 4 pages.

Office Action, dated Feb. 29, 2016, received in Japanese Patent Application No. 2015-511646, which corresponds with U.S. Appl. No. 14/536,141, 3 pages.

Office Action, dated Oct. 25, 2016, received in Japanese Patent Application No. 2015-511646, which corresponds with U.S. Appl. No. 14/536,141, 6 pages.

Notice of Allowance, dated Jun. 30, 2017, received in Japanese Patent Application No. 2015-511646, which corresponds with U.S. Appl. No. 14/536,141, 5 pages.

Patent, dated Jul. 28, 2017, received in Japanese Patent Application No. 2015-511646, which corresponds with U.S. Appl. No. 14/536,141, 3 pages.

Office Action, dated Aug. 10, 2018, received in Japanese Patent Application No. 2017-141953, which corresponds with U.S. Appl. No. 14/536,141, 6 pages.

Office Action, dated Jul. 5, 2019, received in Japanese Patent Application No. 2017-141953, which corresponds with U.S. Appl. No. 14/536,141, 6 pages.

Office Action, dated Dec. 8, 2016, received in U.S. Appl. No. 14/608,942, 9 pages.

Notice of Allowance, dated May 12, 2017, received in U.S. Appl. No. 14/608,942, 10 pages.

Office Action, dated Jan. 29, 2016, received in Australian Patent Application No. 2013368443, which corresponds with U.S. Appl. No. 14/608,942, 3 pages.

Notice of Allowance, dated Mar. 11, 2016, received in Australian Patent Application No. 2013368443, which corresponds with U.S. Appl. No. 14/608,942, 2 pages.

Certificate of Grant, dated Jul. 7, 2016, received in Australian Patent Application No. 14/608,942, which corresponds with U.S. Appl. No. 14/608,942, 3 pages.

Office Action, dated Mar. 29, 2017, received in Australian Patent Application No. 2016201303, which corresponds with U.S. Appl. No. 14/608,942, 3 pages.

Notice of Acceptance, dated Mar. 7, 2018, received in Australian Patent Application No. 2016201303, which corresponds with U.S. Appl. No. 14/608,942, 3 pages.

Certificate of Grant, dated Jul. 5, 2018, received in Australian Patent Application No. 2016201303, which corresponds with U.S. Appl. No. 14/608,942, 4 pages.

Office Action, dated Jun. 16, 2017, received in Chinese Patent Application No. 201380068295.X, which corresponds with U.S. Appl. No. 14/608,942, 6 pages.

Office Action, dated Mar. 28, 2018, received in Chinese Patent Application No. 201380068295.X, which corresponds with U.S. Appl. No. 14/608,942, 5 pages.

Office Action, dated Oct. 8, 2018, received in Chinese Patent Application No. 201380068295.X, which corresponds with U.S. Appl. No. 14/608,942, 3 pages.

Notice of Allowance, dated May 7, 2019, received in Chinese Patent Application No. 201380068295.X, which corresponds with U.S. Appl. No. 14/608,942, 3 pages.

Patent, dated Jul. 5, 2019, received in Chinese Patent Application No. 201380068295.X, which corresponds with U.S. Appl. No. 14/608,942, 8 pages.

Office Action, dated Oct. 7, 2016, received in European Patent Application No. 13798464.7, which corresponds with U.S. Appl. No. 14/608,942, 7 pages.

Decision to Grant, dated Sep. 13, 2018, received in European Patent Application No. 13798464.7, which corresponds with U.S. Appl. No. 14/608,942, 2 pages.

Intention to Grant, dated Nov. 8, 2019, received in European Patent Application No. 18194127.9, which corresponds with U.S. Appl. No. 14/608,942, 7 pages.

Decision to Grant, dated Aug. 20, 2020, received in European Patent Application No. 18194127.9, which corresponds with U.S. Appl. No. 14/608,942, 4 pages.

Patent, dated Sep. 16, 2020, received in European Patent Application No. 18194127.9, which corresponds with U.S. Appl. No. 14/608,942, 4 pages.

Certificate of Grant, dated Jul. 26, 2019, received in Hong Kong, which corresponds with U.S. Appl. No. 14/608,942, 4 pages.

Office Action, dated Jul. 4, 2016, received in Japanese Patent Application No. 2015-549393, which corresponds with U.S. Appl. No. 14/608,942, 4 pages.

Notice of Allowance, dated May 12, 2017, received in Japanese Patent Application No. 2015-549393, which corresponds with U.S. Appl. No. 14/608,942, 5 pages.

Patent, dated Jun. 16, 2017, received in Japanese Patent Application No. 2015-549393, which corresponds with U.S. Appl. No. 14/608,942, 3 pages.

Office Action, dated Apr. 5, 2016, received in Korean Patent Application No. 2015-7018448, which corresponds with U.S. Appl. No. 14/608,942, 6 pages.

Office Action, dated Feb. 24, 2017, received in Korean Patent Application No. 2015-7018448, which corresponds with U.S. Appl. No. 14/608,942, 4 pages.

Notice of Allowance, dated Jan. 15, 2019, received in Korean Patent Application No. 2015-7018448, which corresponds with U.S. Appl. No. 14/608,942, 5 pages.

Patent, dated Mar. 8, 2019, received in Korean Patent Application No. 2015-7018448, which corresponds with U.S. Appl. No. 14/608,942, 4 pages.

Office Action, dated Jul. 17, 2017, received in U.S. Appl. No. 14/536,166, 19 pages.

Notice of Allowance, dated Feb. 28, 2018, received in U.S. Appl. No. 14/536,166, 5 pages.

Office Action, dated Aug. 1, 2016, received in U.S. Appl. No. 14/536,203, 14 pages.

Notice of Allowance, dated Feb. 1, 2017, received in U.S. Appl. No. 14/536,203, 9 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Office Action, dated Jul. 9, 2015, received in Australian Patent Application No. 2013259630, which corresponds with U.S. Appl. No. 14/536,203, 3 pages.

Notice of Allowance, dated Jun. 15, 2016, received in Australian Patent Application No. 2013259630, which corresponds with U.S. Appl. No. 14/536,203, 3 pages.

Certificate of Grant, dated Oct. 21, 2016, received in Australian Patent Application No. 2013259630, which corresponds with U.S. Appl. No. 14/536,203, 3 pages.

Office Action, dated Jul. 4, 2017, received in Australian Patent Application No. 2016238917, which corresponds with U.S. Appl. No. 14/536,203, 5 pages.

Notice of Acceptance, dated Jul. 19, 2018, received in Australian Patent Application No. 2016238917, which corresponds with U.S. Appl. No. 14/536,203, 3 pages.

Certificate of Grant, dated Nov. 1, 2018, received in Australian Patent Application No. 2016238917, which corresponds with U.S. Appl. No. 14/536,203, 1 page.

Office Action, dated Aug. 20, 2018, received in Australian Patent Application No. 2018250481, which corresponds with U.S. Appl. No. 14/536,203, 2 pages.

Notice of Allowance, dated Apr. 29, 2020, received in Australian Patent Application No. 2018250481, which corresponds with U.S. Appl. No. 14/536,203, 3 pages.

Certificate of Grant, dated Sep. 3, 2020, received in Australian Patent Application No. 2018250481, which corresponds with U.S. Appl. No. 14/536,203, 4 pages.

Office Action, dated Oct. 25, 2017, received in Chinese Patent Application No. 201380035977.0, which corresponds with U.S. Appl. No. 14/536,203, 5 pages.

Notice of Allowance, dated Apr. 4, 2018, received in Chinese Patent Application No. 201380035977.0, which corresponds with U.S. Appl. No. 14/536,203, 3 pages.

Patent, dated Jul. 6, 2018, received in Chinese Patent Application No. 201380035977.0, which corresponds with U.S. Appl. No. 14/536,203, 4 pages.

Office Action, dated Jan. 26, 2021, received in Chinese Patent Application No. 201810632507.7, 5 pages.

Notice of Allowance, dated Aug. 11, 2021, received in Chinese Patent Application No. 201810632507.7, which corresponds with U.S. Appl. No. 14/536,203, 1 page.

Patent, dated Oct. 22, 2021, received in Chinese Patent Application No. 201810632507.7, which corresponds with U.S. Appl. No. 14/536,203, 7 pages.

Office Action, dated Nov. 11, 2015, received in European Patent Application No. 13724104.8, which corresponds with U.S. Appl. No. 14/536,203, 5 pages.

Office Action, dated May 31, 2016, received in European Patent Application No. 13724104.8, which corresponds with U.S. Appl. No. 14/536,203, 5 pages.

Office Action, dated Dec. 6, 2017, received in European Patent Application No. 13724104.8, which corresponds with U.S. Appl. No. 14/536,203, 9 pages.

Decision to Grant, dated Oct. 24, 2018, received in European Patent Application No. 13724104.8, which corresponds with U.S. Appl. No. 14/536,203, 5 pages.

Intention to Grant, dated Mar. 18, 2019, received in European Patent Application No. 13724104.8, which corresponds with U.S. Appl. No. 14/536,203, 9 pages.

Decision to Grant, dated Aug. 8, 2019, received in European Patent Application No. 13724104.8, which corresponds with U.S. Appl. No. 14/536,203, 1 page.

Certificate of Grant, dated Sep. 4, 2019, received in European Patent Application No. 13724104.8, which corresponds with U.S. Appl. No. 14/536,203, 4 pages.

Patent, dated Sep. 27, 2019, received in Hong Kong Patent Application No. 15108904.1, which corresponds with U.S. Appl. No. 14/536,203, 6 pages.

Office Action, dated Feb. 15, 2016, received in Japanese Patent Application No. 2015-511650, which corresponds with U.S. Appl. No. 14/536,203, 5 pages.

Notice of Allowance, dated Aug. 5, 2016, received in Japanese Patent Application No. 2015-511650, which corresponds with U.S. Appl. No. 14/536,203, 4 pages.

Certificate of Patent, dated Sep. 9, 2016, received in Japanese Patent Application No. 2015-511650, which corresponds with U.S. Appl. No. 14/536,203, 3 pages.

Office Action, dated Jun. 23, 2017, received in Japanese Patent Application No. 2016173113, which corresponds with U.S. Appl. No. 14/536,203, 5 pages.

Notice of Allowance, dated Jan. 12, 2018, received in Japanese Patent Application No. 2016173113, which corresponds with U.S. Appl. No. 14/536,203, 5 pages.

Patent, dated Feb. 16, 2018, received in Japanese Patent Application No. 2016173113, which corresponds with U.S. Appl. No. 14/536,203, 3 pages.

Office Action, dated Oct. 19, 2018, received in Japanese Patent Application No. 2018-022394, which corresponds with U.S. Appl. No. 14/536,203, 4 pages.

Office Action, dated Sep. 30, 2019, received in Japanese Patent Application No. 2018-022394, which corresponds with U.S. Appl. No. 14/536,203, 5 pages.

Office Action, dated Jan. 22, 2021, received in Japanese Patent Application No. 2018-022394, which corresponds with U.S. Appl. No. 14/536,203, 2 pages.

Notice of Allowance, dated Dec. 3, 2021, received in Japanese Patent Application No. 2018-022394, which corresponds with U.S. Appl. No. 14/536,203, 2 pages.

Office Action, dated Dec. 4, 2015, received in Korean Patent Application No. 2014-7034520, which corresponds with U.S. Appl. No. 14/536,203, 4 pages.

Notice of Allowance, dated Sep. 1, 2016, received in Korean Patent Application No. 2014-7034520, which corresponds with U.S. Appl. No. 14/536,203, 5 pages.

Office Action, dated Feb. 6, 2017, received in Korean Patent Application No. 2016-7033834, which corresponds with U.S. Appl. No. 14/536,203, 4 pages.

Notice of Allowance, dated Oct. 30, 2017, received in Korean Patent Application No. 2016-7033834, which corresponds with U.S. Appl. No. 14/536,203, 5 pages.

Patent, dated Jan. 23, 2018, received in Korean Patent Application No. 2016-7033834, which corresponds with U.S. Appl. No. 14/536,203, 4 pages.

Office Action, dated Oct. 20, 2017, received in U.S. Appl. No. 14/608,965, 14 pages.

Office Action, dated Jul. 2, 2018, received in U.S. Appl. No. 14/608,965, 16 pages.

Final Office Action, dated Jan. 10, 2019, received in U.S. Appl. No. 14/608,965, 17 pages.

Notice of Allowance dated Nov. 7, 2019, received in U.S. Appl. No. 14/608,965, 17 pages.

Notice of Allowance dated Jan. 2, 2020, received in U.S. Appl. No. 14/608,965, 5 pages.

Office action, dated Oct. 11, 2017, received in Chinese Patent Application No. 201380074060.1, which corresponds with U.S. Appl. No. 14/608,965, 5 pages.

Office action, dated Aug. 1, 2018, received in Chinese Patent Application No. 201380074060.1, which corresponds with U.S. Appl. No. 14/608,965, 5 pages.

Office action, dated Nov. 1, 2018, received in Chinese Patent Application No. 201380074060.1, which corresponds with U.S. Appl. No. 14/608,965, 3 pages.

Office action, dated Apr. 3, 2019, received in Chinese Patent Application No. 201380074060.1, which corresponds with U.S. Appl. No. 14/608,965, 3 pages.

Patent, dated May 17, 2019, received in Chinese Patent Application No. 201380074060.1, which corresponds with U.S. Appl. No. 14/608,965, 6 pages.

Office Action, dated Jul. 22, 2016, received in European Office Action No. 13798465.4, which corresponds with U.S. Appl. No. 14/608,965, 3 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Oral Proceedings, dated Mar. 7, 2018, received in European Office Action No. 13798465.4, which corresponds with U.S. Appl. No. 14/608,965, 5 pages.

Decision to Grant, dated Sep. 6, 2018, received in European Office Action No. 13798465.4, which corresponds with U.S. Appl. No. 14/608,965, 2 pages.

Office Action, dated Oct. 20, 2016, received in U.S. Appl. No. 14/536,247, 10 pages.

Final Office Action, dated Mar. 24, 2017, received in U.S. Appl. No. 14/536,247, 14 pages.

Notice of Allowance, dated Nov. 22, 2017, received in U.S. Appl. No. 14/536,247, 6 pages.

Office Action, dated Mar. 24, 2017, received in U.S. Appl. No. 14/536,267, 12 pages.

Notice of Allowance, dated Nov. 9, 2017, received in U.S. Appl. No. 14/536,267, 8 pages.

Notice of Allowance, dated Jun. 1, 2018, received in U.S. Appl. No. 14/536,267, 5 pages.

Office Action, dated Aug. 10, 2015, received in Australian Patent Application No. 2013259637, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Notice of Allowance, dated Jun. 28, 2016, received in Australian Patent Application No. 2013259637, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Certificate of Grant, dated Oct. 21, 2016, received in Australian Patent Application No. 2013259637, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Office Action, dated Mar. 24, 2017, received in Australian Patent Application No. 2016204411, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Notice of Acceptance, dated Feb. 27, 2018, received in Australian Patent Application No. 2016204411, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Certificate of Grant, dated Jun. 28, 2018, received in Australian Patent Application No. 2016204411, which corresponds with U.S. Appl. No. 14/536,267, 4 pages.

Office Action, dated Mar. 15, 2019, received in Australian Patent Application No. 2018204236, which corresponds with U.S. Appl. No. 14/5326,267, 5 pages.

Notice of Acceptance, dated Apr. 29, 2019, received in Australian Patent Application No. 2018204236, which corresponds with U.S. Appl. No. 14/5326,267, 3 pages.

Certificate of Grant, dated Aug. 28, 2019, received in Australian Patent Application No. 2018204236, which corresponds with U.S. Patent Application No. 14/5326,267, 4 pages.

Office Action, dated Dec. 9, 2016, received in Chinese Patent Application No. 2016120601564130, which corresponds with U.S. Appl. No. 14/536,267, 4 pages.

Notice of Allowance, dated Jan. 29, 2018, received in Chinese Patent Application No. 201380035968.1, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Patent, dated Apr. 20, 2018, received in Chinese Patent Application No. 201380035968.1, which corresponds with U.S. Appl. No. 14/536,267, 4 pages.

Office Action, dated Nov. 28, 2018, received in Chinese Patent Application No. 201610537334.1, which corresponds with U.S. Appl. No. 14/536,267, 5 pages.

Office Action, dated Jul. 11, 2019, received in Chinese Patent Application No. 201610537334.1, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Office Action, dated Sep. 30, 2019, received in Chinese Patent Application No. 201610537334.1, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Office Action, dated Dec. 20, 2019, received in Chinese Patent Application No. 201610537334.1, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Office Action, dated Apr. 20, 2020, received in Chinese Patent Application No. 201610537334.1, which corresponds with U.S. Appl. No. 14/536,267, 4 pages.

Patent, dated Sep. 29, 2020, received in Chinese Patent Application No. 201610537334.1, which corresponds with U.S. Appl. No. 14/536,267, 7 pages.

Office Action, dated Jun. 13, 2018, received in Chinese Patent Application No. 201810332044.2, which corresponds with U.S. Appl. No. 14/536,267, 2 pages.

Office Action, dated Jan. 20, 2021, received in Chinese Patent Application No. 201810332044.2, which corresponds with U.S. Appl. No. 14/536,267, 15 pages.

Office Action, dated Jul. 19, 2021, received in Chinese Patent Application No. 201810332044.2, which corresponds with U.S. Appl. No. 14/536,267, 1 page.

Office Action, dated Nov. 23, 2021, received in Chinese Patent Application No. 201810332044.2, which corresponds with U.S. Appl. No. 14/536,267, 2 pages.

Office Action, dated Jan. 25, 2018, received in European Patent Application No. 13724106.3, which corresponds with U.S. Appl. No. 14/536,267, 5 pages.

Intention to Grant, dated Jun. 27, 2018, received in European Patent Application No. 13724106.3, which corresponds with U.S. Appl. No. 14/536,267, 5 pages.

Decision to Grant, dated Oct. 18, 2018, received in European Patent Application No. 13724106.3, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Grant Certificate, dated Nov. 14, 2018, received in European Patent Application No. 13724106.3, which corresponds with U.S. Appl. No. 14/536,267, 3 pages. 4 pages.

Office Action, dated Sep. 13, 2017, received in European Patent Application No. 16177863.4, which corresponds with U.S. Appl. No. 14/536,267, 6 pages.

Decision to Grant, dated Nov. 29, 2018, received in European Patent Application No. 16177863.4, which corresponds with U.S. Appl. No. 14/536,267, 4 pages.

Patent, dated Dec. 26, 2018, received in European Patent Application No. 16177863.4, which corresponds with U.S. Appl. No. 14/536,267, 4 pages.

Office Action, dated Aug. 29, 2019, received in European Patent Application No. 18183789.9, which corresponds with U.S. Appl. No. 16/262,800, 9 pages.

Office Action, dated Aug. 21, 2020, received in European Patent Application No. 18183789.9, which corresponds with U.S. Appl. No. 16/262,800, 9 pages.

Patent, dated Aug. 30, 2019, received in Hong Kong Patent Application No. 15107537.8, which corresponds with U.S. Appl. No. 14/536,267, 9 pages.

Patent, dated Nov. 8, 2019, received in Hong Kong Patent Application No. 15108890.7, which corresponds with U.S. Appl. No. 14/536,267, 4 pages.

Office Action, dated Jan. 29, 2016, received in Japanese Patent Application No. 2015-511652, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Notice of Allowance, dated Sep. 26, 2016, received in Japanese Patent Application No. 2015-511652, which corresponds with U.S. Appl. No. 14/536,267, 5 pages.

Office Action, dated Mar. 3, 2017, received in Japanese Patent Application No. 2016-125839, which corresponds with U.S. Appl. No. 14/536,267, 6 pages.

Notice of Allowance, dated Nov. 17, 2017, received in Japanese Patent Application No. 2016-125839, which corresponds with U.S. Appl. No. 14/536,267, 5 pages.

Office Action, dated Feb. 4, 2019, received in Japanese Patent Application No. 2017-237035, which corresponds with U.S. Appl. No. 14/536,267, 7 pages.

Notice of Allowance, dated Sep. 9, 2019, received in Japanese Patent Application No. 2017-237035, which corresponds with U.S. Appl. No. 14/536,267, 5 pages.

Patent, dated Sep. 27, 2019, received in Japanese Patent Application No. 2017-237035, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Office Action, dated Dec. 4, 2015, received in Korean Patent Application No. 2014-7034530, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Notice of Allowance, dated Sep. 1, 2016, received in Korean Patent Application No. 2014-7034530, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Office Action, dated Jan. 5, 2017, received in Korean Patent Application No. 2016-7029533, which corresponds with U.S. Appl. No. 14/536,267, 2 pages.

Notice of Allowance, dated Sep. 1, 2017, received in Korean Patent Application No. 2016-7029533, which corresponds with U.S. Appl. No. 14/536,267, 4 pages.

Patent, dated Dec. 1, 2017, received in Korean Patent Application No. 2016-7029533, which corresponds with U.S. Appl. No. 14/536,267, 2 pages.

Office Action, dated Jan. 29, 2018, received in Korean Patent Application No. 2017-7034838, which corresponds with U.S. Appl. No. 14/536,267, 4 pages.

Notice of Allowance, dated Dec. 3, 2018, received in Korean Patent Application No. 2017-7034838, which corresponds with U.S. Appl. No. 14/536,267, 5 pages.

Patent, dated Mar. 4, 2019, received in Korean Patent Application No. 2017-7034838, which corresponds with U.S. Appl. No. 14/536,267, 4 pages.

Office Action, dated Apr. 7, 2017, received in U.S. Appl. No. 14/536,291, 11 pages.

Notice of Allowance, dated Dec. 1, 2017, received in U.S. Appl. No. 14/536,291, 19 pages.

Notice of Allowance, dated Mar. 20, 2018, received in U.S. Appl. No. 14/536,291, 5 pages.

Office Action, dated Aug. 18, 2015, received in Australian Patent Application No. 2013259642, which corresponds with U.S. Appl. No. 14/536,291, 3 pages.

Office Action, dated Jul. 25, 2016, received in Australian Patent Application No. 2013259642, which corresponds with U.S. Appl. No. 14/536,291, 3 pages.

Office Action, dated Aug. 10, 2016, received in Australian Patent Application No. 2013259642, which corresponds with U.S. Appl. No. 14/536,291, 4 pages.

Office Action, dated Jul. 21, 2017, received in Australian Patent Application No. 2016216658, which corresponds with U.S. Appl. No. 14/536,291, 3 pages.

Notice of Acceptance, dated Jul. 19, 2018, received in Australian Patent Application No. 2016216658, which corresponds with U.S. Appl. No. 14/536,291, 3 pages.

Patent, dated Nov. 30, 2018, received in Australian Patent Application No. 2016216658, which corresponds with U.S. Appl. No. 14/536,291, 4 pages.

Innovation Patent, dated Sep. 1, 2016, received in Australian Patent Application No. 2016101481, which corresponds with U.S. Appl. No. 14/536,291, 1 page.

Office Action, dated Sep. 29, 2016, received in Australian Patent Application No. 2016101481, which corresponds with U.S. Appl. No. 14/536,291, 3 pages.

Office Action, dated Oct. 23, 2017, received in Chinese Patent Application No. 201380035986.X, which corresponds with U.S. Appl. No. 14/536,291, 9 pages.

Notice of Allowance, dated Jun. 24, 2020, received in Chinese Patent Application No. 201710781246.0, which corresponds with U.S. Appl. No. 14/536,291, 5 pages.

Patent, dated Jul. 31, 2020, received in Chinese Patent Application No. 201710781246.0, which corresponds with U.S. Appl. No. 14/536,291, 6 pages.

Office Action, dated Jul. 17, 2020, received in Chinese Patent Application No. 2018100116175.X, which corresponds with U.S. Appl. No. 14/536,291, 15 pages.

Office Action, dated Nov. 17, 2020, received in Chinese Patent Application No. 2018100116175.X, which corresponds with U.S. Appl. No. 14/536,291, 16 pages.

Notice of Allowance, dated Mar. 29, 2021, received in Chinese Patent Application No. 2018100116175.X, which corresponds with U.S. Appl. No. 14/536,291, 1 page.

Patent, dated Apr. 27, 2021, received in Chinese Patent Application No. 2018100116175.X, which corresponds with U.S. Appl. No. 14/536,291, 6 pages.

Office Action, dated Jan. 7, 2016, received in European Patent Application No. 13724107.1, which corresponds with U.S. Appl. No. 14/536,291, 11 pages.

Office Action, dated Aug. 22, 2016, received in European Patent Application No. 13724107.1, which corresponds with U.S. Appl. No. 14/536,291, 7 pages.

Office Action, dated Mar. 23, 2017, received in European Patent Application No. 13724107.1, which corresponds with U.S. Appl. No. 14/536,291, 8 pages.

Intention to Grant, dated Jan. 8, 2019, received in European Patent Application No. 17186744.3, which corresponds with U.S. Appl. No. 14/536,291, 7 pages.

Decision to Grant, dated Oct. 31, 2019, received in European Patent Application No. 17186744.3, which corresponds with U.S. Appl. No. 14/536,291, 3 pages.

Patent, dated Nov. 27, 2019, received in European Patent Application No. 17186744.3, which corresponds with U.S. Appl. No. 14/536,291, 4 pages.

Office Action, dated Mar. 8, 2016, received in Japanese Patent Application No. 2015-511655, which corresponds with U.S. Appl. No. 14/536,291, 4 pages.

Final Office Action, dated Dec. 22, 2016, received in Japanese Patent Application No. 2015-511655, which corresponds with U.S. Appl. No. 14/536,291, 3 pages.

Office Action, dated Jun. 29, 2018, received in Japanese Patent Application No. 2017-083027, which corresponds with U.S. Appl. No. 14/536,291, 5 pages.

Patent, dated Feb. 22, 2019, received in Japanese Patent Application No. 2017-083027, which corresponds with U.S. Appl. No. 14/536,291, 3 pages.

Notice of Allowance, dated Jan. 15, 2019, received in Japanese Patent Application No. 2017-083027, which corresponds with U.S. Appl. No. 14/536,291, 5 pages.

Office Action, dated Oct. 19, 2017, received in U.S. Appl. No. 14/608,985, 13 pages.

Notice of Allowance, dated Apr. 20, 2018, received in U.S. Appl. No. 14/608,985, 5 pages.

Office Action, dated Jan. 15, 2016, received in Australian Patent Application No. 2013368445, which corresponds with U.S. Appl. No. 14/608,985, 3 pages.

Notice of Allowance, dated Jan. 18, 2017, received in Australian Patent Application No. 2013368445, which corresponds with U.S. Appl. No. 14/608,985, 3 pages.

Patent, dated May 18, 2017, received in Australian Patent Application No. 2013368445, which corresponds with U.S. Appl. No. 14/608,985, 1 page.

Office Action, dated May 19, 2017, received in Chinese Patent Application No. 201380068399.0, which corresponds with U.S. Appl. No. 14/608,985, 5 pages.

Notice of Allowance, dated Sep. 19, 2017, received in Chinese Patent Application No. 201380068399.0, which corresponds with U.S. Appl. No. 14/608,985, 3 pages.

Patent, dated Dec. 8, 2017, received in Chinese Patent Application No. 201380068399.0, which corresponds with U.S. Appl. No. 14/608,985, 4 pages.

Office Action, dated Jul. 25, 2016, received in European Patent Application No. 13811032.5, which corresponds with U.S. Appl. No. 14/608,985, 8 pages.

Office Action, dated Feb. 27, 2017, received in European Patent Application No. 13811032.5, which corresponds with U.S. Appl. No. 14/608,985, 6 pages.

Summons, dated Oct. 6, 2017, received in European Patent Application No. 13811032.5, which corresponds with U.S. Appl. No. 14/608,985, 6 pages.

Intention to Grant, dated Jan. 16, 2019, received in European Patent Application No. 13811032.5, which corresponds with U.S. Appl. No. 14/608,985, 9 pages.

Decision to Grant, dated Aug. 1, 2019, received in European Patent Application No. 13811032.5, which corresponds with U.S. Appl. No. 14/608,985, 2 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Certificate of Grant, dated Aug. 28, 2019, received in European Patent Application No. 13811032.5, which corresponds with U.S. Appl. No. 14/608,985, 4 pages.

Certificate of Grant, dated Jun. 29, 2018, received in Hong Kong Patent Application No. 15112851.6, which corresponds with U.S. Appl. No. 14/608,985, 2 pages.

Office Action, dated Apr. 25, 2016, received in Japanese Patent Application No. 2015-550384, which corresponds with U.S. Appl. No. 14/608,985, 4 pages.

Notice of Allowance, dated Jan. 24, 2017, received in Japanese Patent Application No. 2015-550384, which corresponds with U.S. Appl. No. 14/608,985, 5 pages.

Patent, dated Feb. 24, 2017, received in Japanese Patent Application No. 2015-550384, which corresponds with U.S. Appl. No. 14/608,985, 2 pages.

Office Action, dated Nov. 4, 2016, received in Korean Patent Application No. 2015-7019984, which corresponds with U.S. Appl. No. 14/608,985, 8 pages.

Notice of Allowance, dated Sep. 19, 2017, received in Korean Patent Application No. 2015-7019984, which corresponds with U.S. Appl. No. 14/608,985, 4 pages.

Patent, dated Dec. 19, 2017, received in Korean Patent Application No. 2015-7019984, which corresponds with U.S. Appl. No. 14/608,985, 3 pages.

Office Action, dated Mar. 24, 2017, received in U.S. Appl. No. 14/609,006, 13 pages.

Final Office Action, dated Sep. 21, 2017, received in U.S. Appl. No. 14/609,006, 17 pages.

Office Action, dated Mar. 20, 2018, received in U.S. Appl. No. 14/609,006, 13 pages.

Office Action, dated Oct. 11, 2018, received in U.S. Appl. No. 14/609,006, 12 pages.

Final Office Action, dated May 23, 2019, received in U.S. Appl. No. 14/609,006, 14 pages.

Office Action, dated Jan. 7, 2020, received in U.S. Appl. No. 14/609,006, 17 pages.

Final Office Action, dated Jun. 15, 2020, received in U.S. Appl. No. 14/609,006, 19 pages.

Office Action, dated Apr. 19, 2017, received in U.S. Appl. No. 14/536,296, 12 pages.

Final Office Action, dated Nov. 2, 2017, received in U.S. Appl. No. 14/536,296, 13 pages.

Notice of Allowance, dated Mar. 14, 2018, received in U.S. Appl. No. 14/536,296, 8 pages.

Office Action, dated Nov. 1, 2017, received in U.S. Appl. No. 14/536,648, 22 pages.

Final Office Action, dated Aug. 7, 2018, received in U.S. Appl. No. 14/536,648, 14 pages.

Office Action, dated Jan. 2, 2019, received in U.S. Appl. No. 14/536,648, 12 pages.

Notice of Allowance, dated Jul. 2, 2019, received in U.S. Appl. No. 14/536,648, 5 pages.

Office Action, dated Jul. 21, 2017, received in Australian Patent Application No. 2016247194, which corresponds with U.S. Appl. No. 14/536,648, 3 pages.

Notice of Acceptance, dated Jul. 19, 2018, received in Australian Patent Application No. 2016247194, which corresponds with U.S. Appl. No. 14/536,648, 3 pages.

Office Action, dated Jul. 24, 2020, received in Chinese Patent Application No. 201711422121.5, which corresponds with U.S. Appl. No. 14/536,648, 10 pages.

Notice of Allowance, dated Feb. 2, 2021, received in Chinese Patent Application No. 201711422121.5, which corresponds with U.S. Appl. No. 14/536,648, 1 page.

Patent, dated Mar. 9, 2021, received in Chinese Patent Application No. 201711422121.5, which corresponds with U.S. Appl. No. 14/536,648, 7 pages.

Intention to Grant, dated Apr. 1, 2019, received in European Patent Application No. 17153418.3, which corresponds with U.S. Appl. No. 14/536,648, 7 pages.

Decision to Grant, dated Aug. 16, 2019, received in European Patent Application No. 17153418.3, which corresponds with U.S. Appl. No. 14/536,648, 3 pages.

Grant Certificate, dated Sep. 11, 2019, received in European Patent Application No. 17153418.3, which corresponds with U.S. Appl. No. 14/536,648, 3 pages.

Office Action, dated Apr. 27, 2018, received in Japanese Patent Application No. 2017-008764, which corresponds with U.S. Appl. No. 14/536,648, 5 pages.

Notice of Allowance, dated Feb. 4, 2019, received in Japanese Patent Application No. 2017-008764, which corresponds with U.S. Appl. No. 14/536,648, 5 pages.

Patent, dated Mar. 1, 2019, received in Japanese Patent Application No. 2017-008764, which corresponds with U.S. Appl. No. 14/536,648, 3 pages.

Office Action, dated Jan. 19, 2017, received in U.S. Appl. No. 14/609,042, 12 pages.

Notice of Allowance, dated Jul. 10, 2017, received in U.S. Appl. No. 14/609,042, 8 pages.

Office Action, dated Aug. 24, 2018, received in Japanese Patent Application No. 2017-113598, which corresponds with U.S. Appl. No. 14/609,042, 6 pages.

Notice of Allowance, dated Apr. 9, 2019, received in Japanese Patent Application No. 2017-113598, which corresponds with U.S. Appl. No. 14/609,042, 5 pages.

Patent, dated Apr. 19, 2019, received in Japanese Patent Application No. 2017-113598, which corresponds with U.S. Appl. No. 14/609,042, 2 pages.

Notice of Allowance, dated Dec. 17, 2018, received in Korean Patent Application No. 2017-7008614, which corresponds with U.S. Appl. No. 14/609,042, 5 pages.

Patent, dated Mar. 8, 2019, received in Korean Patent Application No. 2017-7008614, which corresponds with U.S. Appl. No. 14/609,042, 4 pages.

Office Action, dated Mar. 31, 2016, received in U.S. Appl. No. 14/864,737, 17 pages.

Notice of Allowance, dated Feb. 27, 2017, received in U.S. Appl. No. 14/864,737, 9 pages.

Notice of Allowance, dated Jun. 19, 2017, received in U.S. Appl. No. 14/864,737, 8 pages.

Office Action, dated Apr. 16, 2018, received in Australian Patent Application No. 2016233792, which corresponds with U.S. Appl. No. 14/864,737, 2 pages.

Notice of Acceptance, dated Mar. 12, 2019, received in Australian Patent Application No. 2016233792, which corresponds with U.S. Appl. No. 14/864,737, 5 pages.

Certificate of Grant, dated Jul. 4, 2019, received in Australian Patent Application No. 2016233792, which corresponds with U.S. Appl. No. 14/864,737, 1 page.

Office Action, dated Sep. 11, 2018, received in Chinese Patent Application No. 201610159295.6, which corresponds with U.S. Appl. No. 14/864,737, 6 pages.

Notice of Allowance, dated Apr. 17, 2019, received in Chinese Patent Application No. 201610159295.6, which corresponds with U.S. Appl. No. 14/864,737, 3 pages.

Patent, dated May 31, 2019, received in Chinese Patent Application No. 201610159295.6, which corresponds with U.S. Appl. No. 14/864,737, 7 pages.

Notice of Allowance, dated Jul. 1, 2016, received in Chinese Patent Application No. 201620214376.7, which corresponds with U.S. Appl. No. 14/864,737, 3 pages.

Patent, dated Aug. 3, 2016, received in Chinese Patent Application No. 201620214376.7, which corresponds with U.S. Appl. No. 14/864,737, 5 pages.

Certificate of Registration, dated Jun. 20, 2016, received in German Patent Application No. 202016001845.1, which corresponds with U.S. Appl. No. 14/864,737, 3 pages.

Office Action, dated Apr. 5, 2016, received in Danish Patent Application No. 201500577, which corresponds with U.S. Appl. No. 14/864,737, 7 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Intention to Grant, dated Aug. 2, 2016, received in Danish Patent Application No. 201500577, which corresponds with U.S. Appl. No. 14/864,737, 2 pages.

Decision to grant, dated Mar. 29, 2018, received in European Patent Application No. 16710871.1, which corresponds with U.S. Appl. No. 14/864,737, 2 pages.

Grant Certificate, dated Apr. 25, 2018, received in European Patent Application No. 16710871.1, which corresponds with U.S. Appl. No. 14/864,737, 2 pages.

Office Action, dated May 15, 2017, received in Japanese Patent Application No. 2016-558331, which corresponds with U.S. Appl. No. 14/864,737, 5 pages.

Notice of Allowance, dated Jun. 23, 2017, received in Japanese Patent Application No. 2016-558331, which corresponds with U.S. Appl. No. 14/864,737, 5 pages.

Patent, dated Jul. 28, 2017, received in Japanese Patent Application No. 2016-558331, which corresponds with U.S. Appl. No. 14/864,737, 3 pages.

Office Action, dated Feb. 14, 2018, received in Korean Patent Application No. 2017-7030129, which corresponds with U.S. Appl. No. 14/864,737, 17 pages.

Patent, dated Dec. 26, 2018, received in Korean Patent Application No. 2017-7030129, which corresponds with U.S. Appl. No. 14/864,737, 4 pages.

Patent, dated Jul. 12, 2017, received in Dutch Patent Application No. 2016452, which corresponds with U.S. Appl. No. 14/864,737, 2 pages.

Office Action, dated Jun. 27, 2016, received in U.S. Appl. No. 14/866,981, 22 pages.

Notice of Allowance, dated Oct. 24, 2016, received in U.S. Appl. No. 14/866,981, 7 pages.

Notice of Allowance, dated Feb. 10, 2017, received in U.S. Appl. No. 14/866,981, 5 pages.

Office Action, dated May 10, 2016, received in Australian Patent Application No. 2016100254, which corresponds with U.S. Appl. No. 14/866,981, 6 pages.

Patent, dated Nov. 2, 2016, received in Australian Patent Application No. 2016100254, which corresponds with U.S. Appl. No. 14/866,981, 1 page.

Office Action, dated Nov. 5, 2018, received in Chinese Patent Application No. 201610131415.1, which corresponds with U.S. Appl. No. 14/866,981, 6 pages.

Office Action, dated Jul. 16, 2019, received in Chinese Patent Application No. 201610131415.1, which corresponds with U.S. Appl. No. 14/866,981, 4 pages.

Office Action, dated Mar. 16, 2020, received in Chinese Patent Application No. 201610131415.1, which corresponds with U.S. Appl. No. 14/866,981, 3 pages.

Notice of Allowance, dated Dec. 4, 2020, received in Chinese Patent Application No. 201610131415.1, which corresponds with U.S. Appl. No. 14/866,981, 3 pages.

Patent, dated Jan. 22, 2021, received in Chinese Patent Application No. 201610131415.1, which corresponds with U.S. Appl. No. 14/866,981, 6 pages.

Notice of Allowance, dated Jul. 27, 2016, received in Chinese Patent Application No. 201620176169.7, which corresponds with U.S. Appl. No. 14/866,981, 3 pages.

Patent, dated Sep. 28, 2016, received in Chinese Patent Application No. 201620176169.7, which corresponds with U.S. Appl. No. 14/866,981, 4 pages.

Certificate of Registration, dated Jun. 20, 2016, received in German Patent Application No. 202016001514.2, which corresponds with U.S. Appl. No. 14/864,737, 3 pages.

Office Action, dated Mar. 18, 2016, received in Danish Patent Application No. 201500575, which corresponds with U.S. Appl. No. 14/866,981, 9 pages.

Office Action, dated Dec. 5, 2016, received in Danish Patent Application No. 201500575, which corresponds with U.S. Appl. No. 14/866,981, 3 pages.

Office Action, dated Jul. 7, 2017, received in Danish Patent Application No. 201500575, 4 pages.

Patent, Nov. 16, 2017, received in Dutch Patent Application No. 2016375, which corresponds with U.S. Appl. No. 14/866,981, 2 pages.

Office Action, dated Dec. 15, 2017, received in U.S. Appl. No. 14/866,159, 35 pages.

Notice of Allowance, dated May 18, 2018, received in U.S. Appl. No. 14/866,159, 8 pages.

Office Action, dated May 19, 2016, received in Australian Patent Application No. 2016100251, which corresponds with U.S. Appl. No. 14/866,159, 5 pages.

Office Action, dated Jun. 5, 2018, received in Chinese Patent Application No. 201610137839.9, which corresponds with U.S. Appl. No. 14/866,159, 11 pages.

Notice of Allowance, dated Dec. 6, 2018, received in Chinese Patent Application No. 201610137839.9, which corresponds with U.S. Appl. No. 14/866,159, 3 pages.

Patent, dated Feb. 19, 2019, received in Chinese Patent Application No. 201610137839.9, which corresponds with U.S. Appl. No. 14/866,159, 6 pages.

Office Action, dated Jul. 5, 2016, received in Chinese Patent Application No. 201620186008.6, which corresponds with U.S. Appl. No. 14/866,159, 3 pages.

Certificate of Registration, dated Jun. 16, 2016, received in German Patent No. 202016001483.9, which corresponds with U.S. Pat. No. 14,866,159, 3 pages.

Office Action, dated Mar. 9, 2016, received in Danish Patent Application No. 201500574, which corresponds with U.S. Appl. No. 14/866,159, 11 pages.

Office Action, dated Sep. 27, 2016, received in Danish Patent Application No. 201500574, which corresponds with U.S. Appl. No. 14/866,159, 4 pages.

Office Action, dated Mar. 14, 2017, received in Danish Patent Application No. 14/866,159, which corresponds with U.S. Appl. No. 14/866,159, 5 pages.

Office Action, dated Jul. 6, 2017, received in Danish Patent Application No. 201500574, which corresponds with U.S. Appl. No. 14/866,159, 3 pages.

Office Action, dated Jan. 10, 2018, received in Danish Patent Application No. 201500574, which corresponds with U.S. Appl. No. 14/866,159, 2 pages.

Notice of Allowance, dated Mar. 21, 2018, received in Danish Patent Application No. 201500574, which corresponds with U.S. Appl. No. 14/866,159, 2 pages.

Patent, dated May 22, 2018, received in Danish Patent Application No. 201500574, which corresponds with U.S. Appl. No. 14/866,159, 2 pages.

Intention to Grant, dated Oct. 28, 2019, received in European Patent Application No. 16707356.8, which corresponds with U.S. Appl. No. 14/866,159, 7 pages.

Decision to Grant, dated Mar. 5, 2020, received in European Patent Application No. 16707356.8, which corresponds with U.S. Appl. No. 14/866,159, 2 pages.

Patent, dated Apr. 1, 2020, received in European Patent Application No. 16707356.8, which corresponds with U.S. Appl. No. 14/866,159, 3 pages.

Patent, dated Sep. 7, 2017, received in Dutch Patent Application No. 2016377, which corresponds with U.S. Appl. No. 14/866,159, 4 pages.

Office Action, dated Oct. 6, 2017, received in U.S. Appl. No. 14/868,078, 40 pages.

Notice of Allowance, dated May 24, 2018, received in U.S. Appl. No. 14/868,078, 6 pages.

Innovation Patent, dated Aug. 4, 2016, received in Australian Patent Application No. 2016101201, which corresponds with U.S. Appl. No. 14/868,078, 1 page.

Office Action, dated Oct. 12, 2016, received in Australian Patent Application No. 2016101201, which corresponds with U.S. Appl. No. 14/868,078, 3 pages.

Notice of Allowance, dated Sep. 1, 2017, received in Australian Patent Application No. 2016229421, which corresponds with U.S. Appl. No. 14/868,078, 3 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Certificate of Grant, dated Jan. 3, 2018, received in Australian Patent Application No. 2016229421, which corresponds with U.S. Appl. No. 14/868,078, 1 page.

Office Action, dated Feb. 7, 2019, received in Australian Patent Application No. 2017258967, which corresponds with U.S. Appl. No. 14/868,078, 3 page.

Notice of Acceptance, dated Jun. 21, 2019, received in Australian Patent Application No. 2017258967, which corresponds with U.S. Appl. No. 14/868,078, 3 pages.

Certificate of Grant, dated Oct. 17, 2019, received in Australian Patent Application No. 2017258967, which corresponds with U.S. Appl. No. 14/868,078, 4 page.

Office Action, dated Aug. 20, 2018, received in Chinese Patent Application No. 01610130348.1, which corresponds with U.S. Appl. No. 14/868,078, 6 pages.

Office Action, dated Feb. 26, 2019, received in Chinese Patent Application No. 01610130348.1, which corresponds with U.S. Appl. No. 14/868,078, 4 pages.

Notice of Allowance, dated May 6, 2019, received in Chinese Patent Application No. 01610130348.1, which corresponds with U.S. Appl. No. 14/868,078, 3 pages.

Patent, dated Jul. 5, 2019, received in Chinese Patent Application No. 201610130348.1, which corresponds with U.S. Appl. No. 14/868,078, 6 pages.

Notice of Allowance, dated Oct. 1, 2016, received in Chinese Patent Application No. 201620175847.8, which corresponds with U.S. Appl. No. 14/868,078, 1 page.

Office Action, dated Nov. 21, 2019, received in Chinese Patent Application No. 201680011338.4, which corresponds with U.S. Appl. No. 14/868,078, 8 pages.

Office Action, dated May 19, 2020, received in Chinese Patent Application No. 201680011338.4, which corresponds with U.S. Appl. No. 14/868,078, 4 pages.

Office Action, dated Jun. 30, 2020, received in Chinese Patent Application No. 201680011338.4, which corresponds with U.S. Appl. No. 14/868,078, 4 pages.

Patent, dated Dec. 11, 2020, received in Chinese Patent Application No. 201680011338.4, which corresponds with U.S. Appl. No. 14/868,078, 3 pages.

Certificate of Registration, dated Jun. 30, 2016, received in German Patent Application No. 20201600156.9, which corresponds with U.S. Appl. No. 14/868,078, 3 pages.

Office Action, dated Mar. 30, 2016, received in Danish Patent Application No. 201500588, which corresponds with U.S. Appl. No. 14/868,078, 9 pages.

Office Action, dated Sep. 2, 2016, received in Danish Patent Application No. 201500588, which corresponds with U.S. Appl. No. 14/868,078, 4 pages.

Notice of Allowance, dated Jan. 30, 2017, received in received in Danish Patent Application No. 201500588, which corresponds with U.S. Appl. No. 14/868,078, 2 pages.

Notice of Allowance, dated May 2, 2017, received in received in Danish Patent Application No. 201500588, which corresponds with U.S. Appl. No. 14/868,078, 2 pages.

Patent, dated Sep. 11, 2017, received in Danish Patent Application No. 201500588, which corresponds with U.S. Appl. No. 14/868,078, 5 pages.

Office Action, dated Apr. 25, 2018, received in European Patent Application No. 16708916.8, which corresponds with U.S. Appl. No. 14/868,078, 6 pages.

Intention to Grant, dated May 10, 2019, received in European Patent Application No. 16708916.8, which corresponds with U.S. Appl. No. 14/868,078, 5 pages.

Decision to Grant, dated Sep. 12, 2019, received in European Patent Application No. 16708916.8, which corresponds with U.S. Appl. No. 14/868,078, 2 pages.

Patent, dated Oct. 9, 2019, received in European Patent Application No. 16708916.8, which corresponds with U.S. Appl. No. 14/868,078, 3 pages.

Office Action, dated Oct. 25, 2018, received in European Patent Application No. 17184437.6, which corresponds with U.S. Appl. No. 14/868,078, 6 pages.

Intention to Grant, dated May 22, 2019, received in European Patent Application No. 17184437.6, which corresponds with U.S. Appl. No. 14/868,078, 7 pages.

Decision to Grant, dated Sep. 19, 2019, received in European Patent Application No. 17184437.6, which corresponds with U.S. Appl. No. 14/868,078, 2 pages.

Patent, dated Oct. 16, 2019, received in European Patent Application No. 17184437.6, which corresponds with U.S. Appl. No. 14/868,078, 3 pages.

Patent, dated Jul. 12, 2017, received in Dutch Patent Application No. 2016376, which corresponds with U.S. Appl. No. 14/868,078, 2 pages.

Office Action, dated May 9, 2016, received in U.S. Appl. No. 14/863,432, 26 pages.

Notice of Allowance, dated Nov. 14, 2016, received in U.S. Appl. No. 14/863,432, 7 pages.

Notice of Allowance, dated Apr. 27, 2017, received in U.S. Appl. No. 14/863,432, 7 pages.

Notice of Allowance, dated Sep. 18, 2017, received in U.S. Appl. No. 14/863,432, 8 pages.

Office Action, dated Aug. 19, 2016, received in Australian Patent Application No. 2016100647, which corresponds with U.S. Appl. No. 14/863,432, 5 pages.

Office Action, dated Dec. 4, 2018, received in Chinese Patent Application No. 201610342313.4, which corresponds with U.S. Appl. No. 14/863,432, 5 pages.

Office Action, dated Jun. 17, 2019, received in Chinese Patent Application No. 201610342313.4, which corresponds with U.S. Appl. No. 14/863,432, 4 pages.

Office Action, dated Nov. 5, 2019, received in Chinese Patent Application No. 201610342313.4, which corresponds with U.S. Appl. No. 14/863,432, 4 pages.

Notice of Allowance, dated Mar. 20, 2020, received in Chinese Patent Application No. 201610342313.4, which corresponds with U.S. Appl. No. 14/863,432, 6 pages.

Patent, dated May 12, 2020, received in Chinese Patent Application No. 201610342313.4, which corresponds with U.S. Appl. No. 14/863,432, 7 pages.

Notice of Allowance, dated Jan. 12, 2017, received in Chinese Patent Application No. 201620470063.8, which corresponds with U.S. Appl. No. 14/863,432, 1 page.

Patent, dated Feb. 8, 2017, received in Chinese Patent Application No. 201620470063.8, which corresponds with U.S. Appl. No. 14/863,432, 5 pages.

Office Action, dated Apr. 4, 2016, received in Danish Patent Application No. 201500582, which corresponds with U.S. Appl. No. 14/863,432, 10 pages.

Office Action, dated Oct. 7, 2016, received in Danish Patent Application No. 201500582, which corresponds with U.S. Appl. No. 14/863,432, 6 pages.

Office Action, dated Jun. 12, 2017, received in Danish Patent Application No. 201500582, which corresponds with U.S. Appl. No. 14/863,432, 5 pages.

Office Action, dated Jan. 10, 2020, received in Japanese Patent Application No. 2018-243773, which corresponds with U.S. Appl. No. 14/863,432, 6 pages.

Office Action, dated Jul. 17, 2020, received in Japanese Patent Application No. 2018-243773, which corresponds with U.S. Appl. No. 14/863,432, 5 pages.

Notice of Allowance, dated Dec. 4, 2020, received in Japanese Patent Application No. 2018-243773, which corresponds with U.S. Appl. No. 14/863,432, 5 pages.

Patent, dated Jan. 5, 2021, received in Japanese Patent Application No. 2018-243773, which corresponds with U.S. Appl. No. 14/863,432, 4 pages.

Notice of Allowance, dated Jul. 13, 2020, received in Korean Patent Application No. 2020-7015964, which corresponds with U.S. Appl. No. 14/863,432, 6 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Patent, dated Oct. 12, 2020, received in Korean Patent Application No. 2020-7015964, which corresponds with U.S. Appl. No. 14/863,432, 8 pages.

Grant, dated Jul. 21, 2017, received in Dutch Patent Application No. 2016801, which corresponds with U.S. Appl. No. 14/871,227, 8 pages.

Office Action, dated Oct. 13, 2016, received in U.S. Appl. No. 14/866,511, 27 pages.

Final Office Action, dated Jan. 27, 2017, received in U.S. Appl. No. 14/866,511, 26 pages.

Notice of Allowance, dated Oct. 4, 2017, received in U.S. Appl. No. 14/866,511, 37 pages.

Office Action, dated Aug. 19, 2016, received in U.S. Appl. No. 14/291,880—to be referenced in 7294 per Robby), 19 pages.

Notice of Allowance, dated Jan. 10, 2017, received in U.S. Appl. No. 14/291,880—to be referenced in 7294 per Robby), 8 pages.

Patent, dated Aug. 8, 2016, received in Australian Patent Application No. 2016100653, corresponds with U.S. Appl. No. 14/866,511, 1 page.

Office Action, dated Dec. 5, 2018, received in Chinese Patent Application No. 201610342264.4, which corresponds with U.S. Appl. No. 14/866,511, 4 pages.

Office Action, dated Jul. 11, 2019, received in Chinese Patent Application No. 201610342264.4, which corresponds with U.S. Appl. No. 14/866,511, 4 pages.

Office Action, dated Sep. 17, 2019, received in Chinese Patent Application No. 201610342264.4, which corresponds with U.S. Appl. No. 14/866,511, 3 pages.

Notice of Allowance, dated Nov. 28, 2019, received in Chinese Patent Application No. 201610342264.4, which corresponds with U.S. Appl. No. 14/866,511, 3 pages.

Patent, dated Feb. 7, 2020, received in Chinese Patent Application No. 201610342264.4, which corresponds with U.S. Appl. No. 14/866,511, 7 pages.

Notice of Allowance, dated Jan. 12, 2017, received in Chinese Patent Application No. 201620470281.1, which corresponds with U.S. Appl. No. 14/866,511, 1 page.

Office Action, dated Mar. 22, 2016, received in Danish Patent Application No. 201500576, which corresponds with U.S. Appl. No. 14/866,511, 10 pages.

Intention to Grant, dated Jun. 8, 2016, received in Danish Patent Application No. 201500576, which corresponds with U.S. Appl. No. 14/866,511, 2 pages.

Grant, dated Aug. 26, 2016, received in Danish Patent Application No. 201500576, which corresponds with U.S. Appl. No. 14/866,511, 2 pages.

Patent, dated Jan. 23, 2017, received in Danish Patent Application No. 201500576, which corresponds with U.S. Appl. No. 14/866,511, 3 pages.

Office Action, dated Nov. 24, 2017, received in European Patent Application No. 16727900.9, which corresponds with U.S. Appl. No. 14/866,511, 5 pages.

Office Action, dated May 24, 2018, received in European Patent Application No. 16727900.9, which corresponds with U.S. Appl. No. 14/866,511, 7 pages.

Office Action, dated Jan. 2, 2019, received in European Patent Application No. 16727900.9, which corresponds with U.S. Appl. No. 14/866,511, 5 pages.

Intention to Grant, dated Jul. 5, 2019, received in European Patent Application No. 16727900.9, which corresponds with U.S. Appl. No. 14/866,511, 5 pages.

Decision to Grant, dated Dec. 5, 2019, received in European Patent Application No. 16727900.9, which corresponds with U.S. Appl. No. 14/866,511, 2 pages.

Patent, dated Jan. 1, 2020, received in European Patent Application No. 16727900.9, which corresponds with U.S. Appl. No. 14/866,511, 3 pages.

Office Action, dated Jun. 9, 2017, received in Japanese Patent Application No. 2016558214, which corresponds with U.S. Appl. No. 14/866,511, 6 pages.

Notice of Allowance, dated Jul. 14, 2017, received in Japanese Patent Application No. 2016558214, which corresponds with U.S. Appl. No. 14/866,511, 5 pages.

Patent, dated Aug. 18, 2017, received in Japanese Patent Application No. 2016558214, which corresponds with U.S. Appl. No. 14/866,511, 3 pages.

Office Action, dated Apr. 24, 2020, received in Korean Patent Application No. 2020-7003065, which corresponds with U.S. Appl. No. 14/866,511, 3 pages.

Notice of Allowance, dated Jul. 29, 2020, received in Korean Patent Application No. 2020-7003065, which corresponds with U.S. Appl. No. 14/866,511, 5 pages.

Patent, dated Oct. 29, 2020, received in Korean Patent Application No. 2020-7003065, which corresponds with U.S. Appl. No. 14/866,511, 5 pages.

Office Action, dated May 10, 2016, received in U.S. Appl. No. 14/866,489, 15 pages.

Final Office Action, dated Sep. 16, 2016, received in U.S. Appl. No. 14/866,489, 24 pages.

Notice of Allowance, dated Apr. 27, 2017, received in U.S. Appl. No. 14/866,489, 27 pages.

Notice of Allowance, dated Jul. 6, 2017, received in U.S. Appl. No. 14/866,489, 12 pages.

Office Action, dated Mar. 28, 2016, received in U.S. Appl. No. 14/869,899, 17 pages.

Office Action, dated Jun. 28, 2016, received in U.S. Appl. No. 14/869,899, 5 pages.

Final Office Action, dated Sep. 2, 2016, received in U.S. Appl. No. 14/869,899, 22 pages.

Notice of Allowance, dated Feb. 28, 2017, received in U.S. Appl. No. 14/869,899, 9 pages.

Innovation Patent, dated Aug. 25, 2016, received in Australian Patent Application No. 2016101438, which corresponds with U.S. Appl. No. 14/869,899, 1 page.

Certificate of Examination, dated Oct. 11, 2016, received in Australian Patent Application No. 2016101438, which corresponds with U.S. Appl. No. 14/869,899, 1 page.

Notice of Acceptance, dated Aug. 23, 2018, received in Australian Patent Application No. 2018204611, which corresponds with U.S. Appl. No. 14/869,899, 3 pages.

Office Action, dated Nov. 6, 2020, received in Chinese Patent Application No. 201610871595.7, which corresponds with U.S. Appl. No. 14/869,899, 15 pages.

Notice of Allowance, dated Mar. 30, 2021, received in Chinese Patent Application No. 201610871595.7, which corresponds with U.S. Appl. No. 14/869,899, 1 page.

Patent, dated Jun. 4, 2021, received in Chinese Patent Application No. 201610871595.7, which corresponds with U.S. Appl. No. 14/869,899, 7 pages.

Office Action, dated Feb. 3, 2016, received in Danish Patent Application No. 201500592, which corresponds with U.S. Appl. No. 14/869,899, 9 pages.

Office Action, dated Oct. 7, 2016, received in Danish Patent Application No. 201500592, which corresponds with U.S. Appl. No. 14/869,899, 6 pages.

Office Action, dated Jul. 3, 2017, received in Danish Patent Application No. 201500592, which corresponds with U.S. Appl. No. 14/869,899, 5 pages.

Office Action, dated Jan. 29, 2018, received in Danish Patent Application No. 201500592, which corresponds with U.S. Appl. No. 14/869,899, 2 pages.

Notice of Allowance, dated Apr. 24, 2018, received in Danish Patent Application No. 201500592, which corresponds with U.S. Appl. No. 14/869,899, 2 pages.

Patent, dated May 28, 2018, received in Danish Patent Application No. 201500592, which corresponds with U.S. Appl. No. 14/869,899, 2 pages.

Office Action, dated Nov. 22, 2016, received in Danish Patent Application No. 201670594, which corresponds with U.S. Appl. No. 14/869,899, 9 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Office Action, dated Dec. 14, 2017, received in Danish Patent Application No. 201670594, which corresponds with U.S. Appl. No. 14/869,899, 3 pages.

Office Action, dated May 1, 2018, received in Danish Patent Application No. 201670594, which corresponds with U.S. Appl. No. 14/869,899, 2 pages.

Office Action, dated Oct. 9, 2018, received in Danish Patent Application No. 201670594, which corresponds with U.S. Appl. No. 14/869,899, 2 pages.

Patent, dated Feb. 26, 2019, received in Danish Patent Application No. 201670594, which corresponds with U.S. Appl. No. 14/869,899, 3 pages.

Office Action, dated May 8, 2019, received in European Patent Application No. 18168939.9, which corresponds with U.S. Appl. No. 14/869,899, 10 pages.

Intention to Grant, dated Oct. 25, 2019, received in European Patent Application No. 18168939.9, which corresponds with U.S. Appl. No. 14/869,899, 8 pages.

Decision to Grant, dated Mar. 26, 2020, received in European Patent Application No. 14/869,899, which corresponds with U.S. Appl. No. 14/869,899, 3 pages.

Patent, dated Apr. 22, 2020, received in European Patent Application No. 14/869,899, which corresponds with U.S. Appl. No. 14/869,899, 3 pages.

Office Action, dated May 23, 2019, received in European Patent Application No. 18175195.9, which corresponds with U.S. Appl. No. 14/869,899, 10 pages.

Oral Summons, dated Dec. 6, 2019, received in European Patent Application No. 18175195.9, which corresponds with U.S. Appl. No. 14/869,899, 9 pages.

Office Action, dated Sep. 21, 2018, received in Japanese Patent Application No. 2018-100827, which corresponds with U.S. Appl. No. 14/869,899, 4 pages.

Notice of Allowance, dated Mar. 1, 2019, received in Japanese Patent Application No. 2018-100827, which corresponds with U.S. Appl. No. 14/869,899, 5 pages.

Patent, dated Apr. 5, 2019, received in Japanese Patent Application No. 2018-100827, which corresponds with U.S. Appl. No. 14/869,899, 5 pages.

Office Action, dated Oct. 5, 2018, received in Korean Patent Application No. 2018-7017213, which corresponds with U.S. Appl. No. 14/869,899, 3 pages.

Office Action, dated Mar. 22, 2019, received in Korean Patent Application No. 2018-7017213, which corresponds with U.S. Appl. No. 14/869,899, 6 pages.

Patent, dated May 10, 2019, received in Korean Patent Application No. 2018-7017213, which corresponds with U.S. Appl. No. 14/869,899, 8 pages.

Office Action, dated Mar. 4, 2016, received in U.S. Appl. No. 14/866,992, 30 pages.

Final Office Action, dated Jul. 29, 2016, received in U.S. Appl. No. 14/866,992, 35 pages.

Office Action, dated Apr. 13, 2017, received in U.S. Appl. No. 14/866,992, 34 pages.

Final Office Action, dated Oct. 3, 2017, received in U.S. Appl. No. 14/866,992, 37 pages.

Office Action, dated Jan. 29, 2018, received in U.S. Appl. No. 14/866,992, 44 pages.

Final Office Action, dated Aug. 28, 2018, received in U.S. Appl. No. 14/866,992, 52 pages.

Examiner's Answer, dated May 9, 2019, received in U.S. Appl. No. 14/866,992, 26 pages.

Innovation Patent, dated Sep. 22, 2016, received in Australian Patent Application No. 2016101418, which corresponds with U.S. Appl. No. 14/866,992, 1 page.

Office Action, dated Nov. 22, 2016, received in Australian Patent Application No. 2016101418, which corresponds with U.S. Appl. No. 14/866,992, 7 pages.

Office Action, dated Feb. 7, 2017, received in Australian Patent Application No. 2016101418, which corresponds with U.S. Appl. No. 14/866,992, 5 pages.

Office Action, dated Mar. 26, 2018, received in Australian Patent Application No. 2016304890, which corresponds with U.S. Appl. No. 14/866,992, 3 pages.

Notice of Acceptance, dated Mar. 12, 2019, received in Australian Patent Application No. 2016304890, which corresponds with U.S. Appl. No. 14/866,992, 5 pages.

Certificate of Grant, dated Jul. 4, 2019, received in Australian Patent Application No. 2016304890, which corresponds with U.S. Appl. No. 14/866,992, 1 page.

Office Action, dated Jan. 19, 2018, received in Australian Patent Application No. 201761478, which corresponds with U.S. Appl. No. 14/866,992, 6 pages.

Certificate of Grant, dated May 9, 2019, received in Australian Patent Application No. 201761478, which corresponds with U.S. Appl. No. 14/866,992, 3 pages.

Office Action, dated Sep. 12, 2019, received in Chinese Patent Application No. 201610658351.8, which corresponds with U.S. Appl. No. 14/866,992, 5 pages.

Office Action, dated Jan. 13, 2020, received in Chinese Patent Application No. 201610658351.8, which corresponds with U.S. Appl. No. 14/866,992, 3 pages.

Office Action, dated Jun. 30, 2020, received in Chinese Patent Application No. 201610658351.8, which corresponds with U.S. Appl. No. 14/866,992, 11 pages.

Office Action, dated Nov. 25, 2020, received in Chinese Patent Application No. 201610658351.8, which corresponds with U.S. Appl. No. 14/866,992, 9 pages.

Office Action, dated Jul. 24, 2020, received in Chinese Patent Application No. 201680041559.6, which corresponds with U.S. Appl. No. 14/866,992, 13 pages.

Notice of Allowance, dated Apr. 26, 2021, received in Chinese Patent Application No. 201680041559.6, which corresponds with U.S. Appl. No. 14/866,992, 1 page.

Patent, dated May 28, 2021, received in Chinese Patent Application No. 201680041559.6, which corresponds with U.S. Appl. No. 14/866,992, 7 pages.

Office Action, dated Mar. 18, 2016, received in Danish Patent Application 201500593, which corresponds with U.S. Appl. No. 14/866,992, 10 pages.

Office Action, dated Jun. 27, 2016, received in Danish Patent Application No. 201500593, which corresponds with U.S. Appl. No. 14/866,992, 7 pages.

Office Action, dated Feb. 6, 2017, received in Danish Patent Application No. 201500593, which corresponds with U.S. Appl. No. 14/866,992, 4 pages.

Office Action, dated Sep. 5, 2017, received in Danish Patent Application No. 201500593, which corresponds with U.S. Appl. No. 14/866,992, 6 pages.

Office Action, dated Oct. 12, 2018, received in European Patent Application No. 16758008.3, which corresponds with U.S. Appl. No. 14/866,992, 11 pages.

Summons, dated May 8, 2019, received in European Patent Application No. 16758008.3, which corresponds with U.S. Appl. No. 14/866,992, 14 pages.

Office Action, dated Jan. 11, 2019, received in Japanese Patent Application No. 2018-506425, which corresponds with U.S. Appl. No. 14/866,992, 6 pages.

Notice of Allowance, dated Jun. 18, 2019, received in Japanese Patent Application No. 2018-506425, which corresponds with U.S. Appl. No. 14/866,992, 5 pages.

Patent, dated Jul. 26, 2019, received in Japanese Patent Application No. 2018-506425, which corresponds with U.S. Appl. No. 14/866,992, 3 pages.

Notice of Allowance, dated Sep. 10, 2019, received in Korean Patent Application No. 2018-7003890, which corresponds with U.S. Appl. No. 14/866,992, 5 pages.

Patent, dated Oct. 11, 2019, received in Korean Patent Application No. 2018-7003890, which corresponds with U.S. Appl. No. 14/866,992, 5 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Office Action, dated Feb. 12, 2018, received in U.S. Appl. No. 15/009,661, 36 pages.

Final Office Action, dated Sep. 19, 2018, received in U.S. Appl. No. 15/009,661, 28 pages.

Office Action, dated Jun. 28, 2019, received in U.S. Appl. No. 15/009,661, 33 pages.

Final Office Action, dated Dec. 30, 2019, received in U.S. Appl. No. 15/009,661, 33 pages.

Office Action, dated Sep. 16, 2020, received in U.S. Appl. No. 15/009,661, 37 pages.

Final Office Action, dated Feb. 26, 2021, received in U.S. Appl. No. 15/009,661, 46 pages.

Office Action, dated Jul. 1, 2021 received in U.S. Appl. No. 15/009,661, 52 pages.

Office Action, dated Jan. 18, 2018, received in U.S. Appl. No. 15/009,676, 21 Pages.

Notice of Allowance, dated Aug. 3, 2018, received in U.S. Appl. No. 15/009,676, 6 pages.

Notice of Allowance, dated Nov. 15, 2018, received in U.S. Appl. No. 15/009,676, 6 pages.

Office Action, dated Jul. 15, 2020, received in Chinese Patent Application No. 201680047125.7, which corresponds with U.S. Appl. No. 15/009,676, 11 pages.

Office Action, dated Nov. 30, 2020, received in Chinese Patent Application No. 201680047125.7, which corresponds with U.S. Appl. No. 15/009,676, 11 pages.

Notice of Allowance, dated Feb. 24, 2021, received in Chinese Patent Application No. 201680047125.7, which corresponds with U.S. Appl. No. 15/009,676, 1 page.

Patent, dated Apr. 27, 2021, received in Chinese Patent Application No. 201680047125.7, which corresponds with U.S. Appl. No. 15/009,676, 8 pages.

Intention to Grant, dated Apr. 7, 2020, received in European Patent Application No. 16756866.6, which corresponds with U.S. Appl. No. 15/009,676, 8 pages.

Decision to Grant, dated Aug. 27, 2020, received in European Patent Application No. 16756866.6, which corresponds with U.S. Appl. No. 15/009,676, 4 pages.

Patent, dated Sep. 23, 2020, received in European Patent Application No. 16756866.6, which corresponds with U.S. Appl. No. 15/009,676, 4 pages.

Office Action, dated Mar. 13, 2018, received in U.S. Appl. No. 15/009,688, 10 pages.

Notice of Allowance, dated Nov. 6, 2018, received in U.S. Appl. No. 15/009,688, 10 pages.

Office Action, dated Jun. 29, 2020, received in Chinese Patent Application No. 201680047164.7, which corresponds with U.S. Appl. No. 15/009,688, 7 pages.

Notice of Allowance, dated Oct. 9, 2020, received in Chinese Patent Application No. 201680047164.7, which corresponds with U.S. Appl. No. 15/009,688, 5 pages.

Patent, dated Nov. 10, 2020, received in Chinese Patent Application No. 201680047164.7, which corresponds with U.S. Appl. No. 15/009,688, 6 pages.

Intention to Grant, dated Mar. 16, 2020, received in European Patent Application No. 16753796.8, which corresponds with U.S. Appl. No. 15/009,688, 6 pages.

Decision to Grant, dated Sep. 24, 2020, received in European Patent Application No. 16753796.8, which corresponds with U.S. Appl. No. 15/009,688, 4 pages.

Certificate of Grant, dated Oct. 21, 2020, received in European Patent Application No. 16753796.8, which corresponds with U.S. Appl. No. 15/009,688, 4 pages.

Office Action, dated Nov. 30, 2015, received in U.S. Appl. No. 14/845,217, 24 pages.

Final Office Action, dated Apr. 22, 2016, received in U.S. Appl. No. 14/845,217, 36 pages.

Notice of Allowance, dated Aug. 26, 2016, received in U.S. Appl. No. 14/845,217, 5 pages.

Notice of Allowance, dated Jan. 4, 2017, received in U.S. Appl. No. 14/845,217, 5 pages.

Office Action, dated Feb. 3, 2016, received in U.S. Appl. No. 14/856,517, 36 pages.

Final Office Action, dated Jul. 13, 2016, received in U.S. Appl. No. 14/856,517, 30 pages.

Office Action, dated May 2, 2017, received in U.S. Appl. No. 14/856,517, 34 pages.

Final Office Action, dated Oct. 4, 2017, received in U.S. Appl. No. 14/856,517, 33 pages.

Notice of Allowance, dated Jun. 29, 2018, received in U.S. Appl. No. 14/856,517, 11 pages.

Office Action, dated Feb. 11, 2016, received in U.S. Appl. No. 14/856,519, 34 pages.

Final Office Action, dated Jul. 15, 2016, received in U.S. Appl. No. 14/856,519, 31 pages.

Office Action, dated May 18, 2017, received in U.S. Appl. No. 14/856,519, 35 pages.

Final Office Action, dated Nov. 15, 2017, received in U.S. Appl. No. 14/856,519, 31 pages.

Notice of Allowance, dated Jan. 31, 2018, received in U.S. Appl. No. 14/856,519, 9 pages.

Notice of Allowance, dated May 2, 2018, received in U.S. Appl. No. 14/856,519, 10 pages.

Office Action, dated Jun. 9, 2017, received in U.S. Appl. No. 14/856,520, 36 pages.

Final Office Action, dated Nov. 16, 2017, received in U.S. Appl. No. 14/856,520, 41 pages.

Office Action, dated Nov. 20, 2018, received in U.S. Appl. No. 14/856,520, 36 pages.

Final Office Action, dated Apr. 17, 2019, received in U.S. Appl. No. 14/856,520, 38 pages.

Notice of Allowance, dated Jan. 6, 2020, received in U.S. Appl. No. 14/856,520, 5 pages.

Notice of Allowance, dated Mar. 4, 2020, received in U.S. Appl. No. 14/856,520, 6 pages.

Notice of Allowance, dated Oct. 1, 2020, received in U.S. Appl. No. 14/856,520, 5 pages.

Office Action, dated Jun. 30, 2017, received in U.S. Appl. No. 14/856,522, 22 pages.

Notice of Allowance, dated Feb. 9, 2018, received in U.S. Appl. No. 14/856,522, 9 pages.

Office Action, dated Feb. 1, 2016, received in U.S. Appl. No. 14/857,645, 15 pages.

Final Office Action, dated Jun. 16, 2016, received in U.S. Appl. No. 14/857,645, 12 pages.

Notice of Allowance, dated Oct. 24, 2016, received in U.S. Appl. No. 14/857,645, 6 pages.

Notice of Allowance, dated Jun. 16, 2017, received in U.S. Appl. No. 14/857,645, 5 pages.

Office Action, dated Nov. 30, 2017, received in U.S. Appl. No. 14/857,636, 19 pages.

Notice of Allowance, dated Aug. 16, 2018, received in U.S. Appl. No. 14/857,636, 5 pages.

Office Action, dated Jan. 17, 2018, received in Australian U.S. Appl. No. 14/857,636, which corresponds with U.S. Appl. No. 14/857,636, 3 pages.

Notice of Allowance, dated Jan. 15, 2019, received in Australian Patent Application No. 2017202816, which corresponds with U.S. Appl. No. 14/857,636, 3 pages.

Certificate of Grant, dated May 16, 2019, received in Australian Patent Application No. 2017202816, which corresponds with U.S. Appl. No. 14/857,636, 4 pages.

Office Action, dated Jul. 1, 2020, received in Chinese Patent Application No. 201711262953.5, which corresponds with U.S. Appl. No. 14/857,636, 13 pages.

Patent, dated Nov. 27, 2020, received in Chinese Patent Application No. 201711262953.5, which corresponds with U.S. Appl. No. 14/857,636, 6 pages.

Office Action, dated Sep. 22, 2017, received in Japanese Patent Application No. 2017-029201, which corresponds with U.S. Appl. No. 14/857,636, 8 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Office Action, dated Jun. 25, 2018, received in Japanese Patent Application No. 2017-029201, which corresponds with U.S. Appl. No. 14/857,636, 4 pages.

Office Action, dated Jan. 20, 2020, received in Japanese Patent Application No. 2017-029201, which corresponds with U.S. Appl. No. 14/857,636, 21 pages.

Notice of Allowance, dated Oct. 16, 2020, received in Japanese Patent Application No. 2017-029201, which corresponds with U.S. Appl. No. 14/857,636, 4 pages.

Patent, dated Nov. 12, 2020, received in Japanese Patent Application No. 2017-029201, which corresponds with U.S. Appl. No. 14/857,636, 3 pages.

Office Action, dated Nov. 28, 2018, received in Korean U.S. Appl. No. 14/857,636, which corresponds with U.S. Appl. No. 14/857,636, 6 pages.

Notice of Allowance, dated May 10, 2019, received in Korean U.S. Appl. No. 14/857,636, which corresponds with U.S. Appl. No. 14/857,636, 4 pages.

Patent, dated Jul. 11, 2019, received in Korean Patent Application No. 20177036645, which corresponds with U.S. Appl. No. 14/857,636, 8 pages.

Office Action, dated Dec. 1, 2017, received in U.S. Appl. No. 14/857,663, 15 pages.

Notice of Allowance, dated Aug. 16, 2018, received in U.S. Appl. No. 14/857,663, 5 pages.

Office Action, dated Jul. 14, 2020, received in Chinese Patent Application No. 201711261143.8, which corresponds with U.S. Appl. No. 14/857,663, 12 pages.

Notice of Allowance, dated Dec. 2, 2020, received in Chinese Patent Application No. 201711261143.8, which corresponds with U.S. Appl. No. 14/857,663, 3 pages.

Patent, dated Jan. 22, 2021, received in Chinese Patent Application No. 201711261143.8, which corresponds with U.S. Appl. No. 14/857,663, 6 pages.

Office Action, dated Nov. 11, 2019, received in Japanese Patent Application No. 2018-201076, which corresponds with U.S. Appl. No. 14/857,663, 7 pages.

Notice of Allowance, dated Sep. 18, 2020, received in Japanese Patent Application No. 2018-201076, which corresponds with U.S. Appl. No. 14/857,663, 5 pages.

Patent, dated Oct. 19, 2020, received in Japanese Patent Application No. 2018-201076, which corresponds with U.S. Appl. No. 14/857,663, 4 pages.

Office Action, dated Mar. 31, 2017, received in U.S. Appl. No. 14/857,700, 14 pages.

Final Office Action, dated Oct. 11, 2017, received in U.S. Appl. No. 14/857,700, 13 pages.

Notice of Allowance, dated Feb. 12, 2018, received in U.S. Appl. No. 14/857,700, 13 pages.

Notice of Allowance, dated Apr. 9, 2018, received in U.S. Appl. No. 14/857,700, 7 pages.

Notice of Allowance, dated Apr. 19, 2018, received in U.S. Appl. No. 14/864,529, 11 pages.

Notice of Allowance, dated Oct. 9, 2018, received in U.S. Appl. No. 14/864,529, 11 pages.

Office Action, dated Dec. 21, 2020, received in Korean Patent Application No. 2020-7029178, which corresponds with U.S. Appl. No. 14/870,882, 2 pages.

Notice of allowance, dated Jun. 28, 2021, received in Korean Patent Application No. 2020-7029178, which corresponds with U.S. Appl. No. 14/870,882, 2 pages.

Patent, dated Sep. 28, 2021, received in Korean Patent Application No. 2020-7029178, which corresponds with U.S. Appl. No. 14/870,882, 3 pages.

Grant of Patent, dated Apr. 16, 2018, received in Dutch Patent Application No. 2019215, 2 pages.

Office Action, dated Jan. 25, 2016, received in U.S. Pat. No. 14,864,580, 29 pages.

Notice of Allowance, dated May 23, 2016, received in U.S. Appl. No. 14/864,580, 9 pages.

Notice of Allowance, dated Aug. 4, 2016, received in U.S. Appl. No. 14/864,580, 9 pages.

Notice of Allowance, dated Dec. 28, 2016, received in U.S. Appl. No. 14/864,580, 8 pages.

Office Action, dated Aug. 19, 2016, received in Australian Patent Application No. 2016100648, which corresponds with U.S. Appl. No. 14/864,580, 6 pages.

Office Action, dated Jul. 1, 2019, received in Australian Patent Application No. 2019200872, which corresponds with U.S. Appl. No. 14/864,580, 6 pages.

Notice of Acceptance, dated Sep. 19, 2019, received in Australian Patent Application No. 2019200872, which corresponds with U.S. Appl. No. 14/864,580, 3 pages.

Certificate of Grant, dated Jan. 23, 2020, received in Australian Patent Application No. 2019200872, which corresponds with U.S. Appl. No. 14/864,580, 3 pages.

Office Action, dated Nov. 7, 2018, received in Chinese Patent Application No. 201610342151.4, which corresponds with U.S. Appl. No. 14/864,580, 3 pages.

Notice of Allowance, dated Jun. 14, 2019, received in Chinese Patent Application No. 201610342151.4, which corresponds with U.S. Appl. No. 14/864,580, 3 pages.

Patent, dated Jul. 30, 2019, received in Chinese Patent Application No. 201610342151.4, which corresponds with U.S. Appl. No. 14/864,580, 6 pages.

Notice of Allowance, dated Nov. 8, 2016, received in Chinese Patent Application No. 201620470247.4, which corresponds with U.S. Appl. No. 14/864,580, 3 pages.

Certificate of Registration, dated Oct. 14, 2016, received in German Patent Application No. 20201600003234.9, which corresponds with U.S. Appl. No. 14/864,580, 3 pages.

Office Action, dated Apr. 8, 2016, received in Danish Patent Application No. 201500584, which corresponds with U.S. Appl. No. 14/864,580, 9 pages.

Office Action, dated Oct. 7, 2016, received in Danish Patent Application No. 201500584, which corresponds with U.S. Appl. No. 14/864,580, 3 pages.

Office Action, dated May 5, 2017, received in Danish Patent Application No. 201500584, which corresponds with U.S. Appl. No. 14/864,580, 3 pages.

Office Action, dated Dec. 15, 2017, received in Danish Patent Application No. 201500584, which corresponds with U.S. Appl. No. 14/864,580, 4 pages.

Office Action, dated Jun. 17, 2021, received in European Patent Application No. 19194418.0, which corresponds with U.S. Appl. No. 14/864,580, 7 pages.

Notice of Allowance, dated Aug. 14, 2019, received in Korean Patent Application No. 2019-7018317, which corresponds with U.S. Appl. No. 14/864,580, 6 pages.

Patent, dated Nov. 12, 2019, received in Korean Patent Application No. 2019-7018317, which corresponds with U.S. Appl. No. 14/864,580, 6 pages.

Notice of Allowance, dated Nov. 23, 2016, received in U.S. Appl. No. 14/864,601, 12 pages.

Notice of Allowance, dated Apr. 20, 2017, received in U.S. Appl. No. 14/864,601, 13 pages.

Office Action, dated Aug. 31, 2018, received in Australian Patent Application No. 14/864,601, which corresponds with U.S. Appl. No. 14/864,601, 3 pages.

Certificate of Grant, dated Feb. 21, 2019, received in Australian Patent Application No. 2016276030, which corresponds with U.S. Appl. No. 14/864,601, 4 pages.

Office Action, dated Feb. 4, 2019, received in European Patent Application No. 16730554.9, which corresponds with U.S. Appl. No. 14/864,601, 10 pages.

Intention to Grant, dated Jul. 18, 2019, received in European Patent Application No. 16730554.9, which corresponds with U.S. Appl. No. 14/864,601, 5 pages.

Decision to Grant, dated Sep. 12, 2019, received in European Patent Application No. 16730544.9, which corresponds with U.S. Appl. No. 14/864,601, 2 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Patent, dated Oct. 9, 2019, received in European Patent Application No. 16730554.9, which corresponds with U.S. Appl. No. 14/864,601, 3 pages.

Notice of Allowance, dated Dec. 10, 2018, received in Japanese Patent Application No. 2017-561375, which corresponds with U.S. Appl. No. 14/864,601, 5 pages.

Patent, dated Jan. 11, 2019, received in Japanese Patent Application No. 2017-561375, which corresponds with U.S. Appl. No. 14/864,601, 3 pages.

Office Action, dated Jan. 25, 2019, received in Korean Patent Application No. 2017-7033756, which corresponds with U.S. Appl. No. 14/864,601, 8 pages.

Notice of Allowance, dated May 29, 2019, received in Korean Patent Application No. 2017-7033756, which corresponds with U.S. Appl. No. 14/864,601, 6 pages.

Patent, dated Jun. 25, 2019, received in Korean Patent Application No. 2017-7033756, which corresponds with U.S. Appl. No. 14/864,601, 6 pages.

Office Action, dated Apr. 19, 2016, received in U.S. Appl. No. 14/864,627, 9 pages.

Notice of Allowance, dated Jan. 31, 2017, received in U.S. Appl. No. 14/864,627, 7 pages.

Office Action, dated Apr. 8, 2016, received in Danish Patent Application No. 201500585, which corresponds with U.S. Appl. No. 14/864,627, 9 pages.

Office Action, dated Oct. 7, 2016, received in Danish Patent Application No. 201500585, which corresponds with U.S. Appl. No. 14/864,627, 3 pages.

Office Action, dated May 5, 2017, received in Danish Patent Application No. 201500585, which corresponds with U.S. Appl. No. 14/864,627, 4 pages.

Office Action, dated Dec. 15, 2017, received in Danish Patent Application No. 201500585, which corresponds with U.S. Appl. No. 14/864,627, 5 pages.

Office Action, dated Mar. 29, 2016, received in U.S. Appl. No. 14/866,361, 22 pages.

Notice of Allowance, dated Jul. 19, 2016, received in U.S. Appl. No. 14/866,361, 8 pages.

Office Action, dated Jun. 10, 2016, received in Australian Patent Application No. 2016100292, which corresponds with U.S. Appl. No. 14/866,361, 4 pages.

Certificate of Examination, dated Dec. 8, 2016, received in Australian Patent Application No. 2016100292, which corresponds with U.S. Appl. No. 14/866,361, 1 page.

Office Action, dated Oct. 19, 2018, received in Chinese Patent Application No. 201610189298.4, which corresponds with U.S. Appl. No. 14/866,361, 6 pages.

Notice of Allowance, dated May 23, 2019, received in Chinese Patent Application No. 201610189298.4, which corresponds with U.S. Appl. No. 14/866,361, 3 pages.

Patent, dated Jul. 23, 2019, received in Chinese Patent Application No. 201610189298.4, which corresponds with U.S. Appl. No. 14/866,361, 7 pages.

Notice of Allowance/Grant, dated Jul. 1, 2016, received in Chinese Patent Application No. 201620251706.X, which corresponds with U.S. Appl. No. 14/866,361, 3 pages.

Letters Patent, dated Aug. 3, 2016, received in Chinese Patent Application No. 201620251706.X, which corresponds with U.S. Appl. No. 14/866,361, 3 pages.

Certificate of Registration, dated Jun. 24, 2016, received in German Patent Application No. 202016001819.2, which corresponds with U.S. Appl. No. 14/866,361, 3 pages.

Office Action, dated Apr. 7, 2016, received in Danish Patent Application No. 201500579, which corresponds with U.S. Appl. No. 14/866,361, 10 pages.

Office Action, dated Oct. 28, 2016, received in Danish Patent Application No. 201500579, which corresponds with U.S. Appl. No. 14/866,361, 3 pages.

Office Action, dated Jun. 15, 2017, received in Danish Patent Application No. 201500579, which corresponds with U.S. Appl. No. 14/866,361, 2 pages.

Office Action, dated Jan. 4, 2018, received in Danish Patent Application No. 201500579, which corresponds with U.S. Appl. No. 14/866,361, 2 pages.

Notice of Allowance, dated Mar. 16, 2018, received in Danish Patent Application No. 201500579, which corresponds with U.S. Appl. No. 14/866,361, 2 pages.

Patent, dated May 22, 2018, received in Danish Patent Application No. 201500579, which corresponds with U.S. Appl. No. 14/866,361, 2 pages.

Office Action, dated Jun. 11, 2018, received in European Patent Application No. 17188507.2, which corresponds with U.S. Appl. No. 14/866,361, 10 pages.

Office Action, dated Jan. 30, 2019, received in European Patent Application No. 17188507.2, which corresponds with U.S. Appl. No. 14/866,361, 13 pages.

Office Action, dated Oct. 8, 2019, received in European Patent Application No. 17188507.2, which corresponds with U.S. Appl. No. 14/866,361, 6 pages.

Intention to Grant, dated Apr. 14, 2020, received in European Patent Application No. 17188507.2, which corresponds with U.S. Appl. No. 14/866,361, 7 pages.

Intention to Grant, dated Feb. 3, 2021, received in European Patent Application No. 17188507.2, which corresponds with U.S. Appl. No. 14/866,361, 7 pages.

Patent, dated May 26, 2021, received in European Patent Application No. 17188507.2, which corresponds with U.S. Appl. No. 14/866,361, 3 pages.

Office Action, dated Oct. 12, 2018, received in Japanese Patent Application No. 2017-141962, which corresponds with U.S. Appl. No. 14/866,361, 6 pages.

Office Action, dated Jun. 10, 2019, received in Japanese Patent Application No. 2017-141962, which corresponds with U.S. Appl. No. 14/866,361, 6 pages.

Notice of Allowance, dated Oct. 7, 2019, received in Japanese Patent Application No. 2017-141962, which corresponds with U.S. Appl. No. 14/866,361, 5 pages.

Patent, dated Nov. 8, 2019, received in Japanese Patent Application No. 2017-141962, which corresponds with U.S. Appl. No. 14/866,361, 4 pages.

Office Action, dated Sep. 14, 2018, received in Korean Patent Application No. 2018-7013039, which corresponds with U.S. Appl. No. 14/866,361, 2 pages.

Notice of Allowance, dated Jan. 30, 2019, received in Korean Patent Application No. 2018-7013039, which corresponds with U.S. Appl. No. 14/866,361, 5 pages.

Patent, dated Apr. 3, 2019, received in Korean Patent Application No. 2018-7013039, which corresponds with U.S. Appl. No. 14/866,361, 4 pages.

Office Action, dated Jan. 22, 2018, received in U.S. Appl. No. 14/866,987, 22 pages.

Final Office Action, dated Oct. 11, 2018, received in U.S. Appl. No. 14/866,987, 20 pages.

Notice of Allowance, dated Apr. 4, 2019, received in U.S. Appl. No. 14/866,987, 5 pages.

Patent, dated Aug. 8, 2016, received in Australian Patent Application No. 2016100649, which corresponds with U.S. Appl. No. 14/866,987, 1 page.

Office Action, dated Dec. 4, 2018, received in Chinese Patent Application No. 201610342336.5, which corresponds with U.S. Appl. No. 14/866,987, 5 pages.

Rejection Decision, dated Apr. 28, 2019, received in Chinese Patent Application No. 201610342336.5, which corresponds with U.S. Appl. No. 14/866,987, 4 pages.

Office Action, dated Aug. 15, 2019, received in Chinese Patent Application No. 201610342336.5, which corresponds with U.S. Appl. No. 14/866,987, 3 pages.

Notice of Allowance, dated Dec. 3, 2019, received in Chinese Patent Application No. 201610342336.5, which corresponds with U.S. Appl. No. 14/866,987, 3 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Patent, dated Jan. 31, 2020, received in Chinese Patent Application No. 201610342336.5, which corresponds with U.S. Appl. No. 14/866,987, 7 pages.

Office Action, dated Oct. 19, 2016, received in Chinese Patent Application No. 2016201470246.X, which corresponds with U.S. Appl. No. 14/866,987, 4 pages.

Patent, dated May 3, 2017, received in Chinese Patent Application No. 2016201470246.X, which corresponds with U.S. Appl. No. 14/866,987, 2 pages.

Patent, dated Sep. 19, 2016, received in German Patent Application No. 202016002908.9, which corresponds with U.S. Appl. No. 14/866,987, 3 pages.

Office Action, dated Mar. 22, 2016, received in Danish Patent Application No. 201500587, which corresponds with U.S. Appl. No. 14/866,987, 8 pages.

Intention to Grant, dated Jun. 10, 2016, received in Danish Patent Application No. 201500587, which corresponds with U.S. Appl. No. 14/866,987, 2 pages.

Notice of Allowance, dated Nov. 1, 2016, received in Danish Patent Application No. 201500587, which corresponds with U.S. Appl. No. 14/866,987, 2 pages.

Office Action, dated Sep. 9, 2016, received in Danish Patent Application No. 201670463, which corresponds with U.S. Appl. No. 14/866,987, 7 pages.

Notice of Allowance, dated Jan. 31, 2017, received in Danish Patent Application No. 201670463, which corresponds with U.S. Appl. No. 14/866,987, 3 pages.

Office Action, dated Apr. 19, 2017, received in Danish Patent Application No. 201670463, which corresponds with U.S. Appl. No. 14/866,987, 3 pages.

Notice of Allowance, dated Sep. 29, 2017, received in Danish Patent Application No. 201670463, which corresponds with U.S. Appl. No. 14/866,987, 2 pages.

Patent, dated Nov. 6, 2017, received in Danish Patent Application No. 201670463, which corresponds with U.S. Appl. No. 14/866,987, 6 pages.

Office Action, dated May 7, 2018, received in European Patent Application No. 16189421.7, which corresponds with U.S. Appl. No. 14/866,987, 5 pages.

Office Action, dated Dec. 11, 2018, received in European Patent Application No. 16189421.7, which corresponds with U.S. Appl. No. 14/866,987, 6 pages.

Intention to Grant, dated Jun. 14, 2019, received in European Patent Application No. 16189421.7, which corresponds with U.S. Appl. No. 14/866,987, 7 pages.

Intention to Grant, dated Oct. 25, 2019, received in European Patent Application No. 16189421.7, which corresponds with U.S. Appl. No. 14/866,987, 7 pages.

Decision to Grant, dated Nov. 14, 2019, received in European Patent Application No. 16189421.7, which corresponds with U.S. Appl. No. 14/866,987, 2 pages.

Patent, dated Dec. 11, 2019, received in European Patent Application No. 16189421.7, which corresponds with U.S. Appl. No. 14/866,987, 3 pages.

Office Action, dated Feb. 3, 2020, received in European Patent Application No. 17163309.2, which corresponds with U.S. Appl. No. 14/866,987, 6 pages.

Office Action, dated Dec. 22, 2021, received in European Patent Application No. 17163309.2, which corresponds with U.S. Appl. No. 14/866,987, 4 pages.

Patent, dated Feb. 5, 2021, received in Hong Kong Patent Application No. 1235878, which corresponds with U.S. Appl. No. 14/866,987, 6 pages.

Patent, dated Jan. 8, 2021, received in Hong Kong Patent Application No. 18100151.5, which corresponds with U.S. Appl. No. 14/866,987, 6 pages.

Office Action, dated Aug. 26, 2020, received in Indian Application No. 201617032291, which corresponds with U.S. Appl. No. 14/866,987, 9 pages.

Notice of Allowance, dated Sep. 22, 2017, received in Japanese Patent Application No. 2016-233449, which corresponds with U.S. Appl. No. 14/866,987, 5 pages.

Patent, dated Oct. 27, 2017, received in Japanese Patent Application No. 2016-233449, which corresponds with U.S. Appl. No. 14/866,987, 3 pages.

Office Action, dated Jul. 31, 2017, received in Japanese Patent Application No. 2017126445, which corresponds with U.S. Appl. No. 14/866,987, 6 pages.

Notice of Allowance, dated Mar. 6, 2018, received in Japanese Patent Application No. 2017-126445, which corresponds with U.S. Appl. No. 14/866,987, 5 pages.

Patent, dated Apr. 6, 2018, received in Japanese Patent Application No. 2017-126445, which corresponds with U.S. Appl. No. 14/866,987, 3 pages.

Office Action, dated Nov. 29, 2017, received in U.S. Appl. No. 14/866,989, 31 pages.

Final Office Action, dated Jul. 3, 2018, received in U.S. Appl. No. 14/866,989, 17 pages.

Notice of Allowance, dated Jan. 17, 2019, received in U.S. Appl. No. 14/866,989, 8 pages.

Certificate of Exam, dated Jul. 21, 2016, received in Australian Patent Application No. 2016100652, which corresponds with U.S. Appl. No. 14/866,989, 1 page.

Office Action, dated Feb. 26, 2018, received in Australian Patent Application No. 2017201079, which corresponds with U.S. Appl. No. 14/866,989, 6 pages.

Notice of Acceptance, dated Feb. 14, 2019, received in Australian Patent Application No. 2017201079, which corresponds with U.S. Appl. No. 14/866,989, 3 pages.

Certificate of Grant, dated Jun. 13, 2019, received in Australian Patent Application No. 2017201079, which corresponds with U.S. Appl. No. 14/866,989, 1 page.

Office Action, dated Sep. 19, 2018, received in Chinese Patent Application No. 201610342314.9, which corresponds with U.S. Appl. No. 14/866,989, 6 pages.

Office Action, dated Feb. 25, 2019, received in Chinese Patent Application No. 201610342314.9, which corresponds with U.S. Appl. No. 14/866,989, 3 pages.

Rejection Decision, dated Apr. 24, 2019, received in Chinese Patent Application No. 201610342314.9, which corresponds with U.S. Appl. No. 14/866,989, 3 pages.

Office Action, dated Jun. 16, 2017, received in Japanese Patent Application No. 2016-233450, which corresponds with U.S. Appl. No. 14/866,989, 6 pages.

Patent, dated Mar. 9, 2018, received in Japanese Patent Application No. 2016-233450, which corresponds with U.S. Appl. No. 14/866,989, 4 pages.

Office Action, dated Apr. 1, 2016, received in Danish Patent Application No. 201500589, which corresponds with U.S. Appl. No. 14/866,989, 8 pages.

Intention to Grant, dated Jun. 10, 2016, received in Danish Patent Application No. 201500589, which corresponds with U.S. Appl. No. 14/866,989, 2 pages.

Notice of Allowance, dated Nov. 1, 2016, received in Danish Patent Application No. 201500589, which corresponds with U.S. Appl. No. 14/866,989, 2 pages.

Office Action, dated Feb. 3, 2020, received in European Patent Application No. 16189425.8, which corresponds with U.S. Appl. No. 14/866,989, 6 pages.

Intention to Grant, dated Dec. 3, 2020, received in European Patent Application No. 16189425.8, which corresponds with U.S. Appl. No. 14/866,989, 7 pages.

Decision to Grant, dated Feb. 25, 2021, received in European Patent Application No. 16189425.8, which corresponds with U.S. Appl. No. 14/866,989, 1 page.

Notice of Allowance, dated Feb. 5, 2018, received in Japanese Patent Application No. 2016-233450, which corresponds with U.S. Appl. No. 14/866,989, 5 pages.

Office Action, dated Apr. 11, 2016, received in U.S. Appl. No. 14/871,236, 23 pages.

Office Action, dated Jun. 28, 2016, received in U.S. Appl. No. 14/871,236, 21 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Final Office Action, dated Nov. 4, 2016, received in U.S. Appl. No. 14/871,236, 24 pages.

Notice of Allowance, dated Feb. 28, 2017, received in U.S. Appl. No. 14/871,236, 9 pages.

Innovation Patent, dated Aug. 25, 2016, received in Australian Patent Application No. 2016101433, which corresponds with U.S. Appl. No. 14/871,236, 1 page.

Office Action, dated Oct. 14, 2016, received in Australian Patent Application No. 2016101433, which corresponds with U.S. Appl. No. 14/871,236, 3 pages.

Office Action, dated Jun. 23, 2020, received in Brazilian Patent Application No. 11201701119-9, which corresponds with U.S. Appl. No. 14/871,236, 9 pages.

Office Action, dated Sep. 30, 2019, received in Chinese Patent Application No. 201610871466.8, which corresponds with U.S. Appl. No. 14/871,236, 4 pages.

Notice of Allowance, dated Mar. 24, 2020, received in Chinese Patent Application No. 201610871466.8, which corresponds with U.S. Appl. No. 14/871,236, 3 pages.

Patent, dated May 19, 2020, received in Chinese Patent Application No. 201610871466.8, which corresponds with U.S. Appl. No. 14/871,236, 8 pages.

Office Action, dated Apr. 8, 2016, received in Danish Patent Application No. 201500595, which corresponds with U.S. Appl. No. 14/871,236, 12 pages.

Office Action, dated May 26, 2016, received in Danish Patent Application No. 201500595, which corresponds with U.S. Appl. No. 14/871,236, 14 pages.

Office Action, dated Sep. 30, 2016, received in Danish Patent Application No. 201500595, which corresponds with U.S. Appl. No. 14/871,236, 10 pages.

Office Action, dated Jun. 15, 2017, received in Danish Patent Application No. 201500595, which corresponds with U.S. Appl. No. 14/871,236, 4 pages.

Office Action, dated Jan. 29, 2018, received in Danish Patent Application No. 201500595, which corresponds with U.S. Appl. No. 14/871,236, 2 pages.

Notice of Allowance, dated Apr. 26, 2018, received in Danish Patent Application No. 201500595, which corresponds with U.S. Appl. No. 14/871,236, 2 pages.

Patent, dated Jun. 18, 2018, received in Danish Patent Application No. 201500595, which corresponds with U.S. Appl. No. 14/871,236, 3 pages.

Intention to Grant, dated Dec. 4, 2019, received in European Patent Application No. 18168941.5, which corresponds with U.S. Appl. No. 14/871,236, 8 pages.

Intention to Grant, dated Oct. 5, 2020, received in European Patent Application No. 18168941.5, which corresponds with U.S. Appl. No. 14/871,236, 8 pages.

Decision to Grant, dated Mar. 25, 2021, received in European Patent Application No. 18168941.5, which corresponds with U.S. Appl. No. 14/871,236, 2 pages.

Patent, dated Apr. 21, 2021, received in European Patent Application No. 18168941.5, which corresponds with U.S. Appl. No. 14/871,236, 3 pages.

Office Action, dated Mar. 17, 2020, received in Mx/a/2017/011610, which corresponds with U.S. Appl. No. 14/871,236, 4 pages.

Notice of Allowance, dated Sep. 7, 2020, received in Mx/a/2017/011610, which corresponds with U.S. Appl. No. 14/871,236, 12 pages.

Patent, dated Dec. 2, 2020, received in Mx/a/2017/011610, which corresponds with U.S. Appl. No. 14/871,236, 4 pages.

Office Action, dated Jul. 19, 2018, received in Russian Patent Application No. 2017131408, which corresponds with U.S. Appl. No. 14/871,236, 8 pages.

Patent, dated Feb. 15, 2019, received in Russian Patent Application No. 2017131408, which corresponds with U.S. Appl. No. 14/871,236, 2 pages.

Office Action, dated Sep. 1, 2017, received in U.S. Appl. No. 14/870,754, 22 pages.

Final Office Action, dated Mar. 9, 2018, received in U.S. Appl. No. 14/870,754, 19 pages.

Notice of Allowance, dated Jul. 2, 2018, received in U.S. Appl. No. 14/870,754, 9 pages.

Notice of Allowance, dated Dec. 3, 2018, received in U.S. Appl. No. 14/870,754, 8 pages.

Office Action, dated Nov. 14, 2017, received in U.S. Appl. No. 14/870,882, 25 pages.

Final Office Action, dated Apr. 20, 2018, received in U.S. Appl. No. 14/870,882, 7 pages.

Notice of Allowance, dated Jul. 12, 2018, received in U.S. Appl. No. 14/870,882, 5 pages.

Notice of Allowance, dated Dec. 5, 2018, received in U.S. Appl. No. 14/870,882, 8 pages.

Innovation Patent, dated Aug. 25, 2016, received in Australian Patent Application No. 2016101436, which corresponds with U.S. Appl. No. 14/871,236, 1 pages.

Office Action, dated Oct. 31, 2016, received in Australian Patent Application No. 2016101438, which corresponds with U.S. Appl. No. 14/871,236, 6 pages.

Office Action, dated Nov. 28, 2019, received in Chinese Patent Application No. 201610870912.3, which corresponds with U.S. Appl. No. 14/870,882, 10 pages.

Office Action, dated Aug. 3, 2020, received in Chinese Patent Application No. 201610870912.3, which corresponds with U.S. Appl. No. 14/870,882, 4 pages.

Office Action, dated Dec. 21, 2020, received in Chinese Patent Application No. 201610870912.3, which corresponds with U.S. Appl. No. 14/870,882, 5 pages.

Notice of Allowance, dated Mar. 22, 2021, received in Chinese Patent Application No. 201610870912.3, which corresponds with U.S. Appl. No. 14/870,882, 1 pages.

Patent, dated May 25, 2021, received in Chinese Patent Application No. 201610870912.3, which corresponds with U.S. Appl. No. 14/870,882, 8 pages.

Office Action, dated Apr. 6, 2016, received in Danish Patent Application No. 201500596, which corresponds with U.S. Appl. No. 14/870,882, 7 pages.

Office Action, dated Jun. 9, 2016, received in Danish Patent Application No. 201500596, which corresponds with U.S. Appl. No. 14/870,882, 9 pages.

Notice of Allowance, dated Oct. 31, 2017, received in Danish Patent Application No. 201500596, which corresponds with U.S. Appl. No. 14/870,882, 2 pages.

Patent, dated Jan. 29, 2018, received in Danish Patent Application No. 201500596, which corresponds with U.S. Appl. No. 14/870,882, 4 pages.

Office Action, dated Feb. 11, 2019, received in European Patent Application No. 17171972.7, which corresponds with U.S. Appl. No. 14/870,882, 7 pages.

Office Action, dated Sep. 1, 2017, received in U.S. Appl. No. 14/870,988, 14 pages.

Final Office Action, dated Feb. 16, 2018, received in U.S. Appl. No. 14/870,988, 18 pages.

Notice of Allowance, dated Aug. 27, 2018, received in U.S. Appl. No. 14/870,988, 11 pages.

Office Action, dated Nov. 22, 2017, received in U.S. Appl. No. 14/871,227, 24 pages.

Notice of Allowance, dated Jun. 11, 2018, received in U.S. Appl. No. 14/871,227, 11 pages.

Office Action, dated Oct. 17, 2016, received in Australian Patent Application No. 2016203040, which corresponds with U.S. Appl. No. 14/871,227, 7 pages.

Office Action, dated Oct. 16, 2017, received in Australian Patent Application No. 2016203040, which corresponds with U.S. Appl. No. 14/871,227, 5 pages.

Notice of Acceptance, dated Oct. 30, 2018, received in Australian Patent Application No. 2016203040, which corresponds with U.S. Appl. No. 14/871,227, 4 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Certificate of Grant, dated Feb. 28, 2019, received in Australian Patent Application No. 2016203040, which corresponds with U.S. Appl. No. 14/871,227, 1 page.

Office Action, dated Oct. 18, 2016, received in Australian Patent Application No. 2016101431, which corresponds with U.S. Appl. No. 14/871,227, 3 pages.

Office Action, dated Apr. 13, 2017, received in Australian Patent Application No. 2016101431, which corresponds with U.S. Appl. No. 14/871,227, 4 pages.

Office Action, dated Oct. 11, 2018, received in Australian Patent Application No. 2017245442, which corresponds with U.S. Appl. No. 14/871,227, 4 pages.

Office Action, dated Nov. 16, 2018, received in Chinese Patent Application No. 201680000466.9, which corresponds with U.S. Appl. No. 14/871,227, 5 pages.

Notice of Allowance, dated Jun. 5, 2019, received in Chinese Patent Application No. 201680000466.9, which corresponds with U.S. Appl. No. 14/871,227, 5 pages.

Patent, dated Aug. 9, 2019, received in Chinese Patent Application No. 201680000466.9, which corresponds with U.S. Appl. No. 14/871,227, 8 pages.

Intention to Grant, dated Apr. 7, 2016, received in Danish Patent Application No. 201500597, which corresponds with U.S. Appl. No. 14/871,227, 7 pages.

Grant, dated Jun. 21, 2016, received in Danish Patent Application No. 201500597, which corresponds with U.S. Appl. No. 14/871,227, 2 pages.

Patent, dated Sep. 26, 2016, received in Danish Patent Application No. 201500597, which corresponds with U.S. Appl. No. 14/871,227, 7 pages.

Intent to Grant, dated Sep. 17, 2018, received in European Patent No. 16711743.1, which corresponds with U.S. Appl. No. 14/871,227, 5 pages.

Patent, dated Nov. 28, 2018, received in European Patent No. 16711743.1, which corresponds with U.S. Appl. No. 14/871,227, 1 page.

Office Action, dated Jul. 20, 2020, received in Indian Patent Application No. 201617032293, which corresponds with U.S. Appl. No. 14/871,227, 9 pages.

Office Action, dated Mar. 24, 2017, received in Japanese Patent Application No. 2016-533201, which corresponds with U.S. Appl. No. 14/871,227, 6 pages.

Office Action, dated Aug. 4, 2017, received in Japanese Patent Application No. 2016-533201, which corresponds with U.S. Appl. No. 14/871,227, 6 pages.

Notice of Allowance, dated Jan. 4, 2018, received in Japanese Patent Application No. 2016-533201, which corresponds with U.S. Appl. No. 14/871,227, 4 pages.

Patent, dated Feb. 9, 2018, received in Japanese Patent Application No. 2016-533201, which corresponds with U.S. Appl. No. 14/871,227, 4 pages.

Office Action, dated Feb. 20, 2018, received in Korean Patent Application No. 2016-7019816, which corresponds with U.S. Appl. No. 14/871,227, 8 pages.

Notice of Allowance, dated Oct. 1, 2018, received in Korean Patent Application No. 2016-7019816, which corresponds with U.S. Appl. No. 14/871,227, 6 pages.

Patent, dated Dec. 28, 2018, received in Korean Patent Application No. 2016-7019816, which corresponds with U.S. Appl. No. 14/871,227, 8 pages.

Office Action, dated Oct. 26, 2017, received in U.S. Appl. No. 14/871,336, 22 pages.

Final Office Action, dated Mar. 15, 2018, received in U.S. Appl. No. 14/871,336, 23 pages.

Office Action, dated Nov. 5, 2018, received in U.S. Appl. No. 14/871,336, 24 pages.

Notice of Allowance, dated Feb. 5, 2019, received in U.S. Appl. No. 14/871,336, 10 pages.

Office Action, dated Oct. 14, 2016, received in Australian Patent Application No. 2016101437, which corresponds with U.S. Appl. No. 14/871,336, 2 pages.

Office Action, dated Apr. 11, 2017, received in Australian Patent Application No. 2016101437, which corresponds with U.S. Appl. No. 14/871,336, 4 pages.

Office Action, dated Nov. 4, 2019, received in Chinese Patent Application No. 201610871323.7, which corresponds with U.S. Appl. No. 14/871,336, 12 pages.

Office Action, dated Aug. 4, 2020, received in Chinese Patent Application No. 201610871323.7, which corresponds with U.S. Appl. No. 14/871,336, 18 pages.

Office Action, dated Feb. 9, 2021, received in Chinese Patent Application No. 201610871323.7, which corresponds with U.S. Appl. No. 14/871,336, 1 page.

Office Action, dated Jun. 1, 2021, received in Chinese Patent Application No. 201610871323.7, which corresponds with U.S. Appl. No. 14/871,336, 1 page.

Office Action, dated Apr. 18, 2016, received in Danish Patent Application No. 201500601, which corresponds with U.S. Appl. No. 14/871,336, 8 pages.

Office Action, dated Oct. 18, 2016, received in Danish Patent Application No. 201500601, which corresponds with U.S. Appl. No. 14/871,336, 3 pages.

Notice of Allowance, dated Mar. 23, 2017, received in Danish Patent Application No. 201500601, which corresponds with U.S. Appl. No. 14/871,336, 2 pages.

Patent, dated Oct. 30, 2017, Danish Patent Application No. 201500601, which corresponds with U.S. Appl. No. 14/871,336, 5 pages.

Office Action, dated Feb. 12, 2019, received in European Patent Application No. 17172266.3, which corresponds with U.S. Appl. No. 14/871,336, 6 pages.

Office Action, dated Apr. 2, 2018, received in Japanese Patent Application No. 2018-020324, which corresponds with U.S. Appl. No. 14/871,336, 4 pages.

Notice of Allowance, dated Oct. 12, 2018, received in Japanese Patent Application No. 2018-020324, which corresponds with U.S. Appl. No. 14/871,336, 5 pages.

Patent, dated Nov. 16, 2018, received in Japanese Patent Application No. 2018-020324, which corresponds with U.S. Appl. No. 14/871,336, 4 pages.

Office Action, dated Oct. 16, 2017, received in U.S. Appl. No. 14/871,462, 26 pages.

Innovation Patent, dated Aug. 25, 2016, received in Australian Patent Application No. 2016101435, which corresponds with U.S. Appl. No. 14/871,462, 1 page.

Office Action, dated Oct. 4, 2016, received in Australian Patent Application No. 2016101435, which corresponds with U.S. Appl. No. 14/871,462, 3 pages.

Office Action, dated Sep. 29, 2017, received in Australian Patent Application No. 2016231505, which corresponds with U.S. Appl. No. 14/871,462, 5 pages.

Innovation Patent, dated Oct. 11, 2017, received in Australian Patent Application No. 2016231505, which corresponds with U.S. Appl. No. 14/871,462, 1 page.

Office Action, dated Oct. 9, 2021, received in Chinese Patent Application No. 201610869950.7, which corresponds with U.S. Appl. No. 14/871,462, 5 pages.

Office Action, dated Apr. 20, 2017, received in Chinese Patent Application No. 201621044346.2, which corresponds with U.S. Appl. No. 14/871,462, 3 pages.

Intention to Grant, dated Apr. 18, 2016, received in Danish Patent Application No. 201500600, which corresponds with U.S. Appl. No. 14/871,462, 7 pages.

Grant, dated Aug. 30, 2016, received in Danish Patent Application No. 201500600, which corresponds with U.S. Appl. No. 14/871,462, 2 pages.

Office Action, dated Mar. 13, 2017, received in Japanese Patent Application No. 2016-183289, which corresponds with U.S. Appl. No. 14/871,462, 5 pages.

Office Action, dated Nov. 13, 2017, received in Japanese Patent Application No. 2016-183289, which corresponds with U.S. Appl. No. 14/871,462, 5 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Office Action, dated Apr. 29, 2016, received in U.S. Appl. No. 14/867,823, 28 pages.  
Final Office Action, dated Sep. 28, 2016, received in U.S. Appl. No. 14/867,823, 31 pages.  
Office Action, dated May 11, 2017, received in U.S. Appl. No. 14/867,823, 42 pages.  
Final Office Action, dated Nov. 29, 2017, received in U.S. Appl. No. 14/867,823, 47 pages.  
Notice of Allowance, dated Apr. 18, 2018, received in U.S. Appl. No. 14/867,823, 10 pages.  
Notice of Allowance, dated Aug. 7, 2018, received in U.S. Appl. No. 14/867,823, 8 pages.  
Office Action, dated Mar. 18, 2016, received in Danish Patent Application No. 201500594, which corresponds with U.S. Appl. No. 14/867,823, 10 pages.  
Office Action, dated Sep. 7, 2016, received in Danish Patent Application No. 201500594, which corresponds with U.S. Appl. No. 14/867,823, 4 pages.  
Office Action, dated May 15, 2017, received in Danish Patent Application No. 201500594, which corresponds with U.S. Appl. No. 14/867,823, 4 pages.  
Office Action, dated Jan. 23, 2018, received in Danish Patent Application No. 201500594, which corresponds with U.S. Appl. No. 14/867,823, 8 pages.  
Office Action, dated May 10, 2016, received in U.S. Appl. No. 14/867,892, 28 pages.  
Final Office Action, dated Nov. 2, 2016, received in U.S. Appl. No. 14/867,892, 48 pages.  
Office Action, dated Jul. 6, 2017, received in U.S. Appl. No. 14/867,892, 55 pages.  
Final Office Action, dated Dec. 14, 2017, received in U.S. Appl. No. 14/867,892, 53 pages.  
Office Action, dated Apr. 24, 2018, received in U.S. Appl. No. 14/867,892, 63 pages.  
Final Office Action, dated Oct. 17, 2018, received in U.S. Appl. No. 14/867,892, 48 pages.  
Examiner's Answer, dated Jul. 18, 2019, received in U.S. Appl. No. 14/867,892, 17 pages.  
Notice of Allowance, dated May 26, 2021, received in U.S. Appl. No. 14/867,892, 7 pages.  
Notice of Allowance, dated Jul. 13, 2021, received in U.S. Appl. No. 14/867,892, 8 pages.  
Office Action, dated Mar. 21, 2016, received in Danish Patent Application No. 201500598, which corresponds with U.S. Appl. No. 14/867,892, 9 pages.  
Office Action, dated Sep. 14, 2016, received in Danish Patent Application No. 201500598, which corresponds with U.S. Appl. No. 14/867,892, 4 pages.  
Office Action, dated May 4, 2017, received in Danish Patent Application No. 201500598, which corresponds with U.S. Appl. No. 14/867,892, 4 pages.  
Office Action, dated Oct. 31, 2017, received in Danish Patent Application No. 201500598, which corresponds with U.S. Appl. No. 14/867,892, 2 pages.  
Notice of Allowance, dated Jan. 26, 2018, received in Danish Patent Application No. 201500598, which corresponds with U.S. Appl. No. 14/867,892, 2 pages.  
Office Action, dated Feb. 28, 2018, received in U.S. Appl. No. 14/869,361, 26 pages.  
Final Office Action, dated Oct. 4, 2018, received in U.S. Appl. No. 14/869,361, 28 pages.  
Office Action, dated Feb. 27, 2019, received in U.S. Appl. No. 14/869,361, 28 pages.  
Office Action, dated Mar. 1, 2017, received in U.S. Appl. No. 14/869,855, 14 pages.  
Final Office Action, dated Oct. 10, 2017, received in U.S. Appl. No. 14/869,855, 16 pages.  
Office Action, dated Jan. 23, 2018, received in U.S. Appl. No. 14/869,855, 24 pages.

Notice of Allowance, dated May 31, 2018, received in U.S. Appl. No. 14/869,855, 10 pages.  
Office Action, dated Feb. 9, 2017, received in U.S. Appl. No. 14/869,873, 17 pages.  
Final Office Action, dated Aug. 18, 2017, received in U.S. Appl. No. 14/869,873, 20 pages.  
Office Action, dated Jan. 18, 2018, received in U.S. Appl. No. 14/869,873, 25 pages.  
Final Office Action, dated May 23, 2018, received in U.S. Appl. No. 14/869,873, 18 pages.  
Notice of Allowance, dated Jul. 30, 2018, received in U.S. Appl. No. 14/869,873, 8 pages.  
Office Action, dated Jan. 11, 2018, received in U.S. Appl. No. 14/869,997, 17 pages.  
Office Action, dated Sep. 7, 2018, received in U.S. Appl. No. 14/869,997, 23 pages.  
Notice of Allowance, dated Apr. 4, 2019, received in U.S. Appl. No. 14/869,997, 9 pages.  
Notice of Allowance, dated Jan. 17, 2018, received in U.S. Appl. No. 14/867,990, 12 pages.  
Notice of Allowance, dated Mar. 30, 2018, received in U.S. Appl. No. 14/867,990, 5 pages.  
Office Action, dated May 23, 2016, received in Australian Patent Application No. 2016100253, which corresponds with U.S. Appl. No. 14/867,990, 5 pages.  
Notice of Allowance, dated May 21, 2019, received in Chinese Patent Application No. 201610131507.X, which corresponds with U.S. Appl. No. 14/867,990, 3 pages.  
Patent, dated Jul. 19, 2019, received in Chinese Patent Application No. 201610131507.X, which corresponds with U.S. Appl. No. 14/867,990, 6 pages.  
Office Action, dated Jul. 5, 2016, received in Chinese Patent Application No. 201620176221.9, which corresponds with U.S. Appl. No. 14/867,990, 4 pages.  
Office Action, dated Oct. 25, 2016, received in Chinese Patent Application No. 201620176221.9, which corresponds with U.S. Appl. No. 14/867,990, 7 pages.  
Certificate of Registration, dated Jun. 16, 2016, received in German Patent No. 202016001489.8, which corresponds with U.S. Appl. No. 14/867,990, 3 pages.  
Office Action, dated Mar. 18, 2016, received in Danish Patent Application No. 201500581, which corresponds with U.S. Appl. No. 14/867,990, 9 pages.  
Office Action, dated Sep. 26, 2016, received in Danish Patent Application No. 201500581, which corresponds with U.S. Appl. No. 14/867,990, 5 pages.  
Office Action, dated May 3, 2017, received in Danish Patent Application No. 201500581, which corresponds with U.S. Appl. No. 14/867,990, 5 pages.  
Office Action, dated Feb. 19, 2018, received in Danish Patent Application No. 201500581, which corresponds with U.S. Appl. No. 14/867,990, 4 pages.  
Office Action, dated Feb. 21, 2020, received in European Patent Application No. 16711725.8, which corresponds with U.S. Appl. No. 14/867,990, 13 pages.  
Office Action, dated May 14, 2021, received in European Patent Application No. 16711725.8, which corresponds with U.S. Appl. No. 14/867,990, 7 pages.  
Office Action, dated Apr. 19, 2018, received in U.S. Appl. No. 14/869,703, 19 pages.  
Final Office Action, dated Oct. 26, 2018, received in U.S. Appl. No. 14/869,703, 19 pages.  
Notice of Allowance, dated Mar. 12, 2019, received in U.S. Appl. No. 14/869,703, 6 pages.  
Office Action, dated Dec. 12, 2017, received in U.S. Appl. No. 15/009,668, 32 pages.  
Final Office Action, dated Jul. 3, 2018, received in U.S. Appl. No. 15/009,668, 19 pages.  
Office Action, dated Jan. 10, 2019, received in U.S. Appl. No. 15/009,668, 17 pages.  
Notice of Allowance, dated May 1, 2019, received in U.S. Appl. No. 15/009,668, 12 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Office Action, dated Aug. 20, 2020, received in Chinese Patent Application No. 201680046985.9, which corresponds with U.S. Appl. No. 15/009,668, 15 pages.

Notice of Allowance, dated Apr. 20, 2021, received in Chinese Patent Application No. 201680046985.9, which corresponds with U.S. Appl. No. 15/009,668, 1 page.

Office Action, dated Jan. 31, 2020, received in European Patent Application No. 16753795.0, which corresponds with U.S. Appl. No. 15/009,668, 9 pages.

Office Action, dated Mar. 19, 2021, received in European Patent Application No. 16753795.0, which corresponds with U.S. Appl. No. 15/009,668, 5 pages.

Office Action, dated Nov. 25, 2016, received in U.S. Appl. No. 15/081,771, 17 pages.

Final Office Action, dated Jun. 2, 2017, received in U.S. Appl. No. 15/081,771, 17 pages.

Notice of Allowance, dated Dec. 4, 2017, received in U.S. Appl. No. 15/081,771, 10 pages.

Office Action, dated Feb. 1, 2018, received in Australian U.S. Appl. No. 15/081,771, which corresponds with U.S. Appl. No. 15/081,771, 4 pages.

Notice of Acceptance, dated Jan. 24, 2019, received in Australian Patent Application No. 2017202058, which corresponds with U.S. Appl. No. 15/081,771, 3 pages.

Certificate of Grant, dated May 23, 2019, received in Australian Patent Application No. 2017202058, which corresponds with U.S. Appl. No. 15/081,771, 1 page.

Office Action, dated Mar. 2, 2022, received in Chinese Patent Application No. 201811561188.1, which corresponds with U.S. Appl. No. 15/081,771, 1 page.

Office Action, dated Jan. 24, 2020, received in European Patent Application No. 18205283.7, which corresponds with U.S. Appl. No. 15/081,771, 4 pages.

Intention to Grant, dated Apr. 30, 2020, received in European Patent Application No. 18205283.7, which corresponds with U.S. Appl. No. 15/081,771, 7 pages.

Decision to Grant, dated Aug. 27, 2020, received in European Patent Application No. 18205283.7, which corresponds with U.S. Appl. No. 15/081,771, 4 pages.

Patent, dated Sep. 23, 2020, received in European Patent Application No. 18205283.7, which corresponds with U.S. Appl. No. 15/081,771, 4 pages.

Office Action, dated Jan. 26, 2018, received in Japanese Patent Application No. 2017-086460, which corresponds with U.S. Appl. No. 15/081,771, 6 pages.

Notice of Allowance, dated Oct. 12, 2018, received in Japanese Patent Application No. 2017-086460, which corresponds with U.S. Appl. No. 15/081,771, 5 pages.

Office Action, dated Aug. 29, 2017, received in Korean Patent Application No. 2017-7014536, which corresponds with U.S. Appl. No. 15/081,771, 5 pages.

Notice of Allowance, dated Jun. 28, 2018, received in Korean Patent Application No. 2017-7014536, which corresponds with U.S. Appl. No. 15/081,771, 4 pages.

Patent, dated Sep. 28, 2018, received in Korean Patent Application No. 2017-7014536, which corresponds with U.S. Appl. No. 15/081,771, 3 pages.

Final Office Action, dated May 1, 2017, received in U.S. Appl. No. 15/136,782, 18 pages.

Notice of Allowance, dated Oct. 20, 2017, received in U.S. Appl. No. 15/136,782, 9 pages.

Office Action, dated May 4, 2018, received in Australian Patent Application No. 2018202855, which corresponds with U.S. Appl. No. 15/136,782, 3 pages.

Notice of Acceptance, dated Sep. 10, 2018, received in Australian Patent Application No. 2018202855, which corresponds with U.S. Appl. No. 15/136,782, 3 pages.

Certificate of Grant, dated Jan. 17, 2019, received in Australian Patent Application No. 2018202855, which corresponds with U.S. Appl. No. 15/136,782, 4 pages.

Office Action, dated Sep. 27, 2019, received in Chinese Patent Application No. 201810119007.3, which corresponds with U.S. Appl. No. 15/136,782, 6 pages.

Notice of Allowance, dated Feb. 26, 2020, received in Chinese Patent Application No. 201810119007.3, which corresponds with U.S. Appl. No. 15/136,782, 3 pages.

Patent, dated Apr. 7, 2020, received in Chinese Patent Application No. 201810119007.3, which corresponds with U.S. Appl. No. 15/136,782, 7 pages.

Office Action, dated May 23, 2017, received in Danish Patent Application No. 201770190, which corresponds with U.S. Appl. No. 15/136,782, 7 pages.

Office Action, dated Jan. 8, 2018, received in Danish Patent Application No. 2011770190, which corresponds with U.S. Appl. No. 15/136,782, 2 pages.

Notice of Allowance, dated Mar. 19, 2018, received in Danish Patent Application No. 201770190, which corresponds with U.S. Appl. No. 15/136,782, 2 pages.

Patent, dated May 22, 2018, received in Danish Patent Application No. 201770190, which corresponds with U.S. Appl. No. 15/136,782, 2 pages.

Office Action, dated Apr. 17, 2019, received in European Patent Application No. 18171453.6, which corresponds with U.S. Appl. No. 15/136,782, 4 pages.

Office Action, dated Oct. 2, 2019, received in European Patent Application No. 18171453.6, which corresponds with U.S. Appl. No. 15/136,782, 5 pages.

Office Action, dated May 12, 2020, received in European Patent Application No. 18171453.6, which corresponds with U.S. Appl. No. 15/136,782, 5 pages.

Patent, dated Feb. 5, 2021, received in Hong Kong Patent Application No. 1257553, which corresponds with U.S. Appl. No. 15/136,782, 14 pages.

Office Action, dated Jun. 1, 2018, received in Japanese Patent Application No. 2018-062161, which corresponds with U.S. Appl. No. 15/136,782, 5 pages.

Office Action, dated Nov. 12, 2018, received in Japanese Patent Application No. 2018-062161, which corresponds with U.S. Appl. No. 15/136,782, 5 pages.

Notice of Allowance, dated Feb. 18, 2019, received in Japanese Patent Application No. 2018-062161, which corresponds with U.S. Appl. No. 15/136,782, 5 pages.

Patent, dated Mar. 22, 2019, received in Japanese Patent Application No. 2018-062161, which corresponds with U.S. Appl. No. 15/136,782, 5 pages.

Office Action, dated Oct. 31, 2018, received in Korean Patent Application No. 2018-7020659, which corresponds with U.S. Appl. No. 15/136,782, 5 pages.

Notice of Allowance, dated Feb. 25, 2019, received in Korean Patent Application No. 2018-7020659, which corresponds with U.S. Appl. No. 15/136,782, 5 pages.

Patent, dated Apr. 3, 2019, received in Korean Patent Application No. 2018-7020659, which corresponds with U.S. Appl. No. 15/136,782, 5 pages.

Office Action, dated Jan. 20, 2017, received in U.S. Appl. No. 15/231,745, 21 pages.

Notice of Allowance, dated Jul. 6, 2017, received in U.S. Appl. No. 15/231,745, 18 pages.

Office Action, dated Oct. 17, 2016, received in Danish Patent Application No. 201670587, which corresponds with U.S. Appl. No. 15/231,745, 9 pages.

Office Action, dated Jun. 29, 2017, received in Danish Patent Application No. 201670587, which corresponds with U.S. Appl. No. 15/231,745, 4 pages.

Office Action, dated Feb. 22, 2018, received in Danish Patent Application No. 201670587, which corresponds with U.S. Appl. No. 15/231,745, 4 pages.

Office Action, dated Dec. 18, 2018, received in Danish Patent Application No. 201670587, which corresponds with U.S. Appl. No. 15/231,745, 4 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Office Action, dated Dec. 14, 2016, received in Danish Patent Application No. 201670590, which corresponds with U.S. Appl. No. 15/231,745, 9 pages.

Office Action, dated Jul. 6, 2017, received in Danish Patent Application No. 201670590, which corresponds with U.S. Appl. No. 15/231,745, 3 pages.

Office Action, dated Jan. 10, 2018, received in Danish Patent Application No. 201670590, which corresponds with U.S. Appl. No. 15/231,745, 2 pages.

Patent, dated May 28, 2018, received in Danish Patent Application No. 201670590, which corresponds with U.S. Appl. No. 15/231,745, 2 pages.

Office Action, dated Nov. 10, 2016, received in Danish Patent Application No. 201670591, which corresponds with U.S. Appl. No. 15/231,745, 12 pages.

Office Action, dated Apr. 11, 2018, received in Danish Patent Application No. 201670591, which corresponds with U.S. Appl. No. 15/231,745, 3 pages.

Office Action, dated Nov. 23, 2018, received in Danish Patent Application No. 201670591, which corresponds with U.S. Appl. No. 15/231,745, 7 pages.

Office Action, dated Oct. 26, 2016, received in Danish Patent Application No. 201670592, which corresponds with U.S. Appl. No. 15/231,745, 8 pages.

Office Action, dated Jan. 5, 2017, received in Danish Patent Application No. 201670592, which corresponds with U.S. Appl. No. 15/231,745, 3 pages.

Office Action, dated Jan. 30, 2018, received in Danish Patent Application No. 201670592, which corresponds with U.S. Appl. No. 15/231,745, 2 pages.

Notice of Allowance, dated Mar. 27, 2018, received in Danish Patent Application No. 201670592, which corresponds with U.S. Appl. No. 15/231,745, 2 pages.

Patent, dated May 28, 2018, received in Danish Patent Application No. 201670592, which corresponds with U.S. Appl. No. 15/231,745, 2 pages.

Office Action, dated Oct. 12, 2016, received in Danish Patent Application No. 201670593, which corresponds with U.S. Appl. No. 15/231,745, 7 pages.

Patent, dated Oct. 30, 2017, received in Danish Patent Application No. 201670593, which corresponds with U.S. Appl. No. 15/231,745, 3 pages.

Notice of Allowance, dated Nov. 1, 2019, received in Japanese Patent Application No. 2018-158502, which corresponds with U.S. Appl. No. 15/231,745, 5 pages.

Patent, dated Nov. 29, 2019, received in Japanese Patent Application No. 2018-158502, which corresponds with U.S. Appl. No. 15/231,745, 3 pages.

Notice of Allowance, dated Oct. 4, 2018, received in U.S. Appl. No. 15/272,327, 46 pages.

Notice of Acceptance, dated Mar. 2, 2018, received in Australian Patent Application No. 2018200705, which corresponds with U.S. Appl. No. 15/272,327, 3 pages.

Certificate of Grant, dated Jun. 28, 2018, received in Australian Patent Application No. 2018200705, which corresponds with U.S. Appl. No. 15/272,327, 4 pages.

Office Action, dated Mar. 22, 2019, received in Australian Patent Application No. 2018204234, which corresponds with U.S. Appl. No. 15/272,327, 7 pages.

Notice of Acceptance, dated Dec. 10, 2019, received in Australian Patent Application No. 2018204234, which corresponds with U.S. Appl. No. 15/272,327, 3 pages.

Certificate of Grant, dated Apr. 2, 2020, received in Australian Patent Application No. 2018204234, which corresponds with U.S. Appl. No. 15/272,327, 1 page.

Office Action, dated Aug. 31, 2020, received in Chinese Patent Application No. 201810151593.X, which corresponds with U.S. Appl. No. 15/272,327, 10 pages.

Notice of Allowance, dated Jan. 27, 2021, received in Chinese Patent Application No. 201810151593.X, which corresponds with U.S. Appl. No. 15/272,327, 3 pages.

Patent, dated Mar. 19, 2021, received in Chinese Patent Application No. 201810151593.X, which corresponds with U.S. Appl. No. 15/272,327, 6 pages.

Office Action, dated Sep. 14, 2018, received in European Patent Application No. 15155939.4, which corresponds with U.S. Appl. No. 15/272,327, 5 pages.

Intention to Grant, dated Mar. 19, 2019, received in European Patent Application No. 15155939.4, which corresponds with U.S. Appl. No. 15/272,327, 6 pages.

Decision to Grant, dated Apr. 26, 2019, received in European Patent Application No. 15155939.4, which corresponds with U.S. Appl. No. 15/272,327, 2 pages.

Patent, dated May 22, 2019, received in European Patent Application No. 15155939.4, which corresponds with U.S. Appl. No. 15/272,327, 1 page.

Notice of Allowance, dated Jul. 30, 2018, received in Japanese Patent Application No. 2018-506989, which corresponds with U.S. Appl. No. 15/272,327, 4 pages.

Patent, dated Aug. 31, 2018, received in Japanese Patent Application No. 2018-506989, which corresponds with U.S. Appl. No. 15/272,327, 3 pages.

Office Action, dated Oct. 26, 2018, received in U.S. Appl. No. 15/272,341, 22 pages.

Final Office Action, dated Mar. 25, 2019, received in U.S. Appl. No. 15/272,341, 25 pages.

Notice of Allowance, dated Feb. 20, 2020, received in U.S. Appl. No. 15/272,341, 12 pages.

Office Action, dated Jul. 27, 2017, received in Australian Patent Application No. 217100535, which corresponds with U.S. Appl. No. 15/272,341, 4 pages.

Notice of Allowance, dated Sep. 20, 2018, received in U.S. Appl. No. 15/272,343, 44 pages.

Office Action, dated Jun. 5, 2019, received in Chinese Patent Application No. 201810071627.4, which corresponds with U.S. Appl. No. 15/272,343, 6 pages.

Notice of Allowance, dated Dec. 11, 2019, received in Chinese Patent Application No. 201710071627.4, which corresponds with U.S. Appl. No. 15/272,343, 4 pages.

Patent, dated Mar. 3, 2020, received in Chinese Patent Application No. 201710071627.4, which corresponds with U.S. Appl. No. 15/272,343, 7 pages.

Office Action, dated Jan. 8, 2019, received in European Patent Application No. 17206374.5, which corresponds with U.S. Appl. No. 15/272,343, 5 pages.

Intention to Grant, dated May 13, 2019, received in European Patent Application No. 17206374.5, which corresponds with U.S. Appl. No. 15/272,343, 7 pages.

Decision to Grant, dated Sep. 12, 2019, received in European Patent Application No. 17206374.5, which corresponds with U.S. Appl. No. 15/272,343, 3 pages.

Patent, Oct. 9, 2019, received in European Patent Application No. 17206374.5, which corresponds with U.S. Appl. No. 15/272,343, 3 pages.

Office Action, dated Oct. 15, 2018, received in U.S. Appl. No. 15/272,345, 31 pages.

Final Office Action, dated Apr. 2, 2019, received in U.S. Appl. No. 15/272,345, 28 pages.

Notice of Allowance, dated Apr. 22, 2020, received in U.S. Appl. No. 15/272,345, 12 pages.

Notice of Acceptance, dated Mar. 2, 2018, received in Australian Patent Application No. 2016304832, which corresponds with U.S. Appl. No. 15/272,345, 3 pages.

Certificate of Grant, dated Jun. 28, 2018, received in Australian Patent Application No. 2016304832, which corresponds with U.S. Appl. No. 15/272,345, 4 pages.

Office Action, dated Oct. 22, 2019, received in Chinese Patent Application No. 201680022696.5, which corresponds with U.S. Appl. No. 15/272,345, 7 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Notice of Allowance, dated Jul. 6, 2020, received in Chinese Patent Application No. 201680022696.5, which corresponds with U.S. Appl. No. 15/272,345, 5 pages.

Patent, dated Sep. 18, 2020, received in Chinese Patent Application No. 201680022696.5, which corresponds with U.S. Appl. No. 15/272,345, 6 pages.

Office Action, dated Apr. 20, 2018, received in European Patent Application No. 16756862.5, which corresponds with U.S. Appl. No. 15/272,345, 15 pages.

Office Action, dated Nov. 13, 2018, received in European Patent Application No. 16756862.5, which corresponds with U.S. Appl. No. 15/272,345, 5 pages.

Decision to Grant, dated Jan. 31, 2019, received in European Patent Application No. 16756862.5, which corresponds with U.S. Appl. No. 15/272,345, 5 pages.

Patent, dated Feb. 27, 2019, received in European Patent Application No. 16756862.5, which corresponds with U.S. Appl. No. 15/272,345, 3 pages.

Patent, dated Feb. 7, 2020, received in Hong Kong Patent Application No. 18101477.0, which corresponds with U.S. Appl. No. 15/272,345, 6 pages.

Office Action, dated Dec. 4, 2020, received in Japanese Patent Application No. 2019-212493, which corresponds with U.S. Appl. No. 15/272,345, 5 pages.

Notice of Allowance, dated Aug. 27, 2021, received in Japanese Patent Application No. 2019-212493, which corresponds with U.S. Appl. No. 15/272,345, 2 pages.

Patent, dated Sep. 29, 2021, received in Japanese Patent Application No. 2019-212493, which corresponds with U.S. Appl. No. 15/272,345, 4 pages.

Office Action, dated Mar. 7, 2018, received in U.S. Appl. No. 15/482,618, 7 pages.

Notice of Allowance, dated Aug. 15, 2018, received in U.S. Appl. No. 15/482,618, 7 pages.

Office Action, dated Apr. 23, 2018, received in U.S. Appl. No. 15/499,691, 29 pages.

Notice of Allowance, dated Oct. 12, 2018, received in U.S. Appl. No. 15/499,693, 8 pages.

Office Action, dated May 11, 2020, received in Australian Patent Application No. 2019203776, which corresponds with U.S. Appl. No. 15/499,693, 4 pages.

Notice of Acceptance, dated Jul. 22, 2020, received in Australian Patent Application No. 2019203776, which corresponds with U.S. Appl. No. 15/499,693, 3 pages.

Certificate of Grant, dated Nov. 26, 2020, received in Australian Patent Application No. 2019203776, which corresponds with U.S. Appl. No. 15/499,693, 3 pages.

Office action, dated Nov. 20, 2020, received in Japanese Patent Application No. 2019-200174, which corresponds with U.S. Appl. No. 15/499,693, 6 pages.

Notice of Allowance, dated Jul. 16, 2021, received in Japanese Patent Application No. 2019-200174, which corresponds with U.S. Appl. No. 15/499,693, 2 pages.

Patent, dated Aug. 18, 2021, received in Japanese Patent Application No. 2019-200174, which corresponds with U.S. Appl. No. 15/499,693, 3 pages.

Office Action, dated Aug. 2, 2019, received in Korean Patent Application No. 2019-7009439, which corresponds with U.S. Appl. No. 15/499,693, 3 pages.

Notice of Allowance, dated Dec. 27, 2019, received in Korean Patent Application No. 2019-7009439, which corresponds with U.S. Appl. No. 15/499,693, 5 pages.

Patent, dated Mar. 27, 2020, received in Korean Patent Application No. 2019-7009439, which corresponds with U.S. Appl. No. 15/499,693, 4 pages.

Office Action, dated Aug. 30, 2017, received in U.S. Appl. No. 15/655,749, 22 pages.

Final Office Action, dated May 10, 2018, received in U.S. Appl. No. 15/655,749, 19 pages.

Office Action, dated Jan. 24, 2019, received in U.S. Appl. No. 15/655,749, 25 pages.

Final Office Action, dated Jul. 1, 2019, received in U.S. Appl. No. 15/655,749, 24 pages.

Notice of Allowance, dated Feb. 20, 2020, received in U.S. Appl. No. 15/655,749, 10 pages.

Office Action, dated Feb. 3, 2020, received in Chinese Patent Application No. 201710331254.5, which corresponds with U.S. Appl. No. 15/655,749, 8 pages.

Office Action, dated Mar. 22, 2021, received in Chinese Patent Application No. 201710331254.5, which corresponds with U.S. Appl. No. 15/655,749, 4 pages.

Notice of Allowance, dated May 27, 2021, received in Chinese Patent Application No. 201710331254.5, which corresponds with U.S. Appl. No. 15/655,749, 1 page.

Patent, dated Jun. 25, 2021, received in Chinese Patent Application No. 201710331254.5, which corresponds with U.S. Appl. No. 15/655,749, 7 pages.

Notice of Allowance, dated Apr. 18, 2019, received in Korean Patent Application No. 2017-7034248, which corresponds with U.S. Appl. No. 15/655,749, 5 pages.

Patent, dated Jul. 3, 2019, received in Korean Patent Application No. 2017-7034248, which corresponds with U.S. Appl. No. 15/655,749, 5 pages.

Office Action, dated Aug. 1, 2019, received in U.S. Appl. No. 15/785,372, 22 pages.

Final Office Action, dated Feb. 5, 2020, received in U.S. Appl. No. 15/785,372, 26 pages.

Office Action, dated Jul. 23, 2020, received in U.S. Appl. No. 15/785,372, 23 pages.

Final Office Action, dated Nov. 18, 2020, received in U.S. Appl. No. 15/785,372, 27 pages.

Notice of Allowance, dated Jul. 14, 2021, received in U.S. Appl. No. 15/785,372, 11 pages.

Notice of Allowance, dated Oct. 22, 2021, received in U.S. Appl. No. 15/785,372, 11 pages.

Office Action, dated Oct. 31, 2017, received in U.S. Appl. No. 15/723,069, 7 pages.

Notice of Allowance, dated Dec. 21, 2017, received in U.S. Appl. No. 15/723,069, 7 pages.

Office Action, dated Apr. 11, 2019, received in U.S. Appl. No. 15/889,115, 9 pages.

Final Office Action, dated Oct. 28, 2019, received in U.S. Appl. No. 15/889,115, 12 pages.

Notice of Allowance, dated May 19, 2020, received in U.S. Appl. No. 15/889,115, 9 pages.

Office Action, dated Jul. 25, 2019, received in U.S. Appl. No. 15/979,347, 14 pages.

Final Office Action, dated Feb. 27, 2020, received in U.S. Appl. No. 15/979,347, 19 pages.

Office Action, dated Jul. 14, 2020, received in U.S. Appl. No. 15/979,347, 10 pages.

Final Office Action, dated Jan. 25, 2021, received in U.S. Appl. No. 15/979,347, 12 pages.

Office Action, dated Sep. 25, 2020, received in U.S. Appl. No. 15/994,843, 5 pages.

Notice of Allowance, dated Jan. 22, 2021, received in U.S. Appl. No. 15/994,843, 8 pages.

Office Action, dated Nov. 25, 2019, received in U.S. Appl. No. 16/049,725, 9 pages.

Notice of Allowance, dated May 14, 2020, received in U.S. Appl. No. 16/049,725, 9 pages.

Office Action, dated May 31, 2019, received in Australian Patent Application No. 2018253539, which corresponds with U.S. Appl. No. 16/049,725, 3 pages.

Notice of Acceptance, dated Apr. 2, 2020, received in Australian Patent Application No. 2018253539, which corresponds with U.S. Appl. No. 16/049,725, 3 pages.

Certificate of Grant, dated Aug. 13, 2020, received in Australian Patent Application No. 2018253539, which corresponds with U.S. Appl. No. 16/049,725, 3 pages.

Notice of Allowance, dated Oct. 10, 2019, received in U.S. Appl. No. 16/102,409, 9 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Office Action, dated Nov. 29, 2019, received in U.S. Appl. No. 16/136,163, 9 pages.

Final Office Action, dated Jun. 9, 2020, received in U.S. Appl. No. 16/136,163, 10 pages.

Office Action, dated Sep. 17, 2020, received in U.S. Appl. No. 16/136,163, 13 pages.

Final Office Action, dated May 20, 2021, received in U.S. Appl. No. 16/136,163, 13 pages.

Office Action, dated Nov. 23, 2021, received in U.S. Appl. No. 16/136,163, 27 pages.

Office Action, dated Mar. 9, 2020, received in U.S. Appl. No. 16/145,954, 15 pages.

Office Action, dated Dec. 10, 2020, received in U.S. Appl. No. 16/145,954, 5 pages.

Office Action, dated Mar. 6, 2020, received in U.S. Appl. No. 16/154,591, 16 pages.

Final Office Action, dated Oct. 1, 2020, received in U.S. Appl. No. 16/154,591, 19 pages.

Office Action, dated Mar. 4, 2021, received in U.S. Appl. No. 16/154,591, 20 pages.

Office Action, dated May 4, 2020, received in Australian Patent Application No. 2019203175, which corresponds with U.S. Appl. No. 16/154,591, 4 pages.

Office Action, dated Oct. 13, 2020, received in Australian Patent Application No. 2019203175, which corresponds with U.S. Appl. No. 16/154,591, 5 pages.

Office Action, dated Dec. 2, 2019, received in Japanese Patent Application No. 2018-202048, which corresponds with U.S. Appl. No. 16/154,591, 6 pages.

Notice of Allowance, dated Jun. 1, 2020, received in Japanese Patent Application No. 2018-202048, which corresponds with U.S. Appl. No. 16/154,591, 3 pages.

Patent, dated Jun. 25, 2020, received in Japanese Patent Application No. 2018-202048, which corresponds with U.S. Appl. No. 16/154,591, 4 pages.

Office Action, dated Aug. 20, 2019, received in Korean Patent Application No. 2019-7019946, which corresponds with U.S. Appl. No. 16/154,591, 6 pages.

Office Action, dated Feb. 27, 2020, received in Korean Patent Application No. 2019-7019946, which corresponds with U.S. Appl. No. 16/154,591, 5 pages.

Office Action, dated Mar. 29, 2021, received in Korean Patent Application No. 2019-7019946, which corresponds with U.S. Appl. No. 16/154,591, 6 pages.

Notice of Allowance, dated Aug. 26, 2021, received in Korean Patent Application No. 2019-7019946, which corresponds with U.S. Appl. No. 16/154,591, 2 pages.

Patent, dated Sep. 7, 2021, received in Korean Patent Application No. 2019-7019946, which corresponds with U.S. Appl. No. 16/154,591, 4 pages.

Office Action, dated Nov. 25, 2019, received in U.S. Appl. No. 16/174,170, 31 pages.

Final Office Action, dated Mar. 19, 2020, received in U.S. Appl. No. 16/174,170, 25 pages.

Notice of Allowance, dated Jun. 18, 2020, received in U.S. Appl. No. 16/174,170, 19 pages.

Notice of Allowance, dated Aug. 26, 2020, received in U.S. Appl. No. 16/240,669, 18 pages.

Office Action, dated Oct. 30, 2020, received in U.S. Appl. No. 16/230,707, 20 pages.

Notice of Allowance, dated Feb. 18, 2021, received in U.S. Appl. No. 16/230,707, 9 pages.

Office Action, dated Aug. 10, 2020, received in U.S. Appl. No. 16/240,672, 13 pages.

Final Office Action, dated Nov. 27, 2020, received in U.S. Appl. No. 16/240,672, 12 pages.

Office Action, dated May 17, 2021, received in U.S. Appl. No. 16/240,672, 14 pages.

Notice of Allowance, dated Sep. 2, 2021, received in U.S. Appl. No. 16/240,672, 13 pages.

Office Action, dated Sep. 24, 2020, received in Australian Patent Application No. 2019268116, which corresponds with U.S. Appl. No. 16/240,672, 4 pages.

Office Action, dated Jan. 28, 2021, received in Australian Patent Application No. 2019268116, which corresponds with U.S. Appl. No. 16/240,672, 4 pages.

Notice of Allowance, dated Sep. 20, 2021, received in Australian Patent Application No. 2019268116, which corresponds with U.S. Appl. No. 16/240,672, 3 pages.

Office Action, dated Apr. 21, 2021, received in European Patent Application No. 19195414.8, which corresponds with U.S. Appl. No. 16/240,672, 7 pages.

Notice of Allowance, dated May 22, 2020, received in Japanese Patent Application No. 2019-027634, which corresponds with U.S. Appl. No. 16/240,672, 5 pages.

Patent, dated Jun. 23, 2020, received in Japanese Patent Application No. 2019-027634, which corresponds with U.S. Appl. No. 16/240,672, 4 pages.

Office Action, dated May 22, 2019, received in U.S. Appl. No. 16/230,743, 7 pages.

Notice of Allowance, dated Sep. 11, 2019, received in U.S. Appl. No. 16/230,743, 5 pages.

Office Action, dated Mar. 6, 2020, received in U.S. Appl. No. 16/243,834, 19 pages.

Notice of Allowance, dated Sep. 24, 2020, received in U.S. Appl. No. 16/243,834, 10 pages.

Office Action, dated Dec. 18, 2019, received in Australian Patent Application No. 2018282409, which corresponds with U.S. Appl. No. 16/243,834, 3 pages.

Office Action, dated Sep. 18, 2020, received in Australian Patent Application No. 2018282409, which corresponds with U.S. Appl. No. 16/243,834, 3 pages.

Notice of Acceptance, dated Oct. 21, 2020, received in Australian Patent Application No. 2018282409, which corresponds with U.S. Appl. No. 16/243,834, 3 pages.

Certificate of Grant, dated Feb. 18, 2021, received in Australian Patent Application No. 2018282409, which corresponds with U.S. Appl. No. 16/243,834, 3 pages.

Office Action, dated Aug. 7, 2020, received in Japanese Patent Application No. 2019-058800, which corresponds with U.S. Appl. No. 16/243,834, 8 pages.

Office Action, dated Feb. 12, 2021, received in Japanese Patent Application No. 2019-058800, which corresponds with U.S. Appl. No. 16/243,834, 2 pages.

Office Action, dated Jul. 5, 2019, received in Korean Patent Application No. 2018-7037896, which corresponds with U.S. Appl. No. 16/243,834, 2 pages.

Notice of Allowance, dated Dec. 23, 2019, received in Korean Patent Application No. 2018-7037896, which corresponds with U.S. Appl. No. 16/243,834, 6 pages.

Patent, dated Mar. 13, 2020, received in Korean Patent Application No. 2018-7037896, which corresponds with U.S. Appl. No. 16/243,834, 7 pages.

Office Action, dated Nov. 30, 2021, received in Russian Patent Application No. 2018146112, which corresponds with U.S. Appl. No. 16/243,834, 15 pages.

Notice of Allowance, dated Apr. 14, 2022, received in Russian Patent Application No. 2018146112, which corresponds with U.S. Appl. No. 16/243,834, 2 pages.

Notice of Allowance, dated Nov. 20, 2020, received in U.S. Appl. No. 16/262,784, 8 pages.

Office action, dated Feb. 25, 2021, received in Australian Patent Application No. 2020201648, which corresponds with U.S. Appl. No. 16/262,784, 3 pages.

Notice of Allowance, dated Dec. 14, 2021, received in Australian Patent Application No. 2020201648, which corresponds with U.S. Appl. No. 16/262,784, 3 pages.

Office Action, dated Feb. 5, 2021, received in U.S. Appl. No. 16/262,800, 53 pages.

Final Office Action, dated Jun. 4, 2021, received in U.S. Appl. No. 16/262,800, 65 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Office Action, dated Sep. 15, 2020, received in European Patent Application No. 19194439.6, which corresponds with U.S. Appl. No. 16/262,800, 6 pages.

Office Action, dated Mar. 25, 2021, received in European Patent Application No. 19194439.6, which corresponds with U.S. Appl. No. 16/262,800, 5 pages.

Notice of Allowance, dated Apr. 19, 2019, received in U.S. Appl. No. 16/252,478, 11 pages.

Office Action, dated Jun. 11, 2020, received in Australian Patent Application No. 2019257437, which corresponds with U.S. Appl. No. 16/252,478, 3 pages.

Notice of Allowance, dated Sep. 15, 2020, received in Australian Patent Application No. 2019257437, which corresponds with U.S. Appl. No. 16/252,478, 3 pages.

Notice of Allowance, dated Dec. 13, 2019, received in Korean Patent Application No. 2019-7033444, which corresponds with U.S. Appl. No. 16/252,478, 6 pages.

Patent, dated Mar. 12, 2020, received in Korean Patent Application No. 2019-7033444, which corresponds with U.S. Appl. No. 16/252,478, 6 pages.

Office action, dated Aug. 27, 2020, received in U.S. Appl. No. 16/241,883, 11 pages.

Notice of Allowance, dated Sep. 28, 2020, received in U.S. Appl. No. 16/241,883, 10 pages.

Office Action, dated Aug. 10, 2021, received in European Patent Application No. 19181042.3, which corresponds with U.S. Appl. No. 16/241,883, 7 pages.

Office Action, dated Oct. 1, 2021, received in Japanese Patent Application No. 2020-174097, which corresponds with U.S. Appl. No. 16/241,883, 2 pages.

Office Action, dated Jul. 15, 2019, received in U.S. Appl. No. 16/258,394, 8 pages.

Notice of Allowance, dated Nov. 6, 2019, received in U.S. Appl. No. 16/258,394, 8 pages.

Office Action, dated Oct. 21, 2021, received in Australian Patent Application No. 2020267298, which corresponds with U.S. Appl. No. 16/258,394, 2 pages.

Office Action, dated May 14, 2020, received in U.S. Appl. No. 16/354,035, 16 pages.

Notice of Allowance, dated Aug. 25, 2020, received in U.S. Appl. No. 16/354,035, 14 pages.

Office Action, dated Jun. 9, 2021, received in U.S. Appl. No. 16/896,141, 21 pages.

Final Office Action, dated Dec. 13, 2021, received in U.S. Appl. No. 16/896,141, 29 pages.

Office Action, dated Oct. 11, 2019, received in Australian Patent Application No. 2019202417, which corresponds with U.S. Appl. No. 16/896,141, 4 pages.

Notice of Allowance, dated Jul. 6, 2020, received in Australian Patent Application No. 2019202417, which corresponds with U.S. Appl. No. 16/896,141, 3 pages.

Certificate of Grant, dated Nov. 5, 2020, received in Australian Patent Application No. 2019202417, which corresponds with U.S. Appl. No. 16/896,141, 4 pages.

Office Action, dated Aug. 21, 2020, received in Japanese Patent Application No. 2019-047319, which corresponds with U.S. Appl. No. 16/896,141, 6 pages.

Office Action, dated Apr. 9, 2021, received in Japanese Patent Application No. 2019-047319, which corresponds with U.S. Appl. No. 16/896,141, 2 pages.

Office Action, dated Aug. 30, 2019, received in Korean Patent Application No. 2019-7019100, 2 pages.

Notice of Allowance, dated Nov. 1, 2019, received in Korean Patent Application No. 2019-7019100, 5 pages.

Patent, dated Jan. 31, 2020, received in Korean Patent Application No. 2019-7019100, 5 pages.

Office Action, dated May 14, 2020, received in U.S. Appl. No. 16/509,438, 16 pages.

Notice of Allowance, dated Jan. 6, 2021, received in U.S. Appl. No. 16/509,438, 5 pages.

Notice of Allowance, dated Apr. 29, 2021, received in U.S. Appl. No. 16/509,438, 9 pages.

Office Action, dated Sep. 6, 2021, received in Chinese Patent Application No. 201910718931.8, 6 pages.

Notice of Allowance, dated May 20, 2020, received in U.S. Appl. No. 16/534,214, 16 pages.

Office Action, dated Oct. 7, 2020, received in U.S. Appl. No. 16/563,505, 20 pages.

Final Office Action, dated May 12, 2021, received in U.S. Appl. No. 16/563,505, 19 pages.

Office Action, dated Oct. 5, 2021, received in U.S. Appl. No. 16/563,505, 19 pages.

Office Action, dated Oct. 19, 2020, received in U.S. Appl. No. 16/685,773, 15 pages.

Final Office Action, dated Feb. 2, 2021, received in U.S. Appl. No. 16/685,773, 20 pages.

Office Action, dated Dec. 14, 2021, received in U.S. Appl. No. 16/685,773, 20 pages.

Office Action, dated Oct. 30, 2020, received in U.S. Appl. No. 16/824,490, 15 pages.

Notice of Allowance, dated Feb. 24, 2021, received in U.S. Appl. No. 16/824,490, 8 pages.

Office Action, dated Sep. 21, 2020, received in U.S. Appl. No. 16/803,904, 5 pages.

Notice of Allowance, dated Jan. 6, 2021, received in U.S. Appl. No. 16/803,904, 9 pages.

Notice of Allowance, dated Oct. 25, 2021, received in U.S. Appl. No. 17/003,869, 21 pages.

Office Action, dated Aug. 30, 2021, received in Australian Patent Application No. 2020244406, which corresponds with U.S. Appl. No. 17/003,869, 4 pages.

Notice of Allowance, dated May 4, 2020, received in Korean Patent Application No. 2019-7033444, which corresponds with U.S. Appl. No. 17/003,869, 5 pages.

Patent, dated Jun. 3, 2020, received in Korean Patent Application No. 2019-7033444, which corresponds with U.S. Appl. No. 17/003,869, 7 pages.

Notice of Allowance, dated Dec. 21, 2021, received in U.S. Appl. No. 16/921,083, 25 pages.

Office Action, dated Sep. 8, 2021, received in Japanese Patent Application No. 2020-106360, 2 pages.

Office Action, dated May 26, 2021, received in U.S. Appl. No. 16/988,509, 25 pages.

Final Office Action, dated Sep. 16, 2021, received in U.S. Appl. No. 16/988,509, 38 pages.

Office Action, dated Feb. 23, 2021, received in Korean Patent Application No. 2020-7031330, which corresponds with U.S. Appl. No. 15/272,398, 3 pages.

Office Action, dated Aug. 27, 2021, received in Korean Patent Application No. 2020-7031330, which corresponds with U.S. Appl. No. 15/272,398, 6 pages.

Office Action, dated Dec. 23, 2021, received in Korean Patent Application No. 2020-7031330, which corresponds with U.S. Appl. No. 15/272,398, 8 pages.

Office Action, dated Oct. 26, 2021, received in U.S. Appl. No. 17/103,899, 21 pages.

Office Action, dated Nov. 11, 2021, received in Australian Patent Application No. 2021200655, which corresponds with U.S. Appl. No. 17/103,899, 4 pages.

Office Action, dated Oct. 29, 2021, received in Korean Patent Application No. 2021-7031223, 2 pages.

International Search Report and Written Opinion dated May 26, 2014, received in International Application No. PCT/US2013/040053, which corresponds to U.S. Appl. No. 14/535,671, 32 pages.

International Preliminary Report on Patentability dated Nov. 20, 2014, received in International Application No. PCT/US2013/040053, which corresponds to U.S. Appl. No. 14/535,671, 26 pages.

International Search Report and Written Opinion dated Apr. 7, 2014, received in International Application No. PCT/US2013/069472, which corresponds to U.S. Appl. No. 14/608,895, 24 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

International Preliminary Report on Patentability, dated Jun. 30, 2015, received in International Patent Application No. PCT/US2013/069472, which corresponds with U.S. Appl. No. 14/608,895, 18 pages.

International Search Report and Written Opinion dated Aug. 7, 2013, received in International Application No. PCT/US2013/040054, which corresponds to U.S. Appl. No. 14/536,235, 12 pages.

International Preliminary Report on Patentability dated Nov. 20, 2014, received in International Application No. PCT/US2013/040054, which corresponds to U.S. Appl. No. 14/536,235, 11 pages.

International Search Report and Written Opinion dated Aug. 7, 2013, received in International Application No. PCT/US2013/040056, which corresponds to U.S. Appl. No. 14/536,367, 12 pages.

International Preliminary Report on Patentability dated Nov. 20, 2014, received in International Application No. PCT/US2013/040056, which corresponds to U.S. Appl. No. 14/536,367, 11 pages.

Extended European Search Report, dated Nov. 6, 2015, received in European Patent Application No. 15183980.0, which corresponds with U.S. Appl. No. 14/536,426, 7 pages.

Extended European Search Report, dated Jul. 30, 2018, received in European Patent Application No. 14/536,426, which corresponds with U.S. Appl. No. 14/536,426, 7 pages.

International Search Report and Written Opinion dated Aug. 6, 2013, received in International Application No. PCT/US2013/040058, which corresponds to U.S. Appl. No. 14/536,426, 12 pages.

International Preliminary Report on Patentability dated Nov. 20, 2014, received in International Application No. PCT/US2013/040058, which corresponds to U.S. Appl. No. 14/536,426, 11 pages.

International Search Report and Written Opinion dated Feb. 5, 2014, received in International Application No. PCT/US2013/040061, which corresponds to U.S. Appl. No. 14/536,464, 30 pages.

International Preliminary Report on Patentability dated Nov. 20, 2014, received in International Application No. PCT/US2013/040061, which corresponds to U.S. Appl. No. 14/536,464, 26 pages.

International Search Report and Written Opinion dated May 8, 2014, received in International Application No. PCT/US2013/040067, which corresponds to U.S. Appl. No. 14/536,644, 45 pages.

International Preliminary Report on Patentability dated Nov. 20, 2014, received in International Application No. PCT/US2013/040067, which corresponds to U.S. Appl. No. 14/536,644, 36 pages.

International Search Report and Written Opinion dated Mar. 12, 2014, received in International Application No. PCT/US2013/069479, which corresponds with U.S. Appl. No. 14/608,926, 14 pages.

International Preliminary Report on Patentability, dated Jun. 30, 2015, received in International Patent Application No. PCT/US2013/069479, which corresponds with U.S. Appl. No. 14/608,926, 11 pages.

International Search Report and Written Opinion dated Aug. 7, 2013, received in International Application No. PCT/US2013/040070, which corresponds to U.S. Appl. No. 14/535,646, 12 pages.

International Preliminary Report on Patentability dated Nov. 20, 2014, received in International Application No. PCT/US2013/040070, which corresponds to U.S. Appl. No. 14/535,646, 10 pages.

International Search Report and Written Opinion dated Apr. 7, 2014, received in International Application No. PCT/US2013/040072, which corresponds to U.S. Appl. No. 14/536,141, 38 pages.

International Preliminary Report on Patentability dated Nov. 20, 2014, received in International Application No. PCT/US2013/040072, which corresponds to U.S. Appl. No. 14/536,141, 32 pages.

Extended European Search Report, dated Dec. 5, 2018, received in European Patent Application No. 18194127.9, which corresponds with U.S. Appl. No. 14/608,942, 8 pages.

International Search Report and Written Opinion dated Apr. 7, 2014, received in International Application No. PCT/US2013/069483, which corresponds with U.S. Appl. No. 14/608,942, 18 pages.

International Preliminary Report on Patentability, dated Jun. 30, 2015, received in International Application No. PCT/2013/069483, which corresponds to U.S. Appl. No. 14/608,942, 13 pages.

International Search Report and Written Opinion dated Mar. 3, 2014, received in International Application No. PCT/US2013/040087, which corresponds to U.S. Appl. No. 14/536,166, 35 pages.

International Preliminary Report on Patentability dated Nov. 20, 2014, received in International Application No. PCT/2013/040087, which corresponds to U.S. Appl. No. 14/536,166, 29 pages.

International Search Report and Written Opinion dated Aug. 7, 2013, received in International Application No. PCT/US2013/040093, which corresponds to U.S. Appl. No. 14/536,203, 11 pages.

International Preliminary Report on Patentability dated Nov. 20, 2014, received in International Application No. PCT/2013040093, which corresponds to U.S. Pat. No. 14,536,203, 9 pages.

International Search Report and Written Opinion dated Jul. 9, 2014, received in International Application No. PCT/US2013/069484, which corresponds with U.S. Appl. No. 14/608,965, 17 pages.

International Preliminary Report on Patentability, dated Jun. 30, 2015, received in International Patent Application No. PCT/US2013/069484, which corresponds with U.S. Appl. No. 14/608,965, 12 pages.

International Search Report and Written Opinion dated Feb. 5, 2014, received in International Application No. PCT/US2013/040098, which corresponds to U.S. Appl. No. 14/536,247, 35 pages.

International Preliminary Report on Patentability dated Nov. 20, 2014, received in International Application No. PCT/2013/040098, which corresponds to U.S. Appl. No. 14/536,247, 27 pages.

Extended European Search Report, dated Oct. 7, 2016, received in European Patent Application No. 16177863.4, which corresponds with U.S. Appl. No. 14/536,267, 12 pages.

Extended European Search Report, dated Oct. 30, 2018, received in European Patent Application No. 18183789.9, which corresponds with U.S. Appl. No. 14/536,267, 11 pages.

International Search Report and Written Opinion dated Jan. 27, 2014, received in International Application No. PCT/US2013/040101, which corresponds to U.S. Appl. No. 14/536,267, 30 pages.

International Preliminary Report on Patentability dated Nov. 20, 2014, received in International Application No. PCT/2013/040101, which corresponds to U.S. Appl. No. 14/536,267, 24 pages.

Extended European Search Report, dated Nov. 24, 2017, received in European Patent Application No. 17186744.3, which corresponds with U.S. Appl. No. 14/536,291, 10 pages.

International Search Report and Written Opinion dated Jan. 8, 2014, received in International Application No. PCT/US2013/040108, which corresponds to U.S. Appl. No. 14/536,291, 30 pages.

International Preliminary Report on Patentability dated Nov. 20, 2014, received in International Application No. PCT/2013/040108, which corresponds to U.S. Appl. No. 14/536,291, 25 pages.

International Search Report and Written Opinion dated Jun. 2, 2014, received in International Application No. PCT/US2013/069486, which corresponds with U.S. Appl. No. 14/608,985, 7 pages.

International Preliminary Report on Patentability, dated Jun. 30, 2015, received in International Patent Application No. PCT/US2013/069486, which corresponds with U.S. Appl. No. 14/608,985, 19 pages.

International Search Report and Written Opinion dated Mar. 6, 2014, received in International Application No. PCT/US2013/069489, which corresponds with U.S. Appl. No. 14/609,006, 12 pages.

International Preliminary Report on Patentability, dated Jun. 30, 2015, received in International Patent Application No. PCT/US2013/069489, which corresponds with U.S. Appl. No. 14/609,006, 10 pages.

Extended European Search Report, dated Mar. 15, 2017, received in European Patent Application No. 17153418.3, which corresponds with U.S. Appl. No. 14/536,648, 7 pages.

Search Report, dated Apr. 13, 2017, received in Dutch Patent Application No. 2016452, which corresponds with U.S. Appl. No. 14/864,737, 22 pages.

Search Report, dated Jun. 22, 2017, received in Dutch Patent Application No. 2016375, which corresponds with U.S. Appl. No. 14/866,981, 17 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

International Search Report and Written Opinion, dated Oct. 14, 2016, received in International Patent Application No. PCT/US2016/020697, which corresponds with U.S. Appl. No. 14/866,981, 21 pages.

Search Report, dated Jun. 19, 2017, received in Dutch Patent Application No. 2016377, which corresponds with U.S. Appl. No. 14/866,159, 13 pages.

International Search Report and Written Opinion, dated Apr. 25, 2016, received in International Patent Application No. PCT/US2016/018758, which corresponds with U.S. Appl. No. 14/866,159, 15 pages.

Extended European Search Report, dated Oct. 17, 2017, received in European Patent Application No. 17184437.6, Which corresponds with U.S. Appl. No. 14/868,078, 8 pages.

Search Report, dated Apr. 13, 2017, received in Dutch Patent Application No. 2016376, which corresponds with U.S. Appl. No. 14/868,078, 15 pages.

International Search Report and Written Opinion, dated Jul. 21, 2016, received in International Patent Application No. PCT/US2016/019913, which corresponds with U.S. Appl. No. 14/868,078, 16 pages.

Search Report, dated Apr. 18, 2017, received in Dutch Patent Application No. 2016801, which corresponds with U.S. Appl. No. 14/863,432, 34 pages.

International Search Report and Written Opinion, dated Oct. 31, 2016, received in International Patent Application No. PCT/US2016/033578, which corresponds with U.S. Appl. No. 14/863,432, 36 pages.

International Search Report and Written Opinion, dated Nov. 14, 2016, received in International Patent Application No. PCT/US2016/033541, which corresponds with U.S. Appl. No. 14/866,511, 29 pages.

Extended European Search Report, dated Aug. 17, 2018, received in European Patent Application No. 18175195.9, which corresponds with U.S. Appl. No. 14/869,899, 13 pages.

International Search Report and Written Opinion, dated Aug. 29, 2016, received in International Patent Application No. PCT/US2016/021400, which corresponds with U.S. Appl. No. 14/869,899, 48 pages.

International Preliminary Report on Patentability, dated Sep. 12, 2017, received in International Patent Application No. PCT/US2016/021400, which corresponds with U.S. Appl. No. 14/869,899, 39 pages.

International Search Report and Written Opinion, dated Jan. 12, 2017, received in International Patent No. PCT/US2016/046419, which corresponds with U.S. Appl. No. 14/866,992, 23 pages.

International Search Report and Written Opinion, dated Dec. 15, 2016, received in International Patent Application No. PCT/US2016/046403, which corresponds with U.S. Appl. No. 15/009,661, 17 pages.

International Search Report and Written Opinion, dated Feb. 27, 2017, received in International Patent Application No. PCT/US2016/046407, which corresponds with U.S. Appl. No. 15/009,688, 30 pages.

International Preliminary Report on Patentability, dated Feb. 13, 2018, received in International Patent Application No. PCT/US2016/046407, which corresponds with U.S. Appl. No. 15/009,688, 20 pages.

Search Report, dated Feb. 15, 2018, received in Dutch Patent Application No. 2019215, which corresponds with U.S. Appl. No. 14/864,529, 13 pages.

Extended European Search Report, dated Nov. 14, 2019, received in European Patent Application No. 19194418.0, which corresponds with U.S. Appl. No. 14/864,580, 8 pages.

Search Report, dated Feb. 15, 2018, received in Dutch Patent Application No. 2019214, which corresponds with U.S. Appl. No. 14/864,601, 12 pages.

Extended European Search Report, dated Oct. 10, 2017, received in European Patent Application No. 17188507.2, which corresponds with U.S. Appl. No. 14/866,361, 9 pages.

Extended European Search Report, dated Jun. 22, 2017, received in European Patent Application No. 16189421.7, which corresponds with U.S. Appl. No. 14/866,987, 7 pages.

Extended European Search Report, dated Sep. 11, 2017, received in European Patent Application No. 17163309.2, which corresponds with U.S. Appl. No. 14/866,987, 8 pages.

Extended European Search Report, dated Jun. 8, 2017, received in European Patent Application No. 16189425.8, which corresponds with U.S. Appl. No. 14/866,989, 8 pages.

Extended European Search Report, dated Aug. 2, 2018, received in European Patent Application No. 18168941.5, which corresponds with U.S. Appl. No. 14/871,236, 11 pages.

Extended European Search Report, dated Jul. 25, 2017, received in European Patent Application No. 17171972.7, which corresponds with U.S. Appl. No. 14/870,882, 12 pages.

Extended European Search Report, dated Jul. 25, 2017, received in European Patent Application No. 17172266.3, which corresponds with U.S. Appl. No. 14/871,336, 9 pages.

Extended European Search Report, dated Dec. 21, 2016, received in European Patent Application No. 16189790.5, which corresponds with U.S. Appl. No. 14/871,462, 8 pages.

Extended European Search Report, dated Mar. 8, 2019, received in European Patent Application No. 18205283.7, which corresponds with U.S. Appl. No. 15/081,771, 15 pages.

Extended European Search Report, dated Aug. 24, 2018, received in European Patent Application No. 18171453.6, which corresponds with U.S. Appl. No. 15/136,782, 9 pages.

International Search Report and Written Opinion, dated Jan. 3, 2017, received in International Patent Application No. PCT/US2016/046214, which corresponds with U.S. Appl. No. 15/231,745, 25 pages.

Extended European Search Report, dated May 30, 2018, received in European Patent Application No. 18155939.4, which corresponds with U.S. Appl. No. 15/272,327, 8 pages.

Extended European Search Report, dated Mar. 2, 2018, received in European Patent Application No. 17206374.5, which corresponds with U.S. Appl. No. 15/272,343, 11 pages.

Extended European Search Report, dated Oct. 6, 2020, received in European Patent Application No. 20188553.0, which corresponds with U.S. Appl. No. 15/499,693, 11 pages.

Extended European Search Report, dated Oct. 28, 2019, received in European Patent Application No. 19195414.8, which corresponds with U.S. Appl. No. 16/240,672, 6 pages.

Extended European Search Report, dated Nov. 13, 2019, received in European Patent Application No. 19194439.6, which corresponds with U.S. Appl. No. 16/262,800, 12 pages.

Extended European Search Report, dated Oct. 9, 2019, received in European Patent Application No. 19181042.3, which corresponds with U.S. Appl. No. 15/272,343, 10 pages.

Anonymous, RX-V3800AV Receiver Owner's Manual, Yamaha Music Manuals, www.Manualslib.com, Dec. 31, 2007, 169 pages.  
Office Action, dated Jan. 10, 2022, received in Chinese Patent Application No. 201810369259.1, which corresponds with U.S. Appl. No. 14/608,926, 4 pages.

Patent, dated Dec. 13, 2021, received in Japanese Patent Application No. 2018-022394, which corresponds with U.S. Appl. No. 14/536,203, 3 pages.

Notice of Allowance, dated Mar. 21, 2022, received in Chinese Patent Application No. 201810332044.2, which corresponds with U.S. Appl. No. 14/536,267, 1 page.

Intent to Grant, dated Mar. 16, 2022, received in European Patent Application No. 18183789.9, which corresponds with U.S. Appl. No. 16/262,800, 7 pages.

Notice of Allowance, dated Feb. 4, 2022, received in Japanese Patent Application No. 2020-185336, which corresponds with U.S. Appl. No. 14/864,580, 2 pages.

Patent, dated Mar. 3, 2022, received in Japanese Patent Application No. 2020-185336, which corresponds with U.S. Appl. No. 14/864,580, 3 pages.

(56) **References Cited**

## OTHER PUBLICATIONS

Notice of Allowance, dated Feb. 9, 2022, received in Chinese Patent Application No. 201610869950.7, which corresponds with U.S. Appl. No. 14/871,462, 1 page.

Patent, dated Mar. 8, 2022, received in Chinese Patent Application No. 201610869950.7, which corresponds with U.S. Appl. No. 14/871,462, 7 pages.

Patent, dated Jan. 27, 2022, received in Australian Patent Application No. 2019268116, which corresponds with U.S. Appl. No. 16/240,672, 3 pages.

Office Action, dated Apr. 11, 2022, received in Japanese Patent Application No. 2019-058800, which corresponds with U.S. Appl. No. 16/243,834, 4 pages.

Notice of Allowance, dated Jan. 24, 2022, received in U.S. Appl. No. 16/262,800, 26 pages.

Notice of Allowance, dated Jan. 14, 2022, received in Australian Patent Application No. 2020267298, which corresponds with U.S. Appl. No. 16/258,394, 3 pages.

Final Office Action, dated Mar. 4, 2022, received in Japanese Patent Application No. 2019-047319, which corresponds with U.S. Appl. No. 16/896,141, 2 pages.

Office Action, dated Mar. 17, 2022, received in Chinese Patent Application No. 201910718931.8, 1 page.

Notice of Allowance, dated Jan. 14, 2022, received in Australian Patent Application No. 2020244406, which corresponds with U.S. Appl. No. 17/003,869, 3 pages.

Office Action, dated Mar. 16, 2022, received in U.S. Appl. No. 17/138,676, 22 pages.

Patent, dated Jan. 27, 2022, received in Korean Patent Application No. 2021-7031223, 5 pages.

Notice of Allowance, dated Feb. 21, 2022, received in Korean Patent Application No. 2022-7003345, 2 pages.

International Search Report and Written Opinion, dated Jan. 11, 2022, received in International Application No. PCT/US2021/042402, which corresponds with U.S. Appl. No. 17/031,637, 50 pages.

Bognot, "Microsoft Windows 7 Aero Shake, Snap, and Peek", <https://www.youtube.com/watch?v=vgD7wGrsQg4>, Apr. 3, 2012, 4 pages.

Microsoft, "Windows 7 Aero Shake, Snap, and Peek", [hr.msu.edu/techtips/hrsds/window\\_7\\_snappeekandshake.pdf](http://hr.msu.edu/techtips/hrsds/window_7_snappeekandshake.pdf), Apr. 4, 2012, 6 pages.

Intent to Grant, dated May 11, 2022, received in European Patent Application No. 13795392.3, which corresponds with U.S. Appl. No. 14/608,926, 7 pages.

Decision to Grant, dated Jun. 17, 2022, received in European Patent Application No. 13795392.3, which corresponds with U.S. Appl. No. 14/608,926, 7 pages.

Patent, dated Jul. 13, 2022, received in European Patent Application No. 13795392.3, which corresponds with U.S. Appl. No. 14/608,926, 4 pages.

Patent, dated May 27, 2022, received in Chinese Patent Application No. 201810332044.2, which corresponds with U.S. Appl. No. 14/536,267, 6 pages.

Decision to Grant, dated Jul. 21, 2022, received in European Patent Application No. 18183789.9, which corresponds with U.S. Appl. No. 16/262,800, 3 pages.

Patent, dated Aug. 17, 2022, received in European Patent Application No. 18183789.9, which corresponds with U.S. Appl. No. 16/262,800, 4 pages.

Decision on Appeal, dated Jun. 9, 2022, received in U.S. Appl. No. 14/609,006, 11 pages.

Office Action, dated Jul. 29, 2022, received in Indian Patent Application No. 202118007136, which corresponds with U.S. Appl. No. 14/866,511, 9 pages.

Office Action, dated Aug. 23, 2022, received in European Patent Application No. 19194418.0, which corresponds with U.S. Appl. No. 14/864,580, 6 pages.

Intent to Grant, dated Jan. 9, 2023, received in European Patent Application No. 16711725.8, which corresponds with U.S. Appl. No. 14/867,990, 7 pages.

Intention to Grant, dated Sep. 26, 2022, received in European Patent Application No. 16753795.0, which corresponds with U.S. Appl. No. 15/009,668, 7 pages.

Decision to Grant, dated Nov. 24, 2022, received in European Patent Application No. 16753795.0, which corresponds with U.S. Appl. No. 15/009,668, 4 pages.

Patent, dated Dec. 21, 2023, received in European Patent Application No. 16753795.0, which corresponds with U.S. Appl. No. 15/009,668, 4 pages.

Notice of Allowance, dated Oct. 14, 2022, received in Japanese Patent Application No. 2021-157204, which corresponds with U.S. Appl. No. 15/272,327, 2 pages.

Office Action, dated Jun. 7, 2022, received in European Patent Application No. 20188553.0, which corresponds with U.S. Appl. No. 15/499,693, 7 pages.

Notice of Allowance, dated Jan. 20, 2023, received in Japanese Patent Application No. 2019-058800, which corresponds with U.S. Appl. No. 16/243,834, 2 pages.

Office Action, dated Jul. 25, 2022, received in Japanese Patent Application No. 2021-099049, which corresponds with U.S. Appl. No. 16/243,834, 2 pages.

Office Action, dated Jul. 18, 2022, received in Mexican Patent Application No. MX/a/2020/011482, which corresponds with U.S. Appl. No. 16/243,834, 4 pages.

Office Action, dated Jan. 5, 2023, received in Mexican Patent Application No. MX/a/2020/011482, which corresponds with U.S. Appl. No. 16/243,834, 5 pages.

Certificate of Grant, dated Apr. 21, 2022, received in Australian Patent Application No. 2020201648, which corresponds with U.S. Appl. No. 16/262,784, 3 pages.

Patent, dated Jun. 14, 2022, received in Japanese Patent Application No. 2020-174097, which corresponds with U.S. Appl. No. 16/241,883, 3 pages.

Patent, dated May 19, 2022, received in Australian Patent Application No. 2020267298, which corresponds with U.S. Appl. No. 16/258,394, 4 pages.

Office Action, dated Oct. 3, 2022, received in Japanese Patent Application No. 2021-132350, which corresponds with U.S. Appl. No. 16/258,394, 2 pages.

Final Office Action, dated Sep. 16, 2022, received in Japanese Patent Application No. 2019-047319, which corresponds with U.S. Appl. No. 16/896,141, 2 pages.

Notice of Allowance, dated Sep. 20, 2022, received in Chinese Patent Application No. 201910610331.X, 1 page.

Patent, dated Nov. 25, 2022, received in Chinese Patent Application No. 201910610331.X, 7 pages.

Office Action, dated Jul. 18, 2022, received in Chinese Patent Application No. 201910718931.8, 2 pages.

Notice of Allowance, dated Jan. 5, 2023, received in Chinese Patent Application No. 201910718931.8, 4 pages.

Final Office Action, dated Jul. 18, 2022, received in U.S. Appl. No. 16/685,773, 20 pages.

Office Action, dated Dec. 16, 2022, received in Australian Patent Application No. 2022200212, 3 pages.

Office Action, dated May 17, 2022, received in Korean Patent Application No. 2020-7008888, 2 pages.

Notice of Allowance, dated Nov. 23, 2022, received in Korean Patent Application No. 2020-7008888, 2 pages.

Patent, dated May 19, 2022, received in Australian Patent Application No. 2020244406, which corresponds with U.S. Appl. No. 17/003,869, 3 pages.

Office Action, dated Jan. 5, 2023, received in Japanese Patent Application No. 2022-031194, which corresponds with U.S. Appl. No. 17/003,869, 6 pages.

Notice of Allowance, dated Feb. 7, 2022, received in U.S. Appl. No. 16/988,509, 16 pages.

Office Action, dated Apr. 27, 2022, received in Australian Patent Application No. 2020257134, 3 pages.

Notice of Allowance, dated Aug. 23, 2022, received in Australian Patent Application No. 2020257134, 2 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Patent, dated Dec. 22, 2022, received in Australian Patent Application No. 2020257134, 3 pages.

Office Action, dated Apr. 28, 2022, received in Korean Patent Application No. 2022-7005994, 5 pages.

Notice of Allowance, dated Oct. 18, 2022, received in Korean Patent Application No. 2022-7005994, 5 pages.

Final Office Action, dated May 2, 2022, received in U.S. Appl. No. 17/103,899 21 pages.

Office Action, date Aug. 19, 2022, received in U.S. Appl. No. 17/103,899 24 pages.

Final Office Action, dated Jan. 24, 2023, received in U.S. Appl. No. 17/103,899 27 pages.

Office Action, dated Nov. 11, 2021, received in Australian U.S. Appl. No. 17/103,899, which corresponds with U.S. Appl. No. 17/103,899, 4 pages.

Notice of Acceptance, dated Nov. 10, 2022, received in Australian Patent Application No. 2021200655, which corresponds with U.S. Appl. No. 17/103,899, 4 pages.

Office Action, dated Nov. 8, 2022, received in U.S. Appl. No. 17/333,810, 9 pages.

Office Action, dated Jun. 10, 2022, received in U.S. Appl. No. 17/362,852, 12 pages.

Notice of Allowance, dated Aug. 24, 2022, received in U.S. Appl. No. 17/362,852, 9 pages.

Office Action, dated Nov. 9, 2022, received in U.S. Appl. No. 17/409,573, 20 pages.

Notice of Allowance, dated Sep. 22, 2022, received in U.S. Appl. No. 17/524,692, 22 pages.

Office Action, dated Jan. 11, 2023, received in Australian Patent Application No. 2022202892, which corresponds with U.S. Appl. No. 15/113,779, 3 pages.

Office Action, dated Nov. 28, 2022, received in U.S. Appl. No. 17/560,013, 13 pages.

Patent, dated May 10, 2022, received in Korean Patent Application No. 2022-7003345, 8 pages.

Office Action, dated May 23, 2022, received in Korean Patent Application No. 2022-7015718, 2 pages.

Patent, dated Aug. 10, 2022, received in Korean Patent Application No. 2022-7015718, 6 pages.

Office Action, dated Mar. 2, 2023, received in Chinese Patent Application No. 202010281684.2, which corresponds with U.S. Appl. No. 14/864,601, 4 pages.

Office Action, dated Mar. 7, 2023, received in Brazilian Patent Application No. 11201701119-9, which corresponds with U.S. Appl. No. 14/871,236, 4 pages.

Notice of Allowance, dated May 19, 2023, received in Japanese Patent Application No. 2021-099049, which corresponds with U.S. Appl. No. 16/243,834, 2 pages.

Office Action, dated Mar. 2, 2023, received in Indian Patent Application No. 202118003907, which corresponds with U.S. Appl. No. 16/243,834, 11 pages.

Office Action, dated Mar. 12, 2023, received in Chinese Patent Application No. 202010281127.0, which corresponds with U.S. Appl. No. 16/252,478, 4 pages.

Final Office Action, dated Feb. 24, 2023, received in U.S. Appl. No. 16/896,141, 23 pages.

Patent, dated Mar. 17, 2023, received in Chinese Patent Application No. 201910718931.8, 7 pages.

Office Action, dated Feb. 22, 2023, received in Chinese Patent Application No. 202010290361.X, which corresponds with U.S. Appl. No. 17/003,869, 4 pages.

Patent, dated Mar. 16, 2023, received in Australian Patent Application No. 2021200655, which corresponds with U.S. Appl. No. 17/103,899, 3 pages.

Final Office Action, dated Apr. 24, 2023, received in U.S. Appl. No. 17/333,810, 12 pages.

Office Action, dated Mar. 16, 2023, received in U.S. Appl. No. 17/351,035, 23 pages.

Notice of Allowance, dated Mar. 6, 2023, received in U.S. Appl. No. 17/524,692, 14 pages.

Office Action, dated Sep. 20, 2022, received in Australian Patent Application No. 2021254568, which corresponds with U.S. Appl. No. 17/560,013, 4 pages.

Notice of Allowance, dated Mar. 24, 2023, received in U.S. Appl. No. 17/666,495, 28 pages.

Notice of Allowance, dated Apr. 27, 2023, received in U.S. Appl. No. 18/089,397, 16 pages.

Office Action, dated Mar. 30, 2023, received in U.S. Appl. No. 17/875,307, 15 pages.

Office Action, dated Aug. 10, 2023, received in Chinese Patent Application No. 201610658351.8, which corresponds with U.S. Appl. No. 14/866,992, 4 pages.

Patent, dated Aug. 4, 2023, received in Indian Patent Application No. 21617032293, which corresponds with U.S. Appl. No. 14/871,227, 4 pages.

Intent to Grant, dated Jun. 1, 2023, received in European Patent Application No. 14/867,990, which corresponds with U.S. Appl. No. 14/867,990, 8 pages.

Decision to Grant, dated Sep. 7, 2023, received in European Patent Application No. 14/867,990, which corresponds with U.S. Appl. No. 14/867,990, 4 pages.

Intent to Grant, dated Aug. 16, 2023, received in European Patent Application No. 15/499,693, which corresponds with U.S. Appl. No. 15/499,693, 10 pages.

Patent, dated Jan. 27, 2023, received in Japanese Patent Application No. 2019-058800, which corresponds with U.S. Appl. No. 16/243,834, 4 pages.

Patent, dated Jun. 19, 2023, received in Japanese Patent Application No. 2021-099049, which corresponds with U.S. Appl. No. 16/243,834, 4 pages.

Patent, dated Jul. 3, 2023, received in Mexican Patent Application No. MX/a/2020/011482, which corresponds with U.S. Appl. No. 16/243,834, 2 pages.

Final Office Action, dated Jul. 14, 2023, received in Japanese Patent Application No. 2021-132350, which corresponds with U.S. Appl. No. 16/258,394, 2 pages.

Final Office Action, dated Jul. 14, 2023, received in Japanese Patent Application No. 2019-047319, which corresponds with U.S. Appl. No. 16/896,141, 2 pages.

Notice of Allowance, dated Aug. 9, 2023, received in U.S. Appl. No. 17/103,899 7 pages.

Final Office Action, dated May 31, 2023, received in U.S. Appl. No. 17/409,573, 22 pages.

Notice of Allowance, dated Jun. 13, 2023, received in Australian Patent Application No. 2022202892, which corresponds with U.S. Appl. No. 15/113,779, 3 pages.

Office Action, dated Aug. 3, 2023, received in U.S. Appl. No. 17/560,013, 15 pages.

Office Action, dated Jun. 28, 2023, received in Australian Patent Application No. 2021254568, which corresponds with U.S. Appl. No. 17/560,013, 3 pages.

Patent, dated Sep. 15, 2023, received in Chinese Patent Application No. 202010281684.2, which corresponds with U.S. Appl. No. 14/864,601, 7 pages.

Patent, dated Sep. 12, 2023, received in Chinese Patent Application No. 202010281127.0, which corresponds with U.S. Appl. No. 16/252,478, 8 pages.

Patent, dated Sep. 12, 2023, received in Chinese Patent Application No. 202010290361.X, which corresponds with U.S. Appl. No. 17/003,869, 7 pages.

Office Action, dated Sep. 18, 2023, received in U.S. Appl. No. 17/333,810, 12 pages.

Final Office Action, dated Sep. 21, 2023, received in U.S. Appl. No. 17/875,307, 16 pages.

Notice of Allowance, dated Sep. 21, 2023, received in Korean Patent Application No. 2023-702268, 2 pages.

Notice of Allowance, dated Dec. 13, 2023, received in U.S. Appl. No. 17/409,573, 11 pages.

Office Action, dated Oct. 26, 2023, received in U.S. Appl. No. 17/172,032, 17 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Final Office Action, dated Oct. 30, 2023, received in U.S. Appl. No. 17/351,035, 23 pages.

Notice of Allowance, dated Nov. 22, 2023, received in U.S. Appl. No. 17/560,013, 13 pages.

Office Action, dated Nov. 6, 2023, received in Chinese Patent Application No. 201610658351.8, which corresponds with U.S. Appl. No. 14/866,992, 2 pages.

Office Action, dated Oct. 30, 2023, received in European Patent Application No. 19194418.0, which corresponds with U.S. Appl. No. 14/864,580, 9 pages.

Patent, dated Nov. 6, 2023, received in Indian Patent Application No. 201617032291, which corresponds with U.S. Appl. No. 14/866,987, 4 pages.

Patent, dated Oct. 4, 2023, received in European Patent Application No. 16711725.8, which corresponds with U.S. Appl. No. 14/867,990, 2 pages.

Notice of Allowance, dated Oct. 20, 2023, received in Australian Patent Application No. 2022200212, 3 pages.

Patent, dated Oct. 12, 2023, received in Australian Patent Application No. 2022202892, which corresponds with U.S. Appl. No. 15/113,779, 3 pages.

Grant Certificate, dated Oct. 26, 2023, received in Australian Patent Application No. 2021254568, which corresponds with U.S. Appl. No. 17/560,013, 3 pages.

Notice of Allowance, dated Jan. 8, 2024, received in Chinese Patent Application No. 201610658351.8, which corresponds with U.S. Appl. No. 14/866,992, 2 pages.

Office Action, dated Jan. 5, 2024, received in Chinese Patent Application No. 202010969867.3, which corresponds with U.S. Appl. No. 16/262,784, 2 pages.

Notice of Allowance, dated Jan. 12, 2024, received in Japanese Patent Application No. 2021-132350, which corresponds with U.S. Appl. No. 16/258,394, 2 pages.

Notice of Allowance, dated Dec. 6, 2023, received in U.S. Appl. No. 17/103,899 9 pages.

Office Action, dated Dec. 13, 2023, received in Australian Patent Application No. 2023226703, which corresponds with U.S. Appl. No. 18/089,397, 2 pages.

Patent, dated Dec. 21, 2023, received in Korean Patent Application No. 2023-702268, 5 pages.

Notice of Allowance, dated Mar. 1, 2024, received in U.S. Appl. No. 17/333,810, 8 pages.

Notice of Allowance, dated Mar. 14, 2024, received in U.S. Appl. No. 17/351,035, 8 pages.

Notice of Allowance, dated Apr. 2, 2024, received in U.S. Appl. No. 17/875,307, 18 pages.

Patent, dated Feb. 27, 2024, received in Chinese Patent Application No. 201610658351.8, which corresponds with U.S. Appl. No. 14/866,992, 8 pages.

Office Action, dated Apr. 6, 2024, received in Indian U.S. Appl. No. 15/136,782 (7399IN), which corresponds with U.S. Appl. No. 15/136,782, 12 pages.

Intent to Grant, dated Feb. 16, 2024, received in European Application No. 20188553.0, which corresponds with U.S. Appl. No. 15/499,693, 8 pages.

Patent, dated Feb. 14, 2024, received in Japanese Patent Application No. 2021-132350, which corresponds with U.S. Appl. No. 16/258,394, 3 pages.

Office Action, dated Mar. 22, 2024, received in Chinese Patent Application No. 202110696612.9, which corresponds with U.S. Appl. No. 16/896,141, 5 pages.

Patent, dated Feb. 8, 2024, received in Japanese Patent Application No. 2019-047319, which corresponds with U.S. Appl. No. 16/896,141, 3 pages.

Patent, dated Jan. 25, 2024, received in Japanese Patent Application No. 2022-031194, which corresponds with U.S. Appl. No. 17/003,869, 3 pages.

Office Action, dated Feb. 19, 2024, received in Australian Patent Application No. 2022-283731, 5 pages.

\* cited by examiner




Figure 1A




Figure 1B




Figure 2




Figure 3




Figure 4A







Figure 4B





450




451

Figure 5A






450



451

Figure 5B










Figure 5C





450




451

Figure 5D






450



451

Figure 5E








Figure 5F








Figure 5G




450



451

Figure 5H











Figure 5I




450




Intensity of Contact  
11708

451

Figure 5J





450




451

Figure 5K






450



451

Figure 5L



Intensity of Contact  
11708




Figure 5M




Figure 5N






Figure 5O



112


11734

11736




Intensity of Contact  
11738

Figure 5P




112



Intensity of Contact  
11738

Figure 5Q



112





Figure 5R



112






Figure 5S




112




Intensity of Contact 11738

Figure 5T




112



Intensity of Contact 11738

Figure 5U



112





Figure 5V

Intensity of Contact  
11738



112




Figure 5W

Intensity of Contact 11738




Figure 6A




Figure 6B






Figure 7



450



451





Figure 8A



450






Figure 8B



450



451






Figure 8C



450



451






Figure 8D



450



451






Figure 8E



450



451






Figure 8F



450



451




Figure 8G








Figure 8H



450



451






Figure 8I



450



451






Figure 8J



450



451




Figure 8K






Figure 8L



450







Figure 8M



450



451





Figure 8N



450





Figure 80




Figure 8P





Figure 8Q



112


12052-1

12052-2

12052-3


12054

12056



Intensity of Contact  
12056


Figure 8R



112



Figure 8S



112





Figure 8T



112





Figure 8U



112




Figure 8V

12100




Figure 9A




Figure 9B








Figure 10







450



451

Figure 11B





450







Figure 11C





450



451

Figure 11D





450






Figure 11E



450







Figure 11F





450



451

Figure 11G





112





Figure 11H



112





Figure 11I



112





Figure 11J



112





Figure 11K



112





Figure 11L



112





Figure 11M



112




Figure 11N




Figure 12A




Figure 12B







Figure 13



450





450








Figure 14B





450







450





450





450






Figure 14F



450





Figure 14G





Figure 14H





Figure 14I





Figure 14J





Figure 14K





Figure 14L





Figure 14M





Figure 14N

12700




Figure 15A




Figure 15B




Figure 15C




Figure 16

**DEVICE, METHOD, AND GRAPHICAL USER INTERFACE FOR PROVIDING FEEDBACK FOR CHANGING ACTIVATION STATES OF A USER INTERFACE OBJECT**

RELATED APPLICATIONS

This application is a continuation of U.S. application Ser. No. 16/921,083, filed Jul. 6, 2020, which is a continuation of U.S. application Ser. No. 15/889,115, filed Feb. 5, 2018, now U.S. Pat. No. 10,782,871, which is a continuation of U.S. application Ser. No. 14/536,141, filed Nov. 7, 2014, now U.S. Pat. No. 9,886,184, which is continuation of PCT Patent Application Serial No. PCT/US2013/040072, filed on May 8, 2013, entitled “Device, Method, and Graphical User Interface for Providing Feedback for Changing Activation States of a User Interface Object,” which claims the benefit of and priority to U.S. Provisional Patent Application Ser. No. 61/778,287, filed on Mar. 12, 2013, entitled “Device, Method, and Graphical User Interface for Providing Feedback for Changing Activation States of a User Interface Object;” U.S. Provisional Patent Application No. 61/747,278, filed Dec. 29, 2012, entitled “Device, Method, and Graphical User Interface for Manipulating User Interface Objects with Visual and/or Haptic Feedback;” and U.S. Provisional Patent Application No. 61/688,227, filed May 9, 2012, entitled “Device, Method, and Graphical User Interface for Manipulating User Interface Objects with Visual and/or Haptic Feedback,” which applications are incorporated by reference herein in their entireties.

This application is also related to the following: U.S. Provisional Patent Application Ser. No. 61/778,092, filed on Mar. 12, 2013, entitled “Device, Method, and Graphical User Interface for Selecting Object within a Group of Objects;” U.S. Provisional Patent Application Ser. No. 61/778,125, filed on Mar. 12, 2013, entitled “Device, Method, and Graphical User Interface for Navigating User Interface Hierarchies;” U.S. Provisional Patent Application Ser. No. 61/778,156, filed on Mar. 12, 2013, entitled “Device, Method, and Graphical User Interface for Manipulating Framed Graphical Objects;” U.S. Provisional Patent Application Ser. No. 61/778,179, filed on Mar. 12, 2013, entitled “Device, Method, and Graphical User Interface for Scrolling Nested Regions;” U.S. Provisional Patent Application Ser. No. 61/778,171, filed on Mar. 12, 2013, entitled “Device, Method, and Graphical User Interface for Displaying Additional Information in Response to a User Contact;” U.S. Provisional Patent Application Ser. No. 61/778,191, filed on Mar. 12, 2013, entitled “Device, Method, and Graphical User Interface for Displaying User Interface Objects Corresponding to an Application;” U.S. Provisional Patent Application Ser. No. 61/778,211, filed on Mar. 12, 2013, entitled “Device, Method, and Graphical User Interface for Facilitating User Interaction with Controls in a User Interface;” U.S. Provisional Patent Application Ser. No. 61/778,239, filed on Mar. 12, 2013, entitled “Device, Method, and Graphical User Interface for Forgoing Generation of Tactile Output for a Multi-Contact Gesture;” U.S. Provisional Patent Application Ser. No. 61/778,284, filed on Mar. 12, 2013, entitled “Device, Method, and Graphical User Interface for Providing Tactile Feedback for Operations Performed in a User Interface;” U.S. Provisional Patent Application Ser. No. 61/778,363, filed on Mar. 12, 2013, entitled “Device, Method, and Graphical User Interface for Transitioning between Touch Input to Display Output Relationships;” U.S. Provisional Patent Application Ser. No. 61/778,367, filed on Mar. 12, 2013, entitled “Device,

Method, and Graphical User Interface for Moving a User Interface Object Based on an Intensity of a Press Input;” U.S. Provisional Patent Application Ser. No. 61/778,265, filed on Mar. 12, 2013, entitled “Device, Method, and Graphical User Interface for Transitioning between Display States in Response to a Gesture;” U.S. Provisional Patent Application Ser. No. 61/778,373, filed on Mar. 12, 2013, entitled “Device, Method, and Graphical User Interface for Managing Activation of a Control Based on Contact Intensity;” U.S. Provisional Patent Application Ser. No. 61/778,412, filed on Mar. 13, 2013, entitled “Device, Method, and Graphical User Interface for Displaying Content Associated with a Corresponding Affordance;” U.S. Provisional Patent Application Ser. No. 61/778,413, filed on Mar. 13, 2013, entitled “Device, Method, and Graphical User Interface for Selecting User Interface Objects;” U.S. Provisional Patent Application Ser. No. 61/778,414, filed on Mar. 13, 2013, entitled “Device, Method, and Graphical User Interface for Moving and Dropping a User Interface Object;” U.S. Provisional Patent Application Ser. No. 61/778,416, filed on Mar. 13, 2013, entitled “Device, Method, and Graphical User Interface for Determining Whether to Scroll or Select Content;” and U.S. Provisional Patent Application Ser. No. 61/778,418, filed on Mar. 13, 2013, entitled “Device, Method, and Graphical User Interface for Switching between User Interfaces,” which are incorporated herein by reference in their entireties.

This application is also related to the following: U.S. Provisional Patent Application Ser. No. 61/645,033, filed on May 9, 2012, entitled “Adaptive Haptic Feedback for Electronic Devices;” U.S. Provisional Patent Application Ser. No. 61/665,603, filed on Jun. 28, 2012, entitled “Adaptive Haptic Feedback for Electronic Devices;” and U.S. Provisional Patent Application Ser. No. 61/681,098, filed on Aug. 8, 2012, entitled “Adaptive Haptic Feedback for Electronic Devices,” which are incorporated herein by reference in their entireties.

TECHNICAL FIELD

This relates generally to electronic devices with touch-sensitive surfaces, including but not limited to electronic devices with touch-sensitive surfaces that detect inputs for manipulating user interfaces.

BACKGROUND

The use of touch-sensitive surfaces as input devices for computers and other electronic computing devices has increased significantly in recent years. Exemplary touch-sensitive surfaces include touch pads and touch screen displays. Such surfaces are widely used to manipulate user interface objects on a display.

Exemplary manipulations include adjusting the position and/or size of one or more user interface objects or activating buttons or opening files/applications represented by user interface objects, as well as associating metadata with one or more user interface objects or otherwise manipulating user interfaces. Exemplary user interface objects include digital images, video, text, icons, control elements such as buttons and other graphics. A user will, in some circumstances, need to perform such manipulations on user interface objects in a file management program (e.g., Finder from Apple Inc. of Cupertino, California), an image management application (e.g., Aperture or iPhoto from Apple Inc. of Cupertino, California), a digital content (e.g., videos and music) management application (e.g., iTunes from Apple Inc. of Cuper-

tino, California), a drawing application, a presentation application (e.g., Keynote from Apple Inc. of Cupertino, California), a word processing application (e.g., Pages from Apple Inc. of Cupertino, California), a website creation application (e.g., iWeb from Apple Inc. of Cupertino, California), a disk authoring application (e.g., iDVD from Apple Inc. of Cupertino, California), or a spreadsheet application (e.g., Numbers from Apple Inc. of Cupertino, California).

But existing methods for performing these manipulations are cumbersome and inefficient. In addition, existing methods take longer than necessary, thereby wasting energy. This latter consideration is particularly important in battery-operated devices.

### SUMMARY

Accordingly, there is a need for electronic devices with faster, more efficient methods and interfaces for manipulating user interfaces. Such methods and interfaces optionally complement or replace conventional methods for manipulating user interfaces. Such methods and interfaces reduce the cognitive burden on a user and produce a more efficient human-machine interface. For battery-operated devices, such methods and interfaces conserve power and increase the time between battery charges.

The above deficiencies and other problems associated with user interfaces for electronic devices with touch-sensitive surfaces are reduced or eliminated by the disclosed devices. In some embodiments, the device is a desktop computer. In some embodiments, the device is portable (e.g., a notebook computer, tablet computer, or handheld device). In some embodiments, the device has a touchpad. In some embodiments, the device has a touch-sensitive display (also known as a “touch screen” or “touch screen display”). In some embodiments, the device has a graphical user interface (GUI), one or more processors, memory and one or more modules, programs or sets of instructions stored in the memory for performing multiple functions. In some embodiments, the user interacts with the GUI primarily through finger contacts and gestures on the touch-sensitive surface. In some embodiments, the functions optionally include image editing, drawing, presenting, word processing, website creating, disk authoring, spreadsheet making, game playing, telephoning, video conferencing, e-mailing, instant messaging, workout support, digital photographing, digital videoing, web browsing, digital music playing, and/or digital video playing. Executable instructions for performing these functions are, optionally, included in a non-transitory computer readable storage medium or other computer program product configured for execution by one or more processors.

There is a need for electronic devices with faster, more efficient methods and interfaces for selecting a tactile output corresponding to a change in intensity of a contact when relocating user interface objects. Such methods and interfaces may complement or replace conventional methods for relocating user interface objects. Such methods and interfaces reduce the cognitive burden on a user and produce a more efficient human-machine interface. For battery-operated devices, such methods and interfaces conserve power and increase the time between battery charges.

The above deficiencies and other problems associated with user interfaces for electronic devices with touch-sensitive surfaces are reduced or eliminated by the disclosed devices. In some embodiments, the device is a desktop computer. In some embodiments, the device is portable (e.g., a notebook computer, tablet computer, or handheld device).

In some embodiments, the device has a touchpad. In some embodiments, the device has a touch-sensitive display (also known as a “touch screen” or “touch screen display”). In some embodiments, the device has a graphical user interface (GUI), one or more processors, memory and one or more modules, programs or sets of instructions stored in the memory for performing multiple functions. In some embodiments, the user interacts with the GUI primarily through finger contacts and gestures on the touch-sensitive surface. In some embodiments, the functions may include image editing, drawing, presenting, word processing, website creating, disk authoring, spreadsheet making, game playing, telephoning, video conferencing, e-mailing, instant messaging, workout support, digital photographing, digital videoing, web browsing, digital music playing, and/or digital video playing. Executable instructions for performing these functions may be included in a non-transitory computer readable storage medium or other computer program product configured for execution by one or more processors.

In accordance with some embodiments, a method is performed at an electronic device with a touch-sensitive surface and a display, where the device includes one or more sensors to detect intensity of contacts with the touch-sensitive surface. The method includes: displaying a user interface object on the display; detecting, on the touch-sensitive surface, a contact having an intensity above an object-selection threshold; detecting movement of the contact across the touch-sensitive surface, the movement corresponding to a preliminary portion of a gesture for performing an operation corresponding to the user interface object; detecting a reduction in intensity of the contact below an object-release threshold; and in response to detecting the reduction in intensity below the object-release threshold: in accordance with a determination that the movement meets predefined operation-performance criteria: performing the operation and generating a first tactile output on the touch-sensitive surface; and in accordance with a determination that the movement does not meet the predefined operation-performance criteria: forgoing performance of the operation and generating a second tactile output on the touch-sensitive surface, where the second tactile output is different from the first tactile output.

In accordance with some embodiments, an electronic device comprises a display unit configured to display a user interface object; a touch-sensitive surface unit configured to receive contacts; one or more sensor units configured to detect intensity of contacts with the touch-sensitive surface unit; and a processing unit coupled to the display unit, the touch-sensitive surface unit, and the sensor units. The processing unit is configured to: detect, on the touch-sensitive surface unit, a contact having an intensity above an object-selection threshold; detect movement of the contact across the touch-sensitive surface unit, the movement corresponding to a preliminary portion of a gesture for performing an operation corresponding to the user interface object; detect a reduction in intensity of the contact below an object-release threshold; and in response to detecting the reduction in intensity below the object-release threshold: in accordance with a determination that the movement meets predefined operation-performance criteria: perform the operation; and generate a first tactile output on the touch-sensitive surface unit; and in accordance with a determination that the movement does not meet the predefined operation-performance criteria: forgo performance of the operation; and generate a second tactile output on the touch-sensitive surface unit, wherein the second tactile output is different from the first tactile output.

5

Thus, electronic devices with displays, touch-sensitive surfaces, and one or more sensors to detect intensity of contacts with the touch-sensitive surfaces are provided with faster, more efficient methods and interfaces for selecting a tactile output corresponding to a change in intensity of a contact when relocating user interface objects, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces optionally complement or replace conventional methods for dragging and dropping user interface objects.

There is a need for electronic devices with faster, more efficient methods and interfaces for providing feedback corresponding to modifier inputs. Such methods and interfaces may complement or replace conventional methods for providing feedback corresponding to modifier inputs. Such methods and interfaces reduce the cognitive burden on a user and produce a more efficient human-machine interface. For battery-operated devices, such methods and interfaces conserve power and increase the time between battery charges.

In accordance with some embodiments, a method is performed at an electronic device with a display, a touch-sensitive surface and one or more sensors to detect intensity of contacts with the touch-sensitive surface. The method includes: detecting a contact on the touch-sensitive surface; detecting an increase in intensity of the contact above a first activation threshold; after detecting the increase in intensity of the contact above the first activation threshold, detecting a reduction in intensity of the contact below a second activation threshold; and in response to detecting the reduction in intensity of the contact below the second activation threshold: in accordance with a determination that a modifier input was detected while detecting the increase in intensity of the contact above the first activation threshold: performing a first operation and generating a first tactile output on the touch-sensitive surface; and in accordance with a determination that the modifier input was not detected while detecting the increase in intensity of the contact above the first activation threshold: performing a second operation different from the first operation and generating a second tactile output on the touch-sensitive surface, where the second tactile output is different from the first tactile output.

In accordance with some embodiments, an electronic device includes a display unit; a touch-sensitive surface unit configured to receive contacts; one or more sensor units configured to detect intensity of contacts with the touch-sensitive surface unit; and a processing unit coupled to the display unit, the touch-sensitive surface unit and the sensor units. The processing unit is configured to: detect a contact on the touch-sensitive surface unit; detect an increase in intensity of the contact above a first activation threshold; after detecting the increase in intensity of the contact above the first activation threshold, detect a reduction in intensity of the contact below a second activation threshold; and in response to detecting the reduction in intensity of the contact below the second activation threshold: in accordance with a determination that a modifier input was detected while detecting the increase in intensity of the contact above the first activation threshold: perform a first operation and generate a first tactile output on the touch-sensitive surface unit; and in accordance with a determination that the modifier input was not detected while detecting the increase in intensity of the contact above the first activation threshold: perform a second operation different from the first operation and generate a second tactile output on the touch-sensitive surface unit, where the second tactile output is different from the first tactile output.

6

Thus, electronic devices with displays, touch-sensitive surfaces and one or more sensors to detect intensity of contacts with the touch-sensitive surfaces are provided with faster, more efficient methods and interfaces for providing feedback corresponding to modifier inputs, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for providing feedback corresponding to modifier inputs.

There is a need for electronic devices with more efficient methods and interfaces for providing feedback for changing activation states of a user interface object. Such methods and interfaces may complement or replace conventional methods for providing feedback for changing activation states of a user interface object. Such methods and interfaces reduce the cognitive burden on a user and produce a more efficient human-machine interface. For battery-operated devices, such methods and interfaces conserve power and increase the time between battery charges.

In accordance with some embodiments, a method is performed at an electronic device with a display, a touch-sensitive surface and one or more sensors to detect intensity of contacts with the touch-sensitive surface. The method includes: displaying a user interface object on the display, where the user interface object has a plurality of activation states; detecting a contact on the touch-sensitive surface; detecting an increase of intensity of the contact on the touch-sensitive surface from a first intensity to a second intensity; in response to detecting the increase in intensity: changing activation states of the user interface object M times, where M is a positive integer, and generating a tactile output on the touch-sensitive surface corresponding to each change in activation state of the user interface object; detecting a decrease of intensity of the contact from the second intensity to the first intensity; and in response to detecting the decrease in intensity: changing activation states of the user interface object N times, where N is a positive integer, and generating a tactile output on the touch-sensitive surface corresponding to each change in activation state of the user interface object, where N is different from M.

In accordance with some embodiments, an electronic device includes a display unit configured to display a user interface object, where the user interface object has a plurality of activation states, a touch-sensitive surface unit configured to receive contacts, one or more sensor units configured to detect intensity of contacts with the touch-sensitive surface unit, and a processing unit coupled to the display unit, the touch-sensitive surface unit, and the sensor units. The processing unit is configured to: detect a contact on the touch-sensitive surface unit; detect an increase of intensity of the contact on the touch-sensitive surface unit from a first intensity to a second intensity; in response to detecting the increase in intensity: change activation states of the user interface object M times, where M is a positive integer, and generate a tactile output on the touch-sensitive surface unit corresponding to each change in activation state of the user interface object; detect a decrease of intensity of the contact from the second intensity to the first intensity; and in response to detecting the decrease in intensity: change activation states of the user interface object N times, where N is a positive integer, and generate a tactile output on the touch-sensitive surface unit corresponding to each change in activation state of the user interface object, where N is different from M.

Thus, electronic devices with displays, touch-sensitive surfaces and one or more sensors to detect intensity of

contacts with the touch-sensitive surface are provided with more efficient methods and interfaces for providing feedback for changing activation states of a user interface object, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for providing feedback for changing activation states of a user interface object.

There is a need for electronic devices with faster, more efficient methods and interfaces for providing feedback for changing activation states of a user interface object. Such methods and interfaces may complement or replace conventional methods for providing feedback for changing activation states of a user interface object. Such methods and interfaces reduce the cognitive burden on a user and produce a more efficient human-machine interface. For battery-operated devices, such methods and interfaces conserve power and increase the time between battery charges.

In accordance with some embodiments, a method is performed at an electronic device with a display, a touch-sensitive surface and one or more sensors to detect intensity of contacts with the touch-sensitive surface. The method includes: displaying a user interface object on the display, where the user interface object has a first activation state and a second activation state; detecting a contact on the touch-sensitive surface; detecting an increase of intensity of the contact on the touch-sensitive surface from a first intensity to a second intensity; in response to detecting the increase in intensity: changing activation states of the user interface object from the first activation state to the second activation state; and generating M distinct tactile outputs on the touch-sensitive surface, where M is a positive integer; detecting a decrease of intensity of the contact from the second intensity to the first intensity; and in response to detecting the decrease in intensity: changing activation states of the user interface object from the second activation state to the first activation state; and generating N distinct tactile outputs on the touch-sensitive surface, where N is a positive integer and N is different from M.

In accordance with some embodiments, an electronic device includes a display unit configured to display a user interface object, where the user interface object has a first activation state and a second activation state; a touch-sensitive surface unit configured to receive contacts; one or more sensor units configured to detect intensity of contacts with the touch-sensitive surface unit; and a processing unit coupled to the display unit, the touch-sensitive surface unit and the sensor units. The processing unit is configured to: detect a contact on the touch-sensitive surface unit; detect an increase of intensity of the contact on the touch-sensitive surface unit from a first intensity to a second intensity; in response to detecting the increase in intensity: change activation states of the user interface object from the first activation state to the second activation state; and generate M distinct tactile outputs on the touch-sensitive surface unit, where M is a positive integer; detect a decrease of intensity of the contact from the second intensity to the first intensity; and in response to detecting the decrease in intensity: change activation states of the user interface object from the second activation state to the first activation state; and generate N distinct tactile outputs on the touch-sensitive surface unit, where N is a positive integer and N is different from M.

Thus, electronic devices with displays, touch-sensitive surfaces and one or more sensors to detect intensity of contacts with the touch-sensitive surface are provided with faster, more efficient methods and interfaces for providing feedback for changing activation states of a user interface

object, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for providing feedback for changing activation states of a user interface object.

In accordance with some embodiments, an electronic device includes a display, a touch-sensitive surface, optionally one or more sensors to detect intensity of contacts with the touch-sensitive surface, one or more processors, memory, and one or more programs; the one or more programs are stored in the memory and configured to be executed by the one or more processors and the one or more programs include instructions for performing the operations of any of the methods referred to in the fifth paragraph of the Description of Embodiments. In accordance with some embodiments, a graphical user interface on an electronic device with a display, a touch-sensitive surface, optionally one or more sensors to detect intensity of contacts with the touch-sensitive surface, a memory, and one or more processors to execute one or more programs stored in the memory includes one or more of the elements displayed in any of the methods referred to in the fifth paragraph of the Description of Embodiments, which are updated in response to inputs, as described in any of the methods referred to in the fifth paragraph of the Description of Embodiments. In accordance with some embodiments, a computer readable storage medium has stored therein instructions which when executed by an electronic device with a display, a touch-sensitive surface, and optionally one or more sensors to detect intensity of contacts with the touch-sensitive surface, cause the device to perform the operations of any of the methods referred to in the fifth paragraph of the Description of Embodiments. In accordance with some embodiments, an electronic device includes: a display, a touch-sensitive surface, and optionally one or more sensors to detect intensity of contacts with the touch-sensitive surface; and means for performing the operations of any of the methods referred to in the fifth paragraph of the Description of Embodiments. In accordance with some embodiments, an information processing apparatus, for use in an electronic device with a display and a touch-sensitive surface, optionally one or more sensors to detect intensity of contacts with the touch-sensitive surface, includes means for performing the operations of any of the methods referred to in the fifth paragraph of the Description of Embodiments.

#### BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding of the various described embodiments, reference should be made to the Description of Embodiments below, in conjunction with the following drawings in which like reference numerals refer to corresponding parts throughout the figures.

FIG. 1A is a block diagram illustrating a portable multifunction device with a touch-sensitive display in accordance with some embodiments.

FIG. 1B is a block diagram illustrating exemplary components for event handling in accordance with some embodiments.

FIG. 2 illustrates a portable multifunction device having a touch screen in accordance with some embodiments.

FIG. 3 is a block diagram of an exemplary multifunction device with a display and a touch-sensitive surface in accordance with some embodiments.

FIG. 4A illustrates an exemplary user interface for a menu of applications on a portable multifunction device in accordance with some embodiments.

FIG. 4B illustrates an exemplary user interface for a multifunction device with a touch-sensitive surface that is separate from the display in accordance with some embodiments.

FIGS. 5A-5W illustrate exemplary user interfaces for selecting a tactile output corresponding to a change in intensity of a contact in accordance with some embodiments.

FIGS. 6A-6B are flow diagrams illustrating a method of selecting a tactile output corresponding to a change in intensity of a contact in accordance with some embodiments.

FIG. 7 is a functional block diagram of an electronic device in accordance with some embodiments.

FIGS. 8A-8V illustrate exemplary user interfaces for providing feedback corresponding to modifier inputs in accordance with some embodiments.

FIGS. 9A-9B are flow diagrams illustrating a method of providing feedback corresponding to modifier inputs in accordance with some embodiments.

FIG. 10 is a functional block diagram of an electronic device in accordance with some embodiments.

FIGS. 11A-11N illustrate exemplary user interfaces for providing feedback for changing activation states of a user interface object in accordance with some embodiments.

FIGS. 12A-12B are flow diagrams illustrating a method of providing feedback for changing activation states of a user interface object in accordance with some embodiments.

FIG. 13 is a functional block diagram of an electronic device in accordance with some embodiments.

FIGS. 14A-14N illustrate exemplary user interfaces for providing feedback for changing activation states of a user interface object in accordance with some embodiments.

FIGS. 15A-15C are flow diagrams illustrating a method of providing feedback for changing activation states of a user interface object in accordance with some embodiments.

FIG. 16 is a functional block diagram of an electronic device in accordance with some embodiments.

#### DESCRIPTION OF EMBODIMENTS

The methods, devices and GUIs described herein provide visual and/or haptic feedback that makes manipulation of user interface objects more efficient and intuitive for a user. For example, in a system where the clicking action of a trackpad is decoupled from the contact intensity (e.g., contact force, contact pressure, or a substitute therefore) that is needed to reach an activation threshold, the device can generate different tactile outputs (e.g., “different clicks”) for different activation events (e.g., so that clicks that accomplish a particular result are differentiated from clicks that do not produce any result or that accomplish a different result from the particular result). Additionally, tactile outputs can be generated in response to other events that are not related to increasing intensity of a contact, such as generating a tactile output (e.g., a “detent”) when a user interface object is moved to a particular position, boundary or orientation, or when an event occurs at the device.

Additionally, in a system where a trackpad or touch-screen display is sensitive to a range of contact intensity that includes more than one or two specific intensity values (e.g., more than a simple on/off, binary intensity determination), the user interface can provide responses (e.g., visual or tactile cues) that are indicative of the intensity of the contact within the range. In some implementations, a pre-activation-threshold response and/or a post-activation-threshold response to an input are displayed as continuous animations.

As one example of such a response, a preview of an operation is displayed in response to detecting an increase in contact intensity that is still below an activation threshold for performing the operation. As another example of such a response, an animation associated with an operation continues even after the activation threshold for the operation has been reached. Both of these examples provide a user with a continuous response to the force or pressure of a user’s contact, which provides a user with visual and/or haptic feedback that is richer and more intuitive. More specifically, such continuous force responses give the user the experience of being able to press lightly to preview an operation and/or press deeply to push “past” or “through” a predefined user interface state corresponding to the operation.

Additionally, for a device with a touch-sensitive surface that is sensitive to a range of contact intensity, multiple contact intensity thresholds can be monitored by the device and different functions can be mapped to different contact intensity thresholds. This serves to increase the available “gesture space” providing easy access to advanced features for users who know that increasing the intensity of a contact at or beyond a second “deep press” intensity threshold will cause the device to perform a different operation from an operation that would be performed if the intensity of the contact is between a first “activation” intensity threshold and the second “deep press” intensity threshold. An advantage of assigning additional functionality to a second “deep press” intensity threshold while maintaining familiar functionality at a first “activation” intensity threshold is that inexperienced users who are, in some circumstances, confused by the additional functionality can use the familiar functionality by just applying an intensity up to the first “activation” intensity threshold, whereas more experienced users can take advantage of the additional functionality by applying an intensity at the second “deep press” intensity threshold.

Additionally, for a device with a touch-sensitive surface that is sensitive to a range of contact intensity, the device can provide additional functionality by allowing users to perform complex operations with a single continuous contact. For example, when selecting a group of objects, a user can move a continuous contact around the touch-sensitive surface and can press while dragging (e.g., applying an intensity greater than a “deep press” intensity threshold) to add additional elements to a selection. In this way, a user can intuitively interact with a user interface where pressing harder with a contact causes objects in the user interface to be “stickier.”

A number of different approaches to providing an intuitive user interface on a device where a clicking action is decoupled from the force that is needed to reach an activation threshold and/or the device is sensitive to a wide range of contact intensities are described below. Using one or more of these approaches (optionally in conjunction with each other) helps to provide a user interface that intuitively provides users with additional information and functionality, thereby reducing the user’s cognitive burden and improving the human-machine interface. Such improvements in the human-machine interface enable users to use the device faster and more efficiently. For battery-operated devices, these improvements conserve power and increase the time between battery charges. For ease of explanation, systems, methods and user interfaces for including illustrative examples of some of these approaches are described below, as follows:

Many electronic devices have graphical user interfaces including one or more user interface objects. When users attempt to perform operations associated with

## 11

these user interface objects, these operations are sometimes successful and sometimes unsuccessful. For example, in some circumstances, moving a user interface object to a disallowed portion of the user interface will be unsuccessful, whereas moving the same user interface object to an allowed portion of the user interface will be successful. One approach to indicating whether an operation was successful or unsuccessful is providing visual feedback indicative of the successful performance of an operation. However, visual feedback can easily be missed by a user, thereby leaving the user confused as to whether or not the operation has been performed. The embodiments described below improve on these methods by providing additional cues to the user, including tactile outputs, to indicate whether or not an operation was successful, thereby providing a more convenient and efficient user interface. In particular, FIGS. 5A-5W illustrate exemplary user interfaces for relocating a user interface object in accordance with some embodiments. FIGS. 6A-6B are flow diagrams illustrating a method of selecting a tactile output corresponding to a change in intensity of a contact in accordance with some embodiments. The user interfaces in FIGS. 5A-5W are used to illustrate the processes described below, including the processes in FIGS. 6A-6B.

Many electronic devices include a mouse or similar input device that provides left-click functionality and right-click functionality for activating different operations. As devices economize on the number of buttons and input devices, the left-click functionality and right-click functionality is, optionally, invoked using one input device, such as a trackpad. In some methods, when either functionality is invoked using the one input device, the user is not given sufficient feedback indicating whether the activated operation was an operation not associated with a modifier input (e.g., a left-click operation) or an operation associated with a modifier input (e.g., a right-click operation). The embodiments below improve on these methods by providing different tactile output when device detects an input while a modifier input is detected than when the device detects a similar input while a modifier input is not detected, thereby providing a more convenient and efficient user interface. In particular, FIGS. 8A-8V illustrate exemplary user interfaces for providing feedback corresponding to modifier inputs. FIGS. 9A-9B are flow diagrams illustrating a method of providing feedback corresponding to modifier inputs. The user interfaces in FIGS. 8A-8V are used to illustrate the processes in FIGS. 9A-9B.

Many electronic devices have graphical user interfaces that include user interface objects, such as virtual buttons and switches. In some circumstances, a user activates a user interface object to perform an operation or adjust a parameter or property. One approach to indicating an activation state of a user interface object is to mimic the behavior of a corresponding physical object. However, physical objects, such as real buttons and switches, will, in some circumstances provide excessive tactile feedback in some circumstances, and too little feedback in others. The embodiments described below provide tactile feedback that corresponds to changes in activation states of a virtual button, switch or other user interface object rather than tactile feedback that corresponds 1:1 to tactile sensations that would be felt by a user when using a physical

## 12

control to perform similar operations, thereby providing a more convenient and intuitive user interface. In particular, FIGS. 11A-11N illustrate exemplary user interfaces for providing feedback for changing activation states of a user interface object. FIGS. 12A-12B are flow diagrams illustrating a method of providing feedback for changing activation states of a user interface object. The user interfaces in FIGS. 11A-11N are used to illustrate the processes in FIGS. 12A-12B.

Many electronic devices have graphical user interfaces that include user interface objects, such as buttons and switches. In some circumstances, a user activates a user interface object to perform an operation or adjust a parameter or property. One approach to indicating an activation state of a user interface object is to mimic the behavior of a corresponding physical object. However, physical objects, such as real buttons and switches, will, in some circumstances provide excessive tactile feedback in some circumstances, and too little feedback in others. In some devices, a tactile sensation is, in some circumstances, perceived by the user for corresponding physical inputs, such as clicks of a physical actuator mechanism (e.g., a mouse button) that activate a switch. The embodiments described below provide tactile feedback that is not tied to actuations of a physical actuator mechanism. For example, tactile sensations related to activation state changes are, optionally, provided. When tactile sensations not tied to physical actuations are provided for, the user can better discern the activation state of the virtual button without being distracted by too much or too little tactile feedback, thereby providing a more convenient and intuitive user interface. Below, FIGS. 14A-14N illustrate exemplary user interfaces for providing feedback for changing activation states of a user interface object. FIGS. 15A-15C are flow diagrams illustrating a method of providing feedback for changing activation states of a user interface object. The user interfaces in FIGS. 14A-14N are used to illustrate the processes in FIGS. 15A-15C.

## Exemplary Devices

Reference will now be made in detail to embodiments, examples of which are illustrated in the accompanying drawings. In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of the various described embodiments. However, it will be apparent to one of ordinary skill in the art that the various described embodiments may be practiced without these specific details. In other instances, well-known methods, procedures, components, circuits, and networks have not been described in detail so as not to unnecessarily obscure aspects of the embodiments.

It will also be understood that, although the terms first, second, etc. are, in some instances, used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. For example, a first contact could be termed a second contact, and, similarly, a second contact could be termed a first contact, without departing from the scope of the various described embodiments. The first contact and the second contact are both contacts, but they are not the same contact.

The terminology used in the description of the various described embodiments herein is for the purpose of describing particular embodiments only and is not intended to be limiting. As used in the description of the various described embodiments and the appended claims, the singular forms

“a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will also be understood that the term “and/or” as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will be further understood that the terms “includes,” “including,” “comprises,” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

As used herein, the term “if” is, optionally, construed to mean “when” or “upon” or “in response to determining” or “in response to detecting,” depending on the context. Similarly, the phrase “if it is determined” or “if [a stated condition or event] is detected” is, optionally, construed to mean “upon determining” or “in response to determining” or “upon detecting [the stated condition or event]” or “in response to detecting [the stated condition or event],” depending on the context.

Embodiments of electronic devices, user interfaces for such devices, and associated processes for using such devices are described. In some embodiments, the device is a portable communications device, such as a mobile telephone, that also contains other functions, such as PDA and/or music player functions. Exemplary embodiments of portable multifunction devices include, without limitation, the iPhone®, iPod Touch®, and iPad® devices from Apple Inc. of Cupertino, California Other portable electronic devices, such as laptops or tablet computers with touch-sensitive surfaces (e.g., touch screen displays and/or touch pads), are, optionally, used. It should also be understood that, in some embodiments, the device is not a portable communications device, but is a desktop computer with a touch-sensitive surface (e.g., a touch screen display and/or a touch pad).

In the discussion that follows, an electronic device that includes a display and a touch-sensitive surface is described. It should be understood, however, that the electronic device optionally includes one or more other physical user-interface devices, such as a physical keyboard, a mouse and/or a joystick.

The device typically supports a variety of applications, such as one or more of the following: a drawing application, a presentation application, a word processing application, a website creation application, a disk authoring application, a spreadsheet application, a gaming application, a telephone application, a video conferencing application, an e-mail application, an instant messaging application, a workout support application, a photo management application, a digital camera application, a digital video camera application, a web browsing application, a digital music player application, and/or a digital video player application.

The various applications that are executed on the device optionally use at least one common physical user-interface device, such as the touch-sensitive surface. One or more functions of the touch-sensitive surface as well as corresponding information displayed on the device are, optionally, adjusted and/or varied from one application to the next and/or within a respective application. In this way, a common physical architecture (such as the touch-sensitive surface) of the device optionally supports the variety of applications with user interfaces that are intuitive and transparent to the user.

Attention is now directed toward embodiments of portable devices with touch-sensitive displays. FIG. 1A is a

block diagram illustrating portable multifunction device 100 with touch-sensitive displays 112 in accordance with some embodiments. Touch-sensitive display 112 is sometimes called a “touch screen” for convenience, and is sometimes known as or called a touch-sensitive display system. Device 100 includes memory 102 (which optionally includes one or more computer readable storage mediums), memory controller 122, one or more processing units (CPU’s) 120, peripherals interface 118, RF circuitry 108, audio circuitry 110, speaker 111, microphone 113, input/output (I/O) subsystem 106, other input or control devices 116, and external port 124. Device 100 optionally includes one or more optical sensors 164. Device 100 optionally includes one or more intensity sensors 165 for detecting intensity of contacts on device 100 (e.g., a touch-sensitive surface such as touch-sensitive display system 112 of device 100). Device 100 optionally includes one or more tactile output generators 167 for generating tactile outputs on device 100 (e.g., generating tactile outputs on a touch-sensitive surface such as touch-sensitive display system 112 of device 100 or touchpad 355 of device 300). These components optionally communicate over one or more communication buses or signal lines 103.

As used in the specification and claims, the term “intensity” of a contact on a touch-sensitive surface refers to the force or pressure (force per unit area) of a contact (e.g., a finger contact) on the touch sensitive surface, or to a substitute (proxy) for the force or pressure of a contact on the touch sensitive surface. The intensity of a contact has a range of values that includes at least four distinct values and more typically includes hundreds of distinct values (e.g., at least 256). Intensity of a contact is, optionally, determined (or measured) using various approaches and various sensors or combinations of sensors. For example, one or more force sensors underneath or adjacent to the touch-sensitive surface are, optionally, used to measure force at various points on the touch-sensitive surface. In some implementations, force measurements from multiple force sensors are combined (e.g., a weighted average) to determine an estimated force of a contact. Similarly, a pressure-sensitive tip of a stylus is, optionally, used to determine a pressure of the stylus on the touch-sensitive surface. Alternatively, the size of the contact area detected on the touch-sensitive surface and/or changes thereto, the capacitance of the touch-sensitive surface proximate to the contact and/or changes thereto, and/or the resistance of the touch-sensitive surface proximate to the contact and/or changes thereto are, optionally, used as a substitute for the force or pressure of the contact on the touch-sensitive surface. In some implementations, the substitute measurements for contact force or pressure are used directly to determine whether an intensity threshold has been exceeded (e.g., the intensity threshold is described in units corresponding to the substitute measurements). In some implementations, the substitute measurements for contact force or pressure are converted to an estimated force or pressure and the estimated force or pressure is used to determine whether an intensity threshold has been exceeded (e.g., the intensity threshold is a pressure threshold measured in units of pressure).

As used in the specification and claims, the term “tactile output” refers to physical displacement of a device relative to a previous position of the device, physical displacement of a component (e.g., a touch-sensitive surface) of a device relative to another component (e.g., housing) of the device, or displacement of the component relative to a center of mass of the device that will be detected by a user with the user’s sense of touch. For example, in situations where the device or the component of the device is in contact with a

surface of a user that is sensitive to touch (e.g., a finger, palm, or other part of a user's hand), the tactile output generated by the physical displacement will be interpreted by the user as a tactile sensation corresponding to a perceived change in physical characteristics of the device or the component of the device. For example, movement of a touch-sensitive surface (e.g., a touch-sensitive display or trackpad) is, optionally, interpreted by the user as a "down click" or "up click" of a physical actuator button. In some cases, a user will feel a tactile sensation such as an "down click" or "up click" even when there is no movement of a physical actuator button associated with the touch-sensitive surface that is physically pressed (e.g., displaced) by the user's movements. As another example, movement of the touch-sensitive surface is, optionally, interpreted or sensed by the user as "roughness" of the touch-sensitive surface, even when there is no change in smoothness of the touch-sensitive surface. While such interpretations of touch by a user will be subject to the individualized sensory perceptions of the user, there are many sensory perceptions of touch that are common to a large majority of users. Thus, when a tactile output is described as corresponding to a particular sensory perception of a user (e.g., an "up click," a "down click," "roughness"), unless otherwise stated, the generated tactile output corresponds to physical displacement of the device or a component thereof that will generate the described sensory perception for a typical (or average) user.

It should be appreciated that device **100** is only one example of a portable multifunction device, and that device **100** optionally has more or fewer components than shown, optionally combines two or more components, or optionally has a different configuration or arrangement of the components. The various components shown in FIG. **1A** are implemented in hardware, software, or a combination of both hardware and software, including one or more signal processing and/or application specific integrated circuits.

Memory **102** optionally includes high-speed random access memory and optionally also includes non-volatile memory, such as one or more magnetic disk storage devices, flash memory devices, or other non-volatile solid-state memory devices. Access to memory **102** by other components of device **100**, such as CPU **120** and the peripherals interface **118**, is, optionally, controlled by memory controller **122**.

Peripherals interface **118** can be used to couple input and output peripherals of the device to CPU **120** and memory **102**. The one or more processors **120** run or execute various software programs and/or sets of instructions stored in memory **102** to perform various functions for device **100** and to process data.

In some embodiments, peripherals interface **118**, CPU **120**, and memory controller **122** are, optionally, implemented on a single chip, such as chip **104**. In some other embodiments, they are, optionally, implemented on separate chips.

RF (radio frequency) circuitry **108** receives and sends RF signals, also called electromagnetic signals. RF circuitry **108** converts electrical signals to/from electromagnetic signals and communicates with communications networks and other communications devices via the electromagnetic signals. RF circuitry **108** optionally includes well-known circuitry for performing these functions, including but not limited to an antenna system, an RF transceiver, one or more amplifiers, a tuner, one or more oscillators, a digital signal processor, a CODEC chipset, a subscriber identity module (SIM) card, memory, and so forth. RF circuitry **108** optionally communicates with networks, such as the Internet, also referred to

as the World Wide Web (WWW), an intranet and/or a wireless network, such as a cellular telephone network, a wireless local area network (LAN) and/or a metropolitan area network (MAN), and other devices by wireless communication. The wireless communication optionally uses any of a plurality of communications standards, protocols and technologies, including but not limited to Global System for Mobile Communications (GSM), Enhanced Data GSM Environment (EDGE), high-speed downlink packet access (HSDPA), high-speed uplink packet access (HSUPA), Evolution, Data-Only (EV-DO), HSPA, HSPA+, Dual-Cell HSPA (DC-HSPA), long term evolution (LTE), near field communication (NFC), wideband code division multiple access (W-CDMA), code division multiple access (CDMA), time division multiple access (TDMA), Bluetooth, Wireless Fidelity (Wi-Fi) (e.g., IEEE 802.11a, IEEE 802.11b, IEEE 802.11g and/or IEEE 802.11n), voice over Internet Protocol (VoIP), Wi-MAX, a protocol for e-mail (e.g., Internet message access protocol (IMAP) and/or post office protocol (POP)), instant messaging (e.g., extensible messaging and presence protocol (XMPP), Session Initiation Protocol for Instant Messaging and Presence Leveraging Extensions (SIMPLE), Instant Messaging and Presence Service (IMPS)), and/or Short Message Service (SMS), or any other suitable communication protocol, including communication protocols not yet developed as of the filing date of this document.

Audio circuitry **110**, speaker **111**, and microphone **113** provide an audio interface between a user and device **100**. Audio circuitry **110** receives audio data from peripherals interface **118**, converts the audio data to an electrical signal, and transmits the electrical signal to speaker **111**. Speaker **111** converts the electrical signal to human-audible sound waves. Audio circuitry **110** also receives electrical signals converted by microphone **113** from sound waves. Audio circuitry **110** converts the electrical signal to audio data and transmits the audio data to peripherals interface **118** for processing. Audio data is, optionally, retrieved from and/or transmitted to memory **102** and/or RF circuitry **108** by peripherals interface **118**. In some embodiments, audio circuitry **110** also includes a headset jack (e.g., **212**, FIG. **2**). The headset jack provides an interface between audio circuitry **110** and removable audio input/output peripherals, such as output-only headphones or a headset with both output (e.g., a headphone for one or both ears) and input (e.g., a microphone).

I/O subsystem **106** couples input/output peripherals on device **100**, such as touch screen **112** and other input control devices **116**, to peripherals interface **118**. I/O subsystem **106** optionally includes display controller **156**, optical sensor controller **158**, intensity sensor controller **159**, haptic feedback controller **161** and one or more input controllers **160** for other input or control devices. The one or more input controllers **160** receive/send electrical signals from/to other input or control devices **116**. The other input control devices **116** optionally include physical buttons (e.g., push buttons, rocker buttons, etc.), dials, slider switches, joysticks, click wheels, and so forth. In some alternate embodiments, input controller(s) **160** are, optionally, coupled to any (or none) of the following: a keyboard, infrared port, USB port, and a pointer device such as a mouse. The one or more buttons (e.g., **208**, FIG. **2**) optionally include an up/down button for volume control of speaker **111** and/or microphone **113**. The one or more buttons optionally include a push button (e.g., **206**, FIG. **2**).

Touch-sensitive display **112** provides an input interface and an output interface between the device and a user.

Display controller **156** receives and/or sends electrical signals from/to touch screen **112**. Touch screen **112** displays visual output to the user. The visual output optionally includes graphics, text, icons, video, and any combination thereof (collectively termed “graphics”). In some embodiments, some or all of the visual output corresponds to user-interface objects.

Touch screen **112** has a touch-sensitive surface, sensor or set of sensors that accepts input from the user based on haptic and/or tactile contact. Touch screen **112** and display controller **156** (along with any associated modules and/or sets of instructions in memory **102**) detect contact (and any movement or breaking of the contact) on touch screen **112** and converts the detected contact into interaction with user-interface objects (e.g., one or more soft keys, icons, web pages or images) that are displayed on touch screen **112**. In an exemplary embodiment, a point of contact between touch screen **112** and the user corresponds to a finger of the user.

Touch screen **112** optionally uses LCD (liquid crystal display) technology, LPD (light emitting polymer display) technology, or LED (light emitting diode) technology, although other display technologies are used in other embodiments. Touch screen **112** and display controller **156** optionally detect contact and any movement or breaking thereof using any of a plurality of touch sensing technologies now known or later developed, including but not limited to capacitive, resistive, infrared, and surface acoustic wave technologies, as well as other proximity sensor arrays or other elements for determining one or more points of contact with touch screen **112**. In an exemplary embodiment, projected mutual capacitance sensing technology is used, such as that found in the iPhone®, iPod Touch®, and iPad® from Apple Inc. of Cupertino, California.

Touch screen **112** optionally has a video resolution in excess of 100 dpi. In some embodiments, the touch screen has a video resolution of approximately 160 dpi. The user optionally makes contact with touch screen **112** using any suitable object or appendage, such as a stylus, a finger, and so forth. In some embodiments, the user interface is designed to work primarily with finger-based contacts and gestures, which can be less precise than stylus-based input due to the larger area of contact of a finger on the touch screen. In some embodiments, the device translates the rough finger-based input into a precise pointer/cursor position or command for performing the actions desired by the user.

In some embodiments, in addition to the touch screen, device **100** optionally includes a touchpad (not shown) for activating or deactivating particular functions. In some embodiments, the touchpad is a touch-sensitive area of the device that, unlike the touch screen, does not display visual output. The touchpad is, optionally, a touch-sensitive surface that is separate from touch screen **112** or an extension of the touch-sensitive surface formed by the touch screen.

Device **100** also includes power system **162** for powering the various components. Power system **162** optionally includes a power management system, one or more power sources (e.g., battery, alternating current (AC)), a recharging system, a power failure detection circuit, a power converter or inverter, a power status indicator (e.g., a light-emitting diode (LED)) and any other components associated with the generation, management and distribution of power in portable devices.

Device **100** optionally also includes one or more optical sensors **164**. FIG. 1A shows an optical sensor coupled to optical sensor controller **158** in I/O subsystem **106**. Optical

sensor **164** optionally includes charge-coupled device (CCD) or complementary metal-oxide semiconductor (CMOS) phototransistors. Optical sensor **164** receives light from the environment, projected through one or more lens, and converts the light to data representing an image. In conjunction with imaging module **143** (also called a camera module), optical sensor **164** optionally captures still images or video. In some embodiments, an optical sensor is located on the back of device **100**, opposite touch screen display **112** on the front of the device, so that the touch screen display is enabled for use as a viewfinder for still and/or video image acquisition. In some embodiments, another optical sensor is located on the front of the device so that the user’s image is, optionally, obtained for videoconferencing while the user views the other video conference participants on the touch screen display.

Device **100** optionally also includes one or more contact intensity sensors **165**. FIG. 1A shows a contact intensity sensor coupled to intensity sensor controller **159** in I/O subsystem **106**. Contact intensity sensor **165** optionally includes one or more piezoresistive strain gauges, capacitive force sensors, electric force sensors, piezoelectric force sensors, optical force sensors, capacitive touch-sensitive surfaces, or other intensity sensors (e.g., sensors used to measure the force (or pressure) of a contact on a touch-sensitive surface). Contact intensity sensor **165** receives contact intensity information (e.g., pressure information or a proxy for pressure information) from the environment. In some embodiments, at least one contact intensity sensor is collocated with, or proximate to, a touch-sensitive surface (e.g., touch-sensitive display system **112**). In some embodiments, at least one contact intensity sensor is located on the back of device **100**, opposite touch screen display **112** which is located on the front of device **100**.

Device **100** optionally also includes one or more proximity sensors **166**. FIG. 1A shows proximity sensor **166** coupled to peripherals interface **118**. Alternately, proximity sensor **166** is coupled to input controller **160** in I/O subsystem **106**. In some embodiments, the proximity sensor turns off and disables touch screen **112** when the multifunction device is placed near the user’s ear (e.g., when the user is making a phone call).

Device **100** optionally also includes one or more tactile output generators **167**. FIG. 1A shows a tactile output generator coupled to haptic feedback controller **161** in I/O subsystem **106**. Tactile output generator **167** optionally includes one or more electroacoustic devices such as speakers or other audio components and/or electromechanical devices that convert energy into linear motion such as a motor, solenoid, electroactive polymer, piezoelectric actuator, electrostatic actuator, or other tactile output generating component (e.g., a component that converts electrical signals into tactile outputs on the device). Contact intensity sensor **165** receives tactile feedback generation instructions from haptic feedback module **133** and generates tactile outputs on device **100** that are capable of being sensed by a user of device **100**. In some embodiments, at least one tactile output generator is collocated with, or proximate to, a touch-sensitive surface (e.g., touch-sensitive display system **112**) and, optionally, generates a tactile output by moving the touch-sensitive surface vertically (e.g., in/out of a surface of device **100**) or laterally (e.g., back and forth in the same plane as a surface of device **100**). In some embodiments, at least one tactile output generator sensor is located on the back of device **100**, opposite touch screen display **112** which is located on the front of device **100**.

Device **100** optionally also includes one or more accelerometers **168**. FIG. 1A shows accelerometer **168** coupled to peripherals interface **118**. Alternately, accelerometer **168** is, optionally, coupled to an input controller **160** in I/O subsystem **106**. In some embodiments, information is displayed on the touch screen display in a portrait view or a landscape view based on an analysis of data received from the one or more accelerometers. Device **100** optionally includes, in addition to accelerometer(s) **168**, a magnetometer (not shown) and a GPS (or GLONASS or other global navigation system) receiver (not shown) for obtaining information concerning the location and orientation (e.g., portrait or landscape) of device **100**.

In some embodiments, the software components stored in memory **102** include operating system **126**, communication module (or set of instructions) **128**, contact/motion module (or set of instructions) **130**, graphics module (or set of instructions) **132**, text input module (or set of instructions) **134**, Global Positioning System (GPS) module (or set of instructions) **135**, and applications (or sets of instructions) **136**. Furthermore, in some embodiments memory **102** stores device/global internal state **157**, as shown in FIGS. 1A and 3. Device/global internal state **157** includes one or more of: active application state, indicating which applications, if any, are currently active; display state, indicating what applications, views or other information occupy various regions of touch screen display **112**; sensor state, including information obtained from the device's various sensors and input control devices **116**; and location information concerning the device's location and/or attitude.

Operating system **126** (e.g., Darwin, RTXC, LINUX, UNIX, OS X, WINDOWS, or an embedded operating system such as VxWorks) includes various software components and/or drivers for controlling and managing general system tasks (e.g., memory management, storage device control, power management, etc.) and facilitates communication between various hardware and software components.

Communication module **128** facilitates communication with other devices over one or more external ports **124** and also includes various software components for handling data received by RF circuitry **108** and/or external port **124**. External port **124** (e.g., Universal Serial Bus (USB), FIREWIRE, etc.) is adapted for coupling directly to other devices or indirectly over a network (e.g., the Internet, wireless LAN, etc.). In some embodiments, the external port is a multi-pin (e.g., 30-pin) connector that is the same as, or similar to and/or compatible with the 30-pin connector used on iPod (trademark of Apple Inc.) devices.

Contact/motion module **130** optionally detects contact with touch screen **112** (in conjunction with display controller **156**) and other touch sensitive devices (e.g., a touchpad or physical click wheel). Contact/motion module **130** includes various software components for performing various operations related to detection of contact, such as determining if contact has occurred (e.g., detecting a finger-down event), determining an intensity of the contact (e.g., the force or pressure of the contact or a substitute for the force or pressure of the contact) determining if there is movement of the contact and tracking the movement across the touch-sensitive surface (e.g., detecting one or more finger-dragging events), and determining if the contact has ceased (e.g., detecting a finger-up event or a break in contact). Contact/motion module **130** receives contact data from the touch-sensitive surface. Determining movement of the point of contact, which is represented by a series of contact data, optionally includes determining speed (magnitude), velocity (magnitude and direction), and/or an acceleration (a change

in magnitude and/or direction) of the point of contact. These operations are, optionally, applied to single contacts (e.g., one finger contacts) or to multiple simultaneous contacts (e.g., "multitouch"/multiple finger contacts). In some embodiments, contact/motion module **130** and display controller **156** detect contact on a touchpad.

In some embodiments, contact/motion module **130** uses a set of one or more intensity thresholds to determine whether an operation has been performed by a user (e.g., to determine whether a user has "clicked" on an icon). In some embodiments at least a subset of the intensity thresholds are determined in accordance with software parameters (e.g., the intensity thresholds are not determined by the activation thresholds of particular physical actuators and can be adjusted without changing the physical hardware of device **100**). For example, a mouse "click" threshold of a trackpad or touch screen display can be set to any of a large range of predefined thresholds values without changing the trackpad or touch screen display hardware. Additionally, in some implementations a user of the device is provided with software settings for adjusting one or more of the set of intensity thresholds (e.g., by adjusting individual intensity thresholds and/or by adjusting a plurality of intensity thresholds at once with a system-level click "intensity" parameter).

Contact/motion module **130** optionally detects a gesture input by a user. Different gestures on the touch-sensitive surface have different contact patterns and intensities. Thus, a gesture is, optionally, detected by detecting a particular contact pattern. For example, detecting a finger tap gesture includes detecting a finger-down event followed by detecting a finger-up (lift off) event at the same position (or substantially the same position) as the finger-down event (e.g., at the position of an icon). As another example, detecting a finger swipe gesture on the touch-sensitive surface includes detecting a finger-down event followed by detecting one or more finger-dragging events, and subsequently followed by detecting a finger-up (lift off) event.

Graphics module **132** includes various known software components for rendering and displaying graphics on touch screen **112** or other display, including components for changing the visual impact (e.g., brightness, transparency, saturation, contrast or other visual property) of graphics that are displayed. As used herein, the term "graphics" includes any object that can be displayed to a user, including without limitation text, web pages, icons (such as user-interface objects including soft keys), digital images, videos, animations and the like.

In some embodiments, graphics module **132** stores data representing graphics to be used. Each graphic is, optionally, assigned a corresponding code. Graphics module **132** receives, from applications etc., one or more codes specifying graphics to be displayed along with, if necessary, coordinate data and other graphic property data, and then generates screen image data to output to display controller **156**.

Haptic feedback module **133** includes various software components for generating instructions used by tactile output generator(s) **167** to produce tactile outputs at one or more locations on device **100** in response to user interactions with device **100**.

Text input module **134**, which is, optionally, a component of graphics module **132**, provides soft keyboards for entering text in various applications (e.g., contacts **137**, e-mail **140**, IM **141**, browser **147**, and any other application that needs text input).

GPS module **135** determines the location of the device and provides this information for use in various applications

## 21

(e.g., to telephone **138** for use in location-based dialing, to camera **143** as picture/video metadata, and to applications that provide location-based services such as weather widgets, local yellow page widgets, and map/navigation widgets).

Applications **136** optionally include the following modules (or sets of instructions), or a subset or superset thereof: contacts module **137** (sometimes called an address book or contact list);

telephone module **138**;

video conferencing module **139**;

e-mail client module **140**;

instant messaging (IM) module **141**;

workout support module **142**;

camera module **143** for still and/or video images;

image management module **144**;

browser module **147**;

calendar module **148**;

widget modules **149**, which optionally include one or more of: weather widget **149-1**, stocks widget **149-2**, calculator widget **149-3**, alarm clock widget **149-4**, dictionary widget **149-5**, and other widgets obtained by the user, as well as user-created widgets **149-6**;

widget creator module **150** for making user-created widgets **149-6**;

search module **151**;

video and music player module **152**, which is, optionally, made up of a video player module and a music player module;

notes module **153**;

map module **154**; and/or

online video module **155**.

Examples of other applications **136** that are, optionally, stored in memory **102** include other word processing applications, other image editing applications, drawing applications, presentation applications, JAVA-enabled applications, encryption, digital rights management, voice recognition, and voice replication.

In conjunction with touch screen **112**, display controller **156**, contact module **130**, graphics module **132**, and text input module **134**, contacts module **137** are, optionally, used to manage an address book or contact list (e.g., stored in application internal state **192** of contacts module **137** in memory **102** or memory **370**), including: adding name(s) to the address book; deleting name(s) from the address book; associating telephone number(s), e-mail address(es), physical address(es) or other information with a name; associating an image with a name; categorizing and sorting names; providing telephone numbers or e-mail addresses to initiate and/or facilitate communications by telephone **138**, video conference **139**, e-mail **140**, or IM **141**; and so forth.

In conjunction with RF circuitry **108**, audio circuitry **110**, speaker **111**, microphone **113**, touch screen **112**, display controller **156**, contact module **130**, graphics module **132**, and text input module **134**, telephone module **138** are, optionally, used to enter a sequence of characters corresponding to a telephone number, access one or more telephone numbers in address book **137**, modify a telephone number that has been entered, dial a respective telephone number, conduct a conversation and disconnect or hang up when the conversation is completed. As noted above, the wireless communication optionally uses any of a plurality of communications standards, protocols and technologies.

In conjunction with RF circuitry **108**, audio circuitry **110**, speaker **111**, microphone **113**, touch screen **112**, display controller **156**, optical sensor **164**, optical sensor controller **158**, contact module **130**, graphics module **132**, text input

## 22

module **134**, contact list **137**, and telephone module **138**, videoconferencing module **139** includes executable instructions to initiate, conduct, and terminate a video conference between a user and one or more other participants in accordance with user instructions.

In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact module **130**, graphics module **132**, and text input module **134**, e-mail client module **140** includes executable instructions to create, send, receive, and manage e-mail in response to user instructions. In conjunction with image management module **144**, e-mail client module **140** makes it very easy to create and send e-mails with still or video images taken with camera module **143**.

In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact module **130**, graphics module **132**, and text input module **134**, the instant messaging module **141** includes executable instructions to enter a sequence of characters corresponding to an instant message, to modify previously entered characters, to transmit a respective instant message (for example, using a Short Message Service (SMS) or Multimedia Message Service (MMS) protocol for telephony-based instant messages or using XMPP, SIMPLE, or IMPS for Internet-based instant messages), to receive instant messages and to view received instant messages. In some embodiments, transmitted and/or received instant messages optionally include graphics, photos, audio files, video files and/or other attachments as are supported in a MMS and/or an Enhanced Messaging Service (EMS). As used herein, "instant messaging" refers to both telephony-based messages (e.g., messages sent using SMS or MMS) and Internet-based messages (e.g., messages sent using XMPP, SIMPLE, or IMPS).

In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact module **130**, graphics module **132**, text input module **134**, GPS module **135**, map module **154**, and music player module **146**, workout support module **142** includes executable instructions to create workouts (e.g., with time, distance, and/or calorie burning goals); communicate with workout sensors (sports devices); receive workout sensor data; calibrate sensors used to monitor a workout; select and play music for a workout; and display, store and transmit workout data.

In conjunction with touch screen **112**, display controller **156**, optical sensor(s) **164**, optical sensor controller **158**, contact module **130**, graphics module **132**, and image management module **144**, camera module **143** includes executable instructions to capture still images or video (including a video stream) and store them into memory **102**, modify characteristics of a still image or video, or delete a still image or video from memory **102**.

In conjunction with touch screen **112**, display controller **156**, contact module **130**, graphics module **132**, text input module **134**, and camera module **143**, image management module **144** includes executable instructions to arrange, modify (e.g., edit), or otherwise manipulate, label, delete, present (e.g., in a digital slide show or album), and store still and/or video images.

In conjunction with RF circuitry **108**, touch screen **112**, display system controller **156**, contact module **130**, graphics module **132**, and text input module **134**, browser module **147** includes executable instructions to browse the Internet in accordance with user instructions, including searching, linking to, receiving, and displaying web pages or portions thereof, as well as attachments and other files linked to web pages.

In conjunction with RF circuitry **108**, touch screen **112**, display system controller **156**, contact module **130**, graphics

module **132**, text input module **134**, e-mail client module **140**, and browser module **147**, calendar module **148** includes executable instructions to create, display, modify, and store calendars and data associated with calendars (e.g., calendar entries, to do lists, etc.) in accordance with user instructions.

In conjunction with RF circuitry **108**, touch screen **112**, display system controller **156**, contact module **130**, graphics module **132**, text input module **134**, and browser module **147**, widget modules **149** are mini-applications that are, optionally, downloaded and used by a user (e.g., weather widget **149-1**, stocks widget **149-2**, calculator widget **149-3**, alarm clock widget **149-4**, and dictionary widget **149-5**) or created by the user (e.g., user-created widget **149-6**). In some embodiments, a widget includes an HTML (Hypertext Markup Language) file, a CSS (Cascading Style Sheets) file, and a JavaScript file. In some embodiments, a widget includes an XML (Extensible Markup Language) file and a JavaScript file (e.g., Yahoo! Widgets).

In conjunction with RF circuitry **108**, touch screen **112**, display system controller **156**, contact module **130**, graphics module **132**, text input module **134**, and browser module **147**, the widget creator module **150** are, optionally, used by a user to create widgets (e.g., turning a user-specified portion of a web page into a widget).

In conjunction with touch screen **112**, display system controller **156**, contact module **130**, graphics module **132**, and text input module **134**, search module **151** includes executable instructions to search for text, music, sound, image, video, and/or other files in memory **102** that match one or more search criteria (e.g., one or more user-specified search terms) in accordance with user instructions.

In conjunction with touch screen **112**, display system controller **156**, contact module **130**, graphics module **132**, audio circuitry **110**, speaker **111**, RF circuitry **108**, and browser module **147**, video and music player module **152** includes executable instructions that allow the user to download and play back recorded music and other sound files stored in one or more file formats, such as MP3 or AAC files, and executable instructions to display, present or otherwise play back videos (e.g., on touch screen **112** or on an external, connected display via external port **124**). In some embodiments, device **100** optionally includes the functionality of an MP3 player, such as an iPod (trademark of Apple Inc.).

In conjunction with touch screen **112**, display controller **156**, contact module **130**, graphics module **132**, and text input module **134**, notes module **153** includes executable instructions to create and manage notes, to do lists, and the like in accordance with user instructions.

In conjunction with RF circuitry **108**, touch screen **112**, display system controller **156**, contact module **130**, graphics module **132**, text input module **134**, GPS module **135**, and browser module **147**, map module **154** are, optionally, used to receive, display, modify, and store maps and data associated with maps (e.g., driving directions; data on stores and other points of interest at or near a particular location; and other location-based data) in accordance with user instructions.

In conjunction with touch screen **112**, display system controller **156**, contact module **130**, graphics module **132**, audio circuitry **110**, speaker **111**, RF circuitry **108**, text input module **134**, e-mail client module **140**, and browser module **147**, online video module **155** includes instructions that allow the user to access, browse, receive (e.g., by streaming and/or download), play back (e.g., on the touch screen or on an external, connected display via external port **124**), send an e-mail with a link to a particular online video, and otherwise manage online videos in one or more file formats,

such as H.264. In some embodiments, instant messaging module **141**, rather than e-mail client module **140**, is used to send a link to a particular online video.

Each of the above identified modules and applications correspond to a set of executable instructions for performing one or more functions described above and the methods described in this application (e.g., the computer-implemented methods and other information processing methods described herein). These modules (i.e., sets of instructions) need not be implemented as separate software programs, procedures or modules, and thus various subsets of these modules are, optionally, combined or otherwise re-arranged in various embodiments. In some embodiments, memory **102** optionally stores a subset of the modules and data structures identified above. Furthermore, memory **102** optionally stores additional modules and data structures not described above.

In some embodiments, device **100** is a device where operation of a predefined set of functions on the device is performed exclusively through a touch screen and/or a touchpad. By using a touch screen and/or a touchpad as the primary input control device for operation of device **100**, the number of physical input control devices (such as push buttons, dials, and the like) on device **100** is, optionally, reduced.

The predefined set of functions that are performed exclusively through a touch screen and/or a touchpad optionally include navigation between user interfaces. In some embodiments, the touchpad, when touched by the user, navigates device **100** to a main, home, or root menu from any user interface that is displayed on device **100**. In such embodiments, a "menu button" is implemented using a touchpad. In some other embodiments, the menu button is a physical push button or other physical input control device instead of a touchpad.

FIG. 1B is a block diagram illustrating exemplary components for event handling in accordance with some embodiments. In some embodiments, memory **102** (in FIG. 1A) or **370** (FIG. 3) includes event sorter **170** (e.g., in operating system **126**) and a respective application **136-1** (e.g., any of the aforementioned applications **137-151**, **155**, **380-390**).

Event sorter **170** receives event information and determines the application **136-1** and application view **191** of application **136-1** to which to deliver the event information. Event sorter **170** includes event monitor **171** and event dispatcher module **174**. In some embodiments, application **136-1** includes application internal state **192**, which indicates the current application view(s) displayed on touch sensitive display **112** when the application is active or executing. In some embodiments, device/global internal state **157** is used by event sorter **170** to determine which application(s) is (are) currently active, and application internal state **192** is used by event sorter **170** to determine application views **191** to which to deliver event information.

In some embodiments, application internal state **192** includes additional information, such as one or more of: resume information to be used when application **136-1** resumes execution, user interface state information that indicates information being displayed or that is ready for display by application **136-1**, a state queue for enabling the user to go back to a prior state or view of application **136-1**, and a redo/undo queue of previous actions taken by the user.

Event monitor **171** receives event information from peripherals interface **118**. Event information includes information about a sub-event (e.g., a user touch on touch-sensitive display **112**, as part of a multi-touch gesture).

Peripherals interface **118** transmits information it receives from I/O subsystem **106** or a sensor, such as proximity sensor **166**, accelerometer(s) **168**, and/or microphone **113** (through audio circuitry **110**). Information that peripherals interface **118** receives from I/O subsystem **106** includes information from touch-sensitive display **112** or a touch-sensitive surface.

In some embodiments, event monitor **171** sends requests to the peripherals interface **118** at predetermined intervals. In response, peripherals interface **118** transmits event information. In other embodiments, peripheral interface **118** transmits event information only when there is a significant event (e.g., receiving an input above a predetermined noise threshold and/or for more than a predetermined duration).

In some embodiments, event sorter **170** also includes a hit view determination module **172** and/or an active event recognizer determination module **173**.

Hit view determination module **172** provides software procedures for determining where a sub-event has taken place within one or more views, when touch sensitive display **112** displays more than one view. Views are made up of controls and other elements that a user can see on the display.

Another aspect of the user interface associated with an application is a set of views, sometimes herein called application views or user interface windows, in which information is displayed and touch-based gestures occur. The application views (of a respective application) in which a touch is detected optionally correspond to programmatic levels within a programmatic or view hierarchy of the application. For example, the lowest level view in which a touch is detected is, optionally, called the hit view, and the set of events that are recognized as proper inputs are, optionally, determined based, at least in part, on the hit view of the initial touch that begins a touch-based gesture.

Hit view determination module **172** receives information related to sub-events of a touch-based gesture. When an application has multiple views organized in a hierarchy, hit view determination module **172** identifies a hit view as the lowest view in the hierarchy which should handle the sub-event. In most circumstances, the hit view is the lowest level view in which an initiating sub-event occurs (i.e., the first sub-event in the sequence of sub-events that form an event or potential event). Once the hit view is identified by the hit view determination module, the hit view typically receives all sub-events related to the same touch or input source for which it was identified as the hit view.

Active event recognizer determination module **173** determines which view or views within a view hierarchy should receive a particular sequence of sub-events. In some embodiments, active event recognizer determination module **173** determines that only the hit view should receive a particular sequence of sub-events. In other embodiments, active event recognizer determination module **173** determines that all views that include the physical location of a sub-event are actively involved views, and therefore determines that all actively involved views should receive a particular sequence of sub-events. In other embodiments, even if touch sub-events were entirely confined to the area associated with one particular view, views higher in the hierarchy would still remain as actively involved views.

Event dispatcher module **174** dispatches the event information to an event recognizer (e.g., event recognizer **180**). In embodiments including active event recognizer determination module **173**, event dispatcher module **174** delivers the event information to an event recognizer determined by active event recognizer determination module **173**. In some

embodiments, event dispatcher module **174** stores in an event queue the event information, which is retrieved by a respective event receiver module **182**.

In some embodiments, operating system **126** includes event sorter **170**. Alternatively, application **136-1** includes event sorter **170**. In yet other embodiments, event sorter **170** is a stand-alone module, or a part of another module stored in memory **102**, such as contact/motion module **130**.

In some embodiments, application **136-1** includes a plurality of event handlers **190** and one or more application views **191**, each of which includes instructions for handling touch events that occur within a respective view of the application's user interface. Each application view **191** of the application **136-1** includes one or more event recognizers **180**. Typically, a respective application view **191** includes a plurality of event recognizers **180**. In other embodiments, one or more of event recognizers **180** are part of a separate module, such as a user interface kit (not shown) or a higher level object from which application **136-1** inherits methods and other properties. In some embodiments, a respective event handler **190** includes one or more of: data updater **176**, object updater **177**, GUI updater **178**, and/or event data **179** received from event sorter **170**. Event handler **190** optionally utilizes or calls data updater **176**, object updater **177** or GUI updater **178** to update the application internal state **192**. Alternatively, one or more of the application views **191** includes one or more respective event handlers **190**. Also, in some embodiments, one or more of data updater **176**, object updater **177**, and GUI updater **178** are included in a respective application view **191**.

A respective event recognizer **180** receives event information (e.g., event data **179**) from event sorter **170**, and identifies an event from the event information. Event recognizer **180** includes event receiver **182** and event comparator **184**. In some embodiments, event recognizer **180** also includes at least a subset of: metadata **183**, and event delivery instructions **188** (which optionally include sub-event delivery instructions).

Event receiver **182** receives event information from event sorter **170**. The event information includes information about a sub-event, for example, a touch or a touch movement. Depending on the sub-event, the event information also includes additional information, such as location of the sub-event. When the sub-event concerns motion of a touch, the event information optionally also includes speed and direction of the sub-event. In some embodiments, events include rotation of the device from one orientation to another (e.g., from a portrait orientation to a landscape orientation, or vice versa), and the event information includes corresponding information about the current orientation (also called device attitude) of the device.

Event comparator **184** compares the event information to predefined event or sub-event definitions and, based on the comparison, determines an event or sub-event, or determines or updates the state of an event or sub-event. In some embodiments, event comparator **184** includes event definitions **186**. Event definitions **186** contain definitions of events (e.g., predefined sequences of sub-events), for example, event 1 (**187-1**), event 2 (**187-2**), and others. In some embodiments, sub-events in an event **187** include, for example, touch begin, touch end, touch movement, touch cancellation, and multiple touching. In one example, the definition for event 1 (**187-1**) is a double tap on a displayed object. The double tap, for example, comprises a first touch (touch begin) on the displayed object for a predetermined phase, a first lift-off (touch end) for a predetermined phase,

a second touch (touch begin) on the displayed object for a predetermined phase, and a second lift-off (touch end) for a predetermined phase. In another example, the definition for event 2 (187-2) is a dragging on a displayed object. The dragging, for example, comprises a touch (or contact) on the displayed object for a predetermined phase, a movement of the touch across touch-sensitive display 112, and lift-off of the touch (touch end). In some embodiments, the event also includes information for one or more associated event handlers 190.

In some embodiments, event definition 187 includes a definition of an event for a respective user-interface object. In some embodiments, event comparator 184 performs a hit test to determine which user-interface object is associated with a sub-event. For example, in an application view in which three user-interface objects are displayed on touch-sensitive display 112, when a touch is detected on touch-sensitive display 112, event comparator 184 performs a hit test to determine which of the three user-interface objects is associated with the touch (sub-event). If each displayed object is associated with a respective event handler 190, the event comparator uses the result of the hit test to determine which event handler 190 should be activated. For example, event comparator 184 selects an event handler associated with the sub-event and the object triggering the hit test.

In some embodiments, the definition for a respective event 187 also includes delayed actions that delay delivery of the event information until after it has been determined whether the sequence of sub-events does or does not correspond to the event recognizer's event type.

When a respective event recognizer 180 determines that the series of sub-events do not match any of the events in event definitions 186, the respective event recognizer 180 enters an event impossible, event failed, or event ended state, after which it disregards subsequent sub-events of the touch-based gesture. In this situation, other event recognizers, if any, that remain active for the hit view continue to track and process sub-events of an ongoing touch-based gesture.

In some embodiments, a respective event recognizer 180 includes metadata 183 with configurable properties, flags, and/or lists that indicate how the event delivery system should perform sub-event delivery to actively involved event recognizers. In some embodiments, metadata 183 includes configurable properties, flags, and/or lists that indicate how event recognizers interact, or are enabled to interact, with one another. In some embodiments, metadata 183 includes configurable properties, flags, and/or lists that indicate whether sub-events are delivered to varying levels in the view or programmatic hierarchy.

In some embodiments, a respective event recognizer 180 activates event handler 190 associated with an event when one or more particular sub-events of an event are recognized. In some embodiments, a respective event recognizer 180 delivers event information associated with the event to event handler 190. Activating an event handler 190 is distinct from sending (and deferred sending) sub-events to a respective hit view. In some embodiments, event recognizer 180 throws a flag associated with the recognized event, and event handler 190 associated with the flag catches the flag and performs a predefined process.

In some embodiments, event delivery instructions 188 include sub-event delivery instructions that deliver event information about a sub-event without activating an event handler. Instead, the sub-event delivery instructions deliver event information to event handlers associated with the series of sub-events or to actively involved views. Event

handlers associated with the series of sub-events or with actively involved views receive the event information and perform a predetermined process.

In some embodiments, data updater 176 creates and updates data used in application 136-1. For example, data updater 176 updates the telephone number used in contacts module 137, or stores a video file used in video player module 145. In some embodiments, object updater 177 creates and updates objects used in application 136-1. For example, object updater 177 creates a new user-interface object or updates the position of a user-interface object. GUI updater 178 updates the GUI. For example, GUI updater 178 prepares display information and sends it to graphics module 132 for display on a touch-sensitive display.

In some embodiments, event handler(s) 190 includes or has access to data updater 176, object updater 177, and GUI updater 178. In some embodiments, data updater 176, object updater 177, and GUI updater 178 are included in a single module of a respective application 136-1 or application view 191. In other embodiments, they are included in two or more software modules.

It shall be understood that the foregoing discussion regarding event handling of user touches on touch-sensitive displays also applies to other forms of user inputs to operate multifunction devices 100 with input-devices, not all of which are initiated on touch screens. For example, mouse movement and mouse button presses, optionally coordinated with single or multiple keyboard presses or holds; contact movements such as taps, drags, scrolls, etc., on touch-pads; pen stylus inputs; movement of the device; oral instructions; detected eye movements; biometric inputs; and/or any combination thereof are optionally utilized as inputs corresponding to sub-events which define an event to be recognized.

FIG. 2 illustrates a portable multifunction device 100 having a touch screen 112 in accordance with some embodiments. The touch screen optionally displays one or more graphics within user interface (UI) 200. In this embodiment, as well as others described below, a user is enabled to select one or more of the graphics by making a gesture on the graphics, for example, with one or more fingers 202 (not drawn to scale in the figure) or one or more styluses 203 (not drawn to scale in the figure). In some embodiments, selection of one or more graphics occurs when the user breaks contact with the one or more graphics. In some embodiments, the gesture optionally includes one or more taps, one or more swipes (from left to right, right to left, upward and/or downward) and/or a rolling of a finger (from right to left, left to right, upward and/or downward) that has made contact with device 100. In some implementations or circumstances, inadvertent contact with a graphic does not select the graphic. For example, a swipe gesture that sweeps over an application icon optionally does not select the corresponding application when the gesture corresponding to selection is a tap.

Device 100 optionally also includes one or more physical buttons, such as "home" or menu button 204. As described previously, menu button 204 is, optionally, used to navigate to any application 136 in a set of applications that are, optionally executed on device 100. Alternatively, in some embodiments, the menu button is implemented as a soft key in a GUI displayed on touch screen 112.

In one embodiment, device 100 includes touch screen 112, menu button 204, push button 206 for powering the device on/off and locking the device, volume adjustment button(s) 208, Subscriber Identity Module (SIM) card slot 210, head set jack 212, and docking/charging external port 124. Push button 206 is, optionally, used to turn the power

on/off on the device by depressing the button and holding the button in the depressed state for a predefined time interval; to lock the device by depressing the button and releasing the button before the predefined time interval has elapsed; and/or to unlock the device or initiate an unlock process. In an alternative embodiment, device **100** also accepts verbal input for activation or deactivation of some functions through microphone **113**. Device **100** also, optionally, includes one or more contact intensity sensors **165** for detecting intensity of contacts on touch screen **112** and/or one or more tactile output generators **167** for generating tactile outputs for a user of device **100**.

FIG. 3 is a block diagram of an exemplary multifunction device with a display and a touch-sensitive surface in accordance with some embodiments. Device **300** need not be portable. In some embodiments, device **300** is a laptop computer, a desktop computer, a tablet computer, a multimedia player device, a navigation device, an educational device (such as a child's learning toy), a gaming system, or a control device (e.g., a home or industrial controller). Device **300** typically includes one or more processing units (CPU's) **310**, one or more network or other communications interfaces **360**, memory **370**, and one or more communication buses **320** for interconnecting these components. Communication buses **320** optionally include circuitry (sometimes called a chipset) that interconnects and controls communications between system components. Device **300** includes input/output (I/O) interface **330** comprising display **340**, which is typically a touch screen display. I/O interface **330** also optionally includes a keyboard and/or mouse (or other pointing device) **350** and touchpad **355**, tactile output generator **357** for generating tactile outputs on device **300** (e.g., similar to tactile output generator(s) **167** described above with reference to FIG. 1A), sensors **359** (e.g., optical, acceleration, proximity, touch-sensitive, and/or contact intensity sensors similar to contact intensity sensor(s) **165** described above with reference to FIG. 1A). Memory **370** includes high-speed random access memory, such as DRAM, SRAM, DDR RAM or other random access solid state memory devices; and optionally includes non-volatile memory, such as one or more magnetic disk storage devices, optical disk storage devices, flash memory devices, or other non-volatile solid state storage devices. Memory **370** optionally includes one or more storage devices remotely located from CPU(s) **310**. In some embodiments, memory **370** stores programs, modules, and data structures analogous to the programs, modules, and data structures stored in memory **102** of portable multifunction device **100** (FIG. 1A), or a subset thereof. Furthermore, memory **370** optionally stores additional programs, modules, and data structures not present in memory **102** of portable multifunction device **100**. For example, memory **370** of device **300** optionally stores drawing module **380**, presentation module **382**, word processing module **384**, website creation module **386**, disk authoring module **388**, and/or spreadsheet module **390**, while memory **102** of portable multifunction device **100** (FIG. 1A) optionally does not store these modules.

Each of the above identified elements in FIG. 3 are, optionally, stored in one or more of the previously mentioned memory devices. Each of the above identified modules corresponds to a set of instructions for performing a function described above. The above identified modules or programs (i.e., sets of instructions) need not be implemented as separate software programs, procedures or modules, and thus various subsets of these modules are, optionally, combined or otherwise re-arranged in various embodiments. In some embodiments, memory **370** optionally stores a subset

of the modules and data structures identified above. Furthermore, memory **370** optionally stores additional modules and data structures not described above.

Attention is now directed towards embodiments of user interfaces ("UI") that is, optionally, implemented on portable multifunction device **100**.

FIG. 4A illustrates an exemplary user interface for a menu of applications on portable multifunction device **100** in accordance with some embodiments. Similar user interfaces are, optionally, implemented on device **300**. In some embodiments, user interface **400** includes the following elements, or a subset or superset thereof:

Signal strength indicator(s) **402** for wireless communication(s), such as cellular and Wi-Fi signals;

Time **404**;

Bluetooth indicator **405**;

Battery status indicator **406**;

Tray **408** with icons for frequently used applications, such as:

Icon **416** for telephone module **138**, labeled "Phone," which optionally includes an indicator **414** of the number of missed calls or voicemail messages;

Icon **418** for e-mail client module **140**, labeled "Mail," which optionally includes an indicator **410** of the number of unread e-mails;

Icon **420** for browser module **147**, labeled "Browser;" and

Icon **422** for video and music player module **152**, also referred to as iPod (trademark of Apple Inc.) module **152**, labeled "iPod;" and

Icons for other applications, such as:

Icon **424** for IM module **141**, labeled "Text;"

Icon **426** for calendar module **148**, labeled "Calendar;"

Icon **428** for image management module **144**, labeled "Photos;"

Icon **430** for camera module **143**, labeled "Camera;"

Icon **432** for online video module **155**, labeled "Online Video"

Icon **434** for stocks widget **149-2**, labeled "Stocks;"

Icon **436** for map module **154**, labeled "Map;"

Icon **438** for weather widget **149-1**, labeled "Weather;"

Icon **440** for alarm clock widget **149-4**, labeled "Clock;"

Icon **442** for workout support module **142**, labeled "Workout Support;"

Icon **444** for notes module **153**, labeled "Notes;" and

Icon **446** for a settings application or module, which provides access to settings for device **100** and its various applications **136**.

It should be noted that the icon labels illustrated in FIG. 4A are merely exemplary. For example, icon **422** for video and music player module **152** are labeled "Music" or "Music Player." Other labels are, optionally, used for various application icons. In some embodiments, a label for a respective application icon includes a name of an application corresponding to the respective application icon. In some embodiments, a label for a particular application icon is distinct from a name of an application corresponding to the particular application icon.

FIG. 4B illustrates an exemplary user interface on a device (e.g., device **300**, FIG. 3) with a touch-sensitive surface **451** (e.g., a tablet or touchpad **355**, FIG. 3) that is separate from the display **450** (e.g., touch screen display **112**). Device **300** also, optionally, includes one or more contact intensity sensors (e.g., one or more of sensors **357**) for detecting intensity of contacts on touch-sensitive surface

451 and/or one or more tactile output generators 359 for generating tactile outputs for a user of device 300.

Although some of the examples which follow will be given with reference to inputs on touch screen display 112 (where the touch sensitive surface and the display are combined), in some embodiments, the device detects inputs on a touch-sensitive surface that is separate from the display, as shown in FIG. 4B. In some embodiments the touch sensitive surface (e.g., 451 in FIG. 4B) has a primary axis (e.g., 452 in FIG. 4B) that corresponds to a primary axis (e.g., 453 in FIG. 4B) on the display (e.g., 450). In accordance with these embodiments, the device detects contacts (e.g., 460 and 462 in FIG. 4B) with the touch-sensitive surface 451 at locations that correspond to respective locations on the display (e.g., in FIG. 4B, 460 corresponds to 468 and 462 corresponds to 470). In this way, user inputs (e.g., contacts 460 and 462, and movements thereof) detected by the device on the touch-sensitive surface (e.g., 451 in FIG. 4B) are used by the device to manipulate the user interface on the display (e.g., 450 in FIG. 4B) of the multifunction device when the touch-sensitive surface is separate from the display. It should be understood that similar methods are, optionally, used for other user interfaces described herein.

Additionally, while the following examples are given primarily with reference to finger inputs (e.g., finger contacts, finger tap gestures, finger swipe gestures), it should be understood that, in some embodiments, one or more of the finger inputs are replaced with input from another input device (e.g., a mouse based input or stylus input). For example, a swipe gesture is, optionally, replaced with a mouse click (e.g., instead of a contact) followed by movement of the cursor along the path of the swipe (e.g., instead of movement of the contact). As another example, a tap gesture is, optionally, replaced with a mouse click while the cursor is located over the location of the tap gesture (e.g., instead of detection of the contact followed by ceasing to detect the contact). Similarly, when multiple user inputs are simultaneously detected, it should be understood that multiple computer mice are, optionally, used simultaneously, or a mouse and finger contacts are, optionally, used simultaneously.

As used herein, the term “focus selector” refers to an input element that indicates a current part of a user interface with which a user is interacting. In some implementations that include a cursor or other location marker, the cursor acts as a “focus selector,” so that when an input (e.g., a press input) is detected on a touch-sensitive surface (e.g., touchpad 355 in FIG. 3 or touch-sensitive surface 451 in FIG. 4B) while the cursor is over a particular user interface element (e.g., a button, window, slider or other user interface element), the particular user interface element is adjusted in accordance with the detected input. In some implementations that include a touch-screen display (e.g., touch-sensitive display system 112 in FIG. 1A or touch screen 112 in FIG. 4A) that enables direct interaction with user interface elements on the touch-screen display, a detected contact on the touch-screen acts as a “focus selector,” so that when an input (e.g., a press input by the contact) is detected on the touch-screen display at a location of a particular user interface element (e.g., a button, window, slider or other user interface element), the particular user interface element is adjusted in accordance with the detected input. In some implementations focus is moved from one region of a user interface to another region of the user interface without corresponding movement of a cursor or movement of a contact on a touch-screen display (e.g., by using a tab key or arrow keys to move focus from one button to another button); in these implementations, the

focus selector moves in accordance with movement of focus between different regions of the user interface. Without regard to the specific form taken by the focus selector, the focus selector is generally the user interface element (or contact on a touch-screen display) that is controlled by the user so as to communicate the user’s intended interaction with the user interface (e.g., by indicating, to the device, the element of the user interface with which the user is intending to interact). For example, the location of a focus selector (e.g., a cursor, a contact or a selection box) over a respective button while a press input is detected on the touch-sensitive surface (e.g., a touchpad or touch screen) will indicate that the user is intending to activate the respective button (as opposed to other user interface elements shown on a display of the device).

The user interface figures described below include various intensity diagrams that show the current intensity of the contact on the touch-sensitive surface relative to one or more intensity thresholds (e.g., a contact detection intensity threshold  $IT_0$ , a light press intensity threshold  $IT_L$ , a deep press intensity threshold  $IT_D$ , and/or one or more other intensity thresholds). This intensity diagram is typically not part of the displayed user interface, but is provided to aid in the interpretation of the figures. In some embodiments, the light press intensity threshold corresponds to an intensity at which the device will perform operations typically associated with clicking a button of a physical mouse or a trackpad. In some embodiments, the deep press intensity threshold corresponds to an intensity at which the device will perform operations that are different from operations typically associated with clicking a button of a physical mouse or a trackpad. In some embodiments, when a contact is detected with an intensity below the light press intensity threshold (e.g., and above a nominal contact-detection intensity threshold  $IT_0$  below which the contact is no longer detected), the device will move a focus selector in accordance with movement of the contact on the touch-sensitive surface without performing an operation associated with the light press intensity threshold or the deep press intensity threshold. Generally, unless otherwise stated, these intensity thresholds are consistent between different sets of user interface figures.

An increase of intensity of the contact from an intensity below the light press intensity threshold  $IT_L$  to an intensity between the light press intensity threshold  $IT_L$  and the deep press intensity threshold  $IT_D$  is sometimes referred to as a “light press” input. An increase of intensity of the contact from an intensity below the deep press intensity threshold  $IT_D$  to an intensity above the deep press intensity threshold  $IT_D$  is sometimes referred to as a “deep press” input. An increase of intensity of the contact from an intensity below the contact-detection intensity threshold  $IT_0$  to an intensity between the contact-detection intensity threshold  $IT_0$  and the light press intensity threshold  $IT_L$  is sometimes referred to as detecting the contact on the touch-surface. A decrease of intensity of the contact from an intensity above the contact-detection intensity threshold  $IT_0$  to an intensity below the contact intensity threshold  $IT_0$  is sometimes referred to as detecting liftoff of the contact from the touch-surface. In some embodiments  $IT_0$  is zero. In some embodiments  $IT_0$  is greater than zero. In some illustrations a shaded circle or oval is used to represent intensity of a contact on the touch-sensitive surface. In some illustrations a circle or oval without shading is used represent a respective contact on the touch-sensitive surface without specifying the intensity of the respective contact.

In some embodiments described herein, one or more operations are performed in response to detecting a gesture that includes a respective press input or in response to detecting the respective press input performed with a respective contact (or a plurality of contacts), where the respective press input is detected based at least in part on detecting an increase in intensity of the contact (or plurality of contacts) above a press-input intensity threshold. In some embodiments, the respective operation is performed in response to detecting the increase in intensity of the respective contact above the press-input intensity threshold (e.g., a “down stroke” of the respective press input). In some embodiments, the press input includes an increase in intensity of the respective contact above the press-input intensity threshold and a subsequent decrease in intensity of the contact below the press-input intensity threshold, and the respective operation is performed in response to detecting the subsequent decrease in intensity of the respective contact below the press-input threshold (e.g., an “up stroke” of the respective press input).

In some embodiments, the device employs intensity hysteresis to avoid accidental inputs sometimes termed “jitter,” where the device defines or selects a hysteresis intensity threshold with a predefined relationship to the press-input intensity threshold (e.g., the hysteresis intensity threshold is X intensity units lower than the press-input intensity threshold or the hysteresis intensity threshold is 75%, 90% or some reasonable proportion of the press-input intensity threshold). Thus, in some embodiments, the press input includes an increase in intensity of the respective contact above the press-input intensity threshold and a subsequent decrease in intensity of the contact below the hysteresis intensity threshold that corresponds to the press-input intensity threshold, and the respective operation is performed in response to detecting the subsequent decrease in intensity of the respective contact below the hysteresis intensity threshold (e.g., an “up stroke” of the respective press input). Similarly, in some embodiments, the press input is detected only when the device detects an increase in intensity of the contact from an intensity at or below the hysteresis intensity threshold to an intensity at or above the press-input intensity threshold and, optionally, a subsequent decrease in intensity of the contact to an intensity at or below the hysteresis intensity, and the respective operation is performed in response to detecting the press input (e.g., the increase in intensity of the contact or the decrease in intensity of the contact, depending on the circumstances).

For ease of explanation, the description of operations performed in response to a press input associated with a press-input intensity threshold or in response to a gesture including the press input are, optionally, triggered in response to detecting either: an increase in intensity of a contact above the press-input intensity threshold, an increase in intensity of a contact from an intensity below the hysteresis intensity threshold to an intensity above the press-input intensity threshold, a decrease in intensity of the contact below the press-input intensity threshold, and/or a decrease in intensity of the contact below the hysteresis intensity threshold corresponding to the press-input intensity threshold. Additionally, in examples where an operation is described as being performed in response to detecting a decrease in intensity of a contact below the press-input intensity threshold, the operation is, optionally, performed in response to detecting a decrease in intensity of the contact

below a hysteresis intensity threshold corresponding to, and lower than, the press-input intensity threshold.

### User Interfaces and Associated Processes

#### Selecting a Tactile Output Corresponding to a Change in Intensity of a Contact

Many electronic devices have graphical user interfaces including one or more user interface objects. When users attempt to perform operations associated with these user interface objects, these operations are sometimes successful and sometimes unsuccessful. For example, attempting to move a user interface object to a region of a user interface that does not accept user interface objects will be unsuccessful. In many user interfaces, there are one or more visual or audible cues as to whether or not the operation associated with the user interface object was successful. However, in some situations the user will miss a visual or audible cue as to whether or not an operation was successful (e.g., because the user was not looking at the display and/or has the volume of the device turned down or turned off, or because the user was distracted when the cue was provided). A missed cue can result in the user attempting to repeat an operation that was successfully performed or proceeding to perform other operations without realizing that the attempted operation was not performed. Thus, it would be advantageous to provide additional cues to the user to indicate whether or not an operation was successful. In a touch-sensitive surface with an integrated mechanical button, the sensation of reducing the intensity of a contact on touch-sensitive surface is determined based on the mechanism of the mechanical button and thus is the same (for the same user input) without regard to whether or not an operation associated with the contact was performed. In contrast, when the touch-sensitive surface is associated with sensors for determining the intensity of the contact with the touch-sensitive surface and a separate actuator generates a software controlled tactile output on the touch-sensitive surface, the tactile output generated after the user has attempted to perform an operation can be varied depending on whether or not the operation was successfully performed (e.g., because the tactile outputs are decoupled from the intensity inputs). Providing such tactile feedback as to whether or not an attempted operation has been performed improves the machine-user interface by providing the user with timely, accurate feedback regarding performance of the operation.

FIGS. 5A-5W illustrate exemplary user interfaces for selecting a tactile output corresponding to a change in intensity of a contact in accordance with some embodiments. The user interfaces in these are used to illustrate the processes described below, including the processes in FIGS. 6A-6B. FIGS. 5A-5W include intensity diagrams that show the current intensity of the contact on the touch-sensitive surface relative to a plurality of intensity thresholds including an object-selection intensity threshold (e.g., “ $IT_L$ ”) and an object-release threshold (e.g., “ $IT_1$ ”). In some embodiments, the object-selection intensity threshold is different from (e.g., higher than) the object-release intensity threshold. In some embodiments, the object-selection intensity threshold is  $IT_D$  and the object-release intensity threshold is  $IT_D$  or an intensity threshold slightly below  $IT_D$ .

FIG. 5A illustrates user interface 11700 (e.g., a desktop user interface or a drawing input area within a drawing or graphics application) displayed on display 450 (e.g., display 340) of a device (e.g., device 300). One or more user interface objects 11702 are displayed in user interface

**11700.** In FIG. 5A, user interface objects **11702-1** through **11702-3** are displayed in user interface **11700**. A user interface object **11702** is, optionally one of, an application shortcut or launch icon, a shape or object within a drawing or graphics program, or other icon, widget, or object. One or more windows **11704** are, optionally, displayed in user interface **11700** as well. A window **11704** is, optionally, an application window corresponding to a respective application.

Cursor **11706** is also displayed in user interface **11700** on display **450**. In some embodiments, cursor **11706** is a mouse pointer. Cursor **11706** is an example of a focus selector. A user optionally positions cursor **11706** at any location in user interface **11700** by making a contact (for example, a finger contact or a stylus contact) on touch-sensitive surface **451** (e.g., touchpad **355**) of the device and moving the contact on touch-sensitive surface **451** as desired. In response to the detection of the contact and movement of the contact on touch-sensitive surface **451**, cursor **11706** is positioned at a position in user interface **11700** that corresponds to the current position of the contact on touch-sensitive surface **451** and moves in accordance with movement of the contact on touch-sensitive surface **451**. In FIG. 5A, contact **11708** is detected at a position on touch-sensitive surface **451**, and cursor **11706** is positioned at a corresponding position in user interface **11700**, over user interface object **11702-2**, as shown.

The device includes one or more sensors that detect the intensity of contacts with touch-sensitive surface **451**. In FIG. 5A, the intensity of contact **11708** is detected to be below an object-selection threshold (e.g., “ $IT_L$ ” in FIGS. 5A-5W). The intensity of contact **11708** below the object-selection threshold is represented by the empty background in contact **11708** as shown in FIG. 5A.

The intensity of contact **11708** is increased by, for example, the user applying more pressure on touch-sensitive surface **451** with contact **11708**. The change in intensity of contact **11708** is detected by the contact intensity sensors in the device. In response to the detection of an increase in the intensity of contact **11708** above the object-selection threshold (with the intensity that is above the object-selection threshold represented by the densely dotted background in contact **11708** as shown in FIG. 5B), a user interface object over which cursor **11706** is positioned is selected. In FIG. 5B, cursor **11706** is positioned over user interface object **11702-2**, and thus user interface object **11702-2** is selected. User interface object **11702-2** is, optionally, visually highlighted (for example, with a different color; with thicker borders, as shown in FIG. 5B) to indicate the selection. In some embodiments, a tactile output indicative of the selection of user interface object **11702-2** is generated on the touch-sensitive surface. The tactile output indicative of the selection is, optionally, generated in accordance with a movement profile associated with selection of a user interface object. In some embodiments, the selection tactile output corresponds to a tactile sensation that simulates a down-click of a mechanical button (for example, a click sensation of pressing a mouse button or a trackpad with an integrated button).

While the intensity of contact **11708** remains above an object-release threshold (e.g., “ $IT_1$ ” in FIGS. 5A-5W) and user interface object **11702-2** remains selected, the user moves contact **11708** on touch-sensitive surface **451**. In response to detection of the movement of contact **11708**, user interface object **11702-2**, as well as cursor **11706**, is moved across user interface **11700** in accordance with the movement of contact **11708**; user interface object **11702-2** is

dragged across user interface **11700** in accordance with the movement of contact **11708**. For example, as shown in FIGS. 5C-5D, in response to the movement of contact **11708** in direction **11710** on touch-sensitive surface **451**, user interface object **11702-2** moves in direction **11712** to another position in user interface **11700**. The new position of user interface object **11702-2**, as shown in FIG. 5D, is over “empty space” in user interface **11700**, away from window **11704** and other user interface objects **11702**.

The object-release threshold is an intensity threshold that determines whether a selected user interface object is released from selection. In some embodiments, the object-release threshold is below the object-selection threshold. In some other embodiments, the object-release threshold is the same as the object-selection threshold.

While user interface object **11702-2** is located at the new position in user interface **11700**, as shown in FIG. 5D, the user reduces the intensity of contact **11708**, such as by reducing the pressure on touch-sensitive surface **451** with contact **11708** (including, for example, completely releasing contact **11708** from touch-sensitive surface **451**). As shown in FIG. 5E, the intensity of contact **11708** is reduced below the object-release threshold, with the intensity below the object-release threshold represented by the sparsely dotted background in contact **11708** and the intensity meter shown in FIG. 5E. In response to the reduction in intensity of contact **11708** below the object-release threshold, an attempt to relocate (or “drop”) user interface object **11702-2** at the new position is made. The “empty space” in user interface **11700** is a valid drop location, as that empty space is not already occupied by a user interface object **11702** or a window **11704**, and thus the relocation of user interface object **11702-2** to the new position is successful. As a result, user interface object **11702-2** is dropped at the new position in user interface **11700** and de-selected (i.e., released from selection). A tactile output is generated on touch-sensitive surface **451**, along with the dropping of user interface object **502-2**, in response to detection of the reduction in intensity of contact **11708** below the object-release threshold.

Returning to FIG. 5B, selected user interface object **11702-2** moves in response to detection of movement of contact **11708**, as described above. FIGS. 5F-5G show user interface object **11702-2** moving in direction **11716** in user interface **11700** to a new position that is over window **11704**, in response to detection of movement of contact **11708** in direction **11714** on touch-sensitive surface **451**; user interface object **11702-2** is dragged across user interface **11700** in accordance with the movement of contact **11708**.

While user interface object **11702-2** is located at the new position over window **11704**, as shown in FIG. 5G, the user reduces the intensity of contact **11708**, such as by reducing the pressure on touch-sensitive surface **451** with contact **11708** (including, for example, lifting contact **11708** off of touch-sensitive surface **451**). As shown in FIG. 5H, the intensity of contact **11708** has been reduced below the object-release threshold. In response to the reduction in intensity of contact **11708** below the object-release threshold, an attempt to relocate user interface object **11702-2** at the new position is made (e.g., the position of user interface object **11702-2** in FIG. 5G). The position over window **11704** within user interface **11700** is an invalid drop location, as the position is already occupied by window **11704**, and thus the relocation of user interface object **11702-2** at the new position is unsuccessful. As a result, user interface object **11702-2** is returned to its original location and de-selected. A tactile output that is different from the tactile output generated for the successful drop of user interface

object **11702-2**, described above with reference to FIG. 5E, is generated on touch-sensitive surface **451**, along with the return of user interface object **11702-2** to its original position, in response to detection of the reduction in intensity of contact **11708** below the object-release threshold.

Thus, after selection of user interface object **11702-2**, movement of contact **11708** and a decrease in the intensity of contact **11708** below the object-release threshold is performed by the user. In response to the detection of the decrease in intensity below the object-release threshold, an attempt to drop user interface object **11702-2** at a new position is made. Depending on whether the new position is a valid drop target/location or an invalid drop target/location, the drop is successful (i.e., the drop is performed) or unsuccessful (i.e., performance of the drop is not performed).

As described above, different tactile outputs are, optionally, generated for a successful drop of a user interface object (for example, as described above with reference to FIG. 5E) and for an unsuccessful drop of a user interface object (for example, as described above with reference to FIG. 5H). In some embodiments, the tactile output for the successful drop and the tactile output for the unsuccessful drop both correspond to tactile sensations that simulate of an up-click of a mechanical button (for example, releasing a clicked-and-held mouse button). In some embodiments, the tactile outputs for a successful drop and an unsuccessful drop have different amplitudes but are otherwise both generated in accordance with the same movement profile. For example, the tactile output for the successful drop has a higher amplitude than, but otherwise have the same movement profile (e.g., square waveform) as, the tactile output for the unsuccessful drop.

In some other embodiments, the tactile output for a successful drop and the tactile output for an unsuccessful drop have different movement profiles. For example, the tactile output for the successful drop is, optionally, generated in accordance with a sinusoidal movement profile, and the tactile output for the unsuccessful drop is, optionally, generated in accordance with a sawtooth waveform movement profile.

Returning to FIG. 5B, selected user interface object **11702-2** moves in response to detection of movement of contact **11708**, as described above. FIGS. 5I-5K show user interface object **11702-2** moving, continuously, in direction **11722** and then direction **11724** in user interface **11700**, in response to detection of continuous movement of contact **11708** in direction **11718** and then direction **11720**, respectively, on touch-sensitive surface **451**. User interface object **11702-2** moves to a position over window **11704** and then to "empty space" in user interface **11700**; user interface object **11702-2** is dragged across user interface **11700** in accordance with the movement of contact **11708**, over empty space and window **11704** at different times. Thus, during the movement, user interface object **11702-2** moves over an invalid drop location for a period of time and over a valid drop location for another period of time.

As user interface object **11702-2** is moving, while user interface object **11702-2** is over window **11704**, as shown in FIG. 5J, a tactile output associated with an invalid drop location is, optionally, generated on touch-sensitive surface **451**. The tactile output alerts the user that the current position of the user interface object **11702-2** is an invalid drop location.

As user interface object **11702-2** continues to move, while user interface object **11702-2** is over empty space in user interface **11700**, as shown in FIG. 5K, a tactile output

associated with a valid drop location is, optionally, generated on touch-sensitive surface **451**. The tactile output alerts the user that the current position of the user interface object **11702-2** is a valid drop location. The tactile output associated with a valid drop location is different from the tactile output associated with an invalid drop location. For example, the valid drop location tactile output has a higher amplitude and/or different movement profile from the invalid drop location tactile output. In some embodiments, the tactile output associated with a valid drop target/location is generated according to the same movement profile and amplitude as a tactile output associated with a successful drop. Similarly, the tactile output associated with an invalid drop target/location is generated according to the same movement profile and amplitude as a tactile output associated with an unsuccessful drop. For example, the touch-sensitive surface optionally provides a high frequency periodic tactile output (e.g., a slight buzzing) while user interface object **11702-2** is over an invalid drop target and either does not provide any tactile output or provides a low frequency periodic tactile output (e.g., a periodic ping) while user interface object **11702-2** is over a valid drop target.

When the intensity of contact **11708** is reduced below the object-release threshold while user interface object **11702-2** is over empty space in user interface **11700**, as shown in FIG. 5L, user interface object **11702-2** is dropped successfully at its new position.

It should be appreciated that the criteria for a valid drop target/location and an invalid drop target/location described above (whether a location is already occupied by a user interface object **11702** or window **11704**) are merely exemplary, and other criteria are, optionally, employed in other embodiments, implementations, or for different categories of user interface objects or for different operations within an embodiment or implementation. For example, dropping an application shortcut or launch icon at a position over another application shortcut/launch icon or over an application window is invalid, while dropping a shape within a drawing program at a position over another shape is valid. As another example, dropping an application shortcut/launch icon at a position over another application shortcut/launch icon is valid if the operation includes swapping the locations of the application shortcuts/launch icons affected.

As described above, tactile outputs are, optionally, generated for a selection of a user interface object, a valid drop, an invalid drop, a valid drop location, and an invalid drop location. FIGS. 5M-5O illustrate example waveforms of movement profiles for generating these tactile outputs. FIG. 5M illustrates a sawtooth waveform. FIG. 5N illustrates a square waveform, and FIG. 5O illustrates a square waveform that has a lower amplitude than the square waveform of FIG. 5N. The sawtooth movement profile in FIG. 5M is, optionally, associated with selection of a user interface object; the tactile output generated for selection of a user interface object is, optionally, generated in accordance with the sawtooth movement profile. The high-amplitude square movement profile in FIG. 5N is, optionally, associated with a successful drop (or a valid drop target/location); the tactile output generated for a successful drop or valid drop target/location is, optionally, generated in accordance with a high-amplitude square movement profile. The low-amplitude square movement profile in FIG. 5O is, optionally, associated with an unsuccessful drop (or an invalid drop target/location); the tactile output generated for an unsuccessful drop or invalid drop target/location is, optionally, generated in accordance with a low-amplitude square movement profile.

FIGS. 5P-5W illustrate an example of the user interfaces described above, with reference to FIGS. 5A-5O, implemented on a device (e.g., device 100) with a touch-sensitive display 112. FIG. 5P illustrates user interface 11736 (e.g., a home menu or screen interface, a desktop user interface, a drawing input area within a drawing or graphics application) displayed on touch-sensitive display 112 of a device. One or more user interface objects 11732 are, optionally displayed in user interface 11736. In FIG. 5P, user interface objects 11732-1 through 11732-3 are displayed in user interface 11736. A user interface object 11732 is, for example, an application shortcut or launch icon, a shape or object within a drawing or graphics program, or other icon, widget, or object. One or more windows 11734 are, optionally, displayed in user interface 11736 as well. A window 11734 is, for example, an application window corresponding to a respective application. Contact 11738 is detected on touch-sensitive display at a location over user interface object 11732-2.

The device includes one or more sensors that detect the intensity of contacts with touch-sensitive display 112. In FIG. 5P, the intensity of contact 11738 is detected to be below an object-selection threshold. The intensity of contact 11738 below the object-selection threshold is represented by the empty background in contact 11738 as shown in FIG. 5P.

The intensity of contact 11738 is increased by, for example, the user applying more pressure on touch-sensitive display 112 with contact 11738. The change in intensity of contact 11738 is detected by the contact intensity sensors in the device. In response to the detection of an increase in the intensity of contact 11738 above the object-selection threshold (with the intensity that is above the object-selection threshold represented by the densely dotted background in contact 11738 and the intensity meter shown in FIG. 5Q), a user interface object over which contact 11738 is positioned is selected. In FIG. 5Q, contact 11738 is positioned over user interface object 11732-2, and thus user interface object 11732-2 is selected. User interface object 11736-2 is, optionally, visually highlighted (for example, with a different color; with thicker borders, as shown in FIG. 5Q) to indicate the selection. In some embodiments, a tactile output indicative of the selection of user interface object 11732-2 is generated on touch-sensitive display 112. The tactile output indicative of the selection is, optionally, generated in accordance with a movement profile associated with selection of a user interface object. In some embodiments, the selection tactile output corresponds to a tactile sensation that simulates a down-click of a mechanical button (for example, a click sensation of a pressing mouse button).

While the intensity of contact 11738 remains above an object-release threshold and user interface object 11732-2 remains selected, the user moves contact 11738 on touch-sensitive display 112. In response to detection of the movement of contact 11738, user interface object 11732-2 is moved across user interface 11736 in accordance with the movement of contact 11738; user interface object 11732-2 is dragged across user interface 11736 in accordance with the movement of contact 11738. For example, as shown in FIGS. 5R-5S, in response to movement of contact 11738 in direction 11740 on touch-sensitive display 112, user interface object 11732-2 moves in the same direction as contact 11738 to another position in user interface 11736. The new position of user interface object 11732-2, as shown in FIG. 5S, is over “empty space” in user interface 11736, away from window 11734 and other user interface objects 11732-1 and 11732-3.

While user interface object 11732-2 is located at the new position in user interface 11736, as shown in FIG. 5S, the user reduces the intensity of contact 11738, such as by reducing the pressure on touch-sensitive display 112 with contact 11738 (including, for example, lifting contact 11738 off of touch-sensitive display 112). As shown in FIG. 5T, the intensity of contact 11738 is reduced below the object-release threshold, with the intensity below the object-release threshold represented by the sparsely dotted background in contact 11738 and the intensity meter. In response to the reduction in intensity of contact 11738 below the object-release threshold, an attempt to relocate (or “drop”) user interface object 11732-2 at the new position is made. The “empty space” in user interface 11736 is a valid drop location, as that empty space is not already occupied by a user interface object 11732 or a window 11734, and thus the relocation of user interface object 11732-2 to the new position is successful. As a result, user interface object 11732-2 is dropped at the new position in user interface 11736 and de-selected (i.e., released from selection). A tactile output is generated on touch-sensitive display 112, along with the dropping of user interface object 532-2, in response to detection of the reduction in intensity of contact 11738 below the object-release threshold.

Returning to FIG. 5Q, selected user interface object 11732-2 moves in response to detection of movement of contact 11738, as described above. FIGS. 5U-5V show user interface object 11732-2 moving in direction 11742 in user interface 11736 to a new position that is over window 11734, in response to detection of movement of contact 11738 in direction 11742 on touch-sensitive display 112; user interface object 11732-2 is dragged across user interface 11736 in accordance with the movement of contact 11738.

While user interface object 11732-2 is located at the new position over window 11734, as shown in FIG. 5V, the user reduces the intensity of contact 11738, such as by reducing the pressure on touch-sensitive display 112 with contact 11738 (including, for example, completely releasing contact 11738 from touch-sensitive display 112). As shown in FIG. 5W, the intensity of contact 11738 has been reduced below the object-release threshold. In response to the reduction in intensity of contact 11738 below the object-release threshold, an attempt to relocate user interface object 11732-2 at the new position is made. The position over window 11734 within user interface 11736 is an invalid drop location, as the position is already occupied by window 11734, and thus the relocation of user interface object 11732-2 at the new position is unsuccessful. As a result, user interface object 11732-2 is returned to its original location and de-selected. A tactile output that is different from the tactile output generated for the successful drop of user interface object 11732-2, described above with reference to FIG. 5T, is generated on touch-sensitive display 112, along with the return of user interface object 11732-2 to its original position, in response to detection of the reduction in intensity of contact 11738 below the object-release threshold.

FIGS. 6A-6B are flow diagrams illustrating a method 11800 of selecting a tactile output corresponding to a change in intensity of a contact in accordance with some embodiments. The method 11800 is performed at an electronic device (e.g., device 300, FIG. 3, or portable multifunction device 100, FIG. 1A) with a display, a touch-sensitive surface, and one or more sensors to detect intensity of contacts with the touch-sensitive surface. In some embodiments, the display is a touch screen display and the touch-sensitive surface is on the display. In some embodiments, the display is separate from the touch-sensitive surface. Some

operations in method **11800** are, optionally, combined and/or the order of some operations is, optionally, changed.

As described below, the method **11800** provides an intuitive way to relocate a user interface object. The method reduces the cognitive burden on a user when relocating user interface objects, thereby creating a more efficient human-machine interface. For battery-operated electronic devices, enabling a user to relocate a user interface object faster and more efficiently conserves power and increases the time between battery charges.

The device displays (**11802**) a user interface object on the display. FIG. 5A, for example, shows user interface objects **11702-1** through **11702-3** displayed on display **450**. As another example, FIG. 5P shows user interface objects **11732-1** through **11732-3** displayed on touch-sensitive display **112**.

The device detects (**11804**), on the touch-sensitive surface, a contact (e.g., a finger contact or a stylus contact) having an intensity above an object-selection threshold (e.g., “ $IT_L$ ”). The device can, using the one or more sensors, detect an intensity of a contact on the touch-sensitive surface (e.g., touchpad **355**). In FIG. 5B, for example, contact **11708** which has an intensity greater than an object-selection threshold, is detected. Similarly, in FIG. 5Q, contact **11738**, which has an intensity greater than an object-selection threshold, is detected.

In some embodiments, prior to detecting movement of the contact across the touch-sensitive surface (**11806**), in response to detecting an increase in intensity of the contact above the object-selection threshold, the device generates (**11808**) a selection tactile output on the touch-sensitive surface indicative of the selection. The contact that is detected as having an intensity above the object-selection threshold has the intensity above the object-selection threshold as a result of an increase in intensity of the contact from below the object-selection threshold to above the object-selection threshold. When the increase in intensity above the object-selection threshold is detected prior to movement of the contact across the touch-sensitive surface, a user interface object is selected and a selection tactile output is generated in response.

For example, in FIG. 5A, contact **11708** on touch-sensitive surface **451** has an intensity below the object-selection threshold, and a focus selector (e.g., cursor **11706**) is positioned over user interface object **11702-2** in accordance with the position of contact **11708** on touch-sensitive surface **451**. When, prior to movement of contact **11708** across touch-sensitive surface **451**, the intensity of contact **11708** is detected to have increased above the object-selection threshold, as shown in FIG. 5B, user interface object **11702-2** is selected and a tactile output associated with selection of a user interface object is generated on touch-sensitive surface **451**. The tactile output indicates to the user that user interface object **502-2** has been selected. Similarly, a tactile output is generated in response to detection of the increase in the intensity of contact **11738** above the object-selection threshold.

The device detects (**11810**) movement of the contact across the touch-sensitive surface, the movement corresponding to a preliminary portion of a gesture for performing an operation corresponding to the user interface object. For example, the movement is part of an operation to relocate an icon representing a file stored on the device, which will be completed if the icon is moved to a valid drop target and dropped onto the valid drop target (e.g., in response to detecting a liftoff of the contact or a reduction in intensity/pressure of the contact on the touch sensitive

surface below an object-release threshold, such as “ $IT_1$ ” or “ $IT_L$ ”). For example, in FIGS. 5C-5D, contact **11708** moves in direction **11710** on touch-sensitive surface **451**, and the movement is detected by the device. In FIGS. 5F-5G, contact **11708** moves in direction **11714** on touch-sensitive surface **451**, and the movement is detected by the device. In FIGS. 5I-5K, contact **11708** moves in direction **11718** and then **11720** on touch-sensitive surface **451**. In response to the detection of the respective movement of contact **11708**, user interface object **11702-2** is moved in user interface **11700** in accordance with the detected movement of contact **11708**. The movement is part of a gesture to relocate user interface object **11702-2** in user interface **11700**. As another example, in FIGS. 5Q-5R, movement of contact **11738** in direction **11740** is detected, and in FIGS. 5U-5V, movement of contact **11738** in direction **11742** is detected.

In some embodiments, for a first time period during the gesture, the user interface object is over an invalid drop target, and for a second time period during the gesture, the user interface object is over a valid drop target (**11812**). The device, during the first period of time, generates (**11814**) an invalid-drop-target tactile output on the touch-sensitive surface. The device, during the second period of time, generates (**11816**) a valid-drop-target tactile output on the touch-sensitive surface, where the invalid-drop-target tactile output is different from the valid-drop-target tactile output. In some situations, when a user interface object is moved, the user interface object is over a valid drop target or location for a time period and is over an invalid drop target or location for another time period (e.g., as illustrated in FIGS. 5I-5K). During the time period when the user interface object is over a valid drop target or location, a tactile output is generated on touch-sensitive surface **451**. During the time period when the user interface object is over an invalid drop target or location, a different tactile output is generated on touch-sensitive surface **451**.

For example, in FIGS. 5I-5K, user interface object **11702-2** is moved in accordance with the movement of contact **11708** on touch-sensitive surface **451**. In FIG. 5J, user interface object **11702-2** moves over window **11704**, an invalid drop target. In FIG. 5K, user interface object **11702-2** moves over empty space in user interface **11700**, a valid drop target. During the period when user interface object **11702-2** is moving over window **11704**, a tactile output is generated. During the period when user interface object **11702-2** is moving over empty space in user interface **11700**, a tactile output different from that generated for the period when user interface object **11702-2** is moving over window **11704** is generated. The tactile outputs is different with respect to amplitude and/or movement profile. For example, the touch-sensitive surface optionally provides a high frequency periodic tactile output (e.g., a slight buzzing) while user interface object **11702-2** is over an invalid drop target and either does not provide any tactile output or provides a low frequency periodic tactile output (e.g., a periodic ping) while user interface object **11702-2** is over a valid drop target.

The device detects (**11818**) a reduction in intensity of the contact below an object-release threshold. When user interface object **11702-2** is moved to the target location for the drop, the user reduces the intensity of contact **11708** below the object-release threshold (e.g., reducing intensity of the contact while maintaining the contact or lifting the contact off of the touch-sensitive surface) to make the drop attempt, as shown in FIG. 5E, 5H, or 5L, for example. As another example, when user object **11732-2** is moved to the target location for the drop, the user reduces the intensity of

contact **11738** below the object-release threshold (e.g., reducing intensity of the contact while maintaining the contact or lifting the contact off of the touch-sensitive surface) to make the drop attempt, as shown in FIG. 5T or 5W.

In response to detecting the reduction in intensity below the object-release threshold (**11820**), in accordance with a determination that the movement meets predefined operation-performance criteria (**11822**), the device performs (**11824**) the operation and generates (**11826**) a first tactile output on the touch-sensitive surface. In accordance with a determination that the movement does not meet the predefined operation-performance criteria (**11828**), the device forgoes (**11830**) performance of the operation and generates (**11832**) a second tactile output on the touch-sensitive surface, where the second tactile output is different from the first tactile output. For example, in response to the reduction in intensity of contact **11708** or **11738** below the object-release threshold (e.g., a reduction in intensity of the contact while maintaining the contact or lifting the contact off of the touch-sensitive surface), an attempt to drop user interface object **11702-2** or **11732-2**, respectively is made. Whether the drop is performed (e.g., if the drop is successful or not) depends on whether one or more predefined operation-performance criteria are satisfied. In some embodiments, for a drop operation, a criterion for operation performance is whether the drop target/location is valid. If user interface object **11702-2** or **11732-2** is over a valid drop target (and thus a determination is made that the predefined operation-performance criteria for a drop are satisfied), such as empty space in user interface **11700** or **11736**, the drop is performed, as shown in FIG. 5E, 5L, or 5T, respectively, and a tactile output associated with a successful drop is generated on touch-sensitive surface **451** or touch-sensitive display **112**. If user interface object **11702-2** or **11732-2** is over an invalid drop target (and thus a determination is made that the predefined operation-performance criteria for a drop are not satisfied), such as window **11704** or **11734**, the drop is not performed, as shown in FIG. 5H or 5W, respectively, and a tactile output associated with an unsuccessful drop is generated on touch-sensitive surface **451** or touch-sensitive display **112**.

In some embodiments, the operation is an object drop operation (e.g., a file move operation such as dragging an icon representing a file to a new location in a file manager user interface), the movement corresponds to movement of the user interface object to a respective location in the user interface, the movement meets the predefined operation-performance criteria when the respective location is a valid drop location, and the movement does not meet the predefined operation-performance criteria when the respective location is an invalid drop location (**11834**). As described above, the movement of contact **11708** is, optionally, part of a gesture for performing a drag and drop operation in user interface object **11702-2** that corresponds to movement of user interface object **11702-2** to a new location in user interface **11700**. When user interface object **11702-2** is moved to a valid drop target/location, the movement in the gesture is considered to satisfy the criteria for performing a drop operation, and the drop is performed, as shown in FIG. 5E or 5L, for example. On the other hand, when user interface object **11702-2** is moved to an invalid drop target/location, the movement in the gesture is considered to not satisfy the criteria for performing a drop operation, and the drop is not performed, as shown in FIG. 5H, for example. Similarly, movement of contact **11738** is, optionally, part of a gesture for performing a drag and drop operation in user

interface object **11732-2** that corresponds to movement of user interface object **11732-2** to a new location in user interface **11736**. When user interface object **11732-2** is moved to a valid drop target/location, the movement in the gesture is considered to satisfy the criteria for performing a drop operation; the drop is performed, as shown in FIG. 5T, for example. On the other hand, when user interface object **11732-2** is moved to an invalid drop target/location, the movement in the gesture is considered to not satisfy the criteria for performing a drop operation; the drop is not performed, as shown in FIG. 5W, for example.

In some embodiments, the first tactile output is generated by movement of the touch-sensitive surface that includes a first dominant movement component (e.g., movement corresponding to the initial impulse, ignoring any unintended resonance), the second tactile output is generated by movement of the touch-sensitive surface that includes a second dominant movement component, and the first dominant movement component and the second dominant movement component have a same movement profile (e.g., same waveform shape such as square, sine, squine, sawtooth or triangle; and/or approximately the same width/period) and different amplitudes (**11836**). The tactile output for a successful drop and the tactile output for an unsuccessful drop both have respective dominant movement components that have respective movement profiles (for example, the movement profiles depicted in FIGS. 5N and 5O, respectively). The two tactile outputs optionally have the same movement profile but different amplitudes, as shown in FIGS. 5N and 5O, for example. Thus, in some embodiments, the tactile outputs for a successful drop and an unsuccessful drop optionally differ in amplitude rather than in the movement profile; one sensation is a more intense version of the other sensation.

In some embodiments, the selection tactile output corresponds to a tactile sensation that simulates a down-click of a mechanical button, the first tactile output corresponds to a first tactile sensation that simulates an up-click of the mechanical button, and the second tactile output corresponds to a second tactile sensation that simulates an up-click of the mechanical button, where the second tactile sensation feels different (e.g., to a user of the device) from the first tactile sensation (**11838**). The selection tactile output corresponds to a simulation of, for example, a click-and-hold of a mouse button on mouse **350** or trackpad of device **300**. The first tactile output corresponds to a tactile sensation that simulates a release of the mouse button (or trackpad button). The second tactile output corresponds to a tactile sensation that simulates the release of the mouse button (or trackpad button) in a way that is different from the first tactile output. The first and second tactile sensations optionally simulate the mouse button release differently by using, for example, different amplitudes and/or different movement profiles.

It should be understood that the particular order in which the operations in FIGS. 6A-6B have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., those listed in the fifth paragraph of the Description of Embodiments) are also applicable in an analogous manner to method **11800** described above with respect to FIGS. 6A-6B. For example, the contacts, user interface objects, tactile outputs, intensity thresholds, and

focus selectors described above with reference to method **11800** optionally have one or more of the characteristics of the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, and focus selectors described herein with reference to other methods described herein (e.g., those listed in the fifth paragraph of the Description of Embodiments). For brevity, these details are not repeated here.

In accordance with some embodiments, FIG. 7 shows a functional block diagram of an electronic device **11900** configured in accordance with the principles of the various described embodiments. The functional blocks of the device are, optionally, implemented by hardware, software, or a combination of hardware and software to carry out the principles of the various described embodiments. It is understood by persons of skill in the art that the functional blocks described in FIG. 7 are, optionally, combined or separated into sub-blocks to implement the principles of the various described embodiments. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein. As shown in FIG. 7, an electronic device **11900** includes a display unit **11902** configured to display a user interface object, a touch-sensitive surface unit **11904** configured to receive contacts, one or more sensor units **11905** configured to detect intensity of contacts with the touch-sensitive surface unit **11904**, and a processing unit **11906** coupled to the display unit **11902**, the touch-sensitive surface unit **11904**, and the sensor units **11905**. In some embodiments, the processing unit **11906** includes a detecting unit **11908**, a performing unit **11910**, and a generating unit **11912**.

The processing unit **11906** configured to: detect, on the touch-sensitive surface unit **11904**, a contact having an intensity above an object-selection threshold (e.g., with the detecting unit **11908**); detect movement of the contact across the touch-sensitive surface unit **11904**, the movement corresponding to a preliminary portion of a gesture for performing an operation corresponding to the user interface object (e.g., with the detecting unit **11908**); detect a reduction in intensity of the contact below an object-release threshold (e.g., with the detecting unit **11908**); and in response to detecting the reduction in intensity below the object-release threshold: in accordance with a determination that the movement meets predefined operation-performance criteria: perform the operation (e.g., with the performing unit **11910**); and generate a first tactile output on the touch-sensitive surface unit **11904** (e.g., with the generating unit **11912**); and in accordance with a determination that the movement does not meet the predefined operation-performance criteria: forgo performance of the operation (e.g., with the performing unit **11910**); and generate a second tactile output on the touch-sensitive surface unit **11904**, wherein the second tactile output is different from the first tactile output (e.g., with the generating unit **11912**).

In some embodiments, the operation is an object drop operation, the movement corresponds to movement of the user interface object to a respective location in the user interface, the movement meets the predefined operation-performance criteria when the respective location is a valid drop location, and the movement does not meet the predefined operation-performance criteria when the respective location is an invalid drop location.

In some embodiments, the processing unit **11906** is configured to, prior to detecting movement of the contact across the touch-sensitive surface unit **11904**: in response to detecting an increase in intensity of the contact above the object-selection threshold, generate a selection tactile output on the

touch-sensitive surface unit **11904** indicative of the selection (e.g., with the generating unit **11912**).

In some embodiments, the selection tactile output corresponds to a tactile sensation that simulates a down-click of a mechanical button, the first tactile output corresponds to a first tactile sensation that simulates an up-click of the mechanical button, and the second tactile output corresponds to a second tactile sensation that simulates an up-click of the mechanical button, where the second tactile sensation feels different from the first tactile sensation.

In some embodiments, the first tactile output is generated by movement of the touch-sensitive surface unit **11904** that includes a first dominant movement component, the second tactile output is generated by movement of the touch-sensitive surface unit **11904** that includes a second dominant movement component, and the first dominant movement component and the second dominant movement component have a same movement profile and different amplitudes.

In some embodiments, for a first time period during the gesture, the user interface object is over an invalid drop target, for a second time period during the gesture, the user interface object is over a valid drop target, and the processing unit **11906** is configured to: during the first period of time generate an invalid-drop-target tactile output on the touch-sensitive surface unit **11904** (e.g., with the generating unit **11912**), and during the second period of time generate a valid-drop-target tactile output on the touch-sensitive surface unit **11904**, where the invalid-drop-target tactile output is different from the valid-drop-target tactile output (e.g., with the generating unit **11912**).

The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. 1A and 3) or application specific chips.

The operations described above with reference to FIGS. 6A-6B are, optionally, implemented by components depicted in FIGS. 1A-1B or FIG. 7. For example, detection operations **11804**, **11810**, and **11818**, performing operation **11824**, forgoing operation **11830**, and generating operations **11826** and **11832** are, optionally, implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface corresponds to a predefined event or sub-event, such as selection of an object on a user interface. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally utilizes or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. 1A-1B, 3.

#### Performing Operations Based on Modified Inputs

Many electronic devices include a mouse or similar input device that provides left-click functionality and right-click

functionality for activating different operations. As devices economize on the number of buttons and input devices, the left-click functionality and right-click functionality is, optionally, invoked using one input device, such as a trackpad. In existing methods, when either functionality is invoked using the one input device, the user is not given sufficient feedback indicating whether the activated operation was an operation not associated with a modifier input (e.g., a left-click operation) or an operation associated with a modifier input (e.g., a right-click operation). The embodiments below improve on the existing methods by providing different tactile output when device detects an input while a modifier input is detected than when the device detects a similar input while a modifier input is not detected. Thus, the device provides the user with tactile feedback indicating whether or not the modifier input was detected instead of or in addition to any visual or audible feedback indicating that the modifier input was detected. This additional (or alternative) feedback enables the user to operate the device more quickly and efficiently, thereby creating a more efficient human-machine interface.

FIGS. 8A-8V illustrate exemplary user interfaces for providing feedback corresponding to modifier inputs in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIGS. 9A-9B. FIGS. 8A-8V include intensity diagrams that show the current intensity of the contact on the touch-sensitive surface relative to a plurality of intensity thresholds including a first activation threshold (e.g., "IT<sub>L</sub>") and a second activation threshold (e.g., "IT<sub>1</sub>" or "IT<sub>0</sub>"). In some embodiments, operations similar to those described below with reference to "IT<sub>L</sub>" are performed with reference to a different intensity threshold (e.g., "IT<sub>D</sub>").

FIG. 8A illustrates user interface 12000 (e.g., a desktop user interface) displayed on display 450 (e.g., display 340) of a device (e.g., device 300). One or more user interface objects 12002 are, optionally, displayed on user interface 12000. In FIG. 8A, user interface objects 12002-1 through 12002-3 are displayed on user interface 12000. A user interface object 12002 is, optionally, for example, an application shortcut or launch icon.

Cursor 12004 is also displayed on user interface 12000. In some embodiments, cursor 12004 is a mouse pointer. Cursor 12004 is an example of a focus selector. In FIG. 8A, cursor 12004 is displayed over user interface object 12002-2.

The device includes one or more sensors that detect the intensity of contacts with touch-sensitive surface 451 (e.g., touchpad 355) of the device. In FIG. 8A, the intensity of contact 12006 is detected to be below a first activation threshold (e.g., "IT<sub>L</sub>").

The intensity of a contact (e.g., contact 12006) on touch-sensitive surface 451 is, optionally, increased or decreased by, for example, the user increasing or decreasing, respectively, the pressure on touch-sensitive surface 451 with the contact. The change in intensity of the contact is, optionally, detected by the sensors in the device.

In FIG. 8B, the device detects an increase in intensity of contact 12006 above the first activation threshold. In some situations, after detecting the increase in intensity of contact 12006, a decrease in the intensity of contact 12006 (e.g., a liftoff of contact 12006 from touch-sensitive surface 451) below a second activation threshold (e.g., "IT<sub>1</sub>") is detected by the intensity sensors in the device. In some embodiments, the first activation threshold and the second activation threshold are different and the second activation threshold is lower than the first activation threshold (e.g., the

first activation threshold is "IT<sub>L</sub>" and the second activation threshold is "IT<sub>1</sub>" or, alternatively, "IT<sub>0</sub>"). In some other embodiments, the first activation threshold and the second activation threshold are the same (e.g., the first activation threshold is "IT<sub>L</sub>" and the second activation threshold is also "IT<sub>L</sub>").

In response to the detection of the decrease in intensity of contact 12006 below the second activation threshold (e.g., "IT<sub>1</sub>"), after detection of the increase in the intensity of contact 12006 above the first activation threshold (e.g., "IT<sub>L</sub>"), one or more operations associated with user interface object 12002-2, over which cursor 12004 is positioned, are, optionally, performed. In some embodiments, the operation(s) include displaying a new application window associated with user interface object 12002-2. For example, if user interface object 12002-2 is an icon (e.g., an application launch or shortcut icon) corresponding to an application, window 12008 for the corresponding application is, optionally, displayed on user interface 12000, as shown in FIG. 8C.

In some embodiments, user interface object 12002-2 is visually highlighted in response to the detection of the increase then decrease in intensity, or in response to the detection of the increase in intensity. Examples of visual highlighting include a different color or thicker borders (as shown in FIG. 8C).

Additionally, in response to detection of the decrease in the intensity of contact 12006 below the second activation threshold, after detection of the increase in the intensity of contact 12006 above the first activation threshold, a tactile output is generated on touch-sensitive surface 451. The tactile output is, optionally, generated in accordance with a movement profile (e.g., movement profiles illustrated in FIGS. 8P-8Q) and/or an amplitude.

Returning to FIG. 8A, the intensity of contact 12006 is, optionally, increased above the first activation threshold concurrently with the detection of a modifier input. An example of a modifier input is a key press of a key (e.g., on a keyboard) assigned to be a modifier key. A key on keyboard 12011 (e.g., keyboard 350) is, optionally, pre-assigned to be a modifier key (e.g., as a default) or assigned by a user. FIG. 8D shows key press 12012 on key 12010 of keyboard 12011 concurrent with detection of an increase in the intensity of contact 12006 above the first activation threshold. After concurrent detection of the increase in the intensity of contact 12006 above the first activation threshold (e.g., "IT<sub>L</sub>") and of key press 12012 on key 12010, the intensity of contact 12006 is decreased below a second activation threshold (e.g., "IT<sub>1</sub>"), as shown in FIG. 8E (at which point continued pressing of key 12010 is optional). In response to detecting the decrease in the intensity of contact 12006 below the second activation threshold, after concurrent detection of the increase in the intensity of contact 12006 above the first activation threshold and key press 12012 of key 12010, an operation different from that performed when no modifier input is detected is performed. For example, FIG. 8E shows context menu 12014 displayed on user interface 12000 near cursor 12004 in response to the detection of the decrease in the intensity of contact 12006 below the second activation threshold, after concurrent detection of the increase in the intensity of contact 12006 above the first activation threshold and press 12012 of key 12010. The operation of displaying context menu 12014 is different from the operation of displaying application window 12008 (FIG. 8C) that was performed in response to detection of the decrease in the intensity of contact 12006 below the second activation threshold, after detection of the increase in the intensity of contact 12006 above the first

activation threshold without concurrent detection of a press of key **12010**. Context menu **12014** includes menu options associated with user interface object **12002-2**, over which cursor **12004** is positioned, such as “rename,” “properties,” and so on. The menu options include options for performing operations on or with respect to user interface object **12002-2**.

Another example of a modifier input is an additional contact that is detected on touch-sensitive surface **451** concurrently with contact **12006**. FIG. **8F** shows contact **12016** detected on touch-sensitive surface **451** concurrently with the detection of an increase in the intensity of contact **12006** above the first activation threshold (e.g., “ $IT_L$ ”) and a subsequent decrease in the intensity of contact **12006** below the second activation threshold (e.g., “ $IT_1$ ”), as shown in FIG. **8G**. In response to detection of the decrease in the intensity of contact **12006** below the second activation threshold, after concurrent detection of the increase in the intensity of contact **12006** above the first activation threshold and contact **12016**, context menu **12014** is displayed on user interface **12000**, as shown in FIG. **8G**.

A further example of a modifier input is detection of the contact **12006** at a specific area on touch-sensitive surface **451**, as opposed to an arbitrary location on touch-sensitive surface **451** outside of the specific area on the touch-sensitive surface. FIG. **8H** shows contact **12006** detected in area **12018** on touch-sensitive surface **451**, at an intensity below the first activation threshold. An increase in the intensity of contact **12006** in area **12018** above the first activation threshold (e.g., “ $IT_L$ ”) is detected, as shown in FIG. **8I**. Then, a decrease in the intensity of contact **12006** in area **12018** below the second activation threshold (e.g., “ $IT_L$ ”) is detected, as shown in FIG. **8J**. In response to detection of the decrease in the intensity of contact **12006** in area **12018** below the second activation threshold, after detection of the increase in the intensity of contact **12006** in area **12018** above the first activation threshold, context menu **12014** is displayed on user interface **12000**, as shown in FIG. **8J**. Here, intensity of contact **12006** in a defined area (e.g., area **12018**) on touch-sensitive surface **451** modified the input of contact **12006**.

In some embodiments, the defined area (e.g., area **12018**) on touch-sensitive surface **451** for modifying the input is predefined, or it is, optionally, defined by the user (e.g., from a predefined set of choices). Further, it should be appreciated that the size and location of area **12018** as shown in FIGS. **8H-8J** are merely an illustrative example, and other sizes and/or locations for area **12018** are possible.

Additionally, in response to detection of the decrease in the intensity of contact **12006** below the second activation threshold (e.g., “ $IT_1$ ”), after concurrent detection of the increase in the intensity of contact **12006** above the first activation threshold (e.g., “ $IT_L$ ”) and a modifier input (e.g., press **12012** of modifier key **12010**, contact **12016**, detecting contact **12006** in area **12018** on touch-sensitive surface **451**), a tactile output (e.g., a “modifier-active tactile output”) is generated on touch-sensitive surface **451**. This tactile output (e.g., a “modifier-active tactile output”) corresponds to a different tactile sensation from the tactile sensation corresponding to a tactile output (e.g., a “no-modifier tactile output”) generated in response to detection of the decrease in intensity of contact **12006** below the second activation threshold without detection of a modifier input when the increase in intensity of contact **12006** above the first activation threshold is detected, as illustrated in FIGS. **8A-8C**.

Thus, when an increase in the intensity of contact **12006** above the first activation threshold and a subsequent

decrease in the intensity of contact **12006** below the second activation threshold are detected, the operation that is performed depends on whether a modifier input is detected while the increase in intensity above the first activation threshold is detected. In some embodiments, the operation(s) performed in response to detection of the intensity decrease, after detection of the intensity increase without a modifier input, correspond to operations associated with a left-click of a mouse (or similar input device), and the operation(s) performed in response to detection of the intensity decrease, after detection of the intensity increase with a modifier input, correspond to operations associated with a right-click of a mouse (or similar input device). Left-click operations include, for example, activating an application launch or shortcut icon, displaying an application window corresponding to an application associated with an icon, selecting an icon or other user interface object, and so on. Right-click operations include, for example, displaying a context menu (e.g., context menu **12014** or **12024**).

In some other embodiments, the association is, optionally, reversed; the operation(s) performed in response to detection of the intensity decrease, after detection of the intensity increase without a modifier input, correspond to operations associated with a right-click of a mouse (or similar input device), and the operation(s) performed in response to detection of the intensity decrease, after detection of the intensity increase with a modifier input, correspond to operations associated with a left-click of a mouse (or similar input device).

Further, the tactile output that is generated in response to the detection of the decrease in the intensity of contact **12006**, after detection of the increase in the intensity of contact **12006**, depends on the detection of, or lack of, a modifier input along with the detection of the intensity increase. In some embodiments, the tactile output generated when a modifier input is detected (e.g., a “modifier-active tactile output”) is different from the tactile output generated when no modifier input is detected (e.g., a “no-modifier tactile output”) in amplitude, movement profile, or both.

In some embodiments, the operation that is performed, if any, in response to detection of the decrease in intensity of a contact after detection of the increase in intensity of the contact depends on the position of the focus selector (e.g., cursor **12004**) when the increase in intensity is detected, as well as whether a modifier input was detected. In the examples described above with reference to FIGS. **8A-8J**, cursor **12004** is positioned over user interface object **12002-2**. FIG. **8K** shows cursor **12004** positioned over “empty space” on user interface **12000**, away from user interface objects **12002**. Contact **12020** is detected on touch-sensitive surface **451** at an intensity less than the first activation threshold (e.g., “ $IT_L$ ”). In FIG. **8L**, the device detects an increase in intensity of contact **12020** above the first activation threshold (e.g., “ $IT_L$ ”). Then, the device detects a decrease in intensity of contact **12020** below the second activation threshold (e.g., “ $IT_1$ ”), as shown in FIG. **8M**. In response to the decrease of the intensity below the second activation threshold, no operation is performed. In some embodiments, left-clicks that occur when the focus selector is over empty space are ignored, and thus contact **12020** that increases and decreases in intensity with no modifier input while cursor **12004** is over empty space does not cause the device to perform an operation.

On the other hand, FIG. **8N** shows a modifier input (e.g., contact **12022**) detected concurrently with detection of an increase of the intensity of contact **12020** above the first activation threshold. Subsequently, the device detects a

decrease in intensity of contact **12020** below the second activation threshold (e.g., “ $IT_1$ ”), as shown in FIG. **8O**. In response to the decrease of the intensity below the second activation threshold, context menu **12024** is displayed on user interface **12000**. Context menu **12024** optionally includes different options than context menu **12014** (FIG. **8E**, **8G**, or **8J**), as the context is changed by the positioning of cursor **12004** over empty space on user interface **12000** instead of user interface object **12002-2**. In some embodiments, right-clicks that occur when the focus selector is over empty space activate displaying of a context menu, and thus contact **12020** that increases and decreases in intensity with a modifier input while cursor **12004** is over empty space cause the device to display a context menu (e.g., context menu **12024**).

As described above, different tactile outputs are, optionally, generated depending on whether a modifier input was detected. FIGS. **8P-8Q** illustrate example waveforms of movement profiles for generating these tactile outputs. FIG. **8P** illustrates dominant movement components of two different tactile outputs with two different movement profiles (e.g., a sawtooth waveform on the left and a square waveform on the right). In some embodiments, one of the movement profiles (e.g., the sawtooth waveform) corresponds to a tactile output (e.g., a “modifier-active tactile output”) for an increase and subsequent decrease in intensity detected while a modifier input is detected; and the other movement profile (e.g., the square waveform) corresponds to a tactile output (e.g., a “no-modifier tactile output”) for an increase and subsequent decrease in intensity detected without detecting a modifier input. FIG. **8Q** illustrates dominant movement components of two different tactile outputs with two different amplitudes (e.g., a high amplitude square waveform on the left and a low amplitude square waveform on the right). In some embodiments, one of the amplitudes (e.g., the high amplitude square waveform) corresponds to a tactile output (e.g., a “modifier-active tactile output”) for an increase and subsequent decrease in intensity detected while a modifier input is detected; and the other amplitude (e.g., the low amplitude square waveform) corresponds to a tactile output (e.g., a “no-modifier tactile output”) for an increase and subsequent decrease in intensity detected without detecting a modifier input. In some embodiments both the amplitude and the movement profile of the tactile output are selected in accordance with a determination as to on whether or not the modifier input was detected when the device detected the increase prior to detecting the subsequent decrease in intensity of the contact.

FIGS. **8R-8V** illustrate an example of the user interfaces described above, with reference to FIGS. **8A-8Q**, implemented on a device (e.g., device **100**) with a touch-sensitive display **112**. FIG. **8R** shows user interface **12054** and user interface objects **12052** displayed in user interface **12054**, on touch-sensitive display **112** of a device. User interface objects **12052** are similar to user interface objects **12002** described above; the details are not repeated here.

FIG. **8R** also shows contact **12056** detected on user interface object **12052-2**. Contact **12056** as shown in FIG. **8R** has an intensity that is below the first activation threshold (e.g., “ $IT_L$ ”). An increase of the intensity of contact **12056** above the first activation threshold is detected, as shown in FIG. **8S**. After the detection of the increase, a decrease in the intensity of contact **12056** below the second activation threshold (e.g., “ $IT_1$ ”) is detected, as shown in FIG. **8T**.

In response to the detection of the decrease in intensity of contact **12056** below the second activation threshold, after detection of the increase in the intensity of contact **12056**

above the first activation threshold, one or more operations associated with user interface object **12052-2**, over which contact **12056** is detected, are, optionally, performed. For example, if user interface object **12052-2** is an icon (e.g., an application launch or shortcut icon) corresponding to an application, window **12058** for the corresponding application is displayed in user interface **12054**, as shown in FIG. **8T**.

Additionally, in response to detection of the decrease in the intensity of contact **12056** below the second activation threshold, after detection of the increase in the intensity of contact **12056** above the first activation threshold, a tactile output (e.g., a “no-modifier tactile output”) is generated on touch-sensitive display **112**. The tactile output is, optionally, generated in accordance with a movement profile (e.g., movement profiles illustrated in FIGS. **8P-8Q**).

Returning to FIG. **8R**, the intensity of contact **12056** is, optionally, increased above the first activation threshold concurrently with the detection of a modifier input. An example of a modifier input is an additional contact that is detected on touch-sensitive display **112** concurrently with contact **12056**. FIG. **8U** shows contact **12060** detected on touch-sensitive display **112** concurrently with the detection of an increase in the intensity of contact **12056** above the first activation threshold (e.g., “ $IT_L$ ”). Then, a decrease in the intensity of contact **12056** below the second activation threshold (e.g., “ $IT_1$ ”) is detected, as shown in FIG. **8V**. In response to detection of the decrease in the intensity of contact **12056** below the second activation threshold, after concurrent detection of the increase in the intensity of contact **12056** above the first activation threshold and contact **12060**, context menu **12062**, which is similar to context menu **12014** is displayed in user interface **12054**, as shown in FIG. **8V**. In some embodiments, additional contact **12060** is determined to be a modifier input when contact **12060** is detected in a predefined region (e.g., a region in the top right, top left, bottom right, or bottom left corner) of touch-sensitive display **112**.

Additionally, in response to detecting the decrease in the intensity of contact **12056** below the second activation threshold, after concurrent detection of the increase in the intensity of contact **12056** above the first activation threshold and a modifier input (e.g., contact **12060**), the device generates a tactile output (e.g., a “modifier-active tactile output”) on touch-sensitive display **112**. In some embodiments, this tactile output (e.g., a “modifier-active tactile output”) corresponds to a different tactile sensation from the tactile sensation corresponding to a tactile output (e.g., a “no-modifier tactile output”) generated in response to detection of the decrease in intensity of contact **12056** below the second activation threshold without detection of a modifier input when the increase in intensity of contact **12056** above the first activation threshold is detected.

FIGS. **9A-9B** are flow diagrams illustrating a method **12100** of providing feedback corresponding to modifier inputs in accordance with some embodiments. The method **12100** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1A**) with a display and a touch-sensitive surface. In some embodiments, the display is a touch screen display and the touch-sensitive surface is on the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method **12100** are, optionally, combined and/or the order of some operations is, optionally, changed.

As described below, the method **12100** provides an intuitive way to perform operations based on modified inputs. The method reduces the cognitive burden on a user when

providing feedback corresponding to modifier inputs, thereby creating a more efficient human-machine interface. For battery-operated electronic devices, enabling a user to perform operations based on modified inputs faster and more efficiently conserves power and increases the time between battery charges.

The device detects (12102) a contact (e.g., a finger contact) on the touch-sensitive surface. For example, contact 12006 (FIG. 8A or 8H) or 12020 (FIG. 8K) is, optionally, detected on touch-sensitive surface 451. As another example, contact 12056 is, optionally, detected on touch-sensitive display 112.

The device detects (12104) an increase in intensity of the contact above a first activation threshold (e.g., “ $IT_L$ ”). In some embodiments, the first activation threshold is an “increasing-intensity” activation threshold that indicates a threshold at which a tactile output is generated when the intensity of the contact is increasing. The intensity of contact 12006, for example, is, optionally, increased from a level below the first activation threshold (e.g., FIGS. 8A and 8H) to a level above the first activation threshold (e.g., FIG. 8B, 8D, 8F, or 8I), and the increase is detected. Similarly, the intensity of contact 12020 is, optionally, increased from a level below the first activation threshold to a level above the first activation threshold (FIGS. 8K-8L, 8N). As another example, the intensity of contact 12056 is, optionally, increased from a level below the first activation threshold to a level above the first activation threshold (FIGS. 8R-8S, 8U).

After detecting the increase in intensity of the contact above the first activation threshold, the device detects (12106) a reduction in intensity of the contact below a second activation threshold (e.g., “ $IT_1$ ”). In some embodiments, the second activation threshold is a “decreasing-intensity” activation threshold that indicates a threshold at which a tactile output is generated when the intensity of the contact is decreasing. The intensity of contact 12006, for example, is, optionally, decreased to a level below the second activation threshold (e.g., FIG. 8C, 8E, 8G, or 8J), and the increase is detected. Similarly, the intensity of contact 12020 is, optionally, decreased to a level below the second activation threshold (FIGS. 8M, and 8O). As another example, the intensity of contact 12056 is, optionally, decreased to a level below the second activation threshold (FIGS. 8T, and 8V).

In some embodiments, the second activation threshold is (12108) different from the first activation threshold (e.g., the first activation threshold is “ $IT_L$ ” and the second activation threshold is “ $IT_1$ ”). In some embodiments, the second activation threshold is (12110) the same as the first activation threshold (e.g., the first activation threshold is “ $IT_L$ ” and the second activation threshold is also “ $IT_L$ ”).

In response to detecting the reduction in intensity of the contact below the second activation threshold (12112), in accordance with a determination that a modifier input was detected while detecting the increase in intensity of the contact above the first activation threshold (12114), the device performs a first operation (12116) and generates (12118) a first tactile output on the touch-sensitive surface. For example, in FIG. 8D, modifier key 12010 is pressed when the increase in intensity of contact 12006 is detected. When the decrease in the intensity of contact 12006 is detected (FIG. 8E), context menu 12014 is displayed and a first tactile output (e.g., a “modifier-active tactile output”) is generated in response. Similar results occur with other examples of modifier inputs (for example, contact 12016, FIG. 8G; contact 12006 in area 12018, FIG. 8J; contact

12022, FIG. 8O). As another example, in FIG. 8U, additional contact 12060 is detected when the increase in intensity of contact 12056 is detected. When the decrease in the intensity of contact 12056 is detected (FIG. 8V), context menu 12062 is displayed and a first tactile output (e.g., a “modifier-active tactile output”) is generated in response. In some embodiments, the combination of the intensity increase-decrease and the modifier input is associated with a right-click of a mouse or similar input device; the combination activates operations associated with the right-click.

In some embodiments, the modifier input is (12120) an input selected from the set consisting of: a key press of a modifier key, an additional contact on the touch-sensitive surface, and detecting the contact on a predefined portion of the touch-sensitive surface designated to modify inputs (e.g., a predefined “right click” region on a touchpad or a predefined region of a touch-sensitive mouse that corresponds to a “right mouse button”). The modifier input is, optionally, for example, press 12012 of modifier key 12010 (FIG. 8D), additional contact 12016 (FIG. 8F) or 12022 (FIG. 8N) or 12060 (FIG. 8U), or intensity of contact 12006 in area 12018 on touch-sensitive surface 451.

In response to detecting (12112) the reduction in intensity of the contact below the second activation threshold (e.g., “ $IT_1$ ”), in accordance with a determination that the modifier input was not detected (12122) while detecting the increase in intensity of the contact above the first activation threshold (e.g., “ $IT_L$ ”), the device performs (12124) second operation different from the first operation and generates (12126) a second tactile output (e.g., a “no-modifier tactile output”) on the touch-sensitive surface, where the second tactile output is different from the first tactile output. For example, in FIG. 8B, there is no modifier input when the increase in intensity of contact 12006 is detected, and thus when the decrease in the intensity of contact 12006 is detected (FIG. 8C), window 12008 is displayed and a second tactile output (e.g., a “no-modifier tactile output”) is generated in response. As another example, in FIG. 8S, there is no modifier input when the increase in intensity of contact 12056 is detected, and thus when the decrease in the intensity of contact 12056 is detected (FIG. 8T), window 12058 is displayed and a second tactile output (e.g., a “no-modifier tactile output”) is generated in response. In some embodiments, the combination of the intensity increase-decrease and the lack of a modifier input is associated with a left-click of a mouse or similar input device; the combination activates operations associated with the left-click.

In some embodiments, the first operation corresponds (12128) to a right-click operation (e.g., an operation corresponding to clicking on the rightmost button of a two or three button mouse or trackpad, sometimes called a “right-click mouse operation”), and the second operation corresponds to a left-click operation (e.g., an operation corresponding to clicking on the leftmost button of a two or three button mouse or trackpad, sometimes called a “left-click mouse operation”). For example, the displaying of context menu 12014 or 12024 or 12062 is a right-click operation, and the displaying of window 12008 (FIG. 8C) is a left-click operation.

In some embodiments, the contact is detected on the touch-sensitive surface while a focus selector is over an icon on the display, the first operation includes (12130) displaying a context menu that includes selectable options to perform operations associated with the icon, and the second operation includes displaying a new application window associated with the icon (e.g., launching an application or, if the application has already been launched, opening a new

window of the application that includes a document associated with the icon). For example, in FIGS. 8A-8J, contact 12006 is detected on touch-sensitive surface 451 while cursor 12004 is displayed over user interface object 12002-2. When there is no modifier input detected, window 12008 of an application associated with user interface object 12002-2 is displayed, as shown in FIG. 8C. When a modifier input is detected, context menu 12014 is displayed, as shown in FIGS. 8E, 8G, and 8J. Context menu 12014 includes selectable options to perform operations associated with user interface object 12002-2. Analogously, in FIGS. 8R-8V, contact 12056 is detected over user interface object 12052-2 on touch-sensitive display 112. When there is no modifier input detected, window 12058 of an application associated with user interface object 12052-2 is displayed, as shown in FIG. 8T. When a modifier input is detected, context menu 12062 is displayed, as shown in FIG. 8V. Context menu 12062 includes selectable options to perform operations associated with user interface object 12052-2.

In some embodiments, the first tactile output is (12132) generated by movement of the touch-sensitive surface that includes a first dominant movement component (e.g., movement corresponding to the initial impulse, ignoring any unintended resonance), the second tactile output is generated by movement of the touch-sensitive surface that includes a second dominant movement component, and the first dominant movement component and the second dominant movement component have a same movement profile (e.g., same waveform shape such as square, sine, squine, sawtooth, triangle, or approximately the same width/period) and different amplitudes, as shown in FIG. 8Q. Thus, in some embodiments, the tactile outputs with and without the modifier input optionally differs in amplitude rather than in the movement profile, so that one tactile sensation is a stronger version of the other tactile sensation. In contrast, in some embodiments, the tactile output (e.g., a “modifier-active tactile output”) generated when a modifier input was detected and the tactile output (e.g., a “no-modifier tactile output”) generated when a modifier input was not detected both have respective dominant movement components that have different respective movement profiles (for example, the movement profiles depicted in FIG. 8P) with either the same maximum amplitude or different maximum amplitudes.

It should be understood that the particular order in which the operations in FIGS. 9A-9B have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., those listed in the fifth paragraph of the Description of Embodiments) are also applicable in an analogous manner to method 12100 described above with respect to FIGS. 9A-9B. For example, the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, and focus selectors described above with reference to method 12100 optionally has one or more of the characteristics of the contacts, gestures, user interface objects, tactile outputs, intensity thresholds, and focus selectors described herein with reference to other methods described herein (e.g., those listed in the fifth paragraph of the Description of Embodiments). For brevity, these details are not repeated here.

In accordance with some embodiments, FIG. 10 shows a functional block diagram of an electronic device 12200

configured in accordance with the principles of the various described embodiments. The functional blocks of the device are, optionally, implemented by hardware, software, or a combination of hardware and software to carry out the principles of the various described embodiments. It is understood by persons of skill in the art that the functional blocks described in FIG. 10 are, optionally, combined or separated into sub-blocks to implement the principles of the various described embodiments. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

As shown in FIG. 10, an electronic device 12200 includes a display unit 12202, a touch-sensitive surface unit 12204 configured to receive contacts, one or more sensor units 12205 configured to detect intensity of contacts with the touch-sensitive surface unit 12204, and a processing unit 12206 coupled to the display unit 12202, the touch-sensitive surface unit 12204 and the sensor units 12205. In some embodiments, the processing unit 12206 includes a detecting unit 12208, a performing unit 12210, and a generating unit 12212.

The processing unit 12206 is configured to: detect a contact on the touch-sensitive surface unit 12204 (e.g., with the detecting unit 12208); detect an increase in intensity of the contact above a first activation threshold (e.g., with the detecting unit 12208); after detecting the increase in intensity of the contact above the first activation threshold, detect a reduction in intensity of the contact below a second activation threshold (e.g., with the detecting unit 12208); and in response to detecting the reduction in intensity of the contact below the second activation threshold: in accordance with a determination that a modifier input was detected while detecting the increase in intensity of the contact above the first activation threshold: perform a first operation (e.g., with the performing unit 12210) and generate a first tactile output on the touch-sensitive surface unit 12204 (e.g., with the generating unit 12212); and in accordance with a determination that the modifier input was not detected while detecting the increase in intensity of the contact above the first activation threshold: perform a second operation different from the first operation (e.g., with the performing unit 12210) and generate a second tactile output on the touch-sensitive surface unit 12204, wherein the second tactile output is different from the first tactile output (e.g., with the generating unit 12212).

In some embodiments, the modifier input is an input selected from the set consisting of: a key press of a modifier key, an additional contact on the touch-sensitive surface unit 12204, and detection of the contact on a predefined portion of the touch-sensitive surface unit 12204 designated to modify inputs.

In some embodiments, the first operation corresponds to a right-click operation, and the second operation corresponds to a left-click operation.

In some embodiments, the contact is detected on the touch-sensitive surface unit 12204 while a focus selector is over an icon on the display unit 12202, the first operation includes displaying a context menu that includes selectable options to perform operations associated with the icon, and the second operation includes displaying a new application window associated with the icon.

In some embodiments, the second activation threshold is different from the first activation threshold.

In some embodiments, the second activation threshold is the same as the first activation threshold.

In some embodiments, the first tactile output is generated by movement of the touch-sensitive surface unit **12204** that includes a first dominant movement component, the second tactile output is generated by movement of the touch-sensitive surface unit **12204** that includes a second dominant movement component, and the first dominant movement component and the second dominant movement component have a same movement profile and different amplitudes.

The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. **1A** and **3**) or application specific chips.

The operations described above with reference to FIGS. **9A-9B** are, optionally, implemented by components depicted in FIGS. **1A-1B** or FIG. **10**. For example, detection operations **12102**, **12104**, and **12106**, performing operations **12116** and **12124**, and generating operations **12118** and **12126** are, optionally, implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface corresponds to a predefined event or sub-event, such as selection of an object on a user interface. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally utilizes or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1A-1B**.

#### Providing Feedback for Changing Activation States of a User Interface

Many electronic devices have graphical user interfaces that include user interface objects, such as virtual buttons and switches. In some circumstances, a user activates a user interface object to perform an operation or adjust a parameter or property. To make a virtual button or switch easier to use, the virtual object optionally mimics the behavior of the corresponding physical object. For example, haptic sensations are, in some circumstances, felt when a virtual switch is operated, with the haptic sensations mimicking the sensations of the corresponding physical switch, such as mimicking the clicks of a physical actuator mechanism (e.g., a mouse button) that activates the switch. But physical objects, such as real buttons and switches, will, in some circumstances provide excessive tactile feedback in some circumstances, and too little feedback in others. In such situations, a virtual object that just mimicked sensations of the corresponding physical object would also provide too much (or too little) feedback. But a virtual object does not have to be provided with haptic feedback that just mimics tactile sensations from the corresponding physical object. The embodiments described below provide tactile feedback that corresponds to changes in activation states of a virtual button, switch or other user interface object, rather than

tactile feedback that corresponds 1:1 to tactile sensations that would be felt by a user when using a physical control to perform similar operations. When tactile sensations are provided for activation state changes of the virtual button or switch, the user can better discern the activation state of the virtual button without being distracted or confused by too much or too little tactile feedback. This improved haptic feedback for virtual objects enables the user to operate the device more quickly and efficiently, thereby creating a more efficient human-machine interface.

FIGS. **11A-11N** illustrate exemplary user interfaces for providing feedback for changing activation states of a user interface object in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIGS. **12A-12B**. FIGS. **11A-11N** include intensity diagrams that show the current intensity of the contact on the touch-sensitive surface relative to a plurality of intensity thresholds including a light press intensity threshold (e.g., “ $IT_L$ ”) and a deep press intensity threshold (e.g., “ $IT_D$ ”). In some embodiments, operations similar to those described below with reference to “ $IT_L$ ” and “ $IT_D$ ” are performed with reference to different intensity thresholds.

FIG. **11A** illustrates an example of a user interface that includes one or more user interface objects. Image editor user interface **12300** is displayed on display **450** (e.g., display **340**) of a device (e.g., device **300**). Image **12302** is displayed in image editor user interface **12300** for editing in accordance with user commands. One or more user interface objects (for example, buttons, sliders, rocker switches) optionally include control user interface objects such as rocker switches **12304** and status user interface objects such as value indicators **12306** displayed in image editor user interface **12300**. The user interface objects in FIG. **11A-11G** are configured to enable a user to issue commands for editing image **12302** and the user interface objects in FIG. **11H-11N** are configured to enable a user to issue commands for editing image **12322**. For example, one or more rocker switches **12304**, for modifying respective parameters of image **12302**, are displayed in image editor user interface **12300**. Values representing respective parameters are, optionally, displayed in respective value indicators **12306**. Rocker switch **12304-1** enables a user to modify the brightness of image **12302**, for example, and the brightness value (for example, represented by integers, with 0 as the middle value between the upper and lower bounds) is displayed in value indicator **12306-1**. Clearly, a middle value of 0 is merely exemplary. For example, an upper bound of 100 and a lower bound of 0 would have a middle value of 50 (not shown), etc. Cursor **12308** is also displayed in user interface **12300**. In some embodiments, cursor **12308** is a mouse pointer. Cursor **12308** is an example of a focus selector.

A respective rocker switch **12304** optionally has a “minus” portion for reducing the value of a parameter associated with the rocker switch, indicated by the minus sign, and a “plus” portion for increasing the value of a parameter associated with the rocker switch, indicated by a plus sign. A rocker switch **12304** is, optionally, activated when a focus selector (e.g., cursor **12308**) is positioned over a portion of the rocker switch and an intensity of a contact associated with the focus selector changes. In some embodiments, the corresponding value decreases or increases depending on the portion over which the focus selector is positioned. When the focus selector is positioned over the “minus” portion, the corresponding value decreases when the rocker switch is activated. When the focus selector is positioned over the “plus” portion, the corresponding value

increases when the rocker switch is activated. In FIG. 11A, cursor 12308 is positioned over the “minus” portion of rocker switch 12304-1.

While rocker switch 12304-1 is not activated, rocker switch 12304-1 is displayed in a neutral position, as shown in FIG. 11A. When rocker switch 12304-1 is activated, rocker switch 12304-1 is displayed as if either the “minus” portion (if cursor 12308 is positioned over the “minus” portion when rocker switch 12304-1 is activated, thus rocker switch 12304-1 is activated to decrease the value) or the “plus” portion (if cursor 12308 is positioned over the “plus” portion when rocker switch 12304-1 is activated, thus rocker switch 12304-1 is activated to increase the value) is depressed, as shown in FIG. 11B (for the “minus” portion being depressed) and FIG. 11E (for the “plus” portion being depressed), respectively. In some embodiments, when rocker switch 12304-1 is activated, an animation showing a transition of rocker switch 12304-1 from the neutral position to either depressed position is displayed; and when rocker switch 12304-1 is deactivated, an animation showing a transition of rocker switch 12304-1 from either depressed position to the neutral position is displayed.

FIG. 11A shows contact 12310 detected on touch-sensitive surface 451 (e.g., touchpad 355) of the device at an intensity that is above a contact detection threshold (e.g., “ $IT_0$ ”) and below a light press intensity threshold (e.g., “ $IT_L$ ”) for activating rocker switch 12304-1. While contact 12310 continues to be detected on touch-sensitive surface 451 and cursor 12308 is positioned over the “minus” portion of rocker switch 12304-1, the intensity of contact 12310 is, in some circumstances, increased to a first intensity that is above the light press intensity threshold (e.g., “ $IT_L$ ”) for activating rocker switch 12304-1, and the increase in intensity is detected, as shown in FIG. 11B. In response to the detection of the increase in intensity, rocker switch 12304-1 is activated and the brightness value in value indicator 12306-1 decreases. The brightness of image 12302 changes in accordance with the change in the brightness value. In some embodiments, the brightness value decreases at a relatively slow rate (e.g., -1 in value per second). In some embodiments, rocker switch 12304-1 is animated to show the “minus” portion being depressed. In some embodiments, the brightness value continues to decrease as long as the intensity of contact 12310 does not decrease below the light press intensity threshold (e.g., “ $IT_L$ ”).

The intensity of contact 12310 is, in some circumstances, increased further. While contact 12310 continues to be detected on touch-sensitive surface 451 and cursor 12308 is still positioned over the “minus” portion of rocker switch 12304-1, the device detects an increase in intensity of contact 12310 from the first intensity (e.g., an intensity between  $IT_L$  and  $IT_D$ ) to a second, higher intensity that is above a deep press intensity threshold (e.g., “ $IT_D$ ”). In response to this increase in intensity, rocker switch 12304-1 changes to a further activation state, as shown in FIG. 11C where the portion of the rocker switch under focus selector 12308 is pushed “into” the display, and the brightness value of image 12302 decreases at a rate that is faster (e.g., -10 per second) than the rate of decrease at the first intensity, and the brightness of image 12302 changes in accordance with the change in the brightness value, as shown in FIG. 11C.

The intensity of contact 12310 is, in some circumstances, then decreased below the light press intensity threshold (e.g., “ $IT_L$ ”) quickly (e.g., from the second intensity above  $IT_D$  to an intensity below  $IT_L$  in 0.05 seconds or less). In response to the detection of the decrease in intensity below the light press intensity threshold (e.g., “ $IT_L$ ”), the bright-

ness value stops changing, and the brightness of image 12302 stops changing, as shown in FIG. 11D. Depending on the rate at which the intensity decreased from the second intensity to an intensity below the light press intensity threshold (e.g., “ $IT_L$ ”), the brightness value optionally stops changing immediately in response to the detection of the intensity decrease, or the rate of change in the brightness value optionally first decreases to a slower rate (e.g., the rate at the first intensity) before the brightness values stops changing.

Rocker switch 12304-1 includes multiple activation states. In some embodiments, the activation states for rocker switch 12304-1 are different brightness levels as the brightness value changes. In some embodiments, when the brightness value is decreasing at the “slow” rate (e.g., -1 per second), each brightness value increment based on the rate of decrease (e.g., -1, -2, -3, so forth) is considered to be an activation state, and when the brightness value is decreasing at the “fast” rate (e.g., -10 per second), each brightness value increment based on the rate of decrease (e.g., each -10th increment) is considered to be an activation state. In some of these embodiments, at each activation state, a tactile output is, optionally, generated on touch-sensitive surface 451. For example, when the value decreases from -1 to -2, then to -3 and then to -13, tactile outputs are, optionally, generated at -2, -3, and -13.

In some other embodiments, the activation states are the different rates at which the brightness value changes. For example, the “slow” rate is one activation state, the “fast” rate is another activation state, and cessation of activation of rocker switch 12304-1 (e.g., a rate of 0 per second) is another activation state of the rocker switch. A tactile output is, optionally, generated whenever the rate of decrease or increase for the brightness value changes or when rocker switch 12304-1 is activated or ceases to be activated. For example, when the brightness value is not changing, rocker switch 12304-1 is in a first (“neutral”) activation state; when the brightness value is decreasing at the “slow” rate (e.g., -1 per second), rocker switch 12304-1 is in a second (“light press”) activation state; and when the brightness value is decreasing at the “fast” rate (e.g., -10 per second), rocker switch 12304-1 is in a third (“deep press”) activation state. At each activation state, a tactile output is, optionally, generated on touch-sensitive surface 451. For example, when the activation state changes from the first (“neutral”) activation state shown in FIG. 11A to the second (“light press”) activation state shown in FIG. 11B, the device generates a tactile output corresponding to the change in activation state. As another example, when the activation state changes from the second (“light press”) activation state shown in FIG. 11B to the third (“deep press”) activation state shown in FIG. 11C, the device generates a tactile output corresponding to the change in activation state.

In some embodiments, the tactile output generated in response to a change in activation state optionally varies depending on whether the change in activation state was in response to an increase or a decrease in the intensity of contact 12310. A tactile output generated for an activation state change in response to an increase in intensity is, optionally, different from a tactile output generated for an activation state change in response to a decrease in intensity. The tactile outputs are, optionally, different in movement profile, amplitude, or both. In some embodiments, a tactile output generated for an activation state change in response to an increase in intensity corresponds to a tactile sensation that simulates a down-click (e.g., press-and-hold) of a physical button (e.g., a mouse button), and a tactile output

generated for an activation state change in response to a decrease in intensity corresponds to a tactile sensation that simulates an up-click (e.g., release from a press-and-hold) of a physical button.

Returning to FIG. 11D, cursor **12308** has been moved (e.g., from location **12308-a** to location **12308-b**) to the “plus” portion of rocker switch **12304-1** (e.g., in accordance with movement of contact **12310** across touch-sensitive surface **451** while contact **12310** has an intensity between  $IT_0$  and  $IT_L$  from location **12310-a** to location **12310-b** in FIG. 11D). The intensity of contact **12310** is increased to the second intensity quickly (e.g., the intensity of contact **12310-b** increases from an intensity below the  $IT_L$  in FIG. 11D to the second intensity that is above  $IT_D$  in FIG. 11E in 0.05 seconds or less), as shown in FIG. 11E. In response to the increase in intensity, the brightness value increases at the “fast” rate (e.g., +10 per second). As shown in FIG. 11D, rocker switch **12304-1** is in the neutral activation state and transitions directly to the deep press activation state in FIG. 11E in response to a rapid increase in intensity of contact **12310** to an intensity above  $IT_D$ .

As shown in FIG. 11F, the intensity of contact **12310** is subsequently decreased from the second intensity (e.g., an intensity above  $IT_D$ ) to the first intensity (e.g., an intensity between  $IT_L$  and  $IT_D$ ). In response to detecting the intensity decrease to the first intensity, the brightness value increases at the “slow” rate (e.g., +1 per second), as shown in FIG. 11F and rocker switch **12304-1** is shown in the light press activation state.

As shown in FIG. 11G, the intensity of contact **12310** is subsequently decreased further, from the first intensity (e.g., an intensity between  $IT_L$  and  $IT_D$ ) to an intensity below the light press intensity threshold (e.g., “ $IT_L$ ”). In response to the further decrease in intensity of contact **12310**, the brightness value stops increasing (e.g., the rate of change becomes 0 per second), as shown in FIG. 11G and rocker switch **12304-1** is shown in the neutral activation state.

As described above, the activation states of rocker switch **12304-1** optionally correspond to the increments of change in the value, in accordance with the rate of change, or the different rates of change. A tactile output is, optionally, generated whenever one activation state changes to another (e.g., one increment to the next or one rate of change to the next).

FIGS. 11H-11N illustrate an example of the user interfaces described above, with reference to FIGS. 11A-11G, implemented on a device (e.g., device **100**) with a touch-sensitive display **112**. FIG. 11H illustrates image editor user interface **12328** displayed on touch-sensitive display **112** of a device. Image **12322** is displayed in image editor user interface **12328** for editing in accordance with user commands. One or more user interface objects (for example, buttons, sliders, rocker switches) optionally include control user interface objects such as rocker switches **12324** and status user interface objects such as value indicators **12326** displayed in image editor user interface **12328**. The user interface objects in FIGS. 11H-11N are configured to enable a user to issue commands for editing image **12322**. For example, one or more rocker switches **12324**, for modifying respective parameters of image **12322**, are displayed in image editor user interface **12328**. Values representing respective parameters are, optionally, displayed in respective value indicators **12326**. Rocker switch **12324-1** enables a user to modify the brightness of image **12322** in accordance with changes in intensity of contact **12330** while a focus selector is over rocker switch **12324-1**, for example, and the brightness value (for example, represented by inte-

gers, with 0 as the middle value between the upper and lower bounds) is displayed in value indicator **12326-1**. Contact **12330** is an example of a focus selector.

A respective rocker switch **12324** optionally has a “minus” portion for reducing the value of a parameter associated with the rocker switch, indicated by the minus sign, and a “plus” portion for increasing the value of a parameter associated with the rocker switch, indicated by a plus sign. A rocker switch **12324** is, optionally activated when a contact is positioned over a portion of the rocker switch and an intensity of a contact associated with the focus selector changes. In some embodiments, the corresponding value decreases or increases depending on the portion over which the contact is positioned. When the contact is positioned over the “minus” portion, the corresponding value decreases when the rocker switch is activated. When the contact is positioned over the “plus” portion, the corresponding value increases when the rocker switch is activated. In FIG. 11H, contact **12330** is positioned over the “minus” portion of rocker switch **12324-1**.

While rocker switch **12324-1** is not activated, rocker switch **12324-1** is displayed in a neutral position, as shown FIG. 11H. When rocker switch **12324-1** is activated, rocker switch **12324-1** is displayed as if either the “minus” portion (if contact **12330** is positioned over the “minus” portion when rocker switch **12324-1** is activated, thus rocker switch **12324-1** is activated to decrease the value) or the “plus” portion (if contact **12330** is positioned over the “plus” portion when rocker switch **12324-1** is activated, thus rocker switch **12324-1** is activated to increase the value) is depressed, as shown in FIG. 11I (for the “minus” portion being depressed) and FIG. 11L (for the “plus” portion being depressed), respectively. In some embodiments, when rocker switch **12324-1** is activated, an animation showing a transition of rocker switch **12324-1** from the neutral position to either depressed position is displayed; and when rocker switch **12324-1** is deactivated, an animation showing a transition of rocker switch **12324-1** from either depressed position to the neutral position is displayed.

FIG. 11H shows contact **12330** detected on touch-sensitive display **112** at an intensity that is above a contact detection threshold (e.g., “ $IT_0$ ”) and below a light press intensity threshold (e.g., “ $IT_L$ ”) for activating rocker switch **12324-1**. While contact **12330** continues to be detected on touch-sensitive display **112** over the “minus” portion of rocker switch **12324-1**, the intensity of contact **12330** is, in some circumstances, increased to a first intensity that is above the light press intensity threshold (e.g., “ $IT_L$ ”) for activating rocker switch **12324-1**, and the increase in intensity is detected, as shown in FIG. 11I. In response to the detection of the increase in intensity, rocker switch **12324-1** is activated and the brightness value in value indicator **12326-1** decreases. The brightness of image **12322** changes in accordance with the change in the brightness value. In some embodiments, the brightness value decreases at a relatively slow rate (e.g., -1 in value per second). In some embodiments, rocker switch **12324-1** is animated to show the “minus” portion being depressed. In some embodiments, the brightness value continues to decrease as long as the intensity of contact **12330** does not decrease below the light press intensity threshold (e.g., “ $IT_L$ ”).

The intensity of contact **12330** is, in some circumstances, increased further. While contact **12330** continues to be detected on touch-sensitive display **112** over the “minus” portion of rocker switch **12324-1**, the device detects an increase in intensity of contact **12330** from the first intensity (e.g., an intensity between  $IT_L$  and  $IT_D$ ) to a second, higher

intensity that is above a deep press intensity threshold (e.g., “ $IT_D$ ”). In response to this increase in intensity, rocker switch **12324-1** changes to a further activation state, as shown in FIG. **11J** where the portion of the rocker switch under contact **12330** is pushed “into” the display, and the brightness value of image **12322** decreases at a rate that is faster (e.g.,  $-10$  per second) than the rate of decrease at the first intensity, and the brightness of image **12322** changes in accordance with the change in the brightness value, as shown in FIG. **11J**.

The intensity of contact **12330** is, in some circumstances, then decreased below the light press intensity threshold (e.g., “ $IT_L$ ”) quickly (e.g., from the second intensity above  $IT_D$  to an intensity below  $IT_L$  in 0.05 seconds or less). In response to the detection of the decrease in intensity below the light press intensity threshold (e.g., “ $IT_L$ ”), the brightness value stops changing, and the brightness of image **12322** stops changing, as shown in FIG. **11K**. Depending on the rate at which the intensity decreased from the second intensity to an intensity below the light press intensity threshold (e.g., “ $IT_L$ ”), the brightness value optionally stops changing immediately in response to the detection of the intensity decrease, or the rate of change in the brightness value optionally first decreases to a slower rate (e.g., the rate at the first intensity) before the brightness values stops changing.

Rocker switch **12324-1** includes multiple activation states. In some embodiments, the activation states for rocker switch **12324-1** are different brightness levels as the brightness value changes. In some embodiments, when the brightness value is decreasing at the “slow” rate (e.g.,  $-1$  per second), each brightness value increment based on the rate of decrease (e.g.,  $-1$ ,  $-2$ ,  $-3$ , so forth) is considered to be an activation state, and when the brightness value is decreasing at the “fast” rate (e.g.,  $-10$  per second), each brightness value increment based on the rate of decrease (e.g., each  $-10$ th increment) is considered to be an activation state. In some of these embodiments, at each activation state, a tactile output is, optionally, generated on touch-sensitive display **112**. For example, when the value decreases from  $-1$  to  $-2$ , then to  $-3$  and then to  $-13$ , tactile outputs are, optionally, generated at  $-2$ ,  $-3$ , and  $-13$ .

In some other embodiments, the activation states are the different rates at which the brightness value changes. For example, the “slow” rate is one activation state, the “fast” rate is another activation state, and cessation of activation of rocker switch **12324-1** (e.g., a rate of 0 per second) is another activation state. A tactile output is, optionally, generated whenever the rate of decrease or increase for the brightness value changes or when rocker switch **12324-1** is activated or ceases to be activated. For example, when the brightness value is not changing, rocker switch **12324-1** is in a first (“neutral”) activation state; when the brightness value is decreasing at the “slow” rate (e.g.,  $-1$  per second), rocker switch **12324-1** is in a second (“light press”) activation state; and when the brightness value is decreasing at the “fast” rate (e.g.,  $-10$  per second), rocker switch **12324-1** is in a third (“deep press”) activation state. At each activation state, a tactile output is, optionally, generated on touch-sensitive display **112**. For example, when the activation state changes from the first (“neutral”) activation state shown in FIG. **11H** to the second (“light press”) activation state shown in FIG. **11I**, the device generates a tactile output corresponding to the change in activation state. As another example, when the activation state changes from the second (“light press”) activation state shown in FIG. **11I** to the third (“deep press”)

activation state shown in FIG. **11J**, the device generates a tactile output corresponding to the change in activation state.

In some embodiments, the tactile output generated in response to a change in activation state optionally varies depending on whether the change in activation state was in response to an increase or a decrease in the intensity of contact **12330**. A tactile output generated for an activation state change in response to an increase in intensity is, optionally, different from a tactile output generated for an activation state change in response to a decrease in intensity. The tactile outputs is, optionally, different in movement profile, amplitude, or both. In some embodiments, a tactile output generated for an activation state change in response to an increase in intensity corresponds to a tactile sensation that simulates a down-click (e.g., press-and-hold) of a physical button (e.g., a mouse button), and a tactile output generated for an activation state change in response to a decrease in intensity corresponds to a tactile sensation that simulates an up-click (e.g., release from a press-and-hold) of a physical button.

Returning to FIG. **11K**, contact **12330** has been moved (e.g., from location **12330-a** to location **12330-b** while contact **12330** has an intensity between  $IT_0$  and  $IT_L$ ) to the “plus” portion of rocker switch **12324-1**. The intensity of contact **12330** is increased to the second intensity quickly (e.g., the intensity of contact **12330** increases from an intensity below  $IT_L$  of contact **12330-b** in FIG. **11K** to the second intensity that is above  $IT_D$  in FIG. **11L** in 0.05 seconds or less), as shown in FIG. **11L**. In response to the increase in intensity, the brightness value increases at the “fast” rate (e.g.,  $+10$  per second). As shown in FIG. **11K**, rocker switch **12324-1** is in the neutral activation state and transitions directly to the deep press activation state in FIG. **11L** in response to a rapid increase in intensity of contact **12330** to an intensity above  $IT_D$ .

As shown in FIG. **11M**, the intensity of contact **12330** is subsequently decreased from the second intensity (e.g., an intensity above  $IT_D$ ) to the first intensity (e.g., an intensity between  $IT_L$  and  $IT_D$ ). In response to detecting the intensity decrease to the first intensity, the brightness value increases at the “slow” rate (e.g.,  $+1$  per second), as shown in FIG. **11M** and rocker switch **12324-1** is shown in the light press activation state.

As shown in FIG. **11N**, the intensity of contact **12330** is subsequently decreased further, from the first intensity (e.g., an intensity between  $IT_L$  and  $IT_D$ ) to an intensity below the light press intensity threshold (e.g., “ $IT_L$ ”). In response to the further decrease in intensity of contact **12330**, the brightness value stops increasing (e.g., the rate of change becomes 0 per second), as shown in FIG. **11N**, and rocker switch **12324-1** is shown in the neutral activation state.

As described above, the activation states of rocker switch **12324-1** optionally correspond to the increments of change in the value, in accordance with the rate of change, or the different rates of change. A tactile output is, optionally, generated whenever one activation state changes to another (e.g., one increment to the next or one rate of change to the next).

FIGS. **12A-12B** are flow diagrams illustrating a method **12400** of providing feedback for changing activation states of a user interface object in accordance with some embodiments. The method **12400** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1A**) with a display and a touch-sensitive surface. In some embodiments, the display is a touch screen display and the touch-sensitive surface is on the display. In some embodiments, the display is separate from the touch-

sensitive surface. Some operations in method **12400** are, optionally, combined and/or the order of some operations is, optionally, changed.

As described below, the method **12400** provides a more efficient way to provide feedback when changing activation states of a user interface object. The method reduces the cognitive burden on a user when changing activation states of a user interface object, thereby creating a more efficient human-machine interface. For battery-operated electronic devices, enabling a user to change activation states of a user interface object faster and more efficiently conserves power and increases the time between battery charges.

The device displays (**12402**) a user interface object on the display, where the user interface object has a plurality of activation states. FIG. **11A**, for example, shows rocker switches **12304**, for adjusting parameters of an image, displayed in image editor user interface **12300** on a display **450** that is separate from a touch-sensitive surface **451** on which contacts are detected. As another example, FIG. **11H** shows rocker switches **12324**, for adjusting parameters of an image, displayed in image editor user interface **12328** on a touch-sensitive display **112** on which contacts are detected. A respective rocker switch **12304** or **12324** has multiple activation states, which are, optionally, the increments of change in the corresponding parameter value or the rates of change in the parameter value (e.g., a neutral activation state, a light press activation state and a deep press activation state).

The device detects (**12404**) a contact (e.g., a finger contact) on the touch-sensitive surface. As shown in FIG. **11A**, for example, contact **12310** is detected on touch-sensitive surface **451**. As another example, FIG. **11H** shows contact **12330** detected on touch-sensitive display **112**.

The device detects (**12406**) an increase of intensity of the contact on the touch-sensitive surface from a first intensity (e.g., an intensity between  $IT_L$  and  $IT_D$ ) to a second intensity (e.g., an intensity above  $IT_D$ ). FIGS. **11A-11C** shows an increase in the intensity of contact **12310** from an intensity below a light press intensity threshold (e.g., " $IT_L$ ") for activating rocker switch **12304-1**, to a first intensity that is higher than the light press intensity threshold (e.g., " $IT_L$ "), and then to a second intensity that is higher than the first intensity. As another example, in FIGS. **11D-11E**, the device detects an increase in the intensity of contact **12310**, from an intensity below the light press intensity threshold (e.g., " $IT_L$ "), quickly (e.g., intensity increases from the below-threshold intensity to the second intensity in 0.05 seconds or less) to a second intensity that is higher than the first intensity. In FIGS. **11H-11J**, the device detects an increase in the intensity of contact **12330** from an intensity below a light press intensity threshold (e.g., " $IT_L$ ") for activating rocker switch **12324-1**, to a first intensity that is higher than the light press intensity threshold (e.g., " $IT_L$ "), and then to a second intensity that is higher than the first intensity. As another example, in FIGS. **11K-11L**, the device detects an increase in the intensity of contact **12330**, from an intensity below the light press intensity threshold (e.g., " $IT_L$ "), quickly (e.g., intensity increases from the below-threshold intensity to the second intensity in 0.05 seconds or less) to a second intensity that is higher than the first intensity.

In response to detecting the increase in intensity (**12408**), the device changes (**12410**) activation states of the user interface object  $M$  times, where  $M$  is a positive integer, and generates (**12412**) a tactile output on the touch-sensitive surface corresponding to each change in activation state of the user interface object. For example, in FIG. **11A-11C** or **11H-11J**, in response to the detection of the increase in

intensity from below the light press intensity threshold (e.g., " $IT_L$ ") to the first intensity (e.g., an intensity between  $IT_L$  and  $IT_D$ ) and then to the second intensity (e.g., an intensity above  $IT_D$ ), the rocker switch changes from a neutral activation state (corresponding to no change in brightness of the image) to a light press activation state (corresponding to a slow rate of change in brightness of the image) and then to a deep press activation state (corresponding to a fast rate of change in brightness of the image). Here, the activation state (in this case, the rate of change) changes two times, and two tactile outputs are generated.

As another example, in FIG. **11D-11E** or **11K-11L**, in response to the detection of the rapid increase in intensity from below the light press intensity threshold (e.g., " $IT_L$ ") to the second intensity (e.g., an intensity above  $IT_D$ ), the rocker switch changes from the neutral activation state (corresponding to no change in brightness of the image) to the deep press activation state (corresponding to a fast rate of change in brightness of the image), skipping the light press activation state (corresponding to a slow rate of change in brightness of the image). Here, the activation state (in this case, the rate of change) changes once, and one tactile output is generated, even though the device has detected a change in intensity of the contact that has the same magnitude as the change in intensity of contact **12310** between FIGS. **11A** and **11C**.

In some embodiments, the user interface object has a first appearance in a first activation state; the user interface object has a second appearance, different from the first appearance, in a second activation state; and in response to detecting the increase in intensity, the device displays (**12414**) an animation of the user interface object transitioning from the first appearance to the second appearance. Rocker switch **12304-1** appears in a plurality of activation states in FIGS. **11A-11G**, for example, rocker switch **12304-1** appears in a neutral position when the rate of change is 0 (e.g., rocker switch **12304-1** is in a neutral activation state as shown in FIGS. **11A**, **11D** and **11G**) and appears with either the "minus" portion or the "plus" portion depressed when the rate is non-zero (e.g., rocker switch **12304-1** is in a light press activation state as shown in FIGS. **11B** and **11F** or in a deep press activation state as shown in FIGS. **11C** and **11E**). When rocker switch **12304-1** is activated or deactivated (e.g., the rate of change changes), an animation showing a transition from the neutral position to a depressed position, or vice versa, respectively, is, optionally, displayed. Rocker switch **12324-1** appears in a plurality of activation states in FIGS. **11H-11N**, for example, rocker switch **12324-1** appears in a neutral position when the rate of change is 0 (e.g., rocker switch **12324-1** is in a neutral activation state as shown in FIGS. **11H**, **11K** and **11N**) and appears with either the "minus" portion or the "plus" portion depressed when the rate is non-zero (e.g., rocker switch **12324-1** is in a light press activation state as shown in FIGS. **11I** and **11M** or in a deep press activation state as shown in FIGS. **11J** and **11L**). When rocker switch **12324-1** is activated or deactivated (e.g., the rate of change changes), an animation showing a transition from the neutral position to a depressed position, or vice versa, respectively, is, optionally, displayed.

The device detects (**12416**) a decrease of intensity of the contact from the second intensity to the first intensity. As shown in FIGS. **11C-11D**, for example, a quick decrease in the intensity of contact **12310** from the second intensity to below the light press intensity threshold (e.g., " $IT_L$ ") is detected. As another example, in FIGS. **11E-11G**, a decrease in the intensity of contact **12310** from the second intensity

to the first intensity and then to below the light press intensity threshold (e.g., “IT<sub>L</sub>”) is detected. As further examples, in FIGS. 11J-11K, for example, a quick decrease in the intensity of contact 12330 from the second intensity to below the light press intensity threshold (e.g., “IT<sub>L</sub>”) is detected. In FIGS. 11L-11N, a decrease in the intensity of contact 12330 from the second intensity to the first intensity and then to below the light press intensity threshold (e.g., “IT<sub>L</sub>”) is detected.

In response to the detection of the decrease in intensity (12418), the device changes (12420) activation states of the user interface object N times, where N is a positive integer, and generates (12424) a tactile output on the touch-sensitive surface corresponding to each change in activation state of the user interface object, where N is different from M. For example, in FIGS. 11C-11D or FIGS. 11J-11K, in response to the detection of the decrease in intensity, the rate of change in the brightness value changes from the “fast” rate (e.g., the deep press activation state of rocker switch 12324-1) to 0 (e.g., the neutral activation state of rocker switch 12324-1), and one tactile output is generated, whereas two tactile outputs were generated in response to detecting the increase in intensity in FIGS. 11A-11C and 11H-11J, respectively. As another example, in FIG. 11E-11G or 11L-11N, in response to the detection of the decrease in intensity, the rate of change in the brightness value changes from 0 (e.g., the neutral activation state of rocker switch 12324-1) to the “slow” rate (e.g., the light press activation state of rocker switch 12324-1) and then the “fast” rate (e.g., the deep press activation state of rocker switch 12324-1), and two tactile outputs are generated, whereas just one tactile output was generated in response to detecting the increase in intensity in FIGS. 11D-11E and 11K-11L, respectively.

In some embodiments, a distinct tactile output is a tactile output that was generated to provide feedback corresponding to a user interface event (e.g., a change in the activation state of the user interface object, such as activation of a button or other control). In some embodiments, the touch-sensitive surface is moved by an actuator in accordance with a separate waveform for each user interface event. The waveforms for different user interface events optionally overlap, but a waveform that was generated to provide a tactile feedback for a particular user interface event (e.g., activation of a button or change in activation state of a control such as a rocker switch) will still generate a distinct tactile output. In some embodiments, an activation state of a user interface object corresponds to an operational state of an application on the electronic device, and changing activation states of the user interface object changes operational states of the application. If the user interface object is an adjustable control interface such as a multi-state button, rocker-switch or slider, the activation states of the button/switch/slider are typically displayed by changing the visual appearance of the adjustable control interface (e.g., as a change in shading of a button, a change in rotation of a rocker switch or a change in position of a slider). Additionally, when the activation state of the button/switch/slider is changed, operation of an application associated with the button/switch/slider is changed accordingly. For example, if a rocker switch controls the brightness of an image, the activation states of the rocker switch correspond to different brightness levels of the image, and when the rocker switch changes from a first activation state to a second activation state, the brightness of the image changes from a first brightness level corresponding to the first activation state of the rocker switch to a second brightness level corresponding to the second activation state of the rocker switch. In some

embodiments, activation states correspond to image property levels (e.g., hue, saturation, exposure, brightness, contrast), content navigation states (e.g., channel selection, forward navigation, backward navigation, frame-by-frame navigation), system property adjustments (e.g., volume control, screen brightness, date/time settings), rates of change (e.g., the rate at which an adjustable parameter value increases or decreases, speed of forward or backward seeking through video or audio), or other adjustable properties.

In some embodiments, M is (12424) greater than N. In FIG. 11A-11D or 11H-11K, for example, the number of changes in activation state in response to the detection of the increase in intensity of the contact (e.g., a change from the neutral activation state to the light press activation state and a change from the light press activation state to the deep press activation state shown in FIGS. 11A-11C and 11H-11J) is greater than the number of changes in activation state in response to the detection of the decrease in intensity of the contact (e.g., a change from the deep press activation state to the neutral activation state shown in FIGS. 11C-11D and FIGS. 11J-11K).

In some embodiments, M is (12426) less than N. In FIG. 11D-11G or 11K-11N, for example, the number of changes in activation state in response to the detection of the increase in intensity of the contact (e.g., a change from the neutral activation state to the deep press activation state shown in FIGS. 11D-11E and 11K-11L) is less than the number of changes in activation state in response to the detection of the decrease in intensity of the contact (e.g., a change from the deep press activation state to the light press activation state and a change from the light press activation state to the neutral activation state shown in FIGS. 11E-11G and 11L-11N).

In some embodiments, M is (12428) equal to 1 and N is equal to 2. In FIG. 11D-11G or 11K-11N, for example, there is one change in activation state in response to the detection of the increase in intensity and two changes in activation state in response to the detection of the decrease in intensity.

In some embodiments, M is equal to 2 and N is (12430) equal to 1. In FIG. 11A-11D or 11H-11K, for example, there are two changes in activation state in response to the detection of the increase in intensity and one change in activation state in response to the detection of the decrease in intensity.

In some embodiments, at least one tactile output generated in response to detecting the increase in intensity corresponds (12432) to a tactile sensation that simulates a down-click of a physical actuator mechanism (e.g., a simulation of the physical “down-click sensation” generated by the mechanical button apparatus of a physical button when a user activates the physical button), and at least one tactile output generated in response to detecting the decrease in intensity corresponds to a tactile sensation that simulates an up-click of a physical actuator mechanism (e.g., a simulation of the physical “up-click sensation” generated by the mechanical button apparatus of a physical button when a user activates the physical button). For example, the tactile outputs generated for the activation state changes in response to the detection of the increase in intensity of contact 12310 or 12330 correspond to tactile sensations that simulate a down-click, and the tactile outputs generated for the activation state changes in response to the detection of the decrease in intensity of contact 12310 or 12330 correspond to tactile sensations that simulate an up-click.

While M and N have been discussed herein as positive integers, in some circumstances M is zero (e.g., no activation states of the user interface object are changed in

response to detecting the increase in intensity of the contact) and/or N is zero (e.g., no activation states of the user interface object are changed in response to detecting the decrease in intensity of the contact). Additionally, while M has been described as being different from N, in some circumstances M is equal to N (e.g., the number of activation states that are changed in response to detecting the increase in intensity of the contact is the same as the number of activation states that are changed in response to detecting the decrease in intensity of the contact).

It should be understood that the particular order in which the operations in FIGS. 12A-12B have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., those listed in the fifth paragraph of the Description of Embodiments) are also applicable in an analogous manner to method 12400 described above with respect to FIGS. 12A-12B. For example, the contacts, user interface objects, tactile outputs, intensity thresholds, focus selectors, and animations described above with reference to method 12400 optionally has one or more of the characteristics of the contacts, user interface objects, tactile outputs, intensity thresholds, focus selectors, and animations described herein with reference to other methods described herein (e.g., those listed in the fifth paragraph of the Description of Embodiments). For brevity, these details are not repeated here.

In accordance with some embodiments, FIG. 13 shows a functional block diagram of an electronic device 12500 configured in accordance with the principles of the various described embodiments. The functional blocks of the device are, optionally, implemented by hardware, software, or a combination of hardware and software to carry out the principles of the various described embodiments. It is understood by persons of skill in the art that the functional blocks described in FIG. 13 are, optionally, combined or separated into sub-blocks to implement the principles of the various described embodiments. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

As shown in FIG. 13, an electronic device 12500 includes a display unit 12502 configured to display a user interface object, where the user interface object has a plurality of activation states; a touch-sensitive surface unit 12504 configured to receive contacts; one or more sensor units 12505 configured to detect intensity of contacts with the touch-sensitive surface unit 12504; and a processing unit 12506 coupled to the display unit 12502, the touch-sensitive surface unit 12504, and the sensor units 12505. In some embodiments, the processing unit 12506 includes a detecting unit 12508, a changing unit 12510, a generating unit 12512, and a display enabling unit 12514.

The processing unit 12506 is configured to: detect a contact on the touch-sensitive surface unit 12504 (e.g., with the detecting unit 12508); detect an increase of intensity of the contact on the touch-sensitive surface unit 12504 from a first intensity to a second intensity (e.g., with the detecting unit 12508); in response to detecting the increase in intensity: change activation states of the user interface object M times, where M is a positive integer (e.g., with the changing unit 12510), and generate a tactile output on the touch-sensitive surface unit 12504 corresponding to each change in

activation state of the user interface object (e.g., with the generating unit 12512); detect a decrease of intensity of the contact from the second intensity to the first intensity (e.g., with the detecting unit 12508); and in response to detecting the decrease in intensity: change activation states of the user interface object N times, where N is a positive integer (e.g., with the changing unit 12510), and generate a tactile output on the touch-sensitive surface unit 12504 corresponding to each change in activation state of the user interface object, where N is different from M (e.g., with the generating unit 12512).

In some embodiments, the user interface object has a first appearance in a first activation state, the user interface object has a second appearance, different from the first appearance, in a second activation state, and the processing unit 12506 is configured to: in response to detecting the increase in intensity, enable display of an animation of the user interface object transitioning from the first appearance to the second appearance (e.g., with the display enabling unit 12514).

In some embodiments, M is greater than N.

In some embodiments, M is less than N.

In some embodiments, M is equal to 1 and N is equal to 2.

In some embodiments, M is equal to 2 and N is equal to 1.

In some embodiments, at least one tactile output generated (e.g., with the generating unit 12512) in response to detecting the increase in intensity corresponds to a tactile sensation that simulates a down-click of a physical actuator mechanism, and at least one tactile output generated (e.g., with the generating unit 12512) in response to detecting the decrease in intensity corresponds to a tactile sensation that simulates an up-click of a physical actuator mechanism.

The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. 1A and 3) or application specific chips.

The operations described above with reference to FIGS. 12A-12B are, optionally, implemented by components depicted in FIGS. 1A-1B or FIG. 13. For example, detection operations 12404, 12406, 12416, changing operations 12410, 12420, and generating operations 12412, 12422 are, optionally, implemented by event sorter 170, event recognizer 180, and event handler 190. Event monitor 171 in event sorter 170 detects a contact on touch-sensitive display 112, and event dispatcher module 174 delivers the event information to application 136-1. A respective event recognizer 180 of application 136-1 compares the event information to respective event definitions 186, and determines whether a first contact at a first location on the touch-sensitive surface corresponds to a predefined event or sub-event, such as selection of an object on a user interface. When a respective predefined event or sub-event is detected, event recognizer 180 activates an event handler 190 associated with the detection of the event or sub-event. Event handler 190 optionally utilizes or calls data updater 176 or object updater 177 to update the application internal state 192. In some embodiments, event handler 190 accesses a respective GUI updater 178 to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. 1A-1B.

### Providing Feedback for Changing Activation States of a User Interface Object

Many electronic devices have graphical user interfaces that include user interface objects, such as buttons and switches. In some circumstances, a user activates a user interface object to perform an operation or adjust a parameter or property. In some devices, a tactile sensation is, in some circumstances, perceived by the user for corresponding physical inputs, such as clicks of a physical actuator mechanism (e.g., a mouse button) that activate a switch. To make a virtual button or switch easier to use, the virtual object optionally mimics the behavior of the corresponding physical object. For example, haptic sensations is, in some circumstances, felt when a virtual switch is operated, with the haptic sensations mimicking the sensations of the corresponding physical switch, such as mimicking the clicks of a physical actuator mechanism (e.g., a mouse button) that activates the switch. But physical objects, such as real buttons and switches, provide, in some circumstances, excessive tactile feedback in some situations, and too little feedback in others. In such situations, a virtual object that just mimicked sensations of the corresponding physical object would also provide too much (or too little) feedback. But a virtual object does not have to be provided with haptic feedback that just mimics tactile sensations from the corresponding physical object. The embodiments described below provide tactile feedback that is not tied to actuations of a physical actuator mechanism. For example, tactile sensations related to activation state changes are, optionally, provided. When tactile sensations not tied to physical actuations are provided for, the user can better discern the activation state of the virtual button without being distracted by too much or too little tactile feedback. If a user interface object goes through two or more activation state changes in rapid succession, haptic feedback does not need to be provided for each change in activation state, whereas the corresponding physical object would provide more tactile feedback. Also, the number of times that haptic feedback is provided as a contact increases in intensity does not have to be the same as the number of times that haptic feedback is provided as the contact decreases in intensity. This asymmetry in the number of times that haptic feedback is provided as a contact increases in intensity or decreases in intensity is, in some embodiments, dependent on how rapidly the contact intensity changes, and, in other embodiments, independent of how rapidly the contact intensity changes. This additional (or alternative) feedback enables the user to operate the device more quickly and efficiently, thereby creating a more efficient human-machine interface.

FIGS. 14A-14N illustrate exemplary user interfaces for providing feedback for changing activation states of a user interface object in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIGS. 15A-15C. FIGS. 14A-14N include intensity diagrams that show the current intensity of the contact on the touch-sensitive surface relative to a plurality of intensity thresholds including a light press intensity threshold (e.g., “IT<sub>L</sub>”) and a deep press intensity threshold (e.g., “IT<sub>D</sub>”). In some embodiments, operations similar to those described below with reference to “IT<sub>L</sub>” and “IT<sub>D</sub>” are performed with reference to different intensity thresholds.

FIG. 14A illustrates an example of a user interface that includes one or more user interface objects. Image editor user interface 12600 is displayed on display 450 (e.g., display 340) of a device (e.g., device 300). Image 12602 is

displayed in image editor user interface 12600 for editing in accordance with user commands. One or more user interface objects (for example, buttons, sliders, rocker switches) optionally include control user interface objects such as rocker switches 12604 and status user interface objects such as value indicators 12606 displayed in image editor user interface 12600. The user interface objects in FIGS. 14A-14G are configured to enable a user to issue commands for editing image 12602. For example, one or more rocker switches 12604, for modifying respective parameters of image 12602, are displayed in image editor user interface 12600. Values representing respective parameters are, optionally displayed in respective value indicators 12606. Rocker switch 12604-1 is, optionally, used to modify the brightness of image 12602, for example, and the brightness level (for example, represented by integers, with 0 as the middle value between the upper and lower bounds) is displayed in value indicator 12606-1. Cursor 12608 is also displayed on user interface 12600. In some embodiments, cursor 12608 is a mouse pointer. Cursor 12608 is an example of a focus selector.

A respective rocker switch 12604 optionally has a “minus” portion for reducing the value of a parameter associated with the rocker switch, indicated by the minus sign, and a “plus” portion for increasing the value of a parameter associated with the rocker switch, indicated by a plus sign. A rocker switch 12604 is, optionally, activated when a focus selector (e.g., cursor 12608) is positioned over either portion of the rocker switch and an intensity of a contact associated with the focus selector changes. In some embodiments, the corresponding value decreases or increases depending on the portion over which the focus selector is positioned. When the focus selector is positioned over the “minus” portion, the corresponding value decreases when the rocker switch is activated. When the focus selector is positioned over the “plus” portion, the corresponding value increases when the rocker switch is activated. In FIG. 14A, cursor 12608 is positioned over the “minus” portion of rocker switch 12604-1.

When rocker switch 12604-1 is not activated, rocker switch 12604-1 is displayed in a neutral position, as shown FIG. 14A. When rocker switch 12604-1 is activated, rocker switch 12604-1 is displayed as if either the “minus” portion (if cursor 12608 is positioned over the “minus” portion when rocker switch 12604-1 is activated, thus rocker switch 12604-1 is activated to decrease the value) or the “plus” portion (if cursor 12608 is positioned over the “plus” portion when rocker switch 12604-1 is activated, thus rocker switch 12604-1 is activated to increase the value) is depressed. For example, FIG. 14B shows the “minus” portion of rocker switch 12604-1 being depressed. In some embodiments, when rocker switch 12604-1 is activated, an animation showing a transition of rocker switch 12604-1 from the neutral position to either depressed position is, optionally, displayed; and when rocker switch 12604-1 is deactivated, an animation showing a transition of rocker switch 12604-1 from either depressed position to the neutral position is, optionally, displayed.

FIG. 14A shows contact 12610 detected on touch-sensitive surface 451 (e.g., touchpad 355) of the device at an intensity that is above a contact detection threshold (e.g., “IT<sub>0</sub>”) and below a light press intensity threshold (e.g., “IT<sub>L</sub>”) for activating rocker switch 12604-1. While contact 12610 continues to be detected on touch-sensitive surface 451 and cursor 12608 is positioned over the “minus” portion of rocker switch 12604-1, the intensity of contact 12610 is, in some circumstances, increased to a light press intensity

that is above the light press intensity threshold (e.g., “ $IT_L$ ”) for activating rocker switch **12604-1**, and the increase in intensity is detected, as shown in FIG. 14B. In response to the detection of the increase in intensity, rocker switch **12604-1** is activated and the brightness level in value indicator **12606-1** decreases. The brightness of image **12602** changes in accordance with the change in the brightness level. In some embodiments, the rate of change in the brightness level is a relatively slow rate (e.g., 1 brightness level per time step). In some embodiments, rocker switch **12604-1** is animated to show the “minus” portion being depressed. The brightness level continues to decrease as long as the intensity of contact **12610** does not decrease below the light press intensity threshold (e.g., “ $IT_L$ ”).

The intensity of contact **12610** is, in some circumstances, increased further. While contact **12610** continues to be detected on touch-sensitive surface **451** and cursor **12608** is still positioned over the “minus” portion of rocker switch **12604-1**, the device detects an increase in intensity of contact **12610** from the light press intensity (e.g., an intensity between  $IT_L$  and  $IT_D$ ) to a second, higher intensity that is above a deep press intensity threshold (e.g., “ $IT_D$ ”). In response to this increase in intensity, rocker switch **12604-1** changes to a further activation state, as shown in FIG. 14C where the portion of the rocker switch under focus selector **12608** is pushed “into” the display, and brightness level decreases at a “medium” rate that is faster (e.g., 5 brightness levels per time step) than the rate of change at the light press intensity, and the brightness of image **12602** changes in accordance with the change in the brightness level, as shown in FIG. 14C.

The intensity of contact **12610** is, in some circumstances, increased even further. While contact **12610** continues to be detected on touch-sensitive surface **451** and cursor **12608** is still positioned over the “minus” portion of rocker switch **12604-1**, the intensity of contact **12610** is increased from the first deep press intensity (e.g., an intensity above  $IT_D$  shown in FIG. 14C) to a second deep press intensity (e.g., an intensity above  $IT_D$  shown in FIG. 14D) that is higher than the first deep press intensity. In response to this increase in intensity, rocker switch **12604-1** changes to a further activation state, as shown in FIG. 14D where the portion of the rocker switch under focus selector **12608** is pushed even further “into” the display than shown in FIG. 14C, and brightness level decreases at a “fast” rate that is faster (e.g., 10 brightness levels per time step) than the rate of change at the first deep press intensity, and the brightness of image **12602** changes in accordance with the change in the brightness level, as shown in FIG. 14D.

From the second deep press intensity, the intensity of contact **12610** is, in some circumstances, increased even further. Depending on the implementation, the rate at which the brightness level changes optionally does or does not change further in response to the detection of the increase in intensity, as the rate of change at the second deep press intensity is, optionally, a predefined lower-bound (or upper-bound, for a rate of change where the brightness level increases) rate of change.

The intensity of contact **12610** is, optionally, decreased from the second deep press intensity to the first deep press intensity (e.g., an intensity above  $IT_D$  but below the second deep press intensity). While contact **12610** continues to be detected on touch-sensitive surface **451** and cursor **12608** is still positioned over the “minus” portion of rocker switch **12604-1**, the device detects a decrease in intensity of contact **12610** from the second deep press intensity to the first deep press intensity, as shown in FIG. 14E. In response to this

decrease in intensity, rocker switch **12604-1** continues to be activated, and brightness level decreases at the rate that corresponds to the first deep press intensity (e.g., 5 brightness levels per time unit), and the brightness of image **12602** changes in accordance with the change in the brightness level, as shown in FIG. 14E.

The intensity of contact **12610** is, optionally, further decreased from the first deep press intensity to the light press intensity (e.g., an intensity between  $IT_L$  and  $IT_D$ ). While contact **12610** continues to be detected on touch-sensitive surface **451** and cursor **12608** is still positioned over the “minus” portion of rocker switch **12604-1**, the device detects a decrease in the intensity of contact **12610** from the first deep press intensity to the light press intensity, as shown in FIG. 14F. In response to this decrease in intensity, rocker switch **12604-1** continues to be activated, and brightness level decreases at the rate corresponding to the light press intensity (e.g., 1 brightness level per time unit), and the brightness of image **12602** changes in accordance with the change in the brightness level, as shown in FIG. 14F.

The intensity of contact **12610** is, optionally, further decreased from the light press intensity (e.g., an intensity between  $IT_L$  and  $IT_D$ ) to an intensity below the light press intensity threshold (e.g., “ $IT_L$ ”). While contact **12610** continues to be detected on touch-sensitive surface **451** and cursor **12608** is still positioned over the “minus” portion of rocker switch **12604-1**, the device detects a decrease in intensity of contact **12610** from the light press intensity to an intensity below the light press intensity threshold (e.g., “ $IT_L$ ”), as shown in FIG. 14G. In response to detecting this decrease in intensity, rocker switch **12604-1** is deactivated, and the brightness level stops decreasing, as shown in FIG. 14G. The brightness of image **12602** stops changing in accordance with the brightness level ceasing to decrease.

A user interface object, such as rocker switch **12604-1**, optionally has multiple activation states. For example, the activation states for rocker switch **12604-1** are the different rates at which the brightness level changes. For example, when rocker switch **12604-1** is in a “neutral activation state,” while the contact has an intensity below a light press intensity threshold (e.g., an intensity below  $IT_L$ ), the brightness level is not changing, as shown in FIG. 14A; when rocker switch **12604-1** is in a “light press activation state,” while the contact has the light press intensity (e.g., an intensity between  $IT_L$  and  $IT_D$ ), the brightness level is changing at a slow rate, as shown in FIG. 14B; when rocker switch **12604-1** is in a “first deep press activation state,” while the contact has the first deep press intensity (e.g., an intensity above  $IT_D$ ), the brightness level is changing at a medium rate, as shown in FIG. 14C; and when rocker switch **12604-1** is in a “second deep press activation state,” while the contact has the second deep press intensity (e.g., an intensity above  $IT_D$  that is above the first deep press intensity), the brightness level is changing at a fast rate, as shown in FIG. 14D. Alternatively, the activation states of a rocker switch correspond to values of a parameter (e.g., a first activation state corresponds to 0, a second activation state corresponds to 1, a third activation state corresponds to 2, and so on).

When the intensity of contact **12610** changes, rocker switch **12604-1** optionally changes from the activation state at the starting intensity (e.g., a neutral activation state, as shown in FIG. 14A) to the activation state at the destination intensity (e.g., a second deep press activation state, as shown in FIG. 14D). For example, when the intensity of contact **12610** changes from an intensity below the light press intensity threshold (e.g., “ $IT_L$ ”) to the second deep press

intensity (e.g., an intensity above  $IT_D$  that is above the first deep press intensity), the activation state of rocker switch **12604-1** changes from a rate of 0 brightness levels per time step to a rate of 10 brightness levels per time step. As another example, when the intensity of contact **12610** changes from the second deep press intensity to the first deep press intensity (e.g., as illustrated in FIGS. **14D-14E**), the activation state of rocker switch **12604-1** changes from a rate of 10 brightness levels per time step to 5 brightness levels per time step. Thus, the changes in the rate of change for the brightness level, described above with reference to FIGS. **14A-14G**, are changes in the activation state of rocker switch **12604-1**.

In some embodiments, from the activation state at the starting intensity, rocker switch **12604-1** optionally changes to zero or more intermediate activation states on the way to changing to the activation state at the destination intensity. For example, when the intensity of contact **12610** increases from below the light press intensity threshold (e.g., " $IT_L$ ") to the second deep press intensity, from the activation state at the intensity below the light press intensity threshold (e.g., " $IT_L$ "), rocker switch **12604-1** changes to the activation state at the light press intensity (e.g., corresponding to the light press activation state) and then to the activation state at the first deep press intensity (e.g., corresponding to the first deep press activation state), on the way to changing to the activation state at the second deep press intensity (e.g., the second deep press activation state). The activation states at the first and second intensities (e.g., the light press activation state and the first deep press activation state) are the intermediate activation states between the activation state at the intensity below the light press intensity threshold (e.g., " $IT_L$ ") and the activation state at the second deep press intensity.

In some embodiments, the number of intermediate activation states between a starting activation state and a destination activation state for an increase in intensity is different than the number of intermediate activation states between a starting activation state and a destination activation state for a decrease in intensity. For example, referring back to FIGS. **14A-14G** described above, on the decrease in intensity of contact **12610** shown in FIGS. **14D-14G**, on the way to changing from the rate of change at the second deep press intensity to the rate at the neutral activation state, rocker switch **12604-1** optionally skips either or both of the rates at the light press intensity (e.g., corresponding to the light press activation state) and at the first deep press intensity (e.g., corresponding to the first deep press activation state), while those rates are not skipped on the increase in intensity shown in FIGS. **14A-14D**. In some other embodiments, the intermediate activation states are not skipped, but the transitions to these states is, in some circumstances, not be noticeable to the user because of the speed of the increase or decrease in intensity leads to transitions between activation states in such quick succession that the user will, in some circumstances, perceive the entire activation state sequence as merely a transition from the starting activation state to the destination activation state. In some embodiments, the device is pre-configured to skip intermediate activations states on the increase or decrease in intensity. In some other embodiments, intermediate activation states are skipped if the intensity increases or decreases at a rate that exceeds a threshold (e.g., a rate corresponding to transitioning between the intensity below  $IT_L$  and the intensity above  $IT_D$  in less than 0.5, 0.25, 0.1, 0.05 seconds or some other reasonable amount of time). In the latter case, the user has some control over whether

intermediate activations states are skipped, as the user controls how fast the intensity increases or decreases.

In response to the increase in the intensity of contact **12610**, one or more distinct tactile outputs are, optionally, generated on touch-sensitive surface **451**. For example, as the intensity increases from below the light press intensity threshold (e.g., " $IT_L$ ") to the second deep press intensity, as described above with reference to FIGS. **14A-14D**, one or more distinct tactile outputs are, optionally, generated on touch-sensitive surface **451**. For convenience, the number of tactile outputs generated in response to the detection of the increase in intensity is referred to below as the variable "M."

In response to the decrease in the intensity of contact **12610**, one or more distinct tactile outputs are, optionally, generated on touch-sensitive surface **451**. For example, as the intensity decreases from the second deep press intensity to an intensity below the light press intensity threshold (e.g., " $IT_L$ "), as described above with reference to FIGS. **14D-14G**, one or more distinct tactile outputs are, optionally, generated on touch-sensitive surface **451**. For convenience, the number of distinct tactile outputs generated in response to the detection of the decrease in intensity is referred to below as the variable "N." In some circumstances, M and N are the same and in some circumstances, M and N are different—for example, the number of tactile outputs generated in response to the detection of the decrease in intensity is, in some circumstances, the same as or different than the number of tactile outputs generated in response to the detection of the increase in intensity.

For example, the M tactile outputs are, optionally, tactile outputs generated at increments of the brightness level or increments of the change in brightness level as the brightness level changes in response to the detection of the increase in the intensity of contact **12610**. For example, a tactile output is, optionally, generated at each of the 10's in the brightness level or at each 10th level from the starting level. Similarly, the N tactile outputs are, optionally, tactile outputs generated at increments of the brightness level or increments of the change in brightness level as the brightness level changes in response to the detection of the decrease in intensity of contact **12610**. In this example, the tactile outputs are not necessarily generated in response to transitions in activation state.

In some embodiments, the M or N tactile outputs are generated for changes or transitions in activation state; the tactile outputs mark the changes or transitions in activation state. For example, a tactile output is, optionally, generated at each change in the rate of change in the brightness level as the intensity of contact **12610** increases (e.g., each of the M tactile outputs correspond to respective changes in activation state), and a tactile output is, optionally, generated at each change in the rate of change in the brightness level as the intensity of contact **12610** decreases (e.g., each of the N tactile outputs correspond to respective changes in activation state). In some embodiments, when a change or transition in activation state is skipped or not noticeable to the user (e.g., because the rate of increase or decrease in the intensity of contact **12610** occurs faster than a rate of change threshold), generation of one or more corresponding tactile sensations is, optionally forgone (e.g., the one or more corresponding tactile sensations associated with corresponding changes in activation state are not generated by the device even though the changes in activation state occur).

In some embodiments, a tactile output varies depending on whether the tactile output was generated in response to an increase or a decrease in the intensity of contact **12610**. A tactile output generated in response to detection of an

increase in the intensity of contact **12610** is, optionally, different from a tactile output generated in response to detection of a decrease in the intensity of contact **12610**. The tactile outputs are, optionally, different in movement profile, amplitude, or both. In some embodiments, a tactile output generated in response to detection of an increase in the intensity of contact **12610** corresponds to a tactile sensation that simulates a down-click (e.g., press-and-hold) of a physical button (e.g., a mouse button), and a tactile output generated in response to detection of a decrease in the intensity of contact **12610** corresponds to a tactile sensation that simulates an up-click (e.g., release from a press-and-hold) of the physical button.

FIG. **14H-14N** illustrate an example of the user interfaces described above, with reference to FIGS. **14A-14G**, implemented on a device (e.g., device **100**) with a touch-sensitive display **112**. FIG. **14H** illustrates image editor user interface **12628** displayed on touch-sensitive display **112** of a device. Image **12622** is displayed in image editor user interface **12628** for editing in accordance with user commands. One or more user interface objects (for example, buttons, sliders, rocker switches) optionally include control user interface objects such as rocker switches **12604** and status user interface objects such as value indicators **12606** displayed in image editor user interface **12628**. The user interface objects in FIG. **14H-14N** are configured to enable a user to issue commands for editing image **12622**. For example, one or more rocker switches **12624**, for modifying respective parameters of image **12622**, are displayed in image editor user interface **12628**. Values representing respective parameters are, optionally, displayed in respective value indicators **12626**. Rocker switch **12624-1** is, optionally, used to modify the brightness of image **12622**, for example, and the brightness value (for example, represented by integers, with 0 as the middle value between the upper and lower bounds) is displayed in value indicator **12626-1**.

A respective rocker switch **12624** optionally has a “minus” portion, for reducing the value of a parameter associated with the rocker switch indicated by the minus sign, and a “plus” portion for increasing the value of a parameter associated with the rocker switch, indicated by a plus sign. A rocker switch **12624** is, optionally, activated when a contact is positioned over either portion of the rocker switch and an intensity of a contact associated with the focus selector changes. In some embodiments, the corresponding value decreases or increases depending on the portion over which the contact is positioned. When the contact is positioned over the “minus” portion, the corresponding value decreases when the rocker switch is activated. When the contact is positioned over the “plus” portion, the corresponding value increases when the rocker switch is activated. In FIG. **14H**, contact **12630** is positioned over the “minus” portion of rocker switch **12624-1**.

When rocker switch **12624-1** is not activated, rocker switch **12624-1** is displayed in a neutral position, as shown FIG. **14H**. When rocker switch **12624-1** is activated, rocker switch **12624-1** is displayed as if either the “minus” portion (if contact **12630** is positioned over the “minus” portion when rocker switch **12624-1** is activated, thus rocker switch **12624-1** is activated to decrease the value) or the “plus” portion (if contact **12630** is positioned over the “plus” portion when rocker switch **12624-1** is activated, thus rocker switch **12624-1** is activated to increase the value) is depressed. For example, FIG. **14I** shows the “minus” portion of rocker switch **12624-1** being depressed. In some embodiments, when rocker switch **12624-1** is activated, an animation showing a transition of rocker switch **12624-1** from the

neutral position to either depressed position is, optionally, displayed; and when rocker switch **12624-1** is deactivated, an animation showing a transition of rocker switch **12624-1** from either depressed position to the neutral position is, optionally, displayed.

FIG. **14H** shows contact **12630** detected on touch-sensitive display **112** at an intensity that is above a contact detection threshold (e.g., “ $IT_0$ ”) and below a light press intensity threshold (e.g., “ $IT_L$ ”) for activating rocker switch **12624-1**. While contact **12630** continues to be detected on touch-sensitive display **112** over the “minus” portion of rocker switch **12624-1**, the intensity of contact **12630** is, in some circumstances, increased to a light press intensity that is above the light press intensity threshold (e.g., “ $IT_L$ ”) for activating rocker switch **12624-1**, and the increase in intensity is detected, as shown in FIG. **14I**. In response to the detection of the increase in intensity, rocker switch **12624-1** is activated and the brightness level in value indicator **12626-1** decreases. The brightness of image **12622** changes in accordance with the change in the brightness level. In some embodiments, the rate of change in the brightness level is a relatively slow rate (e.g., 1 brightness level per time step). In some embodiments, rocker switch **12624-1** is animated to show the “minus” portion being depressed. The brightness level continues to decrease as long as the intensity of contact **12630** does not decrease below the light press intensity threshold (e.g., “ $IT_L$ ”).

The intensity of contact **12630** is, in some circumstances, increased further. While contact **12630** continues to be detected on touch-sensitive display **112** over the “minus” portion of rocker switch **12624-1**, the device detects an increase in intensity of contact **12630** from the light press intensity (e.g., an intensity between  $IT_L$  and  $IT_D$ ) to a second, higher intensity that is above a deep press intensity threshold (e.g., “ $IT_D$ ”). In response to this increase in intensity, rocker switch **12624-1** changes to a further activation state, as shown in FIG. **14J** where the portion of the rocker switch under the focus selector (e.g., contact **12630**) is pushed “into” the display, and brightness level decreases at a “medium” rate that is faster (e.g., 5 brightness levels per time step) than the rate of change at the light press intensity, and the brightness of image **12622** changes in accordance with the change in the brightness level, as shown in FIG. **14J**.

The intensity of contact **12630** is, in some circumstances, increased even further. While contact **12630** continues to be detected on touch-sensitive display **112** over the “minus” portion of rocker switch **12624-1**, the intensity of contact **12630** is increased from the first deep press intensity (e.g., an intensity above  $IT_D$ ) shown in FIG. **14J**) to a second deep press intensity (e.g., an intensity above  $IT_D$ ) shown in FIG. **14K**) that is higher than the first deep press intensity. In response to this increase in intensity, rocker switch **12624-1** changes to a further activation state, as shown in FIG. **14K** where the portion of the rocker switch under contact **12630** is pushed even further “into” the display than shown in FIG. **14J**, and brightness level decreases at a “fast” rate that is faster (e.g., 10 brightness levels per time step) than the rate of change at the first deep press intensity, and the brightness of image **12622** changes in accordance with the change in the brightness level, as shown in FIG. **14K**.

From the second deep press intensity, the intensity of contact **12630** is, in some circumstances, increased even further. Depending on the implementation, the rate at which the brightness level changes optionally do or do not change further in response to the detection of the increase in intensity, as the rate of change at the second deep press

intensity is, optionally, a predefined lower-bound (or upper-bound, for a rate of change where the value increases) rate of change.

The intensity of contact **12630** is, optionally, decreased from the second deep press intensity to the first deep press intensity (e.g., an intensity above  $IT_D$ ) but below the second deep press intensity). While contact **12630** continues to be detected on touch-sensitive display **112** over the “minus” portion of rocker switch **12624-1**, the device detects a decrease in intensity of contact **12630** from the second deep press intensity to the first deep press intensity, as shown in FIG. **14L**. In response to this decrease in intensity, rocker switch **12624-1** continues to be activated, and brightness level decreases at the rate that corresponds to the first deep press intensity (e.g., 5 brightness levels per time unit), and the brightness of image **12622** changes in accordance with the change in the brightness level, as shown in FIG. **14L**.

The intensity of contact **12630** is, optionally, further decreased from the first deep press intensity to the light press intensity (e.g., an intensity between  $IT_L$  and  $IT_D$ ). While contact **12630** continues to be detected on touch-sensitive display **112** over the “minus” portion of rocker switch **12624-1**, the device detects a decrease in the intensity of contact **12630** from the first deep press intensity to the light press intensity, as shown in FIG. **14M**. In response to this decrease in intensity, rocker switch **12624-1** continues to be activated, and brightness level decreases at the rate corresponding to at the light press intensity (e.g., 1 brightness level per time unit), and the brightness of image **12622** changes in accordance with the change in the brightness level, as shown in FIG. **14M**.

The intensity of contact **12630** is, optionally, further decreased from the light press intensity (e.g., an intensity between  $IT_L$  and  $IT_D$ ) to an intensity below the light press intensity threshold (e.g., “ $IT_L$ ”). While contact **12630** continues to be detected on touch-sensitive display **112** over the “minus” portion of rocker switch **12624-1**, the device detects a decrease in intensity of contact **12630** from the light press intensity to an intensity below the light press intensity threshold (e.g., “ $IT_L$ ”), as shown in FIG. **14N**. In response to detecting this decrease in intensity, rocker switch **12624-1** is deactivated, and the brightness level stops decreasing, as shown in FIG. **14N**. The brightness of image **12622** stops changing in accordance with the brightness level ceasing to decrease.

A user interface object, such as rocker switch **12624-1**, optionally has multiple activation states. For example, the activation states for rocker switch **12624-1** are the different rates at which the brightness level changes. For example, when rocker switch **12624-1** is in a “neutral activation state,” while the contact has an intensity below a light press intensity threshold (e.g., an intensity below  $IT_L$ ), the brightness level is not changing, as shown in FIG. **14H**; when rocker switch **12624-1** is in a “light press activation state,” while the contact has the light press intensity (e.g., an intensity between  $IT_L$  and  $IT_D$ ), the brightness level is changing at a slow rate, as shown in FIG. **14I**; when rocker switch **12624-1** is in a “first deep press activation state,” while the contact has the first deep press intensity (e.g., an intensity above  $IT_D$ ), the brightness level is changing at a medium rate, as shown in FIG. **14J**; and when rocker switch **12624-1** is in a “second deep press activation state,” while the contact has the second deep press intensity (e.g., an intensity above  $IT_D$  that is above the first deep press intensity), the brightness level is changing at a fast rate, as shown in FIG. **14K**. Alternatively, the activation states of a rocker switch correspond to values of a parameter (e.g., a first

activation state corresponds to 0, a second activation state corresponds to 1, a third activation state corresponds to 2, and so on).

When the intensity of contact **12630** changes, rocker switch **12624-1** optionally changes from the activation state at the starting intensity (e.g., a neutral activation state, as shown in FIG. **14H**) to the activation state at the destination intensity (e.g., a second deep press activation state, as shown in FIG. **14K**). For example, when the intensity of contact **12630** changes from an intensity below the light press intensity threshold (e.g., “ $IT_L$ ”) to the second deep press intensity (e.g., an intensity above  $IT_D$  that is above the first deep press intensity), the activation state of rocker switch **12624-1** changes from a rate of 0 brightness levels per time step to a rate of 10 brightness levels per time step. As another example, when the intensity of contact **12630** changes from the second deep press intensity to the first deep press intensity (e.g., as illustrated in FIGS. **14K-14L**), the activation state of rocker switch **12624-1** changes from a rate of 10 brightness levels per time step to a rate of 5 brightness levels per time step. Thus, the changes in the rate of change for the brightness level, described above with reference to FIGS. **14H-14N**, are changes in the activation state of rocker switch **12624-1**.

In some embodiments, from the activation state at the starting intensity, rocker switch **12624-1** optionally changes to zero or more intermediate activation states on the way to changing to the activation state at the destination intensity. For example, when the intensity of contact **12630** increases from below the light press intensity threshold (e.g., “ $IT_L$ ”) to the second deep press intensity, from the activation state at the intensity below the light press intensity threshold (e.g., “ $IT_L$ ”), rocker switch **12624-1** changes to the activation state at the light press intensity (e.g., corresponding to the light press activation state) and then to the activation state at the first deep press intensity (e.g., corresponding to the first deep press activation state), on the way to changing to the activation state at the second deep press intensity (e.g., the second deep press activation state). The activation states at the first and second intensities (e.g., the light press activation state and the first deep press activation state) are the intermediate activation states between the activation state at the intensity below the light press intensity threshold (e.g., “ $IT_L$ ”) and the activation state at the second deep press intensity.

In some embodiments, the number of intermediate activation states between a starting activation state and a destination activation state for an increase in intensity is different than the number of intermediate activation states between a starting activation state and a destination activation state for a decrease in intensity. For example, referring back to FIGS. **14H-14N** described above, on the decrease in intensity of contact **12630** shown in FIGS. **14K-14N**, on the way to changing from the rate of change at the second deep press intensity to the rate at the neutral activation state, rocker switch **12624-1** optionally skips either or both of the rates at the light press intensity (e.g., corresponding to the light press activation state) and at the first deep press intensity (e.g., corresponding to the first deep press activation state), while those rates are not skipped on the increase in intensity shown in FIGS. **14H-14K**. In some other embodiments, the intermediate activation states are not skipped, but the transitions to these states are, in some circumstances, not be noticeable to the user because of the speed of the increase or decrease in intensity leads to transitions between activation states in such quick succession that the user perceives, in some circumstances, the

entire activation state sequence as merely a transition from the starting activation state to the destination activation state. In some embodiments, the device is pre-configured to skip intermediate activations states on the increase or decrease in intensity. In some other embodiments, intermediate activation states are skipped if the intensity increases or decreases at a rate that exceeds a threshold (e.g., the intensity changes from below the light press intensity threshold to the second deep press intensity in less than a pre-defined amount of time such as 0.05 seconds). In the latter case, the user has some control over whether intermediate activations states are skipped, as the user controls how fast the intensity increases or decreases.

In response to the increase in the intensity of contact **12630**, one or more distinct tactile outputs are, optionally, generated on touch-sensitive display **112**. For example, as the intensity increases from below the light press intensity threshold (e.g., “ $IT_L$ ”) to the second deep press intensity, as described above with reference to FIGS. **14H-14K**, one or more distinct tactile outputs are, optionally, generated on touch-sensitive display **112**. For convenience, the number of tactile outputs generated in response to the detection of the increase in intensity is referred to below as the variable “ $M$ .”

In response to the decrease in the intensity of contact **12630**, one or more distinct tactile outputs are, optionally, generated on touch-sensitive display **112**. For example, as the intensity decreases from the second deep press intensity to an intensity below the light press intensity threshold (e.g., “ $IT_L$ ”), as described above with reference to FIGS. **14K-14N**, one or more distinct tactile outputs are, optionally, generated on touch-sensitive display **112**. For convenience, the number of distinct tactile outputs generated in response to the detection of the decrease in intensity is referred to below as the variable “ $N$ .” In some circumstances,  $M$  and  $N$  are the same and in some circumstances,  $M$  and  $N$  are different—for example, the number of tactile outputs generated in response to the detection of the decrease in intensity is, optionally, the same as or different than the number of tactile outputs generated in response to the detection of the increase in intensity.

For example, the  $M$  tactile outputs are, optionally, tactile outputs generated at increments of the brightness level or increments of the change in brightness level as the brightness level changes in response to the detection of the increase in the intensity of contact **12630**. For example, a tactile output is, optionally, generated at each of the  $10^s$  in the brightness level or at each 10th level from the starting level. Similarly, the  $N$  tactile outputs are, optionally, tactile outputs generated at increments of the brightness level or increments of the change in brightness level as the brightness level changes in response to the detection of the decrease in intensity of contact **12630**. In this example, the tactile outputs are not necessarily generated in response to transitions in activation state.

In some embodiments, the  $M$  or  $N$  tactile outputs are generated for changes or transitions in activation state; the tactile outputs mark the changes or transitions in activation state. For example, a tactile output is, optionally, generated at each change in the rate of change in the brightness level as the intensity of contact **12630** increases (e.g., each of the  $M$  tactile outputs correspond to respective changes in activation state), and a tactile output is, optionally, generated at each change in the rate of change in the brightness level as the intensity of contact **12630** decreases (e.g., each of the  $N$  tactile outputs correspond to respective changes in activation state). In some embodiments, when a change or transition in activation state is skipped or not noticeable to the user (e.g.,

because the rate of increase or decrease in the intensity of contact **12630** occurs faster than a rate of change threshold), generation of one or more corresponding tactile sensations is, optionally, forgone (e.g., the one or more corresponding tactile sensations associated with corresponding changes in activation state are not generated by the device even though the changes in activation state occur).

In some embodiments, a tactile output varies depending on whether the tactile output was generated in response to an increase or a decrease in the intensity of contact **12630**. A tactile output generated in response to detection of an increase in the intensity of contact **12630** is, optionally, different from a tactile output generated in response to detection of a decrease in the intensity of contact **12630**. The tactile outputs are, optionally, different in movement profile, amplitude, or both. In some embodiments, a tactile output generated in response to detection of an increase in the intensity of contact **12630** corresponds to a tactile sensation that simulates a down-click (e.g., press-and-hold) of a physical button (e.g., a mouse button), and a tactile output generated in response to detection of a decrease in the intensity of contact **12630** corresponds to a tactile sensation that simulates an up-click (e.g., release from a press-and-hold) of the physical button.

FIGS. **15A-15C** are flow diagrams illustrating a method **12700** of providing feedback for changing activation states of a user interface object in accordance with some embodiments. The method **12700** is performed at an electronic device (e.g., device **300**, FIG. **3**, or portable multifunction device **100**, FIG. **1A**) with a display and a touch-sensitive surface. In some embodiments, the display is a touch screen display and the touch-sensitive surface is on the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method **12700** are, optionally, combined and/or the order of some operations is, optionally, changed.

As described below, the method **12700** provides an intuitive way to provide feedback for change activation states of a user interface object. The method reduces the cognitive burden on a user when changing activation states of a user interface object, thereby creating a more efficient human-machine interface. For battery-operated electronic devices, enabling a user to change activation states of a user interface object faster and more efficiently conserves power and increases the time between battery charges.

The device displays (**12702**) a user interface object on the display, where the user interface object has a first activation state and a second activation state. FIG. **14A**, for example, shows rocker switches **12604**, for adjusting parameters of an image, displayed in image editor user interface **12600**. A respective rocker switch **12604** has at least two activation states (e.g., a neutral activation state, a light press activation state, a first deep press activation state and/or a second deep press activation state), which optionally include various rates of change in the parameter value. As another example, FIG. **14H** shows rocker switches **12624** displayed in image editor user interface **12628**. A respective rocker switch **12624** has at least two activation states, which optionally include various rates of change in the parameter value. A respective rocker switch **12624** has at least two activation states (e.g., a neutral activation state, a light press activation state, a first deep press activation state and/or a second deep press activation state).

The device detects (**12704**) a contact (e.g., a finger contact) on the touch-sensitive surface. As shown in FIG. **14A**, for example, contact **12610** is detected on touch-

sensitive surface **451**. Also, as shown in FIG. **14H**, contact **12630** is detected on touch-sensitive display **112**.

The device detects (**12706**) an increase of intensity of the contact on the touch-sensitive surface from a first intensity to a second intensity. FIGS. **14A-14D** show an increase in the intensity of contact **12610** from an intensity below a light press intensity threshold (e.g., “ $IT_L$ ”) for activating rocker switch **12604-1**, to an intensity above a deep press intensity threshold (e.g., “ $IT_D$ ”) and higher than additional intensities (e.g., a light press intensity that is between  $IT_L$  and  $IT_D$ ) that are also above the threshold. FIGS. **14H-14K** shows an increase in the intensity of contact **12630** from an intensity below a light press intensity threshold (e.g., “ $IT_L$ ”) for activating rocker switch **12624-1**, to an intensity above a deep press intensity threshold (e.g., “ $IT_D$ ”) and higher than additional intensities that are also above the threshold (e.g., a light press intensity that is between  $IT_L$  and  $IT_D$ ).

In response to detecting the increase in intensity (**12708**), the device changes (**12710**) activation states of the user interface from the first activation state to the second activation state, and generates (**12712**) M distinct tactile outputs on the touch-sensitive surface, where M is a positive integer. For example, in FIG. **14A-14D** or **14H-14K**, in response to the detection of the increase in intensity from below the light press intensity threshold (e.g., “ $IT_L$ ”) to an intensity above a deep press intensity threshold (e.g., “ $IT_D$ ”), the rate of change in brightness level changes from zero, to a “fast” rate (e.g., 10 brightness levels per time step). The activation state for rocker switch **12604-1** or **12624-1** changes from the activation state corresponding to the zero rate (e.g., the neutral activation state), through zero or more intermediate activation states (e.g., the light press activation state and/or the first deep press activation state), to the activation state corresponding to the “fast” rate (e.g., the second deep press activation state). In response to the detection of the increase in intensity, M tactile outputs are, optionally, generated. The M tactile outputs are, optionally, generated at predefined increments of the brightness level (e.g., whenever the ones digit in the brightness level is 0) or at predefined increments of the change in the brightness level (e.g., every 10th increment from the starting brightness level), as the brightness of the image (e.g., **12602** or **12622**) changes in accordance with the rate of change of brightness level corresponding to the current activation state of rocker switch **12604-1** or **12624-1**.

In some embodiments, the M distinct tactile outputs correspond to changes in activation state of the user interface object (**12714**). The M tactile sensations are, optionally, generated whenever the activation state of rocker switch **12604-1** or **12624-1** (e.g., the rate of change for the brightness level) changes.

In some embodiments, while detecting the increase in intensity of the contact, the device determines (**12716**) a rate at which the intensity of the contact is increasing. In accordance with a determination that the rate at which the intensity of the contact is increasing remains below a predefined threshold (e.g., a rate corresponding to transitioning between the first intensity and the second intensity in less than 0.5, 0.25, 0.1, 0.05 seconds or some other reasonable amount of time), the device generates (**12718**) a distinct tactile output for each transition between activation states that occurs in response to detecting the increase in intensity of the contact. In accordance with a determination that the rate at which the intensity of the contact is increasing exceeds the predefined threshold (e.g., a rate corresponding to transitioning between the first intensity and the second intensity in less than 0.5, 0.25, 0.1, 0.05 seconds or some

other reasonable amount of time), the device forgoes (**12720**) generation of at least one distinct tactile output for a respective transition between activation states that occurs in response to detecting the increase in intensity of the contact. For example, as the intensity of contact **12610** increases from below the light press intensity threshold (e.g., “ $IT_L$ ”) to an intensity above a deep press intensity threshold (e.g., “ $IT_D$ ”), as depicted in FIGS. **14A-14D**, a speed of the intensity increase is, optionally, determined. As another example, as the intensity of contact **12630** increases from below the light press intensity threshold (e.g., “ $IT_L$ ”) to an intensity above a deep press intensity threshold (e.g., “ $IT_D$ ”), as depicted in FIGS. **14H-14K**, a speed of the intensity increase is, optionally, determined. If the speed of the intensity increase is below the predefined threshold, a tactile output is generated for each transition between activation states along the way. If the speed of the intensity increase is above the predefined threshold, generation of one or more of the tactile outputs is, optionally, forgone, for example the tactile outputs corresponding to transitions between intermediate activation states (e.g., a transitions between the light press activation state and the first deep press activation state).

The device detects (**12722**) a decrease of intensity of the contact from the second intensity to the first intensity. As shown in FIGS. **14D-14G**, for example, a decrease in the intensity of contact **12610** from an intensity above a deep press intensity threshold (e.g., “ $IT_D$ ”) to an intensity below the light press intensity threshold (e.g., “ $IT_L$ ”) is detected. As shown in FIGS. **14K-14N**, for example, a decrease in the intensity of contact **12630** from an intensity above a deep press intensity threshold (e.g., “ $IT_D$ ”) to an intensity below the light press intensity threshold (e.g., “ $IT_L$ ”) is detected.

In response to detecting the decrease in intensity (**12724**), the device changes (**12726**) activation states of the user interface object from the second activation state (e.g., the second deep press activation state) to the first activation state (e.g., the neutral activation state), and generates (**12732**) N distinct tactile outputs on the touch-sensitive surface, where N is a positive integer and N is different from M. For example, in FIG. **14D-14G** or **14K-14N**, in response to the detection of the decrease in intensity from an intensity above a deep press intensity threshold (e.g., “ $IT_D$ ”) to an intensity below the light press intensity threshold (e.g., “ $IT_L$ ”), the rate of change in brightness level changes from the “fast” rate (e.g., 10 per time step) to zero. The activation state for rocker switch **12604-1** or **12624-1** changes from the activation state corresponding to the “fast” rate, through zero or more intermediate activation states (e.g., a first deep press activation state and/or a light press activation state), to the activation state corresponding to the zero rate. In response to the detection of the decrease in intensity, N tactile outputs are, optionally, generated. The N tactile outputs are, optionally, generated at predefined increments of the brightness level (e.g., whenever the ones digit in the brightness level is 0), at predefined increments of the change in the brightness level (e.g., every 10th increment from the starting level), or when the brightness start level starts changing and stops changing, as the brightness level changes in accordance with the rate of change corresponding to the current activation state of rocker switch **12604-1** or **12624-1**. In some circumstances N is different from M (e.g., as the brightness level has optionally changed less on the decrease in intensity, or the tactile outputs are, optionally, predefined to be generated at different points than the increments in the level or in the change in level). For example, when the increase in intensity of the contact is below the predefined threshold and the

decrease in intensity of the contact is above the predefined threshold (e.g., a rate corresponding to transitioning between the first intensity and the second intensity in less than 0.5, 0.25, 0.1, 0.05 seconds or some other reasonable amount of time), the device generates tactile outputs corresponding to each the transitions between the neutral activation state, the light press activation state, the first deep press activation state and the second deep press activation state when the intensity of the contact is increasing, but the device generates tactile outputs for only a subset of these transitions (e.g., only the transition between the second deep press activation state and the neutral activation state).

In some embodiments, changing activation states of the user interface object from the first activation state to the second activation state includes transitioning through a first number of intermediate activation states between the first activation state and the second activation state; and changing activation states of the user interface object from the second activation state to the first activation state includes transitioning through a second number of intermediate activation states between the second activation state and the first activation state (12728). For example, in FIG. 14A-14D or 14H-14K, the transition from the neutral activation state to the second deep press activation state includes intermediate transitions to the light press activation state and the first deep press activation state. In FIG. 14D-14G or 14K-14N, the transition from the second deep press activation state to the neutral activation state includes intermediate transitions to the first deep press activation state and the light press activation state.

In some embodiments, the first number of intermediate activation states between the first activation state and the second activation state is different from the second number of intermediate activation states between the second activation state and the first activation state (12730). For example, the increase in intensity of contact 12610 or 12630 is, in some circumstances, at a speed below the predefined threshold, and the decrease in intensity of contact 12610 or 12630 is, in some circumstances, above the predefined threshold, and as a result the intermediate activations states on the decrease in intensity are skipped (e.g., processing the transition between the first deep press activation state and the second deep press activation state shown in FIGS. 14C-14D and skipping the transition between the second deep press activation threshold to the first deep press activation shown in FIGS. 14D-14E).

In some embodiments, the N distinct tactile outputs correspond to changes in activation state of the user interface object (12734). The N tactile sensations are, optionally, generated whenever the activation state of rocker switch 12604-1 or 12624-1 (e.g., the rate of change for the brightness level) changes.

In some embodiments, while detecting the decrease in intensity of the contact, the device determines (12736) a rate at which intensity of the contact is decreasing. In accordance with a determination that the rate at which the intensity of the contact is decreasing remains below a predefined threshold (e.g., a rate corresponding to transitioning between the first intensity and the second intensity in less than 0.5, 0.25, 0.1, 0.05 seconds or some other reasonable amount of time), the device generates (12738) a distinct tactile output for each transition between activation states that occurs in response to detecting the decrease in intensity of the contact. In accordance with a determination that the rate at which the intensity of the contact is decreasing exceeds the predefined threshold, the device forgoes (12740) generation of at least one distinct tactile output for a respective transition between

activation states that occurs in response to detecting the decrease in intensity of the contact. For example, as the intensity of contact 12610 or 12630 decreases from an intensity above a deep press intensity threshold (e.g., "IT<sub>D</sub>") to an intensity below the light press intensity threshold (e.g., "IT<sub>L</sub>"), as depicted in FIG. 14D-14G or 14K-14N, respectively, a speed of the intensity decrease is, optionally, determined. In some embodiments, if the speed of the intensity decrease is below the predefined threshold, a tactile output is generated for each transition between activation states along the way. If the speed of the intensity decrease is above the predefined threshold, generation of one or more of the tactile outputs is, optionally, forgone, for example the tactile outputs corresponding to transitions between intermediate activation states, such as the light press activation state and the first deep press activation state illustrated in FIGS. 14B-14C.

In some embodiments, at least one tactile output generated in response to detecting the increase in intensity of the contact (e.g., 12610 or 12630) corresponds to a tactile sensation that simulates a down-click of a physical actuator mechanism (e.g., a tactile sensation that simulates the physical "down-click sensation" generated by the mechanical button apparatus of a physical button when a user activates the physical button), and at least one tactile output generated in response to detecting the decrease in intensity of the contact (e.g., 12610 or 12630) corresponds to a tactile sensation that simulates an up-click of a physical actuator mechanism (e.g., a tactile sensation that simulates the physical "up-click sensation" generated by the mechanical button apparatus of a physical button when a user activates the physical button).

As used herein, a distinct tactile output is a tactile output that was generated to provide feedback corresponding to a user interface event (e.g., a change in the activation state of the user interface object, such as activation of a button or other control). In some embodiments, the touch-sensitive surface is moved by an actuator in accordance with a separate waveform for each user interface event. The waveforms for different user interface events optionally overlap, but a waveform that was generated to provide a tactile feedback for a particular user interface event (e.g., activation of a button or change in activation state of a control such as a rocker switch) will still generate a distinct tactile output. As used herein, an activation state of a user interface object corresponds to an operational state of an application on the electronic device, and changing activation states of the user interface object changes operational states of the application. If the user interface object is an adjustable control interface such as a multi-state button, rocker-switch or slider, the activation states of the button/switch/slider are typically displayed by changing the visual appearance of the adjustable control interface (e.g., as a change in shading of a button, a change in rotation of a rocker switch or a change in position of a slider). Additionally, when the activation state of the button/switch/slider is changed, operation of an application associated with the button/switch/slider is changed accordingly. For example, if a rocker switch controls the brightness of an image, the activation states of the rocker switch correspond to different brightness levels of the image, and when the rocker switch changes from a first activation state to a second activation state, the brightness of the image changes from a first brightness level corresponding to the first activation state of the rocker switch to a second brightness level corresponding to the second activation state of the rocker switch. In some embodiments, activation states correspond to image property levels (e.g.,

hue, saturation, exposure, brightness, contrast), content navigation states (e.g., channel selection, forward navigation, backward navigation, frame-by-frame navigation), system property adjustments (e.g., volume control, screen brightness, date/time settings), rates of change, and other adjustable properties.

While M and N have been discussed herein as positive integers, in some circumstances M is zero (e.g., tactile outputs are generated in response to detecting the increase in intensity of the contact) and/or N is zero (e.g., no tactile outputs are generated in response to detecting the decrease in intensity of the contact). Additionally, while M has been described as being different from N, in some circumstances M is equal to N (e.g., the number of tactile outputs that are generated in response to detecting the increase in intensity of the contact is the same as the number of tactile outputs that are generated in response to detecting the decrease in intensity of the contact).

It should be understood that the particular order in which the operations in FIGS. 15A-15C have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., those listed in the fifth paragraph of the Description of Embodiments) are also applicable in an analogous manner to method 12700 described above with respect to FIGS. 15A-15C. For example, the contacts, user interface objects, tactile outputs, intensity thresholds, focus selectors, animations described above with reference to method 12700 optionally have one or more of the characteristics of the contacts, user interface objects, tactile outputs, intensity thresholds, focus selectors, animations described herein with reference to other methods described herein (e.g., those listed in the fifth paragraph of the Description of Embodiments). For brevity, these details are not repeated here.

In accordance with some embodiments, FIG. 16 shows a functional block diagram of an electronic device 12800 configured in accordance with the principles of the various described embodiments. The functional blocks of the device are, optionally, implemented by hardware, software, or a combination of hardware and software to carry out the principles of the various described embodiments. It is understood by persons of skill in the art that the functional blocks described in FIG. 16 are, optionally, combined or separated into sub-blocks to implement the principles of the various described embodiments. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

As shown in FIG. 16, an electronic device 12800 includes a display unit 12802 configured to display a user interface object, wherein the user interface object has a first activation state and a second activation state; a touch-sensitive surface unit 12804 configured to receive contacts; one or more sensor units 12805 configured to detect intensity of contacts with the touch-sensitive surface unit 12804; and a processing unit 12806 coupled to the display unit 12802, the touch-sensitive surface unit 12804 and the sensor units 12805. In some embodiments, the processing unit 12806 includes a detecting unit 12808, a changing unit 12810, a generating unit 12812, and a determining unit 12814.

The processing unit 12806 is configured to: detect a contact on the touch-sensitive surface unit 12804 (e.g., with

the detecting unit 12808); detect an increase of intensity of the contact on the touch-sensitive surface unit 12804 from a first intensity to a second intensity (e.g., with the detecting unit 12808); in response to detecting the increase in intensity: change activation states of the user interface object from the first activation state to the second activation state (e.g., with the changing unit 12810); and generate M distinct tactile outputs on the touch-sensitive surface unit 12804, where M is a positive integer (e.g., with the generating unit 12812); detect a decrease of intensity of the contact from the second intensity to the first intensity (e.g., with the detecting unit 12808); and in response to detecting the decrease in intensity: change activation states of the user interface object from the second activation state to the first activation state (e.g., with the changing unit 12810); and generate N distinct tactile outputs on the touch-sensitive surface unit 12804 (e.g., with the generating unit 12812), where N is a positive integer and N is different from M.

In some embodiments, changing activation states of the user interface object from the first activation state to the second activation state includes transitioning through a first number of intermediate activation states between the first activation state and the second activation state; and changing activation states of the user interface object from the second activation state to the first activation state includes transitioning through a second number of intermediate activation states between the second activation state and the first activation state.

In some embodiments, the first number of intermediate activation states between the first activation state and the second activation state is different from the second number of intermediate activation states between the second activation state and the first activation state.

In some embodiments, the processing unit 12806 is configured to: while detecting the increase in intensity of the contact, determine a rate at which the intensity of the contact is increasing (e.g., with the determining unit 12814); in accordance with a determination that the rate at which the intensity of the contact is increasing remains below a predefined threshold, generate a distinct tactile output for each transition between activation states that occurs in response to detecting the increase in intensity of the contact (e.g., with the generating unit 12812); and in accordance with a determination that the rate at which the intensity of the contact is increasing exceeds the predefined threshold, forgo generation of at least one distinct tactile output for a respective transition between activation states that occurs in response to detecting the increase in intensity of the contact (e.g., with the generating unit 12812).

In some embodiments, the processing unit 12806 is configured to: while detecting the decrease in intensity of the contact, determine a rate at which intensity of the contact is decreasing (e.g., with the determining unit 12814); in accordance with a determination that the rate at which the intensity of the contact is decreasing remains below a predefined threshold, generate a distinct tactile output for each transition between activation states that occurs in response to detecting the decrease in intensity of the contact (e.g., with the generating unit 12812); and in accordance with a determination that the rate at which the intensity of the contact is decreasing exceeds the predefined threshold, forgo generation of at least one distinct tactile output for a respective transition between activation states that occurs in response to detecting the decrease in intensity of the contact (e.g., with the generating unit 12812).

In some embodiments, the M distinct tactile outputs correspond to changes in activation state of the user interface object.

In some embodiments, the N distinct tactile outputs correspond to changes in activation state of the user interface object.

In some embodiments, at least one tactile output generated in response to detecting the increase in intensity corresponds to a tactile sensation that simulates a down-click of a physical actuator mechanism; and at least one tactile output generated in response to detecting the decrease in intensity corresponds to a tactile sensation that simulates an up-click of a physical actuator mechanism.

The operations in the information processing methods described above are, optionally implemented by running one or more functional modules in information processing apparatus such as general purpose processors (e.g., as described above with respect to FIGS. 1A and 3) or application specific chips.

The operations described above with reference to FIGS. 15A-15C are, optionally, implemented by components depicted in FIGS. 1A-1B or FIG. 16. For example, detection operations 12704, 12706, and 12722, changing operations 12710 and 12726, and generating operations 12712 and 12732 are, optionally, implemented by event sorter 170, event recognizer 180, and event handler 190. Event monitor 171 in event sorter 170 detects a contact on touch-sensitive display 112, and event dispatcher module 174 delivers the event information to application 136-1. A respective event recognizer 180 of application 136-1 compares the event information to respective event definitions 186, and determines whether a first contact at a first location on the touch-sensitive surface corresponds to a predefined event or sub-event, such as selection of an object on a user interface. When a respective predefined event or sub-event is detected, event recognizer 180 activates an event handler 190 associated with the detection of the event or sub-event. Event handler 190 optionally utilizes or calls data updater 176 or object updater 177 to update the application internal state 192. In some embodiments, event handler 190 accesses a respective GUI updater 178 to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. 1A-1B.

It should be understood that the particular order in which the operations have been described above is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that the various processes separately described herein (e.g., those listed in the fifth paragraph of the Description of Embodiments) can be combined with each other in different arrangements. For example, the contacts, user interface objects, tactile sensations, intensity thresholds, and/or focus selectors described above with reference to any one of the various processes separately described herein (e.g., those listed in the fifth paragraph of the Description of Embodiments) optionally have one or more of the characteristics of the contacts, gestures, user interface objects, tactile sensations, intensity thresholds, and focus selectors described herein with reference to one or more of the other methods described herein (e.g., those listed in the fifth paragraph of the Description of Embodiments). For brevity, all of the various possible combinations are not specifically enumerated here, but it should be understood

that the claims described above may be combined in any way that is not precluded by mutually exclusive claim features.

The foregoing description, for purpose of explanation, has been described with reference to specific embodiments. However, the illustrative discussions above are not intended to be exhaustive or to limit the various described embodiments to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings. The embodiments were chosen and described in order to best explain the principles of the various described embodiments and their practical applications, to thereby enable others skilled in the art to best utilize the various described embodiments with various modifications as are suited to the particular use contemplated.

What is claimed is:

1. A method, comprising:

at an electronic device with a touch-sensitive surface and a display:

detecting a contact on the touch-sensitive surface of the electronic device, including a first portion of a gesture made with the contact, a second portion of the gesture that follows the first portion, and lift-off of the contact from the touch-sensitive surface during or after the second portion of the gesture;

in response to detecting the second portion of the gesture made with the contact:

in accordance with a determination that a modifier input was detected while detecting the first portion of the gesture made with the contact, wherein the modifier input includes an additional input that is detected concurrently with the first portion of the gesture made with the contact:

performing a first operation; and  
generating a first tactile output on the touch-sensitive surface; and

in accordance with a determination that the modifier input was not detected while detecting the first portion of the gesture made with the contact:

performing a second operation that includes an activation operation different from the first operation; and  
generating a second tactile output on the touch-sensitive surface, wherein the second tactile output is different from the first tactile output.

2. The method of claim 1, wherein the modifier input is an input selected from the set consisting of: a key press of a modifier key, and an additional contact on the touch-sensitive surface.

3. The method of claim 2, wherein:

the first operation corresponds to a right-click operation and includes displaying a menu listing a plurality of distinct operations; and

the second operation corresponds to a left-click operation.

4. The method of claim 1, wherein:

detecting the first portion of the gesture made with the contact includes detecting an increase in intensity of the contact above a first activation threshold; and

detecting the second portion of the gesture made with the contact includes, after detecting the increase in intensity of the contact above the first activation threshold, detecting a reduction in intensity of the contact below a second activation threshold.

91

5. The method of claim 4, including:  
 in response to detecting the reduction in intensity of the contact below the second activation threshold:  
 in accordance with a determination that the modifier input was detected while detecting the increase in intensity of the contact above the first activation threshold:  
 performing the first operation; and  
 generating the first tactile output on the touch-sensitive surface; and  
 in accordance with a determination that the modifier input was not detected while detecting the increase in intensity of the contact above the first activation threshold:  
 performing the second operation different from the first operation; and  
 generating the second tactile output on the touch-sensitive surface,  
 wherein the second tactile output is different from the first tactile output.
6. The method of claim 5, wherein the second activation threshold is different from the first activation threshold.
7. The method of claim 5, wherein the second activation threshold is the same as the first activation threshold.
8. The method of claim 5, wherein:  
 the contact is detected on the touch-sensitive surface while a focus selector is over an icon on the display;  
 the first operation includes displaying a context menu that includes selectable options to perform operations associated with the icon; and  
 the second operation includes displaying a new application window associated with the icon.
9. The method of claim 5, wherein:  
 the first tactile output is generated by movement of the touch-sensitive surface that includes a first dominant movement component;  
 the second tactile output is generated by movement of the touch-sensitive surface that includes a second dominant movement component; and  
 the first dominant movement component and the second dominant movement component have a same movement profile and different amplitudes.
10. The method of claim 1, wherein:  
 the first operation corresponds to a right-click operation; and  
 the second operation corresponds to a left-click operation.
11. The method of claim 1, wherein:  
 the contact is detected on the touch-sensitive surface while a focus selector is over an icon on the display;  
 the first operation includes displaying a context menu that includes selectable options to perform operations associated with the icon; and  
 the second operation includes displaying a new application window associated with the icon.
12. The method of claim 1, wherein:  
 the first tactile output is generated by movement of the touch-sensitive surface that includes a first dominant movement component;  
 the second tactile output is generated by movement of the touch-sensitive surface that includes a second dominant movement component; and  
 the first dominant movement component and the second dominant movement component have a same movement profile and different amplitudes.
13. The method of claim 1, wherein:  
 the first operation corresponds to an operation associated with a right-click of a mouse or other input device; and

92

- the second operation corresponds to an operation associated with a left-click of a mouse or other input device.
14. An electronic device, comprising:  
 a display;  
 a touch-sensitive surface;  
 one or more processors;  
 memory; and  
 one or more programs, wherein the one or more programs are stored in the memory and configured to be executed by the one or more processors, the one or more programs including instructions for:  
 detecting a contact on the touch-sensitive surface of the electronic device, including a first portion of a gesture made with the contact, a second portion of the gesture that follows the first portion, and lift-off of the contact from the touch-sensitive surface during or after the second portion of the gesture;  
 in response to detecting the second portion of the gesture made with the contact:  
 in accordance with a determination that a modifier input was detected while detecting the first portion of the gesture made with the contact, wherein the modifier input includes an additional input that is detected concurrently with the first portion of the gesture made with the contact:  
 performing a first operation; and  
 generating a first tactile output on the touch-sensitive surface; and  
 in accordance with a determination that the modifier input was not detected while detecting the first portion of the gesture made with the contact:  
 performing a second operation that includes an activation operation different from the first operation; and  
 generating a second tactile output on the touch-sensitive surface, wherein the second tactile output is different from the first tactile output.
15. The electronic device of claim 14, wherein the modifier input is an input selected from the set consisting of: a key press of a modifier key, and an additional contact on the touch-sensitive surface.
16. The electronic device of claim 15, wherein:  
 the first operation corresponds to a right-click operation and includes displaying a menu listing a plurality of distinct operations; and  
 the second operation corresponds to a left-click operation.
17. The electronic device of claim 14, wherein:  
 detecting the first portion of the gesture made with the contact includes detecting an increase in intensity of the contact above a first activation threshold; and  
 detecting the second portion of the gesture made with the contact includes, after detecting the increase in intensity of the contact above the first activation threshold, detecting a reduction in intensity of the contact below a second activation threshold.
18. The electronic device of claim 17, wherein the one or more programs include instructions for:  
 in response to detecting the reduction in intensity of the contact below the second activation threshold:  
 in accordance with a determination that the modifier input was detected while detecting the increase in intensity of the contact above the first activation threshold:  
 performing the first operation; and  
 generating the first tactile output on the touch-sensitive surface; and

93

in accordance with a determination that the modifier input was not detected while detecting the increase in intensity of the contact above the first activation threshold:

performing the second operation different from the first operation; and  
generating the second tactile output on the touch-sensitive surface,

wherein the second tactile output is different from the first tactile output.

**19.** The electronic device of claim **18**, wherein the second activation threshold is different from the first activation threshold.

**20.** The electronic device of claim **18**, wherein the second activation threshold is the same as the first activation threshold.

**21.** The electronic device of claim **18**, wherein:

the contact is detected on the touch-sensitive surface while a focus selector is over an icon on the display; the first operation includes displaying a context menu that includes selectable options to perform operations associated with the icon; and

the second operation includes displaying a new application window associated with the icon.

**22.** The electronic device of claim **18**, wherein:

the first tactile output is generated by movement of the touch-sensitive surface that includes a first dominant movement component;

the second tactile output is generated by movement of the touch-sensitive surface that includes a second dominant movement component; and

the first dominant movement component and the second dominant movement component have a same movement profile and different amplitudes.

**23.** The electronic device of claim **14**, wherein:

the first operation corresponds to a right-click operation; and

the second operation corresponds to a left-click operation.

**24.** The electronic device of claim **14**, wherein:

the contact is detected on the touch-sensitive surface while a focus selector is over an icon on the display; the first operation includes displaying a context menu that includes selectable options to perform operations associated with the icon; and

the second operation includes displaying a new application window associated with the icon.

**25.** The electronic device of claim **14**, wherein:

the first tactile output is generated by movement of the touch-sensitive surface that includes a first dominant movement component;

the second tactile output is generated by movement of the touch-sensitive surface that includes a second dominant movement component; and

the first dominant movement component and the second dominant movement component have a same movement profile and different amplitudes.

**26.** The electronic device of claim **14**, wherein:

the first operation corresponds to an operation associated with a right-click of a mouse or other input device; and the second operation corresponds to an operation associated with a left-click of a mouse or other input device.

**27.** A non-transitory computer readable storage medium storing one or more programs, the one or more programs comprising instructions, which when executed by an electronic device with a display, and a touch-sensitive surface, cause the electronic device to:

94

detect a contact on the touch-sensitive surface of the electronic device, including a first portion of a gesture made with the contact, a second portion of the gesture that follows the first portion, and lift-off of the contact from the touch-sensitive surface during or after the second portion of the gesture;

in response to detecting the second portion of the gesture made with the contact:

in accordance with a determination that a modifier input was detected while detecting the first portion of the gesture made with the contact, wherein the modifier input includes an additional input that is detected concurrently with the first portion of the gesture made with the contact:

perform a first operation; and

generate a first tactile output on the touch-sensitive surface; and

in accordance with a determination that the modifier input was not detected while detecting the first portion of the gesture made with the contact:

perform a second operation that includes an activation operation different from the first operation; and

generate a second tactile output on the touch-sensitive surface, wherein the second tactile output is different from the first tactile output.

**28.** The non-transitory computer readable storage medium of claim **27**, wherein the modifier input is an input selected from the set consisting of: a key press of a modifier key, and an additional contact on the touch-sensitive surface.

**29.** The non-transitory computer readable storage medium of claim **28**, wherein:

the first operation corresponds to a right-click operation and includes displaying a menu listing a plurality of distinct operations; and

the second operation corresponds to a left-click operation.

**30.** The non-transitory computer readable storage medium of claim **27**, wherein:

detecting the first portion of the gesture made with the contact includes detecting an increase in intensity of the contact above a first activation threshold; and

detecting the second portion of the gesture made with the contact includes, after detecting the increase in intensity of the contact above the first activation threshold, detecting a reduction in intensity of the contact below a second activation threshold.

**31.** The non-transitory computer readable storage medium of claim **30**, wherein the one or more programs include instructions for:

in response to detecting the reduction in intensity of the contact below the second activation threshold:

in accordance with a determination that the modifier input was detected while detecting the increase in intensity of the contact above the first activation threshold:

performing the first operation; and

generating the first tactile output on the touch-sensitive surface; and

in accordance with a determination that the modifier input was not detected while detecting the increase in intensity of the contact above the first activation threshold:

performing the second operation different from the first operation; and

generating the second tactile output on the touch-sensitive surface,

95

wherein the second tactile output is different from the first tactile output.

32. The non-transitory computer readable storage medium of claim 31, wherein the second activation threshold is different from the first activation threshold.

33. The non-transitory computer readable storage medium of claim 31, wherein the second activation threshold is the same as the first activation threshold.

34. The non-transitory computer readable storage medium of claim 28, wherein:

the contact is detected on the touch-sensitive surface while a focus selector is over an icon on the display;

the first operation includes displaying a context menu that includes selectable options to perform operations associated with the icon; and

the second operation includes displaying a new application window associated with the icon.

35. The non-transitory computer readable storage medium of claim 31, wherein:

the first tactile output is generated by movement of the touch-sensitive surface that includes a first dominant movement component;

the second tactile output is generated by movement of the touch-sensitive surface that includes a second dominant movement component; and

the first dominant movement component and the second dominant movement component have a same movement profile and different amplitudes.

96

36. The non-transitory computer readable storage medium of claim 27, wherein:

the first operation corresponds to a right-click operation; and

the second operation corresponds to a left-click operation.

37. The non-transitory computer readable storage medium of claim 27, wherein:

the contact is detected on the touch-sensitive surface while a focus selector is over an icon on the display;

the first operation includes displaying a context menu that includes selectable options to perform operations associated with the icon; and

the second operation includes displaying a new application window associated with the icon.

38. The non-transitory computer readable storage medium of claim 27, wherein:

the first tactile output is generated by movement of the touch-sensitive surface that includes a first dominant movement component;

the second tactile output is generated by movement of the touch-sensitive surface that includes a second dominant movement component; and

the first dominant movement component and the second dominant movement component have a same movement profile and different amplitudes.

39. The non-transitory computer readable storage medium of claim 27, wherein:

the first operation corresponds to an operation associated with a right-click of a mouse or other input device; and

the second operation corresponds to an operation associated with a left-click of a mouse or other input device.

\* \* \* \* \*