



(51) International Patent Classification:
G03G 15/01 (2006.01) **B41M 3/06** (2006.01)

(21) International Application Number:
PCT/US2010/000461

(22) International Filing Date:
18 February 2010 (18.02.2010)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
12/396,809 3 March 2009 (03.03.2009) US

(71) Applicant (for all designated States except US): **EASTMAN KODAK COMPANY** [US/US]; 343 State Street, Rochester, New York 14650-2201 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **STELTER, Eric Carl** [US/US]; 343 State Street, Rochester, New York 14650-2201 (US).

(74) Common Representative: **EASTMAN KODAK COMPANY**; 343 State Street, Rochester, New York 14650-2201 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: ELECTROPHOTOGRAPHICALLY PRODUCED BARRIER IMAGES




FIG. 1C

(57) Abstract: Systems and methods of producing image products using printing are provided. The printed image products can include stereoscopic and/or color shifting images. These images can be formed by a sequential application of a base image, a clear toner layer and a barrier image layer in a single pass through a printer. The barrier image layer can include opaque barriers (for stereoscopic or color shifting images) or can include translucent or transparent barriers (for color shifting images).

ELECTROPHOTOGRAPHICALLY PRODUCED BARRIER IMAGES

FIELD OF THE INVENTION

This invention relates in general to printing, and more particularly to producing image products that include barrier images using a single printing process.

BACKGROUND OF THE INVENTION

Stereoscopic images provide a viewer with a three-dimensional image. One technique for producing stereoscopic images uses barriers. FIG. 1A is a schematic side view of a typical stereoscopic image reproduction technique using barriers. As illustrated in FIG. 1A, a base image 102a includes two interdigitated images, one designed for each of the viewers eyes (i.e., a left eye image and a right eye image). A set of barriers 104a-104a_n are arranged between the viewer and base image 102. Barriers 104a₁-104a_n are arranged such that a viewer's left eye (106a) views the left eye images (L) and a viewers right eye (106b) views the right eye images (R). By properly designing the interdigitated left and right eye images and proper placement of the barriers 104, a viewer will see a three-dimensional image.

Conventional techniques for producing barrier images suffer from a number of drawbacks. For example, because the base image is formed on a different side of the transparent substrate from that of the barriers, registration of the image and the barriers is difficult because the image product cannot be produced in a single pass through a printer without flipping the substrate over and reregistering the image.

SUMMARY OF THE INVENTION

This invention is directed to producing image products, including stereoscopic, motion, and color shifting image products, by electrographic techniques. The invention is also directed to apparatus for producing such image products and the resultant image products. An exemplary method comprises applying a base image to an image receiving surface. A clear toner is then applied on the base image, and a second toner is applied on the clear toner to form at least one barrier. The barrier can be arranged to form stereoscopic, motion or color

shifting image products. The image receiving surface may be transparent, translucent, or reflective. The image can also be produced on a portion of a substrate that contains conventional color images and it can contain variable data that can correspond to variable data in the conventional image.

5 The invention, and its objects and advantages, will become more apparent in the detailed description of the preferred embodiment presented below.

BRIEF DESCRIPTION OF THE DRAWINGS

10 In the detailed description of the preferred embodiment of the invention presented below, reference is made to the accompanying drawings, in which:

FIG. 1A is a schematic side view of a typical stereoscopic image reproduction technique using barriers;

FIG. 1B is a schematic side view, in cross section of an improved image product;

15 FIG. 1C is a schematic side view, in cross section of an improved stereoscopic image product formed in accordance with the present invention;

FIGs. 1D and 1E are schematic side views, in cross section of a color shifting image products formed in accordance with the present invention;

20 FIG. 1F is a schematic side view, in cross section of a motion image product formed in accordance with the present invention;

FIG. 2A is a flow chart illustrating an exemplary method in accordance with the present invention;

FIG. 2B is a flow chart illustrating another exemplary method in accordance with the present invention;

25 FIG. 3 is a schematic side elevational view, in cross section, of a typical electrographic reproduction apparatus suitable for use with this invention;

FIG. 4 is a schematic side elevational view, in cross section, of the reprographic image-producing portion of the electrographic reproduction apparatus of FIG. 3, on an enlarged scale; and

30 FIG. 5 is a schematic side elevational view, in cross section, of one printing module of the electrographic reproduction apparatus of FIG. 3, on an enlarged scale.

DETAILED DESCRIPTION OF THE INVENTION

Conventional techniques for producing barrier images suffer from a number of drawbacks. For example, because the base image is formed on a different side of the transparent substrate from that of the barriers, registration of the image and the barriers is difficult because the image product cannot be produced in a single pass through a printer without flipping the substrate over and reregistering the image. Additionally, because the base image is viewed from the opposite side of the transparent substrate from which it is applied, the image must be manipulated such that the applied base image is a mirror image of the viewed base image. If the applied image is printed on the side of the transparent substrate closest to the viewer, the separation transferred to the substrate will be a mirror image of the printed image. If the applied image is printed on the side of the transparent substrate farthest from the viewer, the separation transferred to the substrate will have the same parity as the image viewed through the substrate, and the separation will not be a mirror image.

The present invention is a method of producing an image product including applying a base image to an image receiving surface, applying a clear toner on the base image, and applying a second toner on the clear toner to form at least one barrier in various manners as discussed in detail below.

FIG. 1B is a schematic side view, in cross section, of a stereoscopic image product using barriers. Generally, stereoscopic image products that use barriers to produce the stereoscopic images include a base image 102b formed on a backside of a transparent substrate 108b, and the barriers 104b₁-104b_n are printed on the front side of transparent substrate 108b. The backside of the stereoscopic image may be illuminated to increase the three-dimensional effect or the stereoscopic image can be laminated to another substrate. Other types of barrier images include motion images and color-shifting images. Barrier images can appear to move when the viewing angle is changed. These are referred to as motion images. It is possible to print barrier images that produce a color shift when the viewing angle is changed. These are referred to as color-shifting images.

Exemplary embodiments of the invention allow printing stereoscopic images, motion images or color-shifting images in a single pass through an electrographic printer. Specifically, referring now to FIG. 1C, in an embodiment, a receiver member 108c sequentially receives a base image 102c, a layer of clear toner 110c and a layer of barrier images 104c₁-104c_n to produce a stereoscopic image. The base image can be composed of combinations of three colors, such as yellow, magenta and cyan (YMC) or the base image can be composed of combinations of four colors, such as cyan, magenta, yellow, and black (CMYK). As used herein, the term base image broadly includes any type of image (e.g., logos, pictorial images), text and/or a combination of both. The barriers 104c₁-104c_n can be printed in recesses 105c₁ - 105c_i - 105c_n in the layer of clear toner 110c as shown in FIG. 1C or they can be applied in relief to the outer surface of the layer of clear toner 110c, similar to the barriers in FIG. 1B.

FIG. 1C is a schematic side view, in cross section of an improved stereoscopic image product formed in accordance with the present invention that can be printed on one side of a substrate and in which the barrier is recessed into the transparent layer to produce a smooth outer surface that results in a thinner transparent layer in those areas.

FIGs. 1D and 1E are schematic side views, in cross section of a color shifting image products formed in accordance with the present invention. The colors 1-4 shown could alternately be primary colors or composite colors made up of multiple primaries. Color-shifting images are illustrated in FIGs. 1D and 1E. Referring now to FIG. 1D, a base image of, for example, three different colors 102d₁-102d₃ is initially formed on a receiver member 108d. Next a clear toner 110d is applied and finally an opaque color 104d is applied as a barrier.

When the image product of FIG. 1D is viewed from Viewing Angle 1, Color 1 102d₁ and Color 2 102d₂ are visible but Color 3 102d₃ is blocked by Color 4 104d, and is thus not visible (or less visible, depending upon the exact viewing angle). When the image product is viewed from Viewing Angle 2, Color 2 102d₂ is not visible because it is blocked by Color 4 104d, but Color 1 102d₁ and

Color 3 102d₃ are visible. When the image product is viewed from Viewing Angle 3, Color 2 102d₂ and Color 3 102d₃ are visible but Color 1 102d₁ is blocked by Color 4 104d, and is thus not visible (or less visible, depending upon the exact viewing angle). For a color-shift image containing two interdigitated images, a complete color shift is observed when the viewing angle changes by an amount that changes the alignment of the barrier from one image to the other image. This viewing angle change is determined by the arctangent of the ratio of the width of the at least one barrier image, usually one pixel, to the thickness of the clear layer. However, a color shift will be visible for a change of approximately ¼ this angle, as shown in Table 2.

Referring now to FIG. 1E, a base image of, for example, two different colors 102e₁ and 102e₂ is initially formed on a receiver member 108d. Next a clear toner 110e is applied and finally a translucent or transparent color of barriers 104e₁ and 104e_n is applied. Compared to the use of an opaque barrier in FIG. 1D, which provides color-shifting due to obscuring colors, the use of a translucent or transparent color barrier in FIG. 1E also provides color shifting in which a viewer sees subtractive colors based on a combination of the barrier color and the base image color.

Assume, for example, that in FIG. 1E Color 1 is magenta, color 2 is yellow and Color 3 is cyan. Accordingly, when viewed from Viewing Angle 1 or Viewing Angle 3, the image has a bluish tint due to the overlap of the cyan of Color 3 and the magenta of Color 1. When viewed from Viewing Angle 2, the image has a greenish tint due to the overlap of the cyan of Color 3 and the yellow of Color 2.

The color shifting images can be used in a variety of applications. For example, the color shifting images can be used for security imaging with moiré between the barrier and the underlying image by printing the outer separation at a different screen frequency from the underlying image. The underlying image 102e may also contain characters or other data with regions printed in one or more colors. The security imaging can be used in any type of application, such as currency to allow a background to change colors depending upon viewing angle, make portions of the image appear to move (i.e., a person

winking), and/or the like. Additionally, the color shifting can be used for any type of element including, but not limited to, text, logos, pictorial images or any other normally halftoned element of an image.

It should be recognized that the arrangement of colors described
5 above in connection with FIGs. 1C-1E is merely exemplary and that the colors can be provided in different arrangements, so long as the barriers are separated from the base image with a layer of clear toner. Furthermore, the particular shapes of the barriers are merely exemplary, and the barriers can take any number of different shapes including, but not limited to, strips, dots, arcs, triangles, square,
10 text or pictographs. Additionally, the receiver member can be any type of product, including plain paper, clear substrates, reflective substrates (e.g., Mylar) and/or the like.

FIG 1F shows an embodiment of barrier imaging that is used for motion images. Image 1 or image 2 is visible at different viewing angles. As the
15 viewing angle of an observer changes, for example, by walking past the image, image 1 or image 2 is visible. The image that is not visible is obscured by the barrier. To prepare this embodiment, image 1 and image 2 are interdigitated. The thickness of the clear toner layer and the width of the barriers relative to each other are at a ratio, as shown in Table 2 below that allows the plurality of
20 interdigitated images to be observable in series as a viewing angle of an observer changes, producing a moving image when observed by an observer that is in motion. For a motion image containing two interdigitated images, the viewing angle change to obscure one image and allow the other image to be viewed is determined by the arctangent of the ratio of the width of the at least one barrier
25 image, usually one pixel, to the thickness of the clear layer.

For Example, barriers made from toner can be from 5 to 15
microns thick. In this example, barriers of 11 microns are contemplated. Clear toner layers of 17 to 20 microns thick and up to approximately 60 microns in thickness are used.

30 Assuming a viewing distance of 15 inches and a pupil-to-pupil spacing of 2.5 inches, a light ray entering each eye from a point on a substrate makes an angle of approximately 4.76 degrees from perpendicular. For

stereoscopic images as shown in FIG. 1C, with the center of the barrier aligned with the edge of adjacent image pixels, (or offset by $\frac{1}{2}$ the pitch of the image pixels) the thickness of the clear layer between the top of the barrier and the top of the image for common printer resolution in dots per inch (DPI) is given in TABLE

5 1.

TABLE 1

Resolution (DPI)	Pixel width (microns)	Clear layer thickness (microns)
600	42.3	254
1200	21.2	127
2400	10.6	63.5
4800	5.3	31.75

10

TABLE 2 shows for motion images and for color-shifting images the viewing angle for 60 micron and 18 micron thick transparent layers. Here the barrier is aligned with the pixels of the underlying images.

15 TABLE 2

Viewing angle change (degrees from normal)				
Transparent thickness....				
	60 micron	18 micron	60 micron	18 micron
dpi	Barrier Image	Barrier Image	Color-shift Image	Color-shift Image
600	35.18384	66.9487	9.995722	30.43424
1200	19.46001	49.66686	5.048025	16.40677
2400	10.01887	30.49336	2.52892	8.37505
4800	5.048025	16.40677	1.265076	4.210013

FIG. 2A is a flow chart illustrating an exemplary method in accordance with the present invention. Initially, image data is received (step 205) and portions of the received image data that are to include barriers are identified (step 210). For example, a letter, envelope or other printed product, can include portions that have stereoscopic or color-shifting images and portions that include

20

regular images, and these different portions are identified for use in the printing process. Image commands are then generated based on the received image data and the portions that are to include stereoscopic or color-shifting images (step 215) and an image product is printed based on the printer commands (step 220).

- 5 Steps 205-215 can be performed using a general purpose computer with a suitable printer driver and/or using specific purpose hardware and software (e.g., an application specific integrated circuit (ASIC) and/or a field programmable gate array (FPGA)).

- Step 220 is performed using a printer, and the printing process will
- 10 be described in more detail in connection with FIG. 2B. Initially, the printing commands are received by the printer (step 225) and the first, second, third, and any additional toner colors are successively applied to a suitable receiver member in accordance with the printer commands (steps 230-240). Next, a clear toner is applied to the receiver member in accordance with the printer commands (step
- 15 245) in register with the previous images, and a barrier image toner is then applied to the receiver member in accordance with the printer commands (step 250) in register with the previous images. Preferably, the clear toner can be applied such that portions including barriers have less clear toner than portions that do not include barriers. This provides a smooth surface to the resultant image product.
- 20 This is also an additional security feature that makes images less easily modified. This product is described in this embodiment as printed on a substrate or receiver but one skilled in the art understands that the invention could also be printed on a printer intermediate, such as a web and then transferred to a receiver. The print method could be performed in any order, including the one described and others
- 25 described below, as is appropriate for the printing process used.

- The color of the barrier image toner will depend upon whether a stereoscopic image is being applied, in which case the barrier color should be opaque. Additionally, if color shifting is being performed using an opaque barrier (as illustrated in FIG. 1D), then the barrier image toner will be opaque; and if
- 30 color shifting is being performed using a translucent or transparent barrier (as illustrated in FIG. 1E), then the barrier image toner can be any type of translucent or transparent color toner. In the latter case, the interaction between the color of

the barrier image and the colors of the underlying should be considered to achieve a desired effect. For stereoscopic images the toner can be applied, for example, in the order of yellow, magenta, cyan, clear and black (YMCLK) or black, yellow, magenta, cyan, clear and black (KYMCLK). The barrier can be black, white, or
5 any other color. One skilled in the art would understand that any number of colors used, such as a single color image, such as can be printed on the NexPress Digimatster, or multiple color images, such as can be printed using the NexPress 2100 or similar printers using an intermediate web. For color shifting images the toner can be applied, for example, in the order of black, yellow, magenta, clear
10 and cyan (KYMLC) such that at viewing angles where cyan overlaps yellow the image has a more greenish tint and at viewing angles where cyan overlaps magenta the image has a more bluish tint. Color shifting images can also have toner applied, for example, in the order of black, yellow, cyan, clear and magenta (KYCLM) such that at viewing angles where magenta overlaps cyan the image
15 will have a bluish tint and where magenta overlaps yellow the image will have a reddish tint.

Finally, the resultant image product is applied to a fuser in order to fuse the applied toner to the receiving member (step 255). Steps 220-255 can be performed using any type of processor in a printer, including an application
20 specific integrated circuit (ASIC) and/or a field programmable gate array (FPGA).

The resulting image product can be any type of product, such as a multi-language packaging, warning labels, motion imaging in posters, children's books, compact disc (CD) or digital versatile disc (DVD) cases, trading cards, mouse pads, counter displays, key rings, framed pictures, bank checks, security
25 documents, currency, and/or the like. The resulting image product can be backlit when, for example, the product is a poster.

Now that a high level description of the invention has been provided, a more detailed description of the implementation in an electrostatic printer is presented in connection with FIGS. 3-5, which are side elevational views
30 schematically showing portions of a typical electrographic print engine or printer apparatus suitable for printing of pentachrome images. Although one embodiment of the invention involves printing using an electrophotographic engine having

three sets of single color image producing or printing stations or modules arranged in tandem, the invention contemplates that more or less than three colors may be combined on a single receiver member, or may include other typical electrographic writers or printer apparatus.

5 An electrographic printer apparatus 300 has a number of tandemly arranged electrostatographic image forming printing modules M1, M2, M3, M4, and M5. Each of the printing modules M1-M3 and M5 generates a single-color toner image and printing module M4 includes a clear toner for transfer of clear
10 receiver member, during a single pass through the five modules M1-M5, can have transferred in registration thereto up to four single-color toner images (which can form a CMYK process color image) and one clear toner image. As used herein the term process color implies that in an image formed on a receiver member combinations of subsets of the four colors are combined to form other colors on
15 the receiver member at various locations on the receiver member, and that all four colors participate to form process colors in at least some of the subsets wherein each of the four colors may be combined with one or more of the other colors at a particular location on the receiver member to form a color different than the specific color toners combined at that location. In general, printing modules M1-
20 M3 and M5 can each form color separation images using any combination of colors, such as black (K), cyan (C), magenta (M), yellow (Y) and black (K); red (R), green (G) and blue (B); and/or the like. These colors can be arranged in any order. However, for printing barrier images on a 5 color printer, printing modules M1-M3 can be used to produce yellow (Y), magenta (M), and cyan (C)
25 separations, module M4 can produce a clear toner layer, and module M5 can produce a barrier using black (K) or another color toner.

Receiver members (R_n - $R_{(n-6)}$) as shown in FIG. 4) are delivered from a paper supply unit (not shown) and transported through the printing modules M1-M5. The receiver members are adhered (e.g., preferably
30 electrostatically via coupled corona tack-down chargers 324, 325) to an endless transport web 301 entrained and driven about rollers 302, 303. Each of the printing modules M1-M5 similarly includes a photoconductive imaging roller, an

intermediate transfer member roller, and a transfer backup roller. Thus in printing module M1, a first color toner separation image can be created on the photoconductive imaging roller PC1 (311), transferred to intermediate transfer member roller ITM1 (312), and transferred again to a receiver member moving through a transfer station, which transfer station includes ITM1 forming a pressure nip with a transfer backup roller TR1 (313). Similarly, printing modules M2, M3, M4, and M5 include, respectively: PC2, ITM2, TR2 (321, 322, 323); PC3, ITM3, TR3 (331, 332, 333); PC4, ITM4, TR4 (341, 342, 343); and PC5, ITM5, TR5 (351, 352, 353). A receiver member, R_n , arriving from the supply, is shown passing over roller 302 for subsequent entry into the transfer station of the first printing module, M1, in which the preceding receiver member $R_{(n-1)}$ is shown. Similarly, receiver members $R_{(n-2)}$, $R_{(n-3)}$, $R_{(n-4)}$, and $R_{(n-5)}$ are shown moving respectively through the transfer stations of printing modules M2, M3, M4, and M5. An unfused image formed on receiver member $R_{(n-6)}$ is moving as shown towards a fuser of any well known construction, such as the fuser assembly 360 (shown in FIG. 3)

A power supply unit 305 provides individual transfer currents to the transfer backup rollers TR1, TR2, TR3, TR4, and TR5 respectively. A logic and control unit 430 (FIG. 3) includes one or more computers and in response to signals from various sensors associated with the electrophotographic printer apparatus 300 provides timing and control signals to the respective components to provide control of the various components and process control parameters of the apparatus in accordance with well understood and known employments. A cleaning station 301a for transport web 301 is also typically provided to allow continued reuse thereof.

With reference to FIG. 5 wherein a representative printing module (e.g., M1 of M1-M5) is shown, each printing module of the electrographic printer apparatus 300 includes a plurality of electrographic imaging subsystems for producing a single color toned image or a clear image (in the case of M4). Included in each printing module is a primary charging subsystem 410 for uniformly electrostatically charging a surface 406 of a photoconductive imaging member (shown in the form of an imaging cylinder 405). An exposure subsystem

420 is provided for image-wise modulating the uniform electrostatic charge by exposing the photoconductive imaging member to form a latent electrostatic color separation image of the respective color. A development station subsystem 425 serves for toning the image-wise exposed photoconductive imaging member with toner of a respective color (or clear toner). An intermediate transfer member 415 is provided for transferring the respective color separation image (or clear toner separation image) from the photoconductive imaging member through a transfer nip 401 to the surface 416 of the intermediate transfer member 415 and from the intermediate transfer member 415 to a receiver member (receiver member 436 shown prior to entry into the transfer nip and receiver member 437 shown subsequent to transfer of the toned color or clear separation image) which receives the respective toned color separation images and the clear separation image in superposition to form a composite multicolor image and barrier image thereon.

Subsequent to transfer of the respective color separation images, overlaid in registration, one from each of the respective printing modules M1-M5, the receiver member is advanced to a fusing assembly to fuse the multicolor and clear toner image to the receiver member. Additional necessary components provided for control may be assembled about the various process elements of the respective printing modules (e.g., a meter 411 for measuring the uniform electrostatic charge, a meter 412 for measuring the post-exposure surface potential within a patch area of a patch latent image formed from time to time in a non-image area on surface 406, etc). Further details regarding the electrographic printer apparatus 300 are provided in U.S. Publication No. 2006/0133870, published on June 22, 2006, in the name of Yee S. Ng et al and of the printing process provided in U.S. Publication No. 2008/0159786, published on July 3, in the name of Thomas Tombs et al. each of which are hereby incorporated by reference. One preferred method of rendering an image in conjunction with these embodiments is to use a continuous toned image of variable density as described in Technology Watch Vol. 11 Fall 2006.

Associated with the printing modules 400 is a main printer apparatus logic and control unit (LCU) 430, which receives input signals from the various sensors associated with the printer apparatus and sends control signals to

the chargers 410, the exposure subsystem 420 (e.g., LED writers), and the development stations 425 of the printing modules M1-M5. Each printing module may also have its own respective controller coupled to the printer apparatus main LCU 430

5 Subsequent to the transfer of the three color toner separation images and two clear toner separation images in superposed relationship to each receiver member, the receiver member is then serially de-tacked from transport web 301 and sent in a direction to the fusing assembly 360 to fuse or fix the dry toner images to the receiver member. The transport web is then reconditioned for
10 reuse by cleaning and providing charge to both surfaces 324, 325 (see FIG. 4) which neutralizes charge on the opposed surfaces of the transport web 301.

 The electrostatic image is developed by application of pigmented (or non-pigmented) marking particles (toner) to the latent image bearing photoconductive drum by the respective development station 425. Each of the
15 development stations of the respective printing modules M1-M5 is electrically biased by a suitable respective voltage to develop the respective latent image, which voltage may be supplied by a power supply or by individual power supplies (not illustrated). Preferably, the respective developer is a two-component developer that includes toner marking particles and magnetic carrier particles.
20 The toner marking particles can be, for example, polyester based. Each color development station has a particular color of pigmented toner marking particles associated respectively therewith for toning or a clear toner (i.e., non-pigmented) respectively associated therewith. Thus, each of the five modules creates a different color marking particle image or a clear toner image on the respective
25 photoconductive drum.

 With further reference to FIG. 3, transport belt 301 transports the toner image carrying receiver members to a fusing or fixing assembly 360, which fixes the toner particles to the respective receiver members by the application of heat and pressure. More particularly, fusing assembly 360 includes a heated
30 fusing roller 362 and an opposing pressure roller 364 that form a fusing nip therebetween. Fusing assembly 360 also includes a release fluid application substation generally designated 368 that applies release fluid, such as, for

example, silicone oil, to fusing roller 362. The receiver members carrying the fused image are transported serially from the fusing assembly 360 along a path to either a remote output tray, or are returned to the image forming apparatus to create an image on the backside of the receiver member (form a duplex print).

5 The logic and control unit (LCU) 430 includes a microprocessor incorporating suitable look-up tables and control software, which is executable by the LCU 430. The control software is preferably stored in memory associated with the LCU 430. Sensors associated with the fusing assembly provide appropriate signals to the LCU 430. In response to the sensors, the LCU 430
10 issues command and control signals that adjust the heat and/or pressure within fusing nip 366 and otherwise generally nominalizes and/or optimizes the operating parameters of fusing assembly 360 for imaging substrates.

 Image data for writing by the printer apparatus 300 may be processed by a raster image processor (RIP), which may include a color separation
15 screen generator or generators. The output of the RIP may be stored in frame or line buffers for transmission of the color separation print data to each of respective LED writers. The RIP and/or color separation screen generator may be a part of the printer apparatus or remote therefrom. Image data processed by the RIP may be obtained from a color document scanner or a digital camera or generated by a
20 computer or from a memory or network which typically includes image data representing a continuous image that needs to be reprocessed into halftone image data in order to be adequately represented by the printer. The RIP may perform image processing processes including color correction, etc. in order to obtain the desired color print. Color image data is separated into the respective colors and
25 can be converted by the RIP to halftone dot image data in the respective color using matrices, which comprise desired screen angles and screen rulings. The RIP may be a suitably programmed computer and/or logic devices and is adapted to employ stored or generated matrices and templates for processing separated color image data into rendered image data in the form of halftone information suitable
30 for printing. Portions of the image can also be printed as continuous tone images of variable density.

CLAIMS:

1. A method of producing an image product, the method comprising:
- 5 applying a base image comprising a plurality of interdigitated images, to an image receiving surface;
- applying a clear toner on the base image; and
- applying a second toner on the clear toner to form at least one barrier.
- 10
2. The method of claim 1, wherein the second toner is applied to form a plurality of barriers that are arranged to produce a stereoscopic image.
3. The method of claim 2, wherein the second toner is black.
- 15
4. The method of claim 1, wherein the second toner is transparent, translucent or opaque, is a color other than black, and depending upon viewing angle the at least one barrier shifts viewed color of the base image.
- 20
5. The method of claim 1, wherein the base image is applied by sequential application of three different color toners.
6. The method of claim 1, further comprising a motion image containing two interdigitated images such that a viewing angle change necessary
- 25 to obscure one image and allow the other image to be viewed is determined by the arctangent of the ratio of the width of the at least one barrier image, at least one pixel, to the thickness of the clear layer.
7. The method of claim 1, wherein a depth of the clear toner is
- 30 thinner in portions that are to receive the second toner than portions that do not receive the second toner.

8. The method of claim 1, wherein the base image is applied to a first portion of the image receiving surface, the method further comprising:
applying a second image to a second portion of the image receiving
5 surface.

9. The method of claim 8, wherein the base image is comprised of three colors and the second image is comprised of four colors, including a color of the second toner.

10. A method of producing an image product, the method comprising:
receiving printer commands, and in response to the printer commands the method comprises
15 controlling a first print module to apply a base image comprising a plurality of interdigitated images to an image receiving surface;
controlling a second print module to apply a clear toner on the base image; and
controlling a third print module to apply a second toner on the clear
20 toner to form at least one barrier.

11. The method of claim 10, wherein the second toner is applied to form a plurality of barriers that are arranged to produce a stereoscopic image from the base image.

12. The method of claim 11, wherein the second toner is black.

13. The method of claim 10, wherein the second toner is transparent, translucent or opaque, is a color other than black, and depending upon
30 viewing angle the at least one barrier shifts viewed color of the base image.

14. The method of claim 10, wherein the base image is applied by sequential application of three different color toners.

5 15. The method of claim 10, further comprising further comprising a motion image containing two interdigitated images such that a viewing angle change necessary to obscure one image and allow the other image to be viewed is determined by the arctangent of the ratio of the width of the at least one barrier image, at least one pixel, to the thickness of the clear layer.

10 16. The method of claim 10, wherein a depth of the clear toner is thinner in portions that are to receive the second toner than portions that do not receive the second toner.

15 17. The method of claim 10, wherein the base image is applied to a first portion of the image receiving surface, the method further comprising: applying a second image to a second portion of the image receiving surface.

20 18. The method of claim 17, wherein the base image is comprised of three colors and the second image is comprised of four colors, including a color of the second toner.

25 19. A print on a receiver member, said print exhibiting stereoscopic, color-shifting or motion imaging effects, comprising: marking particle coverage on said receiver member providing a desired interdigitated print image, and marking particle coverage, in areas of said receiver member where barrier images are desired in order to yield the desired stereoscopic, color-shifting or motion imaging effect.

20. The print on the receiver member according to Claim 19 wherein the barrier images are located adjacent the substrate and represents at least a part of the printed image.

5

21 The print on the receiver member according to Claim 19 wherein the images comprise at least two interdigitated images such that a viewing angle change necessary to obscure one image and allow the other image to be viewed is determined by the arctangent of the ratio of the width of the at least one barrier image, at least one pixel, to the thickness of the clear layer.

10

22. A method of producing an image product, the method comprising:

applying a base image to an image receiving surface;
applying a clear toner on the base image; and
applying a second toner on the clear toner to form at least one barrier wherein the second toner overlays a portion of the base image.

15




FIG. 1A
(Prior Art)




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 1E

5/10





FIG. 1F

6/10

**FIG. 2A**




FIG. 2B




FIG. 3




FIG. 4

10/10




FIG. 5

INTERNATIONAL SEARCH REPORT

International application No

PCT/US2010/000461

A. CLASSIFICATION OF SUBJECT MATTER

INV. G03G15/01 B41M3/06

ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

G03G B41M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 10 2006 003311 A1 (ROLAND MAN DRUCKMASCH [DE]) 26 July 2007 (2007-07-26)	1,2,5, 8-11,14, 17-20,22
Y	paragraphs [0001], [0002], [0006] - [0011], [0019], [0025], [0027], [0028], [0032], [0033]; figures 1, 2	3,4,7, 12,13,16
X	US 3 161 509 A (HOWE DONALD J ET AL) 15 December 1964 (1964-12-15)	1,2,6, 8-11,15, 17-22
Y	column 3, line 45 - column 4, line 27; figures 1,3 column 5, line 7 - line 27 column 6, line 8 - line 40	3,4,7, 12,13,16
X	JP 07 244343 A (SANYO ELECTRIC CO) 19 September 1995 (1995-09-19)	19-21
Y	abstract; figure 1	3,12
	----- -/--	



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

18 May 2010

Date of mailing of the international search report

26/05/2010

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Billmann, Frank

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2010/000461

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 178 928 A (GOTO HIDEO [JP] ET AL) 12 January 1993 (1993-01-12)	19-22
Y	column 2, line 49 - line 68; figure 1 column 4, line 56 - line 62 -----	4,13
X	US 6 103 345 A (OSHIMA MASAHIRO [JP] ET AL) 15 August 2000 (2000-08-15)	19-21
Y	column 3, line 11 - column 4, line 55; figures 1,2 -----	4,13
X	US 5 260 753 A (HANEDA SATOSHI [JP] ET AL) 9 November 1993 (1993-11-09)	22
Y	column 21, line 5 - line 40; figures 15C, 15D, 20, 22, 23,24 -----	7,16
X	US 6 465 077 B1 (LEE CHARLES C [US] ET AL) 15 October 2002 (2002-10-15) column 1, line 1 - line 67; figure 1 column 5, line 56 - column 6, line 37 column 7, line 6 - line 13 -----	19

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2010/000461

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 102006003311 A1	26-07-2007	NONE	
US 3161509 A	15-12-1964	GB 1032893 A	15-06-1966
JP 7244343 A	19-09-1995	NONE	
US 5178928 A	12-01-1993	NONE	
US 6103345 A	15-08-2000	NONE	
US 5260753 A	09-11-1993	DE 69119549 D1	20-06-1996
		DE 69119549 T2	28-11-1996
		EP 0486235 A2	20-05-1992
US 6465077 B1	15-10-2002	AU 776476 B2	09-09-2004
		AU 5172300 A	07-08-2001
		BR 0017019 A	07-01-2003
		CA 2396122 A1	02-08-2001
		CN 1425146 A	18-06-2003
		EP 1252546 A1	30-10-2002
		JP 2003521736 T	15-07-2003
		WO 0155777 A1	02-08-2001