(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
3 October 2013 (03.10.2013)

WIPO | PCT

(10) International Publication Number
WO 2013/148762 A2

(51) International Patent Classification:
A61B 17/072 (2006.01)

(21) International Application Number:
PCT/US2013/033997

(22) International Filing Date:
27 March 2013 (27.03.2013)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
13/433,098 28 March 2012 (28.03.2012) US

(71) Applicant: **ETHICON ENDO-SURGERY, INC.** [US/US]; 4545 Creek Road, #97, Cincinnati, OH 45242 (US).

(72) Inventors: **ALDRIDGE, Jeffrey, L.**; 106 W. Concord Drive, Lebanon, OH 45036 (US). **YANG, Chunlin**; 93 Mathews Farm Road, Belle Mead, NJ 08502 (US). **SCHEIB, Charles, J.**; 11329 Donwiddle Drive, Loveland, OH 45140 (US). **WIDENHOUSE, Christopher, W.**; 1005 Arabian Run Drive, Clarksville, OH 45113 (US). **WEISENBURGH, William, B., II**; 974 Airymeadows Drive, Maineville, OH 45039 (US). **STAMMEN, John, L.**; 8238 Glenhaven Court, Cincinnati, OH 45241 (US). **RANSICK, Mark, H.**; 7501 Nordan Drive, West Chester, OH 45069 (US). **MUTCHLER, Stephanie, A.**; 328 Glen Lake Road, Loveland, OH 45140 (US). **KNIGHT, Gary, W.**; 8264 Meadowlark Drive, West Chester, OH 45069 (US).

(74) Agents: **JOHNSON, Philip, S.** et al.; Johnson & Johnson, One Johnson & Johnson Plaza, New Brunswick, NJ 08933 (US).

(81) Designated States *(unless otherwise indicated, for every kind of national protection available)*: AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States *(unless otherwise indicated, for every kind of regional protection available)*: ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— *as to the identity of the inventor (Rule 4.17(i))*

— *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*

[Continued on next page]

(54) Title: EXPANDABLE TISSUE THICKNESS COMPENSATOR



(57) Abstract: A tissue thickness compensator may generally comprise a biocompatible material, a first component, and a second component, wherein the first component and second component form a reaction product to expand the tissue thickness compensator. The first component may comprise a first hydrogel precursor, the second component may comprise a second hydrogel precursor, and the reaction product may comprise a hydrogel. The reaction product may be formed in vivo and/or in situ by contacting the first component and the second component. The first component and/or second component may be encapsulated and configured to release the components when ruptured. The reaction product may comprise a fluid-swellable composition. Articles of manufacture comprising the tissue thickness compensator and methods of making and using the tissue thickness compensator are also described.

WO 2013/148762 A2

— *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))*

Published:

— *without international search report and to be republished upon receipt of that report (Rule 48.2(g))*

TITLE

EXPANDABLE TISSUE THICKNESS COMPENSATOR

CROSS-REFERENCE TO RELATED APPLICATIONS

This non-provisional patent application is a continuation-in-part application under 35 U.S.C. §120 of U.S. Patent Application Ser. No. 13/097,891, entitled "Tissue Thickness Compensator For A Surgical Stapler Comprising An Adjustable Anvil, filed on April 29, 2011, which is a continuation-in-part application under 35 U.S.C. §120 of U.S. Patent Application Ser. No. 12/894,377, entitled "Selectively Orientable Implantable Fastener Cartridge", filed on September 30, 2010, the entire disclosures of which are hereby incorporated by reference herein.

BACKGROUND

[0001] The present invention relates to surgical instruments and to surgical cutting and stapling instruments and staple cartridges therefor that are designed to cut and staple tissue.

SUMMARY

[0002] The following is a non-exhaustive list of embodiments of the present invention that are or may be claimed.

1. A tissue thickness compensator comprising:
a biocompatible material;
a first component; and
a second component;
wherein the first component and second component are adapted to form a reaction product to expand the tissue thickness compensator.

2. The tissue thickness compensator of Embodiment 1, further comprising an encapsulated component comprising one of the first component and second component, wherein the other of the first component and second component is embedded in the biocompatible material.

3. The tissue thickness compensator of Embodiment 1, wherein the first component comprises a hydrophilic material embedded in the biocompatible material and the second component is a bodily fluid.

4. The tissue thickness compensator of Embodiment 1 comprising a first encapsulated component comprising the first component and a second encapsulated component comprising the second component.

5. The tissue thickness compensator of Embodiment 4, wherein the biocompatible material comprises at least one encapsulation comprising the first encapsulated component and the second encapsulated component.

6. The tissue thickness compensator of Embodiment 4, wherein the first encapsulated component is configured to release the first component when the first encapsulated component is ruptured, and the second encapsulated component is configured to release the second component when the second encapsulated component is ruptured.

7. The tissue thickness compensator of any preceding Embodiment, wherein the biocompatible material comprises albumin, alginate, carbohydrate, casein, cellulose, chitin, chitosan, collagen, blood, dextran, elastin, fibrin, fibrinogen, gelatin, heparin, hyaluronic acid, keratin, protein, serum, starch, poly(lactic acid), poly(glycolic acid), poly(hydroxybutyrate), poly(phosphazine), polyester, polyethylene glycol, polyalkyleneoxide, polyacrylamide, polycarbonate, polyhydroxyethylmethylacrylate, poly(vinylpyrrolidone), polyvinyl alcohol, poly(caprolactone), poly(dioxanone), polyacrylic acid, polyacetate, polypropylene, glycerol, poly(amino acid), copoly(ether-ester), polyalkylene oxalate, polyamide, poly(iminocarbonate), polyoxaester, polyorthoester, polyphosphazene or a combination of the foregoing.

8. The tissue thickness compensator of Embodiment 1, wherein the reaction product is formed *in situ* by contacting the first component and the second component.

9. The tissue thickness compensator of any preceding Embodiment, wherein the reaction product is a fluid-swellable composition.

10. The tissue thickness compensator of any one of Embodiments 1 and 4-9, wherein the first component comprises a first hydrogel precursor, the second component comprises a second hydrogel precursor, and the reaction product comprises a hydrogel.

11. The tissue thickness compensator of any preceding Embodiment, wherein the first component and second component are independently selected from albumin, alginate, carbohydrate, casein, cellulose, chitin, chitosan, collagen, blood, dextran, elastin, fibrin, fibrinogen, gelatin, heparin, hyaluronic acid, keratin, protein, serum, starch, poly(lactic acid), poly(glycolic acid), polycarbonate, poly(hydroxybutyrate), poly(phosphazine), polyester, polyethylene glycol, polyalkyleneoxide, polyacrylamide, polyhydroxyethylmethylacrylate, poly(vinylpyrrolidone), polyvinyl alcohol, poly(caprolactone), poly(dioxanone), polyacrylic acid, polyacetate, polypropylene, glycerol, poly(amino acid), copoly(ether-ester), polyalkylene oxalate, polyamide, poly(iminocarbonate), polyoxaester, polyorthoester, polyphosphazene or a combination of the foregoing.

12. The tissue thickness compensator of any preceding Embodiment, comprising an outer layer comprising a water impermeable material and an inner layer comprising the biocompatible material and at least one of the first component and second component.

13. The tissue thickness compensator of Embodiment 12, wherein the water impermeable material comprises poly(lactic acid), poly(glycolic acid), poly(hydroxybutyrate), poly(phosphazine), polyester, polyethylene glycol, polyalkyleneoxide, polyacrylamide, polycarbonate, polyhydroxyethylmethylacrylate, poly(vinylpyrrolidone), polyvinyl alcohol, poly(caprolactone), poly(dioxanone), polyacrylic acid, polyacetate, polypropylene, glycerol, poly(amino acid), copoly(ether-ester), polyalkylene oxalate, polyamide, poly(iminocarbonate), polyoxaester, polyorthoester, polyphosphazene or a combination of the foregoing.

14. The tissue thickness compensator of any preceding Embodiment, wherein the biocompatible material comprises a reinforcement material embedded therein, and wherein the reinforcement material comprises a mesh, a fiber, a particle, a powder, or a combination of the foregoing.

15. The tissue thickness compensator of Embodiment 14, wherein the reinforcement material comprises collagen, gelatin, fibrin, fibrinogen, elastin, keratin, albumin, hydroxyethyl cellulose, cellulose, oxidized cellulose, hydroxypropyl cellulose, carboxyethyl cellulose, carboxymethylcellulose, chitan, chitosan, alginate, poly(lactic acid), poly(glycolic acid), poly(hydroxybutyrate), poly(phosphazine), polyester, polyethylene glycol, polyalkyleneoxide, polyacrylamide, polyhydroxyethylmethylacrylate, polyvinylpyrrolidone, polyvinyl alcohol, poly(caprolactone), poly(dioxanone), polyacrylic acid, polyacetate, polycaprolactone, polypropylene, aliphatic polyester, glycerol, poly(amino acid), copoly(ether-ester), polyalkylene oxalate, polyamide, poly(iminocarbonate), polyalkylene oxalate, polyoxaester, polyorthoester, polyphosphazene or a combination of the foregoing.

16. The tissue thickness compensator of any preceding Embodiment comprising a haemostatic agent, an anti-inflammatory agent, an antibiotic agent, an anti-microbial agent, an anti-adhesion agent, an anti-coagulant agent, a medicament, a pharmaceutically active agent, or a combination of the foregoing.

17. An article selected from an anvil of a stapling apparatus and a staple cartridge for a stapling apparatus, the article comprising:

the tissue thickness compensator of Embodiment 1, the tissue thickness compensator comprising:

an outer layer comprising a non-porous material;

an inner layer comprising a porous material, a first encapsulated component comprising said first component and a second encapsulated component comprising said second component.

18. The article of Embodiment 17, wherein:

the outer layer comprises polyglycolic acid, polylactic acid, polydioxanone, polyhydroxyalkanoate, poliglecaprone, polycaprolactone, or a combination thereof;

the porous material comprises oxidized regenerated cellulose, the first component comprises a first hydrogel precursor, and the second component comprises a second hydrogel precursor; and

wherein the reaction product is a hydrogel and the first hydrogel precursor and second hydrogel precursor are adapted to form said hydrogel to expand the tissue thickness compensator when the first encapsulated component and second encapsulated component are ruptured.

19. The article of Embodiment 17 or Embodiment 18, wherein the article defines at least part of a staple-forming path to be followed by a staple from the cartridge to an anvil or from a cartridge to the anvil as the case may be, and wherein the first and second encapsulated components are aligned with the staple-forming path so that a staple following that path punctures or otherwise ruptures the encapsulations.

20. A method of forming *in situ* an expanding tissue thickness compensator using the tissue thickness compensator of Embodiment 4, the method comprising:

rupturing the first encapsulated component and second encapsulated component to allow the *in situ* reaction of the first encapsulated component and second encapsulated component to form said reaction product;

wherein the reaction product expands the tissue thickness compensator to compensate for different tissue thicknesses.

21. The method of Embodiment 20, wherein:

the tissue thickness compensator comprises:

an outer layer comprising polyglycolic acid, polylactic acid, polydioxanone, polyhydroxyalkanoate, poliglecaprone, polycaprolactone, or a combination of the foregoing; and

an inner layer comprising oxidized regenerated cellulose;

the first encapsulated component comprises a first hydrogel precursor;

the second encapsulated component comprising a second hydrogel precursor; and

the reaction product comprises a hydrogel.

BRIEF DESCRIPTION OF THE DRAWINGS

[0003] The features and advantages of this invention, and the manner of attaining them, will become more apparent and the invention itself will be better understood by reference to the following description of the invention taken in conjunction with the accompanying drawings, wherein:

[0004] FIG. 1 is a cross-sectional view of a surgical instrument embodiment;

[0005] FIG. 1A is a perspective view of one embodiment of an implantable staple cartridge;

[0006] FIGS. 1B-1E illustrate portions of an end effector clamping and stapling tissue with an implantable staple cartridge;

[0007] FIG. 2 is a partial cross-sectional side view of another end effector coupled to a portion of a surgical instrument with the end effector supporting a surgical staple cartridge and with the anvil thereof in an open position;

[0008] FIG. 3 is another partial cross-sectional side view of the end effector of FIG. 2 in a closed position;

[0009] FIG. 4 is another partial cross-sectional side view of the end effector of FIGS. 2 and 3 as the knife bar is starting to advance through the end effector;

[0010] FIG. 5 is another partial cross-sectional side view of the end effector of FIGS. 2-4 with the knife bar partially advanced therethrough;

[0011] FIG. 6 is a perspective view of an alternative staple cartridge embodiment installed in a surgical cutting and stapling device;

[0012] FIG. 7 is a top view of the surgical staple cartridge and elongated channel of the device depicted in FIG. 6;

[0013] FIG. 8 is a top view of another surgical staple cartridge embodiment installed in an elongated channel of an end effector;

[0014] FIG. 9 is a bottom view of an anvil;

[0015] FIG. 10 is a partial perspective view of a plurality of staples forming a portion of a staple line;

[0016] FIG. 11 is another partial perspective view of the staple line of FIG. 10 with the staples thereof after being formed by being contacted by the anvil of the surgical cutting and stapling device;

[0017] FIG. 12 is a partial perspective view of alternative staples forming a portion of another staple line;

[0018] FIG 13 is a partial perspective view of alternative staples forming a portion of another staple line;

[0019] FIG. 14 is a partial perspective view of alternative staples forming a portion of another staple line embodiment;

[0020] FIG. 15 is a cross-sectional view of an end effector supporting a staple cartridge;

[0021] FIG. 16 is a cross-sectional view of the elongated channel portion of the end effector of FIG. 15 after the implantable staple cartridge body portion and staples have been removed therefrom;

[0022] FIG. 17 is a cross-sectional view of an end effector supporting another staple cartridge;

[0023] FIGS. 18A-18D diagram the deformation of a surgical staple positioned within a collapsible staple cartridge body in accordance with at least one embodiment;

[0024] FIG. 19A is a diagram illustrating a staple positioned in a crushable staple cartridge body;

[0025] FIG. 19B is a diagram illustrating the crushable staple cartridge body of FIG. 19A being crushed by an anvil;

[0026] FIG. 19C is a diagram illustrating the crushable staple cartridge body of FIG. 19A being further crushed by the anvil;

[0027] FIG. 19D is a diagram illustrating the staple of FIG. 19A in a fully formed configuration and the crushable staple cartridge of FIG. 19A in a fully crushed condition;

[0028] FIG. 20 is a diagram depicting a staple positioned against a staple cartridge support surface and illustrating potential relative movement therebetween;

[0029] FIG. 21 is a cross-sectional view of a staple cartridge support surface comprising a slot, or trough, configured to stabilize the base of the staple of FIG. 20;

[0030] FIG. 22 is a cross-sectional view of a staple comprising an overmolded crown and a slot, or trough, configured to receive a portion of the crown in accordance with at least one alternative embodiment;

[0031] FIG. 23 is a top view of a staple cartridge in accordance with at least one embodiment comprising staples embedded in a collapsible staple cartridge body;

[0032] FIG. 24 is an elevational view of the staple cartridge of FIG. 23;

[0033] FIG. 25 is an elevational view of a staple cartridge in accordance with at least one embodiment comprising a protective layer surrounding staples positioned within a collapsible staple cartridge body;

[0034] FIG. 26 is a cross-sectional view of the staple cartridge of FIG. 25 taken along line 26-26 in FIG. 25;

[0035] FIG. 27 is an elevational view of a staple cartridge in accordance with at least one embodiment comprising staples at least partially extending outside of a collapsible staple cartridge body and a protective layer surrounding the staple cartridge body;

[0036] FIG. 28 is a cross-sectional view of the staple cartridge of FIG. 27 taken along line 28-28 in FIG. 27;

[0037] FIG. 29 is a partial break-away view of a staple cartridge in accordance with at least one embodiment comprising staples at least partially embedded in a collapsible staple cartridge body, the staples being at least partially positioned in a staple cavity void in the staple cartridge body;

[0038] FIG. 30 is a cross-sectional view of the staple cartridge of FIG. 29 taken along line 30-30 in FIG. 29;

[0039] FIG. 31 is a partial break-away view of a staple cartridge in accordance with at least one embodiment;

[0040] FIG. 32 is a partial break-away view of a staple cartridge in accordance with at least one embodiment comprising staples at least partially embedded within a collapsible staple cartridge body and an alignment matrix connecting the staples and aligning the staples with respect to each other;

[0041] FIG. 33 is a cross-sectional view of the staple cartridge of FIG. 32 taken along line 33-33 in FIG. 32;

[0042] FIG. 34 is partial cut-away view of an inner layer of a compressible staple cartridge body;

[0043] FIG. 35 is a diagram illustrating the inner layer of FIG. 34 compressed between a transfer plate and a support plate;

[0044] FIG. 36 is a diagram illustrating staples being inserted into the compressed inner layer of FIG. 35;

[0045] FIG. 37 is a diagram of the support plate of FIG. 35 being removed away from the inner layer;

[0046] FIG. 38 is a diagram of a subassembly comprising the inner layer of FIG. 34 and the staples of FIG. 36 being inserted into an outer layer;

[0047] FIG. 39 is a diagram illustrating the outer layer of FIG. 38 being sealed to form a sealed staple cartridge;

[0048] FIG. 40 is a cross-sectional view of the sealed staple cartridge of FIG. 39;

[0049] FIG. 41 is a cross-sectional view of a staple cartridge and staple cartridge channel in accordance with at least one embodiment;

[0050] FIG. 42 is a diagram illustrating a portion of the staple cartridge of FIG. 41 in a deformed state;

[0051] FIG. 43 is an elevational view of an end effector of a surgical stapler comprising an anvil in an open position and a staple cartridge positioned within a staple cartridge channel;

[0052] FIG. 44 is an elevational view of the end effector of FIG. 43 illustrating the anvil in a closed position and the staple cartridge compressed between the anvil and the staple cartridge channel;

[0053] FIG. 45 is an elevational view of the end effector of FIG. 43 illustrating the staple cartridge of FIG. 43 positioned within the staple cartridge channel in an alternative manner;

[0054] FIG. 46 is a cross-sectional view of an end effector of a surgical stapler comprising a compressible staple cartridge positioned within a staple cartridge channel and a piece of buttress material attached to an anvil;

[0055] FIG. 47 is a cross-sectional view of the end effector of FIG. 46 illustrating the anvil in a closed position;

[0056] FIG. 48 is a cross-sectional view of an alternative embodiment of an end effector of a surgical stapler comprising a staple cartridge comprising a water impermeable layer;

[0057] FIG. 49 is a cross-sectional view of another alternative embodiment of an end effector of a surgical stapler;

[0058] FIG. 50 is a cross-sectional view of an alternative embodiment of an end effector of a surgical stapler comprising a stepped anvil and a staple cartridge comprising a stepped cartridge body;

[0059] FIG. 51 is a cross-sectional view of another alternative embodiment of an end effector of a surgical stapler;

[0060] FIG. 52 is a cross-sectional view of an alternative embodiment of an end effector of a surgical stapler comprising inclined tissue-contacting surfaces;

[0061] FIG. 53 is a cross-sectional view of another alternative embodiment of an end effector of a surgical stapler comprising inclined tissue-contacting surfaces;

[0062] FIG. 54 is a cross-sectional view of an alternative embodiment of an end effector of a surgical stapler comprising a support insert configured to support a staple cartridge;

[0063] FIG. 55 is a cross-sectional view of an alternative embodiment of an end effector of a surgical stapler comprising a staple cartridge comprising a plurality of compressible layers;

[0064] FIG. 56 is a cross-sectional view of an alternative embodiment of an end effector of a surgical stapler comprising a staple cartridge comprising a stepped compressible cartridge body;

[0065] FIG. 57 is a cross-sectional view of another alternative embodiment of an end effector of a surgical stapler comprising a staple cartridge comprising a stepped compressible cartridge body;

[0066] FIG. 58 is a cross-sectional view of an alternative embodiment of an end effector of a surgical stapler comprising a staple cartridge comprising a curved tissue-contacting surface;

[0067] FIG. 59 is a cross-sectional view of an alternative embodiment of an end effector of a surgical stapler comprising a staple cartridge having an inclined tissue-contacting surface;

[0068] FIG. 60 is a cross-sectional view of a compressible staple cartridge comprising staples and at least one medicament stored therein;

[0069] FIG. 61 is a diagram illustrating the compressible staple cartridge of FIG. 60 after it has been compressed and the staples contained therein have been deformed;

[0070] FIG. 62 is a partial cut-away view of a staple cartridge in accordance with at least one embodiment;

[0071] FIG. 63 is a cross-sectional view of the staple cartridge of FIG. 62;

[0072] FIG. 64 is a perspective view of an implanted staple cartridge in accordance with at least one alternative embodiment;

[0073] FIG. 65 is a cross-sectional view of the implanted staple cartridge of FIG. 64;

[0074] FIG. 66 is a perspective view of an alternative embodiment of a staple cartridge comprising deformable members extending from an outer layer of the staple cartridge;

[0075] FIG. 67 is a perspective view of an alternative embodiment of a staple cartridge comprising an outer layer of the staple cartridge being assembled to an inner layer;

[0076] FIG. 68 is a cross-sectional view of an alternative embodiment of a staple cartridge comprising a plurality of staples, a compressible layer, and a pledget layer;

[0077] FIG. 69 is a perspective view of the pledget layer of FIG. 68;

[0078] FIG. 70 is a perspective view of a pledget singulated from the pledget layer of FIG. 68 and a staple aligned with a groove in the pledget;

[0079] FIG. 71 is a perspective view of two connected pledgets from the pledget layer of FIG. 68;

[0080] FIG. 72 is a perspective view of a pledget support frame of the pledget layer of FIG. 68 being removed from the singulated pledgets;

[0081] FIG. 73 is an exploded perspective view of an alternative embodiment of a compressible staple cartridge comprising staples therein and a system for driving the staples against an anvil;

[0082] FIG. 73A is a partial cut-away view of an alternative embodiment of the staple cartridge of FIG. 73;

[0083] FIG. 74 is a cross-sectional view of the staple cartridge of FIG. 73;

[0084] FIG. 75 is an elevational view of a sled configured to traverse the staple cartridge of FIG. 73 and move the staples to toward the anvil;

[0085] FIG. 76 is a diagram of a staple driver which can be lifted toward the anvil by the sled of FIG. 75;

[0086] FIG. 77 is a break-away view of a staple cartridge in accordance with at least one alternative embodiment comprising staples positioned within staple drivers;

[0087] FIG. 78 is a cross-sectional view of the staple cartridge of FIG. 77 positioned within a staple cartridge channel;

[0088] FIG. 79 is a cross-sectional view of the staple cartridge of FIG. 77 illustrating an anvil moved into a closed position and staples contained within the staple cartridge deformed by the anvil;

[0089] FIG. 80 is a cross-sectional view of the staple cartridge of FIG. 77 illustrating the staples moved upwardly toward the anvil;

[0090] FIG. 81 is a perspective view of an alternative embodiment of a staple cartridge comprising straps connecting the flexible sides of the staple cartridge;

[0091] FIG. 82 is a perspective view of a sled and cutting member assembly;

[0092] FIG. 83 is a diagram of the sled and cutting member assembly of FIG. 82 being used to lift the staples of the staple cartridge of FIG. 77;

[0093] FIG. 84 is a diagram illustrating a sled configured to engage and lift staples toward an anvil and a lock-out system configured to selectively permit the sled to move distally;

[0094] FIGS. 85A-85C illustrate the progression of a staple being inserted into a staple crown;

[0095] FIG. 86 is a cross-sectional view of a staple cartridge comprising a support pan or retainer;

[0096] FIG. 87 is a partial cross-sectional view of a compressible staple cartridge in accordance with at least one alternative embodiment;

[0097] FIG. 88 is a diagram illustrating the staple cartridge of FIG. 87 in an implanted condition;

[0098] FIG. 89 is a partial cut-away view of a compressible staple cartridge in accordance with at least one alternative embodiment;

[0099] FIG. 90 is a partial cross-sectional view of the staple cartridge of FIG. 89;

[0100] FIG. 91 is a diagram illustrating the staple cartridge of FIG. 89 in an implanted condition;

[0101] FIG. 92 is a partial cross-sectional view of a crushable staple cartridge in accordance with at least one alternative embodiment;

[0102] FIG. 93 is a partial cut-away view of a collapsible staple cartridge in accordance with at least one embodiment comprising a plurality of collapsible elements;

[0103] FIG. 94 is a perspective view of a collapsible element of FIG. 93 in an uncollapsed state;

[0104] FIG. 95 is a perspective view of the collapsible element of FIG. 94 in a collapsed state;

[0105] FIG. 96A is a partial cross-sectional view of an end effector of a surgical stapling instrument comprising a jaw, a staple cartridge channel positioned opposite the jaw, and a staple cartridge positioned within the staple cartridge channel, wherein the jaw comprises a retention matrix attached thereto;

[0106] FIG. 96B is a partial cross-sectional view of the end effector of FIG. 96A illustrating the jaw being moved toward the staple cartridge channel, the staple cartridge being compressed by the anvil and the retention matrix, and a staple at least partially extending through tissue positioned intermediate the retention matrix and the staple cartridge;

[0107] FIG. 96C is a partial cross-sectional view of the end effector of FIG. 96A illustrating the jaw in a final position and the retention matrix engaged with the staple of FIG. 96B;

[0108] FIG. 96D is a partial cross-sectional view of the end effector of FIG. 96A illustrating the jaw and the staple cartridge channel being moved away from the implanted staple cartridge and retention matrix;

[0109] FIG. 97 is a perspective view of a retention aperture of a retention matrix in accordance with at least one alternative embodiment comprising a plurality of retention members configured to engage a fastener leg extending therethrough;

[0110] FIG. 98 is a perspective view of a retention aperture of a retention matrix in accordance with at least one alternative embodiment comprising six retention members;

[0111] FIG. 99 is a perspective view of a retention aperture of a retention matrix in accordance with at least one alternative embodiment comprising eight retention members;

[0112] FIG. 100 is a perspective view of a retention aperture of a retention matrix in accordance with at least one alternative embodiment comprising a plurality of retention members configured to engage a fastener leg extending therethrough;

[0113] FIG. 101 is a perspective view of a retention aperture of a retention matrix in accordance with at least one alternative embodiment comprising six retention members;

[0114] FIG. 102 is a perspective view of a retention aperture of a retention matrix in accordance with at least one alternative embodiment comprising eight retention members;

[0115] FIG. 103 is a perspective view of a retention aperture of a retention matrix in accordance with at least one alternative embodiment comprising a plurality of retention members that have been stamped from a sheet of metal;

[0116] FIG. 104 is a perspective view of a retention aperture of a retention matrix in accordance with at least one alternative embodiment comprising a plurality of apertures extending around the perimeter of the retention aperture;

[0117] FIG. 105 is a top view of a retention aperture of a retention matrix in accordance with at least one alternative embodiment;

[0118] FIG. 106 is a top view of a retention aperture of a retention matrix in accordance with at least one alternative embodiment;

[0119] FIG. 107 is a top view of a retention aperture of a retention matrix in accordance with at least one alternative embodiment;

[0120] FIG. 108 is a top view of a retention aperture of a retention matrix in accordance with at least one alternative embodiment;

[0121] FIG. 109 is a top view of a retention aperture of a retention matrix in accordance with at least one alternative embodiment;

[0122] FIG. 110 is a top view of a retention aperture of a retention matrix comprising a retention tab extending into the retention aperture in accordance with at least one embodiment;

[0123] FIG. 111 is a top view of a retention aperture of a retention matrix comprising a retention tab extending into the retention aperture in accordance with at least one alternative embodiment;

[0124] FIG. 112 is a perspective view of a fastening system comprising a plurality of staples, a retention matrix engaged with the staples, and an alignment matrix configured to align the staples;

[0125] FIG. 113 is a perspective view of the retention matrix of FIG. 112;

[0126] FIG. 114 is a perspective view of the alignment matrix of FIG. 112;

[0127] FIG. 115 is a partial top view of the retention matrix of FIG. 112 engaged with the staples of FIG. 112;

[0128] FIG. 116 is a partial bottom view of the retention matrix of FIG. 112 engaged with the staples of FIG. 112;

[0129] FIG. 117 is a partial elevational view of the fastening system of FIG. 112;

[0130] FIG. 118 is a partial perspective view of the fastening system of FIG. 112;

[0131] FIG. 119 is a partial cross-sectional view of the retention matrix of FIG. 112 engaged with the staples of FIG. 112;

[0132] FIG. 120 is a partial cross-sectional view of the fastening system of FIG. 112;

[0133] FIG. 121 is a perspective view of the fastening system of FIG. 112 further comprising protective caps assembled to the legs of the staples;

[0134] FIG. 122 is a bottom perspective view of the fastening system arrangement of FIG. 121;

[0135] FIG. 123 is a partial perspective view of the fastening system arrangement of FIG. 121;

[0136] FIG. 124 is a partial cross-sectional view of the fastening system arrangement of FIG. 121;

[0137] FIG. 125 is an elevational view of an end effector in accordance with at least one embodiment comprising a jaw in an open position, a retention matrix and a plurality of protective caps positioned in the jaw, and a staple cartridge positioned in a staple cartridge channel;

[0138] FIG. 126 is an elevational view of the end effector of FIG. 125 in a closed position;

[0139] FIG. 127 is an elevational view of the end effector of FIG. 125 in a fired position;

[0140] FIG. 128 is an elevational view of the retention matrix and protective caps of FIG. 125 assembled to the staple cartridge of FIG. 125;

[0141] FIG. 129 is a detail view of the arrangement of FIG. 128;

[0142] FIG. 130 is an elevational view of the end effector of FIG. 125 illustrating the jaw in an open position with thinner tissue positioned between the retention matrix and the staple cartridge;

[0143] FIG. 131 is an elevational view of the end effector of FIG. 125 illustrating the jaw in a closed position against the thinner tissue of FIG. 130;

[0144] FIG. 132 is an elevational view of the end effector of FIG. 125 illustrating the jaw in a fired position to capture the thinner tissue of FIG. 130 between the retention matrix and the staple cartridge;

[0145] FIG. 133 is an elevational view of the retention matrix and the protective caps of FIG. 125 assembled to the staple cartridge of FIG. 125 with the thin tissue of FIG. 130 positioned therebetween;

[0146] FIG. 134 is a detail view of the arrangement of FIG. 133;

[0147] FIG. 135 is a cross-sectional view of a protective cap positioned on the tip of a staple leg in accordance with at least one alternative embodiment;

[0148] FIG. 136 is a perspective view of a plurality of protective caps embedded within a sheet of material;

[0149] FIG. 137 is a perspective view of a jaw comprising a plurality of recesses configured to receive a plurality of protective caps therein;

[0150] FIG. 138 is a detail view of a portion of a jaw comprising a sheet covering the protective caps positioned within the jaw of FIG. 137;

[0151] FIG. 139 is a cross-sectional view of a protective cap positioned on a tip of a staple leg in accordance with at least one alternative embodiment wherein the protective cap comprises an interior forming surface;

[0152] FIG. 140 is another cross-sectional view of the protective cap of FIG. 139 illustrating the staple leg being deformed against the forming surface;

[0153] FIG. 141 is a top view of an alternative embodiment of a retention matrix comprising a plurality of connected matrix elements;

[0154] FIG. 142 is a top view of an alternative embodiment of a retention matrix comprising a plurality of connected matrix elements;

[0155] FIG. 143 is a top view of an alternative embodiment of a retention matrix comprising a plurality of connected matrix elements;

[0156] FIG. 144 is a top view of an alternative embodiment of an array of retention matrices comprising a plurality of connected matrix elements;

[0157] FIG. 145 is a top view of an alternative embodiment of a retention matrix comprising a plurality of connected matrix elements;

[0158] FIG. 146 is a partial exploded view of a jaw comprising a retention matrix including a compressible cover;

[0159] FIG. 147 is a detail view of the retention matrix of FIG. 146;

[0160] FIG. 148 is a partial cross-sectional view of a fastening system comprising a retention matrix including a compressible layer and a plurality of cells encapsulating one or more medicaments;

[0161] FIG. 149 is a diagram illustrating staple legs which have pierced the cells of FIG. 148 as they are being engaged with the retention matrix;

[0162] FIG. 150 is a partial cross-sectional view of a fastening system comprising a retention matrix including a compressible layer;

[0163] FIG. 151 is an elevational view of a fastener cartridge insertion assembly comprising a holder, a first fastener cartridge, and a second fastener cartridge;

[0164] FIG. 152 is an elevational view of an end effector of a surgical stapler comprising a first jaw and a second jaw, the second jaw being illustrated in an open configuration;

[0165] FIG. 153 is an elevational view of the end effector of FIG. 152 illustrating the second jaw in a closed configuration and the fastener cartridge insertion assembly of FIG. 151 being used to load the first jaw with the first cartridge and the second jaw with the second cartridge;

[0166] FIG. 154 is an elevational view of the loaded end effector of FIG. 153 illustrating the cartridge insertion assembly removed from the end effector, the second jaw in an open configuration once again, and tissue positioned intermediate the first jaw and the second jaw;

[0167] FIG. 155 is an elevational view of the loaded end effector of FIG. 154 in a fired configuration;

[0168] FIG. 156 is an elevational view of the first cartridge and the second cartridge in an implanted condition;

[0169] FIG. 157 is an elevational view of the end effector of FIG. 152 illustrating a portion of the first cartridge still engaged with the first jaw in accordance with at least one embodiment;

[0170] FIG. 158 is an elevational view of an alternative embodiment of a fastener cartridge insertion assembly comprising a holder, a first fastener cartridge, and a second fastener cartridge;

[0171] FIG. 159 is an elevational view of the fastener cartridge insertion assembly of FIG. 158 being used to load a first jaw of an end effector with the first cartridge and a second jaw with the second cartridge;

[0172] FIG. 160 is a cross-sectional view of the loaded end effector of FIG. 159;

[0173] FIG. 161 is a perspective view of a surgical stapler comprising a bottom jaw and a top jaw in accordance with at least one embodiment illustrated with portions of the surgical stapler removed;

[0174] FIG. 162 is a perspective view of the surgical stapler of FIG. 161 with the top jaw removed;

[0175] FIG. 163 is a perspective view of a slidable anvil system of the top jaw of the surgical stapler of FIG. 161 comprising a first slidable anvil and a second slidable anvil;

[0176] FIG. 164 is an end view of the slidable anvil system of FIG. 163;

[0177] FIG. 165 is a top view of the slidable anvil system of FIG. 163;

[0178] FIG. 166 is a diagram illustrating the slidable anvil system of FIG. 163 in an unfired condition;

[0179] FIG. 167 is a diagram illustrating the first slidable anvil of the slidable anvil system of FIG. 163 in an unfired position and staples positioned within the bottom jaw in an undeployed position;

[0180] FIG. 168 is a diagram illustrating the staples in the bottom jaw in a deployed configuration and the first slidable anvil of FIG. 167 being pulled proximally to deform a first group of staple legs of the staples;

[0181] FIG. 169 is a diagram illustrating the first group of staples of FIG. 168 deformed to a fully deformed state;

[0182] FIG. 170 is a diagram illustrating the second slidable anvil of the slidable anvil system of FIG. 163 being pushed distally to deform a second group of staple legs;

[0183] FIG. 171 is a partial perspective view of an anvil comprising a plurality of forming pockets in at least one embodiment;

[0184] FIG. 172 is a cross-sectional end view of the anvil of FIG. 171;

[0185] FIG. 173 is a diagram illustrating a first step in manufacturing the forming pockets of FIG. 171;

[0186] FIG. 174 is a diagram illustrating a second step in manufacturing the forming pockets of FIG. 171;

[0187] FIG. 175 is a top view of the forming pocket arrangement of the anvil of FIG. 171;

[0188] FIG. 176 is a diagram illustrating a first step of a manufacturing process for producing an anvil;

[0189] FIG. 177 is a diagram illustrating a second step in the manufacturing process of FIG. 176;

[0190] FIG. 178 is a diagram illustrating a third step in the manufacturing process of FIG. 176;

[0191] FIG. 179 is a left front perspective view of a surgical stapling and severing instrument with a handle portion including a link triggered automatic retraction and a ratcheting manual retraction mechanism;

[0192] FIG. 180 is a right aft perspective view of the surgical stapling and severing instrument of FIG. 179 with a portion of an elongate shaft cut away and a right half shell of a handle housing removed to expose an automatic end-of-firing travel retraction mechanism and a manual firing retraction mechanism;

[0193] FIG. 181 is a right aft perspective disassembled view of the handle portion and an elongate shaft of the surgical stapling and severing instrument of FIG. 179;

[0194] FIG. 182 is a right aft perspective view of the surgical stapling and severing instrument of FIG. 31 with a right half shell and outer portions of the implement portion removed to expose the closure and firing mechanisms in an initial state;

[0195] FIG. 183 is a right side view in elevation of the partially disassembled surgical stapling and severing instrument of FIG. 182;

[0196] FIG. 184 is a right aft perspective view of the partially disassembled surgical stapling and severing instrument of FIG. 182 with a closure mechanism closed and clamped and the side pawl firing mechanism completing a first stroke and with a manual retraction mechanism removed to expose a distal link of the linked rack that triggers automatic retraction of the firing mechanism;

[0197] FIG. 185 is a right aft perspective view of the partially disassembled surgical stapling and

severing instrument of FIG. 183 with the side pawl firing mechanism disengaged and the distal link approaching automatic retraction;

[0198] FIG. 186 is left side view in elevation of the partially disassembled surgical stapling and severing instrument of FIG. 183 in an initial state of end effector open and anti-backup mechanism engaged;

[0199] FIG. 187 is a left side detail view of the right half shell and an anti-backup release lever of the handle portion of FIG. 186;

[0200] FIG. 188 is a left side detail view in elevation of the disassembled surgical stapling and severing instrument of FIG. 179 with the closure trigger clamped, the firing trigger performing a final stroke and the distal link positioned to trip automatic retraction;

[0201] FIG. 189 is a left side detail in elevation of the disassembled surgical stapling and severing instrument of FIG. 188 immediately after the distal link has actuated and locked forward the anti-backup release lever, allowing the linked rack to retract;

[0202] FIG. 190 is a right disassembled perspective view of the idler and aft gears and manual retraction lever and ratcheting pawl of a manual retraction mechanism of the surgical stapling and severing instrument of FIG. 179;

[0203] FIG. 191 is a right perspective view of the manual retraction mechanism of FIG. 190 with the manual retraction lever partially cut away to expose a smaller diameter ratchet gear on the aft gear engaging the ratcheting pawl;

[0204] FIG. 192 is a partially disassembled left side view in elevation of a surgical stapling and severing instrument of FIG. 179 with the anti-backup mechanism engaged to a fully fired linked rack that is disconnected from a combination tension/compression spring prior to actuation of the manual retraction lever of FIG. 190;

[0205] FIG. 193 is a partially disassembled left side view in elevation of the surgical stapling and severing instrument of FIG. 192 with hidden portions of the anti-backup release lever, aft gear, and manual firing release lever shown in phantom;

[0206] FIG. 194 is a partially disassembled left side view in elevation of the surgical stapling and severing instrument of FIG. 193 after actuation of the manual firing release lever has manually retracted the link rack;

[0207] FIG. 195 is a partially disassembled left side view in elevation of the surgical stapling and severing instrument of FIG. 194 with the linked rack omitted depicting the manual firing release

lever disengaging the anti-backup mechanism;

[0208] FIG. 196 is a left side detail view of an alternative anti-backup release lever and handle housing for the surgical stapling and severing instrument of FIG. 179;

[0209] FIG. 197 is a left perspective disassembled view of the alternative anti-backup release lever, aft gear axle, and automatic retraction cam wheel of FIG. 196;

[0210] FIG. 198 is a right side view in elevation of the alternative anti-backup release mechanism of FIG. 196 with the linked rack in a retracted position and the anti-backup release lever proximally positioned with the anti-backup plate engaged to the firing rod;

[0211] FIG. 198A is a right detail side view in elevation of the aft gear, automatic retraction cam wheel and distal-most link of FIG. 198;

[0212] FIG. 199 is a right side view in elevation of the anti-backup release mechanism of FIG. 198 after a first firing stroke;

[0213] FIG. 199A is a right detail side view in elevation of the aft gear, automatic retraction cam wheel and a second link of FIG. 199;

[0214] FIG. 200 is a right side view in elevation of the anti-backup release mechanism of FIG. 199 after a second firing stroke;

[0215] FIG. 200A is a right detail side view in elevation of the aft gear, automatic retraction cam wheel and third link of FIG. 200;

[0216] FIG. 201 is a right detail side view in elevation of the anti-backup release mechanism of FIG. 200 after a third firing and final stroke;

[0217] FIG. 201A is a right detail side view in elevation of the aft gear, automatic retraction cam wheel and proximal-most fourth link of FIG. 201;

[0218] FIG. 202 is a right side view in elevation of the automatic release mechanism of FIG. 201 after a further firing stroke causes the automatic retraction cam wheel to distally slide and lock the anti-backup release lever, disengaging the anti-backup mechanism;

[0219] FIG. 203 is a left, front perspective view of an open staple applying assembly with a right half portion of a replaceable staple cartridge included in a staple channel;

[0220] FIG. 204 is an exploded perspective view of the staple applying assembly of FIG. 203 with a complete replaceable staple cartridge and an nonarticulating shaft configuration;

[0221] FIG. 205 is a perspective view of a two-piece knife and firing bar ("E-beam") of the staple applying assembly of FIG. 203;

[0222] FIG. 206 is a perspective view of a wedge sled of a staple cartridge of a staple applying assembly;

[0223] FIG. 207 is a left side view in elevation taken in longitudinal cross section along a centerline line 207-207 of the staple applying assembly of FIG. 203;

[0224] FIG. 208 is a perspective view of the open staple applying assembly of FIG. 203 without the replaceable staple cartridge, a portion of the staple channel proximate to a middle pin of two-piece knife and firing bar, and without a distal portion of a staple channel;

[0225] FIG. 209 is a front view in elevation taken in cross section along line 209-209 of the staple applying assembly of FIG. 203 depicting internal staple drivers of the staple cartridge and portions of the two-piece knife and firing bar;

[0226] FIG. 210 is a left side view in elevation taken generally along the longitudinal axis of line 207-207 of a closed staple applying assembly of FIG. 203 to include center contact points between the two-piece knife and wedge sled but also laterally offset to show staples and staple drivers within the staple cartridge;

[0227] FIG. 211 is a left side detail view in elevation of the staple applying assembly of FIG. 210 with the two-piece knife retracted slightly more as typical for staple cartridge replacement;

[0228] FIG. 212 is a left side detail view in elevation of the staple applying assembly of FIG. 211 with the two-piece knife beginning to fire, corresponding to the configuration depicted in FIG. 210;

[0229] FIG. 213 is a left side cross-sectional view in elevation of the closed staple applying assembly of FIG. 210 after the two-piece knife and firing bar has distally fired;

[0230] FIG. 214 is a left side cross-sectional view in elevation of the closed staple applying assembly of FIG. 213 after firing of the staple cartridge and retraction of the two-piece knife;

[0231] FIG. 215 is a left side cross-sectional detail view in elevation of the staple applying assembly of FIG. 214 with the two-piece knife allowed to drop into a lockout position;

[0232] FIG. 216 is a perspective view of a staple cartridge comprising a rigid support portion and a compressible tissue thickness compensator for use with a surgical stapling instrument in accordance with at least one embodiment of the invention;

[0233] FIG. 217 is a partially exploded view of the staple cartridge of FIG. 216;

[0234] FIG. 218 is a fully exploded view of the staple cartridge of FIG. 216;

[0235] FIG. 219 is another exploded view of the staple cartridge of FIG. 216 without a warp covering the tissue thickness compensator;

[0236] FIG. 220 is a perspective view of a cartridge body, or support portion, of the staple cartridge of FIG. 216;

[0237] FIG. 221 is a top perspective view of a sled movable within the staple cartridge of FIG. 216 to deploy staples from the staple cartridge;

[0238] FIG. 222 is a bottom perspective view of the sled of FIG. 221;

[0239] FIG. 223 is an elevational view of the sled of FIG. 221;

[0240] FIG. 224 is a top perspective view of a driver configured to support one or more staples and to be lifted upwardly by the sled of FIG. 221 to eject the staples from the staple cartridge;

[0241] FIG. 225 is a bottom perspective view of the driver of FIG. 224;

[0242] FIG. 226 is a wrap configured to at least partially surround a compressible tissue thickness compensator of a staple cartridge;

[0243] FIG. 227 is a partial cut away view of a staple cartridge comprising a rigid support portion and a compressible tissue thickness compensator illustrated with staples being moved from an unfired position to a fired position during a first sequence;

[0244] FIG. 228 is an elevational view of the staple cartridge of FIG. 227;

[0245] FIG. 229 is a detail elevational view of the staple cartridge of FIG. 227;

[0246] FIG. 230 is a cross-sectional end view of the staple cartridge of FIG. 227;

[0247] FIG. 231 is a bottom view of the staple cartridge of FIG. 227;

[0248] FIG. 232 is a detail bottom view of the staple cartridge of FIG. 227;

[0249] FIG. 233 is a longitudinal cross-sectional view of an anvil in a closed position and a staple cartridge comprising a rigid support portion and a compressible tissue thickness compensator illustrated with staples being moved from an unfired position to a fired position during a first sequence;

[0250] FIG. 234 is another cross-sectional view of the anvil and the staple cartridge of FIG. 233 illustrating the anvil in an open position after the firing sequence has been completed;

[0251] FIG. 235 is a partial detail view of the staple cartridge of FIG. 233 illustrating the staples in an unfired position;

[0252] FIG. 236 is a cross-sectional elevational view of a staple cartridge comprising a rigid support portion and a compressible tissue thickness compensator illustrating the staples in an unfired position;

[0253] FIG. 237 is a detail view of the staple cartridge of FIG. 236;

[0254] FIG. 238 is an elevational view of an anvil in an open position and a staple cartridge comprising a rigid support portion and a compressible tissue thickness compensator illustrating the staples in an unfired position;

[0255] FIG. 239 is an elevational view of an anvil in a closed position and a staple cartridge comprising a rigid support portion and a compressible tissue thickness compensator illustrating the staples in an unfired position and tissue captured between the anvil and the tissue thickness compensator;

[0256] FIG. 240 is a detail view of the anvil and staple cartridge of FIG. 239;

[0257] FIG. 241 is an elevational view of an anvil in a closed position and a staple cartridge comprising a rigid support portion and a compressible tissue thickness compensator illustrating the staples in an unfired position illustrating thicker tissue positioned between the anvil and the staple cartridge;

[0258] FIG. 242 is a detail view of the anvil and staple cartridge of FIG. 241;

[0259] FIG. 243 is an elevational view of the anvil and staple cartridge of FIG. 241 illustrating tissue having different thicknesses positioned between the anvil and the staple cartridge;

[0260] FIG. 244 is a detail view of the anvil and staple cartridge of FIG. 241 as illustrated in FIG. 243;

[0261] FIG. 245 is a diagram illustrating a tissue thickness compensator which is compensating for different tissue thickness captured within different staples;

[0262] FIG. 246 is a diagram illustrating a tissue thickness compensator applying a compressive pressure to one or more vessels that have been transected by a staple line;

[0263] FIG. 247 is a diagram illustrating a circumstance wherein one or more staples have been improperly formed;

[0264] FIG. 248 is a diagram illustrating a tissue thickness compensator which could compensate for improperly formed staples;

[0265] FIG. 249 is a diagram illustrating a tissue thickness compensator positioned in a region of tissue in which multiple staples lines have intersected;

[0266] FIG. 250 is a diagram illustrating tissue captured within a staple;

[0267] FIG. 251 is a diagram illustrating tissue and a tissue thickness compensator captured within a staple;

[0268] FIG. 252 is a diagram illustrating tissue captured within a staple;

[0269] FIG. 253 is a diagram illustrating thick tissue and a tissue thickness compensator captured within a staple;

[0270] FIG. 254 is a diagram illustrating thin tissue and a tissue thickness compensator captured within a staple;

[0271] FIG. 255 is a diagram illustrating tissue having an intermediate thickness and a tissue thickness compensator captured within a staple;

[0272] FIG. 256 is a diagram illustrating tissue having another intermediate thickness and a tissue thickness compensator captured within a staple;

[0273] FIG. 257 is a diagram illustrating thick tissue and a tissue thickness compensator captured within a staple;

[0274] FIG. 258 is a partial cross-sectional view of an end effector of a surgical stapling instrument illustrating a firing bar and staple-firing sled in a retracted, unfired position;

[0275] FIG. 259 is another partial cross-sectional view of the end effector of FIG. 258 illustrating the firing bar and the staple-firing sled in a partially advanced position;

[0276] FIG. 260 is a cross-sectional view of the end effector of FIG. 258 illustrating the firing bar in a fully advanced, or fired, position;

[0277] FIG. 261 is a cross-sectional view of the end effector of FIG. 258 illustrating the firing bar in a retracted position after being fired and the staple-firing sled left in its fully fired position;

[0278] FIG. 262 is a detail view of the firing bar in the retracted position of FIG. 261;

[0279] FIG. 263 is a partial cross-sectional view of an end effector of a surgical stapling instrument including a staple cartridge comprising a tissue thickness compensator and staples at least partially positioned therein;

[0280] FIG. 264 is another partial cross-sectional view of the end effector of FIG. 263 illustrating the staples at least partially moved and/or rotated relative to an anvil positioned opposite the staple cartridge;

[0281] FIG. 265 is a partial cross-sectional view of an end effector of a surgical stapling instrument in accordance with at least one embodiment;

[0282] FIG. 266 is a partial cross-sectional view of an end effector in accordance with at least one alternative embodiment;

[0283] FIG. 267 is a partial cross-sectional view of an end effector in accordance with another alternative embodiment;

[0284] FIG. 268 is a perspective view of an end effector of a surgical stapling instrument in accordance with at least one embodiment;

[0285] FIG. 269 is a partial cross-sectional view of the end effector of FIG. 268 illustrated in a flexed condition;

[0286] FIG. 270 is a partial cross-sectional view of the end effector of FIG. 269 in a released condition;

[0287] FIG. 271 is a perspective view of an end effector comprising a tissue thickness compensator sock;

[0288] FIG. 272 is a rear perspective of the tissue thickness compensator sock in FIG. 271;

[0289] FIG. 273 is a perspective view of an end effector comprising a plurality of rails extending from a support portion and a tissue thickness compensator having a longitudinal cavity defined therein;

[0290] FIG. 274 is a perspective view of the tissue thickness compensator of FIG. 273;

[0291] FIG. 275 is a perspective view of an end effector comprising a plurality of teeth extending from a support portion and a tissue thickness compensator engaged therewith;

[0292] FIG. 276 is a perspective view of an anvil comprising a pocket array in accordance with at least one embodiment;

[0293] FIG. 277 is a partial detail view of the anvil of FIG. 276;

[0294] FIG. 278 is a partial longitudinal cross-sectional view of the anvil of FIG. 276;

[0295] FIG. 279 is a transverse cross-sectional view of the anvil of FIG. 276;

[0296] FIG. 280 is an elevational view of a fired staple comprising a substantially B-shaped configuration;

[0297] FIG. 281 is an elevational view of a fired staple comprising one leg deformed inwardly and one leg deformed outwardly;

[0298] FIG. 282 is an elevational view of a fired staple comprising both legs formed outwardly;

[0299] FIG. 283 is a partial perspective view of a support portion of a staple cartridge comprising detachable and/or displaceable staple leg guides;

[0300] FIG. 284 is a partial cross-sectional view of the staple cartridge of FIG. 283 illustrating staples being deployed from the staple cartridge;

[0301] FIG. 285 is a detail view of the cross-sectional view of FIG. 284 after the staple cartridge has been fired;

[0302] FIG. 286 is an exploded view of a staple cartridge including a tissue thickness compensator comprising voids defined therein;

[0303] FIG. 287 is a diagram illustrating the tissue thickness compensator of FIG. 286 implanted against tissue;

[0304] FIG. 288 is another diagram illustrating the tissue thickness compensator of FIG. 286 implanted against tissue;

[0305] FIG. 289 is a cross-sectional perspective view of a staple cartridge comprising lateral retention members extending from a support portion thereof configured to hold a tissue thickness compensator in position;

[0306] FIG. 290 is a cross-sectional view of the staple cartridge of FIG. 289 being utilized to staple tissue;

[0307] FIG. 291 is another cross-sectional view of the staple cartridge of FIG. 289 illustrating the support portion being moved away from the implanted tissue thickness compensator;

[0308] FIG. 292 is a cross-sectional perspective view of a staple cartridge comprising lateral retention members configured to hold a tissue thickness compensator to a support portion;

[0309] FIG. 293 is a cross-sectional view of the staple cartridge of FIG. 292 being utilized to staple tissue;

[0310] FIG. 294 is another cross-sectional view of the staple cartridge of FIG. 292 illustrating the support portion being moved away from the implanted tissue thickness compensator;

[0311] FIG. 295 is a cross-sectional detail view of a retainer holding a tissue thickness compensator to a support portion of a staple cartridge in accordance with at least one embodiment;

[0312] FIG. 296 is partial cut-away view of a staple cartridge comprising staple drivers having different heights in accordance with at least one embodiment;

[0313] FIG. 296A is a diagram illustrating the staple drivers of FIG. 296 and staples having different unfired heights supported thereon;

[0314] FIG. 297 is a diagram illustrating a tissue thickness compensator comprising a varying thickness, staple drivers having different heights, and staples having different unformed heights;

[0315] FIG. 298 is a diagram illustrating the staples and the tissue thickness compensator of FIG. 297 implanted to tissue;

[0316] FIG. 299 is a partial cross-sectional view of a staple cartridge comprising a tissue thickness compensator comprising a varying thickness in accordance with at least one embodiment;

[0317] FIG. 300 is a cross-sectional view of an end effector of a surgical stapling instrument in an open configuration;

[0318] FIG. 301 is cross-sectional view of the end effector of FIG. 300 illustrated in a partially-fired configuration;

[0319] FIG. 302 is a cross-sectional view of the end effector of FIG. 300 illustrated in a re-opened configuration;

[0320] FIG. 303 is a cross-sectional view of an end effector of a surgical stapling instrument comprising staple drivers having different heights and a contoured deck surface in accordance with at least one embodiment;

[0321] FIG. 304 is a cross-sectional view of an end effector of a surgical stapling instrument comprising staple drivers having different heights and a stepped deck surface in accordance with at least one embodiment;

[0322] FIG. 305 is a perspective view of a staple cartridge being loaded into an effector of a surgical stapling instrument utilizing a staple cartridge applicator;

[0323] FIG. 306 is a bottom perspective view of the staple cartridge applicator of FIG. 305;

[0324] FIG. 307 is a side view of the staple cartridge applicator of FIG. 305 assembled to a staple cartridge;

[0325] FIG. 308 is a cross-sectional view of the assembly of FIG. 307;

[0326] FIG. 309 is a perspective view of a staple cartridge applicator assembly further including an upper tissue thickness compensator positioned on the top surface of the staple cartridge applicator in accordance with at least one embodiment;

[0327] FIG. 310 is an exploded view of the upper tissue thickness compensator and the staple cartridge applicator of FIG. 309;

[0328] FIG. 310A is an exploded view of a staple cartridge applicator assembly comprising a pull member configured to detach an upper tissue thickness compensator adhered to the staple cartridge applicator;

[0329] FIG. 311 is a partial exploded view of a staple cartridge applicator assembly in accordance with at least one alternative embodiment;

[0330] FIG. 312 is a perspective view of a staple cartridge applicator assembly comprising an upper tissue thickness compensator including a plurality of retention features extending therefrom and a staple cartridge comprising a lower tissue thickness compensator;

[0331] FIG. 313 is an elevational view of the staple cartridge applicator assembly of FIG. 312 positioned within a staple cartridge channel and an anvil being closed onto the staple cartridge applicator assembly;

[0332] FIG. 314 is an elevational view of the anvil of FIG. 313 in a re-opened position and the staple cartridge applicator of FIG. 312 being removed from the end effector;

[0333] FIG. 314A is a cross-sectional view of tissue positioned intermediate the upper tissue thickness compensator and the lower tissue thickness compensator of FIG. 312;

[0334] FIG. 314B is a cross-sectional view illustrating the upper tissue thickness compensator and the lower tissue thickness compensator stapled to the tissue and severed by a cutting member;

[0335] FIG. 315 is a diagram illustrating a tissue thickness compensator being inserted into an anvil in accordance with at least one embodiment;

[0336] FIG. 316 is a cross-sectional view of the tissue thickness compensator of FIG. 315;

[0337] FIG. 317 is an exploded view of a tissue thickness compensator and an anvil in accordance with at least one alternative embodiment;

[0338] FIG. 318 is a perspective view of staple cartridge applicator assembly comprising an upper tissue thickness compensator configured to be attached to an anvil in accordance with at least one embodiment;

[0339] FIG. 319 is an elevational view of the staple cartridge applicator assembly of FIG. 318 positioned within a staple cartridge channel and an anvil being moved toward the upper tissue thickness compensator;

[0340] FIG. 320 illustrates the staple cartridge applicator of FIG. 318 being removed from the end effector after the upper tissue thickness compensator has been engaged with the anvil;

[0341] FIG. 321 is a cross-sectional end view of the anvil being moved toward the upper tissue thickness compensator of FIG. 318;

[0342] FIG. 322 is a cross-sectional end view of the anvil engaged with the upper tissue thickness compensator;

[0343] FIG. 323 is a cross-sectional view of an end effector of a surgical stapling instrument comprising a staple cartridge including a segmentable tissue thickness compensator attached to a support portion of the staple cartridge by a plurality of fasteners;

[0344] FIG. 324 is a cross-sectional view of the end effector of FIG. 323 illustrating a firing member in a partially-fired position;

[0345] FIG. 325 is a cross-sectional view of the end effector of FIG. 323 illustrating the support portion being moved away from the partially-implanted tissue thickness compensator;

[0346] FIG. 326 is a partial perspective view of the support portion of FIG. 323;

[0347] FIG. 327 is a perspective view of a staple-deploying sled in accordance with at least one embodiment;

[0348] FIG. 328 is an elevational view of the sled of FIG. 327;

[0349] FIG. 329 is a perspective view of an end effector of a surgical stapling instrument comprising a staple cartridge including a tissue thickness compensator and a plurality of staple guides positioned on the tissue thickness compensator;

[0350] FIG. 330 is a partial cross-sectional view of the tissue thickness compensator and the staple guides of FIG. 329 in an unfired configuration;

[0351] FIG. 331 is a partial cross-sectional view of the tissue thickness compensator and the staple guides of FIG. 329 in a fired configuration;

[0352] FIG. 332 is a cross-sectional view of a staple cartridge comprising a tissue thickness compensator and a support portion in accordance with at least one embodiment;

[0353] FIG. 333 is a partial cross-sectional view of a tissue thickness compensator, a staple guide layer, and a staple in an unfired position;

[0354] FIG. 334 is a partial cross-sectional view of a tissue thickness compensator, a staple guide layer, and a staple in an unfired position in accordance with at least one alternative embodiment;

[0355] FIG. 335 is a partial cross-sectional view of a tissue thickness compensator, a staple guide layer, and a staple in an unfired position in accordance with at least one alternative embodiment;

[0356] FIG. 336 is a partial cross-sectional view of a tissue thickness compensator, a staple guide layer, and a staple in an unfired position in accordance with at least one alternative embodiment;

[0357] FIG. 337 is a partial cross-sectional view of a tissue thickness compensator, a staple guide layer, and a staple in an unfired position in accordance with at least one alternative embodiment;

[0358] FIG. 338 is a partial cross-sectional view of a tissue thickness compensator, a staple guide layer, and a staple in an unfired position in accordance with at least one alternative embodiment;

[0359] FIG. 339 is a partial cross-sectional view of a tissue thickness compensator, a staple guide layer, and a staple in an unfired position in accordance with at least one alternative embodiment;

[0360] FIG. 340 is a detail view of a region surrounding a tip of the staple of FIG. 339;

[0361] FIG. 341 is a partial cross-sectional view of a tissue thickness compensator, a staple guide layer, and a staple in an unfired position in accordance with at least one alternative embodiment;

[0362] FIG. 342 is a detail view of a region surrounding a tip of the staple of FIG. 341;

[0363] FIG. 343 is a partial cross-sectional view of a tissue thickness compensator, a staple guide layer, and a staple in an unfired position in accordance with at least one alternative embodiment;

[0364] FIG. 344 is a perspective view of a staple guide layer and a plurality of staples in an unfired position in accordance with at least one alternative embodiment;

[0365] FIG. 345 is an end view of a tissue thickness compensator configured to be used with a circular surgical stapler;

[0366] FIG. 346 is a perspective view of the tissue thickness compensator and the circular surgical stapler of FIG. 345;

[0367] FIG. 347 is an end view of a tissue thickness compensator configured to be used with a circular surgical stapler in accordance with at least one alternative embodiment;

[0368] FIG. 348 is a perspective view of the tissue thickness compensator and the circular surgical stapler of FIG. 347;

[0369] FIG. 349 is an end view of a tissue thickness compensator configured to be used with a circular surgical stapler;

[0370] FIG. 350 is an end view of the tissue thickness compensator of FIG. 349 in a partially expanded configuration;

[0371] FIG. 351 is an elevational view of a surgical stapling instrument comprising a staple cartridge in accordance with at least one embodiment;

[0372] FIG. 352 is an end view of the surgical stapling instrument of FIG. 351 positioned relative to tissue;

[0373] FIG. 353 is an end view of the surgical stapling instrument of FIG. 351 further comprising a tissue thickness compensator positioned between the staple cartridge and the tissue;

[0374] FIG. 354 is a partial perspective view of staples deployed into tissue from the surgical stapling instrument of FIG. 351 without a tissue thickness compensator;

[0375] FIG. 355 is a partial perspective view of staples deployed into tissue from the surgical stapling instrument of FIG. 351 with a tissue thickness compensator;

[0376] FIG. 356 is a partial cross-sectional view of the end effector of the surgical stapling instrument of FIG. 351 comprising an anvil plate in a first position;

[0377] FIG. 357 is a partial cross-sectional view of the end effector of the surgical stapling instrument of FIG. 351 illustrating the anvil plate of FIG. 356 in a second position;

[0378] FIG. 358 is a cross-sectional view of an end effector of a surgical stapling instrument comprising a staple cartridge including a gap setting element;

[0379] FIG. 359 is a perspective view illustrating a firing member cutting the gap setting element of FIG. 358 at the end of firing stroke of the firing member;

[0380] FIG. 360 is a cross-sectional view of an end effector of a surgical stapling instrument comprising a staple cartridge including a flexible nose;

[0381] FIG. 361 is a cross-sectional view of the end effector of FIG. 360 illustrating the nose in a flexed configuration;

[0382] FIG. 362 is a cross-sectional view of an end effector of a surgical stapling instrument comprising a staple cartridge including a slidable portion;

[0383] FIG. 363 is a cross-sectional view of the end effector of FIG. 362 illustrating the slidable portion slid distally;

[0384] FIG. 364 is a cross-sectional view of an end effector of a surgical stapling instrument comprising a support portion comprising an inclined deck surface and a tissue thickness compensator comprising a varying thickness;

[0385] FIG. 365 is a cross-sectional view of an end effector of a surgical stapling instrument comprising a support portion comprising an inclined deck surface and a tissue thickness compensator comprising a uniform thickness;

[0386] FIG. 366 is a perspective view of a staple cartridge comprising a tissue thickness compensator having a varying thickness;

[0387] FIG. 367 is an end view of the staple cartridge of FIG. 366;

[0388] FIG. 368 is a cross-sectional perspective view of a tissue thickness compensator comprising longitudinal layers;

[0389] FIG. 369 is a cross-sectional perspective view of a tissue thickness compensator comprising a plurality of layers in accordance with at least one alternative embodiment;

[0390] FIG. 370 is a perspective view of a disposable loading unit comprising retention members configured to releasably hold a tissue thickness compensator thereto;

[0391] FIG. 371 is a perspective view of a tissue thickness compensator including retention members configured to releasably hold the tissue thickness compensator to a disposable loading unit;

[0392] FIG. 372 is a perspective view of the tissue thickness compensator of FIG. 371 attached to a disposable loading unit;

[0393] FIG. 373 is an end view of the disposable loading unit of FIG. 372;

[0394] FIG. 374 is a perspective view of a tissue thickness compensator including retention members configured to releasably hold the tissue thickness compensator to a disposable loading unit;

[0395] FIG. 375 is a perspective view of the tissue thickness compensator of FIG. 374 attached to a disposable loading unit;

[0396] FIG. 376 is an end view of the disposable loading unit of FIG. 375;

[0397] FIG. 377 is a perspective view of a tissue thickness compensator including a retention member configured to releasably hold the tissue thickness compensator to a disposable loading unit;

[0398] FIG. 378 is a perspective view of the tissue thickness compensator of FIG. 377 attached to a disposable loading unit;

[0399] FIG. 379 is a perspective view of a tissue thickness compensator applicator positioned within an effector of a disposable loading unit;

[0400] FIG. 380 is a top perspective view of the tissue thickness compensator applicator of FIG. 379;

[0401] FIG. 381 is a bottom perspective view of the tissue thickness compensator applicator of FIG. 379;

[0402] FIG. 382 is a perspective view of a tissue thickness compensator applicator positioned within an effector of a disposable loading unit in accordance with at least one alternative embodiment;

[0403] FIG. 383 is a top perspective view of the tissue thickness compensator applicator of FIG. 382;

[0404] FIG. 384 is a bottom perspective view of the tissue thickness compensator applicator of FIG. 382;

[0405] FIG. 385 is an elevational view of a disposable loading unit including a pivotable jaw configured to support a staple cartridge;

[0406] FIG. 386 is a cross-sectional view of a staple cartridge comprising a tissue thickness compensator attached to a support portion of the staple cartridge in accordance with at least one embodiment;

[0407] FIG. 387 is a cross-sectional view of a staple cartridge comprising a tissue thickness compensator attached to a support portion of the staple cartridge in accordance with at least one embodiment;

[0408] FIG. 388 is a cross-sectional view of a staple cartridge comprising a tissue thickness compensator attached to a support portion of the staple cartridge in accordance with at least one embodiment;

[0409] FIG. 389 is a perspective view of the tissue thickness compensator of FIG. 387;

[0410] FIG. 390 is a perspective view of a tissue thickness compensator in an end effector of a surgical instrument according to at least one embodiment;

[0411] FIG. 391 is a detail view of nonwoven material of the tissue thickness compensator of FIG. 390;

[0412] FIG. 392 is an elevational view depicting the tissue thickness compensator of FIG. 390 implanted against tissue and released from the end effector;

[0413] FIG. 393 is a detail view of nonwoven material of a tissue thickness compensator according to at least one embodiment;

[0414] FIG. 394 is a schematic depicting clusters of randomly oriented crimped fibers according to at least one embodiment;

[0415] FIG. 395 is a schematic depicting a cluster of randomly oriented crimped fibers according to at least one embodiment;

[0416] FIG. 396 is a schematic depicting an arrangement of crimped fibers according to at least one embodiment;

[0417] FIG. 397 is a schematic depicting an arrangement of crimped fibers according to at least one embodiment;

[0418] FIG. 398 is a schematic depicting an arrangement of crimped fibers according to at least one embodiment;

[0419] FIG. 399 is a plan cross-sectional view of coiled fibers in a tissue thickness compensator according to at least one embodiment;

[0420] FIG. 399A is a plan cross-sectional view of the coiled fibers of FIG. 399;

[0421] FIG. 399B is a cross-sectional detail view of the tissue thickness compensator of FIG. 399;

[0422] FIG. 400 is a perspective view of a tissue thickness compensator in an end effector of a surgical instrument according to at least one embodiment;

[0423] FIG. 401 is a diagram depicting deformation of the tissue thickness compensator of FIG. 400;

[0424] FIG. 402 is a schematic of woven suture for a tissue thickness compensator depicting the woven suture in a loaded configuration according to at least one embodiment;

[0425] FIG. 403 is a schematic of the woven suture of FIG. 402 depicting the woven suture in a released configuration;

[0426] FIG. 404 is a plan view of a tissue thickness compensator having the woven suture of FIG. 402 in an end effector of a surgical instrument;

[0427] FIG. 405 is a perspective view of a tissue thickness compensator in an end effector of a surgical instrument according to at least one embodiment;

[0428] FIG. 406 is a partial plan view of the tissue thickness compensator of FIG. 405;

[0429] FIG. 407 is an exploded view of the fastener cartridge assembly of the end effector and tissue thickness compensator of FIG. 390;

[0430] FIG. 408 is a partial cross-sectional view of the fastener cartridge assembly of FIG. 407 depicting unfired, partially fired, and fired fasteners;

[0431] FIG. 409 is an elevational view of the fastener cartridge assembly of FIG. 407 depicting a driver firing fasteners from staple cavities of the fastener cartridge assembly into the tissue thickness compensator;

[0432] FIG. 410 is a detail view of the fastener cartridge assembly of FIG. 409;

[0433] FIG. 411 is an elevational view of the tissue thickness compensator of FIG. 390 and tissue captured within fired fasteners;

[0434] FIG. 412 is an elevational view of the tissue thickness compensator of FIG. 390 and tissue captured within fired fasteners;

[0435] FIG. 413 is a perspective view of a tissue thickness compensator in an end effector of a surgical instrument according to at least one embodiment;

[0436] FIG. 414 is a diagram depicting deformation of a deformable tube of the tissue thickness compensator of FIG. 413;

[0437] FIG. 415 is a detail view of the deformable tube of the tissue thickness compensator of FIG. 413;

[0438] FIG. 416 is a diagram depicting deformation of a deformable tube of a tissue thickness compensator according to at least one embodiment;

[0439] FIG. 417 is an elevational view of a tissue thickness compensator comprising a tubular element implanted against tissue according to at least one embodiment;

[0440] FIG. 418 is an elevational view of a tissue thickness compensator comprising tubular elements implanted against tissue according to at least one embodiment;

[0441] FIG. 419 is a partial perspective view of a deformable tube comprising a tubular lattice according to at least one embodiment;

[0442] FIG. 420 is an elevational view of a tubular strand of the deformable tube of FIG. 419.

[0443] FIG. 421 is an elevational view of the deformable tube of FIG. 419;

[0444] FIG. 422 is an elevational view of multiple tubular strands for the deformable tube of FIG. 419 according to various embodiments;

[0445] FIG. 423 is an elevational view of the tubular lattice of FIG. 419 implanted against tissue;

[0446] FIG. 424 is a partial perspective view of a deformable tube according to at least one embodiment;

[0447] FIG. 425 is a partial perspective view of a deformable tube according to at least one embodiment;

[0448] FIG. 426 is a partial perspective view of a deformable tube according to at least one embodiment;

[0449] FIG. 427 is an elevational view of the deformable tube of FIG. 426;

[0450] FIG. 428 is a partial perspective view of a deformable tube according to at least one embodiment;

[0451] FIG. 429 is a partial perspective view of a deformable tube according to at least one embodiment;

[0452] FIG. 430 is a partial perspective view of a deformable tube according to at least one embodiment;

[0453] FIG. 431 is a perspective view of a tissue thickness compensator positioned in an end effector of a surgical instrument according to at least one embodiment;

[0454] FIG. 432 is an elevational view of a tubular element of the tissue thickness compensator of FIG. 431;

[0455] FIG. 433 is an elevational cross-sectional view of the tissue thickness compensator and the end effector of FIG. 431 depicting the end effector in an unclamped configuration;

[0456] FIG. 434 is an elevational cross-sectional view of the tissue thickness compensator and the end effector of FIG. 431 depicting the end effector in a clamped and fired configuration;

[0457] FIG. 435 is an elevational cross-sectional view of a tissue thickness compensator positioned in an end effector of a surgical instrument according to at least one embodiment;

[0458] FIG. 436 is an elevational cross-sectional view of the tissue thickness compensator and the end effector of FIG. 435 depicting the end effector in a clamped and fired configuration;

[0459] FIG. 437 is an elevational cross-sectional view of a tissue thickness compensator in the end effector of a surgical instrument according to at least one embodiment;

[0460] FIG. 438 is a cross-sectional elevational view of a tissue thickness compensator positioned in an end effector of a surgical instrument according to at least one embodiment;

[0461] FIG. 439 is a cross-sectional elevational view of the tissue thickness compensator and the end effector of FIG. 438 depicting the end effector in a clamped and fired configuration;

[0462] FIG. 440 is a perspective view of a tissue thickness compensator positioned in an end effector of a surgical instrument according to at least one embodiment;

[0463] FIG. 441 is an elevational cross-sectional view of a tissue thickness compensator positioned in an end effector of a surgical instrument according to at least one embodiment;

[0464] FIG. 442 is an elevational cross-sectional view of a tissue thickness compensator positioned in an end effector of a surgical instrument according to at least one embodiment;

[0465] FIG. 443 is an elevational cross-sectional view of a tissue thickness compensator positioned in an end effector of a surgical instrument according to at least one embodiment;

[0466] FIG. 444 is an elevational cross-sectional view of a tissue thickness compensator positioned in an end effector of a surgical instrument according to at least one embodiment;

[0467] FIG. 445 is a partial plan view of a tissue thickness compensator positioned in an end effector of a surgical instrument according to at least one embodiment;

[0468] FIG. 446 is a partial plan view of a tissue thickness compensator positioned in an end effector of a surgical instrument according to at least one embodiment;

[0469] FIG. 447 is a partial elevational cross-sectional view of the tissue thickness compensator and the end effector of FIG. 445 depicting the end effector in an unclamped configuration;

[0470] FIG. 448 is a partial elevational cross-sectional view of the tissue thickness compensator and the end effector of FIG. 445 depicting the end effector in a clamped configuration;

[0471] FIG. 449 is a perspective view of a tissue thickness compensator in an end effector of a surgical instrument according to at least one embodiment;

[0472] FIG. 450 is an elevational view of the tissue thickness compensator and the end effector of FIG. 449;

[0473] FIG. 451 is a perspective view of the tissue thickness compensator and the end effector of FIG. 449 depicting the anvil of the end effector moving towards a clamped configuration;

[0474] FIG. 452 is an elevational view of the tissue thickness compensator and the end effector of FIG. 449 depicting the end effector in a clamped configuration;

[0475] FIG. 453 is an elevational cross-sectional view of tubular elements of the tissue thickness compensator of FIG. 449 in an undeformed configuration;

[0476] FIG. 454 is an elevational cross-sectional view of tubular elements of the tissue thickness compensator of FIG. 449 in a deformed configuration;

[0477] FIG. 455 is a perspective view of a tissue thickness compensator in an end effector of a surgical instrument according to at least one embodiment;

[0478] FIG. 456 is an elevational cross-sectional view of the tissue thickness compensator and the end effector of FIG. 455 depicting the end effector in a clamped configuration;

[0479] FIG. 457 is an elevational cross-sectional view of the tissue thickness compensator and the end effector of FIG. 455 depicting the end effector in a fired and partially unclamped configuration;

[0480] FIG. 458 is a perspective view of a tissue thickness compensator positioned in an end effector of a surgical instrument according to at least one embodiment;

[0481] FIG. 459 is an elevational cross-sectional view of a tissue thickness compensator secured to an anvil of an end effector of a surgical instrument according to at least one embodiment;

[0482] FIG. 460 is an elevational cross-sectional view of the tissue thickness compensator and the end effector of FIG. 459 depicting the end effector in a clamped configuration;

[0483] FIG. 461 is an elevational cross-sectional view of the tissue thickness compensator and the end effector of FIG. 459 depicting the end effector in a fired and partially unclamped configuration;

[0484] FIG. 462 is a detail view of the tissue thickness compensator and the end effector of FIG. 461;

[0485] FIG. 463 is an elevational cross-sectional view of a tissue thickness compensator clamped in an end effector of a surgical instrument depicting deployment of staples by a staple- firing sled according to at least one embodiment;

[0486] FIG. 464 is an elevational cross-sectional view of the tissue thickness compensator and the end effector of FIG. 463 depicting the end effector in a clamped configuration;

[0487] FIG. 465 is an elevational cross-sectional view of the tissue thickness compensator and the end effector of FIG. 463 depicting the end effector in a fired configuration;

[0488] FIG. 466 is a perspective view of a tissue thickness compensator in an end effector of a surgical instrument according to at least one embodiment;

[0489] FIG. 467 is a perspective view of a tubular element of the tissue thickness compensator of FIG. 466;

[0490] FIG. 468 is a perspective view of the tubular element of FIG. 467 severed between a first and second end;

[0491] FIG. 469 is a perspective view of the tissue thickness compensator of FIG. 466 depicting a cutting element severing the tissue thickness compensator and staples engaging the tissue thickness compensator;

[0492] FIG. 470 is perspective view of a frame configured to make the tissue thickness compensator of FIG. 466 according to at least one embodiment;

[0493] FIG. 471 is an elevational cross-sectional view of the frame of FIG. 470 depicting the tissue thickness compensator of FIG. 466 curing in the frame;

[0494] FIG. 472 is an elevational cross-sectional view of the tissue thickness compensator removed from the frame of FIG. 471 and prepared for trimming by at least one cutting instrument;

[0495] FIG. 473 is an elevational cross-sectional view of the tissue thickness compensator of FIG. 472 after at least one cutting instrument has trimmed the tissue thickness compensator;

[0496] FIG. 474 is an elevational cross-sectional view of the tissue thickness compensator formed in the frame of FIG. 471 depicting severable tubes having various cross-sectional geometries;

[0497] FIG. 475 is a perspective view of a tissue thickness compensator in an end effector of a surgical instrument according to at least one embodiment;

[0498] FIG. 476 is a detail view of the tissue thickness compensator of FIG. 475 according to at least one embodiment;

[0499] FIG. 477 is a partial perspective view of a tissue thickness compensator according to at least one embodiment;

[0500] FIG. 478 is a partial perspective view of a tissue thickness compensator according to at least one embodiment;

[0501] FIG. 479A is an elevational cross-sectional view of the tissue thickness compensator and the end effector of FIG. 475 depicting the end effector in an unclamped configuration;

[0502] FIG. 479B is an elevational cross-sectional view of the tissue thickness compensator and the end effector of FIG. 475 depicting the end effector in a clamped configuration;

[0503] FIG. 479C is an elevational cross-sectional view of the tissue thickness compensator and the end effector of FIG. 475 depicting the end effector in a clamped and fired configuration;

[0504] FIG. 479D is an elevational cross-sectional view of the tissue thickness compensator of FIG. 475 captured in fired staples;

[0505] FIG. 479E is an elevational cross-sectional view of the tissue thickness compensator of FIG. 475 captured in fired staples depicting further expansion of the tissue thickness compensator;

[0506] FIG. 480 is a perspective cross-sectional view of a tissue thickness compensator in an end effector of a surgical instrument according to at least one embodiment;

[0507] FIG. 481 is a partial elevational view of the tissue thickness compensator of FIG. 480 captured in a fired staple;

[0508] FIG. 482 is an elevational view of a deformable tube of the tissue thickness compensator of FIG. 480;

[0509] FIG. 483 is an elevational view of a deformable tube according to at least one embodiment;

[0510] FIG. 484 is a perspective cross-sectional view of the tissue thickness compensator of FIG. 480;

[0511] FIG. 485 is a perspective cross-sectional view of a tissue thickness compensator in an end effector of a surgical instrument according to at least one embodiment;

[0512] FIG. 486 is a perspective view of a tissue thickness compensator according to at least one embodiment;

[0513] FIG. 487 is a partial elevational cross-sectional view of the tissue thickness compensator of FIG. 486 depicting a fastener engaged with tissue and with the tissue thickness compensator;

[0514] FIG. 488 is a perspective cross-sectional view of a tissue thickness compensator according to at least one embodiment;

[0515] FIG. 489 is an elevational view of a tissue thickness compensator according to at least one embodiment;

[0516] FIG. 490 is an elevational view of a tissue thickness compensator according to at least one embodiment;

[0517] FIG. 491 is an elevational view of a tissue thickness compensator positioned in a circular end effector of a surgical instrument according to at least one embodiment;

[0518] FIG. 492 is an elevational view of a tissue thickness compensator according to at least one embodiment;

[0519] FIG. 493 is an elevational view of a tissue thickness compensator according to at least one embodiment;

[0520] FIG. 494 is an elevational view of a tissue thickness compensator according to at least one embodiment;

[0521] FIG. 495 is an elevational view of a tissue thickness compensator according to at least one embodiment;

[0522] FIG. 496 is an elevational view of a tissue thickness compensator according to at least one embodiment;

[0523] FIG. 497 is a partial perspective view of a tissue thickness compensator according to at least one embodiment;

[0524] FIG. 498 is a partial perspective view of a tissue thickness compensator positioned in an end effector of a surgical instrument according to at least one embodiment;

[0525] FIG. 499 is a partial perspective view of a tissue thickness compensator with a fastener positioned in the apertures thereof according to at least one embodiment;

[0526] FIG. 500 is a partial perspective view of the tissue thickness compensator of FIG. 498 depicting the tissue thickness compensator in an undeformed configuration;

[0527] FIG. 501 is a partial perspective view of the tissue thickness compensator of FIG. 498 depicting the tissue thickness compensator in a partially deformed configuration;

[0528] FIG. 502 is a partial perspective view of the tissue thickness compensator of FIG. 498 depicting the tissue thickness compensator in a deformed configuration;

[0529] FIG. 503 is a perspective view of a tissue thickness compensator according to at least one embodiment;

[0530] FIG. 504 is a perspective view of an end effector of a stapling instrument comprising an anvil and a staple cartridge in accordance with at least one embodiment;

[0531] FIG. 505 is a cross-sectional view of the end effector of FIG. 504 illustrating staples positioned within the staple cartridge in an unfired state and a tissue thickness compensator comprising a sealed vessel in an unpunctured state, wherein the vessel is depicted with portions thereof removed for the purposes of illustration;

[0532] FIG. 506 is a cross-sectional view of the end effector of FIG. 504 illustrating the staples of FIG. 505 in an at least partially fired state and the vessel in an at least partially punctured state;

[0533] FIG. 507 is a perspective view of an end effector of a stapling instrument comprising an anvil and a staple cartridge in accordance with at least one embodiment;

[0534] FIG. 508 is a cross-sectional view of the end effector of FIG. 507 illustrating staples positioned within the staple cartridge in an unfired state and sealed vessels positioned within a

tissue thickness compensator of the staple cartridge in an unpunctured state, wherein the vessels are depicted with portions thereof removed for the purposes of illustration;

[0535] FIG. 509 is a cross-sectional view of the end effector of FIG. 507 illustrating the staples of FIG. 508 in an at least partially fired state and the vessels in the staple cartridge in an at least partially punctured state;

[0536] FIG. 510 is a perspective view of an end effector of a stapling instrument comprising an anvil and a sealed vessel attached to the anvil in accordance with at least one alternative embodiment wherein the vessel is depicted with portions thereof removed for the purposes of illustration;

[0537] FIG. 511 is a cross-sectional view of the end effector of FIG. 510 illustrating staples at least partially fired from a staple cartridge and the vessels attached to the anvil in an at least partially punctured state;

[0538] FIG. 512 is a cross-sectional view of the vessel attached to the anvil of FIG. 510 illustrated in an expanded state;

[0539] FIG. 513 is a detail view of the vessel attached to the anvil of FIG. 512 illustrated in an expanded state;

[0540] FIG. 514 illustrates a vessel extending in a direction transverse to a line of staples;

[0541] FIG. 515 illustrates a plurality of vessels extending in directions which are transverse to a line of staples;

[0542] FIG. 516 is a cross-sectional view of a staple cartridge in accordance with various embodiments;

[0543] FIG. 517 is a partial cross-section view of FIG. 516 in an implanted condition;

[0544] FIG. 518A is a partial perspective view of a tissue thickness compensator prior to expansion;

[0545] FIG. 518B is a partial perspective view of a tissue thickness compensator of FIG. 518 during expansion;

[0546] FIG. 519 is a partial perspective view of a tissue thickness compensator comprising a fluid swellable composition according to various embodiments;

[0547] FIG. 520 is a cross-sectional view of tissue positioned adjacent a tissue thickness compensator according to various embodiments;

[0548] FIG. 521 is a partial cross-sectional view of FIG. 520 after the staple cartridge has been fired;

[0549] FIG. 522 is a diagram illustrating the tissue thickness compensator of FIG. 520 implanted adjacent the tissue;

[0550] FIG. 523 is a partial perspective view of a tissue thickness compensator according to various embodiments;

[0551] FIG. 524 is a perspective view of a jaw configured to receive the tissue thickness compensator of FIG. 523;

[0552] FIG. 525 is a partial cross-sectional view of a staple cartridge illustrating staples being deployed from the staple cartridge;

[0553] FIG. 526 is a perspective view of an upper tissue thickness compensator and a lower tissue thickness compensator positioned within an effector of a disposable loading unit;

[0554] FIG. 527A is a cross-sectional view of the lower tissue thickness compensator of FIG. 526 being manufactured in a mold in accordance with various embodiments;

[0555] FIG. 527B is a cross-sectional view of a trilayer tissue thickness compensator being manufactured in a mold in accordance with various embodiments;

[0556] FIG. 528 is a cross-sectional view of an anvil comprising a tissue thickness compensator comprising reinforcement material in accordance with various embodiments;

[0557] FIG. 529 is cross-sectional view of a tissue positioned intermediate the upper tissue thickness compensator and lower tissue thickness compensator in accordance with various embodiments;

[0558] FIG. 530 is a cross-sectional view of FIG. 529 illustrating staples being deployed from the staple cartridge;

[0559] FIG. 531 is a cross-sectional view of FIG. 529 after the staple cartridge has been fired;

[0560] FIG. 532A illustrates a needle configured to deliver a fluid to a tissue thickness compensator attached to a staple cartridge according to various embodiments;

[0561] FIG. 532B is a cross-sectional view of a staple cartridge comprising a tissue thickness compensator configured to receive the needle of FIG. 532A;

[0562] FIG. 533 illustrates a method of manufacturing a tissue thickness compensator according to various embodiments;

[0563] FIG. 534 is a diagram and a method of forming an expanding thickness compensator according to various embodiments;

[0564] FIG. 535 illustrates a micelle comprising a hydrogel precursor; and

[0565] FIG. 536 is a diagram of a surgical instrument comprising a tissue thickness compensator and fluids that may be delivered to the tissue thickness compensator according to various embodiments.

[0566] FIG. 537 is a partial perspective view of a tissue thickness compensator secured to an anvil of an end effector of a surgical instrument according to at least one embodiment.

[0567] FIG. 538 is a perspective view of a tubular element of the tissue thickness compensator of FIG. 537.

[0568] FIG. 539 is a perspective view of the tubular element of FIG. 538 depicting the tubular element severed into two halves and fluid contacting the hydrophilic substance within each half.

[0569] FIG. 540 is a perspective view of a half of the severed tubular element of FIG. 539 depicting expansion of the severed tubular element.

[0570] Corresponding reference characters indicate corresponding parts throughout the several views. The exemplifications set out herein illustrate certain embodiments of the invention, in one form, and such exemplifications are not to be construed as limiting the scope of the invention in any manner.

DETAILED DESCRIPTION

[0571] The Applicant of the present application also owns the U.S. Patent Applications identified below which are each herein incorporated by reference in their respective entirety:

U.S. Patent Application Serial No. 12/894,311, entitled SURGICAL INSTRUMENTS WITH RECONFIGURABLE SHAFT SEGMENTS (Attorney Docket No. END6734USNP/100058);

U.S. Patent Application Serial No. 12/894,340, entitled SURGICAL STAPLE CARTRIDGES SUPPORTING NON-LINEARLY ARRANGED STAPLES AND SURGICAL STAPLING INSTRUMENTS WITH COMMON STAPLE-FORMING POCKETS (Attorney Docket No. END6735USNP/100059);

U.S. Patent Application Serial No. 12/894,327, entitled JAW CLOSURE ARRANGEMENTS FOR SURGICAL INSTRUMENTS (Attorney Docket No. END6736USNP/100060);

U.S. Patent Application Serial No. 12/894,351, entitled SURGICAL CUTTING AND FASTENING INSTRUMENTS WITH SEPARATE AND DISTINCT FASTENER DEPLOYMENT AND TISSUE CUTTING SYSTEMS (Attorney Docket No. END6839USNP/100524);
U.S. Patent Application Serial No. 12/894,338, entitled IMPLANTABLE FASTENER CARTRIDGE HAVING A NON-UNIFORM ARRANGEMENT (Attorney Docket No. END6840USNP/100525);
U.S. Patent Application Serial No. 12/894,369, entitled IMPLANTABLE FASTENER CARTRIDGE COMPRISING A SUPPORT RETAINER (Attorney Docket No. END6841USNP/100526);
U.S. Patent Application Serial No. 12/894,312, entitled IMPLANTABLE FASTENER CARTRIDGE COMPRISING MULTIPLE LAYERS (Attorney Docket No. END6842USNP/100527);
U.S. Patent Application Serial No. 12/894,377, entitled SELECTIVELY ORIENTABLE IMPLANTABLE FASTENER CARTRIDGE (Attorney Docket No. END6843USNP/100528);
U.S. Patent Application Serial No. 12/894,339, entitled SURGICAL STAPLING INSTRUMENT WITH COMPACT ARTICULATION CONTROL ARRANGEMENT (Attorney Docket No. END6847USNP/100532);
U.S. Patent Application Serial No. 12/894,360, entitled SURGICAL STAPLING INSTRUMENT WITH A VARIABLE STAPLE FORMING SYSTEM (Attorney Docket No. END6848USNP/100533);
U.S. Patent Application Serial No. 12/894,322, entitled SURGICAL STAPLING INSTRUMENT WITH INTERCHANGEABLE STAPLE CARTRIDGE ARRANGEMENTS (Attorney Docket No. END6849USNP/100534);
U.S. Patent Application Serial No. 12/894,350, entitled SURGICAL STAPLE CARTRIDGES WITH DETACHABLE SUPPORT STRUCTURES AND SURGICAL STAPLING INSTRUMENTS WITH SYSTEMS FOR PREVENTING ACTUATION MOTIONS WHEN A CARTRIDGE IS NOT PRESENT (Attorney Docket No. END6855USNP/100540);
U.S. Patent Application Serial No. 12/894,383, entitled IMPLANTABLE FASTENER CARTRIDGE COMPRISING BIOABSORBABLE LAYERS (Attorney Docket No. END6856USNP/100541);

U.S. Patent Application Serial No. 12/894,389, entitled COMPRESSIBLE FASTENER CARTRIDGE (Attorney Docket No. END6857USNP/100542);
U.S. Patent Application Serial No. 12/894,345, entitled FASTENERS SUPPORTED BY A FASTENER CARTRIDGE SUPPORT (Attorney Docket No. END6858USNP/100543);
U.S. Patent Application Serial No. 12/894,306, entitled COLLAPSIBLE FASTENER CARTRIDGE (Attorney Docket No. END6859USNP/100544);
U.S. Patent Application Serial No. 12/894,318, entitled FASTENER SYSTEM COMPRISING A PLURALITY OF CONNECTED RETENTION MATRIX ELEMENTS (Attorney Docket No. END6860USNP/100546);
U.S. Patent Application Serial No. 12/894,330, entitled FASTENER SYSTEM COMPRISING A RETENTION MATRIX AND AN ALIGNMENT MATRIX (Attorney Docket No. END6861USNP/100547);
U.S. Patent Application Serial No. 12/894,361, entitled FASTENER SYSTEM COMPRISING A RETENTION MATRIX (Attorney Docket No. END6862USNP/100548);
U.S. Patent Application Serial No. 12/894,367, entitled FASTENING INSTRUMENT FOR DEPLOYING A FASTENER SYSTEM COMPRISING A RETENTION MATRIX (Attorney Docket No. END6863USNP/100549);
U.S. Patent Application Serial No. 12/894,388, entitled FASTENER SYSTEM COMPRISING A RETENTION MATRIX AND A COVER (Attorney Docket No. END6864USNP/100550);
U.S. Patent Application Serial No. 12/894,376, entitled FASTENER SYSTEM COMPRISING A PLURALITY OF FASTENER CARTRIDGES (Attorney Docket No. END6865USNP/100551);
U.S. Patent Application Serial No. 13/097,865, entitled SURGICAL STAPLER ANVIL COMPRISING A PLURALITY OF FORMING POCKETS (Attorney Docket No. END6735USCIP1/100059CIP1);
U.S. Patent Application Serial No. 13/097,936, entitled TISSUE THICKNESS COMPENSATOR FOR A SURGICAL STAPLER (Attorney Docket No. END6736USCIP1/100060CIP1);
U.S. Patent Application Serial No. 13/097,954, entitled STAPLE CARTRIDGE COMPRISING A VARIABLE THICKNESS COMPRESSIBLE PORTION (Attorney Docket No. END6840USCIP1/100525CIP1);

U.S. Patent Application Serial No. 13/097,856, entitled STAPLE CARTRIDGE COMPRISING STAPLES POSITIONED WITHIN A COMPRESSIBLE PORTION THEREOF (Attorney Docket No. END6841USCIP1/100526CIP1);
U.S. Patent Application Serial No. 13/097,928, entitled TISSUE THICKNESS COMPENSATOR COMPRISING DETACHABLE PORTIONS (Attorney Docket No. END6842USCIP1/100527CIP1);
U.S. Patent Application Serial No. 13/097,891, entitled TISSUE THICKNESS COMPENSATOR FOR A SURGICAL STAPLER COMPRISING AN ADJUSTABLE ANVIL (Attorney Docket No. END6843USCIP1/100528CIP1);
U.S. Patent Application Serial No. 13/097,948, entitled STAPLE CARTRIDGE COMPRISING AN ADJUSTABLE DISTAL PORTION (Attorney Docket No. END6847USCIP1/100532CIP1);
U.S. Patent Application Serial No. 13/097,907, entitled COMPRESSIBLE STAPLE CARTRIDGE ASSEMBLY (Attorney Docket No. END6848USCIP1/100533CIP1);
U.S. Patent Application Serial No. 13/097,861, entitled TISSUE THICKNESS COMPENSATOR COMPRISING PORTIONS HAVING DIFFERENT PROPERTIES (Attorney Docket No. END6849USCIP1/100534CIP1);
U.S. Patent Application Serial No. 13/097,869, entitled STAPLE CARTRIDGE LOADING ASSEMBLY (Attorney Docket No. END6855USCIP1/100540CIP1);
U.S. Patent Application Serial No. 13/097,917, entitled COMPRESSIBLE STAPLE CARTRIDGE COMPRISING ALIGNMENT MEMBERS (Attorney Docket No. END6856USCIP1/100541CIP1);
U.S. Patent Application Serial No. 13/097,873, entitled STAPLE CARTRIDGE COMPRISING A RELEASABLE PORTION (Attorney Docket No. END6857USCIP1/100542CIP1);
U.S. Patent Application Serial No. 13/097,938, entitled STAPLE CARTRIDGE COMPRISING COMPRESSIBLE DISTORTION RESISTANT COMPONENTS (Attorney Docket No. END6858USCIP1/100543CIP1);
U.S. Patent Application Serial No. 13/097,924, entitled STAPLE CARTRIDGE COMPRISING A TISSUE THICKNESS COMPENSATOR (Attorney Docket No. END6859USCIP1/100544CIP1);
U.S. Patent Application Serial No. 13/242,029, entitled SURGICAL STAPLER WITH FLOATING ANVIL (Attorney Docket No. END6841USCIP2/100526CIP2);

U.S. Patent Application Serial No. 13/242,066, entitled CURVED END EFFECTOR FOR A STAPLING INSTRUMENT (Attorney Docket No. END6841USCIP3/100526CIP3);
U.S. Patent Application Serial No. 13/242,086, entitled STAPLE CARTRIDGE INCLUDING COLLAPSIBLE DECK (Attorney Docket No. END7020USNP/110374);
U.S. Patent Application Serial No. 13/241,912, entitled STAPLE CARTRIDGE INCLUDING COLLAPSIBLE DECK ARRANGEMENT (Attorney Docket No. END7019USNP/110375);
U.S. Patent Application Serial No. 13/241,922, entitled SURGICAL STAPLER WITH STATIONARY STAPLE DRIVERS (Attorney Docket No. END7013USNP/110377);
U.S. Patent Application Serial No. 13/241,637, entitled SURGICAL INSTRUMENT WITH TRIGGER ASSEMBLY FOR GENERATING MULTIPLE ACTUATION MOTIONS (Attorney Docket No. END6888USNP3/110378); and
U.S. Patent Application Serial No. 13/241,629, entitled SURGICAL INSTRUMENT WITH SELECTIVELY ARTICULATABLE END EFFECTOR (Attorney Docket No. END6888USNP2/110379).

[0572] The Applicant of the present application also owns the U.S. Patent Applications identified below which were filed on even date herewith and which are each herein incorporated by reference in their respective entirety:
U.S. Application Serial No. _____, entitled TISSUE THICKNESS COMPENSATOR COMPRISING A PLURALITY OF CAPSULES, (Attorney Docket No. END6864USCIP1/100550CIP1);
U.S. Application Serial No. _____, entitled TISSUE THICKNESS COMPENSATOR COMPRISING A PLURALITY OF LAYERS, (Attorney Docket No. END6864USCIP2/100550CIP2);
U.S. Application Serial No. _____, entitled TISSUE THICKNESS COMPENSATOR COMPRISING A RESERVOIR, (Attorney Docket No. END6843USCIP3/100528CIP3);
U.S. Application Serial No. _____, entitled RETAINER ASSEMBLY INCLUDING A TISSUE THICKNESS COMPENSATOR, (Attorney Docket No. END6843USCIP4/100528CIP4);

U.S. Application Serial No. _____, entitled TISSUE THICKNESS COMPENSATOR COMPRISING AT LEAST ONE MEDICAMENT, (Attorney Docket No. END6843USCIP5/100528CIP5);

U.S. Application Serial No. _____, entitled TISSUE THICKNESS COMPENSATOR COMPRISING CONTROLLED RELEASE AND EXPANSION, (Attorney Docket No. END6843USCIP6/100528CIP6);

U.S. Application Serial No. _____, entitled TISSUE THICKNESS COMPENSATOR COMPRISING FIBERS TO PRODUCE A RESILIENT LOAD, (Attorney Docket No. END6843USCIP7/100528CIP7);

U.S. Application Serial No. _____, entitled TISSUE THICKNESS COMPENSATOR COMPRISING STRUCTURE TO PRODUCE A RESILIENT LOAD, (Attorney Docket No. END6843USCIP8/100528CIP8);

U.S. Application Serial No. _____, entitled TISSUE THICKNESS COMPENSATOR COMPRISING RESILIENT MEMBERS, (Attorney Docket No. END6843USCIP9/100528CIP9);

U.S. Application Serial No. _____, entitled METHODS FOR FORMING TISSUE THICKNESS COMPENSATOR ARRANGEMENTS FOR SURGICAL STAPLERS, (Attorney Docket No. END6843USCIP10/100528CP10);

U.S. Application Serial No. _____, entitled TISSUE THICKNESS COMPENSATORS, (Attorney Docket No. END6843USCIP11/100528CP11);

U.S. Application Serial No. _____, entitled LAYERED TISSUE THICKNESS COMPENSATOR, (Attorney Docket No. END6843USCIP12/100528CP12);

U.S. Application Serial No. _____, entitled TISSUE THICKNESS COMPENSATORS FOR CIRCULAR SURGICAL STAPLERS, (Attorney Docket No. END6843USCIP13/100528CP13);

U.S. Application Serial No. _____, entitled TISSUE THICKNESS COMPENSATOR COMPRISING CAPSULES DEFINING A LOW PRESSURE ENVIRONMENT, (Attorney Docket No. END7100USNP/110601);

U.S. Application Serial No. _____, entitled TISSUE THICKNESS COMPENSATOR COMPRISED OF A PLURALITY OF MATERIALS, (Attorney Docket No. END7101USNP/110602);

U.S. Application Serial No. _____, entitled MOVABLE MEMBER FOR USE WITH A TISSUE THICKNESS COMPENSATOR, (Attorney Docket No. END7107USNP/110603);
U.S. Application Serial No. _____, entitled TISSUE THICKNESS COMPENSATOR COMPRISING A PLURALITY OF MEDICAMENTS, (Attorney Docket No. END7102USNP/110604);
U.S. Application Serial No. _____, entitled TISSUE THICKNESS COMPENSATOR AND METHOD FOR MAKING THE SAME, (Attorney Docket No. END7103USNP/110605);
U.S. Application Serial No. _____, entitled TISSUE THICKNESS COMPENSATOR COMPRISING CHANNELS, (Attorney Docket No. END7104USNP/110606);
U.S. Application Serial No. _____, entitled TISSUE THICKNESS COMPENSATOR COMPRISING TISSUE INGROWTH FEATURES, (Attorney Docket No. END7105USNP/110607); and
U.S. Application Serial No. _____, entitled DEVICES AND METHODS FOR ATTACHING TISSUE THICKNESS COMPENSATING MATERIALS TO SURGICAL STAPLING INSTRUMENTS, (Attorney Docket No. END7106USNP/110608).

[0573] Certain exemplary embodiments will now be described to provide an overall understanding of the principles of the structure, function, manufacture, and use of the devices and methods disclosed herein. One or more examples of these embodiments are illustrated in the accompanying drawings. Those of ordinary skill in the art will understand that the devices and methods specifically described herein and illustrated in the accompanying drawings are non-limiting exemplary embodiments. The features illustrated or described in connection with one exemplary embodiment may be combined with the features of other embodiments. Such modifications and variations are included within the scope of the present invention.

[0574] Any of the methods disclosed or claimed herein for manufacturing, forming or otherwise producing an article or product, may be employed to manufacture, form or otherwise produce all or part of the article or product in question, and where such a method is employed to manufacture, form or otherwise produce part of the article or product in question, the remainder of the article or product may be produced in any way, including by employing any of the other

methods disclosed and claimed herein for manufacturing, forming or otherwise producing the article or product, and the various parts so produced may be combined in any manner. Similarly, any article or product disclosed or claimed herein may exist alone, or in combination with, or as an integral part of any other article or product so disclosed with which it is compatible. Thus, the particular features, structures, or characteristics illustrated or described in connection with one article, product or method may be combined, in whole or in part, with the features structures, or characteristics of one or more other compatible articles, products or methods without limitation. Such modifications and variations are included within the scope of the present invention.

[0575] Where it is disclosed herein, either with reference to a particular figure or otherwise, that a certain embodiment of the invention or a certain article, product or method may comprise certain structures, characteristics or features, it will be understood by the reader that this signifies that those structures, characteristics or features may be embodied in the article, product or method in question in any compatible combination. In particular, such a disclosure of a number of optional structures, characteristics or features shall be understood also to disclose all of those structures, characteristics or features in combination, except in the case of structures, characteristics or features that are disclosed as alternatives to one another. Where such structures, characteristics or features are disclosed as alternatives to one another, this shall be understood to disclose those alternatives as being substitutions for each other.

[0576] The terms “proximal” and “distal” are used herein with reference to a clinician manipulating the handle portion of the surgical instrument. The term “proximal” referring to the portion closest to the clinician and the term “distal” referring to the portion located away from the clinician. It will be further appreciated that, for convenience and clarity, spatial terms such as “vertical”, “horizontal”, “up”, and “down” may be used herein with respect to the drawings. However, surgical instruments are used in many orientations and positions, and these terms are not intended to be limiting and/or absolute.

[0577] Various exemplary devices and methods are provided for performing laparoscopic and minimally invasive surgical procedures. However, the reader will readily appreciate that the various methods and devices disclosed herein can be used in numerous surgical procedures and applications, including in connection with open surgical procedures. As the present Detailed Description proceeds, the reader will further appreciate that the various instruments disclosed herein can be inserted into a body in any way, such as through a natural orifice, through an

incision or puncture hole formed in tissue, etc. The working portions or end effector portions of the instruments can be inserted directly into a patient's body or can be inserted through an access device that has a working channel through which the end effector and elongated shaft of a surgical instrument can be advanced.

[0578] Turning to the Drawings wherein like numerals denote like components throughout the several views, FIG. 1 depicts a surgical instrument 10 that is capable of practicing several unique benefits. The surgical stapling instrument 10 is designed to manipulate and/or actuate various forms and sizes of end effectors 12 that are operably attached thereto. In FIGS. 1-1E, for example, the end effector 12 includes an elongated channel 14 that forms a lower jaw 13 of the end effector 12. The elongated channel 14 is configured to support an "implantable" staple cartridge 30 and also movably support an anvil 20 that functions as an upper jaw 15 of the end effector 12.

[0579] The elongated channel 14 may be fabricated from, for example, 300 & 400 Series, 17-4 & 17-7 stainless steel, titanium, etc. and be formed with spaced side walls 16. The anvil 20 may be fabricated from, for example, 300 & 400 Series, 17-4 & 17-7 stainless steel, titanium, etc. and have a staple forming undersurface, generally labeled as 22 that has a plurality of staple forming pockets 23 formed therein. See FIGS. 1B-1E. In addition, the anvil 20 has a bifurcated ramp assembly 24 that protrudes proximally therefrom. An anvil pin 26 protrudes from each lateral side of the ramp assembly 24 to be received within a corresponding slot or opening 18 in the side walls 16 of the elongated channel 14 to facilitate its movable or pivotable attachment thereto.

[0580] Various forms of implantable staple cartridges may be employed with the surgical instruments disclosed herein. Specific staple cartridge configurations and constructions will be discussed in further detail below. However, in FIG. 1A, an implantable staple cartridge 30 is shown. The staple cartridge 30 has a body portion 31 that consists of a compressible hemostat material such as, for example, oxidized regenerated cellulose ("ORC") or a bio-absorbable foam in which lines of unformed metal staples 32 are supported. In order to prevent the staple from being affected and the hemostat material from being activated during the introduction and positioning process, the entire cartridge may be coated or wrapped in a biodegradable film 38 such as a polydioxanon film sold under the trademark PDS® or with a Polyglycerol sebacate (PGS) film or other biodegradable films formed from PGA (Polyglycolic acid, marketed under the trade mark Vicryl), PCL (Polycaprolactone), PLA or PLLA (Polylactic acid), PHA

(polyhydroxyalkanoate), PGCL (poliglecaprone 25, sold under the trademark Monocryl) or a composite of PGA, PCL, PLA, PDS that would be impermeable until ruptured. The body 31 of staple cartridge 30 is sized to be removably supported within the elongated channel 14 as shown such that each staple 32 therein is aligned with corresponding staple forming pockets 23 in the anvil when the anvil 20 is driven into forming contact with the staple cartridge 30.

[0581] In use, once the end effector 12 has been positioned adjacent the target tissue, the end effector 12 is manipulated to capture or clamp the target tissue between an upper face 36 of the staple cartridge 30 and the staple forming surface 22 of the anvil 20. The staples 32 are formed by moving the anvil 20 in a path that is substantially parallel to the elongated channel 14 to bring the staple forming surface 22 and, more particularly, the staple forming pockets 23 therein into substantially simultaneous contact with the upper face 36 of the staple cartridge 30. As the anvil 20 continues to move into the staple cartridge 30, the legs 34 of the staples 32 contact a corresponding staple forming pocket 23 in anvil 20 which serves to bend the staple legs 34 over to form the staples 32 into a "B shape". Further movement of the anvil 20 toward the elongated channel 14 will further compress and form the staples 32 to a desired final formed height "FF".

[0582] The above-described staple forming process is generally depicted in FIGS. 1B-1E. For example, FIG. 1B illustrates the end effector 12 with target tissue "T" between the anvil 20 and the upper face 36 of the implantable staple cartridge 30. FIG. 1C illustrates the initial clamping position of the anvil 20 wherein the anvil has 20 been closed onto the target tissue "T" to clamp the target tissue "T" between the anvil 20 and the upper face 36 of the staple cartridge 30. FIG. 1D illustrates the initial staple formation wherein the anvil 20 has started to compress the staple cartridge 30 such that the legs 34 of the staples 32 are starting to be formed by the staple forming pockets 23 in the anvil 20. FIG. 1E illustrates the staple 32 in its final formed condition through the target tissue "T" with the anvil 20 removed for clarity purposes. Once the staples 32 have been formed and fastened to the target tissue "T", the surgeon will move the anvil 20 to the open position to enable the cartridge body 31 and the staples 32 to remain affixed to the target tissue while the end effector 12 is being withdrawn from the patient. The end effector 12 forms all of the staples simultaneously as the two jaws 13, 15 are clamped together. The remaining "crushed" body materials 31 act as both a hemostat (the ORC) and a staple line reinforcement (PGA, PDS or any of the other film compositions mentioned above 38). Also, since the staples 32 never have to leave the cartridge body 31 during forming, the likelihood of the staples 32 being malformed

during forming is minimized. As used herein the term "implantable" means that, in addition to the staples, the cartridge body materials that support the staples will also remain in the patient and may eventually be absorbed by the patient's body. Such implantable staple cartridges are distinguishable from prior cartridge arrangements that remain positioned within the end effector in their entirety after they have been fired.

[0583] In various implementations, the end effector 12 is configured to be coupled to an elongated shaft assembly 40 that protrudes from a handle assembly 100. The end effector 12 (when closed) and the elongated shaft assembly 40 may have similar cross-sectional shapes and be sized to operably pass through a trocar tube or working channel in another form of access instrument. As used herein, the term "operably pass" means that the end effector and at least a portion of the elongated shaft assembly may be inserted through or passed through the channel or tube opening and can be manipulated therein as needed to complete the surgical stapling procedure. When in a closed position, the jaws 13 and 15 of the end effector 12 may provide the end effector with a roughly circular cross-sectional shape that facilitates its passage through a circular passage/opening. However, the end effectors of the present invention, as well as the elongated shaft assembly embodiments, could conceivably be provided with other cross-sectional shapes that could otherwise pass through access passages and openings that have non-circular cross-sectional shapes. Thus, an overall size of a cross-section of a closed end effector will be related to the size of the passage or opening through which it is intended to pass. Thus, one end effector for example, may be referred to as a "5mm" end effector which means it can operably pass through an opening that is at least approximately 5mm in diameter.

[0584] The elongated shaft assembly 40 may have an outer diameter that is substantially the same as the outer diameter of the end effector 12 when in a closed position. For example, a 5mm end effector may be coupled to an elongated shaft assembly 40 that has 5mm cross-sectional diameter. However, as the present Detailed Description proceeds, it will become apparent that the present invention may be effectively used in connection with different sizes of end effectors. For example, a 10mm end effector may be attached to an elongated shaft that has a 5mm cross-sectional diameter. Conversely, for those applications wherein a 10mm or larger access opening or passage is provided, the elongated shaft assembly 40 may have a 10mm (or larger) cross-sectional diameter, but may also be able to actuate a 5mm or 10mm end effector. Accordingly,

the outer shaft 40 may have an outer diameter that is the same as or is different from the outer diameter of a closed end effector 12 attached thereto.

[0585] As depicted, the elongated shaft assembly 40 extends distally from the handle assembly 100 in a generally straight line to define a longitudinal axis A-A. For example, the elongated shaft assembly 40 may be approximately 9-16 inches (229-406mm) long. However, the elongated shaft assembly 40 may be provided in other lengths and, as an alternative, may have joints therein or be otherwise configured to facilitate articulation of the end effector 12 relative to other portions of the shaft or handle assembly as will be discussed in further detail below. The elongated shaft assembly 40 includes a spine member 50 that extends from the handle assembly 100 to the end effector 12. The proximal end of the elongated channel 14 of the end effector 12 has a pair of retention trunnions 17 protruding therefrom that are sized to be received within corresponding trunnion openings or cradles 52 that are provided in a distal end of the spine member 50 to enable the end effector 12 to be removably coupled the elongated shaft assembly 40. The spine member 50 may be fabricated from, for example, 6061 or 7075 aluminum, stainless steel, titanium, etc.

[0586] The handle assembly 100 comprises a pistol grip-type housing that may be fabricated in two or more pieces for assembly purposes. For example, the handle assembly 100 as shown comprises a right hand case member 102 and a left hand case member (not illustrated) that are molded or otherwise fabricated from a polymer or plastic material and are designed to mate together. Such case members may be attached together by snap features, pegs and sockets molded or otherwise formed therein and/or by adhesive, screws, etc. The spine member 50 has a proximal end 54 that has a flange 56 formed thereon. The flange 56 is configured to be rotatably supported within a groove 106 formed by mating ribs 108 that protrude inwardly from each of the case members 102, 104. Such arrangement facilitates the attachment of the spine member 50 to the handle assembly 100 while enabling the spine member 50 to be rotated relative to the handle assembly 100 about the longitudinal axis A-A in a 360° path.

[0587] As can be further seen in FIG. 1, the spine member 50 passes through and is supported by a mounting bushing 60 that is rotatably affixed to the handle assembly 100. The mounting bushing 60 has a proximal flange 62 and a distal flange 64 that define a rotational groove 65 that is configured to rotatably receive a nose portion 101 of the handle assembly 100 therebetween. Such arrangement enables the mounting bushing 60 to rotate about longitudinal axis A-A relative

to the handle assembly 100. The spine member 50 is non-rotatably pinned to the mounting bushing 60 by a spine pin 66. In addition, a rotation knob 70 is attached to the mounting bushing 60. For example, the rotation knob 70 has a hollow mounting flange portion 72 that is sized to receive a portion of the mounting bushing 60 therein. The rotation knob 70 may be fabricated from, for example, glass or carbon filled Nylon, polycarbonate, Ultem®, etc. and is affixed to the mounting bushing 60 by the spine pin 66 as well. In addition, an inwardly protruding retention flange 74 is formed on the mounting flange portion 72 and is configured to extend into a radial groove 68 formed in the mounting bushing 60. Thus, the surgeon may rotate the spine member 50 (and the end effector 12 attached thereto) about longitudinal axis A-A in a 360° path by grasping the rotation knob 70 and rotating it relative to the handle assembly 100.

[0588] The anvil 20 is retained in an open position by an anvil spring 21 and/or another biasing arrangement. The anvil 20 is selectively movable from the open position to various closed or clamping and firing positions by a firing system, generally designated as 109. The firing system 109 includes a "firing member" 110 which comprises a hollow firing tube 110. The hollow firing tube 110 is axially movable on the spine member 50 and thus forms the outer portion of the elongated shaft assembly 40. The firing tube 110 may be fabricated from a polymer or other suitable material and have a proximal end that is attached to a firing yoke 114 of the firing system 109. For example, the firing yoke 114 may be over-molded to the proximal end of the firing tube 110. However, other fastener arrangements may be employed.

[0589] As can be seen in FIG. 1, the firing yoke 114 may be rotatably supported within a support collar 120 that is configured to move axially within the handle assembly 100. The support collar 120 has a pair of laterally extending fins that are sized to be slidably received within fin slots formed in the right and left hand case members. Thus, the support collar 120 may slide axially within the handle housing 100 while enabling the firing yoke 114 and firing tube 110 to rotate relative thereto about the longitudinal axis A-A. A longitudinal slot is provided through the firing tube 110 to enable the spine pin 66 to extend therethrough into the spine member 50 while facilitating the axial travel of the firing tube 110 on the spine member 50.

[0590] The firing system 109 further comprises a firing trigger 130 which serves to control the axial travel of the firing tube 110 on the spine member 50. See FIG. 1. Such axial movement in the distal direction of the firing tube 110 into firing interaction with the anvil 20 is referred to herein as "firing motion". As can be seen in FIG. 1, the firing trigger 130 is movably or pivotally

coupled to the handle assembly 100 by a pivot pin 132. A torsion spring 135 is employed to bias the firing trigger 130 away from the pistol grip portion 107 of the handle assembly 100 to an un-actuated "open" or starting position. As can be seen in FIG. 1, the firing trigger 130 has an upper portion 134 that is movably attached to (pinned) firing links 136 that are movably attached to (pinned) the support collar 120. Thus, movement of the firing trigger 130 from the starting position (FIG. 1) toward an ending position adjacent the pistol grip portion 107 of the handle assembly 100 will cause the firing yoke 114 and the firing tube 110 to move in the distal direction "DD". Movement of the firing trigger 130 away from the pistol grip portion 107 of the handle assembly 100 (under the bias of the torsion spring 135) will cause the firing yoke 114 and firing tube 110 to move in the proximal direction "PD" on the spine member 50.

[0591] The present invention may be employed with different sizes and configurations of implantable staple cartridges. For example, the surgical instrument 10, when used in connection with a first firing adapter 140, may be used with a 5mm end effector 12 that is approximately 20mm long (or in other lengths) which supports an implantable staple cartridge 30. Such end effector size may be particularly well-suited, for example, to complete relatively fine dissection and vascular transactions. However, as will be discussed in further detail below, the surgical instrument 10 may also be employed, for example, in connection with other sizes of end effectors and staple cartridges by replacing the first firing adapter 140 with a second firing adapter. In a further alternative, the elongated shaft assembly 40 may configured to be attached to only one form or size of end effector.

[0592] One method of removably coupling the end effector 12 to the spine member 50 will now be explained. The coupling process is commenced by inserting the retention trunnions 17 on the elongated channel 14 into the trunnion cradles 52 in the spine member 50. Thereafter, the surgeon advances the firing trigger 130 toward the pistol grip 107 of the housing assembly 100 to distally advance the firing tube 110 and the first firing adapter 140 over a proximal end portion 47 of the elongated channel 14 to thereby retain the trunnions 17 in their respective cradles 52. Such position of the first firing adapter 140 over the trunnions 17 is referred to herein as the "coupled position". The present invention may also have an end effector locking assembly for locking the firing trigger 130 in position after an end effector 12 has been attached to the spine member 50.

[0593] More specifically, one embodiment of the end effector locking assembly 160 includes a retention pin 162 that is movably supported in the upper portion 134 of the firing trigger 130. As discussed above, the firing tube 110 must initially be advanced distally to the coupled position wherein the first firing adapter 140 retains the retention trunnions 17 of the end effector 12 in the trunnion cradles 52 in the spine member 50. The surgeon advances the firing adapter 140 distally to the coupled position by pulling the firing trigger 130 from the starting position toward the pistol grip 107. As the firing trigger 130 is initially actuated, the retention pin 162 is moved distally until the firing tube 110 has advanced the first firing adapter 140 to the coupled position at which point the retention pin 162 is biased into a locking cavity 164 formed in the case member. When the retention pin 162 enters into the locking cavity 164, the pin 162 may make an audible "click" or other sound, as well as provide a tactile indication to the surgeon that the end effector 12 has been "locked" onto the spine member 50. In addition, the surgeon cannot inadvertently continue to actuate the firing trigger 130 to start to form staples 32 in the end effector 12 without intentionally biasing the retention pin 162 out of the locking cavity 164. Similarly, if the surgeon releases the firing trigger 130 when in the coupled position, it is retained in that position by the retention pin 162 to prevent the firing trigger 130 from returning to the starting position and thereby releasing the end effector 12 from the spine member 50.

[0594] The present invention may further include a firing system lock button 137 that is pivotally attached to the handle assembly 100. In one form, the firing system lock button 137 has a latch 138 formed on a distal end thereof that is oriented to engage the firing yoke 114 when the firing release button is in a first latching position. As can be seen in FIG. 1, a latch spring 139 serves to bias the firing system lock button 137 to the first latching position. In various circumstances, the latch 138 serves to engage the firing yoke 114 at a point where the position of the firing yoke 114 on the spine member 50 corresponds to a point wherein the first firing adapter 140 is about to distally advance up the clamping ramp 28 on the anvil 20. It will be understood that, as the first firing adapter 140 advances axially up the clamping ramp 28, the anvil 20 will move in a path such that its staple forming surface portion 22 is substantially parallel to the upper face 36 of the staple cartridge 30.

[0595] After the end effector 12 has been coupled to the spine member 50, the staple forming process is commenced by first depressing the firing system lock button 137 to enable the firing yoke 114 to be further moved distally on the spine member 50 and ultimately compress the anvil

20 into the staple cartridge 30. After depressing the firing system lock button 137, the surgeon continues to actuate the firing trigger 130 towards the pistol grip 107 thereby driving the first staple collar 140 up the corresponding staple forming ramp 29 to force the anvil 20 into forming contact with the staples 32 in the staple cartridge 30. The firing system lock button 137 prevents the inadvertent forming of the staples 32 until the surgeon is ready to start that process. In this example, the surgeon must depress the firing system lock button 137 before the firing trigger 130 may be further actuated to begin the staple forming process.

[0596] The surgical instrument 10 may be solely used as a tissue stapling device if so desired. However, the present invention may also include a tissue cutting system, generally designated as 170. In at least one form, the tissue cutting system 170 comprises a knife member 172 that may be selectively advanced from an un-actuated position adjacent the proximal end of the end effector 12 to an actuated position by actuating a knife advancement trigger 200. The knife member 172 is movably supported within the spine member 50 and is attached or otherwise protrudes from a knife rod 180. The knife member 172 may be fabricated from, for example, 420 or 440 stainless steel with a hardness of greater than 38HRC (Rockwell Hardness C-scale) and have a tissue cutting edge 176 formed on the distal end 174 thereof and be configured to slidably extend through a slot in the anvil 20 and a centrally disposed slot 33 in the staple cartridge 30 to cut through tissue that is clamped in the end effector 12. The knife rod 180 extends through the spine member 50 and has a proximal end portion which drivingly interfaces with a knife transmission that is operably attached to the knife advance trigger 200. The knife advance trigger 200 is attached to pivot pin 132 such that it may be pivoted or otherwise actuated without actuating the firing trigger 130. A first knife gear 192 is also attached to the pivot pin 132 such that actuation of the knife advance trigger 200 also pivots the first knife gear 192. A firing return spring 202 is attached between the first knife gear 192 and the handle housing 100 to bias the knife advancement trigger 200 to a starting or un-actuated position.

[0597] The knife transmission also include a second knife gear 194 that is rotatably supported on a second gear spindle and in meshing engagement with the first knife gear 192. The second knife gear 194 is in meshing engagement with a third knife gear 196 that is supported on a third gear spindle. Also supported on the third gear spindle 195 is a fourth knife gear 198. The fourth knife gear 198 is adapted to drivingly engage a series of annular gear teeth or rings on a proximal end of the knife rod 180. Thus, such arrangement enables the fourth knife gear 198 to axially drive

the knife rod 180 in the distal direction "DD" or proximal direction "PD" while enabling the firing rod 180 to rotate about longitudinal axis A-A with respect to the fourth knife gear 198. Accordingly, the surgeon may axially advance the firing rod 180 and ultimately the knife member 172 distally by pulling the knife advancement trigger 200 towards the pistol grip 107 of the handle assembly 100.

[0598] The present invention may further include a knife lockout system 210 that prevents the advancement of the knife member 172 unless the firing trigger 130 has been pulled to the fully fired position. Such feature will therefore prevent the activation of the knife advancement system 170 unless the staples have first been fired or formed into the tissue. As can be seen in FIG. 1, various implementations of the knife lockout system 210 comprise a knife lockout bar 211 that is pivotally supported within the pistol grip portion 107 of the handle assembly 100. The knife lockout bar 211 has an activation end 212 that is adapted to be engaged by the firing trigger 130 when the firing trigger 130 is in the fully fired position. In addition, the knife lockout bar 211 has a retaining hook 214 on its other end that is adapted to hookingly engage a latch rod 216 on the first cut gear 192. A knife lock spring 218 is employed to bias the knife lockout bar 211 to a "locked" position wherein the retaining hook 214 is retained in engagement with the latch rod 216 to thereby prevent actuation of the knife advancement trigger 200 unless the firing trigger 130 is in the fully fired position.

[0599] After the staples have been "fired" (formed) into the target tissue, the surgeon may depress the firing trigger release button 167 to enable the firing trigger 130 to return to the starting position under the bias of the torsion spring 135 which enables the anvil 20 to be biased to an open position under the bias of spring 21. When in the open position, the surgeon may withdraw the end effector 12 leaving the implantable staple cartridge 30 and staples 32 behind. In applications wherein the end effector was inserted through a passage, working channel, etc. the surgeon will return the anvil 20 to the closed position by activating the firing trigger 130 to enable the end effector 12 to be withdrawn out through the passage or working channel. If, however, the surgeon desires to cut the target tissue after firing the staples, the surgeon activates the knife advancement trigger 200 in the above-described manner to drive the knife bar 172 through the target tissue to the end of the end effector. Thereafter, the surgeon may release the knife advancement trigger 200 to enable the firing return spring 202 to cause the firing transmission to return the knife bar 172 to the starting (un-actuated) position. Once the knife bar

172 has been returned to the starting position, the surgeon may open the end effector jaws 13, 15 to release the implantable cartridge 30 within the patient and then withdraw the end effector 12 from the patient. Thus, such surgical instruments facilitate the use of small implantable staple cartridges that may be inserted through relatively smaller working channels and passages, while providing the surgeon with the option to fire the staples without cutting tissue or if desired to also cut tissue after the staples have been fired.

[0600] Various unique and novel embodiments of the present invention employ a compressible staple cartridge that supports staples in a substantially stationary position for forming contact by the anvil. The anvil is driven into the unformed staples wherein, for example, the degree of staple formation attained is dependent upon how far the anvil is driven into the staples. Such an arrangement provides the surgeon with the ability to adjust the amount of forming or firing pressure applied to the staples and thereby alter the final formed height of the staples. In other embodiments of the present invention, surgical stapling arrangements can employ staple driving elements which can lift the staples toward the anvil. Such embodiments are described in greater detail further below.

[0601] With regard to the embodiments described in detail above, the amount of firing motion that is applied to the movable anvil is dependent upon the degree of actuation of the firing trigger. For example, if the surgeon desires to attain only partially formed staples, then the firing trigger is only partially depressed inward towards the pistol grip 107. To attain more staple formation, the surgeon simply compresses the firing trigger further which results in the anvil being further driven into forming contact with the staples. As used herein, the term "forming contact" means that the staple forming surface or staple forming pockets have contacted the ends of the staple legs and have started to form or bend the legs over into a formed position. The degree of staple formation refers to how far the staple legs have been folded over and ultimately relates to the forming height of the staple as referenced above. Those of ordinary skill in the art will further understand that, because the anvil 20 moves in a substantially parallel relationship with respect to the staple cartridge as the firing motions are applied thereto, the staples are formed substantially simultaneously with substantially the same formed heights.

[0602] FIGS. 2 and 3 illustrate an alternative end effector 12" that is similar to the end effector 12' described above, except with the following differences that are configured to accommodate a knife bar 172'. The knife bar 172' is coupled to or protrudes from a knife rod 180 and is

otherwise operated in the above described manner with respect to the knife bar 172. However, in this embodiment, the knife bar 172' is long enough to traverse the entire length of the end effector 12" and therefore, a separate distal knife member is not employed in the end effector 12". The knife bar 172' has an upper transverse member 173' and a lower transverse member 175' formed thereon. The upper transverse member 173' is oriented to slidably transverse a corresponding elongated slot 250 in anvil 20" and the lower transverse member 175' is oriented to traverse an elongated slot 252 in the elongated channel 14" of the end effector 12". A disengagement slot (not shown) is also provide din the anvil 20" such that when the knife bar 172' has been driven to an ending position with thin end effector 12", the upper transverse member 173' drops through the corresponding slot to enable the anvil 20" to move to the open position to disengage the stapled and cut tissue. The anvil 20" may be otherwise identical to anvil 20 described above and the elongated channel 14" may be otherwise identical to elongated channel 14 described above.

[0603] In these embodiments, the anvil 20" is biased to a fully open position (FIG. 2) by a spring or other opening arrangement (not shown). The anvil 20" is moved between the open and fully clamped positions by the axial travel of the firing adapter 150 in the manner described above. Once the firing adapter 150 has been advanced to the fully clamped position (FIG. 3), the surgeon may then advance the knife bar 172" distally in the manner described above. If the surgeon desires to use the end effector as a grasping device to manipulate tissue, the firing adapter may be moved proximally to allow the anvil 20" to move away from the elongated channel 14" as represented in FIG. 4 in broken lines. In this example, as the knife bar 172" moves distally, the upper transverse member 173' and the lower transverse member 175' draw the anvil 20" and elongated channel 14" together to achieve the desired staple formation as the knife bar 172" is advanced distally through the end effector 12". See FIG. 5. Thus, in this embodiment, staple formation occurs simultaneously with tissue cutting, but the staples themselves may be sequentially formed as the knife bar 172" is driven distally.

[0604] The unique and novel features of the various surgical staple cartridges and the surgical instruments of the present invention enable the staples in those cartridges to be arranged in one or more linear or non-linear lines. A plurality of such staple lines may be provided on each side of an elongated slot that is centrally disposed within the staple cartridge for receiving the tissue cutting member therethrough. In one arrangement, for example, the staples in one line may be

substantially parallel with the staples in adjacent line(s) of staples, but offset therefrom. In a further alternative, one or more lines of staples may be non-linear in nature. That is, the base of at least one staple in a line of staples may extend along an axis that is substantially transverse to the bases of other staples in the same staple line. For example, as will be discussed in further detail below, in alternative embodiments, the lines of staples on each side of the elongated slot may have a zigzag appearance. Such non-linear staple arrangements may attain better tissue fastening results with fewer staples than various linear staple arrangements employed in prior staple cartridges.

[0605] FIG. 6 illustrates use of a surgical staple cartridge embodiment 900 in an end effector embodiment 612'. As can be seen in FIGS. 6 and 7, an embodiment of the surgical staple cartridge 900 has a cartridge body 902 that has a centrally disposed elongated slot 904 extending through a proximal end 903 to an area adjacent a distal end 905. The elongated slot 904 is configured to permit a knife body to axially move therethrough during a tissue cutting operation in the manner described above. The cartridge body 902 consists of a compressible hemostat material such as, for example, oxidized regenerated cellulose ("ORC") or a bio-absorbable foam fabricated from, for example, PGA (Polyglycolic acid, sold under the trademark Vicryl), PCL (polycaprolactone), PLA or PLLA (Polyactic acid), PDS (Polydioxanone), PHA (polyhydroxyalkanoate), PGCL (poliglecaprone 25, sold under the trademark Monocryl) or a composite of PGA, PCL, PLA and PDS in which lines 920, 930 of unformed staples 922 are supported. However, the cartridge body 902 may be fabricated from other materials that serve to support the unformed staples 922 in a desired orientation such that they may be compressed as the anvil 910' is brought into contact therewith. As with other embodiments already described, the staple cartridge 900 is implantable and is left attached to the stapled tissue after the stapling procedure has been completed. In order to prevent the staples 922 from being affected and the hemostat material from being activated during the introduction and positioning process, the entire cartridge 900 may be coated or wrapped in a biodegradable film 906 such as a polydioxanon film sold under the trademark PDS® or with a Polyglycerol sebacate (PGS) film or other biodegradable films fabricated from, for example, PGA (Polyglycolic acid, marketed under the trade mark Vicryl), PCL (Polycaprolactone), PLA or PLLA (Polylactic acid), PHA (polyhydroxyalkanoate), PGCL (poliglecaprone 25, sold under the trademark Monocryl) or a composite of PGA, PCL, PLA, PDS that would be impermeable until ruptured. The cartridge

body 902 of staple cartridge 900 is sized to be removably supported within the elongated channel of the end effector 612'.

[0606] In FIGS. 6, 10, and 11, the surgical staple cartridge 900 operably supports a first line 920 of staples 922 on one lateral side 907 of the elongated slot 904 and a second line 930 of staples 922 on the other lateral side 909 of the elongated slot 904. The staples 922 may be fabricated from a metal material such as, for example, Titanium, Titanium alloys (e.g., 6AI-4V Titanium, 3al-2.5V Titanium), Stainless Steel, etc. and have a staple base 924 and two upstanding staple legs 926 protruding therefrom. Each staple leg 926 may have a tissue-piercing tip 928 formed thereon. In the first line 920 of staples 922, the staple base 924 of at least one staple 922 overlaps the staple base of another staple 922. In a preferred embodiment, the staple base 924 of each staple 922 overlaps the staple bases 924 of two adjacent staples 922, except for the base 924 of the last staple 922 on each end of the first staple line 920. See FIG. 10. Thus, the first staple line 920 has a substantially non-linear shape. More particularly, when viewed from above, the first staple line 920 has a substantially zigzag appearance.

[0607] As can be seen in FIG. 9, the anvil 90 has two sequential longitudinal staple forming pockets 912 that each has a substantial zigzag shape that corresponds to the shape of the first line 920 of staples 922 such that, when the anvil 910 is brought into forming contact with the staples 922, the legs 926 thereof are formed as shown in FIG. 11. Thus, the distal leg of one staple shares the same pocket as the proximal leg of the next staple longitudinally. Such arrangement allows for a denser pocket pattern, even to a point where the staples themselves interact (e.g., are folded over one another). In prior staple pocket arrangements, in general, there has to be between 0.005 and 0.015 inches of metal/space from one set of pockets to the next. This embodiment of the present invention, however, has a spacing arrangement from 0 to 0.02 inches of interference/overlap (essentially a -0.020") because one staple mates with the next staple, for example. Such arrangements allow for 15-30% more staples in the same space. Furthermore, when the staples interlock, there is less need for multiple lateral rows of staples. Prior arrangements commonly employ three rows on each side of the tissue cut line to prevent the existing of an open path through which blood may pass. Lines of interlocking staples are less likely to leave paths through which blood may pass. Another distinct advantage provided by the various interlocking staple arrangements of the present invention relates to improved "burst strength" which relates to the amount of force required to tear a staple line open.

[0608] Another staple forming pocket arrangement may comprise a common staple forming pocket. As used herein, the term "common staple forming pocket" means that one forming pocket can form all of the staples in a single line of staples as opposed to prior anvil designs wherein a discrete forming pocket is provided for each leg of each staple to be formed.

[0609] FIG. 12 illustrates yet another staple embodiment 922' wherein the base 924' has an offset portion 929 to facilitate a tighter overlap of the bases 924'. As indicated above, the staple cartridge 900 has a second line 930 of staples 922 supported on a second lateral side 909 of the elongated slot 904. The second line 930 of staples 922 is substantially identical to the first line 920 of staples 922. Thus, the anvil 910 has a second common staple forming pocket 912 that corresponds to the second line of staples 930 for forming contact therewith. Alternatively, however, the second line 930 of staples 922 may differ from the first line 920 of staples in shape and, perhaps, number of staples.

[0610] FIG. 8 illustrates a surgical staple cartridge 900' that is substantially identical to the staple cartridge 900 described above, with the exception of the lines 920', 930' of staples 922 supported therein. For example, in this embodiment, the line 920' of staples 922 are arranged relative to each other such that a base axis S-S of at least one staple base 924 is substantially transverse to the base axis S-S of the staple base 924 of at least one other adjacent staple 922. Such predetermined pattern of staples, when viewed from above, comprises a substantially zigzag arrangement. In FIG. 13, the respective bases 924 of staples 922 may additionally have a base support member 927 overmolded thereon as shown. The base support member 927 may be fabricated from, for example, non-absorbable plastic such as Polyether ether ketone "PEEK" or absorbable plastic such as, for example, Polyglycolic acid "PGA", Polylactic acid "PLA" or "PLLA", Polydioxanone "PDS", PCL (polycaprolactone), PHA (polyhydroxyalkanoate), Polyglycerol sebacate (PGS), PGCL (poliglecaprone 25, sold under the trademark Monocryl) or various composite mixes of PGS, PDS, PLA, PGA, and PCL. The base support members 927 facilitate interlocking between the staples without making the staples themselves overlap. Thus, such arrangements could form staples with "B" shapes or inverted "W" shapes without the legs of the staples themselves overlapping. However, the crowns are connected by the base support members so they act like overlapping staples. Such arrangements allow the combined pockets to have two discrete paths for each leg.

[0611] The embodiment depicted in FIG. 14 employs a staple line 920" wherein the legs 926 of adjacent staples 922 are coupled together by a coupler portion 929 molded or otherwise attached thereto. Each coupler portion 929 may be fabricated from, for example, Polyether ether ketone "PEEK" or absorbable plastic such as, for example, Polyglycolic acid "PGA", Polylactic acid "PLA" or "PLLA", Polydioxanone "PDS", PCL (polycaprolactone), PHA (polyhydroxyalkanoate), PGCL (poliglecaprone 25, sold under the trademark Monocryl) or various composite mixes if PGS, PDS, PLA, PGA, and PCL. Such staple line 920" has substantial zigzag appearance when viewed from above. While the various surgical staple cartridge embodiments 900, 900' have been explained with reference to use with the end effector 612', it will be understood that the staple cartridges 900, 900' may be effectively employed with the various other end effectors and surgical instruments described hereinabove, with appropriate staple forming pocket arrangements being provided in the anvils of those instruments in order to achieved the desired amount of staple formation upon movement of the anvils into forming contact with the staples.

[0612] FIGS. 15 and 16 illustrate another surgical staple cartridge 940 embodiment supported in an elongated channel 14 of a surgical instrument 10. The surgical staple cartridge 940 includes a cartridge body 942 that has a centrally disposed elongated slot 944 extending at least partially therethrough. The elongated slot 944 is configured to permit a knife body of the surgical instrument 10 to axially move therethrough during a tissue cutting operation in the manner described above. The cartridge body 942 consists of a compressible hemostat material such as, for example, oxidized regenerated cellulose ("ORC") or a bio-absorbable foam of the types described above or below in which lines 946, 948, 950, 952 of unformed staples 922 are supported. In order to prevent the staples 922 from being affected and the hemostat material from being activated during the introduction and positioning process, the entire cartridge 940 may be coated or wrapped in a biodegradable film 954 such as a polydioxanon film sold under the trademark PDS® or with a Polyglycerol sebacate (PGS) film or other biodegradable films fabricated from, for example, PGA (Polyglycolic acid, marketed under the trade mark Vicryl), PCL (Polycaprolactone), PLA or PLLA (Polylactic acid), PHA (polyhydroxyalkanoate), PGCL (poliglecaprone 25, sold under the trademark Monocryl) or a composite of PGA, PCL, PLA, PDS that would be impermeable until ruptured.

[0613] In FIG. 15, the cartridge 940 further includes a cartridge support member 960 that is coupled to the cartridge body 942. The cartridge support member 960 may be fabricated from a rigid material such as, for example, Titanium, Stainless Steel, Aluminum, any alloy of the foregoing, etc. and may be partially embedded within the cartridge body 942. The cartridge support member 960 may be held in place by, for example, film 954. In alternative cases wherein a limited bond is desired, sporadic use of cyanoacylate could be used to "glue" the two components together. In further alternatives, the cartridge body 942 may be heated and "welded" or "fused" to the cartridge support member 960. The cartridge support member 960 forms at least a portion of the bottom surface of the cartridge body 942 for mating with the elongated channel 14. The cartridge support member 960 has one or more snap features 962 protruding therefrom for releasably coupling the cartridge support member 960 to the elongated channel 14. Other forms of snap features/fastener arrangements may be employed for releasably coupling the cartridge support member 960 to the elongated channel 14.

[0614] The cartridge support member 960 has a series of support ridges 964, 966, 968, 970, 972, 974, 976 formed thereon to provide some lateral support to the bases 924 of the staples 922 in the staple lines 946, 948, 950, 952 as shown in FIG. 15. Thus, as an example, the support ridges are substantially coextensive with the staple lines. FIG. 17 illustrates an alternative staple cartridge embodiment 940' that is substantially identical to cartridge 940, except for the inclusion of upstanding fin portions 978, 979, 980, 981, 982, 983 that protrude from the support ridges 964, 966, 968, 970, 972, 976, respectively to provide additional lateral support to the staples 922. The fin portions may be integrally formed with the cartridge support member 960 and have a height that is about ½ or less of the height of the cartridge. Thus, for example, any standing features supporting the foam cannot extend above the maximum compression height of the foam. Thus, if the cartridge is designed, for example, to compress to 1/3 of its original height when fired, the fins would between 66% of the uncompressed height, all the way down to 10% of uncompressed height.

[0615] In use, once the staples 922 have been formed through contact with the anvil 20 in the manner described above, the anvil 20 is opened and the end effector 12 is pulled away from the stapled tissue. As the end effector 12 is pulled away from the stapled tissue, the cartridge body 942 remains fastened to the stapled tissue and is then separated from the cartridge support member 960 which remains coupled to the elongated channel 14. The cartridge support member

960 is provided with a color that differs from the color of the material comprising the cartridge body 942 as well as the color of the elongated channel 14. Such arrangement provides the surgeon with an easily recognizable indication that no staple cartridge is present within the end effector. Thus, the surgeon will not inadvertently attempt to reinsert/use the end effector without first installing a new staple cartridge therein. To do so, the surgeon simply disconnects the snap features of the cartridge support member 960 from the elongated channel 14 to enable the cartridge support member 960 of a new staple cartridge 940 to be placed therein. While the staple cartridges 940, 940' have been explained with reference to surgical instrument 10, it will be understood that those cartridges may be effectively employed with many of the other surgical instrument embodiments disclosed herein without departing from the spirit and scope of the present invention.

[0616] A staple cartridge can comprise a cartridge body and a plurality of staples stored within the cartridge body. In use, the staple cartridge can be introduced into a surgical site and positioned on a side of the tissue being treated. In addition, a staple-forming anvil can be positioned on the opposite side of the tissue. The anvil can be carried by a first jaw and the staple cartridge can be carried by a second jaw, wherein the first jaw and/or the second jaw can be moved toward the other. Once the staple cartridge and the anvil have been positioned relative to the tissue, the staples can be ejected from the staple cartridge body such that the staples can pierce the tissue and contact the staple-forming anvil. Once the staples have been deployed from the staple cartridge body, the staple cartridge body can then be removed from the surgical site. As described herein, a staple cartridge, or at least a portion of a staple cartridge, can be implanted with the staples. For example, as described in greater detail further below, a staple cartridge can comprise a cartridge body which can be compressed, crushed, and/or collapsed by the anvil when the anvil is moved from an open position into a closed position. When the cartridge body is compressed, crushed, and/or collapsed, the staples positioned within the cartridge body can be deformed by the anvil. Alternatively, the jaw supporting the staple cartridge can be moved toward the anvil into a closed position. In either event, the staples can be deformed while they are at least partially positioned within the cartridge body. The staples may not be ejected from the staple cartridge while, the staples can be ejected from the staple cartridge along with a portion of the cartridge body.

[0617] Referring now to FIGS. 18A-18D, a compressible staple cartridge, such as staple cartridge 1000, for example, can comprise a compressible, implantable cartridge body 1010 and, in addition, a plurality of staples 1020 positioned in the compressible cartridge body 1010, although only one staple 1020 is depicted in FIGS. 18A-18D. FIG. 18A illustrates the staple cartridge 1000 supported by a staple cartridge support, or staple cartridge channel, 1030, wherein the staple cartridge 1000 is illustrated in an uncompressed condition. In such an uncompressed condition, the anvil 1040 may or may not be in contact with the tissue T. In use, the anvil 1040 can be moved from an open position into contact with the tissue T as illustrated in FIG. 18B and position the tissue T against the cartridge body 1010. Even though the anvil 1040 can position the tissue T against a tissue-contacting surface 1019 of staple cartridge body 1010, referring again to FIG. 18B, the staple cartridge body 1010 may be subjected to little, if any, compressive force or pressure at such point and the staples 1020 may remain in an unformed, or unfired, condition. As illustrated in FIGS. 18A and 18B, the staple cartridge body 1010 can comprise one or more layers and the staple legs 1021 of staples 1020 can extend upwardly through these layers. The cartridge body 1010 can comprise a first layer 1011, a second layer 1012, a third layer 1013, wherein the second layer 1012 can be positioned intermediate the first layer 1011 and the third layer 1013, and a fourth layer 1014, wherein the third layer 1013 can be positioned intermediate the second layer 1012 and the fourth layer 1014. The bases 1022 of the staples 1020 can be positioned within cavities 1015 in the fourth layer 1014 and the staple legs 1021 can extend upwardly from the bases 1022 and through the fourth layer 1014, the third layer 1013, and the second layer 1012, for example. Each deformable leg 1021 can comprise a tip, such as sharp tip 1023, for example, which can be positioned in the second layer 1012, for example, when the staple cartridge 1000 is in an uncompressed condition. For example, the tips 1023 may not extend into and/or through the first layer 1011, wherein, the tips 1023 may not protrude through the tissue-contacting surface 1019 when the staple cartridge 1000 is in an uncompressed condition. Alternatively, the sharp tips 1023 may be positioned in the third layer 1013, and/or any other suitable layer, when the staple cartridge is in an uncompressed condition. Alternatively, a cartridge body of a staple cartridge may have any suitable number of layers such as less than four layers or more than four layers, for example.

[0618] As described in greater detail below, the first layer 1011 can be comprised of a buttress material and/or plastic material, such as polydioxanone (PDS) and/or polyglycolic acid (PGA),

for example, and the second layer 1012 can be comprised of a bioabsorbable foam material and/or a compressible haemostatic material, such as oxidized regenerated cellulose (ORC), for example. One or more of the first layer 1011, the second layer 1012, the third layer 1013, and the fourth layer 1014 may hold the staples 1020 within the staple cartridge body 1010 and, in addition, maintain the staples 1020 in alignment with one another. The third layer 1013 can be comprised of a buttress material, or a fairly incompressible or inelastic material, which can be configured to hold the staple legs 1021 of the staples 1020 in position relative to one another. Furthermore, the second layer 1012 and the fourth layer 1014, which are positioned on opposite sides of the third layer 1013, can stabilize, or reduce the movement of, the staples 1020 even though the second layer 1012 and the fourth layer 1014 can be comprised of a compressible foam or elastic material. The staple tips 1023 of the staple legs 1021 can be at least partially embedded in the first layer 1011. For example, the first layer 1011 and the third layer 1013 can be configured to co-operatively and firmly hold the staple legs 1021 in position. The first layer 1011 and the third layer 1013 can each be comprised of a sheet of bioabsorbable plastic, such as polyglycolic acid (PGA) which is marketed under the trade name Vicryl, polylactic acid (PLA or PLLA), polydioxanone (PDS), polyhydroxyalkanoate (PHA), poliglecaprone 25 (PGCL) which is marketed under the trade name Monocryl, polycaprolactone (PCL), and/or a composite of PGA, PLA, PDS, PHA, PGCL and/or PCL, for example, and the second layer 1012 and the fourth layer 1014 can each be comprised of at least one haemostatic material or agent.

[0619] Although the first layer 1011 can be compressible, the second layer 1012 can be substantially more compressible than the first layer 1011. For example, the second layer 1012 can be about twice as compressible, about three times as compressible, about four times as compressible, about five times as compressible, and/or about ten times as compressible, for example, as the first layer 1011. Stated another way, the second layer 1012 may compress about two times, about three times, about four times, about five times, and/or about ten times as much as first layer 1011, for a given force. The second layer 1012 can be between about twice as compressible and about ten times as compressible, for example, as the first layer 1011. The second layer 1012 can comprise a plurality of air voids defined therein, wherein the amount and/or size of the air voids in the second layer 1012 can be controlled in order to provide a desired compressibility of the second layer 1012. Similar to the above, although the third layer 1013 can be compressible, the fourth layer 1014 can be substantially more compressible than the

third layer 1013. For example, the fourth layer 1014 can be about twice as compressible, about three times as compressible, about four times as compressible, about five times as compressible, and/or about ten times as compressible, for example, as the third layer 1013. Stated another way, the fourth layer 1014 may compress about two times, about three times, about four times, about five times, and/or about ten times as much as third layer 1013, for a given force. The fourth layer 1014 can be between about twice as compressible and about ten times as compressible, for example, as the third layer 1013. The fourth layer 1014 can comprise a plurality of air voids defined therein, wherein the amount and/or size of the air voids in the fourth layer 1014 can be controlled in order to provide a desired compressibility of the fourth layer 1014. In various circumstances, the compressibility of a cartridge body, or cartridge body layer, can be expressed in terms of a compression rate, i.e., a distance in which a layer is compressed for a given amount of force. For example, a layer having a high compression rate will compress a larger distance for a given amount of compressive force applied to the layer as compared to a layer having a lower compression rate. This being said, the second layer 1012 can have a higher compression rate than the first layer 1011 and, similarly, the fourth layer 1014 can have a higher compression rate than the third layer 1013. The second layer 1012 and the fourth layer 1014 can be comprised of the same material and can comprise the same compression rate. The second layer 1012 and the fourth layer 1014 can be comprised of materials having different compression rates. Similarly, the first layer 1011 and the third layer 1013 can be comprised of the same material and can comprise the same compression rate. The first layer 1011 and the third layer 1013 can be comprised of materials having different compression rates.

[0620] As the anvil 1040 is moved toward its closed position, the anvil 1040 can contact tissue T and apply a compressive force to the tissue T and the staple cartridge 1000, as illustrated in FIG. 18C. In such circumstances, the anvil 1040 can push the top surface, or tissue-contacting surface 1019, of the cartridge body 1010 downwardly toward the staple cartridge support 1030. The staple cartridge support 1030 can comprise a cartridge support surface 1031 which can be configured to support the staple cartridge 1000 as the staple cartridge 1000 is compressed between the cartridge support surface 1031 and the tissue-contacting surface 1041 of anvil 1040. Owing to the pressure applied by the anvil 1040, the cartridge body 1010 can be compressed and the anvil 1040 can come into contact with the staples 1020. More particularly, the compression of the cartridge body 1010 and the downward movement of the tissue-contacting surface 1019

can cause the tips 1023 of the staple legs 1021 to pierce the first layer 1011 of cartridge body 1010, pierce the tissue T, and enter into forming pockets 1042 in the anvil 1040. As the cartridge body 1010 is further compressed by the anvil 1040, the tips 1023 can contact the walls defining the forming pockets 1042 and, as a result, the legs 1021 can be deformed or curled inwardly, for example, as illustrated in FIG. 18C. As the staple legs 1021 are being deformed, as also illustrated in FIG. 18C, the bases 1022 of the staples 1020 can be in contact with or supported by the staple cartridge support 1030. As described in greater detail below, the staple cartridge support 1030 can comprise a plurality of support features, such as staple support grooves, slots, or troughs 1032, for example, which can be configured to support the staples 1020, or at least the bases 1022 of the staples 1020, as the staples 1020 are being deformed. As also illustrated in FIG. 18C, the cavities 1015 in the fourth layer 1014 can collapse as a result of the compressive force applied to the staple cartridge body 1010. In addition to the cavities 1015, the staple cartridge body 1010 can further comprise one or more voids, such as voids 1016, for example, which may or may not comprise a portion of a staple positioned therein, that can be configured to allow the cartridge body 1010 to collapse. The cavities 1015 and/or the voids 1016 can be configured to collapse such that the walls defining the cavities and/or walls deflect downwardly and contact the cartridge support surface 1031 and/or contact a layer of the cartridge body 1010 positioned underneath the cavities and/or voids.

[0621] Upon comparing FIG. 18B and FIG. 18C, it is evident that the second layer 1012 and the fourth layer 1014 have been substantially compressed by the compressive pressure applied by the anvil 1040. It may also be noted that the first layer 1011 and the third layer 1013 have been compressed as well. As the anvil 1040 is moved into its closed position, the anvil 1040 may continue to further compress the cartridge body 1010 by pushing the tissue-contacting surface 1019 downwardly toward the staple cartridge support 1030. As the cartridge body 1010 is further compressed, the anvil 1040 can deform the staples 1020 into their completely-formed shape as illustrated in FIG. 18D. Referring to FIG. 18D, the legs 1021 of each staple 1020 can be deformed downwardly toward the base 1022 of each staple 1020 in order to capture at least a portion of the tissue T, the first layer 1011, the second layer 1012, the third layer 1013, and the fourth layer 1014 between the deformable legs 1021 and the base 1022. Upon comparing FIGS. 18C and 18D, it is further evident that the second layer 1012 and the fourth layer 1014 have been further substantially compressed by the compressive pressure applied by the anvil 1040. It may

also be noted upon comparing FIGS. 18C and 18D that the first layer 1011 and the third layer 1013 have been further compressed as well. After the staples 1020 have been completely, or at least sufficiently, formed, the anvil 1040 can be lifted away from the tissue T and the staple cartridge support 1030 can be moved away, and/or detached from, the staple cartridge 1000. As depicted in FIG. 18D, and as a result of the above, the cartridge body 1010 can be implanted with the staples 1020. In various circumstances, the implanted cartridge body 1010 can support the tissue along the staple line. In some circumstances, a haemostatic agent, and/or any other suitable therapeutic medicament, contained within the implanted cartridge body 1010 can treat the tissue over time. A haemostatic agent, as mentioned above, can reduce the bleeding of the stapled and/or incised tissue while a bonding agent or tissue adhesive can provide strength to the tissue over time. The implanted cartridge body 1010 can be comprised of materials such as ORC (oxidized regenerated cellulose), extracellular proteins such as collagen, polyglycolic acid (PGA) which is marketed under the trade name Vicryl, polylactic acid (PLA or PLLA), polydioxanone (PDS), polyhydroxyalkanoate (PHA), poliglecaprone 25 (PGCL) which is marketed under the trade name Monocryl, polycaprolactone (PCL), and/or a composite of PGA, PLA, PDS, PHA, PGCL and/or PCL, for example. In certain circumstances, the cartridge body 1010 can comprise an antibiotic and/or anti-microbial material, such as colloidal silver and/or triclosan, for example, which can reduce the possibility of infection in the surgical site.

[0622] The layers of the cartridge body 1010 can be connected to one another. The second layer 1012 can be adhered to the first layer 1011, the third layer 1013 can be adhered to the second layer 1012, and the fourth layer 1014 can be adhered to the third layer 1013 utilizing at least one adhesive, such as fibrin and/or protein hydrogel, for example. Although not illustrated, the layers of the cartridge body 1010 can be connected together by interlocking mechanical features. For example, the first layer 1011 and the second layer 1012 can each comprise corresponding interlocking features, such as a tongue and groove arrangement and/or a dovetail joint arrangement, for example. Similarly, the second layer 1012 and the third layer 1013 can each comprise corresponding interlocking features while the third layer 1013 and the fourth layer 1014 can each comprise corresponding interlocking features. Although not illustrated, the staple cartridge 1000 can comprise one or more rivets, for example, which can extend through one or more layers of the cartridge body 1010. For example, each rivet can comprise a first end, or head, positioned adjacent to the first layer 1011 and a second head positioned adjacent to the

fourth layer 1014 which can be either assembled to or formed by a second end of the rivet. Owing to the compressible nature of the cartridge body 1010, the rivets can compress the cartridge body 1010 such that the heads of the rivets can be recessed relative to the tissue-contacting surface 1019 and/or the bottom surface 1018 of the cartridge body 1010, for example. For example, the rivets can be comprised of a bioabsorbable material, such as polyglycolic acid (PGA) which is marketed under the trade name Vicryl, polylactic acid (PLA or PLLA), polydioxanone (PDS), polyhydroxyalkanoate (PHA), poliglecaprone 25 (PGCL) which is marketed under the trade name Monocryl, polycaprolactone (PCL), and/or a composite of PGA, PLA, PDS, PHA, PGCL and/or PCL, for example. The layers of the cartridge body 1010 may not be connected to one another other than by the staples 1020 contained therein. For example, the frictional engagement between the staple legs 1021 and the cartridge body 1010, for example, can hold the layers of the cartridge body 1010 together and, once the staples have been formed, the layers can be captured within the staples 1020. At least a portion of the staple legs 1021 can comprise a roughened surface or rough coating which can increase the friction forces between the staples 1020 and the cartridge body 1010.

[0623] As described above, a surgical instrument can comprise a first jaw including the staple cartridge support 1030 and a second jaw including the anvil 1040. As described in greater detail further below, the staple cartridge 1000 can comprise one or more retention features which can be configured to engage the staple cartridge support 1030 and, as a result, releasably retain the staple cartridge 1000 to the staple cartridge support 1030. The staple cartridge 1000 can be adhered to the staple cartridge support 1030 by at least one adhesive, such as fibrin and/or protein hydrogel, for example. In use, in at least one circumstance, especially in laparoscopic and/or endoscopic surgery, the second jaw can be moved into a closed position opposite the first jaw, for example, such that the first and second jaws can be inserted through a trocar into a surgical site. For example, the trocar can define an approximately 5mm aperture, or cannula, through which the first and second jaws can be inserted. The second jaw can be moved into a partially-closed position intermediate the open position and the closed position which can allow the first and second jaws to be inserted through the trocar without deforming the staples 1020 contained in the staple cartridge body 1010. For example, the anvil 1040 may not apply a compressive force to the staple cartridge body 1010 when the second jaw is in its partially-closed intermediate position while, alternatively, the anvil 1040 can compress the staple cartridge body

1010 when the second jaw is in its partially-closed intermediate position. Even though the anvil 1040 can compress the staple cartridge body 1010 when it is in such an intermediate position, the anvil 1040 may not sufficiently compress the staple cartridge body 1010 such that the anvil 1040 comes into contact with the staples 1020 and/or such that the staples 1020 are deformed by the anvil 1040. Once the first and second jaws have been inserted through the trocar into the surgical site, the second jaw can be opened once again and the anvil 1040 and the staple cartridge 1000 can be positioned relative to the targeted tissue as described above.

[0624] referring now to FIGS. 19A-19D, an end effector of a surgical stapler can comprise an implantable staple cartridge 1100 positioned intermediate an anvil 1140 and a staple cartridge support 1130. Similar to the above, the anvil 1140 can comprise a tissue-contacting surface 1141, the staple cartridge 1100 can comprise a tissue-contacting surface 1119, and the staple cartridge support 1130 can comprise a support surface 1131 which can be configured to support the staple cartridge 1100. Referring to FIG. 19A, the anvil 1140 can be utilized to position the tissue T against the tissue contacting surface 1119 of staple cartridge 1100 without deforming the staple cartridge 1100 and, when the anvil 1140 is in such a position, the tissue-contacting surface 1141 can be positioned a distance 1101a away from the staple cartridge support surface 1131 and the tissue-contacting surface 1119 can be positioned a distance 1102a away from the staple cartridge support surface 1131. Thereafter, as the anvil 1140 is moved toward the staple cartridge support 1130, referring now to FIG. 19B, the anvil 1140 can push the top surface, or tissue-contacting surface 1119, of staple cartridge 1100 downwardly and compress the first layer 1111 and the second layer 1112 of cartridge body 1110. As the layers 1111 and 1112 are compressed, referring again to FIG. 19B, the second layer 1112 can be crushed and the legs 1121 of staples 1120 can pierce the first layer 1111 and enter into the tissue T. For example, the staples 1120 can be at least partially positioned within staple cavities, or voids, 1115 in the second layer 1112 and, when the second layer 1112 is compressed, the staple cavities 1115 can collapse and, as a result, allow the second layer 1112 to collapse around the staples 1120. The second layer 1112 can comprise cover portions 1116 which can extend over the staple cavities 1115 and enclose, or at least partially enclose, the staple cavities 1115. FIG. 19B illustrates the cover portions 1116 being crushed downwardly into the staple cavities 1115. The second layer 1112 can comprise one or more weakened portions which can facilitate the collapse of the second layer 1112. Such weakened portions can comprise score marks, perforations, and/or thin cross-sections, for

example, which can facilitate a controlled collapse of the cartridge body 1110. The first layer 1111 can comprise one or more weakened portions which can facilitate the penetration of the staple legs 1121 through the first layer 1111. Such weakened portions can comprise score marks, perforations, and/or thin cross-sections, for example, which can be aligned, or at least substantially aligned, with the staple legs 1121.

[0625] When the anvil 1140 is in a partially closed, unfired position, referring again to FIG. 19A, the anvil 1140 can be positioned a distance 1101a away from the cartridge support surface 1131 such that a gap is defined therebetween. This gap can be filled by the staple cartridge 1100, having a staple cartridge height 1102a, and the tissue T. As the anvil 1140 is moved downwardly to compress the staple cartridge 1100, referring again to FIG. 19B, the distance between the tissue contacting surface 1141 and the cartridge support surface 1131 can be defined by a distance 1101b which is shorter than the distance 1101a. In various circumstances, the gap between the tissue-contacting surface 1141 of anvil 1140 and the cartridge support surface 1131, defined by distance 1101b, may be larger than the original, undeformed staple cartridge height 1102a. As the anvil 1140 is moved closer to the cartridge support surface 1131, referring now to FIG. 19C, the second layer 1112 can continue to collapse and the distance between the staple legs 1121 and the forming pockets 1142 can decrease. Similarly, the distance between the tissue-contacting surface 1141 and the cartridge support surface 1131 can decrease to a distance 1101c which may be greater than, equal to, or less than the original, undeformed cartridge height 1102a. Referring now to FIG. 19D, the anvil 1140 can be moved into a final, fired position in which the staples 1120 have been fully formed, or at least formed to a desired height. In such a position, the tissue-contacting surface 1141 of anvil 1140 can be a distance 1101d away from the cartridge support surface 1131, wherein the distance 1101d can be shorter than the original, undeformed cartridge height 1102a. As also illustrated in FIG. 19D, the staple cavities 1115 may be fully, or at least substantially, collapsed and the staples 1120 may be completely, or at least substantially, surrounded by the collapsed second layer 1112. In various circumstances, the anvil 1140 can be thereafter moved away from the staple cartridge 1100. Once the anvil 1140 has been disengaged from the staple cartridge 1100, the cartridge body 1110 can at least partially re-expand in various locations, i.e., locations intermediate adjacent staples 1120, for example. The crushed cartridge body 1110 may not resiliently re-expand. The formed staples 1120 and, in

addition, the cartridge body 1110 positioned intermediate adjacent staples 1120 may apply pressure, or compressive forces, to the tissue T which may provide various therapeutic benefits.

[0626] As discussed above, referring again to FIG. 19A, each staple 1120 can comprise staple legs 1121 extending therefrom. Although staples 1120 are depicted as comprising two staple legs 1121, various staples can be utilized which can comprise one staple leg or, alternatively, more than two staple legs, such as three staple legs or four staple legs, for example. As illustrated in FIG. 19A, each staple leg 1121 can be embedded in the second layer 1112 of the cartridge body 1110 such that the staples 1120 are secured within the second layer 1112. The staples 1120 can be inserted into the staple cavities 1115 in cartridge body 1110 such that the tips 1123 of the staple legs 1121 enter into the cavities 1115 before the bases 1122. After the tips 1123 have been inserted into the cavities 1115, the tips 1123 can be pressed into the cover portions 1116 and incise the second layer 1112. The staples 1120 can be seated to a sufficient depth within the second layer 1112 such that the staples 1120 do not move, or at least substantially move, relative to the second layer 1112. The staples 1120 can be seated to a sufficient depth within the second layer 1112 such that the bases 1122 are positioned or embedded within the staple cavities 1115. Alternatively, the bases 1122 may not be positioned or embedded within the second layer 1112. Referring again to FIG. 19A, the bases 1122 may extend below the bottom surface 1118 of the cartridge body 1110. The bases 1122 can rest on, or can be directly positioned against, the cartridge support surface 1130. The cartridge support surface 1130 can comprise support features extending therefrom and/or defined therein wherein, for example, the bases 1122 of the staples 1120 may be positioned within and supported by one or more support grooves, slots, or troughs, 1132, for example, in the staple cartridge support 1130, as described in greater detail further below.

[0627] Further to the above, referring now to FIG. 20, the bases 1122 of the staples 1120 can be positioned directly against the support surface 1131 of staple cartridge support 1130. Where the staple bases 1122 comprise circular or arcuate bottom surfaces 1124, for example, the staple bases 1122 may move or slide along the staple cartridge support surface 1131. Such sliding can occur when the anvil 1140 is pressed against the tips 1123 of the staple legs 1121 during the staple forming process. As described above and referring now to FIG. 21, the staple cartridge support 1130 can comprise one or more support slots 1132 therein which can be configured to eliminate, or at least reduce, the relative movement between the staple bases 1122 and the

cartridge support surface 1131. For example, each support slot 1132 can be defined by a surface contour which matches, or at least substantially matches, the contour of the bottom surface of the staple positioned therein. For example, the bottom surface 1124 of the base 1122 depicted in FIG. 21 can comprise a circular, or at least substantially circular, surface and the support slot 1132 can also comprise a circular, or at least substantially circular, surface. For example, the surface defining the slot 1132 can be defined by a radius of curvature which is greater than or equal to a radius of curvature which defines bottom surface 1124. Although the slots 1132 may assist in preventing or reducing relative sliding movement between the staples 1120 and the staple cartridge support 1130, the slots 1132 may also be configured to prevent or reduce relative rotational movement between the staples 1120 and the staple cartridge support 1130. More particularly, the slots 1132 can be configured to closely receive the bases 1122 in order to prevent or reduce the rotation of the staples 1120 about axes 1129, for example, such that the staples 1120 do not rotate or twist when they are being deformed.

[0628] Further to the above, each staple 1120 can be formed from a round, or an at least substantially round, wire. The legs and the base of each staple can be formed from a wire having a non-circular cross-section, such as a rectangular cross-section, for example. For example, the staple cartridge support 1130 can comprise corresponding non-circular slots, such as rectangular slots, for example, configured to receive the bases of such staples. Referring now to FIG. 22, each staple 1120 can comprise a crown, such as a crown 1125, for example, overmolded onto a base 1122 wherein each crown 1125 can be positioned within a support slot in the staple cartridge support 1130. For example, each crown 1125 can comprise a square and/or rectangular cross-section, for example, which can be configured to be received within square and/or rectangular slots 1134, for example, in the staple cartridge support 1130. The crowns 1125 can be comprised of a bioabsorbable plastic, such as polyglycolic acid (PGA) which is marketed under the trade name Vicryl, polylactic acid (PLA or PLLA), polydioxanone (PDS), polyhydroxyalkanoate (PHA), poliglecaprone 25 (PGCL) which is marketed under the trade name Monocryl, polycaprolactone (PCL), and/or a composite of PGA, PLA, PDS, PHA, PGCL and/or PCL, for example, and can be formed around the bases 1122 of the staples 1120 by an injection molding process, for example. Various crowns and methods for forming various crowns are disclosed in U.S. Patent Application Serial No. 11/541,123, entitled SURGICAL STAPLES HAVING COMPRESSIBLE OR CRUSHABLE MEMBERS FOR SECURING TISSUE

THEREIN AND STAPLING INSTRUMENTS FOR DEPLOYING THE SAME, filed on September 29, 2006, the entire disclosure of which is incorporated by reference herein. Referring again to FIG. 22, the slots 1134 can further comprise lead-ins, or bevels, 1135 which can be configured to facilitate the insertion of the crowns 1125 into the slots 1134. The bases and/or crowns of the staples 1120 may be positioned within the slots 1134 when the staple cartridge 1100 is assembled to the staple cartridge support 1130. The crowns 1125 of the staples 1120 may be aligned with the slots 1134 when the staple cartridge 1100 is assembled to the staple cartridge support 1130. For example, the crowns 1125 may not enter into the slots 1134 until a compressive force is applied to the staple legs 1121 and the bases and/or crowns of the staples 1120 are pushed downwardly into the slots 1134.

[0629] Referring now to FIGS. 23 and 24, a staple cartridge, such as staple cartridge 1200, for example, can comprise a compressible, implantable cartridge body 1210 comprising an outer layer 1211 and an inner layer 1212. Similar to the above, the staple cartridge 1200 can comprise a plurality of staples 1220 positioned within the cartridge body 1210. Each staple 1220 can comprise a base 1222 and one or more staple legs 1221 extending therefrom. For example, the staple legs 1221 can be inserted into the inner layer 1212 and seated to a depth in which the bases 1222 of the staples 1220 abut and/or are positioned adjacent to the bottom surface 1218 of the inner layer 1212, for example. In FIGS. 23 and 24, the inner layer 1212 does not comprise staple cavities configured to receive a portion of the staples 1220 while, as an alternative, the inner layer 1212 can comprise such staple cavities. Further to the above, the inner layer 1212 can be comprised of a compressible material, such as bioabsorbable foam and/or oxidized regenerated cellulose (ORC), for example, which can be configured to allow the cartridge body 1210 to collapse when a compressive load is applied thereto. The inner layer 1212 can be comprised of a lyophilized foam comprising polylactic acid (PLA) and/or polyglycolic acid (PGA), for example. The ORC may be commercially available under the trade name Surgicel and can comprise a loose woven fabric (like a surgical sponge), loose fibers (like a cotton ball), and/or a foam. The inner layer 1212 can be comprised of a material including medicaments, such as freeze-dried thrombin and/or fibrin, for example, contained therein and/or coated thereon which can be water-activated and/or activated by fluids within the patient's body, for example. For example, the freeze-dried thrombin and/or fibrin can be held on a Vicryl (PGA) matrix, for example. In certain circumstances, however, the activatable medicaments can be unintentionally

activated when the staple cartridge 1200 is inserted into a surgical site within the patient, for example. Referring again to FIGS. 23 and 24, the outer layer 1211 can be comprised of a water impermeable, or at least substantially water impermeable, material such that liquids do not come into contact with, or at least substantially contact, the inner layer 1212 until after the cartridge body 1210 has been compressed and the staple legs have penetrated the outer layer 1211 and/or after the outer layer 1211 has been incised in some fashion. The outer layer 1211 can be comprised of a buttress material and/or plastic material, such as polydioxanone (PDS) and/or polyglycolic acid (PGA), for example. The outer layer 1211 can comprise a wrap which surrounds the inner layer 1212 and the staples 1220. More particularly, the staples 1220 can be inserted into the inner layer 1212 and the outer layer 1211 can be wrapped around the sub-assembly comprising the inner layer 1212 and the staples 1220 and then sealed.

[0630] Referring now to FIGS. 25 and 26, a staple cartridge, such as staple cartridge 1300, for example, can comprise a compressible, implantable cartridge body 1310 including an outer layer 1311 and an inner layer 1312. Similar to the above, the staple cartridge 1300 can further comprise staples 1320 positioned within the cartridge body 1310 wherein each staple 1320 can comprise a base 1322 and one or more legs 1321 extending therefrom. Similar to staple cartridge 1200, the bases 1322 of staples 1320 can extend below the bottom surface 1318 of the inner layer 1312 and the outer layer 1311 can surround the bases 1322. For example, the outer layer 1311 can be sufficiently flexible so as to envelop each staple base 1322 such that the outer layer 1311 conforms to the contour of the bases 1322. Alternatively, referring again to FIG. 24, the outer layer 1211 can be sufficiently rigid such that it extends around the bases 1222 without conforming to each base 1222. In any event, the outer layer 1311 can be positioned intermediate the bases 1322 of staples 1320 and a staple cartridge support surface, such as support surfaces 1031 or 1131, for example, supporting the staple cartridge 1300. For example, the outer layer 1311 can be positioned intermediate the bases 1322 and support slots, such as slots 1032 or 1132, for example, defined in the staple cartridge support surface. For example, further to the above, the outer layer 1311 can be configured to limit the movement of the bases 1322 and/or increase the coefficient of friction between the bases 1322 and the staple cartridge support surface and/or support slots in order to reduce relative movement therebetween. Alternatively, referring now to FIGS. 27 and 28, the outer layer of a staple cartridge, such as staple cartridge 1400, for example, may not entirely surround the staples positioned therein. For example, an outer layer 1411 of a

compressible, implantable cartridge body 1410 may be assembled to the inner layer 1412 before the staple legs 1421 of staples 1420 are inserted into the cartridge body 1410. As a result of the above, the bases 1422 of staples 1420 may extend outside of the outer layer 1411 and, for example, the bases 1422 may be positioned directly into the support slots 1032 or 1132 within the staple cartridge support surfaces 1031 or 1131, for example. The staple legs 1421 may incise the outer layer 1411 when they are inserted therethrough. In various circumstances, the holes created by the staple legs 1421 may closely surround the staple legs 1421 such that very little, if any, fluid can leak between the staple legs 1421 and the outer layer 1411 which can reduce the possibility of, or prevent, the medicament contained within the staple cartridge body 1410 from being activated and/or leaking out of the cartridge body 1410 prematurely.

[0631] As discussed above, referring again to FIGS. 23 and 24, the legs 1221 of the staples 1220 can be embedded within the cartridge body 1210 and the bases 1222 of staples 1220 may extend outwardly from the bottom surface 1218 of the inner layer 1212. Further to the above, the inner layer 1212 may not comprise staple cavities configured to receive the staples 1220. Alternatively, referring now to FIGS. 29 and 30, a staple cartridge, such as staple cartridge 1500, for example, may comprise a compressible, implantable cartridge body 1510 comprising staple cavities 1515 which can be configured to receive at least a portion of the staples 1520 therein. For example, a top portion of the staple legs 1521 of the staples 1520 may be embedded in the inner layer 1512 while a bottom portion of the staple legs 1521, and the bases 1522, may be positioned within the staple cavities 1515. The bases 1522 may be entirely positioned in the staple cavities 1515 while, the bases 1522 may at least partially extend below the bottom surface 1518 of the inner layer 1512. Similar to the above, the outer layer 1511 may enclose the inner layer 1512 and the staples 1520 positioned therein. Alternatively, referring now to FIG. 31, a staple cartridge 1600 may comprise staples 1620 positioned within staple cavities 1615 in a compressible, implantable cartridge body 1610 wherein at least a portion of the staples 1620 are not enclosed by the outer layer 1611. For example, each staple 1620 can comprise staple legs 1621 which are at least partially embedded in the inner layer 1612 and, in addition, bases 1622 which extend outwardly around the outer layer 1611.

[0632] Referring now to FIGS. 32 and 33, a staple cartridge, such as staple cartridge 1700, for example, can comprise a compressible, implantable cartridge body 1710 and a plurality of staples 1720 at least partially positioned within the cartridge body 1710. The cartridge body 1710

can comprise an outer layer 1711, an inner layer 1712, and, in addition, an alignment matrix 1740 which can be configured to align and/or retain the staples 1720 in position within the cartridge body 1710. The inner layer 1712 can comprise a recess 1741 which can be configured to receive the alignment matrix 1740 therein. The alignment matrix 1140 can be press-fit within the recess 1741 and/or otherwise suitably secured to the inner layer 1712 utilizing at least one adhesive, such as fibrin and/or protein hydrogel, for example. The recess 1741 can be configured such that the bottom surface 1742 of alignment matrix 1740 is aligned, or at least substantially aligned, with the bottom surface 1718 of the inner layer 1712. The bottom surface 1742 of the alignment matrix can be recessed with respect to and/or extend from the bottom surface 1718 of the second layer 1712. Each staple 1720 can comprise a base 1722 and one or more legs 1721 extending from the base 1722, wherein at least a portion of the staple legs 1721 can extend through the alignment matrix 1740. The alignment matrix 1740 can further comprise a plurality of apertures and/or slots, for example, extending therethrough which can be configured to receive the staple legs 1721 therein. For example, each aperture can be configured to closely receive a staple leg 1721 such that there is little, if any, relative movement between the staple leg 1721 and the sidewalls of the aperture. The alignment matrix apertures may not extend entirely through the alignment matrix 1740 and the staple legs 1721 may be required to incise the alignment matrix 1740 as the staple legs 1721 are pushed therethrough.

[0633] The alignment matrix 1740 can be comprised of a molded plastic body which can be stiffer or less compressible than the inner layer 1712 and/or the outer layer 1711. For example, the alignment matrix 1740 can be comprised of a plastic material and/or any other suitable material, such as polydioxanone (PDS) and/or polyglycolic acid (PGA), for example. The alignment matrix 1740 can be assembled to the inner layer 1712 and the staple legs 1721 can thereafter be inserted through the alignment matrix 1740 and embedded into the inner layer 1712. The bottom surface 1742 of the alignment matrix 1740 can comprise one or more grooves, slots, or troughs, for example, which can be configured to at least partially receive the bases 1722 of the staples 1720. Similar to the above, the outer layer 1711 can then be placed around the subassembly comprising the inner layer 1712, the alignment matrix 1740, and the staples 1720. Alternatively, the outer layer 1711 can be placed around a subassembly comprising the inner layer 1712 and the alignment matrix 1740 wherein the staples 1720 can be thereafter inserted through the outer layer 1711, the alignment matrix 1740, and the inner layer 1712. In

any event, as a result of the above, the inner layer 1712, the alignment matrix 1740, and/or the outer layer 1711 can be configured to retain the staples 1720 in position until and/or after they are deformed by an anvil as described above. For example, the alignment matrix 1740 can serve to hold the staples 1720 in place before the staple cartridge 1700 is implanted within a patient and, in addition, secure the tissue along the staple line after the staple cartridge 1700 has been implanted. The staples 1720 may be secured within the alignment matrix 1740 without being embedded in the inner layer 1712 and/or the outer layer 1711, for example.

[0634] Referring now to FIGS. 34-40, a staple cartridge, such as staple cartridge 1800, for example, can be assembled by compressing an inner layer 1812, inserting staples, such as staples 1820, for example, into the inner layer 1812, and wrapping the inner layer 1812 with an outer layer 1811. Referring primarily to FIG. 34, a compressible inner layer 1812 is illustrated as comprising a plurality of staple cavities 1815 defined therein, although other embodiments are envisioned in which the inner layer 1812 does not comprise staple cavities, as described above. Referring now to FIG. 35, the compressible inner layer 1812 can be positioned intermediate a transfer plate 1850 and a support plate 1860 and compressed between the compression surfaces 1852 and 1862 thereof, respectively. As illustrated in FIG. 35, the top and bottom surfaces of the inner layer 1812 can be compressed toward one another and, in response thereto, the inner layer 1812 can bulge outwardly in the lateral directions. The inner layer 1812 can be compressed to a height which is approximately one-third of its original height, for example, and can have a height or thickness between approximately 0.06” and approximately 0.08” in its compressed state, for example. As also illustrated in FIG. 35, the transfer plate 1850 can further comprise a plurality of staples, such as staples 1820, for example, positioned within a plurality of staple wells 1853. In addition, the transfer plate 1850 can further comprise a plurality of drivers 1851 which can be configured to push the staples 1820 upwardly and out of the staple wells 1853. Referring now to FIG. 36, the drivers 1851 can be utilized to push the staple legs 1821 of the staples 1820 into and through the compressed inner layer 1812. The drivers 1851 can be configured such that the top surfaces thereof are positioned flush, or at least nearly flush, with the compression surface 1852 of the transfer plate 1850 when the staples 1820 have been fully deployed from the staple wells 1853 of transfer plate 1850. As also illustrated in FIG. 36, the support plate 1860 can comprise a plurality of receiving apertures 1861 which can be configured to receive the staple legs 1821, or at least the tips of the staple legs 1821, after they are pushed through the inner layer 1812. The

receiving apertures 1861, or the like, may be necessitated where the inner layer 1812 has been compressed to a height which is shorter than the height of the staples 1820 and, thus, when the staples 1820 have been fully ejected from the staple wells 1853, the staple legs 1821 may protrude from the top surface of the compressed inner layer 1812. Alternatively, the inner layer 1812 may be compressed to a height which is taller than the height of the staples 1820 and, as a result, the receiving apertures 1861 in support plate 1860 may be unnecessary.

[0635] After the staples 1820 have been inserted into the inner layer 1812, referring now to FIG. 37, the support plate 1860 can be moved away from the transfer plate 1850 in order to allow the inner layer 1812 to decompress. In such circumstances, the inner layer 1812 can resiliently re-expand to its original, or at least near-original, uncompressed height. As the inner layer 1812 re-expands, the height of the inner layer 1812 can increase such that it exceeds the height of the staples 1820 and such that the staple legs 1821 of the staples 1820 no longer protrude from the top surface of the inner layer 1812. In various circumstances, the receiving apertures 1861 can be configured to hold the staple legs 1821 in position at least until the support plate 1860 has been sufficiently moved away such that the legs 1821 are no longer positioned within the receiving apertures 1861. In such circumstances, the receiving apertures 1861 can assist in maintaining the relative alignment of the staples 1820 within the inner layer 1812 as it re-expands. In various circumstances, the inner layer 1812 and the staples 1820 positioned therein can comprise a subassembly 1801 which, referring now to FIG. 38, can be inserted into an outer layer 1811, for example. For example, the outer layer 1811 can comprise a cavity 1802 defined therein which can be configured to receive the subassembly 1801 therein. In various circumstances, a tool, such as pliers 1855, for example, can be utilized to pull the outer layer 1811 onto the subassembly 1801. Once the subassembly 1801 has been sufficiently positioned within the outer layer 1811, referring now to FIG. 39, the outer layer 1811 can be sealed. The outer layer 1811 can be sealed utilizing the application of heat energy to a portion thereof. More particularly, the outer layer 1811 can be comprised of a plastic material wherein the open end of the outer layer 1811 can be heat-staked by one or more heated elements, or irons, 1856 in order to bond and/or seal the perimeter of the open end of the outer layer 1811 together. For example, referring now to FIG. 40, an excess portion 1857 of the outer layer 1811 can be removed and the staple cartridge 1800 can then be used as described herein.

[0636] As described above, a staple cartridge can be positioned within and/or secured to a staple cartridge attachment portion. Referring now to FIGS. 41 and 42, a staple cartridge attachment portion can comprise a staple cartridge channel, such as staple cartridge channel 1930, for example, which can be configured to receive at least a portion of a staple cartridge, such as staple cartridge 1900, for example, therein. The staple cartridge channel 1930 can comprise a bottom support surface 1931, a first lateral support wall 1940, and a second lateral support wall 1941. In use, the staple cartridge 1900 can be positioned within the staple cartridge channel 1930 such that the staple cartridge 1900 is positioned against and/or adjacent to the bottom support surface 1931 and positioned intermediate the first lateral support wall 1940 and the second lateral support wall 1941. The first lateral support wall 1940 and the second lateral support wall 1941 can define a lateral gap therebetween. For example, the staple cartridge 1900 can comprise a lateral width 1903 which is the same as and/or wider than the lateral gap defined between the support walls 1940 and 1941 such that a compressible, implantable cartridge body 1910 of the staple cartridge 1900 can fit securely between the walls 1940 and 1941. Alternatively, the lateral width 1903 of the staple cartridge 1900 can be shorter than the gap defined between the first and second side walls 1940 and 1941. at least a portion of the walls 1940 and 1941 and the bottom support surface 1931 can be defined by a stamped metal channel while, at least a portion of the lateral support wall 1940 and/or lateral support wall 1941 can be comprised of a flexible material, such as an elastomeric material, for example. Referring primarily to FIG. 41, the first side wall 1940 and the second side wall 1941 of the staple cartridge channel 1930 can each be comprised of a rigid portion 1933 extending upwardly from the bottom support surface 1931 and a flexible portion 1934 extending upwardly from the rigid portions 1933.

[0637] Further to the above, the cartridge body 1910 of staple cartridge 1900 can be comprised of one or more compressible layers, such as first layer 1911 and second layer 1912, for example. When the cartridge body 1910 is compressed against the bottom support surface 1931 by an anvil, as described above, the side portions of the cartridge body 1910 can expand laterally. Where the staple cartridge 1930 is comprised of rigid side walls, the lateral expansion of the cartridge body 1910 can be prevented, or at least limited, by the rigid side walls and, as a result, a significant amount of internal pressure, or stress, can be developed within the cartridge body 1910. Where at least a portion of the staple cartridge 1930 is comprised of flexible side walls, the flexible side walls can be configured to flex laterally and permit the side portions of the cartridge

body 1910 to expand laterally, thereby reducing the internal pressure, or stress, generated within the cartridge body 1910. Where the cartridge channel does not comprise lateral side walls, or comprises lateral sidewalls which are relatively shorter than the staple cartridge, the side portions of the staple cartridge may expand laterally uninhibited, or at least substantially uninhibited. In any event, referring now to FIG. 42, a staple cartridge channel 2030 can comprise lateral sidewalls 2040 and 2041 which can be entirely comprised of a flexible material, such as an elastomeric material, for example. The staple cartridge channel 2030 can further comprise lateral slots 2033 extending along the sides of the bottom support surface 2031 of the staple cartridge channel 2030 which can be configured to receive and secure at least a portion of the lateral sidewalls 2040 and 2041 therein. The lateral side walls 2040 and 2041 can be secured in the slots 2033 via a snap-fit and/or press-fit arrangement, or the lateral side walls 2040 and 2041 can be secured in the slots 2033 by one or more adhesives. The sidewalls 2040 and 2041 may be detachable from the bottom support surface 2031 during use. In any event, a compressible, implantable cartridge body 2010 can be detached and/or disengaged from the lateral side walls 2040 and 2041 when the cartridge body 2010 is implanted with the staples 2020.

[0638] Referring now to FIG. 43, a surgical instrument can comprise a shaft 2150 and an end effector extending from the distal end of the shaft 2150. The end effector can comprise, similar to the above, a staple cartridge channel 2130, an anvil 2140 movable between an open position and a closed position, and a staple cartridge 2100 positioned intermediate the staple cartridge channel 2130 and the anvil 2140. Also similar to the above, the staple cartridge 2100 can comprise a compressible, implantable cartridge body 2110 and a plurality of staples 2120 positioned in the cartridge body 2110. The staple cartridge channel 2130 can comprise, one, a bottom support surface 2131 against which the staple cartridge 2100 can be positioned, two, a distal end 2135 and, three, a proximal end 2136. As illustrated in FIG. 43, the staple cartridge 2100 can comprise a first end 2105 which can be positionable in the distal end 2135 of the staple cartridge channel 2130 and a second end 2106 which can be positionable in the proximal end 2136 of the staple cartridge channel 2130. The distal end 2135 of the staple cartridge channel 2130 can comprise at least one distal retention feature, such as a retention wall 2137, for example, and, similarly, the proximal end 2136 can comprise at least one proximal retention feature, such as a retention wall 2138, for example. For example, the distal retention wall 2137 and the proximal retention wall 2138 can define a gap therebetween which can be equal to or less

than the length of the staple cartridge 2100 such that the staple cartridge 2100 can fit securely within the staple cartridge channel 2130 when the staple cartridge 2100 is inserted therein.

[0639] Referring again to FIGS. 23 and 24, a staple cartridge, such as staple cartridge 1200, for example, can comprise a flat, or at least substantially flat, tissue-contacting surface 1219. For example, the staple cartridge body 1210 of staple cartridge 1200 can comprise a first end 1205 which can be defined by a first height, or thickness, 1207 and a second end 1206 which can be defined by a second height, or thickness, 1208, wherein the first height 1207 can be equal to, or at least substantially equal to, the second height 1208. The cartridge body 1210 can comprise a constant, or at least substantially constant, height, or thickness, between the first end 1205 and the second end 1206. For example, the tissue-contacting surface 1219 can be parallel, or at least substantially parallel, to the bottom surface 1218 of the cartridge body 1210. Referring once again to FIG. 43, the first end 2105 of the cartridge body 2110 of staple cartridge 2100 can be defined by a first height 2107 which is different than a second height 2108 of the second end 2106. In the illustrated embodiment, the first height 2107 is larger than the second height 2108, although the second height 2108 could be larger than the first height 2107 in alternative embodiments. The height of the cartridge body 2110 can decrease linearly and/or geometrically between the first end 2105 and the second end 2106. For example, the tissue-contacting surface 2119, which extends between the first end 2105 and the second end 2106, can be oriented along an angle defined therebetween. For example, the tissue-contacting surface 2119 may not be parallel to the bottom surface 2118 of the cartridge body 2110 and/or parallel to the support surface 2131 of the staple cartridge channel 2130.

[0640] Referring again to FIGS. 43 and 44, the anvil 2140 can comprise a tissue-contacting surface 2141 which can be parallel, or at least substantially parallel, to the support surface 2131 of the staple cartridge channel 2130 when the anvil 2140 is in a closed position, as illustrated in FIG. 44. When the anvil 2140 is in a closed position, the anvil 2140 can be configured to compress the first end 2105 of the staple cartridge 2100 more than the second end 2106 owing to the taller height of the first end 2105 and the shorter height of the second end 2106. In some circumstances, including circumstances where the tissue T positioned intermediate the tissue contacting surfaces 2119 and 2141 has a constant, or at least substantially constant, thickness, the pressure generated within the tissue T and the cartridge 2100 can be greater at the distal end of the end effector than the proximal end of the end effector. More particularly, when the tissue T

between the anvil 2140 and the staple cartridge 2100 has a substantially constant thickness, the tissue T positioned intermediate the distal end 2145 of the anvil 2140 and the first end 2105 of the staple cartridge 2100 can be more compressed than the tissue T positioned intermediate the proximal end 2146 of the anvil 2140 and the second end 2106 of the staple cartridge 2100. A pressure gradient can be generated within the tissue T between the proximal end and the distal end of the end effector. More particularly, when the tissue T between the anvil 2140 and the staple cartridge 2100 has a substantially constant thickness and the height of the staple cartridge 2100 decreases linearly from the distal end to the proximal end of the end effector, the pressure within the tissue T can decrease linearly from the distal end of the end effector to the proximal end of the end effector. Similarly, when the tissue T between the anvil 2140 and the staple cartridge 2100 has a substantially constant thickness and the height of the staple cartridge 2100 decreases geometrically from the distal end to the proximal end of the end effector, the pressure within the tissue T can decrease geometrically from the distal end of the end effector to the proximal end of the end effector.

[0641] Referring again to FIG. 43, the tissue T positioned intermediate the staple cartridge 2100 and the anvil 2140 may not have a constant thickness throughout. In at least one such circumstance, the tissue T positioned between the proximal end 2146 of the anvil 2140 and the second end 2106 of the staple cartridge 2100 may be thicker than the tissue T positioned between the distal end 2145 of the anvil 2140 and the first end 2105 of the staple cartridge 2100. In such circumstances, as a result, the thicker tissue T may be generally positioned above the shorter proximal end 2106 of the staple cartridge 2100 and the thinner tissue T may be generally positioned above the taller distal end 2105. In use, the firing collar 2152 of the shaft 2150 can be advanced distally along the shaft spine 2151 such that the firing collar 2152 engages the cam portion 2143 of the anvil 2140 and rotates the anvil 2140 toward the staple cartridge 2100 as illustrated in FIG. 44. Once the anvil 2140 has been rotated into a fully-closed position, the tissue T may be compressed between the tissue-contacting surfaces 2119 and 2141 and, even though the height of the staple cartridge 2100 may not be constant between the proximal and distal ends of the end effector, the pressure or compressive forces applied to the tissue T may be constant, or at least substantially constant, thereacross. More particularly, as the thinner tissue T may be associated with the taller height of the staple cartridge 2100 and the thicker tissue T may be associated with the shorter height of the staple cartridge 2100, the cumulative, or summed, height

of the tissue T and the staple cartridge 2100 may be constant, or at least substantially constant, between the proximal and distal ends of the end effector and, as a result, the compression of this cumulative height by the anvil 2140 may be constant, or at least substantially constant, thereacross.

[0642] Referring again to FIGS. 43 and 44, the staple cartridge 2100 can comprise an asymmetrical configuration. For example, for example, the height of the staple cartridge 2100 at the first end 2105 thereof may be higher than the height of the staple cartridge 2100 at the second end 2106 thereof. The staple cartridge 2100 and/or the staple cartridge channel 2130 can comprise one or more alignment and/or retention features which can be configured to assure that the staple cartridge 2100 can only be positioned within the staple cartridge channel 2130 in one orientation, i.e., an orientation in which the first end 2105 is positioned in the distal end 2135 of the staple cartridge channel 2130 and the second end 2106 is positioned in the proximal end 2136. Alternatively, the staple cartridge 2100 and/or the staple cartridge channel 2130 can comprise one or more alignment and/or retention features which can be configured to permit the staple cartridge 2100 to be positioned within the staple cartridge channel 2130 in more than one orientation. Referring now to FIG. 45, for example, the staple cartridge 2100 can be positioned within the staple cartridge channel 2130 such that the first end 2105 of the staple cartridge 2100 can be positioned in the proximal end 2136 of the staple cartridge channel 2130 and the second end 2106 can be positioned in the distal end 2135. As a result, the shorter height of the staple cartridge 2100 can be positioned proximate the distal retention wall 2137 and the taller height of the staple cartridge 2100 can be positioned proximate to the proximal retention wall 2138. For example, the staple cartridge 2100 can be suitably arranged to apply a constant, or at least substantially constant, clamping pressure to tissue T having a thicker portion within the distal end of the end effector and a thinner portion within the proximal end of the end effector. The staple cartridge 2100, for example, can be selectively oriented within the staple cartridge channel 2130. For example, the alignment and/or retention features of the staple cartridge 2100 can be symmetrical and a surgeon can selectively orient the staple cartridge 2100 within the staple cartridge channel 2130 in the orientations depicted in FIG. 43 and FIG. 45, for example.

[0643] Further to the above, the implantable cartridge body 2110 can comprise a longitudinal axis 2109 which, when the staple cartridge 2100 is positioned in the staple cartridge channel 2130, can extend between the proximal and distal ends of the end effector. The thickness of the

cartridge body 2110 can generally decrease and/or generally increase between the first end 2105 and the second end 2106 along the longitudinal axis 2109. For example, the distance, or height, between the bottom surface 2118 and the tissue-contacting surface 2119 can generally decrease and/or generally increase between the first end 2105 and the second end 2106. The thickness of the cartridge body 2110 can both increase and decrease along the longitudinal axis 2109. For example, the thickness of the cartridge body 2110 can comprise one or more portions which increase in thickness and one or more portions which can decrease in thickness. The staple cartridge 2100 can comprise a plurality of staples 2120 positioned therein. In use, as described above, the staples 2120 can be deformed when the anvil 2140 is moved into a closed position. Each staple 2120 can have the same, or at least substantially the same, height. For example, the height of a staple can be measured from the bottom of the base of the staple to the top, or tip, of the tallest leg of the staple, for example.

[0644] The staples within a staple cartridge can have different staple heights. For example, a staple cartridge can comprise a first group of staples having a first staple height which are positioned in a first portion of a compressible cartridge body and a second group of staples having a second staple height which are positioned in a second portion of the compressible cartridge body. The first staple height can be taller than the second staple height and the first group of staples can be positioned in the first end 2105 of the staple cartridge 2100 while the second group of staples can be positioned in the second end 2106. Alternatively, the taller first group of staples can be positioned in the second end 2106 of the staple cartridge 2100 while the shorter second group of staples can be positioned in the first end 2105. A plurality of staple groups, each group having a different staple height, can be utilized. For example, a third group having an intermediate staple height can be positioned in the cartridge body 2110 intermediate the first group of staples and the second group of staples. Each staple within a staple row in the staple cartridge can comprise a different staple height. The tallest staple within a staple row can be positioned on a first end of a staple row and the shortest staple can be positioned on an opposite end of the staple row. For example, the staples positioned intermediate the tallest staple and the shortest staple can be arranged such that the staple heights descend between the tallest staple and the shortest staple, for example.

[0645] Referring now to FIG. 46, an end effector of a surgical stapler can comprise an anvil 2240, a staple cartridge channel 2230, and a staple cartridge 2200 supported by the staple

cartridge channel 2230. The staple cartridge 2200 can comprise a compressible, implantable cartridge body 2210 and a plurality of staples, such as staples 2220a and staples 2220b, for example, positioned therein. The staple cartridge channel 2230 can comprise a cartridge support surface 2231 and a plurality of staple support slots, such as support slots 2232a and 2232b, for example, defined therein. For example, the staple cartridge 2200 can comprise two outer rows of staples 2220a and two inner rows of staples 2220b, wherein the support slots 2232a can be configured to support the staples 2220a and the support slots 2232b can be configured to support the staples 2220b. Referring to FIGS. 46 and 47, the anvil 2240 can comprise a plurality of staple forming pockets 2242 defined therein which can be configured to receive and deform the staples 2220a and 2220b when the anvil 2240 is moved toward the staple cartridge 2200. For example, the bottom surfaces of the support slots 2232a can be a first distance 2201a away from the top surfaces of the staple forming pockets 2242 while the bottom surfaces of the support slots 2232b can be a second distance 2201b away from the top surfaces of the staple forming pockets 2242. For example, the support slots 2232b are positioned closer to the anvil 2240 owing to the raised step in the support surface 2231 in which they are defined. Owing to the different distances 2201a and 2201b, the outer rows of staples 2220a and the inner rows of staples 2220b can be deformed to different formed heights. In various circumstances, staples deformed to different formed heights can apply different clamping pressures or forces to the tissue T being stapled. In addition to the above, the staples can begin with different unformed staple heights. For example, referring again to FIG. 46, the outer staples 2220a can have an initial, unformed height which is greater than the initial, unformed height of the inner staples 2220b. As illustrated in FIGS. 46 and 47, the inner staples 2220b, which have a shorter unformed height than the outer staples 2220a, can also have a shorter formed height than the outer staples 2220b. Alternatively, the inner staples 2220b may have a taller unformed height than the outer staples 2220a yet have a shorter deformed staple height than the outer staples 2220a.

[0646] Further to the above, the anvil 2240 can be moved into a closed position, as illustrated in FIG. 47, in order to compress the cartridge body 2210 and deform the staples 2220a and 2220b. A surgical stapler comprising the end effector depicted in FIGS 46 and 47, for example, can further comprise a cutting member which can be configured to transect the tissue T positioned intermediate the anvil 2240 and the staple cartridge 2200. For example, the anvil 2240, the staple cartridge channel 2230 and/or the staple cartridge 2200 can define a slot configured to slidably

receive a cutting member therein. More particularly, the anvil 2240 can comprise a slot portion 2249, the staple cartridge channel 2230 can comprise a slot portion 2239, and the staple cartridge 2200 can comprise a slot portion 2203 which can be aligned, or at least substantially aligned, with one another when the anvil 2240 is in a closed, or at least substantially closed, position. The cutting member can be moved from the proximal end of the end effector toward the distal end of the end effector after the anvil 2240 has been closed and the staples 2220a, 2220b have been deformed. The cutting member can be moved independently of the staple deformation process. The cutting member can be advanced at the same time that the staples are being deformed. In any event, the cutting member can be configured to incise the tissue along a path positioned intermediate the inner rows of staples 2220b.

[0647] As illustrated in FIG. 47, the inner staples 2220b can be formed to a shorter height than the outer staples 2220a wherein the inner staples 2220b can apply a larger clamping pressure or force to the tissue adjacent to the cut line created by the cutting member. For example, the larger clamping pressure or force created by the inner staples 2220b can provide various therapeutic benefits such as reducing bleeding from the incised tissue T while the smaller clamping pressure created by the outer staples 2220a can provide flexibility within the stapled tissue. Referring again to FIGS. 46 and 47, the anvil 2240 can further comprise at least one piece of buttress material, such as buttress material 2260, for example, attached thereto. For example, the legs of the staples 2220a, 2220b can be configured to incise the buttress material 2260 and/or pass through apertures in the buttress material 2260 when the staple cartridge 2200 is compressed by the anvil 2240 and thereafter contact the staple forming pockets 2242 in the anvil 2240. As the legs of the staples 2220a, 2220b are being deformed, the legs can contact and/or incise the buttress material 2260 once again. The buttress material 2260 can improve the hemostasis of and/or provide strength to the tissue being stapled.

[0648] Referring again to FIGS. 46 and 47, the bottom surface of the cartridge body 2210 can comprise a stepped contour which matches, or at least substantially matches, the stepped contour of the cartridge support surface 2231. The bottom surface of the cartridge body 2210 can deform to match, or at least substantially match, the contour of the cartridge support surface 2231. Referring now to FIG. 48, an end effector, similar to the end effector depicted in FIG. 46, for example, can comprise a staple cartridge 2300 positioned therein. The staple cartridge 2300 can comprise a compressible, implantable body 2310 comprising an inner layer 2312 and an outer

layer 2311 wherein, further to the above, the outer layer 2311 can be comprised of a water impermeable material. The outer layer 2311 can extend around the staples 2220a, 2220b and can be positioned intermediate the staples 2220a, 2220b and the support slots 2232a, 2232b, respectively. Referring now to FIG. 49, an end effector, similar to the end effector depicted in FIG. 46, for example, can comprise a staple cartridge 2400 positioned therein. Similar to the staple cartridge 2300, the compressible, implantable cartridge body 2410 of staple cartridge 2400 can comprise an inner layer 2412 and an outer layer 2411; however; the cartridge body 2410 may not comprise a cutting member slot therein. For example, the cutting member may be required to incise the inner layer 2412 and/or the outer layer 2411, for example, as it is advanced through the staple cartridge.

[0649] Referring now to FIG. 50, an end effector of a surgical stapler can comprise an anvil 2540, a staple cartridge channel 2530, and a staple cartridge 2500 positioned in the staple cartridge channel 2530. Similar to the above, the staple cartridge 2500 can comprise a compressible, implantable cartridge body 2510, outer rows of staples 2220a, and inner rows of staples 2220b. The staple cartridge channel 2530 can comprise a flat, or an at least substantially flat, cartridge support surface 2531 and staple support slots 2532 defined therein. The anvil 2540 can comprise a stepped surface 2541 and a plurality of staple forming pockets, such as forming pockets 2542a and 2542b, for example, defined therein. Similar to the above, the forming pockets 2542a and the support slots 2532 can define a distance therebetween which is greater than the distance between the forming pockets 2452b and the support slots 2532. The anvil 2540 can further comprise a piece of buttress material 2560 attached to the stepped surface 2541 of the anvil 2540. For example, the buttress material 2560 can conform, or at least substantially conform, to the stepped surface 2541. The buttress material 2560 can be removably attached to the surface 2541 by at least one adhesive, such as fibrin and/or protein hydrogel, for example. The cartridge body 2510 can also comprise a stepped profile which, parallels, or at least substantially parallels, the stepped surface 2541 of the anvil 2540. More particularly, the anvil 2540 can comprise steps 2548 extending toward the staple cartridge 2500 wherein the steps 2548 can comprise a step height which equals, or at least substantially equals, the step height of the steps 2508 extending from the cartridge body 2510. For example, as a result of the above, the amount of the compressible cartridge body 2510 that can be captured in the first staples 2220a

can be different than the amount of the compressible cartridge body 2510 that can be captured in the second staples 2220b, for example.

[0650] Referring now to FIG. 51, an end effector can comprise an anvil 2640, a staple cartridge channel 2530, and a staple cartridge 2600 positioned therebetween. The staple cartridge 2600 can comprise a compressible, implantable cartridge body 2610 including an inner layer 2612, an outer layer 2611, and a plurality of staples, such as staples 2220a and 2200b, for example, positioned therein. The anvil 2640 can comprise a plurality of staple forming pockets 2642 in surface 2641 and the staple cartridge channel 2530 can comprise a plurality of staple forming slots 2532 defined in the support surface 2531. As illustrated in FIG. 51, the anvil surface 2641 can be parallel, or at least substantially parallel, to the cartridge support surface 2531 wherein each forming pocket 2642 can be positioned an equal, or at least substantially equal, distance away from an opposing and corresponding staple support slot 2532. The staple cartridge 2600 can comprise staples having the same, or at least substantially the same, initial, unformed staple height and, in addition, the same, or at least substantially the same, formed staple height. Alternatively, the outer rows of staples can comprise staples 2220a and the inner rows of staples can comprise staples 2220b wherein, as discussed above, the staples 2220a and 2220b can have different unformed staple heights. When the anvil 2640 is moved toward the staple cartridge 2600 into a closed position, the staples 2220a and 2220b can be formed such that they have the same, or at least substantially the same, formed staple height. For example, as a result of the above, the formed outer staples 2220a and the inner staples 2220b may have the same, or at least substantially the same, amount of compressible cartridge body 2610 contained therein; however, as the outer staples 2220a have a taller unformed staple height than the inner staples 2220b and may have the same formed staple height nonetheless, a greater clamping pressure can be generated in the outer staples 2220a than the inner staples 2220b, for example.

[0651] Referring now to FIG. 52, an end effector of a surgical stapler can comprise an anvil 2740, a staple cartridge channel 2530, and a staple cartridge 2700 positioned within the staple cartridge channel 2530. Similar to the above, the staple cartridge 2700 can comprise a compressible, implantable cartridge body 2710 comprising an inner layer 2712, an outer layer 2711, and a plurality of staples, such as staples 2220a and 2220b, for example, positioned therein. The thickness of the cartridge body 2710 can vary across its width. For example, the cartridge body 2710 can comprise a center portion 2708 and side portions 2709, wherein the

center portion 2708 can comprise a thickness which is greater than the thickness of the side portions 2709. The thickest portion of the cartridge body 2710 can be located at the center portion 2708 while the thinnest portion of the cartridge body 2710 can be located at the side portions 2709. For example, the thickness of the cartridge body 2710 can decrease gradually between the center portion 2708 and the side portions 2709. The thickness of the cartridge body 2710 can decrease linearly and/or geometrically between the center portion 2708 and the side portions 2709. For example, the tissue-contacting surface 2719 of cartridge body 2710 can comprise two inclined, or angled, surfaces which slope downwardly from the center portion 2708 toward the side portions 2709. The anvil 2740 can comprise two inclined, or angled, surfaces which parallel, or at least substantially parallel, the inclined tissue-contacting surfaces 2719. The anvil 2740 can further comprise at least one piece of buttress material 2760 attached to the inclined surfaces of the anvil 2740.

[0652] Further to the above, the inner rows of staples in the staple cartridge 2700 can comprise the taller staples 2220a and the outer rows of staples can comprise the shorter staples 2220b. The taller staples 2220a can be positioned within and/or adjacent to the thicker center portion 2708 while the staples 2220b can be positioned within and/or adjacent to the side portions 2709. For example, as a result of the above, the taller staples 2220a can capture more material of the implantable cartridge body 2710 than the shorter staples 2220b. Such circumstances could result in the staples 2220a applying a greater clamping pressure to the tissue T than the staples 2220b. Even though the taller staples 2220a may capture more material of the cartridge body 2710 therein than the shorter staples 2220b, the taller staples 2220a may have a taller formed staple height than the shorter staples 2220b owing to the inclined arrangement of the staple forming pockets 2742a and 2742b. Such considerations can be utilized to achieve a desired clamping pressure within the tissue captured by the staples 2220a and 2220b wherein, as a result, the clamping pressure in the staples 2220a can be greater than, less than, or equal to the clamping pressure applied to the tissue by the staples 2220b, for example. In various alternative embodiments to the end effector illustrated in FIG. 52, the shorter staples 2220b can be positioned within and/or adjacent to the thicker center portion 2708 of the cartridge body 2710 and the taller staples 2220a can be positioned within and/or adjacent to the thinner side portions 2709. Furthermore, although the staple cartridge 2700 is depicted as comprising inner and outer rows of staples, the staple cartridge 2700 may comprise additional rows of staples, such as staple

rows positioned intermediate the inner and outer rows of staples, for example. For example, the intermediate staple rows can comprise staples having an unformed staple height which is intermediate the unformed staple heights of the staples 2220a and 2220b and a formed staple height which is intermediate the formed staple heights of the staples 2220a and 2220b, for example.

[0653] Referring now to FIG. 53, an end effector of a surgical stapler can comprise an anvil 2840, a staple cartridge channel 2530, and a staple cartridge 2800 positioned within the staple cartridge channel 2530. Similar to the above, the staple cartridge 2800 can comprise a compressible, implantable cartridge body 2810 comprising an inner layer 2812, an outer layer 2811, and a plurality of staples, such as staples 2220a and 2220b, for example, positioned therein. The thickness of the cartridge body 2810 can vary across its width. For example, the cartridge body 2810 can comprise a center portion 2808 and side portions 2809, wherein the center portion 2808 can comprise a thickness which is less than the thickness of the side portions 2809. The thinnest portion of the cartridge body 2810 can be located at the center portion 2808 while the thickest portion of the cartridge body 2810 can be located at the side portions 2809. For example, the thickness of the cartridge body 2810 can increase gradually between the center portion 2808 and the side portions 2809. The thickness of the cartridge body 2810 can increase linearly and/or geometrically between the center portion 2808 and the side portions 2809. For example, the tissue-contacting surface 2819 of cartridge body 2810 can comprise two inclined, or angled, surfaces which slope upwardly from the center portion 2808 toward the side portions 2809. The anvil 2840 can comprise two inclined, or angled, surfaces which parallel, or at least substantially parallel, the inclined tissue-contacting surfaces 2819. The anvil 2840 can further comprise at least one piece of buttress material 2860 attached to the inclined surfaces of the anvil 2840. Further to the above, the outer rows of staples in the staple cartridge 2800 can comprise the taller staples 2220a and the inner rows of staples can comprise the shorter staples 2220b. The taller staples 2220a can be positioned within and/or adjacent to the thicker side portions 2809 while the staples 2220b can be positioned within and/or adjacent to the center portion 2808. For example, as a result of the above, the taller staples 2220a can capture more material of the implantable cartridge body 2810 than the shorter staples 2220b.

[0654] As described above with regard to the embodiment of FIG. 46, for example, the staple cartridge channel 2230 can comprise a stepped support surface 2231 which can be configured to

support the staples 2220a and 2220b at different heights with respect the anvil 2240. The staple cartridge channel 2230 can be comprised of metal and the steps in the support surface 2231 may be formed in the support surface 2231 by a grinding operation, for example. Referring now to FIG. 54, an end effector of a surgical instrument can comprise a staple cartridge channel 2930 comprising a support insert 2935 positioned therein. More particularly, the staple cartridge channel 2930 can be formed such that it has a flat, or at least substantially flat, support surface 2931, for example, which can be configured to support the insert 2935 which comprises the stepped surfaces for supporting the staples 2220a and 2220b of the staple cartridge 2200 at different heights. For example, the insert 2935 can comprise a flat, or at least substantially flat, bottom surface which can be positioned against the support surface 2931. The insert 2935 can further comprise support slots, grooves, or troughs 2932a and 2932b which can be configured to support the staples 2220a and 2220b, respectively, at different heights. Similar to the above, the insert 2935 can comprise a knife slot 2939 defined therein which can be configured to permit a cutting member to pass therethrough. The staple cartridge channel 2930 can be comprised of the same material as or a different material than the support insert 2935. The staple cartridge channel 2930 and the support insert 2935 can both be comprised of metal, for example, while, as an alternative, the staple cartridge channel 2930 can be comprised of metal, for example, and the support insert 2935 can be comprised of plastic, for example. The support insert 2935 can be fastened and/or welded into the staple cartridge channel 2930. The support insert 2935 can be snap-fit and/or press-fit into the staple cartridge channel 2930. The support insert 2935 can be secured in the staple cartridge channel 2930 using an adhesive.

[0655] Referring now to FIG. 55, an end effector of a surgical stapler can comprise an anvil 3040, a staple cartridge channel 3030, and a compressible, implantable staple cartridge 3000 positioned in the staple cartridge channel 3030. Similar to the above, the anvil 3040 can comprise a plurality of staple-forming pockets 3042 defined therein and a knife slot 3049 which can be configured to slidably receive a cutting member therein. Also similar to the above, the staple cartridge channel 3030 can comprise a plurality of staple support slots 3032 defined therein and a knife slot 3039 which can also be configured to slidably receive a cutting member therein. The staple cartridge 3000 can comprise a first layer 3011, a second layer 3012, and a plurality of staples, such as staples 3020a and 3020b, for example, positioned therein. The staples 3020a can comprise an unformed staple height which is taller than the unformed staple height of

the staples 3020b. The first layer 3011 can be comprised of a first compressible material and the second layer 3012 can be comprised of a second compressible material. The first compressible material can be compressed at a rate which is higher than the second compressible material while, alternatively, the first compressible material can be compressed at a rate which is lower than the second compressible material. The first compressible material can be comprised of a resilient material which can comprise a first spring rate and the second compressible material can be comprised of a resilient material which can comprise a second spring rate which is different than the first spring rate. The first compressible material can comprise a spring rate which is greater than the spring rate of the second compressible material. Alternatively, the first compressible material can comprise a spring rate which is less than the spring rate of the second compressible material. The first compressible layer can comprise a first stiffness and the second compressible layer can comprise a second stiffness, wherein the first stiffness is different than the second stiffness. The first compressible layer can comprise a stiffness which is greater than the stiffness of the second compressible layer. Alternatively, the first compressible layer can comprise a stiffness which is less than the stiffness of the second compressible layer.

[0656] Referring again to FIG. 55, the second layer 3012 of the staple cartridge 3000 can comprise a constant, or at least substantially constant, thickness across the width thereof. The first layer 3011 can comprise a thickness which varies across the width thereof. For example, the first layer 3011 can comprise one or more steps 3008 which can increase the thickness of the cartridge body 3010 in certain portions of the cartridge body 3010, such as the center portion, for example. Referring again to FIG. 55, the shorter staples 3020b can be positioned in or aligned with the steps 3008, i.e., the thicker portions of the cartridge body 3010, and the taller staples 3020a can be positioned in or aligned with the thinner portions of the cartridge body 3010. As a result of the thicker and thinner portions of the cartridge body 3010, the stiffness of the cartridge body 3010 can be greater along the inner rows of staples 3020b than the outer rows of staples 3020a. The first layer 3011 can be connected to the second layer 3012. For example, the first layer 3011 and the second layer 3012 can comprise interlocking features which can retain the layers 3011 and 3012 together. The first layer 3011 can comprise a first laminate and the second layer 3012 can comprise a second laminate, wherein the first laminate can be adhered to the second laminate by one or more adhesives. The staple cartridge 3000 can comprise a knife slot 3003 which can be configured to slidably receive a cutting member therein.

[0657] Referring now to FIG. 56, a staple cartridge 3100 can comprise a compressible, implantable cartridge body 3110 comprising a single layer of compressible material and, in addition, a plurality of staples, such as staples 3020b, for example, positioned therein. The thickness of the cartridge body 3110 can vary across the width thereof. For example, the cartridge body 3110 can comprise steps 3108 extending along the side portions thereof. Referring now to FIG. 57, a staple cartridge 3200 can comprise a compressible, implantable cartridge body 3210 comprising a single layer of compressible material and, in addition, a plurality of staples, such as staples 3020b, for example, positioned therein. The thickness of the cartridge body 3210 can vary across the width thereof. For example, the cartridge body 3210 can comprise steps 3208 extending along the center portion thereof. Referring now to FIG. 58, a staple cartridge 3300 can comprise a compressible, implantable cartridge body 3310 wherein, similar to the above, the thickness of the cartridge body 3310 can vary across the width thereof. The thickness of the cartridge body 3310 can increase geometrically between the side portions and the center portion of the cartridge body 3310. For example, the thickness of the cartridge body 3310 can be defined by an arcuate or curved profile and can comprise an arcuate or curved tissue-contacting surface 3319. The thickness of the cartridge body 3310, and the contour of the tissue-contacting surface 3319, can be defined by one radius of curvature or, alternatively, by several radiuses of curvature, for example. Referring now to FIG. 59, a staple cartridge 3400 can comprise a compressible, implantable cartridge body 3410 wherein the thickness of the cartridge body 3410 can increase linearly, or at least substantially linearly, between the side portions and the center portion of the cartridge body 3410.

[0658] Referring now to FIG. 60, a staple cartridge 3500 can comprise a compressible, implantable cartridge body 3510 and a plurality of staples 3520 positioned therein. The implantable cartridge body 3510 can comprise a first inner layer 3512, a second inner layer 3513, and an outer layer 3511. The first inner layer 3512 can comprise a first thickness and the second inner layer 3513 can comprise a second thickness wherein the second inner layer 3513 can be thicker than the first inner layer 3512. Alternatively, the first inner layer 3512 can be thicker than the second inner layer 3513. In another alternative, the first inner layer 3512 can have the same, or at least substantially the same, thickness as the second inner layer 3513. Each staple 3520 can comprise a base 3522 and one or more deformable legs 3521 extending from the base 3522. Each leg 3521 can comprise a tip 3523 which is embedded in the first inner layer 3511 and, in

addition, each base 3522 of the staples 3520 can be embedded in the second inner layer 3512. The first inner layer 3512 and/or the second inner layer 3513 can comprise at least one medicament stored therein and the outer layer 3511 can encapsulate and seal the first inner layer 3512 and the second inner layer 3513 such that the medicament does not flow out of the staple cartridge body 3510 until after the outer layer 3511 has been punctured by the staples 3520. More particularly, further to the above, an anvil can be pushed downwardly against tissue positioned against the tissue-contacting surface 3519 of staple cartridge 3500 such that the cartridge body 3510 is compressed and the surface 3519 is moved downwardly toward, and at least partially below, the staple tips 3523 such that the tips 3523 rupture or puncture the outer layer 3511. After the outer layer 3511 has been breached by the staple legs 3521, the at least one medicament M can flow out of the cartridge body 3510 around the staple legs 3521. In various circumstances, additional compression of the cartridge body 3510 can squeeze additional medicament M out of the cartridge body 3510 as illustrated in FIG. 61.

[0659] referring again to FIG. 60, the outer layer 3511 can comprise a water impermeable, or at least substantially impermeable, wrap which can configured to, one, keep the medicament from prematurely flowing out of the staple cartridge 3500 and, two, prevent fluids within a surgical site, for example, from prematurely entering into the staple cartridge 3500. The first inner layer 3512 can comprise a first medicament stored, or absorbed, therein and the second inner layer 3513 can comprise a second medicament stored, or absorbed, therein, wherein the second medicament can be different than the first medicament. An initial compression of the cartridge body 3510, which causes the rupture of the outer layer 3511, can generally express the first medicament out of the first inner layer 3512 and a subsequent compression of the cartridge body 3510 can generally express the second medicament out of the second inner layer 3513. In such cases, however, portions of the first medicament and the second medicament may be expressed simultaneously although a majority of the medicament that is initially expressed can be comprised of the first medicament and a majority of the medicament subsequently expressed thereafter can be comprised of the second medicament. Further to the above, the first inner layer 3512 can be comprised of a more compressible material than the second inner layer 3513 such that the initial compression forces or pressure, which can be lower than the subsequent compression forces or pressure, can cause a larger initial deflection within the first inner layer 3512 than the second inner layer 3513. This larger initial deflection within the first inner layer

3512 can cause a larger portion of the first medicament to be expressed from the first inner layer 3512 than the second medicament from the second inner layer 3513. The first inner layer 3512 can be more porous and/or more flexible than the second inner layer 3513. For example, the first inner layer 3512 can comprise a plurality of pores, or voids, 3508 defined therein and the second inner layer 3513 can comprise a plurality of pores, or voids, 3509 defined therein wherein the pores 3508 can be configured to store the first medicament in the first inner layer 3512 and the pores 3509 can be configured to store the second medicament in the second inner layer 3513. The size and density of the pores 3508 within the first inner layer 3512 and the pores 3509 within the second inner layer 3513 can be selected so as to provide a desired result described herein.

[0660] Referring again to FIGS. 60 and 61, the outer layer 3511, the first inner layer 3512, and/or the second inner layer 3513 can be comprised of a bioabsorbable material. The first inner layer 3512 can be comprised of a first bioabsorbable material, the second inner layer 3513 can be comprised of a second bioabsorbable material, and the outer layer 3511 can be comprised of a third bioabsorbable material, wherein the first bioabsorbable material, the second bioabsorbable material, and/or the third bioabsorbable material can be comprised of different materials. The first bioabsorbable material can be bioabsorbed at a first rate, the second bioabsorbable material can be bioabsorbed at a second rate, and the third bioabsorbable material can be bioabsorbed at a third rate, wherein the first rate, the second rate, and/or the third rate can be different. For example, when a material is bioabsorbed at a particular rate, such a rate can be defined as the amount of material mass that is absorbed by a patient's body over a unit of time. As it is known, the bodies of different patients may absorb different materials at different rates and, thus, such rates may be expressed as average rates in order to account for such variability. In any event, a faster rate may be a rate in which more mass is bioabsorbed for a unit of time than a slower rate. Referring again to FIGS. 60 and 61, the first inner layer 3512 and/or the second inner layer 3513 can be comprised of a material which bioabsorbs faster than the material comprising the outer layer 3511. For example, the first inner layer 3512 and/or the second inner layer 3513 can be comprised of a bioabsorbable foam, tissue sealant, and/or haemostatic material, such as oxidized regenerated cellulose (ORC), for example, and the outer layer 3511 can be comprised of a buttress material and/or plastic material, such as polyglycolic acid (PGA) which is marketed under the trade name Vicryl, polylactic acid (PLA or PLLA), polydioxanone (PDS), polyhydroxyalkanoate (PHA), poliglecaprone 25 (PGCL) which is marketed under the trade

name Monocryl, polycaprolactone (PCL), and/or a composite of PGA, PLA, PDS, PHA, PGCL and/or PCL, for example. In such cases, the first inner layer 3512 and/or the second inner layer 3513 can immediately treat the tissue and can reduce bleeding from the tissue, for example, wherein the outer layer 3514 can provide longer-term structural support and can be bioabsorbed at a slower rate.

[0661] Owing to the slower rate of bioabsorbability of the outer layer 3511, further to the above, the outer layer 3511 can buttress or structurally reinforce the tissue within the staple line as it heals. One of the first inner layer 3512 and the second inner layer 3513 can be comprised of a material which can be bioabsorbed faster than the other such that, one of the layers can provide an initial release of a therapeutic material and the other layer can provide a sustained release of the same therapeutic material and/or a different therapeutic material. For example, the rate in which a therapeutic material can be released from a layer 3512, 3513 can be a function of the bioabsorbability of the substrate layer in which the medicament is absorbed or dispersed. For example, the substrate comprising the first inner layer 3512 can be bioabsorbed faster than the substrate comprising the second inner layer 3513 and, as a result, a medicament can be release from the first inner layer 3512 faster than the second inner layer 3513, for example. As described herein, one or more of the layers 3511, 3512, and 3513 of the cartridge body 3510 can be adhered to one another by at least one adhesive, such as fibrin and/or protein hydrogel, for example. The adhesive can be water soluble and can be configured to release the connection between the layers as the staple cartridge 3500 is being implanted and/or some time thereafter. For example, the adhesive can be configured to bioabsorb faster than the outer layer 3511, the first inner layer 3512, and/or the second inner layer 3513.

[0662] Referring now to FIGS. 62 and 63, a staple cartridge, such as staple cartridge 3600, for example, can comprise a cartridge body 3610 including a compressible first layer 3611, a second layer 3612 attached to the first layer 3611, and a removable compressible layer 3613 attached to the second layer 3612. For example, the first layer 3611 can be comprised of a compressible foam material, the second layer 3612 can comprise a laminate material adhered to the first layer 3611 utilizing one or more adhesives, and the third layer 3613 can comprise a compressible foam material removably adhered to the second layer 3612 utilizing one or more adhesives, for example. The staple cartridge 3600 can further comprise a plurality of staples, such as staples 3620, for example, positioned in the cartridge body 3610. For example, each staple 3620 can

comprise a base 3622 positioned in the third layer 3613 and one or more deformable legs 3621 extending upwardly from the base 3622 through the second layer 3612 and into the first layer 3611, for example. In use, further to the above, the top surface 3619 of the staple cartridge body 3610 can be pushed downwardly by an anvil until the staple legs 3621 penetrate through the top surface 3619 and the targeted tissue and contact the anvil. After the staple legs 3621 have been sufficiently deformed, the anvil can be moved away from the staple cartridge 3600 such that the compressible layers thereof can at least partially re-expand. In various circumstances, the insertion of the staples through the tissue can cause the tissue to bleed. The third layer 3613 can be comprised of an absorbent material, such as protein hydrogel, for example, which can draw blood away from the stapled tissue. In addition to or in lieu of the above, the third layer 3613 can be comprised of a haemostatic material and/or tissue sealant, such as freeze-dried thrombin and/or fibrin, for example, which can be configured to reduce the bleeding from the tissue. The third layer 3613 may provide a structural support to the first layer 3611 and the second layer 3612 wherein the third layer 3613 may be comprised of a bioabsorbable material and/or a non-bioabsorbable material. In any event, the third layer 3613 can be detached from the second layer 3612 after the staple cartridge 3610 has been implanted. Where the third layer 3613 comprises an implantable-quality material, the surgeon can elect whether to remove the third layer 3613 of the cartridge body 3610. The third layer 3613 can be configured to be removed from the second layer 3612 in one piece.

[0663] The first layer 3611 can be comprised of a first foam material and the third layer 3613 can be comprised of a second foam material which can be different than the first foam material. The first foam material can have a first density and the second foam material can have a second density wherein the first density can be different than the second density. For example, the second density can be higher than the first density wherein, as a result, the third layer 3613 may be less compressible, or have a lower compression rate, than the first layer 3611. Alternatively, the first density can be higher than the second density wherein, as a result, the first layer 3611 may be less compressible, or have a lower compression rate, than the third layer 3613. Referring now to FIGS. 64 and 65, a staple cartridge 3700, similar to the staple cartridge 3600, can comprise a cartridge body 3710 comprising a first compressible foam layer 3711, a second layer 3712 attached to the first layer 3711, and a detachable third compressible foam layer 3713 removably attached to the second layer 3712. For example, the third layer 3713 can comprise a

plurality of staple receiving slots, or cut-outs, 3709 which can each be configured to receive at least a portion of a staple 3620, such as a staple base 3622, for example, therein. The staples 3620 can be configured to slide within the staple receiving slots 3709 or, stated another way, the third layer 3713 can be configured to slide relative to the staples 3620 when the staple cartridge 3700 is positioned against the targeted tissue and compressed by an anvil, for example. The receiving slots 3709 can be configured such that there is clearance between the staples 3620 and the side walls of the receiving slots 3709. For example, as a result of the above, the staples 3620 may not capture a portion of the third layer 3713 therein when the staples 3620 are deformed, as illustrated in FIGS. 64 and 65. Alternatively, the ends of the staple receiving slots 3709 adjacent to the second layer 3712 can be closed by a portion of the third layer 3713 and, as a result, at least a portion of the third layer 3713 can be captured within the staples 3620 when they are deformed. In any event, the third layer 3713 can comprise one or more perforations and/or score marks 3708, for example, which can be configured to permit the third layer 3713 to be removed from the second layer 3712 in two or more pieces as illustrated in FIG. 64. In FIG. 64, one of the pieces of the third layer 3713 is illustrated as being removed by a tool 3755. The perforations 3708 can be arranged along a line positioned intermediate a first row of staples and a second row of staples.

[0664] Referring again to FIGS. 64 and 65, the bases 3622 of the staples 3620 can be positioned within the receiving slots 3709 wherein, the side walls of the receiving slots 3709 can be configured to contact and releasable retain the staple legs 3621 in position. Although not illustrated, the third layer 3713 can comprise an elongated slot surrounding all of the staples within a staple line. For example, a staple cartridge comprising four staple rows, for example, can comprise an elongate slot aligned with each staple row in the bottom layer of the staple cartridge. Further to the above, at least a portion of the staple cartridge 3600 and/or the staple cartridge 3700 can be implanted within a patient and at least a portion of the staple cartridge can be removable from the patient. Referring again to FIGS. 64 and 65, the first layer 3711 and the second layer 3712 can be captured within the staples 3620 and can be implanted with the staples 3620, whereas the third layer 3713 can be optionally removed or detached from the staple cartridge 3700. In various circumstances, the removal of a portion of the implanted staple cartridge can reduce the amount of material that the patient's body has to reabsorb which can provide various therapeutic benefits. In the event that a portion of a staple cartridge is detached

and removed, such as by a laparoscopic tool 3755, for example, the detached staple cartridge portion can be removed from the surgical site through a trocar, such as a trocar having a 5 mm aperture, for example. A cartridge body can comprise more than one layer that can be removed. For example, the cartridge body 3710 can comprise a fourth layer wherein the third layer of 3713 of the cartridge body 3710 can be comprised of a haemostatic material and the fourth layer can be comprised of a support layer. For example, a surgeon can remove the support layer and then elect whether to remove the haemostatic layer, for example.

[0665] Referring now to FIG. 66, a staple cartridge, such as staple cartridge 3800, for example, can comprise a cartridge body 3810 including an outer layer 3811 and an inner layer 3812. The inner layer 3812 can be comprised of a compressible foam material and the outer layer 3811 can be at least partially wrapped around the inner layer 3812. The outer layer 3811 can comprise a first portion 3811a configured to be positioned on a first side of the inner layer 3812 and a second portion 3811b configured to be positioned on a second side of the inner layer 3812 wherein the first portion 3811a and the second portion 3811b can be connected by a flexible hinge, such as hinge 3809, for example. For example, at least one adhesive, such as fibrin and/or protein hydrogel, for example, can be applied to the first side and/or the second side of the inner layer 3812 in order to secure the portions of the outer layer 3811 thereto. The outer layer 3811 can comprise one or more fastening members extending therefrom. For example, the outer layer 3811 can comprise a plurality of deformable legs 3821 extending from one side of the outer layer 3811 which can be seated in the compressible inner layer 3812. For example, the legs 3821 may not protrude from the second side of the inner layer 3812 or , alternatively, the legs 3821 may at least partially protrude from the inner layer 3812. When the compressible cartridge body 3810 is compressed, in use, the legs 3821 can be configured to pierce the inner layer 3812 and the second portion 3811b of the outer layer 3811. The second portion 3811b of the outer layer 3811 can comprise apertures, such as apertures 3808, for example defined therein which can be configured to receive the staple legs 3821. At least portions of the staple cartridge 3800 can comprise a knife slot 3803 which can be configured to slidably receive a cutting member therein. For example, the knife slot 3803 may not extend entirely through the thickness of the cartridge body 3810 and, as a result, the cutting member may incise the cartridge body 3810 as it is moved relative thereto.

[0666] Referring now to FIG. 67, a staple cartridge 3900 can comprise, similar to staple cartridge 3800, a cartridge body 3910 including an inner layer 3812 and an outer layer 3811, wherein the outer layer 3811 can comprise a first portion 3811a positioned adjacent to the first side of the inner layer 3812 and a second portion 3811b positioned adjacent to the second side of the inner layer 3812. Similar to the above, the outer layer 3811 can comprise one or more fastening members extending therefrom. For example, the outer layer 3811 can comprise a plurality of deformable legs 3921 extending from one side of the outer layer 3811 which can be seated in the compressible inner layer 3812. Each deformable leg 3921 can comprise at least one hook or barb 3923 protruding therefrom which can be configured to engage the second portion 3811b of the outer layer 3811 and, as a result, retain the outer layer 3811 to the inner layer 3812. For example, the barbs 3923 can be configured to protrude from the second side of the inner layer 3812 and extend through the apertures 3808 in the second portion 3811b of the outer layer 3811 such that the barbs 3923 can engage the outside surface of the outer layer 3811 and lock the outer layer 3811 to the inner layer 3812. In order to construct the staple cartridge 3900, the inner layer 3812 may be at least partially compressed in order to cause the barbs to protrude therefrom and enter into the apertures 3808. For example, the staple cartridge 3900 can be at least partially pre-compressed when it is inserted into a staple cartridge, for example. Further to the above, at least a portion of the legs 3921 can be embedded within the first portion 3811a of the outer layer 3811 wherein, the outer layer 3811 can be comprised of a plastic material, such as polydioxanone (PDS) and/or polyglycolic acid (PGA), for example, and the plastic material can be overmolded around at least a portion of the legs 3921.

[0667] Referring now to FIGS. 68-72, a staple cartridge, such as staple cartridge 4000, for example, can comprise a cartridge body 4010 including a compressible first layer 4011 and a second layer 4012 and, in addition, a plurality of staples 4020 positioned within the cartridge body 4010. Referring to FIG. 70, each staple 4020 can comprise a base 4022 and at least one deformable leg 4023 extending from the base 4022. Referring to FIG. 68, the staple cartridge 4000 can be positioned between a staple cartridge channel 4030 and an anvil 4040 of an end effector of a surgical stapler wherein the second layer 4012 of the cartridge body 4010 and/or the bases 4022 of the staples 4020 can be positioned against the staple cartridge channel 4030. Referring now to FIG. 69, the second layer 4012 can comprise a layer of pledgets 4060 interconnected to one another by a pledget support frame 4061. For example, the pledgets 4060

and the pledget support frame 4061 can be comprised of a molded plastic material, such as polyglycolic acid (PGA), for example. Each pledget 4060 can comprise one or more apertures or slots 4062 which can be configured to receive a staple leg 4021 extending therethrough as illustrated in FIGS. 70 and 71. Each pledget 4060 can further comprise a receiving slot 4063 defined therein which can be configured to receive a base 4022 of a staple 4020. Referring again to FIG. 69, the pledgets 4060 and/or pledget support fame 4061 can comprise a plurality of score marks, perforations, or the like which can be configured to allow the pledgets 4060 to become detached from the pledget support frame 4061 at a desired location. Similarly, referring to FIG. 71, one or more pledgets 4060 can be connected to one another along a line comprising perforations and/or score marks 4064, for example. In use, the compressible foam layer 4011 can be positioned against the targeted tissue T and the cartridge body 4010 can be compressed by the anvil 4040 such that the anvil 4040 can deform the staples 4020. When the staples 4020 are deformed, the staple legs 4021 of each staple 4020 can capture the tissue T, a portion of the first layer 4011, and a pledget 4060 within the deformed staple. When the staple cartridge channel 4030 is moved away from the implanted staple cartridge 4060, for example, the pledget support frame 4061 can be detached from the pledgets 4060 and/or the pledgets 4060 can be detached from one another. In certain circumstances, the pledgets 4060 can be detached from the frame 4061 and/or each other when the staples 4020 are being deformed by the anvil 4040 as described above.

[0668] The staples of a staple cartridge can be fully formed by an anvil when the anvil is moved into a closed position. Alternatively, referring now to FIGS. 73-76, the staples of a staple cartridge, such as staple cartridge 4100, for example, can be deformed by an anvil when the anvil is moved into a closed position and, in addition, by a staple driver system which moves the staples toward the closed anvil. The staple cartridge 4100 can comprise a compressible cartridge body 4110 which can be comprised of a foam material, for example, and a plurality of staples 4120 at least partially positioned within the compressible cartridge body 4110. The staple driver system can comprise a driver holder 4160, a plurality of staple drivers 4162 positioned within the driver holder 4160, and a staple cartridge pan 4180 which can be configured to retain the staple drivers 4162 in the driver holder 4160. For example, the staple drivers 4162 can be positioned within one or more slots 4163 in the driver holder 4160 wherein the sidewalls of the slots 4163 can assist in guiding the staple drivers 4162 upwardly toward the anvil. The staples 4120 can be

supported within the slots 4163 by the staple drivers 4162 wherein, the staples 4120 can be entirely positioned in the slots 4163 when the staples 4120 and the staple drivers 4162 are in their unfired positions. Alternatively, at least a portion of the staples 4120 can extend upwardly through the open ends 4161 of slots 4163 when the staples 4120 and staple drivers 4162 are in their unfired positions. For example, referring primarily now to FIG. 74, the bases of the staples 4120 can be positioned within the driver holder 4160 and the tips of the staples 4120 can be embedded within the compressible cartridge body 4110. Approximately one-third of the height of the staples 4120 can be positioned within the driver holder 4160 and approximately two-thirds of the height of the staples 4120 can be positioned within the cartridge body 4110. Referring to FIG. 73A, the staple cartridge 4100 can further comprise a water impermeable wrap or membrane 4111 surrounding the cartridge body 4110 and the driver holder 4160, for example.

[0669] In use, the staple cartridge 4100 can be positioned within a staple cartridge channel, for example, and the anvil can be moved toward the staple cartridge 4100 into a closed position. The anvil can contact and compress the compressible cartridge body 4110 when the anvil is moved into its closed position. The anvil may not contact the staples 4120 when the anvil is in its closed position. Alternatively, the anvil may contact the legs of the staples 4120 and at least partially deform the staples 4120 when the anvil is moved into its closed position. In either event, the staple cartridge 4100 can further comprise one or more sleds 4170 which can be advanced longitudinally within the staple cartridge 4100 such that the sleds 4170 can sequentially engage the staple drivers 4162 and move the staple drivers 4162 and the staples 4120 toward the anvil. The sleds 4170 can slide between the staple cartridge pan 4180 and the staple drivers 4162. Where the closure of the anvil has started the forming process of the staples 4120, the upward movement of the staples 4120 toward the anvil can complete the forming process and deform the staples 4120 to their fully formed, or at least desired, height. Where the closure of the anvil has not deformed the staples 4120, the upward movement of the staples 4120 toward the anvil can initiate and complete the forming process and deform the staples 4120 to their fully formed, or at least desired, height. The sleds 4170 can be advanced from a proximal end of the staple cartridge 4100 to a distal end of the staple cartridge 4100 such that the staples 4120 positioned in the proximal end of the staple cartridge 4100 are fully formed before the staples 4120 positioned in the distal end of the staple cartridge 4100 are fully formed. Referring to FIG. 75, the sleds 4170

can each comprise at least one angled or inclined surface 4711 which can be configured to slide underneath the staple drivers 4162 and lift the staple drivers 4162 as illustrated in FIG. 76.

[0670] Further to the above, the staples 4120 can be formed in order to capture at least a portion of the tissue T and at least a portion of the compressible cartridge body 4110 of the staple cartridge 4100 therein. After the staples 4120 have been formed, the anvil and the staple cartridge channel 4130 of the surgical stapler can be moved away from the implanted staple cartridge 4100. In various circumstances, the cartridge pan 4180 can be fixedly engaged with the staple cartridge channel 4130 wherein, as a result, the cartridge pan 4180 can become detached from the compressible cartridge body 4110 as the staple cartridge channel 4130 is pulled away from the implanted cartridge body 4110. Referring again to FIG. 73, the cartridge pan 4180 can comprise opposing side walls 4181 between which the cartridge body 4110 can be removably positioned. For example, the compressible cartridge body 4110 can be compressed between the side walls 4181 such that the cartridge body 4110 can be removably retained therebetween during use and releasably disengaged from the cartridge pan 4180 as the cartridge pan 4180 is pulled away. For example, the driver holder 4160 can be connected to the cartridge pan 4180 such that the driver holder 4160, the drivers 4162, and/or the sleds 4170 can remain in the cartridge pan 4180 when the cartridge pan 4180 is removed from the surgical site. Alternatively, the drivers 4162 can be ejected from the driver holder 4160 and left within the surgical site. For example, the drivers 4162 can be comprised of a bioabsorbable material, such as polyglycolic acid (PGA) which is marketed under the trade name Vicryl, polylactic acid (PLA or PLLA), polydioxanone (PDS), polyhydroxyalkanoate (PHA), poliglecaprone 25 (PGCL) which is marketed under the trade name Monocryl, polycaprolactone (PCL), and/or a composite of PGA, PLA, PDS, PHA, PGCL and/or PCL, for example. The drivers 4162 can be attached to the staples 4120 such that the drivers 4162 are deployed with the staples 4120. For example, each driver 4162 can comprise a trough configured to receive the bases of the staples 4120, for example, wherein, the troughs can be configured to receive the staple bases in a press-fit and/or snap-fit manner.

[0671] Further to the above, the driver holder 4160 and/or the sleds 4170 can be ejected from the cartridge pan 4180. For example, the sleds 4170 can slide between the cartridge pan 4180 and the driver holder 4160 such that, as the sleds 4170 are advanced in order to drive the staple drivers 4162 and staples 4120 upwardly, the sleds 4170 can move the driver holder 4160 upwardly out

of the cartridge pan 4180 as well. For example, the driver holder 4160 and/or the sleds 4170 can be comprised of a bioabsorbable material, such as polyglycolic acid (PGA) which is marketed under the trade name Vicryl, polylactic acid (PLA or PLLA), polydioxanone (PDS), polyhydroxyalkanoate (PHA), poliglecaprone 25 (PGCL) which is marketed under the trade name Monocryl, polycaprolactone (PCL), and/or a composite of PGA, PLA, PDS, PHA, PGCL and/or PCL, for example. The sleds 4170 can be integrally formed and/or attached to a drive bar, or cutting member, which pushes the sleds 4170 through the staple cartridge 4100. In such cases, the sleds 4170 may not be ejected from the cartridge pan 4180 and may remain with the surgical stapler while, in other embodiments in which the sleds 4170 are not attached to the drive bar, the sleds 4170 may be left in the surgical site. In any event, further to the above, the compressibility of the cartridge body 4110 can allow thicker staple cartridges to be used within an end effector of a surgical stapler as the cartridge body 4110 can compress, or shrink, when the anvil of the stapler is closed. As a result of the staples being at least partially deformed upon the closure of the anvil, taller staples, such as staples having an approximately 0.18" staple height, for example, could be used, wherein approximately 0.12" of the staple height can be positioned within the compressible layer 4110 and wherein the compressible layer 4110 can have an uncompressed height of approximately 0.14", for example.

[0672] Referring now to FIGS. 77-80, a staple cartridge, such as staple cartridge 4200, for example, can comprise a compressible cartridge body 4210, a plurality of staples 4220 positioned therein, and a plurality of flexible lateral support members 4234. Referring now to FIG. 78, the staple cartridge 4200 can be positioned intermediate an anvil 4240 and a staple cartridge channel 4230 wherein, the lateral support members 4234 can be attached to the staple cartridge channel 4230. When the anvil 4240 is moved downwardly to compress the cartridge body 4210 and at least partially deform the staples 4220, as illustrated in FIG. 79, the side portions of the cartridge body 4210 can bulge laterally and push the lateral support members 4234 outwardly. For example, the lateral support members 4234 can be attached to the cartridge body 4210 and, when the cartridge body 4210 bulges laterally as described above, the lateral support members 4234 can detach from the cartridge body 4210 as illustrated in FIG. 79. The lateral support members 4234 can be adhered to the cartridge body 4210 utilizing at least one adhesive, such as fibrin and/or protein hydrogel, for example. Similar to the above, the closing of the anvil 4240 may only partially deform the staples 4220, wherein the formation of the staples

4220 can be completed by the advancement of one or more sleds 4270 through the staple cartridge 4200 as illustrated in FIG. 80. Referring now to FIGS. 82 and 83, the sleds 4270 can be advanced from a proximal end of the staple cartridge 4200 to a distal end of the staple cartridge 4200 by a cutting member 4280. For example, the cutting member 4280 can comprise a cutting element, or knife, 4283, which can be advanced through the tissue T and/or the compressible cartridge body 4210. The cutting member 4280 can comprise camming members 4282 which can travel along the outside surfaces of the jaws 4230 and 4240 and move or hold the jaws in position. As a result of the above, the staples 4220 can be formed into their final shapes at the same time, or at least substantially the same time, as the tissue T is incised. For example, the sleds 4270 can be positioned distally with respect to the knife 4283 such that the tissue T is only incised when the proceeding portion of the tissue has been fully stapled, for example.

[0673] Referring again to FIGS. 82 and 83, the sleds 4270 can comprise separate slidable members which are advanced together by the cutting member 4280. For example, the sleds 4270 can be contained within the staple cartridge 4200 and the cutting member 4280 can be advanced into the staple cartridge 4200 by a firing bar 4281 such that the cutting member 4280 engages the sleds 4270 and advances the sleds 4270 distally. The sleds 4270 can be connected to one another. In either event, each sled 4270 can comprise an angled surface, or cam, 4271 which can be configured to lift the staples 4220 aligned within a staple row. The angled surfaces 4271 can be integrally formed with the cutting member 4280. Referring again to FIGS. 82 and 83, each staple 4200 can comprise a base, at least one deformable member extending from the base, and a crown 4229 overmolded onto and/or positioned around at least a portion of the base and/or the deformable members of the staple 4200. Such crowns 4229 can be configured to be driven directly by a sled 4270, for example. More particularly, the crowns 4229 of staples 4220 can be configured such that the angled surfaces 4271 of the sleds 4270 can slide underneath and directly contact the crowns 4229 without a staple driver positioned therebetween. In such cases, each crown 4229 can comprise at least one co-operating angled or inclined surface which can be engaged by an angled surface 4271 of the sleds 4270 such that the co-operating angled surfaces can drive the staples 4220 upwardly when the sleds 4270 are slid underneath the staples 4220.

[0674] Referring now to FIG. 81, a staple cartridge, such as staple cartridge 4300, for example, can comprise a compressible body 4310 and a plurality of staples 4320 positioned within the compressible body 4310. Similar to the above, the staple cartridge 4300 can comprise flexible

lateral supports 4334 which can be attached to a staple cartridge channel and/or adhered to the compressible body 4310. In addition to the above, the flexible lateral supports 4334 can be connected together by one or more struts, or connection members, 4335 which can be configured to hold the lateral supports 4334 together. In use, the connection members 4335 can be configured to prevent, or at least inhibit, the lateral supports 4334 from becoming prematurely detached from the cartridge body 4310. The connection members 4335 can be configured to hold the lateral supports 4334 together after the staple cartridge 4300 has been compressed by an anvil. In such cases, the lateral supports 4334 can resist the lateral bulging, or displacement, of the lateral portions of the cartridge body 4310. A cutting member, such as cutting member 4280, for example, can be configured to transect the connection members 4335 as the cutting member 4280 is moved distally within the cartridge body 4310. For example, the cutting member 4280 can be configured to push one or more sleds, such as sleds 4270, for example, distally in order to form the staples 4320 against an anvil. The sleds 4270 can lead the cutting edge 4283 such that the cutting member 4280 does not transect a connection member 4335 until the staples 4320 adjacent to that connection member 4335 have been fully formed, or at least formed to a desired height. In various circumstances, the connection members 4335, in co-operation with the lateral supports 4334, can prevent, or at least reduce, the lateral movement of the compressible cartridge body 4310 and, concurrently, prevent, or at least reduce, the lateral movement of the staples 4320 positioned within the cartridge body 4310. In such circumstances, the connection members 4335 can hold the staples 4320 in position until after they are deformed and the connection members 4335 can be thereafter cut to release the lateral portions of the cartridge body 4310. As mentioned above, the lateral supports 4334 can be connected to the staple cartridge channel and, as a result, can be removed from the surgical site with the staple cartridge channel after the staple cartridge 4300 has been implanted. The lateral supports 4334 can be comprised of an implantable material and can be left within a surgical site. The connection members 4335 can be positioned intermediate the cartridge body 4310 and the tissue T and, after the connection members 4335 have been detached from the lateral supports 4334, the connections members 4335 can remain implanted in the patient. For example, the connection members 4335 can be comprised of an implantable material and the connection members 4335 can be comprised of the same material as the lateral supports 4334, for example. The connection members 4335 and/or lateral supports 4334 can be comprised of a flexible bioabsorbable material such as polyglycolic acid (PGA)

which is marketed under the trade name Vicryl, polylactic acid (PLA or PLLA), polydioxanone (PDS), polyhydroxyalkanoate (PHA), poliglecaprone 25 (PGCL) which is marketed under the trade name Monocryl, polycaprolactone (PCL), and/or a composite of PGA, PLA, PDS, PHA, PGCL and/or PCL, for example. The connection member can comprise a sheet of material connecting the lateral supports 4334. The staple cartridge can comprise connection members extending across the top surface of the cartridge body 4310 and, in addition, connection members extending around the bottom surface of the cartridge body 4310.

[0675] Referring now to FIG. 84, a staple cartridge can comprise staples, such as staples 4420, for example, which can comprise a wire portion inserted into a crown portion. The wire portion can be comprised of metal, such as titanium and/or stainless steel, for example, and/or plastic, such as polydioxanone (PDS) and/or polyglycolic acid (PGA), for example. The crown portion can be comprised of metal, such as titanium and/or stainless steel, for example, and/or plastic, such as polydioxanone (PDS) and/or polyglycolic acid (PGA), for example. The wire portion of each staple 4420 can comprise a base 4422 and deformable legs 4421 extending from the base 4422 wherein the crown portion of each staple 4420 can comprise a crown 4429 which can be configured to receive at least a portion of a base 4422 therein. In order to assemble the portions of each staple 4420, referring now to FIGS. 85A-85C, the legs 4421 of the wire portion can be inserted into an opening 4426 in a crown 4429 wherein the opening 4426 can be configured to guide the legs 4421 into a base chamber 4427. The wire portion can be further inserted into the crown 4429 such that the legs 4421 exit the base chamber 4427 and the base 4422 of the wire portion enters into the base chamber 4427. For example, the base chamber 4427 can be configured such that the wire portion is rotated within the crown 4429 as the base 4422 enters into the base chamber 4427 such that the staple legs 4421 are pointed in an upward, or at least substantially upward, direction. Referring again to FIG. 84, the crown 4429 can comprise exit holes 4425 which can be configured to receive the staple legs 4421 therein.

[0676] Further to the above, a surgical stapler can comprise a sled 4470 configured to transverse the staple cartridge 4400 and staple cartridge channel 4430 and move the staples 4420 contained within the cartridge body 4410 toward an anvil. In various circumstances, the sled 4470 can be moved from a proximal end of the staple cartridge channel 4430 to a distal end of the cartridge channel 4430 in order to implant the cartridge body 4410 and the staples 4420. In certain circumstances, the sled 4470 can be retracted or returned to the proximal end of the cartridge

channel 4430 and another staple cartridge 4400 can be inserted into the cartridge channel 4430. Once the new staple cartridge 4400 has been positioned within the cartridge channel 4430, the sled 4470 can be advanced distally once again. The surgical stapler may comprise one or more lock-out features which can prevent the sled 4470 from being advanced distally once again without a new staple cartridge 4400 being positioned within the cartridge channel 4430. For example, referring again to FIG. 84, the staple cartridge channel 4430 can comprise a lock-out shoulder 4439 which can be configured to prevent, or at least limit, the distal movement of the sled 4470. More particularly, the sled 4470 can be configured to abut the shoulder 4439 unless the sled 4470 is at least partially lifted upwardly over the shoulder 4439 by a lift feature 4428, for example, extending between the proximal-most staples 4420 within a staple cartridge 4400. Stated another way, absent the presence of the proximal-most staples 4420 in a new staple cartridge 4400, the sled 4470 cannot be advanced. Thus, when an expended staple cartridge 4400 is present within the cartridge channel 4430, or no staple cartridge 4400 is present in the cartridge channel 4430 at all, the sled 4470 cannot be advanced within the cartridge channel 4430.

[0677] Further to the above, referring now to FIG. 86, a staple cartridge, such as staple cartridge 4500, for example, can be positioned within a staple cartridge channel 4530 and can comprise a compressible cartridge body 4510, a plurality of staples 4520 positioned within the cartridge body 4510, and a cartridge pan, or retainer, 4580. The compressible cartridge body 4510 can comprise an outer layer 4511 and an inner layer 4512 wherein, the outer layer 4511 can sealingly enclose the inner layer 4512. For example, the outer layer 4511 can extend between the inner layer 4512 and the cartridge pan 4580. Alternatively, the outer layer 4511 may only partially surround the inner layer 4512 and, for example, the outer layer 4511 and the cartridge pan 4580 can co-operate to encompass, or at least substantially encompass, the inner layer 4512. Further to the above, the staples 4520 can be supported by the cartridge pan 4580 wherein the cartridge pan 4580 can comprise one or more staple support channels configured to support the staples 4520. The cartridge pan 4580 can be attached to the cartridge body 4510 wherein, for example, the cartridge body 4510 can be compressed laterally between opposing side walls of the cartridge pan 4580. The side walls of the cartridge pan 4580 can support the cartridge body 4510 laterally and, for example, the cartridge pan 4580 can comprise one or more walls, or fins, 4582 extending upwardly from the bottom support 4583 into the cartridge body 4510. For example, the cartridge

body 4510 can comprise one or more slots, or channels, therein which can be configured to receive and/or interlock with the walls 4582. The walls 4582 can extend partially, or almost entirely, through the cartridge body 4510. For example, the walls 4582 can extend longitudinally through the staple cartridge 4500 between a first row of staples 4520 and a second row of staples 4520.

[0678] The cartridge body 4510 and/or the cartridge pan 4580 can comprise co-operating retention features which can provide a snap-fit between the cartridge pan 4580 and the cartridge body 4510. The staple cartridge 4500 can be positioned within the cartridge channel 4530 such that the cartridge pan 4580 is positioned against and/or attached to the cartridge channel 4530. The cartridge pan 4580 can be detachably coupled to the cartridge channel 4530 such that, after the staple cartridge 4500 has been compressed by the anvil 4540 and the staples 4520 have been deformed, the cartridge pan 4580 can detach from the cartridge channel 4530 and can be implanted with the cartridge body 4510. For example, the cartridge pan 4580 can be comprised of a bioabsorbable material such as polyglycolic acid (PGA) which is marketed under the trade name Vicryl, polylactic acid (PLA or PLLA), polydioxanone (PDS), polyhydroxyalkanoate (PHA), poliglecaprone 25 (PGCL) which is marketed under the trade name Monocryl, polycaprolactone (PCL), and/or a composite of PGA, PLA, PDS, PHA, PGCL and/or PCL, for example. The surgical stapler can further comprise a firing mechanism and/or driver which can be slid intermediate the staple cartridge channel 4530 and a bottom drive surface on the cartridge pan 4580 which can be configured to lift or eject the cartridge pan 4580 from the cartridge channel 4530. The cartridge body 4510 can be detachably coupled to the cartridge pan 4580 such that, after the staple cartridge 4500 has been compressed by the anvil 4540 and the staples 4520 have been deformed, the cartridge body 4510 can detach from the cartridge pan 4580. For example, the cartridge pan 4580 can remain fixedly engaged with the cartridge channel 4530 such that the cartridge pan 4580 is removed from the surgical site with the cartridge channel 4530. The surgical stapler can further comprise a firing mechanism and/or driver which can be slid intermediate the staple cartridge pan 4580 and a bottom drive surface on the cartridge body 4510 which can be configured to lift or eject the cartridge body 4510 from the cartridge pan 4580. For example, the staple cartridge 4500 can further comprise staple drivers positioned intermediate the cartridge pan 4580 and the staples 4520 such that, as the firing mechanism is slid distally, the staple drivers and the staples 4520 can be driven upwardly toward the anvil. For

example, the staple drivers can be at least partially embedded within the compressible cartridge body 4510.

[0679] Similar to the above, the staple cartridge 4500 can comprise a lock-out feature which can be configured to prevent, or at least limit, the distal movement of a cutting member unless an unfired staple cartridge 4500 has been positioned within the staple cartridge channel 4530. The staple cartridge pan 4580 can comprise a surface which lifts the cutting member upwardly and over a locking surface within the staple cartridge channel 4530, for example. In the event that a staple cartridge 4500 comprising a cartridge pan 4580 is not present in the cartridge channel 4530, the cutting member cannot be advanced. The proximal-most staples, and/or any other suitable staples, within a staple cartridge 4500 can comprise a lifting surface which can sufficiently lift the cutting member over the locking surface. In addition to or in lieu of the above, various portions of the staple cartridge 4500 can be comprised of materials having different colors. In such cases, a surgeon may be able to visually identify when an unfired and/or fired staple cartridge is present in the staple cartridge channel 4530. For example, the outer layer 4511 of the cartridge body 4510 may have a first color, the cartridge pan 4580 may have a second color, and the staple cartridge channel 4530 may have a third color. In the event that the surgeon sees the first color, the surgeon may know that an unfired cartridge 4500 is present in the staple cartridge channel 4530; in the event that the surgeon sees the second color, the surgeon may know that a fired cartridge 4500 is present in the staple cartridge channel 4530 and that the remaining cartridge pan 4580 needs to be removed; and in the event that the surgeon sees the third color, the surgeon may know that no portion of a staple cartridge 4500 remains within the cartridge channel 4530.

[0680] Referring now to FIG. 87, a staple cartridge, such as staple cartridge 4600, for example, can comprise a compressible, implantable cartridge body 4610 and a plurality of staples 4620 positioned therein. The cartridge body 4610 can comprise an outer layer 4611 and an inner layer 4612. The inner layer 4612 can comprise a plurality of pockets, such as pockets, or cavities, 4615, for example, defined therein which can facilitate the collapse of the cartridge body 4610. For example, the inner layer 4612 can comprise a corrugated, or honeycomb-configured, lattice which can be configured to withstand a compressive force, or pressure, as long as the compressive force, or pressure, does not exceed a certain threshold value. When the threshold value has not been exceeded, the inner layer 4612 can deform at a linear, or at least substantially

linear, rate with respect to the compressive force, or pressure, being applied. After the compressive force, or pressure, has exceeded the threshold value, the inner layer 4612 can suddenly succumb to large deflections and collapse, or buckle, as a result of the compressive load. The lattice of the inner layer 4612 can be comprised of a plurality of sub-layers 4612a which can be connected together. Each sub-layer 4612a can comprise a plurality of alternating furrows and ridges, or waves, which can be aligned with the alternating furrows and ridges of an adjacent sub-layer 4612a. For example, the furrows of a first sub-layer 4612a can be positioned adjacent to the ridges of a second sub-layer 4612a and, similarly, the ridges of the first sub-layer 4612a can be positioned adjacent to the furrows of the second sub-layer 4612a. The adjacent sub-layers 4612a can be adhered to one another and/or the outer layer 4611 by at least one adhesive, such as fibrin and/or protein hydrogel, for example. FIG. 88 illustrates the staple cartridge 4600 after the cartridge body 4610 has been collapsed and the staples 4620 have been deformed in order to capture and hold tissue T against the cartridge body 4610.

[0681] Referring now to FIGS. 89-91, a staple cartridge, such as staple cartridge 4700, for example, can comprise a compressible, implantable cartridge body 4710 and a plurality of staples 4720 positioned within the cartridge body 4710. Similar to the above, the cartridge body 4710 can comprise an outer layer 4711 and an inner layer 4712, wherein the inner layer 4712 can comprise a plurality of sub-layers 4712a. Also similar to the above, each sub-layer 4712a can comprise alternating furrows 4717 and ridges 4718 which can be aligned with one another to define pockets, or cavities, 4715 therebetween. For example, the furrows 4717 and/or the ridges 4718 can extend along axes which are parallel to one another and/or parallel to a longitudinal axis 4709. The staples 4720 can be aligned in a plurality of staple rows which can extend along axes which are parallel to one another and/or parallel to the longitudinal axis 4709. Alternatively, referring again to FIGS. 87 and 88, the staples 4620 contained in the cartridge body 4600 can extend along axes which are traverse or perpendicular with respect to the axes defined by the furrows and ridges of the sub-layers 4612a. Referring again to FIGS. 89-91, the staples 4720 can extend through the furrows 4717 and the ridges 4718 wherein friction forces between the staples 4720 and the sub-layers 4712a can hold the staples 4720 within the cartridge body 4710. The plurality of sub-layers 4712a can be comprised of a buttress material and/or plastic material, such as polydioxanone (PDS) and/or polyglycolic acid (PGA), for example, which can be configured to hold the staples 4720 in an upright orientation, for example, and/or hold the staples 4720 in

alignment with respect to each other as illustrated in FIGS. 89 and 90. FIG. 91 illustrates the staple cartridge 4700 after the cartridge body 4710 has been collapsed and the staples 4720 have been deformed in order to capture and hold tissue T against the cartridge body 4710.

[0682] Referring again to FIGS. 89-91, the cartridge body 4710 can resiliently or elastically collapse when it is compressed. For example, the waves formed within each sub-layer 4712a by the furrows 4717 and the ridges 4718 can be flattened, or at least substantially flattened, when the cartridge body 4710 is compressed which can collapse, or at least substantially collapse, the cavities 4715 defined therebetween. In various circumstances, the cartridge body 4710, or at least portions of the cartridge body 4710, can resiliently or elastically re-expand after the compressive force, or pressure, has been removed from the cartridge body 4710. For example, the connections between the furrows 4717 and the ridges 4718 of adjacent sub-layers 4712a can remain intact, or at least substantially intact, when the cartridge body 4710 is compressed such that, after the compression force has been removed from the cartridge body 4710, the sub-layers 4712a can bias themselves away from each other and, as a result, at least partially re-expand the cartridge body 4710. The cartridge body 4710 can be plastically deformed, or crushed, when it is compressed and, as a result, the cartridge body 4710 may not re-expand after the compressive force, or pressure, has been removed from the cartridge body 4710. Referring now to FIG. 92, a staple cartridge, such as staple cartridge 4800, for example, can comprise a crushable cartridge body 4810 comprising an outer layer 4811 and an inner layer 4812, wherein the inner layer 4812 can comprise a corrugated, honeycomb-configured, lattice having a plurality of pockets, or cavities, 4815 defined therein. The walls defining the lattice of inner layer 4812 can comprise one or more weakened, or thin, cross-sections 4819 which can be configured to allow the walls defining the lattice to break when the cartridge body 4810 is compressed. In such circumstances, the cartridge body 4810 can be crushed when the staple cartridge 4800 is implanted.

[0683] Referring now to FIGS. 93-95, a staple cartridge, such as staple cartridge 4900, for example, can comprise a cartridge body 4910 comprising an outer layer 4911 and a plurality of collapsible elements 4912 positioned intermediate top and bottom portions of the outer layer 4911, for example. Referring primarily to FIGS. 93 and 94, the staple cartridge 4900 can further comprise a plurality of staples 4920, wherein each staple 4920 can be positioned in a collapsible element 4912. More particularly, each collapsible element 4912 can comprise a first portion 4912a, a second portion 4012b, and a third portion 4012c which can co-operate to define a cavity

4915 therein which is configured to receive a staple 4920. In use, further to the above, the staple cartridge 4900 can be positioned within a staple cartridge channel and a compressive force can be applied to the tissue contacting surface 4919 in order to compress the cartridge body 4910. As the tissue contacting surface 4919 is moved downwardly, the collapsible elements 4912 can collapse. In such circumstances, the second portion 4912b of each collapsible element 4912 can collapse into a corresponding first portion 4912a and, similarly, the third portion 4912c of each collapsible element 4912 can collapse into a corresponding second portion 4912b. As the cartridge body 4910 is compressed and the collapsible elements 4912 are collapsed, the staples 4920 positioned within the collapsible elements 4912 can be deformed, as illustrated in FIG. 95. The second portion 4912b of each collapsible element 4912 can be frictionally engaged and/or press-fit within a corresponding first portion 4912a such that, once the compressive force applied to the collapsible element 4912 exceeds the retention force retaining the first portion 4912a and the second portion 4912b in their extended position (FIG. 94), the first portion 4912a and the second portion 4912b can begin to slide relative to one another. Similarly, the third portion 4912c of each collapsible element 4912 can be frictionally engaged and/or press-fit within a corresponding second portion 4912b such that, once the compressive force applied to the collapsible element 4912 exceeds the retention force retaining the second portion 4912b and the third portion 4912c in their extended position (FIG. 94), the second portion 4912b and the third portion 4912c can begin to slide relative to one another.

[0684] In many embodiments described herein, a staple cartridge can comprise a plurality of staples therein. Such staples can be comprised of a metal wire deformed into a substantially U-shaped configuration having two staple legs. Other embodiments are envisioned in which staples can comprise different configurations such as two or more wires that have been joined together having three or more staple legs. The wire, or wires, used to form the staples can comprise a round, or at least substantially round, cross-section. The staple wires can comprise any other suitable cross-section, such as square and/or rectangular cross-sections, for example. The staples can be comprised of plastic wires. The staples can be comprised of plastic-coated metal wires. A cartridge can comprise any suitable type of fastener in addition to or in lieu of staples. For example, such a fastener can comprise pivotable arms which are folded when engaged by an anvil. Two-part fasteners could be utilized. For example, a staple cartridge can comprise a plurality of first fastener portions and an anvil can comprise a plurality of second fastener

portions which are connected to the first fastener portions when the anvil is compressed against the staple cartridge. As described above, a sled or driver can be advanced within a staple cartridge in order to complete the forming process of the staples. A sled or driver can be advanced within an anvil in order to move one or more forming members downwardly into engagement with the opposing staple cartridge and the staples, or fasteners, positioned therein.

[0685] A staple cartridge can comprise four rows of staples stored therein. The four staple rows can be arranged in two inner staple rows and two outer staple rows. For example, an inner staple row and an outer staple row can be positioned on a first side of a cutting member, or knife, slot within the staple cartridge and, similarly, an inner staple row and an outer staple row can be positioned on a second side of the cutting member, or knife, slot. Alternatively, the staple cartridge may not comprise a cutting member slot; however, such a staple cartridge may comprise a designated portion configured to be incised by a cutting member in lieu of a staple cartridge slot. The inner staple rows can be arranged within the staple cartridge such that they are equally, or at least substantially equally, spaced from the cutting member slot. Similarly, the outer staple rows can be arranged within the staple cartridge such that they are equally, or at least substantially equally, spaced from the cutting member slot. A staple cartridge can comprise more than or less than four rows of staples stored within a staple cartridge. A staple cartridge can comprise six rows of staples. For example, the staple cartridge can comprise three rows of staples on a first side of a cutting member slot and three rows of staples on a second side of the cutting member slot. A staple cartridge may comprise an odd number of staple rows. For example, a staple cartridge may comprise two rows of staples on a first side of a cutting member slot and three rows of staples on a second side of the cutting member slot. The staple rows can comprise staples having the same, or at least substantially the same, unformed staple height. Alternatively, one or more of the staple rows can comprise staples having a different unformed staple height than the other staples. For example, the staples on a first side of a cutting member slot may have a first unformed height and the staples on a second side of a cutting member slot may have a second unformed height which is different than the first height, for example.

[0686] referring now to FIGS. 96A-96D, an end effector of a surgical stapler can comprise a cartridge attachment portion, such as staple cartridge channel 5030, for example, a fastener cartridge removably positioned in the staple cartridge channel 5030, such as staple cartridge 5000, for example, and a jaw 5040 positioned opposite the staple cartridge 5000 and the staple

cartridge channel 5030. The staple cartridge 5000 can comprise a compressible body 5010 and a plurality of staples 5020, and/or any other suitable fasteners, at least partially positioned in the compressible body 5010. For example, each staple 5020 can comprise a base 5022 and, in addition, legs 5021 extending upwardly from the base 5022, wherein at least a portion of the legs 5021 can be embedded in the cartridge body 5010. The compressible body 5010 can comprise a top, or tissue-contacting, surface 5019 and a bottom surface 5018, wherein the bottom surface 5018 can be positioned against and supported by a support surface 5031 of the staple cartridge channel 5030. Similar to the above, the support surface 5031 can comprise a plurality of support slots 5032 (FIG. 96D), for example, defined therein which can be configured to receive and support the bases 5022 of the staples 5020. The end effector of the surgical stapler can further comprise a retention matrix, such as retention matrix 5050, for example, which can be configured to engage the staples 5020 and capture tissue therebetween. For example, the retention matrix 5050 can be removably mounted to the jaw 5040. In use, once the staple cartridge 5000 has been positioned within the staple cartridge channel 5030, the jaw 5040, and the retention matrix 5050 attached thereto, can be moved toward the staple cartridge 5000 and the staple cartridge channel 5030. The jaw 5040 can be moved downwardly along an axis 5099 such that the jaw 5040 and the staple cartridge channel 5030 remain parallel, or at least substantially parallel, to one another as the jaw 5040 is closed. More particularly, for example, the jaw 5040 can be closed in a manner such that a tissue-contacting surface 5051 of the retention matrix 5050 is parallel, or at least substantially parallel, to the tissue-contacting surface 5019 of the staple cartridge 5000 as the jaw 5040 is moved toward the staple cartridge 5000.

[0687] Referring now to FIG. 96A, the retention matrix 5050 can be detachably secured to the jaw 5040 such that there is little, if any, relative movement between the retention matrix 5050 and the jaw 5040 when the retention matrix 5050 is attached to the jaw 5040. The jaw 5040 can comprise one or more retention features which can be configured to hold the retention matrix 5050 in position. For example, the retention matrix 5050 can be snap-fit and/or press-fit into the jaw 5040. The retention matrix 5050 can be adhered to the jaw 5040 utilizing at least one adhesive. In any event, the jaw 5040 can be moved into a position in which the retention matrix 5050 is in contact with the tissue T and the tissue T is positioned against the tissue-contacting surface 5019 of the staple cartridge 5000. When the tissue T is positioned against the staple cartridge 5000 by the jaw 5040, the compressible body 5010 of the staple cartridge 5000 may or

may not be compressed by the jaw 5040. In either circumstance, the legs 5021 of the staples 5200 may not protrude through the tissue-contacting surface 5019 of the staple cartridge 5000 as illustrated in FIG. 96A. Furthermore, as also illustrated in FIG. 96A, the jaw 5040 can hold the tissue T against the compressible body 5010 without engaging the retention matrix 5050 with the staples 5020. Such embodiments can permit a surgeon to open and close the jaw 5040 multiple times in order to obtain a desired positioning of the end effector within a surgical site, for example, without damaging the tissue T. Other embodiments are envisioned, however, where the staple tips 5023 can protrude from the tissue-contacting surface 5019 prior to the cartridge body 5010 being compressed by the anvil 5040. Once the end effector has been suitably positioned, referring now to FIG. 96B, the jaw 5040 can be moved downwardly toward the staple cartridge channel 5030 such that the compressible body 5010 is compressed by the anvil 5040 and such that the tissue-contacting surface 5019 is pushed downwardly relative to the staples 5020. As the tissue-contacting surface 5019 is pushed downwardly, the tips 5023 of the staple legs 5021 can pierce the tissue-contacting surface 5019 and pierce at least a portion of the tissue T. In such circumstances, the retention matrix 5050 may be positioned above the staples 5020 such that the retention apertures 5052 of retention matrix 5050 are aligned, or at least substantially aligned, with the tips 5023 of the staple legs 5021.

[0688] As the retention matrix 5050 is pushed downwardly along the axis 5099, referring now to FIG. 96C, the staple legs 5021 of staples 5020 can enter into the retention apertures 5052. The staple legs 5021 can engage the side walls of the retention apertures 5052. As described in greater detail below, the retention matrix 5050 can comprise one or more retention members extending into and/or around the retention apertures 5052 which can engage the staple legs 5021. In either event, the staple legs 5021 can be retained in the retention apertures 5052. In various circumstances, the tips 5023 of the staple legs 5021 can enter into the retention apertures 5052 and can frictionally engage the retention members and/or the side walls of the apertures 5052. As the retention matrix 5050 is pushed toward the bases 5022 of the staples 5020, the staple legs 5021 can slide relative to the side walls and/or the retention members. As a result of the above, sliding friction forces can be created between the staple legs 5021 and the retention matrix 5050 wherein such sliding friction forces can resist the insertion of the retention matrix 5050 onto the staples 5020. The sliding friction forces between the retention matrix 5050 and the staples 5020 can be constant, or at least substantially constant, as the retention matrix 5050 is slid

downwardly along the staple legs 5021 of the staples 5020. The sliding friction forces may increase and/or decrease as the retention matrix 5050 is slid downwardly along the staple legs 5021 owing to variations in geometry of the staple legs 5021, the retention apertures 5052, and/or the retention members extending into and/or around the retention apertures 5052, for example. The insertion of the retention matrix 5050 onto the staples 5020 can also be resisted by the compressible body 5010 of the staple cartridge 5000. More particularly, the compressible body 5010 can be comprised of an elastic material, for example, which can apply a resistive force to the retention matrix 5050 which increases as the distance in which the compressible body 5010 is compressed increases. For example, the increase in the resistive force generated by the cartridge body 5010 can be linearly proportional, or at least substantially linearly proportional, with respect to the distance in which the cartridge body 5010 is compressed. The increase in the resistive force generated by the cartridge body 5010 can be geometrically proportional with respect to the distance in which the cartridge body 5010 is compressed.

[0689] Further to the above, a sufficient firing force can be applied to the jaw 5040 and the retention matrix 5050 in order to overcome the resistive and friction forces described above. In use, the retention matrix 5050 can be seated to any suitable depth with respect to the staples 5020. The retention matrix 5050 can be seated to a depth with respect to the bases 5022 of the staples 5020 in order to secure two or more layers of tissue together and generate compressive forces, or pressure, within the tissue. In various circumstances, the system comprising the retention matrix 5050 and the staples 5020 can allow a surgeon to select the amount of compressive forces, or pressure, that is applied the tissue by selecting the depth in which the retention matrix 5050 is seated. For example, the retention matrix 5050 can be pushed downwardly toward the staple bases 5022 of the staples 5020 until the retention matrix 5050 is seated a certain depth 5011 away from the bottom of the support slots 5032, wherein a shorter depth 5011 can result in higher compressive forces, or pressure, being applied to the tissue T than a taller depth 5011 which can result in lower compressive forces, or pressure, being applied to the tissue T. The compressive forces, or pressures, applied to the tissue T can be linearly proportional, or at least substantially linearly proportional, to the depth 5011 in which the retention matrix 5050 is seated. In various circumstances, the compressive forces, or pressure, applied to the tissue T can depend on the thickness of the tissue T positioned between the retention matrix 5050 and the staple cartridge 5020. More particularly, for a given distance 5011,

the presence of thicker tissue T can result in higher compression forces, or pressure, than the presence of thinner tissue T.

[0690] In various circumstances, further to the above, a surgeon can adjust the depth in which the retention matrix 5050 is seated in order to account for thicker and/or thinner tissue positioned within the end effector and to apply a certain or predetermined pressure to the tissue T regardless of the tissue thickness. For example, the surgeon can seat the retention matrix 5050 to a shorter depth 5011 when fastening thinner tissue T or a taller depth 5011 when fastening thicker tissue T in order to arrive at the same, or at least substantially the same, compression pressure within the tissue. Further to the above, a surgeon can selectively determine the amount of compressive pressure to apply to the tissue T positioned between the retention matrix 5050 and the staple cartridge 5010. In various circumstances, a surgeon can engage the retention matrix 5050 with the staples 5020 and position the retention matrix 5050 a first distance away from the bases 5022 of the staples 5020 in order to apply a first compressive pressure to the tissue. The surgeon can alternatively position the retention matrix 5050 a second distance away from the bases 5022, which is shorter than the first distance, in order to apply a second compressive pressure to the tissue which is greater than the first pressure. The surgeon can alternatively position the retention matrix 5050 a third distance away from the bases 5022, which is shorter than the second distance, in order to apply a third compressive pressure to the tissue which is greater than the second pressure. The fastening system comprising the retention matrix 5050 and the staples 5020 can be configured to permit a surgeon to apply a wide range of compressive pressures to the targeted tissue.

[0691] Referring now to FIG. 96D, the staple legs 5021 can be inserted through the retention matrix 5050 such that the staple leg tips 5023 extend above the top surface of the retention matrix 5050. Referring again to FIG. 96C, the jaw 5040 can further comprise clearance apertures 5042 defined therein which can be configured to receive the staple leg tips 5023 as they pass through the retention apertures 5052 in the retention matrix 5050. For example, the clearance apertures 5042 can be aligned with the retention apertures 5052 such that the legs 5021 do not contact the jaw 5040. The clearance apertures 5042 can have a sufficient depth such that the staple legs 5021 do not contact the jaw 5040 regardless of the distance in which the retention matrix 5050 is seated. After the retention matrix 5050 has been engaged with the staples 5020 and seated to a desired position, referring now to FIG. 96D, the staple cartridge channel 5030

and the jaw 5040 can be moved away from the tissue T. More particularly, the staple cartridge channel 5030 can be detached from the implanted staple cartridge 5000 and the anvil 5040 can be detached from the implanted retention matrix 5050. As the jaw 5040 is moved away from the retention matrix 5050 and the staple supports 5032 are moved away from the staple bases 5022, the distance 5011 between the retention matrix 5050 and the bottom of the bases 5022 can be maintained even though the jaw 5040 and the staple cartridge channel 5030 are no longer providing support thereto. The static friction forces between the staple legs 5021 and the retention matrix 5050 can be sufficient to maintain the retention matrix 5050 in position despite a biasing force being applied to the retention matrix 5050 by the compressed cartridge body 5010 and/or the compressed tissue T. For example, the cartridge body 5010 can be comprised of a resilient material which, when compressed, can apply an elastic biasing force to the retention matrix 5050 and the staples 5020 in a manner which tends to push the retention matrix 5050 and the staples 5020 apart, although such movement is opposed by the frictional engagement between the staple legs 5021 and the retention matrix 5050.

[0692] As described above, a retention matrix can comprise a plurality of retention apertures, wherein each retention aperture can be configured to receive a leg of a fastener therein. Referring now to FIG. 97, a portion of a retention matrix 5150 is illustrated therein which can comprise a retention aperture 5152 defined by a perimeter 5156. The perimeter 5156 of the aperture 5152 can comprise a circular, or at least substantially circular, profile and/or any other suitable profile. The retention matrix 5150 can comprise one or more retention members, such as retention members 5153, for example, which extend into the aperture 5152 and can be configured to engage a fastener leg when the fastener leg is inserted therethrough. For example, each retention member 5153 can comprise a cantilever which extends inwardly toward a center axis 5159, i.e., toward the center of the aperture 5152. Each cantilever can comprise a first end which is attached to the retention matrix body 5158 and a second end which forms the perimeter 5156 of the retention aperture 5152. The perimeter 5156 of a retention aperture 5152 can be defined by a first diameter, or width and a fastener leg can be defined by a second diameter, or width, wherein the second diameter can be larger than the first diameter. For example, the fastener leg can be configured to contact and deflect one or more of the retention members 5153 in order to increase the diameter of the retention aperture 5152 as the fastener leg is being inserted therethrough. Further to the above, the fastener leg can define a perimeter which is larger than the perimeter

5156 of the retention aperture 5152 such that the fastener leg can expand the perimeter 5156 when the fastener leg is inserted therein.

[0693] Referring again to FIG. 97, the aperture 5152 can be defined by the deformable members 5153, wherein each deformable member 5153 can be configured to deflect relative to, or independently of, the other deformable members 5153. For example, adjacent deformable members 5153 can be separated by slots 5154 which can be configured to permit each deformable member 5153 to flex relative to the others. Each slot 5154 can comprise a first end 5155 in the retention matrix body 5158, a second end opening into the retention aperture 5152, and a constant, or at least substantially constant, width extending between the first end 5155 and the second end. Alternatively, the width of each slot 5154 may not be constant and each slot 5154 may increase and/or decrease in width between the first and second ends thereof. The first ends 5155 of the slots 5154 can comprise an enlarged portion, such as a circular portion, which can provide, one, strain relief to the bases of the deformable members 5153 attached to the retention matrix body 5158 and, two, means for increasing the flexibility of the deformable members 5153. The geometry of the deformable members 5153, and/or slots 5154, can be selected so as to provide the deformable members 5153 with a desired flexibility. For example, the slots 5154 can be lengthened in order to create longer deformable members 5153 which can be more flexible than deformable members 5153 having a shorter length. The width of each deformable member 5153 can be selected so as to provide a desired flexibility thereof. More particularly, deformable members having a thinner width can be more flexible than deformable members having a thicker width. Referring again to FIG. 97, the first ends of the cantilevers of deformable members 5153 attached to the retention matrix body 5158 can be wider than the second ends of the cantilevers. For example, the cantilevers can be tapered in a linear, or at least substantially linear, manner between the first and second ends thereof.

[0694] Referring again to FIG. 97, the retention matrix body 5158 can comprise a flat, or at least substantially flat, sheet of material having a tissue-contacting surface 5151 and a top surface 5157. For example, the tissue-contacting surface 5151 and the top surface 5157 can be parallel, or at least substantially parallel, to one another. Each deformable member 5153 can comprise a first portion 5153a and a second portion 5153b, wherein the first portion 5153a can extend in a first direction and the second portion 5153b can extend in a different, or second, direction. For example, the retention matrix body 5158 can define a plane and the first portions 5153a of the

deformable members 5153 can lie within such a plane. The second portions 5153b of the deformable members 5153 can extend at an angle relative to the first portions 5153a. For example, the second portions 5153b can extend in directions which are pointed away from the top surface 5157 of the retention matrix body 5158 and, The second portions 5153b can converge toward the central axis 5159 of the retention aperture 5152. In any event, the second portions 5153b can be configured to deflect away from the central axis 5159 when the fastener leg is inserted therethrough. Where a staple leg 5021 of a staple 5020 is inserted into a retention aperture 5152, the deformable members 5153 can deform in a direction which is generally away from the bases 5122 of the staples 5120. As a result, the deformable members 5153 can deflect in a general direction which is the same as, or at least substantially the same as, the direction in which the staple legs 5021 are being inserted.

[0695] Referring again to FIG. BD, the second portions 5153b of the deformable members 5153 can each comprise a sharp tip, for example, which can be configured to slide against a staple leg 5021 as the staple leg 5021 is inserted therein. The sharp tips of the second portions 5153b can also be configured to bite into the staple leg 5021 in the event that the staple leg 5021 were to be pulled in the opposite direction, i.e., in a direction which would remove the staple leg 5021 from the retention aperture 5052. In certain circumstances, the second portions 5153b can be inclined at an angle relative to the side of the staple leg 5021 which is greater than 90 degrees and, as a result, the second portions 5153b may dig, or burrow, into the side of the staple leg 5021 when the staple leg 5021 experiences a force which tends to withdraw the staple leg 5021 from the retention aperture 5052. The staple legs 5021 can comprise indentations and/or concavities, such as microindentations, for example, in the surfaces thereof which can be configured to receive the tips of the deformable members 5053, for example, therein. For example, the tips of the deformable members 5053 can catch in and burrow into the indentations in the staple legs 5021 when a withdrawing force is applied to the staple legs 5021. As a result of the burrowing of the second portions 5153b into the staple legs 5021, forces acting to remove the staple legs 5021 from the retention apertures 5022 may only seat the second portions 5153b deeper into the staple legs 5021 and increase the force required to remove the staple legs 5021. Furthermore, owing to the upward inclination of the second portions 5153b, the second portions 5153b can be more permissive to the insertion of a staple leg 5021 within a retention aperture 5152 and more resistive to withdrawal of the staple leg 5021. As a result, the force required to insert a staple leg

5021 into a retention aperture 5022 may be less than the force required to remove the staple leg 5021 from the retention aperture 5022. The force needed to remove the staple leg 5021 from the retention aperture 5022 can be approximately 50 percent greater than the force needed to insert the staple leg 5021 into the retention aperture 5022, for example. Alternatively, the force needed to remove the staple leg 5021 may between approximately 10 percent and approximately 100 percent greater than the force needed to insert the staple leg 5021, for example. The force needed to remove the staple leg 5021 may be approximately 100 percent, approximately 150 percent, approximately 200 percent, and/or greater than approximately 200 percent larger than the force needed to insert the staple leg 5021, for example.

[0696] Referring again to FIG. 97, the second portions 5153b can be arranged circumferentially around the aperture 5152 and can define a pocket therebetween. More particularly, the second portions 5153b can define a pocket 5160 which can be configured to receive the tip of the fastener leg when it is inserted into the retention aperture 5152. The second portions 5153b of the deformable members 5153 can comprise an annular, or an at least substantially annular, contour which can co-operatively define an annular, or at least substantially annular, profile of the pocket 1560, for example. For example, the second portions 5153b can define a conical or frustoconical pocket. The pocket can be defined by a suitable number of deformable members, such as four deformable members 5153 (FIG. 97), six deformable members 5153 (FIG. 98), or eight deformable members 5153 (FIG. 99), for example. Referring now to FIG. 100, the deformable members of a retention matrix, such as retention matrix 5250, for example, can form a pyramidal shape, or an at least substantially pyramidal shape, for example. A retention matrix 5250 can comprise a plurality of retention apertures, such as retention aperture 5252, for example, which can be defined by a perimeter 5256. The perimeter 5256 can comprise a polygonal, or at least substantially polygonal, profile and/or any other suitable profile. The retention matrix 5250 can comprise one or more retention members, such as retention members 5253, for example, which extend into the aperture 5252 and can be configured to engage a fastener leg when the fastener leg is inserted therethrough. For example, each retention member 5253 can comprise a cantilever which extends inwardly toward a center axis 5259, i.e., toward the center of the aperture 5252. Each cantilever can comprise a first end which is attached to the retention matrix body 5258 and a second end which forms the perimeter 5256 of the retention aperture 5252. The perimeter 5256 of a retention aperture 5252 can be defined by a first diameter, or width, and a fastener leg can be

defined by a second diameter, or width, wherein the second diameter can be larger than the first diameter. For example, the fastener leg can be configured to contact and deflect one or more of the retention members 5253 in order to increase the diameter of the retention aperture 5252 as the fastener leg is being inserted therethrough. Further to the above, the fastener leg can define a perimeter which is larger than the perimeter 5256 of the retention aperture 5252 such that the fastener leg can expand the perimeter 5256 when the fastener leg is inserted therein.

[0697] Referring again to FIG. 100, the aperture 5252 can be defined by the deformable members 5253, wherein each deformable member 5253 can be configured to deflect relative to, or independently of, the other deformable members 5253. For example, adjacent deformable members 5253 can be separated by slots 5254 which can be configured to permit each deformable member 5253 to flex relative to the others. The retention matrix body 5258 can comprise a flat, or at least substantially flat, sheet of material having a tissue-contacting surface 5251 and a top surface 5257. For example, the tissue-contacting surface 5251 and the top surface 5257 can be parallel, or at least substantially parallel, to one another. Each deformable member 5253 can comprise a first portion 5253a and a second portion 5253b, wherein the first portion 5253a can extend in a first direction and the second portion 5253b can extend in a different, or second, direction. For example, the retention matrix body 5258 can define a plane and the first portions 5253a of the deformable members 5253 can lie within such a plane. The second portions 5253b of the deformable members 5253 can extend at an angle relative to the first portions 5253a. For example, the second portions 5253b can extend in directions which are pointed away from the top surface 5257 of the retention matrix body 5258 and the second portions 5253b can converge toward the central axis 5259 of the retention aperture 5252. In any event, the second portions 5253b can be configured to deflect away from the central axis 5259 when the fastener leg is inserted therethrough. Referring again to FIG. 100, the second portions 5253b can be arranged circumferentially around the aperture 5252 and can define a pocket therebetween. More particularly, the second portions 5253b can define a pocket which can be configured to receive the tip of the fastener leg when it is inserted into the retention aperture 5252. The second portions 5253b of the deformable members 5253 can define a polygonal, or an at least substantially polygonal, pocket, for example. The pocket can be defined by a suitable number of deformable members, such as four deformable members 5253 (FIG. 100) which can define a square, six

deformable members 5253 (FIG. 101) which can define a hexagon, or eight deformable members 5253 (FIG. 102) which can define an octagon, for example.

[0698] Referring now to FIG. 103, a retention matrix, such as retention matrix 5350, for example, can be formed from a flat, or an at least substantially flat, sheet of material such as titanium and/or stainless steel, for example. For example, a plurality of apertures 5352 can be formed in the body 5358 of the retention matrix 5350 by one or more stamping processes. The sheet of material can be positioned in a stamping die which, when actuated, can punch out certain portions of the material in order to form slots 5354, apertures 5355 of slots 5354, and/or the perimeter 5356 of the retention aperture 5352, for example. The stamping die can also be configured to bend the deformable members 5353 in a suitable configuration. For example, the stamping die can deform the second portions 5353b upwardly relative to the first portions 5353a along a crease line 5353c. Referring now to FIG. 104, a retention matrix, such as retention matrix 5450, for example, can comprise a plurality of retention apertures 5452. Similar to the above, the perimeter 5456 of each retention aperture 5452 can be defined by a plurality of deformable members 5453 separated by slots, or slits, 5454. For example, the entirety of each deformable member 5453 can be bent upwardly wherein the free ends of the cantilevers comprising the deformable members 5453 can define the perimeter 5456. The retention matrix 5450 can comprise a plurality of apertures 5455 surrounding, or at least substantially surrounding, the retention aperture 5452. For example, the apertures 5455 can be arranged in a circular array surrounding or enclosing a perimeter defined by the fixed ends of the cantilevers of the deformable members 5453. Each aperture 5455 can comprise a circular, or at least substantially circular, perimeter and/or any other suitable perimeter. In use, the apertures 5455 can provide, one, strain relief to the bases of the deformable members 5453 attached to the retention matrix body 5458 and, two, means for increasing the flexibility of the deformable members 5453. Larger apertures 5455 can provide more flexibility to the deformable members 5453 as compared to smaller apertures 5455. Furthermore, apertures 5455 which are closer to the deformable members 5453 can provide more flexibility as compared to apertures 5455 which are further away.

[0699] Referring now to FIG. 105, a retention matrix, such as retention matrix 5550, for example, can comprise a plurality of retention apertures 5552. Each retention aperture 5552 can comprise an elongate slot 5554 having enlarged circular, or at least substantially circular, ends

5555. For example, the ends 5555 can be defined by a diameter which is wider than the slot 5554. The elongate slot 5554 and the ends 5555 can positioned along, and/or centered along, a longitudinal axis 5559. The slot 5554 and the ends 5555 can define two opposing tabs 5553 which can be configured to engage a leg of a fastener and deflect as the fastener leg is inserted therethrough. Ends 5555 having a larger perimeter, or diameter, can define longer tabs 5553 which can be more flexible than tabs 5553 defined by ends 5555 having a smaller perimeter, or diameter. The ends 5555 can have the same perimeter and diameter and, for example, each tab 5553 can be symmetrical about an axis which is perpendicular, or at least substantially perpendicular, to the longitudinal axis 5559. Alternatively, the ends 5555 can have different perimeters and/or diameters wherein, each tab 5553 may not be symmetrical about its axis. For example, the tabs 5553 may twist about their axes as the fastener leg is inserted through the retention aperture 5552. Referring now to FIG. 106, a retention matrix, such as retention matrix 5650, for example, can comprise a plurality of retention apertures 5652. Each retention aperture 5652 can comprise an elongate slot 5654 comprising circular, or at least substantially circular, ends 5655. For example, the elongate slot 5654 and the ends 5655 can be positioned along, and/or centered along, a longitudinal axis 5659. Each end 5655 can be defined by a diameter which is the same as, or at least substantially the same as, the width of the slot 5654.

[0700] Referring now to FIG. 107, a retention matrix, such as retention matrix 5750, for example, can comprise a plurality of retention apertures 5752. Each retention aperture 5752 can comprise a plurality of slots, such as slots 5754, for example, having enlarged ends 5755. For example, the slots 5754 and the ends 5755 can be positioned along and/or centered along longitudinal axes 5759. The axes 5759 can extend in directions which are perpendicular or transverse to one another. The slots 5754 and the ends 5755 can define four tabs 5753, for example, which can be configured to engage a fastener leg and deflect when the fastener leg is inserted through the retention aperture 5752. Each tab 5753 can comprise a triangular, or at least substantially triangular, configuration, such as an equilateral triangle, for example. Alternatively, referring now to FIG. 108, a retention matrix, such as retention matrix 5850, for example, can comprise a plurality of retention apertures 5852. Each retention aperture 5852 can comprise a plurality of slots, such as slots 5854, for example, having ends 5855, wherein the slots 5854 and the ends 5855 can be positioned along and/or centered along longitudinal axes 5859. The axes 5859 can extend in directions which are perpendicular or transverse to one another. The slots

5854 and the ends 5855 can define tabs 5853 which can be configured to engage a fastener leg and deflect when the fastener leg is inserted through the retention aperture 5852. Each tab 5853 can comprise an arcuate profile. More particularly, each tab 5853 can comprise a curved end, as opposed to a pointed end depicted in FIG. 105, which can be configured to contact the fastener leg.

[0701] Referring now to FIG. 109, a retention matrix, such as retention matrix 5950, for example, can comprise a plurality of retention apertures 5952. Each retention aperture 5952 can comprise a plurality of slots, such as slots 5954, for example, wherein each slot 5954 can extend along, and/or can be centered along, an axis 5959. The axes 5959 can be transverse to each other and, for example, the axes 5959 can be arranged such that all of the axes 5959 extend through a center of the retention aperture 5952 and are spaced equidistantly, or at least substantially equidistantly, from each other. Each slot 5954 can comprise an open end facing the center of the retention aperture 5952 and a second, or closed, end 5955 at the opposite end of the slot 5954. Similar to the above, the slots 5954 and the ends 5955 can define three tabs 5953, for example, which can be configured to engage a fastener leg and deflect when the fastener leg is inserted into the retention aperture 5952. Each tab 5953 can comprise an arcuate configuration extending between adjacent ends 5955 of the slots 5954. Referring now to FIG. 110, a retention matrix, such as retention matrix 6050, for example, can comprise a plurality of retention apertures 6052. Each retention aperture 6052 can comprise a tab 6053 which can be configured to engage a fastener leg and to deflect when the fastener leg is inserted into the retention aperture 6052. For example, the tab 6053 can comprise a base fixed to the retention matrix body 6058 and a free end comprising an arcuate or curved profile 6056 which can be configured to contact the fastener leg. The fastener leg can be a staple leg comprised of a round wire wherein the curved profile 6056 can be configured to match, or at least substantially match, a curved outer surface of the round wire.

[0702] Referring again to FIG. 110, the retention matrix body 6058 can comprise a plurality of slots 6054 and apertures 6055 which can be configured to define the tab 6053 and various portions of the retention aperture 6052. The tab 6053 can comprise a rectangular configuration comprising parallel, or at least substantially parallel, sides. Referring now to FIG. 111, a retention matrix, such as retention matrix 6150, for example, can comprise a plurality of retention apertures 6152. Each retention aperture 6152 can comprise a tab 6153 which can be

configured to engage a fastener leg and to deflect when the fastener leg is inserted into the retention aperture 6152. For example, the tab 6153 can comprise a base fixed to the retention matrix body 6158 and a free end comprising an arcuate or curved profile 6156 which can be configured to contact the fastener leg. The retention matrix body 6158 can comprise a plurality of slots 6154 and apertures 6155 which can be configured to define the tab 6153 and various portions of the retention aperture 6152. The tab 6153 can comprise a tapered configuration comprising arcuate sides. For example, the tab 6153 can taper geometrically with the base being wider than the free end, for example.

[0703] As described above, a fastening system can comprise a plurality of staples comprising staple legs which are inserted through a plurality of retention apertures in a retention matrix. As described in greater detail below, the staples can be held in a first jaw and the retention matrix can be held in a second jaw, wherein at least one of the first jaw and the second jaw can be moved toward the other. In various circumstances, the staples positioned within the first jaw can be secured therein such that the staple legs are aligned with the retention apertures when the retention matrix is engaged with the staple legs. Referring to FIGS. 112 and 113, a fastener system can comprise a staple cartridge 6200, for example, positioned in a first jaw of a surgical stapler and a retention matrix 6250, for example, positioned in a second jaw of the surgical stapler. Referring now to FIGS. 119 and 120, further to the above, the retention matrix 6250 can comprise a plurality of retention apertures 6252, wherein each retention aperture 6252 can comprise a perimeter 6256 defined by one or more deflectable members 6253. For example, further to the above, the deflectable members 6253 defining each aperture 6252 can define a pocket 6201. Each pocket 6201 can comprise a curved and/or concave surface, for example, which can be configured to guide a tip of a staple leg into the aperture 6252 in the event that the staple leg is misaligned with the retention aperture 6252 and initially contacts the deflectable members 6253 and/or the tissue-contacting surface 6251, for example.

[0704] Further to the above, the fastening system can further comprise a plurality of staples 6220 comprising staple legs 6221 which can be inserted through the retention apertures 6252 in the retention matrix 6250. For example, each staple 6220 can comprise a substantially U-shaped configuration, for example, comprising a base 6222 from which the staple legs 6221 can extend upwardly. Referring now to FIGS. 115 and 116, the retention apertures 6252 in the retention matrix 6250 can be arranged in two parallel, or at least substantially parallel, longitudinal rows,

for example, which can extend along, or parallel to, a longitudinal axis of the retention matrix. The retention apertures 6252 in a first row can be offset, or staggered, with respect to the retention apertures 6252 in a second row. For example, each staple 6220 can comprise a first staple leg 6221 positioned in a retention aperture 6252 in the first row of and a second staple leg 6221 positioned in a retention aperture 6252 in the second row wherein, as a result, the bases 6222 can extend in a direction which is transverse to the longitudinal axis of the retention matrix 6250. For example, the staples 6220 can be parallel, or at least substantially parallel, to one another. More particularly, a base 6222a of a staple 6220a be parallel to, or at least substantially parallel to, a base 6222b of a staple 6220b which can be parallel to, or at least substantially parallel to, a base 6222c of a staple 6220c, for example. The staple legs 6221a of staple 6220a can define a plane which is parallel to, or at least substantially parallel to, a plane defined by the staple legs 6221b of staple 6220b which can be parallel to, or at least substantially parallel to, a plane defined by the staple legs 6221 of staple 6220c, for example.

[0705] Referring now to FIGS. 112 and 114, the staple cartridge 6200 can comprise a plurality of staples 6220 and, in addition, an alignment matrix 6260 comprising a plurality of alignment guides, such as slots, grooves, and/or apertures, for example, which can be configured to align the staples 6220. In various circumstances, the alignment matrix 6260 can be configured such that the staple legs 6221 of the staples 6220 are aligned with the retention apertures 6252 in the retention matrix 6250 before the retention matrix 6250 is engaged with the staple legs 6221. Referring now to FIGS. 117 and 118, the alignment matrix 6260 can comprise a plurality of alignment apertures 6262 which can be configured to closely receive the staple legs 6221 of the staples 6220. For example, each staple 6220 can comprise a base 6222 and two staple legs 6221 extending from the base 6222 wherein the bases 6222 of the staples 6220 can extend around a bottom surface 6264 of the retention matrix 6260 and the staple legs 6221 can extend upwardly through the alignment apertures 6262. Each alignment aperture 6262 can be circular, or at least substantially circular, and can be defined by a diameter which is equal to or slightly larger than the diameter of the staple leg 6221 extending therethrough. The alignment matrix 6260 can further comprise a plurality of raised members 6263 which can extend upwardly from the top surface 6261 of the alignment matrix 6260 and surround, or at least partially surround, the alignment apertures 6262. The raised members 6263 can provide for longer alignment apertures

6262 wherein, in various circumstances, longer apertures 6262 can provide more control over the alignment of the staple legs 6221 than shorter apertures 6262.

[0706] In use, a first jaw supporting the staple cartridge 6200 can be positioned on one side of the tissue that is to be stapled and a second jaw supporting the retention matrix 6250 can be positioned on the other side of the tissue. Once the jaws have been suitably positioned relative to the tissue, The second jaw and the retention matrix 6250 can be moved toward the staple cartridge 6200. As the staple legs 6221 are being inserted through the retention apertures 6252 of the retention matrix 6250, a tissue-contacting, or bottom, surface 6251 of the retention matrix 6250 can contact the tissue and press the tissue against the tissue-contacting, or top, surface 6261 of the alignment matrix 6260. Alternatively, as described in greater detail further below, the staple cartridge 6200 can further comprise a compressible cartridge body positioned above the top surface 6261 of the alignment matrix 6260, for example, which can contact the tissue. Referring again to FIGS. 114 and 118, the alignment matrix 6260 can further comprise one or more apertures 6203 defined therein which, when the alignment matrix 6260 is positioned against tissue, can be configured to receive a portion of the tissue therein. Where a compressible cartridge body is positioned above and/or against the alignment matrix 6260, a portion of the compressible cartridge body can enter into the apertures 6203 when the cartridge body is compressed. Similarly, the retention matrix 6250 can comprise a plurality of apertures 6202 which can be configured to receive at least a portion of the tissue therein when the retention matrix 6250 is positioned against the tissue.

[0707] As the staple legs 6221 of the staples 6220 are inserted through the retention apertures 6252 of the retention matrix 6250, further to the above, the tips of the staple legs 6221 may protrude upwardly from the top surface 6257 of the retention matrix 6250. In various circumstances, as described above, the tips of the staple legs 6221 may remain unbent after they have been inserted through the retention apertures 6252. Referring now to FIGS. 121-124, a fastening system comprising the staple cartridge 6200 and the retention matrix 6250 may further comprise a plurality of protective caps or covers, such as caps 6270, for example, which can be assembled to the staple legs 6221 protruding above the retention matrix 6250. Each cap 6270 can entirely, or at least partially, cover the sharp end of a staple leg 6221 such that the sharp end does not contact tissue positioned adjacent thereto. Referring now to FIG. 124, each cap 6270 can comprise an aperture 6271 defined therein which can be configured to closely receive a tip of a

staple leg 6221 therein. The caps 6270 can be comprised of an elastomeric material, such as silicone, polyisoprene, sanoprene, and/or natural rubber, for example. The aperture 6271 can comprise a perimeter or diameter which is smaller than the perimeter or diameter of the staple leg 6221 inserted therein. For example, the aperture 6271 in the protective cap 6270 can expand in order to receive the staple leg 6221 therein. Alternatively, the caps 6270 may not comprise apertures and the tips of the staple legs 6221 can be configured to incise the caps 6270 as the legs 6221 are inserted therein. In any event, each cap 6270 can be seated onto a staple leg 6221 until the base 6272 of the cap 6270 abuts, or is positioned adjacent to, the top surface 6257 of the retention matrix 6250. In various circumstances, the caps 6270 can be configured such that they are seated snugly onto the tips of the staple legs 6221 such that they are not easily removed therefrom. Each cap 6270 can comprise a conical, or at least substantially conical, outer surface, for example. The caps 6270 can comprise any suitable shape, such as shapes comprising a parabolic, or at least substantially parabolic, outer surface, for example.

[0708] The fastener system described above, for example, could be deployed using the surgical stapler depicted in FIGS. 125-127, for example. The end effector can comprise a first jaw, or staple cartridge channel, 6230 which can be configured to support the staple cartridge 6200 therein and a second jaw 6240 which can be configured to support the retention matrix 6250 and the plurality of protective caps 6270. Referring primarily to FIG. 125, which illustrates the second jaw 6240 in an open configuration, the jaws 6230 and 6240 can be positioned relative to tissue T such that the tissue T is positioned intermediate the retention matrix 6250 and the staple cartridge 6200. As discussed above, the staple cartridge 6200 can further comprise a compressible cartridge body, such as cartridge body 6210, for example, in which the staples 6220 and the alignment matrix 6260 can be positioned. For example, the tissue T can be positioned against a top surface of the cartridge body 6210. The second jaw 6240 can comprise a plurality of recesses, or apertures, 6245 configured to receive the plurality of protective caps 6270 and, in addition, one or more retention features, or retainers, which can be configured to hold the retention matrix 6250 in position over the caps 6270. For example, the retention matrix 6250 can be configured to retain the caps 6270 in the apertures 6245. Referring now to FIG. 137, each aperture 6245 can be configured to receive a portion of, or the entirety of, a cap 6270 therein. The apertures 6245 can be sufficiently sized and configured such that the caps 6270 can be secured therein by at least one of a press-fit and/or snap fit arrangement, for example. At least

one adhesive could be utilized to secure the caps 6270 in the apertures 6245. For example, such an adhesive could be selected such that caps 6270 can detach from the second jaw 6240 after the caps 6270 have been engaged with the staple legs 6221 and the second jaw 6240 is moved away from the implanted fastener assembly. Referring now to FIG. 138, the second jaw 6240 can further comprise at least one cover sheet 6246 which can be assembled to the second jaw 6240 and can extend over and retain the caps 6270 in the apertures 6245. For example, at least a portion of the cover sheet 6246 can be secured to the jaw 6240 utilizing at least one adhesive, for example. In use, the cover sheet 6246 can be at least partially detached from the jaw 6240 before the end effector is inserted into a surgical site. The cover sheet 6246 can be comprised of an implantable material, such as PDS and/or PGA, for example, which can be incised by the staple legs 6221 as the staple legs 6221 emerge from the retention matrix 6250. For example, the cover sheet 6246 can be secured in the fastening system intermediate the covers 6270 and the retention matrix 6250.

[0709] Further to the above, referring now to FIG. 126, the jaw 6240 can be moved from an open position to a closed position in which the tissue T is positioned against the retention matrix 6250 and the cartridge body 6210. In such a position, the retention matrix 6250 may not yet be engaged with the staples 6220. The jaw 6240 can be moved between its open position and its closed position by an actuator 6235. For example, the jaw 6240 can comprise a distal pin 6243 and a proximal pin 6244 extending therefrom, wherein the distal pin 6243 can slide vertically, or at least substantially vertically, within a distal slot 6233 defined in the cartridge channel 6230, and wherein the proximal pin 6244 can slide vertically, or at least substantially vertically, within a proximal slot 6234 which is also defined in the staple cartridge channel 6230. In use, the actuator 6235 can be retracted proximally in order to drive the pins 6243 and 6244 into the upper ends of their respective slots 6233 and 6234 as illustrated in FIG. 126. For example, the actuator 6235 can comprise a distal drive slot 6236 and a proximal drive slot 6237, wherein the sidewalls of the drive slots 6236 and 6237 can be configured to contact the distal pin 6243 and the proximal pin 6244, respectively, and drive the pins 6243 and 6244 upwardly as the actuator 6235 is moved proximally. More particularly, as the actuator 6235 is moved proximally, the distal pin 6243 can slide up an inclined first portion 6236a of the distal drive slot 6236 into an intermediate, or second, portion 6236b and, similarly, the proximal pin 6244 can slide up an inclined first portion 6237a of the distal drive slot 6237 into an intermediate, or second, portion

6237b. As the pins 6243 and 6244 are both moved upwardly, the jaw 6240 can be rotated downwardly toward the tissue T into a closed position.

[0710] Further to the above, referring now to FIG. 127, the actuator 6235 can be pulled further proximally in order to push the second jaw 6240 downwardly toward the first jaw 6230, compress the cartridge body 6210, and engage the retention matrix 6250 and the plurality of protective caps 6270 with the staple legs of the staples 6220. For example, the additional proximal movement of the actuator 6235 can cause the sidewalls of the drive slots 6236 and 6237 to contact the pins 6243 and 6244, respectively, and drive the pins 6243 and 6244 downwardly toward the bottom ends of the slots 6233 and 6234, respectively. In such circumstances, the actuator 6235 can be pulled proximally such that, one, the distal pin 6243 exits the second portion 6236b of the drive slot 6236 and enters into an inclined third portion 6236c and, similarly, the proximal pin 6244 exits the second portion 6237b of the drive slot 6237 and enters into an inclined third portion 6237c. As the pins 6243 and 6244 are both moved downwardly, the second jaw 6240 can move downwardly toward the first jaw 6230 into a fired position. For example, the second jaw 6240 can be moved downwardly such that the retention matrix 6250 remains parallel, or at least substantially parallel, to the top surface of the cartridge body 6210 and/or parallel, or at least substantially parallel, to the alignment matrix 6260. In any event, once the retention matrix 6250 and the protective caps 6270 have been engaged with the staple legs 6221 of the staples 6220, as illustrated in FIG. 129, the second jaw 6240 can be returned to an open, or an at least substantially open, position. For example, the actuator 6235 can be pushed distally in order to drive the pins 6243 and 6244 to the top ends of the slots 6233 and 6234, respectively, and then driven downwardly toward the bottom ends of the slots 6233 and 6234 once the pins have passed through the intermediate portions 6236b and 6237b of the respective drive slots 6236 and 6237. Once the second jaw 6240 has been opened, the first jaw 6230 can be detached from the implanted staple cartridge 6200 and the first and second jaws 6230, 6240 can be removed away from the implanted fastener assembly, as illustrated in FIG. 128.

[0711] Referring to FIG. 127 once again, the reader will note that the pins 6243 and 6244 are not illustrated as being seated in the very bottoms of their respective slots 6233 and 6234 even though the retention matrix 6250 and the caps 6270 have been engaged with the staple legs 6221. Such circumstances can arise when thick tissue T is positioned between the retention matrix

6250 and the cartridge body 6210. In circumstances where thinner tissue T is positioned between the retention matrix 6250 and the cartridge body 6210, referring now to FIG. 130, the pins 6243 and 6244 can be drive further downwardly into their respective slots 6233 and 6234 as illustrated in FIG. 132. In general, for example, the actuator 6235 can be pulled proximally in order to drive the pins 6243 and 6244 upwardly and downwardly through the progressions described above and illustrated in FIGS. 130-132 and, owing to the thinner tissue T, the retention matrix 6250 and the protective caps 6270 can be driven further onto the staple legs 6221 of the staples 6220, as illustrated in FIGS. 133 and 134. As a result of the adjustability afforded by the retention matrix 6250, the same, or at least substantially the same, compressive pressure can be obtained in the fastened tissue regardless of whether the tissue captured within the end effector is thick or thin. The adjustability afforded by the retention matrix 6250 can allow a surgeon can select whether to apply a larger compressive pressure or a smaller compressive pressure to the tissue by selecting the depth to which the retention matrix 6250 is seated. For example, the range in which the retention matrix 6250 can be seated onto the staple legs 6221 can be determined by the lengths, or ranges, of the slots 6233 and 6234, for example.

[0712] As described above, the protective caps 6270 can be comprised of a soft or flexible material, for example, which can be configured to grip the ends of the staple legs 6221. The protective caps 6270 can be comprised of a bioabsorbable plastic, polyglycolic acid (PGA) which is marketed under the trade name Vicryl, polylactic acid (PLA or PLLA), polydioxanone (PDS), polyhydroxyalkanoate (PHA), poliglecaprone 25 (PGCL) which is marketed under the trade name Monocryl, polycaprolactone (PCL), and/or a composite of PGA, PLA, PDS, PHA, PGCL and/or PCL, for example, and/or a biocompatible metal, such as titanium and/or stainless steel, for example. As illustrated in FIG. 124, each cap 6270 can be unconnected to the other caps 6270. Alternatively, one or more caps 6270 can be mounted to the retention matrix 6250. For example, the caps 6270 can be connected to the retention matrix 6250 by at least one adhesive, for example, wherein the apertures 6271 in the caps 6270 can be aligned, or at least substantially aligned, with the retention apertures 6252 in the retention matrix 6270. Referring now to FIG. 135, a protective cap, such as a cap 6370, for example, can define an inner cavity, or dome, 6374 which can be configured to receive a tip of a staple leg 6221, for example, therein. For example, the cap 6370 can comprise a bottom 6372 and an aperture 6371 extending through the bottom 6372. The aperture 6371 can be defined by one or more deflectable members 6373

which can be configured to deflect when the staple leg 6221 is inserted therethrough. Two or more caps 6370, for example, can be connected together to form an array of caps 6370. For example, referring now to FIG. 136, a plurality of caps 6370 can be connected together by a sheet of material 6375. The sheet 6375 can be sufficiently rigid in order to maintain a desired arrangement and/or alignment of the caps 6370. The caps 6370 can be comprised of a biocompatible metal, such as titanium and/or stainless steel, for example, and the sheet 6375 can be comprised of a bioabsorbable plastic, polyglycolic acid (PGA) which is marketed under the trade name Vicryl, polylactic acid (PLA or PLLA), polydioxanone (PDS), polyhydroxyalkanoate (PHA), poliglecaprone 25 (PGCL) which is marketed under the trade name Monocryl, polycaprolactone (PCL), and/or a composite of PGA, PLA, PDS, PHA, PGCL and/or PCL, for example. A sheet 6375 can be comprised of a bioabsorbable material including an anti-microbial agent, such as colloidal silver and/or triclosan, for example, stored and/or dispersed therein which can be released as the sheet 6375 is bioabsorbed, for example.

[0713] Further to the above, the sheet 6375 can be injection molded around the caps 6370 utilizing an injection molding process, for example, such that the caps 6370 are embedded in the sheet 6375. Alternatively, the sheet 6375 can be molded utilizing an injection molding process, for example, wherein apertures 6376 can be formed in the sheet 6375 during the injection molding process and/or after the injection molding process utilizing a stamping process, for example. In either event, the caps 6370 can be inserted into and secured in the apertures 6376 utilizing a press-fit and/or snap-fit interconnection and/or at least one adhesive. Each cap 6370 can comprise an annular groove surrounding, or at least partially surrounding, the perimeter of the cap 6370 which can be configured to receive the perimeter of an aperture 6376 therein. The sheet 6375 can be comprised of a flexible and/or pliable material which can permit relative movement between the caps 6370. For example, the flexible sheet 6375 can be comprised of a rubber, plastic, and/or silicone material, for example, and the caps 6370 can be comprised of a rigid material, such as metal, for example. For example, similar to the above, the flexible material can be molded around the caps 6370. The caps 6370 can be pressed into a pre-molded sheet 6375, for example. The durometer of the flexible material can be selected to provide a desired stiffness of the sheet 6375. The sheet 6375 can be configured such that it comprises a flexible band. In any event, the sheet 6375 can facilitate the assembly of the caps 6370 into an end effector as a plurality of the caps 6370 can be positioned and/or aligned simultaneously

within the end effector. Furthermore, the sheet 6375 connecting the caps 6370, once implanted, can strengthen or bolster the tissue along the staple line, for example. In addition to or in lieu of a sheet connecting the caps 6370, the caps 6370 can be connected together by a plurality of links. For example, such links can be flexible and can permit relative movement between the caps 6370.

[0714] Referring now to FIGS. 139 and 140, a protective cap, such as cap 6470, for example, can comprise a forming surface which can be configured to deform a tip of a staple leg. For example, the cap 6470 can comprise a base 6472 which can include an aperture 6471 extending therethrough. The aperture 6471 can be configured to closely receive a staple leg, such as a staple leg 6221, for example, therein. The aperture 6471 can be defined by a diameter or perimeter which can be equal to or larger than the diameter or perimeter of the staple leg 6221. The cap 6470 can further comprise a cavity, or dome, 6474 which can be configured to receive the tip of the staple leg 6221 as it is inserted into the cap 6470. Referring primarily to FIG. 140, the cap 6470 can further comprise an anvil, or forming surface, 6473 which can be configured to deflect and deform the staple leg 6221. In various circumstances, the forming surface 6473 can be curved and/or concave, for example, and can be configured to curl the staple leg 6221 as it is inserted into the cap 6470. The staple leg 6221 can be sufficiently deformed such that it cannot be withdrawn through the aperture 6471 and, as a result, the cap 6470 can become locked to the staple leg 6221. For example, the base 6472 of the cap 6470 can define a lip extending around the aperture 6471 which can prevent the deformed staple leg 6221 from being removed from the cavity 6474. In various circumstances, as a result of the above, one or more caps 6470 can prevent, or inhibit, a retention matrix, such as retention matrix 6250, for example, from backing up or being disengaged from the staples 6220. Although not illustrated, the cap 6470 can be symmetrically, or at least substantially symmetrically, formed, and the aperture 6471 can be located along a central axis 6479 extending through the cap 6470. Alternatively, referring again to FIG. 139, the aperture 6471 can be offset with respect to the central axis 6479. For example, the offset aperture 6471 can allow the staple leg 6221 to contact a side of the forming surface 6473 and curl over to the other side of the forming surface 6473 instead of contacting the center of the forming surface 6473, as may occur in embodiments comprising a centered aperture 6471 mentioned above.

[0715] As discussed above, a retention matrix, such as retention matrix 6250, for example, can be comprised of a sheet of material and a plurality of retention apertures 6252 extending therethrough. The sheet of material comprising the retention matrix 6250 can be rigid or substantially inflexible. Alternatively, a retention matrix can be comprised of an array of retention matrix elements and a plurality of flexible connectors, or links, connecting the retention matrix elements. Referring now to FIG. 141, a retention matrix, or a portion of retention matrix, 6550 can comprise a plurality of element bodies 6505 which can be connected together by one or more connecting links 6507. Each element body 6505 can comprise a plurality of deformable members 6553 which define a retention aperture 6552 therein. The element bodies 6505 and the connecting links 6507 of a retention matrix 6550 can be integrally formed and can comprise a unitary piece of material. The retention matrix 6550 can be stamped or cast, for example, from a metal material, such as titanium and/or stainless steel, for example. The retention matrix 6550 can be comprised of plastic, such as polyetheretherketone (PEEK), polypropylene which is marketed under the trade name Prolene, polyester, polyethylene terephthalate which is marketed under the trade names Ethibond and Mersilene, polyvinylidene fluoride, polyvinylidene fluoride-co-hexafluoropropylene, poly hexafluoropropylene-VDF which is marketed under the trade name Pronova, and/or long-chain aliphatic polymers Nylon 6 and Nylon 6,6 which are marketed under the trade names Ethilon & Nurolon, for example, and can be formed by an injection molding process, for example. The element bodies 6505 may not be integrally formed with the connecting links 6507. A plurality of singular element bodies 6505 can be produced which are subsequently connected together and embedded in a retention matrix. For example, the element bodies 6505 can be stamped from a metal material, such as titanium and/or stainless steel, for example, and placed in a plastic injection mold wherein a plastic material can be injected into the mold to form, one, a rim 6506 of material surrounding, or at least partially surrounding, the element bodies 6505 and, two, connecting links 6507 extending from the rims 6506. Alternatively, one or more connector lattices can be formed comprising apertures defined within a plurality of rims 6506 wherein each such aperture can be configured to receive an element body 6505 therein. Each element body 6505 can comprise a circular, or at least substantially circular, outer perimeter and, similarly, each rim 6506 can define a circular, or at least substantially circular, aperture therein, wherein the diameter of the aperture can be equal to or smaller than the diameter of the element body 6505. For example, the element bodies 6505 can

be press-fit or embedded into the apertures in the rims 6505. The element bodies 6505 can be secured in the apertures utilizing at least one adhesive.

[0716] Further to the above, a retention matrix can comprise a plurality of element bodies 6505 and a plurality of connecting links 6507 which can connect the element bodies 6505 in any suitable array, such as those illustrated in FIGS. 142-145, for example. Regardless of the pattern of the array, the connecting links 6507 can be configured to allow the element bodies 6505 and the retention apertures 6552 to move relative to one another. For example, the lattice of element bodies 6505 and connecting links 6507 comprising the retention matrix 6550, once engaged with tissue, can be configured to stretch, twist, contract, and/or otherwise flex in order to permit at least some movement within the tissue yet, at the same time, resist larger movements thereof. Each connecting link 6507 can comprise a flexible member configured to stretch, twist, and/or contract in order to permit the retention matrix 6550 to flex intermediate the matrix retention elements 6505, for example. Referring again to FIG. 141, each link 6507 extending from a rim 6506 can be defined by a width which is narrower than the width of the element body 6505 and/or the rim 6506. Referring to FIGS. 142-145, one or more links 6507 can comprise straight portions which extend along a line between adjacent element bodies 6506, for example. For example, each link 6507 can comprise a first end attached to a first rim 6506 and a second end attached to a second rim 6506. Referring once again to FIG. 141, two or more links 6507 can be connected to one another. For example, two or more links 6507 can be connected at an intermediate hinge 6509, for example. The hinge 6509 can comprise a reduction in cross-sectional thickness in one or more directions as compared to the cross-sectional thickness of the links 6507 which can permit the connected links 6507 to move relative to each other, for example. The retention matrix 6550 can further comprise hinges 6508 which can connect the links 6507 to the rims 6506 and permit relative movement between the links 6507 and the rims 6506. Similar to hinges 6509, hinges 6508 can comprise a reduction in cross-sectional thickness in one or more directions as compared to the cross-sectional thickness of the links 6507, for example.

[0717] Further to the above, the connected links 6507 can extend in different directions. For example, a first link 6507 can extend in a first direction and a second link 6507 can extend in a second direction, wherein the first direction can be different than the second direction. The first link 6507 can extend along a first line and the second link 6507 can extend along a second line,

wherein the first line and the second line can intersect each other at an angle, such as approximately 30 degrees, approximately 45 degrees, approximately 60 degrees, and/or approximately 90 degrees, for example. The hinges 6508 and/or hinges 6509 can comprise living hinges which can permit the links 6507 to move relative to each other a number of times without breaking. The hinges 6508 and/or hinges 6509 can comprise frangible, or easily-breakable, portions which can break when flexed too far and/or flexed too many times. For example, such frangible portions can permit one or more portions of the retention matrix 6550 to break away from another portion of the retention matrix 6550. The hinges 6508 and/or hinges 6509, for example, can comprise sections of the retention matrix 6550 which are easier to incise than the other portions of the retention matrix 6550. More particularly, an implanted retention matrix, and the tissue fastened by the implanted retention matrix, may oftentimes by incised by a cutting member for various reasons and, in order to facilitate such cross-cutting, the hinges 6508 and/or hinges 6509 can provide avenues, or thin sections, through which a cutting member can more easily pass through the retention matrix 6550, for example. Further to the above, the connecting links 6507 can comprise one or more coined features or material upsets, for example, defined therein which can facilitate the bending, breakage, and/or incision of the connecting links 6507.

[0718] A retention matrix can comprise a plurality of retention matrix elements, such as matrix element bodies 6505, for example, which can be embedded in a flexible sheet, or band, of material. A flexible sheet of material can be formed from a bioabsorbable, elastomeric material, such as silicone, for example, wherein the flexible sheet can be produced with a plurality of apertures defined therein. For example, a solid flexible sheet can be molded and a plurality of apertures can be punched out of the flexible sheet. Alternatively, the flexible sheet can be molded and the apertures defined therein can be formed during the molding process. In either event, the retention matrix elements 6505, for example, can be inserted into and retained within the flexible sheet. Alternatively, similar to the above, the flexible sheet can be formed around the matrix elements 6505. The flexible sheet can be comprised of a woven mesh, for example, and/or any other suitable material. Such a woven mesh, further to the above, may be easy to cross-cut.

[0719] referring now to FIGS. 146 and 147, a fastener system comprising a retention matrix, such as retention matrix 6250, for example, can further comprise a cover, such as cover 6670, for example, which can cover the tips of the staple legs 6221 when they extend above the top surface 6257 of the retention matrix 6250. The cover 6670 can be attached to the retention matrix 6250.

The cover 6670 and/or the retention matrix 6250 can comprise retention features which can be configured to retain the cover 6670 to the retention matrix 6250. At least one adhesive can be utilized to adhere the cover 6670 to the retention matrix 6250. The cover 6670 can be comprised of a single layer, although the cover 6670 is illustrated as comprising two layers as described in greater detail further below. Referring primarily to FIG. 147, the tips of the staple legs 6221 can extend through a bottom surface 6673 of the cover 6670; however, the cover 6670 can comprise a sufficient thickness such that the staple tips do not extend through the top surface 6675 of the cover 6670. For example, as a result, the tips of the staple legs 6221 may not protrude from the cover 6670. The cover 6670 can comprise a plurality of layers. For example, the cover 6670 can comprise a first layer 6671 and a second layer 6672. The first layer 6671 and the second layer 6672 can be attached to one another wherein, the second layer 6672 can comprise a bottom surface 6676 which is adhered to the first layer 6671. The first layer 6671 and the second layer 6672 can comprise different thicknesses or they can comprise the same thickness. The first layer 6671 and the second layer 6672 can comprise substantially the same width and/or length. Alternatively, the layers 6671 and 6672 can comprise different widths and/or lengths.

[0720] Further to the above, the first layer 6671 can be comprised of a compressible foam, mesh material, and/or hydrogel, for example, which can be incised by the staple legs 6211. The second layer 6672 can be comprise of a tougher material, or skin, such as PGA and/or PDS, for example, and/or any suitable buttress material. For example, the staple legs 6221 can be configured to penetrate the first layer 6671; however, the staple legs 6221 may be unable to penetrate the second layer 6672. The second layer 6672 can be comprised of a material having a sufficient resiliency and/or toughness which can permit the second layer 6672 to be contacted and displaced by the staple leg 6221 but not be incised, or only marginally incised, by the staple tip of the staple leg 6221. Although not illustrated, a cover can comprise more than two layers wherein one or more of such layers may be penetration-resistant. In use, for example, the retention matrix 6250 can be positioned against the tissue to be fastened and pushed downwardly such that the staple legs 6221 of the staples 6220 are pushed through the tissue T and the retention apertures 6252 in the retention matrix 6250 and enter into the first layer 6271 of the cover 6270. The tips of the staple legs 6221 may not enter, or at least substantially enter, into the second layer 6272 of the cover 6270. After the retention matrix 6250 has been suitably positioned, the jaw 6240 can be opened and the cover 6670 and the retention matrix 6250 can

detach from the jaw 6240 as illustrated in FIG. 146. As illustrated in FIG. 146, a jaw 6640 can be configured to hold more than one retention matrix 6250 and cover 6670. For example, the jaw 6640 can comprise two channels 6679 which each can be configured to receive a cover 6670 therein and a retention matrix 6250 positioned thereover such that the tissue-contacting surface 6251 of each retention matrix 6250 depends downwardly from the bottom of the jaw 6240. For example, a retention matrix 6250 and a cover 6270 can be housed in the jaw 6640 on each side of a knife slot 6678. In use, both retention matrices 6250 and covers 6670 can be deployed simultaneously and/or to the same depth with respect to opposing staple cartridges, such as cartridges 6200, for example, positioned thereacross. Thereafter, the fastened tissue can be incised along a cutting line by a cutting member that traverses the knife slot 6678 wherein the jaw 6640 can then be re-opened. The covers 6670 may not be attached to the retention matrix 6250. For example, the covers 6670 can be positioned in the channels 6679 and can be retained in the channels 6679 by the retention matrices 6250 which can be secured to the jaw 6640. The each retention matrix 6250 can be wider and/or longer than their respective covers 6670 such that the retention matrices 6250 can retain the entirety of their covers 6670 in position. Each retention matrix 6250 can comprise the same width and/or length as their respective cover 6670, for example.

[0721] As described above, a fastener system can comprise a layer of material which can be attached to a retention matrix, such as retention matrix 6250, for example. Referring now to FIG. 150, a layer of material 6870 can be attached to the bottom surface 6251 of the retention matrix 6250. The layer 6870 and/or the retention matrix 6250 can comprise retention features which can be configured to retain the layer 6870 to the retention matrix 6250. At least one adhesive can be utilized to adhere the layer 6870 to the retention matrix 6250. In any event, the layer 6870 can comprise a bottom, or tissue-contacting, surface 6873 which can be configured to contact the tissue T when the retention matrix 6250 is moved downwardly toward the staples 6220 to engage the retention apertures 6252 with the staple legs 6221. For example, the layer 6870 can be comprised of a compressible material, such as a bioabsorbable foam, for example, which can be compressed between the bottom surface 6251 of the retention matrix 6250 and the tissue T. The layer 6870 can further comprise at least one medicament stored and/or absorbed therein which can be expressed from the layer 6870 as the layer 6870 is compressed. The medicament can comprise at least one tissue sealant, haemostatic agent, and/or anti-microbial material, such as

ionized silver and/or triclosan, for example. The compression of the layer 6870 can squeeze the medicament from the layer 6870 such that the entirety of, or at least a significant portion of, the surface of the tissue T is covered with the medicament. Furthermore, as the layer 6870 is compressed and the staple legs 6221 penetrate the tissue T and the layer 6870, the medicament can flow down the staple legs 6221 and treat the tissue that has just been incised by the staple legs 6221, for example. The body of the retention matrix 6250 can comprise a first layer which is comprised of a biocompatible material, such as titanium and/or stainless steel, for example, and the bottom layer 6870 can comprise a second layer comprised of a bioabsorbable material, such as oxidized regenerated cellulose (ORC), biologically active agents like fibrin and/or thrombin (either in their liquid state or freeze dried), glycerin, absorbable porcine gelatin in either flue or foam configurations, and/or anti-microbials, such as ionized silver and/or triclosan, for example. Additional bioabsorbable materials can comprise Surgicel Nu-Knit, Surgicel Fibrillar, collagen/ORC which is a hybrid with a built in collagen matrix and is marketed under the trade name Promogran, polyglycolic acid (PGA) which is marketed under the trade name Vicryl, polylactic acid (PLA or PLLA), polydioxanone (PDS), polyhydroxyalkanoate (PHA), poliglecaprone 25 (PGCL) which is marketed under the trade name Monocryl, polycaprolactone (PCL), and/or a composite of PGA, PLA, PDS, PHA, PGCL and/or PCL, for example. Although only one layer 6870 is illustrated in FIG. 150, any suitable number of layers could be used. A first layer comprising a first medicament could be attached to the retention matrix 6250 and a second layer comprising a second, or different, medicament could be attached to the first layer. For example, a plurality of layers could be used wherein each layer can comprise a different medicament and/or a different combination of medicaments contained therein.

[0722] Referring now to FIG. 148, a fastener system can comprise a layer of material 6770 attached to the bottom surface 6251 of the retention matrix 6250. The layer 6770 and/or the retention matrix 6250 can comprise retention features which can be configured to retain the layer 6770 to the retention matrix 6250. At least one adhesive can be utilized to adhere the layer 6770 to the retention matrix 6250. In any event, the layer 6770 can comprise a bottom, or tissue-contacting, surface 6773 which can be configured to contact the tissue T when the retention matrix 6250 is moved downwardly toward the staples 6220 to engage the retention apertures 6252 with the staple legs 6221. For example, the layer 6770 can be comprised of a compressible material, such as a bioabsorbable foam, for example, which can be compressed between the

surface 6251 of the retention matrix 6250 and the tissue T. The layer 6770 can further comprise one or more encapsulations, or cells, 6774 which can be configured to store at least one medicament therein. Referring to FIG. 149, the encapsulations 6774 can be aligned, or at least substantially aligned, with the retention apertures 6252 such that, when the staple legs 6221 are pushed through the tissue T and the layer 6770, the staple legs 6221 can puncture and/or otherwise rupture the encapsulations 6774. After the encapsulations 6774 have been ruptured, the at least one medicament M stored in the encapsulations 6774 can flow out onto the tissue T. For example, the medicament M can comprise a fluid which can flow or wick down the staple legs 6221 and treat the tissue T that was just incised by the staple legs. As a result of the above, the medicament stored within the encapsulations 6774 can provide a localized treatment to the tissue. The encapsulations 6774 in the sheet 6770 can comprise different medicaments stored therein. For example, a first group of encapsulations 6774 can comprise a first medicament, or a first combination of medicaments, stored therein and a second group of encapsulations can comprise a different medicament, or a different combination of medicaments, stored therein. The layer 6770 can be comprised of a flexible silicone sheet and the encapsulations 6774 can represent voids in the silicone sheet. For example, the silicone sheet can comprise two layers that can be attached to one another wherein the encapsulations 6774 can be defined between the two layers. The layer 6770 can comprise one or more thin sections or weakened portions, such as partial perforations, for example, which can facilitate the incision of the layer 6770 and the rupture of the encapsulations 6774 by the legs 6221. At least a portion of the encapsulations 6774 can be positioned within domes 6777, wherein the domes 6777 can extend upwardly from the sheet 6770. For example, the domes 6777 and/or at least a portion of the encapsulations 6774 can be positioned within the pockets 6201 formed within the retention matrix 6250. The encapsulations 6774 may comprise discrete cells which are unconnected to each other. Alternatively, one or more of the encapsulations 6774 can be in fluid communication with each other via one or more passageways, conduits, and/or channels, for example, extending through the layer 6770. The disclosure of U.S. Patent No. 7,780,685, entitled ADHESIVE AND MECHANICAL FASTENER, which issued on August 24, 2010, is hereby incorporated by reference in its entirety.

[0723] Further to the above, a staple cartridge comprising a cartridge body, staples, and/or an alignment matrix therein can be loaded into a first jaw of an end effector and, similarly, a

retention matrix and/or one or more covers can be loaded into a second jaw of the end effector. Referring now to FIG. 151, an instrument, such as cartridge loader 6990, for example, can be used to insert two or more fastener cartridges into an end effector at the same. The cartridge loader 6990 can comprise a handle 6991 and a cartridge carrier 6992, wherein the cartridge carrier 6992 can comprise a first retention portion configured to retain the cartridge body 6210 of the staple cartridge 6200 thereto and, in addition, a second retention portion configured to retain a cartridge body 6980 which supports, one, a plurality of protective caps 6270 therein and, two, a retention matrix 6250 along the bottom surface thereof, for example. The first and second retention portions can each comprise one or more retention members configured to releasably engage the cartridge bodies 6210 and 6980. In use, referring now to FIGS. 152 and 153, an end effector can comprise a first, or bottom, jaw 6230 and a second, or top, jaw 6940, wherein the staple cartridge 6200 can be loaded into the first jaw 6230 and the cartridge body 6980 can be loaded into the second jaw 6940. In various circumstances, the top jaw 6940 can be rotated from an open position (FIG. 152) to a closed position (FIG. 153) by an actuator 6235, wherein the operation of the actuator 6235 is described above and is not repeated herein for the sake of brevity. Once the top jaw 6940 is in its closed position, referring now to FIG. 153, the distal end 6993 of the cartridge carrier 6992 can be inserted into the end effector such that the staple cartridge 6200 is slid through the distal end 6938 of the first jaw 6930 and into a first attachment portion, or channel, 6939 in the first jaw 6230. Similarly, the distal end 6993 of the cartridge carrier 6992 can be inserted into the end effector such that the cartridge body 6980 is slid through the distal end 6948 of the second jaw 6940 and into a second attachment portion, or channel, 6949 in the second jaw 6940. A surgeon, or other clinician, holding the handle 6991 of the cartridge loader 6990 can push the staple cartridge 6200 and the cartridge body 6980 through the channels 6939 and 6949, respectively, until the staple cartridge 6200 and the cartridge body 6980 are fully seated therein.

[0724] As the staple cartridge 6200 and the cartridge body 6980 are being seated, the staple cartridge 6200 and the cartridge body 6980 can each engage one or more retention portions in their respective jaws 6230 and 6940, as described in greater detail further below. In any event, once the staple cartridge 6200 and the cartridge body 6980 have been seated, referring now to FIG. 154, the cartridge loader 6990 can be detached from the staple cartridge 6200 and the cartridge body 6980 and removed from the end effector. For example, the retention force holding

the staple cartridge 6200 in the first jaw 6230 can be greater than the retention force holding the staple cartridge 6200 to the cartridge carrier 6992 such that, as the cartridge carrier 6992 is pulled distally out of the end effector, the staple cartridge 6200 can remain behind in the first jaw 6230. Similarly, the retention force holding the cartridge body 6980 in the second jaw 6940 can be greater than the retention force holding the cartridge body 6940 to the cartridge carrier 6992 such that, as the cartridge carrier 6992 is pulled distally out of the end effector, the cartridge body 6940 can remain behind in the second jaw 6940. Once the cartridge loader 6990 has been removed from the end effector, the loaded first jaw 6230 and the loaded second jaw 6940 can be positioned relative to the tissue T that is to be stapled. Referring now to FIG. 155, the second jaw 6940 can be moved from an open position (FIG. 154) to a fired position (FIG. 155) in order to engage the retention matrix 6250 and the plurality of protective caps 6270 carried by the cartridge body 6980 with the staples 6220 positioned within the staple cartridge 6200.

[0725] Referring now to FIGS. 156 and 157, the second jaw 6940 can be re-opened and the plurality of protective caps 6270 and the retention matrix 6250 can detach from the cartridge body 6980 such that the caps 6270 and the retention matrix 6250 can remain engaged with the tissue T and the staple cartridge 6200. The cartridge body 6980 can comprise a plurality of pockets in which the plurality of caps 6270 can be removably positioned and one or more retention slots configured to removably retain the retention matrix 6250 thereto. The retention members of the second jaw 6940 engaged with the cartridge body 6980 can retain the cartridge body 6980 in the second jaw 6940 after the second jaw 6940 has been opened. The cartridge body 6980 can be configured to tear as the second jaw 6940 is opened such that a portion of the cartridge body 6980 is implanted with the caps 6270 and the retention matrix 6250 and a portion of the cartridge body 6980 remains in the second jaw 6940. Similarly, referring again to FIGS. 156 and 157, the retention members of the first jaw 6230 engaged with the cartridge body 6210 can retain the cartridge body 6210 in the first jaw 6230 after the second jaw 6940 has been opened. The cartridge body 6210 can be configured to tear as the first jaw 6230 is pulled away from the implanted cartridge 6200 such that a portion of the cartridge body 6210 is implanted with the staples 6220 and alignment matrix 6260 and a portion of the cartridge body 6210 remains in the first jaw 6230. Referring now to FIGS. 158-160, a staple cartridge, such as staple cartridge 6900, for example, can comprise one or more longitudinal retention slots 6913 extending along the length of the cartridge body 6910 which, when the staple cartridge 6900 is

inserted into a jaw 6930, for example, can be configured to receive one or more longitudinal retention rails 6916 extending from the jaw 6930 therein. In use, an end of the retention slots 6913 can be aligned with the distal ends of the retention rails 6916 before the staple cartridge 6900 is slid through the distal end 6938 of the retention channel 6939, for example.

[0726] Referring again to FIG. 160, the jaw 6940 can comprise two retention channels 6949, wherein each retention channel 6949 can be configured to receive a cartridge body 6980 comprising a plurality of caps 6270 and a retention matrix 6250 therein. Each cartridge body 6980 can comprise one or more longitudinal retention shoulders 6917 which can be configured to be slid along one or more longitudinal retention rails 6918 of the second jaw 6940 as the cartridge bodies 6980 are inserted into their respective retention channels 6949 in jaw 6940. The retention rails 6918 and the retention shoulders 6917 can co-operate to retain the cartridge body 6980 in the second jaw 6940 as the cartridge bodies 6980 are detached from the caps 6270 and the retention matrix 6250 stored therein. Referring now to FIG. 159, the second jaw 6940 can further comprise one or more distal bumps, or retention members, 6915 extending therefrom which can be configured to removably lock the cartridge bodies 6980 in their respective retention channels. For example, the second jaw 6940 can comprise a distal bump 6915 configured and positioned relative to each retention channel 6949 such that each cartridge body 6980 can flex around the bumps 6915 as the cartridge bodies 6980 are being inserted into the channels 6949 wherein, just as the cartridge bodies 6915 are being fully seated in the channels 6949, the distal ends of the cartridge bodies 6980 can clear and snap over the bumps 6915. In order to remove the cartridge bodies 6980 after they have been expended, as described above, the cartridge bodies 6980 can be pulled back over the bumps 6915 and removed from the retention channels 6949. Similar to the above, the first jaw 6930 can comprise one or more distal retention bumps 6914 extending therefrom which can be configured to be received in one or more retention grooves, or slots, 6912 (FIG. 158) in the cartridge body 6910 when the staple cartridge 6900 has been fully seated.

[0727] Further to the above, a first fastener cartridge comprising a plurality of first fasteners positioned therein can be positioned in a first jaw of a surgical fastening device and a second fastener cartridge comprising a plurality of second fasteners positioned therein can be positioned in a second jaw of the surgical fastening device. In use, the first jaw and/or the second jaw can be moved toward the other in order to engage the first fasteners with the second fasteners and secure

tissue therebetween. The first fastener cartridge and the second fastener cartridge can be engaged with each other as the first fasteners are engaged with the second fasteners. The body of the first fastener cartridge can be comprised of a first compressible material and the body of the second fastener cartridge can be comprised of a second compressible material, wherein the first body and/or the second body can be compressed against the tissue being fastened. After the tissue has been fastened, the first jaw can be moved away from the implanted first fastener cartridge and the second jaw can be moved away from the implanted second fastener cartridge. Thereafter, the first jaw can be reloaded with another first fastener cartridge, or the like, and the second jaw can be reloaded with another second fastener cartridge, or the like, and the surgical fastening instrument can be reused. While staples can be used in some embodiments, other embodiments are envisioned comprising other types of fasteners, such as two-part fasteners which are locked together when they are engaged with one another, for example. For example, the first fastener cartridge can comprise a first storage portion for storing the first fastener portions and the second fastener cartridge can comprise a second storage portion for storing the second fastener portions. The fastening systems described herein can utilize fasteners comprising any suitable type of material and/or form. The fasteners can comprise penetrating members. Such penetrating members could be comprised of a polymer, a composite, and/or a multi-layered substrate, for example. An example of a multi-layered substrate could be a wire or a sheet substrate with an elastomeric or polymeric coating. It could be a thin sheet formed such that penetrating members are oriented perpendicular, or at least substantially perpendicular, to the connecting member. The penetrating members could comprise a rectangular profile, semi-circular profile, and/or any beam profile. The fasteners described herein can be manufactured utilizing any suitable process, such as a wire extruding process, for example. Another possibility is the use of microfabrication to create hollow penetrating members. These penetrating members could be fabricated from a process which is different than a wire extruded process and could use a combination of materials.

[0728] As described above, the tips of staple legs protruding through a retention matrix can be covered by one or more caps and/or covers. The tips of the staple legs can be deformed after they have been inserted through the retention matrix. A jaw holding the retention matrix can further comprise anvil pockets positioned above and/or aligned with the retention apertures which can be configured to deform the staple legs as they protrude above the retention matrix. The staple legs of each staple can be curled inwardly toward each other and/or toward the center of the

staple, for example. Alternatively, one or more of the staple legs of a staple can be curled outwardly away from the other staple legs and/or away from the center of the staple. Regardless of the direction in which the staple legs are curled, the tips of the staple legs can contact the body of the retention matrix and may not re-enter the tissue that has been fastened by the staples. The deformation of the staple legs after they have passed through the retention matrix can lock the retention matrix in position.

[0729] Referring now to FIGS. 161 and 162, a surgical stapling instrument, such as surgical stapler 7000, for example, can comprise a first jaw 7030 and a second jaw 7040, wherein the second jaw 7040 can be moved toward and away from the first jaw 7030 by the movement of actuator 6235. The operation of actuator 6235 is described above and is not repeated herein for the sake of brevity. The first jaw 7030 can comprise a distal end 7031 and a proximal end 7032, wherein the first jaw 7030 can define a channel extending between the distal end 7031 and the proximal end 7032 which is configured to receive a staple cartridge. For the purposes of illustration, the cartridge body of such a staple cartridge is not depicted in FIG. 161, although such a staple cartridge can comprise a cartridge body, staples 6220 positioned within the cartridge body, and staple drivers 7012 positioned underneath the staples 6220. Although not illustrated in FIG. 161 for the sake of clarity, the second jaw 7040 can be configured to hold a retention matrix, such as retention matrix 6250, for example, over the staples 6220 and/or move the retention matrix into engagement with the legs of the staples 6220 as described above. The surgical stapler 7000 can further comprise a sled 7010 positioned in the first jaw 7030 which can be slid from the distal end 7031 of the first jaw 7030 toward the proximal end 7032, for example, and lift the staple drivers 7012, and the staple 6220 supported thereon, toward the retention matrix and the second jaw 7040. Alternatively, the sled 7010 can be moved from the proximal end 7032 toward the distal end 7031 in order to deploy the staples 6020, for example. The sled 7010 can comprise one or more inclined ramps, or cams, 7011 which can be configured to slide underneath the staple drivers 7012 and lift the staple drivers 7012 upwardly. The surgical stapler 7000 can further comprise a pull, or push, rod operably coupled to the sled 7010 which can be moved proximally and/or distally by an actuator located on a handle and/or shaft of the surgical stapler 7000, for example.

[0730] Referring again to FIG. 161, the second jaw 7040 of the surgical stapler 7000 can comprise a frame 7041, a distal end 7048, and a proximal end 7049 positioned opposite the distal

end 7048. The second jaw 7040 can further comprise a guide system comprising one or more guide rails, such as guide rails 7045 and 7046, for example, extending along the longitudinal axis of the frame 7041 which, as described in greater detail further below, can be configured to guide one or more anvils, or cams, which can engage and deform the staple legs of the staples 6220 after the staple legs 6221 of the staples 6220 have passed through the retention matrix. For example, the guide rails 7045 and 7046 can comprise a guide wire or cable which extends along a top portion or surface of the frame 7041, around a distal post 7047, and back along the top portion or surface of the frame 7041, for example. As mentioned above and referring primarily now to FIGS. 163 and 165, the second jaw 7040 can further comprise one or more anvils, or cams, such as first anvil 7050 and second anvil 7060, for example, which can be moved longitudinally along the second jaw 7040 in order to deform the legs of the staples 6220 after they have passed through the retention matrix. The surgical stapler 7000 can further comprise a first anvil driver, or actuator, 7051 connected to and/or operably coupled to the first anvil 7050 which can be configured to pull the first anvil 7050 proximally and/or push the first anvil 7050 distally. Similarly, the surgical stapler 7000 can further comprise a second anvil driver, or actuator, connected to and/or operably coupled to the second anvil 7060 which can be configured to push the second anvil 7060 distally and/or pull the second anvil 7060 proximally. The first anvil 7050 can comprise guide slots 7052 and the second anvil 7060 can comprise guide slots 7062 which can each be configured to slidably receive guide rail 7045 or guide rail 7046 therein. For example, the guide rails 7045 and 7046 can be closely received within the guide slots 7052 and 7062 such that relative lateral, or side-to-side, movement therebetween can be prevented, or at least limited.

[0731] Further to the above, the first anvil 7050 can be pulled proximally and the second anvil 7060 can be pulled distally. Referring to FIG. 161, the guide rails 7045 and 7046 and the distal post 7047 can comprise a pulley system configured to pull the second anvil 7060 distally and/or pull the second anvil 7060 proximally. For example, the guide rail 7045 and the guide rail 7046 can comprise a continuous wire or cable extending around the distal post 7047, wherein a portion of the continuous wire can be pulled in order to cycle the wire around the distal post 7047. The guide rail 7046, for example, can be mounted to the second anvil 7060 such that, when the continuous cable is cycled in a first direction, the second anvil 7060 can be pulled distally toward the distal end 7048 of the jaw 7040 and, when the continuous cable is cycled in a second, or

opposite, direction, the second anvil 7060 can be pulled proximally toward the proximal end 7049. Referring now to FIG. 163, the guide rail 7046 can be secured within a guide slot 7062 such that a pulling force can be transmitted therebetween. For example, the guide rail 7045 can be configured to slide within the other guide slot 7062. The first anvil 7050 may operate independently of the second anvil 7060 and the pulley system and the guide slots 7052 defined in the first anvil 7050 may be configured to slidably receive the guide rails 7045 and 7046 such that relative movement is permitted therebetween. The continuous cable comprising guide rails 7045 and 7046 can be sufficiently flexible in order to accommodate the opening and closing of the top jaw 7040. The continuous cable can also be sufficiently flexible in order to accommodate the vertical movement of the second anvil 7060 toward and away from the bottom jaw 7030, which is described in greater detail further below.

[0732] Referring again to FIGS. 163 and 165, the first anvil 7050 can comprise cam followers 7055 extending therefrom which can be configured to ride in one or more cam slots, or guide slots, such as cam slot 7070 (FIG. 166), for example, defined in the frame 7041 of the second jaw 7040. More particularly, the frame 7041 can comprise a first cam slot 7070 extending longitudinally along a first side of the frame 7041 and a second cam 7070 extending longitudinally along a second, or opposite, side of the frame 7041, wherein the cam followers 7055 extending from a first side of the first anvil 7050 can ride in the first cam slot 7070 and the cam followers 7055 extending from a second side of the first anvil 7050 can ride in the second cam slot 7070. For example, the contours of each cam slot 7070 can be identical, or at least substantially identical, and can be aligned, or at least substantially aligned, with one another. Similarly, the second anvil 7060 can comprise cam followers 7065 extending therefrom which can be configured to ride in the cam slots 7070 (FIG. 166) defined in the frame 7041 of the second jaw 7040. More particularly, the cam followers 7065 extending from a first side of the second anvil 7060 can ride in the first cam slot 7070 and the cam followers 7065 extending from a second side of the second anvil 7060 can ride in the second cam slot 7070. In use, the cam followers 7055 of the first anvil 7050 and the cam followers 7065 of the second anvil 7060 can slide within the cam slots 7070 such that first anvil 7050 and the second anvil 7060 follow the contours of the cam slots 7070 as the first anvil 7050 and the second anvil 7060 are pulled proximally and/or pushed distally. Each cam slot 7070 can comprise a plurality of dwell, or upper, portions 7071 and a plurality of driver, or lower, portions 7072 which can be configured

to move the anvils 7050 and 7060 vertically, i.e., toward and away from the bottom jaw 7030, at the same time that the anvils 7050 and 7060 are being moved longitudinally, i.e., between the distal end 7048 and the proximal end 7049 of the frame 7041, as described in greater detail further below.

[0733] When the surgical stapler 7000 is in an unfired condition, referring to FIG. 166, the first anvil 7050 can be positioned at the distal end 7048 of the frame 7041 and the second anvil 7060 can be positioned at the proximal end 7049 of the frame 7041; furthermore, referring now to FIG. 167, the staples 6220 positioned in the first jaw 7030 may not yet be inserted into the tissue T and/or the retention matrix positioned thereabove when the surgical stapler 7000 is in an unfired condition. In use, referring now to FIG. 168, the staples 6220 can be driven upwardly within the staple cavities 7033 of a staple cartridge by the staple drivers 7012 and, in addition, the first anvil 7050 can be moved proximally from the distal end 7048 of the frame 7041 toward the distal end 7049 in order to engage the staple legs 6221 of the staples 6220. The staples 6220 can be driven upwardly before the first anvil 7050 is engaged with the staple legs 6221 thereof. All of the staples 6220 may be deployed upwardly by the sled 7010 before the first anvil 7050 is advanced into contact with the staple legs 6221 or, alternatively, the sled 7010 may be moved proximally at the same time that the first anvil 7050 is moved proximally, although the sled 7010 may sufficiently lead the first anvil 7050 in order to deploy the staples 6220 ahead of the first anvil 7050. As illustrated in FIG. 168, the cam slots 7070 can be configured and arranged such that the forming surfaces, such as forming, or camming, surfaces 7053 and 7054, for example, of the first cam 7050 can contact at least some of the staple legs 6221 when the first cam 7050 is passing through a dwell, or upper, position. In various circumstances, the cam followers 7055 of the first anvil 7050 can each be positioned in a dwell portion 7071 of the cam slots 7070 such that the forming surfaces 7053 and 7054 are in a raised position and such that the staple legs 6221 are only partially deformed when the anvil 7050 passes thereby in the dwell position. As the first cam 7050 is moved further along the cam slots 7070, as illustrated in FIG. 169, the cam followers 7055 of the first anvil 7050 can be driven into driven, or lower, portions 7072 of the cam slots 7070 such that the forming surfaces 7053 and 7054 are moved vertically downwardly toward the staple legs 6021 in order to drive the staple legs 6021 into their finally formed configurations. Thereafter, as the first anvil 7050 is progressed further along the cam slots 7070, the first anvil 7050 can be driven vertically upwardly into another set of dwell portions 7071 of

the cam slots 7070. As illustrated in FIGS. 168 and 169, the reader will note that the first anvil 7050 may only engage some of the staple legs and not others. For example, the first anvil 7050 can be configured to only deform a group of staple legs comprising the distal staple legs 6221 of the staples 6220, for example. For example, the first anvil 7050 can be configured to deform the distal staple legs 6221 toward the center of the staples 6220. Each proximal staple leg 6221 can be contacted twice by the first anvil 7050, i.e., by a first forming surface 7053 and by a second forming surface 7054 aligned with the first forming surface 7053. For example, the first forming surfaces 7053 can deform the distal staple legs 6221 into a partially-deformed configuration when the first anvil 7050 is in a dwell, or upper, position and the second forming surfaces 7054 can deform the distal staple legs 6221 into a fully-formed configuration when the first anvil 7050 is moved into a driven, or lower, position. Referring now to FIGS. 163 and 164, the first anvil 7050 can comprise a plurality of first forming surfaces 7053 and a plurality of second forming surfaces 7054 in order to deform the distal staple legs 6221 of staples 6220 when the staple legs 6221 are arranged in more than one row or line. As described in greater detail further below, the proximal staple legs 6221 of the staples 6020 can be deformed by the second anvil 7060, for example.

[0734] Further to the above, the first anvil 7050 can be moved from the distal end 7048 of the frame 7041 to the proximal end 7049 in order to deform all of the distal staple legs 6221 of the staples 6220. As the reader will note, the first anvil 7050 can be moved up and down relative to the undeformed proximal staple legs 6221 and, in order to accommodate such relative movement, the first anvil 7050 can comprise one or more clearance slots 7057 (FIG. 165) which can be configured to receive the unbent proximal staple legs 6221 as the first anvil 7050 bends the distal staple legs 6221. Similarly, referring again to FIG. 163, the second anvil 7060 can comprise a clearance slot 7067 which can be configured to accommodate the vertical movement of the first cam actuator 7051 which moves up and down as the first anvil 7050 is moved between its dwell and driven positions as described above. After all of the distal staple legs 6221 have been bent, the second anvil 7060 can be moved from the proximal end 7049 of the frame 7041 to the distal end 7048 by the anvil actuator 7061. Similar to the above, referring now to FIG. 170, the cam followers 7065 of the second anvil 7060 can slide within the cam slots 7070 such that the second anvil 7060 is moved between dwell, or upper, positions and driven, or lower, positions in order to deform the proximal staple legs 6221 inwardly toward the centers of

the staples 6220, for example. Similar to the above, the second anvil 7060 can comprise a plurality of first forming, or camming, surfaces 7063 and a plurality of second forming, or camming, surfaces 7064 which can each be configured to at least partially deform and/or completely deform one or more of the proximal staple legs 6021. Referring again to FIG. 164, the second anvil 7060 can comprise a plurality of first forming surface 7063 and a plurality of second forming surfaces 7064 which can be configured to deform the proximal staple legs 6221 of staples 6220 arranged in a plurality of rows, or lines, for example. As also illustrated in FIG. 164, the first forming surfaces 7063 and the second forming surfaces 7064 of the second anvil 7060 may not be aligned with the first forming surfaces 7053 and the second forming surfaces 7054 of the first anvil 7050 wherein, as a result, the proximal legs 6221 of the staples 6220 may be positioned in different rows, or lines, than the distal legs 6221 of the staples 6220. As the reader will also note, the second anvil 7060 can push the first anvil 7050 as the second anvil 7060 is moved distally. For example, the second anvil 7060 can push the first anvil 7050 back into the distal end 7048 of the frame 7041 such that the first anvil 7050 can be returned to its initial, or unfired, position. After all of the proximal staple legs 6221 of the staples 6220 have been deformed, the second anvil 7060 can be retracted proximally and returned to its initial, or unfired, position. In this way, the surgical stapler 7000 can be reset such that a new staple cartridge can be positioned in the first jaw 7030 and a new retention matrix can be positioned in the second jaw 7040 in order to use the surgical stapler 7000 once again.

[0735] As described above, a surgical stapler can comprise two or more anvils which can travel longitudinally in order to engage the legs of a plurality of staples in a transverse direction. A surgical stapler can comprise an anvil which is moved proximally, for example, in order to deform a first group of staple legs and distally, for example, in order to deform a second group of staple legs. For example, such an anvil can comprise forming surfaces facing proximally and forming surfaces facing distally, for example.

[0736] Referring now to FIG. 171, an anvil, such as anvil 7140, for example, can comprise a bottom, or tissue-contacting, surface 7141 and a plurality of forming pockets 7142 defined therein. The anvil 7140 can comprise more than one plate, such as pocket plates 7143, for example, which can be welded into a frame 7144. For example, each pocket plate 7143 can be positioned in a plate channel 7145 in the frame 7144 and welded to the frame 7144 through a weld slot 7146 extending through the frame 7144 in order to form a longitudinal weld 7147. In

various circumstances, the longitudinal weld 7147 can comprise a continuous weld extending along the entire length of the weld slot 7146 or a series of spaced-apart spot welds extending along the length thereof, for example. Each pocket plate 7143 can comprise two or more plate portions that have been welded together. For example, each pocket plate 7143 can comprise a first plate portion 7143a and a second plate portion 7143b which can be welded together along a seam 7148. The first plate portion 7143a and the second plate portion 7143b of each plate 7143 can be welded together before the plates 7143 are welded into the plate channels 7145 in the frame 7144. For example, the first plate portion 7143a and the second plate portion 7143b can comprise co-operating profiles, such as the toothed profiles illustrated in FIG. 171, for example, which can be fitted together to form a tight seam 7148. Each plate 7143 can comprise a height of approximately .02", for example, which can be taller than the depth of the plate channels 7145 such that the tissue-contacting surfaces 7141 thereof extend from the frame 7044 of the anvil 7040. Referring now to FIG. 172, the plates 7143 can be connected together by at least one weld 7149 at the distal ends of the plates 7143, for example.

[0737] As illustrated in FIGS. 171 and 172, each pocket plate 7143 can comprise a plurality of forming pockets 7142 defined therein. The forming pockets 7142 can be formed in the plates 7143 by any suitable manufacturing process, such as a grinding process and/or electrode-burning process, for example. For example, referring now to FIGS. 173 and 174, each forming pocket 7142 can be manufactured by first forming a deep well 7150, then forming an arcuate or curved surface 7151 surrounding the deep well 7150, and then forming a staple leg guide groove 7152 in the curved surface 7151, for example. Alternatively, these steps can be performed in any suitable order. Referring now to FIG. 175, the staple forming pockets 7142 can be formed such that the inner edges 7153 of the forming pockets are separated by a consistent, or at least substantially consistent, gap 7154. For example, the gap 7154 can be approximately .008", for example. Furthermore, for example, the forming pockets 7142 can be positioned along two or more rows, or lines, the centerlines of which can be separated by a consistent, or at least substantially consistent, spacing 7155. For example, the spacing 7155 between the centerlines can be approximately .035", for example. Referring again to FIG. 175, each forming pocket 7142 can taper between a narrow width 7156 and a wide width 7157. For example, the narrow width 7156 can be approximately .045" and the wide width 7157 can be approximately .075", for example. The plates 7143 can be comprised of the same material as the frame 7144. For example, the

plates 7143 and the frame 7144 can both be comprised of stainless steel, such as a 300 series or a 400 series stainless steel, for example, and/or titanium, for example. Alternatively, the plates 7143 and the frame 7144 can be comprised of different materials. For example, the plates 7143 can be comprised of a ceramic material, for example, and the frame 7144 can be comprised of a stainless steel and/or titanium, for example. In various circumstances, depending on the materials used, at least one brazing process could be used to secure the plates 7143 in the frame 7144 in addition to or in lieu of the welding processes described above, for example.

[0738] Referring now to FIGS. 176-178, an anvil 7240 can comprise a frame 7244 and a plurality of pocket plates 7243 which can be inserted into the frame 7244. Similar to the above, each pocket plate 7243 can comprise a plurality of forming pockets 7242 defined therein. The anvil frame 7244 can comprise retention slots 7246 defined therein which can each be configured to receive a retention rail 7247 extending from a pocket plate 7243. In order to assemble the pocket plates 7243 to the anvil frame 7244, the side walls 7245 of the anvil frame 7244 can be flexed or splayed outwardly, as illustrated in FIG. 177, in order to widen the retention slots 7246 such that each retention slot 7246 can receive a retention rail 7247 of a pocket plate 7243 therein. Once the retention rails 7247 have been positioned in the retention slots 7246, the side walls 7245 can be released, as illustrated in FIG. 178, thereby allowing the frame 7244 to resiliently contract and/or return to its unflexed state. In such circumstances, the retention slots 7246 can contract and thereby capture the retention rails 7247 therein. The retention rails 7247 and/or the retention slots 7246 can comprise one or more co-operating tapered surfaces which, after the flexed retention slots 7246 have been released, can form a taper-lock engagement which can retain the retention rails 7247 in the retention slots 7246. Similar to the above, the pocket plates 7243 can be comprised of the same material as or a different material than the frame 7244. For example, the plates 7243 can be comprised of a ceramic material, for example, and the frame 7244 can be comprised of a stainless steel and/or titanium, for example. In various circumstances, depending on the materials used, at least one brazing process and/or at least one welding process, for example, could be used to secure the plates 7243 in the frame 7244.

[0739] In FIGS. 179 and 180, a surgical stapling and severing instrument 8010 can comprise an anvil 8014 which may be repeatably opened and closed about its pivotal attachment to an elongate staple channel 8016. A staple applying assembly 8012 can comprise the anvil 8014 and the channel 8016, wherein the assembly 8012 can be proximally attached to the elongate shaft

8018 forming an implement portion 8022. When the staple applying assembly 8012 is closed, or at least substantially closed, the implement portion 8022 can present a sufficiently small cross-section suitable for inserting the staple applying assembly 8012 through a trocar. The assembly 8012 can be manipulated by a handle 8020 connected to the shaft 8018. The handle 8020 can comprise user controls such as a rotation knob 8030 that rotates the elongate shaft 8018 and staple applying assembly 8012 about a longitudinal axis of the shaft 8018. A closure trigger 8026, which can pivot in front of a pistol grip 8036 about a closure trigger pin 8152 (FIG. 181) engaged laterally across the handle housing 8154, can be depressed to close the staple applying assembly 8012. A closure release button 8038 can be outwardly presented on the handle 8020 when the closure trigger 8026 is clamped such that the release button 8038 can be depressed to unclamp the closure trigger 8026 and open the staple applying assembly 8012, as described in greater detail below. A firing trigger 8034, which can pivot in front of the closure trigger 8026, can cause the staple applying assembly 8012 to simultaneously sever and staple tissue clamped therein. In various circumstances, as described in greater detail below, multiple firing strokes can be employed using the firing trigger 8034 to reduce the amount of force required to be applied by the surgeon's hand per stroke. The handle 8020 can comprise rotatable right and/or left indicator wheels 8040, 8041 (FIG. 181) which can indicate the firing progress. For instance, full firing travel may require three full firing strokes of firing trigger 8034 and thus the indicator wheels 8040, 8041 can rotate up to one-third of a revolution each per stroke of firing trigger 8034. As described in greater detail below, a manual firing release lever 8042 can allow the firing system to be retracted before full firing travel has been completed, if desired, and, in addition, the firing release lever 8042 can allow a surgeon, or other clinician, to retract the firing system in the event that the firing system binds and/or fails.

[0740] With reference to FIGS. 179 and 181, the elongate shaft 8018 can comprise an outer structure including a longitudinally reciprocating closure tube 8024 that pivots the anvil 8014 toward its close position in response to the proximal depression of the closure trigger 8026 of handle 8020. The elongate channel 8018 can be connected to the handle 8020 by a frame 8028 (FIG. 181) that is internal to the closure tube 8024. The frame 8028 can be rotatably engaged to the handle 8020 so that the rotation of the rotation knob 8030 (FIG. 179) can rotate the implement portion 8022. With particular reference to FIG. 181, the rotation knob 8030 can be comprised of two half-shells which can include one or more inward projections 8031 that can

extend through one or more elongate side openings 8070 in the closure tube 8024 and engage the frame 8028. As a result of the above, the rotation knob 8030 and the frame 8028 can be rotated together, or synchronously, such that the rotated position of knob 8030 determines the rotated position of the implement portion 8022. The longitudinal length of the longer opening 8070 is sufficiently long to allow the longitudinal closure motion, and opening motion, of the closure tube 8024. With regard to generating the closure motion of closure tube 8024, referring primarily to FIGS. 181 and 183, an upper portion 8160 of the closure trigger 8026 can push forward a closure yoke 8162 via a closure link 8164. The closure link 8164 is pivotally attached at its distal end by a closure yoke pin 8166 to the closure yoke 8162 and is pivotally attached at its proximal end by a closure link pin 8168. The closure trigger 8026 can be urged to an open position by a closure trigger tension spring 8246 that is connected proximally to the upper portion 8160 of the closure trigger 8026 and a handle housing 8154 formed by right and left half shells 8156, 8158. The tension force applied by the tension spring 8246 can be overcome by a closing force applied to the closure trigger 8026 in order to advance the yoke 8162, closure link 8164, and the closure tube 8024 distally.

[0741] As the closure trigger 8026 is actuated, or depressed, as described above, the closure release button 8038 can be positioned such that the surgeon, or other clinician, can push the closure release button 8038, if desired, and allow the closure trigger 8026, and the rest of the surgical instrument, to return to an unactuated state. The closure release button 8038 can be connected to a pivoting locking arm 8172 by a central lateral pivot 8173 such that motion can be transferred between the release button 8038 and the locking arm 8172. Referring again to FIG. 181, a compression spring 8174 can bias the closure release button 8038 proximally, i.e., clockwise about the central lateral pivot 8173 as viewed from the right and the upper portion 8160 of the closure trigger 8026 can include a proximal crest 8170 with an aft notch 8171. As the closure trigger 8026 is depressed, the pivoting locking arm 8172 can ride upon the proximal crest 8170 and when the closure trigger 8026 reaches its fully depressed position, it should be appreciated that the aft notch 8171 is presented below the pivoting locking arm 8172 which drops into and locks against the aft notch 8171 under the urging of the compression spring 8174. At such point, manual depression of the closure release button 8038 rotates the pivoting locking arm 8172 upward and out of aft notch 8171 thereby unlocking the closure trigger 8026 and allowing the closure trigger 8026 to be returned to its unclamped position.

[0742] Once the closure trigger 8026 is proximally clamped, as discussed above, the firing trigger 8034 can be drawn toward the pistol grip 8036 in order to advance a firing rod 8032 distally from the handle 8020. The firing trigger 8034 can pivot about a firing trigger pin 8202 that laterally traverses and is engaged with the right and left half shells 8156, 8158 of the handle 8020. The firing trigger 8034, when actuated, can advance a linked transmission firing mechanism 8150. The linked transmission firing mechanism 8150 can be urged into a retracted, unfired, position by a spring 8184 that is, one, attached to the pistol grip 8036 of the handle 8020 and, two, attached to one of the links, for example, of the linked transmission firing mechanism 8150 as described in greater detail below. The spring 8184 can comprise a nonmoving end 8186 connected to the housing 8154 and a moving end 8188 connected to a proximal end 8190 of a steel band 8192. A distally-disposed end 8194 of the steel band 8192 can be attached to an attachment feature 8195 on a front link 8196a of a plurality of links 8196a -8196d that form a linked rack 8200. Linked rack 8200 can be flexible such that it can readily retract into the pistol grip 8036 and minimize the length of the handle 8020 and yet form a straight rigid rack assembly that may transfer a significant firing force to and/or through the firing rod 8032. As described in greater detail below, the firing trigger 8034 can be engaged with a first link 8196a during a first actuation of the firing trigger 8034, engaged with a second link 8196b during a second actuation of the firing trigger 8034, engaged with a third link 8196c during a third actuation of the firing trigger 8034, and engaged with a fourth link 8196d during a fourth actuation of the firing trigger 8034, wherein each actuation of the firing trigger 8034 can advance the linked rack 8200 distally an incremental amount. Further to the above, the multiple strokes of firing trigger 1034 can rotate the right and left indicator gauge wheels 1040, 1041 to indicate the distance in which the linked rack 8200 has been advanced.

[0743] Referring now to FIGS. 181 and 183, an anti-backup mechanism 8250 can prevent the combination tension/compression spring 8184 from retracting the linked rack 8200 between firing strokes. A coupling slide tube 8131 abuts the first link 8196a and connects to the firing rod 8032 to communicate the firing motion. The firing rod 8032 extends proximally out of a proximal end of the frame 8028 and through a through hole 8408 of an anti-backup plate 8266. The through hole 8408 is sized to slidingly receive the firing rod 8032 when perpendicularly aligned but to bind when tipped. A lower tab attachment 8271 extends proximally from a lower lip of the proximal end of the frame 8028, extending through an aperture 8269 on a lower edge

of the anti-backup plate 8266. This lower tab attachment 8271 draws the lower portion of the anti-backup plate 8266 proximate to the frame 8028 so that the anti-backup plate 8266 is perpendicular when the firing rod 8032 is distally advanced and allowed to tip top aft into a binding state when the firing rod 8032 attempts to retract. An anti-backup compression spring 8264 is distally constrained by the proximal end of the frame 8028 and proximally abuts a top portion of the anti-backup plate 8266, biasing the anti-backup plate 8266 to a locking state. Opposing the spring bias, an anti-backup cam tube 8268 slidingly encompasses the coupling slide tube 8131 and abuts the anti-backup plate 8266. A proximally projecting anti-backup yoke 8256 attached to the anti-backup cam tube 8268 extends overtop of the closure yoke 8162.

[0744] Referring to FIG. 181, a link triggered automatic retraction mechanism 8289 is incorporated into the surgical stapling and severing instrument 8010 to cause knife retraction at the end of full firing travel. To that end, the distal link 8196d includes a tang 8290 that projects upwardly when the distal link 8196d is advanced into rack channel 8291 (FIG. 181) formed in the closure yoke 8162. This tang 8290 is aligned to activate a bottom proximal cam 8292 on an anti-backup release lever 8248 (FIG. 186). With particular reference to FIGS. 186 and 187, structures formed in the right and left half shells 8156, 8158 constrain movement of the anti-backup release lever 8248. A pin receptacle 8296 and circular pin 8293 formed respectively between right and left half shells 8156, 8158 is received through a longitudinally elongate aperture 8294 formed in the anti-backup release lever 8248 distal to the bottom proximal cam 8292, thus allowing longitudinal translation as well as rotation about the circular pin 8293. In the right half shell 8156, a proximally open channel 8295 includes a proximal horizontal portion 8295a that communicates with an upwardly and distally angled portion 8295b that receives a rightward aft pin 8297 (FIG. 187) near the proximal end of the anti-backup release lever 8248, thus imparting an upward rotation as the anti-backup release lever 8248 reaches the distal most portion of its translation. A blocking structure formed in the right half shell 8156 proximal to the anti-backup release lever 8248 prevents proximal movement thereof once assembled to maintain rightward aft pin 8297 in the proximally open channel 8295.

[0745] Further to the above, as depicted in FIGS. 187 and 188, a distal end 8254 of the anti-backup release lever 8248 thus is urged distally and downwardly, causing a rightward front pin 8298 to drop into distally open step structure 8299 formed in the right half shell 8156, which is urged into this engagement by a compression spring 8300 (FIG. 188) hooked to a leftward hook

8301 on the anti-backup release lever 8248 between the rightward front pin 8298 and the longitudinally elongate aperture 8294. The other end of the compression spring 8300 is attached to a hook 8302 (FIGS. 186, 188, 189) formed in the right half shell 8156 in a more proximal and lower position just above the closure yoke 8266. The compression spring 8300 thus pulls the distal end 8254 of the anti-backup release lever 8248 down and aft, which results in the rightward front pin 8298 locking into the distally open step structure 8299 when distally advanced. Thus, once tripped, referring to FIG. 189, the anti-backup release lever 8248 remains forward holding the anti-backup plate 8266 perpendicularly and thus allowing the linked rack 8200 to be retracted. When the closure yoke 8266 is subsequently retracted when unclamping the end effector 8012, an upwardly projecting reset tang 8303 on the closure yoke 8266 contacts a bottom distal cam 8305 of the anti-backup release lever 8248, lifting the rightward front pin 8298 out of the distally open step structure 8299 so that the anti-backup compression spring 8264 can proximally push the anti-backup cam tube 8268 and the anti-backup release lever 8248 to their retracted positions (FIG. 186).

[0746] Referring to FIGS. 179 and 189, the firing trigger 8034 can be operably engaged to the linked rack 8200 in any suitable manner. With particular reference to FIGS. 180 and 185, the firing trigger 8034 pivots about a firing trigger pin 8202 that is connected to the housing 8154. An upper portion 8204 of the firing trigger 8034 moves distally about the firing trigger pin 8202 as the firing trigger 8034 is depressed towards pistol grip 8036, stretching a proximally placed firing trigger tension spring 8206 (FIG. 181) proximally connected between the upper portion 8204 of the firing trigger 8034 and the housing 8154. The upper portion 8204 of the firing trigger 8034 engages the linked rack 8200 during each firing trigger depression via a spring biased side pawl mechanism 8210. When the firing trigger is released, the side pawl mechanism is disengaged from the linked rack 8200 and the firing trigger can be returned to an undepressed, or unfired, position. In use, a ramped right-side track formed by a proximally and rightwardly facing beveled surface 8284 in each of the links 8196a-8196d is engaged by a side pawl assembly 8285. In particular, a pawl slide 8270 (FIGS. 181 and 183) has right and left lower guides 8272 that slide respectively in a left track 8274 (FIG. 181) formed in the closure yoke 8266 below the rack channel 8291 and a right track 8275 in a closure yoke rail 8276 that parallels rack channel 8291 and is attached to a rack channel cover 8277 that closes a rightwardly open portion of the rack channel 8291 in the closure yoke 8266 that is distal to the travel of the

pawl slide 8270. In FIGS. 181, 182, and 185, a compression spring 8278 is attached between a hook 8279 on a top proximal position on the closure yoke rail 8276 and a hook 8280 on a distal right-side of the pawl slide 8270, which keeps the pawl slide 8270 drawn proximally into contact with the upper portion 8204 of the firing trigger 8034.

[0747] With particular reference to FIG. 181, a pawl block 8318 sits on the pawl slide 8270 pivoting about a vertical aft pin 8320 that passes through a left proximal corner of pawl block 8318 and pawl slide 8270. A kick-out block recess 8322 is formed on a distal portion of a top surface of the block 8318 to receive a kick-out block 8324 pivotally pinned therein by a vertical pin 8326 whose bottom tip extends into a pawl spring recess 8328 on a top surface of the pawl slide 8270. A pawl spring 8330 in the pawl spring recess 8328 extends to the right of the vertical front pin 8326 urging the pawl block 8318 to rotate counterclockwise when viewed from above into engagement with the ramped right-side track 8282. A small coil spring 8332 in the kick-out block recess 8322 urges the kick-out block 8324 to rotate clockwise when viewed from above, its proximal end urged into contact with a contoured lip 8334 formed in the closure yoke 8266 above the rack channel 8291. As shown in FIG. 184, the stronger mechanical advantage of the pawl spring 8330 over the small coil spring 8332 means that the pawl block 8318 tends toward engagement with the kick-out block 8324 rotated clockwise. In FIG. 185, as the firing trigger 8034 is fully depressed and begins to be release, the kick-out block 8324 encounters a ridge 8336 in the contoured lip 8334 as the pawl slide 8270 retracts, forcing the kick-out block 8324 to rotate clockwise when viewed from above and thereby kicking out the pawl block 8318 from engagement with the linked rack 8200. The shape of the kick-out block recess 8322 stops the clockwise rotation of the kick-out block 8324 to a perpendicular orientation to the contoured lip 8334 maintaining this disengagement during the full retraction and thereby eliminating a ratcheting noise.

[0748] In FIGS. 181, 183, 190, and 195, the surgical stapling and severing instrument 8010 can include a manual retraction mechanism 8500 that provides for a manual release of the firing mechanism, manual retraction, and in one version (FIGS. 196-202) further performs automatic retraction at the end of full firing travel. Referring now to FIGS. 181, 190, and 191, in particular, a front idler gear 8220 is engaged with a toothed upper, left surface 8222 of the linked rack 8200 wherein the front idler gear 8220 also engages an aft idler gear 8230 having a smaller right-side ratchet gear 8231. Both the front idler gear 8220 and aft idler gear 8230 are rotatably connected

to the handle housing 8154 respectively on front idler axle 8232 and aft idler axle 8234. Each end of the aft axle 8232 extend through the respective right and left housing half shells 8156, 8158 and are attached to the left and right indicator gauge wheels 8040, 8041 and, since the aft axle 8234 is free spinning in the handle housing 8154 and has a keyed engagement to the aft gear 8230, the indicator gauge wheels 8040, 8041 rotate with the aft gear 8230. The gear relationship between the linked rack 8200, idler gear 8220 and aft gear 8230 may be advantageously selected so that the toothed upper surface 8222 has tooth dimensions that are suitably strong and that the aft gear 8230 makes no more than one revolution during the full firing travel of the linked transmission firing mechanism 8150. In addition to gear mechanism 8502 visually indicating the firing travel, or progress, the gear mechanism 8502 can also be used to manual retract the knife. The smaller right-side ratchet gear 8231 of the aft idler gear 8230 extends into a hub 8506 of the manual retraction lever 8042, specifically aligned with a vertical longitudinally-aligned slot 8508 (FIG. 190) bisecting the hub 8506. A lateral through hole 8510 of the hub 8506 communicates with an upper recess 8512. A front portion 8514 is shaped to receive a proximally directed locking pawl 8516 that pivots about a rightward lateral pin 8518 formed in a distal end of the upper recess 8512. An aft portion 8520 is shaped to receive an L-shaped spring tab 8522 that urges the locking pawl 8516 downward into engagement with the right-side smaller ratchet gear 8231. A hold-up structure 8524 (FIGS. 186 and 193) projects from the right half shell 8156 into the upper recess 8512 holding up the locking pawl 8516 from engaging the smaller right-side ratchet gear 8231 when the manual retraction lever 8042 is down (FIG. 193). A coil spring 8525 (FIG. 181) urges the manual retraction lever 8042 down.

[0749] In use, as depicted in FIGS. 192 and 193, the combination tension/compression spring 8184 may become disconnected with the linked rack distally positioned. In FIGS. 194 and 195, as the manual retraction lever 8042 is raised, the locking pawl 8516 rotates clockwise and no longer is held up by the hold-up structure 8524 and engages the smaller right-side ratcheting gear 8231, rotating the aft idler gear 8230 clockwise when viewed from the left. Thus, the forward idler gear 8220 responds counterclockwise retracting the linked rack 8200. In addition, a rightward curved ridge 8510 projects out from the hub 8506, sized to contact and distally move the anti-backup release lever 8248 to release the anti-backup mechanism 8250 as the manual retraction lever 8042 is rotated.

[0750] In FIGS. 196-202, an automatic retraction mechanism 8600 for a surgical stapling and

severing instrument 8010a can incorporate automatic retraction at the end of full firing travel into a front idler gear 8220a having a tooth 8602 that moves within a circular groove 8604 in a cam wheel 8606 until encountering a blockage 8608 after nearly a full rotation corresponding to three firing strokes. In such circumstances, rightward ridge 8610 is rotated upward into contact a bottom cam recess 8612 to distally move an anti-backup release lever 8248a. With particular reference to FIG. 197, the anti-backup release lever 8248a includes the distal end 8254 that operates as previously described. The circular pin 8293 and pin receptacle 8296 formed between right and left half shells 8156, 8158 is received through a generally rectangular aperture 8294a formed in the anti-backup release lever 8248a aft of the bottom cam 8192, thus allowing longitudinal translation as well as downward locking motion of the distal end 8254 of the anti-backup release lever 8248a. In the right half shell 8156, a horizontal proximally open channel 8295a receives the rightward aft pin 8297 near the proximal end of the anti-backup release lever 8248a.

[0751] In operation, before firing in FIGS. 198, 198A, the linked rack 8200 and the anti-backup cam tube 8268 are in a retracted position, locking the anti-backup mechanism 8250 as the anti-backup compression spring 8264 proximally tips the anti-backup plate 8266. The automatic retraction mechanism 8600 is at an initial state with the anti-backup release lever 8248a retracted with link 8196a in contact with the forward idler gear 8220a. The tooth 8602 is at a six o'clock position with full travel of the circular groove 8604 progressing counterclockwise thereof with the rightward ridge 8610 just proximal to the tooth 8602. In FIGS. 199, 199A, one firing stroke has occurred moving up one distal link 8196b into contact with the forward idler gear 8220a. The tooth 8602 has progressed one third of a turn through the circular groove 8604 of the immobile cam wheel 8606. In FIGS. 200, 200A, a second firing stroke has occurred moving up one more link 8196c into contact with the forward idler gear 8220a. The tooth 8602 has progressed two thirds of a turn through the circular groove 8604 of the immobile cam wheel 8606. In FIGS. 201, 201A, a third firing stroke has occurred moving up one distal link 8196d into contact with the forward idler gear 8220a. The tooth 8602 has progressed fully around the circular groove 8604 into contact with the blockage 8608 initiating counterclockwise rotation (when viewed from the right) of the cam wheel 8606 bringing the rightward ridge 8608 into contact with the anti-backup release lever 8248a. In FIG. 202, the anti-backup release lever 8248a has moved distally in response thereto, locking the rightward front pin 8298 into the distally open step structure 8299

and releasing the anti-backup mechanism 8250. Similar surgical stapling instruments are disclosed in U.S. Patent No. 7,083,075, which issued on August 1, 2006, the entire disclosure of which is incorporated by reference herein.

[0752] Referring to FIG. 203, the staple applying assembly 9012 of a surgical stapling instrument 9010 accomplishes the functions of clamping onto tissue, driving staples and severing tissue by two distinct motions transferred longitudinally down the shaft 9016 relative to a shaft frame 9070. This shaft frame 9070 is proximally attached to a handle of a surgical stapling instrument and is coupled thereto for rotation about a longitudinal axis. An illustrative multi-stroke handle for the surgical stapling and severing instrument is described in greater detail in the co-pending and co-owned U.S. patent application entitled SURGICAL STAPLING INSTRUMENT INCORPORATING A MULTISTROKE FIRING POSITION INDICATOR AND RETRACTION MECHANISM, Ser. No. 10/374,026, the disclosure of which is hereby incorporated by reference in its entirety. Other applications consistent with the present invention may incorporate a single firing stroke, such as described in co-pending and commonly owned U.S. patent application SURGICAL STAPLING INSTRUMENT HAVING SEPARATE DISTINCT CLOSING AND FIRING SYSTEMS, Ser. No. 10/441,632, the disclosure of which is hereby incorporated by reference in its entirety.

[0753] With particular reference to FIG. 204, the distal end of the shaft frame 9070 is attached to the staple channel 9018. The anvil 9022 has a proximal pivoting end 9072 that is pivotally received within a proximal end 9074 of the staple channel 9018, just distal to its engagement to the shaft frame 9070. When the anvil 9022 is pivoted downwardly, the anvil 9022 moves a tissue contacting surface 9028 and forming pockets 9026 toward an opposing staple cartridge, described in greater detail further below. The pivoting end 9072 of the anvil 9022 includes a closure feature 9076 proximate but distal to its pivotal attachment with the staple channel 9018. Thus, a closure tube 9078, whose distal end includes a horseshoe aperture 9080 that engages this closure feature 9076, selectively imparts an opening motion to the anvil 9022 during proximal longitudinal motion and a closing motion to the anvil 9022 during distal longitudinal motion of the closure tube 9078 sliding over the shaft frame 9070 in response to a closure trigger, similar to the above. The shaft frame 9070 encompasses and guides a firing motion from the handle through a longitudinally reciprocating, two-piece knife and firing bar 9090. In particular, the shaft frame 9070 includes a longitudinal firing bar slot 9092 that receives a proximal portion of

the two-piece knife and firing bar 9090, specifically a laminate tapered firing bar 9094. It should be appreciated that the laminated tapered firing bar 9094 may be substituted with a solid firing bar and/or any other suitable materials.

[0754] An E-beam 9102 is the distal portion of the two-piece knife and firing bar 9090, which facilitates separate closure and firing as well as spacing of the anvil 9022 from the elongate staple channel 9018 during firing. With particular reference to FIGS. 204 and 205, in addition to any attachment treatment such as brazing or an adhesive, the knife and firing bar 9090 are formed of a female vertical attachment aperture 9104 proximally formed in the E-beam 9102 that receives a corresponding male attachment member 9106 distally presented by the laminated tapered firing bar 9094, allowing each portion to be formed of a selected material and process suitable for their disparate functions (e.g., strength, flexibility, friction). The E-beam 9102 may be advantageously formed of a material having suitable material properties for forming a pair of top pins 9110, a pair of middle pins 9112 and a bottom pin or foot 9114, as well as being able to acquire a sharp cutting edge 9116. In addition, integrally formed and proximally projecting top guide 9118 and middle guide 9120 bracketing each vertical end of the cutting edge 9116 further define a tissue staging area 9122 assisting in guiding tissue to the sharp cutting edge 9116 prior to being severed. The middle guide 9120 also serves to engage and fire the staple applying apparatus 9012 by abutting a stepped central member 9124 of a wedge sled 9126 (FIG. 206) that effects staple formation by the staple applying assembly 9012, as described in greater detail below. Forming these features (e.g., top pins 9110, middle pins 9112, and bottom foot 9114) integrally with the E-beam 9102 facilitates manufacturing at tighter tolerances relative to one another as compared to being assembled from a plurality of parts, ensuring desired operation during firing and/or effective interaction with various lockout features of the staple applying assembly 9012.

[0755] In FIGS. 207 and 208, the staple applying assembly 9012 is shown open, with the E-beam 9102 fully retracted. During assembly, the lower foot 9114 of the E-beam 9102 is dropped through a widened hole 9130 in the staple channel 9018 and the E-beam 9102 is then advanced such that the E-beam 9102 slides distally along a lower track 9132 formed in the staple channel 9018. In particular, the lower track 9132 includes a narrow slot 9133 that opens up as a widened slot 9134 on an undersurface of the staple channel 9018 to form an inverted T-shape in lateral cross section, as depicted particularly in FIGS. 208 and 209, which communicates with the

widened hole 9130. Once assembled, the components proximally coupled to the laminate tapered firing bar 9094 do not allow the lower foot 9114 to proximally travel again to the widened hole 9130 to permit disengagement. Referring to FIG. 210, the laminate tapered firing bar 9094 facilitates insertion of the staple applying assembly 9012 through a trocar. In particular, a more distal, downward projection 9136 raises the E-beam 9102 when fully retracted. This is accomplished by placement of the downward projection 9136 at a point where it cams upwardly on a proximal edge of the widened hole 9130 in the staple channel 9018. Referring now to FIG. 211, the laminate tapered firing bar 9094 also enhances operation of certain lockout features that may be incorporated into the staple channel 9018 by including a more proximal upward projection 9138 that is urged downwardly by the shaft frame 9070 during an initial portion of the firing travel. In particular, a lateral bar 9140 is defined between a pair of square apertures 9142 in the shaft frame 9070 (FIG. 204). A clip spring 9144 that encompasses the lateral bar 9140 downwardly urges a portion of the laminate tapered firing bar 9094 projecting distally out of the longitudinal firing bar slot 9092, which ensures certain advantageous lockout features are engaged when appropriate. This urging is more pronounced or confined solely to that portion of the firing travel when the upward projection 9138 contacts the clip spring 9144.

[0756] In FIGS. 207 and 208, the E-beam 9102 is retracted with the top pins 9110 thereof residing within an anvil pocket 9150 near the pivoting proximal end of the anvil 9022. A downwardly open vertical anvil slot 9152 (FIG. 203) laterally widens in the anvil 9022 into an anvil internal track 9154 that captures the top pins 9110 of the E-beam 9102 as they distally advance during firing, as depicted in FIGS. 210 and 211, affirmatively spacing the anvil 9022 from the staple channel 9018. Thus, with the E-beam 9102 retracted, the surgeon is able to repeatably open and close the staple applying assembly 9012 until satisfied with the placement and orientation of tissue captured therein for stapling and severing, yet the E-beam 9102 assists in proper positioning of tissue even for a staple applying assembly 9012 of reduced diameter and correspondingly reduced rigidity. In FIGS. 203, 204, 206, 207, 209, and 215, the staple applying assembly 9012 is shown with the replaceable staple cartridge 9020 that includes the wedge sled 9126. Longitudinally aligned and parallel plurality of downwardly open wedge slots 9202 (FIG. 209) receive respective wedges 9204 integral to the wedge sled 9126. In FIGS. 209-211, the wedge sled 9126 thus cams upwardly a plurality of staple drivers 9206 that are vertically slidable within staple driver recesses 9208. In this illustrative version, each staple driver 9206 includes

two vertical prongs, each translating upwardly into a respective staple hole 9210, or cavity 9024, to upwardly force out and deform a staple 9023 resting thereupon against a staple forming surface 9214 (FIG. 211) of the anvil 9022. A central firing recess 9216 (FIG. 204) defined within the staple cartridge 9020 proximate to the staple channel 9018 allows the passage of the bottom, horizontal portion 9218 (FIG. 206) of the wedge sled 9126 as well as the middle pins 9112 of the E-beam 9102. Specifically, a staple cartridge tray 9220 (FIGS. 204, 209) attaches to and underlies a polymer staple cartridge body 9222 that has the staple driver recesses 9208, staple holes 9210, and central firing recess 9216 formed therein. As staples 9023 are thus formed to either side, the sharp cutting edge 9116 enters a vertical through slot 9230 passing through the longitudinal axis of the staple cartridge 9020, excepting only a most distal end thereof.

[0757] Firing the staple applying assembly 9012 begins as depicted in FIG. 211 with the two-piece knife and firing bar 9090 proximally drawn until the downward projection 9136 cams the middle guide 9120 on the E-beam 9102 upward and aft, allowing a new staple cartridge 9020 to be inserted into the staple channel 9018 when the anvil 9022 is open as depicted in FIGS. 203 and 207. In FIG. 212, the two-piece knife and firing bar 9090 has been distally advanced a small distance, allowing the downward projection 9136 to drop into the widened hole 9130 of the lower track 9132 under the urging of the clip spring 9144 against the upward projection 9138 of the laminate tapered firing bar 9094. The middle guide 9120 prevents further downward rotation by resting upon the stepped central member 9124 of the wedge sled 9126, thus maintaining the middle pin 9112 of the E-beam within the central firing recess 9216. In FIG. 213, the two-piece knife and firing bar 9090 has been distally fired, advancing the wedge sled 9126 to cause formation of staples 9023 while severing tissue 9242 clamped between the anvil 9022 and staple cartridge 9020 with the sharp cutting edge 9116. Thereafter, in FIG. 214, the two-piece knife and firing bar 9090 is retracted, leaving the wedge sled 9126 distally positioned. In FIG. 215, the middle pin 9112 is allowed to translate down into a lockout recess 9240 formed in the staple channel 9018 (also see FIGS. 208, 211). Thus, the operator would receive a tactile indication as the middle pin 9112 encounters the distal edge of the lockout recess 9240 when the wedge sled 9126 (not shown in FIG. 215) is not proximally positioned (i.e., missing staple cartridge 9020 or spent staple cartridge 9020). Similar surgical stapling instruments are disclosed in U.S. Patent No. 7,380,696, which issued on June 3, 2008, the entire disclosure of which is incorporated by reference herein.

[0758] As described above, a staple cartridge can comprise a cartridge body including a plurality of staple cavities defined therein. The cartridge body can comprise a deck and a top deck surface wherein each staple cavity can define an opening in the deck surface. As also described above, a staple can be positioned within each staple cavity such that the staples are stored within the cartridge body until they are ejected therefrom. Prior to being ejected from the cartridge body, the staples can be contained with the cartridge body such that the staples do not protrude above the deck surface. As the staples are positioned below the deck surface, in such embodiments, the possibility of the staples becoming damaged and/or prematurely contacting the targeted tissue can be reduced. In various circumstances, the staples can be moved between an unfired position in which they do not protrude from the cartridge body and a fired position in which they have emerged from the cartridge body and can contact an anvil positioned opposite the staple cartridge. The anvil, and/or the forming pockets defined within the anvil, can be positioned a predetermined distance above the deck surface such that, as the staples are being deployed from the cartridge body, the staples are deformed to a predetermined formed height. In some circumstances, the thickness of the tissue captured between the anvil and the staple cartridge may vary and, as a result, thicker tissue may be captured within certain staples while thinner tissue may be captured within certain other staples. In either event, the clamping pressure, or force, applied to the tissue by the staples may vary from staple to staple or vary between a staple on one end of a staple row and a staple on the other end of the staple row, for example. In certain circumstances, the gap between the anvil and the staple cartridge deck can be controlled such that the staples apply a certain minimum clamping pressure within each staple. In some such circumstances, however, significant variation of the clamping pressure within different staples may still exist.

[0759] A staple cartridge can comprise means for compensating for the thickness of the tissue captured within the staples deployed from the staple cartridge. Referring to FIG. 216, a staple cartridge, such as staple cartridge 10000, for example, can include a rigid first portion, such as support portion 10010, for example, and a compressible second portion, such as tissue thickness compensator 10020, for example. Referring primarily to FIG. 218, the support portion 10010 can comprise a cartridge body, a top deck surface 10011, and a plurality of staple cavities 10012 wherein, similar to the above, each staple cavity 10012 can define an opening in the deck surface 10011. A staple 10030, for example, can be removably positioned in each staple cavity 10012.

For example, referring primarily to FIG. 245 and as described in greater detail below, each staple 10030 can comprise a base 10031 and one or more legs 10032 extending from the base 10031. Prior to the staples 10030 being deployed, as also described in greater detail below, the bases 10031 of the staples 10030 can be supported by staple drivers positioned within the support portion 10010 and, concurrently, the legs 10032 of the staples 10030 can be at least partially contained within the staple cavities 10012. The staples 10030 can be deployed between an unfired position and a fired position such that the legs 10032 move through the tissue thickness compensator 10020, penetrate through a top surface of the tissue thickness compensator 10020, penetrate the tissue T, and contact an anvil positioned opposite the staple cartridge 10000. As the legs 10032 are deformed against the anvil, the legs 10032 of each staple 10030 can capture a portion of the tissue thickness compensator 10020 and a portion of the tissue T within each staple 10030 and apply a compressive force to the tissue. Further to the above, the legs 10032 of each staple 10030 can be deformed downwardly toward the base 10031 of the staple to form a staple entrapment area 10039 in which the tissue T and the tissue thickness compensator 10020 can be captured. In various circumstances, the staple entrapment area 10039 can be defined between the inner surfaces of the deformed legs 10032 and the inner surface of the base 10031. The size of the entrapment area for a staple can depend on several factors such as the length of the legs, the diameter of the legs, the width of the base, and/or the extent in which the legs are deformed, for example.

[0760] Previously, a surgeon was often required to select the appropriate staples having the appropriate staple height for the tissue being stapled. For example, a surgeon could select tall staples for use with thick tissue and short staples for use with thin tissue. In some circumstances, however, the tissue being stapled did not have a consistent thickness and, thus, some staples were unable to achieve the desired fired configuration. For example, FIG. 250 illustrates a tall staple used in thin tissue. Referring now to FIG. 251, when a tissue thickness compensator, such as tissue thickness compensator 10020, for example, is used with thin tissue, for example, the larger staple may be formed to a desired fired configuration.

[0761] Owing to the compressibility of the tissue thickness compensator, the tissue thickness compensator can compensate for the thickness of the tissue captured within each staple. More particularly, referring now to FIGS. 245 and 246, a tissue thickness compensator, such as tissue thickness compensator 10020, for example, can consume larger and/or smaller portions of the

staple entrapment area 10039 of each staple 10030 depending on the thickness and/or type of tissue contained within the staple entrapment area 10039. For example, if thinner tissue T is captured within a staple 10030, the tissue thickness compensator 10020 can consume a larger portion of the staple entrapment area 10039 as compared to circumstances where thicker tissue T is captured within the staple 10030. Correspondingly, if thicker tissue T is captured within a staple 10030, the tissue thickness compensator 10020 can consume a smaller portion of the staple entrapment area 10039 as compared to the circumstances where thinner tissue T is captured within the staple 10030. In this way, the tissue thickness compensator can compensate for thinner tissue and/or thicker tissue and assure that a compressive pressure is applied to the tissue irrespective, or at least substantially irrespective, of the tissue thickness captured within the staples. In addition to the above, the tissue thickness compensator 10020 can compensate for different types, or compressibilities, of tissues captured within different staples 10030. Referring now to FIG. 246, the tissue thickness compensator 10020 can apply a compressive force to vascular tissue T which can include vessels V and, as a result, restrict the flow of blood through the less compressible vessels V while still applying a desired compressive pressure to the surrounding tissue T. In various circumstances, further to the above, the tissue thickness compensator 10020 can also compensate for malformed staples. Referring to FIG. 247, the malformation of various staples 10030 can result in larger staple entrapment areas 10039 being defined within such staples. Owing to the resiliency of the tissue thickness compensator 10020, referring now to FIG. 248, the tissue thickness compensator 10020 positioned within malformed staples 10030 may still apply a sufficient compressive pressure to the tissue T even though the staple entrapment areas 10039 defined within such malformed staples 10030 may be enlarged. In various circumstances, the tissue thickness compensator 10020 located intermediate adjacent staples 10030 can be biased against the tissue T by properly-formed staples 10030 surrounding a malformed staple 10030 and, as a result, apply a compressive pressure to the tissue surrounding and/or captured within the malformed staple 10030, for example. In various circumstances, a tissue thickness compensator can compensate for different tissue densities which can arise due to calcifications, fibrous areas, and/or tissue that has been previously stapled or treated, for example.

[0762] A fixed, or unchangeable, tissue gap can be defined between the support portion and the anvil and, as a result, the staples may be deformed to a predetermined height regardless of the

thickness of the tissue captured within the staples. When a tissue thickness compensator is used with these embodiments, the tissue thickness compensator can adapt to the tissue captured between the anvil and the support portion staple cartridge and, owing to the resiliency of the tissue thickness compensator, the tissue thickness compensator can apply an additional compressive pressure to the tissue. Referring now to FIGS. 252-257, a staple 10030 has been formed to a predefined height H. With regard to FIG. 252, a tissue thickness compensator has not been utilized and the tissue T consumes the entirety of the staple entrapment area 10039. With regard to FIG. 259, a portion of a tissue thickness compensator 10020 has been captured within the staple 10030, compressed the tissue T, and consumed at least a portion of the staple entrapment area 10039. Referring now to FIG. 254, thin tissue T has been captured within the staple 10030. In this example, the compressed tissue T has a height of approximately 2/9H and the compressed tissue thickness compensator 10020 has a height of approximately 7/9H, for example. Referring now to FIG. 255, tissue T having an intermediate thickness has been captured within the staple 10030. In this example, the compressed tissue T has a height of approximately 4/9H and the compressed tissue thickness compensator 10020 has a height of approximately 5/9H, for example. Referring now to FIG. 256, tissue T having an intermediate thickness has been captured within the staple 10030. In this example, the compressed tissue T has a height of approximately 2/3H and the compressed tissue thickness compensator 10020 has a height of approximately 1/3H, for example. Referring now to FIG. 255, thick tissue T has been captured within the staple 10030. In this example, the compressed tissue T has a height of approximately 8/9H and the compressed tissue thickness compensator 10020 has a height of approximately 1/9H, for example. In various circumstances, the tissue thickness compensator can comprise a compressed height which comprises approximately 10% of the staple entrapment height, approximately 20% of the staple entrapment height, approximately 30% of the staple entrapment height, approximately 40% of the staple entrapment height, approximately 50% of the staple entrapment height, approximately 60% of the staple entrapment height, approximately 70% of the staple entrapment height, approximately 80% of the staple entrapment height, and/or approximately 90% of the staple entrapment height, for example.

[0763] The staples 10030 can comprise any suitable unformed height. The staples 10030 can comprise an unformed height between approximately 2 mm and approximately 4.8 mm, for example. The staples 10030 can comprise an unformed height of approximately 2.0 mm,

approximately 2.5 mm, approximately 3.0 mm, approximately 3.4 mm, approximately 3.5 mm, approximately 3.8 mm, approximately 4.0 mm, approximately 4.1 mm, and/or approximately 4.8 mm, for example. The height H to which the staples can be deformed can be dictated by the distance between the deck surface 10011 of the support portion 10010 and the opposing anvil. The distance between the deck surface 10011 and the tissue-contacting surface of the anvil can be approximately 0.097", for example. The height H can also be dictated by the depth of the forming pockets defined within the anvil. The forming pockets can have a depth measured from the tissue-contacting surface, for example. As described in greater detail below, the staple cartridge 10000 can further comprise staple drivers which can lift the staples 10030 toward the anvil and, lift, or "overdrive", the staples above the deck surface 10011. In such cases, the height H to which the staples 10030 are formed can also be dictated by the distance in which the staples 10030 are overdriven. For example, the staples 10030 can be overdriven by approximately .028", for example, and can result in the staples 10030 being formed to a height of approximately 0.189", for example. The staples 10030 can be formed to a height of approximately 0.8 mm, approximately 1.0 mm, approximately 1.5 mm, approximately 1.8 mm, approximately 2.0 mm, and/or approximately 2.25 mm, for example. The staples can be formed to a height between approximately 2.25 mm and approximately 3.0 mm, for example. Further to the above, the height of the staple entrapment area of a staple can be determined by the formed height of the staple and the width, or diameter, of the wire comprising the staple. The height of the staple entrapment area 10039 of a staple 10030 can comprise the formed height H of the staple less two diameter widths of the wire. The staple wire can comprise a diameter of approximately 0.0089", for example. The staple wire can comprise a diameter between approximately 0.0069" and approximately 0.0119", for example. For example, the formed height H of a staple 10030 can be approximately 0.189" and the staple wire diameter can be approximately 0.0089" resulting in a staple entrapment height of approximately 0.171", for example.

[0764] Further to the above, the tissue thickness compensator can comprise an uncompressed, or pre-deployed, height and can be configured to deform to one of a plurality of compressed heights. The tissue thickness compensator can comprise an uncompressed height of approximately 0.125", for example. The tissue thickness compensator can comprise an uncompressed height of greater than or equal to approximately 0.080", for example. The tissue thickness compensator can comprise an uncompressed, or pre-deployed, height which is greater

than the unfired height of the staples. The uncompressed, or pre-deployed, height of the tissue thickness compensator can be approximately 10% taller, approximately 20% taller, approximately 30% taller, approximately 40% taller, approximately 50% taller, approximately 60% taller, approximately 70% taller, approximately 80% taller, approximately 90% taller, and/or approximately 100% taller than the unfired height of the staples, for example. The uncompressed, or pre-deployed, height of the tissue thickness compensator can be up to approximately 100% taller than the unfired height of the staples, for example. The uncompressed, or pre-deployed, height of the tissue thickness compensator can be over 100% taller than the unfired height of the staples, for example. The tissue thickness compensator can comprise an uncompressed height which is equal to the unfired height of the staples. The tissue thickness compensator can comprise an uncompressed height which is less than the unfired height of the staples. The uncompressed, or pre-deployed, height of the thickness compensator can be approximately 10% shorter, approximately 20% shorter, approximately 30% shorter, approximately 40% shorter, approximately 50% shorter, approximately 60% shorter, approximately 70% shorter, approximately 80% shorter, and/or approximately 90% shorter than the unfired height of the staples, for example. The compressible second portion can comprise an uncompressed height which is taller than an uncompressed height of the tissue T being stapled. The tissue thickness compensator can comprise an uncompressed height which is equal to an uncompressed height of the tissue T being stapled. The tissue thickness compensator can comprise an uncompressed height which is shorter than an uncompressed height of the tissue T being stapled.

[0765] As described above, a tissue thickness compensator can be compressed within a plurality of formed staples regardless of whether thick tissue or thin tissue is captured within the staples. For example, the staples within a staple line, or row, can be deformed such that the staple entrapment area of each staple comprises a height of approximately 2.0 mm, for example, wherein the tissue T and the tissue thickness compensator can be compressed within this height. In certain circumstances, the tissue T can comprise a compressed height of approximately 1.75 mm within the staple entrapment area while the tissue thickness compensator can comprise a compressed height of approximately 0.25 mm within the staple entrapment area, thereby totaling the approximately 2.0 mm staple entrapment area height, for example. In certain circumstances, the tissue T can comprise a compressed height of approximately 1.50 mm within the staple

entrapment area while the tissue thickness compensator can comprise a compressed height of approximately 0.50 mm within the staple entrapment area, thereby totaling the approximately 2.0 mm staple entrapment area height, for example. In certain circumstances, the tissue T can comprise a compressed height of approximately 1.25 mm within the staple entrapment area while the tissue thickness compensator can comprise a compressed height of approximately 0.75 mm within the staple entrapment area, thereby totaling the approximately 2.0 mm staple entrapment area height, for example. In certain circumstances, the tissue T can comprise a compressed height of approximately 1.0 mm within the staple entrapment area while the tissue thickness compensator can comprise a compressed height of approximately 1.0 mm within the staple entrapment area, thereby totaling the approximately 2.0 mm staple entrapment area height, for example. In certain circumstances, the tissue T can comprise a compressed height of approximately 0.75 mm within the staple entrapment area while the tissue thickness compensator can comprise a compressed height of approximately 1.25 mm within the staple entrapment area, thereby totaling the approximately 2.0 mm staple entrapment area height, for example. In certain circumstances, the tissue T can comprise a compressed height of approximately 1.50 mm within the staple entrapment area while the tissue thickness compensator can comprise a compressed height of approximately 0.50 mm within the staple entrapment area, thereby totaling the approximately 2.0 mm staple entrapment area height, for example. In certain circumstances, the tissue T can comprise a compressed height of approximately 0.25 mm within the staple entrapment area while the tissue thickness compensator can comprise a compressed height of approximately 1.75 mm within the staple entrapment area, thereby totaling the approximately 2.0 mm staple entrapment area height, for example.

[0766] Further to the above, the tissue thickness compensator can comprise an uncompressed height which is less than the fired height of the staples. The tissue thickness compensator can comprise an uncompressed height which is equal to the fired height of the staples. Alternatively, the tissue thickness compensator can comprise an uncompressed height which is taller than the fired height of the staples. For example, the uncompressed height of a tissue thickness compensator can comprise a thickness which is approximately 110% of the formed staple height, approximately 120% of the formed staple height, approximately 130% of the formed staple height, approximately 140% of the formed staple height, approximately 150% of the formed staple height, approximately 160% of the formed staple height, approximately 170% of the

formed staple height, approximately 180% of the formed staple height, approximately 190% of the formed staple height, and/or approximately 200% of the formed staple height, for example. The tissue thickness compensator can comprise an uncompressed height which is more than twice the fired height of the staples. The tissue thickness compensator can comprise a compressed height which is from approximately 85% to approximately 150% of the formed staple height, for example. As described above, the tissue thickness compensator can be compressed between an uncompressed thickness and a compressed thickness. The compressed thickness of a tissue thickness compensator can be approximately 10% of its uncompressed thickness, approximately 20% of its uncompressed thickness, approximately 30% of its uncompressed thickness, approximately 40% of its uncompressed thickness, approximately 50% of its uncompressed thickness, approximately 60% of its uncompressed thickness, approximately 70% of its uncompressed thickness, approximately 80% of its uncompressed thickness, and/ or approximately 90% of its uncompressed thickness, for example. The uncompressed thickness of the tissue thickness compensator can be approximately two times, approximately ten times, approximately fifty times, and/or approximately one hundred times thicker than its compressed thickness, for example. The compressed thickness of the tissue thickness compensator can be between approximately 60% and approximately 99% of its uncompressed thickness. The uncompressed thickness of the tissue thickness compensator can be at least 50% thicker than its compressed thickness. The uncompressed thickness of the tissue thickness compensator can be up to one hundred times thicker than its compressed thickness. The compressible second portion can be elastic, or at least partially elastic, and can bias the tissue T against the deformed legs of the staples. For example, the compressible second portion can resiliently expand between the tissue T and the base of the staple in order to push the tissue T against the legs of the staple. As is discussed in further detail below, the tissue thickness compensator can be positioned intermediate the tissue T and the deformed staple legs. In various circumstances, as a result of the above, the tissue thickness compensator can be configured to consume any gaps within the staple entrapment area.

[0767] Any of the tissue thickness compensators described herein may comprise materials characterized by one or more of the following properties: biocompatible, bioabsorable, bioresorbable, biodurable, biodegradable, compressible, fluid absorbable, swellable, self-expandable, bioactive, medicament, pharmaceutically active, anti-adhesion, haemostatic,

antibiotic, anti-microbial, anti-viral, nutritional, adhesive, permeable, hydrophilic and/or hydrophobic, for example. In all cases, any surgical stapling or fastening instrument comprising an anvil and a staple or fastener cartridge may also comprise a tissue thickness compensator associated with the anvil and/or staple cartridge. Such a tissue thickness compensator may be any of the tissue thickness compensators described herein and may, or may in addition, comprise at least one of a haemostatic agent, such as fibrin and thrombin, an antibiotic, such as doxycpl, and a medicament, such as matrix metalloproteinases (MMPs).

[0768] The tissue thickness compensator may comprise synthetic and/or non-synthetic materials. The tissue thickness compensator may comprise a polymeric composition comprising one or more synthetic polymers and/or one or more non-synthetic polymers. The synthetic polymer may comprise a synthetic absorbable polymer and/or a synthetic non-absorbable polymer. The polymeric composition may comprise a biocompatible foam, for example. The biocompatible foam may comprise a porous, open cell foam and/or a porous, closed cell foam, for example. The biocompatible foam may have a uniform pore morphology or may have a gradient pore morphology (i.e. small pores gradually increasing in size to large pores across the thickness of the foam in one direction). The polymeric composition may comprise one or more of a porous scaffold, a porous matrix, a gel matrix, a hydrogel matrix, a solution matrix, a filamentous matrix, a tubular matrix, a composite matrix, a membranous matrix, a biostable polymer, and a biodegradable polymer, and combinations thereof. For example, the tissue thickness compensator may comprise a foam reinforced by a filamentous matrix or may comprise a foam having an additional hydrogel layer that expands in the presence of bodily fluids to further provide the compression on the tissue. A tissue thickness compensator could also be comprised of a coating on a material and/or a second or third layer that expands in the presence of bodily fluids to further provide the compression on the tissue. Such a layer could be a hydrogel that could be a synthetic and/or naturally derived material and could be either biodurable and/or biodegradable, for example. The tissue thickness compensator may comprise a microgel or a nanogel. The hydrogel may comprise carbohydrate-derived microgels and/or nanogels. A tissue thickness compensator may be reinforced with fibrous non-woven materials or fibrous mesh type elements, for example, that can provide additional flexibility, stiffness, and/or strength. A tissue thickness compensator that has a porous morphology which exhibits a gradient structure such as, for example, small pores on one surface and larger pores on the other surface. Such morphology

could be more optimal for tissue in-growth or haemostatic behavior. Further, the gradient could be also compositional with a varying bio-absorption profile. A short term absorption profile may be preferred to address hemostasis while a long term absorption profile may address better tissue healing without leakages.

[0769] Examples of non-synthetic materials include, but are not limited to, lyophilized polysaccharide, glycoprotein, bovine pericardium, collagen, gelatin, fibrin, fibrinogen, elastin, proteoglycan, keratin, albumin, hydroxyethyl cellulose, cellulose, oxidized cellulose, oxidized regenerated cellulose (ORC), hydroxypropyl cellulose, carboxyethyl cellulose, carboxymethylcellulose, chitan, chitosan, casein, alginate, and combinations thereof.

[0770] Examples of synthetic absorbable materials include, but are not limited to, poly(lactic acid) (PLA), poly(L-lactic acid) (PLLA), polycaprolactone (PCL), polyglycolic acid (PGA), poly(trimethylene carbonate) (TMC), polyethylene terephthalate (PET), polyhydroxyalkanoate (PHA), a copolymer of glycolide and ε-caprolactone (PGCL), a copolymer of glycolide and-trimethylene carbonate, poly(glycerol sebacate) (PGS), poly(dioxanone) (PDS), polyesters, poly(orthoesters), polyoxaesters, polyetheresters, polycarbonates, polyamide esters, polyanhydrides, polysaccharides, poly(ester-amides), tyrosine-based polyarylates, polyamines, tyrosine-based polyiminocarbonates, tyrosine-based polycarbonates, poly(D,L-lactide-urethane), poly(hydroxybutyrate), poly(B-hydroxybutyrate), poly(E-caprolactone), polyethyleneglycol (PEG), poly[bis(carboxylatophenoxy) phosphazene] poly(amino acids), pseudo-poly(amino acids), absorbable polyurethanes, poly (phosphazine), polyphosphazenes, polyalkyleneoxides, polyacrylamides, polyhydroxyethylmethylacrylate, polyvinylpyrrolidone, polyvinyl alcohols, poly(caprolactone), polyacrylic acid, polyacetate, polypropylene, aliphatic polyesters, glycerols, copoly(ether-esters), polyalkylene oxalates, polyamides, poly(iminocarbonates), polyalkylene oxalates, and combinations thereof. The polyester is may be selected from the group consisting of polylactides, polyglycolides, trimethylene carbonates, polydioxanones, polycaprolactones, polybutesters, and combinations thereof.

[0771] The synthetic absorbable polymer may comprise one or more of 90/10 poly(glycolide-L-lactide) copolymer, commercially available from Ethicon, Inc. under the trade designation VICRYL (polyglactic 910), polyglycolide, commercially available from American Cyanamid Co. under the trade designation DEXON, polydioxanone, commercially available from Ethicon, Inc. under the trade designation PDS, poly(glycolide-trimethylene carbonate) random block

copolymer, commercially available from American Cyanamid Co. under the trade designation MAXON, 75/25 poly(glycolide-ε-caprolactone-poliglecaprolactone 25) copolymer, commercially available from Ethicon under the trade designation MONOCRYL, for example.

[0772] Examples of synthetic non-absorbable materials include, but are not limited to, polyurethane, polypropylene (PP), polyethylene (PE), polycarbonate, polyamides, such as nylon, polyvinylchloride (PVC), polymethylmetacrylate (PMMA), polystyrene (PS), polyester, polyetheretherketone (PEEK), polytetrafluoroethylene (PTFE), polytrifluorochloroethylene (PTFCE), polyvinylfluoride (PVF), fluorinated ethylene propylene (FEP), polyacetal, polysulfone, silicons, and combinations thereof. The synthetic non-absorbable polymers may include, but are not limited to, foamed elastomers and porous elastomers, such as, for example, silicone, polyisoprene, and rubber. The synthetic polymers may comprise expanded polytetrafluoroethylene (ePTFE), commercially available from W. L. Gore & Associates, Inc. under the trade designation GORE-TEX Soft Tissue Patch and co-polyetherester urethane foam commercially available from Polyganics under the trade designation NASOPORE.

[0773] The polymeric composition may comprise from approximately 50% to approximately 90% by weight of the polymeric composition of PLLA and approximately 50% to approximately 10% by weight of the polymeric composition of PCL, for example. The polymeric composition may comprise approximately 70% by weight of PLLA and approximately 30% by weight of PCL, for example. The polymeric composition may comprise from approximately 55% to approximately 85% by weight of the polymeric composition of PGA and 15% to 45% by weight of the polymeric composition of PCL, for example. The polymeric composition may comprise approximately 65% by weight of PGA and approximately 35% by weight of PCL, for example. The polymeric composition may comprise from approximately 90% to approximately 95% by weight of the polymeric composition of PGA and approximately 5% to approximately 10% by weight of the polymeric composition of PLA, for example.

[0774] The synthetic absorbable polymer may comprise a bioabsorbable, biocompatible elastomeric copolymer. Suitable bioabsorbable, biocompatible elastomeric copolymers include but are not limited to copolymers of ε-caprolactone and glycolide (preferably having a mole ratio of ε-caprolactone to glycolide of from about 30:70 to about 70:30, preferably 35:65 to about 65:35, and more preferably 45:55 to 35:65); elastomeric copolymers of ε-caprolactone and lactide, including L-lactide, D-lactide blends thereof or lactic acid copolymers (preferably having

a mole ratio of ε-caprolactone to lactide of from about 35:65 to about 65:35 and more preferably 45:55 to 30:70) elastomeric copolymers of p-dioxanone (1,4-dioxan-2-one) and lactide including L-lactide, D-lactide and lactic acid (preferably having a mole ratio of p-dioxanone to lactide of from about 40:60 to about 60:40); elastomeric copolymers of ε-caprolactone and p-dioxanone (preferably having a mole ratio of ε-caprolactone to p-dioxanone of from about 30:70 to about 70:30); elastomeric copolymers of p-dioxanone and trimethylene carbonate (preferably having a mole ratio of p-dioxanone to trimethylene carbonate of from about 30:70 to about 70:30); elastomeric copolymers of trimethylene carbonate and glycolide (preferably having a mole ratio of trimethylene carbonate to glycolide of from about 30:70 to about 70:30); elastomeric copolymer of trimethylene carbonate and lactide including L-lactide, D-lactide, blends thereof or lactic acid copolymers (preferably having a mole ratio of trimethylene carbonate to lactide of from about 30:70 to about 70:30) and blends thereof. The elastomeric copolymer is a copolymer of glycolide and ε-caprolactone. In another example, the elastomeric copolymer is a copolymer of lactide and ε-caprolactone.

[0775] The disclosures of U.S. Patent No. 5,468,253, entitled ELASTOMERIC MEDICAL DEVICE, which issued on November 21, 1995, and U.S. Patent No. 6,325,810, entitled FOAM BUTTRESS FOR STAPLING APPARATUS, which issued on December 4, 2001, are hereby incorporated by reference in their respective entireties.

[0776] The tissue thickness compensator may comprise an emulsifier. Examples of emulsifiers may include, but are not limited to, water-soluble polymers, such as, polyvinyl alcohol (PVA), polyvinyl pyrrolidone (PVP), polyethylene glycol (PEG), polypropylene glycol (PPG), PLURONICS, TWEENS, polysaccharides and combinations thereof.

[0777] The tissue thickness compensator may comprise a surfactant.

Examples of surfactants may include, but are not limited to, polyacrylic acid, methalose, methyl cellulose, ethyl cellulose, propyl cellulose, hydroxy ethyl cellulose, carboxy methyl cellulose, polyoxyethylene cetyl ether, polyoxyethylene lauryl ether, polyoxyethylene octyl ether, polyoxyethylene octylphenyl ether, polyoxyethylene oleyl ether, polyoxyethylene sorbitan monolaurate, polyoxyethylene stearyl ether, polyoxyethylene nonylphenyl ether, dialkylphenoxy poly(ethyleneoxy) ethanol, and polyoxamers.

[0778] The polymeric composition may comprise a pharmaceutically active agent. The polymeric composition may release a therapeutically effective amount of the pharmaceutically

active agent. The pharmaceutically active agent may be released as the polymeric composition is desorbed/absorbed. The pharmaceutically active agent may be released into fluid, such as, for example, blood, passing over or through the polymeric composition. Examples of pharmaceutically active agents may include, but are not limited to, haemostatic agents and drugs, such as, for example, fibrin, thrombin, and oxidized regenerated cellulose (ORC); anti-inflammatory drugs, such as, for example, diclofenac, aspirin, naproxen, sulindac, and hydrocortisone; antibiotic and antimicrobial drug or agents, such as, for example, triclosan, ionic silver, ampicillin, gentamicin, polymyxin B, chloramphenicol; and anticancer agents, such as, for example, cisplatin, mitomycin, adriamycin.

[0779] The polymeric composition may comprise a haemostatic material. The tissue thickness compensator may comprise haemostatic materials comprising poly(lactic acid), poly(glycolic acid), poly(hydroxybutyrate), poly(caprolactone), poly(dioxanone), polyalkyleneoxides, copoly(ether-esters), collagen, gelatin, thrombin, fibrin, fibrinogen, fibronectin, elastin, albumin, hemoglobin, ovalbumin, polysaccharides, hyaluronic acid, chondroitin sulfate, hydroxyethyl starch, hydroxyethyl cellulose, cellulose, oxidized cellulose, hydroxypropyl cellulose, carboxyethyl cellulose, carboxymethyl cellulose, chitan, chitosan, agarose, maltose, maltodextrin, alginate, clotting factors, methacrylate, polyurethanes, cyanoacrylates, platelet agonists, vasoconstrictors, alum, calcium, RGD peptides, proteins, protamine sulfate, ε-amino caproic acid, ferric sulfate, ferric subsulfates, ferric chloride, zinc, zinc chloride, aluminum chloride, aluminum sulfates, aluminum acetates, permanganates, tannins, bone wax, polyethylene glycols, fucans and combinations thereof. The tissue thickness compensator may be characterized by haemostatic properties.

[0780] The polymeric composition of a tissue thickness compensator may be characterized by percent porosity, pore size, and/or hardness, for example. The polymeric composition may have a percent porosity from approximately 30% by volume to approximately 99% by volume, for example. The polymeric composition may have a percent porosity from approximately 60% by volume to approximately 98% by volume, for example. The polymeric composition may have a percent porosity from approximately 85% by volume to approximately 97% by volume, for example. The polymeric composition may comprise approximately 70% by weight of PLLA and approximately 30% by weight of PCL, for example, and can comprise approximately 90% porosity by volume, for example. For example, as a result, the polymeric composition would

comprise approximately 10% copolymer by volume. The polymeric composition may comprise approximately 65% by weight of PGA and approximately 35% by weight of PCL, for example, and can have a percent porosity from approximately 93% by volume to approximately 95% by volume, for example. The polymeric composition may comprise greater than 85% porosity by volume. The polymeric composition may have a pore size from approximately 5 micrometers to approximately 2000 micrometers, for example. The polymeric composition may have a pore size between approximately 10 micrometers to approximately 100 micrometers, for example. For example, the polymeric composition can comprise a copolymer of PGA and PCL, for example. The polymeric composition may have a pore size between approximately 100 micrometers to approximately 1000 micrometers, for example. For example, the polymeric composition can comprise a copolymer of PLLA and PCL, for example.

[0781] According to certain aspects, the hardness of a polymeric composition may be expressed in terms of the Shore Hardness, which can defined as the resistance to permanent indentation of a material as determined with a durometer, such as a Shore Durometer. In order to assess the durometer value for a given material, a pressure is applied to the material with a durometer indenter foot in accordance with ASTM procedure D2240-00, entitled, "Standard Test Method for Rubber Property-Durometer Hardness", the entirety of which is incorporated herein by reference. The durometer indenter foot may be applied to the material for a sufficient period of time, such as 15 seconds, for example, wherein a reading is then taken from the appropriate scale. Depending on the type of scale being used, a reading of 0 can be obtained when the indenter foot completely penetrates the material, and a reading of 100 can be obtained when no penetration into the material occurs. This reading is dimensionless. The durometer may be determined in accordance with any suitable scale, such as Type A and/or Type OO scales, for example, in accordance with ASTM D2240-00. The polymeric composition of a tissue thickness compensator may have a Shore A hardness value from approximately 4 A to approximately 16 A, for example, which is approximately 45 OO to approximately 65 OO on the Shore OO range. For example, the polymeric composition can comprise a PLLA/PCL copolymer or a PGA/PCL copolymer, for example. The polymeric composition of a tissue thickness compensator may have a Shore A Hardness value of less than 15 A. The polymeric composition of a tissue thickness compensator may have a Shore A Hardness value of less than 10 A. The polymeric composition of a tissue thickness compensator may have a Shore A Hardness value of less than 5 A. The

polymeric material may have a Shore OO composition value from approximately 35 OO to approximately 75 OO, for example.

[0782] The polymeric composition may have at least two of the above-identified properties. The polymeric composition may have at least three of the above-identified properties. The polymeric composition may have a porosity from 85% to 97% by volume, a pore size from 5 micrometers to 2000 micrometers, and a Shore A hardness value from 4 A to 16 A and Shore OO hardness value from 45 OO to 65 OO, for example. The polymeric composition may comprise 70% by weight of the polymeric composition of PLLA and 30% by weight of the polymeric composition of PCL having a porosity of 90% by volume, a pore size from 100 micrometers to 1000 micrometers, and a Shore A hardness value from 4 A to 16 A and Shore OO hardness value from 45 OO to 65 OO, for example. The polymeric composition may comprise 65% by weight of the polymeric composition of PGA and 35% by weight of the polymeric composition of PCL having a porosity from 93% to 95% by volume, a pore size from 10 micrometers to 100 micrometers, and a Shore A hardness value from 4 A to 16 A and Shore OO hardness value from 45 OO to 65 OO, for example.

[0783] Any of the tissue thickness compensators described herein may comprise a material that expands. As discussed above, the tissue thickness compensator may comprise a compressed material that expands when uncompressed or deployed, for example. In addition or alternatively, any such tissue thickness compensator may comprise a self-expanding material that can be formed *in situ*. For example, the tissue thickness compensator may comprise at least one precursor selected to spontaneously crosslink when contacted with at least one of: another precursor or other precursors, water, and/or bodily fluids. Referring to FIG. 534, a first precursor may contact one or more other precursors to form an expandable and/or swellable tissue thickness compensator. The tissue thickness compensator may comprise a fluid-swellable composition, such as a water-swellable composition, and/or a gel comprising water.

[0784] Referring to FIGS. 518A and B, for example, a tissue thickness compensator 70000, representative of any of the tissue thickness compensators described herein, may comprise at least one hydrogel precursor 70010 selected to form a hydrogel *in situ* and/or *in vivo* to expand the tissue thickness compensator 70000. FIG. 518A illustrates such a tissue thickness compensator 70000 comprising an encapsulation comprising a first hydrogel precursor 70010A and a second hydrogel precursor 70010B prior to expansion. As shown in FIG. 518A, the first

hydrogel precursor 70010A and second hydrogel precursor 70010B may be physically separated from one another in the same encapsulation. Alternatively, a first encapsulation may comprise the first hydrogel precursor 70010A and a second encapsulation may comprise the second hydrogel precursor 70010B. FIG. 518B illustrates the expansion of the thickness tissue compensator 70000 when the hydrogel is formed *in situ* and/or *in vivo*. As shown in FIG. 518B, the encapsulation may be ruptured, and the first hydrogel precursor 70010A may contact the second hydrogel precursor 70010B to form the hydrogel 70020. As illustrated, the hydrogel may comprise an expandable material. It may expand for up to 72 hours, for example.

[0785] Any of the tissue thickness compensators described herein, including those discussed in the previous paragraph, may comprise a biodegradable foam having an encapsulation comprising dry hydrogel particles or granules embedded therein. The encapsulations in the foam may be formed by contacting an aqueous solution of a hydrogel precursor and an organic solution of biocompatible materials to form the foam. As shown in FIG. 535, the aqueous solution and organic solution may form micelles. The aqueous solution and organic solution may be dried to encapsulate dry hydrogel particles or granules within the foam. For example, a hydrogel precursor, such as a hydrophilic polymer, may be dissolved in water to form a dispersion of micelles. The aqueous solution may contact an organic solution of dioxane comprising poly(glycolic acid) and polycaprolactone. The aqueous and organic solutions may be lyophilized to form a biodegradable foam having dry hydrogel particles or granules dispersed therein. It is believed that the micelles may form the encapsulation having dry hydrogel particles or granules dispersed within the foam structure. This encapsulation may subsequently be ruptured, and the dry hydrogel particles or granules may then contact a fluid, such as a bodily fluid, and expand.

[0786] Generally, any tissue thickness compensator described herein may be constituted to expand when contacted with an activator, such as a fluid, for example. Referring to FIG. 519, for example, a tissue thickness compensator 70050, representative of any of the tissue thickness compensators described herein, may comprise a swellable material, such as a hydrogel, that expands when contacted with a fluid 70055, such as bodily fluids, saline, water and/or an activator, for example. Examples of bodily fluids may include, but are not limited to, blood, plasma, peritoneal fluid, cerebral spinal fluid, urine, lymph fluid, synovial fluid, vitreous fluid, saliva, gastrointestinal luminal contents, bile, and/or gas (e.g., CO_2). In some cases, the tissue thickness compensator 70050 may expand when the tissue thickness compensator 70050 absorbs

the fluid. In other cases, the tissue thickness compensator 70050 may comprise a non-cross-linked hydrogel that expands when contacted with an activator 70055 comprising a cross-linking agent to form a cross-linked hydrogel. In all cases, the tissue thickness compensator may be constituted to expand or swell from contact up to 72 hours, such as from 24-72 hours, up to 24 hours, up to 48 hours, and up to 72 hours, for example, to provide continuously increasing pressure and/or compression to the tissue. As shown in FIG. 519, the initial thickness of the tissue thickness compensator 70050 is thus less than an expanded thickness after the fluid 70055 contacts the tissue thickness compensator 70050.

[0787] Referring to FIGS. 516 and 517, a staple cartridge 70100 may comprise a tissue thickness compensator 70105, representative of any of the tissue thickness compensators described herein, and a plurality of staples 70110 each comprising staple legs 70112. As shown in FIG. 516, tissue thickness compensator 70105 may have an initial thickness or compressed height that is less than the fired height of the staples 70110. The tissue thickness compensator 70100 may be configured to expand *in situ* and/or *in vivo* when contacted with a fluid 70102, such as bodily fluids, saline, and/or an activator for example, to push the tissue T against the legs 70112 of the staple 70110. As shown in FIG. 517, the tissue thickness compensator 70100 may expand and/or swell when contacted with a fluid 70102. The tissue thickness compensator 70105 can compensate for the thickness of the tissue T captured within each staple 70110. As shown in FIG. 517, tissue thickness compensator 70105 may have an expanded thickness or an uncompressed height that is less than the fired height of the staples 70110.

[0788] Any of the tissue thickness compensator described or claimed herein may comprise an initial thickness and an expanded thickness. In all cases, the initial thickness of the tissue thickness compensator can be approximately 0.001% of its expanded thickness, approximately 0.01% of its expanded thickness, approximately 0.1% of its expanded thickness, approximately 1% of its expanded thickness, approximately 10% of its expanded thickness, approximately 20% of its expanded thickness, approximately 30% of its expanded thickness, approximately 40% of its expanded thickness, approximately 50% of its expanded thickness, approximately 60% of its expanded thickness, approximately 70% of its expanded thickness, approximately 80% of its expanded thickness, or approximately 90% of its expanded thickness. Alternatively, in all cases, the expanded thickness of the tissue thickness compensator can be approximately two times, approximately five times, approximately ten times, approximately fifty times, approximately one

hundred times, approximately two hundred times, approximately three hundred times, approximately four hundred times, approximately five hundred times, approximately six hundred times, approximately seven hundred times, approximately eight hundred times, approximately nine hundred times, or approximately one thousand times thicker than its initial thickness. Alternatively, in all cases, the initial thickness of the tissue thickness compensator can be up to 1% its expanded thickness, up to 5% its expanded thickness, up to 10% its expanded thickness, or up to 50% its expanded thickness. Alternatively, in all cases, the expanded thickness of the tissue thickness compensator can be at least 50% thicker than its initial thickness, at least 100% thicker than its initial thickness, at least 300% thicker than its initial thickness, or at least 500% thicker than its initial thickness. As a result, the tissue thickness compensator can be configured to consume any gaps within the staple entrapment area.

[0789] Any of the tissue thickness compensators described herein may comprise a hydrogel. The hydrogel may comprise homopolymer hydrogels, copolymer hydrogels, multipolymer hydrogels, interpenetrating polymer hydrogels, or combinations thereof. The hydrogel may comprise microgels, nanogels, or combinations thereof. The hydrogel may generally comprise a hydrophilic polymer network capable of absorbing and/or retaining fluids. The hydrogel may comprise a non-crosslinked hydrogel, a crosslinked hydrogel, or combinations thereof. The hydrogel may comprise chemical crosslinks, physical crosslinks, hydrophobic segments and/or water insoluble segments. The hydrogel may be chemically crosslinked by polymerization, small-molecule crosslinking, and/or polymer-polymer crosslinking. The hydrogel may be physically crosslinked by ionic interactions, hydrophobic interactions, hydrogen bonding interactions, sterocomplexation, and/or supramolecular chemistry. The hydrogel may be substantially insoluble due to the crosslinks, hydrophobic segments and/or water insoluble segments, but be expandable and/or swellable due to absorption and/or retention of fluids. Moreover, a hydrogel precursor may be used that crosslinks with endogenous materials and/or tissues.

[0790] In any of the tissue thickness compensators that comprise a hydrogel, the hydrogel may comprise an environmentally sensitive hydrogel (ESH). The ESH may comprise materials having fluid-swelling properties that relate to environmental conditions. The environmental conditions may include, but are not limited to, the physical conditions, biological conditions, and/or chemical conditions at the surgical site. For example, the hydrogel may swell or shrink in

response to temperature, pH, electric fields, ionic strength, enzymatic and/or chemical reactions, electrical and/or magnetic stimuli, or other physiological and environmental variables. The ESH may comprise multifunctional acrylates, hydroxyethylmethacrylate (HEMA), elastomeric acrylates, or related monomers.

[0791] Any of the tissue thickness compensators comprising a hydrogel (including any tissue thickness compensator described or claimed herein that comprises a hydrogel or is modified to comprise a hydrogel), may comprise at least one of the non-synthetic materials and synthetic materials described above. The hydrogel may comprise a synthetic hydrogel and/or a non-synthetic hydrogel. In addition or instead, the tissue thickness compensator may comprise a plurality of layers. The plurality of the layers may comprise porous layers and/or non-porous layers. For example, the tissue thickness compensator may comprise a non-porous layer and a porous layer. In another example, the tissue thickness compensator may comprise a porous layer intermediate a first non-porous layer and a second non-porous layer. In another example, the tissue thickness compensator may comprise a non-porous layer intermediate a first porous layer and a second porous layer. The non-porous layers and porous layers may be positioned in any order relative to the surfaces of the staple cartridge and/or anvil.

[0792] Examples of the non-synthetic material mentioned in the previous paragraph include, but are not limited to, albumin, alginate, carbohydrate, casein, cellulose, chitin, chitosan, collagen, blood, dextran, elastin, fibrin, fibrinogen, gelatin, heparin, hyaluronic acid, keratin, protein, serum, and starch. The cellulose may comprise hydroxyethyl cellulose, oxidized cellulose, oxidized regenerated cellulose (ORC), hydroxypropyl cellulose, carboxyethyl cellulose, carboxymethylcellulose, and combinations thereof. The collagen may comprise bovine pericardium. The carbohydrate may comprise a polysaccharide, such as lyophilized polysaccharide. The protein may comprise glycoprotein, proteoglycan, or combinations thereof.

[0793] Likewise, examples of the synthetic material previously mentioned include, but are not limited to, poly(lactic acid), poly(glycolic acid), poly(hydroxybutyrate), poly(phosphazine), polyesters, polyethylene glycols, polyethylene oxide, polyethylene oxide-co-polypropylene oxide, co-polyethylene oxide, polyalkyleneoxides, polyacrylamides, polyhydroxyethylmethylacrylate, poly(vinylpyrrolidone), polyvinyl alcohols, poly(caprolactone), poly(dioxanone), polyacrylic acid, polyacetate, polypropylene, aliphatic polyesters, glycerols, poly(amino acids), copoly(ether-esters), polyalkylene oxalates, polyamides,

poly(iminocarbonates), polyoxaesters, polyorthoesters, polyphosphazenes and combinations thereof. These non-synthetic materials may be synthetically prepared, e.g., synthetic hyaluronic acid, utilizing conventional methods.

[0794] In any of the tissue thickness compensators comprising a hydrogel (including any tissue thickness compensator described or claimed herein that comprises a hydrogel or is modified to comprise a hydrogel), the hydrogel may be made from one or more hydrogel precursors. Such precursors may comprise a monomer and/or a macromer. The hydrogel precursor may comprise an electrophile functional group and/or a nucleophile electrophile functional group. In general, electrophiles may react with nucleophiles to form a bond. The term "functional group" as used herein refers to electrophilic or nucleophilic groups capable of reacting with each other to form a bond. Examples of electrophilic functional groups include, but are not limited to, N-hydroxysuccinimides ("NHS"), sulfosuccinimides, carbonyldiimidazole, sulfonyl chloride, aryl halides, sulfosuccinimidyl esters, N-hydroxysuccinimidyl esters, succinimidyl esters such as succinimidyl succinates and/or succinimidyl propionates, isocyanates, thiocyanates, carbodiimides, benzotriazole carbonates, epoxides, aldehydes, maleimides, imidoesters, combinations thereof, and the like. In one specific example, the electrophilic functional group may comprise a succinimidyl ester. Examples of nucleophile functional groups include, but are not limited to, $-NH_2$, -SH, -OH, $-PH_2$, and $-CO-NH-NH_2$.

[0795] The hydrogel may be formed from a single precursor or multiple precursors. For example, the hydrogel may be formed from a first precursor and a second precursor. The first hydrogel precursor and second hydrogel precursor may form a hydrogel *in situ* and/or *in vivo* upon contact. The hydrogel precursor may generally refer to a polymer, functional group, macromolecule, small molecule, and/or crosslinker that can take part in a reaction to form a hydrogel. The precursor may comprise a homogeneous solution, heterogeneous, or phase separated solution in a suitable solvent, such as water or a buffer, for example. The buffer may have a pH from about 8 to about 12, such as, about 8.2 to about 9, for example. Examples of buffers include, but are not limited to borate buffers. In some circumstances, the precursor(s) may be in an emulsion. Thus, a first precursor may react with a second precursor to form the hydrogel. For example, the first precursor may spontaneously crosslink when contacted with the second precursor, and/or a first set of electrophilic functional groups on a first precursor may react with a second set of nucleophilic functional groups on a second precursor. When the

precursors are mixed in an environment that permits reaction (e.g., as relating to pH, temperature, and/or solvent), the functional groups may react with each other to form covalent bonds. The precursors may become crosslinked when at least some of the precursors react with more than one other precursor.

[0796] The tissue thickness compensator may comprise at least one monomer selected from the group consisting of 3-sulfopropyl acrylate potassium salt ("KSPA"), sodium acrylate ("NaA"), N-(tris(hydroxylmethyl)methyl)acrylamide ("tris acryl"), and 2-acrylamido-2-methyl-1-propane sulfonic acid (AMPS). The tissue thickness compensator may comprise a copolymer comprising two or more monomers selected from the group consisting of KSPA, NaA, tris acryl, AMPS. The tissue thickness compensator may comprise homopolymers derived from KSPA, NaA, trisacryl and AMPS. The tissue thickness compensator may comprise hydrophilicity modifying monomers copolymerizable therewith. The hydrophilicity modifying monomers may comprise methylmethacrylate, butylacrylate, cyclohexylacrylate, styrene, styrene sulphonic acid.

[0797] The tissue thickness compensator may comprise a crosslinker. The crosslinker may comprise a low molecular weight di- or polyvinylic crosslinking agent, such as ethylenglycol diacrylate or dimethacrylate, di-, tri- or tetraethylen-glycol diacrylate or dimethacrylate, allyl (meth)acrylate, a C_2-C_8-alkylene diacrylate or dimethacrylate, divinyl ether, divinyl sulfone, di- and trivinylbenzene, trimethylolpropane triacrylate or trimethacrylate, pentaerythritol tetraacrylate or tetramethacrylate, bisphenol A diacrylate or dimethacrylate, methylene bisacrylamide or bismethacrylamide, ethylene bisacrylamide or ethylene bismethacrylamide, triallyl phthalate or diallyl phthalate. As a specific example, the crosslinker may comprise N,N'-methylenebisacrylamide ("MBAA").

[0798] The tissue thickness compensator may comprise at least one of acrylate and/or methacrylate functional hydrogels, biocompatible photoinitiator, alkyl-cyanoacrylates, isocyanate functional macromers, optionally comprising amine functional macromers, succinimidyl ester functional macromers, optionally comprising amine and/or sulfhydryl functional macromers, epoxy functional macromers, optionally comprising amine functional macromers, mixtures of proteins and/or polypeptides and aldehyde crosslinkers, Genipin, and water-soluble carbodiimides, anionic polysaccharides and polyvalent cations.

[0799] The tissue thickness compensator may comprise unsaturated organic acid monomers, acrylic substituted alcohols, and/or acrylamides. The tissue thickness compensator may comprise

methacrylic acids, acrylic acids, glycerolacrylate, glycerolmethacryulate, 2-hydroxyethylmethacrylate, 2-hydroxyethylacrylate, 2-(dimethylaminoethyl) methacrylate, N-vinyl pyrrolidone, methacrylamide, and/or N, N-dimethylacrylamide poly(methacrylic acid).

[0800] The tissue thickness compensator may comprise a reinforcement material. The reinforcement material may comprise at least one of the non-synthetic materials and synthetic materials described above. The reinforcement material may comprise collagen, gelatin, fibrin, fibrinogen, elastin, keratin, albumin, hydroxyethyl cellulose, cellulose, oxidized cellulose, hydroxypropyl cellulose, carboxyethyl cellulose, carboxymethylcellulose, chitan, chitosan, alginate, poly(lactic acid), poly(glycolic acid), poly(hydroxybutyrate), poly(phosphazine), polyesters, polyethylene glycols, polyalkyleneoxides, polyacrylamides, polyhydroxyethylmethylacrylate, polyvinylpyrrolidone, polyvinyl alcohols, poly(caprolactone), poly(dioxanone), polyacrylic acid, polyacetate, polycaprolactone, polypropylene, aliphatic polyesters, glycerols, poly(amino acids), copoly(ether-esters), polyalkylene oxalates, polyamides, poly(iminocarbonates), polyalkylene oxalates, polyoxaesters, polyorthoesters, polyphosphazenes and combinations thereof.

[0801] The tissue thickness compensator may comprise a layer comprising the reinforcement material. A porous layer and/or a non-porous layer of a tissue thickness compensator may comprise the reinforcement material. For example, the porous layer may comprise the reinforcement material and the non-porous layer may not comprise the reinforcement material. The reinforcement layer may comprise an inner layer intermediate a first non-porous layer and a second non-porous layer. The reinforcement layer may comprise an outer layer of the tissue thickness compensator and/or an exterior surface of the tissue thickness compensator.

[0802] The reinforcement material may comprise meshes, monofilaments, multifilament braids, fibers, mats, felts, particles, and/or powders. The reinforcement material may be incorporated into a layer of the tissue thickness compensator. The reinforcement material may be incorporated into at least one of a non-porous layer and a porous layer. A mesh comprising the reinforcement material may be formed using conventional techniques, such as, for example, knitting, weaving, tatting, and/or knipling. A plurality of reinforcement materials may be oriented in a random direction and/or a common direction. The common direction may be parallel to the staple line or perpendicular to the staple line, for example. Monofilaments and/or multifilament braids may be oriented in a random direction and/or a common direction. The monofilaments and multifilament

braids may be associated with the non-porous layer and/or the porous layer. The tissue thickness compensator may comprise a plurality of reinforcement fibers oriented in a random direction or a common direction within a non-porous layer.

[0803] Referring to FIG. 528, an anvil 70300 may comprise a tissue thickness compensator 70305, representative of any of the tissue thickness compensators described herein, comprising a first non-porous layer 70307 and a second non-porous layer 70309 sealingly enclosing a reinforcement layer 70310. The reinforcement layer 70310 may comprise a hydrogel comprising ORC particles or fibers embedded therein, and the non-porous layers may comprise ORC. As shown in FIG. 528, the tissue thickness compensator 70305, representative of any of the tissue thickness compensators described herein, may be configured to conform to the contour of the anvil 70300. The inner layer of the tissue thickness compensator 70305 may conform to the inner surface of the anvil 70300, which includes the forming pockets 70301.

[0804] In all cases where reinforcement fibres are used in a tissue thickness compensator, the fibers may form a non-woven material, such as, for example, a mat or a felt. The fibers may have any suitable length, such as, for example from 0.1 mm to 100 mm and 0.4 mm to 50 mm. Alternatively, a reinforcement material may be ground to a powder. The powder may have a particle size from 10 micrometers to 1 cm, for example. The powder may be incorporated into the tissue thickness compensator.

[0805] Any of the tissue thickness compensators described or claimed herein may be formed or partially formed *in situ*. For example, in the case where the tissue thickness compensator includes a hydrogel, the hydrogel may be formed *in situ*. The tissue thickness compensator may be formed *in situ* by covalent, ionic, and/or hydrophobic bonds. Physical (non-covalent) crosslinks may result from complexation, hydrogen bonding, desolvation, Van der Waals interactions, ionic bonding, or combinations thereof. Chemical (covalent) crosslinking may be accomplished by any one of a number of mechanisms, including: free radical polymerization, condensation polymerization, anionic or cationic polymerization, step growth polymerization, electrophile-nucleophile reactions, and combinations thereof.

[0806] *In situ* formation of the tissue thickness compensator may comprise reacting two or more precursors that are physically separated until contacted *in situ* and/or react to an environmental condition to react with each other to form a hydrogel, for example. *In situ* polymerizable polymers may be prepared from precursor(s) that can be reacted to form a polymer at the surgical

site. The tissue thickness compensator may be formed by crosslinking reactions of the precursor(s) *in situ*. At least one precursor may comprise an initiator capable of initiating a polymerization reaction for the formation of the *in situ* tissue thickness compensator. The tissue thickness compensator may comprise a precursor that can be activated at the time of application to create, for example, a crosslinked hydrogel. *In situ* formation of the tissue thickness compensator may comprise activating at least one precursor to form bonds to form the tissue thickness compensator. This activation may be achieved by changes in the physical conditions, biological conditions, and/or chemical conditions at the surgical site, including, but not limited to temperature, pH, electric fields, ionic strength, enzymatic and/or chemical reactions, electrical and/or magnetic stimuli, and other physiological and environmental variables. Alternatively, precursors may be contacted outside the body and introduced to the surgical site.

[0807] Another way of forming, or partially forming, a tissue thickness compensator *in situ* or *in vivo*, applicable to any of the tissue thickness compensators described herein, involves using a tissue thickness compensator that comprises one or more encapsulations, or cells, which can be configured to store at least one component therein. For example, the encapsulation may be configured to store a hydrogel precursor therein. The encapsulation may be configured to store two components therein, for example, as has already been described. The encapsulation may be configured to store a first hydrogel precursor and a second hydrogel precursor therein. Alternatively, a first encapsulation may be configured to store a first hydrogel precursor therein and a second encapsulation may be configured to store a second hydrogel precursor therein. As described above, these encapsulations can be aligned, or at least substantially aligned, with the staple legs to puncture and/or otherwise rupture the encapsulations when the staple legs contact the encapsulation. The encapsulations may be compressed, crushed, collapsed, and/or otherwise ruptured when the staples are deployed. After the encapsulations have been ruptured, the component(s) stored therein can flow out of the encapsulation. The component stored therein may contact other components, layers of the tissue thickness compensator, and/or the tissue. These other components may be flowing from the same or different encapsulations, provided in, or in the layers of, the tissue thickness compensator, and/or provided to the surgical site by the clinician. As a result of the above, the component(s) stored within the encapsulations can provide expansion and/or swelling of the tissue thickness compensator.

[0808] The tissue thickness compensator may comprise a layer comprising these encapsulations. Such an encapsulation may comprise a void, a pocket, a dome, a tube, and combinations thereof associated with the layer. The encapsulations may comprise voids in the layer. For example, the layer can comprise two layers that can be attached to one another wherein the encapsulations can be defined between the two layers. The encapsulations may comprise domes on the surface of the layer. For example, at least a portion of the encapsulations can be positioned within domes extending upwardly from the layer. The encapsulations may comprise pockets formed within the layer. For example, a first portion of the encapsulations may comprise a dome and a second portion of the encapsulations may comprise a pocket. The encapsulations may comprise a tube embedded within the layer. This tube may comprise any of the non-synthetic materials and/or synthetic materials described herein, such as PLA. The tissue thickness compensator may comprise a bioabsorable foam, such as ORC, comprising PLA tubes embedded therein, and the tube may encapsulate a hydrogel, for example. The encapsulations may comprise discrete cells that are unconnected to each other. Alternatively, one or more of the encapsulations can be in fluid communication with each other via one or more passageways, conduits, and/or channels, for example, extending through the layer.

[0809] The rate of release of a component from the encapsulation may be controlled by the thickness of the tissue thickness compensator, the composition of tissue thickness compensator, the size of the component, the hydrophilicity of the component, and/or the physical and/or chemical interactions among the component, the composition of the tissue thickness compensator, and/or the surgical instrument, for example. The layer can comprise one or more thin sections or weakened portions, such as partial perforations, for example, which can facilitate the incision of the layer and the rupture of the encapsulations. These partial perforations may extend through only a part of a layer or, alternatively, the perforations may extend completely through the layer.

[0810] Referring to FIGS. 523 and 524, a tissue thickness compensator 70150, representative of any of the tissue thickness compensators described herein, may comprise an outer layer 70152A and an inner layer 70152B comprising encapsulations 70154. The encapsulations may comprise a first encapsulated component and a second encapsulated component. Alternatively, the encapsulations may independently comprise one of a first encapsulated component and a second encapsulated component. The first encapsulated component may be separated from the second

encapsulated component. The outer layer 70152A may comprise a tissue-contacting surface. The inner layer 70152B may comprise an instrument-contacting surface. The instrument-contacting surface 70152B may be releasably attached to the anvil 70156. The outer layer 70152A may be attached to the inner layer 70152B to define a void between the outer layer 70152A and inner layer 70152B. As shown in FIG. 523, each encapsulation 70154 may comprise a dome on the instrument-contacting surface of the inner layer 70152B. The dome may comprise partial perforations to facilitate the incision of the layer by the staple legs and the rupture of the encapsulation. As shown in the FIG. 524, the anvil 70156 can comprise a plurality of forming pocket rows 70158 wherein the domes of the encapsulations 70154 may be aligned with the forming pocket 70158. The tissue-contacting surface may comprise a flat surface lacking domes , and/or the tissue-contacting surface may comprise one or more encapsulations, such as encapsulations 70154, for example, extending therefrom.

[0811] An anvil of any surgical stapling instrument may comprise a tissue thickness compensator comprising an encapsulated component comprising at least one microsphere particle. In accordance with the above description, the tissue thickness compensator may comprise an encapsulation comprising a first encapsulated component and a second encapsulated component , and/or the tissue thickness compensator may comprise an encapsulation comprising a first microsphere particle and a second microsphere particle.

[0812] Referring to FIG. 525, a stapling apparatus may comprise an anvil 70180 and a staple cartridge (illustrated in other figures). The staples 70190 of a staple cartridge can be deformed by an anvil 70180 when the anvil 70180 is moved into a closed position and/or by a staple driver system 70192 which moves the staples 70190 toward the closed anvil 70180. The legs 70194 of the staples may contact the anvil 70180 such that the staples 70190 are at least partially deformed. The anvil 70180 may comprise a tissue thickness compensator 70182 comprising an outer layer 70183A, an inner layer 70183B. The tissue thickness compensator 70182 may comprise a first encapsulated component and a second encapsulated component. The encapsulations 210185 can be aligned, or at least substantially aligned, such that, when the staple legs 70194 are pushed through the tissue T and the outer layer 70183A, the staple legs 70194 can puncture and/or otherwise rupture the encapsulations 70185. As shown in FIG. 525, the staple 70190C is in its fully fired position, the staple 70190B is in the process of being fired, and the staple 70190A is in its unfired position. The legs of staples 70190C and 70190B have moved

through the tissue T, the outer layer 70183A, and the inner layer 70183B of the tissue thickness compensator 70182, and have contacted an anvil 70180 positioned opposite the staple cartridge. After the encapsulations 70185 have been ruptured, the encapsulated components can flow out and contact each other, bodily fluids, and/or the tissue T, for example. The encapsulated components may react to form a reaction product such as a hydrogel, for example, to expand between the tissue T and the base of the staple and to push the tissue T against the legs of the staple. As a result, the tissue thickness compensator can be configured to consume any gaps within the staple entrapment area.

[0813] The tissue thickness compensators described herein, including all of those that are formed or partially formed or expandable *in* situ or *in* vivo, may be suitable for use with any surgical instrument. As described above, the tissue thickness compensator may be associated with the staple cartridge and/or the anvil. The tissue thickness compensator may be configured into any shape, size and/or dimension suitable to fit the staple cartridge and/or anvil. As described herein, the tissue thickness compensator may be releasably attached to the staple cartridge and/or anvil. The tissue thickness compensator may be attached to the staple cartridge and/or anvil in any mechanical and/or chemical manner capable of retaining the tissue thickness compensator in contact with the staple cartridge and/or anvil prior to and during the stapling process. The tissue thickness compensator may be removed or released from the staple cartridge and/or anvil after the staple penetrates the tissue thickness compensator. The tissue thickness compensator may be removed or released from the staple cartridge and/or anvil as the staple cartridge and/or anvil is moved away from the tissue thickness compensator.

[0814] Referring to FIGS. 520-522, any stapling apparatus 70118 may comprise an anvil 70120 and a staple cartridge 70122 comprising a firing member 70124, a plurality of staples 70128, a knife edge 70129, and a tissue thickness compensator 70130. The tissue thickness compensator 70130, representative of any of the tissue thickness compensators described herein, may comprise at least one encapsulated component. The encapsulated component may be ruptured when the tissue thickness compensator is compressed, stapled, and/or cut. Referring to FIG. 521, for example, the staples 70128 can be deployed between an unfired position and a fired position such that the staple legs move through the tissue thickness compensator 70130, penetrate through a bottom surface and a top surface of the tissue thickness compensator 70130, penetrate the tissue T, and contact an anvil 70120 positioned opposite the staple cartridge 70118. The

encapsulated components may react with each other, a hydrophilic powder embedded or dispersed in the tissue thickness compensator, and/or bodily fluids to expand or swell the tissue thickness compensator 70130. As the legs are deformed against the anvil, the legs of each staple can capture a portion of the tissue thickness compensator 70130 and a portion of the tissue T within each staple 70128 and apply a compressive force to the tissue T. As shown in FIGS. 521 and 522, the tissue thickness compensator 70130 can compensate for the thickness of the tissue T captured within each staple 70128.

[0815] Referring to FIG. 526, a surgical instrument 70200 may comprise an anvil 70205 comprising an upper tissue thickness compensator 70210 and a staple cartridge 70215 comprising a lower tissue thickness compensator comprising an outer layer 70220 and an inner layer 70225. The upper tissue thickness compensator 70210 can be positioned on a first side of the targeted tissue and the lower tissue thickness compensator can be positioned on a second side of the tissue. The upper tissue thickness compensator 70210 may comprise ORC, the outer layer of the lower tissue thickness compensator may comprise a hydrogel having ORC particles embedded therein, and the inner layer of the lower tissue thickness compensator may comprise ORC, for example.

[0816] Referring to FIGS. 529-531, a surgical instrument 70400 may comprise a staple cartridge 70405 and an anvil 70410. The staple cartridge 70405 may comprise a tissue thickness compensator 70415 including bioabsorbable foam. The bioabsorbable foam can comprise an encapsulation which comprises an encapsulated component 70420. The bioabsorable foam may comprise ORC and the encapsulated component may comprise a medicament, for example. The tissue thickness compensator 70415 of the anvil 70410 may comprise an inner layer 70425 and an outer layer 70430. The inner layer 70425 may comprise a bioabsorbable foam, and the outer layer 70430 may comprise a hydrogel, optionally comprising reinforcement materials, for example. During an exemplary firing sequence, referring primarily to FIG. 530, a sled 70435 can first contact staple 70440A and begin to lift the staple upwardly. As the sled 70435 is advanced further distally, the sled 70435 can begin to lift staples 70440B-D, and any other subsequent staples, in a sequential order. The sled 70435 can drive the staples 70440 upwardly such that the legs of the staples contact the opposing anvil 70410 and are deformed to a desired shape. With regard to the firing sequence illustrated in FIG. 530, the staples 70440A-C have been moved into their fully fired positions, the staple 70440D is in the process of being fired, and the staple

70420E is still in its unfired position. The encapsulated component 70470 may be ruptured by the staple legs during the exemplary firing sequence. The encapsulated component 70420 may flow from the encapsulation around the staple legs to contact the tissue T. In various circumstances, additional compression of the tissue thickness compensator can squeeze additional medicament out of the encapsulation. The medicament can immediately treat the tissue and can reduce bleeding from the tissue.

[0817] In various circumstances, a surgeon, or other clinician, may deliver a fluid to the tissue thickness compensator to manufacture a tissue thickness compensator comprising at least one medicament stored and/or absorbed therein. A staple cartridge and/or anvil may comprise a port configured to provide access to the tissue thickness compensator. Referring to FIG. 532B, a staple cartridge 70500 may comprise a port 70505 at a distal end thereof, for example. The port 70505 may be configured to receive a needle 70510, such as a fenestrated needle shown in FIG. 532A. The clinician may insert a needle 70510 through the port 70505 into the tissue thickness compensator 70515 to deliver the fluid to the tissue thickness compensator 70515. The fluid may comprise a medicament and hydrogel precursor, for example. As described above, the fluid may be released from tissue thickness compensator to the tissue when the tissue thickness compensator is ruptured and/or compressed. For example, the medicament may be released from the tissue thickness compensator 70515 as the tissue thickness compensator 70515 biodegrades.

[0818] Referring now to FIG. 216, a staple cartridge, such as staple cartridge 10000, for example, can comprise a support portion 10010 and a compressible tissue thickness compensator 10020. Referring now to FIGS. 218-220, the support portion 10010 can comprise a deck surface 10011 and a plurality of staple cavities 10012 defined within the support portion 10010. Each staple cavity 10012 can be sized and configured to removably store a staple, such as a staple 10030, for example, therein. The staple cartridge 10000 can further comprise a plurality of staple drivers 10040 which can each be configured to support one or more staples 10030 within the staple cavities 10012 when the staples 10030 and the staple drivers 10040 are in their unfired positions. For example, referring primarily to FIGS. 224 and 225, each staple driver 10040 can comprise one or more cradles, or troughs, 10041, for example, which can be configured to support the staples and limit relative movement between the staples 10030 and the staple drivers 10040. Referring again to FIG. 218, the staple cartridge 10000 can further comprise a staple-firing sled 10050 which can be moved from a proximal end 10001 to a distal end 10002 of the

staple cartridge in order to sequentially lift the staple drivers 10040 and the staples 10030 from their unfired positions toward an anvil positioned opposite the staple cartridge 10000. Referring primarily to FIGS. 218 and 220, each staple 10030 can comprise a base 10031 and one or more legs 10032 extending from the base 10031 wherein each staple can be at least one of substantially U-shaped and substantially V-shaped, for example. The staples 10030 can be configured such that the tips of the staple legs 10032 are recessed with respect to the deck surface 10011 of the support portion 10010 when the staples 10030 are in their unfired positions. The staples 10030 can be configured such that the tips of the staple legs 10032 are flush with respect to the deck surface 10011 of the support portion 10010 when the staples 10030 are in their unfired positions. The staples 10030 can be configured such that the tips of the staple legs 10032, or at least some portion of the staple legs 10032, extend above the deck surface 10011 of the support portion 10010 when the staples 10030 are in their unfired positions. In such cases, the staple legs 10032 can extend into and can be embedded within the tissue thickness compensator 10020 when the staples 10030 are in their unfired positions. For example, the staple legs 10032 can extend above the deck surface 10011 by approximately 0.075", for example. The staple legs 10032 can extend above the deck surface 10011 by a distance between approximately 0.025" and approximately 0.125", for example. Further to the above, the tissue thickness compensator 10020 can comprise an uncompressed thickness between approximately 0.08" and approximately 0.125", for example.

[0819] In use, further to the above and referring primarily to FIG. 233, an anvil, such as anvil, 10060, for example, can be moved into a closed position opposite the staple cartridge 10000. As described in greater detail below, the anvil 10060 can position tissue against the tissue thickness compensator 10020 and compress the tissue thickness compensator 10020 against the deck surface 10011 of the support portion 10010, for example. Once the anvil 10060 has been suitably positioned, the staples 10030 can be deployed, as also illustrated in FIG. 233. As mentioned above, the staple-firing sled 10050 can be moved from the proximal end 10001 of the staple cartridge 10000 toward the distal end 10002, as illustrated in FIG. 234. As the sled 10050 is advanced, the sled 10050 can contact the staple drivers 10040 and lift the staple drivers 10040 upwardly within the staple cavities 10012. The sled 10050 and the staple drivers 10040 can each comprise one or more ramps, or inclined surfaces, which can co-operate to move the staple drivers 10040 upwardly from their unfired positions. For example, referring to FIGS. 221-225,

each staple driver 10040 can comprise at least one inclined surface 10042 and the sled 10050 can comprise one or more inclined surfaces 10052 which can be configured such that the inclined surfaces 10052 can slide under the inclined surface 10042 as the sled 10050 is advanced distally within the staple cartridge. As the staple drivers 10040 are lifted upwardly within their respective staple cavities 10012, the staple drivers 10040 can lift the staples 10030 upwardly such that the staples 10030 can emerge from their staple cavities 10012 through openings in the staple deck 10011. During an exemplary firing sequence, referring primarily to FIGS. 227-229, the sled 10050 can first contact staple 10030a and begin to lift the staple 10030a upwardly. As the sled 10050 is advanced further distally, the sled 10050 can begin to lift staples 10030b, 10030c, 10030d, 10030e, and 10030f, and any other subsequent staples, in a sequential order. As illustrated in FIG. 229, the sled 10050 can drive the staples 10030 upwardly such that the legs 10032 of the staples contact the opposing anvil, are deformed to a desired shape, and ejected therefrom the support portion 10010. In various circumstances, the sled 10030 can move several staples upwardly at the same time as part of a firing sequence. With regard to the firing sequence illustrated in FIG. 229, the staples 10030a and 10030b have been moved into their fully fired positions and ejected from the support portion 10010, the staples 10030c and 10030d are in the process of being fired and are at least partially contained within the support portion 10010, and the staples 10030e and 10030f are still in their unfired positions.

[0820] As discussed above, and referring to FIG. 235, the staple legs 10032 of the staples 10030 can extend above the deck surface 10011 of the support portion 10010 when the staples 10030 are in their unfired positions. With further regard to this firing sequence illustrated in FIG. 229, the staples 10030e and 10030f are illustrated in their unfired position and their staple legs 10032 extend above the deck surface 10011 and into the tissue thickness compensator 10020. The tips of the staple legs 10032, or any other portion of the staple legs 10032, may not protrude through a top tissue-contacting surface 10021 of the tissue thickness compensator 10020 when the staples 10030 are in their unfired positions. As the staples 10030 are moved from their unfired positions to their fired positions, as illustrated in FIG. 229, the tips of the staple legs can protrude through the tissue-contacting surface 10032. The tips of the staple legs 10032 can comprise sharp tips which can incise and penetrate the tissue thickness compensator 10020. The tissue thickness compensator 10020 can comprise a plurality of apertures which can be configured to receive the staple legs 10032 and allow the staple legs 10032 to slide relative to the tissue thickness

compensator 10020. The support portion 10010 can further comprise a plurality of guides 10013 extending from the deck surface 10011. The guides 10013 can be positioned adjacent to the staple cavity openings in the deck surface 10011 such that the staple legs 10032 can be at least partially supported by the guides 10013. A guide 10013 can be positioned at a proximal end and/or a distal end of a staple cavity opening. A first guide 10013 can be positioned at a first end of each staple cavity opening and a second guide 10013 can be positioned at a second end of each staple cavity opening such that each first guide 10013 can support a first staple leg 10032 of a staple 10030 and each second guide 10013 can support a second staple leg 10032 of the staple. Referring to FIG. 235, each guide 10013 can comprise a groove or slot, such as groove 10016, for example, within which a staple leg 10032 can be slidably received. Each guide 10013 can comprise a cleat, protrusion, and/or spike that can extend from the deck surface 10011 and can extend into the tissue thickness compensator 10020. As discussed in greater detail below, the cleats, protrusions, and/or spikes can reduce relative movement between the tissue thickness compensator 10020 and the support portion 10010. The tips of the staple legs 10032 may be positioned within the guides 10013 and may not extend above the top surfaces of the guides 10013 when the staples 10030 are in their unfired position. In at least such embodiment, the guides 10013 can define a guide height and the staples 10030 may not extend above this guide height when they are in their unfired position.

[0821] A tissue thickness compensator, such as tissue thickness compensator 10020, for example, can be comprised of a single sheet of material. A tissue thickness compensator can comprise a continuous sheet of material which can cover the entire top deck surface 10011 of the support portion 10010 or, alternatively, cover less than the entire deck surface 10011. The sheet of material can cover the staple cavity openings in the support portion 10010 while, as an alternative, the sheet of material can comprise openings which can be aligned, or at least partially aligned, with the staple cavity openings. A tissue thickness compensator can be comprised of multiple layers of material. Referring now to FIG. 217, a tissue thickness compensator can comprise a compressible core and a wrap surrounding the compressible core. A wrap 10022 can be configured to releasably hold the compressible core to the support portion 10010. For example, the support portion 10010 can comprise one or more projections, such as projections 10014 (FIG. 220), for example, extending therefrom which can be received within one or more apertures and/or slots, such as apertures 10024, for example, defined in the wrap 10022. The

projections 10014 and the apertures 10024 can be configured such that the projections 10014 can retain the wrap 10022 to the support portion 10010. The ends of the projections 10014 can be deformed, such as by a heat-stake process, for example, in order to enlarge the ends of the projections 10014 and, as a result, limit the relative movement between the wrap 10022 and the support portion 10010. The wrap 10022 can comprise one or more perforations 10025 which can facilitate the release of the wrap 10022 from the support portion 10010, as illustrated in FIG. 217. Referring now to FIG. 226, a tissue thickness compensator can comprise a wrap 10222 including a plurality of apertures 10223, wherein the apertures 10223 can be aligned, or at least partially aligned, with the staple cavity openings in the support portion 10010. The core of the tissue thickness compensator can also comprise apertures which are aligned, or at least partially aligned, with the apertures 10223 in the wrap 10222. Alternatively, the core of the tissue thickness compensator can comprise a continuous body and can extend underneath the apertures 10223 such that the continuous body covers the staple cavity openings in the deck surface 10011.

[0822] As described above, a tissue thickness compensator can comprise a wrap for releasably holding a compressible core to the support portion 10010. For example, referring to FIG. 218, a staple cartridge can further comprise retainer clips 10026 which can be configured to inhibit the wrap, and the compressible core, from prematurely detaching from the support portion 10010. Each retainer clip 10026 can comprise apertures 10028 which can be configured to receive the projections 10014 extending from the support portion 10010 such that the retainer clips 10026 can be retained to the support portion 10010. The retainer clips 10026 can each comprise at least one pan portion 10027 which can extend underneath the support portion 10010 and can support and retain the staple drivers 10040 within the support portion 10010. As described above, a tissue thickness compensator can be removably attached to the support portion 10010 by the staples 10030. More particularly, as also described above, the legs of the staples 10030 can extend into the tissue thickness compensator 10020 when the staples 10030 are in their unfired position and, as a result, releasably hold the tissue thickness compensator 10020 to the support portion 10010. The legs of the staples 10030 can be in contact with the sidewalls of their respective staple cavities 10012 wherein, owing to friction between the staple legs 10032 and the sidewalls, the staples 10030 and the tissue thickness compensator 10020 can be retained in position until the staples 10030 are deployed from the staple cartridge 10000. When the staples 10030 are deployed, the tissue thickness compensator 10020 can be captured within the staples

10030 and held against the stapled tissue T. When the anvil is thereafter moved into an open position to release the tissue T, the support portion 10010 can be moved away from the tissue thickness compensator 10020 which has been fastened to the tissue. An adhesive can be utilized to removably hold the tissue thickness compensator 10020 to the support portion 10010. A two-part adhesive can be utilized wherein, a first part of the adhesive can be placed on the deck surface 10011 and a second part of the adhesive can be placed on the tissue thickness compensator 10020 such that, when the tissue thickness compensator 10020 is placed against the deck surface 10011, the first part can contact the second part to active the adhesive and detachably bond the tissue thickness compensator 10020 to the support portion 10010. Any other suitable means could be used to detachably retain the tissue thickness compensator to the support portion of a staple cartridge.

[0823] Further to the above, the sled 10050 can be advanced from the proximal end 10001 to the distal end 10002 to fully deploy all of the staples 10030 contained within the staple cartridge 10000. Referring now to FIGS. 258-262, the sled 10050 can be advanced distally within a longitudinal cavity 10016 within the support portion 10010 by a firing member, or knife bar, 10052 of a surgical stapler. In use, the staple cartridge 10000 can be inserted into a staple cartridge channel in a jaw of the surgical stapler, such as staple cartridge channel 10070, for example, and the firing member 10052 can be advanced into contact with the sled 10050, as illustrated in FIG. 258. As the sled 10050 is advanced distally by the firing member 10052, the sled 10050 can contact the proximal-most staple driver, or drivers, 10040 and fire, or eject, the staples 10030 from the cartridge body 10010, as described above. As illustrated in FIG. 258, the firing member 10052 can further comprise a cutting edge 10053 which can be advanced distally through a knife slot in the support portion 10010 as the staples 10030 are being fired. A corresponding knife slot can extend through the anvil positioned opposite the staple cartridge 10000 such that, the cutting edge 10053 can extend between the anvil and the support portion 10010 and incise the tissue and the tissue thickness compensator positioned therebetween. In various circumstances, the sled 10050 can be advanced distally by the firing member 10052 until the sled 10050 reaches the distal end 10002 of the staple cartridge 10000, as illustrated in FIG. 260. At such point, the firing member 10052 can be retracted proximally. The sled 10050 can be retracted proximally with the firing member 10052 but, referring now to FIG. 261, the sled 10050 can be left behind in the distal end 10002 of the staple cartridge 10000 when the firing

member 10052 is retracted. Once the firing member 10052 has been sufficiently retracted, the anvil can be re-opened, the tissue thickness compensator 10020 can be detached from the support portion 10010, and the remaining non-implanted portion of the expended staple cartridge 10000, including the support portion 10010, can be removed from the staple cartridge channel 10070.

[0824] After the expended staple cartridge 10000 has been removed from the staple cartridge channel, further to the above, a new staple cartridge 10000, or any other suitable staple cartridge, can be inserted into the staple cartridge channel 10070. Further to the above, the staple cartridge channel 10070, the firing member 10052, and/or the staple cartridge 10000 can comprise co-operating features which can prevent the firing member 10052 from being advanced distally a second, or subsequent, time without a new, or unfired, staple cartridge 10000 positioned in the staple cartridge channel 10070. More particularly, referring again to FIG. 258, as the firing member 10052 is advanced into contact with the sled 10050 and, when the sled 10050 is in its proximal unfired position, a support nose 10055 of the firing member10052 can be positioned on and/or over a support ledge 10056 on the sled 10050 such that the firing member 10052 is held in a sufficient upward position to prevent a lock, or beam, 10054 extending from the firing member 10052 from dropping into a lock recess defined within the staple cartridge channel. As the lock 10054 will not drop into the lock recess, in such circumstances, the lock 10054 may not abut a distal sidewall 10057 of the lock recess as the firing member 10052 is advanced. As the firing member 10052 pushes the sled 10050 distally, the firing member 10052 can be supported in its upward firing position owing to the support nose 10055 resting on the support ledge 10056. When the firing member 10052 is retracted relative to the sled 10050, as discussed above and illustrated in FIG. 261, the firing member 10052 can drop downwardly from its upward position as the support nose 10055 is no longer resting on the support ledge 10056 of the sled 10050. For example, the surgical staple can comprise a spring 10058, and/or any other suitable biasing element, which can be configured to bias the firing member 10052 into its downward position. Once the firing member 10052 has been completely retracted, as illustrated in FIG. 262, the firing member 10052 cannot be advanced distally through the spent staple cartridge 10000 once again. More particularly, the firing member 10052 can't be held in its upper position by the sled 10050 as the sled 10050, at this point in the operating sequence, has been left behind at the distal end 10002 of the staple cartridge 10000. Thus, as mentioned above, in the event that the firing member 10052 is advanced once again without replacing the staple cartridge, the lock beam

10054 will contact the sidewall 10057 of the lock recess which will prevent the firing member 10052 from being advanced distally into the staple cartridge 10000 once again. Stated another way, once the spent staple cartridge 10000 has been replaced with a new staple cartridge, the new staple cartridge will have a proximally-positioned sled 10050 which can hold the firing member 10052 in its upper position and allow the firing member 10052 to be advanced distally once again.

[0825] As described above, the sled 10050 can be configured to move the staple drivers 10040 between a first, unfired position and a second, fired position in order to eject staples 10030 from the support portion 10010. The staple drivers 10040 can be contained within the staple cavities 10012 after the staples 10030 have been ejected from the support portion 10010. The support portion 10010 can comprise one or more retention features which can be configured to block the staple drivers 10040 from being ejected from, or falling out of, the staple cavities 10012. Alternatively, the sled 10050 can be configured to eject the staple drivers 10040 from the support portion 10010 with the staples 10030. For example, the staple drivers 10040 can be comprised of a bioabsorbable and/or biocompatible material, such as Ultem, for example. The staple drivers can be attached to the staples 10030. For example, a staple driver can be molded over and/or around the base of each staple 10030 such that the driver is integrally formed with the staple. U.S. Patent Application Serial No. 11/541,123, entitled SURGICAL STAPLES HAVING COMPRESSIBLE OR CRUSHABLE MEMBERS FOR SECURING TISSUE THEREIN AND STAPLING INSTRUMENTS FOR DEPLOYING THE SAME, filed on September 29, 2006, is hereby incorporated by reference in its entirety.

[0826] In various circumstances, further to the above, a compressible tissue thickness compensator can move, twist, and/or deflect relative to the underlying rigid support portion of a staple cartridge. The support portion, and/or any other suitable portion of the staple cartridge, can comprise one or more features configured to limit relative movement between the tissue thickness compensator and the support portion. As described above, at least a portion of the staples 10030 can extend above the deck surface 10011 of the support portion 10010 wherein, in certain circumstances, referring now to FIGS. 263 and 264, lateral forces applied to a tissue thickness compensator 10120, for example, can be resisted by the staples 10030 and/or the cleats 10013 extending from the support portion 10010, for example. In various circumstances, the staples 10030 may tilt and/or bend within the staple cavities 10012 while resisting the lateral

movement of the tissue thickness compensator 10120 wherein the staple cavities 10012 and the staples 10030 can be sized and configured to maintain the relative alignment between the legs 10032 of the staples 10030 and the forming pockets 10062 in the opposing anvil 10060 such that the staples 10000 are properly formed during the staple forming process. The staples 10030 and/or the cleats 10013 can be configured to prevent or at least limit lateral distortion within the tissue thickness compensator 10020, as illustrated in FIG. 264. For example, the staples 10030 and/or cleats 10013, for example, can be configured to stiffen, or limit the lateral and/or longitudinal movement of, a first, or tissue-contacting, surface 10021 of the tissue thickness compensator relative to a second, or bottom, surface 10029. A staple cartridge, and/or a staple cartridge channel in which the staple cartridge is positioned, can comprise at least one distortion minimizing member which can extend upwardly to limit the lateral and/or longitudinal movement, or distortion, of a tissue thickness compensator. A wrap at least partially surrounding a tissue thickness compensator, as discussed above, may also prevent, or at least limit, the lateral and/or longitudinal movement, or distortion, of the tissue thickness compensator.

[0827] Referring again to FIGS. 263 and 264, a tissue thickness compensator, such as tissue thickness compensator 10120, for example, can comprise a core 10128 and a skin 10122. The skin 10122 and the compressible core 10128 can be comprised of different materials or, alternatively, of the same material. In either event, the skin 10122 can have a higher density than the core 10128. In circumstances where the skin 10122 comprises the top of the tissue thickness compensator 10120, the tips of the staple legs 10032 can be embedded in the skin 10122. Wherein a skin comprises the bottom of the tissue thickness compensator 10120, the staple legs 10032 can extend through the skin and into the core. In either event, the skin of the tissue thickness compensator can assist in holding the staple legs 10032 in alignment with the forming pockets 10062 of the anvil 10060. The skin 10122 can comprise a density which is approximately 10% greater than the density of the core 10128, approximately 20% greater than the density of the core 10128, approximately 30% greater than the density of the core 10128, approximately 40% greater than the density of the core 10128, approximately 50% greater than the density of the core 10128, approximately 60% greater than the density of the core 10128, approximately 70% greater than the density of the core 10128, approximately 80% greater than the density of the core 10128, approximately 90% greater than the density of the core 10128, and/or approximately 100% greater than the density of the core 10128, for example. The skin

10122 can comprise a density which is more than the density of the core 10128 and less than twice the density of the core 10128, for example. The skin 10122 can comprise a density which is over twice the density of the core 10128, for example. Further to the above, the skin 10122 and the core 10128 can be formed, or manufactured, simultaneously. For example, a fluid comprising any suitable material disclosed herein can be poured into a dish or mold and, while the fluid solidifies, the fluid can form a skin, or layer, which has a higher density than the remainder of the material. Multiple layers within a material can be formed by utilizing a process in which one or more subsequent layers of material are poured onto a previously cured layer. Two or more layers can be bonded to each other with an adhesive, for example. Two or more layers can be attached to each other by one or more fasteners and/or one or more mechanical interlocking features, for example. For example, adjacent layers can be connected together by one or more dovetail joints, for example. The skin can comprise a sealed surface which can prevent, or at least limit, the flow of fluid therethrough. Alternatively, the skin can comprise an open cell porous structure, for example.

[0828] Further to the above, the skin can be cut off of the tissue thickness compensator. The tissue thickness compensator can be cut from a larger block of material such that the tissue thickness compensator does not comprise a skin. For example, the tissue thickness compensator can be comprised of a homogenous, or at least substantially homogeneous, material, comprising large pores, for example.

[0829] A staple cartridge can comprise a plurality of staple cavities each containing a staple positioned therein wherein the staple cavities can be arranged in a plurality of rows, and wherein an anvil positioned opposite the staple cartridge can comprise a plurality of forming pockets which correspond to the staple cavities in the staple cartridge. Stated another way, the anvil can comprise a plurality of forming pocket rows wherein each forming pocket can be positioned opposite a staple cavity in the staple cartridge. Each forming pocket can comprise two forming cups configured to receive the staple legs 10032 of a staple 10030 wherein each forming cup is configured to receive a staple leg 10032 and form or curl the staple leg 10032 toward the other staple leg 10032, for example. In various circumstances, the legs 10032 may miss or not properly enter into the forming cups and, as a result, the staple legs 10032 may become malformed during the firing sequence. An anvil can comprise an array, or grid, of forming pockets which are each configured to receive and form a staple leg. For example, the array of forming pockets can

comprise a quantity of forming pockets that exceeds the quantity of staples contained within the staple cartridge. A staple cartridge can comprise six longitudinal rows of staple cavities, for example, wherein the anvil can comprise six rows of forming pockets aligned with the six rows of staple cavities and, in addition, forming pockets positioned intermediate the rows of forming pockets. For example, on one side of the anvil, the anvil can comprise a first row of forming pockets which can be positioned over a first row of staple cavities, a second row of forming pockets which can be positioned over a second row of staple cavities that is adjacent to the first row of staple cavities, and, in addition, a row of forming pockets positioned intermediate the first row of forming pockets and the second row of forming pockets. Referring now to FIGS. 276-279, an anvil 10260 can comprise six rows of forming pockets 10261 which can be configured to be placed over six corresponding rows of staple cavities in the staple cartridge 10200. For example, rows of intermediate forming pockets 10262 can be positioned intermediate and/or adjacent to the rows of forming pockets 10261. Referring now to FIGS. 277, 278, and 280, each forming pocket 10261 and 10262 can comprise two forming cups, wherein each forming cup can comprise a distal portion 10263 which can be configured to form or curl a staple leg 10032 proximally and a proximal portion 10264 which can be configured to form or curl a staple leg 10032 distally. In various other circumstances, the staples 10030 can be formed in a variety of other ways. For example, a staple 10030 can be formed such that one leg 10032 is formed outwardly and the other leg 10032 is formed inwardly (FIG. 281), or such that both legs 10032 are formed outwardly (FIG. 282) depending on, one, which forming cups that the staple legs 10032 enter into and/or, two, whether the legs 10032 enter into the proximal portion 10263 or the distal portion 10064 of each forming cup, for example.

[0830] Further to the above, each forming pocket 10261 and/or forming pocket 10262 can comprise a triangular or diamond-like shape, for example. Each distal portion 10263 and/or each proximal portion 10264 of the forming pockets can comprise a triangular shape wherein, for example, the triangular shapes of the distal portions 10263 and the proximal portions 10264 can be arranged such that they have vertices pointing in opposite directions. The anvil can comprise an array of substantially square forming pockets, for example. For example, the forming surface of each square forming pocket can comprise an arcuate surface that extends between the sides of the square. The anvil can comprise an array of circular or spherical dimples, for example. Further to the above, the forming pockets 10261 can be positioned along one or more lines and,

similarly, the forming pockets 10262 can also be positioned along one or more lines. Alternatively, the forming pockets 10261 and/or the forming pockets 10262 can be arranged in one or more circular rows. For example, the forming pockets 10261 can be arranged along a primary circumference and the forming pockets 10262 can be arranged along a different circumference. The primary circumference and the different circumference can be concentric, or at least substantially concentric. The forming pockets 10262 can be arranged along an inner circumference positioned radially inwardly with respect to the primary circumference and/or an outer circumference positioned radially outwardly with respect to the primary circumference, for example. The primary circumference can be defined by a primary diameter, the inner circumference can be defined by an inner diameter, and the outer circumference can be defined by an outer diameter. For example, the inner diameter can be shorter than the primary diameter and the outer diameter can be longer than the primary diameter.

[0831] As described above, an anvil can be moved from an open position to a closed position in order to compress tissue against the tissue thickness compensator of a staple cartridge, such as tissue thickness compensator 10020, for example. In various circumstances, the tissue thickness compensator can be positioned adjacent to the support portion of the staple cartridge prior to the tissue thickness compensator being positioned relative to the tissue. The tissue thickness compensator 10020 can be in a position in which it abuts the support portion 10018 prior to the anvil being moved into its closed position. Alternatively, the tissue thickness compensator 10020 can be in a position in which a gap is present between the tissue thickness compensator 10020 and the support portion 10018. For example, the anvil can displace the tissue and the tissue thickness compensator 10020 downwardly until the tissue thickness compensator 10020 abuts the support portion 10018 wherein, at such point, the anvil can be moved into is closed position and generate compression within the tissue. In the event that a surgeon is not satisfied with the positioning of the tissue between the anvil and the staple cartridge, the surgeon can open the anvil, adjust the position of the anvil and the staple cartridge, and close the anvil once again. Owing to such positioning and re-positioning of the staple cartridge relative to the tissue, in various circumstances, the distal end of the tissue thickness compensator 10020 may become dislodged from the support portion 10010, for example. In some such circumstances, the distal end of the tissue thickness compensator 10020 can contact the tissue and peel away from, or roll relative to, the support portion 10010. As described in greater detail below, a staple cartridge can

comprise one or more features configured to releasably retain a tissue thickness compensator to an underlying support portion of the staple cartridge

[0832] Referring now to FIG. 265, a staple cartridge 10300 can comprise a support portion 10310, a tissue thickness compensator 10320 supported by the support portion 10310, and a distal end 10302 which includes a nose 10303 configured to releasably hold a distal end 10325 of the tissue thickness compensator 10320 in position. The nose 10303 can comprise a slot 10305 configured to receive the distal end 10325 of the tissue thickness compensator 10320. The distal end 10325 can be compressed, or wedged, within the slot 10305 such that the distal end 10325 can be held in place as the staple cartridge 10300 is positioned relative to the tissue. For example, the slot 10305 can be oriented in a direction which is parallel, or at least substantially parallel, to the deck surface 10311 of the support portion 10310. The slot 10305 can be horizontal with respect to the deck surface 10311. Alternatively, referring now to FIG. 266, a staple cartridge 10400 can comprise a support portion, a tissue thickness compensator 10420 supported by support portion, and a distal end 10402 which includes a nose 10403 configured to releasably hold the distal end 10425 of the tissue thickness compensator 10420 in position. The distal end 10425 can comprise a projection extending therefrom and the nose 10403 can comprise a vertical slot 10405 configured to receive the projection of the distal end 10425. The distal end 10425, and/or the projection extending therefrom, can be compressed, or wedged, within the slot 10405 such that the distal end 10425 can be held in place as the staple cartridge 10400 is positioned relative to the tissue. The tissue thickness compensator 10420 can comprise a slot, such as slot 10429, for example, which can be configured to receive at least a portion of the nose 10403 therein. The slot 10405 can be oriented in a direction which is perpendicular, or at least substantially perpendicular, to the deck surface 10411 of the support portion. Referring now to FIG. 267, a staple cartridge 10500 can comprise a support portion, a tissue thickness compensator 10520 supported by the support portion, and a distal end 10502 which includes a nose configured to releasably hold the distal end 10525 of the tissue thickness compensator 10520 in position. The nose can comprise a vertical slot 10505 configured to receive the distal end 10525 of the tissue thickness compensator 10520. The distal end 10525 can be compressed, or wedged, within the slot 10505 such that the distal end 10525 can be held in place as the staple cartridge 10500 is positioned relative to the tissue.

[0833] Referring again to FIG. 265, the tissue thickness compensator 10320 can comprise a top surface 10324 which can be positioned above the top surface 10304 of the nose 10303. Another exemplary embodiment in which the top surface of a tissue thickness compensator is positioned above the nose of the staple cartridge is illustrated in FIG. 238, wherein the top surface 10721 of the tissue thickness compensator 10720 is positioned above the top surface 10004 of the nose 10003, for example. In use, referring once again to FIG. 265, tissue can slide over the top surface 10304 of the nose 10303 and, in some circumstance, the tissue can contact the distal end 10325 of the tissue thickness compensator 10320 and can apply a force to the tissue thickness compensator 10320 tending to peel the tissue thickness compensator 10320 away from the support portion 10310. In the embodiments described herein, this peel force can be resisted by the portion of the distal end 10325 wedged within the nose 10303. In any event, once the tissue has been suitably positioned relative to the staple cartridge 13000, an anvil can be rotated into a closed position to compress the tissue and the tissue thickness compensator 10320 against the support portion 10310. For example, the anvil can be rotated into a position in which the anvil contacts the top surface 10304 of the nose 10303 and, as a result, the anvil can be prevented from rotating further. In various circumstances, owing to the top surface 10324 of the tissue thickness compensator 10320 being positioned above the top surface 10304 of the nose 10303, the top surface 10324 can be pushed downwardly toward the support portion 10310 as the anvil is being closed and, in some circumstances, the top surface 10324 can be pushed below the top surface 10304 of the nose 10303, for example. After the staples contained within the staple cartridge 10300 have been deployed and the tissue thickness compensator 10320 has been incised, as described herein, the support portion 10310 and the nose 10303 can be moved away from the tissue thickness compensator 10320 such that the distal end 10325 of the tissue thickness compensator 10320 can slide out of the slot 10305.

[0834] As described above, an anvil, such as anvil 10060, for example, can be rotated into a closed position in which the anvil 10060 contacts the top nose surface 10004 of a staple cartridge, such as staple cartridge 10000, for example. Once the anvil has reached its closed position, the amount in which a tissue thickness compensator, such as tissue thickness compensator 10020, for example, is compressed will depend on, among other things, the uncompressed thickness, or height, of the tissue thickness compensator and the thickness of the tissue. Referring now to FIGS. 236 and 237, a tissue thickness compensator 10920 can comprise

a top surface which is flush, or at least substantially flush, with the top surface 10004 of the nose 10003. In such cases, the top surface of the tissue thickness compensator 10920 can be pushed below the top surface 10004 of the nose 10003. Referring now to FIGS. 241 and 242, a tissue thickness compensator, such as tissue thickness compensator 10820, for example, can comprise a top surface 10821 which is positioned below the top nose surface 10004 prior to the tissue thickness compensator 10820 being compressed by the tissue T and anvil 10060. In the circumstances where the tissue T is relatively thin, as illustrated in FIGS. 239 and 240, the tissue thickness compensator 10920 may undergo relatively little compression. Referring now to FIGS. 241 and 242, the tissue thickness compensator 10820 may undergo a larger compression when the tissue T is relatively thicker. In the circumstances where the tissue T has both thin sections and thicker sections, as illustrated in FIGS. 243 and 244, the tissue thickness compensator 10820 may be compressed a larger amount when it is positioned under the thicker tissue T and a lesser amount when it is positioned under the thinner tissue T, for example. In this way, as described above, the tissue thickness compensator can compensate for different tissue thicknesses.

[0835] Referring now to FIGS. 268-270, a surgical stapling instrument can comprise, one, a cartridge channel 16670 configured to receive a staple cartridge 16600 and, two, an anvil 16660 pivotably coupled to the cartridge channel 16670. The staple cartridge 16600 can comprise a support portion 16610 and a tissue thickness compensator 16620 wherein a distal end 16625 of the tissue thickness compensator 16620 can be releasably held to the support portion 16610 by a nose 16603 at the distal end 16602 of the staple cartridge 16600. The nose 16603 can comprise a slot 16605 and can be comprised of a flexible material. In use, referring primarily to FIG. 269, the nose 16603 can be flexed downwardly in order to expand the opening of slot 16605. The nose 16603 can comprise notches or cut-outs 16606 which can be configured to permit the nose 16603 to flex downwardly. In any event, in various circumstances, the expanded opening of the slot 16605 can facilitate the insertion of the distal end 16625 of the tissue thickness compensator 16620 into the slot 16605. Once the tissue thickness compensator 16620 has been suitably positioned, the nose 16603 can be released and, owing to the resiliency of the material comprising the nose 16603, the nose 16603 can return, or at least substantially return, to its unflexed condition and trap the distal end 16625 of the tissue thickness compensator 16620 against the deck surface 16611, as illustrated in FIG. 270. In use, similar to the above, the distal end 16625 can be pulled out of the slot 16605 when the support portion 16610 is moved away

from the stapled tissue. In various circumstances, the flexible nose 16603 can be configured to deflect as the tissue thickness compensator 16620 is detached from the support portion 16610. Referring again to FIG. 270, the tissue thickness compensator 16620 can comprise a top surface 16621 which is aligned, or at least substantially aligned, with a top surface 16604 of the nose 16603.

[0836] Referring to FIG. 271, a surgical stapling instrument can comprise, one, a channel 10770 configured to receive a staple cartridge 10700 and, two, an anvil 10760 rotatably coupled to the channel 10770. The staple cartridge 10700 can comprise a support portion 10710 and a tissue thickness compensator 10720. The tissue thickness compensator 10720 can be held in position by a nose sock 10703 which can be slid over the support portion 10710. Referring primarily to FIG. 272, the nose sock 10703 can comprise one or more side slots 10707 which can be configured to removably receive one or more attachment rails extending along the support portion 10710, for example. The tissue thickness compensator 10720 can be positioned intermediate the side slots 10707. The nose sock 10703 can further comprise a distal end 10702 and a cavity 10706 defined in the distal end 10702 wherein the cavity 10706 can also be configured to receive at least a portion of the support portion 10710, for example, therein. In use, the nose sock 10703 can be slid onto the support portion 10710 in a distal to proximal direction. The tissue thickness compensator 10720 can be removably mounted to the nose sock 10703 such that, after staples have been fired through the tissue thickness compensator 10720, the tissue thickness compensator 10720 can detach from the nose sock 10703 as the support portion 10710 and the nose sock 10703 are moved away from the tissue thickness compensator 10720. The top surface 10721 of the tissue thickness compensator 10720 can be positioned below the top surface 10704 of the nose 10703.

[0837] Referring now to FIGS. 273 and 274, a surgical stapling instrument can comprise, one, a staple cartridge channel 11070 configured to receive a staple cartridge 11000 and, two, an anvil 11060 rotatably coupled to the channel 11070. The staple cartridge 11000 can comprise a support portion 11010 and a tissue thickness compensator 11020. The tissue thickness compensator 11020 can be held in position by a one or more longitudinal rails 11019 extending from the deck 11011 of the support portion 11010. The longitudinal rails 11019 can be embedded within the tissue thickness compensator 11020. Referring primarily to FIG. 274, the tissue thickness compensator 11020 can comprise a longitudinal recess 11029 which can be

configured to receive the longitudinal rails 11019. For example, the recess 11029 can be sized and configured to receive the rails 11019 in a press-fit arrangement, for example. Such features, further to the above, can be configured to prevent, or at least limit, relative lateral movement between the tissue thickness compensator 11020 and the support portion 11010 and, in addition, limit the pre-mature release of the tissue thickness compensator 11020 from the support portion 11010, for example. Referring now to FIG. 275, a surgical stapling instrument can comprise, one, a staple cartridge channel 11170 configured to receive a staple cartridge 11100 and, two, an anvil 11160 rotatably coupled to the channel 11170. The staple cartridge 11100 can comprise a support portion 11110 and a tissue thickness compensator 11120. The tissue thickness compensator 11120 can be held in position by one or more longitudinal rows of spikes, or teeth, 11119 extending from the deck 11111 of the support portion 11110. The longitudinal rows of spikes 11119 can be embedded within the tissue thickness compensator 11120.

[0838] With regard to FIG. 273, further to the above, the tissue thickness compensator 11020 of the staple cartridge 11000 can be progressively released from the support portion 11010 as the staples are ejected from the staple cavities 10012 defined therein. More particularly, further to the above, the staples positioned in the staple cavities 10012 can be ejected sequentially between the proximal end 11001 of the staple cartridge 11000 and the distal end 11002 of the staple cartridge 11000 such that, as the staples are being ejected, the staples can apply an upward biasing force to the tissue thickness compensator 11020 which acts to push the tissue thickness compensator 11020 off of the rails 11019. In such circumstances, the proximal end 11006 of the tissue thickness compensator 11020 can be released from the support portion 11010 as the staples are ejected from the proximal-most staple cavities 10012. The tissue thickness compensator 11020 can then be progressively released from the support portion 11010 as the staples are progressively ejected from the support portion 11010 between the proximal end 11001 and the distal end 11002 of the staple cartridge 11000. When the staples positioned within the distal-most staple cavities 10012 are ejected from the support portion 11010, the distal end 11007 of the tissue thickness compensator 11020 can be released from the support portion 11010. With regard to FIG. 275, the tissue thickness compensator 11120 can be progressively released from the spikes 1119 extending from the support portion 11110 as the staples are progressively ejected from the staple cartridge between the proximal end 11101 and the distal end 11102.

[0839] As discussed above, a tissue thickness compensator can be progressively released from the support portion of a staple cartridge as the staples are progressively ejected from the support portion and contact the tissue thickness compensator. The legs of the staple, such as staple legs 10032, for example, may be able to pass through the tissue thickness compensator without releasing the tissue thickness compensator from the support portion. In such cases, the tissue thickness compensator may remain engaged with the support portion until the bases of the staples, such as bases 10031, contact the tissue thickness compensator and push it upwardly. However, cleats and/or other retention features extending from the support portion, for example, may oppose the release of the tissue thickness compensator from the support portion. As described in greater detail below, a support portion can comprise retention features which can be configured to progressively release a tissue thickness compensator from the support portion as the staples are progressively fired from the staple cartridge. Referring now to FIG. 283, a staple cartridge, such as staple cartridge 11200, for example, can comprise a support portion 11210 including retention features 11213 which can be configured to releasably hold a tissue thickness compensator 11220 (FIG. 284) to the support portion 11210. The retention features 11213 can be positioned at the ends of each staple cavity 11212, for example, wherein each retention feature 11213 can comprise a guide groove 11216 defined therein which is configured to slidably receive a staple leg 10032 of a staple 10030. In such cases, both the staple legs 10032 and the retention features 11213 can be configured to releasably retain the tissue thickness compensator 11220 to the support portion 11210. In use, referring now to FIG. 284, staple drivers 10040 contained within the support portion 11210 can be driven upwardly by a sled 10050, as described above, wherein the staple drivers 10040 can be configured to contact the retention features 11213, at least partially detach the retention features 11213 from the support portion 11210, and displace the retention features 11213 outwardly and away from the staples 10030 and the staple cavities 11212. When the retention features 11213 are detached from the support portion 11210 and/or displaced outwardly, as illustrated in FIG. 284, the retention features 11213 may no longer be able to retain the tissue thickness compensator 11220 to the support portion 11210 and, as a result, the tissue thickness compensator 11220 can be released from the support portion 11210. Similar to the above, the tissue thickness compensator 11220 can be progressively released from the support portion 11210 as the staples 10030 are progressively ejected from the staple cartridge toward an anvil, such as anvil 11260, for example. The staple drivers 10040 may

contact the retention features 11213 when the top surfaces of the staple drivers 10040 become co-planar, or at least substantially co-planar, with the deck surface 11211 of the support portion 11210, for example. In such cases, the tissue thickness compensator 11220 may be released from the support portion 11210 at the same time as and/or just before the staples 10030 are formed to their fully-formed, or fully-fired, configuration. For example, referring primarily to FIG. 285, the drivers 10040 can be overdriven such that they are pushed above the deck surface 11211 to fully form the staples 10030 and, during the process of being overdriven, break the retention features 11213 away from the support portion 11210. Referring again to FIG. 284, the retention features 11213 may extend over, or overhang, into the staple cavities 11212 prior to being detached or displaced outwardly such that the drivers 10040 can contact the retention features 11213 just as the drivers 10040 reach the deck surface 11211. In any event, once the tissue thickness compensator 11220 has been released from the support portion 11210, referring now to FIG. 285, the support portion 11210 can be moved away from the implanted tissue thickness compensator 11220.

[0840] As described above, a compressible tissue thickness compensator of a staple cartridge can be progressively released from a support portion, or cartridge body, of the staple cartridge as the staples are fired, or deployed, from the staple cartridge. In various circumstances, such a release can comprise a progressive loosening of the tissue thickness compensator from the support portion wherein, in some circumstances, a complete detachment of the tissue thickness compensator from the support portion may not occur until the anvil is opened and the support portion is moved away from the implanted tissue thickness compensator. Referring now to FIG. 289, a staple cartridge, such as staple cartridge 11300, for example, can comprise a tissue thickness compensator 11320 which is releasably retained to a support portion 11310. The support portion 11310 can comprise a plurality of retention members 11313 extending therefrom which are configured to releasably compress and hold the longitudinal sides of the tissue thickness compensator 11320 to the support portion 11310. For example, each retention member 11313 can comprise an inwardly-facing channel or slot 11316 which can be configured to receive the longitudinal sides of the tissue thickness compensator 11320 therein. In various circumstances, a plurality of retention members 11313 can extend along a first longitudinal side of the support portion 11310 and a plurality of retention members 11313 can extend along a second longitudinal side of the support portion 11310 wherein, in certain circumstances, the

retention members 11313 can be configured to prevent, or at least limit, relative lateral movement between the tissue thickness compensator 11320 and the support portion 11310 and, in addition, prevent, or at least limit, the premature release of the tissue thickness compensator 11320 from the support portion 11310. The retention members 11313 can be integrally formed with the support portion 11310 and, referring to FIG. 290, the retention members 11313 can be configured to detach, or at least partially detach, from the support portion 11310 in order to allow the tissue thickness compensator 11320 to detach from the support portion 11310, as illustrated in FIG. 291, for example. The anvil, such as anvil 11360, for example, can be configured to compress the tissue thickness compensator 11320 and, in response to pressure generated within the tissue thickness compensator 11320, the tissue thickness compensator 11320 can expand laterally to at least partially detach, or disengage, the retention members 11313 from the tissue thickness compensator 11320. The advancement of a knife member, discussed above, through the anvil 11360 and the staple cartridge 11300 can deploy the staples contained therein and, simultaneously, squeeze the anvil 11360 and the staple cartridge 11300 closer to one another which can apply an added compressive pressure to the tissue thickness compensator 11320 and thereby cause the retention members 11313 to sequentially detach as the knife member passes through the staple cartridge 11300.

[0841] Referring now to FIGS. 292-294, a staple cartridge, such as staple cartridge 11400, for example, can comprise a tissue thickness compensator 11420 removably attached to a support portion 11410. The staple cartridge 11400 can comprise one or more retainer bars 11413 which can be configured to hold the longitudinal sides of the tissue thickness compensator 11420 to the deck surface 11411. For example, each retainer bar 11413 can comprise opposing arms 11418 which can define a channel 11416 therebetween. In such cases, one of the arms 11418 can be configured to extend over the tissue thickness compensator 11420 and the other arm 11418 can be configured to extend under a lip 11419 extending from the support portion 11410. Referring primarily to FIG. 292, the channel 11416 of each retainer bar 11413 can be sized and configured to apply a compressive force to the longitudinal sides of the tissue thickness compensator 11420 prior to the staple cartridge 11400 being used. During use, referring primarily to FIG. 293, the staple cartridge 11400 can be positioned within a staple cartridge channel and, once the staple cartridge 11400 has been suitably positioned, an anvil, such as anvil 11460, for example, can be moved into a position in which it can compress the tissue thickness compensator 11420. Similar

to the above, the thickness tissue compensator 11420, when compressed, can expand laterally, or outwardly, and, as a result, detach the retainer bars 11413 from the staple cartridge 11400. Alternatively, the closing of the anvil 11460 may not detach, or may not completely detach, the retainer bars 11413 from the staple cartridge. For example, the advancement of a firing bar, described above, through the staple cartridge 11400 can deploy the staples 10030 from the support portion 11410 and, simultaneously, squeeze the anvil 11460 and the staple cartridge 11400 closer together to apply a compressive force to the tissue thickness compensator 11420 that is sufficient to cause the tissue thickness compensator 11420 to expand laterally and detach the retainer bars 11413 from the staple cartridge 11400. Once the retainer bars 11413 have been detached from the staple cartridge 11400, referring to FIG. 294, the support portion 11410 can be moved away from the implanted tissue thickness compensator 11420 and removed from the surgical site. In certain alternative embodiments, referring now to FIG. 295, a staple cartridge 11400' can comprise retainer bars 11413' which, similar to the above, can comprise arms 11418' extending therefrom. For example, each of the arms 11418' can comprise a wedge-lock bevel 11417' which can be configured to releasably latch the retainer bars 11413' to the staple cartridge 11400'. More particularly, the support portion 11410' of the staple cartridge 11400'can comprise undercuts 11419' which, in co-operation with the wedge-lock bevels 11417', can be configured to releasably retain the retainer bars 11413' to the staple cartridge 11400 and inhibit the tissue thickness compensator 11420 from being prematurely detached from the support portion 11410'. During use, similar to the above, the retainer bars 11413' can be detached from the staple cartridge 11400' when a sufficient compressive force is applied to the tissue thickness compensator 11420, for example.

[0842] In various circumstances, as described above and referring again to FIGS. 259 and 260, the sled 10050 of the staple cartridge 10000 and the firing member 10052 of a surgical stapling instrument can be moved from the proximal end 10001 of the staple cartridge 10000 to the distal end 10002 (FIG. 219) of the staple cartridge 10000 in order to deploy the staples 10030 from the support portion 10010. In at least one such circumstance, each staple 10030 can be moved from an unfired position to a fired position and ejected from the support portion 10010 to capture the entirety of the tissue thickness compensator 10020 against the tissue positioned between the anvil 10060 and the staple cartridge 10000. In certain circumstances, a surgeon may not need to fire all of the staples 10030 from the staple cartridge 10000 and the surgeon may stop the

progression of the sled 10050 and the firing bar 10052 at a point located intermediate the proximal end 10001 and the distal end 10002 of the staple cartridge 10000. In such circumstances, the tissue thickness compensator 10020 may only be partially implanted to the tissue T and, in order to detach the unimplanted portion of the tissue thickness compensator 10020 from the support portion 10010, the surgeon can pull the support portion 10010 away from the partially implanted tissue thickness compensator 10020 such that the unimplanted portion peels or pulls off of the support portion 10010. While such embodiments are suitable in various circumstances, an improvement is illustrated in FIGS. 300-302 wherein a tissue thickness compensator, such as tissue thickness compensator 11520 of staple cartridge 11500, for example, can comprise a plurality of connected segments which can be configured to detach from one another. For example, the tissue thickness compensator 11520 can comprise a first, or proximal-most, segment 11520a, a second segment 11520b removably connected to the first segment 11520a, a third segment 11520c removably connected to the second segment 11520b, a fourth segment 11520d removably connected to the third segment 11520c, and a fifth segment 11520e removably connected to the fourth segment 11520d, for example. The tissue thickness compensator 11520 can comprise at least one thin section 11529 positioned intermediate any two adjacent segments 11520a-11520e which can be configured to define a pre-determined rupture or separation point in which the tissue thickness compensator segments can separate from one another. The tissue thickness compensator can include any suitable arrangement of perforations, thin sections, and/or any other means for creating a separation point within the tissue thickness compensator. Referring primarily to FIG. 301, an anvil 11560 is illustrated in a closed position and the firing member 10052 is illustrated as having been partially advanced through the staple cartridge 11500 such that the staples 10030 underlying the first segment11520a, the second segment 11520b, and the third segment 11520c have been fired to capture the tissue thickness compensator 11520 against the tissue T. In such a position, the firing member 10052 has not yet been advanced to deploy the staples 10030 underlying the fourth segment 11520d and the fifth segment 11520e, for example. Referring now to FIG. 302, the anvil 11560 has been moved into an open position and the support portion 11510 of the staple cartridge 11500 has been moved away from the portion of the tissue thickness compensator 11520 that has been implanted. As illustrated in FIG. 302, the thin section 11529 (FIG. 300) located intermediate the third segment

11520c and the fourth segment 11520d has allowed the unimplanted portion of the tissue thickness compensator 11520 to separate from the implanted portion.

[0843] Further to the above, a staple cartridge can comprise a plurality of fasteners configured to releasably hold a tissue thickness compensator to a support portion of the staple cartridge. The support portion can comprise a plurality of apertures defined in the deck surface, for example, wherein the fasteners can extend through the tissue thickness compensator and can be releasably retained in the support portion apertures. In use, the fasteners can be progressively released from the support portion as the staples are progressively ejected from the support portion. For example, the fasteners can be implanted with the tissue thickness compensator and, the fasteners can be comprised of at least one bioabsorbable material, for example. The fasteners can detach from the support portion after the tissue thickness compensator has been at least partially implanted and as the support portion is moved away from the implanted tissue thickness compensator. Referring now to FIGS. 323-325, a staple cartridge, such as staple cartridge 11600, for example, can comprise a tissue thickness compensator 11620 releasably mounted to a support portion 11610 by a plurality of fasteners 11613. Each fastener 11613 can comprise a first end 11618 embedded within and/or otherwise engaged with the tissue thickness compensator 11620, a second end 11618 engaged with the support portion 11610, and a connector 11616 which connects the first end 11618 to the second end 11618. The fasteners 11613 can extend through a knife slot 11615 defined in the support portion 11610. In use, the firing member 10052, described above, can move a knife edge through the knife slot 11615 in the support portion 11610 and incise the fasteners 11613 in order to release the tissue thickness compensator 11620 from the support portion 11610. For example, the firing bar 10052 can be advanced from a proximal end 11601 of the staple cartridge 11600 to a distal end 11602 of the staple cartridge 11600 in order to, one, advance the sled 10050 distally and progressively fire the staples 10030, as discussed above, and, two, progressively incise and/or break the fasteners 11613 to progressively release the tissue thickness compensator 11620 from the support portion 11610. Similar to the above, the tissue thickness compensator 11620 can comprise a plurality of detachable segments 11620a-11620e which can each be held to support portion 11610 by one or more fasteners 11613, for example. In the event that the firing member 10052 is stopped intermediate the proximal end 11601 and the distal end 11602 of the staple cartridge 11600, as illustrated in FIG. 324, the fasteners 11613 can assist in holding the unimplanted portion of the

tissue thickness compensator 11620 to the support portion 11610 after the anvil 11660 is opened and the support portion 11610 is moved away from the tissue T, as illustrated in FIG. 325. Further to the above, the cutting edge 10053 of the firing member 10052 can be configured to incise and/or break the fasteners 11613. In certain alternative embodiments, referring now to FIGS. 327 and 328, a staple-deploying sled, such as sled 11650, for example, can comprise a knife edge 11653 which can be configured to incise the connectors 11616 of the fasteners 11613 as the sled 11650 traverses the staple cartridge 11600. For example, each connector 11616 can comprise a cylindrical member extending between the T-shaped ends 11618 of the fasteners 11613 wherein the knife edge 11653 can comprise a concave profile 11653 which can be configured to receive the cylindrical connector 11616, for example.

[0844] As discussed above, a staple cartridge can be loaded into a staple cartridge channel of a surgical stapling instrument. In various circumstances, a surgeon, or other clinician, may insert the staple cartridge into the staple cartridge channel by placing a downward force onto the staple cartridge to lock the staple cartridge in place. In some such circumstances, the clinician may place their thumb, for example, on the top surface of the staple cartridge to apply such a downward force. The top surface of the staple cartridge may comprise the top surface of a tissue thickness compensator wherein, as described above, the tissue thickness compensator can be compressible and the downward force applied to tissue thickness compensator can cause the tissue thickness compensator to compress to the point in which the clinician's thumb comes into contact with the tips of the staples stored within the support portion. A staple cartridge applicator can be utilized to insert a staple cartridge into a staple cartridge channel which can be configured to prevent, or at least limit, the possibility of the clinician touching the staples in the staple cartridge. After the staple cartridge has been suitably positioned within the staple cartridge channel, as described in greater detail below, the applicator can be detached from the staple cartridge.

[0845] Referring now to FIGS. 305 and 306, a staple cartridge applicator can comprise a rigid cover, such as cover 10080, for example, which can be attached to a staple cartridge 10000. Further to the above, the cover 10080 can be configured to prevent, or at least inhibit, a clinician's thumb, for example, from contacting the tips of the staples 10030 positioned within the staple cartridge 10000 when the staple cartridge 10000 is inserted into a staple cartridge channel. Referring now to FIGS. 307 and 308, the cover 10080 can extend over the top surface

10021, or at least a portion of the top surface 10021, of the tissue thickness compensator 10020 and can include, one, a bottom surface 10081 which can extend over and/or abut the tissue thickness compensator 10020 and, two, a top surface 10082 which can provide a pushing surface for the clinician to apply a downward force thereto, for example. In use, the clinician can grab a handle portion 10084 of the cover 10080, align the support portion 10010 of the staple cartridge 10000 with the staple cartridge channel, and at least partially insert the staple cartridge 10000 within the staple cartridge channel. Thereafter, the clinician can completely seat the staple cartridge 10000 in the staple cartridge channel by applying the downward force to the top surface 10082 of the cover 10880 which can transmit the downward force directly to the support portion 10010. For example, the cover 10080 can comprise proximal supports 10087 which can extend downwardly and contact the deck surface 10011 of the support portion. The cover 10080 can further comprise a distal support portion 10083 which can be configured to abut the nose 10003. When a downward force is applied the cover 10080, the downward force can be transmitted through the proximal supports 10087 and/or the distal support portion 10083 without transmitting, or at least without substantially transmitting, the downward force to the support portion 10010 through the tissue thickness compensator 10020. In various circumstances, as a result of the above, the clinician may not directly contact the tissue thickness compensator 10020. Also as a result of the above, the cover 10080 may not compress, or at least substantially compress, the tissue thickness compensator 10020 as the staple cartridge 10000 is being inserted into the staple cartridge channel. A cover can comprise any suitable number of supports which are configured to transmit a downward force to the support portion without transmitting, or at least substantially transmitting, the downward force through the tissue thickness compensator. The supports can extend around the distal end, the proximal end, and/or the longitudinal sides of the tissue thickness compensator. The supports can extend through the tissue thickness compensator. For example, the supports can extend through apertures within the tissue thickness compensator and abut the deck of the support portion. At least some of the supports may not be in contact with the deck before the downward force is applied to the cover; however, the cover can be configured to flex, or move, downwardly until the supports contact the deck of the support portion. At such point, the downward flexure, or movement, of the cover can be impeded, or at least substantially impeded, from flexing further.

[0846] As described above, the cover 10080 can be attached to the staple cartridge 10000 and can be used to manipulate the position of the staple cartridge 10000. The cover 10080 can comprise any suitable number of gripping members which can be configured to releasably hold the cover 10080 to the support portion 10010 of the staple cartridge 10000, for example. For example, the cover 10080 can further comprise one or more retention members, such as latch arms 10088 and/or 10089, for example. The latch arms 10089 can be configured to extend around the sides of the nose 10003 and engage the bottom surface 10009 (FIG. 306) of the nose 10003. Similarly, the latch arms 10088 can extend around the sides of lock projections 10008 extending from the support portion 10010 and engage the bottom surfaces of the lock projections 10008. These latch arms can be configured to position the cover 10080 over the zone or region in which the staples are stored within the support portion 10010. In any event, once the staple cartridge 10000 has been suitably positioned, the cover 10080 can be detached from the staple cartridge 10000. The clinician can apply an upward lifting force to the handle 10084 in order to detach the distal end of the cover 10080 from the distal end 10002 of the staple cartridge 10000. For example, the latch arms 10088 and 10089 can flex outwardly as the handle 10084 is lifted upwardly such that the latch arms 10088 and 10089 can flex around the lock projections 10008 and the nose 10003, respectively. Thereafter, the proximal end of the cover 10080 can be lifted away from the proximal end 10001 of the staple cartridge and the cover 10080 can be moved away from the staple cartridge 10000.

[0847] Referring now to FIGS. 309 and 310, a staple cartridge applicator, such as staple cartridge applicator 10680, for example, can be configured to position an upper tissue thickness compensator, such as tissue thickness compensator 10690, for example, relative to an anvil in addition to positioning a staple cartridge, such as staple cartridge 10600, for example, within a staple cartridge channel. Similar to the above, the applicator 10680 can comprise latch arms 10688 which can be releasably engaged with lock projections 10608 extending from a support portion 10610 of the staple cartridge 10600 such that the applicator 10680 can be maintained in position over a tissue thickness compensator 10620 of the staple cartridge 10600. The upper tissue thickness compensator 10690 can be removably attached to the staple cartridge applicator 10680 such that the anvil of a surgical instrument, such as anvil 10060, for example, can be closed onto the applicator 10680, engage the tissue thickness compensator 10690, and detach the tissue thickness compensator 10690 from the applicator 10680. The tissue thickness compensator

10690 and/or the anvil 10060 can comprise one or more retention features which can be configured to releasably hold the tissue thickness compensator 10690 to the anvil 10060. For example, the tissue thickness compensator 10690 can comprise a longitudinal rail 10695, for example, extending from the top surface 10691 of the tissue thickness compensator 10690 which can be received within a longitudinal knife slot 10065 defined within the anvil 10060. The tissue thickness compensator 10690 and the longitudinal rail 10695 can be comprised of any suitable compressible material, such as those described in the this patent application, for example, wherein the longitudinal rail 10695 can be compressed and/or wedged within the knife slot 10065, for example. Once the anvil 10060 has been engaged with the tissue thickness compensator 10690, the anvil 10060 can be returned to an open position and, in such circumstances, the tissue thickness compensator 10690 can detach from the applicator 10680. Thereafter, the applicator 10680 can be detached from the staple cartridge 10600 such that the anvil 10060 and the staple cartridge 10600 can be positioned relative to the tissue that is to be stapled and/or incised. In use, a staple-deploying sled, such as sled 10050 (FIG. 236), for example, can be advanced distally through the staple cartridge 10600 by a firing member 10052 (FIG. 236), for example, in order to eject the staples from the staple cartridge 10060, as outlined above. As the staples are deformed, each staple can capture a portion of the tissue thickness compensator 10690 against the top surface of the tissue and a portion of the tissue thickness compensator 10620 against the bottom surface of the tissue. At the same time, the firing member 10052 can advance a knife edge 10053 (FIG. 236) through the tissue thickness compensator 10620 and/or the tissue thickness compensator 10690 wherein, the knife edge 10053 can be advanced through the longitudinal rail 10695 in order to incise the rail 10695 and progressively detach the tissue thickness compensator 10690 from the anvil 10060. After the staples have been deployed, the anvil 10060 can be re-opened and moved away from the implanted tissue thickness compensator 10690 and, similarly, the support portion 10610 of the staple cartridge 10600 can be moved away from the implanted tissue thickness compensator 10620. Further to the above, the tissue thickness compensator 10620 and/or the tissue thickness compensator 10690 can comprise a plurality of detachable segments which can be configured to separate from one another in the event that only portions of the tissue thickness compensators 10620 and 10690 are implanted by the staples.

[0848] Further to the above, the applicator 10680 can comprise one or more retention features which can be configured to releasably hold the tissue thickness compensator 10690 to the applicator 10680. For example, referring primarily to FIG. 310, the applicator 10680 can comprise a longitudinal retention rail 10685 which can be configured to be received in a longitudinal retention slot 10694 defined in the bottom surface 10692 of the tissue thickness compensator 10690 in a press-fit manner, for example. In various circumstances, the retention rail 10685 and the retention slot 10694 can be configured to retain the tissue thickness compensator 10690 to the applicator 10680 until a sufficient upward lifting force is applied to the tissue thickness compensator 10690 by the anvil 10060, as described above. For example, the retention rail 10685 extending from the applicator 10680 can further comprise end stops 10686 positioned at the proximal and distal ends of the retention rail 10685 which can be configured to prevent, or at least limit, relative longitudinal movement between the tissue thickness compensator 10690 and the applicator 10680. Referring again to FIG. 310, one or more adhesives, such as longitudinal adhesive strips 10693, for example, can be placed on the contact surface 10691 of the tissue thickness compensator 10690 such that, when the anvil 10060 contacts the tissue thickness compensator 10690, as described above, the adhesive can releasably attach the tissue thickness compensator 10690 to the anvil 10060. One or more adhesives can be utilized in addition to or in lieu of the compressible retention features described above, for example. One or more adhesives can be utilized to releasably hold a tissue thickness compensator to a staple cartridge applicator. Referring now to FIG. 310A, the cover 10080, for example, can include one or more adhesive pads 12185 which can be configured to releasably retain an upper tissue thickness compensator, such as tissue thickness compensator 12190, for example, to the top surface 10082 of the cover 10080. For example, similar to the embodiments described above, an anvil can be closed onto to the tissue thickness compensator 12190 to engage the longitudinal retention rail 12195 of the tissue thickness compensator 12190. A release mechanism can be positioned intermediate the tissue thickness compensator 12190 and the cover 10080 which can be utilized to break the adhesive bonds holding the tissue thickness compensator 12190 to the cover 10080 and detach the tissue thickness compensator 12190 from the cover 10080. The release mechanism can comprise a pull tab 12196 and a loop 12197 wherein the loop 12197 can comprise first and second ends which are attached to the pull tab 12196. The loop 12197 can comprise a suture, for example, which can define a perimeter which

circumscribes the adhesive pads 12185 such that, when the pull tab 12196 is pulled distally, the suture can slide between the tissue thickness compensator 12190 and the cover 10080 and contact the tissue pads 12185. In such circumstances, the suture can at least one of separate the adhesive pads 12185 from the tissue thickness compensator 12190, separate the adhesive pads 12185 from the cover 10080, and/or sever the adhesive pads 12185, for example.

[0849] Referring now to FIG. 311, a staple cartridge can comprise a support portion 10710, for example, which, similar to the above, can comprise a longitudinal knife slot 10715 extending therethrough. For example, a staple cartridge applicator, such as applicator 10780, for example, can comprise a longitudinal retention and alignment member 10786 which can extend into the knife slot 10715 in the support portion 10710. The retention member 10786 can be configured to engage the sidewalls of the knife slot 10715 in a press-fit manner, for example, such that the applicator 10780 can be releasably retained to the support portion 10710. Although not illustrated, a first portion of a tissue thickness compensator can be positioned on a first side of the retention member 10786 and a second portion of the tissue thickness compensator can be positioned on an opposite, or second, side of the retention member 10786. Similar to the above, the first and second portions of the tissue thickness compensator can be mounted to the support portion 10710 of the staple cartridge via retention members 10013, for example. Also similar to the above, an upper tissue thickness compensator 10790 can be removably mounted to the applicator 10780 via a longitudinal retention member 10785 extending from the loading surface 10782 of the applicator 10780 wherein the retention member 10785 can be releasably press-fit into a longitudinal slot 10794 defined in the bottom surface 10792 of the tissue thickness compensator 10790, for example. Also similar to the above, the tissue thickness compensator 10790 can further comprise a longitudinal retention member 10795 extending from the top surface 10791 of the tissue thickness compensator 10790 which can be releasably retained in the longitudinal knife slot 10065 defined in the anvil 10060, for example. For example, the longitudinal retention member 10795 can comprise a wedge-shaped cross-section comprising a top portion which is larger than a bottom portion, wherein the bottom portion can attach the retention member 10795 to the tissue thickness compensator 10790, for example.

[0850] Referring now to FIGS. 312 and 313, a staple cartridge 10800 comprising a support portion 10810 and a tissue thickness compensator 10820 can be loaded into a staple cartridge channel with a staple cartridge applicator 10880, for example. Similar to the above, the staple

cartridge applicator 10880 can also be configured to position an upper tissue thickness compensator 10890, for example, relative to an anvil, such as anvil 10060, for example, such that, when the anvil 10060 is closed, the anvil 10060 can contact and engage the tissue thickness compensator 10890. The tissue thickness compensator 10890 can comprise a plurality of retention legs 10895 extending from the top surface 10891 of the tissue thickness compensator 10890 which can be configured to be engaging the anvil 10060 and releasably retain the tissue thickness compensator 10890 to the anvil 10060. For example, the legs 10895 can be arranged in a longitudinal row wherein each leg 10895 can comprise at least one foot configured to enter into and engage the knife slot 10065 defined in the anvil 10060. Some of the feet of legs 10895 can extend in one direction while other feet can extend in another direction. Some of the feet can extend in opposite directions. In any event, once the anvil 10060 has been engaged with the tissue thickness compensator 10890, referring now to FIGS. 313 and 314, the anvil 10060 can be reopened and the clinician can move the staple cartridge applicator 10880 away from the tissue thickness compensators 10820 and 10890. Thereafter, referring to FIG. 314A, the upper tissue thickness compensator 10890 can be positioned on a first side of the targeted tissue and the tissue thickness compensator 10820, which can comprise a lower tissue thickness compensator, can be positioned on a second side of the tissue. After the tissue thickness compensators 10820 and 10890 have been suitably positioned, referring now to FIG. 314B, a knife edge of a firing member, such as knife edge 10053, for example, can be advanced through the tissue and the tissue thickness compensators. Referring now to FIG. 318, a staple cartridge applicator, such as applicator 12280, for example, can comprise a tissue thickness compensator 12290 detachably mounted thereto which can be, similar to the above, inserted into a staple cartridge channel, as illustrated in FIG. 319, and engaged by the anvil 10060 when the anvil 10060 is moved into a closed position. For example, the tissue thickness compensator 12290 can comprise a plurality of retention members 12295 extending upwardly from the top surface 12291 of the tissue thickness compensator 12290 wherein each retention member 12295 can comprise a plurality of flexible legs 12296 which can be configured to be inserted into the knife slot 10065 in the anvil 10060. Referring primarily to FIGS. 321 and 322, the flexible legs 12296 of each retention member 12295 can be separated by a gap 12298 such that, as the legs 12296 are inserted into the knife slot 10065, the legs 12296 can flex inwardly and then resiliently return outwardly once the enlarged feet of the flexible legs 12296 have passed through the knife slot 10065. The enlarged

feet of the flexible legs 12296 can flex behind opposing retention lips 12297 defined in the anvil 10060 and, as a result of the interaction of the legs 12296 and the lips 12297, the tissue thickness compensator 12290 can be retained to the anvil 10060. Thereafter, the staple cartridge applicator 12280 can be moved away from the tissue thickness compensator 12290, as illustrated in FIG. 320. In use, once the tissue thickness compensator 12290 has been implanted against the tissue by staples deployed from staple cartridge 10000, for example, the anvil 10060 can be re-opened and, as the anvil 10060 is moved away from the implanted tissue thickness compensator 12290, the legs 12296 of the retention members 12995 can flex inwardly such that they can be pulled out of the knife slot 10065.

[0851] Referring now to FIGS. 315 and 316, a tissue thickness compensator, such as tissue thickness compensator 11990, for example, can be loaded longitudinally into an anvil, such as anvil 11960, for example. More particularly, the tissue thickness compensator 11990 can comprise one or more longitudinal rails 11995 which can be inserted into a distal opening in a knife slot 11965 of the anvil 11960 and then pushed proximally until the tissue thickness compensator 11990 has been properly seated in the anvil 11960. For example, each rail 11995 can comprise a longitudinal retention foot 11996 which can be positioned behind a longitudinal retention lip 11997 which at least partially defines the knife slot 11965, for example. As illustrated in FIG. 316, the feet 11996 can extend in opposite directions in order to be positioned behind retention lips 11997 positioned on the opposite sides of the knife slot 11965. A longitudinal gap 11998 can be defined between the rails 11995 which can be configured to permit the rails 11995 to flex inwardly toward one another when the tissue thickness compensator 11990 is detached from the anvil 11960. Referring now to FIG. 317, a tissue thickness compensator, such as tissue thickness compensator 12090, for example, can comprise one or more lock arms 12098 which can extend around the sides of an anvil, such as anvil 12060, for example. In use, the lock arms 12098 can engage the anvil 12060 and releasably retain the tissue thickness compensator 12090 to the anvil 12060. For example, the anvil 12060 can comprise one or more notches, or lock shoulders, 12097, for example, which can each be configured to receive a foot extending from a lock arm 12098. In use, the arms 12098 can flex outwardly and detach from the anvil 12060 when the anvil 12060 is moved away from the tissue thickness compensator 12090 after the tissue thickness compensator 12090 has been at least partially implanted.

[0852] As described above, a surgical stapling instrument can comprise a staple cartridge channel configured to receive a staple cartridge, an anvil rotatably coupled to the staple cartridge channel, and a firing member comprising a knife edge which is movable relative to the anvil and the staple cartridge channel. In use, a staple cartridge can be positioned within the staple cartridge channel and, after the staple cartridge has been at least partially expended, the staple cartridge can be removed from the staple cartridge channel and replaced with a new staple cartridge. In some such embodiments, the staple cartridge channel, the anvil, and/or the firing member of the surgical stapling instrument may be re-used with the replacement staple cartridge. Alternatively, a staple cartridge may comprise a part of a disposable loading unit assembly which can include a staple cartridge channel, an anvil, and/or a firing member, for example, which can be replaced along with the staple cartridge as part of replacing the disposable loading unit assembly. Certain disposable loading unit assemblies are disclosed in U.S. Patent Application Serial No. 12/031,817, entitled END EFFECTOR COUPLING ARRANGEMENTS FOR A SURGICAL CUTTING AND STAPLING INSTRUMENT, which was filed on February 15, 2008, the entire disclosure of which is incorporated by reference herein. Referring now to FIG. 370, a disposable loading unit, such as disposable loading unit 12500, for example, can comprise a support portion 12510, an anvil 12560 rotatably coupled to the support portion 12510, and an elongate shaft 12570 extending from the support portion 12510. Similar to the staple cartridges described herein, the support portion 12510 can comprise a plurality of staple cavities 10012 and a staple, such as a staple 10030, for example, positioned in each staple cavity 10012, for example. The disposable loading unit 12500 can further comprise a firing member 12552 which can be advanced distally in order to move the anvil 12560 from an open position, as illustrated in FIG. 370, to a closed position. The disposable loading unit 12500 can further comprise a tissue thickness compensator 12520 positioned on and/or attached to the support portion 12510 wherein, when the anvil 12560 is in its closed position, the anvil 12560 can be positioned opposite the tissue thickness compensator 12520 and, the anvil 12560 can at least partially compress the tissue thickness compensator 12520 when the anvil 12560 is in its closed position. In either event, the firing member 12552 can be advanced further in order to eject the staples from the support portion 12510. As the staples are ejected, the staples can be deformed by the anvil 12560 and trap at least a portion of the tissue thickness compensator 12520 therein. Thereafter, the firing member 12552 can be retracted proximally, the anvil 12560 can be re-

opened, and the support portion 12510 can be moved away from the implanted tissue thickness compensator 12520.

[0853] Further to the above, the tissue thickness compensator 12520 can be detachably mounted to the support portion 12510. For example, the support portion 12510 can comprise a longitudinal retention rail 12526 mounted to each side thereof wherein each rail 12526 can comprise one or more apertures 12528 which can be configured to receive at least a portion of the tissue thickness compensator 12520 therein. Once the tissue thickness compensator 12520 has been at least partially implanted, the tissue thickness compensator 12520 can pull out of the apertures 12528 as the support portion 12510 is moved away. Referring now to FIGS. 371-373, a disposable loading unit 12600 can comprise a support portion 12610, a tissue thickness compensator 12620 detachably mounted to the support portion 12610, and one or more retention rails 12626 which can be configured to extend under the tissue thickness compensator 12620 and mount the tissue thickness compensator 12620 to the support portion 12610. Each retention rail 12626 can comprise a plurality of retention hooks 12628, for example, which can be engaged to the support portion 12610 via retention slots 12614, for example, defined in the support portion 12610. In use, for example, the tissue thickness compensator 12620 can be configured to detach from the retention rails 12626 after the tissue thickness compensator 12620 has been at least partially implanted and the support portion 12610 is moved away from the tissue thickness compensator 12620. Referring now to FIGS. 374-376, a disposable loading unit 12700 can comprise one or more retention rails 12726 which can each comprise a bottom bar 12725 which can extend under the tissue thickness compensator 12720 and a top bar 12727 which can extend over the top surface 12621 of the tissue thickness compensator 12620. The tissue thickness compensator 12620 can be at least partially compressed between the top bars 12727 and the bottom bars 12725 such that the retention rails 12726 can releasably hold the tissue thickness compensator 12620 relative to the support portion 12610. For example, each retention rail 12726 can comprise one or more retention hooks 12728 which can be engaged with the support portion 12610 to retain the retention rails 12726 to the support portion 12610.

[0854] Referring now to FIGS. 377 and 378, a disposable loading unit 12800 can comprise a retention member 12822 which can be configured to mount a tissue thickness compensator 12620 to the support portion 12610. For example, the retention member 12822 can comprise a sheet of material positioned against the deck surface 12611 of the support portion wherein the

tissue thickness compensator 12620 can be attached to the sheet of material by at least one adhesive, for example. The retention member 12822 can further comprise a longitudinal retention rail 12825 configured to extend downwardly into a knife slot 12615 defined in the support portion 12610. For example, the retention rail 12825 can be sized and configured such that it is compressed between the sidewalls of the knife slot 12615. In use, the firing member 12552 can comprise a knife edge which can pass through the knife slot 12615 as the firing member 12552 is advanced distally and transect the tissue thickness compensator 12620 and the retention rail 12825 longitudinally. Also, in use, the staples ejected from the support portion 12610 can penetrate the retention member 12822, the tissue thickness compensator 12820, and the tissue positioned between the tissue thickness compensator 12820 and the anvil 12560. The retention member 12822 can be comprised of a biocompatible and/or bioabsorbable material. The retention member 12822 can be comprised of a sufficiently compressible material to comprise a tissue thickness compensator underlying the tissue thickness compensator 12620. Referring now to FIGS. 379-381, a disposable loading unit 12900 can comprise a loading assembly including a bottom portion 12922 which can be removably attached to the support portion 12610, a top portion 12990 which can be removably attached to the anvil 12560, and a flexible joint 12991 connecting the bottom portion 12922 and the top portion 12990. Similar to the above, a longitudinal retention rail 12825 can extend downwardly from the bottom portion 12922 and into the knife slot 12615 defined in the support portion 12610 such that the bottom portion 12922 can be releasably retained to the support portion 12610. Similarly, a longitudinal retention rail 12995 can extend upwardly from the top portion 12990 into a knife slot defined in the anvil 12560 such that the top portion 12990 can be releasably retained to the anvil 12560. As illustrated in FIGS. 380 and 381, a tissue thickness compensator 12620 can be mounted to the bottom portion 12922 of the loading assembly wherein, in order to position the tissue thickness compensator 12620 relative to the support portion 12610, a clinician could flex the top portion 12990 and the bottom portion 12922 toward one another, position the loading assembly between the anvil 12560 and the support portion 12610, and release the flexed loading assembly such that it can resiliently expand and bias the top portion 12990 against the anvil 12560 and the bottom portion 12922 against the support portion 12610. Referring now to FIGS. 382-384, the loading assembly can further comprise one or more latch hooks, such as latch hooks 12994, for example,

extending therefrom which can be configured to releasably connect the top portion 12990 to the anvil 12560 and/or releasably connect the bottom portion 12922 to the support portion 12610.

[0855] Referring now to FIG. 385, a disposable loading unit 15900, for example, can comprise an anvil 15960 and a staple cartridge channel 15970 wherein the staple cartridge channel 15970 can rotate relative to the anvil 15960. For example, the anvil 15960 may not be able to rotate. Tissue can be positioned between the anvil 15960 and the staple cartridge channel 15970 and, thereafter, the staple cartridge channel 15970 can be rotated toward the tissue to clamp the tissue against the anvil. For example, the disposable loading unit 15900 can further comprise a tissue thickness compensator 15920 which can be configured to contact the tissue.

[0856] As discussed above and referring to FIG. 332, a staple cartridge, such as staple cartridge 10000, for example, can comprise a support portion 10010 and a tissue thickness compensator 10020 wherein a plurality of staples 10030 can be at least partially stored in the support portion 10010 and can extend into the tissue thickness compensator 10020 when the staples 10030 are in their unfired position. The tips of the staples 10030 do not protrude from the tissue thickness compensator 10020 when the staples 10030 are in their unfired positions. As the staples 10030 are moved from their unfired positions to their fired positions by the staple drivers 10040, as discussed above, the tips of the staples 10030 can penetrate through the tissue thickness compensator 10020 and/or penetrate through the upper layer, or skin, 10022. In certain alternative embodiments, the tips of the staples 10030 can protrude through the top surface of the tissue thickness compensator 10020 and/or skin 10022 when the staples 10030 are in their unfired position. In either event, the staples 10030, as they extend upwardly out of the support portion 10010 prior to being deployed, may tilt and/or deflect relative to the support portion, as also discussed above. Referring now to FIG. 329, a staple cartridge, such as staple cartridge 13000, for example, can comprise a plurality of guide members, or retainers, which can be configured to limit relative movement between the support portion 13010 of the staple cartridge 13000 and the tips of the staples positioned therein. Referring primarily to FIG. 330, the staple cartridge 13000 can comprise a tissue thickness compensator 13020 mounted to a support portion 13010 and, in addition, a plurality of pledgets 13022 attached to the top surface 13021 of the tissue thickness compensator 13020. Each pledget 13022 can comprise a plurality of apertures 13029 defined therein which can be configured to slidably receive and/or guide the legs 13022 of a staple 13030 therein. In addition to or in lieu of the apertures, a pledget can comprise

any suitable opening such as a slot, guide, and/or groove, for example, which can be configured to slidably receive and/or guide the legs 13022. As illustrated in FIG. 330, the tips of the staple legs 13032 can be positioned within the apertures 13029 when the staples 13030 are in their unfired positions. For example, the tips of the staple legs 13032 can protrude above the pledgets 13022 when the staples are in their unfired position. Alternatively, the tips of the staple legs 13032 may be positioned just below the pledgets 13022 when the staples 13030 are in their unfired positions such that, when the staples 13030 are moved upwardly through the tissue thickness compensator 13020, the staple legs 13032 can enter into the apertures 13029 of the pledgets 13022 and slide therethrough. In any event, when the legs 13032 of the staples 13030 are positioned within the pledgets, the lateral and/or longitudinal movement of the staple legs 13032 can be limited without preventing the upward movement of the staple legs 13032 when the staples 13030 are deployed. When the staples 13030 are deployed, referring now to FIG. 331, the staple legs 13032 can slide upwardly through the pledgets 13022 to penetrate the tissue T, contact an anvil positioned opposite the staple cartridge 13030, and deform downwardly to capture the tissue T and the tissue thickness compensator 13030 therein.

[0857] Further to the above, the pledgets 13022 can be attached to the tissue thickness compensator 13020 utilizing at least one biocompatible and/or bioabsorbable adhesive, for example. The pledgets 13022, and/or a retention member extending from each pledget, can be at least partially embedded within the tissue thickness compensator 13020. For example, the tissue thickness compensator 13020 can comprise pockets defined therein which are configured to at least partially receive a pledget 13022. The tissue thickness compensator 13020 can be integrally molded, or formed around, the pledgets 13022 during a molding manufacturing process. The pledgets 13022 may comprise discrete retainers that can move independently of one another. Referring primarily to FIG. 330, each pledget 13022 can comprise interlocking and/or keyed features which can be configured to permit and, to a certain extent, limit relative lateral and longitudinal movement between the pledgets 13022. For example, each pledget 13022 can comprise a projection 13026 and one or more recesses 13027, for example, wherein the projection 13026 of a first pledget 13022 can be positioned within and/or aligned with respect to the recesses of 13027 of adjacent second and third pledgets 13022. Gaps can be present between adjacent pledgets 13022 which can permit the pledgets 13022 to move or slide relative to one another until they contact an adjacent pledget 13022. The pledgets 13022 can be loosely

interconnected. The pledgets 13022 can be detachably connected to one another. For example, the pledgets 13022 can be manufactured as a sheet of interconnected pledgets wherein, when a sufficient force is applied to the sheet, one or more of the pledgets 13022 can break away from the others. Referring again to FIG. 329, a first sheet 13024 of pledgets 13022 can be positioned on a first side of a longitudinal slot 13025 and a second sheet 13024 of pledgets 13022 can be positioned on a second side of slot 13025. Further to the above, the longitudinal slot 13025 extending through the tissue thickness compensator 13020 can be configured to facilitate the passage of a knife edge of a firing member through the tissue thickness compensator 13020 and, as the firing member passes thereby, the firing member can apply a compressive force to the sheets 13024 and separate or singulate at least some of the pledgets 13022.

[0858] The pledgets 13022 can be comprised of a biocompatible and/or bioabsorbable plastic, for example. The pledgets 13022 can be comprised of a solid material, a semi-solid material, and/or a flexible material, for example. The pledgets 13022 can be embedded within a tissue thickness compensator such that the pledgets 13022 move with the tissue thickness compensator. For example, the pledgets 13022 can be sufficiently flexible such that they can flex with the top surface of the tissue thickness compensator. The pledgets 13022 can be configured to remain embedded in the tissue thickness compensator while, alternatively, the pledgets 13022 can be configured to pop out of, or detach from, the tissue thickness compensator. The pledges 13022 can comprise a top surface which is flush with the top surface of the tissue thickness compensator. The top surfaces of the pledgets 13022 can be positioned above and/or below the top surface of the tissue thickness compensator. The top surfaces of the pledgets 13022 can be disposed such that they are visible when viewing the top surface of the tissue thickness compensator while, as an alternative, the top surfaces of the pledgets 13022 can be positioned below a layer of the tissue thickness compensator, for example. Guide features can be molded into the top surface of a tissue thickness compensator, for example. For example, the tissue thickness compensator may not comprise a composite material and may comprise a unitary piece of material, for example.

[0859] Referring now to FIG. 338, a staple cartridge can comprise a tissue thickness compensator 13620 and a skin, or top layer, 13621, for example. For example, one or more pledgets, or retainers, 13622, for example, can be embedded in the skin 13621. Each retainer 13622 can comprise one or more apertures 13629 defined therein which can be configured to

receive the staple legs 13032 of staples 13030 therein when the staples 13030 are in their unfired position, as illustrated in FIG. 338. In use, further to the above, the staple legs 10032 can slide through the apertures 13629 when the staples 13030 are moved from their unfired position to their fired position until the bases 13031 of the staples 13030 contact the tissue thickness compensator 13620 and compress at least a portion of the tissue thickness compensator 13620 against the bottom surfaces of the pledgets 13622, for example. Referring now to FIG. 333, a staple cartridge can comprise a tissue thickness compensator 13120 and a skin, or top layer, 13122, for example. For example, the tissue thickness compensator 13120 can comprise conical bumps, projections, and/or protrusions 13128, for example, which can extend upwardly from the top surface 13121 of the tissue thickness compensator 13120. The projections 13128 can be configured to receive and envelop the tips of the staple legs 13032 of the staples 13030 when the staples 13030 are in their unfired position, as illustrated in FIG. 333. The top layer 13122 can also comprise conical bumps, projections, and/or protrusions 13129 which can be aligned, or at least substantially aligned, with the projections 13128. In use, the staple legs 10032 can penetrate the projections 13128 and 13129 and emerge from the tissue thickness compensator 13120. Referring now to FIG. 337, a staple cartridge can comprise a tissue thickness compensator 13520 and a skin, or top layer, 13522, for example. For example, the skin 13522 can comprise conical bumps, projections, and/or protrusions 13529, for example, which can extend upwardly from the top surface 13521 of the tissue thickness compensator 13520. Similar to the above, the projections 13529 can be configured to receive and envelop the tips of the staple legs 13032 of the staples 13030 when the staples 13030 are in their unfired position, as illustrated in FIG. 337. In use, the staple legs 10032 can penetrate the projections 13529 and emerge from the skin 13522.

[0860] Referring now to FIG. 334, a staple cartridge can comprise a tissue thickness compensator 13220 and a skin, or top layer, 13222, for example. For example, the tissue thickness compensator 13220 can comprise conical dimples and/or recesses 13128, for example, which can extend downwardly into the top surface 13221 of the tissue thickness compensator 13220. The tips of the staple legs 13032 can extend through the recesses 13128 when the staples 13030 are in their unfired position, as illustrated in FIG. 334. The top layer 13222 can also comprise conical dimples and/or recesses 13229 which can be aligned, or at least substantially aligned, with the recesses 13228. Referring now to FIG. 335, a staple cartridge can comprise a

tissue thickness compensator 13320 and a skin, or top layer, 13322, for example. For example, the skin 13320 can comprise thick portions 13329 which can extend downwardly into the top surface 13321 of the tissue thickness compensator 13320. In various circumstances, the thick portions 13329 can be configured to receive at least a portion of the staple legs 13032 of the staples 13030 therein when the staples 13030 are in their unfired position, as illustrated in FIG. 335. In such cases, the thick portions 13329 can hold the staple legs 13032 in position such that the legs 13032 are aligned, or at least substantially aligned, with the staple-forming pockets of an anvil positioned opposite the tissue thickness compensator 13320. Referring now to FIG. 336, a staple cartridge can comprise a tissue thickness compensator 13420 and a skin, or top layer, 13422, for example. For example, the skin 13422 can comprise thick portions 13429 which can extend upwardly from the top surface 13421 of the tissue thickness compensator 13420. In various circumstances, the thick portions 13429 can be configured to receive at least a portion of the staple legs 13032 of the staples 13030 therein when the staples 13030 are in their unfired position, as illustrated in FIG. 336. In such cases, the thick portions 13429 can hold the staple legs 13032 in position such that the legs 13032 are aligned, or at least substantially aligned, with the staple-forming pockets of an anvil positioned opposite the tissue thickness compensator 13420.

[0861] Referring now to FIGS. 339 and 340, a staple cartridge can comprise a tissue thickness compensator 13720 and a skin, or top layer, 13721, for example. For example, the tissue thickness compensator 13720 can comprise pyramidal and/or stepped bumps, projections, and/or protrusions 13728, for example, which can extend upwardly from the top surface 13721 of the tissue thickness compensator 13720. The projections 13728 can be configured to receive and envelop the tips of the staple legs 13032 of the staples 13030 when the staples 13030 are in their unfired position, as illustrated in FIG. 340. Similarly, the top layer 13721 can comprise pyramidal and/or stepped bumps, projections, and/or protrusions 13729 which can be aligned, or at least substantially aligned, with the projections 13728. The skin 13721 can further comprise one or more teeth 13727 extending upwardly from the projections 13729 which can be configured to engage tissue positioned against the top layer 13721 and prevent, or at least limit, relative lateral and/or longitudinal movement between the tissue, the top layer 13721, and/or the tips of the staple legs 13032. In use, the staple legs 13032 can penetrate the projections 13728 and 13729 and emerge from the tissue thickness compensator 13720 when the staples 13030 are

moved from their unfired positions to their fired positions. Referring now to FIGS. 341 and 342, a staple cartridge can comprise a tissue thickness compensator 13820 and a skin, or top layer, 13821, for example. For example, the tissue thickness compensator 13820 can comprise pyramidal and/or stepped bumps, projections, and/or protrusions 13828, for example, which can extend upwardly from the top surface 13821 of the tissue thickness compensator 13820. The projections 13828 can be configured to receive and envelop the tips of the staple legs 13032 of the staples 13030 when the staples 13030 are in their unfired position, as illustrated in FIG. 342. Similarly, the top layer 13821 can comprise pyramidal and/or stepped bumps, projections, and/or protrusions 13829 which can be aligned, or at least substantially aligned, with the projections 13828. The top layer 13821 can further comprise one or more teeth 13827 extending downwardly into the tissue thickness compensator 13820 which can be configured to prevent, or at least limit, relative lateral and/or longitudinal movement between the top layer 13821 and the tissue thickness compensator 13820, for example. In use, the staple legs 10032 can penetrate the projections 13828 and 13829 and emerge from the tissue thickness compensator 13820 when the staples 13030 are moved from their unfired positions and their fired positions.

[0862] Referring now to FIG. 343, a staple cartridge can comprise a tissue thickness compensator, such as tissue thickness compensator 13920, for example, which can include ridges 13923 and valleys 13924 defined therein wherein, the valleys 13924 can be defined between the ridges 13923. Each ridge 13923 can comprise the same height, substantially the same height, or different heights. Similarly, each valley 13924 can comprise the same depth, substantially the same depth, or different depths. A plurality of staples 13030 can be at least partially stored within the tissue thickness compensator 13920 such that the tips of the staples 13030 can be positioned within the ridges 13923. For example, the staple legs 13032 of the staples 13030 may not protrude from the tissue thickness compensator 13920 and/or a skin, or top layer, 13921 attached to the tissue thickness compensator 13920, for example, when the staples 13030 are stored in their unfired position. The ridges 13923 and/or the valleys 13924 can extend laterally across the staple cartridge. For example, the staple cartridge can comprise a longitudinal knife slot wherein the ridges 13923 and the valleys 13924 can extend in a direction which is transverse and/or perpendicular to the knife slot. In various circumstances, the ridges 13923 can be configured to hold the tips of the staple legs 13032 in position until the staples 13030 are moved from their unfired position into their fired position. Referring now to FIG. 344, a tissue thickness

compensator, and/or a skin covering a tissue thickness compensator, can comprise longitudinal ridges and/or valleys. For example, a tissue thickness compensator can comprise a top surface defined by ridges 14023 and valleys 14024, wherein the valleys 14024 can be defined between the ridges 14023, for example. The tissue thickness compensator can comprise a skin 14021 which can include a plurality of apertures 14029 defined therein which can each be configured to receive a staple leg 13032. The apertures 14029 can be defined in the ridges 14023 wherein the tips of the staple legs 13032 may be positioned below the peaks 14028 of the ridges 14029, positioned flush with the peaks 14028, and/or positioned above the peaks 14028. In addition to or in lieu of the above, the apertures 14029 can be defined in the valleys 14024, for example. Each aperture can be surrounded, or at least partially surrounded, by an embossment, for example, which can strengthen the skin and/or tissue thickness compensator surrounding the apertures. In any event, further to the above, the skin 14021 can be attached to a tissue thickness compensator in any suitable manner, including using at least one adhesive, for example.

[0863] As described above and referring again to FIG. 233, a surgical stapling instrument can comprise an anvil, such as anvil 10060, for example, which can be moved between an open position and a closed position in order to compress tissue T against the tissue thickness compensator 10020 of a staple cartridge 10000, for example. In various circumstances, the anvil 10060 can be rotated toward the staple cartridge 10000 until its downward movement is stopped by some portion of the staple cartridge 10000 and/or some portion of the channel in which the staple cartridge 10000 is positioned. In at least one such circumstance, the anvil 10060 can be rotated downwardly until its downward movement is resisted by the nose 10003 of the staple cartridge 10000 and/or the tissue T positioned intermediate the nose 10003 and the staple cartridge 10000. In some circumstances, the anvil 10060 may sufficiently compress the tissue thickness compensator 10020 to permit the tissue T to contact the tips of the staples 10030. In certain circumstances, depending on the thickness of the tissue T, the anvil 10060 may sufficiently compress the tissue thickness compensator 10020 such that the anvil 10060 comes into contact with the staples 10030 by the time the anvil 10060 has reached its fully closed position. Stated another way, in such circumstances, the anvil 10060 may deform the staples 10030 prior to the firing member 10052 being advanced into the staple cartridge 10000 to fire the staples 10030. Such circumstances may be acceptable in certain embodiments; however, referring now to FIGS. 358 and 359, other embodiments are envisioned in which a distal gap-

setting element, such as element 10059, for example, can be utilized to limit the distance in which the anvil 10060 can be closed prior to the firing bar 10052 being advanced into the staple cartridge 10000. The element 10059 can extend upwardly from the top surface 10021 of the tissue thickness compensator 10020 such that the downward movement of the anvil 10060 can be arrested as the tissue T is compressed against the element 10059 and a resistive force is generated therebetween. In use, as described above, the firing member 10052 can be advanced distally into the staple cartridge 10000 toward the distal end 10002 of the staple cartridge 10000 in order to eject the staples 10030 from the support portion 10010. Simultaneously, the firing member 10052 can engage the anvil 10060 and position the anvil 10060 a desired distance from the deck surface 10011 (FIG. 218) of the support portion 10010 over the staples 10030 being formed. In this way, the firing member 10052 can control the distance, or gap, between the tissue-contacting surface of the anvil 10060 and the deck surface 10011 at a particular location, wherein this particular location can be advanced distally as the firing member 10052 is advanced distally. In various circumstances, this gap distance may be shorter than the gap between the anvil 10060 and the deck surface 10011 being controlled or dictated by the distal gap-setting element 10059 at the distal end of the tissue thickness compensator 10020. Referring now to FIG. 359, the knife edge 10053 of the firing member 10052 can be configured to transect the distal gap-setting element 10059 when the firing member 10052 reaches the distal end of the tissue thickness compensator 10020 such that, after the element 10059 has been transected, the firing member 10052 can pull the anvil 10060 downwardly toward the support portion 10010 and close the gap to the desired gap height when firing the staples 10030 at the distal end of the staple cartridge 10000. In certain alternative embodiments, a distal gap-setting element can be configured to collapse as the firing member approaches the distal end of the staple cartridge. For example, the distal gap-setting element can comprise a column which can provide resistance to the anvil as described above and then suddenly buckle once the buckling strength of the gap-setting element has been reached when the firing member approaches the distal end of the staple cartridge. This buckling force can be approximately 10 lbf, for example. A gap setting element can be configured to drop downwardly into the deck of the support portion when a force exceeding a predetermined amount is applied to the gap setting element, for example. Alternatively, the distal gap can be controlled by the nose of the staple cartridge. For example, the downward movement of the anvil 10060 can be limited by the nose until the firing member

has reached the distal end of the cartridge wherein, at such point, the compressive force applied to the nose can cause the nose to collapse. The nose can comprise a cavity defined by cavity walls which can allow the cavity to collapse once the compressive force applied thereto has exceed a predetermined force. For example, the cavity can be defined by collapsible walls.

[0864] As described above, an anvil, such as anvil 10060, for example, can be moved between an open position and a closed position in order to compress a tissue thickness compensator between the anvil and the support portion of a staple cartridge. In certain circumstances, referring now to FIGS. 360 and 361, the tissue thickness compensator of a staple cartridge, such as tissue thickness compensator 14120 of staple cartridge 14100, for example, may expand laterally and/or longitudinally when the tissue thickness compensator 14120 is compressed against a support portion 14110 of the staple cartridge 14100. The ends and/or sides of the tissue thickness compensator 14120 may not be constrained by the support portion 14110 and/or the anvil 10060 and, as a result, the tissue thickness compensator 14120 can expand in those directions without generating a compressive pressure, or at least an undesirable compressive pressure, within the tissue thickness compensator 14120. In such cases, a firing member, such as firing member 10052 (FIG. 236), for example, passing through the tissue thickness compensator 14120 may not be unduly impeded by an undesirable compressive pressure within the tissue thickness compensator 14120, for example. Alternatively, referring again to FIG. 360, the distal end 14125 of the tissue thickness compensator 14120 may be constrained by the nose 14103 of the staple cartridge 14100, for example. In this particular embodiment, similar to the above, the distal end 14125 of the tissue thickness compensator 14120 may be constrained by the nose 14103 in order to reduce the possibility of the tissue thickness compensator 14120 from becoming prematurely detached from the support portion 14110. In any event, as a result of the above, a large internal pressure can be generated within the distal end 14125 which can impede the advancement of the firing member 10052, especially when the firing member 10052 reaches the distal end 14125. More particularly, in certain circumstances, the firing member 10052 can push, plow, and/or displace the tissue thickness compensator 14120 distally as it transects the tissue thickness compensator 14120 and, as a result, an even larger internal pressure can be created within the distal end 14125 of the tissue thickness compensator 14120. In order to at least partially dissipate this pressure within the tissue thickness compensator 14120, the nose 14103 can be comprised of a flexible material which can allow the nose 14103 to flex distally, for example, and create

additional space for the tissue thickness compensator 14120. Referring now to FIGS. 362 and 363, the nose of a staple cartridge can comprise a portion which can slide distally. More particularly, the nose 14203 of the staple cartridge 14200 can comprise a slidable portion 14204 which can be slidably connected to the nose 14203 such that, when the anvil 10060 is closed and/or the firing member 10052 is advanced into the distal end of the staple cartridge 14200, the slidable portion 14204 can slide distally and create additional room for the tissue thickness compensator 14200 and at least partially alleviate the internal pressure therein. One of the nose 14203 and the slidable portion 14204 can comprise one or more rails and the other of the nose 14203 and the slidable portion 14204 can comprise one or more channels configured to slidably receive the rails therein. For example, the channels and rails can be configured to co-operatively limit the movement of the slidable portion 14204 to a longitudinal distal path, for example.

[0865] In various circumstances, further to the above, certain staples, such as the distal-most staples within a staple cartridge, for example, can capture a larger portion of a tissue thickness compensator than the proximal staples within the staple cartridge. In such circumstances, as a result, a large clamping pressure can be applied to the tissue captured within the distal staples as compared to the proximal staples. These circumstances can arise when at least a portion of the tissue thickness compensator is shifted to and/or gathered at the distal end of the staple cartridge during use, as described above, even though the tissue thickness compensator may be comprised of a substantially homogenous material having a substantially constant thickness. In various circumstances, it may be desirable for certain staples to apply a higher clamping pressure to the tissue than other staples wherein, A support portion and/or a tissue thickness compensator can be constructed and arranged to control which staples may apply the higher clamping pressure to the tissue and which staples may apply a lower clamping pressure to the tissue. Referring now to FIG. 364, a staple cartridge 14300 can comprise a support portion 14310 and, in addition, a tissue thickness compensator 14320 positioned on the deck surface 14311 of the support portion 14310. As compared to other embodiments disclosed in this application which comprise a support portion 14310 having a flat, or at least substantially flat, deck surface, the deck surface 14311 can be inclined and/or declined between the distal end 14305 and the proximal end 14306 of the support portion 14310. The deck surface 14311 of the support portion 14310 can comprise a deck height at its distal end 14305 which is shorter than the deck height at its proximal end 14306. For example, the staples 10030 at the distal end of the staple cartridge 14300 can extend

above the deck surface 14311 a larger distance than the staples 10030 at the proximal end. In various alterative embodiments, the deck surface of a support portion can comprise a height at its distal end which is taller than its height at its proximal end. Referring again to FIG. 364, the tissue thickness compensator 14320 may comprise a thickness which is different along the longitudinal length thereof. The tissue thickness compensator 14320 can comprise a thickness at its distal end 14325 which is thicker than its proximal end 14326, for example. For example, the tissue thickness compensator 14322 can comprise a bottom surface 14322 which can be inclined or declined to match, or at least substantially match, the inclined or declined deck surface 14311 of the support portion 14310. As a result, the top, or tissue-contacting, surface 14321 of the tissue thickness compensator 14320 can comprise a flat, or at least substantially flat, surface upon which the tissue T can be positioned. In any event, as the tissue thickness compensator 14320 is thicker at its distal end 14325, the distal staples 10030 can capture a larger portion of the tissue thickness compensator 14320 therein than the proximal staples 10030 and, as a result, the distal staples 10030 can apply a larger compressive force to the tissue T, especially when the gap distance between the anvil 10060 and the deck surface 14311 is constant, or at least substantially constant, at the proximal and distal ends of the staple cartridge. In certain circumstances, however, the anvil 10060 may not reach a fully closed position and, as a result, the gap distance between the anvil 10060 and the deck surface 14311 may be larger at the distal end of the staple cartridge 14300 than the proximal end. In various circumstances, the distal staples 10030 may not be fully formed and, as a result, the distal staples 10030 may not apply the desired clamping pressure to the tissue T. In the embodiments where the tissue thickness compensator is thicker at the distal end of the staple cartridge, the tissue thickness compensator may compensate for the under forming of the staples and apply a sufficient pressure to the tissue T.

[0866] Referring now to FIG. 365, a staple cartridge, such as staple cartridge 14400, for example, can comprise a support portion 14410 and, in addition, a tissue thickness compensator 14420 positioned on the deck surface 14411 of the support portion 14410. Similar to the above, the deck surface 14411 can be inclined and/or declined such that, the distal end 14405 of the support portion 14410 can have a deck height which is shorter than the deck height at the proximal end 14406, for example. The tissue thickness compensator 14420 can comprise a constant, or at least substantially constant, thickness along the length thereof and, as a result, the

top, or tissue-contacting, surface 14421 of the tissue thickness compensator 14420 may parallel, or at least substantially parallel, the contour of the deck surface 14411. The staples 10030 of the staple cartridge 14400 can be completely embedded within the tissue thickness compensator 14420 and the support portion 14410 when the staples 10030 are in their unfired position. The staples 10030 positioned at the proximal end of the staple cartridge 14400 may be completely embedded within the tissue thickness compensator 14420 and the support portion 14410 when the staples 10030 are in their unfired position whereas, due to the declined slope of the deck 14411 and top surface 14421, the tips of certain staples 10030, including the staples 10030 positioned at the distal end of the staple cartridge 14400, can protrude through the top surface 14421 of the tissue thickness compensator 14420 when the staples 10030 are in their unfired position.

[0867] as described above, a tissue thickness compensator can be comprised of a single material wherein the entirety of the tissue thickness compensator can have the same, or at least substantially the same, material properties, such as density, stiffness, spring rate, durometer, and/or elasticity, for example, throughout. Alternatively, referring now to FIG. 368, a tissue thickness compensator, such as tissue thickness compensator 14520, for example, can comprise a plurality of materials or layers of materials. The tissue thickness compensator 14520 can comprise a first, or central, layer 14520a, second, or intermediate, layers 14520b attached to the first layer 14520a on opposite sides thereof, and a third, or outer layer 14520c attached to each of the second layers 14520b. The intermediate layers 14520b can be attached to the central layer 14520a utilizing at least one adhesive and, similarly, the outer layers 14520c can be attached the second layers 14520 utilizing at least one adhesive. In addition to or in lieu of an adhesive, the layers 14520a-14520c can be held together by one or more interlocking features and/or fasteners, for example. In any event, the inner layer 14520a can be comprised of a first material having a first set of material properties, the intermediate layers 14520b can be comprised of a second material having a second set of material properties, and the outer layers 14520c can be comprised of a third material having a third set of material properties, for example. These sets of material properties can include density, stiffness, spring rate, durometer, and/or elasticity, for example. The staple cartridge can comprise six rows of staples 10030, for example, wherein a row of staples 10030 can be at least partially positioned in each of the outer layers 14520c and each of the inner layers 14520b, for example, and wherein two rows of staples 10030 can be at least

partially positioned with the inner layer 14520a. In use, similar to the above, the staples 10030 can be ejected from the staple cartridge such that the staple legs 10032 of the staples 10030 penetrate the top surface 14521 of the tissue thickness compensator 14520, penetrate tissue positioned against the top surface 14521 by an anvil, and then contact the anvil such that the legs 10032 are deformed to capture the tissue thickness compensator 14520 and the tissue within the staples 10030. Also similar to the above, the tissue thickness compensator 14520 can be transected by a firing member as the firing member is advanced through the staple cartridge. For example, the firing member can transect the inner layer 14520a, and the tissue, along a path defined by axis 14529, for example.

[0868] Further to the above, the rows of staples 10030 positioned within the inner layer 14520a can comprise the staple rows which are closest to the edges of the transected tissue. Correspondingly, the rows of staples 10030 positioned within the outer layers 14520c can comprise the staple rows which are furthest away from the edges of the transected tissue. The first material comprising the inner layer 14520a may comprise a density which is higher than the density of the second material comprising the intermediate layers 14520b and, similarly, the density of the second material may be higher than the density of the third material comprising the outer layers 14520c, for example. In various circumstances, as a result, larger compressive forces can be created within the staples 10030 positioned within the inner layer 14520a as compared to the compressive forces generated within the staples 10030 positioned within the intermediate layers 14520b and the outer layers 14520c. Similarly, larger compressive forces can be created within the staples 10030 positioned within the intermediate layers 14520b as compared to compressive forces created within the staples 10030 positioned within the outer layers 14520c, for example. Alternatively, the first material comprising the inner layer 14520a may comprise a density which is lower than the density of the second material comprising the intermediate layers 14520b and, similarly, the density of the second material may be lower than the density of the third material comprising the outer layers 14520c, for example. In various circumstances, as a result, larger compressive forces can be created within the staples 10030 positioned within the outer layers 14520c as compared to the compressive forces created within the staples 10030 positioned within the intermediate layers 14520b and the inner layer 14520a. Similarly, larger compressive forces can be created within the staples 10030 positioned within the intermediate layers 14520b as compared to the compressive forces created within the staples 10030 positioned

within the inner layer 14520a, for example. Alternatively, any other suitable arrangement of layers, materials, and/or material properties could be utilized. In any event, the layers 14520a-14520c of the tissue thickness compensator 14520 can be configured to remain attached to one another after they have been implanted. Alternatively, the layers 14520a-14520c of the tissue thickness compensator 14520 can be configured to detach from one another after they have been implanted. For example, the layers 14520a-14520c can be bonded together utilizing one or more bioabsorbable adhesives which can initially hold the layers together and then allow the layers to release from one another over time.

[0869] As described above, a tissue thickness compensator of a staple cartridge, such as tissue thickness compensator 14520, for example, can comprise a plurality of longitudinal layers. Alternatively, referring now to FIG. 369, a staple cartridge can comprise a tissue thickness compensator, such as tissue thickness compensator 14620, for example, which can comprise a plurality of horizontal layers. For example, the tissue thickness compensator 14620 can comprise a first, or bottom, layer 14620a, a second, or intermediate, layer 14620b attached to the bottom layer 14620a, and a third, or top, layer 14620c attached to the intermediate layer 14620b. The first layer 14620a can comprise a flat, or substantially flat, bottom surface 14626a and a triangular, or pyramidal, top surface 14625a, for example. For example, the second layer 14620b can comprise a triangular, or pyramidal, bottom surface 14626b which can be configured to parallel and abut the top surface 14625a of the first layer 14620a. Similar to the above, the second layer 14620b can comprise a triangular, or pyramidal, top surface 14625b which can parallel and abut a bottom triangular, or pyramidal, bottom surface 14626c of the third layer 14620c, for example. The top surface of the third layer 14626c can comprise a flat, or at least substantially flat, tissue-contacting surface 14621. Also similar to the above, the tissue thickness compensator 14620 can be configured to at least partially store six rows of staples, such as staples 10030, for example, therein wherein a firing member can transect the tissue thickness compensator 14620 between the two innermost staple rows along a path extending through axis 14629, for example. Similar to the above, each layer 14620a, 14620b, and 14620c can be comprised of a different material which can comprise different material properties and, as a result of the triangular, or pyramidal, configuration of the layers 14620a-14620c, the tissue thickness compensator 14620 can have different overall properties at various locations therewithin. For example, the outermost rows of staples 10030 may capture more of the third

layer 14620c than the first layer 14620a therein whereas the innermost rows of staples 10030 may capture less of the third layer 14620c than the first layer 14620a and, as a result, the tissue thickness compensator 14620 may compress the tissue captured within the outermost staples 10030 differently than the tissue captured within the innermost staples 10030, for example, even though the tissue thickness compensator 14620 may have the same, or at least substantially the same, overall thickness thereacross.

[0870] Referring now to FIG. 286, a tissue thickness compensator of a staple cartridge, such as tissue thickness compensator 14720 of staple cartridge 14700, for example, can comprise voids, pockets, channels, and/or grooves, for example, defined therein which can vary the thickness of the tissue thickness compensator 14720. For example, the tissue thickness compensator 14720 can be positioned against the deck surface 14711 of a support portion 14710 of the staple cartridge 14700 such that voids 14723 defined in the bottom surface 14722 of the tissue thickness compensator 14720 can overlie certain staple cavities 10012, but not others. The voids 14723 can extend transversely to the knife slot 14715 of the support portion 14710, perpendicular to the knife slot 14715, and/or parallel to the knife slot 14715, for example. The voids 14723 can define a tread pattern in the bottom surface 14722 of the tissue thickness compensator 14720. In any event, when staples, such as staples 10030, for example, are deployed from the support portion 14710, referring now to FIGS. 287 and 288, certain staples 10030 can capture the tissue thickness compensator 14720 within a region containing a void 14723 while other staples 10030 can capture the tissue thickness compensator 14720 within a region positioned intermediate the voids 14723. In addition to or in lieu of the above, the tissue thickness compensator 14720 can comprise voids, pockets, channels, and/or grooves, for example, defined in the top, or tissue-contacting, surface 14721. Referring now to FIGS. 366 and 367, a staple cartridge 14800 can comprise a tissue thickness compensator 14820 which can include a plurality of treads 14823 extending at least one of upwardly from a top surface 14821 of the tissue thickness compensator 14820, inwardly toward a central groove 14825, and/or distally toward the distal end of the staple cartridge 14800, for example. For example, the treads 14823 can be separated by channels, slots, and/or grooves, such as channels 14824, for example. In various circumstances, as a result of the above, the overall thickness of the tissue thickness compensator can vary between staple rows and/or vary between the staples within a staple row. In certain circumstances, the treads, or thick portions, can be constructed and arranged such that

they can flow in a desire direction, such as inwardly, for example, when the tissue thickness compensator is compressed.

[0871] Referring now to FIG. 303, a staple cartridge, such as staple cartridge 14900, for example, can comprise a support portion 14910 and, in addition, a tissue thickness compensator 14920 positioned against the support portion 14910. Similar to the above, the support portion 14910 can comprise staple drivers which can be lifted upwardly by a staple-deploying sled in order to lift staples, such as staples 10030, for example, at least partially positioned within the support portion 14910 toward an anvil, such as anvil 10060, for example, positioned opposite the staple cartridge 14900. The support portion 14910 can comprise six rows of staple cavities, such as two outer rows of staple cavities, two inner rows of staple cavities, and two intermediate rows of staple cavities positioned intermediate the inner rows and the outer rows, for example, wherein the anvil 10060 can comprise six rows of forming pockets 10062 aligned, or at least substantially aligned, with the staple cavities. The inner rows of staple cavities can include staple drivers 14940a positioned therein, the intermediate rows of staple cavities can include staple drivers 14940b positioned therein, and the outer rows of staple cavities can include staple drivers 14940c positioned therein, wherein each of the staple drivers 14940a can include a cradle 14949a configured to support a staple 10030, wherein each of the staple drivers 14940b can include a cradle 14949b configured to support a staple 10030, and wherein each of the staple drivers 14940c can include a cradle 14949c configured to support a staple 10030. In their unfired positions, i.e., when the staple drivers 14940a-14940c are sitting on driver supports 14926 which extend underneath the support portion 14910, the cradles 14949a of the staple drivers 14940a can be positioned closer to the anvil 10060 than the cradles 14949b of the staple drivers 14940b and the cradles 14949c of the staple drivers 14940c. In such a position, a first forming distance can be defined between the cradles 14949a and the forming pockets 10062 positioned over the cradles 14949a, a second forming distance can be defined between the cradles 14949b and the forming pockets 10062 positioned over the cradles 14949b, and a third forming distance can be defined between the cradles 14949c and the forming pockets 10062 positioned over the cradles 14949c, wherein the first forming distance can be shorter than the second forming distance and the second forming distance can be shorter than the third forming distance, for example. When the staple drivers 14940a-14940c are moved from their unfired positions (FIG. 303) to their fired positions, each staple driver 14940a-14940c can be moved upwardly an equal, or an at least

substantially equal, distance toward the anvil 10060 by the staple-deploying sled such that the first drivers 14940a drive their respective staples 10030 to a first formed height, the second drivers 14940b drive their respective staples 10030 to a second formed height, and the third drivers 14940c drive their respective staples 10030 to a third formed height, wherein the first formed height can be shorter than the second formed height and the second formed height can be shorter than the third formed height, for example. Various other embodiments are envisioned in which the first staple drivers 14940a are displaced upwardly a first distance, the second staple drivers 14940b are displaced upwardly a second distance, and the third staple drivers 14940c are displaced upwardly a third distance, wherein one or more of the first distance, the second distance, and the third distance can be different.

[0872] Referring again to FIG. 303, the deck surface 14911 of the support portion 14910 can vary in height with respect to the tissue-contacting surface 10061 of the anvil 10060. This height variation can occur laterally and, the height of the deck surface 14911 surrounding the inner rows of staple cavities can be higher than the deck surface 14911 surrounding the outer rows of staple cavities, for example. The bottom surface 14922 of the tissue thickness compensator 14920 can be configured to parallel, or at least substantially parallel, the deck surface 14911 of the support portion 14910. Further to the above, the tissue thickness compensator 14920 can also vary in thickness wherein, the top, or tissue-contacting, surface 14921 of the tissue thickness compensator 14920 can slope inwardly from the outside or lateral edges thereof. For example, as a result of the above, the tissue thickness compensator 14920 can be thinner in a region positioned over the inner rows of staple cavities and thicker in a region positioned over the outer rows of staple cavities, for example. Referring now to FIG. 304, the deck surface of a support portion 15010 can comprise a stepped deck surface, for example, wherein the highest steps of the stepped surface can surround the inner rows of staple cavities and the lowest steps of the stepped surface can surround the outer rows of staple cavities, for example. For example, steps having an intermediate height can surround the intermediate rows of staple cavities. A tissue thickness compensator, such as tissue thickness compensator 15020, for example, can comprise a bottom surface which can parallel and abut the deck surface of the support portion 15010. The top, or tissue-contacting, surface 15021 of the tissue thickness compensator can comprise an arcuate, parabolic, and/or curved surface, for example, which, for example, can extend from a first lateral side of the tissue thickness compensator 15020 to a second lateral side of the tissue thickness

compensator 15020 with an apex aligned, or at least substantially aligned, with the center of the staple cartridge 15000, for example. Referring now to FIG. 299, a staple cartridge 15300, for example, can comprise a support portion 15310, a plurality of staple drivers 15340 movably positioned within staple cavities defined in the support portion 15310, and a tissue thickness compensator 15320 positioned above the deck surface 15311 of the support portion 15310. The staple cartridge 15300 can further comprise one or more bottom pan portions 15326 which can be attached to the support portion 15310 and extend around the bottom of the support portion 15310 and support the drivers 15340, and staples 15330, in their unfired positions. As a staple-deploying sled is advanced through the staple cartridge, the sled can also be supported by the bottom pan portions 15326 as the sled lifts the staple drivers 15340 and the staples 15330 upwardly through the tissue thickness compensator 15320. The tissue thickness compensator 15320 can comprise a first, or inner, portion 15322a positioned over an inner row of staple cavities, a second, or intermediate portion 15322b positioned over an intermediate row of staple cavities, and a third, or outer, portion 15322c positioned over a row of staple cavities, wherein the inner portion 15322a can be thicker than the intermediate portion 15322b and the intermediate portion 15322b can be thicker than the outer portion 15322c, for example. The tissue thickness compensator 15320 can comprise longitudinal channels, for example, defined therein which can create the thinner portions 15322b and 15322c of the tissue thickness compensator 15320. Alternatively, the longitudinal channels can be defined in the top surface and/or the bottom surface of a tissue thickness compensator. The top surface 15321 of the tissue thickness compensator 15320 can comprise a flat, or at least substantially flat, surface, for example.

[0873] Referring now to FIG. 296, a staple cartridge can comprise a tissue thickness compensator, such as tissue thickness compensator 15120, for example, which can comprise a plurality of portions having different thicknesses. The tissue thickness compensator 15120 can comprise a first, or inner, portion 15122a which can have a first thickness, second, or intermediate, portions 15122b extending from the first portion 15122b which can each have a second thickness, and third, or outer, portions 15122c extending from the second portions 15122b which can each have a third thickness. For example, the third thickness can be thicker than the second thickness and the second thickness can be thicker than the first thickness, for example, although any suitable thicknesses could be utilized in various other embodiments. The

portions 15122a-15122c of the tissue thickness compensator 15120 can comprise steps having different thickness. Similar to the above, a staple cartridge can comprise several rows of staples 10030 and a plurality of staple drivers having different heights which can deform the staples 10030 to different formed heights. Also similar to the above, the staple cartridge can comprise first staple drivers 15140a which can drive the staples 10030 supported thereon to a first formed height, second staple drivers 15140b which can drive the staples 10030 supported thereon to a second formed height, and third staple drivers which can drive the staples 10030 supported thereon to a third formed height, wherein the first formed height can be shorter than the second formed height and the second formed height can be shorter than the third formed height, for example. As illustrated in FIG. 296, each staple 10030 can comprise the same, or substantially the same, unformed, or unfired, height. Alternatively, referring now to FIG. 296A, the first drivers 15140a, the second drivers 15140b, and/or the third drivers 15140c can support staples having different unformed heights. For example, the first staple drivers 15140a can support staples 15130a having a first unformed height, the second staple drivers 15140b can support staples 15130b having a second unformed height, and the third staple drivers 15140c can support staples 15130c having a third unformed height, wherein the first unformed height can be shorter than the second unformed height and the second unformed height can be shorter than the third unformed height, for example. Referring again to FIG. 296A, the tips of the staples 15130a, 15130b, and/or 15130c can lie, or at least substantially lie, in the same plane while, as an alternative, the tips of the staples 15130a, 15130b, and/or 15130c may not lie in same plane. Referring now to FIG. 297, a staple cartridge can include a tissue thickness compensator 15220 having a plurality of portions having different thickness which can be implanted against the tissue T by the staples 15130a, 15130b, and 15130c, as described above. Referring now to FIG. 298, the staples 15130a, 15130b, and/or 15130c can be deformed to different formed heights wherein the first staples 15130a can be formed to a first formed height, the second staples 15130b can be formed to a second formed height, and the third staples 15130c can be formed to a third formed height, and wherein the first formed height can be shorter than the second formed height and the second formed height can be shorter than the third formed height, for example. Other embodiments are envisioned in which the staples 15130a, 15130b, and 15130c can be formed to any suitable formed heights and/or any relative formed heights.

[0874] As described above, the anvil of a surgical stapling instrument can be moved between an open position and a closed position. In such circumstances, the tissue-contacting surface of the anvil can be moved into its final, or forming, position as the anvil is moved into its closed position. Once the anvil is in its closed position, the tissue-contacting surface may no longer be adjustable. Alternatively, referring now to FIG. 351, a surgical stapler, such as surgical stapler 15500, for example, can comprise an anvil channel 15560 and an adjustable tissue-contacting anvil adjustment plate 15561 positioned within the anvil channel 15560. In such cases, the anvil plate 15561 can be raised and/or lowered within the anvil channel 15560 in order to adjust the position of the tissue-contacting surface of the anvil plate 15561 relative to a staple cartridge positioned opposite the anvil plate 15561. The surgical stapler 15500 can comprise an adjustment slide 15564 which, referring to FIGS. 356 and 357, can be slid intermediate the anvil channel 15560 and the anvil plate 15561 in order to control the distance between the anvil plate 15561 and the staple cartridge. Referring again to FIGS. 351 and 352, the surgical stapler 15500 can further comprise an actuator 15562 coupled to the adjustment slide 15564 which can be slid proximally in order to slide the adjustment slide 15564 proximally and/or slid distally in order to slide the adjustment slide 15564 distally. Referring again to FIGS. 356 and 357, the actuator 15562 can be slid between two or more pre-defined positions in order to adjust the anvil plate 15561 between two or more positions, respectively. Such pre-defined positions can be demarcated on the surgical stapler 15500 as demarcations 15563 (FIG. 351), for example. Referring to FIG. 357, the adjustment slide 15564 can comprise a plurality of support surfaces, such as first support surface 15565a, second support surface 15565b, and third support surface 15565c, for example, which can be aligned with a plurality of plate positioning surfaces, such as first positioning surface 15569a, second positioning surface 15569b, and third positioning surface 15569c, respectively, on the backside of the anvil plate 15561 in order to position the anvil plate 15561 in a first position. In order to position the anvil plate 15561 in a second position, the actuator 15562 and the slide 15564 can be slid proximally, for example, in order to realign the support surfaces 15565a-15565c of the slide 15564 relative to the positioning surfaces 15569a-15569c of the anvil plate 15561. More particularly, referring to FIG. 356, the slide 15564 can be slid distally such that the first support surface 15565a of the slide 15564 can be positioned behind the second positioning surface 15569b of the anvil plate 15561 and such that the second support surface 15565b of the slide 15564 can be positioned behind the third positioning surface

15569c of the anvil plate 15561 in order to move the anvil plate 15561 closer to the staple cartridge. When the anvil plate 15561 is moved from its first position to its second position, in such circumstances, the adjustable anvil plate 15561 can further compress the tissue T positioned between the anvil plate 15561 and the staple cartridge. In addition to the above, the formed height of the staples can be controlled by the position of the anvil plate 15561 relative to the staple cartridge as the forming pockets defined in the anvil plate 15561 will move closer to and/or further away from the staple cartridge when the anvil plate 15561 is adjusted. Although only two positions are discussed above, the slide 15564 can be slid into a suitable number of positions to move the anvil plate 15561 closer to and/or away from the staple cartridge. In any event, once the anvil plate 15561 has been suitably positioned, a staple-deploying sled 15550 can be slid distally within the staple cartridge in order to lift staple drivers 15540 and staples 15530 toward the anvil plate 15561 and staple the tissue T, as illustrated in FIG. 354. Similar surgical staplers are disclosed in U.S Patent Application Serial No. 13/036,647, entitled SURGICAL STAPLING INSTRUMENT, which was filed on February 28, 2011, the entire disclosure of which is incorporated by reference herein.

[0875] Referring now to FIG. 353, a staple cartridge can be positioned within a staple cartridge channel 15570 of the surgical stapler 15500 which can comprise a tissue thickness compensator, such as tissue thickness compensator 15520, for example. When the anvil plate 15561 is moved toward the staple cartridge, as described above, the anvil plate 15561 can compress the tissue thickness compensator 15520 and/or the tissue T positioned intermediate the anvil plate 15561 and the tissue thickness compensator 15520. As the staples 15530 are deployed from the staple cartridge, referring to FIG. 355, the staples 15530 can compress and implant the tissue thickness compensator 15520 against the tissue T. When the anvil plate 15561 is positioned against the slide 15564 and tissue has not yet been placed between the anvil plate 15561 and the tissue thickness compensator 15520, a gap can be defined between the anvil plate 15561 and the top surface 15521 of the tissue thickness compensator 15520 when the anvil plate 15561 is in a first position. When the anvil plate 15561 is moved into a second position, the anvil plate 15561 can contact the tissue thickness compensator 15520. Alternatively, when the anvil plate 15561 is positioned against the slide 15564 and tissue has not yet been placed between the anvil plate 15561 and the tissue thickness compensator 15520, a gap can be defined between the anvil plate 15561 and the top surface 15521 of the tissue thickness compensator 15520 when the anvil plate

15561 is in a first position and/or a second position. For example, the anvil plate 15561 may not come into contact with the tissue thickness compensator 15520. In further alternative embodiments, when the anvil plate 15561 is positioned against the slide 15564 and tissue has not yet been placed between the anvil plate 15561 and the tissue thickness compensator 15520, the anvil plate 15561 can be in contact with the top surface 15521 of the tissue thickness compensator 15520 regardless of whether the anvil plate 15561 is in a first position and/or a second position, for example. Although only two positions for the anvil plate 15611 are described herein, the anvil plate 15611 may be positioned, or indexed, into any suitable number of positions.

[0876] As a result of the above, a surgical stapling instrument can comprise means for adjusting the formed height of the staples which can, in various circumstance, compensate for different tissue thicknesses. In addition, the surgical stapling instrument can comprise other means for compensating for different tissue thicknesses and/or thickness variations within the tissue, for example. For example, the anvil plate 15561 can be adjusted upwardly, or away, from the opposing staple cartridge to increase the formed, or fired, height of the staples. Correspondingly, the anvil plate 15561 can be adjusted downwardly, or toward, the opposing staple cartridge to decrease the formed, or fired, height of the staples. The adjustment of the anvil plate 15561, for example, can adjust the gap between the forming pockets defined in the anvil plate 15561 and the fired height of the staple drivers or, more specifically, the fired height of the staple driver cradles, for example. Even with such a capacity to adjust the formed height of the staples to account for thicker and/or thinner tissue, for example, a tissue thickness compensator can also compensate for thicker and/or thinner tissue and/or compensate for thickness variations within the tissue, as described above. In such cases, a surgeon can be afforded with several compensation means within the same surgical stapling instrument.

[0877] As described above and illustrated in several embodiments, a surgical stapling instrument can utilize a staple cartridge having a linear arrangement of staple cavities and staples wherein a firing member can be advanced distally through the staple cartridge to deploy the staples from the staple cavities. A staple cartridge can comprise rows of staple cavities and staples which are curved. Referring now to FIGS. 345 and 346, a surgical stapling instrument, such as stapler 15600, for example, can comprise one or more circular or annular rows of staple cavities defined in a circular or annular support portion 15610. Such circular staple rows can comprise a circular

row of inner staple cavities 15612 and a circular row of outer staple cavities 15613, for example. For example, the circular rows of staple cavities can surround a circular or annular aperture 15615 defined in the stapler 15600 which can house a circular or annular knife movably positioned therein. In use, tissue can be positioned against the deck surface 15611 of the support portion 15610 and an anvil (not illustrated) can be assembled to the surgical stapler 15600 via an actuator extending through and/or positioned within the aperture 15615 such that, when the actuator is actuated, the anvil can be clamped toward the support portion 15610 and compress the tissue against the deck surface 15611. Once the tissue has been sufficiently compressed, the staples positioned within the staple cavities 15612 and 15613 can be ejected from the support portion 15610 and through the tissue such that the staples can contact the anvil and be sufficiently deformed to capture the tissue therein. As the staples are being fired and/or after the staples have been fired, the circular knife can be advanced to transect the tissue. Thereafter, the anvil can be moved away from the support portion 15610 and/or detached from the surgical stapler 15600 such that the anvil and the surgical stapler 15600 can be removed from the surgical site. Such surgical staplers 15600 and such surgical techniques can be utilized to join two portions of a large intestine, for example. In various circumstances, the circular staple lines may be configured to hold the portions of the large intestine together while the tissue heals and, at the same time, permit the portions of the large intestine to resiliently expand. Similar surgical stapling instruments and surgical techniques are disclosed in U.S. Patent No. 5,285,945, entitled SURGICAL ANASTOMOSIS STAPLING INSTRUMENT, which issued on February 15, 1994, the entire disclosure of which is incorporated by reference herein.

[0878] Further to the above, a tissue thickness compensator may be positioned against and/or attached to the support portion 15610 of the surgical stapler 15600, for example. The tissue thickness compensator can be comprised of a circular or annular ring of material comprising an inner radius and an outer radius, for example. In certain circumstances, tissue can be positioned against this ring of material and, when the anvil is used to move the tissue toward the support portion 15610, the tissue thickness compensator can be compressed between the tissue and the deck surface 15611. During use, the staples can be fired through the tissue thickness compensator and the tissue such that the staples can contact the anvil and deform to their fired position to capture portions of the tissue and the tissue thickness compensator within the staples. In various circumstances, further to the above, the ring of material comprising the tissue

thickness compensator must be sufficiently resilient to permit the portions of the large intestine surrounding the staple lines to expand. Referring again to FIGS. 345 and 346, a flexible tissue thickness compensator 15620 can comprise a circular or annular flexible inner ring 15624, for example, which, can define a circular or annular aperture 15625. The inner ring 15624 may be configured such that it is not captured within staples deployed from the surgical stapler 15600; rather, the inner ring 15624 may be positioned radially inwardly with respect to the inner row of staple cavities 15612. For example, the tissue thickness compensator 15620 can comprise a plurality of tags, such as inner tags 15622 and outer tags 15623, for example, extending therefrom such that the tags can be at least partially captured within the staples as they are being deformed. More particularly, referring primarily to FIG. 345, each inner tag 15622 can comprise a head which is positioned over a staple cavity 15612 defined in the surgical stapler 15600 wherein the head can be attached to the inner ring 15624 by a neck 15626, for example, and, similarly, each outer tag 15623 can comprise a head which is positioned over a staple cavity 15613 defined in the surgical stapler 15600 wherein the head can be attached to the inner ring 15624 by a neck 15627, for example. The heads of the inner tags 15622 and the outer tags 15623 can comprise any suitable shape, such as round, oval, and/or elliptical, for example. The necks 15626 and/or 15627 can also comprise any suitable shape wherein, the necks 15627 connecting the heads of the outer tags 15623 to the inner ring 15624 can be configured to extend between adjacent inner staple cavities 15612 in the support portion 15610 such that the necks 15627 are not captured within the staples deployed from the inner staple cavities 15612.

[0879] Referring now to FIGS. 347 and 348, a flexible tissue thickness compensator 15720 can comprise a circular or annular flexible outer ring 15724, for example. The outer ring 15724 may be configured such that it is not captured within staples deployed from the surgical stapler 15600; rather, the outer ring 15724 may be positioned radially outwardly with respect to the outer row of staple cavities 15613. For example, the tissue thickness compensator 15720 can comprise a plurality of tags, such as inner tags 15622 and outer tags 15623, for example, extending therefrom such that the tags can be at least partially captured within the staples as they are being deformed. More particularly, referring primarily to FIG. 347, each inner tag 15622 can comprise a head which is positioned over a staple cavity 15612 defined in the surgical stapler 15600 wherein the head can be attached to the outer ring 15724 by a neck 15726, for example, and, similarly, each outer tag 15623 can comprise a head which is positioned over a staple cavity

15613 defined in the surgical stapler 15600 wherein the head can be attached to the outer ring 15724 by a neck 15727, for example. The heads of the inner tags 15622 and the outer tags 15623 can comprise any suitable shape, such as round, oval, and/or elliptical, for example. The necks 15726 and/or 15727 can also comprise any suitable shape wherein, the necks 15726 connecting the heads of the inner tags 15622 to the outer ring 15724 can be configured to extend between adjacent outer staple cavities 15613 such that the necks 15726 are not captured within the staples deployed from the outer staple cavities 15613. In certain alternative embodiments, a tissue thickness compensator can comprise a circular or annular flexible inner ring, a circular or annular flexible outer ring, and, in addition, a plurality of tags which can be connected to the inner ring and/or the outer ring. Certain tags can be connected to the inner ring and certain other tags can be connected to the outer ring. At least some of the tags can be connected to both the inner ring and the outer ring. In any event, further to the above, the inner ring 15624 of the tissue thickness compensator 15620, the outer ring 15724 of the tissue thickness compensator 15720, and/or any other suitable tissue thickness compensator, can be configured to resiliently expand and/or contract in order to accommodate the expansion and/or contraction of the tissue that it has been implanted against. Furthermore, although various embodiments are described herein as comprising circular or annular support rings, a tissue thickness compensator can comprise any suitably-shaped support structure for connecting the tags thereto. Further to the above, the circular knife advanced by the surgical stapler to cut the tissue captured between the anvil and the support portion can also cut the buttress material. For example, the knife can separate the inner support ring from the tags by cutting the necks thereof, for example.

[0880] Further to the above, a tissue thickness compensator can comprise detachable and/or relatively movable positions which can be configured to allow the tissue thickness compensator to expand and/or contract in order to accommodate the movement of the tissue that it has been implanted against. Referring now to FIGS. 349 and 350, a circular or annular tissue thickness compensator 15820 can be positioned against and/or supported by the deck surface 15611 of the surgical stapler 15600 which can be held in an unexpanded position (FIG. 349) as it is being implanted against the tissue and, after the tissue thickness compensator 15820 has been implanted, the tissue thickness compensator 15820 can be configured to expand outwardly, as illustrated in FIG. 350. The tissue thickness compensator 15820 can comprise a plurality of arcuate portions 15822 which can be connected together by an inner ring 15824, for example.

The arcuate portions 15822 can be separated from one another by seams 15828. In at least one other embodiment, the arcuate portions 15822 may be connected to one another wherein, for example, an arrangement of perforations may permit the arcuate portions 15822 to separate from one another. In either event, the arcuate portions 15822 can each comprise interlocking features, such as projections 15826 and notches 15823, for example, which can co-operate to limit relative movement between the arcuate portions 15822 prior to the tissue thickness compensator 15820 being implanted. Further to the above, each arcuate portion 15822 can be connected to the inner ring 15824 by one or more connectors 15827, for example, which can be configured to releasably hold the arcuate portions 15822 in position. After the staples, such as staples 10030, for example, stored within the support portion 15610 have been utilized to implant the tissue thickness compensator 15620 against the tissue, referring primarily to FIG. 350, the connectors 15827 can detach from the inner ring 15824 and allow the tissue thickness compensator 15820 to at least partially expand to accommodate movement within the underlying tissue. In various circumstances, all of the arcuate portions 15822 may detach from the inner ring 15824 while, in other circumstances, only some of the arcuate portions 15822 may detach from the inner ring 15824. In certain alternative embodiments, the arcuate portions 15822 can be connected by flexible sections which can permit the arcuate portions 15822 to move relative to each other but not detach from one another. For example, the flexible sections may not receive staples therein and can be configured to stretch and/or contract to accommodate the relative movement of the arcuate portions 15822. In FIGS. 349 and 350, the tissue thickness compensator 15820 can comprise eight arcuate portions 15822, for example. Alternatively, a tissue thickness compensator can comprise any suitable number of arcuate portions, such as two or more arcuate portions, for example.

[0881] Further to the above, a tissue thickness compensator 15620, 15720, and/or 15820, for example, can be configured to compensate for thicker and/or thinner tissue captured between the anvil and the support portion 15610 of the surgical instrument 15600. Similar to the above, the formed, or fired, height of the staples can be adjusted by moving the anvil toward and/or away from the support portion 15610. More particularly, the anvil can be moved closer to the support portion 15610 to decrease the formed height of the staples while, correspondingly, the anvil can be moved further away from the support portion 15610 to increase the formed height of the staples. In such cases, as a result, a surgeon can adjust the anvil away from the support portion

15610 to account for thick tissue and toward the support portion 15610 to account for thin tissue. In various other circumstances, the surgeon may decide not to adjust the anvil at all and rely on the tissue thickness compensator to account for the thinner and/or thicker tissue. As a result, the surgical instrument 15600 can comprise at least two means for compensating for different tissue thicknesses and/or variations in the tissue thickness.

[0882] As described above, a tissue thickness compensator can be attached to a support portion of a staple cartridge. The bottom surface of the tissue thickness compensator can comprise one of a layer of hooks or a layer of loops while a deck surface on the support portion can comprise the other one of the layer of hooks and the layer of loops. For example, the hooks and the loops can be configured to engage one another and releasably retain the tissue thickness compensator to the support portion. Each hook can comprise an enlarged head extending from a neck, for example. A plurality of pads comprising the loops, for example, can be bonded to the bottom surface of the tissue thickness compensator while a plurality of pads comprising the hooks can be bonded to the deck surface of the support portion. The support portion can comprise one or more apertures and/or recesses, for example, which can be configured to receive an insert therein comprising hooks and/or loops. In addition to or in lieu of the above, a tissue thickness compensator can be removably mounted to an anvil utilizing such hook and loop arrangements, for example. The hooks and loops can comprise fibrous surfaces, for example.

[0883] As described above, a staple cartridge can comprise a support portion and a tissue thickness compensator attached to the support portion. As also described above, the support portion can comprise a longitudinal slot configured to receive a cutting member therein and the tissue thickness compensator can comprise a retention member that can be retained in the longitudinal slot. Referring now to FIG. 386, a staple cartridge 16000 can comprise a support portion 16010 including a deck surface 16011 and a longitudinal slot 16015. The staple cartridge 16000 can further comprise a tissue thickness compensator 16020 positioned above the deck surface 16011. The tissue thickness compensator 16020 can include a longitudinal retention member 16025 which extends downwardly into the longitudinal slot 16015. For example, the retention member 16025 can be pressed into the slot 16015 such that the interaction between the retention member 16025 and the slot 16015 can resist relative movement between the support portion 16010 and the tissue thickness compensator 16020. The body of the tissue thickness compensator 16020 can be comprised of a first material and the retention member 16025 can be

comprised of a second, or different, material. The body of the tissue thickness compensator 16020 can be comprised of a material having a first durometer and the retention member 16025 can be comprised of a material having a second durometer, wherein the second durometer can be higher than the first durometer, for example. In use, the staples 10030 can be pushed upwardly by staple drivers 10040 such that the tips of the staples 10030 can push through the body of the tissue thickness compensator 16020 and emerge from the tissue contacting surface 16021 and capture at least a portion of the tissue thickness compensator 16020 against the targeted tissue. A cutting member passing through the slot 16015 can transect the retention member 16025 as the staples 10030 are being deployed. Once the tissue thickness compensator 16020 has been implanted, the retention member 16025 can be pulled out of the slot 16015. Alternatively, the body of the tissue thickness compensator 16020 can be configured to detach from the retention member 16025.

[0884] Referring now to FIGS. 387 and 389, a staple cartridge 17000 can comprise a support portion 17010 including a deck surface 17011 and a longitudinal slot 17015. The staple cartridge 17000 can further comprise a tissue thickness compensator 17020 positioned above the deck surface 17011. The tissue thickness compensator 17020 can include a longitudinal retention member 17025 which extends downwardly into the longitudinal slot 17015. For example, the retention member 17025 can be pressed into the slot 17015 such that the interaction between the retention member 17025 and the slot 17015 can resist relative movement between the support portion 17010 and the tissue thickness compensator 17020. The retention member 17025 can extend through the entirety of the tissue thickness compensator 17020 to the top surface 17021 thereof wherein body portions 17024 of the tissue thickness compensator 17020 can be attached to opposite sides of the retention member 17025. For example, the retention member 17025 can also be configured to resist the lateral deflection, for example, of the tissue thickness compensator 17020. The body portions 17024 can be comprised of a first material and the retention member 17025 can be comprised of a second, or different, material. The body portions 17024 can be comprised of a material having a first durometer and the retention member 17025 can be comprised of a material having a second durometer, wherein the second durometer can be higher than the first durometer, for example. Further to the above, a cutting member passing through the slot 17015 can transect the retention member 17025 as the staples 10030 are being deployed. Once the tissue thickness compensator 17020 has been implanted, the retention

member 17025 can be pulled out of the slot 17015. Alternatively, the body portions 17024 can be configured to detach from the retention member 17025.

[0885] Referring now to FIG. 388, a staple cartridge 18000 can comprise a support portion 18010 including a deck surface 18011 and a longitudinal slot 18015. The staple cartridge 18000 can further comprise a tissue thickness compensator 18020 positioned above the deck surface 18011. The tissue thickness compensator 18020 can include a longitudinal retention member 18025 which extends downwardly into the longitudinal slot 18015. For example, the retention member 18025 can be pressed into the slot 18015 such that the interaction between the retention member 18025 and the slot 18015 can resist relative movement between the support portion 18010 and the tissue thickness compensator 18020. The retention member 18025 can extend through the entirety of the tissue thickness compensator 18020 to the top surface 18021 thereof wherein body portions 18024 of the tissue thickness compensator 18020 can be attached to opposite sides of the retention member 18025. The retention member 18025 can comprise an enlarged portion 18026 which can be received in a cavity 18016 defined in the slot 18015. For example, the enlarged portion 18026 can resist the withdrawal of the retention member 18025 from the slot 18015.

[0886] The tissue thickness compensator may comprise an extrudable, a castable, and/or moldable composition comprising at least one of the synthetic and/or non-synthetic materials described herein. The tissue thickness compensator may comprise a film or sheet comprising two or more layers. The tissue thickness compensator may be obtained using conventional methods, such as, for example, mixing, blending, compounding, spraying, wicking, solvent evaporating, dipping, brushing, vapor deposition, extruding, calendaring, casting, molding and the like. In extrusion, an opening may be in the form of a die comprising at least one opening to impart a shape to the emerging extrudate. In calendering, an opening may comprise a nip between two rolls. Conventional molding methods may include, but are not limited to, blow molding, injection molding, foam injection, compression molding, thermoforming, extrusion, foam extrusion, film blowing, calendaring, spinning, solvent welding, coating methods, such as dip coating and spin coating, solution casting and film casting, plastisol processing (including knife coating, roller coating and casting), and combinations thereof. In injection molding, an opening may comprise a nozzle and/or channels/runners and/or mold cavities and features. In compression molding, the composition may be positioned in a mold cavity, heated to a suitable

temperature, and shaped by exposure to compression under relatively high pressure. In casting, the composition may comprise a liquid or slurry that may be poured or otherwise provided into, onto and/or around a mold or object to replicate features of the mold or object. After casting, the composition may be dried, cooled, and/or cured to form a solid.

[0887] A method of manufacturing a tissue thickness compensator may generally comprise providing a tissue thickness compensator composition, liquifying the composition to make it flowable, and forming the composition in the molten, semi-molten, or plastic state into a layer and/or film having the desired thickness. Referring to FIG. 527A, a tissue thickness compensator may be manufactured by dissolving a hydrogel precursor in an aqueous solution, dispersing biocompatible particles and/or fibers therein, providing a mold having biocompatible particles therein, providing the solution into the mold, contacting an activator and the solution, and curing the solution to form the tissue thickness compensator comprising an outer layer comprise biocompatible particles and an inner layer comprising biocompatible particles embedded therein. A shown in FIG. 527A, a biocompatible layer 70250 may be provided in the bottom of a mold 70260, and an aqueous solution of a hydrogel precursor 70255 having biocompatible particles 70257 disposed therein may be provided to the mold 70260, and the aqueous solution may be cured to form a tissue thickness compensator having a first layer comprising a biocompatible material, such as ORC, for example, and a second layer comprising a hydrogel having biocompatible fibers, such as ORC fibers, disposed therein. The tissue thickness compensator may comprise a foam comprising an outer layer comprise biocompatible particles and an inner layer comprising biocompatible particles embedded therein. A tissue thickness compensator may be manufactured by dissolving a sodium alginater in water, dispersing ORC particles therein, providing a mold having ORC particles therein, pouring the solution into the mold, spraying or infusing calcium chloride to contact the solution to initiate crosslinking of the sodium alginater, freeze drying the hydrogel to form the tissue thickness compensator comprising an outer layer comprising ORC and an inner layer comprising a hydrogel and ORC particles embedded therein.

[0888] Referring to FIG. 527B, a method of manufacturing a trilayer tissue thickness compensator may generally comprise by dissolving a first hydrogel precursor in a first aqueous solution, dispersing biocompatible particles and/or fibers in the first aqueous solution, providing a mold 70260 having a first layer 70250 of biocompatible particles therein, providing the first aqueous solution into the mold, contacting an activator and the first aqueous solution, curing the

first aqueous solution to form a second layer 70255, dissolving a second hydrogel precursor in a second aqueous solution, providing the second aqueous solution into the mold, curing the second aqueous solution to form a third layer 70265. A trilayer tissue thickness compensator may be manufactured by dissolving a sodium alginater in water to form a first aqueous solution, dispersing ORC particles in the first aqueous solution, providing a mold having a first layer of ORC particles therein, pouring the first aqueous solution into the mold, spraying or infusing calcium chloride to contact the first aqueous solution to initiate crosslinking of the sodium alginater, freeze drying the first aqueous solution to form a second layer comprising a hydrogel having OCR particles embedded therein, dissolving a sodium alginater in water to form a second aqueous solution, pouring the second aqueous solution into the mold, spraying or infusing calcium chloride to contact the second aqueous solution to initiate crosslinking of the sodium alginater, freeze drying the second aqueous solution to form a third layer comprising a hydrogel.

[0889] A method of manufacturing a tissue thickness compensator comprising at least one medicament stored and/or absorbed therein may generally comprise providing a tissue thickness compensator and contacting the tissue thickness compensator and the medicament to retain the medicament in the tissue thickness compensator. A method of manufacturing a tissue thickness compensator comprising an antibacterial material may comprise providing a hydrogel, drying the hydrogel, swelling the hydrogel in an aqueous solution of silver nitrate, contacting the hydrogel and a solution of sodium chloride to form the tissue thickness compensator having antibacterial properties. The tissue thickness compensator may comprise silver dispersed therein.

[0890] Referring to FIG. 533, a method for manufacturing a tissue thickness compensator may comprise co-extrusion and/or bonding. The tissue thickness compensator 70550 may comprise a laminate comprising a first layer 70555 and a second layer 70560 sealingly enclosing an inner layer 70565 comprising a hydrogel, for example. The hydrogel may comprise a dry film, a dry foam, a powder, and/or granules, for example. The hydrogel may comprise super absorbent materials, such as, for example, polyvinylpyrrolidone, carboxy methycellulose, poly sulful propyl acrylate. The first and/or second layers may be made in-line by feeding raw materials of the first and second layers, respectively, into an extruder from a hopper, and thereafter supplying the first and second layers. The raw materials of the inner layer 70565 may be added to a hopper of an extruder. The raw materials can be dispersively mixed and compounded at an elevated temperature within the extruder. As the raw materials exit the die 70570 at an opening, the inner

layer 70565 may be deposited onto a surface of the first layer 70555. The tissue thickness compensator may comprise a foam, film, powder, and/or granule. The first and second layers 70555 and 70560 may be positioned in the face-to-face relationship. The second layer 70560 may be aligned with the first layer 70555 in a face-to-face relationship by a roller 70575. The first layer 70555 may adhere to the second layer 70560 wherein the first and second layers 70555, 70560 may physically entrap the inner layer 70565. The layers may be joined together under light pressure, under conventional calendar bonding processes, and/or through the use of adhesives, for example, to form the tissue thickness compensator 70550. As shown in FIG. 407, the first and second layers 70555 and 70560 may be joined together through a rolling process utilizing a grooved roller 70580, for example. As a result of the above, the inner layer 70565 may be contained and/or sealed by the first and second layers 70555 and 70560 which can collectively form an outer layer, or barrier. The outer layer may prevent or reduce moisture from contacting the inner layer 70565 until the outer layer is ruptured.

[0891] Referring to **FIG. 390**, an end effector 12 for a surgical instrument 10 (**FIG. 1**) can be configured to receive a fastener cartridge assembly, such as staple cartridge 20000, for example. As illustrated in **FIG. 390**, the staple cartridge 20000 can be configured to fit in a cartridge channel 20072 of a jaw 20070 of the end effector 12. Alternatively, the staple cartridge 20000 can be integral to the end effector 12 such that the staple cartridge 20000 and the end effector 12 are formed as a single unit construction. The staple cartridge 20000 can comprise a first body portion, such as rigid support portion 20010, for example. The staple cartridge 20000 can also comprise a second body portion, such as a compressible portion or a tissue thickness compensator 20020, for example. Alternatively, the tissue thickness compensator 20020 may not comprise an integral part of the staple cartridge 20000 but may be otherwise positioned relative to the end effector 12. For example, the tissue thickness compensator 20020 can be secured to an anvil 20060 of the end effector 12 or can be otherwise retained in the end effector 12. Referring to **FIG. 407**, the staple cartridge can further comprise retainer clips 20126 which can be configured to inhibit the tissue thickness compensator 20020 from prematurely detaching from the support portion 20010. The reader will appreciate that the tissue thickness compensators described herein can be installed in or otherwise engaged with a variety of end effectors and that such embodiments are within the scope of the present disclosure.

[0892] Similar to the tissue thickness compensators described herein, referring now to **FIG. 407**, the tissue thickness compensator 20020 can be released from or disengaged with the surgical end effector 12. For example, the rigid support portion 20010 of the staple cartridge 20000 can remain engaged with the fastener cartridge channel 20072 of the end effector jaw 20070 while the tissue thickness compensator 20020 disengages from the rigid support portion 20010. The tissue thickness compensator 20020 can release from the end effector 12 after staples 20030 (**FIGS. 407-412**) are deployed from staple cavities 20012 in the rigid support portion 2010, similar to various embodiments described herein. Staples 20030 can be fired from staple cavities 20012 such that the staples 20030 engage the tissue thickness compensator 20020. Also similar to various embodiments described herein, referring generally to **FIGS. 392, 411** and **412**, a staple 20030 can capture a portion of the tissue thickness compensator 20020 along with stapled tissue T. The tissue thickness compensator 20020 can be deformable and the portion of the tissue thickness compensator 20020 that is captured within a fired staple 20030 can be compressed. Similar to the tissue thickness compensators described herein, the tissue thickness compensator 20020 can compensate for different thicknesses, compressibilities, and / or densities of tissue T captured within each staple 20030. Further, as also described herein, the tissue thickness compensator 20020 can compensate for gaps created by malformed staples 20030.

[0893] The tissue thickness compensator 20020 can be compressible between non-compressed height(s) and compressed height(s). Referring to **FIG. 407**, the tissue thickness compensator 20020 can have a top surface 20021 and a bottom surface 20022. The height of the tissue thickness compensator can be the distance between the top surface 20021 and the bottom surface 20022. The non-compressed height of the tissue thickness compensator 20020 can be the distance between the top surface 20021 and the bottom surface 20022 when minimal or no force is applied to the tissue thickness compensator 20020, i.e., when the tissue thickness compensator 20020 is not compressed. The compressed height of the tissue thickness compensator 20020 can be the distance between the top surface 20021 and the bottom surface 20022 when a force is applied to the tissue thickness compensator 20020, such as when a fired staple 20030 captures a portion of the tissue thickness compensator 20020, for example. The tissue thickness compensator 20020 can have a distal end 20025 and a proximal end 20026. As illustrated in **FIG. 407**, the non-compressed height of the tissue thickness compensator 20020 can be uniform between the distal end 20025 and the proximal end 20026 of the tissue thickness compensator

20020. Alternatively, the non-compressed height can vary between the distal end 20025 and the proximal end 20026. For example, the top surface 20021 and / or bottom surface 20022 of the tissue thickness compensator 20020 can be angled and / or stepped relative to the other such that the non-compressed height varies between the proximal end 20026 and the distal end 20025. The non-compressed height of the tissue thickness compensator 20020 can be approximately 0.08 inches, for example. Alternatively, the non-compressed height of the tissue thickness compensator 20020 can vary between approximately 0.025 inches and approximately 0.10 inches, for example.

[0894] As described in greater detail herein, the tissue thickness compensator 20020 can be compressed to different compressed heights between the proximal end 20026 and the distal end 20025 thereof. Alternatively, the tissue thickness compensator 20020 can be uniformly compressed throughout the length thereof. The compressed height(s) of the tissue thickness compensator 20020 can depend on the geometry of the end effector 12, characteristics of the tissue thickness compensator 20020, the engaged tissue T and / or the staples 20030, for example. The compressed height of the tissue thickness compensator 20020 can relate to the tissue gap in the end effector 12. When the anvil 20060 is clamped towards the staple cartridge 20000, the tissue gap can be defined between a top deck surface 20011 (FIG. 407) of the staple cartridge 20000 and a tissue contacting surface 20061 (FIG. 390) of the anvil 20060, for example. The tissue gap can be approximately 0.025 inches or approximately 0.100 inches, for example. The tissue gap can be approximately 0.750 millimeters or approximately 3.500 millimeters, for example. The compressed height of the tissue thickness compensator 20020 can equal or substantially equal the tissue gap, for example. When tissue T is positioned within the tissue gap of the end effector 12, the compressed height of the tissue thickness compensator can be less in order to accommodate the tissue T. For example, where the tissue gap is approximately 0.750 millimeters, the compressed height of the tissue thickness compensator can be approximately 0.500 millimeters. Where the tissue gap is approximately 3.500 millimeters, the compressed height of the tissue thickness compensator 20020 can be approximately 2.5 mm, for example. Furthermore, the tissue thickness compensator 20020 can comprise a minimum compressed height. For example, the minimum compressed height of the tissue thickness compensator 20020 can be approximately 0.250 millimeters. The tissue gap defined between the deck surface of the staple cartridge and the tissue contacting surface of the anvil can equal, or at

least substantially equal, the uncompressed height of the tissue thickness compensator, for example.

[0895] Referring primarily to **FIG. 391**, the tissue thickness compensator 20020 can comprise a fibrous, nonwoven material 20080 including fibers 20082. The tissue thickness compensator 20020 can comprise felt or a felt-like material. Fibers 20082 in the nonwoven material 20080 can be fastened together by any means known in the art, including, but not limited to, needle-punching, thermal bonding, hydro-entanglement, ultrasonic pattern bonding, chemical bonding, and meltblown bonding. Further, layers of nonwoven material 20080 can be mechanically, thermally, or chemically fastened together to form the tissue thickness compensator 20020. As described in greater detail herein, the fibrous, nonwoven material 20080 can be compressible, which can enable compression of the tissue thickness compensator 20020. The tissue thickness compensator 20020 can comprise a non-compressible portion as well. For example, the tissue thickness compensator 20020 can comprise a compressible nonwoven material 20080 and a non-compressible portion.

[0896] Still referring primarily to **FIG. 391**, the nonwoven material 20080 can comprise a plurality of fibers 20082. At least some of the fibers 20082 in the nonwoven material 20080 can be crimped fibers 20086. The crimped fibers 20086 can be, for example, crimped, twisted, coiled, bent, crippled, spiraled, curled, and / or bowed within the nonwoven material 20080. As described in greater detail herein, the crimped fibers 20086 can be formed in any suitable shape such that deformation of the crimped fibers 20086 generates a spring load or restoring force. The crimped fibers 20086 can be heat-shaped to form a coiled or substantially coil-like shape. The crimped fibers 20086 can be formed from non-crimped fibers 20084. For example, non-crimped fibers 20084 can be wound around a heated mandrel to form a substantially coil-like shape.

[0897] The tissue thickness compensator 20020 can comprise a homogeneous absorbable polymer matrix. The homogenous absorbable polymer matrix can comprise a foam, gel, and / or film, for example. Further, the plurality of fibers 20082 can be dispersed throughout the homogenous absorbable polymer matrix. At least some of the fibers 20082 in the homogenous absorbable polymer matrix can be crimped fibers 20086, for example. As described in greater detail herein, the homogeneous absorbable polymer matrix of the tissue thickness compensator 2002 can be compressible.

[0898] Referring to **FIGS. 394** and **395**, crimped fibers 20086 can be randomly dispersed throughout at least a portion of the nonwoven material 20080. For example, crimped fibers 20086 can be randomly dispersed throughout the nonwoven material 20080 such that a portion of the nonwoven material 20080 comprises more crimped fibers 20086 than other portions of the nonwoven material 20080. Further, the crimped fibers 20086 can congregate in fiber clusters 20085a, 20085b, 20085c, 20085d and 20085e, for example, in the nonwoven material 20080. The shape of the crimped fibers 20086 can cause entanglement of the fibers 20086 during manufacturing of the nonwoven material 20080; entanglement of the crimped fibers 20086 can, in turn, result in the formation of the fiber clusters 20085a, 20085b, 20085c, 20085d and 20085e. Additionally or alternatively, crimped fibers 20086 can be randomly oriented throughout the nonwoven material 20080. For example, referring to **FIG. 391**, a first crimped fiber 20086a can be oriented in a first direction, a second crimped fiber 20086b can be oriented in a second direction, and a third crimped fiber 20086c can be oriented in a third direction.

[0899] The crimped fibers 20086 can be systematically distributed and / or arranged throughout at least a portion of the nonwoven material 20080. For example, referring now to **FIG. 396**, crimped fibers 20186 can be positioned in an arrangement 20185, in which a plurality of crimped fibers 20186a are arranged in a first direction and another plurality of crimped fibers 20186b are arranged in a second direction. The crimped fibers 20186 can overlap such that they become entangled or interconnected with each other. The crimped fibers 20186 can be systematically arranged such that a crimped fiber 20186a is substantially parallel to another crimped fiber 20186a. Still another crimped fiber 20186b can be substantially transverse to some crimped fibers 20186a. Crimped fibers 20186a can be substantially aligned with a first axis Y and crimped fibers 20186b can be substantially aligned with a second axis X. In some cases the first axis Y can be perpendicular or substantially perpendicular to the second axis X, for example.

[0900] Referring primarily to **FIG. 397**, crimped fibers 20286 can be arranged in an arrangement 20285. Each crimped fibers 20286 can comprise a longitudinal axis defined between a first end 20287 and a second end 20289 of the crimped fiber 20286. The crimped fibers 20286 can be systematically distributed in the nonwoven material 20080 such that a first end 20287 of one crimped fiber 20286 is positioned adjacent to a second end 20289 of another crimped fiber 20286. In another example, referring now to **FIG. 398**, a fiber arrangement 20385 can comprise a first crimped fiber 20386a oriented in a first direction, a second crimped fiber 20386b oriented

in a second direction, and a third crimped fiber 20386c oriented in a third direction, for example. A single pattern or arrangement of crimped fibers 20286 can be repeated throughout the nonwoven material 20080. Crimped fibers can be arranged in different patterns throughout the nonwoven material 20080. In a further alternative, the nonwoven material 20080 can comprise at least one pattern of crimped fibers, as well as a plurality of randomly oriented and / or randomly distributed crimped fibers.

[0901] Referring again to **FIG. 391**, the plurality of fibers 20082 in the nonwoven material 20080 can comprise at least some non-crimped fibers 20084. The non-crimped fibers 20084 and crimped fibers 20086 in the nonwoven material 20080 can be entangled or interconnected. The ratio of crimped fibers 20086 to non-crimped fibers 20084 can be approximately 25:1, for example. In another example, the ratio of crimped fibers 20086 to non-crimped fibers 20084 can be approximately 1:25, for example. Alternatively, the ratio of crimped fibers 20086 to non-crimped fibers 20084 can be approximately 1:1, for example. As described in greater detail herein, the number of crimped fibers 20086 per unit volume of nonwoven material 20080 can affect the restoring force generated by the nonwoven material 20080 when the nonwoven material 20080 has been deformed. As also described in greater detail herein, the restoring force generated by the nonwoven material 20080 can also depend on, for example, the material, shape, size, position and / or orientation of crimped and non-crimped fibers 20086, 20084 in the nonwoven material 20080.

[0902] The fibers 20082 of the nonwoven material 20080 can comprise a polymeric composition. The polymeric composition of the fibers 20082 can comprise non-absorbable polymers, absorbable polymers, or combinations thereof. The absorbable polymers can include bioabsorbable, biocompatible elastomeric polymers. Furthermore, the polymeric composition of the fibers 20082 can comprise synthetic polymers, non-synthetic polymers, or combinations thereof. Examples of synthetic polymers include, but are not limited to, polyglycolic acid (PGA), poly(lactic acid) (PLA), polycaprolactone (PCL), polydioxanone (PDO), and copolymers thereof. For example, the fibers 20082 can comprise a 90/10 poly(glycolide-L-lactide) copolymer, such as, for example, the copolymer commercially available from Ethicon, Inc. under the trade designation “VICRYL (polyglactic 910).” Examples of non-synthetic polymers include, but are not limited to, lyophilized polysaccharide, glycoprotein, elastin, proteoglycan, gelatin, collagen, and oxidized regenerated cellulose (ORC). Similar to the polymeric compositions in

tissue thickness compensators described herein, the polymeric composition of the fibers 20082 can include varied amounts of absorbable polymers, non-absorbable polymers, synthetic polymers, and / or non-synthetic polymers, for example, by weight percentage.

[0903] The crimped fibers 20086 of the nonwoven material 20080 can comprise a first polymeric composition and the non-crimped fibers 20084 of the nonwoven material 20080 can comprise a different polymeric composition. For example, the crimped fibers 20086 can comprise synthetic polymer(s), such as, for example, 90/10 poly(glycolide-L-lactide), while the non-crimped fibers 20084 can comprise non-synthetic polymer(s), such as, for example, oxidized regenerated cellulose. Alternatively, the crimped fibers 20086 and the non-crimped fibers 20084 can comprise the same polymeric composition.

[0904] As described herein, crimped fibers 20086 and non-crimped fibers 20084 can be fastened together, for example, by needle-punching, thermal bonding, hydro-entanglement, ultrasonic pattern bonding, chemical bonding, and meltblown bonding. Crimped fibers 20086 comprising synthetic polymers such as, for example, "VICRYL (polyglactic 910)", and non-crimped fibers 20084 comprising oxidized regenerated cellulose can be needle-punched together to form the nonwoven material 20080. The nonwoven material 20080 can comprise approximately 5% to 50% crimped "VICRYL (polyglactic 910)" fibers 20086 by weight and approximately 5% to 50% non-crimped oxidized regenerated cellulose (ORC) fibers 20084 by weight, for example. When the nonwoven material 20080 contacts tissue T, the non-crimped ORC fibers 20084 can rapidly react with plasma in the tissue to form a gelatinous mass, for example. The formation of the gelatinous ORC mass can be instantaneous or nearly instantaneous with the tissue contact. Further, after the formation of the gelatinous ORC mass, the crimped "VICRYL (polyglactic 910)" fibers 20086 can remain dispersed throughout the nonwoven material 20080. For example, the crimped fibers 20086 can be suspended in the gelatinous ORC mass. As the gelatinous ORC mass is bioabsorbed, the crimped "VICRYL (polyglactic 910)" fibers 20086 can exert a springback force on adjacent tissue, as described in greater detail herein. Further, the tissue can begin to heal around the "VICRYL (polyglactic 910)" fibers and / or the formed staples 30030, as also described in greater detail herein.

[0905] Referring primarily to **FIGS. 407-410**, the support portion 20010 of the staple cartridge 20000 can comprise a cartridge body 20017, a top deck surface 20011, and a plurality of staple cavities 20012. Each staple cavity 20012 can define an opening in the deck surface 20011. A

staple 20030 can be removably positioned in a staple cavity 20012. A single staple 20030 is disposed in each staple cavity 20012. Referring primarily to **FIGS. 411** and **412** and similar to the staples described herein, each staple 20030 can comprise a base 20031 having a first end 20035 and a second end 20036. A staple leg 20032 can extend from the first end 20035 of the base 20031 and another staple leg 20032 can extend from the second end 20036 of the base 20031. Referring again to **FIGS. 407-410**, prior to the deployment of the staples 20030, the base 20031 of each staple 20030 can be supported by a staple driver 20040 positioned within the rigid support portion 20010 of the staple cartridge 20000. Also prior to deployment of the staples 20030, the legs 20032 of each staple 20030 can be at least partially contained within a staple cavity 20012.

[0906] The staples 20030 can be deployed between an initial position and a fired position. For example, referring primarily to **FIG. 410**, staples 20030 can be in an initial position (staples 20030e, 20030f), a partially fired or intermediate position (staples 20030c, 20030d), or a fired position (staples 20030a, 20030b). A driver 20040 can motivate the staples between the initial position and the fired position. For example, the base 20031 of each staple 20030 can be supported by a driver 20040. The legs 20032 of a staple (staples 20030e, 20030f in **FIG. 409**, for example) can be positioned within a staple cavity 20012. As the firing member or staple-firing sled 20050 translates from the proximal end 20001 to the distal end 20002 of the staple cartridge 20000, an inclined surface 20051 on the sled 20050 can contact an inclined surface 20042 on a driver 20040 to deploy the staple 20030 positioned above to the contacted driver 20040. The staples 20030 can be deployed between an initial position and a fired position such that the legs 20032 move through the nonwoven material 20080 of the tissue thickness compensator 20020, penetrate the top surface 20021 of the tissue thickness compensator 20020, penetrate tissue T, and contact an anvil 20060 (**FIG. 390**) positioned opposite the staple cartridge 20000 in the end effector 12. The staple legs 20032 can be deformed against the anvil 20060 and the legs 20032 of each staple 20030 can capture a portion of the nonwoven material 20080 and a portion of the tissue T.

[0907] In the fired configuration (**FIGS. 411** and **412**), each staple 20030 can apply a compressive force to the tissue T and to the tissue thickness compensator 20020 captured within the staple 20030. Referring primarily to **FIGS. 409** and **410**, the legs 20032 of each staple 20030 can be deformed downwardly toward the base 20031 of the staple 20030 to form a staple

entrapment area 20039. The staple entrapment area 20039 can be the area in which the tissue T and the tissue thickness compensator 20020 can be captured by a fired staple 20030. In various circumstances, the staple entrapment area 20039 can be defined between the inner surfaces of the deformed legs 20032 and the inner surface of the base 20031 of a staple 20030. The size of the entrapment area 20039 for a staple 20030 can depend on several factors such as the length of the legs, the diameter of the legs, the width of the base, and/or the extent in which the legs are deformed, for example.

[0908] When a nonwoven material 20080 is captured in a staple entrapment area 20039, the captured portion of the nonwoven material 20080 can be compressed. The compressed height of the nonwoven material 20080 captured in a staple entrapment area 20039 can vary within the staple cartridge 20000 depending on the tissue T in that same staple entrapment area 20039. For example, where the tissue T is thinner, the staple entrapment area 20039 may have more room for the nonwoven material 20080 and, as a result, the nonwoven material 20080 may not be as compressed as it would be if the tissue T were thicker. Where the tissue T is thicker, the nonwoven material 20080 can be compressed more to accommodate the thicker tissue T, for example. For example, referring to **FIG. 411**, the nonwoven material 20080 can be compressed to a first height in a first staple entrapment area 20039a, a second height in a second staple entrapment area 20039b, a third height in a third staple entrapment area 20039c, a fourth height in a fourth staple entrapment area 20039d, and a fifth height in a fifth staple entrapment area 20039e, for example. Similarly, as illustrated in **FIG. 412**, the nonwoven material 20080 can be compressed to a first height in the first staple entrapment area 20039a, a second height in the second staple entrapment area 20039b, a third height in the third staple entrapment area 20039c, and a fourth height in the fourth staple entrapment area 20039d. Alternatively, the compressed height of the nonwoven material 20080 can be uniform throughout the staple cartridge 20010.

[0909] An applied force can move the nonwoven material 20080 from an initial uncompressed configuration to a compressed configuration. Further, the nonwoven material 20080 can be resilient, such that, when compressed, the nonwoven material 20080 can generate a springback or restoring force. When deformed, the nonwoven material 20080 can seek to rebound from the compressed or deformed configuration. As the nonwoven material 20080 seeks to rebound, it can exert a springback or restoring force on the tissue also captured in the staple entrapment area 30039, as described in greater detail herein. When the applied force is subsequently removed, the

restoring force can cause the nonwoven material to rebound from the compressed configuration. The nonwoven material 20080 can rebound to the initial, uncompressed configuration or may rebound to a configuration substantially similar to the initial, uncompressed configuration. The deformation of the nonwoven material 20080 can be elastic. The deformation of the nonwoven material can be partially elastic and partially plastic.

[0910] When a portion of the nonwoven material 20080 is compressed in a staple entrapment area 20039, the crimped fibers 20086 in that portion of the nonwoven compensator 20039 can also be compressed or otherwise deformed. The amount a crimped fiber 20086 is deformed can correspond to the amount that the captured portion of the nonwoven material 20080 is compressed. For example, referring to **FIG. 392**, the nonwoven material 20080 can be captured by deployed staples 20030. Where the nonwoven material 20080 is more compressed by a deployed staple 20030, the average deformation of crimped fibers 20086 can be greater. Further, where the nonwoven material 20080 is less compressed by a deployed staple, the average deformation of crimped fibers 20086 can be smaller. Similarly, referring to **FIGS. 411** and **412**, in a staple entrapment area 20039d where the nonwoven material 20080 is more compressed, the crimped fibers 20086 in that staple entrapment area 20039d can be, on average, more deformed. Further, in a staple entrapment area 20039a where the nonwoven material 20080 is less compressed, the crimped fibers 20086 in that staple entrapment area 20039a can be, on average, less deformed.

[0911] The ability of the nonwoven material 20080 to rebound from the deformed configuration, i.e., the resiliency of the nonwoven material 20080, can be a function of the resiliency of the crimped fibers 20086 in the nonwoven material 20080. The crimped fibers 20086 can deform elastically. Deformation of the crimped fibers 20086 can be partially elastic and partially plastic. Compression of each crimped fiber 20086 can cause the compressed crimped fibers 20086 to generate a springback or restoring force. For example, the compressed crimped fibers 20086 can generate a restoring force as the fibers 20086 seek to rebound from their compressed configuration. The fibers 20086 can seek to return to their initial, uncompressed configuration or to a configuration substantially similar thereto. The crimped fibers 20086 can seek to partially return to their initial configuration. Only a portion of the crimped fibers 20086 in the nonwoven material 20080 can be resilient. When a crimped fiber 20086 is comprised of a linear-elastic material, the restoring force of the compressed crimped fiber 20086 can be a function of the

amount the crimped fiber 20086 is compressed and the spring rate of the crimped fiber 20086, for example. The spring rate of the crimped fiber 20086 can at least depend on the orientation, material, shape and / or size of the crimped fiber 20086, for example.

[0912] The crimped fibers 20086 in the nonwoven material 20080 can comprise a uniform spring rate. Alternatively, the spring rate of the crimped fibers 20086 in the nonwoven material 20080 can vary. When a crimped fiber 20086 having a large spring rate is greatly compressed, the crimped fiber 20086 can generate a large restoring force. When a crimped fiber 20086 having the same large spring rate is less compressed, the crimped fiber 20086 can generate a smaller restoring force. The aggregate of restoring forces generated by compressed crimped fibers 20086 in the nonwoven material 20080 can generate a combined restoring force throughout the nonwoven material 20080 of the tissue thickness compensator 20020. The nonwoven material 20080 can exert the combined restoring force on tissue T captured within a fired staple 20030 with the compressed nonwoven material 20080.

[0913] Furthermore, the number of crimped fibers 20086 per unit volume of nonwoven material 20080 can affect the spring rate of the nonwoven material 20080. For example, the resiliency in a nonwoven material 20080 can be low when the number of crimped fibers 20086 per unit volume of nonwoven material 20080 is low, for example; the resiliency of the nonwoven material 20080 can be higher when the number of crimped fibers 20086 per unit volume of nonwoven material 20080 is higher, for example; and the resiliency of the nonwoven material 20080 can be higher still when the number of crimped fibers 20086 per unit volume of nonwoven material 20080 is even higher, for example. When the resiliency of the nonwoven material 20080 is low, such as when the number of crimped fibers 20086 per unit volume of nonwoven material 20080 is low, the combined restoring force exerted by the tissue thickness compensator 20020 on captured tissue T can also be low. When the resiliency of the nonwoven material 20080 is higher, such as when the number of crimped fibers 20086 per unit volume of nonwoven material 20080 is higher, the aggregate restoring force exerted by the tissue thickness compensator 20020 on captured tissue T can also be higher.

[0914] Referring primarily to **FIG. 393**, a nonwoven material 20080' of a tissue thickness compensator 20020' can comprise a therapeutic agent 20088, such as a medicament and / or pharmaceutically active agent, for example. The nonwoven material 20080' can release a therapeutically effective amount of the therapeutic agent 20088. For example, the therapeutic

agent 20088 can be released as the nonwoven material 20080' is absorbed. The therapeutic agent 20088 can be released into fluid, such as blood, for example, passing over or through the nonwoven material 20080'. Examples of therapeutic agents 20088 can include, but are not limited to, haemostatic agents and drugs such as, for example, fibrin, thrombin, and / or oxidized regenerated cellulose (ORC); anti-inflammatory drugs such as, for example, diclofenac, aspirin, naproxen, sulindac, and / or hydrocortisone; antibiotic and antimicrobial drugs or agents such as, for example, triclosan, ionic silver, ampicillin, gentamicin, polymyxin B, and / or chloramphenicol; and anticancer agents such as, for example, cisplatin, mitomycin, and / or adriamycin. The therapeutic agent 20088 can comprise a biologic, such as a stem cell, for example. The fibers 20082 of the nonwoven material 20080' can comprise the therapeutic agent 20088. Alternatively, the therapeutic agent 20088 can be added to the nonwoven material 20080' or otherwise integrated into the tissue thickness compensator 20020'.

[0915] Primarily referring to **FIGS. 399-399B**, a tissue thickness compensator 20520 for an end effector 12 (**FIG. 390**) can comprise a plurality of springs or coiled fibers 20586. Similar to the crimped fibers 20086 described herein, the coiled fibers 20586 can be, for example, crimped, twisted, coiled, bent, crippled, spiraled, curled, and / or bowed within the tissue thickness compensator 20520. The coiled fibers 20586 can be wound around a mandrel to form a coiled or substantially coil-like shape. The coiled fibers 20586 can be randomly oriented and / or randomly distributed throughout the tissue thickness compensator 20520. Alternatively, the coiled fibers 20586 can be systematically arranged and / or uniformly distributed throughout the tissue thickness compensator 20520. For example, referring to **FIG. 399**, the coiled fibers 20586 can comprise a longitudinal axis between a first end 20587 and a second end 20589 of the coiled fiber 20586. The longitudinal axes of the coiled fibers 20520 in the tissue thickness compensator 20520 can be parallel or substantially parallel. The first end 20587 of each coiled fiber 20520 can be positioned along a first longitudinal side 20523 of the tissue thickness compensator 20520 and the second end 20589 of each coiled fiber 20586 can be positioned along a second longitudinal side 20524 of the tissue thickness compensator 20520. In such an arrangement, the coiled fibers 20586 can laterally traverse the tissue thickness compensator. Alternatively, the coiled fibers 20586 can longitudinally or diagonally traverse the tissue thickness compensator 20520.

[0916] Similar to the crimped fibers 20086 described herein, the coiled fibers 20586 can comprise a polymeric composition. The crimped fibers 20586 can be at least partially elastic

such that deformation of the crimped fibers 20586 generates a restoring force. The polymeric composition of the coiled fibers 20586 can comprise polycaprolactone (PCL), for example, such that the coiled fibers 20586 are not soluble in a chlorophyll solvent. Referring to **FIG. 399A**, the springs or coiled fibers 20520 can be retained in a compensation material 20580. The compensation material 20580 can hold the coiled fibers 20586 in a loaded position such that the coiled fibers 20586 exert a spring load on, or within, the compensation material 20580. The compensation material 20580 can hold the coiled fibers 20586 in a neutral position where the coiled fibers 20586 are not exerting a spring load on, or within, the compensation material 20580. The compensation material 20580 can be bioabsorbable and, can comprise a foam, such as, for example, polyglycolic acid (PGA) foam. Furthermore, the compensation material 20580 can be soluble in a chlorophyll solvent, for example. The tissue thickness compensator can comprise coiled fibers 20586 that comprise polycaprolactone (PCL) and compensation material 20580 that comprises polyglycolic acid (PGA) foam, for example, such that the coiled fibers 20520 are not soluble in a chlorophyll solvent while the compensation material 20580 is soluble in the chlorophyll solvent. The compensation material 20580 can be at least partially elastic, such that compression of the compensation material 20580 generates a restoring force. Further, referring to **FIG. 399B**, the compensation material 20580 of the tissue thickness compensator 20520 can comprise a therapeutic agent 20588, such as stem cells, for example. The compensation material 20580 can release a therapeutically effective amount of the therapeutic agent 20588 as the compensation material 20580 is absorbed.

[0917] Similar to the tissue thickness compensator 20020 described herein, the tissue thickness compensator 20520 can be compressible. For example, as staples 20030 (**FIGS. 407-410**) are deployed from an initial position to a fired position, the staples 20030 can engage a portion of tissue thickness compensator 20520. A staple 20030 can capture a portion of the tissue thickness compensator 20520 and adjacent tissue T. The staple 20030 can apply a compressive force to the captured portion of the tissue thickness compensator 20520 and tissue T such that the tissue thickness compensator 20520 is compressed from a non-compressed height to a compressed height. Compression of the tissue thickness compensator 20520 can result in a corresponding deformation of the coiled fibers 20586 therein. As described in greater detail herein, deformation of each coiled fiber 20586 can generate a restoring force that can depend on the resiliency of the coiled fiber, for example, the amount the coiled fiber 20586 is deformed and / or the spring rate

of the coiled fiber 20586. The spring rate of the coiled fiber 20586 can at least depend on the orientation, material, shape and / or size of the coiled fiber 20586, for example. Deformation of the coiled fibers 20586 in the tissue thickness compensator 20520 can generate restoring forces throughout the tissue thickness compensator 20520. The tissue thickness compensator 20520 can exert the aggregate restoring force generated by the deformed coiled fibers 20586 and / or the resilient compensation material 20586 on the captured tissue T in the fired staples 20030.

[0918] Primarily referring to **FIGS. 400** and **401**, a tissue thickness compensator 20620 for an end effector 12 can comprise a plurality of spring coils 20686. Similar to the crimped fibers 20086 and coiled fibers 20586 described herein, spring coils 20686 can be, for example, crimped, twisted, coiled, bent, crippled, spiraled, curled, and / or bowed within the tissue thickness compensator 20620. Similar to the fibers and coils described herein, the spring coils 20686 can comprise a polymeric composition. Further, the spring coils 20686 can be at least partially elastic such that deformation of the spring coils 20686 generates a restoring force. The spring coils 20686 can comprise a first end 20687, a second end 20689, and a longitudinal axis therebetween. Referring to **FIG. 400**, the first end 20686 of a spring coil 20686 can be positioned at or near a proximal end 20626 of the tissue thickness compensator and the second end 20689 of the same spring coil 20686 can be positioned at or near a distal end 20625 of the tissue thickness compensator 20620 such that the spring coil 20686 longitudinally traverses the tissue thickness compensator 20620, for example. Alternatively, the coiled fibers 20686 can laterally or diagonally traverse the tissue thickness compensator 20620.

[0919] The tissue thickness compensator 20620 can comprise an outer film 20680 that at least partially surrounds at least one spring coil 20686. Referring to **FIG. 400**, the outer film 20680 can extend around the perimeter of multiple spring coils 20686 in the tissue thickness compensator 20620. Alternatively, the outer film 20680 can completely encapsulate the spring coils 20686 or at least one spring coil 20686 in the tissue thickness compensator 20620. The outer film 20680 can retain the spring coils 20686 in the end effector 12. The outer film 20680 can hold the spring coils 20686 in a loaded position such that the spring coils 20686 generate a spring load and exert a springback force on the outer film 20680. Alternatively, the outer film 20680 can hold the spring coils 20686 in a neutral position. The tissue thickness compensator 20620 can also comprise a filling material 20624. The filling material 20624 can be retained within and / or around the spring coils 20686 by the outer film 20680. The filling material 20624

can comprise a therapeutic agent 20688, similar to the therapeutic agents described herein. Further, the filling material 20624 can support the spring coils 20686 within the tissue thickness compensator 20620. The filling material 20624 can be compressible and at least partially resilient, such that the filling material 20624 contributes to the springback or restoring force generated by the tissue thickness compensator 20620, as described in greater detail herein.

[0920] Similar to the tissue thickness compensators described herein, the tissue thickness compensator 20620 can be compressible. As staples 20030 (**FIGS. 407-410**) are deployed from an initial position to a fired position, the staples 20030 can engage a portion of the tissue thickness compensator 20620. Each staple 20030 can capture a portion of the tissue thickness compensator 20620 along with adjacent tissue T. The staple 20030 can apply a compressive force to the captured portion of the tissue thickness compensator 20620 and the captured tissue T such that the tissue thickness compensator 20620 is compressed between a non-compressed height and a compressed height. Compression of the tissue thickness compensator 20620 can result in a corresponding deformation of the spring coils 20686 retained therein (**FIG. 401**). As described in greater detail herein, deformation of each spring coils 20686 can generate a restoring force that depends on the resiliency of the spring coil 20686, for example, the amount the spring coil 20686 is deformed and / or the spring rate of the spring coil 20686. The spring rate of a spring coil 20686 can at least depend on the material, shape and / or dimensions of the spring coil 20686, for example. Furthermore, depending on the resiliency of the filling material 20624 and the outer film 20680, compression of the filling material 20624 and / or the outer film 20680 can also generate restoring forces. The aggregate of restoring forces generated at least by the deformed spring coils 20686, the filling material 20624 and / or the outer film 20680 in the tissue thickness compensator 20620 can generate restoring forces throughout the tissue thickness compensator 20620. The tissue thickness compensator 20620 can exert the aggregate restoring force generated by the deformed spring coils 20686 on the captured tissue T in a fired staple 20030.

[0921] Primarily referring to **FIGS. 402-404**, a tissue thickness compensator 20720 for an end effector 12 can comprise a plurality of spring coils 20786. Similar to the coiled fibers and springs described herein, spring coils 20786 can be, for example, crimped, twisted, coiled, bent, crippled, spiraled, curled, and / or bowed within the tissue thickness compensator 20720. The spring coils 20786 can be at least partially elastic such that deformation of the spring coils 20786 generates a

restoring force. Further, the spring coils 20786 can comprise a first end 20787, a second end 20789, and a longitudinal axis therebetween. Referring primarily to **FIG. 404**, the first end 20787 of the spring coil 20786 can be positioned at or near a proximal end 20726 of the tissue thickness compensator 20720 and the second end 20789 of the spring coil 20786 can be positioned at or near a distal end 20725 of the tissue thickness compensator 20720 such that the spring coil 20786 longitudinally traverses the tissue thickness compensator 20720. The spring coil 20786 can longitudinally extend in two parallel rows in the tissue thickness compensator 20720. The tissue thickness compensator 20720 can be positioned in an end effector 12 such that a sled 20050 (**FIG. 390**) or cutting element 20052 can translate along a slot 20015 between the parallel rows of spring coils 20786. Alternatively, the spring coils 20786 can laterally or diagonally traverse the tissue thickness compensator 20720.

[0922] Referring again to **FIG. 404**, the spring coils 20786 can be retained or embedded in a compensation material 20780. The compensation material 20780 can be bioabsorbable and, can comprise foam, such as, for example, polyglycolic acid (PGA) foam. The compensation material 20780 can be resilient such that deformation of the compensation material 20780 generates a springback force. The compensation material 20780 can be soluble in a chlorophyll solvent, for example. For example, the tissue thickness compensator can comprise spring coils 20786 that comprise polycaprolactone (PCL) and compensation material 20780 that comprises polyglycolic acid (PGA) foam such that the spring coils 20786 are not soluble in a chlorophyll solvent while the compensation material 20780 is soluble in a chlorophyll solvent, for example. The compensation material 20780 can be at least partially resilient such that deformation of the compensation material 20780 generates a spring load or restoring force.

[0923] The tissue thickness compensator 20720 can comprise interwoven threads 20790, which can extend between parallel rows of spring coils 20786. For example, referring to **FIG. 404**, a first interwoven thread 20790 can diagonally traverse the two parallel rows of spring coils 20786 and a second interwoven thread 20790 can also diagonally traverse the two parallel rows of spring coils 20786. The first and second interwoven threads 20790 can crisscross. The interwoven threads 20790 can crisscross multiple times along the length of the tissue thickness compensator 20720. The interwoven threads 20790 can hold the spring coils 20786 in a loaded configuration such that the spring coils 20786 are held in a substantially flat position in the tissue thickness compensator 20720. The interwoven threads 20790 that traverse the tissue thickness

compensator 20720 can be directly attached to the spring coils 20786. Alternatively, the interwoven threads 20790 can be coupled to the spring coils 20786 via a support 20792 that extends through each spring coil 20786 along the longitudinal axis thereof.

[0924] As described in greater detail herein, a staple cartridge 20000 can comprise a slot 20015 configured to receive a translating sled 20050 comprising a cutting element 20052 (**FIG. 390**). As the sled 20050 translates along the slot 20015, the sled 20050 can eject staples 20030 from fastener cavities 20012 in the staple cartridge 20000 and the cutting element 20052 can simultaneously or nearly simultaneously sever tissue T. Referring again to **FIG. 404**, as the cutting element 20052 translates, it can also sever the interwoven threads 20790 that crisscross between the parallel rows of spring coils 20786 in the tissue thickness compensator 20720. As the interwoven threads 20790 are severed, each spring coil 20786 can be released from its loaded configuration such that each spring coil 20786 reverts from the loaded, substantially flat position to an expanded position in the tissue thickness compensator 20720. When a spring coil 20786 is expanded, the compensation material 20780 surrounding the spring coil 20786 can also expand.

[0925] As staples 20030 (**FIGS. 407-410**) are deployed from an initial position to a fired position, the staples 20030 can engage a portion of the tissue thickness compensator 20720 and the tissue thickness compensator 20720 can expand, or attempt to expand, within the staples 20030 and can apply a compressive force to the tissue T. At least one staple 20030 can capture a portion of the tissue thickness compensator 20720, along with adjacent tissue T. The staple 20030 can apply a compressive force to the captured portion of the tissue thickness compensator 20720 and the captured tissue T, such that the tissue thickness compensator 20720 is compressed between a non-compressed height and a compressed height. Compression of the tissue thickness compensator 20720 can result in a corresponding deformation of the spring coils 20786 and compensation material 20780 retained therein. As described in greater detail herein, deformation of each spring coils 20786 can generate a restoring force that can depend on the resiliency of the spring coil, for example, the amount the spring coil 20786 is deformed and / or the spring rate of the spring coil 20786. The spring rate of a spring coil 20786 can at least depend on the orientation, material, shape and / or size of the spring coil 20786, for example. The aggregate of restoring forces generated by at least the deformed spring coils 20786 and / or the compensation material 30380 in the tissue thickness compensator 20720 can generate restoring forces throughout the tissue thickness compensator 20720. The tissue thickness compensator 20720 can

exert the aggregate restoring force generated by the deformed spring coils 20786 in the tissue thickness compensator 20720 on the captured tissue T and fired staples 20030.

[0926] Primarily referring to **FIGS. 405** and **406**, a tissue thickness compensator 20820 for a surgical end effector 12 can comprise a spring coil 20886. Similar to the fibers and coils described herein, spring coil 20886 can be, for example, crimped, twisted, coiled, bent, crippled, spiraled, curled, and / or bowed within the tissue thickness compensator 20820. The spring coil 20886 can comprise a polymeric composition and can be at least partially elastic, such that deformation of the spring coil 20886 generates a springback force. Further, the spring coil 20886 can comprise a first end 20887 and a second end 20889. Referring to **FIG. 405**, the first end 20887 can be positioned at or near a proximal end 20826 of the tissue thickness compensator 20820 and the second end 20889 can be positioned at or near a distal end 20825 of the tissue thickness compensator 20820. The spring coil 20886 can wind or meander from the proximal end 20825 to the distal end 20826 of the tissue thickness compensator 20820.

[0927] Referring again to **FIG. 405**, the spring coil 20886 can be retained or embedded in a compensation material 20880. The compensation material 20880 can be bioabsorbable and, can comprise a foam, such as, for example, polyglycolic acid (PGA) foam. The compensation material 20880 can be soluble in a chlorophyll solvent, for example. The tissue thickness compensator can comprise spring coils 20886 comprising polycaprolactone (PCL) and compensation material 20880 comprising polyglycolic acid (PGA) foam, for example, such that the spring coil 20886 is not soluble in a chlorophyll solvent while the compensation material 20880 is soluble in a chlorophyll solvent. The compensation material 20880 can be at least partially resilient such that deformation of the compensation material 20880 generates a spring load or restoring force.

[0928] Similar to tissue thickness compensators described herein, for example, the tissue thickness compensator 20820 can be compressible. Compression of the tissue thickness compensator 20820 can result in a deformation of at least a portion of the spring coil 20886 retained or embedded in the compensation material 20880 of the tissue thickness compensator 20820. As described in greater detail herein, deformation of the spring coil 20886 can generate restoring forces that can depend on the resiliency of the spring coil 20886, the amount the spring coil 20886 is deformed, and / or the spring rate of the spring coil 20886, for example. The aggregate of restoring forces generated by the deformed spring coil 20886 and / or deformed

compensation material 20880 can generate restoring forces throughout the tissue thickness compensator 20820. The tissue thickness compensator 20820 can exert the aggregate restoring force on the captured tissue T in the fired staples 20030.

[0929] Referring now to **FIG. 413**, a surgical end effector 12 can comprise a tissue thickness compensator 30020 having at least one tubular element 30080. The tissue thickness compensator 30020 can be retained in the surgical end effector 12. As described in greater detail herein, a fastener in the end effector 12 can be deployed such that the fastener moves to a fired position and deforms at least a portion of the tubular element 30080 in the tissue thickness compensator 30020. The reader will appreciate that tissue thickness compensators comprising at least one tubular element as described herein can be installed in or otherwise engaged with a variety of surgical end effectors and that such embodiments are within the scope of the present disclosure.

[0930] Still referring to **FIG. 413**, the tissue thickness compensator 30020 can be positioned relative to the anvil 30060 of the end effector 12. Alternatively, the tissue thickness compensator 30020 can be positioned relative to a fastener cartridge assembly, such as staple cartridge 30000, of the end effector 12. The staple cartridge 30000 can be configured to fit in a cartridge channel 30072 of a jaw 30070 of the end effector 12. For example, the tissue thickness compensator 30020 can be releasably secured to the staple cartridge 30000. The tubular element 30080 of the tissue thickness compensator 30020 can be positioned adjacent to a top deck surface 30011 of a rigid support portion 30010 of the staple cartridge 30000. The tubular element 30080 can be secured to the top deck surface 30011 by an adhesive or by a wrap, similar to at least one of the wraps described herein (*e.g.*, **FIG. 218**). The tissue thickness compensator 30020 can be integral to an assembly comprises the staple cartridge 30000 such that the staple cartridge 30000 and the tissue thickness compensator 30020 are formed as a single unit construction. For example, the staple cartridge 30000 can comprise a first body portion, such as the rigid support portion 30010, and a second body portion, such as the tissue thickness compensator 30020, for example.

[0931] Referring to **FIGS. 413-415**, the tubular element 30080 in the tissue thickness compensator 30020 can comprise an elongate portion 30082 having at least one lumen 30084 that extends at least partially therethrough. Referring primarily to **FIG. 415**, the elongate portion 30082 of the tubular element 30080 can comprise woven or braided strands 30090, as described in greater detail herein. Alternatively, the elongate portion 30082 can comprise a solid structure, such as a polymer extrusion, rather than woven strands 30090. The elongate portion 30082 of the

tubular element 30080 can comprise a thickness. The thickness of the elongate portion 30082 can be substantially uniform throughout the length and around the diameter thereof; in other cases, the thickness can vary. The elongate portion 30082 can be elongated such that the length of the elongate portion 30082 is greater than the diameter of the elongate portion 30082, for example. The elongate portion can comprise a length of approximately 1.20 inches to approximately 2.60 inches and a diameter of approximately 0.10 inches to approximately 0.15 inches, for example. The length of the tubular element 20080 can be approximately 1.40 inches, for example, and the diameter of the tubular element 20080 can be approximately 0.125 inches, for example. Furthermore, the elongate portion 30082 can define a substantially circular or elliptical cross-sectional shape, for example. Alternatively, the cross-sectional shape can comprise a polygonal shape, such as, for example, a triangle, a hexagon and / or an octagon. Referring again to **FIG. 413**, the tubular element 30080 can comprise a first distal end 30083 and a second proximal end 30085. The cross-sectional shape of the elongate portion 30082 can narrow at the first and / or second end 30083, 30085 wherein at least one end 30083, 30085 of the tubular element 30080 can be closed and / or sealed. Alternatively, a lumen 30084 can continue through the distal ends 30083, 30085 of the tubular element 30080 such that the ends 30083, 30085 are open.

[0932] The tubular element 30080 can comprise a single central lumen 30084 that extends at least partially through the elongate portion 30084. The lumen 30084 can extend through the entire length of the elongate portion 30084. In a further alternative, the tubular element 30080 can comprise multiple lumens 30084 extending therethrough. Lumens 30084 extending through the tubular element 30080 can be circular, semi-circular, wedge-shaped, and / or combinations thereof. A tubular element 30080 can also comprise support webs that can form a modified "T" or "X" shape, for example, within the lumen 30084. The dimensions, lumen(s), and / or support web(s) within the tubular element 30080 can define the cross-sectional shape of the tubular element 30080. The cross-sectional shape of the tubular element 30080 can be consistent throughout the length thereof or, as an alternative, the cross-sectional shape of the tubular element 30080 can vary along the length thereof. As described in greater detail herein, the cross-sectional shape of the tubular element 30080 can affect the compressibility and resiliency of the tubular element 30080.

[0933] The tubular element 30080 can comprise a vertical diameter and a horizontal diameter; the dimensions thereof can be selected depending on the arrangement of the tubular element

30080 in the end effector 12, the dimensions of the end effector 12, including the tissue gap of the end effector 12, and the expected geometry of the staple entrapment areas 30039. For example, the vertical diameter of the tubular element 30080 can relate to the expected height of a formed staple. In such cases, the vertical diameter of the tubular element 30080 can be selected such that the vertical diameter can be reduced approximately 5% to approximately 20% when the tubular element 30080 is captured within a formed staple 30030. For example, a tubular element 30080 having a vertical diameter of approximately 0.100 inches may be used for staples having an expected formed height of approximately 0.080 inches to approximately 0.095 inches. As a result, the vertical diameter of the tubular element 30080 can be reduced approximately 5% to approximately 20% when captured within the formed staple 30030 even when no tissue T is captured therein. When tissue T is captured within the formed staple 30030, the compression of the tubular element 30080 may be even greater. The vertical diameter can be uniform throughout the length of the tubular element 30080 or, as an alternative, the vertical diameter can vary along the length thereof.

[0934] The horizontal diameter of the tubular element 30080 can be greater than, equal to, or less than the vertical diameter of the tubular element 30080 when the tubular element 30080 is in an undeformed or rebounded configuration. For example, referring to **FIG. 414**, the horizontal diameter can be approximately three times larger than the vertical diameter, for example. In some cases the horizontal diameter can be approximately 0.400 inches and the vertical diameter can be approximately 0.125 inches, for example. Alternatively, referring now to **FIG. 416**, the horizontal diameter of a tubular element 31080 can be equal to or substantially equal to the vertical diameter of the tubular element 31080 when the tubular element 31080 is in an undeformed or rebounded configuration. In some cases the horizontal diameter can be approximately 0.125 inches and the vertical diameter can also be approximately 0.125 inches, for example. The tubular element 30080 can comprise a vertical diameter of approximately 0.125 inches, a horizontal diameter of approximately 0.400 inches, and a length of approximately 1.400 inches. As described in greater detail herein, when a force A is applied to the tubular element 30080 and / or 31080, the tubular element can deform such that the cross-sectional geometry, including the horizontal and vertical diameters, can change.

[0935] Referring again to **FIGS. 413-415**, the tubular element 30080 in the tissue thickness compensator 30020 can be deformable. The entire tubular element 30080 can be deformable. For

example, the tubular element 30080 can be deformable from the proximal end 30083 to the distal end 30085 of the elongate portion 30082 and around the entire circumference thereof. Alternatively, only a portion of the tubular element 30080 can be deformable. For example, only an intermediate length of the elongate portion 30082 and / or only a portion of the circumference of the tubular element 30080 can be deformable.

[0936] When a compressive force is applied to a contact point on the elongate portion 30082 of the tubular element 30080, the contact point can shift, which can alter the cross-sectional dimensions of the tubular element 30080. For example, referring again to **FIG. 414**, the tubular element 30080 can comprise a top apex 30086 and a bottom apex 30088 on the elongate portion 30082. In the initial, undeformed configuration, the tubular element 30080 can comprise undeformed cross-sectional dimensions, including an undeformed vertical diameter between the top apex 30086 and the bottom apex 30088. When a compressive force A is applied to the top apex 30086, the tubular element 30080 can move to a deformed configuration. In the deformed configuration, the cross-sectional dimensions of the tube 30080 can be altered. For example, the tube 30086 can comprise a deformed vertical diameter between the top apex 30086 and the bottom apex 30088, which can be less than the undeformed vertical diameter. Referring to **FIG. 416**, the horizontal diameter of the deformed tube 30080 can be lengthened, for example, when the tubular element 30080 moves from an undeformed configuration to a deformed configuration. The deformed cross-sectional dimensions of the deformed tube 30080 can at least depend on the position, angular orientation, and / or magnitude of the applied force A. As described in greater detail herein, deformation of a tubular element 30080 can generate a springback or restoring force that can depend on the resiliency of the tubular element 30080.

[0937] Referring still to **FIG. 414**, the tubular element 30080 can generate a springback or restoring force when compressed. In such cases, as described herein, the tubular element 30080 can move from an initial undeformed configuration to a deformed configuration when a force A is applied to a contact point on the elongate portion 30082 of the tubular element 30080. When the applied force A is removed, the deformed tube 30080 can rebound from the deformed configuration. The deformed tube 30080 may rebound to the initial, undeformed configuration or may rebound to a configuration substantially similar to the initial, undeformed configuration. The ability of the tubular element 30080 to rebound from a deformed configuration relates to the resiliency of the tubular element 30080.

[0938] Referring again to **FIG. 414**, a tubular element 30080 can exert a springback or restoring force. The restoring force can be generated by the tubular element 30080 when an applied force A is exerted on the tubular element 30080, for example, by a staple 30030 (**FIGS. 417 and 418**), as described in greater detail herein. An applied force A can alter the cross-sectional dimensions of the tubular element 30080. Furthermore, in linear-elastic materials, the restoring force of each deformed portion of the tubular element 30080 can be a function of the deformed dimensions of the tubular element 30080 and the spring rate of that portion of the tubular element 30080. The spring rate of a tubular element 30080 can at least depend on the orientation, material, cross-sectional geometry and / or dimensions of the tubular element 30080, for example. The tubular element 30080 in a tissue thickness compensator 30020 can comprise a uniform spring rate. Alternatively, the spring rate can vary along the length and / or around the diameter of the tubular element 30080. When a portion of a tubular element 30080 having a first spring rate is greatly compressed, the tubular element 30080 can generate a large restoring force. When a portion of the tubular element 30080 having the same first spring rate is less compressed, the tubular element 30080 can generate a smaller restoring force.

[0939] Referring again to **FIG. 413**, the tubular element 30080 in the tissue thickness compensator 30020 can comprise a polymeric composition. The elongate portion 30082 of the tubular element 30080 can comprise the polymeric composition. Further, the polymeric composition can comprise an at least partially elastic material such that deformation of the tubular element 30080 generates a restoring force. The polymeric composition can comprise non-absorbable polymers, absorbable polymers, or combinations thereof, for example. Examples of synthetic polymers include, but are not limited to, polyglycolic acid (PGA), poly(lactic acid) (PLA), polycaprolactone (PCL), polydioxanone (PDO), and copolymers thereof. The absorbable polymers can include bioabsorbable, biocompatible elastomeric polymers, for example. Furthermore, the polymeric composition of the tubular element 30080 can comprise synthetic polymers, non-synthetic polymers, or combinations thereof, for example. The polymeric composition of the tubular element 30080 can include varied amounts of absorbable polymers, non-absorbable polymers, synthetic polymers, and / or non-synthetic polymers, for example, by weight percentage.

[0940] Referring to **FIG. 413** and **414**, the tubular element 30080 can comprise a therapeutic agent 30098 such as a pharmaceutically active agent or medicament, for example. The

therapeutic agent 30098 can be retained in the lumen 30084 of the tubular element 30080. The elongate portion 30082 can encapsulate or partially encapsulate the therapeutic agent 30098. Additionally or alternatively, the polymeric composition of the elongate portion 30082 can comprise the therapeutic agent 30098. The tubular element 30080 can release a therapeutically effective amount of the therapeutic agent 30098. The therapeutic agent 30098 can be released as the tubular element 30080 is absorbed. For example, the therapeutic agent 30098 can be released into fluid (such as blood) passing over or through the tubular element 30080. In a further alternative, the therapeutic agent 30098 can be released when a staple 30030 (**FIG. 417** and **418**) pierces the tubular element 30080 and/or when the cutting element 30052 on the staple-firing sled 30050 (**FIG. 413**) cuts a portion of the tubular element 30080, for example. Examples of therapeutic agents 30098 can include, but are not limited to, haemostatic agents and drugs such as, for example, fibrin, thrombin, and / or oxidized regenerated cellulose (ORC), anti-inflammatory drugs such as, for example, diclofenac, aspirin, naproxen, sulindac, and / or hydrocortisone, antibiotic and antimicrobial drugs or agents such as, for example, triclosan, ionic silver, ampicillin, gentamicin, polymyxin B, and / or chloramphenicol, anticancer agents such as, for example, cisplatin, mitomycin, and / or adriamycin, and / or biologics such as, for example, stem cells.

[0941] Referring again to **FIGS. 413, 417** and **418,** fasteners such as staples 30030, for example, can be deployed from a staple cartridge 30000 such that the staples 30030 engage a tissue thickness compensator 30020 and apply a force A to a tubular element 32080 therein. As described herein, application of a force A to the tubular element 30080 can cause deformation of the tubular element 30080. Similar to the end effectors 12 described herein, the rigid support portion 30010 of the staple cartridge 30000 can comprise a cartridge body 30017, a deck surface 30011, and a plurality of staple cavities 30012 therein. Each staple cavity 30012 can define an opening in the deck surface 30011 and a staple 30030 can be removably positioned in a staple cavity 30012 (**FIG. 433**). Referring primarily to **FIGS. 417** and **418**, each staple 30030 can comprise a base 30031 and two staple legs 30032 extending from the base 30031. Prior to the deployment of the staples 30030, the base 30031 of each staple 30030 can be supported by a staple driver 30040 (**FIG. 433**) positioned within the rigid support portion 30010 of the staple cartridge 30000. Also prior to the deployment of the staples 30030, the legs 30032 of each staple 30030 can be at least partially contained within the staple cavity 30012 (**FIG. 433**).

[0942] As described in greater detail herein, the staples 30030 can be deployed between an initial position and a fired position. For example, a staple-firing sled 30050 can engage a driver 30040 (**FIG. 433**) to move at least one staple 30030 between the initial position and the fired position. Referring primarily to **FIG. 417**, the staple 30030 can be moved to a fired position, wherein the legs 30032 of the staple 30030 engage a tubular element 32080 of a tissue thickness compensator 32020, penetrate tissue T, and contact an anvil 30060 (**FIG. 433**) positioned opposite the staple cartridge 30000 in the surgical end effector 12. Staple forming pockets 30062 in the anvil 30060 can bend the staple legs 30032 such that the fired staple 30030 captures a portion of the tubular element 32080 and a portion of the tissue T in a staple entrapment area 30039. As described in greater detail herein, at least one staple leg 30032 can pierce the tubular element 32080 of the tissue thickness compensator 32020 when the staple 30030 moves between the initial position and the fired position. Alternatively, the staple legs 30032 can move around the perimeter of the tubular element 32080 such that the staple legs 30032 avoid piercing the tubular element 32080. Similar to the fasteners described herein, the legs 30032 of each staple 30030 can be deformed downwardly toward the base 30031 of the staple 30030 to form a staple entrapment area 30039 therebetween. The staple entrapment area 30039 can be the area in which tissue T and a portion of the tissue thickness compensator 32020 can be captured by a fired staple 30030. In the fired position, each staple 30030 can apply a compressive force to the tissue T and to the tissue thickness compensator 32020 captured within the staple entrapment area 30039 of the staple 30030.

[0943] Referring still to **FIG. 417**, when the tubular element 32080 is captured in a staple entrapment area 30039, the captured portion of the tubular element 32080 can be deformed, as described herein. Furthermore, the tubular element 32080 can be deformed to different deformed configurations in different staple entrapment areas 30039 depending on, for example, the thickness, compressibility, and / or density of the tissue T captured in that same staple entrapment area 30039. The tubular element 32080 in the tissue thickness compensator 32080 can extend longitudinally through successive staple entrapment areas 30039. In such an arrangement, the tubular element 32080 can be deformed to different deformed configurations in each staple entrapment area 30039 along a row of fired staples 30030. Referring now to **FIG. 418**, tubular elements 33080 in a tissue thickness compensator 33020 can be laterally arranged in the staple entrapment areas 30039 along a row of fired staples 30030. The tubular elements

33080 can be retained by a flexible shell 33210. In such arrangements, the tubular elements 33080 and flexible shell 33210 can be deformed to different deformed configurations in each staple entrapment area 30039. For example, where the tissue T is thinner, the tubular elements 33080 can be compressed less and where the tissue T is thicker, the tubular elements 33080 can be compressed more to accommodate the thicker tissue T. Alternatively, the deformed dimensions of the tubular elements 33080 can be uniform throughout the entire length and / or width of the tissue thickness compensator 33020.

[0944] Referring to **FIGS. 419-421**, a tubular element 34080 in a tissue thickness compensator 34020 can comprise a plurality of strands 34090. Referring primarily to **FIG. 419**, the strands 34090 can be woven or braided into a tubular lattice 34092 forming the tubular element 34080. The tubular lattice 34092 formed by the strands 34090 can be substantially hollow. The strands 34090 of the tubular element 34080 can be solid strands, tubular strands, and / or another other suitable shape. For example, referring to **FIG. 420**, a single strand 34090 of the tubular lattice 34092 can be a tube. Referring to **FIG. 422**, a strand 34090 can comprise at least one lumen 34094 extending therethrough. The number, geometry and / or dimensions(s) of the lumens 34094 can determine the cross-sectional shape of the strand 34090. For example, a strand 34090 can comprise circular lumen(s), semi-circular lumen(s), wedge-shaped lumen(s), and / or combinations thereof. A strand 34090 can also comprise support webs 34096 that can form a modified "T" or "X" shape, for example. At least the diameter of the strand 34090, the lumen(s) extending therethrough, and the support web(s) can characterize the cross-sectional shape of a strand 34090. The cross-sectional shape of each strand 34090, as discussed in greater detail herein, can affect the springback or restoring force generated by the strand 34090 and the corresponding springback or restoring force generated by the tubular element 34080.

[0945] Referring to **FIG. 423**, a tubular lattice 34092 of strands 34090 can be deformable. The tubular lattice 34092 can produce or contribute to the deformability and / or the resiliency of the tubular element 34080. For example, the strands 34090 of the tubular lattice 34092 can be woven together such that the strands 34090 are configured to slide and / or bend relative to each other. When a force is applied to the elongate portion 34082 of the tubular element 34080, the strands 34090 therein may slide and / or bend such that the tubular lattice 34092 moves to a deformed configuration. For example, referring still to **FIG. 423**, a staple 30030 can compress the tubular lattice 34092 and the tissue T captured in a staple entrapment area 34039 which can cause the

strands 34090 of the tubular lattice 34092 to slide and / or bend relative to each other. A top apex 34086 of the tubular lattice 34092 can move towards a bottom apex 34088 of the tubular lattice 34092 when the tubular lattice 34092 is compressed to the deformed configuration in order to accommodate the captured tissue T in a staple entrapment area 30039. In various circumstances, the tubular lattice 34092 captured in a fired stapled 30030 will seek to regain its undeformed configuration and can apply a restoring force to the captured tissue T. Further, the portions of the tubular lattice 34092 positioned between staple entrapment areas 30039, i.e., not captured within a fired staple 30030, can also be deformed due to the deformation of adjacent portions of the tubular lattice 34092 that are within the staple entrapment areas 30039. Where the tubular lattice 34092 is deformed, the tubular lattice 34092 can seek to rebound or partially rebound from the deformed configuration. Portions of the tubular lattice 34092 can rebound to their initial configurations and other portions of the tubular lattice 34092 can only partially rebound and / or remain fully compressed.

[0946] Similar to the description of the tubular elements herein, each strand 34090 can also be deformable. Further, deformation of a strand 34090 can generate a restoring force that depends on the resiliency of each strand 34090. Referring primarily to **FIGS. 420** and **421**, each strand 34090 of a tubular lattice 34092 can be tubular. Alternatively, each strand 34090 of a tubular lattice 34092 can be solid. In a further alternative, the tubular lattice 30092 can comprise at least one tubular strand 34090, at least one solid strand 34090, at least one “X”- or “T”-shaped strand 34090, and / or a combination thereof.

[0947] The strands 34090 in the tubular element 34080 can comprise a polymeric composition. The polymeric composition of a strand 34090 can comprise non-absorbable polymers, absorbable polymers, or combinations thereof. Examples of synthetic polymers include, but are not limited to, polyglycolic acid (PGA), poly(lactic acid) (PLA), polycaprolactone (PCL), polydioxanone (PDO), and copolymers thereof. The absorbable polymers can include bioabsorbable, biocompatible elastomeric polymers, for example. Furthermore, the polymeric composition of the strand 34090 can comprise synthetic polymers, non-synthetic polymers, and / or combinations thereof. The polymeric composition of the strand 34090 can include varied amounts of absorbable polymers, non-absorbable polymers, synthetic polymers, and / or non-synthetic polymers, for example, by weight percentage.

[0948] The strands 34090 in the tubular element 34080 can further comprise a therapeutic agent 34098 (**FIG. 420**) such as a pharmaceutically active agent or medicament, for example. The strand 34090 can release a therapeutically effective amount of the therapeutic agent 34098. The therapeutic agent 34098 can be released as the tubular strand 34090 is absorbed. For example, the therapeutic agent 30098 can be released into fluid, such as blood for example, passing over or through the strand 34090. In a further alternative, the therapeutic agent 34098 can be released when a staple 30030 pierces the strand 34090 and/or when the cutting element 30052 on the staple-firing sled 30050 (**FIG. 413**) cuts a portion of the tubular lattice 34092, for example. Examples of therapeutic agents 34098 can include, but are not limited to, haemostatic agents and drugs such as, for example, fibrin, thrombin, and / or oxidized regenerated cellulose (ORC), anti-inflammatory drugs such as, for example, diclofenac, aspirin, naproxen, sulindac, and / or hydrocortisone, antibiotic and antimicrobial drugs or agents such as, for example, triclosan, ionic silver, ampicillin, gentamicin, polymyxin B, and / or chloramphenicol, anticancer agents such as, for example, cisplatin, mitomycin, and / or adriamycin; and / or biologics such as, for example, stem cells.

[0949] Referring to **FIGS. 424** and **425**, a tubular element 35080 can comprise multiple layers 35100 of strands 35090. The tubular element 35080 can comprise multiple layers 35100 of tubular lattices 35092. Referring to **FIG. 424**, the tubular element 35080 can comprise a first layer 35100a and a second layer 35100b of strands 35090, for example. Referring now to **FIG. 425**, a tubular element 35180 of a tissue thickness compensator 35120 can comprise a third layer 35100c of strands 35090, for example. Furthermore, different layers 35100 in the tubular element 35180 can comprise different materials. Each layer 35100a, 35100b, 35100c can be bioabsorbable, wherein, each layer 35100a, 35100b, 35100c can comprise a different polymeric composition. For example, the first layer 35100a can comprise a first polymeric composition; the second layer 35100b can comprise a second polymeric composition; and the third layer 35100c can comprise a third polymeric composition. In such cases, layers 35100a, 35100b, 35100c of the tubular element 35180 can be bioabsorbed at different rates. For example, the first layer 35100a can absorb quickly, the second layer 35100b can absorb slower than the first layer 35100a, and the third layer 35100c can absorb slower than the first layer 35100a and / or the second layer 35100b. Alternatively, the first layer 35100a can absorb slowly, the second layer 35100b can

absorb faster than the first layer 35100a, and the third layer 35100c can absorb faster than the first layer 35100a and / or the second layer 35100b.

[0950] Similar to strands 34090 described herein, the strands 35090 in the tubular element 35180 can comprise a medicament 35098. Referring again to **FIG. 424**, to control elusion or release of the medicament(s) 35098, the first layer 35100a of strands 35090 comprising a medicament 35098a can be bioabsorbed at a first rate and the second layer 35100b of strands 35090 comprising a medicament 30098b can be bioabsorbed at a second rate. For example, the first layer 35100a can absorb quickly to allow for a rapid initial release of the medicament 35098a and the second layer 35100b can absorb slower to allow controlled release of the medicament 30098b. The medicament 35098a in the strands 35090 of the first layer 30100a can be different than the medicament 35098b in the strands 35090 of the second layer 35100b. For example, the strands 35090 in the first layer 35100a can comprise oxidized regenerated cellulose (ORC) and the strands 35090 in the second layer 35100b can comprise a solution comprising hyaluronic acid. In such cases, initial absorption of the first layer 35100a can release oxidized regenerated cellulose to help control bleeding while subsequent absorption of the second layer 35100b can release a solution comprising hyaluronic acid to can help prevent the adhesion of tissue. Alternatively, the layers 35100a, 35100b can comprise the same medicament 35098a, 35098b. For example, referring again to **FIG. 425**, strands 35090 in layers 35100a, 35100b and 35100c can comprise an anticancer agent, such as, for example, cisplatin. Furthermore, the first layer 35100a can absorb quickly to allow for a rapid initial release of cisplatin, the second layer 35100b can absorb slower to allow for a controlled release of cisplatin, and the third layer 35100c can absorb slowest to allow for a more extended, controlled release of cisplatin.

[0951] Referring to **FIGS. 426** and **427**, a tissue thickness compensator 36020 can comprise an overmold material 36024. The overmold material 36024 can be formed outside a tubular element 36080, inside a tubular element 36080, or both inside and outside a tubular element 36080. Referring to **FIG. 426**, the overmold material 36024 can be coextruded both inside and outside the tubular element 36080 and, the tubular element 36080 can comprise a tubular lattice 36092 of strands 36090. Similar to the polymeric composition described herein, the overmold material 36024 can comprise polyglycolic acid (PGA), poly(lactic acid) (PLA), and / or any other suitable, bioabsorbable and biocompatible elastomeric polymers, for example. Further, the overmold material 36024 can be non-porous such that the overmold material 36024 forms a

fluid-impervious layer in the tubular element 36080. The overmold material 36024 can define a lumen 36084 therethrough.

[0952] Further to the discussion above, the tubular element 36080 and / or the strands 36090 in a tubular lattice 36092 can comprise a therapeutic agent 36098. Referring still to **FIGS. 426** and **427**, a non-porous overmold material 36024 can contain the medicament 36098 within an inner lumen 36084a. Alternatively or additionally, the non-porous, overmold material 36024 can contain the medicament 36098 within an intermediate lumen 36084b, such as, for example, the intermediate lumen 36084b that contains the tubular lattice 36092 of medicament-comprising strands 36090. Similar to the above, the tubular element 36080 can be positioned relative to staple cavities 30012 and a cutting element 30052 in staple cartridge 30000 (**FIG. 413**). For example, the deployment of the staples 30030 and / or the translation of the cutting element 30052 can be configured to pierce or rupture the non-porous, overmold material 36024 such that the medicament 36098 contained in at least one lumen 36084 of the tubular element 30080 can be released from the lumen 30084. Referring to **FIG. 428**, a tubular element 37080 can comprise a non-porous film 37110. The non-porous film 37110 can at least partially surround a tubular lattice 37092 or a first layer 37100a and a second layer 37100b of tubular lattices 30092 to provide a fluid-impervious cover similar to the overmold material 36024 described herein.

[0953] As described herein, a tubular element can comprise at least one of a bioabsorbable material, a therapeutic agent, a plurality of strands, a tubular lattice, layers of tubular lattices, an overmold material, a non-porous film, or combinations thereof. For example, referring to **FIG. FIG. 429**, a tubular element 38080 can comprise an overmold material 38024 and a plurality of strands 38090 positioned through a central lumen 38084 of the tubular element 38080. The strands 38090 can comprise a therapeutic agent 38098. Alternatively, for example, referring to **FIG. 430**, a tubular element 39080 can comprise an overmold material 39024 and a therapeutic agent 39098 positioned in a central lumen 39084 of the tubular element 39080, for example. At least one of the tubular element 39080 and overmold material 39024 can comprise a fluidic therapeutic agent 39098.

[0954] Referring again primarily **FIG. 413,** the tubular element 30080 can be positioned relative to the rigid support portion 30010 of the staple cartridge 30000. The tubular element 30080 can be longitudinally positioned adjacent to the rigid support portion 30010. The tubular element 30080 can be substantially parallel to or aligned with a longitudinal slot or cavity 30015 in the

rigid support portion 30010. The tubular element 30080 can be aligned with the longitudinal slot 30015 such that a portion of the tubular element 30080 overlaps a portion of the longitudinal slot 30015. In such cases, a cutting element 30052 on the staple-firing sled 30050 can sever a portion of the tubular element 30080 as the cutting edge 30052 translates along the longitudinal slot 30015. Alternatively, the tubular element 30080 can be longitudinally positioned on a first or second side of the longitudinal slot 30015. In a further alternative, the tubular element 30080 can be positioned relative to the rigid support portion 30010 of the staple cartridge 30000 such that the tubular element 30080 laterally or diagonally traverses at least a portion of the rigid support portion 30010.

[0955] Referring to **FIG. 431** for example, a tissue thickness compensator 40020 can comprise multiple tubular elements 40080. The tubular elements 40080 can comprise different lengths, cross-sectional shapes, and / or materials, for example. Further, the tubular elements 40080 can be positioned relative to the rigid support portion 40010 of the staple cartridge 30000 such that the tubular axes of the tubular elements 40080 are parallel to each other. The tubular axes of tubular elements 40080 can be longitudinally aligned such that a first tubular element 40080 is positioned within another tubular element 40080. Alternatively, parallel tubular elements 40080 can longitudinally traverse the staple cartridge 30000, for example. In a further alternative, parallel tubular elements 40080 can laterally or diagonally traverse the staple cartridge 30000. Alternatively, non-parallel tubular elements 40080 can be angularly-oriented relative to each other such that their tubular axes intersect and / or are not parallel to each other.

[0956] Referring to **FIGS. 431-434**, a tissue thickness compensator 40020 can have two tubular elements 40080; a first tubular element 40080a can be longitudinally positioned on a first side of the longitudinal slot 30015 in the rigid support portion 30010 and a second tubular element 40080b can be longitudinally positioned on a second side of the longitudinal slot 30015. Each tubular element 40080 can comprise a tubular lattice 40092 of strands 40090. The staple cartridge 30000 can comprise a total of six rows of staple cavities 30012, wherein three rows of staple cavities 30012 are positioned on each side of the longitudinal slot 30015, for example. In such cases, the cutting edge 30052 on the translating staple-firing sled 30050 may not be required to sever a portion of the tubular element 40080.

[0957] Similarly, referring now to **FIGS. 435-436**, a tissue thickness compensator 41020 can comprise two tubular elements 41080a, 41080b longitudinally arranged in the staple cartridge

30000. Similar to the above, staples 30030 from three rows of staple cavities 30012 can engage one tubular element 41080a and staples 30030 from three different rows of staple cavities 30012 can engage another tubular element 41080b. Referring still to **FIGS. 435-436**, deployed staples 30030 can engage the tubular element 40080 at different locations across the cross-section of the tubular element 40080. As discussed herein, the springback resiliency and corresponding restoring force exerted by the tubular element 41080 can depend on the cross-sectional shape of the tubular element 41080, among other things. A staple 30030 positioned in a staple entrapment area 30039 located at or near an arced portion of the tubular element 41080 can experience a greater restoring force than a staple 30030 in a staple entrapment area 30039 positioned near a non-arced portion. Similarly, a staple 30030 positioned in staple entrapment area 30039 in the non-arced portion of the tubular element 41080 can experience a lesser restoring force than the restoring force experienced by a staple 30030 positioned at or nearer to the arced portion of the tubular element 30080. In other words, the arced portions of a tubular element 41080 can have a greater spring rate than the non-arced portion of the tubular element 41080 owing to the possibility that a larger quantity of elastic material may be captured by the staples 30030 along such portions. As a result, referring primarily to **FIG. 436**, the restoring force generated by the tissue thickness compensator 41020 can be greater near staples 30030a and 30030c and less near staple 30030b in tubular element 30080a. Correspondingly, the restoring force generated by the tissue thickness compensator 41020 can be greater near staples 30030d and 30030f than near staple 30030e in tubular element 30080b.

[0958] Referring again to **FIGS. 431-434**, the cross-sectional geometries of strands 40090 comprising the tubular lattice 40092 can be selected in order to provide a desired springback resiliency and corresponding restoring force exerted by the tubular lattice 40092. For example, referring again to **FIG. 432**, strands 40090a positioned in arced portions of the tubular element 40080 can comprise X-shaped cross-sections, whereas strands 40090b positioned in non-arced portions of the tubular element 40080 can comprise tubular cross-sections. Strands 40090a and 40090b comprising different cross-sectional geometries can be woven together to form the tubular lattice 40092. Alternatively, the strands 40090a and 40090b can be attached to one another with an adhesive, for example. Referring to **FIGS. 433** and **434**, the different cross-sectional geometries of strands 40090 in the tubular element 40080 can optimize the restoring force experienced in staple entrapment areas 30039 across the staple cartridge 30000. Specific

cross-sectional geometries can be selected such that the springback constant in staple entrapment areas 30039 across the staple cartridge is substantially balanced or equal.

[0959] Referring to **FIG. 437**, the tubular elements 41080a, 41080b of a tissue thickness compensator 41120 can be fastened together by an adjoining portion 41126. Though the translating cutting element 30052 can be configured to pass between tubular elements 41080a and 41080b, the cutting element 30052 can be required to sever at least a portion of the adjoining portion 41126. The adjoining portion 41126 can comprise a soft material, such as, for example, a foam or gel, which is easily severed by the translating cutting element 30052. The adjoining portion 41026 can releasably secure the tissue thickness compensator 41120 to the surgical end effector 12. The adjoining portion 41126 can be fixed to the top deck surface 30011 of the rigid support portion 30010 such that the adjoining portion 41126 remains retained in the surgical end effector 12 after the tubular elements 41080a, 41080b are released therefrom.

[0960] Referring to **FIGS. 438-439,** a tissue thickness compensator 42020 can comprise multiple tubular elements 42080 such that the number of tubular elements 42080 is the same as the number of rows of staple cavities 30012 in the staple cartridge 30000, for example. The staple cartridge 30000 can comprise six rows of staple cavities 30012 and the tissue thickness compensator 42020 can comprise six tubular elements 42080. Each tubular element 42080 can be substantially aligned with a row of staple cavities 30012. When staples 30030 are ejected from a row of staple cavities 30012, each staple 30030 from that row can pierce the same tubular element 42080 (**FIG. 439**). The deformation of one tube 42080 can have little or no impact on the deformation of an adjacent tube 42080. Accordingly, the tubular elements 42080 can exert a substantially discrete and customized springback force in staple entrapment areas 30039 across the width of the staple cartridge 30030. Where staples 30030 fired from multiple rows of staple cavities 30012 engage the same tubular element 35080 (**FIG. 436**), the deformation of the tubular element 35080 can be less customized. For example, the deformation of a tubular element 35080 in a staple entrapment area 30039 in a first row can impact the deformation of that tubular element 35080 in staple entrapment area 30039 in another row. The translating cutting edge 30052 can avoid severing the tubular elements 42080. Alternatively, referring to **FIG. 440**, a tissue thickness compensator 43020 can comprise more than six tubular elements 43080, such as, for example, seven tubular elements 44080. Further, the tubular elements 43080 can be symmetrically or non-symmetrically arranged in the end effector 12. When an odd

number of tubular elements 43080 are longitudinally and symmetrically arranged in the end effector 12, the translating cutting element 30052 can be configured to sever the middle tubular element that overlies the longitudinal channel 30015.

[0961] Referring to **FIG. 441**, a tissue thickness compensator 44020 can comprise a central tubular element 44080b that is at least partially aligned with the longitudinal slot 30015 in the rigid support portion 33010 of the staple cartridge 30000. The tissue thickness compensator 44020 can further comprise at least one peripheral tubular element 44080a, 44080c located on a side of the longitudinal slot 30015. For example, the tissue thickness compensator 44020 can comprise three tubular elements 44080: a first peripheral tubular element 44080a can be longitudinally positioned on a first side of the longitudinal slot 30015 of the staple cartridge 30000, a central tubular element 44080b can be substantially positioned over and / or aligned with the longitudinal slot 30015, and a second peripheral tubular element 44080c can be longitudinally positioned on a second side of the longitudinal slot 30015. The central tubular element 44080b can comprise a horizontal diameter that is substantially elongated relative to the vertical diameter. The central tubular element 44080b, and / or any other tubular element, can overlap multiples rows of staple cavities 30012. Referring still to **FIG. 441**, the central tubular element 44080b can overlap four staple rows of staple cavities 30012 and each peripheral tubular element 44080a, 44080c can overlap a single row of staple cavities 30012, for example. Alternatively, the central tubular element 44080b can overlap less than four rows of staple cavities 30012, such as, for example, two rows of staple cavities 30012, for example. Further, peripheral tubular elements 44080a, 44080c can overlap more than one row of staple cavities 30012, such as, for example, two rows of staple cavities 30012. Referring now to **FIG. 442**, a central tubular element 44180b of a tissue thickness compensator 44120 can comprise a therapeutic agent 44198 in a lumen 44184 of the central tubular element 44180b. Central tubular element 44180b and / or at least one peripheral tubular element 44080a, 44080c can comprise the therapeutic agent 44198 and / or any other suitable therapeutic agent.

[0962] Referring to **FIG. 443**, the tissue thickness compensator 44220 can comprise a shell 44224, which can be similar to overmold material 32024 described herein. The shell 44224 retains multiple tubular elements 44080 in position in the end effector 12. The shell 44224 can be coextruded with the tubular elements 44080. The tubular elements 44080 can comprise a tubular lattice 44092 of strands 44090. Similar to the polymeric compositions described herein, the shell

44224 can comprise polyglycolic acid (PGA), poly(lactic acid) (PLA), and / or any other suitable bioabsorbable, biocompatible elastomeric polymers, for example. Further, the shell 44224 can be non-porous such that the shell 44224 forms a fluid-impervious layer in the tissue thickness compensator 44220, for example. Further to the discussion herein, the tubular element 44080 and / or the strands 44090 in the tubular lattice 44092 can comprise a therapeutic agent 44098. The non-porous shell 44224 can contain the therapeutic agent 44098 within the tissue thickness compensator. As described herein, the tubular element 44080 can be positioned relative to staple cavities 30012 and a cutting element 30052 in staple cartridge 30000. For example, deployment of the staples 30030 and / or translation of the cutting element 30052 can be configured to pierce or rupture the non-porous, shell 44224 such that the therapeutic agent 44198 contained therein can be released from the tissue thickness compensator 44020.

[0963] Referring to **FIG. 444**, a tissue thickness compensator 44320 can comprise a central tubular element 44380b comprising a tubular lattice 44392. The tubular lattice 44392 can have a non-woven portion or a gap 44381 that is substantially aligned with the longitudinal slot 30015 of the rigid support portion 30010. In such cases, a woven portion of the tubular lattice 44092 of the tubular element 44380b does not overlap the longitudinal slot 30015. Accordingly, the cutting element 30052 on the translating staple-fire sled 30052 can translate along the longitudinal slot 30015 without severing an overlapping a woven portion of the tubular lattice 44392. Though staples 30030c and 30030d positioned adjacent to the gap 44381 in tubular element 44380b may receive less support from the tubular lattice 44392 structure, additional features can provide support for those staples 30030 and / or additional restoring force in the staple entrapment areas 30039 thereof. For example, as described in greater detail herein, additional tubular elements, support webbing, springs and / or buttressing material can be positioned at least one of inside and outside tubular element 44380b near gap 44381, for example.

[0964] Referring now to **FIGS. 445-448**, a tissue thickness compensator 45020 can comprise multiple tubular elements 45080 that laterally traverse the staple cartridge 30000. The tubular elements 45080 can be positioned perpendicular to the rows of staple cavities 30012 and / or the longitudinal axis of the rigid support portion 30010 of the staple cartridge 30000. Referring to **FIG. 445**, the tubular elements 45080 can traverse the longitudinal slot 30015 in the staple cartridge 30000 such that the cutting element 30052 on the staple-firing sled 30050 is configured

to sever the tubular elements 45080 as the staple-firing sled 30050 translates along the longitudinal slot 30015. Alternatively, referring now to **FIG. 446**, the tissue thickness compensator 46020 can comprise two sets of laterally traversing tubular elements 46080. The first set of laterally traversing tubular elements 46080a can be positioned on a first side of the longitudinal slot 30015 and the second set of laterally traversing tubular elements 46080b can be positioned on a second side of the longitudinal slot 30015. In such an arrangement, the cutting element 30052 can be configured to pass between the two sets of tubular elements 46080 without severing a portion of the tubular elements 46080. Alternatively, the cutting element 30052 can sever at least one tubular element 46080 that traverses the longitudinal slot 30015 while at least one other tubular element 46080 does not traverse the longitudinal slot 30015 and is not severed by the cutting element 30052.

[0965] As the tubular elements 45080 laterally traverse the staple cartridge 30000, referring to **FIGS. 447** and **448,** a staple 30030 can engage at least one tubular element 45080 in each staple entrapment area 30039. In such an arrangement, each tubular element 45080 can provide a discrete restoring force along the length of the staple cartridge 30000. For example, referring primarily to **FIG. 448**, the tubular elements 45080 positioned near the proximal end of the tissue thickness compensator 45020 where the tissue is thicker can be greatly compressed compared to the tubular elements 45080 positioned near to the distal end of the tissue thickness compensator 45020 where the tissue is thinner. As a result, the tubular elements 45080 positioned closer to the proximal end of the tissue thickness compensator 45020 can provide a greater restoring force than the restoring force that could be generated by the tubular elements 46080 positioned closer to the distal end of the tissue thickness compensator 45020. Further, referring still to **FIG. 448**, the deformation of one tube 45080 can have little or no impact on the deformation of an adjacent tube 45080. Accordingly, the tubular elements 45080 can exert a substantially discrete and customized springback force in staple entrapment areas 30039 along the length of the staple cartridge 30030. Where multiple staples 30030 fired from a single row of staple cavities 30012 engage the same tubular element 35080, the deformation of the tubular element 35080 can be less customized. For example, the deformation of a tubular element 35080 in one staple entrapment area 30039 can impact the deformation of that tubular element 35080 in another staple entrapment area 30039.

[0966] In a further alternative, referring to **FIGS. 449-454**, tubular elements 47080 of the tissue thickness compensator 47020 can diagonally traverse the staple cartridge 30000. The tubular elements 47080 can traverse the longitudinal slot 30015 of the staple cartridge 30000 such that the cutting element 30052 on the staple-firing sled 30050 is configured to sever the diagonally traversing tubular elements 47080 as the staple-firing sled 30052 translates along the longitudinal slot 30015. Alternatively, the tissue thickness compensator 47020 can comprise two sets of diagonally traversing tubular elements 47080. A first set of diagonally traversing tubular elements 47080 can be positioned on a first side of the longitudinal slot 30015 and a second set of diagonally traversing tubular elements 47080 can be positioned on a second side of the longitudinal slot 30015. In such an arrangement, the cutting element 30052 can pass between the two sets of tubular elements 47080 and may not sever any tubular element 47080.

[0967] Referring still to **FIGS. 449-452**, the diagonally traversing tubular elements 47080 can be positioned in the staple cartridge 30000 such that a gap is defined between the tubular elements 47080. A gap between adjacent tubular elements 47080 can provide space for horizontal expansion of the tubular elements 47080 when a compressive force is applied thereto, such as, for example, by tissue T captured within the staple entrapment area 30039 of the formed staple 30030. The tubular elements 47080 can be connected across a gap by a film or sheet of material 47024. The sheet of material can be positioned on at least one of the deck surface 30011 of the rigid support portion 30010 and / or the tissue contacting side of the tubular elements 47080.

[0968] Referring to **FIGS. 453** and **454**, at least one diagonally traversing tubular element 47080 can be positioned relative to the staple cavities 30012 in the staple cartridge 30000 such that the tubular element 47080 is positioned between the legs 30032 of the staples 30030 deployed from multiple rows of staple cavities 30012. As the staples 30030 are moved from the initial position to the fired position, as described in greater detail herein, the staple legs 30032 can remain positioned around the tubular element 47080. Further, the staples can be deformed such that the staple legs 30032 wrap around the perimeter of the tubular element 47080, for example. In such an arrangement, the staples 30030 can be configured to move to the fired or formed position without piercing the tubular element 47080. Movement of the staple legs 30032 around the tubular element 47080 could, in some cases, prevent the inadvertent release of a therapeutic agent 47098 retained therein. The selected angular orientation of each tubular element 47080 relative to the longitudinal slot 30015 of the staple cartridge 30000 can depend on the position of

the staple cavities 30012 in the staple cartridge 30000. For example, the tubular elements 47080 can be positioned at an approximately forty-five (45) degree angle relative to the longitudinal slot 30015 of the staple cartridge 30000. Alternatively, the tubular elements 47080 can be positioned at a fifteen (15) to seventy-five (75) degree angle relative to the longitudinal slot 30015 of the staple cartridge 30000, for example.

[0969] Similar to descriptions throughout the present disclosure, multiple tubular elements in a tissue thickness compensator can be connected by a binding agent, wrap, webbing, overmold, compensation material, and/or any other suitable connecting adhesive or structure, for example. Referring to **FIGS. 455-457**, a flexible shell 48024 may surround or encapsulate tubular elements 48080 in a tissue thickness compensator 48020. The flexible shell 48024 can restrain the tubular elements 48080 in the end effector 12 and can hold each tubular element 48080 in position, such as, for example, in longitudinal alignment with a row of staple cavities 30012. The tissue thickness compensator 48020 can comprise six tubular elements 48080, for example. The flexible shell 48024 can be sufficiently deformable and resilient to restrain the tubular elements 48020 encased therein while permitting deformation and rebound of the tubular elements 48080. Further, the flexible shell 48024 can tautly surround the tubular elements 48080 and can remain tautly engaged with the tubular elements 48080 as they deform and / or rebound.

[0970] Referring to **FIG. 456**, prior to the deployment of staples 30030, the anvil 30060 can be pivoted or rotated downwardly to compress the tissue thickness compensator 48020 and tissue T between the anvil 30060 and the staple cartridge 30000. Compression of the tissue thickness compensator 48020 can include a corresponding compression of the flexible shell 48024 and the tubular elements 48020 therein. As the tubular elements 48020 deform, the flexible shell 48024 can similarly deform. The tubular elements 48020 can be uniformly compressed across the width of the staple cartridge 30000 and the flexible shell 48024 can experience a similarly uniform compression across the tubular elements 48080. Referring to **FIG. 457**, when the anvil 30060 is opened after the staples 30030 have been deployed from the staple cartridge 30000, the tubular elements 48080 can rebound or partially rebound from the compressed configurations (**FIG. 456**). A tubular element 48080 can rebound such that the tubular element 48080 returns to its initial, undeformed configuration. A tubular element 48080 can partially rebound such that the tubular element 48080 partially returns to its initial undeformed configuration. For example, the deformation of the tubular element 48080 can be partially elastic and partially plastic. As the

tubular elements 48080 rebound, the flexible shell 48024 can remain tautly engaged with each tubular element 48080. The tubular elements 48080 and flexible shell 48024 can rebound to such a degree that the tubular elements 48080 and tissue T fill the staple entrapment areas 30039 while the tubular elements 48080 exert an appropriate restoring force on the tissue T therein. Referring to **FIG. 458**, as an alternative, a tissue thickness compensator 48120 comprising six tubular elements 48180 retained in a flexible shell 48124 can be positioned on the anvil 30060 of the end effector 12, for example.

[0971] Referring to **FIGS. 459-462**, a tissue thickness compensator 49020 can comprise a tubular element 49080 longitudinally positioned along the longitudinal axis of the anvil 30060. The tissue thickness compensator 49020 can be secured to the anvil 30060 of the end effector 12 by a compressible compensation material 49024. Further, the compressible compensation material 49024 can surround or encapsulate the tubular element 49080. Similar to the descriptions herein, the tubular element 49080 can comprise at least one therapeutic agent 49098 which may be released by the absorption of various components of the tissue thickness compensator 49020, the piercing of the tubular element 49080 by staples 30030 fired from the staple cartridge 30000, and / or by the cutting element 30052.

[0972] Referring to **FIG. 460**, a staple cartridge 30000 can comprise staples 30030 positioned in staple cavities 30012, wherein, prior to deployment of the staples 30030, the anvil 30060 and the tissue thickness compensator 49020 attached thereto can pivot toward the staple cartridge 30000 and compress tissue T captured therebetween. The tubular element 49080 of the tissue thickness compensator 49020 can be uniformly deformed along the length of the staple cartridge 30000 by the pivoting anvil 30060 (**FIG. 460**). Referring to **FIGS. 461** and **462**, the staple-firing sled 30050 can translate along the longitudinal slot 30015 in the staple cartridge 30000 and engage each driver 30040 positioned beneath a staple 30030 in a staple cavity 30010, wherein each engaged driver 30040 can fire or eject the staple 30030 from the staple cavity 30012. When the anvil 30060 releases pressure on the tissue T and the tissue thickness compensator 49020, the tissue thickness compensator 49020, including the tubular element 49080 and the compressible compensation material 49024, can rebound or partially rebound from the compressed configurations (**FIG. 460**) to a rebounded configuration (**FIGS. 461** and **462**). The tubular element 49080 and compressible compensation material 49024 can rebound to such a degree that

the tissue thickness compensator 49020 and tissue T fill the staple entrapment areas 30039 while the tissue thickness compensator 49020 exert an a restoring force on the captured tissue T.

[0973] Referring to **FIGS. 463-465**, two tissue thickness compensators 50020a, 50020b can be positioned in the end effector 12 of a surgical instrument. For example, a first tissue thickness compensator 50020a can be attached to the staple cartridge 30000 in the lower jaw 30070 and a second tissue thickness compensator 50020b can be attached to the anvil 30060. The first tissue thickness compensator 50020a can comprise a plurality of tubular elements 50080 longitudinally arranged and retained in a first compensation material 50024a. At least one tubular element 50080 can comprise a therapeutic agent 50098, similar to the therapeutic agents described herein. The first compensation material 50024a can be deformable or substantially rigid. Further, the first compensation material 50024a can hold the tubular elements 50080 in position relative to the staple channel 30000. For example, the first compensation material 50024a can hold each tubular element 50080 in longitudinal alignment with a row of staple cavities 30012. The second tissue thickness compensator 50020b can comprise the first compensation material 50024a, a second compensation material 50024b and / or a third compensation material 50024c. The second and third compensation material 50024b, 50024c can be deformable or substantially rigid.

[0974] The anvil 30060 can pivot and apply a compressive force to the tissue thickness compensators 50020a, 50020b and the tissue T between the anvil 30060 and the staple cartridge 30000. Neither the first tissue thickness compensators 50020a nor the second tissue thickness compensators 50020b need be compressible. Alternatively, at least one component of the first tissue thickness compensators 50020a and / or the second tissue thickness compensators 50020b can be compressible. When the staples 30030 are fired from the staple cartridge 30000, referring now to **FIGS. 464** and **465**, each staple 30030 can pierce a tubular element 50080 retained in the first tissue thickness compensator 50020a. As shown in **FIG. 464**, the therapeutic agent 50098 retained in the tubular element 50080 can be released when a staple 30030 pierces the tubular element 50080. When released, the therapeutic agent 50098 can coat the staple legs 30032 and tissue T surrounding the fired staple 30030. The staples 30030 can also pierce the second tissue thickness compensator 50020b when the staples 30030 are fired from the staple cartridge 30000.

[0975] Referring to **FIGS. 466-469**, a tissue thickness compensator 51020, representative of any of the tissue thickness compensators described herein, can comprise at least one tubular element

51080 that laterally traverses the tissue thickness compensator 51020. For example, referring to **FIG. 466**, the tissue thickness compensator 51020 can be positioned relative to the staple cartridge 30000 such that a first end 51083 of the laterally traversing tubular element 51080 can be positioned near a first longitudinal side of the staple cartridge 30000 and a second end 51085 of the laterally traversing tubular element 51080 can be positioned near a second longitudinal side of the staple cartridge 30000. The tubular element 51080 can comprise a capsule-like shape, for example. As illustrated in **FIG. 467**, the tubular element 51080 can be perforated between the first end 51083 and the second end 51085 and, the tubular element 51080 can be perforated at or near the center 51087 of the tubular element 51080. The tubular element 51080 can comprise a polymeric composition, such as a bioabsorbable, biocompatible elastomeric polymer, for example. Further, referring again to **FIG. 466**, the tissue thickness compensator 51020 can comprise a plurality of laterally traversing tubular elements 51080. Thirteen tubular elements 51080 can be laterally arranged in the tissue thickness compensator 51020, for example.

[0976] Referring again to **FIG. 466**, the tissue thickness compensator 51020 can further comprise a compensation material 51024 that at least partially surrounds the tubular elements 51080. The compensation material 51024 can comprise a bioabsorbable polymer, such as, for example, lyophilized polysaccharide, glycoprotein, elastin, proteoglycan, gelatin, collagen, and / or oxidized regenerated cellulose (ORC). The compensation material 51024 can hold the tubular elements 51080 in position in the tissue thickness compensator 51020. Further, the compensation material 51024 can be secured to the top deck surface 30011 of the rigid support portion 30010 of the staple cartridge 30000 such that the compensation material 51020 is securely positioned in the end effector 12. The compensation material 51024 can comprise at least one medicament 51098.

[0977] Still referring to FIG. 466, laterally positioned tubular elements 51080 can be positioned relative to the translating cutting element 30052 such that the cutting element 30052 is configured to sever the tubular elements 51080. The cutting element 30052 can sever the tubular elements 51080 at or near the perforation therein. When the tubular elements 51080 are severed in two halves, the severed portions of the tubular elements 51080 can be configured to swell or expand, as illustrated in FIG. 468. For example, the tubular element 51080 can comprise a hydrophilic substance 51099 that can be released and / or exposed when the tubular element 51080 is severed. Furthermore, when the hydrophilic substance 51099 contacts bodily fluids in

tissue T, the hydrophilic substance 51099 can attract the fluid, which can cause the tubular element 51080 to swell or expand. As the tubular element 51080 expands, the compensation material 51024 surrounding the tubular element 51080 can shift or adjust to accommodate the swollen tubular element 51080. For example, when the compensation material 51024 comprises gelatin, the gelatin can shift to accommodate the swollen tubular elements 51080. Referring now to FIG. 469, expansion of the tubular elements 51080 and shifting of the compensation material 51024 can cause a corresponding expansion of the tissue thickness compensator 51020.

[0978] Similar to other tissue thickness compensators discussed throughout the present disclosure, the tissue thickness compensator 51020 can be deformed or compressed by an applied force. Further, the tissue thickness compensator 51020 can be sufficiently resilient such that it produces a springback force when deformed by the applied force and can subsequently rebound or partially rebound when the applied force is removed. When the tissue thickness compensator 51020 is captured in a staple entrapment area 30039, the staple 30030 can deform the tissue thickness compensator 51020. For example, the staple 30030 can deform the tubular elements 51080 and / or the compensation material 51024 of the tissue thickness compensator 51020 that are captured within the fired staple 30030. Non-captured portions of the tissue thickness compensator 51020 can also be deformed due to the deformation in the staple entrapment areas 30039. When deformed, the tissue thickness compensator 51020 can seek to rebound from the deformed configuration. Such a rebound may occur prior to the hydrophilic expansion of the tubular element 51080, simultaneously with the hydrophilic expansion of the tubular element 51080, and / or after the hydrophilic expansion of the tubular element 51080. As the tissue thickness compensator 51020 seeks to rebound, it can exert a restoring force on the tissue also captured in the staple entrapment area 30039, as described in greater detail herein.

[0979] At least one of the tubular elements 51080 and / or the compensation material 51024 in the tissue thickness compensator 51020 can comprise a therapeutic agent 51098. When the tubular element 51080 that contains a therapeutic agent 51098 is severed, the therapeutic agent 51098 contained within the tubular elements 51080 can be released. Furthermore, when the compensation material 51024 comprises the therapeutic agent 51098, the therapeutic agent 51098 can be released as the bioabsorbable compensation material 51024 is absorbed. The tissue thickness compensator 51020 can provide for a rapid initial release of the therapeutic agent 51098 followed by a controlled release of the therapeutic agent 51098. For example, the tissue

thickness compensator 51020 can provide a rapid initial release of the therapeutic agent 51098 from the tubular elements 51080 to the tissue T along the cut line when the tubular elements 51080 comprising the therapeutic agent 51098 are severed. Further, as the bioabsorbable compensation material 51024 comprising the therapeutic agent 51098 is absorbed, the tissue thickness compensator 51020 can provide an extended, controlled release of the therapeutic agent 51098. At least some of the therapeutic agent 51098 can remain in the tubular element 51080 for a short period of time before the therapeutic agent 51098 flows into the compensation material 51024. Alternatively, at least some of the therapeutic agent 51098 can remain in the tubular element 51080 until the tubular element 51080 is absorbed. The therapeutic agent 51098 released from the tubular element 51080 and the compensation material 51024 can be the same. Alternatively, the tubular element 51080 and the compensation material 51024 can comprise different therapeutic agents or different combinations of therapeutic agents, for example.

[0980] Referring still to FIG. 469, the end effector 12 can cut tissue T and fire staples 30030 into the severed tissue T nearly simultaneously or in quick succession. In such cases, a staple 30030 can be deployed into the tissue T immediately after the cutting element 30052 has severed the tubular element 51080 adjacent to the tissue T. In other words, the staples 30030 can engage the tissue thickness compensator 51020 immediately following or simultaneously with the swelling of the tubular element 51080 and the expansion of the tissue thickness compensator 51020. The tissue thickness compensator 51020 can continue to grow or expand after the staples 30030 have been fired into the tissue T. The staples 30030 can be configured to puncture the tubular elements 51080 when the staples 30030 are deployed. In such cases, therapeutic agents 51098 still retained in the severed tubular elements 51080 can be released from the tubular elements 51080 and, can cover the legs 30031 of the fired staples 30030.

[0981] Referring to **FIG. 470**, the tissue thickness compensator 51020 can be manufactured by a molding technique, for example. A frame, or a mold, 51120 can comprise a first longitudinal side 51122 and a second longitudinal side 51124. Each longitudinal side 51124 can comprise one or more notches 51130, which can each be configured to receive the first or second end 50183, 50185 of a tubular element 51080. The first end 50183 of the tubular element 51080 can be positioned in a first notch 51130a on the first longitudinal side 51122 and the second end 50183 of the tubular element 51080 can be positioned in a second notch 51130b on the second longitudinal side 51124 such that the tubular element 51080 laterally traverses the frame 51120.

The notch 51180 can comprise a semi-circular groove, which can securely fit the first or second end 50183, 50185 of the tubular element 51080 therein. The first notch 51130a can be positioned directly across from the second notch 51130b and the tubular element 51080 can be positioned perpendicular, or at least substantially perpendicular, to the longitudinal axis of the frame 51120. Alternatively, the first notch 51130a can be offset from the second notch 51130b such that the tubular element 51080 is angularly positioned relative to the longitudinal axis of the frame 51120. In a further alternative, at least one tubular element 51080 can be longitudinally positioned within the frame 51120 such that the tubular element extends between the lateral sides 51126, 51128 of the frame 51120. Further, at least one tubular element can be angularly positioned in the frame between two notches on the lateral sides 51126, 51128 of the frame and / or between a notch on a lateral side 51126 and a notch on a longitudinal side 51124, for example. The frame 51120 can comprise a support ledge 51136, which can support the tubular elements 51080 positioned within the frame 51120.

[0982] The frame 51120 can comprise notches 51130 to accommodate twelve tubular elements 51080, for example. The frame notches 51130 can be filled with tubular elements 51080 while, as an alternative, less than all of the notches 51130 may be filled. At least one tubular element 51080 can be positioned in the frame 51120. As an example, at least half the notches 51130 can receive tubular elements 51080. Once the tubular elements 51080 are positioned in the frame 51120, compensation material 51024 can be added to the frame 51120. The compensation material 51024 can be fluidic when added to the frame 51120. For example, the compensation material 51024 can be poured into the frame 51120 and can flow around the tubular elements 51080 positioned therein. Referring to **FIG. 471**, the fluidic compensation material 51024 can flow around the tubular element 51080 supported by notches 51130 in the frame 51120. After the compensation material 51024 cures, or at least sufficiently cures, referring now to **FIG. 472**, the tissue thickness compensator 51020 comprising the compensation material 51024 and tubular elements 51080 can be removed from the frame 51120. The tissue thickness compensator 51020 can be trimmed. For example, excess compensation material 51024 can be removed from the tissue thickness compensator 51020 such that the longitudinal sides of the compensation material are substantially planar. Furthermore, referring to **FIG. 473**, the first and second ends 50183, 50185 of the tubular elements 51080 can be pressed together, or closed, to seal the tubular element 51080. The ends can be closed before the tubular elements 51080 are placed in the

frame 51120. Alternatively, the trimming process may transect the ends 51083, 51085 and a heat stacking process can be used to seal and / or close the ends 51083, 51085 of the tubular elements 51080.

[0983] Referring again to FIG. 470, a stiffening pin 51127 can be positioned within each tubular element 51080. For example, the stiffening pin 51127 can extend through a longitudinal lumen of the tubular element 51080. The stiffening pin 51127 can extend beyond each tubular element 51080 such that the stiffening pin 51127 can be positioned in notches 51130 in the frame 51120. In embodiments having stiffening pins 51127, the stiffening pins 51127 can support the tubular elements 51080 when the compensation material 51204 is poured into the frame 51120 and as the fluidic compensation material 51024 flows around the tubular elements 51080, for example. Once the compensation material 51024 cures, solidifies, and / or lyophilizes or sufficiently cures, solidifies, and / or lyophilizes the tissue thickness compensator 51020 can be removed from the frame 51120 and the stiffening pins 51127 can be removed from the longitudinal lumens of the tubular elements 51080. The tubular elements 51080 can then be filled with medicaments, for example. After the tubular elements 51080 are filled with medicaments, the tissue thickness compensator 51020, including the ends 51083, 51085 of the tubular elements 51080, for example, can be trimmed. The tissue thickness compensator 51020 can be die cut, for example, and / or sealed by heat and / or pressure, for example.

[0984] As discussed herein, the tissue thickness compensator 52020 can comprise multiple tubular elements 51080. Referring now to **FIG. 474**, the tubular elements 51080 can comprise different material properties, dimensions and geometries. For example, a first tubular element 51080a can comprise a first thickness and a first material and a second tubular element 51080b can comprise a second thickness and a second material. At least two tubular elements 51080 in the tissue thickness compensator 52020 can comprise the same material. Alternatively, each tubular element 51080 in the tissue thickness compensator 5202 can comprise different materials. Similarly, at least two tubular elements 51080 in the tissue thickness compensator 52020 can comprise the same geometry. Alternatively, each tubular element 51080 in the tissue thickness compensator 52020 can comprise different geometries.

[0985] Referring now to **FIGS. 537-540,** a tissue thickness compensator 51220 can comprise at least one tubular element 51280 that laterally traverses the tissue thickness compensator 51220. Referring to **FIG. 537**, the tissue thickness compensator 51220 can be positioned relative to the

anvil 30060 of the end effector 12. The tissue thickness compensator 51220 can be secured to a securing surface 30061 of the anvil 30060 of the end effector 12, for example. Referring primarily to **FIG. 538**, the tubular element 51280 can comprise a capsule-like shape, for example. The tubular element 51280 can comprise a polymeric composition, such as a bioabsorbable, biocompatible elastomeric polymer, for example.

[0986] Referring again to **FIG. 537**, the tissue thickness compensator 51220 can further comprise a compensation material 51224 that at least partially surrounds the tubular elements 51280. The compensation material 51224 can comprise a bioabsorbable polymer, such as, for example, lyophilized polysaccharide, glycoprotein, elastin, proteoglycan, gelatin, collagen, and / or oxidized regenerated cellulose (ORC), for example. Similar to the above, the compensation material 51024 can hold the tubular elements 51280 in position in the tissue thickness compensator 51220. Further, the compensation material 51224 can be secured to the securing surface 30061 of the anvil 30060 such that the compensation material 51220 is securely positioned in the end effector 12. The compensation material 51224 can comprise at least one medicant.

[0987] Still referring to FIG. 537, the laterally positioned tubular elements 51280 can be positioned relative to the cutting element 30252 on a translating sled 30250 such that the translatable cutting element 30252 is configured to sever the tubular elements 51280. The cutting element 30252 can sever the tubular elements 51280 at or near the center of each tubular element 51280, for example. When the tubular elements 51280 are severed in two halves, the severed portions of the tubular elements 51280 can be configured to swell or expand, as illustrated in FIG. 537. Referring primarily to FIG. 539, a tubular element 51280 can comprise a hydrophilic substance 51099 that can be released and / or exposed when the tubular element 51280 is severed. Furthermore, referring now to FIG. 540, when the hydrophilic substance 51099 contacts bodily fluids in the tissue T, the hydrophilic substance 51099 can attract the fluid, which can cause the tubular element 51280 to swell or expand. As the tubular element 51280 expands, the compensation material 51224 surrounding the tubular element 51280 can shift or adjust to accommodate the swollen tubular element 51280. For example, when the compensation material 51224 comprises gelatin, the gelatin can shift to accommodate the swollen tubular element 51280. Referring again to FIG. 537, expansion of the tubular elements 51280 and shifting of the

compensation material 51224 can cause a corresponding expansion of the tissue thickness compensator 51220.

[0988] Similar to other tissue thickness compensators discussed throughout the present disclosure, the tissue thickness compensator 51220 can be deformed or compressed by an applied force. Further, the tissue thickness compensator 51220 can be sufficiently resilient such that it produces a springback force when deformed by the applied force and can subsequently rebound or partially rebound when the applied force is removed. When the tissue thickness compensator 51220 is captured in a staple entrapment area 30039 (FIG. 417), the staple 30030 can deform the tissue thickness compensator 51220. For example, the staple 30030 can deform the tubular elements 51280 and / or the compensation material 51224 of the tissue thickness compensator 51220 captured within the fired staple 30030. Non-captured portions of the tissue thickness compensator 51220 can also be deformed due to the deformation in the staple entrapment areas 30039. When deformed, the tissue thickness compensator 51220 can seek to rebound from the deformed configuration. Such a rebound may occur prior to the hydrophilic expansion of the tubular element 51280, simultaneously with the hydrophilic expansion of the tubular element 51280, and / or after the hydrophilic expansion of the tubular element 51280. As the tissue thickness compensator 51220 seeks to rebound, it can exert a restoring force on the tissue also captured in the staple entrapment area 30039, as described in greater detail herein.

[0989] Referring to **FIGS. 475-478**, a tissue thickness compensator 52020 can comprise one or more tubular elements 52080 that laterally traverse the tissue thickness compensator 52020, similar to at least one tissue thickness compensator described herein. The tissue thickness compensator 52020 can comprise multiple laterally traversing tubular elements 52080. The tissue thickness compensator 52020 can further comprise one or more sheets of material 52024 that hold or retain at least one tubular element 52080 in the tissue thickness compensator 52020. The one or more sheets of material 52024 can be positioned above and / or below the tubular elements 52080 and can securely retain each tubular element 52080 in the tissue thickness compensator 52020. Referring primarily to **FIG. 475**, the tissue thickness compensator can comprise a first sheet of material 52024a and a second sheet of material 52024b. The tubular elements 52080 can be positioned between the first and second sheets of material 52024a, 52024b. Further, referring still to **FIG. 475**, the sheet of material 52024b can be secured to the top deck surface 30011 of the rigid support portion of the staple cartridge 30000 such that the

tissue thickness compensator 52020 is securely positioned in the end effector 12. Alternatively, one or more of the sheets of material 52024 can be secured to the anvil 30060 or otherwise retained in the end effector 12.

[0990] Referring primarily to **FIG. 476**, the tissue thickness compensator 52020 can be porous and / or permeable. For example, the sheet of material 52024 can comprise a plurality of apertures 52026. The apertures 52026 can be substantially circular. The apertures 52036 can be visible in the sheet of material 52024. Alternatively, the apertures 52036 can be microscopic. Referring still to **FIG. 476**, the tubular elements 52080 can comprise a plurality of apertures 52026, as well. Referring to **FIG. 477**, a tissue thickness compensator 52120 can comprise a sheet of material 52124 that comprises a plurality of non-circular apertures 52126. For example, the apertures 52126 can comprise a diamond and / or slotted shape. Alternatively, referring to **FIG. 478**, a tissue thickness compensator 52220 can comprise a tubular element 52280 that comprises a permeable tubular lattice 52292. The sheet of material 52224 can comprise a bioabsorbable, biocompatible elastomeric polymer and can comprise a medicament, for example.

[0991] In any of the tissue thickness compensators described herein, at least one tubular element 52080 can be configured to swell or expand, as illustrated in FIGS. 479A-479D. For example, referring to FIG. 479A, the tubular elements 52080 can be positioned intermediate the first and second sheet of material 52024a, 52024b in the tissue thickness compensator 52020. When the tissue thickness compensator 52020 contacts tissue T, as illustrated in FIG. 479B, the tissue thickness compensator 52020 can expand. For example, the tubular elements 52080 can comprise a hydrophilic substance 52099 that expands when exposed to fluid in and / or on the tissue T. Further, the sheet of material 52024 and tubular elements 52080 can be permeable, as described herein, such that fluid from the tissue T can permeate the tissue thickness compensator 52020 thereby allowing the fluid to contact the hydrophilic substance 52099 within the tubular elements 52080. As the tubular elements 52080 expand, the sheet of material 52024 surrounding the tubular elements 52080 can shift or adjust to accommodate the swollen tubular elements 52080. Similar to various tissue thickness compensators discussed throughout the present disclosure, the expanded tissue thickness compensator 52020 can be deformed or compressed by an applied force, such as, for example, a compressive force applied by fired staples, as illustrated in FIG. 479C. Further, the tissue thickness compensator 52020 can be sufficiently resilient such that it produces a springback force when deformed by the applied force and can subsequently

rebound when the applied force is removed. Referring now to FIGS. 479D and 479E, the tissue thickness compensator 52020 can rebound to different configurations in different staple entrapment areas 30039 to appropriately accommodate the captured tissue T.

[0992] Referring to **FIGS. 480-485**, a tissue thickness compensator 53020 can comprise a plurality of vertically positioned tubular elements 53080. Each tubular element 53080 can comprise a tubular axis that is substantially perpendicular to the top deck surface 30011 of the rigid support portion 30010 of the staple cartridge 30000. Further, the first end of each tubular element 53080 can be positioned adjacent to the top deck surface 30011, for example. The tubular elements 53080 can be deformable and may comprise an elastomeric polymer, for example. As illustrated in **FIG. 481**, the tubular elements 53080 can be compressed when captured in a staple entrapment area 30039 with stapled tissue T. A tubular element 53080 can comprise an elastic material such that deformation of the tubular element 53080 generates a restoring force as the tubular element 53080 seeks to rebound from the deformed configuration. Deformation of the tubular element 53080 can be at least partially elastic and at least partially plastic. The tubular element 53080 can be configured to act as a spring under an applied force and can be configured not to buckle. Referring to **FIG. 482**, the tubular elements 53080 can be substantially cylindrical. Referring to **FIG. 483**, a tubular element 53180 can comprise a buckling region 53112. The tubular element 53180 can be configured to buckle or deform at the buckling region 53112 when a compressive force is applied thereto. The tubular element 53180 can deform elastically and / or plastically and then be designed to buckle suddenly at the buckling region 53112 under a preselected buckling force.

[0993] Referring primarily to **FIG. 484**, a first tubular element 53080 can be positioned at a first end of a staple cavity 30012 and another tubular element 53080 can be positioned at a second end of the staple cavity 30012. As illustrated in **FIG. 482**, the tubular element 53080 can comprise a lumen 53084 extending therethrough. Referring again to **FIG. 481**, when the staple 30030 is moved from the initial position to the fired position, each staple leg 30032 can be configured to pass through a lumen 53084 of each tubular element 53080. Alternatively, referring primarily to **FIG. 485**, vertically positioned tubular elements 54080 can be arranged in a tissue thickness compensator 54020 such that the tubular elements 54080 abut or contact each other. In other words, the tubular elements 54080 can be clustered or gathered together. The

tubular elements 54080 can be systematically arranged in the tissue thickness compensator 54020; however, as an alternative, the tubular elements 54080 can be randomly arranged.

[0994] Referring again to **FIGS. 480, 484,** and **485**, the tissue thickness compensator 53020 can also comprise a sheet of material 53024 that holds or retains the tubular elements 53080 in the tissue thickness compensator 53020. The sheet of material 53024 can be positioned above and / or below the tubular elements 53080 and can securely retain each tubular element 53080 in the tissue thickness compensator 53020. The tissue thickness compensator 53020 can comprise a first and a second sheet of material 53024. The tubular elements 53080 can be positioned between the first and second sheets of material 53024. Further, the sheet of material 53024 can be secured to the top deck surface 30011 of the rigid support portion of the staple cartridge 30000 such that the tissue thickness compensator 53020 is securely positioned in the end effector 12. Alternatively, a sheet of material 53024 can be secured to the anvil 30060 or otherwise retained in the end effector 12. The sheet of material 53024 can be sufficiently deformable such that the sheet of material 53024 deforms as springs 55080 within the tissue thickness compensator are deformed.

[0995] Referring to **FIGS. 486** and **487**, a tissue thickness compensator 55020 can comprise at least one spring 55080 that is sufficiently resilient such that it is capable of producing a springback force when deformed. Referring primarily to **FIG. 486**, the tissue thickness compensator 55020 can comprise a plurality of springs 55080, such as, for example, three rows of springs 55080. The springs 55080 can be systematically and / or randomly arranged in the tissue thickness compensator 55020. The springs 55080 can comprise an elastomeric polymer, for example. The shape of the springs 55080 can allow for deformation thereof. The springs 55080 can be deformed from an initial configuration to a deformed configuration. For example, when a portion of the tissue thickness compensator 55020 is captured in a staple entrapment area 30039, the springs 55080 in and / or around the staple entrapment area 30039 can be deformed. The springs 55080 can buckle or collapse under a compressive force applied for a fired staple 30030 and the springs 55080 may generate a restoring force that is a function of the spring rate of the deformed spring 55080 and / or the amount the spring 55080 is deformed, for example. The spring 55080 can act as a sponge under a compressive force applied by a fired staple 30030. Further, the spring 55080 can comprise a compensation material, as described in greater detail throughout the present disclosure.

[0996] The tissue thickness compensator 55020 can further comprise one or more sheets of material 55024 that hold or retain at least one spring 55080 in the tissue thickness compensator 55020. The sheets of material 55024 can be positioned above and / or below the springs 55080 and can securely retain the springs 55080 in the tissue thickness compensator 55020. The tissue thickness compensator 55020 can comprise a first sheet of material 55024a and a second sheet of material 55024b. The tubular elements 52080 can be positioned between the first and second sheets of material 55024a, 55024b. Referring primarily to **FIG. 487**, the tissue thickness compensator 55020 can further comprise a third sheet of material 55024c positioned adjacent to either the first or second sheet of material 55024a, 55024b. At least one sheet of material 55024 can be secured to the top deck surface 30011 of the rigid support portion of the staple cartridge 30000, such that the tissue thickness compensator 55020 is securely positioned in the end effector 12. Alternatively, at least one sheet of material 55024 can be secured to the anvil 30060 or otherwise retained in the end effector 12.

[0997] Referring now to **FIG. 487**, when a staple 30030 is fired from the staple cartridge 30000 (**FIG. 485**), the staple 30030 can engage the tissue thickness compensator 55020. The fired staple 30030 can capture tissue T and a portion of the tissue thickness compensator 55020 in the staple entrapment area 30039. The springs 55080 can be deformable such that the tissue thickness compensator 55020 compresses when captured by a fired staple 30030. The springs 55080 can be positioned between fired staples 30030 in the tissue thickness compensator 55020. Alternatively, at least one spring 55080 can be captured within the staple entrapment area 30039.

[0998] Referring to **FIG. 488**, a tissue thickness compensator 60020 can comprise at least two compensation layers 60022. The tissue thickness compensator 60020 can comprise a plurality of compensation layers 60022 which can be stacked on top of each other, positioned side-by-side, or a combination thereof. As described in greater detail herein, the compensation layers 60022 of the tissue thickness compensator 60020 can comprise different geometric and / or material properties, for example. Furthermore, as described in greater detail herein, pockets and / or channels can exist between adjacently stacked compensation layers 60022. For example, a tissue thickness compensator 62020 can comprise six compensation layers 62022a, 62022b, 62022c, 62022d, 62022e, 62022f, which can be adjacently stacked on top of each other (**FIG. 503**).

[0999] Referring to **FIGS. 489, 490,** and **492-497**, a tissue thickness compensator can comprise a first compensation layer 60122a and a second compensation layer 60122b. The first

compensation layer 60122a can be adjacently stacked on top of the second compensation layer 60122b. Adjacently stacked compensation layers 60122 can be separated by a separation gap or pocket 60132. Referring primarily to **FIG. 489**, a tissue thickness compensator 60120 can also comprise at least one cantilever beam or support 60124 positioned between the first and second compensation layers 60122a, 60122b. The support 60124 can be configured to position the first compensation layer 60122a relative to the second compensation layer 60122b such that compensation layers 60122 are separated by the separation gap 60132. As described in greater detail herein, deformation of the support 60124 and / or the compensation layers 60122a, 60122b, for example, can reduce the separation gap 60132.

[1000] The support beam of a tissue thickness compensator can comprise various geometries and dimensions. For example, the support beam can be a simple I-beam, a centered, single-bend support beam 60124 (**FIG. 489**), an off-centered, single-bend support beam 60224 (**FIG. 490**), an elliptical support beam 60324 (**FIG. 492**), a multi-bend support beam 60424 (**FIG. 493**), and / or a symmetrical, dual-cantilevered support beam 60524 (**FIG. 494**). Furthermore, referring now to **FIGS. 489**, **495**, and **496**, a support beam 60624 can be thinner than at least one compensation layer 60122 (**FIG. 495**), a support beam 60724 can be thicker than at least one compensation layer 60122 (**FIG. 496**), and / or a support beam 60124 can be substantially the same thickness as at least one compensation layer 60122 (**FIG. 489**), for example. The material, geometry and / or dimensions of the support beam 60124, for example, can affect the deformability and springback resiliency of the tissue thickness compensator 60120.

[1001] Referring still to **FIG. 489**, the compensation layers 60122 and support beam 60124 of the tissue thickness compensator 60120 can comprise different materials, such as, for example, structural material, biological material, and / or electrical material, for example. For example, at least one compensation layer 60122 can comprise a polymeric composition. The polymeric composition can comprise an at least partially elastic material such that deformation of the compensation layer 60122 and / or the support beam 60124 can generate a springback force. The polymeric composition of the compensation layer 60122 can comprise non-absorbable polymers, absorbable polymers, or combinations thereof. The absorbable polymers can include bioabsorbable, biocompatible elastomeric polymers, for example. Furthermore, the polymeric composition of the compensation layer 60122 can comprise synthetic polymers, non-synthetic polymers, or combinations thereof. Examples of synthetic polymers include, but are not limited

to, polyglycolic acid (PGA), poly(lactic acid) (PLA), polycaprolactone (PCL), polydioxanone (PDO), and copolymers thereof. Examples of non-synthetic polymers include, but are not limited to, polysaccharides, glycoprotein, elastin, proteoglycan, gelatin, collagen, and oxidized regenerated cellulose (ORC). The polymeric composition of the compensation layers 60122 can include varied amounts of absorbable polymers, non-absorbable polymers, synthetic polymers, and non-synthetic polymers, for example, by weight percentage. Each compensation layer 60022 in the tissue thickness compensator 60120 can comprise a different polymeric composition or, alternatively, at least two compensation layers 60122 can comprise the same polymeric composition.

[1002] Referring again to **FIG. 488**, at least one compensation layer 60022 can comprise a therapeutic agent 60098 such as a medicament or pharmaceutically active agent, for example. The compensation layer 60022 can release a therapeutically effective amount of the therapeutic agent 60098. The therapeutic agent 60098 can be released as the compensation layer 60022 is absorbed. Examples of therapeutic agents 60098 can include, but are not limited to, haemostatic agents and drugs, such as, for example, fibrin, thrombin, and / or oxidized regenerated cellulose (ORC), anti-inflammatory drugs such as, for example, diclofenac, aspirin, naproxen, sulindac, and / or hydrocortisone antibiotic and antimicrobial drugs or agents such as, for example, triclosan, ionic silver, ampicillin, gentamicin, polymyxin B, and / or chloramphenicol, and / or anticancer agents such as, for example, cisplatin, mitomycin, and / or adriamycin. The therapeutic agent 60098 can comprise a biologic, such as a stem cell, for example. Each compensation layer 60022 in a tissue thickness compensator 60020 can comprise a different therapeutic agent 60098 or, alternatively, at least two compensation layers 60022 can comprise the same therapeutic agent 60098. A compensation layer 60022 comprising a therapeutic agent 60098, such as a biologic, for example, can be encased between two structural compensation layers 60022 comprising a polymeric composition, such as, for example, polyglycolic acid (PGA) foam, for example. A compensation layer 60022 can also comprise an electrically conductive material, such as, for example, copper.

[1003] Referring again to **FIG. 503**, the compensation layers 62022 in the tissue thickness compensator 62020 can have different geometries. When layers 62022 are adjacently positioned in the tissue thickness compensator 62020, the compensation layers 62022 can form at least one three-dimensional conduit 62032 between the layers 62022. For example, when a second

compensation layer 62022b comprising a channel is positioned above a substantially flat third compensation layer 62022c, the channel and flat surface of the third compensation layer 62022c can define a three-dimensional conduit 62032a therebetween. Similarly, for example, when a fifth compensation layer 62022e comprising a channel is positioned below a fourth compensation layer 62022d comprising a corresponding channel, the channels can form a three-dimensional conduit 62032b defined by the channels in the adjacently stacked compensation layers 62022d, 62022e. The conduits 62032 can direct therapeutic agents and / or bodily fluids as the fluids flow through the tissue thickness compensator 62020.

[1004] Referring to **FIG. 499**, a tissue thickness compensator 61020 can comprise compensation layers 61022, such as layers 60122a and 21022b, configured to receive staples 30030 deployed from the staple cartridge 20000 (**FIG. 498**). As a staple 30030 is moved from an initial position to a fired position, the geometry of at least one compensation layer 61022 can guide the staple legs 30032 to the fired position. At least one compensation layer 61022 can comprise apertures 61030 extending therethrough, wherein the apertures 61030 can be arranged to receive the staple legs 30032 of deployed staples 30030 when the staples 30030 are fired from the staple cartridge 20000 (**FIG. 498**), as described in greater detail herein. Alternatively, referring again to **FIG. 503**, staple legs 30032 can pierce through at least one compensation layer, such as compensation layer 62022f, for example, and can be received through apertures 62030 in at least one compensation layer, such as, for example, compensation layer 62022a.

[1005] Referring primarily to **FIG. 499**, the tissue thickness compensator 60120 can comprise at least one support tab 61026 on one of the compensation layers 61022a, 61022b. The support tab 61026 can protrude into the separation gap 61032 defined between adjacent compensation layers, such as the gap 61032 between the first compensation layer 61020a and second compensation layer 61020b. The support tab 61026 can protrude from a longitudinal side of a first compensation layer 61022a. Further, the support tab 61026 can extend along the length of the longitudinal side or only along a portion thereof. At least one support tab 61026 can protrude from two longitudinal sides of the compensation layer 61022a, 61022b. Further, adjacently positioned compensation layers 61022a, 61022b can comprise corresponding support tabs 60126, such that the support tab 60126 that extends from the first compensation layer 60122a can at least partially align with the support tab 60126 that extends from the second compensation layer 60122b. Referring again to **FIG. 497**, a tissue thickness compensator 60820 can comprise a

limiter plate 60828 between adjacent compensation layers 60122a, 60122b. The limiter plate 60828 can be positioned in the gap 60132 defined between the first compensation layer 60122a and the second compensation layer 60122b, for example. As described in greater detail herein, support tab(s) 61026 and / or limiter plate(s) 60828 can control the deformation and / or deflection of a support 60124 and / or the compensation layers 60122a, 60122b.

[1006] As described herein, the compensation layers 60022 of the tissue thickness compensator 60020 can comprise different materials, geometries and / or dimensions. Such tissue thickness compensators 60020 can be assembled by a variety of manufacturing techniques. Referring primarily to **FIG. 488**, the tissue thickness compensator 60022 can be manufactured by lithographic, stereolithographic (SLA), or silk screening processes. For example, a stereolithographic manufacturing process can create a tissue thickness compensator 60020 in which each compensation layer 60022 comprises different materials and / or geometric features. For example, an ultraviolet light in a stereolithography machine can draw the geometry of a first compensation layer 60022, such that the first compensation layer 60022 comprising a first material, geometry and / or dimensions is cured by the ultraviolet light. The ultraviolet light can subsequently draw the geometry of a second compensation layer 60022, such that the second compensation layer 60022 comprising a second material, geometry and / or dimensions is cured by the ultraviolet light. A stereolithography machine can draw compensation layers 60022 on top of each other, side-by-side, or a combination thereof. Further, the compensation layers 60022 can be drawn such that pockets 60132 exist between adjacent compensation layers 60022. Because a stereolithography machine can create very thin layers having unique geometries, a tissue thickness compensator 60020 manufactured by a stereolithographic process can comprise a very complex three-dimensional geometry.

[1007] Referring to **FIG. 498**, the tissue thickness compensator 60920 can be positioned in the end effector 12 of a surgical instrument 10 (**FIG. 1**). The tissue thickness compensator 60920 can be positioned relative to the staple cartridge 20000 of the end effector 12. For example, the tissue thickness compensator 60920 can be releasably secured to the staple cartridge 20000. At least one compensation layer 60922 of the tissue thickness compensator 60920 can be positioned adjacent to the top deck surface 20011 (**FIG. 408**) of the staple cartridge 20000. For example, a second compensation layer 60922b can be secured to the top deck surface 20011 by an adhesive or by a wrap, similar to at least one of the wraps described herein (**FIG. 218**). The tissue

thickness compensator 60920 can be integral to the staple cartridge 20000 such that the staple cartridge 20000 and the tissue thickness compensator 60920 are formed as a single unit construction. For example, the staple cartridge 20000 can comprise a first body portion, such as the rigid support portion 20010 (**FIG. 408**), and a second body portion, such that as tissue thickness compensator 60920.

[1008] Still referring to **FIG. 498**, the tissue thickness compensator 60920 can comprise a first compensator portion 60920a and a second compensator portion 60920b. The first compensator portion 60920a can be positioned on a first longitudinal side of the staple cartridge 20000 and the second compensator portion 60920b can be positioned on a second longitudinal side of the staple cartridge 20000. When the tissue thickness compensator 60920 is positioned relative to the staple cartridge 20000, the longitudinal slot 20015 (**FIG. 407**) in the rigid support portion 20010 (**FIG. 407**) can extend between the first compensator portion 60920a and the second compensator portion 60920b. When the cutting element 20052 on the staple-firing sled 20050 (**FIG. 407**) translates through the end effector 12, the cutting element 20052 can pass through the longitudinal slot 20015 between the first compensator portion 60920a and the second compensator portion 60920b without severing a portion of the tissue thickness compensator 60920, for example. Alternatively, the cutting element 20052 can be configured to sever a portion of the tissue thickness compensator 60920.

[1009] Referring now to **FIG. 491**, a tissue thickness compensator 63020 can be configured to fit in the end effector 12' of a circular surgical instrument. The tissue thickness compensator 62030 can comprise a circular first compensation layer 63022a and a circular second compensation layer 63022b. The second compensation layer 63022b can be positioned on a circular top deck surface 20011' of a circular staple cartridge 20000', wherein the second compensation layer 63022b can comprise a geometry that corresponds to the geometry of the deck surface 20011'. For example, the deck surface 20011' can comprise a stepped portion and the second compensation layer 63022b can comprise a corresponding stepped portion. The tissue thickness compensator can further comprise at least one support 63024 and / or support tabs 63026, for example, extending around the tissue thickness compensator 63020.

[1010] Referring again to **FIG. 499**, fired staples 30030 can be configured to engage the tissue thickness compensator 60920. As described throughout the present disclosure, a fired staple 30030 can capture a portion of the tissue thickness compensator 60920 and tissue T and apply a

compressive force to the tissue thickness compensator 60920. Further, referring primarily to **FIGS. 500-502**, the tissue thickness compensator 60920 can be deformable. As described herein, a first compensation layer 60920a can be separated from a second compensation layer 60920b by a separation gap 60932. Referring to **FIG. 500**, prior to compression of the tissue thickness compensator 60920, the gap 60932 can comprise a first distance. When a compressive force A is applied to the tissue thickness compensator 60920 and tissue T, for example, by a fired staple 30030 (**FIG. 499**), the support 60924 can be configured to deform. Referring now to **FIG. 501**, the single-bend support beam 60924 can bend under the compressive force A such that the separation gap 60932 between the first compensation layer 60920a and the second compensation layer 60920b is reduced to a second distance. Referring primarily to **FIG. 502**, the first and second compensation layers 60922a, 60922b can also deform under the compressive force A. The support tabs 60926 can control deformation of the compensation layers 60920. For example, the support tabs 60926 can prevent excessive bending of the compensation layers 60920 by supporting the longitudinal sides of the compensation layer 60920 when they come into contact with one another. The support tabs 60926 can also be configured to bend or bow under the compressive force A. Additionally or alternatively, the limiter plate 60128 (**FIG. 497**) described in greater detail herein, can limit the deformation of the compensation layers 60920 when the compensation layers 60920 and / or support tabs 60926 contact the limiter plate 60128.

[1011] Furthermore, similar to various tissue thickness compensators described herein, tissue thickness compensator 60920 can generate a springback or restoring force when deformed. The restoring force generated by the deformed tissue thickness compensator can at least depend on the orientation, dimensions, material, and / or geometry of the tissue thickness compensator 60920, as well as the amount of the tissue thickness compensator 60920 that is deformed by the applied force. Furthermore, at least a portion of the tissue thickness compensator 60920 can be resilient such that the tissue thickness compensator 60920 generates a spring load or restoring force when deformed by a fired staple 30030. The support 60924 can comprise an elastic material and / or at least one compensation layer 60922 can comprise an elastic material such that the tissue thickness compensator 60920 is resilient.

[1012] Referring now to FIG. 504, an end effector of a surgical stapling instrument can comprise a first jaw and a second jaw, wherein at least one of the first jaw and the second jaw can be configured to be moved relative to the other. The end effector can comprise a first jaw including

a staple cartridge channel 19070 and a second jaw including an anvil 19060, wherein the anvil 19060 can be pivoted toward and/or away from the staple cartridge channel 19070, for example. The staple cartridge channel 19070 can be configured to receive a staple cartridge 19000, for example, which, can be removably retained within the staple cartridge channel 19070. The staple cartridge 19000 can comprise a cartridge body 19010 and a tissue thickness compensator 19020 wherein, the tissue thickness compensator 19020 can be removably attached to the cartridge body 19010. Referring now to FIG. 505, the cartridge body 19010 can comprise a plurality of staple cavities 19012 and a staple 19030 positioned within each staple cavity 19012. Also, the staples 19030 can be supported by staple drivers 19040 positioned within the cartridge body 19010 wherein a sled and/or firing member, for example, can be advanced through the staple cartridge 19000 to lift the staple drivers 19040 upwardly within the staple cavities 19012, as illustrated in FIG. 506, and eject the staples 19030 from the staple cavities 19012.

[1013] Referring primarily to FIGS. 504 and 505, the tissue thickness compensator 19020 can comprise resilient members 19022 and a vessel 19024 encapsulating the resilient members 19022. The vessel 19024 can be sealed and can define a cavity containing an inner atmosphere having a pressure which is different than the surrounding atmospheric pressure. The pressure of the inner atmosphere can be greater than the pressure of the surrounding atmosphere while, as an alternative, the pressure of the inner atmosphere can be less than the pressure of the surrounding atmosphere. Where the vessel 19024 contains a pressure less than the pressure of the surrounding atmosphere, the sidewall of the vessel 19024 can enclose a vacuum. In such cases, the vacuum can cause the vessel 19024 to distort, collapse, and/or flatten wherein the resilient members 19022 positioned within the vessel 19024 can be resiliently compressed within the vessel 19024. When a vacuum is drawn on the vessel 19024, the resilient members 19022 can deflect or deform downwardly and can be held in position by the sidewalls of the vessel 19024 in a compressed, or vacuum-packed, state.

[1014] Resilient member 19022 and vessel 19024 are comprised of biocompatible materials. Resilient member 19022 and/or vessel 19024 can be comprised of bioabsorbable materials such as PLLA, PGA, and/or PCL, for example. Resilient member 19022 can be comprised of a resilient material. Resilient member 19022 can also comprise structural resilience. For example, resilient member 19022 can be in the form of a hollow tube.

[1015] Further to the above, the tissue thickness compensator 19020 can be positioned against or adjacent to the deck surface 19011 of the cartridge body 19010. When the staples 19030 are at least partially fired, referring now to FIG. 506, the legs of the staples 19030 can puncture or rupture the vessel 19024. The vessel 19024 can comprise a central portion 19026 which can be positioned over a cutting slot 19016 of the cartridge body 19010 such that, when a cutting member 19080 is advanced to incise tissue T positioned between the staple cartridge 19000 and the anvil 19060, the cutting member 19080 can also incise the central portion 19026 of the vessel 19024 thereby puncturing or rupturing the vessel 19024. In either event, once the vessel 19024 has been ruptured, the inner atmosphere within the vessel 19024 can equalize with the atmosphere surrounding the tissue thickness compensator 19020 and allow the resilient members 19022 to resiliently expand to regain, or at least partially regain, their undistorted and/or unflattened configuration. In such circumstances, the resilient members 19022 can apply a biasing force to the tissue T captured within the deformed staples 19020. More specifically, after being deformed by the forming surfaces of pockets19062 defined in the anvil 19060, the legs of the staples 19030 can capture tissue T and at least a portion of a resilient member 19022 within the staples 19030 such that, when the vessel 19024 ruptures, the tissue thickness compensator 19020 can compensate for the thickness of the tissue T captured within the staples 19030. For instance, when the tissue T captured within a staple 19030 is thinner, a resilient member 19022 captured within that staple 19030 can expand to fill gaps within the staple 19030 and apply a sufficient compression force to the tissue T. Correspondingly, when the tissue T captured within a staple 19030 is thicker, a resilient member 19022 captured within that staple 19030 can remain compressed to make room for the thicker tissue within the staple 19030 and, likewise, apply a sufficient compression force to the tissue T.

[1016] When the vessel 19024 is punctured, as outlined above, the resilient members 19022 can expand in an attempt to resiliently return to their original configuration. In certain circumstances, the portion of resilient members 19022 that have been captured within the staples 19030 may not be able to return to their original undistorted shape. In such circumstances, the resilient members 19022 can comprise a spring which can apply a compression force to the tissue T captured within the staples 19030. A resilient member 19022 can emulate a linear spring wherein the compression force applied by the resilient member 19022 is linearly proportional to the amount, or distance, in which the resilient member 19022 remains deflected within the staple 19030.

Alternatively, a resilient member 19022 can emulate a non-linear spring wherein the compression force applied by the resilient member 19022 is not linearly proportional to the amount, or distance, in which the resilient member 19022 remains deflected within the staple 19030.

[1017] Referring primarily to FIGS. 507 and 508, a staple cartridge 19200 can comprise a tissue thickness compensator 19220 which can comprise one or more sealed vessels 19222 therein. Each of the vessels 19222 can be sealed and can contain an inner atmosphere. The pressure of the inner atmosphere within a sealed vessel 19222 can exceed atmospheric pressure while, alternatively, the pressure of the inner atmosphere within a sealed vessel 19222 can be below atmospheric pressure. Where the pressure of the inner atmosphere within a vessel 19222 is below atmospheric pressure, the vessel 19222 can be described as containing a vacuum. One or more of the vessels 19222 can be wrapped or contained in an outer shroud, container, wrap, and/or film 19224, for example, wherein the tissue thickness compensator 19220 can be positioned above a deck surface 19011 of the cartridge body 19010. Each vessel 19222 can be manufactured from a tube having a circular, or an at least substantially circular, cross-section, for example, having a closed end and an open end. A vacuum can be drawn on the open end of the tube and, when a sufficient vacuum has been reached within the tube, the open end can be closed and sealed. For example, the tube can be comprised of a polymeric material, for example, wherein the open end of the tube can be heat staked in order to close and seal the same. In any event, the vacuum within each vessel 19222 can pull the sidewalls of the tube inwardly and resiliently distort and/or flatten the tube. The vessels 19222 are illustrated in an at least partially flattened state in FIG. 508.

[1018] When the staples 19030 are in their unfired position, as illustrated in FIG. 508, the tips of the staples 19030 can be positioned below the tissue thickness compensator 19220. For example, the staples 19030 can be positioned within their respective staple cavities 19012 such that the staples 19030 do not contact the vessels 19222 until the staples 19030 are moved from the unfired positions, illustrated in FIG. 508, to their fired positions, illustrated in FIG. 509. The wrap 19224 of the tissue thickness compensator 19220 can protect the vessels 19220 from being prematurely punctured by the staples 19030. When the staples 19030 are at least partially fired, referring now to FIG. 509, the legs of the staples 19030 can puncture or rupture the vessels 19222. In such circumstances, the inner atmospheres within the vessels 19222 can equalize with

the atmosphere surrounding the vessels 19222 and resiliently expand to regain, or at least partially regain, their undistorted and/or unflattened configuration. In such circumstances, the punctured vessels 19222 can apply a biasing force to the tissue captured within the deformed staples 19030. More specifically, after being deformed by the forming surfaces of pockets19062 defined in the anvil 19060, the legs of the staples 19030 can capture tissue T and at least a portion of a vessel 19222 within the staples 19030 such that, when the vessels 19222 rupture, the vessels 19222 can compensate for the thickness of the tissue T captured within the staples 19030. For instance, when the tissue T captured within a staple 19030 is thinner, a vessel 19222 captured within that staple 19030 can expand to fill gaps within the staple 19030 and, concurrently, apply a sufficient compression force to the tissue T. Correspondingly, when the tissue T captured within a staple 19030 is thicker, a vessel 19222 captured within that staple 19030 can remain compressed to make room for the thicker tissue within the staple 19030 and, concurrently, apply a sufficient compression force to the tissue T.

[1019] When the vessels 19222 are punctured, as outlined above, the vessels 19222 can expand in an attempt to resiliently return to their original configuration. The portion of vessels 19222 that have captured within the staples 19030 may not be able to return to their original undistorted shape. In such circumstances, the vessel 19222 can comprise a spring which can apply a compression force to the tissue T captured within the staples 19030. A vessel 19222 can emulate a linear spring wherein the compression force applied by the vessel 19222 is linearly proportional to the amount, or distance, in which the vessel 19222 remains deflected within the staple 19030. Alternatively, a vessel 19222 can emulate a non-linear spring wherein the compression force applied by the vessel 19222 is not linearly proportional to the amount, or distance, in which the vessel 19222 remains deflected within the staple 19030. The vessels 19222 can be hollow and, empty when they are in their sealed configuration. Alternatively, each of the vessels 19222 can define a cavity and can further include at least one medicament contained therein. The vessels 19222 can be comprised of at least one medicament which can be released and/or bioabsorbed, for example.

[1020] The vessels 19222 of the tissue thickness compensator 19220 can be arranged in any suitable manner. As illustrated in FIG. 507, the staple cavities 19012 defined in the cartridge body 19010, and the staples 19030 positioned in the staple cavities 19012, can be arranged in rows. As illustrated, the staple cavities 19012 can be arranged in six longitudinal, linear rows, for

example; however, any suitable arrangement of staple cavities 19012 could be utilized. As also illustrated in FIG. 507, the tissue thickness compensator 19220 can comprise six vessels 19222 wherein each of the vessels 19222 can be aligned with, or positioned over, a row of staple cavities 19012. Each of the staples 19030 within a row of staple cavities 19012 can be configured to puncture the same vessel 19222. In certain situations, some of the staple legs of the staples 19030 may not puncture the vessel 19222 positioned thereover; however, where the vessel 19222 defines a continuous internal cavity, for example, the cavity can be sufficiently punctured by at least one of the staples 19030 in order to allow the pressure of the internal cavity atmosphere to equalize with the atmospheric pressure surrounding the vessel 19222. Referring now to FIG. 514, a tissue thickness compensator can comprise a vessel, such as vessel 19222', for example, which can extend in a direction which is transverse to a line of staples 19030. For example, a vessel 19222' can extend across multiple staple rows. Referring now to FIG. 515, a tissue thickness compensator 19220" can comprise a plurality of vessels 19222" which extend in a direction which is perpendicular, or at least substantially perpendicular, to a line of staples 19030. For example, some of the vessels 19222" may be punctured by the staples 19030 while others may not be punctured by the staples 19030. The vessels 19222" can extend across or through a cutting path in which a cutting member could transect and rupture the vessels 19222", for example.

[1021] As described above, a tissue thickness compensator, such as tissue thickness compensator 19220, for example, can comprise a plurality of sealed vessels, such as vessels 19222, for example. As also described above, each of the sealed vessels 19222 can comprise a separate internal atmosphere. The vessels 19222 can have different internal pressures. For example, a first vessel 19222 can comprise an internal vacuum having a first pressure and a second vessel 19222 can comprise an internal vacuum having a second, different pressure, for example. For example, the amount of distortion or flattening of a vessel 19222 can be a function of the vacuum pressure of the internal atmosphere contained therein. For instance, a vessel 19222 having a greater vacuum can be distorted or flattened a greater amount as compared to a vessel 19222 having a smaller vacuum. The cavity of a vessel can be segmented into two or more separate, sealed cavities wherein each separate, sealed cavity can comprise a separate internal atmosphere. For example, some of the staples within a staple row can be configured and arranged to puncture a first cavity defined in the vessel while other staples within the staple row can be configured and

arranged to puncture a second cavity defined in the vessel, for example. In such cases, especially where the staples in a staple row are sequentially fired from one end of the staple row to the other, as described above, one of the cavities can remain intact and can maintain its internal atmosphere when another cavity is ruptured. The first cavity can have an inner atmosphere having a first vacuum pressure and the second cavity can have an inner atmosphere having a second, different vacuum pressure, for example. A cavity that remains intact can maintain its inner pressure until the vessel is bioabsorbed thereby creating a timed pressure release.

[1022] Referring now to FIGS. 510 and 511, a tissue thickness compensator, such as tissue thickness compensator 19120, for example, can be attached to an anvil 19160. Similar to the above, the tissue thickness compensator 19120 can comprise a vessel 19124 and a plurality of resilient members 19122 positioned therein. Also similar to the above, the vessel 19124 can define a cavity containing an inner atmosphere having a pressure which is less than or greater than the pressure of the atmosphere surrounding the tissue thickness compensator 19120. Where the inner atmosphere within the vessel 19124 comprises a vacuum, the vessel 19124 and the resilient members 19122 positioned therein can be distorted, collapsed, and/or flattened by the difference in pressure between the vacuum in the vessel 19124 and the atmospheric pressure outside of the vessel 19124. In use, the anvil 19160 can be moved into a closed position in which it is positioned opposite a staple cartridge 19100 and in which a tissue engaging surface 19121 on the vessel 19124 can engage the tissue T positioned intermediate the tissue thickness compensator 19120 and a staple cartridge 19100. In use, the firing member 19080 can be advanced distally to fire the staples 19030, as described above, and, at the same time, incise the tissue T. The tissue thickness compensator 19120 can further comprise an intermediate portion 19126 which can be aligned with a cutting slot defined in the anvil 19160 wherein, when the firing member 19080 is advanced distally through the tissue thickness compensator 19120, the firing member 19080 can puncture or rupture the vessel 19124. Also, similar to the above, the firing member 19080 can lift the staple drivers 19040 upwardly and fire the staples 19030 such that the staples 19030 can contact the anvil 19160 and be deformed into their deformed configuration, as illustrated in FIG. 512. When the staples 19030 are fired, the staples 19030 can pierce the tissue T and then pierce or rupture the vessel 19124 such that the resilient members 19122 positioned within the vessel 19124 can at least partially expand, as outlined above.

[1023] Further to the above, a tissue thickness compensator can be comprised of a biocompatible material. The biocompatible material, such as, a foam, may comprise tackifiers, surfactants, fillers, cross-linkers, pigments, dyes, antioxidants and other stabilizers and/or combinations thereof to provide desired properties to the material. A biocompatible foam may comprise a surfactant. The surfactant may be applied to the surface of the material and/or dispersed within the material. Without wishing to be bound to any particular theory, the surfactant applied to the biocompatible material may reduce the surface tension of the fluids contacting the material. For example, the surfactant may reduce the surface tension of water contacting the material to accelerate the penetration of water into the material. The water may act as a catalyst. The surfactant may increase the hydrophilicity of the material.

[1024] The surfactant may comprise an anionic surfactant, a cationic surfactant, and/or a non-ionic surfactant. Examples surfactants include, but are not limited to polyacrylic acid, methalose, methyl cellulose, ethyl cellulose, propyl cellulose, hydroxy ethyl cellulose, carboxy methyl cellulose, polyoxyethylene cetyl ether, polyoxyethylene lauryl ether, polyoxyethylene octyl ether, polyoxyethylene octylphenyl ether, polyoxyethylene oleyl ether, polyoxyethylene sorbitan monolaurate, polyoxyethylene stearyl ether, polyoxyethylene nonylphenyl ether, dialkylphenoxy poly(ethyleneoxy) ethanol, and polyoxamers, and combinations thereof. The surfactant may comprise a copolymer of polyethylene glycol and polypropylene glycol. The surfactant may comprise a phospholipid surfactant. The phospholipid surfactant may provide antibacterial stabilizing properties and/or disperse other materials in the biocompatible material. The tissue thickness compensator may comprise at least one medicament. The tissue thickness compensator may comprise one or more of the natural materials, non-synthetic materials, and/or synthetic materials described herein. The tissue thickness compensator may comprise a biocompatible foam comprising gelatin, collagen, hyaluronic acid, oxidized regenerated cellulose, polyglycolic acid, polycaprolactone, polyactic acid, polydioxanone, polyhydroxyalkanoate, poliglecaprone, and combinations thereof. The tissue thickness compensator may comprise a film comprising the at least one medicament. The tissue thickness compensator may comprise a biodegradable film comprising the at least one medicament. The medicament may comprise a liquid, gel, and/or powder. The medicaments may comprise anticancer agents, such as, for example, cisplatin, mitomycin, and/or adriamycin.

[1025] The tissue thickness compensator may comprise a biodegradable material to provide controlled elution of the at least one medicament as the biodegradable material degrades. The biodegradable material may degrade may decompose, or loses structural integrity, when the biodegradable material contacts an activator, such as, for example an activator fluid. The activator fluid may comprise saline or any other electrolyte solution, for example. The biodegradable material may contact the activator fluid by conventional techniques, including, but not limited to spraying, dipping, and/or brushing. In use, for example, a surgeon may dip an end effector and/or a staple cartridge comprising the tissue thickness compensator comprising the at least one medicament into an activator fluid comprising a salt solution, such as sodium chloride, calcium chloride, and/or potassium chloride. The tissue thickness compensator may release the medicament as the tissue thickness compensator degrades. The elution of the medicament from the tissue thickness compensator may be characterized by a rapid initial elution rate and a slower sustained elution rate.

[1026] A tissue thickness compensator, for example, can be comprised of a biocompatible material which may comprise an oxidizing agent. The oxidizing agent may an organic peroxide and/or an inorganic peroxide. Examples of oxidizing agents may include, but are not limited to, hydrogen peroxide, urea peroxide, calcium peroxide, and magnesium peroxide, and sodium percarbonate. The oxidizing agent may comprise peroxygen-based oxidizing agents and hypohalite-based oxidizing agents, such as, for example, hydrogen peroxide, hypochlorous acid, hypochlorites, hypocodites, and percarbonates. The oxidizing agent may comprise alkali metal chlorites, hypochlorites and perborates, such as, for example, sodium chlorite, sodium hypochlorite and sodium perborate. The oxidizing agent may comprise vanadate. The oxidizing agent may comprise ascorbic acid. The oxidizing agent may comprise an active oxygen generator. A tissue scaffold may comprise the biocompatible material comprising an oxidizing agent.

[1027] The biocompatible material may comprise a liquid, gel, and/or powder. The oxidizing agent may comprise microparticles and/or nanoparticles, for example. For example, the oxidizing agent may be milled into microparticles and/or nanoparticles. The oxidizing agent may be incorporated into the biocompatible material by suspending the oxidizing agent in a polymer solution. The oxidizing agent may be incorporated into the biocompatible material during the lyophylization process. After lyophylization, the oxidizing agent may be attached to the cell

walls of the biocompatible material to interact with the tissue upon contact. The oxidizing agent may not be chemically bonded to the biocompatible material. A percarbonate dry power may be embedded within a biocompatible foam to provide a prolonged biological effect by the slow release of oxygen. A percarbonate dry power may be embedded within a polymeric fiber in a non-woven structure to provide a prolonged biological effect by the slow release of oxygen. The biocompatible material may comprise an oxidizing agent and a medicament, such as, for example, doxycycline and ascorbic acid.

[1028] The biocompatible material may comprise a rapid release oxidizing agent and/or a slower sustained release oxidizing agent. The elution of the oxidizing agent from the biocompatible material may be characterized by a rapid initial elution rate and a slower sustained elution rate. The oxidizing agent may generate oxygen when the oxidizing agent contacts bodily fluid, such as, for example, water. Examples of bodily fluids may include, but are not limited to, blood, plasma, peritoneal fluid, cerebral spinal fluid, urine, lymph fluid, synovial fluid, vitreous fluid, saliva, gastrointestinal luminal contents, and/or bile. Without wishing to be bound to any particular theory, the oxidizing agent may reduce cell death, enhance tissue viability and/or maintain the mechanical strength of the tissue to tissue that may be damaged during cutting and/or stapling. The biocompatible material may comprise at least one microparticle and/or nanoparticle. The biocompatible material may comprise one or more of the natural materials, non-synthetic materials, and synthetic materials described herein. The biocompatible material may comprise particles having a mean diameter of about 10 nm to about 100 nm and/or about 10 μm to about 100 μm, such as, for example, 45-50 nm and/or 45-50 μm. The biocompatible material may comprise biocompatible foam comprising at least one microparticle and/or nanoparticle embedded therein. The microparticle and/or nanoparticle may not be chemically bonded to the biocompatible material. The microparticle and/or nanoparticle may provide controlled release of the medicament. The microparticle and/or nanoparticle may comprise at least one medicament. The microparticle and/or nanoparticle may comprise a hemostatic agent, an anti-microbial agent, and/or an oxidizing agent, for example. The tissue thickness compensator may comprise a biocompatible foam comprising a hemostatic agent comprising oxidized regenerated cellulose, an anti-microbial agent comprising doxycline and/or Gentamicin, and/or an oxidizing agent comprising a percarbant. The microparticle and/or nanoparticle may provide controlled release of the medicament up to three days, for example.

[1029] The microparticle and/or nanoparticle may be embedded in the biocompatible material during a manufacturing process. For example, a biocompatible polymer, such as, for example, a PGA/PCL, may contact a solvent, such as, for example, dioxane to form a mixture. The biocompatible polymer may be ground to form particles. Dry particles, with or without ORC particles, may be contacted with the mixture to form a suspension. The suspension may be lyophilized to form a biocompatible foam comprising PGA/PCL having dry particles and/or ORC particles embedded therein.

[1030] The tissue thickness compensators or layers disclosed herein can be comprised of an absorbable polymer, for example. A tissue thickness compensator can be comprised of foam, film, fibrous woven, fibrous non-woven PGA, PGA/PCL (Poly(glycolic acid-co-caprolactone)), PLA/PCL (Poly(lactic acid-co- polycaprolactone)), PLLA/PCL, PGA/TMC (Poly(glycolic acid-co-trimethylene carbonate)), PDS, PEPBO or other absorbable polyurethane, polyester, polycarbonate, Polyorthoesters, Polyanhydrides, Polyesteramides, and/or Polyoxaesters, for example. A tissue thickness compensator can be comprised of PGA/PLA (Poly(glycolic acid-co-lactic acid)) and/or PDS/PLA (Poly(p-dioxanone-co-lactic acid)), for example. A tissue thickness compensator can be comprised of an organic material, for example. A tissue thickness compensator can be comprised of Carboxymethyl Cellulose, Sodium Alginate, Cross-linked Hyaluronic Acid, and/or Oxidized regenerated cellulose, for example. The tissue thickness compensator can comprise a durometer in the 3-7 Shore A (30-50 Shore OO) ranges with a maximum stiffness of 15 Shore A (65 Shore OO), for example. The tissue thickness compensator can undergo 40% compression under 3 lbf load, 60% compression under 6 lbf load, and/or 80% compression under 20 lbf load, for example. One or more gasses, such as air, nitrogen, carbon dioxide, and/or oxygen, for example, can be bubbled through and/or contained within the tissue thickness compensator. A tissue thickness compensator can comprise beads therein which comprise between approximately 50% and approximately 75% of the material stiffness comprising the tissue thickness compensator.

[1031] The tissue thickness compensator can comprise hyaluronic acid, nutrients, fibrin, thrombin, platelet rich plasma, Sulfasalazine (Azulfidine® – 5ASA+Sulfapyridine diazo bond))– prodrug – colonic bacterial (Azoreductase), Mesalamine (5ASA with different prodrug configurations for delayed release), Asacol® (5ASA + Eudragit-S coated – pH > 7 (coating dissolution)), Pentasa® (5ASA + ethylcellulose coated – time/pH dependent slow release),

Mesasal® (5ASA + Eudragit-L coated – pH > 6), Olsalazine (5ASA + 5ASA – colonic bacterial (Azoreductase)), Balsalazide (5ASA + 4Aminobenzoyl-B-alanine) - colonic bacterial (Azoreductase)), Granulated mesalamine, Lialda (delay and SR formulation of mesalamine), HMPL-004 (herbal mixture that may inhibit TNF-alpha, interleukin-1 beta, and nuclear-kappa B activation), CCX282-B (oral chemokine receptor antagonist that interferes with trafficking of T lymphocytes into the intestinal mucosa), Rifaximin (nonabsorbable broad-spectrum antibiotic), Infliximab, murine chymieric (monoclonal antibody directed against TNF-alpha-approved for reducing signs/symptoms and maintaining clinical remission in adult/pediatric patients with moderate/severe luminal and fistulizing Crohn's disease who have had inadequate response to conventional therapy), Adalimumab, Total Human IgG1 (anti-TNF-alpha monoclonal antibody - approved for reducing signs/symptoms of Crohn's disease, and for the induction and maintenance of clinical remission in adult patients with moderate/severe active Crohn's disease with inadequate response to conventional therapies, or who become intolerant to Infliximab), Certolizumab pegoll, humanized anti-TNF FAB' (monoclonal antibody fragment linked to polyethylene glycol - approved for reducing signs/symptoms of Crohn's disease and for the induction and maintenance of response in adult patients w/ moderate/severe disease with inadequate response to conventional therapies), Natalizumab, First non-TNF-alpha inhibitor (biologic compound approved for Crohn's disease), Humanized monoclonal IgG4 antibody (directed against alpha-4 integrin - FDA approved for inducing and maintaining clinical response and remission in patients with moderate/severe disease with evidence of inflammation and who have had inadequate response to or are unable to tolerate conventional Crohn's therapies and inhibitors of TNF-alpha), concomitant Immunomodulators potentially given with Infliximab, Azathioprine 6-Mercaptopurine (purine synthesis inhibitor – prodrug), Methotrexate (binds dihydrofolate reductase (DHFR) enzyme that participates in tetrahydrofolate synthesis, inhibits all purine synthesis), Allopurinol and Thioprine therapy, PPI, H2 for acid suppression to protect the healing line, C-Diff – Flagyl, Vancomycin (fecal translocation treatment; probiotics; repopulation of normal endoluminal flora), and/or Rifaximin (treatment of bacterial overgrowth (notably hepatic encephalopathy); not absorbed in GI tract with action on intraluminal bacteria), for example.

[1032] As described herein, a tissue thickness compensator can compensate for variations in the thickness of tissue that is captured within the staples ejected from a staple cartridge and/or

contained within a staple line, for example. Stated another way, certain staples within a staple line can capture thick portions of the tissue while other staples within the staple line can capture thin portions of the tissue. In such circumstances, the tissue thickness compensator can assume different heights or thicknesses within the staples and apply a compressive force to the tissue captured within the staples regardless of whether the captured tissue is thick or thin. A tissue thickness compensator can compensate for variations in the hardness of the tissue. For instance, certain staples within a staple line can capture highly compressible portions of the tissue while other staples within the staple line can capture portions of the tissue which are less compressible. In such circumstances, the tissue thickness compensator can be configured to assume a smaller height within the staples that have captured tissue having a lower compressibility, or higher hardness, and, correspondingly, a larger height within the staples that have captured tissue having a higher compressibility, or lower hardness, for example. In any event, a tissue thickness compensator, regardless of whether it compensates for variations in tissue thickness and/or variations in tissue hardness, for example, can be referred to as a 'tissue compensator' and/or as a 'compensator', for example.

[1033] The devices disclosed herein can be designed to be disposed of after a single use, or they can be designed to be used multiple times. In either case, however, the device can be reconditioned for reuse after at least one use. Reconditioning can include any combination of the steps of disassembly of the device, followed by cleaning or replacement of particular pieces, and subsequent reassembly. In particular, the device can be disassembled, and any number of the particular pieces or parts of the device can be selectively replaced or removed in any combination. Upon cleaning and/or replacement of particular parts, the device can be reassembled for subsequent use either at a reconditioning facility, or by a surgical team immediately prior to a surgical procedure. Those skilled in the art will appreciate that reconditioning of a device can utilize a variety of techniques for disassembly, cleaning/replacement, and reassembly. Use of such techniques, and the resulting reconditioned device, are all within the scope of the present application.

[1034] Preferably, the invention described herein will be processed before surgery. First, a new or used instrument is obtained and if necessary cleaned. The instrument can then be sterilized. In one sterilization technique, the instrument is placed in a closed and sealed container, such as a plastic or TYVEK bag. The container and instrument are then placed in a field of radiation that

can penetrate the container, such as gamma radiation, x-rays, or high-energy electrons. The radiation kills bacteria on the instrument and in the container. The sterilized instrument can then be stored in the sterile container. The sealed container keeps the instrument sterile until it is opened in the medical facility.

[1035] Any patent, publication, or other disclosure material, in whole or in part, that is said to be incorporated by reference herein is incorporated herein only to the extent that the incorporated materials does not conflict with existing definitions, statements, or other disclosure material set forth in this disclosure. As such, and to the extent necessary, the disclosure as explicitly set forth herein supersedes any conflicting material incorporated herein by reference. Any material, or portion thereof, that is said to be incorporated by reference herein, but which conflicts with existing definitions, statements, or other disclosure material set forth herein will only be incorporated to the extent that no conflict arises between that incorporated material and the existing disclosure material.

[1036] While this invention has been described as having exemplary designs, the present invention may be further modified within the spirit and scope of the disclosure. This application is therefore intended to cover any variations, uses, or adaptations of the invention using its general principles. Further, this application is intended to cover such departures from the present disclosure as come within known or customary practice in the art to which this invention pertains.

Claims

1. A tissue thickness compensator comprising:

a biocompatible material;

a first component; and

a second component;

wherein the first component and second component are adapted to form a reaction product to expand the tissue thickness compensator.

2. The tissue thickness compensator of claim 1, further comprising an encapsulated component comprising one of the first component and second component, wherein the other of the first component and second component is embedded in the biocompatible material.

3. The tissue thickness compensator of claim 1, wherein the first component comprises a hydrophilic material embedded in the biocompatible material and the second component is a bodily fluid.

4. The tissue thickness compensator of claim 1 comprising a first encapsulated component comprising the first component and a second encapsulated component comprising the second component.

5. The tissue thickness compensator of claim 4, wherein the biocompatible material comprises at least one encapsulation comprising the first encapsulated component and the second encapsulated component.

6. The tissue thickness compensator of claim 4, wherein the first encapsulated component is configured to release the first component when the first encapsulated component is ruptured, and the second encapsulated component is configured to release the second component when the second encapsulated component is ruptured.

7. The tissue thickness compensator of any preceding claim, wherein the biocompatible material comprises albumin, alginate, carbohydrate, casein, cellulose, chitin, chitosan, collagen,

blood, dextran, elastin, fibrin, fibrinogen, gelatin, heparin, hyaluronic acid, keratin, protein, serum, starch, poly(lactic acid), poly(glycolic acid), poly(hydroxybutyrate), poly(phosphazine), polyester, polyethylene glycol, polyalkyleneoxide, polyacrylamide, polycarbonate, polyhydroxyethylmethylacrylate, poly(vinylpyrrolidone), polyvinyl alcohol, poly(caprolactone), poly(dioxanone), polyacrylic acid, polyacetate, polypropylene, glycerol, poly(amino acid), copoly(ether-ester), polyalkylene oxalate, polyamide, poly(iminocarbonate), polyoxaester, polyorthoester, polyphosphazene or a combination of the foregoing.

8. The tissue thickness compensator of Claim 1, wherein the reaction product is formed *in situ* by contacting the first component and the second component.

9. The tissue thickness compensator of any preceding claim, wherein the reaction product is a fluid-swellable composition.

10. The tissue thickness compensator of any one of claims 1 and 4-9, wherein the first component comprises a first hydrogel precursor, the second component comprises a second hydrogel precursor, and the reaction product comprises a hydrogel.

11. The tissue thickness compensator of any preceding claim, wherein the first component and second component are independently selected from albumin, alginate, carbohydrate, casein, cellulose, chitin, chitosan, collagen, blood, dextran, elastin, fibrin, fibrinogen, gelatin, heparin, hyaluronic acid, keratin, protein, serum, starch, poly(lactic acid), poly(glycolic acid), polycarbonate, poly(hydroxybutyrate), poly(phosphazine), polyester, polyethylene glycol, polyalkyleneoxide, polyacrylamide, polyhydroxyethylmethylacrylate, poly(vinylpyrrolidone), polyvinyl alcohol, poly(caprolactone), poly(dioxanone), polyacrylic acid, polyacetate, polypropylene, glycerol, poly(amino acid), copoly(ether-ester), polyalkylene oxalate, polyamide, poly(iminocarbonate), polyoxaester, polyorthoester, polyphosphazene or a combination of the foregoing.

12. The tissue thickness compensator of any preceding claim, comprising an outer layer comprising a water impermeable material and an inner layer comprising the biocompatible material and at least one of the first component and second component.

13. The tissue thickness compensator of claim 12, wherein the water impermeable material comprises poly(lactic acid), poly(glycolic acid), poly(hydroxybutyrate), poly(phosphazine), polyester, polyethylene glycol, polyalkyleneoxide, polyacrylamide, polycarbonate, polyhydroxyethylmethylacrylate, poly(vinylpyrrolidone), polyvinyl alcohol, poly(caprolactone), poly(dioxanone), polyacrylic acid, polyacetate, polypropylene, glycerol, poly(amino acid), copoly(ether-ester), polyalkylene oxalate, polyamide, poly(iminocarbonate), polyoxaester, polyorthoester, polyphosphazene or a combination of the foregoing.

14. The tissue thickness compensator of any preceding claim, wherein the biocompatible material comprises a reinforcement material embedded therein, and wherein the reinforcement material comprises a mesh, a fiber, a particle, a powder, or a combination of the foregoing.

15. The tissue thickness compensator of claim 14, wherein the reinforcement material comprises collagen, gelatin, fibrin, fibrinogen, elastin, keratin, albumin, hydroxyethyl cellulose, cellulose, oxidized cellulose, hydroxypropyl cellulose, carboxyethyl cellulose, carboxymethylcellulose, chitan, chitosan, alginate, poly(lactic acid), poly(glycolic acid), poly(hydroxybutyrate), poly(phosphazine), polyester, polyethylene glycol, polyalkyleneoxide, polyacrylamide, polyhydroxyethylmethylacrylate, polyvinylpyrrolidone, polyvinyl alcohol, poly(caprolactone), poly(dioxanone), polyacrylic acid, polyacetate, polycaprolactone, polypropylene, aliphatic polyester, glycerol, poly(amino acid), copoly(ether-ester), polyalkylene oxalate, polyamide, poly(iminocarbonate), polyalkylene oxalate, polyoxaester, polyorthoester, polyphosphazene or a combination of the foregoing.

16. The tissue thickness compensator of any preceding claim comprising a haemostatic agent, an anti-inflammatory agent, an antibiotic agent, an anti-microbial agent, an anti-adhesion agent, an anti-coagulant agent, a medicament, a pharmaceutically active agent, or a combination of the foregoing.

17. An article selected from an anvil of a stapling apparatus and a staple cartridge for a stapling apparatus, the article comprising:

the tissue thickness compensator of claim 1, the tissue thickness compensator comprising:

an outer layer comprising a non-porous material;

an inner layer comprising a porous material, a first encapsulated component comprising said first component and a second encapsulated component comprising said second component.

18. The article of claim 17, wherein:

the outer layer comprises polyglycolic acid, polylactic acid, polydioxanone, polyhydroxyalkanoate, poliglecaprone, polycaprolactone, or a combination thereof;

the porous material comprises oxidized regenerated cellulose, the first component comprises a first hydrogel precursor, and the second component comprises a second hydrogel precursor; and

wherein the reaction product is a hydrogel and the first hydrogel precursor and second hydrogel precursor are adapted to form said hydrogel to expand the tissue thickness compensator when the first encapsulated component and second encapsulated component are ruptured.

19. The article of Claim 17 or Claim 18, wherein the article defines at least part of a staple-forming path to be followed by a staple from the cartridge to an anvil or from a cartridge to the anvil as the case may be, and wherein the first and second encapsulated components are aligned with the staple-forming path so that a staple following that path punctures or otherwise ruptures the encapsulations.

20. A method of forming *in situ* an expanding tissue thickness compensator using the tissue thickness compensator of claim 4, the method comprising:

rupturing the first encapsulated component and second encapsulated component to allow the *in situ* reaction of the first encapsulated component and second encapsulated component to form said reaction product;

wherein the reaction product expands the tissue thickness compensator to compensate for different tissue thicknesses.

21. The method of claim 20, wherein:

the tissue thickness compensator comprises:

an outer layer comprising polyglycolic acid, polylactic acid, polydioxanone, polyhydroxyalkanoate, poliglecaprone, polycaprolactone, or a combination of the foregoing; and

an inner layer comprising oxidized regenerated cellulose;

the first encapsulated component comprises a first hydrogel precursor;

the second encapsulated component comprising a second hydrogel precursor; and

the reaction product comprises a hydrogel.


100
102
A
180
202
211
218
210
107
170
180
137
196
198
194
192
216
PD
214
212
40
108
139
56
106
120
54
136
164
134
135
162
132
130
110
DD
138
114
62
65
74
70
72
64
101
66
68
60
200
140
172
50
52
17
47
176
18
26
24
12
45
16
D
15
21
13
109
20
31
30
14
10
50
A
40
22
36

FIG. 1



FIG. 1A



FIG. 1B FIG. 1C FIG. 1D FIG. 1E



FIG. 2



FIG. 3



FIG. 4



FIG. 5


690
680
626
624
903
909
902
644
922
922
930
905
904
906
910'
612'
900
922
922
920

FIG. 6


904
903
909
907
902
900
922
922
922
922
922
612'
920
905
930

FIG. 7


922
900'
922
922
922
922
922
922
S
920'
930'

FIG. 8



FIG. 9



FIG. 11



FIG. 10



FIG. 13



FIG. 12



FIG. 14



FIG. 15



FIG. 16



FIG. 17



FIG. 18A FIG. 18B FIG. 18C FIG. 18D



FIG. 19A



FIG. 19B



FIG. 19C



FIG. 19D



FIG. 22



FIG. 21



FIG. 20


1200
1220
1211
1212

FIG. 23


1200
1220
1221
1222
1205
1210
1211
1212
1218
1219
1206
1208
1207

FIG. 24


1320
1311
1312
1320
1321
1322
26
26
1321
1320
1320
1321
1322
1320
1321
1322
1300
1321
1322
1320
1310
1318

FIG. 25


1300
1311
1310
1312
1320
1311
1320
1322
1311
1311
1312
1320

FIG. 26


1400
1411
1412
1420
1421
1422
28
28
1420
1421
1422
1420
1421
1422
1420
1421
1422
1410
1420

FIG. 27


1400
1412
1420
1420
1411
1421
1422
1411
1412
1420
1420

FIG. 28



FIG. 30



FIG. 33



FIG. 29



FIG. 31



FIG. 32

FIG. 34



FIG. 35



FIG. 36





FIG. 37



FIG. 38



FIG. 39



FIG. 40


1900
1911
1934
1940
1933
1930
1912
1910
1931
1920
1903
1931
1920
1934
1941
1933
1930

FIG. 41


T
2040
2033
2031
1920
2030
2031
1920
2030
1911
2041
2033
1912

FIG. 42


2150
2151
2152
2143
2108
2136
2130
2106
2146
2138
2140
2120
2118
2120
2131
2141
2105
2110
2137
2145
T
2119
2107
2135
2100

FIG. 43


2150
2151
2152
2143
2136
2106
2146
2138
2120
2140
2131
2141
2130
2120
2110
2105
2137
2145
T
2135
2100

FIG. 44


2151
2150
2152
2143
2146
2107
2136
2130
2105
2138
2119
2120
2140
2118
2120
2131
2141
2110
2137
2145
2108
2135
2106
2100

FIG. 45



FIG. 47



FIG. 46



FIG. 49



FIG. 48



FIG. 51



FIG. 53



FIG. 50



FIG. 52


2201b
2260
2212
2211
2200
2220a
2203
2220b
2932a
2932b
2435
2931
2242
2240
2249
2930
2939
2242
2211
2220a
2220b
2932a
2932b
2201a

FIG. 54



FIG. 55

FIG. 56

FIG. 57



FIG. 59

FIG. 58


3500
3519
3511
3508
3512
3510
3513
3509
3511
3521
3523
3520
3522
3521
3509
3523
3521
3522
3523
3508
3509

FIG. 60


T
3519
3500
M
3521
M
3520
3521
M
3521
M
3520
M
M
3521
M
3520
T
3511
3512
3513
3511

FIG. 61



FIG. 62



FIG. 63



FIG. 64



FIG. 65


3800
3811b
3808
3803
3821
3812
3803
3808
3821
3811
3821
3811a
3809
3810
3808

FIG. 66


3900
3808
3811b
3811
3803
3921
3803
3812
3808
3921
3821
3910
3811a
3809

FIG. 67



FIG. 72



FIG. 68



FIG. 71



FIG. 69



FIG. 70


4130
4180
4181
4163
4160
4163
4120
4162
4162
4163
4120
4163
4110
4170

FIG. 73



FIG. 73A



FIG. 74



FIG. 75



FIG. 76



FIG. 77



FIG. 81



FIG. 80



FIG. 79



FIG. 78



FIG. 82



FIG. 83



FIG. 84


4427
4421
4429
4426
4422
A
4421
4422
4429
4427
4426
B
4421
4429
4427
4422
4426
C

FIG. 85


4540
4511
4520
4520
4511
4512
4512
4510
4582
4582
4530
4580
4583
4583

FIG. 86



FIG. 88



FIG. 87



FIG. 89



FIG. 91



FIG. 90



FIG. 92



FIG. 94



FIG. 95



FIG. 93



FIG. 96B



FIG. 96A



FIG. 96D



FIG. 96C



FIG. 97



FIG. 98



FIG. 99



FIG. 100



FIG. 101



FIG. 102



FIG. 103


5458
5455
5455
5454
5453
5455
5453
5450
5454
5452
5456
5453
5454
5453
5455
5455
5453
5453
5454
5455
5455
5455

FIG. 104



FIG. 105



FIG. 107



FIG. 106



FIG. 108



FIG. 109



FIG. 110



FIG. 111


6252
6221
6221
6222
6252
6262
6221
6252
6262
6221
6252
6222
6221
6262
6220
6261
6262
6252
6260
6221
6262
6222
6220
6264
6262
6250
6200

FIG. 112


6252
6250
6252
6252
6252
6202
6257
6202
6252
6251
6202
6202
6252
6252
6202
6202

FIG. 113


6260
6261
6262
6203
6203
6262
6262
6203
6268
6203
6262
6262
6203
6203
6262
6262
6203
6203
6262
6262
6203
6203
6262
6264

FIG. 114


6200
6252
6221c
6202
6253
6220c
6202
6252
6253
6221b
6202
6222c
6250
6252
6221c
6252
6202
6257
6222b
6252
6202
6253
6221a
6220b
6221b
6252
6202
6220a
6222a
6252
6221a
6253

FIG. 115


6201
6253
6202
6221c
6252
6253
6252
6221
6221b
6202
6252
6202
6252
6221c
6201
6202
6253
6221a
6252
6253
6253
6252
6221b
6202
6201
6221a
6253
6251
6252
6250
6201

FIG. 116


6221c
6252
6263
6262
6222c
6220c
6222b
6220b
6222a
6220a
6221b
6221a
6257
6251
6264
6250
6200
6261
6260

FIG. 117


6253
6252
6201
6263
6221b
6262
6202
6220b
6222b
6250
6252
6263
6262
6203
6221a
6221c
6253
6252
6262
6222a
6202
6220a
6253
6203
6201
6262
6253
6261
6221b
6252
6263
6203
6202
6260
6253
6262
6264
6221a
6252
6263
6251
6257

FIG. 118


6257
6250
6251
6252
6201
6221
6256
6253
6252
6221
6256
6253
6252
6201
6221
6256
6253

FIG. 119


6221
6221
6252
6252
6253
6257
6253
6251
6201
6220
6262
6262
6263
6263
6261
6264
6260
6222

FIG. 120


6250
6270
6270
6270
6221
6270
6270
6260
6221
6270
6270
6221
6270
6270
6257
6221
6261
6221

FIG. 121



FIG. 122


6270
6250
6202
6270
6221
6263
6260
6262
6222
6220
6263
6262
6222
6203
6263
6262
6261
6221
6270
6202
6270
6202
6270
6253
6253
6250
6270
6202
6270
6257
6251
6221
6203
6263
6262

FIG. 123


6221
6271
6272
6262
6263
6222
6270
6270
6272
6221
6262
6222
6252
6263
6270
6221
6262
6271
6201
6263
6270
6221
6262
6272
6263
6222
6250
6270
6272
6262
6263
6221
6251
6257
6261
6260

FIG. 124



FIG. 125



FIG. 126



FIG. 127



FIG. 128



FIG. 129



FIG. 130



FIG. 131



FIG. 132



FIG. 133



FIG. 134



FIG. 135



FIG. 136



FIG. 137



FIG. 138



FIG. 139



FIG. 140



FIG. 141



FIG. 142



FIG. 143



FIG. 144



FIG. 145


6640
6670
6672
6679
6671
6678
6670
6220
6257
6673
6672
6220
6220
6671
6250
6251
6257
6220
6220
6260
6251
6250

FIG. 146


6670
6675
6672
6676
6671
6673
6220
6676
6221
6221
6252
6221
6260
6221
6222
6252
6257
6250

FIG. 147



FIG. 148



FIG. 149


6201
6201
6250
6252
6251
6870
8673
T
T
6221
6221
6260
6222
6220
6220

FIG. 150



FIG. 151



FIG. 152



FIG. 153



FIG. 154



FIG. 155



FIG. 156



FIG. 157



FIG. 158



FIG. 159


6980
6940
6949
6949
6918
6270
6270
6980
6917
6250
6251
6917
6917
6917
6918
6251
6250
6918
6918
6221
6221
6900
6220
6220
6910
6260
6913
6260
6916
6916
6913
6930
6939

FIG. 160


7030
6237
6244
6235
6243
6236
7046
7045
7049
7032
7060
7000
7030
6220
7012
7046
7040
7011
7010
7031
7050
7045
7047
7048
7041

FIG. 161



FIG. 162


7052
7052
7055
7050
7057
7055
7057
7054
7055
7053
7046
7054
7054
7051
7053
7053
7045
7062
7062
7060
7065
7065
7065
7063
7067
7064
7063
7064

FIG. 163


7062
7046
7060
7045
7062
7050
7057
7060
7050
7055
7057
7052
7055
7063
7063
7054
7054
7054
7054

FIG. 164


7051
7061
7065
7065
7062
7062
7060
7065
7065
7045
7051
7046
7052
7052
7055
7055
7050
7057
7057
7055
7055

FIG. 165


7049
6244
7065
7060
6243
7041
7065
7040
7071
7070
7072
7071
7072
7055
7050
7071
7055
7048

FIG. 166


7040
7071
7041
7072
7071
7070
7072
7055
7053
7050
7054
7071
7055
7048
6250
T
7033
6221
6220
6222
7012
7033
6221
6220
6222
7012

FIG. 167


7040
7071
7070
7041
6221
6220
T
6222
7012
7033
7055
7053
6221
6220
6222
7012
7033
7050
7072
7054
7055
7072
7071

FIG. 168


7040
7071
7072
7055
7053
6250
T
6220
7050
7071
7033
7012
7070
7055
7054
6221
7071
7072

FIG. 169


7040
7065
7041
7070
7071
7072
6250
6220
6221
6222
7071
7060
7065
7064
7072
7071
7050
7072
7071
7063
7055
7055
6221
6220
6222
7033
7012

FIG. 170



FIG. 172



FIG. 175



FIG. 171



FIG. 173



FIG. 174



FIG. 177



FIG. 176



FIG. 178


8038
8154
8042
8041
8036
8026
8034
8020
8030
8022
8024
8010
8018
8012
8016
8014

FIG. 179


8012
8014
8016
8024
8022
8018
8210
8318
8034
8204
8202
8026
8020
8042
8010
8154
8038
8036

FIG. 180


8028
8070
8024
8018
8022
8032
8269
8408
8264
8266
8271
8010
8298
8303
8268
8131
8195
8250
8289
8254
8301
8256
8294
8196d
8194
8324
8332
8322
8318
8285
8328
8277
8279
8276
8275
8296
8040
8156
8154
8020
8036
8300
8297
8326
8320
8291
8063
8292
8248
8330
8270
8272
8280
8210
8034
8278
8204
8026
8042
8516
8234
8500
8522
8525
8220
8231
8502
8230
8232
8506
8206
8274
8166
8168
8202
8164
8160
8246
8170
8171
8192
8190
8188
8184
8186
8150
8194
8031
8030
8293
8234
8152
8202
8200
8222
8196b
8284
8196c
8290
8174
8282
8038
8172
8173
8041
8158
8154
8036

FIG. 181


8032
8264
8277
8034
8210
8280
8026
8278
8276
8202
8158
8154
8042
8184
8036
8010
8318
8204
8020
8038

FIG. 182


8250
8010
8292
8162
8298
8296
8294
8220
8042
8318
8516
8230
8506
8204
8154
8200
8158
8282
8284
8138
8290
8192
8184
8036
8026
8034
8202
8210
8270
8285
8324
8293

FIG. 183


8032
8264
8268
8324
8210
8318
8204
8284
8248
8320
8158
8010
8034
8026
8282
8290
8036

FIG. 184


8032
8264
8268
8324
8280
8210
8318
8276
8278
8204
8202
8034
8026
8279
8184
8042
8336
8334
8158
8154
8038
8010

FIG. 185



FIG. 186


8154
8156
8524
8297
8294
8248
8301
8254
8295a
8295b
8295
8296
8298
8299

FIG. 187


8042
8295
8297
8292
8290
8294
8293
8296
8299
8300
8301
8302
8298
8254
8154
8156

FIG. 188



FIG. 189


8500
8502
8042
8516
8522
8506
8518
8514
8510
8610
8220
8512
8232
8520
8508
8231
8230
8234

FIG. 190


8042
8502
8220
8232
8234
8518
8414
8516
8512
8522
8520
8231
8230

FIG. 191



FIG. 192



FIG. 193



FIG. 194



FIG. 195


8295a
8604
8612
8610
8606
8402
8600
8608
8294a
8400
8293
8248a
8296
8302
8301
8300
8254
8292
8299
8298
8010a

FIG. 196


8232
8248a
8400
8010a
8612
8606
8610
8608
8604
8294a
8298
8254
8301
8220a

FIG. 197



FIG. 198



FIG. 198A



FIG. 199



FIG. 199A



FIG. 200



FIG. 200A



FIG. 201



FIG. 201A



FIG. 202


9016
9010
9078
9012
9022
9080
207
210
9110
9154
9128
9152
9094
209
9090
9102
209
9126
9024
9124
9020
210
9230
9018
207

FIG. 203


9078
9016
9012
9080
9076
9070
9022
9142
9144
9072
9140
9142
9094
9092
9138
9090
9110
9136
9102
9126
9112
9114
9074
9230
9020
9220
9222
9024
9023
9018

FIG. 204



FIG. 206

FIG. 205


9140
9144
9070
9094
9090
9078
9076
9072
9138
9102
9130
9010
9150
9136
9112
9114
9110
9022
9154
9026
9018
9020
9028

FIG. 207


9016
9010
9078
9080
9022
9154
9110
9118
9152
9116
9090
9120
9094
9130
9102
9112
9240
9114
9132
9018
9133
9134

FIG. 208


9012
9023
9222
9204
9018
9208
9220
9216
9206
9202
9110
9102
9116
9126
9134
9132
9124
9204
9218
9133
9114
9020
9230
9210
9206

FIG. 209



FIG. 210



FIG. 211



FIG. 212



FIG. 213



FIG. 214



FIG. 215


10001
10010
10014
10025
10020
10014
10025
10021
10014
10025
10025
10026
10002
10000

FIG. 216



FIG. 217


10021
10022
10000
10024
10025
10024
10025
10020
10024
10052
10001
10052
10011
10012
10050
10028
10010
10015
10026
10014
10012
10026
10014
10028
10012
10028
10027
10032
10027
10030
10002
10032
10031
10031
10040

FIG. 218


10020
10021
10000
10052
10001
10052
10012
10050
10015
10028
10011
10012
10026
10028
10014
10026
10028
10013
10028
10027
10030
10027
10014
10040
10002

FIG. 219


10001
10010
10013
10015
10014
10013
10011
10014
10012
10030
10013
10014
10030
10012
10013
10013
10002

FIG. 220



FIG. 221



FIG. 222



FIG. 223



FIG. 224



FIG. 225


10024
10025
10222
10024
10025
10024
10025
10223
10223
10021
10223
10223

FIG. 226


10015
10001
10010
10030b
10011
10012
10040
230
10030a
10030b
10040
10030c
10030d
10030e
230
10030f
10014
10002
10000
10020

FIG. 227



FIG. 228



FIG. 229


10000
10030
10022
10020
10011
10012
10032
10031
10041
10014
10010
10026
10040
10027
10030
10030
10015
10030
10027
10030
10020
10022
10032
10014
10031
10041
10026
10010
10040

FIG. 230



FIG. 231



FIG.232



FIG. 233



FIG. 234


10032
10011
10012
10013
10013
10016
10032
10012
10013
10030
10032
10016
10032
10030
10012
10010
10013
10012
10031
10041
10031
10041
10040
10040

FIG. 235



FIG. 236



FIG. 237


10052
10058
10054
10053
10050
10060
10030
10040
10010
10030
10040
10721
10720
10003
10002
10700
10004

FIG. 238



FIG. 239



FIG. 240



FIG. 241



FIG. 242



FIG. 243



FIG. 244



FIG. 245



FIG. 246



FIG. 247



FIG. 248



FIG. 249



FIG. 251



FIG. 250



FIG. 253



FIG. 255



FIG. 252



FIG. 254



FIG. 257



FIG. 256



FIG. 258



FIG. 259



FIG. 260



FIG. 261



FIG. 262



FIG. 263



FIG. 264



FIG. 265



FIG. 266



FIG. 267


16670
16620
16624
16625
16605
16606
16602
16660
16604
16600
16603

FIG. 268



FIG. 269



FIG. 270



FIG. 272

FIG. 271



FIG. 273



FIG. 274


11170
11101
10012
11119
11119
11119
11160
11120
11111
11110
11102
10012
11100

FIG. 275



FIG. 276



FIG. 277



FIG. 279



FIG. 278



FIG. 282



FIG. 280 FIG. 281


11212
11216
11213
11210
11213
11212
11213
11216
11213
11216
11213
11216
11213
10032
11212
11213
11212
10030
11213
10032
11213
11216
11212

FIG. 283


11260
11220
10031
11213
11213
10040
11210
10032
10030
11212
10030
10032
10032
11213
11212
10030
10032
10032
10050
11211
10032
10030
10052
10040
10040
T
T
11213
11220
11213
10030
10032
10031

FIG. 284


T
T
11220
10030
10030
11213
10040
11211
11212
11210
10040
11213
10040
11211
11212

FIG. 285


14700
14710
14723
14720
14723
14721
14722
10012
10012
14711
14715

FIG. 286



FIG. 287



FIG. 288


11300
11313
11316
11310
11313
11316
11313
11316
11320
10030
10030
10040
10040
11313
10030
11310
10030

FIG. 289


T
11320
11316
11313
10040
11310
10030
11360
10030
10030
10030
T
11316
11313
10040

FIG. 290


11360
T
11320
11313
10040
11310
10030
10040
10030
10040
11313
10040

FIG. 291


11418
11413
11418
11411
11416
11419
11410
10040
11452
10030
11453
10030
11420
11413
11418
11416
11419
10040
11400

FIG. 292


11420
11418
11416
11413
11418
11419
11400
T
11410
11460
11452
10030
10030
11419
11418
11413
11416

FIG. 293


11460
T
11420
11411
11410
11419
11416
11418
11413
10030
10040
11418
11419
11413
11416
11418

FIG. 294


11400′
11420
11418′
11413′
11417′
11411
11417′
11418′
11419′
11410′

FIG. 295



FIG. 296

FIG. 296A



FIG. 297



FIG. 298


15320
15321
15311
15322a
15322b
15330
15340
15322c
15326
15310
15370
15300

FIG. 299



FIG. 300



FIG. 301


11520a
11501
10030
10040
11520b
11560
10050
11520d
11520c
11520e
11510
11503
11502
T

FIG. 302



FIG. 303

FIG. 304



FIG. 305



FIG. 306



FIG. 307



FIG. 308


10688
10608
10610
10600
10620
10688
10608
10060
10695
10065
10690
10686
10685
10680

FIG. 309


10693
10695
10693
10690
10691
10692
10694
10682
10685
10686
10688
10065
10060
10610
10611
10608
10670
10620
10608
10603
10688
10686
10680
10684

FIG. 310


12185
10087
12185
10082
12185
10088
10080
10089
12195
12190
12192
12197
12196

FIG. 310A


10013
10715
10013
10710
10060
10065
10782
10786
10781
10780
10790
10794
10785
10795
10791
10792

FIG. 311


10013
10012
10013
10810
10800
10820
10880
10895
10060
10895
10065
10890
10895
10891

FIG. 312



FIG. 313



FIG. 314



FIG. 314B

FIG. 314A



FIG. 315

FIG. 316



FIG. 317


10010
10088
12298
12295
10000
10020
10088
12280
10089
10060
12298
12295
12298
12295
12298
12295
12298
12295
12298
12295
12291
10065
12290
10084

FIG. 318



FIG. 319



FIG. 320



FIG. 321

FIG. 322


10052
11660
10053
10050
11601
11618
11618
11616
11615
11620b
11620a
11620c
11613
11618
11616
11613
11620d
11620
11620e
11616
11613
11600
11618
11610
11602

FIG. 323



FIG. 324



FIG. 325



FIG. 326



FIG. 327



FIG. 328


13022
13021
13010
13024
13060
13020
13022
13000
13024
13025

FIG. 329



FIG. 330



FIG. 331



FIG. 333



FIG. 335



FIG. 332



FIG. 334



FIG. 337



FIG. 338



FIG. 336



FIG. 339



FIG. 340



FIG. 341



FIG. 342



FIG. 343



FIG. 344



FIG. 345



FIG. 346



FIG. 347



FIG. 348



FIG. 349

FIG. 350



FIG. 351



FIG. 353



FIG. 352



FIG. 355



FIG. 354



FIG. 356



FIG. 357



FIG. 358



FIG. 359



FIG. 360



FIG. 361



FIG. 362



FIG. 363



FIG. 364



FIG. 365



FIG. 366



FIG. 367


14520
14520C
10032
C
10032
14520B
B
A
14529
14521
14520A
14520B
14520C
10032

FIG. 368


14620
14621
14629
14620C
14626C
14625B
14620B
14626B
14625A
14620A
14626A
C
B
A

FIG. 369


12570
12552
12528
12526
12528
12510
12528
12560
12500
12520
10012

FIG. 370



FIG. 371



FIG. 373

FIG. 372



FIG. 374



FIG. 376

FIG. 375



FIG. 377

FIG. 378



FIG. 379

FIG. 380

FIG. 381



FIG. 382

FIG. 383



FIG. 384



FIG. 385



FIG. 387



FIG. 389



FIG. 386



FIG. 388



FIG. 390



FIG. 391



FIG. 392



FIG. 393



FIG. 394



FIG. 395



FIG. 397



FIG. 396



FIG. 398



FIG. 399A



FIG. 399



FIG. 399B



FIG. 400

FIG. 401



FIG. 402



FIG. 403



FIG. 404


20826
20015
20010
20887
20072
20011
20880
20886
20820
20000
12
20825
20889
20070
20002

FIG. 405



FIG. 406


20080
20026
20020
20086
20021
20050
20028
20082
20052
20022
20001
20000
20025
20011
20051
20126
20010
20012
20126
20017
20002
20030
20040

FIG. 407


20001
20010
20011
20017
20040
20012
20040
20012
20040
20015
20030
20086
20126
20020
20080
20021
20025
20002

FIG. 408



FIG. 409



FIG. 410



FIG. 411



FIG. 412


30015
30052
30050
30011
30017
30070
30092
30072
30082
30000
30083
30098
30010
30085
30060
30020
30084
30080
12

FIG. 413



FIG. 415





FIG. 414


A
31080
31086
31098
31082
31084
31088
31080
31086
31098
31082
31084
31088

FIG. 416



FIG. 417



FIG. 418



FIG. 419



FIG. 420



FIG. 421


34090
34094
34090
34094
34090
34094
34090
34094
34090
34094
34096
34090
34094
34090
34094
34090
34096

FIG. 422



FIG. 423



FIG. 424



FIG. 425



FIG. 426



FIG. 427



FIG. 428



FIG. 429



FIG. 430



FIG. 431



FIG. 432


12
T
T
40092
40080b
30012
30040
30010
30000
30062
30060
30015
30062
40020
40080a
40092
30030
30040

FIG. 433


12
30062
T
30030
T
40092
40080b
30040
30012
30010
30000
30060
30015
30062
T
T
40092
40020
40080a
30030
30040
30012

FIG. 434


12
T
T
30062
30060
41080b
30012
30030f
30030e
30030d
30040
30010
30000
30015
30062
40020
41080a
30012
30030a
30030b
30030c
30040

FIG. 435


12
T
30062
30030e
T
41080b
30030d
30030c
30040
30012
30010
30000
30060
30070
30015
30062
41020
30030a
30030b
30030c
30040
30012
30072
41080a

FIG. 436


12
T
T
30062
30062
30060
41080b
41120
41080a
41126
30030
30030
30040
30040
30010
30072
30000
30070
30015

FIG. 437


12
T
30062
T
42080
30012
30030
30072
30040
30010
30000
30060
30015
30062
42020
42080
30012
30030
30040
30070

FIG. 438


12
T
T
42080
30040
30012
30072
30010
30000
30070
30060
30015
30030
42020
42080
30040
30012

FIG. 439


30017
30050
30052
30015
30072
30010
30070
30000
43080
30011
43080
30060
12
43020

FIG. 440


12
T
T
30062
44080c
30012
30030
30072
30040
30010
30000
30070
30060
44080b
30015
30062
44020
44080a
30012
30030

FIG. 441


12
T
T
30062
44080c
30012
30030
30072
30010
30040
30000
30070
30060
44198
44184
30015
44080b
30062
44080a
30012
30030
44120

FIG. 442


12
T
T
30062
44224
44080c
44092
44098
30012
30030
30040
30072
30010
30000
30060
44092
30070
30015
44090
44092
44220
44080a
44080b
30012
30030
30062

FIG. 443


12
T
30062
T
44080c
44380b
30012
30030
30030d
30040
30072
30010
30000
30070
30060
44392
44381
30015
30062
44320
44080a
30012
30030
30030c

FIG. 444



FIG. 445



FIG. 446



FIG. 447



FIG. 448


30015
30050
30052
30011
30010
47024
47080
30072
30070
47020
30000
30060
12
30000

FIG. 449



FIG. 450



FIG. 451



FIG. 452



FIG. 453



FIG. 454


30015
30010
30052
30050
30011
30072
30070
48024
30000
30011
30060
48020
48080
30012
12

FIG. 455


12
30061
T
30062
48024
T
48080
30012
30030
30040
30072
30010
30000
30070
30015
30062
48020
30012
30030
30040

FIG. 456


12
T
T
30062
48024
48080
30040
30012
30072
30010
30000
30030
30060
30070
30015
30062
48080
48020
30012

FIG. 457



FIG. 458



FIG. 459



FIG. 460


49020
49080
49024
30030
30040
30000
30070
30012
30050
30060
30040
T
T
12

FIG. 461


30062
49020
49098
30030
30040
30012
30000
30070
30060
30050
49024
49080
T
T

FIG. 462


30030
50020b
50020
50080
50020a
50024a
30040
30000
30070
30030
30060
30050
30040
50098
30030
30012
50024a
50024b

FIG. 463


30062
50024b
50024c
50020
50024a
50080
30012
30030
30040
30072
30010
30000
30070
30060
30015
30062
50020b
T
T
50020a
50080
30012
30030
30040

FIG. 464


50020b
50020
50024b
50024c
T
T
50098
50080
30040
30012
30072
30010
30000
30070
30060
30030
30015
30030
50020a
50024a
30040
30012

FIG. 465


30060
30072
30050
30052
30015
30011
30010
51024
51083
30070
30000
51080
51020
51085
30000
12

FIG. 466



FIG. 467



FIG. 468


30050
51020
30052
51024
30030
51080
51083
51080
30030
51098
51087
51085

FIG. 469


51122
51024
51083
51130a
51136
51120
51130
51080
51185
51130b
51124
51130
51127
51126

FIG. 470



FIG. 471



FIG. 472



FIG. 473



FIG. 474


12
30000
52026
52024a
52024b
52020
52024
52080
30070
30011
30010

FIG. 475



FIG. 476



FIG. 478



FIG. 477



FIG. 479A



FIG. 479B



FIG. 479C



FIG. 479E



FIG. 479D


12
30060
30072
30010
30011
53024
53080
30070
30012
30000
53020

FIG. 480



FIG. 481



FIG. 482



FIG. 483


30015
30011
30010
53080
30012
30000
53024
53080
30012
30070

FIG. 484



FIG. 485



FIG. 486



FIG. 487



FIG. 488



FIG. 495



FIG. 496



FIG. 497



FIG. 492



FIG. 493



FIG. 494



FIG. 489



FIG. 490



FIG. 491



FIG. 499



FIG. 502



FIG. 501



FIG. 498



FIG. 500


62030
62022a
62022b
62022c
62022d
62022e
62022f
62020
62032a
62032b

FIG. 503


19080
19020
19024
19070
19024
19026
19012
19000
19011
19010
19060
19022
19022
19012
19016

FIG. 504


T
T
19011
19012
19000
19030
19070
19040
19060
19062
19022
19080
19026
19016
19080
19062
19022
19020
19010
19012
19030
19040

FIG. 505


19020
T
19022
T
19024
19040
19000
19012
19070
19030
19060
19080
19016
19026
19080
19062
19030
19022
19024
19010
19040
19012

FIG. 506


19080
19070
19220
19224
19200
19222
19011
19012
19060
19224
19222
19012
19010
19016

FIG. 507


19080
19060
19062
T
19224
T
19220
19010
19012
19030
19070
19200
19040
19222
19080
19016
19080
19062
19222
19224
19012
19030
19040

FIG. 508


19080
19060
19030
T
19220
T
19224
19222
19010
19040
19070
19200
19012
19080
19080
19030
19224
19222
19040
19012

FIG. 509


19080
19080
19121
19124
19120
19160
19126
19122
19126
19122
19070
19100

FIG. 510


18124
19122
T
19030
19040
19070
19122
19012
19160
19040
19120
19012
19040
19124
19012
19030
19100

FIG. 511


19122
19120
19124
19040
19012
19100
19160
19070
19030
19124
19122
19040
19012
19080

FIG. 512


19120
19122
19124
19062
19130
T
19040
19012
19100
19106
19070
19080
19124
19122
T
T

FIG. 513



FIG. 514



FIG. 515



FIG. 516



FIG. 517


70000
70010A
70010B
70010A
70010B
70010B
70010A
70010A
70010B
70010B
70010A

FIG. 518A



FIG. 518B



FIG. 519



FIG. 520



FIG. 521



FIG. 522



FIG. 523



FIG. 524


315/327
70180
70190C
70192
70190B
70185
70182
70183B
70183A
70182
70194
70190A

FIG. 525



FIG. 526



FIG. 527A



FIG. 527B



FIG. 528



FIG. 529


320/327
70425
70430
T
T
70415
70440A
70410
70440B
70435
70440C
70440D
70440E

FIG. 530



FIG. 531



FIG. 532A

FIG. 532B



FIG. 533


A
CHEMICAL COMPONENT(S)
B
CHEMICAL COMPONENT
C
EXPANDED TISSUE THICKNESS COMPENSATOR

FIG. 534



FIG. 535


HEMO-STATIC FIBRIN & THROMBIN
ANTIBIOTIC DOXYCPL
HEALING MMPS

FIG. 536



FIG. 537



FIG. 540



FIG. 539



FIG. 538