

(86) Date de dépôt PCT/PCT Filing Date: 2012/09/07
(87) Date publication PCT/PCT Publication Date: 2013/03/14
(85) Entrée phase nationale/National Entry: 2014/01/14
(86) N° demande PCT/PCT Application No.: NL 2012/050626
(87) N° publication PCT/PCT Publication No.: 2013/036124
(30) Priorité/Priority: 2011/09/09 (NL2007381)

(51) *Cl.Int./Int.Cl. B01D 53/52* (2006.01),
B01D 53/34 (2006.01), *B01D 53/58* (2006.01)

(71) **Demandeur/Applicant:**
 DUIKER COMBUSTION ENGINEERS B.V., NL

(72) **Inventeurs/Inventors:**
 BETLEM, MAARTEN, NL;
 OLSTHOORN, SJAAK, NL;
 VAN WELSEME, MARK, NL

(74) **Agent:** BROUILLETTE & ASSOCIES/PARTNERS

(54) Titre : PROCEDE POUR L'INCINERATION DE NH3 ET INCINERATEUR DE NH3
(54) Title: A PROCESS FOR INCINERATING NH3 AND A NH3 INCINERATOR




Fig. 1

(57) **Abrégé/Abstract:**

This invention relates to a process for incinerating NH_3 in an NH_3 incinerator comprising a first incineration step at controlled sub-stoichiometric incineration conditions and a second incineration step with at a greater than stoichiometric amount of oxygen, whereby a product stream is produced with reduced NO formation. The invention also relates to an NH_3 incinerator.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(10) International Publication Number
WO 2013/036124 A1

(43) International Publication Date
14 March 2013 (14.03.2013)

(51) International Patent Classification:

B01D 53/52 (2006.01) **B01D 53/34** (2006.01)
B01D 53/58 (2006.01)

(21) International Application Number:

PCT/NL2012/050626

(22) International Filing Date:

7 September 2012 (07.09.2012)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2007381 9 September 2011 (09.09.2011) NL

(71) Applicant (for all designated States except US): **DUIKER COMBUSTION ENGINEERS B.V.** [NL/NL]; 91, Turfschipper, NL-2291 JK Wateringen (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BETLEM, Maarten** [NL/NL]; 91, Turfschipper, NL-2292 JK Wateringen (NL). **OLSTHOORN, Sjaak** [NL/NL]; 91, Turfschipper, NL-2292 JK Wateringen (NL). **VAN WELSEME, Mark** [NL/NL]; 91, Turfschipper, NL-2292 JK Wateringen (NL).

(74) Agent: **KORTEKAAS, M.**; Exter Polak & Charlois B.V., P.O. Box 3241, NL-2280 GE Rijswijk (NL).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: A PROCESS FOR INCINERATING NH₃ AND A NH₃ INCINERATOR




Fig. 1

(57) Abstract: This invention relates to a process for incinerating NH₃ in an NH₃ incinerator comprising a first incineration step at controlled sub-stoichiometric incineration conditions and a second incineration step with at a greater than stoichiometric amount of oxygen, whereby a product stream is produced with reduced NO formation. The invention also relates to an NH₃ incinerator.

WO 2013/036124 A1

WO 2013/036124

PCT/NL2012/050626

Title: **A PROCESS FOR INCINERATING NH₃ AND A NH₃ INCINERATOR**

Technical field:

This invention relates to NH₃ incineration. More in particular, this invention relates to a process for NH₃ incineration with reduced NO formation, the controlling of such a process, and to a NH₃ incinerator.

5 Background Art:

NH₃ (ammonia) is a corrosive, colourless gas with a sharp odour. It occurs naturally and is also manufactured by the chemical industry. Waste gas streams comprising ammonia are frequently encountered in refineries. Sometimes such waste gas streams also contain hydrogen sulphide in comparable proportions.

- 10 NH₃ may be processed in a NH₃ incineration process, or alternatively in a Claus process. These two routes to NH₃ destruction are different in terms of equipment requirements, in chemistry and in process conditions. Both achieve the destruction of NH₃. Thus, H₂S gas streams containing NH₃ can be employed as a feed stream in a Claus process. The Claus process is a gas desulphurising process, recovering elemental sulphur from gaseous
- 15 hydrogen sulphide. Moreover, the Claus process is a very efficient process to convert NH₃ in the presence of H₂S and SO₂ with little or no production of NO.

- Downside of the Claus process is the formation of ammonium salts when a feed is used that comprises NH₃ in addition to H₂S. A Claus furnace that is adapted for handling the presence of NH₃ is therefore run at a higher temperature (typically with increased
- 20 temperature of at least 1250°C). Moreover, the amount of oxygen required when using a mixed gas stream versus a relatively pure H₂S stream is significantly higher, thereby increasing the operational and investment costs.

According to WO2006106289 a gas stream comprising hydrogen sulphide and ammonia is passed from a stripping column to a single combustion stage or furnace of a Claus plant.

- 25 The combustion is conducted under conditions that eliminate essentially all the ammonia. The combustion is supported by a gas stream containing at least 40% by volume of oxygen. In WO2008124625 oxidative and reductive methods are described for the cost-effective destruction of an ammonia-containing gas stream, potentially containing minor but significant quantities of hydrogen sulphide, in a conventional Claus sulphur recovery tail gas
- 30 treating unit, using controlled rates and compositions of combustion gases in order to obtain the temperatures necessary for the desired destruction of unwanted combustibles.

In US 6902713 a partial oxidation procedure is described for gas containing hydrogen sulphide and ammonia in a Claus furnace with the aid of an oxygen-rich gas. The procedure involves measuring the residual content of ammonia at the output from the furnace, i.e., after the various stages of the Claus process and irrespective of the yield and conversions
5 during the Claus process, comparing this value with a maximum value set by the user of the Claus unit, and modifying the flow of the oxygen-rich gas in proportion to the flow of ammonia gas accordingly. The residual ammonia content is measured continuously by means of a laser diode located in the main duct or a branch sampling pipe at the outlet from the Claus furnace, with the gases from the sampling pipe re-injected into the main duct, and
10 the flow of oxygen rich gas is modified by means of a regulating loop between the continuous measuring apparatus and an automatic controller for the regulator. This sour gas stream may contain up to 60 mol% ammonia and contains significant amounts of hydrogen sulphide.

Although the above mentioned processes for treating waste streams containing hydrogen
15 sulphide and ammonia have the advantage of eliminating essentially all the ammonia, unfortunately a Claus furnace is not always available. Moreover, a typical Claus furnace is rather complex, comprising several stages for partial combustion of hydrogen sulphide and for carrying out the Claus reaction of hydrogen sulphide with sulphide dioxide to form elemental sulphur, several condensers to recover elemental sulphur, and several reheaters
20 to warm up the remaining gases prior to subsequent reactions. In other words, although in the aforementioned references improved Claus processes and furnaces have been described that make possible the virtual complete incineration of NH_3 without NO , the downside is the investment of a relatively expensive Claus furnace and the equipment downstream of the Claus furnace, moreover run at relatively high operational costs. Finally,
25 as is shown in US6902713, even a Claus process generally requires an incinerator for treatment of the tail gas of the Claus process.

A dedicated NH_3 incinerator is more attractive than a Claus process for the treatment of waste gas streams comprising NH_3 as the major or sole combustible component. However, the problem of NH_3 incinerators is that oxides of nitrogen may be formed during the
30 combustion. There is a need to destroy essentially all of the ammonia in such gas streams but without creating appreciable amounts of oxides of nitrogen in the effluent gas arising from the incineration process.

In GB2116531 a process and apparatus is described for the simultaneous disposal of NH_3 containing waste gas and combustible sulphur compounds-containing waste gas. In this
35 process combustion is carried out in three separate steps, with the combustion of the sulphur compounds-containing waste gas in the third step. In a first incineration step, the waste gas containing NH_3 is combusted in the presence of a fuel gas with a first, sub-

stoichiometric amount of free oxygen in the incinerator. Next, the combustion gases are mixed with a second amount of free oxygen, the total of the first and second amount being super-stoichiometric and combusting the mixture in a second incinerator. No information is provided or suggested how to optimize the combustion efficiency with further reduced NO
5 formation.

In JP49042749 combustion of ammonia with air is described in two stages with intermediate cooling.

From EP 1106239 an alternative process is known. A gas stream containing at least 50% by volume of ammonia but less than 5% by volume of hydrogen sulphide is burned in a reaction
10 region which is supplied with oxygen and oxygen-enriched air. Both combustion and thermal cracking of ammonia takes place in the reaction region. The rate of supplying oxygen to the reaction region is from 75 to 98% of the stoichiometric rate required for full combustion of all combustible fluids supplied to the reaction region; the ratio of oxygen to ammonia is therefore even less. The effluent from the reaction region is subsequently burned (with
15 preferably pure oxygen or oxygen enriched air) and discharged to the atmosphere. Under these conditions essentially no ammonia remains in the effluent gas whereas formation of oxides of nitrogen can be minimised. This process therefore requires pure oxygen or oxygen enriched air. A process for incinerating NH₃ that does not rely on pure oxygen or oxygen enriched air would be more attractive. Still it would be desirable to reduce the amount of NO
20 to 100 ppm or less, preferably less than 50 ppm.

The current inventors set out to optimize the process for incinerating NH₃, e.g., a stream containing at least 30 vol% NH₃ and preferably containing no more than 40 vol% H₂S, whereby NO formation is reduced to less than 100 ppm NO. This problem has been solved as follows.

25 **Disclosure of the Invention:**

The invention provides a process for incinerating NH₃ in an NH₃ incinerator comprising:

- a. a first incineration step comprising:
 - i. reacting a gas stream comprising NH₃ and optionally a fuel stream under incineration conditions with a first oxygen containing stream, at a sub-stoichiometric amount of oxygen in
30 the first oxygen-containing stream with respect to the NH₃ in the gas stream, whereby a first product stream is produced;
 - ii. analyzing the composition of the first product stream for content of residual NH₃ and/or formed HCN and/or formed NO, and
 - iii. adjusting the first oxygen-containing stream and/or the gas stream comprising NH₃
35 and/or the fuel stream, if any, based on the analysis of the first product stream so as to produce a first product stream containing both residual NH₃ and NO, but no more than 250 ppm HN₃ and no more than 250 ppm NO; and

- b. a second incineration step comprising
 - i. reacting the first product stream under incineration conditions with a second oxygen-containing stream at a greater than stoichiometric amount of oxygen, whereby a second product stream is produced.

- 5 The process is particularly suitable for waste gas streams containing significant amounts of NH₃ and relatively low amounts of H₂S, if any. Also provided is an NH₃ incinerator suitable for the process according to the invention.

Brief description of the drawings:

Figure 1 is a simplified representation of the NH₃ incinerator of the current invention.

- 10 Shown is an NH₃ incinerator comprising a first reactor zone **100** comprising: a burner **110** for incinerating NH₃; an inlet **120** at the burner **110** for a first oxygen-containing stream (**B**), provided with a first oxygen control means **121** for adjusting the amount of the oxygen-containing stream; an inlet **130** at the burner **110** for a gas stream (**A**) comprising NH₃ optionally provided with a first NH₃ control means **131** for adjusting the amount of the NH₃-
 - 15 containing stream; optionally an inlet **140** at the burner **110** for a fuel stream (**C**) optionally provided with a first fuel control means **141** for adjusting the amount of the fuel stream; an outlet **160** downstream of the reaction zone **100** for a first product stream prepared in the reaction zone **100**; an analyser **170** at the end of the reaction zone **100** capable of analyzing the content of NH₃ and/or HCN and/or NO in the first product stream prepared in the
 - 20 reaction zone **100** and capable of adjusting one or more of the first control means **121**, **131** and **141**; and optionally a temperature control means **180** downstream of the reaction zone **100** (e.g., in the form of a quench unit or waste heat boiler for recovery of reaction heat) ; and further comprising a second reaction zone **200** downstream of the reaction zone **100** for incinerating the first product stream prepared in the reaction zone **100**, comprising an inlet
 - 25 **230** at the start of the reaction zone **200** for the first product stream prepared in the reaction zone **100**; comprising an inlet **220** at the start of the reaction zone **200** for a second oxygen-containing stream (**B**), optionally provided with a second control means **221** for adjusting the amount of the second oxygen-containing stream; optionally comprising a second burner **210**; provided with an inlet **211** at the second burner **210** for a third oxygen-containing
 - 30 stream (**B**), and an inlet **212** at the second burner **210** for a second fuel stream (**C**); optionally an inlet **250** at the start of the reaction zone **200** for a waste stream (**D**); an outlet **260** downstream of the reactor zone **200** for a second product stream prepared in the reaction zone **200**; optionally an analyser **270** at the end of the reactor zone **200** capable of analyzing the content of oxygen in the second product stream prepared in the reaction zone
 - 35 **200** and preferably capable of adjusting the second control means **221**; and optionally a waste heat boiler **280** downstream of the reactor zone **200** for recovery of reaction heat.

Modes for carrying out the Invention:

Preferred embodiments are described herein below.

Incineration conditions are known. Typically, NH₃ is incinerated at atmospheric pressure.

The reaction is exothermic and typically reaches a temperature of about 1500 °C, depending
 5 on the additional components (e.g. added fuel) of the NH₃ containing stream. The process
 is particularly interesting for waste streams comprising at least 30 volume %, preferably at
 least 50 volume % NH₃, more preferably at least 60 volume % NH₃. The gas stream may
 comprise some H₂S, preferably at most 40 volume % H₂S, more preferably at most 5
 volume % H₂S. Gas streams containing more H₂S are more suitably treated in a Claus
 10 furnace. Suitable sources of NH₃ containing gas streams are for instance streams from a
 sour water stripper.

In Figure 1, a simplified representation of a NH₃ incinerator of the current invention is
 shown.

To start the reaction, a fuel stream is ignited together with oxygen in the reactor zone **100** to
 15 reach the desirable incineration conditions. For incinerating NH₃ in reactor zone **100** a
 temperature in the range of 950 to 1700°C, preferably in the range of 1200 to 1400°C is
 preferred. Below 950°C stable combustion of the NH₃-containing stream will be difficult.
 Above 1700°C, commonly applied refractory lining materials that are used for heat insulation
 are not suitable. After a suitable temperature has been reached an NH₃ containing stream is
 20 introduced. Fuel may be mixed with the NH₃ containing stream, whereupon it co-reacts with
 the first oxygen-containing stream. For instance, it is beneficial to add fuel if the NH₃
 containing stream contains water. The presence of water may reduce the exotherm reached
 in the reactor. The amount of fuel to NH₃ containing stream is therefore such as to maintain
 a reaction temperature in the range of 950 to 1700°C, preferably in the range of 1200 to
 25 1400°C. For the embodiment described hereafter, it is assumed that the NH₃ containing
 stream is substantially free from water. Addition of a fuel gas is therefore not required.
 Ideally NH₃ is incinerated without formation of NO or by-products such as HCN according to
 the following reaction:



Ideally, the weight ratio of NH₃ to oxygen is about 2:3 (i.e., 4*17 : 3*32). However, the
 content of the NH₃ in the NH₃ containing stream is typically less than 100%, whereas
 generally air from the plant is used as the oxygen containing stream at an oxygen content of
 35 about 20 vol%, rather than pure oxygen. Typically, the weight ratio of the NH₃ containing
 stream to the oxygen containing stream is therefore about 1:6. The content of the NH₃ in the
 NH₃ containing stream may fluctuate over time, however, as may the content of other

components. To maintain more or less steady state conditions, the analyser **170** adjusts the first control means **121** (e.g., a valve, or a series of valves) which modifies the amount of oxygen introduced in reaction zone **100**. In an alternative embodiment, the analyser **170** adjusts the first control means **131** which modifies the amount of NH₃ introduced in reaction zone **100**. In a further alternative embodiment, the analyser **170** adjusts the first control means **141** (which modifies the amount of fuel introduced in reaction zone **100**). Also a combination of adjusting two or more of the first control means is possible. If there are no other combustible components in the reaction zone **100**, then the oxygen is supplied at a rate to reach a level of 95 to 98% of the stoichiometric rate required for incineration of all the NH₃. If the NH₃ containing stream comprises additional combustible components, like fuel, then the amount of oxygen should be increased up to an amount of oxygen in the range of 50 to 99% of stoichiometry with respect to the combustible components that are present in the gas streams. Using the analyser **170** in accordance with the current invention has the advantage that the amount of reactants can be adjusted, despite the rather complex interrelation when there are multiple components and hence multiple reactions taking place at changing incineration conditions. For instance, the amount of oxygen may be adjusted by increasing the weight ratio of oxygen to the NH₃ containing stream. Alternatively, the air used as oxygen stream may be enriched in oxygen.

The oxygen-containing stream may be introduced thru one or more inlets, but introducing thru one inlet suffices. The residence time of the reactants in reaction zone **100** can be short, i.e. 1 second or less, even 0.2 seconds or less.

Various analysers may be used as analyser **170**. Preferably, the analyser **170** is a laser diode, which analyses the residual NH₃ content at the end of the reaction zone **100**. The analysis may be carried out at intervals and the like, or continuously. When a short response time is needed, for instance because of rapid changes in the content of the reactant feed streams, then the analysis is preferably continuously or semi-continuously (e.g., once every 5 seconds or at shorter intervals). The analysis may be carried out in a bypass or in the reaction zone **100**. In a bypass the conditions for analysing the first product can be kept constant, which improves the reliability. On the other hand, analysing in the reaction zone **100** provides a shorter response time to changes in the composition of the gas stream and hence better control of the incineration conditions.

In accordance with the current invention, NH₃ is incinerated in reactor zone **100** close to completion, but not entirely. There is still some residual NH₃. If the incineration is completed to the extent that the residual NH₃ content is (about) nil, then the production of NO has already started and it was found that the overall production of NO may be too high. If the incineration in reactor zone **100** is not carried out long enough, then the gas stream will have a high NH₃ content which will lead to a high NO content when this gas stream is combusted

in the reactor zone **200**. In other words, the inventors have found out that to reduce the NO in the end product, the reaction in the first stage should continue until some NO is produced. In a preferred embodiment the first oxygen-containing stream and/or any of the other reactant feed streams are adjusted to result in an NH₃ content in the first product stream of
5 less than 100 ppm, more preferably less than 50 ppm. Alternative analysers may be used, that adjust the first oxygen-containing stream on the basis of other components possibly present in the first product stream, such as HCN or NO. For instance, when a propane /air flame with a NH₃ content of 4 % is incinerated, resulting in HCN as a combustion product, then one or more reactant feed streams may be adjusted to result in a HCN content in the
10 first product stream of less than 1400 ppm preferably less than 1000 ppm. Likewise, one or more of the reactant feed streams may be adjusted to result in an NO content in the first product stream of less than 200 ppm, preferably less than 100 ppm.

A temperature is maintained in the second reaction zone **200** that is preferably in a range of from 800 to 1100°C, more preferably in the range of 850 to 1000°C. Oxygen is supplied in
15 an amount to ensure full incineration. If the reaction temperature as a result of the incineration of the combustible components in the first product stream drops below the lower limit, then it may be advantageous to add fuel. It may also be advantageous to quench the temperature in the reaction zone **200**, e.g., by adding water to any of the feed streams. As described in more detail hereinafter, a very effective use of the elevated temperature of the
20 first product stream is to warm a further waste stream which is then incinerated in reaction zone **200**.

The design of the incinerator burner **110** in the reaction zone **100** and the optional incinerator burner **210** in the reaction zone **200** is not particularly relevant. Various types of incinerator burners may be used. Preferably, a burner is used that mixes the combustible
25 stream(s) and the oxygen containing stream. The burner may be equipped with an ignitor. The design of the reaction zones **100** and **200** is not particular relevant either. In fact, the NH₃ incinerator may have both reaction zones as part of a single reactor vessel or comprise two separate reactor vessels that are connected.

The present invention also covers the NH₃ incinerator used in the process described above,
30 comprising a first reactor zone **100** comprising: a burner **110** for incinerating NH₃; an inlet **120** at the burner **110** for a first oxygen-containing stream, provided with a first oxygen control means **121** for adjusting the amount of the oxygen-containing stream; an inlet **130** at the burner **110** for a gas stream comprising NH₃ optionally provided with a first NH₃ control means **131** for adjusting the amount of the NH₃-containing stream; optionally an inlet **140** at
35 the burner **110** for a fuel stream optionally provided with a first fuel control means **141** for adjusting the amount of the fuel stream; an outlet **160** downstream of the reaction zone **100** for a first product stream prepared in the reaction zone **100**; an analyser **170** at the end of

the reaction zone **100** capable of analyzing the content of NH₃ and/or HCN and/or NO in the first product stream prepared in the reaction zone **100** and capable of adjusting one or more of the first control means **121**, **131** and **141**; and optionally a temperature control means **180** downstream of the reaction zone **100** (e.g., in the form of a quench unit or waste heat boiler for recovery of reaction heat); and further comprising a second reaction zone **200** downstream of the reaction zone **100** for incinerating the first product stream prepared in the reaction zone **100**, comprising an inlet **230** at the start of the reaction zone **200** for the first product stream prepared in the reaction zone **100**; comprising an inlet **220** at the start of the reaction zone **200** for a second oxygen-containing stream, optionally provided with a second control means **221** for adjusting the amount of the second oxygen-containing stream; optionally comprising a second burner **210**; provided with an inlet **211** at the second burner **210** for a third oxygen-containing stream, and an inlet **212** at the second burner **210** for a second fuel stream; optionally an inlet **250** at the start of the reaction zone **200** for a waste stream; an outlet **260** downstream of the reactor zone **200** for a second product stream prepared in the reaction zone **200**; optionally an analyser **270** at the end of the reactor zone **200** capable of analyzing the content of oxygen in the second product stream prepared in the reaction zone **200** and preferably capable of adjusting the second control means **221**; and optionally a waste heat boiler **280** downstream of the reactor zone **200** for recovery of reaction heat.

Each of the reaction zones **100** and **200**, the latter in particular, may be equipped with a waste heat boiler, to recover energy.

As mentioned above, in the second incineration step additional waste gasses may be introduced. Examples thereof include tail gasses from other processes, for instance the tail gas of a Claus unit. This is particularly beneficial as it allows the economical use of the heat of the reaction generated in the first incineration step to warm the relatively cold waste gasses.

The NH₃ incinerator of the current invention may comprise both reaction zones as part of a single reactor vessel. Alternatively, each reaction zone is a separate reactor vessel wherein both reactor vessels are connected. Preferably, the incinerator comprises one or more waste heat boilers, to reclaim energy. If there are additional combustible waste gases that need to be treated, then the incinerator preferably comprises an inlet **250** for such combustible waste gases. Finally, the NH₃ incinerator may be provided with an oxygen analyser **270** to adjust the second oxygen-containing stream and/or the third oxygen-containing stream, if any. This may be useful to adjust the amount of the second/third oxygen containing stream, thereby ensuring that at least a stoichiometric amount of oxygen, but preferably an excess amount of oxygen is present in the second incineration step. Preferably, the total amount of the second and/or third oxygen containing stream is such that a residual amount of at least

0.5 vol% oxygen is found in the second product stream. Additional analysers may be used, to ensure the second product stream may be safely released into the atmosphere.

Examples:

The following example is included for illustrative purposes only.

- 5 A NH₃ stream at a rate of 1.95 Nm³/hr was introduced together with a C₃H₈ stream at a rate of 0.034 Nm³/hr into reaction zone **100** of an NH₃ incinerator. Also introduced was a sub-stoichiometric amount of a first oxygen-containing stream at a rate of 6.9 Nm³/hr. A first incineration step took place at a temperature of approx 1000 °C, and at ambient pressure. The first product stream was reacted with a second oxygen-containing stream. The second
- 10 oxygen-containing stream was supplied at an amount greater than stoichiometric with the result that the oxygen content measured at the end of the reaction zone was 3 vol % (measured in dry flu gas). The second incineration step took place at a temperature of 840°C and at ambient pressure.

- Without analyser and thus without adjusting the oxygen feed ratio in the first incineration
- 15 step a second product stream was obtained having an NO content varying between 0 and 270 ppm and a NH₃ content varying between 0 and 275 ppm

- When the same experiment was repeated, but now with a laser diode used as analyser **170** set to adjust the oxygen feed ratio based on a residual NH₃ content downstream of the reaction zone **100** of 100 ppm, a second product stream was obtained having a NO content
- 20 of less than 50 ppm and a NH₃ content of 0 ppm.

- Model experiments (first incineration step only) were repeated twice in a similar fashion as described above. First, an NH₃ stream was incinerated, but now with an oxygen feed ratio wherein in the first incineration step a first product stream was obtained having an NO content of 0 ppm. In a second experiment an oxygen feed ratio was used to generate a first
- 25 product stream with an NH₃ content of 0 ppm. The first experiment shows that the formation of NO during the first stage can be avoided, but only at the detriment of insufficient NH₃ combustion. If this first product stream would be incinerated in a second step with greater than stoichiometric amounts of oxygen to achieve full NH₃ combustion, then the NO content would be greater than 50 ppm. In the second experiment the NO content is greater than 50
- 30 ppm already in the first product stream. Achieving a low NO content is no longer possible. Only if the first incineration is carried out to the extent that a limited amount of NO is produced, is it possible to achieve the desired results of the current invention. The results of these model experiments are set out in the below table.

	NH ₃ capacity Nm ³ /h	Air capacity Nm ³ /h	NH ₃ content ppm	NO content ppm
1	2.20	5.86	1172	0

WO 2013/036124**- 10 -****PCT/NL2012/050626**

2	2.06	5.98	2	1185
---	------	------	---	------

CLAIMS

1. A process for incinerating NH₃ in an NH₃ incinerator comprising:
 - a. a first incineration step comprising:
 - i. reacting a gas stream comprising NH₃ and optionally a fuel stream under incineration conditions with a first oxygen containing stream, at a sub-stoichiometric amount of oxygen in the first oxygen-containing stream with respect to the NH₃ in the gas stream, whereby a first product stream is produced;
 - ii. analyzing the composition of the first product stream for content of residual NH₃ and/or formed HCN and/or formed NO, and
 - iii. adjusting one or more of the streams based on the analysis of the first product stream so as to produce a first product stream containing both residual NH₃ and NO, but no more than 250 ppm HN₃ and no more than 250 ppm NO; and
 - b. a second incineration step comprising
 - i. reacting the first product stream under incineration conditions with a second oxygen-containing stream at a greater than stoichiometric amount of oxygen, whereby a second product stream is produced.
2. The process of claim 1, wherein the gas stream comprises at least 30 volume %, preferably at least 50 volume % NH₃, more preferably at least 60 volume % NH₃.
3. The process of claim 2, wherein the gas stream comprises at most 40 volume % H₂S, preferably at most 5 volume % H₂S.
4. The process of any one of claims 1 to 3, wherein the amount of oxygen is in the range of 50 to 99% of stoichiometry with respect to the combustible components that are present in the gas streams.
5. The process of claim 4, wherein NH₃ is the only combustible component and the amount of oxygen is in the range of 95 to 98% of stoichiometry with respect to the NH₃ in the gas stream.
6. The process of any one of claims 1 to 4, wherein the first product stream is analysed for residual NH₃ content.
7. The process of any one of claims 1 to 4, wherein the first product stream is analysed for formed HCN content.
8. The process of any one of claims 1 to 4, wherein the first product stream is analysed for formed NO content.

9. The process of claim 6, wherein one or more of the reactant stream, preferably the first oxygen-containing stream is adjusted such that the residual NH₃ content of the first product stream is less than 100 ppm.
10. The process of claim 7, wherein one or more of the reactant stream, preferably the first oxygen-containing stream is adjusted such that the formed HCN content of the first product stream is less than 1400 ppm.
11. The process of claim 8, wherein one or more of the reactant stream, preferably the first oxygen-containing stream is adjusted such that the formed NO content of the first product stream is less than 200 ppm.
12. The process of any one of claims 1 to 11, wherein the composition of the first product stream is analysed continuously or at intervals of 5 seconds or less.
13. The process of any one of claims 1 or 12, wherein a fuel stream is co-reacted with the first oxygen-containing stream.
14. The process of claim 13, wherein the ratio of fuel gas stream to NH₃ containing stream is such as to maintain a reaction temperature in the range of 950 to 1700°C.
15. The process of any one of claims 13 to 14, wherein the fuel stream comprises one or more of hydrocarbons, hydrogen sulphide, carbon monoxide or hydrogen gas.
16. The process of any one of claims 1 to 15, wherein the second oxygen-containing stream is reacted in an amount such that the residual amount of oxygen in the second product stream is at least 0,5 volume %.
17. The process of any one of claims 1 to 16, wherein a waste gas is co-reacted with the second oxygen-containing stream.
18. The process of any one of claims 1 to 17, wherein reaction heat of the first incineration step and/or the second incineration step is recovered.
19. An NH₃ incinerator comprising:
 - a. a first reaction zone **100** comprising: a burner **110** for incinerating NH₃; an inlet **120** at the burner **110** for a first oxygen-containing stream, provided with a first oxygen control means **121** for adjusting the amount of the oxygen-containing stream; an inlet **130** at the burner **110** for a gas stream comprising NH₃ optionally provided with a first NH₃ control means **131** for adjusting the amount of the NH₃-containing stream; an inlet **140** at the burner **110** for a fuel stream optionally provided with a first fuel control means **141** for adjusting the amount of the fuel stream; an outlet **160** downstream of the reaction zone **100** for a first product stream prepared in the reaction zone **100**; an analyser **170** at the end of the reaction zone **100** capable of

analyzing the content of NH₃ and/or HCN and/or NO in the first product stream prepared in the reaction zone **100** and capable of adjusting one or more of the first control means **121**, **131** and **141**; and optionally a temperature control means **180** downstream of the reaction zone **100**; and

- b. a second reaction zone **200** downstream of the reaction zone **100** for incinerating the first product stream prepared in the reaction zone **100**, comprising: an inlet **230** at the start of the reaction zone **200** for the first product stream prepared in the reaction zone **100**; an inlet **220** at the start of the reaction zone **200** for a second oxygen-containing stream, optionally provided with a second control means **221** for adjusting the amount of the second oxygen-containing stream; optionally a second burner **210** provided with an inlet **211** at the second burner **210** for a third oxygen-containing stream, and an inlet **212** at the second burner **210** for a second fuel stream; optionally an inlet **250** at the start of the reaction zone **200** for a waste stream; an outlet **260** downstream of the reactor zone **200** for a second product stream prepared in the reaction zone **200**; optionally an analyser **270** at the end of the reactor zone **200** capable of analyzing the content of oxygen in the second product stream prepared in the reaction zone **200** and preferably capable of adjusting the second control means **221**; and optionally a waste heat boiler **280** downstream of the reactor zone **200** for recovery of reaction heat.

20. The NH₃ incinerator of claim 19, wherein the analyser **170** is a laser diode.
21. The NH₃ incinerator of any one of claims 19 to 20, wherein both reaction zones are part of a single reactor vessel.
22. The NH₃ incinerator of any one of claims 19 to 20, wherein each reaction zone is a separate reactor vessel, and wherein both reactor vessels are connected.




Fig. 1




Fig. 1