



(86) Date de dépôt PCT/PCT Filing Date: 2016/01/13
(87) Date publication PCT/PCT Publication Date: 2016/07/21
(85) Entrée phase nationale/National Entry: 2017/06/20
(86) N° demande PCT/PCT Application No.: SE 2016/050011
(87) N° publication PCT/PCT Publication No.: 2016/114709
(30) Priorité/Priority: 2015/01/16 (SE1550031-7)

(51) Cl.Int./Int.Cl. *A46B 13/00* (2006.01),
A46B 7/04 (2006.01), *A46B 3/14* (2006.01),
A46B 7/10 (2006.01), *A46B 9/12* (2006.01),
A46D 3/05 (2006.01), *E01H 1/05* (2006.01),
E01H 5/09 (2006.01)

(71) Demandeur/Applicant:
SVENSKA INDUSTRIBORSTAR I VASTERAS AB, SE

(72) Inventeur/Inventor:
DAHLBERG, CECIL, SE

(74) Agent: ROBIC

(54) Titre : BROSSE MODULAIRE, VEHICULE MUNI DE CELLE-CI ET PROCEDE DE PRODUCTION D'UN MODULE
POUR BROSSE MODULAIRE
(54) Title: A CASSETTE BRUSH, A VEHICLE PROVIDED THEREWITH AND A METHOD OF PRODUCING A
CASSETTE ELEMENT FOR A CASSETTE BRUSH




Fig. 5

(57) Abrégé/Abstract:

A brush(1)intended for industrial use comprises one or more bristle bunches formed by a plurality of elongated bristles, one or more cassette elements having said bristle bunches, and a cassette element holding member(3)at which said cassette elements

(57) **Abrégé(suite)/Abstract(continued):**

may be removably secured. At least one of said cassette elements comprises a body, one or more recesses configured to receive said bristle bunches therein, and a securing wire configured to secure said bristle bunches in said recesses. Said at least one cassette element further comprises means configured to counteract movement of the bristles of a bristle bunch with respect to each other and/or with respect to the securing wire.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property

Organization

International Bureau

(43) International Publication Date

21 July 2016 (21.07.2016)



(10) International Publication Number

WO 2016/114709 A1

(51) International Patent Classification:

A46B 13/00 (2006.01) A46B 9/12 (2006.01)
 A46B 3/14 (2006.01) A46D 3/05 (2006.01)
 A46B 7/04 (2006.01) E01H 1/05 (2006.01)
 A46B 7/10 (2006.01) E01H 5/09 (2006.01)

(21) International Application Number:

PCT/SE2016/050011

(22) International Filing Date:

13 January 2016 (13.01.2016)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

1550031-7 16 January 2015 (16.01.2015) SE

(71) Applicant: SVENSKA INDUSTRIBORSTAR I
 VÄSTERÅS AB [SE/SE]; Ödhumlagatan 4, SE-723 55
 Västerås (SE).

(72) Inventor: DAHLBERG, Cecil; Propellergatan 7, SE-723
 48 Västerås (SE).

(74) Agents: OLSSON, Andreas et al.; Bjerkéns Patentbyrå
 KB, Box 1274, SE-801 37 Gävle (SE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: A CASSETTE BRUSH, A VEHICLE PROVIDED THEREWITH AND A METHOD OF PRODUCING A CASSETTE ELEMENT FOR A CASSETTE BRUSH




Fig. 5

(57) Abstract: A brush(1)intended for industrial use comprises one or more bristle bunches formed by a plurality of elongated bristles, one or more cassette elements having said bristle bunches, and a cassette element holding member(3)at which said cassette elements may be removably secured. At least one of said cassette elements comprises a body,one or more recesses configured to receive said bristle bunches therein, and a securing wire configured to secure said bristle bunches in said recesses. Said at least one cassette element further comprises means configured to counteract movement of the bristles of a bristle bunch with respect to each other and/or with respect to the securing wire.

WO 2016/114709 A1

A cassette brush, a vehicle provided therewith and a method of producing a cassette element for a cassette brush

5 TECHNICAL FIELD OF THE INVENTION

The present invention relates to a brush intended for industrial use according to the preamble of claim 1 and a method for producing a cassette element for such a brush according to the pre-
10 amble of the appended independent method claim.

The invention relates to such a brush of any conceivable type, which can be arranged on tractors, floor sweepers, street sweepers, industrial machines and robots etc., but a brush arranged on
15 some type of airfield runway sweeper may be mentioned as a typical example without restricting the invention thereto.

Such a brush is used for sweeping a surface. Arranged at an airfield runway sweeper the brush is used for sweeping a runway at
20 an airfield so as to keep this free from stones, dust, snow and other objects and substances that may disturb the starts and landings of airplanes. In other examples, such a brush arranged at an industrial machine may be used for removing disturbing particles from a conveyor and arranged at a floor sweeper the brush may
25 be used for cleaning a concrete floor.

BACKGROUND ART

A brush of the type described in the introduction is already known through the document US 4 302 863 A.

5

Said document discloses a brush intended for use in sweeping machines, especially for airfields or streets. This brush has a plurality of cassette elements (brush bridges) intended to be mounted on a cassette element holding member (brush roller) which cassette elements each has a plurality of bristle bunches arranged there along. A body of a said cassette element has recesses (openings) each configured to receive a U-shaped end of a bristle bunch being bent double therein in such a way that the end of the double bent bristle bunch opposite to the U-shaped end projects out of the respective recess, and a securing wire (locking wire) is drawn through the doubled ends of the bristle bunches to lock the bunches against withdrawal at the cassette element.

20 The bristle bunches of a brush of this type are after approximately 50-100 hours use torn down to such a degree that either the whole brush or the bristle bunches thereof have to be replaced. As the cassette element holding member of the brush is an expensive component and it is time consuming to replace individual bristle bunches the holding member and the cassette elements having
25 the bristle bunches are made separately and then mounted together before use of the brush. One or all of the cassette elements of the brush may therefore fast and easy be replaced when the

bristle bunches thereof are so torn down that the result of the sweeping deteriorates.

5 The major steps of a known method of producing a cassette element intended to be used with a brush of the type defined in the introduction is illustrated through appended Figs. 1-4.

A cassette element 5b having a plurality of bristle bunches 9b is produced by:

10

• pressing a middle portion 11b of each said bristle bunch 9b down in an associated recess 7b, located at a first outer surface 8b of a body 6b of the cassette element 5b, by means of either a member 21b or by hand, in such a way that the middle portion of a bristle bunch forms substantially a U-shape therein and a first 12b and a second end portion 13b of said bristle bunch 9b extend out of the recess in a direction away from said first outer surface of the body (see figures 1-3), and

15

20 • securing said middle portion 11b of each said bristle bunch in the respective recess 7b by pressing a securing wire 14b into an opening 22b at a short side 23b of the body 6b and over the bristles 10b contained in a bottom portion 15b of the U-shape of each of the bristle bunches 9b, in a direction perpendicular to the extension of the bristle bunches in their bottom portions, so that the securing wire 14b secures the bristle bunches 9b in the associated recesses 7b by urging parts of said U-shape of each bristle bunch 9b against surfaces of wall 17b and

25

bottom portions 18b of the respective recess 7b (see fig 4).

There are at least two problems related to this method of producing such cassette elements 5b. Firstly, there is a risk that the middle portion of individual bristles 10c (see fig 4) are not being pushed down to a proper position, below said opening 22b, in a recess 7b. This results in that the securing wire 14b will be pressed into the cassette element body 6b over the bottom portion 15b of the bristle bunch 9b but under the middle portions of the bristles 10c being out of position with the consequence that these are not secured by the securing wire. This means that a bristle bunch 9b of the brush will be one or more bristles 10c short leading to impaired efficiency of the brush and in the worst scenario these loose bristles 10c will come off during sweeping of a runway and consequently endanger the use of the runway.

Secondly, there is a risk that the middle portion of individual bristles 10b are not being pushed down to a proper position, below said opening 22b, but is positioned at the same height as the opening 22b in a recess 7b. This results in that the securing wire 14b will be pressed into the cassette element body 6b over the bottom portion 15b of the bristle bunch 9b and into parts of the bristles being out of position with the consequence that these might be damaged before pushed down and secured by the securing wire 14b. This means that the damaged bristles eventually will break and come off during sweeping which for instance shortens the life-span of the cassette elements 5b. Also, if a few bristles 10b-c come off from a bristle bunch 9b there is more room for

the remaining bristles 10b to move and the damage of the brush might be even worse.

5 A possible but not desirable solution for solving these problems is to let an operator examine and manually push individual bristles 10c that are out of position down into the associated bristle bunch 9b before the securing wire 14b is arranged. This solution would be related to high production costs and consequently an expensive brush for the consumers.

10

There is a strong desire of providing a brush of this type with cassette elements having bristle bunches secured to that degree that the bristle bunches or individual bristles thereof may never move out of the position in which they are secured to the cassette
15 element body by the securing wire, i.e. to overcome the common problem with brushes of this type already known. This problem occur due to the poorly developed method for producing a cassette element already known, in combination with lack of an effective way of securing the securing wire over the bristle bunches
20 of a cassette element already known, since a poorly secured securing wire may lead to that individual bristles or even a complete bristle bunch is ripped out of a cassette element during use of the brush, and a bristle bunch with missing or damaged bristles may lead to impaired securement of the securing wire.

25

SUMMARY OF THE INVENTION

The object of the present invention is to provide a brush as well as a method of the type defined in the introduction being improved

in at least some aspect with respect to such brushes and methods already known.

This object is according to the invention with respect to the brush
5 obtained by providing such a brush with a said at least one cassette element that further comprises:

- means configured to counteract movement of the bristles in said bottom portion of the bristle bunch with respect to each other and/or with respect to said securing wire.

10

A cassette element provided with said means result in that the risk that individual bristles, a complete bristle bunch and/or the securing wire move during use of the brush, is reduced. This means that the bristle bunches of the brush may be subjected to
15 larger forces during use without limitations in the effectiveness of the brush due to insufficient fixation of the bristles thereof.

According to an embodiment of the invention said means comprises:

- 20 • a first friction layer portion arranged over or secured to said part of the outer surface of the U-shape of the bristle bunch upon which part the securing wire is applying an urging action, and that said friction layer portion is configured to provide high friction by a first contact surface
25 facing away from said outer surface and a high friction by a second contact surface applied to said outer surface when not secured thereto.

Said first friction layer portion improves the ability of the securing wire to fixate the U-shape of the bristle bunch in the recess by friction locking.

5 According to another embodiment of the invention said means comprises:

- a second friction layer portion arranged between said one or more surfaces of wall and/or bottom portions of the recess and at least a part of the outer surface of the bottom portion of the U-shape of the bristle bunch so as to enable high friction force between these surfaces.

Said second friction layer portion provides a high coefficient of friction between said one or more surfaces of wall and/or bottom portions of the recess and at least a part of the outer surface of the bottom portion of the U-shape of the bristle bunch resulting in that the risk that individual bristles of or a complete bristle bunch move during use of the brush is further reduced, due to an even better ability of the securing wire to fixate the bristle bunch through friction locking.

According to another embodiment of the invention said means comprises:

- a holding element provided around the periphery of the bottom portion of the U-shape of the bristle bunch so as to enclose and hold the bristles of the bristle bunch together, said element is preferably a tape, more preferred an adhesive tape, wound around the bristle bunch.

With such a holding element the bristles of a bristle bunch may be held tightly together in the recess which prevents individual bristles of the bristle bunch from moving with respect to each other and thereby results in a better ability of the securing wire to
5 secure the bristle bunch in the recess.

According to another embodiment of the invention the securing wire is coated with a friction layer configured to provide high friction between the securing wire and parts of the cassette element
10 in contact therewith. Said friction layer improves the ability of the securing wire to fixate the U-shape of the bristle bunch in the recess by friction locking.

According to another embodiment of the invention the brush comprises one or more said cassette elements provided with a plurality of bristle bunches.
15

According to another embodiment of the invention the brush comprises a plurality of cassette elements having a plurality of bristle bunches, each of the bristle bunches of a said cassette element being provided with said means and the bristle bunches of a said cassette element being secured in their respective recesses by the same securing wire.
20

According to another embodiment of the invention the brush comprises a plurality of said cassette elements.
25

According to another embodiment of the invention at least a majority, preferably all, of the cassette elements are configured as

said at least one cassette element. With at least a majority, preferably all, of the cassette elements configured as said at least one cassette element a durable high-quality brush is obtained.

- 5 According to another embodiment of the invention said cassette element holding member has a body with a circular cylindrical shape, said body being provided with said fastening members. This type of cassette element holding member is suitable for a brush of this type.

10

According to another embodiment of the invention at least a majority, preferably all, of the bristles of a said bristle bunch are made of a synthetic material, preferably a plastic material. This is a suitable material for the bristles of the brush, regarding stiffness
15 and flexibility.

15

According to another embodiment of the invention the bristles of a said bristle bunch has an individual cross-section diameter of between 0.5 and 10 mm, preferably between 1 and 5 mm, and a
20 said bristle bunch has a total cross-section diameter of between 5 and 50 mm, preferably between 10 and 25 mm. These dimensions are suitable for a brush of this type.

20

According to another embodiment of the invention the securing
25 wire is made of metal, preferably steel.

25

According to another embodiment of the invention the brush is configured to be driven by a motor.

The object of the invention is with respect to the method obtained by providing a method according to the independent method claim. The advantages thereof appear from the above discussion of the brush according to the invention and the embodiments thereof, as well as from the following discussion of a method according to the invention.

The invention also comprises a vehicle intended for sweeping a ground, such as a runway on an airfield or a road, which is provided with a brush according to the invention.

Further advantages as well as advantageous features of the invention will appear from the following description of an embodiment of the invention as well as of a method according to the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

With reference to the appended drawings, below follows a specific description of an embodiment of the invention as well as a method according to the invention cited as examples.

In the drawings:

Fig 1 is a simplified side-elevation view showing a first production step of a method of producing a cassette element already known,

- Fig 2 is a perspective view showing the production step of Fig 1,
- 5 Fig 3 is a simplified side-elevation view showing a second production step of the method of producing a cassette element already known,
- 10 Fig 4 is a simplified side-elevation view showing a third production step of the method of producing a cassette element already known,
- 15 Fig 5 is a simplified perspective view of an airport runway sweeper provided with a brush according to the invention,
- Fig 6 is an enlarged simplified perspective view of the brush of Fig 5 during replacement of cassette elements,
- 20 Fig 7 is a simplified side-elevation view showing a first production step of a method of producing a cassette element according to the invention,
- 25 Fig 8 is a perspective view showing the production step of Fig 7,
- Fig 9 is a simplified side-elevation view showing a second production step of the method of producing a cassette element according to the invention,

Fig 10 is a simplified side-elevation view showing a third production step of the method of producing a cassette element according to the invention,

5 Fig 11 is a simplified perspective view of a cassette element body of a brush according to the invention, and

Fig 12 is a simplified perspective view of a cassette element according to the invention.

10

DETAILED DESCRIPTION OF AN EMBODIMENT OF THE INVENTION

A brush 1 according to an embodiment of the invention is illustrated in the appended Figures 5-12 and will now be described while at the same time making reference to all these Figures. The brush is intended to be arranged at an airfield runway sweeper 2 used for keeping a runway at an airfield free from stones, dust, snow etc. Sweeping of a runway on an airfield calls for high quality requirements of the brush 1 and its components as unwanted objects on the runway might be a danger at a take-off or landing of an airplane thereon.

The brush 1 comprises a circular cylindrical cassette element holding member 3 configured to be rotated during use of the brush. The holding member has a body 3a provided with fastening members in the form of elongated grooves 4, each configured to removably secure a series of cassette elements 5 at the body 3a of the holding member 3. To secure the cassette elements at said

body, these are pushed into a groove 4 through an opening thereof at one end of the body. As the groove is filled with cassette elements a locking disc is arranged at said end of the body 3a to close said opening and the cassette elements 5 are secured through fit locking with the groove 4. To remove one or all of the cassette elements the locking disc is simply dismounted from the holding member 3 and the cassette elements 5 may be pulled out of said opening (see fig 6).

Each cassette element 5 comprises an elongated body 6 provided with a plurality of recesses 7 at a first outer surface 8 thereof. The recesses are provided with bristle bunches 9, formed by a plurality of elongated bristles 10, in such a way that a middle portion 11 of a bristle bunch 9 is pushed down in a recess 7 in such a way that the middle portion forms substantially a U-shape therein and a first 12 and a second end portion 13 of the bristle bunch extend out of the recess in a direction away from said first outer surface 8 of said body 6. The bristles 10 are made of a plastic material, preferably polypropylene.

20

A securing wire 14 made of steel secures all said bristle bunches 9 of a cassette element 5 in the respective recesses 7 by extending over every bristle 10 contained in a bottom portion 15 of the U-shape of the bristle bunches, tightly over said bottom portion of the U-shape and in a direction perpendicular to the extension of the bristle bunches 9 in said bottom portion 15 so as to secure the bristle bunches in the recesses by urging parts of an outer surface 16 of said U-shape of the bristle bunches against one or

more surfaces of wall 17 and/or bottom portions 18 of the recesses 7. Said outer surface 16 extends around the complete periphery of the bottom portion 15 of a bristle bunch 9. The bottom portion 15 is in this disclosure considered to be the curved part
5 of the U-shape of a bristle bunch.

Every bristle bunch 9 is provided with a holding element 20 in the form of an adhesive tape wound around the complete periphery of the bottom portion 15 of the U-shape of each bristle bunch so
10 as to enclose and hold the bristles 10 of a bristle bunch together. Through this holding element 20 it is ensured that the bristles 10 of a bristle bunch 9 are arranged as a unit in the recess 7 and thereby that individual bristles are prevented from moving out of their position in the bristle bunch. Also, due to that at least outer
15 portions (20a-b) of the adhesive tape has a high coefficient of friction and thereby a high coefficient of friction is provided at least between said surfaces 16-18 each bristle bunch 9 will be retained in a predetermined proper position in the respective recess 7 even when subjected to large forces during use of the
20 brush 1. Preferably, the complete outer surface of a holding element 20 facing away from the bristle bunch 9 around which the holding element is arranged, is a surface configured to provide high friction against surrounding parts in a cassette element 5.

25 The bristles 10 of a bristle bunch 9 has an individual cross-section diameter of between 0.5 and 10 mm, preferably between 1 and 5 mm, and a bristle bunch has a total cross-section diameter of between 5 and 50 mm, preferably between 10 and 25 mm, when it is not double folded. A bristle bunch typically consists of between

20 and 40 individual bristles. The numbers presented above may vary and be adapted to suit the use of the brush 1. For instance, a brush intended for sweeping snow may have fewer and thicker bristles than a brush intended for sweeping dust.

5

In a method of producing a cassette element 5 according to an embodiment of the invention a holding element 20 is arranged around the complete periphery of the middle portion 11 of each said bristle bunch 9 before these are pushed down in the associated recesses 7 by a member 21 (see fig 7-8). An easy way of performing this is to wind an adhesive tape around the middle portion 11 of the bristle bunches.

The holding element 20 will then enclose and hold the bristles 10 together as a unit at the middle portion 11 of each bristle bunch 9 so that all of the bristles 10 of a bristle bunch 9 will be pushed down to a proper position, below an opening 22 (see fig 7) through which the securing wire 14 is inserted into the cassette element body 6, in the associated recess 7 (see fig 9). This means that the securing wire will be pressed into the cassette element body 6 over every bristle 10 contained in the bottom portion 15 of the bristle bunches 9 and secure the bristle bunches in a proper position and without the risk of damaging any individual bristles thereof (see fig 10). Consequently, the problems with the method already known addressed above are solved in an easy and cost-effective way and a method of producing cassette elements 5 for a brush 1 that is efficient to use and has an extended life-span compared to such brushes already known is provided.

The invention is of course not in any way restricted to the embodiment thereof described above, but many possibilities to modifications thereof will be apparent to a person with ordinary skill in the art without departing from the scope of the invention as defined in the appended claims.

The holding element may for instance be some other element than an adhesive tape, for example a textile strip or a thread wound around a bristle bunch. However, a thin thread wound around a bristle bunch in a single loop only is considered to not be such a holding element. If a thin thread is used to form a holding element, this has to be wound in multiple loops around a bristle bunch, to form a unit of threads which unit is considered to be the holding element. The width of a holding element arranged around a bristle bunch is at least 3-5 mm, preferably at least 10 mm, more preferred at least 20 mm.

The friction layer portions may be portions of the holding element but may also be portions of an additional element, such as a textile strip arranged over and/or under the bottom portion of a bristle bunch in a recess, and said first friction layer portion may even be a portion of a layer provided on the outer surface of the securing wire, such as a thin rubber layer. The friction layer portions may have a thickness of ≤ 5 mm, ≤ 3 mm, preferably ≤ 2 mm, more preferred ≤ 1 mm.

That a friction layer portion “provides high friction” or “enables a high friction force” between two surfaces means that the coefficient of friction between these surfaces is higher with the friction layer portion arranged there between than without this.

5

The fastening members being elongated grooves configured to secure the cassette elements through fit locking may be formed in some other way, and may also be configured to secure the cassette elements at the holding member through other means, such as by magnets or screws.

10

A cassette element holding member with a body having a circular cylindrical shape is one type of such a holding member. However, the body of the holding member may for instance have the shape of a cone or be substantially flat.

15

A brush according to the invention may be provided with only one cassette element but may also be provided with up to 100 cassette elements, or even more. Also, such a cassette element may have only one bristle bunch, 2-10, 11-20, 21-30 bristle bunches or even more.

20

The phrase “industrial use” as used in this disclosure refers to such use that is not commonly performed in a regular household. For example, use of a broom is considered to not be included in this definition, even if it is used in an industrial facility.

25

The word “wire” as used in this disclosure in the phrase “securing wire” is not to be interpreted as it has to be flexible but may also be an elongated thin rod, such as a thin steel rebar or the like.

- 5 That a recess is provided “at” a first outer surface of a cassette element body also includes that the opening of such a recess may be located above said first outer surface, protruding therefrom (as shown in Fig 11, as an example).

Claims

1. A brush (1) intended for industrial use comprising:
- 5 • one or more bristle bunches (9), each formed by a plurality of elongated bristles (10),
 - one or more cassette elements (5), each having at least one said bristle bunch (9), and
 - 10 • a cassette element holding member (3) provided with one or more fastening members (4), each fastening member (4) being configured to removably secure at least one said cassette element (5) at the holding member (3),
at least one of said cassette elements (5) comprising:
 - a body (6),
 - 15 • one or more recesses (7) at a first outer surface (8) of said body (6), each recess (7) being configured to receive a middle portion (11) of a said bristle bunch (9) therein, and
 - 20 • a securing wire (14) configured to secure said middle portion (11) of a said bristle bunch (9) in a said recess (7), with the middle portion (11) of the bristle bunch (9) pushed down in the recess (7) in such a way that the middle portion (11) forms substantially a U-shape therein and a first (12) and a second end portion (13) of the bristle bunch (9) extending out of the recess (7) in a direction away from said first outer surface (8) of said body (6), by extending over every bristle (10) contained in a bottom portion (15) of the U-shape of the bristle bunch (9), in a direction perpendicular to the extension of the bristle
- 25

bunch (9) in said bottom portion (15) so as to secure the
bristle bunch (9) in the recess (7) by urging parts of said
U-shape of the bristle bunch (9) against one or more sur-
faces of wall (17) and/or bottom portions (18) of the re-
cess (7),

characterized in that said at least one cassette element
(5) further comprises:

- means configured to counteract movement of the bristles
(10) in said bottom portion (15) of the bristle bunch (9)
with respect to each other and/or with respect to said se-
curing wire (14).

2. A brush (1) according to claim 1, **characterized** in that said
means comprises:

- a first friction layer portion (20a) arranged over or se-
cured to said part of the outer surface (16) of the U-shape
of the bristle bunch (9) upon which part the securing wire
(14) is applying an urging action, and that said friction
layer portion (20a) is configured to provide high friction
by a first contact surface facing away from said outer sur-
face (16) and a high friction by a second contact surface
applied to said outer surface (16) when not secured
thereto.

3. A brush (1) according to claim 1, **characterized** in that said
means comprises:

- a second friction layer portion (20b) arranged between
said one or more surfaces of wall (17) and/or bottom por-
tions (18) of the recess (7) and at least a part of the outer

surface (16) of the bottom portion (15) of the U-shape of the bristle bunch (9) so as to enable high friction force between these surfaces (16-18).

- 5 4. A brush (1) according to any of the preceding claims, **characterized** in that said means comprises:
- a holding element (20) provided around the periphery of the bottom portion (15) of the U-shape of the bristle bunch (9) so as to enclose and hold the bristles (10) of the bristle bunch (9) together, said element (20) is preferably a tape, more preferred an adhesive tape, wound around the bristle bunch (9).
- 10
- 15 5. A brush (1) according to any of the preceding claims, **characterized** in that the securing wire (14) is coated with a friction layer configured to provide high friction between the securing wire (14) and parts of the cassette element in contact therewith.
- 20 6. A brush (1) according to any of the preceding claims, **characterized** in that the brush (1) comprises one or more said cassette elements (5) provided with a plurality of bristle bunches (9).
- 25 7. A brush (1) according to any of the preceding claims, **characterized** in that the brush (1) comprises a plurality of cassette elements (5) provided with a plurality of bristle bunches (9), each of the bristle bunches (9) of a said cassette element (5) being provided with said means (20) and

the bristle bunches (9) of a said cassette element (5) being secured in their respective recesses (7) by the same securing wire (14).

- 5 8. A brush (1) according to any of the preceding claims, **characterized** in that the brush (1) comprises a plurality of said cassette elements (5).
- 10 9. A brush (1) according to claim 7 or 8, **characterized** in that at least a majority, preferably all, of the cassette elements (5) of the brush (1) are configured as said at least one cassette element (5).
- 15 10. A brush (1) according to any of the preceding claims, **characterized** in that said cassette element holding member (3) has a body (3a) with a circular cylindrical shape, said body (3a) being provided with said fastening members (4).
- 20 11. A brush (1) according to any of the preceding claims, **characterized** in that at least a majority, preferably all, of the bristles (10) of each said bristle bunch (9) are made of a synthetic material, preferably a plastic material.
- 25 12. A brush (1) according to any of the preceding claims, **characterized** in that the bristles (10) of a said bristle bunch (9) has an individual cross-section diameter of between 0.5 and 10 mm, preferably between 1 and 5 mm, and that a said bristle bunch (9) has a total cross-section diameter of between 5 and 50 mm, preferably between 10 and 25 mm.

13. A brush (1) according to any of the preceding claims, **characterized** in that the securing wire (14) is made of metal, preferably steel.
- 5
14. A brush (1) according to any of the preceding claims, **characterized** in that the brush (1) is configured to be driven by a motor.
- 10
15. A vehicle (2) intended for sweeping a ground, such as a runway on an airfield or a road, **characterized** in that the vehicle (2) is provided with a brush (1) according to any of the claims 1-14.
- 15
16. A method of producing a cassette element (5) having one or more bristle bunches (9) to be used with a brush (1) intended for industrial use, comprising the steps of:
- 20
- pressing a middle portion (11) of each said bristle bunch (9) down in an associated recess (7), located at a first outer surface (8) of a body (6) of the cassette element (5), in such a way that the middle portion (11) forms substantially a U-shape therein and a first (12) and a second end portion (13) of a said bristle bunch (9) extend out of
- 25
- the recess (7) in a direction away from said first outer surface (8) of said body (6), and
 - securing said middle portion (11) of each said bristle bunch (9) in the respective recess (7) by arranging a se-



5 curing wire (14) over every bristle (10) contained in a bottom portion (15) of the U-shape of a said bristle bunch (9), so that the securing wire (14) extends in a direction perpendicular to the extension of the bristle bunch (9) in said bottom portion (15) and secures the bristle bunch (9) in the associated recess (7) by urging parts of said U-shape of the bristle bunch (9) against one or more surfaces of wall (17) and/or bottom portions (18) of the recess (7),



10 **characterized** in that the method further comprises the step of:

- arranging means configured to counteract movement of the bristles (10) in said bottom portion (15) of the bristle bunch (9) with respect to each other and/or with respect to said securing wire (14).

17. A method according to claim 16, **characterized** in that the step of arranging means comprises:

- arranging a holding element (20) around the periphery of the middle portion (11) of a said bristle bunch (9) before the middle portion (11) is pushed down in the associated recess (7), so that the holding element (20) encloses and holds the bristles (10) of the bristle bunch (9) together, said element (20) is preferably a tape, more preferred an adhesive tape, which is wound around the bristle bunch (9).





3/6





Fig. 6

4/6




Fig. 7




Fig. 8




Fig. 9






Fig. 10

6/6






Fig. 5