



US011054990B2

(12) **United States Patent**  
**Alonso Ruiz et al.**

(10) **Patent No.:** **US 11,054,990 B2**

(45) **Date of Patent:** **Jul. 6, 2021**

(54) **TOUCH INPUT CURSOR MANIPULATION**

(56) **References Cited**

(71) Applicant: **Apple Inc.**, Cupertino, CA (US)

U.S. PATENT DOCUMENTS

(72) Inventors: **Marcos Alonso Ruiz**, San Francisco, CA (US); **Imran A. Chaudhri**, San Francisco, CA (US); **Nicholas K. Jong**, Seattle, WA (US); **Craig M. Federighi**, Los Altos Hills, CA (US)

4,864,520 A 9/1989 Setoguchi et al.  
5,184,120 A 2/1993 Schultz  
(Continued)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **APPLE INC.**, Cupertino, CA (US)

CA 2780765 A1 5/2011  
CN 1356493 A 7/2002  
(Continued)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

OTHER PUBLICATIONS

(21) Appl. No.: **16/824,490**

Patent, dated Apr. 14, 2020, received in Japanese Patent Application No. 2018-079290, which corresponds with U.S. Appl. No. 14/608,926, 5 pages.

(22) Filed: **Mar. 19, 2020**

(Continued)

(65) **Prior Publication Data**

US 2020/0218445 A1 Jul. 9, 2020

*Primary Examiner* — Stephen G Sherman  
(74) *Attorney, Agent, or Firm* — Morgan, Lewis & Bockius LLP

**Related U.S. Application Data**

(63) Continuation of application No. 16/258,394, filed on Jan. 25, 2019, now Pat. No. 10,599,331, which is a  
(Continued)

(57) **ABSTRACT**


An electronic device selects content and moves selected content displayed on a touch screen display. Content of an electronic document is displayed, and a selection input corresponding to selection of a respective portion of the content (selected content) is detected. In response, the device concurrently displays the selected content with a changed appearance, to indicate the selection, and a set of options related to the selected content. In response to detecting a single touch input at a location over the selected content, if the single touch input remains, during a first portion of the single touch input, at the location for a predetermined amount of time, followed, during a second portion of the single touch input, by a continuous touch gesture away from the location, the representation of the selected content is moved to a different location in a direction of the continuous touch gesture.

(51) **Int. Cl.**  
**G06F 3/0488** (2013.01)  
**G06F 3/0484** (2013.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **G06F 3/04886** (2013.01); **G06F 3/03547** (2013.01); **G06F 3/04812** (2013.01);  
(Continued)

(58) **Field of Classification Search**  
CPC ..... G06F 3/03547; G06F 3/041–047; G06F 3/0488; G06F 3/04883; G06F 2203/04101;  
(Continued)

**24 Claims, 145 Drawing Sheets**



**Related U.S. Application Data**

continuation of application No. 15/499,693, filed on Apr. 27, 2017, now Pat. No. 10,222,980, which is a continuation of application No. 14/866,361, filed on Sep. 25, 2015, now Pat. No. 9,639,184, which is a continuation of application No. 14/864,737, filed on Sep. 24, 2015, now Pat. No. 9,785,305.

(60) Provisional application No. 62/215,720, filed on Sep. 8, 2015, provisional application No. 62/213,593, filed on Sep. 2, 2015, provisional application No. 62/172,162, filed on Jun. 7, 2015, provisional application No. 62/135,619, filed on Mar. 19, 2015.

(51) **Int. Cl.**

**G06F 3/0481** (2013.01)  
**G06F 3/0354** (2013.01)

(52) **U.S. Cl.**

CPC ..... **G06F 3/04842** (2013.01); **G06F 3/04845** (2013.01); **G06F 3/04883** (2013.01); **G06F 2203/04104** (2013.01); **G06F 2203/04808** (2013.01)

(58) **Field of Classification Search**

CPC ..... G06F 3/04886; G06F 3/04812; G06F 3/04842; G06F 3/04845; G06F 2203/04808

See application file for complete search history.

(56)

**References Cited**

U.S. PATENT DOCUMENTS

5,374,787 A 12/1994 Miller et al.  
5,428,730 A 6/1995 Baker et al.  
5,463,722 A 10/1995 Venolia  
5,510,813 A 4/1996 Makinwa et al.  
5,555,354 A 9/1996 Strasnick et al.  
5,559,301 A 9/1996 Bryan, Jr. et al.  
5,710,896 A 1/1998 Seidl  
5,717,438 A 2/1998 Kim et al.  
5,793,360 A 8/1998 Fleck et al.  
5,793,377 A 8/1998 Moore  
5,801,692 A 9/1998 Muzio et al.  
5,805,144 A 9/1998 Scholder et al.  
5,805,167 A 9/1998 Van Cruyningen  
5,809,267 A 9/1998 Moran et al.  
5,819,293 A 10/1998 Corner et al.  
5,825,352 A 10/1998 Bisset et al.  
5,844,560 A 12/1998 Crutcher et al.  
5,872,922 A 2/1999 Hogan et al.  
5,946,647 A 8/1999 Miller et al.  
5,973,670 A 10/1999 Barber et al.  
6,002,397 A 12/1999 Kolawa et al.  
6,031,989 A 2/2000 Cordell  
6,088,019 A 7/2000 Rosenberg  
6,088,027 A 7/2000 Konar et al.  
6,111,575 A 8/2000 Martinez et al.  
6,121,960 A 9/2000 Carroll et al.  
6,208,329 B1 3/2001 Ballare  
6,208,340 B1 3/2001 Amin et al.  
6,219,034 B1 4/2001 Elbing et al.  
6,232,891 B1 5/2001 Rosenberg  
6,243,080 B1 6/2001 Molne  
6,252,594 B1 6/2001 Xia et al.  
6,300,936 B1 10/2001 Braun et al.  
6,313,836 B1 11/2001 Russell, Jr. et al.  
6,396,523 B1 5/2002 Segal et al.  
6,429,846 B2 8/2002 Rosenberg et al.  
6,448,977 B1 9/2002 Braun et al.  
6,459,442 B1 10/2002 Edwards et al.  
6,489,978 B1 12/2002 Gong et al.  
6,512,530 B1 1/2003 Rzepkowski et al.  
6,563,487 B2 5/2003 Martin et al.

6,567,102 B2 5/2003 Kung  
6,583,798 B1 6/2003 Hoek et al.  
6,590,568 B1 7/2003 Astala et al.  
6,661,438 B1 12/2003 Shiraishi et al.  
6,735,307 B1 5/2004 Volckers  
6,750,890 B1 6/2004 Sugimoto  
6,806,893 B1 10/2004 Kolawa et al.  
6,822,635 B2 11/2004 Shahoian et al.  
6,906,697 B2 6/2005 Rosenberg  
6,919,927 B1 7/2005 Hyodo  
6,943,778 B1 9/2005 Astala et al.  
7,036,088 B2 4/2006 Tunney  
7,138,983 B2 11/2006 Wakai et al.  
7,312,791 B2 12/2007 Hoshino et al.  
7,411,575 B2 8/2008 Hill et al.  
7,434,177 B1 10/2008 Ordning et al.  
7,453,439 B1 11/2008 Kushler et al.  
7,471,284 B2 12/2008 Bathiche et al.  
7,479,949 B2 1/2009 Jobs et al.  
7,516,404 B1 4/2009 Colby et al.  
7,533,352 B2 5/2009 Chew et al.  
7,552,397 B2 6/2009 Holecek et al.  
7,577,530 B2 8/2009 Vignalou-Marche  
7,614,008 B2 11/2009 Ordning  
7,619,616 B2 11/2009 Rimas Ribikauskas et al.  
7,629,966 B2 12/2009 Anson  
7,656,413 B2 2/2010 Khan et al.  
7,657,849 B2 2/2010 Chaudhri et al.  
7,683,889 B2 3/2010 Rimas Ribikauskas et al.  
7,702,733 B2 4/2010 Fleck et al.  
7,743,348 B2 6/2010 Robbins et al.  
7,760,187 B2 7/2010 Kennedy  
7,787,026 B1 8/2010 Flory et al.  
7,797,642 B1 9/2010 Karam et al.  
7,801,950 B2 9/2010 Eisenstadt et al.  
7,812,826 B2 10/2010 Ordning et al.  
7,890,862 B2 2/2011 Kompe et al.  
7,903,090 B2 3/2011 Soss et al.  
7,952,566 B2 5/2011 Poupyrev et al.  
7,956,847 B2 6/2011 Christie  
7,973,778 B2 7/2011 Chen  
8,040,142 B1 10/2011 Bokma et al.  
8,059,104 B2 11/2011 Shahoian et al.  
8,059,105 B2 11/2011 Rosenberg et al.  
8,106,856 B2 1/2012 Matas et al.  
8,125,440 B2 2/2012 Guyot-Sionnest et al.  
8,125,492 B1 2/2012 Wainwright et al.  
RE43,448 E 6/2012 Kimoto et al.  
8,209,628 B1 6/2012 Davidson  
8,271,900 B2 9/2012 Walizaka et al.  
8,300,005 B2 10/2012 Tateuchi et al.  
8,325,398 B2 12/2012 Satomi et al.  
8,363,020 B2 1/2013 Li et al.  
8,390,583 B2 3/2013 Forutanpour et al.  
8,423,089 B2 4/2013 Song et al.  
8,446,376 B2 5/2013 Levy et al.  
8,453,057 B2 5/2013 Stallings et al.  
8,456,431 B2 6/2013 Victor  
8,466,889 B2 6/2013 Tong et al.  
8,482,535 B2 7/2013 Pryor  
8,499,243 B2 7/2013 Yuki  
8,504,946 B2 8/2013 Williamson et al.  
8,508,494 B2 8/2013 Moore  
8,542,205 B1 9/2013 Keller  
8,553,092 B2 10/2013 Tezuka et al.  
8,570,296 B2 10/2013 Birnbaum et al.  
8,581,870 B2 11/2013 Bokma et al.  
8,587,542 B2 11/2013 Moore  
8,593,415 B2 11/2013 Han et al.  
8,593,420 B1 11/2013 Buuck  
8,625,882 B2 1/2014 Backlund et al.  
8,638,311 B2 1/2014 Kang et al.  
8,665,227 B2 3/2014 Gunawan  
8,669,945 B2 3/2014 Coddington  
8,698,765 B1 4/2014 Keller  
8,706,172 B2 4/2014 Priyantha et al.  
8,717,305 B2 5/2014 Williamson et al.  
8,726,198 B2 5/2014 Rydenhag et al.  
8,743,069 B2 6/2014 Morton et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

8,760,425 B2	6/2014	Crisan	9,645,722 B1	5/2017	Stasior et al.
8,769,431 B1	7/2014	Prasad	9,665,762 B2	5/2017	Thompson et al.
8,773,389 B1	7/2014	Freed	9,671,943 B2	6/2017	Van der Velden
8,788,964 B2	7/2014	Shin et al.	9,678,571 B1	6/2017	Robert et al.
8,793,577 B2	7/2014	Schellingerhout et al.	9,733,716 B2	8/2017	Shaffer
8,799,816 B2	8/2014	Wells et al.	9,740,381 B1	8/2017	Chaudhri et al.
8,816,989 B2	8/2014	Nicholson et al.	9,753,527 B2	9/2017	Connell et al.
8,854,316 B2	10/2014	Shenfield	9,760,241 B1	9/2017	Lewbel
8,872,729 B2	10/2014	Lyons et al.	9,785,305 B2	10/2017	Alonso Ruiz et al.
8,872,773 B2	10/2014	Mak et al.	9,804,665 B2	10/2017	DeBates et al.
8,875,044 B2	10/2014	Ozawa et al.	9,829,980 B2	11/2017	Lissemann et al.
8,881,062 B2	11/2014	Kim et al.	10,055,066 B2	8/2018	Lynn et al.
8,914,732 B2	12/2014	Jun et al.	10,057,490 B2	8/2018	Shin et al.
8,952,987 B2	2/2015	Momeyer et al.	10,095,396 B2	10/2018	Kudurshian et al.
8,954,889 B2	2/2015	Fujibayashi	10,133,388 B2	11/2018	Sudou
8,959,430 B1	2/2015	Spivak et al.	10,133,397 B1	11/2018	Smith
8,976,128 B2	3/2015	Moore	10,180,722 B2	1/2019	Lu
9,026,932 B1	5/2015	Dixon	10,222,980 B2	3/2019	Alonso Ruiz et al.
9,030,419 B1	5/2015	Freed	10,235,023 B2	3/2019	Gustafsson et al.
9,030,436 B2	5/2015	Ikeda	10,275,087 B1	4/2019	Smith
9,032,321 B1	5/2015	Cohen et al.	10,331,769 B1	6/2019	Hill et al.
9,043,732 B2	5/2015	Nurmi et al.	10,386,960 B1	8/2019	Smith
9,046,999 B1	6/2015	Teller et al.	10,469,767 B2	11/2019	Shikata
9,052,820 B2	6/2015	Jarrett et al.	10,496,151 B2	12/2019	Kim et al.
9,052,925 B2	6/2015	Chaudhri	10,547,895 B1	1/2020	Morris
9,063,563 B1	6/2015	Gray et al.	10,739,896 B2	8/2020	Kim et al.
9,063,731 B2	6/2015	Heo et al.	10,782,871 B2	9/2020	Bernstein et al.
9,069,460 B2	6/2015	Moore	2001/0024195 A1	9/2001	Hayakawa et al.
9,086,755 B2	7/2015	Cho et al.	2001/0045965 A1	11/2001	Orbanes et al.
9,092,058 B2	7/2015	Kasahara et al.	2002/0008691 A1	1/2002	Hanajima et al.
9,098,188 B2	8/2015	Kim	2002/0015064 A1	2/2002	Robotham et al.
9,104,260 B2	8/2015	Marsden et al.	2002/0042925 A1	4/2002	Ebisu et al.
9,111,076 B2	8/2015	Park et al.	2002/0054011 A1	5/2002	Bruneau et al.
9,116,569 B2	8/2015	Stacy et al.	2002/0057256 A1	5/2002	Flack
9,116,571 B2	8/2015	Zeliff et al.	2002/0109668 A1	8/2002	Rosenberg et al.
9,122,364 B2	9/2015	Kuwabara et al.	2002/0109678 A1	8/2002	Marmolin et al.
9,128,605 B2	9/2015	Nan et al.	2002/0140680 A1	10/2002	Lu
9,146,914 B1	9/2015	Dhaundiyal	2002/0140740 A1	10/2002	Chen
9,164,779 B2	10/2015	Brakensiek et al.	2002/0163498 A1	11/2002	Chang et al.
9,170,607 B2	10/2015	Bose et al.	2002/0180763 A1	12/2002	Kung
9,170,649 B2	10/2015	Ronkainen	2002/0186257 A1	12/2002	Cadiz et al.
9,218,105 B2	12/2015	Mansson et al.	2003/0001869 A1	1/2003	Nissen
9,244,562 B1	1/2016	Rosenberg et al.	2003/0013492 A1	1/2003	Bokhari et al.
9,244,576 B1	1/2016	Vadagave et al.	2003/0068053 A1	4/2003	Chu
9,244,601 B2	1/2016	Kim et al.	2003/0086496 A1	5/2003	Zhang et al.
9,244,606 B2	1/2016	Kocienda et al.	2003/0112269 A1	6/2003	Lentz et al.
9,246,487 B2	1/2016	Casparian et al.	2003/0117440 A1	6/2003	Hellyar et al.
9,262,002 B2	2/2016	Momeyer et al.	2003/0122779 A1	7/2003	Martin et al.
9,304,668 B2	4/2016	Rezende et al.	2003/0128242 A1	7/2003	Gordon
9,307,112 B2	4/2016	Molgaard et al.	2003/0151589 A1	8/2003	Bensen et al.
9,349,552 B2	5/2016	Huska et al.	2003/0184574 A1	10/2003	Phillips et al.
9,361,018 B2	6/2016	Defazio et al.	2003/0189552 A1	10/2003	Chuang et al.
9,383,887 B1	7/2016	Khafizov et al.	2003/0189647 A1	10/2003	Kang
9,389,718 B1	7/2016	Letourneur	2003/0206169 A1	11/2003	Springer et al.
9,389,722 B2	7/2016	Matsuki et al.	2003/0222915 A1	12/2003	Marion et al.
9,395,800 B2	7/2016	Liu et al.	2004/0015662 A1	1/2004	Cummings
9,400,581 B2	7/2016	Bokma et al.	2004/0021643 A1	2/2004	Hoshino et al.
9,405,367 B2	8/2016	Jung et al.	2004/0056849 A1	3/2004	Lohbihler et al.
9,405,428 B2	8/2016	Roh et al.	2004/0108995 A1	6/2004	Hoshino et al.
9,417,754 B2	8/2016	Smith	2004/0138849 A1	7/2004	Schmidt et al.
9,423,938 B1	8/2016	Morris	2004/0150631 A1	8/2004	Fleck et al.
9,436,344 B2	9/2016	Kuwabara et al.	2004/0150644 A1	8/2004	Kincaid et al.
9,448,694 B2	9/2016	Sharma et al.	2004/0155869 A1	8/2004	Robinson et al.
9,451,230 B1	9/2016	Henderson et al.	2004/0168131 A1	8/2004	Blumberg
9,471,145 B2	10/2016	Langlois et al.	2004/0174399 A1	9/2004	Wu et al.
9,477,393 B2	10/2016	Zambetti et al.	2004/0219969 A1	11/2004	Casey et al.
9,542,013 B2	1/2017	Dearman et al.	2004/0267877 A1	12/2004	Shiparo et al.
9,547,436 B2	1/2017	Ohki et al.	2005/0012723 A1	1/2005	Pallakoff
9,569,093 B2	2/2017	Lipman et al.	2005/0039141 A1	2/2005	Burke et al.
9,582,178 B2	2/2017	Grant et al.	2005/0064911 A1	3/2005	Chen et al.
9,600,114 B2	3/2017	Milam et al.	2005/0066207 A1	3/2005	Fleck et al.
9,600,116 B2	3/2017	Tao et al.	2005/0076256 A1	4/2005	Fleck et al.
9,612,741 B2	4/2017	Brown et al.	2005/0078093 A1	4/2005	Peterson, Jr. et al.
9,619,076 B2	4/2017	Bernstein et al.	2005/0091604 A1	4/2005	Davis
9,625,987 B1	4/2017	LaPenna et al.	2005/0110769 A1	5/2005	DaCosta et al.
			2005/0114785 A1	5/2005	Finnigan et al.
			2005/0125742 A1	6/2005	Grotjohn et al.
			2005/0134578 A1	6/2005	Chambers et al.
			2005/0183017 A1	8/2005	Cain

(56)		References Cited					
		U.S. PATENT DOCUMENTS					
2005/0190280	A1	9/2005	Haas et al.	2008/0066010	A1	3/2008	Brodersen et al.
2005/0204295	A1	9/2005	Voorhees et al.	2008/0094367	A1	4/2008	Van De Ven et al.
2005/0223338	A1	10/2005	Partanen	2008/0094368	A1	4/2008	Ording et al.
2005/0229112	A1	10/2005	Clay et al.	2008/0094398	A1	4/2008	Ng et al.
2005/0283726	A1	12/2005	Lunati	2008/0106523	A1	5/2008	Conrad
2005/0289476	A1	12/2005	Tokkonen	2008/0109753	A1	5/2008	Karstens
2006/0001650	A1	1/2006	Robbins et al.	2008/0136790	A1	6/2008	Hio
2006/0001657	A1	1/2006	Monney et al.	2008/0155415	A1	6/2008	Yoon et al.
2006/0012577	A1	1/2006	Kyrola	2008/0163119	A1	7/2008	Kim et al.
2006/0022955	A1	2/2006	Kennedy	2008/0165141	A1	7/2008	Christie
2006/0026536	A1	2/2006	Hotelling et al.	2008/0165160	A1	7/2008	Kocienda et al.
2006/0031776	A1	2/2006	Glein et al.	2008/0168379	A1	7/2008	Forstall et al.
2006/0036971	A1	2/2006	Mendel et al.	2008/0168395	A1	7/2008	Ording et al.
2006/0059436	A1	3/2006	Nurmi	2008/0168403	A1	7/2008	Westerman et al.
2006/0067677	A1	3/2006	Tokiwa et al.	2008/0168404	A1	7/2008	Ording
2006/0101347	A1	5/2006	Runov et al.	2008/0189605	A1	8/2008	Kay et al.
2006/0109252	A1	5/2006	Kolmykov-Zotov et al.	2008/0202824	A1	8/2008	Philipp et al.
2006/0109256	A1	5/2006	Grant et al.	2008/0204427	A1	8/2008	Heesemans et al.
2006/0119586	A1	6/2006	Grant et al.	2008/0219493	A1	9/2008	Tadmor
2006/0132455	A1	6/2006	Rimas-Ribikauskas et al.	2008/0222569	A1	9/2008	Champion et al.
2006/0132456	A1	6/2006	Anson	2008/0225007	A1	9/2008	Nakadaira et al.
2006/0132457	A1	6/2006	Rimas-Ribikauskas et al.	2008/0244448	A1	10/2008	Goering et al.
2006/0136834	A1	6/2006	Cao et al.	2008/0259046	A1	10/2008	Carsanaro
2006/0136845	A1	6/2006	Rimas-Ribikauskas et al.	2008/0263452	A1	10/2008	Tomkins
2006/0161861	A1	7/2006	Holecsek et al.	2008/0284866	A1	11/2008	Mizutani
2006/0161870	A1	7/2006	Hotelling et al.	2008/0294984	A1	11/2008	Ramsay et al.
2006/0190834	A1	8/2006	Marcjan	2008/0297475	A1	12/2008	Woolf et al.
2006/0195438	A1	8/2006	Galuten	2008/0303795	A1	12/2008	Lowles et al.
2006/0197753	A1	9/2006	Hotelling	2008/0303799	A1	12/2008	Schwesig et al.
2006/0212812	A1	9/2006	Simmons et al.	2008/0307335	A1	12/2008	Chaudhri et al.
2006/0213754	A1	9/2006	Jarrett et al.	2008/0307359	A1	12/2008	Louch et al.
2006/0224989	A1	10/2006	Pettiross et al.	2008/0317378	A1	12/2008	Steinberg et al.
2006/0233248	A1	10/2006	Rynderman et al.	2008/0320419	A1	12/2008	Matas et al.
2006/0236263	A1	10/2006	Bathiche et al.	2009/0007017	A1	1/2009	Anzures et al.
2006/0274042	A1	12/2006	Krah et al.	2009/0046110	A1	2/2009	Sadler et al.
2006/0274086	A1	12/2006	Forstall et al.	2009/0058828	A1	3/2009	Jiang et al.
2006/0277469	A1	12/2006	Chaudhri et al.	2009/0061837	A1	3/2009	Chaudhri et al.
2006/0282778	A1	12/2006	Barsness et al.	2009/0066668	A1	3/2009	Kim et al.
2006/0284858	A1	12/2006	Rekimoto	2009/0073118	A1	3/2009	Yamaji et al.
2006/0290681	A1	12/2006	Ho et al.	2009/0075738	A1	3/2009	Pearce
2007/0024595	A1	2/2007	Baker et al.	2009/0083665	A1	3/2009	Anttila et al.
2007/0024646	A1	2/2007	Saarinen et al.	2009/0085878	A1	4/2009	Heubel et al.
2007/0080953	A1	4/2007	Lii	2009/0085881	A1	4/2009	Keam
2007/0113681	A1	5/2007	Nishimura et al.	2009/0085886	A1	4/2009	Huang et al.
2007/0120834	A1	5/2007	Boillot	2009/0089293	A1	4/2009	Garritano et al.
2007/0120835	A1	5/2007	Sato	2009/0100343	A1	4/2009	Lee et al.
2007/0124699	A1	5/2007	Michaels	2009/0102804	A1	4/2009	Wong et al.
2007/0152959	A1	7/2007	Peters	2009/0102805	A1	4/2009	Meijer et al.
2007/0157089	A1	7/2007	Van Os et al.	2009/0140985	A1	6/2009	Liu
2007/0157173	A1	7/2007	Klein et al.	2009/0150775	A1	6/2009	Miyazaki et al.
2007/0168369	A1	7/2007	Bruns	2009/0158198	A1	6/2009	Hayter et al.
2007/0168890	A1	7/2007	Zhao et al.	2009/0160793	A1	6/2009	Rekimoto
2007/0176904	A1	8/2007	Russo	2009/0160814	A1	6/2009	Li et al.
2007/0182999	A1	8/2007	Anthony et al.	2009/0167507	A1	7/2009	Maenpaa
2007/0186178	A1	8/2007	Schiller	2009/0167508	A1	7/2009	Fadell et al.
2007/0200713	A1	8/2007	Weber et al.	2009/0167509	A1	7/2009	Fadell et al.
2007/0222768	A1	9/2007	Geurts et al.	2009/0167704	A1	7/2009	Terlizzi et al.
2007/0229455	A1	10/2007	Martin et al.	2009/0169061	A1	7/2009	Anderson et al.
2007/0229464	A1	10/2007	Hotelling et al.	2009/0187824	A1	7/2009	Hinckley et al.
2007/0236450	A1	10/2007	Colgate et al.	2009/0189866	A1	7/2009	Haffenden et al.
2007/0236477	A1	10/2007	Ryu et al.	2009/0195959	A1	8/2009	Ladouceur et al.
2007/0245241	A1	10/2007	Bertram et al.	2009/0198767	A1	8/2009	Jakobson et al.
2007/0257821	A1	11/2007	Son et al.	2009/0201260	A1	8/2009	Lee et al.
2007/0270182	A1	11/2007	Gulliksson et al.	2009/0219294	A1	9/2009	Young et al.
2007/0288862	A1	12/2007	Ording	2009/0225037	A1	9/2009	Williamson et al.
2007/0294295	A1	12/2007	Finkelstein et al.	2009/0228842	A1	9/2009	Westerman et al.
2007/0299923	A1	12/2007	Skelly et al.	2009/0237374	A1	9/2009	Li et al.
2008/0001924	A1	1/2008	dos los Reyes et al.	2009/0244357	A1	10/2009	Huang
2008/0010610	A1	1/2008	Lim et al.	2009/0247112	A1	10/2009	Lundy et al.
2008/0024459	A1	1/2008	Poupyrev et al.	2009/0247230	A1	10/2009	Lundy et al.
2008/0034306	A1	2/2008	Ording	2009/0251410	A1	10/2009	Mori et al.
2008/0034331	A1	2/2008	Josephsoon et al.	2009/0251421	A1	10/2009	Bloebaum
2008/0036743	A1	2/2008	Westerman et al.	2009/0256947	A1	10/2009	Ciurea et al.
2008/0051989	A1	2/2008	Welsh	2009/0259975	A1	10/2009	Asai et al.
2008/0052945	A1	3/2008	Matas et al.	2009/0267906	A1	10/2009	Schroderus
				2009/0276730	A1	11/2009	Aybes et al.
				2009/0280860	A1	11/2009	Dahlke
				2009/0282360	A1	11/2009	Park et al.
				2009/0284478	A1	11/2009	De la Torre Baltierra et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2009/0288032	A1	11/2009	Chang et al.	2010/0295805	A1	11/2010	Shin et al.
2009/0293009	A1	11/2009	Meserth et al.	2010/0302177	A1	12/2010	Kim et al.
2009/0295713	A1	12/2009	Piot et al.	2010/0302179	A1	12/2010	Ahn et al.
2009/0295739	A1	12/2009	Nagara	2010/0306702	A1	12/2010	Warner
2009/0303187	A1	12/2009	Pallakoff	2010/0308983	A1	12/2010	Conte et al.
2009/0307583	A1	12/2009	Tonisson	2010/0309147	A1	12/2010	Fleizach et al.
2009/0307633	A1	12/2009	Haughay, Jr. et al.	2010/0313050	A1	12/2010	Harrat et al.
2009/0322893	A1	12/2009	Stallings et al.	2010/0313124	A1	12/2010	Privault et al.
2009/0325566	A1	12/2009	Bell et al.	2010/0313156	A1	12/2010	Louch et al.
2010/0007926	A1	1/2010	Imaizumi et al.	2010/0313158	A1	12/2010	Lee et al.
2010/0011304	A1	1/2010	Van Os	2010/0313166	A1	12/2010	Nakayama et al.
2010/0013613	A1	1/2010	Weston	2010/0315417	A1	12/2010	Cho et al.
2010/0013777	A1	1/2010	Baudisch et al.	2010/0315438	A1	12/2010	Horodezky et al.
2010/0017710	A1	1/2010	Kim et al.	2010/0317410	A1	12/2010	Song et al.
2010/0020035	A1	1/2010	Ryu et al.	2010/0321301	A1	12/2010	Casparian et al.
2010/0026640	A1	2/2010	Kim et al.	2010/0321312	A1	12/2010	Han et al.
2010/0026647	A1	2/2010	Abe et al.	2010/0325578	A1	12/2010	Mital et al.
2010/0039446	A1	2/2010	Hillis et al.	2010/0328229	A1	12/2010	Weber et al.
2010/0044121	A1	2/2010	Simon et al.	2011/0010626	A1	1/2011	Fino et al.
2010/0045619	A1	2/2010	Birnbaum et al.	2011/0012851	A1	1/2011	Ciesla et al.
2010/0057235	A1	3/2010	Wang et al.	2011/0018695	A1	1/2011	Bells et al.
2010/0058231	A1	3/2010	Duarte et al.	2011/0026099	A1	2/2011	Kwon et al.
2010/0060548	A1	3/2010	Choi et al.	2011/0035145	A1	2/2011	Yamasaki
2010/0060605	A1	3/2010	Rimas-Ribikauskas et al.	2011/0037706	A1	2/2011	Pasquero et al.
2010/0061637	A1	3/2010	Mochizuki et al.	2011/0038552	A1	2/2011	Lam
2010/0062803	A1	3/2010	Yun et al.	2011/0039602	A1	2/2011	McNamara et al.
2010/0070908	A1	3/2010	Mori et al.	2011/0047368	A1	2/2011	Sundaramurthy et al.
2010/0073329	A1	3/2010	Raman et al.	2011/0050576	A1	3/2011	Forutanpour et al.
2010/0083116	A1	4/2010	Akifusa et al.	2011/0050588	A1	3/2011	Li et al.
2010/0085302	A1	4/2010	Fairweather et al.	2011/0050591	A1	3/2011	Kim et al.
2010/0085314	A1	4/2010	Kwok	2011/0050594	A1	3/2011	Kim et al.
2010/0085317	A1	4/2010	Park et al.	2011/0050628	A1	3/2011	Hornma et al.
2010/0088596	A1	4/2010	Griffin et al.	2011/0050629	A1	3/2011	Homma et al.
2010/0088654	A1	4/2010	Henhoefler	2011/0050630	A1	3/2011	Ikeda
2010/0110082	A1	5/2010	Myrick et al.	2011/0050653	A1	3/2011	Miyazawa et al.
2010/0111434	A1	5/2010	Madden	2011/0050687	A1	3/2011	Alyshev et al.
2010/0127983	A1	5/2010	Irani et al.	2011/0054837	A1	3/2011	Ikeda
2010/0128002	A1	5/2010	Stacy et al.	2011/0055135	A1	3/2011	Dawson et al.
2010/0138776	A1	6/2010	Korhonen	2011/0055741	A1	3/2011	Jeon et al.
2010/0148999	A1	6/2010	Casparian et al.	2011/0057886	A1	3/2011	Ng et al.
2010/0149096	A1	6/2010	Migos et al.	2011/0057903	A1	3/2011	Yamano et al.
2010/0153879	A1	6/2010	Rimas-Ribikauskas et al.	2011/0061029	A1	3/2011	Yeh et al.
2010/0156807	A1	6/2010	Stallings et al.	2011/0063248	A1	3/2011	Yoon
2010/0156813	A1	6/2010	Duarte et al.	2011/0069012	A1	3/2011	Martensson
2010/0156818	A1	6/2010	Burrough et al.	2011/0069016	A1	3/2011	Victor
2010/0156823	A1	6/2010	Paleczny et al.	2011/0074697	A1	3/2011	Rapp et al.
2010/0156825	A1	6/2010	Sohn et al.	2011/0080349	A1	4/2011	Holbein et al.
2010/0159995	A1	6/2010	Stallings et al.	2011/0080350	A1	4/2011	Almalki et al.
2010/0171713	A1	7/2010	Kwok et al.	2011/0080367	A1	4/2011	Marchand et al.
2010/0175023	A1	7/2010	Gatlin et al.	2011/0084910	A1	4/2011	Almalki et al.
2010/0180225	A1	7/2010	Chiba et al.	2011/0087982	A1	4/2011	McCann et al.
2010/0199227	A1	8/2010	Xiao et al.	2011/0087983	A1	4/2011	Shim
2010/0211872	A1	8/2010	Rolston et al.	2011/0093815	A1	4/2011	Gobeil
2010/0214135	A1	8/2010	Bathiche et al.	2011/0093817	A1	4/2011	Song et al.
2010/0214239	A1	8/2010	Wu	2011/0102829	A1	5/2011	Jourdan
2010/0220065	A1	9/2010	Ma	2011/0107272	A1	5/2011	Aguilar
2010/0225604	A1	9/2010	Homma et al.	2011/0109617	A1	5/2011	Snook et al.
2010/0231534	A1	9/2010	Chaudhri et al.	2011/0116716	A1	5/2011	Kwon et al.
2010/0235118	A1	9/2010	Moore et al.	2011/0119610	A1	5/2011	Hackborn et al.
2010/0235726	A1	9/2010	Ording et al.	2011/0126139	A1	5/2011	Jeong et al.
2010/0235733	A1	9/2010	Drislane et al.	2011/0138295	A1	6/2011	Momchilov et al.
2010/0235746	A1	9/2010	Anzures	2011/0141031	A1	6/2011	McCullough et al.
2010/0240415	A1	9/2010	Kim et al.	2011/0141052	A1	6/2011	Bernstein et al.
2010/0241955	A1	9/2010	Price et al.	2011/0144777	A1	6/2011	Firkins et al.
2010/0248787	A1	9/2010	Smuga et al.	2011/0145752	A1	6/2011	Fagans
2010/0251168	A1	9/2010	Fujita et al.	2011/0145753	A1	6/2011	Prakash
2010/0259500	A1	10/2010	Kennedy	2011/0145759	A1	6/2011	Leffert et al.
2010/0271312	A1	10/2010	Alameh et al.	2011/0145764	A1	6/2011	Higuchi et al.
2010/0271500	A1	10/2010	Park et al.	2011/0149138	A1	6/2011	Watkins
2010/0277419	A1	11/2010	Ganey et al.	2011/0154199	A1	6/2011	Maffitt et al.
2010/0277496	A1	11/2010	Kawanishi et al.	2011/0163971	A1	7/2011	Wagner et al.
2010/0281379	A1	11/2010	Meaney et al.	2011/0163978	A1	7/2011	Park et al.
2010/0281385	A1	11/2010	Meaney et al.	2011/0169765	A1	7/2011	Aono
2010/0287486	A1	11/2010	Coddington	2011/0175826	A1	7/2011	Moore et al.
2010/0289807	A1	11/2010	Yu et al.	2011/0175832	A1	7/2011	Miyazawa et al.
				2011/0181521	A1	7/2011	Reid et al.
				2011/0181526	A1	7/2011	Shaffer et al.
				2011/0181538	A1	7/2011	Aono
				2011/0181751	A1	7/2011	Mizumori

(56)		References Cited					
		U.S. PATENT DOCUMENTS					
2011/0185299	A1	7/2011	Hinckley et al.	2012/0062732	A1	3/2012	Marman et al.
2011/0185300	A1	7/2011	Hinckley et al.	2012/0066630	A1	3/2012	Kim et al.
2011/0185316	A1	7/2011	Reid et al.	2012/0066648	A1	3/2012	Rolleston et al.
2011/0191675	A1	8/2011	Kauranen	2012/0081326	A1	4/2012	Heubel et al.
2011/0193788	A1	8/2011	King et al.	2012/0081375	A1	4/2012	Robert et al.
2011/0193809	A1	8/2011	Walley et al.	2012/0084644	A1	4/2012	Robert et al.
2011/0193881	A1	8/2011	Rydenhag	2012/0084689	A1	4/2012	Ledet et al.
2011/0197160	A1	8/2011	Kim et al.	2012/0084713	A1	4/2012	Desai et al.
2011/0201387	A1	8/2011	Paek et al.	2012/0089932	A1	4/2012	Kano et al.
2011/0202834	A1	8/2011	Mandryk et al.	2012/0089942	A1	4/2012	Gammon
2011/0202853	A1	8/2011	Mujkic	2012/0089951	A1	4/2012	Cassidy
2011/0202879	A1	8/2011	Stovicek et al.	2012/0096393	A1	4/2012	Shim et al.
2011/0205163	A1	8/2011	Hinckley et al.	2012/0096400	A1	4/2012	Cho
2011/0209088	A1	8/2011	Hinckley et al.	2012/0098780	A1	4/2012	Fujisawa et al.
2011/0209093	A1	8/2011	Hinckley et al.	2012/0102437	A1	4/2012	Worley et al.
2011/0209097	A1	8/2011	Hinckley et al.	2012/0105358	A1	5/2012	Momeyer et al.
2011/0209099	A1	8/2011	Hinckley et al.	2012/0105367	A1	5/2012	Son et al.
2011/0209104	A1	8/2011	Hinckley et al.	2012/0106852	A1	5/2012	Khawand et al.
2011/0210926	A1	9/2011	Pasquero et al.	2012/0113007	A1	5/2012	Koch et al.
2011/0210931	A1	9/2011	Shai	2012/0113023	A1	5/2012	Koch et al.
2011/0215914	A1	9/2011	Edwards	2012/0126962	A1	5/2012	Ujii et al.
2011/0221684	A1	9/2011	Rydenhag	2012/0131495	A1	5/2012	Goossens et al.
2011/0221776	A1	9/2011	Shimotani et al.	2012/0139844	A1	6/2012	Ramstein et al.
2011/0231789	A1	9/2011	Bukurak et al.	2012/0139864	A1	6/2012	Sleeman et al.
2011/0234639	A1	9/2011	Shimotani et al.	2012/0144330	A1	6/2012	Flint
2011/0238690	A1	9/2011	Arrasvouri et al.	2012/0146945	A1	6/2012	Miyazawa et al.
2011/0239110	A1	9/2011	Garrett et al.	2012/0147052	A1	6/2012	Homma et al.
2011/0242029	A1	10/2011	Kasahara et al.	2012/0154303	A1	6/2012	Lazaridis et al.
2011/0246801	A1	10/2011	Seethaler et al.	2012/0154328	A1	6/2012	Kono
2011/0246877	A1	10/2011	Kwak et al.	2012/0158629	A1	6/2012	Hinckley et al.
2011/0248916	A1	10/2011	Griffin et al.	2012/0159380	A1	6/2012	Kocienda et al.
2011/0248942	A1	10/2011	Yana et al.	2012/0169646	A1	7/2012	Berkes et al.
2011/0248948	A1	10/2011	Griffin et al.	2012/0169716	A1	7/2012	Mihara
2011/0252346	A1	10/2011	Chaudhri	2012/0176403	A1	7/2012	Cha et al.
2011/0252357	A1	10/2011	Chaudhri	2012/0179967	A1	7/2012	Hayes
2011/0252362	A1	10/2011	Cho et al.	2012/0180001	A1	7/2012	Griffen et al.
2011/0258537	A1	10/2011	Rives et al.	2012/0182226	A1	7/2012	Tuli
2011/0260994	A1	10/2011	Saynac et al.	2012/0183271	A1	7/2012	Forutanpour et al.
2011/0263298	A1	10/2011	Park	2012/0192108	A1	7/2012	Kolb
2011/0267530	A1	11/2011	Chun	2012/0200528	A1	8/2012	Ciesla et al.
2011/0279380	A1	11/2011	Weber et al.	2012/0206393	A1	8/2012	Hillis et al.
2011/0279381	A1	11/2011	Tong et al.	2012/0216114	A1	8/2012	Privault et al.
2011/0279395	A1	11/2011	Kuwabara et al.	2012/0218203	A1	8/2012	Kanki
2011/0279852	A1	11/2011	Oda et al.	2012/0235912	A1	9/2012	Laubach
2011/0285656	A1	11/2011	Yaksick et al.	2012/0236037	A1	9/2012	Lessing et al.
2011/0285659	A1	11/2011	Kuwabara et al.	2012/0240044	A1	9/2012	Johnson et al.
2011/0291945	A1	12/2011	Ewing, Jr. et al.	2012/0249575	A1	10/2012	Krolczyk et al.
2011/0291951	A1	12/2011	Tong	2012/0249853	A1	10/2012	Krolczyk et al.
2011/0296334	A1	12/2011	Ryu et al.	2012/0250598	A1	10/2012	Lonnfors et al.
2011/0296351	A1	12/2011	Ewing, Jr. et al.	2012/0256829	A1	10/2012	Dodge
2011/0304559	A1	12/2011	Pasquero	2012/0256846	A1	10/2012	Mak
2011/0304577	A1	12/2011	Brown et al.	2012/0256847	A1	10/2012	Mak et al.
2011/0310049	A1	12/2011	Homma et al.	2012/0256857	A1	10/2012	Mak
2011/0319136	A1	12/2011	Labowicz et al.	2012/0257071	A1	10/2012	Prentice
2012/0001856	A1	1/2012	Davidson	2012/0260219	A1	10/2012	Piccolotto
2012/0005622	A1	1/2012	Park et al.	2012/0260220	A1	10/2012	Griffin
2012/0007857	A1	1/2012	Noda et al.	2012/0274578	A1	11/2012	Snow et al.
2012/0011437	A1	1/2012	James et al.	2012/0274591	A1	11/2012	Rimas-Ribikauskas et al.
2012/0013541	A1	1/2012	Boka et al.	2012/0274662	A1	11/2012	Kim et al.
2012/0013542	A1	1/2012	Shenfield	2012/0278744	A1	11/2012	Kozitsyn et al.
2012/0013607	A1	1/2012	Lee	2012/0284673	A1	11/2012	Lamb et al.
2012/0019448	A1	1/2012	Pitkanen et al.	2012/0293449	A1	11/2012	Dietz
2012/0026110	A1	2/2012	Yamano	2012/0293551	A1	11/2012	Momeyer et al.
2012/0030623	A1	2/2012	Hoellwarth	2012/0297041	A1	11/2012	Momchilov
2012/0032979	A1	2/2012	Blow et al.	2012/0303548	A1	11/2012	Johnson et al.
2012/0036441	A1	2/2012	Basir et al.	2012/0304108	A1	11/2012	Jarrett et al.
2012/0036556	A1	2/2012	LeBeau et al.	2012/0304132	A1	11/2012	Sareen et al.
2012/0038580	A1	2/2012	Sasaki	2012/0304133	A1	11/2012	Nan et al.
2012/0044153	A1	2/2012	Arrasvouri et al.	2012/0306632	A1	12/2012	Fleizach et al.
2012/0047380	A1	2/2012	Nurmi	2012/0306748	A1	12/2012	Fleizach et al.
2012/0056837	A1	3/2012	Park et al.	2012/0306764	A1	12/2012	Kamibepu
2012/0056848	A1	3/2012	Yamano et al.	2012/0306765	A1	12/2012	Moore
2012/0062470	A1	3/2012	Chang	2012/0306766	A1	12/2012	Moore
2012/0062564	A1	3/2012	Miyashita et al.	2012/0306772	A1	12/2012	Tan et al.
2012/0062604	A1	3/2012	Lobo	2012/0306778	A1	12/2012	Wheeldreyer et al.
				2012/0306927	A1	12/2012	Lee et al.
				2012/0311429	A1	12/2012	Decker et al.
				2012/0311437	A1	12/2012	Weeldreyer et al.
				2012/0311498	A1	12/2012	Kluttz et al.

(56)		References Cited	
U.S. PATENT DOCUMENTS			
2012/0311504	A1	12/2012	van Os et al.
2013/0002561	A1	1/2013	Wakasa
2013/0014057	A1	1/2013	Reinpoldt et al.
2013/0016042	A1	1/2013	Makinen et al.
2013/0016122	A1	1/2013	Bhatt et al.
2013/0019158	A1	1/2013	Watanabe
2013/0019174	A1	1/2013	Gil et al.
2013/0031514	A1	1/2013	Gabbert
2013/0036386	A1	2/2013	Park et al.
2013/0042199	A1	2/2013	Fong et al.
2013/0044062	A1	2/2013	Bose et al.
2013/0047100	A1	2/2013	Kroeger et al.
2013/0050131	A1	2/2013	Lee et al.
2013/0050143	A1	2/2013	Kim et al.
2013/0061172	A1	3/2013	Huang et al.
2013/0063364	A1	3/2013	Moore
2013/0063389	A1	3/2013	Moore
2013/0067383	A1	3/2013	Kataoka et al.
2013/0067513	A1	3/2013	Takami
2013/0067527	A1	3/2013	Ashbook et al.
2013/0069889	A1	3/2013	Pearce et al.
2013/0074003	A1	3/2013	Dolenc
2013/0076676	A1	3/2013	Gan
2013/0077804	A1	3/2013	Glebe et al.
2013/0082824	A1	4/2013	Colley
2013/0082937	A1	4/2013	Liu et al.
2013/0086056	A1	4/2013	Dyor et al.
2013/0093691	A1	4/2013	Moosavi
2013/0093764	A1	4/2013	Andersson et al.
2013/0097520	A1	4/2013	Lewin et al.
2013/0097521	A1	4/2013	Lewin et al.
2013/0097534	A1	4/2013	Lewin et al.
2013/0097539	A1	4/2013	Mansson et al.
2013/0097556	A1	4/2013	Louch
2013/0097562	A1	4/2013	Kermoian et al.
2013/0102366	A1	4/2013	Teng et al.
2013/0111345	A1	5/2013	Newman et al.
2013/0111378	A1	5/2013	Newman et al.
2013/0111398	A1	5/2013	Lu et al.
2013/0111415	A1	5/2013	Newman et al.
2013/0111579	A1	5/2013	Newman et al.
2013/0113715	A1	5/2013	Grant et al.
2013/0113720	A1	5/2013	Van Eerd et al.
2013/0113760	A1	5/2013	Gossweiler, III et al.
2013/0120278	A1	5/2013	Cantrell
2013/0120280	A1	5/2013	Kukulski
2013/0120295	A1	5/2013	Kim et al.
2013/0120306	A1	5/2013	Furukawa
2013/0125039	A1	5/2013	Murata
2013/0127755	A1	5/2013	Lynn et al.
2013/0135243	A1	5/2013	Hirsch et al.
2013/0135288	A1	5/2013	King et al.
2013/0135499	A1	5/2013	Song
2013/0141364	A1	6/2013	Lynn et al.
2013/0141396	A1	6/2013	Lynn et al.
2013/0145313	A1	6/2013	Roh et al.
2013/0154948	A1	6/2013	Schediwy et al.
2013/0154959	A1	6/2013	Lindsay et al.
2013/0155018	A1	6/2013	Dagdeviren
2013/0159893	A1	6/2013	Lewis et al.
2013/0162603	A1	6/2013	Peng et al.
2013/0162667	A1	6/2013	Eskolin et al.
2013/0169549	A1	7/2013	Seymour et al.
2013/0174049	A1	7/2013	Townsend et al.
2013/0174089	A1	7/2013	Ki
2013/0174094	A1	7/2013	Heo et al.
2013/0174179	A1	7/2013	Park et al.
2013/0179840	A1	7/2013	Fisher et al.
2013/0185642	A1	7/2013	Gammons
2013/0187869	A1	7/2013	Rydenhag et al.
2013/0191791	A1	7/2013	Rydenhag et al.
2013/0194217	A1	8/2013	Lee et al.
2013/0194480	A1	8/2013	Fukata et al.
2013/0198690	A1	8/2013	Barsoum et al.
2013/0201139	A1	8/2013	Tanaka
2013/0212515	A1	8/2013	Eleftheriou
2013/0212541	A1	8/2013	Dolenc et al.
2013/0215079	A1	8/2013	Johnson et al.
2013/0222274	A1	8/2013	Mori et al.
2013/0222323	A1	8/2013	McKenzie
2013/0222333	A1	8/2013	Miles et al.
2013/0222671	A1	8/2013	Tseng et al.
2013/0227413	A1	8/2013	Thorsander et al.
2013/0227419	A1	8/2013	Lee et al.
2013/0227450	A1	8/2013	Na et al.
2013/0228023	A1	9/2013	Drasnin et al.
2013/0232353	A1	9/2013	Belesiu et al.
2013/0232402	A1	9/2013	Lu et al.
2013/0234929	A1	9/2013	Libin
2013/0239057	A1	9/2013	Ubillos et al.
2013/0246954	A1	9/2013	Gray et al.
2013/0249814	A1	9/2013	Zeng
2013/0257793	A1	10/2013	Zeliff et al.
2013/0257817	A1	10/2013	Yliaho
2013/0265246	A1	10/2013	Tae
2013/0265452	A1	10/2013	Shin et al.
2013/0268875	A1	10/2013	Han et al.
2013/0271395	A1	10/2013	Tsai et al.
2013/0275422	A1	10/2013	Silber et al.
2013/0278520	A1	10/2013	Weng et al.
2013/0293496	A1	11/2013	Takamoto
2013/0305184	A1	11/2013	Kim et al.
2013/0307790	A1	11/2013	Konttori et al.
2013/0307792	A1	11/2013	Andres et al.
2013/0314359	A1	11/2013	Sudou
2013/0314434	A1	11/2013	Shetterly et al.
2013/0321340	A1	12/2013	Seo et al.
2013/0321457	A1	12/2013	Bauermeister et al.
2013/0325342	A1	12/2013	Pylappan et al.
2013/0326420	A1	12/2013	Liu et al.
2013/0326421	A1	12/2013	Jo
2013/0326583	A1	12/2013	Freihold et al.
2013/0328770	A1	12/2013	Parham
2013/0328793	A1	12/2013	Chowdhury
2013/0328796	A1	12/2013	Al-Dahle et al.
2013/0332836	A1	12/2013	Cho
2013/0332892	A1	12/2013	Matsuki
2013/0335373	A1	12/2013	Tomiyasu
2013/0338847	A1	12/2013	Lisseman et al.
2013/0339001	A1	12/2013	Craswell et al.
2013/0339909	A1	12/2013	Ha
2014/0002355	A1	1/2014	Lee et al.
2014/0002374	A1	1/2014	Hunt et al.
2014/0002386	A1	1/2014	Rosenberg et al.
2014/0013271	A1	1/2014	Moore et al.
2014/0024414	A1	1/2014	Fuji
2014/0026098	A1	1/2014	Gilman
2014/0026099	A1	1/2014	Andersson Reimer et al.
2014/0028554	A1	1/2014	De Los Reyes et al.
2014/0028571	A1	1/2014	St. Clair
2014/0028601	A1	1/2014	Moore
2014/0028606	A1	1/2014	Giannetta
2014/0035804	A1	2/2014	Dearman
2014/0035826	A1	2/2014	Frazier et al.
2014/0049491	A1	2/2014	Nagar et al.
2014/0055367	A1	2/2014	Dearman et al.
2014/0055377	A1	2/2014	Kim
2014/0059460	A1	2/2014	Ho
2014/0059485	A1	2/2014	Lehrian et al.
2014/0063316	A1	3/2014	Lee et al.
2014/0063541	A1	3/2014	Yamazaki
2014/0067293	A1	3/2014	Parivar et al.
2014/0068475	A1	3/2014	Li et al.
2014/0071060	A1	3/2014	Santos-Gomez
2014/0072281	A1	3/2014	Cho et al.
2014/0072283	A1	3/2014	Cho et al.
2014/0078318	A1	3/2014	Alameh
2014/0078343	A1	3/2014	Dai et al.
2014/0082536	A1	3/2014	Costa et al.
2014/0092025	A1	4/2014	Pala et al.
2014/0092030	A1	4/2014	Van Der Velden
2014/0092031	A1	4/2014	Schwartz et al.
2014/0108936	A1	4/2014	Khosropour et al.
2014/0109016	A1	4/2014	Ouyang et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2014/0111456	A1	4/2014	Kashiwa et al.	2015/0058723	A1	2/2015	Cieplinski et al.
2014/0111480	A1	4/2014	Kim et al.	2015/0062046	A1	3/2015	Cho et al.
2014/0111670	A1	4/2014	Lord et al.	2015/0062052	A1	3/2015	Bernstein et al.
2014/0118268	A1	5/2014	Kuscher	2015/0062068	A1	3/2015	Shih et al.
2014/0123080	A1	5/2014	Gan	2015/0067495	A1	3/2015	Bernstein et al.
2014/0139456	A1	5/2014	Wigdor et al.	2015/0067496	A1	3/2015	Missig et al.
2014/0139471	A1	5/2014	Matsuki	2015/0067497	A1	3/2015	Cieplinski et al.
2014/0145970	A1	5/2014	Cho	2015/0067513	A1	3/2015	Zambetti et al.
2014/0152581	A1	6/2014	Case et al.	2015/0067519	A1	3/2015	Missig et al.
2014/0157203	A1	6/2014	Jeon et al.	2015/0067534	A1	3/2015	Choi et al.
2014/0160063	A1	6/2014	Yairi et al.	2015/0067559	A1	3/2015	Missig et al.
2014/0160073	A1	6/2014	Matsuki	2015/0067560	A1	3/2015	Cieplinski et al.
2014/0164955	A1	6/2014	Thiruvidam et al.	2015/0067563	A1	3/2015	Bernstein et al.
2014/0164966	A1	6/2014	Kim et al.	2015/0067596	A1	3/2015	Brown et al.
2014/0165006	A1	6/2014	Chaudhri et al.	2015/0067601	A1	3/2015	Bernstein et al.
2014/0168093	A1	6/2014	Lawrence	2015/0067602	A1	3/2015	Bernstein et al.
2014/0168153	A1	6/2014	Deichmann et al.	2015/0067605	A1	3/2015	Zambetti et al.
2014/0173517	A1	6/2014	Chaudhri	2015/0071547	A1	3/2015	Keating et al.
2014/0179377	A1	6/2014	Song et al.	2015/0082162	A1	3/2015	Cho et al.
2014/0184526	A1	7/2014	Cho	2015/0082238	A1	3/2015	Meng
2014/0201660	A1	7/2014	Clausen et al.	2015/0116205	A1	4/2015	Westerman et al.
2014/0208271	A1	7/2014	Bell et al.	2015/0121218	A1	4/2015	Kim et al.
2014/0210758	A1	7/2014	Park et al.	2015/0121225	A1	4/2015	Somasundaram et al.
2014/0210760	A1	7/2014	Aberg et al.	2015/0128092	A1	5/2015	Lee et al.
2014/0210798	A1	7/2014	Wilson	2015/0135108	A1	5/2015	Pope et al.
2014/0223376	A1	8/2014	Tarvainen et al.	2015/0135109	A1	5/2015	Zambetti et al.
2014/0223381	A1	8/2014	Huang et al.	2015/0138126	A1	5/2015	Westerman
2014/0237408	A1	8/2014	Ohlsson et al.	2015/0138155	A1	5/2015	Bernstein et al.
2014/0245202	A1	8/2014	Yoon et al.	2015/0139605	A1	5/2015	Wiklof
2014/0245367	A1	8/2014	Sasaki et al.	2015/0143273	A1	5/2015	Bernstein et al.
2014/0267114	A1	9/2014	Lisseman et al.	2015/0143284	A1	5/2015	Bennett et al.
2014/0267135	A1	9/2014	Chhabra	2015/0143294	A1	5/2015	Piccinato et al.
2014/0267362	A1	9/2014	Kocienda et al.	2015/0143303	A1	5/2015	Sarrazin et al.
2014/0282084	A1	9/2014	Murarka et al.	2015/0149899	A1	5/2015	Bernstein et al.
2014/0282211	A1	9/2014	Ady et al.	2015/0149964	A1	5/2015	Bernstein et al.
2014/0282214	A1	9/2014	Shirzadi et al.	2015/0149967	A1	5/2015	Bernstein et al.
2014/0300569	A1	10/2014	Matsuki et al.	2015/0153897	A1	6/2015	Huang et al.
2014/0304599	A1	10/2014	Alexandersson	2015/0153929	A1	6/2015	Bernstein et al.
2014/0304646	A1	10/2014	Rossmann	2015/0160729	A1	6/2015	Nakagawa
2014/0304651	A1	10/2014	Johansson et al.	2015/0169059	A1	6/2015	Behles et al.
2014/0306897	A1	10/2014	Cueto	2015/0185840	A1	7/2015	Golyshko et al.
2014/0306899	A1	10/2014	Hicks	2015/0193099	A1	7/2015	Murphy
2014/0310638	A1	10/2014	Lee et al.	2015/0193951	A1	7/2015	Lee et al.
2014/0313130	A1	10/2014	Yamano et al.	2015/0205495	A1	7/2015	Koide et al.
2014/0333551	A1	11/2014	Kim et al.	2015/0205775	A1	7/2015	Berdahl et al.
2014/0333561	A1	11/2014	Bull et al.	2015/0234446	A1	8/2015	Nathan et al.
2014/0344765	A1	11/2014	Hicks et al.	2015/0234493	A1	8/2015	Parivar et al.
2014/0351744	A1	11/2014	Jeon et al.	2015/0253866	A1	9/2015	Amm et al.
2014/0354845	A1	12/2014	Molgaard et al.	2015/0268786	A1	9/2015	Kitada
2014/0354850	A1	12/2014	Kosaka et al.	2015/0268813	A1	9/2015	Bos
2014/0359438	A1	12/2014	Matsuki	2015/0309573	A1	10/2015	Brombach et al.
2014/0359528	A1	12/2014	Murata	2015/0321607	A1	11/2015	Cho et al.
2014/0361982	A1	12/2014	Shaffer	2015/0332107	A1	11/2015	Paniaras
2014/0365945	A1	12/2014	Karunamuni et al.	2015/0332607	A1	11/2015	Gardner, Jr. et al.
2014/0365956	A1	12/2014	Karunamuni et al.	2015/0378519	A1	12/2015	Brown et al.
2014/0380247	A1	12/2014	Tecarro et al.	2015/0378982	A1	12/2015	McKenzie et al.
2015/0002664	A1	1/2015	Eppinger et al.	2015/0381931	A1	12/2015	Uhma et al.
2015/0012861	A1	1/2015	Loginov	2016/0004373	A1	1/2016	Huang
2015/0015763	A1	1/2015	Lee et al.	2016/0004393	A1	1/2016	Faaborg et al.
2015/0019997	A1*	1/2015	Kim ..... G06F 3/0488 715/752	2016/0004427	A1	1/2016	Zambetti et al.
2015/0020032	A1	1/2015	Chen	2016/0004428	A1	1/2016	Bernstein et al.
2015/0020033	A1	1/2015	Newham et al.	2016/0004430	A1	1/2016	Missig et al.
2015/0020036	A1	1/2015	Kim et al.	2016/0004431	A1	1/2016	Bernstein et al.
2015/0026584	A1	1/2015	Kobayakov et al.	2016/0004432	A1	1/2016	Bernstein et al.
2015/0026592	A1	1/2015	Mohammed et al.	2016/0011725	A1	1/2016	D'Argenio et al.
2015/0026642	A1	1/2015	Wilson et al.	2016/0011771	A1	1/2016	Cieplinski
2015/0029149	A1	1/2015	Andersson et al.	2016/0019718	A1	1/2016	Mukkamala et al.
2015/0033184	A1	1/2015	Kim et al.	2016/0021511	A1	1/2016	Jin et al.
2015/0040065	A1	2/2015	Bianco et al.	2016/0041750	A1	2/2016	Cieplinski et al.
2015/0042588	A1	2/2015	Park	2016/0048326	A1	2/2016	Kim et al.
2015/0046876	A1	2/2015	Goldenberg	2016/0062466	A1	3/2016	Moussette et al.
2015/0049033	A1	2/2015	Kim et al.	2016/0062619	A1	3/2016	Reeve et al.
2015/0052464	A1	2/2015	Chen et al.	2016/0070401	A1	3/2016	Kim et al.
2015/0055890	A1	2/2015	Lundin et al.	2016/0077721	A1	3/2016	Laubach et al.
				2016/0085385	A1	3/2016	Gao et al.
				2016/0092071	A1	3/2016	Lawson et al.
				2016/0124924	A1	5/2016	Greenberg et al.
				2016/0125234	A1	5/2016	Ota et al.
				2016/0132139	A1	5/2016	Du et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2016/0188181 A1 6/2016 Smith  
 2016/0196028 A1 7/2016 Kenney et al.  
 2016/0210025 A1 7/2016 Bernstein et al.  
 2016/0246478 A1 8/2016 Davis et al.  
 2016/0259412 A1 9/2016 Flint et al.  
 2016/0259413 A1 9/2016 Anzures et al.  
 2016/0259495 A1 9/2016 Butcher et al.  
 2016/0259496 A1 9/2016 Butcher et al.  
 2016/0259498 A1 9/2016 Foss et al.  
 2016/0259499 A1 9/2016 Kocienda et al.  
 2016/0259516 A1 9/2016 Kudurshian et al.  
 2016/0259517 A1 9/2016 Butcher et al.  
 2016/0259518 A1 9/2016 King et al.  
 2016/0259519 A1 9/2016 Foss et al.  
 2016/0259527 A1 9/2016 Kocienda et al.  
 2016/0259528 A1 9/2016 Foss et al.  
 2016/0259536 A1 9/2016 Kudurshian et al.  
 2016/0259548 A1 9/2016 Ma  
 2016/0274686 A1 9/2016 Ruiz et al.  
 2016/0274728 A1 9/2016 Luo et al.  
 2016/0274761 A1 9/2016 Ruiz et al.  
 2016/0283054 A1 9/2016 Suzuki  
 2016/0306507 A1 10/2016 Defazio et al.  
 2016/0320906 A1 11/2016 Bokma et al.  
 2016/0357368 A1 12/2016 Federighi et al.  
 2016/0357389 A1 12/2016 Dakin et al.  
 2016/0357390 A1 12/2016 Federighi et al.  
 2016/0357404 A1 12/2016 Alonso Ruiz et al.  
 2016/0360116 A1 12/2016 Penha et al.  
 2017/0045981 A1 2/2017 Karunamuni et al.  
 2017/0046039 A1 2/2017 Karunamuni et al.  
 2017/0046058 A1 2/2017 Karunamuni et al.  
 2017/0046059 A1 2/2017 Karunamuni et al.  
 2017/0046060 A1 2/2017 Karunamuni et al.  
 2017/0075520 A1 3/2017 Bauer et al.  
 2017/0075562 A1 3/2017 Bauer et al.  
 2017/0075563 A1 3/2017 Bauer et al.  
 2017/0090699 A1 3/2017 Pennington et al.  
 2017/0091153 A1 3/2017 Thimbleby  
 2017/0109011 A1 4/2017 Jiang  
 2017/0115867 A1 4/2017 Bargmann  
 2017/0123497 A1 5/2017 Yonezawa  
 2017/0124699 A1 5/2017 Lane  
 2017/0139565 A1 5/2017 Choi  
 2017/0315694 A1 11/2017 Alonso Ruiz et al.  
 2017/0357403 A1 12/2017 Geary et al.  
 2018/0024681 A1 1/2018 Bernstein et al.  
 2018/0059866 A1 3/2018 Drake et al.  
 2018/0082522 A1 3/2018 Bartosik  
 2018/0188920 A1 7/2018 Bernstein et al.  
 2018/0342103 A1 11/2018 Schwartz et al.  
 2018/0349362 A1 12/2018 Sharp et al.  
 2018/0364898 A1 12/2018 Chen  
 2019/0012059 A1 1/2019 Kwon et al.  
 2019/0018562 A1 1/2019 Bernstein et al.  
 2019/0042075 A1 2/2019 Bernstein et al.  
 2019/0042078 A1 2/2019 Bernstein et al.  
 2019/0065043 A1 2/2019 Zambetti et al.  
 2019/0121493 A1 4/2019 Bernstein et al.  
 2019/0121520 A1 4/2019 Cieplinski et al.  
 2019/0138101 A1 5/2019 Bernstein  
 2019/0138102 A1 5/2019 Missig  
 2019/0138189 A1 5/2019 Missig  
 2019/0146643 A1 5/2019 Foss et al.  
 2019/0155503 A1 5/2019 Alonso Ruiz et al.  
 2019/0158727 A1 5/2019 Penha et al.  
 2019/0163358 A1 5/2019 Dascola et al.  
 2019/0171353 A1 6/2019 Missig et al.  
 2019/0171354 A1 6/2019 Dascola et al.  
 2019/0212896 A1 7/2019 Karunamuni et al.  
 2019/0332257 A1 10/2019 Kudurshian et al.  
 2019/0364194 A1 11/2019 Penha et al.  
 2019/0391658 A1 12/2019 Missig et al.  
 2020/0081614 A1 3/2020 Zambetti  
 2020/0142548 A1 5/2020 Kurunimuni et al.

2020/0201472 A1 6/2020 Bernstein et al.  
 2020/0210059 A1 7/2020 Hu et al.  
 2020/0301556 A1 9/2020 Alonso Ruiz et al.  
 2020/0333936 A1 10/2020 Khoe et al.  
 2020/0371683 A1 11/2020 Zambetti et al.  
 2020/0396375 A1 12/2020 Penha et al.  
 2021/0081082 A1 3/2021 Dascola et al.

## FOREIGN PATENT DOCUMENTS

CN 1620327 A 5/2005  
 CN 1808362 A 7/2006  
 CN 101118469 A 2/2008  
 CN 101192097 A 6/2008  
 CN 101202866 A 6/2008  
 CN 101222704 A 7/2008  
 CN 101227764 A 7/2008  
 CN 101241397 A 8/2008  
 CN 101320303 A 12/2008  
 CN 101384977 A 3/2009  
 CN 101390039 A 3/2009  
 CN 101421707 A 4/2009  
 CN 101464777 A 6/2009  
 CN 101498979 A 8/2009  
 CN 101526876 A 9/2009  
 CN 101527745 A 9/2009  
 CN 101562703 A 10/2009  
 CN 101593077 A 12/2009  
 CN 101609380 A 12/2009  
 CN 101620507 A 1/2010  
 CN 101627359 A 1/2010  
 CN 101630230 A 1/2010  
 CN 101692194 A 4/2010  
 CN 101727179 A 6/2010  
 CN 101739206 A 6/2010  
 CN 101763193 A 6/2010  
 CN 101784981 A 7/2010  
 CN 101809526 A 8/2010  
 CN 101896962 A 11/2010  
 CN 101937304 A 1/2011  
 CN 101971603 A 2/2011  
 CN 101998052 A 3/2011  
 CN 102004575 A 4/2011  
 CN 102004576 A 4/2011  
 CN 102004577 A 4/2011  
 CN 102004593 A 4/2011  
 CN 102004602 A 4/2011  
 CN 102004604 A 4/2011  
 CN 102016777 A 4/2011  
 CN 102053790 A 5/2011  
 CN 102067068 A 5/2011  
 CN 102112946 A 6/2011  
 CN 102150018 A 8/2011  
 CN 102160021 A 8/2011  
 CN 102195514 A 9/2011  
 CN 102203702 A 9/2011  
 CN 102214038 A 10/2011  
 CN 102223476 A 10/2011  
 CN 102243662 A 11/2011  
 CN 102257460 A 11/2011  
 CN 102301322 A 12/2011  
 CN 102349038 A 2/2012  
 CN 102349040 A 2/2012  
 CN 102354269 A 2/2012  
 CN 102365666 A 2/2012  
 CN 102375605 A 3/2012  
 CN 102385478 A 3/2012  
 CN 102388351 A 3/2012  
 CN 102438092 A 5/2012  
 CN 102483666 A 5/2012  
 CN 102483677 A 5/2012  
 CN 102546925 A 7/2012  
 CN 102566908 A 7/2012  
 CN 102576251 A 7/2012  
 CN 102576282 A 7/2012  
 CN 102646013 A 8/2012  
 CN 102662571 A 9/2012  
 CN 102662573 A 9/2012  
 CN 102722312 A 10/2012

(56) References Cited					
FOREIGN PATENT DOCUMENTS					
CN	102752441 A	10/2012	EP	2 813 938 A1	12/2014
CN	102792255 A	11/2012	GB	2 402 105 A	12/2004
CN	102819331 A	12/2012	JP	58-182746	10/1983
CN	102819401 A	12/2012	JP	H06-161647 A	6/1994
CN	102841677 A	12/2012	JP	H07-98769 A	4/1995
CN	103019586 A	4/2013	JP	H07-098769 A	4/1995
CN	103092386 A	5/2013	JP	H07-104915	4/1995
CN	103092406 A	5/2013	JP	H07-151512 A	6/1995
CN	103097992 A	5/2013	JP	H08-227341 A	9/1996
CN	103186345 A	7/2013	JP	H09-269883 A	10/1997
CN	103201714 A	7/2013	JP	H09-330175 A	12/1997
CN	103279295 A	9/2013	JP	H11-203044 A	7/1999
CN	103518176 A	1/2014	JP	2001-078137 A	3/2001
CN	103649885 A	3/2014	JP	2001-202192 A	7/2001
CN	103699295 A	4/2014	JP	2001-222355 A	8/2001
CN	103777850 A	5/2014	JP	2001-306207 A	11/2001
CN	103777886 A	5/2014	JP	2002-044536 A	2/2002
CN	103793134 A	5/2014	JP	2002-149312 A	5/2002
CN	103838465 A	6/2014	JP	3085481 U	5/2002
CN	103870190 A	6/2014	JP	2002-182855 A	6/2002
CN	103970474 A	8/2014	JP	2003-157131 A	5/2003
CN	104011637 A	8/2014	JP	2003-186597 A	7/2003
CN	104020868 A	9/2014	JP	2004-054861 A	2/2004
CN	104020955 A	9/2014	JP	2004-062648 A	2/2004
CN	104021021 A	9/2014	JP	2004-070492 A	3/2004
CN	104024985 A	9/2014	JP	2004-086733 A	3/2004
CN	104077014 A	10/2014	JP	2004-152217 A	5/2004
CN	104142798 A	11/2014	JP	2004-288208 A	10/2004
CN	104160362 A	11/2014	JP	2005-031786 A	2/2005
CN	104267902 A	1/2015	JP	2005-092386 A	4/2005
CN	104331239 A	2/2015	JP	2005-102106 A	4/2005
CN	104392292 A	3/2015	JP	2005-135106 A	5/2005
CN	104412201 A	3/2015	JP	2005-157842 A	6/2005
CN	104471521 A	3/2015	JP	2005-196810 A	7/2005
CN	104487928 A	4/2015	JP	2005-317041 A	11/2005
CN	104487929 A	4/2015	JP	2005-352927	12/2005
CN	104487930 A	4/2015	JP	2006-059238 A	3/2006
CN	105264476 A	1/2016	JP	2006-185443 A	7/2006
DE	100 59 906 A1	6/2002	JP	2007-116384 A	5/2007
EP	0 859 307 A1	3/1998	JP	2007-148104 A	6/2007
EP	0 880 090 A2	11/1998	JP	2007-264808 A	10/2007
EP	1 028 583 A1	8/2000	JP	2008-009759 A	1/2008
EP	1 406 150 A1	4/2004	JP	2008-015890 A	1/2008
EP	1 674 977 A2	6/2006	JP	2008-033739 A	2/2008
EP	1 882 902 A1	1/2008	JP	2008-516348 A	5/2008
EP	2 000 896 A2	12/2008	JP	2008-146453 A	6/2008
EP	2 017 701 A1	1/2009	JP	2008-191086 A	8/2008
EP	2 028 583 A2	2/2009	JP	2008-537615 A	9/2008
EP	2 141 574 A2	1/2010	JP	2008-305174 A	12/2008
EP	2 175 357 A1	4/2010	JP	2009-500761 A	1/2009
EP	2 196 893 A2	6/2010	JP	2009-110243 A	5/2009
EP	2 214 087 A1	8/2010	JP	2009-129171 A	6/2009
EP	2 226 715 A2	9/2010	JP	2009-129443 A	6/2009
EP	2 284 675 A2	2/2011	JP	2009-169452 A	7/2009
EP	2 299 351 A2	3/2011	JP	2009-211704 A	9/2009
EP	2 302 496 A1	3/2011	JP	2009-217543 A	9/2009
EP	2 375 309 A1	10/2011	JP	2009-294688 A	12/2009
EP	2 375 314 A1	10/2011	JP	2009-545805 A	12/2009
EP	2 386 935 A1	11/2011	JP	2010-009321 A	1/2010
EP	2 407 868 A1	1/2012	JP	2010-503126 A	1/2010
EP	2 420 924 A2	2/2012	JP	2010-503130 A	1/2010
EP	2 426 580 A2	3/2012	JP	2010-055274 A	3/2010
EP	2 445 182 A2	4/2012	JP	2010-097353 A	4/2010
EP	2 447 818 A1	5/2012	JP	2010-146507 A	7/2010
EP	2 527 966 A2	11/2012	JP	2010-152716 A	7/2010
EP	2 530 677 A2	12/2012	JP	2010-176174 A	8/2010
EP	2 541 376 A1	1/2013	JP	2010-176337 A	8/2010
EP	2 555 500 A1	2/2013	JP	2010-181934 A	8/2010
EP	2 615 535 A1	7/2013	JP	2010-181940 A	8/2010
EP	2 631 737 A1	8/2013	JP	2010-198385 A	9/2010
EP	2 674 846 A2	12/2013	JP	2009-545805 A	12/2009
EP	2 708985 A1	3/2014	JP	2010-009321 A	1/2010
EP	2 733 578 A2	5/2014	JP	2010-503126 A	1/2010
EP	2 808 764 A1	12/2014	JP	2010-503130 A	1/2010
EP	2 809 058 A1	12/2014	JP	2010-055274 A	3/2010
			JP	2010-097353 A	4/2010
			JP	2010-146507 A	7/2010
			JP	2010-152716 A	7/2010
			JP	2010-176174 A	8/2010
			JP	2010-176337 A	8/2010
			JP	2010-181934 A	8/2010
			JP	2010-181940 A	8/2010
			JP	2010-198385 A	9/2010
			JP	2010-541071 A	12/2010
			JP	2011-501307 A	1/2011
			JP	2011-028635 A	2/2011
			JP	2011-048666 A	3/2011
			JP	2011-048686 A	3/2011
			JP	2011-048762 A	3/2011
			JP	2011-048832 A	3/2011
			JP	2011-053831 A	3/2011
			JP	2011-053972 A	3/2011

(56)

## References Cited

## FOREIGN PATENT DOCUMENTS

JP	2011-053973	A	3/2011	KR	2014 0122000	A	10/2014
JP	2011-053974	A	3/2011	KR	20150013263	A	2/2015
JP	2011-059821	A	3/2011	KR	20150021977	A	3/2015
JP	2011-070342	A	4/2011	RU	2007145218	A	7/2009
JP	2011-100290	A	5/2011	WO	WO 2005/106637	A2	11/2005
JP	2011-107823	A	6/2011	WO	WO 2006/013485	A2	2/2006
JP	2011-123773	A	6/2011	WO	WO 2006/042309	A1	4/2006
JP	2011-141868	A	7/2011	WO	WO 2006/094308	A2	9/2006
JP	2011-170538	A	9/2011	WO	WO 2007/121557	A1	11/2007
JP	2011-192179	A	9/2011	WO	WO 2008/030976	A2	3/2008
JP	2011-192215	A	9/2011	WO	WO 2008/064142	A2	5/2008
JP	2011-197848	A	10/2011	WO	WO 2009/155981	A1	12/2009
JP	2011-221640	A	11/2011	WO	WO 2009/158549	A2	12/2009
JP	2011-232947	A	11/2011	WO	WO 2010/013876	A1	2/2010
JP	2011-242386	A	12/2011	WO	WO 2010/032598	A1	3/2010
JP	2011-250004	A	12/2011	WO	WO 2010/090010	A1	8/2010
JP	2011-253556	A	12/2011	WO	WO 2010/122813	A1	10/2010
JP	2011-257941	A	12/2011	WO	WO 2010/134729	A2	11/2010
JP	2011-530101	A	12/2011	WO	WO 2011/024389	A1	3/2011
JP	2012-027940	A	2/2012	WO	WO 2011/024465	A1	3/2011
JP	2012-033061	A	2/2012	WO	WO 2011/024521	A1	3/2011
JP	2012-043266	A	3/2012	WO	WO 2011/093045	A1	8/2011
JP	2012-043267	A	3/2012	WO	WO 2011/105009	A1	9/2011
JP	2012-053687	A	3/2012	WO	WO 2011/108190	A1	9/2011
JP	2012-053754	A	3/2012	WO	WO 2011/115187	A1	9/2011
JP	2012-053926	A	3/2012	WO	WO 2011/121375	A1	10/2011
JP	2012-073785	A	4/2012	WO	WO 2012/021417	A1	2/2012
JP	2012-073873	A	4/2012	WO	WO 2012/037664	A1	3/2012
JP	2012-509605	A	4/2012	WO	WO 2012/096804	A2	7/2012
JP	2012-093820	A	5/2012	WO	WO 2012/108213	A1	8/2012
JP	2012-118825	A	6/2012	WO	WO 2012/114760	A1	8/2012
JP	2012-118993	A	6/2012	WO	WO 2012/137946	A1	10/2012
JP	2012-123564	A	6/2012	WO	WO 2012/150540	A2	11/2012
JP	2012-128825	A	7/2012	WO	WO 2012/153555	A1	11/2012
JP	2012-527685	A	11/2012	WO	WO 2013/022486	A1	2/2013
JP	2013-025357	A	2/2013	WO	WO 2013/035725	A1	3/2013
JP	2013-030050	A	2/2013	WO	WO 2013/112453	A1	8/2013
JP	2013-058149	A	3/2013	WO	WO 2013/169302	A1	11/2013
JP	2013-080521	A	5/2013	WO	WO 2013/169845	A1	11/2013
JP	2013-093020	A	5/2013	WO	WO 2013/169846	A1	11/2013
JP	2013-101465	A	5/2013	WO	WO 2013/169849	A2	11/2013
JP	2013-105410	A	5/2013	WO	WO 2013/169851	A2	11/2013
JP	2013-131185	A	7/2013	WO	WO 2013/169853	A1	11/2013
JP	2013-529339	A	7/2013	WO	WO 2013/169854	A2	11/2013
JP	2013-200879	A	10/2013	WO	WO 2013/169870	A1	11/2013
JP	2013-542488	A	11/2013	WO	WO 2013/169875	A2	11/2013
JP	2013-250602	A	12/2013	WO	WO 2013/169877	A2	11/2013
JP	2014-504419	A	2/2014	WO	WO 2013/169882	A2	11/2013
JP	2014-052852	A	3/2014	WO	WO 2013/173838	A2	11/2013
JP	2014-130567	A	7/2014	WO	WO 2014/105275	A1	7/2014
JP	2014-140112	A	7/2014	WO	WO 2014/105276	A1	7/2014
JP	2014-149833	A	8/2014	WO	WO 2014/105277	A2	7/2014
JP	2014-519109	A	8/2014	WO	WO 2014/105278	A1	7/2014
JP	2014-529137	A	10/2014	WO	WO 2014/105279	A1	7/2014
JP	2015-099555	A	5/2015	WO	WO 2014/129655	A1	8/2014
JP	2015-521315	A	7/2015	WO	WO 2014/149473	A1	9/2014
JP	2015-153420	A	8/2015	WO	WO 2014/152601	A1	9/2014
JP	2015-185161	A	10/2015	WO	WO 2014/200733	A1	12/2014
KR	2006-0071353	A	6/2006	WO	WO 2016/200584	A2	12/2016
KR	2008-0045143	A	4/2008				
KR	100823871	B1	4/2008				
KR	2008-0054346	A	6/2008				
KR	2010-0010860	A	2/2010				
KR	2010-0014095	A	2/2010				
KR	2010 0133246	A	12/2010				
KR	2011 0026176	A	3/2011				
KR	2011 0086501	A	7/2011				
KR	20120130972	A	1/2012				
KR	2012 0103670	A	9/2012				
KR	20120135723	A	12/2012				
KR	2013 0099647	A	9/2013				
KR	2014 0016495	A	2/2014				
KR	2014 0029720	A	3/2014				
KR	2014 0043760	A	4/2014				
KR	2014 0079110	A	6/2014				

## OTHER PUBLICATIONS

Notice of Allowance, dated Apr. 29, 2020, received in Australian Patent Application No. 2018250481, which corresponds with U.S. Appl. No. 14/536,203, 3 pages.

Office Action, dated Apr. 20, 2020, received in Chinese Patent Application No. 201610537334.1, which corresponds with U.S. Appl. No. 14/536,267, 4 pages.

Patent, dated Apr. 1, 2020, received in European Patent Application No. 16707356.8, which corresponds with U.S. Appl. No. 14/866,159, 3 pages.

Patent, dated May 12, 2020, received in Chinese Patent Application No. 201610342313.4, which corresponds with U.S. Appl. No. 14/863,432, 7 pages.

Office Action, dated Apr. 24, 2020, received in Korean Patent Application No. 2020-7003065, which corresponds with U.S. Appl. No. 14/866,511, 3 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Patent, dated Apr. 22, 2020, received in European Patent Application No. 18168939.9, which corresponds with U.S. Appl. No. 14/869,899, 3 pages.

Intention to Grant, dated Apr. 7, 2020, received in European Patent Application No. 16756866.6, which corresponds with U.S. Appl. No. 15/009,676, 8 pages.

Intention to Grant, dated Apr. 14, 2020, received in European Patent Application No. 17188507.2, which corresponds with U.S. Appl. No. 14/866,361, 7 pages.

Patent, dated May 19, 2020, received in Chinese Patent Application No. 201610871466.8, which corresponds with U.S. Appl. No. 14/871,236, 8 pages.

Office Action, dated Apr. 30, 2020, received in European Patent Application No. 18205283.7, which corresponds with U.S. Appl. No. 15/081,771, 7 pages.

Patent, dated Apr. 7, 2020, received in Chinese Patent Application No. 201810119007.3, which corresponds with U.S. Appl. No. 15/136,782, 7 pages.

Office Action, dated May 12, 2020, received in European Patent Application No. 18171453.6, which corresponds with U.S. Appl. No. 15/136,782, 5 pages.

Certificate of Grant, dated Apr. 2, 2020, received in Australian Patent Application No. 2018204234, which corresponds with U.S. Appl. No. 15/272,327, 1 page.

Patent, dated Mar. 3, 2020, received in Chinese Patent Application No. 201810071627.4, which corresponds with U.S. Appl. No. 15/272,343, 7 pages.

Notice of Allowance, dated Apr. 22, 2020, received in U.S. Appl. No. 15/272,345, 12 pages.

Office Action, dated May 11, 2020, received in Australian Patent Application No. 2019203776, which corresponds with U.S. Appl. No. 15/499,693, 4 pages.

Notice of Allowance, dated May 19, 2020, received in U.S. Appl. No. 15/889,115, 9 pages.

Notice of Allowance, dated May 14, 2020, received in U.S. Appl. No. 16/049,725, 9 pages.

Notice of Acceptance, dated Apr. 2, 2020, received in Australian Patent Application No. 2018253539, which corresponds with U.S. Appl. No. 16/049,725, 3 pages.

Office Action, dated May 4, 2020, received in Australian Patent Application No. 2019203175, which corresponds with U.S. Appl. No. 16/154,591, 4 pages.

Office Action, dated May 14, 2020, received in U.S. Appl. No. 16/354,035, 16 pages.

Office Action, dated May 14, 2020, received in U.S. Appl. No. 16/509,438, 16 pages.

Notice of Allowance, dated May 20, 2020, received in U.S. Appl. No. 16/534,214, 17 pages.

Notice of Allowance, dated May 4, 2020, received in Korean Patent Application No. 2019-7033444, 5 pages.

Certificate of Grant, dated May 21, 2020, received in Australian Patent Application No. 2018256616, which corresponds with U.S. Appl. No. 14/536,141, 3 pages.

Final Office Action, dated Jun. 15, 2020, received in U.S. Appl. No. 14/609,006, 19 pages.

Office Action, dated May 19, 2020, received in Chinese Patent Application No. 201680011338.4, which corresponds with U.S. Appl. No. 14/868,078, 4 pages.

Office Action, dated Jun. 23, 2020, received in Brazilian Patent Application No. 11201701119-9, which corresponds with U.S. Appl. No. 14/871,236, 9 pages.

Final Office Action, dated Jun. 9, 2020, received in U.S. Appl. No. 16/136,163, 10 pages.

Notice of Allowance, dated Jun. 1, 2020, received in Japanese Patent Application No. 2018-202048, which corresponds with U.S. Appl. No. 16/154,591, 3 pages.

Notice of Allowance, dated May 22, 2020, received in Japanese Patent Application No. 2019-027634, which corresponds with U.S. Appl. No. 16/240,672, 5 pages.

Office Action, dated Jun. 11, 2020, received in Australian Patent Application No. 2019257437, which corresponds with U.S. Appl. No. 16/252,478, 3 pages.

Patent, dated Jun. 3, 2020, received in Korean Patent Application No. 2019-7033444, 7 pages.

Notice of Allowance, dated Jun. 24, 2020, received in Chinese Patent Application No. 201710781246.0, which corresponds with U.S. Appl. No. 14/536,291, 5 pages.

Office Action, dated Jul. 3, 2020, received in Chinese Patent Application No. 201711425148.X, which corresponds with U.S. Appl. No. 14/536,646, 13 pages.

Office Action, dated Jun. 30, 2020, received in Chinese Patent Application No. 201680011338.4, which corresponds with U.S. Appl. No. 14/868,078, 4 pages.

Office Action, dated Jul. 17, 2020, received in Japanese Patent Application No. 2018-243773, which corresponds with U.S. Appl. No. 14/863,432, 5 pages.

Notice of Allowance, dated Jul. 13, 2020, received in Korean Patent Application No. 2020-7015964, which corresponds with U.S. Appl. No. 14/863,432, 6 pages.

Office Action, dated Jun. 30, 2020, received in Chinese Patent Application No. 201610658351.8, which corresponds with U.S. Appl. No. 14/866,992, 11 pages.

Office Action, dated Jul. 15, 2020, received in Chinese Patent Application No. 201680047125.7, which corresponds with U.S. Appl. No. 15/009,676, 11 pages.

Office Action, dated Jun. 29, 2020, received in Chinese Patent Application No. 201680047164.7, which corresponds with U.S. Appl. No. 15/009,688, 7 pages.

Office Action, dated Jul. 14, 2020, received in Chinese Patent Application No. 201711261143.8, which corresponds with U.S. Appl. No. 14/857,663, 12 pages.

Notice of Allowance, dated Jul. 6, 2020, received in Chinese Patent Application No. 201680022696.5, which corresponds with U.S. Appl. No. 15/272,345, 5 pages.

Office Action, dated Jul. 14, 2020, received in U.S. Appl. No. 15/979,347, 10 pages.

Notice of Allowance, dated Jun. 18, 2020, received in U.S. Appl. No. 16/174,170, 19 pages.

Patent, dated Jun. 23, 2020, received in Japanese Patent Application No. 2019-027634, which corresponds with U.S. Appl. No. 16/240,672, 4 pages.

Notice of Allowance, dated Apr. 3, 2020, received in Japanese Patent Application No. 2018-079290, which corresponds with U.S. Appl. No. 14/608,926, 5 pages.

Patent, dated Mar. 27, 2020, received in Korean Patent Application No. 2019-7009439, which corresponds with U.S. Appl. No. 15/499,693, 4 pages.

Agarwal, "How to Copy and Paste Text on Windows Phone 8," Guiding Tech, <http://web.archive.org/web/20130709204246/http://www.guidingtech.com/20280/copy-paste-text-windows-phone-8/>, Jul. 9, 2013, 10 pages.

Angelov, "Sponsor Flip Wall with JQuery & CSS", Tutorialzine. N.p., Mar. 24, 2010. Web. <http://tutorialzine.com/2010/03/sponsor-wall-slip-jquery-css/>, Mar. 24, 2010, 8 pages.

Anonymous, "1-Click Installer for Windows Media Taskbar Mini-Player for Windows 7, 8, 8.1 10", <http://metadataconsulting.blogspot.de/2014/05/installer-for-windows-media-taskbar.htm>, May 5, 2014, 6 pages.

Anonymous, "Acer Liquid Z5 Duo User's Manual", <https://global-download.acer.com>, Feb. 21, 2014, 65 pages.

Anonymous, "Android—What Should Status Bar Toggle Button Behavior Be?", <https://ux.stackexchange.com/questions/34814>, Jan. 15, 2015, 2 pages.

Anonymous, "Google Android 5.0 Release Date, Specs and Editors Hands on Review—CNET", <http://www.cnet.com/products/google-an-android-5-0-lollipop/>, Mar. 12, 2015, 10 pages.

Anonymous, "How Do I Add Contextual Menu to My Apple Watch App?", <http://www.tech-recipes.com/rx/52578/how-do-i-add-contextual-menu-to-my-apple-watch-app>, Jan. 13, 2015, 3 pages.

Anonymous, "[new] WMP12 with Taskbar Toolbar for Windows 7—Windows Customization—WinMatrix", <http://www.winmatrix.com>.

(56)

## References Cited

## OTHER PUBLICATIONS

com/forums/index.php?/topic/25528-new-wmp12-with-taskbar-toolbar-for-windows-7, Jan. 27, 2013, 6 pages.

Anonymous, "Nokia 808 PureView screenshots", retrieved from Internet; no URL, Nov. 12, 2012, 8 pages.

Anonymous, "Nokia 808 PureView User Guide," [http://download-fds.webapps.microsoft.com/supportFiles/phones/files/pdf\\_guides/devices/808/Nokia\\_808\\_UG\\_en\\_APAC.pdf](http://download-fds.webapps.microsoft.com/supportFiles/phones/files/pdf_guides/devices/808/Nokia_808_UG_en_APAC.pdf), Jan. 1, 2012, 144 pages.

Anonymous, "Notifications, Android 4.4 and Lower", Android Developers, [https://developer.android.com/design/patterns/notifications\\_k.html](https://developer.android.com/design/patterns/notifications_k.html), May 24, 2015, 9 pages.

Anonymous, "Taskbar Extensions", [https://web.archive.org/web/20141228124434/http://msdn.microsoft.com:80/en-us/library/windows/desktop/dd378460\(v=vs.85\).aspx](https://web.archive.org/web/20141228124434/http://msdn.microsoft.com:80/en-us/library/windows/desktop/dd378460(v=vs.85).aspx), Dec. 28, 2014, 8 pages.

Apple, "Apple—September Event 2014", <https://www.youtube.com/watch?v=38IqQpwPe7s>, Sep. 10, 2014, 5 pages.

Azundris, "A Fire in the Pie," <http://web.archive.org/web/20140722062639/http://blog.azundrix.com/archives/168-A-fire-in-the-sky.html>, Jul. 22, 2014, 8 pages.

Billibi, "Android 5.0 Lollipop", <https://www.bilibili.com/video/av1636046?from=search&seid=3128140235778895126>, Oct. 19, 2014, 6 pages.

B-log—betriebsraum weblog, "Extremely Efficient Menu Selection: Marking Menus for the Flash Platform," <http://www.betriebsraum.de/blog/2009/12/11/extremely-efficient-menu-selection-marking-for-the-flash-platform>, Dec. 11, 2009, 9 pages.

Bolluyt, "5 Apple Watch Revelations from Apple's New WatchKit", <http://www.cheatsheet.com/tecnology/5-apple-watch-revelations-from-apples-new-watchkit.html?a=viewall>, Nov. 22, 2014, 3 pages.

Boring, "The Fat Thumb: Using the Thumb's Contact Size for Single-Handed Mobile Interaction", <https://www.youtube.com/watch?v=E9vGU5R8nsc&feature=youtu.be>, Jun. 14, 2012, 2 pages.

Borowska, "6 Types of Digital Affordance that Impact Your UX", <https://www.webdesignerdepot.com/2015/04/6-types-of-digital-affordance-that-impact-your-ux>, Apr. 7, 2015, 6 pages.

Brownlee, "Android 5.0 Lollipop Feature Review!", <https://www.youtube.com/watch?v=pEDQ1z1-PvU>, Oct. 27, 2014, 5 pages.

Clark, "Global Moxie, Touch Means a Renaissance for Radial Menus," <http://globalmoxie.com/blog/radial-menus-for-touch-ui-print.shtml>, Jul. 17, 2012, 7 pages.

Cohen, Cinemagraphs are Animated Gifs for Adults, <http://www.tubefilter.com/2011/07/10/cinemagraph>, Jul. 10, 2011, 3 pages.

CrackBerry Forums, Windows 8 Bezel Control and Gestures, <http://wwwforums.crackberry.com/blackberry-playbook-f222/windows-8-bezel-control-gestures-705129/>, Mar. 1, 2012, 8 pages.

Crook, "Microsoft Patenting Multi-Screen, Milti-Touch Gestures," <http://techcrunch.com/2011/08/25/microsoft-awarded-patents-for-multi-screen-multi-touch-gestures/>, Aug. 25, 2011, 8 pages.

civil.ly—a design blog, Interesting Touch Interactions on Windows 8, <http://civil.ly/2011/06/04/interesting-touch-interactions-on-windows-8/>, Jun. 4, 2011, 3 pages.

Davidson, et al., "Extending 2D Object Arrangement with Pressure-Sensitive Layering Cues", Proceedings of the 21st Annual ACM Symposium on User Interface Software and Technology, Oct. 19, 2008, 4 pages.

Dinwiddie, et al., "Combined-User Interface for Computers, Television, Video Recorders, and Telephone, Etc", *ip.com Journal*, Aug. 1, 1990, 3 Pages.

Drinkwater, "Glossary: Pre/Post Alarm Image Buffer," <http://www.networkwebcams.com/ip-camera-learning-center/2008/07/17/glossary-prepost-alarm-image-buffer/>, Jul. 17, 2008, 1 page.

Dzyre, "10 Android Notification Features You Can Fiddle With", <http://www.hongkiat.com/blog/android-notification-features>, Mar. 10, 2014, 10 pages.

Easton-Ellett, "Three Free Cydia Utilities to Remove iOS Notification Badges", <http://www.ijailbreak.com/cydia/three-free-cydia-utilities-to-remove-ios-notification-badges>, Apr. 14, 2012, 2 pages.

Elliot, "Mac System 7", YouTube. Web. Mar. 8, 2017, <http://www.youtube.com/watch?v=XLv22hfuiuk>, Aug. 3, 2011, 1 page.

Farshad, "SageThumbs—Preview and Convert Pictures From Windows Context Menu", <https://web.addictivetips.com/windows-tips/sagethumbs-preview-and-convert-photos-from-windows-context-menu>, Aug. 8, 2011, 5 pages.

Fenlon, "The Case for Bezel Touch Gestures on Apple's iPad," <http://www.tested.com/tech/tablets/3104-the-case-for-bezel-touch-gestures-on-apples-ipad/>, Nov. 2, 2011, 6 pages.

Flaherty, "Is Apple Watch's Pressure-Sensitive Screen a Bigger Deal Than the Gadget Itself?", <http://www.wired.com/2014/09/apple-watches-pressure-sensitive-screen-bigger-deal-gadget>, Sep. 15, 2014, 3 pages.

Flixel, "Cinemagraph Pro for Mac", <https://flixel.com/products/mac/cinemagraph-pro>, 2014, 7 pages.

Flowplayer, "Slowmotion: Flowplayer," <https://web.archive.org/web/20150226191526/http://flash.flowplayer.org/plugins/streaming/slowmotion.html>, Feb. 26, 2015, 4 pages.

Forlines, et al., "Glimpse: a Novel Input Model for Multi-level Devices", Chi '05 Extended Abstracts on Human Factors in Computing Systems, Apr. 2, 2005, 4 pages.

Gardner, "Recenz—Recent Apps in One Tap", YouTube, <https://www.youtube.com/watch?v=qailSHRgTo>, May 15, 2015, 1 page.

Gonzalo et al., "Zliding: Fluid Zooming and Sliding for High Precision Parameter Manipulation", Department of Computer Science, University of Toronto, Seattle, Washington, Oct. 23, 2005, 10 pages.

Google-Chrome, "Android 5.0 Lollipop", <http://androidlovernet/android-os/android-5-0-lollipop/android-5-0-lollipop-recent-apps-card-google-search.html>, Oct. 19, 2014, 10 pages.

Grant, "Android's Notification Center", <https://www.objc.io/issues/11-android/android-notifications>, Apr. 30, 2014, 26 pages.

Gurman, "Force Touch on iPhone 6S Revealed: Expect Shortcuts, Faster Actions, iOS", 9To5Mac Aug. 10, 2015, 31 pages.

IBM et al., "Pressure-Sensitive Icons", IBM Technical Disclosure Bulletin, vol. 33, No. 1B, Jun. 1, 1990, 3 pages.

ICIMS Recruiting Software, "Blackberry Playbook Review," <http://www.tested.com/tech/tablets/5749-blackberry-playbook-review/>, 2015, 11 pages.

IPhoneHacksTV, "Confero allows you to easily manage your Badge notifications—iPhone Hacks", youtube, <https://www.youtube.com/watch?v=JcK61pnL4SU>, Dec. 26, 2014, 3 pages.

IPhoneOperator, "Wasser Liveeffekt für Homescreen & Lockscreen—AquaBoard (Cydia)", <http://www.youtube.com/watch?v=fG9YMFmB0Q>, Sep. 22, 2012, 3 pages.

IPodHacks 142: "Water Ripple Effects on the Home and Lock Screen: AquaBoard Cydia Tweak Review", YouTube, [https://www.youtube.com/watch?v=Auu\\_uRaYHJs](https://www.youtube.com/watch?v=Auu_uRaYHJs), Sep. 24, 2012, 3 pages.

Jauregui, "Design and Evaluation of 3D Cursors and Motion Parallax for the Exploration of Desktop Virtual Environments", IEEE Symposium on 3D User Interfaces 2012, Mar. 4, 2012, 8 pages.

Kaaresoja, "Snap-Crackle-Pop: Tactile Feedback for Mobile Touch Screens," Nokia Research Center, Helsinki, Finland, Proceedings of Eurohaptics vol. 2006, Jul. 3, 2006, 2 pages.

Kiener, "Force Touch on iPhone", <https://www.youtube.com/watch?v=CEMmnsU5fC8>, Aug. 4, 2015, 4 pages.

Kleinman, "iPhone 6s Said to Sport Force Touch Display, 2GB of RAM", <https://www.technobuffalo.com/2015/01/15/iphone-6s-said-to-sport-force-touch-display-2gb-of-ram>, Jan. 15, 2015, 2 pages.

Kost, "LR3—Deselect All Images But One", Julieanne Kost's Blog, <https://blogs.adobe.com/jkost/2011/12/lr3-deselect-all-images-but-one.html>, Dec. 22, 2011, 1 page.

Kronfli, "HTC Zoe Comes to Google Play, Here's Everything You Need to Know," Know Your Mobile, <http://www.knowyourmobile.com/htc/htc-one/19550/what-htc-zoe>, Aug. 14, 2014, 5 pages.

Kumar, "How to Enable Ripple Effect on Lock Screen of Galaxy S2", YouTube, <http://www.youtube.com/watch?v=B9-4M5ablXA>, Feb. 12, 2013, 3 pages.

Kurdi, "XnView Shell Extension: A Powerful Image Utility Inside the Context Menu", <http://www.freewaregenius.com/xnview-shell-extension-a-powerful-image-utility-inside-the-context-menu>, Jul. 30, 2008, 4 pages.

Laurie, "The Power of the Right Click," <http://vlaurie.com/right-click/customize-context-menu.html>, 2002-2016, 3 pages.

(56)

## References Cited

## OTHER PUBLICATIONS

- MacKenzie et al., "The Tactile Touchpad", Chi '97 Extended Abstracts on Human Factors in Computing Systems Looking to the Future, Chi '97, Mar. 22, 1997, 5 pages.
- Mandi, Confero now available in Cydia, brings a new way to manage Notification badges [Jailbreak Tweak], <http://www.iphonehacks.com/2015/01/confero/tweak-manage-notification-badges.html>, Jan. 1, 2015, 2 pages.
- Matthew, "How to Preview Photos and Images From Right-Click Context Menu in Windows [Tip]", <http://www.dottech.org/159009/add-image-preview-in-windows-context-menu-tip>, Jul. 4, 2014, 5 pages.
- McGarry, "Everything You Can Do With Force Touch on Apple Watch", Macworld, [www.macworld.com](http://www.macworld.com), May 6, 2015, 4 pages.
- McRitchie, "Internet Explorer Right-Click Menus," <http://web.archive.org/web-201405020/http://dmcritchie.mvps.org/ie/rightie6.htm>, May 2, 2014, 10 pages.
- Microsoft, "Lumia—How to Personalize Your Start Screen", <https://www.youtube.com/watch?v=6GI5Z3TrSEs>, Nov. 11, 2014, 3 pages.
- Microsoft, "Use Radial Menus to Display Commands in OneNote for Windows 8," <https://support.office.com/en-us/article/Use-radial-menus-to-display-OneNote-commands-Od75f03f-cde7-493a-a8a0b2ed6f99be2>, 2016, 5 pages.
- Minsky, "Computational Haptics the Sandpaper System for Synthesizing Texture for a Force-Feedback Display," Massachusetts Institute of Technology, Jun. 1978, 217 pages.
- Mitroff, "Google Android 5.0 Lollipop," <http://www.cnet.com/products/google-android-5-0-lollipop>, Mar. 12, 2015, 5 pages.
- Mohr, "Do Not Disturb—The iPhone Feature You Should Be Using", <http://www.wonderoftech.com/do-not-disturb-iphone>, Jul. 14, 2014, 30 pages.
- Nacca, "NiLS Lock Screen Notifications / Floating Panel—Review", <https://www.youtube.com/watch?v=McT4QnS9TDY>, Feb. 3, 2014, 4 pages.
- Neuburg, "Detailed Explanation iOS SDK", O'Reilly Japan, Dec. 22, 2014, vol. 4, P175-186, 15 pages.
- Nickinson, How to Use Do Not Disturb on the HTC One M8, <https://www.androidcentral.com/how-to-use-do-not-disturb-htc-one-m8>, Apr. 7, 2014, 9 pages.
- Nickinson, "Inside Android 4.2: Notifications and Quick Settings", <https://www.androidcentral.com/inside-android-42-notifications-and-quick-settings>, Nov. 3, 2012, 3 pages.
- Nikon, "Scene Recognition System and Advanced SRS," <http://www.nikonusa.com/en.Learn-And-Explore/Article/filzi4rr/Scene-Recognition-System.html>, Jul. 22, 2015, 2 pages.
- Ogino, "iOS 7 Design Standard", Japan, Impress Japan Corporation, 1st edition, Nov. 21, 2013, 2 pages.
- Oh, et al., "Moving Objects with 2D Input Devices in CAD Systems and Desktop Virtual Environments", Proceedings of Graphics Interface 2005, 8 pages, May 2005.
- O'Hara, et al., "Pressure-Sensitive Icons", ip.com Journal, Ip.Com Inc., West Henrietta, NY, US, Jun. 1, 1990, 2 Pages.
- Pallenberg, "Wow, the new iPad had gestures." <https://plus.google.com/+SaschaPallenberg/posts/aaJtJogu8ac>, Mar. 7, 2012, 2 pages.
- Phonebuff, "How to Pair Bluetooth on the iPhone", <https://www.youtube.com/watch?v=LudNwEar9A8>, Feb. 8, 2012, 3 pages.
- Plaisant et al. "Touchscreen Toggle Design", Proceedings of CHI '92, pp. 667-668, May 3-7, 1992, 2 pages.
- PoliceOne.com, "COBAN Technologies Pre-Event Buffer & Fail Safe Feature," <http://www.policeone.com/police-products/police-technology/mobile-computers/videos/5955587-COBAN-Technologies-Pre-Event>, Nov. 11, 2010, 2 pages.
- Pradeep, "Android App Development—Microsoft Awarded With Patents on Gestures Supported on Windows 8," <http://mspoweruser.com/microsoft-awarded-with-patents-on-gestures-supported-on-windows-8/>, Aug. 25, 2011, 16 pages.
- "Quickly Preview Songs in Windows Media Player 12 in Windows 7," Quickly Preview Songs in Windows Media Player 12 in Windows 7. How-to Geek, Apr. 28, 2010, Web. May 8, 2010, <http://web.archive.org/web/20100502013134/http://www.howtogeek.com/howto/16157/quickly-preview-songs-in-windows-media-center-12-in-windows-7->, 6 pages.
- Quinn, et al., "Zooing! Faster List Selections with Pressure-Zoom-Flick-Scrolling", Proceedings of the 21st Annual Conference of the Australian Computer-Human Interaction Special Interest Group on Design, Nov. 23, 2009, ACM Press, vol. 411, 8 pages.
- Rekimoto, et al., "PreSense: Interaction Techniques for Finger Sensing Input Devices", Proceedings of the 16th Annual ACM Symposium on User Interface Software and Technology, Nov. 30, 2003, 10 pages.
- Rekimoto, et al., "PreSense: Bi-directional Touch and Pressure Sensing Interactions with Tactile Feedback", Conference on Human Factors in Computing Systems Archive, ACM, Apr. 22, 2006, 6 pages.
- Rekimoto, et al., "SmartPad: A Finger-Sensing Keypad for Mobile Interaction", CHI 2003, Ft. Lauderdale, Florida, ACM 1-58113-637-Apr. 5-10, 2003, 2 pages.
- Ritchie, "How to see all the unread message notifications on your iPhone, all at once, all in the same place | iMore", <https://www.imore.com/how-see-all-unread-message-notifications-your-iphone-all-once-all-same-place>, Feb. 22, 2014, 2 pages.
- Roth et al., "Bezel Swipe: Conflict-Free Scrolling and Multiple Selection on Mobile Touch Screen Devices," Chi 2009, Boston, Massachusetts, USA, Apr. 4-9, 2009, 4 pages.
- Rubino et al., "How to Enable 'Living Images' on your Nokia Lumia with Windows Phone 8.1", <https://www.youtube.com/watch?v=RX7vpoFy1Dg>, Jun. 6, 2014, 5 pages.
- Sony, "Intelligent Scene Recognition," <https://www.sony-asia.com/article/252999/section/product/product/dsc-t77>, downloaded on May 20, 2016, 5 pages.
- Sood, "Multitasking Gestures", <http://cydia.saurik.com/package/org.thebigboxx.multitaskinggestures/>, Mar. 3, 2014, 2 pages.
- Stewart, et al., "Characteristics of Pressure-Based Input for Mobile Devices", Proceedings of the SIGCHI Conference on Human Factors in Computing Systems, Apr. 2010, 10 pages.
- Stross, "Wearing a Badge, and a Video Camera," The New York Times, <http://www.nytimes.com/2013/04/07/business/wearable-video-cameras-for-police-offers.html?R=0>, Apr. 6, 2013, 4 pages.
- Taser, "Taser Axon Body Camera User Manual," [https://www.taser.com/images/support/downloads/product-resources/axon\\_body\\_product\\_manual.pdf](https://www.taser.com/images/support/downloads/product-resources/axon_body_product_manual.pdf), Oct. 1, 2013, 24 pages.
- Tidwell, "Designing Interfaces," O'Reilly Media, Inc., USA, Nov. 2005, 348 pages.
- Tweak, "QuickCenter—Add 3D-Touch Shortcuts to Control Center", <https://www.youtube.com/watch?v=8rHOFpGvZFM>, Mar. 22, 2016, 2 pages.
- Tweak, "iOS 10 Tweak on iOS 9.0.2 Jailbreak & 9.2.1-9.3 Support: QuickCenter 3D, Touch Cydia Tweak!" [https://www.youtube.com/watch?v=op0Br30\\_Fkl](https://www.youtube.com/watch?v=op0Br30_Fkl), Mar. 6, 2016, 3 pages.
- UpDown-G, "Using Multiple Selection Mode in Android 4.0 / Getting Started", <https://techbooster.org/android/13946>, Mar. 7, 2012, 7 pages.
- VGFJFeliz, "How to Master Android Lollipop Notifications in Four Minutes!", <https://www.youtube.com/watch?v=S-zBRG7GJgs>, Feb. 8, 2015, 5 pages.
- VisioGuy, "Getting a Handle on Selecting and Subselecting Visio Shapes", <http://www.visioguy.com/2009/10/13/getting-a-handle-on-selecting-and-subselecting-visio-shapes/>, Oct. 13, 2009, 18 pages.
- Vitucci, "Apple Watch: Our Complete Overview—MacStories", <https://www.macstories.net>, Sep. 10, 2014, 21 pages.
- Wikipedia, "AirDrop," Wikipedia, the free encyclopedia, <http://en.wikipedia.org/wiki/AirDrop>, May 17, 2016, 5 pages.
- Wikipedia, "Cinemagraph," Wikipedia, the free encyclopedia, <http://en.wikipedia.org/wiki/Cinemagraph>, Last Modified Mar. 16, 2016, 2 pages.
- Wikipedia, "Context Menu," Wikipedia, the free encyclopedia [https://en.wikipedia.org/wiki/Context\\_menu](https://en.wikipedia.org/wiki/Context_menu), Last Modified May 15, 2016, 4 pages.
- Wikipedia, "HTC One (M7)," Wikipedia, the free encyclopedia, [https://en.wikipedia.org/wiki/HTC\\_One\\_\(M7\)](https://en.wikipedia.org/wiki/HTC_One_(M7)), Mar. 2013, 20 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Wikipedia, "Mobile Ad Hoc Network," Wikipedia, the free encyclopedia, [http://en.wikipedia.org/wiki/Mobile\\_ad\\_hoc\\_network](http://en.wikipedia.org/wiki/Mobile_ad_hoc_network), May 20, 2016, 4 pages.

Wikipedia, "Pie Menu," Wikipedia, the free encyclopedia, [http://en.wikipedia.org/wiki/Pie\\_menu](http://en.wikipedia.org/wiki/Pie_menu), Last Modified Jun. 4, 2016, 3 pages.

Wikipedia, "Quick Look," from Wikipedia, the free encyclopedia, [https://en.wikipedia.org/wiki/Quick\\_Look](https://en.wikipedia.org/wiki/Quick_Look), Last Modified Jan. 15, 2016, 3 pages.

Wikipedia, "Sony Xperia Z1," Wikipedia, the free encyclopedia, [https://en.wikipedia.org/wiki/Sony\\_Xperia\\_Z1](https://en.wikipedia.org/wiki/Sony_Xperia_Z1), Sep. 2013, 10 pages.

Wilson, et al., "Augmenting Tactile Interaction with Pressure-Based Input", School of Computing Science, Glasgow, UK, Nov. 15-17, 2011, 2 pages.

Yang, et al., "Affordance Application on Visual Interface Design of Desk-Top Virtual Experiments", 2014 International Conference on Information Science, Electronics and Electrical Engineering, IEEE, vol. 1, Apr. 26, 2014, 5 pages.

Yatani, et al., SemFeel: A User Interface with Semantic Tactile Feedback for Mobile Touch-Screen Devices, Proceedings of the 22nd annual ACM symposium on user interface software and technology (UIST '09), Oct. 2009, 10 pages.

YouTube, "Android Lollipop Lock-Screen Notification Tips", <https://www.youtube.com/watch?v=LZTxHBOwzIU>, Nov. 13, 2014, 3 pages.

YouTube, "Blackberry Playbook bezel interaction," <https://www.youtube.com/watch?v=YGkzFqnOwXI>, Jan. 10, 2011, 2 pages.

YouTube, "How to Master Android Lollipop Notifications in Four Minutes!", Video Gadgets Journal (VGJFelix), <https://www.youtube.com/watch?v=S-zBRG7GGJgs>, Feb. 8, 2015, 4 pages.

YouTube, "HTC One Favorite Camera Features", <http://www.youtube.com/watch?v=sUYHfcjI4RU>, Apr. 28, 2013, 3 pages.

YouTube, "Multitasking Gestures: Zephyr Like Gestures on iOS", <https://www.youtube.com/watch?v=Jcod-f7Lw0I>, Jan. 27, 2014, 3 pages.

YouTube, "Recentz—Recent Apps in a Tap", <https://www.youtube.com/watch?v=qailSHRgsTo>, May 15, 2015, 1 page.

Zylom, "House Secrets", <http://game.zylom.com/servlet/Entry?g=38&s=19521&nocache=1438641323066>, Aug. 3, 2015, 1 page.

Office Action, dated Mar. 15, 2017, received in U.S. Appl. No. 14/535,671, 13 pages.

Office Action, dated Nov. 30, 2017, received in U.S. Appl. No. 14/535,671, 21 pages.

Notice of Allowance, dated Sep. 5, 2018, received in U.S. Appl. No. 14/535,671, 5 pages.

Office Action, dated Jun. 29, 2017, received in U.S. Appl. No. 14/608,895, 30 pages.

Final Office Action, dated Feb. 22, 2018, received in U.S. Appl. No. 14/608,895, 20 pages.

Notice of Allowance, dated Jun. 26, 2018, received in U.S. Appl. No. 14/608,895, 9 pages.

Office Action, dated Dec. 18, 2015, received in Australian Patent Application No. 2013368440, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Office Action, dated Oct. 18, 2016, received in Australian Patent Application No. 2013368440, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Notice of Allowance, dated Dec. 20, 2016, received in Australian Patent Application No. 2013368440, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Certificate of Grant, dated Apr. 29, 2017, received in Australian Patent Application No. 2013368440, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Office Action, dated Nov. 6, 2017, received in Chinese Patent Application No. 201380068493.6, which corresponds with U.S. Appl. No. 14/608,895, 5 pages.

Office Action, dated Oct. 9, 2018, received in Chinese Patent Application No. 201380068493.6, which corresponds with U.S. Appl. No. 14/608,895, 3 pages.

Patent, dated Dec. 25, 2018, received in Chinese Patent Application No. 201380068493.6, which corresponds with U.S. Appl. No. 14/608,895, 4 pages.

Office Action, dated Jul. 21, 2016, received in European Patent Application No. 13795391.5, which corresponds with U.S. Appl. No. 14/536,426, 9 pages.

Office Action, dated Mar. 9, 2018, received in European Patent Application No. 13795391.5, which corresponds with U.S. Appl. No. 14/536,426, 4 pages.

Intention to Grant, dated Jul. 6, 2018, received in European Patent Application No. 13795391.5, which corresponds with U.S. Appl. No. 14/536,426, 5 pages.

Certificate of Grant, dated Dec. 26, 2018, received in European Patent Application No. 13795391.5, which corresponds with U.S. Appl. No. 14/536,426, 4 pages.

Office Action, dated Sep. 13, 2016, received in Japanese Patent Application No. 2015-547948, which corresponds with U.S. Appl. No. 14/536,426, 5 pages.

Patent, dated May 12, 2017, received in Japanese Patent Application No. 2015-547948, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Office Action, dated Apr. 5, 2016, received in Korean Patent Application No. 10-2015-7018851, which corresponds with U.S. Appl. No. 14/536,426, 7 pages.

Office Action, dated Feb. 24, 2017, received in Korean Patent Application No. 10-2015-7018851, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Patent, dated May 26, 2017, received in Korean Patent Application No. 2015-7018851, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Office Action, dated Oct. 5, 2018, received in Korean Patent Application No. 2018-7028236, which corresponds with U.S. Appl. No. 14/608,895, 6 pages.

Notice of Allowance, dated May 24, 2019, received in Korean Patent Application No. 2018-7028236, which corresponds with U.S. Appl. No. 14/608,895, 4 pages.

Patent, dated Jul. 9, 2019, received in Korean Patent Application No. 2018-7028236, which corresponds with U.S. Appl. No. 14/608,895, 4 pages.

Office Action, dated Jul. 26, 2017, received in U.S. Appl. No. 14/536,235, 14 pages.

Final Office Action, dated Feb. 26, 2018, received in U.S. Appl. No. 14/536,235, 13 pages.

Notice of Allowance, dated Aug. 15, 2018, received in U.S. Appl. No. 14/536,235, 5 pages.

Office Action, dated Apr. 5, 2017, received in U.S. Appl. No. 14/536,367, 16 pages.

Notice of Allowance, dated Nov. 30, 2017, received in U.S. Appl. No. 14/536,367, 9 pages.

Notice of Allowance, dated May 16, 2018, received in U.S. Appl. No. 14/536,367, 5 pages.

Office Action, dated Dec. 17, 2015, received in U.S. Appl. No. 14/536,426, 28 pages.

Final Office Action, dated May 6, 2016, received in U.S. Appl. No. 14/536,426, 23 pages.

Office action, dated Aug. 3, 2017, received in U.S. Appl. No. 14/536,426, 10 pages.

Office Action, dated Jul. 15, 2015, received in Australian Patent Application No. 2013259606, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Notice of Allowance, dated May 23, 2016, received in Australian Patent Application No. 2013259606, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Certificate of Grant, dated Sep. 15, 2016, received in Australian Patent Application No. 2013259606, which corresponds with U.S. Appl. No. 14/536,426, 1 page.

Office Action, dated Nov. 18, 2015, received in Australian Patent Application No. 2015101231, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Office Action, dated May 15, 2017, received in Australian Patent Application No. 2016216580, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Office Action, dated May 8, 2018, received in Australian Patent Application No. 2016216580, which corresponds with U.S. Appl. No. 14/536,426, 5 pages.

Notice of Allowance, dated May 17, 2018, received in Australian Patent Application No. 2016216580, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Certificate of Grant, dated Sep. 13, 2018, received in Australian Patent Application No. 2016216580, which corresponds with U.S. Appl. No. 14/536,426, 1 page.

Office Action, dated Apr. 12, 2019, received in Australian Patent Application No. 2018223021, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Office Action, dated Nov. 18, 2019, received in Australian Patent Application No. 2018223021, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Office Action, dated Sep. 19, 2017, received in Chinese Patent Application No. 201380035982.1, which corresponds with U.S. Appl. No. 14/536,426, 5 pages.

Notice of Allowance, dated May 10, 2018, received in Chinese Patent Application No. 201380035982.1, which corresponds with U.S. Appl. No. 14/536,426, 2 pages.

Patent, dated Aug. 17, 2018, received in Chinese Patent Application No. 201380035982.1, which corresponds with U.S. Appl. No. 14/536,426, 4 pages.

Office Action, dated Sep. 20, 2017, received in Chinese Patent Application No. 201510566550.4, which corresponds with U.S. Appl. No. 14/536,426, 11 pages.

Notice of Allowance, dated Aug. 8, 2018, received in Chinese Patent Application No. 201510566550.4, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Patent, dated Oct. 23, 2018, received in Chinese Patent Application No. 201510566550.4, which corresponds with U.S. Appl. No. 14/536,426, 4 pages.

Decision to Grant, dated Jul. 14, 2016, received in European Patent Application No. 13724100.6, which corresponds with U.S. Appl. No. 14/536,426, 1 page.

Letters Patent, dated Aug. 10, 2016, received in European Patent Application No. 13724100.6, which corresponds with U.S. Appl. No. 14/536,426, 1 page.

Office Action, dated Jan. 20, 2017, received in European Patent Application No. 15183980.0, which corresponds with U.S. Appl. No. 14/536,426, 5 pages.

Office Action, dated Aug. 21, 2017, received in European Patent Application No. 15183980.0, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Intention to Grant, dated Mar. 9, 2018, received in European Patent Application No. 15183980.0, which corresponds with U.S. Appl. No. 14/536,426, 5 pages.

Intention to Grant, dated Aug. 14, 2018, received in European Patent Application No. 15183980.0, which corresponds with U.S. Appl. No. 14/536,426, 5 pages.

Decision to Grant, dated Jan. 10, 2019, received in European Patent Application No. 15183980.0, which corresponds with U.S. Appl. No. 14/536,426, 4 pages.

Patent, dated Feb. 6, 2019, received in European Patent Application No. 15183980.0, which corresponds with U.S. Appl. No. 14/536,426, 4 pages.

Office Action, dated Sep. 6, 2019, received in European Patent Application No. 18180503.7, which corresponds with U.S. Appl. No. 14/536,426, 5 pages.

Certificate of Grant, dated Nov. 10, 2017, received in Hong Kong Patent Application No. 15107535.0, which corresponds with U.S. Appl. No. 14/536,426, 2 pages.

Certificate of Grant, dated Jul. 5, 2019, received in Hong Kong Patent Application No. 15108892.5, which corresponds with U.S. Appl. No. 14/536,426, 5 pages.

Patent, dated Nov. 22, 2019, received in Hong Kong Patent Application No. 16107033.6, which corresponds with U.S. Appl. No. 14/536,426, 6 pages.

Office Action, dated Mar. 4, 2016, received in Japanese Patent Application No. 2015-511644, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Office Action, dated Feb. 6, 2017, received in Japanese Patent Application No. 2015-511644, which corresponds with U.S. Appl. No. 14/536,426, 6 pages.

Notice of Allowance, dated Dec. 8, 2017, received in Japanese Patent Application No. 2015-511644, which corresponds with U.S. Appl. No. 14/536,426, 6 pages.

Patent, dated Jan. 12, 2018, received in Japanese Patent Application No. 2015-511644, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Office Action, dated Nov. 6, 2018, received in Japanese Patent Application No. 2018-000753, which corresponds with U.S. Appl. No. 14/536,426, 8 pages.

Office Action, dated Oct. 7, 2019, received in Japanese Patent Application No. 2018-000753, which corresponds with U.S. Appl. No. 14/536,426, 5 pages.

Office Action, dated Mar. 9, 2017, received in U.S. Appl. No. 14/536,464, 21 pages.

Final Office Action, dated Aug. 25, 2017, received in U.S. Appl. No. 14/536,464, 30 pages.

Office Action, dated Feb. 12, 2018, received in U.S. Appl. No. 14/536,464, 33 pages.

Final Office Action, dated Jun. 22, 2018, received in U.S. Appl. No. 14/536,464, 32 pages.

Office Action, dated Sep. 25, 2017, received in U.S. Appl. No. 14/536,644, 29 pages.

Final Office Action, dated May 3, 2018, received in U.S. Appl. No. 14/536,644, 28 pages.

Office Action, dated Nov. 2, 2018, received in U.S. Appl. No. 14/536,644, 24 pages.

Notice of Allowance, dated Jul. 2, 2019, received in U.S. Appl. No. 14/536,644, 5 pages.

Office Action, dated Oct. 19, 2017, received in U.S. Appl. No. 14/608,926, 14 pages.

Final Office Action, dated Jun. 6, 2018, received in U.S. Appl. No. 14/608,926, 19 pages.

Notice of Allowance, dated Apr. 10, 2019, received in U.S. Appl. No. 14/608,926, 16 pages.

Notice of Allowance, dated May 21, 2019, received in U.S. Appl. No. 14/608,926, 5 pages.

Office Action, dated Feb. 1, 2016, received in Australian Patent Application No. 2013368441, which corresponds with U.S. Appl. No. 14/608,926, 3 pages.

Notice of Allowance, dated Mar. 30, 2016, received in Australian Patent Application No. 2013368441, which corresponds with U.S. Appl. No. 14/608,926, 1 page.

Certificate of Grant, dated Jul. 29, 2016, received in Australian Patent Application No. 2013368441, which corresponds with U.S. Appl. No. 14/608,926, 1 page.

Office Action, dated Jan. 3, 2017, received in Australian Patent Application No. 2016201451, which corresponds with U.S. Appl. No. 14/608,926, 3 pages.

Notice of Acceptance, dated Dec. 20, 2017, received in Australian Patent Application No. 2016201451, which corresponds with U.S. Appl. No. 14/608,926, 3 pages.

Certificate of Grant, dated May 3, 2018, received in Australian Patent Application No. 2016201451, which corresponds with U.S. Appl. No. 14/608,926, 1 page.

Office Action, dated May 4, 2017, received in Chinese Patent Application No. 201380068414.1, which corresponds with U.S. Appl. No. 14/608,926, 5 pages.

Notice of Allowance, dated Feb. 8, 2018, received in Chinese Patent Application No. 201380068414.1, which corresponds with U.S. Appl. No. 14/608,926, 2 pages.

Patent, dated May 4, 2018, received in Chinese Patent Application No. 201380068414.1, which corresponds with U.S. Appl. No. 14/608,926, 4 pages.

Office Action, dated Apr. 21, 2016, received in European Patent Application No. 13795392.3, which corresponds with U.S. Appl. No. 14/608,926, 6 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Office Action, dated May 6, 2016, received in European Patent Application No. 13795392.3, which corresponds with U.S. Appl. No. 14/608,926, 6 pages.

Office Action, dated Nov. 11, 2016, received in European Patent Application No. 13795392.3, which corresponds with U.S. Appl. No. 14/608,926, 6 pages.

Office Action, dated Jul. 4, 2017, received in European Patent Application No. 13795392.3, which corresponds with U.S. Appl. No. 14/608,926, 4 pages.

Oral Summons, dated Feb. 13, 2017, received in European Patent Application No. 13795392.3, which corresponds with U.S. Appl. No. 14/608,926, 11 pages.

Office Action, dated Mar. 14, 2016, received in Japanese Patent Application No. 2015-549392, which corresponds with U.S. Appl. No. 14/608,926, 4 pages.

Notice of Allowance, dated Jan. 17, 2017, received in Japanese Patent Application No. 2015-549392, which corresponds with U.S. Appl. No. 14/608,926, 2 pages.

Patent, dated Feb. 17, 2017, received in Japanese Patent Application No. 2015-549392, which corresponds with U.S. Appl. No. 14/608,926, 3 pages.

Patent, dated Apr. 27, 2018, received in Japanese Patent Application No. 2017-024234, which corresponds with U.S. Appl. No. 14/608,926, 3 pages.

Office Action, dated Feb. 22, 2019, received in Japanese Patent Application No. 2018-079290, which corresponds with U.S. Appl. No. 14/608,926, 7 pages.

Office Action, dated Sep. 30, 2019, received in Japanese Patent Application No. 2018-079290, which corresponds with U.S. Appl. No. 14/608,926, 5 pages.

Office Action, dated May 12, 2016, received in Korean Patent Application No. 10-2015-7018853, which corresponds with U.S. Appl. No. 14/608,926, 4 pages.

Notice of Allowance, dated Mar. 31, 2017, received in Korean Patent Application No. 2015-7018853, which corresponds with U.S. Appl. No. 14/608,926, 4 pages.

Patent, dated Jun. 30, 2017, received in Korean Patent Application No. 2015-7018853, which corresponds with U.S. Appl. No. 14/608,926, 3 pages.

Office Action, dated Aug. 22, 2017, received in Korean Patent Application No. 2017-7018250, which corresponds with U.S. Appl. No. 14/608,926, 2 pages.

Notice of Allowance, dated Dec. 29, 2017, received in Korean Patent Application No. 2017-7018250, which corresponds with U.S. Appl. No. 14/608,926, 3 pages.

Office Action, dated Oct. 19, 2017, received in U.S. Appl. No. 14/536,646, 21 pages.

Notice of Allowance, dated Aug. 9, 2018, received in U.S. Appl. No. 14/536,646, 5 pages.

Office Action, dated Jul. 17, 2015, received in Australian Patent Application No. 2013259613, which corresponds with U.S. Appl. No. 14/536,646, 5 pages.

Office Action, dated May 31, 2016, received in Australian Patent Application No. 2013259613, which corresponds with U.S. Appl. No. 14/536,646, 4 pages.

Notice of Allowance, dated Jul. 5, 2016, received in Australian Patent Application No. 2013259613, which corresponds with U.S. Appl. No. 14/536,646, 3 pages.

Office Action, dated Jun. 6, 2019, received in Australian Patent Application No. 2018256626, which corresponds with U.S. Appl. No. 14/536,646, 3 pages.

Notice of Acceptance, dated Aug. 1, 2019, received in Australian Patent Application No. 2018256626, which corresponds with U.S. Appl. No. 14/536,646, 3 pages.

Office Action, dated Dec. 1, 2016, received in Chinese Patent Application No. 2013800362059, which corresponds with U.S. Appl. No. 14/536,646, 3 pages.

Notice of Allowance, dated Oct. 9, 2017, received in Chinese Patent Application No. 2013800362059, which corresponds with U.S. Appl. No. 14/536,646, 3 pages.

Office Action, dated Nov. 12, 2015, received in European Patent Application No. 13724102.2, which corresponds with U.S. Appl. No. 14/536,646, 6 pages.

Office Action, dated May 31, 2016, received in European Patent Application No. 13724102.2, which corresponds with U.S. Appl. No. 14/536,646, 5 pages.

Notice of Allowance, dated Jan. 4, 2017, received in European Patent Application No. 13724102.2, which corresponds with U.S. Appl. No. 14/536,646, 5 pages.

Patent, dated May 26, 2017, received in European Patent Application No. 13724102.2, which corresponds with U.S. Appl. No. 14/536,646, 1 page.

Office Action, dated Feb. 29, 2016, received in Japanese Patent Application No. 2015-511645, which corresponds with U.S. Appl. No. 14/536,646, 5 pages.

Notice of Allowance, dated Dec. 22, 2016, received in Japanese Patent Application No. 2015-511645, which corresponds with U.S. Appl. No. 14/536,646, 2 pages.

Certificate of Grant, dated Jan. 25, 2019, received in Hong Kong Patent Application No. 2015-511645, which corresponds with U.S. Appl. No. 14/536,646, 4 pages.

Office Action, dated Apr. 3, 2017, received in U.S. Appl. No. 14/536,646, 11 pages.

Notice of Allowance, dated Sep. 20, 2017, received in U.S. Appl. No. 14/536,646, 10 pages.

Office Action, dated Aug. 27, 2015, received in Australian Patent Application No. 2013259614, which corresponds with U.S. Appl. No. 14/536,646, 4 pages.

Notice of Allowance, dated Aug. 15, 2016, received in Australian Patent Application No. 2013259614, which corresponds with U.S. Appl. No. 14/536,646, 1 page.

Office Action, dated Jul. 21, 2017, received in Australian Patent Application No. 2016262773, which corresponds with U.S. Appl. No. 14/536,646, 3 pages.

Notice of Acceptance, dated Jul. 19, 2018, received in Australian Patent Application No. 2016262773, which corresponds with U.S. Appl. No. 14/536,646, 3 pages.

Office Action, dated Jun. 5, 2019, received in Australian Patent Application No. 2018256616, which corresponds with U.S. Appl. No. 14/536,646, 3 pages.

Office Action, dated Mar. 3, 2017, received in Chinese Patent Application No. 201380035893.7, which corresponds with U.S. Appl. No. 14/536,646, 8 pages.

Office Action, dated Feb. 2, 2018, received in Chinese Patent Application No. 201380035893.7, which corresponds with U.S. Appl. No. 14/536,646, 5 pages.

Notice of Allowance, dated Aug. 31, 2018, received in Chinese Patent Application No. 201380035893.7, which corresponds with U.S. Appl. No. 14/536,646, 6 pages.

Patent, dated Oct. 23, 2018, received in Chinese Patent Application No. 201380035893.7, which corresponds with U.S. Appl. No. 14/536,646, 4 pages.

Office Action, dated Jan. 7, 2016, received in European Patent Application No. 13726053.5, which corresponds with U.S. Appl. No. 14/536,646, 10 pages.

Office Action, dated Aug. 31, 2016, received in European Patent Application No. 13726053.5, which corresponds with U.S. Appl. No. 14/536,646, 10 pages.

Office Action, dated Apr. 9, 2018, received in European Patent Application No. 13726053.5, which corresponds with U.S. Appl. No. 14/536,646, 9 pages.

Office Action, dated Mar. 7, 2019, received in European Patent Application No. 13726053.5, which corresponds with U.S. Appl. No. 14/536,646, 5 pages.

Intention to Grant, dated Sep. 6, 2019, received in European Patent Application No. 13726053.5, which corresponds with U.S. Appl. No. 14/536,646, 7 pages.

Office Action, dated Feb. 29, 2016, received in Japanese Patent Application No. 2015-511646, which corresponds with U.S. Appl. No. 14/536,646, 3 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Office Action, dated Oct. 25, 2016, received in Japanese Patent Application No. 2015-511646, which corresponds with U.S. Appl. No. 14/536,141, 6 pages.

Notice of Allowance, dated Jun. 30, 2017, received in Japanese Patent Application No. 2015-511646, which corresponds with U.S. Appl. No. 14/536,141, 5 pages.

Patent, dated Jul. 28, 2017, received in Japanese Patent Application No. 2015-511646, which corresponds with U.S. Appl. No. 14/536,141, 3 pages.

Office Action, dated Aug. 10, 2018, received in Japanese Patent Application No. 2017-141953, which corresponds with U.S. Appl. No. 14/536,141, 6 pages.

Office Action, dated Jul. 5, 2019, received in Japanese Patent Application No. 2017-141953, which corresponds with U.S. Appl. No. 14/536,141, 6 pages.

Office Action, dated Dec. 8, 2016, received in U.S. Appl. No. 14/608,942, 9 pages.

Notice of Allowance, dated May 12, 2017, received in U.S. Appl. No. 14/608,942, 10 pages.

Office Action, dated Jan. 29, 2016, received in Australian Patent Application No. 2013368443, which corresponds with U.S. Appl. No. 14/608,942, 3 pages.

Notice of Allowance, dated Mar. 11, 2016, received in Australian Patent Application No. 2013368443, which corresponds with U.S. Appl. No. 14/608,942, 2 pages.

Certificate of Grant, dated Jul. 7, 2016, received in Australian Patent Application No. 2013368443, which corresponds with U.S. Appl. No. 14/608,942, 3 pages.

Office Action, dated Mar. 29, 2017, received in Australian patent Application No. 2016201303, which corresponds with U.S. Appl. No. 14/608,942, 3 pages.

Notice of Acceptance, dated Mar. 7, 2018, received in Australian patent Application No. 2016201303, which corresponds with U.S. Appl. No. 14/608,942, 3 pages.

Certificate of Grant, dated Jul. 5, 2018, received in Australian patent Application No. 2016201303, which corresponds with U.S. Appl. No. 14/608,942, 4 pages.

Office Action, dated Jun. 16, 2017, received in Chinese Patent Application No. 201380068295.X, which corresponds with U.S. Appl. No. 14/608,942, 6 pages.

Office Action, dated Mar. 28, 2018, received in Chinese Patent Application No. 201380068295.X, which corresponds with U.S. Appl. No. 14/608,942, 5 pages.

Office Action, dated Oct. 8, 2018, received in Chinese Patent Application No. 201380068295.X, which corresponds with U.S. Appl. No. 14/608,942, 3 pages.

Notice of Allowance, dated May 7, 2019, received in Chinese Patent Application No. 201380068295.X, which corresponds with U.S. Appl. No. 14/608,942, 3 pages.

Patent, dated Jul. 5, 2019, received in Chinese Patent Application No. 201380068295.X, which corresponds with U.S. Appl. No. 14/608,942, 8 pages.

Office Action, dated Oct. 7, 2016, received in European Patent Application No. 13798464.7, which corresponds with U.S. Appl. No. 14/608,942, 7 pages.

Decision to Grant, dated Sep. 13, 2018, received in European Patent Application No. 13798464.7, which corresponds with U.S. Appl. No. 14/608,942, 2 pages.

Intent on to Grant, dated Nov. 8, 2019, received in European Patent Application No. 18194127.9, which corresponds with U.S. Appl. No. 14/608,942, 7 pages.

Certificate of Grant, dated Jul. 26, 2019, received in Hong Kong, which corresponds with U.S. Appl. No. 14/608,942, 4 pages.

Office Action, dated Jul. 4, 2016, received in Japanese Patent Application No. 2015-549393, which corresponds with U.S. Appl. No. 14/608,942, 4 pages.

Notice of Allowance, dated May 12, 2017, received in Japanese Patent Application No. 2015-549393, which corresponds with U.S. Appl. No. 14/608,942, 5 pages.

Patent, dated Jun. 16, 2017, received in Japanese Patent Application No. 2015-549393, which corresponds with U.S. Appl. No. 14/608,942, 3 pages.

Office Action, dated Apr. 5, 2016, received in Korean Patent Application No. 2015-7018448, which corresponds with U.S. Appl. No. 14/608,942, 6 pages.

Office Action, dated Feb. 24, 2017, received in Korean Patent Application No. 2015-7018448, which corresponds with U.S. Appl. No. 14/608,942, 4 pages.

Notice of Allowance, dated Jan. 15, 2019, received in Korean Patent Application No. 2015-7018448, which corresponds with U.S. Appl. No. 14/608,942, 5 pages.

Patent, dated Mar. 8, 2019, received in Korean Patent Application No. 2015-7018448, which corresponds with U.S. Appl. No. 14/608,942, 4 pages.

Office Action, dated Jul. 17, 2017, received in U.S. Appl. No. 14/536,166, 19 pages.

Notice of Allowance, dated Feb. 28, 2018, received in U.S. Appl. No. 14/536,166, 5 pages.

Office Action, dated Aug. 1, 2016, received in U.S. Appl. No. 14/536,203, 14 pages.

Notice of Allowance, dated Feb. 1, 2017, received in U.S. Appl. No. 14/536,203, 9 pages.

Office Action, dated Jul. 9, 2015, received in Australian Patent Application No. 2013259630, which corresponds with U.S. Appl. No. 14/536,203, 3 pages.

Notice of Allowance, dated Jun. 15, 2016, received in Australian Patent Application No. 2013259630, which corresponds with U.S. Appl. No. 14/536,203, 3 pages.

Certificate of Grant, dated Oct. 21, 2016, received in Australian Patent Application No. 2013259630, which corresponds with U.S. Appl. No. 14/536,203, 3 pages.

Office Action, dated Jul. 4, 2017, received in Australian Patent Application No. 2016238917, which corresponds with U.S. Appl. No. 14/536,203, 5 pages.

Notice of Acceptance, dated Jul. 19, 2018, received in Australian Patent Application No. 2016238917, which corresponds with U.S. Appl. No. 14/536,203, 3 pages.

Certificate of Grant, dated Nov. 1, 2018, received in Australian Patent Application No. 2016238917, which corresponds with U.S. Appl. No. 14/536,203, 1 page.

Office Action, dated Aug. 20, 2018, received in Australian Patent Application No. 2018250481, which corresponds with U.S. Appl. No. 14/536,203, 2 pages.

Office Action, dated Oct. 25, 2017, received in Chinese Patent Application No. 201380035977.0, which corresponds with U.S. Appl. No. 14/536,203, 5 pages.

Notice of Allowance, dated Apr. 4, 2018, received in Chinese Patent Application No. 201380035977.0, which corresponds with U.S. Appl. No. 14/536,203, 3 pages.

Patent, dated Jul. 6, 2018, received in Chinese Patent Application No. 201380035977.0, which corresponds with U.S. Appl. No. 14/536,203, 4 pages.

Office Action, dated Nov. 11, 2015, received in European Patent Application No. 13724104.8, which corresponds with U.S. Appl. No. 14/536,203, 5 pages.

Office Action, dated May 31, 2016, received in European Patent Application No. 13724104.8, which corresponds with U.S. Appl. No. 14/536,203, 5 pages.

Office Action, dated Dec. 6, 2017, received in European Patent Application No. 13724104.8, which corresponds with U.S. Appl. No. 14/536,203, 9 pages.

Decision to Grant, dated Oct. 24, 2018, received in European Patent Application No. 13724104.8, which corresponds with U.S. Appl. No. 14/536,203, 5 pages.

Intention to Grant, dated Mar. 18, 2019, received in European Patent Application No. 13724104.8, which corresponds with U.S. Appl. No. 14/536,203, 9 pages.

Decision to Grant, dated Aug. 8, 2019, received in European Patent Application No. 13724104.8, which corresponds with U.S. Appl. No. 14/536,203, 1 page.

(56)

**References Cited**

## OTHER PUBLICATIONS

Certificate of Grant, dated Sep. 4, 2019, received in European Patent Application No. 13724104.8, which corresponds with U.S. Appl. No. 14/536,203, 4 pages.

Patent, dated Sep. 27, 2019, received in Hong Kong Patent Application No. 15108904.1, which corresponds with U.S. Appl. No. 14/536,203, 6 pages.

Office Action, dated Feb. 15, 2016, received in Japanese Patent Application No. 2015-511650, which corresponds with U.S. Appl. No. 14/536,203, 5 pages.

Notice of Allowance, dated Aug. 5, 2016, received in Japanese Patent Application No. 2015-511650, which corresponds with U.S. Appl. No. 14/536,203, 4 pages.

Certificate of Patent, dated Sep. 9, 2016, received in Japanese Patent Application No. 2015-511650, which corresponds with U.S. Appl. No. 14/536,203, 3 pages.

Office Action, dated Jun. 23, 2017, received in Japanese Patent Application No. 2016173113, which corresponds with U.S. Appl. No. 14/536,203, 5 pages.

Notice of Allowance, dated Jan. 12, 2018, received in Japanese Patent Application No. 2016173113, which corresponds with U.S. Appl. No. 14/536,203, 5 pages.

Patent, dated Feb. 16, 2018, received in Japanese Patent Application No. 2016173113, which corresponds with U.S. Appl. No. 14/536,203, 3 pages.

Office Action, dated Oct. 19, 2018, received in Japanese Patent Application No. 2018-022394, which corresponds with U.S. Appl. No. 14/536,203, 4 pages.

Office Action, dated Sep. 30, 2019, received in Japanese Patent Application No. 2018-022394, which corresponds with U.S. Appl. No. 14/536,203, 5 pages.

Office Action, dated Dec. 4, 2015, received in Korean Patent Application No. 2014-7034520, which corresponds with U.S. Appl. No. 14/536,203, 4 pages.

Notice of Allowance, dated Sep. 1, 2016, received in Korean Patent Application No. 2014-7034520, which corresponds with U.S. Appl. No. 14/536,203, 5 pages.

Office Action, dated Feb. 6, 2017, received in Korean Patent Application No. 2016-7033834, which corresponds with U.S. Appl. No. 14/536,203, 4 pages.

Notice of Allowance, dated Oct. 30, 2017, received in Korean Patent Application No. 2016-7033834, which corresponds with U.S. Appl. No. 14/536,203, 5 pages.

Patent, dated Jan. 23, 2018, received in Korean Patent Application No. 2016-7033834, which corresponds with U.S. Appl. No. 14/536,203, 4 pages.

Office Action, dated Oct. 20, 2017, received in U.S. Appl. No. 14/608,965, 14 pages.

Office Action, dated Jul. 2, 2018, received in U.S. Appl. No. 14/608,965, 16 pages.

Final Office Action, dated Jan. 10, 2019, received in U.S. Appl. No. 14/608,965, 17 pages.

Notice of Allowance dated Nov. 7, 2019, received in U.S. Appl. No. 14/608,965, 17 pages.

Office action, dated Oct. 11, 2017, received in Chinese Patent Application No. 201380074060.1, which corresponds with U.S. Appl. No. 14/608,965, 5 pages.

Office action, dated Aug. 1, 2018, received in Chinese Patent Application No. 201380074060.1, which corresponds with U.S. Appl. No. 14/608,965, 5 pages.

Office action, dated Nov. 1, 2018, received in Chinese Patent Application No. 201380074060.1, which corresponds with U.S. Appl. No. 14/608,965, 3 pages.

Office action, dated Apr. 3, 2019, received in Chinese Patent Application No. 201380074060.1, which corresponds with U.S. Appl. No. 14/608,965, 3 pages.

Patent, dated May 17, 2019, received in Chinese Patent Application No. 201380074060.1, which corresponds with U.S. Appl. No. 14/608,965, 6 pages.

Office Action, dated Jul. 22, 2016, received in European Office Action No. 13798465.4, which corresponds with U.S. Appl. No. 14/608,965, 3 pages.

Oral Proceedings, dated Mar. 7, 2018, received in European Office Action No. 13798465.4, which corresponds with U.S. Appl. No. 14/608,965, 5 pages.

Decision to Grant, dated Sep. 6, 2018, received in European Office Action No. 13798465.4, which corresponds with U.S. Appl. No. 14/608,965, 2 pages.

Office Action, dated Oct. 20, 2016, received in U.S. Appl. No. 14/536,247, 10 pages.

Final Office Action, dated Mar. 24, 2017, received in U.S. Appl. No. 14/536,247, 14 pages.

Notice of Allowance, dated Nov. 22, 2017, received in U.S. Appl. No. 14/536,247, 6 pages.

Office Action, dated Mar. 24, 2017, received in U.S. Appl. No. 14/536,267, 12 pages.

Notice of Allowance, dated Nov. 9, 2017, received in U.S. Appl. No. 14/536,267, 8 pages.

Notice of Allowance, dated Jun. 1, 2018, received in U.S. Appl. No. 14/536,267, 5 pages.

Office Action, dated Aug. 10, 2015, received in Australian Patent Application No. 2013259637, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Notice of Allowance, dated Jun. 28, 2016, received in Australian Patent Application No. 2013259637, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Certificate of Grant, dated Oct. 21, 2016, received in Australian Patent Application No. 2013259637, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Office Action, dated Mar. 24, 2017, received in Australian Patent Application No. 2016204411, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Notice of Acceptance, dated Feb. 27, 2018, received in Australian Patent Application No. 2016204411, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Certificate of Grant, dated Jun. 28, 2018, received in Australian Patent Application No. 2016204411, which corresponds with U.S. Appl. No. 14/536,267, 4 pages.

Office Action, dated Mar. 15, 2019, received in Australian Patent Application No. 2018204236, which corresponds with U.S. Appl. No. 14/5326,267, 5 pages.

Notice of Acceptance, dated Apr. 29, 2019, received in Australian Patent Application No. 2018204236, which corresponds with U.S. Appl. No. 14/5326,267, 3 pages.

Certificate of Grant, dated Aug. 28, 2019, received in Australian Patent Application No. 2018204236, which corresponds with U.S. Appl. No. 14/5326,267, 4 pages.

Office Action, dated Dec. 9, 2016, received in Chinese Patent Application No. 2016120601564130, which corresponds with U.S. Appl. No. 14/536,267, 4 pages.

Notice of Allowance, dated Jan. 29, 2018, received in Chinese Patent Application No. 201380035968.1, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Patent, dated Apr. 20, 2018, received in Chinese Patent Application No. 201380035968.1, which corresponds with U.S. Appl. No. 14/536,267, 4 pages.

Office Action, dated Nov. 28, 2018, received in Chinese Patent Application No. 201610537334.1, which corresponds with U.S. Appl. No. 14/536,267, 5 pages.

Office Action, dated Jul. 11, 2019, received in Chinese Patent Application No. 201610537334.1, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Office Action, dated Sep. 30, 2019, received in Chinese Patent Application No. 201610537334.1, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Office Action, dated Jun. 13, 2018, received in Chinese Patent Application No. 201810332044.2, which corresponds with U.S. Appl. No. 14/536,267, 2 pages.

Office Action, dated Jan. 25, 2018, received in European Patent Application No. 13724106.3, which corresponds with U.S. Appl. No. 14/536,267, 5 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Intention to Grant, dated Jun. 27, 2018, received in European Patent Application No. 13724106.3, which corresponds with U.S. Appl. No. 14/536,267, 5 pages.

Decision to Grant, dated Oct. 18, 2018, received in European Patent Application No. 13724106.3, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Grant Certificate, dated Nov. 14, 2018, received in European Patent Application No. 13724106.3, which corresponds with U.S. Appl. No. 14/536,267, 3 pages. 4 pages.

Office Action, dated Sep. 13, 2017, received in European Patent Application No. 16177863.4, which corresponds with U.S. Appl. No. 14/536,267, 6 pages.

Decision to Grant, dated Nov. 29, 2018, received in European Patent Application No. 16177863.4, which corresponds with U.S. Appl. No. 14/536,267, 4 pages.

Patent, dated Dec. 26, 2018, received in European Patent Application No. 16177863.4, which corresponds with U.S. Appl. No. 14/536,267, 4 pages.

Office Action, dated Aug. 29, 2019, received in European Patent Application No. 18183789.9, which corresponds with U.S. Appl. No. 16/262,800, 9 pages.

Patent, dated Aug. 30, 2019, received in Hong Kong Patent Application No. 15107537.8, which corresponds with U.S. Appl. No. 14/536,267, 9 pages.

Patent, dated Nov. 8, 2019, received in Hong Kong Patent Application No. 15108890.7, which corresponds with U.S. Appl. No. 14/536,267, 4 pages.

Office Action, dated Jan. 29, 2016, received in Japanese Patent Application No. 2015-511652, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Notice of Allowance, dated Sep. 26, 2016, received in Japanese Patent Application No. 2015-511652, which corresponds with U.S. Appl. No. 14/536,267, 5 pages.

Office Action, dated Mar. 3, 2017, received in Japanese Patent Application No. 2016-125839, which corresponds with U.S. Appl. No. 14/536,267, 6 pages.

Notice of Allowance, dated Nov. 17, 2017, received in Japanese Patent Application No. 2016-125839, which corresponds with U.S. Appl. No. 14/536,267, 5 pages.

Office Action, dated Feb. 4, 2019, received in Japanese Patent Application No. 2017-237035, which corresponds with U.S. Appl. No. 14/536,267, 7 pages.

Notice of Allowance, dated Sep. 9, 2019, received in Japanese Patent Application No. 2017-237035, which corresponds with U.S. Appl. No. 14/536,267, 5 pages.

Patent, dated Sep. 27, 2019, received in Japanese Patent Application No. 2017-237035, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Office Action, dated Dec. 4, 2015, received in Korean Patent Application No. 2014-7034530, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Notice of Allowance, dated Sep. 1, 2016, received in Korean Patent Application No. 2014-7034530, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Office Action, dated Jan. 5, 2017, received in Korean Patent Application No. 2016-7029533, which corresponds with U.S. Appl. No. 14/536,267, 2 pages.

Notice of Allowance, dated Sep. 1, 2017, received in Korean Patent Application No. 2016-7029533, which corresponds with U.S. Appl. No. 14/536,267, 4 pages.

Patent, dated Dec. 1, 2017, received in Korean Patent Application No. 2016-7029533, which corresponds with U.S. Appl. No. 14/536,267, 2 pages.

Office Action, dated Jan. 29, 2018, received in Korean Patent Application No. 2017-7034838, which corresponds with U.S. Appl. No. 14/536,267, 4 pages.

Notice of Allowance, dated Dec. 3, 2018, received in Korean Patent Application No. 2017-7034838, which corresponds with U.S. Appl. No. 14/536,267, 5 pages.

Patent, dated Mar. 4, 2019, received in Korean Patent Application No. 2017-7034838, which corresponds with U.S. Appl. No. 14/536,267, 4 pages.

Office Action, dated Apr. 7, 2017, received in U.S. Appl. No. 14/536,291, 11 pages.

Notice of Allowance, dated Dec. 1, 2017, received in U.S. Appl. No. 14/536,291, 19 pages.

Notice of Allowance, dated Mar. 20, 2018, received in U.S. Appl. No. 14/536,291, 5 pages.

Office Action, dated Aug. 18, 2015, received in Australian Patent Application No. 2013259642, which corresponds with U.S. Appl. No. 14/536,291, 3 pages.

Office Action, dated Jul. 25, 2016, received in Australian Patent Application No. 2013259642, which corresponds with U.S. Appl. No. 14/536,291, 3 pages.

Office Action, dated Aug. 10, 2016, received in Australian Patent Application No. 2013259642, which corresponds with U.S. Appl. No. 14/536,291, 4 pages.

Office Action, dated Jul. 21, 2017, received in Australian Patent Application No. 2016216658, which corresponds with U.S. Appl. No. 14/536,291, 3 pages.

Notice of Acceptance, dated Jul. 19, 2018, received in Australian Patent Application No. 2016216658, which corresponds with U.S. Appl. No. 14/536,291, 3 pages.

Patent, dated Nov. 30, 2018, received in Australian Patent Application No. 2016216658, which corresponds with U.S. Appl. No. 14/536,291, 4 pages.

Innovation Patent, dated Sep. 1, 2016, received in Australian Patent Application No. 2016101481, which corresponds with U.S. Appl. No. 14/536,291, 1 page.

Office Action, dated Sep. 29, 2016, received in Australian Patent Application No. 2016101481, which corresponds with U.S. Appl. No. 14/536,291, 3 pages.

Office Action, dated Oct. 23, 2017, received in Chinese Patent Application No. 201380035986.X, which corresponds with U.S. Appl. No. 14/536,291, 9 pages.

Office Action, dated Jan. 7, 2016, received in European Patent Application No. 13724107.1, which corresponds with U.S. Appl. No. 14/536,291, 11 pages.

Office Action, dated Aug. 22, 2016, received in European Patent Application No. 13724107.1, which corresponds with U.S. Appl. No. 14/536,291, 7 pages.

Office Action, dated Mar. 23, 2017, received in European Patent Application No. 13724107.1, which corresponds with U.S. Appl. No. 14/536,291, 8 pages.

Intention to Grant, dated Jan. 8, 2019, received in European Patent Application No. 17186744.3, which corresponds with U.S. Appl. No. 14/536,291, 7 pages.

Decision to Grant, dated Oct. 31, 2019, received in European Patent Application No. 17186744.3, which corresponds with U.S. Appl. No. 14/536,291, 3 pages.

Office Action, dated Mar. 8, 2016, received in Japanese Patent Application No. 2015-511655, which corresponds with U.S. Appl. No. 14/536,291, 4 pages.

Final Office Action, dated Dec. 22, 2016, received in Japanese Patent Application No. 2015-511655, which corresponds with U.S. Appl. No. 14/536,291, 3 pages.

Office Action, dated Jun. 29, 2018, received in Japanese Patent Application No. 2017-083027, which corresponds with U.S. Appl. No. 14/536,291, 5 pages.

Patent, dated Feb. 22, 2019, received in Japanese Patent Application No. 2017-083027, which corresponds with U.S. Appl. No. 14/536,291, 3 pages.

Notice of Allowance, dated Jan. 15, 2019, received in Japanese Patent Application No. 2017-083027, which corresponds with U.S. Appl. No. 14/536,291, 5 pages.

Office Action, dated Oct. 19, 2017, received in U.S. Appl. No. 14/608,985, 13 pages.

Notice of Allowance, dated Apr. 20, 2018, received in U.S. Appl. No. 14/608,985, 5 pages.

Office Action, dated Jan. 15, 2016, received in Australian Patent Application No. 2013368445, which corresponds with U.S. Appl. No. 14/608,985, 3 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Notice of Allowance, dated Jan. 18, 2017, received in Australian Patent Application No. 2013368445, which corresponds with U.S. Appl. No. 14/608,985, 3 pages.

Patent, dated May 18, 2017, received in Australian Patent Application No. 2013368445, which corresponds with U.S. Appl. No. 14/608,985, 1 page.

Office Action, dated May 19, 2017, received in Chinese Patent Application No. 201380068399.0, which corresponds with U.S. Appl. No. 14/608,985, 5 pages.

Notice of Allowance, dated Sep. 19, 2017, received in Chinese Patent Application No. 201380068399.0, which corresponds with U.S. Appl. No. 14/608,985, 3 pages.

Patent, dated Dec. 8, 2017, received in Chinese Patent Application No. 201380068399.0, which corresponds with U.S. Appl. No. 14/608,985, 4 pages.

Office Action, dated Jul. 25, 2016, received in European Patent Application No. 13811032.5, which corresponds with U.S. Appl. No. 14/608,985, 8 pages.

Office Action, dated Feb. 27, 2017, received in European Patent Application No. 13811032.5, which corresponds with U.S. Appl. No. 14/608,985, 6 pages.

Summons, dated Oct. 6, 2017, received in European Patent Application No. 13811032.5, which corresponds with U.S. Appl. No. 14/608,985, 6 pages.

Intention to Grant, dated Jan. 16, 2019, received in European Patent Application No. 13811032.5, which corresponds with U.S. Appl. No. 14/608,985, 9 pages.

Decision to Grant, dated Aug. 1, 2019, received in European Patent Application No. 13811032.5, which corresponds with U.S. Appl. No. 14/608,985, 2 pages.

Certificate of Grant, dated Aug. 28, 2019, received in European Patent Application No. 13811032.5, which corresponds with U.S. Appl. No. 14/608,985, 4 pages.

Certificate of Grant, dated Jun. 29, 2018, received in Hong Kong Patent Application No. 15112851.6, which corresponds with U.S. Appl. No. 14/608,985, 2 pages.

Office Action, dated Apr. 25, 2016, received in Japanese Patent Application No. 2015-550384, which corresponds with U.S. Appl. No. 14/608,985, 4 pages.

Notice of Allowance, dated Jan. 24, 2017, received in Japanese Patent Application No. 2015-550384, which corresponds with U.S. Appl. No. 14/608,985, 5 pages.

Patent, dated Feb. 24, 2017, received in Japanese Patent Application No. 2015-550384, which corresponds with U.S. Appl. No. 14/608,985, 2 pages.

Office Action, dated Nov. 4, 2016, received in Korean Patent Application No. 2015-7019984, which corresponds with U.S. Appl. No. 14/608,985, 8 pages.

Notice of Allowance, dated Sep. 19, 2017, received in Korean Patent Application No. 2015-7019984, which corresponds with U.S. Appl. No. 14/608,985, 4 pages.

Patent, dated Dec. 19, 2017, received in Korean Patent Application No. 2015-7019984, which corresponds with U.S. Appl. No. 14/608,985, 3 pages.

Office Action, dated Mar. 24, 2017, received in U.S. Appl. No. 14/609,006, 13 pages.

Final Office Action, dated Sep. 21, 2017, received in U.S. Appl. No. 14/609,006, 17 pages.

Office Action, dated Mar. 20, 2018, received in U.S. Appl. No. 14/609,006, 13 pages.

Office Action, dated Oct. 11, 2018, received in U.S. Appl. No. 14/609,006, 12 pages.

Final Office Action, dated May 23, 2019, received in U.S. Appl. No. 14/609,006, 14 pages.

Office Action, dated Apr. 19, 2017, received in U.S. Appl. No. 14/536,296, 12 pages.

Final Office Action, dated Nov. 2, 2017, received in U.S. Appl. No. 14/536,296, 13 pages.

Notice of Allowance, dated Mar. 14, 2018, received in U.S. Appl. No. 14/536,296, 8 pages.

Office Action, dated Nov. 1, 2017, received in U.S. Appl. No. 14/536,648, 22 pages.

Final Office Action, dated Aug. 7, 2018, received in U.S. Appl. No. 14/536,648, 14 pages.

Office Action, dated Jan. 2, 2019, received in U.S. Appl. No. 14/536,648, 12 pages.

Notice of Allowance, dated Jul. 2, 2019, received in U.S. Appl. No. 14/536,648, 5 pages.

Office Action, dated Jul. 21, 2017, received in Australian Patent Application No. 2016247194, which corresponds with U.S. Appl. No. 14/536,648, 3 pages.

Notice of Acceptance, dated Jul. 19, 2018, received in Australian Patent Application No. 2016247194, which corresponds with U.S. Appl. No. 14/536,648, 3 pages.

Intention to Grant, dated Apr. 1, 2019, received in European Patent Application No. 17153418.3, which corresponds with U.S. Appl. No. 14/536,648, 7 pages.

Decision to Grant, dated Aug. 16, 2019, received in European Patent Application No. 17153418.3, which corresponds with U.S. Appl. No. 14/536,648, 3 pages.

Grant Certificate, dated Sep. 11, 2019, received in European Patent Application No. 17153418.3, which corresponds with U.S. Appl. No. 14/536,648, 3 pages.

Office Action, dated Apr. 27, 2018, received in Japanese Patent Application No. 2017-008764, which corresponds with U.S. Appl. No. 14/536,648, 5 pages.

Notice of Allowance, dated Feb. 4, 2019, received in Japanese Patent Application No. 2017-008764, which corresponds with U.S. Appl. No. 14/536,648, 5 pages.

Patent, dated Mar. 1, 2019, received in Japanese Patent Application No. 2017-008764, which corresponds with U.S. Appl. No. 14/536,648, 3 pages.

Office Action, dated Jan. 19, 2017, received in U.S. Appl. No. 14/609,042, 12 pages.

Notice of Allowance, dated Jul. 10, 2017, received in U.S. Appl. No. 14/609,042, 8 pages.

Office Action, dated Aug. 24, 2018, received in Japanese Patent Application No. 2017-113598, which corresponds with U.S. Appl. No. 14/609,042, 6 pages.

Notice of Allowance, dated Apr. 9, 2019, received in Japanese Patent Application No. 2017-113598, which corresponds with U.S. Appl. No. 14/609,042, 5 pages.

Patent, dated Apr. 19, 2019, received in Japanese Patent Application No. 2017-113598, which corresponds with U.S. Appl. No. 14/609,042, 2 pages.

Notice of Allowance, dated Dec. 17, 2018, received in Korean Patent Application No. 2017-7008614, which corresponds with U.S. Appl. No. 14/609,042, 5 pages.

Patent, dated Mar. 8, 2019, received in Korean Patent Application No. 2017-7008614, which corresponds with U.S. Appl. No. 14/609,042, 4 pages.

Office Action, dated Mar. 31, 2016, received in U.S. Appl. No. 14/864,737, 17 pages.

Notice of Allowance, dated Feb. 27, 2017, received in U.S. Appl. No. 14/864,737, 9 pages.

Notice of Allowance, dated Jun. 19, 2017, received in U.S. Appl. No. 14/864,737, 8 pages.

Office Action, dated Apr. 16, 2018, received in Australian Patent Application No. 2016233792, which corresponds with U.S. Appl. No. 14/864,737, 2 pages.

Notice of Acceptance, dated Mar. 12, 2019, received in Australian Patent Application No. 2016233792, which corresponds with U.S. Appl. No. 14/864,737, 5 pages.

Certificate of Grant, dated Jul. 4, 2019, received in Australian Patent Application No. 2016233792, which corresponds with U.S. Appl. No. 14/864,737, 1 page.

Office Action, dated Sep. 11, 2018, received in Chinese Patent Application No. 201610159295.6, which corresponds with U.S. Appl. No. 14/864,737, 6 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Notice of Allowance, dated Apr. 17, 2019, received in Chinese Patent Application No. 201610159295.6, which corresponds with U.S. Appl. No. 14/864,737, 3 pages.

Patent, dated May 31, 2019, received in Chinese Patent Application No. 201610159295.6, which corresponds with U.S. Appl. No. 14/864,737, 7 pages.

Notice of Allowance, dated Jul. 1, 2016, received in Chinese Patent Application No. 201620214376.7, which corresponds with U.S. Appl. No. 14/864,737, 3 pages.

Patent, dated Aug. 3, 2016, received in Chinese Patent Application No. 201620214376.7, which corresponds with U.S. Appl. No. 14/864,737, 5 pages.

Certificate of Registration, dated Jun. 20, 2016, received in German Patent Application No. 202016001845.1, which corresponds with U.S. Appl. No. 14/864,737, 3 pages.

Office Action, dated Apr. 5, 2016, received in Danish Patent Application No. 201500577, which corresponds with U.S. Appl. No. 14/864,737, 7 pages.

Intention to Grant, dated Aug. 2, 2016, received in Danish Patent Application No. 201500577, which corresponds with U.S. Appl. No. 14/864,737, 2 pages.

Decision to grant, dated Mar. 29, 2018, received in European Patent Application No. 16710871.1, which corresponds with U.S. Appl. No. 14/864,737, 2 pages.

Grant Certificate, dated Apr. 25, 2018, received in European Patent Application No. 16710871.1, which corresponds with U.S. Appl. No. 14/864,737, 2 pages.

Office Action, dated May 15, 2017, received in Japanese Patent Application No. 2016-558331, which corresponds with U.S. Appl. No. 14/864,737, 5 pages.

Notice of Allowance, dated Jun. 23, 2017, received in Japanese Patent Application No. 2016-558331, which corresponds with U.S. Appl. No. 14/864,737, 5 pages.

Patent, dated Jul. 28, 2017, received in Japanese Patent Application No. 2016-558331, which corresponds with U.S. Appl. No. 14/864,737, 3 pages.

Office Action, dated Feb. 14, 2018, received in Korean Patent Application No. 2017-7030129, which corresponds with U.S. Appl. No. 14/864,737, 17 pages.

Patent, dated Dec. 26, 2018, received in Korean Patent Application No. 2017-7030129, which corresponds with U.S. Appl. No. 14/864,737, 4 pages.

Patent, dated Jul. 12, 2017, received in Dutch Patent Application No. 2016452, which corresponds with U.S. Appl. No. 14/864,737, 2 pages.

Office Action, dated Jun. 27, 2016, received in U.S. Appl. No. 14/866,981, 22 pages.

Notice of Allowance, dated Oct. 24, 2016, received in U.S. Appl. No. 14/866,981, 7 pages.

Notice of Allowance, dated Feb. 10, 2017, received in U.S. Appl. No. 14/866,981, 5 pages.

Office Action, dated May 10, 2016, received in Australian Patent Application No. 2016100254, which corresponds with U.S. Appl. No. 14/866,981, 6 pages.

Patent, dated Nov. 2, 2016, received in Australian Patent Application No. 2016100254, which corresponds with U.S. Appl. No. 14/866,981, 1 page.

Office Action, dated Nov. 5, 2018, received in Chinese Patent Application No. 201610131415.1, which corresponds with U.S. Appl. No. 14/866,981, 6 pages.

Office Action, dated Jul. 16, 2019, received in Chinese Patent Application No. 201610131415.1, which corresponds with U.S. Appl. No. 14/866,981, 4 pages.

Notice of Allowance, dated Jul. 27, 2016, received in Chinese Patent Application No. 201620176169.7, which corresponds with U.S. Appl. No. 14/866,981, 3 pages.

Patent, dated Sep. 28, 2016, received in Chinese Patent Application No. 201620176169.7, which corresponds with U.S. Appl. No. 14/866,981, 4 pages.

Certificate of Registration, dated Jun. 20, 2016, received in German Patent Application No. 202016001514.2, which corresponds with U.S. Appl. No. 14/864,737, 3 pages.

Office Action, dated Mar. 18, 2016, received in Danish Patent Application No. 201500575, which corresponds with U.S. Appl. No. 14/866,981, 9 pages.

Office Action, dated Dec. 5, 2016, received in Danish Patent Application No. 201500575, which corresponds with U.S. Appl. No. 14/866,981, 3 pages.

Office Action, dated Jul. 7, 2017, received in Danish Patent Application No. 201500575, 4 pages.

Patent, Nov. 16, 2017, received in Dutch Patent Application No. 2016375, which corresponds with U.S. Appl. No. 14/866,981, 2 pages.

Office Action, dated Dec. 15, 2017, received in U.S. Appl. No. 14/866,159, 35 pages.

Notice of Allowance, dated May 18, 2018, received in U.S. Appl. No. 14/866,159, 8 pages.

Office Action, dated May 19, 2016, received in Australian Patent Application No. 2016100251, which corresponds with U.S. Appl. No. 14/866,159, 5 pages.

Office Action, dated Jun. 5, 2018, received in Chinese Patent Application No. 201610137839.9, which corresponds with U.S. Appl. No. 14/866,159, 11 pages.

Notice of Allowance, dated Dec. 6, 2018, received in Chinese Patent Application No. 201610137839.9, which corresponds with U.S. Appl. No. 14/866,159, 3 pages.

Patent, dated Feb. 19, 2019, received in Chinese Patent Application No. 201610137839.9, which corresponds with U.S. Appl. No. 14/866,159, 6 pages.

Office Action, dated Jul. 5, 2016, received in Chinese Patent Application No. 201620186008.6, which corresponds with U.S. Appl. No. 14/866,159, 3 pages.

Certificate of Registration, dated Jun. 16, 2016, received in German Patent No. 202016001483.9, which corresponds with U.S. Appl. No. 14/866,159, 3 pages.

Office Action, dated Mar. 9, 2016, received in Danish Patent Application No. 201500574, which corresponds with U.S. Appl. No. 14/866,159, 11 pages.

Office Action, dated Sep. 27, 2016, received in Danish Patent Application No. 201500574, which corresponds with U.S. Appl. No. 14/866,159, 4 pages.

Office Action, dated Mar. 14, 2017, received in Danish Patent Application No. 201500574, which corresponds with U.S. Appl. No. 14/866,159, 5 pages.

Office Action, dated Jul. 6, 2017, received in Danish Patent Application No. 201500574, which corresponds with U.S. Appl. No. 14/866,159, 3 pages.

Office Action, dated Jan. 10, 2018, received in Danish Patent Application No. 201500574, which corresponds with U.S. Appl. No. 14/866,159, 2 pages.

Notice of Allowance, dated Mar. 21, 2018, received in Danish Patent Application No. 201500574, which corresponds with U.S. Appl. No. 14/866,159, 2 pages.

Patent, dated May 22, 2018, received in Danish Patent Application No. 201500574, which corresponds with U.S. Appl. No. 14/866,159, 2 pages.

Intention to Grant, dated Oct. 28, 2019, received in European Patent Application No. 16707356.8, which corresponds with U.S. Appl. No. 14/866,159, 7 pages.

Patent, dated Sep. 7, 2017, received in Dutch Patent Application No. 2016377, which corresponds with U.S. Appl. No. 14/866,159, 4 pages.

Office Action, dated Oct. 6, 2017, received in U.S. Appl. No. 14/868,078, 40 pages.

Notice of Allowance, dated May 24, 2018, received in U.S. Appl. No. 14/868,078, 6 pages.

Innovation Patent, dated Aug. 4, 2016, received in Australian Patent Application No. 2016101201, which corresponds with U.S. Appl. No. 14/868,078, 1 page.

Office Action, dated Oct. 12, 2016, received in Australian Patent Application No. 2016101201, which corresponds with U.S. Appl. No. 14/868,078, 3 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Notice of Allowance, dated Sep. 1, 2017, received in Australian Patent Application No. 2016229421, which corresponds with U.S. Appl. No. 14/868,078, 3 pages.

Certificate of Grant, dated Jan. 3, 2018, received in Australian Patent Application No. 2016229421, which corresponds with U.S. Appl. No. 14/868,078, 1 page.

Office Action, dated Feb. 7, 2019, received in Australian Patent Application No. 2017258967, which corresponds with U.S. Appl. No. 14/868,078, 3 pages.

Notice of Acceptance, dated Jun. 21, 2019, received in Australian Patent Application No. 2017258967, which corresponds with U.S. Appl. No. 14/868,078, 3 pages.

Certificate of Grant, dated Oct. 17, 2019, received in Australian Patent Application No. 2017258967, which corresponds with U.S. Appl. No. 14/868,078, 4 pages.

Office Action, dated Aug. 20, 2018, received in Chinese Patent Application No. 01610130348.1, which corresponds with U.S. Appl. No. 14/868,078, 6 pages.

Office Action, dated Feb. 26, 2019, received in Chinese Patent Application No. 01610130348.1, which corresponds with U.S. Appl. No. 14/868,078, 4 pages.

Notice of Allowance, dated May 6, 2019, received in Chinese Patent Application No. 01610130348.1, which corresponds with U.S. Appl. No. 14/868,078, 3 pages.

Patent, dated Jul. 5, 2019, received in Chinese Patent Application No. 201610130348.1, which corresponds with U.S. Appl. No. 14/868,078, 6 pages.

Notice of Allowance, dated Oct. 1, 2016, received in Chinese Patent Application No. 201620175847.8, which corresponds with U.S. Appl. No. 14/868,078, 1 page.

Office Action, dated Nov. 21, 2019, received in Chinese Patent Application No. 201680011338.4, which corresponds with U.S. Appl. No. 14/868,078, 8 pages.

Certificate of Registration, dated Jun. 30, 2016, received in German Patent Application No. 20201600156.9, which corresponds with U.S. Appl. No. 14/868,078, 3 pages.

Office Action, dated Mar. 30, 2016, received in Danish Patent Application No. 201500588, which corresponds with U.S. Appl. No. 14/868,078, 9 pages.

Office Action, dated Sep. 2, 2016, received in Danish Patent Application No. 201500588, which corresponds with U.S. Appl. No. 14/868,078, 4 pages.

Notice of Allowance, dated Jan. 30, 2017, received in received in Danish Patent Application No. 201500588, which corresponds with U.S. Appl. No. 14/868,078, 2 pages.

Notice of Allowance, dated May 2, 2017, received in received in Danish Patent Application No. 201500588, which corresponds with U.S. Appl. No. 14/868,078, 2 pages.

Patent, dated Sep. 11, 2017, received in Danish Patent Application No. 201500588, which corresponds with U.S. Appl. No. 14/868,078, 5 pages.

Office Action, dated Apr. 25, 2018, received in European Patent Application No. 16708916.8, which corresponds with U.S. Appl. No. 14/868,078, 6 pages.

Intention to Grant, dated May 10, 2019, received in European Patent Application No. 16708916.8, which corresponds with U.S. Appl. No. 14/868,078, 5 pages.

Decision to Grant, dated Sep. 12, 2019, received in European Patent Application No. 16708916.8, which corresponds with U.S. Appl. No. 14/868,078, 2 pages.

Patent, dated Oct. 9, 2019, received in European Patent Application No. 16708916.8, which corresponds with U.S. Appl. No. 14/868,078, 3 pages.

Office Action, dated Oct. 25, 2018, received in European Patent Application No. 17184437.6, which corresponds with U.S. Appl. No. 14/868,078, 6 pages.

Intention to Grant, dated May 22, 2019, received in European Patent Application No. 17184437.6, which corresponds with U.S. Appl. No. 14/868,078, 7 pages.

Decision to Grant, dated Sep. 19, 2019, received in European Patent Application No. 17184437.6, which corresponds with U.S. Appl. No. 14/868,078, 2 pages.

Patent, dated Oct. 16, 2019, received in European Patent Application No. 17184437.6, which corresponds with U.S. Appl. No. 14/868,078, 3 pages.

Patent, dated Jul. 12, 2017, received in Dutch Patent Application No. 2016376, which corresponds with U.S. Appl. No. 14/868,078, 2 pages.

Office Action, dated May 9, 2016, received in U.S. Appl. No. 14/863,432, 26 pages.

Notice of Allowance, dated Nov. 14, 2016, received in U.S. Appl. No. 14/863,432, 7 pages.

Notice of Allowance, dated Apr. 27, 2017, received in U.S. Appl. No. 14/863,432, 7 pages.

Notice of Allowance, dated Sep. 18, 2017, received in U.S. Appl. No. 14/863,432, 8 pages.

Office Action, dated Aug. 19, 2016, received in Australian Patent Application No. 2016100647, which corresponds with U.S. Appl. No. 14/863,432, 5 pages.

Office Action, dated Dec. 4, 2018, received in Chinese Patent Application No. 201610342313.4, which corresponds with U.S. Appl. No. 14/863,432, 5 pages.

Office Action, dated Jun. 17, 2019, received in Chinese Patent Application No. 201610342313.4, which corresponds with U.S. Appl. No. 14/863,432, 4 pages.

Office Action, dated Nov. 5, 2019, received in Chinese Patent Application No. 201610342313.4, which corresponds with U.S. Appl. No. 14/863,432, 4 pages.

Notice of Allowance, dated Jan. 12, 2017, received in Chinese Patent Application No. 201620470063.8, which corresponds with U.S. Appl. No. 14/863,432, 1 page.

Office Action, dated Apr. 4, 2016, received in Danish Patent Application No. 201500582, which corresponds with U.S. Appl. No. 14/863,432, 10 pages.

Office Action, dated Oct. 7, 2016, received in Danish Patent Application No. 201500582, which corresponds with U.S. Appl. No. 14/863,432, 6 pages.

Office Action, dated Jun. 12, 2017, received in Danish Patent Application No. 201500582, which corresponds with U.S. Appl. No. 14/863,432, 5 pages.

Grant, dated Jul. 21, 2017, received in Dutch Patent Application No. 2016801, which corresponds with U.S. Appl. No. 14/871,227, 8 pages.

Office Action, dated Oct. 13, 2016, received in U.S. Appl. No. 14/866,511, 27 pages.

Final Office Action, dated Jan. 27, 2017, received in U.S. Appl. No. 14/866,511, 26 pages.

Notice of Allowance, dated Oct. 4, 2017, received in U.S. Appl. No. 14/866,511, 37 pages.

Office Action, dated Aug. 19, 2016, received in U.S. Appl. No. 14/291,880—to be referenced in 7294 per Robby), 19 pages.

Notice of Allowance, dated Jan. 10, 2017, received in U.S. Appl. No. 14/291,880—to be referenced in 7294 per Robby), 8 pages.

Patent, dated Aug. 8, 2016, received in Australian Patent Application 2016100653, corresponds with U.S. Appl. No. 14/866,511, 1 page.

Office Action, dated Dec. 5, 2018, received in Chinese Patent Application No. 201610342264.4, which corresponds with U.S. Appl. No. 14/866,511, 4 pages.

Office Action, dated Jul. 11, 2019, received in Chinese Patent Application No. 201610342264.4, which corresponds with U.S. Appl. No. 14/866,511, 4 pages.

Office Action, dated Sep. 17, 2019, received in Chinese Patent Application No. 201610342264.4, which corresponds with U.S. Appl. No. 14/866,511, 3 pages.

Notice of Allowance, dated Nov. 28, 2019, received in Chinese Patent Application No. 201610342264.4, which corresponds with U.S. Appl. No. 14/866,511, 3 pages.

Notice of Allowance, dated Jan. 12, 2017, received in Chinese Patent Application No. 201620470281.1, which corresponds with U.S. Appl. No. 14/866,511, 1 page.

(56)

**References Cited**

## OTHER PUBLICATIONS

Office Action, dated Mar. 22, 2016, received in Danish Patent Application No. 201500576, which corresponds with U.S. Appl. No. 14/866,511, 10 pages.

Intention to Grant, dated Jun. 8, 2016, received in Danish Patent Application No. 201500576, which corresponds with U.S. Appl. No. 14/866,511, 2 pages.

Grant, dated Aug. 26, 2016, received in Danish Patent Application No. 201500576, which corresponds with U.S. Appl. No. 14/866,511, 2 pages.

Patent, dated Jan. 23, 2017, received in Danish Patent Application No. 201500576, which corresponds with U.S. Appl. No. 14/866,511, 3 pages.

Office Action, dated Nov. 24, 2017, received in European Patent Application No. 16727900.9, which corresponds with U.S. Appl. No. 14/866,511, 5 pages.

Office Action, dated May 24, 2018, received in European Patent Application No. 16727900.9, which corresponds with U.S. Appl. No. 14/866,511, 7 pages.

Office Action, dated Jan. 2, 2019, received in European Patent Application No. 16727900.9, which corresponds with U.S. Appl. No. 14/866,511, 5 pages.

Intention to Grant, dated Jul. 5, 2019, received in European Patent Application No. 16727900.9, which corresponds with U.S. Appl. No. 14/866,511, 5 pages.

Decision to Grant, dated Dec. 5, 2019, received in European Patent Application No. 16727900.9, which corresponds with U.S. Appl. No. 14/866,511, 2 pages.

Office Action, dated Jun. 9, 2017, received in Japanese Patent Application No. 2016558214, which corresponds with U.S. Appl. No. 14/866,511, 6 pages.

Notice of Allowance, dated Jul. 14, 2017, received in Japanese Patent Application No. 2016558214, which corresponds with U.S. Appl. No. 14/866,511, 5 pages.

Patent, dated Aug. 18, 2017, received in Japanese Patent Application No. 2016558214, which corresponds with U.S. Appl. No. 14/866,511, 3 pages.

Office Action, dated May 10, 2016, received in U.S. Appl. No. 14/866,489, 15 pages.

Final Office Action, dated Sep. 16, 2016, received in U.S. Appl. No. 14/866,489, 24 pages.

Notice of Allowance, dated Apr. 27, 2017, received in U.S. Appl. No. 14/866,489, 27 pages.

Notice of Allowance, dated Jul. 6, 2017, received in U.S. Appl. No. 14/866,489, 12 pages.

Office Action, dated Mar. 28, 2016, received in U.S. Appl. No. 14/869,899, 17 pages.

Office Action, dated Jun. 28, 2016, received in U.S. Appl. No. 14/869,899, 5 pages.

Final Office Action, dated Sep. 2, 2016, received in U.S. Appl. No. 14/869,899, 22 pages.

Notice of Allowance, dated Feb. 28, 2017, received in U.S. Appl. No. 14/869,899, 9 pages.

Innovation Patent, dated Aug. 25, 2016, received in Australian Patent Application No. 2016101438, which corresponds with U.S. Appl. No. 14/869,899, 1 page.

Certificate of Examination, dated Oct. 11, 2016, received in Australian Patent Application No. 2016101438, which corresponds with U.S. Appl. No. 14/869,899, 1 page.

Notice of Acceptance, dated Aug. 23, 2018, received in Australian Patent Application No. 2018204611, which corresponds with U.S. Appl. No. 14/869,899, 3 pages.

Office Action, dated Feb. 3, 2016, received in Danish Patent Application No. 201500592, which corresponds with U.S. Appl. No. 14/869,899, 9 pages.

Office Action, dated Oct. 7, 2016, received in Danish Patent Application No. 201500592, which corresponds with U.S. Appl. No. 14/869,899, 6 pages.

Office Action, dated Jul. 3, 2017, received in Danish Patent Application No. 201500592, which corresponds with U.S. Appl. No. 14/869,899, 5 pages.

Office Action, dated Jan. 29, 2018, received in Danish Patent Application No. 201500592, which corresponds with U.S. Appl. No. 14/869,899, 2 pages.

Notice of Allowance, dated Apr. 24, 2018, received in Danish Patent Application No. 201500592, which corresponds with U.S. Appl. No. 14/869,899, 2 pages.

Patent, dated May 28, 2018, received in Danish Patent Application No. 201500592, which corresponds with U.S. Appl. No. 14/869,899, 2 pages.

Office Action, dated Nov. 22, 2016, received in Danish Patent Application No. 201670594, which corresponds with U.S. Appl. No. 14/869,899, 9 pages.

Office Action, dated Dec. 14, 2017, received in Danish Patent Application No. 201670594, which corresponds with U.S. Appl. No. 14/869,899, 3 pages.

Office Action, dated May 1, 2018, received in Danish Patent Application No. 201670594, which corresponds with U.S. Appl. No. 14/869,899, 2 pages.

Office Action, dated Oct. 9, 2018, received in Danish Patent Application No. 201670594, which corresponds with U.S. Appl. No. 14/869,899, 2 pages.

Patent, dated Feb. 26, 2019, received in Danish Patent Application No. 201670594, which corresponds with U.S. Appl. No. 14/869,899, 3 pages.

Office Action, dated May 8, 2019, received in European Patent Application No. 18168939.9, which corresponds with U.S. Appl. No. 14/869,899, 10 pages.

Intention to Grant, dated Oct. 25, 2019, received in European Patent Application No. 18168939.9, which corresponds with U.S. Appl. No. 14/869,899, 8 pages.

Office Action, dated May 23, 2019, received in European Patent Application No. 18175195.9, which corresponds with U.S. Appl. No. 14/869,899, 10 pages.

Oral Summons, dated Dec. 6, 2019, received in European Patent Application No. 18175195.9, which corresponds with U.S. Appl. No. 14/869,899, 9 pages.

Office Action, dated Sep. 21, 2018, received in Japanese Patent Application No. 2018-100827, which corresponds with U.S. Appl. No. 14/869,899, 4 pages.

Notice of Allowance, dated Mar. 1, 2019, received in Japanese Patent Application No. 2018-100827, which corresponds with U.S. Appl. No. 14/869,899, 5 pages.

Patent, dated Apr. 5, 2019, received in Japanese Patent Application No. 2018-100827, which corresponds with U.S. Appl. No. 14/869,899, 5 pages.

Office Action, dated Oct. 5, 2018, received in Korean Patent Application No. 2018-7017213, which corresponds with U.S. Appl. No. 14/869,899, 3 pages.

Office Action, dated Mar. 22, 2019, received in Korean Patent Application No. 2018-7017213, which corresponds with U.S. Appl. No. 14/869,899, 6 pages.

Patent, dated May 10, 2019, received in Korean Patent Application No. 2018-7017213, which corresponds with U.S. Appl. No. 14/869,899, 8 pages.

Office Action, dated Mar. 4, 2016, received in U.S. Appl. No. 14/866,992, 30 pages.

Final Office Action, dated Jul. 29, 2016, received in U.S. Appl. No. 14/866,992, 35 pages.

Office Action, dated Apr. 13, 2017, received in U.S. Appl. No. 14/866,992, 34 pages.

Final Office Action, dated Oct. 3, 2017, received in U.S. Appl. No. 14/866,992, 37 pages.

Office Action, dated Jan. 29, 2018, received in U.S. Appl. No. 14/866,992, 44 pages.

Final Office Action, dated Aug. 28, 2018, received in U.S. Appl. No. 14/866,992, 52 pages.

Examiner's Answer, dated May 9, 2019, received in U.S. Appl. No. 14/866,992, 26 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Innovation Patent, dated Sep. 22, 2016, received in Australian Patent Application No. 2016101418, which corresponds with U.S. Appl. No. 14/866,992, 1 page.

Office Action, dated Nov. 22, 2016, received in Australian Patent Application No. 2016101418, which corresponds with U.S. Appl. No. 14/866,992, 7 pages.

Office Action, dated Feb. 7, 2017, received in Australian Patent Application No. 2016101418, which corresponds with U.S. Appl. No. 14/866,992, 5 pages.

Office Action, dated Mar. 26, 2018, received in Australian Patent Application No. 2016304890, which corresponds with U.S. Appl. No. 14/866,992, 3 pages.

Notice of Acceptance, dated Mar. 12, 2019, received in Australian Patent Application No. 2016304890, which corresponds with U.S. Appl. No. 14/866,992, 5 pages.

Certificate of Grant, dated Jul. 4, 2019, received in Australian Patent Application No. 2016304890, which corresponds with U.S. Appl. No. 14/866,992, 1 page.

Office Action, dated Jan. 19, 2018, received in Australian Patent Application No. 201761478, which corresponds with U.S. Appl. No. 14/866,992, 6 pages.

Certificate of Grant, dated May 9, 2019, received in Australian Patent Application No. 201761478, which corresponds with U.S. Appl. No. 14/866,992, 3 pages.

Office Action, dated Sep. 12, 2019, received in Chinese Patent Application No. 201610658351.8, which corresponds with U.S. Appl. No. 14/866,992, 5 pages.

Office Action, dated Mar. 18, 2016, received in Danish Patent Application No. 201500593, which corresponds with U.S. Appl. No. 14/866,992, 10 pages.

Office Action, dated Jun. 27, 2016, received in Danish Patent Application No. 201500593, which corresponds with U.S. Appl. No. 14/866,992, 7 pages.

Office Action, dated Feb. 6, 2017, received in Danish Patent Application No. 201500593, which corresponds with U.S. Appl. No. 14/866,992, 4 pages.

Office Action, dated Sep. 5, 2017, received in Danish Patent Application No. 201500593, which corresponds with U.S. Appl. No. 14/866,992, 6 pages.

Office Action, dated Oct. 12, 2018, received in European Patent Application No. 16758008.3, which corresponds with U.S. Appl. No. 14/866,992, 11 pages.

Summons, dated May 8, 2019, received in European Patent Application No. 16758008.3, which corresponds with U.S. Appl. No. 14/866,992, 14 pages.

Office Action, dated Jan. 11, 2019, received in Japanese Patent Application No. 2018-506425, which corresponds with U.S. Appl. No. 14/866,992, 6 pages.

Notice of Allowance, dated Jun. 18, 2019, received in Japanese Patent Application No. 2018-506425, which corresponds with U.S. Appl. No. 14/866,992, 5 pages.

Patent, dated Jul. 26, 2019, received in Japanese Patent Application No. 2018-506425, which corresponds with U.S. Appl. No. 14/866,992, 3 pages.

Notice of Allowance, dated Sep. 10, 2019, received in Korean Patent Application No. 2018-7003890, which corresponds with U.S. Appl. No. 14/866,992, 5 pages.

Patent, dated Oct. 11, 2019, received in Korean Patent Application No. 2018-7003890, which corresponds with U.S. Appl. No. 14/866,992, 5 pages.

Office Action, dated Feb. 12, 2018, received in U.S. Appl. No. 15/009,661, 36 pages.

Final Office Action, dated Sep. 19, 2018, received in U.S. Appl. No. 15/009,661, 28 pages.

Office Action, dated Jun. 28, 2019, received in U.S. Appl. No. 15/009,661, 33 pages.

Office Action, dated Jan. 18, 2018, received in U.S. Appl. No. 15/009,676, 21 pages.

Notice of Allowance, dated Aug. 3, 2018, received in U.S. Appl. No. 15/009,676, 6 pages.

Notice of Allowance, dated Nov. 15, 2018, received in U.S. Appl. No. 15/009,676, 6 pages.

Office Action, dated Mar. 13, 2018, received in U.S. Appl. No. 15/009,688, 10 pages.

Notice of Allowance, dated Nov. 6, 2018, received in U.S. Appl. No. 15/009,688, 10 pages.

Office Action, dated Nov. 30, 2015, received in U.S. Appl. No. 14/845,217, 24 pages.

Final Office Action, dated Apr. 22, 2016, received in U.S. Appl. No. 14/845,217, 36 pages.

Notice of Allowance, dated Aug. 26, 2016, received in U.S. Appl. No. 14/845,217, 5 pages.

Notice of Allowance, dated Jan. 4, 2017, received in U.S. Appl. No. 14/845,217, 5 pages.

Office Action, dated Feb. 3, 2016, received in U.S. Appl. No. 14/856,517, 36 pages.

Final Office Action, dated Jul. 13, 2016, received in U.S. Appl. No. 14/856,517, 30 pages.

Office Action, dated May 2, 2017, received in U.S. Appl. No. 14/856,517, 34 pages.

Final Office Action, dated Oct. 4, 2017, received in U.S. Appl. No. 14/856,517, 33 pages.

Notice of Allowance, dated Jun. 29, 2018, received in U.S. Appl. No. 14/856,517, 11 pages.

Office Action, dated Feb. 11, 2016, received in U.S. Appl. No. 14/856,519, 34 pages.

Final Office Action, dated Jul. 15, 2016, received in U.S. Appl. No. 14/856,519, 31 pages.

Office Action, dated May 18, 2017, received in U.S. Appl. No. 14/856,519, 35 pages.

Final Office Action, dated Nov. 15, 2017, received in U.S. Appl. No. 14/856,519, 31 pages.

Notice of Allowance, dated Jan. 31, 2018, received in U.S. Appl. No. 14/856,519, 9 pages.

Notice of Allowance, dated May 2, 2018, received in U.S. Appl. No. 14/856,519, 10 pages.

Office Action, dated Jun. 9, 2017, received in U.S. Appl. No. 14/856,520, 36 pages.

Final Office Action, dated Nov. 16, 2017, received in U.S. Appl. No. 14/856,520, 41 pages.

Office Action, dated Nov. 20, 2018, received in U.S. Appl. No. 14/856,520, 36 pages.

Final Office Action, dated Apr. 17, 2019, received in U.S. Appl. No. 14/856,520, 38 pages.

Office Action, dated Jun. 30, 2017, received in U.S. Appl. No. 14/856,522, 22 pages.

Notice of Allowance, dated Feb. 9, 2018, received in U.S. Appl. No. 14/856,522, 9 pages.

Office Action, dated Feb. 1, 2016, received in U.S. Appl. No. 14/857,645, 15 pages.

Final Office Action, dated Jun. 16, 2016, received in U.S. Appl. No. 14/857,645, 12 pages.

Notice of Allowance, dated Oct. 24, 2016, received in U.S. Appl. No. 14/857,645, 6 pages.

Notice of Allowance, dated Jun. 16, 2017, received in U.S. Appl. No. 14/857,645, 5 pages.

Office Action, dated Nov. 30, 2017, received in U.S. Appl. No. 14/857,636, 19 pages.

Notice of Allowance, dated Aug. 16, 2018, received in U.S. Appl. No. 14/857,636, 5 pages.

Office Action, dated Jan. 17, 2018, received in Australian Patent Application No. 2017202816, which corresponds with U.S. Appl. No. 14/857,636, 3 pages.

Notice of Allowance, dated Jan. 15, 2019, received in Australian Patent Application No. 2017202816, which corresponds with U.S. Appl. No. 14/857,636, 3 pages.

Certificate of Grant, dated May 16, 2019, received in Australian Patent Application No. 2017202816, which corresponds with U.S. Appl. No. 14/857,636, 4 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Office Action, dated Sep. 22, 2017, received in Japanese Patent Application No. 2017-029201, which corresponds with U.S. Appl. No. 14/857,636, 8 pages.

Office Action, dated Jun. 25, 2018, received in Japanese Patent Application No. 2017-029201, which corresponds with U.S. Appl. No. 14/857,636, 4 pages.

Office Action, dated Nov. 28, 2018, received in Korean Patent Application No. 20177036645, which corresponds with U.S. Appl. No. 14/857,636, 6 pages.

Notice of Allowance, dated May 10, 2019, received in Korean Patent Application No. 20177036645, which corresponds with U.S. Appl. No. 14/857,636, 4 pages.

Patent, dated Jul. 11, 2019, received in Korean Patent Application No. 20177036645, which corresponds with U.S. Appl. No. 14/857,636, 8 pages.

Office Action, dated Dec. 1, 2017, received in U.S. Appl. No. 14/857,663, 15 pages.

Notice of Allowance, dated Aug. 16, 2018, received in U.S. Appl. No. 14/857,663, 5 pages.

Office Action, dated Nov. 11, 2019, received in Japanese Patent Application No. 2018-201076, which corresponds with U.S. Appl. No. 14/857,663, 7 pages.

Office Action, dated Mar. 31, 2017, received in U.S. Appl. No. 14/857,700, 14 pages.

Final Office Action, dated Oct. 11, 2017, received in U.S. Appl. No. 14/857,700, 13 pages.

Notice of Allowance, dated Feb. 12, 2018, received in U.S. Appl. No. 14/857,700, 13 pages.

Notice of Allowance, dated Apr. 9, 2018, received in U.S. Appl. No. 14/857,700, 7 pages.

Notice of Allowance, dated Apr. 19, 2018, received in U.S. Appl. No. 14/864,529, 11 pages.

Notice of Allowance, dated Oct. 9, 2018, received in U.S. Appl. No. 14/864,529, 11 pages.

Grant of Patent, dated Apr. 16, 2018, received in Dutch Patent Application No. 2019215, 2 pages.

Office Action, dated Jan. 25, 2016, received in U.S. Appl. No. 14/864,580, 29 pages.

Notice of Allowance, dated May 23, 2016, received in U.S. Appl. No. 14/864,580, 9 pages.

Notice of Allowance, dated Aug. 4, 2016, received in U.S. Appl. No. 14/864,580, 9 pages.

Notice of Allowance, dated Dec. 28, 2016, received in U.S. Appl. No. 14/864,580, 8 pages.

Office Action, dated Aug. 19, 2016, received in Australian Patent Application No. 2016100648, which corresponds with U.S. Appl. No. 14/864,580, 6 pages.

Office Action, dated Jul. 1, 2019, received in Australian Patent Application No. 2019200872, which corresponds with U.S. Appl. No. 14/864,580, 6 pages.

Notice of Acceptance, dated Sep. 19, 2019, received in Australian Patent Application No. 2019200872, which corresponds with U.S. Appl. No. 14/864,580, 3 pages.

Notice of Allowance, dated Jun. 14, 2019, received in Chinese Patent Application No. 201610342151.4, which corresponds with U.S. Appl. No. 14/864,580, 3 pages.

Patent, dated Jul. 30, 2019, received in Chinese Patent Application No. 201610342151.4, which corresponds with U.S. Appl. No. 14/864,580, 6 pages.

Notice of Allowance, dated Nov. 8, 2016, received in Chinese Patent Application No. 201620470247.4, which corresponds with U.S. Appl. No. 14/864,580, 3 pages.

Certificate of Registration, dated Oct. 14, 2016, received in German Patent Application No. 20201600003234.9, which corresponds with U.S. Appl. No. 14/864,580, 3 pages.

Office Action, dated Apr. 8, 2016, received in Danish Patent Application No. 201500584, which corresponds with U.S. Appl. No. 14/864,580, 9 pages.

Office Action, dated Oct. 7, 2016, received in Danish Patent Application No. 201500584, which corresponds with U.S. Appl. No. 14/864,580, 3 pages.

Office Action, dated May 5, 2017, received in Danish Patent Application No. 201500584, which corresponds with U.S. Appl. No. 14/864,580, 3 pages.

Office Action, dated Dec. 15, 2017, received in Danish Patent Application No. 201500584, which corresponds with U.S. Appl. No. 14/864,580, 4 pages.

Notice of Allowance, dated Aug. 14, 2019, received in Korean Patent Application No. 2019-7018317, which corresponds with U.S. Appl. No. 14/864,580, 6 pages.

Patent, dated Nov. 12, 2019, received in Korean Patent Application No. 2019-7018317, which corresponds with U.S. Appl. No. 14/864,580, 6 pages.

Notice of Allowance, dated Nov. 23, 2016, received in U.S. Appl. No. 14/864,601, 12 pages.

Notice of Allowance, dated Apr. 20, 2017, received in U.S. Appl. No. 14/864,601, 13 pages.

Office Action, dated Aug. 31, 2018, received in Australian Patent Application No. 2016276030, which corresponds with U.S. Appl. No. 14/864,601, 3 pages.

Certificate of Grant, dated Feb. 21, 2019, received in Australian Patent Application No. 2016276030, which corresponds with U.S. Appl. No. 14/864,601, 4 pages.

Office Action, dated Feb. 4, 2019, received in European Patent Application No. 16730554.9, which corresponds with U.S. Appl. No. 14/864,601, 10 pages.

Intention to Grant, dated Jul. 18, 2019, received in European Patent Application No. 16730554.9, which corresponds with U.S. Appl. No. 14/864,601, 5 pages.

Decision to Grant, dated Sep. 12, 2019, received in European Patent Application No. 16730554.9, which corresponds with U.S. Appl. No. 14/864,601, 2 pages.

Patent, dated Oct. 9, 2019, received in European Patent Application No. 16730554.9, which corresponds with U.S. Appl. No. 14/864,601, 3 pages.

Notice of Allowance, dated Dec. 10, 2018, received in Japanese Patent Application No. 2017-561375, which corresponds with U.S. Appl. No. 14/864,601, 5 pages.

Patent, dated Jan. 11, 2019, received in Japanese Patent Application No. 2017-561375, which corresponds with U.S. Appl. No. 14/864,601, 3 pages.

Office Action, dated Jan. 25, 2019, received in Korean Patent Application No. 2017-7033756, which corresponds with U.S. Appl. No. 14/864,601, 8 pages.

Notice of Allowance, dated May 29, 2019, received in Korean Patent Application No. 2017-7033756, which corresponds with U.S. Appl. No. 14/864,601, 6 pages.

Patent, dated Jun. 25, 2019, received in Korean Patent Application No. 2017-7033756, which corresponds with U.S. Appl. No. 14/864,601, 6 pages.

Office Action, dated Apr. 19, 2016, received in U.S. Appl. No. 14/864,627, 9 pages.

Notice of Allowance, dated Jan. 31, 2017, received in U.S. Appl. No. 14/864,627, 7 pages.

Office Action, dated Apr. 8, 2016, received in Danish Patent Application No. 201500585, which corresponds with U.S. Appl. No. 14/864,627, 9 pages.

Office Action, dated Oct. 7, 2016, received in Danish Patent Application No. 201500585, which corresponds with U.S. Appl. No. 14/864,627, 3 pages.

Office Action, dated May 5, 2017, received in Danish Patent Application No. 201500585, which corresponds with U.S. Appl. No. 14/864,627, 4 pages.

Office Action, dated Dec. 15, 2017, received in Danish Patent Application No. 201500585, which corresponds with U.S. Appl. No. 14/864,627, 5 pages.

Office Action, dated Mar. 29, 2016, received in U.S. Appl. No. 14/866,361, 22 pages.

Notice of Allowance, dated Jul. 19, 2016, received in U.S. Appl. No. 14/866,361, 8 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Office Action, dated Jun. 10, 2016, received in Australian Patent Application No. 2016100292, which corresponds with U.S. Appl. No. 14/866,361, 4 pages.

Certificate of Examination, dated Dec. 8, 2016, received in Australian Patent Application No. 2016100292, which corresponds with U.S. Appl. No. 14/866,361, 1 page.

Office Action, dated Oct. 19, 2018, received in Chinese Patent Application No. 201610189298.4, which corresponds with U.S. Appl. No. 14/866,361, 6 pages.

Notice of Allowance, dated May 23, 2019, received in Chinese Patent Application No. 201610189298.4, which corresponds with U.S. Appl. No. 14/866,361, 3 pages.

Patent, dated Jul. 23, 2019, received in Chinese Patent Application No. 201610189298.4, which corresponds with U.S. Appl. No. 14/866,361, 7 pages.

Notice of Allowance/Grant, dated Jul. 1, 2016, received in Chinese Patent Application No. 201620251706.X, which corresponds with U.S. Appl. No. 14/866,361, 3 pages.

Letters Patent, dated Aug. 3, 2016, received in Chinese Patent Application No. 201620251706.X, which corresponds with U.S. Appl. No. 14/866,361, 3 pages.

Certificate of Registration, dated Jun. 24, 2016, received in German Patent Application No. 202016001819.2, which corresponds with U.S. Appl. No. 14/866,361, 3 pages.

Office Action, dated Apr. 7, 2016, received in Danish Patent Application No. 201500579, which corresponds with U.S. Appl. No. 14/866,361, 10 pages.

Office Action, dated Oct. 28, 2016, received in Danish Patent Application No. 201500579, which corresponds with U.S. Appl. No. 14/866,361, 3 pages.

Office Action, dated Jun. 15, 2017, received in Danish Patent Application No. 201500579, which corresponds with U.S. Appl. No. 14/866,361, 2 pages.

Office Action, dated Jan. 4, 2018, received in Danish Patent Application No. 201500579, which corresponds with U.S. Appl. No. 14/866,361, 2 pages.

Notice of Allowance, dated Mar. 16, 2018, received in Danish Patent Application No. 201500579, which corresponds with U.S. Appl. No. 14/866,361, 2 pages.

Patent, dated May 22, 2018, received in Danish Patent Application No. 201500579, which corresponds with U.S. Appl. No. 14/866,361, 2 pages.

Office Action, dated Jun. 11, 2018, received in European Patent Application No. 17188507.2, which corresponds with U.S. Appl. No. 14/866,361, 10 pages.

Office Action, dated Jan. 30, 2019, received in European Patent Application No. 17188507.2, which corresponds with U.S. Appl. No. 14/866,361, 13 pages.

Office Action, dated Oct. 8, 2019, received in European Patent Application No. 17188507.2, which corresponds with U.S. Appl. No. 14/866,361, 6 pages.

Office Action, dated Oct. 12, 2018, received in Japanese Patent Application No. 2017-141962, which corresponds with U.S. Appl. No. 14/866,361, 6 pages.

Office Action, dated Jun. 10, 2019, received in Japanese Patent Application No. 2017-141962, which corresponds with U.S. Appl. No. 14/866,361, 6 pages.

Notice of Allowance, dated Oct. 7, 2019, received in Japanese Patent Application No. 2017-141962, which corresponds with U.S. Appl. No. 14/866,361, 5 pages.

Patent, dated Nov. 8, 2019, received in Japanese Patent Application No. 2017-141962, which corresponds with U.S. Appl. No. 14/866,361, 4 pages.

Office Action, dated Sep. 14, 2018, received in Korean Patent Application No. 2018-7013039, which corresponds with U.S. Appl. No. 14/866,361, 2 pages.

Notice of Allowance, dated Jan. 30, 2019, received in Korean Patent Application No. 2018-7013039, which corresponds with U.S. Appl. No. 14/866,361, 5 pages.

Patent, dated Apr. 3, 2019, received in Korean Patent Application No. 2018-7013039, which corresponds with U.S. Appl. No. 14/866,361, 4 pages.

Office Action, dated Jan. 22, 2018, received in U.S. Appl. No. 14/866,987, 22 pages.

Final Office Action, dated Oct. 11, 2018, received in U.S. Appl. No. 14/866,987, 20 pages.

Notice of Allowance, dated Apr. 4, 2019, received in U.S. Appl. No. 14/866,987, 5 pages.

Patent, dated Aug. 8, 2016, received in Australian Patent Application No. 2016100649, which corresponds with U.S. Appl. No. 14/866,987, 1 page.

Office Action, dated Dec. 4, 2018, received in Chinese Patent Application No. 201610342336.5, which corresponds with U.S. Appl. No. 14/866,987, 5 pages.

Rejection Decision, dated Apr. 28, 2019, received in Chinese Patent Application No. 201610342336.5, which corresponds with U.S. Appl. No. 14/866,987, 4 pages.

Office Action, dated Aug. 15, 2019, received in Chinese Patent Application No. 201610342336.5, which corresponds with U.S. Appl. No. 14/866,987, 3 pages.

Notice of Allowance, dated Dec. 3, 2019, received in Chinese Patent Application No. 201610342336.5, which corresponds with U.S. Appl. No. 14/866,987, 3 pages.

Office Action, dated Oct. 19, 2016, received in Chinese Patent Application No. 2016201470246.X, which corresponds with U.S. Appl. No. 14/866,987, 4 pages.

Patent, dated May 3, 2017, received in Chinese Patent Application No. 2016201470246.X, which corresponds with U.S. Appl. No. 14/866,987, 2 pages.

Patent, dated Sep. 19, 2016, received in German Patent Application No. 202016002908.9, which corresponds with U.S. Appl. No. 14/866,987, 3 pages.

Office Action, dated Mar. 22, 2016, received in Danish Patent Application No. 201500587, which corresponds with U.S. Appl. No. 14/866,987, 8 pages.

Intention to Grant, dated Jun. 10, 2016, received in Danish Patent Application No. 201500587, which corresponds with U.S. Appl. No. 14/866,987, 2 pages.

Notice of Allowance, dated Nov. 1, 2016, received in Danish Patent Application No. 201500587, which corresponds with U.S. Appl. No. 14/866,987, 2 pages.

Office Action, dated Sep. 9, 2016, received in Danish Patent Application No. 201670463, which corresponds with U.S. Appl. No. 14/866,987, 7 pages.

Notice of Allowance, dated Jan. 31, 2017, received in Danish Patent Application No. 201670463, which corresponds with U.S. Appl. No. 14/866,987, 3 pages.

Office Action, dated Apr. 19, 2017, received in Danish Patent Application No. 201670463, which corresponds with U.S. Appl. No. 14/866,987, 3 pages.

Notice of Allowance, dated Sep. 29, 2017, received in Danish Patent Application No. 201670463, which corresponds with U.S. Appl. No. 14/866,987, 2 pages.

Patent, dated Nov. 6, 2017, received in Danish Patent Application No. 201670463, which corresponds with U.S. Appl. No. 14/866,987, 6 pages.

Office Action, dated May 7, 2018, received in European Patent Application No. 16189421.7, which corresponds with U.S. Appl. No. 14/866,987, 5 pages.

Office Action, dated Dec. 11, 2018, received in European Patent Application No. 16189421.7, which corresponds with U.S. Appl. No. 14/866,987, 6 pages.

Intention to Grant, dated Jun. 14, 2019, received in European Patent Application No. 16189421.7, which corresponds with U.S. Appl. No. 14/866,987, 7 pages.

Intention to Grant, dated Oct. 25, 2019, received in European Patent Application No. 16189421.7, which corresponds with U.S. Appl. No. 14/866,987, 7 pages.

Decision to Grant, dated Nov. 14, 2019, received in European Patent Application No. 16189421.7, which corresponds with U.S. Appl. No. 14/866,987, 2 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Notice of Allowance, dated Sep. 22, 2017, received in Japanese Patent Application No. 2016-233449, which corresponds with U.S. Appl. No. 14/866,987, 5 pages.

Patent, dated Oct. 27, 2017, received in Japanese Patent Application No. 2016-233449, which corresponds with U.S. Appl. No. 14/866,987, 3 pages.

Office Action, dated Jul. 31, 2017, received in Japanese Patent Application No. 2017126445, which corresponds with U.S. Appl. No. 14/866,987, 6 pages.

Notice of Allowance, dated Mar. 6, 2018, received in Japanese Patent Application No. 2017-126445, which corresponds with U.S. Appl. No. 14/866,987, 5 pages.

Patent, dated Apr. 6, 2018, received in Japanese Patent Application No. 2017-126445, which corresponds with U.S. Appl. No. 14/866,987, 3 pages.

Office Action, dated Nov. 29, 2017, received in U.S. Appl. No. 14/866,989, 31 pages.

Final Office Action, dated Jul. 3, 2018, received in U.S. Appl. No. 14/866,989, 17 pages.

Notice of Allowance, dated Jan. 17, 2019, received in U.S. Appl. No. 14/866,989, 8 pages.

Certificate of Exam, dated Jul. 21, 2016, received in Australian Patent Application No. 2016100652, which corresponds with U.S. Appl. No. 14/866,989, 1 page.

Office Action, dated Feb. 26, 2018, received in Australian Patent Application No. 2017201079, which corresponds with U.S. Appl. No. 14/866,989, 6 pages.

Notice of Acceptance, dated Feb. 14, 2019, received in Australian Patent Application No. 2017201079, which corresponds with U.S. Appl. No. 14/866,989, 3 pages.

Certificate of Grant, dated Jun. 13, 2019, received in Australian Patent Application No. 2017201079, which corresponds with U.S. Appl. No. 14/866,989, 1 page.

Office Action, dated Sep. 19, 2018, received in Chinese Patent Application No. 201610342314.9, which corresponds with U.S. Appl. No. 14/866,989, 6 pages.

Office Action, dated Feb. 25, 2019, received in Chinese Patent Application No. 201610342314.9, which corresponds with U.S. Appl. No. 14/866,989, 3 pages.

Rejection Decision, dated Apr. 24, 2019, received in Chinese Patent Application No. 201610342314.9, which corresponds with U.S. Appl. No. 14/866,989, 3 pages.

Office Action, dated Jun. 16, 2017, received in Japanese Patent Application No. 2016-233450, which corresponds with U.S. Appl. No. 14/866,989, 6 pages.

Patent, dated Mar. 9, 2018, received in Japanese Patent Application No. 2016-233450, which corresponds with U.S. Appl. No. 14/866,989, 4 pages.

Office Action, dated Apr. 1, 2016, received in Danish Patent Application No. 201500589, which corresponds with U.S. Appl. No. 14/866,989, 8 pages.

Intention to Grant, dated Jun. 10, 2016, received in Danish Patent Application No. 201500589, which corresponds with U.S. Appl. No. 14/866,989, 2 pages.

Notice of Allowance, dated Nov. 1, 2016, received in Danish Patent Application No. 201500589, which corresponds with U.S. Appl. No. 14/866,989, 2 pages.

Notice of Allowance, dated Feb. 5, 2018, received in Japanese Patent Application No. 2016-233450, which corresponds with U.S. Appl. No. 14/866,989, 5 pages.

Office Action, dated Apr. 11, 2016, received in U.S. Appl. No. 14/871,236, 23 pages.

Office Action, dated Jun. 28, 2016, received in U.S. Appl. No. 14/871,236, 21 pages.

Final Office Action, dated Nov. 4, 2016, received in U.S. Appl. No. 14/871,236, 24 pages.

Notice of Allowance, dated Feb. 28, 2017, received in U.S. Appl. No. 14/871,236, 9 pages.

Innovation Patent, dated Aug. 25, 2016, received in Australian Patent Application No. 2016101433, which corresponds with U.S. Appl. No. 14/871,236, 1 page.

Office Action, dated Oct. 14, 2016, received in Australian Patent Application No. 2016101433, which corresponds with U.S. Appl. No. 14/871,236, 3 pages.

Office Action, dated Sep. 30, 2019, received in Chinese Patent Application No. 201610871466.8, which corresponds with U.S. Appl. No. 14/871,236, 4 pages.

Office Action, dated Apr. 8, 2016, received in Danish Patent Application No. 201500595, which corresponds with U.S. Appl. No. 14/871,236, 12 pages.

Office Action, dated May 26, 2016, received in Danish Patent Application No. 201500595, which corresponds with U.S. Appl. No. 14/871,236, 14 pages.

Office Action, dated Sep. 30, 2016, received in Danish Patent Application No. 201500595, which corresponds with U.S. Appl. No. 14/871,236, 10 pages.

Office Action, dated Jun. 15, 2017, received in Danish Patent Application No. 201500595, which corresponds with U.S. Appl. No. 14/871,236, 4 pages.

Office Action, dated Jan. 29, 2018, received in Danish Patent Application No. 201500595, which corresponds with U.S. Appl. No. 14/871,236, 2 pages.

Notice of Allowance, dated Apr. 26, 2018, received in Danish Patent Application No. 201500595, which corresponds with U.S. Appl. No. 14/871,236, 2 pages.

Patent, dated Jun. 18, 2018, received in Danish Patent Application No. 201500595, which corresponds with U.S. Appl. No. 14/871,236, 3 pages.

Intention to Grant, dated Dec. 4, 2019, received in European Patent Application No. 18168941.5, which corresponds with U.S. Appl. No. 14/871,236, 8 pages.

Office Action, dated Jul. 19, 2018, received in Russian Patent Application No. 2017131408, which corresponds with U.S. Appl. No. 14/871,236, 8 pages.

Patent, dated Feb. 15, 2019, received in Russian Patent Application No. 2017131408, which corresponds with U.S. Appl. No. 14/871,236, 2 pages.

Office Action, dated Sep. 1, 2017, received in U.S. Appl. No. 14/870,754, 22 pages.

Final Office Action, dated Mar. 9, 2018, received in U.S. Appl. No. 14/870,754, 19 pages.

Notice of Allowance, dated Jul. 2, 2018, received in U.S. Appl. No. 14/870,754, 9 pages.

Notice of Allowance, dated Dec. 3, 2018, received in U.S. Appl. No. 14/870,754, 8 pages.

Office Action, dated Nov. 14, 2017, received in U.S. Appl. No. 14/870,882, 25 pages.

Final Office Action, dated Apr. 20, 2018, received in U.S. Appl. No. 14/870,882, 7 pages.

Notice of Allowance, dated Jul. 12, 2018, received in U.S. Appl. No. 14/870,882, 5 pages.

Notice of Allowance, dated Dec. 5, 2018, received in U.S. Appl. No. 14/870,882, 8 pages.

Innovation Patent, dated Aug. 25, 2016, received in Australian Patent Application No. 2016101436, which corresponds with U.S. Appl. No. 14/871,236, 1 page.

Office Action, dated Oct. 31, 2016, received in Australian Patent Application No. 2016101438, which corresponds with U.S. Appl. No. 14/871,236, 6 pages.

Office Action, dated Nov. 28, 2019, received in Chinese Patent Application No. 201610870912.3, which corresponds with U.S. Appl. No. 14/870,882, 10 pages.

Office Action, dated Apr. 6, 2016, received in Danish Patent Application No. 201500596, which corresponds with U.S. Appl. No. 14/870,882, 7 pages.

Office Action, dated Jun. 9, 2016, received in Danish Patent Application No. 201500596, which corresponds with U.S. Appl. No. 14/870,882, 9 pages.

Notice of Allowance, dated Oct. 31, 2017, received in Danish Patent Application No. 201500596, which corresponds with U.S. Appl. No. 14/870,882, 2 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Patent, dated Jan. 29, 2018, received in Danish Patent Application No. 201500596, which corresponds with U.S. Appl. No. 14/870,882, 4 pages.

Office Action, dated Feb. 11, 2019, received in European Patent Application No. 17171972.7, which corresponds with U.S. Appl. No. 14/870,882, 7 pages.

Office Action, dated Sep. 1, 2017, received in U.S. Appl. No. 14/870,988, 14 pages.

Final Office Action, dated Feb. 16, 2018, received in U.S. Appl. No. 14/870,988, 18 pages.

Notice of Allowance, dated Aug. 27, 2018, received in U.S. Appl. No. 14/870,988, 11 pages.

Office Action, dated Nov. 22, 2017, received in U.S. Appl. No. 14/871,227, 24 pages.

Notice of Allowance, dated Jun. 11, 2018, received in U.S. Appl. No. 14/871,227, 11 pages.

Office Action, dated Oct. 17, 2016, received in Australian Patent Application No. 2016203040, which corresponds with U.S. Appl. No. 14/871,227, 7 pages.

Office Action, dated Oct. 16, 2017, received in Australian Patent Application No. 2016203040, which corresponds with U.S. Appl. No. 14/871,227, 5 pages.

Notice of Acceptance, dated Oct. 30, 2018, received in Australian Patent Application No. 2016203040, which corresponds with U.S. Appl. No. 14/871,227, 4 pages.

Certificate of Grant, dated Feb. 28, 2019, received in Australian Patent Application No. 2016203040, which corresponds with U.S. Appl. No. 14/871,227, 1 page.

Office Action, dated Oct. 18, 2016, received in Australian Patent Application No. 2016101431, which corresponds with U.S. Appl. No. 14/871,227, 3 pages.

Office Action, dated Apr. 13, 2017, received in Australian Patent Application No. 2016101431, which corresponds with U.S. Appl. No. 14/871,227, 4 pages.

Office Action, dated Oct. 11, 2018, received in Australian Patent Application No. 2017245442, which corresponds with U.S. Appl. No. 14/871,227, 4 pages.

Office Action, dated Nov. 16, 2018, received in Chinese Patent Application No. 201680000466.9, which corresponds with U.S. Appl. No. 14/871,227, 5 pages.

Notice of Allowance, dated Jun. 5, 2019, received in Chinese Patent Application No. 201680000466.9, which corresponds with U.S. Appl. No. 14/871,227, 5 pages.

Patent, dated Aug. 9, 2019, received in Chinese Patent Application No. 201680000466.9, which corresponds with U.S. Appl. No. 14/871,227, 8 pages.

Intention to Grant, dated Apr. 7, 2016, received in Danish Patent Application No. 201500597, which corresponds with U.S. Appl. No. 14/871,227, 7 pages.

Grant, dated Jun. 21, 2016, received in Danish Patent Application No. 201500597, which corresponds with U.S. Appl. No. 14/871,227, 2 pages.

Patent, dated Sep. 26, 2016, received in Danish Patent Application No. 201500597, which corresponds with U.S. Appl. No. 14/871,227, 7 pages.

Intent to Grant, dated Sep. 17, 2018, received in European Patent No. 16711743.1, which corresponds with U.S. Appl. No. 14/871,227, 5 pages.

Patent, dated Nov. 28, 2018, received in European Patent No. 16711743.1, which corresponds with U.S. Appl. No. 14/871,227, 1 page.

Office Action, dated Mar. 24, 2017, received in Japanese Patent Application No. 2016-533201, which corresponds with U.S. Appl. No. 14/871,227, 6 pages.

Office Action, dated Aug. 4, 2017, received in Japanese Patent Application No. 2016-533201, which corresponds with U.S. Appl. No. 14/871,227, 6 pages.

Notice of Allowance, dated Jan. 4, 2018, received in Japanese Patent Application. No. 2016-533201, which corresponds with U.S. Appl. No. 14/871,227, 4 pages.

Patent, dated Feb. 9, 2018, received in Japanese Patent Application No. 2016-533201, which corresponds with U.S. Appl. No. 14/871,227, 4 pages.

Office Action, dated Feb. 20, 2018, received in Korean Patent Application No. 2016-7019816, which corresponds with U.S. Appl. No. 14/871,227, 8 pages.

Notice of Allowance, dated Oct. 1, 2018, received in Korean Patent Application. No. 2016-7019816, which corresponds with U.S. Appl. No. 14/871,227, 6 pages.

Patent, dated Dec. 28, 2018, received in Korean Patent Application No. 2016-7019816, which corresponds with U.S. Appl. No. 14/871,227, 8 pages.

Office Action, dated Oct. 26, 2017, received in U.S. Appl. No. 14/871,336, 22 pages.

Final Office Action, dated Mar. 15, 2018, received in U.S. Appl. No. 14/871,336, 23 pages.

Office Action, dated Nov. 5, 2018, received in U.S. Appl. No. 14/871,336, 24 pages.

Notice of Allowance, dated Feb. 5, 2019, received in U.S. Appl. No. 14/871,336, 10 pages.

Office Action, dated Oct. 14, 2016, received in Australian Patent Application No. 2016101437, which corresponds with U.S. Appl. No. 14/871,336, 2 pages.

Office Action, dated Apr. 11, 2017, received in Australian Patent Application No. 2016101437, which corresponds with U.S. Appl. No. 14/871,336, 4 pages.

Office Action, dated Nov. 4, 2019, received in Chinese Patent Application No. 201610871323.7, which corresponds with U.S. Appl. No. 14/871,336, 12 pages.

Office Action, dated Apr. 18, 2016, received in Danish Patent Application No. 201500601, which corresponds with U.S. Appl. No. 14/871,336, 8 pages.

Office Action, dated Oct. 18, 2016, received in Danish Patent Application No. 201500601, which corresponds with U.S. Appl. No. 14/871,336, 3 pages.

Notice of Allowance, dated Mar. 23, 2017, received in Danish Patent Application No. 201500601, which corresponds with U.S. Appl. No. 14/871,336, 2 pages.

Patent, dated Oct. 30, 2017, Danish Patent Application No. 201500601, which corresponds with U.S. Appl. No. 14/871,336, 5 pages.

Office Action, dated Feb. 12, 2019, received in European Patent Application No. 17172266.3, which corresponds with U.S. Appl. No. 14/871,336, 6 pages.

Office Action, dated Apr. 2, 2018, received in Japanese Patent Application No. 2018-020324, which corresponds with U.S. Appl. No. 14/871,336, 4 pages.

Notice of Allowance, dated Oct. 12, 2018, received in Japanese Patent Application No. 2018-020324, which corresponds with U.S. Appl. No. 14/871,336, 5 pages.

Patent, dated Nov. 16, 2018, received in Japanese Patent Application No. 2018-020324, which corresponds with U.S. Appl. No. 14/871,336, 4 pages.

Office Action, dated Oct. 16, 2017, received in U.S. Appl. No. 14/871,462, 26 pages.

Innovation Patent, dated Aug. 25, 2016, received in Australian Patent Application No. 2016101435, which corresponds with U.S. Appl. No. 14/871,462, 1 page.

Office Action, dated Oct. 4, 2016, received in Australian Patent Application No. 2016101435, which corresponds with U.S. Appl. No. 14/871,462, 3 pages.

Office Action, dated Oct. 4, 2016, received in Australian Patent Application No. 2016231505, which corresponds with U.S. Appl. No. 14/871,462, 3 pages.

Office Action, dated Sep. 29, 2017, received in Australian Patent Application No. 2016231505, which corresponds with U.S. Appl. No. 14/871,462, 5 pages.

Innovation Patent, dated Oct. 11, 2017, received in Australian Patent Application No. 2016231505, which corresponds with U.S. Appl. No. 14/871,462, 1 page.

(56)

**References Cited**

## OTHER PUBLICATIONS

Office Action, dated Apr. 20, 2017, received in Chinese Patent Application No. 201621044346.2, which corresponds with U.S. Appl. No. 14/871,462, 3 pages.

Intention to Grant, dated Apr. 18, 2016, received in Danish Patent Application No. 201500600, which corresponds with U.S. Appl. No. 14/871,462, 7 pages.

Grant, dated Aug. 30, 2016, received in Danish Patent Application No. 201500600, which corresponds with U.S. Appl. No. 14/871,462, 2 pages.

Office Action, dated Mar. 13, 2017, received in Japanese Patent Application No. 2016-183289, which corresponds with U.S. Appl. No. 14/871,462, 5 pages.

Office Action, dated Nov. 13, 2017, received in Japanese Patent Application No. 2016-183289, which corresponds with U.S. Appl. No. 14/871,462, 5 pages.

Office Action, dated Apr. 29, 2016, received in U.S. Appl. No. 14/867,823, 28 pages.

Final Office Action, dated Sep. 28, 2016, received in U.S. Appl. No. 14/867,823, 31 pages.

Office Action, dated May 11, 2017, received in U.S. Appl. No. 14/867,823, 42 pages.

Final Office Action, dated Nov. 29, 2017, received in U.S. Appl. No. 14/867,823, 47 pages.

Notice of Allowance, dated Apr. 18, 2018, received in U.S. Appl. No. 14/867,823, 10 pages.

Notice of Allowance, dated Aug. 7, 2018, received in U.S. Appl. No. 14/867,823, 8 pages.

Office Action, dated Mar. 18, 2016, received in Danish Patent Application No. 201500594, which corresponds with U.S. Appl. No. 14/867,823, 10 pages.

Office Action, dated Sep. 7, 2016, received in Danish Patent Application No. 201500594, which corresponds with U.S. Appl. No. 14/867,823, 4 pages.

Office Action, dated May 15, 2017, received in Danish Patent Application No. 201500594, which corresponds with U.S. Appl. No. 14/867,823, 4 pages.

Office Action, dated Jan. 23, 2018, received in Danish Patent Application No. 201500594, which corresponds with U.S. Appl. No. 14/867,823, 8 pages.

Office Action, dated May 10, 2016, received in U.S. Appl. No. 14/867,892, 28 pages.

Final Office Action, dated Nov. 2, 2016, received in U.S. Appl. No. 14/867,892, 48 pages.

Office Action, dated Jul. 6, 2017, received in U.S. Appl. No. 14/867,892, 55 pages.

Final Office Action, dated Dec. 14, 2017, received in U.S. Appl. No. 14/867,892, 53 pages.

Office Action, dated Apr. 24, 2018, received in U.S. Appl. No. 14/867,892, 63 pages.

Final Office Action, dated Oct. 17, 2018, received in U.S. Appl. No. 14/867,892, 48 pages.

Examiner's Answer, dated Jul. 18, 2019, received in U.S. Appl. No. 14/867,892, 17 pages.

Office Action, dated Mar. 21, 2016, received in Danish Patent Application No. 201500598, which corresponds with U.S. Appl. No. 14/867,892, 9 pages.

Office Action, dated Sep. 14, 2016, received in Danish Patent Application No. 201500598, which corresponds with U.S. Appl. No. 14/867,892, 4 pages.

Office Action, dated May 4, 2017, received in Danish Patent Application No. 201500598, which corresponds with U.S. Appl. No. 14/867,892, 4 pages.

Office Action, dated Oct. 31, 2017, received in Danish Patent Application No. 201500598, which corresponds with U.S. Appl. No. 14/867,892, 2 pages.

Notice of Allowance, dated Jan. 26, 2018, received in Danish Patent Application No. 201500598, which corresponds with U.S. Appl. No. 14/867,892, 2 pages.

Office Action, dated Feb. 28, 2018, received in U.S. Appl. No. 14/869,361, 26 pages.

Final Office Action, dated Oct. 4, 2018, received in U.S. Appl. No. 14/869,361, 28 pages.

Office Action, dated Feb. 27, 2019, received in U.S. Appl. No. 14/869,361, 28 pages.

Office Action, dated Mar. 1, 2017, received in U.S. Appl. No. 14/869,855, 14 pages.

Final Office Action, dated Oct. 10, 2017, received in U.S. Appl. No. 14/869,855, 16 pages.

Office Action, dated Jan. 23, 2018, received in U.S. Appl. No. 14/869,855, 24 pages.

Notice of Allowance, dated May 31, 2018, received in U.S. Appl. No. 14/869,855, 10 pages.

Office Action, dated Feb. 9, 2017, received in U.S. Appl. No. 14/869,873, 17 pages.

Final Office Action, dated Aug. 18, 2017, received in U.S. Appl. No. 14/869,873, 20 pages.

Office Action, dated Jan. 18, 2018, received in U.S. Appl. No. 14/869,873, 25 pages.

Final Office Action, dated May 23, 2018, received in U.S. Appl. No. 14/869,873, 18 pages.

Notice of Allowance, dated Jul. 30, 2018, received in U.S. Appl. No. 14/869,873, 8 pages.

Office Action, dated Jan. 11, 2018, received in U.S. Appl. No. 14/869,997, 17 pages.

Office Action, dated Sep. 7, 2018, received in U.S. Appl. No. 14/869,997, 23 pages.

Notice of Allowance, dated Apr. 4, 2019, received in U.S. Appl. No. 14/869,997, 9 pages.

Notice of Allowance, dated Jan. 17, 2018, received in U.S. Appl. No. 14/867,990, 12 pages.

Notice of Allowance, dated Mar. 30, 2018, received in U.S. Appl. No. 14/867,990, 5 pages.

Office Action, dated May 23, 2016, received in Australian Patent Application No. 2016100253, which corresponds with U.S. Appl. No. 14/867,990, 5 pages.

Notice of Allowance, dated May 21, 2019, received in Chinese Patent Application No. 201610131507.X, which corresponds with U.S. Appl. No. 14/867,990, 3 pages.

Patent, dated Jul. 19, 2019, received in Chinese Patent Application No. 201610131507.X, which corresponds with U.S. Appl. No. 14/867,990, 6 pages.

Office Action, dated Jul. 5, 2016, received in Chinese Patent Application No. 201620176221.9, which corresponds with U.S. Appl. No. 14/867,990, 4 pages.

Office Action, dated Oct. 25, 2016, received in Chinese Patent Application No. 201620176221.9, which corresponds with U.S. Appl. No. 14/867,990, 7 pages.

Certificate of Registration, dated Jun. 16, 2016, received in German Patent No. 202016001489.8, which corresponds with U.S. Appl. No. 14/867,990, 3 pages.

Office Action, dated Mar. 18, 2016, received in Danish Patent Application No. 201500581, which corresponds with U.S. Appl. No. 14/867,990, 9 pages.

Office Action, dated Sep. 26, 2016, received in Danish Patent Application No. 201500581, which corresponds with U.S. Appl. No. 14/867,990, 5 pages.

Office Action, dated May 3, 2017, received in Danish Patent Application No. 201500581, which corresponds with U.S. Appl. No. 14/867,990, 5 pages.

Office Action, dated Feb. 19, 2018, received in Danish Patent Application No. 201500581, which corresponds with U.S. Appl. No. 14/867,990, 4 pages.

Office Action, dated Apr. 19, 2018, received in U.S. Appl. No. 14/869,703, 19 pages.

Final Office Action, dated Oct. 26, 2018, received in U.S. Appl. No. 14/869,703, 19 pages.

Notice of Allowance, dated Mar. 12, 2019, received in U.S. Appl. No. 14/869,703, 6 pages.

Office Action, dated Dec. 12, 2017, received in U.S. Appl. No. 15/009,668, 32 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Final Office Action, dated Jul. 3, 2018, received in U.S. Appl. No. 15/009,668, 19 pages.

Office Action, dated Jan. 10, 2019, received in U.S. Appl. No. 15/009,668, 17 pages.

Notice of Allowance, dated May 1, 2019, received in U.S. Appl. No. 15/009,668, 12 pages.

Office Action, dated Nov. 25, 2016, received in U.S. Appl. No. 15/081,771, 17 pages.

Final Office Action, dated Jun. 2, 2017, received in U.S. Appl. No. 15/081,771, 17 pages.

Notice of Allowance, dated Dec. 4, 2017, received in U.S. Appl. No. 15/081,771, 10 pages.

Office Action, dated Feb. 1, 2018, received in Australian Patent Application No. 2017202058, which corresponds with U.S. Appl. No. 15/081,771, 4 pages.

Notice of Acceptance, dated Jan. 24, 2019, received in Australian Patent Application No. 2017202058, which corresponds with U.S. Appl. No. 15/081,771, 3 pages.

Certificate of Grant, dated May 23, 2019, received in Australian Patent Application No. 2017202058, which corresponds with U.S. Appl. No. 15/081,771, 1 page.

Office Action, dated Jan. 26, 2018, received in Japanese Patent Application No. 2017-086460, which corresponds with U.S. Appl. No. 15/081,771, 6 pages.

Notice of Allowance, dated Oct. 12, 2018, received in Japanese Patent Application No. 2017-086460, which corresponds with U.S. Appl. No. 15/081,771, 5 pages.

Office Action, dated Aug. 29, 2017, received in Korean Patent Application No. 2017-7014536, which corresponds with U.S. Appl. No. 15/081,771, 5 pages.

Notice of Allowance, dated Jun. 28, 2018, received in Korean Patent Application No. 2017-7014536, which corresponds with U.S. Appl. No. 15/081,771, 4 pages.

Patent, dated Sep. 28, 2018, received in Korean Patent Application No. 2017-7014536, which corresponds with U.S. Appl. No. 15/081,771, 3 pages.

Final Office Action, dated May 1, 2017, received in U.S. Appl. No. 15/136,782, 18 pages.

Notice of Allowance, dated Oct. 20, 2017, received in U.S. Appl. No. 15/136,782, 9 pages.

Office Action, dated May 4, 2018, received in Australian Patent Application No. 2018202855, which corresponds with U.S. Appl. No. 15/136,782, 3 pages.

Notice of Acceptance, dated Sep. 10, 2018, received in Australian Patent Application No. 2018202855, which corresponds with U.S. Appl. No. 15/136,782, 3 pages.

Certificate of Grant, dated Jan. 17, 2019, received in Australian Patent Application No. 2018202855, which corresponds with U.S. Appl. No. 15/136,782, 4 pages.

Office Action, dated Sep. 27, 2019, received in Chinese Patent Application No. 201810119007.3, which corresponds with U.S. Appl. No. 15/136,782, 6 pages.

Office Action, dated May 23, 2017, received in Danish Patent Application No. 201770190, which corresponds with U.S. Appl. No. 15/136,782, 7 pages.

Office Action, dated Jan. 8, 2018, received in Danish Patent Application No. 201770190, which corresponds with U.S. Appl. No. 15/136,782, 2 pages.

Notice of Allowance, dated Mar. 19, 2018, received in Danish Patent Application No. 201770190, which corresponds with U.S. Appl. No. 15/136,782, 2 pages.

Patent, dated May 22, 2018, received in Danish Patent Application No. 201770190, which corresponds with U.S. Appl. No. 15/136,782, 2 pages.

Office Action, dated Apr. 17, 2019, received in European Patent Application No. 18171453.6, which corresponds with U.S. Appl. No. 15/136,782, 4 pages.

Office Action, dated Oct. 2, 2019, received in European Patent Application No. 18171453.6, which corresponds with U.S. Appl. No. 15/136,782, 5 pages.

Office Action, dated Jun. 1, 2018, received in Japanese Patent Application No. 2018-062161, which corresponds with U.S. Appl. No. 15/136,782, 5 pages.

Office Action, dated Nov. 12, 2018, received in Japanese Patent Application No. 2018-062161, which corresponds with U.S. Appl. No. 15/136,782, 5 pages.

Notice of Allowance, dated Feb. 18, 2019, received in Japanese Patent Application No. 2018-062161, which corresponds with U.S. Appl. No. 15/136,782, 5 pages.

Patent, dated Mar. 22, 2019, received in Japanese Patent Application No. 2018-062161, which corresponds with U.S. Appl. No. 15/136,782, 5 pages.

Office Action, dated Oct. 31, 2018, received in Korean Patent Application No. 2018-7020659, which corresponds with U.S. Appl. No. 15/136,782, 5 pages.

Notice of Allowance, dated Feb. 25, 2019, received in Korean Patent Application No. 2018-7020659, which corresponds with U.S. Appl. No. 15/136,782, 5 pages.

Patent, dated Apr. 3, 2019, received in Korean Patent Application No. 2018-7020659, which corresponds with U.S. Appl. No. 15/136,782, 5 pages.

Office Action, dated Jan. 20, 2017, received in U.S. Appl. No. 15/231,745, 21 pages.

Notice of Allowance, dated Jul. 6, 2017, received in U.S. Appl. No. 15/231,745, 18 pages.

Office Action, dated Oct. 17, 2016, received in Danish Patent Application No. 201670587, which corresponds with U.S. Appl. No. 15/231,745, 9 pages.

Office Action, dated Jun. 29, 2017, received in Danish Patent Application No. 201670587, which corresponds with U.S. Appl. No. 15/231,745, 4 pages.

Office Action, dated Feb. 22, 2018, received in Danish Patent Application No. 201670587, which corresponds with U.S. Appl. No. 15/231,745, 4 pages.

Office Action, dated Dec. 18, 2018, received in Danish Patent Application No. 201670587, which corresponds with U.S. Appl. No. 15/231,745, 4 pages.

Office Action, dated Dec. 14, 2016, received in Danish Patent Application No. 201670590, which corresponds with U.S. Appl. No. 15/231,745, 9 pages.

Office Action, dated Jul. 6, 2017, received in Danish Patent Application No. 201670590, which corresponds with U.S. Appl. No. 15/231,745, 3 pages.

Office Action, dated Jan. 10, 2018, received in Danish Patent Application No. 201670590, which corresponds with U.S. Appl. No. 15/231,745, 2 pages.

Patent, dated May 28, 2018, received in Danish Patent Application No. 201670590, which corresponds with U.S. Appl. No. 15/231,745, 2 pages.

Office Action, dated Nov. 10, 2016, received in Danish Patent Application No. 201670591, which corresponds with U.S. Appl. No. 15/231,745, 12 pages.

Office Action, dated Apr. 11, 2018, received in Danish Patent Application No. 201670591, which corresponds with U.S. Appl. No. 15/231,745, 3 pages.

Office Action, dated Nov. 23, 2018, received in Danish Patent Application No. 201670591, which corresponds with U.S. Appl. No. 15/231,745, 7 pages.

Office Action, dated Oct. 26, 2016, received in Danish Patent Application No. 201670592, which corresponds with U.S. Appl. No. 15/231,745, 8 pages.

Office Action, dated Jan. 5, 2017, received in Danish Patent Application No. 201670592, which corresponds with U.S. Appl. No. 15/231,745, 3 pages.

Office Action, dated Jan. 30, 2018, received in Danish Patent Application No. 201670592, which corresponds with U.S. Appl. No. 15/231,745, 2 pages.

Notice of Allowance, dated Mar. 27, 2018, received in Danish Patent Application No. 201670592, which corresponds with U.S. Appl. No. 15/231,745, 2 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Patent, dated May 28, 2018, received in Danish Patent Application No. 201670592, which corresponds with U.S. Appl. No. 15/231,745, 2 pages.

Office Action, dated Oct. 12, 2016, received in Danish Patent Application No. 201670593, which corresponds with U.S. Appl. No. 15/231,745, 7 pages.

Patent, dated Oct. 30, 2017, received in Danish Patent Application No. 201670593, which corresponds with U.S. Appl. No. 15/231,745, 3 pages.

Notice of Allowance, dated Nov. 1, 2019, received in Japanese Patent Application No. 2018-158502, which corresponds with U.S. Appl. No. 15/231,745, 5 pages.

Notice of Allowance, dated Oct. 4, 2018, received in U.S. Appl. No. 15/272,327, 46 pages.

Notice of Acceptance, dated Mar. 2, 2018, received in Australian Patent Application No. 2018200705, which corresponds with U.S. Appl. No. 15/272,327, 3 pages.

Certificate of Grant, dated Jun. 28, 2018, received in Australian Patent Application No. 2018200705, which corresponds with U.S. Appl. No. 15/272,327, 4 pages.

Office Action, dated Mar. 22, 2019, received in Australian Patent Application No. 2018204234, which corresponds with U.S. Appl. No. 15/272,327, 7 pages.

Office Action, dated Sep. 14, 2018, received in European Patent Application No. 15155939.4, which corresponds with U.S. Appl. No. 15/272,327, 5 pages.

Intention to Grant, dated Mar. 19, 2019, received in European Patent Application No. 15155939.4, which corresponds with U.S. Appl. No. 15/272,327, 6 pages.

Decision to Grant, dated Apr. 26, 2019, received in European Patent Application No. 15155939.4, which corresponds with U.S. Appl. No. 15/272,327, 2 pages.

Patent, dated May 22, 2019, received in European Patent Application No. 15155939.4, which corresponds with U.S. Appl. No. 15/272,327, 1 page.

Notice of Allowance, dated Jul. 30, 2018, received in Japanese Patent Application No. 2018-506989, which corresponds with U.S. Appl. No. 15/272,327, 4 pages.

Patent, dated Aug. 31, 2018, received in Japanese Patent Application No. 2018-506989 (7429JP), which corresponds with U.S. Appl. No. 15/272,327, 3 pages.

Office Action, dated Oct. 26, 2018, received in U.S. Appl. No. 15/272,341, 22 pages.

Final Office Action, dated Mar. 25, 2019, received in U.S. Appl. No. 15/272,341, 25 pages.

Office Action, dated Jul. 27, 2017, received in Australian Patent Application No. 2017100535, which corresponds with U.S. Appl. No. 15/272,341, 4 pages.

Notice of Allowance, dated Sep. 20, 2018, received in U.S. Appl. No. 15/272,343, 44 pages.

Office Action, dated Jun. 5, 2019, received in Chinese Patent Application No. 201810071627.4, which corresponds with U.S. Appl. No. 15/272,343, 6 pages.

Office Action, dated Jan. 8, 2019, received in European Patent Application No. 17206374.5, which corresponds with U.S. Appl. No. 15/272,343, 5 pages.

Intention to Grant, dated May 13, 2019, received in European Patent Application No. 17206374.5, which corresponds with U.S. Appl. No. 15/272,343, 7 pages.

Decision to Grant, dated Sep. 12, 2019, received in European Patent Application No. 17206374.5, which corresponds with U.S. Appl. No. 15/272,343, 3 pages.

Patent, Oct. 9, 2019, received in European Patent Application No. 17206374.5, which corresponds with U.S. Appl. No. 15/272,343, 3 pages.

Office Action, dated Oct. 15, 2018, received in U.S. Appl. No. 15/272,345, 31 pages.

Final Office Action, dated Apr. 2, 2019, received in U.S. Appl. No. 15/272,345, 28 pages.

Notice of Acceptance, dated Mar. 2, 2018, received in Australian Patent Application No. 2016304832, which corresponds with U.S. Appl. No. 15/272,345, 3 pages.

Certificate of Grant, dated Jun. 28, 2018, received in Australian Patent Application No. 2016304832, which corresponds with U.S. Appl. No. 15/272,345, 4 pages.

Office Action, dated Oct. 22, 2019, received in Chinese Patent Application No. 201680022696.5, which corresponds with U.S. Appl. No. 15/272,345, 7 pages.

Office Action, dated Apr. 20, 2018, received in European Patent Application No. 16756862.5, which corresponds with U.S. Appl. No. 15/272,345, 15 pages.

Office Action, dated Nov. 13, 2018, received in European Patent Application No. 16756862.5, which corresponds with U.S. Appl. No. 15/272,345, 5 pages.

Decision to Grant, dated Jan. 31, 2019, received in European Patent Application No. 16756862.5, which corresponds with U.S. Appl. No. 15/272,345, 5 pages.

Patent, dated Feb. 27, 2019, received in European Patent Application No. 16756862.5, which corresponds with U.S. Appl. No. 15/272,345, 3 pages.

Office Action, dated Mar. 7, 2018, received in U.S. Appl. No. 15/482,618, 7 pages.

Notice of Allowance, dated Aug. 15, 2018, received in U.S. Appl. No. 15/482,618, 7 pages.

Office Action, dated Apr. 23, 2018, received in U.S. Appl. No. 15/499,691, 29 pages.

Notice of Allowance, dated Oct. 12, 2018, received in U.S. Appl. No. 15/499,693, 8 pages.

Office Action, dated Aug. 2, 2019, received in Korean Patent Application No. 2019-7009439, which corresponds with U.S. Appl. No. 15/499,693, 3 pages.

Office Action, dated Aug. 30, 2017, received in U.S. Appl. No. 15/655,749, 22 pages.

Final Office Action, dated May 10, 2018, received in U.S. Appl. No. 15/655,749, 19 pages.

Office Action, dated Jan. 24, 2019, received in U.S. Appl. No. 15/655,749, 25 pages.

Final Office Action, dated Jul. 1, 2019, received in U.S. Appl. No. 15/655,749, 24 pages.

Notice of Allowance, dated Apr. 18, 2019, received in Korean Patent Application No. 2017-7034248, which corresponds with U.S. Appl. No. 15/655,749, 5 pages.

Patent, dated Jul. 3, 2019, received in Korean Patent Application No. 2017-7034248, which corresponds with U.S. Appl. No. 15/655,749, 5 pages.

Office Action, dated Aug. 1, 2019, received in U.S. Appl. No. 15/785,372, 22 pages.

Office Action, dated Oct. 31, 2017, received in U.S. Appl. No. 15/723,069, 7 pages.

Notice of Allowance, dated Dec. 21, 2017, received in U.S. Appl. No. 15/723,069, 7 pages.

Office Action, dated Apr. 11, 2019, received in U.S. Appl. No. 15/889,115, 9 pages.

Final Office Action, dated Oct. 28, 2019, received in U.S. Appl. No. 15/889,115, 12 pages.

Office Action, dated Jul. 25, 2019, received in U.S. Appl. No. 15/979,347, 14 pages.

Office Action, dated Nov. 25, 2019, received in U.S. Appl. No. 16/049,725, 9 pages.

Office Action, dated May 31, 2019, received in Australian Patent Application No. 2018253539, which corresponds with U.S. Appl. No. 16/049,725, 3 pages.

Notice of Allowance, dated Oct. 10, 2019, received in U.S. Appl. No. 16/102,409, 9 pages.

Office Action, dated Nov. 29, 2019, received in U.S. Appl. No. 16/136,163, 9 pages.

Office Action, dated Dec. 2, 2019, received in Japanese Patent Application No. 2018-202048, which corresponds with U.S. Appl. No. 16/154,591, 6 pages.

Office Action, dated Aug. 20, 2019, received in Korean Patent Application No. 2019-7019946, which corresponds with U.S. Appl. No. 16/154,591, 6 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Office Action, dated Nov. 25, 2019, received in U.S. Appl. No. 16/174,170, 31 pages.

Office Action, dated May 22, 2019, received in U.S. Appl. No. 16/230,743, 7 pages.

Notice of Allowance, dated Sep. 11, 2019, received in U.S. Appl. No. 16/230,743, 5 pages.

Office Action, dated Jul. 5, 2019, received in Korean Patent Application No. 2018-7037896, which corresponds with U.S. Appl. No. 16/243,834, 2 pages.

Notice of Allowance, dated Apr. 19, 2019, received in U.S. Appl. No. 16/252,478, 11 pages.

Office Action, dated Jul. 15, 2019, received in U.S. Appl. No. 16/258,394, 8 pages.

Notice of Allowance, dated Nov. 6, 2019, received in U.S. Appl. No. 16/258,394, 8 pages.

Office Action, dated Oct. 11, 2019, received in Australian Patent Application No. 2019202417, 4 pages.

Office Action, dated Aug. 30, 2019, received in Korean Patent Application No. 2019-7019100, 2 pages.

Notice of Allowance, dated Nov. 1, 2019, received in Korean Patent Application No. 2019-7019100, 5 pages.

International Search Report and Written Opinion dated May 26, 2014, received in International Application No. PCT/US2013/040053, which corresponds to U.S. Appl. No. 14/535,671, 32 pages.

International Preliminary Report on Patentability dated Nov. 20, 2014, received in International Application No. PCT/US2013/040053, which corresponds to U.S. Appl. No. 14/535,671, 26 pages.

International Search Report and Written Opinion dated Apr. 7, 2014, received in International Application No. PCT/US2013/069472, which corresponds to U.S. Appl. No. 14/608,895, 24 pages.

International Preliminary Report on Patentability, dated Jun. 30, 2015, received in International Patent Application No. PCT/US2013/069472, which corresponds with U.S. Appl. No. 14/608,895, 18 pages.

International Search Report and Written Opinion dated Aug. 7, 2013, received in International Application No. PCT/US2013/040054, which corresponds to U.S. Appl. No. 14/536,235, 12 pages.

International Preliminary Report on Patentability dated Nov. 20, 2014, received in International Application No. PCT/US2013/040054, which corresponds to U.S. Appl. No. 14/536,235, 11 pages.

International Search Report and Written Opinion dated Aug. 7, 2013, received in International Application No. PCT/US2013/040056, which corresponds to U.S. Appl. No. 14/536,367, 12 pages.

International Preliminary Report on Patentability dated Nov. 20, 2014, received in International Application No. PCT/US2013/040056, which corresponds to U.S. Appl. No. 14/536,367, 11 pages.

Extended European Search Report, dated Nov. 6, 2015, received in European Patent Application No. 15183980.0, which corresponds with U.S. Appl. No. 14/536,426, 7 pages.

Extended European Search Report, dated Jul. 30, 2018, received in European Patent Application No. 18180503.7, which corresponds with U.S. Appl. No. 14/536,426, 7 pages.

International Search Report and Written Opinion dated Aug. 6, 2013, received in International Application No. PCT/US2013/040058, which corresponds to U.S. Appl. No. 14/536,426, 12 pages.

International Preliminary Report on Patentability dated Nov. 20, 2014, received in International Application No. PCT/US2013/040058, which corresponds to U.S. Appl. No. 14/536,426, 11 pages.

International Search Report and Written Opinion dated Feb. 5, 2014, received in International Application No. PCT/US2013/040061, which corresponds to U.S. Appl. No. 14/536,464, 30 pages.

International Preliminary Report on Patentability dated Nov. 20, 2014, received in International Application No. PCT/US2013/040061, which corresponds to U.S. Appl. No. 14/536,464, 26 pages.

International Search Report and Written Opinion dated May 8, 2014, received in International Application No. PCT/US2013/040067, which corresponds to U.S. Appl. No. 14/536,644, 45 pages.

International Preliminary Report on Patentability dated Nov. 20, 2014, received in International Application No. PCT/US2013/040067, which corresponds to U.S. Appl. No. 14/536,644, 36 pages.

International Search Report and Written Opinion dated Mar. 12, 2014, received in International Application No. PCT/US2013/069479, which corresponds with U.S. Appl. No. 14/608,926, 14 pages.

International Preliminary Report on Patentability, dated Jun. 30, 2015, received in International Patent Application No. PCT/US2013/069479, which corresponds with U.S. Appl. No. 14/608,926, 11 pages.

International Search Report and Written Opinion dated Aug. 7, 2013, received in International Application No. PCT/US2013/040070, which corresponds to U.S. Appl. No. 14/535,646, 12 pages.

International Preliminary Report on Patentability dated Nov. 20, 2014, received in International Application No. PCT/US2013/040070, which corresponds to U.S. Appl. No. 14/535,646, 10 pages.

International Search Report and Written Opinion dated Apr. 7, 2014, received in International Application No. PCT/US2013/040072, which corresponds to U.S. Appl. No. 14/536,141, 38 pages.

International Preliminary Report on Patentability dated Nov. 20, 2014, received in International Application No. PCT/US2013/040072, which corresponds to U.S. Appl. No. 14/536,141, 32 pages.

Extended European Search Report, dated Dec. 5, 2018, received in European Patent Application No. 18194127.9, which corresponds with U.S. Appl. No. 14/608,942, 8 pages.

International Search Report and Written Opinion dated Apr. 7, 2014, received in International Application No. PCT/US2013/069483, which corresponds with U.S. Appl. No. 14/608,942, 18 pages.

International Preliminary Report on Patentability, dated Jun. 30, 2015, received in International Application No. PCT/2013/069483, which corresponds to U.S. Appl. No. 14/608,942, 13 pages.

International Search Report and Written Opinion dated Mar. 3, 2014, received in International Application No. PCT/US2013/040087, which corresponds to U.S. Appl. No. 14/536,166, 35 pages.

International Preliminary Report on Patentability dated Nov. 20, 2014, received in International Application No. PCT/2013/040087, which corresponds to U.S. Appl. No. 14/536,166, 29 pages.

International Search Report and Written Opinion dated Aug. 7, 2013, received in International Application No. PCT/US2013/040093, which corresponds to U.S. Appl. No. 14/536,203, 11 pages.

International Preliminary Report on Patentability dated Nov. 20, 2014, received in International Application No. PCT/2013/040093, which corresponds to U.S. Appl. No. 14/536,203, 9 pages.

International Search Report and Written Opinion dated Jul. 9, 2014, received in International Application No. PCT/US2013/069484, which corresponds with U.S. Appl. No. 14/608,965, 17 pages.

International Preliminary Report on Patentability, dated Jun. 30, 2015, received in International Patent Application No. PCT/US2013/069484, which corresponds with U.S. Appl. No. 14/608,965, 12 pages.

International Search Report and Written Opinion dated Feb. 5, 2014, received in International Application No. PCT/US2013/040098, which corresponds to U.S. Appl. No. 14/536,247, 35 pages.

International Preliminary Report on Patentability dated Nov. 20, 2014, received in International Application No. PCT/2013/040098, which corresponds to U.S. Appl. No. 14/536,247, 27 pages.

Extended European Search Report, dated Oct. 7, 2016, received in European Patent Application No. 16177863.4, which corresponds with U.S. Appl. No. 14/536,267, 12 pages.

Extended European Search Report, dated Oct. 30, 2018, received in European Patent Application No. 18183789.9, which corresponds with U.S. Appl. No. 14/536,267, 11 pages.

International Search Report and Written Opinion dated Jan. 27, 2014, received in International Application No. PCT/US2013/040101, which corresponds to U.S. Appl. No. 14/536,267, 30 pages.

International Preliminary Report on Patentability dated Nov. 20, 2014, received in International Application No. PCT/2013/040101, which corresponds to U.S. Appl. No. 14/536,267, 24 pages.

Extended European Search Report, dated Nov. 24, 2017, received in European Patent Application No. 17186744.3, which corresponds with U.S. Appl. No. 14/536,291, 10 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

International Search Report and Written Opinion dated Jan. 8, 2014, received in International Application No. PCT/US2013/040108, which corresponds to U.S. Appl. No. 14/536,291, 30 pages.

International Preliminary Report on Patentability dated Nov. 20, 2014, received in International Application No. PCT/2013/040108, which corresponds to U.S. Appl. No. 14/536,291, 25 pages.

International Search Report and Written Opinion dated Jun. 2, 2014, received in International Application No. PCT/US2013/069486, which corresponds with U.S. Appl. No. 14/608,985, 7 pages.

International Preliminary Report on Patentability, dated Jun. 30, 2015, received in International Patent Application No. PCT/US2013/069486, which corresponds with U.S. Appl. No. 14/608,985, 19 pages.

International Search Report and Written Opinion dated Mar. 6, 2014, received in International Application No. PCT/US2013/069489, which corresponds with U.S. Appl. No. 14/609,006, 12 pages.

International Preliminary Report on Patentability, dated Jun. 30, 2015, received in International Patent Application No. PCT/US2013/069489, which corresponds with U.S. Appl. No. 14/609,006, 10 pages.

Extended European Search Report, dated Mar. 15, 2017, received in European Patent Application No. 17153418.3, which corresponds with U.S. Appl. No. 14/536,648, 7 pages.

Search Report, dated Apr. 13, 2017, received in Dutch Patent Application No. 2016452, which corresponds with U.S. Appl. No. 14/864,737, 22 pages.

Search Report, dated Jun. 22, 2017, received in Dutch Patent Application No. 2016375, which corresponds with U.S. Appl. No. 14/866,981, 17 pages.

International Search Report and Written Opinion, dated Oct. 14, 2016, received in International Patent Application No. PCT/US2016/020697, which corresponds with U.S. Appl. No. 14/866,981, 21 pages.

Search Report, dated Jun. 19, 2017, received in Dutch Patent Application No. 2016377, which corresponds with U.S. Appl. No. 14/866,159, 13 pages.

International Search Report and Written Opinion, dated Apr. 25, 2016, received in International Patent Application No. PCT/US2016/018758, which corresponds with U.S. Appl. No. 14/866,159, 15 pages.

Extended European Search Report, dated Oct. 17, 2017, received in European Patent Application No. 17184437.6, which corresponds with U.S. Appl. No. 14/868,078, 8 pages.

Search Report, dated Apr. 13, 2017, received in Dutch Patent Application No. 2016376, which corresponds with U.S. Appl. No. 14/868,078, 15 pages.

International Search Report and Written Opinion, dated Jul. 21, 2016, received in International Patent Application No. PCT/US2016/019913, which corresponds with U.S. Appl. No. 14/868,078, 16 pages.

Search Report, dated Apr. 18, 2017, received in Dutch Patent Application No. 2016801, which corresponds with U.S. Appl. No. 14/863,432, 34 pages.

International Search Report and Written Opinion, dated Oct. 31, 2016, received in International Patent Application No. PCT/US2016/033578, which corresponds with U.S. Appl. No. 14/863,432, 36 pages.

International Search Report and Written Opinion, dated Nov. 14, 2016, received in International Patent Application No. PCT/US2016/033541, which corresponds with U.S. Appl. No. 14/866,511, 29 pages.

Extended European Search Report, dated Aug. 17, 2018, received in European Patent Application No. 18175195.9, which corresponds with U.S. Appl. No. 14/869,899, 13 pages.

International Search Report and Written Opinion, dated Aug. 29, 2016, received in International Patent Application No. PCT/US2016/021400, which corresponds with U.S. Appl. No. 14/869,899, 48 pages.

International Preliminary Report on Patentability, dated Sep. 12, 2017, received in International Patent Application No. PCT/US2016/021400, which corresponds with U.S. Appl. No. 14/869,899, 39 pages.

International Search Report and Written Opinion, dated Jan. 12, 2017, received in International Patent No. PCT/US2016/046419, which corresponds with U.S. Appl. No. 14/866,992, 23 pages.

International Search Report and Written Opinion, dated Dec. 15, 2016, received in International Patent Application No. PCT/US2016/046403, which corresponds with U.S. Appl. No. 15/009,661, 17 pages.

International Search Report and Written Opinion, dated Feb. 27, 2017, received in International Patent Application No. PCT/US2016/046407, which corresponds with U.S. Appl. No. 15/009,688, 30 pages.

International Preliminary Report on Patentability, dated Feb. 13, 2018, received in International Patent Application No. PCT/US2016/046407, which corresponds with U.S. Appl. No. 15/009,688, 20 pages.

Search Report, dated Feb. 15, 2018, received in Dutch Patent Application No. 2019215, which corresponds with U.S. Appl. No. 14/864,529, 13 pages.

Extended European Search Report, dated Nov. 14, 2019, received in European Patent Application No. 19194418.0, which corresponds with U.S. Appl. No. 14/864,580, 8 pages.

Search Report, dated Feb. 15, 2018, received in Dutch Patent Application No. 2019214, which corresponds with U.S. Appl. No. 14/864,601, 12 pages.

Extended European Search Report, dated Oct. 10, 2017, received in European Patent Application No. 17188507.2, which corresponds with U.S. Appl. No. 14/866,361, 9 pages.

Extended European Search Report, dated Jun. 22, 2017, received in European Patent Application No. 16189421.7, which corresponds with U.S. Appl. No. 14/866,987, 7 pages.

Extended European Search Report, dated Sep. 11, 2017, received in European Patent Application No. 17163309.2, which corresponds with U.S. Appl. No. 14/866,987, 8 pages.

Extended European Search Report, dated Jun. 8, 2017, received in European Patent Application No. 16189425.8, which corresponds with U.S. Appl. No. 14/866,989, 8 pages.

Extended European Search Report, dated Aug. 2, 2018, received in European Patent Application No. 18168941.5, which corresponds with U.S. Appl. No. 14/871,236, 11 pages.

Extended European Search Report, dated Jul. 25, 2017, received in European Patent Application No. 17171972.7, which corresponds with U.S. Appl. No. 14/870,882, 12 pages.

Extended European Search Report, dated Jul. 25, 2017, received in European Patent Application No. 17172266.3, which corresponds with U.S. Appl. No. 14/871,336, 9 pages.

Extended European Search Report, dated Dec. 21, 2016, received in European Patent Application No. 16189790.5, which corresponds with U.S. Appl. No. 14/871,462, 8 pages.

Extended European Search Report, dated Mar. 8, 2019, received in European Patent Application No. 18205283.7, which corresponds with U.S. Appl. No. 15/081,771, 15 pages.

Extended European Search Report, dated Aug. 24, 2018, received in European Patent Application No. 18171453.6, which corresponds with U.S. Appl. No. 15/136,782, 9 pages.

International Search Report and Written Opinion, dated Jan. 3, 2017, received in International Patent Application No. PCT/US2016/046214, which corresponds with U.S. Appl. No. 15/231,745, 25 pages.

Extended European Search Report, dated May 30, 2018, received in European Patent Application No. 18155939.4, which corresponds with U.S. Appl. No. 15/272,327, 8 pages.

Extended European Search Report, dated Mar. 2, 2018, received in European Patent Application No. 17206374.5, which corresponds with U.S. Appl. No. 15/272,343, 11 pages.

Extended European Search Report, dated Oct. 28, 2019, received in European Patent Application No. 19195414.8, which corresponds with U.S. Appl. No. 16/240,672, 6 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Extended European Search Report, dated Nov. 13, 2019, received in European Patent Application No. 19194439.6, which corresponds with U.S. Appl. No. 16/262,800, 12 pages.

Extended European Search Report, dated Oct. 9, 2019, received in European Patent Application No. 19181042.3, which corresponds with U.S. Appl. No. 15/272,343, 10 pages.

Geisler, "Enriched Links: A Framework for Improving Web Navigation Using Pop-Up Views", Journal of the American Society for Information Science, Chapel Hill, NC, Jan. 1, 2000, 13 pages.

Office Action, dated Feb. 18, 2020, received in Australian Patent Application No. 2018223021, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Notice of Allowance, dated Mar. 27, 2020, received in Australian Patent Application No. 2018223021, which corresponds with U.S. Appl. No. 14/536,426, 3 pages.

Certificate of Grant, dated Dec. 5, 2019, received in Australian Patent Application No. 2018256626, which corresponds with U.S. Appl. No. 14/536,646, 3 pages.

Notice of Acceptance, dated Jan. 22, 2020, received in Australian Patent Application No. 2018256616, which corresponds with U.S. Appl. No. 14/536,141, 3 pages.

Decision to Grant, dated Jan. 23, 2020, received in European Patent Application No. 13726053.5, which corresponds with U.S. Appl. No. 14/536,141, 1 page.

Patent, dated Feb. 19, 2020, received in European Patent Application No. 13726053.5, which corresponds with U.S. Appl. No. 14/536,141, 4 page.

Notice of Allowance dated Jan. 2, 2020, received in U.S. Appl. No. 14/608,965, 5 pages.

Office Action, dated Dec. 20, 2019, received in Chinese Patent Application No. 201610537334.1, which corresponds with U.S. Appl. No. 14/536,267, 3 pages.

Patent, dated Nov. 27, 2019, received in European Patent Application No. 17186744.3, which corresponds with U.S. Appl. No. 14/536,291, 4 pages.

Office Action, dated Jan. 7, 2020, received in U.S. Appl. No. 14/609,006, 17 pages.

Office Action, dated Mar. 16, 2020, received in Chinese Patent Application No. 201610131415.1, which corresponds with U.S. Appl. No. 14/866,981, 3 pages.

Decision to Grant, dated Mar. 5, 2020, received in European Patent Application No. 16707356.8, which corresponds with U.S. Appl. No. 14/866,159, 2 pages.

Notice of Allowance, dated Mar. 20, 2020, received in Chinese Patent Application No. 201610342313.4, which corresponds with U.S. Appl. No. 14/863,432, 6 pages.

Patent, dated Feb. 8, 2017, received in Chinese Patent Application No. 201620470063.8, which corresponds with U.S. Appl. No. 14/863,432, 5 pages.

Office Action, dated Jan. 10, 2020, received in Japanese Patent Application No. 2018-243773, which corresponds with U.S. Appl. No. 14/863,432, 6 pages.

Patent, dated Feb. 7, 2020, received in Chinese Patent Application No. 201610342264.4, which corresponds with U.S. Appl. No. 14/866,511, 7 pages.

Patent, dated Jan. 1, 2020, received in European Patent Application No. 16727900.9, which corresponds with U.S. Appl. No. 14/866,511, 3 pages.

Decision to Grant, dated Mar. 26, 2020, received in European Patent Application No. 18168939.9, which corresponds with U.S. Appl. No. 14/869,899, 3 pages.

Office Action, dated Jan. 13, 2020, received in Chinese Patent Application No. 201610658351.8, which corresponds with U.S. Appl. No. 14/866,992, 3 pages.

Final Office Action, dated Dec. 30, 2019, received in U.S. Appl. No. 15/009,661, 33 pages.

Intention to Grant, dated Mar. 16, 2020, received in European Patent Application No. 16753796.8, which corresponds with U.S. Appl. No. 15/009,688, 6 pages.

Notice of Allowance, dated Jan. 6, 2020, received in U.S. Appl. No. 14/856,520, 5 pages.

Notice of Allowance, dated Mar. 4, 2020, received in U.S. Appl. No. 14/856,520, 6 pages.

Office Action, dated Jan. 20, 2020, received in Japanese Patent Application No. 2017-029201, which corresponds with U.S. Appl. No. 14/857,636, 21 pages.

Certificate of Grant, dated Jan. 23, 2020, received in Australian Patent Application No. 2019200872, which corresponds with U.S. Appl. No. 14/864,580, 3 pages.

Patent, dated Jan. 31, 2020, received in Chinese Patent Application No. 201610342336.5, which corresponds with U.S. Appl. No. 14/866,987, 7 pages.

Patent, dated Dec. 11, 2019, received in European Patent Application No. 16189421.7, which corresponds with U.S. Appl. No. 14/866,987, 3 pages.

Office Action, dated Feb. 3, 2020, received in European Patent Application No. 17163309.2, which corresponds with U.S. Appl. No. 14/866,987, 6 pages.

Office Action, dated Feb. 3, 2020, received in European Patent Application No. 16189425.8, which corresponds with U.S. Appl. No. 14/866,989, 6 pages.

Office Action, dated Mar. 17, 2020, received in Mx/a/2017/011610, which corresponds with U.S. Appl. No. 14/871,236, 4 pages.

Office Action, dated Feb. 21, 2020, received in European Patent Application No. 16711725.8, which corresponds with U.S. Appl. No. 14/867,990, 13 pages.

Office Action, dated Jan. 31, 2020, received in European Patent Application No. 16753795.0, which corresponds with U.S. Appl. No. 15/009,668, 9 pages.

Office Action, dated Jan. 24, 2020, received in European Patent Application No. 18205283.7, which corresponds with U.S. Appl. No. 15/081,771, 4 pages.

Office Action, dated Feb. 26, 2020, received in Chinese Patent Application No. 201810119007.3, which corresponds with U.S. Appl. No. 15/136,782, 3 pages.

Patent, dated Nov. 29, 2019, received in Japanese Patent Application No. 2018-158502, which corresponds with U.S. Appl. No. 15/231,745, 3 pages.

Notice of Acceptance, dated Dec. 10, 2019, received in Australian Patent Application No. 2018204234, which corresponds with U.S. Appl. No. 15/272,327, 3 pages.

Notice of Allowance, dated Feb. 20, 2020, received in U.S. Appl. No. 15/272,341, 12 pages.

Notice of Allowance, dated Dec. 11, 2019, received in Chinese Patent Application No. 201810071627.4, which corresponds with U.S. Appl. No. 15/272,343, 4 pages.

Patent, dated Feb. 7, 2020, received in Hong Kong Patent Application No. 18101477.0, which corresponds with U.S. Appl. No. 15/272,345, 6 pages.

Notice of Allowance, dated Dec. 27, 2019, received in Korean Patent Application No. 2019-7009439, which corresponds with U.S. Appl. No. 15/499,693, 5 pages.

Notice of Allowance, dated Feb. 20, 2020, received in U.S. Appl. No. 15/655,749, 10 pages.

Office Action, dated Feb. 3, 2020, received in Chinese Patent Application No. 201710331254.5, which corresponds with U.S. Appl. No. 15/655,749, 8 pages.

Final Office Action, dated Feb. 5, 2020, received in U.S. Appl. No. 15/785,372, 26 pages.

Final Office Action, dated Feb. 27, 2020, received in U.S. Appl. No. 15/979,347, 19 pages.

Office Action, dated Mar. 9, 2020, received in U.S. Appl. No. 16/145,954, 15 pages.

Office Action, dated Mar. 6, 2020, received in U.S. Appl. No. 16/154,591, 16 pages.

Office Action, dated Feb. 27, 2020, received in Korean Patent Application No. 2019-7019946, which corresponds with U.S. Appl. No. 16/154,591, 5 pages.

Final Office Action, dated Mar. 19, 2020, received in U.S. Appl. No. 16/174,170, 35 pages.

Office Action, dated Mar. 6, 2020, received in U.S. Appl. No. 16/243,834, 19 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Office Action, dated Dec. 18, 2019, received in Australian Patent Application No. 2018282409, which corresponds with U.S. Appl. No. 16/243,834, 3 pages.

Notice of Allowance, dated Dec. 23, 2019, received in Korean Patent Application No. 2018-7037896, which corresponds with U.S. Appl. No. 16/243,834, 6 pages.

Patent, dated Mar. 13, 2020, received in Korean Patent Application No. 2018-7037896, which corresponds with U.S. Appl. No. 16/243,834, 7 pages.

Notice of Allowance, dated Dec. 13, 2019, received in Korean Patent Application No. 2019-7033444, which corresponds with U.S. Appl. No. 16/252,478, 6 pages.

Patent, dated Mar. 12, 2020, received in Korean Patent Application No. 2019-7033444, which corresponds with U.S. Appl. No. 16/252,478, 6 pages.

Patent, dated Jan. 31, 2020, received in Korean Patent Application No. 2019-7019100, 5 pages.

Brewster, "The Design and Evaluation of a Vibrotactile Progress Bar", Glasgow Interactive Systems Group, University of Glasgow, Glasgow, G12 8QQ, UK, 2005, 2 pages.

Jones, "Touch Screen with Feeling", IEEE Spectrum spectrum.ieee.org/commuting/hardware/touch-screens-with-feeling, May 1, 2009, 2 pages.

Nishino, "A Touch Screen Interface Design with Tactile Feedback", Computer Science, 2011 International Conference on Complex, Intelligent, and Software Intensive Systems, 2011, 4 pages.

Certificate of Grant, dated Jul. 23, 2020, received in Australian Patent Application No. 2018223021, which corresponds with U.S. Appl. No. 14/536,426, 4 pages.

Decision to Grant, dated Aug. 20, 2020, received in European Patent Application No. 18194127.9, which corresponds with U.S. Appl. No. 14/608,942, 4 pages.

Certificate of Grant, dated Sep. 3, 2020, received in Australian Patent Application No. 2018250481, which corresponds with U.S. Appl. No. 14/536,203, 4 pages.

Patent, dated Sep. 29, 2020, received in Chinese Patent Application No. 201610537334.1, which corresponds with U.S. Appl. No. 14/536,267, 7 pages.

Office Action, dated Aug. 21, 2020, received in European Patent Application No. 18183789.9, which corresponds with U.S. Appl. No. 16/262,800, 9 pages.

Patent, dated Jul. 31, 2020, received in Chinese Patent Application No. 201710781246.0, which corresponds with U.S. Appl. No. 14/536,291, 6 pages.

Office Action, dated Jul. 17, 2020, received in Chinese Patent Application No. 2018100116175.X, which corresponds with U.S. Appl. No. 14/536,291, 15 pages.

Office Action, dated Jul. 24, 2020, received in Chinese Patent Application No. 201711422121.5, which corresponds with U.S. Appl. No. 14/536,648, 10 pages.

Notice of Allowance, dated Jul. 29, 2020, received in Korean Patent Application No. 2020-7003065, which corresponds with U.S. Appl. No. 14/866,511, 5 pages.

Office Action, dated Jul. 24, 2020, received in Chinese Patent Application No. 201680041559.6, which corresponds with U.S. Appl. No. 14/866,992, 13 pages.

Office Action, dated Sep. 16, 2020, received in U.S. Appl. No. 15/009,661, 37 pages.

Decision to Grant, dated Aug. 27, 2020, received in European Patent Application No. 16756866.6, which corresponds with U.S. Appl. No. 15/009,676, 4 pages.

Notice of Allowance, dated Oct. 9, 2020, received in Chinese Patent Application No. 201680047164.7, which corresponds with U.S. Appl. No. 15/009,688, 5 pages.

Decision to Grant, dated Sep. 24, 2020, received in European Patent Application No. 16753796.8, which corresponds with U.S. Appl. No. 15/009,688, 4 pages.

Notice of Allowance, dated Oct. 1, 2020, received in U.S. Appl. No. 14/856,520, 5 pages.

Office Action, dated Jul. 1, 2020, received in Chinese Patent Application No. 201711262953.5, which corresponds with U.S. Appl. No. 14/857,636, 13 pages.

Notice of Allowance, dated Oct. 16, 2020, received in Japanese Patent Application No. 2017-029201, which corresponds with U.S. Appl. No. 14/857,636, 4 pages.

Notice of Allowance, dated Sep. 18, 2020, received in Japanese Patent Application No. 2018-201076, which corresponds with U.S. Appl. No. 14/857,663, 5 pages.

Office Action, dated Aug. 26, 2020, received in Indian Application No. 201617032291, which corresponds with U.S. Appl. No. 14/866,987, 9 pages.

Intention to Grant, dated Oct. 5, 2020, received in European Patent Application No. 18168941.5, which corresponds with U.S. Appl. No. 14/871,236, 8 pages.

Notice of Allowance, dated Sep. 7, 2020, received in Mx/a/2017/011610, which corresponds with U.S. Appl. No. 14/871,236, 12 pages.

Office Action, dated Aug. 3, 2020, received in Chinese Patent Application No. 201610870912.3, which corresponds with U.S. Appl. No. 14/870,882, 4 pages.

Office Action, dated Jul. 20, 2020, received in Indian Patent Application No. 201617032293, which corresponds with U.S. Appl. No. 14/871,227, 9 pages.

Office Action, dated Aug. 4, 2020, received in Chinese Patent Application No. 201610871323.7, which corresponds with U.S. Appl. No. 14/871,336, 18 pages.

Office Action, dated Aug. 20, 2020, received in Chinese Patent Application No. 201680046985.9, which corresponds with U.S. Appl. No. 15/009,668, 15 pages.

Decision to Grant, dated Aug. 27, 2020, received in European Patent Application No. 18205283.7, which corresponds with U.S. Appl. No. 15/081,771, 4 pages.

Office Action, dated Aug. 31, 2020, received in Chinese Patent Application No. 201810151593.X, which corresponds with U.S. Appl. No. 15/272,327, 10 pages.

Patent, dated Sep. 18, 2020, received in Chinese Patent Application No. 201680022696.5, which corresponds with U.S. Appl. No. 15/272,345, 6 pages.

Notice of Acceptance, dated Jul. 22, 2020, received in Australian Patent Application No. 2019203776, which corresponds with U.S. Appl. No. 15/499,693, 3 pages.

Office Action, dated Jul. 23, 2020, received in U.S. Appl. No. 15/785,372, 23 pages.

Office Action, dated Sep. 25, 2020, received in U.S. Appl. No. 15/994,843, 5 pages.

Office Action, dated Sep. 17, 2020, received in U.S. Appl. No. 16/136,163, 13 pages.

Final Office Action, dated Oct. 1, 2020, received in U.S. Appl. No. 16/154,591, 19 pages.

Office Action, dated Oct. 13, 2020, received in Australian Patent Application No. 2019203175, which corresponds with U.S. Appl. No. 16/154,591, 5 pages.

Notice of Allowance, dated Aug. 26 2020, received in U.S. Appl. No. 16/240,669, 18 pages.

Office Action, dated Aug. 10, 2020, received in U.S. Appl. No. 16/240,672, 13 pages.

Office Action, dated Sep. 24, 2020, received in Australian Patent Application No. 2019268116, which corresponds with U.S. Appl. No. 16/240,672, 4 pages.

Notice of Allowance, dated Sep. 24, 2020, received in U.S. Appl. No. 16/243,834, 10 pages.

Office Action, dated Sep. 18, 2020, received in Australian Patent Application No. 2018282409, which corresponds with U.S. Appl. No. 16/243,834, 3 pages.

Office Action, dated Aug. 7, 2020, received in Japanese Patent Application No. 2019-058800, which corresponds with U.S. Appl. No. 16/243,834, 8 pages.

Office Action, dated Sep. 15, 2020, received in European Patent Application No. 19194439.6, which corresponds with U.S. Appl. No. 16/262,800, 6 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Notice of Allowance, dated Sep. 15, 2020, received in Australian Patent Application No. 2019257437, which corresponds with U.S. Appl. No. 16/252,478, 3 pages.

Office action, dated Aug. 27, 2020, received in U.S. Appl. No. 16/241,883, 11 pages.

Notice of Allowance, dated Sep. 28, 2020, received in U.S. Appl. No. 16/241,883, 10 pages.

Notice of Allowance, dated Aug. 25, 2020, received in U.S. Appl. No. 16/354,035, 14 pages.

Notice of Allowance, dated Jul. 6, 2020, received in Australian Patent Application No. 2019202417, which corresponds with U.S. Appl. No. 16/896,141, 3 pages.

Office Action, dated Aug. 21, 2020, received in Japanese Patent Application No. 2019-047319, which corresponds with U.S. Appl. No. 16/896,141, 6 pages.

Office Action, dated Oct. 7, 2020, received in U.S. Appl. No. 16/563,505, 20 pages.

Office Action, dated Oct. 19, 2020, received in U.S. Appl. No. 16/685,773, 15 pages.

Office Action, dated Sep. 21, 2020, received in U.S. Appl. No. 16/803,904, 5 pages.

Extended European Search Report, dated Oct. 6, 2020, received in European Patent Application No. 20188553.0, which corresponds with U.S. Appl. No. 15/499,693, 11 pages.

Office Action, dated Jan. 4, 2021, received in Chinese Patent Application No. 201810826224.6, which corresponds with U.S. Appl. No. 14/536,426, 6 pages.

Notice of Allowance, dated Jan. 25, 2021, received in U.S. Appl. No. 14/536,464, 5 pages.

Office Action, dated Dec. 1, 2020, received in Chinese Patent Application No. 201810369259.1, which corresponds with U.S. Appl. No. 14/608,926, 14 pages.

Office Action, dated Oct. 26, 2020, received in Chinese Patent Application No. 201711422092.2, which corresponds with U.S. Appl. No. 14/536,646, 20 pages.

Office Action, dated Jan. 22, 2021, received in Japanese Patent Application No. 2018-022394, which corresponds with U.S. Appl. No. 14/536,203, 2 pages.

Office Action, dated Jan. 20, 2021, received in Chinese Patent Application No. 201810332044.2, which corresponds with U.S. Appl. No. 14/536,267, 15 pages.

Office Action, dated Nov. 17, 2020, received in Chinese Patent Application No. 2018100116175.X, which corresponds with U.S. Appl. No. 14/536,291, 16 pages.

Notice of Allowance, dated Dec. 4, 2020, received in Chinese Patent Application No. 201610131415.1, which corresponds with U.S. Appl. No. 14/866,981, 3 pages.

Patent, dated Jan. 22, 2021, received in Chinese Patent Application No. 201610131415.1, which corresponds with U.S. Appl. No. 14/866,981, 6 pages.

Patent, dated Dec. 11, 2020, received in Chinese Patent Application No. 201680011338.4, which corresponds with U.S. Appl. No. 14/868,078, 3 pages.

Notice of Allowance, dated Dec. 4, 2020, received in Japanese Patent Application No. 2018-243773, which corresponds with U.S. Appl. No. 14/863,432, 5 pages.

Patent, dated Jan. 5, 2021, received in Japanese Patent Application No. 2018-243773, which corresponds with U.S. Appl. No. 14/863,432, 4 pages.

Patent, dated Oct. 12, 2020, received in Korean Patent Application No. 2020-7015964, which corresponds with U.S. Appl. No. 14/863,432, 8 pages.

Patent, dated Oct. 29, 2020, received in Korean Patent Application No. 2020-7003065, which corresponds with U.S. Appl. No. 14/866,511, 5 pages.

Office Action, dated Nov. 6, 2020, received in Chinese Patent Application No. 201610871595.7, which corresponds with U.S. Appl. No. 14/869,899, 15 pages.

Office Action, dated Nov. 25, 2020, received in Chinese Patent Application No. 201610658351.8, which corresponds with U.S. Appl. No. 14/866,992, 9 pages.

Office Action, dated Nov. 30, 2020, received in Chinese Patent Application No. 201680047125.7, which corresponds with U.S. Appl. No. 15/009,676, 11 pages.

Patent, dated Sep. 23, 2020, received in European Patent Application No. 16756866.6, which corresponds with U.S. Appl. No. 15/009,676, 4 pages.

Patent, dated Nov. 10, 2020, received in Chinese Patent Application No. 201680047164.7, which corresponds with U.S. Appl. No. 15/009,688, 6 pages.

Certificate of Grant, dated Oct. 21, 2020, received in European Patent Application No. 16753796.8, which corresponds with U.S. Appl. No. 15/009,688, 4 pages.

Patent, dated Nov. 27, 2020, received in Chinese Patent Application No. 201711262953.5, which corresponds with U.S. Appl. No. 14/857,636, 6 pages.

Patent, dated Nov. 12, 2020, received in Japanese Patent Application No. 2017-029201, which corresponds with U.S. Appl. No. 14/857,636, 3 pages.

Notice of Allowance, dated Dec. 2, 2020, received in Chinese Patent Application No. 201711261143.8, which corresponds with U.S. Appl. No. 14/857,663, 3 pages.

Patent, dated Jan. 22, 2021, received in Chinese Patent Application No. 201711261143.8, which corresponds with U.S. Appl. No. 14/857,663, 6 pages.

Patent, dated Oct. 19, 2020, received in Japanese Patent Application No. 2018-201076, which corresponds with U.S. Appl. No. 14/857,663, 4 pages.

Office Action, dated Dec. 21, 2020, received in Korean Patent Application No. 2020-7029178, which corresponds with U.S. Appl. No. 14/870,882, 2 pages.

Intention to Grant, dated Feb. 3, 2021, received in European Patent Application No. 17188507.2, which corresponds with U.S. Appl. No. 14/866,361, 7 pages.

Patent, dated Jan. 8, 2021, received in Hong Kong Patent Application No. 18100151.5, which corresponds with U.S. Appl. No. 14/866,987, 6 pages.

Intention to Grant, dated Dec. 3, 2020, received in European Patent Application No. 16189425.8, which corresponds with U.S. Appl. No. 14/866,989, 7 pages.

Patent, dated Dec. 2, 2020, received in Mx/a/2017/011610, which corresponds with U.S. Appl. No. 14/871,236, 4 pages.

Office Action, dated Dec. 21, 2020, received in Chinese Patent Application No. 201610870912.3, which corresponds with U.S. Appl. No. 14/870,882, 5 pages.

Notice of Allowance, dated Jan. 27, 2021, received in Chinese Patent Application No. 201810151593.X, which corresponds with U.S. Appl. No. 15/272,327, 3 pages.

Office Action, dated Dec. 4, 2020, received in Japanese Patent Application No. 2019-212493, which corresponds with U.S. Appl. No. 15/272,345, 5 pages.

Certificate of Grant, dated Nov. 26, 2020, received in Australian Patent Application No. 2019203776, which corresponds with U.S. Appl. No. 15/499,693, 3 pages.

Office action, dated Nov. 20, 2020, received in Japanese Patent Application No. 2019-200174, which corresponds with U.S. Appl. No. 15/499,693, 6 pages.

Final Office Action, dated Nov. 18, 2020, received in U.S. Appl. No. 15/785,372, 27 pages.

Final Office Action, dated Jan. 25, 2021, received in U.S. Appl. No. 15/979,347, 12 pages.

Notice of Allowance, dated Jan. 22, 2021, received in U.S. Appl. No. 15/994,843, 8 pages.

Office Action, dated Dec. 10, 2020, received in U.S. Appl. No. 16/145,954, 5 pages.

Office Action, dated Oct. 30, 2020, received in U.S. Appl. No. 16/230,707, 20 pages.

Final Office Action, dated Nov. 27, 2020, received in U.S. Appl. No. 16/240,672, 12 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Office Action, dated Jan. 28, 20201, received in Australian Patent Application No. 2019268116, which corresponds with U.S. Appl. No. 16/240,672, 4 pages.

Notice of Acceptance, dated Oct. 21, 2020, received in Australian Patent Application No. 2018282409, which corresponds with U.S. Appl. No. 16/243,834, 3 pages.

Notice of Allowance, dated Nov. 20, 2020, received in U.S. Appl. No. 16/262,784, 8 pages.

Office Action, dated Feb. 5, 2021, received in U.S. Appl. No. 16/262,800, 53 pages.

Certificate of Grant, dated Nov. 5, 2020, received in Australian Patent Application No. 2019202417, which corresponds with U.S. Appl. No. 16/896,141, 4 pages.

Notice of Allowance, dated Jan. 6, 2021, received in U.S. Appl. No. 16/509,438, 5 pages.

Final Office Action, dated Feb. 2, 2021, received in U.S. Appl. No. 16/685,773, 20 pages.

Notice of Allowance, dated Jan. 6, 2021, received in U.S. Appl. No. 16/803,904, 9 pages.

Patent, dated Sep. 16, 2020, received in European Patent Application No. 18194127.9, which corresponds with U.S. Appl. No. 14/608,942, 4 pages.

Patent, dated Sep. 23, 2020, received in European Patent Application No. 18205283.7, which corresponds with U.S. Appl. No. 15/081,771, 4 pages.

Garcia-Hernandez et al., "Orientation Discrimination of Patterned Surfaces through an Actuated and Non-Actuated Tactile Display", 2011 IEEE World Haptics Conference, Istanbul, Jun. 21-24, 2011, 3 pages.

Notice of Allowance, dated Feb. 23, 2021, received in U.S. Appl. No. 14/536,464, 5 pages.

Final Office Action, dated Feb. 26, 2021, received in U.S. Appl. No. 15/009,661, 46 pages.

Office Action, dated Mar. 4, 2021, received in U.S. Appl. No. 16/154,591, 20 pages.

Notice of Allowance, dated Feb. 18, 2021, received in U.S. Appl. No. 16/230,707, 9 pages.

Office Action, dated Feb. 8, 2021, received in Japanese Patent Application No. 2018-000753, which corresponds with U.S. Appl. No. 14/536,426, 2 pages.

Notice of Allowance, dated Mar. 22, 2021, received in Chinese Patent Application No. 201711422092.2, which corresponds with U.S. Appl. No. 14/536,646, 2 pages.

Office Action, dated Mar. 10, 2021, received in Chinese Patent Application No. 20181142423.1, which corresponds with U.S. Appl. No. 14/536,141, 6 pages.

Notice of Allowance, dated Mar. 29, 2021, received in Chinese Patent Application No. 2018100116175.X, which corresponds with U.S. Appl. No. 14/536,291, 1 page.

Notice of Allowance, dated Feb. 2, 2021, received in Chinese Patent Application No. 201711422121.5, which corresponds with U.S. Appl. No. 14/536,648, 1 page.

Patent, dated Mar. 9, 2021, received in Chinese Patent Application No. 201711422121.5, which corresponds with U.S. Appl. No. 14/536,648, 7 pages.

Notice of Allowance, dated Feb. 24, 2021, received in Chinese Patent Application No. 201680047125.7, which corresponds with U.S. Appl. No. 15/009,676, 1 page.

Decision to Grant, dated Feb. 25, 2021, received in European Patent Application No. 16189425.8, which corresponds with U.S. Appl. No. 14/866,989, 1 page.

Decision to Grant, dated Mar. 25, 2021, received in European Patent Application No. 18168941.5, which corresponds with U.S. Appl. No. 14/871,236, 2 pages.

Notice of Allowance, dated Mar. 22, 2021, received in Chinese Patent Application No. 201610870912.3, which corresponds with U.S. Appl. No. 14/870,882, 1 pages.

Office Action, dated Feb. 9, 2021, received in Chinese Patent Application No. 201610871323.7, which corresponds with U.S. Appl. No. 14/871,336, 1 page.

Office Action, dated Mar. 19, 2021, received in European Patent Application No. 16753795.0, which corresponds with U.S. Appl. No. 15/009,668, 5 pages.

Patent, dated Feb. 5, 2021, received in Hong Kong Patent Application No. 1257553, which corresponds with U.S. Appl. No. 15/136,782, 14 pages.

Office Action, dated Mar. 22, 2021, received in Chinese Patent Application No. 201710331254.5, which corresponds with U.S. Appl. No. 15/655,749, 4 pages.

Certificate of Grant, dated Feb. 18, 2021, received in Australian Patent Application No. 2018282409, which corresponds with U.S. Appl. No. 16/243,834, 3 pages.

Office Action, dated Feb. 12, 2021, received in Japanese Patent Application No. 2019-058800, which corresponds with U.S. Appl. No. 16/243,834, 2 pages.

Office action, dated Feb. 25, 2021, received in Australian Patent Application No. 2020201648, which corresponds with U.S. Appl. No. 16/262,784, 3 pages.

Office Action, dated Mar. 25, 2021, received in European Patent Application No. 19194439.6, which corresponds with U.S. Appl. No. 16/262,800, 5 pages.

Office Action, dated Feb. 23, 2021, received in Korean Patent Application No. 2020-7031330, which corresponds with U.S. Appl. No. 15/272,398, 6 pages.

\* cited by examiner




Figure 1A




Figure 1B




Figure 2A





Figure 2B




Figure 2C




Figure 2D




Figure 2E




Figure 3




Figure 4A




Figure 4B




Figure 4C




Figure 5A




Figure 5B




Figure 5C




Figure 5D

Portable Multifunction Device  
100




Figure 5E




Figure 5F




Figure 5G




Figure 5H




Figure 5I




Figure 5J




Figure 5K




Figure 5L




Figure 5M




Figure 5N




Figure 50




Figure 5P




Figure 5Q




Figure 5R




Figure 5S




Figure 5T




Figure 5U




Figure 5V




Figure 5W




Figure 5X

Portable Multifunction Device  
100




Figure 5Y

Portable Multifunction Device  
100




Figure 5Z




Figure 5AA




Figure 5AB




Figure 5AC

Portable Multifunction Device  
100




Figure 5AD




Figure 5AE




Figure 5AF




Figure 5AG




Figure 5AH




Figure 5A1




Figure 5AJ




Figure 5AK




Figure 5AL




Figure 5AM




Figure 5AN




Figure 5AO




Figure 5AP




Figure 5AQ




Figure 5AR




Figure 5AS




Figure 5AT

Portable Multifunction Device  
100




Figure 5AU






Figure 5AW

Portable Multifunction Device  
100




Figure 5AX

Portable Multifunction Device  
100




Figure 6A

Portable Multifunction Device  
100




Figure 6B




Figure 6C




Figure 6D

Portable Multifunction Device  
100




Figure 6E




Figure 6F




Figure 6G




Figure 6H




Figure 6I




Figure 6J




Figure 7A




Figure 7B




Figure 7C




Figure 8




Figure 9A





Figure 9B





Figure 9C





Figure 9D







Figure 9E







Figure 9G







Figure 9H







Figure 9J







Figure 9K







Figure 9M





Figure 9N





Figure 90





Figure 9P





Figure 9Q





Figure 9R





Figure 9S





Figure 9T





Figure 9U





Figure 9V





Figure 9W





Figure 9X





Figure 9Y





Figure 9Z





Figure 9AA





Figure 9AB





Figure 9AC





Figure 9AD

1000




Figure 10A

1000

A






Figure 10B

1000




Figure 10C




Figure 10D




Figure 10E




Figure 10F

1000

N




Figure 10G

1100




Figure 11A

1100




Figure 11B





Figure 11C

1100

E



F




Figure 11D

1100




Figure 11E

1100



Forego performing the text selection operation, in response to detecting the second press input, in accordance with a determination that the second press input is accompanied by simultaneous movement of the contact across the touch-sensitive surface

1156



When the text is editable text, the text selection indicator is a cursor and selecting content between the first location and the second location includes expand the selection character-by-character in accordance with movement of the contact on the touch-sensitive surface; and when the text is non-editable text, the text selection indicator is a selection region that initially encompasses a single word and selecting content between the first location and the second location includes expanding the selection word-by-word in accordance with movement of the contact on the touch-sensitive surface

1158

Figure 11F




Figure 12





Figure 13A





Figure 13B





Figure 13C





Figure 13D





Figure 13E





Figure 13F





Figure 13G





Figure 13H





Figure 13I





Figure 13J





Figure 13K





Figure 13L





Figure 13M





Figure 13N





Figure 130





Figure 13P





Figure 13Q

1400





Figure 14A

1400



A

1420 Enter the text into the content region includes enter a character that corresponds to character key at a location at which touchdown of the contact was detected on the onscreen keyboard.

1422 Enter the text into the content region includes enter a character that corresponds to character key at a location at which liftoff of the contact was detected on the onscreen keyboard.

B

1424 In response to detecting that the text-selection criteria have been met, generate a tactile output that is indicative of an entry into a text selection mode of operation.

C

1426 In response to detecting that the text-selection criteria have been met, change an appearance of the onscreen keyboard to indicate that the device is operating in a text selection mode of operation. Change the appearance of the onscreen keyboard includes obscure an appearance of characters on keys of the onscreen keyboard.

1428 End the text selection mode of operation and, in conjunction with the end of the text selection mode of operation, reverse the change in appearance of the onscreen keyboard to reveal the characters on the keys of the onscreen keyboard.

Figure 14B

1400

D

1430 When the touch input satisfies the text-selection criteria, detect movement of the contact after the touch input has satisfied the text-selection criteria and move a cursor in the content region in accordance with the movement of the contact detected after the touch input has satisfied the text-selection criteria.

E

1432 When the touch input satisfies the text-selection criteria, detect a first subsequent change in the characteristic intensity of the contact followed by additional movement of the contact on the touch-sensitive display.

1434 In response to detecting the first subsequent change in the characteristic intensity of the contact:

1436 In accordance with a determination that the touch input satisfies selection-start criteria, the selection-start criteria include a criterion that is met when the characteristic intensity of the contact increases above a selection-start intensity threshold, start to select content in the content region at a location of a cursor in accordance with the additional movement of the contact; and in accordance with a determination that the touch input does not satisfy the selection-start criteria, move the cursor in accordance with the additional movement of the contact without starting to select content in the content region.

F

1438 When the touch input satisfies selection-start criteria, after starting to select content in the content region, detect liftoff of the contact from the touch-sensitive display and confirm the selection in response to detecting the liftoff of the contact.

Figure 14C

1400

F

1440 When the touch input satisfies selection-start criteria, after starting to select content in the content region, and while continuing to detect the contact on the touch-sensitive display, detect a second subsequent change in intensity of the contact.

1442 In response to detecting the second subsequent change in the characteristic intensity of the contact:

1444 In accordance with a determination that the second subsequent change in the characteristic intensity of the contact satisfies selection-cancellation criteria, the selection-cancellation criteria include a criterion that is met when the characteristic intensity of the contact increases above a selection-cancellation intensity threshold, cancel the selection; and in accordance with a determination that the second subsequent change in the characteristic intensity of the contact does not satisfy the selection-cancellation criteria, maintain the selection.

1446 The selection-cancellation criterion include a criterion that is met when the contact moves no more than a threshold distance within a threshold amount of time before the characteristic intensity of the contact increases above the selection-cancellation intensity threshold.

G

1448 In response to detecting that the selection-cancellation criteria have been met, generate a tactile output that is indicative of an exit from the text selection mode of operation.

Figure 14D




Figure 14E

1400



1460 While the respective word is selected, detect first subsequent movement of the contact; and in response to detecting the first subsequent movement of the contact while the respective word is selected: in accordance with a determination that the touch input meets selection-expansion criteria which includes a movement criterion that is met when the contact moves more than a respective threshold amount, expand the selection to include a word that is adjacent to the respective word in a first direction in accordance with the first subsequent movement of the contact.



1462 While the respective word is selected, detect a fourth subsequent change in the characteristic intensity of the contact above a respective intensity threshold; and, in response to detecting the fourth subsequent change in the characteristic intensity of the contact, in accordance with a determination that the touch input meets the selection-cancellation criteria, which includes a criterion that is met when the amount of time between when the third subsequent change in the characteristic intensity of the contact is detected and when the fourth subsequent change in the characteristic intensity of the contact is detected is greater than the delay threshold, cancel selection of the respective word.



1464 While the respective word is selected, detecting a fourth subsequent change in the characteristic intensity of the contact above a respective intensity threshold (e.g., the selection-start intensity threshold); and, in response to detecting the fourth subsequent change in the characteristic intensity of the contact, in accordance with a determination that the touch input meets sentence-selection criteria which include a movement criterion that is met when the contact moves less than a threshold amount within a threshold time period before the fourth subsequent change in intensity of the contact was detected and a time criterion that is met when an amount of time between when the third subsequent change in the characteristic intensity of the contact is detected and when the fourth subsequent change in the characteristic intensity of the contact is detected is less than a delay threshold, expand the selection to include the respective sentence that contains the respective word.



Figure 14F




Figure 14G




Figure 14H




Figure 15

## TOUCH INPUT CURSOR MANIPULATION

## RELATED APPLICATIONS

This application is a continuation of U.S. application Ser. No. 16/258,394, filed Jan. 25, 2019, which is a continuation of U.S. application Ser. No. 15/499,693, filed Apr. 27, 2017, now U.S. Pat. No. 10,222,980, which is a continuation of U.S. patent application Ser. No. 14/866,361, filed Sep. 25, 2015, now U.S. Pat. No. 9,639,184, which is a continuation of U.S. patent application Ser. No. 14/864,737, filed Sep. 24, 2015, now U.S. Pat. No. 9,785,305, which claims priority to U.S. Provisional Patent Application Ser. No. 62/215,720, filed Sep. 8, 2015, U.S. Provisional Patent Application Ser. No. 62/213,593, filed Sep. 2, 2015, U.S. Provisional Patent Application Ser. No. 62/172,162, filed Jun. 7, 2015, and U.S. Provisional Patent Application Ser. No. 62/135,619, filed Mar. 19, 2015. All of these applications are incorporated by reference herein in their entireties.

## TECHNICAL FIELD

This disclosure relates generally to electronic devices with touch-sensitive surfaces, and in particular to cursor manipulation and content selection in an electronic document.

## BACKGROUND

The use of touch-sensitive surfaces as input devices for computers and other electronic computing devices has increased significantly in recent years. Exemplary touch-sensitive surfaces include touch pads and touch screen displays. Such surfaces are widely used to review and edit electronic documents by manipulating a cursor within the electronic document presented on a display. These electronic documents are viewed or edited within applications having viewing and editing capabilities (e.g., drawing applications, presentation applications (e.g., Apple's KEYNOTE, or Microsoft's POWERPOINT), word processing applications (e.g., Apple's PAGES or Microsoft's WORD), website creation applications, spreadsheet applications (e.g., Apple's NUMBERS or Microsoft's EXCEL)).

Conventional cursor manipulation methods that require the use of a mouse, or other peripheral input mechanism, are relatively inefficient as they require the user to move one hand away from the keyboard to the mouse in order to make the selection. Similarly, conventional user interfaces provided on touch screen displays do not provide a simple and intuitive way to manipulate the cursor for content selection and editing. As such, it is desirable to provide a more efficient means for manipulating a cursor displayed in an electronic document presented on a touch screen display.

## SUMMARY

Accordingly, there is a need for electronic devices with faster, more efficient methods and interfaces for cursor manipulation and content (e.g., text) selection. Such methods and interfaces optionally complement or replace conventional methods for cursor manipulation and content selection. Such methods and interfaces reduce the number, extent, and/or nature of the inputs from a user and produce a more efficient human-machine interface. For battery-operated devices, a more efficient input mechanism also requires less computing resources, thereby increasing battery life of the device.

In order to manipulate a cursor in a document on a conventional portable multifunction device, users often need to make finger contact with precise locations on a touch sensitive screen at the location of the cursor. This is often difficult and the user cannot see the precise location of the cursor under their finger.

The above deficiencies and other problems associated with user interfaces for electronic devices with touch-sensitive surfaces are addressed by the devices and methods described herein. The methods described herein allow a user to manipulate a cursor and perform editing functions, such as text selection and moving a selection, from any part of the touch-sensitive surface. For example, a two-finger touch input can be detected anywhere on the touch screen, including over the keyboard. Users can greatly benefit from this for at least two reasons. First, the multi-finger gesture detection can be distinguished from a single-finger detection (e.g., single-finger taps), so that a single-finger contact or gesture at the keyboard can be reserved for other functions, e.g., text entry. Second, it allows for a more efficient user input because the user does not have to consider where the cursor gestures are being made (e.g., the user need not be concerned about inadvertent key activation) and can instead focus on the movement of the cursor.

In some embodiments, the device is portable (e.g., a notebook computer, tablet computer, or handheld device), while in other embodiments, the device is a desktop computer. The device has a touch-sensitive display (also known as a "touch screen" or "touch screen display"), and in some embodiments it also includes a touchpad.

In some embodiments, the device has a graphical user interface (GUI), one or more processors, memory and one or more modules, programs or sets of instructions stored in the memory for performing multiple functions. In some embodiments, the user interacts with the GUI primarily through touch inputs, including finger contacts and gestures, on the touch-sensitive surface. In some embodiments, the functions optionally include image reviewing, editing, drawing, presenting, word processing, website creation, authoring disks, spreadsheet creation or editing, playing games, using a telephone on the device, video-conferencing, e-mailing, instant messaging, digital photography or videography, web browsing, playing digital music or video, note taking, or the like. Executable instructions for performing these functions are, optionally, included in a non-transitory computer readable storage medium or other computer program product configured for execution by one or more processors.

In accordance with some embodiments, a method of cursor manipulation is performed at a portable multifunction device including one or more processors, memory, and a touch screen display. The method includes: displaying content of an electronic document on the display; displaying a cursor within the electronic document; detecting two substantially simultaneous touch inputs anywhere on the touch screen display; and in response to detecting the two substantially simultaneous touch inputs: selecting a portion of the content in the document closest to the cursor; and displaying the portion of the content as selected content.

In accordance with some embodiments, the method of cursor manipulation further includes: while the portion of the content is displayed as selected content, detecting an additional two substantially simultaneous touch inputs anywhere on the touch screen display; in response to detecting the additional two substantially simultaneous touch inputs, selecting a first expanded portion of the content that includes the portion of the content; and displaying the first expanded portion as selected content.

In accordance with some embodiments, the method of cursor manipulation further includes: while the first expanded portion of the content is displayed as selected content, detecting an additional two substantially simultaneous touch inputs on the touch screen display; in response to detecting the additional two substantially simultaneous touch inputs, selecting a second expanded portion of the content that includes the expanded portion of the content; and displaying the second expanded portion as selected content.

In accordance with some embodiments, the method of cursor manipulation further includes: while the second expanded portion of the content is displayed as selected content, detecting an additional two substantially simultaneous touch inputs on the touch screen display; in response to detecting the additional two substantially simultaneous touch inputs, selecting a third expanded portion of the content that includes the first expanded portion of the content; and displaying the third expanded portion as selected content.

In accordance with some embodiments, the content includes text and the portion of the content is a word located closest to the cursor in the text, the expanded portion is a sentence, the first expanded portion is a paragraph, and the second expanded cursor is a page.

In accordance with some embodiments, the content includes text and the portion of the content is a word located closest to the cursor.

In accordance with some embodiments, the method of cursor manipulation further includes: detecting lift-off of the two substantially simultaneous touch inputs from the touch screen display, followed by an additional two substantially simultaneous touch inputs anywhere on the touch screen display; detecting a continuous touch gesture from locations of the additional two substantially simultaneous touch inputs on the touch screen display to additional locations on the touch screen display; and in response to detecting the continuous touch gesture, expanding the selected content to include additional content beyond the portion in a direction of toward the additional locations.

In accordance with some embodiments, the method of cursor manipulation further includes: detecting a first touch input on the touch screen display at a first location within the expanded selected content; detecting, substantially simultaneous with the detection of the first touch input, a second touch input at a second location within the expanded selected content; and in response to detecting the first and second touch inputs, expanding the display of the selected content based on the selected content.

In accordance with some embodiments, the method further includes: upon determining that the two substantially simultaneous touch inputs remain in contact with the touch screen display, detecting a continuous touch gesture at least partially across the touch screen display from locations of the two substantially simultaneous touch inputs; in response to the gesture, expanding the selection of the content beyond the portion of the content in a direction of the gesture.

In accordance with some embodiments, the cursor is an insertion point.

In accordance with some embodiments, the method of cursor manipulation further includes: detecting an additional two substantially simultaneous touch inputs on the touch screen display at respective first and second locations within boundaries of the selected content; upon determining that the two substantially simultaneous touch inputs remain in contact with the touch screen display, detecting a continuous touch gesture across the touch screen display; in response to

detecting a lift off of the continuous touch gesture, moving the selected content to a different location.

In accordance with some embodiments, the method of cursor manipulation further includes: prior to moving the selected content to the second location, displaying a ghost cursor offset from the selected content, wherein the ghost selection moves with the continuous touch gesture, wherein the different location is the location of the ghost cursor at the time of the lift off.

In accordance with some embodiments, a method of cursor manipulation is performed at a portable multifunction device including one or more processors, memory, and a touch screen display. The method includes: displaying content of an electronic document on the touch screen display; displaying a cursor at a current location within the content on the touch screen display; detecting two substantially simultaneous touch inputs at a first region on the touch screen display; upon determining that the two substantially simultaneous touch inputs remain in contact with the touch screen display, detecting a continuous touch gesture from a location of the two substantially simultaneous touch inputs across the touch screen display from the first region to a second region; and in response to detecting the continuous touch gesture: moving the cursor from the current location to a new location in a direction of the continuous touch gesture.

In accordance with some embodiments, a distance between the first region and the second region is substantially the same as a distance between the current location and the new location.

In accordance with some embodiments, the method further includes: while moving the cursor, displaying a ghost cursor offset from the cursor; and upon detecting a termination of the continuous touch gesture, placing the cursor at the location of the ghost cursor and ceasing the display of the ghost cursor.

In accordance with some embodiments, displaying the cursor at a current location includes displaying a selection of a portion of the content at the current location, moving the cursor from the current location to a new location in a direction of the continuous touch gesture includes: dismissing the selection and moving the cursor from the current location to the new location.

In accordance with some embodiments, a method of cursor manipulation is performed at a portable multifunction device including one or more processors, memory, and a touch screen display. The method includes: displaying text on the display; displaying a cursor at a line within the text; detecting a two-finger swipe gesture on the touch screen display in a direction at least partially parallel to the line and towards an edge of the touch screen display; and in response to detecting the two-finger swipe gesture moving the cursor to a distal point of the text. For example, an end or beginning of a line or a top or bottom of a page or document.

In accordance with some embodiments, the detecting requires that the two-finger swipe gesture be performed at a speed higher than a predetermined speed.

In accordance with some embodiments, the distal point of the text is at a location in the direction of the gesture. For example, an end or beginning of a line or a top or bottom of a page or document.

In accordance with some embodiments, moving the cursor to the distal point of the text includes moving the cursor to a beginning or an end of the line of the text or a beginning or an end of the text (e.g., the top or bottom of a document or page) in accordance with the direction of the two-finger swipe.

5

In accordance with some embodiments, a method of cursor manipulation is performed at a portable multifunction device including one or more processors, memory, and a touch screen display. The method includes: displaying content of an electronic document on the display; displaying a cursor within the electronic document; detecting a touch input on the touch screen display, wherein the touch input is located on a word within the content; and in response to detecting the touch input: selecting the word; and displaying a command display area adjacent to the selected word, wherein the second command display area includes an icon for cutting the selected word, an icon for copying the selected word, and an icon for pasting a previously selected content.

In accordance with some embodiments, a method of selection manipulation is performed at a portable multifunction device including one or more processors, memory, and a touch screen display. The method includes: displaying content of an electronic document on the display; displaying a selection of the content within the electronic document; detecting a single touch input on the touch screen display at a location over the selection; in response to detecting the single touch input at the location, displaying a set of options related to the selection; determining if the single touch input remains at the location for a predetermined amount of time followed by a continuous touch gesture away from the location on the touch screen display; and in response to detecting the single touch input remaining at the location for the predetermined amount of time followed by the continuous touch gesture away from the location, moving the selection to a different location in a direction of the continuous touch gesture.

In accordance with some embodiments, a method of selection manipulation is performed at a portable multifunction device including one or more processors, memory, and a touch screen display. The method includes: displaying content of an electronic document on the display; displaying a selection of the content within the electronic document; detecting three substantially simultaneous touch inputs at locations anywhere on the touch screen display; determining if the three substantially simultaneous touch inputs is followed by three continuous touch gestures away from the locations on the touch screen display; and in response to detecting the three continuous touch gestures, moving the selection to a different location in a direction of the continuous touch gestures.

In accordance with some embodiments, a method of cursor manipulation is performed at a portable multifunction device including one or more processors, memory, and a touch screen display. The method includes: displaying content of an electronic document on the touch screen display, the content includes at least one line of text comprising at least two words; detecting a touch input on the content; and in response to detecting the touch input: determining a distance of the touch input to a closest space between the two words within the electronic document; and in accordance with a determination that the distance is greater than a predetermined threshold distance, selecting a word within the electronic document closest to the touch input and displaying an indication of the selection.

In accordance with some embodiments, the method further places a cursor in the closest space after a preceding word when the distance is less than the predetermined threshold distance.

In accordance with some embodiments, the predetermined threshold distance is calculated based on the percentage of the size of the word closest to the touch input.

6

In accordance with some embodiments, the method further includes: while displaying the selection, detecting an additional touch input on the touch screen display at a location within the selection; and in response to detecting the additional touch input, dismissing the selection and placing a cursor adjacent to a word within the electronic document based on the location of the additional touch input relative to the closest space to this word.

In accordance with some embodiments, the method further includes: while displaying the selection, detecting an additional touch input on the touch screen display at a location within the selection; detecting, without breaking contact with the touch screen display following the additional touch input, a continuous touch gesture from a first location of the additional touch input on the touch screen display to a second location on the touch screen display; and in response to detecting the continuous touch gesture, expanding the selection to include additional content beyond the word in a direction towards the second location.

In accordance with some embodiments, the method further includes: detecting a double-tap touch input; in response to detecting the double-tap touch input, selecting a word closest to the double-tap touch input; and displaying an indication of the selection.

In accordance with some embodiments, the method further includes: detecting a double-tap touch input at a space between two words within the electronic document; in response to detecting the double-tap touch input, selecting the word closest to the double-tap touch input that follows the space; and displaying an indication of the selection.

In accordance with some embodiments, the method further includes: detecting a triple-tap touch input; in response to detecting the triple-tap touch input, selecting a sentence closest to the triple-tap touch input; and displaying an indication of the selection of the sentence.

In accordance with some embodiments, the method further includes: detecting a quadruple-tap touch input; in response to detecting the quadruple-tap touch input, selecting a paragraph closest to the quadruple-tap touch input; and displaying an indication of the selection of the paragraph.

In accordance with some embodiments, the method further includes: detecting a quintuple-tap touch input; in response to detecting the quintuple-tap touch input, selecting the content; and displaying an indication of the selection of the content.

In accordance with some embodiments, selecting the word within the electronic document closest to the touch input is performed when the distance is equal to the predetermined threshold distance.

In accordance with some embodiments, placing the cursor in the closest space after the preceding word is performed when the distance is equal to the predetermined threshold distance.

In accordance with some embodiments, a method of keyboard display is performed at a portable multifunction device including one or more processors, memory, and a touch screen display. The method includes: displaying content of an electronic document on the touch screen display; displaying a soft keyboard on the touch screen display; detecting two substantially simultaneous touch inputs on the soft keyboard; and in response to detecting the two substantially simultaneous touch inputs on the soft keyboard, displaying a blurred soft keyboard.

In accordance with some embodiments, the method further includes: detecting, without breaking contact with the touch screen display following the two substantially simultaneous touch inputs, movements of the two substantially

touch inputs from the soft keyboard to the content; and in response to detecting the continuous finger contact to the content, replacing display of the blurred soft keyboard with display of the soft keyboard.

In accordance with some embodiments, displaying the blurred soft keyboard includes changing one or more of: color, hue, saturation, brightness, and contrast of the soft keyboard based on the content of the electronic document.

In accordance with some embodiments, a method of content selection is performed at a portable multifunction device including one or more processors, memory, and a touch-sensitive display. The method includes: concurrently displaying an onscreen keyboard and a content presentation region on the touch-sensitive display, wherein the content presentation region displays text input received from the onscreen keyboard; detecting a touch input on the onscreen keyboard displayed on the touch-sensitive display; in response to detecting the touch input on the onscreen keyboard displayed on the touch-sensitive display, determining whether the touch input satisfies one or more criteria for entering a text selection mode; and in accordance with a determination that the touch input satisfies the one or more criteria for entering the text selection mode: concurrently displaying, in the content presentation region, a first cursor at a first location and a second cursor at a second location that is different from the first location.

In accordance with some embodiments, the one or more criteria for entering the text selection mode include the touch input including a two-finger drag gesture over the onscreen keyboard.

In accordance with some embodiments, the device has one or more sensors to detect intensity of contacts with the touch-sensitive display, the touch input on the touch-sensitive display includes an input by a contact on the onscreen keyboard, and the one or more criteria for entering the text selection mode include the contact on the onscreen keyboard having an intensity that exceeds a predetermined deep press intensity threshold.

In accordance with some embodiments, the method further includes: in accordance with the determination that the touch input satisfies the one or more criteria for entering the text selection mode: visually obscuring keys on the onscreen keyboard.

In accordance with some embodiments, visually obscuring the keys on the onscreen keyboard includes applying a blurring effect to the onscreen keyboard.

In accordance with some embodiments, visually obscuring the keys on the onscreen keyboard includes transforming the onscreen keyboard into an onscreen touchpad.

In accordance with some embodiments, visually obscuring the keys on the onscreen keyboard includes making the onscreen keyboard semitransparent to partially reveal content lying underneath the onscreen keyboard.

In accordance with some embodiments, the second location is based on a location of an initial contact in the touch input; and the first location is a permitted insertion position in the content presentation region that is based on the second location.

In accordance with some embodiments, the first location is an insertion position at which the first cursor is located when the touch input is determined to satisfy the one or more criteria for entering the text selection mode; and the second location is displaced from the first location by a predetermined offset.

In accordance with some embodiments, one of the first and second cursors is already displayed in the content

presentation region before both of the first and second cursors are concurrently displayed in the content presentation region.

In accordance with some embodiments, the method further includes: detecting movement of one or more contacts of the touch input; and moving the second cursor within the content presentation region in accordance with the movement of the one or more contacts of the touch input.

In accordance with some embodiments, the method further includes: moving the first cursor based on the movement of the second cursor, wherein movement of the first cursor includes discrete movements between permitted insertion positions in the content presentation region.

In accordance with some embodiments, the method further includes: detecting a lift-off of the touch input after detecting the movement of the one or more contacts of the touch input; and in response to detecting the lift-off of the touch input: ceasing to display the second cursor.

In accordance with some embodiments, the method further includes: in response to detecting the lift-off of the touch input, maintaining display of the first cursor at a respective permitted insertion position reached by the first cursor after the discrete movements of the first cursor.

In accordance with some embodiments, the method further includes: in response to detecting the lift-off of the touch input, ceasing to display the first cursor.

In accordance with some embodiments, the onscreen keyboard is obscured in accordance with the determination that the touch input satisfies the one or more criteria for entering the text selection mode, and the method further includes: in response to detecting the lift-off of the touch input, restoring display of the onscreen keyboard.

In accordance with some embodiments, the device has one or more sensors to detect intensity of contacts with the touch-sensitive display, and the method further includes: in the text selection mode, detecting that an intensity of a contact in the touch input exceeds a predetermined intensity threshold; after detecting that the intensity of the contact in the touch input exceeds the predetermined intensity threshold, detecting movement of the contact in the touch input; in response to detecting the movement of the contact in the touch input, after detecting that the intensity of the contact in the touch input exceeds the predetermined intensity threshold: selecting a portion of the text input in accordance with the movement of the contact in the touch input.

In accordance with some embodiments, the selected portion of the text input begins at a position of the first cursor when the detected intensity of the contact in the touch input exceeded the predetermined intensity threshold.

In accordance with some embodiments, the method further includes: detecting lift-off of the contact in the touch input after selecting the portion of the text input in accordance with the movement of the contact in the touch input; and, in response to detecting the lift-off of the contact in the touch input, confirming selection of the portion of the text input.

In accordance with some embodiments, the method further includes: after selecting the portion of the text input, while the portion of the text input is selected, detecting an intensity of the contact in the touch input that exceeds the predetermined threshold; and, in response to detecting the intensity of the contact in the touch input that exceeds the predetermined threshold while the portion of the text input is selected, clearing selection of the portion of the text input.

In accordance with some embodiments, the method further includes: after selecting the portion of the text input, while the portion of the text input is selected, detecting an

intensity of the contact in the touch input that exceeds the predetermined threshold and that is followed by lift-off of the contact without further movement of the contact; and, in response to detecting the intensity of the contact in the touch input that exceeds the predetermined threshold and that is followed by lift-off of the contact without further movement of the contact, confirming selection of the portion of the text input.

In accordance with some embodiments, the method further includes: after selecting the portion of the text input, while the portion of the text input is selected, detecting an intensity of the contact in the touch input that exceeds the predetermined threshold and that is followed by further movement of the contact; and, in response to detecting the intensity of the contact in the touch input that exceeds the predetermined threshold and that is followed by the further movement of the contact: clearing selection of the portion of the text input.

In accordance with some embodiments, the method further includes: in response to detecting the intensity of the contact in the touch input that exceeds the predetermined threshold and that is followed by the further movement of the contact: starting selection of a new portion of the text input in accordance with the further movement of the contact.

In accordance with some embodiments, the method further includes: in response to detecting the intensity of the contact in the touch input that exceeds the predetermined threshold and that is followed by the further movement of the contact: further moving the second cursor and the first cursor within the content presentation region in accordance with the further movement of the contact.

In accordance with some embodiments, the device has one or more sensors to detect intensity of contacts with the touch-sensitive display, and the method further includes: in the text selection mode, detecting a first local intensity peak in the touch input followed by a second local intensity peak in the touch input that both exceed a predetermined intensity threshold; and, in response to detecting the first local intensity peak followed by the second local intensity peak that both exceed the predetermined intensity threshold, selecting a first predetermined unit of the text input according to a current location of the first cursor.

In accordance with some embodiments, the method further includes: after detecting the first local intensity peak followed by the second local intensity peak, detecting a third consecutive local intensity peak in the touch input that exceeds the predetermined intensity threshold; and in response to detecting the three consecutive local intensity peaks in the touch input that all exceed the predetermined deep press intensity threshold, selecting a second predetermined unit of the text input that is larger than and includes the first predetermined unit of the text input.

In accordance with some embodiments, a method of content selection is performed at a portable multifunction device including one or more processors, memory, a touch screen display, and one or more sensors to detect intensity of contacts with the touch-sensitive surface. The method includes: while a contact is detected on the touch-sensitive surface, concurrently displaying on the display content and a text selection indicator at a first location within the content; detecting a first press input by the contact followed by movement of the contact across the touch-sensitive surface that corresponds to movement of at least a portion of the text selection indicator from the first location to a second location on the display; in response to detecting the first press input by the contact followed by movement of the contact

across the touch-sensitive surface, selecting content between the first location and the second location; while the content between the first location and the second location is selected, detecting a second press input by the contact on the touch-sensitive surface; in response to detecting the second press input by the contact on the touch-sensitive surface, performing a text selection operation, associated with the content between the first location and the second location, in accordance with the second press input, wherein the contact in the first press input, the movement across the touch-sensitive surface, and the second press input is a single continuous contact with the touch-sensitive surface.

In accordance with some embodiments, detecting the first press input by the contact followed by movement of the contact across the touch-sensitive surface includes: detecting an increase in intensity of the contact above a predetermined intensity threshold followed by detecting a decrease in intensity of the contact to an intensity that remains above a predetermined minimum intensity value.

In accordance with some embodiments, the method further includes: in response to detecting the first press input by the contact followed by movement of the contact across the touch-sensitive surface: displaying at least the portion of the text selection indicator at the second location within the content.

In accordance with some embodiments, the text selection operation includes stopping selection of content at the second location and maintaining selection of the content between the first location and the second location.

In accordance with some embodiments, the method further includes: after detecting the second press input and while the content between the first location and the second location remains selected, detecting lift-off of the contact; and in response to detecting the lift-off of the contact, displaying an action menu for the selected content between the first location and the second location.

In accordance with some embodiments, the method further includes: after detecting the second press input by the contact on the touch-sensitive surface and stopping the selection of the content at the second location, detecting further movement of the contact; and in response to detecting the further movement of the contact, displaying at least a portion of the text selection indicator at a third location within the content.

In accordance with some embodiments, the method further includes: in response to detecting the further movement of the contact, canceling selection of content between the first location and the second location without selecting content between the second location and the third location.

In accordance with some embodiments, the text selection operation includes cancelling selection of content between the first location and the second location.

In accordance with some embodiments, the method further includes: after detecting the second press input by the contact on the touch-sensitive surface and canceling the selection of content between the first location and the second location, detecting further movement of the contact; and, in response to detecting the further movement of the contact, selecting content between the second location and a third location.

In accordance with some embodiments, the method further includes: while the content between the second location and the third location is selected, detecting lift-off of the contact; and, in response to detecting the lift-off of the contact while the content between the second location and the third location is selected, stopping selection of the

content at the third location and maintaining selection of the content between the second location and the third location.

In accordance with some embodiments, the method further includes: before displaying the text selection indicator at the first location within the content, detecting an initial press input by the contact on the touch-sensitive surface; and in response to detecting the initial press input, displaying the text selection indicator at an initial location within the content that corresponds to a location of the initial press input on the touch-sensitive surface.

In accordance with some embodiments, the display is a touch-sensitive display that includes the touch-sensitive surface, and the method further includes: concurrently displaying, on the touch-sensitive display, the content and an onscreen keyboard, wherein the initial press input is detected on the onscreen keyboard.

In accordance with some embodiments, the initial press input is detected at a location on the touch-sensitive surface that corresponds to a location of the content on the display.

In accordance with some embodiments, the display is a touch-sensitive display that includes the touch-sensitive surface, and the method further includes: concurrently displaying, on the touch-sensitive display, the content and an onscreen keyboard; before displaying the text selection indicator at the first location within the content, detecting a multi-contact drag input on the onscreen keyboard; and, in response to detecting the multi-contact drag input on the onscreen keyboard, displaying the text selection indicator at an initial location within the content based on a location of the multi-contact drag input on the onscreen keyboard.

In accordance with some embodiments, the content includes editable content and the text selection indicator includes a cursor.

In accordance with some embodiments, the method further includes: displaying a magnifying loupe that displays a magnified version of the cursor and a region surrounding the cursor.

In accordance with some embodiments, selecting the content between the first location and the second location includes: moving the cursor one character space at a time in response to detecting the movement of the contact across the touch-sensitive surface; and selecting one additional character at a time in accordance with the movement of the cursor.

In accordance with some embodiments, the content includes read-only content and the text selection indicator includes a selection area; and displaying the text selection indicator at the first location includes displaying a first word located at the first location within the selection area.

In accordance with some embodiments, the method further includes: displaying a magnifying loupe that displays a magnified version of the selection area and a region surrounding the selection area.

In accordance with some embodiments, selecting the content between the first location and the second location includes: expanding the selection area one word at a time in accordance with the movement of the contact across the touch-sensitive surface; and selecting one additional word at a time in accordance with the expansion of the selection area.

In accordance with some embodiments, the method further includes: foregoing performing the text selection operation, in response to detecting the second press input, in accordance with a determination that the second press input is accompanied by simultaneous movement of the contact across the touch-sensitive surface.

In accordance with some embodiments, when the text is editable text, the text selection indicator is a cursor and selecting content between the first location and the second location includes expanding the selection character-by-character in accordance with movement of the contact on the touch-sensitive surface; and when the text is non-editable text, the text selection indicator is a selection region that initially encompasses a single word and selecting content between the first location and the second location includes expanding the selection word-by-word in accordance with movement of the contact on the touch-sensitive surface.

In accordance with some embodiments, a method of content selection is performed at a portable multifunction device including one or more processors, memory, and a touch-sensitive display. The method includes: concurrently displaying an onscreen keyboard and a content presentation region on the touch-sensitive display, wherein the content presentation region displays text input received from the onscreen keyboard; detecting a touch input on the onscreen keyboard displayed on the touch-sensitive display, wherein detecting the touch input includes detecting movement of a contact and liftoff of the contact; in response to detecting the touch input on the onscreen keyboard displayed on the touch-sensitive display: in accordance with a determination that the touch input satisfies text-selection criteria, wherein the text-selection criteria include a criterion that is met when a characteristic intensity of the contact increases above a text-selection intensity threshold, performing a text selection operation based on the movement of the contact; and in accordance with a determination that the touch input satisfies text-entry criteria, wherein the text-entry criteria include a criterion that is met when the characteristic intensity of the contact does not increase above the text-selection intensity threshold, entering text into the content presentation region based on the touch input.

In accordance with some embodiments, the text-entry criteria include a criterion that is met when the liftoff of the contact is detected while the contact is at a location of a character key of the onscreen keyboard.

In accordance with some embodiments, the text-entry criteria include a criterion that is met when the contact does not move outside of the onscreen keyboard before liftoff of the contact is detected.

In accordance with some embodiments, entering the text into the content region includes entering a character that corresponds to character key at a location at which touchdown of the contact was detected on the onscreen keyboard.

In accordance with some embodiments, entering the text into the content region includes entering a character that corresponds to character key at a location at which liftoff of the contact was detected on the onscreen keyboard.

In accordance with some embodiments, the text-selection criteria include a criterion that is met when the contact does not move more than a threshold distance before detecting an increase in the characteristic intensity of the contact above the text-selection intensity threshold.

In accordance with some embodiments, the text-selection operation includes one of: moving a cursor within the content region or selecting text within the content region.

In accordance with some embodiments, the method further includes, in response to detecting that the text-selection criteria have been met, generating a tactile output that is indicative of an entry into a text selection mode of operation.

In accordance with some embodiments, the method further includes, in response to detecting that the text-selection criteria have been met, changing an appearance of the onscreen keyboard to indicate that the device is operating in

a text selection mode of operation, wherein changing the appearance of the onscreen keyboard includes obscuring an appearance of characters on keys of the onscreen keyboard.

In accordance with some embodiments, the method further includes, ending the text selection mode of operation and, in conjunction with the end of the text selection mode of operation, reversing the change in appearance of the onscreen keyboard to reveal the characters on the keys of the onscreen keyboard.

In accordance with some embodiments, the method further includes, when the touch input satisfies the text-selection criteria, detecting movement of the contact after the touch input has satisfied the text-selection criteria and moving a cursor in the content region in accordance with the movement of the contact detected after the touch input has satisfied the text-selection criteria.

In accordance with some embodiments, the method further includes, when the touch input satisfies the text-selection criteria, detecting a first subsequent change in the characteristic intensity of the contact followed by additional movement of the contact on the touch-sensitive display; and, in response to detecting the first subsequent change in the characteristic intensity of the contact: in accordance with a determination that the touch input satisfies selection-start criteria, wherein the selection-start criteria include a criterion that is met when the characteristic intensity of the contact increases above a selection-start intensity threshold, starting to select content in the content region at a location of a cursor in accordance with the additional movement of the contact; and in accordance with a determination that the touch input does not satisfy the selection-start criteria, moving the cursor in accordance with the additional movement of the contact without starting to select content in the content region.

In accordance with some embodiments, the method further includes, when the touch input satisfies selection-start criteria, after starting to select content in the content region, detecting liftoff of the contact from the touch-sensitive display and confirming the selection in response to detecting the liftoff of the contact.

In accordance with some embodiments, the method further includes, when the touch input satisfies selection-start criteria, after starting to select content in the content region, and while continuing to detect the contact on the touch-sensitive display, detecting a second subsequent change in intensity of the contact; in response to detecting the second subsequent change in the characteristic intensity of the contact: in accordance with a determination that the second subsequent change in the characteristic intensity of the contact satisfies selection-cancellation criteria, wherein the selection-cancellation criteria include a criterion that is met when the characteristic intensity of the contact increases above a selection-cancellation intensity threshold cancelling the selection; and in accordance with a determination that the second subsequent change in the characteristic intensity of the contact does not satisfy the selection-cancellation criteria, maintaining the selection.

In accordance with some embodiments, the selection-cancellation criteria include a criterion that is met when the contact moves no more than a threshold distance within a threshold amount of time before the characteristic intensity of the contact increases above the selection-cancellation intensity threshold.

In accordance with some embodiments, the method further includes, in response to detecting that the selection-

cancellation criteria have been met, generating a tactile output that is indicative of an exit from the text selection mode of operation.

In accordance with some embodiments, the method further includes, after canceling the selection, and while continuing to detect the contact on the touch-sensitive display, detecting a third subsequent change in the characteristic intensity of the contact; and, in response to detecting the third subsequent change in the characteristic intensity of the contact: in accordance with a determination that the touch input satisfies the selection-start criteria, starting to select content in the content region at a location of the cursor; and in accordance with a determination that the touch input does not satisfy the selection-start criteria, forgoing starting to select content in the content region.

In accordance with some embodiments, starting to select content in response to detecting the third subsequent change in the characteristic intensity of the contact includes selecting a respective word at the location of the cursor.

In accordance with some embodiments, the selected respective word is a first word, and the method further includes, while the first word is selected, detecting first subsequent movement of the contact; and in response to detecting the first subsequent movement of the contact while the first word is selected: in accordance with a determination that the touch input meets selection-movement criteria which includes a movement criterion that is met when the contact moves more than a respective threshold amount, canceling selection of the first word; and selecting a second word that is adjacent to the first word in a first direction in accordance with the first subsequent movement of the contact, such that the selected respective word is the second word.

In accordance with some embodiments, the method further includes, while the respective word is selected, detecting first subsequent movement of the contact; and in response to detecting the first subsequent movement of the contact while the respective word is selected: in accordance with a determination that the touch input meets selection-expansion criteria which includes a movement criterion that is met when the contact moves more than a respective threshold amount, expanding the selection to include a word that is adjacent to the respective word in a first direction in accordance with the first subsequent movement of the contact.

In accordance with some embodiments, the method further includes, while the respective word is selected, detecting a fourth subsequent change in the characteristic intensity of the contact above a respective intensity threshold; and, in response to detecting the fourth subsequent change in the characteristic intensity of the contact, in accordance with a determination that the touch input meets the selection-cancellation criteria, which includes a criterion that is met when the amount of time between when the third subsequent change in the characteristic intensity of the contact is detected and when the fourth subsequent change in the characteristic intensity of the contact is detected is greater than the delay threshold, cancelling selection of the respective word.

In accordance with some embodiments, the method further includes, while the respective word is selected, detecting a fourth subsequent change in the characteristic intensity of the contact above a respective intensity threshold; and, in response to detecting the fourth subsequent change in the characteristic intensity of the contact, in accordance with a determination that the touch input meets sentence-selection criteria which include a movement criterion that is met when

the contact moves less than a threshold amount within a threshold time period before the fourth subsequent change in intensity of the contact was detected and a time criterion that is met when an amount of time between when the third subsequent change in the characteristic intensity of the contact is detected and when the fourth subsequent change in the characteristic intensity of the contact is detected is less than a delay threshold, expanding the selection to include the respective sentence that contains the respective word.

In accordance with some embodiments, the method further includes, while the respective sentence is selected, detecting second subsequent movement of the contact; and in response to detecting the second subsequent movement of the contact while the respective sentence is selected: in accordance with a determination that the touch input meets selection-expansion criteria which includes a movement criterion that is met when the contact moves more than a respective threshold amount, expanding the selection to include a sentence that is adjacent to the respective sentence in a first direction in accordance with the second subsequent movement of the contact.

In accordance with some embodiments, the respective sentence is selected in response to the fourth subsequent change in the characteristic intensity of the contact and the method further includes, while the respective sentence is selected: detecting a fifth subsequent change in the characteristic intensity of the contact above the respective intensity threshold; and, in response to detecting the fifth subsequent change in the characteristic intensity of the contact, in accordance with a determination that the touch input meets the selection-cancellation criteria, which includes a criterion that is met when the amount of time between when the fourth subsequent change in the characteristic intensity of the contact is detected and when the fifth subsequent change in the characteristic intensity of the contact is detected is greater than the delay threshold, cancelling selection of the respective sentence.

In accordance with some embodiments, the method further includes, in response to detecting the fifth subsequent change in the characteristic intensity of the contact, in accordance with a determination that the touch input meets paragraph-selection criteria which include a movement criterion that is met when the contact moves less than the threshold amount within the threshold time period before the fifth subsequent change in intensity of the contact was detected and a time criterion that is met when an amount of time between when the fourth subsequent change in the characteristic intensity of the contact is detected and when the fifth subsequent change in the characteristic intensity of the contact is detected is less than the delay threshold, expanding the selection to include the respective paragraph that contains the respective sentence.

In accordance with some embodiments, the method further includes, while the respective paragraph is selected, detecting third subsequent movement of the contact; and in response to detecting the third subsequent movement of the contact while the respective paragraph is selected: in accordance with a determination that the touch input meets selection-expansion criteria which includes a movement criterion that is met when the contact moves more than a respective threshold amount, expanding the selection to include a paragraph that is adjacent to the respective paragraph in a first direction in accordance with the third subsequent movement of the contact.

In accordance with some embodiments, the respective paragraph is selected in response to the fifth subsequent change in the characteristic intensity of the contact and the

method further includes, while the respective paragraph is selected: detecting a sixth subsequent change in the characteristic intensity of the contact above the respective intensity threshold; and, in response to detecting the sixth subsequent change in the characteristic intensity of the contact, in accordance with a determination that the touch input meets selection-cancellation criteria, which includes a criterion that is met when the amount of time between when the fifth subsequent change in the characteristic intensity of the contact is detected and when the sixth subsequent change in the characteristic intensity of the contact is detected is greater than the delay threshold, cancelling selection of the respective paragraph.

In accordance with some embodiments, the method further includes, in response to detecting the sixth subsequent change in the characteristic intensity of the contact, in accordance with a determination that the touch input meets document selection criteria which include a movement criterion that is met when the contact moves less than the threshold amount within the threshold time period before the sixth subsequent change in intensity of the contact was detected and a time criterion that is met when an amount of time between when the fifth subsequent change in the characteristic intensity of the contact is detected and when the sixth subsequent change in the characteristic intensity of the contact is detected is less than the delay threshold, expanding the selection to include the respective document that contains the respective paragraph.

In accordance with some embodiments, a method of content manipulation is performed at a portable multifunction device including one or more processors, memory, and a touch screen display. The method includes: displaying content of an electronic document and a cursor within the content on the touch screen display; displaying, on the touch screen display, a soft keyboard having multiple keys each having a respective alphanumeric character of a plurality of alphanumeric characters; detecting two substantially simultaneous touch inputs on the soft keyboard; and in response to detecting the two substantially simultaneous touch inputs on the soft keyboard, changing the appearance of the soft keyboard to a changed appearance.

In accordance with some embodiments, the method of content manipulation further includes: detecting, without breaking contact with the touch screen display following the two substantially simultaneous touch inputs, a sliding gesture from a first location of the two substantially simultaneous touch inputs on the soft keyboard to a second location on the content; and in response to detecting the sliding gesture, maintaining the changed appearance of the soft keyboard.

In accordance with some embodiments, changing the appearance of the soft keyboard includes: removing the plurality of alphanumeric characters from the multiple keys, or changing one or more of: color, hue, saturation, brightness, or contrast of the soft keyboard based on the content of the electronic document.

In accordance with some embodiments, the method of content manipulation further includes: detecting a continuous movement of the two substantially simultaneous touch inputs from a first location on the soft keyboard to a second location anywhere on the touch screen display without breaking contact with the touch screen display; and expanding the selected content to include additional content beyond the portion in a direction towards the second location in response to detecting the continuous movement.

In accordance with some embodiments, expanding the selected content to include additional content beyond the portion in a direction towards the second location includes:

displaying a start-point object and an end-point object at respective ends of the selection; and moving one of the start-point object or the end-point object in accordance with the location of the first location and the second location. For example, the selection is expanded by moving a start-point object or an end-point object like dragging a cursor. The initial direction of the continuous movement of the two substantially simultaneous touch inputs defines what part of the selection is expanded. For example, a left/up movement of the two substantially simultaneous touch inputs drags a lollipop shaped start-point object and expands the selection backwards, while a right/down movement of the two substantially simultaneous touch inputs drags an upside down lollipop shaped end-point object and expands the selection forward.

In accordance with some embodiments, expanding the selected content to include additional content beyond the portion in a direction towards the second location includes: in accordance with a determination that the speed of the continuous movement exceeds a predetermined threshold, expanding the selection one word at a time.

In accordance with some embodiments, the method of content manipulation further includes: after detecting the two substantially simultaneous touch inputs, detecting a lift-off followed by an additional two substantially simultaneous touch inputs followed by a sliding gesture of the additional two substantially simultaneous touch inputs across the touch screen display to additional locations; dismissing the selected content; selecting a word as the selected content closest to the cursor; and expanding the selected content to include additional content beyond the selected content in a direction towards the additional locations.

In accordance with some embodiments, the method of content manipulation further includes: detecting an additional two substantially simultaneous touch inputs on the soft keyboard; and in response to detecting the additional two substantially simultaneous touch inputs on the soft keyboard: in accordance with a determination that the selected content is a word, expanding the selected content to include a sentence containing the word.

In accordance with some embodiments, the method of content manipulation further includes: in accordance with a determination that the selected content is more than a word, displaying the cursor at the beginning of the selected content and dismissing the selected content.

In accordance with some embodiments, the method of content manipulation further includes: detecting additional two substantially simultaneous touch inputs; in response to detecting the additional two substantially simultaneous touch inputs, expanding the selected content to a sentence containing the portion; and displaying an indication of the selected content.

In accordance with some embodiments, expanding the selected content to a sentence containing the portion includes expanding the selected content to the sentence containing the portion in accordance with a determination that the duration between the two substantially simultaneous touch inputs and the additional two substantially simultaneous touch inputs is less than a predetermined threshold (e.g., 0.66 seconds).

In accordance with some embodiments, the method of content manipulation further includes: detecting a further two substantially simultaneous touch inputs; in response to detecting the further two substantially simultaneous touch

inputs, expanding the selected content to a paragraph containing the portion; and displaying an indication of the selected content.

In accordance with some embodiments, expanding the selected content to a paragraph containing the portion includes: expanding the selected content to the paragraph containing the portion in accordance with a determination that the duration between the two substantially simultaneous touch inputs and the further two substantially simultaneous touch inputs is less than a predetermined threshold (e.g., 0.66 seconds).

In accordance with some embodiments, there is provided an electronic device that includes a display, a touch-sensitive surface, one or more processors, memory, and one or more programs; the one or more programs are stored in the memory and configured to be executed by the one or more processors, where the one or more programs include instructions for performing any of the methods described herein.

In accordance with some embodiments there is provided a graphical user interface on an electronic device with a display, a touch-sensitive surface, a memory, and one or more processors to execute one or more programs stored in the memory. The graphical user interface includes one or more of the elements displayed in any of the methods described above, which are updated in response to inputs, as described in any of the methods described herein.

In accordance with some embodiments, there is provided a non-transitory computer readable storage medium that has stored therein instructions which when executed by an electronic device with a display, a touch-sensitive surface, cause the device to perform the any of the methods described herein.

In accordance with some embodiments, an electronic device includes a display unit configured to display content of an electronic document and a cursor within the electronic document; a touch-sensitive surface unit configured to receive user contacts; and a processing unit coupled to the display unit and the touch-sensitive surface unit. The processing unit is configured to: detect two substantially simultaneous touch inputs anywhere on the touch screen display; and in response to detecting the two substantially simultaneous touch inputs: select a portion of the content in the document closest to the cursor; and display the portion of the content as selected content.

In accordance with some embodiments, an electronic device includes a display unit configured to display content of an electronic document and a cursor at a current location within the content; a touch-sensitive surface unit configured to receive user contacts; and a processing unit coupled to the display unit and the touch-sensitive surface unit. The processing unit is configured to: detect two substantially simultaneous touch inputs at a first region on the touch screen display; upon determining that the two substantially simultaneous touch inputs remain in contact with the touch screen display, detect a continuous touch gesture from a location of the two substantially simultaneous touch inputs across the touch screen display from the first region to a second region; and in response to detecting the continuous touch gesture: move the cursor from the current location to a new location in a direction of the continuous touch gesture.

In accordance with some embodiments, an electronic device includes a display unit configured to display text and a cursor at a line within the text; a touch-sensitive surface unit configured to receive user contacts; and a processing unit coupled to the display unit and the touch-sensitive surface unit. The processing unit is configured to: detect a two-finger swipe gesture on the touch screen display in a

direction at least partially parallel to the line and towards an edge of the touch screen display; and in response to detecting the two-finger swipe gesture: move the cursor to a distal point of the text.

In accordance with some embodiments, an electronic device includes a display unit configured to display content of an electronic document and a cursor within the electronic document; a touch-sensitive surface unit configured to receive user contacts; and a processing unit coupled to the display unit and the touch-sensitive surface unit. The processing unit is configured to: detect a touch input on the touch screen display, wherein the touch input is located on a word within the content; and in response to detecting the touch input: select the word; and display a command display area adjacent to the selected word, wherein the second command display area includes an icon for cutting the selected word, an icon for copying the selected word, and an icon for pasting a previously selected content.

In accordance with some embodiments, an electronic device includes a display unit configured to display content of an electronic document and a selection of the content within the electronic document; a touch-sensitive surface unit configured to receive user contacts; and a processing unit coupled to the display unit and the touch-sensitive surface unit. The processing unit is configured to: detect a single touch input on the touch screen display at a location over the selection; in response to detecting the single touch input at the location, display a set of options related to the selection; determine if the single touch input remains at the location for a predetermined amount of time followed by a continuous touch gesture away from the location on the touch screen display; and in response to detecting the single touch input remaining at the location for the predetermined amount of time followed by the continuous touch gesture away from the location, move the selection to a different location in a direction of the continuous touch gesture.

In accordance with some embodiments, an electronic device includes a display unit configured to display content of an electronic document and a selection of the content within the electronic document; a touch-sensitive surface unit configured to receive user contacts; and a processing unit coupled to the display unit and the touch-sensitive surface unit. The processing unit is configured to: detect three substantially simultaneous touch inputs at locations anywhere on the touch screen display; determine if the three substantially simultaneous touch inputs is followed by three continuous touch gestures away from the locations on the touch screen display; and in response to detecting the three continuous touch gestures, move the selection to a different location in a direction of the continuous touch gestures.

In accordance with some embodiments, an electronic device includes a display unit configured to display content of an electronic document, the content includes at least one line of text comprising at least two words; a touch-sensitive surface unit configured to receive user contacts; and a processing unit coupled to the display unit and the touch-sensitive surface unit. The processing unit is configured to: detect a touch input on the content; and in response to detecting the touch input: determine a distance of the touch input to a closest space between the two words within the electronic document; and in accordance with a determination that the distance is greater than a predetermined threshold distance, select a word within the electronic document closest to the touch input and display an indication of the selection.

In accordance with some embodiments, an electronic device includes a display unit configured to display content

of an electronic document and a soft keyboard; a touch-sensitive surface unit configured to receive user contacts; and a processing unit coupled to the display unit and the touch-sensitive surface unit. The processing unit is configured to: detect two substantially simultaneous touch inputs on the soft keyboard; and in response to detecting the two substantially simultaneous touch inputs on the soft keyboard, display a blurred soft keyboard.

In accordance with some embodiments, an electronic device includes a touch-sensitive surface unit configured to receive user touch inputs, a display unit configured to concurrently display an onscreen keyboard and a content presentation region on the touch-sensitive display unit, wherein the content presentation region displays text input received from the onscreen keyboard; a touch-sensitive surface unit configured to receive user touch inputs; and a processing unit coupled to the display unit and the touch-sensitive surface unit. The processing unit is configured to: detect a touch input on the onscreen keyboard displayed on the touch-sensitive display; in response to detecting the touch input on the onscreen keyboard displayed on the touch-sensitive display, determine whether the touch input satisfies one or more criteria for entering a text selection mode; and in accordance with a determination that the touch input satisfies the one or more criteria for entering the text selection mode: concurrently display, in the content presentation region, a first cursor at a first location and a second cursor at a second location that is different from the first location.

In accordance with some embodiments, an electronic device includes a touch-sensitive surface unit configured to receive user touch inputs; a display unit configured to, while a contact is detected on the touch-sensitive surface unit, concurrently display on the display unit content and a text selection indicator at a first location within the content; one or more sensors to detect intensity of contacts with the touch-sensitive surface unit; and a processing unit coupled to the display unit and the touch-sensitive surface unit. The processing unit is configured to: detect a first press input by the contact followed by movement of the contact across the touch-sensitive surface unit that corresponds to movement of at least a portion of the text selection indicator from the first location to a second location on the display unit; in response to detecting the first press input by the contact followed by movement of the contact across the touch-sensitive surface unit, select content between the first location and the second location; while the content between the first location and the second location is selected, detect a second press input by the contact on the touch-sensitive surface unit; in response to detecting the second press input by the contact on the touch-sensitive surface unit, perform a text selection operation, associated with the content between the first location and the second location, in accordance with the second press input, wherein the contact in the first press input, the movement across the touch-sensitive surface unit, and the second press input is a single continuous contact with the touch-sensitive surface unit.

In accordance with some embodiments, an electronic device includes a touch-sensitive surface unit configured to receive user touch inputs; a display unit configured to concurrently display an onscreen keyboard and a content presentation region on the touch-sensitive display unit, wherein the content presentation region displays text input received from the onscreen keyboard; one or more sensors to detect intensity of contacts with the touch-sensitive surface unit; and a processing unit coupled to the display unit and the touch-sensitive surface unit. The processing unit is

configured to: detect a touch input on the onscreen keyboard displayed on the touch-sensitive display unit, wherein detecting the touch input includes detecting movement of a contact and liftoff of the contact; in response to detecting the touch input on the onscreen keyboard displayed on the touch-sensitive display: in accordance with a determination that the touch input satisfies text-selection criteria, wherein the text-selection criteria include a criterion that is met when a characteristic intensity of the contact increases above a text-selection intensity threshold, perform a text selection operation based on the movement of the contact; and in accordance with a determination that the touch input satisfies text-entry criteria, wherein the text-entry criteria include a criterion that is met when the characteristic intensity of the contact does not increase above the text-selection intensity threshold, enter text into the content presentation region based on the touch input.

In accordance with some embodiments, there is provided an electronic device that includes a display unit configured to display content of an electronic document and a cursor within the electronic document; a touch-sensitive surface unit configured to receive user contacts; and a processing unit coupled to the display unit and the touch-sensitive surface unit. The processing unit is configured to: display, on the touch-sensitive surface display unit, a soft keyboard having multiple keys each having a respective alphanumeric character of a plurality of alphanumeric characters; detect two substantially simultaneous touch inputs on the soft keyboard; and in response to detecting the two substantially simultaneous touch inputs on the soft keyboard, change the appearance of the soft keyboard to a changed appearance.

Thus, electronic devices with displays, touch-sensitive surfaces are provided with faster, more efficient methods and interfaces for cursor manipulation, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for cursor manipulation.

#### BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding of the various described embodiments, reference should be made to the Description of Embodiments below, in conjunction with the following drawings in which like reference numerals refer to corresponding parts throughout the figures.

FIG. 1A is a block diagram illustrating a portable multi-function device with a touch-sensitive display in accordance with some embodiments.

FIG. 1B is a block diagram illustrating exemplary components for event handling, in accordance with some embodiments.

FIG. 2A is a schematic diagram of a portable multifunction device having a touch screen, in accordance with some embodiments.

FIG. 2B illustrates an exemplary user interface for a multifunction device with a touch-sensitive surface that is separate from the display in accordance with some embodiments.

FIGS. 2C-2E illustrate exemplary dynamic intensity thresholds in accordance with some embodiments.

FIG. 3 is a schematic diagram of a user interface for a menu of applications on a portable multifunction device, in accordance with some embodiments.

FIG. 4A is a flow chart illustrating a method of cursor manipulation with two substantially simultaneous touch inputs, in accordance with some embodiments.

FIG. 4B is a flow chart illustrating a method of cursor manipulation with a single touch input, in accordance with some embodiments.

FIG. 4C is a flow chart illustrating a method of cursor manipulation with three substantially simultaneous touch inputs (e.g., three finger touch input), in accordance with some embodiments.

FIGS. 5A-5AX illustrate exemplary user interfaces for cursor manipulation, in accordance with some embodiments.

FIGS. 6A-6J illustrate exemplary user interfaces for cursor manipulation with a single touch input, in accordance with some embodiments.

FIGS. 7A-7C illustrate exemplary keyboard appearance changes in response to two substantially simultaneous touch inputs, in accordance with some embodiments.

FIG. 8 is a functional block diagram of an electronic device in accordance with some embodiments.

FIGS. 9A-9AD illustrate exemplary user interfaces for manipulating a cursor and selecting content in accordance with some embodiments.

FIGS. 10A-10G are flow diagrams illustrating a method of manipulating a cursor in accordance with some embodiments.

FIGS. 11A-11F are flow diagrams illustrating a method of selecting content in accordance with some embodiments.

FIG. 12 is a functional block diagram of an electronic device in accordance with some embodiments.

FIGS. 13A-13Q illustrate exemplary user interfaces for manipulating a cursor and selecting content in accordance with some embodiments.

FIGS. 14A-14H are flow diagrams illustrating a method of manipulating a cursor and selecting content in accordance with some embodiments.

FIG. 15 is a functional block diagram of an electronic device in accordance with some embodiments.

#### DESCRIPTION OF EMBODIMENTS

Described below are devices and methods that allow a user to efficiently manipulate a cursor in an electronic document. The methods are particularly useful on portable devices with small displays, including handheld or pocket-sized devices (e.g., smartphones). When using conventional portable devices, a user may find it difficult to precisely place her finger (or make contact) at the cursor location on the touch screen display, as the cursor is often small, hidden under the user's finger, and/or disposed between text or graphics. As such, users often need to lift their finger and reposition it multiple times until the cursor is placed at the correct location. This conventional process is time consuming, inefficient, and alienates users. The methods described herein allow a user to manipulate and place a cursor at a desired location within an electronic document, as well as perform certain editing functions, such as text selection or moving text. In some embodiments, this cursor (or selected text) manipulation can be controlled from any part of the touch-sensitive surface, not just the location of the cursor. These methods greatly reduce the number of steps that a user need perform to navigate and edit a document, thereby increasing efficiency and ease of use when performing these tasks.

Below, FIGS. 1A-1B, 2A-2B, and 3 provide a description of exemplary devices. FIGS. 5A-5AR illustrate exemplary user interfaces for cursor manipulation when editing an electronic document. FIGS. 4A-4C are flow charts illustrating methods of cursor manipulation. The user interfaces in

FIGS. 5A-5AX, 6A-6J, 7A-7C, 9A-9AD, and 13A-13Q are used to illustrate the processes in FIGS. 4A-4C, 10A-10G, 11A-11F, 14A-14H and the method recited in the claims.

#### Exemplary Devices

Reference will now be made in detail to embodiments, examples of which are illustrated in the accompanying drawings. In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of the present invention. However, it will be apparent to one of ordinary skill in the art that the present invention may be practiced without these specific details. In other instances, well-known methods, procedures, components, circuits, and networks have not been described in detail so as not to unnecessarily obscure aspects of the embodiments.

It will also be understood that, although the terms first, second, etc. may be used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. For example, a first contact could be termed a second contact, and, similarly, a second contact could be termed a first contact, without departing from the scope of the present invention. The first contact and the second contact are both contacts, but they are not the same contact.

The terminology used in the description of the invention herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used in the description of the invention and the appended claims, the singular forms "a", "an" and "the" are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will also be understood that the term "and/or" as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will be further understood that the terms "comprises" and/or "comprising," when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

As used herein, the term "if" may be construed to mean "when" or "upon" or "in response to determining" or "in response to detecting," depending on the context. Similarly, the phrase "if it is determined" or "if [a stated condition or event] is detected" may be construed to mean "upon determining" or "in response to determining" or "upon detecting [the stated condition or event]" or "in response to detecting [the stated condition or event]," depending on the context.

Embodiments of computing devices, user interfaces for such devices, and associated processes for using such devices are described. In some embodiments, the computing device is a portable communications device such as a mobile telephone that also contains other functions, such as PDA and/or music player functions. Exemplary embodiments of portable multifunction devices include, without limitation, the IPHONE, IPAD, and IPOD TOUCH devices from Apple Computer, Inc. of Cupertino, Calif.

In the discussion that follows, a computing device that includes a touch-sensitive display is described. It should be understood, however, that the computing device may include one or more other physical user-interface devices, such as a separate display, physical keyboard, a mouse, and/or a joystick.

The device supports a variety of applications, such as one or more of the following: a note taking application, a

drawing application, a presentation application, a word processing application, a website creation application, a disk authoring application, a spreadsheet application, a gaming application, a telephone application, a video-conferencing application, an e-mail application, an instant messaging application, a fitness application, a photo management application, a digital camera application, a digital video camera application, a web browsing application, a digital music player application, a digital video player application, and/or a home automation application.

The various applications that may be executed on the device may use at least one common physical user-interface device, such as the touch-sensitive surface. One or more functions of the touch-sensitive surface as well as corresponding information displayed on the device may be adjusted and/or varied from one application to the next and/or within a respective application. In this way, a common physical architecture (such as the touch-sensitive surface) of the device may support the variety of applications with user interfaces that are intuitive and transparent.

The user interfaces may include one or more soft keyboard embodiments. The soft keyboard embodiments may include standard (QWERTY) and/or non-standard configurations of symbols on the displayed icons of the keyboard, such as those described in U.S. patent application Ser. No. 11/459,606, "Keyboards For Portable Electronic Devices," filed Jul. 24, 2006, and Ser. No. 11/459,615, "Touch Screen Keyboards For Portable Electronic Devices," filed Jul. 24, 2006, the contents of which are hereby incorporated by reference in their entirety. The keyboard embodiments may include a reduced number of icons (or soft keys) relative to the number of keys in existing physical keyboards, such as that for a typewriter. This may make it easier for users to select one or more icons in the keyboard, and thus, one or more corresponding symbols. The keyboard embodiments may be adaptive. For example, displayed icons may be modified in accordance with user actions, such as selecting one or more icons and/or one or more corresponding symbols. One or more applications on the device may utilize common and/or different keyboard embodiments. Thus, the keyboard embodiment used may be tailored to at least some of the applications. In some embodiments, one or more keyboard embodiments may be tailored to a respective user. For example, one or more keyboard embodiments may be tailored to a respective user based on a word usage history (lexicography, slang, individual usage) of the respective user. Some of the keyboard embodiments may be adjusted to reduce a probability of a user error when selecting one or more icons, and thus one or more symbols, when using the soft keyboard embodiments.

Attention is now directed toward embodiments of portable devices with touch-sensitive displays. FIG. 1A is a block diagram illustrating portable multifunction device 100 with touch-sensitive display system 112 in accordance with some embodiments. Touch-sensitive display system 112 is sometimes called a "touch screen" for convenience, and is sometimes simply called a touch-sensitive display. Device 100 includes memory 102 (which optionally includes one or more computer readable storage mediums), memory controller 122, one or more processing units (CPUs) 120, peripherals interface 118, RF circuitry 108, audio circuitry 110, speaker 111, microphone 113, input/output (I/O) subsystem 106, other input or control devices 116, and external port 124. Device 100 optionally includes one or more optical sensors 164. Device 100 optionally includes one or more intensity sensors 165 for detecting intensity of contacts on device 100 (e.g., a touch-sensitive surface such as touch-

sensitive display system **112** of device **100**). Device **100** optionally includes one or more tactile output generators **167** for generating tactile outputs on device **100** (e.g., generating tactile outputs on a touch-sensitive surface such as touch-sensitive display system **112** of device **100** or touchpad **355** of device **300**). These components optionally communicate over one or more communication buses or signal lines **103**.

As used in the specification and claims, the term “tactile output” refers to physical displacement of a device relative to a previous position of the device, physical displacement of a component (e.g., a touch-sensitive surface) of a device relative to another component (e.g., housing) of the device, or displacement of the component relative to a center of mass of the device that will be detected by a user with the user’s sense of touch. For example, in situations where the device or the component of the device is in contact with a surface of a user that is sensitive to touch (e.g., a finger, palm, or other part of a user’s hand), the tactile output generated by the physical displacement will be interpreted by the user as a tactile sensation corresponding to a perceived change in physical characteristics of the device or the component of the device. For example, movement of a touch-sensitive surface (e.g., a touch-sensitive display or trackpad) is, optionally, interpreted by the user as a “down click” or “up click” of a physical actuator button. In some cases, a user will feel a tactile sensation such as an “down click” or “up click” even when there is no movement of a physical actuator button associated with the touch-sensitive surface that is physically pressed (e.g., displaced) by the user’s movements. As another example, movement of the touch-sensitive surface is, optionally, interpreted or sensed by the user as “roughness” of the touch-sensitive surface, even when there is no change in smoothness of the touch-sensitive surface. While such interpretations of touch by a user will be subject to the individualized sensory perceptions of the user, there are many sensory perceptions of touch that are common to a large majority of users. Thus, when a tactile output is described as corresponding to a particular sensory perception of a user (e.g., an “up click,” a “down click,” “roughness”), unless otherwise stated, the generated tactile output corresponds to physical displacement of the device or a component thereof that will generate the described sensory perception for a typical (or average) user.

It should be appreciated that device **100** is only one example of a portable multifunction device, and that device **100** optionally has more or fewer components than shown, optionally combines two or more components, or optionally has a different configuration or arrangement of the components. The various components shown in FIG. **1A** are implemented in hardware, software, firmware, or a combination thereof, including one or more signal processing and/or application specific integrated circuits.

Memory **102** optionally includes high-speed random access memory and optionally also includes non-volatile memory, such as one or more magnetic disk storage devices, flash memory devices, or other non-volatile solid-state memory devices. Access to memory **102** by other components of device **100**, such as CPU(s) **120** and the peripherals interface **118**, is, optionally, controlled by memory controller **122**.

Peripherals interface **118** can be used to couple input and output peripherals of the device to CPU(s) **120** and memory **102**. The one or more processors **120** run or execute various software programs and/or sets of instructions stored in memory **102** to perform various functions for device **100** and to process data.

In some embodiments, peripherals interface **118**, CPU(s) **120**, and memory controller **122** are, optionally, implemented on a single chip, such as chip **104**. In some other embodiments, they are, optionally, implemented on separate chips.

RF (radio frequency) circuitry **108** receives and sends RF signals, also called electromagnetic signals. RF circuitry **108** converts electrical signals to/from electromagnetic signals and communicates with communications networks and other communications devices via the electromagnetic signals. RF circuitry **108** optionally includes well-known circuitry for performing these functions, including but not limited to an antenna system, an RF transceiver, one or more amplifiers, a tuner, one or more oscillators, a digital signal processor, a CODEC chipset, a subscriber identity module (SIM) card, memory, and so forth. RF circuitry **108** optionally communicates with networks, such as the Internet, also referred to as the World Wide Web (WWW), an intranet and/or a wireless network, such as a cellular telephone network, a wireless local area network (LAN) and/or a metropolitan area network (MAN), and other devices by wireless communication. The wireless communication optionally uses any of a plurality of communications standards, protocols and technologies, including but not limited to Global System for Mobile Communications (GSM), Enhanced Data GSM Environment (EDGE), high-speed downlink packet access (HSDPA), high-speed uplink packet access (HSUPA), Evolution, Data-Only (EV-DO), HSPA, HSPA+, Dual-Cell HSPA (DC-HSPA), long term evolution (LTE), near field communication (NFC), wideband code division multiple access (W-CDMA), code division multiple access (CDMA), time division multiple access (TDMA), Bluetooth, Wireless Fidelity (Wi-Fi) (e.g., IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g and/or IEEE 802.11n), voice over Internet Protocol (VoIP), Wi-MAX, a protocol for e-mail (e.g., Internet message access protocol (IMAP) and/or post office protocol (POP)), instant messaging (e.g., extensible messaging and presence protocol (XMPP), Session Initiation Protocol for Instant Messaging and Presence Leveraging Extensions (SIMPLE), Instant Messaging and Presence Service (IMPS)), and/or Short Message Service (SMS), or any other suitable communication protocol, including communication protocols not yet developed as of the filing date of this document.

Audio circuitry **110**, speaker **111**, and microphone **113** provide an audio interface between a user and device **100**. Audio circuitry **110** receives audio data from peripherals interface **118**, converts the audio data to an electrical signal, and transmits the electrical signal to speaker **111**. Speaker **111** converts the electrical signal to human-audible sound waves. Audio circuitry **110** also receives electrical signals converted by microphone **113** from sound waves. Audio circuitry **110** converts the electrical signal to audio data and transmits the audio data to peripherals interface **118** for processing. Audio data is, optionally, retrieved from and/or transmitted to memory **102** and/or RF circuitry **108** by peripherals interface **118**. In some embodiments, audio circuitry **110** also includes a headset jack (e.g., **212**, FIG. **2A**). The headset jack provides an interface between audio circuitry **110** and removable audio input/output peripherals, such as output-only headphones or a headset with both output (e.g., a headphone for one or both ears) and input (e.g., a microphone).

I/O subsystem **106** couples input/output peripherals on device **100**, such as touch-sensitive display system **112** and other input or control devices **116**, with peripherals interface **118**. I/O subsystem **106** optionally includes display control-

ler **156**, optical sensor controller **158**, intensity sensor controller **159**, haptic feedback controller **161**, and one or more input controllers **160** for other input or control devices. The one or more input controllers **160** receive/send electrical signals from/to other input or control devices **116**. The other input or control devices **116** optionally include physical buttons (e.g., push buttons, rocker buttons, etc.), dials, slider switches, joysticks, click wheels, and so forth. In some alternate embodiments, input controller(s) **160** are, optionally, coupled with any (or none) of the following: a keyboard, infrared port, USB port, stylus, and/or a pointer device such as a mouse. The one or more buttons (e.g., **208**, FIG. 2A) optionally include an up/down button for volume control of speaker **111** and/or microphone **113**. The one or more buttons optionally include a push button (e.g., **206**, FIG. 2A).

Touch-sensitive display system **112** provides an input interface and an output interface between the device and a user. Display controller **156** receives and/or sends electrical signals from/to touch-sensitive display system **112**. Touch-sensitive display system **112** displays visual output to the user. The visual output optionally includes graphics, text, icons, video, and any combination thereof (collectively termed “graphics”). In some embodiments, some or all of the visual output corresponds to user-interface objects. As used herein, the term “affordance” refers to a user-interactive graphical user interface object (e.g., a graphical user interface object that is configured to respond to inputs directed toward the graphical user interface object). Examples of user-interactive graphical user interface objects include, without limitation, a button, slider, icon, selectable menu item, switch, hyperlink, or other user interface control.

Touch-sensitive display system **112** has a touch-sensitive surface, sensor or set of sensors that accepts input from the user based on haptic and/or tactile contact. Touch-sensitive display system **112** and display controller **156** (along with any associated modules and/or sets of instructions in memory **102**) detect contact (and any movement or breaking of the contact) on touch-sensitive display system **112** and converts the detected contact into interaction with user-interface objects (e.g., one or more soft keys, icons, web pages or images) that are displayed on touch-sensitive display system **112**. In an exemplary embodiment, a point of contact between touch-sensitive display system **112** and the user corresponds to a finger of the user or a stylus.

Touch-sensitive display system **112** optionally uses LCD (liquid crystal display) technology, LPD (light emitting polymer display) technology, or LED (light emitting diode) technology, although other display technologies are used in other embodiments. Touch-sensitive display system **112** and display controller **156** optionally detect contact and any movement or breaking thereof using any of a plurality of touch sensing technologies now known or later developed, including but not limited to capacitive, resistive, infrared, and surface acoustic wave technologies, as well as other proximity sensor arrays or other elements for determining one or more points of contact with touch-sensitive display system **112**. In an exemplary embodiment, projected mutual capacitance sensing technology is used, such as that found in the iPhone®, iPod Touch®, and iPad® from Apple Inc. of Cupertino, Calif.

Touch-sensitive display system **112** optionally has a video resolution in excess of 100 dpi. In some embodiments, the touch screen video resolution is in excess of 400 dpi (e.g., 500 dpi, 800 dpi, or greater). The user optionally makes contact with touch-sensitive display system **112** using any suitable object or appendage, such as a stylus, a finger, and

so forth. In some embodiments, the user interface is designed to work with finger-based contacts and gestures, which can be less precise than stylus-based input due to the larger area of contact of a finger on the touch screen. In some embodiments, the device translates the rough finger-based input into a precise pointer/cursor position or command for performing the actions desired by the user.

In some embodiments, in addition to the touch screen, device **100** optionally includes a touchpad (not shown) for activating or deactivating particular functions. In some embodiments, the touchpad is a touch-sensitive area of the device that, unlike the touch screen, does not display visual output. The touchpad is, optionally, a touch-sensitive surface that is separate from touch-sensitive display system **112** or an extension of the touch-sensitive surface formed by the touch screen.

Device **100** also includes power system **162** for powering the various components. Power system **162** optionally includes a power management system, one or more power sources (e.g., battery, alternating current (AC)), a recharging system, a power failure detection circuit, a power converter or inverter, a power status indicator (e.g., a light-emitting diode (LED)) and any other components associated with the generation, management and distribution of power in portable devices.

Device **100** optionally also includes one or more optical sensors **164**. FIG. 1A shows an optical sensor coupled with optical sensor controller **158** in I/O subsystem **106**. Optical sensor(s) **164** optionally include charge-coupled device (CCD) or complementary metal-oxide semiconductor (CMOS) phototransistors. Optical sensor(s) **164** receive light from the environment, projected through one or more lens, and converts the light to data representing an image. In conjunction with imaging module **143** (also called a camera module), optical sensor(s) **164** optionally capture still images and/or video. In some embodiments, an optical sensor is located on the back of device **100**, opposite touch-sensitive display system **112** on the front of the device, so that the touch screen is enabled for use as a viewfinder for still and/or video image acquisition. In some embodiments, another optical sensor is located on the front of the device so that the user’s image is obtained (e.g., for selfies, for videoconferencing while the user views the other video conference participants on the touch screen, etc.).

Device **100** optionally also includes one or more contact intensity sensors **165**. FIG. 1A shows a contact intensity sensor coupled with intensity sensor controller **159** in I/O subsystem **106**. Contact intensity sensor(s) **165** optionally include one or more piezoresistive strain gauges, capacitive force sensors, electric force sensors, piezoelectric force sensors, optical force sensors, capacitive touch-sensitive surfaces, or other intensity sensors (e.g., sensors used to measure the force (or pressure) of a contact on a touch-sensitive surface). Contact intensity sensor(s) **165** receive contact intensity information (e.g., pressure information or a proxy for pressure information) from the environment. In some embodiments, at least one contact intensity sensor is collocated with, or proximate to, a touch-sensitive surface (e.g., touch-sensitive display system **112**). In some embodiments, at least one contact intensity sensor is located on the back of device **100**, opposite touch-screen display system **112** which is located on the front of device **100**.

Device **100** optionally also includes one or more proximity sensors **166**. FIG. 1A shows proximity sensor **166** coupled with peripherals interface **118**. Alternately, proximity sensor **166** is coupled with input controller **160** in I/O subsystem **106**. In some embodiments, the proximity sensor

turns off and disables touch-sensitive display system 112 when the multifunction device is placed near the user's ear (e.g., when the user is making a phone call).

Device 100 optionally also includes one or more tactile output generators 167. FIG. 1A shows a tactile output generator coupled with haptic feedback controller 161 in I/O subsystem 106. Tactile output generator(s) 167 optionally include one or more electroacoustic devices such as speakers or other audio components and/or electromechanical devices that convert energy into linear motion such as a motor, solenoid, electroactive polymer, piezoelectric actuator, electrostatic actuator, or other tactile output generating component (e.g., a component that converts electrical signals into tactile outputs on the device). Tactile output generator(s) 167 receive tactile feedback generation instructions from haptic feedback module 133 and generates tactile outputs on device 100 that are capable of being sensed by a user of device 100. In some embodiments, at least one tactile output generator is collocated with, or proximate to, a touch-sensitive surface (e.g., touch-sensitive display system 112) and, optionally, generates a tactile output by moving the touch-sensitive surface vertically (e.g., in/out of a surface of device 100) or laterally (e.g., back and forth in the same plane as a surface of device 100). In some embodiments, at least one tactile output generator sensor is located on the back of device 100, opposite touch-sensitive display system 112, which is located on the front of device 100.

Device 100 optionally also includes one or more accelerometers 168. FIG. 1A shows accelerometer 168 coupled with peripherals interface 118. Alternately, accelerometer 168 is, optionally, coupled with an input controller 160 in I/O subsystem 106. In some embodiments, information is displayed on the touch-screen display in a portrait view or a landscape view based on an analysis of data received from the one or more accelerometers. Device 100 optionally includes, in addition to accelerometer(s) 168, a magnetometer (not shown) and a GPS (or GLONASS or other global navigation system) receiver (not shown) for obtaining information concerning the location and orientation (e.g., portrait or landscape) of device 100.

In some embodiments, the software components stored in memory 102 include operating system 126, communication module (or set of instructions) 128, contact/motion module (or set of instructions) 130, graphics module (or set of instructions) 132, haptic feedback module (or set of instructions) 133, text input module (or set of instructions) 134, Global Positioning System (GPS) module (or set of instructions) 135, and applications (or sets of instructions) 136. Furthermore, in some embodiments, memory 102 stores device/global internal state 157, as shown in FIGS. 1A and 3. Device/global internal state 157 includes one or more of: active application state, indicating which applications, if any, are currently active; display state, indicating what applications, views or other information occupy various regions of touch-sensitive display system 112; sensor state, including information obtained from the device's various sensors and other input or control devices 116; and location and/or positional information concerning the device's location and/or attitude.

Operating system 126 (e.g., iOS, Darwin, RTXC, LINUX, UNIX, OS X, WINDOWS, or an embedded operating system such as VxWorks) includes various software components and/or drivers for controlling and managing general system tasks (e.g., memory management, storage device control, power management, etc.) and facilitates communication between various hardware and software components.

Communication module 128 facilitates communication with other devices over one or more external ports 124 and also includes various software components for handling data received by RF circuitry 108 and/or external port 124. External port 124 (e.g., Universal Serial Bus (USB), FIREWIRE, etc.) is adapted for coupling directly to other devices or indirectly over a network (e.g., the Internet, wireless LAN, etc.). In some embodiments, the external port is a multi-pin (e.g., 30-pin) connector that is the same as, or similar to and/or compatible with the 30-pin connector used in some iPhone®, iPod Touch®, and iPad® devices from Apple Inc. of Cupertino, Calif. In some embodiments, the external port is a Lightning connector that is the same as, or similar to and/or compatible with the Lightning connector used in some iPhone®, iPod Touch®, and iPad® devices from Apple Inc. of Cupertino, Calif.

Contact/motion module 130 optionally detects contact with touch-sensitive display system 112 (in conjunction with display controller 156) and other touch-sensitive devices (e.g., a touchpad or physical click wheel). Contact/motion module 130 includes various software components for performing various operations related to detection of contact (e.g., by a finger or by a stylus), such as determining if contact has occurred (e.g., detecting a finger-down event), determining an intensity of the contact (e.g., the force or pressure of the contact or a substitute for the force or pressure of the contact), determining if there is movement of the contact and tracking the movement across the touch-sensitive surface (e.g., detecting one or more finger-dragging events), and determining if the contact has ceased (e.g., detecting a finger-up event or a break in contact). Contact/motion module 130 receives contact data from the touch-sensitive surface. Determining movement of the point of contact, which is represented by a series of contact data, optionally includes determining speed (magnitude), velocity (magnitude and direction), and/or an acceleration (a change in magnitude and/or direction) of the point of contact. These operations are, optionally, applied to single contacts (e.g., one finger contacts or stylus contacts) or to multiple simultaneous contacts (e.g., "multitouch"/multiple finger contacts). In some embodiments, contact/motion module 130 and display controller 156 detect contact on a touchpad.

Contact/motion module 130 optionally detects a gesture input by a user. Different gestures on the touch-sensitive surface have different contact patterns (e.g., different motions, timings, and/or intensities of detected contacts). Thus, a gesture is, optionally, detected by detecting a particular contact pattern. For example, detecting a finger tap gesture includes detecting a finger-down event followed by detecting a finger-up (lift off) event at the same position (or substantially the same position) as the finger-down event (e.g., at the position of an icon). As another example, detecting a finger swipe gesture on the touch-sensitive surface includes detecting a finger-down event followed by detecting one or more finger-dragging events, and subsequently followed by detecting a finger-up (lift off) event. Similarly, tap, swipe, drag, and other gestures are optionally detected for a stylus by detecting a particular contact pattern for the stylus.

Graphics module 132 includes various known software components for rendering and displaying graphics on touch-sensitive display system 112 or other display, including components for changing the visual impact (e.g., brightness, transparency, saturation, contrast or other visual property) of graphics that are displayed. As used herein, the term "graphics" includes any object that can be displayed to a user, including without limitation text, web pages, icons (such as

user-interface objects including soft keys), digital images, videos, animations and the like.

In some embodiments, graphics module **132** stores data representing graphics to be used. Each graphic is, optionally, assigned a corresponding code. Graphics module **132** receives, from applications etc., one or more codes specifying graphics to be displayed along with, if necessary, coordinate data and other graphic property data, and then generates screen image data to output to display controller **156**.

Haptic feedback module **133** includes various software components for generating instructions used by tactile output generator(s) **167** to produce tactile outputs at one or more locations on device **100** in response to user interactions with device **100**.

Text input module **134**, which is, optionally, a component of graphics module **132**, provides soft keyboards for entering text in various applications (e.g., contacts **137**, e-mail **140**, IM **141**, browser **147**, and any other application that needs text input).

GPS module **135** determines the location of the device and provides this information for use in various applications (e.g., to telephone **138** for use in location-based dialing, to camera **143** as picture/video metadata, and to applications that provide location-based services such as weather widgets, local yellow page widgets, and map/navigation widgets).

Applications **136** optionally include the following modules (or sets of instructions), or a subset or superset thereof:

- contacts module **137** (sometimes called an address book or contact list);
- telephone module **138**;
- video conferencing module **139**;
- e-mail client module **140**;
- instant messaging (IM) module **141**;
- workout support module **142**;
- camera module **143** for still and/or video images;
- image management module **144**;
- browser module **147**;
- calendar module **148**;
- widget modules **149**, which optionally include one or more of: weather widget **149-1**, stocks widget **149-2**, calculator widget **149-3**, alarm clock widget **149-4**, dictionary widget **149-5**, and other widgets obtained by the user, as well as user-created widgets **149-6**;
- widget creator module **150** for making user-created widgets **149-6**;
- search module **151**;
- video and music player module **152**, which is, optionally, made up of a video player module and a music player module;
- notes module **153**;
- map module **154**; and/or
- online video module **155**.

Examples of other applications **136** that are, optionally, stored in memory **102** include other word processing applications, other image editing applications, drawing applications, presentation applications, JAVA-enabled applications, encryption, digital rights management, voice recognition, and voice replication.

In conjunction with touch-sensitive display system **112**, display controller **156**, contact module **130**, graphics module **132**, and text input module **134**, contacts module **137** includes executable instructions to manage an address book or contact list (e.g., stored in application internal state **192** of contacts module **137** in memory **102** or memory **370**), including: adding name(s) to the address book; deleting

name(s) from the address book; associating telephone number(s), e-mail address(es), physical address(es) or other information with a name; associating an image with a name; categorizing and sorting names; providing telephone numbers and/or e-mail addresses to initiate and/or facilitate communications by telephone **138**, video conference **139**, e-mail **140**, or IM **141**; and so forth.

In conjunction with RF circuitry **108**, audio circuitry **110**, speaker **111**, microphone **113**, touch-sensitive display system **112**, display controller **156**, contact module **130**, graphics module **132**, and text input module **134**, telephone module **138** includes executable instructions to enter a sequence of characters corresponding to a telephone number, access one or more telephone numbers in address book **137**, modify a telephone number that has been entered, dial a respective telephone number, conduct a conversation and disconnect or hang up when the conversation is completed. As noted above, the wireless communication optionally uses any of a plurality of communications standards, protocols and technologies.

In conjunction with RF circuitry **108**, audio circuitry **110**, speaker **111**, microphone **113**, touch-sensitive display system **112**, display controller **156**, optical sensor(s) **164**, optical sensor controller **158**, contact module **130**, graphics module **132**, text input module **134**, contact list **137**, and telephone module **138**, videoconferencing module **139** includes executable instructions to initiate, conduct, and terminate a video conference between a user and one or more other participants in accordance with user instructions.

In conjunction with RF circuitry **108**, touch-sensitive display system **112**, display controller **156**, contact module **130**, graphics module **132**, and text input module **134**, e-mail client module **140** includes executable instructions to create, send, receive, and manage e-mail in response to user instructions. In conjunction with image management module **144**, e-mail client module **140** makes it very easy to create and send e-mails with still or video images taken with camera module **143**.

In conjunction with RF circuitry **108**, touch-sensitive display system **112**, display controller **156**, contact module **130**, graphics module **132**, and text input module **134**, the instant messaging module **141** includes executable instructions to enter a sequence of characters corresponding to an instant message, to modify previously entered characters, to transmit a respective instant message (for example, using a Short Message Service (SMS) or Multimedia Message Service (MMS) protocol for telephony-based instant messages or using XMPP, SIMPLE, Apple Push Notification Service (APNs) or IMPS for Internet-based instant messages), to receive instant messages and to view received instant messages. In some embodiments, transmitted and/or received instant messages optionally include graphics, photos, audio files, video files and/or other attachments as are supported in a MMS and/or an Enhanced Messaging Service (EMS). As used herein, "instant messaging" refers to both telephony-based messages (e.g., messages sent using SMS or MMS) and Internet-based messages (e.g., messages sent using XMPP, SIMPLE, APNs, or IMPS).

In conjunction with RF circuitry **108**, touch-sensitive display system **112**, display controller **156**, contact module **130**, graphics module **132**, text input module **134**, GPS module **135**, map module **154**, and music player module **146**, workout support module **142** includes executable instructions to create workouts (e.g., with time, distance, and/or calorie burning goals); communicate with workout sensors (in sports devices and smart watches); receive workout sensor data; calibrate sensors used to monitor a

workout; select and play music for a workout; and display, store and transmit workout data.

In conjunction with touch-sensitive display system 112, display controller 156, optical sensor(s) 164, optical sensor controller 158, contact module 130, graphics module 132, and image management module 144, camera module 143 includes executable instructions to capture still images or video (including a video stream) and store them into memory 102, modify characteristics of a still image or video, and/or delete a still image or video from memory 102.

In conjunction with touch-sensitive display system 112, display controller 156, contact module 130, graphics module 132, text input module 134, and camera module 143, image management module 144 includes executable instructions to arrange, modify (e.g., edit), or otherwise manipulate, label, delete, present (e.g., in a digital slide show or album), and store still and/or video images.

In conjunction with RF circuitry 108, touch-sensitive display system 112, display system controller 156, contact module 130, graphics module 132, and text input module 134, browser module 147 includes executable instructions to browse the Internet in accordance with user instructions, including searching, linking to, receiving, and displaying web pages or portions thereof, as well as attachments and other files linked to web pages.

In conjunction with RF circuitry 108, touch-sensitive display system 112, display system controller 156, contact module 130, graphics module 132, text input module 134, e-mail client module 140, and browser module 147, calendar module 148 includes executable instructions to create, display, modify, and store calendars and data associated with calendars (e.g., calendar entries, to do lists, etc.) in accordance with user instructions.

In conjunction with RF circuitry 108, touch-sensitive display system 112, display system controller 156, contact module 130, graphics module 132, text input module 134, and browser module 147, widget modules 149 are mini-applications that are, optionally, downloaded and used by a user (e.g., weather widget 149-1, stocks widget 149-2, calculator widget 149-3, alarm clock widget 149-4, and dictionary widget 149-5) or created by the user (e.g., user-created widget 149-6). In some embodiments, a widget includes an HTML (Hypertext Markup Language) file, a CSS (Cascading Style Sheets) file, and a JavaScript file. In some embodiments, a widget includes an XML (Extensible Markup Language) file and a JavaScript file (e.g., Yahoo! Widgets).

In conjunction with RF circuitry 108, touch-sensitive display system 112, display system controller 156, contact module 130, graphics module 132, text input module 134, and browser module 147, the widget creator module 150 includes executable instructions to create widgets (e.g., turning a user-specified portion of a web page into a widget).

In conjunction with touch-sensitive display system 112, display system controller 156, contact module 130, graphics module 132, and text input module 134, search module 151 includes executable instructions to search for text, music, sound, image, video, and/or other files in memory 102 that match one or more search criteria (e.g., one or more user-specified search terms) in accordance with user instructions.

In conjunction with touch-sensitive display system 112, display system controller 156, contact module 130, graphics module 132, audio circuitry 110, speaker 111, RF circuitry 108, and browser module 147, video and music player module 152 includes executable instructions that allow the user to download and play back recorded music and other sound files stored in one or more file formats, such as MP3

or AAC files, and executable instructions to display, present or otherwise play back videos (e.g., on touch-sensitive display system 112, or on an external display connected wirelessly or via external port 124). In some embodiments, device 100 optionally includes the functionality of an MP3 player, such as an iPod (trademark of Apple Inc.).

In conjunction with touch-sensitive display system 112, display controller 156, contact module 130, graphics module 132, and text input module 134, notes module 153 includes executable instructions to create and manage notes, to do lists, and the like in accordance with user instructions.

In conjunction with RF circuitry 108, touch-sensitive display system 112, display system controller 156, contact module 130, graphics module 132, text input module 134, GPS module 135, and browser module 147, map module 154 includes executable instructions to receive, display, modify, and store maps and data associated with maps (e.g., driving directions; data on stores and other points of interest at or near a particular location; and other location-based data) in accordance with user instructions.

In conjunction with touch-sensitive display system 112, display system controller 156, contact module 130, graphics module 132, audio circuitry 110, speaker 111, RF circuitry 108, text input module 134, e-mail client module 140, and browser module 147, online video module 155 includes executable instructions that allow the user to access, browse, receive (e.g., by streaming and/or download), play back (e.g., on the touch screen 112, or on an external display connected wirelessly or via external port 124), send an e-mail with a link to a particular online video, and otherwise manage online videos in one or more file formats, such as H.264. In some embodiments, instant messaging module 141, rather than e-mail client module 140, is used to send a link to a particular online video.

Each of the above identified modules and applications correspond to a set of executable instructions for performing one or more functions described above and the methods described in this application (e.g., the computer-implemented methods and other information processing methods described herein). These modules (i.e., sets of instructions) need not be implemented as separate software programs, procedures or modules, and thus various subsets of these modules are, optionally, combined or otherwise re-arranged in various embodiments. In some embodiments, memory 102 optionally stores a subset of the modules and data structures identified above. Furthermore, memory 102 optionally stores additional modules and data structures not described above.

In some embodiments, device 100 is a device where operation of a predefined set of functions on the device is performed exclusively through a touch screen and/or a touchpad. By using a touch screen and/or a touchpad as the primary input control device for operation of device 100, the number of physical input control devices (such as push buttons, dials, and the like) on device 100 is, optionally, reduced.

The predefined set of functions that are performed exclusively through a touch screen and/or a touchpad optionally include navigation between user interfaces. In some embodiments, the touchpad, when touched by the user, navigates device 100 to a main, home, or root menu from any user interface that is displayed on device 100. In such embodiments, a "menu button" is implemented using a touchpad. In some other embodiments, the menu button is a physical push button or other physical input control device instead of a touchpad.

FIG. 1B is a block diagram illustrating exemplary components for event handling in accordance with some embodiments. In some embodiments, memory 102 (in FIG. 1A) includes event sorter 170 (e.g., in operating system 126) and a respective application 136-1 (e.g., any of the aforementioned applications 137-153).

Event sorter 170 receives event information and determines the application 136-1 and application view 191 of application 136-1 to which to deliver the event information. Event sorter 170 includes event monitor 171 and event dispatcher module 174. In some embodiments, application 136-1 includes application internal state 192, which indicates the current application view(s) displayed on touch sensitive display 112 when the application is active or executing. In some embodiments, device/global internal state stored in the memory 102 is used by event sorter 170 to determine which application(s) is (are) currently active, and application internal state 192 is used by event sorter 170 to determine application views 191 to which to deliver event information.

In some embodiments, application internal state 192 includes additional information, such as one or more of: resume information to be used when application 136-1 resumes execution, user interface state information that indicates information being displayed or that is ready for display by application 136-1, a state queue for enabling the user to go back to a prior state or view of application 136-1, and a redo/undo queue of previous actions taken by the user.

Event monitor 171 receives event information from peripherals interface 118. Event information includes information about a sub-event (e.g., a user touch on touch-sensitive display 112, as part of a multi-touch gesture). Peripherals interface 118 transmits information it receives from I/O subsystem 106 or a sensor, such as proximity sensor 166, accelerometer(s) 168, and/or microphone 113 (through audio circuitry 110). Information that peripherals interface 118 receives from I/O subsystem 106 includes information from touch-sensitive display 112 or a touch-sensitive surface.

In some embodiments, event monitor 171 sends requests to the peripherals interface 118 at predetermined intervals. In response, peripherals interface 118 transmits event information. In other embodiments, peripheral interface 118 transmits event information only when there is a significant event (e.g., receiving an input above a predetermined noise threshold and/or for more than a predetermined duration).

In some embodiments, event sorter 170 also includes a hit view determination module 172 and/or an active event recognizer determination module 173.

Hit view determination module 172 provides software procedures for determining where a sub-event has taken place within one or more views, when touch sensitive display 112 displays more than one view. Views are made up of controls and other elements that a user can see on the display.

Another aspect of the user interface associated with an application is a set of views, sometimes herein called application views or user interface windows, in which information is displayed and touch-based gestures occur. The application views (of a respective application) in which a touch is detected may correspond to programmatic levels within a programmatic or view hierarchy of the application. For example, the lowest level view in which a touch is detected may be called the hit view, and the set of events that are recognized as proper inputs may be determined based, at least in part, on the hit view of the initial touch that begins a touch-based gesture.

Hit view determination module 172 receives information related to sub-events of a touch-based gesture. When an application has multiple views organized in a hierarchy, hit view determination module 172 identifies a hit view as the lowest view in the hierarchy which should handle the sub-event. In most circumstances, the hit view is the lowest level view in which an initiating sub-event occurs (e.g., the first sub-event in the sequence of sub-events that form an event or potential event). Once the hit view is identified by the hit view determination module, the hit view typically receives all sub-events related to the same touch or input source for which it was identified as the hit view.

Active event recognizer determination module 173 determines which view or views within a view hierarchy should receive a particular sequence of sub-events. In some embodiments, active event recognizer determination module 173 determines that only the hit view should receive a particular sequence of sub-events. In other embodiments, active event recognizer determination module 173 determines that all views that include the physical location of a sub-event are actively involved views, and therefore determines that all actively involved views should receive a particular sequence of sub-events. In other embodiments, even if touch sub-events were entirely confined to the area associated with one particular view, views higher in the hierarchy would still remain as actively involved views.

Event dispatcher module 174 dispatches the event information to an event recognizer (e.g., event recognizer 180). In embodiments including active event recognizer determination module 173, event dispatcher module 174 delivers the event information to an event recognizer determined by active event recognizer determination module 173. In some embodiments, event dispatcher module 174 stores in an event queue the event information, which is retrieved by a respective event receiver module 182.

In some embodiments, operating system 126 includes event sorter 170. Alternatively, application 136-1 includes event sorter 170. In yet other embodiments, event sorter 170 is a stand-alone module, or a part of another module stored in memory 102, such as contact/motion module 130.

In some embodiments, application 136-1 includes a plurality of event handlers 190 and one or more application views 191, each of which includes instructions for handling touch events that occur within a respective view of the application's user interface. Each application view 191 of the application 136-1 includes one or more event recognizers 180. Typically, a respective application view 191 includes a plurality of event recognizers 180. In other embodiments, one or more of event recognizers 180 are part of a separate module, such as a user interface kit (not shown) or a higher level object from which application 136-1 inherits methods and other properties. In some embodiments, a respective event handler 190 includes one or more of: data updater 176, object updater 177, GUI updater 178, and/or event data 179 received from event sorter 170. Event handler 190 may utilize or call data updater 176, object updater 177 or GUI updater 178 to update the application internal state 192. Alternatively, one or more of the application views 191 includes one or more respective event handlers 190. Also, in some embodiments, one or more of data updater 176, object updater 177, and GUI updater 178 are included in a respective application view 191.

A respective event recognizer 180 receives event information (e.g., event data 179) from event sorter 170, and identifies an event from the event information. Event recognizer 180 includes event receiver 182 and event comparator 184. In some embodiments, event recognizer 180 also

includes at least a subset of: metadata **183**, and event delivery instructions **188** (which may include sub-event delivery instructions).

Event receiver **182** receives event information from event sorter **170**. The event information includes information about a sub-event, for example, a touch or a touch movement. Depending on the sub-event, the event information also includes additional information, such as location of the sub-event. When the sub-event concerns motion of a touch the event information may also include speed and direction of the sub-event. In some embodiments, events include rotation of the device from one orientation to another (e.g., from a portrait orientation to a landscape orientation, or vice versa), and the event information includes corresponding information about the current orientation (also called device attitude) of the device.

Event comparator **184** compares the event information to predefined event or sub-event definitions and, based on the comparison, determines an event or sub-event, or determines or updates the state of an event or sub-event. In some embodiments, event comparator **184** includes event definitions **186**. Event definitions **186** contain definitions of events (e.g., predefined sequences of sub-events), for example, event **1** (**187-1**), event **2** (**187-2**), and others. In some embodiments, sub-events in an event **187** include, for example, touch begin, touch end, touch movement, touch cancellation, and multiple touching. In one example, the definition for event **1** (**187-1**) is a double-tap on a displayed object. The double-tap, for example, comprises a first touch (touch begin) on the displayed object for a predetermined phase, a first lift-off (touch end) for a predetermined phase, a second touch (touch begin) on the displayed object for a predetermined phase, and a second lift-off (touch end) for a predetermined phase. In another example, the definition for event **2** (**187-2**) is a dragging on a displayed object. The dragging, for example, comprises a touch (or contact) on the displayed object for a predetermined phase, a movement of the touch across touch-sensitive display **112**, and lift-off of the touch (touch end). In some embodiments, the event also includes information for one or more associated event handlers **190**.

In some embodiments, event definition **187** includes a definition of an event for a respective user-interface object. In some embodiments, event comparator **184** performs a hit test to determine which user-interface object is associated with a sub-event. For example, in an application view in which three user-interface objects are displayed on touch-sensitive display **112**, when a touch is detected on touch-sensitive display **112**, event comparator **184** performs a hit test to determine which of the three user-interface objects is associated with the touch (sub-event). If each displayed object is associated with a respective event handler **190**, the event comparator uses the result of the hit test to determine which event handler **190** should be activated. For example, event comparator **184** selects an event handler associated with the sub-event and the object triggering the hit test.

In some embodiments, the definition for a respective event **187** also includes delayed actions that delay delivery of the event information until after it has been determined whether the sequence of sub-events does or does not correspond to the event recognizer's event type.

When a respective event recognizer **180** determines that the series of sub-events do not match any of the events in event definitions **186**, the respective event recognizer **180** enters an event impossible, event failed, or event ended state, after which it disregards subsequent sub-events of the touch-based gesture. In this situation, other event recogniz-

ers, if any, that remain active for the hit view continue to track and process sub-events of an ongoing touch-based gesture.

In some embodiments, a respective event recognizer **180** includes metadata **183** with configurable properties, flags, and/or lists that indicate how the event delivery system should perform sub-event delivery to actively involved event recognizers. In some embodiments, metadata **183** includes configurable properties, flags, and/or lists that indicate how event recognizers may interact with one another. In some embodiments, metadata **183** includes configurable properties, flags, and/or lists that indicate whether sub-events are delivered to varying levels in the view or programmatic hierarchy.

In some embodiments, a respective event recognizer **180** activates event handler **190** associated with an event when one or more particular sub-events of an event are recognized. In some embodiments, a respective event recognizer **180** delivers event information associated with the event to event handler **190**. Activating an event handler **190** is distinct from sending (and deferred sending) sub-events to a respective hit view. In some embodiments, event recognizer **180** throws a flag associated with the recognized event, and event handler **190** associated with the flag catches the flag and performs a predefined process.

In some embodiments, event delivery instructions **188** include sub-event delivery instructions that deliver event information about a sub-event without activating an event handler. Instead, the sub-event delivery instructions deliver event information to event handlers associated with the series of sub-events or to actively involved views. Event handlers associated with the series of sub-events or with actively involved views receive the event information and perform a predetermined process.

In some embodiments, data updater **176** creates and updates data used in application **136-1**. For example, data updater **176** updates the telephone number used in contacts module **137**, or stores a video file used in video and music player module **145**. In some embodiments, object updater **177** creates and updates objects used in application **136-1**. For example, object updater **177** creates a new user-interface object or updates the position of a user-interface object. GUI updater **178** updates the GUI. For example, GUI updater **178** prepares display information and sends it to graphics module **132** for display on a touch-sensitive display.

In some embodiments, event handler(s) **190** includes or has access to data updater **176**, object updater **177**, and GUI updater **178**. In some embodiments, data updater **176**, object updater **177**, and GUI updater **178** are included in a single module of a respective application **136-1** or application view **191**. In other embodiments, they are included in two or more software modules.

It shall be understood that the foregoing discussion regarding event handling of user touches on touch-sensitive displays also applies to other forms of user inputs to operate multifunction devices **100** with input-devices, not all of which are initiated on touch screens, e.g., coordinating mouse movement and mouse button presses with or without single or multiple keyboard presses or holds, user movements taps, drags, scrolls, etc., on touch-pads, pen stylus inputs, movement of the device, oral instructions, detected eye movements, biometric inputs, and/or any combination thereof, which may be utilized as inputs corresponding to sub-events which define an event to be recognized.

FIG. 2A illustrates a portable multifunction device **100** having a touch screen (e.g., touch-sensitive display system **112**, FIG. 1A) in accordance with some embodiments. The

touch screen optionally displays one or more graphics within user interface (UI) **200**. In this embodiment, as well as others described below, a user is enabled to select one or more of the graphics by making a gesture on the graphics, for example, with one or more fingers **202** (not drawn to scale in the figure) or one or more styluses **203** (not drawn to scale in the figure). In some embodiments, selection of one or more graphics occurs when the user breaks contact with the one or more graphics. In some embodiments, the gesture optionally includes one or more taps, one or more swipes (from left to right, right to left, upward and/or downward) and/or a rolling of a finger (from right to left, left to right, upward and/or downward) that has made contact with device **100**. In some implementations or circumstances, inadvertent contact with a graphic does not select the graphic. For example, a swipe gesture that sweeps over an application icon optionally does not select the corresponding application when the gesture corresponding to selection is a tap.

Device **100** optionally also includes one or more physical buttons, such as “home” or menu button **204**. As described previously, menu button **204** is, optionally, used to navigate to any application **136** in a set of applications that are, optionally executed on device **100**. Alternatively, in some embodiments, the menu button is implemented as a soft key in a GUI displayed on the touch-screen display.

In some embodiments, device **100** includes the touch-screen display, menu button **204**, push button **206** for powering the device on/off and locking the device, volume adjustment button(s) **208**, Subscriber Identity Module (SIM) card slot **210**, head set jack **212**, and docking/charging external port **124**. Push button **206** is, optionally, used to turn the power on/off on the device by depressing the button and holding the button in the depressed state for a predefined time interval; to lock the device by depressing the button and releasing the button before the predefined time interval has elapsed; and/or to unlock the device or initiate an unlock process. In some embodiments, device **100** also accepts verbal input for activation or deactivation of some functions through microphone **113**. Device **100** also, optionally, includes one or more contact intensity sensors **165** for detecting intensity of contacts on touch-sensitive display system **112** and/or one or more tactile output generators **167** for generating tactile outputs for a user of device **100**.

FIG. 2B illustrates an exemplary user interface on a device (e.g., device **100**, FIG. 1A) with a touch-sensitive surface **251** (e.g., a tablet or touchpad) that is separate from the display **250**. Device **100** also, optionally, includes one or more contact intensity sensors (e.g., one or more of sensors **259**) for detecting intensity of contacts on touch-sensitive surface **251** and/or one or more tactile output generators **257** for generating tactile outputs for a user of device **100**.

Although many of the examples that follow will be given with reference to inputs on touch screen display **112** (where the touch sensitive surface and the display are combined), in some embodiments, the device detects inputs on a touch-sensitive surface that is separate from the display, as shown in FIG. 2B. In some embodiments, the touch-sensitive surface (e.g., **251** in FIG. 2B) has a primary axis (e.g., **252** in FIG. 2B) that corresponds to a primary axis (e.g., **253** in FIG. 2B) on the display (e.g., **250**). In accordance with these embodiments, the device detects contacts (e.g., **260** and **262** in FIG. 2B) with the touch-sensitive surface **251** at locations that correspond to respective locations on the display (e.g., in FIG. 2B, **260** corresponds to **268** and **262** corresponds to **270**). In this way, user inputs (e.g., contacts **260** and **262**, and movements thereof) detected by the device on the touch-sensitive surface (e.g., **251** in FIG. 2B) are used by the

device to manipulate the user interface on the display (e.g., **250** in FIG. 2B) of the multifunction device when the touch-sensitive surface is separate from the display. It should be understood that similar methods are, optionally, used for other user interfaces described herein.

Additionally, while the following examples are given primarily with reference to finger inputs (e.g., finger contacts, finger tap gestures, finger swipe gestures, etc.), it should be understood that, in some embodiments, one or more of the finger inputs are replaced with input from another input device (e.g., a mouse based input or a stylus input). For example, a swipe gesture is, optionally, replaced with a mouse click (e.g., instead of a contact) followed by movement of the cursor along the path of the swipe (e.g., instead of movement of the contact). As another example, a tap gesture is, optionally, replaced with a mouse click while the cursor is located over the location of the tap gesture (e.g., instead of detection of the contact followed by ceasing to detect the contact). Similarly, when multiple user inputs are simultaneously detected, it should be understood that multiple computer mice are, optionally, used simultaneously, or a mouse and finger contacts are, optionally, used simultaneously.

As used herein, the term “focus selector” refers to an input element that indicates a current part of a user interface with which a user is interacting. In some implementations that include a cursor or other location marker, the cursor acts as a “focus selector,” so that when an input (e.g., a press input) is detected on a touch-sensitive surface (e.g., touchpad or touch-sensitive surface **251** in FIG. 2B) while the cursor is over a particular user interface element (e.g., a button, window, slider or other user interface element), the particular user interface element is adjusted in accordance with the detected input. In some implementations that include a touch-screen display (e.g., touch-sensitive display system **112** in FIG. 1A or the touch screen in FIG. 2A) that enables direct interaction with user interface elements on the touch-screen display, a detected contact on the touch-screen acts as a “focus selector,” so that when an input (e.g., a press input by the contact) is detected on the touch-screen display at a location of a particular user interface element (e.g., a button, window, slider or other user interface element), the particular user interface element is adjusted in accordance with the detected input. In some implementations, focus is moved from one region of a user interface to another region of the user interface without corresponding movement of a cursor or movement of a contact on a touch-screen display (e.g., by using a tab key or arrow keys to move focus from one button to another button); in these implementations, the focus selector moves in accordance with movement of focus between different regions of the user interface. Without regard to the specific form taken by the focus selector, the focus selector is generally the user interface element (or contact on a touch-screen display) that is controlled by the user so as to communicate the user’s intended interaction with the user interface (e.g., by indicating, to the device, the element of the user interface with which the user is intending to interact). For example, the location of a focus selector (e.g., a cursor, a contact, or a selection box) over a respective button while a press input is detected on the touch-sensitive surface (e.g., a touchpad or touch screen) will indicate that the user is intending to activate the respective button (as opposed to other user interface elements shown on a display of the device).

As used in the specification and claims, the term “intensity” of a contact on a touch-sensitive surface refers to the force or pressure (force per unit area) of a contact (e.g., a

finger contact or a stylus contact) on the touch-sensitive surface, or to a substitute (proxy) for the force or pressure of a contact on the touch-sensitive surface. The intensity of a contact has a range of values that includes at least four distinct values and more typically includes hundreds of distinct values (e.g., at least 256). Intensity of a contact is, optionally, determined (or measured) using various approaches and various sensors or combinations of sensors. For example, one or more force sensors underneath or adjacent to the touch-sensitive surface are, optionally, used to measure force at various points on the touch-sensitive surface. In some implementations, force measurements from multiple force sensors are combined (e.g., a weighted average or a sum) to determine an estimated force of a contact. Similarly, a pressure-sensitive tip of a stylus is, optionally, used to determine a pressure of the stylus on the touch-sensitive surface. Alternatively, the size of the contact area detected on the touch-sensitive surface and/or changes thereto, the capacitance of the touch-sensitive surface proximate to the contact and/or changes thereto, and/or the resistance of the touch-sensitive surface proximate to the contact and/or changes thereto are, optionally, used as a substitute for the force or pressure of the contact on the touch-sensitive surface. In some implementations, the substitute measurements for contact force or pressure are used directly to determine whether an intensity threshold has been exceeded (e.g., the intensity threshold is described in units corresponding to the substitute measurements). In some implementations, the substitute measurements for contact force or pressure are converted to an estimated force or pressure and the estimated force or pressure is used to determine whether an intensity threshold has been exceeded (e.g., the intensity threshold is a pressure threshold measured in units of pressure). Using the intensity of a contact as an attribute of a user input allows for user access to additional device functionality that may otherwise not be readily accessible by the user on a reduced-size device with limited real estate for displaying affordances (e.g., on a touch-sensitive display) and/or receiving user input (e.g., via a touch-sensitive display, a touch-sensitive surface, or a physical/mechanical control such as a knob or a button).

In some embodiments, contact/motion module 130 uses a set of one or more intensity thresholds to determine whether an operation has been performed by a user (e.g., to determine whether a user has “clicked” on an icon). In some embodiments, at least a subset of the intensity thresholds are determined in accordance with software parameters (e.g., the intensity thresholds are not determined by the activation thresholds of particular physical actuators and can be adjusted without changing the physical hardware of device 100). For example, a mouse “click” threshold of a trackpad or touch-screen display can be set to any of a large range of predefined thresholds values without changing the trackpad or touch-screen display hardware. Additionally, in some implementations a user of the device is provided with software settings for adjusting one or more of the set of intensity thresholds (e.g., by adjusting individual intensity thresholds and/or by adjusting a plurality of intensity thresholds at once with a system-level click “intensity” parameter).

As used in the specification and claims, the term “characteristic intensity” of a contact refers to a characteristic of the contact based on one or more intensities of the contact. In some embodiments, the characteristic intensity is based on multiple intensity samples. The characteristic intensity is, optionally, based on a predefined number of intensity samples, or a set of intensity samples collected during a predetermined time period (e.g., 0.05, 0.1, 0.2, 0.5, 1, 2, 5,

10 seconds) relative to a predefined event (e.g., after detecting the contact, prior to detecting liftoff of the contact, before or after detecting a start of movement of the contact, prior to detecting an end of the contact, before or after detecting an increase in intensity of the contact, and/or before or after detecting a decrease in intensity of the contact). A characteristic intensity of a contact is, optionally based on one or more of: a maximum value of the intensities of the contact, a mean value of the intensities of the contact, an average value of the intensities of the contact, a top 10 percentile value of the intensities of the contact, a value at the half maximum of the intensities of the contact, a value at the 90 percent maximum of the intensities of the contact, or the like. In some embodiments, the duration of the contact is used in determining the characteristic intensity (e.g., when the characteristic intensity is an average of the intensity of the contact over time). In some embodiments, the characteristic intensity is compared to a set of one or more intensity thresholds to determine whether an operation has been performed by a user. For example, the set of one or more intensity thresholds may include a first intensity threshold and a second intensity threshold. In this example, a contact with a characteristic intensity that does not exceed the first threshold results in a first operation, a contact with a characteristic intensity that exceeds the first intensity threshold and does not exceed the second intensity threshold results in a second operation, and a contact with a characteristic intensity that exceeds the second intensity threshold results in a third operation. In some embodiments, a comparison between the characteristic intensity and one or more intensity thresholds is used to determine whether or not to perform one or more operations (e.g., whether to perform a respective option or forgo performing the respective operation) rather than being used to determine whether to perform a first operation or a second operation.

In some embodiments, a portion of a gesture is identified for purposes of determining a characteristic intensity. For example, a touch-sensitive surface may receive a continuous swipe contact transitioning from a start location and reaching an end location (e.g., a drag gesture), at which point the intensity of the contact increases. In this example, the characteristic intensity of the contact at the end location may be based on only a portion of the continuous swipe contact, and not the entire swipe contact (e.g., only the portion of the swipe contact at the end location). In some embodiments, a smoothing algorithm may be applied to the intensities of the swipe contact prior to determining the characteristic intensity of the contact. For example, the smoothing algorithm optionally includes one or more of: an unweighted sliding-average smoothing algorithm, a triangular smoothing algorithm, a median filter smoothing algorithm, and/or an exponential smoothing algorithm. In some circumstances, these smoothing algorithms eliminate narrow spikes or dips in the intensities of the swipe contact for purposes of determining a characteristic intensity.

The user interface figures described herein optionally include various intensity diagrams that show the current intensity of the contact on the touch-sensitive surface relative to one or more intensity thresholds (e.g., a contact detection intensity threshold  $IT_D$ , a light press intensity threshold  $IT_L$ , a deep press intensity threshold  $IT_D$  (e.g., that is at least initially higher than  $I_L$ ), and/or one or more other intensity thresholds (e.g., an intensity threshold  $hi$  that is lower than  $I_L$ )). This intensity diagram is typically not part of the displayed user interface, but is provided to aid in the interpretation of the figures. In some embodiments, the light press intensity threshold corresponds to an intensity at which

the device will perform operations typically associated with clicking a button of a physical mouse or a trackpad. In some embodiments, the deep press intensity threshold corresponds to an intensity at which the device will perform operations that are different from operations typically associated with clicking a button of a physical mouse or a trackpad. In some embodiments, when a contact is detected with a characteristic intensity below the light press intensity threshold (e.g., and above a nominal contact-detection intensity threshold  $IT_0$  below which the contact is no longer detected), the device will move a focus selector in accordance with movement of the contact on the touch-sensitive surface without performing an operation associated with the light press intensity threshold or the deep press intensity threshold. Generally, unless otherwise stated, these intensity thresholds are consistent between different sets of user interface figures.

In some embodiments, the response of the device to inputs detected by the device depends on criteria based on the contact intensity during the input. For example, for some “light press” inputs, the intensity of a contact exceeding a first intensity threshold during the input triggers a first response. In some embodiments, the response of the device to inputs detected by the device depends on criteria that include both the contact intensity during the input and time-based criteria. For example, for some “deep press” inputs, the intensity of a contact exceeding a second intensity threshold during the input, greater than the first intensity threshold for a light press, triggers a second response only if a delay time has elapsed between meeting the first intensity threshold and meeting the second intensity threshold. This delay time is typically less than 200 ms in duration (e.g., 40, 100, or 120 ms, depending on the magnitude of the second intensity threshold, with the delay time increasing as the second intensity threshold increases). This delay time helps to avoid accidental deep press inputs. As another example, for some “deep press” inputs, there is a reduced-sensitivity time period that occurs after the time at which the first intensity threshold is met. During the reduced-sensitivity time period, the second intensity threshold is increased. This temporary increase in the second intensity threshold also helps to avoid accidental deep press inputs. For other deep press inputs, the response to detection of a deep press input does not depend on time-based criteria.

In some embodiments, one or more of the input intensity thresholds and/or the corresponding outputs vary based on one or more factors, such as user settings, contact motion, input timing, application running, rate at which the intensity is applied, number of concurrent inputs, user history, environmental factors (e.g., ambient noise), focus selector position, and the like. Exemplary factors are described in U.S. patent application Ser. Nos. 14/399,606 and 14/624,296, which are incorporated by reference herein in their entireties.

For example, FIG. 2C illustrates a dynamic intensity threshold **280** that changes over time based in part on the intensity of touch input **276** over time. Dynamic intensity threshold **280** is a sum of two components, first component **274** that decays over time after a predefined delay time **p1** from when touch input **276** is initially detected, and second component **278** that trails the intensity of touch input **276** over time. The initial high intensity threshold of first component **274** reduces accidental triggering of a “deep press” response, while still allowing an immediate “deep press” response if touch input **276** provides sufficient intensity. Second component **278** reduces unintentional triggering of a “deep press” response by gradual intensity fluctuations of in a touch input. In some embodiments, when touch input **276**

satisfies dynamic intensity threshold **280** (e.g., at point **281** in FIG. 2C), the “deep press” response is triggered.

FIG. 2D illustrates another dynamic intensity threshold **286** (e.g., intensity threshold ID). FIG. 2D also illustrates two other intensity thresholds: a first intensity threshold  $I_L$  and a second intensity threshold  $I_L$ . In FIG. 2D, although touch input **284** satisfies the first intensity threshold  $I_L$  and the second intensity threshold  $I_L$  prior to time **p2**, no response is provided until delay time **p2** has elapsed at time **282**. Also in FIG. 2D, dynamic intensity threshold **286** decays over time, with the decay starting at time **288** after a predefined delay time **p1** has elapsed from time **282** (when the response associated with the second intensity threshold  $I_L$  was triggered). This type of dynamic intensity threshold reduces accidental triggering of a response associated with the dynamic intensity threshold ID immediately after, or concurrently with, triggering a response associated with a lower intensity threshold, such as the first intensity threshold  $I_L$  or the second intensity threshold  $I_L$ .

FIG. 2E illustrate yet another dynamic intensity threshold **292** (e.g., intensity threshold ID). In FIG. 2E, a response associated with the intensity threshold  $I_L$  is triggered after the delay time **p2** has elapsed from when touch input **290** is initially detected. Concurrently, dynamic intensity threshold **292** decays after the predefined delay time **p1** has elapsed from when touch input **290** is initially detected. So a decrease in intensity of touch input **290** after triggering the response associated with the intensity threshold  $I_L$ , followed by an increase in the intensity of touch input **290**, without releasing touch input **290**, can trigger a response associated with the intensity threshold ID (e.g., at time **294**) even when the intensity of touch input **290** is below another intensity threshold, for example, the intensity threshold  $I_L$ .

An increase of characteristic intensity of the contact from an intensity below the light press intensity threshold  $IT_L$  to an intensity between the light press intensity threshold  $IT_L$  and the deep press intensity threshold  $IT_D$  is sometimes referred to as a “light press” input. An increase of characteristic intensity of the contact from an intensity below the deep press intensity threshold  $IT_D$  to an intensity above the deep press intensity threshold  $IT_D$  is sometimes referred to as a “deep press” input. An increase of characteristic intensity of the contact from an intensity below the contact-detection intensity threshold  $IT_0$  to an intensity between the contact-detection intensity threshold  $IT_0$  and the light press intensity threshold  $IT_L$  is sometimes referred to as detecting the contact on the touch-surface. A decrease of characteristic intensity of the contact from an intensity above the contact-detection intensity threshold  $IT_0$  to an intensity below the contact-detection intensity threshold  $IT_0$  is sometimes referred to as detecting liftoff of the contact from the touch-surface. In some embodiments  $IT_0$  is zero. In some embodiments,  $IT_0$  is greater than zero. In some illustrations a shaded circle or oval is used to represent intensity of a contact on the touch-sensitive surface. In some illustrations, a circle or oval without shading is used represent a respective contact on the touch-sensitive surface without specifying the intensity of the respective contact.

In some embodiments, described herein, one or more operations are performed in response to detecting a gesture that includes a respective press input or in response to detecting the respective press input performed with a respective contact (or a plurality of contacts), where the respective press input is detected based at least in part on detecting an increase in intensity of the contact (or plurality of contacts) above a press-input intensity threshold. In some embodiments, the respective operation is performed in response to

detecting the increase in intensity of the respective contact above the press-input intensity threshold (e.g., the respective operation is performed on a “down stroke” of the respective press input). In some embodiments, the press input includes an increase in intensity of the respective contact above the press-input intensity threshold and a subsequent decrease in intensity of the contact below the press-input intensity threshold, and the respective operation is performed in response to detecting the subsequent decrease in intensity of the respective contact below the press-input threshold (e.g., the respective operation is performed on an “up stroke” of the respective press input).

In some embodiments, the device employs intensity hysteresis to avoid accidental inputs sometimes termed “jitter,” where the device defines or selects a hysteresis intensity threshold with a predefined relationship to the press-input intensity threshold (e.g., the hysteresis intensity threshold is X intensity units lower than the press-input intensity threshold or the hysteresis intensity threshold is 75%, 90%, or some reasonable proportion of the press-input intensity threshold). Thus, in some embodiments, the press input includes an increase in intensity of the respective contact above the press-input intensity threshold and a subsequent decrease in intensity of the contact below the hysteresis intensity threshold that corresponds to the press-input intensity threshold, and the respective operation is performed in response to detecting the subsequent decrease in intensity of the respective contact below the hysteresis intensity threshold (e.g., the respective operation is performed on an “up stroke” of the respective press input). Similarly, in some embodiments, the press input is detected only when the device detects an increase in intensity of the contact from an intensity at or below the hysteresis intensity threshold to an intensity at or above the press-input intensity threshold and, optionally, a subsequent decrease in intensity of the contact to an intensity at or below the hysteresis intensity, and the respective operation is performed in response to detecting the press input (e.g., the increase in intensity of the contact or the decrease in intensity of the contact, depending on the circumstances).

For ease of explanation, the description of operations performed in response to a press input associated with a press-input intensity threshold or in response to a gesture including the press input are, optionally, triggered in response to detecting: an increase in intensity of a contact above the press-input intensity threshold, an increase in intensity of a contact from an intensity below the hysteresis intensity threshold to an intensity above the press-input intensity threshold, a decrease in intensity of the contact below the press-input intensity threshold, or a decrease in intensity of the contact below the hysteresis intensity threshold corresponding to the press-input intensity threshold. Additionally, in examples where an operation is described as being performed in response to detecting a decrease in intensity of a contact below the press-input intensity threshold, the operation is, optionally, performed in response to detecting a decrease in intensity of the contact below a hysteresis intensity threshold corresponding to, and lower than, the press-input intensity threshold. As described above, in some embodiments, the triggering of these responses also depends on time-based criteria being met (e.g., a delay time has elapsed between a first intensity threshold being met and a second intensity threshold being met).

FIG. 3 is a schematic of a user interface for a menu of applications on portable multifunction device 100, in accordance with some embodiments. Similar user interfaces may be implemented on a desktop device 300 in accordance with

some embodiments. In some embodiments, user interface 300 includes the following elements, or a subset or superset thereof:

Signal strength indicator(s) 302 for wireless communication(s), such as cellular and Wi-Fi signals;

Time 304;

Bluetooth indicator 305;

Battery status indicator 306;

Tray 308 with icons for frequently used applications, such as:

Phone 138, which may include an indicator 314 of the number of missed calls or voicemail messages;

E-mail client 140, which may include an indicator 310 of the number of unread e-mails;

Browser 147; and

Video and music player 145, also referred to as iPod (trademark of Apple Inc.) module 152; and

Icons for other applications, such as:

IM 141;

Calendar 148;

Image management 144;

Camera 143;

Online video module 145, also referred to as YouTube (trademark of Google Inc.) module 145;

Stocks 149-2;

Map 146;

Weather 149-1;

Dictionary 149-3;

User-Created Widget 149-6;

Notes 146;

Settings 312, which provides access to settings for device 100 and its various applications 136;

Word processor 153-1;

Drawing 153-2;

Spreadsheet 153-3; and

Presentation 153-4.

#### User Interfaces and Associated Processes

Attention is now directed towards embodiments of processes and associated user interfaces (“UI”) that may be implemented on an electronic device with a display, a touch-sensitive surface, and optionally one or more sensors to detect intensities of contacts with the touch-sensitive surface, such as the portable multifunction device 100.

FIG. 4A is a flow chart illustrating a method 400 of cursor manipulation, in accordance with some embodiments. The method 400 is performed at a portable multifunction device (e.g., the device 100 in FIG. 1A) with a touch screen display (e.g., the touch screen display 112 in FIG. 1A). As described below, the method 400 provides an expedient mechanism for selecting content at a portable multifunction device with a touch screen display. This method is both faster and easier to perform than using a peripheral device, like a mouse. The method is also intuitive to a user, thereby reducing the number, extent, and/or nature of the inputs from the user when selecting content, and creating a more efficient human-machine interface. A more efficient input mechanism also requires less computing resources, thereby increasing battery life of the device.

In some embodiments, the device 100 displays content of an electronic document on the touch screen display 112. In some embodiments, the content comprises text (e.g., plain text, unstructured text, formatted text, or text in a web page). In other embodiments, the content comprises graphics with or without text. Moreover, the content may be editable or read-only. In addition to displaying the content, when no

content is selected, the device **100** may display a cursor within the electronic document, e.g., for text entry. In some embodiments, while displaying the content of the electronic document, the device **100** detects two substantially simultaneous touch inputs at **402**. These two substantially simultaneous touch inputs can occur and be detected anywhere on the screen, including over an active virtual keyboard being displayed on the screen.

In some embodiments, the device **100** continuously monitors touch inputs and continuous movements of the touch inputs on the touch screen **112**. Once touch inputs are detected by the device **100**, the device **100** determines whether the two substantially simultaneous touch inputs are located on a soft keyboard on the touch screen at **406**. In response to detecting the two substantially simultaneous touch inputs that started on the soft keyboard (**406—Yes**), the device **100** displays a soft keyboard that has a changed appearance at **404**. In some embodiments, the device continuously monitors the touch inputs at step **406** so that the appearance of the keyboard remains changed when the two substantially simultaneous touch inputs that started on the soft keyboard are followed by a continuous movement of the two substantially simultaneous touch inputs without breaking contact with the touch screen **112**. In other words, the device at step **406** detects whether there were two substantially simultaneous inputs on the soft keyboard either with or without a subsequent continuous movement off the keyboard. In some embodiments, in response to detecting the two substantially simultaneous touch inputs where not initially detected on the soft keyboard (**406—No**), the device **100** displays a soft keyboard with an unchanged appearance at **408**, e.g., displays a regular unblurred soft keyboard or a keyboard with all alphanumeric characters displayed. A soft keyboard is a set of multiple virtual keys displayed on the screen, e.g., a QWERTY keyboard, as shown in FIG. **13A**.

In FIG. **13A**, the exemplary soft keyboard **1321** has multiple virtual keys and each key has a respective alphanumeric character. In addition, in some embodiments, each key has simulated three-dimensional characteristics (e.g., a three-dimensional shape, drop shadow, etc.) In some embodiments, in response to detecting two substantially simultaneous touch inputs at a first location on the soft keyboard, the device **100** displays a soft keyboard with a changed appearance as shown in FIG. **13B**. In comparison with the soft keyboard with the unchanged appearance shown in FIG. **13A**, the soft keyboard **1321** with the changed appearance shown in FIG. **13B** does not have the simulated three-dimensional characteristics (e.g., the drop shadow is removed) and the alphanumeric characters on the keys are removed. In addition, in some embodiments, the color, hue, saturation, brightness, and/or contrast of the soft keyboard **1321** is also changed (e.g., semitransparent) to indicate that the application has entered a mode that is different from a text entering mode. In the non-text entering mode, the soft keyboard is not responsive to keystrokes for text entries, but rather serves as an onscreen touchpad or track pad for moving the cursor or for selecting content. The changed keyboard appearance provides an intuitive indication that the function of the soft keyboard has changed.

As shown in FIG. **13B**, in some embodiments, the device **100** detects a sliding gesture **1332** starting from the first location on the soft keyboard **1321** to a second location anywhere on the touch screen **112**. The sliding gesture **1332** follows the two substantially simultaneous touch inputs without breaking contact with the touch screen **112**, e.g., it starts on the soft keyboard and moves beyond the soft keyboard **1321** into the content region **1302**. In response to

detecting the sliding gesture, the device **100** maintains the changed appearance of the soft keyboard **1320** throughout the entire sliding gesture. At the end of the sliding gesture, as shown in FIG. **13C**, in response to a lift-off gesture, the device **100** displays the soft keyboard with its original unchanged appearance, e.g., with the alphanumeric characters on the virtual keys and the three-dimensional characteristics of the virtual keys and/or an unblurred the virtual keyboard.

FIGS. **7A-7C** illustrate exemplary user interfaces of soft keyboard appearance changes, in accordance with some embodiments. In FIG. **7A**, content of an electronic document is displayed on the touch screen display **112**. Also displayed on the touch screen display **112** is a soft keyboard **521** that is displayed in focus. Subsequently, the device **100** detects two substantially simultaneous touch inputs (e.g., two-finger tap) **524** on the soft keyboard **521**. In response to detecting the two substantially simultaneous touch inputs on the soft keyboard **521**, the device **100** displays a blurred soft keyboard **521**, as shown in FIG. **7B**.

In some embodiments, instead of displaying the blurred soft keyboard, the device changes one or more of: color, hue, saturation, brightness, and contrast of the soft keyboard **521** based on the content of the electronic document. In some embodiments, the appearance of the blurred keyboard **521** is based on the content displayed and a set of control-appearance values for blur radius, saturation adjustment, opacity of a white overlay, opacity of a black overlay, opacity of user interface elements in keyboard **521**, and/or the color of text displayed in the region where the keyboard **521** is displayed. For example, in FIG. **7B**, the region where keyboard **521** is located has been blurred in accordance with a value for the blur radius, the black text color of the content **500**, etc.

As shown in FIG. **7B**, once the device **100** detects a continuous movement without breaking contact with the touch screen display following the two substantially simultaneous touch input from location **524-1** on the keyboard **521**, leaving the keyboard **521**, and moving to location **524-2** on the content **500** and not over the keyboard. In response, the device **100** replaces the display of the blurred soft keyboard with display of focused soft keyboard **521**, as shown in FIG. **7C**. Subsequently, as shown in FIG. **7C**, as long as the touch inputs **524** are not located on the keyboard **521**, the keyboard stays in focus.

Referring back to FIG. **4A**, following the detection of two substantially simultaneous touch inputs, the portable multifunction device **100** determines whether prior to detecting the touch inputs, there is an existing selection of the content at **411**. By a selection it is meant that certain text, graphics, or other objects are selected (e.g., shown as highlighted text). If the device **100** does not detect an existing selection, the device **100** then determines the type of touch input at **413**. The portable multifunction device **100** can identify at least four types of the touch inputs, namely, drag, tap, hold-and-drag, and flick, among others. In some embodiments, a drag input is a sliding gesture along the surface of the touch screen. In some embodiments, a tap is a touch contact followed by a lift-off or release of contact from the surface of the touch screen, without any intervening sliding gesture detected between the touch and the lift-off. In some embodiments, a hold-and-drag is an initial touch contact, followed by a predetermined period of time greater than zero (the hold period) (e.g., 1.5 seconds), and then followed by a sliding gesture on the surface of the touch screen away from the initial point of contact, without any intervening lift-off or release of contact from the surface of the touch screen. In some embodiments, a flick is a rapid sliding gesture in a

single direction along the surface of the touch screen followed by a lift-off or release of contact from the surface of the touch screen.

Depending on the type of the touch input received, the device 100 performs different actions. As shown in FIG. 4A, if a drag is detected immediately after the two touch inputs are detected at 402 (e.g., with no intervening lift-off), then the device 100 moves the cursor, at 421. In some embodiments, prior to dragging the cursor, the cursor is animated (e.g., enlarged) to clearly indicate the beginning of a cursor movement. In some embodiments, a ghost cursor is displayed while the cursor is being moved or instead of the actual cursor being moved. For example, a ghost cursor can be a cursor with a different appearance, such as a lighter colored cursor, that is offset from the cursor but linked to it, so that when the cursor moves around the screen, so does the ghost cursor. Alternatively, the ghost cursor is a lighter colored cursor, while the cursor is moved around the screen by the user, the ghost cursor shows the closest right position for the cursor, until a lift off event occurs, whereafter the real cursor replaces the ghost cursor at the position of the ghost cursor when the lift off event occurred. If a tap is detected (e.g., if after the two touch inputs are detected at 402, a lift-off is detected without any intervening swipe gesture), then a portion of the document, such as a word, image, or other object closest to the cursor is selected, at 442. If a hold and drag is detected (e.g., the touch inputs remain in contact with the screen without moving for a predetermined period of time before the drag gesture occurs), then the device 100 starts selecting text and/or graphics while the selection is extended in the direction of the drag gesture, at 452. If a flick is detected, then the device 100 moves the cursor to a distal point of the text of the document, at 430. For example, the distal point in the text is the end or beginning of a line or a top or bottom of a page or document. Examples are described in further detail below with respect to each type of touch input.

For example, if the type of touch input is a drag and the touch input is not located on a selection, then the device 100 moves the cursor and displays a ghost cursor at 421. FIG. 5A illustrates an exemplary user interface for dragging cursor when there is no existing selection of content, in accordance with some embodiments. In this embodiment, the electronic document 500 is displayed in the user interface of an application (e.g., a word processing application 152, a presentation application 153, a spreadsheet application 155, or the like). The application user interface in which document 500 is displayed may include toolbar 510 and button(s) 512 for navigating to, if any, other documents. Electronic document 500 includes content, such as text, images, objects, tables, charts, and so on. In addition to displaying the content of the electronic document, the device 100 further displays a cursor 522-1 within the electronic document. In some embodiments, the cursor 522-1 is the same as an insertion point. In some embodiments, the insertion point marker is identified by an insertion point marker 522-1.

While document 500 is displayed in a document editing mode, keyboard 521 is also displayed. A user may enter text into document 500 by typing on keyboard 521, and confirm completion of editing of document 500 by performing a touch input (e.g., a tap on “done” button 512) to exit an editing mode.

In some embodiments, the device 100 detects two substantially simultaneous touch inputs at a first region 524-1, 524-2 on the touch screen display 112. The device 100 can further determine that the two substantially simultaneous touch inputs remain in contact with the touch screen display

112, and detect a continuous touch gesture or drag gesture from a location of the two substantially simultaneous touch inputs across the touch screen display from the first region 524-1, 524-2 to a second region 524-3, 524-3. In response to detecting the continuous touch gesture, the device 100 moves the cursor or insertion point marker 522-1 across document 500 from the current location 522-1 in FIG. 5A to a new location 522-2 in FIG. 5B along a path 533 of the continuous gesture.

FIG. 5B illustrates an exemplary user interface brought about by the drag gesture of FIG. 5A, in accordance with some embodiments. In some embodiments, as soon as the device 100 determines that there is a drag gesture (421 of FIG. 4A), it displays a ghost cursor 522-2 offset from the real cursor 522-1. In this embodiment, when the user drags their two-fingers around the screen, both the cursor 522-1 and the ghost cursor 522-2 move together, e.g., the ghost cursor is linked to the actual cursor. The position of this ghost cursor is the position in the document where the actual cursor will be placed when the user lifts their fingers from the screen (e.g., a lift-off event of the two-fingers), e.g., while dragging, the ghost cursor 522-2 moves in the direction of the two-finger drag gesture, and indicates the position where the cursor 522-1 will be dropped or displayed when the user lifts the two fingers. In some embodiments, the ghost cursor 522-2 has a different appearance to the cursor 522-1. For example, the ghost cursor 522-2 can have a different color, size, and/or shape to the cursor 522-1. The ghost cursor 522-2 can also be animated to get the user’s attention. For example, the animation of the cursor 522-1 can include shrinking, enlarging, rotating, blinking, and/or flipping, or the like.

In another embodiment, instead of moving the cursor while dragging two-fingers (e.g., a two-finger slide gesture), the ghost cursor 522-2 moves but not the actual cursor. In some embodiments, a distance between the first region 524-1, 524-2 and the second region 524-3, 524-4 of the touch inputs in FIG. 5A is substantially the same as a distance between the original location of the cursor shown in FIG. 5A and a new location of the cursor shown in FIG. 5B. On release of the two-finger drag, the device 100 places the cursor 522-1 at the location of the ghost cursor 522-2. As a result, upon detecting the termination of the continuous touch gesture, the device 100 ceases display of the ghost cursor 522-2, and the insertion marker 522-3 replaces the ghost cursor 522-2, as shown in FIG. 5C.

The above examples as shown in FIGS. 5A-5C illustrate cursor manipulation in response to detecting a drag gesture when there is no existing selection of content. Referring back to FIG. 4A, if there is existing selection of content in the document (411—Yes) (e.g., a word is selected), then the device 100 determines if the touch inputs are located on the selection at 415. If the device 100 determines that the touch inputs are located on the selection (415—Yes), the device then determines the type of touch input at 417. If the touch input is a drag gesture, then the device 100 dismisses the selection and moves the cursor in a direction of the drag at 433. FIGS. 5D-5E illustrate exemplary user interfaces implementing step 433 in response to a drag gesture.

For example, as shown in FIG. 5D, the device 100 detects a selection of a portion of the content 500 and displays the selection 528. For example, the selection of “ought” from the word “brought” is highlighted as selected. In some embodiments, the device 100 displays markers, such as a start-point object 526 and an end-point object 530 at respective ends of “ought” to indicate the selection 528. The device 100 can detect two substantially simultaneous touch inputs

51

at a first region **524-1** on the touch screen display followed by a continuous touch movement or drag gesture of the two substantially simultaneous touch inputs across the touch screen display from the first region **524-1** to a second region **524-2**. The first region **524-1** is at least partially over the selection **528**. In response to detecting the continuous touch movement or drag gesture, the device **100** dismisses the selection **528** and moves the cursor **522** to a new location as shown in FIG. **5E**. In some embodiments, the new location is at a proximate location of the termination of the two-finger drag.

In some embodiments, in addition to the selection indicators **526-530**, the device **100** displays a command display area adjacent to the selected content **528** as shown in FIG. **5AR** and described in greater detail below. The command display area includes affordances such as an affordance for cutting the selected content **528** and an affordance for copying the selected content **528** (e.g., “Cut” icon **542** and “Copy” icon **544** in FIG. **5AR**). In some embodiments, the command display area is displayed every time text is selected. In some embodiments, when the text is selected by two substantially simultaneous touch inputs, the command display area is not displayed until the device **100** detects a tap on the selected text.

Referring back to FIG. **4A**, in some embodiments, if the device **100** determines that the touch inputs are not on the selection (**415—No**) (e.g., outside the selection), and then determines at **419** that the touch inputs are a drag gesture, then the device **100** expands the selection in accordance with the dragging gesture at **434**.

For example, prior to detecting touch inputs, the device **100** detects an existing selection of a portion of the content and displays the selection. The selection is highlighted, and the device **100** displays markers, such as a start-point object and an end-point object at respective ends of the selection. After displaying a soft keyboard that has a changed appearance in response to detecting two substantially simultaneous touch inputs on the soft keyboard, the device **100** detects a continuous movement of the two substantially simultaneous touch inputs from a first location on the soft keyboard to a second location anywhere on the touch screen display (e.g., within the boundaries of the soft keyboard or beyond the soft keyboard and onto the content region) without breaking contact with the touch screen display. In response to detecting the continuous movement that started on the soft keyboard outside the selected content, the device expands the selected content to include additional content beyond the portion in a direction towards the second location in response to detecting the continuous movement.

In some embodiments, when expanding the selected content, the selection can expand either backward or forward. The initial direction of the drag gesture determines the direction of the expansion. For example, a right and/or down continuous movement moves the end-point object right and/or down without moving the start-point object in order to expand the selection forward; while a left and/or up drag gesture moves the start-point object **530** left and/or up without moving the end-point object in order to expand the selection backward. In some embodiments, the selection expands one word at a time if the continuous movement is fast, and expands one character at a time if the continuous movement is slow.

In some embodiments, in accordance with a determination that the touch inputs are not on the selection (**415—No**) (e.g., outside the selection) and determines at **419** that the

52

touch inputs are a drag gesture, the device **100** dismisses the selection and moves the cursor in a direction of the drag gesture.

FIGS. **5A-5E** above illustrate cursor manipulation in response to detecting a drag gesture. In addition to drag, the device **100** can detect the touch inputs as a flick and perform corresponding actions. As used herein, a flick gesture is the same type of motion as a swipe gesture in that both slides the finger(s) across the touch screen display in one direction. However, different from swipe, a flick gesture is a faster movement across the touch screen display. In some embodiments, the device **100** detects a flick gesture, e.g., a swipe gesture that is performed at a speed higher than a predetermined speed, or an acceleration beyond a predetermined velocity. Referring back to FIG. **4A**, after determining that there is no selection (**411—No**), and that the touch input is a flick gesture, the device **100** moves the cursor to a distal point of line at **430**. If the flick was up or down, the cursor would be moved to the top or bottom of a page or document, respectively. FIGS. **5F-5G** illustrate exemplary user interfaces of moving the cursor to a distal point in the text.

For example, in FIG. **5F**, electronic document **500** includes content, such as text, images, objects, tables, charts, and so on is displayed on the touch screen display **112**. In addition to displaying the content of the electronic document, without detecting any existing selection, the device **100** further displays a cursor **522** within the electronic document. In some embodiments, the cursor **522** is the same as an insertion point. The insertion point marker is identified by an insertion point marker **522** placed between the letter “c” and “e” in the word “conceived”. The device **100** detects a two-finger flick gesture on the touch screen display in a direction **524** towards an edge of the touch screen display as shown, such as a left two-finger flick towards the left edge of the touch screen display **112**. In response to detecting the two-finger left flick gesture, the device **100** moves the cursor **522** to a distal point of the text, as shown in FIG. **5G** where the cursor **522** has been moved to the beginning of the line containing the word “conceived.” If the flick was up or down, the cursor would be moved to the top or bottom of a page or document, respectively. In some embodiments, the two-finger flick gesture detected on the touch screen display **112** is in a direction along the line within the text where the cursor **522** is displayed, and the distal location of the line is at a location in the direction of the two-finger flick. In those embodiments where the flick is vertical, e.g., perpendicular to the line of text, either up or down, the cursor would be moved to the top or bottom of a page or document, respectively.

The above examples as shown in FIG. **5F-5G** illustrate cursor manipulation in response to detecting a flick gesture when there is no existing selection of content. Referring back to FIG. **4A**, on the other hand, if there is existing selection of content detected by the device **100** (**411—Yes**), then the device **100** determines if the touch inputs are located on the selection at **415**. If the device **100** determines that the touch inputs are located on the selection (**415—Yes**), and the device determines at **417** that the touch input is a flick gesture, then the device **100** dismisses the selection and moves the cursor to the distal point (e.g., beginning or end) of the text (e.g., line, page or document) at **444**.

Similarly, if the device **100** determines at **415** that the touch inputs are not on the selection (**415—No**) (e.g., outside the selection), and determines at **419** that the touch input is a flick gesture (also known as a “swipe” gesture), then the selection is again dismissed and the cursor is moved

to the distal point of the text at **445**. FIGS. **5H-5I** illustrate exemplary user interfaces implementing step **445** in response to flick.

For example, as shown in FIG. **5H**, the device **100** detects an existing selection of a portion of the content **500** and displays the selection **528**. The selection of “ought” is highlighted, and the device **100** displays markers, such as a start-point object **526** and an end-point object **530** at respective ends of “ought” to indicate the selection **528**. The device **100** detects a two-finger flick gesture on the touch screen display in a direction **524** towards an edge of the touch screen display. In response to detecting a two-finger left flick gesture, the device **100** dismisses the selection **528** before moving the cursor **522** to a distal point of the text, such as to the beginning of the line where the cursor **522** was initially located, as shown in FIG. **5I**.

Though FIGS. **5F-5I** illustrate cursor manipulation in response to a left flick or swipe, similarly, a right flick or swipe towards right edge of the touch screen display **112**, an up flick or swipe towards top edge of the touch screen display **112**, and a down flick or swipe towards bottom edge of the touch screen display **112** can be detected by the device **100**. In response to the right, up, and down flick or swipe, the device **100** moves the cursor to the end of line, beginning of page, and end of page, respectively.

Referring back to FIG. **4A**, in addition to determining the type of touch inputs as drag and flick, the device **100** can detect the type of touch inputs as tap and perform corresponding actions. After determining the type of the touch inputs is tap and the touch inputs that are not located on a selection, the device **100** selects the closest word to the cursor at **442**. FIGS. **5J-5P** illustrate exemplary user interfaces of selecting the closest word to the cursor in step **442**.

For example, in FIG. **5J**, electronic document **500** is displayed in the user interface of an application (e.g., a word processing application **152**, a presentation application **153**, a spreadsheet application **155**, etc.). The application user interface in which document **500** is displayed may include toolbar **510** and button **512** for navigating to, if any, other documents. Electronic document **500** includes content, such as text, images, objects, tables, charts, and so on. In addition to displaying the content of the electronic document, the device **100** further displays a cursor **522** within the electronic document. In some embodiments, the cursor **522** is the same as an insertion point. The cursor **522** indicates the insertion point in the electronic document **500** as on a word “score”, between the character “s” and “c” of the word “score”.

Subsequently, while displaying the content of the document **500**, and when there is no existing selection (**411—No** of FIG. **4A**), the device **100** detects two substantially simultaneous touch inputs **524** that are not located on a selection (**442** of FIG. **4A**). Turning to FIG. **5K**, in response to detecting the touch inputs, the device **100** determines the touch inputs are not located on a selection, and selects the word “score”, since it is the closest to the cursor **522**. The selection of the word “score” is displayed and highlighted, and the device **100** displays markers, such as a start-point object **526** and an end-point object **530** at respective ends of “score” to indicate the selection **528**.

In some embodiments, a word is selected if the cursor **522** is within the word (e.g., the word “score” in FIGS. **5J-5K**), adjacent to the first letter of the word (e.g., the word “Four” in FIGS. **5L-5M**), or adjacent to the last letter of the word (e.g., the word “forth” in FIGS. **5N-5O**). In some embodiments, the closest word and any punctuation and/or spaces are selected if the cursor **522** is currently located after a

sentence and not within a word or adjacent to the first or last letter of a word (e.g., “equal.” in FIGS. **5P-5Q**).

It should be noted that in FIGS. **5J-5P**, the two substantially simultaneous touch inputs **524** can be located anywhere on the touch screen display, not just where the cursor is located. Conventional portable multifunction devices often require users to precisely contact their fingers on a touch sensitive screen at the location where the cursor is located in order to manipulate the cursor. Such a requirement is cumbersome. The methods described herein allow a user to manipulate a cursor and perform editing functions, such as text selection and moving selection, from any part of the touch-sensitive surface **112**, not just where the cursor is located. For example, the two substantially simultaneous touch inputs **524** can be located after a first paragraph but before a second paragraph (e.g., FIG. **5J**), on a different word not adjacent to the cursor **522** (e.g., FIG. **5L**), on the touch screen keyboard (e.g., FIG. **5N**), or on the word that the cursor is located within (e.g., FIG. **5P**), among others. These methods reduce the number of steps that a user has to perform to navigate and edit a document, thereby increasing efficiency and ease of use when performing these tasks.

The above examples as shown in FIG. **5J-5P** illustrate cursor manipulation in response to detecting tap when there is no existing selection of content. Referring back to FIG. **4A**, on the other hand, if there is an existing selection of content detected by the device **100**, then the device **100** determines if the touch inputs are located on the selection at **415**. If the device **100** determines that the touch inputs are located on the selection (**415—Yes**), and determines at **417** that the touch inputs are a tap, then the device **100** expands the selection at **440**. For example, if a word is selected, and a tap **440** is detected, then the sentence containing the previously selected word is selected. In this way a selection can be expanded from a word to a sentence to a paragraph to a page to a document. In some embodiments, instead of expanding the selection, a single two-finger tap on a selected word deselects the word and returns to an initial cursor placement display (e.g., ceasing display of the selection indication **528** and displaying a cursor on the touch screen display). In some embodiments, the placement of the cursor depends on the location of the single two-finger tap.

On the other hand, if the device **100** determines at **415** that the touch inputs are not on the selection (**415—No**) (e.g., outside the selection) and determines at **419** that the touch inputs are a tap, then the device **100** determines whether the selected content is one word at **466**. In accordance with a determination that the selected content is one word (**466—Yes**), the device **100** expands the selected content to include a sentence containing the word at **467**. On the other hand, in accordance with a determination that the selected content is more than a word, the device **100** displays a cursor at the beginning or end of the selection and dismisses the selection at **468**. In some embodiments, in accordance with a determination that the tap is not on the selection, the device **100** dismisses the selection and selects the closest word to the contact point of the tap.

In other embodiments, after selecting the closest word to the cursor, the device **100** can further detect a two-finger double-tap (e.g., tapping twice with two fingers), a two-finger triple-tap (e.g., tapping three times with two fingers), or a two-finger quadruple-tap (e.g., tapping four times with two fingers). In response to detecting a two-finger double-tap, two-finger triple-tap, or two-finger quadruple-tap, the device **100** expands the selection to a sentence or a line at **460**, to a paragraph at **462**, or to the document at **464**, respectively. In some embodiments, the selection expansion

operation is only operable to paragraph level. For example, in response to a two-finger quadruple-tap, the device 100 keeps the paragraph selected without further expanding the selection to the entire document at 464. In some embodiments, device 100 determines if there is a multi-tap and expands the selection if the duration between each subsequent tap is less than a predetermined threshold (e.g., 0.66 seconds).

In some embodiments, if the device 100 determines two substantially simultaneous touch inputs that are located outside an existing selection (415—No) (e.g., on a soft keyboard) and the type of touch inputs is a tap (down), followed by a lift-off (up), followed by another tap (down), and without lift-off, a drag (419—Tap-±half±drag), the device 100 at step 465 first dismisses the selection, then performs actions similar to those performed at step 471 in FIG. 4B described below, such as selecting a word closest to the touch input and expanding the selection while dragging. In some embodiments, similar to the selection expansion behavior described with respect to steps 452 and 434 above, the initial direction of the drag gesture determines the direction of the expansion and the selection expands one word at a time if the drag gesture moves fast, and expands one character at a time if the drag gesture moves slow.

FIGS. 5R-5S illustrate exemplary user interfaces for implementing a tap that is detected outside a selection and selecting the closest word to a contact point of the tap. FIGS. 5T-5Y illustrate exemplary user interfaces implementing the steps 460-464 (FIG. 4A) of expanding the selection in response to a two-finger double-tap, a two-finger triple-tap, and a two-finger quadruple-tap. FIGS. 5Z-5AD illustrate exemplary user interfaces for implementing step 440 of expanding the selection in response to tapping on a selection.

Turning to FIG. 5R, which illustrates an exemplary user interface of selecting the closest word to a contact point of a two-finger tap in accordance with some embodiments. In some embodiments, an existing selection 528 (e.g., the word “equal”) is detected by the device 100, a cursor is not displayed on the touch screen display. In response to detecting the two substantially simultaneous touch inputs 524 located outside the selection 528 (e.g., on the word “any” in FIG. 5S), the device 100 selects a word closest to the contact location of the two substantially simultaneous touch inputs 524 (e.g., selects the word “any” 528 in FIG. 5S).

FIGS. 5T-5Y illustrate the steps 442 and 460-464 (FIG. 4A) of cursor manipulation in response to two-finger single tap, two-finger double-tap, two-finger triple-tap, and two-finger quadruple-tap, in accordance with an alternative embodiment. When there is no existing selection (411—No) (FIG. 4A), in response to detecting a two-finger tap 524 (FIG. 5T), and when the cursor 522 is located closest to the word “and,” the device 100 selects (442—FIG. 4A) the word “and” and displays markers, such as a start-point object 526 and an end-point object 530 at respective ends of “and” to indicate the selection 528, as shown in FIG. 5U.

In some embodiments, upon determining that there is an existing selection 528 (411—Yes, FIG. 4A), e.g., following the two-finger tap as shown in FIG. 5U, the device 100 detects a two-finger double-tap at a contact point not on the selection (415—No, 419, and 460 of FIG. 4A). In some embodiments, the two-finger double-taps need to be at or near the same contact point on the touch screen display and made within a short predetermined time of one another, e.g., 0.5 seconds. In response to detecting the two-finger double-tap (460 of FIG. 4A), the device 100 selects a first predetermined expanded portion of the content (e.g., a line or a

sentence) that includes at least a portion of the previously selected content 528. For example, the single line of text (“any nation so conceived and so”) containing the word “and” is selected with a start-point object 526 and an end-point object 530 at respective ends of the single line of text selection 528, as shown in FIG. 5V, or the sentence (“Now we are engaged in a great civil war, testing whether that nation, or any nation so conceived and so dedicated, can long endure”) containing the word “and” is selected with a start-point object 526 and an end-point object 530 at respective ends of the sentence selection 528, as shown in FIG. 5W.

In some embodiments, upon determining that there is an existing selection (411—Yes, FIG. 4A), e.g., following the two-finger double-tap to select a line or a sentence shown in FIG. 5V or 5W, the device 100 detects a two-finger triple-tap at a contact point not on the selection (415—No, 419, and 462 of FIG. 4A). In some embodiments, the two-finger triple-taps need to be at or near the same contact point on the touch screen display and made within a short predetermined time of one another, e.g., 0.5 seconds. In response to detecting the two-finger triple-tap (462 of FIG. 4A), the device 100 selects a second predetermined expanded portion of the content (e.g., a paragraph) that includes at least a portion of the previously selected content 528, as shown in FIG. 5X. As further shown in FIG. 5X, to indicate the paragraph selection 528, the device 100 displays the second expanded portion of the content as selected content and displays markers, such as a start-point object 526 and possibly an end-point object (not shown in FIG. 5X) at respective ends of the paragraph selection 528.

In some embodiments, upon determining that there is an existing selection (411—Yes, FIG. 4A), e.g., following the two-finger triple-tap to select a paragraph shown in FIG. 5X, the device 100 detects a two-finger quadruple-tap at a contact point not on the selection (415—No, 419, and 464 of FIG. 4A). In some embodiments, the two-finger quadruple-taps need to be at or near the same contact point on the touch screen display and made within a short predetermined time of one another, e.g., 0.5 seconds. In response to detecting the two-finger quadruple-tap (464 of FIG. 4A), the device 100 selects a third predetermined expanded portion of the content (e.g., a page or document) that includes at least a portion of the previously selected content 528, as shown in FIG. 5Y.

It should be noted that expansion of the selection illustrated in FIGS. 5T-5Y is performed in response to successive touch inputs. FIGS. 5T-5Y illustrate exemplary user interfaces corresponding to the steps 460-464 in FIG. 4A after the device determines that the touch inputs are located outside a selection or not on or over a selection. In some embodiments, the duration between each successive touch input in a multi-tap input is less than a predetermined amount, such as less than 0.25 seconds. For example, a two-finger quadruple-tap is four two finger taps in rapid succession. In response to a two-finger double-tap, the selection is expanded to a sentence or line; In response to a two-finger triple-tap, the selection is expanded to a paragraph; and in response to a two-finger quadruple-tap, the selection is expanded to the page or document.

FIGS. 5Z-5AD are used to illustrate the step 440 (FIG. 4A) of expanding the selection in response to tapping on a selection. After detecting two substantially simultaneous touch inputs at 402 (FIG. 4A), and detecting that there is an existing selection (411—Yes) (FIG. 4A), and determining that the touch inputs were made on or over a selection (415—Yes), the device determines the type of touch inputs that were detected 417 (FIG. 4A). When the device deter-

mines that the touch inputs are a tap over an existing selection, then the existing selection is expanded at 440. This is shown in FIGS. 5Z-5AD. FIG. 5Z shows an existing selection 528 of the word "and" with displayed markers, such as a start-point object 526 and an end-point object (not shown) at respective ends of the word to indicate the selection 528. FIG. 5Z also shows the two substantially simultaneous touch inputs 524 detected as a tap for expanding the selection to the next largest size of selection, e.g., word to line, line to sentence, sentence to paragraph, paragraph to page, page to document, or the like. For example, when the selected content is a word (or a plurality of words that are part of a single line or a sentence), the selected content can be expanded to a single line of text (as shown in FIG. 5AA) or a sentence (as shown in FIG. 5AB) containing the word "and."

In a similar vein, in some embodiments, the device 100 determines that the location of the tap 524 is on a selection 528 of a single line of text (FIG. 5AA) or a sentence (FIG. 5AB). In response to detecting the tap 440 (FIG. 4A), as shown in FIG. 5AC, the device 100 expands the selection 528 to a paragraph containing the single line of text or the sentence. In some embodiments, to indicate the paragraph selection 528, the device 100 displays markers, such as a start-point object 526 and possibly an end-point object 530 (not shown in FIG. 5AC) at respective ends of the paragraph selection 528. In some embodiments, the device 100 can further determine the location of the tap 524 is on a selection 528 of a paragraph (FIG. 5AC). In response, as shown in FIG. 5AD, the device 100 expands the selection 528 to the electronic document. To indicate the document selection 528, the device 100 displays markers, such as a start-point object 526 and possibly an end-point object 530 (not shown in FIG. 5AD) at respective ends of the document selection 528.

It should be noted that the selection expansion in response to successive touch inputs illustrated in FIGS. 5T-5Y is different from the selection expansion illustrated in FIGS. 5Z-5AD. FIGS. 5Z-5AD illustrate exemplary user interfaces corresponding to the step 440 in FIG. 4A after the device 100 determines the touch inputs are located on a selection. In contrast, FIGS. 5T-5Y illustrate exemplary user interfaces corresponding to the steps 460-464 in FIG. 4A after the device determines the touch inputs are located outside a selection or not on or over a selection. As stated with respect to FIGS. 5J-5P above, the two substantially simultaneous touch inputs 524 in FIG. 5T can be located anywhere on the touch screen display 112. In response to the first two-finger tap, a word closest to the cursor is selected, as shown in FIG. 5U. Subsequently each additional two-finger tap on the touch screen display 112 is detected by the device 100. In some embodiments, the duration of each contact is less than a predetermined threshold such that the additional two substantially simultaneous touch inputs can be detected as a two-finger double-tap, two-finger triple-tap, and two-finger quadruple-tap etc. In response to the double-tap, the selection is expanded to a sentence or line; in response to a triple-tap, the selection is expanded to a paragraph; and in response to a quadruple-tap, the selection is expanded to the page or document. In contrast, the device 100 performs the selection expansion as shown in FIGS. 5Z-5AD in response to detecting independent touch inputs on a selection. Thus, the touch inputs illustrates in FIGS. 5Z-5AD are detected by the device 100 as separate touch events, not as successive touch events in a single sequence.

Referring back to FIG. 4A, in addition to determining the type of touch inputs as drag, flick, and tap, the device 100

can detect the type of touch inputs as hold and drag. If the device 100 does not detect an existing selection (411—No), in response to determining 413 the type of touch inputs as hold and drag, the device 100 initiates selecting a portion of the document and extends the selection commensurate with the dragging gesture at 452. To determine if the inputs are a hold and drag gesture as compared to simply a drag gesture, the device determines if the touch inputs remain in contact with the screen without moving for a predetermined period of time (e.g., >0.75 seconds or >1 second) before the drag gesture occurs. In some embodiments, the selection starts at the point of contact and expands in the drag direction.

If the device 100 detects an existing selection (411—Yes), and further determines that the touch inputs are located on an existing selection (415—Yes), and then determines at 417 that the inputs are a hold and drag, then the device 100 moves the selection at 451. In some embodiments, the selected text remains in place with only a cursor moving, and only once the user releases contact with the touch screen surface (e.g., a lift-off event) is the selected text moved to the position of the cursor at the time of the lift-off or release. In other embodiments, the selection is dragged around the document and placed at the position of the selection (or a cursor) at the time of contact release or lift off. In yet another embodiment, a ghost copy of the selection is dragged around the document, while the original selection remains in place, and only placed at the position of the selection (or a cursor) at the time of contact release or lift off.

If the touch inputs are not located on an existing selection (e.g., outside an existing selection) (415—No), the device 100 determines the type of selection at 419, and if the type is a hold and drag 453, expands the existing selection in the direction of the drag gesture at 453. Here, the expanded selection includes the original selection and any expanded portion of the document. FIGS. 5AE-5AG illustrate the step 452 of expanding the selection while dragging. FIGS. 5AH-5AJ illustrate exemplary user interfaces implementing the step 451 of moving an existing selection. FIGS. 5AK-5AL illustrate exemplary user interfaces implementing the step 453 of starting a selection and extending the selection while dragging.

FIGS. 5AE-5AG illustrate the step 452 (FIG. 4A) of expanding the selection while dragging. In FIG. 5AE, the device 100 determines that prior to detecting the two-finger touch inputs, there is no existing selection. In response to detecting the two-finger touch contacts 524, followed by a predetermined period of time, followed by a dragging gesture 532 (FIG. 5AF), the device 100 determines that the inputs are a hold and drag gesture and starts a selection at the cursor 522 and expands it in a direction of the drag gesture 532. For example, the cursor is located between the letters "br" and "ought" and the dragging gesture is in the right direction so expansion of the selection is in the right direction to select "ought" 528. If the dragging continues in a rightward and downward direction, where a release or lift-off event occurs at 531, the selection ("ought forth on this continent . . . in a great") 528 is shown in FIG. 5AG.

FIGS. 5AE-5AG illustrate expanding the selection 528 in accordance with the dragging gesture 532. In some embodiments, the selection can expand either backward or forward. The initial direction of the drag gesture 532 determines the direction of the expansion. For example, a right (e.g., FIG. 5AF) and/or down drag gesture 532 moves the upside down lollipop shaped end-point object 530 right and/or down without moving the lollipop shaped start-point object 526 in order to expand the selection 528 forward; while a left and/or up drag gesture moves the lollipop shaped start-point

object **526** left and/or up without moving the upside down lollipop shaped end-point object **530** in order to expand the selection **528** backward. In some embodiments, the selection **528** expands one word at a time if the drag is fast, and expands one character at a time if the drag is slow.

FIGS. 5AH-5AJ illustrate the step **451** (FIG. 4A) of moving an existing selection. Once the device detects two substantially simultaneous touch inputs at **402** (FIG. 4A), determines that there is an existing selection (**411—Yes**) (FIG. 4A), and determines that the inputs are on a selection (**415—Yes**) (FIG. 4A), then the device determines the type of input at **417** (FIG. 4A). If the type is a hold and drag, as described above, then the selection is moved at **451**. In FIG. 5AH, the device **100** detects two substantially simultaneous touch inputs at a first region **524-1** on the touch screen display. The first region **524-1** is at least partially on or over a location of a selection **528-1**, which may be marked by markers, such as a start-point object **526-1** and an end-point object **530-1** at respective ends of a partial word “ought”. The device **100** further detects the two substantially simultaneous touch inputs remaining motionless on the touch screen display for a predetermined duration followed by a continuous drag gesture (e.g., start dragging within 0.5 or 0.75 seconds after remaining motionless) from the location of the two substantially simultaneous touch inputs in a direction **532** across the touch screen display from the first region **524-1** to a second region **524-2**. In response to detecting the continuous touch movement, the device **100** moves the selection **528-1** across document **500** to a new location **528-2** as shown in FIG. 5AI following the continuous movement.

As mentioned above, in some embodiments, instead of moving the selection **528-1**, a ghost selection **528** is displayed in response to the detection of the two-finger dragging. As shown in FIG. 5AI, in some embodiments, the ghost selection **528-2** is displayed offset from the selection **528-1**, and in some embodiments, the ghost selection **528-2** can have a different appearance to the selection **528-1**. For example, the ghost selection **528-2** can have a different color and/or shade to highlight the ghost selection **528-2** from the color and/or shade used to highlight the selection **528-1**. Further, the ghost markers **526-2** and **530-2** mark the beginning and the ending of the ghost selection block **528** can have different color, size, and/or shape from the markers **526-1** and **528-1**.

In some embodiments, the ghost selection **528-2** appears at location of the current position of the selection **528-1** as soon as the device **100** detects the two-finger dragging, and the start-point object **526-1** and the end-point object **530-1** can animate to attract the users attention to the appearance of the ghost selection **528-2**. While dragging, the ghost selection **528-2** moves in the direction of the two-finger movement to indicate the position to where the selection will be moved when the user lifts or releases the contact (e.g., at the lift-off event). The ghost selection **528-2** may include a ghost start-point object **526-2** and a ghost end-point object **530-2**. Both the ghost start point object **526-2** and the ghost end-point object **530-2** may have different appearances from the start point object **526-1** and the end-point object **530-1**. On release of the two-finger drag, the selection moves to the location of the ghost selection **528-2**. At release of the contacts, the device **100** ceases the display of the ghost selection **528-2** along with the ghost markers **526-2** and **530-2** as shown in FIG. 5AJ. In FIG. 5AJ, the selection **528-3** is indicated by markers, such as a start-point object

**526-3** and an end-point object **530-3**. Other suitable mechanisms for displaying the movement of the selection are described above.

Turning to FIG. 5AK, FIGS. 5AK-5AL illustrate exemplary user interfaces implementing step **453** (FIG. 4A) of starting a selection and extending the selection while dragging, when the hold and drag are not located on an existing selection (e.g., outside an existing selection in the content region or outside the existing selection on the soft keyboard), in accordance with some embodiments. In FIG. 5AK, after detecting two substantially simultaneous touch inputs **524-1** (**402** of FIG. 4A), the device **100** determines that there is an existing selection (**411—Yes**) (FIG. 4A). The device **100** further determines at **415** that the touch inputs are not on the selection (**415—No**) (FIG. 4A) (e.g., outside the selection) and determines at **419** that the touch inputs are hold and drag. In response to determining the type of the touch inputs is a hold and drag, the device **100** expands the existing selection in the direction of the drag gesture at **453**.

For example, as shown in FIG. 5AK, the device **100** detects the two substantially simultaneous touch inputs **524-1** remaining motionless on the touch screen display for a predetermined duration followed by a continuous drag gesture (e.g., start dragging within 0.5 or 0.75 seconds after remaining motionless) from the location of the two substantially simultaneous touch inputs in a direction **532** across the touch screen display from the first region **524-1** to a second region **524-2**. In some embodiments, the drags are detected by the device **100** as a continuous touch movement across the touch screen display from the first location **524-1** to the second location **524-2**.

As shown in FIG. 5AK, an existing selection **528-1** (e.g., the part “ought” of the word “brought”) is detected by the device **100** and a cursor is not displayed on the touch screen display. In some embodiments, while the selection **528** is displayed, the device **100** also display a cursor and the cursor moves in accordance with the drag gesture. In response to detecting the two substantially simultaneous touch inputs **524-1** located outside the selection **528** (e.g., located below the selection “ought” in FIG. 5AK), the device **100** expands the original selection **528-1** in the direction of the drag gesture **532**. In FIG. 5AK, the dragging gesture is in the rightward and downward direction towards **524-2**. As a result, the expansion of the selection **528-1** is in the right and downward direction. When a release or lift-off event occurs at **524-2**, the selection (“ought forth on this continent . . . in a great”) **528** is shown in FIG. 5AL. In FIG. 5AL, the selection **528** is indicated by markers, such as a start-point object **526** and an end-point object **530**.

FIGS. 5AK-5AL illustrate expanding the selection in accordance with the continuous touch movement **532**. In some embodiments, the selection can expand either backward or forward. The initial direction of the drag gesture **532** determines the direction of the expansion. For example, a right and/or down (as shown in FIG. 5AK) drag gesture **532** moves the upside down lollipop shaped end-point object **530** right and/or down without moving the lollipop shaped start-point object **526** in order to expand the selection **528** forward; while a left and/or up dragging gesture moves the lollipop shaped start-point object **526** left and/or up without moving the upside down lollipop shaped end-point object **530** in order to expand the selection **528** backward. In some embodiments, the selection **528** expands one word at a time if the drag is fast, and expands one character at a time if the drag is slow.

FIG. 4B is a flow chart illustrating a method **470** of cursor manipulation with a single touch input (e.g., a single-finger

touch input), in accordance with some embodiments. The method **470** is performed at a portable multifunction device (e.g., the device **100** in FIG. **1A**) with a touch screen display (e.g., the touch screen display **112** in FIG. **1A**). As described below, the method **470** provides an expedient mechanism for moving the cursor, selecting the content, and providing options to edit the content at a portable multifunction device with a touch screen display. This method is both faster and easier to perform than using a peripheral device, like a mouse. The method is also intuitive to a user, thereby reducing the number, extent, and/or nature of the inputs from the user when selecting content, and creating a more efficient human-machine interface. A more efficient input mechanism also requires less computing resources, thereby increasing battery life of the device.

In some embodiments, the device **100** displays content of an electronic document on the touch screen display **112**. In some embodiments, the content comprises text (e.g., plain text, unstructured text, formatted text, or text in a web page). In other embodiments, the content comprises graphics with or without text. Moreover, the content may be editable or read-only. In addition to displaying the content, when no content is selected, the device **100** may display a cursor within the electronic document. In some embodiments, while displaying the content of the electronic document, the device **100** detects a single-finger touch input (e.g., a single-finger tap) at **472**. The portable multifunction device **100** then determines whether prior to detecting the touch input, there is an existing selection of the content at **474**.

If the device **100** detects an existing selection (**474—Yes**), then the device **100** further determines if the single-finger touch input is located on the selection at **475**. If the device **100** determines that the single-finger touch input is not located on the selection (**475—No**), then device **100** dismisses the selection at **476** and proceeds to step **480**. On the other hand, if the device **100** determines that the single-finger touch input is located on the selection (**475—Yes**), the device **100** determines the type of the touch input at **477**.

If the device **100** determines the type of single-finger touch input is tap (down), lift (up), tap (down), and a drag (**477—Tap±half±drag**), the device **100** at **487** first dismisses the selection, then performs actions similar to those performed at step **471**, such as selecting a word closest to the touch input and expanding the selection while dragging. If the device **100** determines the type of single-finger touch input is a tap (**477—Tap**), then the device **100** can perform one of three different options depending on embodiment.

In some embodiments, one of the options (Tap Option 3, **489**) is to do-nothing, such that the device **100** does not respond to the single-finger tap in accordance with a determination that the tap is located on a selection (e.g., a selected word). In some embodiment, another option includes dismissing the selection at **485** (Tap Option 1) and performing additional actions (e.g., steps **481-484** in FIG. **4B**) in response to the tap gesture as if there were no existing selection. In some embodiments, a third option is to dismiss the selection and place the cursor adjacent to a word within the electronic document based on the location of the single-finger input relative to the closest space to this word at **479** (Tap Option 2). With respect to this embodiment, if the single-finger touch input is on a word and the contact location of the single-finger touch input is closer to the beginning of the word, then the device **100** places the cursor before the word, since the closest space to this word is the white space before the word. Conversely, if the single-finger touch input is on a word and the contact location of the single-finger touch input is closer to the end of the word,

then the device **100** places the cursor after the word, since the closest space to this word is the white space after the word.

For example, FIGS. **5AM-5AN** illustrate step **479** (Tap Option 2, FIG. **4B**) of dismissing a selection and moving the cursor in response to detecting an existing selection and a single-finger tap on the selection. In FIG. **5AM**, the device **100** detects a single-finger tap at a region **524** on the touch screen display **112**. The region **524** is at a proximate location of the contact point of the single finger tap to the touch screen display **112**, such as located on the word “brought”, closer to the end of the word. As shown in FIG. **5AM**, the region **524** is on the selection **528**, which may be marked by markers, such as a start-point object **526** and an end-point object **530** at respective ends of a partial word “ought”. In response to detecting the single-finger tap **524** outside the selection **528**, the device **100** dismisses the selection and moves to the cursor to the closest white space before the word “brought”, as shown in FIG. **5AN**.

It should be noted that FIGS. **5AM-5AN** illustrate dismissing selection in response to tapping on an existing selection of editable text in accordance with some embodiments. In some embodiments, similar actions are performed when tapping on an existing selection of non-editable text (e.g., a web page), such that the existing selection is deselected.

Still referring to FIG. **4B**, the above steps are performed when the device **100** detects an existing selection. When there is no existing selection (**474—No**), the device **100** first determines the type of the single-finger touch input at **480**. In response to recognizing a tap gesture (**480—Tap**), the device **100** determines a distance to the closest space between two words within the electronic document at **481**. In accordance with a determination that the distance is less than a predetermined threshold distance (**483—Yes**), the device **100** moves the cursor to the closest space after a preceding word at **482**. In accordance with a determination that the distance is more than a predetermined threshold distance (**483—No**), the device **100** selects the word closest to the touch input and displays an indication of the selection on the touch screen at **484**.

For example, FIGS. **6A-6B** illustrate step **482** (FIG. **4B**) of moving cursor in response to a tap gesture, in accordance with some embodiments. In FIG. **6A**, content of an electronic document is displayed on the touch screen display **112**. The content includes at least one line of text, which further includes at least two words. Based on the distance to the closest white space between two words within the electronic document, the device **100** defines zones (e.g., X zones and Y zone) for each word. In some embodiments, X zones are defined as zones from the beginning or end of a word to a distance less than or equal to a percentage of the word size. In some embodiments, the Y zone is the zone between X-zones for that word, e.g., where the distance to the closest white space is greater than or equal to a percentage of the word size.

For example, in FIG. **6A**, the word “Lorem” is the first word in a line of text. The closest white space is the white space between the word “Lorem” and “ipsum”. As shown in FIG. **6A**, X1 starts from the end of the word “Lorem” to a distance less than or equal to a percentage of the word size (e.g., between the letter “e” and the letter “m” of “Lorem”). Within Y1, the distance to the closest white space is greater than or equal to a percentage of the word size “Lorem”. Similarly, X2-X6 start from the beginning/end of a word to a distance less than or equal to a percentage of the word size,

and within Y2-Y4, the distance to the closest white space is greater than or equal to a percentage of the word size.

In FIG. 6A, the device 100 detects a single-finger tap 524 on the touch screen display 112. The single-finger tap 524 is located approximately on the letter “m” of the word “ipsum” in X3. The closest white space to the single-finger tap 524 is the space between the word “ipsum” and the word “dolor”. As a result of detecting the distance from the single-finger tap 524 to the closest white space between words less than a predetermined threshold distance (e.g., the distance from the touch input to the end of the word is less than X3), the device 100 places the cursor in the closest space after a preceding word (e.g., after “ipsum”), as shown in FIG. 6B.

In another example, FIGS. 5AO-5AP illustrate step 482 (FIG. 4B) of moving the cursor when tapping on white space in between two words. In FIG. 5AO, the device 100 detects a single-finger tap at a region 524 on the touch screen display 112. Different from the existing selection scenario as shown in FIGS. 5AM-5AN, there is no existing selection prior to the single-finger tap at the region 524. Instead, a cursor 522-1 is displayed in the middle of the word “brought.” In FIG. 5AO, the region 524 indicates the contact point of the single-finger tap to the touch screen display is at a proximate location of the space between two paragraphs. In response to detecting the single-finger tap 524 not located on a word, the device 100 moves the cursor to the contact point 522-2 as shown in FIG. 5AP, in between two paragraphs right after a preceding word (e.g., right after “equal.”).

In yet another example, FIGS. 5AQ-5AR illustrate steps 484 (FIG. 4B) when a single-finger tap is located on a word. In FIG. 5AQ, similar to FIG. 5AO, there is no existing selection prior to the single-finger tap at the region 524. Instead, a cursor 522 is displayed in the middle of the word “brought.” Different from FIG. 5AO, in FIG. 5AQ, the region 524 indicates the contact point of the single-finger tap to the touch screen display is located on a word “conceived”, approximately in the middle (e.g., in a Y zone). As a result of the distance to the closest white space between words (e.g., the white space between the word “nation,” and the word “conceived”) greater than a predetermined threshold distance, the device 100 selects the word “conceived” and displays the selection as shown in FIG. 5AR. The selection is marked by The word “conceived” shown in the exemplary user interface is long enough for the device 100 to recognize the touch input located in a Y zone. In some embodiments, for short words, e.g., “as”, “do”, “I”, due to the small size of a Y zone for such short words, the device 100 will always place the cursor and not select the word.

In FIG. 5AR, the selection 528 may be marked by markers as an indication of the selection 528, such as a start-point object 526 and an end-point object 530 at respective ends of a partial word “conceived.” In addition, the device 100 displays a command display area 540 adjacent to the selected content 528. The command display area 540 includes an affordance for cutting the selected content 528 and an affordance for copying the selected content 528 (e.g., “Cut” icon 542 and “Copy” icon 544 in FIG. 5AR). In some embodiments, the command display area 540 includes an affordance for pasting previously cut or copied content (e.g., “Paste” icon 546). Though not shown in FIG. 5AR, in some embodiments, the command display area 540 includes an affordance for undoing a previous action, an affordance for displaying additional command options, an affordance redoing a previous action, at least one command that is user

configurable, an affordance for defining the word, and/or at least one command that is context sensitive, among others.

The above examples (FIGS. 6A-6B, 5AO-5AP, and 5AQ-5AR) illustrate various operations performed in response to a single-finger tap on editable content. In some embodiments, in accordance with a determination that the content is editable text, the device 100 displays a cursor in the content displays a soft keyboard for text editing.

Referring back to FIG. 4B, if the device 100 determines (at 480) the type of single-finger touch input is hold and drag, the device 100 displays a loupe and moves the cursor at 473. FIG. 6C illustrates an exemplary user interface of cursor movement in response to a hold and drag gesture, in accordance with some embodiments.

As used herein, a hold and drag gesture is a stationary (or substantially stationary) pressing gesture by a single-finger at a location in the content displayed on the touch screen immediately followed by a drag. For example, a single-finger contact that moves less than a predefined amount (e.g., 1-2 mm) in a predefined time (e.g., 0.2-0.5 seconds) immediately followed by a drag is a hold and drag gesture. In response to recognizing the hold and drag gesture, as shown in FIG. 6C, the device 100 magnifies a portion of the content proximate to the contact location 524 on the touch screen 112. The content magnifier 508 displays the magnified portion 543 of the content as well as an insertion marker 545. The insertion marker 545 is displayed at a location within the expanded portion of the content that corresponds to the contact location of the single-finger. In some embodiments, in response to detecting a movement 532 of the single-finger across the touch screen 112, the device 100 moves the content magnifier 508, moves the insertion marker 545, and changes the magnified portion 543 of the content in accordance with the detected movement of the single-finger.

Although not shown in FIG. 4B, in some embodiments, if the device 100 determines the type of single-finger touch input is hold and drag and the touch input is located on a selection, the device 100 moves the selection. For example, FIGS. 5AS-5AU illustrate step 479 (FIG. 4B) of moving a selection when the device 100 detects a hold and drag gesture located on a selection. In FIG. 5AS, the device 100 detects a single-finger touch input at a first region 524-1 on the touch screen display 112. The first region 524-1 is at least partially on or over a location of a selection 528-1, which may be marked by markers, such as a start-point object 526-1 and an end-point object 530-1 at respective ends of a partial word “ought.” The device 100 further detects the single-finger touch input remains motionless on the touch screen display for a predetermined duration followed by a continuous drag gesture (e.g., start dragging within 0.5 or 0.75 seconds after remaining motionless) from the location of the single-finger touch input in a direction 532 across the touch screen display from the first region 524-1 to a second region 524-2. In response to detecting the continuous touch movement, the device 100 moves the selection 528-1 across document 500 to a new location 528-2 as shown in FIG. 5AU following the continuous movement.

As mentioned above, in some embodiments, instead of moving the selection 528-1, a ghost selection 528 is displayed in response to the detection of the single-finger dragging. As shown in FIG. 5AT, in some embodiments, the ghost selection 528-2 is displayed offset from the selection 528-1, and in some embodiments, the ghost selection 528-2 can have a different appearance to the selection 528-1. For example, the ghost selection 528-2 can have a different color and/or shade to highlight the ghost selection 528-2 from the

color and/or shade used to highlight the selection **528-1**. Further, the ghost markers **526-2** and **530-2** mark the beginning and the ending of the ghost selection block **528** can have different color, size, and/or shape from the markers **526-1** and **528-1**.

In some embodiments, the ghost selection **528-2** appears at location of the current position of the selection **528-1** as soon as the device **100** detects the single-finger dragging, and the start-point object **526-1** and the end-point object **530-1** can animate to attract the users attention to the appearance of the ghost selection **528-2**. While dragging, the ghost selection **528-2** moves in the direction of the single-finger movement to indicate the position to where the selection will be moved when the user lifts or releases the contact (e.g., at the lift-off event). The ghost selection **528-2** may include a ghost start-point object **526-2** and a ghost end-point object **530-2**. Both the ghost start point object **526-2** and the ghost end-point object **530-2** may have different appearances from the start point object **526-1** and the end-point object **530-1**. On release of the single-finger drag, the selection moves to the location of the ghost selection **528-2**. At release of the contacts, the device **100** ceases the display of the ghost selection **528-2** along with the ghost markers **526-2** and **530-2** as shown in FIG. 5AU. In FIG. 5AU, the selection **528-3** is indicated by markers, such as a start-point object **526-3** and an end-point object **530-3**. Other suitable mechanisms for displaying the movement of the selection are described above.

Referring back to FIG. 4B, if the device **100** determine (at **480**) that the single-finger touch input is tap±half±drag, the device **100** selects a word closest to the touch input and expands the selection while dragging at **471**. As used herein, a tap±half±drag gesture is a gesture that includes an initial touch input followed immediately (e.g., within a predefined time period such as 0.3-0.5 seconds) by an additional touch input on the touch screen display that subsequently moves on the touch screen display without breaking contact with the touch screen display. The move is a continuous touch gesture from a first location of the additional touch input on the touch screen display to a second location on the touch screen display.

Still referring to FIG. 4B, if the device **100** determines (at **480**) that the single-finger touch input is a drag gesture, the device **100** scrolls the content displayed in the content region of the touch screen display **112** in accordance with the direction of the drag at **488**. For example, an upward drag scrolls the content upward, a downward drag scrolls the content downward, a left drag scrolls the content to the left, and likewise, a right drag scrolls the content to the right.

In some embodiments, similar to scrolling in response to a drag gesture, the device **100** scrolls the content displayed in the content region in response to a swipe gesture in accordance with the direction of the swipe. For example, an upward swipe scrolls the content upward, a downward swipe scrolls the content downward, a left swipe scrolls the content to the left, and likewise, a right swipe scrolls the content to the right.

FIGS. 6D-6E illustrate exemplary user interfaces of expanding a selection while dragging in response to a tap±half±drag gesture, in accordance with some embodiments. The user interfaces in these figures illustrate steps **476** and **471** (FIG. 4B). In FIG. 6D, the device **100** detects a single-finger touch input **524-1**. Upon detecting the single-finger touch input **524-1**, the device **100** determines that there is an existing selection **528** (e.g., the word “testing”). The selection **528** is marked by markers, such as a start-point object **526** and an end-point object **530** at respective ends of

the selection **528**. The device **100** further determines that the single-finger touch input is not located on the existing selection **528** (e.g., on the word “nation”), and dismisses the existing selection **528**. The device **100** then determines that the single-finger touch input is a tap-a-half-and-drag gesture. The dragging part of the tap-a-half-and-drag gesture starts from a first location **524-1** to a second location **524-2** in a direction **532** of the dragging.

In response to the tap±half±drag gesture, the device **100** selects the word closest to the starting location **524-1** (e.g., selecting the word “nation”), then expands the selection to include additional content beyond the selected word in the direction **532** towards the second location **524-2**. The end of the selected portion of the content **530** is increased as the finger contact moves forward through text on the touch screen **112**, as illustrated in FIG. 6E, while the beginning of the selected portion of the content **526** remains fixed (e.g., the beginning of the word “nation”).

In some embodiments, the start-point object **526** and the end-point object **530** are displayed moving while the finger is dragging to indicate the expanding selection **528**. The selection **528** expands one word at a time if the finger drags fast, and expands one character at a time if the finger drags slow. Though not shown in FIGS. 6D-6E, in some embodiments, whenever text is selected, the device **100** displays a command display area adjacent to the selected portion of the content to facilitate editing functions such as cut, copy, paste etc. An exemplary command display area displayed adjacent to a selected portion of the content is shown in FIG. 5AR and described in greater detail above with respect to FIG. 5AR.

In some embodiments, as shown in FIG. 6E, the device **100** displays a content magnifier **552** adjacent to the respective end of the selected content. The content magnifier **552** displays: an expanded portion **588** of the content proximate to the respective end of the selected content, and a boundary marker **554** that denotes a current position of the respective end of the selected content **528**. In some embodiments, the expanded portion **558** of the content displayed by the content magnifier **552** includes selected content adjacent to the respective end (e.g., “ves tha” in FIG. 6E) and unselected content adjacent to the respective end (e.g., “t that” in FIG. 6E).

Referring back to FIG. 4B, in some embodiments, if the device **100** determines the type of single-finger touch input is double-tap, triple-tap, quadruple-tap, or 5th-tap (**480**—double/triple/4th/5th-Tap). In response to recognizing the multi-tap gesture, the device **100** selects a word closest to the touch input in response to a double-tap, and for each successive tap, the device **100** expands the selection with each successive tap at **478**.

For example, in FIG. 6F, in response to detecting a single-finger double-tap touch input, the device **100** selects a word closest to the double-tap touch input (e.g., the word “and”). As shown in FIG. 6G, the word “and” is selected and an indication of the selection **528** is displayed and enclosed with a start-point object **526** and an end-point object **530**. In case the single-finger touch input is a triple-tap, quadruple-tap, or 5th-tap, in response to detecting the touch input, the device **100** expands the selection, selects a sentence (e.g., the sentence “any nation so conceived and so” in FIG. 6H), a paragraph (e.g., the paragraph of “Now we are engaged in a great civil war . . .” in FIG. 6I), or the content of the electronic document (FIG. 6J) respectively and the respective selection **528** is displayed with an indication **528** and enclosed with a start-point object **526** and an end-point object **528**.

It should be noted that different from in response to a single-tap gesture described above with respect to FIGS. 6A-6B, in some embodiments, even though the distance between the double-tap and the closest white space is less than a predetermined threshold distance (e.g., in X zone), in response to detecting a double-tap, the device 100 selects the word closest to the double-tap touch input (e.g., the word “and”). Furthermore, different from in response to a single-tap gesture described above with respect to FIGS. 5A0-5A9, in some embodiments, in response to detecting a double-tap located on a white space between two words within the electronic document, the device 100 selects the word following the white space and displays an indication of the selection. Additionally, in some embodiments, when the double-tap is located on the cursor 522, the device 100 selects the word connected to the cursor and displays an indication of the selection. Exemplary indication of the selection is shown in FIG. 6G and described above.

In some embodiments, the device 100 can alternatively move the selected content in response to detecting three substantially simultaneous touch inputs, e.g., a three-finger touch input. FIG. 4C is a flow chart illustrating a method 490 of content movement with three substantially simultaneous touch inputs (e.g., a three-finger touch input), in accordance with some embodiments. The method 490 is performed at a portable multifunction device (e.g., the device 100 in FIG. 1A) with a touch screen display (e.g., the touch screen display 112 in FIG. 1A). As described below, the method 490 provides an expedient mechanism for moving the selected content at a portable multifunction device with a touch screen display.

Similar to the illustration in FIGS. 5AS-5AU, in some embodiments, the device 100 first displays content of an electronic document on the touch screen display 112. In some embodiments, the content comprises text (e.g., plain text, unstructured text, formatted text, or text in a web page). In other embodiments, the content comprises graphics with or without text. Moreover, the content may be editable or read-only. In some embodiments, while displaying the content of the electronic document, the device 100 detects three substantially simultaneous touch inputs (e.g., a three-finger tap) at 492. The portable multifunction device 100 then determines whether prior to detecting the touch input, there is an existing selection of the content at 494. If the device 100 detects an existing selection (494—Yes), then the device 100 moves the selection at 496 in response to a hold and drag gesture of the three-finger.

It should be noted that the three substantially simultaneous touch inputs can be located anywhere on the touch screen display 112. For example, a user can touch the touch screen display 112 with three fingers close together or three fingers spread out. Regardless the three touch inputs locations on the touch screen display 112, the device 100 can detect the three substantially simultaneous touch inputs and perform actions such as moving a selection in response to detecting a drag of the three-fingers following the initial three substantially simultaneous touch inputs.

It should also be noted that different from the single-finger hold and drag of a selection as illustrated in FIGS. 5AS-5AU, in some embodiments, the three substantially simultaneous touch inputs are not necessarily located on the selection. As illustrated in FIGS. 5AV-5AX and described below, the three substantially simultaneous touch inputs can be located outside a selection, on or over a selection, or even on the keyboard.

For example, FIGS. 5AV-5AX illustrate step 496 (FIG. 4C) of moving a selection in response to the device 100

detecting a hold and drag gesture of the three-finger. In FIG. 5AV, the device 100 detects a three-finger touch input at a first region 524-1 on the touch screen display 112. The first region 524-1 can be located anywhere on the touch screen display 112. As shown in FIG. 5AV, the three-finger touch input can be located outside a selection 528-1, which may be marked by markers, such as a start-point object 526-1 and an end-point object 530-1 at respective ends of a partial word “ought”. Though not shown in FIG. 5AV, the three-finger touch input can be partially on or over a location of the selection 528-1, or even on the keyboard 521.

In some embodiments, the device 100 further detects the three-finger touch input remains motionless on the touch screen display for a predetermined duration followed by a continuous drag gesture (e.g., start dragging within 0.5 or 0.75 seconds after remaining motionless) from the location of the three-finger touch input in a direction 532 across the touch screen display from the first region 524-1 to a second region 524-2. In other embodiments, a delay (e.g., the predetermined duration, is not required for moving the selection.

In response to detecting the continuous touch movement, the device 100 moves the selection 528-1 across document 500 to a new location 528-2 as shown in FIG. 5AX following the continuous movement.

As mentioned above, in some embodiments, instead of moving the selection 528-1, a ghost selection 528 is displayed in response to the detection of the single-finger dragging. As shown in FIG. 5AW, in some embodiments, the ghost selection 528-2 is displayed offset from the selection 528-1, and in some embodiments, the ghost selection 528-2 can have a different appearance to the selection 528-1. For example, the ghost selection 528-2 can have a different color and/or shade to highlight the ghost selection 528-2 from the color and/or shade used to highlight the selection 528-1. Further, the ghost markers 526-2 and 530-2 mark the beginning and the ending of the ghost selection block 528 can have different color, size, and/or shape from the markers 526-1 and 528-1.

In some embodiments, the ghost selection 528-2 appears at location of the current position of the selection 528-1 as soon as the device 100 detects the three-finger dragging, and the start-point object 526-1 and the end-point object 530-1 can be animated to attract the user’s attention to the appearance of the ghost selection 528-2. While dragging, the ghost selection 528-2 moves in the direction of the three-finger movement to indicate the position to where the selection will be moved when the user lifts or releases the contact (e.g., at the lift-off event). The ghost selection 528-2 may include a ghost start-point object 526-2 and a ghost end-point object 530-2. Both the ghost start point object 526-2 and the ghost end-point object 530-2 may have different appearances from the start point object 526-1 and the end-point object 530-1. On release of the three-finger drag, the selection moves to the location of the ghost selection 528-2. At release of the contacts, the device 100 ceases the display of the ghost selection 528-2 along with the ghost markers 526-2 and 530-2 as shown in FIG. 5AX. In FIG. 5AX, the selection 528-3 is indicated by markers, such as a start-point object 526-3 and an end-point object 530-3. Other suitable mechanisms for displaying the movement of the selection are described above.

It should be understood that the particular order in which the operations in FIGS. 4A-4C have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would

recognize various ways to reorder the operations described herein. For brevity, these details are not repeated here.

In accordance with some embodiments, FIG. 8 shows a functional block diagram of an electronic device 800 configured in accordance with the principles of the invention as described above. The functional blocks of the device may be implemented by hardware, software, or a combination of hardware and software to carry out the principles of the invention. It is understood by persons of skill in the art that the functional blocks described in FIG. 8 may be combined or separated into sub-blocks to implement the principles of the invention as described above. Therefore, the description herein may support any possible combination or separation or further definition of the functional blocks described herein.

In some embodiments, the electronic device 800 includes a display unit 802 configured to display content of an electronic document and a cursor within the electronic document; a touch-sensitive surface unit 804 configured to receive user contacts; and a processing unit 808 coupled to the display unit 802 and the touch-sensitive surface unit 804. In some embodiments, the processing unit 808 includes a detecting unit 810 and a selecting unit 812.

The processing unit 808 is configured to: detect two substantially simultaneous touch inputs anywhere on the touch-sensitive surface unit 804 (e.g., with the detecting unit 810); and in response to detecting the two substantially simultaneous touch inputs: select a portion of the content in the document closest to the cursor (e.g., with the selecting unit 812); and display the portion of the content as selected content (e.g., with the display unit 802).

In some embodiments, the electronic device 800 includes the display unit 802 configured to display content of an electronic document and a cursor at a current location within the content; the touch-sensitive surface unit 804 configured to receive user contacts; and the processing unit 808 coupled to the display unit 802 and the touch-sensitive surface unit 804. In some embodiments, the processing unit 808 includes the detecting unit 810, a determining unit 816, and a moving unit 814.

The processing unit 808 is configured to: detect two substantially simultaneous touch inputs at a first region on the touch-sensitive surface unit 804 (e.g., with the detecting unit 810); upon determining that the two substantially simultaneous touch inputs remain in contact with the touch-sensitive surface unit 804 (e.g., with the detecting unit 810), detect a continuous touch gesture from a location of the two substantially simultaneous touch inputs across the touch-sensitive surface unit 804 (e.g., with the detecting unit 810) from the first region to a second region; and in response to detecting the continuous touch gesture: move the cursor from the current location to a new location in a direction of the continuous touch gesture (e.g., with the moving unit 814).

In some embodiments, the electronic device 800 includes the display unit 802 configured to display text and a cursor at a line within the text; the touch-sensitive surface unit 804 configured to receive user contacts; and the processing unit 808 coupled to the display unit 802 and the touch-sensitive surface unit 804. In some embodiments, the processing unit 808 includes the detecting unit 810 and the moving unit 814.

The processing unit 808 is configured to: detect a two-finger swipe gesture on the touch-sensitive surface unit 804 (e.g., with the detecting unit 810) in a direction at least partially parallel to the line and towards an edge of the touch-sensitive surface unit 804 (e.g., with the detecting unit

810); and in response to detecting the two-finger swipe gesture: move the cursor to a distal point of the text (e.g., with the moving unit 814).

In some embodiments, the electronic device 800 includes the display unit 802 configured to display content of an electronic document and a cursor within the electronic document; the touch-sensitive surface unit 804 configured to receive user contacts; and the processing unit 808 coupled to the display unit 802 and the touch-sensitive surface unit 804. In some embodiments, the processing unit 808 includes the detecting unit 810 and the selecting unit 812.

The processing unit 808 is configured to: detect a touch input on the touch-sensitive surface unit 804 (e.g., with the detecting unit 810), wherein the touch input is located on a word within the content; and in response to detecting the touch input: select the word (e.g., with the selecting unit 812); and display a command display area adjacent to the selected word, wherein the second command display area includes an icon for cutting the selected word, an icon for copying the selected word, and an icon for pasting a previously selected content.

In some embodiments, the electronic device 800 includes the display unit 802 configured to display content of an electronic document and a selection of the content within the electronic document; the touch-sensitive surface unit 804 configured to receive user contacts; and the processing unit 808 coupled to the display unit 802 and the touch-sensitive surface unit 804. In some embodiments, the processing unit 808 includes the detecting unit 810, the determining unit 816, and the moving unit 814.

The processing unit 808 is configured to: detect a single touch input on the touch-sensitive surface unit 804 (e.g., with the detecting unit 810) at a location over the selection; in response to detecting the single touch input at the location, display a set of options related to the selection (e.g., with the display unit 802); determine if the single touch input remains at the location for a predetermined amount of time followed by a continuous touch gesture away from the location on the touch-sensitive surface unit 804 (e.g., with the determining unit 816); and in response to detecting the single touch input remaining at the location for the predetermined amount of time followed by the continuous touch gesture away from the location, move the selection to a different location in a direction of the continuous touch gesture (e.g., with the moving unit 814).

In some embodiments, the electronic device 800 includes the display unit 802 configured to display content of an electronic document and a selection of the content within the electronic document; the touch-sensitive surface unit 804 configured to receive user contacts; and the processing unit 808 coupled to the display unit 802 and the touch-sensitive surface unit 804. In some embodiments, the processing unit 808 includes the detecting unit 810, the determining unit 816, and the moving unit 814.

The processing unit 808 is configured to: detect three substantially simultaneous touch inputs at locations anywhere on the touch-sensitive surface unit 804 (e.g., with the detecting unit 810); determine if the three substantially simultaneous touch inputs is followed by three continuous touch gestures away from the locations on the touch-sensitive surface unit 804 (e.g., with the determining unit 816); and in response to detecting the three continuous touch gestures, move the selection to a different location in a direction of the continuous touch gestures (e.g., with the moving unit 814).

In some embodiments, the electronic device 800 includes the display unit 802 configured to display content of an

71

electronic document, the content includes at least one line of text comprising at least two words; the touch-sensitive surface unit **804** configured to receive user contacts; and the processing unit **808** coupled to the display unit **802** and the touch-sensitive surface unit **804**. In some embodiments, the processing unit **808** includes the detecting unit **810**, the determining unit **816**, and the selecting unit **812**.

The processing unit **808** is configured to: detect a touch input on the content (e.g., with the detecting unit **810**); and in response to detecting the touch input: determine a distance of the touch input to a closest space between the two words within the electronic document (e.g., with the determining unit **816**); and in accordance with a determination that the distance is greater than a predetermined threshold distance, select a word within the electronic document closest to the touch input and display the selection (e.g., with the display unit **802**).

In some embodiments, the electronic device **800** includes the display unit **802** configured to display content of an electronic document and a soft keyboard in focus; the touch-sensitive surface unit **804** configured to receive user contacts; and the processing unit **808** coupled to the display unit **802** and the touch-sensitive surface unit **804**. In some embodiments, the processing unit **808** includes the detecting unit **810** and the changing appearance unit **818**.

The processing unit **808** is configured to: detect two substantially simultaneous touch inputs on the soft keyboard (e.g., with the detecting unit **810**); and in response to detecting the two substantially simultaneous touch inputs on the soft keyboard, blur the soft keyboard (e.g., with the changing appearance unit **818**).

In some embodiments, the electronic device **800** includes the display unit **802** configured to display content of an electronic document and a cursor within the electronic document; the touch-sensitive surface unit **804** configured to receive user contacts; and the processing unit **808** coupled to the display unit **802** and the touch-sensitive surface unit **804**. In some embodiments, the processing unit **808** includes the detecting unit **810** and the changing appearance unit **818**.

The processing unit **808** is configured to: display, on the touch-sensitive surface display unit **802**, a soft keyboard having multiple keys each having a respective alphanumeric character of a plurality of alphanumeric characters; detect two substantially simultaneous touch inputs on the soft keyboard (e.g., with the detecting unit **810**); and in response to detecting the two substantially simultaneous touch inputs on the soft keyboard, change the appearance of the soft keyboard to a changed appearance (e.g., with the changing appearance unit **818**).

Turning to FIGS. 9A-9AD, these figures illustrate exemplary user interfaces for selecting content, moving a text selection indicator, and changing keyboard appearance based on contact intensity (e.g., pressure), in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below with respect to FIGS. 10A-10G and 11A-11F. FIGS. 9B-9AD include intensity versus time diagrams that show the current intensity of the contact on the touch-sensitive surface relative to a plurality of intensity thresholds (e.g., “ $IT_D$ ”, “ $IT_L$ ”, and “ $IT_0$ ”).

FIGS. 9A-9N illustrate exemplary user interfaces for selecting content in a text selection mode in response to a deep press on an onscreen keyboard in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below with respect to FIGS. 10A-10G.

72

In FIG. 9A, editable content **900** is displayed in a content presentation region **902** while an application is in a document editing mode. The application runs on a device **100** that has one or more sensors (e.g., contact intensity sensor(s) **259**, FIG. 2B) to detect intensity of contacts with the touch-sensitive display. In the document editing mode, an onscreen keyboard **921** is displayed for text inputs. A user may enter text by touch inputs (e.g., by contact) on the onscreen keyboard **921** and confirm completion of the editing by performing another touch input (e.g., a tap on “done” button) to exit the editing mode. An insertion marker (e.g., cursor **922**) is displayed to indicate a current location for text inputs.

In FIG. 9B, at time  $T_1$ , while in the editing mode and displaying the keyboard **921**, the device detects a deep press by a finger contact **924** on the onscreen keyboard **921**, such that the intensity of the press input has increased above the deep press intensity threshold  $IT_D$ . In response to detecting the deep press, the appearance of the keyboard **921** changes to indicate that the application has entered a text selection mode. In the text selection mode, the keyboard **921** is not responsive to keystrokes, but rather serves as an onscreen touchpad or track pad for moving the cursor. As shown in FIG. 9B, in some embodiments, the keys are visually obscured. Visually obscuring keys on the keyboard **921** provides an intuitive indication that the function of the keyboard **921** has changed. In some embodiments, the onscreen keyboard **921** shown in FIG. 9B is dimmed or blurred relative to the keyboard **921** shown in FIG. 9A prior to detecting the deep press, such that the keys are no longer visible or clearly displayed as before. In some embodiments, the keyboard **921** becomes semitransparent, to reveal content lying underneath the keyboard.

When the keyboard **921** serves as an onscreen touch pad or track pad, in response to detecting finger movement **932** on the keyboard **921**, in some embodiments, a floating cursor **922-1** moves across the touch screen display **112** in accordance with the movement of one or more finger contacts, and a ghost cursor **922-2** is displayed offset from the real cursor **922-1**. In some embodiments, the ghost cursor **922-2** indicates where the cursor will be located after a lift-off of the finger contact **924**. In some embodiments, the ghost cursor **922-2** is a modified version of the original cursor **922** displayed on the screen (e.g., the ghost cursor **922-2** is in grey color, while the original cursor **922** as shown in FIG. 9A is in black color).

In some embodiments, when the touch input for entering the text selection mode is detected, the original cursor **922** changes its appearance, while the floating cursor **922-1** springs into its initial location from the original text cursor **922**. In some embodiment, the initial location of the floating cursor **922-1** is slightly offset from the location of the ghost cursor **922-2** (e.g., slightly higher in FIG. 9B). In some embodiments, the animation displayed in response to the touch input has the visual effect that the original text cursor **922** has jumped off the page and becomes a floating cursor **922-1**, while leaving a shadow or ghost image at its original location. For example, the ghost cursor **922-2** shown in FIG. 9B is in the middle of the word “Liberty”, the same location as the cursor **922** in FIG. 9A when the touch input by finger contact **924** is determined to satisfy the one or more criteria for entering the text selection mode at time  $T_1$ .

In some embodiments, when the user subsequently moves the finger contact, the floating cursor **922-1** moves with the finger contact **924** in a continuous fluid motion in the content presentation region **902**, while the ghost cursor **922-2** moves in discrete jumps from one permitted insertion location to

another permitted insertion location to indicate the final location of the cursor if the touch input was terminated at that moment. For example, in FIG. 9C, when the finger moves **932** along a path, the floating cursor **922-1** moves along a similar path, while the ghost cursor **922-2** moves in the direction of the finger movement and in discrete jumps from the middle of the word “Liberty” (FIG. 9B) to the end of the word “conceived” (FIG. 9C), then to the middle of the word “created” (FIG. 9D). The ghost cursor **922-2** indicates the position where a cursor will be displayed when the user lifts the finger. As shown in FIGS. 9C and 9D, after the initial deep press at time  $T_1$ , the intensity of the contact **924** on the touch screen **112** can be above or below the deep press intensity threshold  $IT_D$  during the finger movement between time  $T_1$  and  $T_3$ .

In FIG. 9E, at the end of the finger movement **932**, the contact intensity decreases to zero at time  $T_4$ , which corresponds to a lift-off of the finger. In response to the lift-off, in some embodiments, the device ceases to display the floating cursor, maintains display of the ghost cursor at a respective permitted insertion position reached by the ghost cursor after the discrete movements of the ghost cursor (e.g., in the middle of the word “created”). As shown in FIG. 9E, in some embodiments, the device ceases to display the ghost cursor, displays the cursor **922** in the middle of the word “created”, and restores the appearance of the onscreen keyboard **921** (e.g., no longer obscured) to indicate the end of the text selection mode and that the onscreen keyboard **921** is responsive to keystrokes.

In FIG. 9F, while in the text selection mode, at time  $T_4$ , when a ghost cursor (not shown in FIG. 9F) is located in the middle of the word “created”, the device detects the intensity of the press input exceed the deep press intensity threshold  $IT_D$ . In response to detecting the deep press on the editable content **900**, the device begins to select a portion of the text input **928** in accordance with the movement **932** of the contact in the touch input. After time  $T_4$ , during the movement **932**, the intensity of the press input can be above or below the deep press intensity threshold III).

FIGS. 9G-9L illustrate a variety of possible behaviors that can occur at time  $T_5$  in accordance with some embodiments.

In FIG. 9G, at time  $T_5$ , the device detects lift-off of the contact in the touch input, such that the intensity of the press input is zero. In response to detecting the lift-off of the contact in the touch input, in some embodiments, the device confirms selection of the portion of the text input **928**. In some embodiments, a selection box **930** (e.g., a grey box) is maintained on the selected portion of the text input, and/or a menu bar **940** is displayed that shows actions that can be performed on the selected portion of the text input (e.g., copying **944**, defining, cutting **942**, pasting, etc.). Thus, FIGS. 9F and 9G illustrate using a first deep press input by a contact (**924**) to initiate text selection, then movement of the contact to select text, and then lift-off of the contact to confirm the selection.

In FIG. 9H, after selecting the portion of the text input between time  $T_4$  and  $T_5$ , while the portion of the text input is selected (FIG. 9F), the device detects an intensity of the contact in the touch input that exceeds the deep press intensity threshold  $IT_D$  at time  $T_5$ . In response to detecting the deep press while the portion of the text input is selected, in some embodiments, the device clears selection of the portion of the text input and displays the insertion marker **922**, as shown in FIG. 9H. Thus, FIGS. 9F and 9H illustrate using a first deep press input by a contact (**924**) to initiate

text selection, then movement of the contact to select text, and then a second deep press input by the contact to clear the selection.

In FIG. 9I, instead of clearing the selection as shown in FIG. 9H, upon detecting the deep press at time  $T_5$ , while the portion of the text input is selected (FIG. 9F), the device detects an intensity of the contact in the touch input that exceeds the deep press intensity threshold  $IT_D$  followed by lift-off of the contact without further movement of the contact. In response to detecting the stationary deep press followed by the lift-off, the device confirms the selection **928**, and in some embodiments, displays a menu bar **940**. Thus, FIGS. 9F and 9I illustrate using a first deep press input by a contact (**924**) to initiate text selection, then movement of the contact to select text, and then a second deep press input by the contact and lift-off without further movement of the contact to confirm the selection.

In FIG. 9J, upon detecting the deep press at time  $T_5$ , while the portion of the text input is selected (FIG. 9F), the device detects an intensity of the contact in the touch input that exceeds the deep press intensity threshold  $IT_D$  followed by further movement **932** of the contact. In response to the movement following the deep press, the device clears the selection and displays the insertion marker **922** at the end of the word “created”. After clearing the selection at time  $T_5$ , a new selection **928** is made in accordance with the finger movement **932** between time  $T_5$  and  $T_6$ , as shown in FIG. 9K. The new selection **928** starts from the end of the word “created”, where the insertion marker **922** was located when a deep press was detected at time  $T_5$ . Thus, FIGS. 9F, 9J, and 9K illustrate using a first deep press input by a contact (**924**) to initiate text selection, then movement of the contact to select text, then a second deep press input by the contact to confirm the selection, and then further movement of the contact to clear the prior selection and start a new selection.

In FIG. 9L, upon detecting the deep press at time  $T_5$ , while the portion of the text input is selected (FIG. 9F), the device detects an intensity of the contact in the touch input that exceeds the deep press intensity threshold  $IT_D$  followed by further movement **932** of the contact. In response to the movement following the deep press, the device moves the floating cursor **922-1** and the ghost cursor **922-2** within the content presentation region **902** in accordance with the further movement **932** of the contact. Thus, FIGS. 9F and 9L illustrate using a first deep press input by a contact (**924**) to initiate text selection, then movement of the contact to select text, then a second deep press input by the contact to confirm the selection, and then further movement of the contact to clear the prior selection and move the cursor(s), without starting a new selection.

In FIG. 9M, while in the text selection mode after detecting a deep press at time  $T_1$ , the device detects a first local intensity peak of the touch input at time  $T_4$  followed by a second local intensity peak in the touch input at time  $T_5$  that both exceed the deep press intensity threshold  $IT_D$ . In response, the device selects a predetermined unit (e.g., a word, or a phrase, or a sentence) of the text input according to a current location of the ghost cursor. For example, at time  $T_3$ , the ghost cursor **922-2** is located in the middle of the word “created” (FIG. 9D). In response to detecting two local intensity peak exceeding the deep press intensity threshold  $IT_D$  at time  $T_4$  and  $T_5$  respectively, the device selects the word “created” according to the current location of the ghost cursor located in the middle of the word.

In some embodiments, as shown in FIG. 9M, the device detects an increase in a characteristic intensity of the contact above the predefined threshold (e.g.,  $IT_D$ ) followed by a

decrease in the characteristic intensity of the contact below the predefined intensity threshold (e.g.,  $IT_D$ , and, optionally, a hysteresis intensity threshold that is below the predefined intensity threshold), which in turn is followed by another increase in the characteristic intensity of the contact above the predefined intensity threshold (e.g.,  $IT_D$ ).

In some embodiments, the criteria for selecting the first predetermined unit of the text includes a criterion that is met when the second increase in characteristic intensity of the contact above the predefined intensity threshold (e.g.,  $IT_D$ ) occurs within a predetermined time period after the first increase in characteristic intensity of the contact above the predefined intensity threshold (e.g.,  $IT_D$ , the double press is a quick double press to trigger selection of the first predetermined unit of text input). For example, when the duration between time  $T_4$  and  $T_5$  is less than a threshold, the criteria for selecting the first predetermined unit of text are met.

In some embodiments, instead of just two increases in the characteristic intensity of the contact above the predefined intensity threshold (e.g.,  $IT_D$ ), three such increases are detected and used to trigger selection of a second predetermined unit of text input (e.g., a quick triple press triggers selection of a sentence, whereas a quick double press triggers selection of a word).

In FIG. 9N, after detecting the first local intensity peak followed by the second local intensity peak, the device detects a third consecutive local intensity peak in the touch input that exceeds the predetermined intensity threshold (e.g.,  $IT_D$ ). In some embodiments, the three consecutive local intensity peaks at time  $T_4$ ,  $T_5$ , and  $T_6$  are spaced within a predetermined duration (e.g., within 100 ms or within 200 ms) such that the three intensity peaks are recognized as a single user command (e.g., a triple deep press). In response to detecting the triple deep press, the device selects a second predetermined unit (e.g., a sentence "Four score . . . equal.") of the text input that is larger than and includes the first predetermined unit (e.g., the word "created" in FIG. 9M) of the text input.

Turning to FIGS. 9O-9AD, FIGS. 9O-9AD illustrate exemplary user interfaces for selecting content. The user interfaces in these figures are used to illustrate the processes described below with respect to FIGS. 11A-11F.

In FIG. 9O, editable content **900** is displayed while an application is in a document editing mode. The application runs on a device **100** that has one or more sensors (e.g., contact intensity sensor(s) **259**, FIG. 2B) to detect intensity of contacts with the touch-sensitive display. A user may edit text (e.g., via a keyboard, not shown) and confirm completion of the editing by performing a touch input (e.g., a tap on "done" button) to exit the editing mode. An insertion marker (e.g., cursor **922**) is displayed to indicate a current location for text inputs.

At a time prior to  $T_0$ , no contact is present or detected on touch screen display **112**. At  $T_0$ , the device detects the intensity of the press input increases above the contact intensity threshold  $IT_0$ . In response to detecting the finger contact **925** on the editable content **900**, the device moves a text selection indicator (e.g., a cursor **922**) to the location that corresponds to the finger contact (e.g., between the character "r" and "o" of the word "from").

In FIG. 9P, in some embodiments, after the intensity of the press input increases above the contact intensity threshold  $IT_0$  at  $T_0$ , the finger press maintains its pressure, which corresponds to a press and hold gesture. In response to detecting the press and hold gesture, the device displays a magnifying loupe **908**. In the magnifying loupe **908**, the device expands a portion **943** of the editable content on the

touch screen display to a second magnification that is greater than the first magnification. The content magnifier **908** displays the expanded portion **943** of the editable content and a position marker **945** (which corresponds to cursor **922**, and which may be displayed in addition to cursor **922** or in place of cursor **922**) at a first location within the expanded portion of the editable content (e.g., in the middle of the word "from"). In some embodiments, the expanded portion **943** of the editable content displayed in the content magnifier includes portions of at least three horizontal lines of text displayed concurrently. In some embodiments, the content magnifier **908** has a predefined shape (e.g., a circle).

In FIG. 9Q, in some embodiments, after the intensity of the press input increases above the contact intensity threshold  $IT_0$  at  $T_0$ , the intensity of the finger press further increases. At time  $T_1$ , the device detects that the intensity of the press input has increased above the deep press intensity threshold  $IT_D$ . In some embodiments, in response to detecting the deep press on the editable content **900**, the device displays the content magnifier **908**.

In FIG. 9P or FIG. 9Q, when the device detects movement **932** of the finger contact **925** across the touch screen display, the device moves the content magnifier **908** and the insertion marker **922** (and/or position marker **945**) in accordance with the movement of the finger contact **925**. In FIG. 9R, in response to detecting the movement **932** of the finger gesture from the middle of the word "from" at  $T_1$  to the middle of the word "nation" at  $T_2$ , the device moves the content magnifier **908** and the insertion marker **922** in accordance with the movement of the finger. During the finger movement **932**, the intensity of the press input can increase or decrease. For example, as shown in FIG. 9R, after time  $T_1$ , the intensity continues to rise above the deep press intensity threshold  $IT_D$  then decreases to dip below the deep press intensity threshold  $IT_D$  at time  $T_2$ . The device continues to move the content magnifier **908** and the insertion marker **922** until the device detects the intensity of the press input has once again increased above the deep press intensity threshold  $IT_D$  at time  $T_3$ , as shown in FIG. 9S.

In FIG. 9S, at time  $T_3$ , the device detects a deep press followed by movement of contact **925**. In response to detecting the deep press followed by movement of contact **925**, the device selects editable text (e.g., one character at a time) as the finger contact **925** moves. In some embodiments, the selected content **928** is marked by a start-point object **926** and an end-point object **930** at respective ends of the selected content **928**. For example, in response to detecting the movement **932** of the finger contact **925** from the middle of the word "nation" to the middle of the word "under", the device selects the editable content as the finger moves and marks the selection **928** by the start-point object **926** in the middle of the word "nation" and the end-point object **930** in the middle of the word "under".

In the corresponding intensity diagram, the movement of the finger from the middle of the word "nation" to the middle of the word "under" corresponds to the segment between time  $T_3$  and  $T_4$ . As shown in FIG. 9S, once the initial deep press is detected, the intensity of the press input does not need to be constantly above the deep press intensity threshold  $IT_D$ . Even when the intensity of the press input has fallen below  $IT_D$  during part of the finger movement, the content selection continues.

FIGS. 9T-9X illustrate a variety of possible behaviors that can occur at time  $T_5$  in accordance with some embodiments.

In FIG. 9T, at the end of the content selection, in some embodiments, the device detects lift-off of the finger contact at time  $T_5$  such that the device detects the intensity of the

finger contact **925** decreases to zero. In response to detecting the lift-off, the device maintains the selection **928** and displays an action menu **940** adjacent to the selected content **928**. In some embodiments, the action menu **940** includes an icon **942** for cutting the selected content **928**, an icon **944** for copying the selected content **928**, and an icon **946** for looking up the selected content **928**. Thus, FIGS. **9S** and **9T** illustrate using a first deep press input by a contact (**925**) to initiate text selection, then movement of the contact to select text, and then lift-off of the contact to confirm the selection.

In FIG. **9U**, at the end of the content selection, in some embodiments, the device detects another deep press by finger contact **925** at time  $T_5$ . In response to detecting the deep press, the device cancels the selection, and places the text selection indicator (e.g., cursor **922**) at the deep press location (e.g., in the middle of the word “under”), and starts a new selection upon detecting further finger movement. Thus, FIGS. **9S** and **9U** illustrate using a first deep press input by a contact (**925**) to initiate text selection, then movement of the contact to select text, and then a second deep press input by the contact to clear the selection.

In FIG. **9V**, in some embodiments, instead of canceling the selection upon detecting another deep press by finger contact **925**, at time  $T_5$ , in response to detecting the deep press, the device maintains the selection **928**. Subsequently, in some embodiments, as shown in FIG. **9W**, the device detects finger movement **932** between time  $T_5$  and  $T_6$ . In response to detecting the finger movement **932**, the selection is cleared, and the text selection indicator (e.g., cursor **922**) moves from the middle of the word “under” to the middle of the word “of” in accordance with the movement **932** of the finger. Thus, FIGS. **9S**, **9V**, and **9W** illustrate using a first deep press input by a contact (**925**) to initiate text selection, then movement of the contact to select text, then a second deep press input by the contact to confirm the selection, and then further movement of the contact to clear the prior selection and move the cursor(s), without starting a new selection.

FIG. **9X** illustrates, in some embodiments, both cursor positioning and text selection occur in the text selection mode. After detecting the deep press at time  $T_5$ , in response to detecting further finger movement **932** between time  $T_5$  and  $T_6$ , the device maintains the selection **928** and displays an action menu **940** adjacent to the selected content **928**. In addition, the device displays the text selection indicator (e.g., cursor **922**) that moves in accordance with movement **932** of the finger. The device will clear the selection **928** upon detecting another deep press. Thus, FIGS. **9S** and **9X** illustrate using a first deep press input by a contact (**925**) to initiate text selection, then movement of the contact to select text, then a second deep press input by the contact to confirm and complete the selection, and then further movement of the contact to move the cursor(s) and maintain the action menu **940**, without clearing the selected content.

In some embodiments, if a third deep press input by the contact **925** is detected after the further movement of the contact to move the cursor(s), then the selected content (e.g., “ation un” in FIG. **9X**) is cleared and display of the action menu **940** ends. In some embodiments, the third deep press input by the contact initiates text selection such that movement of the contact **925** after the third deep press input selects text in accordance with the movement of the contact **925**.

In some embodiments, the third deep press input does not clear the previously selected content, but the third deep press input by the contact does initiate additional text selection such that movement of the contact **925** after the third deep

press input selects an additional portion of text in accordance with the movement. In these embodiments, a user is able to select multiple portions of content with a single continuous contact by repeatedly: deep pressing to initiate text selection, moving to select text, deep pressing again to complete text selection, and moving without selecting text to a next position on the touch-sensitive surface that corresponds to a desired starting location for the next text selection.

On the other hand, if lift off of contact **925** is detected without detecting a third deep press input by contact **925**, then display of the selected content “ation un” and the action menu **940** are maintained.

In some embodiments, in FIG. **9X**, the selected text “ation un” is copied by moving contact **925** across the touch-sensitive surface to a position that corresponds to the location of copy icon **944**, and then detecting a deep press with contact **925** at that position. Similarly, in FIG. **9X**, the selected text “ation un” is cut by moving contact **925** across the touch-sensitive surface to a position that corresponds to the location of cut icon **942**, and then detecting a deep press with contact **925** at that position. Similarly, in FIG. **9X**, the selected text “ation un” is looked up by moving contact **925** across the touch-sensitive surface to a position that corresponds to the location of lookup icon **946**, and then detecting a deep press with contact **925** at that position. Alternatively, while action menu **940** is displayed, a tap gesture on the touch-sensitive surface at a location that corresponds to the location of one of icons **942**, **944**, and **946** in the action menu **940** initiates the corresponding action. In some embodiments, a deep press input (e.g., an increase in intensity from below  $IT_D$  to above  $IT_D$ ) by contact **925** on text (e.g., a word, set of words or characters, hyperlink, or other portion of text) while the text is selected initiates a predefined user interface action associated with the selected text. In some embodiments, the predefined user interface action includes displaying additional information about the selected text (e.g., displaying a region displayed overlaid on the user interface that includes the text, wherein the overlaid region includes additional information about the text such as a definition for a word, an encyclopedia entry for a word or phrase, or a preview of a linked resource such as a webpage for a hyperlink). In some embodiments, the additional information continues to be displayed overlaid on the user interface that includes the text until contact **925** ceases to be detected, and the device ceases to display the additional information in response to ceasing to detect contact **925**. In some embodiments, the additional information for the selected text continues to be displayed overlaid on the user interface that includes the text until another deep press (e.g., an increase in intensity from below  $IT_D$  to above  $IT_D$ ) by contact **925** is detected on the selected text, and the device ceases to display the additional information in response to detecting a deep press (e.g., an increase in intensity from below  $IT_D$  to above  $IT_D$ ) by contact **925** on the selected text while the additional information for the selected text is displayed.

Turning to FIGS. **9Y-9AD**, FIGS. **9Y-9AD** illustrate exemplary user interfaces for selecting read-only content (e.g., a webpage) on a device **100** that has one or more sensors (e.g., contact intensity sensor(s) **259**, FIG. **2B**) to detect intensity of contacts with the touch-sensitive display. In FIG. **9Y**, prior to time  $T_0$ , no contact is present or detected on the touch screen **112**. At  $T_0$ , the device detects the intensity of a press input by finger contact **927** increases above the contact intensity threshold  $IT_0$ .

In FIG. 9Z, at time  $T_1$ , the device detects that the intensity of the press input by finger contact 927 has increased above the deep press intensity threshold  $IT_D$ . In response to detecting the deep press on the read-only content, the device displays a selection box 929 around a word (e.g., “Translation”) in the read-only text.

In FIG. 9AA, at time  $T_2$ , the device detects a movement 932 of the finger contact 927 from the word “Translation” to “Gift” in the read-only content. In accordance with the movement of the finger contact 927, additional words are selected, and the selection box 929 expands to “Translation: A.U.S. Gift”. In some embodiments, the expansion increases one word at a time.

In FIG. 9AB, at time  $T_3$ , the device detects that the intensity of the press input by finger contact 927 has increased above the deep press intensity threshold  $IT_D$ . In response to detecting the deep press, the device clears the selection, and starts a new selection by selecting a word at the deep press location of finger contact 927 (e.g., the word “Gift”) as shown in FIG. 9AB and increases the new selection box 929 one word at a time in accordance with the movement 932 of the finger contact 927, as shown in FIG. 9AC.

In FIG. 9AD, at the end of the content selection, in some embodiments, the device detects a lift-off of the finger contact 927, such that the intensity of the press input has decreased to zero. In response to detecting the lift-off, the device maintains the selection and displays an action menu 940 adjacent to the selected content in selection box 929. The action menu 940, in some embodiments, includes an icon for copying the selected content.

FIGS. 10A-10G illustrate a flow diagram of a method 1000 of manipulating a cursor in accordance with some embodiments. The method 1000 is performed at (1002) an electronic device (e.g., portable multifunction device 100, FIG. 1A) with one or more processors, memory, and a display. In some embodiments, the display is a touch-screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method 1000 are, optionally, combined and/or the order of some operations is, optionally, changed.

As described below, the method 1000 provides an efficient way to manipulate a cursor. The method reduces the cognitive burden on a user when using a cursor, thereby creating a more efficient human-machine interface. For battery-operated electronic devices, enabling a user to manipulate a cursor faster and more efficiently conserves power and increases the time between battery charges.

The device concurrently displays (1004) an onscreen keyboard (e.g., keyboard 921, FIG. 9A) and a content presentation region 902 on the touch-sensitive display. In some embodiments, the content presentation region displays (1006) text input received from the onscreen keyboard. The device then detects (1008) a touch input (e.g., by finger contact 924) on the onscreen keyboard 921 displayed on the touch-sensitive display. In response to detecting the touch input on the onscreen keyboard displayed on the touch-sensitive display, the device determines (1010) whether the touch input satisfies one or more criteria for entering a text selection mode.

In some embodiments, the one or more criteria for entering the text selection mode include (1012) the touch input including a two-finger drag gesture over the onscreen keyboard (FIG. 7B). In some embodiments, a two-finger drag gesture that starts outside of the onscreen keyboard and enters the onscreen keyboard through movement of the

finger contacts satisfies the criteria for entering the text selection mode (FIGS. 7A and 7B). In some embodiments, after entering the onscreen keyboard, as long as the two-finger gesture is confined within the onscreen keyboard, the criteria for entering the text selection mode are satisfied.

In accordance with a determination that the touch input satisfies the one or more criteria for entering the text selection mode, the device concurrently displays (1014), in the content presentation region 902, a first cursor (e.g., ghost cursor 922-2, FIG. 9B) at a first location and a second cursor (e.g., floating cursor 922-1, FIG. 9B) at a second location that is different from the first location. In some embodiments, the second cursor 922-1 is a cursor that moves across the touch-sensitive display in accordance with the movement of one or more finger contacts in the touch input (FIGS. 9C-9E). In some embodiments, the first cursor 922-2 is a ghost cursor that indicates where the cursor will be located after the lift-off of the finger contact (FIGS. 9C-9E).

In some embodiments, the electronic device has (1016) one or more sensors to detect intensity of contacts with the touch-sensitive display, the touch input on the touch-sensitive display includes an input by a contact on the onscreen keyboard, and the one or more criteria for entering the text selection mode include the contact on the onscreen keyboard having an intensity that exceeds a predetermined deep press intensity threshold (FIG. 9B). In some embodiments, determining whether the touch input satisfies the one or more criteria for entering the text selection mode includes determining whether the touch input on the touch-sensitive display includes a press input by finger contact 924 over the onscreen keyboard 921, and the press input by finger contact 924 has a contact intensity that exceeds a predetermined deep press intensity threshold  $IT_D$  (FIG. 9B).

In some embodiments, in accordance with the determination that the touch input satisfies the one or more criteria for entering the text selection mode, the device visually obscures (1018) keys on the onscreen keyboard (FIG. 9B). In some embodiments, visually obscuring the keys on the onscreen keyboard includes (1020) applying a blurring effect to the onscreen keyboard (FIG. 9B). As shown in FIG. 9B, by applying a blurring effect to the keyboard, the keys on the keyboard become fuzzy and indiscernible. In some embodiments, visually obscuring the keys on the onscreen keyboard includes (1022) transforming the onscreen keyboard into an onscreen touchpad (FIGS. 9B-9D). In some embodiments, visually obscuring the keys on the onscreen keyboard includes (1024) making the onscreen keyboard semitransparent to partially reveal content lying underneath the onscreen keyboard (FIGS. 9B-9D).

In some embodiments, the second location 922-1 (FIG. 9B) is (1026) based on a location of an initial contact in the touch input, and the first location is a permitted insertion position in the content presentation region that is based on the second location. In some embodiments, the initial location of a finger contact 924 on the touch screen display 112 determines the initial position of the second cursor. For example, if the initial location of the finger contact is on the left portion of the touch screen display 112, the second cursor 922-1 will be displayed at a corresponding location on the left portion of the content presentation region (FIG. 9L). Conversely, as shown in FIG. 9B, when the initial location of the finger contact 924 is on the right portion of the touch screen display 112, the second cursor 922-1 will be displayed at a corresponding location on the right portion of the content presentation region 902 (FIG. 9B).

In some embodiments, once the initial position of the second cursor (e.g., floating cursor 922-1, FIG. 9B) is

determined based on the initial position of the finger contact, the initial position of the first cursor (e.g., ghost cursor **922-2**, FIG. **9B**) is determined based on the initial position of the second cursor. In some embodiments, the original text cursor (e.g., cursor **922**, FIG. **9A**) jumps to the position of the second cursor (e.g., floating cursor **922-1**, FIG. **9B**) to serve as the second cursor, and the first cursor (e.g., ghost cursor **922-2**, FIG. **9B**) is created at the corresponding insertion position (e.g., the position in the middle of the word “Liberty” marked by the insertion marker **922** in FIG. **9A**) that is associated with the second cursor.

In some embodiments, as shown in FIG. **9B**, the first location is (**1028**) an insertion position at which the first cursor **922-2** is located when the touch input is determined to satisfy the one or more criteria for entering the text selection mode, and the second location is displaced from the first location by a predetermined offset. For example, the insertion marker **922** is displayed in the text input (e.g., in the middle of the word “Liberty, FIG. **9A**) when the touch input is determined to satisfy the one or more criteria for entering the text selection mode (FIG. **9B**). When it is determined that the touch input satisfies the one or more criteria for entering the text selection mode, the first cursor (e.g., ghost cursor **922-2**) is displayed at the position of the insertion marker (e.g., in the middle of the word “Liberty, FIG. **9B**), and a second cursor (e.g., floating cursor **922-1**) is created and placed near the first cursor. When the user subsequently moves the finger contact in the touch input, the floating cursor is dragged by the finger contact, and the first cursor moves from permitted insertion location to permitted insertion location in accordance with the current position of the floating cursor. In some embodiments, when the touch input is determined to satisfy the one or more criteria for entering the text selection mode, an animation is displayed that shows the floating cursor **922-1** being peeled off the first cursor **922-2**, and floating above the first cursor **922-2** at a predetermined distance, and the first cursor **922-1** takes on an appearance (e.g., grayed) that mimics a shadow or ghost of the floating cursor **922-1**.

In some embodiments, one of the first and second cursors is (**1030**) already displayed in the content presentation region **902** before both of the first and second cursors are concurrently displayed in the content presentation region **902**. In some embodiments, the floating cursor **922-1** is already displayed when the touch input is determined to satisfy the one or more criteria for entering the text selection mode. In some embodiments, the insertion cursor **922-2** is already displayed when the touch input is determined to satisfy the one or more criteria for entering the text selection mode.

In some embodiments, the device detects (**1032**) movement of one or more contacts of the touch input, and moves (**1034**) the second cursor (e.g., the floating cursor **922-1**) within the content presentation region in accordance with the movement of the one or more contacts of the touch input (e.g., the movement of the floating cursor smoothly follows the movement of a finger contact in terms of speed and direction). In some embodiments, the device moves (**1036**) the first cursor based on the movement of the second cursor, and movement of the first cursor includes discrete movements between permitted insertion positions in the content presentation region. For example, when the user moves the finger contact in the touch input (FIGS. **9B-9D**), the floating cursor **922-1** is dragged by the finger contact, and the first cursor (e.g., ghost cursor **922-2**) moves from permitted insertion location to permitted insertion location in accordance with the current position of the floating cursor **922-1**

(e.g., from the middle of the word “Liberty in FIG. **9B** to the end of the word “conceived” in FIG. **9C**”, then to the middle of the word “created” in FIG. **9D**).

In some embodiments, the device detects (**1038**) a lift-off of the touch input after detecting the movement of the one or more contacts of the touch input (FIG. **9E**). In response to detecting the lift-off of the touch input, the device ceases (**1040**) to display the second cursor.

In some embodiments, in response to detecting the lift-off of the touch input, the device maintains (**1042**) display of the first cursor at a respective permitted insertion position reached by the first cursor after the discrete movements of the first cursor (e.g., the middle of the word “created” in FIG. **9D**).

In some embodiments, in response to detecting the lift-off of the touch input, the device ceases (**1044**) to display the first cursor (FIG. **9E**).

In some embodiments, the onscreen keyboard is obscured in accordance with a determination that the touch input satisfies the one or more criteria for entering the text selection mode, and in response to detecting the lift-off of the touch input, the device restores (**1046**) display of the onscreen keyboard (FIG. **9E**).

In some embodiments, the device has (**1048**) one or more sensors to detect intensity of contacts with the touch-sensitive display, and using the one or more sensors, the device detects that an intensity of a contact in the touch input exceeds a predetermined intensity threshold (e.g.,  $IT_D$ ). After detecting that the intensity of the contact in the touch input exceeds the predetermined intensity threshold, the device detects (**1050**) movement of the contact in the touch input. In response to detecting the movement of the contact in the touch input, after detecting that the intensity of the contact in the touch input exceeds the predetermined intensity threshold, the device selects (**1052**) a portion of the text input in accordance with the movement of the contact in the touch input (e.g., selecting “eated” in accordance with the finger movement **932**, FIG. **9F**). In some embodiments, the selected portion of the text input begins (**1054**) at a position of the first cursor (e.g., between the character “r” and “e” of the word “created”, FIG. **9F**), when the detected intensity of the contact in the touch input exceeded the predetermined intensity threshold.

In some embodiments, the device detects (**1056**) lift-off of the contact in the touch input after selecting the portion of the text input in accordance with the movement of the contact in the touch input. In response to detecting the lift-off of the contact in the touch input, the device confirms (**1058**) selection of the portion of the text input (FIG. **9G**).

In some embodiments, after selecting the portion of the text input, while the portion of the text input is selected, the device detects (**1060**) an intensity of the contact in the touch input that exceeds the predetermined threshold (e.g.,  $IT_D$ ). In response to detecting the intensity of the contact in the touch input that exceeds the predetermined threshold while the portion of the text input is selected, the device clears (**1062**) selection of the portion of the text input (FIG. **9H**).

In some embodiments, after selecting the portion of the text input, while the portion of the text input is selected, the device detects (**1064**) an intensity of the contact in the touch input that exceeds the predetermined threshold and that is followed by lift-off of the contact without further movement of the contact. In response to detecting the intensity of the contact in the touch input that exceeds the predetermined threshold and that is followed by lift-off of the contact without further movement of the contact, the device confirms (**1066**) selection of the portion of the text input (FIG.

9I). In some embodiments, in response to detecting the intensity of the contact in the touch input that exceeds the predetermined threshold and that is followed by lift-off of the contact without further movement of the contact: selection of text is stopped, a selection box is maintained on the selected portion of the text input, and/or a menu bar is displayed that shows actions that can be performed on the selected portion of the text input (e.g., copying, defining, cutting, pasting, etc.).

In some embodiments, after selecting the portion of the text input, while the portion of the text input is selected, the device detects (1068) an intensity of the contact in the touch input that exceeds the predetermined threshold and that is followed by further movement of the contact. In response to detecting the intensity of the contact in the touch input that exceeds the predetermined threshold and that is followed by the further movement of the contact, the device clears (1070) selection of the portion of the text input (FIG. 9J). Further, in some embodiments, in response to detecting the intensity of the contact in the touch input that exceeds the predetermined threshold and that is followed by the further movement of the contact, the device starts (1072) selection of a new portion of the text input in accordance with the further movement of the contact (FIG. 9K). In some other embodiments, instead of starting a new selection, in response to detecting the intensity of the contact in the touch input that exceeds the predetermined threshold and that is followed by the further movement of the contact, the device moves (1074) the second cursor and the first cursor within the content presentation region in accordance with the further movement of the contact (FIG. 9L).

In some embodiments, the device has one or more sensors to detect intensity of contacts with the touch-sensitive display, and using the one or more sensors, in the text selection mode, the device detects (1076) a first local intensity peak in the touch input followed by a second local intensity peak in the touch input that both exceed a predetermined intensity threshold (e.g., ITS). In response to detecting the first local intensity peak followed by the second local intensity peak that both exceed the predetermined intensity threshold, the device selects (1078) a first predetermined unit (e.g., a word as shown in FIG. 9M, or a phrase, or a sentence as shown in FIG. 9N) of the text input according to a current location of the first cursor.

In some embodiments, after detecting the first local intensity peak followed by the second local intensity peak, the device detects (1080) a third consecutive local intensity peak in the touch input that exceeds the predetermined intensity threshold (e.g., a triple deep press). In response to detecting the three consecutive local intensity peaks in the touch input that all exceed the predetermined deep press intensity threshold, the device selects (1082) a second predetermined unit (e.g., a sentence, FIG. 9N) of the text input that is larger than and includes the first predetermined unit (e.g., a word, FIG. 9M) of the text input.

It should be understood that the particular order in which the operations in FIGS. 10A-10G have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., methods 400 and 1100) are also applicable in an analogous manner to method 1000 described above with respect to FIGS. 10A-10G. For example, the contacts, gestures, user interface objects, inten-

sity thresholds, and/or animations described above with reference to method 1000 optionally have one or more of the characteristics of the contacts, gestures, user interface objects, intensity thresholds, and/or animations described herein with reference to other methods described herein (e.g., methods 400 and 1100). For brevity, these details are not repeated here.

FIGS. 11A-11F illustrate a flow diagram of a method 1100 of selecting content in accordance with some embodiments. The method 1100 is performed at (1102) an electronic device (e.g., portable multifunction device 100, FIG. 1A) with one or more processors, memory, a touch-sensitive surface, a display, and one or more sensors to detect intensity of contacts with the touch-sensitive surface. In some embodiments, the display is a touch-screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method 1100 are, optionally, combined and/or the order of some operations is, optionally, changed.

As described below, the method 1100 provides an efficient way to select content with press and movement inputs by a single continuous contact on the touch-sensitive surface, thereby creating a more efficient human-machine interface. For battery-operated electronic devices, enabling a user to select content faster and more efficiently conserves power and increases the time between battery charges.

While a contact (e.g., a finger contact or a stylus contact) is detected on the touch-sensitive surface, the device concurrently displays (1104) on the display content (e.g., editable content in FIGS. 9A-9X and/or read-only content in FIGS. 9Y-9AD) and a text selection indicator at a first location within the content.

In some embodiments, the text selection indicator is a cursor (e.g., cursor 922) that moves within editable content (FIGS. 9O-9R). In some embodiments, the text selection indicator is a selection box or other area that encloses selected content for read-only content (e.g., selection box 929, FIG. 9Z-9AD). In some embodiments, the text selection indicator indicates the starting location of content selection when no content is currently selected (FIG. 9P), and indicates the end location of the currently selected content as a result of contact movement in a content selection mode. In some embodiments, the selection box has a starting edge that indicates the starting location of the selected content, and an end edge that indicates the end location of the selected content (e.g., FIGS. 9S and 9Z). In some embodiments, the cursor moves one character at a time (FIGS. 9P-9R). In some embodiments, the selection box expands or contracts one word at a time (e.g., selection of read-only content by selection box 929, FIGS. 9Z-9AA). In some embodiments, the selection box selects at least one word at any given time (e.g., selection of read-only content, FIG. 9Z). In some embodiments, a magnifying loupe (e.g., 908 in FIG. 9P) is displayed with the cursor and shows a magnified version of the cursor and surrounding content. In some embodiments, a magnifying loupe is displayed with the selection box and shows a magnified version of the selection box and surrounding content (e.g., 952 in FIG. 9S).

The device detects (1106) a first press input by the contact followed by movement of the contact across the touch-sensitive surface that corresponds to movement of at least a portion of the text selection indicator from the first location to a second location on the display (e.g., moving a cursor to the second location on the display or moving an edge of a selection box to the second location on the display, where the edge of the selection box corresponds to one end of the

selected content). In some embodiments, the device detects the first press input and the subsequent movement by detecting an increase in intensity of the contact above a predetermined intensity threshold (e.g., a deep press intensity threshold  $IT_D$ ), followed by detecting a decrease in intensity of the contact to an intensity that remains above a predetermined minimum intensity value (e.g., a light press intensity threshold or a contact detection threshold). For example, as shown in FIG. 9AA, after applying a deep press using contact 927 at time  $T_1$ , the user may ease the contact intensity on the touch-sensitive surface during movement of the contact, as long as the contact intensity is maintained above a predetermined minimum value, such as the light press threshold intensity  $IT_L$ , or the contact detection threshold  $IT_0$ .

In response to detecting the first press input by the contact followed by movement of the contact across the touch-sensitive surface, the device selects (1110) content between the first location and the second location (e.g., selecting content for an editing operation, such as copying). In some embodiments, the selected content (e.g., editable text or read-only text) is enclosed by a highlighted area (e.g., area 928 in FIG. 9S or area 929 in FIG. 9AA) that starts at the first location (e.g., 926 in FIG. 9S) and ends at the second location (e.g., 930 in FIG. 9S). In some embodiments, the selected content is enclosed by the selection box that encloses a word at the first location and a word at the second location and every word in between (FIG. 9AA). In some embodiments, the first location corresponds to the location of the contact on the touch-sensitive surface at the time that a first press input is received (e.g., in the middle of the word “nation” at time  $T_3$  in FIG. 9S), and the second location corresponds to the location of the contact on the touch-sensitive surface when a second press input is received (e.g., in the middle of the word “under” at time  $T_5$  in FIG. 9V).

While the content between the first location and the second location is selected (e.g., after moving at least the portion of the text selection indicator to the second location), the device detects (1112) a second press input by the contact on the touch-sensitive surface. For example, as shown in FIG. 9V, the device detects an increase in intensity of the contact above an intensity threshold, such as a deep press threshold  $IT_D$  at time  $T_5$ .

In response to detecting the second press input by the contact on the touch-sensitive surface, the device performs (1114) a text selection operation, associated with the content between the first location and the second location, in accordance with the second press input. In some embodiments, the contact in the first press input, the movement across the touch-sensitive surface, and the second press input is a single continuous contact with the touch-sensitive surface (e.g., contact 924, contact 925, or contact 927).

In some embodiments, in response to detecting the first press input by the contact followed by movement of the contact across the touch-sensitive surface: the device displays (1116) at least the portion of the text selection indicator at the second location within the content. For example, the device displays a cursor at the second location on the display (FIG. 9U) or displays an edge of a selection box at the second location on the display (FIG. 9AA), where the edge of the selection box corresponds to one end of the selected content. In some embodiments, the current location of the cursor corresponds to the current location of the contact on the touch-sensitive surface during the movement of the contact on the touch-sensitive surface.

In some embodiments, the text selection operation includes (1118) stopping selection of content at the second

location and maintaining selection of the content between the first location and the second location (e.g., FIG. 9V).

In some embodiments, after detecting the second press input and while the content between the first location and the second location remains selected, the device detects (1120) lift-off of the contact, and in response to detecting the lift-off of the contact, the device displays an action menu. For example, after detecting the second press input at a location on the touch-sensitive surface that corresponds to the second location on the display (e.g., in the middle of the word “under”), the device detects lift-off of the contact from that location on the touch-sensitive surface without detecting further movement of the contact. In response, the device displays an action menu bar 940 or other area that shows actions that can be performed on the selected portion of the text input (e.g., copying, defining, cutting, pasting, etc.) for the selected content between the first location and the second location.

In some embodiments, after detecting the second press input by the contact on the touch-sensitive surface and stopping the selection of the content at the second location, the device detects (1124) further movement of the contact. In response to detecting the further movement of the contact, the device displays at least a portion of the text selection indicator at a third location within the content. For example, in FIG. 9W, after detecting the second press input at a location on the touch-sensitive surface that corresponds to the second location on the display (e.g., in FIG. 9V, the press input at  $T_5$  at a location on the touch-sensitive surface that corresponds to the middle of the word “under” on the display), the device detects further movement of the contact from that location on the touch-sensitive surface to another location on the touch-sensitive surface (e.g., in FIG. 9W, to a location on the touch-sensitive surface that corresponds to the middle of the word “of” at  $T_6$ ). In response, the device moves the cursor 922 or an edge of the selection box to the third location (e.g., to the middle of the word “of” in FIG. 9W) in accordance with the movement of the contact on the touch-sensitive surface.

In some embodiments, in response to detecting the further movement of the contact, the device cancels (1126) selection of content between the first location and the second location without selecting content between the second location and the third location (FIG. 9W).

In some embodiments, the text selection operation includes (1128) cancelling selection of content between the first location and the second location (FIG. 9AB).

In some embodiments, after detecting the second press input by the contact on the touch-sensitive surface and canceling the selection of content between the first location and the second location, the device detects (1130) further movement of the contact. In response to detecting the further movement of the contact, the device selects content between the second location and a third location (FIGS. 9AB-9AC).

In some embodiments, while the content between the second location and the third location is selected, the device detects (1132) lift-off of the contact (e.g., without detecting further movement of the contact). In response to detecting the lift-off of the contact while the content between the second location and the third location is selected, the device stops selection of the content at the third location and maintains selection of the content between the second location and the third location (as shown in FIGS. 9AC-9AD).

In some embodiments, before displaying the text selection indicator at the first location within the content, the device detects (1134) an initial press input by the contact on the touch-sensitive surface. In response to detecting the initial

press input, the device displays the text selection indicator at an initial location within the content that corresponds to a location of the initial press input on the touch-sensitive surface. In some embodiments, the initial press input is (1136) detected at a location on the touch-sensitive surface that corresponds to a location of the content on the display. When the initial press input is detected at a location that corresponds to the first location within the content, the text selection indicator (e.g. the cursor 922) is displayed at the first location within the content. If the initial press input is detected at a location that does not correspond to the first location within the content, the text selection indicator is displayed at the first location within the content when the contact, after making the initial press input, moves to a location on the touch-sensitive surface that corresponds to the first location. For example, for a “first location” of position marker 945 in FIG. 9R (which corresponds to cursor 922) between the letters “n” and “a” in “nation,” the position marker was moved to this location after the initial press input shown in FIG. 9Q placed position marker 945 between the letters “r” and “o” in “from.”

In some embodiments, the display is a touch-sensitive display that includes the touch-sensitive surface, and the device concurrently displays (1138), on the touch-sensitive display, the content and an onscreen keyboard. In some embodiments, the initial press input is detected on the onscreen keyboard (FIG. 9A).

In some embodiments, the display is a touch-sensitive display that includes the touch-sensitive surface, and the device concurrently displays (1140), on the touch-sensitive display, the content and an onscreen keyboard. Before displaying the text selection indicator at the first location within the content, the device detects (1142) a multi-contact drag input (e.g., a two-finger drag input as shown in FIG. 7B) on the onscreen keyboard. In response to detecting the multi-contact drag input on the onscreen keyboard, the device displays the text selection indicator at an initial location within the content based on a location of the multi-contact drag input on the onscreen keyboard. In some embodiments, as shown in FIG. 7B, the multi-contact drag input is detected on the onscreen keyboard, the keyboard is converted to a virtual trackpad as described with respect to FIG. 9B, and the text selection indicator is displayed. Subsequent movement of the contact(s) in the multi-contact drag input on the virtual trackpad moves the text selection indicator within the content.

In some embodiments, the content includes (1144) editable content and the text selection indicator includes a cursor (FIG. 9A). In such embodiments, the device displays (1146) a magnifying loupe that displays a magnified version of the cursor and a region surrounding the cursor in response to a deep press, as shown in FIG. 9Q. Further, when selecting the content between the first location and the second location, the device moves (1148) the cursor one character space at a time in response to detecting the movement of the contact across the touch-sensitive surface and selects one additional character at a time in accordance with the movement of the cursor (FIG. 9S).

In some embodiments, the content includes (1150) read-only content and the text selection indicator includes a selection area (e.g., a rectangular selection box 929, FIG. 9Z). In such embodiments, displaying the text selection indicator at the first location includes displaying a first word (e.g., “Translation” in FIG. 9Z) located at the first location within the selection area. When selecting the read-only content between the first location and the second location, the device expands (1152) the selection area one word at a

time in accordance with the movement of the contact across the touch-sensitive surface and selects one additional word at a time in accordance with the expansion of the selection area (e.g., “Translation: A U.S. Gift” in selection area 929 in FIG. 9AA). In some embodiments, the device displays (1154) a magnifying loupe that displays a magnified version of the selection area and a region surrounding the selection area.

In some embodiments, the device foregoes (1156) performing the text selection operation, in response to detecting the second press input, in accordance with a determination that the second press input is accompanied by simultaneous movement of the contact across the touch-sensitive surface. For example, the text selection operation is not performed when the device detects the second press input accompanied by simultaneous movement of the contact. In other words, movement cancels the operation that is typically triggered by the second press input.

In some embodiments, when the text is editable text, the text selection indicator is a cursor and selecting content between the first location and the second location includes (1158) expanding the selection character-by-character in accordance with movement of the contact on the touch-sensitive surface (FIG. 9S); and when the text is non-editable text, the text selection indicator is a selection region that initially encompasses a single word and selecting content between the first location and the second location includes expanding the selection word-by-word in accordance with movement of the contact on the touch-sensitive surface (FIG. 9AA).

It should be understood that the particular order in which the operations in FIGS. 11A-11F have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., methods 400 and 1000) are also applicable in an analogous manner to method 1100 described above with respect to FIGS. 11A-11F. For example, the contacts, gestures, user interface objects, intensity thresholds, and/or animations described above with reference to method 1100 optionally have one or more of the characteristics of the contacts, gestures, user interface objects, intensity thresholds, and/or animations described herein with reference to other methods described herein (e.g., methods 400 and 1000). For brevity, these details are not repeated here.

In accordance with some embodiments, FIG. 12 shows a functional block diagram of an electronic device 1200 configured in accordance with the principles of the invention as described above. The functional blocks of the device may be implemented by hardware, software, or a combination of hardware and software to carry out the principles of the invention. It is understood by persons of skill in the art that the functional blocks described in FIG. 12 may be combined or separated into sub-blocks to implement the principles of the invention as described above. Therefore, the description herein may support any possible combination or separation or further definition of the functional blocks described herein.

In some embodiments, the electronic device 1200 includes a display unit 1202 configured to concurrently display an onscreen keyboard and a content presentation region on the display unit 1202, wherein the content presentation region displays text input received from the

onscreen keyboard; a touch-sensitive surface unit **1204** configured to receive user touch inputs; one or more sensor units **1206** to detect intensity of contacts with the touch-sensitive surface unit **1204**; and a processing unit **1208** coupled to the display unit **1202**, the touch-sensitive surface unit **1204**, and the one or more sensor units **1206**. In some embodiments, the processing unit **1208** includes a detecting unit **1210**, a determining unit **1216**, an obscuring unit **1218**, a moving unit **1214**, and a selecting unit **1212**.

The processing unit **1208** is configured to: detect a touch input on the onscreen keyboard displayed on the touch-sensitive surface unit **1204** (e.g., with the detecting unit **1210**); in response to detecting the touch input on the onscreen keyboard displayed on the display unit **1202**, determine whether the touch input satisfies one or more criteria for entering a text selection mode (e.g., with the determining unit **1216**); and in accordance with a determination that the touch input satisfies the one or more criteria for entering the text selection mode: concurrently display (e.g., with the displaying unit **1202**), in the content presentation region, a first cursor at a first location and a second cursor at a second location that is different from the first location.

In some embodiments, the one or more criteria for entering the text selection mode include the touch input including a two-finger drag gesture over the onscreen keyboard.

In some embodiments, the device has one or more sensor units **1206** to detect intensity of contacts with the touch-sensitive display; the touch input on the touch-sensitive display includes an input by a contact on the onscreen keyboard, and the one or more criteria for entering the text selection mode include the contact on the onscreen keyboard having an intensity that exceeds a predetermined deep press intensity threshold.

In some embodiments, the processing unit **1208** is configured to: in accordance with the determination that the touch input satisfies the one or more criteria for entering the text selection mode: visually obscure keys on the onscreen keyboard (e.g., with the obscuring unit **1218**).

In some embodiments, visually obscuring the keys on the onscreen keyboard includes applying a blurring effect to the onscreen keyboard (e.g., with the display unit **1202**).

In some embodiments, visually obscuring the keys on the onscreen keyboard includes transforming the onscreen keyboard into an onscreen touchpad (e.g., with the display unit **1202**).

In some embodiments, visually obscuring the keys on the onscreen keyboard includes making the onscreen keyboard semitransparent to partially reveal content lying underneath the onscreen keyboard (e.g., with the display unit **1202**).

In some embodiments, the second location is based on a location of an initial contact in the touch input; and the first location is a permitted insertion position in the content presentation region that is based on the second location.

In some embodiments, the first location is an insertion position at which the first cursor is located when the touch input is determined to satisfy the one or more criteria for entering the text selection mode; and the second location is displaced from the first location by a predetermined offset.

In some embodiments, one of the first and second cursors is already displayed in the content presentation region before both of the first and second cursors are concurrently displayed in the content presentation region.

In some embodiments, the processing unit **1208** is further configured to: detect movement of one or more contacts of the touch input (e.g., with the detecting unit **1210**); and move the second cursor within the content presentation

region in accordance with the movement of the one or more contacts of the touch input (e.g., with the moving unit **1214**).

In some embodiments, the processing unit **1208** is further configured to: move the first cursor based on the movement of the second cursor, wherein movement of the first cursor includes discrete movements between permitted insertion positions in the content presentation region (e.g., with the moving unit **1214**).

In some embodiments, the processing unit **1208** is further configured to: detect a lift-off of the touch input after detecting the movement of the one or more contacts of the touch input (e.g., with the detecting unit **1210**); and in response to detecting the lift-off of the touch input: cease to display the second cursor (e.g., with the display unit **1202**).

In some embodiments, the processing unit **1208** is further configured to: in response to detecting the lift-off of the touch input, maintain display of the first cursor at a respective permitted insertion position reached by the first cursor after the discrete movements of the first cursor (e.g., with the display unit **1202**).

In some embodiments, the processing unit **1208** is further configured to: in response to detecting the lift-off of the touch input, cease to display the first cursor (e.g., with the display unit **1202**).

In some embodiments, the onscreen keyboard is obscured in accordance with the determination that the touch input satisfies the one or more criteria for entering the text selection mode, and the processing unit **1208** is further configured to: in response to detecting the lift-off of the touch input, restore display of the onscreen keyboard (e.g., with the display unit **1202**).

In some embodiments, the device has one or more sensor units **1206** to detect intensity of contacts with the touch-sensitive surface unit **1204**, and the processing unit **1208** is further configured to: in the text selection mode, detect that an intensity of a contact in the touch input exceeds a predetermined intensity threshold (e.g., with the detecting unit **1210**); after detecting that the intensity of the contact in the touch input exceeds the predetermined intensity threshold, detect movement of the contact in the touch input (e.g., with the detecting unit **1210**); in response to detecting the movement of the contact in the touch input, after detecting that the intensity of the contact in the touch input exceeds the predetermined intensity threshold: select a portion of the text input in accordance with the movement of the contact in the touch input (e.g., with the selecting unit **1212**).

In some embodiments, the selected portion of the text input begins at a position of the first cursor when the detected intensity of the contact in the touch input exceeded the predetermined intensity threshold.

In some embodiments, the processing unit **1208** is further configured to: detect lift-off of the contact in the touch input after selecting the portion of the text input in accordance with the movement of the contact in the touch input (e.g., with the detecting unit **1210**); and, in response to detecting the lift-off of the contact in the touch input, confirm selection of the portion of the text input (e.g., with the selecting unit **1212**).

In some embodiments, the processing unit **1208** is further configured to: after selecting the portion of the text input, while the portion of the text input is selected, detect an intensity of the contact in the touch input that exceeds the predetermined threshold (e.g., with the detecting unit **1210**); and, in response to detecting the intensity of the contact in the touch input that exceeds the predetermined threshold

91

while the portion of the text input is selected, clear selection of the portion of the text input (e.g., with the selecting unit 1212).

In some embodiments, the processing unit 1208 is further configured to: after selecting the portion of the text input, while the portion of the text input is selected, detect an intensity of the contact in the touch input that exceeds the predetermined threshold and that is followed by lift-off of the contact without further movement of the contact (e.g., with the detecting unit 1210); and, in response to detecting the intensity of the contact in the touch input that exceeds the predetermined threshold and that is followed by lift-off of the contact without further movement of the contact, confirm selection of the portion of the text input (e.g., with the selecting unit 1212).

In some embodiments, the processing unit 1208 is further configured to: after selecting the portion of the text input, while the portion of the text input is selected, detect an intensity of the contact in the touch input that exceeds the predetermined threshold and that is followed by further movement of the contact (e.g., with the detecting unit 1210); and, in response to detecting the intensity of the contact in the touch input that exceeds the predetermined threshold and that is followed by the further movement of the contact: clear selection of the portion of the text input (e.g., with the selecting unit 1212).

In some embodiments, the processing unit 1208 is further configured to: in response to detecting the intensity of the contact in the touch input that exceeds the predetermined threshold and that is followed by the further movement of the contact: start selection of a new portion of the text input in accordance with the further movement of the contact (e.g., with the selecting unit 1212).

In some embodiments, the processing unit 1208 is further configured to: in response to detecting the intensity of the contact in the touch input that exceeds the predetermined threshold and that is followed by the further movement of the contact: further move the second cursor and the first cursor within the content presentation region in accordance with the further movement of the contact (e.g., with the moving unit 1214).

In some embodiments, the device has one or more sensor units (1206) to detect intensity of contacts with the touch-sensitive display, and the processing unit 1208 is further configured to: in the text selection mode, detect a first local intensity peak in the touch input followed by a second local intensity peak in the touch input that both exceed a predetermined intensity threshold (e.g., with the detecting unit 1210); and, in response to detecting the first local intensity peak followed by the second local intensity peak that both exceed the predetermined intensity threshold, select a first predetermined unit of the text input according to a current location of the first cursor (e.g., with the selecting unit 1212).

In some embodiments, the processing unit 1208 is further configured to: after detecting the first local intensity peak followed by the second local intensity peak, detect a third consecutive local intensity peak in the touch input that exceeds the predetermined intensity threshold (e.g., with the detecting unit 1210); and in response to detecting the three consecutive local intensity peaks in the touch input that all exceed the predetermined deep press intensity threshold, select a second predetermined unit of the text input that is larger than and includes the first predetermined unit of the text input (e.g., with the selecting unit 1212).

In some embodiments, the electronic device 1200 includes a display unit 1202 configured to, while a contact

92

is detected on the touch-sensitive surface unit 1204, concurrently display on the display unit 1202 content and a text selection indicator at a first location within the content; a touch-sensitive surface unit 1204 configured to receive user contacts; one or more sensor units 1206 to detect intensity of contacts with the touch-sensitive surface unit 1204; and a processing unit 1208 coupled to the display unit 1202, the touch-sensitive surface unit 1204, and the one or more sensor units 1206. In some embodiments, the processing unit 1208 includes a detecting unit 1210, a determining unit 1216, an obscuring unit 1218, a moving unit 1214, and a selecting unit 1212.

The processing unit 1208 is configured to: detect a first press input by the contact followed by movement of the contact across the touch-sensitive surface unit 1204 that corresponds to movement of at least a portion of the text selection indicator from the first location to a second location on the display unit 1202 (e.g., with the detecting unit 1210); in response to detecting the first press input by the contact followed by movement of the contact across the touch-sensitive surface unit 1204, select content between the first location and the second location (e.g., with the selecting unit 1212); while the content between the first location and the second location is selected, detect a second press input by the contact on the touch-sensitive surface unit 1204 (e.g., with the detecting unit 1210); in response to detecting the second press input by the contact on the touch-sensitive surface unit, perform a text selection operation, associated with the content between the first location and the second location, in accordance with the second press input, wherein the contact in the first press input, the movement across the touch-sensitive surface unit 1204, and the second press input is a single continuous contact with the touch-sensitive surface unit 1204 (e.g., with the selecting unit 1212).

In some embodiments, detecting the first press input by the contact followed by movement of the contact across the touch-sensitive surface unit 1204 includes: detecting an increase in intensity of the contact above a predetermined intensity threshold followed by detecting a decrease in intensity of the contact to an intensity that remains above a predetermined minimum intensity value (e.g., with the detecting unit 1210).

In some embodiments, the processing unit 1208 is configured to: in response to detecting the first press input by the contact followed by movement of the contact across the touch-sensitive surface unit 1204: display at least the portion of the text selection indicator at the second location within the content (e.g., with the display unit 1202).

In some embodiments, wherein the text selection operation includes stopping selection of content at the second location and maintaining selection of the content between the first location and the second location (e.g., with the selecting unit 1212).

In some embodiments, the processing unit 1208 is configured to: after detecting the second press input and while the content between the first location and the second location remains selected, detect lift-off of the contact (e.g., with the detecting unit 1210); and in response to detecting the lift-off of the contact, display an action menu for the selected content between the first location and the second location (e.g., with the display unit 1202).

In some embodiments, the processing unit 1208 is configured to: after detecting the second press input by the contact on the touch-sensitive surface unit 1204 and stopping the selection of the content at the second location, detect further movement of the contact (e.g., with the detecting unit 1210); and in response to detecting the further

movement of the contact, display at least a portion of the text selection indicator at a third location within the content (e.g., with the display unit 1202).

In some embodiments, the processing unit 1208 is configured to: in response to detecting the further movement of the contact, cancel selection of content between the first location and the second location without selecting content between the second location and the third location (e.g., with the selecting unit 1212).

In some embodiments, the text selection operation includes cancelling selection of content between the first location and the second location.

In some embodiments, the processing unit 1208 is configured to: after detecting the second press input by the contact on the touch-sensitive surface unit and canceling the selection of content between the first location and the second location, detect further movement of the contact (e.g., with the detecting unit 1210); and, in response to detecting the further movement of the contact, select content between the second location and a third location (e.g., with the selecting unit 1212).

In some embodiments, the processing unit 1208 is configured to: while the content between the second location and the third location is selected, detect lift-off of the contact (e.g., with the detecting unit 1210); and, in response to detecting the lift-off of the contact while the content between the second location and the third location is selected, stop selection of the content at the third location and maintaining selection of the content between the second location and the third location (e.g., with the selecting unit 1212).

In some embodiments, the processing unit 1208 is configured to: before displaying the text selection indicator at the first location within the content, detect an initial press input by the contact on the touch-sensitive surface unit 1204 (e.g., with the detecting unit 1210); and in response to detecting the initial press input, enable display of the text selection indicator at an initial location within the content that corresponds to a location of the initial press input on the touch-sensitive surface unit 1204.

In some embodiments, the display unit 1202 is a touch-sensitive display that includes the touch-sensitive surface unit 1204, and the processing unit 1208 is configured to: concurrently display, on the touch-sensitive display, the content and an onscreen keyboard, wherein the initial press input is detected on the onscreen keyboard.

In some embodiments, the initial press input is detected at a location on the touch-sensitive surface unit 1204 that corresponds to a location of the content on the display unit 1202.

In some embodiments, the display unit 1202 is a touch-sensitive display that includes the touch-sensitive surface unit 1204, and the processing unit 1208 is configured to: concurrently enable display of, on the touch-sensitive display, the content and an onscreen keyboard; before displaying the text selection indicator at the first location within the content, detect a multi-contact drag input on the onscreen keyboard (e.g., with the detecting unit 1210); and, in response to detecting the multi-contact drag input on the onscreen keyboard, enable display of the text selection indicator at an initial location within the content based on a location of the multi-contact drag input on the onscreen keyboard.

In some embodiments, the content includes editable content and the text selection indicator includes a cursor.

In some embodiments, the processing unit 1208 is configured to: enable display of a magnifying loupe that displays a magnified version of the cursor and a region surrounding the cursor.

In some embodiments, selecting the content between the first location and the second location includes: moving the cursor one character space at a time in response to detecting the movement of the contact across the touch-sensitive surface unit 1204 (e.g., with the moving unit 1214); and selecting one additional character at a time in accordance with the movement of the cursor (e.g., with the selecting unit 1212).

In some embodiments, the content includes read-only content and the text selection indicator includes a selection area; and displaying the text selection indicator at the first location includes displaying a first word located at the first location within the selection area (e.g., with the display unit 1202).

In some embodiments, the processing unit 1208 is configured to: enable display of a magnifying loupe that displays a magnified version of the selection area and a region surrounding the selection area.

In some embodiments, selecting the content between the first location and the second location includes: expanding the selection area one word at a time in accordance with the movement of the contact across the touch-sensitive surface unit 1204 (e.g., with the selecting unit 1212); and selecting one additional word at a time in accordance with the expansion of the selection area (e.g., with the selecting unit 1212).

In some embodiments, the processing unit 1208 is configured to: forego performing the text selection operation, in response to detecting the second press input, in accordance with a determination that the second press input is accompanied by simultaneous movement of the contact across the touch-sensitive surface unit 1204.

In some embodiments, when the text is editable text, the text selection indicator is a cursor and selecting content between the first location and the second location includes expanding the selection character-by-character in accordance with movement of the contact on the touch-sensitive surface unit 1204 (e.g., with the selecting unit 1212); and when the text is non-editable text, the text selection indicator is a selection region that initially encompasses a single word and selecting content between the first location and the second location includes expanding the selection word-by-word in accordance with movement of the contact on the touch-sensitive surface unit 1204 (e.g., with the selecting unit 1212).

Turning to FIGS. 13A-13Q, these figures illustrate exemplary user interfaces for selecting content, moving a text selection indicator, and changing keyboard appearance based on contact intensity (e.g., pressure), in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below with respect to FIGS. 14A-14H. FIGS. 13A-13Q include intensity versus time diagrams that show the variations of a characteristic intensity of the contact on the touch-sensitive surface relative to a plurality of intensity thresholds (e.g., "IT<sub>D</sub>", "IT<sub>L</sub>", and "IT<sub>O</sub>").

In FIG. 13A, editable content 1300 is displayed in a content presentation region 1302 while an application is in a document editing mode. The application runs on a device 100 that has one or more sensors (e.g., contact intensity sensor(s) 259, FIG. 2B) to detect intensity of contacts with the touch-sensitive display. In the document editing mode, an onscreen keyboard 1321 is displayed for text inputs. A

user may enter text by touch inputs (e.g., by contact) on the onscreen keyboard **1321** and confirm completion of the editing by performing another touch input (e.g., a tap on “done” button) to exit the editing mode. An insertion marker (e.g., cursor **1322**) is displayed to indicate a current location for text inputs.

When entering text into the content region **1302**, a character can be entered upon detecting a touchdown or liftoff event. In some embodiments, entering the text into the content region **1302** includes entering a character that corresponds to character key at a location at which touchdown of the contact was detected on the onscreen keyboard. For example, touchdown of the finger contact **1324** was detected on the character key “h”. In response to detecting the touchdown, character “h” is entered. In some embodiments, entering the text into the content region includes entering a character that corresponds to character key at a location at which liftoff of the contact was detected on the onscreen keyboard. For example, in response to liftoff of the finger contact **1324** from character key “h”, character “h” is entered.

In FIG. **13B**, at time  $T_1$ , while in the editing mode and displaying the keyboard **1321**, the device detects a deep press by a finger contact **1324** on the onscreen keyboard **1321**, such that the intensity of the press input has increased above a text selection intensity threshold (e.g.,  $IT_D$ ) before the movement of the contact is detected. In response to detecting the deep press, the appearance of the keyboard **1321** changes to indicate that the application has entered a text selection mode. In the text selection mode, the keyboard **1321** is not responsive to keystrokes, but rather serves as an onscreen touchpad or track pad for moving the cursor or selecting content.

In some embodiments, the press input is a stationary press input such that there is less than a threshold amount of movement between when touchdown of the finger contact **1324** is detected on the onscreen keyboard **1321** and when the increase in the characteristic intensity of the contact over the text selection intensity threshold  $IT_D$  is detected. In some embodiments, if more than the threshold amount of movement is detected, upon liftoff, a character entry operation is performed based on which character entry key the contact is over when liftoff of the contact is detected.

As shown in FIG. **13B**, in some embodiments, the keys are visually obscured. Visually obscuring keys on the keyboard **1321** provides an intuitive indication that the function of the keyboard **1321** has changed. In some embodiments, the onscreen keyboard **1321** is dimmed, faded, or blurred relative to the keyboard **1321** shown in FIG. **13A** prior to detecting the deep press, such that the keys are no longer visible or clearly displayed as before. In some embodiments, as shown in FIG. **13B**, an indication of a location of the keys is maintained while the appearance of the characters is obscured (e.g., by maintaining display of the shapes of some or all of the keys on the keyboard while removing or blurring the characters on the key caps) and three-dimensional characteristics (e.g., a three-dimensional shape, drop shadow, etc.) of some or all of the keys are no longer visible. In some embodiments, the keyboard **1321** becomes semitransparent, to reveal content lying underneath the keyboard.

When the keyboard **1321** serves as an onscreen touch pad or track pad, in response to detecting finger movement **1332** started on the keyboard **1321**, text selection operations such as moving the cursor **1322** as shown in FIG. **13B** within the content region **1302** or selecting text within the content region **1302** as shown in FIGS. **13D-13Q** are performed. For example, after entering the text selection mode, upon detect-

ing movement of the finger contact **1324** along a path **1332**, which started from the keyboard region **1321**, extended to the content region **1302**, and returned back to the keyboard region **1321**, the cursor **1322** is moved along a similar path in accordance with the movement of the finger contact **1324**. In some embodiments, in response to detecting movement of the contact after the touch input has satisfied the text selection criteria, instead of displaying cursor **1322** and cursor movement, a ghost cursor and a floating cursor are displayed, and the floating cursor is moved along a similar path in accordance with the movement of the finger contact **1324** as shown in FIGS. **9B-9D** and described in greater detail above.

FIGS. **13C-13Q** illustrate a variety of possible text selection behaviors that can occur after entering text selection mode (e.g., after time  $T_1$ ), in accordance with some embodiments.

Turning to FIG. **13C**, at the end of the text selection mode (e.g., detecting liftoff of the contact such that the intensity of the press input has fallen to zero), in response to detecting liftoff of the contact, the device exits the text selection mode of operation. In conjunction with the end of the text selection mode of operation, the device reverses the change in appearance of the onscreen keyboard **1321** to reveal the characters on the keys of the onscreen keyboard **1321**. As shown in FIG. **13C**, the device reverses a fading or blurring of the keyboard **1321** to indicate that the device is no longer in the text selection mode of operation. In some embodiments, three-dimensional characteristics (e.g., a three-dimensional shape, drop shadow, etc.) of some or all of the keys are restored, and the characters on the key caps are displayed.

In FIG. **13D**, continuing the example shown in FIG. **13B**, while in the text selection mode, at time  $T_2$ , when a cursor is located in the middle of the word “imperdiet” (not shown in FIG. **13D**), the device detects a portion of the touch input (e.g., a second deep press with the same contact **1324**), such that the touch input satisfies selection-start criteria, which include a criterion that is met when the characteristic intensity of the contact increases above a selection-start intensity threshold. In some embodiments, the selection-start intensity threshold is the same as, greater than, or less than the text selection intensity threshold (e.g.,  $IT_D$ ) before the movement of the contact is detected. For illustration purpose, the selection-start intensity threshold is shown in FIG. **13D** as  $IT_D$ .

In response to detecting the second deep press by the same contact on the onscreen keyboard **1321** at time  $T_2$ , the device begins to select a portion of the text input **1328** in accordance with the movement **1332** of the contact in the touch input. After time  $T_2$ , during the movement **1332**, the intensity of the contact can be above or below the selection-start intensity threshold  $IT_D$ . In some embodiments, the text selection starts when an increase in intensity of the contact is detected while the contact is substantially stationary (e.g., moves not more than a threshold distance within a threshold amount of time before the characteristic intensity of the contact increases above the selection-start intensity threshold).

In FIG. **13E**, at time  $T_3$ , the device detects lift-off of the contact in the touch input, such that the intensity of the contact is below a contact detection threshold. In response to detecting the lift-off of the contact, in some embodiments, the device confirms selection of the portion of the text input **1328**. In some embodiments, a selection box **1328** (e.g., a grey box) is displayed on the selected portion of the text input, and/or a menu bar **1340** is displayed that showing actions that can be performed on the selected portion of the

text input (e.g., copying **1344**, defining, cutting **1342**, pasting, etc.). In some embodiments, the menu bar **1340** is displayed in response to a touch input on the selection box **1328**. Thus, FIGS. **13D** and **13E** illustrate using a substantially stationary deep press input by a contact **1324** to initiate text selection at time  $T_2$ , then movement of the contact to select text, followed by lift-off of the contact to confirm the selection at time  $T_3$ .

In FIG. **13F**, continuing the example shown in FIG. **13D**, instead of detecting a lift-off of the contact, after time  $T_2$  and while continuing to detect the contact **1324** on the touch-sensitive display **112**, the device detects a subsequent change in intensity of the contact (e.g. a substantially stationary deep press with the same contact) at time  $T_3$ . Upon detecting the substantially stationary deep press at time  $T_3$ , in accordance with a determination that the change in intensity of the contact satisfies selection-cancellation criteria, the device cancels the selection (e.g., deselecting the selected content and redisplaying the cursor). In some embodiments, as shown in FIG. **13F**, upon the selection cancellation, the cursor **1322** is displayed at the end of the selection (e.g., at the end of the word “enim”). In some embodiments, upon cancelling the selection, the cursor **1322** is displayed at the beginning of the selection.

In some embodiments, the selection-cancellation criteria include a criterion that is met when the characteristic intensity of the contact increases above a selection-cancellation intensity threshold (e.g., a threshold that is the same as, greater than, or less than the text-selection intensity threshold and/or the selection-start intensity threshold). For illustration purpose, the selection-cancellation intensity threshold shown in FIG. **13F** is the same as the text-selection intensity threshold and the selection-start intensity threshold  $IT_D$ . In some embodiments, the selection-cancellation criteria are met when an increase in intensity of the contact is detected while the contact is substantially stationary (e.g., the contact **1324** moves no more than a threshold distance within a threshold amount of time before the characteristic intensity of the contact increases above the selection-cancellation intensity threshold).

In FIG. **13G**, following the substantially stationary deep press at time  $T_3$  to cancel the selection and redisplay the cursor at the end of the word “enim”, while continuing to detect the contact on the touch-sensitive display **112** after time  $T_3$ , the device detects a subsequent change in the intensity of the contact at time  $T_4$ . In response to detecting the subsequent change in the characteristic intensity of the contact and in accordance with a determination that the touch input (e.g., the subsequent change in the characteristic intensity of the contact at time  $T_4$ ) satisfies the selection-start criteria described above with respect to FIG. **13D**, the device starts a new selection of content in the content region **1302** in accordance with the finger movement **1332**. The new selection starts at the end of the word “enim”, where the cursor **1322** was located when the deep press was detected at time  $T_4$ , and expands character by character in accordance with the finger movement **1332**. Thus, FIGS. **13D**, **13F**, and **13G** illustrate a first deep press by a contact **1324** to initiate a text selection at time  $T_2$ , then movement of the contact **1324** to select text, followed by a second deep press with the same contact at time  $T_3$  to cancel the text selection and display a cursor at the end of the selection, and a third deep press with the same contact at time  $T_4$  to restart a new text selection.

In some embodiments, continuing the example shown in FIG. **13F**, the new text selection includes a selection of a respective word. When the third subsequent change detected

at time  $T_4$  includes an increase in the characteristic intensity of the contact above the selection-start intensity threshold, a word is selected at the location of the cursor. For example, in FIG. **13F**, after the selection cancellation at time  $T_3$ , the cursor **1322** is located at the end of the word “enim”. Subsequently, as shown in FIG. **13H**, the word “enim” is selected at the location of the cursor in response to detecting a deep press at time  $T_4$ .

In FIG. **13H**, the deep press by contact **1324** is substantially stationary. Alternatively, in some embodiments, when the third subsequent change in the touch input includes an increase in the characteristic intensity of the contact above the selection-start intensity threshold followed by movement of the contact, selection is started at the location of the cursor and expanded character by character in accordance with the movement of the contact; and in response to a subsequent increase in the characteristic intensity of the contact above a respective intensity threshold (e.g., the selection-start intensity threshold) within a threshold time, the current selection is expanded to include the entire word that was partially selected during the character-by-character expansion.

In FIG. **13I**, continuing the example shown in FIG. **13H**, while the respective word “enim” is selected, a subsequent finger movement **1332** is detected after time  $T_4$ . In response to detecting the subsequent finger movement **1332** while the respective word “enim” is selected, in accordance with a determination that the touch input meets selection-movement criteria, the selection of the first word “enim” is canceled, and a second word “imperdiet” is selected that is adjacent to the first word in a first direction (e.g., before or after the respective word) in accordance with the subsequent finger movement **1332**, such that the selected respective word is the second word “imperdiet”. As shown in FIG. **13H**, the subsequent finger movement **1332** is moving in a left/up direction. As a result, the word “imperdiet” that is before the word “enim” is selected. Conversely, in case a right/down finger movement is detected, a word after the word “enim” is selected.

In some embodiments, the selection-movement criteria include a movement criterion that is met when the contact moves more than a respective threshold amount (e.g., the contact is not substantially stationary and optionally a respective time criterion that is met when an amount of time between the third subsequent change in the characteristic intensity of the contact is detected and when the first subsequent movement of the contact is detected is less than a respective delay threshold). Thus, FIGS. **13H** and **13I** illustrate selecting a first word, cancels selection of the first word and selects a second word that is adjacent to a first word “enim” in a direction in accordance with the finger movement **1332**.

In FIG. **13J**, continuing the example shown in FIG. **13H**, while the respective word “enim” is selected, a subsequent finger movement **1332** is detected. In response to detecting the subsequent finger movement **1332** while the respective word “enim” is selected, in accordance with a determination that the touch input meets selection-expansion criteria at time  $T_4$ , the device expands the selection of the respective word “enim” to include a word “imperdiet” that is adjacent to the word “enim” in a direction of the finger movement **1332** (e.g., before or after the respective word “enim”) without selecting one or more words in the respective sentence “Numc viverra imperdiet enim.” that are adjacent to the respective word “enim” in the respective sentence in a direction that is different from the direction of the finger movement **1332**. In other words, the expansion only goes in

the direction corresponding to the finger movement **1332**, and does not expand to include words in the reverse direction of the movement (e.g., as distinguished from expansion to select the whole sentence or more described below with respect to FIGS. **13K-13Q**). In some embodiments, the selection expansion criteria include a criterion that is met when the contact moves more than the threshold amount (e.g., that the contact has remained stationary for at least a threshold amount of time prior to detecting the increase in intensity and that the increase in intensity was detected less than a threshold amount of time after detecting the third subsequent change in the characteristic intensity of the contact). Thus, FIGS. **13H** and **13J** illustrate selecting a word “enim” and expanding the selection word by word in a direction in accordance with the finger movement **1332**.

In FIG. **13K**, continuing the example shown in FIG. **13H**, while the respective word “enim” is selected, the device detects another subsequent change in the intensity of the contact above a respective intensity threshold (e.g., the selection-cancellation intensity threshold) at time  $T_5$ . The touch input **1324** meets selection-cancellation criteria described above with respect to FIG. **13F**, the device cancels selection of the respective sentence and displays the cursor **1332** at the end of the selection. Thus, FIGS. **13H** and **13K** illustrate a deep press to select a word at time  $T_4$  followed by another deep press at time  $T_5$  to cancel the selection.

In FIG. **13L**, continuing the example shown in FIG. **13H**, while the respective word “enim” is selected, the device detects another subsequent change in the intensity of the contact above a respective intensity threshold (e.g., the selection-start intensity threshold) at time  $T_5$ , such that the touch input **1324** meets sentence-selection criteria, e.g., the contact is substantially stationary before (e.g., just before) the subsequent change in intensity of the contact was detected at time  $T_5$  and the amount of time between  $T_4$ , when the previous subsequent change in the characteristic intensity of the contact is detected, and  $T_5$ , when the subsequent change in the characteristic intensity of the contact is detected, is less than a delay threshold. In response to detecting such change in the touch input at time  $T_5$ , (e.g., in response to detecting the subsequent change in the intensity of the contact at time  $T_5$ ), the device expands the selection **1328** to include the (entire) respective sentence “Nunc viverra imperdiet enim.” that contains the respective word “enim”. Thus, FIGS. **13H** and **13L** illustrate a deep press at time  $T_4$  to select a word followed by another deep press at time  $T_5$  within a threshold time and while the contact remains substantially stationary, to expand the selection to a sentence containing the selected word.

In FIG. **13M**, while the respective sentence “Nunc viverra imperdiet enim.” is selected, the device detects a subsequent movement of the contact **1332**. In response to detecting the subsequent movement of the contact **1332** while the respective sentence is selected and in accordance with a determination that the touch input meets selection-expansion criteria described above with respect to FIG. **13J**, the device expands the selection to include a sentence that is adjacent to the respective sentence in a first direction (e.g., before or after the respective sentence) in accordance with the subsequent movement of the contact (e.g., the expansion of the selection does not select one or more sentences in a respective paragraph that includes the respective sentence, that are adjacent to the respective sentence in the respective paragraph in a second direction that is different from the first direction). In other words, the expansion to include the sentence “Fusce posuere, magna sed pulvinar ultricies, purus lectus malesuada libero, sit amet commodo magna eros quis

urna.” only goes in the direction corresponding to the movement of the contact **1332**, and does not expand to include in the reverse direction of the movement (e.g., as distinguished from expansion to select the whole paragraph or more described below). Thus, FIGS. **13L** and **13M** illustrate after a sentence selection at time  $T_5$ , expanding the selection sentence by sentence in a direction in accordance with the finger movement **1332**.

In FIG. **13N**, continuing the example shown in FIG. **13L**, in some embodiments, while the respective sentence “Nunc viverra imperdiet enim.” is selected, the device detects a subsequent change in the characteristic intensity of the contact above the respective intensity threshold (e.g., the selection-start intensity threshold) at time  $T_6$ . In response to detecting the subsequent change in the characteristic intensity of the contact at time  $T_6$ , in accordance with a determination that the touch input meets the selection-cancellation criteria described above with respect to FIG. **13F**, the device cancels selection of the respective sentence and displays the cursor **1322** at the end of the selection. Thus, FIGS. **13L** and **13M** illustrate after a deep press to select a sentence at time  $T_5$ , in response to another deep press at time  $T_6$  (which is more than a threshold amount of time after  $T_5$ ), the sentence selection is cancelled.

In FIG. **13O**, following the deep press at time  $T_5$ , the device detects a subsequent change in the characteristic intensity of the contact above the respective intensity threshold (e.g., the selection-start intensity threshold) at time  $T_6$ . In response to detecting the subsequent change in the characteristic intensity of the contact at time  $T_6$ , in accordance with a determination that the touch input **1324** (e.g., the subsequent change in the characteristic intensity of the contact detected at time  $T_6$ ) meets paragraph-selection criteria (e.g., the paragraph-selection criteria include a movement criterion that is met when the contact moves less than the threshold amount within the threshold time period (e.g., is substantially stationary) before (e.g., just before) the subsequent change in intensity of the contact was detected at  $T_6$  and a time criterion that is met when an amount of time between when the deep press is detected at time  $T_5$  and when the subsequent change in the characteristic intensity of the contact is detected at time  $T_6$  is less than the delay threshold), the device expands the selection to include the (entire) respective paragraph that contains the respective sentence. Thus, FIGS. **13L** and **13O** illustrate after a deep press to select a sentence at time  $T_5$ , in response to detecting another deep press that meets paragraph-selection criteria, the sentence selection is expanded to a paragraph containing the sentence.

In FIG. **13P**, continuing the example shown in FIG. **13O**, while the respective paragraph is selected, the device detects subsequent movement of the contact **1332** after time  $T_6$ . In response to detecting the subsequent movement of the contact while the respective paragraph is selected, in accordance with a determination that the touch input (e.g., the movement detected at time  $T_6$ ) meets selection-expansion criteria described above with respect to FIG. **13J**, the device expands the selection to include a paragraph that is adjacent to the respective paragraph in a first direction (e.g., before or after the respective paragraph) in accordance with the subsequent movement of the contact **1332**.

For example, in FIG. **13P**, the expansion of the selection does not select one or more paragraph in a respective document that includes the respective paragraph, that are adjacent to the respective paragraph in the respective document in a second direction that is different from the first direction. In other words, the expansion only goes in the

direction corresponding to the movement of the contact, and does not expand to include in the reverse direction of the movement (e.g., as distinguished from expansion to select the whole document described below). Thus, FIGS. 13O and 13P illustrate after a paragraph selection, expanding the selection paragraph by paragraph in a direction in accordance with the finger movement 1332.

In FIG. 13Q, continuing the example shown in FIG. 13O, while the respective paragraph is selected, the device detects a subsequent change in the characteristic intensity of the contact above the respective intensity threshold (e.g., the selection-start intensity threshold) at time  $T_7$ . In response to detecting the subsequent change in the characteristic intensity of the contact at time  $T_7$ , in accordance with a determination that the touch input (e.g., the subsequent change in the characteristic intensity of the contact at  $T_7$ ) meets selection-cancellation criteria (e.g., the deep press detected at  $T_7$  is more than a threshold amount of time after the deep press detected at  $T_6$ ) described above with respect to FIG. 13F, the device cancels selection of the respective paragraph. Thus, FIGS. 13O and 13Q illustrate after a paragraph selection, in response to detecting a subsequent deep press that meets selection-cancellation criteria, cancelling the paragraph selection.

Though not shown in figures, continuing the example shown in FIG. 13O, while the respective paragraph is selected, the selected paragraph can be expanded to the entire document that contains the selected paragraph in response to detecting a subsequent deep press at  $T_7$  after time  $T_6$ . The subsequent deep press is a subsequent change in the characteristic intensity of the contact such that the subsequent change meets document-selection criteria, which include a movement criterion that is met when the contact moves less than the threshold amount within the threshold time period (e.g., is substantially stationary) before (e.g., just before) the subsequent deep press was detected, and a time criterion that is met when an amount of time between when the deep press is detected at time  $T_6$  and when the subsequent deep press is detected at  $T_7$  is less than the delay threshold.

FIGS. 14A-14H illustrate a flow diagram of method 1400 of content manipulation in accordance with some embodiments. Method 1400 is performed at an electronic device (e.g., portable multifunction device 100, FIG. 1A) with one or more processors, memory, and a display. In some embodiments, the display is a touch-screen display and the touch-sensitive surface is on or integrated with the display. In some embodiments, the display is separate from the touch-sensitive surface. Some operations in method 1400 are, optionally, combined and/or the order of some operations is, optionally, changed.

As described below, method 1400 provides an efficient way to manipulate a cursor. The method reduces the cognitive burden on a user when using a cursor, thereby creating a more efficient human-machine interface. For battery-operated electronic devices, enabling a user to manipulate a cursor faster and more efficiently conserves power and increases the time between battery charges.

The device concurrently displays (1402) an onscreen keyboard (e.g., keyboard 1321, FIG. 13A) and a content presentation region (e.g., region 1302, FIG. 13A) on the touch-sensitive display. In some embodiments, the content presentation region displays text input received from the onscreen keyboard (FIG. 13A). The device further detects (1404) a touch input on the onscreen keyboard displayed on the touch-sensitive display (e.g., by finger contact 1324, FIG. 13A). In some embodiments, detecting the touch input

includes detecting movement of a contact (e.g., FIGS. 13B and 13D etc.) and liftoff of the contact (e.g., FIGS. 13C and 13E).

In some embodiments, in response to detecting (1406) the touch input on the onscreen keyboard displayed on the touch-sensitive display, in accordance with a determination that the touch input satisfies text-selection criteria, the text-selection criteria include a criterion that is met when a characteristic intensity of the contact increases above a text-selection intensity threshold (e.g., a deep press with contact characteristic intensity increases above ITS at time  $T_1$ , FIG. 13B), the device performs (1408) a text selection operation based on the movement of the contact (FIGS. 13D-13Q). In some embodiments, the text-selection criteria include (1410) a criterion that is met when the contact does not move more than a threshold distance before detect an increase in the characteristic intensity of the contact above the text-selection intensity threshold (e.g., the finger contact 1324 is substantially stationary at time  $T_1$ , there is less than a threshold amount of movement between when touchdown of the contact 1324 is detected on the onscreen keyboard and when the increase in the characteristic intensity of the contact over the text-selection intensity threshold is detected at time  $T_1$ , FIG. 13B). In some embodiments, if more than the threshold amount of movement is detected, upon liftoff, a character entry operation is performed based on which character entry key the contact is over when liftoff of the contact is detected. In some embodiments, the text-selection operation includes (1412) one of: moving a cursor within the content region (as shown in FIG. 13B) or selecting text within the content region (e.g., as shown in FIGS. 13D-13Q).

In addition to text-selection operations, in response to detecting (1406) the touch input on the onscreen keyboard displayed on the touch-sensitive display and in accordance with a determination that the touch input satisfies text-entry criteria (e.g., as shown in FIG. 13A), the text-entry criteria include a criterion that is met when the characteristic intensity of the contact does not increase above the text-selection intensity threshold, the device enters (1414) text into the content presentation region based on the touch input (e.g., entering text when the contact characteristic intensity does not increase above ITS, FIG. 13A). In some embodiments, the text-entry criteria include (1416) a criterion that is met when the liftoff of the contact is detected while the contact is at a location of a character key of the onscreen keyboard. In some embodiments, the text-entry criteria include (1418) a criterion that is met when the contact does not move outside of the onscreen keyboard before liftoff of the contact is detected. In some embodiments, entering the text into the content region includes (1420) entering a character that corresponds to character key at a location at which touchdown of the contact was detected on the onscreen keyboard (e.g., entering character "h" when a touchdown of the contact 1324 is detected, FIG. 13A). In some embodiments, entering the text into the content region includes (1422) entering a character that corresponds to character key at a location at which liftoff of the contact was detected on the onscreen keyboard (e.g., entering character "h" when a liftoff of the contact 1324 is detected, FIG. 13A).

In some embodiments, in response to detecting that the text-selection criteria have been met, the device generates (1424) a tactile output (e.g., with one or more tactile output generating components of the device, 167 in FIG. 2A and/or 257 in FIG. 2B) that is indicative of an entry into a text selection mode of operation. In some embodiments, the tactile output that is indicative of entry into the text selection

mode of operation is different from the tactile output that is generated when a device alert such as a notification of an incoming message is provided by the device.

In some embodiments, in response to detecting that the text-selection criteria have been met, the device changes (1426) an appearance of the onscreen keyboard to indicate that the device is operating in a text selection mode of operation. In some embodiments, changing the appearance of the onscreen keyboard includes obscuring an appearance of characters on keys of the onscreen keyboard (e.g., blurring in FIG. 9N, fading, and/or removing the characters on the key caps in FIG. 13B). In some embodiments, an indication of a location of the keys is maintained while the appearance of the characters is obscured (e.g., by maintaining display of the shapes of some or all of the keys on the keyboard while removing or blurring the characters on the key caps and the drop shadows of the key caps, FIG. 13B). In some embodiments, the device ends (1428) the text selection mode of operation (e.g., detecting liftoff of the contact and, in response to detecting liftoff of the contact, exiting the text selection mode of operation, FIGS. 13C and 13E) and, in conjunction with the end of the text selection mode of operation, the device reverses the change in appearance of the onscreen keyboard to reveal the characters on the keys of the onscreen keyboard (e.g., reversing a fading, blurring of the keyboard to indicate that the device is no longer in the text selection mode of operation, FIGS. 13C and 13E).

In some embodiments, when the touch input satisfies the text-selection criteria, the device detects (1430) movement of the contact after the touch input has satisfied the text-selection criteria and moving a cursor (FIG. 13B) in the content region in accordance with the movement of the contact detected after the touch input has satisfied the text-selection criteria. In some embodiments, instead of displaying a cursor and moving the cursor, a ghost cursor and a floating cursor are displayed and moved in the content region in accordance with the movement of the contact, as described in greater detail above with respect to FIGS. 9B-9D).

In some embodiments, when the touch input satisfies the text-selection criteria, the device detects (1432) a first subsequent change (e.g., a deep press at time  $T_2$ , FIG. 13D) in the characteristic intensity of the contact (optionally, after first detecting a decrease in intensity of the contact to an intensity below the text-selection intensity threshold) followed by additional movement of the contact on the touch-sensitive display. In response to detecting (1434) the first subsequent change in the characteristic intensity of the contact and in accordance with a determination that the touch input satisfies selection-start criteria, the selection-start criteria include a criterion that is met when the characteristic intensity of the contact increases above a selection-start intensity threshold (e.g., a threshold that is the same as, greater than, or less than the text-selection intensity threshold  $IT_D$  before the movement of the contact is detected, FIG. 13D), the device starts (1436) to select content in the content region at a location of a cursor in accordance with the additional movement of the contact (e.g., starting the selection at the location of the cursor and expand the selection character by character in accordance with the movement of the contact as shown in FIG. 13G; or start selection at the word at the location of the cursor, and expand the selection word by word in accordance with the movement of the contact as shown in FIGS. 13H and 13J). On the other hand, in accordance with a determination that the touch input does not satisfy the selection-start criteria, the device moves the

cursor in accordance with the additional movement of the contact without starting to select content in the content region (FIG. 13B). In some embodiments, the selection-start criteria are met when an increase in intensity of the contact is detected while the contact is substantially stationary (e.g., moves not more than a threshold distance within a threshold amount of time before the characteristic intensity of the contact increases above the selection-start intensity threshold).

In some embodiments, when the touch input satisfies selection-start criteria, after starting to select content in the content region, the device detects (1438) liftoff of the contact from the touch-sensitive display and confirms the selection in response to detecting the liftoff of the contact (e.g., as shown in FIG. 13E).

Alternatively, when the touch input satisfies selection-start criteria, after starting to select content in the content region, and while continuing to detect the contact on the touch-sensitive display, the device detects (1440) a second subsequent change in intensity of the contact (e.g., a deep press at time  $T_3$  in FIG. 13F). In response to detecting (1442) the second subsequent change in the characteristic intensity of the contact and in accordance with a determination that the second subsequent change in the characteristic intensity of the contact satisfies selection-cancellation criteria, the selection-cancellation criteria include a criterion that is met when the characteristic intensity of the contact increases above a selection-cancellation intensity threshold (e.g., a threshold that is the same as, greater than, or less than the text-selection intensity threshold and/or the selection-start intensity threshold ITS), the device cancels (1444) the selection (e.g., deselecting the selected content and redisplaying the cursor, as shown in FIG. 13F). On the other hand, in response to detecting the second subsequent change in the characteristic intensity of the contact and in accordance with a determination that the second subsequent change in the characteristic intensity of the contact does not satisfy the selection-cancellation criteria (e.g., if the contact did not reach the selection-cancellation intensity threshold and/or the contact was not substantially stationary when the selection-cancellation intensity threshold was reached), the device maintains the selection (e.g., and expanding the selection or contracting the selection in accordance with continued movement of the contact on the touch-sensitive display, as shown in FIG. 13D). In some embodiments, the selection-cancellation criterion include (1446) a criterion that is met when the contact moves no more than a threshold distance within a threshold amount of time before the characteristic intensity of the contact increases above the selection-cancellation intensity threshold.

In some embodiments, in response to detecting that the selection-cancellation criteria have been met, the device generates (1448) a tactile output (e.g., with one or more tactile output generating components of the device, 167 in FIG. 2A and/or 257 in FIG. 2B) that is indicative of an exit from the text selection mode of operation. In some embodiments, the tactile output that is indicative of exit from the text selection mode of operation is different from the tactile output that is generated when a device alert such as a notification of an incoming message is provided by the device. In some embodiments, this tactile output is not generated when corresponding selection cancellation operations are performed in the text (as opposed to being performed on the keyboard).

In some embodiments, after canceling the selection, and while continuing to detect the contact on the touch-sensitive display, the device detects (1450) a third subsequent change

in the characteristic intensity of the contact (e.g., a deep press at time  $T_4$  in FIG. 13G). In response to detecting (1452) the third subsequent change in the characteristic intensity of the contact and in accordance with a determination that the touch input (e.g., the third subsequent change in the characteristic intensity of the contact) satisfies the selection-start criteria, the device starts (1454) to select content in the content region at a location of the cursor (as shown in FIG. 13G). On the other hand, in response to detecting the third subsequent change in the characteristic intensity of the contact and in accordance with a determination that the touch input (e.g., the third subsequent change in the characteristic intensity of the contact) does not satisfy the selection-start criteria, the device forgoes starting to select content in the content region.

In some embodiments, starting to select content in response to detecting the third subsequent change in the characteristic intensity of the contact includes (1456) selecting a respective word at the location of the cursor (as shown in FIG. 13H). For example, after the cancellation of the selection (e.g., in response to a deep press at time  $T_3$  in FIG. 13F), when the third subsequent change includes an increase in the characteristic intensity of the contact above the selection-start intensity threshold (e.g., a deep press at time  $T_4$  in FIG. 13H), a word is selected at the location of the cursor (as shown in FIG. 13H).

In some embodiments, the selected respective word is (1458) a first word (e.g., the word “enim” is the selected first word, FIG. 13H). In some embodiments, while the first word is selected, the device detects first subsequent movement of the contact (13I). In response to detecting the first subsequent movement of the contact while the first word is selected and in accordance with a determination that the touch input meets selection-movement criteria which includes a movement criterion that is met when the contact moves more than a respective threshold amount (e.g., the contact is not substantially stationary and optionally a respective time criterion that is met when an amount of time between the third subsequent change in the characteristic intensity of the contact is detected and when the first subsequent movement of the contact is detected is less than a respective delay threshold), the device cancels selection of the first word and selects a second word that is adjacent to the first word in a first direction (e.g., before or after the respective word) in accordance with the first subsequent movement of the contact, such that the selected respective word is the second word (e.g., as shown in FIG. 13I).

In some embodiments, instead of selecting a second word that is adjacent to the first word, while the respective word is selected (e.g., as shown in FIG. 13H), the device detects (1460) first subsequent movement of the contact (e.g., as shown in FIG. 13J). In response to detecting the first subsequent movement of the contact while the respective word is selected and in accordance with a determination that the touch input meets selection-expansion criteria which includes a movement criterion that is met when the contact moves more than a respective threshold amount (e.g., the contact is not substantially stationary and optionally a respective time criterion that is met when an amount of time between the third subsequent change in the characteristic intensity of the contact is detected and when the first subsequent movement of the contact is detected is less than a respective delay threshold), the device expands the selection to include a word that is adjacent to the respective word in a first direction (e.g., before or after the respective word) in accordance with the first subsequent movement of the contact (e.g., as shown in FIG. 13J).

In some embodiments, instead of selecting a second word that is adjacent to the first word or expanding the selection word by word in respect to detecting a subsequent movement of the contact, while the respective word is selected, the device detects (1462) a fourth subsequent change (e.g., a deep press at time  $T_5$ , as shown in FIG. 13K) in the characteristic intensity of the contact above a respective intensity threshold (e.g., the selection-cancellation intensity threshold). In response to detecting the fourth subsequent change in the characteristic intensity of the contact, in accordance with a determination that the touch input (e.g., the fourth subsequent change in the characteristic intensity of the contact at time  $T_5$ ) meets the selection-cancellation criteria, which includes a criterion that is met when the amount of time between when the third subsequent change in the characteristic intensity of the contact is detected and when the fourth subsequent change in the characteristic intensity of the contact is detected is greater than the delay threshold (e.g., and, optionally, that the contact is substantially stationary), the device cancels selection of the respective word (e.g., as shown in FIG. 13K).

In some embodiments, instead of canceling a selected word in response to a fourth subsequent change in the characteristic intensity of the contact above a respective intensity threshold, while the respective word is selected, the device detects (1464) a fourth subsequent change (e.g., a deep press at time  $T_5$ , FIG. 13L) in the characteristic intensity of the contact above a respective intensity threshold (e.g., the sentence-selection intensity threshold). In response to detecting the fourth subsequent change in the characteristic intensity of the contact, in accordance with a determination that the touch input (e.g., the fourth subsequent change in the characteristic intensity of the contact at time  $T_5$ ) meets sentence-selection criteria which include a movement criterion that is met when the contact moves less than a threshold amount within a threshold time period (e.g., the contact is substantially stationary) before (e.g., just before) the fourth subsequent change in intensity of the contact was detected and a time criterion that is met when an amount of time between when the third subsequent change in the characteristic intensity of the contact is detected and when the fourth subsequent change in the characteristic intensity of the contact is detected is less than a delay threshold, the device expands the selection to include the (entire) respective sentence that contains the respective word (e.g., as shown in FIG. 13L).

In some embodiments, while the respective sentence is selected, the device detects (1466) second subsequent movement of the contact (e.g., as shown in FIG. 13M). In response to detecting the second subsequent movement of the contact while the respective sentence is selected: in accordance with a determination that the touch input meets selection-expansion criteria which includes a movement criterion that is met when the contact moves more than a respective threshold amount (e.g., the contact is not substantially stationary and optionally a respective time criterion that is met when an amount of time between the fourth subsequent change in the characteristic intensity of the contact is detected and when the second subsequent movement of the contact is detected is less than a respective delay threshold), the device expands the selection to include a sentence that is adjacent to the respective sentence in a first direction (e.g., before or after the respective sentence) in accordance with the second subsequent movement of the contact (e.g., the expansion of the selection does not select one or more sentences in a respective paragraph that includes the respective sentence, that are adjacent to the

respective sentence in the respective paragraph in a second direction that is different from the first direction (e.g., as shown in FIG. 13M).

In some embodiments, instead of expanding the sentence selection in response to a subsequent movement of the contact, while the respective sentence is selected, the device detects (1468) a fifth subsequent change in the characteristic intensity of the contact above the respective intensity threshold (e.g., the selection-start intensity threshold) (e.g., as shown in FIG. 13N). In response to detecting the fifth subsequent change in the characteristic intensity of the contact, in accordance with a determination that the touch input meets the selection-cancellation criteria, which includes a criterion that is met when the amount of time between when the fourth subsequent change in the characteristic intensity of the contact is detected and when the fifth subsequent change in the characteristic intensity of the contact is detected is greater than the delay threshold (e.g., and, optionally, that the contact is substantially stationary), the device cancels selection of the respective sentence (e.g., as shown in FIG. 13N).

In some embodiments, instead of canceling the sentence selection, in response to detecting a subsequent change in the characteristic intensity of the contact, in response to detecting the fifth subsequent change in the characteristic intensity of the contact, in accordance with a determination that the touch input meets paragraph-selection criteria which include a movement criterion that is met when the contact moves less than the threshold amount within the threshold time period (e.g., is substantially stationary) before (e.g., just before) the fifth subsequent change in intensity of the contact was detected and a time criterion that is met when an amount of time between when the fourth subsequent change in the characteristic intensity of the contact is detected and when the fifth subsequent change in the characteristic intensity of the contact is detected is less than the delay threshold, the device expands (1470) the selection to include the (entire) respective paragraph that contains the respective sentence (e.g., as shown in FIG. 13O).

In some embodiments, while the respective paragraph is selected, the device detects (1472) third subsequent movement of the contact. In response to detecting the third subsequent movement of the contact while the respective paragraph is selected: in accordance with a determination that the touch input meets selection-expansion criteria which includes a movement criterion that is met when the contact moves more than a respective threshold amount, the device expands the selection to include a paragraph that is adjacent to the respective paragraph in a first direction in accordance with the third subsequent movement of the contact (e.g., as shown in FIG. 13P).

In some embodiments, the respective paragraph is selected in response to the fifth subsequent change in the characteristic intensity of the contact. While the respective paragraph is selected: the device detects (1474) a sixth subsequent change in the characteristic intensity of the contact above the respective intensity threshold; and, in response to detecting the sixth subsequent change in the characteristic intensity of the contact, in accordance with a determination that the touch input meets selection-cancellation 138-156 criteria, which includes a criterion that is met when the amount of time between when the fifth subsequent change in the characteristic intensity of the contact is detected and when the sixth subsequent change in the characteristic intensity of the contact is detected is greater than the delay threshold, the device cancels selection of the respective paragraph (e.g., as shown in FIG. 13Q).

In some embodiments, in response to detecting the sixth subsequent change in the characteristic intensity of the contact, in accordance with a determination that the touch input meets document selection criteria which include a movement criterion that is met when the contact moves less than the threshold amount within the threshold time period before the sixth subsequent change in intensity of the contact was detected and a time criterion that is met when an amount of time between when the fifth subsequent change in the characteristic intensity of the contact is detected and when the sixth subsequent change in the characteristic intensity of the contact is detected is less than the delay threshold, the device expands (1476) the selection to include the respective document that contains the respective paragraph.

It should be understood that the particular order in which the operations in FIGS. 14A-14H have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other methods described herein (e.g., methods 400, 1000, and 1100) are also applicable in an analogous manner to method 1400 described above with respect to FIGS. 14A-14H. For example, the contacts, gestures, user interface objects, intensity thresholds, and/or animations described above with reference to method 1400 optionally have one or more of the characteristics of the contacts, gestures, user interface objects, intensity thresholds, and/or animations described herein with reference to other methods described herein (e.g., methods 400, 1000, and 1100). For brevity, these details are not repeated here.

In accordance with some embodiments, FIG. 15 shows a functional block diagram of an electronic device 1500 configured in accordance with the principles of the invention as described above. The functional blocks of the device may be implemented by hardware, software, or a combination of hardware and software to carry out the principles of the invention. It is understood by persons of skill in the art that the functional blocks described in FIG. 15 may be combined or separated into sub-blocks to implement the principles of the invention as described above. Therefore, the description herein may support any possible combination or separation or further definition of the functional blocks described herein.

In some embodiments, the electronic device 1500 includes a display unit 1502 configured to concurrently display an onscreen keyboard and a content presentation region on the display unit 1502, wherein the content presentation region displays text input received from the onscreen keyboard; a touch-sensitive surface unit 1504 configured to receive user touch inputs; one or more sensor units 1506 to detect intensity of contacts with the touch-sensitive surface unit 1504; and a processing unit 1508 coupled to the display unit 1502, the touch-sensitive surface unit 1504, and the one or more sensor units 1506. In some embodiments, the processing unit 1508 includes a detecting unit 1510, a selecting unit 1512, a moving unit 1514, a determining unit 1516, and a changing appearance unit 1518.

In some embodiments, the processing unit 1208 is configured to: in accordance with the determination that the touch input satisfies the one or more criteria for entering the text selection mode: visually obscure keys on the onscreen keyboard (e.g., with the obscuring unit 1218).

The processing unit **1508** is configured to: detect (e.g., with detecting unit **1510**) a touch input on the onscreen keyboard displayed on the touch-sensitive display. In some embodiments, detect (e.g., with detecting unit **1510**) the touch input includes detect (e.g., with detecting unit **1510**) movement of a contact and liftoff of the contact. The processing unit **1508** is also configured to: in response to detecting the touch input on the onscreen keyboard displayed on the touch-sensitive display, in accordance with a determination (e.g., with determining unit **1516**) that the touch input satisfies text-selection criteria, the text-selection criteria include a criterion that is met when a characteristic intensity of the contact increases above a text-selection intensity threshold, perform a text selection operation (e.g., with selecting unit **1512**) based on the movement of the contact. Conversely, in accordance with a determination (e.g., with determining unit **1516**) that the touch input satisfies text-entry criteria, the text-entry criteria include a criterion that is met when the characteristic intensity of the contact does not increase above the text-selection intensity threshold, the processing unit **1508** is configured to enter text into the content presentation region based on the touch input.

In some embodiments, the text-entry criteria include a criterion that is met when the liftoff of the contact is detected while the contact is at a location of a character key of the onscreen keyboard.

In some embodiments, the text-entry criteria include a criterion that is met when the contact does not move outside of the onscreen keyboard before liftoff of the contact is detected.

In some embodiments, enter the text into the content region includes enter a character that corresponds to character key at a location at which touchdown of the contact was detected on the onscreen keyboard.

In some embodiments, enter the text into the content region includes enter a character that corresponds to character key at a location at which liftoff of the contact was detected on the onscreen keyboard.

In some embodiments, the text-selection criteria include a criterion that is met when the contact does not move more than a threshold distance before detecting an increase in the characteristic intensity of the contact above the text-selection intensity threshold.

In some embodiments, the text-selection operation includes one of: moving a cursor within the content region or selecting text within the content region.

In some embodiments, the processing unit **1508** is configured to, in response to detecting that the text-selection criteria have been met, generate a tactile (e.g., with tactile output generator(s) **167**, FIG. 2A or tactile output generator (s) **257**, FIG. 2B) output that is indicative of an entry into a text selection mode of operation.

In some embodiments, the processing unit **1508** is configured to, in response to detecting that the text-selection criteria have been met, change an appearance (e.g., with changing appearance unit **1518**) of the onscreen keyboard to indicate that the device is operating in a text selection mode of operation. In some embodiments, change the appearance (e.g., with changing appearance unit **1518**) of the onscreen keyboard includes obscure an appearance (e.g., with changing appearance unit **1518**) of characters on keys of the onscreen keyboard.

In some embodiments, the processing unit **1508** is configured to end the text selection mode of operation and, in conjunction with the end of the text selection mode of operation, reverse the change in appearance (e.g., with

changing appearance unit **1518**) of the onscreen keyboard to reveal the characters on the keys of the onscreen keyboard.

In some embodiments, the processing unit **1508** is configured to, when the touch input satisfies the text-selection criteria, detect (e.g., with detecting unit **1510**) movement of the contact after the touch input has satisfied the text-selection criteria and move (e.g., with moving unit **1514**) a cursor in the content region in accordance with the movement of the contact detected after the touch input has satisfied the text-selection criteria.

In some embodiments, the processing unit **1508** is configured to, when the touch input satisfies the text-selection criteria, detect (e.g., with detecting unit **1510**) a first subsequent change in the characteristic intensity of the contact followed by additional movement of the contact on the touch-sensitive display; and, in response to detecting the first subsequent change in the characteristic intensity of the contact, in accordance with a determination (e.g., with determining unit **1516**) that the touch input satisfies selection-start criteria, the selection-start criteria include a criterion that is met when the characteristic intensity of the contact increases above a selection-start intensity threshold, the processing unit **1508** is configured to start to select (e.g., with selecting unit **1512**) content in the content region at a location of a cursor in accordance with the additional movement of the contact. Conversely, in accordance with a determination (e.g., with determining unit **1516**) that the touch input does not satisfy the selection-start criteria, the processing unit **1508** is configured to move (e.g., with moving unit **1514**) the cursor in accordance with the additional movement of the contact without starting to select content in the content region.

In some embodiments, the processing unit **1508** is configured to: when the touch input satisfies selection-start criteria, after starting to select content in the content region, detect (e.g., with detecting unit **1510**) liftoff of the contact from the touch-sensitive display and confirm the selection (e.g., with selecting unit **1512**) in response to detecting the liftoff of the contact.

In some embodiments, the processing unit **1508** is configured to: when the touch input satisfies selection-start criteria, after starting to select content in the content region, and while continuing to detect (e.g., with detecting unit **1510**) the contact on the touch-sensitive display, detect (e.g., with detecting unit **1510**) a second subsequent change in intensity of the contact. In response to detecting the second subsequent change in the characteristic intensity of the contact, in accordance with a determination (e.g., with determining unit **1516**) that the second subsequent change in the characteristic intensity of the contact satisfies selection-cancellation criteria, the selection-cancellation criteria include a criterion that is met when the characteristic intensity of the contact increases above a selection-cancellation intensity threshold, the processing unit **1508** is configured to cancel the selection (e.g., with selecting unit **1512**). Conversely, in accordance with a determination (e.g., with determining unit **1516**) that the second subsequent change in the characteristic intensity of the contact does not satisfy the selection-cancellation criteria, the processing unit **1508** is configured to maintain the selection (e.g., with selecting unit **1512**).

In some embodiments, the selection-cancellation criterion include a criterion that is met when the contact moves no more than a threshold distance within a threshold amount of time before the characteristic intensity of the contact increases above the selection-cancellation intensity threshold.

111

In some embodiments, the processing unit **1508** is configured to, in response to detecting that the selection-cancellation criteria have been met, generate a tactile (e.g., with tactile output generator(s) **167**, FIG. 2A or tactile output generator(s) **257**, FIG. 2B) output that is indicative of an exit from the text selection mode of operation.

In some embodiments, the processing unit **1508** is configured to: after canceling the selection, and while continuing to detect (e.g., with detecting unit **1510**) the contact on the touch-sensitive display, detect (e.g., with detecting unit **1510**) a third subsequent change in the characteristic intensity of the contact. In response to detecting the third subsequent change in the characteristic intensity of the contact, in accordance with a determination (e.g., with determining unit **1516**) that the touch input satisfies the selection-start criteria, the processing unit **1508** is configured to start to select (e.g., with selecting unit **1512**) content in the content region at a location of the cursor. Conversely, in accordance with a determination (e.g., with determining unit **1516**) that the touch input does not satisfy the selection-start criteria, the processing unit **1508** is configured to forgo starting to select content (e.g., with selecting unit **1512**) in the content region.

In some embodiments, start to select (e.g., with selecting unit **1512**) content in response to detecting the third subsequent change in the characteristic intensity of the contact includes select (e.g., with selecting unit **1512**) a respective word at the location of the cursor.

In some embodiments, the selected respective word is a first word, and the processing unit **1508** is configured to, while the first word is selected, detect (e.g., with detecting unit **1510**) first subsequent movement of the contact. In response to detecting the first subsequent movement of the contact while the first word is selected, in accordance with a determination (e.g., with determining unit **1516**) that the touch input meets selection-movement criteria which includes a movement criterion that is met when the contact move (e.g., with moving unit **1514**)s more than a respective threshold amount, the processing unit **1508** is configured to cancel selection (e.g., with selecting unit **1512**) of the first word, and select (e.g., with selecting unit **1512**) a second word that is adjacent to the first word in a first direction in accordance with the first subsequent movement of the contact, such that the selected respective word is the second word.

In some embodiments, the processing unit **1508** is configured to, while the respective word is selected, detect (e.g., with detecting unit **1510**) first subsequent movement of the contact. In response to detecting the first subsequent movement of the contact while the respective word is selected, in accordance with a determination (e.g., with determining unit **1516**) that the touch input meets selection-expansion criteria which includes a movement criterion that is met when the contact moves more than a respective threshold amount, the processing unit **1508** is configured to expand the selection (e.g., with selecting unit **1512**) to include a word that is adjacent to the respective word in a first direction in accordance with the first subsequent movement of the contact.

In some embodiments, the processing unit **1508** is configured to, while the respective word is selected, detect (e.g., with detecting unit **1510**) a fourth subsequent change in the characteristic intensity of the contact above a respective intensity threshold. In response to detecting the fourth subsequent change in the characteristic intensity of the contact, in accordance with a determination (e.g., with determining unit **1516**) that the touch input meets the selection-cancellation criteria, which includes a criterion that is met when the amount of time between when the third

112

subsequent change in the characteristic intensity of the contact is detected and when the fourth subsequent change in the characteristic intensity of the contact is detected is greater than the delay threshold, the processing unit **1508** is configured to cancel selection (e.g., with selecting unit **1512**) of the respective word.

In some embodiments, the processing unit **1508** is configured to, while the respective word is selected, detect (e.g., with detecting unit **1510**) a fourth subsequent change in the characteristic intensity of the contact above a respective intensity threshold. In response to detecting the fourth subsequent change in the characteristic intensity of the contact, in accordance with a determination (e.g., with determining unit **1516**) that the touch input meets sentence-selection criteria which include a movement criterion that is met when the contact move (e.g., with moving unit **1514**)s less than a threshold amount within a threshold time period before the fourth subsequent change in intensity of the contact was detected and a time criterion that is met when an amount of time between when the third subsequent change in the characteristic intensity of the contact is detected and when the fourth subsequent change in the characteristic intensity of the contact is detected is less than a delay threshold, the processing unit **1508** is configured to expand the selection (e.g., with selecting unit **1512**) to include the respective sentence that contains the respective word.

In some embodiments, the processing unit **1508** is configured to, while the respective sentence is selected, detect (e.g., with detecting unit **1510**) second subsequent movement of the contact. In response to detecting the second subsequent movement of the contact while the respective sentence is selected, in accordance with a determination (e.g., with determining unit **1516**) that the touch input meets selection-expansion criteria which includes a movement criterion that is met when the contact move (e.g., with moving unit **1514**)s more than a respective threshold amount, the processing unit **1508** is configured to expand the selection (e.g., with selecting unit **1512**) to include a sentence that is adjacent to the respective sentence in a first direction in accordance with the second subsequent movement of the contact.

In some embodiments, the respective sentence is selected in response to the fourth subsequent change in the characteristic intensity of the contact and the processing unit **1508** is configured to, while the respective sentence is selected: detect (e.g., with detecting unit **1510**) a fifth subsequent change in the characteristic intensity of the contact above the respective intensity threshold. In response to detecting the fifth subsequent change in the characteristic intensity of the contact, in accordance with a determination (e.g., with determining unit **1516**) that the touch input meets the selection-cancellation criteria, which includes a criterion that is met when the amount of time between when the fourth subsequent change in the characteristic intensity of the contact is detected and when the fifth subsequent change in the characteristic intensity of the contact is detected is greater than the delay threshold, the processing unit **1508** is configured to cancel selection (e.g., with selecting unit **1512**) of the respective sentence.

In some embodiments, the processing unit **1508** is configured to, in response to detecting the fifth subsequent change in the characteristic intensity of the contact, in accordance with a determination (e.g., with determining unit **1516**) that the touch input meets paragraph-selection criteria which include a movement criterion that is met when the contact move (e.g., with moving unit **1514**)s less than the threshold amount within the threshold time period before the

fifth subsequent change in intensity of the contact was detected and a time criterion that is met when an amount of time between when the fourth subsequent change in the characteristic intensity of the contact is detected and when the fifth subsequent change in the characteristic intensity of the contact is detected is less than the delay threshold, the processing unit **1508** is configured to expand the selection (e.g., with selecting unit **1512**) to include the respective paragraph that contains the respective sentence.

In some embodiments, the processing unit **1508** is configured to, while the respective paragraph is selected, detecting third subsequent movement of the contact. In response to detecting the third subsequent movement of the contact while the respective paragraph is selected, in accordance with a determination (e.g., with determining unit **1516**) that the touch input meets selection-expansion criteria which includes a movement criterion that is met when the contact move (e.g., with moving unit **1514**)s more than a respective threshold amount, expand the selection (e.g., with selecting unit **1512**) to include a paragraph that is adjacent to the respective paragraph in a first direction in accordance with the third subsequent movement of the contact.

In some embodiments, the respective paragraph is selected in response to the fifth subsequent change in the characteristic intensity of the contact and the processing unit **1508** is configured to, while the respective paragraph is selected, detect (e.g., with detecting unit **1510**) a sixth subsequent change in the characteristic intensity of the contact above the respective intensity threshold. In response to detecting the sixth subsequent change in the characteristic intensity of the contact, in accordance with a determination (e.g., with determining unit **1516**) that the touch input meets selection-cancellation criteria, which includes a criterion that is met when the amount of time between when the fifth subsequent change in the characteristic intensity of the contact is detected and when the sixth subsequent change in the characteristic intensity of the contact is detected is greater than the delay threshold, the processing unit **1508** is configured to cancel selection (e.g., with selecting unit **1512**) of the respective paragraph.

In some embodiments, the processing unit **1508** is configured to, in response to detecting the sixth subsequent change in the characteristic intensity of the contact, in accordance with a determination (e.g., with determining unit **1516**) that the touch input meets document selection criteria which include a movement criterion that is met when the contact move (e.g., with moving unit **1514**)s less than the threshold amount within the threshold time period before the sixth subsequent change in intensity of the contact was detected and a time criterion that is met when an amount of time between when the fifth subsequent change in the characteristic intensity of the contact is detected and when the sixth subsequent change in the characteristic intensity of the contact is detected is less than the delay threshold, the processing unit **1508** is configured to expand the selection (e.g., with selecting unit **1512**) to include the respective document that contains the respective paragraph.

The foregoing description, for purpose of explanation, has been described with reference to specific embodiments. However, the illustrative discussions above are not intended to be exhaustive or to limit the invention to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings. The embodiments were chosen and described in order to best explain the principles of the invention and its practical applications, to thereby enable others skilled in the art to best use the invention and various

described embodiments with various modifications as are suited to the particular use contemplated.

What is claimed is:

1. A method of selection manipulation, comprising:
  - at a portable multifunction device including one or more processors, memory, and a touch screen display:
    - displaying content of an electronic document on the display;
    - detecting a selection input corresponding to selection of a respective portion of the content;
    - in response to detecting the selection input, changing an appearance of the respective portion of the content to indicate that the respective portion of the content has been selected, wherein the respective portion of the content that has been selected comprises selected content;
    - while displaying the selected content with the changed appearance, detecting a single touch input on the touch screen display at a location over the selected content; and
    - in response to detecting the single touch input at the location, in accordance with a determination that the single touch input remains, during a first portion of the single touch input, at the location for a predetermined amount of time, followed, during a second portion of the single touch input, by a continuous touch gesture away from the location, moving a representation of the selected content to a different location in a direction of the continuous touch gesture, wherein the representation of the selected content is an additional representation of the selected content, and moving the additional representation of the selected content includes moving the additional representation of the selected content offset from the selected content in a direction of the continuous touch gesture to indicate a position to where the selected content will be moved when the continuous touch gesture terminates.
  2. The method of claim 1, wherein displaying the selected content with the changed appearance includes concurrently displaying a start-point object and an end-point object at respective ends of the selected content.
  3. The method of claim 2, wherein the additional representation of the selected content includes an additional start-point object and an additional end-point object different from the start-point object and the end-point object of the selected content.
  4. The method of claim 1, wherein the additional representation of the selected content has a different appearance from the selected content with the changed appearance.
  5. The method of claim 1, further including, in response to detecting the selection input, concurrently displaying the selected content with the changed appearance and a set of options related to the selected content, wherein the set of options related to the selected content includes a first affordance for cutting the selected content and a second affordance for copying the selected content.
  6. The method of claim 5, wherein the set of options related to the selected content includes a third affordance for pasting a previously cut or copied selection of content.
  7. The method of claim 5, wherein the set of options related to the selected content includes an affordance for displaying additional command options, or an affordance for presenting a definition of a word in the selected content.
  8. The method of claim 1, wherein determining if the single touch input remains at the location for the predeter-

115

mined amount of time includes determining that the single touch input moves no more than a threshold distance within a threshold amount of time.

9. An electronic device, comprising:

a touch screen display;  
one or more processors;  
memory; and

one or more programs, wherein the one or more programs are stored in the memory and configured to be executed by the one or more processors, the one or more programs including instructions for:

displaying content of an electronic document on the display;

detecting a selection input corresponding to selection of a respective portion of the content;

in response to detecting the selection input, changing an appearance of the respective portion of the content to indicate that the respective portion of the content has been selected, wherein the respective portion of the content that has been selected comprises selected content;

while displaying the selected content with the changed appearance, detecting a single touch input on the touch screen display at a location over the selected content; and

in response to detecting the single touch input at the location, in accordance with a determination that the single touch input remains, during a first portion of the single touch input, at the location for a predetermined amount of time, followed, during a second portion of the single touch input, by a continuous touch gesture away from the location, moving a representation of the selected content to a different location in a direction of the continuous touch gesture, wherein the representation of the selected content is an additional representation of the selected content, and moving the additional representation of the selected content includes moving the additional representation of the selected content offset from the selected content in a direction of the continuous touch gesture to indicate a position to where the selected content will be moved when the continuous touch gesture terminates.

10. The electronic device of claim 9, wherein displaying the selected content with the changed appearance includes concurrently displaying a start-point object and an end-point object at respective ends of the selected content.

11. The electronic device of claim 10, wherein the additional representation of the selected content includes an additional start-point object and an additional end-point object different from the start-point object and the end-point object of the selected content.

12. The electronic device of claim 9, wherein the additional representation of the selected content has a different appearance from the selected content with the changed appearance.

13. The electronic device of claim 9, wherein the one or more programs include instructions for, in response to detecting the selection input, concurrently displaying the selected content with the changed appearance and a set of options related to the selected content, wherein the set of options related to the selected content includes a first affordance for cutting the selected content and a second affordance for copying the selected content.

116

14. The electronic device of claim 13, wherein the set of options related to the selected content includes a third affordance for pasting a previously cut or copied selection of content.

15. The electronic device of claim 13, wherein the set of options related to the selected content includes an affordance for displaying additional command options, or an affordance for presenting a definition of a word in the selected content.

16. The electronic device of claim 9, wherein determining if the single touch input remains at the location for the predetermined amount of time includes determining that the single touch input moves no more than a threshold distance within a threshold amount of time.

17. A non-transitory computer readable storage medium storing one or more programs, the one or more programs comprising instructions, which when executed by an electronic device with a touch screen display, cause the electronic device to:

display content of an electronic document on the touch screen display;

detect a selection input corresponding to selection of a respective portion of the content;

in response to detecting the selection input, change an appearance of the respective portion of the content to indicate that the respective portion of the content has been selected, wherein the respective portion of the content that has been selected comprises selected content;

while displaying the selected content with the changed appearance, detect a single touch input on the touch screen display at a location over the selected content; and

in response to detecting the single touch input at the location, in accordance with a determination that the single touch input remains, during a first portion of the single touch input, at the location for a predetermined amount of time, followed, during a second portion of the single touch input, by a continuous touch gesture away from the location, move a representation of the selected content to a different location in a direction of the continuous touch gesture, wherein the representation of the selected content is an additional representation of the selected content, and moving the additional representation of the selected content includes moving the additional representation of the selected content offset from the selected content in a direction of the continuous touch gesture to indicate a position to where the selected content will be moved when the continuous touch gesture terminates.

18. The non-transitory computer readable storage medium of claim 17, wherein displaying the selected content with the changed appearance includes concurrently displaying a start-point object and an end-point object at respective ends of the selected content.

19. The non-transitory computer readable storage medium of claim 18, wherein the additional representation of the selected content includes an additional start-point object and an additional end-point object different from the start-point object and the end-point object of the selected content.

20. The non-transitory computer readable storage medium of claim 17, wherein the additional representation of the selected content has a different appearance from the selected content with the changed appearance.

21. The non-transitory computer readable storage medium of claim 17, wherein the one or more programs include instructions, which when executed by the electronic device, cause the electronic device to respond to detecting the

selection input by concurrently displaying the selected content with the changed appearance and a set of options related to the selected content, wherein the set of options related to the selected content includes a first affordance for cutting the selected content and a second affordance for copying the selected content. 5

22. The non-transitory computer readable storage medium of claim 21, wherein the set of options related to the selected content includes a third affordance for pasting a previously cut or copied selection of content. 10

23. The non-transitory computer readable storage medium of claim 21, wherein the set of options related to the selected content includes an affordance for displaying additional command options, or an affordance for presenting a definition of a word in the selected content. 15

24. The non-transitory computer readable storage medium of claim 17, wherein determining if the single touch input remains at the location for the predetermined amount of time includes determining that the single touch input moves no more than a threshold distance within a threshold amount of time. 20

\* \* \* \* \*