



(86) Date de dépôt PCT/PCT Filing Date: 2006/08/30
(87) Date publication PCT/PCT Publication Date: 2007/11/22
(45) Date de délivrance/Issue Date: 2012/04/24
(85) Entrée phase nationale/National Entry: 2008/11/06
(86) N° demande PCT/PCT Application No.: IB 2006/002375
(87) N° publication PCT/PCT Publication No.: 2007/132288
(30) Priorité/Priority: 2006/05/12 (FR06/04221)

(51) Cl.Int./Int.Cl. *A61M 25/02* (2006.01)
(72) Inventeurs/Inventors:
TAMBOURGI, CHRISTINA, FR;
BERNARD, PASCAL, BE;
GOBY, JEAN MICHEL, FR
(73) Propriétaire/Owner:
FRESENIUS MEDICAL CARE DEUTSCHLAND GMBH,
DE
(74) Agent: SHAPIRO COHEN

(54) Titre : BANDAGE A USAGE MEDICAL
(54) Title: MEDICAL-USE BANDAGE

(57) **Abrégé/Abstract:**

The invention relates to a medical-use bandage (1) designed to immobilize a tube implanted in a body, the implanted tube defining an exit site from the body and a part of the tube projecting from the body; the bandage comprising: - a base support (2) having a lower face (21) designed to be applied to the skin and an upper face (22) , - first fixing means (3) for fixing the exit site, comprising on the lower face (21) of the base support (2) an adhesive fixing part (32) designed to be stuck at least partly around the exit site to the skin and to a proximal portion of the projecting part of the tube; and - second fixing means (4) for engaging the distal portion of the projecting part of the tube in a defined shape and in a sliding manner, the second fixing means (4) consisting at least partly of a part (43) of the upper face (22) of the support (2) .

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
22 November 2007 (22.11.2007)

PCT

(10) International Publication Number
WO 2007/132288 A1

(51) International Patent Classification:
A61M 25/02 (2006.01)

(74) Agents: VILLANOVA, Massimo et al.; P.o. Box 98,
I-41037 Mirandola (IT).

(21) International Application Number:
PCT/IB2006/002375

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(22) International Filing Date: 30 August 2006 (30.08.2006)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
06/04221 12 May 2006 (12.05.2006) FR

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): **GAMBRO LUNDIA AB** [SE/SE]; No. 16, Magistratsvagen, S-22010 Lund (SE).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **TAMBOURGI, Christina** [FR/FR]; No. 206, Grande Rue, FR-OULLINS 69600 (FR). **BERNARD, Pascal** [FR/FR]; No. 78, Chemin Du Petit Bois, FR-69130 Ecully (FR). **GOBY, Jean Michel** [FR/FR]; No. 5, Impasse Du Sans Souci, FR-21800 Sennecey Les Dijon (FR).

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: MEDICAL-USE BANDAGE.

(57) Abstract: The invention relates to a medical-use bandage (1) designed to immobilize a tube implanted in a body, the implanted tube defining an exit site from the body and a part of the tube projecting from the body; the bandage comprising: - a base support (2) having a lower face (21) designed to be applied to the skin and an upper face (22), - first fixing means (3) for fixing the exit site, comprising on the lower face (21) of the base support (2) an adhesive fixing part (32) designed to be stuck at least partly around the exit site to the skin and to a proximal portion of the projecting part of the tube; and - second fixing means (4) for engaging the distal portion of the projecting part of the tube in a defined shape and in a sliding manner, the second fixing means (4) consisting at least partly of a part (43) of the upper face (22) of the support (2).



WO 2007/132288 A1

Medical-Use Bandage

Technical field of the invention

The present invention relates to a medical-use bandage for a tube implanted in a patient, and the process for applying this bandage to the skin of a patient. The
5 tube is more particularly the tube of a catheter for dialysis, notably peritoneal dialysis.

Dialysis is a way of cleaning the blood when a person's kidneys are no longer able to function. Dialysis takes the place of the kidneys by removing the body's waste products, notably excess water or salt. There are two basic methods of
10 dialysis: haemodialysis and peritoneal dialysis.

In haemodialysis the blood is pumped out of the body to a machine which acts as an artificial kidney and contains a special membrane for filtering the blood and removing waste products. The cleaned blood is then returned via tubes connecting the patient to the machine. The haemodialysis process takes
15 approximately 4 hours and must be carried out three times a week.

In peritoneal dialysis the waste products are filtered out of the blood through the wall of the patient's abdominal cavity. The wall is called the peritoneum and acts as a natural filtration membrane. The waste products are removed by means of a sterile cleaning fluid which is introduced and removed from the abdomen in
20 cycles. A flexible plastic tube known as a catheter is permanently installed surgically in the lower part of the patient's abdomen. One part of this catheter is inserted inside the patient and one part projects outside the patient. The junction between the two parts on the surface of the skin is known as the "exit site". The patient therefore has part of the catheter permanently projecting from his or her
25 body.

During the treatment, the distal end (meaning the end furthest from the patient) of the catheter is connected by an adapter to another tube, the patient extender. A connector at the end of the extender allows communication with the cleaning fluid. The cleaning fluid thus enters the abdomen through the extender and then
30 through the catheter.

Waste products from the blood pass through the peritoneal membrane into the cleaning fluid. Then, when the filtration process is over, the fluid leaves the body through the catheter.

5 More particularly, peritoneal dialysis employs two different methods in terms of duration and the number of cycles: Automatic Peritoneal Dialysis (APD), done by machine, and Continuous Ambulatory Peritoneal Dialysis (CAPD), which uses gravity.

10 Continuous Ambulatory Peritoneal Dialysis does not require the use of a dialysis machine. Patients perform the treatment themselves by introducing into their abdomen approximately 2 litres of cleaning fluid into their peritoneal cavity by connecting up via the extender a bag of cleaning fluid which is placed above shoulder level and drained in. Then, when the fluid has been introduced into the patient's peritoneal cavity, an empty bag is connected via the extender at a level below the abdomen. In this way the solution containing the waste products is drained off from the peritoneal cavity into the empty bag. This process is usually performed 4 or 5 times every day. Each of these
15 cycles takes around 30 minutes.

In automatic dialysis, these cycles are programmed by a machine at least several times a night.

One drawback with peritoneal dialysis is the permanent installation of the catheter and extender near the patient's belt.

20 In the first place, the projecting part of this extender (which can measure between 20 and 30 cm) must be protected and kept in position between cycles to avoid damage or movement of the catheter and its extender. In the second place, during the cycle, the projecting part of the tube may move undesirably as the fluid is passing through it. This can be uncomfortable for the patient and can influence the rate of flow of the fluid, or
25 result in the implanted catheter being moved relative to the body.

In addition, the exit site of the catheter must be carefully monitored because it can be subject to unwanted infections (such as peritonitis).

Prior art:

As regards the fixing and protecting of the catheter and extender during non-treatment time, a number of dressings or bandages designed to secure the projecting part of the tube are known. The best-known method is a bandage which is made by the patient or
5 nurse and consists of gauze placed on the exit site and then secured with several strips of adhesive tape.

More sophisticated belts having a bag for receiving the unused tube have been developed. Patent US 6,436,074 discloses a belt for securing the catheter and protecting the exit site during non-treatment time. The belt is doubled over and closed
10 to form a bag to receive the tube. The exit site is protected by sterile gauze in contact with the exit site and applied by a block of foam rubber all the way around it. The device is held in place during non-treatment time by its belt shape which is adjusted to fit the patient's pelvis.

As regards the fixing and protection of the catheter during treatment, several bandages
15 have been produced, mostly bandages for applying to a tube connecting a vascular access of a patient.

One bandage for use during treatment is known from Patent US 5,344,415. This bandage comprises two distinct separate parts: the first part is a dressing with an absorbent material applied to the exit site and surrounded by an adhesive dressing.
20 The second part is a simple, entirely adhesive band. The first part is applied first, followed by the second part which will be applied along the edge of the first part covering the tube. In one edge of the second part is an indentation for receiving the tube. The second part is stuck to the skin in such a way as to cover an edge of the first part and immobilize the tube between the two edges inside the indentation.

25 A second bandage for use during treatment is known from Patent EP 0 569 565. This is a square adhesive bandage with an area of gauze in its centre designed to be placed over the exit site. The bandage is slit through its thickness from the centre of the gauze to the perimeter of the bandage. The slit makes it possible to position the centre of the bandage over the exit site of the patient and allows the bandage to be
30 stuck all the way around the exit site. Where the vascular access device is a cannula

assembly comprising a voluminous assembly body comprising two branches, one for the vascular access tube and the other for the administration of medication, the assembly device is itself attached, in addition to the square bandage, by an entirely adhesive band attached to the bandage enabling the vascular access tube to be held
5 in place by adhesive.

The third intravenous bandage for use during treatment is known from Patent US 5,707,348. It is composed of a first part applied all the way around the exit site by adhesive fixing, and a second part which, in the position of complete usage, will be fixed adhesively to the skin to hold the tube in a chosen direction.

10 Each proposed type uses adhesive fixing for the first part around the vascular access site and adhesive fixing for the second part in such a way that the two parts keep the tube in position adhesively for the whole time the bandage is being used in a chosen form.

Consequently, in the three described cases of dressings used during treatment, each
15 bandage has a single-use adhesive fixing for the tube. In other words, each bandage is applied adhesively to keep the tube immobile throughout the period of application of the bandage. The tube can only be moved when the bandage is removed after the patient has been treated.

The object of the invention is to provide a bandage that will allow the projecting portion
20 of a tube implanted in a patient to be immobilized in a first position during a treatment involving passage of fluid, and immobilized in a second position during non-treatment when there is no passage of fluid.

One object of the invention is to provide a bandage capable of remaining in place on the skin for several days.

25 Another object of the invention is to provide permanent protection of the patient's exit site.

A further object is to provide a bandage that will allow easy monitoring of the condition of the exit site for the whole of the time during which the bandage is in position.

Additional objects are to obtain a strong bandage that is impermeable to water and bacteria, is easy and inexpensive to produce, is easy for the user to handle when applying it to his skin, and is easy for the user to handle when detaching it.

The dressing can be used for the tube of a catheter implanted in the peritoneum of a patient undergoing peritoneal dialysis, but can be used for any catheter or implanted medical tube that must be secured in two different positions.

Summary of the invention:


- 10 According to the present invention, there is provided a medical-use bandage (1) having a lower face designed to be turned to the skin, and on the opposite side an upper face; this bandage being designed to immobilize a tube (100) implanted in a body, the implanted tube (100) defining an exit site (101) from the body and a part (102) of the tube projecting from the body; the bandage (1) comprising:
- a base support (2) having a lower face (21) designed to be applied to the skin and an upper face (22),
 - first fixing means (3) for fixing the exit site (101), comprising on the lower face (21) of the base support (2) an adhesive fixing part (32) designed to be stuck at least
20 partly around the exit site (101) to the skin and to a proximal portion (102') of the projecting part (102) of the tube; and
 - second fixing means (4) for engaging the distal portion (102'') of the projecting part (102) of the tube in a defined shape and in a sliding manner, the second fixing means (4) consisting at least partly of a part (43) of the upper face (22) of the support (2), wherein the second fixing means (4) comprise:
 - a band (41) having at least part of its non-adhesive lower face designed to be turned to the skin, this band comprising:

- two opposite sides (41', 41'') connected to the base support (2), and
 - two auxiliary opposite sides (411', 411'') defining through the upper face of the bandage (1) two openings for allowing the distal projecting portion (102'') of the tube to pass through the openings; and
- an adhesive attachment area (42) that is situated at least partly around the band (41), is defined on the lower face (21) of the support, and is designed to be stuck to the skin.

The invention also relates to a process for applying the bandage according to the invention comprising the following steps:

10

- applying and fixing adhesively at least in part the first fixing means 3 to the skin and the proximal part of the projecting portion of the tube,
- applying and fixing adhesively at least in part the second fixing means 4 to the skin, and



5a

- forming a loop with the distal portion of the projecting part of the tube and engaging the projecting part of the tube in a sliding manner in the second fixing means and in contact with at least the part 43 of the upper surface 22 of the support 2.

5

Brief description of the drawings:

Other advantages and features of the invention will become apparent on reading the description which follows.

The reader should refer to the accompanying drawings, in which:

10 Figure 1 shows the lower face (the face designed to be turned to the skin) of the bandage, ready to be applied to the patient,

Figure 2 shows the upper face of the bandage,

Figure 3 shows the lower face (the face to be turned to the skin) of the bandage, equipped with detachable films for bandage storage,

15 Figure 4 shows the upper face of the bandage, once the bandage has been applied to the skin, with the projecting portion of the tube immobilized for treatment purposes, and

Figure 5 is an exploded view of the components of the bandage in storage.

Detailed description of the embodiments of the invention:

20 The medical-use bandage 1 comprises a lower face designed to be turned to the skin, shown in Figure 2, and an upper face on the opposite side, shown in Figure 1.

As illustrated in Figure 4, the bandage is designed to immobilize a tube 100 implanted in a body, the implanted tube 100 defining an exit site 101 from the body and a part 102 of the tube projecting from the body. The projecting part 102 of the tube is
25 composed of a proximal portion 102', that is to say the portion of the tube which is nearest the body and which will be held in place by the first fixing means of the

bandage, and a distal portion, that is to say the portion of the tube furthest from the body, a part of which will be held in place during non-treatment by the second fixing means of the bandage in a predetermined shape, preferably a loop.

5 The bandage 1 comprises a base support 2 having a lower face 21 designed to be applied to the skin. This support may be for example a sheet of an impermeable material, the face applied to the skin consisting of a hypoallergenic material. The material may have good breatheability. All this allows the patient to tolerate the same bandage for several days. The bandage may be coated with a quantity of acrylic adhesive recognized for its high cutaneous tolerance. The material may be made
10 impermeable to bacteria. This material may comprise a natural material such as cotton, woven or otherwise, applied to the lower face of an impermeable sheet, and/or may comprise a polyurethane material. The material may be elastic or rigid. The bandage will be white or flesh-coloured in particular.

15 The bandage 1 essentially comprises two fixing means for fixing the tube of the catheter at two locations.

The first fixing means 3 for fixing the exit site 101 have on the lower face 21 of the base support 2 an adhesive fixing part 32 designed to be stuck at least partly around the exit site 101 to the skin and to a proximal portion 102' of the projecting part 102 of the tube. The adhesive fixing part 32 (the unhatched area of the first means 3 in Figure
20 1) may partly or completely surround the exit site, may be in the shape of a ring on the base support, and may also be made adhesive as far as the edge of the base support. This part may be essentially square as shown in Figure 1 or rectangular or indeed round.

25 These first fixing means therefore make it possible to fix the proximal part of the tube of the catheter adhesively and permanently. This means that the proximal part of the tube is fixed adhesively and permanently throughout the period of usage and application of the bandage on the patient (some 2 to 3 days).

The bandage 1 has second fixing means 4 for engaging the distal portion 102'' of the projecting part 102 of the tube in a defined shape and in particular in a sliding manner.

30 More particularly, the second fixing means 4 may comprise:

- a band 41 having at least part of its nonadhesive lower face (the nonadhesive area, shown hatched) designed to be turned to the skin. This band may comprise:

- two opposite sides (41', 41'') connected to the base support 2, and
- two auxiliary opposite sides (411', 411'') defining through the upper face of the bandage 1 two openings for allowing the distal projecting portion 102'' of the tube to pass through the openings. The tube can therefore pass between the lower face of the band and the base support, or between the lower face of the band and the skin.

This band is an illustrative embodiment of means allowing the sliding passage of the tube which is to be fixed in position. The band will have all or part of its lower face nonadhesive. The band may be rectangular or square or be of some other shape.

The second fixing means also comprise an adhesive attachment area 42 (the unhatched area) that is situated at least partly around the band 41, is defined on the lower face 21 of the support, and is designed to be stuck to the skin. This attachment area 42 allows the band to be fixed permanently to the skin. The adhesive attachment may surround the band completely or partially.

These second fixing means therefore make it possible to fix nonadhesively and movably, for example in a sliding manner, the distal part of the looped catheter tube. For the entire period of use and application of the bandage on the patient (some 2 to 3 days), the user can thus easily alternate the two positions of the distal part of the tube which correspond to the peritoneal dialysis treatments which he or she has to perform 4 to 5 times every day.

Thus, the tube will be fixed to the second fixing means to form a loop during non-treatment time, and will be withdrawn from the second fixing means during treatment.

If the dressing is left stuck in position for three days and the patient undergoes 5 treatments of peritoneal dialysis per day, this bandage easily allows the tube to be passed underneath the band $3 \times 5 = 15$ times to give it the desired loop position during each of the 15 dialysis treatments. Although the distal part of the tube can be moved

(typically by sliding it) because of the second fixing means, the proximal part of the tube will remain adhesively fixed in position by the first fixing means.

Any other embodiment of the second fixing means that may be devised by those skilled in the art may be produced. For example, the fixing band of the second means may be
5 attached by one or both of its sides by means of a fixed or removable attachment to the support, e.g. to facilitate the insertion of the tube through the second fixing means.

The looped position of the tube is wanted during non-treatment time because it has been found by the applicant that this shape ensures that no tension is applied to the point where the catheter emerges due to the weight and length of the external line of
10 the catheter. The external part of the catheter and the extender are thus held securely against the body of the patient and will not move during non-treatment time.

The second fixing means will therefore be situated at a suitable distance from the first fixing means to allow a loop to be formed without too much risk of the tube being creased between the two fixing means. The distance between the two means depends
15 on the dimension of each of the fixing means and/or on the length of external line to be attached.

Without implying any restriction, an example would be a rectangular bandage measuring approximately 10 cm by approximately 9 cm. The window of the first means (the nonadhesive part is transparent or semi-transparent in this example) would be
20 roughly square with sides of approximately 4 cm. The band would be roughly a rectangle with a width of approximately 1 cm and a length of approximately 5 cm. The long sides of the rectangle would be parallel to one side of the square of the window and separated by approximately 2 cm.

The band 41 may essentially be in the shape of a rectangle whose two long sides are
25 the sides defining the two openings (411', 411"). The two long sides have a length greater than the diameter of the tube, sufficient to allow the tube and the connector joining the catheter to the extender to be passed through (the dimension of the extender is greater than the diameter of the tube). This length may be at least twice as great as the dimension of the connector. The two short sides of the rectangle may have
30 a length of for example at least twice the diameter of the tube.

The band 41 can be formed in the base support 2: the two auxiliary sides (411', 411'') forming the two openings are produced by two slits made through the thickness of the base support 2. If the band is rectangular, the two long sides of the band are the two slits. The tube will thus be able to be positioned (typically by sliding it) between the
5 lower face of the band and the skin.

Alternatively, the band 41 is a separate element from the base support 2 and is attached to the base support 2 by the opposite sides (41', 41'') permanently or removably. In a simple embodiment of this form, the base support of the second fixing means 4 is a sheet and the band is a separate rectangular (for example) sheet
10 attached to the support by two opposite sides. The tube can thus pass, typically by sliding, between the lower face of the band and that part of the upper face of the base support which is next to the band.

The ends of each slit (411', 411'') can be formed essentially into an arc of a circle tangent to the auxiliary opposite side and extending away from the band. The diameter
15 of this arc of a circle is small compared with the length of the slit. The arc of a circle may be a semicircle. This form of arc of a circle allows the band to be lifted more easily and gives the band better resistance to movement of the tube. This reduces the risk of the end of an auxiliary opposite side tearing.

The adhesive attachment area 42 of the second fixing means 4 can be in contact with
20 the two auxiliary opposite sides (411', 411'') of the band 41. In other words, the lower face of the part 42 of the second fixing means is adhesive at least on each side and in contact with the band 41, for example at least on the areas 43 of the part 42 that are hatched in Figure 1. This allows the second means to keep the part 42 from moving and enables the tube to be inserted easily underneath the band 41 without the part 42
25 moving.

The second fixing means 4 may comprise a thickened area 50 formed on the band 41 compared with the thickness of the base support 2, to enhance the strength of the band, which represents that area of the bandage which is subjected to the greatest tensile force.

30 The thickened area 50 may extend only over the band 41.

A sheet stuck to the lower face 21 of the base support may form the thickened area 50. This embodiment can be envisaged when the base support used for the second means is a film of generally constant thickness with one face entirely adhesive: it is easy to apply definitively the additional sheet which is intended to form the lower face of the
5 band against the adhesive film.

The thickened area 50 may also extend over the full width of the band 41.

The thickened area 50 may extend over a major part of the length of the band and be situated approximately in the middle of the band, as shown in Figure 1, to leave the ends of the auxiliary opposite sides with no thickened area. The thickened area
10 preferably extends over approximately 80 to 95% of the band 41. This is to prevent tearing of the arcs of circles.

In addition, the first fixing means 3 of the bandage may comprise, on the lower face of the base support, a protective part 31 designed to be placed over the exit site and surrounded by the adhesive fixing part 32. This protective part may be a film consisting
15 of the base support which will be applied to the tube and the exit site to protect them against being knocked. Alternatively, this protective part may be a special sheet attached to the base support. These protective means may comprise a material designed to come into direct contact with the exit site and capable of absorbing any unwanted body fluid that oozes out of the patient's exit site and/or that is capable of
20 forming a barrier to bacteria. The bandage here therefore has a dressing function on the exit site.

The protective part 31 of the first fixing means 3 may be made of a transparent or semi-transparent material, meaning a material such that the exit site is left visible. In this way the condition of the exit site, which stays underneath the dressing for some 2
25 to 3 days, can be checked visually.

The protective part 31 of the first fixing means 3 may be nonadhesive. This will allow the bandage to be withdrawn definitively without pulling on the part of the tube just in contact with the exit site and without subjecting the tube (which has been permanently implanted by surgery) to undesired pulling and/or withdrawal. For this purpose the user
30 will detach part of the adhesive part 32, place his finger on roughly the part of the tube

coming out of the exit site, and detach the rest of the adhesive part 32 stuck to the tube, thus not pulling on the tube.

Moreover, at least one indentation 51 may be formed in an edge of the adhesive fixing part 32 of the first fixing means 3 of the bandage 1. The dimensions of the indentation
5 are such that the projecting part 102 of the tube passing out of the adhesive fixing part 32 of the first fixing means 3 can be engaged in and held by the indentation 51.

The outline of at least one indentation 51 is preferably in the shape of a mushroom so that the tube can be passed along the stalk of the mushroom and the head of the mushroom can accommodate the tube. The width of the stalk may be practically zero
10 (a slit) or be approximately equal to the diameter of the tube.

Alternatively, the outline of the indentation may be an arc of a circle (for example a semicircle) of diameter approximately equal to the diameter of the tube of the catheter or may be V-shaped or may be a combined shape of a slightly rounded V. The indentation may be any other shape envisaged by those skilled in the art capable of
15 accommodating the tube on an edge of the first fixing means.

At least one indentation may be situated on a straight line parallel to the band. This straight line is preferably in the mid-plane of the protective part (31).

The dressing may have one indentation.

Alternatively, the dressing may have two indentations, one on each of the two opposite
20 sides of the first fixing means of the bandage (Figure 1). This will allow the user to choose which of the 2 indentations to place the tube in. In use, the bandage will be placed on the patient's abdomen in such a way that the first means are situated next to the second means (if the dressing is rectangular as shown in Figure 1, then it will be arranged so as to extend horizontally across the abdomen). The catheter tube can be
25 passed through either of the two indentations, as desired. It has been observed that the projecting proximal part of the tube emerging from the abdomen needs to be positioned vertically to achieve a better flow. It is for this reason that the indentations are positioned on the bandage in such a way as to keep the projecting proximal part of the tube vertical.

For storing the bandage and protecting the adhesive parts (32, 44), the lower face of the base support may be entirely covered with a detachable film 70. This detachable film may contain silicone or any other material that can be stuck to one adhesive face and detached without harming the adhesive properties of the face.

- 5 In more detail, the detachable film 70 may be composed of one part or of at least two parts. In the case of a nonadhesive film composed of at least two parts, the film is divided into at least a first film part 71 designed to at least partly cover the first fixing means 3 and a second film part 72 designed to at least partly cover the second fixing means 4.
- 10 More particularly, the detachable film may comprise a third film part 73 designed to cover both a part at least of the first fixing means 3 and a part at least of the second fixing means 4, as illustrated in Figures 3 and 5. This will allow the first fixing means to be applied to the skin, followed by the second fixing means, after which the tube can be passed underneath the band.
- 15 More particularly, the first film part 71 is designed to cover a part of the first fixing means 3 that does not include the protective part 31, the second film part 72 is designed to cover a part of the band as far as a line 75 passing between the auxiliary opposite sides (411', 411'') of the band 41 of the second fixing means 4, and the third film part 73 intermediate between the first and second film parts (71, 72) is designed to
- 20 cover the non-covered parts of the first and second fixing means not covered by the first and second film parts (71, 72).

The base support of the bandage can be formed in one piece. In the case of a rectangular bandage, the first fixing means will be roughly a square with sides equal to the width of the rectangle and the second fixing means will be the remaining rectangle,

25 as shown in Figure 1 by the broken-line boundary. This boundary is purely abstract in the case of a one-piece support, but will be actual in the case of a support made in two pieces composed of the first and second fixing means. That is to say, the base support can be formed in a first part and a separate second part which define the first and second fixing means, respectively.

If the support comprises two pieces, the attachment area 42 of the second fixing means 4 may in one case consist simply of two parts on either side of the band 41 for fixing the band to the skin: the separate second means comprise the band 41, which would be fixed to the skin by at least two opposite adhesive attachment points. In this case, the part 43 of the upper face 22 of the support consists of the upper face of the first fixing means. In another case, the area of attachment 42 of the second fixing means 4 may consist of two parts on either side of the band 41 for fixing the band to the skin and may also consist of the areas 43 shown in Figure 2 on either side of the auxiliary opposite sides (411', 411"). In this way the area of the second fixing means that adheres to the skin surrounds the band.

The length and/or area of the adhesive attachment points will be decided with respect notably to the length of the nonadhesive base, to prevent either or both points peeling off at the wrong time. For a two-part support, the user selects the optimum spacing between the first and second fixing means so that the loop of the tube can be of the optimum dimensions.

For storage, transport and distribution, the bandage in its packaging has been sterilized, for example with ethylene oxide. The bandage could be sterilized first and then enclosed in its packaging, or the reverse, or the bandage could be sterilized as it is being placed in the unclosed/unsealed packaging. The packaging may take the form of a peelable sachet consisting of two faces, e.g. one paper face and one transparent face.

The bandage according to the invention may be envisaged with a medical-use tube fixed to it, the tube having an initial part fixed to the first fixing means, a free intermediate part that is essentially in the form of a loop, and a final part that is fixed in a sliding manner to the second fixing means over at least a part 43 of the upper face 22 of the support 2. The tube/bandage assembly can be applied to the skin of a patient who has an implanted tube, the projecting part of which is to be connected to the tube attached to the bandage.

A process for applying the bandage according to the invention comprises the following steps:

- (1) applying and fixing adhesively the first fixing means 3 to the skin and the proximal part of the projecting portion of the tube,
- (2) applying and fixing adhesively the second fixing means 4 to the skin, and
- (3) forming a loop with the distal portion of the projecting part of the tube and sliding the projecting part of the tube between the lower surface of the band 41 and the skin.

Step (1) may be preceded or followed directly by placing the tube in an indentation 51.

In step (3) the tube is inserted, e.g. slid, between the band and the skin directly, in the case of a band produced by two slits through the base support. Alternatively, in step (3) the tube may be slid between the band and the support directly, in the case of a bandage made of a band added to the base support. In another alternative, step (3) will be total or partial detachment of the support band, positioning of the tube, and re-attachment of the band to place the band over the tube.

The order in which the steps have been written is preferably the order in which the process is carried out in time.

Where the bandage comprises a nonadhesive detachable film 70 comprising a first film part 71 designed to at least partly cover the first fixing means 3, and a second film part 72 designed to at least partly cover the second fixing means 23, the process for applying the bandage will include the following steps:

- detaching the first nonadhesive film part 71 from the bandage before the step of fixing adhesively at least in part the first fixing means 3 to the skin and the proximal part of the projecting portion of the tube, and
- after fixing the first adhesive means, detaching the second nonadhesive film part 72 from the bandage before the step of fixing adhesively at least in part the second fixing means 4 to the skin.

If the bandage comprises a nonadhesive detachable film 70 divided into a first film part 71 designed to cover a part of the first fixing means 3 which does not include the protective part 31, a second film part 72 designed to cover a part of the band as far as

a line 75 passing between the auxiliary opposite sides (411', 411'') of the band of the second fixing means 4, and a third film part 73 intermediate between the first and second film parts (71, 72) and designed to cover the non-covered parts of the first and second fixing means not covered by the first and second film parts (71, 72); then the process for applying the bandage includes the following steps:

- detaching the third nonadhesive film part 73 from the bandage before the step of fixing adhesively at least the first fixing means 3 to the skin and the proximal part of the projecting portion of the tube and a part of the second fixing means 4 to the skin (this step being preceded or followed directly by passing the tube into an indentation if desired),
- detaching the second nonadhesive film part 72 from the bandage before the step of fixing adhesively the other part of the second fixing means 4 to the skin, and
- detaching the first nonadhesive film part 71 before the step of fixing adhesively the other part of the first fixing means 3 to the skin.

Advantages of the invention:

The many advantages of the invention are as follows:

- the bandage makes it possible to immobilize the projecting portion of a tube implanted in a patient in a first position during treatment involving the passage of fluid, and immobilizing it in a second position during non-treatment time corresponding to non-passage of fluid,
- the bandage is capable of staying in position on the skin for several days,
- the bandage provides permanent protection of the patient's exit site,
- the bandage permits easy verification of the condition of the exit site throughout the period during which the bandage is on,
- the bandage is strong and impermeable to water and/or bacteria,

- the bandage is easy and inexpensive to manufacture,
- the bandage is easily handled and applied to the skin by the user, and easily detached by the user,
- the bandage can be the same colour as the patient's skin colour or white and pass more or less unnoticed,
- 5 - the bandage saves the nurse or patient time in application,
- the bandage is hypoallergenic,
- the bandage has good breatheability,
- the bandage prevents tugging of the catheter at its point of emergence, and
- 10 - the bandage is small compared with the length of the external catheter part that is to be fixed.

WHAT IS CLAIMED IS:

1) Medical-use bandage (1) having a lower face designed to be turned to the skin, and on the opposite side an upper face; this bandage being designed to immobilize a tube (100) implanted in a body, the implanted tube (100) defining an exit site (101) from the body and a part (102) of the tube projecting from the body; the bandage (1) comprising:

- a base support (2) having a lower face (21) designed to be applied to the skin and an upper face (22),

10 - first fixing means (3) for fixing the exit site (101), comprising on the lower face (21) of the base support (2) an adhesive fixing part (32) designed to be stuck at least partly around the exit site (101) to the skin and to a proximal portion (102') of the projecting part (102) of the tube; and

- second fixing means (4) for engaging the distal portion (102'') of the projecting part (102) of the tube in a defined shape and in a sliding manner, the second fixing means (4) consisting at least partly of a part (43) of the upper face (22) of the support (2), wherein the second fixing means (4) comprise:

- a band (41) having at least part of its non-adhesive lower face designed to be turned to the skin, this band comprising:

20 ▪ two opposite sides (41', 41'') connected to the base support (2), and
 ▪ two auxiliary opposite sides (411', 411'') defining through the upper face of the bandage (1) two openings for allowing the distal projecting portion (102'') of the tube to pass through the openings; and

- an adhesive attachment area (42) that is situated at least partly around the band (41), is defined on the lower face (21) of the support, and is designed to be stuck to the skin.

- 2) Bandage according to claim 1, in which the band (41) is essentially in the shape of a rectangle whose two long sides are the sides defining the two openings (411', 411").
- 3) Bandage according to claim 2, in which the band (41) is formed in the base support (2) and in which the two auxiliary sides (411', 411") forming the two openings are produced by two slits made through the thickness of the base support (2).
- 4) Bandage according to claim 2, in which the band (41) is a separate element from the base support (2) and is attached to the base support (2) by the opposite sides (41', 41").
- 10 5) Bandage according to any one of claims 1 to 3, in which the ends of each auxiliary opposite side (411', 411") is formed essentially into an arc of a circle tangent to the auxiliary opposite side and extending away from the band.
- 6) Bandage according to any one of claims 1 to 5, in which the adhesive attachment area (42) of the second fixing means (4) is in contact with the two auxiliary opposite sides (411', 411") of the band (41).
- 7) Bandage according to any one of claims 1 to 6, in which the second fixing means (4) comprise a thickened area (50) on the band (41) compared with the thickness of the base support (2).
- 8) Bandage according to claim 7, in which the thickened area (50) extends only
20 over the band (41).
- 9) Bandage according to claim 7 or 8, comprising a sheet stuck to the lower face (21) of the base support, the sheet forming the thickened area (50).
- 10) Bandage according to claim 9, in which the thickened area (50) extends over the full width of the band (41).

11) Bandage according to claim 10, in which the thickened area (50) extends over a major part of the length of the band.

12) Bandage according to any one of claims 1 to 11, in which the first fixing means (3) comprise, on the lower face of the base support, a protective part (31) designed to be placed over the exit site and surrounded by the adhesive fixing part (32).

13) Bandage according to claim 11 or 12, in which the protective part (31) of the first fixing means (3) is nonadhesive.

14) Bandage according to any one of claims 1 to 13, in which at least one indentation (51) is formed in an edge of the adhesive fixing part (32) of the first fixing means (3) of the bandage (1), the dimensions of this indentation being such that the projecting part (102) of the tube passing out of the adhesive fixing part (32) of the first fixing means can be engaged in and held by the indentation (51).

15) Bandage according to claim 14, in which the outline of at least one indentation (51) is in the shape of a mushroom so that the tube can be passed along the stalk of the mushroom and the head of the mushroom can accommodate the tube.

16) Bandage according to claim 14 or 15, in which at least one indentation is situated on a straight line parallel to the band, the straight line being preferably in the mid-plane of the protective part (31).

17) Bandage according to any one of claims 1 to 16, in which the lower face of the base support is entirely covered with a detachable film (70).

18) Bandage according to claim 17, in which the detachable film (70) is nonadhesive and is divided into at least:

- a first film part (71) designed to at least partly cover the first fixing means (3),
and

- a second film part (72) designed to at least partly cover the second fixing means (4).

19) Bandage according to claim 18, in which the detachable film comprises a third film part (73) designed to cover both a part at least of the first fixing means (3) and a part at least of the second fixing means (4).

20) Bandage according to claim 19, in which:

- the first film part (71) is designed to cover a part of the first fixing means (3) that does not include the protective part (31),

10 - the second film part (72) is designed to cover a part of the band as far as a line (75) passing between the auxiliary opposite sides (411', 411'') of the band (41) of the second fixing means (4), and

- the third film part (73) intermediate between the first and second film parts (71, 72) is designed to cover the non-covered parts of the first and second fixing means not covered by the first and second film parts (71, 72).

21) Bandage according to any one of claims 1 to 20, in which the base support is formed in one piece.

22) Bandage according to one of Claims 1 to 20, in which the base support is formed in a first part and a second part which define the first and second fixing means, respectively.


20 23) Bandage according to any one of claims 1 to 22, sterilized and enclosed in packaging.

24) Bandage according to any one of claims 1 to 23, to which a medical-use tube is fixed, the tube comprising: an initial part fixed to the first fixing means, a free

intermediate part that is essentially in the form of a loop, and a final part that is fixed in a sliding manner to the second fixing means over at least a part (43) of the upper face (22) of the support (2).


1/5

figure 1




back view

figure 2



top view

figure 3



back view

figure 4




figure 5

