




US 20040258563A1

(19) **United States**(12) **Patent Application Publication** (10) **Pub. No.: US 2004/0258563 A1****Young et al.**(43) **Pub. Date: Dec. 23, 2004**(54) **CAPS FOR SAMPLE WELLS AND  
MICROCARDS FOR BIOLOGICAL  
MATERIALS****Publication Classification**(51) **Int. Cl.<sup>7</sup>** ..... **G01N 21/00**(52) **U.S. Cl.** ..... **422/58; 422/99; 422/102;  
422/82.05**(75) **Inventors: Eugene F. Young, Marietta, GA (US);  
Steven J. Boege, San Mateo, CA (US);  
Donald R. Sandell, San Jose, CA (US)****Correspondence Address:  
MILA KASAN, PATENT DEPT.  
APPLIED BIOSYSTEMS  
850 LINCOLN CENTRE DRIVE  
FOSTER CITY, CA 94404 (US)**(57) **ABSTRACT**

A cover for a biological sample well tray, comprising a cap for sealing a sample well. The cap comprises a well lens for focusing light into the sample well and collecting light from the sample. In another aspect, the cap comprises an elongate portion configured to permit incoming light to pass into the sample well and out of the sample well. Various other aspects comprise a microcard for biological material, and an apparatus for a plurality of sample well strips. A method for testing a biological sample is also provided.

(73) **Assignee: Applera Corporation, Foster City, CA**(21) **Appl. No.: 10/602,113**(22) **Filed: Jun. 23, 2003**





FIG. 1C

FIG. 1B

FIG. 1A



**FIG. 1D**






FIG. 2B


FIG. 2A




**FIG. 3**




**FIG. 4**




**FIG. 5**




**FIG. 6A**



**FIG. 6B**



**FIG. 7**



**FIG. 8**






FIG. 10

FIG. 9B


FIG. 9A




**FIG. 11B**




**FIG. 11A**




**FIG. 11C**



**FIG. 14**



**FIG. 12**



**FIG. 13**




Figure 15A




Figure 15B




Figure 16




Figure 17




Figure 18




Figure 19

## CAPS FOR SAMPLE WELLS AND MICROCARDS FOR BIOLOGICAL MATERIALS

### FIELD

[0001] The present teachings relate to devices and methods for containing samples of biological material. The present teachings relate to well lenses for the samples of biological material that can be contained in a sample container.

### BACKGROUND

[0002] Biological testing has become an important tool in detecting and monitoring diseases. In the biological testing field, polymerase chain reactions (PCR), ligase chain reactions, antibody binding reactions, oligonucleotide ligations assays, hybridization assays, and other reactions can be used to analyze nucleic acids. In the biological field, cell-surface receptor binding assays, fluorescence-linked immunosorbent assays (FLISA), protein-protein interactions, enzyme assays, apoptosis assays, and other reactions can be used to analyze cells. These reactions have become valuable research tools with applications such as cloning, analysis of genetic expression, DNA sequencing, and drug discovery.

[0003] Recent developments in the field have led to an increased demand for biological testing devices. Biological testing devices are now being used in an increasing number of ways. It can be desirable to provide real-time detection capability in order to analyze on-going reactions.

[0004] In a real-time detection device, a plurality of lenses can be used to focus light from a light source onto the samples to be tested, and to collect the light emitted by the sample. These lenses can be bulky, taking up a considerable amount of space above the sample well tray. The use of a large number of components can make assembly and alignment of the optical components of the detection apparatus time consuming. Therefore, it can be desirable to have a simple, less complex structure.

### SUMMARY

[0005] According to various embodiments, a cover for a biological sample well tray can comprise a cap for sealing a sample well. The cap can comprise a well lens for focusing light into the sample well and substantially collimating light emitted by the sample. The well can comprise a well lens for focusing light into the sample well and collecting light emitted by the sample. The well lens can be positioned in the side or bottom of the well.

[0006] According to various embodiments, a cover for a biological sample well tray can comprise a cap for sealing a sample well. The cap can comprise an elongate portion configured to permit incoming light to pass into the sample well and out of the sample well. The elongate portion can comprise a well lens for focusing light into the sample well and collecting light emitted by the sample. The elongate portion can be positioned to provide a gap between cap and sample.

[0007] According to various embodiments, a microcard for biological material can comprise a first member and a second member. The second member can provide a plurality of sample chambers between the first member and the second member, the second member comprising a plurality

of well lenses corresponding to the plurality of sample chambers. The well lenses can be in fluid contact with a sample of biological material in the sample chamber. The well lenses can focus light into the sample well and collecting light emitted by the sample.

[0008] According to various embodiments, an apparatus for a plurality of sample well strips can be provided, wherein each sample well strip comprises a plurality of sample wells defined by side walls and bottoms, and a plurality of bottom stacking projections. Each bottom stacking projection can extend downward from a sample well bottom. The bottom stacking projection can be configured to cap another sample well in another sample well strip. The side walls can comprise a plurality of well lenses for focusing light into the sample well and collecting light emitted by the sample.

[0009] According to various embodiments, a method for testing a biological sample comprises: providing a sample well or sample chamber containing said biological sample; providing a cap for the sample well, wherein the cap comprises a well lens; focusing light into the sample well; and collecting light emitted by the sample.

[0010] It is to be understood that both the foregoing general description and the following description of various embodiments are exemplary and explanatory only and are not restrictive.

### BRIEF DESCRIPTION OF THE DRAWINGS

[0011] The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate several exemplary embodiments. In the drawings,

[0012] According to various embodiments, **FIG. 1A** illustrates a cross-sectional view of a sample well of a sample well tray sealed with a transparent plastic sheet.

[0013] According to various embodiments **FIG. 1B** illustrates a cross-sectional view of a sample well of a sample well tray with a flat cap.

[0014] According to various embodiments, **FIG. 1C** illustrates a cross-sectional view of a sample well of a sample well tray with a domed cap.

[0015] According to various embodiments, **FIG. 1D** illustrates a perspective view of a sample well tray with a plurality of sample wells.

[0016] According to various embodiments, **FIG. 2A** illustrates a cross-sectional view of a cap for a sample well, the cap comprising well lens.

[0017] According to various embodiments, **FIG. 2B** illustrates a cross-sectional view of a cap for a sample well, the cap comprising a Fresnel well lens.

[0018] According to various embodiments, **FIG. 3** illustrates a cross-sectional view of a cap comprising a solid elongate portion and a separate well lens.

[0019] According to various embodiments, **FIG. 4** illustrates a side view of the cap of **FIG. 3**.

[0020] According to various embodiments, **FIG. 5** illustrates a cross-sectional view of a cap comprising a solid elongate portion and a well lens.

[0021] According to various embodiments, **FIG. 6A** illustrates a cross-sectional view of a cap comprising a hollow elongate portion positioned in a sample well and a separate well lens.

[0022] According to various embodiments, **FIG. 6B** illustrates a cross-sectional view of a cap comprising a hollow elongate portion similar to **FIG. 6A**.

[0023] According to various embodiments, **FIG. 7** illustrates a side view of the cap comprising a hollow elongate portion of **FIG. 6A**.

[0024] According to various embodiments, **FIG. 8** illustrates a cross-sectional view of the cap comprising a hollow elongate portion of **FIGS. 6A and 7**.

[0025] According to various embodiments, **FIG. 9A** illustrates a cross-sectional view of a cap comprising a hollow elongated portion and a well lens.

[0026] According to various embodiments, **FIG. 9B** illustrates a cross-sectional view of a cap comprising a hollow elongate portion similar to **FIG. 9A**.

[0027] According to various embodiments, **FIG. 10** illustrates a cross-sectional view of a cap comprising a solid elongate portion and a well lens.

[0028] According to various embodiments, **FIG. 11A** illustrates a top view of a microcard with a plurality of sample chambers comprising well lenses.

[0029] According to various embodiments, **FIG. 11B** illustrates a cross-sectional view of the microcard of **FIG. 11A**, taken along line 11B-11B of **FIG. 11A**, showing the microcard positioned in a horizontal orientation.

[0030] According to various embodiments, **FIG. 11C** illustrates a cross-sectional view of the microcard of **FIG. 11A**, showing the microcard positioned in a vertical orientation.

[0031] According to various embodiments, **FIG. 12** illustrates a cross-sectional frontal view of a plurality of sample well strips in a stacked configuration.

[0032] According to various embodiments, **FIG. 13** illustrates a cross-sectional side view of the plurality of sample well strips of **FIG. 12**.

[0033] According to various embodiments, **FIG. 14** illustrates a top view of the plurality of sample well strips of **FIG. 12**.

[0034] According to various embodiments, **FIG. 15A** illustrates a cross-sectional view of a sample well with a flat window on the bottom.

[0035] According to various embodiments, **FIG. 15B** illustrates a cross-sectional view of a sample well with a well lens on the bottom.

[0036] According to various embodiments, **FIG. 16** illustrates a cross-sectional view of a sample well with a well lens on the side.

[0037] According to various embodiments, **FIG. 17** illustrates a cross-sectional view of a plurality of sample well strips in a stacked configuration, with well lenses on the bottom and side. and

[0038] According to various embodiments, **FIG. 18** illustrates a cross-sectional view of a sample well with an elongate portion leaving an air gap with sample.

#### DESCRIPTION OF VARIOUS EMBODIMENTS

[0039] Reference will now be made to various exemplary embodiments, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers are used in the drawings and the description to refer to the same or like parts.

[0040] Although terms like “horizontal,” “vertical,” “upward,” “downward,” “side,” “front,” “upper,” and “lower” are used in describing various aspects of the present teachings, it should be understood that such terms are for purposes of more easily describing the teachings, and do not limit the scope of the teachings.

[0041] According to various embodiments, a sample well tray for biological samples can be provided. An example of a sample well tray **10** with a plurality of sample wells **12** is shown in **FIG. 1D**. It should be understood that any type of sample well tray can be used. Sample well trays typically have a plurality of sample wells for holding a biological sample. **FIG. 1A** shows a sample well **12** of a sample well tray **10**. A sample well tray can have a rectangular shape with a matrix of sample wells **12** contained therein. Although **FIG. 1D** shows a sample well tray with 96 wells in a 8×12 matrix, it should be understood that the present invention is applicable for use with sample well trays having any number of wells from one well to several thousand wells, such as, for example, 24 and 384 sample wells. Sample well trays having any number of sample well sizes can also be used. Although the term sample well tray is used, it should be understood that many aspects of the present teachings are also suitable with other substrates such as microcard sample trays, where sample wells are replaced by sample chambers.

[0042] According to various embodiments, the sample well tray can be suitable for incorporation into a number of different thermal cyclers, including but not limited to a 96-well Applied Biosystems thermal cycler. The thermal cycler can be configured for thermally cycling samples of biological material. The thermal cycling device can be configured to perform nucleic acid amplification on samples of biological material. One common method of performing nucleic acid amplification of biological samples is PCR. Various PCR methods are known in the art, as described in, for example, U.S. Pat. Nos. 5,928,907 and 6,015,674 to Woudenberg et al., the complete disclosures of which are hereby incorporated by reference for any purpose. Other methods of nucleic acid amplification include, for example, ligase chain reaction, oligonucleotide ligation assay, and hybridization assay. These and other methods are described in greater detail in U.S. Pat. Nos. 5,928,907 and 6,015,674.

[0043] According to various embodiments, the sample well tray can be used in a thermal cycling device that performs real-time detection of the nucleic acid amplification of the samples in the sample disk during thermal cycling. Real-time detection systems are known in the art, as also described in greater detail in, for example, U.S. Pat. Nos. 5,928,907 and 6,015,674 to Woudenberg et al., incorporated herein above. During real-time detection, various characteristics of the samples are detected during the thermal cycling in a manner known in the art of nucleic acid

amplification. Real-time detection can permit more accurate and efficient detection and monitoring of the samples during the nucleic acid amplification process. Alternatively, the sample well tray can be used in a thermal cycling device that performs endpoint detection of the nucleic acid amplification of the samples.

[0044] According to various embodiments, the sample well tray can be configured to contact a sample block for thermally cycling the biological materials in the sample wells of the sample well tray. The sample block can be operatively connected to a temperature control unit programmed to raise and lower the temperature of the sample block according to a user-defined profile. For example, in various embodiments, a user can supply data defining time and temperature parameters of the desired PCR protocol to a control computer that causes a central processing unit (CPU) of the temperature control unit to control thermal cycling of the sample block. Several non-limiting examples of suitable temperature control units for raising and lowering the temperature of a sample block are described in U.S. Pat. No. 5,656,493 to Mullis et al. and U.S. Pat. No. 5,475,610 to Atwood et al., the disclosures of which are both hereby incorporated by reference for any purpose.

[0045] According to various embodiments, FIGS. 1A, 1B, and 1C show sealing structures for sample wells in sample well trays where the well lenses are separate. For example, FIG. 1A is a cross-sectional view of a sample well 12 of sample well tray 10 sealed with a transparent plastic sheet that can be adhesive. The sample well 12 can include side walls 14 and a bottom surface 16. The sample well 12 of FIG. 1A is configured to store a biological sample S in the interior of the side walls 14 and bottom surface 16. According to various embodiments, the sample well can have a working volume of approximately 200  $\mu$ l. The volume of the sample wells can vary anywhere from 0.1  $\mu$ l to thousands of microliters ( $\mu$ l). According to various embodiments, a volume between 5  $\mu$ l and 500  $\mu$ l, or 10  $\mu$ l and 200  $\mu$ l, or 50  $\mu$ l can be used. In FIG. 1A, a thin, adhesive, transparent plastic sheet 18 is provided for sealing the top surface 20 of the sample well 12. The sheet 18 can be made out of any suitable material such as hydrocarbon-based polymers compatible with PCR as known in the art of nucleic acid amplification. These polymers can include, for example, polypropylene, polycarbonate, and polyethylene. According to various embodiments, the sheet 18 is PCR-compatible. The sheet 18 can provide an appropriate seal to the sample well 12.

[0046] According to various embodiments, as shown in FIG. 1A, a well lens 22 can be provided adjacent to the sample well 12. The well lens 22 can focus incoming light 24 from a light source (not shown) to a region in the sample of biological material S. The well lens 22 can collect the emitted light from the sample of biological material S and direct it toward the light detection apparatus (not shown). A wide variety of well lenses can be used for this purpose.

[0047] According to various embodiments, FIG. 1B shows a sample well tray 10 with a flat cap 30 placed in the sample well 12. The flat cap 30 includes a top portion 32 having a flat top surface 34 and a flat bottom surface 36. Cap 30 further includes a cylindrical sealing structure 38. According to various embodiments, the flat bottom surface 36 forms an annular surface for engaging a top surface 20 of

the sample well 12. Cylindrical sealing structure 38 extends downward into the sample well 12 to engage the inside of side walls 14. The engagement of an outside surface 39 of the cylindrical sealing structure 38 serves to promote sealing of the sample well 12. The engagement of the flat bottom surface 36 of the top portion of the cap 30 with the top surface 20 of the sample well 12 also serves to promote sealing of the sample well 12. The sample well configuration of FIG. 1B further includes the well lens 22 for directing the incoming light 24 into the sample S of biological material, as discussed in greater detail with respect to FIG. 1A.

[0048] According to various embodiments, the cap 30 shown in FIG. 1B can be provided individually, in strips, or in sheets in order to facilitate the insertion and removal of the caps from the top of the sample wells 12. In a 96-well configuration, the caps 30 can be provided in strips typically having either 8 or 12 interconnected caps. In a 384-well configuration, the caps can be provided in strips typically having either 16 or 24 interconnected caps.

[0049] According to various embodiments, FIG. 1C shows sample well tray 10 with a round domed cap 40 placed in the sample well 12. The round cap 40 is similar to the flat cap 30 of FIG. 1B but has a slightly curved or domed central cap portion 42. The round cap 40 operates similarly to the flat cap. Both require the use of a separate well lens 22 positioned over the cap, for directing the incoming light 24 into the sample S of biological material. The feature of a separate well lens takes up space above the sample well tray.

[0050] According to various embodiments, a cover for a biological sample well tray is provided. In one aspect, the cover comprises a cap for sealing a sample well. The cap can comprise a well lens for focusing light into the sample well from a light source and/or collect light emitted by the sample toward a detection apparatus.

[0051] According to various embodiments, such as illustrated in FIGS. 2A and 2B, a cap with an integrated well lens is provided. As shown for example in FIG. 2A, the sample well 12 can be provided with a cap 50 having a well lens 52 integrally formed into the cap 50. The well lens 52 can provide focusing to the incoming light into the sample S of biological material, without the need for a separate well lens. This can save space, reducing costs and the number of parts and increases collection efficiency. As shown in FIG. 2A, the well lens 52 can include a top surface 54 and a bottom surface 58. The top surface 54 can be curved and the bottom surface 58 can be flat. Incoming light 24 from a light source (not shown) passes through top surface 54 through to the bottom surface 58 of the well lens 52 and into the sample well 12, focusing on a region in the sample S of biological material. The well lens 52 can further serve to collect the light emitted from the biological material and direct it toward the light detection apparatus (not shown). The term "emitted light" or grammatical variations thereof as used herein refers to the light emitted from the biological material that can include fluorescence emitted by the sample or dye molecules, for example fluorescent dyes, upon excitation by the incoming light. Emitted light can also include light scattering off of objects in the biological sample. Emitted light can also include chemiluminescence, phosphorescence, and Raman scattering. As discussed previously, the light detection can be performed either by an end-point detection apparatus or a real-time detection apparatus, depending on the specific application.

[0052] According to various embodiments, the well lens can be of any of a variety of types known in the optics. **FIG. 2A** shows a cap comprising a plano-convex well lens. The well lens **52** can focus substantially collimated light on an object plane within the biological sample **S** and collect light from an object plane in the biological sample and substantially collimate the light.

[0053] According to various embodiments, cap **50** and well lens **52** can be made out of any acceptable material, such as polypropylene and other hydrocarbon-based polymers. Other suitable materials include glass and acrylic. The material can be compatible with PCR as known in the art of nucleic acid amplification. The cap and well lens can be manufactured by any known method, such as injection or compression molding, vacuum forming, and pressure forming. In the embodiment shown, the well lens **52** is integrally formed with the cap **50**. It should be understood however that the well lens **52** could be attached by any known method.

[0054] According to various embodiments, the cap can include a cylindrical sealing member configured to engage an inner surface of the sample well. As shown in **FIG. 2A**, cap **50** can include a sealing structure **56** integrally formed with the well lens **52** for promoting sealing of the inside of sample well **12**. Sealing structure **56** is shown as a generally cylindrical member extending downward from the bottom surface **58** of the well lens **52**. An outer surface **59** of the cylindrical sealing structure **56** can contact or otherwise engage the inner side wall of the sample well **12** to assist in promoting sealing of the sample well from the outside atmosphere. The outer surface **59** can be sized to have an interference fit with the inner surface of the sample well **12**.

[0055] According to various embodiments, the cap **50** can further include an outer annular flat bottom surface **60** for engaging the top surface **20** of the sample well **12**. This engagement also serves to promote sealing of the sample well **12**.

[0056] According to various embodiments, the caps of the present teachings are suitable to fit in a wide variety of sample wells. **FIG. 2A** shows the cap **50** in a sample well **12** with sidewalls **14** being tapered in a conical manner. It should be understood that the sidewalls **14** of the sample wells **12** can also be non-tapered, or any other suitable configuration. Additionally, although the bottom surface **16** is shown as being rounded, the bottom surface **16** can have any other suitable configuration, such as, for example, flat. The cap can also be dimensioned to fit virtually any type of sample well. For example, with a 96-well sample well tray such as shown in **FIG. 11D**, the caps will be designed and sized to fit within each sample well. With a 384-well sample tray, the size of the caps will typically be smaller. It should be understood that the dimensions can greatly vary, depending on the size of the sample wells. Further, caps **50** can be manufactured into strips or sheets. The use of strips or sheets can facilitate the insertion and removal of the caps from the sample wells.

[0057] According to various embodiments, by integrating the well lens **52** into the cap **50**, the need for a separate well lens spaced from the sample well **12** can be eliminated, thereby reducing the number of parts that are needed. With fewer parts, concerns about alignment between the well lens

and the sample well are reduced. Moreover, integrating several parts into one can make the apparatus more compact, taking up less space.

[0058] According to various embodiments, the well lens can be a Fresnel lens integrated into the sample well cap. **FIG. 2B** shows an embodiment wherein the cap **70** includes a well lens **72** in the form of a Fresnel lens of the type manufactured by Fresnel Technologies of Fort Worth, Tex. **FIG. 2B** shows a Fresnel lens **72** integrated into a top surface **74** of the cap **70**. The Fresnel lens **72** serves to focus the incoming light **24** from the light source (not shown) into the sample **S** of biological material. Fresnel lenses are flat on one side and on the other side comprise a plurality of ridges as shown in **FIG. 2B**. The angle of the ridges focus the light even though the lens is flat. Among the characteristics of Fresnel lenses is that they can be thin and easily be made of plastic. Fresnel lenses can be used as a positive focal length collector or collimator. Fresnel lenses can have the power of convex lenses, but are thinner. This is an advantage because the optical path in the bulk of the lens is substantially reduced. Bulk transmission losses are proportional to optical path length, so reducing optical path length reduces transmission losses. The Fresnel lens **72** also serves to collect the light emitted from the sample **S** to be tested. The use of the Fresnel lens allows for optical detection without requiring a separate well lens.

[0059] According to various embodiments, the sample well cap is provided that includes an elongate member extending into the biological sample in the sample well. To the extent that any of the following structure is similar to the structure described above, a detailed description will not be repeated. For example, the sample well tray **10** and sample wells **12** are assumed to be identical, or at least similar in important aspects, to the sample well tray and sample well previously described. In the embodiments shown in **FIGS. 3-10**, a cap is provided for a sample well of a sample well tray, the cap having an elongate portion.

[0060] According to various embodiments, the cap can be provided with an elongate member and a separate well lens. As shown for example in **FIGS. 3-4**, a cap **110** can be provided for the sample well **12**. The cap **110** includes a top portion **112**. In the embodiment shown in **FIGS. 3-4**, the top portion **112** comprises a flat top surface **114** and an annular bottom surface **130**. The top portion **112** assists in sealing the inside of the sample wells **12** from the outside atmosphere. The top portion **112** includes an annular bottom surface **130** for engaging a top surface **20**, of the sample well **12** to promote sealing of the sample well **12**, as shown in **FIG. 3**.

[0061] According to various embodiments, the cap **110** can further comprise an intermediate portion **118** that extends from the top portion **112**. In the embodiment shown, the intermediate portion **118** has a smaller diameter than the top portion **112**. The intermediate portion **118** is positioned between the top portion **112** and an elongate end portion **120** of the cap **1110**.

[0062] In various embodiments, the intermediate portion **118** includes a generally cylindrical sealing member **116** that can be sized so that an outer surface of the intermediate portion **118** engages the inner surface of the sample well side wall **14** upon insertion in the sample well **12**. The intermediate portion **118** is shown as being solid in **FIGS. 3-4**. The intermediate portion **118** shown in **FIG. 3** includes an outer

surface **122** configured for mating with the inner surface of the side wall **14**. As shown in **FIG. 3**, the portion of the outer surface **122** that engages the inner surface of the side wall **14** has a greater diameter than the portion of the intermediate portion **118** that does not engage the side wall **14**. The outer surface **122** shown in **FIG. 3** provides a line contact with the sample well side wall **14** to assist in sealing the sample well **12** from the outside atmosphere. It should be understood, that alternatively, the outer surface **122** can have a constant diameter so that a large amount of the outer surface engages the inner surface of the side wall **14**. In alternative embodiments, a portion of the outer surface can include a separate ring or gasket to ensure a tight seal. The engagement assists in promoting a seal between the inside of the sample well **12** and the atmosphere.

[0063] According to various embodiments, the cap **110** can further include an elongate portion **120** extending from the intermediate portion **118** of the cap. Although shown as having a different diameter than the intermediate portion **118**, it should be understood that the elongate portion **120** could, in some embodiments, have the same diameter as the intermediate portion **118**. Alternatively, the intermediate portion **118** can not be required, so that the elongate portion can be all; that is needed. In the embodiment shown in **FIGS. 3-4**, the elongate portion **120** is a solid cylinder with an outside diameter less than the diameter of the intermediate portion **118**. It should be understood that the elongate portion **120** can be any other suitable shape. The elongate portion **120** further includes a bottom surface **138** configured to contact the liquid sample **S** in the sample well.

[0064] According to various embodiments, the elongate portion **120** is configured to permit incoming light to focus in a desired portion of the sample **S** in the sample well **12**. The incoming light can enter the cap **110** through the top surface **114** of the cap and then exit the cap **110** through the bottom surface **138** of the elongate portion **120**, directly into the liquid sample. By being in direct contact with the liquid sample **S** in the sample well **12**, condensation is prevented on the bottom surface **138** of the cap. It is desirable to avoid the formation of condensation on the bottom portion of a cap. Condensation can obstruct the optical path, thereby compromising the quality of the optical data. In various embodiments air adjacent to the caps can permit condensation to occur on the caps. In various embodiments, a heated cover raises the temperature of the caps **110** and sample well **12** to the desired temperature to avoid condensation. A heated cover, however, adds to the complexity of the device and increases costs. In various embodiments, the device can be simplified and costs can be reduced by providing the elongate portion **120** of the cap **110** that directly contacts the sample **S**, as described in the present teachings.

[0065] According to various embodiments, as shown in **FIGS. 3-4**, the cap **110**, including the elongate portion **120**, is solid. The cap **110** can be made out of any material. According to various embodiments, the cap **110** is made out of an optically clear PCR-compatible material. Examples of suitable materials include, but are not limited to, thermoplastic materials such as polypropylene, or polycarbonate resin marketed as LEXAN® by GE Plastics, Inc., Pittsfield, Mass.) that provides high transparency (light transmittance or clarity). Another suitable material includes resin-based polymethylpentene marketed as TPX® by Mitsui Chemicals, Inc. (Tokyo, Japan) which provides high transparency

and resistance to heat and chemicals. Other high transparency plastics which can be used for the cap include polymethyl methacrylate (PMMA) marketed as Lucryl® by BASF (Germany). The cap **110**, including the elongate portion **120**, can be formed by any known method, such as, for example, injection molding.

[0066] It should be understood that the cap **110** described in **FIGS. 3-4** is suitable for use with any type of sample well. The sample well cap can be suitably dimensioned for virtually any type of sample well and sample well tray. In one example for a 96-well tray, the cap **110** shown in **FIGS. 3-4** has the following dimensions: top diameter (d2)=8.00 mm; elongate portion diameter (d1)=4.00 mm; and height (h1)=12.00 mm. These dimensions are for purposes of example only.

[0067] According to various embodiments, as shown in **FIG. 3**, a well lens can be provided adjacent to the cap **110**. The well lens **22** can be identical to those described previously. The well lens **22** acts to direct incoming light from a light source (not shown) to a region in the sample of biological material **S**. The well lens **22** further serves to collect the light emitted from the biological material and direct it toward the light detection apparatus (not shown).

[0068] As discussed above, it is preferable to minimize the amount of condensation that occurs on the cap. According to various embodiments, a heater can be provided around the air gap **A** (see **FIG. 3**) above the top level of the liquid sample and below the intermediate portion **118**. In various embodiments, a resistive, or other type of heater, could be provided around the sample well side walls **14** in order to heat the sample well walls and prevent condensation from occurring on the inside of the sample well where air is located. In various embodiments, the heaters can be resistive heaters or Peltier heaters used to heat a metal sample block as known in the art of thermal cycling.

[0069] According to various embodiments, a cap can be provided with a well lens integral with the cap, and an elongate portion extending into the sample well. **FIG. 5** shows a cap **140** similar to the cap shown in **FIGS. 3-4**, but with a well lens **142** attached to or integral with the top portion **112** of the cap. The well lens **142** shown in **FIG. 5** is a curved lens similar to those described above. In the embodiment shown in **FIG. 5**, the well lens **142** is integrated into the cap **140**. The cap **140** can be formed in any known manner, such as injection or compression molding. The well lens **142** is configured to direct incoming light to a desired position in the interior of the sample well **12** and to direct reflected outgoing light to a detection apparatus (not shown).

[0070] According to various embodiments, by integrating the well lens **142** into the cap **140**, the need for a separate well lens spaced from the sample well is eliminated, thereby reducing the number of parts that are needed. This results in the features described regarding the embodiment illustrated in **FIG. 2B**, such as reducing concerns about alignment, making the apparatus more compact, and reducing costs.

[0071] According to various embodiments, a sample well cap with a hollow elongated portion can be provided. A hollow elongate portion can have less bulk transmission loss than a solid elongate portion. As shown in **FIGS. 6A, 7** and **8**, a sample well cap **150** can be provided that has a hollow interior portion **152**. The cap **150** includes a top portion **154**

and an elongate portion **156**. The top portion **154** includes an annular bottom surface **158** for engaging a top portion **20** of the sample well **12** in a manner discussed earlier.

[0072] According to various embodiments, as shown for example in **FIG. 6A**, the elongate portion **156** of sample well cap **150** is defined by conical walls **162** extending from the top portion **154** in a frusto-conical manner. When the cap **150** is positioned on the sample well **12**, the walls taper so that a space is provided between an outer surface **164** of the conical walls **162** and an inner surface of the sample well side walls **14**, except at the point of contact **C** between the conical walls **162** and the side walls **14**. In the embodiment shown in **FIG. 6A**, the elongate portion **156** contacts the side walls at an upper region thereof via notch **166**. As shown in **FIG. 6A**, the diameter of the elongated portion **156** decreases progressively as the distance from the top portion **154** increases. In various embodiments, the progression of the elongated portion decreases linearly or exponentially.

[0073] According to various embodiments, the elongate portion **156** further includes a bottom portion (or surface) **168**. As shown in **FIG. 6A** for example, the elongate portion **156** is configured so that the bottom surface **170** of bottom portion **168** extends into and contacts the sample of biological material **S** to be tested. Light can pass through bottom portion **168** for purposes of optical detection. With the embodiment illustrated in **FIG. 6A**, the incoming light **24** from the light source (not shown) passes through the well lens **22**, through the hollow interior region of the cap, and then through the bottom portion **168** into the sample **S** to be tested. The reflected light can then pass back through the bottom portion **168** to the well lens **22** and to the detection apparatus (not shown).

[0074] It should be understood that the cap **150** can be of any suitable dimension. In one example shown in **FIG. 7**, the cap has the following dimensions: top portion diameter ( $d_2$ )=8.00 mm; bottom surface diameter ( $d_1$ )=4.00 mm; and height ( $h_1$ )=12.00 mm. This embodiment reflects a 96-well tray. The size of the cap is determined from the working volume of the sample well, and will vary depending on the desired working volume. **FIG. 8** shows a cross-section of cap **150**.

[0075] According to various embodiments, as shown in **FIG. 6B**, the cap shown in **FIG. 6A** can have different dimensions and a different sample well. Sample well cap **150'** shown in **FIG. 6B** is similar to sample well cap **150** shown in **FIG. 6A**. In **FIG. 6B**, the outer surface of the upper portion **174** of the elongate portion **156'** is shown as having a smooth outer surface. In contrast, the outer surface of the upper portion of the elongate portion **156** shown in **FIG. 6A** has a notch **166**.

[0076] According to various embodiments, a sample well cap is provided with a hollow elongate portion with a bottom surface incorporating a well lens. **FIG. 9A** illustrates a variation of the sample well cap shown in **FIGS. 6A, 7**, and **8**. As shown in **FIG. 9A**, the sample well cap **180** has a top portion and elongate portion **186** similar to that described in **FIG. 6A**, but further includes a well lens **182** integrally formed in a bottom surface **184** of sample well cap **180**. The well lenses in this embodiment are similar to those described above. The provision of a well lens integral with the elongate portion eliminates the need for the separate well lens posi-

tioned above the sample well cap. Eliminating the need for a separate well lens has all of the advantages previously discussed.

[0077] According to various embodiments, **FIG. 9B** shows a cap similar to that shown in **FIG. 9A**, but with different dimensions, and a different sample well. For most purposes, sample cap **180'** is similar to sample cap **180** shown in **FIG. 9A**. According to various embodiments, as shown in **FIG. 9B**, the condensation cannot form on the bottom surface of the lens, because there is no air present, i.e. the bottom of the elongate portion **186** is immersed in sample **S**. According to various embodiments, as shown in **FIG. 19**, an air gap can be present between the bottom surface of the lens and sample **S**.

[0078] According to various embodiments, a sample well cap with an solid elongate portion and an integral well lens can be provided. **FIG. 10** shows a cap with a solid elongate tube, and a sealing member surrounding the elongate tube. In the embodiment shown in **FIG. 10**, the cap **200** includes a sealing member **202** and an elongate tube **204**. The sealing member **202** can be of any shape. In the embodiment shown in **FIG. 10**, the sealing member **202** is similar to the top and intermediate portions of the other embodiments. For example, sealing member **202** includes a bottom surface **206** for contacting a top surface **20** of the sample well **12**, and side surfaces **208** for contacting an inner surface of the sidewall of the sample well, to promote sealing in a manner discussed previously. Sealing member **202** can be constructed of a variety of suitable materials, including hydrocarbon-based polymers compatible with PCR as known in the art of nucleic acid amplification. The sealing member **202** can include a through-hole **210** passing through the center thereof, for permitting an elongate tube **204** to be fixed thereto. In the embodiment shown in **FIG. 10**, the elongate tube **204** is fixedly attached to the sealing member **202**, in any known manner. The elongate tube **204** can also be integral with the sealing member **202**.

[0079] According to various embodiments, as shown in **FIG. 10**, the bottom of the elongate tube **204** can include a curved lens **210**. The curved lens **210** serves to focus the incoming light from the light source (not shown) onto the sample **S** to be tested. The curved lens **210** is similar to those previously discussed. In one embodiment, the curved lens **210** is a spherical convex lens.

[0080] According to various embodiments, a microcard for biological material is provided. The microcard can comprise a first member, and a second member defining a plurality of sample chambers between the first member and the second member. In various embodiments, the second member can include a plurality of well lenses corresponding to the plurality of sample chambers. The well lenses are in fluid contact with a sample of biological material in the sample chamber. The well lenses focus light into the sample chamber and transmit light out of the sample chamber.

[0081] According to various embodiments, as shown in **FIGS. 11A and 11B**, a substrate such as microcard **250** can be provided. A microcard is a two-dimensional array of sample loci held within a continuous or non-perforated substrate. The microcard can be flexible or rigid. The substrate or microcard can contain any number of sample chambers for containing samples of biological material. The most typical number of sample chambers is 60, 96, 384, or

1536, however, the microcard can include any number of sample chambers from one to at least several thousand. **FIG. 11A** shows an example of a microcard **250** according to the embodiment of the present teachings.

[0082] According to various embodiments, as shown in **FIG. 11B**, the microcard **250** includes a first member **262** and a second member **264**. In the embodiment shown in **FIG. 20B**, the first member **262** includes all of the features of the flow paths and sample chambers **266** in a polymeric sheet. A plurality of sample chambers **266** are defined between the first and second member.

[0083] According to various embodiments, the first member **262** can be made of any suitable material such as a polymer. One such suitable polymer is polypropylene. Other suitable polymers include, for example, polyester, polycarbonate, and polyethylene as described above. It can be desirable to make the first member **262** out of a PCR-compatible material. The second member **264** is provided as a substantially flat plate that is attached to the first member **262** to complete the formation of the features of the sample chambers and flow paths. The second member **264** can be made out of any suitable material such as a metal foil. Alternatively, the second member could be made out of any of the polymers suitable for use in the first member. The metal foil is particularly suitable because it enhances the heat transfer to the sample chambers from a sample block (not shown) that is typically positioned under the microcard. The foil backing promotes the heating of the sample **S** to be tested to a desired temperature. The first and second members are typically adhered to each other in order to create the requisite seal for the sample chambers.

[0084] According to various embodiments, as shown in **FIG. 11B**, the first member **262** includes a plurality of raised portions **268** that each define a lens **270** for light to pass through and focus on a region within the sample **S** to be tested. The lenses **270** are similar to those described above. In the embodiment shown, the lens **270** includes a projection **274** that extends downward into the sample to be tested. The projection is defined by an angled surface **276** and a flat bottom surface **278**. The projection is preferably sized so that the bottom surface contacts the sample to be tested, as shown for example in **FIG. 11B**. According to various embodiments, the condensation cannot form on the bottom surface of the lens, because there is no air present.

[0085] According to various embodiments, the microcard can be positioned on a sample block for thermally cycling the biological material in the sample chambers. The sample block can be operatively connected to a temperature control unit programmed to raise and lower the temperature of the sample block according to a user defined profile. According to various embodiments, the user can supply data defining time and temperature parameters of the desired PCR protocol to a control computer that causes a central processing unit (CPU) of the temperature control unit to control thermal cycling of the sample block. Several non-limiting examples of suitable temperature control units for raising and lowering the temperature of a sample block for a microcard or other sample-holding member or other sample-holding member are described in U.S. Pat. No. 5,656,493 to Mullis et al. and U.S. Pat. No. 5,475,610 to Atwood et al., incorporated herein above. Any suitable optical detection device can also be used.

[0086] According to various embodiments, as shown in **FIG. 11C**, the microcard **250** can be oriented vertically. The microcard **250** is identical to the microcard shown in **FIG. 11B**. The lens **270** includes the projection that extends into the sample chamber to contact the sample **S** to be tested. This reduces the possibility of condensation on the lens **270**. As shown in **FIG. 11C**, in the case of a vertically oriented sample card, it is preferable that the sample be of sufficient volume so that the flat surface **278** of the projection **274** is immersed in liquid. No condensation can form on the inside of the sample chamber at the flat surface **278** because it is immersed in sample **S**.

[0087] According to various embodiments, an apparatus including a plurality of sample well strips is provided. In various embodiments, a plurality of sample wells are defined by side walls and bottoms. The sample well strips further comprise a plurality of bottom stacking projections, each bottom stacking projection extending downward from a sample well bottom, the bottom stacking projection configured to cap another sample well in another sample well strip. The side walls can comprise a plurality of well lenses for focusing light into the 4 sample well and collecting light emitted by the sample.

[0088] According to various embodiments, as shown in **FIGS. 12-14**, an apparatus **300** with a plurality of sample well strips **310**, **310'**, and **310''** is provided. **FIG. 12** shows three rows of sample well strips (denoted as **310**, **31'**, and **310''**) stacked on top of each other, with a first row of sample well strips **310** on the bottom, a second row of sample well strips **310'** in the middle, and a third row of sample well strips **310''** on the top thereof. For purposes of ease of discussion, the strips will generally be referred to by reference number **310**, but will be referred to as **310**, **310'**, and **310''** when necessary. It should be understood that although only three rows of sample well strips are shown in **FIGS. 12-13**, any suitable number of rows can be provided in accordance with the present teachings.

[0089] According to various embodiments, each of the sample well strips can comprise a plurality of sample wells **320** defined by side walls **322** and bottom surfaces **324**. The strips can contain any number of sample wells. In one embodiment, each strip includes 20 wells. Other sample well strips can include anywhere from two to several hundred wells. In one embodiment, the sample wells **320** have a volume of approximately 5  $\mu$ l, however, the size of the sample wells can vary from 0.001  $\mu$ l to thousands of microliters ( $\mu$ l). In one embodiment, 48 sample well strips can be stacked, each sample well strip containing 20 wells, for a total of 960 wells. It should be understood that any number and size of sample well strips can be envisioned with the present teachings.

[0090] According to various embodiments, the side walls **332** of the sample wells **320** can be any suitable shape. According to various embodiments, as shown in **FIGS. 12-14**, the side walls are generally rectangular in shape, however, it is understood that the side walls can be any other shape, such as cylindrical. The side walls **332** define a top sample well opening **348** that is generally rectangular. The top surface **330** of the side walls **332** is generally flat in the example shown in **FIGS. 12-14**.

[0091] According to various embodiments, the sample well strips can further comprise a plurality of bottom stack-

ing projections extending downward from a sample well bottom. As shown in **FIGS. 12 and 13**, a bottom stacking projection **328** extends downward from each of the sample well bottom surfaces **324**. The bottom stacking projections **328** shown % in **FIGS. 12 and 13** are shaped to be generally rectangular in order to mate with a top sample well opening **348** of an adjacent sample well strip. According to various embodiments, there is a close interference fit between the outer surface **326** of the bottom stacking projections **328** and the inner surface **332** of the sample wells **320**. According to various embodiments, the plurality of sample well strips have a snap-fit connection so that the sample well strips are securely fastened together. This close mating enhances the sealing inside of the sample wells **320**. According to various embodiments, the open recess or well interior can be cylindrical to provide a maximum volume to surface area ratio.

[0092] According to various embodiments, as shown in **FIGS. 12-14**, the bottom stacking projection **328** includes an open recess **334**. Open recess **334** provides a head space such that side walls **322** are completely in fluid contact with biological sample. The sample well bottom surfaces **324** further define a bottom recess **344** around the bottom stacking projections **328**. The bottom recess **344** is a flat surface positioned between the bottom stacking projections **328**. When the sample well strips **310** are stacked, the top surface **330** of the side walls **322** engages the flat surface on the bottom recess **344**. As discussed previously, the bottom stacking projections **328** can be sized so that there is an interference fit in each of the sample wells when stacked. When stacked, the engagement of the top surface **330** of the side walls **322** with the bottom recess **344** further promotes sealing of the sample wells **320**.

[0093] According to various embodiments, the sample well strips can include a plurality of lenses positioned in the side walls of the sample well strips. As shown in **FIGS. 13 and 14**, at least one lens **340** can be positioned in the side wall of each sample well **320**. In the embodiment shown in **FIGS. 12-14**, the lens is positioned on one of the front side walls, so that an optical detection device can be placed perpendicular to a front surface **342** of the plurality of lenses. Lenses **340** are similar to those described above.

[0094] According to various embodiments, the side of the sample well strip opposite the side with the lens will be referred to as the rear surface **346**, although it should be understood that terms such as “front” and “rear” are simply being used for purposes of more easily describing the teachings, and do not limit the scope of the teachings. The sample well strips include a rear surface **346**. Since the optical detection is occurring through the front surface **342**, in some embodiments, a heating member (not shown) such as a sample block can be positioned against the rear surface **346**. This can assist in providing uniform temperatures for each of the sample wells.

[0095] According to various embodiments, the sample well strips can be stacked vertically or horizontally. **FIGS. 12-14** illustrate an embodiment in which the strips are stacked vertically, therefore the stacking operation will be described for this embodiment. First, a predetermined amount of sample to be tested is inserted into the sample wells of a first sample well strip **310** by any known method, such as, for example, pipetting. Next, a second sample well strip **310'** is placed above the first sample well strip **310**. The

second sample well strip can already be loaded with sample, or can not be loaded with sample yet. The bottom stacking projections **328** of the second sample well strip **310'** are then aligned with the top openings **348** of the sample wells of the first sample well strip **310**, and inserted therein. The bottom stacking projections **328** of the second sample well strip **310'** should preferably snap fit or have a close interference fit with the openings of the sample wells of the first sample well strip. If the second sample well strip has not been filled with liquid sample, it can be filled with sample at this time. This process can be repeated for all of the remaining strips. It should be noted that, in the embodiment shown in **FIGS. 12-14**, the top or third sample well strip **310'** will not typically be loaded with sample, but will instead be used as a cap for the second sample well strip **310'**. In alternative embodiments, the third sample well strip **310''** can be loaded with sample.

[0096] According to various embodiments, the sample well strips can be stacked to provide excitation light from a light source that is substantially orthogonal from the light emitted by the sample. According to various embodiments, as shown in **FIG. 17**, excitation light **24a** passes to the sample well strips **310** and **310'**. Lenses **340** can collect emitted light **24b** from the sample and transmit the collected light to a detector (not shown). Excitation light **24a** and emitted light **24b** can be substantially orthogonal. According to various embodiments, sample well strips **310** and **310'** can comprise lenses to focus excitation light **24a** into a region of the sample. Lenses **340** can collect emitted light **24b** from the sample and transmit the collected light to a detector.

[0097] According to various embodiments, the sample well tray can be used in a device that performs fluorescence detection. Fluorescence detection is known in the art for many applications including nucleic acids other than PCR, proteins, and cells. Fluorescent detection systems are known in the art, as also described in greater detail in, for example, U.S. Pat. No. 6,130,745 to Manian et al., incorporated herein. According to various embodiments, fluorescence detection can provide high sensitivity to detect low levels of fluorescence. According to various embodiments, fluorescence detection can provide multiplexing to detect multiple excitation and emission wavelengths in a sample.

[0098] According to various embodiments, the well lens can be positioned at the bottom of the sample wells to focus light coming into the sample well from below the sample well tray and to collect light emitted by the sample. According to various embodiments, **FIG. 15A** illustrates a sample well **12** comprising a flat window **410**. Window **410** is a flat surface and does not focus the light **24** emitted from the sample. According to various embodiments, **FIG. 15B** illustrates a sample well **12** comprising a well lens **420** for collecting light **24** emitted from sample **S**. Well lens **420** can focus excitation light **24** from a light source (not shown) into a region of the sample **S**. Well lens **420** can be a plano-convex lens. The lens radius can be chosen so that the center of curvature lies on the piano surface making the well lens aplanatic and increasing the numerical aperture of the well lens by a factor related to the index of refraction of the well lens material without introducing substantial spherical aberration, coma, or astigmatism. According to various embodiments, the apparatus can comprise an objective lens. The distance between the sample well tray and the objective lens can be decreased to compensate for the well lens. According

to various embodiments, the apparatus can comprise a beam expander. A beam expander can be used with the well lens to provide substantially similar focus spot size of light as the flat window. According to various embodiments, the sides **400** of the sample well can be constructed of a dark material to reduce emitted light from escaping through sides **400**. According to various embodiments, the well lens can be a Fresnel lens, or other lens known in the art of optics for focusing and collecting light. According to various embodiments, as illustrated in **FIG. 16**, well lens **420** can be positioned at other locations on the sample well **12**, such as sides **400**.

[0099] According to various embodiments, the present teachings for sample wells receiving excitation light from above, sample well strips, and/or sample wells receiving excitation light from below can be combined. As shown in **FIG. 18**, sample well **12** can receive excitation light **24a** from a light source (not shown) through cap **70** comprising a Fresnel well lens **72** integrated into the top surface **74** of cap **70**. Well lens **72** can focus excitation light **24a** into a region of sample **S**. Sample well **12** can comprise concave well lens **420** on its side. Well lens **420** can collect emitted light **24b** from sample **S** in a direction substantially orthogonal to the direction of excitation light **24a**. According to various embodiments, other combinations will be apparent to one skilled in the art.

[0100] It will be apparent to those skilled in the art that various modifications and variations can be made to the structure and methods described above. Thus, it should be understood that the present teachings are not limited to the examples discussed in the specification. Rather, the present teachings are intended to cover modifications and variations.

What is claimed is:

1. A cover for a biological sample well tray, comprising:
  - a cap for sealing a sample well, wherein said cap comprises a well lens for focusing light into the sample well and collecting light emitted by the sample.
2. The cover of claim 1, wherein the well lens is a convex lens.
3. The cover of claim 1, wherein the well lens is a Fresnel lens.
4. The cover of claim 1, wherein the cap further comprises a cylindrical sealing member configured to engage an inner surface of the sample well.
5. The cover of claim 1, wherein the cap further comprises an elongate portion.
6. The cover of claim 5, wherein the elongate portion is substantially cylindrical.
7. The cover of claim 5, wherein the elongate portion is solid or hollow.
8. The cover of claim 7, wherein the well lens is positioned in the elongate portion.
9. The cover of claim 8, wherein the elongate portion is hollow.
10. The cover of claim 9, wherein the well lens is positioned on the bottom surface of the hollow elongate portion.
11. The cover of claim 7, wherein the well lens comprises a curved lens extending into the biological sample.
12. A cover for a biological sample well tray, comprising:
  - a cap for sealing a sample well, wherein said cap comprises an elongate portion, the elongate portion config-

ured to permit incoming light to pass into the sample well and out of the sample well.

13. The cover of claim 12, wherein the elongate portion is solid or hollow.

14. The cover of claim 13, further comprising a well lens positioned adjacent to the cap for focusing light into the sample well and transmitting light out of the sample well.

15. The cover of claim 13, further comprising a well lens positioned in the cap for focusing light into the sample well and transmitting light out of the sample well.

16. The cover of claim 15, wherein the elongate portion is hollow.

17. The cover of claim 16, wherein the well lens is positioned on the bottom surface of the hollow elongate portion.

18. The cover of claim 15, wherein the elongate portion is substantially cylindrical and the well lens comprises a curved lens extending into the biological sample.

19. A microcard for biological material, comprising:

a first member; and

a second member defining a plurality of sample chambers between the first member and the second member, the second member comprising a plurality of well lenses corresponding to the plurality of sample chambers, wherein the well lenses are in fluid contact with a sample of biological material in the sample chamber and wherein the well lenses focus light into the sample chamber and collect light emitted by the sample.

20. The microcard of claim 19, wherein the well lens comprises a round lens.

21. The microcard of claim 19, wherein the well lens further comprises a flat bottom surface.

22. The microcard of claim 21, wherein the well lens further comprises angled projections to the flat bottom surface.

23. The microcard of claim 19, wherein the first member is a generally flat plate.

24. The microcard of claim 23, wherein the first member is metallic.

25. The microcard of claim 19, wherein the first member is polypropylene.

26. The microcard of claim 19, wherein the plurality of sample chambers are positioned in a matrix.

27. An apparatus for holding samples of biological material, comprising:

a plurality of sample well strips, each sample well strip comprising:

a plurality of sample wells defined by side walls and bottoms; and

a plurality of bottom stacking projections, each bottom stacking projection extending downward from a sample well bottom, the bottom stacking projection configured to cap another sample well in another sample well strip,

wherein said side walls comprise a plurality of well lenses for focusing light into the sample well and transmitting light out of the sample well.

28. The apparatus of claim 27, wherein the plurality of lens in the side walls of the sample strip are molded into the side walls of the sample well strips.

29. The apparatus of claim 27, wherein the sample well strips are configured to be stacked vertically with the well lenses in fluid contact with the biological sample.

30. A method for testing a biological sample, comprising:

providing a sample well or sample chamber containing said biological sample;

providing a cap for said sample well, wherein said cap comprises a well lens;

focusing light into said sample well; and

collecting light from said sample.

31. The method of claim 30, wherein said focusing light comprises directing light from a light source to said biological sample.

32. The method of claim 30, wherein said collecting light comprises directing light from said biological sample to a detector.

33. The method of claim 32, wherein said light directed from said biological sample comprises fluorescence.

34. The method of claim 32, wherein said light directed from said biological sample comprises at least one of scattering, chemiluminescence, phosphorescence, and Raman scattering.

35. An apparatus for holding samples of biological material, comprising:

a plurality of conical sample wells, wherein each sample well comprises a well lens for focusing light into the

sample and collecting light emitted from the sample, wherein each conical sample well has a circular opening and a angled closure, and wherein the well lens forms the angled closure of each conical sample well.

36. An apparatus for holding samples of biological material, comprising:

A plurality of sample wells, wherein each sample well comprises a well lens for focusing light into the sample and collecting light emitted from the sample, wherein the well lens provides a bottom for the sample well, and wherein the well lens is a Fresnel lens.

37. A system for analyzing samples of biological material, comprising:

a plurality of sample wells, wherein each sample well comprises a well lens for focusing light into the sample and collecting light emitted from the sample, and wherein the well lens provides a bottom for the sample well;

a light source for providing excitation light to the sample wells; and

a detector, wherein said detector provides a surface area to detect the collected light from each sample well, wherein the surface area comprises regions corresponding to each sample well.

\* \* \* \* \*