



US009469030B2

(12) **United States Patent**
Wang et al.

(10) **Patent No.:** **US 9,469,030 B2**
(45) **Date of Patent:** ***Oct. 18, 2016**

(54) **INTERFACING WITH A MOBILE TELEPRESENCE ROBOT**

Related U.S. Application Data

(71) Applicants: **IROBOT CORPORATION**, Bedford, MA (US); **INTOUCH TECHNOLOGIES, INC.**, Goleta, CA (US)

(60) Continuation of application No. 14/799,450, filed on Jul. 14, 2015, now Pat. No. 9,168,656, which is a continuation of application No. 14/221,827, filed on Mar. 21, 2014, now Pat. No. 9,079,311, which is a division of application No. 13/360,579, filed on Jan. 27, 2012, now Pat. No. 8,718,837.

(72) Inventors: **Yulun Wang**, Goleta, CA (US); **Charles S. Jordan**, Santa Barbara, CA (US); **Tim Wright**, Santa Barbara, CA (US); **Michael Chan**, Santa Barbara, CA (US); **Marco Pinter**, Santa Barbara, CA (US); **Kevin Hanrahan**, Santa Barbara, CA (US); **Daniel Sanchez**, Summerland, CA (US); **James Ballantyne**, Santa Barbara, CA (US); **Cody Herzog**, Santa Barbara, CA (US); **Blair Whitney**, Santa Barbara, CA (US); **Fuji Lai**, Goleta, CA (US); **Kelton Temby**, Goleta, CA (US); **Eben Christopher Rauhut**, Watertown, MA (US); **Justin H. Kearns**, Los Angeles, CA (US); **Cheuk Wah Wong**, Bedford, MA (US); **Timothy Sturtevant Farlow**, Billerica, MA (US)

(60) Provisional application No. 61/437,433, filed on Jan. 28, 2011.

(51) **Int. Cl.**

B25J 9/16 (2006.01)
B25J 11/00 (2006.01)
G05D 1/00 (2006.01)
G05D 1/02 (2006.01)
G06F 19/00 (2011.01)
G06T 11/00 (2006.01)
B25J 5/00 (2006.01)
G06F 3/0482 (2013.01)
G06F 3/0484 (2013.01)
G06T 11/60 (2006.01)
G06T 15/10 (2011.01)

(52) **U.S. Cl.**

CPC **B25J 9/1664** (2013.01); **B25J 5/00** (2013.01); **B25J 9/1689** (2013.01); **B25J 9/1697** (2013.01); **B25J 11/009** (2013.01); **B25J 11/0095** (2013.01); **G05D 1/0038** (2013.01); **G05D 1/024** (2013.01); **G05D 1/0274** (2013.01); **G06F 3/0482** (2013.01); **G06F 3/04847** (2013.01); **G06F 19/3418** (2013.01); **G06T 11/00** (2013.01); **G06T 11/60** (2013.01); **G06T 15/10** (2013.01); **G05D 2201/0206** (2013.01); **G06T 2200/24** (2013.01); **Y10S 901/01** (2013.01); **Y10S 901/47** (2013.01)

(73) Assignees: **INTOUCH TECHNOLOGIES**, Goleta, CA (US); **IROBOT CORPORATION**, Bedford, MA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/924,471**

(58) **Field of Classification Search**


CPC .. **B25J 9/1697**; **B25J 11/009**; **B25J 11/0095**; **G05D 1/0038**; **G05D 1/024**; **G05D 1/0274**; **G05D 2201/0206**; **G06F 19/3418**; **G06T 11/00**; **Y10S 901/01**; **Y10S 901/47**

(22) Filed: **Oct. 27, 2015**

See application file for complete search history.

(65) **Prior Publication Data**

US 2016/0046021 A1 Feb. 18, 2016



(56)

References Cited

U.S. PATENT DOCUMENTS

3,821,995 A	7/1974	Aghnides	5,544,649 A	8/1996	David et al.
4,107,689 A	8/1978	Jellinek	5,550,577 A	8/1996	Verbiest et al.
4,213,182 A	7/1980	Eichelberger et al.	5,553,609 A	9/1996	Chen et al.
4,413,693 A	11/1983	Derby	5,563,998 A	10/1996	Yaksich et al.
4,471,354 A	9/1984	Smith	5,572,229 A	11/1996	Fisher
4,519,466 A	5/1985	Shiraishi	5,572,999 A	11/1996	Funda et al.
4,553,309 A	11/1985	Hess et al.	5,594,859 A	1/1997	Palmer et al.
4,572,594 A	2/1986	Schwartz	5,600,573 A	2/1997	Hendricks et al.
4,625,274 A	11/1986	Schroeder	5,617,539 A	4/1997	Ludwig et al.
4,638,445 A	1/1987	Mattaboni	5,619,341 A	4/1997	Auyeung et al.
4,652,204 A	3/1987	Arnett	5,623,679 A	4/1997	Rivette et al.
4,669,168 A	6/1987	Tamura et al.	5,630,566 A	5/1997	Case
4,679,152 A	7/1987	Perdue	5,636,218 A	6/1997	Ishikawa et al.
4,697,278 A	9/1987	Fleischer	5,652,849 A	7/1997	Conway et al.
4,697,472 A	10/1987	Hiyane	5,657,246 A	8/1997	Hogan et al.
4,709,265 A	11/1987	Silverman et al.	5,659,779 A	8/1997	Laird et al.
4,733,737 A	3/1988	Falamak	5,673,082 A	9/1997	Wells et al.
4,751,658 A	6/1988	Kadonoff et al.	5,675,229 A	10/1997	Thorne
4,766,581 A	8/1988	Korn et al.	5,682,199 A	10/1997	Lankford
4,777,416 A	10/1988	George et al.	5,684,695 A	11/1997	Bauer
4,797,557 A	1/1989	Ohman	5,701,904 A	12/1997	Simmons et al.
4,803,625 A	2/1989	Fu et al.	5,734,804 A	3/1998	Bergner
4,847,764 A	7/1989	Halvorson	5,734,805 A	3/1998	Isensee et al.
4,875,172 A	10/1989	Kanayama	5,739,657 A	4/1998	Takayama et al.
4,878,501 A	11/1989	Shue	5,748,629 A	5/1998	Caldara et al.
4,942,512 A	7/1990	Kohno	5,749,058 A	5/1998	Hashimoto
4,942,538 A	7/1990	Yuan et al.	5,749,362 A	5/1998	Funda et al.
4,953,159 A	8/1990	Hayden et al.	5,754,631 A	5/1998	Cave
4,974,607 A	12/1990	Miwa	5,758,079 A	5/1998	Ludwig et al.
4,977,971 A	12/1990	Crane et al.	5,762,458 A	6/1998	Wang et al.
5,006,988 A	4/1991	Borenstein et al.	5,764,731 A	6/1998	Yablon
5,040,116 A	8/1991	Evans et al.	5,767,897 A	6/1998	Howell
5,051,906 A	9/1991	Evans et al.	5,786,846 A	7/1998	Hiroaki
5,073,749 A	12/1991	Kanayama	5,787,545 A	8/1998	Colens
5,084,828 A	1/1992	Kaufman et al.	5,793,365 A	8/1998	Tang et al.
5,130,794 A	7/1992	Ritchey	5,801,755 A	9/1998	Echerer
5,148,591 A	9/1992	Pryor	5,802,494 A	9/1998	Kuno
5,153,833 A	10/1992	Gordon et al.	5,836,872 A	11/1998	Kenet et al.
5,155,684 A	10/1992	Burke et al.	5,838,575 A	11/1998	Lion
5,157,491 A	10/1992	Kassatly	5,844,599 A	12/1998	Hildin
5,182,641 A	1/1993	Diner et al.	5,857,534 A	1/1999	Devault et al.
5,186,270 A	2/1993	West	5,867,494 A	2/1999	Krishnaswamy et al.
5,193,143 A	3/1993	Kaemmerer et al.	5,867,653 A	2/1999	Aras et al.
5,217,453 A	6/1993	Wilk	5,871,451 A	2/1999	Unger et al.
5,220,263 A	6/1993	Onishi et al.	5,872,922 A	2/1999	Hogan et al.
5,224,157 A	6/1993	Yamada et al.	5,876,325 A	3/1999	Mizuno et al.
5,230,023 A	7/1993	Nakano	5,911,036 A	6/1999	Wright et al.
5,231,693 A	7/1993	Backes et al.	5,917,958 A	6/1999	Nunally et al.
5,236,432 A	8/1993	Matsen et al.	5,927,423 A	7/1999	Wada et al.
5,262,944 A	11/1993	Weisner et al.	5,949,758 A	9/1999	Kober
5,305,427 A	4/1994	Nagata	5,954,692 A	9/1999	Smith et al.
5,315,287 A	5/1994	Sol	5,959,423 A	9/1999	Nakanishi et al.
5,319,611 A	6/1994	Korba	5,961,446 A	10/1999	Beller et al.
5,341,242 A	8/1994	Gilboa et al.	5,966,130 A	10/1999	Benman, Jr.
5,341,459 A	8/1994	Backes	5,973,724 A	10/1999	Riddle
5,341,854 A	8/1994	Zezulka et al.	5,974,446 A	10/1999	Sonnenreich et al.
5,347,306 A	9/1994	Nitta	5,983,263 A	11/1999	Rothrock et al.
5,347,457 A	9/1994	Tanaka et al.	5,995,119 A	11/1999	Cosatto et al.
5,350,033 A	9/1994	Kraft	5,995,884 A	11/1999	Allen et al.
5,366,896 A	11/1994	Margrey et al.	5,999,977 A	12/1999	Riddle
5,374,879 A	12/1994	Pin et al.	6,006,946 A	12/1999	Williams et al.
5,375,195 A	12/1994	Johnston	6,031,845 A	2/2000	Walding
5,400,068 A	3/1995	Ishida et al.	6,036,812 A	3/2000	Williams et al.
5,417,210 A	5/1995	Funda et al.	6,047,259 A	4/2000	Campbell et al.
5,419,008 A	5/1995	West	6,091,219 A	7/2000	Maruo et al.
5,436,542 A	7/1995	Petelin et al.	6,113,343 A	9/2000	Goldenberg et al.
5,441,042 A	8/1995	Putman	6,133,944 A	10/2000	Braun et al.
5,441,047 A	8/1995	David et al.	6,135,228 A	10/2000	Asada et al.
5,442,728 A	8/1995	Kaufman et al.	6,148,100 A	11/2000	Anderson et al.
5,462,051 A	10/1995	Oka et al.	6,160,582 A	12/2000	Hill
5,486,853 A	1/1996	Baxter et al.	6,170,929 B1	1/2001	Wilson et al.
5,510,832 A	4/1996	Garcia	6,175,779 B1	1/2001	Barrett
5,511,147 A	4/1996	AbdelMalek	6,189,034 B1	2/2001	Riddle
5,528,289 A	6/1996	Cortjens et al.	6,201,984 B1	3/2001	Funda et al.
5,539,741 A	7/1996	Barraclough et al.	6,211,903 B1	4/2001	Bullister
			6,219,587 B1	4/2001	Ahlin et al.
			6,232,735 B1	5/2001	Baba et al.
			6,233,504 B1	5/2001	Das et al.
			6,233,735 B1	5/2001	Ebihara

6,250,928 B1	6/2001	Poggio et al.	6,667,592 B2	12/2003	Jacobs et al.
6,256,556 B1	7/2001	Zenke	6,674,259 B1	1/2004	Norman et al.
6,259,806 B1	7/2001	Green	6,684,129 B2	1/2004	Salisbury et al.
6,259,956 B1	7/2001	Myers et al.	6,691,000 B2	2/2004	Nagai et al.
6,266,162 B1	7/2001	Okamura et al.	6,693,585 B1	2/2004	Macleod
6,266,577 B1	7/2001	Popp et al.	6,710,797 B1	3/2004	Mcnelley et al.
6,289,263 B1	9/2001	Mukherjee	6,724,823 B2	4/2004	Rovati et al.
6,292,713 B1	9/2001	Jouppi et al.	6,728,599 B2	4/2004	Wang et al.
6,292,714 B1	9/2001	Okabayashi	6,763,282 B2	7/2004	Glenn et al.
6,304,050 B1	10/2001	Skaar et al.	6,764,373 B1	7/2004	Osawa et al.
6,314,631 B1	11/2001	Pryor	6,769,771 B2	8/2004	Trumbull
6,317,652 B1	11/2001	Osada	6,781,606 B2	8/2004	Jouppi
6,317,953 B1	11/2001	Pryor	6,784,916 B2	8/2004	Smith
6,321,137 B1	11/2001	De Smet	6,785,589 B2	8/2004	Eggenberger et al.
6,324,184 B1	11/2001	Hou et al.	6,791,550 B2	9/2004	Goldhor et al.
6,324,443 B1	11/2001	Kurakake et al.	6,798,753 B1	9/2004	Doganata et al.
6,325,756 B1	12/2001	Webb et al.	6,799,065 B1	9/2004	Niemeyer
6,327,516 B1	12/2001	Zenke	6,799,088 B2	9/2004	Wang et al.
6,330,486 B1	12/2001	Padula	6,804,580 B1	10/2004	Stoddard et al.
6,330,493 B1	12/2001	Takahashi et al.	6,804,656 B1	10/2004	Rosenfeld et al.
6,346,950 B1	2/2002	Jouppi	6,810,411 B1	10/2004	Coughlin et al.
6,346,962 B1	2/2002	Goodridge	6,816,192 B1	11/2004	Nishikawa
6,369,847 B1	4/2002	James et al.	6,816,754 B2	11/2004	Mukai et al.
6,373,855 B1	4/2002	Downing et al.	6,836,703 B2	12/2004	Wang et al.
6,381,515 B1	4/2002	Inoue et al.	6,839,612 B2	1/2005	Sanchez et al.
6,389,329 B1	5/2002	Colens	6,840,904 B2	1/2005	Goldberg
6,400,378 B1	6/2002	Snook	6,845,297 B2	1/2005	Allard
6,408,230 B2	6/2002	Wada	6,852,107 B2	2/2005	Wang et al.
6,411,055 B1	6/2002	Fujita et al.	6,853,878 B2	2/2005	Hirayama et al.
6,430,471 B1	8/2002	Kintou et al.	6,853,880 B2	2/2005	Sakagami et al.
6,430,475 B2	8/2002	Okamoto et al.	6,871,117 B2	3/2005	Wang et al.
6,438,457 B1	8/2002	Yokoo et al.	6,879,879 B2	4/2005	Jouppi et al.
6,445,964 B1	9/2002	White et al.	6,888,333 B2	5/2005	Laby
6,449,762 B1	9/2002	Mcelvain	6,892,112 B2	5/2005	Wang et al.
6,452,915 B1	9/2002	Jorgensen	6,893,267 B1	5/2005	Yueh
6,457,043 B1	9/2002	Kwak et al.	6,895,305 B2	5/2005	Lathan et al.
6,459,955 B1	10/2002	Bartsch et al.	6,898,484 B2	5/2005	Lemelson et al.
6,463,352 B1	10/2002	Tadokoro et al.	6,914,622 B1	7/2005	Smith et al.
6,463,361 B1	10/2002	Wang et al.	6,925,357 B2	8/2005	Wang et al.
6,466,844 B1	10/2002	Ikeda et al.	6,951,535 B2	10/2005	Ghodoussi et al.
6,468,265 B1	10/2002	Evans et al.	6,952,470 B1	10/2005	Tioe et al.
6,470,235 B2	10/2002	Kasuga et al.	6,957,712 B2	10/2005	Song et al.
6,474,434 B1	11/2002	Bech	6,958,706 B2	10/2005	Chaco et al.
6,480,762 B1	11/2002	Uchikubo et al.	6,965,394 B2	11/2005	Gutta et al.
6,491,701 B2	12/2002	Tierney et al.	6,990,112 B1	1/2006	Brent et al.
6,496,099 B2	12/2002	Wang et al.	6,995,664 B1	2/2006	Darling
6,496,755 B2	12/2002	Wallach et al.	7,007,235 B1	2/2006	Hussein et al.
6,501,740 B1	12/2002	Sun et al.	7,011,538 B2	3/2006	Chang
6,507,773 B2	1/2003	Parker et al.	7,015,934 B2	3/2006	Toyama et al.
6,522,906 B1	2/2003	Salisbury et al.	RE39,080 E	4/2006	Johnston
6,523,629 B1	2/2003	Buttz et al.	7,030,757 B2	4/2006	Matsuhira et al.
6,526,332 B2	2/2003	Sakamoto et al.	7,053,578 B2	5/2006	Diehl et al.
6,529,620 B2	3/2003	Thompson	7,055,210 B2	6/2006	Keppler et al.
6,529,765 B1	3/2003	Franck et al.	7,058,689 B2	6/2006	Parker et al.
6,529,802 B1	3/2003	Kawakita et al.	7,092,001 B2	8/2006	Schulz
6,532,404 B2	3/2003	Colens	7,096,090 B1	8/2006	Zweig
6,535,182 B2	3/2003	Stanton	7,115,102 B2	10/2006	Abbruscato
6,535,793 B2*	3/2003	Allard 700/259	7,117,067 B2	10/2006	Mclurkin et al.
6,540,039 B1	4/2003	Yu et al.	7,123,285 B2	10/2006	Smith et al.
6,543,899 B2	4/2003	Covannon et al.	7,123,974 B1	10/2006	Hamilton
6,549,215 B2	4/2003	Jouppi	7,123,991 B2	10/2006	Graf et al.
6,563,533 B1	5/2003	Colby	7,127,325 B2	10/2006	Nagata et al.
6,567,038 B1	5/2003	Granot et al.	7,129,970 B2	10/2006	James et al.
6,580,246 B2	6/2003	Jacobs	7,133,062 B2	11/2006	Castles et al.
6,581,798 B2	6/2003	Liff et al.	7,142,945 B2	11/2006	Wang et al.
6,584,376 B1	6/2003	Van Kommer	7,142,947 B2	11/2006	Wang et al.
6,587,750 B2	7/2003	Gerbi et al.	7,151,982 B2	12/2006	Liff et al.
6,590,604 B1	7/2003	Tucker et al.	7,154,526 B2	12/2006	Foote et al.
6,594,269 B1	7/2003	Polcyn	7,155,306 B2	12/2006	Haitin et al.
6,594,552 B1	7/2003	Nowlin et al.	7,156,809 B2	1/2007	Quy
6,597,392 B1	7/2003	Jenkins et al.	7,158,859 B2	1/2007	Wang et al.
6,602,469 B1	8/2003	Maus et al.	7,158,860 B2	1/2007	Wang et al.
6,604,019 B2	8/2003	Ahlin et al.	7,158,861 B2	1/2007	Wang et al.
6,604,021 B2	8/2003	Imai et al.	7,161,322 B2	1/2007	Wang et al.
6,611,120 B2	8/2003	Song et al.	7,162,338 B2	1/2007	Goncalves et al.
6,643,496 B1	11/2003	Shimoyama et al.	7,164,969 B2	1/2007	Wang et al.
6,646,677 B2	11/2003	Noro et al.	7,164,970 B2	1/2007	Wang et al.
6,650,748 B1	11/2003	Edwards et al.	7,167,448 B2	1/2007	Wookey et al.
6,666,374 B1	12/2003	Green et al.	7,171,286 B2	1/2007	Wang et al.

7,174,238 B1	2/2007	Zweig	7,982,763 B2	7/2011	King
7,181,455 B2	2/2007	Wookey et al.	7,982,769 B2	7/2011	Jenkins et al.
7,184,559 B2	2/2007	Jouppi	7,987,069 B2	7/2011	Rodgers et al.
7,188,000 B2	3/2007	Chiappetta et al.	8,077,963 B2	12/2011	Wang et al.
7,199,790 B2	4/2007	Rosenberg et al.	8,116,910 B2	2/2012	Walters et al.
7,202,851 B2	4/2007	Cunningham et al.	8,126,960 B2	2/2012	Obradovich et al.
7,206,627 B2	4/2007	Abovitz et al.	8,170,241 B2	5/2012	Roe et al.
7,215,786 B2	5/2007	Nakadai et al.	8,179,418 B2	5/2012	Wright et al.
7,219,364 B2	5/2007	Bolle et al.	8,180,486 B2	5/2012	Saito et al.
7,222,000 B2	5/2007	Wang et al.	8,209,051 B2	6/2012	Wang et al.
7,227,334 B2	6/2007	Yang et al.	8,212,533 B2	7/2012	Ota
7,256,708 B2	8/2007	Rosenfeld et al.	8,265,793 B2	9/2012	Cross et al.
7,262,573 B2	8/2007	Wang et al.	8,287,522 B2	10/2012	Moses et al.
7,283,153 B2	10/2007	Provost et al.	8,292,807 B2	10/2012	Perkins et al.
7,289,883 B2	10/2007	Wang et al.	8,320,534 B2	11/2012	Kim et al.
7,292,257 B2	11/2007	Kang et al.	8,340,654 B2	12/2012	Bratton et al.
7,292,912 B2	11/2007	Wang et al.	8,340,819 B2	12/2012	Mangaser et al.
7,305,114 B2	12/2007	Wolff et al.	8,348,675 B2	1/2013	Dohrmann
7,317,685 B1	1/2008	Flott et al.	8,374,171 B2	2/2013	Cho et al.
7,321,807 B2	1/2008	Laski	8,400,491 B1	3/2013	Panpaliya et al.
7,332,890 B2	2/2008	Cohen et al.	8,401,275 B2	3/2013	Wang et al.
7,333,642 B2	2/2008	Green	8,423,284 B2	4/2013	O'Shea
7,346,429 B2	3/2008	Goldenberg et al.	8,451,731 B1	5/2013	Lee et al.
7,352,153 B2	4/2008	Yan	8,463,435 B2	6/2013	Herzog et al.
7,363,121 B1	4/2008	Chen et al.	8,503,340 B1	8/2013	Xu
7,382,399 B1	6/2008	Mccall et al.	8,515,577 B2	8/2013	Wang et al.
7,386,730 B2	6/2008	Uchikubo	8,527,094 B2	9/2013	Kumar et al.
7,391,432 B2	6/2008	Terada	8,531,502 B2	9/2013	Cheng et al.
7,400,578 B2	7/2008	Guthrie et al.	8,532,860 B2	9/2013	Daly
7,404,140 B2	7/2008	O'Rourke	8,610,786 B2	12/2013	Ortiz
7,421,470 B2	9/2008	Ludwig et al.	8,612,051 B2	12/2013	Norman et al.
7,430,209 B2	9/2008	Porter	8,639,797 B1	1/2014	Pan et al.
7,432,949 B2	10/2008	Remy et al.	8,670,017 B2	3/2014	Stuart et al.
7,433,921 B2	10/2008	Ludwig et al.	8,718,837 B2	5/2014	Yulun Wang
7,441,953 B2	10/2008	Banks	8,726,454 B2	5/2014	Gilbert, Jr. et al.
7,467,211 B1	12/2008	Herman et al.	8,836,751 B2	9/2014	Ballantyne et al.
7,483,867 B2	1/2009	Ansari et al.	8,849,679 B2	9/2014	Wang et al.
7,492,731 B2	2/2009	Hagendorf	8,849,680 B2	9/2014	Wright et al.
7,510,428 B2	3/2009	Obata et al.	8,861,750 B2	10/2014	Roe et al.
7,523,069 B1	4/2009	Friedl et al.	8,897,920 B2	11/2014	Wang et al.
7,525,281 B2	4/2009	Koyanagi et al.	8,902,278 B2	12/2014	Pinter et al.
7,535,486 B2	5/2009	Motomura et al.	8,965,579 B2	2/2015	Wang et al.
7,557,758 B2	7/2009	Rofougaran	9,098,611 B2	8/2015	Pinter et al.
7,587,260 B2	9/2009	Bruemmer et al.	9,147,284 B2	9/2015	Keene et al.
7,587,512 B2	9/2009	Ta et al.	2001/0002448 A1	5/2001	Wilson et al.
7,590,060 B2	9/2009	Miceli	2001/0010053 A1	7/2001	Ben-Shachar et al.
7,593,030 B2	9/2009	Wang et al.	2001/0020200 A1	9/2001	Das et al.
7,599,290 B2	10/2009	Dos Remedios et al.	2001/0034475 A1	10/2001	Flach et al.
7,624,166 B2	11/2009	Foote et al.	2001/0034544 A1	10/2001	Mo
7,630,314 B2	12/2009	Dos Remedios et al.	2001/0037163 A1	11/2001	Allard
7,631,833 B1	12/2009	Ghaleb et al.	2001/0048464 A1	12/2001	Barnett
7,643,051 B2	1/2010	Sandberg et al.	2001/0051881 A1	12/2001	Filler
7,647,320 B2	1/2010	Mok et al.	2001/0054071 A1	12/2001	Loeb
7,657,560 B1	2/2010	Dirienzo	2001/0055373 A1	12/2001	Yamashita
7,680,038 B1	3/2010	Gourlay	2002/0015296 A1	2/2002	Howell et al.
7,693,757 B2	4/2010	Zimmerman	2002/0027597 A1	3/2002	Sachau
7,698,432 B2	4/2010	Short et al.	2002/0027652 A1	3/2002	Paromtchik et al.
7,703,113 B2	4/2010	Dawson	2002/0033880 A1	3/2002	Sul et al.
7,719,229 B2	5/2010	Kaneko et al.	2002/0038168 A1	3/2002	Kasuga et al.
7,737,993 B2	6/2010	Kaasila et al.	2002/0044201 A1	4/2002	Alexander et al.
7,739,383 B1	6/2010	Short et al.	2002/0049517 A1	4/2002	Ruffner
7,756,614 B2	7/2010	Jouppi	2002/0055917 A1	5/2002	Muraca
7,761,185 B2	7/2010	Wang et al.	2002/0057279 A1	5/2002	Jouppi
7,769,492 B2	8/2010	Wang et al.	2002/0058929 A1	5/2002	Green
7,769,705 B1	8/2010	Luechtefeld	2002/0059587 A1	5/2002	Cofano et al.
7,774,158 B2	8/2010	Domingues Goncalves et al.	2002/0063726 A1	5/2002	Jouppi
7,813,836 B2	10/2010	Wang et al.	2002/0073429 A1	6/2002	Beane et al.
7,831,575 B2	11/2010	Trossell et al.	2002/0082498 A1	6/2002	Wendt et al.
7,835,775 B2	11/2010	Sawayama et al.	2002/0085030 A1	7/2002	Ghani
7,860,680 B2	12/2010	Arms et al.	2002/0095238 A1	7/2002	Ahlin et al.
7,861,366 B2	1/2011	Hahm et al.	2002/0095239 A1	7/2002	Wallach et al.
7,885,822 B2	2/2011	Akers et al.	2002/0098879 A1	7/2002	Rheey
7,890,382 B2	2/2011	Robb et al.	2002/0104094 A1	8/2002	Alexander et al.
7,912,583 B2	3/2011	Gutmann et al.	2002/0106998 A1	8/2002	Presley et al.
RE42,288 E	4/2011	Degioanni	2002/0109770 A1	8/2002	Terada
7,924,323 B2	4/2011	Walker et al.	2002/0109775 A1	8/2002	White et al.
7,949,616 B2	5/2011	Levy et al.	2002/0111988 A1	8/2002	Sato
7,956,894 B2	6/2011	Akers et al.	2002/0120362 A1	8/2002	Lathan et al.
7,957,837 B2	6/2011	Ziegler et al.	2002/0128985 A1	9/2002	Greenwald

2002/0130950	A1	9/2002	James et al.	2004/0168148	A1	8/2004	Goncalves et al.
2002/0133062	A1	9/2002	Arling et al.	2004/0170300	A1	9/2004	Jouppi
2002/0141595	A1	10/2002	Jouppi	2004/0172301	A1	9/2004	Mihai et al.
2002/0143923	A1	10/2002	Alexander	2004/0172306	A1	9/2004	Wohl et al.
2002/0177925	A1	11/2002	Onishi et al.	2004/0174129	A1	9/2004	Wang et al.
2002/0183894	A1	12/2002	Wang et al.	2004/0175684	A1	9/2004	Kaasa et al.
2002/0184674	A1	12/2002	Xi et al.	2004/0179714	A1	9/2004	Jouppi
2002/0186243	A1	12/2002	Ellis et al.	2004/0186623	A1	9/2004	Dooley et al.
2003/0021107	A1	1/2003	Howell et al.	2004/0189700	A1	9/2004	Mandavilli et al.
2003/0030397	A1	2/2003	Simmons	2004/0201602	A1	10/2004	Mody et al.
2003/0048481	A1	3/2003	Kobayashi et al.	2004/0205664	A1	10/2004	Prendergast
2003/0050733	A1	3/2003	Wang et al.	2004/0215490	A1	10/2004	Duchon et al.
2003/0050734	A1	3/2003	Lapham	2004/0218099	A1	11/2004	Washington
2003/0060808	A1	3/2003	Wilk	2004/0222638	A1	11/2004	Bednyak
2003/0063600	A1	4/2003	Noma et al.	2004/0224676	A1	11/2004	Iseki
2003/0069752	A1	4/2003	Ledain et al.	2004/0230340	A1	11/2004	Fukuchi et al.
2003/0080901	A1	5/2003	Piotrowski	2004/0240981	A1	12/2004	Dothan et al.
2003/0100892	A1	5/2003	Morley et al.	2004/0241981	A1	12/2004	Doris et al.
2003/0104806	A1	6/2003	Ruef et al.	2004/0260790	A1	12/2004	Balloni et al.
2003/0112823	A1	6/2003	Collins et al.	2005/0003330	A1	1/2005	Asgarinejad et al.
2003/0114962	A1	6/2003	Niemeyer et al.	2005/0004708	A1	1/2005	Goldenberg et al.
2003/0120714	A1	6/2003	Wolff et al.	2005/0007445	A1	1/2005	Foote et al.
2003/0126361	A1	7/2003	Slater et al.	2005/0013149	A1	1/2005	Trossell
2003/0135097	A1	7/2003	Wiederhold et al.	2005/0021182	A1	1/2005	Wang et al.
2003/0135203	A1	7/2003	Wang et al.	2005/0021183	A1	1/2005	Wang et al.
2003/0144579	A1	7/2003	Buss	2005/0021187	A1	1/2005	Wang et al.
2003/0144649	A1	7/2003	Ghodoussi et al.	2005/0021309	A1	1/2005	Alexander et al.
2003/0151658	A1	8/2003	Smith	2005/0024485	A1	2/2005	Castles et al.
2003/0152145	A1	8/2003	Kawakita	2005/0027567	A1	2/2005	Taha
2003/0171710	A1	9/2003	Bassuk et al.	2005/0027794	A1	2/2005	Decker
2003/0174285	A1	9/2003	Trumbull	2005/0028221	A1	2/2005	Liu et al.
2003/0180697	A1	9/2003	Kim et al.	2005/0035862	A1	2/2005	Wildman et al.
2003/0195662	A1	10/2003	Wang et al.	2005/0038416	A1	2/2005	Wang et al.
2003/0199000	A1	10/2003	Valkirs et al.	2005/0038564	A1	2/2005	Burick
2003/0206242	A1	11/2003	Choi	2005/0049898	A1	3/2005	Hirakawa
2003/0212472	A1	11/2003	Mckee	2005/0052527	A1	3/2005	Remy et al.
2003/0216833	A1	11/2003	Mukai et al.	2005/0060211	A1	3/2005	Xiao et al.
2003/0216834	A1	11/2003	Allard	2005/0065435	A1	3/2005	Rauch et al.
2003/0220541	A1	11/2003	Salisbury et al.	2005/0065438	A1	3/2005	Miller
2003/0220715	A1	11/2003	Kneifel et al.	2005/0065659	A1	3/2005	Tanaka et al.
2003/0231244	A1	12/2003	Bonilla et al.	2005/0065813	A1	3/2005	Mishelevich et al.
2003/0232649	A1	12/2003	Gizis et al.	2005/0071046	A1	3/2005	Miyazaki et al.
2003/0236590	A1	12/2003	Park et al.	2005/0073575	A1	4/2005	Thacher et al.
2004/0001197	A1	1/2004	Ko et al.	2005/0078816	A1	4/2005	Sekiguchi et al.
2004/0001676	A1	1/2004	Colgan et al.	2005/0083011	A1	4/2005	Yang et al.
2004/0008138	A1	1/2004	Hockley, Jr. et al.	2005/0099493	A1	5/2005	Chew
2004/0010344	A1	1/2004	Hiratsuka et al.	2005/0104964	A1	5/2005	Bovyryn et al.
2004/0012362	A1	1/2004	Tsurumi	2005/0110867	A1	5/2005	Schulz
2004/0013295	A1	1/2004	Sabe et al.	2005/0122390	A1	6/2005	Wang et al.
2004/0017475	A1	1/2004	Akers et al.	2005/0125083	A1	6/2005	Kiko
2004/0019406	A1	1/2004	Wang et al.	2005/0125098	A1	6/2005	Wang et al.
2004/0024490	A1	2/2004	Mclurkin et al.	2005/0149364	A1	7/2005	Ombrellaro
2004/0041904	A1	3/2004	Lapalme et al.	2005/0152447	A1	7/2005	Jouppi et al.
2004/0065073	A1	4/2004	Nash	2005/0152565	A1	7/2005	Jouppi et al.
2004/0068657	A1	4/2004	Alexander et al.	2005/0154265	A1	7/2005	Miro et al.
2004/0078219	A1	4/2004	Kaylor et al.	2005/0168568	A1	8/2005	Jouppi
2004/0080610	A1	4/2004	James et al.	2005/0182322	A1	8/2005	Grispo
2004/0088077	A1	5/2004	Jouppi et al.	2005/0192721	A1	9/2005	Jouppi
2004/0088078	A1	5/2004	Jouppi et al.	2005/0204438	A1	9/2005	Wang et al.
2004/0093409	A1	5/2004	Thompson et al.	2005/0212478	A1	9/2005	Takenaka
2004/0095516	A1	5/2004	Rohlicek	2005/0219356	A1	10/2005	Smith et al.
2004/0098167	A1	5/2004	Yi et al.	2005/0225634	A1	10/2005	Brunetti et al.
2004/0102167	A1	5/2004	Shim et al.	2005/0231156	A1	10/2005	Yan
2004/0107254	A1	6/2004	Ludwig et al.	2005/0231586	A1	10/2005	Rodman et al.
2004/0107255	A1	6/2004	Ludwig et al.	2005/0232647	A1	10/2005	Takenaka
2004/0117065	A1	6/2004	Wang et al.	2005/0234592	A1	10/2005	Mcgee et al.
2004/0117067	A1	6/2004	Jouppi	2005/0264649	A1	12/2005	Chang et al.
2004/0123158	A1	6/2004	Roskind	2005/0267826	A1	12/2005	Levy et al.
2004/0135879	A1	7/2004	Stacy et al.	2005/0283414	A1	12/2005	Fernandes et al.
2004/0138547	A1	7/2004	Wang et al.	2005/0286759	A1	12/2005	Zitnick et al.
2004/0140404	A1	7/2004	Ohta et al.	2006/0007943	A1	1/2006	Fellman
2004/0143421	A1	7/2004	Wang et al.	2006/0010028	A1	1/2006	Sorensen
2004/0148638	A1	7/2004	Weisman et al.	2006/0013263	A1	1/2006	Fellman
2004/0150725	A1	8/2004	Taguchi	2006/0013469	A1	1/2006	Wang et al.
2004/0153211	A1	8/2004	Kamoto et al.	2006/0013488	A1	1/2006	Inoue
2004/0157612	A1	8/2004	Kim, II	2006/0014388	A1	1/2006	Lur et al.
2004/0162637	A1	8/2004	Wang et al.	2006/0020694	A1	1/2006	Nag et al.
2004/0167666	A1	8/2004	Wang et al.	2006/0029065	A1	2/2006	Fellman
2004/0167668	A1	8/2004	Wang et al.	2006/0047365	A1	3/2006	Ghodoussi et al.

2006/0048286	A1	3/2006	Donato	2008/0045804	A1	2/2008	Williams
2006/0052676	A1	3/2006	Wang et al.	2008/0051985	A1	2/2008	DAndrea et al.
2006/0052684	A1	3/2006	Takahashi et al.	2008/0056933	A1	3/2008	Moore et al.
2006/0056655	A1	3/2006	Wen et al.	2008/0065268	A1	3/2008	Wang et al.
2006/0056837	A1	3/2006	Vapaakoski	2008/0082211	A1	4/2008	Wang et al.
2006/0064212	A1	3/2006	Thorne	2008/0086241	A1	4/2008	Phillips et al.
2006/0066609	A1	3/2006	Iodice et al.	2008/0091340	A1	4/2008	Milstein et al.
2006/0071797	A1	4/2006	Rosenfeld et al.	2008/0126132	A1	5/2008	Warner et al.
2006/0074525	A1	4/2006	Close et al.	2008/0133052	A1	6/2008	Jones et al.
2006/0074719	A1	4/2006	Horner	2008/0161969	A1	7/2008	Lee et al.
2006/0082642	A1	4/2006	Wang et al.	2008/0174570	A1	7/2008	Jobs et al.
2006/0087746	A1	4/2006	Lipow	2008/0201016	A1	8/2008	Finlay
2006/0095158	A1	5/2006	Lee et al.	2008/0201017	A1	8/2008	Wang et al.
2006/0095170	A1	5/2006	Yang et al.	2008/0215987	A1	9/2008	Alexander et al.
2006/0098573	A1	5/2006	Beer et al.	2008/0229531	A1	9/2008	Takida
2006/0103659	A1	5/2006	Karandikar et al.	2008/0232763	A1	9/2008	Brady
2006/0104279	A1	5/2006	Fellman et al.	2008/0255703	A1	10/2008	Wang et al.
2006/0106493	A1	5/2006	Niemeyer et al.	2008/0263451	A1	10/2008	Portele et al.
2006/0122482	A1	6/2006	Mariotti et al.	2008/0263628	A1	10/2008	Norman et al.
2006/0125356	A1	6/2006	Meek et al.	2008/0267069	A1	10/2008	Thielman et al.
2006/0142983	A1	6/2006	Sorensen et al.	2008/0269949	A1	10/2008	Norman et al.
2006/0149418	A1	7/2006	Anvari	2008/0281467	A1	11/2008	Pinter
2006/0161136	A1	7/2006	Anderson et al.	2008/0285886	A1	11/2008	Allen et al.
2006/0161303	A1	7/2006	Wang et al.	2008/0306375	A1	12/2008	Sayler et al.
2006/0164546	A1	7/2006	Adachi	2009/0021572	A1	1/2009	Garudadri et al.
2006/0171515	A1	8/2006	Hintermeister et al.	2009/0030552	A1	1/2009	Nakadai et al.
2006/0173708	A1	8/2006	Vining et al.	2009/0044334	A1	2/2009	Parsell et al.
2006/0173712	A1	8/2006	Joubert	2009/0049640	A1	2/2009	Lee et al.
2006/0178559	A1	8/2006	Kumar et al.	2009/0055023	A1	2/2009	Walters et al.
2006/0178776	A1	8/2006	Feingold et al.	2009/0070135	A1	3/2009	Parida et al.
2006/0178777	A1	8/2006	Park et al.	2009/0086013	A1	4/2009	Thapa
2006/0184274	A1	8/2006	Sakai et al.	2009/0102919	A1	4/2009	Zamierowski et al.
2006/0189393	A1	8/2006	Edery	2009/0105882	A1	4/2009	Wang et al.
2006/0195569	A1	8/2006	Barker	2009/0106679	A1	4/2009	Anzures et al.
2006/0224781	A1	10/2006	Tsao et al.	2009/0122699	A1	5/2009	Alperovitch et al.
2006/0247045	A1	11/2006	Jeong et al.	2009/0125147	A1	5/2009	Wang et al.
2006/0259193	A1	11/2006	Wang et al.	2009/0144425	A1	6/2009	Marr et al.
2006/0268704	A1	11/2006	Ansari et al.	2009/0146882	A1	6/2009	Halivaara et al.
2006/0271238	A1	11/2006	Choi et al.	2009/0164255	A1	6/2009	Menschik et al.
2006/0271400	A1	11/2006	Clements et al.	2009/0164657	A1	6/2009	Li et al.
2006/0293788	A1	12/2006	Pogodin	2009/0171170	A1	7/2009	Li et al.
2007/0016328	A1	1/2007	Ziegler et al.	2009/0177323	A1	7/2009	Ziegler et al.
2007/0021871	A1	1/2007	Wang et al.	2009/0177641	A1	7/2009	Raghavan
2007/0025711	A1	2/2007	Marcus	2009/0234499	A1	9/2009	Nielsen et al.
2007/0046237	A1	3/2007	Lakshmanan et al.	2009/0237317	A1	9/2009	Rofougaran
2007/0050937	A1	3/2007	Song et al.	2009/0240371	A1	9/2009	Wang et al.
2007/0061041	A1	3/2007	Zweig et al.	2009/0248200	A1	10/2009	Root
2007/0064092	A1	3/2007	Sandbeg et al.	2009/0259339	A1	10/2009	Wright et al.
2007/0078566	A1	4/2007	Wang et al.	2010/0010672	A1	1/2010	Wang et al.
2007/0093279	A1	4/2007	Janik	2010/0010673	A1	1/2010	Wang et al.
2007/0112700	A1	5/2007	Den et al.	2010/0017046	A1	1/2010	Cheung et al.
2007/0116152	A1	5/2007	Thesling	2010/0019715	A1	1/2010	Roe et al.
2007/0117516	A1	5/2007	Saidi et al.	2010/0026239	A1	2/2010	Li et al.
2007/0120965	A1	5/2007	Sandberg et al.	2010/0030578	A1	2/2010	Siddique et al.
2007/0122783	A1	5/2007	Habashi	2010/0051596	A1	3/2010	Diedrick et al.
2007/0133407	A1	6/2007	Choi et al.	2010/0063848	A1	3/2010	Kremer et al.
2007/0135967	A1	6/2007	Jung et al.	2010/0066804	A1	3/2010	Shoemaker et al.
2007/0142964	A1	6/2007	Abramson	2010/0070079	A1	3/2010	Mangaser et al.
2007/0170886	A1	7/2007	Plishner	2010/0073490	A1	3/2010	Wang et al.
2007/0176060	A1	8/2007	White et al.	2010/0076600	A1	3/2010	Cross et al.
2007/0182811	A1	8/2007	Rockefeller et al.	2010/0085874	A1	4/2010	Noy et al.
2007/0192910	A1	8/2007	Vu et al.	2010/0088232	A1	4/2010	Gale
2007/0197896	A1	8/2007	Moll et al.	2010/0115418	A1	5/2010	Wang et al.
2007/0198128	A1	8/2007	Ziegler et al.	2010/0116566	A1	5/2010	Ohm et al.
2007/0198130	A1	8/2007	Wang et al.	2010/0128104	A1	5/2010	Fabregat et al.
2007/0199108	A1	8/2007	Angle et al.	2010/0131103	A1	5/2010	Herzog et al.
2007/0216347	A1	9/2007	Kaneko et al.	2010/0145479	A1	6/2010	Griffiths
2007/0226949	A1	10/2007	Hahm et al.	2010/0157825	A1	6/2010	Anderlind et al.
2007/0250212	A1	10/2007	Halloran et al.	2010/0171826	A1	7/2010	Hamilton et al.
2007/0255706	A1	11/2007	Iketani et al.	2010/0191375	A1	7/2010	Wright et al.
2007/0262884	A1	11/2007	Goncalves et al.	2010/0228249	A1	9/2010	Mohr et al.
2007/0273751	A1	11/2007	Sachau	2010/0268383	A1	10/2010	Wang et al.
2007/0290040	A1	12/2007	Wurman et al.	2010/0278086	A1	11/2010	Pochiraju et al.
2007/0291109	A1	12/2007	Wang et al.	2010/0286905	A1	11/2010	Goncalves et al.
2007/0291128	A1	12/2007	Wang et al.	2010/0301679	A1	12/2010	Murray et al.
2008/0009969	A1	1/2008	Bruemmer et al.	2010/0323783	A1	12/2010	Nonaka et al.
2008/0011904	A1	1/2008	Cepollina et al.	2011/0022705	A1	1/2011	Yellamraju et al.
2008/0027591	A1	1/2008	Lenser et al.	2011/0050841	A1	3/2011	Wang et al.
2008/0033641	A1	2/2008	Medalia	2011/0071675	A1	3/2011	Wells et al.

2011/0071702	A1	3/2011	Wang et al.	EP	1594660	A2	11/2005
2011/0072114	A1	3/2011	Hoffert et al.	EP	1763243	A2	3/2007
2011/0153198	A1	6/2011	Kokkas et al.	EP	1791464	A2	6/2007
2011/0169832	A1	7/2011	Brown et al.	EP	1800476	A2	6/2007
2011/0172822	A1	7/2011	Ziegler et al.	EP	1819108	A2	8/2007
2011/0187875	A1	8/2011	Sanchez et al.	EP	1856644	A2	11/2007
2011/0190930	A1	8/2011	Hanrahan et al.	EP	1536660	A3	4/2008
2011/0193949	A1	8/2011	Nambakam et al.	EP	1928310	A2	6/2008
2011/0195701	A1	8/2011	Cook et al.	EP	1232610	B1	1/2009
2011/0213210	A1	9/2011	Temby et al.	EP	2027716	A2	2/2009
2011/0218674	A1	9/2011	Stuart et al.	EP	2145274	A1	1/2010
2011/0245973	A1	10/2011	Wang et al.	EP	2214111	A2	8/2010
2011/0249079	A1	10/2011	Santamaria et al.	EP	2263158	A2	12/2010
2011/0280551	A1	11/2011	Sammon	EP	2300930	A1	3/2011
2011/0288417	A1	11/2011	Pinter et al.	EP	2342651	A1	7/2011
2011/0292193	A1	12/2011	Wang et al.	GB	2431261	A	4/2007
2011/0301759	A1	12/2011	Wang et al.	JP	7-194609	A	8/1995
2011/0306400	A1	12/2011	Nguyen	JP	7-213753	A	8/1995
2012/0023506	A1	1/2012	Maeckel et al.	JP	7-248823	A	9/1995
2012/0036484	A1	2/2012	Zhang et al.	JP	7-257422	A	10/1995
2012/0059946	A1	3/2012	Wang	JP	8-84328	A	3/1996
2012/0072023	A1	3/2012	Ota	JP	8-166822	A	6/1996
2012/0072024	A1	3/2012	Wang et al.	JP	8-320727	A	12/1996
2012/0092157	A1	4/2012	Tran	JP	9-267276	A	10/1997
2012/0095352	A1	4/2012	Tran	JP	10-79097	A	3/1998
2012/0113856	A1	5/2012	Krishnaswamy	JP	10-288689	A	10/1998
2012/0182392	A1	7/2012	Kearns et al.	JP	11-220706	A	8/1999
2012/0191246	A1	7/2012	Roe et al.	JP	2000-032319	A	1/2000
2012/0191464	A1	7/2012	Stuart et al.	JP	2000-049800	A	2/2000
2012/0203731	A1	8/2012	Nelson et al.	JP	2000-079587	A	3/2000
2012/0215380	A1	8/2012	Fouillade et al.	JP	2000-196876	A	7/2000
2012/0215830	A1	8/2012	Anguiano et al.	JP	2001-125641	A	5/2001
2012/0218374	A1	8/2012	Matula et al.	JP	2001-147718	A	5/2001
2012/0220372	A1	8/2012	Cheung et al.	JP	2001-179663	A	7/2001
2012/0291809	A1	11/2012	Kuhe et al.	JP	2001-188124	A	7/2001
2012/0316676	A1	12/2012	Fouillade et al.	JP	2001-198865	A	7/2001
2013/0158720	A1	6/2013	Zywicki et al.	JP	2001-198868	A	7/2001
2013/0250938	A1	9/2013	Anandakumar et al.	JP	2001-199356	A	7/2001
2013/0325244	A1	12/2013	Wang et al.	JP	2002-000574	A	1/2002
2014/0047022	A1	2/2014	Chan et al.	JP	2002-046088	A	2/2002
2014/0085543	A1	3/2014	Hartley et al.	JP	2002-101333	A	4/2002
2014/0133590	A1	5/2014	Stuart et al.	JP	2002-112970	A	4/2002
2014/0139616	A1	5/2014	Pinter et al.	JP	2002-235423	A	8/2002
2014/0155755	A1	6/2014	Pinter et al.	JP	2002-305743	A	10/2002
2014/0207286	A1	7/2014	Wang et al.	JP	2002-321180	A	11/2002
2014/0267549	A1	9/2014	Pinter et al.	JP	2002-355779	A	12/2002
2015/0077502	A1	3/2015	Jordan et al.	JP	2004-181229	A	7/2004
2015/0081338	A1	3/2015	Lai et al.	JP	2004-524824	T	8/2004
2015/0088310	A1	3/2015	Pinter et al.	JP	2004-261941	A	9/2004
2015/0296177	A1	10/2015	Pinter et al.	JP	2004-289379	A	10/2004
2015/0314449	A1	11/2015	Wang et al.	JP	2005-028066	A	2/2005
				JP	2005-059170	A	3/2005
				JP	2005-111083	A	4/2005
				JP	2006-035381	A	2/2006
				JP	2006-508806	A	3/2006
				JP	2006-109094	A	4/2006
				JP	2006-224294	A	8/2006
				JP	2006-246438	A	9/2006
				JP	2007-007040	A	1/2007
				JP	2007-081646	A	3/2007
				JP	2007-232208	A	9/2007
				JP	2007-316966	A	12/2007
				JP	2009-125133	A	6/2009
				JP	2010-064154	A	3/2010
				JP	2010-532109	A	9/2010
				JP	2010-246954	A	11/2010
				KR	10-2006-0037979	A	5/2006
				KR	10-2009-0012542	A	2/2009
				KR	10-2010-0019479	A	2/2010
				KR	10-2010-0139037	A	12/2010
				WO	93/06690	A1	4/1993
				WO	97/42761	A1	11/1997
				WO	98/51078	A1	11/1998
				WO	99/67067	A1	12/1999
				WO	00/25516	A1	5/2000
				WO	00/33726	A1	6/2000
				WO	01/31861	A1	5/2001
				WO	03/077745	A1	9/2003
				WO	2004/008738	A1	1/2004

FOREIGN PATENT DOCUMENTS

AU	1216200	A	5/2000				
CA	2289697	A1	11/1998				
CN	1404695	A	3/2003				
CN	1554193	A	12/2004				
CN	1554985	A	12/2004				
CN	1561923	A	1/2005				
CN	1743144	A	3/2006				
CN	101049017	A	10/2007				
CN	101106939	A	1/2008				
CN	101151614	A	3/2008				
CN	100407729	C	7/2008				
CN	101390098	A	3/2009				
CN	101507260	A	8/2009				
CN	101730894	A	6/2010				
CN	101866396	A	10/2010				
CN	101978365	A	2/2011				
CN	102203759	A	9/2011				
CN	101106939	B	11/2011				
EP	466492	A2	1/1992				
EP	488673	A2	6/1992				
EP	981905	B1	1/2002				
EP	1262142	A2	12/2002				
EP	1304872	A1	4/2003				
EP	1536660	A2	6/2005				
EP	1573406	A2	9/2005				

WO	2004/012018	A2	2/2004
WO	2004/075456	A2	9/2004
WO	2006/012797	A1	2/2006
WO	2006/044847	A2	4/2006
WO	2006/078611	A2	7/2006
WO	2007/041295	A2	4/2007
WO	2007/041038	A3	6/2007
WO	2008/100272	A2	8/2008
WO	2008/100272	A3	10/2008
WO	2009/117274	A2	9/2009
WO	2009/128997	A1	10/2009
WO	2009/145958	A2	12/2009
WO	2010/006205	A1	1/2010
WO	2010/006211	A1	1/2010
WO	2010/033666	A1	3/2010
WO	2010/047881	A1	4/2010
WO	2010/062798	A1	6/2010
WO	2010/065257	A1	6/2010
WO	2010/120407	A1	10/2010
WO	2011/028589	A2	3/2011
WO	2011/028589	A3	4/2011
WO	2011/097130	A2	8/2011
WO	2011/097132	A2	8/2011
WO	2011/109336	A2	9/2011
WO	2011/097132	A3	12/2011
WO	2011/149902	A2	12/2011
WO	2013/097264	A1	7/2013

OTHER PUBLICATIONS

Yamauchi, Brian, "PackBot: A Versatile Platform for Military Robotics", Proceedings of SPIE for Military Robotics, 2004, pp. 228-237.

Yong et al., "Robot Task Execution with Telepresence Using Virtual Reality Technology", 1998 International Conference on Mechatronic Technology, Nov. 30-Dec. 2, 1998, pp. 1-8.

Zambroski, James, "CMU, Pitt Developing 'Nursebot'", Available at: <http://www.cs.cmu.edu/nursebot/web/press/tribunereview.html>, Retrieved on Jun. 26, 2012, Oct. 27, 2000, 3 pages.

Zamazil, Kristie, "Telemedicine in Texas: Public Policy Concerns", Focus Report, House Research Organization, Texas House of Representatives, No. 76-22, May 5, 2000, pp. 1-16.

Zipperer, Lorri, "Robotic Dispensing System", ISMP Medication Safety Alert!, vol. 4, No. 17, Aug. 25, 1999, 2 pages.

Zorn, Benjamin G., "Ubiquitous Telepresence", Department of Computer Science, University of Colorado, 1996, 13 pages.

Adams, Chris, "Simulation of Adaptive Behavior (SAB'02)", Mobile Robotics Research Group, The Seventh International Conference, retrieved on Jan. 22, 2014, available at: <http://www.dai.ed.ac.uk/groups/mrg/MRG.html>, Aug. 4-11, 2002, 1 page.

Bartholomew, "Pharmacy Apothecary", available online at <http://classes.bnf.fr/ema/grands/034.htm>, retrieved on Jul. 26, 2012.

Jouppi et al., "BiReality: Mutually-Immersive Telepresence", Proceedings of the 12th Annual ACM International Conference on Multimedia, Oct. 10-16, 2004, pp. 860-867.

International Preliminary Report on Patentability and Written Opinion Received for International Patent Application No. PCT/US2005/037347, mailed on Apr. 17, 2006, 7 pages.

International Preliminary Report on Patentability and Written Opinion Received for International Patent Application No. PCT/US2006/037076, mailed on Apr. 1, 2008, 6 pages.

International Search Report and Written Opinion Received for International Application No. PCT/US2006/037076, mailed on May 11, 2007, 6 pages.

International Preliminary Report on Patentability and Written Opinion Received for International Patent Application No. PCT/US/2007/14099, mailed on Dec. 16, 2008, 5 pages.

International Search Report Received for international Patent Application No. PCT/US2007/14099, mailed on Jul. 30, 2008, 1 page.

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2013/031708, mailed on Dec. 4, 2014, 10 pages.

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2013/031708, mailed on Jun. 26, 2013, 13 pages.

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2013/031778, issued on Nov. 25, 2014, 18 pages.

International Search Report and Written Opinion received for PCT Application No. PCT/US2013/031778, mailed on Jun. 28, 2013, 23 pages.

CMU Course 16X62, "Robot user's manual", (describing the Nomad Scout), Carnegie Mellon University, Feb. 1, 2001, 11 pages.

CNN, "Floating 'Droids' to Roam Space Corridors of the Future", Available online at <http://edition.cnn.com/2000/TECH/space/01/12/psa/>, retrieved on Nov. 11, 2010, Jan. 12, 2000, 3 pages.

Cnn.com, "Paging Dr.Robot: Machine Helps Doctors with Patients", Sep. 30, 2003, 3 pages.

Crowley, Susan L., "Hello to Our Future", AARP Bulletin, Jan. 2000, 12 pages.

Dalton, Barnaby, "Techniques for Web Telerobotics", PhD Thesis, University of Western Australia, 2001, 243 pages.

Dario et al., "A Robot Workstation for Diagnosis and Physical Therapy", IEEE Catalog No. 88TH0234-5, 1989, pp. 67-72.

Davies, Brian, "Robotics in Minimally Invasive Surgery", Mechatronics in Medicine Lab, Dept Mechanical Engineering, Imperial College, London SW7 2BX, 1995, pp. 1-2.

Davis, Erik, "Telefriend, Meet iRobot, The Smartest Webcam on Wheels", Wired Magazine, Issue 8.09, Available at: http://www.wired.com/wired/archive/8.09/irobot.html?pg=1&topic=&topic_set=, Sep. 2000, 3 pages.

Dean et al., "1992 AAAI Robot Exhibition and Competition", Articles, AI Magazine, vol. 14, No. 1, 1993, 15 pages.

Digiorgio, James, "Is Your Emergency Department of the Leading Edge?", Chicago Hospital News, vol. 2, No. 12, 2005, 3 pages.

Dudenhoeffer et al., "Command and Control Architectures for Autonomous Micro-Robotic Forces", FY00 Project Report, Idaho National Engineering and Environmental Laboratory Human Systems Engineering and Sciences Department, Idaho Falls, Apr. 2001, 43 pages.

Elhajj et al., "Real-Time Haptic Feedback in Internet-Based Telerobotic Operation", IEEE International Conference On Electro/Information Technology, Available online at http://www.egr.msu.edu/~ralab-web/cgi_bin/internet-teleoperation.php, Jun. 2000, 10 pages.

Elhajj et al., "Supermedia in Internet-Based Telerobotic Operations", Management of Multimedia on the Internet Lecture Notes in Computer Science, vol. 2216, Springer-Verlag Berlin Heidelberg, 2001, Oct. 29- Nov. 1, 2001, pp. 359-372.

Elhajj et al., "Synchronization and Control of Supermedia Transmission via the Internet", Proceedings of 2001 International Symposium on Intelligent Multimedia Video and Speech Processing, May 2-4, 2001, pp. 320- 323.

Ellison et al., "Telerounding and Patient Satisfaction Following Surgery", pp. 523-530.

Evans et al., "The Trackless Robotic Courier", Pyxis HelpMate®, 2007, 3 pages.

Fels et al., "Developing a Video-Mediated Communication System for Hospitalized Children", Telemedicine Journal, vol. 5, No. 2, 1999, 30 pages.

Fetterman et al., "Videoconferencing Over the Internet", 2001, 8 pages.

Fiorini et al., "Health Care Robotics: A Progress Report", IEEE International Conference on Robotics and Automation, 1997, Apr. 20-25, 1997, pp. 1271-1276.

Fong, Terrence, "Collaborative Control: A Robot-Centric Model for Vehicle Teleoperation", Doctoral Dissertation, Technical Report CMU-RI-TR-01-34, Robotics Institute, Carnegie Mellon University, Nov. 2001, 197 pages.

Fulbright, Ron et al., "An Autonomous Mobile Robot for Inspection of Nuclear Waste Storage Facilities", Autonomous Robots vol. 2, Nov. 24, 2011, pp. 225-235.

Gaidioz et al., "Synchronizing Network Probes to Avoid Measurement Intrusiveness with the Network Weather Service", Proceedings of the Ninth International Symposium on High-Performance Distributed Computing, 2000, pp. 147-154.

Garner et al., "The Application of Telepresence in Medicine", BT Technology Journal, vol. 15, No. 4, Oct. 1, 1997, pp. 181-187.

- Ghiasi et al., "A Generic Web-based Teleoperations Architecture: Details and Experience", Proceedings of SPIE, Telemanipulator and Telepresence Technologies VI, vol. 3840, No. 234, Sep. 19, 1999, 14 pages.
- Goldberg et al., "Collaborative Teleoperation via the Internet", IEEE International Conference on Robotics and Automation (ICRA), vol. 2, 2000, pp. 2019-2024.
- Goldberg et al., "Desktop Teleoperation via the World Wide Web", Robotics and Automation, 1995. Proceedings., 1995 IEEE International Conference, vol. 1, May 21-27, 1995, pp. 654-659.
- Goldenberg et al., "Telemedicine in Otolaryngology", American Journal of Otolaryngology, vol. 23, No. 1, 2002, pp. 35-43.
- Goldman, Lea, "Machine Dreams", Available Online at <http://www.forbes.com/global/2002/0527/043.html>, retrieved on Nov. 23, 2010, May 27, 2002, 5 pages.
- Gostai, "Gostai Jazz: Robotic Telepresence", Available online at <http://www.robotshop.com/media/files/pdf/gostai-jazz-information-sheet.pdf>, 4 pages.
- Gump, Michael D., "Robot Technology Improves VA Pharmacies", U.S. Medicine Informational Central, Jul. 2001, 3 pages.
- Hameed, Mohammed et al., "A Review of Telemedicine", Journal of Telemedicine and Telecare., vol. 5, Supplement 1, 1999, pp. 103-106.
- Han et al., "Construction of an Omnidirectional Mobile Robot Platform Based on Active Dual-Wheel Caster Mechanisms and Development of a Control Simulator", Kluwer Academic Publishers, vol. 29, Nov. 2000, pp. 257-275.
- Handley et al., "RFC 2327—SDP: Session Description Protocol", Available Online at <http://www.faqs.org/rfcs/rfc2327.html>, Retrieved on Nov. 23, 2010, Apr. 1998, 22 pages.
- Hanebeck et al., "Roman: A Mobile Robotic Assistant for Indoor Service Applications", Proceedings of the 1997 IEEE/RSJ International Conference on Intelligent Robots and Systems, vol. 2, Sep. 7-11, 1997, pp. 518-525.
- Harmo et al., "Moving Eye-Interactive Telepresence Over Internet With a Ball Shaped Mobile Robot", Available Online at <http://automation.tkk.fi/files/tervetaas/MovingEye4.pdf>, 2000, 6 pages.
- Haule et al., "Control Scheme for Delayed Teleoperation Tasks", Proceedings of IEEE Pacific Rim Conference Communications, Computers, and Signal Processing, May 17-19, 1995, pp. 157-160.
- Hees, William P., "Communications Design for a Remote Presence Robot", CSCI E-131b, Final Project, Jan. 14, 2002, 12 pages.
- Herias et al., "Flexible Virtual and Remote Laboratory for Teaching Robotics", FORMATEX 2006; Proc. Advance in Control Education Madrid, Spain, Jun. 2006, pp. 1959-1963.
- Holmberg, "Development of a Holonomic Mobile Robot for Mobile Manipulation Tasks", The Robotics Laboratory, Computer Science Department, Stanford University, Stanford, California, USA, vol. 19, No. 11, Nov. 2000, pp. 1066-1074.
- Ishiguro et al., "Integrating a Perceptual Information Infrastructure with Robotic Avatars: A Framework for Tele-Existence", Proceedings of IEEE/RSJ International Conference on Intelligent Robots and Systems, vol. 2, 1999, pp. 1032-1038.
- Ishihara et al., "Intelligent Microrobot DDS (Drug Delivery System) Measured and Controlled by Ultrasonics", Proceedings of IEEE/RSJ International Workshop on Intelligent Robots and Systems Intelligence for Mechanical Systems, vol. 2, Nov. 3-5, 1991, pp. 1145-1150.
- ITU, "Call Completion Supplementary Services for H.323", ITU-T, Telecommunication Standardization Sector of ITU, H.450.9, Series H: Audiovisual and Multimedia Systems, Nov. 2000, 63 pages.
- ITU, "Call Intrusion Supplementary Service for H.323", ITU-T, Telecommunication Standardization Sector of ITU, H.450.11, Series H: Audiovisual and Multimedia Systems, Mar. 2001, 59 pages.
- ITU, "Packet-Based Multimedia Communications Systems", ITU-T, Telecommunication Standardization Sector of ITU, H.323, Series H: Audiovisual and Multimedia Systems, Feb. 1998, 128 pages.
- ITU, "Transmission of Non-Telephone Signals: A Far End Camera Control Protocol for Videoconferences Using H.224", ITU-T, Telecommunication Standardization Sector of ITU, H.281, Nov. 1994, 12 pages.
- Ivanova, Natali, "Master's thesis: Internet Based Interface for Control of a Mobile Robot", Department of Numerical Analysis and Computer Science, 2003, 59 pages.
- Jacobs et al., "Applying Telemedicine to Outpatient Physical Therapy", AMIA, Annual Symposium Proceedings, 2002, 1 page.
- Jenkins et al., "Telehealth Advancing Nursing Practice", Nursing Outlook, vol. 49, No. 2, Mar. 2001, pp. 100-105.
- Johanson, Mathias, "Supporting Video-Mediated Communication Over the Internet", Department of Computer Engineering, Chalmers University of Technology, Gothenburg, Sweden, 2003, 222 pages.
- Paulos et al., "Ubiquitous Tele-Embodiment: Applications and Implications", International Journal of Human Computer Studies, vol. 46, No. 6, Jun. 1997, pp. 861-877.
- Paulos, "Video of PRoP 2 at Richmond Field Station", www.prop.org Printout of Home Page of Website and two-page Transcript of the audio portion of said PRoP Video, May 2001.
- Picturetel Corporation, "PictureTel Live200 for Windows NT Product Guide", 1997, 63 pages.
- Pin et al., "A New Family of Omnidirectional and Holonomic Wheeled Platforms for Mobile Robots", IEEE Transactions on Robotics and Automation, vol. 10, No. 4, Aug. 1994, pp. 480-489.
- Piquetpaille, Roland, "This Blog and its RSS Feed Are Moving", Roland Piquetpaille's Technology Trends, How new technologies are modifying our way of life, Oct. 31, 2004, 2 pages.
- Radvision, "Making Sense of Bandwidth the NetsenseWay", Network Congestion in Unmanaged Networks Bandwidth Estimation and Adaptation Techniques, White Paper, Radvision's Netsense Technology, 2010, 7 pages.
- Reynolds et al., "Review of Robotic Telemedicine Utilization in Intensive Care Units (ICUs)", 11th Annual ATA Symposium, Tampa, Florida, 2011, 1 page.
- Roach, Adam, "Automatic Call Back Service in SIP", Internet Engineering Task Force, Internet Draft, Category: Informational, Mar. 2000, 8 pages.
- Rovetta et al., "A New Telerobotic Application: Remote Laparoscopic Surgery Using Satellites and optical fiber Networks for Data Exchange", International Journal of Robotics Research, vol. 15, No. 3, Jun. 1, 1996, pp. 267-279.
- Roy, N. et al., "Towards Personal Service Robots for the Elderly", Workshop on Interactive Robots and Entertainment (WIRE 2000), vol. 25, http://www.ri.cmu.edu/pb_files/pub2/roy_nicholas_2000_1/roy_nicholas_2000_1.pdf, Apr. 30-May 1, 2000, 7 pages.
- Sachs et al., "Virtual Visit: Improving Communication for Those Who Need it Most", Studies in Health Technology and Informatics, vol. 94, Medicine Meets Virtual Reality 11, 2003, pp. 302-308.
- Salemi et al., "MILO: Personal Robot Platform", IEEE/RSJ International Conference on Intelligent Robots and Systems, Aug. 2005, pp. 4089-4094.
- Sandt et al., "Perceptions for a Transport Robot in Public Environments", Proceedings of the IEEE/RSJ International Conference on Intelligent Robots and Systems, vol. 1, Sep. 7-11, 1997, pp. 360-365.
- Sawyer, Robert J., "Inventing the Future: 2000 Years of Discovery", Available online at <http://www.sfwriter.com/pritf.htm>, retrieved on May 25, 2008, Jan. 2, 2000, 2 pages.
- Schaeffer et al., "Care-O-Bot™: The Concept of a System for Assisting Elderly or Disabled Persons in Home Environments", Proceedings of the 24th Annual Conference of the IEEE Industrial Electronics Society, vol. 4, 1998, pp. 2476-2481.
- Schraft et al., "Care-O-bot™: the concept of a system for assisting elderly or disabled persons in home environments", IEEE Proceedings of the 24th Annual Conference of the Industrial Electronics Society, IECON, Aug. 31-Sep. 4, 1998, pp. 2476-2481.
- Schultz et al., "Web Interfaces for Mobile Robots in Public Places", IEEE Robotics & Automation Magazine, vol. 7, No. 1, Mar. 2000, pp. 48-56.
- Shimoga et al., "Touch and Force Reflection for Telepresence Surgery", Proceedings of the 16th Annual International Conference of the IEEE Engineering in Medicine and Biology Society, Nov. 1994, pp. 1049-1050.
- Siegwart et al., "Interacting Mobile Robots on the Web", Proceedings of the 1999 IEEE International Conference on Robotics and Automation, May 1999, pp. 1-7.

- Simmons et al., "Xavier: An Autonomous Mobile Robot on the Web", IEEE Robotics and Automation Magazine, 1999, pp. 43-48.
- Stephenson, Gary, "Dr. Robot Tested at Hopkins", Available at: <http://www.hopkinsmedicine.org/press/2003/august/030805.htm>, Aug. 5, 2003, 2 pages.
- Stoianovici et al., "Robotic Tools for Minimally Invasive Urologic Surgery", Complications of Urologic Laparoscopic Surgery: Recognition, Management and Prevention, Dec. 2002, 17 pages.
- Suplee, Curt, "Mastering the Robot", The Washington Post, Washington Post Staff Writer, Sep. 17, 2000, 5 pages.
- Tahboub et al., "Dynamics Analysis and Control of a Holonomic Vehicle With Continuously Variable Transmission", Transactions of the ASME, Journal of Dynamic Systems, Measurement and Control, vol. 124, Mar. 2002, pp. 118-126.
- Telepresence Research, Inc., "The Telepresence Mobile Robot System", Available at: <http://www.telepresence.com/telepresence-research/telebot/>, Retrieved on Nov. 23, 2010, Feb. 20, 1995, 3 pages.
- Tendick et al., "Human-Machine Interfaces for Minimally Invasive Surgery", vol. 6, Proceedings of the 19th Annual International Conference of the IEEE Engineering in Medicine and Biology Society, Oct. 30-Nov. 2, 1997, pp. 2771-2776.
- Theodosiou et al., "MuLVAT: A Video Annotation Tool Based on XML-Dictionaries and Shot Clustering", Part II, 19th International Conference, Artificial Neural Networks-ICANN 2009, Sep. 14-17, 2009, pp. 913-922.
- Thrun et al., "Probabilistic Algorithms and the Interactive Museum Tour-Guide Robot Minerva", vol. 19, International Journal of Robotics Research, 2000, pp. 1-35.
- Time, Lists, "Office Coworker Robot", Best Inventions of 2001, Available at: http://content.time.com/time/specials/packages/article/0,28804,1936165_1936255_1936640,00.html, Nov. 19, 2001, 2 pages.
- Tipsuwan et al., "Gain Adaptation of Networked Mobile Robot to Compensate QoS Deterioration", vol. 4, 28th Annual Conference of the Industrial Electronics Society, Nov. 5-8, 2002, pp. 3146-3151.
- Tsui et al., "Exploring Use Cases for Telepresence Robots", 6th ACM/IEEE International Conference on Human-Robot Interaction (HRI), Mar. 2011, pp. 11-18.
- Tyrrell et al., "Teleconsultation in Psychology: The Use of Videolinks for Interviewing and Assessing Elderly Patients", Age and Ageing, vol. 30, No. 3, May 2001, pp. 191-195.
- Tzafestas et al., "VR-Based Teleoperation of a Mobile Robotic Assistant: Progress Report", Technical Report DEMO 2000/13, Institute of Informatics and Telecommunications, National Center for Scientific Research "Demokritos", Nov. 2000, pp. 1-23.
- UMASS Lowell Robotics Lab, "Robotics Lab @ UMASS Lowell", Brochure, 2011, 2 pages.
- Urquhart, Kim, "InTouch's Robotic Companion 'Beams Up' Healthcare Experts", Medical Device Daily, vol. 7, No. 39, Feb. 27, 2003, pp. 1, 4.
- Video Middleware Cookbook, "H.350 Directory Services for Multimedia", 2 pages.
- Weaver et al., "Monitoring and Controlling Using the Internet and Java", Proceedings of the 25th Annual Conference of the IEEE Industrial Electronics Society, vol. 3., 1999, pp. 1152-1158.
- Weiss et al., "Pebbles: A Personal Technology for Meeting Education, Social and Emotional Needs of Hospitalised Children", Personal and Ubiquitous Computing, vol. 5, No. 3, Aug. 2001, pp. 157-168.
- Weiss et al., "Telework and Video-Mediated Communication: Importance of Real-Time, Interactive Communication for Workers with Disabilities", Available at: http://www.telbotics.com/research_3.htm, Retrieved on Nov. 23, 2010, 3 pages.
- West et al., "Design of Ball Wheel Mechanisms for Omnidirectional Vehicles with Full Mobility and Invariant Kinematics", Journal of Mechanical Design, vol. 119, Jun. 1997, pp. 153-161.
- Yamasaki et al., "Applying Personal Robots and Active Interface to Video Conference Systems", 6th International Conference on Human Computer Interaction, vol. B, 1995, pp. 243-248.
- Screenshot Showing Google Date for Lemaire Telehealth Manual, 1 page, screenshot retrieved on Dec. 18, 2014.
- Appeal from the U.S. District Court for the Central District of California in case No. 11-cv-9185, Judge Percy Anderson, Joint Appendix, vol. I of IV, Jun. 24, 2013, pp. A1-A6357.
- Appeal from the U.S. District Court for the Central District of California in case No. 11-cv-9185, Judge Percy Anderson, Joint Appendix, vol. II of IV, Jun. 24, 2013, pp. A6849-A10634.
- Appeal from the U.S. District Court for the Central District of California in case No. 11-cv-9185, Judge Percy Anderson, Joint Appendix, vol. III of IV, Jun. 24, 2013, pp. A10654-A15517.
- Appeal from the U.S. District Court for the Central District of California in case No. 11-cv-9185, Judge Percy Anderson, Joint Appendix, vol. IV of IV, Jun. 24, 2013, pp. A15677-A18127.
- Appeal from the U.S. District Court for the Central District of California in No. 11-CV-9185, Judge Percy Anderson, May 9, 2014, pp. 1-48.
- Civil Minutes-General: Case No. CV 11-9185PA (AJWx), *InTouch Tech., Inc. v. VGO Commons, Inc.*, Sep. 10, 2012, 7 pages.
- Defendant VGO Communications, Inc.'s Invalidity Contentions Pursuant to the Feb. 27, 2012 Civil Minute Order, May 2, 2012, 143 pages.
- Defendant-Counterclaimant VGO Communications, Inc.'s Supplemental Invalidity Contentions Pursuant to the Feb. 27, 2012 Civil Minute Order, May 14, 2012, 228 pages.
- Google translation of: Innovations Report, From research project to television star: Care-O-bot in ZDF series, <http://www.innovations-report.de/specials/printa.php?id=5157>, Sep. 28, 2001, 2 pages.
- Magne Charge, Smart Power for Electric Vehicles, Aug. 26, 1997, 2 pages.
- More Online Robots: Robots that Manipulate, available online at http://ford.ieor.berkeley.edu/ir/robots_a2.html, Retrieved on Nov. 23, 2010, Aug. 2001, 2 pages.
- MPEG File Format Summary, downloaded from: <http://www.fileformat.info/format/mpeg/egff.htm>, Feb. 1, 2001, 8 pages.
- Nomad Scout Language Reference Manual, Nomadic Technologies, Software Version 2.7, Part No. DOC00002, Jul. 12, 1999, 47 pages.
- Nomad Scout User's Manual, Nomadic Technologies, Software Version 2.7, Part No. DOC00004, Jul. 12, 1999, pp. 1-59.
- Opening Brief for Plaintiff-Appellant InTouch Technologies, Inc., Appeal from the U.S. District Court for the Central District of California in Case No. 11-cv-9185, Judge Percy Anderson, Apr. 12, 2013, 187 pages.
- PictureTel Adds New Features and Functionality to Its Award-Winning Live200 Desktop Videoconferencing System, PR Newswire Association, LLC, Gale, Cengage Learning, Jun. 13, 1997, 5 pages.
- Reply Brief for Defendant-Appellee VGO Communications, Inc., Appeal from the U.S. District Court for the Central District of California, in Case No. 2:11-cv-9185, Judge Percy Anderson, May 28, 2013, 75 pages.
- Reply Brief for Plaintiff-Appellant InTouch Technologies, Inc., Appeal from the U.S. District Court for the Central District of California in Case No. 11-cv-9185, Judge Percy Anderson, Jun. 14, 2013, 39 pages.
- Robert I, II, III, Spawar, Systems Center Pacific, 1998, 8 pages.
- Using your Infrared Cell Phone Camera, <http://www.catsdomain.com/xray/about.htm>, Courtesy of Internet Wayback Machine, Jan. 30, 2010, 4 pages.
- U.S. Appl. No. 10/783,760, filed Feb. 20, 2004, 48 pages.
- Office Action Received for Chinese Patent Application No. 200680044698.0, Nov. 4, 2010, 26 pages.
- U.S. Appl. No. 60/449,762, filed Feb. 24, 2003, 28 pages.
- ACM Digital Library Record, "Autonomous Robots vol. 11 Issue 1", downloaded from <http://dl.acm.org/citation.cfm?id=591550&picked=prox&cfid=360891374&cfToken=35225929>, Jul. 2001, 2 pages.
- Activemedia, Inc., "Saphira Software Manual", Saphira Version 5.3, ActiveMedia, Inc., 1997, 105 pages.
- Activmedia Robotics, "Pioneer 2/PeopleBot TM", Operations Manual, Version 9, Oct. 2001, 78 pages.
- Ando et al., "A Multimedia Self-service Terminal with Conferencing Functions", Robot and Human Communication, RO-MAN'95, Tokyo, Proceedings of 4th IEEE International Workshop, Jul. 5-7, 1995, pp. 357-362.

- Android Amusement Corp., "What Marketing Secret Renting Robots from Android Amusement Corp!", (Advertisement), 1982, 1 page.
- Apple Inc., "I Phone", iPhone Series, XP002696350, Sep. 21, 2012, pp. 1-29.
- Applebome, Peter, "Planning Domesticated Robots for Tomorrow's Household", New York Times, <http://www.theoldrobots.com/images17/dc17.JPG>, Mar. 4, 1982, p. 21 and 23.
- Bar-Cohen et al., "Virtual Reality Robotic Telesurgery Simulations Using MEMICA Haptic System", Proceedings of SPIE's 8th Annual International Symposium on Smart Structures and Materials, Mar. 5-8, 2001, pp. 1-7.
- Barrett, Rick, "Video Conferencing Business Soars as Companies Cut Travel; Some Travel Cuts Are Permanent", http://www.ivci.com/international_videoconferencing_news_videoconferencing_news_19.html, May 13, 2002, 2 pages.
- Bauer et al., "Remote Telesurgical Mentoring: Feasibility and Efficacy", IEEE, Proceedings of the 33rd Hawaii International Conference on System Sciences, 2000, pp. 1-9.
- Bauer, Jeffrey C., "Service Robots in Health Care: The Evolution of Mechanical Solutions to Human Resource Problems", Bon Secours Health System Inc., Technology Early Warning System (TEWS), Future of Service Robots in Health Care, Jun. 2003, pp. 1-10.
- Bischoff, Rainer, "Design Concept and Realization of the Humanoid Service Robot HERMES", Field and Service Robotics, Springer, 1998, pp. 485-492.
- Blackwell, Gerry, "Video: A Wireless LAN Killer App?", Available online at <http://www.wi-fiplanet.com/columns/article.php/1010261/Video-A-Wireless-LAN-Killer>, retrieved on Nov. 22, 2010, Apr. 16, 2002, 4 pages.
- Blaer et al., "TopBot: Automated Network Topology Detection With a Mobile Robot", IEEE, Proceedings of the 2003 International Conference on Robotics 7 Automation, Taipei, Taiwan, Sep. 14-19, 2003, pp. 1582-1587.
- Bradner, S., "The Internet Standards Process—Revision 3", Network Working Group, Request for Comments: 2026, BCP: 9, Obsoletes: 1602, Category: Best Current Practice, Oct. 1996, pp. 1-36.
- Brenner, Pablo, "A technical tutorial on the IEEE 802.11 protocol", BreezeCOM Wireless Communications, 1997, pp. 1-24.
- Breslow et al., "Effect of a Multiple-Site Intensive Care Unit Telemedicine Program on Clinical and Economic Outcome an Alternative Paradigm for Intensivist Staffing", Critical Care Med; vol. 32, No. 1, Jan. 2004, pp. 31-38.
- Brooks, Rodney, "A Robust Layered Control System for a Mobile Robot", IEEE, Journal of Robotics and Automation, vol. 2, No. 1, Mar. 1986, pp. 14-23.
- Brooks, Rodney Allen., "Remote Presence", Abstracts from Flesh & Machines, How Robots Will Change Us, Feb. 2002, pp. 131-147.
- Celi et al., "The EICU: It's Not Just Telemedicine", Critical Care Medicine vol. 29, No. 8 (Supplement), Aug. 2001, pp. 183-189.
- Cheatham et al., "Interface Development for a Child's Video Conferencing Robot", Available online at www.ryerson.ca/pebbles/publications/paper-iea200hfes-last.pdf, 2000, 4 pages.
- Christensen et al., "BeeSoft User's Guide and Reference", Robots for the Real World™, Real World Interface, Inc., Sep. 26, 1997, 203 pages.
- Chu et al., "Detection of Target Mobile Signal Strength", Technical Development, Motorola Inc, Jan. 1999, pp. 205-206.
- Cleary et al., "State of the Art in Surgical Robotics: Clinical Applications and Technology Challenges", Feb. 24, 2002, pp. 1-26.
- Jouppi et al., "First Steps Towards Mutually-Immersive Mobile Telepresence", Proceedings of the 2002 ACM conference on Computer Supported Cooperative Work, Nov. 16-20, 2002, pp. 354-363.
- Kanehiro et al., "Virtual Humanoid Robot Platform to Develop Controllers of Real Humanoid Robots without Porting", Proceedings of the IEEE/RSJ International Conference on Intelligent Robots and Systems, vol. 2, 2001, pp. 1093-1099.
- Kaplan et al., "An Internet Accessible Telepresence", Multimedia Systems Journal, vol. 5, 1996, 7 pages.
- Keller et al., "Raven Interface Project", The National Aviary's Teleconferencing Carnegie Mellon University Robot, Interaction and Visual Interface Design, School of Design, Carnegie Mellon University, 2001, 8 pages.
- Khatib, "Robots in Human Environments", Proceedings International Conference on Control, Automation, Robotics, and Vision ICRACV2000, 1999, pp. 15.
- Knight et al., "Active Visual Alignment of a Mobile Stereo Camera Platform", Proceedings of IEEE International Conference on Robotics and Automation, vol. 4, Apr. 24-28, 2000, pp. 3203-3208.
- Koenen, Rob, "MPEG-4: a Powerful Standard for Use in Web and Television Environments", (KPN Research), downloaded from <http://www.w3.org/Architecture/1998/06/Workshop/paper26>, Jul. 1, 1998, 4 pages.
- Kurlowicz et al., "The Mini Mental State Examination (MMSE)", Try This: Best Practices in Nursing Care to Older Adults, A series from the Hartford Institute of Geriatric Nursing, Issue No. 3, Jan. 1999, 2 pages.
- Kuzuoka et al., "Can the GestureCam Be a Surrogate?", Proceedings of the Fourth European Conference on Computer-Supported Cooperative Work, 1995, pp. 181-196.
- Lane, Earl, "Automated Aides", Available online at <http://www.cs.cmu.edu/nursebot/web/press/nd4380.htm>, Retrieved on Nov. 23, 2010, Oct. 17, 2000, 4 pages.
- Lee et al., "A Novel Method of Surgical Instruction: International Telementoring", World Journal of Urology, vol. 16, No. 6, Dec. 1998, pp. 367-370.
- Leifer et al., "VIPRR: A Virtually in Person Rehabilitation Robot", Proceedings of 1997 International Conference on Rehabilitation Robotics, Apr. 14-15, 1997, 4 pages.
- Lemaire, Edward, "Using Communication Technology to Enhance Rehabilitation Services: A Solution Oriented User Manual", Institute for Rehabilitation Research and Development, Terry Fox Mobile Clinic, The Rehabilitation Centre, Ottawa, Ontario, Canada, Version 2.0; http://www.irrd.ca/telehealth/distfile/distman_v2_1.pdf, 1998-2001, 104 pages.
- Library of Congress, "008-Fixed-Length Data Elements (NR)", MARC 21 Format for Classification Data, downloaded from <http://www.loc.gov/marc/classification/cd008.html>, Jan. 2000, pp. 1-14.
- Lim et al., "Control to Realize Human-Like Walking of a Biped Humanoid Robot", Systems, Man, and Cybernetics, 2000, IEEE International Conference, vol. 5, 2000, pp. 3271-3276.
- Linebarger, John M. et al., "Concurrency Control Mechanisms for Closely Coupled Collaboration in Multithreaded Virtual Environments", Department of Computer Science and Engineering, Lehigh University, vol. 13, 2004, 40 pages.
- Long, "Robot Navigation Technology", Available Online at <http://www.atp.nist.gov/eao/sp950-1/helpmate.htm>, Retrieved on Nov. 23, 2010, Mar. 1999, 3 pages.
- Luna, Nancy, "Robot a New Face on Geriatric Care", oregister.com, Aug. 6, 2003.
- Mack, Michael J., "Minimally Invasive and Robotic Surgery", The Journal of the American Medical Association, vol. 285, No. 5, 2001, pp. 568-572.
- Mair, G. M., "Telepresence—The Technology and its Economic and Social Implications", Proceedings on International Symposium on Technology and Society, Jun. 20-21, 1997, pp. 118-124.
- Martin, Anya, "Brighter Days Ahead", Assisted Living Today, vol. 9, Nov./Dec. 2002, pp. 19-22.
- McCardle et al., "The Challenge of Utilizing New Technology in Design Education", Loughborough University, IDATER, 2000, pp. 122-127.
- Meng et al., "E-Service Robot in Home Healthcare", Proceedings of the IEEE/RSJ International Conference on Intelligent Robots and Systems, 2000, pp. 832-837.
- Metz, Cade, "HP Labs", Available Online at <http://www.pcmag.com/article2/0,2817,1130820,00.asp>, Jul. 1, 2003, 4 pages.
- Michaud, Anne, "Introducing "Nursebot"", Available Online at <http://www.cs.cmu.edu/nursebot/web/press/globe301/index.html>, Retrieved on May 5, 2008, 2001, 4 pages.
- Microsoft Corporation, Inc., "Microsoft NetMeeting 3 Features excerpt from Official Microsoft NetMeeting 3.0 Book", Available

- at: <http://technet.microsoft.com/en-us/library/cc723477.aspx>, Retrieved on Jun. 26, 2012, 6 pages.
- Nakajima, Marvin, "Telepresence", OMNI Magazine, Jun. 1980, 6 pages.
- Montemerlo, "Telepresence: Experiments in Next Generation Internet", Available Online at <http://www.ri.cmu.edu/creative/archives.htm>, Retrieved on May 25, 2008, Oct. 20, 1998.
- Murphy, "Introduction to AI Robotics", A Bradford Book, The MIT Press, Cambridge, Massachusetts, London, England, 2000, 487 pages.
- Nakajima et al., "A Multimedia Teleteaching System using an Electronic Whiteboard for Two Way Communication of Motion Videos and Chalkboards", Proceedings of 2nd IEEE International Workshop on Robot and Human Communication, 1993, pp. 436-441.
- Nakazato et al., "Group-Based Interface for Content-Based Image Retrieval", Proceedings of the Working Conference on Advanced Visual Interfaces, 2002, pp. 187-194.
- Nakazato et al., "ImageGrouper: A Group-Oriented User Interface for Content-Based Image Retrieval and Digital Image Arrangement", Journal of Visual Languages & Computing, vol. 14, No. 4, Aug. 2003, pp. 45-46.
- NERSC, "Berkeley Lab's Rage Telepresence Robot Captures R&D100 Award", Available at: <https://www.nersc.gov/news-publications/news/nersc-center-news/2002/berkeley-lab-s-rage-telepresence-robot-captures-r-and-d100-award/>, Retrieved on Jan. 22, 2014, Jul. 2, 2002.
- Nomadic Technologies Inc., "Nomad XR4000 Hardware Manual", Release 1.0, Mar. 1999, 34 pages.
- Noritsugu et al., "Application of Rubber Artificial Muscle Manipulator as a Rehabilitation Robot", Mechatronics, IEEE/ASME Transactions, vol. 2, No. 4, Dec. 1997, pp. 259-267.
- North, Michael, "Telemedicine: Sample Script and Specifications for a Demonstration of Simple Medical Diagnosis and Treatment Using Live Two-Way Video on a Computer Network", Greenstar Corporation, 1998, 5 pages.
- Ogata et al., "Development of Emotional Communication Robot: WAMOEBA-2R—Experimental evaluation .", Proceedings of the 2000 IEEE/RSJ International Conference on Intelligent Robots and Systems, vol. 1, 2000, pp. 175-180.
- Ogata et al., "Emotional Communication Robot: WAMOEBA-2R—Emotion Model and Evaluation Experiments", Proceedings of the International Conference on Humanoid Robots, 2000, pp. 1-16.
- Oh et al., "Autonomous Battery Recharging for Indoor Mobile Robots", Proceedings of Australian Conference on Robotics and Automation, 2000, pp. 1-6.
- Ojha, Anand K., "An application of Virtual Reality in Rehabilitation", Proceedings of the 1994 IEEE Southeastcon 1994 on Creative Technology Transfer—A Global Affair, Apr. 1994, pp. 4-6.
- Osborn, Jim, "Quality of Life Technology Center", QoLT Research Overview: A National Science Foundation Engineering Research Center, Carnegie Mellon University of Pittsburgh, 2 pages.
- Panusopone et al., "Performance comparison of MPEG-4 and H.263+ for streaming video applications", Circuits Systems Signal Processing, vol. 20, No. 3, 2001, pp. 293-309.
- Paulos et al., "A World Wide Web Telerobotic Remote Environment Browser", Available at: <http://www.w3.org/Conferences/WWW4/Papers/326/>, Retrieved on Nov. 23, 2010, 1995, 15 pages.
- Paulos et al., "Designing Personal Tele-Embodiment", Proceedings of IEEE International Conference on Robotics and Automation, vol. 4, May 16-20, 1998, pp. 3173-3178.
- Paulos, Eric J., "Personal Tele-Embodiment", Dissertation, Doctor of Philosophy in Computer Science in the Graduate Division of the University of California at Berkeley, 2001, 282 pages.
- Paulos, Eric John., "Personal tele-embodiment", OskiCat Catalog Record, UCB Library Catalog, 2001, 3 pages.
- Paulos et al., "Personal Tele-Embodiment", Chapter 9 in Goldberg et al., ed. "Beyond webcams", MIT Press, Jan. 4, 2002, pp. 155-167.
- Paulos, Eric John., "Personal Tele-Embodiment", Introductory and cover pages from 2001 Dissertation including Contents table, together with e-mails relating thereto from UC Berkeley Libraries, as shelved at UC Berkeley Engineering Library (Northern Regional library Facility), May 8, 2002, 25 pages, including 4 pages of e-mails.
- Paulos et al., "PRoP: Personal Roving Presence", ACM:CHI Proceedings of CHI, 1998, 8 pages.
- Paulos et al., "Social Tele-Embodiment: Understanding Presence", Autonomous Robots, vol. 11, Issue 1, Kluwer Academic Publishers, Jul. 2001, pp. 87-95.

* cited by examiner

Primary Examiner — Yuen Wong

(74) Attorney, Agent, or Firm — Kory D. Christensen; Stoel Rives LLP

(57)

ABSTRACT

A telepresence robot may include a drive system, a control system, an imaging system, and a mapping module. The mapping module may access a plan view map of an area and tags associated with the area. In various embodiments, each tag may include tag coordinates and tag information, which may include a tag annotation. A tag identification system may identify tags within a predetermined range of the current position and the control system may execute an action based on an identified tag whose tag information comprises a telepresence robot action modifier. The telepresence robot may rotate an upper portion independent from a lower portion. A remote terminal may allow an operator to control the telepresence robot using any combination of control methods, including by selecting a destination in a live video feed, by selecting a destination on a plan view map, or by using a joystick or other peripheral device.

20 Claims, 43 Drawing Sheets






FIG. 1








FIG. 3C




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D




FIG. 4E




FIG. 4F




FIG. 5




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 7




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 8D




FIG. 8E




FIG. 8F




FIG. 9A

612






FIG. 9B

622b






FIG. 10C






FIG. 10D






FIG. 10G




FIG. 11A




FIG. 11B




FIG. 11C




FIG. 11D





FIG. 12



1302 FIG. 13




FIG. 14




FIG. 15A




FIG. 15B




FIG. 16A




FIG. 16B




FIG. 16C





FIG. 16D






FIG. 18




FIG. 19




FIG. 20A




FIG. 20B




FIG. 20C

INTERFACING WITH A MOBILE TELEPRESENCE ROBOT

CROSS REFERENCE TO RELATED APPLICATIONS

This U.S. patent application is a Continuation of U.S. patent application Ser. No. 14/799,450, titled INTERFACING WITH A MOBILE TELEPRESENCE ROBOT, filed on Jul. 14, 2015, which is a Continuation of U.S. patent application Ser. No. 14/221,827, titled INTERFACING WITH A MOBILE TELEPRESENCE ROBOT, filed on Mar. 21, 2014, which is a Divisional of U.S. patent application Ser. No. 13/360,579, titled INTERFACING WITH A MOBILE TELEPRESENCE ROBOT, filed on Jan. 27, 2012, which claims priority under 35 U.S.C. §119(e) to U.S. Provisional Application No. 61/437,433 filed on Jan. 28, 2011, which applications are hereby incorporated by reference in their entireties. In addition, U.S. Patent Publication No. 2007/0199108 and U.S. Pat. No. 6,535,793 are also incorporated herein by reference in their entireties.

TECHNICAL FIELD

This disclosure relates to mobile telepresence robots.

BACKGROUND

A robot is generally an electro-mechanical machine guided by a computer or electronic programming. Telepresence robots have the capability to move around in their environment and are not fixed to one physical location. An example of a telepresence robot that is in common use today is an automated guided vehicle or automatic guided vehicle (AGV). An AGV is generally a telepresence robot that follows markers or wires in the floor, or uses a vision system or lasers for navigation. Telepresence robots can be found in industry, military and security environments. They also appear as consumer products, for entertainment or to perform certain tasks like home assistance.

SUMMARY

One aspect of the disclosure provides a telepresence robot system including a local terminal and a remote telepresence robot. The local terminal may include an electronic display, a processor, and a memory in communication with the processor, the memory comprising instructions executable by the processor. The executable instructions may be configured to cause the processor to retrieve at least a portion of a plan view map representative of robot-navigable areas of a robot operating surface; retrieve at least one of a plurality of tags, each of the plurality of tags comprising tag coordinates describing the relative location of the tag and tag information, which may include a tag annotation; receive a video feed from an imaging system of a remote telepresence robot; receive positioning information; display the video feed from the imaging system of the remote telepresence robot; display the plan view map with an indication of a current position of the telepresence robot on the plan view map; display a rendition of the tag annotation of the at least one tag on at least one of the plan view map and the video feed using the tag coordinates; and transmit one or more commands to the remote telepresence robot.

In some embodiments, the instructions executable by the processor are further configured to cause the processor to determine a distortion (e.g., a coordinate transformation

between a two-dimensional coordinate system and a three-dimensional coordinate system) between the plan view map and the video feed received from the imaging system of the remote telepresence robot; apply the distortion to the tag coordinates of the at least one tag to determine corresponding video coordinates and perspective data describing a location and perspective of the at least one tag relative to the video feed; and display a three-dimensional rendition of the tag annotation of the at least one tag overlaid on the video feed using the tag video coordinates.

In some embodiments, the three-dimensional rendition of the tag annotation may be dynamically re-rendered based on the current position of the remote telepresence robot and a perspective of the at least one tag relative to the video feed.

In some embodiments, the three-dimensional rendition of the tag annotation may be overlaid on the video feed with respect to an object detected in the video feed.

In some embodiments, the three-dimensional rendition of the tag annotation may be overlaid along a wall detected in the video feed.

In some embodiments, the tag information of the at least one tag comprises a telepresence robot action modifier and the robot action modifier may be configured to provide execution instructions to a control system of the telepresence robot to execute a first action in response to the telepresence robot being within a predetermined range of the tag coordinates of the at least one tag.

In some embodiments, the instructions executable by the processor are further configured to cause the processor to transmit the execution instruction to the control system of the telepresence robot when the telepresence robot is within a predetermined range of the tag coordinates of the at least one tag.

In some embodiments, the robot action modifier further comprises instructions regarding one of a time and a location on the plan view map that the control system of the telepresence robot should execute the first action.

In some embodiments, the instructions executable by the processor are further configured to cause the processor to receive a sequence of coordinates relative to the plan view map forming a path along which the remote telepresence robot has traveled; store the sequence of coordinates forming the path as a path tag comprising tag coordinates and tag information, which may include a tag annotation; retrieve the path tag when the remote telepresence robot arrives within a predetermined distance of the tag coordinates; and display a rendition of the tag annotation of the path tag on at least one of the plan view map and the video feed using the tag coordinates.

In some embodiments, the telepresence robot system local terminal further comprises at least one user input device and the sequence of coordinates forming the path may be provided by the user input device.

In some embodiments, the sequence of coordinates forming the path may be provided by the remote telepresence robot.

In some embodiments, the telepresence robot system further comprises a communication system configured to facilitate communication between the telepresence robot system local terminal and the remote telepresence robot.

In some embodiments, the local terminal further comprises at least one user input device and the user input device may be configured to allow a user to provide an indication of a desired destination of the remote telepresence robot on at least one of the plan view map and the video feed from the imaging system of the remote telepresence robot; and the

command transmitted to the remote telepresence robot comprises the desired destination.

In some embodiments, the sequence of coordinates forming the robot path may be based at least in part on tagging information associated with the at least one tag.

In some embodiments, the instructions executable by the processor are further configured to cause the processor to determine a sequence of coordinates relative to the plan view map to create a robot path between the current position of the remote telepresence robot and the desired destination of the remote telepresence robot and the command transmitted to the remote telepresence robot comprises the sequence of coordinates forming the robot path.

In some embodiments, the instructions executable by the processor are further configured to cause the processor to display the sequence of coordinates forming the robot path overlaid on the plan view map.

In some embodiments, the instructions executable by the processor are further configured to cause the processor to determine a distortion (e.g., a coordinate transformation between a two-dimensional coordinate system and a three-dimensional coordinate system) between the plan view map and the video feed received from the imaging system of the remote telepresence robot; apply the distortion to the sequence of coordinates forming the robot path to determine corresponding video coordinates and perspective data describing a location and perspective of the sequence of coordinates relative to the video feed; and display a three-dimensional rendition of the sequence of coordinates forming the robot path overlaid on the video feed.

In some embodiments, the three-dimensional rendition of the sequence of coordinates forming the robot path may be overlaid on the video feed with respect to a floor detected in the video feed.

In some embodiments, the instructions executable by the processor are further configured to cause the processor to receive a sequence of coordinates relative to the plan view map from a navigation system of the remote telepresence robot, the sequence of coordinates forming a robot path between the current position of the remote telepresence robot and a desired destination of the remote telepresence robot; and display the sequence of coordinates forming the robot path overlaid on the plan view map.

In some embodiments, the instructions executable by the processor are further configured to cause the processor to determine a distortion (e.g., a coordinate transformation between a two-dimensional coordinate system and a three-dimensional coordinate system) between the plan view map and the video feed received from the imaging system of the remote telepresence robot; apply the distortion to the sequence of coordinates forming the robot path to determine corresponding video coordinates and perspective data describing the location and perspective of the sequence of coordinates relative to the video feed; and display a three-dimensional rendition of the sequence of coordinates forming the robot path overlaid on the video feed.

In some embodiments, the three-dimensional rendition of the sequence of coordinates forming the robot path may be overlaid on the video feed with respect to a floor detected in the video feed.

In some embodiments, the tag information comprises information regarding one of: an availability of a wireless communication signal, a speed the remote telepresence robot should travel, a location of a point of interest, a location of a person, a location of a docking station, a location of a rest area, a location of a glass wall, a location of a ramp, a location of an object, an optimal route to

navigate a tight area, an optimal route to navigate a congested area, and an action a remote telepresence robot should execute.

In some embodiments, the tag information may relate to a position, a path, and/or a volume, and the control system may be configured to execute an action relative to the position, the path, and/or the volume.

In some embodiments, the instructions executable by the processor are further configured to cause the processor to receive coordinates on the plan view map of an obstacle detected by a sensor system of the remote telepresence robot.

In some embodiments, the plan view map and the plurality of tags are stored remotely.

In some embodiments, the plan view map and the plurality of tags are stored within the remote telepresence robot.

In some embodiments, the instructions executable by the processor are further configured to cause the processor to determine a distortion (e.g., a coordinate transformation between a two-dimensional coordinate system and a three-dimensional coordinate system) between the plan view map and the video feed received from the imaging system of the remote telepresence robot; and generate a hybrid map view comprising a blended view of the plan view map and the video feed from the imaging system of the remote telepresence robot.

In some embodiments, the hybrid map view comprises a three-dimensional representation of the plan view map overlaid on the video feed.

In some embodiments, the telepresence robot system local terminal further comprises at least one user input device and the instructions executable by the processor are further configured to cause the processor to receive a request via the at least one input device for a rendered look ahead for a virtual location of the remote telepresence robot on the plan view map; determine a distortion (e.g., a coordinate transformation between a two-dimensional coordinate system and a three-dimensional coordinate system) between the plan view map and the video feed received from the imaging system of the remote telepresence robot; and generate a virtual three-dimensional video feed based on a virtual location of the remote telepresence robot; and display the virtual three-dimensional video feed based on the virtual location of the remote telepresence robot.

In some embodiments, the tag information of the at least one tag comprises a set of coordinates with respect to the plan view map defining a protected region, and the tag annotation of the at least one tag may be configured to indicate the presence of a protected region.

In some embodiments, the instructions executable by the processor are further configured to cause the processor to receive a request to create a new tag; associate tag coordinates describing a relative location of the new tag and tag information, which may include a tag annotation with the new tag; and display a rendition of the tag annotation of the new tag on at least one of the plan view map and the video feed using the tag coordinates.

In some embodiments, the request to create the new tag may be generated by the remote telepresence robot.

In some embodiments, the request to create the new tag may be automatically generated based on a detected object in the video feed.

In some embodiments, the new tag may be a temporary tag configured to expire once the detected object is no longer present in the video feed.

In some embodiments, the object may be a person and the tag information of the new tag comprises identification information associated with the person.

In some embodiments, the object may be a person and the tag information of the new tag comprises potential actions the remote telepresence robot can execute with respect to the person.

In some embodiments, the request to create the new tag may be generated by a user input device in communication with the telepresence robot system local terminal.

In some embodiments, the request to create the new tag is made with respect to the video feed.

In some embodiments, the request to create the new tag is made with respect to the plan view map.

In some embodiments, the request to create a new tag is made with respect to the current position of the remote telepresence robot.

In some embodiments, the tag information comprises information regarding one of: an availability of a wireless communication signal, a speed the remote telepresence robot should travel, a location of a point of interest, a location of a person, a location of a docking station, a location of a rest area, a location of a glass wall, a location of a ramp, a location of an object, an optimal route to navigate a tight area, an optimal route to navigate a congested area, and an action a remote telepresence robot should execute.

In other embodiments, a telepresence robot may communicate with a remote terminal. The telepresence robot may include a drive system configured to move the telepresence robot according to drive instructions; a control system in communication with the drive system, the control system configured to generate drive instructions to cause the drive system to move the telepresence robot; an imaging system in communication with the control system; a mapping module in communication with the control system, the mapping module configured to access a map data source, the map data source comprising a plan view map representative of robot-navigable areas of a robot operating surface; and a plurality of tags, each tag being a data structure comprising tag coordinates describing the relative location of the tag and tag information, which may include a tag annotation; a positioning system in communication with the control system configured to provide a current position with respect to the plan view map; a tag identification system configured to identify at least one tag relevant to a navigation path of the telepresence robot; and a communication system configured to facilitate communication between the control system and a remote terminal, and the control system may be configured to execute an action based on an identified tag whose tag information comprises a telepresence robot action modifier.

In some embodiments, the tagging information for the identified tag comprises instructions regarding one of a time and a location on the plan view map that the control system should execute the action.

In some embodiments, the control system may be configured to transmit a video feed from the imaging system to the remote terminal via the communication system and the control system may be configured to receive an indication of a desired destination on the plan view map from the remote terminal via the communication system.

In some embodiments, the telepresence robot may further comprise: a plurality of sensors configured to identify obstacles in the vicinity of the telepresence robot and an obstacle avoidance system in communication with the plurality of sensors and in communication with the control system, where the control system may be further configured

to generate additional drive instructions to avoid obstacles in the vicinity of the telepresence robot.

In some embodiments, the plurality of sensors comprises at least one of a proximity sensor, a contact sensor, an odometry sensor, and a three-dimensional image sensor.

In some embodiments, the plurality of sensors may comprise a three-dimensional image sensor that forms a point cloud, including a three-dimensional occupancy of obstacles, and the drive instructions may be configured to avoid the three-dimensional occupancy of the obstacles.

In some embodiments, the telepresence robot may further comprise: a map generation system in communication with the control system, the map generation system configured to autonomously create the plan view map of the robot operating surface, where the control system generates drive instructions to cause the telepresence robot to move throughout the robot operating surface and obtain a plurality of measurements, and the map generation system uses the plurality of measurements to generate the plan view map.

In some embodiments, the telepresence robot may further comprise a navigation system configured to generate a navigation path comprising a sequence of coordinates from the current position on the plan view map to the desired destination on the plan view map.

In some embodiments, the telepresence robot may transmit coordinates relative to the plan view map of a detected obstacle to the remote terminal via the communication system.

In some embodiments, the sequence of coordinates forming the navigation path may be based at least in part on tagging information associated with the identified tag.

In some embodiments, the navigation system is configured to generate the navigation path by selecting a navigation path from a plurality of potential navigation paths, and the tags relevant to the navigation path of the telepresence robot are associated with the plurality of potential navigation paths, and the navigation system is configured to select the navigation path based at least in part on the identified relevant tags.

In some embodiments, the sequence of coordinates forming the navigation path is transmitted via the communication system to the remote terminal.

In some embodiments, the telepresence robot may be configured to create a new tag using the sequence of coordinates forming the navigation path, such that the new tag comprises the sequence of coordinates, tagging information related to the navigation path, and a tag annotation related to the navigation path.

In some embodiments, the tag information of each of the plurality of tags comprises information regarding one of: an availability of a wireless communication signal, a speed the remote telepresence robot should travel, a location of a point of interest, a location of a person, a location of a docking station, a location of a rest area, a location of a glass wall, a location of a ramp, a location of an object, an optimal route to navigate a tight area, an optimal route to navigate a congested area, and an action a remote telepresence robot should execute.

In some embodiments, the control system may be further configured to receive a navigation path from the current position on the plan view map to the desired destination on the plan view map and the control system may be further configured to generate drive instructions to cause the drive system to move the telepresence robot to the desired destination based on the navigation path.

In some embodiments, the communication system may be configured to detect a disruption in communication between

the telepresence robot and a remote terminal, wherein the control system may be further configured to continue to generate drive instructions to cause the telepresence robot to autonomously move to the desired destination during the disruption in communication.

In some embodiments, the map data source may be stored remotely, such that the mapping module may be configured to access the map data source via the communication system.

In some embodiments, the map data source may be stored within the telepresence robot, such that the mapping module may be configured to access an internal map data source.

In some embodiments, the internal map data source may be synced with a remotely stored map data source.

In some embodiments, the positioning system may be further configured to provide a robot pose relative to the plan view map.

In some embodiments, the telepresence robot may be configured to create a new tag by: associating tag coordinates describing the relative location of the new tag with respect to one of the plan view map and a video feed generated by the imaging system; associating tag information with the new tag; and associating a tag annotation with the new tag.

In some embodiments, the new tag may be created in response to the telepresence robot detecting an object in the video feed.

In some embodiments, the object may be a person and the tag information of the new tag comprises identification information associated with the person.

In some embodiments, the object may be a person and the tag information of the new tag comprises potential actions the remote telepresence robot can execute with respect to the person.

In some embodiments, the tag information comprises information regarding one of: an availability of a wireless communication signal, a speed the remote telepresence robot should travel, a location of a point of interest, a location of a person, a location of a docking station, a location of a rest area, a location of a glass wall, a location of a ramp, a location of an object, an optimal route to navigate a tight area, an optimal route to navigate a congested area, and an action a remote telepresence robot should execute.

In some embodiments, the telepresence robot system may further comprise: an RFID reader in communication with the positioning system, where the positioning system associates a plurality of RFID chips with a corresponding plurality of coordinates on the plan view map, and the positioning system may be configured to determine the current position of the telepresence robot based at least in part on the location of one or more RFID chips within range of the RFID reader.

Various methods of control may be employed in the present systems and methods. For example, a telepresence robot system local terminal may comprise: an electronic display; a processor in communication with the electronic display interface; a memory in communication with the processor, the memory comprising instructions executable by the processor configured to cause the processor to: retrieve at least a portion of a plan view map representative of robot-navigable areas of a robot operating surface; receive a video feed from an imaging system of the remote telepresence robot at a first perspective; receive a current position from a positioning system of the remote telepresence robot with respect to a plan view map; display the video feed from the imaging system of the remote telepresence robot; display the plan view map with an indication of the

current position of the telepresence robot on the plan view map; transmit a command to the remote telepresence robot; and a user input device in communication with the processor, the user input device configured to allow a user to select a movement for a remote telepresence robot, the selection of the movement comprising selecting a destination of the remote telepresence robot with respect to the video feed; with respect to the plan view map; and by incrementally advancing the remote telepresence robot in one of at least four possible directions relative to the current position of the remote telepresence robot.

In some embodiments, the selection of the movement comprises selecting an alternative perspective of the video feed by selecting a point within the video feed. This mode would likely be used for intermediate distances to get to locations within view on the video feed.

In some embodiments, selection of the movement comprises selecting an alternative perspective of the video feed by selecting a point on the plan view map. This mode would likely be used for farther distances (e.g., down hallways, between rooms, etc.) to locations not within view on the video feed. In some embodiments, selection of the movement comprises using a joystick or meta joystick in manual control. This mode would likely be used for micro/finer adjustments, e.g., within a room in close proximity to humans/patients.

In some embodiments, the selection of the movement comprises selecting an alternative perspective of the video feed by incrementally panning or tilting the imaging system while the remote telepresence robot remains in the current position.

In some embodiments, wherein the selection of the movement may relate to rotating one of a lower portion of the remote telepresence robot and an upper portion of the remote telepresence robot.

In some embodiments, there will be a way to switch between modes, e.g. multi-modal user interface wherein one can select to control either head/imaging system movement or movement of the base/lower portion of the remote telepresence robot.

In some embodiments when control of head/imaging system movement is selected there may be options to select either position-based box-zoom head motion via mouse or velocity-based head motion via mouse.

In some embodiments when control of base/lower portion of the remote telepresence robot is selected there may be options to select from one of the following: (1) click-on-map, i.e. top down map view and click on target destination or select from destination list; (2) click-on-video, i.e. position-based control that enables click on location in the video and robot drives there; (3) joystick or meta joystick, e.g., mouse velocity-based control or arrows specifying forward, left, right, etc.

In some embodiments the functionality/information needed to be accessed by user at all times while robot base is moving includes: (1) remote view, i.e., where the robot is headed (view should be large enough to provide meaningful visual information for user to operate safely); (2) for supervisory control modes, potential need for override capability to cancel/abort operation as needed.

In some embodiments, the instructions executable by the processor are further configured to cause the processor to receive a selection of a destination of the remote robot from the user input device; determine a sequence of coordinates relative to the plan view map to create a navigation path between the current position of the remote telepresence robot and the selected destination of the remote telepresence

robot; and transmit a command to the remote telepresence robot comprising the sequence of coordinates forming the navigation path.

In some embodiments, the instructions executable by the processor are further configured to cause the processor to display the sequence of coordinates forming the navigation path overlaid on the plan view map.

In some embodiments, the instructions executable by the processor are further configured to cause the processor to determine a distortion between the plan view map and the video feed received from the imaging system of the remote telepresence robot (e.g., a coordinate transformation between a two-dimensional coordinate system and a three-dimensional coordinate system); apply the distortion to the sequence of coordinates forming the navigation path to determine corresponding video coordinates and perspective data describing the location and perspective of the sequence of coordinates relative to the video feed; and display a three-dimensional rendition of the sequence of coordinates forming the navigation path overlaid on the video feed.

In some embodiments, the three-dimensional rendition of the sequence of coordinates forming the navigation path may be overlaid on the video feed with respect to a floor detected in the video feed.

In some embodiments, the instructions executable by the processor are further configured to cause the processor to receive a selection of a destination of the remote robot from the user input device; transmit destination coordinates relative to the plan view map to the remote telepresence robot, the destination coordinates corresponding to the selected destination; receive a sequence of coordinates relative to the plan view map from a navigation system of the remote telepresence robot, the sequence of coordinates forming a navigation path between the current position of the remote telepresence robot and the desired destination of the remote telepresence robot; and display the sequence of coordinates forming the navigation path overlaid on the plan view map.

In some embodiments, the instructions executable by the processor are further configured to cause the processor to determine a distortion between the plan view map and the video feed received from the imaging system of the remote telepresence robot (e.g., a coordinate transformation between a two-dimensional coordinate system and a three-dimensional coordinate system); apply the distortion to the sequence of coordinates forming the navigation path to determine corresponding video coordinates and perspective data describing the location and perspective of the sequence of coordinates relative to the video feed; and display a three-dimensional rendition of the sequence of coordinates forming the navigation path overlaid on the video feed.

In some embodiments, the three-dimensional rendition of the sequence of coordinates forming the navigation path may be overlaid on the video feed with respect to a floor detected in the video feed.

In some embodiments, the instructions executable by the processor are further configured to cause the processor to receive coordinates on the plan view map of an obstacle detected by a sensor system of the remote telepresence robot.

In some embodiments, the plan view map is stored remotely.

In some embodiments, the plan view map is stored within the remote telepresence robot.

In some embodiments, the instructions executable by the processor are further configured to cause the processor to determine a distortion between the plan view map and the video feed received from the imaging system of the remote

telepresence robot (e.g., a coordinate transformation between a two-dimensional coordinate system and a three-dimensional coordinate system); and generate a hybrid map view comprising a blended view of the plan view map and the video feed from the imaging system of the remote telepresence robot.

In some embodiments, the hybrid map view comprises a three-dimensional representation of the plan view map overlaid on the video feed.

In some embodiments, the instructions executable by the processor are further configured to cause the processor to receive a request via the input device for a rendered look-ahead for a virtual location of the remote telepresence robot on the plan view map determine a distortion between the plan view map and the video feed received from the imaging system of the remote telepresence robot (e.g., a coordinate transformation between a two-dimensional coordinate system and a three-dimensional coordinate system); and generate a virtual three-dimensional video feed based on a virtual location of the remote telepresence robot; and display the virtual three-dimensional video feed based on the virtual location of the remote telepresence robot.

In some embodiments, a robot may be configured to unwind and/or to control an upper portion and a lower portion independently in order to appear human-like. For example, a telepresence robot may comprise: an upper portion; a lower portion rotatably connected to the upper portion; a drive system configured to move the telepresence robot according to drive instructions; a control system in communication with the drive system, the control system configured to generate drive instructions to cause the drive system to move the telepresence robot; a rotation system configured to rotate the robot from a first heading to a second heading by rotating the upper portion and the lower portion independently.

In some embodiments, the rotation system may be configured to rotate the robot toward a second heading by rotating the upper portion of the robot toward the second heading; detecting that the upper portion of the robot has reached a panning limit of the upper portion of the robot relative to the lower portion of the robot; begin rotating the lower portion of the robot toward the second heading at the panning limit of the upper portion of the robot; detect that the upper portion of the robot has reached the second heading; and continue rotating the lower portion of the robot toward the second heading while simultaneously counter-rotating the upper portion of the robot, such that the upper portion of the robot maintains the second heading.

In some embodiments, the panning limit may be reached when the upper portion cannot physically rotate anymore with respect to the lower portion of the robot.

In some embodiments, the panning limit may be reached when the upper portion is misaligned with respect to the lower portion a predefined number of rotation degrees.

In some embodiments, the panning limit may be a function of the number of degrees the upper portion is misaligned with respect to the lower portion and the length of time the upper portion has been misaligned with respect to the lower portion.

In some embodiments, the rotation system may be configured to rotate the robot toward a second heading by rotating the upper portion of the robot toward the second heading at a first rotational velocity; rotating the lower portion of the robot toward the second heading at a second rotation velocity; detect that the upper portion of the robot has reached the second heading; and continue rotating the lower portion of the robot toward the second heading while

simultaneously counter-rotating the upper portion of the robot, such that the upper portion of the robot maintains the second heading.

In some embodiments the telepresence robot may further comprise an imaging system in communication with the control system and a positioning system in communication with the control system configured to provide a current position of the robot relative to a plan view map and a current alignment of the upper portion with respect to the plan view map, where the control system may be configured to transmit a video feed from the imaging system, the current position of the robot, and the current alignment of the upper portion to a remote terminal, such that the remote terminal can determine a distortion between the plan view map and the video feed received from the imaging system of the remote telepresence robot (e.g., a coordinate transformation between a two-dimensional coordinate system and a three-dimensional coordinate system); apply the distortion to a tag having coordinates associated with the plan view map in order to determine corresponding video coordinates and perspective data describing the location and perspective of the tag relative to the video feed; and display a three-dimensional rendition of the tag overlaid on the video feed using the video coordinates.

The above described embodiments are described from the perspective of a robot and/or a local terminal. It should be apparent to one of skill in the art that the embodiments described above could be implemented as systems, adapted as methods performed by a system, or embodied in a computer-readable medium that could be executed by a system. For example, a method for changing a heading of a robot may comprise transmitting a heading to a control system of a robot, the control system of the robot in communication with a drive system configured to move the robot according to drive instructions and rotating an upper portion of the robot toward the heading independently from the lower portion of the robot.

In some embodiments, a method for controlling a remote telepresence robot may comprise retrieving at least a portion of a plan view map representative of robot-navigable areas of a robot operating surface; retrieving at least one of a plurality of tags, each of the plurality of tags comprising tag coordinates describing the relative location of the tag and tag information; receiving a video feed from an imaging system of a remote telepresence robot; receiving positioning information associated with a current position of the remote telepresence robot; displaying, via an electronic display, the video feed from the imaging system of the remote telepresence robot; displaying, via the electronic display, a rendition of the tag information of the at least one tag on the video feed using the tag coordinates; and transmitting a command to the remote telepresence robot. A method for controlling a telepresence robot, comprising retrieving at least a portion of a plan view map; retrieving at least one of a plurality of tags, each tag being a data structure comprising tag coordinates describing the relative location of the tag and tag information; determining a current position relative to the plan view map; identifying at least one tag of the plurality of tags relevant to a navigation path of the telepresence robot; executing an action based on the identified tag whose tag information comprises a telepresence action modifier.

In some embodiments, a method for controlling a telepresence robot may comprise retrieving at least a portion of a plan view map representative of robot-navigable areas of a robot operating surface; receiving a video feed from an imaging system of the remote telepresence robot at a first perspective; receiving positioning data associated with a

current position of the remote telepresence robot; displaying the video feed from the imaging system of the remote telepresence robot; and transmitting a command to the remote telepresence robot; and receiving a plurality of movement selections from a user input device movement, the movement selections made (1) with respect to the video feed; (2) with respect to the plan view map; and/or (3) by incrementally advancing the remote telepresence robot in a direction relative to the current position of the remote telepresence robot.

The details of one or more implementations of the disclosure are set forth in the accompanying drawings and the description below. Other aspects, features, and advantages will be apparent from the description and drawings, and from the claims.

DESCRIPTION OF DRAWINGS

FIG. 1 is a perspective view of an exemplary telepresence robot.

FIG. 2 is an elevated perspective view of an exemplary telepresence robot.

FIGS. 3A-3C are schematic views of exemplary telepresence robots.

FIG. 4A is a front perspective view of an exemplary base for a mobile human interface robot.

FIG. 4B is a rear perspective view of the base shown in FIG. 4A.

FIG. 4C is a top view of the base shown in FIG. 4A.

FIG. 4D is a top schematic view of an exemplary base for a telepresence robot.

FIG. 4E is a bottom perspective view of an exemplary drive system for a telepresence robot.

FIG. 4F is a top perspective view of the drive system shown in FIG. 4E.

FIG. 5 is a schematic view of an exemplary control system executed by a controller of a telepresence robot.

FIG. 6A provides a schematic view of an exemplary robot system including multiple robots in communication with robot endpoint servers.

FIG. 6B illustrates a teleoperation software application executed by a robot or a terminal.

FIG. 6C illustrates one embodiment of a screen shot of a user interface for controlling navigation of a semi-autonomous telepresence robot.

FIG. 6D illustrates a screen shot, in which the relative area of the screen devoted to the map window is increased.

FIG. 7 is a schematic view of an exemplary robot system architecture.

FIG. 8A is a schematic view of an exemplary occupancy map.

FIG. 8B is a schematic view of a telepresence robot having a field of view of a scene in a working area.

FIG. 8C is a schematic view of an exemplary layout map.

FIG. 8D is a schematic view of an exemplary robot map corresponding to the layout map shown in FIG. 8C.

FIG. 8E provides an exemplary arrangement of operations for operating a telepresence robot to navigate about an environment using a layout map and a robot map.

FIG. 8F illustrates a method for using a robot location and perspective to determine a distortion between a video feed and a plan view map.

FIG. 9A is schematic view of an exemplary remote video view from a robot positioned in a hallway.

FIG. 9B is a schematic view of an exemplary hybrid map incorporating the remote video view shown in FIG. 9A, together with a map indicating room numbers.

13

FIG. 10A provides an exemplary remote view of a remote video window of a telepresence software application.

FIG. 10B is a schematic view of an exemplary map of the area shown by the remote view of FIG. 10A.

FIG. 10C is a schematic view of an exemplary look-ahead view of a telepresence software application.

FIG. 10D is a schematic view of the map shown in FIG. 10B with a robot icon and a corresponding camera field of view.

FIG. 10E is a schematic view of an exemplary look-ahead view of a telepresence software application.

FIG. 10F is a schematic view of the map shown in FIG. 10B with a robot icon and a corresponding camera field of view.

FIG. 10G provides an exemplary arrangement of operations for a look-ahead routine of a telepresence software application.

FIG. 11A is a schematic view of an exemplary user interface that allows a user to specify a robot destination within an identified navigable area.

FIG. 11B provides an exemplary arrangement of operations for a method of navigating a robot to a destination.

FIG. 11C is a schematic view of an exemplary user interface prompting a user that a ramp was selected as a robot destination.

FIG. 11D is a schematic view of an exemplary user interface prompting a user that an obstacle was selected as a robot destination.

FIG. 12 is a schematic view of an exemplary user interface that allows a user to specify a robot drive path within an identified navigable area.

FIG. 13 is a schematic view of an exemplary user interface that incorporates hyper-tags and context sensitive commands.

FIG. 14 is a perspective view of an exemplary telepresence robot maintaining a sensor field of view on a person.

FIG. 15A is a schematic view of an exemplary three-dimensional map view that includes hyper-tags.

FIG. 15B is a schematic view of an exemplary two-dimensional map view that include hyper-tags.

FIG. 16A is a schematic view of an exemplary robot system.

FIG. 16B is a schematic view of exemplary interactions with a map data source.

FIG. 16C is a schematic view of exemplary interactions between a robot control system and a map data source.

FIG. 16D is a schematic view of an exemplary robot system.

FIG. 17 is a schematic view of an exemplary user interface that includes an augmented overlay corresponding to a telepresence robot.

FIG. 18 is a schematic view of an exemplary sequence of robot actions.

FIG. 19 is a schematic view of an exemplary user interface having a screen indicator overlaid on a remote video feed received from a telepresence robot.

FIGS. 20A-20C provide an exemplary arrangement of operations for recovering from a loss of robot communications.

Like reference symbols in the various drawings indicate like elements.

DETAILED DESCRIPTION

Telepresence robots can interact or interface with humans to provide a number of services, such as a physician or healthcare worker providing remote medical consultation,

14

home assistance, commercial assistance, and more. In the example of home assistance, a telepresence robot can assist elderly people with everyday tasks, including, but not limited to, maintaining a medication regime, mobility assistance, communication assistance (e.g., video conferencing, telecommunications, Internet access, etc.), home or site monitoring (inside and/or outside), person monitoring, and/or providing a personal emergency response system (PERS). For commercial assistance, the telepresence robot can provide videoconferencing (e.g., in a hospital setting), a point of sale terminal, an interactive information/marketing terminal, etc.

Referring to FIGS. 1-3B, in some implementations, a telepresence robot 100 includes a robot body 110 (or chassis) that defines a forward drive direction F. The robot 100 also includes a drive system 200 (FIG. 4D), an interfacing module 300, and a sensor system 400, each supported by the robot body 110 and in communication with a controller 500 (FIG. 5) that coordinates operation and movement of the robot 100. A power source 105 (e.g., battery or batteries) can be carried by the robot body 110 and in electrical communication with, and deliver power to, each of these components, as necessary.

The robot body 110, in the examples shown, includes a base 120, at least one leg 130 extending upwardly from the base 120, and a torso 140 supported by the at least one leg 130. The base 120 may support the drive system 200. The robot body (lower portion) 110 also includes a neck 150 supported by the torso 140. The neck 150 supports a head (upper portion) 160, which supports at least a portion of the interfacing module 300. The base 120 includes enough weight (e.g., by supporting the power source 105 (batteries)) to maintain a low center of gravity CG_B of the base 120 and a low overall center of gravity CG_R of the robot 100 for maintaining mechanical stability.

Referring to FIGS. 2 and 4A-4C, in some implementations, the base 120 defines a trilaterally symmetric shape (e.g., a triangular shape from the top view). For example, the base 120 may include a base chassis 122 that supports a base body 124 having first, second, and third base body portions 124a, 124b, 124c corresponding to each leg of the trilaterally shaped base 120 (see e.g., FIG. 4A). Each base body portion 124a, 124b, 124c can be movably supported by the base chassis 122 so as to move independently with respect to the base chassis 122 in response to contact with an object. The trilaterally symmetric shape of the base 120 allows bump detection 360° around the robot 100. Each base body portion 124a, 124b, 124c can have an associated contact sensor (e.g., capacitive sensor, read switch, etc.) that detects movement of the corresponding base body portion 124a, 124b, 124c with respect to the base chassis 122.

In some implementations, the drive system 200 provides omni-directional and/or holonomic motion control of the robot 100. As used herein the term "omni-directional" refers to the ability to move in substantially any planar direction, i.e., side-to-side (lateral), forward/back, and rotational. These directions are generally referred to herein as x, y, and θ_z , respectively. Furthermore, the term "holonomic" is used in a manner substantially consistent with the literature use of the term and refers to the ability to move in a planar direction with three planar degrees of freedom, i.e., two translations and one rotation. Hence, a holonomic robot has the ability to move in a planar direction at a velocity made up of substantially any proportion of the three planar velocities (lateral, forward/back, and rotational), as well as the ability to change these proportions in a substantially continuous manner.

The robot **100** can operate in human environments (e.g., environments typically designed for bipedal, walking occupants) using wheeled mobility. In some implementations, the drive system **200** includes first, second, and third drive wheels **210a**, **210b**, **210c** equally spaced (i.e., trilaterally symmetric) about the vertical axis Z (e.g., 120 degrees apart); however, other arrangements are possible as well. Referring to FIG. 4D, the drive wheels **210a**, **210b**, **210c** may define a transverse arcuate rolling surface (i.e., a curved profile in a direction transverse or perpendicular to the rolling direction D_R), which may aid maneuverability of the holonomic drive system **200**. Each drive wheel **210a**, **210b**, **210c** is coupled to a respective drive motor **220a**, **220b**, **220c** that can drive the drive wheel **210a**, **210b**, **210c** in forward and/or reverse directions independently of the other drive motors **220a**, **220b**, **220c**. Each drive motor **220a-c** can have a respective encoder, which provides wheel rotation feedback to the controller **500**. In some examples, each drive wheel **210a**, **210b**, **210c** is mounted on or near one of the three points of an equilateral triangle and has a drive direction (forward and reverse directions) that is perpendicular to an angle bisector of the respective triangle end. Driving the trilaterally symmetric holonomic base **120** with a forward driving direction F allows the robot **100** to transition into non-forward drive directions for autonomous escape from confinement or clutter and then rotate and/or translate to drive along the forward drive direction F after the escape has been resolved.

Referring to FIGS. 4E and 4F, in some implementations, the drive system **200** includes first, second, third, and fourth drive wheels **210a-d** arranged in a square or rectangular configuration (e.g., equidistantly from the Z axis) from a top view. The drive system **200** may operate in a holonomic manner, allowing strafing. Each drive wheel **210a-d** is coupled to a respective drive motor **220a-d** that can drive the drive wheel **210a-d** in forward and/or reverse directions independently of the other drive motors **220a-d**. Each drive motor **220a-d** can have a respective encoder, which provides wheel rotation feedback to the controller **500**. A base chassis **122** supports the drive motors **220a-d** and the correspondingly coupled drive wheels **210a-d**.

In some examples, as illustrated in FIG. 2, the first drive wheel **210a** is arranged as a leading drive wheel along the forward drive direction F with the remaining two drive wheels **210b**, **210c** trailing behind. In this arrangement, to drive forward, the controller **500** may issue a drive command that causes the second and third drive wheels **210b**, **210c** to drive in a forward rolling direction at an equal rate while the first drive wheel **210a** slips along the forward drive direction F . Moreover, this drive wheel arrangement allows the robot **100** to stop short (e.g., incur a rapid negative acceleration against the forward drive direction F). This is due to the natural dynamic instability of the three-wheeled design. If the forward drive direction F were along an angle bisector between two forward drive wheels, stopping short would create a torque that would force the robot **100** to fall, pivoting over its two “front” wheels. Instead, traveling with one drive wheel **210a** forward naturally supports or prevents the robot **100** from toppling over forward, if there is need to come to a quick stop. When accelerating from a stop, however, the controller **500** may take into account a moment of inertia I of the robot **100** from its overall center of gravity CG_R .

In some implementations of the drive system **200**, each drive wheel **210a**, **210b**, **210c** has a rolling direction D_R radially aligned with a vertical axis Z , which is orthogonal to X and Y axes of the robot **100**. The first drive wheel **210a**

can be arranged as a leading drive wheel along the forward drive direction F with the remaining two drive wheels **210b**, **210c** trailing behind. In this arrangement, to drive forward, the controller **500** may issue a drive command that causes the first drive wheel **210a** to drive in a forward rolling direction and the second and third drive wheels **210b**, **210c** to drive at an equal rate as the first drive wheel **210a**, but in a reverse direction.

In other implementations, the drive system **200** can be arranged to have the first and second drive wheels **210a**, **210b** positioned such that an angle bisector of an angle between the two drive wheels **210a**, **210b** is aligned with the forward drive direction F of the robot **100**. In this arrangement, to drive forward, the controller **500** may issue a drive command that causes the first and second drive wheels **210a**, **210b** to drive in a forward rolling direction and an equal rate, while the third drive wheel **210c** drives in a reverse direction or remains idle and is dragged behind the first and second drive wheels **210a**, **210b**. To turn left or right while driving forward, the controller **500** may issue a command that causes the corresponding first or second drive wheel **210a**, **210b** to drive at a relatively quicker/slower rate. Other drive system arrangements can be used as well. The drive wheels **210a**, **210b**, **210c** may define a cylindrical, circular, elliptical, or polygonal profile.

Referring again to FIGS. 1-3B, the base **120** supports at least one leg **130** extending upward in the Z direction from the base **120**. The leg(s) **130** may be configured to have a variable height for raising and lowering the torso **140** with respect to the base **120**. In some implementations, each leg **130** includes first and second leg portions **132**, **134** that move with respect to each other (e.g., telescopic, linear, and/or angular movement). Rather than having extrusions of successively smaller diameter telescopically moving in and out of each other and out of a relatively larger base extrusion, the second leg portion **134**, in the examples shown, moves telescopically over the first leg portion **132**, thus allowing other components to be placed along the second leg portion **134** and potentially move with the second leg portion **134** to a relatively close proximity of the base **120**. The leg **130** may include an actuator assembly for moving the second leg portion **134** with respect to the first leg portion **132**. The actuator assembly **136** may include a motor driver in communication with a lift motor and an encoder, which provides position feedback to the controller.

Generally, telescopic arrangements include successively smaller diameter extrusions telescopically moving up and out of relatively larger extrusions at the base **120** in order to keep a center of gravity CG_Z of the entire leg **130** as low as possible. Moreover, stronger and/or larger components can be placed at the bottom to deal with the greater torques experienced at the base **120** when the leg **130** is fully extended. This approach, however, offers two problems. First, when the relatively smaller components are placed at the top of the leg **130**, any rain, dust, or other particulate tends to run or fall down the extrusions, infiltrating a space between the extrusions, thus obstructing nesting of the extrusions. This creates a very difficult sealing problem while still trying to maintain full mobility/articulation of the leg **130**. Second, it may be desirable to mount payloads or accessories on the robot **100**. One common place to mount accessories is at the top of the torso **140**. If the second leg portion **134** moves telescopically in and out of the first leg portion, accessories and components could only be mounted above the entire second leg portion **134**, if they need to move

with the torso **140**. Otherwise, any components mounted on the second leg portion **134** would limit the telescopic movement of the leg **130**.

By having the second leg portion **134** move telescopically over the first leg portion **132**, the second leg portion **134** provides additional payload attachment points that can move vertically with respect to the base **120**. This type of arrangement causes water or airborne particulate to run down the torso **140** on the outside of every leg portion **132**, **134** (e.g., extrusion) without entering a space between the leg portions **132**, **134**. This greatly simplifies sealing any joints of the leg **130**. Moreover, payload/accessory mounting features of the torso **140** and/or second leg portion **134** are always exposed and available no matter how the leg **130** is extended.

Referring to FIG. 2, the leg **130** supports the torso **140**, which may have a shoulder **142** extending over and above the base **120**. In the example shown, the torso **140** has a downward facing or bottom surface **144** (e.g., toward the base) forming at least part of the shoulder **142** and an opposite upward facing or top surface **146** (FIG. 3A), with a side surface **148** extending therebetween. The torso **140** may define various shapes or geometries, such as a circular or an elliptical shape having a central portion **141** supported by the leg(s) **130** and a peripheral free portion **143** that extends laterally beyond a lateral extent of the leg(s) **130**, thus providing an overhanging portion that defines the downward facing surface **144**. In some examples, the torso **140** defines a polygonal or other complex shape that defines a shoulder, which provides an overhanging portion that extends beyond the leg(s) **130** over the base **120**.

The robot **100** may include one or more accessory ports **170** (e.g., mechanical and/or electrical interconnect points) for receiving payloads. The accessory ports **170** can be located so that received payloads do not occlude or obstruct sensors of the sensor system **400** (e.g., on the bottom and/or top surfaces **144**, **146** of the torso **140**, etc.).

An external surface of the torso **140** may be sensitive to contact or touching by a user, so as to receive touch commands from the user. For example, when the user touches the top surface **146** of the torso **140**, the robot **100** responds by lowering a height of the torso with respect to the floor (e.g., by decreasing the height of the leg(s) **130** supporting the torso **140**). Similarly, when the user touches the bottom surface **144** of the torso **140**, the robot **100** responds by raising the torso **140** with respect to the floor (e.g., by increasing the height of the leg(s) **130** supporting the torso **140**). Moreover, upon receiving a user touch on forward, rearward, right or left portions of side surface **148** of the torso **140**, the robot **100** responds by moving in a corresponding direction of the received touch command (e.g., rearward, forward, left, and right, respectively). The external surface(s) of the torso **140** may include a capacitive sensor in communication with the controller that detects user contact.

Referring again to FIGS. 1-3B, the torso **140** supports the neck **150**, which provides panning and tilting of the head **160** with respect to the torso **140**. In the examples shown, the neck **150** includes a rotator **152** and a tilter **154**. The rotator **152** may provide a range of angular movement θ_R (e.g., about the Z axis) of between about 90° and about 360° . Other ranges are possible as well. Moreover, in some examples, the rotator **152** includes electrical connectors or contacts that allow continuous 360° rotation of the head **160** with respect to the torso **140** in an unlimited number of rotations while maintaining electrical communication between the head **160** and the remainder of the robot **100**. The tilter **154** may include the same or similar electrical

connectors or contacts allow rotation of the head **160** with respect to the torso **140** while maintaining electrical communication between the head **160** and the remainder of the robot **100**. The rotator **152** may include a rotator motor coupled to or engaging a ring (e.g., a toothed ring rack). The tilter **154** may move the head at an angle θ_T (e.g., about the Y axis) with respect to the torso **140** independently of the rotator **152**. In some examples that tilter **154** includes a tilter motor, which moves the head **160** between an angle θ_T of $\pm 90^\circ$ with respect to Z axis. Other ranges are possible as well, such as $\pm 45^\circ$, etc. The robot **100** may be configured so that the leg(s) **130**, the torso **140**, the neck **150**, and the head **160** stay within a perimeter of the base **120** for maintaining stable mobility of the robot **100**.

The head **160** may be sensitive to contact or touching by a user, so as to receive touch commands from the user. For example, when the user pulls the head **160** forward, the head **160** tilts forward with passive resistance and then holds the position. Moreover, if the user pushes/pulls the head **160** vertically downward, the torso **140** may lower (via a reduction in length of the leg **130**) the head **160**. The head **160** and/or neck **150** may include strain gauges and/or contact sensors **165** that sense user contact or manipulation.

In some implementations, the head **160** supports one or more portions of the interfacing module **300**. The head **160** may include a dock **302** for releasably receiving one or more computing tablets **310**, also referred to as a web pad or a tablet PC, each of which may have a touch screen **312**. The web pad **310** may be oriented forward, rearward or upward. In some implementations, web pad **310** includes a touch screen, optional I/O (e.g., buttons and/or connectors, such as micro-USB, etc.) a processor, and memory in communication with the processor. An exemplary web pad **310** includes the Apple iPad by Apple, Inc. In some examples, the web pad **310** functions as the controller **500** or assist the controller **500** in controlling the robot **100**. The touch screen may detect, monitor, and/or reproduce points of user touching thereon for receiving user inputs and providing a graphical user interface that is touch interactive. In some examples, the web pad **310** includes a touch screen caller that allows the user to find it when it has been removed from the robot **100**.

The interfacing module **300** may include a camera **320** disposed on the head **160** (see e.g., FIG. 3A), which can be used to capture video from an elevated vantage point of the head **160** (e.g., for videoconferencing). In the example shown in FIG. 2, the camera **320** is disposed on the neck **150**. In some examples, the camera **320** is operated only when the web pad **310** is detached or undocked from the head **160**. When the web pad **310** is attached or docked on the head **160** in the dock **302** (and optionally covering the camera **320**), the robot **100** may use a camera of the web pad **310** for capturing video. In such instances, the camera **320** may be disposed behind the docked web pad **310** and enter an active state when the web pad **310** is detached or undocked from the head **160** and an inactive state when the web pad **310** is attached or docked on the head **160**.

The robot **100** can provide videoconferencing (e.g., at 24 fps or higher) through the interface module **300** (e.g., using a web pad **310**, the camera **320**, the microphones **330**, and/or the speakers **340**). The videoconferencing can be multiparty. The robot **100** can provide eye contact between both parties of the videoconferencing by maneuvering the head **160** to face the user. Moreover, the robot **100** can have a gaze angle of $< 5^\circ$ (e.g., an angle away from an axis normal to the forward face of the head **160**). At least one three-dimensional image sensor **450** and/or the camera **320** on the robot

100 can capture life-size images including body language. The controller **500** can synchronize audio and video (e.g., with a difference of <50 ms). The camera **320** may be movable within at least 1° of freedom separately from the web pad **310**. The head **160** may include one or more speakers **340** so as to have sound emanate from the head **160** near the web pad **310** displaying the videoconferencing.

The interfacing module **300** may include a microphone **330** (or micro-phone array) for receiving sound inputs and one or more speakers **340** disposed on the robot body **110** for delivering sound outputs.

Referring to FIGS. 1-3C, to achieve reliable and robust autonomous movement, the sensor system **400** may include several different types of sensors which can be used in conjunction with one another to create a perception of the robot's environment sufficient to allow the robot **100** to make intelligent decisions about actions to take in that environment. The sensor system **400** may include one or more types of sensors supported by the robot body **110**, which may include obstacle detection obstacle avoidance (ODOA) sensors, communication sensors, navigation sensors, etc. For example, these sensors may include, but are not limited to, proximity sensors, contact sensors, three-dimensional imaging/depth map sensors, a camera (e.g., visible light and/or infrared camera), sonar, radar, Light Detection And Ranging (LIDAR), which can entail optical remote sensing that measures properties of scattered light to find range and/or other information of a distant target), Laser Detection and Ranging (LADAR), etc. In some implementations, the sensor system **400** includes ranging sonar sensors **410** (e.g., nine about a perimeter of the base **120**), proximity cliff detectors **420**, contact sensors **430** (FIG. 4A), a laser scanner **440**, one or more three-dimensional imaging/depth sensors **450**, and an imaging sonar **460**.

In some implementations, the sensor system **400** includes a set or an array of proximity sensors **410**, **420** in communication with the controller **500** and arranged in one or more zones or portions of the robot **100** (e.g., disposed on or near the base body portion **124a**, **124b**, **124c** of the robot body **110**) for detecting any nearby or intruding obstacles. The proximity sensors **410**, **420** may be converging infrared (IR) emitter-sensor elements, sonar sensors, ultrasonic sensors, and/or imaging sensors (e.g., 3D depth map image sensors) that provide a signal to the controller **500** when an object is within a given range of the robot **100**.

In the example shown in FIGS. 4A-4C, the robot **100** includes an array of sonar-type proximity sensors **410** disposed (e.g., substantially equidistant) around the base **124** of body **120** and arranged with an upward field of view. First, second, and third sonar proximity sensors **410a**, **410b**, **410c** are disposed on or near the first (forward) base body portion **124a**, with at least one of the sonar proximity sensors near a radially outermost edge **125a** of the first base **124a** of body **120**. Fourth, fifth, and sixth sonar proximity sensors **410d**, **410e**, **410f** are disposed on or near the second (right) base body portion **124b**, with at least one of the sonar proximity sensors near a radially outermost edge **125b** of the second base **124b** of body **120**. Seventh, eighth, and ninth sonar proximity sensors **410g**, **410h**, **410i** are disposed on or near the third (left) base body portion **124c**, with at least one of the sonar proximity sensors near a radially outermost edge **125c** of the third base **124c** of body **120**. This configuration provides at least three zones of detection.

In some examples, the set of sonar proximity sensors **410** (e.g., **410a-410i**) disposed around the base **124** of body **120** are arranged to point upward (e.g., substantially in the Z direction) and optionally angled outward away from the Z

axis, thus creating a detection curtain **412** around the robot **100**. Each sonar proximity sensor **410a-410i** may have a shroud or emission guide **414** that guides the sonar emission upward or at least not toward the other portions of the robot body **110** (e.g., so as not to detect movement of the robot body **110** with respect to itself). The emission guide **414** may define a shell or half-shell shape. In the example shown, the base **124** of body **120** extends laterally beyond the leg **130**, and the sonar proximity sensors **410** (e.g., **410a-410i**) are disposed on the base **124** of body **120** (e.g., substantially along a perimeter of the base **124** of body **120**) around the leg **130**. Moreover, the upward pointing sonar proximity sensors **410** are spaced to create a continuous or substantially continuous sonar detection curtain **412** around the leg **130**. The sonar detection curtain **412** can be used to detect obstacles having elevated lateral protruding portions, such as table tops, shelves, etc.

The upward looking sonar proximity sensors **410** provide the ability to see objects that are primarily in the horizontal plane, such as table tops. These objects, due to their aspect ratio, may be missed by other sensors of the sensor system, such as the laser scanner **440** or imaging sensors **450**, and as such, can pose a problem to the robot **100**. The upward viewing sonar proximity sensors **410** arranged around the perimeter of the base **120** provide a means for seeing or detecting those type of objects/obstacles. Moreover, the sonar proximity sensors **410** can be placed around the widest points of the base perimeter and angled slightly outwards, so as not to be occluded or obstructed by the torso **140** or head **160** of the robot **100**, thus not resulting in false positives for sensing portions of the robot **100** itself. In some implementations, the sonar proximity sensors **410** are arranged (upward and outward) to leave a volume about the torso **140** outside of a field of view of the sonar proximity sensors **410** and thus free to receive mounted payloads or accessories, such as the basket **360**. The sonar proximity sensors **410** can be recessed into the base body **124** to provide visual concealment and no external features to snag on or hit obstacles.

The sensor system **400** may include one or more sonar proximity sensors **410** (e.g., a rear proximity sensor **410j**) directed rearward (e.g., opposite to the forward drive direction F) for detecting obstacles while backing up. The rear sonar proximity sensor **410j** may include an emission guide **414** to direct its sonar detection field **412**. Moreover, the rear sonar proximity sensor **410j** can be used for ranging to determine a distance between the robot **100** and a detected object in the field of view of the rear sonar proximity sensor **410j** (e.g., as "back-up alert"). In some examples, the rear sonar proximity sensor **410j** is mounted recessed within the base **124** of body **120** so as not to provide any visual or functional irregularity in the housing form.

Referring to FIGS. 2 and 4B, in some implementations, the robot **100** includes cliff proximity sensors **420** arranged near or about the drive wheels **210a**, **210b**, **210c**, so as to allow cliff detection before the drive wheels **210a**, **210b**, **210c** encounter a cliff (e.g., stairs). For example, a cliff proximity sensors **420** can be located at or near each of the radially outermost edges **125a-c** of the base bodies **124a-c** and in locations therebetween. In some cases, cliff sensing is implemented using infrared (IR) proximity or actual range sensing, using an infrared emitter **422** and an infrared detector **424** angled toward each other so as to have overlapping emission and detection fields, and hence a detection zone, at a location where a floor should be expected. IR proximity sensing can have a relatively narrow field of view, may depend on surface albedo for reliability, and can have varying range accuracy from surface to surface. As a result,

multiple discrete sensors can be placed about the perimeter of the robot **100** to adequately detect cliffs from multiple points on the robot **100**. Moreover, IR proximity based sensors typically cannot discriminate between a cliff and a safe event, such as just after the robot **100** climbs a thresh-

old.

The cliff proximity sensors **420** can detect when the robot **100** has encountered a falling edge of the floor, such as when it encounters a set of stairs. The controller **500** (executing a control system) may execute behaviors that cause the robot **100** to take an action, such as changing its direction of travel, when an edge is detected. In some implementations, the sensor system **400** includes one or more secondary cliff sensors (e.g., other sensors configured for cliff sensing and optionally other types of sensing). The cliff detecting proximity sensors **420** can be arranged to provide early detection of cliffs, provide data for discriminating between actual cliffs and safe events (such as climbing over thresholds), and be positioned down and out so that their field of view includes at least part of the robot body **110** and an area away from the robot body **110**. In some implementations, the controller **500** executes cliff detection routine that identifies and detects an edge of the supporting work surface (e.g., floor), an increase in distance past the edge of the work surface, and/or an increase in distance between the robot body **110** and the work surface. This implementation allows: 1) early detection of potential cliffs (which may allow faster mobility speeds in unknown environments); 2) increased reliability of autonomous mobility since the controller **500** receives cliff imaging information from the cliff detecting proximity sensors **420** to know if a cliff event is truly unsafe or if it can be safely traversed (e.g., such as climbing up and over a threshold); 3) a reduction in false positives of cliffs (e.g., due to the use of edge detection versus the multiple discrete IR proximity sensors with a narrow field of view). Additional sensors arranged as “wheel drop” sensors can be used for redundancy and for detecting situations where a range-sensing camera cannot reliably detect a certain type of cliff.

Threshold and step detection allows the robot **100** to effectively plan for either traversing a climbable threshold or avoiding a step that is too tall. This can be the same for random objects on the work surface that the robot **100** may or may not be able to safely traverse. For those obstacles or thresholds that the robot **100** determines it can climb, knowing their heights allows the robot **100** to slow down appropriately, if deemed needed, to allow for a smooth transition in order to maximize smoothness and minimize any instability due to sudden accelerations. In some implementations, threshold and step detection is based on object height above the work surface along with geometry recognition (e.g., discerning between a threshold or an electrical cable versus a blob, such as a sock). Thresholds may be recognized by edge detection. The controller **500** may receive imaging data from the cliff detecting proximity sensors **420** (or another imaging sensor on the robot **100**), execute an edge detection routine, and issue a drive command based on results of the edge detection routine. The controller **500** may use pattern recognition to identify objects as well. Threshold detection allows the robot **100** to change its orientation with respect to the threshold to maximize smooth step climbing ability.

The proximity sensors **410**, **420** may function alone, or as an alternative, may function in combination with one or more contact sensors **430** (e.g., bump switches) for redundancy. For example, one or more contact or bump sensors **430** on the robot body **110** can detect if the robot **100**

physically encounters an obstacle. Such sensors may use a physical property such as capacitance or physical displacement within the robot **100** to determine when it has encountered an obstacle. In some implementations, each base body portion **124a**, **124b**, **124c** of the base **120** has an associated contact sensor **430** (e.g., capacitive sensor, read switch, etc.) that detects movement of the corresponding base body portion **124a**, **124b**, **124c** with respect to the base chassis **122** (see e.g., FIG. 4A). For example, each base **124a** of body **120-c** may move radially with respect to the Z axis of the base chassis **122**, so as to provide three-way bump detection.

Referring again to FIGS. 1-4C, in some implementations, the sensor system **400** includes a laser scanner **440** mounted on a forward portion of the robot body **110** and in communication with the controller **500**. In the examples shown, the laser scanner **440** is mounted on the base **124** of body **120** facing forward (e.g., having a field of view along the forward drive direction F) on or above the first base **124a** of body **120** (e.g., to have maximum imaging coverage along the drive direction F of the robot). Moreover, the placement of the laser scanner on or near the front tip of the triangular base **120** means that the external angle of the robotic base (e.g., 300°) is greater than a field of view **442** of the laser scanner **440** (e.g., $\sim 285^\circ$), thus preventing the base **120** from occluding or obstructing the detection field of view **442** of the laser scanner **440**. The laser scanner **440** can be mounted recessed within the base body **124** as much as possible without occluding its fields of view, to minimize any portion of the laser scanner sticking out past the base body **124** (e.g., for aesthetics and to minimize snagging on obstacles).

The laser scanner **440** scans an area about the robot **100** and the controller **500**, using signals received from the laser scanner **440**, and creates an environment map or object map of the scanned area. The controller **500** may use the object map for navigation, obstacle detection, and obstacle avoidance. Moreover, the controller **500** may use sensory inputs from other sensors of the sensor system **400** for creating an object map and/or for navigation.

In some examples, the laser scanner **440** is a scanning LIDAR, which may use a laser that quickly scans an area in one dimension, as a “main” scan line, and a time-of-flight imaging element that uses a phase difference or similar technique to assign a depth to each pixel generated in the line (returning a two-dimensional depth line in the plane of scanning). In order to generate a three-dimensional map, the LIDAR can perform an “auxiliary” scan in a second direction (for example, by “nodding” the scanner). This mechanical scanning technique can be complemented, if not supplemented, by technologies such as the “Flash” LIDAR/LADAR and “Swiss Ranger” type focal plane imaging element sensors, techniques which use semiconductor stacks to permit time of flight calculations for a full two-dimensional matrix of pixels to provide a depth at each pixel, or even a series of depths at each pixel (with an encoded illuminator or illuminating laser).

The sensor system **400** may include one or more three-dimensional image sensors **450** in communication with the controller **500**. If the three-dimensional image sensor **450** has a limited field of view, the controller **500** or the sensor system **400** can actuate the three-dimensional image sensor **450a** in a side-to-side scanning manner to create a relatively wider field of view to perform robust obstacle detection/obstacle avoidance (ODOA). Referring to FIGS. 1-3B, in some implementations, the robot **100** includes a scanning three-dimensional image sensor **450a** mounted on a forward portion of the robot body **110** with a field of view along the

forward drive direction F (e.g., to have maximum imaging coverage along the drive direction F of the robot). The scanning three-dimensional image sensor **450a** can be used primarily for ODOA. In the example shown, the scanning three-dimensional image sensor **450a** is mounted on the torso **140** underneath the shoulder **142** or on the bottom surface **144** and recessed within the torso **140** (e.g., flush or past the bottom surface **144**), as shown in FIG. 2, for example, to prevent user contact with the scanning three-dimensional image sensor **450a**. The scanning three-dimensional image sensor **450** can be arranged to aim substantially downward and away from the robot body **110**, so as to have a downward field of view **452** in front of the robot **100** for ODOA (e.g., with obstruction by the base **120** or other portions of the robot body **110**). Placement of the scanning three-dimensional image sensor **450a** on or near a forward edge of the torso **140** allows the field of view of the three-dimensional image sensor **450** (e.g., $\sim 285^\circ$) to be less than an external surface angle of the torso **140** (e.g., 300°) with respect to the three-dimensional image sensor **450**, thus preventing the torso **140** from occluding or obstructing the detection field of view **452** of the scanning three-dimensional image sensor **450a**. Moreover, the scanning three-dimensional image sensor **450a** (and associated actuator) can be mounted recessed within the torso **140** as much as possible without occluding its fields of view (e.g., also for aesthetics and to minimize snagging on obstacles). The distracting scanning motion of the scanning three-dimensional image sensor **450a** is not visible to a user, creating a less distracting interaction experience. Unlike a protruding sensor or feature, the recessed scanning three-dimensional image sensor **450a** will not tend to have unintended interactions with the environment (snagging on people, obstacles, etc.), especially when moving or scanning, as virtually no moving part extends beyond the envelope of the torso **140**.

In some implementations, the sensor system **400** includes additional three-dimensional image sensors **450** disposed on the base **124** of body **120**, the leg **130**, the neck **150**, and/or the head **160**. In the example shown in FIG. 1, the robot **100** includes three-dimensional image sensors **450** on the base **124** of body **120**, the torso **140**, and the head **160**. In the example shown in FIG. 3A, the robot **100** includes three-dimensional image sensors **450** on the leg **130**, the torso **140**, and the neck **150**. Other configurations are possible as well. One three-dimensional image sensor **450** (e.g., on the neck **150** and over the head **160**) can be used for people recognition, gesture recognition, and/or videoconferencing, while another three-dimensional image sensor **450** (e.g., on the base **120** and/or the leg **130**) can be used for navigation and/or obstacle detection and obstacle avoidance.

A forward facing three-dimensional image sensor **450** disposed on the neck **150** and/or the head **160** can be used for person, face, and/or gesture recognition of people about the robot **100**. For example, using signal inputs from the three-dimensional image sensor **450** on the head **160**, the controller **500** may recognize a user by creating a three-dimensional map of the viewed/captured user's face and comparing the created three-dimensional map with known three-dimensional images of people's faces and determining a match with one of the known three-dimensional facial images. Facial recognition may be used for validating users as allowable users of the robot **100**. Moreover, one or more of the three-dimensional image sensors **450** can be used for

determining gestures of a person viewed by the robot **100**, and optionally reacting based on the determined gesture(s) (e.g., hand pointing, waving, and/or hand signals). For example, the controller **500** may issue a drive command in response to a recognized hand pointing in a particular direction.

The three-dimensional image sensors **450** may be capable of producing the following types of data: (i) a depth map, (ii) a reflectivity based intensity image, and/or (iii) a regular intensity image. The three-dimensional image sensors **450** may obtain such data by image pattern matching, measuring the flight time and/or phase delay shift for light emitted from a source and reflected off of a target.

In some implementations, reasoning or control software, executable on a processor (e.g., of the robot controller **500**), uses a combination of algorithms executed using various data types generated by the sensor system **400**. The reasoning software processes the data collected from the sensor system **400** and outputs data for making navigational decisions on where the robot **100** can move without colliding with an obstacle, for example. By accumulating imaging data over time of the robot's surroundings, the reasoning software can in turn apply effective methods to selected segments of the sensed image(s) to improve depth measurements of the three-dimensional image sensors **450**. This may include using appropriate temporal and spatial averaging techniques.

The reliability of executing robot collision-free moves may be based on: (i) a confidence level built by high-level reasoning over time and (ii) a depth-perceptive sensor that accumulates three major types of data for analysis: (a) a depth image, (b) an active illumination image and (c) an ambient illumination image. Algorithms cognizant of the different types of data can be executed on each of the images obtained by the depth-perceptive image sensor **450**. The aggregate data may improve the confidence level compared to a system using only one of the kinds of data.

The three-dimensional image sensors **450** may obtain images containing depth and brightness data from a scene about the robot **100** (e.g., a sensor view portion of a room or work area) that contains one or more objects. The controller **500** may be configured to determine occupancy data for the object based on the captured reflected light from the scene. Moreover, the controller **500**, in some examples, issues a drive command to the drive system **200** based at least in part on the occupancy data to circumnavigate obstacles (i.e., the object in the scene). The three-dimensional image sensors **450** may repeatedly capture scene depth images for real-time decision-making by the controller **500** to navigate the robot **100** about the scene without colliding into any objects in the scene. For example, the speed or frequency in which the depth image data is obtained by the three-dimensional image sensors **450** may be controlled by a shutter speed of the three-dimensional image sensors **450**. In addition, the controller **500** may receive an event trigger (e.g., from another sensor component of the sensor system **400**, such as proximity sensor **410**, **420**, notifying the controller **500** of a nearby object or hazard. The controller **500**, in response to the event trigger, can cause the three-dimensional image sensors **450** to increase a frequency at which depth images are captured and occupancy information is obtained.

In some implementations, the robot includes a sonar scanner **460** for acoustic imaging of an area surrounding the robot **100**. In the examples shown in FIGS. 1 and 2, the sonar scanner **460** is disposed on a forward portion of the base **124** of body **120**.

Referring to FIGS. 1-3B, in some implementations, the robot 100 uses the laser scanner or laser range finder 440 for redundant sensing, as well as a rear-facing sonar proximity sensor 410j for safety, both of which are oriented parallel to the ground G. The robot 100 may include first and second three-dimensional image sensors 450a, 450b (depth cameras) to provide robust sensing of the environment around the robot 100. The first three-dimensional image sensor 450a is mounted on the torso 140 and pointed downward at a fixed angle to the ground G. By angling the first three-dimensional image sensor 450a downward, the robot 100 receives dense sensor coverage in an area immediately forward or adjacent to the robot 100, which is relevant for short-term travel of the robot 100 in the forward direction. The rear-facing sonar 410j provides object detection when the robot travels backward. If backward travel is typical for the robot 100, the robot 100 may include a third 3D image sensor 450 facing downward and backward to provide dense sensor coverage in an area immediately rearward or adjacent to the robot 100.

The second three-dimensional image sensor 450b is mounted on the head 160, which can pan and tilt via the neck 150. The second three-dimensional image sensor 450b can be useful for remote driving since it allows a human operator to see where the robot 100 is going. The neck 150 enables the operator tilt and/or pan the second three-dimensional image sensor 450b to see both close and distant objects. Panning the second three-dimensional image sensor 450b increases an associated horizontal field of view. During fast travel, the robot 100 may tilt the second three-dimensional image sensor 450b downward slightly to increase a total or combined field of view of both three-dimensional image sensors 450a, 450b, and to give sufficient time for the robot 100 to avoid an obstacle (since higher speeds generally mean less time to react to obstacles). At slower speeds, the robot 100 may tilt the second three-dimensional image sensor 450b upward or substantially parallel to the ground G to track a person that the robot 100 is meant to follow. Moreover, while driving at relatively low speeds, the robot 100 can pan the second three-dimensional image sensor 450b to increase its field of view around the robot 100. The first three-dimensional image sensor 450a can stay fixed (e.g., not moved with respect to the base 120) when the robot is driving to expand its perceptual range. Additionally and/or alternatively, the first three-dimensional image sensor 450a can scan at low speeds in order to detect potential obstacles around the robot when it is maneuvering. In some examples, the height of the first three-dimensional image sensor 450a can be adjusted upward, such as through the use of a Z-lift, in order to optimize the field of view of the first three-dimensional sensor 450a.

In some implementations, at least one of three-dimensional image sensors 450 can be a volumetric point cloud imaging device (such as a speckle or time-of-flight camera) positioned on the robot 100 at a height of greater than one or two feet above the ground (or at a height of about one or two feet above the ground) and directed to obtain a point cloud from a volume of space including a floor plane in a direction of movement of the robot (via the omni-directional drive system 200). In the examples shown in FIGS. 1 and 3, the first three-dimensional image sensor 450a can be positioned on the base 120 at height of greater than one or two feet above the ground and aimed along the forward drive direction F to capture images (e.g., volumetric point cloud) of a volume including the floor while driving (e.g., for obstacle detection and obstacle avoidance). The second three-dimensional image sensor 450b is shown mounted on the head 160 (e.g., at a height greater than about three or four

feet above the ground), so as to obtain skeletal recognition and definition point clouds from a volume of space adjacent the robot 100. The controller 500 may execute skeletal/digital recognition software to analyze data of the captured volumetric point clouds.

Referring to FIGS. 3A-4C, the sensor system 400 may include an inertial measurement unit (IMU) 470 in communication with the controller 500 to measure and monitor a moment of inertia of the robot 100 with respect to the overall center of gravity CG_R of the robot 100.

The controller 500 may monitor any deviation in feedback from the IMU 470 from a threshold signal corresponding to normal unencumbered operation. For example, if the robot begins to pitch away from an upright position, it may be “clotheslined” or otherwise impeded, or someone may have suddenly added a heavy payload. In these instances, it may be necessary to take urgent action (including, but not limited to, evasive maneuvers, recalibration, and/or issuing an audio/visual warning) in order to assure safe operation of the robot 100.

Since robot 100 may operate in a human environment, it may interact with humans and operate in spaces designed for humans (and without regard for robot constraints). The robot 100 can limit its drive speeds and accelerations when in a congested, constrained, or highly dynamic environment, such as at a cocktail party or busy hospital. However, the robot 100 may encounter situations where it is safe to drive relatively fast, as in a long empty corridor, but yet be able to decelerate suddenly, as when something crosses the robot’s motion path.

When accelerating from a stop, the controller 500 may take into account a moment of inertia of the robot 100 from its overall center of gravity CG_R to prevent robot tipping. The controller 500 may use a model of its pose, including its current moment of inertia. When payloads are supported, the controller 500 may measure a load impact on the overall center of gravity CG_R and monitor movement of the robot moment of inertia. For example, the torso 140 and/or neck 150 may include strain gauges to measure strain. If this is not possible, the controller 500 may apply a test torque command to the drive wheels 210 and measure actual linear and angular acceleration of the robot using the IMU 470, in order to experimentally determine safe limits.

During a sudden deceleration, a commanded load on the second and third drive wheels 210b, 210c (the rear wheels) is reduced, while the first drive wheel 210a (the front wheel) slips in the forward drive direction and supports the robot 100. If the loading of the second and third drive wheels 210b, 210c (the rear wheels) is asymmetrical, the robot 100 may “yaw” which will reduce dynamic stability. The IMU 470 (e.g., a gyro) can be used to detect this yaw and command the second and third drive wheels 210b, 210c to reorient the robot 100.

Referring to FIG. 5, in some implementations, the controller 500 executes a control system 510, which includes a behavior system 510a and a control arbitration system 510b in communication with each other. The control arbitration system 510b allows applications 520 to be dynamically added and removed from the control system 510, and facilitates allowing applications 520 to each control the robot 100 without needing to know about any other applications 520. In other words, the control arbitration system 510b provides a simple prioritized control mechanism between applications 520 and resources 530 of the robot 100. The resources 530 may include the drive system 200, the sensor system 400, and/or any payloads or controllable devices in communication with the controller 500.

The applications **520** can be stored in memory of or communicated to the robot **100**, to run concurrently on (e.g., a processor) and simultaneously control the robot **100**. The applications **520** may access behaviors **512** of the behavior system **510a**. The independently deployed applications **520** are combined dynamically at runtime and share robot resources **530** (e.g., drive system **200**, arm(s), head(s), etc.) of the robot **100**. A low-level policy is implemented for dynamically sharing the robot resources **530** among the applications **520** at run-time. The policy determines which application **520** has control of the robot resources **530** required by that application **520** (e.g. it creates a priority hierarchy among the applications **520**). Applications **520** can start and stop dynamically and run completely independently of each other. The control system **510** also allows for complex behaviors **512** which can be combined together to assist each other.

The control arbitration system **510b** includes one or more resource controllers **540**, a robot manager **550**, and one or more control arbiters **560**. These components do not need to be in a common process or computer, and do not need to be started in any particular order. The resource controller **540** component provides an interface to the control arbitration system **510b** for applications **520**. There is an instance of this component for every application **520**. The resource controller **540** abstracts and encapsulates away the complexities of authentication, distributed resource control arbiters, command buffering, and the like. The robot manager **550** coordinates the prioritization of applications **520**, by controlling which application **520** has exclusive control of any of the robot resources **530** at any particular time. Since this is the central coordinator of information, there is only one instance of the robot manager **550** per robot. The robot manager **550** implements a priority policy, which has a linear prioritized order of the resource controllers **540**, and keeps track of the resource control arbiters **560** that provide hardware control. The control arbiter **560** receives the commands from every application **520** generates a single command based on the applications' priorities and publishes it for its associated resources **530**. The control arbiter **560** also receives state feedback from its associated resources **530** and sends it back up to the applications **520**. The robot resources **530** may be a network of functional modules (e.g. actuators, drive systems, and groups thereof) with one or more hardware controllers. The commands of the control arbiter **560** are specific to the resource **530** to carry out specific actions.

A dynamics model **570** executable on the controller **500** can be configured to compute the center of gravity (CG), moments of inertia, and cross products of inertia of various portions of the robot **100** for the assessing a current robot state. The dynamics model **570** may also model the shapes, weight, and/or moments of inertia of these components. In some examples, the dynamics model **570** communicates with the IMU **470** or portions of one (e.g., accelerometers and/or gyros) disposed on the robot **100** and in communication with the controller **500** for calculating the various centers of gravity of the robot **100**. The dynamics model **570** can be used by the controller **500**, along with other programs **520** or behaviors **512** to determine operating envelopes of the robot **100** and its components.

Each application **520** has an action selection engine **580** and a resource controller **540**, one or more behaviors **512** connected to the action selection engine **580**, and one or more action models **590** connected to action selection engine **580**. The behavior system **510a** provides predictive modeling and allows the behaviors **512** to collaboratively decide on the robot's actions by evaluating possible outcomes of

robot actions. In some examples, a behavior **512** is a plug-in component that provides a hierarchical, state-full evaluation function that couples sensory feedback from multiple sources with a-priori limits and information into evaluation feedback on the allowable actions of the robot. Since the behaviors **512** can be plugged into the application **520** (e.g., residing inside or outside of the application **520**), they can be removed and added without having to modify the application **520** or any other part of the control system **510**. Each behavior **512** is a standalone policy. To make behaviors **512** more powerful, it is possible to attach the output of multiple behaviors **512** together into the input of another so as to have complex combination functions. The behaviors **512** are intended to implement manageable portions of the total cognizance of the robot **100**.

The action selection engine **580** is the coordinating element of the control system **510** and runs a fast, optimized action selection cycle (prediction/correction cycle) searching for the best action given the inputs of all the behaviors **512**. The action selection engine **580** has three phases: nomination, action selection search, and completion. In the nomination phase, each behavior **512** is notified that the action selection cycle has started and is provided with the cycle start time, the current state, and limits of the robot actuator space. Based on internal policy or external input, each behavior **512** decides whether or not it wants to participate in this action selection cycle. During this phase, a list of active behavior primitives is generated whose input will affect the selection of the commands to be executed on the robot **100**.

In the action selection search phase, the action selection engine **580** generates feasible outcomes from the space of available actions, also referred to as the action space. The action selection engine **580** uses the action models **590** to provide a pool of feasible commands (within limits) and corresponding outcomes as a result of simulating the action of each command at different time steps with a time horizon in the future. The action selection engine **580** calculates a preferred outcome, based on the outcome evaluations of the behaviors **512**, and sends the corresponding command to the control arbitration system **510b** and notifies the action model **590** of the chosen command as feedback.

In the completion phase, the commands that correspond to a collaborative best scored outcome are combined together as an overall command, which is presented to the resource controller **540** for execution on the robot resources **530**. The best outcome is provided as feedback to the active behaviors **512**, to be used in future evaluation cycles.

Received sensor signals from the sensor system **400** can cause interactions with one or more behaviors **512** to execute actions. For example, using the control system **510**, the controller **500** selects an action (or move command) for each robotic component (e.g., motor or actuator) from a corresponding action space (e.g., a collection of possible actions or moves for that particular component) to effectuate a coordinated move of each robotic component in an efficient manner that avoids collisions with itself and any objects about the robot **100**, which the robot **100** is aware of. The controller **500** can issue a coordinated command over robot network, such as an EtherIO network, as described in U.S. Ser. No. 61/305,069, filed Feb. 16, 2010, the entire contents of which are hereby incorporated by reference.

FIG. 6A provides a schematic view of an exemplary robot system **600** having one or more telepresence robots **100** in communication with a bridge **602**, which communicates with a local robot endpoint server **604a** and a remote endpoint server **604b** (e.g., such as the cloud computing

service **720** (FIG. 7)). The local robot endpoint server **604a** communicates with a local technician computing device **606** and the remote endpoint server **604b** communicates with a remote operator computing device **608**.

Referring to FIGS. **2** and **4C**, in some implementations, the robot **100** includes multiple antennas. In the examples shown, the robot **100** includes a first antenna **490a** and a second antenna **490b** both disposed on the base **120** (although the antennas may be disposed at any other part of the robot **100**, such as the leg **130**, the torso **140**, the neck **150**, and/or the head **160**). The use of multiple antennas provides robust signal reception and transmission. The use of multiple antennas provides the robot **100** with multiple-input and multiple-output (MIMO) which is the use of multiple antennas for a transmitter and/or a receiver to improve communication performance. MIMO offers significant increases in data throughput and link range without additional bandwidth or transmit power. It achieves this by higher spectral efficiency (more bits per second per hertz of bandwidth) and link reliability or diversity (reduced fading). Because of these properties, MIMO is an important part of modern wireless communication standards such as IEEE 802.11n (Wifi), 4G, 3GPP Long Term Evolution, WiMAX and HSPA+. Moreover, the robot **100** can act as a Wi-Fi bridge, hub or hotspot for other electronic devices nearby. The mobility and use of MIMO of the robot **100** can allow the robot to serve as a relatively reliable Wi-Fi bridge **602**.

Referring to FIGS. **6A** and **6B**, a teleoperation software application **601** executes on at least one of the robot controller **500**, the local robot endpoint server **604a**, the remote endpoint server **604b**, the local technician computing device **606** and the remote operator computing device **608**. In some examples, a portion of the teleoperation software application **601** executes on one or more of the aforementioned devices. The teleoperation software application **601** allows one or more users to interact with the robot **100** (e.g., to drive the robot **100**) and/or remotely with other people or objects adjacent the robot **100** through telepresence features of the robot **100**.

FIG. **6C** provides a schematic view of an exemplary user interface **605** of the teleoperation software application **601** that can be rendered on a display, such as the touch screen **312** of the web pad **310** and/or the remote operator computing device **608**, for controlling navigation, telepresence, and/or other aspects of the robot **100**. The user interface **605** includes a remote video feed window **610** displaying a remote view **612**, such as a video feed of a patient **614**. The video feed may be generated by one of the cameras **320**, **450** on the robot **100**. The user interface **605** may display a plan view map window **620** having a map **622** of the local area in which the robot **100** is operating. In the example shown, the map **622** displayed in the plan view map window **620** is a two-dimensional, top-down map **622a** (FIG. **6D**); however, other types of maps are possible as well. The user interface **605** may also include a local video window **630** displaying a local view **632**, such as a video feed of the user (e.g., remote from the robot **100**). The video feed displayed in the local video window **630** may be transmitted to the robot **100** and displayed to the patient **614** using a display device, such as the web pad **310** on the robot **100**.

A dashboard **640** may provide information regarding the orientation of the robot **100**, an indication of the robot's battery charge, an indication of the strength of a wireless data signal, and/or an indication of the network quality. The orientation of the robot **100** may be indicated by an icon **642** displaying the orientation of the head **160** of the robot **100** with respect to the torso **140** or the base **120**. Such an

indication may assist a user in orienting the robot **100** to view items of interest. The range of motion of the robot head **160** may be limited. Accordingly, certain implementations may display an indication of the rotational position of the head **160** and a range of motion of the head **160**.

Media controls **647** may allow the user to interact with the patient **614** using various types of media and to acquire and store media documenting the interactions of the user and the patient **614**. The media controls **647** may allow the user to play audio and/or video clips, for example, that may be used to educate the patient **614** about a medical condition or procedure. Still photographs may be acquired using a camera **320**, **450** of the robot **100** in order to document various conditions. Further, the robot **100** may acquire audio (e.g., using the microphone **330**) or video (e.g., using the camera **320**) documenting the user's interaction with the patient **614** and optionally storing the acquired audio/video in memory of the controller **500** and/or transmitting the acquired audio/video to a remote device or cloud service.

In some implementations, the media controls **647** allow the user to manage temporary connectivity issues. For example, upon the unexpected disconnection of a session, video recording may begin. The robot **100** may continue recording video and saving it to local memory, such as that of the controller **500**. Upon an unexpected disconnection, a message may be displayed by the robot, such as "Session terminated—Video recording continuing . . ." A button below may be displayed with a caption of "Stop recording." A nurse on the robot side may touch the "Stop recording" button (e.g., on the touch screen **312**) and terminate the local recording. Otherwise, the recording may continue for a specified time interval. If the same user logs back into the robot **100** in the specified time interval, the record button on the remote station may show that recording is in progress. When the robot's local recording is complete, it may begin to transmit the video file to a remote station or other location that may be accessible to the disconnected user. Accordingly, the user may be able to see what events transpired during the time that the session was interrupted.

In the example shown in FIG. **6C**, the remote video feed window **610** occupies a relatively large portion of the display area. The user interface **605** may have the remote video feed window **610** rendered at a 640×480 pixel resolution, the local video window **630** at a 320×240 pixel resolution, and the plan view map window **620** at a 530×200 pixel resolution. Accordingly, this view may be most appropriate when the user is communicating with the patient **614** and/or manually driving the robot **100**. The layout of the default user interface **605a** shown in FIG. **6C** may allow the user to swap the contents of the plan view map window **620** with the remote video feed window **610**. The view may be swapped, for example, by double-clicking on the map window **620**. The windows could later be swapped back by double-clicking on the remote video feed window **610**.

Alternative screen layouts may be displayed to a user as may be appropriate for the task being performed by the user. In the example shown in FIG. **6D**, in anticipation of directing the robot **100** to move using semi-autonomous navigation from one location to another, the size of the plan view map window **620** is increased. For example, the user interface **605**, **605a** shown in FIG. **6C** can be a default state for patient interaction and the user interface **605**, **605b** shown in FIG. **6D** can be an alternate state for robot navigation.

A map view switch button **645** of the user interface may allow the user to invoke the alternative user interface **605b** that includes a relatively larger map window **620**. For example, the user interface **605b** shown in FIG. **6D** may be

primarily used to manually drive the robot **100** or to autonomously navigate to a desired destination. Clicking the map view switch button **645** again takes the user back to the default user interface **605a**, which may be used when actively performing a medical consultation. Accordingly, a user may emphasize or de-emphasize (e.g., maximize or minimize) the plan view map window **620** as desired. Certain of the windows shown in the alternate user interface **605b** are also displayed, such as the remote video feed window **610** and the local video window **630**. In some examples, the plan view map window **620** may be displayed at a 880×700 pixel resolution, the remote video feed window **610** may be displayed at a 320×240 pixel resolution, and the local video window **630** may be displayed at a 160×120 pixel resolution.

Referring to FIG. 6D, the plan view map window **620** may provide a robot location icon **650** designating a location of the robot **100** within the local environment. A user may click on or touch a point on the displayed map **622** in order to cause the robot to semi-autonomously or autonomously navigate to the selected point. In some examples, the user may zoom in and out using a mouse wheel while the cursor is over the plan view map window **620** or by touch gestures, when displayed on a touch screen **312**.

Simultaneous localization and mapping (SLAM) technology may utilize laser range scanners, odometry, acoustic range finders, or all of the above to build a map of the local environment and place the robot **100** on the map. Images recorded by a robot **100** (e.g., via the camera **320** or three-dimensional image sensor **450**) as it traverses an environment may be stored in an internal database (e.g., of the controller **500**) and/or a remote database (e.g., a cloud service). When the robot **100** reacquires an image currently in the database, the algorithm resets the robot's current position to that which was recorded when the landmark was originally entered in the database. This method helps to counter the inherent drift of wheel encoder odometry. Systems may also utilize RFID chips and/or triangulation of wireless access points. Further, the names or identifying numbers of specific rooms may be associated with locations on the map. Image data can accumulate over time and, as a cost savings or space savings, the robot **100** may use remote data storage and/or remote processing for storing and/or processing the image data, respectively. For example, an RFID reader may detect RFID chips associated with coordinates on a plan view map in order to identify a current location of a robot. An "RFID chip" may include an RFID device or an RFID "tag" as is understood by those having skill in the art. The RFID chips may be embodied as passive, active, or battery assisted passive (BAP) RFID chips.

FIG. 7 provides a schematic view of an exemplary robot system architecture **700**, which may include the robot **100** (or a portion thereof, such as the controller **500** or drive system **200**), a computing device **310** (e.g., detachably or fixedly attached to the head **160**), a cloud **720** (i.e., cloud computing service), and a portal **730**. The computing device **310** may execute one or more robot applications **710**, which may include software applications (e.g., stored in memory and executable on a processor) for security, medicine compliance, telepresence, behavioral coaching, social networking, active alarm, home management, etc. The computing device **310** may provide communication capabilities (e.g., secure wireless connectivity and/or cellular communication), refined application development tools, speech recognition, and person or object recognition capabilities. The computing device **310** in some examples utilizes an interaction/COMS featured operating system, such as Android

provided by Google Inc., iOS provided by Apple, Inc., or other smart phone operating systems, or specialized robot operating systems, such as RSS A2.

The cloud **720** provides cloud computing and/or cloud storage capabilities. Cloud computing may provide Internet-based computing, whereby shared servers provide resources, software, and data to computers and other devices on demand. For example, the cloud **720** may be a cloud computing service that includes at least one server computing device, which may include a service abstraction layer and a hypertext transfer protocol wrapper over a server virtual machine instantiated thereon. The server computing device may be configured to parse HTTP requests and send HTTP responses. Cloud computing may be a technology that uses the Internet and central remote servers to maintain data and applications. Cloud computing can allow users to access and use applications **710** without installation and to access personal files at any computer with Internet access. Cloud computing allows for relatively more efficient computing by centralizing storage, memory, processing and bandwidth. The cloud **720** can provide scalable, on-demand computing power, storage, and bandwidth, while reducing robot hardware requirements (e.g., by freeing up CPU and memory usage). Robot connectivity to the cloud **720** allows automatic data gathering of robot operation and usage histories without requiring the robot **100** to return to a base station. Moreover, continuous data collection over time can yield a wealth of data that can be mined for marketing, product development, and support.

Cloud storage **722** can be a model of networked computer data storage where data is stored on multiple virtual servers, generally hosted by third parties. By providing communication between the robot **100** and the cloud **720**, information gathered by the robot **100** can be securely viewed by authorized users via a web-based information portal.

The portal **730** may be a web-based user portal for gathering and/or providing information, such as personal information, home status information, and robot status information. Information can be integrated with third-party information to provide additional functionality and resources to the user and/or the robot **100**. The robot system architecture **700** can facilitate proactive data collection. For example, applications **710** executed on the computing device **310** may collect data and report on actions performed by the robot **100** and/or a person or an environment viewed by the robot **100** (using the sensor system **400**). This data can be a unique property of the robot **100**.

"Dense data" vs. "sparse data" and "dense features" vs. "sparse features" are referred to herein with respect to spatial data sets. Without limiting or narrowing the meaning from that of how those skilled in the art would interpret such terms to mean, "dense" vs. "sparse" generally means many data points per spatial representation vs. few data points, and specifically may mean:

(i) in the context of two-dimensional image data or three-dimensional "images" including two-dimensional data and range, "dense" image data includes image data substantially fully populated with pixels, or capable of being rasterized to pixels with substantially no losses and/or artifacting from the original image capture (including substantially uncompressed, raw, or losslessly compressed images), while a "sparse" image is one where the image is quantized, sampled, lossy compressed, vectorized, segmented (e.g., into superpixels, nodes, edges, surfaces, interest points, voxels), or otherwise materially reduced in fidelity from the original capture, or must be interpolated in being rasterized to pixels to re-represent an image;

(ii) in the context of two-dimensional or three-dimensional features, “dense features” may be features that are populated in a substantially unconstrained manner, to the resolution of the detection approach, all that can be detected and recorded, and/or features that are recognized by detectors recognized to collect many features (HOG, wavelets) over a sub-image; “sparse features” may be purposefully constrained in number, in the number of feature inputs, lateral inhibition, and/or feature selection, and/or may be recognized by detectors recognized to identify a limited number of isolated points in an image (Harris corner, edges, Shi-Tomasi).

With respect to three-dimensional environment structure, the robot 100 may acquire images, such as dense images 701, of a scene 10 about the robot 100 while maneuvering about a work surface 5. In some implementations, the robot 100 uses a camera 320 and/or an image sensor 450 (e.g., volumetric point cloud imaging device) for obtaining the dense images 701. The controller 500, which is in communication with the camera 320 and/or the image sensor 450 may associate information with the dense images 701 (e.g., mark-up or tag the dense images 701 with data), such as accelerometer data traces, odometry data, and/or other data from the sensor system 400 along with timestamps. In some examples, the robot 100 captures a streaming sequence of dense images 701 and marks the dense image sequence with mark-up data, providing a marked-up dense image sequence. The cloud service 720 may process the received image data 701 and return a processed data set to the robot controller 500, which may issue drive commands to the drive system 200 based on the received processed data set for maneuvering about the scene 10.

The cloud service 720 may execute one of a variety of off-line methods to process a stored image data set 703 into a dense three-dimensional map or model 705 of the scene 10 (environment) and then simplify this dense three-dimensional map or model 705 into a two-dimensional height map 707, which can be a two-dimensional map with height data at each point (e.g., similar to a two-dimensional topographical map). In some examples, the two-dimensional height map 707 is a topographical map having X and Y coordinates with Z data. Each X,Y coordinate may have one or more Z points (i.e., height data). Unlike the dense three-dimensional map, which may have numerous Z points (e.g., hundreds or thousands of Z points) for each X,Y coordinate, the two-dimensional height map 707 may have less than threshold number of Z points for each X,Y coordinate, such as between 2 and 20 (e.g., 10) points. A two-dimensional height map 707 derived from a three-dimensional map of a table in a room may show a first Z point for the bottom surface of a table top and a second Z point for the top surface of the table top for each X,Y coordinate along the table. This information allows the robot 100 to determine if it can pass under the table top. By reducing the Z points from a dense data set of a continuous range of Z points for each X,Y coordinate to a sparse data set of a select number of Z points indicative of a detected objects 12, the robot 100 can receive a two-dimensional height map 707 having a relatively smaller size than the three-dimensional map used by the cloud service 720. This, in turn, allows the robot 100 to store the two-dimensional height map 707 on local memory having a practical and cost effective size as compared to the scalable memory space available to the cloud service 720. The robot 100 receives the two-dimensional height map 707 from the cloud 720, which provides the robot 100 and associated controller 500 with navigational data for future work in the scene 10.

Additional methods and features of three-dimensional map data compression are disclosed in “Multi-Level Surface Maps for Outdoor Terrain Mapping and Loop Closing” by R. Triebel, P. Pfaff and W. Burgard; IEEE/RSJ International Conference on Intelligent Robots and Systems, 2006, which is hereby incorporated by reference in its entirety.

The cloud 720 provides the robot 100 with on-demand scaling of resources (e.g., computational, processing, memory, etc.) that may not otherwise be practical or cost effective on the robot 100. For example, the cloud 720 can provide scalable cloud storage 722 that scales up to a first size for storing and/or processing a relatively large amount of data 701, which may only be used for a short period of time and then discarded, and then scaled back down to a second size. Moreover, the cloud 720 can provide computer processing power for executing relatively complex computations or “brute force” algorithms that might not otherwise be possible on the robot. By displacing computer processing power and memory to a scalable cloud 720, the robot 100 can use a controller 500 having relatively less computing power and memory, thus providing a cost effective solution. Moreover, the robot 100 may execute real-time tasks (on the controller 500 or the web pad 310), such as obstacle avoidance, while passing non-real-time or non-time-sensitive tasks to the cloud 720 for processing and later retrieval.

The cloud 720 may execute one or more filters (e.g., a Bundle Adjustment, RANSAC, Expectation Maximization, SAM or other 3D structural estimation algorithms) for processing the stored image data set 703 into a 3D representation. Once processed and a dense three-dimensional map 705 has been created or updated, the image data set 703 can be discarded from the cloud storage 722, freeing up resources and allowing the cloud 720 to scale accordingly. As a result, the robot 100 needs neither the on-board storage nor the processing to handle the storage and processing of the image data set 703, due to the use of cloud based resources. The cloud 720 may return processed navigational data 701 or a map 707 (e.g., a compressed two-dimensional height map) to the robot 100, which it can then use for relatively simpler localization and navigation processing.

Additional methods and features of three-dimensional reconstruction are disclosed in “3D Models from Extended Uncalibrated Video Sequences: Addressing Key-frame Selection and Projective Drift” by J. Repko and M. Pollefeys; Fifth International Conference on three-dimensional Digital Imaging and Modeling, 2005, which is hereby incorporated by reference in its entirety.

Referring to FIGS. 8A and 8B, in some circumstances, the robot 100 receives an occupancy map 800 of objects 12 in a scene 10 and/or work surface 5, or the robot controller 500 produces (and may update) the occupancy map 800 based on image data and/or image depth data received from an image sensor 450 (e.g., the second three-dimensional image sensor 450b) over time. SLAM is a technique that may be used by the robot 100 to build up an occupancy map 800 within an unknown environment or scene 10 (without a priori knowledge), or to update an occupancy map 800 within a known environment (with a priori knowledge from a given map), while at the same time keeping track of its current location.

The controller 500 may communicate the occupancy map 800 to the telepresence software application 601 for displaying a map 622 in the user interface 605. The user interface map 622 may be derived partly or wholly from the occupancy map 800. Moreover, referring also to FIG. 7, the telepresence software application 601 may receive periodic updates of the occupancy map 800 via the cloud service 720. For example, the cloud service 720 may provide with

telepresence software application **601** with the dense three-dimensional map or model **705** of the scene **10** about the robot **100** and/or the simplified two-dimensional height map **707** for generating the user interface map **622**. In additional examples, the cloud service **720** provides the user interface map **622** to the telepresence software application **601** based on the dense three-dimensional map or model **705** or the two-dimensional height map **707**.

Referring again to FIGS. **8A** and **8B**, maps **800** can be used to determine a location within an environment **10** and to depict an environment for planning and navigation. The maps **800** support the assessment of actual location by recording information obtained from a form of perception and comparing it to a current set of perceptions. The benefit of a map **800** in aiding the assessment of a location increases as the precision and quality of the current perceptions decrease. Maps **800** generally represent the state at the time that the map **800** is provided or produced. This is not necessarily consistent with the state of the environment at the time the map **800** is used. Other localization techniques include monocular visual SLAM (MonoSLAM) and implementations using an extended Kalman filter (EKF) for MonoSLAM solutions.

The controller **500** may execute a scale-invariant feature transform (SIFT) to detect and describe local features in captured images. For any object **12** in an image, interesting points on the object **12** can be extracted to provide a “feature description” of the object **12**. This description, extracted from a training image, can then be used to identify the object **12** when attempting to locate the object **12** in a test image containing many other objects. To perform reliable recognition, it is important that the features extracted from the training image be detectable even under changes in image scale, noise and illumination. Such points usually lie on high-contrast regions of the image, such as object edges. For object recognition and detection, the robot **100** may use a SIFT to find distinctive key points that are invariant to location, scale and rotation, and robust to affine transformations (changes in scale, rotation, shear, and position) and changes in illumination. In some implementations, the robot **100** captures multiple images (using the camera **320** and/or image sensor **450**) of a scene **10** or object **12** (e.g., under different conditions, from different angles, etc.) and stores the images, such as in a matrix. The robot **100** can access the stored images to identify a new image by comparison, filter, etc. For example, SIFT features can be obtained from an input image and matched to a SIFT feature database obtained from training images (captured previously). The feature matching can be done through a Euclidean-distance based nearest neighbor approach. A Hough transform may be used to increase object identification by clustering those features that belong to the same object and reject the matches that are left out in the clustering process. A speeded up robust feature (SURF) may be a robust image detector and descriptor.

In addition to localization of the robot **100** in the scene **10** (e.g., the environment about the robot **100**), the robot **100** may travel to other points in a connected space (e.g., the work surface **5**) using the sensor system **400**. The robot **100** may include a short range type of image sensor **450a** (e.g., mounted on the underside of the torso **140**, as shown in FIGS. **1** and **3**) for mapping a nearby area about the robot **110** and discerning relatively close objects **12**, and a long range type of image sensor **450b** (e.g., mounted on the head **160**, as shown in FIGS. **1** and **3**) for mapping a relatively larger area about the robot **100** and discerning relatively far away objects **12**. The robot **100** can use the occupancy map

800 to identify known objects **12** in the scene **10** as well as occlusions **16** (e.g., where an object **12** should or should not be, but cannot be confirmed from the current vantage point). The robot **100** can register an occlusion **16** or new object **12** in the scene **10** and attempt to circumnavigate the occlusion **16** or new object **12** to verify the location of new object **12** or any objects **12** in the occlusion **16**. Moreover, using the occupancy map **800**, the robot **100** can determine and track movement of an object **12** in the scene **10**. For example, the image sensor **450**, **450a**, **450b** may detect a new position of the object **12** in the scene **10** while not detecting a mapped position of the object **12** in the scene **10**. The robot **100** can register the position of the old object **12** as an occlusion **16** and try to circumnavigate the occlusion **16** to verify the location of the object **12**. The robot **100** may compare new image depth data with previous image depth data (e.g., the map **800**) and assign a confidence level of the location of the object **12** in the scene **10**. The location confidence level of objects **12** within the scene **10** can time out after a threshold period of time. The sensor system **400** can update location confidence levels of each object **12** after each imaging cycle of the sensor system **400**. In some examples, a detected new occlusion **16** (e.g., a missing object **12** from the occupancy map **800**) within an occlusion detection period (e.g., less than 10 seconds) may signify a “live” object **12** (e.g., a moving object **12**) in the scene **10**.

In some implementations, a second object **12b** of interest, located behind a detected first object **12a** in the scene **10**, may be initially undetected as an occlusion **16** in the scene **10**. An occlusion **16** can be an area in the scene **10** that is not readily detectable or viewable by the image sensor **450**, **450a**, **450b**. In the example shown, the sensor system **400** (e.g., or a portion thereof, such as image sensor **450**, **450a**, **450b**) of the robot **100** has a field of view **452** with a viewing angle θ_v (which can be any angle between 0 degrees and 360 degrees) to view the scene **10**. In some examples, the image sensor **450** includes omni-directional optics for a 360 degree viewing angle θ_v while in other examples, the image sensor **450**, **450a**, **450b** has a viewing angle θ_v of less than 360 degrees (e.g., between about 45 degrees and 180 degrees). In examples, where the viewing angle θ_v is less than 360 degrees, the image sensor **450**, **450a**, **450b** (or components thereof) may rotate with respect to the robot body **110** to achieve a viewing angle θ_v of 360 degrees. In some implementations, the image sensor **450**, **450a**, **450b** or portions thereof, can move with respect to the robot body **110** and/or drive system **200**. Moreover, in order to detect the second object **12b**, the robot **100** may move the image sensor **450**, **450a**, **450b** by driving about the scene **10** in one or more directions (e.g., by translating and/or rotating on the work surface **5**) to obtain a vantage point that allows detection of the second object **12b**. Robot movement or independent movement of the image sensor **450**, **450a**, **450b**, or portions thereof, may resolve monocular difficulties as well.

A confidence level may be assigned to detected locations or tracked movements of objects **12** in the working area **5**. For example, upon producing or updating the occupancy map **800**, the controller **500** may assign a confidence level for each object **12** on the map **800**. The confidence level can be directly proportional to a probability that the object **12** is actually located in the working area **5** as indicated on the map **800**. The confidence level may be determined by a number of factors, such as the number and type of sensors used to detect the object **12**. For example, the contact sensor **430** may provide the highest level of confidence, as the contact sensor **430** senses actual contact with the object **12** by the robot **100**. The image sensor **450** may provide a

different level of confidence, which may be higher than the proximity sensor **430**. Data received from more than one sensor of the sensor system **400** can be aggregated or accumulated for providing a relatively higher level of confidence over any single sensor.

Odometry is the use of data from the movement of actuators to estimate change in position over time (distance traveled). In some examples, an encoder is disposed on the drive system **200** for measuring wheel revolutions, therefore a distance traveled by the robot **100**. The controller **500** may use odometry in assessing a confidence level for an object location. In some implementations, the sensor system **400** includes an odometer and/or an angular rate sensor (e.g., gyroscope or the IMU **470**) for sensing a distance traveled by the robot **100**. A gyroscope is a device for measuring or maintaining orientation, based on the principles of conservation of angular momentum. The controller **500** may use odometry and/or gyro signals received from the odometer and/or angular rate sensor, respectively, to determine a location of the robot **100** in a working area **5** and/or on an occupancy map **800**. In some examples, the controller **500** uses dead reckoning. Dead reckoning is the process of estimating a current position based upon a previously determined position, and advancing that position based upon known or estimated speeds over elapsed time, and course. By knowing a robot location in the working area **5** (e.g., via odometry, gyroscope) as well as a sensed location of one or more objects **12** in the working area **5** (via the sensor system **400**), the controller **500** can assess a relatively higher confidence level of a location or movement of an object **12** on the occupancy map **800** and in the working area **5** (versus without the use of odometry or a gyroscope).

Odometry based on wheel motion can be electrically noisy. The controller **500** may utilize scan matching in conjunction with or in place of wheel odometry. The use of scan matching may improve accuracy and/or reduce the computational burden. In such an embodiment, two partial maps obtained using LIDAR and/or other mapping methods may be merged into a single map. The two or more partial maps may be merged using a known scanning location. Alternatively, two or more partial maps may be merged using geometrical features of the partial scans. The controller **500** may receive image data from the image sensor **450** of the environment or scene **10** about the robot **100** for computing robot motion, independently of wheel based odometry of the drive system **200**, through visual odometry. Visual odometry may entail using optical flow to determine the motion of the image sensor **450**. The controller **500** can use the calculated motion based on imaging data of the image sensor **450** for correcting any errors in the wheel based odometry, thus allowing for improved mapping and motion control. Visual odometry may have limitations with low-texture or low-light scenes **10**, if the image sensor **450** cannot track features within the captured image(s).

Other details and features on odometry and imaging systems, which may be combinable with those described herein, can be found in U.S. Pat. No. 7,158,317 (describing a "depth-of field" imaging system), and U.S. Pat. No. 7,115,849 (describing wavefront coding interference contrast imaging systems), the contents of which are hereby incorporated by reference in their entireties.

Referring to FIGS. **8C** and **8D**, when a robot is new to a building that it will be working in, the robot may need to be shown around or provided with a map of the building (e.g., room and hallway locations) for autonomous navigation. For example, in a hospital, the robot may need to know the location of each patient room, nursing stations, etc. In some

implementations, the robot **100** receives a plan view map **810**, such as the one shown in FIG. **8C**, and can be trained to learn the plan view map **810**. For example, while leading the robot **100** around the building, the robot **100** may record specific locations corresponding to locations on the plan view map **810**. The robot **100** may display the plan view map **810** on the web pad **310** and when the user takes the robot **100** to a specific location, the user can tag that location on the plan view map **810** (e.g., using a touch screen or other pointing device of the web pads **310**). The user may choose to enter a label for a tagged location, like a room name or a room number. At the time of tagging, the robot **100** may store the tag, with a point on the plan view map **810** and a corresponding point on a robot map **820**, such as the one shown in FIG. **8D**. As illustrated, the robot map **820** may be a two-dimensional plan view map similar to the plan view map **810**. In alternative embodiments, the robot map **820** may be a three-dimensional map including a ground level corresponding to a two-dimensional plan view map similar to the plan view map **810**.

Using the sensor system **400**, the robot **100** may build the robot map **820** as it moves around. For example, the sensor system **400** can provide information on how far the robot **100** has moved and a direction of travel. The robot map **820** may include fixed obstacles in addition to the walls provided in the plan view map **810**. The robot **100** may use the robot map **820** to execute autonomous navigation. In the robot map **820**, the "walls" may not look perfectly straight, for example, due to detected packing crates along the wall in the corresponding hallway and/or furniture detected inside various cubicles. Moreover, rotational and resolution differences may exist between the plan view map **810** and the robot map **820**.

Referring to FIG. **8E**, in some implementations, the telepresence software application **601** displays a tagging view **660** that allows the user to place tags **662** on the plan view map **810**. The plan view map **810** may be the same map as that displayed by the plan view map window **620** or it may be a different map used internally for navigation purposes.

The user, a remote terminal, and/or the robot may insert tags **662** onto specific locations of the plan view map **810** and/or robot map **820** to mark map locations with information, such as driving hazards, obstacles, robot aids, etc. For example, the user may drag-and-drop tags **662** onto specific location of the plan view map **810**. As is described herein, the tags may include tag coordinates associated with a point or a region, tag information defining the purpose of the tag, type of the tag, nature of the tag, instructions for the user and/or robot related to the tag, and/or other information relevant to the tag, and finally, the tag may include a tag annotation comprising a two-dimensional and/or three-dimensional graphic or text corresponding to the tag. An example of a tag annotation is an octagonal red stop sign associated with a tag containing tag information indicating an area that a robot should not enter. A tag annotation may be human and/or machine interpretable. Tag coordinates may be points, lines, plans, surfaces, volumes, and/or 2.5D or hybrid surfaces. Tags may be formed as data structures having any number of additional fields and/or parameters. For example, a tag include fields associated with time, scheduling, spatial coordinates, and/or triggers for predetermined functions.

The term annotation, as used herein, includes text, words, or other verbal representations. Accordingly, the tag annotation may be a picture, graphical image, a pictograph, a hieoannotation, a non-verbal symbol. In addition, a tag annotation may be a word, a letter, a phrase, or other text

form. For example, a tag associated with a nurses station may include a tag annotation comprising a textual representation of the nurses name. The textual representation of the nurses name could be two-dimensional text, or it could be a three-dimensional text. Alternatively, the tag annotation associated with the nurse's station could be a large letter N, or a symbol representative of a nurse's station (e.g., a nurses hat or nursing symbol).

The tags **662** may include a wireless local area network (WLAN) warm tag **662a** denoting an area having relatively good signal reception and a WLAN cold tag **662b** denoting an area having relatively poor signal reception. The robot **100** may use this information to navigate from one location to another through an area having relatively good wireless signal reception, while avoiding areas having relatively poor wireless signal reception.

A low traffic tag **662c** denotes an area having relatively low traffic (person and/or robot). The robot **100** may select a travel path through an area having a relatively low traffic volume, rather than through an area having a relatively high traffic volume. Moreover, if the robot **100** must travel through a high traffic area, the robot **100** may execute one or more specific object detection obstacle avoidance (ODOA) behaviors to navigate the area successfully without collisions.

A dock tag **662d** denotes a location of a robot docking station. A low battery event may signal the controller **500** to seek recharging. The robot **100** may use the map location tagged with a dock tag **662d** to locate a robot docking station for recharging. For example, by applying a resolved distortion between the plan view map **810** and the robot map **820** (FIGS. **8C** and **8D**), the robot **100** can determine a corresponding robot map location **824** corresponding to the tagged layout map location **814** to navigate to that tagged location to dock with a robot docking station. Resolving the distortion may include determining a distortion between two maps that use the same coordinate system. The robot map **820** and the plan view map **810** may both be two-dimensional and as such, determining a distortion may not require determining a coordinate transformation between different dimensions.

Some tags **662** may be used to indicate obstacles or special traversal areas. For example, a glass tag **662e** indicates the location of a glass wall, window, or door. The robot **100** may use this information to avoid the tagged glass structures, since infrared proximity sensors may not detect them. A ramp tag **662f** indicates the location of a floor ramp. For a distance, the robot **100** may detect the ramp as an obstacle, since it may appear to have a vertical height greater than a threshold traversal height. When approaching a tagged ramp, the robot **100** may execute a ramp or traversal behavior to successfully negotiate the ramp. A tight tag **662g** indicates the location of a relatively narrow corridor or thoroughway. The robot **100** may avoid such areas, so as to avoid any confining situations.

A slow tag **662h** indicates a location or area in which the robot **100** drives relatively slowly. This location or area may coincide with a high traffic area. An avoid tag **662i** denotes a location or area that the robot **100** should avoid (i.e., not drive through). In some embodiments, an avoid tag **662i** may be operation mode-dependent. For example, the avoid tag **662i** may be applicable only when the robot is operating in a fully autonomous mode. During teleoperation, the avoid tag **662i** may be effectively ignored by the robot. An operating room user interface (OR UI) tag **662j** indicates the location or area of a hospital operating room. The robot **100** may use this tag to find the operating room to provide

telepresence support and/or to display a specific user interface (e.g., an OR UI) upon entering the OR area. A training tag **662k** can be used to mark general locations, such as hallways and rooms, to train the robot **100** to learn its environment **10**.

A manual elevator tag **662l** indicates the location of an elevator where the robot **100** should allow a user to aid the robot's traversal into/out of the elevator. Manual elevator negotiation may be based on remote user piloting or robot-local user guidance. For remote user piloting, a remote user provides drive commands to the robot **100** (e.g., using a joystick). For robot-local user guidance, a person adjacent to the robot **100** may physically touch the robot **100** and, in response to those touches, the robot **100** moves accordingly. Features regarding robot responsiveness to user touching combinable with those described herein can be found in application Ser. No. 13/032,390, filed on Feb. 22, 2011, which is hereby incorporated by reference in its entirety.

An auto elevator tag **662m** indicates the location of an elevator that the robot **100** may negotiate (into and out of) autonomously. The robot **100** may execute a threshold traversal behavior **512d** (FIG. **5**) to enter into and drive out of the elevator, so as to avoid tipping. Features regarding robot responsiveness to user touching combinable with those described herein can be found in application serial number PCT/US11/59910, filed on Nov. 9, 2011, which is hereby incorporated by reference in its entirety.

A keep right tag **662n** indicates a map location or area in which the robot **100** should keep to the right. A user may place this tag along certain corridors, such as high traffic corridors. In response to the keep right tag **662n**, the robot **100** may execute a wall following behavior to stay along the wall while driving in the tagged area.

After map training, when a user wants to send the robot **100** to a location, the user can either refer to a label/tag **622** (e.g., enter a label or tag into a location text box displayed on the web pad **310**) or the robot **100** can display the plan view map **810** to the user on the web pad **310** and the user may select the location on the plan view map **810**. If the user selects a tagged layout map location **814**, the robot **100** can easily determine the corresponding robot map location **824** on the robot map **820** and can proceed to navigate to the selected location **814**.

In some implementations, the robot controller **500** may execute a first behavior **512** while maneuvering about a first area and then execute a second behavior **512** while maneuvering about a second area associated with a tag having an associated robot behavior modifier. For example, while executing a person follow behavior **512b**, the robot controller may either cease execution of that behavior **512b** or concurrently execute a threshold traversal behavior **512d** upon reaching a map location **814** tagged with a ramp tag **662f** or an auto elevator tag **622m**.

If the selected location on the plan view map **810** is not a tagged location **814**, the robot **100** determines a corresponding location **824** on the robot map **820**. In some implementations, the robot **100** computes a scaling size, origin mapping, and rotation between the plan view map **810** and the robot map **820** using existing tagged locations, and then applies the computed parameters to determine the robot map location (e.g., using an affine transformation or coordinates).

The robot map **820** may not be the same orientation and scale as the plan view map **810**. Moreover, the layout map may not be to scale and may have distortions that vary by map area. For example, a plan view map **810** created by scanning a fire evacuation map typically seen in hotels,

offices, and hospitals is usually not drawn to scale and can even have different scales in different regions of the map. The robot map **820** may have its own errors. For example, locations on the robot map **820** may have been computed by counting wheel turns as a measure of distance, and if the floor was slightly slippery or turning around corners caused extra wheel turns, inaccurate rotation calculations may cause the robot **100** to determine inaccurate locations of mapped objects.

A method of mapping a given point **814** on the plan view map **810** to a corresponding point **824** on the robot map **820** may include using existing tagged points **812** to compute a local distortion (in the same two-dimensional coordinate system) between the plan view map **810** and the robot map **820** in a region (e.g., within a threshold radius) containing the layout map point. The method further includes applying a distortion calculation to the layout map point **814** in order to find a corresponding robot map point **824**. The reverse can be done if you are starting with a given point on the robot map **820** and want to find a corresponding point on the plan view map **810**, for example, for asking the robot for its current location.

Any of a wide variety of tag schemas and data structures may be used. For example, tags may contain attributes in the form of key-value pairs that specify a purpose of the tag, tag parameters, and tag attributes (generally “tag information”). Table 1 below provides a specific example.

TABLE 1

Field name	Data type	Description
tagId	integer	the ID of the tag entry in the tag table described above
name	text	the parameter name
value	text	the parameter value

Tags associated with regions may have attributes associated with them that specify their purpose and specify parameters that influence behaviors associated with the region. These key-value pairs may be stored using a data structure similar to the example in Table 2 below:

TABLE 2

Field name	Data type	Description
regionId	integer	the ID of the region entry in the region table described above
name	text	the parameter name
value	text	the parameter value

The data structure for each tag may include tag coordinates and tag information, which may include a tag annotation (such as a two-dimensional and/or three-dimensional graphical representation of the tag). Table 3 below provides a specific example of a data structure for a tag.

TABLE 3

Field name	Data type	Description
id	integer	globally unique identifier for the tag in the database
mapId	integer	the identifier of the robot map to which the tag belongs
timestamp	float	a timestamp representing when the tag was created
poseX	float	the X coordinate of the tag in the robot map’s coordinate system

TABLE 3-continued

Field name	Data type	Description
poseY	float	the Y coordinate of the tag in the robot map’s coordinate system
poseZ	float	the Z coordinate of the tag in the robot map’s coordinate system
poseXr	float	the tag’s rotation about the X axis
poseYr	float	the tag’s rotation about the Y axis
poseZr	float	the tag’s rotation about the Z axis
name	text	a human-readable identifier for the tag
annotation	image	a 2D and/or 3D graphical representation

As described herein, a tag may be associated with a region, rather than a specific point, on a map. There may be a many-to-one relationship between tag information and a tag. A specific example of a data structure for a tag associated with a region is provided below in Table 4.

TABLE 4

Field name	Data type	Description
id	integer	globally unique identifier for the region in the database
mapId	integer	the identifier of the robot map to which the region belongs
timestamp	float	a timestamp representing when the region was created
poseX	float	the X coordinate of the region’s centroid in the same coordinate system as the robot map
poseY	float	the Y coordinate of the region’s centroid in the same coordinate system as the robot map
poseZ	float	the Z coordinate of the region’s centroid in the same coordinate system as the robot map
poseXr	float	the region’s rotation about the X axis
poseYr	float	the region’s rotation about the Y axis
poseZr	float	the region’s rotation about the Z axis
name	text	a human-readable identifier for the region
annotation	image	a 2D and/or 3D graphical representation

In some examples, the geometry of regions may be broken into the components of their centroid and offsets from the centroid to allow for the position and rotation of many objects to be updated quickly. When CPU resources permit, the bounding box of the final coordinates (the polygon points relative to the centroid, transformed by the centroid’s pose into the map’s coordinate system) can be indexed using an R*-tree or similar data structure for fast lookup based on geometric constraints. The points comprising the region’s polygon may be stored in clockwise (or counter-clockwise) order to facilitate point-in-polygon tests based on ray-tracing algorithms.

As an example, a tag indicating a region that is a slow zone may have a data structure as provided below in Table 5.

TABLE 5

Name	Value
type	speedZone
subtype	explicit
maxXVelocity	0.75
maxYVelocity	0.0
maxThetaVelocity	0.75

Table 5 illustrates an example of a slow-zone tag in which the speed limits are explicitly set based on values associated with the region itself. Alternatively, a region may be defined in such a manner that a robot may interpret the region as a

slow zone. For example, in Table 6 below, a robot may interpret a region defined as an intersection as a slow zone and reduce its speed to a predetermined velocity.

TABLE 6

Name	Value
type subtype	speedZone intersection

Tags associated with points or regions on a map may include tag coordinates, tag information, and tag annotations of any of a wide variety. Additionally, the tags may be implemented using any of a wide variety of data types, including those illustrated above in Tables 1-6. The terms tag information and tag annotation are referred herein as separate elements. However, according to various embodiments, a tag annotation may be a part of the tag information. Specifically, a data structure may or may not include a distinct field for the tag annotation. Rather, a field in the data structure for the tag information may incorporate the tag annotation.

FIG. 8F provides an exemplary arrangement 800f of operations for operating the robot 100 to navigate about an environment using the plan view map 810 and the robot map 820. The operations include receiving 802f a plan view map 810 corresponding to an environment of the robot 100, moving 804f the robot 100 in the environment to a layout map location 812 on the plan view map 810, recording 806f a robot map location 822 on a robot map 820 corresponding to the environment and produced by the robot 100, determining 808f a distortion (two-dimensional) between the robot map 820 and the plan view map 810 using the recorded robot map locations 822 and the corresponding layout map locations 812, and applying 810f the determined distortion to a target layout map location 814 to determine a corresponding target robot map location 824, thus allowing the robot to navigate to the selected location 814 on the plan view map 810. In some implementations, the operations include determining a scaling size, origin mapping, and rotation between the plan view map 810 and the robot map 820 using existing tagged locations and resolving a robot map location corresponding to the selected target layout map location 814. The operations may include applying an affine transformation to the determined scaling size, origin mapping, and rotation to resolve the robot map location. Any of the above operations may be repeated any number of times in order to increase accuracy and/or efficiency. For example, moving 804f the robot 100 in the environment and recording 806f a robot map location may be repeated multiple times in order to gather sufficient correlation points for the subsequent transformations and calculations between the layout map and the robot map.

Other details and features combinable herewith can be found in PCT application Serial No.: PCT/US11/60935, filed on Nov. 16, 2011, which is hereby incorporated by reference in its entirety.

Referring to FIGS. 9A and 9B, in some implementations, the teleoperation software application 601 displays a hybrid three-dimensional image map 622b (hybrid map) in the map window 620. The hybrid map 622b may be a combination of the remote view 612 displayed in the remote video feed window 610 and a plan view map 810, such as the two-dimensional, top-down map 622a displayed in the plan view map window 620 (FIG. 6D). FIG. 9A illustrates a remote video view 612 that a user may see when the robot 100 is

positioned in a hallway. FIG. 9B illustrates a hybrid map 622b in which the plan view map 810 is partially overlaid and modified to fit the remote view 612, indicating the room numbers and/or room types of the areas in the field of view of the robot 100. When viewing a live video feed, the user may place the cursor over the window and start moving the scroll wheel upward. During the transitional process, the perspective video view (from the camera 320 on the robot 100) is progressively transitioned between the remote video view 612 and the map 622. The map 622 is fully warped at the start of the transition to map the perspective remote video view 612, and gradually reverts to its unwarped view at the end of the transition. So if the mouse wheel is 30% up, then the user sees a dissolved image which contains 70% video and 30% map, and the video portion is 30% de-warped, while the map is 70% warped. This implementation allows for a single view to fluidly represent both a perspective live remote video view 612 and a map 622.

To provide the hybrid map 622b, the teleoperation software application 601 may determine a distortion (between two-dimensional coordinates and three-dimensional coordinates) between the remote view 612 and the plan view map 810 using recorded robot map locations 822 of a robot map 820 and corresponding layout map locations 812 and then applying the determined distortion to fit the plan view map 810 to the remote view 612. In some implementations, determining the distortion includes determining a scaling size, origin mapping, and rotation between the plan view map 810 and the remote view 612, for example, by applying an affine transformation to the determined scaling size, origin mapping, and rotation. Determining a distortion between a two-dimensional plan view map and a three-dimensional video feed may include determining a coordinate transformation between the disparate coordinate systems.

Referring to FIGS. 6D and 10A-10E, in some implementations, the user interface 605 provides a look-ahead command 624 that causes the display of a rendered look-ahead view 612a in the map window 620, a dedicated separate window, or some other window. While driving the robot 100, the user may invoke a look-ahead command 624, which causes the robot 100 to stop moving physically, while the teleoperation software application 601 generates and displays a rendered look-ahead view 612a providing a perspective view of a proposed robot drive path as if the robot 100 were continuing to move along its drive path. This may be accomplished by using the map data, such as location of walls, and constructing a perspective “virtual reality” view based on the virtual location of the robot 100. For example, the telepresence software application 601 may use the plan view map 810, the robot map 820, and/or stored image data 701 (FIG. 7) to construct the look-ahead view 612a. For robot systems using a cloud computing service 720, such as the example shown in FIG. 7, the telepresence software application 601 and optionally the robot 100 may communicate with the cloud computing service 720, which may construct the look-ahead view 612a based on stored image data 701, the three-dimensional map 705, and/or the two-dimensional height map 707 (or alternatively a 2.5D hybrid map) and then provide the look-ahead view 612a for rendering in the map window 620. This implementation allows the telepresence software application 601 to leverage the scalable computer processing and data storage capability of the cloud service (e.g., the cloud service 720 can elastically scale up to process the data and then scale down afterwards),

thus reducing a processing and memory requirement for a computing device executing the telepresence software application 601.

FIG. 10A illustrates an exemplary remote view 612 of the remote video feed window 610 of the telepresence software application 601. FIG. 10B illustrates a complementary map 622 displayed in the map window 620. The map 622 provides the current location of the robot 100 as denoted by the robot icon 650 along with a camera field of view 322 for a robot camera 320. FIGS. 10C and 10E provide exemplary look-ahead views 612a displayed in the remote video feed window 610. The remote video feed window 610 may continue to display the remote view 612 from the robot camera 320 in a picture-in-picture window, for example, placed in a corner of the remote video feed window 610. FIGS. 10D and 10F provide exemplary maps 622 displayed in the map window 620. While executing the look-ahead command, the telepresence software application 601 may render the robot icon 650 at the robot's current location along with the robot's camera field of view 322. In addition or alternatively, the telepresence software application 601 may render in the plan view map window 620 a virtual robot icon 650a moving along a look-ahead path along with a projected look-ahead camera field of view 322a.

In some implementations, as the user drives the robot 100 along a corridor using a joystick in communication with the telepresence software application 601, the user may invoke the look-ahead command 624 (e.g., by selecting a corresponding button on the user interface 605 or the joystick). For example, at a location 50 feet away from a turn in the corridor, the user may invoke the look-ahead command 624, causing the generation of a look-ahead view 612a and stopping further movement of the robot 100 along the corridor. The user may continue, however, to virtually move the robot 100 in a look-ahead mode. The user interface 605 may display the look-ahead view 612a (e.g., a three-dimensional model) of the same corridor at the same position. As the user drives forward in the look-ahead mode, continues 50 feet, turns left, and continues driving, the user can see the location of rooms and other corridors along the way in the three-dimensional model/look-ahead view 612a. In some examples, for the first 30 feet of "virtual" driving, the telepresence software application 601 may display a blend of the actual view (from the stationary physical robot, further magnified and perspective-warped to match the virtual location) and the three-dimensional model/look-ahead view 612a.

FIG. 10G provides an exemplary arrangement 1000 of operations for executing a look-ahead mode of the telepresence software application 601. The operations include initiating 1002 the look-ahead mode (also referred to as the flythrough mode) and checking 1004 an actual localization of the robot 100, such as a current pose and/or coordinates of the robot 100. The robot 100 may determine its localization based on received sensor signals of its sensor system 400 and then forward the localization to the telepresence software application 601 and/or a cloud computing service 720. The operations further include creating 1006 a virtual localization and/or pose of the robot 100. The telepresence software application 601 or the cloud computing service 720 may use a dynamics model 570 (FIG. 5) associated with the robot 100 and image data 701 (FIG. 7) (e.g., volumetric point cloud image data) to generate the virtual localization and/or pose. The operations may include accessing 1008 three-dimensional rendering data corresponding to the determined virtual robot localization and generating 1010 a three-dimensional rendering of the robot 100 and/or local

environment about the robot 100. This may entail accessing image data 701 (e.g., volumetric point cloud image data) and/or the three-dimensional map 705 stored locally or remotely in cloud storage 722 to construct the local three-dimensional model/look-ahead view 612a, which may be displayed by the telepresence software application 601 in the remote video feed window 610. Moreover, this may entail generating a three-dimensional model of the robot 100 illustrated by the virtual robot icon 650a and the projected look-ahead camera field of view 322a in the map window 620. The operations may include updating 1012 the displayed look-ahead view 612a or a first person point of view (POV) and updating a virtual localization/pose of the robot 100 as the robot 100 virtually maneuvers about in the look-ahead mode. Steps 1008-1014 can be repeated (e.g., on a periodic basis) until terminating 1016 the look-ahead/flythrough mode.

Referring to FIG. 11A, in some implementations, the user interface 605 of the telepresence software application 601 displays a remote navigation view 612b in the remote video feed window 610 (or another window). The remote navigation view 612b may have a navigable area 616 rendered over the live video feed of the remote view 612. The user may toggle between the remote view 612 and the remote navigation view 612b. The navigable area 616 may be determined based on the plan view map 810 and/or the robot map 820. The navigable area 616 may be shown as a bounded area with a field of view 832 of the robot camera(s) 320, 450, excluding obstacles. Moreover, the navigable area 616 may be filled with a color or other signal that communicates to a user that the navigable area is free of obstacles or other impediments.

Navigable area on the layout map may be highlighted based on information in the robot's internal obstacle map. In one embodiment, the navigable area may be identified as white-colored pixels in the image. The robot may return its position on the robot map and the position and orientation of the 3D depth camera. A processor may use the robot position and the kinematic state (e.g., pan and tilt angles) of the head camera to determine which pixels on the video screen represent the ground plane. That is, the processor may utilize the robot position and the perspective of the video feed to calculate the coordinates for each ground level pixel on the video feed. The white-colored pixels designating the navigable areas may then be overlaid on the ground level pixels on the video feed. Accordingly, the robot and/or a user controlling the robot could identify navigable areas by following the white-colored pixels. In alternative embodiments, any color pixel or other identifying mark could be used. Alternative data structures or marks could be used in place of white-colored pixels. Specifically, from the robot's POV the coordinates of ground level pixels that are navigable could be tagged in any of a wide variety of ways, so long as the robot is configured to recognize them.

The user may select a robot destination 618 in the navigable area 616, which causes the telepresence software application 601 to issue a drive command to the robot 100 to move to a location corresponding to the selected robot destination 618. In the example shown, the remote video feed window 610 of the user interface 605 provides a remote navigation view 612b of the robot 100 in a hospital room. The user selects a robot destination 618 as a location in the room next to a patient bed. The telepresence software application 601 may use the plan view map 810, robot map 820, three-dimensional map 705, two-dimensional (or 2.5D hybrid) height map 707, and/or stored image data 701 to resolve a distortion (within the same dimension and/or

between dimensions) between the selected robot destination **618** on the remote navigation view **612b** and a corresponding robot map location **824**. The telepresence software application **601** may then issue a drive command to the robot **100** to maneuver autonomously or semi-autonomously to the robot map location **824**, using its sensor system **400** and behavior system **510a** to avoid any obstacles, such as moving people.

In one example, a map may be returned from a robot API call as an image, such as a PNG, JPG, or TIFF image. The robot could process the image in order to detect the pixels (e.g., black-colored pixels) that form the outline of an obstacle in the image. A curve fitting algorithm could be used to process the pixels that form the outline of the obstacle. The resulting curve(s) could then be used to generate an obstacle map. Additional processing may be done to further improve the obstacle detection and/or improve the accuracy of the curves fitting the detected obstacle outlines. For example, if a curve closes and forms a shape similar to a circle, the obstacle map could simply use a circle as a replacement. A similar idea could be applied to shapes like rectangles or ovals, people, faces, and/or those objects approximating a database of known object shapes from various perspectives.

The user interface **605** may provide a proximity sensor window **670** which displays a proximity of obstacles within a sensor field of view **442**, **452** (e.g., within a three-dimensional imaging sensor field of view **452** and/or a laser scanner field of view **442**).

In some implementations, the user may mark a protected region/zone on the remote video feed window **610** and/or the plan view map window **620** (not shown), using an avoid tag **662**, **662i**. A protected zone may be treated by the robot **100** as an object **12**, and accordingly, protected zones may be avoided during autonomous navigation. Protected zones can be used to help create a wide berth around delicate equipment, or in order to ensure that the robot avoids other areas. The user may place an avoid tag **662**, **662i** on the plan view map **810** in the tagging view **660** or on the remote navigation view **612b**. Moreover, the user may place other tags **662** on the remote navigation view **612b**. The telepresence software application **601** may resolve a distortion between the remote navigation view **612b** and the plan view map **810** and/or robot map **820** and then update the robot map **820** accordingly.

For example, determining a distortion between a plan view map and a video feed may comprise creating a transformation mapping between coordinate points in any of the navigation view **612b**, the plan view map **810**, and/or the robot map **820**. Similar to overlaying a restricted region on a ground level in a video feed, the ground level of two-dimensional maps may be effectively coordinate-mapped onto a detected ground level in a video feed provided by a robot.

FIG. **11B** illustrates a flow chart of an exemplary arrangement **1100** of operations for a method of robot navigation (e.g., semi-autonomous) to a selected robot destination **618**. The method includes identifying **1102** a navigable area **616** within a field of view **322**, **442**, **452** of the robot **100**. Identification of navigable areas **616** may be accomplished using the sensor system **400** of the robot **100**. The method also includes visually indicating **1104** the navigable areas **616** on the user interface **605**, for example by displaying a bounded area (e.g., highlighted boundaries, filled with a color or pattern) on the remote navigation view **612b**. The method may include receiving **1106** a user selection of a robot destination **618** and determining **1108** whether the

robot destination **618** is within the identified navigable areas **616**. If the robot destination is outside of identified navigable areas **616**, the method includes prompting **1110** the user for a valid robot destination **618** within the navigable area(s) **616**. If the robot destination **618** is within identified navigable areas **616**, the method may include determining **1112** a route to the robot destination **618**. This may entail determining a distortion between the remote navigation view **612b** and the robot map **820** and then resolving a robot map location **824** corresponding to the selected robot destination **618**. The method includes allowing **1114** the robot **100** to navigate (autonomously or semi-autonomously) to the robot destination **618**.

FIGS. **11C** and **11D** illustrate exemplary remote navigation views **612b** where the user selected a robot destination **618** either beyond a navigable area **616** or on an obstacle **1120** (either actual or perceived by the robot **100**). In the example shown in FIG. **11C**, the user selected a robot destination **618** on a perceived obstacle **1120a**, a ramp **1122**. From a distance, the robot sensor system **400** may discern the ramp **1122** as an obstacle, because from a distance the ramp **1122** may have a perceived height above a threshold traversal height of the robot **100**. Moreover, the robot behavior system **510a** may execute an ODOA behavior **512c** in response to sensor events raised due to sensor signals of the sensor system **400** indicating an obstacle having a height greater than the threshold traversal height. Using the plan view map **810** and/or the robot map **820**, the robot **100** may determine that its local perception of the environment may be inaccurate, and that the ramp **1122** is not an actual obstacle, but is rather a perceived obstacle **1120a**.

Although the ramp **1122** is within the navigable area **616**, the telepresence software application **601** may determine the robot destination **618** on the ramp **1122** is an unsafe location to stop. The telepresence software application **601** may display an alert dialog box **1130**, noting that the selected robot destination is an unsafe location to stop. In the example shown, the alert dialog box **1130** indicates that the user selected a ramp **1122** for the robot destination **618** and offers an alternative robot destination **619** just before the ramp **1122**. Stopping the robot **100** on the ramp **1122** may be hazardous for people near the robot **100** and for the robot **100** itself, if the robot **100** tips or rolls down the ramp **1122**. By determining that the robot destination **618** is on the ramp **1122**, the telepresence software application **601** can either prohibit such a robot destination **618** and/or offer a safe alternative destination **619**, in this case before the ramp **1122**.

Referring to FIG. **11D**, when the user selects an actual obstacle **1120b**, the telepresence software application **601** may display an alert dialog box **1130**, noting that the selected robot destination **618** is outside of the navigable area **616** or an obstacle **1120**. In the example shown, the alert dialog box **1130** indicates that the user selected an obstacle **1120b** for the robot destination **618** and offers an alternative robot destination **619** just before the obstacle **1120b**.

Referring to FIG. **12**, in some implementations, the remote navigation view **612b** displayed by the user interface **605** of the telepresence software application **601** allows a user to specify a robot path **652** to a selected robot destination **618** in the navigable area **616**. The user may specify the robot path **652** using a variety of input devices. For example, on a touch screen display, the user may drag his/her finger or a stylus from the robot icon **650**, denoting the current robot position, to the robot destination **618**. In additional examples, the user may drag the robot icon **650** (e.g., using a mouse or touch gesture) along the prescribed

robot path **652** to the robot destination **618**. In the example shown, the user may select a set path button **1202** on the user interface **605** allowing the user to indicate that a gesture performed within the navigable area **616** should be interpreted as the robot path **652**. The user may trace the robot path **652** within the remote video feed window **610**. Similarly, the user may select the robot path **652** on the plan view map **810** displayed as the two-dimensional map **622a** in the map window **620**. After setting the robot path **652**, the user may press a go button **1204** to set the robot **100** into motion. Similarly, a stop button **1208** may be used to stop the motion of the robot **100**. A clear path button **1206** may remove or clear the set robot path **652** from the remote navigation view **612b**.

A display window may include a fly-out icon panel that is revealed by a mouse-over. For example, the icon panel may “fly” out from the top left of the window. The icon panel may allow a user to select a manual drive, a click-to-drive, and a head motion icon. In one embodiment, the a user may toggle through the icons using the space bar. Manual drive may allow a user to click-to-destination and/or click-and-drag a path. After drawing a path on the map, the user may right-click and select “Save Path” from the popup menu. They can give a name to the path. Later the user may “Load Path”, and the robot will navigate to the starting point of the path, and then navigate along the prescribed path to the destination. The path may be stored as a tag data structure, including tag coordinates and tag information. The tag path include multiple stops along the way. When drawing the path, the user may indicate way points along the path. In some embodiments, the way points may be represented by tag annotations that include stop signs. Later, when traversing the path, upon reaching a way point, the robot may flash the “stop” button and the path may become lighter and/or translucent. At this point the user may perform a consult and do local driving, then click “go” to resume the path. Accordingly, a physician can save a path for his evening rounds, hitting all the rooms and stations in a preferred order and with a pre-planned route.

In head mode, a user may draw a box or outline on a portion of a video feed in order to center the head (upper portion) of the robot on the center of the box or an object within the box. Additionally, a user may click a location in order to change the heading of the head (upper portion) of the robot and/or the entire robot. Various button and peripheral control toggles may be used to independently control the base (lower portion) and head (upper portion) of the robot. For example, holding the shift key while in the head mode may make the cursor a hand icon on the screen and allow the user to grab and drag the viewpoint of the head.

In some embodiments, a star icon may be used to control the navigation of the robot. The star icon may be displayed in any of the various views and may be selectively moved by the user to change the direction and/or velocity of the robot. Alternative icons in addition to a star icon may be used.

Returning to FIG. 12, a virtual joystick window **680** may provide another input device for specifying the desired path **652** or to manually control of the robot **100**. The virtual joystick window **680** may display a robot orientation indicator **682** and a navigation vector **684**. A user may control the direction and speed of the robot **100** using the navigation vector **684**. A virtual joystick may facilitate control of the robot **100** by the user of a device that may not typically have a mouse or conventional joystick, such as a tablet computer.

A “stitched” video image may be displayed in the virtual joystick window **680**. The “stitch” video and image may be generated using a live downward pointing camera **320**, **450**

on the front of the robot **100** and using a live downward pointing camera on the rear of the robot **100**. A user may grab (e.g., using a mouse or touch gesture) and drag on robot motion indicator **686** in order to specify a direction of robot movement and a drive velocity. Driving the robot **100** from the virtual joystick window **680** has advantages over using the remote video feed window **610** for mouse-based or virtual joystick driving. Specifically, this view may reduce lens distortion, lack of depth information, and perception issues based on the rotation of the robot head **160** that a user may experience while driving the robot **100** using the video feed displayed in remote video feed window **610**.

In addition to allowing the user to specify a desired path within the remote video feed window **610**, the user may specify the robot path **652** on the map **622** displayed in the map window **620**. Specifying the robot path **652** in the plan view map window **620** may allow the robot **100** to navigate over longer distances, and thus may free the user to perform other tasks while the robot **100** is in transit. Various controls may also be provided in order to manipulate the zoom and displayed area of the map **622** shown in the map window **620**. A desired zoom may be specified using slider **1210**, and a desired area may be displayed using an area pan control **1212**.

Accordingly, a non-technical user may be able to navigate from one location to another using any combination of the various navigation methods and controls. For example, in long-distance travel, a user may click a destination on a plan view map and the robot may autonomously navigate to the selected location. In mid-range travel, the user may select a destination in a video window of a location within the field of view of the robot. In close range travel, the user may manually control the robot’s navigation path, rotations, head movements, and the like using a mouse, joystick, virtual joystick, or meta-joystick.

FIG. 13 illustrates an exemplary user interface **605** of the telepresence software application **601** having a maximized remote video feed window **610** displaying a remote navigation view **612b** that accepts hyper-tags **1310** and/or context sensitive commands selectable by the user. The user interface **605** includes the local video window **630** and the plan view map window **620** overlaid on the remote video feed window **610**. In the example shown, the plan view map window **620** displays a three-dimensional (three-dimensional) map **622c**. The three-dimensional map **622c** may be utilized by the user to cause the robot **100** to navigate semi-autonomously to a selected robot destination **618** on the three-dimensional map **612c**. In some implementations, a virtual three-dimensional grid **1302** is displayed in the remote navigation view **612b**. Using a determined distortion between the plan view map **810** and the robot map **820**, the telepresence software application **601** can determine the location of the floor surface **5** in the live video feed to overlay the three-dimensional map **622c**. The user may select a grid square **1304** as a robot destination **618** on the virtual grid **1302** in order to cause the robot **100** to autonomously navigate to the selected grid square **1304**. The virtual three-dimensional grid **1302** may allow for improved precision in the positioning of the robot **100**.

In the example shown, a variety of hyper-tags (tags) **1310** providing context-sensitive actions are displayed and made available to a user. The context-sensitive actions include an approach command **1312** and a follow command **1314**. These context-sensitive actions may be generated upon the identification of a person **1330** within the field of view **322**, **442**, **452** of the robot **100**. The user may invoke the approach command **1312** in order to position the robot **100** in front of

the person 1330. The approach command 1312 may cause the execution of an approach behavior 512a (FIG. 5) by the robot behavior system 510a, whereby the robot 100 identifies the person 1330 using its sensor system 400 (e.g., using facial recognition) and drives to face the identified person 1330. The user may invoke the follow command 1314 to drive the robot 100 behind the person 1330 and follow at a three-foot distance. The follow command 1314 may cause the execution of a person follow behavior 512b (FIG. 5) by the robot behavior system 510a, whereby the robot 100 identifies the person 1330 using its sensor system 400 (e.g., using facial recognition) and drives to follow the identified person 1330. In some examples, the robot 100 may detect individuals within its field of view 322, 442, 452 using a facial recognition routine. A label 1340 may be displayed that identifies the individual. For example, the information may include name, title, occupation, address, business address, email address, web-page address, user notes, etc.

The telepresence software application 601 may determine a distortion between the displayed two-dimensional map 622a and the first-person video feed captured by the robot camera 320. Determining such a distortion may include determining a coordinate transformation between the two-dimensional map and the three-dimensional "map." When the user places a tag 662 and/or hyper-tag (which may comprise a tag) 1310 either on the remote view 612 of the remote video feed window 610 or on the two-dimensional map 622a of the map window 620, the telepresence software application 601 may apply the distortion to tag map coordinates associated with the tag 662 and/or the hyper-tag 1310 to determine corresponding video coordinates or plan view map coordinates, respectively, and overlay a tag annotation associated with the tag 662 or hyper-tag 1310 on the displayed remote view 612 (i.e., first-person video feed) or the map 622, respectively, using the determined video or map view coordinates. In various embodiments, the three-dimensional rendition of the tag annotation may be dynamically re-rendered based on the current position of the remote telepresence robot and a perspective of the tag relative to the video feed. Accordingly, as the location of the robot and/or the perspective of the live video feed changes, such as when the head (upper portion) of the robot pans or tilts, the tag annotation may be dynamically re-rendered. For example, a tag annotation corresponding to a ramp may be overlaid in the video feed with respect to the floor. Similarly, a tag annotation associated with an object on a wall may be overlaid with respect to the object or the wall.

As described herein, the tag may include tag information comprising a robot action modifier. The tag may be interpreted by a robot operator, a local terminal, or the remote telepresence robot and cause the robot to execute a predetermined action. For example, the robot action modifier may direct a robot to not enter a specific area, to travel slow through a certain area, to travel fast through a certain area, to use extra caution, and/or to perform other actions. Tags in general may include any of a wide variety of information, such as an availability of a wireless communication signal, a speed the remote telepresence robot should travel, a location of a point of interest, a location of a person, a location of a docking station, a location of a rest area, a location of a glass wall, a location of a ramp, a location of an object, an optimal route to navigate a tight area, an optimal route to navigate a congested area, and an action a remote telepresence robot should execute. The tag may be created by a user, automatically by a terminal, automatically by a robot, and/or in response to historical data collected by the terminal and/or robot.

The robot may include a tag identification system configured to identify tags having tag coordinates encountered along a navigation path. A robot may "encounter" a tag when the tag coordinates are within the local perceptual space of the robot and/or the tag coordinates are relevant to an objective, planned navigation path, or the planning of a navigation path. Accordingly, a tag identification system may "encounter" a tag along a navigation path, even if the robot is not yet in proximity and/or may never be in proximity to the tag coordinates of the tag.

A robot and/or remote terminal determining a navigation path for a robot may take into account tags or potential tags that could influence the navigation path. Accordingly, the tag identification system may be used to identify tags having tag coordinates projected to be along potential navigation paths during the determination of a navigation path. For instance, several potential navigation paths may be used to reach a desired destination and the selection of which navigation path will be used may depend on the tags relevant to each of the potential navigation paths. A robot selecting between multiple potential navigation paths may identify relevant tags in order to determine which navigation path would provide the best wireless connectivity. Other factors, such as ramps, elevators, distance, congestion, objects,

In the exemplary user interface 605 shown, the dashboard window 640 provides a battery charge status, a wireless signal strength indicator, and a robot outline having portions that may light up when service is required. An options window 690 allows the user to disconnect or dock the robot with a docking station and set software and/or robot options.

Referring to FIG. 14, in some implementations, while executing the person follow behavior 512b, the robot 100 may detect, track, and follow a person 1330. Since the robot 100 can pan and tilt the head 160 using the neck 150, the robot 100 can orient the second three-dimensional image sensor 450b to maintain a corresponding field of view 452 on the person 1330. Moreover, since the head 160 can move relatively more quickly than the base 120 (e.g., using the drive system 200), the head 160 (and the associated second three-dimensional image sensor 450b) can track the person 1330 more quickly than by turning the robot 100 in place. The robot 100 can drive toward the person 1330 to keep the person 1330 within a threshold follow distance range D_F (e.g., corresponding to a sensor field of view). In some examples, the robot 100 turns to face forward toward the person/user 1330 while tracking the person 1330. The robot 100 may use velocity commands and/or waypoint commands to follow the person 1330.

Additional details and features concerning person recognition and person following can be found in PCT application serial number PCT/US11/35488, filed on May 6, 2011, which is hereby incorporated by reference in its entirety.

FIGS. 15A and 15B illustrate alternative three-dimensional maps 622c and two-dimensional maps 622a displayable in the plan view map window 620 that include hyper-tags 1310 associated with various information and that may be used to cause the robot to navigate autonomously to a particular destination. The hyper-tags 1310 may include information about various locations or information related to patients. A user may add labels 1502 or mark-ups 1504, such as personal notes, shared notes, sketches, drawings, etc. A robot location 1510 may also be identified. A user may specify a robot destination 1512, such as a nurse's station. The robot 100 may navigate autonomously to the specified robot destination 1512.

The telepresence software application 601 may display information on the remote video view 612 and/or a map 622,

indicating physical areas of interest. For example, a small arrow with an attached bubble reading “Pharma” may indicate the location of the pharmacy room. Such a bubble could comprise a tag. For example, the tag could include tag coordinates indicating where the word “Pharma” should be displayed; tag information, such as relevant information related to the pharmacy; and a tag annotation, such as a graphical representation in two-dimensional and/or three-dimensional of the word “Pharma.” In some examples, the user can determine what information is available about nearby rooms by placing the mouse over or gesturing over that area, causing the display of any corresponding available information. With this information, the user can quickly choose to go to a destination (e.g., the pharmacy room) by selecting a robot destination **618** in the remote navigation view **612b** (FIG. 12).

For example, according to one example a robot or remote terminal could retrieve tag coordinates that correspond to tags associated with a robot map. Using the robot position, tags that are in close proximity to the robot may be identified. Tags within the field of view of the robot may be identified using the orientation of the robot’s head (upper portion). The robot and/or remote terminal could then calculate a set of coordinates for all of the pixels on the video screen and render a tag annotation associated with each tag within the line of sight based on the position of the robot and the perspective provided by the robot’s current head orientation (pan and/or tilt). According to some embodiments, Denavit-Hartenberg parameters (DH parameters) may be used as a standard coordinate system for spatial linkages between the video feed and the map plan view.

Referring again to FIG. 8E, the tagging view **660** of the user interface **605** allows the user to place tags **662** on a plan view map **810** to designate locations of interest and/or mark the plan view map **810** with information, such as obstacles, preferred robot travel routes, etc. Referring also to FIG. 13, the user may place hyper-tags **1310** on the remote navigation view **612b** to mark locations with context-sensitive information. The map data source **1620** may store the tagging and hyper-tag information (e.g., locations, tag identifiers, tag content) along with layout map and/or robot map information. As used herein, hyper-tags may be embodied as tags and use a similar data structure to tags, as described herein.

In addition or alternatively to allowing the user to place tags **662** and hyper-tags **1310** in the user interface **605**, the user may enter user-specific hyper-tags **1310** during operation of the robot **100**. The user may invoke a command that allows for the insertion of a hyper-tag **1310** at a current robot location. Another command may allow for the removal of the hyper-tag **1310**. Further, other users (e.g., nurses) may be allowed to add hyper-tags **1310** that may be shown to a user of the robot **100**. A “nurse map application” may display a top-down map or a tagging view **660** that allows placement of temporary hyper-tags **1310**, for example, to identify rooms of interest to a doctor who may soon be logging in. Moreover, some hyper-tags **1310** may be user-specific and/or time-specific. For example, a stroke patient in a room may be showing signs of deterioration. The nurse can call up the “nurse map application,” find that room on the map and enter a hyper-tag **1310**. The nurse may fill in a hyper-tag as follows: hyper-tag_name=“Stroke patient deteriorating,” user_specific=“Dr. Reynolds,” duration=1 hour. Thus, if Dr. Reynolds logs in within the next hour, he would see a hyper-tag **1310** associated with the patient’s room on the map additionally indicating “Stroke patient deteriorating.” On approaching that wing, he may also see a hyper-tag **1310** pop up pointing to that room in the video stream, labeled

“Stroke patient deteriorating.” No other doctor would see those labels, and Dr. Reynolds would only see them during that first hour.

A doctor may also set up temporary bookmark and reminder hyper-tags **1310**, directly at a local or remote station interface **606**, **608**, to assist with his/her work plan. In some examples, the doctor may assign numbers to several patient rooms at the start of the session. Then during the session, he/she may see the numbers on the displayed map **622** and in popup hyper-tags **1310** to remind him/her of the order in which to visit the patients **614**. The doctor may add notes which can be viewed through the remainder of the session or upon next returning, for example, “come back at end of session” on one patient, or “write prescription” or “check in again at 4 pm.”

Additionally, “smart” hyper-tags **1310** may be displayed automatically. For example, a nurse may enter photos of incoming patients **614** into a database (e.g., stored locally and/or on cloud storage **722**) cross-referenced with their electronic medical record. The telepresence software application **601** may execute a face recognition algorithm on a video stream captured by the robot camera **320** to identify the patients **614**, **1330**, which can be cross-referenced to the database. Upon recognition of a patient’s face, the telepresence software application **601** may automatically pull up and display the patient’s electronic medical record.

Referring again to FIG. 14, in some implementations, each patient **614**, **1330** receives a radio frequency identification (RFID) chip **497**, such as on a wristband. The robot **100** may have an RFID reader **498** in communication with the controller **500** as part of its sensor system **400** to recognize nearby patients via the RFID chip. The telepresence software application **601** may display a corresponding hyper-tag when the patient comes within RFID range (e.g., six feet) of the robot **100**. The hyper-tag **1310** may appear to be floating in the air, since RFID is not direction-specific. An alternative hybrid approach may use computer vision techniques to identify the existence of a patient **614**, **1330** in the field of view **322** of the robot **100** by identifying a human face, and then assuming that the RFID match belongs to that patient and localizing the hyper-tag **1310** on the patient **614**, **1330**.

Referring to FIGS. 16A-16D, in some implementations, a robot system **1600** includes one or more telepresence robots **100** in communication with a bridge **602**, which communicates with a local robot endpoint server **604a** and a remote endpoint server **604b** (e.g., such as the cloud computing service **720** (FIG. 7)). The local robot endpoint server **604a** communicates with a local technician computing device **606** and the remote endpoint server **604b** communicates with a remote operator computing device **608**. The robot system **1600** also includes one or more data sources **1610** for storing sensor data received from the robot sensor system **400** and/or user interaction data, such as information obtained from the user through the web pad **310** and/or the user interface **605**. In the example shown, the robot system **1600** includes at least one robot sensor data source **1610a** for storing sensor data and at least one head data source **1610b** for storing user interaction data. The data sources **1610** may reside on the robot **100**, cloud storage **722** (FIG. 7), the local robot endpoint server **604a** and/or the remote endpoint server **604b**.

A map data source **1620**, such as a database stored on the robot **100**, cloud storage **722**, the local robot endpoint server **604a** and/or the remote endpoint server **604b**, can store information for the plan view map **810**, the robot map **820**, tag **662** information, and/or hyper-tag **1310** information. The

map data source **1620** may be a single database or combination of data sources **1610**, such as the robot sensor data source **1610a** and the head data source **1610b**. The telepresence software application **601** and/or the robot **100** (e.g., the controller **500**) may access the map data source **1620** to execute real-time or off-line concordance processing, provide user interface feedback, perform navigation routines, render maps **622**, etc.

In some implementations, the control system **510** executing on the controller **500** of the robot **100** accesses one or more of the data sources **1610**, such as the robot sensor data source **1610a**, the head data source **1610b**, and/or the map data source **1620** to issue events recognizable by the behavior system **510a**. In response to raised events, the behavior system **510a** may execute one or more behaviors **512** that affect the selection of a command executed by the resource control arbiter **560** on the robot resources **530** (FIG. 5). In the example shown in FIG. 16C, the robot control system **510** communicates with the map data source **1620** to access a concordance matrix/database, which may store concordance process information, such as real-time sensor/flag data **1622a**, operator commands **1622b**, local perceptual space data **1622c** (e.g., volumetric point cloud data received from a three-dimensional image sensor **450**), occupancy bitmap data **1622d** (e.g., the robot map **820**), floor plan data **1622e** (e.g., the plan view map **810**), and an end-user tag table **1622f** (e.g., storing x, y, z coordinates and tag fields), and/or a robot behavior tag table **1622g** (e.g., storing x, y, z coordinates and tag fields). Referring also to FIG. 5, behaviors **512** of the behavior system **510a** may evaluate possible outcomes of robot actions based on raised events, such as sensor events from the sensor system **400** and tag events (e.g., which may mimic a sensor event) raised by placed tags **662**, **1310** stored in the tag tables **1622f**, **1622g**. Accordingly, the action selection engine **580** may select a feasible robot action having the best outcome based on behavior evaluations. As a result, the robot **100** may autonomously operate in a manner that takes into account the tags **662**, **1310** received by the telepresence software application **601**.

Referring again to the ramp example shown in FIG. 11C, when the robot **100** approaches a ramp **1122**, the robot control system **510** may perceive the ramp **1122** as an obstacle **1120**, based on sensor signals received from the sensor system **400**. In order to discern between a perceived obstacle **1120a** and an actual obstacle **1120b**, the control system **510** may need to access a common database, such as the map data source **1620**, storing robot data and user data. Using the map data source **1620**, the control system **510** can determine that the detected ramp **1122** is a perceived obstacle **1120a**, rather than an actual obstacle **1120b**. Moreover, the control system **510** may communicate with the telepresence software application **601** to receive a user input as to whether the user perceives the ramp **1122** as an actual obstacle **1120b** and/or to receive an alternative robot path **652** and/or an alternative robot destination **619**. The telepresence software application **601** can use the map data source **1620** to resolve distortions between two-dimensional maps **622a**, **810** and three-dimensional maps **622c**, between live video feeds in the remote view **612** and two-dimensional and/or three-dimensional maps **622a**, **622c** to provide hybrid maps **622b** (FIG. 9B). Moreover, the telepresence software application **601** can use the map data source **1620** to render the look-ahead view **612a** in the plan view map window **620** (FIG. 10C).

Referring again to FIG. 12, in additional implementations, when the user selects a robot path **652** on one of the two-dimensional map **622a**, hybrid map **622b**, three-dimen-

sional map **622c**, and the remote view **610**, the telepresence software application **601** can use the map data source **1620** to resolve distortions between any of the maps **622** and the remote view **612** and apply the distortion to the selected robot path to determine a corresponding sequence of robot path map coordinates on the robot map **820** for use by the robot controller **500** when executing a drive command to the destination **618**. Moreover, the telepresence software application **601** may apply the determined distortion(s) to resolve corresponding sequences of robot path coordinates for displaying the robot path **652** on any of the maps **622** and the remote view **612**. The map data source **1620** may store the determined distortions and/or the sequences of robot path coordinates for displaying the robot path **652** on any of the maps **622** and the remote view **612**.

Accordingly, it should be broadly understood that the term “distortion” as used herein relates to resolving spatial coordinate errors, differences of transformation from one coordinate system to another, including between coordinates systems of different dimensions. For example, a robot and/or remote terminal may determine a distortion between a two-dimensional plan view map and a two-dimensional map generated, at least in part, by a robot, such as those generated using various robot sensor or laser scans. Additionally, a robot and/or remote terminal may determine a distortion between a three-dimensional map or video feed and a two-dimensional plan view map. Moreover, determining a distortion may relate to transforming coordinates between first person views, third person views, plan view map views, hybrid map views, and/or between any two different coordinate systems or perspectives within the same coordinate system.

Referring again to FIG. 13, in some implementations, when the user places a tag **662** or hyper-tag **1310** on the plan view map **810** displayed as the map **622** in the map window, the telepresence software application **601** determines a user selected location on an electronic display displaying the map **622** and overlays an annotation associated with the tag **662**, **1310** on the map **622**. The telepresence software application **601** may also determine a distortion between the plan view map **810** and the remote view **610** (i.e., first-person video captured by the robot camera **320**) and apply the distortion to coordinates of the tag **662**, **1310** on the plan view map **810** to determine corresponding video coordinates of the remote view **610**. A tag annotation associate with the tag **662**, **1310** and stored by the map data source **1620** can be displayed by the telepresence software application **601** on the remote view **610** using the determined video coordinates.

Referring to FIG. 17, in some implementations, the user interface **605** provides an augmented overlay **1710**, for example, in the remote video feed window **610** and/or the map window **620**, that allows the user to visualize a position of the robot head **160** with respect to the robot base **120**. The augmented overlay **1710** may allow the user to appreciate a current field of view **322**, **442**, **452**, denoted by an arc **1720** in the example shown, of the robot sensor system **400** relative to a full 360 degrees field of view. This allows the user to make selections for rotation (e.g., of the head **160** and/or base **120**) which are outside the current field of view **322**, **442**, **452**.

The user may click within the zone defined by first and second rings **1722** and **1724** in order to rotate a virtual head **1728** to that point. As the user rotates the virtual head **1728**, the robot head **160** may move in real time with the telepresence software application **601** updating the live video feed from the robot camera **320** displayed in the remote view **612** of the remote video feed window **610** in real time as

well. In the example shown, the augmented overlay 1710 has a virtual base 1726 corresponding to the robot base 120 and a virtual head 1728 corresponding to the robot head 160 arranged at an angle/orientation with respect to the virtual base 1726 that corresponds to a current pose of the robot 100. In some examples, one of the virtual base 1726 and the virtual head 1728 is shown static while the other is free to move relative to the static one.

If the user clicks within the zone defined by the first and second rings 1722 and 1724 to rotate the head 1728 outside of the current field of view 1720, the robot 100 may rotate the head 160 and/or the base 120 in order to accomplish the user's command. In some examples, after rotating the head 160 according to the user command, the base 120 may rotate and the head 160 may then move to a center position. Such changes in position may be problematic if the user then attempts to reposition the robot 100 based on the previous rotation. To mitigate this, certain implementations may employ a system to reduce the requirement of base rotations in order to accommodate head rotations. For example, a counter may be initiated when the virtual head 1728 is turned to an angle. If the robot head 160 remains at that angle for a specified interval, the system may slowly rotate the base 120 in order to center the head 160 with respect to the base 120 while simultaneously rotating the head 160 in the opposite direction at the same speed. This keeps the current subject in view, while also ensuring that the head 160 and the base 120 are now in alignment and the forward frame of reference is dictated by where the user is looking. Further, if the user wishes to continue looking farther in that direction, the full panning range of motion of the head 160 is available.

FIG. 18 illustrates an exemplary sequence of robot events for responding to a user command, for example, in the telepresence software application 601. In an initial state, the robot 100 may receive a drive command to move from one location to another. The command may be operator-initiated, behavior-initiated (e.g., of a behavior executing on a control system of the controller), or planner-initiated (e.g., a pre-planned task or routine). In this example, the command includes a new heading for moving in an opposite direction to a new destination. In response to the command, the robot 100 may turn its head 160 (left or right) toward a panning limit. After reaching the panning limit, the robot 100 may rotate the base 120 (e.g., holonomically in place), to allow movement of the head 160 in order for the head to turn toward the new heading. The term "panning limit" may refer to a point when the upper portion of the robot cannot physically rotate anymore with respect to the lower portion of the robot, a point where the upper portion is misaligned with respect to the lower portion a predefined number of rotational degrees, and/or the term "panning limit" may be a function of the number of degrees the upper portion is misaligned with respect to the lower portion and the length of time the upper portion has been misaligned with respect to the lower portion.

In some examples, the robot 100 continues to rotate the base 120, so that the forward drive direction F coincides with the new heading, thus providing the head 160 relatively equal left/right panning ability. As the robot 100 rotates the base, it may simultaneously rotate the head 160 so as to face the heading and optionally so that a field of view 322, 452 of a sensor 320, 450, 450b on the head 160 can point along the new heading. In some implementations, the robot 100 turns the base 120 and the head 160 together, so as to allow

the head 160 to face the new heading relatively quicker. If the base 120 over-rotates, the head 160 can counter-pan to recover alignment.

FIG. 19 illustrates an exemplary remote view 612 where the telepresence software application 601 overlays a screen indicator 1910 on the remote video feed received from the robot 100. The screen indicator 1910 may be displayed near a mouse cursor 1912 and may represent a current head range of motion. As the user moves the mouse cursor 1912 toward the left or right side of the remote video view 612 (with the probable intention of clicking to move the head to point there), the on screen indicator 1910 may be displayed above the cursor 1912 to indicate how much head motion remains in that direction (e.g., how much remaining range of motion of the head 160 is available).

A highlight box 1920 may highlight an area of interest within the remote video view 612. The user may create the highlight box 1920 around an area of interest on a portion of the remote video view 612, for example, by dragging and dropping a box onto the screen and/or by clicking and dragging open a box around the area of interest. In response, the telepresence software application 601 may cause the robot head 160 to move to center on the highlight box 1920. Moreover, the camera 320 may zoom in to match the dimensions of the highlight box 1920.

Referring to FIGS. 20A-20B, in some implementations, if the robot 100 unexpectedly loses communication connectivity (e.g., a loss of the wireless signal), the robot 100 may stop or continue driving to its destination. As a telepresence robot moves throughout an environment, communication may be disrupted, for example, as the robot 100 transitions between various wireless access points and/or encounters disruptions in the data transmission as a result of poor signal strength. By continuing to navigate autonomously, communication may be restored by the time the robot arrives at a desired destination.

When the robot 100 experiences a loss of communication connectivity, the robot 100 may refer to a last trusted localization/pose (e.g., stored locally by the controller 500) and/or a current determined localization/pose (e.g., based on the robot sensor system 400) to continue navigating to the destination. If the robot path is a planned path, the robot 100 may resume the planned path to the destination. On the other hand, if the user was teleoperating the robot 100 to the destination, the robot 100 may follow a planned path to a nearest/last trusted location having communication connectivity (e.g., radiofrequency and/or wireless). Alternatively, the robot 100 may drive along a shortest path (i.e., a new path) to a nearest/last trusted location having communication connectivity.

After reaching the nearest/last trusted location, the robot 100 may determine if communication connectivity has been reestablished and if so, whether the destination has been reached. If communication connectivity was not reestablished, the robot 100 may synchronize its video recordings (and any other sensor data of the sensor system 400) to move to a next trusted location stored by the controller 500. Moreover, if the destination has not been reached, but communication connectivity was reestablished, the controller 500 may execute safe harbor countermeasures, which may entail continuing recording sensor data and displaying a new robot-side user interface (e.g., on the web pad 310) indicating that the session was terminated due to loss of communication connectivity. The robot 100 may improve its connectivity recovery percentage by reassessing and/or executing path planning to move to the last trusted location (using ODOA). The robot 100 may also move its antennas

490a, 490b (FIGS. 2 and 4C) to possibly gain better communication reception. The robot **100** may use a mobile ad-hoc network (MANET), which is a self-configuring infrastructureless network of mobile devices connected by wireless links.

In some examples, the robot **100** may improve the integrity/accuracy of the robot map **820** by marking the location of lost communications and any location of reestablished communications. The robot **100** may use waypoint navigation to move to an area having known connectivity (e.g., a WLAN warm zone or high signal zone). Waypoints are sets of coordinates that identify a point in physical space. The robot **100** may use waypoints established on the robot map **820** to maneuver to the destination.

Additional safe harbor countermeasures may include planning a path to a nearest lowest traffic area or moving to a nearest charging/docking station based on the robot map **820**. In some examples, the robot **100** may move toward another nearest robot **100**, which may use multiple antennas **490a, 490b** for multiple-input and multiple-output (MIMO) to act as a Wi-Fi bridge **602**.

Various implementations of the systems and techniques described here can be realized in digital electronic circuitry, integrated circuitry, specially designed application specific integrated circuits (ASICs), computer hardware, firmware, software, and/or combinations thereof. These various implementations can include implementation in one or more computer programs that are executable and/or interpretable on a programmable system including at least one programmable processor, which may be special or general purpose, coupled to receive data and instructions from, and to transmit data and instructions to, a storage system, at least one input device, and at least one output device.

These computer programs (also known as programs, software, software applications or code) include machine instructions for a programmable processor, and can be implemented in a high-level procedural and/or object-oriented programming language, and/or in assembly/machine language. As used herein, the terms “machine-readable medium” and “computer-readable medium” refer to any computer program product, apparatus and/or device (e.g., magnetic discs, optical disks, memory, Programmable Logic Devices (PLDs)) used to provide machine instructions and/or data to a programmable processor, including a machine-readable medium that receives machine instructions as a machine-readable signal. The term “machine-readable signal” refers to any signal used to provide machine instructions and/or data to a programmable processor.

Implementations of the subject matter and the functional operations described in this specification can be implemented in digital electronic circuitry, or in computer software, firmware, or hardware, including the structures disclosed in this specification and their structural equivalents, or in combinations of one or more of them. Embodiments of the subject matter described in this specification can be implemented as one or more computer program products, i.e., one or more modules of computer program instructions encoded on a computer-readable medium for execution by, or to control the operation of, data processing apparatus. The computer-readable medium can be a machine-readable storage device, a machine-readable storage substrate, a memory device, a composition of matter effecting a machine-readable propagated signal, or a combination of one or more of them. The term “data processing apparatus” encompasses all apparatus, devices, and machines for processing data, including by way of example a programmable processor, a computer, or multiple processors or computers. The appa-

ratus can include, in addition to hardware, code that creates an execution environment for the computer program in question, e.g., code that constitutes processor firmware, a protocol stack, a database management system, an operating system, or a combination of one or more of them. A propagated signal is an artificially generated signal, e.g., a machine-generated electrical, optical, or electromagnetic signal, that is generated to encode information for transmission to suitable receiver apparatus.

A computer program (also known as a program, software, software application, script, or code) can be written in any form of programming language, including compiled or interpreted languages, and it can be deployed in any form, including as a standalone program or as a module, a component, a subroutine, or other unit suitable for use in a computing environment. A computer program does not necessarily correspond to a file in a file system. A program can be stored in a portion of a file that holds other programs or data (e.g., one or more scripts stored in a markup language document), in a single file dedicated to the program in question, or in multiple coordinated files (e.g., files that store one or more modules, sub programs, or portions of code). A computer program can be deployed to be executed on one computer or on multiple computers that are located at one site or distributed across multiple sites and interconnected by a communication network.

The processes and logic flows described in this specification can be performed by one or more programmable processors executing one or more computer programs to perform functions by operating on input data and generating output. The processes and logic flows can also be performed by, and apparatus can also be implemented as, special purpose logic circuitry, e.g., a field programmable gate array (FPGA) or an ASIC.

Processors suitable for the execution of a computer program include, by way of example, both general and special purpose microprocessors, and any one or more processors of any kind of a digital computer. Generally, a processor will receive instructions and data from a read only memory or a random access memory or both. The essential elements of a computer are a processor for performing instructions and one or more memory devices for storing instructions and data. Generally, a computer will also include, or be operatively coupled to receive data from or transfer data to, or both, one or more mass storage devices for storing data, e.g., magnetic disks, magneto optical disks, or optical disks. However, a computer need not have such devices. Moreover, a computer can be embedded in another device, e.g., a mobile telephone, a personal digital assistant (PDA), a mobile audio player, a Global Positioning System (GPS) receiver, to name just a few. Computer-readable media suitable for storing computer program instructions and data include all forms of non-volatile memory, media and memory devices, including by way of example semiconductor memory devices, e.g., EPROM, EEPROM, and flash memory devices; magnetic disks, e.g., internal hard disks or removable disks; magneto optical disks; and CD ROM and DVD-ROM disks. The processor and the memory can be supplemented by, or incorporated in, special purpose logic circuitry.

Implementations of the subject matter described in this specification can be implemented in a computing system that includes a back end component, e.g., as a data server; that includes a middleware component, e.g., an application server; or that includes a front end component, e.g., a client computer having a graphical user interface or a web browser through which a user can interact with an implementation of

61

the subject matter described is this specification, or any combination of one or more such back end, middleware, or front end components. The components of the system can be interconnected by any form or medium of digital data communication, e.g., a communication network. Examples of communication networks include a local area network (LAN) and a wide area network (WAN), e.g., the Internet.

The computing system can include clients and servers. A client and server are generally remote from each other and typically interact through a communication network. The relationship of a client and server arises by virtue of computer programs running on the respective computers and having a client-server relationship to each other.

While this specification contains many specifics, these should not be construed as limitations on the scope of the invention or of what may be claimed, but rather as descriptions of features specific to particular implementations of the invention. Certain features that are described in this specification in the context of separate implementations can also be implemented in combination in a single implementation. Conversely, various features that are described in the context of a single implementation can also be implemented in multiple implementations separately or in any suitable sub-combination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination may be directed to a sub-combination or variation of a sub-combination.

Similarly, while operations are depicted in the drawings in a particular order, this should not be understood as requiring that such operations be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results. In certain circumstances, multi-tasking and parallel processing may be advantageous. Moreover, the separation of various system components in the embodiments described above should not be understood as requiring such separation in all embodiments, and it should be understood that the described program components and systems can generally be integrated together in a single software product or packaged into multiple software products.

A number of implementations have been described. Nevertheless, it will be understood that various modifications may be made without departing from the spirit and scope of the disclosure. Accordingly, other implementations are within the scope of the following claims. For example, the actions recited in the claims can be performed in a different order and still achieve desirable results.

What is claimed is:

1. A telepresence robot system comprising:

an electronic display;

a processor in communication with the electronic display;

a memory device in communication with the processor, the memory device containing instructions, that when executed by the processor, cause the processor to:

retrieve a destination list including destination locations within a facility;

receive a video feed from an imaging system of a remote telepresence robot at a first perspective;

display the video feed from the imaging system of the remote telepresence robot; and

control a movement of the remote telepresence robot by transmitting a command to the remote telepresence robot specifying the movement for the remote telepresence robot from a current location to a destination location via a drive motor; and

62

a user input device in communication with the processor, the user input device configured to enable a user to select the movement for the remote telepresence robot from the current location to the destination location via one of a plurality of options on a single user interface, the plurality of options comprising:

selecting a velocity-based control specifying a direction of the movement of the remote telepresence robot;

selecting a destination location of the remote telepresence robot with respect to the destination list; and selecting a destination location of the remote telepresence robot with respect to the video feed.

2. The telepresence robot system of claim 1, wherein the selection of the movement for the remote telepresence robot from the current location to the destination location via the one of the plurality of options on the single user interface results in selection of an alternative perspective of the video feed.

3. The telepresence robot system of claim 1, wherein the selection of the movement further comprises selecting an alternative perspective of the video feed by selecting a point within the video feed.

4. The telepresence robot system of claim 1, wherein the selection of the movement further comprises selecting an alternative perspective of the video feed by incrementally panning or tilting the imaging system while the remote telepresence robot remains stationary.

5. The telepresence robot system of claim 1, wherein the selection of the movement relates to rotating one of a lower portion of the remote telepresence robot and an upper portion of the remote telepresence robot.

6. The telepresence robot system of claim 1, wherein the processor is further configured to:

receive the selection of the destination location of the remote robot from the user input device;

determine a sequence of coordinates relative to a plan view map to create a navigation path between the current location of the remote telepresence robot and the selected destination location of the remote telepresence robot; and

transmit a command to the remote telepresence robot, the command comprising the sequence of coordinates forming the navigation path.

7. The telepresence robot system of claim 6, wherein the processor is further configured to display the sequence of coordinates forming the navigation path overlaid on the plan view map.

8. The telepresence robot system of claim 6, wherein the processor is further configured to:

determine a distortion between the plan view map and the video feed received from the imaging system of the remote telepresence robot;

apply the distortion to the sequence of coordinates forming the navigation path to determine corresponding video coordinates and perspective data describing a location and perspective of the sequence of coordinates relative to the video feed; and

display a three-dimensional rendition of the sequence of coordinates forming the navigation path overlaid on the video feed.

9. The telepresence robot system of claim 8, wherein the three-dimensional rendition of the sequence of coordinates forming the navigation path is overlaid on the video feed with respect to a floor detected in the video feed.

10. The telepresence robot system of claim 1, wherein the processor is further configured to:

63

receive the selection of the destination location of the remote robot from the user input device; transmit destination coordinates relative to a plan view map to the remote telepresence robot, the destination coordinates corresponding to the selected destination location;

receive a sequence of coordinates relative to the plan view map from a navigation system of the remote telepresence robot, the sequence of coordinates forming a navigation path between the current location of the remote telepresence robot and the selected destination location of the remote telepresence robot; and

display the sequence of coordinates forming the navigation path overlaid on the plan view map.

11. The telepresence robot system of claim 10, wherein the processor is further configured to:

determine a distortion between the plan view map and the video feed received from the imaging system of the remote telepresence robot;

apply the distortion to the sequence of coordinates forming the navigation path to determine corresponding video coordinates and perspective data describing a location and perspective of the sequence of coordinates relative to the video feed; and

display a three-dimensional rendition of the sequence of coordinates forming the navigation path overlaid on the video feed.

12. The telepresence robot system of claim 11, wherein the three-dimensional rendition of the sequence of coordinates forming the navigation path is overlaid on the video feed with respect to a floor detected in the video feed.

13. The telepresence robot system of claim 1, wherein the processor is further configured to receive coordinates on the plan view map of an obstacle detected by a sensor system of the remote telepresence robot.

14. The telepresence robot system of claim 1, wherein the destination list is stored remotely.

15. The telepresence robot system of claim 14, wherein the destination list is stored within the remote telepresence robot.

16. The telepresence robot system of claim 1, wherein the processor is further configured to:

determine a distortion between a plan view map and the video feed received from the imaging system of the remote telepresence robot; and

64

generate a hybrid map view comprising a blended view of the plan view map and the video feed from the imaging system of the remote telepresence robot.

17. The telepresence robot system of claim 16, wherein the hybrid map view comprises a three-dimensional representation of the plan view map overlaid on the video feed.

18. The telepresence robot system of claim 1, wherein the processor is further configured to:

receive a request via the user input device for a rendered look ahead for a virtual location of the remote telepresence robot on a plan view map;

determine a distortion between the plan view map and the video feed received from the imaging system of the remote telepresence robot;

generate a virtual three-dimensional video feed based on a virtual location of the remote telepresence robot; and display the virtual three-dimensional video feed based on the virtual location of the remote telepresence robot.

19. The telepresence robot system of claim 1, wherein the processor is further configured to display a plan view map with an indication of the current location of the remote telepresence robot on a plan view map.

20. A method for controlling a remote telepresence robot, comprising:

receiving a video feed from an imaging system of the remote telepresence robot at a first perspective;

retrieving a destination list from a memory device including destination locations within a facility;

displaying, on an electronic display, the video feed from the imaging system of the remote telepresence robot;

controlling, by a processor, movement of the remote telepresence robot by transmitting a command to the remote telepresence robot to move from a current location to a destination location via a drive motor; and

receiving, by the processor, a selection of the movement for the remote telepresence robot from the current location to the destination location via one of a plurality of options on a single user interface, the plurality of options comprising:

selecting a velocity-based control specifying a direction of the movement of the remote telepresence robot;

selecting a destination location of the remote telepresence robot with respect to the destination list; and selecting a destination location of the remote telepresence robot with respect to the video feed.

* * * * *