



US00RE45512E

(19) **United States**
(12) **Reissued Patent**
Tearney et al.

(10) **Patent Number:** **US RE45,512 E**
(45) **Date of Reissued Patent:** ***May 12, 2015**

(54) **SYSTEM AND METHOD FOR OPTICAL COHERENCE IMAGING**

(75) Inventors: **Guillermo J. Tearney**, Cambridge, MA (US); **Milen Shishkov**, Watertown, MA (US); **Brett E. Bouma**, Quincy, MA (US)

(73) Assignee: **The General Hospital Corporation**, Boston, MA (US)

(*) Notice: This patent is subject to a terminal disclaimer.

(21) Appl. No.: **13/611,926**

(22) Filed: **Sep. 12, 2012**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **7,366,376**
Issued: **Apr. 29, 2008**
Appl. No.: **11/241,907**
Filed: **Sep. 29, 2005**

U.S. Applications:

(63) Continuation of application No. 12/323,228, filed on Nov. 25, 2008, now Pat. No. Re. 43,875, which is an application for the reissue of Pat. No. 7,366,376.

(60) Provisional application No. 60/614,228, filed on Sep. 29, 2004.

(51) **Int. Cl.**
G02B 6/02 (2006.01)
G02B 6/12 (2006.01)
G02B 6/26 (2006.01)
G02B 6/28 (2006.01)
G02B 6/32 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC **H04J 14/0267** (2013.01)

(58) **Field of Classification Search**
USPC 385/14, 15, 31-35, 100, 123-128
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,339,754 A 1/1944 Brace
3,090,753 A 5/1963 Matuszak et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1550203 12/2004
DE 4105221 9/1991

(Continued)

OTHER PUBLICATIONS

International Search Report and Written Opinion mailed Mar. 7, 2006 for PCT/US2005/035711.

(Continued)


Primary Examiner — Jerry Blevins

(74) *Attorney, Agent, or Firm* — Andrews Kurth LLP

(57) **ABSTRACT**

Apparatus and method are provided for transmitting at least one electro-magnetic radiation is provided. In particular, at least one optical fiber having at least one end extending along a first axis may be provided. Further, a light transmissive optical arrangement may be provided in optical cooperation with the optical fiber. The optical arrangement may have a first surface having a portion that is perpendicular to a second axis, and a second surface which includes a curved portion. The first axis can be provided at a particular angle that is more than 0° and less than 90° with respect to the second axis.

37 Claims, 10 Drawing Sheets



(51)	Int. Cl.		5,281,811 A	1/1994	Lewis
	G02B 6/36	(2006.01)	5,283,795 A	2/1994	Fink
	G02B 6/42	(2006.01)	5,291,885 A	3/1994	Taniji et al.
	G02B 6/44	(2006.01)	5,293,872 A	3/1994	Alfano et al.
	H04J 14/02	(2006.01)	5,293,873 A	3/1994	Fang
			5,302,025 A	4/1994	Kleinerman
			5,304,173 A	4/1994	Kittrell et al.
			5,304,810 A	4/1994	Amos
			5,305,759 A	4/1994	Kaneko et al.
			5,317,389 A	5/1994	Hochberg et al.
(56)	References Cited		5,318,024 A	6/1994	Kittrell et al.
	U.S. PATENT DOCUMENTS		5,321,501 A	6/1994	Swanson et al.
			5,333,144 A	7/1994	Liedenbaum et al.
			5,348,003 A	9/1994	Caro
			5,353,790 A	10/1994	Jacques et al.
			5,383,467 A	1/1995	Auer et al.
			5,394,235 A	2/1995	Takeuchi et al.
			5,404,415 A	4/1995	Mori et al.
			5,411,016 A	5/1995	Kume et al.
			5,419,323 A	5/1995	Kittrell et al.
			5,424,827 A	6/1995	Horwitz et al.
			5,439,000 A	8/1995	Gunderson et al.
			5,441,053 A	8/1995	Lodder et al.
			5,450,203 A	9/1995	Penkethman
			5,454,807 A	10/1995	Lennox et al.
			5,459,325 A	10/1995	Hueton et al.
			5,459,570 A	10/1995	Swanson et al.
			5,465,147 A	11/1995	Swanson
			5,486,701 A	1/1996	Norton et al.
			5,491,524 A	2/1996	Hellmuth et al.
			5,491,552 A	2/1996	Kittrell
			5,522,004 A	5/1996	Djupsjobacka et al.
			5,526,338 A	6/1996	Hasman et al.
			5,555,087 A	9/1996	Miyagawa et al.
			5,562,100 A	10/1996	Kittrell et al.
			5,565,983 A	10/1996	Barnard et al.
			5,565,986 A	10/1996	Knüttel
			5,566,267 A	10/1996	Neuberger
			5,583,342 A	12/1996	Ichie
			5,590,660 A	1/1997	MacAulay et al.
			5,600,486 A	2/1997	Gal et al.
			5,601,087 A	2/1997	Gunderson et al.
			5,621,830 A	4/1997	Lucey et al.
			5,623,336 A	4/1997	Raab et al.
			5,635,830 A	6/1997	Itoh
			5,643,176 A	7/1997	Persidsky
			5,649,924 A	7/1997	Everett et al.
			5,697,373 A	12/1997	Richards-Kortum et al.
			5,698,397 A	12/1997	Zarling et al.
			5,710,630 A	1/1998	Essenpreis et al.
			5,716,324 A	2/1998	Toida
			5,719,399 A	2/1998	Alfano et al.
			5,730,731 A	3/1998	Mollenauer et al.
			5,735,276 A	4/1998	Lemelson
			5,740,808 A	4/1998	Panescu et al.
			5,748,318 A	5/1998	Maris et al.
			5,748,598 A	5/1998	Swanson et al.
			5,752,518 A	5/1998	McGee et al.
			5,784,352 A	7/1998	Swanson et al.
			5,785,651 A	7/1998	Kuhn et al.
			5,795,295 A	8/1998	Hellmuth et al.
			5,801,826 A	9/1998	Williams
			5,801,831 A	9/1998	Sargoytchev et al.
			5,803,082 A	9/1998	Stapleton et al.
			5,807,261 A	9/1998	Benaron et al.
			5,810,719 A	9/1998	Toida
			5,817,144 A	10/1998	Gregory
			5,836,877 A	11/1998	Zavislan et al.
			5,840,023 A	11/1998	Oraevsky et al.
			5,840,075 A	11/1998	Mueller et al.
			5,842,995 A	12/1998	Mahadevan-Jansen et al.
			5,843,000 A	12/1998	Nishioka et al.
			5,843,052 A	12/1998	Benja-Athon
			5,847,827 A	12/1998	Fercher
			5,862,273 A	1/1999	Pelletier
			5,865,754 A	2/1999	Sevick-Muraca et al.
			5,867,268 A	2/1999	Gelikonov et al.
			5,871,449 A	2/1999	Brown
			5,872,879 A	2/1999	Hamm

(56)

References Cited

U.S. PATENT DOCUMENTS

5,877,856 A	3/1999	Fercher	6,324,419 B1	11/2001	Guzelsu et al.
5,887,009 A	3/1999	Mandella et al.	6,341,036 B1	1/2002	Tearney et al.
5,892,583 A	4/1999	Li	6,353,693 B1	3/2002	Kano et al.
5,910,839 A	6/1999	Erskine et al.	6,359,692 B1	3/2002	Groot
5,912,764 A	6/1999	Togino et al.	6,374,128 B1	4/2002	Toida et al.
5,920,373 A	7/1999	Bille	6,377,349 B1	4/2002	Fercher
5,920,390 A	7/1999	Farahi et al.	6,384,915 B1	5/2002	Everett et al.
5,921,926 A	7/1999	Rolland et al.	6,393,312 B1	5/2002	Hoyns
5,926,592 A	7/1999	Harris et al.	6,394,964 B1	5/2002	Sievert, Jr. et al.
5,949,929 A	9/1999	Hamm	6,396,941 B1	5/2002	Bacus et al.
5,951,482 A	9/1999	Winston et al.	6,421,164 B2	7/2002	Tearney et al.
5,955,737 A	9/1999	Hallidy et al.	6,437,867 B2	8/2002	Zeylikovich et al.
5,956,355 A	9/1999	Swanson et al.	6,441,892 B2	8/2002	Xiao et al.
5,968,064 A	10/1999	Selmon et al.	6,441,959 B1	8/2002	Yang et al.
5,975,697 A	11/1999	Podoleanu et al.	6,445,485 B1	9/2002	Frigo et al.
5,983,125 A	11/1999	Alfano et al.	6,445,939 B1	9/2002	Swanson et al.
5,987,346 A	11/1999	Benaron et al.	6,445,944 B1	9/2002	Ostrovsky
5,991,697 A	11/1999	Nelson et al.	6,459,487 B1	10/2002	Chen et al.
5,994,690 A	11/1999	Kulkarni et al.	6,463,313 B1	10/2002	Winston et al.
5,995,223 A	11/1999	Power	6,469,846 B2	10/2002	Ebizuka et al.
6,002,480 A	12/1999	Izatt et al.	6,475,159 B1	11/2002	Casscells et al.
6,004,314 A	12/1999	Wei et al.	6,475,210 B1	11/2002	Phelps et al.
6,006,128 A	12/1999	Izatt et al.	6,477,403 B1	11/2002	Eguchi et al.
6,007,996 A	12/1999	McNamara et al.	6,485,413 B1	11/2002	Boppart et al.
6,010,449 A	1/2000	Selmon et al.	6,485,482 B1	11/2002	Belef
6,014,214 A	1/2000	Li	6,501,551 B1	12/2002	Tearney et al.
6,016,197 A	1/2000	Krivoshlykov	6,501,878 B2	12/2002	Hughes et al.
6,020,963 A	2/2000	DiMarzio et al.	6,516,014 B1	2/2003	Sellin et al.
6,025,956 A	2/2000	Nagano et al.	6,517,532 B1	2/2003	Altshuler et al.
6,033,721 A	3/2000	Nassuphis	6,538,817 B1	3/2003	Farmer et al.
6,037,579 A	3/2000	Chan et al.	6,540,391 B2	4/2003	Lanzetta et al.
6,044,288 A	3/2000	Wake et al.	6,549,801 B1	4/2003	Chen et al.
6,045,511 A	4/2000	Ott et al.	6,552,796 B2	4/2003	Magnin et al.
6,048,742 A	4/2000	Weyburne et al.	6,556,305 B1	4/2003	Aziz et al.
6,053,613 A	4/2000	Wei et al.	6,556,853 B1	4/2003	Cabib et al.
6,069,698 A	5/2000	Ozawa et al.	6,558,324 B1	5/2003	Von Behren et al.
6,078,047 A	6/2000	Mittleman et al.	6,560,259 B1	5/2003	Hwang et al.
6,091,496 A	7/2000	Hill	6,564,087 B1	5/2003	Pitris et al.
6,091,984 A	7/2000	Perelman et al.	6,564,089 B2	5/2003	Izatt et al.
6,094,274 A	7/2000	Yokoi	6,567,585 B2	5/2003	Harris
6,107,048 A	8/2000	Goldenring et al.	6,593,101 B2	7/2003	Richards-Kortum et al.
6,111,645 A	8/2000	Tearney et al.	6,611,833 B1	8/2003	Johnson et al.
6,117,128 A	9/2000	Gregory	6,615,071 B1	9/2003	Casscells, III et al.
6,120,516 A	9/2000	Selmon et al.	6,622,732 B2	9/2003	Constantz
6,134,003 A	10/2000	Tearney et al.	6,654,127 B2	11/2003	Everett et al.
6,134,010 A	10/2000	Zavislan	6,657,730 B2	12/2003	Pfau et al.
6,134,033 A	10/2000	Bergano et al.	6,658,278 B2	12/2003	Gruhl
6,141,577 A	10/2000	Rolland et al.	6,680,780 B1	1/2004	Fee
6,151,522 A	11/2000	Alfano et al.	6,685,885 B2	2/2004	Nolte et al.
6,159,445 A	12/2000	Klaveness et al.	6,687,007 B1	2/2004	Meigs
6,160,826 A	12/2000	Swanson et al.	6,687,010 B1	2/2004	Horii et al.
6,161,031 A	12/2000	Hochman et al.	6,687,036 B2	2/2004	Riza
6,166,373 A	12/2000	Mao	6,692,430 B2	2/2004	Adler
6,174,291 B1	1/2001	McMahon et al.	6,701,181 B2	3/2004	Tang et al.
6,175,669 B1	1/2001	Colston et al.	6,721,094 B1	4/2004	Sinclair et al.
6,185,271 B1	2/2001	Kinsinger	6,738,144 B1	5/2004	Dogariu et al.
6,191,862 B1	2/2001	Swanson et al.	6,741,355 B2	5/2004	Drabarek
6,193,676 B1	2/2001	Winston et al.	6,757,467 B1	6/2004	Rogers
6,198,956 B1	3/2001	Dunne	6,790,175 B1	9/2004	Furusawa et al.
6,201,989 B1	3/2001	Whitehead et al.	6,806,963 B1	10/2004	Wälti et al.
6,208,415 B1	3/2001	De Boer et al.	6,816,743 B2	11/2004	Moreno et al.
6,208,887 B1	3/2001	Clarke	6,831,781 B2	12/2004	Tearney et al.
6,215,925 B1	4/2001	Kaneyama	6,839,496 B1	1/2005	Mills et al.
6,245,026 B1	6/2001	Campbell et al.	6,882,432 B2	4/2005	Deck
6,249,349 B1	6/2001	Lauer	6,900,899 B2	5/2005	Nevis
6,249,381 B1	6/2001	Suganuma	6,903,820 B2	6/2005	Wang
6,249,630 B1	6/2001	Stock et al.	6,909,105 B1	6/2005	Heintzmann et al.
6,263,234 B1	7/2001	Engelhardt et al.	6,949,072 B2	9/2005	Furnish et al.
6,264,610 B1	7/2001	Zhu	6,961,123 B1	11/2005	Wang et al.
6,272,376 B1	8/2001	Marcu et al.	6,980,299 B1	12/2005	de Boer
6,274,871 B1	8/2001	Dukor et al.	6,996,549 B2	2/2006	Zhang et al.
6,282,011 B1	8/2001	Tearney et al.	7,006,231 B2	2/2006	Ostrovsky et al.
6,297,018 B1	10/2001	French et al.	7,006,232 B2	2/2006	Rollins et al.
6,301,048 B1	10/2001	Cao et al.	7,019,838 B2	3/2006	Izatt et al.
6,308,092 B1	10/2001	Hoyns	7,027,633 B2	4/2006	Foran et al.
			7,061,622 B2	6/2006	Rollins et al.
			7,072,047 B2	7/2006	Westphal et al.
			7,075,658 B2	7/2006	Izatt et al.
			7,099,358 B1	8/2006	Chong et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,113,288	B2	9/2006	Fercher	2003/0082105	A1	5/2003	Fischman et al.
7,113,625	B2	9/2006	Watson et al.	2003/0090753	A1	5/2003	Takeyama et al.
7,130,320	B2	10/2006	Tobiason et al.	2003/0097048	A1	5/2003	Ryan et al.
7,139,598	B2	11/2006	Hull et al.	2003/0108911	A1	6/2003	Klimant et al.
7,142,835	B2	11/2006	Paulus	2003/0120137	A1	6/2003	Pawluczyk et al.
7,148,970	B2	12/2006	De Boer	2003/0135101	A1	7/2003	Webler
7,177,027	B2	2/2007	Hirasawa et al.	2003/0137669	A1	7/2003	Rollins et al.
7,190,464	B2	3/2007	Alphonse	2003/0164952	A1	9/2003	Deichmann et al.
7,230,708	B2	6/2007	Lapotko et al.	2003/0165263	A1	9/2003	Hamer et al.
7,231,243	B2	6/2007	Tearney et al.	2003/0171691	A1	9/2003	Casscells, III et al.
7,236,637	B2	6/2007	Sirohey et al.	2003/0174339	A1	9/2003	Feldchtein et al.
7,242,480	B2	7/2007	Alphonse	2003/0199769	A1	10/2003	Podoleanu et al.
7,267,494	B2	9/2007	Deng et al.	2003/0216719	A1	11/2003	Debenedictis et al.
7,272,252	B2	9/2007	De La Torre-Bueno et al.	2003/0218756	A1	11/2003	Chen et al.
7,304,798	B2	12/2007	Izumi et al.	2003/0220749	A1	11/2003	Chen et al.
7,310,150	B2	12/2007	Guillermo et al.	2003/0236443	A1	12/2003	Cespedes et al.
7,330,270	B2	2/2008	O'Hara et al.	2004/0002650	A1	1/2004	Mandrusov et al.
7,336,366	B2	2/2008	Choma et al.	2004/0039298	A1	2/2004	Abreu
7,342,659	B2	3/2008	Horn et al.	2004/0054268	A1	3/2004	Esenaliev et al.
7,355,716	B2	4/2008	De Boer et al.	2004/0072200	A1	4/2004	Rigler et al.
7,355,721	B2	4/2008	Quadling et al.	2004/0075841	A1	4/2004	Van Neste et al.
7,359,062	B2	4/2008	Chen et al.	2004/0076940	A1	4/2004	Alexander et al.
7,366,376	B2	4/2008	Shishkov et al.	2004/0077949	A1	4/2004	Blofgett et al.
7,382,809	B2	6/2008	Chong et al.	2004/0085540	A1	5/2004	Lapotko et al.
7,391,520	B2	6/2008	Zhou et al.	2004/0086245	A1	5/2004	Farroni et al.
7,458,683	B2	12/2008	Chernyak et al.	2004/0095464	A1	5/2004	Miyagi et al.
7,530,948	B2	5/2009	Seibel et al.	2004/0100631	A1	5/2004	Bashkansky et al.
7,539,530	B2	5/2009	Caplan et al.	2004/0100681	A1	5/2004	Bjarklev et al.
7,609,391	B2	10/2009	Betzig	2004/0110206	A1	6/2004	Wong et al.
7,630,083	B2	12/2009	de Boer et al.	2004/0126048	A1	7/2004	Dave et al.
7,643,152	B2	1/2010	de Boer et al.	2004/0126120	A1	7/2004	Cohen et al.
7,643,153	B2	1/2010	de Boer et al.	2004/0133191	A1	7/2004	Momiuchi et al.
7,646,905	B2	1/2010	Guittet et al.	2004/0150829	A1	8/2004	Koch et al.
7,649,160	B2	1/2010	Colomb et al.	2004/0150830	A1	8/2004	Chan
7,664,300	B2	2/2010	Lange et al.	2004/0152989	A1	8/2004	Puttappa et al.
7,733,497	B2	6/2010	Yun et al.	2004/0165184	A1	8/2004	Mizuno
7,782,464	B2	8/2010	Mujat et al.	2004/0166593	A1	8/2004	Nolte et al.
7,805,034	B2	9/2010	Kato et al.	2004/0189999	A1	9/2004	De Groot et al.
2001/0036002	A1	11/2001	Tearney et al.	2004/0212808	A1	10/2004	Okawa et al.
2001/0047137	A1	11/2001	Moreno et al.	2004/0239938	A1	12/2004	Izatt et al.
2002/0016533	A1	2/2002	Marchitto et al.	2004/0246490	A1	12/2004	Wang
2002/0024015	A1	2/2002	Hoffmann et al.	2004/0246583	A1	12/2004	Mueller et al.
2002/0048025	A1	4/2002	Takaoka	2004/0254474	A1	12/2004	Seibel et al.
2002/0048026	A1	4/2002	Isshiki et al.	2004/0258106	A1	12/2004	Araujo et al.
2002/0052547	A1	5/2002	Toida	2004/0263843	A1	12/2004	Knopp et al.
2002/0057431	A1	5/2002	Fateley et al.	2005/0004453	A1	1/2005	Tearney et al.
2002/0064341	A1	5/2002	Fauver et al.	2005/0018133	A1	1/2005	Huang et al.
2002/0076152	A1*	6/2002	Hughes et al.	2005/0018200	A1	1/2005	Guillermo et al.
2002/0085209	A1	7/2002	Mittleman et al.	2005/0018201	A1	1/2005	De Boer
2002/0086347	A1	7/2002	Johnson et al.	2005/0035295	A1	2/2005	Bouma et al.
2002/0091322	A1	7/2002	Chaiken et al.	2005/0036150	A1	2/2005	Izatt et al.
2002/0093662	A1	7/2002	Chen et al.	2005/0046837	A1	3/2005	Izumi et al.
2002/0109851	A1	8/2002	Deck	2005/0057680	A1	3/2005	Agan
2002/0113965	A1	8/2002	Yun	2005/0057756	A1	3/2005	Fang-Yen et al.
2002/0122182	A1	9/2002	Everett et al.	2005/0059894	A1	3/2005	Zeng et al.
2002/0122246	A1	9/2002	Tearney et al.	2005/0065421	A1	3/2005	Burckhardt et al.
2002/0140942	A1	10/2002	Fee et al.	2005/0075547	A1	4/2005	Wang
2002/0158211	A1	10/2002	Gillispie	2005/0083534	A1	4/2005	Riza et al.
2002/0161357	A1	10/2002	Rox et al.	2005/0119567	A1	6/2005	Choi et al.
2002/0163622	A1	11/2002	Magnin et al.	2005/0128488	A1	6/2005	Yelin et al.
2002/0168158	A1	11/2002	Furusawa et al.	2005/0165303	A1	7/2005	Kleen et al.
2002/0172485	A1	11/2002	Keaton et al.	2005/0171438	A1	8/2005	Chen et al.
2002/0183623	A1	12/2002	Tang et al.	2005/0190372	A1	9/2005	Dogariu et al.
2002/0188204	A1	12/2002	McNamara et al.	2005/0254061	A1	11/2005	Alphonse et al.
2002/0196446	A1	12/2002	Roth et al.	2006/0020172	A1	1/2006	Luerssen et al.
2002/0198457	A1	12/2002	Tearney et al.	2006/0033923	A1	2/2006	Hirasawa et al.
2003/0001071	A1	1/2003	Mandella et al.	2006/0093276	A1	5/2006	Bouma et al.
2003/0013973	A1	1/2003	Georgakoudi et al.	2006/0103850	A1	5/2006	Alphonse et al.
2003/0023153	A1	1/2003	Izatt et al.	2006/0146339	A1	7/2006	Fujita et al.
2003/0026735	A1	2/2003	Nolte et al.	2006/0155193	A1	7/2006	Leonardi et al.
2003/0028114	A1	2/2003	Casscells, III et al.	2006/0164639	A1	7/2006	Horn et al.
2003/0030816	A1	2/2003	Eom et al.	2006/0171503	A1	8/2006	O'Hara et al.
2003/0043381	A1	3/2003	Fercher	2006/0184048	A1	8/2006	Saadat et al.
2003/0053673	A1	3/2003	Dewaele et al.	2006/0193352	A1	8/2006	Chong et al.
2003/0067607	A1	4/2003	Wolleschensky et al.	2006/0244973	A1	11/2006	Yun et al.
				2006/0279742	A1	12/2006	Tearney
				2007/0019208	A1	1/2007	Toida et al.
				2007/0038040	A1	2/2007	Cense et al.
				2007/0070496	A1	3/2007	Gweon et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2007/0076217 A1 4/2007 Baker et al.
 2007/0086013 A1 4/2007 De Lega et al.
 2007/0086017 A1 4/2007 Buckland et al.
 2007/0091317 A1 4/2007 Freischlad et al.
 2007/0133002 A1 6/2007 Wax et al.
 2007/0188855 A1 8/2007 Shishkov et al.
 2007/0208225 A1 9/2007 Czaniera
 2007/0223006 A1 9/2007 Tearney et al.
 2007/0233056 A1 10/2007 Yun
 2007/0233396 A1 10/2007 Tearney et al.
 2007/0236700 A1 10/2007 Yun et al.
 2007/0258094 A1 11/2007 Izatt et al.
 2007/0291277 A1 12/2007 Everett et al.
 2008/0002197 A1 1/2008 Sun et al.
 2008/0007734 A1 1/2008 Park et al.
 2008/0049220 A1 2/2008 Izzia et al.
 2008/0094613 A1 4/2008 de Boer et al.
 2008/0094637 A1 4/2008 de Boer et al.
 2008/0097225 A1 4/2008 Tearney et al.
 2008/0097709 A1 4/2008 de Boer et al.
 2008/0100837 A1 5/2008 de Boer et al.
 2008/0152353 A1 6/2008 de Boer et al.
 2008/0154090 A1 6/2008 Hashimshony
 2008/0192236 A1 8/2008 Smith et al.
 2008/0204762 A1 8/2008 Izatt et al.
 2008/0228086 A1 9/2008 Ilegbusi
 2008/0265130 A1 10/2008 Colomb et al.
 2008/0308730 A1 12/2008 Vizi et al.
 2009/0005691 A1 1/2009 Huang
 2009/0011948 A1 1/2009 Unlu et al.
 2009/0192358 A1 7/2009 Yun
 2009/0196477 A1 8/2009 Cense et al.
 2009/0273777 A1 11/2009 Yun et al.
 2009/0281390 A1 11/2009 Qiu et al.
 2009/0290156 A1 11/2009 Popescu et al.
 2010/0002241 A1 1/2010 Hirose
 2010/0086251 A1 4/2010 Xu et al.
 2010/0094576 A1 4/2010 de Boer et al.
 2010/0150467 A1 6/2010 Zhao et al.

FOREIGN PATENT DOCUMENTS

DE 4309056 9/1994
 DE 19542955 5/1997
 DE 10351319 6/2005
 EP 0110201 6/1984
 EP 0251062 1/1988
 EP 0617286 2/1994
 EP 0590268 4/1994
 EP 0728440 8/1996
 EP 0933096 8/1999
 EP 1324051 7/2003
 EP 1426799 6/2004
 FR 2738343 8/1995
 GB 1257778 12/1971
 GB 2030313 4/1980
 GB 2209221 5/1989
 GB 2298054 8/1996
 JP 6073405 4/1985
 JP 20040056907 2/1992
 JP 4135550 5/1992
 JP 4135551 5/1992
 JP 5509417 11/1993
 JP 2002214127 7/2002
 JP 20030035659 2/2003
 WO 7900841 10/1979
 WO WO 91/10474 7/1991
 WO 9201966 2/1992
 WO 9216865 10/1992
 WO WO 92/16865 10/1992
 WO 9219930 11/1992
 WO 9303672 3/1993
 WO 9216865 10/1993
 WO 0617286 2/1994

WO 9533971 12/1995
 WO 9628212 9/1996
 WO 9732182 9/1997
 WO 9800057 1/1998
 WO 9801074 1/1998
 WO 9814132 4/1998
 WO 9835203 8/1998
 WO 9838907 9/1998
 WO 9846123 10/1998
 WO 9848838 11/1998
 WO 9848846 11/1998
 WO 9905487 2/1999
 WO 9944089 2/1999
 WO 9944089 9/1999
 WO 9957507 11/1999
 WO 0058766 10/2000
 WO 0101111 1/2001
 WO 0108579 2/2001
 WO 200127679 4/2001
 WO 0138820 5/2001
 WO 0142735 6/2001
 WO 0236015 5/2002
 WO 0238040 5/2002
 WO 02037075 5/2002
 WO 0254027 7/2002
 WO 02053050 7/2002
 WO 02054027 7/2002
 WO 02084263 10/2002
 WO 03013624 2/2003
 WO 03020119 3/2003
 WO 03046495 6/2003
 WO 03046636 6/2003
 WO 03052478 6/2003
 WO 03053226 7/2003
 WO 03062802 7/2003
 WO 03105678 12/2003
 WO 2004034869 4/2004
 WO 2004057266 7/2004
 WO 20040066824 8/2004
 WO 2004088361 10/2004
 WO 04105598 12/2004
 WO 20050000115 1/2005
 WO 2005047813 5/2005
 WO 2005054780 6/2005
 WO 20050082225 9/2005
 WO 2006004743 1/2006
 WO 2006014392 2/2006
 WO 2006039091 4/2006
 WO 20060038876 4/2006
 WO 2006059109 6/2006
 WO 2006124860 11/2006
 WO 2006130797 12/2006
 WO 2007028531 3/2007
 WO 2007038787 4/2007
 WO 200708995 7/2007
 WO 2007083138 7/2007
 WO 2007271761 10/2007
 WO 20090153929 12/2009

OTHER PUBLICATIONS

International Preliminary Report on Patentability mailed Apr. 12, 2007 for PCT/US2005/035711.
 Liptak David C. et al., (2007) "On the Development of a Confocal Rayleigh-Brillouin Microscope" *American Institute of Physics* vol. 78, 016106.
 Office Action mailed Oct. 1, 2008 for U.S. Appl. No. 11/955,986.
 Invitation of Pay Additional Fees mailed Aug. 7, 2008 for International Application No. PCT/US2008/062354.
 Invitation of Pay Additional Fees mailed Jul. 20, 2008 for International Application No. PCT/US2007/081982.
 International Search Report and Written Opinion mailed Jul. 18, 2008 for PCT/US2008/057533.
 Aizu, Y et al. (1991) "Bio-Speckle Phenomena and Their Application to the Evaluation of Blood Flow" *Optics and Laser Technology*, vol. 23, No. 4, Aug. 1, 1991.
 Richards G.J. et al. (1997) "Laser Speckle Contrast Analysis (LASCA): A Technique for Measuring Capillary Blood Flow Using the First Order Statistics of Laser Speckle Patterns" Apr. 2, 1997.

(56)

References Cited

OTHER PUBLICATIONS

- Gonick, Maria M., et al (2002) "Visualization of Blood Microcirculation Parameters in Human Tissues by Time Integrated Dynamic Speckles Analysis" vol. 972, No. 1, Oct. 1, 2002.
- International Search Report and Written Opinion mailed Jul. 4, 2008 for PCT/US2008/051432.
- Jonathan, Enock (2005) "Dual Reference Arm Low-Coherence Interferometer-Based Reflectometer For Optical Coherence Tomography (OCT) Application" *Optics Communications* vol. 252.
- Motaghian Nezam, S.M.R. (2007) "increased Ranging Depth in optical Frequency Domain Imaging by Frequency Encoding" *Optics Letters*, vol. 32, No. 19, Oct. 1, 2007.
- Office Action dated Jun. 30, 2008 for U.S. Appl. No. 11/670,058.
- Office Action dated Jul. 7, 2008 for U.S. Appl. No. 10/551,735.
- Australian Examiner's Report mailed May 27, 2008 for Australian patent application No. 2003210669.
- Notice of Allowance mailed Jun. 4, 2008 for U.S. Appl. No. 11/174,425.
- European communication dated May 15, 2008 for European patent application No. 05819917.5.
- International Search Report and Written Opinion mailed Jun. 10, 2008 for PCT/US2008/051335.
- Oh, W.Y. et al (2006) "Ultrahigh-Speed Optical Frequency Domain Imaging and Application to laser Ablation Monitoring" *Applied Physics Letters*, vol. 88.
- Office Action dated Aug. 21, 2008 for U.S. Appl. No. 11/505,700.
- Sticker, Markus (2002) En Face Imaging of Single Cell layers by Differential Phase-Contrast Optical Coherence Microscopy) *Optics Letters*, col. 27, No. 13, Jul. 1, 2002.
- International Search Report and Written Opinion dated Jul. 17, 2008 for International Application No. PCT/US2008/057450.
- International Search Report and Written Opinion dated Aug. 11, 2008 for International Application No. PCT/US2008/058703.
- US National Library of Medicine (NLM), Bethesda, MD, US; Oct. 2007, "Abstracts of the 19th Annual Symposium of Transcatheter Cardiovascular Therapeutics, Oct. 20-25, 2007, Washington, DC, USA."
- International Search Report and Written Opinion dated May 26, 2008 for International Application No. PCT/US2008/051404.
- Office Action dated Aug. 25, 2008 for U.S. Appl. No. 11/264,655.
- Office Action dated Sep. 11, 2008 for U.S. Appl. No. 11/624,334.
- Office Action dated Aug. 21, 2008 for U.S. Appl. No. 11/956,079.
- Gelikono, V. M. et al. (Oct. 1, "Two-Wavelength Optical Coherence Tomography" Radio physics and Quantum Electronics, Kluwer Academic Publishers-Consultants. vol. 47, No. 10-1.
- International Search Report and Written Opinion for PCT/US2007/081982 dated Oct. 19, 2007.
- Database Compendex Engineering Information, Inc., New York, NY, US; Mar. 5, 2007, Yelin, Dvir et al: "Spectral-Domain Spectrally-Encoded Endoscopy".
- Database Biosis Biosciences Information Service, Philadelphia, PA, US; Oct. 2006, Yelin D. et al: "Three-Dimensional Miniature Endoscopy".
- International Search Report and Written Opinion mailed Mar. 14, 2005 for PCT/US2004/018045.
- Notification of the international Preliminary Report on Patentability mailed Oct. 21, 2005.
- Shim M.G. et al., "Study of Fiber-Optic Probes for In vivo Medical Raman Spectroscopy" *Applied Spectroscopy*. vol. 53, No. 6, Jun. 1999.
- Bingid U. et al., "Fibre-Optic Laser-Assisted Infrared Tumour Diagnostics (FLAIR); Infrared Tumour Diagnostics" *Journal of Physics D: Applied Physics*, vol. 38, No. 15, Aug. 7, 2005.
- Jun Zhang et al. "Full Range Polarization-Sensitive Fourier Domain Optical Coherence Tomography" *Optics Express*, vol. 12, No. 24, Nov. 29, 2004.
- Yonghua et al., "Real-Time Phase-Resolved Functional Optical Hilbert Transformation" *Optics Letters*, vol. 27, No. 2, Jan. 15, 2002.
- Siavash et al., "Self-Referenced Doppler Optical Coherence Tomography" *Optics Letters*, vol. 27, No. 23, Dec. 1, 2002.
- International Search Report and Written Opinion dated Dec. 20, 2004 for PCT/US04/10152.
- Notification Concerning Transmittal of International Preliminary Report on Patentability dated Oct. 13, 2005 for PCT/US04/10152.
- International Search Report and Written Opinion dated Mar. 23, 2006 for PCT/US2005/042408.
- International Preliminary Report on Patentability dated Jun. 7, 2007 for PCT/US2005/042408.
- International Search Report and Written Opinion dated Feb. 28, 2007 for International Application No. PCT/US2006/038277.
- International Search Report and Written Opinion dated Jan. 30, 2009 for International Application No. PCT/US2008/081834.
- International Search Report and Written Opinion dated Feb. 2, 2009 for International Application No. PCT/US2008/071786.
- Bilenca A et al: "The Role of Amplitude and phase in Fluorescence Coherence Imaging: From Wide Filed to Nanometer Depth Profiling", *Optics IEEE*, May 5, 2007.
- Inoue, Yusuke et al: "Variable Phase-Contrast Fluorescence Spectrometry for Fluorescently Strained Cells", *Applied Physics Letters*, Sep. 18, 2006.
- Bernet, S et al: "Quantitative Imaging of Complex Samples by Spiral Phase Contrast Microscopy", *Optics Express*, May 9, 2006.
- International Search Report and Written Opinion dated Jan. 15, 2009 for International Application No. PCT/US2008/074863.
- Office Action dated Feb. 17, 2009 for U.S. Appl. No. 11/211,483.
- Notice of Reasons for Rejection mailed Dec. 2, 2008 for Japanese patent application No. 2000-533782.
- International Search Report and Written Opinion dated Feb. 24, 2009 for PCT/US2008/076447.
- Tang C. L. et al., "Wide-band electro-optical tuning of semiconductor lasers", *Applied Physics Letters*, vol. 30, No. 2, Jan. 15, 1977, pp. 113-116.
- Tang C. L. et al., "Transient effects in wavelength-modulated dye lasers", *Applied Physics Letters*, vol. 26, No. 9, May 1, 1975, pp. 534-537.
- Telle M. John, et al., "Very rapid tuning of cw dye laser", *Applied Physics Letters*, vol. 26, No. 10, May 15, 1975, pp. 572-574.
- Telle M. John, et al., "New method for electro-optical tuning of tunable lasers", *Applied Physics Letters*, vol. 24, No. 2, Jan. 15, 1974, pp. 85-87.
- Schmitt M. Joseph et al. "OCT elastography: imaging microscopic deformation and strain of tissue", *Optics Express*, vol. 3, No. 6, Sep. 14, 1998, pp. 199-211.
- M. Gualini Muddassir et al., "Recent Advancements of Optical Interferometry Applied to Medicine", *IEEE Transactions on Medical Imaging*, vol. 23, No. 2, Feb. 2004, pp. 205-212.
- Maurice L. Roch et al. "Noninvasive Vascular Elastography: Theoretical Framework", *IEEE Transactions on Medical Imaging*, vol. 23, No. 2, Feb. 2004, pp. 164-180.
- Kirkpatrick J. Sean et al. "Optical Assessment of Tissue Mechanical Properties", *Proceedings of the SPIE—The International Society for Optical Engineering SPIE—vol. 4001, 2000, pp. 92-101.*
- Lisaukas B. Jennifer et al., "Investigation of Plaque Biomechanics from Intravascular Ultrasound Images using Finite Element Modeling", *Proceedings of the 19th International Conference—IEEE* Oct. 30-Nov. 2, 1997, pp. 887-888.
- Parker K. J. et al., "Techniques for Elastic Imaging: A Review", *IEEE Engineering in Medicine and Biology*, Nov./Dec. 1996, pp. 52-59.
- European Patent Office Search Report dated Nov. 20, 2007 for European Application No. 05791226.3.
- Dubois Arnaud et al., "Ultrahigh-resolution OCT using white-light interference microscopy", *Proceedings of SPIE*, 2003, vol. 4956, pp. 14-21.
- Office Action dated Jan. 3, 2008 for U.S. Appl. No. 10/997,789.
- Office Action dated Dec. 21, 2007 for U.S. Appl. No. 11/264,655.
- Office Action dated Dec. 18, 2007 for U.S. Appl. No. 11/288,994.
- Office Action dated Jan. 10, 2008 for U.S. Appl. No. 11/435,228.
- Office Action dated Jan. 10, 2008 for U.S. Appl. No. 11/410,937.
- Office Action dated Jan. 11, 2008 for U.S. Appl. No. 11/445,990.
- Office Action dated Feb. 4, 2008 for U.S. Appl. No. 10/861,179.
- PCT International Search Report and Written Opinion for Application No. PCT/US2007/061463 dated Jan. 23, 2008.

(56)

References Cited

OTHER PUBLICATIONS

- PCT International Search Report and Written Opinion for Application No. PCT/US2007/061481 dated Mar. 17, 2008.
- PCT International Search Report and Written Opinion for Application No. PCT/US2007/078254 dated Mar. 28, 2008.
- Sadhwani, Ajay et al., "Determination of Teflon thickness with laser speckle I. Potential for burn depth diagnosis", Optical Society of America, 1996, vol. 35, No. 28, pp. 5727-5735.
- C.J. Stewart et al., "A comparison of two laser-based methods for determination of burn scar perfusion: Laser Doppler versus laser speckle imaging", Elsevier Ltd., 2005, vol. 31, pp. 744-752.
- G. J. Tearney et al., "Atherosclerotic plaque characterization by spatial and temporal speckle pattern analysis", CLEO 2001, vol. 56, pp. 307-307.
- PCT International Search Report for Application No. PCT/US2007/068233 dated Feb. 21, 2008.
- PCT International Search Report for Application No. PCT/US2007/060787 dated Mar. 18, 2008.
- Statement under Article 19 and Reply to PCT Written Opinion for PCT International Application No. PCT/US2005/043951 dated Jun. 6, 2006.
- PCT International Preliminary Report on Patentability for Application No. PCT/US2005/043951 dated Jun. 7, 2007.
- Gelikono, V. M. et al. Oct. 1, 2004 "Two-Wavelength Optical Coherence Tomography" Radio physics and Quantum Electronics, Kluwer Academic Publishers-Consultants. vol. 47, No. 10-1.
- Fox, J.A. et al; "A New Galvanometric Scanner for Rapid tuning of C02 Lasers" New York, IEEE, US vol. Apr. 7, 1991.
- Motaghian Nezam, S.M. et al: "High-speed Wavelength-Swept Semiconductor laser using a Diffraction Grating and a Polygon Scanner in Littro Configuration" *Optical Fiber Communication and the National Fiber Optic Engineers Conference* Mar. 29, 2007.
- European Official Action dated Dec. 2, 2008 for EP 07718117.0.
- Barfuss et al (1989) "Modified Optical Frequency Domain Reflectometry with High spatial Resolution for Components of integrated optic Systems", *Journal of Lightwave Technology*, IEEE vol. 7, No. 1.
- Yun et al., (2004) "Removing the Depth-Degeneracy in Optical Frequency Domain Imaging with Frequency Shifting", *Optics Express*, vol. 12, No. 20.
- International Search Report and Written Opinion dated Jun. 10, 2009 for PCT/US08/075456.
- European Search Report issued May 5, 2009 for European Application No. 01991471.2.
- Motz, J.T. et al: "Spectral-and Frequency-Encoded Fluorescence Imaging" *Optics Letters*, OSA, Optical Society of America, Washington, DC, US, vol. 30, No. 20, Oct. 15, 2005, pp. 2760-2762.
- Japanese Notice of Reasons for Rejection dated Jul. 14, 2009 for Japanese Patent application No. 2006-503161.
- Office Action dated Aug. 18, 2009 for U.S. Appl. No. 12/277,178.
- Office Action dated Aug. 13, 2009 for U.S. Appl. No. 10/136,813.
- Office Action dated Aug. 6, 2009 for U.S. Appl. No. 11/624,455.
- Office Action dated May 15, 2009 for U.S. Appl. No. 11/537,123.
- Office Action dated Apr. 17, 2009 for U.S. Appl. No. 11/537,343.
- Office Action dated Apr. 15, 2009 for U.S. Appl. No. 12/205,775.
- Office Action dated Dec. 9, 2008 for U.S. Appl. No. 09/709,162.
- Office Action dated Dec. 23, 2008 for U.S. Appl. No. 11/780,261.
- Office Action dated Jan. 9, 2010 for U.S. Appl. No. 11/624,455.
- Office Action dated Feb. 18, 2009 for U.S. Appl. No. 11/285,301.
- Beddow et al.(May 2002) "Improved Performance Interferometer Designs for Optical Coherence Tomography", IEEE Optical Fiber Sensors Conference, pp. 527-530.
- Yagoob et al., (Jun. 2002) "High-Speed Wavelength-Multiplexed Fiber-Optic Sensors for Biomedicine," *Sensors Proceedings of the IEEE*, pp. 325-330.
- Office Action dated Feb. 18, 2009 for U.S. Appl. No. 11/697,012.
- Zhan et al, (Sep. 2004), "Fourier Domain Functional Optical Coherence Tomography", Saratov Fall Meeting 2004, pp. 8-14.
- Office Action dated Feb. 23, 2009 for U.S. Appl. No. 11/956,129.
- Office Action dated Mar. 16, 2009 for U.S. Appl. No. 11/621,694.
- Office Action dated Oct. 1, 2009 for U.S. Appl. No. 11/677,278.
- Office Action dated Oct. 6, 2009 for U.S. Appl. No. 12/015,642.
- Lin, Stollen et al., (1977) "A CW Tunable Near-infrared (1.085-1.175- μ m) Raman Oscillator," *Optics Letters*, vol. 1, 96.
- Summons to attend Oral Proceedings dated Oct. 9, 2009 for European patent application No. 06813365.1.
- Office Action dated Dec. 15, 2009 for U.S. Appl. No. 11/549,397.
- European Search Report dated Apr. 13, 2011 for European Patent Application No. 10185617.7.
- Fujimoto et al., "High Resolution in Vivo Intra-Arterial Imaging with Optical Tomography," *Official Journal of the British Cardiac Society*, vol. 82, pp. 128-133 Heart, 1999.
- D. Huang et al., "Optical Coherence Tomography," *Science*, vol. 254, pp. 1178-1181, Nov. 1991.
- Tearney et al., "High-Speed Phase—and Group Delay Scanning with a Grating Based Phase Control Delay Line", *Optics Letters*, vol. 22, pp. 1811-1813, Dec. 1997.
- Rollins, et al., "In Vivo Video Rate Optical Coherence Tomography," *Optics Express*, vol. 3, pp. 219-229, Sep. 1998.
- Oscar Eduardo Martinez, "3000 Times Grating Compress or with Positive Group Velocity Dispersion," *IEEE*, vol. QE-23, pp. 59-64, Jan. 1987.
- Kulkarni, et al., "Image Enhancement in Optical Coherence Tomography Using Deconvolution," *Electronics Letters*, vol. 33, pp. 1365-1367, Jul. 1997.
- Bashkansky, et al., "Signal Processing for Improving Field Cross-Correlation Function in Optical Coherence Tomography," *Optics & Photonics News*, vol. 9, pp. 8137-8138.
- Yung et al., "Phase-Domain Processing of Optical Coherence Tomography Images," *Journal of Biomedical Optics*, vol. 4, pp. 125-136, Jan. 1999.
- Tearney, et al., "In Vivo Endoscopic Optical Biopsy with Optical Coherence Tomography," *Science*, vol. 276, Jun. 1997.
- W. Drexler et al., "In Vivo Ultrahigh-Resolution Optical Coherence Tomography," *Optics Letters* vol. 24, pp. 1221-1223, Sep. 1999.
- Nicuser V. Iftimia et al., "A Portable, Low Coherence Interferometry Based Instrument for Fine Needle Aspiration Biopsy Guidance," Accepted to Review of Scientific Instruments, 2005.
- Abbas, G.L., V.W.S. Chan et al., "Local-Oscillator Excess-Noise Suppression for Homodyne and Heterodyne-Detection," *Optics Letters*, vol. 8, pp. 419-421, Aug. 1983 issue.
- Agrawal, G.P., "Population Pulsations and Nondegenerate 4-Wave Mixing in Semiconductor-Lasers and Amplifiers," *Journal Of The Optical Society Of America B-Optical Physics*, vol. 5, pp. 147-159, Jan. 1998.
- Andretzky, P. et al., "Optical Coherence Tomography by Spectral Radar: Improvement of Signal-to-Noise Ratio," *The International Society for Optical Engineering, USA*, vol. 3915, 2000.
- Ballif, J. et al., "Rapid and Scalable Scans at 21 m/s in optical Low-Coherence Reflectometry," *Optics Letters*, vol. 22, pp. 757-759, Jun. 1997.
- Barfuss H. et al., "Modified Optical Frequency-Domain Reflectometry with High Spatial-Resolution for Components of Integrated Optic Systems," *Journal of Lightwave Technology*, vol. 7, pp. 3-10, Jan. 1989.
- Beaud, P. et al., "Optical Reflectometry with Micrometer Resolution for the Investigation of Integrated Optical-Devices," *IEEE Journal of Quantum Electronics*, vol. 25, pp. 755-759, Apr. 1989.
- Bouma, Brett et al., "Power-Efficient Nonreciprocal Interferometer and Linear-Scanning Fiber-Optic Catheter for Optical Coherence Tomography," *Optics Letters*, vol. 24, pp. 531-533, Apr. 1999.
- Brinkmeyer, E. et al., "Efficient Algorithm for Non-Equidistant Interpolation of Sampled Data," *Electronics Letters*, vol. 28, p. 693, Mar. 1992.
- Brinkmeyer, E. et al., "High-Resolution OADR in Dispersive Waveguides," *Electronics Letters*, vol. 26, pp. 413-414, Mar. 1990.
- Chinn, S.R. et al., "Optical Coherence Tomography Using a Frequency-Tunable Optical Source," *Optics Letters*, vol. 22, pp. 340-342, Mar. 1997.
- Danielson, B.L. et al., "Absolute Optical Ranging Using Low Coherence Interferometry," *Applied Optics*, vol. 30, p. 2975, Jul. 1991.

(56)

References Cited

OTHER PUBLICATIONS

- Dorrer, C. et al., "Spectral Resolution and Sampling Issues in Fourier-Transform Spectral Interferometry," *Journal of the Optical Society of America B—Optical Physics*, vol. 17, pp. 1795-1802, Oct. 2000.
- Dudley, J.M. et al., "Cross-Correlation Frequency Resolved Optical Gating Analysis of Broadband Continuum Generation in Photonic Crystal Fiber: Simulations and Experiments," *Optics Express*, vol. 10, p. 1215, Oct. 2002.
- Eickhoff, W. et al., "Optical Frequency-Domain Reflectometry in Single-Mode Fiber," *Applied Physics Letters*, vol. 39, pp. 693-695, 1981.
- Fercher, Adolf "Optical Coherence Tomography," *Journal of Biomedical Optics*, vol. 1, pp. 157-173, Apr. 1996.
- Glance, B., "Polarization Independent Coherent Optical Receiver," *Journal of Lightwave Technology*, vol. LT-5, p. 274, Feb. 1987.
- Glombitza, U., "Coherent Frequency-Domain Reflectometry for Characterization of Single-Mode Integrated-Optical Wave-Guides," *Journal of Lightwave Technology*, vol. 11, pp. 1377-1384, Aug. 1993.
- Golubovic, B. et al., "Optical Frequency-Domain Reflectometry Using Rapid Wavelength Tuning of a Cr⁴⁺:Forsterite Laser," *Optics Letters*, vol. 11, pp. 1704-1706, Nov. 1997.
- Haberland, U. H. P. et al., "Chirp Optical Coherence Tomography of Layered Scattering Media," *Journal of Biomedical Optics*, vol. 3, pp. 259-266, Jul. 1998.
- Hammer, Daniel X. et al., "Spectrally Resolved White-Light Interferometry for Measurement of Ocular Dispersion," *Journal of the Optical Society of America A—Optics Image Science and Vision*, vol. 16, pp. 2092-2102, Sep. 1999.
- Harvey, K. C. et al., "External-Cavity Diode-Laser Using a Grazing-Incidence Diffraction Grating," *Optics Letters*, vol. 16, pp. 910-912, Jun. 1991.
- Hausler, Gerd et al., "'Coherence Radar' and 'Spectral Radar' New Tools for Dermatological Diagnosis," *Journal of Biomedical Optics*, vol. 3, pp. 21-31, Jan. 1998.
- Hee, Michael R. et al., "Polarization-Sensitive Low-Coherence Reflectometer for Birefringence Characterization and Ranging," *Journal of the Optical Society of America B. (Optical Physics)*, vol. 9, p. 903-908, Jun. 1992.
- Hotate Kazuo et al., "Optical Coherence Domain Reflectometry by Synthesis of Coherence Function," *Journal of Lightwave Technology*, vol. 11, pp. 1701-1710, Oct. 1993.
- Inoue, Kyo et al., "Nearly Degenerate 4-Wave-Mixing in a Traveling-Wave Semiconductor-Laser Amplifier," *Applied Physics Letters*, vol. 51, pp. 1051-1053, 1987.
- Ivanov, A. P. et al., "New Method for High-Range Resolution Measurements of Light Scattering in Optically Dense Inhomogeneous Media," *Optics Letters*, vol. 1, pp. 226-228, Dec. 1977.
- Ivanov, A. P. et al., "Interferometric Study of the Spatial Structure of a Light-Scattering Medium," *Journal of Applied Spectroscopy*, vol. 28, pp. 518-525, 1978.
- Kazovsky, L. G. et al., "Heterodyne Detection Through Rain, Snow, and Turbid Media: Effective Receiver Size at Optical Through Millimeter Wavelengths," *Applied Optics*, vol. 22, pp. 706-710, Mar. 1983.
- Kersey, A. D. et al., "Adaptive Polarization Diversity Receiver Configuration for Coherent Optical Fiber Communications," *Electronics Letters*, vol. 25, pp. 275-277, Feb. 1989.
- Kohlhaas, Andreas et al., "High-Resolution OCDR for Testing Integrated-Optical Waveguides: Dispersion-Corrupted Experimental Data Corrected by a Numerical Algorithm," *Journal of Lightwave Technology*, vol. 9, pp. 1493-1502, Nov. 1991.
- Larkin, Kieran G., "Efficient Nonlinear Algorithm for Envelope Detection in White Light Interferometry," *Journal of the Optical Society of America A—Optics Image Science and Vision*, vol. 13, pp. 832-843, Apr. 1996.
- Leitgeb, R. et al., "Spectral measurement of Absorption by Spectroscopic Frequency-Domain Optical Coherence Tomography," *Optics Letters*, vol. 25, pp. 820-822, Jun. 2000.
- Lexer, F. et al., "Wavelength-Tuning Interferometry of Intraocular Distances," *Applied Optics*, vol. 36, pp. 6548-6553, Sep. 1997.
- Mitsui, Takahisa, "Dynamic Range of Optical Reflectometry with Spectral Interferometry," *Japanese Journal of Applied Physics Part I—Regular Papers Short Notes & Review Papers*, vol. 38, pp. 6133-6137, 1999.
- Naganuma, Kazunori et al., "Group-Delay Measurement Using the Fourier-Transform of an Interferometric Cross-Correlation Generated by White Light," *Optics Letters*, vol. 15, pp. 393-395, Apr. 1990.
- Okoshi, Takanori, "Polarization-State Control Schemes for Heterodyne or Homodyne Optical Fiber Communications," *Journal of Lightwave Technology*, vol. LT-3, pp. 1232-1237, Dec. 1995.
- Passy, R. et al., "Experimental and Theoretical Investigations of Coherent OFDR with Semiconductor-Laser Sources," *Journal of Lightwave Technology*, vol. 12, pp. 1622-1630, Sep. 1994.
- Podoleanu, Adrian G., "Unbalanced Versus Balanced Operation in an Optical Coherence Tomography System," *Applied Optics*, vol. 39, pp. 173-182, Jan. 2000.
- Price, J. H. V. et al., "Tunable, Femtosecond Pulse Source Operating in the Range 1.06-1.33 μ m Based on an Yb³⁺-doped Hole Fiber Amplifier," *Journal of the Optical Society of America B—Optical Physics*, vol. 19, pp. 1286-1294, Jun. 2002.
- Schmitt, J. M. et al., "Measurement of Optical-Properties of Biological Tissues by Low-Coherence Reflectometry," *Applied Optics*, vol. 32, pp. 6032-6042, Oct. 1993.
- Silberberg, Y. et al., "Passive-Mode Locking of a Semiconductor Diode-Laser," *Optics Letters*, vol. 9, pp. 507-509, Nov. 1984.
- Smith, L. Montgomery et al., "Absolute Displacement Measurements Using Modulation of the Spectrum of White-Light in a Michelson Interferometer," *Applied Optics*, vol. 28, pp. 3339-3342, Aug. 1989.
- Sonnenschein, C. M. et al., "Signal-To-Noise Relationships for Coaxial Systems that Heterodyne Backscatter from Atmosphere," *Applied Optics*, vol. 10, pp. 1600-1604, Jul. 1971.
- Sorin, W. V. et al., "Measurement of Rayleigh Backscattering at 1.55 μ m with 32 μ m Spatial Resolution," *IEEE Photonics Technology Letters*, vol. 4, pp. 374-376, Apr. 1992.
- Sorin, W. V. et al., "A Simple Intensity Noise-Reduction Technique for Optical Low-Coherence Reflectometry," *IEEE Photonics Technology Letters*, vol. 4, pp. 1404-1406, Dec. 1992.
- Swanson, E. A. et al., "High-Speed Optical Coherence Domain Reflectometry," *Optics Letters*, vol. 17, pp. 151-153, Jan. 1992.
- Takada, K. et al., "High-Resolution OFDR with Incorporated Fiberoptic Frequency Encoder," *IEEE Photonics Technology Letters*, vol. 4, pp. 1069-1072, Sep. 1992.
- Takada, Kazumasa et al., "Narrow-Band light Source with Acoustooptic Tunable Filter for Optical Low-Coherence Reflectometry," *IEEE Photonics Technology Letters*, vol. 8, pp. 658-660, May 1996.
- Takada, Kazumasa et al., "New Measurement System for Fault Location in Optical Wave-Guide Devices Based on an Interometric-Technique," *Applied Optics*, vol. 26, pp. 1603-1606, May 1987.
- Tateda, Mitsuhiro et al., "Interferometric Method for Chromatic Dispersion Measurement in a Single-Mode Optical Fiber," *IEEE Journal Of Quantum Electronics*, vol. 17, pp. 404-407, Mar. 1981.
- Toide, M. et al., "Two-Dimensional Coherent Detection Imaging in Multiple Scattering Media Based the Directional Resolution Capability of the Optical Heterodyne Method," *Applied Physics B (Photophysics and Laser Chemistry)*, vol. B52, pp. 391-394, 1991.
- Trutna, W. R. et al., "Continuously Tuned External-Cavity Semiconductor-Laser," *Journal of Lightwave Technology*, vol. 11, pp. 1279-1286, Aug. 1993.
- Utam, Deepak et al., "Precision Time Domain Reflectometry in Optical Fiber Systems Using a Frequency Modulated Continuous Wave Ranging Technique," *Journal of Lightwave Technology*, vol. 3, pp. 971-977, Oct. 1985.
- Von Der Weid, J. P. et al., "On the Characterization of Optical Fiber Network Components with Optical Frequency Domain Reflectometry," *Journal of Lightwave Technology*, vol. 15, pp. 1131-1141, Jul. 1997.
- Wysocki, P.F. et al., "Broad-Spectrum, Wavelength-Swept, Erbium-Doped Fiber Laser at 1.55- μ m," *Optics Letters*, vol. 15, pp. 879-881, Aug. 1990.

(56)

References Cited

OTHER PUBLICATIONS

- Youngquist, Robert C. et al., "Optical Coherence-Domain Reflectometry—A New Optical Evaluation Technique," *Optics Letters*, vol. 12, pp. 158-160, Mar. 1987.
- Yun, S. H. et al., "Wavelength-Swept Fiber Laser with Frequency Shifted Feedback and Resonantly Swept Intra-Cavity Acoustooptic Tunable Filter," *IEEE Journal of Selected Topics In Quantum Electronics*, vol. 3, pp. 1087-1096, Aug. 1997.
- Yun, S. H. et al., "Interrogation of Fiber Grating Sensor Arrays with a Wavelength-Swept Fiber Laser," *Optics Letters*, vol. 23, pp. 843-845, Jun. 1998.
- Yung, K. M., "Phase-Domain Processing of Optical Coherence Tomography Images," *Journal of Biomedical Optics*, vol. 4, pp. 125-136, Jan. 1999.
- Zhou, Xiao-Qun et al., "Extended-Range FMCW Reflectometry Using an optical Loop with a Frequency Shifter," *IEEE Photonics Technology Letters*, vol. 8, pp. 248-250, Feb. 1996.
- Zorabedian, Paul et al., "Tuning Fidelity of Acoustooptically Controlled External Cavity Semiconductor-Lasers," *Journal of Lightwave Technology*, vol. 13, pp. 62-66, Jan. 1995.
- Victor S. Y. Lin et al., "A Porous Silicon-Based Optical Interferometric Biosensor," *Science Magazine*, vol. 278, pp. 840-843, Oct. 31, 1997.
- De Boer, Johannes F. et al., "Review of Polarization Sensitive Optical Coherence Tomography and Stokes Vector Determination," *Journal of Biomedical Optics*, vol. 7, No. 3, Jul. 2002, p. 359-371.
- Wang, Xuedong et al., (2001) "Propagation of Polarized Light in Birefringent Turbid Media: Time-Resolved Simulations," Optical Imaging Laboratory, Biomedical Engineering Program, Texas A&M University, Aug. 27, 2001, pp. 254-259.
- Yasuno, Y. et al., "Birefringence Imaging of Human Skin by Polarization-Sensitive Spectral Interferometric Optical Coherence Tomography," *Optics Letters*, vol. 27, No. 20, Oct. 15, 2002 pp. 1803-1805.
- Nassif, N.A. et al., "In Vivo High-Resolution Video-Rate Spectral-Domain Optical Coherence Tomography of the Human Retina and Optical Nerve," *Optics Express*, vol. 12, No. 3, Feb. 9, 2004, pp. 367-376.
- Pircher, Michael et al., "Imaging of Polarization Properties of Human Retina in Vivo with Phase Resolved Transversal PS-OCT," *Optics Express*, vol. 12, No. 24, Nov. 29, 2004 pp. 5940-5951.
- Blumenthal, E. Z., J. M. Williams, et al. (2000). "Reproducibility of nerve fiber layer thickness measurements by use of optical coherence tomography," *Ophthalmology* 107(12): 2278-82.
- Bouma, B. E. and J. G. Fujimoto (1996). "Compact Kerr-lens mode-locked resonators," *Optics Letters* 21. 134-136.
- Bouma, B. E., L. E. Nelson, et al. (1998). "Optical coherence tomographic imaging of human tissue at 1.55 μm and 1.81 μm using Er and Tm-doped fiber sources," *Journal of Biomedical Optics* 3. 76-79.
- Bouma, B. E., M. Ramaswamy-Paye, et al. (1997). "Compact resonator designs for mode-locked solid-state lasers," *Applied Physics B (Lasers and Optics)* B65. 213-220.
- Drexler, W., O. Findl, et al. (1998). "Partial coherence interferometry: A novel approach to biometry in cataract surgery," *American Journal of Ophthalmology* 126(4): 524-534.
- Droog, E. J., W. Steenbergen, et al. (2001). "Measurement of depth of burns by laser Doppler perfusion imaging," *Burns* 27(6): 561-8.
- Eisenbeiss, W., J. Marotz, et al. (1999). "Reflection-optical multispectral imaging method for objective determination of burn depth," *Burns* 25(8): 697-704.
- Feldchtein, F. I., G. V. Gelikonov, et al. (1998). "Endoscopic applications of optical coherence tomography," *Optics Express* 3(6): 257-270.
- Fercher, A. F., W. Drexler, et al. (1994). *Measurement of optical distances by optical spectrum modulation*. Proceedings of SPIE—The International Society for Optical Engineering.
- Fercher, A. F., W. Drexler, et al. (2003). "Optical coherence tomography—principles and applications," *Reports on Progress in Physics* 66(2): 239-303.
- Ferro, P., M. Haelterman, et al. (1991). "All-Optical Polarization Switch with Long Low-Birefringence Fiber," *Electronics Letters* 27(16): 1407-1408.
- Hoeling, B. M., A. D. Fernandez, et al. (2000). "An optical coherence microscope for 3-dimensional imaging in developmental biology," *Optics Express* 6(7): 136-146.
- Imai, M., H. Iijima, et al. (2001). "Optical coherence tomography of tractional macular elevations in eyes with proliferative diabetic retinopathy. [republished in Am J Ophthalmol. Sep. 2001;132(3):458-61 ; 11530091.]," *American Journal of Ophthalmology* 132(1):81-4.
- Jopson, R. M. The., L. E. Nelson, et al. (1999). "Measurement of second-order polarization-mode dispersion vectors in optical fibers," *Ieee Photonics Technology Letters* 11 (9): 1153-1155.
- Leibowitz, H. M., D. E. Krueger, et al. (1980). "The Framingham Eye Study monograph: An ophthalmological and epidemiological study of cataract, glaucoma, diabetic retinopathy, macular degeneration, and visual acuity in a general population of 2631 adults, 1973-1975," *Survey of Ophthalmology* 24(Suppl): 335-610.
- Leske, M. C., A. M. Connell, et al. (2001). "Incidence of open-angle glaucoma: the Barbados Eye Studies. The Barbados Eye Studies Group. [see comments]," *Archives of Ophthalmology* 119(1):89-95.
- Lewis, S. E., J. R. DeBoer, et al. (2005). "Sensitive, selective, and analytical improvements to a porous silicon gas sensor," *Sensors and Actuators B: Chemical* 110(1): 54-65.
- Mansuripur, M. (1991). "Effects of High-Numerical-Aperture Focusing on the State of Polarization in Optical and Magnetooptic Data-Storage Systems," *Applied Optics* 30(22): 3154-3162.
- Martinez, O. E. (1987). "3000 Times Grating Compressor with Positive Group-Velocity Dispersion—Application to Fiber Compensation in 1.3-1.6 μm Region," *Ieee Journal of Quantum Electronics* 23(1): 59-64.
- Miglior, S., M. Casula, et al. (2001). "Clinical ability of Heidelberg retinal tomograph examination to detect glaucomatous visual field changes," *Ophthalmology* 108(9): 1621-7.
- Morgner, U., F. X. Kartner, et al. (1999). "Sub-two-cycle pulses from a Kerr-lens mode-locked Ti:sapphire laser (vol. 24, p. 411, 1999)," *Optics Letters* 24(13): 920-920.
- Park, B. H., M. C. Pierce, et al. (2005). "Real-time fiber-based multifunctional spectral-domain optical coherence tomography at 1.3 μm ," *Optics Express* 13(11): 3931-3944.
- Sarunic, M. V., M. A. Choma, et al. (2005). "Instantaneous complex conjugate resolved spectral domain and swept-source OCT using 3x3 fiber couplers," *Optics Express* 13(3): 957-967.
- Shi, H., J. Finlay, et al. (1997). "Multiwavelength 10-GHz picosecond pulse generation from a single-stripe semiconductor diode laser," *Ieee Photonics Technology Letters* 9(11): 1439-1441.
- Smith, P. J. M., E.M.; Taylor, C.M.; Selviah, D.R.; Day, S.E.; Commander, L.G. (2000) "Variable-Focus Microlenses as a Potential Technology for Endoscopy," *SPIE* (vol. 3919), USA pp. 187-192.
- Sticker, M., C. K. Hitzengerber, et al. (2001). "Quantitative differential phase measurement and imaging in transparent and turbid media by optical coherence tomography," *Optical Letters* 26(8): 518-520.
- Vansteenkiste, N., P. Vignolo, et al. (1993). "Optical Reversibility Theorems for Polarization—Application to Remote-Control of Polarization," *Journal of the Optical Society of America a—Optics Image Science and Vision* 10(10): 2240-2245.
- Wang, X. J., T. E. Milner, et al., (1997). "Measurement of fluid-flow-velocity profile in turbid media by the use of optical Doppler tomography," *Applied Optics* 36(1): 144-149.
- Wang, Y. M., Y. H. Zhao, et al. (2003). "Ultrahigh-resolution optical coherence tomography by broadband continuum generation from a photonic crystal fiber," *Optics Letters* 28(3): 182-184.
- Wong, B. J. F., Y. H. Zhao, et al. (2004). "Imaging the internal structure of the rat cochlea using optical coherence tomography at 0.827 μm and 1.3 μm ," *Otolaryngology-Head and Neck Surgery* 130(3): 334-338.
- Yabushita, H. B., et al. (2002) "Measurement of Thin Fibrous Caps in Atherosclerotic Plaques by Optical Coherence Tomography," American Heart Association, INC, Circulation 2002;106:1640.
- Hajime Tanaka et al., "New Method of Superheterodyne Light Beating Spectroscopy for Brillouin-Scattering Using Frequency-Tunable Lasers", *Physical Review Letters* 1995, 74 (9): 1609-1612.

(56)

References Cited

OTHER PUBLICATIONS

- K.J. Koski et al., "Brillouin imaging" *Applied Physics Letters* 87, 2005.
- David J. Briers, "Speckle fluctuations and biomedical optics: implications and applications", *Optical Engineering*, 1993, 32(2):277-283.
- Clark et al., "Tracking Speckle Patterns with Optical Correlation", *SPIE*, 1992, 1772:77-87.
- Notice of Reasons for Rejection and English translation for Japanese Patent Application No. 2002-538830 dated May 12, 2008.
- Office Action dated Aug. 24, 2006 for U.S. Appl. No. 10/137,749.
- Barry Cense et al., "Spectral-domain polarization-sensitive optical coherence tomography at 850nm", *Coherence Domain Optical Methods and Optical Coherence Tomography in Biomedicine IX*, 2005, pp. 159-162.
- Elliott, K. H. "The use of commercial CCD cameras as linear detectors in the physics undergraduate teaching laboratory", *European Journal of Physics*, 1998, pp. 107-117.
- Jerath, Maya R. et al (1992) "Dynamic Optical Property Changes: Implications for Reflectance Feedback Control of Photocoagulation" *Journal of Photochemical, Photobiology: B: Biol* vol. 16, pp. 113-126.
- Lewis, Neil E. et al., (2006) "Applications of Fourier Transform Infrared Imaging Microscopy in Neurotoxicity", *Annals New York Academy of Sciences*, Dec. 17, 2006, vol. 820, pp. 234-246.
- Joo, Chulmin et al., Spectral-domain optical coherence phase microscopy for quantitative phase-contrast imaging, *Optics Letters*, Aug. 15, 2005, vol. 30, No. 16, pp. 2131-2133.
- Nadkarni, Seemantini K., et al., "Measurement of fibrous cap thickness in atherosclerotic plaques by spatiotemporal analysis of laser speckle images", *Journal of Biomedical Optics*, vol. 11 Marsh/Apr. 2006, pp. 021006-1-8.
- J. M. Schmitt et al., (1999) "Speckle in Optical Coherence Tomography: An Overview", *SPIE* vol. 3726, pp. 450-461.
- Office Action dated Oct. 9, 2007 for U.S. Appl. No. 09/709,162.
- R. Haggitt et al., "Barrett's Esophagus Correlation Between Mucin Histochemistry, Flow Cytometry, and Histological Diagnosis for Predicting Increased Cancer Risk," Apr. 1988, *American Journal of Pathology*, vol. 131, No. 1, pp. 53-61.
- R.H. Hardwick et al., (1995) "c-erbB3-2 Overexpression in the Dysplasia/Carcinoma Sequence of Barrett's Oesophagus," *Journal of Clinical Pathology*, vol. 48, No. 2, pp. 129-132.
- W. Polkowski et al., (1998) Clinical Decision making in Barrett's Oesophagus can be supported by Computerized Immunoquantitation and Morphometry of Features Associated with Proliferation and Differentiation, *Journal of pathology*, vol. 184, pp. 161-168.
- J.R. Turner et al., MN Antigen Expression in Normal Preneoplastic, and Neoplastic Esophagus: A Clinicopathological Study of a New Cancer-Associated Biomarker, Jun. 1997, *Human Pathology*, vol. 28, No. 6, pp. 740-744.
- D.J. Bowery et al., (1999) "Patterns of Gastritis in Patients with Gastro-Oesophageal Reflux Disease," *Gut*, vol. 45, pp. 798-803.
- O'Reich et al., (2000) "Expression of Oestrogen and Progesterone Receptors in Low-Grade Endometrial Stromal Sarcomas," *British Journal of Cancer*, vol. 82, No. 5, pp. 1030-1034.
- M.I. Canto et al., (1999) "Vital Staining and Barrett's Esophagus," *Gastrointestinal Endoscopy*, vol. 49, No. 3, Part 2, pp. S12-S16.
- S. Jackie et al., (2000) "In Vivo Endoscopic Optical Coherence Tomography of the Human Gastrointestinal Tract-Toward Optical Biopsy," *Endoscopy*, vol. 32, No. 10, pp. 743-749.
- E. Montgomery et al., "Reproducibility of the Diagnosis of Dysplasia in Barrett Esophagus: A Reaffirmation," Apr. 2001, *Human Pathology*, vol. 32, No. 4, pp. 368-378.
- H. Geddert et al., "Expression of Cyclin B1 in the Metaplasia-Dysplasia-Carcinoma Sequence of Barrett Esophagus," Jan. 2002, *Cancer*, vol. 94, No. 1, pp. 212-218.
- P. Pfau et al., (2003) "Criteria for the Diagnosis of Dysphasia by Endoscopic Optical Coherence Tomography," *Gastrointestinal Endoscopy*, vol. 58, No. 2, pp. 196-2002.
- R. Kiesslich et al., (2004) "Confocal Laser Endoscopy for Diagnosing Intraepithelial Neoplasias and Colorectal Cancer in Vivo," *Gastroenterology*, vol. 127, No. 3, pp. 706-713.
- X. Qi et al., (2004) "Computer Aided Diagnosis of Dysphasia in Barrett's Esophagus Using Endoscopic Optical Coherence Tomography," *SPIE, Coherence Domain Optical Methods and Optical Coherence Tomography in Biomedicine VIII. Proc. of Conference on*, vol. 5316, pp. 33-40.
- Seltzer et al., (1991) "160 nm Continuous Tuning of a MQW Laser in an External Cavity Across the Entire 1.3 μ m Communications Window," *Electronics Letters*, vol. 27, pp. 95-96.
- Office Action dated Jan. 25, 2010 for U.S. Appl. No. 11/537,048.
- International Search Report dated Jan. 27, 2010 for PCT/US2009/050553.
- International Search Report dated Jan. 27, 2010 for PCT/US2009/047988.
- International Search Report dated Feb. 23, 2010 for U.S. Appl. No. 11/445,131.
- Office Action dated Mar. 18, 2010 of U.S. Appl. No. 11/844,454.
- Office Action dated Apr. 8, 2010 of U.S. Appl. No. 11/414,564.
- Japanese Office Action dated Apr. 13, 2010 for Japanese Patent application No. 2007-515029.
- International Search Report dated May 27, 2010 for PCT/US2009/063420.
- Office Action dated May 28, 2010 for U.S. Appl. No. 12/015,642.
- Office Action dated Jun. 2, 2010 for U.S. Appl. No. 12/112,205.
- Office Action dated Jul. 7, 2010 for U.S. Appl. No. 11/624,277.
- Montag Ethan D., "Parts of the Eye" online textbook for JIMG 774: Vision & Psychophysics, download on Jun. 23, 2010 from http://www.cis.rit.edu/people/faculty/montag/vandplite/pages/chap_8/ch8p3.html.
- Office Action dated Jul. 16, 2010 for U.S. Appl. No. 11/445,990.
- Office Action dated Jul. 20, 2010 for U.S. Appl. No. 11/625,135.
- Office Action dated Aug. 5, 2010 for U.S. Appl. No. 11/623,852.
- Chinese office action dated Aug. 4, 2010 for CN 200780005949.9.
- Chinese office action dated Aug. 4, 2010 for CN 200780016266.3.
- Zhang, et al., "Full Range Polarization-Sensitive Fourier Domain Optical Coherence Tomography" *Optics Express*, Nov. 29, 2004, vol. 12, No. 24.
- Office Action dated Aug. 27, 2010 for U.S. Appl. No. 11/569,790.
- Office Action dated Aug. 31, 2010 for U.S. Appl. No. 11/677,278.
- Office Action dated Sep. 3, 2010 for U.S. Appl. No. 12/159,314.
- Yong Zhao et al: "Virtual Data Grid Middleware Services for Data-Intensive Science", *Concurrency and Computation: Practice and Experience*, Wiley, London, GB, Jan. 1, 2000, pp. 1-7, pp. 1532-0626.
- Swan et al., "Toward Nanometer-Scale Resolution in Fluorescence Microscopy using Spectral Self-Interference" *IEEE Journal. Selected Topics in Quantum Electronics* 9 (2) 2003, pp. 294-300.
- Moiseev et al., "Spectral Self-Interference Fluorescence Microscopy", *J. Appl. Phys.* 96 (9) 2004, pp. 5311-5315.
- Hendrik Verschuere, "Interference Reflection Microscopy in Cell Biology", *J. Cell Sci.* 75, 1985, pp. 289-301.
- Park et al., "Diffraction Phase and Fluorescence Microscopy", *Opt. Expr.* 14 (18) 2006, pp. 8263-8268.
- Swan et al., "High Resolution Spectral Self-Interference Fluorescence Microscopy", *Proc. SPIE* 4621, 2002, pp. 77-85.
- Sanchez et al., "Near-Field Fluorescence Microscopy Based on Two-Photon Excitation with Metal Tips", *Phys. Rev. Lett.* 82 (20) 1999, pp. 4014-4017.
- Wojtkowski, Maciej, Ph.D. "Three-Dimensional Retinal Imaging with High-Speed Ultrahigh-Resolution Optical Coherence Tomography" *Ophthalmology*, Oct. 2005, 112(10): 1734-1746.
- Vaughan, J.M. et al., "Brillouin Scattering, Density and Elastic Properties of the Lens and Cornea of the Eye", *Nature*, vol. 284, Apr. 3, 1980, pp. 489-491.
- Hess, S.T. et al. "Ultra-high Resolution Imaging by Fluorescence Photoactivation Localization Microscopy" *Biophysical Journal* vol. 91, Dec. 2006.
- Fernandez-Suarez, M. et al., "Fluorescent Probes for Super-Resolution Imaging in Living Cells" *Nature Reviews Molecular Cell Biology* vol. 9, Dec. 2008.

(56)

References Cited

OTHER PUBLICATIONS

Extended European Search Report mailed Dec. 14, 2010 for EP 10182301.1.

S. Hell et al., "Breaking the diffraction resolution limit by stimulated-emission—stimulated-emission depletion fluorescence microscopy," *Optics Letters*, 19:495 (1995) and Ground State Depletion (GSD).

S. Hell et al. "Ground-State-Depletion fluorescence microscopy—a concept for breaking the diffraction resolution limit," *Applied Physics B*, 60:780 (1994)) fluorescence microscopy, photo-activated localization microscopy (PALM).

E. Betzig et al. "Imaging intracellular fluorescent proteins at nanometer resolution," *Science* 313:1642 (2006), stochastic optical reconstruction microscopy (STORM).

M. Rust et al. "Sub-diffraction-limited imaging by stochastic optical reconstruction microscopy (STORM)," *Nature Methods* 3:783 (2006), and structured illumination microscopy (SIM).

Bailey et al. "Enhancement of Axial Resolution in Fluorescence Microscopy by Standing-Wave Excitation," *Nature* 366:44 (1993).

M. Gustafsson "Surpassing the lateral resolution limit by a factor of two using structured illumination microscopy," *Journal of Microscopy* 198:82 (2000).

M. Gustafsson "Nonlinear structured illumination microscopy: Wide-field fluorescence imaging with theoretically unlimited resolution," *PNAS* 102:13081 (2005)).

R. Thompson et al. "Precise nanometer localization analysis for individual fluorescent probes," *Biophysical Journal* 82:2775 (2002).

K. Drabe et al. "Localization of Spontaneous Emission in front of a mirror," *Optics Communications* 73:91 (1989).

Swan et al. "Toward nanometer-scale resolution in fluorescence microscopy using spectral self-interference," *IEEE Quantum Electronics* 9:294 (2003).

C. Joo, et al. "Spectral Domain optical coherence phase and multiphoton microscopy," *Optics Letters* 32:623 (2007).

Virmani et al., "Lesions from sudden coronary death: A comprehensive morphological classification scheme for atherosclerotic lesions," *Arterioscler. Thromb. Vase. Bio.*, 20:1262-75 (2000).

Gonzalez, R.C. and Wintz, P., "Digital Image Processing" Addison-Wesley Publishing Company, Reading MA, 1987.

V. Tuchin et al., "Speckle interferometry in the measurements of tissues vibrations," *SPIE*, 1647: 125 (1992).

A.A. Bednov et al., "Investigation of Statistical Properties of Lymph Flow Dynamics Using Speckle-Microscopy," *SPIE*, 2981: 181-90 (1997).

Feng et al., "Mesoscopic Conductors and Correlations in Laser Speckle Patterns" *Science*, New Series, vol. 251, No. 4994, pp. 633-639 (Feb. 8, 1991).

Lee et al., "The Unstable Atheroma," *Arteriosclerosis, Thrombosis & Vascular Biology*, 17:1859-67 (1997).

International Search report dated Apr. 29, 2011 for PCT/US2010/051715.

International Search report dated Sep. 13, 2010 for PCT/US2010/023215.

International Search Report dated Jul. 28, 2011 for PCT/US2010/059534.

International Search report dated Nov. 18, 2011 for PCT/US2011/027450.

International Search report dated Nov. 18, 2011 for PCT/US2011/027437.

International Search report dated Nov. 22, 2011 for PCT/US2011/027421.

De Boer, Johannes F. et al., "Review of Polarization Sensitive Optical Coherence Tomography and Stokes Vector Determination," *Journal of Biomedical Optics*, vol. 7, No. 3, Jul. 2002, pp. 359-371.

Jiao, Shuliang et al., "Depth-Resolved Two-Dimensional Stokes Vectors of Backscattered Light and Mueller Matrices of Biological Tissue Measured with Optical Coherence Tomography," *Applied Optics*, vol. 39, No. 34, Dec. 1, 2000, pp. 6318-6324.

Park, B. Hyle et al., "In Vivo Burn Depth Determination by High-Speed Fiber-Based Polarization Sensitive Optical Coherence Tomography," *Journal of Biomedical Optics*, vol. 6 No. 4, Oct. 2001, pp. 474-479.

Roth, Jonathan E. et al., "Simplified Method for Polarization-Sensitive Optical Coherence Tomography," *Optics Letters*, vol. 26, No. 14, Jul. 15, 2001, pp. 1069-1071.

Hitzenberger, Christopher K. et al., "Measurement and Imaging of Birefringence and Optic Axis Orientation by Phase Resolved Polarization Sensitive Optical Coherence Tomography," *Optics Express*, vol. 9, No. 13, Dec. 17, 2001, pp. 780-790.

Wang, Xueding et al., "Propagation of Polarized Light in Birefringent Turbid Media: Time-Resolved Simulations," *Optical Imaging Laboratory, Biomedical Engineering Program, Texas A&M University*.

Wong, Brian J.F. et al., "Optical Coherence Tomography of the Rat Cochlea," *Journal of Biomedical Optics*, vol. 5, No. 4, Oct. 2000, pp. 367-370.

Yao, Gang et al., "Propagation of Polarized Light in Turbid Media: Simulated Animation Sequences," *Optics Express*, vol. 7, No. 5, Aug. 28, 2000, pp. 198-203.

Wang, Xiao-Jun et al., "Characterization of Dentin and Enamel by Use of Optical Coherence Tomography," *Applied Optics*, vol. 38, No. 10, Apr. 1, 1999, pp. 2092-2096.

De Boer, Johannes F. et al., "Determination of the Depth-Resolved Stokes Parameters of Light Backscattered from Turbid Media by use of Polarization-Sensitive Optical Coherence Tomography," *Optics Letters*, vol. 24, No. 5, Mar. 1, 1999, pp. 300-302.

Ducros, Mathieu G. et al., "Polarization Sensitive Optical Coherence Tomography of the Rabbit Eye," *IEEE Journal of Selected Topics in Quantum Electronics*, vol. 5, No. 4, Jul./Aug. 1999, pp. 1159-1167.

Groner, Warren et al., "Orthogonal Polarization Spectral Imaging: A New Method for Study of the Microcirculation," *Nature Medicine Inc.*, vol. 5 No. 10, Oct. 1999, pp. 1209-1213.

De Boer, Johannes F. et al., "Polarization Effects in Optical Coherence Tomography of Various Biological Tissues," *IEEE Journal of Selected Topics in Quantum Electronics*, vol. 5, No. 4, Jul./Aug. 1999, pp. 1200-1204.

Yao, Gang et al., "Two-Dimensional Depth-Resolved Mueller Matrix Characterization of Biological Tissue by Optical Coherence Tomography," *Optics Letters*, Apr. 15, 1999, vol. 24, No. 8, pp. 537-539.

Lu, Shih-Yau et al., "Homogeneous and Inhomogeneous Jones Matrices," *J. Opt. Soc. Am. A*, vol. 11, No. 2, Feb. 1994, pp. 766-773.

Bickel, S. William et al., "Stokes Vectors, Mueller Matrices, and Polarized Scattered Light," *Am. J. Phys.*, vol. 53, No. 5, May 1985 pp. 468-478.

Bréhonnet, F. Le Roy et al., "Optical Media and Target Characterization by Mueller Matrix Decomposition," *J. Phys. D: Appl. Phys.* 29, 1996, pp. 34-38.

Cameron, Brent D. et al., "Measurement and Calculation of the Two-Dimensional Backscattering Mueller Matrix of a Turbid Medium," *Optics Letters*, vol. 23, No. 7, Apr. 1, 1998, pp. 485-487.

De Boer, Johannes F. et al., "Two-Dimensional Birefringence Imaging in Biological Tissue by Polarization-Sensitive Optical Coherence Tomography," *Optics Letters*, vol. 22, No. 12, Jun. 15, 1997, pp. 934-936.

De Boer, Johannes F. et al., "Imaging Thermally Damaged Tissue by Polarization Sensitive Optical Coherence Tomography," *Optics Express*, vol. 3, No. 6, Sep. 14, 1998, pp. 212-218.

Everett, M.J. et al., "Birefringence Characterization of Biological Tissue by Use of Optical Coherence Tomography," *Optics Letters*, vol. 23, No. 3, Feb. 1, 1998, pp. 228-230.

Hee, Michael R. et al., "Polarization-Sensitive Low-Coherence Reflectometer for Birefringence Characterization and Ranging," *J. Opt. Soc. Am. B*, vol. 9, No. 6, Jun. 1992, pp. 903-908.

Barakat, Richard, "Statistics of the Stokes Parameters," *J. Opt. Soc. Am. B*, vol. 4, No. 7, Jul. 1987, pp. 1256-1263.

Schmitt, J.M. et al., "Cross-Polarized Backscatter in Optical Coherence Tomography of Biological Tissue," *Optics Letters*, vol. 23, No. 13, Jul. 1, 1998, pp. 1060-1062.

(56)

References Cited

OTHER PUBLICATIONS

- Schoenenberger, Klaus et al., "Mapping of Birefringence and Thermal Damage in Tissue by use of Polarization-Sensitive Optical Coherence Tomography," *Applied Optics*, vol. 37, No. 25, Sep. 1, 1998, pp. 6026-6036.
- Pierce, Mark C. et al., "Simultaneous Intensity, Birefringence, and Flow Measurements with High-Speed Fiber-Based Optical Coherence Tomography," *Optics Letters*, vol. 27, No. 17, Sep. 1, 2002, pp. 1534-1536.
- De Boer, Johannes F. et al., "Review of Polarization Sensitive Optical Coherence Tomography and Stokes Vector Determination," *Journal of Biomedical Optics*, Jul. 2002, vol. 7, No. 3, pp. 359-371.
- Fried, Daniel et al., "Imaging Caries Lesions and Lesion Progression with Polarization Sensitive Optical Coherence Tomography," *Journal of Biomedical Optics*, vol. 7, No. 4, Oct. 2002, pp. 618-627.
- Jiao, Shuliang et al., "Two-Dimensional Depth-Resolved Mueller Matrix of Biological Tissue Measured with Double-Beam Polarization-Sensitive Optical Coherence Tomography," *Optics Letters*, vol. 27, No. 2, Jan. 15, 2002, pp. 101-103.
- Jiao, Shuliang et al., "Jones-Matrix Imaging of Biological Tissues with Quadruple-Channel Optical Coherence Tomography," *Journal of Biomedical Optics*, vol. 7, No. 3, Jul. 2002, pp. 350-358.
- Kuranov, R.V. et al., "Complementary Use of Cross-Polarization and Standard OCT for Differential Diagnosis of Pathological Tissues," *Optics Express*, vol. 10, No. 15, Jul. 29, 2002, pp. 707-713.
- Cense, Barry et al., "In Vivo Depth-Resolved Birefringence Measurements of the Human Retinal Nerve Fiber Layer by Polarization-Sensitive Optical Coherence Tomography," *Optics Letters*, vol. 27, No. 18, Sep. 15, 2002, pp. 1610-1612.
- Ren, Hongwu et al., "Phase-Resolved Functional Optical Coherence Tomography: Simultaneous Imaging of In Situ Tissue Structure, Blood Flow Velocity, Standard Deviation, Birefringence, and Stokes Vectors in Human Skin," *Optics Letters*, vol. 27, No. 19, Oct. 1, 2002, pp. 1702-1704.
- Tripathi, Renu et al., "Spectral Shaping for Non-Gaussian Source Spectra in Optical Coherence Tomography," *Optics Letters*, vol. 27, No. 6, Mar. 15, 2002, pp. 406-408.
- Yasuno, Y. et al., "Birefringence Imaging of Human Skin by Polarization-Sensitive Spectral Interferometric Optical Coherence Tomography," *Optics Letters*, vol. 27, No. 20, Oct. 15, 2002, pp. 1803-1805.
- White, Brian R. et al., "In Vivo Dynamic Human Retinal Blood Flow Imaging Using Ultra-High-Speed Spectral Domain Optical Doppler Tomography," *Optics Express*, vol. 11, No. 25, Dec. 15, 2003, pp. 3490-3497.
- De Boer, Johannes F. et al., "Improved Signal-to-Noise Ratio in Spectral-Domain Compared with Time-Domain Optical Coherence Tomography," *Optics Letters*, vol. 28, No. 21, Nov. 1, 2003, pp. 2067-2069.
- Jiao, Shuliang et al., "Optical-Fiber-Based Mueller Optical Coherence Tomography," *Optics Letters*, vol. 28, No. 14, Jul. 15, 2003, pp. 1206-1208.
- Jiao, Shuliang et al., "Contrast Mechanisms in Polarization-Sensitive Mueller-Matrix Optical Coherence Tomography and Application in Burn Imaging," *Applied Optics*, vol. 42, No. 25, Sep. 1, 2003, pp. 5191-5197.
- Moreau, Julien et al., "Full-Field Birefringence Imaging by Thermal-Light Polarization-Sensitive Optical Coherence Tomography. I. Theory," *Applied Optics*, vol. 42, No. 19, Jul. 1, 2003, pp. 3800-3810.
- Moreau, Julien et al., "Full-Field Birefringence Imaging by Thermal-Light Polarization-Sensitive Optical Coherence Tomography. II. Instrument and Results," *Applied Optics*, vol. 42, No. 19, Jul. 1, 2003, pp. 3811-3818.
- Morgan, Stephen P. et al., "Surface-Reflection Elimination in Polarization Imaging of Superficial Tissue," *Optics Letters*, vol. 28, No. 2, Jan. 15, 2003, pp. 114-116.
- Oh, Jung-Taek et al., "Polarization-Sensitive Optical Coherence Tomography for Photoelasticity Testing of Glass/Epoxy Composites," *Optics Express*, vol. 11, No. 14, Jul. 14, 2003, pp. 1669-1676.
- Park, B. Hyle et al., "Real-Time Multi-Functional Optical Coherence Tomography," *Optics Express*, vol. 11, No. 7, Apr. 7, 2003, pp. 782-793.
- Shribak, Michael et al., "Techniques for Fast and Sensitive Measurements of Two-Dimensional Birefringence Distributions," *Applied Optics*, vol. 42, No. 16, Jun. 1, 2003, pp. 3009-3017.
- Somervell, A.R.D. et al., "Direct Measurement of Fringe Amplitude and Phase Using a Heterodyne Interferometer Operating in Broad-band Light," *Elsevier, Optics Communications*, Oct. 2003.
- Stifter, D. et al., "Polarisation-Sensitive Optical Coherence Tomography for Material Characterisation and Strain-Field Mapping," *Applied Physics A 76, Materials Science & Processing*, Jan. 2003, pp. 947-951.
- Davé, Digant P. et al., "Polarization-Maintaining Fiber-Based Optical Low-Coherence Reflectometer for Characterization and Ranging of Birefringence," *Optics Letters*, vol. 28, No. 19, Oct. 1, 2003, pp. 1775-1777.
- Yang, Ying et al., "Observations of Birefringence in Tissues from Optic-Fibre-Based Optical Coherence Tomography," *Measurement Science and Technology*, Nov. 2002, pp. 41-46.
- Yun, S.H. et al., "High-Speed Optical Frequency-Domain Imaging," *Optics Express*, vol. 11, No. 22, Nov. 3, 2003, pp. 2953-2963.
- Yun, S.H. et al., "High-Speed Spectral-Domain Optical Coherence Tomography at 1.3 μm Wavelength," *Optics Express*, vol. 11, No. 26, Dec. 29, 2003, pp. 3598-3604.
- Zhang, Jun et al., "Determination of Birefringence and Absolute Optic Axis Orientation Using Polarization-Sensitive Optical Coherence Tomography with PM Fibers," *Optics Express*, vol. 11, No. 24, Dec. 1, 2003, pp. 3262-3270.
- Pircher, Michael et al., "Three Dimensional Polarization Sensitive OCT of Human Skin In Vivo," 2004, *Optical Society of America*.
- Götzinger, Erich et al., "Measurement and Imaging of Birefringent Properties of the Human Cornea with Phase-Resolved, Polarization-Sensitive Optical Coherence Tomography," *Journal of Biomedical Optics*, vol. 9, No. 1, Jan./Feb. 2004, pp. 94-102.
- Guo, Shuguang et al., "Depth-Resolved Birefringence and Differential Optical Axis Orientation Measurements with Finer-based Polarization-Sensitive Optical Coherence Tomography," *Optics Letters*, vol. 29, No. 17, Sep. 1, 2004, pp. 2025-2027.
- Huang, Xiang-Run et al., "Variation of Peripapillary Retinal Nerve Fiber Layer Birefringence in Normal Human Subjects," *Investigative Ophthalmology & Visual Science*, vol. 45, No. 9, Sep. 2004, pp. 3073-3080.
- Matcher, Stephen J. et al., "The Collagen Structure of Bovine Intervertebral Disc Studied Using Polarization-Sensitive Optical Coherence Tomography," *Physics in Medicine and Biology*, 2004, pp. 1295-1306.
- Nassif, Nader et al., "In Vivo Human Retinal Imaging by Ultrahigh-Speed Spectral Domain Optical Coherence Tomography," *Optics Letters*, vol. 29, No. 5, Mar. 1, 2004, pp. 480-482.
- Nassif, N.A. et al., "In Vivo High-Resolution Video-Rate Spectral-Domain Optical Coherence Tomography of the Human Retina and Optic Nerve," *Optics Express*, vol. 12, No. 3, Feb. 9, 2004, pp. 367-376.
- Park, B. Hyle et al., "Comment on Optical-Fiber-Based Mueller Optical Coherence Tomography," *Optics Letters*, vol. 29, No. 24, Dec. 15, 2004, pp. 2873-2874.
- Park, B. Hyle et al., "Jones Matrix Analysis for a Polarization-Sensitive Optical Coherence Tomography System Using Fiber-Optic Components," *Optics Letters*, vol. 29, No. 21, Nov. 1, 2004, pp. 2512-2514.
- Pierce, Mark C. et al., "Collagen Denaturation can be Quantified in Burned Human Skin Using Polarization-Sensitive Optical Coherence Tomography," *Elsevier, Burns*, 2004, pp. 511-517.
- Pierce, Mark C. et al., "Advances in Optical Coherence Tomography Imaging for Dermatology," *The Society for Investigative Dermatology, Inc.* 2004, pp. 458-463.
- Pierce, Mark C. et al., "Birefringence Measurements in Human Skin Using Polarization-Sensitive Optical Coherence Tomography," *Journal of Biomedical Optics*, vol. 9, No. 2, Mar./Apr. 2004, pp. 287-291.
- Cense, Barry et al., "In Vivo Birefringence and Thickness Measurements of the Human Retinal Nerve Fiber Layer Using Polarization-

(56)

References Cited

OTHER PUBLICATIONS

- Sensitive Optical Coherence Tomography," *Journal of Biomedical Optics*, vol. 9, No. 1, Jan./Feb. 2004, pp. 121-125.
- Pircher, Michael et al., "Imaging of Polarization Properties of Human Retina in Vivo with Phase Resolved Transversal PS-OCT," *Optics Express*, vol. 12, No. 24, Nov. 29, 2004 pp. 5940-5951.
- Pircher, Michael et al., "Transversal Phase Resolved Polarization Sensitive Optical Coherence Tomography," *Physics in Medicine & Biology*, 2004, pp. 1257-1263.
- Srinivas, Shyam M. et al., "Determination of Burn Depth by Polarization-Sensitive Optical Coherence Tomography," *Journal of Biomedical Optics*, vol. 9, No. 1, Jan./Feb. 2004, pp. 207-212.
- Strasswimmer, John et al., "Polarization-Sensitive Optical Coherence Tomography of Invasive Basal Cell Carcinoma," *Journal of Biomedical Optics*, vol. 9, No. 2, Mar./Apr. 2004, pp. 292-298.
- Todorović, Miloš et al., "Determination of Local Polarization Properties of Biological Samples in the Presence of Diattenuation by use of Mueller Optical Coherence Tomography," *Optics Letters*, vol. 29, No. 20, Oct. 15, 2004, pp. 2402-2404.
- Yasuno, Yoshiaki et al., "Polarization-Sensitive Complex Fourier Domain Optical Coherence Tomography for Jones Matrix Imaging of Biological Samples," *Applied Physics Letters*, vol. 85, No. 15, Oct. 11, 2004, pp. 3023-3025.
- Acioli, L. H., M. Ulman, et al. (1991). "Femtosecond Temporal Encoding in Barium-Titanate," *Optics Letters* 16(24): 1984-1986.
- Aigouy, L., A. Lahrech, et al. (1999). "Polarization effects in apertureless scanning near-field optical microscopy: an experimental study," *Optics Letters* 24(4): 187-189.
- Akiba, M., K. P. Chan, et al. (2003). "Full-field optical coherence tomography by two-dimensional heterodyne detection with a pair of CCD cameras," *Optics Letters* 28(10): 816-818.
- Akkin, T., D. P. Dave, et al. (2004). "Detection of neural activity using phase-sensitive optical low-coherence reflectometry," *Optics Express* 12(11): 2377-2386.
- Akkin, T., D. P. Dave, et al. (2003). "Surface analysis using phase sensitive optical low coherence reflectometry," *Lasers in Surgery and Medicine*: 4-4.
- Akkin, T., D. P. Dave, et al. (2003). "Imaging tissue response to electrical and photothermal stimulation with nanometer sensitivity," *Lasers in Surgery and Medicine* 33(4): 219-225.
- Akkin, T., T. E. Milner, et al. (2002). "Phase-sensitive measurement of birefringence change as an indication of neural functionality and diseases," *Lasers in Surgery and Medicine*: 6-6.
- Andretzky, P., Lindner, M.W., Herrmann, J.M., Schultz, A., Konzog, M., Kiesewetter, F., Haeusler, G. (1999). "Optical coherence tomography by 'spectral radar': Dynamic range estimation and in vivo measurements of skin," *Proceedings of SPIE—The International Society for Optical Engineering* 3567: pp. 78-87.
- Antcliff, R. J., T. J. ffytche, et al. (2000). "Optical coherence tomography of melanocytoma," *American Journal of Ophthalmology* 130(6): 845-7.
- Antcliff, R. J., M. R. Stanford, et al. (2000). "Comparison between optical coherence tomography and fundus fluorescein angiography for the detection of cystoid macular edema in patients with uveitis," *Ophthalmology* 107(3): 593-9.
- Anvari, B., T. E. Milner, et al. (1995). "Selective Cooling of Biological Tissues—Application for Thermally Mediated Therapeutic Procedures," *Physics in Medicine and Biology* 40(2): 241-252.
- Anvari, B., B. S. Tanenbaum, et al. (1995). "A Theoretical-Study of the Thermal Response of Skin to Cryogen Spray Cooling and Pulsed-Laser Irradiation—Implications for Treatment of Port-Wine Stain Birthmarks," *Physics in Medicine and Biology* 40(9): 1451-1465.
- Arend, O., M. Ruffer, et al. (2000). "Macular circulation in patients with diabetes mellitus with and without arterial hypertension," *British Journal of Ophthalmology* 84(12): 1392-1396.
- Arimoto, H. and Y. Ohtsuka (1997). "Measurements of the complex degree of spectral coherence by use of a wave-front-folded interferometer," *Optics Letters* 22(13): 958-960.
- Azzolini, C., F. Patelli, et al. (2001). "Correlation between optical coherence tomography data and biomicroscopic interpretation of idiopathic macular hole," *American Journal of Ophthalmology* 132(3): 348-55.
- Baba, T., K. Ohno-Matsui, et al. (2002). "Optical coherence tomography of choroidal neovascularization in high myopia," *Acta Ophthalmologica Scandinavica* 80(1): 82-7.
- Bail, M. A. H., Gerd; Herrmann, Juergen M.; Lindner, Michael W.; Ringler, R. (1996). "Optical coherence tomography with the 'spectral radar': fast optical analysis in volume scatterers by short-coherence interferometry," *Proc. SPIE*, 2925: p. 298-303.
- Baney, D. M. and W. V. Sorin (1993). "Extended-Range Optical Low-Coherence Reflectometry Using a Recirculating Delay Technique," *Ieee Photonics Technology Letters* 5(9): 1109-1112.
- Baney, D. M., B. Szafraniec, et al. (2002). "Coherent optical spectrum analyzer," *Ieee Photonics Technology Letters* 14(3): 355-357.
- Barakat, R. (1981). "Bilinear Constraints between Elements of the 4by4 Mueller-Jones Transfer-Matrix of Polarization Theory," *Optics Communications* 38(3): 159-161.
- Barakat, R. (1993). "Analytic Proofs of the Arago-Fresnel Laws for the Interference of Polarized-Light," *Journal of the Optical Society of America a-Optics Image Science and Vision* 10(1): 180-185.
- Barbastathis, G. and D. J. Brady (1999). "Multidimensional tomographic imaging using volume holography," *Proceedings of the Ieee* 87(12): 2098-2120.
- Bardal, S., A. Kamal, et al. (1992). "Photoinduced Birefringence in Optical Fibers—a Comparative-Study of Low-Birefringence and High-Birefringence Fibers," *Optics Letters* 17(6): 411-413.
- Barsky, S. H., S. Rosen, et al. (1980). "Nature and Evolution of Port Wine Stains—Computer-Assisted Study," *Journal of Investigative Dermatology* 74(3): 154-157.
- Barton, J. K., J. A. Izatt, et al. (1999). "Three-dimensional reconstruction of blood vessels from in vivo color Doppler optical coherence tomography images," *Dermatology* 198(4): 355-361.
- Barton, J. K., A. Rollins, et al. (2001). "Photothermal coagulation of blood vessels: a comparison of high-speed optical coherence tomography and numerical modelling," *Physics in Medicine and Biology* 46.
- Barton, J. K., A. J. Welch, et al. (1998). "Investigating pulsed dye laser-blood vessel interaction with color Doppler optical coherence tomography," *Optics Express* 3.
- Bashkansky, M., M. D. Duncan, et al. (1997). "Subsurface defect detection in ceramics by high-speed high-resolution optical coherent tomography," *Optics Letters* 22 (1): 61-63.
- Bashkansky, M. and J. Reintjes (2000). "Statistics and reduction of speckle in optical coherence tomography," *Optics Letters* 25(8): 545-547.
- Baumgartner, A., S. Dichtl, et al. (2000). "Polarization-sensitive optical coherence tomography of dental structures," *Caries Research* 34(1): 59-69.
- Baumgartner, A., C. K. Hitzengerger, et al. (2000). "Resolution-improved dual-beam and standard optical coherence tomography: a comparison," *Graefes Archive for Clinical and Experimental Ophthalmology* 238(5): 385-392.
- Baumgartner, A., C. K. Hitzengerger, et al. (1998). "Signal and resolution enhancements in dual beam optical coherence tomography of the human eye," *Journal of Biomedical Optics* 3(1): 45-54.
- Beaurepaire, E., P. Gleyzes, et al. (1998). *Optical coherence microscopy for the in-depth study of biological structures: System based on a parallel detection scheme*, Proceedings of SPIE—The International Society for Optical Engineering.
- Beaurepaire, E., L. Moreaux, et al. (1999). "Combined scanning optical coherence and two-photon-excited fluorescence microscopy," *Optics Letters* 24(14): 969-971.
- Bechara, F. G., T. Gambichler, et al. (2004). "Histomorphologic correlation with routine histology and optical coherence tomography," *Skin Research and Technology* 10 (3): 169-173.
- Bechmann, M., M. J. Thiel, et al. (2000). "Central corneal thickness determined with optical coherence tomography in various types of glaucoma. [see comments]," *British Journal of Ophthalmology* 84(11): 1233-7.

(56)

References Cited

OTHER PUBLICATIONS

- Bek, T. and M. Kandi (2000). "Quantitative anomalouscopy and optical coherence tomography scanning in central serous chorioretinopathy." *Acta Ophthalmologica Scandinavica* 78(6): 632-7.
- Benoit, A. M., K. Naoun, et al. (2001). "Linear dichroism of the retinal nerve fiber layer expressed with Mueller matrices." *Applied Optics* 40(4): 565-569.
- Bicout, D., C. Brosseau, et al. (1994). "Depolarization of Multiply Scattered Waves by Spherical Diffusers—Influence of the Size Parameter." *Physical Review E* 49(2): 1767-1770.
- Blanchot, L., M. Lebec, et al. (1997). *Low-coherence in depth microscopy for biological tissues imaging: Design of a real time control system*. Proceedings of SPIE—The International Society for Optical Engineering.
- Blumenthal, E. Z. and R. N. Weinreb (2001). "Assessment of the retinal nerve fiber layer in clinical trials of glaucoma neuroprotection. [Review] [36 refs]." *Survey of Ophthalmology* 45(Suppl 3): S305-12; discussion S332-4.
- Blumenthal, E. Z., J. M. Williams, et al. (2000). "Reproducibility of nerve fiber layer thickness measurements by use of optical coherence tomography." *Ophthalmology* 107(2): 2278-82.
- Boppart, S. A., B. E. Bouma, et al. (1996). "Imaging developing neural morphology using optical coherence tomography." *Journal of Neuroscience Methods* 70.
- Boppart, S. A., B. E. Bouma, et al. (1997). "Forward-imaging instruments for optical coherence tomography." *Optics Letters* 22.
- Boppart, S. A., B. E. Bouma, et al. (1998). "Intraoperative assessment of microsurgery with three-dimensional optical coherence tomography." *Radiology* 208: 81-86.
- Boppart, S. A., J. Herrmann, et al. (1999). "High-resolution optical coherence tomography-guided laser ablation of surgical tissue." *Journal of Surgical Research* 82(2): 275-84.
- Bouma, B. E. and J. G. Fujimoto (1996). "Compact Kerr-lens mode-locked resonators." *Optics Letters* 21.
- Bouma, B. E., L. E. Nelson, et al. (1998). "Optical coherence tomographic imaging of human tissue at 1.55 μm and 1.81 μm using Er and Tm-doped fiber sources." *Journal of Biomedical Optics* 3.
- Bouma, B. E., M. Ramaswamy-Payne, et al. (1997). "Compact resonator designs for mode-locked solid-state lasers." *Applied Physics B (Lasers and Optics)* B65.
- Bouma, B. E. and G. J. Tearney (2002). "Clinical imaging with optical coherence tomography." *Academic Radiology* 9(8): 942-953.
- Bouma, B. E., G. J. Tearney, et al. (1996). "Self-phase-modulated Kerr-lens mode-locked Cr:forsterite laser source for optical coherence tomography." *Optics Letters* 21(22): 1839.
- Bouma, B. E., G. J. Tearney, et al. (2000). "High-resolution imaging of the human esophagus and stomach in vivo using optical coherence tomography." *Gastrointestinal Endoscopy* 51(4): 467-474.
- Bouma, B. E., G. J. Tearney, et al. (2003). "Evaluation of intracoronary stenting by intravascular optical coherence tomography." *Heart* 89(3): 317-320.
- Bourquin, S., V. Monterosso, et al. (2000). "Video-rate optical low-coherence reflectometry based on a linear smart detector array." *Optics Letters* 25(2): 102-104.
- Bourquin, S., P. Seitz, et al. (2001). "Optical coherence tomography based on a two-dimensional smart detector array." *Optics Letters* 26(8): 512-514.
- Bouzd, A., M. A. G. Abushagur, et al. (1995). "Fiber-optic four-detector polarimeter." *Optics Communications* 118(3-4): 329-334.
- Bowd, C., R. N. Weinreb, et al. (2000). "The retinal nerve fiber layer thickness in ocular hypertensive, normal, and glaucomatous eyes with optical coherence tomography." *Archives of Ophthalmology* 118(1): 22-6.
- Bowd, C., L. M. Zangwill, et al. (2001). "Detecting early glaucoma by assessment of retinal nerve fiber layer thickness and visual function." *Investigative Ophthalmology & Visual Science* 42(9): 1993-2003.
- Bowd, C., L. M. Zangwill, et al. (2002). "Imaging of the optic disc and retinal nerve fiber layer: the effects of age, optic disc area, refractive error, and gender." *Journal of the Optical Society of America, A, Optics, Image Science, & Vision* 19(1): 197-207.
- Brand, S., J. M. Ponomeros, et al. (2000). "Optical coherence tomography in the gastrointestinal tract." *Endoscopy* 32(10): 796-803.
- Brezinski, M. E. and J. G. Fujimoto (1999). "Optical coherence tomography: high-resolution imaging in nontransparent tissue." *IEEE Journal of Selected Topics in Quantum Electronics* 5(4): 1185-1192.
- Brezinski, M. E., G. J. Tearney, et al. (1996). "Imaging of coronary artery microstructure (in vitro) with optical coherence tomography." *American Journal of Cardiology* 77 (1): 92-93.
- Brezinski, M. E., G. J. Tearney, et al. (1996). "Optical coherence tomography for optical biopsy—Properties and demonstration of vascular pathology." *Circulation* 93(6): 1206-1213.
- Brezinski, M. E., G. J. Tearney, et al. (1997). "Assessing atherosclerotic plaque morphology: Comparison of optical coherence tomography and high frequency intravascular ultrasound." *Heart* 77(5): 397-403.
- Brink, H. B. K. and G. J. Vanblokkland (1988). "Birefringence of the Human Foveal Area Assessed In vivo with Mueller-Matrix Ellipsometry." *Journal of the Optical Society of America a—Optics Image Science and Vision* 5(1): 49-57.
- Brosseau, C. and D. Bicout (1994). "Entropy Production in Multiple-Scattering of Light by a Spatially Random Medium." *Physical Review E* 50(6): 4997-5005.
- Burgoyne, C. F., D. E. Mercante, et al. (2002). "Change detection in regional and volumetric disc parameters using longitudinal confocal scanning laser tomography." *Ophthalmology* 109(3): 455-66.
- Candido, R. and T. J. Allen (2002). "Haemodynamics in microvascular complications in type 1 diabetes." *Diabetes-Metabolism Research and Reviews* 18(4): 286-304.
- Cense, B., T. C. Chen, et al. (2004). "Thickness and birefringence of healthy retinal nerve fiber layer tissue measured with polarization-sensitive optical coherence tomography." *Investigative Ophthalmology & Visual Science* 45(8): 2606-2612.
- Cense, B., N. Nassif, et al. (2004). "Ultrahigh-Resolution High-Speed Retinal Imaging Using Spectral-Domain Optical Coherence Tomography." *Optics Express* 12(11): 2435-2447.
- Chance, B., J. S. Leigh, et al. (1988). "Comparison of Time-Resolved and Time-Unresolved Measurements of Deoxyhemoglobin in Brain." *Proceedings of the National Academy of Sciences of the United States of America* 85(14): 4971-4975.
- Chang, E. P., D. A. Keedy, et al. (1974). "Ultrastructures of Rabbit Corneal Stroma—Mapping of Optical and Morphological Anisotropies." *Biochimica Et Biophysica Acta* 343(3): 615-626.
- Chartier, T., A. Hideur, et al. (2001). "Measurement of the elliptical birefringence of single-mode optical fibers." *Applied Optics* 40(30): 5343-5353.
- Chauhan, B. C., J. W. Blanchard, et al. (2000). "Technique for Detecting Serial Topographic Changes in the Optic Disc and Peripapillary Retina Using Scanning Laser Tomograph." *Invest Ophthalmol Vis Sci* 41: 775-782.
- Chen, Z. P., T. E. Milner, et al. (1997). "Optical Doppler tomographic imaging of fluid flow velocity in highly scattering media." *Optics Letters* 22(1): 64-66.
- Chen, Z. P., T. E. Milner, et al. (1997). "Noninvasive imaging of in vivo blood flow velocity using optical Doppler tomography." *Optics Letters* 22(14): 1119-1121.
- Chen, Z. P., Y. H. Zhao, et al. (1999). "Optical Doppler tomography." *Ieee Journal of Selected Topics in Quantum Electronics* 5(4): 1134-1142.
- Cheong, W. F., S. A. Prael, et al. (1990). "A Review of the Optical Properties of Biological Tissues." *Ieee Journal of Quantum Electronics* 26(12): 2166-2185.
- Chernikov, S. V., Y. Zhu, et al. (1997). "Supercontinuum self-Q-switched ytterbium fiber laser." *Optics Letters* 22(5): 298-300.
- Cho, S. H., B. E. Bouma, et al. (1999). "Low-repetition-rate high-peak-power Kerr-lens mode-locked Ti:Al/sub 2/O/sub 3/ laser with a multiple-pass cavity." *Optics Letters* 24(6): 417-419.
- Choma, M. A., M. V. Sarunic, et al. (2003). "Sensitivity advantage of swept source and Fourier domain optical coherence tomography." *Optics Express* 11(18): 2183-2189.

(56)

References Cited

OTHER PUBLICATIONS

- Choma, M. A., C. H. Yang, et al. (2003). "Instantaneous quadrature low-coherence interferometry with 3x3 fiber-optic couplers." *Optics Letters* 28(22): 2162-2164.
- Choplin, N. T. and D. C. Lundy (2001). "The sensitivity and specificity of scanning laser polarimetry in the detection of glaucoma in a clinical setting." *Ophthalmology* 108 (5): 899-904.
- Christens Barry, W. A., W. J. Green, et al. (1996). "Spatial mapping of polarized light transmission in the central rabbit cornea." *Experimental Eye Research* 62(6): 651-662.
- Chvapil, M., D. P. Speer, et al. (1984). "Identification of the depth of burn injury by collagen stainability." *Plastic & Reconstructive Surgery* 73(3): 438-41.
- Cioffi, G. A. (2001). "Three common assumptions about ocular blood flow and glaucoma." *Survey of Ophthalmology* 45: S325-S331.
- Coleman, A. L. (1999). "Glaucoma." *Lancet* 354(9192): 1803-10.
- Collaborative Normal-Tension Glaucoma Study Group (1998). "Comparison of Glaucomatous Progression Between Untreated Patients With Normal Tension Glaucoma and Patients with Therapeutically Reduced Intraocular Pressures." *Am J Ophthalmol* 126: 487-97.
- Collaborative Normal-Tension Glaucoma Study Group (1998). "The effectiveness of intraocular pressure reduction in the treatment of normal-tension glaucoma." *Am J Ophthalmol* 126: 498-505.
- Collaborative Normal-Tension Glaucoma Study Group (2001). "Natural History of Normal-Tension Glaucoma." *Ophthalmology* 108: 247-253.
- Colston, B. W., M. J. Everett, et al. (1998). "Imaging of hard- and soft-tissue structure in the oral cavity by optical coherence tomography." *Applied Optics* 37(16): 3582-3585.
- Colston, B. W., U. S. Sathyam, et al. (1998). "Dental OCT." *Optics Express* 3(6): 230-238.
- Congdon, N. G., D. S. Friedman, et al. (2003). "Important causes of visual impairment in the world today." *Jama-Journal of the American Medical Association* 290(15): 2057-2060.
- Cregan, R. F., B. J. Mangan, et al. (1999). "Single-mode photonic band gap guidance of light in air." *Science* 285(5433): 1537-1539.
- DalMolin, M., A. Galtarossa, et al. (1997). "Experimental investigation of linear polarization in high-birefringence single-mode fibers." *Applied Optics* 36(12): 2526-2528.
- Danielson, B. L. and C. D. Whittenberg (1987). "Guided-Wave Reflectometry with Micrometer Resolution." *Applied Optics* 26(14): 2836-2842.
- Dave, D. P. and T. E. Milner (2000). "Doppler-angle measurement in highly scattering media." *Optics Letters* 25(20): 1523-1525.
- de Boer, J. F., T. E. Milner, et al. (1998). *Two dimensional birefringence imaging in biological tissue using phase and polarization sensitive optical coherence tomography*. Trends in Optics and Photonics (TOPS): Advances in Optical Imaging and Photon Migration, Orlando, USA, Optical Society of America, Washington, DC 1998.
- de Boer, J. F., C. E. Saxer, et al. (2001). "Stable carrier generation and phase-resolved digital data processing in optical coherence tomography." *Applied Optics* 40(31): 5787-5790.
- Degroot, P. and L. Deck (1993). "3-Dimensional Imaging by Sub-Nyquist Sampling of White-Light Interferograms." *Optics Letters* 18(17): 1462-1464.
- Denk, W., J. H. Strickler, et al. (1990). "2-Photon Laser Scanning Fluorescence Microscopy." *Science* 248(4951): 73-76.
- Descour, M. R., A. H. O. Karkkainen, et al. (2002). "Toward the development of miniaturized Imaging systems for detection of precancer." *Ieee Journal of Quantum Electronics* 38(2): 122-130.
- Dettwiller, L. (1997). "Polarization state interference: A general investigation." *Pure and Applied Optics* 6(1): 41-53.
- DiCarlo, C. D., W. P. Roach, et al. (1999). "Comparison of optical coherence tomography imaging of cataracts with histopathology." *Journal of Biomedical Optics* 4.
- Ding, Z., Y. Zhao, et al. (2002). "Real-time phase-resolved optical coherence tomography and optical Doppler tomography." *Optics Express* 10(5): 236-245.
- Dobrin, P. B. (1996). "Effect of histologic preparation on the cross-sectional area of arterial rings." *Journal of Surgical Research* 61(2): 413-5.
- Donohue, D. J., B. J. Stoyanov, et al. (1995). "Numerical Modeling of the Corneas Lamellar Structure and Birefringence Properties." *Journal of the Optical Society of America a-Optics Image Science and Vision* 12(7): 1425-1438.
- Doornbos, R. M. P., R. Lang, et al. (1999). "The determination of in vivo human tissue optical properties and absolute chromophore concentrations using spatially resolved steady-state diffuse reflectance spectroscopy." *Physics in Medicine and Biology* 44(4): 967-981.
- Drexler, W., A. Baumgartner, et al. (1997). "Biometric investigation of changes in the anterior eye segment during accommodation." *Vision Research* 37(19): 2789-2800.
- Drexler, W., A. Baumgartner, et al. (1997). "Submicrometer precision biometry of the anterior segment of the human eye." *Investigative Ophthalmology & Visual Science* 38(7): 1304-1313.
- Drexler, W., A. Baumgartner, et al. (1998). "Dual beam optical coherence tomography: signal identification for ophthalmologic diagnosis." *Journal of Biomedical Optics* 3 (1): 55-65.
- Drexler, W., O. Findl, et al. (1998). "Partial coherence interferometry: A novel approach to biometry in cataract surgery." *American Journal of Ophthalmology* 126(4): 524-534.
- Drexler, W., O. Findl, et al. (1997). "Clinical feasibility of dual beam optical coherence topography and tomography for ophthalmologic diagnosis." *Investigative Ophthalmology & Visual Science* 38(4): 1038-1038.
- Drexler, W., C. K. Hitzenberger, et al. (1998). "Investigation of dispersion effects in ocular media by multiple wavelength partial coherence interferometry." *Experimental Eye Research* 66(1): 25-33.
- Drexler, W., C. K. Hitzenberger, et al. (1996). "(Sub)micrometer precision biometry of the human eye by optical coherence tomography and topography." *Investigative Ophthalmology & Visual Science* 37(3): 4374-4374.
- Drexler, W., C. K. Hitzenberger, et al. (1995). "Measurement of the Thickness of Fundus Layers by Partial Coherence Tomography." *Optical Engineering* 34(3): 701-710.
- Drexler, W., U. Morgner, et al. (2001). "Ultrahigh-resolution ophthalmic optical coherence tomography." *Nature Medicine* 7(4): 502-507.
- Drexler, W., U. Morgner, et al. (2001). "Ultrahigh-resolution ophthalmic optical coherence tomography. [erratum appears in Nat Med May 2001;7(5):636.]" *Nature Medicine* 7(4): 502-7.
- Drexler, W., H. Sattmann, et al. (2003). "Enhanced visualization of macular pathology with the use of ultrahigh-resolution optical coherence tomography." *Archives of Ophthalmology* 121(5): 695-706.
- Drexler, W., D. Stamper, et al. (2001). "Correlation of collagen organization with polarization sensitive imaging of in vitro cartilage: implications for osteoarthritis." *Journal of Rheumatology* 28(6): 1311-8.
- Droog, E. J., W. Steenberger, et al. (2001). "Measurement of depth of burns by laser Doppler perfusion imaging." *Burns* 27(6): 561-8.
- Dubois, A., K. Grieve, et al. (2004). "Ultrahigh-resolution full-field optical coherence tomography." *Applied Optics* 43(14): 2874-2883.
- Dubois, A., L. Vabre, et al. (2002). "High-resolution full-field optical coherence tomography with a Linnik microscope." *Applied Optics* 41(4): 805-812.
- Ducros, M., M. Laubscher, et al. (2002). "Parallel optical coherence tomography in scattering samples using a two-dimensional smart-pixel detector array." *Optics Communications* 202(1-3): 29-35.
- Ducros, M. G., J. D. Marsack, et al. (2001). "Primate retina imaging with polarization-sensitive optical coherence tomography." *Journal of the Optical Society of America a-Optics Image Science and Vision* 18(12): 2945-2956.
- Duncan, A., J. H. Meek, et al. (1995). "Optical Pathlength Measurements on Adult Head, Calf and Forearm and the Head of the Newborn-Infant Using Phase-Resolved Optical Spectroscopy." *Physics in Medicine and Biology* 40(2): 295-304.
- Eigensee, A., G. Haeusler, et al. (1996). "New Method of short-coherence interferometry in human skin (in vivo) and in solid volume scatterers." *Proceedings of SPIE—The International Society for Optical Engineering* 2925: 169-178.

(56)

References Cited

OTHER PUBLICATIONS

- Eisebeiss, W., J. Marotz, et al. (1999). "Reflection-optical multispectral imaging method for objective determination of burn depth." *Burns* 25(8): 697-704.
- Elbaum, M., M. King, et al. (1972). "Wavelength-Diversity Technique for Reduction of Speckle Size." *Journal of the Optical Society of America* 62(5): 732-8.
- Ervin, J. C., H. G. Lemij, et al. (2002). "Clinician change detection viewing longitudinal stereophotographs compared to confocal scanning laser tomography in the LSU Experimental Glaucoma (LEG) Study." *Ophthalmology* 109(3): 467-81.
- Essenpreis, M., C. E. Elwell, et al. (1993). "Spectral Dependence of Temporal Point Spread Functions in Human Tissues." *Applied Optics* 32(4): 418-425.
- Eun, H. C. (1995). "Evaluation of skin blood flow by laser Doppler flowmetry. [Review] [151 refs]." *Clinics in Dermatology* 13(4): 337-47.
- Evans, J. A., J. M. Poneros, et al. (2004). "Application of a histopathologic scoring system to optical coherence tomography (OCT) images to identify high-grade dysplasia in Barrett's esophagus." *Gastroenterology* 126(4): A51-A51.
- Feldchtein, F. I., G. V. Gelikonov, et al. (1998). "In vivo OCT imaging of hard and soft tissue of the oral cavity." *Optics Express* 3(6): 239-250.
- Feldchtein, F. I., G. V. Gelikonov, et al. (1998). "Endoscopic applications of optical coherence tomography." *Optics Express* 3(6): 250-270.
- Fercher, A. F., W. Drexler, et al. (1997). "Optical ocular tomography." *Neuro-Ophthalmology* 18(2): 39-49.
- Fercher, A. F., W. Drexler, et al. (1994). *Measurement of optical distances by optical spectrum modulation*. Proceedings of SPIE—The International Society for Optical Engineering.
- Fercher, A. F., W. Drexler, et al. (2003). "Optical coherence tomography—principles and application." *Reports on Progress in Physics* 66(2): 239-303.
- Fercher, A. F., C. K. Hitzenberger, et al. (1991). "Measurement of Intraocular Optical Distances Using Partially Coherent Laser-Light." *Journal of Modern Optics* 38(7): 1327-1333.
- Fercher, A. F., C. K. Hitzenberger, et al. (1996). *Ocular partial coherence interferometry*. Proceedings of SPIE—The International Society for Optical Engineering.
- Fercher, A. F., C. K. Hitzenberger, et al. (1993). "In-Vivo Optical Coherence Tomography." *American Journal of Ophthalmology* 116(1): 113-115.
- Fercher, A. F., C. K. Hitzenberger, et al. (1994). *In-vivo dual-beam optical coherence tomography*. Proceedings of SPIE—The International Society for Optical Engineering.
- Fercher, A. F., C. K. Hitzenberger, et al. (1995). "Measurement of Intraocular Distances by Backscattering Spectral Interferometry." *Optics Communications* 117(1-2): 43-48.
- Fercher, A. F., C. K. Hitzenberger, et al. (2000). "A thermal light source technique for optical coherence tomography." *Optics Communications* 185(1-3): 57-64.
- Fercher, A. F., C. K. Hitzenberger, et al. (2001). "Numerical dispersion compensation for Partial Coherence Interferometry and Optical Coherence Tomography." *Optics Express* 9(12): 610-615.
- Fercher, A. F., C. K. Hitzenberger, et al. (2002). "Dispersion compensation for optical coherence tomography depth-scan signals by a numerical technique." *Optics Communications* 204(1-6): 67-74.
- Fercher, A. F., H. C. Li, et al. (1993). "Slit Lamp Laser-Doppler Interferometer." *Lasers in Surgery and Medicine* 13(4): 447-452.
- Fercher, A. F., K. Mengedoh, et al. (1988). "Eye-Length Measurement by Interferometry with Partially Coherent-Light." *Optics Letters* 13(3): 186-188.
- Ferro, P., M. Haelterman, et al. (1991). "All-Optical Polarization Switch with Long-Low Birefringence Fiber." *Electronics Letters* 27(16): 1407-1408.
- Fetterman, M. R., D. Goswami, et al. (1998). "Ultrafast pulse shaping: amplification and characterization." *Optics Express* 3(10): 366-375.
- Findl, O., W. Drexler, et al. (2001). "Improved prediction of intraocular lens power using partial coherence interferometry." *Journal of Cataract and Refractive Surgery* 27(6): 861-867.
- Fork, R. L., C. H. B. Cruz, et al. (1987). "Compression of Optical Pulses to 6 Femtoseconds by Using Cubic Phase Compensation." *Optics Letters* 12(7): 483-485.
- Foschini, G. J. and C. D. Poole (1991). "Statistical-Theory of Polarization Dispersion in Single-Mode Fibers." *Journal of Lightwave Technology* 9(11): 1439-1456.
- Francia, C., F. Bruyere, et al. (1998). "PMD second-order effects on pulse propagation in single-mode optical fibers." *Ieee Photonics Technology Letters* 10(12): 1739-1741.
- Fried, D., R. E. Glena, et al. (1995). "Nature of Light-Scattering in Dental Enamel and Dentin at Visible and near-Infrared Wavelengths." *Applied Optics* 34(7): 1278-1285.
- Fujimoto, J. G., M. E. Brezinski, et al. (1995). "Optical Biopsy and Imaging Using Optical Coherence Tomography." *Nature Medicine* 1(9): 970-972.
- Fukasawa, A. and H. Iijima (2002). "Optical coherence tomography of choroidal osteoma." *American Journal of Ophthalmology* 133(3): 419-21.
- Fymat, A. L. (1981). "High-Resolution Interferometric Spectrophotopolarimetry." *Optical Engineering* 20(1): 25-30.
- Galtarossa, A., L. Palmieri, et al. (2000). "Statistical characterization of fiber random birefringence." *Optics Letters* 25(18): 1322-1324.
- Galtarossa, A., L. Palmieri, et al. (2000). "Measurements of beat length and perturbation length in long single-mode fibers." *Optics Letters* 25(6): 384-386.
- Gandjbakhche, A. H., P. Mills, et al. (1994). "Light-Scattering Technique for the Study of Orientation and Deformation of Red-Blood-Cells in a Concentrated Suspension." *Applied Optics* 33(6): 1070-1078.
- Garcia, N. and M. Nieto-Vesperinas (2002). "Left-handed materials do not make a perfect lens." *Physical Review Letters* 88(20).
- Gelikonov, V. M., G. V. Gelikonov, et al. (1995). "Coherent Optical Tomography of Microscopic Inhomogeneities in Biological Tissues." *Jep Letters* 61(2): 158-162.
- George, N. and A. Jain (1973). "Speckle Reduction Using Multiple Tones of Illumination." *Applied Optics* 12(6): 1202-1212.
- Gibson, G. N., R. Klank, et al. (1996). "Electro-optically cavity-dumped ultrashort-pulse Ti:sapphire oscillator." *Optics Letters* 21(14): 1055.
- Gil, J. J. (2000). "Characteristic properties of Mueller matrices." *Journal of the Optical Society of America a-Optics Image Science and Vision* 17(2): 328-334.
- Gil, J. J. and E. Bernabeu (1987). "Obtainment of the Polarizing and Retardation Parameters of a Nondepolarizing Optical-System from the Polar Decomposition of Its Mueller Matrix." *Optik* 76(2): 67-71.
- Gladkova, N. D., G. A. Petrova, et al. (2000). "In vivo optical coherence tomography imaging of human skin: norm and pathology." *Skin Research and Technology* 6(1): 6-16.
- Glaessl, A., A. G. Schreyer, et al. (2001). "Laser surgical planning with magnetic resonance imaging-based 3-dimensional reconstructions for intralesional Nd:YAG laser therapy of a venous malformation of the neck." *Archives of Dermatology* 137(10): 1331-1335.
- Gloesmann, M., B. Hermann, et al. (2003). "Histologic correlation of pig retina radial stratification with ultrahigh-resolution optical coherence tomography." *Investigative Ophthalmology & Visual Science* 44(4): 1696-1703.
- Goldberg, L. and D. Mehuys (1994). "High-Power Superluminescent Diode Source." *Electronics Letters* 30(20): 1682-1684.
- Goldsmith, J. A., Y. Li, et al. (2005). "Anterior chamber width measurement by high speed optical coherence tomography." *Ophthalmology* 112(2): 238-244.
- Goldstein, L. E., J. A. Muffat, et al. (2003). "Cytosolic beta-amyloid deposition and supranuclear cataracts in lenses from people with Alzheimer's disease." *Lancet* 361(9365): 1258-1265.
- Golubovic, B., B. E. Bouma, et al. (1996). "Thin crystal, room-temperature Cr³⁺/sup 4 +/forstefite laser using near-infrared pumping." *Optics Letters* 21(24): 1993-1995.
- Gonzalez, S. and Z. Tannous (2002). "Real-time, in vivo confocal reflectance microscopy of basal cell carcinoma." *Journal of the American Academy of Dermatology* 47(6): 869-874.

(56)

References Cited

OTHER PUBLICATIONS

- Gordon, M. O. and M. A. Kass (1999). "The Ocular Hypertension Treatment Study: design and baseline description of the participants." *Archives of Ophthalmology* 117(5): 573-83.
- Grayson, T. P., J. R. Torgerson, et al. (1994). "Observation of a Nonlocal Pancharatnam Phase-Shift in the Process of Induced Coherence without Induced Emission." *Physical Review A* 49(1): 626-628.
- Greaney, M. J., D. C. Hoffman, et al. (2002). "Comparison of optic nerve imaging methods to distinguish normal eyes from those with glaucoma." *Investigative Ophthalmology & Visual Science* 43(1): 140-5.
- Greenfield, D. S., H. Bagga, et al. (2003). "Macular thickness changes in glaucomatous optic neuropathy detected using optical coherence tomography." *Archives of Ophthalmology* 121(1): 41-46.
- Greenfield, D. S., R. W. Knighton, et al. (2000). "Effect of corneal polarization axis on assessment of retinal nerve fiber layer thickness by scanning laser polarimetry." *American Journal of Ophthalmology* 129(6): 715-722.
- Griffin, R. A., D. D. Sampson, et al. (1995). "Coherence Coding for Photonic Code-Division Multiple-Access Networks." *Journal of Lightwave Technology* 13(9): 1826-1837.
- Guedes, V., J. S. Schuman, et al. (2003). "Optical coherence tomography measurement of macular and nerve fiber layer thickness in normal and glaucomatous human eyes." *Ophthalmology* 110(1): 177-189.
- Gueugniaud, P. Y., H. Carsin, et al. (2000). "Current advances in the initial management of major thermal burns. [Review] [76 refs]." *Intensive Care Medicine* 26(7): 848-56.
- Guido, S. and R. T. Tranquillo (1993). "A Methodology for the Systematic and Quantitative Study of Cell Contact Guidance in Oriented Collagen Gels—Correlation of Fibroblast Orientation and Gel Birefringence." *Journal of Cell Science* 105: 317-331.
- Gurses-Ozden, R., H. Ishikawa, et al. (1999). "Increasing sampling density improves reproducibility of optical coherence tomography measurements." *Journal of Glaucoma* 8(4): 238-41.
- Guzzi, R. (1998). "Scattering Theory from Homogeneous and Coated Spheres." 1-11.
- Haberland, U. B., Vladimir; Schmitt, Hans J. (1996). "Optical coherent tomography of scattering media using electrically tunable near-infrared semiconductor laser." *Applied Optics* Draft Copy.
- Haberland, U. R., Walter; Blazek, Vladimir; Schmitt, Hans J. (1995). "Investigation of highly scattering media using near-infrared continuous wave tunable semiconductor laser." *Proc. SPIE*, 2389: 503-512.
- Hale, G. M. and M. R. Querry (1973). "Optical-Constants of Water in 200-Nm to 200-Mum Wavelength Region." *Applied Optics* 12(3): 555-563.
- Hammer, D. X., R. D. Ferguson, et al. (2002). "Image stabilization for scanning laser ophthalmoscopy." *Optics Express* 10(26): 1542.
- Hara, T., Y. Ooi, et al. (1989). "Transfer Characteristics of the Microchannel Spatial Light-Modulator." *Applied Optics* 28(22): 4781-4786.
- Harland, C. C., S. G. Kale, et al. (2000). "Differentiation of common benign pigmented skin lesions from melanoma by high-resolution ultrasound." *British Journal of Dermatology* 143(2): 281-289.
- Hartl, I., X. D. Li, et al. (2001). "Ultrahigh-resolution optical coherence tomography using continuum generation in an air-silica microstructure optical fiber." *Optics Letters* 26(9): 608-610.
- Hassenstein, A., A. A. Bialasiewicz, et al. (2000). "Optical coherence tomography in uveitis patients." *American Journal of Ophthalmology* 130(5): 669-70.
- Hattenhauer, M. G., D. H. Johnson, et al. (1998). "The probability of blindness from open-angle glaucoma. [see comments]." *Ophthalmology* 105(11): 2099-104.
- Hausler, G., J. M. Herrmann, et al. (1996). "Observation of light propagation in volume scatterers with 10(11)-fold slow motion." *Optics Letters* 21(14): 1087-1089.
- Hazebroek, H. F. and A. A. Holscher (1973). "Interferometric Ellipsometry." *Journal of Physics E-Scientific Instruments* 6(9): 822-826.
- Hazebroek, H. F. and W. M. Visser (1983). "Automated Laser Interferometric Ellipsometry and Precision Reflectometry." *Journal of Physics E-Scientific Instruments* 16(7): 654-661.
- He, Z. Y., N. Mukohzaka, et al. (1997). "Selective image extraction by synthesis of the coherence function using two-dimensional optical lock-in amplifier with microchannel spatial light modulator." *Ieee Photonics Technology Letters* 9(4): 514-516.
- Hee, M. R., J. A. Izatt, et al. (1993). "Femtosecond Transillumination Optical Coherence Tomography." *Optics Letters* 18(12): 950-952.
- Hee, M. R., J. A. Izatt, et al. (1995). "Optical coherence tomography of the human retina." *Archives of Ophthalmology* 113(3): 325-32.
- Hee, M. R., C. A. Puliafito, et al. (1998). "Topography of diabetic macular edema with optical coherence tomography." *Ophthalmology* 105(2): 360-70.
- Hee, M. R., C. A. Puliafito, et al. (1995). "Quantitative assessment of macular edema with optical coherence tomography." *Archives of Ophthalmology* 113(8): 1019-29.
- Hellmuth, T. and M. Welle (1998). "Simultaneous measurement of dispersion, spectrum, and distance with a fourier transform spectrometer." *Journal of Biomedical Optics* 3(1): 7-11.
- Hemenger, R. P. (1989). "Birefringence of a medium of tenuous parallel cylinders." *Applied Optics* 28(18): 4030-4034.
- Henry, M. (1981). "Fresnel-Arago Laws for Interference in Polarized-Light—Demonstration Experiment." *American Journal of Physics* 49(7): 690-691.
- Herz, P. R., Y. Chen, et al. (2004). "Micromotor endoscope catheter for in vivo, ultrahigh-resolution optical coherence tomography." *Optics Letters* 29(19): 2261-2263.
- Hirakawa, H., H. Iijima, et al. (1999). "Optical coherence tomography of cystoid macular edema associated with retinitis pigmentosa." *American Journal of Ophthalmology* 128(2): 185-91.
- Hitzenberger, C. K., A. Baumgartner, et al. (1994). "Interferometric Measurement of Corneal Thickness with Micrometer Precision." *American Journal of Ophthalmology* 118(4): 468-476.
- Hitzenberger, C. K., A. Baumgartner, et al. (1999). "Dispersion effects in partial coherence interferometry: Implications for intraocular ranging." *Journal of Biomedical Optics* 4(1): 144-151.
- Hitzenberger, C. K., A. Baumgartner, et al. (1998). "Dispersion induced multiple signal peak splitting in partial coherence interferometry." *Optics Communications* 154(4): 179-185.
- Hitzenberger, C. K., M. Danner, et al. (1999). "Measurement of the spatial coherence of superluminescent diodes." *Journal of Modern Optics* 46(12): 1763-1774.
- Hitzenberger, C. K. and A. F. Fercher (1999). "Differential phase contrast in optical coherence tomography." *Optics Letters* 24(9): 622-624.
- Hitzenberger, C. K., M. Sticker, et al. (2001). "Differential phase measurements in low-coherence interferometry without 2 pi ambiguity." *Optics Letters* 26(23): 1864-1866.
- Hoeling, B. M., A. D. Fernandez, et al. (2000). "An optical coherence microscopy for 3-dimensional imaging in developmental biology." *Optics Express* 6(7): 136-146.
- Hoerauf, H., C. Scholz, et al. (2002). "Transscleral optical coherence tomography: a new imaging method for the anterior segment of the eye." *Archives of Ophthalmology* 120(6): 816-9.
- Hoffmann, K., M. Happe, et al. (1998). "Optical coherence tomography (OCT) in dermatology." *Journal of Investigative Dermatology* 110(4): 583-583.
- Hoh, S. T., D. S. Greenfield, et al. (2000). "Optical coherence tomography and scanning laser polarimetry in normal, ocular hypertensive, and glaucomatous eyes." *American Journal of Ophthalmology* 129(2): 129-35.
- Hohenleutner, U., M. Hilbert, et al. (1995). "Epidermal Damage and Limited Coagulation Depth with the Flashlamp-Pumped Pulsed Dye-Laser—a Histochemical-Study." *Journal of Investigative Dermatology* 104(5): 798-802.
- Holland, A. J. A., H. C. O. Martin, et al. (2002). "Laser Doppler imaging prediction of burn wound outcome in children." *Burns* 28(1): 11-17.
- Hotate, K. and T. Okugawa (1994). "Optical Information-Processing by Synthesis of the Coherence Function." *Journal of Lightwave Technology* 12(7): 1247-1255.

(56)

References Cited

OTHER PUBLICATIONS

- Hourdakis, C. J. and A. Perris (1995). "A Monte-Carlo Estimation of Tissue Optical-Properties for Use in Laser Dosimetry." *Physics in Medicine and Biology* 40(3): 351-364.
- Hu, Z., F. Li, et al. (2000). "Wavelength-tunable narrow-linewidth semiconductor fiber-ring laser." *IEEE Photonics Technology Letters* 12(8): 977-979.
- Huang, F., W. Yang, et al. (2001). "Quadrature spectral interferometric detection and pulse shaping." *Optics Letters* 26(6): 382-384.
- Huang, X. R. and R. W. Knighton (2002). "Linear birefringence of the retinal nerve fiber layer measured in vitro with a multispectral imaging micropolarimeter." *Journal of Biomedical Optics* 7(2): 199-204.
- Huber, R., M. Wojtkowski, et al. (2005). "Amplified, frequency swept lasers for frequency domain reflectometry and OCT imaging: design and scaling principles." *Optics Express* 13(9): 3513-3528.
- Hunter, D. G., J. C. Sandruck, et al. (1999). "Mathematical modeling of retinal birefringence scanning." *Journal of the Optical Society of America a-Optics Image Science and Vision* 16(9): 2103-2111.
- Hurwitz, H. H. and R. C. Jones (1941). "A new calculus for the treatment of optical systems II. Proof of three general equivalence theorems." *Journal of the Optical Society of America* 31(7): 493-499.
- Huttner, B., C. De Barros, et al. (1999). "Polarization-induced pulse spreading in birefringent optical fibers with zero differential group delay." *Optics Letters* 24(6): 370-372.
- Huttner, B., B. Gisin, et al. (1999). "Distributed PMD measurement with a polarization-OTDR in optical fibers." *Journal of Lightwave Technology* 17(10): 1843-1848.
- Huttner, B., J. Reecht, et al. (1998). "Local birefringence measurements in single-mode fibers with coherent optical frequency-domain reflectometry." *Ieee Photonics Technology Letters* 10(10): 1458-1460.
- Hyde, S. C. W., N. P. Barry, et al. (1995). "Sub-100-Mu-M Depth-Resolved Holographic Imaging through Scattering Media in the near-Infrared." *Optics Letters* 20(22): 2330-2332.
- Hyde, S. C. W., N. P. Barry, et al. (1995). "Depth-Resolved Holographic Imaging through Scattering Media by Photorefractive." *Optics Letters* 20(11): 1331-1333.
- Ifimia, N. V., B. E. Bouma, et al. (2004). "Adaptive ranging for optical coherence tomography." *Optics Express* 12(17): 4025-4034.
- Iida, T., N. Hagimura, et al. (2000). "Evaluation of central serous chorioretinopathy with optical coherence tomography." *American Journal of Ophthalmology* 129(1): 16-20.
- Imai, M., H. Iijima, et al. (2001). "Optical coherence tomography of tractional macular elevations in eyes with proliferative diabetic retinopathy. [republished in Am J Ophthalmol. Sep. 2001;132(3):458-61 ; 11530091.]" *American Journal of Ophthalmology* 132(1): 81-4.
- Indebetouw, G. and P. Klysubun (2000). "Imaging through scattering media with depth resolution by use of low-coherence gating in spatiotemporal digital holography." *Optics Letters* 25(4): 212-214.
- Ip, M. S., B. J. Baker, et al. (2002). "Anatomical outcomes of surgery for idiopathic macular hole as determined by optical coherence tomography." *Archives of Ophthalmology* 120(1): 29-35.
- Ismail, R., V. Tanner, et al. (2002). "Optical coherence tomography imaging of severe commotio retinae and associated macular hole." *British Journal of Ophthalmology* 86(4): 473-4.
- Izatt, J. A., M. R. Hee, et al. (1994). "Optical Coherence Microscopy in Scattering Media." *Optics Letters* 19(8): 590-592.
- Izatt, J. A., M. R. Hee, et al. (1994). "Micrometer-scale resolution imaging of the anterior eye in vivo with optical coherence tomography." *Archives of Ophthalmology* 112 (12): 1584-9.
- Izatt, J. A., M. D. Kulkarni, et al. (1997). "In vivo bidirectional color Doppler flow imaging of picoliter blood volumes using optical coherence tomography." *Optics Letters* 22(18): 1439-1441.
- Izatt, J. A., M. D. Kulkarni, et al. (1996). "Optical coherence tomography and microscopy in gastrointestinal tissues." *IEEE Journal of Selected Topics in Quantum Electronics* 2(4): 1017.
- Jacques, S. L., J. S. Nelson, et al. (1993). "Pulsed Photothermal Radiometry of Port-Wine-Stain Lesions." *Applied Optics* 32(13): 2439-2446.
- Jacques, S. L., J. R. Roman, et al. (2000). "Imaging superficial tissues with polarized light." *Lasers in Surgery and Medicine* 26(2): 119-129.
- Jang, I. K., B. E. Bouma, et al. (2002). "Visualization of coronary atherosclerotic plaques in patients using optical coherence tomography: Comparison with intravascular ultrasound." *Journal of the American College of Cardiology* 39(4): 604-609.
- Jang, I. K., B. D. MacNeill, et al. (2002). "In-vivo characterization of coronary plaques in patients with ST elevation acute myocardial infarction using optical coherence tomography (OCT)." *Circulation* 106(19): 698-698 3440 Suppl. S.
- Jang, I. K., G. J. Tearney, et al. (2000). "Comparison of optical coherence tomography and intravascular ultrasound for detection of coronary plaques with large lipid-core in living patients." *Circulation* 102(18): 509-509.
- Jeng, J. C., A. Bridgeman, et al. (2003). "Laser Doppler imaging determines need for excision and grafting in advance of clinical judgment: a prospective blinded trial." *Burns* 29(7): 665-670.
- Jesser, C. A., S. A. Boppart, et al. (1999). "High resolution imaging of transitional cell carcinoma with optical coherence tomography: feasibility for the evaluation of bladder pathology." *British Journal of Radiology* 72: 1170-1176.
- Johnson, C. A., J. L. Keltner, et al. (2002). "Baseline visual field characteristics in the ocular hypertension treatment study." *Ophthalmology* 109(3): 432-7.
- Jones, R. C. (1941). "A new calculus for the treatment of optical systems III. The Sohncke theory of optical activity." *Journal of the Optical Society of America* 31 (7): 500-503.
- Jones, R. C. (1941). "A new calculus for the treatment of optical systems I. Description and discussion of the calculus." *Journal of the Optical Society of America* 31(7): 488-493.
- Jones, R. C. (1942). "A new calculus for the treatment of optical systems. IV." *Journal of the Optical Society of America* 32(8): 486-493.
- Jones, R. C. (1947). "A New Calculus for the Treatment of Optical Systems .6. Experimental Determination of the Matrix." *Journal of the Optical Society of America* 37(2): 110-112.
- Jones, R. C. (1947). "A New Calculus for the Treatment of Optical Systems .5. A More General Formulation, and Description of Another Calculus." *Journal of the Optical Society of America* 37(2): 107-110.
- Jones, R. C. (1948). "A New Calculus for the Treatment of Optical Systems .7. Properties of the N-Matrices." *Journal of the Optical Society of America* 38(8): 671-685.
- Jones, R. C. (1956). "New Calculus for the Treatment of Optical Systems .8. Electromagnetic Theory." *Journal of the Optical Society of America* 46(2): 126-131.
- Jopson, R. M., L. E. Nelson, et al. (1999). "Measurement of second-order polarization-mode dispersion vectors in optical fibers." *Ieee Photonics Technology Letters* 11 (9): 1153-1155.
- Jost, B. M., A. V. Sergienko, et al. (1998). "Spatial correlations of spontaneously down-converted photon pairs detected with a single-photon-sensitive CCD camera." *Optics Express* 3(2): 81-88.
- Kaplan, B., E. Compain, et al. (2000). "Phase-modulated Mueller ellipsometry characterization of scattering by latex sphere suspensions." *Applied Optics* 39 (4): 629-636.
- Kass, M. A., D. K. Heuer, et al. (2002). "The Ocular Hypertension Treatment Study: a randomized trial determines that topical ocular hypotensive medication delays or prevents the onset of primary open-angle glaucoma." *Archives of Ophthalmology* 120(6): 701-13; discussion 829-30.
- Kasuga, Y., J. Arai, et al. (2000). "Optical coherence tomography to confirm early closure of macular holes." *American Journal of Ophthalmology* 130(5): 675-6.
- Kaufman, T., S. N. Lusthaus, et al. (1990). "Deep Partial Skin Thickness Burns—a Reproducible Animal-Model to Study Burn Wound-Healing." *Burns* 16(1): 13-16.

(56)

References Cited

OTHER PUBLICATIONS

- Kemp, N. J., J. Park, et al. (2005). "High-sensitivity determination of birefringence in turbid media with enhanced polarization-sensitive optical coherence tomography." *Journal of the Optical Society of America a-Optics Image Science and Vision* 22(3): 552-560.
- Kerrigan-Baumrind, L. A., H. A. Quigley, et al. (2000). "Number of ganglion cells in glaucoma eyes compared with threshold visual field tests in the same persons." *Investigative Ophthalmology & Visual Science* 41(3): 741-8.
- Kesen, M. R., G. L. Spaeth, et al. (2002). "The Heidelberg Retina Tomograph vs clinical impression in the diagnosis of glaucoma." *American Journal of Ophthalmology* 133(5): 613-6.
- Kienle, A. and R. Hibst (1995). "A New Optimal Wavelength for Treatment of Port-Wine Stains." *Physics in Medicine and Biology* 40(10): 1559-1576.
- Kienle, A., L. Lilge, et al. (1996). "Spatially resolved absolute diffuse reflectance measurements for noninvasive determination of the optical scattering and absorption coefficients of biological tissue." *Applied Optics* 35(13): 2304-2314.
- Kim, B. Y. and S. S. Choi (1981). "Analysis and Measurement of Birefringence in Single-Mode Fibers Using the Backscattering Method." *Optics Letters* 6(11): 578-580.
- Kimel, S., L. O. Svaasand, et al. (1994). "Differential Vascular-Response to Laser Photothermolysis." *Journal of Investigative Dermatology* 103(5): 693-700.
- Kloppenborg, F. W. H., G. Beerthuis, et al. (2001). "Perfusion of burn wounds assessed by Laser Doppler Imaging is related to burn depth and healing time." *Burns* 27(4): 359-363.
- Knighton, R. W. and X. R. Huang (2002). "Analytical methods for scanning laser polarimetry." *Optics Express* 10(21): 1179-1189.
- Knighton, R. W., X. R. Huang, et al. (2002). "Analytical model of scanning laser polarimetry for retinal nerve fiber layer assessment." *Investigative Ophthalmology & Visual Science* 43(2): 383-392.
- Knuettel, A. R. S., Joseph M.: Shay, M.; Knutson, Jay R. (1994). "Stationary low-coherence light imaging and spectroscopy using a CCD camera." *Proc. SPIE*, vol. 2135: p. 239-250.
- Knuttel, A. and M. Boehlau-Godau (2000). "Spatially confined and temporally resolved refractive index and scattering evaluation in human skin performed with optical coherence tomography." *Journal of Biomedical Optics* 5(1): 83-92.
- Knuttel, A. and J. M. Schmitt (1993). "Stationary Depth-Profiling Reflectometer Based on Low-Coherence Interferometry." *Optics Communications* 102(3-4): 193-198.
- Knuttel, A., J. M. Schmitt, et al. (1994). "Low-Coherence Reflectometry for Stationary Lateral and Depth Profiling with Acoustooptic Deflectors and a Ccd Camera." *Optics Letters* 19(4): 302-304.
- Kobayashi, M., H. Hanafusa, et al. (1991). "Polarization-Independent Interferometric Optical-Time-Domain Reflectometer." *Journal of Lightwave Technology* 9(5): 623-628.
- Kolios, M. C., M. D. Sherar, et al. (1995). "Large Blood-Vessel Cooling in Heated Tissues—a Numerical Study." *Physics in Medicine and Biology* 40(4): 477-494.
- Koozekanani, D., K. Boyer, et al. (2001). "Retinal thickness measurements from optical coherence tomography using a Markov boundary model." *Ieee Transactions on Medical Imaging* 20(9): 900-916.
- Kop, R. H. J. and R. Sprk (1995). "Phase-sensitive interferometry with ultrashort optical pulses." *Review of Scientific Instruments* 66(12): 5459-5463.
- Kramer, R. Z., J. Bella, et al. (1999). "Sequence dependent conformational variations of collagen triple-helical structure." *Nature Structural Biology* 6(5): 454-7.
- Kulkarni, M. D., T. G. van Leeuwen, et al. (1998). "Velocity-estimation accuracy and frame-rate limitations in color Doppler optical coherence tomography." *Optics Letters* 23(13): 1057-1059.
- Kwon, Y. H., C. S. Kim, et al. (2001). "Rate of visual field loss and long-term visual outcome in primary open-angle glaucoma." *American Journal of Ophthalmology* 132(1): 47-56.
- Kwong, K. F., D. Yankelevich, et al. (1993). "400-Hz Mechanical Scanning Optical Delay-Line." *Optics Letters* 18(7): 558-560.
- Landers, J., I. Goldberg, et al. (2002). "Analysis of risk factors that may be associated with progression from ocular hypertension to primary open angle glaucoma." *Clin Experiment Ophthalmology* 30(4): 242-7.
- Laszlo, A. and A. Venetianer (1998). Heat resistance in mammalian cells: Lessons and challenges. *Stress of Life*. 851: 169-178.
- Laszlo, A. and A. Venetianer (1998). "Heat resistance in mammalian cells: lessons and challenges. [Review] [52 refs]." *Annals of the New York Academy of Sciences* 851: 169-78.
- Laufer, J., R. Simpson, et al. (1998). "Effect of temperature on the optical properties of ex vivo human dermis and subdermis." *Physics in Medicine and Biology* 43(9): 2479-2489.
- Lederer, D. E., J. S. Schuman, et al. (2003). "Analysis of Macular volume in normal and glaucomatous eyes using optical coherence tomography." *American Journal of Ophthalmology* 135(6): 838-843.
- Lee, P. P., Z. W. Feldman, et al. (2003). "Longitudinal prevalence of major eye diseases." *Archives of Ophthalmology* 121(9): 1303-1310.
- Lehrer, M. S., T. T. Sun, et al. (1998). "Strategies of epithelial repair: modulation of stem cell and transit amplifying cell proliferation." *Journal of Cell Science* 111(Pt 19): 2867-75.
- Leibowitz, H. M., D. E. Krueger, et al. (1980). "The Framingham Eye Study monograph: An ophthalmological and epidemiological study of cataract, glaucoma, diabetic retinopathy, macular degeneration, and visual acuity in a general population of 2631 adults, 1973-1975." *Survey of Ophthalmology* 24(Suppl): 335-610.
- Leitgeb, R., C. K. Hitzenberger, et al. (2003). "Performance of fourier domain vs. time domain optical coherence tomography." *Optics Express* 11(8): 889-894.
- Leitgeb, R., L. F. Schmetterer, et al. (2002). "Flow velocity measurements by frequency domain short coherence interferometry." *Proc. SPIE* 4619: 16-21.
- Leitgeb, R. A., W. Drexler, et al. (2004). "Ultrahigh resolution Fourier domain optical coherence tomography." *Optics Express* 12(10): 2156-2165.
- Leitgeb, R. A., C. K. Hitzenberger, et al. (2003). "Phase-shifting algorithm to achieve high-speed long-depth-range probing by frequency-domain optical coherence tomography." *Optics Letters* 28(22): 2201-2203.
- Leitgeb, R. A., L. Schmetterer, et al. (2003). "Real-time assessment of retinal blood flow with ultrafast acquisition by color Doppler Fourier domain optical coherence tomography." *Optics Express* 11(23): 3116-3121.
- Leitgeb, R. A., L. Schmetterer, et al. (2004). "Real-time measurement of in vitro flow by Fourier-domain color Doppler optical coherence tomography." *Optics Letters* 29 (2): 171-173.
- LeRoyBrehonnet, F. and B. LeJeune (1997). "Utilization of Mueller matrix formalism to obtain optical targets depolarization and polarization properties." *Progress in Quantum Electronics* 21(2): 109-151.
- Leske, M. C., A. M. Connell, et al. (1995). "Risk Factors for open-angle glaucoma. The Barbados Eye Study. [see comments]." *Archives of Ophthalmology* 113(7): 918-24.
- Leske, M. C., A. M. Connell, et al. (2001). "Incidence of open-angle glaucoma: the Barbados Eye Studies. The Barbados Eye Studies Group. [see comments]." *Archives of Ophthalmology* 119(1): 89-95.
- Leske, M. C., A. Heijl, et al. (1999). "Early Manifest Glaucoma Trial. Design and Baseline Data." *Ophthalmology* 106(11): 2144-2153.
- Lewis, S. E., J. R. DeBoer, et al. (2005). "Sensitive, selective, and analytical improvements to a porous silicon gas sensor." *Sensor and Actuators B: Chemical* 110(1): 54-65.
- Lexer, F., C. K. Hitzenberger, et al. (1999). "Dynamic coherent focus OCT with depth- independent transversal resolution." *Journal of Modern Optics* 46(3): 541-553.
- Li, X., C. Chudoba, et al. (2000). "Imaging needle for optical coherence tomography." *Optics Letters* 25: 1520-1522.
- Li, X., T. H. Ko, et al. (2001). "Intraluminal fiber-optic Doppler imaging catheter for structural and functional optical coherence tomography." *Optics Letters* 26: 1906-1908.
- Liddington, M. I. and P. G. Shakespeare (1996). "Timing of the thermographic assessment of burns." *Burns* 22(1): 26-8.

(56)

References Cited

OTHER PUBLICATIONS

- Lindmo, T., D. J. Smithies, et al. (1998). "Accuracy and noise in optical Doppler tomography studied by Monte Carlo simulation." *Physics in Medicine and Biology* 43(10): 3045-3064.
- Liu, J., X. Chen, et al. (1999). "New thermal wave aspects on burn evaluation of skin subjected to instantaneous heating." *IEEE Transactions on Biomedical Engineering* 46(4): 420-8.
- Luke, D. G., R. McBride, et al. (1995). "Polarization mode dispersion minimization in fiber-wound piezoelectric cylinders." *Optics Letters* 20(24): 2550-2552.
- MacNeill, B. D., I. K. Jang, et al. (2004). "Focal and multi-focal plaque distributions in patients with macrophage acute and stable presentations of coronary artery disease." *Journal of the American College of Cardiology* 44(5): 972-979.
- Mahgerefteh, D. and C. R. Menyuk (1999). "Effect of first-order PMD compensation on the statistics of pulse broadening in a fiber with randomly varying birefringence." *Ieee Photonics Technology Letters* 11(3): 340-342.
- Maitland, D. J. and J. T. Walsh, Jr. (1997). "Quantitative measurements of linear birefringence during heating of native collagen." *Lasers in Surgery & Medicine* 20 (3): 310-8.
- Majaron, B., S. M. Srinivas, et al. (2000). "Deep coagulation of dermal collagen with repetitive Er:YAG laser irradiation." *Lasers in Surgery and Medicine* 26(2): 215-222.
- Mansuripur, M. (1991). "Effects High-Numerical-Aperture Focusing on the State of Polarization in Optical and Magneto-optic Data-Storage Systems." *Applied Optics* 30(22): 3154-3162.
- Marshall, G. W., S. J. Marshall, et al. (1997). "The dentin substrate: structure and properties related to bonding." *Journal of Dentistry* 25(6): 441-458.
- Martin, P. (1997). "Wound healing—Aiming for perfect skin regeneration." *Science* 276 (5309): 75-81.
- Martinez, O. E. (1987). "3000 Times Grating Compressor with Positive Group-Velocity Dispersion—Application to Fiber Compensation in 1.3-1.6 μm -M Region." *Ieee Journal of Quantum Electronics* 23(1): 59-64.
- Martinez, O. E., J. P. Gordon, et al. (1984). "Negative Group-Velocity Dispersion Using Refraction." *Journal of the Optical Society of America a—Optics Image Science and Vision* 1(10): 1003-1006.
- McKinney, J. D., M. A. Webster, et al. (2000). "Characterization and imaging in optically scattering media by use of laser speckle and a variable-coherence source." *Optics Letters* 25(1): 4-6.
- Miglior, S., M. Casula, et al. (2001). "Clinical ability of Heidelberg retinal tomograph examination to detect glaucomatous visual field changes." *Ophthalmology* 108 (9): 1621-7.
- Milner, T. E., D. M. Goodman, et al. (1996). "Imaging laser heated subsurface chromophores in biological materials: Determination of lateral physical dimensions." *Physics in Medicine and Biology* 41(1): 31-44.
- Milner, T. E., D. M. Goodman, et al. (1995). "Depth Profiling of Laser-Heated Chromophores in Biological Tissues by Pulsed Photothermal Radiometry." *Journal of the Optical Society of America a—Optics Image Science and Vision* 12 (7): 1479-1488.
- Milner, T. E., D. J. Smithies, et al. (1996). "Depth determination of chromophores in human skin by pulsed photothermal radiometry." *Applied Optics* 35(19): 3379-3385.
- Mishchenko, M. I. and J. W. Hovenier (1995). "Depolarization of Light Backscattered by Randomly Oriented Nonspherical Particles." *Optics Letters* 20(12): 1356-8.
- Mistlberger, A., J. M. Liebmann, et al. (1999). "Heidelberg retina tomography and optical coherence tomography in normal, ocular-hypertensive, and glaucomatous eyes." *Ophthalmology* 106(10): 2027-32.
- Mitsui, T. (1999). "High-speed detection of ballistic photons propagating through suspensions using spectral interferometry." *Japanese Journal of Applied Physics Part 1-Regular Papers Short Notes & Review Papers* 38(5A): 2978-2982.
- Molteno, A. C., N. J. Bosma, et al. (1999). "Otago glaucoma surgery outcome study: long-term results of trabeculectomy—1976 to 1995." *Ophthalmology* 106(9): 1742-50.
- Morgner, U., W. Drexler, et al. (2000). "Spectroscopic optical coherence tomography." *Optics Letters* 25(2): 111-113.
- Morgner, U., F. X. Kartner, et al. (1999). "Sub-two-cycle pulses from a Kerr-lens mode-locked Ti sapphire laser (vol. 24, p. 411, 1999)." *Optics Letters* 24(13): 920-920.
- Mourant, J. R., A. H. Hielscher, et al. (1998). "Evidence of intrinsic differences in the light scattering properties of tumorigenic and nontumorigenic cells." *Cancer Cytopathology* 84(6): 366-374.
- Muller, M., J. Squier, et al. (1998). "Dispersion pre-compensation of 15 femtosecond optical pulses for high-numerical-aperture objectives." *Journal of Microscopy-Oxford* 191: 141-150.
- Muscat, S., N. McKay, et al. (2002). "Repeatability and reproducibility of corneal thickness measurements by optical coherence tomography." *Investigative Ophthalmology & Visual Science* 43(6): 1791-5.
- Musch, D. C., P. R. Lichter, et al. (1999). "The Collaborative Initial Glaucoma Treatment Study. Study Design, Methods, and Baseline Characteristics of Enrolled Patients." *Ophthalmology* 106: 653-662.
- Neerken, S., Lucassen, G.W., Bisschop, M.A., Lenderink, E., Nuijs, T.A.M. (2004). "Characterization of age-related effects in human skin: A comparative study that applies confocal laser scanning microscopy and optical coherence tomography." *Journal of Biomedical Optics* 9(2): 274-281.
- Nelson, J. S., K. M. Kelly, et al. (2001). "Imaging blood flow in human port-wine stain in situ and in real time using optical Doppler tomography." *Archives of Dermatology* 137(6): 741-744.
- Newson, T. P., F. Farahi, et al. (1988). "Combined Interferometric and Polarimetric Fiber Optic Temperature Sensor with a Short Coherence Length Source." *Optics Communications* 68(3): 161-165.
- November, L. J. (1993). "Recovery of the Matrix Operators in the Similarity and Congruency Transformations—Applications in Polarimetry." *Journal of the Optical Society of America a—Optics Image Science and Vision* 10(4): 719-739.
- Oh, W. Y., S. H. Yun, et al. (2005). "Wide tuning range wavelength-swept laser with two semiconductor optical amplifiers." *Ieee Photonics Technology Letters* 17(3): 678-680.
- Oka, K. and T. Kato (1999). "Spectroscopic polarimetry with a channeled spectrum." *Optics Letters* 24(21): 1475-1477.
- Okugawa, T. and K. Rotate (1996). "Real-time optical image processing by synthesis of the coherence function using real-time holography." *Ieee Photonics Technology Letters* 8(2): 257-259.
- Oshima, M., R. Torii, et al. (2001). "Finite element simulation of blood flow in the cerebral artery." *Computer Methods in Applied Mechanics and Engineering* 191 (6-7): 661-671.
- Pan, Y. T., H. K. Xie, et al. (2001). "Endoscopic optical coherence tomography based on a microelectromechanical mirror." *Optics Letters* 26(24): 1966-1968.
- Parisi, V., G. Manni, et al. (2001). "Correlation between optical coherence tomography, pattern electroretinogram, and visual evoked potentials in open-angle glaucoma patients." *Ophthalmology* 108(5): 905-12.
- Park, B. H., M. C. Pierce, et al. (2005). "Real-time fiber-based multifunctional spectral-domain optical coherence tomography at 1.3 μm ." *Optics Express* 13(11): 3931-3944.
- Park, D. H., J. W. Hwang, et al. (1998). "Use of laser Doppler flowmetry for estimation of the depth of burns." *Plastic and Reconstructive Surgery* 101(6): 1516-1523.
- Pendry, J. B., A. J. Holden, et al. (1999). "Magnetism from conductors and enhanced nonlinear phenomena." *Ieee Transactions on Microwave Theory and Techniques* 47(11): 2075-2084.
- Penninckx, D. and V. Morenas (1999). "Jones matrix of polarization mode dispersion." *Optics Letters* 24(13): 875-877.
- Pierce, M. C., M. Shishkov, et al. (2005). "Effects of sample arm motion in endoscopic polarization-sensitive optical coherence tomography." *Optics Express* 13(15): 5739-5749.
- Pircher, M., E. Gotzinger, et al. (2003). "Measurement and imaging of water concentration in human cornea with differential absorption optical coherence tomography." *Optics Express* 11(18): 2190-2197.
- Pircher, M., E. Gotzinger, et al. (2003). "Speckle reduction in optical coherence tomography by frequency compounding." *Journal of Biomedical Optics* 8(3): 565-569.

(56)

References Cited

OTHER PUBLICATIONS

- Podoleanu, A. G., G. M. Dobre, et al. (1998). "En-face coherence imaging using galvanometer scanner modulation." *Optics Letters* 23(3): 147-149.
- Podoleanu, A. G. and D. A. Jackson (1999). "Noise analysis of a combined optical coherence tomograph and a confocal scanning ophthalmoscope." *Applied Optics* 38(10): 2116-2127.
- Podoleanu, A. G., J. A. Rogers, et al. (2000). "Three dimensional OCT images from retina and skin." *Optics Express* 7(9): 292-298.
- Podoleanu, A. G., M. Seeger, et al. (1998). "Transversal and longitudinal images from the retina of the living eye using low coherence reflectometry." *Journal of Biomedical Optics* 3(1): 12-20.
- Poole, C. D. (1988). "Statistical Treatment of Polarization Dispersion in Single-Mode Fiber." *Optics Letters* 13(8): 687-689.
- Povazay, B., K. Bizheva, et al. (2002). "Submicrometer axial resolution optical coherence tomography." *Optics Letters* 27(20): 1800-1802.
- Qi, B., A. P. Himmer, et al. (2004). "Dynamic focus control in high-speed optical coherence tomography based on a microelectromechanical mirror." *Optics Communications* 232(1-6): 123-128.
- Radhakrishnan, S., A. M. Rollins, et al. (2001). "Real-time optical coherence tomography of the anterior segment at 1310 nm." *Archives of Ophthalmology* 119(8): 1179-1185.
- Rogers, A. J. (1981). "Polarization-Optical Time Domain Reflectometry—a Technique for the Measurement of Field Distributions." *Applied Optics* 20(6): 1060-1074.
- Rollins, A. M. and J. A. Izatt (1999). "Optimal interferometer designs for optical coherence tomography." *Optics Letters* 24(21): 1484-1486.
- Rollins, A. M., R. Ung-arunyawee, et al. (1999). "Real-time in vivo imaging of human gastrointestinal ultrastructure by use of endoscopic optical coherence tomography with a novel efficient interferometer design." *Optics Letters* 24(19): 1358-1360.
- Rollins, A. M., S. Yazdanfar, et al. (2002). "Real-time in vivo colors Doppler optical coherence tomography." *Journal of Biomedical Optics* 7(1): 123-129.
- Rollins, A. M., S. Yazdanfar, et al. (2000). "Imaging of human retinal hemodynamics using color Doppler optical coherence tomography." *Investigative Ophthalmology & Visual Science* 41(4): S548-S548.
- Sandoz, P. (1997). "Wavelet transform as a processing tool in white-light interferometry." *Optics Letters* 22(14): 1065-1067.
- Sankaran, V., M. J. Everett, et al. (1999). "Comparison of polarized-light propagation in biological tissue and phantoms." *Optics Letters* 24(15): 1044-1046.
- Sankaran, V., J. T. Walsh, et al. (2000). "Polarized light propagation through tissue phanto, ehms containing densely packed scatterers." *Optics Letters* 25(4): 239-241.
- Sarunic, M. V., M. A. Choma, et al. (2005). "Instantaneous complex conjugate resolved spectral domain and swept-source OCT using 3x3 fiber couplers." *Optics Express* 13(3): 957-967.
- Sathyam, U. S., B. W. Colston, et al. (1999). "Evaluation of optical coherence quantitation of analytes in turbid media by use of two wavelengths." *Applied Optics* 38(10): 2097-2104.
- Schmitt, J. M. (1997). "Array detection for speckle reduction in optical coherence microscopy." *Physics in Medicine and Biology* 42(7): 1427-1439.
- Schmitt, J. M. (1999). "Optical coherence tomography (OCT): A review." *Ieee Journal of Selected Topics in Quantum Electronics* 5(4): 1205-1215.
- Schmitt, J. M. and A. Knüttel (1997). "Model of optical coherence tomography of heterogeneous tissue." *Journal of the Optical Society of America a—Optics Image Science and Vision* 14(6): 1231-1242.
- Schmitt, J. M., S. L. Lee, et al. (1997). "An optical coherence microscope with enhanced resolving power in thick tissue." *Optics Communications* 142(4-6): 203-207.
- Schmitt, J. M., S. H. Xiang, et al. (1998). "Differential absorption imaging with optical coherence tomography." *Journal of the Optical Society of America a—Optics Image Science and Vision* 15(9): 2288-2296.
- Schmitt, J. M., S. H. Xiang, et al. (1999). "Speckle in optical coherence tomography." *Journal of Biomedical Optics* 4(1): 95-105.
- Schmitt, J. M., M. J. Yablowsky, et al. (1995). "Subsurface Imaging of Living Skin with Optical Coherence Microscopy." *Dermatology* 191(2): 93-98.
- Shi, H., J. Finlay, et al. (1997). "Multiwavelength 10-GHz picosecond pulse generation from a single-strip semiconductor diode laser." *Ieee Photonics Technology Letters* 9(11): 1439-1441.
- Shi, H., I. Nitta, et al. (1999). "Demonstration of phase correlation in multiwavelength mode-locked semiconductor diode lasers." *Optics Letters* 24(4): 238-240.
- Simon, R. (1982). "The Connection between Mueller and Jones Matrices of Polarization Optics." *Optics Communications* 42(5): 293-297.
- Smith, P. J. M., E. M.; Taylor, C. M.; Selviah, D. R.; Day, S. E.; Commander, L. G. "Variable-Focus Microlenses as Potential Technology for Endoscopy."
- Smithies, D. J., T. Lindmo, et al. (1998). "Signal attenuation and localization in optical coherence tomography studied by Monte Carlo simulation." *Physics in Medicine and Biology* 43(10): 3025-3044.
- Sorin, W. V. and D. F. Gray (1992). "Simultaneous Thickness and Group Index Measurement Using Optical Low-Coherence Reflectometry." *Ieee Photonics Technology Letters* 4(1): 105-107.
- Sticker, M., C. K. Hitzenberger, et al. (2001). "Quantitative differential phase measurement and imaging in transparent and turbid media by optical coherence tomography." *Optics Letters* 26(8): 518-520.
- Sticker, M., M. Pircher, et al. (2002). "En face imaging of single cell layers by differential phase-contrast optical coherence microscopy." *Optics Letters* 27(13): 1126-1128.
- Stoller, P., B. M. Kim, et al. (2002). "Polarization-dependent optical second-harmonic imaging of a rat-tail tendon." *Journal of Biomedical Optics* 7(2): 205-214.
- Sun, C. S. (2003). "Multiplexing of fiber-optic acoustic sensors in a Michelson interferometer configuration." *Optics Letters* 28(12): 1001-1003.
- Swanson, E. A., J. A. Izatt, et al. (1993). "In-Vivo Retinal Imaging by Optical Coherence Tomography." *Optics Letters* 18(21): 1864-1866.
- Takada, K., A. Himeno, et al. (1991). "Phase-Noise and Shot-Noise Limited Operations of Low Coherence Optical-Time Domain Reflectometry." *Applied Physics Letters* 59(20): 2483-2485.
- Takenaka, H. (1973). "Unified Formalism for Polarization Optics by Using Group-Theory I (Theory)." *Japanese Journal of Applied Physics* 12(2): 226-231.
- Tanno, N., T. Ichimura, et al. (1994). "Optical Multimode Frequency-Domain Reflectometer." *Optics Letters* 19(8): 587-589.
- Tan-no, N., T. Ichimura, et al. (1994). "Optical Multimode Frequency-Domain Reflectometer." *Optics Letters* 19(8): 587-589.
- Targowski, P., M. Wojtkowski, et al. (2004). "Complex spectral OCT in human eye imaging in vivo." *Optics Communications* 229(1-6): 79-84.
- Tearney, G. J., S. A. Boppart, et al. (1996). "Scanning single-mode fiber optic catheter- endoscope for optical coherence tomography (vol. 21, p. 543, 1996)." *Optics Letters* 21(12): 912-912.
- Tearney, G. J., B. E. Bouma, et al. (1996). "Rapid acquisition of in vivo biological images by use of optical coherence tomography." *Optics Letters* 21(17): 1408-1410.
- Tearney, G. J., B. E. Bouma, et al. (1997). "In vivo endoscopic optical biopsy with optical coherence tomography." *Science* 276(5321): 2037-2039.
- Tearney, G. J., M. E. Brezinski, et al. (1996). "Catheter-based optical imaging of a human coronary artery." *Circulation* 94(11): 3013-3013.
- Tearney, G. J., M. E. Brezinski, et al. (1997). "In vivo endoscopic optical biopsy with optical coherence tomography." *Science* 276(5321): 2037-9.
- Tearney, G. J., M. E. Brezinski, et al. (1997). "Optical biopsy in human gastrointestinal tissue using optical coherence tomography." *American Journal of Gastroenterology* 92(10): 1800-1804.
- Tearney, G. J., M. E. Brezinski, et al. (1995). "Determination of the refractive index of highly scattering human tissue by optical coherence tomography." *Optics Letters* 20(21): 2258-2260.

(56)

References Cited

OTHER PUBLICATIONS

- Tearney, G. J., I. K. Jang, et al. (2000). "Porcine coronary imaging in vivo by optical coherence tomography." *Acta Cardiologica* 55(4): 233-237.
- Tearney, G. J., R. H. Webb, et al. (1998). "Spectrally encoded confocal microscopy." *Optics Letters* 23(15): 1152-1154.
- Tearney, G. J., H. Yabushita, et al. (2003). "Quantification of macrophage content in atherosclerotic plaques by optical coherence tomography." *Circulation* 107(1): 113-119.
- Tower, T. T. and R. T. Tranquillo (2001). "Alignment maps of tissues: I. Microscopic elliptical polarimetry." *Biophysical Journal* 81(5): 2954-2963.
- Tower, T. T. and R. T. Tranquillo (2001). "Alignment maps of tissues: II. Fast harmonic analysis for imaging." *Biophysical Journal* 81(5): 2964-2971.
- Troy, T. L. and S. N. Thennadil (2001). "Optical properties of human skin in the near infrared wavelength range of 1000 to 2200 nm." *Journal of Biomedical Optics* 6(2): 167-176.
- Vabre, L., A. Dubois, et al. (2002). "Thermal-light full-field optical coherence tomography." *Optics Letters* 27(7): 530-532.
- Vakhtin, A. B., D. J. Kane, et al. (2003). "Common-path interferometer for frequency-domain optical coherence tomography." *Applied Optics* 42(34): 6953-6958.
- Vakhtin, A. B., K. A. Peterson, et al. (2003). "Differential spectral interferometry: an imaging technique for biomedical applications." *Optics Letters* 28(15): 1332-1334.
- Vakoc, B. J., S. H. Yun, et al. (2005). "Phase-resolved optical frequency domain imaging." *Optics Express* 13(14): 5483-5493.
- van Leeuwen, T. G., M. D. Kulkarni, et al. (1999). "High-flow-velocity and shear-rate imaging by use of color Doppler optical coherence tomography." *Optics Letters* 24(22): 1584-1586.
- Vansteenkiste, N., P. Vignolo, et al. (1993). "Optical Reversibility Theorems for Polarization—Application to Remote-Control of Polarization." *Journal of the Optical Society of America a—Optics Image Science and Vision* 10(10): 2240-2245.
- Vargas, O., E. K. Chan, et al. (1999). "Use of an agent to reduce scattering in skin." *Lasers in Surgery and Medicine* 24(2): 133-141.
- Wang, R. K. (1999). "Resolution improved optical coherence-gated tomography for imaging through biological tissues." *Journal of Modern Optics* 46(13): 1905-1912.
- Wang, X. J., T. E. Milner, et al. (1997). "Measurement of fluid-flow-velocity profile in turbid media by the use of optical Doppler tomography." *Applied Optics* 36(1): 144-149.
- Wang, X. J., T. E. Milner, et al. (1995). "Characterization of Fluid-Flow Velocity by Optical Doppler Tomography." *Optics Letters* 20(11): 1337-1339.
- Wang, Y. M., J. S. Nelson, et al. (2003). "Optimal wavelength for ultrahigh-resolution optical coherence tomography." *Optics Express* 11(12): 1411-1417.
- Wang, Y. M., Y. H. Zhao, et al. (2003). "Ultrahigh-resolution optical coherence tomography by broadband continuum generation from a photonic crystal fiber." *Optics Letters* 28(3): 182-184.
- Watkins, L. R., S. M. Tan, et al. (1999). "Determination of interferometer phase distributions by use of wavelets." *Optics Letters* 24(13): 905-907.
- Wetzel, J. (2001). "Optical coherence tomography in dermatology: a review." *Skin Research and Technology* 7(1): 1-9.
- Wentworth, R. H. (1989). "Theoretical Noise Performance of Coherence-Multiplexed Interferometric Sensors." *Journal of Lightwave Technology* 7(6): 941-956.
- Westphal, V., A. M. Rollins, et al. (2002). "Correction of geometric and refractive image distortions in optical coherence tomography applying Fermat's principle." *Optics Express* 10(9): 397-404.
- Westphal, V., S. Yazdanfar, et al. (2002). "Real-time, high velocity-resolution color Doppler optical coherence tomography." *Optics Letters* 27(1): 34-36.
- Williams, P. A. (1999). "Rotating-wave-plate Stokes polarimeter for differential group delay measurements of polarization-mode dispersion." *Applied Optics* 38(31): 6508-6515.
- Wojtkowski, M., T. Bajraszewski, et al. (2003). "Real-time in vivo imaging by high-speed spectral optical coherence tomography." *Optics Letters* 28(19): 1745-1747.
- Wojtkowski, M., A. Kowalczyk, et al. (2002). "Full range complex spectral optical coherence tomography technique in eye imaging." *Optics Letters* 27(16): 1415-1417.
- Wojtkowski, M., R. Leitgeb, et al. (2002). "In vivo human retinal imaging by Fourier domain optical coherence tomography." *Journal of Biomedical Optics* 7(3): 457-463.
- Wojtkowski, M., R. Leitgeb, et al. (2002). "Fourier domain OCT imaging of the human eye in vivo." *Proc. SPIE* 4619: 230-236.
- Wojtkowski, M., V. J. Srinivasan, et al. (2004). "Ultrahigh-resolution, high-speed, Fourier domain optical coherence tomography and methods for dispersion compensation." *Optics Express* 12(11): 2404-2422.
- Wong, B. J. F., Y. H. Zhao, et al. (2004). "Imaging the internal structure of the rat cochlea using optical coherence tomography at 0.827 μm and 1.3 μm ." *Otolaryngology-Head and Neck Surgery* 130(3): 334-338.
- Yabushita, H. B., B. E.; Houser, S.L.; Aretz, H.T.; Jang, I.; Schlendorf, K.H.; Kauffman, C.R.; Shishkov, M.; Halpern, E.F.; Tearney, G.J. "Measurement of Thin Fibrous Caps in Atherosclerotic Plaques by Optical Coherence Tomography."
- Yang, C., A. Wax, et al. (2001). "Phase-dispersion optical tomography." *Optics Letters* 26(10): 686-688.
- Yang, C., A. Wax, et al. (2001). "Phase-referenced interferometer with subwavelength and subhertz sensitivity applied to the study of cell membrane dynamics." *Optics Letters* 26(16): 1271-1273.
- Yang, C. H., A. Wax, et al. (2001). "Phase-dispersion optical tomography." *Optics Letters* 26(10): 686-688.
- Yang, C. H., A. Wax, et al. (2000). "Interferometric phase-dispersion microscopy." *Optics Letters* 25(20): 1526-1528.
- Yang, V. X. D., M. L. Gordon, et al. (2002). "Improved phase-resolved optical Doppler tomography using the Kasai velocity estimator and histogram segmentation." *Optics Communications* 208(4-6): 209-214.
- Yang, V. X. D., M. L. Gordon, et al. (2003). "High speed, wide velocity dynamic range Doppler optical coherence tomography (Part I): System design, signal processing, and performance." *Optics Express* 11(7): 794-809.
- Yang, V. X. D., M. L. Gordon, et al. (2003). "High speed, wide velocity dynamic range Doppler optical coherence tomography (Part II): Imaging in vivo cardiac dynamics of *Xenopus laevis*." *Optics Express* 11(14): 1650-1658.
- Yang, V. X. D., M. L. Gordon, et al. (2003). "High speed, wide velocity dynamic range Doppler optical coherence tomography (Part III): in vivo endoscopic imaging of blood flow in the rat and human gastrointestinal tracts." *Optics Express* 11(19): 2416-2424.
- Yang, V. X. D., B. Qi, et al. (2003). "In vivo feasibility of endoscopic catheter-based Doppler optical coherence tomography." *Gastroenterology* 124(4): A49-A50.
- Yao, G. and L. H. V. Wang (2000). "Theoretical and experimental studies of ultrasound-modulated optical tomography in biological tissue." *Applied Optics* 39(4): 659-664.
- Yazdanfar, S. and J. A. Izatt (2002). "Self-referenced Doppler optical coherence tomography." *Optics Letters* 27(23): 2085-2087.
- Yazdanfar, S., M. D. Kulkarni, et al. (1997). "High resolution imaging of in vivo cardiac dynamics using color Doppler optical coherence tomography." *Optics Express* 1 (13): 424-431.
- Yazdanfar, S., A. M. Rollins, et al. (2000). "Imaging and velocimetry of the human retinal circulation with color Doppler optical coherence tomography." *Optics Letters* 25(19): 1448-1450.
- Yazdanfar, S., A. M. Rollins, et al. (2000). "Noninvasive imaging and velocimetry of human retinal blood flow using color Doppler optical coherence tomography." *Investigative Ophthalmology & Visual Science* 41(4): S548-S548.
- Yazdanfar, S., A. M. Rollins, et al. (2003). "In vivo imaging of human retinal flow dynamics by color Doppler optical coherence tomography." *Archives of Ophthalmology* 121(2): 235-239.
- Yazdanfar, S., C. H. Yang, et al. (2005). "Frequency estimation precision in Doppler optical coherence tomography using the Cramer-Rao lower bound." *Optics Express* 13(2): 410-416.

(56)

References Cited

OTHER PUBLICATIONS

- Yun, S. H., C. Boudoux, et al. (2004). "Extended-cavity semiconductor wavelength- swept laser for biomedical imaging." *Ieee Photonics Technology Letters* 16(1): 293-295.
- Yun, S. H., C. Boudoux, et al. (2003). "High-speed wavelength-swept semiconductor laser with a polygon-scanner-based wavelength filter." *Optics Letters* 28(20): 1981-1983.
- Yun, S. H., G. J. Tearney, et al. (2004). "Pulsed-source and swept-source spectral- domain optical coherence tomography with reduced motion artifacts." *Optics Express* 12(23): 5614-5624.
- Yun, S. H., G. J. Tearney, et al. (2004). "Removing the depth-degeneracy in optical frequency domain imaging with frequency shifting." *Optics Express* 12(20): 4822-4828.
- Yun, S. H., G. J. Tearney, et al. (2004). "Motion artifacts in optical coherence tomography with frequency-domain ranging." *Optics Express* 12(13): 2977-2998.
- Zhang, J., J. S. Nelson, et al. (2005). "Removal of a mirror image and enhancement of the signal-to-noise ratio in Fourier-domain optical coherence tomography using an electro-optic phase modulator." *Optics Letters* 30(2): 147-149.
- Zhang, Y., M. Sato, et al. (2001). "Numerical investigations of optimal synthesis of several low coherence sources for resolution improvement." *Optics Communications* 192(3-6): 183-192.
- Zhang, Y., M. Sato, et al. (2001). "Resolution improvement in optical coherence tomography by optimal synthesis of light-emitting diodes." *Optics Letters* 26(4): 205-207.
- Zhao, Y., Z. Chen, et al. (2002). "Real-time phase-resolved functional optical coherence tomography by use of optical Hilbert transformation." *Optics Letters* 27(2): 98-100.
- Zhao, Y. H., Z. P. Chen, et al. (2000). "Doppler standard deviation imaging for clinical monitoring of in vivo human skin blood flow." *Optics Letters* 25(18): 1358-1360.
- Zhao, Y. H., Z. P. Chen, et al. (2000). "Phase-resolved optical coherence tomography and optical Doppler tomography for imaging blood flow in human skin with fast scanning speed and high velocity sensitivity." *Optics Letters* 25(2): 114-116.
- Zhou, D., P. R. Prucnal, et al. (1998). "A widely tunable narrow linewidth semiconductor fiber ring laser." *IEEE Photonics Technology Letters* 10(6): 781-783.
- Zuluaga, A. F. and R. Richards-Kortum (1999). "Spatially resolved spectral interferometry for determination of subsurface structure." *Optics Letters* 24(8): 519-521.
- Zvyagin, A. V., J. B. FitzGerald, et al. (2000). "Real-time detection technique for Doppler optical coherence tomography." *Optics Letters* 25(22): 1645-1647.
- Marc Nikles et al., "Brillouin gain spectrum characterization in single-mode optical fibers", *Journal of Lightwave Technology* 1997, 15 (10): 1842-1851.
- Tsuyoshi Sonehara et al., "Forced Brillouin Spectroscopy Using Frequency-Tunable Continuous-Wave Lasers", *Physical Review Letters* 1995, 75 (23): 4234-4237.
- Hajima Tanaka et al., "New Method of Superheterodyne Light Beating Spectroscopy for Brillouin-Scattering Using Frequency-Tunable Lasers", *Physical Review Letters* 1995, 74 (9): 1609-1612.
- Webb RH et al. "Confocal Scanning Laser Ophthalmoscope", *Applied Optics* 1987, 26 (8): 1492-1499.
- Andreas Zumbusch et al. "Three-dimensional vibrational imaging by coherent anti-Stokes Raman scattering", *Physical Review Letters* 1999, 82 (20): 4142-4145.
- Katrin Kneipp et al., "Single molecule detection using surface-enhanced Raman scattering (SERS)", *Physical Review Letters* 1997, 78 (9): 1667-1670.
- K.J. Koski et al., "Billouin imaging" *Applied Physics Letters* 87, 2005.
- Boas et al., "Diffusing temporal light correlation for burn diagnosis", *SPIE*, 1999, 2979:468-477.
- David J. Briers, "Speckle fluctuations and biomedical optics: implications and applications", *Optical Engineering*, 1993, 32(2):277-283.
- Clark et al., "Tracking Speckle Patterns with Optical Correlation", *SPIE*, 1992, 1772:77-87.
- Facchini et al., "An endoscopic system for DSPI", *Optik*, 1993, 95(1):27-30.
- Hrabovsky, M., "Theory of speckle displacement and decorrelation: application in mechanics", *SPIE*, 1998, 3479:345-354.
- Sean J. Kirkpatrick et al., "Micromechanical behavior of cortical bone as inferred from laser speckle data", *Journal of Biomedical Materials Research*, 1998, 39(3):373-379.
- Sean J. Kirkpatrick et al., "Laser speckle microstrain measurements in vascular tissue", *SPIE*, 1999, 3598:121-129.
- Loree et al., "Mechanical Properties of Model Atherosclerotic Lesion Lipid Pools", *Arteriosclerosis and Thrombosis*, 1994, 14(2):230-234.
- Podbielska, H. "Interferometric Methods and Biomedical Research", *SPIE*, 1999, 2732:134-141.
- Richards-Kortum et al., "Spectral diagnosis of atherosclerosis using an optical fiber laser catheter", *American Heart Journal*, 1989, 118(2):381-391.
- Ruth, B. "blood flow determination by the laser speckle method", *Int J Microcirc: Clin Exp*, 1990, 9:21-45.
- Shapo et al., "Intravascular strain imaging: Experiments on an Inhomogeneous Phantom", *IEEE Ultrasonics Symposium* 1996, 2:1177-1180.
- Shapo et al., "Ultrasonic displacement and strain imaging of coronary arteries with a catheter array", *IEEE Ultrasonics Symposium* 1995, 2:1511-1514.
- Thompson et al., "Imaging in scattering media by use of laser speckle", *Opt. Soc. Am. A*, 1997, 14(9):2269-2277.
- Thompson et al., "Diffusive media characterization with laser speckle", *Applied Optics*, 1997, 36(16):3726-3734.
- Tuchin, Valery V., "Coherent Optical Techniques for the Analysis of Tissue Structure and Dynamics," *Journal of Biomedical Optics*, 1999, 4(1):106-124.
- M. Wussling et al., "Laser diffraction and speckling studies in skeletal and heart muscle", *Biomed, Biochim, Acta*, 1986, 45(1/2):S 23-S 27.
- T. Yoshimura et al., "Statistical properties of dynamic speckles", *J. Opt. Soc. Am A*. 1986, 3(7):1032-1054.
- Zimnyakov et al., "Spatial speckle correlometry in applications to tissue structure monitoring", *Applied Optics* 1997, 36(22): 5594-5607.
- Zimnyakov et al., "A study of statistical properties of partially developed speckle fields as applied to the diagnosis of structural changes in human skin", *Optics and Spectroscopy*, 1994, 76(5): 747-753.
- Zimnyakov et al., "Speckle patterns polarization analysis as an approach to turbid tissue structure monitoring", *SPIE* 1999, 2981:172-180.
- Ramasamy Manoharan et al., "Biochemical analysis and mapping of atherosclerotic human artery using FT-IR microspectroscopy", *Atherosclerosis*, May 1993, 181-1930.
- N.V. Salunke et al., "Biomechanics of Atherosclerotic Plaque" *Critical Reviews™ in Biomedical Engineering* 1997, 25(3):243-285.
- Office Action dated Aug. 24, 2006 for U.S. Appl. No. 10/137,749.
- Barry Cense et al., "Spectral-domain polarization-sensitive optical coherence tomography at 850nm", *Coherence Domain Optical Methods and Optical Coherence Tomography in Biomedicine IX*, 2005, pp. 159-162.
- A. Ymeti et al., "Integration of microfluidics with a four-channel integrated optical Young interferometer immunosensor", *Biosensors and Bioelectronics*, Elsevier Science Publishers, 2005, pp. 1417-1421.
- PCT International Search Report for Application No. PCT/US2006/018865 filed May 5, 2006.
- International Written Opinion for International Patent application No. PCT/US2006/018865 filed May 5, 2006.
- John M. Poneris, "Diagnosis of Barrett's esophagus using optical coherence tomography", *Gastrointestinal Endoscopy clinics of North America*, 14 (2004) pp. 573-588.
- P.F. Escobar et al., "Diagnostic efficacy of optical coherence tomography in the management of preinvasive and invasive cancer of uterine cervix and vulva", *Int. Journal of Gynecological Cancer* 2004, 14, pp. 470-474.

(56)

References Cited

OTHER PUBLICATIONS

- Ko T et al., "Ultrahigh resolution in vivo versus ex vivo OCT imaging and tissue preservation", Conference on Lasers and electro-optics, 2001, pp. 252-253.
- Paul M. Ripley et al., "A comparison of Artificial Intelligence techniques for spectral classification in the diagnosis of human pathologies based upon optical biopsy", Journal of Optical Society of America, 2000, pp. 217-219.
- Wolfgang Drexler et al., "Ultrahigh-resolution optical coherence tomography", Journal of Biomedical Optics Spie USA, 2004, pp. 47-74.
- PCT International Search Report for Application No. PCT/US2006/016677 filed Apr. 28, 2006.
- International Written Opinion for International Patent application No. PCT/US2006/016677 filed Apr. 28, 2006.
- Office Action dated Nov. 13, 2006 for U.S. Appl. No. 10/501,268.
- Office Action dated Nov. 20, 2006 for U.S. Appl. No. 09/709,162.
- PCT International Search Report and Written Opinion for Application No. PCT/US2004/023585 filed Jul. 23, 2004.
- Notice of Reasons for Rejection and English translation for Japanese Patent Application No. 2002-538830.
- International Written Opinion for International Patent application No. PCT/US2005/043951.
- International Search Report for International Patent application No. PCT/US2005/043951.
- Erdelyi et al., "Generation of diffraction-free beams for applications in optical microlithography", J. Vac. Sci. Technol. B 15 (12), Mar./Apr. 1997, pp. 287-292.
- International Search Report for International Patent application No. PCT/US2005/023664.
- International Written Opinion for International Patent application No. PCT/US2005/023664.
- Tearney et al., "Spectrally encoded miniature endoscopy" Optical Society of America; Optical Letters vol. 27, No. 6, Mar. 15, 2002; pp. 412-414.
- Yelin et al., "Double-clad Fiber for Endoscopy" Optical Society of America; Optical Letters vol. 29, No. 20, Oct. 16, 2005; pp. 2408-2410.
- International Search Report for International Patent application No. PCT/US2001/049704.
- International Search Report for International Patent application No. PCT/US2004/039454.
- International Written Opinion for International Patent application No. PCT/US2004/039454.
- PCT International Preliminary Report on Patentability for International Application No. PCT/US2004/038404 dated Jun. 2, 2006.
- D. Fu et al., "Non-invasive quantitative reconstruction of tissue elasticity using an iterative forward approach", Phys. Med. Biol. 2000 (45): 1495-1509.
- S.B. Adams Jr. et al., "The use of polarization sensitive optical coherence tomography and elastography to assess connective tissue", Optical Soc. of American Washington 2002, p. 3.
- International Search Report for International Patent application No. PCT/US2005/039740.
- International Written Opinion for International Patent application No. PCT/US2005/039740.
- International Search Report for International Patent application No. PCT/US2005/030294.
- Fujimoto et al., "High Resolution in Vivo Intra-Arterial Imaging with Optical Coherence Tomography" *Official Journal of the British Cardiac Society*, vol. 82, pp. 128-133 Heart, 1999.
- D. Huang et al., "Optical Coherence Tomography", *SCIENCE*, vol. 254, pp. 1178-1181, Nov. 1991.
- Tearney et al., "High-Speed Phase—and Group Delay Scanning with a Grating Based Control Delay Line", *Optics Letters*, vol. 22, pp. 1811-1813, Dec. 1997.
- Rollins, et al., "In Vivo Video Rate Optical Coherence Tomography", *Optics Express*, vol. 3, pp. 219-229, Sep. 1998.
- Saxer, et al., High Speed Fiber-Based Polarization-Sensitive Optical Coherence Tomography of in Vivo Human Skin, *Optical Society of America*, vol. 25, pp. 1355-1357, Sep. 2000.
- Oscar Eduardo Martinez, "3000 Times Grating Compress or with Positive Group Velocity Dispersion", *IEEE*, vol. QE-23, pp. 59-64, Jan. 1987.
- Kulkarni, et al., "Image Enhancement in Optical Coherence Tomography Using Deconvolution", *Electronics Letters*, vol. 33, pp. 1365-1367, Jul. 1997.
- Bashkansky, et al., "Signal Processing for Improving Field Cross-Correlation Function in Optical Coherence Tomography", *Optics & Photonics News*, vol. 9, pp. 8137-8138, May 1998.
- Yung et al., "Phase-Domain Processing of Optical Coherence Tomography Images", *Journal of Biomedical Optics*, vol. 4, pp. 125-136, Jan. 1999.
- Tearney, et al., "In Vivo Endoscopic Optical Biopsy with Optical Coherence Tomography", *Science*, vol. 276, Jun. 1997.
- W. Drexler et al., "In Vivo Ultrahigh-Resolution Optical Coherence Tomography", *Opt. Lett.* vol. 24, pp. 1221-1223, Sep. 1999.
- Nicutor V. Iftimia et al., "A Portable, Low Coherence Interferometry Based Instrument for Fine Needle Aspiration Biopsy Guidance" Accepted to Review of Scientific Instruments, 2005.
- Abbas, G.L., V.W.S. Chan et al., "Local-Oscillator Excess-Noise Suppression for Homodyne and Heterodyne-Detection", *Optics Letters*, vol. 8, pp. 419-421, Aug. 1983 issue.
- Agrawal, G.P., "Population Pulsations and Nondegenerate 4-Wave Mixing in Semiconductor-Lasers and Amplifiers", *Journal Of The Optical Society Of America B-Optical Physics*, vol. 5, pp. 147-159, Jan. 1998.
- Andretzky, P. et al., "Optical Coherence Tomography by Spectral Radar: Improvement of Signal-to-Noise Ratio", *The International Society for Optical Engineering, USA*, vol. 3915, 2000.
- Ballif, J. et al., "Rapid and Scalable Scans at 21 m/s in optical Low-Coherence Reflectometry", *Optics Letters*, vol. 22, pp. 757-759, Jun. 1997.
- Barfuss H. et al., "Modified Optical Frequency-Domain Reflectometry with High Spatial-Resolution for Components of Integrated Optic Systems", *Journal Of Lightwave Technology*, vol. 7, pp. 3-10, Jan. 1989.
- Beaud, P. et al., "Optical Reflectometry with Micrometer Resolution for the Investigation of Integrated Optical-Devices", *IEEE Journal of Quantum Electronics*, vol. 25, pp. 755-759, Apr. 1989.
- Bouma, Brett et al., "Power-Efficient Nonreciprocal Interferometer and Linear-Scanning Fiber-Optic Catheter for Optical Coherence Tomography", *Optics Letters*, vol. 24, pp. 531-533, Apr. 1999.
- Brinkmeyer, E. et al., "Efficient Algorithm for Non-Equidistant Interpolation of Sampled Data", *Electronics Letters*, vol. 28, p. 693, Mar. 1992.
- Brinkmeyer, E. et al., "High-Resolution OADR in Dispersive Waveguides", *Electronics Letters*, vol. 26, pp. 413-414, Mar. 1990.
- Chinn, S.R. et al., "Optical Coherence Tomography Using a Frequency-Tunable Optical Source", *Optics Letters*, vol. 22, pp. 340-342, Mar. 1997.
- Danielson, B.L. et al., "Absolute Optical Ranging Using Low Coherence Interferometry", *Applied Optics*, vol. 30, p. 2975, Jul. 1991.
- Dorner, C. et al., "Spectral Resolution and Sampling Issues in Fourier-Transform Spectral Interferometry", *Journal of the Optical Society of America B-Optical Physics*, vol. 17, pp. 1795-1802, Oct. 2000.
- Dudley, J.M. et al., "Cross-Correlation Frequency Resolved Optical Gating Analysis of Broadband Continuum Generation in Photonic Crystal Fiber: Simulations and Experiments", *Optics Express*, vol. 10, p. 1215, Oct. 2002.
- Eickhoff, W. et al., "Optical Frequency-Domain Reflectometry in Single-Mode Fiber", *Applied Physics Letters*, vol. 39, pp. 693-695, 1981.
- Fercher, Adolf "Optical Coherence Tomography", *Journal of Biomedical Optics*, vol. 1, pp. 157-173, Apr. 1996.
- Ferreira, L.A. et al., "Polarization-Insensitive Fiberoptic White-Light Interferometry", *Optics Communications*, vol. 114, pp. 386-392, Feb. 1995.

(56)

References Cited

OTHER PUBLICATIONS

- Fujii, Yohji, "High-Isolation Polarization-Independent Optical Circulator", *Journal of Lightwave Technology*, vol. 9, pp. 1239-1243, Oct. 1991.
- Glance, B., "Polarization Independent Coherent Optical Receiver", *Journal of Lightwave Technology*, vol. LT-5, p. 274, Feb. 1987.
- Glombitza, U., "Coherent Frequency-Domain Reflectometry for Characterization of Single-Mode Integrated-Optical Wave-Guides", *Journal of Lightwave Technology*, vol. 11, pp. 1377-1384, Aug. 1993.
- Golubovic, B. et al., "Optical Frequency-Domain Reflectometry Using Rapid Wavelength Tuning of a Cr⁴⁺:Forsterite Laser", *Optics Letters*, vol. pp. 1704-1706, Nov. 1997.
- Haberland, U. H. P. et al., "Chirp Optical Coherence Tomography of Layered Scattering Media", *Journal of Biomedical Optics*, vol. 3, pp. 259-266, Jul. 1998.
- Hammer, Daniel X. et al., "Spectrally Resolved White-Light Interferometry for Measurement of Ocular Dispersion", *Journal of the Optical Society of America A—Optics Image Science and Vision*, vol. 16, pp. 2092-2102, Sep. 1999.
- Harvey, K. C. et al., "External-Cavity Diode-Laser Using a Grazing-Incidence Diffraction Grating", *Optics Letters*, vol. 16, pp. 910-912, Jun. 1991.
- Hausler, Gerd et al., "'Coherence Radar' and 'Spectral Radar' New Tools for Dermatological Diagnosis", *Journal of Biomedical Optics*, vol. 3, pp. 21-31, Jan. 1998.
- Hee, Michael R. et al., "Polarization-Sensitive Low-Coherence Reflectometer for Birefringence Characterization and Ranging", *Journal of the Optical Society of America B (Optical Physics)* vol. 9, p. 903-908, Jun. 1992.
- Hotate Kazuo et al., "Optical Coherence Domain Reflectometry by Synthesis of Coherence Function", *Journal of Lightwave Technology*, vol. 11, pp. 1701-1710, Oct. 1993.
- Inoue, Kyo et al., "Nearly Degenerate 4-Wave-Mixing in a Traveling-Wave Semiconductor-Laser Amplifier", *Applied Physics Letters*, vol. 51, pp. 1051-1053, 1987.
- Ivanov, A. P. et al., "New Method for High-Range Resolution Measurements of Light Scattering in Optically Dense Inhomogeneous Media", *Optics Letters*, vol. 1, pp. 226-228, Dec. 1977.
- Ivanov, A. P. et al., "Interferometric Study of the Spatial Structure of a Light-Scattering Medium", *Journal of Applied Spectroscopy*, vol. 28, pp. 518-525, 1978.
- Kazovsky, L. G. et al., "Heterodyne Detection Through Rain, Snow, and Turbin Media: Effective Receiver Size at Optical Through Millimeter Wavelengths", *Applied Optics* vol. 22, pp. 706-710, Mar. 1983.
- Kersey, A. D. et al., "Adaptive Polarization Diversity Receiver Configuration for Coherent Optical Fiber Communications", *Electroics Letters*, vol. 25, pp. 275-277, Feb. 1989.
- Kohlhaas, Andreas et al., "High-Resolution OCDR for Testing Integrated-Optical Waveguides: Dispersion-Corrupted Experimental Data Corrected by a Numerical Algorithm", *Journal of Lightwave Technology*, vol. 9, pp. 1493-1502, Nov. 1991.
- Larkin, Kieran G., "Efficient Nonlinear Algorithm for Envelope Detection in White Light Interferometry", *Journal of the Optical Society of America A—Optics Image Science and Vision*, vol. 13, pp. 832-843, Apr. 1996.
- Leitgeb, R. et al., "Spectral measurement of Absorption by Spectroscopic Frequency-Domain Optical Coherence Tomography", *Optics Letters*, vol. 25, pp. 820-822, Jun. 2000.
- Lexer, F. et al., "Wavelength-Tuning Interferometry of Intraocular Distances", *Applied Optics*, vol. 36, pp. 6548-6553, Sep. 1997.
- Mitsui, Takahisa, "Dynamic Range of Optical Reflectometry with Spectral Interferometry" *Japanese Journal of Applied Physics Part I—Regular Papers Short Notes & Review Papers*, vol. 38, pp. 6133-6137, 1999.
- Naganuma, Kazunori et al., "Group-Delay Measurement Using the Fourier-Transform of an Interferometric Cross-Correlation Generated by White Light", *Optics Letters*, vol. 15, pp. 393-395, Apr. 1990.
- Okoshi, Takanori, "Polarization-State Control Schemes for Heterodyne or Homodyne Optical Fiber Communications", *Journal of Lightwave Technology*, vol. L-T-3, pp. 1232-1237, Dec. 1995.
- Passy, R. et al., "Experimental and Theoretical Investigations of Coherent OFDR with Semiconductor-Laser Sources", *Journal of Lightwave Technology*, vol. 12, pp. 1622-1630, Sep. 1994.
- Podoleanu, Adrian G., "Unbalanced Versus Balanced Operation in an Optical Coherence Tomography System", *Applied Optics*, vol. 39, pp. 173-182, Jan. 2000.
- Price, J. H. V. et al., "Tunable, Femtosecond Pulse Source Operating in the Range 1.06-1.33 μ m Based on an Yb³⁺-doped Holey Fiber Amplifier", *Journal of the Optical Society of America B—Optical Physics*, vol. 19, pp. 1286-1294, Jun. 2002.
- Schmitt, J. M. et al., "Measurement of Optical-Properties O Biological Tissues By Low-Coherence Reflectometry" *Applied Optics*, vol. 32, pp. 6032-6042, Oct. 1993.
- Silberberg, Y. et al., "Passive-Mode Locking of a Semiconductor Diode-Laser", *Optics Letters*, vol. 9, pp. 507-509, Nov. 1984.
- Smith, L. Montgomery et al., "Absolute Displacement Measurements Using Modulation of the Spectrum of White-Light in a Michelson Interferometer", *Applied Optics*, vol. 28, pp. 3339-3342, Aug. 1989.
- Sonnenschein, C. M. et al., "Signal-To-Noise Relationships for Coaxial Systems that Heterodyne Backscatter from Atmosphere", *Applied Optics*, vol. 10, pp. 1600-1604, Jul. 1971.
- Sorin, W. V. et al., "Measurement of Rayleigh Backscattering at 1.55 μ m with 32 μ m Spatial Resolution", *IEEE Photonics Technology Letters*, vol. 4, pp. 374-376, Apr. 1992.
- Sorin, W. V. et al., "A Simple Reflectometry", *IEEE Photonics Technology Letters*, vol. 4, pp. 1404-1406, Dec. 1992.
- Swanson, E. A. et al., "High-Speed Optical Coherence Domain Reflectometry", *Optics Letters*, vol. 17, pp. 151-153, Jan. 1992.
- Takada, K. et al., "High-Resolution OFDR with Incorporated Fiber-optic Frequency Encoder", *IEEE Photonics Technology Letters*, vol. 4, pp. 1069-1072, Sep. 1992.
- Takada, Kazumasa et al., "Narrow-Band light Source with Acoustooptic Tunable Filter for Optical Low-Coherence Reflectometry", *IEEE Photonics Technology Letters*, vol. 8, pp. 658-660, May 1996.
- Takada, Kazumasa et al., "New Measurement System for Fault Location in Optical Wave-Guide Devices Based on an Interometric-Technique", *Applied Optics*, vol. 26, pp. 1603-1606, May 1987.
- Tateda, Mitsuhiro et al., "Interferometric Method for Chromatic Dispersion Measurement in a Single-Mode Optical Fiber", *IEEE Journal Of Quantum Electronics*, vol. 17, pp. 404-407, Mar. 1981.
- Toide, M. et al., "Two-Dimensional Coherent Detection Imaging in Multiple Scattering Media Based the Directional Resolution Capability of the Optical Heterodyne Method", *Applied Physics B (Photophysics and Laser Chemistry)*, vol. B52, pp. 391-394, 1991.
- Trutna, W. R. et al., "Continuously Tuned External-Cavity Semiconductor-Laser", *Journal of Lightwave Technology*, vol. 11, pp. 1279-1286, Aug. 1993.
- Uttam, Deepak et al., "Precision Time Domain Reflectometry in Optical Fiber Systems Using a Frequency Modulated Continuous Wave Ranging Technique", *Journal of Lightwave Technology*, vol. 3, pp. 971-977, Oct. 1985.
- Von Der Weid, J. P. et al., "On the Characterization of Optical Fiber Network Components with Optical Frequency Domain Reflectometry", *Journal of Lightwave Technology*, vol. 15, pp. 1131-1141, Jul. 1997.
- Wysocki, P. F. et al., "Broad-Spectrum, Wavelength-Swept, Erbium-Doped Fiber Laser at 1.55- μ m", *Optics Letters*, vol. 15, pp. 879-881, Aug. 1990.
- Youngquist, Robert C. et al., "Optical Coherence-Domain Reflectometry—A New Optical Evaluation Technique", *Optics Letters*, vol. 12, pp. 158-160, Mar. 1987.
- Yun, S. H. et al., "Wavelength-Swept Fiber Laser with Frequency Shifted Feedback and Resonantly Swept Intra-Cavity Acoustooptic Tunable Filter", *IEEE Journal of Selected Topics in Quantum Electronics*, vol. 3, pp. 1087-1096, Aug. 1997.
- Yun, S. H. et al., "Interrogation of Fiber Grating Sensor Arrays with a Wavelength-Swept Fiber Laser", *Optics Letters*, vol. 23, pp. 843-845, Jun. 1998.

(56)

References Cited

OTHER PUBLICATIONS

- Yung, K. M., "Phase-Domain Processing of Optical Coherence Tomography Images", *Journal of Biomedical Optics*, vol. 4, pp. 125-136, Jan. 1999.
- Zhou, Xiao-Qun et al., "Extended-Range FMCW Reflectometry Using an optical Loop with a Frequency Shifter", *IEEE Photonics Technology Letters*, vol. 8, pp. 248-250, Feb. 1996.
- Zorabedian, Paul et al., "Tuning Fidelity of Acoustooptically Controlled External Cavity Semiconductor-Lasers", *Journal of Lightwave Technology*, vol. 13, pp. 62-66, Jan. 1995.
- Victor S. Y. Lin et al., "A Porous Silicon-Based Optical Interferometric Biosensor", *Science Magazine*, vol. 278, pp. 840-843, Oct. 31, 1997.
- Office Action dated Dec. 6, 2006 for U.S. Appl. No. 10/997,789.
- Elliot, K. H. "The use of commercial CCD cameras as linear detectors in the physics undergraduate teaching laboratory", *European Journal of Physics* 19, 1998, pp. 107-117.
- Lauer, V. "New approach to optical diffraction tomography yielding a vector equation of diffraction tomography and a novel tomographic microscope", *Journal of Microscopy* vol. 205, Issue 2, 2002, pp. 165-176.
- Yu, P. et al. "Imaging of tumor necroses using full-frame optical coherence imaging", *Proceedings of SPIE* vol. 4956, 2003, pp. 34-41.
- Zhao, Y. et al. "Three-dimensional reconstruction of in vivo blood vessels in human skin using phase-resolved optical Doppler tomography", *IEEE Journal of Selected Topics in Quantum Electronics* 7.6 (2001): 931-935.
- Office Action dated Dec. 18, 2006 for U.S. Appl. No. 10/501,276.
- Devesa, Susan S. et al. (1998) "Changing Patterns in the Incidence of Esophageal and Gastric Carcinoma in the United States." *American Cancer Society* vol. 83, No. 10 pp. 2049-2053.
- Barr, H et al. (2005) "Endoscopic Therapy for Barrett's Oesophagus" *Gut* vol. 54:875-884.
- Johnston, Mark H. (2005) "Technology Insight: Ablative Techniques for Barrett's Esophagus—Current and Emerging Trends" www.Nature.com/clinicalpractice/gasthep.
- Falk, Gary W. et al. (1997) "Surveillance of Patients with Barrett's Esophagus for Dysplasia and Cancer with Ballon Cytology" *Gastroenterology* vol. 112, pp. 1787-1797.
- Sepchler, Stuart Jon. (1997) "Barrett's Esophagus: Should We Brush off this Balloning Problem?" *Gastroenterology* vol. 112, pp. 2138-2152.
- Froehly, J. et al. (2003) "Multiplexed 3D Imaging Using Wavelength Encoded Spectral Interferometry: A Proof of Principle" *Optics Communications* vol. 222, pp. 127-136.
- Kubba A.K. et al. (1999) "Role of p53 Assessment in Management of Barrett's Esophagus" *Digestive Disease and Sciences* vol. 44, No. 4, pp. 659-667.
- Reid, Brian J. (2001) "p53 and Neoplastic Progression in Barrett's Esophagus" *The American Journal of Gastroenterology* vol. 96, No. 5, pp. 1321-1323.
- Sharma, P. et al. (2003) "Magnification Chromoendoscopy for the Detection of Intestinal Metaplasia and Dysplasia in Barrett's Oesophagus" *Gut* vol. 52, pp. 24-27.
- Kuipers E.J et al. (2005) "Diagnostic and Therapeutic Endoscopy" *Journal of Surgical Oncology* vol. 92, pp. 203-209.
- Georgakoudi, Irene et al. (2001) "Fluorescence, Reflectance, and Light-Scattering Spectroscopy for Evaluating Dysplasia in Patients with Barrett's Esophagus" *Gastroenterology* vol. 120, pp. 1620-1629.
- Adrain, Alyn L. et al. (1997) "High-Resolution Endoluminal Sonography is a Sensitive Modality for the Identification of Barrett's Meaplasia" *Gastrointestinal Endoscopy* vol. 46, No. 2, pp. 147-151.
- Canto, Marcia Irene et al (1999) "Vital Staining and Barrett's Esophagus" *Gastrointestinal Endoscopy* vol. 49, No. 3, part 2, pp. 12-16.
- Evans, John A. et al. (2006) "Optical Coherence Tomography to Identify Intramucosal Carcinoma and High-Grade Dysplasia in Barrett's Esophagus" *Clinical Gastroenterology and Hepatology* vol. 4, pp. 38-3.
- Poneros, John M. et al. (2001) "Diagnosis of Specialized Intestinal Metaplasia by Optical Coherence Tomography" *Gastroenterology* vol. 120, pp. 7-12.
- Ho, W. Y. et al. (2005) "115 KHz Tuning Repetition Rate Ultrahigh-Speed Wavelength-Swept Semiconductor Laser" *Optics Letters* col. 30, No. 23, pp. 3159-3161.
- Brown, Stanley B. et al. (2004) "The Present and Future Role of Photodynamic Therapy in Cancer Treatment" *The Lancet Oncology* vol. 5, pp. 497-508.
- Boogert, Jolanda Van Den et al. (1999) "Endoscopic Ablation Therapy for Barrett's Esophagua with High-Grade Dysplasia: A Review" *The American Journal of Gastroenterology* vol. 94, No. 5, pp. 1153-1160.
- Sampliner, Richard E. et al. (1996) "Reversal of Barrett's Esophagus with Acid Suppression and Multipolar Electrocoagulation: Preliminary Results" *Gastrointestinal Endoscopy* vol. 44, No. 5, pp. 532-535.
- Sampliner, Richard E. (2004) "Endoscopic Ablative Therapy for Barrett's Esophagus: Current Status" *Gastrointestinal Endoscopy* vol. 59, No. 1, pp. 66-69.
- Soetikno, Roy M. et al. (2003) "Endoscopic Mucosal resection" *Gastrointestinal Endoscopy* vol. 57, No. 4, pp. 567-579.
- Ganz, Robert A. et al. (2004) "Complete Ablation of Esophageal Epithelium with a Balloon-based Bipolar Electrode: A Phased Evaluation in the Porcine and in the Human Esophagus" *Gastrointestinal Endoscopy* vol. 60, No. 6, pp. 1002-1010.
- Pfefer, Jorje et al. (2006) "Performance of the Aer-O-Scope, A Pneumatic, Self Propelling, Self Navigating Colonoscope in Animal Experiments" *Gastrointestinal Endoscopy* vol. 63, No. 5, pp. AB223.
- Overholt, Bergein F. et al. (1999) "Photodynamic Therapy for Barrett's Esophagus: Follow-Up in 100 Patients" *Gastrointestinal Endoscopy* vol. 49, No. 1, pp. 1-7.
- Vogel, Alfred et al. (2003) "Mechanisms of Pulsed Laser Ablation of Biological Tissues" *American Chemical Society* vol. 103, pp. 577-644.
- McKenzie, A. L. (1990) "Physics of Thermal Processes in Laser-Tissue Interaction" *Phys. Med. Biol.* 35, No. 9, pp. 1175-1209.
- Anderson, R. Rox et al. (1983) "Selective Photothermolysis Precise Microsurgery by Selective Absorption of Pulsed Radiation" *Science* vol. 220, No. 4596, pp. 524-527.
- Jacques, Steven L. (1993) "Role of Tissue Optics and Pulse Duration on Tissue Effects During High-Power Laser Irradiation" *Applied Optics* vol. 32, No. 13, pp. 2447-2454.
- Nahen, Kester et al. (1999) "Investigations on Acosustic On-Line Monitoring of IR Laser Ablation of burned Skin" *Lasers in Surgery and Medicine* vol. 25, pp. 69-78.
- Jerath, Maya R. et al. (1993) "Calibrated Real-Time Control of Lesion Size Based on Reflectance Images" *Applied Optics* vol. 32, No. 7, pp. 1200-1209.
- Jerath, Maya R. et al (1992) "Dynamic Optical Property Changes: Implications for Reflectance Feedback Control of Photocoagulation" *Journal of Photochemical, Photobiology. B; Biol* vol. 16, pp. 113-126.
- Deckelbaum, Lawrence I. (1994) "Coronary Laser Angioplasty" *Lasers in Surgery and Medicine* vol. 14, pp. 101-110.
- Kim, B.M. et al. (1998) "Optical Feedback Signal for Ultrashort Laser Pulse Ablation of Tissue" *Applied surface Science* vol. 127-129, pp. 857-862.
- Brinkman, Ralf et al. (1996) "Analysis of Cavitation Dynamics During Pulsed Laser Tissue Ablation by Optical On-Line Monitoring" *IEEE Journal of Selected Topics in Quantum Electronics* vol. 2, No. 4, pp. 826-835.
- Whelan, W.M. et al. (2005) "A novel Strategy for Monitoring Laser Thermal Therapy Based on Changes in Optothermal Properties of Heated Tissues" *International Journal of Thermophysics* vol. 26., No. 1, pp. 233-241.
- Thomsen, Sharon et al. (1990) "Microscopic Correlates of Macroscopic Optical Property Changes During Thermal Coagulation of Myocardium" *SPIE* vol. 1202, pp. 2-11.
- Khan, Misban Huzaira et al. (2005) "Intradermally Focused Infrared Laser Pulses: Thermal Effects at Defined Tissue Depths" *Lasers in Surgery and Medicine* vol. 36, pp. 270-280.

(56)

References Cited

OTHER PUBLICATIONS

- Neumann, R.A. et al. (1991) "Enzyme Histochemical Analysis of Cell Viability After Argon Laser-Induced Coagulation Necrosis of the Skin" *Journal of the American Academy of Dermatology* vol. 25, No. 6, pp. 991-998.
- Nadkarni, Seemantini K. et al. (2005) "Characterization of Atherosclerotic Plaques by Laser Speckle Imaging" *Circulation* vol. 112, pp. 885-892.
- Zimnyakov, Dmitry A. et al. (2002) "Speckle-Contrast Monitoring of Tissue Thermal Modification" *Applied Optics* vol. 41, No. 28, pp. 5989-5996.
- Morelli, J.G., et al. (1986) "Tunable Dye Laser (577 nm) Treatment of Port Wine Stains" *Lasers in Surgery and Medicine* vol. 6, pp. 94-99.
- French, P.M.W. et al. (1993) "Continuous-wave Mode-Locked Cr⁴⁺: YAG Laser" *Optics Letters* vol. 18, No. 1, pp. 39-41.
- Sennaroglu, Alphan et al. (1995) "Efficient Continuous-Wave Chromium-Doped YAG Laser" *Journal of Optical Society of America* vol. 12, No. 5, pp. 930-937.
- Bouma, B et al. (1994) "Hybrid Mode Locking of a Flash-Lamp-Pumped Ti: Al₂O₃ Laser" *Optics Letters* vol. 19, No. 22, pp. 1858-1860.
- Bouma, B et al. (1995) "High Resolution Optical Coherence Tomography Imaging Using a Mode-Locked Ti: Al₂O₃ Laser Source" *Optics Letters* vol. 20, No. 13, pp. 1486-1488.
- Fernández, Cabrera Delia et al. "Automated detection of retinal layer structures on optical coherence tomography images", *Optics Express* vol. 13, No. 25, Oct. 4, 2005, pp. 10200-10216.
- Ishikawa, Hiroshi et al. "Macular Segmentation with Optical coherence tomography", *Investigative Ophthalmology & Visual Science*, vol. 46, No. 6, Jun. 2005, pp. 2012-2017.
- PCT International Search Report and Written Opinion for Application No. PCT/US2006/031905 dated May 3, 2007.
- PCT International Search Report and Written Opinion for Application No. PCT/US2007/060481 dated May 23, 2007.
- PCT International Search Report and Written Opinion for Application No. PCT/US2007/060717 dated May 24, 2007.
- PCT International Search Report and Written Opinion for Application No. PCT/US2007/060319 dated Jun. 6, 2007.
- D. Yelin et al., "Three-dimensional imaging using spectral encoding heterodyne interferometry", *Optics Letters*, Jul. 15, 2005, vol. 30, No. 14, pp. 1794-1796.
- Office Action dated Feb. 2, 2007 for U.S. Appl. No. 11/174,425.
- Office Action dated Mar. 28, 2007 for U.S. Appl. No. 11/241,907.
- Office Action dated May 23, 2007 for U.S. Appl. No. 10/406,751.
- Office Action dated May 23, 2007 for U.S. Appl. No. 10/551,735.
- European Patent Office Search report for Application No. 01991092.6-2305 dated Jan. 12, 2006.
- Office Action dated Oct. 11, 2007 for U.S. Appl. No. 11/534,095.
- Office Action dated Oct. 9, 2007 for U.S. Appl. No. 09/709,162.
- Notice of Allowance dated Oct. 3, 2007 for U.S. Appl. No. 11/225,840.
- Siavash Yazdanfar et al., "In Vivo imaging in blood flow in human retinal vessels using color Doppler optical coherence tomography", *SPIE*, 1999 vol. 3598, pp. 177-184.
- Office Action dated Oct. 30, 2007 for U.S. Appl. No. 11/670,069.
- Hariri, Lida P. et al. "Endoscopic Optical Coherence Tomography and Laser-Induced Fluorescence Spectroscopy in a Murine Colon Cancer Model", *Laser in Surgery and Medicine*, vol. 38, 2006, pp. 305-313.
- Akiba, Masahiro et al. "En-face optical coherence imaging for three-dimensional microscopy", *SPIE*, 2002, pp. 8-15.
- Office Action dated Aug. 10, 2007 for U.S. Appl. No. 10/997,789.
- PCT International Search Report and Written Opinion for Application No. PCT/US2007/060657 dated Aug. 13, 2007.
- Lewis, Neil E. et al., "Applications of Fourier Transform Infrared Imaging Microscopy in Neurotoxicity", *Annals New York Academy of Sciences*, pp. 234-246.
- Joo, Chulmin et al., "Spectral-domain optical phase microscopy for quantitative phase-contrast imaging", *Optics Letters*, Aug. 15, 2005, vol. 30, No. 16, pp. 2131-2133.
- Guo, Bujin et al., "Laser-based mid-infrared reflectance imaging of biological tissues", *Optics Express*, Jan. 12, 2004, vol. 12, No. 1, pp. 208-219.
- PCT International Search Report and Written Opinion for Application No. PCT/US2007/061815 dated Aug. 2, 2007.
- Sir Randall, John et al., "Brillouin scattering in systems of biological significance", *Phil. Trans. R. Soc. Lond. A* 293, 1979, pp. 341-348.
- Takagi, Yasunari, "Application of a microscope to Brillouin scattering spectroscopy", *Review of Scientific Instruments*, No. 12, Dec. 1992, pp. 5552-5555.
- Lees, S. et al., "Studies of Compact hard Tissues and Collagen by Means of Brillouin Light Scattering", *Connective Tissue Research*, 1990, vol. 24, pp. 187-205.
- Berovic, N. "Observation of Brillouin scattering from single muscle fibers", *European Biophysics Journal*, 1989, vol. 17, pp. 69-74.
- PCT International Search Report and Written Opinion for Application No. PCT/US2007/062465 dated Aug. 8, 2007.
- Pyhtila John W. et al., "Rapid, depth-resolved light scattering measurements using Fourier domain, angle-resolved low coherence interferometry", *Optics Society of America*, 2004.
- Pyhtila John W. et al., "Determining nuclear morphology using an improved angle-resolved low coherence interferometry system", *Optics Express*, Dec. 15, 2003, vol. 11, No. 25, pp. 3473-3484.
- Desjardins A.E., et al., "Speckle reduction in OCT using massively-parallel detection and frequency-domain ranging", *Optics Express*, May 15, 2006, vol. 14, No. 11, pp. 4736-4745.
- Nadkarni, Seemantini K., et al., "Measurement of fibrous cap thickness in atherosclerotic plaques by spatiotemporal analysis of laser speckle images", *Journal of Biomedical Optics*, vol. 11 Marsh/Apr. 2006, pp. 02106-1-8.
- PCT International Search Report and Written Opinion for Application No. PCT/US2007/066017 dated Aug. 30, 2007.
- Yamanari M. et al., "Polarization sensitive Fourier domain optical coherence tomography with continuous polarization modulation", *Proc. of SPIE*, vol. 6079, 2006.
- Zhang Jun et al., "Full range polarization-sensitive Fourier domain optical coherence tomography", *Optics Express*, Nov. 29, 2004, vol. 12, No. 24, pp. 6033-6039.
- PCT International Search Report and Written Opinion for Application No. PCT/US2007/060670 dated Sep. 21, 2007.
- J. M. Schmitt et al., "Speckle in Optical Coherence Tomography: An Overview", *SPIE* vol. 3726, pp. 450-461.

* cited by examiner




Figure 1a




Figure 1b




Figure 1c




Figure 1d

Figure 2a








Figure 2b



**Figure 3**

**Figure 4**






Figure 6a




Figure 6b




Figure 7




Figure 8




Figure 9




Figure 10

SYSTEM AND METHOD FOR OPTICAL COHERENCE IMAGING

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

[CROSS-REFERENCE TO RELATED APPLICATION(S)] CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation reissue application of, and therefore claims priority from, U.S. application Ser. No. 12/323,228, filed on Nov. 25, 2008 (issued as U.S. Pat. No. Re. 43,875—the “228 Application”), which is a reissue of U.S. Pat. No. 7,366,376, that issued on Apr. 29, 2008 from U.S. application Ser. No. 11/241,907, filed on Sep. 29, 2005. The present [invention] application also claims priority from U.S. patent application Ser. No. 60/614,228 filed on Sep. 29, 2004[the]. The entire [disclosure of which] disclosures of these applications are incorporated herein by reference.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH

The invention was made with the U.S. Government support under Grant Number DAMD17-99-2-9001 awarded by the U.S. Department of the Army. Thus, the U.S. Government has certain rights in the invention.

FIELD OF THE INVENTION

The present invention relates generally to imaging probes and systems for imaging biological samples, and more particularly, to optical fiber probes and optical imaging systems which are capable of using such probes for imaging of the biological samples.

BACKGROUND INFORMATION

In vivo optical imaging of internal organs of a patient is commonly performed through a fiber-optic catheter. Many clinical areas such as cardiology, interventional radiology and gastroenterology require a small diameter, rotating optical probe or catheter to generate r-□ cross-sectional images. In addition, the rotating catheter may be pulled back along a longitudinal direction to obtain three dimensional images of the tissue volume of interest. For this application, a catheter providing a focused optical beam and connectivity to the imaging system may be an important device. The optical imaging system can include optical frequency domain imaging and optical coherence tomography.

Generally, ideal characteristics of fiber-optic catheters may include: a) a narrow diameter, b) a high flexibility, and c) a low optical aberration. Since an optical fiber can easily be produced with a diameter less than 250 μm, fiber-optic probes have the potential for minimally invasive access to small vessels and narrow spaces within living subjects. Typically, catheters are directed to locations of interest through the use of a guide-wire that is placed under fluoroscopic guidance. To achieve compatibility with the guide-wire, and additionally to protect the optical fiber, catheters typically utilize an outer transparent sheath. The optical fiber can be placed inside of

the sheath and is free to rotate or translate longitudinally. Light transmitted through the fiber is directed to a path perpendicular to the longitudinal axis of the catheter and focused to a point outside of the sheath, within the tissue of interest. As the light propagates through the sheath, its focal properties are modified by refraction at the inner and outer surface of the sheath. In other words, the sheath acts as a lens. Due to the cylindrical shape of the sheath, however, its lens characteristics may be undesirable and, in particular, can introduce significant aberrations. One of the most significant aberrations of the sheath is astigmatism, an effect that increases dramatically when using narrow diameter sheaths. Light rays passing through an optical element having astigmatism would exhibit two distinct foci, one focus for rays in the sagittal plane and another focus for rays in the orthogonal, tangential plane. An arrangement (e.g., a catheter) that overcomes this limitation would improve optical imaging, and may have widespread applications in medicine and biology, in particular.

One approach to overcome astigmatism introduced by the sheath can be to match the index of refraction of the sheath with the medium outside of an inside of the sheath. For biological imaging, this can be approximated by using a sheath having an index of refraction approximately equal to that of water, and to fill the lumen of the sheath with water or a substance of approximately equal index of refraction. It is highly desirable for the optical imaging catheter to enable both rotation and longitudinal pull-back of the components internal to the sheath. Although a rotation of the internal components within a water-filled sheath is possible, a longitudinal pull-back is problematic due to the viscosity of the fluid and turbulence. A more desirable solution may be to compensate the astigmatism of the sheath using other optical components, and to operate the catheter with air or another gas occupying the void between the internal components and the sheath.

It is known in the art that miniature lenses, having diameters approximately equal to that of standard optical communications fibers, can be used to shape the light emitted from an optical fiber to form a focal spot external to the fiber. It is also well-known that these devices can collect light from a focal spot and transmit that light backward through the optical fiber.

FIGS. 1a-1d show exemplary conventional configurations for combining miniature lenses and optical fiber. For example, in order to achieve a small package size, approximately equal to the diameter of optical fibers (less than approximately 500 μm), a gradient-index (GRIN or SEL-FOC) lens 25 is typically used. Commonly, the protective outer layer 10 of a glass optical fiber is partially stripped back from an end of the fiber 15, and a lens 25 is fixed to the fiber using optical adhesive or optical epoxy. In the case of a gradient-index lens, light emitted from the core 20 of the fiber follows a path whose marginal rays 30 describe a sinusoid. Through an appropriate selection of the index-of-refraction profile in the material of the lens and the lens length, the focal properties of the light emitted from the lens can be controlled. A common configuration for such a lens-fiber combination provides a focal spot 35 at a predetermined distance from the distal face of the lens. In addition to a lens, a beam deflector such as a prism 90 can be used to redirect the light 85 emitted from the lens to illuminate a focus 80 located transversely with respect to the axis of the fiber. In order to minimize a back-reflection from the lens and to improve the mechanical integrity of the device, the lens may be directly bonded or fusion spliced to the optical fiber. Alternatively, a spacer 105 that includes a glass cylinder of homogeneous index of refraction can be inserted between the fiber 100 and the lens 115 to

3

allow for beam expansion **110** prior to focusing. A prism or beam deflector **120** can further be used to redirect the beam to a focal spot **125** located at a position with a transverse offset with respect to the axis of the fiber.

For each of the probes illustrated in FIGS. 1a-1c, the length of the lens and spacer must be carefully controlled and the elements carefully aligned to achieve the desired focal characteristics for a specific application. As a result, such probes are difficult to manufacture. Additionally, these designs lack mechanical integrity and require an additional structure, such as an outer protective sleeve, to avoid mechanical failure. This requirement may result in a larger probe diameter and longer rigid length than otherwise might be possible.

Ball lenses that include a single spherical particle of glass can alternatively be used to produce a focus from light emitted from an optical fiber. In this case, as shown in FIG. 1d, the light **130** emitted from the fiber is refracted at the surface of the sphere **135**. The ball lens can be positioned at the distal end of the fiber or can be formed directly from the material of the fiber by controlled heating and melting of the glass. During the heating process, a portion of the light-guiding core of the fiber **125** can be destroyed and the light can diffract to a larger beam size at the ball-lens external surface **135** producing improved focal characteristics **140**. An important aspect of the device shown in FIG. 1 is that the ball lens is fabricated by melting and reforming the distal end of an optical fiber is that the surface of the ball is approximately spherical over the portion where light is transmitted. Additionally, a beam deflector such as a prism cannot be directly bonded to the spherical surface of the ball lens, thus requiring an additional housing for its positioning and mechanical fixture.

Therefore, there is a need to overcome at least some of the deficiencies described herein above.

SUMMARY OF THE INVENTION

In order to overcome at least some of the deficiencies described above, exemplary embodiments of sculptured optical fiber probes and optical imaging systems that use such probes can be provided for performing imaging of a biological sample according to the present invention. In one exemplary embodiment, the probe can be used to provide a focused optical beam with light from the imaging system, to collect light reflected from the biological sample, convey it back to the imaging system, as well as to scan the focused optical beam across the biological sample in two or three spatial dimensions. The application of the imaging system using the sculptured optical probe according to the present invention can include intravascular imaging, cardio vascular imaging, and gastrointestinal tract imaging.

According to an exemplary embodiment of the present invention, apparatus and method are provided for transmitting at least one electro-magnetic radiation is provided. In particular, at least one optical fiber having at least one end extending along a first axis may be provided. Further, a light transmissive optical arrangement may be provided in optical cooperation with the optical fiber. The optical arrangement may have a first surface having a portion (e.g., a planar portion) that is perpendicular to a second axis, and a second surface which includes a curved portion. The first axis can be provided at a particular angle that is more than 0° and less than 90° with respect to the second axis.

In one exemplary embodiment of the present invention, the portion may be adapted to at least partially reflect at least one portion of the at least one electro-magnetic radiation, and the curved portion can be adapted to transmit the at least one portion of the at least one electro-magnetic radiation there

4

through. The curved portion may have a first curvature in a first plane perpendicular to the first axis, and a second curvature in a second plane perpendicular to a third axis. For example, the first plane can be different from the second plane, and the first curvature may be different from the second curvature. A further angle between the first axis and the third axis may be approximately 90°.

According to another exemplary embodiment of the present invention, the particular angle may be at least an angle for a total internal reflection between the light transmissive optical arrangement and a medium external thereto. The portion of the first surface may be a reflective surface and/or may have a metal layer. Further, the optical fiber and the light transmissive optical arrangement may be formed as a single piece from the same material. The optical fiber can have at least one first region and at least one second region, the first region being adapted to guide the at least one electro-magnetic radiation, and the second region having non-guiding properties of the at least one electro-magnetic radiation. Further, the first and second regions can be positioned along the first axis.

A sheath having a substantially transparent portion may be provided, and the light transmissive optical arrangement may be arranged within the substantially transparent portion. In addition, the first and second curvatures may have properties which effectuate a reduction of astigmatism caused by the substantially transparent portion. The first and second curvatures may have properties which effectuate a reduction of astigmatism. The optical fiber may include first and second optical fibers, one of which can be rotated (e.g., at a substantially uniform rotational speed of greater than about 30 revolutions per second). A translation stage configured to translate at least one of the first and second optical fibers can be provided along a longitudinal direction. The first and/or second optical fibers may be single mode fibers with a nominal cutoff wavelength. The nominal cutoff wavelength of the first and/or second optical fibers may be between about 900 nm and 1300 nm.

According to another exemplary embodiment of the present invention, the first and second curvatures may have properties which effectuate a reduction of astigmatism. The optical fiber may include first and second optical fibers, and the first optical fiber and/or the second optical fiber may be at least partially rotated. A translation stage may be provided which is configured to translate the first optical fiber and/or the second optical fiber approximately along the first axis. The light transmissive optical arrangement can be configured to concentrate the electro-magnetic radiation at a focal point which is provided outside of the apparatus. The first and second curvatures may have properties which effectuate a reduction of astigmatism at the focal point.

These and other objects, features and advantages of the present invention will become apparent upon reading the following detailed description of embodiments of the invention, when taken in conjunction with the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

Further objects, features and advantages of the invention will become apparent from the following detailed description taken in conjunction with the accompanying figures showing illustrative embodiments of the invention, in which:

FIG. 1a is a diagram of a conventional arrangement of miniature lenses and beam directors which includes a gradient-index lens for focusing light from an optical fiber;

5

FIG. 1b is a diagram of a conventional arrangement of miniature lenses and beam directors which includes a gradient-index lens and prism for focusing light from the optical fiber;

FIG. 1c is a diagram of a conventional arrangement of miniature lenses and beam directors which includes a gradient-index lens and prism with a spacer between the fiber and the lens for focusing light from the optical fiber;

FIG. 1d is a diagram of a conventional arrangement of miniature lenses and beam directors which includes a ball lens formed by heating tip of optical fiber for focusing light from the optical fiber.

FIG. 2a is a side longitudinal side view of an exemplary embodiment of a sculptured tip optical fiber probe for imaging according to the present invention; and

FIG. 2b is a cross-sectional view of the probe shown in FIG. 2a;

FIG. 3 is a graph of exemplary calculations of probe parameters to achieve a desired focal distance in air;

FIG. 4 is a graph of exemplary calculations of probe parameters to achieve a desired focal distance in water;

FIG. 5a is a schematic diagram illustrating a first exemplary fabrication step for producing the exemplary sculptured tip fiber probe according to the present invention;

FIG. 5b is a schematic diagram illustrating a second exemplary fabrication step for producing the sculptured tip fiber probe according to the present invention;

FIG. 5c is a schematic diagram illustrating a third exemplary fabrication step for producing the sculptured tip fiber probe according to the present invention;

FIG. 5d is a schematic diagram illustrating a fourth exemplary fabrication step for producing the sculptured tip fiber probe according to the present invention;

FIG. 5e is a schematic diagram illustrating a fifth exemplary fabrication step for producing the sculptured tip fiber probe according to the present invention;

FIG. 6a is an exemplary image of the exemplary probe according to the present invention after a ball lens thereof is formed;

FIG. 6b is an exemplary image of the exemplary probe according to the present invention after polishing an angled facet of the ball lens;

FIG. 7 is an exemplary image of human skin in vivo acquired using the probe shown in FIGS. 6a and 6b;

FIG. 8 is an illustration of an exemplary embodiment of a rotary junction according to the present invention which can be used with the probe shown in FIGS. 6a and 6b;

FIG. 9 is a block diagram of an exemplary embodiment of an optical system based on optical frequency domain imaging which is adapted to utilize the probe of FIGS. 6a and 6b; and

FIG. 10 is a block diagram of an exemplary embodiment of an optical system based on spectral-domain optical coherence tomography which is adapted to utilize the probe of FIGS. 6a and 6b.

Throughout the drawings, the same reference numerals and characters, unless otherwise stated, are used to denote like features, elements, components, or portions of the illustrated embodiments. Moreover, while the present invention will now be described in detail with reference to the Figures, it is done so in connection with the illustrative embodiments.

DETAILED DESCRIPTION

FIG. 2 depicts an exemplary embodiment of a sculptured tip optical fiber probe according to the present invention. Features of this exemplary embodiment of the probe can include an optical fiber 150 (e.g., preferably a single-mode

6

fiber), in which a distal end of the optical fiber can include a portion of a prolate spheroidal ball 160, monolithic with the fiber. A prolate spheroid may be characterized by a sphere that has been pulled or extended along an axis separating its poles. Over a predetermined (e.g., small) portion 195 of the surface of the ball 160, the surface can be characterized as having two distinct radii of curvature, R_1 170 and R_2 180 (as shown in a side view of FIG. 2a, and an end view of FIG. 2b) of the fiber distal end. The radius of curvature R_1 170 is greater than the physical radius R_b 172 of the ball. The radius of curvature R_2 180 is approximately equivalent to the physical radius 172.

The distal end of the fiber can be further characterized by an approximately flat surface 190 oriented at an angle with respect to the axis of the fiber. The surface 190 is configured to deflect light emitted from the fiber (denoted as the dashed line in FIG. 2a) so that the light passes through a surface of the ball 195 to a focus 200. The distal end of the fiber is further characterized by a region 210 in which the light-to guiding core 155 of the fiber is absent so as to allow light from the core to diffract, and thus illuminate a significant fraction of the surface 195. The region 210, having a particular length (L) 215, can be fabricated through a destruction procedure of the core by heat or by fusion splicing a core-less fiber to an end of a fiber having a light-guiding core. In the latter case, the ball lens 160 and surface 190 can be fabricated from the material of the core-less fiber. Specific methods for fabricating the exemplary probe shown in FIGS. 2a and 2b, and for controlling the radii of curvature 170, 180 are described as follows.

The exemplary embodiment of the probe shown in FIGS. 2a and 2b provide certain desired characteristics, e.g., the radii of curvature 170, 180 are distinct and independently controllable in the fabrication process. This attribute is advantageous since it permits for a compensation of astigmatism introduced by the catheter sheath. As light passes through a spherical surface, it likely experiences a refraction. The effective focal length of for collimated light refracted by transmission through a spherical surface is given by the equation

$$f = \frac{n_m R}{n_b - n_m},$$

where n_m is the index of refraction of the medium outside the surface, n_b is the index of refraction inside the surface and R is the radius of curvature. The effective focal length for the exemplary probe shown in FIGS. 2a and 2b may have two distinct values; one associated with R_1 and another associated with R_2 .

Through an appropriate selection of R_1 and R_2 , the focal length difference between the sagittal and tangential plane rays that results from the sheath can be compensated, and an astigmatism-free focus, external to the sheath, can be produced. For biomedical imaging, the catheter may be immersed in tissue or fluid having an index of refraction approximately equal to that of water. In such case, with air inside the sheath, the refractive power of the sheath is negative. In other words, the sheath can act to defocus the light propagating across it. The refractive power of the sheath, however, may act, e.g., only along one axis. Along the longitudinal axis of the sheath, there is likely no refractive power. An exemplary design for the probe likely has $R_1 > R_2$.

The effective focal length of the surface 190 can also be determined by the separation of L 215 between the light guiding core 155 and the surface 190, in addition to the radii of curvature 170, 180. FIG. 3 shows a graph of an exemplary calculation representing pairs of exemplary acceptable values

7

for L and R that can yield various focal distances. The dependent axis **250** of FIG. **3** represents the difference between L and R in units of microns, and the horizontal axis **252** represents two-times the value of R in units of microns. Each of the curves of this figure represent different focal distances: 1.0 mm (label **254**), 1.5 mm (label **256**), 2.0 mm (label **258**), 2.5 mm (label **260**), 3.0 mm (label **262**), and 50 mm (label **264**). The exemplary calculation the results of which are shown in FIG. **3** can be based on a probe made from fused silica surrounded by air.

FIG. **4** depicts an exemplary graph of a similar calculation in which an exemplary fused silica probe may be immersed in water. The dependent axis **266** of FIG. **4** represents the difference between L and R in units of microns and the horizontal axis **268** represents two-times the value of R in units of microns. Each of the curves of this figure represent different focal distances: 1.0 mm (label **270**), 1.5 mm (label **272**), 2.0 mm (label **274**), 2.5 mm (label **276**), 3.0 mm (label **280**), and 50 mm (label **282**).

FIGS. **5a-5e** depict exemplary products produced by fabrications steps which can be used to produce the example embodiment of the optical imaging probe shown in FIGS. **2a** and **2b**. Standard telecommunications fiber (e.g., SMF-28 shown in FIG. **5a**) can include a protective acrylic jacket **300** having a diameter of 250 μm , a glass cladding **305** having a diameter of 125 μm , and a light-guiding core **310**, in which the mode-field diameter can nominally be 9 μm . The fabrication of the exemplary imaging probe can begin by stripping off a section of the acrylic jacket to expose the glass cladding (see FIG. **5a**). A length of homogeneous glass fiber **315** having, e.g., the same diameter as the SMF-28 cladding can then be fusion-spliced to the fiber **305** and cleaved to a predetermined length (see FIG. **5b**).

The fiber fusion-splicing procedure is well-known in the art as a method for affixing two optical fibers while introducing low insertion loss and back-reflection. Fusion splicing fibers of dissimilar diameters can also be performed in cases where a more significant beam expansion is desirable. A ball lens **325** can be produced at the end of the homogeneous glass fiber **315** (see FIG. **5c**), e.g., using a fiber fusion workstation, such as Vytran FFS-2000. Parameters including temperature, duration and insertion rate determine the volume of the fiber tip **320** that is melted. In this manner, the radius **330** of the resulting ball and the distance **335** between the center of the ball and the splice between the homogeneous fiber **320** and the light-guiding fiber **340** can be ascertained. Following the formation of the ball, the distal end of probe can be polished to produce an angled face **345** (see FIG. **5d**). Machines for polishing optical fiber and miniature optical components are readily available, and can produce high-quality optical surface with high-degrees of flatness and smoothness.

The angle **350** used for the exemplary graph of FIG. **3** can be selected so that all rays of light emitted from the single mode fiber **305** may be incident upon the polished surface **345** at an angle **350** that is greater than that of total internal reflection. For this exemplary configuration, the surface **345** can act as a nearly perfect reflector, deflecting the light to the upper surface **325** of the ball. Alternatively, the angle can be arbitrarily determined, and a coating such as gold or aluminum may be used to achieve a high degree of reflectivity from the face **345**. In the case of an applied coating, the distal tip of the probe can be protected by applying an acrylic coat **355** as, e.g., a final fabrication step (see FIG. **5e**).

FIGS. **6a** and **6b** show exemplary images which can illustrate various stages of the formation/fabrication of the exemplary embodiment of the probe according to the present invention. For example, the image of FIG. **6a** may approxi-

8

mately correspond to the illustration of FIG. **5c** following the formation of the ball **370** at a distal end of a fiber **375**. In addition, the image of FIG. **6b** may approximately correspond to the illustration of FIG. **5d** following the polishing of the ball **370** to create an angled face **380**.

FIG. **7** shows an exemplary optical coherence tomography ("OCT") image which can be acquired using the exemplary probe shown in FIGS. **6a** and **6b**. The sample in FIG. **7** is a ventral portion of a finger of a human subject. The upper most thin, dark layer **400** corresponds to the stratum corneum, the lighter region just below the stratum corneum corresponds to the epidermis **410** and the dark underlying band **420** to the dermis.

For intravascular or intraluminal imaging, an exemplary catheter shown in FIG. **2a** can be used in conjunction with an optical rotary junction permitting rotation. FIG. **8** shows an exemplary embodiment of a rotary junction using a pair of collimators, **12** and **18** which can be used with the exemplary probe shown in FIGS. **2a** and **2b**. One of the collimating lenses **18** can be attached (either directly or indirectly) to a tubular structure **26**. The distal end of the fiber **21** may be inserted into a connector ferrule **28** which is positioned inside a sleeve **34**. A matching connector with a connector housing case **33** and ferrule **32** can be inserted to the sleeve **34**.

This exemplary arrangement facilitates an optical transmission between two fibers **21**, **31**. The tubular structure **26** is connected to a housing **39** via a bearing **36**. The tubular structure **26** may also be connected to a rotational motor **37** via a belt or gear **38**. The motor **37** can rotate the tubular structure **26** and thereby the collimator **18**. The housing **39** may be mounted to a translation stage **40** that is provided on a stationary rail **41**, e.g., for a pull-back operation. The rotary junction provides optical transmission between a non-rotating fiber **11** and a rotating fiber **31** while permitting an interchange of the alternate fibers **31** at the connector housing **33**.

In one exemplary embodiment of the present invention, the optical fibers **11**, **21**, **31** can be single mode optical fibers. According to other exemplary embodiments of the present invention, each of the fibers **11**, **21**, **31** may be a multimode fiber, a polarization maintaining fiber, and/or a photonic crystal fiber. The fibers **11**, **21** can be fused to the lenses **12**, **18**, thus dramatically reducing a back-reflection and increasing throughput. The collimating lenses **12**, **18** may alternately be aspheric refractive lenses or axial gradient index lenses. The optics surfaces of the lenses **12**, **18** may be antireflection coated at an operating wavelength range of light. The wavelength range includes 800+/-100 nm, 1000-1300 nm, or 1600-1800 nm. The focal length of the lenses **12**, **18** can be selected to provide a beam diameter of about 100 μm to 1000 μm . The overall throughput from the fibers **11**, **21**, **31** can typically be greater than 70%, and the back-reflection may be less than -55 dB.

The tubular structure **26** may be a hollow motor shaft and the motor **37** is positioned coaxially to the tubular structure **26**; e.g., the belt or gear **38**, may not be needed. The polishing angle of the connectors **28**, **32** can be between about 4 degrees and 10 degrees with respect to the surface normal to minimize back reflection. The connector housing **33** preferably provides a snap-one connection, e.g., similar to the SC type and may be equipped with a built-in end-protection gate.

FIG. **9** shows an exemplary embodiment of an optical frequency domain imaging ("OFDI") system which can use the rotary junction and catheter as described above. For example, the light source may be a wavelength swept laser **81**. The rotary junction **39** may be connected to a sample arm of an interferometer which includes a 10/90 coupler **82**, an attenuator **84**, a polarization controller **86**, circulators **88**, **89**,

a length matching fiber 90, a collimating lens 92, and a reference mirror 94. The detection circuit may include a 50/50 coupler 96, a polarization controller 98, polarization beam splitters 99, 101, dual balanced receivers 103, 104, electrical filters 106, 107, and a data acquisition board 111. The data acquisition board 111 may be connected to a computer 112, and can be in communication with a trigger circuit 114, a motor controller 94, and the translation stage 41, 42. The operating principle of OCT is well known in the art. In order to provide dual-balanced detection and polarization diverse detection simultaneously, the polarization controller 98 is configured to allow the birefringence of the two fiber paths from the coupler to be matched. Another polarization controller 86 in the reference arm may be adjusted to split the reference light with an equal ratio at each of the polarization beam splitters 101, 102. Corresponding polarization states following the splitters, labeled x or y, can be directed to dual-balanced receivers 103, 104.

FIG. 10 shows an exemplary embodiment of a spectral-domain OCT system which is configured to be used with the rotary junction and catheter according to the present invention described above. The light source 121 may include a low coherence broadband source, a pulsed broadband source, and/or a wavelength varying source with repetition synchronized to the readout rate of a camera 122. The camera 122 can utilize a detector array 124 based on charge coupled devices and/or CMOS imager. The interference signal can be directed to the detector array 124 using a collimator 126, a diffraction element such as a grating arrangement 128, and a focusing lens 131. The operating principle of OCT is well known in the art, and are incorporated herein.

The foregoing merely illustrates the principles of the invention. Various modifications and alterations to the described embodiments will be apparent to those skilled in the art in view of the teachings herein. For example, the invention described herein is usable with the exemplary methods, systems and apparatus described in U.S. Provisional Patent Appn. No. 60/514,769 filed Oct. 27, 2003, and International Patent Application No. PCT/US03/02349 filed on Jan. 24, 2003, the disclosures of which are incorporated by reference herein in their entireties. It will thus be appreciated that those skilled in the art will be able to devise numerous systems, arrangements and methods which, although not explicitly shown or described herein, embody the principles of the invention and are thus within the spirit and scope of the present invention. In addition, all publications, patents and patent applications referenced above are incorporated herein by reference in their entireties.

What is claimed is:

[1. An apparatus for transmitting at least one electromagnetic radiation, comprising:

at least one optical fiber having at least one end extending along a first axis; and

a light transmissive optical arrangement provided in optical cooperation with the at least one optical fiber, the optical arrangement including a first surface having a portion that is approximately perpendicular to a second axis, and a second surface which includes a curved portion, wherein the first axis is provided at a particular angle that is more than 0° and less than 90° with respect to the second axis,

wherein the curved portion has a first radius of a first curvature in a first plane lying along the first and second axes, and a second radius of a second curvature in a second plane which is perpendicular to the first plane,

and wherein the first radius is different from the second radius, and wherein the first curvature is different from the second curvature.]

[2. The apparatus according to claim 1, wherein the portion is adapted to at least partially reflect at least one portion of the at least one electro-magnetic radiation, and wherein the curved portion is adapted to transmit the at least one portion of the at least one electro-magnetic radiation there through.]

[3. The apparatus according to claim 1, wherein the curved portion has a first curvature in a first plane perpendicular to the first axis, and a second curvature in a second plane perpendicular to a third axis, wherein the first plane is different from the second plane, and wherein the first curvature is different from the second curvature.]

[4. The apparatus according to claim 3, wherein a further angle between the first axis and the third axis is approximately 90°.]

[5. The apparatus according to claim 1, wherein the particular angle is at least an angle for a total internal reflection between the light transmissive optical arrangement and a medium external thereto.]

[6. The apparatus according to claim 1, wherein the portion of the first surface is a reflective surface.]

[7. The apparatus according to claim 1, wherein the portion of the first surface has a metal layer.]

[8. The apparatus according to claim 1, wherein the at least one optical fiber and the light transmissive optical arrangement are formed as a single piece from the same material.]

[9. The apparatus according to claim 1, wherein the at least one optical fiber has at least one first region and at least one second region, the first region being adapted to guide the at least one electro-magnetic radiation, and the second region having non-guiding properties of the at least one electro-magnetic radiation, and wherein the first and second regions are positioned approximately along the first axis.]

[10. The apparatus according to claim 1, wherein the second plane is provided at approximately the particular angle with respect to the second axis and at approximately twice the particular angle with respect to the first axis.]

[11. The apparatus according to claim 1, wherein the light transmissive optical arrangement is configured to concentrate the at least one electro-magnetic radiation at a focal point which is provided outside of the apparatus, and wherein the focal point is provided approximately at an intersection of the first and second planes.]

[12. An apparatus for transmitting at least one electromagnetic radiation, comprising:

at least one optical fiber having at least one end extending along a first axis;

a light transmissive optical arrangement provided in optical cooperation with the at least one optical fiber, the optical arrangement including a first surface having a portion that is approximately perpendicular to a second axis, and a second surface which includes a curved portion, wherein the first axis is provided at a particular angle that is more than 0° and less than 90° with respect to the second axis; and

a sheath having a substantially transparent portion, wherein the light transmissive optical arrangement is arranged within the substantially transparent portion.]

[13. The apparatus according to claim 12, wherein the first and second curvatures have properties which effectuate a reduction of astigmatism caused by the substantially transparent portion.]

[14. An apparatus for transmitting at least one electromagnetic radiation, comprising:

11

at least one optical fiber having at least one end extending along a first axis; and

a light transmissive optical arrangement provided in optical cooperation with the at least one optical fiber, the optical arrangement including a first surface having a portion that is approximately perpendicular to a second axis, and a second surface which includes a curved portion, wherein the first axis is provided at a particular angle that is more than 0° and less than 90° with respect to the second axis,

wherein the curved portion has a first curvature in a first plane perpendicular to the first axis, and a second curvature in a second plane perpendicular to a third axis, wherein the first plane is different from the second plane, and wherein the first curvature is different from the second curvature, and wherein the first and second curvatures have properties which effectuate a reduction of aberration.]

[15. The apparatus according to claim 14, wherein the first and second curvatures have properties which effectuate a reduction of astigmatism.]

[16. An apparatus for transmitting at least one electro-magnetic radiation, comprising:

at least one optical fiber having at least one end extending along a first axis; and

a light transmissive optical arrangement provided in optical cooperation with the at least one optical fiber, the optical arrangement including a first surface having a portion that is approximately perpendicular to a second axis, and a second surface which includes a curved portion, wherein the first axis is provided at a particular angle that is more than 0° and less than 90° with respect to the second axis, wherein the at least one optical fiber includes first and second optical fibers, and wherein at least one of the first and second optical fibers is at least partially rotated.]

[17. The apparatus according to claim 16, further comprising a translation stage configured to translate at least one of the first and second optical fibers approximately along the first axis.]

[18. An apparatus for transmitting at least one electro-magnetic radiation, comprising:

at least one optical fiber having at least one end extending along a first axis; and

a light transmissive optical arrangement provided in optical cooperation with the at least one optical fiber, the optical arrangement including a first surface having a portion that is approximately perpendicular to a second axis, and a second surface which includes a curved portion, wherein the first axis is provided at a particular angle that is more than 0° and less than 90° with respect to the second axis,

wherein the curved portion has a first curvature in a first plane perpendicular to the first axis, and a second curvature in a second plane perpendicular to a third axis, wherein the first plane is different from the second plane, and wherein the first curvature is different from the second curvature, and wherein the first and second curvatures have properties which effectuate a reduction of astigmatism at the focal point.]

[19. A method for transmitting at least one electro-magnetic radiation, comprising:

providing at least one optical fiber having at least one end extending along a first axis; and

providing a light transmissive optical arrangement provided in optical cooperation with the at least one optical fiber, the optical arrangement including a first surface

12

having a portion that is approximately perpendicular to a second axis, and a second surface which includes a curved portion, wherein the first axis is provided at a particular angle that is more than 0° and less than 90° with respect to the second axis,

wherein the curved portion has a first radius of a first curvature in a first plane lying along the first and second axes, and a second radius of a second curvature in a second plane which is perpendicular to the first plane, wherein the first radius is different from the second radius, and wherein the first curvature is different from the second curvature.]

[20. The method according to claim 19, wherein the portion is adapted to at least partially reflect at least one portion of the at least one electro-magnetic radiation, and wherein the curved portion is adapted to transmit the at least one portion of the at least one electro-magnetic radiation there through.]

[21. The method according to claim 20, wherein the curved portion has a first curvature in a first plane perpendicular to the first axis, and a second curvature in a second plane perpendicular to a third axis, wherein the first plane is different from the second plane, and wherein the first curvature is different from the second curvature.]

[22. The method according to claim 21, wherein a further angle between the first axis and the third axis is approximately 90°.]

[23. The method according to claim 19, wherein the particular angle is at least an angle for a total internal reflection between the light transmissive optical arrangement and a medium external thereto.]

[24. The method according to claim 19, wherein the portion of the first surface is a reflective surface.]

[25. The method according to claim 19, wherein the portion of the first surface has a metal layer.]

[26. The method according to claim 19, wherein the at least one optical fiber and the light transmissive optical arrangement are formed as a single piece from the same material.]

[27. The method according to claim 19, wherein the at least one optical fiber has at least one first region and at least one second region, the first region being adapted to guide the at least one electro-magnetic radiation, and the second region having non-guiding properties of the at least one electro-magnetic radiation, and wherein the first and second regions are positioned along the first axis.]

[28. The method according to claim 19, wherein the second plane is provided at approximately the particular angle with respect to the second axis and at approximately twice the particular angle with respect to the first axis.]

[29. The method according to claim 19, wherein the light transmissive optical arrangement is configured to concentrate the at least one electro-magnetic radiation at a focal point which is provided outside of the apparatus, and wherein the focal point is provided approximately at an intersection of the first and second planes.]

[30. A method for transmitting at least one electro-magnetic radiation, comprising:

providing at least one optical fiber having at least one end extending along a first axis; and

providing a light transmissive optical arrangement provided in optical cooperation with the at least one optical fiber, the optical arrangement including a first surface having a portion that is approximately perpendicular to a second axis, and a second surface which includes a curved portion, wherein the first axis is provided at a particular angle that is more than 0° and less than 90° with respect to the second axis, wherein the light trans-

13

missive optical arrangement is arranged within a substantially transparent portion of a sheath.]

[31. The method according to claim 30, wherein the first and second curvatures have properties which effectuate a reduction of astigmatism caused by the substantially transparent portion.]

[32. A method for transmitting at least one electro-magnetic radiation, comprising:

providing at least one optical fiber having at least one end extending along a first axis; and

providing a light transmissive optical arrangement provided in optical cooperation with the at least one optical fiber, the optical arrangement including a first surface having a portion that is approximately perpendicular to a second axis, and a second surface which includes a curved portion, wherein the first axis is provided at a particular angle that is more than 0° and less than 90° with respect to the second axis,

wherein the curved portion has a first curvature in a first plane perpendicular to the first axis, and a second curvature in a second plane perpendicular to a third axis, wherein the first plane is different from the second plane, and wherein the first curvature is different from the second curvature, and wherein the first and second curvatures have properties which effectuate a reduction of aberration.]

[33. The method according to claim 32, wherein the first and second curvatures have properties which effectuate a reduction of astigmatism.]

[34. A method for transmitting at least one electro-magnetic radiation, comprising:

providing at least one optical fiber having at least one end extending along a first axis; and

providing a light transmissive optical arrangement provided in optical cooperation with the at least one optical fiber, the optical arrangement including a first surface having a portion that is approximately perpendicular to a second axis, and a second surface which includes a curved portion, wherein the first axis is provided at a particular angle that is more than 0° and less than 90° with respect to the second axis, wherein the at least one optical fiber includes first and second optical fibers, and wherein one of the first and second optical fibers is at least partially rotated.]

[35. The method according to claim 34, further comprising a translation stage configured to translate at least one of the first and second optical fibers approximately along the first axis.]

[36. A method for transmitting at least one electro-magnetic radiation, comprising:

providing at least one optical fiber having at least one end extending along a first axis;

providing a light transmissive optical arrangement provided in optical cooperation with the at least one optical fiber, the optical arrangement including a first surface having a portion that is approximately perpendicular to a second axis, and a second surface which includes a curved portion, wherein the first axis is provided at a particular angle that is more than 0° and less than 90° with respect to the second axis; and

concentrating the at least one electro-magnetic radiation at a focal point which is provided outside of the apparatus, wherein the first and second curvatures have properties which effectuate a reduction of astigmatism at the focal point.]

37. An apparatus for transmitting at least one electro-magnetic radiation, comprising:

14

at least one optical fiber having at least one end extending along a first axis;

a light transmissive optical first arrangement provided in optical cooperation with the at least one optical fiber; the optical arrangement including a first surface having a portion that is approximately perpendicular to a second axis, and a second surface which includes a curved portion, wherein the first axis is provided at a particular angle that is more than 0° and less than 90° with respect to the second axis, wherein the curved portion has a first radius of a first curvature in a first plane lying along the first and second axes, and a second radius of a second curvature in a second plane which is perpendicular to the first plane, and wherein the first radius is different from the second radius, and wherein the first curvature is different from the second curvature;

at least one second arrangement in optical communication with the first arrangement, and configured at least one of transmit or receive at least one first electro-magnetic radiation to or from a sample and at least one second electro-magnetic radiation to or from a reference, wherein a frequency of at least one of the first electro-magnetic radiation or the second electro-magnetic radiation varies over time; and

at least one third arrangement configured to detect an interference between at least one third radiation associated with the at least one first radiation and at least one fourth radiation associated with the at least one second radiation.

38. The apparatus according to claim 37, wherein the portion is adapted to at least partially reflect at least one portion of the at least one electro-magnetic radiation, and wherein the curved portion is adapted to transmit the at least one portion of the at least one electro-magnetic radiation there through.

39. The apparatus according to claim 37, wherein the curved portion has a first curvature in a first plane perpendicular to the first axis, and a second curvature in a second plane perpendicular to a third axis, wherein the first plane is different from the second plane, and wherein the first curvature is different from the second curvature.

40. The apparatus according to claim 39, wherein a further angle between the first axis and the third axis is approximately 90°.

41. The apparatus according to claim 37, wherein the particular angle is at least an angle for a total internal reflection between the light transmissive optical arrangement and a medium external thereto.

42. The apparatus according to claim 37, wherein the portion of the first surface is a reflective surface.

43. The apparatus according to claim 37, wherein the portion of the first surface has a metal layer.

44. The apparatus according to claim 37, wherein the at least one optical fiber and the light transmissive optical arrangement are formed as a single piece from the same material.

45. The apparatus according to claim 37, wherein the at least one optical fiber has at least one first region and at least one second region, the first region being adapted to guide the at least one electro-magnetic radiation, and the second region having non-guiding properties of the at least one electro-magnetic radiation, and wherein the first and second regions are positioned approximately along the first axis.

46. The apparatus according to claim 37, wherein the second plane is provided at approximately the particular angle with respect to the second axis and at approximately twice the particular angle with respect to the first axis.

15

47. The apparatus according to claim 37, wherein the light transmissive optical arrangement is configured to concentrate the at least one electro-magnetic radiation at a focal point which is provided outside of the apparatus, and wherein the focal point is provided approximately at an intersection of the first and second planes. 5

48. An apparatus for transmitting at least one electro-magnetic radiation, comprising:

at least one optical fiber having at least one end extending along a first axis;

a light transmissive optical first arrangement provided in optical cooperation with the at least one optical fiber, the optical arrangement including a first surface having a portion that is approximately perpendicular to a second axis, and a second surface which includes a curved portion, wherein the first axis is provided at a particular angle that is more than 0° and less than 90° with respect to the second axis; 15

a sheath having a substantially transparent portion, wherein the light transmissive optical arrangement is arranged within the substantially transparent portion; 20

at least one second arrangement in optical communication with the first arrangement, and configured at least one of transmit or receive at least one first electro-magnetic radiation to or from a sample and at least one second electro-magnetic radiation to or from a reference, wherein a frequency of at least one of the first electro-magnetic radiation or the second electro-magnetic radiation varies over time; and 25 30

at least one third arrangement configured to detect an interference between at least one third radiation associated with the at least one first radiation and at least one fourth radiation associated with the at least one second radiation. 35

49. The apparatus according to claim 48, wherein the first and second curvatures have properties which effectuate a reduction of astigmatism caused by the substantially transparent portion.

50. An apparatus for transmitting at least one electro-magnetic radiation, comprising: 40

at least one optical fiber having at least one end extending along a first axis;

a light transmissive optical first arrangement provided in optical cooperation with the at least one optical fiber, the optical arrangement including a first surface having a portion that is approximately perpendicular to a second axis, and a second surface which includes a curved portion, 45

wherein the first axis is provided at a particular angle that is more than 0° and less than 90° with respect to the second axis, wherein the curved portion has a first curvature in a first plane perpendicular to the first axis, and a second curvature in a second plane perpendicular to a third axis, wherein the first plane is different from the second plane, and wherein the first curvature is different from the second curvature, and 50 55

wherein the first and second curvatures have properties which effectuate a reduction of aberration;

at least one second arrangement in optical communication with the first arrangement, and configured at least one of transmit or receive at least one first electro-magnetic radiation to or from a sample and at least one second electro-magnetic radiation to or from a reference, wherein a frequency of at least one of the first electro-magnetic radiation or the second electro-magnetic radiation varies over time; and 60 65

16

at least one third arrangement configured to detect an interference between at least one third radiation associated with the at least one first radiation and at least one fourth radiation associated with the at least one second radiation.

51. The apparatus according to claim 50, wherein the first and second curvatures have properties which effectuate a reduction of astigmatism.

52. An apparatus for transmitting at least one electro-magnetic radiation, comprising:

at least one optical fiber having at least one end extending along a first axis;

a light transmissive optical first arrangement provided in optical cooperation with the at least one optical fiber, the optical arrangement including a first surface having a portion that is approximately perpendicular to a second axis, and a second surface which includes a curved portion, wherein the first axis is provided at a particular angle that is more than 0° and less than 90° with respect to the second axis, wherein the at least one optical fiber includes first and second optical fibers, and wherein at least one of the first and second optical fibers is at least partially rotated; 15

at least one second arrangement in optical communication with the first arrangement, and configured at least one of transmit or receive at least one first electro-magnetic radiation to or from a sample and at least one second electro-magnetic radiation to or from a reference, wherein a frequency of at least one of the first electro-magnetic radiation or the second electro-magnetic radiation varies over time; and 20 25 30

at least one third arrangement configured to detect an interference between at least one third radiation associated with the at least one first radiation and at least one fourth radiation associated with the at least one second radiation. 35

53. The apparatus according to claim 52, further comprising a translation stage configured to translate at least one of the first and second optical fibers approximately along the first axis.

54. An apparatus for transmitting at least one electro-magnetic radiation, comprising:

at least one optical fiber having at least one end extending along a first axis;

a light transmissive optical first arrangement provided in optical cooperation with the at least one optical fiber, the optical arrangement including a first surface having a portion that is approximately perpendicular to a second axis, and a second surface which includes a curved portion, wherein the first axis is provided at a particular angle that is more than 0° and less than 90° with respect to the second axis, wherein the curved portion has a first curvature in a first plane perpendicular to the first axis, and a second curvature in a second plane perpendicular to a third axis, wherein the first plane is different from the second plane, and wherein the first curvature is different from the second curvature, and wherein the first and second curvatures have properties which effectuate a reduction of astigmatism at the focal point; 40 45 50 55

at least one second arrangement in optical communication with the first arrangement, and configured at least one of transmit or receive at least one first electro-magnetic radiation to or from a sample and at least one second electro-magnetic radiation to or from a reference, wherein a frequency of at least one of the first electro-magnetic radiation or the second electro-magnetic radiation varies over time; and 60 65

17

at least one third arrangement configured to detect an interference between at least one third radiation associated with the at least one first radiation and at least one fourth radiation associated with the at least one second radiation.

55. A method for transmitting at least one electro-magnetic radiation, comprising:

providing at least one optical fiber having at least one end extending along a first axis;

providing a light transmissive optical arrangement provided in optical cooperation with the at least one optical fiber, the optical arrangement including a first surface having a portion that is approximately perpendicular to a second axis, and a second surface which includes a curved portion, wherein the first axis is provided at a particular angle that is more than 0° and less than 90° with respect to the second axis, wherein the curved portion has a first radius of a first curvature in a first plane lying along the first and second axes, and a second radius of a second curvature in a second plane which is perpendicular to the first plane, wherein the first radius is different from the second radius, and wherein the first curvature is different from the second curvature;

transmitting or receiving at least one first electro-magnetic radiation to or from a sample and at least one second electro-magnetic radiation to or from a reference, wherein a frequency of at least one of the first electro-magnetic radiation or the second electro-magnetic radiation varies over time; and

detecting an interference between at least one third radiation associated with the at least one first radiation and at least one fourth radiation associated with the at least one second radiation.

56. The method according to claim 55, wherein the portion is adapted to at least partially reflect at least one portion of the at least one electro-magnetic radiation, and wherein the curved portion is adapted to transmit the at least one portion of the at least one electro-magnetic radiation there through.

57. The method according to claim 56, wherein the curved portion has a first curvature in a first plane perpendicular to the first axis, and a second curvature in a second plane perpendicular to a third axis, wherein the first plane is different from the second plane, and wherein the first curvature is different from the second curvature.

58. The method according to claim 57, wherein a further angle between the first axis and the third axis is approximately 90°.

59. The method according to claim 55, wherein the particular angle is at least an angle for a total internal reflection between the light transmissive optical arrangement and a medium external thereto.

60. The method according to claim 55, wherein the portion of the first surface is a reflective surface.

61. The method according to claim 55, wherein the portion of the first surface has a metal layer.

62. The method according to claim 55, wherein the at least one optical fiber and the light transmissive optical arrangement are formed as a single piece from the same material.

63. The method according to claim 55, wherein the at least one optical fiber has at least one first region and at least one second region, the first region being adapted to guide the at least one electro-magnetic radiation, and the second region having non-guiding properties of the at least one electro-magnetic radiation, and wherein the first and second regions are positioned along the first axis.

64. The method according to claim 55, wherein the second plane is provided at approximately the particular angle with

18

respect to the second axis and at approximately twice the particular angle with respect to the first axis.

65. The method according to claim 64, wherein the light transmissive optical arrangement is configured to concentrate the at least one electro-magnetic radiation at a focal point which is provided outside of the apparatus, and wherein the focal point is provided approximately at an intersection of the first and second planes.

66. A method for transmitting at least one electro-magnetic radiation, comprising:

providing at least one optical fiber having at least one end extending along a first axis;

providing a light transmissive optical arrangement provided in optical cooperation with the at least one optical fiber, the optical arrangement including a first surface having a portion that is approximately perpendicular to a second axis, and a second surface which includes a curved portion, wherein the first axis is provided at a particular angle that is more than 0° and less than 90° with respect to the second axis, wherein the light transmissive optical arrangement is arranged within a substantially transparent portion of a sheath;

transmitting or receiving at least one first electro-magnetic radiation to or from a sample and at least one second electro-magnetic radiation to or from a reference, wherein a frequency of at least one of the first electro-magnetic radiation or the second electro-magnetic radiation varies over time; and

detecting an interference between at least one third radiation associated with the at least one first radiation and at least one fourth radiation associated with the at least one second radiation.

67. The method according to claim 66, wherein the first and second curvatures have properties which effectuate a reduction of astigmatism caused by the substantially transparent portion.

68. A method for transmitting at least one electro-magnetic radiation, comprising:

providing at least one optical fiber having at least one end extending along a first axis;

providing a light transmissive optical arrangement provided in optical cooperation with the at least one optical fiber, the optical arrangement including a first surface having a portion that is approximately perpendicular to a second axis, and a second surface which includes a curved portion, wherein the first axis is provided at a particular angle that is more than 0° and less than 90° with respect to the second axis, wherein the curved portion has a first curvature in a first plane perpendicular to the first axis, and a second curvature in a second plane perpendicular to a third axis, wherein the first plane is different from the second plane, and wherein the first curvature is different from the second curvature, and wherein the first and second curvatures have properties which effectuate a reduction of aberration;

transmitting or receiving at least one first electro-magnetic radiation to or from a sample and at least one second electro-magnetic radiation to or from a reference, wherein a frequency of at least one of the first electro-magnetic radiation or the second electro-magnetic radiation varies over time; and

detecting an interference between at least one third radiation associated with the at least one first radiation and at least one fourth radiation associated with the at least one second radiation.

19

69. The method according to claim 68, wherein the first and second curvatures have properties which effectuate a reduction of astigmatism.

70. A method for transmitting at least one electro-magnetic radiation, comprising:

providing at least one optical fiber having at least one end extending along a first axis;

providing a light transmissive optical arrangement provided in optical cooperation with the at least one optical fiber, the optical arrangement including a first surface having a portion that is approximately perpendicular to a second axis, and a second surface which includes a curved portion, wherein the first axis is provided at a particular angle that is more than 0° and less than 90° with respect to the second axis, wherein the at least one optical fiber includes first and second optical fibers, and wherein one of the first and second optical fibers is at least partially rotated;

transmitting or receiving at least one first electro-magnetic radiation to or from a sample and at least one second electro-magnetic radiation to or from a reference, wherein a frequency of at least one of the first electro-magnetic radiation or the second electro-magnetic radiation varies over time; and

detecting an interference between at least one third radiation associated with the at least one first radiation and at least one fourth radiation associated with the at least one second radiation.

71. The method according to claim 70, further comprising a translation stage configured to translate at least one of the first and second optical fibers approximately along the first axis.

72. A method for transmitting at least one electro-magnetic radiation, comprising:

providing at least one optical fiber having at least one end extending along a first axis;

providing a light transmissive optical arrangement provided in optical cooperation with the at least one optical fiber, the optical arrangement including a first surface having a portion that is approximately perpendicular to a second axis, and a second surface which includes a curved portion, wherein the first axis is provided at a particular angle that is more than 0° and less than 90° with respect to the second axis; concentrating the at least one electro-magnetic radiation at a focal point which is provided outside of the apparatus, wherein the

20

first and second curvatures have properties which effectuate a reduction of astigmatism at the focal point;

transmitting or receiving at least one first electro-magnetic radiation to or from a sample and at least one second electro-magnetic radiation to or from a reference, wherein a frequency of at least one of the first electro-magnetic radiation or the second electro-magnetic radiation varies over time; and

detecting an interference between at least one third radiation associated with the at least one first radiation and at least one fourth radiation associated with the at least one second radiation.

73. An apparatus for transmitting at least one electro-magnetic radiation, comprising:

at least one optical fiber having at least one end extending along a first axis;

a light transmissive optical first arrangement provided in optical cooperation with the at least one optical fiber, the optical arrangement including a first planar surface provided in position to first receive an electromagnetic radiation from the at least one optical fiber and having a portion that is approximately perpendicular to a second axis, and a second surface which includes a curved portion, wherein the first axis is provided at a particular angle that is more than 0° and less than 90° with respect to the second axis, wherein the curved portion has a first radius of a first curvature in a first plane lying along the first and second axes, and a second radius of a second curvature in a second plane which is perpendicular to the first plane, and wherein the first radius is different from the second radius, and wherein the first curvature is different from the second curvature;

at least one second arrangement in optical communication with the first arrangement, and configured at least one of transmit or receive at least one first electro-magnetic radiation to or from a sample and at least one second electro-magnetic radiation to or from a reference, wherein a frequency of at least one of the first electro-magnetic radiation or the second electro-magnetic radiation varies over time; and

at least one third arrangement configured to detect an interference between at least one third radiation associated with the at least one first radiation and at least one fourth radiation associated with the at least one second radiation.

* * * * *