Patented Nov. 13, 1923. 1,473,947

UNITED STATES PATENT OFFICE.

TILLMAN BAILEY, OF NASHVILLE, TENNESSEE.

COMPOSITION FOR POLISHES.

No Drawing. Application filed November 28, 1920. Serial No. 426,037.

To all whom it may concern:

Be it known that I, TILLMAN BAILEY, a citizen of the United States, and a resident of Nashville, in the county of Davidson and State of Tennessee, have invented certain new and useful Improvements in Compositions for Polishes, of which the following is a specification.

My invention is an improvement in compositions for polishes, and has for its object to provide a simple inexpensive polish of the character specified, adapted for use with furniture, automobiles and wood and metal work of every character.

My improved polish is composed of oil of sassafras, kerosene, turpentine, Sinclair motor oil, Bon Ami, gasoline and distilled water.

The Sinclair motor oil is a petroleum product with paraffine—asphalt base, the distinguishing characteristics of which are:

Gravity (Baumé)----	20 degrees.
Viscosity at 100 F.----	635 Saybolt.
Flash ----------	400
Fire ----------	450
Color about----------	6

Fire and flash by Cleveland open cup.

My polish is componded in the following manner:

The Bon Ami (which is a mild soap containing a finely divided abradant such as pumice), in the proportion of one-half pound is first mixed with one quart of distilled water, and the mixture is violently agitated by stirring until the Bon Ami is thoroughly dissolved and the solution lathers freely.

I then take one-half ounce of the oil of sassafras, three-fourths of an ounce each of kerosene and turpentine, with eight ounces of the Sinclair motor oil, mix and shake well, until thoroughly mixed. Three-fourths gallons of gasoline is then poured into the solution of water and Bon Ami, and the mixture is agitated for five minutes, by churning or stirring rapidly. Now the oils mixed as before stated, are added, and the mixture is agitated by churning or the like, until a white clabber is formed.

The mixture is now permitted to stand until settled, then decanted, in order to clear from the sediment, which sediment is thrown away.

The improved polish will remove grease and gum, and will give a brilliant gloss to the surface upon which it is used. It does not injure the surface upon which it is used. The turpentine, kerosene and motor oil act to give a sustaining gloss while the oil of sassafras is a perfume. Gasoline with the Bon Ami is a general cleanser, leaving a non-greasy finish.

The polish is used in the following manner: For automobiles and metal work, the parts should be free from mud and grit. Then saturate a soft cloth with the polish, and rub over the parts to remove grease and gum, taking care that the polish does not dry on the hood or fender. Then with another soft cloth, flannel or cheese-cloth, rub until the desired gloss is obtained. To obtain the best result, the car should be polished in the shade and with a cool engine.

For polishing wood work or furniture, the surface should be rubbed with the polish in the same manner as before stated, and afterwards rubbed brisky with soft flannel or cheese cloth, till the desired gloss is obtained.

Distilled water is used to prevent fermentation.

I claim:

1. The herein described process of making a polish, consisting in the following steps: mixing Bon Ami powder with distilled water to form a lather mixture, combining gasoline with the lather mixture, forming a mixture composed of oil of sassafras, kerosene, turpentine and Sinclair motor oil, combining the oil mixture with the lather mixture and agitating the combined mixtures, and finally decanting to clear away sediment.

2. A liquid polish including Bon Ami powder, distilled water, light motor oil, turpentine, kerosene, oil of sassafras and gasoline, substantially in the proportions described.

3. A polish composed of Bon Ami powder, one-half pound, distilled water, one quart, Sinclair motor oil, eight ounces, turpentine and kerosene each three-fourths ounce, oil of sassafras, one ounce, gasoline, three-fourths gallons.

4. A liquid polish including Bon Ami, distilled water, light motor oil, turpentine, kerosene, gasoline, and perfuming matter, substantially in the proportions described.

TILLMAN BAILEY.