United States Patent [19]

Dove

[11] **3,777,781**

[45] **Dec. 11, 1973**

[54] **STEAM SUPPLY APPARATUS**

[76] Inventor: **Norman F. Dove,** 34-21st Ave., South, Cranbrook, British Columbia, Canada

[22] Filed: **Oct. 25, 1972**

[21] Appl. No.: **300,490**

[30] **Foreign Application Priority Data**

Apr. 21, 1972 Canada 140239

[52] **U.S. Cl.** **137/608,** 137/561, 162/290, 34/160

[51] **Int. Cl.** **F26b 21/12,** D21f 5/18

[58] **Field of Search** 137/561, 608; 239/430, 450, 504, 594, 597; 162/207, 290; 34/34, 155, 160

[56] **References Cited**

UNITED STATES PATENTS


1,144,896	6/1915	Fosbraey	34/155 X
2,838,982	6/1958	Dupasquier	162/290
3,242,587	3/1966	Dupasquier	34/160 X
3,669,831	6/1972	Dupasquier	162/290
3,726,757	4/1973	Dupasquier	34/155 X

Primary Examiner—William R. Cline
Attorney—George H. Spencer et al.

[57] **ABSTRACT**

A steam supply apparatus includes at least two pipes located in spaced apart, side by side relationship, and a cover member extending across the pipes and secured thereto. End members are secured to the respective opposite ends of the pipes, and a pair of baffles between each pair of pipes are secured thereto in a substantially V-shaped configuration with a slot between adjacent ends of the baffles at the base of the V-shape, the base of the V-shape being directed towards the cover member. Steam is supplied to the pipes, and each pipe has a series of apertures communicating the interior of the pipe with the space between the pipes, the cover member and the baffles.

9 Claims, 5 Drawing Figures





31
29
38
39
36
37
19
32
35
15
15
14
23
23
23
23
15
15
23
23
11
13
12
3
15
15
3
19
30
30a
30a
31

FIG. 1.




FIG. 2.



18
17
39
13
15
26
20
35
23
22
34
37
28
21
16
12
14
27
23
22
21
33
36
32
26
20
15
38
A
17
18

FIG. 3.




FIG. 4.




FIG. 5.

STEAM SUPPLY APPARATUS

This invention relates to steam supply apparatus.

In some processes, it is desirable to supply steam in a relatively dry state over a relatively long length and width. One example of such a process is in a paper-making machine, in which steam is directed at the paper web from a steam supply apparatus as the paper web passes thereby.

It is therefore an object of the invention to provide an improved steam supply apparatus suitable for this purpose.

According to the invention, at least two pipes are located in spaced apart, side by side relationship, with a cover member extending across the pipes and secured thereto, end members secured to the respective opposite ends of the pipes, a pair of baffles between each pair of pipes and secured thereto in a substantially V-shaped configuration with a slot between adjacent ends of the baffles at the base of the V-shape, the base of the V-shape being directed towards the cover member, and means for supplying steam to the pipes, each pipe having a series of apertures communicating the interior of the pipe with the space between the pipes, the cover member and the baffles.

In use, the apparatus is positioned so that the pipes extend transversely to the direction of motion of the web. Steam supplied to the pipes passes through the apertures into the spaces between the pipes, the baffles and the cover member, and then passes out of the apparatus through the slot between each pair of baffles. Condensation of steam within the apparatus drains to the bottom of the pipes and to the lowermost parts of the baffles, from whence it can be drained by appropriately positioned apertures and drain tubes.

The pipes form a main part of the structure. Preferably, stiffeners are secured at intervals between each pair of pipes, the baffles and the cover member. Also, spacers may be secured between the cover member and the adjacent end portions of the baffles.

The apparatus may be provided with a jacket extending in spaced relationship to the cover member, with insulating material being located in the space between the jacket and the cover member. The jacket preferably extends also over the outer sides of the outer pipes in spaced relationship thereto, with insulation therebetween.

The steam supply means may include a steam supply pipe connected to one end of one pipe, and a connector connecting the opposite end of the pipe to an adjacent pipe. The connector may include an adjustable valve to regulate the flow of steam from the one pipe to the adjacent pipe, or where at least three pipes are provided may include separate adjustable valves to regulate the flow of steam from an inner pipe to outer pipes.

One embodiment of the invention will now be described, by way of example, with reference to the accompanying drawings, of which:

FIG. 1 is a plan view, partly broken away, of the steam supply apparatus,

FIG. 2 is a side view of the apparatus,

FIG. 3 is a sectional view on an enlarged scale along the line 3—3 of FIG. 1,

FIG. 4 is a front view, on an enlarged scale, of one of the stiffeners, and

FIG. 5 is a front view on an enlarged scale of one of the spacers.

Referring to the drawings, a steam supply apparatus intended for use in a paper making machine includes three spaced parallel steam header pipes **11, 12, 13**, the outer pipes **11, 13** being of greater diameter than the inner pipe **12**. The tops of each pipe **11, 12, 13** are welded to the underside of a cover member in the form of a top plate **14**.

Three stiffeners **15** are located between and are welded to each adjacent pair of pipes **11, 12**, and **12, 13**, and each stiffener **15** projects above the top plate **14** through a respective slot therein. A jacket **16** extends across the top plate **14** in spaced relationship therewith, and is secured to the upper edges of the stiffeners **15**. The jacket **16** extends downwardly at the side in spaced relationship to the outer pipes **11, 13**, and adjacent the bottom of each outer pipe **11, 13** has an inwardly projecting member **17** whose inner end is welded to the respective pipes **11, 13**. This member **17** can operate as a low pressure steam seal or a deflector. A spacing bracket **18** extends between and is welded to the outer pipes **11, 13** respectively and the jacket **16**. The space between the jacket **16** on the one hand and the top plate **14** and the outer pipes **11, 13** on the other hand is filled with glass fibre for heat insulation purposes. An end plate **19** is welded to each end of the pipes **11, 12, 13**, the top plate **14** and the jacket **16**.

Between each pair of pipes **11, 12**, and **12, 13** is a pair of baffles **20, 21** in inverted V-shaped configuration, the base of the V-shape thus being directed towards the top plate **14**. The lower ends of each pair of baffles **20, 21** are welded to the lower adjacent parts of the pipes **11, 12** and **13, 12** respectively, and the upper ends are spaced apart by a small amount to provide a slot **22** between each pair of baffles **20, 21** extending the length of the pipes **11, 12, 13**. The slot **22** is maintained by a series of spacers **23** welded at regular intervals to the baffles **20, 21** at the lower ends of the spacers and to the under side of the top plate **14** at the upper ends of the spacers. The baffles **20, 21** are also welded to the lower ends of the stiffeners **15**. Both the stiffeners **15** and the spacers **23** have lower edges of inverted V-shape to conform with the inclination of the baffles **20, 21**, with the apex of the V-shape being cut away in the stiffeners **15** and spacers **23** and **24** and **25** respectively so as not to unduly interrupt the slots **22**.

Each outer pipe **11, 13** has a series of spaced apertures **26** extending along the length of the respective pipes in the upper interior portion thereof. The inner pipe **12** has two series of spaced apertures **27, 28** extending along the length of the pipe **12** on each side of the upper portion thereof.

At one end of the apparatus, a steam supply pipe **29** is secured to one end of the inner pipe **12**. At the opposite end, a pipe connector **30** connects the opposite end of the inner pipe **12** to the two outer pipes **11, 13**. The pipe connector **30** includes two manually operable valves **30a** to regulate the flow of steam individually from the inner pipe **12** to the outer pipes **11** and **13** respectively. Mounting brackets **31** extend outwardly from the end plates **19**.

At the steam supply end of the apparatus, a drain tube assembly includes four tubes **32, 33, 34, 35** connected to apertures in the respective baffles **20, 21**, and outlet tubes **36, 37** extending from the tubes **32, 33** and **34, 35** respectively through the adjacent end plate **19** to the exterior of the apparatus. Drain tubes **38, 39** ex-

tend through the end plate **19** from the outer pipes **11, 13** respectively, and a convenient drain is also provided from the central pipe **12.**

In use, the apparatus is positioned above the paper web so that the pipes **11, 12, 13** extend transversely to the direction of motion of the web, as indicated by the arrow A in FIG. **3.** One or more suction boxes will be arranged in known manner below the web. Steam is supplied through the supply pipe **29** to the inner pipe **12,** from which the steam flows through the connector **30** and valve **30***a* into the two outer pipes **11, 13.** Steam escapes from the pipes **11, 12, 13** through the apertures **26, 27, 28** into the spaces between the pipes, and from these spaces the steam passes through the slots **22** out of the apparatus. Condensation remains in the pipes or drains to the lowermost parts of the baffles **20, 21** from whence it drains through the various tubes mentioned above. The whole apparatus will of course be slightly tilted towards the end at which the drain tubes are located so that the condensation will run to the drain tubes.

By operation of the valve **30***a*, the inner pipe **12** can be used alone, or in combination with either or both outer pipes **11, 13** at the same or lower pressures, thus giving a wide range of distribution of steam to the sheet.

The spacers **15** are preferably provided with apertures **15***a* to allow equalization of steam pressure along the outside of the length of each pipe **11, 12, 13,** that is to say across the width of the web.

In one specific embodiment, the apparatus was about 12 feet in length between the end plates, and 3 feet wide. The inner pipe was about 6 inches in diameter, and the outer pipes about 8 inches in diameter. The apertures **26, 27, 28** were 5/16ths inches in diameter and were located every 4 inches along the length of the respective pipes. The apertures were located on radii of the respective pipes which were inclined at an angle of 20° above the horizontal.

The described embodiment is relatively noise-free compared to known steam supply apparatus used in paper making machines.

Although the described embodiment is for use above a paper web with the steam being directed downwardly, it will be apparent that it is also within the scope of the invention to provide apparatus for use below a paper web with the steam being directed upwadly.

I claim:

1. A steam supply apparatus including at least two pipes located in spaced apart, side by side relationship, a cover member extending across the pipes and secured thereto, end members secured to the respective opposite ends of the pipes, a pair of baffles between each pair of pipes and secured thereto in a substantially V-shaped configuration with a slot between adjacent ends of the baffles, at the base of the V-shape, the base of the V-shape being directed towards the cover member, means for supplying steam to the pipes, and each pipe having a series of apertures communicating the interior of the pipe with the space between the pipes, the cover member and the baffles.

2. Apparatus according to claim **1** wherein condensation drainage means is provided and comprises tubes connected to apertures in the lower parts of the baffles.

3. Apparatus according to claim **1** wherein stiffeners are secured at intervals between each pair of pipes, baffles and the cover member.

4. Apparatus according to claim **1** wherein spacers are secured at intervals to the cover member and the adjacent end portions of the baffles.

5. Apparatus according to claim **1** wherein a jacket member is secured in spaced relationship to the cover member, and insulating material is located in the space between the jacket member and the cover member.

6. Apparatus according to claim **5** wherein the jacket extends on the outer side of the outer pipes in spaced relationship thereto, with insulating material therebetween.

7. Apparatus according to claim **1** wherein the steam supply means includes a steam supply pipe connected to one end of one pipe, and a connector connecting the opposite end of said pipe to an adjacent pipe.

8. Apparatus according to claim **7** wherein the connector includes an adjustable valve to regulate the flow of steam from said one pipe to the adjacent pipe.

9. Apparatus according to claim **7** wherein at least three pipes are provided, and the connector includes separate adjustable valves to regulate the flow of steam from an inner pipe to outer pipes.

* * * * *