



(12) **United States Patent**
Harvey et al.

(10) **Patent No.:** **US 11,448,383 B2**
(45) **Date of Patent:** **Sep. 20, 2022**

(54) **UTILITY MOUNT LIGHT**
(71) Applicant: **MILWAUKEE ELECTRIC TOOL CORPORATION**, Brookfield, WI (US)
(72) Inventors: **Kyle Harvey**, Wauwatosa, WI (US); **Jason D. Thurner**, Menomonee Falls, WI (US); **David Proeber**, Milwaukee, WI (US); **Justin D. Dorman**, Wauwatosa, WI (US)
(73) Assignee: **MILWAUKEE ELECTRIC TOOL CORPORATION**, Brookfield, WI (US)
(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **17/381,791**
(22) Filed: **Jul. 21, 2021**

(65) **Prior Publication Data**
US 2021/0348744 A1 Nov. 11, 2021

Related U.S. Application Data
(63) Continuation of application No. 16/999,742, filed on Aug. 21, 2020, now Pat. No. 11,073,265, which is a (Continued)

(51) **Int. Cl.**
F21V 21/14 (2006.01)
F21L 4/02 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **F21V 21/145** (2013.01); **F21L 4/027** (2013.01); **F21L 4/04** (2013.01); **F21V 21/0885** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC **F21V 21/145**; **F21V 21/0885**; **F21V 21/30**; **F21V 21/406**; **F21V 23/0414**; **F21L 4/027**; **F21L 4/04**
See application file for complete search history.


(56) **References Cited**
U.S. PATENT DOCUMENTS
3,331,958 A 7/1967 Adler
3,973,179 A 8/1976 Weber et al.
(Continued)
FOREIGN PATENT DOCUMENTS
CN 303851715 9/2016
DE 10023183 A1 11/2001
(Continued)
OTHER PUBLICATIONS

Extended European Search Report for Application No. 16198619.5 dated Mar. 1, 2017, 9 pages.
(Continued)

Primary Examiner — Peggy A Neils
(74) *Attorney, Agent, or Firm* — Michael Best & Friedrich LLP

(57) **ABSTRACT**
A battery-powered utility light mountable to a workpiece comprising a main body and a plurality of lights coupled to the main body. Each of the plurality of lights are independently movable relative to the main body. The utility light further includes a first mode actuator that is configured to cycle one of the plurality of lights through a plurality of lighting modes and a second mode actuator that is configured to cycle a different one of the plurality of lights through a plurality of lighting modes separately from the other plurality of lights. The utility light further includes a hooking element that is moveably coupled to the main body between an open position, in which the workpiece is permitted to be received in an opening, and a closed position, in which the workpiece is inhibited from being removed from the opening. The opening is disposed between the main body and the hooking element.

20 Claims, 8 Drawing Sheets



Related U.S. Application Data

continuation of application No. 16/404,197, filed on May 6, 2019, now Pat. No. 10,753,585, which is a continuation of application No. 15/349,689, filed on Nov. 11, 2016, now Pat. No. 10,323,831.

(60) Provisional application No. 62/255,078, filed on Nov. 13, 2015.

(51) **Int. Cl.**

F21V 21/30 (2006.01)

F21V 23/04 (2006.01)

F21L 4/04 (2006.01)

F21V 21/088 (2006.01)

F21V 21/40 (2006.01)

(52) **U.S. Cl.**

CPC *F21V 21/30* (2013.01); *F21V 21/406* (2013.01); *F21V 23/0414* (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,032,771 A 6/1977 Ilzig
 4,228,489 A 10/1980 Martin
 4,268,894 A 5/1981 Bartunek et al.
 4,324,477 A 4/1982 Miyazaki
 5,019,951 A 5/1991 Osterhout et al.
 5,203,621 A 4/1993 Weinmeister et al.
 5,207,747 A 5/1993 Gordin et al.
 5,351,172 A 9/1994 Attree et al.
 5,400,234 A 3/1995 Yu
 5,428,520 A 6/1995 Skief
 D376,535 S 12/1996 Gary et al.
 5,630,660 A 5/1997 Chen
 5,934,628 A 8/1999 Bosnakovic
 5,944,407 A 8/1999 Lynch et al.
 5,964,524 A 10/1999 Qian
 D422,203 S 4/2000 Gary et al.
 6,045,240 A 4/2000 Hochstein
 D424,418 S 5/2000 Gary et al.
 D428,176 S 7/2000 Bamber et al.
 6,092,911 A 7/2000 Baker, III et al.
 6,099,142 A 8/2000 Liu
 6,149,283 A 11/2000 Conway et al.
 6,183,114 B1 2/2001 Cook et al.
 6,213,626 B1 4/2001 Qian
 6,255,786 B1 7/2001 Yen
 6,265,969 B1 7/2001 Shih
 D452,022 S 12/2001 Osiecki et al.
 6,367,949 B1 4/2002 Pederson
 6,379,023 B1 4/2002 Passno
 6,394,631 B1 5/2002 Yuen
 6,461,017 B2 10/2002 Selkee
 6,474,844 B1 11/2002 Ching
 6,554,459 B2 4/2003 Yu et al.
 6,637,904 B2 10/2003 Hernandez
 D494,849 S 8/2004 Jones et al.
 6,824,297 B1 11/2004 Lee
 6,854,862 B1 2/2005 Hopf
 6,857,756 B2 2/2005 Reiff et al.
 6,873,249 B2 3/2005 Chu
 6,877,881 B2 4/2005 Tsao
 6,899,441 B2 5/2005 Chen
 D506,847 S 6/2005 Hussaini et al.
 6,902,294 B2 6/2005 Wright
 6,926,428 B1 8/2005 Lee
 6,953,260 B1 10/2005 Mien
 7,001,044 B2 2/2006 Leen
 7,001,047 B2 2/2006 Holder et al.
 7,011,280 B2 3/2006 Murray et al.
 7,063,444 B2 6/2006 Lee et al.
 7,073,926 B1 7/2006 Kremers et al.
 D529,360 S 10/2006 Wimmer
 D529,926 S 10/2006 Krieger et al.

D532,536 S 11/2006 Krieger et al.
 7,152,997 B1 12/2006 Kovacik et al.
 7,153,004 B2 12/2006 Galli
 D537,330 S 2/2007 Cox et al.
 D538,636 S 3/2007 Jackson et al.
 7,194,358 B2 3/2007 Callaghan et al.
 7,195,377 B2 3/2007 Tsai
 7,224,271 B2 5/2007 Wang
 D549,859 S 8/2007 Kovacik et al.
 D551,048 S 9/2007 Huang
 D551,532 S 9/2007 Huang
 D553,281 S 10/2007 Rugendyke et al.
 D553,461 S 10/2007 Neiser
 D553,771 S 10/2007 Watson et al.
 7,278,761 B2 10/2007 Kuan
 D556,353 S 11/2007 Gebhard et al.
 7,350,940 B2 4/2008 Haugaard et al.
 7,364,320 B2 4/2008 Van Deursen et al.
 7,367,695 B2 5/2008 Shiau
 7,470,036 B2 12/2008 Deighton et al.
 7,484,858 B2 2/2009 Deighton
 7,503,530 B1 3/2009 Brown
 D593,236 S 5/2009 Ng et al.
 D595,105 S 6/2009 White
 7,566,151 B2 7/2009 Whelan et al.
 7,618,154 B2 11/2009 Rosiello
 7,638,970 B1 12/2009 Gebhard et al.
 7,670,034 B2 3/2010 Zhang et al.
 7,798,684 B2 9/2010 Boissevain
 7,828,465 B2 11/2010 Roberge et al.
 7,857,486 B2 12/2010 Long et al.
 7,914,178 B2 3/2011 Xiang et al.
 7,914,182 B2 3/2011 Mrakovich et al.
 7,972,036 B1 7/2011 Schach et al.
 D643,138 S 8/2011 Kawase et al.
 7,988,335 B2 8/2011 Liu et al.
 7,990,062 B2 8/2011 Liu
 7,997,753 B2 8/2011 Walesa
 8,007,128 B2 8/2011 Wu et al.
 8,007,145 B2 8/2011 Leen
 8,029,169 B2 10/2011 Liu
 8,047,481 B2 11/2011 Shen
 8,087,797 B2 1/2012 Pelletier et al.
 8,142,045 B2 3/2012 Peak
 8,167,466 B2 5/2012 Liu
 8,201,979 B2 6/2012 Deighton et al.
 D665,521 S 8/2012 Werner et al.
 8,235,552 B1 8/2012 Tsuge
 8,262,246 B2 9/2012 Pelletier et al.
 8,262,248 B2 9/2012 Wessel
 8,294,340 B2 10/2012 Yu et al.
 8,322,892 B2 12/2012 Scordino et al.
 8,328,398 B2 12/2012 Van Deursen
 8,330,337 B2 12/2012 Yu et al.
 8,360,607 B2 1/2013 Bretschneider et al.
 8,366,290 B2 2/2013 Maglica
 8,403,522 B2 3/2013 Chang
 D679,845 S 4/2013 Huang
 8,425,091 B2 4/2013 Chen
 8,434,915 B2 5/2013 Liu et al.
 8,439,531 B2 5/2013 Trott et al.
 8,465,178 B2 6/2013 Wilcox et al.
 8,485,691 B2 7/2013 Hamel et al.
 8,547,022 B2 10/2013 Summerford et al.
 D695,434 S 12/2013 Shen
 8,599,097 B2 12/2013 Intravatology
 D698,471 S 1/2014 Poon
 D699,874 S 2/2014 Chilton et al.
 8,651,438 B2 2/2014 Deighton et al.
 8,659,433 B2 2/2014 Petrou
 8,668,349 B2 3/2014 Richardson
 D702,863 S 4/2014 Kotsis
 D703,354 S 4/2014 Kotsis
 D703,355 S 4/2014 Kotsis
 D703,851 S 4/2014 Gebhard et al.
 8,692,444 B2 4/2014 Patel et al.
 8,696,177 B1 4/2014 Frost
 D705,467 S 5/2014 Aglassinger
 8,757,815 B2 6/2014 Saruwatari et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

D708,376	S	7/2014	Crowe et al.	2010/0091495	A1	4/2010	Patrick
8,801,226	B2	8/2014	Moore	2010/0132203	A1	6/2010	Green et al.
8,840,264	B2	9/2014	Molina et al.	2010/0142213	A1	6/2010	Bigge et al.
8,851,699	B2	10/2014	McMillan	2010/0315824	A1	12/2010	Chen
8,858,016	B2	10/2014	Strelchuk	2010/0328951	A1	12/2010	Boissevain
8,858,026	B2	10/2014	Lee et al.	2011/0031887	A1	2/2011	Stoll et al.
8,939,602	B2	1/2015	Wessel	2011/0038144	A1	2/2011	Chang
8,979,331	B2	3/2015	Lee et al.	2011/0050070	A1	3/2011	Pickard
D726,354	S	4/2015	Davies	2011/0058367	A1	3/2011	Shiau et al.
9,010,279	B1	4/2015	Saber et al.	2011/0075404	A1	3/2011	Allen et al.
D728,402	S	5/2015	Case	2011/0121727	A1	5/2011	Sharrah et al.
9,046,231	B2	6/2015	Christ et al.	2011/0228524	A1	9/2011	Greer
9,052,072	B2*	6/2015	Renk, Jr. F21V 23/0414	2011/0286216	A1	11/2011	Araman
9,068,736	B2	6/2015	Lee et al.	2011/0317420	A1	12/2011	Jeon et al.
D734,886	S	7/2015	Lazalier et al.	2012/0026729	A1	2/2012	Sanchez et al.
D737,487	S	8/2015	Beckett et al.	2012/0033400	A1	2/2012	Remus et al.
D744,139	S	11/2015	Itoh et al.	2012/0033429	A1	2/2012	Van De Ven
9,188,320	B2	11/2015	Russello et al.	2012/0044707	A1	2/2012	Breidenassel
9,205,774	B2	12/2015	Kennemer et al.	2012/0048511	A1	3/2012	Moshtag
D747,263	S	1/2016	Lafferty	2012/0049717	A1	3/2012	Lu
D750,822	S	3/2016	Hernandez et al.	2012/0057351	A1	3/2012	Wilcox et al.
D755,034	S	5/2016	DeBaker et al.	2012/0087118	A1	4/2012	Bailey et al.
D759,291	S	6/2016	Chen	2012/0087125	A1	4/2012	Liu
D772,670	S	11/2016	Barezzani et al.	2012/0098437	A1	4/2012	Smed
D774,231	S	12/2016	Recker et al.	2012/0120674	A1	5/2012	Jonker
D774,674	S	12/2016	Hanwell	2012/0140455	A1	6/2012	Chang et al.
D776,320	S	1/2017	Bobel	2012/0155104	A1	6/2012	Jonker
9,539,952	B2	1/2017	Gebhard et al.	2012/0212963	A1	8/2012	Jigamain
D779,694	S	2/2017	Crowe et al.	2012/0234519	A1	9/2012	Lee
9,579,735	B2	2/2017	Wattenbach et al.	2012/0236551	A1	9/2012	Sharrah et al.
D781,480	S	3/2017	Zhan	2012/0247735	A1	10/2012	Ito et al.
D781,718	S	3/2017	Ko	2012/0262917	A1	10/2012	Courcelle
9,596,776	B2	3/2017	Takahashi et al.	2012/0300487	A1	11/2012	Jonker
D788,180	S	5/2017	Mantes et al.	2013/0032323	A1	2/2013	Hsu
D804,074	S	11/2017	Fang	2013/0058078	A1	3/2013	Meng
D805,365	S	12/2017	Ballard et al.	2013/0077296	A1	3/2013	Goeckel et al.
D816,252	S	4/2018	Harvey et al.	2013/0128565	A1	5/2013	Cugini et al.
D823,088	S	7/2018	Lafavour et al.	2013/0148366	A1	6/2013	Adams, IV et al.
D824,246	S	7/2018	Ming	2013/0176713	A1	7/2013	Deighton et al.
10,323,831	B2	6/2019	Harvey et al.	2013/0187785	A1	7/2013	McIntosh et al.
10,571,102	B1	2/2020	Bao	2013/0258645	A1	10/2013	Weber et al.
D877,948	S	3/2020	Thompson	2013/0265780	A1	10/2013	Choski et al.
D881,431	S	4/2020	Burczyk et al.	2013/0322073	A1	12/2013	Hamm et al.
10,948,166	B2	3/2021	Ohara et al.	2014/0126192	A1	5/2014	Ancona et al.
2002/0136005	A1	9/2002	Lee	2014/0140050	A1	5/2014	Wong et al.
2002/0167814	A1	11/2002	Ching	2014/0192543	A1	7/2014	Deighton et al.
2003/0090904	A1	5/2003	Ching	2014/0218936	A1	8/2014	Mahling et al.
2003/0137847	A1	7/2003	Cooper	2014/0231486	A1	8/2014	Burch et al.
2003/0174503	A1	9/2003	Yueh	2014/0268775	A1	9/2014	Kennemer et al.
2004/0228117	A1	11/2004	Witzel et al.	2014/0301066	A1	10/2014	Inskeep
2005/0201085	A1	9/2005	Aikawa et al.	2014/0307443	A1	10/2014	Clifford et al.
2006/0007682	A1	1/2006	Reiff, Jr. et al.	2014/0376216	A1	12/2014	McLoughlin et al.
2006/0067077	A1	3/2006	Kumthampinij et al.	2015/0023771	A1	1/2015	Carr et al.
2006/0146550	A1	7/2006	Simpson et al.	2015/0198298	A1	7/2015	Scarлата et al.
2006/0279948	A1	12/2006	Tsai	2015/0233569	A1	8/2015	Xue et al.
2006/0285323	A1	12/2006	Fowler	2015/0233571	A1	8/2015	Inan et al.
2007/0211470	A1	9/2007	Huang	2016/0341239	A1	11/2016	Inkavesvaanit
2007/0297167	A1	12/2007	Greenhoe	2016/0354664	A1	12/2016	DeCarlo
2008/0112170	A1	5/2008	Trott et al.	2016/0356439	A1	12/2016	Inskeep
2008/0158887	A1	7/2008	Zhu et al.	2017/0138575	A1	5/2017	Harvey et al.
2008/0165537	A1	7/2008	Shiau	2017/0204864	A1	7/2017	Mantes et al.
2008/0198588	A1	8/2008	O'Hern	2017/0331163	A1	11/2017	Ebner et al.
2008/0253125	A1	10/2008	Kang et al.	2019/0257505	A1	8/2019	Harvey et al.
2008/0302933	A1	12/2008	Cardellini	2019/0285257	A1	9/2019	Gall et al.
2009/0080205	A1	3/2009	Chang et al.	2020/0378586	A1	12/2020	Harvey et al.
2009/0097263	A1	4/2009	Ko et al.				
2009/0116230	A1	5/2009	Young				
2009/0134191	A1	5/2009	Phillips				
2009/0135594	A1	5/2009	Yu et al.				
2009/0284963	A1	11/2009	Intravatology				
2009/0303717	A1	12/2009	Long				
2010/0027260	A1	2/2010	Liu				
2010/0027269	A1	2/2010	Lo et al.				
2010/0072897	A1	3/2010	Zheng				
2010/0080005	A1	4/2010	Gattar				

FOREIGN PATENT DOCUMENTS

EP	0193756	A2	9/1986
EP	1205428	A1	5/2002
EP	2436641	A1	4/2012
GB	2424694	A	10/2006
GB	2468740	A	9/2010
KR	20100116933	A	11/2010
WO	2002044503	A1	6/2002

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO 2014083117 A1 6/2014
WO 2014207595 A1 12/2014

OTHER PUBLICATIONS

European Patent Office Action for Application No. 16198619.5
dated May 18, 2018, 5 pages.

Milwaukee Tool, "M18 Utility Bucket Light (Tool Only)", <<https://www.milwaukeetool.com/Products/Lighting/Specialty-Lights/2122-22HD>>, website accessed Dec. 30, 2019, 5 pages.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5





FIG. 6






FIG. 8

1

UTILITY MOUNT LIGHT

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 16/999,742, filed on Aug. 21, 2020, now U.S. Pat. No. 11,073,265, which is a continuation of U.S. patent application Ser. No. 16/404,197, filed on May 6, 2019, now U.S. Pat. No. 10,753,585, which is a continuation of U.S. patent application Ser. No. 15/349,689, filed on Nov. 11, 2016, now U.S. Pat. No. 10,323,831, which claims priority to U.S. Provisional Patent Application No. 62/255,078, filed on Nov. 13, 2015, the entire contents of all of which are incorporated herein by reference.

FIELD OF THE INVENTION

The present invention relates to utility lights.

SUMMARY OF THE INVENTION

The present invention provides, in one aspect, a utility light comprising a main body and a light assembly defined on the main body including a light source disposed within a light housing. The light housing is pivotable and rotatable relative to the main body. The utility light also comprises a handle movably coupled to the main body. The handle is linearly extensible relative to the main body to a position in which an opening is defined between the handle and the main body, such that the opening is configured to receive a workpiece to support the utility light. The handle has a gripping portion defined by an aperture extending through the handle.

The present invention provides, in another aspect, a utility light comprising a main body and a light assembly defined on the main body including a light source disposed within a light housing. The light housing is pivotable and rotatable relative to the main body. The utility light also comprises a handle including a portion that is movably coupled to the main body. The handle is linearly extensible relative to the main body and biased toward the main body such that the handle is configured to clamp a workpiece between the handle and the main body.

The present invention provides, in yet another aspect, a utility light comprising a main body and a handle movably coupled to the main body. The handle linearly extensible in a first direction relative to the main body and biased toward the main body in a second direction that is opposite the first direction. The utility light also comprises a light assembly defined on the main body including a light source disposed within a light housing, the light housing being pivotally supported within a yoke that is rotatable relative to the main body.

Other features and aspects of the invention will become apparent by consideration of the following detailed description and accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a front perspective view of a utility mount light.
 FIG. 2 is a rear perspective view of the utility mount light.
 FIG. 3 is a front view of the utility mount light.
 FIG. 4 is a side view of the utility mount light.
 FIG. 5 is a rear view of the utility mount light.
 FIG. 6 is a second front perspective view with a door of a battery support portion of the utility mount light removed.

2

FIG. 7 is a side view of a cross section taken along line 7-7 in FIG. 3.

FIG. 8 is a perspective view of the utility mount light with the handle in an open or extended position.

Before any embodiments of the invention are explained in detail, it is to be understood that the invention is not limited in its application to the details of construction and the arrangement of components set forth in the following description or illustrated in the following drawings. The invention is capable of other embodiments and of being practiced or of being carried out in various ways. Also, it is to be understood that the phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting.

DETAILED DESCRIPTION

FIGS. 1-5 illustrate a utility mount light 10 including a main housing 14, a handle portion 18 supporting a handle 22, a pair of rotatable light head assemblies 26, and a battery support portion 30 configured to detachably couple a battery pack (not shown). As explained in greater detail below, the utility mount light 10 is configured to be attached to a bucket of an elevated work platform (i.e., boom lift, man lift, basket crane, hydraladder, cherry picker, etc.), other components such as tables, or to a workpiece using the handle 22. For convenience, the component to which the light 10 attaches will hereinafter be referred to as a workpiece. Once the light 10 is mounted to the workpiece, the rotatable light head assemblies 26 may be rotated as desired to illuminate a work area.

With reference to FIGS. 1 and 2, the light assemblies 26 each include a light housing 38 that is pivotally coupled between two opposed arms of a yoke 42 for pivoting motion about a first pivot axis A such that a direction of the light housing 38 is adjustable by a user. Each of the light housings 38 is independently rotatable to enhance the ability to direct the light as desired. In one embodiment, a pivoting range of the light housing 38 within the yoke 42 may be limited to approximately 180° about the first pivot axis A (e.g., via stops within the yoke 42). In another embodiment, the light housing 38 may pivot 360° about the first pivot axis A within the yoke 42. In other embodiments, the light housing 38 may have a discrete pivot range about the first pivot axis A within the yoke 42 (e.g., any discrete pivot range between 0-360°).

The yoke 42 is further coupled to the main housing 14 via a joint 46 that may be rotatable about a second pivot axis B that is orthogonal to the first pivot axis A such that a rotational orientation of the yoke 42 is adjustable by a user. In some embodiments, the yoke 42 is coupled to the main housing via a joint 46 that is rotatable 360° about the second pivot axis B. In other embodiments, the yoke 42 is coupled to the main housing 14 via a joint 46 that limits rotation (e.g., using stops in the joint 46). For example, rotation may be limited to discrete angles less than 360° but more than 180°, or rotation may be limited to discrete angles less than or equal to 180°. These configurations allow the light assemblies 26 to be directed in a variety of directions and orientations, and also allow the light assemblies 26 to be movable independently of one another.

In one embodiment, the light housing 38 may be fixed within the yoke 42 (i.e., the light housing is not pivotable) while the yoke 42 is rotatably coupled to the main housing 14 via a joint 46 that permits rotation as described above. In another embodiment, the yoke 42 may be fixedly coupled to the main housing 14 (i.e., the yoke 42 is not rotatable) while the light housing 38 is pivotable within the yoke 42 as

described above. In yet another embodiment, the light housing **38** may be fixed within the yoke **42** (i.e., the light housing is not pivotable) and the yoke **42** may be fixedly coupled to the main housing **14** (i.e., the yoke **42** is not rotatable).

As seen in FIG. **3**, the light assemblies **26** are disposed on opposing sides of the main housing **14** and the battery support portion **30**.

The light housings **38** further support a plurality of lights. The lights may be, for example, spot LEDs, flood LEDs, a fluorescent bulb, an incandescent bulb, or any other suitable lighting elements. In a preferred embodiment, the lights supported within the light housing **30** are a combination of multiple spot LEDs and/or multiple flood LEDs configured to be operated separately and/or in tandem. The lights may be surrounded by a light guide disposed within the housing that directs light through lenses **50** of the light assemblies **26**.

With reference to FIGS. **1** and **6**, the battery support portion **30** is formed as one piece with the main housing **14** and is configured to detachably couple the battery pack. In the illustrated embodiment, the battery support portion **30** defines a cavity **54** for receiving the battery pack (FIG. **6**). A door **58** is pivotally coupled to the battery support portion **30** at an open end of the cavity, and is releasably secured to the casing via a latch **62**. The door **58** is further configured to sealingly engage the open end of the cavity such that, when the battery pack is secured within the cavity **54**, no water or contaminants may enter the cavity **54**. The sealed engagement may be accomplished by, for example, providing a gasket, an O-ring, a deformable member, or other sealing member to one or both of the battery support portion **30** and the door **58**. In preferred constructions, the battery pack is a power tool battery pack.

With reference to FIG. **1**, the handle portion **18** includes a power actuator, a first mode actuator, and a second mode actuator (e.g., buttons, trigger switches, knobs, etc.). Each of the actuators may be coupled to a processor supported within the utility mount light **10**. The processor is coupled to the lights within each of the light housings **38** and to the battery pack control to the power supplied by the battery pack to each of the light assemblies. In some constructions, some or all of the actuators may be virtual controls (e.g., touch screens) rather than real buttons, switches, or knobs.

The processor is implemented as a microprocessor including a non-transitory, computer-readable memory that stores executable instructions to carry out functionalities of the utility mount light **10**. The processor **12** may be implemented partially or entirely as, for example, a field-programmable gate array (FPGA), and application specific integrated circuit (ASIC).

The power actuator may be operated by a user to simultaneously turn both light assemblies **26** on or off. The first mode actuator may be successively operated by a user to cycle one of the light assemblies **26** through a plurality of modes, and the second mode actuator may be successively operated by a user to cycle the other light assembly **26** through the plurality of modes. The plurality of modes may include, for example, a spot mode in which spot LEDs are activated, a flood mode in which flood LEDs are activated, spot/flood mode in which both spot LEDs and flood LEDs are activated, and an off mode (i.e., such that each light assembly **26** may be independently turned off). In one embodiment, the plurality of modes may further include brightness modes for one or more of the spot mode, the flood mode, and the spot/flood mode. In another embodiment, the

plurality of modes may be a multiple discrete brightness modes (e.g., low/medium/high, etc.).

In another embodiment, the utility mount light **10** may include separate power actuators for each light, such that there is a first power actuator, a second power actuator, a first mode switch, and a second mode switch. In such an embodiment, the first power actuator controls the on/off state of one of the light assemblies **26**, while the second power actuator controls the on/off state of the other light assembly **26**.

In yet another embodiment, the utility mount light may include a first actuator and a second actuator. In this embodiment, the first actuator is configured to operate one of the light assemblies **26** while the second actuator is configured to operate the other light assembly. The first actuator may be successively operated by a user to turn the light assembly **26** on, cycle the light assembly **26** through a plurality of modes, and turn the light assembly **26** off. The second actuator may be successively operated by a user to turn the other light assembly **26** on, cycle the other light assembly **26** through a plurality of modes, and turn the other light assembly **26** off.

In any of the embodiments described above, it should be clear that each light assembly **26** may be individually operated (i.e., turned on/off) and/or individually cycled through the plurality of modes such that the light assemblies **26** may be in independent operating states.

With reference to FIGS. **2** and **4**, the handle **22** includes a gripping portion **66** defined by an aperture **70** extending through the handle **22**, and a hook portion **74** adjacent the gripping portion **66**. The handle **22** is movably coupled to the handle portion **18** at an end adjacent the gripping portion **66**, and is biased by a constant force or a clock spring **86** (FIG. **7**) toward a closed position (FIG. **4**) where the handle **22** maintains contact with a workpiece and/or an opposing support surface **78** disposed on the main housing **14**. However, in other embodiments, other biasing members such as a torsion spring, a helical spring, or an adjustable spiral spring, among others, may be used in place of or in conjunction with the constant force spring **86**. The handle **22** is movable in a linear direction to an open or extended position (FIG. **8**) away from the support surface **78** (i.e., the handle **22** is linearly extensible). In addition, when the handle **22** is extended away from the support surface **78**, an opening **82** is defined between the handle portion **18**, the handle **22**, and the main housing **14**. The opening **82** is configured to receive a portion or a lip of the work platform (i.e., boom lift, man lift, basket crane, hydaladder, cherry picker, etc.) or the workpiece. In addition, the size of the opening **82** is such that it can receive a variety of differently sized lips.

In operation, the utility mount light **10** may be attached to a work platform or a workpiece using the handle **22**. A user may grasp the gripping portion **66** and the main housing **14**, for example, and pull the handle **22** against the bias of the constant force spring **86** toward the open position to disengage contact between the handle **22** and the support surface **78** to create a gap. The handle **22** and support surface **78** may then be placed on opposing sides of a workpiece or a work platform (i.e., a bucket, etc.) and subsequently released such that the bias of the constant force spring **86** pulls the handle **22** toward the support surface **78** to clamp the work platform or workpiece between the handle **22** and the support surface **78**. In one embodiment, the movable range of the handle **22** may be limited such that the maximum gap is approximately 3.5 inches.

The utility mount light **10** may be detached from a work platform or workpiece by pulling the handle **22** against the bias of the constant force spring **86** to open a gap between the work platform or workpiece and the handle **22** and/or the

5

support surface **78** (i.e., un-clamp the utility mount light **10** form the work platform or workpiece). However, pulling the handle **22** may not be required in some embodiments. For example, the biasing force of the constant force spring **86** may be set such that the spring **86** retracts the handle and provides the desired clamping/frictional force on the work platform or workpiece, but allows the user to detach the utility mount light **10** from the work platform or workpiece by grasping the handle portion **18** and lifting the utility mount light **10** away from the workpiece. Using this method, a user can remove the light **10** with one hand by simply grasping the handle portion **18** and pulling the light upward.

It should be noted that the placement of the gripping portion **66** of the handle **22** adjacent to the handle portion **18** provides certain advantages. This placement reduces the distance between a gripping portion **66** and the spring, thereby reducing rotational torqueing on the handle **22** and the spring during operation thereby increasing the operational life.

In addition, the linearly displaceable handle **22** advantageously allows the utility light **10** to be coupled to work platforms or workpieces of various sizes (e.g., various widths).

Various features of the invention are set forth in the following claims.

What is claimed is:

1. A battery-powered utility light mountable to a workpiece, the utility light comprising:

a main body;

a plurality of lights coupled to the main body, each of the plurality of lights being independently movable relative to the main body;

a first mode actuator that is configured to cycle one of the plurality of lights through a plurality of lighting modes; a second mode actuator that is configured to cycle a different one of the plurality of lights through a plurality of lighting modes separately from the other plurality of lights; and

a hooking element that is moveably coupled to the main body between an open position, in which the workpiece is permitted to be received in an opening, and a closed position, in which the workpiece is inhibited from being removed from the opening,

wherein the opening is disposed between the main body and the hooking element.

2. The utility light of claim **1**, wherein each of the plurality of lights includes a light housing, a lens coupled to the light housing, and one or more lights emitters disposed within the light housing for projecting light through the lens.

3. The utility light of claim **2**, wherein each light housing is pivotable relative to the main body about a light axis, such that the one or more light emitters may project light at various angles relative to the workpiece.

4. The utility light of claim **3**, wherein the hooking element slides between the open position and the closed position along an axial direction that is perpendicular to the light axis.

5. The utility light of claim **1**, wherein the hooking element is biased by a spring toward the closed position.

6. The utility light of claim **5**, wherein the hooking element is moved toward the open position against the bias of the spring by pulling a handle.

7. The utility light of claim **1**, wherein the main body includes a battery receptacle for receiving a battery.

6

8. A battery-powered utility light mountable to a workpiece, the utility light comprising:

a main body;

a first light having a first light housing, a first lens, and a first light emitter within the first light housing for projecting light through the first lens, wherein the first light housing is pivotable relative to the main body about a light axis;

a second light having a second light housing, a second lens, and a second light emitter within the second light housing for projecting light through the second lens, wherein the second light housing is pivotable relative to the main body about the light axis separately from the first light housing;

a hooking element that is translatable relative to the main body along an axial direction that is perpendicular to the light axis, wherein the hooking element facilitates with coupling the main body to the workpiece; and a spring coupled to the hooking element to bias the hooking element toward the main body.

9. The utility light of claim **8**, wherein the hooking element is translatable between an open position, in which the workpiece is permitted to be received in an opening, and a closed position, in which the workpiece is inhibited from being removed from the opening.

10. The utility light of claim **9**, wherein the opening is between the main body and the hooking element.

11. The utility light of claim **9**, wherein the hooking element is biased toward the closed position by the spring.

12. The utility light of claim **11**, wherein the hooking element is moved toward the open position against the bias of the spring by pulling a handle.

13. The utility light of claim **12**, wherein the handle is coupled to the hooking element.

14. The utility light of claim **8**, wherein the main body includes a battery receptacle for receiving a battery.

15. A battery-powered utility light mountable to a workpiece, the utility light comprising:

a main body;

a plurality of lights coupled to the main body, each of the plurality of lights being independently movable relative to the main body;

a first mode actuator that is configured to cycle one of the plurality of lights through a plurality of lighting modes; a second mode actuator that is configured to cycle a different one of the plurality of lights through a plurality of lighting modes separately from the other plurality of lights; and

an opening formed by at least a portion of the main body and configured to selectively receive the workpiece, wherein the opening is opened to allow the workpiece to be received within the opening adjacent the main body, and

wherein the opening is closed to inhibit the workpiece from being removed from the opening adjacent the main body.

16. The utility light of claim **15**, further comprising a hooking element that is moveable to open and close the opening.

17. The utility light of claim **16**, wherein the plurality of lights are independently pivotable relative to the main body about a light axis.

18. The utility light of claim **17**, wherein the hooking element is translatable along an axial direction that is perpendicular to the light axis.

19. The utility light of claim **18**, wherein the hooking element is biased along the axial direction via a spring to close the opening.

20. The utility light of claim 19, wherein the hooking element is moved against the bias of the spring by pulling a handle coupled to the hooking element.

* * * * *