

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
22 July 2010 (22.07.2010)

PCT

(10) International Publication Number
WO 2010/083124 A1

(51) International Patent Classification:

C11D 3/22 (2006.01) *C11D 3/50* (2006.01)
C11D 3/39 (2006.01) *C11D 17/00* (2006.01)

(21) International Application Number:

PCT/US2010/020618

(22) International Filing Date:

11 January 2010 (11.01.2010)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

09150731.9 16 January 2009 (16.01.2009) EP
09178786.1 11 December 2009 (11.12.2009) EP

(71) Applicant (for all designated States except US): **THE PROCTER & GAMBLE COMPANY** [US/US]; One Procter & Gamble Plaza, Cincinnati, Ohio 45202 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BIANCHETTI, Giulia, Ottavia** [IT/IT]; Via Catarina Troiani 250, I-00144 Rome (IT). **EVERS, Marc, Francois Theophile** [BE/BE]; Lakensestraat 37, B-1853 Strombeek-Bever (BE). **SMETS, Johan** [BE/BE]; Bollenberg 79, B-3210 Lubbeek (BE). **GRANDE, Giovanni** [IT/IT]; Via Giuditta Rissone 39/A, I-00125 Rome (IT).

(74) Common Representative: **THE PROCTER & GAMBLE COMPANY**; c/o Eileen L. Hughett, Global Patent

Services, 299 East Sixth Street, Sycamore Building, 4th Floor, Cincinnati, Ohio 45202 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: BLEACHING COMPOSITIONS CONTAINING PERFUME MICROCAPSULES

(57) Abstract: Liquid compositions, which are chemically and physically stable, comprising peroxygen bleach, perfume microcapsules and less than 10% of surfactant by weight of the total composition. The perfumes microcapsules, preferably, comprise a polymeric outer shell made of the condensation of melamine and formaldehyde. Process for laundering fabrics comprising the step of contacting the fabrics with said bleaching compositions.



WO 2010/083124 A1

BLEACHING COMPOSITIONS CONTAINING PERFUME MICROCAPSULES

TECHNICAL FIELD

5

The present invention relates to bleaching compositions, more particularly to peroxygen bleach-containing compositions comprising perfume microcapsules.

BACKGROUND OF THE INVENTION

10

Peroxygen bleach-containing compositions have been extensively described in laundry applications as laundry detergents, laundry additives or even laundry pretreaters. Many bleach compositions, including peroxygen bleach-containing compositions, comprise a perfume for the purpose of delivering a pleasant smell in addition to the whitening performance; but also for the purpose of improving the overall consumer acceptance of bleaching compositions.

15

Indeed, nowadays, having a good perfume is of such importance for consumers that some compositions might have as a main purpose to impart a pleasant smell to laundry. Therefore, it would be a significant advancement in the art to provide a composition which gives a pleasant smell to laundry in addition to excellent whitening and cleaning performances. However, the incorporation of some ingredients, such as perfumes, into conventional bleaching compositions has always been problematic due to the tendency of bleaching compositions to chemically react with these specific ingredients.

20

Most of the time, the addition of these compounds leads bleaching compositions to be unstable. More particularly, such bleaching composition will be chemically unstable: the active ingredients will have the tendency to diminish upon time, leading therefore to a less efficient composition. This effect is particularly significant in the case of incorporation of perfume. The perfume will react with the bleaching component upon storage and will result in compositions which do not have the desired benefit, i.e., the delivery of a good perfume to the laundry treated thereby.

25

30

Several different methods have been used to overcome this problem. One of these methods, in view of introducing perfumes in detergent and bleaching compositions, is the use of microcapsules and/or compounds in a form of particles with perfumes encapsulated therein. The

following documents are representative of the prior art available on bleaching composition comprising perfume microcapsules:

WO 00/032735, published on June 8th, 2000, discloses a bleaching formulation containing perfume in a microencapsulated form.

- 5 US 2003/012222, published on July 3rd, 2003, relates to detergents and cleaning agents comprising capsules having a core of a hydrophobic material which encloses at least one perfume.

10 However, the addition to bleaching compositions of such microcapsules and/or compounds in a form of particles, has a tendency to lead to products which are physically unstable. Indeed, these bleaching compositions will have the tendency to sediment and/or settle out, especially during storage and/or transportation. Furthermore, the addition to bleaching compositions of such microcapsules and/or compounds in a form of particles, will often result in compositions which are not homogenous and/or in compositions forming layer at its surfaces.

15 Accordingly, there is a need to formulate bleaching compositions having stably suspended perfume microcapsules. This need for stably suspended perfume microcapsules encompasses both physical stability and chemical stability.

The present invention provides, therefore, a stable bleaching composition which, in the same time, delivers a good perfume to the laundry treated thereby and which have excellent bleaching
20 performance.

SUMMARY OF THE INVENTION

25 The present invention fulfils the needs identified above by providing a liquid composition comprising peroxygen bleach, perfume microcapsules and less than 10% of surfactant by weight of the total composition and wherein the composition further comprises a polysaccharide polymer. The microcapsules of the present invention comprise, preferably, a polymeric outer shell made of the condensation of melamine and formaldehyde.

30 Surprisingly, it has been found that by incorporating the microcapsules of the present invention in a peroxygen bleaching composition comprising less than 10% of surfactant by weight of the total composition, the perfume microcapsule can be stably suspended. By stably suspending the microcapsules in the bleaching products, the perfume microcapsules within the bleaching

composition have a reduced tendency to sediment and/or settle out of the products during storage and/or transportation.

As a result of the microcapsules having a reduced tendency to sediment and/or settle out of the bleaching composition products, consumers have more consistent perfumes which will be deposited on the laundry treated thereby. Further, as a result of the microcapsules having a reduced tendency to sediment and/or settle out of the bleaching composition products, the appearance of the product will stay homogenous.

In another aspect, the present invention relates also to a process for laundering fabrics comprising the step of contacting the fabrics with the bleaching compositions of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

The present invention relates to liquid composition comprising peroxygen bleach, perfume microcapsules, a polysaccharide polymer, less than 10% of surfactant by weight of the total composition.

The bleaching compositions of the present invention are chemically stable and physically stable. By "chemically stable", it is meant that the composition will have limited perfume leakage and that the active ingredients, contained in said composition, such as the perfume, will not have the tendency to disappear upon time.

Furthermore, by "chemically stable", it is meant also herein that there is virtually no chemical changes of the different ingredients due to reaction between them. It is meant also that said compositions of the present invention comprising peroxygen bleach do not undergo more than 20% available oxygen loss at 50°C in 2 weeks. Chemical stability of the compositions herein may be evaluated by measuring the concentration of available oxygen at given storage time after having manufactured the compositions. The concentration of available oxygen can be measured by chemical titration methods known in the art, such as the iodimetric method, the permanganometric method and the cerimetric method. Said methods and the criteria for the choice of the appropriate method are described for example in "Hydrogen Peroxide", W. C. Schumb, C. N. Satterfield and R. L. Wentworth, Reinhold Publishing Corporation, New York, 1955 and "Organic Peroxides", Daniel Swern, Editor Wiley Int. Science, 1970. Alternatively, the chemical stability of said compositions may also be evaluated by visually observing bulging of the container or bottle containing it.

The bleaching compositions of the present invention are physically stable. By "physically stable" it is meant herein that the compositions of the present invention do not split in two or more phases when exposed in stressed conditions, e.g., at a temperature of 40 °C during 2 weeks. By
5 "physically stable", it is meant also that the compositions of the invention do not sediment and/or settle out, especially during storage and/or transportation. Furthermore, it means also that the microcapsules will remain in suspension in the composition, the product will thus stay homogenous.

10 The Liquid Compositions

The bleaching composition according to the present invention is formulated as a liquid composition. By "liquid" it is meant to include liquids, gels and pastes.

The bleaching compositions herein are preferably, but not necessarily, formulated as aqueous compositions. Liquid bleaching compositions are preferred herein for convenience of use.

15 Preferred liquid bleaching compositions of the present invention are aqueous and therefore, preferably may comprise water, more preferably may comprise water in an amount of from 60% to 98%, even more preferably of from 80% to 97% and most preferably 85% to 97% by weight of the total composition.

20 In a preferred embodiment the liquid compositions according to the present invention are formulated in the neutral to the acidic pH range, i.e. the pH of the present composition is preferably between 3 and 9, more preferably between 4 and 6 when measured at 25°C on neat composition. It is within this neutral to acidic pH range that the optimum chemical stability and bleaching and/or cleaning performance of the peroxygen bleach are obtained.

25 More precisely, the pH of the liquid bleaching compositions herein, as is measured at 25°C on neat product, preferably is at least, with increasing preference in the order given, 0.1, 0.5, 1, 1.5, 2, 2.5, 3, 3.5, 4, 4.5 or 5.

Independently, the pH of the liquid bleaching compositions herein, as is measured at 25°C on neat product, preferably is no more than, with increasing preference in the order given, 9, 8.5, 8,
30 7.5, 7, 6.5, 6 or 5.5.

Accordingly, the compositions herein may further comprise an acid or a base to adjust the pH as appropriate. Preferred acids herein are organic or inorganic acids or mixtures thereof. Preferred

organic acids are acetic acid, citric acid or a mixture thereof. Preferred inorganic acids are sulfuric acid, phosphoric acid or a mixture thereof. A particularly preferred acid to be used herein is an inorganic acid and most preferred is sulfuric acid. Typical levels of such acids, when present, are of from 0.01% to 3.0%, preferably from 0.05% to 2.0% and more preferably from 0.1% to 1.0% by weight of the total composition. The bases to be used herein can be organic or inorganic bases. Suitable bases for use herein are the caustic alkalis, such as sodium hydroxide, potassium hydroxide and/or lithium hydroxide, and/or the alkali metal oxides such, as sodium and/or potassium oxide or mixtures thereof. A preferred base is a caustic alkali, more preferably sodium hydroxide and/or potassium hydroxide. Other suitable bases include ammonia, ammonium carbonate and hydrogen carbonate. Typical levels of such bases, when present, are of from 0.01% to 1.0%, preferably from 0.05% to 0.8% and more preferably from 0.1% to 0.5% by weight of the total composition.

Peroxygen Bleach

As an essential element the bleaching compositions according to the present invention comprise peroxygen bleach. The presence of peroxygen bleach providing excellent bleaching and cleaning benefits.

Suitable peroxygen bleaches to be used herein are, preferably, selected from the group consisting of: hydrogen peroxide; water soluble sources of hydrogen peroxide; organic or inorganic peracids; hydroperoxides; diacyl peroxides; and mixtures thereof. As used herein a hydrogen peroxide source refers to any compound that produces perhydroxyl ions on contact with water. Suitable water-soluble sources of hydrogen peroxide for use herein include percarbonates, perborates and persilicates and mixtures thereof.

Suitable diacyl peroxides for use herein include aliphatic, aromatic and aliphatic-aromatic diacyl peroxides, and mixtures thereof.

Suitable aliphatic diacyl peroxides for use herein are dilauroyl peroxide, didecanoyl peroxide, dimyristoyl peroxide, or mixtures thereof. Suitable aromatic diacyl peroxide for use herein is for example benzoyl peroxide. Suitable aliphatic-aromatic diacyl peroxide for use herein is for example lauroyl benzoyl peroxide.

Suitable organic or inorganic peracids for use herein include: persulphates such as monopersulfate; peroxyacids such as diperoxydodecandioic acid (DPDA); magnesium perphthalic acid; perlauric acid; phthaloyl amidoperoxy caproic acid (PAP); perbenzoic and alkylperbenzoic acids; and mixtures thereof.

Suitable hydroperoxides for use herein are tert-butyl hydroperoxide, cumyl hydroperoxide, 2,4,4-trimethylpentyl-2-hydroperoxide, di-isopropylbenzene-monohydroperoxide, tert-amyl hydroperoxide and 2,5-dimethyl-hexane-2,5-dihydroperoxide and mixtures thereof. Such hydroperoxides have the advantage of being particularly safe to fabrics and color while
5 delivering excellent bleaching performance when used in any laundry application.

A preferred peroxygen bleach herein is selected from the group consisting of: hydrogen peroxide; water-soluble sources of hydrogen peroxide; organic or inorganic peracids; hydroperoxides; and diacyl peroxides; and mixtures thereof.

A more preferred peroxygen bleach herein is selected from the group consisting of hydrogen
10 peroxide, water-soluble sources of hydrogen peroxide and diacyl peroxides and mixtures thereof.

An even more preferred peroxygen bleach herein is selected from the group consisting of hydrogen peroxide, water soluble sources of hydrogen peroxide, aliphatic diacyl peroxides, aromatic diacyl peroxides and aliphatic-aromatic diacyl peroxides and mixtures thereof. The most preferred peroxygen bleach herein is hydrogen peroxide, water-soluble sources of hydrogen
15 peroxide or mixtures thereof.

The liquid compositions according to the present invention comprise from 0.1% to 30% by weight of the total composition of said peroxygen bleach. Preferably, the bleaching composition herein may comprise from 1% to 20%, preferably from 2% to 15%, more preferably from 3% to 10% by weight of the total composition of said peroxygen bleach.

The presence of peroxygen bleach in bleaching compositions according to the present invention contributes to the excellent bleaching and/or cleaning performance on various types of soils including on spot stains like bleachable stains (e.g., coffee, beverage, food) of the compositions of the present invention. Furthermore, peroxygen bleaches are chosen herein as oxidising agents over other oxidising agents, as for example hypohalite bleaches, as they are considered as being
25 safer to fabrics, specifically to coloured fabrics.

By "bleachable stains" it is meant herein any soils or stains containing ingredients sensitive to bleach that can be found on any carpet, e.g., coffee or tea.

The perfume microcapsule

The liquid compositions of the present invention comprise as an essential ingredient a perfume
30 microcapsule. By "perfume microcapsule", it is meant, herein, a perfume that is encapsulated in a microcapsule.

The perfume microcapsule of the present invention comprises a core material, which enclosed at least one perfume, and a wall material, the shell, that at least partially surrounds said core material.

The wall material of the present invention has a certain combination of physical and chemical characteristics. The physical and chemical characteristics of the capsules shell are fracture strength, particle size, particle wall thickness and perfume microcapsule leakage. This physical and chemical characteristics can be evaluated by the techniques and process commonly used by the skilled person in the art. Therefore, as tested in accordance with applicants test methods, at least 75%, 85% or even 90% of said microcapsule have a fracture strength of from 0.2 MPa to 30.0 MPa, from 0.4 MPa to 10.0 MPa, from 0.6 MPa to 8.0MPa, or even from 0.7 MPa to 7.0MPa; and a microcapsule leakage of from 0% to 30%, from 0% to 20%, or even from 0% to 5%. In one aspect of the present invention, at least 75%, 85% or even 90% of said perfume microcapsule have a particle size of from 1 microns to 80 microns, 5 microns to 60 microns, from 6 microns to 50 microns, or even from 8 microns to 40 microns.

In one other aspect of the present invention, at least 75%, 85% or even 90% of said microcapsule have a wall thickness of from 40 nm to 250 nm, from 50 nm to 180 nm, or even from 60 nm to 160 nm.

In one embodiment of the invention, the wall material of the microcapsules comprises a suitable resin including the reaction product of an aldehyde and an amine. According to the present invention, suitable aldehydes include formaldehyde; and suitable amines include melamine, urea, benzoguanamine, glycoluril, and mixtures thereof. Suitable melamines include, methylol melamine, methylated methylol melamine, imino melamine and mixtures thereof. Suitable ureas include, dimethylol urea, methylated dimethylol urea, urea-resorcinol, and mixtures thereof. Suitable materials for making may be obtained from one or more of the following companies Solutia Inc. (St Louis, Missouri U.S.A.), Cytec Industries (West Paterson, New Jersey U.S.A.), sigma-Aldrich (St. Louis, Missouri U.S.A.).

In a preferred embodiment of the present invention, the wall of the microcapsule is made of the condensation of melamine and formaldehyde.

In one aspect of the invention, the core of the perfume microcapsule comprises a material selected from the group consisting of a perfume raw material.

In one aspect of the present invention, said perfume microcapsule comprise, based on total particle weight, from 20% to 95%, from 50% to 90%, from 70% to 85%, or even from 80% to 85% by weight of a perfume composition.

Suitable perfumes for use herein include materials which provide an olfactory aesthetic benefit and/or help to cover any "chemical" odour that the product may have. By perfume is meant, thus, any substance which has the desired olfactory property. Such substances include all fragrances or perfumes that are commonly used in perfumery or in laundry detergent or cleaning product compositions.

Such perfume may have a natural, semi-synthetic or synthetic origin. Preferably, perfumes are selected from the class of substance comprising the hydrocarbons, aldehydes or esters.

The perfume of the present invention also include natural extracts and/or essences, which may comprise complex mixtures of constituents, such as orange oil, lemon oil, rose extract, lavender, musk, patchouli, balsam essence, sandalwood oil, pine oil, and cedar oil. The perfumes, according to the present invention, can be used as single substances or in a mixture with one another.

The core of the microcapsules may thus comprise only perfume as the sole hydrophobic material or, alternatively, the core of the microcapsules may, in addition to the perfume, include a further hydrophobic material in which the perfume is dissolved or dispersed.

The hydrophobic materials, which can be used as core material in addition to the fragrance or perfume, include all types of oils, such as vegetable oils, animal oils, mineral oils, paraffins, chloroparaffins, fluorocarbons, and other synthetic oils.

Such material may be selected from the group consisting of vegetable oil, including neat and/or blended vegetable oils including castor oil, coconut oil, cottonseed oil, grape oil, rapeseed, soybean oil, corn oil, palm oil, linseed oil, safflower oil, olive oil, peanut oil, coconut oil, palm kernel oil, castor oil, lemon oil and mixtures thereof; esters of vegetable oils, esters, including dibutyl adipate, dibutyl phthalate, butyl benzyl adipate, benzyl octyl adipate, tricresyl phosphate, trioctyl phosphate and mixtures thereof; straight or branched chain hydrocarbons, including those straight or branched chain hydrocarbons having a boiling point of greater than 80°C; partially hydrogenated terphenyls, dialkyl phthalates, alkyl biphenyls, including monoisopropylbiphenyl, alkylated naphthalene, including dipropyl naphthalene, petroleum spirits, including kerosene, mineral oil and mixtures thereof; aromatic solvents, including benzene, toluene and mixtures thereof; silicone oils; and mixtures thereof.

The perfume ingredients and compositions suitable to be used herein are the conventional ones known in the art. Selection of any perfume component, or amount of perfume, is mainly based on aesthetic considerations.

Suitable perfume compounds and compositions can be found in the art including U.S. Pat. No. 4,145,184, Brain and Cummins, issued Mar. 20, 1979; U.S. Pat. No. 4,209,417, Whyte, issued Jun. 24, 1980; U.S. Pat. No. 4,515, 705, Moeddel, issued May 7, 1985; and U.S. Pat. No. 4,152,272, Young, issued May 1, 1979.

5

Polysaccharide Polymer

The liquid compositions of the present invention comprise, as an important ingredient, a polysaccharide polymer or a mixture thereof. The presence of such polymer provides improved physical stability of the composition.

- 10 Preferably, the compositions of the present invention comprise from 0.01% to 10% by weight of the total composition of a polysaccharide polymer or a mixture thereof, more preferably from 0.05% to 5% and most preferably from 0.1% to 2%.

Suitable polysaccharide polymers for use herein include substituted cellulose materials like carboxymethylcellulose, ethyl cellulose, hydroxyethyl cellulose, hydroxypropyl cellulose, 15 hydroxymethyl cellulose, succinoglycan and naturally occurring polysaccharide polymers like xanthan gum, guar gum, locust bean gum, tragacanth gum or derivatives thereof, or mixtures thereof.

In one embodiment, the polysaccharide polymer is selected from the group constitutive of carboxymethylcellulose, ethyl cellulose, hydroxyethyl cellulose, hydroxypropyl cellulose, 20 hydroxymethyl cellulose, succinoglycan and naturally occurring polysaccharide polymers like xanthan gum, guar gum, locust bean gum, tragacanth gum or derivatives thereof, or mixtures thereof

Particularly preferred polysaccharide polymers for use herein are xanthan gum and derivatives thereof.

- 25 Xanthan gum and derivatives thereof may be commercially available for instance from Kelco under the trade name Keltrol RD[®], Keizan S[®] or Kelzan T[®]. Other suitable Xanthan gum are commercially available from Rhone Poulenc under the trade name Rhodopol T[®] and Rhodigel X747[®]. Succinoglycan gum for use herein is commercially available from Rhone Poulenc under the trade name Rheozan[®].

- 30 In one embodiment, polysaccharide polymers for use herein are selected from the group comprising carboxymethylcellulose, ethyl cellulose, hydroxyethyl cellulose, hydroxypropyl cellulose, hydroxymethyl cellulose, succinoglycan and naturally occurring polysaccharide

polymers, said naturally occurring polymers being selected from the group comprising xanthan gum, guar gum, locust bean gum, tragacanth gum or derivatives thereof, or mixtures thereof.

Surfactants

- 5 The compositions of the present invention comprise as an essential ingredient surfactants or a mixture thereof.

The compositions will comprise from 0.001% to 10%, preferably from 0.01% to 7% and more preferably from 0.5% to 5% by weight of the total composition of surfactant or a mixture thereof.

- 10 The presence of surfactants, in such specific amount, is necessary to provide excellent cleaning performance as well as a good physical stability of the composition.

Suitable surfactants for use herein include any nonionic, anionic, zwitterionic, cationic and/or amphoteric surfactants. Particularly suitable surfactants for use herein are nonionic surfactants such as alkoxyated nonionic surfactants and/or polyhydroxy fatty acid amide surfactants and/or
15 amine oxides and/or zwitterionic surfactants like the zwitterionic betaine surfactants described herein after.

- Suitable nonionic surfactants include alkoxyated nonionic surfactants. Preferred alkoxyated nonionic surfactants herein are ethoxyated nonionic surfactants according to the formula RO-
20 $(C_2H_4O)_nH$, wherein R is a C_6 to C_{22} alkyl chain or a C_6 to C_{28} alkyl benzene chain, and wherein n is from 0 to 20, preferably from 1 to 15 and, more preferably from 2 to 15 and most preferably from 2 to 12. The preferred R chains for use herein are the C_8 to C_{22} alkyl chains. Propoxyated nonionic surfactants and ethoxy/propoxyated ones may also be used herein instead of the ethoxyated nonionic surfactants as defined herein above or together with said surfactants

- 25 Preferred ethoxyated nonionic surfactants are substantially linear ethoxyated nonionic surfactants according to the above formula. By "linear" it is meant herein that the fatty alcohols used as a basis of the nonionic surfactant (raw material) at least 90%, preferably at least 95%, more preferably at least 97%, and most preferably 100% by weight of the total amount of fatty alcohols of linear (i.e., straight chain) fatty alcohols.

- 30 Suitable substantially linear ethoxyated nonionic surfactants for use herein are Marlipal[®] 24-7 (R is a mixture of linear C_{12} and C_{14} alkyl chains, n is 7), Marlipal[®] 24-4 (R is a mixture of linear C_{12} and C_{14} alkyl chains, n is 4), Marlipal[®] 24-3 (R is a mixture of linear C_{12} and C_{14} alkyl chains, n is 3), Marlipal[®] 24-2 (R is a mixture of linear C_{12} and C_{14} alkyl chains, n is 2), or

mixtures thereof. Preferred herein are Marlipal[®] 24-7, Marlipal[®] 24-4, or mixtures thereof. These Marlipal[®] surfactants are commercially available from Condea.

Preferred ethoxylated nonionic surfactants are according to the formula above and have an HLB (hydrophilic-lipophilic balance) below 16, preferably below 15, and more preferably below 14.

5 Those ethoxylated nonionic surfactants have been found to provide good grease cutting properties.

Accordingly suitable ethoxylated nonionic surfactants for use herein are Dobanol[®] or Lutensol[®] ethoxylated nonionic surfactant series. Preferred herein are Dobanol[®] 91-2.5, or Lutensol[®] TO3, or Lutensol[®] AO3, or Tergitol[®] 25L3, or Dobanol[®] 23-3, or Dobanol[®] 23-2, or Dobanol[®] 45-7,
10 Dobanol[®] 91-8, or Dobanol[®] 91-10, or Dobanol[®] 91-12, or mixtures thereof. These Dobanol[®] surfactants are commercially available from SHELL. These Lutensol[®] surfactants are commercially available from BASF and these Tergitol[®] surfactants are commercially available from UNION CARBIDE.

Suitable chemical processes for preparing the alkoxyated nonionic surfactants for use herein
15 include condensation of corresponding alcohols with alkylene oxide, in the desired proportions. Such processes are well known to the man skilled in the art and have been extensively described in the art.

Suitable zwitterionic betaine surfactants for use herein contain both a cationic hydrophilic group,
20 i.e., a quaternary ammonium group, and anionic hydrophilic group on the same molecule at a relatively wide range of pH's. The typical anionic hydrophilic groups are carboxylates and sulphonates, although other groups like sulfates, phosphonates, and the like can be used. A generic formula for the zwitterionic betaine surfactant to be used herein is : $R^1-N+(R^2)(R^3)R^4X-$ wherein R^1 is a hydrophobic group; R^2 is hydrogen, C_1-C_6 alkyl, hydroxy alkyl or other substituted C_1-C_6 alkyl group; R^3 is C_1-C_6 alkyl, hydroxy alkyl or other substituted C_1-C_6 alkyl
25 group which can also be joined to R^2 to form ring structures with the N, or a C_1-C_6 sulphonate group; R^4 is a moiety joining the cationic nitrogen atom to the hydrophilic group and is typically an alkylene, hydroxy alkylene, or polyalkoxy group containing from 1 to 10 carbon atoms; and X is the hydrophilic group, which is a carboxylate or sulphonate group.

30 Preferred hydrophobic groups R^1 are aliphatic or aromatic, saturated or unsaturated, substituted or unsubstituted hydrocarbon chains that can contain linking groups such as amido groups, ester groups. More preferred R^1 is an alkyl group containing from 1 to 24 carbon atoms, preferably from 8 to 18, and more preferably from 10 to 16. These simple alkyl groups are preferred for cost

and stability reasons. However, the hydrophobic group R^1 can also be an amido radical of the formula $Ra-C(O)-NH-(C(Rb)_2)_m$, wherein Ra is an aliphatic or aromatic, saturated or unsaturated, substituted or unsubstituted hydrocarbon chain, preferably an alkyl group containing from 8 up to 20 carbon atoms, preferably up to 18, more preferably up to 16, Rb is selected from the group consisting of hydrogen and hydroxy groups, and m is from 1 to 4, preferably from 2 to 3, more preferably 3, with no more than one hydroxy group in any $(C(Rb)_2)$ moiety.

Preferred R^2 is hydrogen, or a C_1 - C_3 alkyl and more preferably methyl. Preferred R^3 is C_1 - C_4 sulphonate group, or a C_1 - C_3 alkyl and more preferably methyl. Preferred R^4 is $(CH_2)_n$ wherein n is an integer from 1 to 10, preferably from 1 to 6, more preferably is from 1 to 3.

Suitable anionic surfactants to be used in the compositions herein include water-soluble salts or acids of the formula $ROSO_3M$ wherein R preferably is a C_{10} - C_{24} hydrocarbyl, preferably an alkyl or hydroxyalkyl having a C_{10} - C_{20} alkyl component, more preferably a C_{12} - C_{18} alkyl or hydroxyalkyl, and M is H or a cation, e.g., an alkali metal cation (e.g., sodium, potassium, lithium), or ammonium or substituted ammonium (e.g., methyl-, dimethyl-, and trimethyl ammonium cations and quaternary ammonium cations, such as tetramethyl-ammonium and dimethyl piperdinium cations and quaternary ammonium cations derived from alkylamines such as ethylamine, diethylamine, triethylamine, and mixtures thereof, and the like). Typically, alkyl chains of C_{12-16} are preferred for lower wash temperatures (e.g., below $50^\circ C$) and C_{16-18} alkyl chains are preferred for higher wash temperatures (e.g., above $50^\circ C$).

Other suitable anionic surfactants for use herein are water-soluble salts or acids of the formula $RO(A)_mSO_3M$ wherein R is an unsubstituted C_{10} - C_{24} alkyl or hydroxyalkyl group having a C_{10} - C_{24} alkyl component, preferably a C_{12} - C_{20} alkyl or hydroxyalkyl, more preferably C_{12} - C_{18} alkyl or hydroxyalkyl, A is an ethoxy or propoxy unit, m is greater than zero, typically between 0.5 and 6, more preferably between 0.5 and 3, and M is H or a cation which can be, for example, a metal cation (e.g., sodium, potassium, lithium, calcium, magnesium, etc.), ammonium or substituted-ammonium cation. Alkyl ethoxylated sulfates as well as alkyl propoxylated sulfates are contemplated herein. Specific examples of substituted ammonium cations include methyl-, dimethyl-, trimethyl-ammonium and quaternary ammonium cations, such as tetramethyl-ammonium, dimethyl piperdinium and cations derived from alkanolamines such as ethylamine, diethylamine, triethylamine, mixtures thereof, and the like. Exemplary surfactants are C_{12} - C_{18} alkyl polyethoxylate (1.0) sulfate (C_{12} - $C_{18}E(1.0)SM$), C_{12} - C_{18} alkyl polyethoxylate (2.25) sulfate (C_{12} - $C_{18}E(2.25)SM$), C_{12} - C_{18} alkyl polyethoxylate (3.0) sulfate (C_{12} - $C_{18}E(3.0)SM$), and C_{12} - C_{18}

alkyl polyethoxylate (4.0) sulfate (C_{12} - $C_{18}E(4.0)SM$), wherein M is conveniently selected from sodium and potassium.

Other suitable anionic surfactants for use herein are sulphonated anionic surfactants. Suitable sulphonated anionic surfactants for use herein include alkyl sulphonates, alkyl aryl sulphonates, naphthalene sulphonates, alkyl alkoxyated sulphonates, C_6 - C_{20} alkyl alkoxyated linear or branched diphenyl oxide disulphonates, or mixtures thereof. Suitable alkyl sulphonates for use herein include water-soluble salts or acids of the formula RSO_3M wherein R is a C_6 - C_{20} linear or branched, saturated or unsaturated alkyl group, preferably a C_8 - C_{18} alkyl group and more preferably a C_{14} - C_{17} alkyl group, and M is H or a cation, e.g., an alkali metal cation (e.g., sodium, potassium, lithium), or ammonium or substituted ammonium (e.g., methyl-, dimethyl-, and trimethyl ammonium cations and quaternary ammonium cations, such as tetramethyl-ammonium and dimethyl piperdinium cations and quaternary ammonium cations derived from alkylamines such as ethylamine, diethylamine, triethylamine, and mixtures thereof, and the like).

Suitable alkyl aryl sulphonates for use herein include water-soluble salts or acids of the formula RSO_3M wherein R is an aryl, preferably a benzyl, substituted by a C_6 - C_{20} linear or branched saturated or unsaturated alkyl group, preferably a C_8 - C_{18} alkyl group and more preferably a C_{10} - C_{16} alkyl group, and M is H or a cation, e.g., an alkali metal cation (e.g., sodium, potassium, lithium, calcium, magnesium and the like) or ammonium or substituted ammonium (e.g., methyl-, dimethyl-, and trimethyl ammonium cations and quaternary ammonium cations, such as tetramethyl-ammonium and dimethyl piperdinium cations and quaternary ammonium cations derived from alkylamines such as ethylamine, diethylamine, triethylamine, and mixtures thereof, and the like).

By "linear alkyl sulphonate" it is meant herein a non-substituted alkyl sulphonate wherein the alkyl chain comprises from 6 to 20 carbon atoms, preferably from 8 to 18 carbon atoms, and more preferably from 14 to 17 carbon atoms, and wherein this alkyl chain is sulphonated at one terminus.

Suitable alkoxyated sulphonate surfactants for use herein are according to the formula $R(A)_mSO_3M$ wherein R is an unsubstituted C_6 - C_{20} alkyl, hydroxyalkyl or alkyl aryl group, having a linear or branched C_6 - C_{20} alkyl component, preferably a C_{12} - C_{20} alkyl or hydroxyalkyl, more preferably C_{12} - C_{18} alkyl or hydroxyalkyl, A is an ethoxy or propoxy or butoxy unit, m is greater than zero, typically between 0.5 and 6, more preferably between 0.5 and 3, and M is H or

a cation which can be, for example, a metal cation (e.g., sodium, potassium, lithium, calcium, magnesium, etc.), ammonium or substituted-ammonium cation. Alkyl ethoxylated sulphonates, alkyl butoxylated sulphonates as well as alkyl propoxylated sulphonates are contemplated herein. Specific examples of substituted ammonium cations include methyl-, dimethyl-, trimethyl-
5 ammonium and quaternary ammonium cations, such as tetramethyl-ammonium, dimethyl piperdinium and cations derived from alkanolamines such as ethylamine, diethylamine, triethylamine, mixtures thereof, and the like. Exemplary surfactants are C₁₂-C₁₈ alkyl polyethoxylate (1.0) sulphonate (C₁₂-C₁₈E(1.0) SO₃M), C₁₂-C₁₈ alkyl polyethoxylate (2.25) sulphonate (C₁₂-C₁₈E(2.25) SO₃M), C₁₂-C₁₈ alkyl polyethoxylate (3.0) sulphonate (C₁₂-
10 C₁₈E(3.0) SO₃M), and C₁₂-C₁₈ alkyl polyethoxylate (4.0) sulphonate (C₁₂-C₁₈E(4.0) SO₃M), wherein M is conveniently selected from sodium and potassium. Particularly suitable alkoxyated sulphonates include alkyl aryl polyether sulphonate like Triton X-200[®] commercially available from Union Carbide.

15 Other anionic surfactants suitable herein include sulfosuccinate surfactants, alkyl carboxylate surfactants, sulfosuccinamate surfactants and sulfosuccinamide surfactants.

Suitable alkyl carboxylate surfactants for use herein are according to the formula RCO₂M wherein : R represents a hydrocarbon group selected from the group consisting of straight or branched alkyl radicals containing from 6 to 20, preferably 8 to 18, more preferably 10 to 16,
20 carbon atoms and alkyl phenyl radicals containing from 6 to 18 carbon atoms in the alkyl group. M is H or a cation, e.g., an alkali metal cation (e.g., sodium, potassium, lithium, calcium, magnesium and the like) or ammonium or substituted ammonium (e.g., methyl-, dimethyl-, and trimethyl ammonium cations and quaternary ammonium cations, such as tetramethyl-ammonium and dimethyl piperdinium cations and quaternary ammonium cations derived from alkylamines
25 such as ethylamine, diethylamine, triethylamine, and mixtures thereof, and the like).

Other anionic surfactants useful for deterative purposes can also be used herein. These can include salts (including, for example, sodium, potassium, ammonium, and substituted ammonium salts such as mono-, di- and triethanolamine salts) of soap, sulphonated polycarboxylic acids prepared by sulphonation of the pyrolyzed product of alkaline earth metal
30 citrates, e.g., as described in British patent specification No. 1,082,179, C₈-C₂₄ alkylpolyglycoethersulfates (containing up to 10 moles of ethylene oxide); alkyl ester sulphonates such as C₁₄-₁₆ methyl ester sulphonates; acyl glycerol sulphonates, fatty oleyl glycerol sulfates, alkyl phenol ethylene oxide ether sulfates, alkyl phosphates, isethionates such

as the acyl isethionates, N-acyl taurates, sulfates of alkylpolysaccharides such as the sulfates of alkylpolyglucoside (the nonionic nonsulfated compounds being described below), branched primary alkyl sulfates, alkyl polyethoxy carboxylates such as those of the formula $RO(CH_2CH_2O)_kCH_2COO^-M^+$ wherein R is a C₈-C₂₂ alkyl, k is an integer from 0 to 10, and M is a soluble salt-forming cation. Resin acids and hydrogenated resin acids are also suitable, such as rosin, hydrogenated rosin, and resin acids and hydrogenated resin acids present in or derived from tall oil.

Other suitable anionic surfactants to be used herein also include acyl sarcosinate, in its acid and/or salt form. Being derivatives of natural fatty acids, said acyl sarcosinates are rapidly and completely biodegradable and have good skin compatibility.

Optional ingredients

The compositions herein may further comprise a variety of other optional ingredients such as chelating agents, builders, radical scavengers, antioxidants, bleach activators, soil suspenders polymers, catalysts, brighteners, pigments and dyes.

Chelating agents

The bleaching compositions of the present invention may comprise a chelating agent as a highly preferred optional ingredient.

Suitable chelating agents may be any of those known to those skilled in the art, such as the ones selected from the group comprising phosphonate chelating agents, amino carboxylate chelating agents, other carboxylate chelating agents, polyfunctionally-substituted aromatic chelating agents, ethylenediamine N,N'-disuccinic acids, or mixtures thereof.

Suitable phosphonate chelating agents to be used herein may include alkali metal ethane 1-hydroxy diphosphonates (HEDP), alkylene poly (alkylene phosphonate), as well as amino phosphonate compounds, including amino aminotri(methylene phosphonic acid) (ATMP), nitrilo trimethylene phosphonates (NTP), ethylene diamine tetra methylene phosphonates, and diethylene triamine penta methylene phosphonates (DTPMP). The phosphonate compounds may be present either in their acid form or as salts of different cations on some or all of their acid functionalities. Preferred phosphonate chelating agents to be used herein are diethylene triamine

penta methylene phosphonate (DTPMP) and ethane 1-hydroxy diphosphonate (HEDP). Such phosphonate chelating agents are commercially available from Monsanto under the trade name DEQUEST[®].

Polyfunctionally-substituted aromatic chelating agents may also be useful in the compositions herein. See U.S. patent 3,812,044, issued May 21, 1974, to Connor et al. Preferred compounds of this type in acid form are dihydroxydisulfobenzenes such as 1,2-dihydroxy -3,5-disulfobenzene. A preferred biodegradable chelating agent for use herein is ethylene diamine N,N'- disuccinic acid, or alkali metal, or alkaline earth, ammonium or substitutes ammonium salts thereof or mixtures thereof. Ethylenediamine N,N'- disuccinic acids, especially the (S,S) isomer, have been extensively described in US patent 4, 704, 233, November 3, 1987, to Hartman and Perkins. Ethylenediamine N,N'- disuccinic acid is, for instance, commercially available under the tradename ssEDDS[®] from Palmer Research Laboratories.

Suitable amino carboxylates to be used herein include ethylene diamine tetra acetates, diethylene triamine pentaacetates, diethylene triamine pentaacetate (DTPA), N-hydroxyethylethylenediamine triacetates, nitrilotri-acetates, ethylenediamine tetrapropionates, triethylenetetraaminehexa-acetates, ethanol-diglycines, propylene diamine tetracetic acid (PDTA) and methyl glycine di-acetic acid (MGDA), both in their acid form, or in their alkali metal, ammonium, and substituted ammonium salt forms. Particularly suitable amino carboxylates to be used herein are diethylene triamine penta acetic acid, propylene diamine tetracetic acid (PDTA) which is, for instance, commercially available from BASF under the trade name Trilon FS[®] and methyl glycine di-acetic acid (MGDA).

Further carboxylate chelating agents to be used herein include salicylic acid, aspartic acid, glutamic acid, glycine, malonic acid or mixtures thereof.

Particularly preferred chelating agents to be used herein are amino aminotri(methylene phosphonic acid), di-ethylene-triamino-pentaacetic acid, diethylene triamine penta methylene phosphonate, 1-hydroxy ethane diphosphonate, ethylenediamine N, N'-disuccinic acid, and mixtures thereof.

Typically, the bleaching compositions according to the present invention may comprise up to 5%, preferably from 0.01% to 1.5% by weight and more preferably from 0.01% to 0.5% by weight of the total composition of a chelating agent.

Preferably, the composition comprises less than 0.5% by weight of the total composition of a chelating agent, preferably less than 0.5% by weight of the total composition of HEDP.

Builder

The bleaching compositions of the present invention may further comprise one or more builders and/or a modified polycarboxylate co-builder.

Suitable builders are selected from the group consisting of : organic acids and salts thereof; polycarboxylates; and mixtures thereof. Typically said builders have a calcium chelating constant (pKCa) of at least 3. Herein the pKCa the value of a builder or a mixture thereof is measured using a 0.1M NH₄Cl-NH₄OH buffer (pH 10 at 25°C) and a 0.1% solution of said builder or mixture thereof with a standard calcium ion electrode.

Examples of builders are organic acids like citric acid, lactic acid, tartaric acid, oxalic acid, malic acid, monosuccinic acid, disuccinic acid, oxydisuccinic acid, carboxymethyl oxysuccinic acid, diglycolic acid, carboxymethyl tartronate, ditartronate and other organic acid or mixtures thereof. Suitable salts of organic acids include alkaline, preferably sodium or potassium, alkaline earth metal, ammonium or alkanolamine salts.

Such organic acids and the salts thereof are commercially available from Jungbunzlaur, Haarman & Reimen, Sigma-Aldrich or Fluka.

Other suitable builders include a wide variety of polycarboxylate compounds. As used herein, "polycarboxylate" refers to compounds having a plurality of carboxylate groups, preferably at least 3 carboxylates. Polycarboxylate builder can generally be added to the composition in acid form, but can also be added in the form of a neutralized salt or "overbased". When utilized in salt form, alkali metals, such as sodium, potassium, and lithium, or alkanolammonium salts are preferred. Useful polycarboxylates include homopolymers of acrylic acid and copolymers of acrylic acid and maleic acid.

Other useful polycarboxylate builders include the ether hydroxypolycarboxylates, copolymers of maleic anhydride with ethylene or vinyl methyl ether, 1,3,5-trihydroxy benzene-2,4,6-trisulfonic acid, and carboxymethyloxysuccinic acid, the various alkali metal, ammonium and substituted ammonium salts of polyacetic acids such as nitrilotriacetic acid, as well as polycarboxylates such as mellitic acid, succinic acid, oxydisuccinic acid, polymaleic acid, benzene 1,3,5-tricarboxylic acid, carboxymethyloxysuccinic acid, and soluble salts thereof.

Suitable polycarboxylates are commercially available from Rohm & Haas under the trade name Norasol[®] or Acusol[®].


Preferred builders herein are selected from the group consisting of : citric acid; tartaric acid; tartrate monosuccinate; tartrate disuccinate; lactic acid; oxalic acid; and malic acid; and mixtures thereof. Even more preferred builders herein are selected from the group consisting of : citric

acid; tartaric acid; tartrate monosuccinate; tartrate disuccinate; and malic acid; and mixtures thereof. The most preferred builders herein are selected from the group consisting of : citric acid; tartaric acid; tartrate monosuccinate; and tartrate disuccinate; and mixtures thereof.

Typically the bleaching compositions herein may comprise up to 40%, preferably from 0.01% to 25%, more preferably from 0.1% to 15%, and most preferably from 0.5% to 10% by weight of the total composition of said builder.

The compositions of the present invention may further comprise a modified polycarboxylate co-builder. The term “polycarboxylate” refers to compounds having a plurality of carboxylate groups, preferably at least 3 carboxylates.

By “modified polycarboxylate” it is meant herein that at least at one end of the polycarboxylate compound, i.e., the polycarboxylate chain, said compound is modified by a functional group, e.g., a phosphono group. Preferred modified polycarboxylate co-builders are polycarboxylates with phosphono end groups. By “phosphono end group” it is meant herein a phosphono functional group according to the formula :



wherein each M is independently H or a cation, preferably both M are H.

Examples of suitable polycarboxylates with phosphono end groups are copolymers of acrylic acid and maleic acid having a phosphono end group and homopolymers of acrylic acid having a phosphono end group. Such modified polycarboxylate are available from Rohm & Haas under the trade name Acusol 425[®], Acusol 420[®] or Acusol 470[®].

Typically the bleaching compositions herein may comprise up to 40%, preferably from 0.01% to 25%, more preferably from 0.1% to 15%, and most preferably from 0.5% to 5% by weight of the total composition of said modified polycarboxylate co-builder.

Radical Scavengers

The compositions of the present invention may comprise a radical scavenger or a mixture thereof. Suitable radical scavengers for use herein include the well-known substituted mono and dihydroxy benzenes and their analogs, alkyl and aryl carboxylates and mixtures thereof. Preferred such radical scavengers for use herein include di-tert-butyl hydroxy toluene (BHT), hydroquinone, di-tert-butyl hydroquinone, mono-tert-butyl hydroquinone, tert-butyl-hydroxy

anysole, benzoic acid, toluic acid, catechol, t-butyl catechol, benzylamine, 1,1,3-tris(2-methyl-4-hydroxy-5-t-butylphenyl)butane, n-propyl-gallate or mixtures thereof and highly preferred is di-tert-butyl hydroxy toluene. Such radical scavengers like N-propyl-gallate may be commercially available from Nipa Laboratories under the trade name Nipanox S1®. Radical scavengers, when
5 used, are present in amounts ranging from up to 10% by weight of the total composition, preferably from 0.001% to 2% and more preferably from 0.001% to 0.5% by weight.

The presence of radical scavengers may contribute to reduce tensile strength loss of fabrics and/or color damage when the compositions of the present invention are used in any laundry application, especially in a laundry pretreatment application.

10

Bleach Activators

As an optional ingredient, the compositions of the present invention may comprise a bleach activator or mixtures thereof. By "bleach activator", it is meant herein a compound which reacts with hydrogen peroxide to form a peracid. The peracid thus formed constitutes the activated
15 bleach. Suitable bleach activators to be used herein include those belonging to the class of esters, amides, imides, or anhydrides. Suitable examples of such compounds to be used herein are tetracetyl ethylene diamine (TAED), sodium 3,5,5 trimethyl hexanoyloxybenzene sulphonate, diperoxy dodecanoic acid as described for instance in U.S. Pat. No. 4,818,425 and nonylamide of peroxyadipic acid as described for instance in U.S. Pat. No. 4,259,201 and n-
20 nonanoyloxybenzenesulphonate (NOBS). Also suitable are N-acyl caprolactams selected from the group consisting of substituted or unsubstituted benzoyl caprolactam, octanoyl caprolactam, nonanoyl caprolactam, hexanoyl caprolactam, decanoyl caprolactam, undecenoyl caprolactam, formyl caprolactam, acetyl caprolactam, propanoyl caprolactam, butanoyl caprolactam pentanoyl caprolactam or mixtures thereof. A particular family of bleach activators of interest was
25 disclosed in EP 624 154, and particularly preferred in that family is acetyl triethyl citrate (ATC). Acetyl triethyl citrate has the advantage that it is environmental-friendly as it eventually degrades into citric acid and alcohol. Furthermore, acetyl triethyl citrate has a good hydrolytical stability in the product upon storage and it is an efficient bleach activator. Finally, it provides good building capacity to the composition. The compositions according to the present invention
30 may comprise from 0.01% to 20% by weight of the total composition of said bleach activator, or mixtures thereof, preferably from 1% to 10%, and more preferably from 3% to 7%

Process of bleaching fabrics

In another aspect, the present invention also encompass the process of bleaching fabrics using the above mentioned composition.

The liquid bleaching composition according to the present invention needs to be contacted with the fabrics to be bleached. This can be done either in a so-called "pretreatment mode", where the liquid composition is applied neat onto said fabrics before the fabrics are rinsed, or washed then rinsed, or in a "soaking mode" where the liquid composition is first diluted in an aqueous bath and the fabrics are immersed and soaked in the bath, before they are rinsed. The contact with fabrics can also be done in a "through the wash mode", where the liquid composition is added on top of a wash liquor formed by dissolution or dispersion of a typical laundry detergent.

It is essential in both cases, that the fabrics are rinsed after they have been contacted with said composition, before said composition has completely dried off.

In the pretreatment mode, the process comprises the steps of applying said liquid composition in its neat form onto said fabrics, or at least soiled portions thereof, and subsequently rinsing, or washing then rinsing said fabrics. In this mode, the neat compositions can optionally be left to act onto said fabrics for a period of time ranging from 1 minute to 1 hour, before the fabrics are rinsed, or washed then rinsed, provided that the composition is not left to dry onto said fabrics. For particularly tough stains, it may be appropriate to further rub or brush said fabrics by means of a sponge or a brush, or by rubbing two pieces of fabrics against each other.

In another mode, generally referred to as "soaking mode", the process comprises the steps of diluting said liquid composition in its neat form in an aqueous bath so as to form a diluted composition. The dilution level of the liquid composition in an aqueous bath is typically up to 1:85, preferably up to 1:50 and more preferably 1:25 (composition:water). The fabrics are then contacted with the aqueous bath comprising the liquid composition, and the fabrics are finally rinsed, or washed then rinsed. Preferably in that embodiment, the fabrics are immersed in the aqueous bath comprising the liquid composition, and also preferably, the fabrics are left to soak therein for a period of time ranging from 1 minute to 48 hours, preferably from 1 hour to 24 hours.

In yet another mode which can be considered as a sub-embodiment of "soaking mode", generally referred to as "bleaching through the wash mode", the liquid composition is used as a so-called laundry additive. And in that embodiment the aqueous bath is formed by dissolving or dispersing a conventional laundry detergent in water. The liquid composition in its neat form is contacted

with the aqueous bath, and the fabrics are then contacted with the aqueous bath containing the liquid composition. Finally, the fabrics are rinsed.

Depending on the end-use envisioned, the compositions herein can be packaged in a variety of containers including conventional bottles, bottles equipped with roll-on, sponge, brusher or
5 sprayer.

The dimensions and values disclosed herein are not to be understood as being strictly limited to the exact numerical values recited. Instead, unless otherwise specified, each such dimension is intended to mean both the recited value and a functionally equivalent range surrounding that
10 value. For example, a dimension disclosed as “40 mm” is intended to mean “about 40 mm

CLAIMS

What is claimed is:

1. A liquid composition comprising peroxygen bleach, perfume microcapsules and less than 10% of surfactant by weight of the total composition, and wherein the composition comprises a polysaccharide polymer.
2. Composition according to claim 1 wherein the composition comprises less than 5% of surfactant by weight of the total composition.
3. Composition according to any of the preceding claims wherein the perfume microcapsules comprise a polymeric outer shell made of the condensation of melamine and formaldehyde.
4. Composition according to claim 1 wherein the polysaccharide polymer is selected from the group comprising carboxymethylcellulose, ethyl cellulose, hydroxyethyl cellulose, hydroxypropyl cellulose, hydroxymethyl cellulose, succinoglycan and naturally occurring polysaccharide polymers, said naturally occurring polymers being selected from the group comprising xanthan gum, guar gum, locust bean gum, tragacanth gum or derivatives thereof, or mixtures thereof.
5. Composition according to claim 4 wherein the polysaccharide polymer comprises xanthan gum and derivatives thereof.
6. Composition according to claim 1 wherein the composition comprises from 0.01% to 10% by weight of the total composition of said polysaccharide polymer or a mixture thereof, more preferably from 0.05% to 5% and most preferably from 0.1% to 2%.
7. Composition according to any of the preceding claims wherein the peroxygen bleach is selected from the group consisting of hydrogen peroxide; water-soluble sources of hydrogen peroxide; organic or inorganic peracids; hydroperoxides; and diacyl peroxides; and mixtures thereof.

8. Composition according to any of the preceding claims wherein the composition comprises from 0.1% to 30% by weight of the total composition of said peroxygen bleach or a mixture thereof; preferably from 1% to 20%, most preferably from 3% to 10% by weight of the total composition of said peroxygen bleach or a mixture thereof.
9. Composition according to any of the preceding claims wherein the composition further comprises less than 0.5% by weight of the total composition of a chelating agent, preferably less than 0.5% by weight of the total composition of HEDP.
10. Composition according to any of the preceding claims wherein the pH of the composition is between 3 and 9.
11. A process of treating fabrics with the composition such as defined in any of the claims 1 to 10, wherein said process comprises the steps of contacting said fabrics with said liquid composition in its neat or diluted form and washing said fabrics with an aqueous bath comprising water and a conventional laundry detergent, preferably comprising at least one surface active agent, before and/or during and/or after the step of contacting said fabrics with said liquid composition.

INTERNATIONAL SEARCH REPORT

International application No

PCT/US2010/020618

A. CLASSIFICATION OF SUBJECT MATTER

INV. C11D3/22 C11D3/39 C11D3/50 C11D17/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

C11D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 198 55 349 A1 (HENKEL KGAA [DE]) 8 June 2000 (2000-06-08)	1-11
Y	page 2, lines 29-35; claims 1-10; examples 1-3 page 4, lines 57-62 page 5, lines 6,7 page p, line 22 - line 37	3
A	GB 1 561 389 A (PROCTER & GAMBLE) 20 February 1980 (1980-02-20) page 9, lines 43-51; example 1	1-11
A	EP 0 965 326 A (PROCTER & GAMBLE [US]) 22 December 1999 (1999-12-22) example CI	1-11
	----- -/--	

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

17 March 2010

Date of mailing of the international search report

26/03/2010

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Klier, Erich

INTERNATIONAL SEARCH REPORT

International application No

PCT/US2010/020618

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 1 637 188 A (FIRMENICH & CIE [CH]) 22 March 2006 (2006-03-22) paragraph [0001]; claims 1,9,10; examples 1,2,5 -----	3

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2010/020618

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 19855349	A1	08-06-2000	AU 1272700 A CA 2291869 A1 WO 0032730 A1	19-06-2000 01-06-2000 08-06-2000
GB 1561389	A	20-02-1980	BE 848832 A1 DE 2653259 A1 FR 2333042 A1 IT 1076848 B NL 7613203 A	26-05-1977 02-06-1977 24-06-1977 27-04-1985 01-06-1977
EP 0965326	A	22-12-1999	AT 367845 T AU 3949999 A BR 9911218 A CA 2334752 A1 CN 1305367 A DE 69838130 T2 ES 2289771 T3 WO 9965458 A1 JP 2002518525 T MA 24878 A1 US 6869923 B1	15-08-2007 05-01-2000 06-03-2001 23-12-1999 25-07-2001 10-04-2008 01-02-2008 23-12-1999 25-06-2002 31-12-1999 22-03-2005
EP 1637188	A	22-03-2006	WO 2006018694 A1 US 2007123442 A1	23-02-2006 31-05-2007