

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
11 January 2007 (11.01.2007)

PCT

(10) International Publication Number
WO 2007/004880 A2

(51) International Patent Classification: **Not classified**

(21) International Application Number:
PCT/NL2006/050161

(22) International Filing Date: 3 July 2006 (03.07.2006)

(25) Filing Language: Dutch

(26) Publication Language: English

(30) Priority Data:
1029412 3 July 2005 (03.07.2005) NL

(71) Applicant (for all designated States except US): **WIDEE B.V.** [NL/NL]; Dedemsvaartseweg Zuid 59, NL-7775 AC Lutten (NL).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **DE WILDE, Gerrit Jan** [NL/NL]; Anerveenseweg 58, NL-7788 AH Anerveen (NL).


(74) Agent: **SCHUMANN, Bernard Herman Johan**; Schumann Patent Consultancy B.V., Kerkedennen 43, NL-7621 EB Borne (NL).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT,

[Continued on next page]

(54) Title: COUPLING BETWEEN TWO BODIES



(57) Abstract: The invention relates to a coupling between a first body with a hole and a cylindrical-as4 zone of a second body to be inserted therein, in which hole extend elastically deformable tongues, the free end edges of which tongues lie on a circle, the diameter of which is smaller than the outer diameter of said end zone, which tongues bend in the insertion direction when said end zone is inserted and scrape over the surface thereof with their free edges such that after inserting the end zone over some distance the movement in backward direction is blocked. The end edges of the tongues have an inclining position corresponding to a part of a helix, so that during a relative rotation of the two bodies the form of the helix is followed whereby an axial relative movement ' also occurs and the end zone can be removed from the hole.



RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *without international search report and to be republished upon receipt of that report*

COUPLING BETWEEN TWO BODIES

The invention relates to a coupling between a first body with a cylindrical hole with an axis and a cylindrical end zone of a second body to be inserted therein in an axial insertion direction, in which hole and/or on the surface of which end zone extend a number of elastically deformable tongues which are fixedly connected to the relevant body and ordered in angularly regular manner, for instance equidistantly, the free end edges of which tongues lie substantially on the peripheral plane of an imaginary, substantially rotation-symmetrical body, respectively the diameter of which is smaller than the outer diameter of the end zone of the second body or the diameter of which is greater than the diameter of the hole, which tongues extend at an angle to the axial direction such that, when said end zone is inserted, they bend in the insertion direction and scrape over the surface thereof with their free edges such that after insertion of the end zone over some distance the movement in backward direction relative to the insertion direction is blocked.

Such a coupling is known from EP-A-0 378 035, EP-A-0 212 883, EP-A-0 579 194, EP-A-0 294 948, EP-A-0 972 981 and DE-A-197 23 594. Relative to this stated prior art it is an object of the invention to embody a coupling between two bodies such that it can be released very easily without specific uncoupling operations and the use of tools intended specifically for this purpose, while in the coupled situation the bodies are nevertheless coupled to each other very firmly and even, ostensibly, inseparably.

These and other objects are realized with a coupling of the type specified in the preamble which has the feature that the end edges of the tongues have an inclining position corresponding to a part of a helix, as a consequence of which, when the second body is rotated around the axis relative to the first body, the form of said helix is followed whereby an axial movement

also occurs and said end zone of the second body can be removed from the hole of the first body.

The tongues can extend on the inner side of the hole but, alternatively, can also be situated on the surface of said end zone. It is recommended for safety reasons when the coupling is effected that the tongues are situated inside the hole, since there is otherwise the danger of the person effecting the coupling being injured by the possibly sharp tongues.

The tongues can consist of any suitable material. A sufficiently strong plastic such as for instance ABS is therefore suitable. Cheaper and very reliable is an embodiment where the tongues consist of metal, in particular steel.

In a preferred embodiment, the coupling according to the invention has the special feature that the tongues form part of a monolithic unit, also comprising a substantially flat ring which is at least partially received in the wall of the hole of the first body. This embodiment is relatively easy to manufacture by punching and pressing, whereby production costs will be relatively low.

This latter embodiment can advantageously have the special feature that the ring has a number of protrusions which during mutual rotation of the two bodies in the stated manner brace themselves against the material of the body to which the ring is fixedly connected. When the end zone of the second body is displaced outward by rotation, a distribution of forces thus takes place over the whole periphery of the ring, which in turn distributes these forces over the protrusions serving as barbed hooks. It will therefore be apparent that these protrusions are preferably distributed regularly, for instance angularly equidistant, over the periphery of the ring. They can lie in the same plane as the ring or also be embodied as additional tongues pressed out of the plane of the ring.

According to yet another aspect of the invention, the coupling according to the invention has the special feature that each tongue has a main direction in axial projection which differs from the radial direction and

is in a direction opposite the direction of rotation when the end zone of the second body is moved outward. A more or less radially directed additional force is hereby exerted on each tongue during rotation of the
5 cylindrical end zone of the second body, whereby the ring has a slight tendency to expand, which somewhat facilitates the helical rotation.

In a specific embodiment, the coupling according to the invention has the special feature that the hole has
10 an axial stop for bounding the distance over which said end zone of the second body can be inserted into the hole. Using this embodiment the coupling can be effected in very simple manner by inserting the cylindrical end zone of the second body with some axial force into the
15 cylindrical hole in the first body, wherein the axial insertion distance is determined by said axial stop. This axial stop can for instance be embodied as an annular shoulder, against which the leading edge of the end zone of the second body comes to lie.

20 According to a determined aspect of the invention, the coupling has the special feature that the first body is a tube or tube stub.

According to yet another aspect of the invention, the coupling can have the special feature that at least
25 said end zone of the second body consists of plastic, concrete, wood or metal, such as iron, copper or aluminium. It is important that the material of the tongues is chosen such that it can co-act effectively in the above described manner with the material of the
30 second body.

An embodiment which is easy to assemble has the specific feature that the ring has an interruption and is accommodated clampingly while being elastically deformed in an annular recess in the relevant wall of
35 the relevant body. In order to prevent unintended rotation of the ring in the situation where the bodies must be separated from each other by relative rotation, use can be made of means preventing such a rotation. The above specified coupling can have for this purpose the
40 special feature that the ring has a number of protrusions which during mutual rotation of the two

bodies in the stated manner brace themselves against the material of the body to which the ring is fixedly connected. Alternatively, the annular recess can have a local interruption in the form of a stop wall, with
5 which an end of the ring at the position of the interruption can co-act during ~~said~~ rotation. Unintended rotation of the ring is effectively prevented with both variants.

A specific embodiment of the coupling according to
10 the invention has the special feature that the ring is secured against rotation in both directions.

Such a coupling is suitable for carrying out a method for establishing such a coupling, the method comprising the steps of:

15 (a) displacing the surface of the related body over some distance in axial direction along the end edges; and

(b) displacing the end zone of the second body axially further into the hole by relative rotation of
20 the two bodies.

According to a further aspect of the invention the coupling has the special feature that upstream relative to the insert direction a sealing ring is present on the first or the second body. As a result of the upstream
25 position of the sealing ring it is prevented that a defective sealing is caused to occur as a result of scratches caused by the end edges of the tongues in the surface of the related body cooperating therewith.

According to a last aspect of the invention the
30 coupling has the special feature that the sealing ring is accommodated in an annular groove broadening in the insert direction, in a way such that after inserting the cylindrical end zone of the second body in the hole and subsequently displacing same in the opposite direction
35 the ring is caused to cooperate in a clamping and sealing manner with the bottom of the annular groove and the facing surface of the related body.

During establishing of the coupling of this type a circumferential wedge shaped space is created between
40 the broadening annular groove and the cylindrical surface of the related body. Initially the elastic

sealing ring will move together with the surface of the related body until it is blocked for further displacement, particularly by the presence of the tongues that for instance may form part of a ring.

- 5 During a further axial displacement the sealing ring shifts over the related surface ~~in axial direction~~, until the operator is of the opinion that the insert displacement is sufficient or until a further displacement is blocked due to the presence of stopping
- 10 means. Subsequently a backward axial displacement is caused by a suitable relative rotation of the two bodies, resulting in that the sealing ring is fixed by a wedge operation in a clamping manner against the bottom of the groove tapering in that backward direction. In
- 15 the case in which the coupling is loaded by medium under pressure the sealing ring will be urged into the described wedge-shaped space, which further enhances the sealing operation.

- A coupling according to the invention can for
- 20 instance be applied for the coupling of two tubes. A two-sided coupling sleeve can thus for instance be coupled at both its ends to respective tubes by means of two associated couplings according to the invention. Such a sleeve can optionally be an outer sleeve or an
- 25 inner sleeve. In the case of an outer sleeve, the connection between the tubes for coupling to each other can be realized such that these tubes come to rest with their free end edges against each other. A completely medium-tight sealing can further be ensured by making
- 30 use of suitable sealing means, for instance sealing rings present on the inner surface of the outer sleeve.

- The invention is not only suitable for coupling tubes but in general for coupling a body provided with a hole to another body having at least a cylindrical end
- 35 zone, for instance a solid rod. The coupling according to the invention can thus serve to place an outside letterbox on a for instance wooden post. Table legs can also be connected to a tabletop provided with holes using the coupling according to the invention. A
- 40 hammerhead provided with a suitable hole can also be

connected to a handle with the coupling according to the invention.

The given examples are not limitative and serve only as an indication of possible applications of the invention. What is important is that an established
5 coupling cannot be released by ~~exerting~~ only an axial tensile force on the two bodies. The connection by means of the coupling according to the invention can only be released by mutually rotating the bodies in the above
10 described manner.

The invention will now be elucidated on the basis of the accompanying drawings.

In the drawings:

Fig. 1a shows a cut-away perspective view of a
15 coupling between two tubes according to the invention at a stage where the tubes to be mutually coupled still lie a distance apart;

Fig. 1b shows a cross-section corresponding with the situation of Fig. 1a;

20 Fig. 2a is a perspective view of a unit comprising a ring with inward extending tongues and a number of barbed hooks on the outer side;

Fig. 2b shows a bottom view of the ring of Fig. 2a;

Fig. 2c shows the cross-section A-A of Fig. 2b;

25 Fig. 3a shows a view corresponding with Fig. 1a of the first stage in which the tube coupling is effected;

Fig. 3b shows a view corresponding with Fig. 1b of the situation of Fig. 3a;

30 Fig. 4a shows a view corresponding with Fig. 1a and 3a of the situation a start has been made with uncoupling of the two tubes by mutual rotation;

Fig. 4b shows a view corresponding with Fig. 1b and 3b of the situation of Fig. 4a;

35 Fig. 5a shows a view corresponding with Fig. 1a, 3a and 4a of the final stage in which the uncoupling is fully effected and the tubes have been uncoupled into the situation shown in Fig. 1a;

Fig. 5b is a view corresponding with Fig. 1b, 3b and 4b of the uncoupled situation shown in Fig. 5a;

Fig. 6a, 6b and 6c show corresponding exploded views in respectively side view, longitudinal section and perspective view of an alternative;

Fig. 7 shows an exploded view of a coupling sleeve according to the invention in yet another embodiment;

Fig. 8 shows a cross-section through a sleeve in a further embodiment; and

Fig. 9 shows a view corresponding with Fig. 8 of a final embodiment.

Fig. 1a shows a first tube 1 and a second tube 2. The first tube has an inner diameter corresponding to the outer diameter of the second tube 2 such that this second tube 2 can be inserted as far as an annular axial stop 3 into first tube 1. The axial insertion direction is indicated with an arrow 4. Lying on an annular shoulder 5 is a steel ring 6 which is provided with twelve inward protruding tongues 7 and which forms a monolithic unit therewith. Reference is also made in this respect to Fig. 2a, 2b and 2c. As shown clearly in Fig. 1a and 1b, tongues 7 have a position bent slightly downward in accordance with the insertion direction 4.

In this embodiment the ring 6 is fixed relative to tube 1 by means of a cylindrical fixation ring 8 which can be connected fixedly to tube 1 by means of screwing, glueing, welding or any other suitable process after insertion of ring 6. It is noted that ring 6 can also be embedded in the first tube 1, for instance if it is manufactured from plastic.

It is essential according to the invention that the end edges 9 of tongues 7 have an inclining position corresponding to a part of a helix. This aspect can be seen particularly well in Fig. 1b and Fig. 2c. As a result of this inclining position the direction 13 (see Fig. 4a) of the helix is formed during mutual rotation of tubes 1 and 2 around axis 10 of hole 11, i.e. the internal cavity of tube 1, whereby an axial displacement 14 occurs, and end zone 15 of second tube 2 can be removed from hole 11 of the first tube.

Fig. 1a and 1b show the initial stage prior to effecting the coupling.

Fig. 2a, 2b, 2c show a possible construction of the integral, monolithic steel ring with the tongues 7 and barbed hook-like protrusions 16 extending on the outer side of the ring.

5 Fig. 3a and 3b show that by axially displacing the second tube 2 with force relative to first tube 1 as according to arrow 4 the tongues 7 are bent further downward by tube 2 such that the leading edge 17 of second tube 2 eventually comes to rest on the upper
10 surface 18 serving as axial stop of the annular axial stop 3. This is the coupled situation according to Fig. 3a and 3b. Owing to the presence of tongues 7 the backward displacement of second tube 2 relative to arrow 4 is blocked, whereby the coupling between tubes 1 and 2
15 in this manner is very firm.

As shown in Fig. 4a and 4b, when tube 2 is rotated relative to tube 1 as according to arrow 12, there occurs a helical movement in accordance with vector 13 which is accompanied by an axial displacement 14,
20 whereby tube 2 is gradually displaced out of tube 1. The sharp steel tongues 7 cause damage to the outer surface of tube 2 in the form of grooves 19 scored therein. Particularly in the case of relatively soft plastics such as PVC, these grooves are clearly visible. This
25 does not however make it impossible to couple tube 2 once again to tube 1 as according to Fig. 1 and 3.

Fig. 5a and 5b show the final situation in which tube 2 is wholly separated from tube 1 through continued rotation 12. Grooves 19 then extend over a larger axial
30 area.

Fig. 6 shows a tube coupling according to the invention in exploded view. The coupling is adapted for mutual coupling of two tubes 30 and 31. Use is made for this purpose of a coupling sleeve 32. Tube 31 is pushed
35 into this coupling sleeve 32 until it lies against an annular stop shoulder 33. The coupling between sleeve 32 and tube 31 is fixed, for instance by means of a glue connection.

Sleeve 32 has an annular recess 34 in which a
40 rubber elastic sealing ring 35 is received. This serves for sealing relative to the outer surface of tube 30.

A spring steel ring 37 with tongues 38 placed in a helical position is arranged clampingly under elastic tension in an annular recess 36. This ring is shown particularly clearly in Fig. 6c.

5 Tube 30 is inserted with force into sleeve 32 and passes the yielding tongues 38 ~~without~~ at least partial elastic deformation and sealing ring 35 until it rests against stop shoulder 33.

10 The coupling is hereby completed. It will be apparent that tube 31 is fixed sealingly relative to sleeve 32 and that tube 30 seals relative to sleeve 32 by means of sealing ring 35 and can only be removed by suitable rotation from the fixation relative to sleeve 32.

15 Fig. 7 shows a coupling sleeve 41 in exploded view. A rotation-symmetrical bush 42 co-acts with a clamping ring 43 for clamping stainless-steel or spring-steel ring 44 on which tongues 7 are present. The ring has on its outer edge four recesses, all designated with the
20 reference numeral 45. These recesses 45 co-act with elongate protrusions 46 arranged on the inner side of bush 42 such that the rotation of ring 44 relative to bush 42 is blocked in both directions. Clamping ring 43 is provided with correspondingly formed recesses 47.

25 An O-ring 48 of rubber elastic material serving as sealing element is placed on the inner surface of clamping ring 43. Present for this purpose on the inner surface of ring 43, as will become apparent with reference to the variant according to Fig. 8, is an
30 annular recess in which the O-ring 48 fits partially.

 The rotation locking of ring 44 relative to sleeve 42 in two directions is important because it is thereby possible to ensure that, when for instance a tube is inserted over a limited distance into sleeve 41 such
35 that it comes into contact with end edges 9 of tongues 7 of ring 44, a continuous, inward displacement of the tube can be obtained relative to coupling sleeve 41 with a suitable rotation of the inserted tube, as a result of the helical position of edges 9. This is particularly
40 important in the case where a tube has a relatively large diameter as a result of tolerance variations and

it is not automatically possible to displace it inward by axial pressure. Once the tube in question has reached its desired end position, an outward displacement can be obtained according to the invention by rotation in

5 reverse direction.

It is noted that the sealing ring 48 co-acting with the outer surface of the inserted tube is placed upstream of the tongues 7. The outer wall of the inserted tube is thereby not damaged by scraping of
10 edges 9, which could result during upstream displacement in an inadequate sealing action of O-ring 48.

Fig. 8 shows a coupling sleeve 51 in which a spring steel ring 52 is formed integrally with the plastic bush 53 of sleeve 51 during the injection moulding process.
15 An excellent rotation locking is hereby realized in both directions. To the extent this is necessary, the edge part of ring 52 encased by plastic could also be provided with a determined profiling in order to further strengthen, if necessary, the anchoring in the plastic.

20 Fig. 9 shows a coupling sleeve 61 wherein the steel ring 44 is clamped between a bush 62 and a clamping ring 63 in accordance with the embodiment of Fig. 7. In this embodiment clamping ring 63 has on its inner surface a truncated cone-shaped part 64 with which the O-ring 48
25 co-acts.

Only the coupling between two tubes is shown by way of example in the drawings. The invention is not limited to this application.

It will be apparent that many modifications are
30 possible within the scope of the invention.

CLAIMS

- 5 1. Coupling between a first body with a hole, for instance a cylindrical hole with an ~~axis~~, and a cylindrical end zone of a second body to be inserted therein in an axial insertion direction, in which hole and/or on the surface of which end zone extend a number
10 of elastically deformable tongues which are fixedly connected to the relevant body and ordered in angularly regular manner, for instance equidistantly, the free end edges of which tongues lie substantially on the peripheral plane of an imaginary, substantially
15 rotation-symmetrical body, respectively the diameter of which is smaller than the outer diameter of the end zone of the second body or the diameter of which is greater than the diameter of the hole, which tongues extend at an angle to the axial direction such that, when said end
20 zone is inserted, they bend in the insertion direction and scrape over the surface thereof with their free edges such that after insertion of the end zone over some distance the movement in backward direction relative to the insertion direction is blocked,
25 characterized in that
the end edges of the tongues have an inclining position corresponding to a part of a helix, as a consequence of which, when the second body is rotated around the axis relative to the first body, the form of
30 said helix is followed so that an axial relative movement also occurs and said end zone of the second body can be removed from the hole of the first body.
2. Coupling as claimed in claim 1, wherein the
35 tongues consist of metal, in particular steel.

3. Coupling as claimed in any of the foregoing claims, wherein the tongues form part of a monolithic unit, also comprising a substantially flat ring which is
40 at least partially received in the wall of the hole of the first body.

4. Coupling as claimed in claim 3, wherein the ring has a number of protrusions which during mutual rotation of the two bodies in said manner brace themselves
5 against the material of the body to which the ring is fixedly connected.

5. Coupling as claimed in any of the foregoing claims, wherein each tongue has a main direction in
10 axial projection which differs from the radial direction and is in a direction opposite the direction of rotation when the end zone of the second body is moved outward.

6. Coupling as claimed in claim 5, wherein the
15 protrusions are embodied as barbed hooks.

7. Coupling as claimed in claim 1, wherein the hole comprises an axial stop for bounding the distance over which said end zone of the second body can be inserted
20 into the hole.

8. Coupling as claimed in claim 1, wherein the first body is a tube or tube stub.

25 9. Coupling as claimed in any of the foregoing claims, wherein at least said end zone of the second body consists of plastic, concrete, wood or metal, such as iron, copper or aluminium.

30 10. Coupling as claimed in claim 3, wherein the ring has an interruption and is accommodated clampingly while being elastically deformed in an annular recess in the relevant wall of the relevant body.

35 11. Coupling as claimed in any of the foregoing claims, in which the ring is secured against rotation in both directions.

40 12. Coupling as claimed in any of the foregoing claims, in which upstream relative to the insert

direction a sealing ring is present on the first or the second body.

13. Coupling as claimed in claim 12, in which the
5 sealing ring is accommodated in an annular groove
broadening in the insert direction, in a way such that
after inserting the cylindrical end zone of the second
body in the hole and subsequently displacing same in the
opposite direction the ring is caused to cooperate in a
10 clamping and sealing manner with the bottom of the
annular groove and the facing surface of the related
body.

14. Method for establishing a coupling according to
15 claim 11, comprising the steps of:

(a) displacing the surface of the related body over
some distance in axial direction along the end edges;
and

(b) displacing the end zone of the second body
20 axially further into the hole by relative rotation of
the two bodies.





FIG 1a

FIG 1b








FIG 3b

FIG 3a








FIG 5b

FIG 5a






Fig. 6C




FIG. 7




FIG. 8




FIG.9