

(19)



(11)

EP 3 320 965 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
25.09.2019 Bulletin 2019/39

(51) Int Cl.:
B01F 5/04 ^(2006.01) **B01F 3/04** ^(2006.01)
B01F 3/08 ^(2006.01) **B01F 5/00** ^(2006.01)
B01F 15/02 ^(2006.01)

(21) Application number: **17200615.7**

(22) Date of filing: **08.11.2017**

(54) MIXING UNIT WITH REPLACEABLE INJECTOR

MISCHEINHEIT MIT AUSWECHSELBAREM INJEKTOR

UNITÉ DE MÉLANGE COMPORTANT UN INJECTEUR REMPLAÇABLE

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

(30) Priority: **08.11.2016 DK 201600690**

(43) Date of publication of application:
16.05.2018 Bulletin 2018/20

(73) Proprietor: **Nilfisk Food A/S
2605 Brøndby (DK)**

(72) Inventor: **ASP, Flemming
9400 Nørresundby (DK)**

(74) Representative: **Budde Schou A/S
Haugsgade 3
1128 Copenhagen K (DK)**

(56) References cited:
WO-A1-2015/067989

EP 3 320 965 B1

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

[0001] The present invention pertains to a mixing unit for producing foam for cleaning purposes, a cleaning device with a mixing unit, particularly for use in the food manufacturing industries. More particularly, the invention concerns the use of injectors for sucking a cleaning agent into a water flow. Such injectors are extensively used in cleaning devices and cleaning systems for cleaning heavily soiled surfaces in the food processing area, for instance in meat and fish processing industries, vegetables processing or the pastry industry. The cleaning device according to the invention may also be used for cleaning cars, tractors and other agricultural machines, which often get heavily soiled during use.

[0002] The present invention relates to a mixing unit for use in a cleaning device and cleaning system, the mixing unit having replaceable injectors.

Background of the invention/Background Art

[0003] In the food processing industry, in particular in heavily soiled areas, such as slaughter-houses or in the meat and fish processing industries, tenacious soiling through grease, protein and starch residues requires the application of a series of different treatments procedures, including disinfection, in order to achieve a level of cleaning that complies with official standards. Traditionally, the cleaning procedure would involve an initial flushing with water, wherein all larger debris are removed and the surfaces are made wet. Then it is customary to apply a "carpet" of foam comprising a cleaning agent over these surfaces, particularly in order to clean these surfaces from grease. Finally, the areas may be disinfected with yet another chemical agent, such as chlorine.

[0004] Injectors are typically used for such devices and systems.

[0005] The injectors typically used in cleaning devices and cleaning systems in the industry today, where water is mixed with some type of chemistry (also known as a cleaning agent), are all in one way or another built in to a piping system. Typically, the piping systems are assembled on or fixed to a pipe-manifold or the like. Consequently, it is cumbersome to access modern type injectors, e.g. in order to change the size (capacity) of the injector, or in connection with service or maintenance of the injectors. In order to access the prior art injectors, it is necessary to disassemble the entire or at least portions of the piping system.

[0006] Fig. 1 of the attached description shows a typical cleaning device where injectors are built-in to a piping system. As it appears from Fig. 1, the injectors cannot be accessed without disassembling the piping system, at least to some extent.

[0007] Other similar injectors and cleaning devices are disclosed in US 5,855,217 and WO 2015/067989 A1.

[0008] Injectors are built in to a pipe or some other type of housing. Such housings are often referred to as mixing

units, because it is inside the mixing unit, that the cleaning agent is drawn into and mixed with a flow of water, and where air may be added to provide a foam.

[0009] There is thus a need for mixing unit and an injector that allows easy access to and replacement of injectors.

Disclosure of the invention

[0010] On this background, it is an object of the present invention to provide a mixing unit which is simpler in construction, and more compact, flexible and robust than the prior art mixing units. It is a further object of the invention to provide a mixing unit where an injector may be interchanged more easily than in the prior art devices. Yet further it is an object of the present invention to obtain a mixing device that minimizes the need for welding components of the cleaning system or the cleaning device together.

[0011] In a first aspect, these objects are achieved by a mixing unit for supplying foam for cleaning, the mixing unit comprising:

a housing having a liquid inlet for receiving pressurized water, a gas inlet for receiving pressurized gas, a fluid outlet for delivering said foam, and a cleaning agent inlet, and an injector receiving bay/port for receiving an injector;

the mixing unit further comprising an injector, the injector having

- injector body with a first end and a second end opposite to the first end and a longitudinal axis;
- an injector inlet;
- an injector outlet formed/arranged through the second end; and
- an injector liquid inlet;

which injector inlet is fluidly connectable to the cleaning agent inlet of the housing, which injector liquid inlet is fluidly connectable to the liquid inlet/water inlet of the housing, and which injector outlet is fluidly connected to the fluid outlet of the housing, wherein the injector liquid inlet formed/arranged in a direction transverse to the a longitudinal axis of the injector.

[0012] Preferably, the pressurized gas is air.

[0013] Thereby, is achieved, that the injector may be accessed from a side of a housing of a mixing unit, where no fluid connections enters the injector when located in the mixing unit. Therefore, the need for making water tight connections is diminished and easier access to the injector may thus be provide. The principle may also be used to retrofit in prior at pipe-manifold-type systems.

[0014] In an embodiment, the injector liquid inlet is formed/arranged as a bore from an outer surface of the injector body.

[0015] In a further embodiment the injector liquid inlet communicates with a water inlet connection channel ex-

tending in the direction of the longitudinal axis of the injector body and opens into an injector chamber at the injector inlets.

[0016] In a further embodiment the injector liquid inlet is formed/arranged at a circumferential groove, formed/arranged in the outer surface of the injector body, the circumferential groove forming an annular water inlet channel around the injector together with a portion of the inner surface of the injector receiving bay/port of the mixing unit, when the injector is inserted in the injector receiving bay/port.

[0017] In a further embodiment the injector is positioned within the mixing unit in such a way that a gap around the injector outlet is provided, said gap being fluidly connected to the gas inlet for allowing pressurized gas/air to enter and pass through the gap and mix with a cleaning agent and water at the fluid outlet of the housing.

[0018] In a further embodiment the injector body only has a decreasing maximum dimension from the first end to outlet end, and where the injector body comprises means for releasably connecting the injector to a portion of the housing of the mixing unit.

[0019] In further embodiment, the means for releasably connecting the injector to a portion of the housing of the mixing unit comprises a threading on a portion located at the first end of the injector, the threading cooperating with a corresponding threading on the surface of the injector receiving bay/port of the mixing unit.

[0020] In a further embodiment helical grooves may be formed/arranged in an outer surface of a portion of the injector body in order to provide a swirling gas/air flow surrounding the injector outlet.

[0021] In a second aspect of the invention the objects of the invention are obtained by a cleaning device comprising:

- a mixing unit according to any one of the above mentioned embodiments;
- at least one cleaning agent valve for supplying cleaning agents, and connectable to a source of a cleaning agent;
- an injector valve connectable to a source of pressurized liquid;
- a gas supply valve connectable to a source of pressurized gas;

wherein the at least one injector and the injector valve are integrated within the mixing unit housing;
 wherein cleaning agent channels fluidly connecting the at least one injector and sources of cleaning agent are formed/arranged within the mixing unit housing,
 wherein a liquid supply channel fluidly connecting the injector valve with the injector is formed/arranged within the mixing unit housing; and
 wherein a gas supply channel fluidly connecting the gas supply valve and the at least one injector is formed/arranged in the mixing unit housing.

[0022] In an embodiment of the cleaning device, the mixing unit housing is formed as a solid block of material,

wherein the at least one injector is arranged in an injector receiving bay/port formed/arranged as a bore in said block;
 wherein the injector valve, is arranged in an injector receiving bay/port formed/arranged as a bore in said block, and
 wherein the cleaning agent connection channels, the water supply channel and the gas supply channel are formed/arranged as bores in the block.

[0023] Further objects, features, advantages and properties of the cleaning system and cleaning device according to the invention will become apparent from the detailed description.

Brief description of the drawings

[0024] In the following detailed portion of the present description, the invention will be explained in more detail with reference to the exemplary embodiments shown in the drawings, in which:

Fig 1 shows a prior art cleaning device with three prior art mixing units;

Fig. 2, in a sectional view, shows a diagrammatic depiction of a mixing unit for a cleaning device according to the present invention, and with an injector mounted in the mixing unit;

Fig. 3 shows the mixing unit of Fig. 2, with an injector dismantled from the mixing unit;

Fig. 4A, in a perspective view, shows an embodiment of a mixing unit according to the invention;

Fig. 4B, in a perspective view, shows the mixing unit of Fig. 4A from a different angle;

Fig. 5, in diagrammatic form, shows a cleaning system according to one aspect of the invention including a cleaning device according to another aspect of the invention, and an extended cleaning system;

Fig. 6A, in a sectional view, shows a close up of an injector of a cleaning device according to the invention mounted in a mixing unit of the cleaning device; Figs. 6B and 6C shows the injector and the mixing unit of Fig. 6A, where the injector has been loosened and partly extracted from a bay/port of the mixing unit;

Fig. 6D shows the injector and the mixing unit of Fig. 6A, where the injector has been fully extracted from a bay/port of the mixing unit;

Fig. 6E, in a perspective view, shows an injector and a portion of a mixing unit for a cleaning device according to the invention, before mounting the injector in a bay/port of the mixing unit;

Fig. 6F shows the injector and the portion of a mixing unit of Fig. 6E, where the injector has been mounted in the mixing unit;

Fig. 7, in a partly sectional perspective view, shows an injector according to an aspect of the invention, and a part of a mixing unit for a cleaning device according to the invention;

Fig. 8, in a front view, shows the injector of Fig. 7 and a portion of the mixing unit;

Fig. 9, in a side sectional view shows a portion of the injector and the mixing unit of Fig. 7; and

Fig. 10 shows a section through the injector of Fig. 7.

Detailed description of the invention

[0025] In the following detailed description of the mixing unit according to the invention will be described by preferred embodiments. Also described herein is a cleaning system and a cleaning unit, in which the mixing unit may be implemented. The present invention will now be described more fully hereinafter with reference to the accompanying drawings, in which exemplary embodiments of the invention are shown. The invention may however be embodied in different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. Like reference numerals refer to like elements throughout. Like elements may therefore not be described in detail with respect to the description of each figure.

[0026] The present invention concerns a new mixing unit 9, e.g. for use in a cleaning system 1 and a cleaning device 2 within the field of automated hygienic systems for cleaning of process-systems/apparatuses in the food processing industry. The invention further concerns an integrated mixing unit or module 9 for handling liquid (preferably water), gas (preferably air), and different chemical cleaning compounds, hereinafter called cleaning agents. The mixing unit 9 comprises a suction vacuum chamber, preferably in the form of a so-called injector 100 for mixing water, air and one or more cleaning agents.

[0027] In a further aspect of the invention, the mixing unit 9 of the cleaning device 2 may further include a function for integrated flushing or rinsing of the mixing chamber(s), i.e. the injector(s).

[0028] The mixing unit 9 varies from the mixing units of existing cleaning devices, in that all functions may be integrated in one and the same compact module/unit. This contrasts the cleaning systems available in the market for the food processing industry today. These prior art cleaning devices are typically constructed from different and independent standard components, which via tubes, weldings, fittings and valves (see e.g. Fig. 1) are connected into a cleaning manifold.

[0029] Fig. 1 shows a prior art cleaning device for room surfaces cleaning in the food processing industry. The cleaning device shown is representative of the prior art cleaning devices for surface cleaning in the food processing industry. Other types of apparatuses are used in con-

nection with CIP cleaning.

[0030] In Fig. 1, the encircled device indicated by the reference AA is a cleaning agent valve with tubing. The cleaning agent valve AA includes an injector, which is encircled by the smaller circle inside circle AA, and with the reference "aa". The injector aa is mounted inside the shown tubing by matching threading inside the tube and on the injector. An example of such an injector can be seen in WO 2015/067989. The injector housing, i.e. the tubing is welded together, making it difficult to access the injector for maintenance or repair.

[0031] In Fig. 1, the encircled devices indicated by the references BB and CC are further cleaning agent valves with tubing, similar to AA described above. Further, the encircled device indicated by the reference DD is a valve for supplying spraying water directly to a surface to be cleaned, without being mixed with a cleaning agent, i.e. the valve circumvents the cleaning agent valves AA, BB, CC. Further, in Fig. 1, the arrow marked with the reference WI indicates the incoming water from a pump, delivering water under pressure. Yet further, the arrow marked with the reference OU indicates the outlet for water, water/cleaning agent mix, or water/cleaning agent/air-mix. The encircled device indicated by the reference EE is a valve for supplying air to water/cleaning agent mix in order to provide a foam. The structure encircled and named FF is a valve and tubing for supplying water for rinsing the injectors, aa, in the cleaning agent valves AA, BB, CC. In connection with an aspect of the present invention, such an additional valve may be completely spared, due to the new setup.

[0032] As is apparent from Fig. 1, the prior art system is a large and complex construction.

[0033] Further, the system illustrated in Fig. 1 shows the housing in which the prior art injectors are typically build into. It is evident that the injectors are located inside the tubing and cannot be accessed without disassembling the piping at the unions.

[0034] The cleaning device and the cleaning system according to the present invention integrates some or all the functionalities of the prior art devices in one compact module for automated surface cleaning, in order reduce the space requirements, the production time, and to improve the overall hygiene in the cleaning device 2 and system 1, based on a hygienic design without weldings and with a minimum of connections.

[0035] Fig. 5 shows a first exemplary embodiment of cleaning device 2 and a cleaning system 1, which is particular suitable for performing cleaning in the food processing industry, in particular surface cleaning (as opposed to e.g. CIP).

[0036] The cleaning system 1 comprises a cleaning device 2, and an external cleaning system 300, and a control system 200. The external cleaning system 300 may comprise a tubing 310, 311, 312, 313, in order to deliver water, foam and cleaning agents/water mix from the cleaning device 2 to the locations to be cleaned, e.g. surfaces of rooms and/or machinery of a food process-

ing facility.

[0037] The illustrated cleaning device 2 comprises a source of liquid 49. The source of liquid 49 may include a liquid pump 41. The liquid is preferably water. The liquid pump 41 has a pump inlet 41' to be connected to a liquid (water) supply (not shown), such as regular municipal tap water, and an outlet 41" for the provision of pressurized water.

[0038] The cleaning device 2 also comprises a source 51 of pressurized gas, preferably comprising a compressor 51, having an gas/air inlet (not shown), and a gas outlet 51' for the provision of pressurized gas, such as air. In other embodiments (not shown) other pressurized gasses may be used, e.g. O₂.

[0039] The cleaning device 2 also comprises one or more sources 33, 34 of cleaning agents. In Fig. 5 two such sources are shown. However, in other embodiments there may be another number of cleaning agent sources, such as one or three or more.

[0040] It is understood that, in other embodiments (as explained in the general description above), the cleaning device 2 could be embodied without a compressor 51 or a water pump 41 or sources 33, 34 of cleaning agents, or without either. Alternatively, either the compressor 51 or the water pump 41 or the sources 33, 34 of cleaning agents could form part of the device 2, but be placed at a different location.

[0041] Furthermore, as indicated in Fig. 5, the cleaning device 2 comprises a mixing unit 9. The mixing unit 9 allows mixing of liquid, e.g. water, with a cleaning agent, and a gas, e.g. air, to provide a foam for cleaning purposes. The mixing unit 9, according to the invention may also allow spraying with water only, or spraying with a mixture of cleaning agent and water (i.e. without gas/air).

[0042] The mixing unit 9 has a liquid inlet 43, which is fluidly connectable to the outlet 41" of the water pump 41 via suitable liquid supply tubing 42. The mixing unit 9 further comprises a fluid outlet 44. The water flow through the mixing unit 9 may be controlled by an injector valve 40, which is a flow control valve, i.e. a valve for controlling the magnitude or volume of water flowing there through per unit of time. The valve may be a ball valve, or a seat valve, or any other suitable valve. The injector valve 40 is located in the mixing unit 9 in a liquid supply channel 64', 64 forming a fluid connection between the liquid inlet 43 and an injector 100 of the mixing unit 9. Although this may not be necessary, a second flow control valve, a spraying liquid valve 80 is shown inside the mixing unit 9 in Fig. 5. The valve may be of the same type as the injector valve 40. The spraying liquid valve 80 is arranged in a fluid connection 81, 82 between the liquid inlet 43 and the liquid outlet 44 of the mixing unit 9. This spraying liquid valve 80 may be used for providing clean water for spraying in the external cleaning system 300.

[0043] Further, the mixing unit 9 has a gas inlet 53, which is fluidly connected the gas outlet 51' of the source of pressurized gas/compressor 51 via suitable gas piping 52. The flow of gas (air) to the mixing unit may be con-

trolled by a gas supply valve 50, which in the embodiment shown in Fig. 5 is provided in the fluid connection piping 52 between the source of pressurized gas/compressor 51 and the gas inlet 53 of the mixing unit 9. However, in other embodiments (not shown) the gas supply valve 50 may be arranged inside the mixing unit 9.

[0044] Yet further, the mixing unit 9 has a number of cleaning agent inlets 37, 38, 39, which are fluidly connected with the cleaning agent sources 33, 34, via cleaning agent input lines 35, 36, which as formed by suitable tubes or pipes. The flow of cleaning agents to the mixing device 9 may be controlled by cleaning agent valves 30, 31 arranged in the respective cleaning agent input lines 35, 36. In alternative embodiments (not shown) cleaning agent valves may instead be located inside the mixing unit 9.

[0045] The cleaning device 2 may further be connected to an electrical power supply (not shown) via a suitable cable (not shown) in order to supply electrical power to the water pump 41 and the compressor 51, and/or any further valves, actuators as described below, and the control system 200 for the cleaning device 2 and cleaning system 1.

[0046] The water pump 41, the compressor 50, the mixing unit 9, and further components of the cleaning device 2 may placed inside a housing, not shown. However, they may also be distributed in different locations and connected via suitable tubing.

[0047] The illustrated mixing unit 9 may be a wall or floor mountable device, but it could in alternative embodiments be placed on a wheeled chassis, whereby a mobile cleaning device 2 could be provided.

[0048] The pressurized water provided by the water pump 41, i.e. at the pump outlet 41", may have has a pressure of between 3 bar and 60 bar, preferably between 10 bar and 60 bar, even more preferably between 20 bar and 60 bar. Hereby is achieved that sufficient pressure is provided by the water pump 41 in order to suck (see explanation of injector function below) a first cleaning agent and/or a second cleaning agent, even when an air pressure provided by the compressor 51 (for foaming) is supplied to an injector 100 of the mixing unit 9. This will be explained below. The air pressure provided by the compressor 51 is preferably around 5-10 bar.

[0049] Water vapor can carry contagious/infectious germs, which can pose a real health hazard to the operators performing cleaning work in for example the food industry. However, by keeping the water pressure below 60 bar or below 40 bar, it is assured that the health risk associated with water vapor carried infections is minimized, while at the same time providing sufficient pressure in order to suck up the first or second cleaning agent for cleaning or disinfection purposes. Preferably, the water provided by the water supply to the inlet 41' of the water pump 41 has a pressure of less than 10 bar, preferably less than 8 bar.

[0050] Further, and as shown in Fig. 5, the cleaning system 1 and the cleaning device 2 comprises a control

system 200, for controlling the operation of the cleaning device 2 and in some embodiments the external cleaning system 300, which may form part of the cleaning system 1 of the invention.

[0051] The control system 200 controls at least the cleaning device 2. The control system 200 comprises a control unit 201. The control unit 201 may be any suitable electronic processing unit available. The control unit 201 may be connected to various sensors and actuators via suitable cables or wirelessly.

[0052] Thus, the control unit 201 may control the operation of the pump 41, which forms part of the source of liquid/water for the cleaning device 2. The pump 41 may preferably be a variable pump driven by a motor 210, connected to and controlled by the control unit 201, via a control connection 211. As mentioned above the control connection may be a cable or a wireless connection.

[0053] The control unit 201 also may control the operation of the injector valve 40. The injector valve 40 may be controlled by an actuator 240, connected to and controlled by the control unit 201, via a control connection 241. As mentioned above the control connection 241 may be a cable or a wireless connection. In Fig. 5, the actuator 241 is represented by the symbol of a magnetic actuator, and is illustrated within the mixing unit 9. However, it must be emphasized that the actuator 240 may in other embodiments, see e.g. Figs. 4A, 4B, physically be located outside of and adjacent to the mixing unit 9 housing 10, and connected to the injector valve 40 via e.g. a shaft extending through a wall of the housing 10. Further, it must be emphasized that the actuator 240 may be of a different type than a magnetic actuator. For the injector valve the actuator may e.g. be a pneumatic actuator (which may be supplied by the compressor 51 (not shown) or by an additional source of pressurized gas or fluid (not shown)), which in itself may be controlled by an electrical actuator such as a magnetic actuator.

[0054] Further, the control unit 201 also may control the operation of the spraying liquid valve 80. The spraying liquid valve 80 may be controlled by an actuator 280, connected to and controlled by the control unit 201, via a control connection 281. As mentioned above the control connection 281 may be a cable or a wireless connection. In Fig. 5, the actuator 280 is represented by the symbol of a magnetic actuator, and is illustrated within the mixing unit 9. However, it must be emphasized that the actuator 280 may in other embodiments, see e.g. Figs. 4A, 4B, physically be located outside of and adjacent to the mixing unit 9 housing 10, and connected to the spraying liquid valve 80 via e.g. a shaft extending through a wall of the housing 10. Further, it must be emphasized that the actuator 280 may be of a different type than a magnetic actuator. For the spraying liquid valve 80, the actuator may e.g. be a pneumatic actuator (which may be supplied by the compressor 51 (not shown) or by an additional source of pressurized gas or fluid (not shown)), which in itself may be controlled by an electrical actuator such as

a magnetic actuator.

[0055] Yet further, the control unit 201 may control the operation of the gas supply valve 50. The gas supply valve 50 may be controlled by an actuator 250, connected to and controlled by the control unit 201, via a control connection 251. As mentioned above the control connection 251 may be a cable or a wireless connection. In Fig. 5, the actuator 250 is represented by the symbol of a magnetic actuator, and is illustrated outside the housing 10 of the mixing unit 9, along with the gas supply valve 50. However, it must be emphasized that the actuator 250 and the gas supply valve may in other embodiments (not shown), physically be located inside the mixing unit 9 housing 10. Alternatively, in a further embodiment (not shown), the gas supply valve 50 may be located inside the housing 10 of the mixing unit 9, and the actuator 250 may be located externally of and adjacent to housing 10 of the mixing unit 9, and connected to the gas supply valve 50 via e.g. a shaft extending through a wall of the housing 10. Further, it must be emphasized that the actuator 250 may be of a different type than a magnetic actuator.

[0056] Yet further, the control unit 201 may control the operation of the each of the cleaning agent valves 30, 31. The cleaning agent valves 30, 31 may be controlled by actuators 230, 232 connected to and controlled by the control unit 201, via control connections 231, 233, respectively. As mentioned above the control connections 231, 233 may be cables or wireless connections. In Fig. 5, the actuators 230, 232 are represented by the symbol of a magnetic actuator, and are illustrated as located outside the housing 10 of the mixing unit 9, along with the cleaning agent valves 30, 31. However, it must be emphasized that the actuators 230, 232 and the cleaning agent valves 30, 31 may in other embodiments (not shown), physically be located inside the mixing unit 9 housing 10. Alternatively, in a further embodiment (not shown), on or more of the cleaning agent valves 30, 31 may be located inside the housing 10 of the mixing unit 9, and one or more of the actuators 230, 232 may be located externally of and adjacent to housing 10 of the mixing unit 9, and be connected to the cleaning agent valve 30, 31 via e.g. a shaft extending through a wall of the housing 10. Further, it must be emphasized that the actuators 230, 232 may be of a different type than a magnetic actuator.

[0057] Fig. 5 further shows that the cleaning device 2 according to the invention may be connected to an extended cleaning system 300. A suitable piping 310 of the extended cleaning system 300 may be connected to the liquid outlet 44 of the mixing unit 9. The piping 310 may extend to a plurality of locations where cleaning is expected to be necessary, e.g. different rooms or machines, such as food packing machines, etc. The piping may thus have several branches 311, 312, 313 supplying water, mixture of water and a cleaning agent or foam to cleaning outlets 331, 332, 333. In Fig. 5 three branches 311, 312, 313 are shown. It will however be appreciated that alter-

natively the tubing 310 may branch into only two, or several more branches, or not branch of at all.

[0058] Further, each cleaning outlet 331, 332, 333 may comprise delivery nozzles 340. Each cleaning outlet 331, 332, 333 may comprise a number of delivery nozzles 340. In Fig. 5 it has been shown that cleaning outlet 331 has five delivery nozzles 340, cleaning outlet 334 has three delivery nozzles 340, and cleaning outlet 333 has one delivery nozzles. It is however evident, that the number of delivery nozzles 340 may be adapted to the purpose.

[0059] The supply of water, water/cleaning agent mixture or foam to the cleaning outlet may be controlled by outlet control valves 321, 322, 323. The outlet control valves 321, 322, 323 may in turn be controlled by the control system 200. Thus, the control unit 201 may control the operation of the each of the outlet control valves 321, 322, 323. The outlet control valves 321, 322, 323 may be controlled by actuators 261, 262, 263 connected to and controlled by the control unit 201, via control connections 270, 271, 272, 273. As mentioned above the control connections 270, 271, 272, 273 may be cables or wireless connections. In Fig. 5, the actuators 261, 262, 263 are represented by the symbol of a magnetic actuator. It must be emphasized that the actuators 261, 262, 263 may be of a different type than a magnetic actuator.

[0060] Fig. 2 shows an embodiment of a mixing unit 9, which forms part of a cleaning device 2 according to one aspect of the invention. The mixing unit 9 comprises a housing 10. Inside the housing 10, the mixing unit 9 has a mixing chamber located inside an injector 100. The injector 100 is arranged inside the housing 10.

[0061] The mixing unit utilizes the injector principle for mixing a water and one or more cleaning agent. The injector principle utilizes that when water is under pressure is led through a channel with a decreasing and increasing cross-sectional area (in the direction of the flow of the water) and a channel is formed to intersect the water flow chamber, then a vacuum is formed in the intersecting channel. This vacuum sucks a cleaning agent into the chamber where the water flows. There, the cleaning agent starts to mix with the water. Thus, the cleaning agent may be transported into the flowing water without the use of pumps. This principle is well known and will not be discussed further. Also, known in the art, is to subsequently add gas/air under pressure to the water/cleaning agent mixture in order to provide a foam. Various principles for adding air/gas for foaming are known in the art, and provides foam of varying qualities and quantities. One principle is to let the gas/air impinge on the stream of water/cleaning agent mixture. Another, principle is inject air/gas in parallel with the flow of water/cleaning agent mixture. Both of the principles may be used in the present context. However, further below a specific embodiment of the latter principle is described.

[0062] Fig. 2 shows a cross section of an embodiment of a mixing unit 9 for supplying foam and/or water/cleaning agent mixture and/or pure water for cleaning. The

illustrated mixing unit 9 comprises a housing 10 having a liquid/water inlet 43 for receiving pressurized liquid/water. The water is supplied to the water inlet 43 via a suitable pipe, liquid supply tubing 42, as described above.

5 The liquid supply tubing 42 may be connected to the mixing unit via a connector 43', which may secured to the mixing unit 9, e.g. by cooperating threading (not shown) on the mixing unit 9 and connector 43', or by other fastening means. Further, the connection may be water tight by application of a suitable gasket 43" such as an O-ring.

[0063] The housing 10 also has a gas inlet 53 for receiving pressurized gas, preferably air from compressor 51 as described above. The gas inlet 53 may comprise a connector 53', allowing easy connection to the hose, tube, or pipe forming the gas piping 52 described in connection with Fig. 5 above. The connector 53' may be connected to the mixing device 9, e.g. by cooperating threading (not shown) on the mixing unit 9 and connector 53', or by other fastening means. Further, the connection may be water tight by application of a suitable gasket (not shown), such as an O-ring.

[0064] The housing 10 also comprises a fluid outlet 44 for said foam and/or water/cleaning agent mixture and/or pure water. The fluid outlet 44 may comprise a connector 44', allowing easy connection to the hose, tube, or pipe forming the tubing of external cleaning system 310 described in connection with Fig. 5 above. The connector 44' may be connected to the mixing device 9, e.g. by cooperating threading (not shown) on the mixing unit 9 and connector 44', or by other fastening means. Further, the connection may be water tight by application of a suitable gasket 44" such as an O-ring.

[0065] The housing 10 also comprises at least one cleaning agent inlet 37. The cleaning agent inlet 37 may comprise a connector 37', allowing easy connection to the hose, tube, or pipe forming the cleaning agent input line described in connection with Fig. 5 above. The connector 37' may be connected to the mixing device 9, e.g. by cooperating threading (not shown) on the mixing unit 9 and connector 37', or by other fastening means. Further, the connection may be water tight by application of a suitable gasket (not shown) such as an O-ring. In some embodiments, the cleaning agent connector 37' (or connectors) may be one-way valves in order to prevent a back flow of cleaning agent.

[0066] The gas/air is supplied to the housing 10 via a suitable pipe 52, which is preferable connected with a compressor 51, and the first cleaning agent is supplied to the housing 10 via a suitable pipe 35, which is in fluid communication with a reservoir 33. The water pipe 42 is fluidly connectable to a water pump 41 for supplying pressurized water to the housing 10 of the mixing unit 9.

[0067] The mixing unit 9 further comprises an injector 100 positioned inside the housing 10. The injector is received in an injector receiving bay 70 (the injector receiving bay 70 may alternatively be called an injector receiving port 70) in the housing 10, as may be appreciated by comparing e.g. Figs 2 and 3. Fig. 3 shows the injector

100 removed from the injector receiving bay 70, and Fig. 2 shows the injector 100 in place in the injector receiving bay 70. The injector 100 is in fluid communication with the fluid outlet 44 via a turbulence chamber 14 formed inside the housing 10 between the injector receiving bay 70 and the fluid outlet 44. Preferably, and as shown in e.g. Fig. 3, the injector receiving bay 70 opens into the turbulence chamber 14. Also, preferably, and as shown in e.g. Fig. 3, the turbulence chamber 14 opens into the fluid outlet 44 of the mixing unit 9. In the turbulence chamber 14 the water/cleaning agent mix is mixed with air in order to provide foam.

[0068] As shown in Figs. 2 and 3, the mixing unit further comprises an injector valve 40 formed within the housing 10. The flow of liquid (water) through the mixing unit 9 may be controlled by the injector valve 40, which is a flow control valve, i.e. a valve for controlling the magnitude or volume of water flowing there through per unit of time. The valve may be a ball valve, a seat valve, or any other suitable valve. The injector valve 40 is in fluid connection with the liquid inlet 43 via a channel 64'. The injector valve 40 is further in fluid connection with the injector 100 via a liquid supply channel 64, that opens into the above-mentioned injector receiving bay 70. Thus, the injector valve 40 is located in the mixing unit 9 in a liquid supply channel 64, 64' forming a fluid connection between the liquid inlet 43 and an injector 100 of the mixing unit 9.

[0069] As shown in e.g. Figs. 2, 3 and 5, a second flow control valve, a spraying liquid valve 80 may preferably be arranged inside the housing 10 of the mixing unit 9. The valve may be of the same type as the injector valve 40. The spraying liquid valve 80 is in fluid communication with the liquid inlet 43 via a channel 81 formed in the housing 10. Further, the spraying liquid valve 80 is in fluid communication with the turbulence chamber 14, and thereby the fluid outlet 44. Thus, the spraying liquid valve 80 is arranged in a fluid connection 81, 82 between the liquid inlet 43 and the liquid outlet 44 of the mixing unit 9. This spraying liquid valve 80 may be used for providing clean water for spraying in the external cleaning system 300.

[0070] As shown in Figs 2 and 3, the liquid inlet 43 is preferably in fluid communication with a distribution chamber 13. The distribution chamber opens into the liquid inlet 43. The channel 64' to the injector valve 40 and the channel 81 to the spraying liquid valve 80 thus extend from the distribution chamber 14.

[0071] The injector valve 40 is preferably arranged in an injector valve bay 74 (The injector valve bay 74 may alternatively be called an injector valve port 74). The injector valve bay 74 is arranged within the housing 10, and adapted for receiving the injector valve 40. Thus, the above mentioned channel 64' opens into the injector bay 74 at one (downstream) end and into the distribution chamber 13 at the other (upstream) end.

[0072] The spraying liquid valve 80 is preferably arranged in a spraying liquid valve bay 78 (The spraying liquid valve bay 78 may alternatively be called a spraying

liquid valve port 78). The spraying liquid valve bay 78 is arranged within the housing 10, and adapted for receiving the spraying liquid valve bay 78. Thus, the above mentioned channel 81 opens into the spraying liquid valve bay 78 at one (downstream) end, and into the distribution chamber 13 at the other (upstream) end.

[0073] As described above, in not shown embodiments, an actuator 240 for operating the injector valve 40 may further be arranged inside the housing, and preferably adjacent to the injector valve bay 74. However, in the illustrated embodiments, see Figs 4A and B, the actuator 240 is arranged external to the mixing unit 9 housing 10, but adjacent to a sidewall thereof. A shaft (not shown) extends from the actuator 240 to the injector valve bay 74 via a channel or passage (not shown) from the sidewall, where the actuator 240 is located, to the injector valve bay 74.

[0074] As also described above, in not shown embodiments, an actuator 280 for operating the spraying liquid valve 80 may further be arranged inside the housing, and preferably adjacent to the spraying liquid valve bay 78. However, in the illustrated embodiments, see Figs 4A and B, the actuator 280 is arranged external to the mixing unit 9 housing 10, but adjacent to a sidewall thereof. A shaft (not shown) extends from the actuator 280 to the spraying liquid valve bay 78 via a channel or passage (not shown) from the sidewall, where the actuator 280 is located, to the spraying liquid valve bay 78.

[0075] As shown in Figs 2 and 3, in some embodiments, a further channel 15 may extend from the distribution chamber 13 an outlet 16 formed in a sidewall of the housing 10. As shown in Figs. 4A and B, the outlet 16 may be formed through a connector 16'. The connector 16' may allow easy mounting of a hose for manual cleaning in the vicinity of the mixing unit 9.

[0076] In further embodiments (not shown) the mixing unit may comprise more than one injector 100, such as two or three or more formed inside the housing. In this case each injector may be arranged in injector receiving bay as described above and fluidly connected to a fluid outlet and to the liquid inlet as described above. In the case where the mixing unit 9 comprises more than one injector 100, the mixing unit may have one injector valve 40 per injector, each arranged in an injector valve bay 74 as described above. However, it may also be possible that a plurality of injectors may be connected to a single injector valve 40 arranged in a single injector valve bay 74, as described above. In this case a selector mechanism may be integrated into the housing 10 of the mixing unit 9, the selector mechanism being arranged to switch between liquid supply channel 64 in the mixing unit leading to each of the injectors 100. Such a selector mechanism may further be connected to the control system 200 via an actuator, which may be integrated inside the housing 10, or be located externally thereto.

[0077] However, an advantage of the mixing unit 9, the cleaning device 2 and the cleaning system 1 according to the invention is that one and only one injector is nec-

essary.

[0078] Preferably, the at least one injector 100 and the injector valve 40 are integrated within the mixing unit housing 10. Preferably, the cleaning agent connection channels 61, 62, 63 for fluidly connecting the at least one injector 100 and the sources of cleaning agent 33, 34 are formed within the mixing unit housing 10. Preferably, the liquid supply channel 64 for fluidly connecting the injector valve 40 with the injector 100 is formed within the mixing unit housing 10. Preferably, the gas supply channel 65, for fluidly connecting the gas supply valve 50 and the at least one injector 100 is formed inside the mixing unit housing 10.

[0079] As also mentioned above, the injector 100 (or each injector 100) may be connected to a plurality of sources 33, 34 of cleaning agents. In Figs. 2 and 3, for the sake of simplicity, only one cleaning agent connection channel 61 is shown, the cleaning agent connection channel 61 extending from a cleaning agent inlet 37 of the mixing unit 9 to the injector 100. In the diagram of Fig. 5, two sources 33, 34 of cleaning agent are illustrated.

[0080] Fig. 2 shows the injector 100 inserted in the mixing unit 9 housing 10. Fig 3 shows the injector when separated from the housing. Details of the injector 100 can be appreciated from Fig. 3. However, Fig. 10 show more details of the injector 100.

[0081] Fig. 10 shows a section through an injector 100 according to an aspect of the invention. The injector 100 has an injector body 101. The injector body 101 is elongate, generally cylindrical in structure. Thus, injector 100 has a longitudinal axis A. The elongate injector body 101 has first end 102 and a second end 103 opposite to the first end 102.

[0082] An elongate injector chamber 110 is formed centrally within in the injector body 101. The injector chamber 110 comprises two sections, a first section 111 and a second section 112 opening into an injector outlet 113. The injector outlet 113 is formed in an end wall 114 of the injector body 101, at the second end 103 (the outlet end of the injector 100). At the end opposite to the injector outlet 113, the first section 111 of the injector chamber 110 has an injector inlet 115. The injector inlet 115 also is in fluid connection with one or more cleaning agent bores 116, 117. In Fig. 10, two cleaning agent bores 116, 117 are shown in the injector body 101 extending in a direction perpendicularly to the longitudinal axis A of the injector 100. It will be appreciated, that in other, not shown embodiments, the injector 100 may comprise one or three, or four or more cleaning agent bores 116, 117. It may also be noted, that the cleaning agent bores 116, 117 does not necessarily need to be formed perpendicularly to the longitudinal axis A of the injector 100, but may more generally be formed at an angle with the longitudinal axis A, however such that the cleaning agent bores 116, 117 will intersect with the injector chamber 110 at the injector inlet 115. Each of the cleaning agent bores 116, 117 has an inlet 116', 117', respectively, at an outer surface 118 of the injector body 101.

[0083] It may further be appreciated, that the inlet 116', 117' of the cleaning agent bores 116, 117 are formed at a place where the outer surface 118 of the injector body 101 has a circumferential groove, cleaning agent groove 119. The cleaning agent groove 119 forms an annular cleaning agent channel 120 (see Fig. 2) around the injector 100 together with the inner surface of the injector receiving bay 70 of the mixing unit 9 housing 10, when the injector 100 is inserted in the injector receiving bay 70 as shown in Fig. 2. The annular cleaning agent channel 120 serves to distribute the cleaning agent. Further, it is clear that the cleaning agent connection channel 61 of the mixing unit housing 10 opens into the annular cleaning agent channel 120 in an inlet 121 thereto (Figs 2 and 3).

[0084] In order to secure that cleaning agent only goes into the annular cleaning agent channel 120 not into the remainder of the injector receiving bay 70 suitable gaskets, such as O-rings may be arranged in annular grooves, gasket grooves 122, 123, which are formed in the outer surface 118 of the injector body 101, and on either side of the cleaning agent groove 119. In alternative embodiments (not shown), gaskets may instead be provided in grooves formed in the surface of the injector receiving bay 70.

[0085] Further, the injector comprises an injector liquid inlet 124. The injector liquid inlet 124 is formed as a bore from the outer surface 118 of the injector body 101 and into the injector body 101 in a transverse direction to the longitudinal axis A of the injector 100. The injector liquid inlet 124 communicates with a water inlet connection channel 125 (may also be called liquid inlet connection channel 125) formed in the longitudinal direction of the injector 100 (parallel to longitudinal axis A) that opens into the injector chamber 110 at the injector inlet 115.

[0086] It may further be appreciated, that the injector liquid inlet 124 is formed at a place where the outer surface 118 of the injector body 101 has a circumferential groove, water inlet groove 126 (may also be called liquid inlet groove 126). The water inlet groove 126 forms an annular water inlet channel 127 (may also be called annular liquid inlet channel 127), (see Fig. 2) around the injector 100 together with a portion of the inner surface of the injector receiving bay 70 of the mixing unit 9 housing 10, when the injector 100 is inserted in the injector receiving bay 70 as shown in Fig. 2. The annular water inlet channel 127 serves to distribute the water. Further it is clear that the liquid supply channel 64 in the mixing unit housing 10 opens into the annular water inlet channel 127 in an inlet 128 thereto (Figs 2 and 3).

[0087] In order to secure that water only goes into the annular water inlet channel 127, and not into the remainder of the injector receiving bay 70 suitable gaskets, such as O-rings may be arranged in annular grooves, gasket grooves 122, 129, which are formed in the outer surface 118 of the injector body 101, and on either side of the water inlet groove 126. In alternative embodiments (not shown), gaskets may instead be provided in grooves

formed in the surface of the injector receiving bay 70.

[0088] Thereby, pressurized liquid, preferably in the form of water, may be transported from the pump 141 via the liquid supply channel 64 in the mixing unit housing 10 into the annular water inlet channel 127 and further into the injector liquid inlet 124, and the water inlet connection channel 125 passing the injector inlet 115, and further into the injector chamber 110 and out the injector outlet 113. When the pressurized water passes the injector inlet 115, a vacuum is created in the cleaning agent bores 116, 117 and further the in annular cleaning agent channel 120. Thereby, cleaning agent will be sucked from the cleaning agent source 33, 34 into the annular cleaning agent channel 120 via the cleaning agent connection channel 61 of the mixing unit housing 10. In the injection chamber 110, water and cleaning agent is thereby mixed.

[0089] The injector outlet 113 is fluidly connected to the fluid outlet 44 of the housing 10 via a turbulence chamber 14 formed within the housing 10. As illustrated in e.g. Fig. 10, the injector inlet 115 has a narrower cross section than the cross section of the injector outlet 113.

[0090] As will be further appreciated from Fig. 3 and Fig. 10, the outer surface 118 of the injector body 101 has a further circumferential groove, gas groove 130. The gas groove 130 forms an annular gas inlet channel 131 (see Fig. 2) around the injector 100 together with a portion of the inner surface of the injector receiving bay 70 of the housing 10 of the mixing unit 9, when the injector 100 is inserted in the injector receiving bay 70 as shown in Fig. 2. The annular gas inlet channel 131 serves to distribute the gas (air). Further it is clear that gas supply channel 65 in mixing unit housing 10 opens into the annular gas inlet channel 131 in an inlet 132 thereto (Figs 2 and 3). When the injector 100 is in place in the injector receiving bay 70 in the mixing unit 9, the annular gas inlet channel 131 is in fluid communication with the turbulence chamber 14, via one or more helical grooves 133 formed in the outer surface 118 of a portion 134 of the injector body 101, and via a gap 135 between a cylindrical end portion 136 at the second (outlet) end 103 of the injector body and the inner surface of the injector receiving bay 70. The one or more helical grooves 133 formed in the outer surface 118 forms a helical channel 137 between the helical groove 133 and the inner surface of the injector receiving bay 70, when the injector is in place in the injector receiving bay 70 as shown in Fig. 2.

[0091] Thereby, the helical grooves 133 and the gap 135 forms a swirling stream of air around the stream of water and cleaning agent mixture exiting from the injector outlet 113. Experiments has shown that this provides an improved foaming effect.

[0092] We note that the helical grooves 133 are only used in certain aspects of the invention. In other aspects of the invention an acceptable foaming effect may be obtained using other types of air injection as mentioned above.

[0093] We also note, that in principle, the helical grooves may alternatively be formed in the surface of the

injector receiving bay 70 (not shown).

[0094] When, as described above, the injector 100 has an injector liquid inlet 124 formed in a direction transverse to a longitudinal axis A of the injector 110 it allows the insertion and retraction of the injector 100 from the housing 10 of the mixing unit 9, through a wall 22 thereof. This means that instead of the cleaning device comprising numerous injectors, with various capacities for providing foam and/or water/cleaning agent mixture, the injector may instead easily be exchanged with another injector 100 with a different capacity.

[0095] The interchangeability of the injectors 100 is further supported by the above described cleaning device 2 where

the injector 100 has an elongate injector body 101 with a first end 102 and an outlet end 103 opposite to the first end 102;

the outlet end 103 has smaller maximum dimension d2, than a maximum dimension d1 of the injector body at the first end 102;

wherein the injector body 101 only has a decreasing maximum dimension from the first end 102 to the outlet end 103,

wherein the injector body 101 comprises means for releaseably connecting the injector to a portion 70 of the housing 10 of the mixing unit 9.

[0096] The maximum dimension d1 and d2 of the injector body 101 at the first end 102 and at the outlet end 103 is the largest cross sectional extent (perpendicular to the longitudinal axis A) of the injector body at those locations. Preferably, the injector body 101 is cylindrical, or formed from generally cylindrical portions 134, 136, 143, 144, 145. In that case the maximum dimensions corresponds to diameters. In the shown embodiments the maximum dimension d1 at the first end 102 is the dimension (diameter) of the portion 145 of the injector body. In the shown embodiments the maximum dimension d2 at the outlet end 103 is the dimension (diameter) of the portion 134 of the injector body 101, wherein the helical grooves 133 are formed.

[0097] By the injector body 101 only having a decreasing maximum dimension from the first end 102 to the outlet end 103, is meant that none of the portions 144, 143, in between the two maximum dimension d1 and d2 exceeds that of a previous portion as seen from the first end 102 to the outlet end 103. In this context, the above-mentioned grooves 119, 126, 130 and the gasket grooves 122, 123, 129 are not counted with. Further, the gaskets (O-rings) 138, 139, 140 are not counted either as these are at least partly compressible.

[0098] By the injector body 101 comprising means for releaseably connecting the injector 100 to a portion 70 (such as the injector bay/port 70) of the housing 10 of the mixing unit 9 is meant e.g. that one or more of the cylindrical portions 143, 144, or 145 may be provided with means such as a threading (141, not shown in Fig.

10), which is configured to cooperate with connection means, such as corresponding threading (142 not shown in Fig. 10) in a section of the injector receiving bay 70 in the mixing unit 9. Apart from threading, other connection means known in the art may be used e.g. latches, bayonet fixtures, etc.

[0099] We note that, corresponding to the maximum dimensions of the cylindrical portions 135, 143, 144, or 145, the injector receiving bay 70 comprises sections 70-1, 70-2, 70-3 and 70-4 of increasing maximum dimensions from the end at the turbulence chamber 14 to the opposite end.

[0100] As mentioned above the mixing unit housing 10 is preferably formed as a solid block 11 of material, and the at least one injector 100 is arranged in an injector receiving bay 70 which is formed as a bore in the block 11. Further, the injector valve 40 is arranged in an injector receiving bay 74 formed as a bore in the block 11). Yet further, the cleaning agent connection channels 61, 62, 63, the water supply channel 64 and the gas supply channel 65 are preferably formed as bores in the block 11.

[0101] Thus, preferably, the housing 10 is formed from a solid block 11 of a uniform material as an integrated unit. The illustrated mixing unit 9 may preferably be manufactured from a metal alloy, e.g. stainless steel. Hereby, a robust mixing unit 9, which can withstand pressures up to 60 bar without malfunction or any noticeable leakage may be obtained. Also, it is obtained that weldings may be omitted or reduced in relation to the fluid connections of the cleaning device 2.

[0102] The bores mentioned above and below are channels, which may be formed in the block 11 by drilling out the bores and/or they may be formed by e.g. a molding process.

[0103] The block 11 may as shown in Figs 4A and B be an elongate box shaped structure, having two end surfaces 20, 21 and four side surfaces 22, 23, 24, 25. However, in not shown embodiments, the block 11 may have other shapes e.g. cylindrical.

[0104] The injector 100 may be arranged in a bore of stepwise decreasing maximum dimension (injector receiving bay 70) in the block 11, this bore being provided in one side surface (a bottom surface) 22 of the block 11. The fluid outlet 44 of the mixing unit 9 may be provided through an opposite side surface 23 (top surface). The turbulence chamber 14 is preferably provided as a bore through this side surface 23.

[0105] The cleaning agent connection channel 61, 62, 63, and the gas supply channel 65 may preferably be formed as bores through on or both of further sidewalls 24, 25, as are the bores for shafts for connecting the actuators 240, 280 to the injector valve 40 and the spraying liquid valve 80, respectively.

[0106] The injector valve 40 and the spraying liquid valve 80 are, as described above, arranged in an injector valve bay 74 and a spraying liquid valve bay 78, respectively. These bays 74, 78 may, in not shown embodiments, be formed as bores through one of the free side-

walls 22, 23, 24, 25.

[0107] However, in a preferred embodiment, and as shown in Figs. 2 and 3, the block 11 may preferably comprise a main block portion 11' and a lid block portion 11". The lid block portion 11" may be provided in extension of an end wall 20' of the main block portion 11'. The lid block portion 11" is preferably formed in the same material as the main block portion 11'. The distribution chamber 13, the liquid inlet 43, and the channels 81 and 64' are preferably provide as bores in the lid block portion 11". The injector valve bay 74 and a spraying liquid valve bay 78 are then formed as bores in through the main block portion 11', and the lid block portion 11" is then used to secure the injector valve 40 and the spraying liquid valve 80 in the injector valve bay 74 and a spraying liquid valve bay 78. The lid block portion 11" may be connected to the main portion 11' by use of suitable fasteners, such as bolts (not shown).

[0108] Returning now to Fig. 10, the injector 100 may preferably comprise a tool receiving lock 146 arranged at the portion 145 of the injector 100 at the first end thereof. The tool receiving lock 146 is preferably formed as a depression in the end wall 104 of the injector 100, opposite the injector outlet 113. Preferably, the tool receiving lock 146 has a polygonal cross sectional shape (in a plane perpendicular to the longitudinal axis A), e.g. a hexagonal shape. The tool receiving lock 146 may thereby allow rotation of the injector by a tool (not shown) having a correspondingly shaped cross-sectional shape. Thereby, the injector may be secured in the injector receiving bay 70 - or released therefrom.

[0109] Figs. 6A-F shows the injector 100 in various positions relative to the injector receiving bay 70 in mixing unit 9. In Fig. 6A, the injector 100 is inserted totally into the injector receiving bay 70 of the mixing unit 9, and is ready for use. In Fig. 6B the injector 100 has been released from the mating connection means, and has been slightly displaced relative to the housing 10. In Figs. 6C, the injector 100 has been further displaced away from its connected location. In Fig. 6D, the injector is seen completely removed from the injector receiving bay 70. In this figure, the corresponding shapes (dimension of sections of the injector 100 and the injector receiving bay 70) can be seen very clearly.

[0110] In Figs. 6E and 6F, the injector 100 and the housing 10 is again seen in a disassembled (Fig. 6E) and an assembled state (Fig. 6F). In the two figures, the above-mentioned hexagonal shape of a tool receiving lock 146 is clearly visible.

[0111] Turning now to Figs. 7-10, the figures illustrate in further detail, the principle of a swirling gas (air) flow, describe above. Fig. 7 is a partly sectional, perspective view through a housing 10 of a mixing unit and an injector. In Fig. 7, the housing 10 is sectioned at the injector receiving bay 70, and the injector 100 is shown un-sectioned and in perspective. In Figs. 7 the swirling air is represented by the arrows 400, 401, 402, 403. Gas (air) is injected via the gas supply channel 65 in the mixing

unit 9, as indicated by the arrow 404, and entered into the annular gas inlet channel 131 formed between the inner surface of injector receiving bay 70 and the gas groove 130 in outer surface 118 of injector body 101, as explained above in connection with Fig. 10. Cleaning agent is sucked into the injector 100 via the first cleaning agent connection channel 61 as indicated by arrow 405. Further, water is injected into the injector 100 via liquid supply channel 64, as indicated by the arrow 406 in Fig. 7. The water and cleaning agent will mix in the injector chamber 110 and exit mixed through the injector outlet 113 as indicated by the arrow 407 in Fig. 7.

[0112] Also, in Fig. 7 a threading 141 on the portion 145 of the injector 100 is clearly illustrated, the threading 141 cooperating with a corresponding threading 142 on the inside surface of the injector receiving bay 70 of the housing 11.

[0113] Now turning to Fig 9, this figure shows details of the portion 134, in which the helical grooves 133 are located. From the figure, it may be appreciated that a helical channel 137 is formed between the helical groove 133 and the inner surface of the injector receiving bay 70. At least one such channel 137 is formed, but preferably a plurality of channels 137 are formed. In the shown embodiment, and as most clearly visible in Fig. 8, four channels 137 are formed. Also, clearly visible in Fig. 9 is the inlet 132 from the gas supply channel 65 of the mixing unit 9. Also, Fig. 9 clearly visualizes that the outlet 113 in the end wall 114 of the injector body 101 at outlet/second end 103 of injector body 101 is formed on a platform provided by the cylindrical portion 136, which extends further in the direction of the second end 103, than the portion 134 with the helical groove 133. Thereby, when the injector 100 is arranged in the injector receiving bay 70, a small gap 135 is provided between injector receiving bay 70 and the outer surface 118 of the injector body 101 of the cylindrical portion 136. This gap 135 allows to format the swirling air flow around the injector outlet 113, before the air flow enters the turbulence chamber 14.

[0114] In the embodiments shown throughout the figures, the portion 136 of the body 101 of the injector 100 is shown and described as a cylindrical object. However, in further embodiments (not shown), a sidewall 105 may show an outward taper in the direction from the first end 102 towards the second end 103 of the portion 136 of the body 101 of the injector 100. Thus, in side view, the portion 136 would appear to have a conical section. This may aid in dimensioning the airflow. The diameter d4 of the portion 136 at the end wall 114 may thereby be increased to minimize the gap 135. This may limit/control the air-flow through the gap 135, while still allowing the swirl to create and develop in the space of the gap 135.

[0115] Now referring to Fig. 8, the figure shows a front view of an injector 100 inserted in the injector receiving bay 70 of a mixing unit. 9. The turbulence chamber 14 is the outmost facing surface. The inner circle of the figure shows the injector inlet 115. The next circle outward indicates the injector outlet 113. The area between this

circle and the next is the top surface 114 of the cylindrical portion 136, which forms the aforementioned extension ahead of the portion 134 where the helical grooves 133 are formed. The area between this circle and the next depicts the gap 135. The helical grooves 133 and thereby the helical channels 137 are shown with their exit into the gap 135.

[0116] Preferably, the injector 100 is positioned within the mixing unit 9 for providing a gap 135 around the injector outlet 132. This gap 135 is fluidly connected to the gas inlet 53 of the housing 10 for allowing gas (air) to pass between the injector outlet 132 and a portion of the injector receiving bay 70 of the housing 10 and mix with the first cleaning agent and water mixture at the turbulence chamber 14 and/or the fluid outlet 44 of the housing 10 to form foam.

[0117] When an injector is replaced with another injector, the ratio between the cross sectional area of the injector outlet and the cross sectional area of the helical channels 137 must remain constant, in order to obtain the same quality of foam, at different quantities.

[0118] The term "comprising" as used in the claims does not exclude other elements or steps. The term "a" or "an" as used in the claims does not exclude a plurality. The single processor or other unit may fulfill the functions of several means recited in the claims.

List of reference numbers

[0119]

A	longitudinal axis of injector
1	cleaning system
2	cleaning device
9	mixing unit
10	housing of mixing unit
11	block
11'	main part of block
11"	lid part of block
13	distribution chamber of mixing unit
14	turbulence chamber of mixing unit
15	channel from distribution chamber
16	outlet of channel from distribution chamber
16'	connector at outlet of channel from distribution chamber
20	end surface (outer surface) of housing of mixing unit
21	end surface (outer surface) of housing of mixing unit
22	side surface/bottom surface (outer surface) of housing of mixing unit
23	side surface/top surface (outer surface) of housing of mixing unit
24	side surface (outer surface) of housing of mixing unit
25	side surface (outer surface) of housing of mixing unit
30	cleaning agent valve - valve for regulating flow of

	cleaning agent from a 1 st source of a cleaning agent	102	first end of injector body
31	cleaning agent valve - valve for regulating flow of cleaning agent from a 2 nd source of a cleaning agent	103	second end of injector body/outlet end of injector body
32	valve for regulating flow of cleaning agent from a 3 rd source of a cleaning agent	104	end wall of injector opposite injector outlet
33	1 st source of a cleaning agent, reservoir	5 110	injector chamber
34	2 nd source of a cleaning agent, reservoir	111	first section of injector chamber
35	cleaning agent input line	112	second section of injector chamber
36	cleaning agent input line	113	injector outlet
37	cleaning agent inlet of mixing unit	114	an end wall of the injector body at outlet end
37'	cleaning agent connector	10 115	injector inlet
38	cleaning agent inlet of mixing unit	116	cleaning agent bore in injector
38'	cleaning agent connector	117	cleaning agent bore in injector
39	cleaning agent inlet of mixing unit	118	outer surface of the injector body
39'	cleaning agent connector	119	cleaning agent groove in injector body
40	injector valve	15 120	annular cleaning agent channel between the injector receiving port/bay and cleaning agent groove
41	source of liquid, pump	121	inlet of cleaning agent connection channel 61 of the mixing unit housing into annular cleaning agent channel
41'	pump inlet	20	
41"	pump outlet	122	gasket groove in injector
42	liquid supply tubing	123	gasket groove in injector
43	liquid inlet of mixing unit	124	injector liquid inlet
43'	connector, liquid connector	125	liquid/water inlet connection channel
43"	gasket	25 126	liquid/water inlet groove in outer surface of injector body
44	fluid outlet of mixing unit	127	annular liquid/water inlet channel formed between injector receiving port/bay and water inlet groove
44'	connector, gas connector		
44"	gasket		
49	source of liquid		
50	gas supply valve	30 128	inlet of liquid supply channel into annular water inlet channel
51	source of pressurized gas, compressor	129	gasket groove
52	gas piping	130	gas groove in outer surface of injector body
51'	gas outlet of source of pressurized gas/compressor	131	annular gas inlet channel formed between the surface of injector receiving port/bay and gas groove in outer surface of injector body
53	gas inlet of mixing unit	35	
53'	connector, gas connector.		
61	first cleaning agent connection channel in mixing unit	132	inlet of gas supply channel in housing into the annular gas inlet channel
62	second cleaning agent connection channel in mixing unit	133	helical grooves formed in the outer surface of a portion 134 of the injector body
63	third cleaning agent connection channel in mixing unit	40 134	portion of the injector body with helical grooves
64	liquid supply channel in mixing unit	135	gap between a cylindrical end portion at the second (outlet) end of the injector body and the inner surface of the injector receiving port/bay
65	gas supply channel in mixing unit		
66	rinsing channel	45 136	cylindrical end portion at the second (outlet) end of the injector body
70	injector receiving port/bay in mixing unit		
74	injector valve receiving port/bay in mixing unit	137	helical channel formed between the helical groove and the inner surface of the injector receiving port/bay
78	spraying liquid valve receiving port/bay in mixing unit	50 138	gasket, O-ring
80	spraying liquid valve	139	gasket, O-ring
81	fluid connection between the liquid inlet 43 and the spraying liquid valve 80 in mixing unit	140	gasket, O-ring
82	fluid connection between the spraying liquid valve 80 and the liquid outlet 44 in mixing unit	d1	maximum dimension (diameter) of the injector body at the first end
100	injector	55 d2	maximum dimension (diameter) of the injector body at the outlet end
101	injector body	d3	dimension (diameter) of the portion 134 of the injector body

d4	dimension (diameter) of the injector outlet 113		injector
141	threading on injector body for connection to the injector receiving port/bay in mixing unit	403	arrow, indicating airflow passing away from the injector
142	threading in the housing of the mixing unit	404	arrow, indicating the airflow into the injector
143	portion of injector body	5 405	arrow, indicating the flow of cleaning agent into the injector
144	portion of injector body		
145	portion of injector body at first end	406	arrow, indicating the flow of liquid/water into the injector
146	tool receiving lock	407	arrow, indicating the flow of water and cleaning agent mixture from the outlet 113 of the injector.
200	control system	10	
201	control unit		
210	pump motor		
230	actuator for cleaning agent valve		
231	control connection between control unit 200 and actuator 230	15	
232	actuator for cleaning agent valve		
233	control connection between control unit 200 and actuator 232		
240	actuator for injector valve 40		
241	control connection between control unit 200 and actuator for injector valve	20	
250	actuator for gas supply valve 50		
251	control connection between control unit 200 and actuator for gas supply valve		
261	actuator for outlet control valve	25	
262	actuator for outlet control valve		
263	actuator for outlet control valve		
270	control connection for actuator for outlet control valve		
271	control connection for actuator for outlet control valve	30	
272	control connection for actuator for outlet control valve		
273	control connection for actuator for outlet control valve	35	
280	actuator for the spraying liquid valve 80		
281	control connection between control unit 200 and actuator for spraying liquid valve		
290	actuator for rinsing valve	40	
300	external cleaning system		
310	tubing of external cleaning system		
311	tubing of external cleaning system, branch		
312	tubing of external cleaning system, branch		
313	tubing of external cleaning system, branch	45	
321	outlet control valve		
322	outlet control valve		
323	outlet control valve		
331	cleaning outlet of external cleaning system		
332	cleaning outlet of external cleaning system	50	
333	cleaning outlet of external cleaning system		
340	delivery nozzles at cleaning outlet		
400	arrow, indicating airflow passing away from the injector	55	
401	arrow, indicating airflow passing away from the injector		
402	arrow, indicating airflow passing away from the		

Claims

1. A mixing unit (9) for supplying foam for cleaning, the mixing unit (9) comprising:

a housing (10) having a liquid inlet (43) for receiving pressurized water, a gas inlet (53) for receiving pressurized air, a fluid outlet (44) for delivering said foam, a cleaning agent inlet (39), and an injector receiving bay (70) for receiving an injector (100);
the mixing unit (9) further comprising an injector (100), the injector (100) having

- an injector body (101) with a first end (102) and a second end (103) opposite to the first end (102), and a longitudinal axis (A);
- an injector inlet (115);
- an injector outlet (113) formed through the second end (103); and
- an injector liquid inlet (124);

which injector inlet (115) is fluidly connectable to the cleaning agent inlet (39) of the housing (10),
which injector liquid inlet (124) is fluidly connectable to the liquid inlet (43) of the housing (10), and
which injector outlet (113) is fluidly connected to the fluid outlet (44) of the housing (10),
characterised in that the injector liquid inlet (124) is in a direction transverse to the a longitudinal axis (A) of the injector (100).

2. A mixing unit (9) according to claim 1, wherein the injector liquid inlet (124) is formed as a bore from an outer surface (118) of the injector body (101).

3. A mixing unit (9) according to claim 1 or 2, wherein the injector liquid inlet (124) communicates with a liquid inlet connection channel (125) extending in the direction of the longitudinal axis (A) of the injector body and opens into an injector chamber (110) at the injector inlet (115).

4. A mixing unit (9) according to any one of the claims

1-3, wherein the injector liquid inlet (124) is formed at a circumferential groove (26), which circumferential groove (26) is formed in the outer surface (118) of the injector body (101), the circumferential groove (126), forming an annular water inlet channel (127) around the injector (100) together with a portion of the inner surface of the injector receiving bay (70) of the mixing unit (9), when the injector (100) is inserted in the injector receiving bay (70).

5. A mixing unit (9) according to any one of the claims 1-4, wherein the injector (100) is positioned within the mixing unit (9) in such a way that a gap (135) around the injector outlet (113) is provided, said gap (135) being fluidly connected to the gas inlet (65) for allowing pressurized gas to enter and pass through the gap (135) and mix with a cleaning agent and liquid at the fluid outlet (44) of the housing (10).

6. A mixing unit (9) according to any one of the claims 1-5, wherein the injector body (101) only has a decreasing maximum dimension from the first end (102) to the second end (103), and where the injector body (101) comprises means for releaseably connecting the injector to a portion (70) of the housing (10) of the mixing unit (9).

7. A mixing unit (9) according to claim 6, wherein the means for releaseably connecting the injector (100) to a portion (70) of the housing (10) of the mixing unit (9) comprises a threading (141) located on a portion (145) of the injector body (101) at the first end (102) of the injector (100), the threading (141) cooperating with a corresponding threading (142) on the surface of the injector receiving bay (70) of the mixing unit (9).

8. A mixing unit (9) according to any one of the claims 1-7, wherein helical grooves (133) are formed in the outer surface (118) of a portion (134) of the injector body in order to provide a swirling air flow surrounding the injector outlet (113).

9. A cleaning device (2) comprising:

- a mixing unit (9) according to any one of the claims 1-8;
- at least one cleaning agent valve (30, 31) for supplying cleaning agents, and connectable to a source of a cleaning agent (33,34);
- an injector valve (40) connectable to a source of pressurized liquid (49);
- a gas supply valve (50) connectable to a source of pressurized gas (51);

wherein the at least one injector (100) and the injector valve (40) are integrated within the mixing unit housing (10);

wherein cleaning agent channels (61, 62, 63) fluidly connecting the at least one injector (100) and the source of cleaning agent (33, 34) are formed within the mixing unit housing (10),

wherein a liquid supply channel (64) fluidly connecting the injector valve (40) with the injector (100) is formed within the mixing unit housing (10); and wherein a gas supply channel (65), fluidly connecting the gas supply valve (50) and the at least one injector (100), is formed in the mixing unit housing (10).

10. A cleaning device (2) according to claim 9, wherein the mixing unit housing (10) is formed as a solid block (11) of material,

wherein the at least one injector (100) is arranged in an injector receiving bay (70) formed as a bore in said block (11);

wherein the injector valve (40), is arranged in an injector receiving bay (74) formed as a bore in said block (11), and

wherein the cleaning agent connection channels (61, 62, 63), the water supply channel (64) and the gas supply channel (65) are formed as bores in the block (11).

Patentansprüche

1. Mischeinheit (9) für die Bereitstellung von Schaum für Reinigung, wobei die Mischeinheit (9) umfasst:

ein Gehäuse (10) mit einem Flüssigkeitseintritt (43) für die Aufnahme von Druckwasser, einem Gaseinlass (53) für die Aufnahme von Druckluft, einem Flüssigkeitsaustritt (44) für das Abgeben des Schaums, einem Reinigungsmiteleinlass (39) und einem Injektoraufnahmegestell (70) für die Aufnahme eines Injektors (100); wobei die Mischeinheit (9) ausserdem einen Injektor (100) umfasst, wobei der Injektor (100) aufweist

- einen Injektorhauptteil (101) mit einem ersten Endstück (102) und einem zweiten Endstück (103) gegenüber dem ersten Endstück (102), und einer längslaufenden Achse (A);
- einen Injektoreinlass (115);
- einen durch das zweite Endstück (103) geformten Injektorauslass (113); und
- einen Injektorflüssigkeitseintritt (124);

wobei der Injektoreinlass (115) mit dem Reinigungsmiteleinlass (39) des Gehäuses (10) fluidverbindbar ist,

wobei der Injektorflüssigkeitseintritt (124) mit dem Flüssigkeitseintritt (43) des Gehäuses (10)

- fluidverbindbar ist, und
wobei der Injektorauslass (113) mit dem Flüssigkeitsaustritt (44) des Gehäuses (10) fluidverbunden ist,
dadurch gekennzeichnet, dass der Injektorflüssigkeitseintritt (124) in einer Richtung diagonal zur längslaufenden Achse (A) des Injektors (100) positioniert ist.
2. Mischeinheit (9) nach Anspruch 1, wobei der Injektorflüssigkeitseintritt (124) aus einer äusseren Oberfläche (118) des Injektorhauptteils (101) als eine Bohrröffnung geformt ist.
3. Mischeinheit (9) nach Anspruch 1 oder 2, wobei der Injektorflüssigkeitseintritt (124) mit einer Flüssigkeitseintrittsverbindungsrinne (125) kommuniziert, die sich in die Richtung der längslaufenden Achse (A) des Injektorhauptteils erstreckt und sich in eine Injektorkammer (110) an dem Injektoreinlass (115) öffnet.
4. Mischeinheit (9) nach einem jeglichen der Ansprüche 1-3, wobei der Injektorflüssigkeitseintritt (124) an einer umlaufenden Nut (26) geformt ist, wobei die umlaufende Nut (26) in der äusseren Oberfläche (118) des Injektorhauptteils (101) geformt ist, wobei die umlaufende Nut (126) einen Wassereintrittsringkanal (127) um den Injektor (100) formt zusammen mit einem Teilbereich der inneren Oberfläche des Injektoraufnahmegestells (70) der Mischeinheit (9), wenn der Injektor (100) in das Injektoraufnahmegestell (70) eingeführt wird.
5. Mischeinheit (9) nach einem jeglichen der Ansprüche 1-4, wobei der Injektor (100) auf solche Weise in der Mischeinheit (9) angeordnet ist, dass um den Injektorauslass (113) eine Lücke (135) erschafft wird, wobei die Lücke (135) zum Gaseinlass (65) fluidverbunden ist, um zuzulassen dass Druckgas hineinkommt und durch die Lücke (135) durchläuft und sich mit einem Reinigungsmittel und Flüssigkeit beim Flüssigkeitsaustritt (44) des Gehäuses (10) mischt.
6. Mischeinheit (9) nach einem jeglichen der Ansprüche 1-5, wobei der Injektorhauptteil (101) nur eine abnehmende Maximaldimension vom ersten Endstück (102) zum zweiten Endstück (103) aufweist, und wobei der Injektorhauptteil (101) dafür Mittel umfasst, den Injektor zu einem Teilbereich (70) des Gehäuses (10) der Mischeinheit (9) freigebbar zu verbinden.
7. Mischeinheit (9) nach Anspruch 6, wobei die Mittel dafür, den Injektor zu einem Teilbereich (70) des Gehäuses (10) der Mischeinheit (9) freigebbar zu verbinden, ein Gewindeschneiden (141) umfassen, das auf einem Teilbereich (145) des Injektorhauptteils (101) angeordnet ist am ersten Endstück (102) des Injektors (100), wobei das Gewindeschneiden (141) mit einem entsprechenden Gewindeschneiden (142) auf der Oberfläche des Injektoraufnahmegestells (70) der Mischeinheit (9) zusammenarbeitet.
8. Mischeinheit (9) nach einem jeglichen der Ansprüche 1-7, wobei helikale Nuten (133) in der äusseren Oberfläche (118) des Teilbereichs (134) des Injektorhauptteils geformt sind, um eine Drallströmung von Luft um den Injektorauslass (113) herum zu versorgen.
9. Reinigungsgerät (2) umfassend:
- eine Mischeinheit (9) nach einem jeglichen der Ansprüche 1-8;
- wenigstens ein Reinigungsmittelventil (30, 31) für die Versorgung von Reinigungsmitteln, das zu einer Reinigungsmittelquelle (33,34) verbindbar ist;
- ein Injektorventil (40), das zu einer Quelle von unter Druck stehender Flüssigkeit (49) verbindbar ist;
- ein Gasversorgungsventil (50), das zu einer Druckgasquelle (51) verbindbar ist;
wobei der wenigstens eine Injektor (100) und das Injektorventil (40) in dem Gehäuse der Mischeinheit (10) integriert sind;
wobei Reinigungsmittelrinnen (61, 62, 63), die den wenigstens einen Injektor (100) und die Reinigungsmittelquelle (33, 34) fluidverbinden, in dem Gehäuse der Mischeinheit (10) geformt sind, wobei eine Flüssigkeitsversorgungsrinne (64), die das Injektorventil (40) mit dem Injektor (100) fluidverbinden, in dem Gehäuse der Mischeinheit (10) geformt ist; und
wobei eine Gasversorgungsrinne (65), die das Gasversorgungsventil (50) und den wenigstens einen Injektor (100) fluidverbinden, in dem Gehäuse der Mischeinheit (10) geformt ist.
10. Reinigungsgerät (2) nach Anspruch 9, wobei das Gehäuse der Mischeinheit (10) als einen soliden Block (11) von Material geformt ist,
wobei der wenigstens eine Injektor (100) in einem Injektoraufnahmegestell (70), das als eine Bohrröffnung in dem Block (11) geformt ist, angeordnet ist,
wobei das Injektorventil (40) in einem Injektoraufnahmegestell (74), das als eine Bohrröffnung in dem Block (11) geformt ist, angeordnet ist, und
wobei die Reinigungsmittelverbindungsrinnen (61, 62, 63), die Wasserversorgungsrinne (64)

und die Gasversorgungsrinne (65) als Bohröffnungen in dem Block (11) geformt sind.

Revendications

1. Unité de mélange (9) pour l'approvisionnement en mousse pour le nettoyage, l'unité de mélange (9) comprenant:

un boîtier (10) ayant une entrée du liquide (43) pour recevoir de l'eau pressurisée, une entrée de gaz (53) pour recevoir de l'air pressurisé, une sortie de liquide (44) pour livrer ladite mousse, une entrée de produit de nettoyage (39), et une baie de réception d'injecteur (70) pour recevoir un injecteur (100);
l'unité de mélange (9) comprenant en outre un injecteur (100), l'injecteur (100) ayant

- un corps d'injecteur (101) avec une première extrémité (102) et une deuxième extrémité (103) à l'opposé de la première extrémité (102), et un axe longitudinal (A);
- une entrée d'injecteur (115);
- une sortie d'injecteur (113) formée à travers la deuxième extrémité (103); et
- une entrée de liquide d'injecteur (124);

laquelle entrée d'injecteur (115) étant reliée fluidiquement à l'entrée du produit de nettoyage (39) du boîtier (10),
laquelle entrée du liquide d'injecteur (124) étant reliée fluidiquement à l'entrée du liquide (43) du boîtier (10), et
laquelle sortie d'injecteur (113) étant reliée fluidiquement à la sortie du liquide (44) du boîtier (10),
caractérisée en ce que l'entrée du liquide d'injecteur (124) se situe dans une direction transversale à l'axe longitudinale (A) de l'injecteur (100).

2. Unité de mélange (9) selon la revendication 1, où l'entrée du liquide d'injecteur (124) est formée comme un trou d'une surface extérieure (118) du corps d'injecteur (101).
3. Unité de mélange (9) selon la revendication 1 ou la revendication 2, où l'entrée du liquide d'injecteur (124) communique avec un canal de connexion d'entrée de liquide (125) s'étendant dans la direction de l'axe longitudinal (A) du corps d'injecteur et s'ouvre dans une chambre d'injecteur (110) à l'entrée de l'injecteur (115).
4. Unité de mélange (9) selon l'une quelconque des revendications 1 à 3, où l'entrée du liquide d'injecteur

(124) est formée à une gorge en circonférence (26), laquelle gorge en circonférence (26) étant formée dans la surface extérieure (118) du corps d'injecteur (101), la gorge en circonférence (26) formant un canal annulaire d'entrée en eau (127) autour de l'injecteur (100) avec une partie de la surface intérieure de la baie de réception d'injecteur (70) de l'unité de mélange (9), lorsque l'injecteur (100) est inséré dans la baie de réception d'injecteur (70).

5. Unité de mélange (9) selon l'une quelconque des revendications 1 à 4, où l'injecteur (100) est positionné à l'intérieur de l'unité de mélange (9) d'une telle manière qu'un écart (135) autour de la sortie de l'injecteur (113) est fourni, ledit écart (135) étant fluidiquement lié à l'entrée de gaz (65) afin de permettre au gaz pressurisé d'entrer et de passer à travers l'écart (135) et de se mélanger avec un produit de nettoyage et d'un liquide à la sortie du liquide (44) du boîtier (10).
6. Unité de mélange (9) selon l'une quelconque des revendications 1 à 5, où le corps d'injecteur (101) a seulement une dimension maximale diminuant de la première extrémité (102) à la deuxième extrémité (103), et où le corps d'injecteur (101) comprend des moyens pour lier de manière amovible l'injecteur à une partie (70) du boîtier (10) de l'unité de mélange (9).
7. Unité de mélange (9) selon la revendication 6, où les moyens pour lier de manière amovible l'injecteur (100) à une partie (70) du boîtier (10) de l'unité de mélange (9) comprennent un filetage (141) localisé sur une partie (145) du corps d'injecteur (101) à la première extrémité (102) de l'injecteur (100), le filetage (141) coopérant avec un filetage correspondant (142) sur la surface de la baie de réception d'injecteur (70) de l'unité de mélange (9).
8. Unité de mélange (9) selon l'une quelconque des revendications 1 à 7, où des cannelures hélicoïdales (133) sont formées dans la surface extérieure (118) d'une partie (134) du corps d'injecteur de manière à fournir un écoulement d'air tournant entourant la sortie d'injecteur (113).

9. Dispositif de nettoyage (2) comprenant:

- une unité de mélange (9) selon l'une quelconque des revendications 1 à 8;
- au moins une valve de produit de nettoyage (30, 31) pour fournir des produits de nettoyage, et reliable à une source d'un produit de nettoyage (33, 34);
- une valve d'injecteur (40) reliable à une source de liquide pressurisé (49);
- un robinet de gaz (50) reliable à une source de

gaz pressurisé (51);

où le au moins un injecteur (100) et la valve d'injecteur (40) sont intégrés à l'intérieur du boîtier de l'unité de mélange (10); 5

où des canaux de produit de nettoyage (61, 62, 63) reliant fluidiquement le au moins un injecteur (100) et la source du produit de nettoyage (33, 34), sont formés à l'intérieur du boîtier de l'unité de mélange (10), 10

où un canal d'alimentation en liquide (64) reliant fluidiquement la valve d'injecteur (40) avec l'injecteur (100), est formé à l'intérieur du boîtier de l'unité de mélange (10); et

où un canal d'alimentation en gaz (65), fluidiquement reliant le robinet de gaz (50) et le au moins un injecteur (100), est formé dans le boîtier de l'unité de mélange (10). 15

10. Dispositif de nettoyage (2) selon la revendication 9, 20
où le boîtier de l'unité de mélange (10) est formé comme un bloc solide (11) de matériau,

où le au moins un injecteur (100) est agencé dans une baie de réception d'injecteur (70) formée comme un trou dans ledit bloc (11); 25

où ladite valve d'injecteur (40) est agencée dans une baie de réception d'injecteur (70) formée comme un trou dans ledit bloc (11); et

où les canaux de produit de nettoyage (61, 62, 63), le canal d'alimentation en eau (64) et le canal d'alimentation en gaz (65) sont formés comme des trous dans le bloc (11). 30

35

40

45

50

55




Fig. 1 (Prior art)




Fig. 2




Fig. 3










Fig. 4A
















Fig. 6E



Figs. 6F








Fig. 9



REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 5855217 A [0007]
- WO 2015067989 A1 [0007]
- WO 2015067989 A [0030]