



US008072766B2

(12) **United States Patent**
Shimura et al.

(10) **Patent No.:** **US 8,072,766 B2**
(45) **Date of Patent:** **Dec. 6, 2011**

(54) **PORTABLE DEVICE FOR TRANSMITTING SIGNAL**

(75) Inventors: **Tokio Shimura, Anjo (JP); Mitsuru Nakagawa, Chiryu (JP)**

(73) Assignee: **Denso Corporation, Kariya (JP)**

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 394 days.

4,876,441 A *	10/1989	Hara et al.	235/488
5,038,251 A *	8/1991	Sugiyama et al.	235/61 R
5,291,193 A *	3/1994	Isobe et al.	340/825.69
5,422,783 A *	6/1995	Darbee	361/679.08
5,523,745 A *	6/1996	Fortune et al.	340/825.19
5,654,111 A *	8/1997	Minomiya et al.	429/162
5,782,867 A *	7/1998	Shrock et al.	606/234
5,805,423 A *	9/1998	Wever et al.	361/760
6,137,710 A *	10/2000	Iwasaki et al.	365/52
6,172,431 B1 *	1/2001	Honeyman	307/10.2
6,262,886 B1 *	7/2001	DiFonzo et al.	361/679.34

(Continued)

(21) Appl. No.: **12/175,860**

(22) Filed: **Jul. 18, 2008**

(65) **Prior Publication Data**

US 2009/0040737 A1 Feb. 12, 2009

(30) **Foreign Application Priority Data**

Aug. 7, 2007 (JP) 2007-205873

(51) **Int. Cl.**
H05K 5/00 (2006.01)

(52) **U.S. Cl.** **361/752**; 361/679.08; 361/679.34; 361/760; 174/359; 307/11; 340/5.61; 340/5.62

(58) **Field of Classification Search** 361/752, 361/679.08, 679.34, 760; 174/359; 307/11; 340/5.61, 5.62

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,158,230 A *	6/1979	Washizuka et al.	708/142
4,635,354 A *	1/1987	Chrobak et al.	29/622
4,681,987 A *	7/1987	Suwa	200/5 A
4,801,768 A *	1/1989	Sugiyama et al.	200/5 A
4,864,115 A *	9/1989	Imran et al.	235/492

FOREIGN PATENT DOCUMENTS

JP 62-290024 12/1987

(Continued)

OTHER PUBLICATIONS

Japanese Office Action dated Sep. 15, 2009, issued in corresponding Japanese Application No. 2007-205873, with English translation.


Primary Examiner — Xiaoliang Chen

(74) *Attorney, Agent, or Firm* — Nixon & Vanderhye PC

(57) **ABSTRACT**

A portable device includes an operating part, a circuit board, and a case body for housing the operating part and the circuit board. The circuit board has a circuit section configured to transmit a signal to an external device. A terminal electrode and a pair of switch electrodes are disposed on the circuit board. The terminal electrode supplies electricity from a power source to the circuit section. A switch element is configured to electrically couple the pair of switch electrodes in accordance with an operation of the operating part. A resin member is disposed on the circuit board in such a manner that the circuit section is covered with the resin member and the terminal electrode and the pair of switch electrodes are exposed to an outside of the resin member.

16 Claims, 3 Drawing Sheets



U.S. PATENT DOCUMENTS

6,282,819	B1 *	9/2001	Gu	40/124.03
6,349,824	B1 *	2/2002	Yamada	206/316.1
6,377,465	B1 *	4/2002	Tanaka	361/760
6,463,263	B1 *	10/2002	Feilner et al.	455/90.1
6,545,233	B2 *	4/2003	Takezawa	200/6 A
6,546,435	B1 *	4/2003	Yoshimura et al.	710/4
6,733,327	B2	5/2004	Sugimoto et al.	
6,849,817	B2 *	2/2005	Takata et al.	200/339
7,050,292	B2	5/2006	Shimura et al.	
7,067,734	B2 *	6/2006	Abe et al.	174/359
7,142,413	B2 *	11/2006	Sugimoto et al.	361/679.57
7,201,310	B2 *	4/2007	Kawamata	235/375
7,225,972	B2 *	6/2007	Kawamata	235/375
7,271,423	B2 *	9/2007	Hanamoto et al.	257/98
7,330,743	B2 *	2/2008	Hutchison et al.	455/575.8
7,355,137	B2 *	4/2008	Kawasaki et al.	200/302.2
7,445,476	B2 *	11/2008	Ujii et al.	439/159
7,463,134	B1 *	12/2008	Stilley	340/5.61
7,519,404	B2 *	4/2009	Lonka et al.	455/575.4
7,561,684	B2 *	7/2009	Tsutaichi et al.	379/433.01

7,635,821	B2 *	12/2009	Hamada	200/343
2003/0010721	A1 *	1/2003	Aldred et al.	210/694
2005/0052128	A1 *	3/2005	Nakanishi	313/506
2005/0060064	A1 *	3/2005	Valen et al.	700/264
2005/0136852	A1 *	6/2005	Nakagawa et al.	455/90.3
2005/0181843	A1 *	8/2005	Tsujimoto	455/575.1
2006/0066151	A1 *	3/2006	Hatemata	307/11
2006/0245145	A1	11/2006	Wada et al.	
2007/0066394	A1 *	3/2007	Ikeda et al.	463/37
2007/0200053	A1 *	8/2007	Nomura et al.	250/206
2007/0223317	A1 *	9/2007	Sun	368/88
2008/0084403	A1 *	4/2008	Kimura et al.	345/204
2010/0048249	A1 *	2/2010	Furuta et al.	455/566

FOREIGN PATENT DOCUMENTS

JP	06-268548	9/1994
JP	11-280313	10/1999
JP	2002-343905	11/2002
JP	2004-153526	5/2004
JP	2004-172176	6/2004

* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5A





FIG. 5B



PORTABLE DEVICE FOR TRANSMITTING SIGNAL

CROSS REFERENCE TO RELATED APPLICATIONS

The present application is based on and claims priority to Japanese Patent Application No. 2007-205873 filed on Aug. 7, 2007, the contents of which are incorporated in their entirety herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a portable device for transmitting a signal.

2. Description of the Related Art

U.S. Pat. No. 7,050,292 (corresponding to JP-A-2004-153526) discloses a portable equipment that can be used for a keyless entry system. The portable equipment includes a circuit board, a button battery, and a case body for housing the circuit board and the button battery therein. The case body includes an upper case and a lower case. The circuit board has a circuit section that includes electronic elements. The circuit section is supplied with electricity from the button battery. At opening portions of the upper case, knob pieces are disposed so that switching elements disposed on the circuit board can be controlled by operating the knob pieces.

In the case body, a water-proof cover is disposed. The water-proof cover includes a thin-film cover and a ring-shaped part integrally formed at an outer peripheral portion of the thin-film cover. The ring-shaped part is held between the upper case and the lower case. The thin-film cover is disposed between the circuit board and the knob pieces.

In the above-described portable equipment, a pressing surface of the upper case and a pressing surface of the lower case that press the ring-shaped part of the water-proof cover are required to be formed with a high accuracy so as to provide a stable waterproof property of the circuit section. In addition, the upper case and the lower case are required to have a high rigidity to maintain the pressing surfaces formed with the high accuracy. Thus, a thickness of the upper case and a thickness of the lower case may increase, and thereby a dimension of the portable equipment may increase.

SUMMARY OF THE INVENTION

In view of the foregoing problems, it is an object of the present invention to provide a portable device including a waterproof circuit section.

According to an aspect of the invention, a portable device includes a case body, an operating part, a circuit board, a terminal electrode, a pair of switch electrodes, a switch element, and a resin member. The operating part is disposed in the case body. The circuit board is housed in the case body and has a circuit section. The circuit section includes an electronic element mounted on the circuit board and is configured to transmit a signal to an external device. The terminal electrode is disposed on the circuit board for supplying electricity from a power source to the circuit section. The pair of switch electrodes is disposed on the circuit board. The switch element is configured to electrically couple the pair of switch electrodes in accordance with an operation of the operating part. The resin member is disposed on the circuit board in such a manner that the circuit section is covered with the resin member and the terminal electrode and the pair of switch electrodes are exposed to an outside of the resin member.

The present portable device can ensure a waterproof property of the circuit section of the printed circuit board.

BRIEF DESCRIPTION OF THE DRAWINGS

Additional objects and advantages of the present invention will be more readily apparent from the following detailed description of preferred embodiments when taken together with the accompanying drawings. In the drawings:

FIG. 1 is a perspective view illustrating a portable device according to an exemplary embodiment of the invention;

FIG. 2 is an exploded perspective view illustrating the portable device;

FIG. 3 is a perspective view illustrating a circuit unit viewed from a knob sheet side;

FIG. 4 is a plan view illustrating a pair of opposite electrodes; and

FIG. 5A and FIG. 5B are perspective views illustrating a resin member in the circuit unit.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

A portable device **1** according to an exemplary embodiment of the invention can be suitably used as a portable electronic key, i.e., a smart key. For example, identification data of the portable device **1** is verified with identification data of a vehicle by a two-way communication, and then each door of the vehicle can be locked and unlocked by using the portable device **1**. In addition, when a passenger having the portable device **1** is in a vehicle compartment, a steering lock mechanism can be unlocked and an engine can be started by using the portable device **1**.

As illustrated in FIG. 1, the portable device **1** includes a case body including a front case **10** and a rear case **50**. The front case **10** has a plurality of opening portions. A plurality of knob pieces **21** is disposed at the plurality of opening portions respectively.

The front case **10** may be made of resin such as polycarbonate resin, acrylonitrile-butadiene-styrene resin (ABS resin), and polyamide resin. The rear case **50** may be made of resin similar to the resin of the front case **10**. On an outer surface of the rear case **50**, elastomer layer **51** is integrally formed with the rear case **50**. The elastomer layer **51** is an elastic sheet made of thermoplastic elastomer resin. The case body has a through hole as a key ring hole, for example.

In the portable device **1** illustrated in FIG. 1, four knob pieces **21** are disposed. Each knob piece **21** is provided for controlling one of a door lock/unlock function, a trunk open function, a power slide door open/close function, a power back door open/close function, and a panic response function, for example. The panic response function is a function for activating an emergency response operation of the vehicle when the vehicle is involved in a criminal act or when the vehicle has a possibility of being involved in a criminal act. Each knob piece **21** is an example of an operating part.

As illustrated in FIG. 2, between the front case **10** and the rear case **50**, a knob sheet **20**, a circuit unit **30**, and battery holder **40** is arranged in this order from the front case side to the rear case side. Each of the knob sheet **20** and the circuit unit **30** has an approximately rectangular shape corresponding to a shape in the front case **10** and the rear case **50**. The battery holder **40** is configured to house a button battery **41** therein.

The knob sheet **20** is made of silicon rubber for example. The knob pieces **21** are formed in the knob sheet **20** and are coupled to each other. On a rear case side of each knob piece

21, a conductive contact 22 is integrally formed. The conductive contacts 22 consist mainly of carbon, for example.

The circuit unit 30 includes a printed circuit board 31. The printed circuit board 31 has a first surface 311 arranged on the rear case side, a second surface 312 arranged on the front case side, and a side surface 313 extending from a peripheral edge of first surface 311 to a peripheral edge of the second surface 312. On the first surface side of the printed circuit board 31, a circuit section 32 is provided. In the circuit section 32, electronic elements (not shown) including an antenna element are mounted on the first surface 311. The circuit section 32 is configured to transmit a signal to an external device disposed in the vehicle.

On the first surface 311 of the printed circuit board 31, a pair of terminals 33 is also disposed. The pair of terminals 33 is an example of a terminal electrode for supplying electricity from the button battery 41 to the circuit section 32.

As illustrated in FIG. 3, on the second surface 312 of the printed circuit board 31, four pairs of opposite electrodes 34 are disposed to face the four conductive contacts 22 of the knob sheet 20, respectively. When one conductive contact 22 comes in contact with the corresponding pair of opposite electrodes 34, electric current flows between the pair of opposite electrodes 34. When the one conductive contact 22 separates from the pair of opposite electrodes 34, electric current does not flow between the pair of opposite electrodes 34. Thus, an electric switching is controlled when the conductive contact 22 comes in contact with and separates from the pair of the opposite electrodes 34.

As illustrated in FIG. 4, each opposite electrode 34 has a pectinate shape. That is, each opposite electrode 34 has a plurality of protruding portions. In each pair of opposite electrodes 34, one opposite electrode 34 is separated from the other opposite electrode 34 and the protruding portions of the one opposite electrode 34 are alternately arranged with the protruding portions of the other opposite electrode 34. Each conductive contact 22 is an example of a switch element and each pair of opposite electrodes 34 is an example of a pair of switch electrodes.

Each of the terminals 33 and the opposite electrodes 34 has a surface plated with gold. Thereby, electric resistances of the surfaces can be reduced and the surfaces can be restricted from rusting. Thus, the pair of terminals 33 and the four pair of the opposite electrodes 34 can keep low electric resistances of the surfaces thereof.

The circuit unit 30 is molded with a resin member 35 in such a manner that the whole circuit section 32 is covered with the resin member 35, and the pair of terminals 33 and the four pair of opposite electrodes 34 are exposed to an outside of the resin member 35. The resin member 35 is made of epoxy resin, for example.

For example, as illustrated by the shaded area in FIG. 5A and FIG. 5B, the resin member 35 covers an area of the first surface 311 other than an area having a shape corresponding to a shape of the button battery 41 and including the pair of terminals 33. In addition, the resin member 35 covers the whole side surface 313 of the printed circuit board 31.

The whole second surface 312 of the printed circuit board 31 is not covered with the resin member 35. Thus, when the circuit section 32 including the electronic elements is molded with resin, the second surface 312, on which the electronic elements are not mounted, can closely come in contact with an inner surface of a cavity of a molding tool. Thereby, even if resin is filled into the cavity with a high pressure, the printed circuit board 31 is difficult to be warped and the resin member 35 can be firmly attached to the circuit section 32.

In the circuit unit 30, the pair of terminals 33 and the four pairs of the opposite electrodes 34 are exposed to the outside of the resin member 35 and the circuit section 32 including the electronic elements is covered with the resin member 35. Thus, the circuit section 32 can have a waterproof property without a waterproof cover including a ring-shaped part. As a result, a dimension of the case body of the portable device 1 can be reduced.

The resin member 35 covers the side surface 313 in addition to the area of the first surface 311 where the circuit section 32 is provided. Thus, an adhesion of the resin member 35 with the printed circuit board 31 can be improved.

As described above, each opposite electrode 34 has a plurality of protruding portions. In each pair of opposite electrodes 34, one opposite electrode 34 is separated from the other opposite electrode 34 and the protruding portions of the one opposite electrode 34 are alternately arranged with the protruding portions of the other opposite electrode 34. In accordance with an operation of one of the knob pieces 21, the corresponding conductive contact 22 comes in contact with and separates from the corresponding pair of opposite electrodes 34. Thereby the electric switching can be controlled with a high degree of certainty.

The conductive contacts 22 are integrally formed with the surfaces of the knob pieces 21 on the printed circuit board side. Thus, when one of the knob pieces 21 is operated, the corresponding conductive contact 22 comes in contact with and separates from the corresponding pair of opposite electrodes 34 with a high degree of certainty.

The knob sheet 20 has a planar shape similar to a planar shape of the circuit unit 30 and is disposed in the front case 10 along an inner surface of the front case 10. The elastomer layer 51 is integrally formed with the rear case 50 so as to cover the whole outer surface of the rear case 50. The circuit unit 30 can be protected from a vibration and a drop impact by the knob sheet 20 and the elastomer layer 51 made of elastic sheets.

Because the knob sheet 20 is held between the front case 10 and the circuit unit 30, the knob sheet 20 is difficult to get out of position. In addition, because the elastomer layer 51 is integrally formed with the rear case 50, the elastomer layer 51 does not get out position with respect to the rear case 50.

Although the present invention has been fully described in connection with the exemplary embodiments thereof with reference to the accompanying drawings, it is to be noted that various changes and modifications will become apparent to those skilled in the art.

In the above-described exemplary embodiment, resin is filled into the cavity of the molding tool and is solidified under pressure so that the resin member 35 covers the circuit section 32. Alternatively, the resin member 35 may be formed by potting. In the present case, a frame body is disposed to surround the circuit section 32, and then resin is filled into the frame body and is solidified without applying pressure.

The resin member 35 may be made of polyurethane resin, for example, without being limited to epoxy resin.

The conductive contacts 22 may be made of various conductive materials without being limited to carbon. For example, the conductive contacts 22 may be made of metal.

In the above-described exemplary embodiment, each opposite electrode 34 has the pectinate shapes, as an example. Alternatively, each opposite electrode 34 may have other shape. Also in the present case, in each pair of opposite electrodes 34, one opposite electrode 34 is arranged to oppose the other opposite electrode 34.

In the above-described exemplary embodiment, the circuit unit 30 is protected by elastic sheets including the knob sheet

5

disposed along the inner surface of the front case 10 and the elastomer layer 51 integrally formed at an outer surface of the rear case 50. Alternatively, the elastic sheet may be disposed one of an inner surface and an outer surface of the case body. For example, the elastic sheet may be disposed along the inner surface of the case body on both sides of the circuit unit 30.

The portable device 1 is not limited to the portable electronic key (i.e., smart key) as illustrated in FIG. 1. Alternatively, the portable device 1 may be other device that can transmit a signal to an external device. For example, the portable device 1 may be a keyless transmitter for a keyless entry system.

Such changes and modifications are to be understood as being within the scope of the present invention as defined by the appended claims.

What is claimed is:

1. A portable device comprising:

a case body;

an operating part disposed in the case body;

a circuit board housed in the case body and having a circuit section, the circuit section including an electronic element mounted on the circuit board, and the circuit section configured to transmit a signal to an external device;

a battery holder disposed on the circuit board and configured to house a button battery;

a terminal electrode disposed on the circuit board for supplying electricity from the button battery to the circuit section;

a pair of switch electrodes disposed on the circuit board; a switch element configured to electrically couple the pair of switch electrodes in accordance with an operation of the operating part; and

a resin member disposed on the circuit board in such a manner that the circuit section is covered with the resin member, whereas the battery holder, the terminal electrode and the pair of switch electrodes are not covered with the resin member and are exposed to an outside of the resin member, wherein

the battery holder is a distinct and separate component from the resin member.

2. The portable device according to claim 1, wherein: the circuit board has a first surface and a second surface opposing the first surface;

the electronic element is mounted on the first surface; the first surface is covered with the resin member; and the second surface is exposed to the outside of the resin member.

3. The portable device according to claim 2, wherein: the circuit board further has a side surface extending from a peripheral edge of the first surface to a peripheral edge of the second surface; and

the resin member covers the first surface and the side surface.

6

4. The portable device according to claim 1, wherein each of the terminal electrode and the pair of switch electrodes has a surface plated with gold.

5. The portable device according to claim 1, wherein: one of the switch electrodes is separated from the other switch electrode;

the switch element is made of conductive material; and the switch element is capable of coming in contact with and separating from the pair of switch electrodes.

6. The portable device according to claim 5, wherein: each of the switch electrodes has a plurality of protruding portions; and

the plurality of protruding portions of the one switch electrode is alternately arranged with the plurality of protruding portions of the other switch electrode.

7. The portable device according to claim 5, wherein: the operating part is made of a flexible sheet; and the switch element is integrally disposed on a surface of the flexible sheet opposed to the circuit board.

8. The portable device according to claim 1, further comprising an elastic sheet disposed on one of an inner surface and an outer surface of the case body.

9. The portable device according to claim 8, wherein the elastic sheet is integrally formed with the case body.

10. The portable device according to claim 1, wherein the external device is disposed in a vehicle.

11. The portable device according to claim 1, wherein there are a plurality of operating parts, and the case body includes a front case and a rear case, the front case having a plurality of opening portions, each corresponding to a respective said operating part.

12. The portable device according to claim 11, wherein said operating parts are carried by a support member sheet disposed within said case body, adjacent the front case.

13. The portable device according to claim 1, wherein the support member sheet is held between the front case and the circuit unit.

14. The portable device according to claim 1, wherein an elastomer layer is integrally formed with the rear case so as to cover an entire outer surface of the rear case.

15. The portable device according to claim 1, wherein the battery holder is disposed adjacent one longitudinal end of the circuit board and said circuit section is longitudinally spaced from the battery holder, so that the circuit section is disposed next to a portion of the circuit board on which the battery holder is disposed.

16. The portable device according to claim 1, wherein the resin member covers an area of a first surface of the circuit board other than an area having a shape corresponding to a shape of the button battery and the resin member covers an entire side surface of the printed circuit board, whereas an entire second surface of the printed circuit board, opposite said first surface, is not covered with the resin member.

* * * * *