
Patents Act 1990

PATENT REQUEST : STANDARD PATENT

I/We, being the person/s identified below as the Applicant, request the grant of a patent to the person/s indicated below as the Nominated Person/s, for an invention described in the accompanying standard complete specification.

Full application details follow.

[71] [70] Applicant/s and Nominated Person/s:
Alain Buffet,
of 81 Rue Gabriel Peri, F-54110 VARANGEVILLE, FRANCE

[54] Invention Title:
Filter mounting frame for eyeglasses

[72] Name/s of actual inventor/s: (optional)

[74] Address for service in Australia:
DAVIES COLLISON CAVE, Patent Attorneys
10 Barrack Street, SYDNEY NSW 2000

Attorney Code : CA

BASIC CONVENTION APPLICATION/S DETAILS:

[31] Appln No.:
92 07 314

[33] Country:
FRANCE

Code:
FR

[32] Date:
12 June 1992

Drawing number recommended to accompany the abstract:

DATED this SECOND day of JUNE 1993

Alain Buffet
By Patent Attorneys
DAVIES COLLISON CAVE

Peter Stearne

Dr. PETER STEARNE, FIPAA

Fee: \$ 165.00

S 037976 020693

5010


AUSTRALIA
PATENTS ACT 1990
NOTICE OF ENTITLEMENT

I, ALAIN BUFFET, the applicant in respect of Application No. 39997/93 state the following:-

The Nominated Person is the actual inventor.

The Nominated Person is the applicant of the basic application listed on the patent request form.

DATED this 2nd day of November, 1994.



.....

a member of the firm of
DAVIES COLLISON CAVE
for and on behalf of the
applicant



AU9339997

(12) PATENT ABRIDGMENT (11) Document No. **AU-B-39997/93**
(19) AUSTRALIAN PATENT OFFICE (10) Acceptance No. **656268**

- (54) Title
FILTER MOUNTING FRAME FOR EYEGLASSES
- International Patent Classification(s)
(51)⁵ **G02C 007/10 G02C 009/02**
- (21) Application No. : **39997/93** (22) Application Date : **02.06.93**
- (30) Priority Data
- (31) Number (32) Date (33) Country
92 07314 12.06.92 FR FRANCE
- (43) Publication Date : **16.12.93**
- (44) Publication Date of Accepted Application : **27.01.95**
- (71) Applicant(s)
ALAIN BUFFET
- (72) Inventor(s)
ALAIN BUFFET
- (74) Attorney or Agent
DAVIES COLLISON CAVE , GPO Box 3876, SYDNEY NSW 2001
- (56) Prior Art Documents
FR 2537292
DE 2458107
AU 20026/29 87.6
- (57) Claim

1. A mounting frame for eyeglass filters whose filtering properties are distributed asymmetrically over their surface, comprising a pair of mounting seats, each comprising a pair of nested annular elements having an inwardly directed channel-shaped cross section; a filter lens mounted in an inner said annular element of each said mounting seat; manipulating means for angularly orienting each lens in its associated mounting seat, each said manipulating means comprising a slidable detent member extending transversely through the inner annular element and engageable in locating holes formed in the associated outer annular element; biasing means for resiliently urging said detent member into engagement with said locating holes; and gripping means protruding through a slot in the wall of the outer annular member to permit manual disengagement of said detent member against the action of said biasing means.

Our Ref: 471744

P/00/011
Regulation 3:2

AUSTRALIA

Patents Act 1990

656268

ORIGINAL
COMPLETE SPECIFICATION
STANDARD PATENT

Applicant(s):

Alain Buffet
81 Rue Gabriel Peri
F-54110 VARANGEVILLE
FRANCE

Address for Service:

DAVIES COLLISON CAVE
Patent & Trade Mark Attorneys
Level 10, 10 Barrack Street
SYDNEY NSW 2000

Invention Title:

Filter mounting frame for eyeglasses

The following statement is a full description of this invention, including the best method of performing it known to me:-

The present invention relates to eyeglasses, and more particularly to a mounting frame for eyeglass filter lenses whose filtering properties are distributed asymmetrically over their surface. The mounting frame comprises
5 manipulating means for angularly orienting each filter lens in a mounting seat.

One type of mounting frame for eyeglasses has already been proposed in which the filter lenses can be oriented in accordance with the field of view to be obscured. Eyeglasses with orientable filter lenses having filtering properties distributed asymmetrically over their surface are intended particularly for car drivers to protect them from being dazzled by the sun during the day and the headlights of vehicles moving in the opposite direction at night. Such
15 mounting frames are described in FR A 2 341 147. The disadvantage of the proposal in this document stems from the complexity of the device which results in an expensive
.. article of little aesthetic value.

The object of the present invention is to overcome, at least in part, the above mentioned disadvantages.

Accordingly, the present invention provides a mounting frame for eyeglass filters whose filtering properties are distributed asymmetrically over their surface, comprising a pair of mounting seats, each comprising a pair of nested
25 annular elements having an inwardly directed channel-shaped cross section, a filter lens mounted in an inner said annular element of each said mounting seat, manipulating means for angularly orienting each lens in its associated mounting seat, each said manipulating means comprising a
30 slidable detent member extending transversely through the inner annular element and engageable in locating holes formed in the associated outer annular element, biasing means for resiliently urging said detent member into

engagement with said locating holes, and gripping means protruding through a slot in the wall of the outer annular member to permit manual disengagement of said detent member against the action of said biasing means.

5 Preferably, each mounting seat comprises two annular elements, shaped in the form of a prone U whose opening is directed toward the center of said nested annular elements, the annular space of the inner nested annular element receiving a filter lens and carrying the manipulating means which has a gripping member integral with one end of a rod extending perpendicularly to the plane of the annular elements. The resilient means comprises a spring urging the other end of the rod against the internal face of one of the parallel limbs of the portion of the external annular
15 element which has the positioning openings for locating the end of the rod.

... The attached drawing illustrates, schematically and by way of example, one embodiment of the mounting frame for eyeglass filters in accordance with the invention.

20 Figure 1 is a front elevation of the mounting frame for eyeglass filters;

... Figure 2 is a partial sectional view taken along line II-II of Figure 1; and

25 Figure 3 is a perspective view of the mounting frame with the filters raised.

... The mounting frame for eyeglass filters according to the invention comprises two annular mounting seats 1, 1' for two filter lenses 2, 2' attached to a common rod 3 connected to the rest of the mounting frame 4 by two hinges 5, 5'.

30 The mounting frame further comprises two arms 6, 6' and two

pads 7, 7' for resting on the sides of the nose. As shown in Figure 1, the filter lenses 2, 2' are completely transparent over one-half of their circular surface bounded by a line extending substantially diametrically, while the other half displays filtering properties for light rays, preferably filtering properties exhibiting a gradient from the center towards the periphery where the degree of filtration is more pronounced. Of course, tinted lenses can also be employed so that the transparent half of the lens can be lightly tinted, the other half having more pronounced filtering properties.

Each annular mounting seat 1, 1' comprises two nested rings 8, 9 (Figure 2) having a prone U-shaped section whose opening is directed to the center of the annular seat, contained one within the other. The outer ring 8 is split at 10 such that the two ends of the split can be elastically drawn apart to permit the introduction of the inner ring 9 which is contained in its annular opening. Each end of the outer ring 8 adjacent to the split 10 is integral with the sleeve 11, 12. The two sleeves are tangential to the outer ring 8 so that they are coaxial when the ends of the split are reunited, which permits them to be fitted onto the rod 3 to which they are fixed by screws 13.

The ring 8' includes a tube 14 attached radially along an axis parallel to the rod 3. The ring 8 carries a piston fixed radially coaxially to the tube 14 in which it is engaged. Thus, the two annular mounting seats 1, 1' are integral and able to articulate about hinges 5, 5'. A tongue 16 is fixed to one of the outer rings 8' to permit rotation of the annular seats about the hinges 5, 5'.

As illustrated in Figure 2, the filter lens is mounted in the annular opening of the inner ring 9. The lens 2 has a cut-out 2a formed in its periphery (Figure 1 and 2), in

which is mounted an actuator device comprising a molded member 17 having a shape complementary to that of the cut-out 2a. This molded member 17 is engaged in the annular opening of the inner ring 9. A cylindrical recess 18 is formed in one of the plane faces of this molded member 17 and the base of this recess is open. A spring 19 and a piston 20 integral with a rod 21 are located in this recess 18. One end of the rod 21 passes through the opening in the base of the recess 18. This end is threaded and a gripping member 22 is screwed onto it. The other end of the rod is engaged in one of the positioning holes 23 formed through one of the parallel limbs of the outer profiled ring 8. A slot 24 extending over half of the circumference of the ring 8 is formed in the other of the parallel limbs of the outer profile ring 8, opposite the part having positioning holes 23. This slot 24 permits the angular displacement of the rod 21 and the gripping member 22 when the end of rod 21 is disengaged from the positioning opening 23 by pulling axially on the rod with the aid of the gripping member 22 against the pressure that the spring 19 exerts on the piston 20. By displacing the gripping member 22 angularly after disengaging the rod 21 from the positioning opening 23, the ring 9 is displaced angularly in the ring 8 and consequently so is the lens 2 which, by means of its cut-out 2a, is angularly fixed relative to the molded member 17 and the rod 21. This permits the displacement of the filtering zone of the lens 2. The same operation can orient angularly the filtering zone of the lens 2 which is supplied with the same manipulating means as those illustrated in Figure 2.

In the example illustrated, three positions 90° apart are provided. In particular, this permits the filtering zones to be located to the left of the visual axis of the user to avoid being dazzled from the left of his field of view. This is particularly useful for drivers traveling in countries that drive on the right of the road relative to

the forward direction of vehicles. By displacing the lens 2, 2' 90° relative to the previous position counterclockwise, referring to Figure 1, a filtering zone can be brought into the upper part of the field of view of the user, which provides protection against sun rays. Finally, the third position is intended in particular to protect against dazzling from the right of the field of view, and is particularly useful for drivers traveling in countries where vehicles move on the left of the road relative to the forward direction.

The lenses are preferably mounted on mounting frame 4 by a system of hinges 5, 5' and are made integral about the pivot axis of these hinges by means of piston 15 engaged in tube 14. By grabbing the tongue 16, it is thus possible to lift up the annular mounting seats 1, 1' into the position shown in Figure 1. This is useful particularly if filters are mounted on a pair of eyeglasses provided with optical correction lenses, such that the filters can be removed from the field of view when the user does not require them.

It is further pointed out that the mounting of the annular mountings 1, 1' on the rod 3 through the intermediary of sleeves 11, 12, 11', 12' and their fixing on the screws 13 permits the changing at will of the separation of the lenses 2, 2' and consequently the pupillary separation by gliding the annular mountings 1, 1' on the rod 3. In this case, the piston 15 of the mounting 1 also slides in the tube 14 of the mounting 1'.

The Claims defining the invention are as follows:

1. A mounting frame for eyeglass filters whose filtering properties are distributed asymmetrically over their surface, comprising a pair of mounting seats, each comprising a pair of nested annular elements having an inwardly directed channel-shaped cross section; a filter lens mounted in an inner said annular element of each said mounting seat; manipulating means for angularly orienting each lens in its associated mounting seat, each said manipulating means comprising a slidable detent member extending transversely through the inner annular element and engageable in locating holes formed in the associated outer annular element; biasing means for resiliently urging said detent member into engagement with said locating holes; and gripping means protruding through a slot in the wall of the outer annular member to permit manual disengagement of said detent member against the action of said biasing means.

2. A mounting frame as claimed in claim 1, wherein the outer annular nested element of each mounting seat is split to permit the separation of its two ends for the insertion of the inner annular nested element, each of the ends of the split annular nested element being attached by a connecting element to a support member.

3. A mounting frame as claimed in claim 2, wherein said support member is connected to the rest of the mounting frame by articulation means permitting the displacement of the mounting seats away from their position of use.

4. A mounting frame as claimed in claim 3, wherein the two mounting seats for the respective filter lenses have interconnecting means for rigidly connecting them together with respect to rotation about the axis of said articulation means.

5. A mounting frame as claimed in claim 1, wherein each filter lens has a peripheral recess in which are located the said manipulating means.

6. *A mounting frame as claimed in claim 2*
wherein each said connecting element comprises a tube whose wall is traversed by at least one fixing screw, said tube being engageable on a rod providing said support member, and said at least one fixing screw permitting the locking of said tubes along said rod and permitting the regulation at will of the separation between said mounting seats.

7. A mounting frame as claimed in claim 1, wherein said detent member comprises a rod extending through a molded block located within said inner nested annular element, and said block has a recess formed around said rod accommodating said biasing means.

8. A mounting frame for eyeglass filters substantially as herein described with reference to the accompanying drawings.

DATED this 2nd day of June 1993,

ALAIN BUFFET

By His Patent Attorney

DAVIES COLLISON CAVE



ABSTRACT OF THE DISCLOSURE

In a pair of eyeglasses with filter lenses, each filter is mounted in a ring shaped in the form of a prone U whose opening is directed toward the center of the ring. The ring is contained within an outer ring connected to the eyeglasses mounting frame. A manipulating device comprising a molded member is located inside the ring in a recess formed in the periphery of the filter lens. The outer ring has a semicircular slot permitting the angular displacement of a positioning rod, which is integral with a piston slidably mounted in a recess against the action of a spring. One end of the rod is integral with a gripping member, while the other end is engageable in one of the positioning openings formed through one limb of the shaped outer ring.

