



Office de la Propriété

Intellectuelle
du Canada

Un organisme
d'Industrie Canada

Canadian
Intellectual Property
Office

An agency of
Industry Canada

CA 2352880 C 2008/01/29

(11)(21) **2 352 880**

(12) **BREVET CANADIEN
CANADIAN PATENT**

(13) **C**

(86) Date de dépôt PCT/PCT Filing Date: 1999/11/22
(87) Date publication PCT/PCT Publication Date: 2000/06/08
(45) Date de délivrance/Issue Date: 2008/01/29
(85) Entrée phase nationale/National Entry: 2001/05/29
(86) N° demande PCT/PCT Application No.: US 1999/028204
(87) N° publication PCT/PCT Publication No.: 2000/032296
(30) Priorités/Priorities: 1998/11/30 (US60/110,229);
1999/06/04 (US60/137,497)

(51) Cl.Int./Int.Cl. *B01D 46/12*(2006.01),
A61B 18/00(2006.01), *A61M 13/00*(2006.01),
B01D 39/16(2006.01), *B01D 71/36*(2006.01)


(72) Inventeur/Inventor:
BOOTH, CHARLES S., US

(73) Propriétaire/Owner:
PALL CORPORATION, US

(74) Agent: MARKS & CLERK

(54) Titre : FILTRE DESTINE A ETRE UTILISE POUR DES ACTES MEDICAUX

(54) Title: FILTER FOR USE IN MEDICAL PROCEDURES



(57) Abrégé/Abstract:

A filter device (300) for use in medical procedures such as laparoscopy is disclosed. Preferably, the device (300) comprises a filter arrangement (200) and a filter housing (50) having first and second side walls (5, 55), wherein at least a portion of each of the first and second side walls is flexible and porous.


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : B01D 46/12		A2	(11) International Publication Number: WO 00/32296
			(43) International Publication Date: 8 June 2000 (08.06.00)
(21) International Application Number:	PCT/US99/28204	(81) Designated States:	AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
(22) International Filing Date:	22 November 1999 (22.11.99)		
(30) Priority Data:			
60/110,229	30 November 1998 (30.11.98)	US	
60/137,497	4 June 1999 (04.06.99)	US	
(71) Applicant (for all designated States except US):	PALL CORPORATION [US/US]; 2200 Northern Boulevard, East Hills, NY 11548-1209 (US).		
(72) Inventor; and		Published	
(75) Inventor/Applicant (for US only):	BOOTH, Charles, S. [US/US]; 11221 Haller, Livonia, MI 48150 (US).		Without international search report and to be republished upon receipt of that report.
(74) Agent:	JAY, Jeremy, M.; Leydig, Voit & Mayer, Ltd., 700 Thirteenth Street, Suite 300, Washington, DC 20005 (US).		

(54) Title: FILTER FOR USE IN MEDICAL PROCEDURES



(57) Abstract

A filter device (300) for use in medical procedures such as laparoscopy is disclosed. Preferably, the device (300) comprises a filter arrangement (200) and a filter housing (50) having first and second side walls (5, 55), wherein at least a portion of each of the first and second side walls is flexible and porous.

FILTER FOR USE IN MEDICAL PROCEDURES

5

TECHNICAL FIELD

This invention relates to a filter for use in medical 10 procedures, more particularly, for use in laparoscopic or endoscopic surgery.

BACKGROUND OF THE INVENTION

During some medical procedures, e.g., laparoscopic and 15 endoscopic surgery, a suitable gas is introduced into the abdominal cavity to inflate the abdomen. The inflation of the abdomen tends to separate the interior organs and to provide an enlarged cavity within which to perform the surgery. For example, one or more trocars can be used to 20 puncture the abdomen, and insufflation gas can be passed through at least one of the trocar(s) to inflate the abdomen. One or more instruments involved in the surgery, e.g., a laparoscope, scalpel, laser and/or electrocautery device, can be inserted through the appropriate trocar(s) as needed.

25 When a particular procedure requires cutting of tissues and/or blood vessels, lasers, ultrasonic tissue fragmentation devices and electrocautery devices can be used as they are easily manipulated, and produce relatively clean cuts. Moreover, they have a cauterizing effect, thus limiting 30 bleeding.

Once surgery is completed, the gas used to inflate the cavity is vented from the abdominal cavity. Additionally, since cutting with lasers, ultrasonic tissue fragmentation devices and electrocautery devices often produces vapor or 35 "smoke," that can cloud or obstruct the surgeon's view of the operative site, the surgeon may vent gas (including smoke) during the surgery to remove the smoke from the abdominal

cavity. For example, the surgeon may release a valve associated with a cannula communicating with one of the trocars and vent the smoke to the surrounding atmosphere. Alternatively, the smoke can be recirculated, e.g., withdrawn 5 from one trocar and reintroduced into the abdominal cavity through another trocar.

However, the smoke can contain toxic, odiferous, and otherwise undesirable material (e.g., benzene, hydrogen cyanide, toluene, formaldehyde, carbon monoxide, viruses, 10 bacteria, cells, and/or body fluids from diseased tissue of the patient) that, if released into the environment of the operating room, could expose the surgeon and the surgeon's staff to a health risk. Additionally, the release or recirculation of this smoke (that can, for example, contain 15 bacteria and/or viruses) can subject the patient to the risk of additional contamination, e.g., via absorption through the peritoneum, or by entering the body at a location other than the abdominal cavity.

Attempts have been made to filter some of the gas passed 20 from the abdominal cavity of the patient. However, these filters have suffered from a number of drawbacks. For example, some of the filters are bulky, and interfere with the surgeon's vision and/or the surgeon's ability to move in and around the surgical site. The filters may be easily 25 plugged, fail to remove sufficient undesirable material and/or may require a labor intensive effort (possibly requiring numerous steps) to operate. Special equipment (e.g., instruments, valves and/or evacuators) may have to be utilized with the filters. Alternatively, or additionally, 30 the filters may be unsuitable for use with adjustable gas flow rates and/or gas flow rates of about 1 liter/min or more at standard insufflation pressure.

The present invention provides for ameliorating at least some of the disadvantages of the prior art. These and other 35 advantages of the present invention will be apparent from the description as set forth below.

19-02-2001

US 009928204

2A

D1 (U.S. Patent No. 5,108,474) discloses a smoke filter that is hermetically sealed into a housing or canister. The filter is utilized in a conventional vacuum system, and the filter is placed in the outlet of the smoke filter housing.

5 D2 (U.S. Patent No. 4,561,868) discloses a canister filter assembly for use in a vacuum line for trapping particulates and liquids from fluid drawn through the vacuum line including a cupped shaped container portion and a lid portion disposed over the container in sealing engagement
10 therewith.

D3 (U.S. Patent No. 5,507,847) discloses an improved filter unit suitable for use in a variety of clean air filtration applications.

15 D4 (International Publication No. WO 98/31451, corresponding to EP 0,960,644 A1), discloses a filter medium by use of which a long-life compact air cleaning system having a function of removing floating fine particles from the air, and a function of decomposing organisms for deodorizing and antibacterial effects is provided.

20 D5 (U.S. Patent No. 4,487,606) discloses a suction canister assembly comprising an enclosed receptacle having a first opening for providing suction to the receptacle and a second opening for drawing fluids, including liquids and gases, into the receptacle during suction.

25 D6 (U.S. Patent No. 5,647,881) discloses a vacuum cleaner bag with high fine particle removal efficiency under normal and shock loading conditions, shock loading including a short term challenge with high particle concentrations (e.g., when a vacuum is used to pick up a pile of debris).

30 D7 (DE 196,06,718 A1) discloses a multi-layer bag filter with a filter bag and a securing plate, especially for a vacuum cleaner.

35 D8 (U.S. Patent No. 4,894,074) discloses a filter consisting of hollow cylindrical open-pore ceramic foam cylinder elements and an end plate made of gas-impermeable material, as an insert in a filter cup for cleaning exhaust gases of diesel engines, in which the exhaust gases flow

19-02-2001

US 009928204

2B

through the active filter section essentially perpendicularly to the cylinder axis.

D9 (U.S. Patent No. 5,205,850) discloses a particulate filter including a housing having opposite ends, a pair of support walls adjacent respective opposite ends of the housing and defining therein an interior, and a pair of pure gas chambers defined at respective opposite ends of the housing at sides of the respective support walls outwardly of the interior.

SUMMARY OF THE INVENTION

In accordance with an embodiment of the instant invention, a filter device for gas(es), preferably gas vented from a patient's body cavity (e.g., during laparoscopic surgery) is provided comprising at least one flexible filter comprising a flexible filter element, wherein the filter device is arranged to allow gas to pass therethrough. For example, a surface of the flexible filter can provide a wall or side of the filter device, wherein gas passes from one surface of the flexible filter, through the filter, and through an opposing surface of the filter, wherein a wall or side of the filter device comprises the opposing surface of the filter.

In some embodiments, the filter device comprises a housing and at least one filter element, wherein at least a portion of the housing is flexible and allows gas to pass therethrough, the filter device being arranged to allow gas to pass through the filter element(s) and the flexible portion of the housing.

In another embodiment, the filter device comprises a housing and at least one filter element, wherein the filter element has an effective filtration area of at least about 12.9 cm² (at least about 2 in²), the filter device being arranged to allow gas to pass through the filter element(s) and through a portion of the housing.

In some embodiments, at least a portion of the housing and/or the filter element is flexible. In other embodiments, the housing and the filter element are substantially inflexible.

In preferred embodiments, the filter device removes laparoscopic smoke and reduces odor as the gas passes through the device to the exterior of the housing.

Embodiments of the filter and filter device are suitable for use at any desirable constant or variable gas flow rate. Preferably, the filter device can be easily added to any suitable system (e.g., a system for use in laparoscopic surgery). In an embodiment, the filter device (that can be

part of a set) allows one-handed gas flow adjustment.

Embodiments of the invention are particularly for use in surgical environments, especially for use in laparoscopic surgery, as they can allow the surgical procedure to be completed more quickly and/or cost efficiently, e.g., by reducing the amount of valuable surgeon-, nurse-, technician- and/or operating room-time needed for the procedure. Time savings are particularly advantageous, since, for example, as of 1999, at least one study has estimated the value of time in the operating room during laparoscopic surgery as well over \$120 per minute.

In accordance with the invention, a gas filter (preferably a smoke filter) comprises a retentive member, i.e., it retains at least one undesirable material such as at least one of microorganisms (e.g., bacteria), viruses, cells, body fluids, aerosols and liquid droplets, and allows at least a portion of the gas to pass through the retentive member, wherein the gas is depleted of at least some level of the undesirable material(s). The retentive member may also retain or reduce the passage therethrough of other undesirable material such as at least one of benzene, hydrogen cyanide, formaldehyde, and toluene, and/or the member may reduce the passage of odor therethrough. The smoke filter comprises at least one porous substrate of any suitable nature, e.g., a porous medium such as a fibrous web, a membrane, combinations thereof, and the like. Typically, at least a portion of the smoke filter is flexible.

Typically, the gas filter comprises at least one smoke filter element comprising a porous retentive substrate, preferably a porous retentive medium. The porous substrate can have any suitable physical dimensions and typically will be in sheet form having two opposing sides (e.g., a first side and an opposing second side) with a central portion therebetween, wherein the pores in the porous substrate will generally enable fluid communication between the first and second sides of the porous substrate. Typically, the gas filter comprises a smoke filter element comprising at least

one hydrophobic membrane (preferably a hydrophobic microporous membrane) and/or at least one hydrophobic fibrous medium, through which the fluid (e.g., gas) to be treated passes. The element has two opposing sides (e.g., a first 5 side and an opposing second side, in relation to a fluid to be treated wherein at least a portion of the gas is passed through the element), with a central portion therebetween. The pores in the element generally enable fluid communication between the two opposing sides (e.g., between the first and 10 second sides) of the element.

The smoke filter can have any suitable pore structure, for example, a Dioctyl Phthalate (DOP) smoke penetration rating, or a pore rating (e.g., ability to remove particles of a given size to a specified degree, as evidenced, for 15 example, by bubble point). The smoke filter can have a pore structure that is uniform, substantially uniform, or it can vary in a continuous, a discontinuous, or a stepwise manner. For example, the smoke filter can have a graded pore structure. In some embodiments, the smoke filter includes a 20 plurality of elements and/or layers wherein individual elements and/or layers have different pore structures, e.g., different pore ratings. For example, the smoke filter can comprise a smoke filter element having a plurality of layers wherein at least two layers have different pore ratings.

25 The smoke filter can include additional elements, layers, or structures, which can also be membranes, or other porous media. For example, in some embodiments, the smoke filter can include additional components that have different structures and/or functions, e.g., at least one of prefiltration, odor-reduction, support, drainage, spacing and 30 cushioning. In some embodiments wherein the smoke filter includes one or more additional elements, at least a portion of each of the additional elements is flexible.

As used herein, the term "smoke" includes gas (e.g., the 35 insufflation gas), as well as some of the material and/or some of the by-products produced by the ablation of tissues and/or blood vessels (e.g., aerosols and droplets). Smoke

can include additional material, such as at least one of bacteria and viruses.

BRIEF DESCRIPTION OF THE DRAWINGS

5 Figure 1 is a perspective view of an embodiment of an assembled smoke filter device.

Figure 2 is an exploded view of an embodiment of a smoke filter device including a smoke filter arrangement according to the present invention.

10 Figure 3 is a cross-sectional view of the embodiment illustrated in Figure 1, along line 3-3, including the smoke filter arrangement illustrated in Figure 2.

Figure 4 is an exploded view of another embodiment of a smoke filter device including a smoke filter arrangement

15 according to the present invention.

Figure 5 is an exploded view of another embodiment of a smoke filter device including a smoke filter arrangement according to the present invention.

Figure 6 is a cross-sectional view of another embodiment

20 of a smoke filter device according to the invention wherein the device does not include a housing, and a portion of the first side wall of the device comprises a surface of the first smoke filter, and a portion of the second side wall of the device comprises a surface of the second smoke filter.

25 Figure 7 is a top view (Figure 7a) and a cross-sectional view (Figure 7b, along line 7b-7b of Figure 7a) of another embodiment of an assembled smoke filter device wherein the device includes a manifold including an inlet port.

30 SPECIFIC DESCRIPTION OF THE INVENTION

In accordance with an embodiment of the present invention, a gas filter device is provided comprising a gas filter adapted to filter smoke, the gas filter having a first surface and an opposing second surface, the device having at

35 least one wall (typically a side wall) comprising at least a portion of the second surface of the gas filter, wherein at least the portion of the wall allows gas to pass

therethrough, the gas filter comprising at least one porous filter element comprising a hydrophobic retentive member, wherein the gas filter device is arranged to allow gas to pass through the filter and through the portion of the wall.

5 In some embodiments, at least a portion of the wall is flexible, and the filter device is arranged to allow gas to pass through the filter and through the flexible portion of the wall.

In an embodiment of the gas filter device, the gas filter comprises at least two gas filters (preferably at least two smoke filters), the first and second gas filters each having a first surface and an opposing second surface, the device having at least two side walls, the first side wall comprising at least a portion of the second surface of the first gas filter, the second side wall comprising at least a portion of the second surface of the second gas filter, wherein the gas filter device is arranged to allow gas to pass through the filters and through the portions of the side walls.

20 In accordance with an embodiment of the present invention, a gas filter device is provided comprising a filter housing having an interior cavity, the housing having at least one wall, wherein at least a portion of the wall allows gas to pass therethrough, and a gas filter capable of filtering smoke comprising at least one porous filter element, wherein the filter element comprises a hydrophobic retentive member, and the gas filter device is arranged to allow gas to pass through the smoke filter and through the portion of the wall of the housing. In one embodiment, the filter element has an effective filtration area of at least about 12.9 cm² (about 2 in²). Preferably, the hydrophobic retentive member comprises a microorganism- and/or virus-retentive member. In one preferred embodiment, the filter housing has at least one side wall substantially comprising a non-woven medium that allows gas to pass therethrough.

In an embodiment, a smoke filter device comprises a

smoke filter comprising at least one porous filter element comprising a hydrophobic retentive member, the filter element having an effective filtration area of at least about 12.9 cm² (about 2 in²), wherein the smoke filter device is capable of

5 filtering smoke for at least about 3 minutes of cumulative smoke with a reduction of gas flow of about 50% or less. The filter element can include at least a portion that is flexible. In another embodiment, the filter element is substantially inflexible.

10 Typically, the gas filter comprises a smoke filter including at least one additional element such as a prefilter element and/or an odor-reducing element that also allow gas to pass therethrough. In an embodiment, the smoke filter prevents the passage of bacteria therethrough.

15 In some embodiments, the gas filter device comprises a housing having at least first and second side walls, wherein at least a portion of each of the two side walls is flexible, and allows gas to pass therethrough, and at least first and second smoke filters, each smoke filter comprising at least 20 one porous filter element, each porous filter element comprising a hydrophobic retentive member, wherein the device is arranged to allow a portion of gas to pass through the first smoke filter and the first side wall, and to allow a portion of gas to pass through the second smoke filter and 25 the second side wall. In a preferred embodiment, the first and second smoke filters each include at least one additional element such as a prefilter element and/or an odor-reducing element. In some embodiments, the first and second side walls of the filter housing substantially comprise a non-woven 30 medium that allows gas to pass therethrough.

In accordance with another embodiment of the invention, a smoke filter arrangement that allows gas to pass therethrough is provided comprising a first smoke filter, the first smoke filter comprising a first porous element 35 comprising a hydrophobic retentive member, a prefilter element and/or an additional element comprising an odor-reducing medium; and a second smoke filter, the second

smoke filter comprising a second porous filter element comprising a hydrophobic retentive member, a prefilter element and/or an additional element comprising an odor-reducing medium. In an embodiment, the retentive member 5 also comprises a prefilter element, and the smoke filter(s) comprise a porous element comprising a hydrophobic retentive member/prefilter and an additional element comprising an odor-reducing medium.

In accordance with another embodiment of the invention, 10 a smoke filter arrangement that allows gas to pass therethrough is provided comprising a first smoke filter, the first smoke filter comprising a first porous element comprising a hydrophobic retentive member; and a second smoke filter, the second smoke filter comprising a second porous filter element comprising a hydrophobic retentive member, 15 wherein the smoke filter arrangement has an effective filtration area of at least about 12.9 cm² (about 2 in²).

In some embodiments, a smoke filter device including the smoke filter arrangement comprises at least a first side wall 20 and a second side wall, at least a portion of the first side wall and the second side being flexible and allowing gas to pass therethrough, wherein at least a portion of the first side wall comprises a surface of the first smoke filter, and wherein at least a portion of the second side wall comprises 25 a surface of the second smoke filter.

Each of the components of the invention will now be described in more detail below, wherein like components have like reference numbers.

Figures 1-5 illustrate a perspective view of an 30 assembled device (Figure 1), an exploded view (Figures 2, 4 and 5) and a cross-sectional view (Figure 3) of embodiments of a filter device according to the invention, wherein the device is arranged to allow gas (e.g., in the form of smoke) to enter the interior of the device, pass through the gas 35 filter(s), and through a portion of the housing of the filter device. Typically, each gas filter (hereinafter referred to as a "smoke filter") includes a plurality of elements that

allow gas to pass therethrough, e.g., a smoke filter element, as well as a prefilter element and/or an odor-reducing element.

In the illustrative embodiments shown in Figures 2-5, 5 the smoke filter device 300 comprises filter housing 50, having first side wall 5, and second side wall 55, wherein at least a portion of each of the first and second side walls is flexible (e.g., pliable) and porous. The filter device 300 includes a filter arrangement 200 comprising a first smoke 10 filter 100 and a second smoke filter 101, typically with a space 90 between the first smoke filter and the second smoke filter. The illustrated filter device also includes an inlet 75 including an inlet port, the filter device being arranged to allow gas to pass through the inlet, into the space 90 15 between the first and second smoke filter 100, 101, wherein a portion of the gas subsequently passes through the first smoke filter 100 and the first side wall 5, and another portion of the gas passes through the second smoke filter 101 and the second side wall 55.

20 In the embodiment illustrated in Figures 7a and 7b, the filter device includes a manifold 700. As shown in Figure 7b in the illustrated embodiment the manifold includes the inlet 75, allowing gas to pass through the manifold and the inlet, and into the space 90 between the first and second smoke 25 filters 100 and 101, wherein a portion of the gas subsequently passes through the first smoke filter 100 and the first side wall 5, and another portion of the gas passes through the second smoke filter 101 and the second side wall 55.

30 The first and second smoke filters 100, 101, each comprise a porous smoke filter element 1, 11 comprising at least one hydrophobic retentive member. Preferably, the hydrophobic retentive member comprises a microorganism and/or virus retentive member. The hydrophobic retentive member 35 typically comprises at least one membrane and/or at least one depth filter. Typically, the smoke filter includes additional elements such as a prefilter element and/or an

odor-reducing element. In the embodiment illustrated in Figures 2 and 3, the first and second smoke filters also include a prefilter element 2, 22, and an odor-reducing element 3, 33, wherein the porous smoke filter element 1, 11 is interposed between the prefilter element 2, 22 and the odor-reducing element 3, 33. Alternatively, or additionally, the hydrophobic retentive member can also provide prefiltration.

Preferably, the smoke filter arrangement 200 is secured to the housing 50. For example, in accordance with the embodiments shown in Figures 3 and 7b, the first smoke filter 100 is sealed to a portion of the first side wall 5, and the second smoke filter 101 is sealed to a portion of the second side wall 55. The embodiment illustrated in Figure 7b also shows portions of the first and second smoke filters sealed to a portion of the manifold 700.

Figures 4 and 5 show other two other embodiments of the filter device 300, wherein the smoke filter includes a porous smoke filter element 1, 11 and an odor-reducing element 3, 33. In the embodiment shown in Figure 4, the odor-reducing element 3, 33 is downstream of the porous smoke filter element 1, 11, and in the embodiment shown in Figure 5, the odor-reducing element is upstream of the porous smoke filter element.

Figure 6 illustrates a cross-sectional view of an embodiment of the filter device wherein the device lacks a housing, and the device is arranged to allow gas to enter the interior of the device, and pass through the gas filters to the exterior of the device.

The smoke filter device 300 can be utilized as part of a set, that can include additional components such as, but not limited to, at least one of a conduit, flow control device, and a connector. Typically, the set comprises a smoke filter device, at least one conduit, and at least one connector.

Figures 1, 2, 4, and 5 illustrate an embodiments of a set 500, comprising the filter device 300, a connector 550, first and second conduits 501, 502, and flow control device 600.

In another embodiment (e.g., as shown in Figure 7a) the set includes at least one connector between the first conduit 501, and the filter device 300. Suitable connectors include, but are not limited to, a universal fitting or coupler such 5 as a luer fitting; a push-on fitting such as a barb type fitting, and the like.

Turning now to the individual components of the smoke filter device according to the embodiments of the invention, these components are compatible with the gas being utilized 10 and, for those protocols that include producing smoke, these components are compatible with the smoke being produced in the protocol (e.g., laparoscopy, endoscopy, thorascopy, obstetrics-gynescopy), and can be produced from a variety of materials. In some embodiments, the components are 15 compatible with one or more disinfection and/or sterilization protocols, including, for example, using ethylene oxide or gamma sterilization.

In those embodiments wherein the device includes a housing, the housing 50 can be of any suitable configuration 20 and size. In a preferred embodiment, the housing is light weight. In an embodiment, the housing can be formed without the use of a mold. The housing can be, for example, generally teardrop shaped, round, oval, square, rectangular, or triangular. In the embodiment shown in Figure 1, the 25 housing 50 has a generally bag-like configuration, with first and second side walls, an open end, and a sealed end, wherein the open end is secured (e.g., sealed) to the inlet. In the embodiment shown in Figure 7a, the housing 50 has a generally rounded configuration, with first and second side walls, 30 wherein the side walls are secured (e.g., sealed) to the manifold 700. Typically, at least a portion of each of the first and second side walls 5, 55 is flexible. In some embodiments, at least a substantial portion (e.g., at least about 50% of the area) of each of the side walls is flexible, 35 and substantially all of the housing can be flexible.

The filter device can include additional components, e.g., the housing can include a manifold 700 (Figures 7a and

7b), typically providing a common inlet flow path into interior of the device. In accordance with the embodiment illustrated in Figures 7a and, more particularly, 7b, at least a portion of each of first and second side walls 5, 55 5 is preferably flexible. The manifold can be flexible or substantially inflexible.

A variety of materials that allow gas to pass therethrough are suitable for the housing. Typically, the material has a low profile, low weight, and is compact. For 10 example, the housing can comprise one or more screens (e.g., polyester or polypropylene) and/or one or more porous woven and/or non-woven materials, for example, but not limited to, REEMAY™ (Reemay, Inc.), and TYPAR™ (Reemay, Inc.). The housing can include a plurality of layers.

15 Typically, the housing 50 comprises one or more sheets of non-woven material that are secured (e.g., sealed) together. If desired, the housing can comprise a single sheet that is folded one or more times, before securing. The housing can be sealed, e.g., at the ends, sides, and to other 20 components of the filter device and/or the set (such as, but not limited to, one or more components of the smoke filter, a conduit, a connector, a manifold, or a port), utilizing an adhesive, a solvent, radio frequency sealing, ultrasonic sealing and/or heat sealing. If desired, the housing can 25 include any number of seals, with or without a seal to one or more components of the smoke filter and/or to the set.

In those embodiments wherein the smoke filter device includes a housing and a smoke filter, the smoke filter is associated with the housing to allow gas entering the device 30 to pass through the filter and through the housing. In those embodiments wherein the smoke filter device does not include a housing (e.g., as shown in Figure 6), the device is arranged to allow gas entering the device to pass through the smoke filter to the exterior of the device.

35 In accordance with these embodiments, the smoke filter comprises at least one porous smoke filter element comprising a hydrophobic retentive member, that typically comprises at

least one microporous hydrophobic membrane and/or at least one hydrophobic depth filter medium. The embodiment of the filter device 300 illustrated in Figures 2-6 (as well as the embodiment of the filter device illustrated in Figure 7b) has 5 two smoke filters 100, 101, each comprising a porous smoke filter element 1, 11 comprising a hydrophobic retentive member. The porous smoke filter element can have one section or a plurality of sections and/or can comprise a plurality of layers. Alternatively, or additionally, the porous smoke 10 filter element can comprise a plurality of media (e.g., at least one hydrophobic membrane and at least one fibrous hydrophobic medium).

Typically, the DOP smoke penetration rating of the smoke filter element 1, 11 is less than the rating for the 15 odor-reducing element.

In those embodiments wherein the hydrophobic retentive member comprises at least one membrane, the pore structure (e.g., the pore rating, or the pore size) of the smoke filter element 1, 11 is typically less than the pore structure of 20 the odor-reducing element. In some of those embodiments wherein the smoke filter element 1, 11 is not a depth filter (e.g., wherein the filter element does not provide prefiltration), the pore structure of the filter element is less than the pore structure of the separate prefiltration 25 element.

The smoke filter element can be selected in accordance with several factors, including the nature and size of the undesirable materials in the smoke, the desired flow rate, and the acceptable pressure drop across the smoke filter.

30 In a preferred embodiment, the smoke filter element substantially prevents the passage therethrough of bacteria. In an even more preferred embodiment, the smoke filter element also substantially prevents the passage therethrough of viruses. For example, the embodiments of the smoke filter 35 element can remove at least about 95% of the bacteria in the smoke, and provide at least about a 4 log viral reduction. In more preferred embodiments, the smoke filter element can

19-02-2001

US 009928204

remove at least about 99% of the bacteria (in some embodiments, providing at least about 5 log bacterial reduction), and provide at least about a 5 log viral reduction.

5 In an even more preferred embodiment, the smoke filter element can remove essentially 100% of the bacteria (in some embodiments, providing at least about 7 log bacterial reduction), and provide at least about a 7 log viral reduction.

10 Typically, the smoke filter element removes at least about 99.97% of smoke particles having diameters of at least about 0.3 μm or greater, and more preferably, removes at least about 99.999%, or more, (for example, at least about 99.9995%) of smoke particles having diameters of at least 15 about 0.12 μm . Illustratively, in one embodiment, smoke filter element has a DOP Smoke Penetration (e.g., as measured by ASTM D2986-71) at 0.3 μm at 10.5 ft/minute (5.3 cm/sec) gas flow of at least about 0.03%, more preferably, at least about 0.015%.

20 Typically, in those embodiment wherein the smoke filter element includes a membrane, the smoke filter element 1, 11 has a pore rating (e.g., as evidenced by bubble point) of about 10 micrometers or less, more preferably, about 5 micrometers or less, and even more preferably, about 2 25 micrometers or less.

Without being held to any particular mechanism, it is believed that small particles such as bacteria and viruses are removed by the smoke filter element by diffusion, including strong intermolecular forces (i.e., van der Waals' 30 forces) even the element may have pores of a size larger than the size of the particles (free particles, or particles suspended in a droplet). Additionally, particles, including larger particles, can be removed by at least one of straining, inertial impaction and/or interception.

19-02-2001

US 009928204

Typically, the effective filter area for the smoke filter(s) is at least 12.9 cm² (about 2 in²), more preferably, at least about 19.4 cm² (about 3 in²). In some embodiments, the effective filter area is about 22.6 cm² (about 3.5 in²) or 5 more, e.g., in the range of about 32.3 cm² to about 51.6 cm² (about 5 in² to about 8 in²), or more.

The smoke filter element may be produced from any suitable natural and/or synthetic material capable of forming a substrate, fibers or a membrane that is compatible with the 10 gas and smoke. In some embodiments, commercially available materials are preferred. Suitable polymers include, but are not limited to, polytetrafluoroethylene (PTFE), any nylon, e.g., 6, 6T, 11, 46, 66, and 610, polyvinylidene difluoride (PVDF), polyethersulfone (PES), polypropylene, and polyester. 15 Other suitable materials include cellulosic derivatives. Non-resinous materials, such as glass fibers, including microglass and/or laminated glass, can also be used.

Commercially available media, such as those available from Pall Corporation (East Hills, NY) under the trademarks 20 SUPOR®, and PALLFLEX®, are also suitable. Other suitable commercially available media include, but are not limited to, H&V HOVOGLAS™ (Hollingsworth & Vose Company, East Walpole, MA) and VERIFLO™ (Enhanced Filter, Ventura, CA).

The smoke filter element may remain untreated, or may be 25 treated to increase its effectiveness. Surface characteristics of the element can be modified (e.g., to affect the Critical Wetting Surface Tension (CWST), to include a surface charge, e.g., a positive or negative charge, and/or to alter the polarity or hydrophilicity of the 30 surface) by chemical reaction including, for example, wet or dry oxidation, by coating or depositing a polymer on the surface, or by a grafting reaction. Modifications include, e.g., irradiation, a polar or charged monomer, coating and/or 35 curing the surface with a charged polymer, and carrying out chemical modification to attach functional groups on the

16A

surface. Grafting reactions may be activated by exposure to an energy source such as gas plasma, heat, a Van der Graff generator, ultraviolet light, electron beam, or to various other forms of radiation, or by surface etching or deposition 5 using a plasma treatment. The

smoke filter element can be initially hydrophilic, and treated to be made hydrophobic, and/or the smoke filter element can be treated to increase its hydrophobicity (i.e., to make it more hydrophobic).

5 The smoke filter element can have a variety of configurations. For example, the element can be substantially planar, pleated, corrugated, or cylindrical.

As noted earlier, the smoke filter 100, 101 can include additional components such as additional elements. For 10 example, the smoke filter can include one or more upstream and/or downstream elements, such as a prefilter element, an odor-reducing element, as well as support and/or drainage elements. In some embodiments, at least a portion each of the elements of the smoke filter is flexible, e.g., pliant.

15 The smoke filter can comprise a composite, e.g., wherein one or more components is secured, e.g., laminated, to the smoke filter element. Alternatively, or additionally, the additional elements can be separate from the smoke filter.

20 Preferably, the smoke filter also includes an odor-reducing element. The smoke filter may also include a prefilter element, or the retentive member can provide retention and prefiltration (e.g., the retentive membrane can comprise a plurality of depth filter elements and/or fibrous layers).

25 In the illustrative embodiments shown in Figures 2-5, and 7b, the smoke filter also includes an odor-reducing element 3, 33, disposed downstream of the hydrophobic member (Figures 2-4, 7b) or upstream of the hydrophobic member (Figure 5). The illustrative embodiment shown in Figure 6 30 does not include an odor-reducing element.

The embodiment illustrated in Figures 2 and 3 includes prefilter elements 2, 22 and odor-reducing elements 3, 33. Either of these elements can include a plurality of layers. Preferably, the prefilter element and the odor-reducing 35 element are very open and have good porosity. The prefilter element and odor reducing element can comprise any suitable woven or non-woven material, and can be formed from natural

and/or synthetic material, e.g., fibers, polymeric material and/or glass. Exemplary materials include polypropylene, polyester, polyethersulfone, carbon (preferably activated carbon, e.g., charcoal and/or novoloid fibers) and/or

5 microglass. Carbon can be granular and embedded in a matrix, or fibers mixed in a blend (e.g., a cotton/cellulose blend).

In some embodiments including a separate prefilter element, the prefilter element comprises a fibrous medium, e.g., including polymeric fibers and/or glass fibers.

10 In some embodiments including an odor-reducing element, the odor-reducing element also reduces the passage therethrough of undesirable substances such as other chemical matter and/or organic vapors. For example, in one illustrative embodiment including an odor-reducing element, 15 the element may reduce the passage therethrough at least one of benzene, formaldehyde, hydrogen cyanide, and toluene.

In one preferred embodiment, the odor-reducing element comprises a carbon medium, preferably an activated carbon medium, even more preferably an activated fibrous carbon 20 medium. One example of a suitable commercially available medium is the activated charcoal ULTRASORB™ (Enhanced Filter, Ventura, CA), e.g., as a fibrous or granulated laminate. Another example of a suitable commercially available medium is AQF® media (AQF Technologies, Charlotte, NC), e.g., 25 activated carbon in a three dimensional polyester non-woven structure.

Typically, in those embodiments including an odor-reducing element, the odor-reducing element is downstream of the hydrophobic retentive member, i.e., gas 30 passes through the retentive member before passing through the odor-reducing element. However, in some embodiments, e.g., as shown in Figure 5, the odor-reducing element can be upstream of the hydrophobic retentive member, and can be the first element in the smoke filter.

35 In some embodiments, the smoke filter 100, 101 also includes one or more window elements, e.g., window elements 4, 44 as shown in Figures 2-6 and 7b. One or more window

elements can have one or more windows or openings. The embodiments of the window elements 4, 44 shown in the Figures have one window or opening.

The window elements and windows can be of any suitable 5 number, size and/or shape (e.g., rectangular, circular, triangular, oval). The smoke filter can include a plurality of window elements having different characteristics (e.g., shape, size and/or number of windows), and a window element can have a plurality of windows of different characteristics.

10 In a typical embodiment, at least one window element provides surface area for securing elements of the smoke filter together and/or for securing the filter to the housing. For example, in the embodiments illustrated in Figures 2, 3, 6, and 7b, window elements secured to the smoke 15 filter element 1, 11, and the prefilter element 2, 22, allow these elements to be sealed together. In accordance with the embodiment illustrated in Figure 2 and 3, the window elements also allow the smoke filter to be sealed to the inner surface of the side walls of the housing (with the odor-reducing 20 element interposed between the smoke filter element and the side wall). In accordance with the embodiment illustrated in Figure 7B, the window elements can also be secured to the manifold 700.

The window elements can also allow the inlet to be 25 sealed to the housing. The widow elements can be secured to, for example, either of the opposing surfaces of a smoke filter element or a prefilter element. Securing, e.g., sealing, can include, for example, utilizing an adhesive, a solvent, radio frequency sealing, ultrasonic sealing and/or 30 heat sealing. In some embodiments, e.g., some embodiments providing a subcomponent or subassembly of the filter device including carbon media, radio frequency sealing may be less desirable.

Typical materials suitable for producing the window 35 element(s) include, but are not limited to, for example, plasticized polyvinyl chloride (PVC), polyester, polyurethane, polycarbonate, polypropylene, polyolefin,

polyethylene, ethylene vinyl acetate (EVA), and combinations of materials.

In accordance with the invention, embodiments of the smoke filter device can be used in any medical protocol that 5 involves venting gas from a patient's body cavity, and can be used with any suitable gas flow rate. The gas flow rate can be constant or variable, and can range from low flow rates, e.g., about 0.5 liters/min or less, or up to about 15 liters/min, or even more. In some embodiments, e.g., some 10 embodiments of a smoke filter set including the smoke filter device, the set also includes a gas flow control device such as a valve, closure or clamp (including a screw clamp or pinch clamp). In some embodiments, the flow control device can be operated with one hand. If desired, the flow control 15 device can be adjustable.

The smoke filter device is especially useful in those protocols that involve the production of smoke (e.g., created by a laser, electrocautery device, or an ultrasonic tissue fragmentation device). Typically, the device is capable of 20 filtering smoke for up to about 6 minutes of cumulative cauterization, or more, with a reduction in gas flow of about 50% or less. In some embodiments, the device is capable of filtering smoke for up to about 6 minutes of cumulative cauterization, or more, with a reduction in gas flow of about 25 40%, or less, e.g., about 30%, or less. In an embodiment, the device is capable of filtering smoke for up to about 6 minutes of cumulative cauterization, or more, with a reduction in gas flow of about 40% or less.

In accordance with an embodiment of the invention, a 30 smoke filter device can deplete at least one chemical from (e.g., in, or associated with) the smoke, e.g., to provide an exposure limit that is equal to or less than the OSHA standard. Illustrative chemicals present in smoke, and exposure limits include those listed in Surgical Smoke: What 35 We Know Today (Valleylab Inc., Boulder, CO, copyright 1996), e.g., as listed in "Table 5: Chemicals, Exposure Limits, and Associated Health Effects" (page 12). For example, an

19-02-2001

US 009928204

embodiment of the smoke filter can deplete at least one of the following chemicals from smoke: acetaldehyde, acrolein, acetonitrile, benzene, hydrogen cyanide, carbon monoxide, formaldehyde, polycyclic aromatic hydrocarbons (PAHs), styrene, 5 toluene, and xylene.

Embodiments of the smoke filter device according to the invention can have any number of smoke filters, e.g., a single smoke filter, two smoke filters, or more than two smoke filters, and the smoke filter device can include a 10 housing, or lack a housing. A portion of a smoke filter (e.g., a surface of the filter) can provide a portion of a side or an end of the smoke filter device. Alternatively, or additionally, an embodiment of the smoke device can include a housing having at least one portion (e.g., a portion of least 15 one side wall) that is flexible and allows gas to pass therethrough, wherein the device is arranged to allow gas to pass through the smoke filter and the flexible portion of the housing.

In yet another embodiment, the housing is substantially 20 inflexible, and/or the smoke filter is substantially inflexible. The housing may include one or more open portions (e.g., on at least one side of the device) that allow gas to pass through a flexible or inflexible smoke filter and through the open portion(s) of the device. 25 Alternatively, or additionally, the smoke filter device can include a substantially inflexible housing, and can be arranged to allow the smoke filter to flex in the housing during use.

30

EXAMPLE 1

A smoke filter device is prepared with the configuration as generally shown in Figures 1-3. Each filter element disc has an effective diameter of 2.25 inches (5.72 cm). The smoke filter elements are PTFE membranes that remove at least 35 99.999% of smoke particles having diameters of at least 0.10 μm or greater at 20 Liters/minute gas flow. The prefilter elements are H&V HOVOGLAS™ (Hollingsworth & Vose Co.) fiber

19-02-2001

US 009928204

elements, and the odor-reducing elements are ULTRASORB (Enhanced Filter) activated carbon fibers (grade ACF-200) with a basis weight of 200 g/m². The window elements are PVC sheets, that have been cut to provide a central window with a 5 diameter of 2.25 inches (5.72 cm). The housing is REEMAY (Reemay, Inc.) non-woven media. The conduit is flexible PVC tubing.

The elements and housing are sealed together to provide a central cavity, bounded by the prefilter elements. The 10 flexible tubing is inserted into the housing and sealed thereto. The filter device, that is pliable, is arranged to allow gas passing through the tubing into the central cavity to pass through the downstream prefilters, and subsequently through the smoke filter elements, the odor-reducing 15 elements, and the side walls of the housing.

The smoke filter device is connected to a one-handed adjustable gas flow device, an additional conduit, and a luer fitting, that is subsequently connected to a trocar during a laparoscopic cholecystectomy (gall bladder removal). The CO₂ 20 gas flow (when frequent cauterization begins) is 11 liters/min, and after 6 minutes cumulative electrocauterization, the gas flow remains well over 10 liters/min (i.e., the decrease in gas flow is less than 10%) at a constant pressure of 15 mm Hg (2 kPa) (0.29 psi). The 25 surgeon's vision is not obstructed by smoke in the abdominal cavity and there is no need to stop the procedure and vent smoke from the abdomen. There is no noticeable odor in the gas passing through the smoke filter device.

This example shows that a smoke filter device according 30 to the invention is suitable for use in filtering smoke during electrocauterization.

EXAMPLE 2

A smoke filter device is prepared as described in 35 Example 1.

The smoke filter device is connected to a one-handed adjustable gas flow device, an additional conduit, and a luer

19-02-2001

US 009928204

23

decrease in gas flow less than 20%) at a constant pressure of 15 mm Hg (2 kPa) (0.29 psi). The surgeon's vision is not obstructed by aerosol in the abdominal cavity, and there is no need to stop the procedure and vent aerosol from the 5 abdomen. There is no noticeable odor in the gas passing through the smoke filter device.

This example shows that a smoke filter device according to the invention is suitable for filtering smoke and for use with a Harmonic Scalpel™ device.

10

EXAMPLE 3

This example is designed to show whether smoke filter devices according to the invention can remove volatile organic chemicals in cautery smoke.

15 Three embodiments of smoke filter devices are prepared and tested. The first device is prepared as generally described in Example 1, but without a flow control device and an extra conduit. The second device is prepared in a similar configuration; however, the odor-reducing elements are AQF® media 2750 (AQF Technologies, Charlotte, NC) having a basis weight of 600 g/m², rather than the ULTRASORB™ media utilized 20 in Example 1.

25 The third device has a configuration as generally shown in Figure 4, wherein each smoke filter element has two H&V HOVOGLAS™ fiber elements, and the odor-reducing elements are ULTRASORB™ activated carbon fibers (grade ACF-200) with a basis weight of 200 g/m². The device does not include a membrane. The window elements, housing (and sealing thereof), as well as the conduit, are as described in Example 30 1.

The smoke filter devices are separately connected to a test chamber. The test chamber includes a lid having two trocar sleeve access ports. A carbon dioxide canister is

35

connected to an insufflator, and an insufflation tubing set connects the insufflator to the chamber.

A first trocar is used to pass the cautery scalpel through a trocar sleeve access port into the chamber to 5 create smoke, and the other trocar sleeve access port is used as a collection port for either a filtered sample, or a control sample. The filter device is attached via the second trocar to the collection port. For each test, a prepared tube treated with Tenax TA polymer resin (Scientific 10 Instrument Services, Ringoes, NJ) is placed downstream of the filter device to absorb the substances of interest, and the polymer treated tube will be disconnected and the resin desorbed to quantify the substance of interest. The tubes are prepared for quantifying the following substances:

15 3-methyl-2-butenal, benzene, styrene, toluene, and ethyl benzene.

Beef liver is placed on a grounding plate in the test chamber, and the chamber is sealed. The insufflator is turned on and set for 15 mm Hg at a maximum fill rate of 40 20 Liters/min. The trocar ports are closed via a stopcock. A 10 second cautery burst clouds the chamber, and 6 bursts are created to provide a cumulative total of 1 minute of smoke. After each burst, the trocar stopcocks are opened, allowing gas to flow through the ports and the filter device for about 25 30 seconds. The stopcocks are then closed. After recording the total gas flow through the insufflator, the polymer treated tube is disconnected and stored for desorption.

The filter device is then removed, and a control tube is attached. Another minute of smoke is provided and passed 30 through the ports as described previously, and the polymer treated tube is disconnected and stored for desorption.

The filter device is then reconnected (without a polymer treated tube), and another minute of smoke is passed through the filter. The chamber is then cleared, and a polymer 35 treated tube is connected. Another minute of smoke is provided as described previously (for a cumulative total of 3 minutes of smoke), and the tube is disconnected and stored

and desorption.

The filter device is then removed, and another control tube is attached. Another minute of smoke is provided as described previously, and the tube is disconnected and stored 5 for desorption.

The above-described process, i.e., with a filter, and with a control (without a filter), is repeated, using a new filter to test each substance of interest.

The results are provided in the following Table:

10

TABLE

Removal Efficiency (Units = Nanograms)

	<u>3-Methyl-2-Butenal</u>	<u>Minute 1</u>	<u>Minute 3</u>	<u>Control</u>	<u>Average %</u>
	First Device	0	0	35	100.0
15	Second Device	0	0	23	100.0
	Third Device	0	0	42	100.0
20	<u>Benzene</u>	<u>Minute 1</u>	<u>Minute 3</u>	<u>Control</u>	<u>Average %</u>
	First Device	17	17	460	96.3
	Second Device	31	10	440	95.3
	Third Device	57	62	390	84.7
25	 				
	<u>Styrene</u>	<u>Minute 1</u>	<u>Minute 3</u>	<u>Control</u>	<u>Average %</u>
	First Device	0	0	110	100.0
	Second Device	0	0	120	100.0
	Third Device	0	18	0	not applicable
30	 				
	<u>Toluene</u>	<u>Minute 1</u>	<u>Minute 3</u>	<u>Control</u>	<u>Average %</u>
	First Device	14	39	420	93.7
	Second Device	28	23	470	94.6
35	Third Device	47	63	640	91.4
	<u>Ethyl Benzene</u>	<u>Minute 1</u>	<u>Minute 3</u>	<u>Control</u>	<u>Average %</u>
40	First Device	0	104	104	50.0
	Second Device	0	28	110	87.3
	Third Device	183	0	210	56.4

With respect to 3-methyl-2-butenal in particular, that 45 is believed to be a substance responsible for a significant portion of the foul odor produced during cauterization, the smoke filter devices deplete 3-methyl-2-butenal to below detectable levels in both the first and third minute of

exposure, whereas the control levels range from 23 ng to 42 ng. Odor is not detected in the filtered samples, whereas odor is detected in each of the control samples.

As shown in the Table, in addition to depleting 5 3-methyl-2-butenal, these embodiments of smoke filter devices reduced the levels of the following organic substances: benzene, styrene, and toluene.

This example shows smoke filter devices according to the invention remove organic volatiles, including some of the 10 volatiles thought to be responsible for a portion of the foul odor produced during cauterization.

All of the references cited herein, including publications, patents, and patent applications, are hereby 15 incorporated in their entireties by reference.

While the invention has been described in some detail by way of illustration and example, it should be understood that the invention is susceptible to various modifications and alternative forms, and is not restricted to the specific 20 embodiments set forth. It should be understood that these specific embodiments are not intended to limit the invention but, on the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the invention.

The embodiments of the invention in which an exclusive property or privilege is claimed are defined as follows:

1. A smoke filter device for use with positive pressure during a medical procedure comprising:
 - a filter housing having an interior cavity, the housing having at least a first side wall and an opposing second side wall, the first and second side walls each having at least a portion that is flexible and allows gas to pass therethrough; and
 - a smoke filter capable of filtering smoke from gas comprising at least a first porous filter element and a second porous filter element, the first and second filter elements each comprising a hydrophobic retentive member;

wherein the filter device is arranged to allow gas to pass into the interior cavity, through the first porous filter element, and through the first side wall of the housing.
2. The smoke filter device of claim 1, wherein the smoke filter device is arranged to allow gas to pass into the interior cavity, through the second porous filter element, and through the second side wall of the housing.
3. The smoke filter device of claim 1 or 2, wherein the first side wall of the housing and the second side wall of the housing each comprise a non-woven medium.
4. The smoke filter device of any one of claims 1-3, further comprising a first odor-reducing element comprising a carbon medium and a second odor-reducing element comprising a carbon medium.
5. The smoke filter device of any one of claims 1-4, wherein the first and second porous filter elements each have an effective filtration area of at least about 12.9 cm².
6. The smoke filter device of claim 3, wherein the first porous filter element is sealed to the first side wall of the housing comprising a non-woven medium and the second porous

filter element is sealed to the second side wall of the housing comprising a non-woven medium.

7. The smoke filter device of claim 4, wherein the first porous filter element is adjacent to the first odor-reducing element, and the second porous filter element is adjacent to the second odor-reducing element.
8. The smoke filter device of any one of claims 1-7, wherein the first porous filter element and the second porous filter element each comprise a membrane.
9. The smoke filter device of any one of claims 1-8, further comprising a first window element sealed to the first side wall of the housing and a second window element sealed to the second side wall of the housing.
10. The smoke filter device of any one of claims 1-9, further comprising an inlet port and a conduit communicating with the port.
11. The smoke filter device of any one of claims 1-10, wherein the filter device is capable of filtering smoke for up to about 6 minutes of cumulative smoke with a reduction in gas flow of about 50% or less from an initial gas flow of 11 liters/min at a constant pressure.
12. A smoke filter set comprising the smoke filter device of claim 10, further comprising a gas flow control device for controlling the flow of gas into the smoke device, communicating with the conduit.
13. A smoke filter device for use with positive pressure during a medical procedure comprising:

a filter housing having an inlet port and an interior cavity, the housing having at least a first side wall and a second side wall, the first and second side walls each comprising a non-woven medium; and

a smoke filter capable of filtering smoke from gas comprising at least a first porous filter element and a first odor-reducing element, and a second porous filter element and a second odor-reducing element, the first and second filter elements each comprising a hydrophobic retentive member, and the first and second odor-reducing elements each comprising an activated carbon medium;

wherein the filter device is arranged to allow gas to pass through the inlet port into the interior cavity, through the first porous filter element, the first odor-reducing element and through the first side wall of the housing, and through the second porous filter element, the second odor-reducing element and through the second side wall of the housing.

14. The smoke filter device of claim 13, wherein the first and second porous filter elements each comprise a membrane.

15. The smoke filter device of claim 14, wherein the membrane comprises a PTFE membrane.

16. The smoke filter device of claim 13, 14 or 15, wherein the first and second porous filter elements each have an effective filtration area of at least about 12.9 cm².

17. The smoke filter device of any one of claims 13-16, wherein the first porous filter element is sealed to the first side wall of the housing comprising a non-woven medium and the second porous filter element is sealed to the second side wall of the housing comprising a non-woven medium.

18. The smoke filter device of any one of claims 13-17, wherein the first porous filter element is adjacent to the first odor-reducing element, and the second porous filter element is adjacent to the second odor-reducing element.
19. The smoke filter device of any one of claims 13-18, further comprising a first window element sealed to the first side wall of the housing and a second window element sealed to the second side wall of the housing.
20. The smoke filter device of any one of claims 1-7, wherein each hydrophobic retentive member comprises a PTFE membrane.
21. A smoke filter device for use with positive pressure during a medical procedure comprising:
 - a filter housing having an inlet port and an interior cavity, the housing having a first side wall and a second side wall, the first and second side walls each comprising a non-woven medium;
 - a first smoke filter adjacent the first side wall, the first smoke filter comprising a first porous filter element comprising a hydrophobic retentive member;
 - a prefilter element or an additional element comprising a carbon medium, or both, in fluid communication with the first smoke filter;
 - a second smoke filter adjacent the second side wall, the second smoke filter comprising a second porous filter element comprising a hydrophobic retentive member; and
 - a prefilter element or an additional element comprising a carbon medium, or both, in fluid communication with the second smoke filter;

wherein the filter device is arranged to allow gas to pass through the inlet port into the interior cavity, through the first smoke filter and through the first side wall of the housing, and through the second smoke filter and through the second side wall of the housing.


22. The smoke filter device of claim 21, wherein the first porous filter element and the second porous filter element each comprise a membrane, and the prefilter element in communication with the first smoke filter and the prefilter element in communication with the second smoke filter each comprise a fibrous medium.
23. The smoke filter device of claim 22, wherein the membrane comprises a PTFE membrane.
24. The smoke filter device of claim 23, wherein the first and second smoke filters each comprise a prefilter element and an additional element comprising an odor-reducing element including activated carbon.
25. The smoke filter device of claim 21, wherein the first smoke filter comprises a first porous element comprising a hydrophobic retentive member, a prefilter element and an additional element comprising a carbon medium; and the second smoke filter comprises a second porous element comprising a hydrophobic retentive member, a prefilter element and an additional element comprising a carbon medium.
26. A gas filter device for use with positive pressure during a medical procedure comprising: a filter housing having an inlet port and an interior cavity, the housing having a first side wall and a second side wall, at least the first wall allowing gas to pass therethrough; and, a gas filter comprising a porous filter element comprising a hydrophobic membrane, and an odor-reducing element comprising an activated carbon medium; wherein the filter device is arranged to allow gas to pass through the inlet port into the interior cavity, through the porous filter element, the odor-reducing element and through the first side wall of the housing.
27. A gas filter device for use with positive pressure during a medical procedure comprising: a filter housing having an inlet port and an interior cavity, the housing having a

first side wall and a second side wall, at least the first side wall allowing gas to pass therethrough; and, a gas filter comprising a porous filter element comprising a hydrophobic retentive member; wherein the filter device is arranged to allow gas to pass through the inlet port into the interior cavity, and through the porous filter element and the first side wall of the housing.

28. A gas filter device for use with positive pressure during a medical procedure comprising: an inlet port; a first side wall and a second side wall, the device including an interior cavity between the first and second walls; wherein at least the first side wall comprises a gas filter comprising a porous filter element comprising a hydrophobic membrane, the gas filter having a first surface and an opposing second surface; wherein the first side wall comprises the second surface of the gas filter, and wherein the gas filter device is arranged to allow gas to pass through the inlet port into the interior cavity and through the gas filter and the first side wall.
29. The gas filter device of claim 26 or 28, wherein the hydrophobic membrane is a PTFE membrane.
30. The gas filter device of claim 27, wherein the filter element comprises a hydrophobic membrane, and the gas filter further comprises an odor-reducing element including carbon.
31. The gas filter device of any one of claims 26-30, wherein the filter element has an effective filtration area of at least about 12.9 cm².
32. The gas filter device of any one of claims 26-31, wherein the gas filter is adapted to substantially prevent the passage therethrough of bacteria.
33. The gas filter device of any one of claims 26-32, wherein the gas filter is adapted to substantially prevent the passage therethrough of viruses.

34. The gas filter device of claim 27 or 28, further comprising a conduit communicating with the inlet port.
35. The gas filter device of any one of claims 26-34, wherein the first wall comprises at least one of a screen, a porous woven material, and a porous non-woven material.
36. The gas filter device of claim 27, wherein the hydrophobic retentive member comprises a fibrous medium.
37. The gas filter device of claim 36, wherein the fibrous medium comprises glass fibers.
38. The gas filter device of claim 36 or 37, wherein the fibrous medium comprises microglass fibers.

1/7



Marks & Clark




FIG. 2




FIG. 3




FIG. 4




FIG. 5

6/7




FIG. 6

7/7




FIG. 7b




FIG. 7a

