

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
2 March 2006 (02.03.2006)

PCT

(10) International Publication Number
WO 2006/023119 A1

- (51) International Patent Classification⁷: **C07C 37/58**, 39/04
- (21) International Application Number: PCT/US2005/023870
- (22) International Filing Date: 5 July 2005 (05.07.2005)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
10/921,686 19 August 2004 (19.08.2004) US
- (71) Applicant: **LYONDELL CHEMICAL TECHNOLOGY, L.P.** [US/US]; Two Greenville Crossing, 4001 Kennett Pike, Suite 238, Greenville, DE 19807 (US).
- (72) Inventors: **COCHRAN, Robert, N.**; 310 Carlyle Road, West Chester, PA 19382 (US). **MILLER, Jay, F.**; 65 Fairfield Lane, Chester Springs, PA 19425-2222 (US). **BECKMAN, Erick, John**; 213 Tenth Street, Aspinwall, PA 15215 (US). **JONES, Sarah, Emma**; 4 Bryn Cerrig, Lixwm, Nr. Mold, Flintshire Wales CH8 8PF (GB).
- (74) Agents: **CARROLL, Kevin, M.** et al.; Lyondell Chemical Company, 3801 West Chester Pike, Newtown Square, PA 19073 (US).
- (81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
- *with international search report*
 - *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: DENSE PHASE OXIDATION OF BENZENE

(57) Abstract: Phenol is formed by reaction of oxidant and benzene over a solid catalyst such as Pd on TS-1, the reaction being carried out in carbon dioxide solvent at conditions effective to provide a dense phase reaction mixture.



WO 2006/023119 A1

DENSE PHASE OXIDATION OF BENZENE

FIELD OF THE INVENTION

5 The present invention relates to the oxidation of benzene to phenol using a solid catalyst such as Pd on TS-1, the improvement being that the reaction is carried out in carbon dioxide solvent under dense reaction mixture phase conditions.

BACKGROUND OF THE INVENTION

10 Phenol is an important chemical of commerce. Many different methods for synthesizing phenol have been described in the literature, most notably the phenol/acetone remote from cumene. In addition, it has been proposed to produce phenol by oxidation of benzene; see, e.g. USP 5,110,995 wherein nitrous oxide is employed as oxidant in the reaction.

15 As with any process to produce a commercial chemical, it would be desirable to attain further improvements in phenol production.

 Dense phase reaction mixture conditions have been employed in various reaction systems, e.g. in the production of tertiary butyl hydroperoxide by direct oxidation of isobutene. See, for example, USP 4,408,081 and 4,408,082. See
20 also USP 6,710,192 wherein propylene oxide is formed by epoxidation of propylene under dense phase reaction conditions

SUMMARY OF THE INVENTION

 In accordance with the present invention, the oxidation of benzene to produce phenol is carried out by reacting benzene and oxidant, using an
25 appropriate catalyst, the reaction being carried out using CO₂ as the essential solvent at dense phase reaction conditions.

DETAILED DESCRIPTION

 There are a number of significant advantages which are achieved through practice of the present invention. CO₂ is the essential solvent used for the
30 reaction and by products, which are generally formed in systems using organic solvents, are substantially avoided. Where a noble metal supported catalyst is used, leaching of noble metal from the solid catalyst is minimal due to insolubility in CO₂. Because the benzene and oxidants are totally miscible in the dense

phase system, better control of the reagent concentrations can be achieved and the head space in the reactor can be substantially eliminated.

The catalysts to be used in the present process preferably are comprised of a titanium or vanadium zeolite and a noble metal (preferably an element of Group VIII of the Periodic Table). Suitable zeolites are those crystalline materials having a porous molecular sieve structure with titanium or vanadium atoms substituted in the framework. The use of a TS-1 titanium silicalite or vanadium silicalite is especially advantageous.

The titanium-containing zeolites useful as catalysts in the process comprise the class of zeolitic substances wherein titanium atoms are substituted for a portion of the silicon atoms in the lattice framework of a molecular sieve. Such substances are well known in the art.

Particularly preferred titanium-containing zeolites include the class of molecular sieves commonly referred to as titanium silicalites, particularly "TS-1" (having an MFI topology analogous to that of the ZSM-5 aluminosilicate zeolites), "TS-2" (having an MEL topology analogous to that of the ZSM-11 aluminosilicate zeolites), and "TS-3" (as described in Belgian Pat. No. 1,001,038). Also suitable for use are the titanium-containing molecular sieves having framework structures isomorphous to zeolite beta, mordenite, ZSM-48, ZSM-12, and MCM-41. The titanium-containing zeolite preferably contains no elements other than titanium, silicon and oxygen in the lattice framework, although minor amounts of boron, iron, aluminum, and the like may be present. Other metals such as tin or vanadium may also be present in the lattice framework of the zeolite in addition to the titanium, as described in U.S. Pat. Nos. 5,780,654 and 5,744,619.

Preferred titanium-containing zeolite catalysts suitable for use in the process of this invention will generally have a composition corresponding to the following empirical formula $x\text{TiO}_2 \cdot (1-x)\text{SiO}_2$ where x is between 0.0001 and 0.500. More preferably, the value of x is from 0.01 to 0.125. The molar ratio of Si:Ti in the lattice framework of the zeolite is advantageously from 9.5:1 to 99:1 (most preferably from 9.5:1 to 60:1). The use of relatively titanium-rich zeolites may also be desirable.

While any of the noble metals can be utilized (i.e., gold, silver, platinum, palladium, iridium, ruthenium, osmium), either alone or in combination, palladium

is particularly desirable. Typically, the amount of noble metal present in the catalyst will be in the range of from 0.01 to 20 weight percent, preferably 0.1 to 5 weight percent. The manner in which the noble metal is incorporated into the catalyst is not considered to be particularly critical. For example, the noble metal
5 may be supported on the zeolite by impregnation means or the like or first supported on another substance such as silica, alumina, activated carbon or the like and then physically mixed with the zeolite. Alternatively, the noble metal can be incorporated into the zeolite by ion-exchange with, for example, Pd tetraammine chloride with or without added ammonium hydroxide. The catalyst
10 is recovered by filtration and washing and is substantially free (0.1 wt. % or less) of halide. There are no particular restrictions regarding the choice of noble metal compound or complex used as the source of the noble metal. For example, suitable compounds for such purpose include the nitrates, sulfates, halides (e.g., chlorides, bromides), carboxylates (e.g., acetate), and amine complexes of noble
15 metals. Similarly, the oxidation state of the noble metal is not considered critical. In the case of palladium for instance, the palladium may be in an oxidation state anywhere from 0 to +4 or any combination of such oxidation states. To achieve the desired oxidation state or combination of oxidation states, the noble metal compound after being introduced into the catalyst may be fully or partially pre-
20 reduced. Satisfactory catalytic performance can, however, be attained without any pre-reduction whatsoever. To achieve the active state of palladium, the catalyst may undergo pretreatment such as thermal treatment in nitrogen, vacuum, hydrogen or air.

The catalyst may additionally comprise a binder or the like and may be
25 molded, spray dried, shaped or extruded into any desired form prior to use in epoxidation. In addition to the noble metal, the catalyst may be modified with additional elements such as, for example, lanthanide metals (e.g., europium), iron, cobalt, nickel, boron, aluminum, phosphorus, calcium, vanadium, chromium, manganese, copper, zinc, and gallium.

30 Alternatively, others of the various catalysts known for use in the oxidation of benzene to phenol can also be used. For example, USP 5,110,995 describes reacting nitrous oxide with benzene to form phenol using various zeolitic catalysts such as iron silicate with ZSM-5 structure. The reaction systems and

catalysts described in USP 5,110,995 can be employed in practice of the present invention, the disclosure of USP 5,110,995 is incorporated herein by reference.

Nitrous oxide is a suitable oxidant when used with catalysts described in USP 5,110,995. Where noble metal on titanium silicate is used, the reactant
5 gases comprise mixtures of oxygen and hydrogen as hereinafter described.

The oxidation reaction is carried out using CO₂ as essential solvent, at conditions which are effective to provide a single dense phase reaction mixture. Although small amounts of other solvents can be tolerated, it is preferred that CO₂ comprise the major amount and preferably at least 98% by weight of the
10 reaction solvent. The CO₂ solvent comprises at least about 10 wt % of the reaction mixture, preferably about 75% or more up to 95% or more.

A dense-phase feed reaction mixture is one maintained at a pressure sufficiently elevated so that the reaction mixture comprised of benzene – CO₂ - oxidant behaves like a single, dense, liquid-like phase with a density higher than
15 0.25 g/cm³. Suitable temperatures are in the range of 20 to 100°C and suitable pressures from 10 to 300 atm. In other words, the dense-phase reaction mixture is free of the vapor phase, which has been characteristic of prior art reactions in the vapor phase or in a two phase (vapor-liquid) mixture. Preferably, the feed reaction mixture is under supercritical conditions, that is, a mixture comprising of
20 oxidant and CO₂ is maintained above its critical temperature as well as above its critical pressure. The oxygen and hydrogen or nitrous oxide are present in solution in the dense phase mixture, not as a separate vapor phase.

Although the critical points of temperature and pressure of CO₂ of 31.1°C and 72.9 atm are useful in establishing conditions for carrying out the reaction in
25 accordance with the invention, suitable operating conditions are pressure of 15 to 300 atm and temperatures of 20 to 100°C. Where the oxidant comprises oxygen/hydrogen mixtures, the molar ratio of hydrogen to oxygen can usually be varied in the range of H₂:O₂=1:10 to 5:1 and is especially favorable at 1:5 to 2:1. The molar ratio of oxygen or nitrous oxide to benzene is usually 1:1 to 1:20, and
30 preferably 1:1.5 to 1:10.

The following examples illustrate practice of the invention.

Example 1.

The reaction was carried out in a stainless steel batch reactor (volume 42 cm³) connected to three high pressure syringe pumps (High Pressure

Equipment, 30 cm³), a high pressure recirculating pump (Micropump) and a Hewlett Packard 5890 Series 2 Gas Chromatograph with both TCD and FID detectors. The reactor was charged with Pd/TS-1 catalyst (0.153g), 0.34 wt % Pd, and benzene (5.6 mmol) and the system was then evacuated under vacuum.

- 5 The reactor was heated to 70° C and known amounts of hydrogen (2.5 mmol), CO₂ (32.8 mmol) and oxygen (5.9 mmol-from air) were added (in this order). Additional CO₂ (AGA Speciality Gas, Coleman grade, 99.99%, approximately 20 g) was added via a gas booster (single stage, Haskel) to reach 2200 psi, to provide a dense phase reaction mixture. The reaction mixture was stirred
10 vigorously throughout the reaction. The dense phase was analyzed at various time intervals by on-line GC and then slowly depressurized to atmospheric pressure. Over a two hour period, phenol was produced at the rate of 0.0276g/g catalyst – hour.

Example 2

- 15 Benzene (5.6 mmol), hydrogen (2.5 mmol) and oxygen 5.9 mmol-from air) were added into the reactor to form phenol as described in Example 1. 0.075g of the same Pd/TS-1 catalyst as used in Example 1 was added into the reactor. Approximately 20 g of CO₂ was added as the solvent and the reaction was carried out in the dense phase at 70° C and 2200 psi. Over a two hour period,
20 phenol was produced at the rate of 0.7 g/g catalyst – hour.

Example 3

- Benzene (5.6 mmol), hydrogen (2.5 mmol) and oxygen (5.9 mmol-from air) were added into the reactor to form phenol as described in Example 1. 0.041g of the same Pd/TS-1 catalyst used above was added into the reactor.
25 Approximately 20 g of CO₂ was added as the solvent and the reaction was carried out in the dense phase at 70° C and 2200 psi. Over a two hour period, phenol was produced at the rate of 0.73 g/g catalyst – hour.

Examples 4-9

- Using the equipment and catalyst described above in Example 1, a series
30 of runs were made with the amount of catalyst and the reaction time being varied. The reactor was charged with the indicated amount of Pd/TS-1 catalyst and 11 mmol benzene. The system was evacuated under vacuum. The system was heated to 60° C and 5 mmols of hydrogen and 10 mmols of oxygen were added. CO₂ was added to pressurize the system to 2700 psi and the reaction

was conducted for the designated times. The results obtained are shown in Table 1.

Table 1

Example	Catalyst Weight (mg)	Time hours)	Phenol yield (moles phenol/moles benzene) x 100
4	300	4	0.11
5	300	2	0.032
6	300	3	0.042
7	75	4	0.0025
8	300	4	0.0708
9	150	4	0.0043

5 A GC trace showed there were no products other than phenol formed.

The above examples demonstrate the highly selective production of phenol achieved through practice of the invention. Analysis of the reaction products in each case showed only phenol as product; no substantial amounts of other reaction products were detected.

We claim:

1. In a process for the production of phenol by contacting oxidant and benzene at reactive conditions with a solid catalyst, the improvement which comprises carrying out the reaction in carbon dioxide solvent at conditions
5 effective to provide a dense phase reaction mixture.
2. The process of claim 1 wherein the catalyst is noble metal on titanium or vanadium silicalite.
3. The process of claim 1 wherein the catalyst is Pd on TS-1.
4. The process of claim 1 wherein the reaction is carried out at is a
10 temperature of 20 to 100°C and a pressure of 10-300 atm.
5. The process of claim 1 wherein the oxidant comprises a mixture of oxygen and hydrogen.
6. The process of claim 1 wherein the oxidant comprises nitrous oxide.
7. The process of claim 5 wherein the molar ratio of hydrogen to
15 oxygen in the oxidant is in the range 1:10 to 5:1.
8. The process of claim 1 wherein the molar ratio of oxidant to benzene is in the range 1:1 to 1:20.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US2005/023870

A. CLASSIFICATION OF SUBJECT MATTER

C07C37/58 C07C39/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

C07C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, CHEM ABS Data, BEILSTEIN Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 894 783 A (ENICHEM S.P.A) 3 February 1999 (1999-02-03) claims 1-33; examples 1-6 -----	1-8
A	US 2003/073856 A1 (HANCU DAN ET AL) 17 April 2003 (2003-04-17) claims 1-4; examples 1-8 -----	1-8
A	SAHLE-DEMESSIE ENDALKACHEW ET AL: "Selective Oxidation in Supercritical Carbon Dioxide Using Clean Oxidants" INDUSTRIAL & ENGINEERING CHEMISTRY RESEARCH, AMERICAN CHEMICAL SOCIETY. WASHINGTON, US, vol. 39, 2000, pages 4858-4864, XP002224379 ISSN: 0888-5885 page 4859, left-hand column, line 30 - right-hand column, line 49 -----	1-8

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

17 November 2005

Date of mailing of the international search report

24/11/2005

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Kleidernigg, O

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US2005/023870

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
EP 0894783	A	03-02-1999	IT	MI971806 A1	29-01-1999
US 2003073856	A1	17-04-2003	BR	0213326 A	13-10-2004
			CA	2464399 A1	24-04-2003
			CN	1571775 A	26-01-2005
			EP	1436274 A1	14-07-2004
			JP	2005505624 T	24-02-2005
			WO	03033485 A1	24-04-2003