




(86) **Date de dépôt PCT/PCT Filing Date:** 2005/08/10
 (87) **Date publication PCT/PCT Publication Date:** 2006/02/23
 (45) **Date de délivrance/Issue Date:** 2016/09/20
 (85) **Entrée phase nationale/National Entry:** 2007/02/08
 (86) **N° demande PCT/PCT Application No.:** US 2005/028595
 (87) **N° publication PCT/PCT Publication No.:** 2006/020793
 (30) **Priorité/Priority:** 2004/08/11 (US60/600,575)

(51) **Cl.Int./Int.Cl. H04W 24/10** (2009.01),
H04B 7/185 (2006.01), **H04W 24/02** (2009.01)
 (72) **Inventeurs/Inventors:**
 KARABINIS, PETER D., US;
 DUTTA, SANTANU, US
 (73) **Propriétaire/Owner:**
 ATC TECHNOLOGIES, LLC, US
 (74) **Agent:** SIM & MCBURNEY

(54) **Titre : UTILISATION DU SPECTRE DE BANDES SATELLITES OFFRANT UNE INTERFERENCE REDUITE OU MINIMALE**
 (54) **Title: SATELLITE-BAND SPECTRUM UTILIZATION FOR REDUCED OR MINIMUM INTERFERENCE**



(57) **Abrégé/Abstract:**

A first and/or a second communications system may provide communications service over a geographic area. A method of operating the first and/or the second communications systems may include generating a measure of aggregate interference reaching a satellite of the second communications system substantially from devices of the first communications system. The measure of aggregate interference reaching the satellite of the second communications system may be transmitted to an element of the first communications system.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
23 February 2006 (23.02.2006)

PCT

(10) International Publication Number
WO 2006/020793 A3

(51) International Patent Classification:

H04B 7/185 (2006.01) **H04Q 7/32** (2006.01)

(21) International Application Number:

PCT/US2005/028595

(22) International Filing Date: 10 August 2005 (10.08.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/600,575 11 August 2004 (11.08.2004) US

(71) Applicant (for all designated States except US): **ATC TECHNOLOGIES, LLC** [US/US]; 10802 Parkridge Boulevard, Reston, VA 20191-5416 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **KARABINIS, Peter, D.** [US/US]; 101 Chalon Drive, Cary, NC 27511 (US). **DUTTA, Santanu** [US/US]; 201 Tawny Ridge Lane, Cary, NC 27513 (US).

(74) Agent: **HATFIELD, Scott, C.**; Myers Bigel Sibley & Sajovec, P.A., P.O. Box 37428, Raleigh, NC 27627 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:


- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(88) Date of publication of the international search report:

6 July 2006

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SYSTEM FOR REDUCTION OF INTERFERENCE BETWEEN DIFFERENT COMMUNICATIONS SYSTEM



(57) Abstract: A first and/or a second communications system may provide communications service over a geographic area. A method of operating the first and/or the second communications systems may include generating a measure of aggregate interference reaching a satellite of the second communications system substantially from devices of the first communications system. The measure of aggregate interference reaching the satellite of the second communications system may be transmitted to an element of the first communications system.

WO 2006/020793 A3

SATELLITE-BAND SPECTRUM UTILIZATION FOR REDUCED OR MINIMUM INTERFERENCE

[0001]

Field of the Invention

[0002] This invention relates to wireless communications systems and methods, and more particularly to satellite communications systems and methods.

Background

[0003] Satellite radioterminal communications systems and methods are widely used for radioterminal communications. Satellite radioterminal communications systems and methods generally employ at least one space-based component, such as one or more satellites that is/are configured to wirelessly communicate with a plurality of satellite radioterminals.

[0004] A satellite radioterminal communications system or method may utilize a single antenna pattern (i.e., a global beam) to cover an entire area served by the system. Alternatively or in addition, in cellular satellite radioterminal communications systems and methods, multiple antenna patterns (i.e., beams or cells) are provided, each of which can serve substantially distinct geographical areas in an overall service region, to collectively serve an overall satellite footprint. Thus, a cellular architecture similar to that used in conventional terrestrial cellular radioterminal systems and methods can be implemented in cellular satellite-based systems and methods. The satellite typically communicates with radioterminals over a bidirectional communications pathway, with radioterminal communication signals being communicated from the satellite to the radioterminal over a down-link, forward-link or forward service link, and from the radioterminal to the satellite over an up-link, return-link or return service link.

[0005] The overall design and operation of cellular satellite radioterminal systems and methods are well known to those having skill in the art.

and need not be described further herein. Moreover, as used herein, the term "radioterminal" includes cellular and/or satellite radioterminals with or without a multi-line display; Personal Communications System (PCS) terminals that may combine a radioterminal with data processing, facsimile and/or data communications capabilities; Personal Digital Assistants (PDA) that can include a radio frequency transceiver and/or a pager, Internet and/or Intranet access, Web browser, organizer, calendar and/or a global positioning system (GPS) receiver; and/or conventional laptop and/or palmtop computers or other appliances, which include a radio frequency transceiver. As used herein, the term "radioterminal" also includes any other radiating user device/equipment/source that may have time-varying or fixed geographic coordinates, and may be portable, transportable, installed in a vehicle (aeronautical, maritime, or land-based), or situated and/or configured to operate locally and/or in a distributed fashion at any other location(s) on earth and/or in space. A "radioterminal" also may be referred to herein as a "radiotelephone," "terminal," or "wireless user device".

[0006] As is well known to those having skill in the art, terrestrial networks can enhance cellular satellite radioterminal system availability, efficiency and/or economic viability by terrestrially reusing at least some of the frequency bands that are allocated to cellular satellite radioterminal systems. In particular, it is known that it may be difficult for cellular satellite radioterminal systems to reliably serve densely populated areas, because the satellite signal may be blocked by high-rise structures and/or may not penetrate into buildings. As a result, the satellite band spectrum may be underutilized or unutilized in such areas. The use of terrestrial retransmission of all or some of the satellite band frequencies can reduce or eliminate this problem.

[0007] Moreover, the capacity of the overall system can be increased significantly by the introduction of terrestrial retransmission, since terrestrial frequency reuse can be much denser than that of a satellite-only system. In fact, capacity can be enhanced where it may be mostly needed, i.e., in and/or proximate to densely populated urban, industrial, and/or commercial areas. As a result, the overall system can become much more economically viable, as it may be able to serve a much larger subscriber base. Finally, satellite radioterminals for a satellite radioterminal system having a terrestrial component within the same satellite frequency band and using substantially the same air interface for both terrestrial

and satellite communications can be more cost effective and/or aesthetically appealing. Conventional dual band and/or dual mode alternatives, such as the well known Thuraya, Indium and/or Globalstar dual mode satellite and/or terrestrial radiotelephone systems, may duplicate some components, which may lead to increased cost, size and/or weight of the radioterminal.

[0008] United States Patent No. 6,684,057 issued January 27, 2004, to the present inventor Karabinis, and entitled Systems and Methods for Terrestrial Reuse of Cellular Satellite Frequency Spectrum, describes that a satellite radioterminal frequency can be reused terrestrially by an ancillary terrestrial network even within the same satellite cell, using interference cancellation techniques. In particular, the satellite radioterminal system according to some embodiments of U.S. Patent No. 6,684,057 includes a space-based component that is configured to receive wireless communications from a first radioterminal in a satellite footprint over a satellite radioterminal frequency band, and an ancillary terrestrial network that is configured to receive wireless communications from a second radioterminal in the satellite footprint over the satellite radioterminal frequency band. The space-based component also receives the wireless communications from the second radioterminal in the satellite footprint over the satellite radioterminal frequency band as interference, along with the wireless communications that are received from the first radioterminal in the satellite footprint over the satellite radioterminal frequency band. An interference reducer is responsive to the space-based component and to the ancillary terrestrial network that is configured to reduce the interference from the wireless communications that are received by the space-based component from the first radioterminal in the satellite footprint over the satellite radioterminal frequency band, using the wireless communications that are received by the ancillary terrestrial network from the second radioterminal in the satellite footprint over the satellite radioterminal frequency band.

[0009] United States Patent Application Publication No. 2003/0054761 A1, published March 20, 2003 to the present inventor Karabinis and entitled Spatial Guardbands for Terrestrial Reuse of Satellite Frequencies, describes satellite radioterminal systems that include a space-based

component that is configured to provide wireless radioterminal communications in a satellite footprint over a satellite radioterminal frequency band. The satellite footprint is divided into a plurality of satellite cells, in which satellite radioterminal frequencies of the satellite radioterminal frequency band are spatially reused. An ancillary terrestrial network is configured to terrestrially reuse at least one of the ancillary radioterminal frequencies that is used in a satellite cell in the satellite footprint, outside the cell and in some embodiments separated therefrom by a spatial guardband. The spatial guardband may be sufficiently large to reduce or prevent interference between the at least one of the satellite radioterminal frequencies that is used in the satellite cell in the satellite footprint, and the at least one of the satellite radioterminal frequencies that is terrestrially reused outside the satellite cell and separated therefrom by the spatial guardband. The spatial guardband may be about half a radius of a satellite cell in width.

[0010] United States Patent Application Publication No. US 2003/0054815 A1, published March 20, 2003 to the present inventor Karabinis, and entitled Methods and Systems for Modifying Satellite Antenna Cell Patterns in Response to Terrestrial Reuse of Satellite Frequencies, describes that space-based wireless radioterminal communications are provided in a satellite footprint over a satellite radioterminal frequency band. The satellite footprint is divided into satellite cells in which satellite radioterminal frequencies of the satellite radioterminal frequency band are spatially reused. At least one of the satellite radioterminal frequencies that is assigned to a given satellite cell in the satellite footprint is terrestrially reused outside the given satellite cell. A radiation pattern of at least the given satellite cell is modified to reduce interference with the at least one of the satellite radioterminal frequencies that is terrestrially reused outside the given satellite cell.

Summary

[0011] According to some embodiments of the present invention, methods of operating a first and/or a second communications system providing communications service over a geographic area may be provided. More particularly, a measure of aggregate interference reaching a satellite of the second communications system substantially from devices of the first communications

system may be generated. The measure of aggregate interference reaching the satellite of the second communications system may then be transmitted to an element of the first communications system.

[0012] According to some other embodiments of the present invention, methods of operating a first and/or a second communications system providing communications service over a geographic area may be provided. More particularly, a measure of an aggregate interference reaching a satellite of the second communications system may be received at the first communications system. A transmission of an element of the first communications system may then be altered responsive to receiving the measure of the aggregate interference reaching the satellite of the second communications system.

[0013] According to still other embodiments of the present invention, methods of operating a first and/or a second communications system providing communications service over a geographic area may be provided. More particularly, a measure of interfering signals to the second communications system substantially generated by transmissions of the first communications system may be received at the first communications system from the second communications system. An interference received at a satellite of the second communications system may then be reduced responsive to the measure of interfering signals received from the second communications system.

[0014] According to yet other embodiments of the present invention, methods of operating a first and/or a second communications system providing communications service over a geographic area may be provided. More particularly, a measure of aggregate interference reaching a satellite of the second communications system substantially from devices of the first communications system may be generated. In addition, interference received at a satellite of the second communications system may be reduced responsive to the measure of aggregate interference reaching the satellite of the second communications system substantially from devices of the first communications system.

[0015] According to more embodiments of the present invention, methods of operating a first and/or a second communications system providing communications service to a plurality of radioterminals over a geographic area may be provided. Interference from the first communications system received at a radioterminal of the second communications system may be measured. Moreover,

the measure of interference received at the radioterminal may be transmitted to an element of the second communications system.

[0016] According to still more embodiments of the present invention, a radioterminal may include an antenna, a receiver coupled to the antenna, and a controller coupled to the receiver. More particularly, the receiver may include a front-end filter configured to attenuate frequencies outside a band of frequencies for communication with the radioterminal. In addition, the receiver may be coupled between the antenna and the controller, and the controller may be configured to process communications received through the antenna and receiver.

[0016a] In accordance with an aspect of an embodiment, there is provided a method of operating a second communications system providing communications service over a geographic area wherein a first communications system provides communications service over at least a portion of the geographic area, the method comprising: generating a measure of aggregate interference reaching a satellite of the second communications system substantially from devices of the first communications system based on signals received at the satellite of the second communications system; and transmitting the measure of aggregate interference reaching the satellite of the second communications system to an element of the first communications system.

[0016b] In accordance with another aspect of an embodiment, there is provided a method of operating a first communications system providing communications service over a geographic area wherein a second communications system provides communications service over at least a portion of the geographic area, the method comprising: receiving a measure of an aggregate interference reaching a satellite of the second communications system at the first communications system, wherein the measure of aggregate interference is based on signals received at the satellite of the second communications system; and altering a transmission of an element of the first communications system responsive to receiving the measure of the aggregate interference reaching the satellite of the second communications system.

[0016c] In accordance with yet another aspect of an embodiment, there is provided a method of operating a first communications system providing communications service over a geographic area wherein a second communications system provides communications service over at least a portion of the geographic

area, the method comprising: receiving at the first communications system from the second communications system a measure of interfering signals to the second communications system substantially generated by transmissions of the first communications system; and reducing an interference received at a satellite of the second communications system responsive to the measure of interfering signals received from the second communications system.

[0016d] In accordance with yet another aspect of an embodiment, there is provided a method of operating at least one communications system providing communications service over a geographic area, the method comprising: generating a measure of aggregate interference reaching a satellite of a second communications system substantially from devices of a first communications system wherein the measure of aggregate interference is based on signals received at the satellite of the second communications system; and reducing interference received at a satellite of the second communications system responsive to the measure of aggregate interference reaching the satellite of the second communications system substantially from devices of the first communications system by altering a transmission from at least one of the devices of the first communications system responsive to the measure of aggregate interference reaching the satellite of the second communications system.

[0016e] In accordance with yet another aspect of an embodiment, there is provided a communications system providing communications service over a geographic area, the communications system comprising: a satellite configured to provide a communications link with at least one radioterminal in the geographic area; and a controller configured to generate a measure of aggregate interference reaching the satellite of the communications system substantially from devices of another communications system based on signals received at the satellite of the communications system, and to transmit the measure of aggregate interference reaching the satellite of the communications system to an element of the other communications system.

[0016f] In accordance with yet another aspect of an embodiment, there is provided a communications system providing communications service over a geographic area, the communications system comprising: at least one satellite configured to provide a communications link with at least one radioterminal in the geographic region; and a controller coupled to the at least one satellite and the at least one radioterminal, the controller being configured to receive a measure of an

aggregate interference reaching a satellite of another communications system, wherein the measure of aggregate interference is based on signals received at the satellite of the other communications system, and to alter a transmission from the at least one satellite and the at least one radioterminal responsive to receiving the measure of the aggregate interference reaching the satellite of the other communications system.

[0016g] In accordance with yet another aspect of an embodiment, there is provided a communications system providing communications service over a geographic region, the communications system comprising: at least one satellite configured to provide a communications link with at least one radioterminal in the geographic region; and a controller coupled to the at least one satellite and the at least one radioterminal, the controller being configured to receive a measure of interfering signals to another communications system substantially generated by transmissions from/to the at least one satellite and the at least one radioterminal, and to reduce interference received at a satellite of the other communications system responsive to the measure of interfering signals.

[0016h] In accordance with yet another aspect of an embodiment, there is provided a method of operating first and second radioterminal communications systems including respective first and second elements providing communications service to a plurality of radioterminals over a geographic area, the method comprising: providing communications between a radioterminal and the second element of the second radioterminal communications system; generating a measure of interference from the first radioterminal communications system including the first element to the radioterminal of the second radioterminal communications system including the second element, wherein the first radioterminal communications system is a source of the interference to the radioterminal of the second radioterminal communications system; transmitting the measure of interference to an element of the second radioterminal communications system via the second element; and transmitting the measure of interference from the second radioterminal communications system including the second element to the first radioterminal communications system including the first element.

[0016i] In accordance with yet another aspect of an embodiment, there is provided a method of operating first and second radioterminal communications systems including respective first and second elements providing communications service to a plurality of radioterminals over a geographic area, the method comprising:

providing communications between a radioterminal and the second element of the second radioterminal communications system; generating a measure of interference from the first radioterminal communications system including the first element to the radioterminal of the second radioterminal communications system including the second element, wherein the first radioterminal communications system is a source of the interference to the radioterminal of the second radioterminal communications system; transmitting the measure of interference to a ground based element of the second radioterminal communications system via the second element; and transmitting the measure of interference from the second radioterminal communications system including the second element to the first radioterminal communications system including the first element.

Brief Description Of The Drawings

[0017] Figure 1 is a diagram illustrating communications systems according to embodiments of the present invention.

[0018] Figure 2 is a diagram illustrating bandwidth sharing between communications systems according to embodiments of the present invention.

[0019] Figure 3 is a diagram illustrating communications systems according to additional embodiments of the present invention.

[0020] Figure 4 is a block diagram illustrating radioterminals according to embodiments of the present invention.

Detailed Description

[0021] Specific exemplary embodiments of the invention now will be described with reference to the accompanying drawings. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. In the drawings, like designations refer to like elements. It will be understood that when an element is referred to as being "connected", "coupled" or "responsive" to another element, it can be directly connected, coupled or responsive to the other element or intervening elements may be present. Furthermore, "connected", "coupled" or "responsive" as used herein may include wirelessly connected, coupled or responsive.

[0022] The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms "a", "an" and "the" are intended to include the plural forms as well, unless expressly stated otherwise. It will be further understood that the terms "includes," "comprises," "including" and/or "comprising," when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

[0023] Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. It will be further understood that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and the present disclosure, and will not be interpreted in an idealized or overly formal sense unless expressly so defined herein.

[0024] It will be understood that although the terms first and second may be used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another element. Thus, a first radiotelephone below could be termed a second radiotelephone, and similarly, a second radiotelephone may be termed a first radiotelephone without departing from the teachings of the present invention. As used herein, the term "and/or" includes any and all combinations of one or more of the associated listed items. The symbol "/" is also used as a shorthand notation for "and/or".

[0025] Moreover, as used herein, "substantially the same" band(s) means that two or more bands being compared substantially overlap in frequency, but that there may be some areas of non-overlap, for example at a band end(s). "Substantially the same" air interface(s) means that two or more air interfaces being compared are similar but need not be identical. Some differences may exist in one air interface (i.e., a satellite air interface) relative to another (i.e., a terrestrial air interface) to account for and/or accommodate different characteristics that may exist between, for example, a terrestrial and satellite communications environments. For example, a different vocoder rate may be used for satellite

communications compared to the vocoder rate that may be used for terrestrial communications (i.e., for terrestrial communications, voice may be compressed ("vocoder") to approximately 9 to 13 kbps, whereas for satellite communications a vocoder rate of 2 to 4 kbps, for example, may be used); a different forward error correction coding, different interleaving depth, and/or different spread-spectrum codes may also be used, for example, for satellite communications compared to the coding, interleaving depth, and/or spread spectrum codes (i.e., Walsh codes, long codes, and/or frequency hopping codes) that may be used for terrestrial communications.

[0026] Terrestrial reuse of satellite band frequencies, by radioterminals and/or terrestrial infrastructure components (also referred to as base stations, ancillary terrestrial components or ATCs, and/or ancillary terrestrial networks or ATNs), may subject a satellite system to up-link and/or down-link interference. Interference into a satellite and/or satellite gateway receiver, referred to as up-link interference (also referred to as return-link interference), may be generated, in part, by transmissions of radioterminals that are communicating with at least one terrestrial infrastructure component (base station) using at least some frequencies of a satellite up-link band and/or by transmissions of base stations that may also be using at least some of the satellite up-link band frequencies to communicate with radioterminals. A terrestrial infrastructure component (base station) may also be using at least some of the satellite up-link (return link) band frequencies to communicate with radioterminals as discussed, for example in United States Patent No. 6,684,057, to Karabinis, entitled Systems and Methods for Terrestrial Reuse of Cellular Satellite Frequency Spectrum. Interference into satellite radioterminal receivers, referred to as down-link interference (also referred to as forward-link interference), may occur from transmissions of base stations and/or radioterminals that are radiating at least some frequencies of a satellite down-link band. A radioterminal may also be using at least some of the satellite down-link (forward-link) band frequencies to communicate with at least one terrestrial infrastructure component (base station) as discussed, for example, in United States Continuation-in-Part Patent Application No. 10/730,660, to Karabinis, entitled Systems and Methods for Terrestrial Reuse of Cellular Satellite Frequency Spectrum in a Time-Division Duplex Mode, filed

December 8, 2003 and assigned to the assignee of the present invention. According to embodiments of the present invention, systems and methods may be used by a first and/or a second system operator, who may be concurrently operating a first and second system, respectively, to reduce or eliminate up-link and/or down-link interference therebetween. Moreover, each system may include a space-based and/or a ground-based sub-system, and each system may use one or more blocks of frequencies, of a given band of frequencies (such as an L-band of frequencies, S-band of frequencies and/or any other band of frequencies), over overlapping and/or separate geographic regions to provide services via the space-based and/or ground-based sub-system.

[0027] Some embodiments of the present invention will be described herein relative to the terms "first" and "second" systems. For convenience and for illustrative purposes the first system, and/or components thereof, may also be referred to as "MSV" and may, in some embodiments, correspond to a system provided by Mobile Satellite Ventures, LP (the assignee of the present invention). The second system and/or components thereof may be referred to as "non-MSV" or "Inmarsat." However, it will be understood that the invention is not limited to applications involving combinations of MSV and non-MSV or Inmarsat systems, and that any first and second system may be encompassed by the designations MSV and non-MSV or Inmarsat. Furthermore, as used herein, the term "measure" of a given signal (real-valued, complex-valued, scalar, vector, matrix, and/or of any other characteristic or dimension), and/or of any other physical or imaginary entity, includes any entity, observable and/or imaginary, that is related to, and/or derived from (via natural or man-induced processes) from the given signal (real-valued, complex-valued, scalar, vector, matrix, and/or of any other characteristic or dimension), and/or the other physical or imaginary entity. It will also be understood that even though some embodiments of the present invention may be described in terms of L-band systems and spectrum, the invention may be applied to any other (such as non-L-band) system and/or spectrum.

[0028] According to embodiments of the present invention, monitoring and control of up-link interference may be provided. Referring to Figure 1, a wireless communications system may utilize L-band spectrum, and at least some of

the down-link band frequencies of an L-band (i.e., from 1525 MHz to 1559 MHz) may be used by a first satellite 101 that may be operated by a first satellite operator (i.e., Mobile satellite Ventures, LP "MSV") to transmit information to at least one satellite radioterminal in the geographic region 111 of the first satellite 101. The at least some of the down-link band frequencies of the L-band (or a subset thereof) may also be used by a terrestrial infrastructure component, such as a base station, ATC, ATN, and/or a sub-system thereof, to transmit information to at least one radioterminal. The at least one radioterminal may be a stand-alone terrestrial-only radioterminal or an integrated radioterminal that may comprise at least some of the functionality of a stand-alone terrestrial-only radioterminal and at least some of the functionality of a satellite radioterminal. The terrestrial infrastructure component may be part of an overall infrastructure of an Ancillary Terrestrial Component (ATC) and part of an overall Ancillary Terrestrial Network (ATN) comprising a plurality of ATCs. As used herein, the term Ancillary Terrestrial Component (ATC) may also be referred to as a base station, and a plurality of ATCs may be included in an ATN.

[0029] ATCs are described, for example, in U.S. Patent No. 6,684,057 to Karabinis, entitled Systems and Methods for Terrestrial Reuse of Cellular Satellite Frequency Spectrum; and Published U.S. Patent Application Nos. US 2003/0054760 to Karabinis, entitled Systems and Methods for Terrestrial Reuse of Cellular Satellite Frequency Spectrum; US 2003/0054761 to Karabinis, entitled Spatial Guardbands for Terrestrial Reuse of Satellite Frequencies; US 2003/0054814 to Karabinis et al., entitled Systems and Methods for Monitoring Terrestrially Reused Satellite Frequencies to Reduce Potential Interference; US 2003/0054762 to Karabinis, entitled Multi-Band/Multi-Mode Satellite Radiotelephone Communications Systems and Methods; US 2003/0153267 to Karabinis, entitled Wireless Communications Systems and Methods Using Satellite-Linked Remote Terminal Interface Subsystems; US 2003/0224785 to Karabinis, entitled Systems and Methods for Reducing Satellite Feeder Link Bandwidth/Carriers In Cellular Satellite Systems; US 2002/0041575 to Karabinis et al., entitled Coordinated Satellite-Terrestrial Frequency Reuse; US 2002/0090942 to Karabinis et al., entitled Integrated or Autonomous System and Method of Satellite-Terrestrial Frequency Reuse Using Signal Attenuation and/or Blockage, Dynamic Assignment of Frequencies and/or Hysteresis;

US 2003/0068978 to Karabinis et al., entitled Space-Based Network Architectures or Satellite Radiotelephone Systems; US 2003/0143949 to Karabinis, entitled Filters for Combined Radiotelephone/GPS Terminals; US 2003/0153308 to Karabinis, entitled Staggered Sectorization for Terrestrial Reuse of Satellite Frequencies; and US 2003/0054815 to Karabinis, entitled Methods and Systems for Modifying Satellite Antenna Cell Patterns In Response to Terrestrial Reuse of Satellite Frequencies, all of which are assigned to the assignee of the present invention.

[0030] Continuing with system embodiments utilizing L-band spectrum, at least some of the up-link band frequencies of an L-band (for example, from 1626.5 MHz to 1660.5 MHz) may be used by at least one satellite radioterminal to transmit information to the first satellite 101. The at least some of the up-link band frequencies of the L-band (or a subset thereof) may also be used by the satellite radioterminal and/or by at least one other radioterminal to transmit information to at least one terrestrial infrastructure component that may be part of an overall infrastructure of an Ancillary Terrestrial Component (ATC) and part of an overall Ancillary Terrestrial Network (ATN) comprising a plurality of ATCs. The satellite radioterminal may be a stand-alone satellite-only radioterminal or it may comprise at least some of the functionality of a stand-alone terrestrial-only radioterminal and at least some of the functionality of a satellite radioterminal. The at least one other radioterminal may be a stand-alone terrestrial-only radioterminal or an integrated radioterminal that may comprise at least some of the functionality of a stand-alone terrestrial-only radioterminal and at least some of the functionality of a satellite radioterminal.

[0031] Continuing with system embodiments utilizing L-band spectrum, a second satellite 102 that may be operated by a second satellite operator (i.e., Inmarsat) and/or the radioterminal(s) thereof may be using at least some of the L-band frequencies that are also used by the first satellite 101 and/or the radioterminals thereof to communicate. Specifically, at least some of the up-link band frequencies used by the satellite radioterminals communicating with the second satellite 102 may also be frequencies that are used by at least one radioterminal communicating with the first satellite 101 and/or the at least one terrestrial infrastructure component. As such, the second satellite 102 may receive

a level of interference from the emissions of the at least one radioterminal communicating with the first satellite 101 and/or the at least one terrestrial infrastructure component.

[0032] According to embodiments of the present invention, the second satellite 102, which may be an Inmarsat 4 satellite, may form at least one beam (satellite cell) over a geographic region spanning an ensemble of radioterminal emissions that are intended for the first satellite 101 and/or the at least one terrestrial infrastructure component. Referring to Figure 1, a geographic region 111 labeled "Geographic Region of Satellite Coverage (MSV System)" is shown. Within this geographic region 111, the First Satellite 101 (MSV Satellite) is providing communications services to satellite radioterminals. Included in the Geographic Region 111 of Satellite Coverage (MSV System) is a geographic region 112 labeled "Geographic Region of Satellite & ATC Coverage (MSV System)." Within this geographic region 112, communications services may be provided to radioterminals by the First Satellite 101 (MSV Satellite) and/or by infrastructure components (base stations) that may reuse at least some of the satellite band frequencies.

[0033] The at least one beam 115 (satellite cell) that may be formed by the Second Satellite 102 (Inmarsat Satellite) substantially over the Geographic Region of Satellite & ATC Coverage (MSV System), as illustrated in Figure 1, may be configured to detect and/or estimate a measure of aggregate interference reaching the Second Satellite 102 (Inmarsat Satellite) from radioterminal and/or infrastructure component emissions originating from substantially within the Geographic Region of Satellite & ATC Coverage (MSV System) and are intended for the First Satellite 101 (MSV Satellite) and/or the at least one terrestrial infrastructure component. Techniques for detecting and/or estimating aggregate interference may be found, for example, in Published U.S. Patent Application Nos. US 2003/0054814 to Karabinis et al., entitled Systems and Methods for Monitoring Terrestrially Reused Satellite Frequencies to Reduce Potential Interference, and US 2003/0073436 to Karabinis et al., entitled Additional Systems and Methods for Monitoring Terrestrially Reused Satellite Frequencies to Reduce Potential Interference; both of which are assigned to the assignee of the present invention. The Second Satellite 102 (Inmarsat Satellite) and/or other system element(s) associated with the Second Satellite 102 (Inmarsat Satellite),

and/or other system element(s) associated with the Second Satellite **102** (Inmarsat Satellite), such as a satellite gateway, may be configured to further process the detected and/or estimated measure of aggregate interference reaching the Second Satellite **102** (Inmarsat Satellite) and relay a measure of the further processed detected and/or estimated measure of aggregate interference reaching the Second Satellite **102** (Inmarsat Satellite) and/or the detected and/or estimated measure of aggregate interference reaching the Second Satellite **102** (Inmarsat Satellite) to a system element associated with the First Satellite **101** (MSV Satellite) and/or the at least one terrestrial infrastructure component, ATC, or ATN associated with the First Satellite **101** (MSV Satellite). Responsive to the received measure of the further processed detected and/or estimated measure of aggregate interference reaching the Second Satellite **102** (Inmarsat Satellite) and/or the detected and/or estimated measure of aggregate interference reaching the Second Satellite **102** (Inmarsat Satellite) having approached, equaled, or exceeded a predetermined threshold, the at least one terrestrial infrastructure component, ATC, ATN, and/or at least one radioterminal that is substantially within the Geographic Region of Satellite & ATC Coverage (MSV System) and is associated with the First Satellite **101** (MSV Satellite) may be configured to reduce a level of transmitted radiation.

[0034] The at least one beam **115** (satellite cell) that may be formed by the Second Satellite **102** (Inmarsat Satellite) substantially over the Geographic Region of Satellite & ATC Coverage (MSV System), as illustrated in Figure 1, may be a receive-only beam. The receive-only beam may provide to the Second Satellite **102** (Inmarsat Satellite) and/or other system element(s) associated with the Second Satellite **102** (Inmarsat Satellite), such as a satellite gateway, a measure of an aggregate signal power that is reaching the Second Satellite **102** (Inmarsat Satellite), representative of at least one emission occurring substantially within the Geographic Region of Satellite & ATC Coverage (MSV System), as illustrated in Figure 1, over a band of frequencies that is used by at least one radioterminal and/or the at least one terrestrial infrastructure component.

[0035] In some embodiments, the Second Satellite **102** (Inmarsat Satellite), a satellite gateway(s) associate with the second satellite **102**, and/or other system component(s) thereof may be equipped with an interference reducer to reduce interference in signals that are intended for the Second Satellite **102** (Inmarsat Satellite), caused by MSV System emissions (occurring from within any

geographic region of satellite and/or ATC MSV system coverage). Interference reducers are known to those of skill in the art and need not be discussed further herein. Embodiments of interference reducers for reducing interference in satellite systems are disclosed for example, in the previously referenced United States Patent No. 6,684,057, to Karabinis, entitled Systems and Methods for Terrestrial Reuse of Cellular Satellite Frequency Spectrum, published Jan. 27, 2004; in Utility Patent Application No. 10/890,758, to Karabinis et al., entitled Intra- and/or Inter-System Interference Reducing Systems and Methods for Satellite Communications Systems, filed July 14, 2004; and in Provisional Patent Application No. 60/573,991 to Karabinis, entitled Systems and Methods for Monitoring Selected Terrestrially Reused Satellite Frequency Signals to Reduce Potential Interference, filed May 24, 2004; all of which are assigned to the assignee of the present invention.

[0036] It will be understood by those having skill in the art that some modifications may be applied to the interference reducer embodiments that are disclosed in the immediately above referenced Patent, Patent Application, and Provisional Patent Application when applying an interference reducer embodiment (of the Patent, Patent Application, and/or Provisional Patent Application) to reducing interference of a signal intended for an Inmarsat satellite. For example, whereas in the embodiments disclosed in the above referenced Patent, Patent Application, and Provisional Patent Application, the interference reducer may be configured to operate on a desired signal that is intended for an MSV satellite ("Signal of satellite cell S" in Figure 3 of the above referenced Patent Application; signal "f₀" of the "Satellite Radiotelephone Link" in Figure 1 of the above referenced Patent), the interference reducer, in accordance with embodiments of the present invention, may be configured to operate on a desired signal that is intended for an Inmarsat satellite. Furthermore, whereas in the embodiments disclosed in the above referenced Patent, Patent Application, and Provisional Patent Application, the interference reducer may be configured to operate at an MSV system location (such as at an MSV satellite gateway and/or other MSV facility), the interference reducer, in accordance with the embodiments of the present invention, may be configured to operate at an Inmarsat system location (such as at an Inmarsat satellite gateway and/or other Inmarsat facility). In

addition to the above, at least some of the signals "T, U, V, W, X, Y, A3, A5, A7, B4, B6, B7" that are shown in Figure 3 of the above referenced Patent Application and/or the signal "142" shown in Figure 1 of the above referenced Patent, may be transported to an Inmarsat system location to be used as inputs to the interference reducer. In some embodiments, the interference signal input(s) "T, U, V, W, X, Y, A3, A5, A7, B4, B6, B7" that are shown in Figure 3 of the above referenced Patent Application and/or the signal "142" shown in Figure 1 of the above referenced Patent, and/or a desired signal plus interference (that may be provided to an Inmarsat system location by an Inmarsat satellite) may be delay-equalized to substantially align in time the interfering signal path(s) provided via the MSV satellite relative to the interference signal path(s) provided via the Inmarsat satellite. In some embodiments, the satellite 102 of the Inmarsat satellite system may form spot beams (that may be receive-only spot beams) over ATC areas of the MSV system and may thus provide to the interference reducer measures of the interfering signals. In some embodiments, measures of the interfering signals are provided by an MSV satellite and an Inmarsat satellite. In other embodiments, a desired signal plus interference that may be provided to an Inmarsat system facility (such as an Inmarsat satellite gateway), by an Inmarsat satellite, may be transported to a MSV system facility (such as an MSV satellite gateway) and the interference reducer may be configured to be functionally operative at the MSV system facility to reduce interference of a signal that is intended for an Inmarsat satellite.

[0037] In addition, or in alternatives, monitoring and control of down-link interference may be provided according to embodiments of the present invention. In accordance with system embodiments addressed earlier, utilizing L-band spectrum, portions of the down-link band frequencies of an L-band (for example, from 1525 MHz to 1559 MHz) may be used by a first system and a satellite (for example, satellite 101) thereof that may be operated by a first satellite operator (*i.e.*, Mobile satellite Ventures, LP "MSV") to transmit information to at least one satellite radioterminal. The portions of the down-link band frequencies of the L-band (or a subset thereof) may also be used by at least one terrestrial infrastructure component (*i.e.*, an ATC) that may be operated by and/or associated with the first system and the satellite thereof (MSV system), to transmit information to at least one radioterminal. A radioterminal of a second system

(such as a satellite radioterminal of an Inmarsat system including satellite 102) may be operative while proximate to a terrestrial infrastructure component of the first system that is radiating at least some frequencies of the portions of the down-link band frequencies of the L-band (or a subset thereof) to communicate with at least one radioterminal. As such, the radioterminal of the second system may experience interference, such as overload interference and/or inter-modulation interference.

[0038] In some embodiments, a radioterminal may be operatively configured with signaling capability, such as, for example, in-band signaling capability, so as to inform a system, and/or a component thereof, such as a satellite gateway and/or other component of the system, of a Bit Error Rate (BER) measure at the radioterminal. In response to the BER measure received by the system, the system (i. e., a satellite and/or a satellite gateway) may provide a different amount of power to the radioterminal (such as more power to the radioterminal if the BER measure is, for example, greater than a first predetermined threshold, or less power to the radioterminal if the BER measure is, for example, smaller than a second predetermined threshold; where the first and second predetermined thresholds may be the same or different) relative to the power delivered to the radioterminal by the system prior to the reception by the system of the BER measure transmitted by the radioterminal via a signaling channel.

[0039] In other embodiments, in response to the BER measure received by the system from the radioterminal, and following a predetermined increase in power level to the radioterminal for the purpose of establishing a BER measure that may be within an acceptable range, the system may command the radioterminal to utilize a different down-link (forward-link) carrier and/or channel, if the radioterminal continues to report to the system a BER measure that is not within the predetermined range and is inferior to the system's Quality of Service (QoS) standard for the service being provided by the radioterminal. The different down-link (forward-link) carrier may be chosen from an available pool of carriers, and/or the different down-link (forward-link) carrier may be chosen at a maximum or near maximum frequency distance relative to a frequency or frequencies used by the at least one terrestrial infrastructure component, ATC, and/or ATN of the first system.

[0040] In yet other embodiments, in response to the BER measure received by the system from the radioterminal, the system may command the radioterminal to utilize a different down-link (forward-link) carrier and/or channel without first attempting to provide more power to the radioterminal. In some embodiments, the system may process at least two BER measures (a sequence of BER measures) before sending more power to the radioterminal and/or commanding the radioterminal to utilize a different down-link (forward-link) carrier. In some embodiments, one or more down-link (forward-link) signaling carriers/channels may be provided by a system (i. e., Inmarsat) at a frequency separation that is maximally-distant, or near maximally-distant, from a down-link (forward-link) band of frequencies used by another system (i. e., MSV).

[0041] In additional embodiments of the present invention, to further reduce the potential of down-link interference, two systems (for example, a first system including satellite **101** and a second system including satellite **102**) that are using a band of frequencies, such as an L-band of frequencies, may partition the band of frequencies into relatively large and contiguous blocks of spectrum, as illustrated in Figure 2, and use the blocks of spectrum in accordance with a minimum or substantially minimum interference potential criterion. As illustrated in Figure 2, a first relatively large contiguous block of down-link frequencies **201** (labeled "MSV ATC and/or Satellite Operations," which may be, for example, approximately 10 MHz in bandwidth) may be used by MSV to offer satellite and ATC service(s). Still referring to Figure 2, a second block of frequencies **203** (labeled "INMARSAT Operations") may be, for example, approximately 17 MHz in bandwidth. The second block of frequencies **203** labeled "INMARSAT Operations" may be used by Inmarsat to offer satellite services with, for example, a first sub-block of frequencies **203a** (that may be closest in frequency to the first block of frequencies **201** used by MSV for satellite and/or ATC operations) allocated, for example, by Inmarsat to maritime and/or land-mobile operations; followed by, for example, a second sub-block of frequencies **203b** that may be allocated by Inmarsat to aeronautical operations; and followed by, for example, a third sub-block of frequencies **203c** that may be allocated by Inmarsat to land-mobile and/or aeronautical operations. Following the INMARSAT Operations block (i. e., the second block of frequencies **203**), as illustrated in Figure 2, a third block of frequencies **205** (labeled "MSV Satellite Operations," which may be, for

example, approximately 7 MHz in bandwidth) may be used by MSV for satellite services only. In some embodiments, at least a portion of the third block of frequencies **205** may also be used by MSV to provide ATC communications.

[0042] In accordance with the illustrative embodiment relating to L-band spectrum usage by two system operators (as depicted in Figure 2 and described immediately above), at least some of the land-mobile operations of Inmarsat comprising land-mobile radioterminals that may be most susceptible to down-link interference, comprising, for example, a class of radioterminals configured for high-speed data mode(s) (such as Inmarsat radioterminals of type/class GAN, R-BGAN, and/or BGAN), may be allocated down-link carrier frequencies in the third Inmarsat sub-block **203c** and/or at a maximum or near maximum frequency distance away from MSV's ATC operations. At least some aeronautical operations of Inmarsat may also be conducted over the third Inmarsat sub-block **203c** and/or at a maximum, or near maximum, frequency separation from MSV's ATC operations. Owing to the mobility aspects of some land-mobile radioterminals (and/or some non-land-mobile radioterminals), at least some radioterminals communicating with satellite **102** may be operative, from time-to-time, from locations proximate to base station/ATC emissions generated by the communications system including satellite **101**. The at least some radioterminals that may be operative proximate to such locations may include at least one radioterminal that may be relatively more susceptible to down-link interference than other radioterminals. (A radioterminal providing a high-speed data service, for example, may be more susceptible to down-link interference than a radioterminal providing, for example, a voice service and/or low-speed data service.) The at least one radioterminal that may be relatively more susceptible to down-link interference than the other radioterminals may be allocated a down-link carrier frequency in the third Inmarsat sub-block and/or at a maximum or near maximum frequency distance away from MSV's ATC operations. This may be accomplished *a priori* by the system, during a call set-up procedure between the radioterminal and the system, prior to establishing an initial communications channel, via recognition by the system of a radioterminal profile/identity/service, or it may be accomplished *a posteriori*, after an initial communications channel has been established and a measure of unacceptable performance has been provided to the system by the radioterminal, as described earlier.

[0043] In further embodiments of the invention, an operator (Inmarsat) of a system including the satellite **102** may deploy at least one terrestrial infrastructure component, ATC, and/or ATN in parts of, all, or substantially all of the geographic area that an operator (MSV) of a system including the satellite **101** plans to, and/or has deployed, at least one terrestrial infrastructure component, ATC, and/or ATN. Having done so, the second system operator (Inmarsat) may also configure at least some of the radioterminals that are capable of communicating with the satellite **102** of the second system to also be capable of communicating with the at least one terrestrial infrastructure component, ATC, and/or ATN of the second and/or first system, and/or a terrestrial infrastructure of any other system. As such, a radioterminal of the second system (that may be operative proximate to at least one terrestrial infrastructure component, ATC, and/or ATN of the first system, and may thus be subjected to down-link interference) may establish a communications link with the at least one terrestrial infrastructure component, ATC, and/or ATN of the second and/or first system, and/or the terrestrial infrastructure of the any other system (instead of communicating via a satellite) to minimize, or eliminate the potential of down-link and/or up-link interference.

[0044] In other embodiments of the invention, in order to further reduce or eliminate the potential of down-link interference, two systems that are using a band of frequencies, such as an L-band of frequencies, and may have partitioned the band of frequencies into relatively large and contiguous blocks of spectrum, as illustrated in Figure 2, may incorporate filtering, such as band-pass, low-pass, high-pass, notch filtering and/or any other type of filtering, into at least some radioterminals to reduce further or eliminate the potential of interference. At least some radioterminals configured to communicate with the satellite **102** of the second system (Inmarsat system) may, for example, be configured with a receiver filter that attenuates at least some frequencies of the "MSV ATC and/or Satellite Operations" frequency block **201** more than frequencies of the "INMARSAT Operations" block **203**. The filter may be a front-end filter (operatively configured at the Radio Frequency (RF) section of the radioterminal receiver; before and/or after the receiver Low Noise Amplifier (LNA)), or the filter may be operatively distributed between the RF, Intermediate Frequency (IF), and/or base-band sections of the radioterminal receiver. A filter characteristic, such as an

attenuation response of the filter, may be operationally responsive to a geographic location of the radioterminal. For example, if the radioterminal is operative in North America (or proximate to North America) the filter attenuation response may be configured to attenuate at least some of the frequencies occupying the "MSV ATC and/or Satellite Operations" frequency block and/or any other MSV frequency block; otherwise, the filter may be switched out and/or by-passed, or may be altered in at least one characteristic. In some embodiments, at power-on of a radioterminal the radioterminal may be configured to function with the filter by-passed (or switched out), totally or partially. In other embodiments, radioterminals of a first system (MSV) may also be configured with a band-pass, low-pass, high-pass, notch and/or any other type of receiver-chain filter characteristic (distributed or lumped) that attenuates frequencies that lie outside of one or more MSV frequency blocks.

[0045] According to embodiments of the present invention shown in Figure 3, a first wireless communications system may include a satellite 301, an ancillary terrestrial network (ATN) including a plurality of ancillary terrestrial components (ATCs) 321a-c (also referred to as base stations), a satellite gateway 323, and a communications system controller 327. The satellite 301 may provide communications services over a relatively large geographic region 311, and the ATN (including ATCs 321a-c) may provide communications services over a smaller geographic region 312. Accordingly, each of the radioterminals 325a-c of the first wireless communications system may be configured to establish communication links with the satellite 301 and/or with an ATC 321a-c. As shown in Figure 3, the radioterminal 325a outside the geographic region 312 may establish a communications link with the satellite 301 while the radioterminals 325b-c inside the geographic region 312 may establish communications with one or more ATCs 321a-c. Moreover, a system controller 327 may coordinate operations of the first communications system. While a single contiguous geographic region 312 for ATC communications (using ATCs 321a-c) is shown inside the larger geographic region 311 for satellite communications (using satellite 301), a plurality of separate geographic regions may be provided for ATC communications, and/or a geographic region for ATC communications or portions thereof may be outside the geographic region 311 for satellite communications. Moreover, an aggregate geographic region of ATN/ATC coverage may be less

than, the same as, or larger than an aggregate geographic region of satellite coverage.

[0046] If the radioterminal **325a** moves to the geographic region **312**, the radioterminal **325a** may establish a communications link with one or more of the ATCs **321a-c**. If either of the radioterminals **325b-c** is moved outside the geographic region **312**, the moved radioterminal(s) **325b** and/or **325c** may establish a communications link with the satellite **301**. While radioterminals **325b-c** may establish communications links with the satellite **301** while in the geographic region **312**, communications links with ATCs may be preferred to increase system capacity and/or quality of service.

[0047] In addition, a second wireless communications system may include a satellite **302**, a satellite gateway **333**, and an interference reducer **337**. The satellite **302** may provide communications services for radioterminals **335a-c**. Moreover, the interference reducer may reduce up-link interference received at the satellite **302** resulting from transmissions of ATCs **321a-c**, radioterminals **325a-c**, and/or satellite **301** of the first communications system. In addition, the first and second communications systems of Figure 3 may be operated by different system operators. While the interference reducer **337** is shown as a separate functional block, functionality of the interference reducer **337** and/or portions thereof may be implemented at the satellite **302**, at the satellite gateway **333**, at the controller **327** of the first communications system, at the satellite **301** of the first communications system, at the satellite gateway **323** of the first communications system, and/or at an ATC **321a-c** of the first communications system. The interference reducer **337**, for example, may be provided as a portion of a controller of the communications system including the satellite **302** and the satellite gateway **333**.

[0048] Monitoring and control of up-link interference may thus be provided for the second communications system wherein the first and second communications systems use similar frequencies. More particularly, the first satellite **301** may use L-band spectrum, and at least some of the down-link band frequencies of an L-band (*e.g.*, from 1525 MHz to 1559 MHz) may be used by a first satellite **301** that may be operated by a first satellite operator (*e.g.*, Mobile satellite Ventures, LP "MSV") to transmit information to at least one satellite radioterminal (such as one or more of radioterminals **325a-c**) in the geographic region **311** of the first satellite **301**. The at least some of the down-link band

frequencies of the L-band (or a subset thereof) may also be used by one or more of the ATCs **321a-c** to transmit information to at least one of the radioterminals **325a-c** in the geographic region **312** of the ATN. Each of the radioterminals **325a-c** may be a stand-alone terrestrial-only radioterminal or an integrated radioterminal that may comprise at least some of the functionality of a stand-alone terrestrial-only radioterminal and at least some of the functionality of a satellite radioterminal.

[0049] Continuing with system embodiments using L-band spectrum, at least some of the up-link band frequencies of an L-band (for example, from 1626.5 MHz to 1660.5 MHz) may be used by one or more of the radioterminals **325a-c** to transmit information to the first satellite **301**. The at least some of the up-link band frequencies of the L-band (or a subset thereof) may also be used by the radioterminals **325a-c** to transmit information to at least one of the ATCs **321a-c** that may be part of an overall Ancillary Terrestrial Network (ATN) including a larger number of ATCs. One of the radioterminals **321a-c** may be a stand-alone satellite-only radioterminal or it may comprise at least some of the functionality of a stand-alone terrestrial-only radioterminal and at least some of the functionality of a satellite radioterminal. Another of the radioterminals **325a-c** may be a stand-alone terrestrial-only radioterminal or an integrated radioterminal that may comprise at least some of the functionality of a stand-alone terrestrial-only radioterminal and at least some of the functionality of a satellite radioterminal.

[0050] Continuing with system embodiments utilizing L-band spectrum, the second satellite **302** that may be operated by the second satellite operator (*e.g.*, Inmarsat) and/or the radioterminal(s) **335a-c** thereof may be using at least some of the L-band frequencies that are also used by the first satellite **301** and/or the radioterminals **325a-c** thereof to communicate. Specifically, at least some of the up-link band frequencies used by the radioterminals **335a-c** communicating with the second satellite **302** may also be frequencies that are used by at least one of the radioterminals **325a-c** communicating with the first satellite **301** and/or with at least one of the ATCs **321a-c**. The second satellite **302** may thus receive up-link interference from emissions/transmissions of at least one of the radioterminals **325a-c** communicating with the first satellite **301** and/or at least one of the ATCs **321a-c**. In some embodiments, at least one of the ATCs **321a-c** may also be using at least some of the up-link frequencies used by the radioterminals **335a-c** communicating with the second satellite **302** to

communicate with at least one of the radioterminals 325a-c. The second satellite 302 may thus also receive up-link interference from emissions/transmissions of at least one of the ATCs 321a-c.

[0051] According to embodiments of the present invention, the second satellite 302 (which may be an Inmarsat 4 satellite) may form at least one beam 315 (satellite cell or antenna pattern) over a geographic region spanning an ensemble of radioterminal and/or ATC emissions that are intended for the first satellite 301, the ATCs 321a-c and/or the radioterminals 325a-c. Within the geographic region 311, the first satellite 301 (MSV Satellite) may provide communications services to satellite radioterminals of the first communications system (such as radioterminals 325a-c). As shown, the geographic region 312 may be included in the geographic region 311. Within the geographic region 312, communications services may be provided to one or more of radioterminals 325a-c by the first satellite 301 (MSV Satellite) and/or by the ATCs 321a-c that may reuse at least some of the satellite band frequencies.

[0052] The at least one beam 315 (satellite cell or antenna pattern) may be formed by the second (e.g., Inmarsat) satellite 302 substantially over the geographic region 312 over which the ATCs 321a-c operate, as shown in Figure 3. Moreover, the beam 315 may be configured to detect and/or estimate a measure of aggregate interference reaching the second (e.g., Inmarsat) satellite 302 from radioterminal and/or ATC emissions originating from substantially within the Geographic Region 312 that are intended for radioterminals 325a-c, ATCs 321a-c and/or satellite 301 of the first communications system including satellite 301 and/or the ATN including ATCs 321a-c. Techniques for detecting and/or estimating aggregate interference may be found, for example, in Published U.S. Patent Application Nos. US 2003/0054814 to Karabinis et al., entitled Systems and Methods for Monitoring Terrestrially Reused Satellite Frequencies to Reduce Potential Interference, and US 2003/0073436 to Karabinis et al., entitled Additional Systems and Methods for Monitoring Terrestrially Reused Satellite Frequencies to Reduce Potential Interference. The second (e.g., Inmarsat) satellite 302 and/or other system element(s) associated with the second (e.g., Inmarsat) satellite 302, such as the satellite gateway 333, and/or the interference reducer 337, may be configured to further process the detected

and/or estimated measure of aggregate interference reaching the second (*e.g.*, Inmarsat) satellite **302** and relay a measure of the further processed detected and/or estimated measure of aggregate interference reaching the second (*e.g.*, Inmarsat) satellite **302** and/or the detected and/or estimated measure of aggregate interference reaching the second (*e.g.*, Inmarsat) satellite **302** to a system element (such as the controller **327**) associated with the first (*e.g.*, MSV) satellite **301** and/or at least one terrestrial infrastructure component, ATC, or ATN associated with the first (*e.g.*, MSV) satellite **301**. Responsive to the received measure of the further processed detected and/or estimated measure of aggregate interference reaching the second (*e.g.*, Inmarsat) satellite **302** and/or the detected and/or estimated measure of aggregate interference reaching the second (*e.g.*, Inmarsat) satellite **302** having approached, equaled, or exceeded a predetermined threshold, the at least one terrestrial infrastructure component, ATC, ATN, and/or at least one radioterminal that is substantially within the Geographic Region **312** of Satellite & ATC Coverage (of the first communications system including satellite **301** and ATCs **321a-c**) and is associated with the first satellite **301** may be configured to reduce a level of transmitted radiation.

[0053] The at least one beam **315** (satellite cell or antenna pattern) that may be formed by the Second Satellite **302** substantially over the Geographic Region **312** of Satellite & ATC Coverage, as illustrated in Figure 3, may be a receive-only beam. The receive-only beam may provide to the second (*e.g.*, Inmarsat) satellite **302** and/or other system element(s) associated with the second (*e.g.*, Inmarsat) satellite **302**, such as a satellite gateway **333**, and/or the interference reducer **337**, a measure of an aggregate signal power that is reaching the second (*e.g.*, Inmarsat) satellite **302**, representative of at least one emission occurring substantially within the Geographic Region **312** of Satellite & ATC Coverage (*e.g.*, MSV System), as illustrated in Figure 3, over a band of frequencies that is used by at least one radioterminal and/or at least one terrestrial infrastructure component (such as one or more of ATCs **321a-c**).

[0054] In some embodiments, the second (*e.g.*, Inmarsat) satellite **302**, a satellite gateway(s) **333** associate with the second satellite **302**, and/or other system component(s) thereof may be equipped with an interference reducer **337** to reduce interference in signals that are intended for the second (*e.g.*, Inmarsat) satellite **302**, caused by emissions from the first communications system from one or more of

radioterminals 325a-c and/or ATCs 321 a-c (occurring from within any geographic region of satellite 301 and/or ATC system coverage of the first communications system associated with the first satellite 301). Interference reducers are known to those of skill in the art and need not be discussed further herein. Embodiments of interference reducers for reducing interference in satellite systems are disclosed for example, in the previously referenced United States Patent No. 6,684,057, to Karabinis, entitled Systems and Methods for Terrestrial Reuse of Cellular Satellite Frequency Spectrum, published Jan. 27, 2004; in Utility Patent Application No. 10/890,758, to Karabinis et al., entitled Intra- and/or Inter-System Interference Reducing Systems and Methods for Satellite Communications Systems, filed July 14, 2004; in Provisional Patent Application No. 60/573,991, to Karabinis, entitled Systems and Methods for Monitoring Selected Terrestrially Reused Satellite Frequency Signals to Reduce Potential Interference, filed May 24, 2004; and in Utility Patent Application No. 11/133,102 to Karabinis entitled Systems and Methods for Monitoring Selected Terrestrially Reused Satellite Frequency Signals to Reduce Potential Interference, filed May 19, 2005.

[0055] It will be understood by those having skill in the art that some modifications may be applied to the interference reducer embodiments that are disclosed in the immediately above referenced Patent, Patent Applications, and Provisional Patent Application when applying an interference reducer embodiment (of the Patent, Patent Applications, and/or Provisional Patent Application) to reducing interference of a signal intended for the second (e.g., Inmarsat) satellite 302. For example, whereas in embodiments disclosed in the above referenced Patent, Patent Applications, and Provisional Patent Application, the interference reducer may be configured to operate on a desired signal that is intended for the first (e.g., MSV) satellite 301 ("Signal of satellite cell S" in Figure 3 of the above referenced Patent Application No. 10/890,758; signal "f_u" of the "Satellite Radiotelephone Link" in Figure 1 of the above referenced Patent No. 6,684,057), the interference reducer 337, in accordance with embodiments of the present invention, may be configured to operate on a desired signal that is intended for the second (e.g., Inmarsat) satellite 302. Furthermore, whereas in the embodiments disclosed in the above referenced Patent, Patent Applications, and Provisional

Patent Application, the interference reducer may be configured to operate at an MSV system location (such as at an MSV satellite gateway and/or other MSV facility), the interference reducer 337, in accordance with the embodiments of the present invention, may be configured to operate at an Inmarsat system location (such as at an Inmarsat satellite gateway and/or other Inmarsat facility). In addition to the above, at least some of the signals "T, U, V, W, X, Y, A3, A5, A7, B4, B6, B7" that are shown in Figure 3 of the above referenced Patent Application No. 10/890,758 and/or the signal "142" shown in Figure 1 of the above referenced Patent No. 6,684,057, may be transported to an Inmarsat system location to be used as inputs to the interference reducer 337. In some embodiments, the interference signal input(s) "T, U, V, W, X, Y, A3, A5, A7, B4, B6, B7" that are shown in Figure 3 of the above referenced Patent Application No. 10/890,758 and/or the signal "142" shown in Figure 1 of the above referenced Patent No. 6,684,057, and/or a desired signal plus interference (that may be provided to an Inmarsat system location by an Inmarsat satellite) may be delay-equalized to substantially align in time the interfering signal path(s) provided via the first (*e.g.*, MSV) satellite relative to the interference signal path(s) provided via the Inmarsat satellite. In some embodiments, the second (*e.g.*, Inmarsat) satellite 302 may form spot beams (that may be receive-only spot beams) over ATC areas of the first (*e.g.*, MSV) system and may thus provide to the interference reducer 337 measures of the interfering signals. In some embodiments, measures of the interfering signals are provided by the first (*e.g.*, MSV) satellite 301 and the second (*e.g.*, Inmarsat) satellite 302. In other embodiments, a desired signal plus interference that may be provided to a system facility of the second (*e.g.*, Inmarsat) system (such as satellite gateway 333), by the second (*e.g.*, Inmarsat) satellite 302, may be transported to a system facility of the first (*e.g.*, MSV) system (such as satellite gateway 323) and the interference reducer 337 may be configured to be functionally operative at the MSV system facility to reduce interference of a signal that is intended for the second (*e.g.*, Inmarsat) satellite 302.

[0056] In addition, or in alternatives, monitoring and control of down-link interference may be provided according to embodiments of the present invention. In accordance with system embodiments addressed earlier, utilizing L-band spectrum, portions of the down-link band frequencies of an L-band (for example, from 1525 MHz to 1559 MHz) may be used by a first communications

system and a satellite (for example, satellite **301**) thereof that may be operated by a first satellite operator (*e.g.*, Mobile satellite Ventures, LP “MSV”) to transmit information to at least one satellite radioterminal (such as radioterminals **325a-c**). The portions of the down-link band frequencies of the L-band (or a subset thereof) may also be used by at least one terrestrial infrastructure component (*e.g.*, ATCs **321a-c**) that may be operated by and/or associated with the first communications (*e.g.*, MSV) system and the satellite **301** thereof, to transmit information to at least one of the radioterminals **325a-c**. A radioterminal of a second communications system (such as satellite radioterminal **335a** of the second communications system including satellite **302**, such as an Inmarsat system) may be operative while proximate to a terrestrial infrastructure component (such as ATC **321c**) of the first communications system that is radiating at least some frequencies of the portions of the down-link band frequencies of the L-band (or a subset thereof) to communicate with at least one radioterminal (such as radioterminal **325c**). As such, the radioterminal **335a** of the second communications system may experience interference, such as overload interference and/or inter-modulation interference.

[0057] In some embodiments, the radioterminal **335a** of the second communications system may be operatively configured with signaling capability, such as, for example, in-band signaling capability, to inform a system component, such as the satellite **302**, satellite gateway **333**, and/or another component of the communications system, of a Bit Error Rate (BER) measure at the radioterminal **335a**. In response to the BER measure received by the second communications system, the second communications system (*e.g.*, the satellite **302** and/or the satellite gateway **333**) may provide a different amount of power for transmissions to the radioterminal **335a** (such as more power for transmission to the radioterminal **335a** if the BER measure is, for example, greater than a first predetermined threshold, or less power to the radioterminal **335a** if the BER measure is, for example, smaller than a second predetermined threshold; where the first and second predetermined thresholds may be the same or different) relative to the power delivered for transmission to the radioterminal **335a** by the second communications system prior to the reception by the second communications system of the BER measure transmitted by the radioterminal **335a** via a signaling channel.

[0058] In other embodiments, in response to the BER measure received by the second communications system from the radioterminal 335a, and following a predetermined increase in power level for transmission to the radioterminal 335a for the purpose of establishing a BER measure that may be within an acceptable range, the second communications system may command the radioterminal 335a to utilize a different down-link (forward-link) carrier and/or channel, if the radioterminal 335a continues to report to the system a BER measure that is not within the predetermined range and is inferior to the system's Quality of Service (QoS) standard for the service being provided by the radioterminal 335a. The different down-link (forward-link) carrier and/or channel may be chosen from an available pool of carriers and/or channels, and/or the different down-link (forward-link) carrier and/or channel may be chosen at a maximum or near maximum frequency distance relative to a frequency or frequencies used by at least one terrestrial infrastructure component and/or radioterminal such as ATCs 321a-c and/or radioterminals 325a-c.

[0059] In yet other embodiments, in response to a BER measure received by the satellite 302 from the radioterminal 335a, the system may command the radioterminal 335a to utilize a different down-link (forward-link) carrier and/or channel without first attempting to provide more power for transmission to the radioterminal 335a. In some embodiments, the second communications system may process at least two BER measures (i.e., a sequence of BER measures) before sending more power for transmissions to the radioterminal 335a and/or commanding the radioterminal 335a to utilize a different down-link (forward-link) carrier and/or channel. In some embodiments, one or more down-link (forward-link) signaling carriers/channels may be provided by the second (e.g., Inmarsat) satellite 302 at a frequency separation that is maximally-distant, or near maximally-distant, from a down-link (forward-link) band of frequencies used by the ATCs 312a-c of the first communications (e.g., MSV) system.

[0060] In additional embodiments of the present invention, to further reduce the potential of down-link interference, two systems (for example, a first communications system including satellite 301 and a second communications system including satellite 302) that are using a band of frequencies, such as an L-band of frequencies, may partition the band of frequencies into relatively large and

contiguous blocks of spectrum, as illustrated above in Figure 2, and use the blocks of spectrum in accordance with a minimum or substantially minimum interference potential criterion. As illustrated in Figure 2, a first relatively large contiguous block of down-link frequencies **201** (labeled "MSV ATC and/or Satellite Operations," which may be, for example, approximately 10 MHz in bandwidth) may be used by MSV to offer satellite and ATC service(s) using satellite **301** and/or ATCs **321a-c**. Still referring to Figure 2, a second block of frequencies **203** (labeled "INMARSAT Operations") may be, for example, approximately 17 MHz in bandwidth. The second block of frequencies **203** labeled "INMARSAT Operations" may be used by Inmarsat to offer satellite services with, for example, a first sub-block of frequencies **203a** (that may be closest in frequency to the first block of frequencies **201** used by MSV for satellite and/or ATC operations) allocated, for example, by Inmarsat to maritime and/or land-mobile operations using satellite **302**; followed by, for example, a second sub-block of frequencies **203b** that may be allocated by Inmarsat to aeronautical operations using satellite **302**; and followed by, for example, a third sub-block of frequencies **203c** that may be allocated by Inmarsat to land-mobile and/or aeronautical operations using satellite **302**. Following the INMARSAT Operations block (*e.g.*, the second block of frequencies **203**), as illustrated in Figure 2, a third block of frequencies **205** (labeled "MSV Satellite Operations," which may be, for example, approximately 7 MHz in bandwidth) may be used by MSV for satellite services only using satellite **301**. In some embodiments, at least a portion of the third block of frequencies **205** may also be used by MSV for the provision of ATC/ATN communications.

[0061] In accordance with the illustrative embodiment relating to L-band spectrum usage by two system operators (as depicted in Figure 2 and described immediately above), at least some of the land-mobile operations of the second (*e.g.*, Inmarsat) system comprising land-mobile radioterminals (such as radioterminals **335a-c**) that may be most susceptible to down-link interference (*i.e.*, overload and/or inter-modulation interference), comprising, for example, a class of radioterminals configured for high-speed data mode(s) (such as Inmarsat radioterminals of type/class GAN, R-BGAN, and/or BGAN), may be allocated down-link carrier frequencies in the third Inmarsat sub-block **203c** and/or at a maximum or near maximum frequency distance away from ATC/ATN operations of the first (*e.g.*, MSV) system using ATCs **321a-c**. At least some aeronautical

operations of the second (*e.g.*, Inmarsat) system may also be conducted over the third Inmarsat sub-block **203c** and/or at a maximum, or near maximum, frequency separation from ATC/ATN operations of the first (*e.g.*, MSV) system using ATCs **321a-c**. Owing to the mobility aspects of some land-mobile radioterminals (and/or some non-land-mobile radioterminals), at least some of the radioterminals **335a-c** communicating with satellite **302** may be operative, from time-to-time, from locations proximate to base station/ATC emissions (such as emissions generated by one or more of ATCs **312a-c**) generated by the communications system including satellite **301**. The at least some radioterminals that may be operative proximate to such locations may include at least one radioterminal that may be relatively more susceptible to down-link interference than other radioterminals. (A radioterminal providing a high-speed data service, for example, may be more susceptible to down-link interference than a radioterminal providing, for example, a voice service and/or low-speed data service.) The at least one radioterminal that may be relatively more susceptible to down-link interference than the other radioterminals may be allocated a down-link carrier frequency in the third Inmarsat sub-block **203c** and/or at a maximum or near maximum frequency distance away from MSV's ATC operations using ATCs **321a-c**. This may be accomplished *a priori* by the system, during a call set-up procedure between the radioterminal (such as one of the radioterminals **335a-c**) and the system (including the satellite **302**), prior to establishing an initial communications channel, via recognition by the system of a radioterminal profile/identity/service, or it may be accomplished *a posteriori*, after an initial communications channel has been established and a measure of unacceptable performance has been provided to the system (including the satellite **302**) by the radioterminal (such as one of the radioterminals **335a-c**), as described earlier.

[0062] In further embodiments of the invention, an operator (*e.g.*, Inmarsat) of a system including the satellite **302** may deploy at least one terrestrial infrastructure component, ATC, and/or ATN in parts of, all, or substantially all of the geographic region **312** that an operator (*e.g.*, MSV) of a system including the satellite **301** plans to, and/or has deployed, at least one terrestrial infrastructure component, such as at least one of ATCs **321a-c**. Having done so, the second communications system operator (*e.g.*, Inmarsat) may also configure at least some of the radioterminals (such as radioterminals **335a-c**) that are capable of

communicating with the satellite **302** of the second communications system to also be capable of communicating with the at least one terrestrial infrastructure component, ATC, and/or ATN of the second and/or first communications system, and/or a terrestrial infrastructure of any other system. As such, a radioterminal **335a** of the second communications system including satellite **302** (that may be operative proximate to at least one terrestrial infrastructure component such as ATC **321c** of the first communications system, and may thus be subjected to down-link interference) may establish a communications link with the at least one terrestrial infrastructure component (such as ATC **321c**) of the second and/or first communications system, and/or the terrestrial infrastructure of the any other system (instead of communicating via a satellite) to minimize, or eliminate the potential of down-link and/or up-link interference.

[0063] In other embodiments of the invention, in order to further reduce or eliminate the potential of down-link interference, two systems (such as first and second communications systems respectively including the satellites **301** and **302**) that may use a band of frequencies (such as an L-band of frequencies) may partition the band of frequencies into relatively large and contiguous blocks of spectrum, as illustrated in Figure 2. Moreover, at least some radioterminals (such as radioterminals **335a-c** of the second communications system) may incorporate filtering (such as band-pass, low-pass, high-pass, notch and/or any other type of filtering) to substantially reduce further and/or eliminate potential interference.

[0064] As shown in Figure 4, at least some radioterminals **335** configured to communicate with the satellite **302** of the second communications (e.g., Inmarsat) system may, for example, be configured with a receiver filter **401** that attenuates at least some frequencies of the "MSV ATC and/or Satellite Operations" frequency block **201** and/or at least some frequencies of any other MSV frequency block, more than frequencies of the "INMARSAT Operations" block **203**. More particularly, the radioterminal **335** may include a controller **407**, a transmitter **411**, a receiver **403**, an antenna **415**, and a user interface **409**. In addition, the receiver **403** may include a filter **401** and a Low Noise Amplifier (LNA) **405** with the filter **401** provided, in some embodiments, between the antenna **415** and the LNA **405**. In applications requiring only reception, the transmitter **411** may be omitted. In radiotelephone applications, the user interface **409** may include a microphone, a speaker, a display, and a keypad. In applications

not providing voice communications, a microphone and/or a speaker may be omitted from the user interface 409.

[0065] The filter 401 may be a front-end filter (operatively configured at a Radio Frequency (RF) section of the radioterminal receiver 403; before and/or after the receiver Low Noise Amplifier (LNA) 405), or the filter 401 may be operatively distributed between RF, Intermediate Frequency (IF), and/or base-band sections of the radioterminal 335 receiver 403. A filter characteristic, such as an attenuation response of the filter 401, may be operationally responsive to a geographic location of the radioterminal 335 and/or a level of interference received at the radioterminal 335. For example, if the radioterminal 335 is operative in North America (or proximate to North America) the filter 401 attenuation response may be configured to attenuate at least some of the frequencies occupying the "MSV ATC and/or Satellite Operations" frequency block (e.g., block 201 of Figure 2) and/or at least some of the frequencies of any other MSV frequency block. If the radioterminal 335 is operative outside North America, the filter 401 may be switched out and/or by-passed, or may be altered in at least one characteristic. The controller 407, for example, may determine a location of the radioterminal 335 responsive to information/signaling received from the satellite 302 and/or responsive to information/signaling received from a Global Positioning Satellite (GPS) system and/or other radio positioning system. In combination with the above or in an alternative, the controller 407 may determine a location of the radioterminal 335 responsive to information provided by a user through the user interface 409. Accordingly, the controller 407 may switch-out and/or by-pass the filter 401 when the radioterminal 335 is in a geographic area of relatively low expected interference so that the filter 401 is not coupled between two or more elements of receiver 403 such as, for example, the antenna 415 and the LNA 405. When the radioterminal 335 is in a geographic area of relatively high expected interference, the controller 407 may switch-in the filter 401 so that the filter 401 is coupled between the antenna 415 and the LNA 405 and/or coupled between two or more elements of the receiver 403 that may or may not include the antenna 415 and/or the LNA 405.

[0066] In some embodiments, at power-on of the radioterminal 335 the radioterminal 335 may be configured to function with the filter 401 by-passed (or switched-out), totally or partially. After power-on of the radioterminal 335, the

controller 407 may monitor a level of received interference at the radioterminal 335. If the received level of interference at the radioterminal 335 exceeds a predetermined threshold, the controller 407 may switch-in the filter 401 so that the filter is coupled between two or more elements of the receiver 403 such as, for example, between the antenna 415 and the LNA 405, as illustrated in Figure 4. If the received interference is less than the predetermined threshold, the controller 407 may switch-out and/or by-pass the filter 401 so that the filter 401 is not coupled between any two or more elements of the receiver 403. Monitoring the level of received interference at the radioterminal 335 may comprise detecting and/or estimating (at the radioterminal and/or elsewhere) a power level received at the radioterminal 335 over a frequency interval (sub-band) that is used by MSV to provide ATC/ATN communications.

[0067] In other embodiments, radioterminals (such as one or more of radioterminals 325a-c) of the first communications (*e.g.*, MSV) system of Figure 3 may also be configured with a band-pass, low-pass, high-pass, notch and/or any other type of receiver-chain filter characteristic that attenuates frequencies that lie outside of one or more MSV frequency blocks.

[0068] In the drawings and specification, there have been disclosed embodiments of the invention and, although specific terms are employed, they are used in a generic and descriptive sense only and not for purposes of limitation, the scope of the invention being set forth in the following claims.

That Which is Claimed Is:

1. A method of operating a second communications system providing communications service over a geographic area wherein a first communications system provides communications service over at least a portion of the geographic area, the method comprising:

generating a measure of aggregate interference reaching a satellite of the second communications system substantially from devices of the first communications system based on signals received at the satellite of the second communications system; and

transmitting the measure of aggregate interference reaching the satellite of the second communications system to an element of the first communications system.

2. A method according to claim 1 wherein the first communications system and the second communications system are operated by different entities.

3. A method according to claim 1 wherein the first communications system and the second communications system are operated by a same entity.

4. A method according to claim 1 wherein the first and/or the second communications system comprises at least one satellite and/or at least one terrestrial component, the at least one terrestrial component and/or the at least one satellite being configured to communicate with at least one radioterminal.

5. A method according to claim 1 wherein the first communications system comprises at least one satellite and/or at least one terrestrial component, the first communications system further comprising at least one radioterminal configured to communicate with the at least one satellite and/or with the at least one terrestrial component.

6. A method according to claim 1 wherein the first communications system and the second communications system are both configured for communications using L band and/or S band frequencies.

7. A method according to claim 1 wherein a portion of the aggregate interference reaching the satellite of the second communications system comprises transmissions

between a radioterminal and at least one of a terrestrial component and/or a satellite of the first communications system.

8. A method according to claim 1 further comprising:
receiving the measure of aggregate interference at the first communications system; and
altering a transmission of an element of the first communications system responsive to the measure of aggregate interference.

9. A method of operating a first communications system providing communications service over a geographic area wherein a second communications system provides communications service over at least a portion of the geographic area, the method comprising:

receiving a measure of an aggregate interference reaching a satellite of the second communications system at the first communications system, wherein the measure of aggregate interference is based on signals received at the satellite of the second communications system; and

altering a transmission of an element of the first communications system responsive to receiving the measure of the aggregate interference reaching the satellite of the second communications system.

10. A method according to claim 9 wherein altering a transmission of an element of the first communications system comprises altering a transmission power of the element of the first communications system.

11. A method according to claim 9 wherein altering a transmission of an element of the first communications system comprise altering a frequency of transmission of the element of the first communications system.

12. A method according to claim 9 wherein the first communications system and the second communications system are operated by different entities.

13. A method according to claim 9 wherein the first communications system and the second communications system are operated by a same entity.

14. A method according to claim 9 wherein the first and/or the second communications system comprises at least one satellite and/or at least one terrestrial component, the at least one terrestrial component and/or the at least one satellite being configured to communicate with a radioterminal.

15. A method according to claim 9 wherein the first communications system comprises at least one satellite and/or at least one terrestrial component, the at least one satellite and/or the at least one terrestrial component being configured to communicate with at least one radioterminal.

16. A method according to claim 9 wherein the first communications system and the second communications system are both configured for communications using L band and/or S band frequencies.

17. A method according to claim 9 wherein a portion of the aggregate interference reaching the satellite of the second communications system comprises transmissions between a radioterminal and at least one of a terrestrial component and/or a satellite of the first communications system.

18. A method according to claim 9 further comprising:
before receiving the measure of aggregate interference, generating the measure of aggregate interference reaching the satellite of the second communications system;
and

before receiving the measure of the aggregate interference, transmitting the measure of aggregate interference from the second communications system to the first communications system.

19. A method of operating a first communications system providing communications service over a geographic area wherein a second communications system provides communications service over at least a portion of the geographic area, the method comprising:

receiving at the first communications system from the second communications system a measure of interfering signals to the second communications system substantially generated by transmissions of the first communications system; and

reducing an interference received at a satellite of the second communications system responsive to the measure of interfering signals received from the second communications system.

20. A method according to claim 19 wherein the first communications system and the second communications system are operated by different entities.

21. A method according to claim 19 wherein the first communications system and the second communications system are operated by a same entity.

22. A method according to claim 19 wherein the first communications system and/or the second communications system comprises at least one satellite and/or at least one terrestrial component, the at least one terrestrial component and/or the at least one satellite being configured to communicate with at least one radioterminal.

23. A method according to claim 19 wherein the first communications system comprises at least one satellite and/or at least one terrestrial component, the at least one satellite and/or the at least one terrestrial component being configured to communicate with at least one radioterminal.

24. A method according to claim 19 wherein the first communications system and the second communications system are both configured for communications using L band and/or S band frequencies.

25. A method according to claim 19 wherein a portion of the interfering signals reaching the satellite of the second communications system comprises transmissions between a radioterminal and at least one of a terrestrial component and/or at least one satellite of the first communications system.

26. A method according to claim 19 wherein reducing an interference component received at the satellite of the second communications system comprises altering a transmission from an element of the first communications system responsive to receiving the measure of interfering signals at the first communications system to reduce interference from the element of the first communications system received at the satellite of the second communications system.

27. A method of operating at least one communications system providing communications service over a geographic area, the method comprising:

generating a measure of aggregate interference reaching a satellite of a second communications system substantially from devices of a first communications system wherein the measure of aggregate interference is based on signals received at the satellite of the second communications system; and

reducing interference received at a satellite of the second communications system responsive to the measure of aggregate interference reaching the satellite of the second communications system substantially from devices of the first communications system by altering a transmission from at least one of the devices of the first communications system responsive to the measure of aggregate interference reaching the satellite of the second communications system.

28. A method according to claim 27 wherein the first communications system and the second communications system are operated by different entities.

29. A method according to claim 27 wherein the first communications system and the second communications system are operated by a same entity.

30. A method according to claim 27 wherein the first and/or the second communications system comprises at least one satellite and/or at least one terrestrial component, the at least one terrestrial component and/or the at least one satellite being configured to communicate with at least one radioterminal.

31. A method according to claim 27 wherein the first communications system comprises at least one satellite and/or at least one terrestrial component, the at least one satellite and/or the at least one terrestrial component being configured to communicate with at least one radioterminal.

32. A method according to claim 27 wherein the first communications system and the second communications system are both configured for communications using L band and/or S band frequencies.

33. A method according to claim 27 wherein a portion of the aggregate interference reaching the satellite of the second communications system comprises

transmissions between a radioterminal and at least one of a terrestrial component and/or a satellite of the first communications system.

34. A method according to claim 27 wherein generating the measure of aggregate interference comprises generating the measure of aggregate interference at the first communications system, and receiving the measure of aggregate interference at the second communications system from the first communications system.

35. A method according to claim 27 wherein generating the measure of aggregate interference comprises receiving at least portions of transmissions between at least two elements of the first communications system at the second communications system, and generating the measure of aggregate interference responsive to the at least portions of transmissions between the at least two elements of the first communications system received at the second communications system.

36. A communications system providing communications service over a geographic area, the communications system comprising:

a satellite configured to provide a communications link with at least one radioterminal in the geographic area; and

a controller configured to generate a measure of aggregate interference reaching the satellite of the communications system substantially from devices of another communications system based on signals received at the satellite of the communications system, and to transmit the measure of aggregate interference reaching the satellite of the communications system to an element of the other communications system.

37. A communications system providing communications service over a geographic area, the communications system comprising:

at least one satellite configured to provide a communications link with at least one radioterminal in the geographic region; and

a controller coupled to the at least one satellite and the at least one radioterminal, the controller being configured to receive a measure of an aggregate interference reaching a satellite of another communications system, wherein the measure of aggregate interference is based on signals received at the satellite of the other communications system, and to alter a transmission from the at least one satellite and the at least one radioterminal responsive to receiving the measure of the aggregate interference reaching the satellite of the other communications system.


38. The communications system according to claim 37 further comprising at least one terrestrial component configured to provide a communications link with the at least one radioterminal in the geographic region, wherein the controller is further coupled to the at least one terrestrial component and further configured to alter a transmission from the at least one terrestrial component responsive to receiving the measure of the aggregate interference reaching the satellite of the other communications system.

39. A communications system providing communications service over a geographic region, the communications system comprising:

at least one satellite configured to provide a communications link with at least one radioterminal in the geographic region; and

a controller coupled to the at least one satellite and the at least one radioterminal, the controller being configured to receive a measure of interfering signals to another communications system substantially generated by transmissions from/to the at least one satellite and the at least one radioterminal, and to reduce interference received at a satellite of the other communications system responsive to the measure of interfering signals.

40. The communications system according to claim 37 further comprising at least one terrestrial component configured to provide a communications link with the at least one radioterminal in the geographic region, wherein the controller is further coupled to the at least one terrestrial component and further configured to receive a measure of interfering signals to another communications system substantially generated by transmissions from/to the at least one terrestrial component.






Figure 2




Figure 3

4/4




Figure 4

First Satellite (MSV Satellite)

Second Satellite (Inmarsat Satellite)

