

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(10) International Publication Number

WO 2018/156852 A1

(43) International Publication Date

30 August 2018 (30.08.2018)

(51) International Patent Classification:

A61F 2/97 (2013.01) A61F 2/07 (2013.01)

MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR, OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

(21) International Application Number:

PCT/US2018/019354

Declarations under Rule 4.17:

— of inventorship (Rule 4.17(iv))

(22) International Filing Date:

23 February 2018 (23.02.2018)

Published:

— with international search report (Art. 21(3))

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

62/463,051 24 February 2017 (24.02.2017) US

(71) Applicant: BOLTON MEDICAL, INC. [US/US]; 799 International Parkway, Sunrise, FL 33325 (US).

(72) Inventor: LOSTETTER, Timothy; 799 International Parkway, Sunrise, FL 33325 (US).

(74) Agent: MURRAY, Mary, K. et al.; Hamilton, Brook, Smith & Reynolds, P.C., 530 Virginia Rd, P.O. Box 9133, Concord, MA 01742-9133 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,

(54) Title: STENT GRAFT DELIVERY SYSTEM WITH CONSTRICTED SHEATH AND METHOD OF USE




FIG. 4A

(57) **Abstract:** A delivery system and method for implanting a stent graft includes a flexible sheath that defines openings distributed longitudinally and wherein substantial alignment of the openings along a longitudinal axis of a guidewire catheter radially constrict the flexible sheath. The flexible sheath includes at least one fenestration. A ligature extends through the openings of the flexible sheath and causes the openings to be substantially aligned, thereby constraining the flexible sheath. The ligature is proximally retractable from the openings to thereby release the flexible sheath from a radially constricted configuration.

Stent Graft Delivery System with Constricted Sheath and Method of Use

RELATED APPLICATION

[0001] This application claims the benefit of U.S. Provisional Application No. 62/463,051, filed on February 24, 2017. The entire teachings of the above application is incorporated herein by reference.

BACKGROUND

[0002] Fenestrated endovascular aortic repair (FEVAR) is a minimally invasive procedure to treat aortic aneurysms that span blood vessels arising from the aorta that supply blood to vital organs including the kidneys, intestine and liver. Endovascular grafts employed in FEVAR define fenestrations for insertion of branch prostheses that serve as passageways for blood flow through arterial branches to vital organs following implantation of the endovascular graft. Maximizing blood flow to vital organs and minimizing endoleaks following repair of aneurysms with fenestrated vascular prostheses, such as juxtarenal aortic aneurysms and short-neck abdominal aortic aneurysms, present medical challenges that must be overcome if additional surgical intervention is to be avoided.

[0003] Therefore, a need exists for new and improved delivery devices, endovascular repair devices for implanting stent grafts and for methods of their use, to treat aortic pathologies, such as juxtarenal and short-neck abdominal aortic aneurysms.

SUMMARY

[0004] The present invention relates to a stent graft delivery system and a method for its use in treating and repairing arterial vascular damage, such as vascular damage associated with aortic aneurysms in regions of the aorta having arterial branches that supply blood to vital organs and tissues, including abdominal aortic aneurysms and thoracoabdominal aortic aneurysms, such as juxtarenal aortic aneurysms and short-neck abdominal aortic aneurysms.

[0005] In one embodiment, a stent graft delivery system of the invention includes a handle, a guidewire catheter, an outer catheter, a flexible sheath, and a ligature. The guidewire catheter extends distally from the handle and includes a distal end and a proximal end, and defines a longitudinal axis, the guidewire catheter being movable relative to the handle. The outer catheter is fixed to and extends distally from the handle and about the

guidewire catheter. The flexible sheath extends between the guidewire catheter and the outer catheter and is longitudinally movable relative to the guidewire catheter and the outer catheter. The flexible sheath includes openings, whereby an arrangement of the openings will cause the flexible sheath to have a luminal configuration having a constricted radial diameter. The ligature extends through the openings that causes the openings to conform to the arrangement, thereby configuring the flexible sheath to conform to the constricted radial diameter of the luminal configuration, the ligature being proximally retracted from the openings to thereby release the flexible sheath from the constricted radial diameter.

[0006] In another embodiment, the invention is a method for delivering a stent graft to an aneurysm site of a patient, including the steps of directing the stent graft to an aneurysm site of the patient, the stent graft being radially constricted, at least in part, by a flexible sheath that includes openings conforming to an arrangement along a longitudinal axis of a guidewire catheter to which the stent graft is releasably fixed. The openings are released from the arrangement, whereby the stent graft is released from radial constriction, thereby delivering a stent graft to the aneurysm site.

[0007] The stent graft delivery systems and methods of the invention have several advantages. For example, the surgeon is provided with increased flexibility in the placement of the stent graft by enabling rotation or repositioning of the stent graft after it has been partially deployed while remaining in the flexible sheath, such as by only partially releasing at least one ligature extending through openings in the flexible sheath. In an embodiment wherein the stent graft includes a fenestration, the flexible sheath can also include a fenestration that is aligned with the fenestration of the stent graft, whereby the fenestration can be better aligned with a branch artery and, optionally, the proximal end of a branch prosthesis can be directed through the fenestration of the stent graft while the stent graft is radially constrained by the flexible sheath. In this embodiment, removal of the ligature releases the flexible sheath from the arrangement of openings and therefore allows the stent graft to radially expand. The flexible sheath can then be removed without interference from the implanted branch stent graft. As a consequence, a stent graft can be deployed at a surgical site with more accuracy, less risk of injury to the vasculature of the subject, and without significant risk of distorting the intended shape of the stent graft when implanted at the surgical site.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] The foregoing will be apparent from the following more particular description of example embodiments, as illustrated in the accompanying drawings in which like reference characters refer to the same parts throughout the different views. The drawings are not necessarily to scale, emphasis instead being placed upon illustrating embodiments.

[0009] FIG. 1A is a side view of a flexible sheath of one embodiment of a stent graft delivery system of the invention, including a wire holding openings in the flexible sheath in an arrangement that causes the flexible sheath to have a luminal configuration and a constricted radial diameter, and wherein the flexible sheath defines a fenestration in the luminal configuration that is aligned with a fenestration in a stent graft radially constricted within the flexible sheath.

[0010] FIG. 1B is a plan view of the flexible sheath and stent graft represented in FIG. 1A.

[0011] FIG. 2A is a perspective view of a flexible sheath of a stent graft stent graft delivery system of the invention having openings that, when in an arrangement by a ligature, cause the flexible sheath to have a luminal configuration having a constricted radial diameter.

[0012] FIG. 2B is a perspective view of the embodiment shown in FIG. 2A following retraction of the ligature and consequent release of the openings of the flexible sheath from the arrangement.

[0013] FIG. 3A is a perspective view of another embodiment of a flexible sheath of the stent graft delivery system of the invention, wherein the openings of the flexible sheath are suture loops that, when in an arrangement, cause the flexible sheath to have a luminal configuration having a constricted radial diameter, and wherein the arrangement of openings by a ligature causes scalloped edges of the flexible sheath to define a fenestration in the luminal configuration.

[0014] FIG. 3B is a perspective view of the embodiment shown in FIG. 3A following retraction of the ligature and consequent release of the openings from the arrangement.

[0015] FIG. 4A is a side view of an embodiment of the stent graft delivery system of the invention, wherein a stent graft is captured by the stent graft delivery system and is radially constricted by a flexible sheath of the stent graft delivery system while openings in the flexible sheath are held in an arrangement that causes the flexible sheath to assume a luminal configuration having a constricted radial diameter, and wherein the flexible sheath defines a fenestration that is aligned with a fenestration in the stent graft.

[0016] FIG. 4B is a side view of the stent graft delivery system shown in FIG. 4A depicting radial expansion of the stent graft, while still captured by the stent graft stent graft delivery system at a proximal end, but following proximal retraction of a ligature, to release the openings of the flexible sheath from the radially constricted arrangement.

[0017] FIG. 4C is a side view of the stent graft delivery system shown in FIGs. 4A and 4B following proximal retraction of the flexible sheath to expose the stent graft during delivery to an aneurysm site.

[0018] FIG. 4C(i) is a detail of the apex capture assembly of the stent graft delivery system shown in FIG. 4C.

[0019] FIG. 4C(ii) is another detail of the apex capture assembly of the stent graft delivery system shown in FIG. 4C.

[0020] FIG. 4D is a side view of the stent graft delivery system shown in FIGs. 4A through 4C following release of a proximal bare stent of the stent graft from an apex capture assembly of the stent graft delivery system and prior to complete retraction of the stent graft delivery system from the stent graft.

[0021] FIG. 4D(i) is an apex capture assembly of the stent graft delivery system shown in FIG. 4D.

[0022] FIG. 5 is an exploded view of a stent graft delivery system of the invention.

[0023] FIG. 6A is a side view of the stent graft delivery system shown in FIG. 5 when assembled, and containing a stent graft (not shown) loaded within an introducer sheath of the stent graft delivery system and having been advanced to an aneurysm to be treated by one embodiment of a method of the invention.

[0024] FIG. 6B is a side view of the stent graft delivery system shown in FIG. 6A after retraction of the introducer sheath to thereby expose the stent graft contained therein.

[0025] FIG. 6C is a side view of the stent graft delivery system shown in FIGs. 6A and 6B following retraction of a wire that releases the stent graft from a radially constricted position within a flexible sheath of the stent graft delivery system of the invention.

[0026] FIG. 6D is a side view of the stent graft delivery system shown in FIGs. 6A through 6C, following retraction of the flexible sheath from the stent graft still captured by an apex capture assembly of the stent graft delivery system of the invention.

[0027] FIG. 6E is a side view of the stent graft delivery system shown in FIGs. 6A through 6D, following release of the stent graft from the apex capture assembly of the stent graft delivery system of the invention.

[0028] FIG. 6F is a side view of the stent graft delivery system shown in FIGs. 6A through 6E, following retraction of the stent graft delivery system from within the stent graft.

[0029] FIG. 6G is a side view of the stent graft delivery system shown in FIGs. 6A through 6F following retraction of the stent graft delivery system from within the stent graft, thereby completing implantation of the stent graft at the aneurysm by one embodiment of the invention.

[0030] FIG. 7A is a side view of an embodiment of the stent graft delivery system of the invention, wherein a stent graft having a bare stent is radially constricted by a flexible sheath of the stent graft delivery system.

[0031] FIG. 7B is a side view of the stent graft delivery system shown in FIG. 7A following retraction of the flexible sheath.

[0032] FIG. 8 is a side view of a vascular prosthesis implanted at an aneurysm in a patient employing a stent graft delivery system of the invention, and branch prostheses implanted through respective fenestrations of the vascular prosthesis and into arterial branches of the aorta.

DETAILED DESCRIPTION

[0033] The invention is generally directed to stent graft delivery systems for use in treating and repairing aortic vascular damage, such as vascular damage associated with an aortic aneurysm in regions of the aorta having arterial branches to vital organs and tissues, such as juxtarenal aortic aneurysms and short-neck abdominal aortic aneurysms.

[0034] The features and other details of the invention, either as steps of the invention or as combinations of parts of the invention will now be more particularly described and pointed out in the claims. It will be understood that the particular embodiments of the invention are shown by way of illustration and not as limitations of the invention. The principle features of this invention can be employed in various embodiments without departing from the scope of the invention.

[0035] A description of example embodiments of the invention follows.

[0036] When reference is made herein to a prosthesis, also referred to herein as a “stent graft,” “stent graft prosthesis,” or “vascular prostheses,” to be delivered, or implanted in a patient, the word “proximal” means that portion of the prosthesis or component of the prosthesis that is relatively close to the heart of the patient and “distal” means that portion of the prosthesis or component of the prosthesis that is relatively far from the heart of the

patient. A “longitudinal axis,” as that term is defined herein, means an axis along a lengthwise direction of a body that also passes through a center of gravity of the body.

[0037] When, however, reference is made to a delivery system or a component of a delivery system employed to deliver, or implant, a prosthesis, the word, “proximal,” as employed herein, means closer to the clinician using the delivery system. When reference is made to a delivery system or a component of a delivery system, “distal,” as that term is employed herein, means, further away from the clinician using the delivery system.

[0038] For clarity, the word “proximate” means “close to,” as opposed to the meanings ascribed to “proximal” or “distal” described above with respect to either the prosthesis or a delivery system.

[0039] In one embodiment, a stent graft delivery system of the invention includes a flexible sheath, as shown in FIGs. 1A and 1B. As shown in FIG. 1A, flexible sheath 10 is held in a luminal configuration by an arrangement of openings 12 that causes flexible sheath 10 to have a constricted radial diameter **D**. In the embodiment shown in FIG. 1A, the arrangement of openings 12 is maintained by wire 14 that extends through openings 12. Wire 14 extends generally parallel to flexible sheath 10. It is to be understood, however, that openings 12 could be arranged in any pattern that causes flexible sheath 10 to assume a luminal configuration. When openings are so arranged, regardless, stent graft 16 is maintained in a radially constricted position. In the embodiment shown in FIG. 1A, when openings 12 are arranged to cause flexible sheath 10 to have a luminal configuration having constricted diameter **D**, flexible sheath 10 defines fenestration 18 that exposes fenestration 20 of stent graft 16 radially constricted therein. FIG. 1B is a view of the embodiment shown in FIG. 1A, rotated 90° about longitudinal axis 13, showing wire 14 extending through openings 12 and spanning fenestration 18 of flexible sheath 10 while stent graft 16 is radially constricted within flexible sheath 10.

[0040] Examples of a suitable material for use in ligature is a wire that includes at least one member of the group consisting of a shape memory alloy, stainless steel, or a polymer, such as nylon. In one embodiment, the shape memory alloy is Nitinol. In another embodiment, ligature is a suitable thread such as is known in the art and employed to form sutures.

[0041] FIG. 2A is a perspective view of another embodiment of a flexible sheath component 22 of the stent graft delivery system of the invention, wherein openings are slits 24 defined by flexible sheath 22 and are longitudinally aligned by wire 26 in a linear

arrangement to thereby cause flexible sheath 22 to have a luminal configuration of constricted radial diameter **D**. FIG. 2B is a perspective view of flexible sheath 22 shown in FIG. 2A, following retraction of wire 26, thereby releasing slits 24 from the linear arrangement that causes flexible sheath to have a constricted radial diameter **D**. Radial expansion of flexible sheath 22, such as by radial expansion of a previously radially constricted stent graft (not shown) within flexible sheath 22 causes slits 24 to move relative to each other so they are no longer aligned in a linear arrangement, thereby causing radial diameter of flexible sheath to expand from a constricted radial diameter **D** to a larger radial diameter **D'**, as shown in FIG. 2B.

[0042] As shown in FIG. 3A, another embodiment of a stent graft delivery system of the invention that includes a flexible sheath 28, wherein the openings of flexible sheath 28 are suture loops 30 that, when in an arrangement, cause flexible sheath 28 to have a luminal configuration having a constricted radial diameter **D**. In this embodiment, the arrangement of suture loops 30 is a longitudinal alignment of suture loops by wire 32 that forms seam 36. Further, when in the luminal configuration, flexible sheath 28 defines fenestration 34.

[0043] FIG. 3B is a perspective view of the embodiment shown in FIG. 3A, following retraction of wire 32 from suture loops 30, whereby suture loops 30 are released from the arrangement causing flexible sheath 28 to have a luminal configuration. As further shown in FIG. 3B, seam 36 of FIG. 3A includes edges 38. Scalloped edges 38, as shown in FIG. 3B, define fenestration 34 represented in FIG. 3A, when loops 30 of flexible sheath 28 are arranged to cause flexible sheath 28 to assume a luminal configuration having constricted radial diameter **D**. Radial expansion of flexible sheath 28, such as by radial expansion of a self-expanding stent graft (not shown) previously radially constricted within flexible sheath 28, causes suture loops 30 to move relative to each other and opens seam 36, so that suture loops 30 and flexible sheath 28 are no longer in a radially constricted arrangement.

[0044] While the openings can be, for example, slits in the material of the flexible sheath, as shown in FIGs. 2A and 2B, the openings can also be suture loops fixed to flexible sheath, such as shown in FIGs. 3A and 3B. It is also to be understood that openings can have some other configuration, such as combinations of suture loops and slits. Further, as stated above, the arrangement of openings that cause flexible sheath to have a luminal configuration of constricted radial diameter **D** need not be linear, so long as the arrangement is maintained with sufficient strength to sufficiently radially constrict a stent graft for delivery to an aneurysm site of a patient.

[0045] FIGS. 4A through 4D represent successive steps in the release of a stent graft according to one embodiment of a method of the invention. As shown in FIG. 4A, flexible sheath 40 radially constricts stent graft 42 by a linear arrangement of openings 44 maintained by wire 46. Stent graft 42 includes fenestration 51 and bare stent 48 at proximal end 50 of stent graft 42 that is captured by apex capture assembly 52.

[0046] Retraction of wire 46 releases openings 44 from the linear arrangement shown in FIG. 4A, thereby enabling radial expansion of stent graft 42, such as by radial self-expansion of stent graft 42 as shown in FIG. 4B. Radial self-expansion of stent graft 42 can be effected by employing radially self-expanding stents, such as shown in the art. In one embodiment, for example, radially self-expanding stents can include struts that are joined at opposite ends to define proximal and distal apices, and can be fabricated of Nitinol, or some other shape memory alloy. Where stents are not radially self-expanding, they can be radially expanded by, for example, employing a balloon catheter, such as is known in the art.

[0047] Openings 44 previously aligned along 46 wire move as a consequence of radial expansion of stent graft 42, thereby separating edges of seam 74. Retraction of flexible sheath 40 from stent graft 42 as shown in FIG. 4C, completes exposure of stent graft 42. Proximal apices 68 of bare stent 48 are released by actuation of apex capture assembly 52, as can be seen in FIG. 4D, wherein proximal apex capture component 60 and nose cone 76 are separated from distal apex capture component 54 by proximal retraction of apex capture catheter 70, as can be seen in the transition from detailed views shown in FIGs. 4C(i) and 4C(ii) to FIG. 4D(i).

[0048] As shown in the detail of FIG. 4C(i), apex capture assembly 52 includes distal apex capture component 54 fixed to distal end 56 of guidewire catheter 58, and proximal apex capture component 60 defines tines 62, whereby distal apex capture component 54 and proximal apex capture component 60 together define a capture opening 64 that captures bare stent 48 at proximal apices 68 to thereby releasably secure and at least partially constrain proximal end 50 of stent graft 42. Apex capture catheter 70 of apex capture assembly 52 extends about guidewire catheter 58 and has a distal end 72 to which proximal apex capture component 60 is fixed. Bare stent 48 is thereby released from the stent graft delivery system.

[0049] FIG. 5 is an exploded view of one embodiment of a stent graft delivery system 80 of the invention. As shown therein, guidewire catheter 82 includes proximal end 84 and distal end 86. Nose cone 90 is fixed to distal end 86 of guidewire catheter 82. Flexible sheath 92 is secured to pushrod 94 and flexible sheath handle 96. Pushrod 94 includes

proximal end 98, to which flexible sheath handle 96 is fixed, and distal end 100, to which flexible sheath 92 is fixed. Wire 102 extends through openings 104 of flexible sheath 92 and extends from flexible sheath 92 along pushrod 94 to flexible sheath handle 96. Flexible sheath 92, when wire 102 extends through openings 104, causes openings 104 to have an arrangement wherein flexible sheath 92 is in a luminal configuration and has constricted diameter **D**. When in a luminal configuration, scalloped edges, as shown in FIGs. 3B, and 4B through 4D form a seam, as shown in FIGs. 3A and 4A, and define fenestration 106. Introducer sheath 110 includes proximal end 112 and distal end 114. Distal handle 116 is fixed to proximal end 112 of introducer sheath 110, and releasably fixed to guidewire catheter 82.

[0050] FIGs. 6A-6F represent successive stages of a method of the invention employing the assembled stent graft delivery system of FIG. 5 and loaded with stent graft prosthesis 120, such as that shown in FIGs. 4A-4D. Specifically, FIG. 6A is a side view in assembled form of stent graft delivery system 80 of FIG. 5, within which a stent graft (not shown) has been loaded and delivered to an aneurysm site 122 of a patient. Distal handle 116 and introducer sheath 110 are then retracted without being fixed to guidewire catheter 82, as shown in FIG. 6B, in the direction of arrow 117 to expose flexible sheath 92 and stent graft 120 at the aneurysm site 122. The diameter of stent graft 120 is thereby limited, at least in part, to diameter **D** of flexible sheath 92 prior to retraction of wire 102. In another embodiment, now shown, stent graft 120 can be delivered to aneurysm 122 by directing introducer sheath to a position distal to aneurysm 122, followed by fixing flexible sheath handle 96 to guidewire catheter 82, and advancing both in a distal direction, indicated by arrow 119, whereby stent graft 120 is advanced from introducer sheath 110 to thereby span aneurysm 122.

[0051] As can be seen in FIG. 6C, at least guidewire catheter 82, pushrod 94 and flexible sheath 92 are axially rotated about longitudinal axis 124 to thereby align fenestration 126 of stent graft 120 and fenestration 106 of flexible sheath 92 with arterial branch 128. Branch prosthesis 130 can then be implanted in fenestration 126 of stent graft prosthesis 120 and arterial branch 128 without significant interference by flexible sheath 92. Wire 102 is retracted from openings 104 of flexible sheath 92, as shown in FIG. 6D, thereby releasing openings 104 from the arrangement, in this case a linear arrangement, that causes flexible sheath 92 to have a luminal configuration of constricted radial diameter **D'**. Flexible sheath handle 96 thereafter is retracted, thereby retracting pushrod 94, causing flexible sheath 92 to be separated from stent graft 120, as shown in FIG. 6E. Stent graft 120 is then released from

stent graft delivery system 80 of the invention, such as by releasing bare stent 132 of stent graft prosthesis 120 from apex capture assembly 134, as shown in FIG. 6F. Distal handle is then fixed to guidewire 82, and retracted in proximal direction 117, whereby the remainder of stent graft delivery system 80 of the invention is retracted from stent graft 120, thereby completing treatment of the aortic aneurysm, as shown in FIG. 6G.

[0052] It is to be understood that implantation of a branch prosthesis through a fenestration of a stent graft prosthesis can be conducted by the same or a similar stent graft delivery system as that of the invention. It is also understood that branch prosthesis can be implanted after release of openings of the flexible sheath from the arrangement constraining the stent graft.

[0053] In another embodiment, the invention is a method for delivering a stent graft to an aneurysm site of a patient. In one embodiment, shown in FIGs. 7A and 7B, stent graft 140, which includes no bare stent is directed to an aneurysm site (not shown) of a patient, introducer sheath 152 is retracted from flexible sheath 142 and radially constricted stent graft 140. Stent graft 140 being radially constricted, at least in part, by a flexible sheath 142 that includes openings 144 conforming to an arrangement that causes the flexible sheath 142 to have a luminal configuration having a constricted radial diameter **D**, as shown in FIG. 7A. Openings 144 are released from the arrangement, whereby stent graft 140 is released from constraint, as shown in FIG. 7B, opening seam 152 of scalloped edge 154, thereby causing stent graft 140 to radially expand in diameter to **D'**. Stent graft 140 is thereby delivered to the aneurysm.

[0054] In one embodiment, prior to release of openings 144 from the arrangement by retraction of wire 146, flexible sheath 142, defining aperture 148 and aligned with fenestration 150 of stent graft 140 is rotated to align fenestration with an arterial branch, as shown in FIG. 8, which shows one embodiment of an implanted stent graft 152 at aneurysm site 180 by use of a stent graft stent graft delivery system and method of the invention. Thereafter, branch prostheses 154,156,158,160 can be directed through fenestrations 162,164,166,168 of stent graft 152 to respective arterial branches 170,172,174,176, shown in FIG. 8. Leg stent graft prostheses 182,184 extend from distal end 186 of stent graft 180.

[0055] Although not shown, the distal end of the vascular repair device of the invention can be bifurcated and additional prostheses can be implanted into the distal end of the bifurcated vascular prosthesis.

[0056] Vascular prostheses implanted by the stent graft systems and methods of the invention can be implanted, for example, by transfemoral access. Additional branch prostheses that are directed into the vascular prostheses of the invention can be implanted, for example, by supraaortic vessel access (e.g., through the brachial artery), or by transfemoral access, or access from some other branch or branch of major blood vessels, including peripheral blood vessels.

[0057] The teachings of all patents, published applications and references cited herein are incorporated by reference in their entirety. The relevant teachings of U.S. Patent Nos. 8,292,943; 7,763,063; 8,308,790; 8,070,790; 8,740,963; 8,007,605; 9,320,631; 8,062,349; 9,198,786; 8,062,345; 9,561,124; 9,173,755; 8,449,595; 8,636,788; 9,333,104; 9,408,734; 9,408,735; 8,500,792; 9,220,617; 9,364,314; 9,101,506; 8,998,970; 9,554,929; 9,439,751; 9,592,112; 9,655,712, 9,827,123, 9,877,857, 9,907,686; U.S. Patent Application Nos. 14/575,673; 15/166,818; 15/167,055; 14/272,818; 14/861,479; 15/478,424; 15/478,737; 15/587,664; 15/604,032; 15/672,404; 15/816,772; 15/839,272; 15/417,467; PCT/US2017/025844; PCT/US2017/025849; PCT/US2017/025912; PCT/US2017/034223 and PCT/US2017/046062, are also incorporated by reference in their entirety.

[0058] The relevant teachings of the “Delivery System For Radially Constricting a Stent Graft and Method of Use,” by Eduardo Alejandro Garcia, Attorney Docket No.: 4221.1043-001, filed on February 23, 2018; “System and Method to Radially Constrict Stent Graft,” by Samuel Arbefeuille, Attorney Docket No.: 4221.1044-001, filed on February 23, 2018; “Delivery System and Method to Radially Constrict a Stent Graft,” by Timothy Lostetter, Attorney Docket No.: 4221.1046-001, filed on February 23, 2018; “Vascular Prosthesis with Moveable Fenestration and Method of Use,” by Samuel Arbefeuille, Attorney Docket No.: 4221.1047-001, filed on February 23, 2018; “Stent Graft with Fenestration Lock and Methods of Use,” by Timothy Lostetter, Attorney Docket No.: 4221.1049-001, filed on February 23, 2018; “Stent Graft, Delivery System and Methods of Use,” by Samuel Arbefeuille and Nico Bahar, Attorney Docket No.: 4221.1050-001, filed on February 23, 2018; “Vascular Prosthesis with Crimped Adapter and Methods of Use,” by Samuel Arbefeuille, Attorney Docket No.: 4221.1052-001, filed on February 23, 2018; “Radially Adjustable Stent Graft Delivery System and Method of Use,” by Samuel Arbefeuille, Eduardo Alejandro Garcia and Scott L. Rush, Attorney Docket No.: 4221.1053-001, filed on February 23, 2018; “Vascular Prosthesis with Fenestration Ring and Methods of Use,” by Timothy Lostetter, Attorney Docket No.: 4221.1054-001, filed on February 23, 2018; “Distal

Torque Component, Delivery System and Method of Using Same," by Samuel Arbefeuille, Attorney Docket No.: 4221.1055-001, filed on February 23, 2018, are also incorporated by reference in their entirety.

[0059] While example embodiments have been particularly shown and described, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the scope of the embodiments encompassed by the appended claims.

CLAIMS

What is claimed is:

1. A stent graft delivery system, comprising:
 - a) a handle;
 - b) a guidewire catheter extending distally from the handle and having a distal end and a proximal end, and defining a longitudinal axis, the guidewire catheter being moveable relative to the handle;
 - c) an outer catheter fixed to and extending distally from the handle and about the guidewire catheter;
 - d) a flexible sheath extending between the guidewire catheter and the outer catheter and longitudinally moveable relative to the guidewire catheter and the outer catheter, wherein the flexible sheath includes openings, whereby an arrangement of the openings will cause the flexible sheath to have a luminal configuration having a constricted radial diameter; and
 - e) a ligature extending through the openings that causes the openings to conform to the arrangement, thereby configuring the flexible sheath to conform to the constricted radial diameter of the luminal configuration, the ligature being proximally retractable from the openings to thereby release the flexible sheath from the constricted radial diameter.
2. The delivery system of claim 1, wherein the openings are defined by the flexible sheath.
3. The delivery system of claim 1, wherein the openings are defined, at least in part, by loops fixed to the flexible sheath.
4. The delivery system of claim 1, wherein the arrangement includes substantial alignment along the longitudinal axis of the guidewire catheter.
5. The delivery system of claim 1, wherein the ligature is a thread, whereby the openings are aligned by tension on the thread.
6. The delivery system of claim 1, wherein the ligature is a wire.

7. The delivery system of claim 6, wherein the wire includes at least one member of the group consisting of a shape memory alloy, stainless steel, and a polymer.
8. The delivery system of claim 7, wherein the shape memory alloy includes Nitinol.
9. The delivery system of claim 8, wherein the polymer includes nylon.
10. The delivery system of claim 1, wherein the flexible sheath defines longitudinal edges, whereby the longitudinal edges at least partially form a seam and the flexible sheath defines a longitudinal lumen when the openings are aligned.
11. The delivery system of claim 10, wherein at least one of the longitudinal edges is scalloped, whereby upon alignment of the openings the flexible sheath defines a fenestration in the luminal configuration of the flexible sheath.
12. The delivery system of claim 1, wherein the flexible sheath has a luminal configuration that has an expanded radial diameter when the openings are not aligned, the expanded radial diameter being greater than the constricted radial diameter of the flexible sheath when the openings are aligned.
13. The delivery system of claim 1, further including a stent graft prosthesis within the flexible sheath, the stent graft including:
 - a) a proximal end at the distal end of the guidewire catheter, a distal end, and a wall extending about the guidewire catheter, and
 - b) a plurality of stents fixed to and distributed along the wall of the stent graft, wherein the stent graft is radially constricted when the openings of the flexible sheath are aligned.
14. The delivery system of claim 13, wherein the flexible sheath defines a fenestration when the openings are substantially aligned, and the wall of the stent graft prosthesis defines a fenestration that is substantially aligned with the fenestration of the flexible sheath.
15. The delivery system of claim 14, wherein the stent graft further includes a bare stent at the proximal end of the stent graft, the bare stent including struts that define proximal apices.

16. The delivery system of claim 15, further including an apex capture assembly that releasably captures the proximal apices of the bare stent.
17. The delivery system of claim 16, wherein the apex capture assembly includes a distal apex capture component fixed to the distal end of the guidewire catheter, a proximal apex capture component whereby the distal and proximal apex capture component together define a capture opening that captures the proximal apices of the bare stent to thereby releasably capture and at least partially constrain the proximal end of the stent graft, and an apex capture catheter extending about the guidewire catheter and having a distal end to which the proximal apex capture component is fixed, whereby the proximal apices of the bare stent and, consequently, the proximal apex capture component can be released when the apex capture catheter is retracted from the distal apex capture component.
18. A method for delivering a stent graft prosthesis to an aneurysm site of a patient, comprising the steps of:
 - a) directing a stent graft to an aneurysm site of a patient by a delivery system, the stent graft being radially constricted, at least in part, by a flexible sheath of the delivery system that includes openings conforming to an arrangement that causes the flexible sheath to have a luminal configuration having a constricted radial diameter; and
 - b) releasing the openings from the arrangement whereby the stent graft is released from radial constriction by the flexible sheath, thereby delivering the stent graft to the aneurysm site.
19. The method of claim 18, wherein the delivery system further includes:
 - a) a handle;
 - b) a guidewire catheter extending distally from the handle and having a distal end and a proximal end, and defining a longitudinal axis, the guidewire catheter being moveable relative to the handle;
 - c) an outer catheter, fixed to and extending distally from the handle and about the guidewire catheter, and wherein the flexible sheath extends between the guidewire catheter and the outer catheter and is longitudinally moveable relative to the guidewire catheter and the outer catheter; and

- d) a ligature extending through the openings that causes the openings to conform to the arrangement, thereby causing the flexible sheath to conform to the constricted radial diameter of the luminal configuration, the ligature being proximally retractable from the openings to thereby release the flexible sheath from constricted radial diameter.
- 20. A method of claim 19, wherein the openings are defined by the flexible sheath.
- 21. A method of claim 19, wherein the openings are defined, at least in part, by loops fixed to the flexible sheath.
- 22. A method of claim 19, wherein the arrangement includes substantial alignment along the longitudinal axis of the guidewire catheter.
- 23. A method of claim 19, wherein the ligature is a thread, whereby the openings are aligned by tension on the thread.
- 24. A method of claim 19, wherein the ligature is a wire.
- 25. A method of claim 24, wherein the wire includes at least one member of the group consisting of a shape memory alloy, stainless steel, and a polymer.
- 26. A method of claim 25, wherein the shape memory alloy includes Nitinol.
- 27. The method of claim 26, wherein the polymer includes nylon.
- 28. The method of claim 19, wherein the flexible sheath defines longitudinal edges, whereby the longitudinal edges at least partially form a seam and the flexible sheath defines a longitudinal lumen when the openings are aligned.
- 29. The method of claim 28, wherein at least one of the longitudinal edges is scalloped, whereby upon alignment of the openings the flexible sheath defines a fenestration in the luminal configuration of the flexible sheath.
- 30. The method of claim 19, wherein the flexible sheath has a luminal configuration that has an expanded radial diameter when the openings are not aligned, the expanded radial diameter being greater than the constricted radial diameter of the flexible sheath.

31. The method of claim 19, wherein the stent graft prosthesis is within the flexible sheath and at least a portion of the radial stents are radially self-expanding.
32. The method of claim 31, wherein the flexible sheath defines a fenestration when the flexible sheath is radially constricted by the arrangement, and the wall of the stent graft prosthesis defines a fenestration that is substantially aligned with the fenestration of the flexible sheath.
33. The method of claim 32, wherein the stent graft further includes a bare stent at the proximal end of the stent graft, the bare stent including struts that define proximal apices.
34. The method of claim 33, wherein the delivery system further includes an apex capture assembly that releasably captures the proximal apices of the bare stent.
35. The method of claim 34, wherein the apex capture assembly includes a distal apex capture component fixed to the distal end of the guidewire catheter, a proximal apex capture component, whereby the distal and proximal apex capture component together define a capture opening that captures the proximal apices of the bare stent to thereby releasably secure and at least partially constrain the proximal end of the stent graft, and an apex capture catheter extending about the guidewire catheter and having a distal end to which the proximal apex capture component is fixed, whereby the proximal apices of the bare stent and, consequently, the proximal apex capture component can be released when the apex capture catheter is retracted from the distal apex capture component.





FIG. 2A











FIG. 2B









FIG. 4C(*i*)FIG. 4C(*ii*)










FIG. 8

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2018/019354

A. CLASSIFICATION OF SUBJECT MATTER
INV. A61F2/97
ADD. A61F2/07

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 8 236 040 B2 (MAYBERRY KEVIN [US]) 7 August 2012 (2012-08-07)	1,2,4-7, 10,12, 13,15
Y	column 10, line 18 - column 22, line 46; figures 2-11d -----	3,8,16, 17
X	US 2008/269867 A1 (JOHNSON ERIC GERARD [US]) 30 October 2008 (2008-10-30) ----- paragraphs [0029] - [0045]; figures 1-5a -----	1,2,4,6, 7,9,10, 12-14
X	US 8 641 752 B1 (HOLM BRIAN C [US] ET AL) 4 February 2014 (2014-02-04) column 3, line 51 - column 5, line 52; claim 4; figures 1-6 ----- -/-	1,2,4-7, 10-12

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance
"E" earlier application or patent but published on or after the international filing date
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
"O" document referring to an oral disclosure, use, exhibition or other means
"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

Date of mailing of the international search report

26 April 2018

07/05/2018

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Porta, Marcello

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2018/019354

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5 755 769 A (RICHARD THIERRY [FR] ET AL) 26 May 1998 (1998-05-26) column 3, line 65 - column 4, line 5; figure 8 -----	3
Y	US 2013/123900 A1 (EBLACAS JULIO E [US] ET AL) 16 May 2013 (2013-05-16) paragraph [0053]; figure 2 -----	8
A		1
Y	US 2011/257720 A1 (PETERSON SUSAN REA [US] ET AL) 20 October 2011 (2011-10-20) paragraphs [0134] - [0136]; figures 16a-16c -----	16,17

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US2018/019354

Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. Claims Nos.: 18-35 because they relate to subject matter not required to be searched by this Authority, namely:
Claims 18-35 are considered a method for treatment of the human or animal body by surgery (Rule 39.1(iv) PCT) as they involve the insertion and implantation of an implant to an implantation site.
2. Claims Nos.: because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. Claims Nos.: because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. As all searchable claims could be searched without effort justifying an additional fees, this Authority did not invite payment of additional fees.
3. As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.

The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.

No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2018/019354

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
US 8236040	B2	07-08-2012		EP 2268227 A2 JP 5722764 B2 JP 2011516215 A US 2009259298 A1 US 2011224772 A1 US 2013138200 A1 WO 2009126906 A2		05-01-2011 27-05-2015 26-05-2011 15-10-2009 15-09-2011 30-05-2013 15-10-2009
US 2008269867	A1	30-10-2008		AU 2008241571 A1 CA 2683011 A1 EP 2139436 A2 EP 3037062 A1 ES 2581215 T3 JP 5123376 B2 JP 2010524630 A US 2008269867 A1 WO 2008130503 A2		30-10-2008 30-10-2008 06-01-2010 29-06-2016 02-09-2016 23-01-2013 22-07-2010 30-10-2008 30-10-2008
US 8641752	B1	04-02-2014		US 8641752 B1 US 2014107760 A1		04-02-2014 17-04-2014
US 5755769	A	26-05-1998		AT 155993 T CA 2102416 A1 DE 69312601 D1 DE 69312601 T2 EP 0584352 A1 FR 2688401 A1 JP 3901725 B2 JP H06511408 A JP 2007007442 A US 5755769 A US 6019787 A WO 9317636 A1		15-08-1997 13-09-1993 04-09-1997 26-02-1998 02-03-1994 17-09-1993 04-04-2007 22-12-1994 18-01-2007 26-05-1998 01-02-2000 16-09-1993
US 2013123900	A1	16-05-2013		AU 2012339653 A1 BR 112014011679 A2 CA 2854189 A1 CN 103945798 A EP 2779960 A1 ES 2588370 T3 HK 1202044 A1 JP 6189852 B2 JP 2014533554 A KR 20140096366 A RU 2014124116 A US 2013123900 A1 WO 2013074646 A1		08-05-2014 16-05-2017 23-05-2013 23-07-2014 24-09-2014 02-11-2016 18-09-2015 30-08-2017 15-12-2014 05-08-2014 27-12-2015 16-05-2013 23-05-2013
US 2011257720	A1	20-10-2011		EP 2560585 A1 JP 5927618 B2 JP 2013524934 A US 2011257720 A1 US 2014257471 A1 US 2018008401 A1 WO 2011133271 A1		27-02-2013 01-06-2016 20-06-2013 20-10-2011 11-09-2014 11-01-2018 27-10-2011