



US 20160114229A1

(19) **United States**

(12) **Patent Application Publication**

Jertson et al.

(10) **Pub. No.: US 2016/0114229 A1**

(43) **Pub. Date: Apr. 28, 2016**

(54) **GOLF CLUB HEADS WITH ENERGY STORAGE CHARACTERISTICS**

(71) Applicant: **Karsten Manufacturing Corporation**,
Phoenix, AZ (US)

(72) Inventors: **Martin R. Jertson**, Phoenix, AZ (US);
Eric J. Morales, Laveen, AZ (US); **Cory S. Bacon**, Cave Creek, AZ (US); **Calvin Wang**, Chandler, AZ (US); **Xiaojian Chen**, Phoenix, AZ (US)

(21) Appl. No.: **14/920,484**

(22) Filed: **Oct. 22, 2015**

Related U.S. Application Data

(60) Provisional application No. 62/206,152, filed on Aug. 17, 2015, provisional application No. 62/131,739, filed on Mar. 11, 2015, provisional application No. 62/105,460, filed on Jan. 20, 2015, provisional application No. 62/105,464, filed on Jan. 20, 2015, provisional application No. 62/068,232, filed on Oct. 24, 2014.


Publication Classification



(51) **Int. Cl.**
A63B 53/04 (2006.01)
(52) **U.S. Cl.**
CPC *A63B 53/0466* (2013.01); *A63B 2053/0433* (2013.01)

(57)

ABSTRACT

Embodiments of golf club heads with energy storage characteristics are presented herein. In some embodiments, a golf club head comprises a hollow body comprising a strikeface, a heel region, a toe region opposite the heel region, a sole, and a crown. In many embodiments, the crown comprises an upper region comprising a top rail and a lower region. In some embodiments, a cavity is located below the top rail, is located above the lower region of the crown, and is defined at least in part by the upper and lower regions of the crown. The cavity comprises a top wall, a back wall, a bottom incline, a back cavity angle measured between the top and back walls of the cavity and at least one channel.








Fig. 3





Fig. 5




Fig. 4




Fig. 6




Fig. 7





Fig. 8



900

Fig. 9




Fig. 10





Fig. 11



1000

Fig. 12




Fig. 13





Fig. 14






Fig. 16

PROVIDING A BODY, THE BODY HOUSING,
A STRIKEFACE, A HEEL REGION, A TOE
REGION OPPOSITE THE HEEL REGION, A
SOLE, AND A CROWN COMPRISING AN UPPER
REGION COMPRISING A TOP RAIL AND
A LOWER REGION

-1705

PROVIDING A CAVITY LOCATED BELOW THE
TOP RAIL, ABOVE THE LOWER REGION OF THE
CROWN, AND IS DEFINED AT LEAST IN PART BY
THE UPPER AND LOWER REGIONS OF THE CROWN

-1710

1700
Fig. 17




Fig. 18




Fig. 19





Fig. 20



1000

Fig. 21

GOLF CLUB HEADS WITH ENERGY STORAGE CHARACTERISTICS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This claims priority to U.S. Provisional Application No. 62/206,152, filed Aug. 17, 2015, U.S. Provisional Application No. 62/131,739, filed Mar. 11, 2015, U.S. Provisional Application No. 62/105,460, filed Jan. 20, 2015, U.S. Provisional Application No. 62/105,464, filed Jan. 20, 2015, and U.S. Provisional Application No. 62/068,232, filed Oct. 24, 2014, all of which are incorporated by reference herein in their entirety.

TECHNICAL FIELD

[0002] This disclosure relates generally to golf clubs, and relates more particularly to golf club heads with energy storage characteristics.

BACKGROUND

[0003] Golf club manufacturers have designed golf club heads to relieve stress in the strikeface of the golf club head. In many instances, these designs do not allow the golf club head to flex in the crown to sole direction. Additionally, these designs may not change where peak bending of the golf club head occurs and do not allow additional storage of spring energy in the golf club head due to impact with the golf ball. Additional spring energy can increase ball speed across the strikeface.

BRIEF DESCRIPTION OF THE DRAWINGS

[0004] To facilitate further description of the embodiments, the following drawings are provided in which:

[0005] FIG. 1 depicts a front, crown-side perspective view of a golf club head according to an embodiment;

[0006] FIG. 2 depicts the golf club head of FIG. 1 along the cross-sectional line II-II in FIG. 1;

[0007] FIG. 3 depicts a view of a portion of a golf club head that is similar to the golf club head of FIG. 1, along a cross-sectional line similar to the cross-sectional line II-II in FIG. 1, according to another embodiment;

[0008] FIG. 4 depicts a view of a portion of a golf club head that is similar to the golf club head of FIG. 1, along a cross-sectional line similar to the cross-sectional line II-II in FIG. 1, according to another embodiment;

[0009] FIG. 5 depicts a view of a portion of a golf club head that is similar to the golf club head of FIG. 1, along a cross-sectional line similar to the cross-sectional line II-II in FIG. 1, according to another embodiment;

[0010] FIG. 6 depicts a view of another portion of a golf club head that is similar to the golf club head of FIG. 1, along a cross-sectional line similar to the cross-sectional line II-II in FIG. 1, according to another embodiment;

[0011] FIG. 7 depicts a cross-sectional view of a golf club similar to the golf club head of FIG. 1 along a similar cross-sectional line as the cross-sectional line VII-VII in FIG. 1, according to another embodiment;

[0012] FIG. 8 depicts a view of a portion of a golf club head similar to the golf club head of FIG. 4, according to an embodiment, and a view of the same area of a standard golf club head;

[0013] FIG. 9 depicts a method of manufacturing a golf club head according to an embodiment of a method.

[0014] FIG. 10 depicts a back, toe-side perspective view of a golf club head according to an embodiment;

[0015] FIG. 11 depicts a back, heel-side perspective view of the golf club head according to the embodiment of FIG. 10;

[0016] FIG. 12 depicts a cross-sectional view of the golf club head of FIG. 10 along the cross-sectional line XII-XII of FIG. 10;

[0017] FIG. 13 depicts a view of a portion of the golf club head of FIG. 12 and a view of the same area of a standard golf club head;

[0018] FIG. 14 depicts a cross-section view of a golf club head, similar to the golf club head of FIG. 10, along a cross-sectional line similar to cross-sectional line XII-XII of FIG. 10, according to another embodiment;

[0019] FIG. 15 depicts a back, toe-side perspective view of a golf club according to another embodiment;

[0020] FIG. 16 depicts a cross-sectional view of the golf club head of FIG. 15 along the cross-sectional line XVI-XVI of FIG. 15;

[0021] FIG. 17 depicts a flow diagram illustrating a method of manufacturing a golf club head according to an embodiment of another method;

[0022] FIG. 18 depicts a front perspective view of a golf club according to another embodiment;

[0023] FIG. 19 depicts results from testing of the golf club head of FIG. 14, according to another embodiment; and

[0024] FIG. 20 depicts results from testing of the golf club head of FIG. 14, according to another embodiment.

[0025] FIG. 21 depicts a cross sectional view of the golf club head of FIG. 10.

[0026] For simplicity and clarity of illustration, the drawing figures illustrate the general manner of construction, and descriptions and details of well-known features and techniques may be omitted to avoid unnecessarily obscuring the golf clubs and their methods of manufacture. Additionally, elements in the drawing figures are not necessarily drawn to scale. For example, the dimensions of some of the elements in the figures may be exaggerated relative to other elements to help improve understanding of embodiments of the golf clubs and their methods of manufacture. The same reference numerals in different figures denote the same elements.

[0027] The terms "first," "second," "third," "fourth," and the like in the description and in the claims, if any, are used for distinguishing between similar elements and not necessarily for describing a particular sequential or chronological order. It is to be understood that the terms so used are interchangeable under appropriate circumstances such that the embodiments of golf clubs and methods of manufacture described herein are, for example, capable of operation in sequences other than those illustrated or otherwise described herein. Furthermore, the terms "contain," "include," and "have," and any variations thereof, are intended to cover a non-exclusive inclusion, such that a process, method, article, or apparatus that comprises a list of elements is not necessarily limited to those elements, but may include other elements not expressly listed or inherent to such process, method, article, or apparatus.

[0028] The terms "left," "right," "front," "back," "top," "bottom," "side," "under," "over," and the like in the description and in the claims, if any, are used for descriptive purposes and not necessarily for describing permanent relative positions. It is to be understood that the terms so used are interchangeable under appropriate circumstances such that the embodiments of golf clubs and methods of manufacture

described herein are, for example, capable of operation in other orientations than those illustrated or otherwise described herein. The term "coupled," as used herein, is defined as directly or indirectly connected in a physical, mechanical, or other manner.

DESCRIPTION OF EXAMPLES OF EMBODIMENTS

[0029] Various embodiments of the golf club heads with tiered internal thin sections include a golf club head comprising a body. The body comprises a strikeface, a heel region, a toe region opposite the heel region, a sole, a crown, and an internal radius transition region from the strikeface to at least one of the sole or the crown. In many embodiments, the internal radius transition region is not visible from an exterior of the golf club head and comprises a first tier, a second tier, and a tier transition region between the first tier and the second tier.

[0030] Another embodiment of the golf club heads with tiered internal thin sections include a golf club comprising a golf club head and a shaft coupled to the golf club head. The golf club head comprises a strikeface, a heel region, a toe region opposite the heel region, a sole, a crown, and an internal radius transition region from the strikeface to at least one of the sole or the crown. In many embodiments, the internal radius transition region is not visible from an exterior of the golf club head and comprises a first tier, a second tier, and a tier transition region between the first tier and the second tier.

[0031] Other embodiments of the golf club heads with tiered internal thin sections include a method for manufacturing a golf club head. The method comprises providing a body. The body comprises a strikeface, a heel region, a toe region opposite the heel region, a sole, and a crown. The method further comprises providing an internal radius transition region from the strikeface to at least one of the sole or the crown. The internal radius transition region is not visible from an exterior of the golf club head and comprises a first tier, a second tier, and a tier transition region between the first tier and the second tier. In many embodiments, the first tier has a first thickness, the second tier has a second thickness, and the second thickness is smaller than the first thickness.

[0032] Various embodiments include a golf club head comprising a hollow body. The hollow body comprises a strikeface, a heel region, a toe region opposite the heel region, a sole, and a crown. In many embodiments, the crown comprises an upper region comprising a top rail, and a lower region. In some embodiments, a cavity is located below the top rail, is located above the lower region of the crown, and is defined at least in part by the upper and lower regions of the crown. In many embodiments, the cavity comprises a top wall, a back wall, a bottom incline, a back cavity angle measured between the top and back walls of the cavity, and at least one channel.

[0033] Some embodiments include a golf club comprising a hollow-bodied golf club and a shaft coupled to the hollow-bodied golf club head. The hollow-bodied golf club head comprises a strikeface, a heel region, a toe region opposite the heel region, a sole, and a crown. In many embodiments, the crown comprises an upper region comprising a top rail, and a lower region. In some embodiments, a cavity is located below the top rail, is located above the lower region of the crown, and is defined at least in part by the upper and lower regions of the crown. In many embodiments, the cavity comprises a

top wall, a back wall, a bottom incline, a back cavity angle measured between the top and back walls of the cavity, and at least one channel.

[0034] Other embodiments include a method for manufacturing a golf club head. In many embodiments, the method comprises providing a body. The body having a strikeface, a heel region, a toe region opposite the heel region, a sole, and a crown. The crown comprises an upper region comprising a top rail and a lower region. In some embodiments, a cavity is located below the top rail, above the lower region of the crown, and is defined at least in part by the upper and lower regions of the crown. In many embodiments, the cavity comprises a top wall, a back wall adjacent to the top wall, a bottom incline adjacent to the back wall, a back cavity angle measured between the top and back walls of the cavity, and at least one channel.

[0035] Other examples and embodiments are further disclosed herein. Such examples and embodiments may be found in the figures, in the claims, and/or in the present description.

I. Golf Club Head with Cascading Sole

[0036] Turning to the drawings, FIG. 1 illustrates an embodiment of a golf club head 100. Golf club head 100 can be a wood-type golf club head. For example, golf club head 100 can be a fairway wood-type golf club head or a driver-type golf club head or a hybrid-type golf club head or an iron-type golf club head. Golf club head 100 comprises a body 101. Body 101 comprises a strikeface 112, a heel region 102, a toe region 104, a sole 106, and a crown 108. In FIG. 1, body 101 also comprises a skirt 110 extending between sole 106 and crown 108. In some embodiments, body 101 does not comprise skirt 110 or any skirt. FIG. 18 depicts a front perspective view of a golf club 1800 according to an embodiment. In some embodiments, golf club 1800 comprises golf club head 100 and a shaft 190.

[0037] In some embodiments, body 101 can comprise stainless steel, titanium, aluminum, a steel alloy (e.g. 455 steel, 475 steel, 431 steel, 17-4 stainless steel, maraging steel), a titanium alloy (e.g. Ti 7-4, Ti 6-4, T-9S), an aluminum alloy, or a composite material. In some embodiments, strikeface 112 can comprise stainless steel, titanium, aluminum, a steel alloy (e.g. 455 steel, 475 steel, 431 steel, 17-4 stainless steel, maraging steel), a titanium alloy (e.g. Ti 7-4, Ti 6-4, T-9S), an aluminum alloy, or a composite material. In some embodiments, body 101 can comprise the same material as strikeface 112. In some embodiments, body 101 can comprise a different material than strikeface 112.

[0038] FIG. 2 illustrates a cross-section of golf club head 100 along the cross-sectional line II-II in FIG. 1, according to one embodiment. FIG. 2 shows an internal radius transition 210 from strikeface 112 to sole 106, according to an embodiment. Internal radius transition 210 can comprise a smooth transition, or internal radius transition 210 can comprise a cascading sole of at least two tiers or levels of thickness. For example, internal radius transition 210 can comprise a cascading sole having 2, 3, 4, 5, 6, or 7 tiers. In some embodiments, internal radius transition can provide more bending of strikeface 112. In some examples, the increase in bending or deflection of strikeface 112 can allow approximately 1% to approximately 3% more energy from the deflection of strikeface 112.

[0039] In many embodiments, internal radius transition 210 is not visible from an exterior of golf club head 100. FIG. 2 also shows a top internal radius transition 260 from strike-

face 112 to crown 108. In some embodiments, top internal radius transition 260 can comprise a smooth transition, while in other embodiments, top internal radius transition 260 can comprise at least two tiers or levels of thickness. For example, top internal radius transition 260 can comprise 2, 3, 4, 5, 6, or 7 tiers or levels of thickness. In some embodiments, golf club head 100 also can have an internal sole thickness 220. Internal sole thickness 220 can be thicker than the smallest thickness of internal radius transition 210. In many embodiments, internal sole thickness 220 also is thicker than an adjacent tier or a final tier in internal radius transition 210. In some embodiments, internal sole thickness 220 can be thicker than all of internal radius transition 210.

[0040] In some embodiments, internal radius transition 210 can be similar to the sole front section and/or the weight distribution channels as described in U.S. Pat. No. 8,579,728, entitled Golf Club Heads with Weight Redistribution Channels and Related Methods, which is incorporated by reference herein.

[0041] In some embodiments, the golf club head can comprise a cascading transition region, tiered transition region or internal radius transition from the strikeface to at least one of a crown, a heel, a toe, a sole, or a skirt. In some embodiments, the golf club head can comprise a single, continuous tiered transition region ring around a circumference of perimeter of the golf club head, for example a tiered transition region ring from the strikeface to each of the crown, the toe region, the heel region, and the sole region. In other embodiments, the golf club head comprises a tiered transition region only at the crown and/or at the sole. In some embodiments, the golf club head comprises a tiered transition region only at the toe region and/or at the heel region. In other examples, the tiered transition region is only located from the strikeface to the skirt. In other embodiments, the golf club head comprises separate or individual tiered transition regions from the strikeface to the toe region of the crown, the heel region of the crown, the toe region of the sole, and/or the heel region of the sole.

[0042] FIG. 3 depicts a view of an internal radius transition 310 of a golf club head 300 that is similar to the golf club head of FIG. 1, along a cross-sectional line similar to the cross-sectional line II-II in FIG. 1, according to another embodiment. FIG. 4 depicts a view of an internal radius transition 410 of a golf club head 400 that is similar to the golf club head of FIG. 1, along a cross-sectional line similar to the cross-sectional line II-II in FIG. 1, according to another embodiment. FIG. 5 depicts a view of an internal radius transition 510 of a golf club head 500 that is similar to the golf club head of FIG. 1, along a cross-sectional line similar to the cross-sectional line II-II in FIG. 1, according to another embodiment.

[0043] As shown in FIG. 3, internal radius transition 310 can be similar to internal radius transition 210 (FIG. 2) and golf club head 300 can be similar to golf club head 100 (FIGS. 1 and 2). Internal radius transition 310 comprises a first tier 315 having a first thickness, and a second tier 317 having a second thickness. In many embodiments, the thickness of each tier is substantially constant. For example, the first thickness of first tier 315 can comprise a first substantially constant thickness, and the second thickness of second tier 317 can comprise a second substantially constant thickness. In other embodiments, first tier 315 can comprise a first slope, wherein the first thickness of first tier 315 is thicker closer to strikeface 312 and thinner closer to a tier transition region 316. Tier transition region 316 can comprise a tier

slope that is steeper than the first slope of first tier 315. Tier transition region 316 can be linearly sloped at an angle less than 90 degrees to transition from first tier 315 to second tier 317. In other embodiments, tier transition region 316 can comprise an approximately 90 degree step, as shown in tier transition regions 516 and 518 of FIG. 5. Tier transition region 516 (FIG. 5) and 518 (FIG. 5) can be similar to tier transition region 316 (FIG. 3), and tier transition regions 416 (FIG. 4) and 418 (FIG. 4).

[0044] As shown in FIG. 4, in some embodiments, each tiered transition 316, 416, 418, 516, 518 can include a first arcuate surface 420 and a second arcuate surface 422. The first arcuate surface 420 has a first radius of curvature and the second arcuate surface 422 has a second radius of curvature. The first radius of curvature and the second radius of curvature of each tiered transition 316, 416, 418, 516, 518 can be the same, or the first radius of curvature and the second radius of curvature of each tiered transition 316, 416, 418, 516, 518 can be different. For example, the first radius of curvature of the first arcuate surface 420 can be the same as the second radius of curvature of the first arcuate surface 420, the first radius of curvature of the first arcuate surface 420 can be less than the second radius of curvature of the first arcuate surface 420, or the first radius of curvature of the first arcuate surface 420 can be greater than the second radius of curvature of the first arcuate surface 420. For further example, the first radius of curvature of the second arcuate surface 422 can be the same as the second radius of curvature of the second arcuate surface 422, the first radius of curvature of the second arcuate surface 422 can be less than the second radius of curvature of the second arcuate surface 422, or the first radius of curvature of the second arcuate surface 422 can be greater than the second radius of curvature of the second arcuate surface 422.

[0045] Further, each of the tiered transitions 316, 416, 418, 516, 518 can have the same first radius of curvature or a different first radius of curvature, and each of the tiered transitions 316, 416, 418, 516, 518 can have the same second radius of curvature or a different second radius of curvature. For example, the first radius of curvature of the first arcuate surface 420 can be the same as the first radius of curvature of the second arcuate surface 422, the first radius of curvature of the first arcuate surface 420 can be less than the first radius of curvature of the second arcuate surface 422, or the first radius of curvature of the first arcuate surface 420 can be greater than the first radius of curvature of the second arcuate surface 422. For further example, the second radius of curvature of the first arcuate surface 420 can be the same as the second radius of curvature of the second arcuate surface 422, the second radius of curvature of the first arcuate surface 420 can be less than the second radius of curvature of the second arcuate surface 422, or the second radius of curvature of the first arcuate surface 420 can be greater than the second radius of curvature of the second arcuate surface 422.

[0046] The internal radius transition features (e.g. internal tier transition 310, FIG. 3) can change where a peak bending of a golf club head occurs. The tiered transition region can create a “plastic hinge” at the peak bending, promoting more localized deformation due to impact with the golf ball. In many embodiments, the buckling process starts at the location of the peak bending and the golf club head is optimized to stay just under the critical buckling threshold. The intentional plastic hinge allows the club to flex more in the crown

and sole direction. Intentional Plastic Hinge allows control over exactly where and how much the crown and sole will flex by using the tiered features.

[0047] Using the internal radius transition, the stress of the golf club head can be distributed across a larger volume of material, thus lowering the localized peak stress. In many embodiments, the additional flex from crown to sole allows the face to bend further based on the same loading. This additional flex can generate more stress and bending in the face of the club to create more spring energy. An increase in spring energy can be stored in the golf club head due to an impact with the golf ball. In many embodiments, the additional spring energy will help to increase ball speed. In some embodiments, the internal radius transition can create more overall bending in the golf club head, which also can lead to more ball speed. Higher ball speeds across the strikeface can result in better distance control. In some embodiments, the golf club head with internal radius transition features can store approximately 4% to approximately 6% more energy, which can then be returned to the golf ball.

[0048] Returning to FIG. 3, internal radius transition 310 can change where a peak bending 350 of the sole of golf club head 300 occurs. In addition, internal radius transition 310 can engage more of the body of club head 300 in the bending process on impact from a golf ball. In some embodiments, first tier 315 and second tier 317 allow some of the stress created by an impact of strikeface 312 with the golf ball to build up on each tier. This structure can prevent the stress from collecting primarily at the thinnest section of the sole to increase the reliability and durability of golf club head 300. In many embodiments, this structure creates a plastic hinge opposite the strikeface end of internal radius transition 310 and promotes more localized deformation at the plastic hinge location. In many embodiments, the plastic hinge can be located at the peak bending, for example, peak bending 350. This structure also can allow for the storage of more potential energy, for example, in the crown and/or the sole. In some embodiments, body 301 can experience an increase of approximately 4% to approximately 7% in flex or bending in the crown to sole direction at the sole and/or the crown. The additional flex in the crown to sole direction at the sole and/or the crown can allow strikeface 312 to bend further on the same loading or impact by the golf ball. Therefore, this structure can create more stress and bending in strikeface 312 of golf club head 300 that can be transferred to the ball on impact with the strikeface 312.

[0049] In some embodiments, each tier comprises an approximately constant thickness throughout the tier. In many embodiments, first tier 315 is thicker than second tier 317. In some embodiments of a driver-type golf club head, first tier 315 can be approximately 0.030 inch (0.076 cm) to approximately 0.060 inch (0.152 cm) thick, or approximately 0.040 inch (0.102 cm) to approximately 0.050 inch (0.127 cm) thick, and second tier 317 can be approximately 0.020 inch (0.051 cm) to approximately 0.050 inch thick (0.127 cm), or approximately 0.030 inch (0.076 cm) to approximately 0.040 inch (0.102 cm) thick. In some embodiments of a fairway wood-type golf club head, first tier 315 can be approximately 0.035 inch (0.089 cm) to approximately 0.065 inch (0.165 cm) thick, or approximately 0.045 inch (0.114 cm) to approximately 0.055 inch (0.140 cm) thick, and second tier 317 can be approximately 0.025 inch (0.064 cm) to approximately 0.055 inch (0.140 cm) thick, or approximately 0.035 inch (0.089 cm) to approximately 0.045 inch (0.114 cm) thick.

cm) thick. In some embodiments of a hybrid-type golf club head, first tier 315 can be approximately 0.050 inch (0.127 cm) to approximately 0.080 inch (0.203 cm) thick, or approximately 0.060 inch (0.152 cm) to approximately 0.070 inch thick (0.178 cm), and second tier 317 can be approximately 0.040 inch (0.102 cm) to approximately 0.070 inch (0.178 cm) thick, or approximately 0.050 inch (0.127 cm) to approximately 0.060 inch (0.152 cm) thick. In many embodiments of an iron-type golf club head, the first tier 315 can be approximately 0.055 inch (0.140 cm) to approximately 0.085 inch (0.216 cm) thick, or approximately 0.060 inch (0.152 cm) to approximately 0.080 inch thick (0.203 cm), and the second tier 317 can be approximately 0.045 inch (0.114 cm) to approximately 0.075 inch (0.191 cm) thick, or approximately 0.050 inch (0.127 cm) to approximately 0.070 inch (0.178 cm) thick.

[0050] In other embodiments, such as shown in FIG. 4, internal radius transition 410 can have more than 2 tiers. For example, internal radius transition 410 can have 2, 3, 4, 5, 6, or 7 tiers. A three tier internal radius transition 410 can be similar to internal radius transition 310 (FIG. 3) and has a first tier 415, a second tier 417, and a third tier 419. First tier 415 can be similar to first tier 315 in FIG. 3, and second tier 417 can be similar to second tier 317. In many embodiments, a peak bending 450 can occur further back from strikeface 412 as more tiers are added to the internal radius transition.

[0051] In many embodiments, second tier 417 is thicker than third tier 419. In some embodiments of a driver-type golf club head, third tier 419 is approximately 0.010 inch to approximately 0.040 inch (0.102 cm) thick, or approximately 0.020 inch (0.051 cm) to approximately 0.030 inch (0.076 cm) thick. In some embodiments of a fairway wood-type golf club head, third tier 419 is approximately 0.015 inch (0.038 cm) to approximately 0.045 inch (0.114 cm) thick, or approximately 0.025 inch (0.064 cm) to approximately 0.035 inch (0.089 cm) thick. In some embodiments of a hybrid-type golf club head, third tier 419 is approximately 0.030 inch (0.076 cm) to approximately 0.060 inch (0.152 cm) thick, or approximately 0.040 inch (0.102 cm) to approximately 0.050 inch (0.127 cm) thick. In some embodiments of an iron-type club head the third tier 419 is approximately 0.030 inch (0.076 cm) to approximately 0.060 inch (0.152 cm) thick, or approximately 0.035 inch (0.089 cm) to approximately 0.055 inch (0.140 cm) thick.

[0052] Meanwhile, referring to FIG. 5, in some embodiments of a driver-type golf club head, first tier 515 can be approximately 0.045 inch (0.114 cm) thick; second tier 517 can be approximately 0.035 inch (0.089 cm) thick; and third tier 519 can be approximately 0.025 inch (0.064 cm) thick. In some embodiments of a fairway wood-type golf club head, first tier 515 can be approximately 0.051 inch (0.130 cm) thick; second tier 517 can be approximately 0.039 inch (0.099 cm) thick; and third tier 519 can be approximately 0.030 inch (0.076 cm) thick. In some embodiments of a hybrid-type golf club head, first tier 515 can be approximately 0.067 inch (0.170 cm) thick; second tier 517 can be approximately 0.054 inch (0.137 cm) thick; and third tier 519 can be approximately 0.045 inch (0.114 cm) thick. In some embodiments of an iron-type club head, the first tier 515 can be approximately 0.067 inch (0.170 cm) thick; the second tier can be approximately 0.057 inch (0.145 cm) thick; and the third tier 519 can be approximately 0.042 inch (0.107 cm) thick.

[0053] In some embodiments, first tiers 315, 415, 515 in FIGS. 3, 4, and 5, respectively, can have a first tier length that

is approximately equal to a second tier length of second tiers **317, 417, 517** in FIGS. 3, 4, and 5, respectively. In some embodiments, the first tier length of first tiers **315, 415, 515** in FIGS. 3, 4, and 5, respectively, can have a first tier length that is longer than the second tier length of second tiers **317, 417, 517**. In other embodiments, the second tier length of second tiers **417, 517** in FIGS. 4 and 5, respectively, can be approximately equal to a third tier length of third tiers **419, 519** in FIGS. 4 and 5, respectively. In some embodiments, the second tier length of second tiers **417, 517** in FIGS. 4 and 5, respectively, can be longer than the third tier length of third tiers **419, 519** in FIGS. 4 and 5, respectively. In other embodiments, the second tier length of second tiers **417, 517** in FIGS. 4 and 5, respectively, can be shorter than the third tier length of third tiers **419, 519** in FIGS. 4 and 5, respectively.

[0054] Referring to FIGS. 3, 4, and 5, in some embodiments of a fairway wood-type golf club head or a driver-type golf club head or a hybrid-type golf club head, the first tiers **315, 415, 515** can have first tier lengths of approximately 0.05 inch (0.127 cm) to approximately 0.80 inch (2.03 cm); the second tiers **317, 417, 517** can have second tier lengths of approximately 0.03 inch (0.076 cm) to approximately 0.60 inch (1.52 cm); and the third tiers **419, 519** can have third tier lengths of approximately 0.04 inch (0.102 cm) to approximately 0.70 inch (1.78 cm). In some embodiments of an iron-type golf club head, the first tiers **315, 415, 515** can have first tier lengths of approximately 0.03 inch (0.076 cm) to approximately 0.30 inch (0.762 cm); the second tiers **317, 417, 517** can have second tier lengths of approximately 0.04 inch (0.102 cm) to approximately 0.40 inch (1.02 cm); and the third tiers **419, 519** can have third tier lengths of approximately 0.05 inch (0.127 cm) to approximately 0.50 inch (1.27 cm).

[0055] As shown in FIGS. 3, 4, and 5, in some embodiments, the first and the second arcuate surface of tiered transitions **316, 416, 516** can have first and second radii of curvatures that are at least two times larger than the difference between the first thickness T_1 and the second thickness T_2 of the first tier **315, 415, 515**, and the second tier **317, 417, 517**, respectively. In one embodiment, the first and the second arcuate surface of tiered transitions **316, 416, 516** has a first and a second radius of curvature that are approximately 6.5 times larger than the difference between the first thicknesses T_1 and the second thickness T_2 of the first tier **315, 415, 515** and the second tier **317, 417, 517**, respectively. As shown in FIGS. 4 and 5, in some embodiments, the first and the second arcuate surface of tiered transitions **418, 518** can have first and second radii of curvatures that are at least two times larger than the difference between the second thickness T_2 and the third thickness T_3 of the second tier **417, 517** and the third tier **419, 519**, respectively. In one embodiment, the first and the second arcuate surface of tiered transitions **418, 518** has a first and a second radius of curvature that are approximately 6.5 times larger than the difference between the second thicknesses T_2 and the third thickness T_3 of the second tier **417, 517** and the third tier **419, 519**, respectively.

[0056] Some embodiments, such as golf club head **300**, as shown in FIG. 3, comprise weight pad **330** to lower the center of gravity of golf club head **300**. Weight pad **330** comprises a weight pad thickness **331** that is greater than the final tier thickness **321** of the adjacent tier. In this example, the adjacent tier is second tier **317**. In many embodiments which comprise weight pad **330**, internal sole thickness **320** can be approximately equal to final tier thickness **321**. In some

embodiments, internal sole thickness **320** can be thicker than final tier thickness **321**. In some embodiments, internal sole thickness **320** is thinner than final tier thickness **321**.

[0057] Some embodiments, such as golf club head **400**, as shown in FIG. 4, comprise a rib **440**. Rib **440** can be located internal to body **401** and approximately parallel to the strikeface. In many embodiments, rib **440** can be a ridge or bar. In some embodiments, rib **440** can have a rib thickness **441** that is greater than a third tier thickness **421**, the thickness of the adjacent tier, or the thickness of the final tier of internal radius transition **410**. The purpose for rib **440** is to reinforce the sole of golf club head **400** so that the peak bending of the sole occurs at tier transition region **416** and/or tier transition region **418**.

[0058] Turning to FIG. 6, in some embodiments, golf club head **600** can comprise a crown internal radius transition **660** at crown **608**. Crown internal radius transition **660** can be similar to internal radius transition **310** in FIG. 3, except crown internal radius transition **660** is located at the strikeface to crown transition instead of the strikeface to sole transition. In many embodiments, first tier **615** can be similar to first tiers **315, 415**, and/or **515** in FIGS. 3, 4, and 5, respectively; second tier **617** can be similar to second tiers **317, 417**, and/or **517** in FIGS. 3, 4, and 5, respectively; third tier **619** can be similar to third tiers **419** and/or **519** in FIGS. 4 and 5, respectively; and tier transition regions **616** and/or **618** can be similar to tier transition regions **316, 416, 516, 418**, and/or **518** in FIGS. 3, 4, and 5. Similarly, the crown internal radius transition **660** can have several internal radius transitions to form more than two tiers. For example, the crown internal radius transition **660** can have 2, 3, 4, 5, 6, or 7 tiers.

[0059] In FIG. 7, a golf club head **700** can comprise a skirt internal radius transition **780** as shown in FIG. 7. FIG. 7 depicts a cross-sectional view of golf club **700** similar to golf club head **100** (FIG. 1) along a similar cross-sectional line as the cross-sectional line VII-VII in FIG. 1, according to another embodiment. Skirt internal radius transition **780** can be similar to internal radius transition **210** (FIG. 2), and first tier **715** can be similar to first tiers **315, 415**, and/or **515** in FIGS. 3, 4, and 5, respectively; second tier **717** can be similar to second tiers **317, 417**, and/or **517** in FIGS. 3, 4, and 5; third tier **719** can be similar to third tiers **419** and/or **519** in FIGS. 4 and 5, respectively; and tier transition regions **716** and/or **718** can be similar to tier transition regions **316, 416, 516, 418**, and/or **518** in FIGS. 3, 4, and 5. Similarly, skirt internal radius transition **780** can have more than two tiers. For example, skirt internal radius transition **780** can have 2, 3, 4, 5, 6, or 7 tiers. As shown in FIG. 7, golf club head **700** also can comprise a skirt internal radius transition at the other side of strikeface **712**. In another embodiment, golf club head **700** can comprise a skirt internal radius transition at a single side of strikeface **712**.

[0060] FIG. 8 depicts a view of a portion of a golf club head **800** similar to golf club head **400** (FIG. 4), according to an embodiment, and a view of the same area of standard golf club head **850**. Standard golf club head **850** comprises a uniform sole thickness **855** from a strikeface **852** to a sole **856**, and an internal sole weight **870** that is thicker than a uniform sole thickness **855**. Golf club head **800** comprises an internal radius transition **810** similar to internal radius transition **410** (FIG. 4). Internal radius transition **810** can comprise a first tier **815**, similar to first tier **415** (FIG. 4), a second tier **817**, similar to second tier **417** (FIG. 4), and a third tier **819**, similar to third tier **419** (FIG. 4). Internal radius transi-

tion **810** also can comprise tier transition regions **816** and **818**, similar to tier transition regions **416** (FIG. 4) and **418** (FIG. 4), and internal sole weight **820** that is similar to internal sole weight **870**. In many embodiments, at least one of first tier **815**, second tier **817**, or third tier **819** can be thinner than uniform sole thickness **855**. The thinness of the tiers can save weight that can then be redistributed in the club head.

[0061] There is a greater dispersion of higher stress over a greater area of sole **806** with internal transition region **810** than sole **856** without the cascading sole. In many embodiments, a general curve of a sole similar to uniform sole thickness **855** can absorb greater particular concentrations of impact force from a golf ball in particular regions, but will not disperse the force over a larger area. The cascading structure (or tiers of varying thickness along the internal radius transition), such as internal radius transition **810**, however provides a technique to “package” the impact force from the golf ball over a larger area as the undulating or tier structure transfers higher stresses from one internal radius region of particular thickness to the next. In many embodiments, there is a bleeding, overflow, or pooling of the stress over internal radius transition **810** or the cascading thin sole. The greater dispersion of the greater stress force provides a greater recoil force to the strikeface. The pooling of the stress over internal radius transition **810** also can prevent all of the stress from collecting directly at the thinnest tier. In many embodiments, the tiered features can help distribute the stress along the sole to prevent one large stress riser. Instead, there are multiple stress risers for a more even distribution of the stress. The stresses are extended along the cascading sole, allowing the sole to take on (or absorb) more stress. The stress, however, decreases at the thickest portion of the sole that without the cascading sole experiences the highest level of stress, and provides less spring back force to the strikeface.

[0062] An embodiment of a golf club head (e.g. 100, 300, 400, 500, 600, or 700) having the cascading sole was tested compared to a similar control club head devoid of a cascading sole. The club head with the cascading sole showed an increase in ball speed of approximately 0.5-1.5 miles per hour (mph) (0.8-2.4 kilometers per hour, kph), or approximately 0.5-0.9%, compared to the control club head. The increase in ball speed for center impacts was approximately 0.5-1.0 mph (0.8-1.6 kph), and the increase in ball speed for off-center impacts was approximately 1-1.5 mph (1.6-2.4 kph). The club head with the cascading sole further showed an increase in launch angle of approximately 0.1-0.3 degrees, a decrease in spin of approximately 275-315 revolutions per minute (rpm), and an increase in carry distance of approximately 3-6 yards (2.7-5.5 meters) compared to the control club head.

[0063] In some embodiments, the crown of a driver-type, hybrid-type, or wood-type golf club head having the cascading sole (e.g. 100, 300, 400, 500, 600, or 700) may further include a first crown thickness (not shown) and a second crown thickness (not shown). The first crown thickness may be positioned on the crown behind the strikeface or crown internal radius transition. The second crown thickness may be positioned on the crown behind the first crown thickness toward the rear of the club head. The first crown thickness is greater than the second crown thickness. Further, the first crown thickness may transition to the second crown thickness gradually according to any profile, or the first crown thickness may transition to the second crown thickness abruptly, such as with a step.

[0064] The first crown thickness may comprise any portion of the crown on a front end of the club head. For example, the first crown thickness may comprise 5%, 10%, 15%, 20%, 25%, 30%, 35%, 40%, 45%, 50%, or any other portion of the crown on the front end of the club head. The second crown thickness may comprise any portion of the crown on the rear of the club head. For example, the second crown thickness may comprise 40%, 45%, 50%, 55%, 60%, 65%, 70%, 75%, 80%, or any other portion of the rear of the club head.

[0065] The crown thickness may transition between the first crown thickness and the second crown thickness at any position on the crown of the club head, defining a crown thickness transition. The crown thickness transition may be any shape. In the exemplary embodiment, the crown thickness transition defines a bell-shaped curve, similar to the bell-shaped curve in U.S. Pat. No. 7,892,111, which is incorporated herein by reference. The first crown thickness is positioned on the crown between the strikeface and the bell-shaped curve, and the second crown thickness is positioned on the crown between the bell-shaped curve and the rear of the club head.

[0066] In the exemplary embodiment, the first crown thickness is approximately 0.022 inches (0.056 cm) and the second crown thickness is approximately 0.019 inches (0.048 cm) when the golf club head is a fairway wood type golf club head. Further, in the exemplary embodiment, the first crown thickness is approximately 0.024 inches (0.061 cm) and the second crown thickness is approximately 0.019 inches (0.048 inches) when the golf club head is a hybrid type golf club head.

[0067] In other embodiments of a fairway wood or hybrid type golf club head, the first crown thickness may be less than approximately 0.029 (0.074), 0.028 (0.071), 0.027 (0.069), 0.026 (0.066), 0.025 (0.064), 0.024 (0.061), 0.023 (0.058), 0.022 (0.056), 0.021 (0.053), 0.020 (0.051), 0.019 (0.048), 0.018 (0.046), or 0.017 (0.043) inches (cm), and the second crown thickness may be less than approximately 0.024 (0.061), 0.023 (0.058), 0.022 (0.056), 0.021 (0.053), 0.020 (0.051), 0.019 (0.048), 0.018 (0.046), 0.017 (0.043), 0.016 (0.041), 0.015 (0.038), 0.014 (0.036), 0.013 (0.033), or 0.012 (0.031) inches (cm).

[0068] The crown internal radius transition dissipates and/or reduces stresses on the crown of the club head, thereby allowing the first and the second crown thickness to be reduced compared to previous designs. In the exemplary embodiment, the first crown thickness is reduced by approximately 17.2-24.1%, and the second crown thickness is reduced by approximately 20.8% compared to previous designs. Reducing the first and the second crown thickness allows the center of gravity of the club head to be lowered (positioned closer to the sole) compared to previous designs. The lowered center of gravity of the club head improves the performance characteristics of the club head by reducing gearing and spin on the ball.

[0069] Turning to FIG. 9, various embodiments of golf club heads with tiered internal thin sections include a method 900 for manufacturing a golf club head. Method 900 comprises providing a body (block 910). The body comprises a strikeface, a heel region, a toe region opposite the heel region, a sole, and a crown. In some embodiments, the body further comprises a skirt extending from the crown to the sole. Method 900 further comprises providing an internal radius transition region from the strikeface to at least one of the sole, the crown, or the skirt (block 920). Method 900 further comprises providing a first tier of the internal radius transition

region (block 930), providing a second tier of the internal transition region (block 940), and providing a tier transition region between the first tier and the second tier of the internal transition region (block 950). In some embodiments, each of blocks 910, 920, 930, 940, and 950 can be performed simultaneously with each other such as by casting the body of a club head. In other embodiments, one or more of blocks 920, 930, 940, and/or 950 can be performed after block 910 through a machining process, as an example.

II. Golf Club Head with Back Cavity

[0070] In one embodiment, the golf club head has a back cavity located in an upper crown area of the golf club. In many embodiments, the back cavity can provide a box spring affect when striking a golf ball. The back cavity can be combined with varying thicknesses of the internal radius of the sole of the club head (cascading sole) to provide a spring like effect.

[0071] Some embodiments are directed to a club head (hybrid or fairway wood or iron with hollow design) that features a hollowed construction club head that provides a more “iron-like” look and feel. In some embodiments, the golf club head can feature a flat strikeface and iron-like profile, which can provide improved workability and accuracy, similar to an iron. A back cavity located below a top rail and along the upper crown of the club head has been designed for hybrids, fairway woods and irons with a hollow construction. The back cavity may be a full channel from the heel to the toe just below the top rail and along the upper crown or back portion of the club head. The top rail and the cavity may be any design. In some embodiments, the cavity is angled at approximately 90 degrees and provides a targeted hinge point in the crown region of the golf club head. This hinge or buckling region enables the top rail to absorb more of the impact force over a wider volumetric area causing the cavity and the top rail to act as a springboard by returning more recoiled force back to the strikeface as it returns to its original orientation thereby imparting more force into the ball. This greater club face deflection by the cavity design can lead to less spin, a higher loft angle of the golf ball upon impact, and greater ball speed with the same club speed over standard golf club heads.

[0072] In a standard hybrid club head, the top rail and upper crown regions do not have a cavity of this design. In comparison to the present disclosure, there is less club strikeface bending or deflection in such a standard hybrid club head. Standard hybrids are unable to have as great a spring-back effect because less energy is transferred to the top rail of the club due to the lack of a cavity. The disclosed golf club head with back cavity allows more of the impact force of the golf ball to be absorbed and then returned to the strikeface. In many embodiments, the angle of the cavity can provide a buckling point, or plastic hinge, or targeted hinge, for the strikeface to deflect more over the standard golf club.

[0073] The recoiling effect of the cavity on the strikeface provides: (1) a higher golf ball speed relative to the same club head speed of a club head with an upper crown cavity (or back cavity) and one without, due in part to the spring effect that is transferred from the hinged region to the strikeface to the ball; (2) less spin of the golf ball after impact with the club, due in part to the hinge point above the cavity counters more force being absorbed by the club and instead transfers more force to the ball thereby preventing the ball from spinning backward off the strikeface; (3) a higher loft angle to the golf ball upon impact, due to the hinge and strikeface acting as a diving board or catapult to the ball. In some embodiments, the cavity

may provide an increase in ball speed of approximately 1.0-1.2%, and an increase in launch angle of approximately 0.4-0.7 degrees.

[0074] Turning back to the drawings, FIG. 10 illustrates a back toe-side perspective view of an embodiment of golf club head 1000 and FIG. 11 illustrates a back heel-side perspective view of golf club head 1000 according to the embodiment of FIG. 10. Golf club head 1000 can be a hybrid-type golf club head. In other embodiments, golf club head 1000 can be an iron-type golf club head or a fairway wood-type golf club head. In many embodiments, golf club head 1000 does not include a badge or a custom tuning port.

[0075] Golf club head 1000 comprises a body 1001. In many embodiments, the body is hollow. In some embodiments, the body is at least partially hollow. Body 1001 comprises a strikeface 1012, a heel region 1002, a toe region 1004 opposite heel region 1002, a sole 1006, and a crown 1008. Crown 1008 comprises an upper region 1011 and a lower region 1013. Upper region 1011 comprises a top rail 1015. In some embodiments, top rail 1015 can be a flatter and taller top rail or skirt. The flatter and taller top rail can account for mishits on strikeface 1012 to increase playability off the tee.

[0076] In some embodiments, body 1001 can comprise stainless steel, titanium, aluminum, a steel alloy (e.g. 455 steel, 475 steel, 431 steel, 17-4 stainless steel, maraging steel), a titanium alloy (e.g. Ti 7-4, Ti 6-4, T-9S), an aluminum alloy, or a composite material. In some embodiments, strikeface 1012 can comprise stainless steel, titanium, aluminum, a steel alloy (e.g. 455 steel, 475 steel, 431 steel, 17-4 stainless steel, maraging steel), a titanium alloy (e.g. Ti 7-4, Ti 6-4, T-9S), an aluminum alloy, or a composite material. In some embodiments, body 1001 can comprise the same material as strikeface 1012. In some embodiments, body 1001 can comprise a different material than strikeface 1012.

[0077] In many embodiments, a cavity 1030 is located below top rail 1015. In many embodiments, cavity 1030 comprises a top rail box spring design. In many embodiments, top rail 1015 and cavity 1030 provide an increase in the overall bending of strikeface 1012. In some embodiments, the bending of strikeface 1012 can allow for an approximately 2% to approximately 5% increase of energy. The cavity 1030 allows for the strikeface 1012 to be thinner and allow additional overall bending. For some fairway wood-type golf club head embodiments, cavity 1030 can be a reverse scoop or indentation of crown 1008 with greater thickness toward sole 1006.

[0078] Referring to FIG. 10, in some embodiments, golf club head 1000 can further comprise an insert 1062 at lower region 1013 of crown 1008 towards toe region 1004. Some embodiments comprise an internal weight at sole 1006. In many embodiments, insert 1062 may be comprised of tungsten or some other high density material. In many embodiments, the insert shifts the center of gravity (CG) back from strikeface 1012 by approximately 0.04 inch (1 mm) to 0.10 inch (2.5 mm) and provides a 3.5% to 5.5% increase in launch angle, which can lead to an increase of playability off the tee and high or low mishits.

[0079] In many embodiments, the CG is in lower region 1013 of crown 1008, close to the intersection of toe region 1004 and sole 1006. In some embodiments, the CG of golf club head 1000 is 0.597 inches along the CGy plane and 0.541 inches along the CGz plane. For the moment of inertia, Ixx, there was a 20.5% increase over the G30 iron and a 28%

increase over the Rapture DI by golf club head **1000**. For Iyy, there was a 1.7% increase over the G30 iron and a 22% increase over Rapture DI.

[0080] In some embodiments, approximately 3 grams (g) to approximately 4 g is added to top rail **1015**. In most embodiments, the overall mass of golf club head **1000** remains the same. In some embodiments, mass can be removed from sole **1006** or toe region **1004** to offset the addition of mass to top rail **1015**. In some embodiments, adding the approximately 3 g to approximately 4 g of mass to top rail **1015** can assist in the golf club head resisting turning. In some embodiments, the CG of the golf club head is slightly raised.

[0081] FIG. 12 illustrates a cross-section of golf club head **1000** along the cross-sectional line XII-XII in FIG. 10, according to one embodiment. As seen in FIG. 12, strikeface **1012** comprises a high region **1076**, a middle region **1074**, and a low region **1072**. In many embodiments, upper region **1011** of crown **1008** comprises a rear wall **1023**, a top wall **1017** of cavity **1030** below and adjacent to rear wall **1023**, and a back wall **1019** of cavity **1030** below and adjacent to top wall **1017**.

[0082] In some embodiments, a height **1280** of rear wall **1023** of the upper region **1011** of crown **1008** can be approximately 0.125 inch (0.318 cm) to approximately 0.75 inch (1.91 cm), or approximately 0.150 inch (0.381 cm) to approximately 0.400 inch (1.02 cm). For example, in some embodiments, the height **1280** of rear wall **1023** of the upper region **1011** of crown **1008** can be approximately 0.175 inch (0.445 cm), 0.275 inch (0.699 cm), 0.375 inch (0.953 cm), 0.475 inch (1.21 cm), 0.575 inch (1.46 cm), or 0.675 inch (1.71 cm). In some embodiments, the height **1280** of rear wall **1023** of the upper region **1011** of crown **1008** can be approximately 5% to approximately 25% of the height of golf club head **1000**. In some embodiments, the length of top rail **1015**, measured from heel region **1002** to toe region **1004**, can be approximately 70% to approximately 95% of the length of golf club head **1000**.

[0083] The height **1280** of rear wall **1023** of the upper region **1011** of crown **1008**, as described herein, allows cavity **1030** to absorb at least a portion of the stress on strikeface **1012** during impact with a golf ball. A golf club head having a rear wall height greater than the rear wall height **1280** described herein would absorb less stress (and allow less strikeface deflection) on impact than the golf club head **1000** described herein, due to increased dispersion of the impact stress along the top rail prior to reaching the cavity.

[0084] In some embodiments, cavity **1030** is located above lower region **1013** of crown **1008** and is defined at least in part by upper region **1011** and lower region **1013** of crown **1008**. Cavity **1030** comprises a top wall **1017**, a back wall **1019**, and a bottom incline **1021**. A first inflection point **1082** is located between top wall **1017** of cavity **1030** and rear wall **1019** of cavity. A second inflection point **1086** is located between rear wall **1019** of cavity **1030** and bottom incline **1021**.

[0085] In some embodiments, the height of back wall **1019**, measured from first inflection point **1082** to second inflection point **1086**, can be approximately 0.010 inch (0.25 mm) to approximately 0.138 inch (3.5 mm), or approximately 0.010 inch (0.25 mm) to approximately 0.059 inch (1.5 mm). For example, the height of back wall **1019** can be approximately 0.01 inch (0.25 mm), 0.02 inch (0.5 mm), 0.03 inch (0.75 mm), 0.04 inch (1.0 mm), 0.05 inch (1.25 mm), 0.06 inch (1.5 mm), 0.07 inch (1.75 mm), 0.08 inch (2.0 mm), 0.09 inch (2.25 mm), 0.10 inch (2.5 mm), 0.11 inch (2.75 mm), 0.012

inch (3.0 mm), 0.13 inch (3.25 mm), or 0.14 inch (3.5 mm). In many embodiments, an apex of top wall **1017** can be approximately 0.125 inch (0.318 cm) to approximately 1.25 inches (3.18 cm) or approximately 0.25 inch (0.635 cm) to approximately 1.25 inches (3.18 cm) below an apex of top rail **1015**. For example, the apex of top wall **1017** can be approximately 0.125 inch (0.318 cm), 0.25 inch (0.635 cm), 0.375 inch (0.953 cm), 0.5 inch (1.27 cm), 0.625 inch (1.59 cm), 0.75 inch (1.91 cm), 0.825 inch (2.10 cm), 1.0 inch (2.54 cm), 1.125 inches (2.88 cm), or 1.25 inches (3.18 cm) below the apex of top rail **1015**.

[0086] In many embodiments, back wall **1019** of cavity **1030** can be substantially parallel to strikeface **1012**. In other embodiments, back wall **1019** is not substantially parallel to strikeface **1012**. In many embodiments, top wall **1017** of cavity is angled toward strikeface **1012** when moving toward the first inflection point **1082**. This orientation of top wall **1017** creates a buckling point or hinge point or plastic hinge to direct the stress of impact toward cavity **1030** and allowing increased flexing of strikeface **1012** during impact.

[0087] Lower region **1013** of crown **1008** comprises bottom incline **1021** of cavity **1030**. In many embodiments, the second inflection point **1086**, adjacent to bottom incline **1021**, can be at least approximately 0.25 inch (0.635 cm) to approximately 2.0 inches (5.08 cm), or approximately 0.5 inch (1.27 cm) to approximately 1.5 inches (3.81 cm) below the apex of top rail **1015**. For example, the second inflection point **1086** can be at least approximately 0.25 inch (0.635 cm), 0.5 inch (1.27 cm), 0.75 inch (1.91 cm), 1.0 inch (2.53 cm), 1.25 inches (3.18 cm), 1.5 inches (3.81 cm), 1.75 inches (4.45 cm) or 2.0 inches (5.08 cm) below the apex of top rail **1015**. In some embodiments, the maximum height of the bottom incline, measured from the sole **1006** of the club head **1000** to the second inflection point **1086**, can be at least approximately 0.25 inch (0.635 cm) to approximately 3 inches (7.62 cm), or approximately 0.50 inch (1.27 cm) to approximately 2 inches (5.08 cm) above a lowest point of the sole **1006**. For example, the second inflection point **1086** can be at least approximately 0.25 inch (0.635 cm), 0.375 inch (0.953 cm), 0.5 inch (1.27 cm), 0.625 inch (1.59 cm), 0.75 inch (1.91 cm), 0.825 inch (2.10 cm), 1.0 inch (2.54 cm), 1.125 inches (2.88 cm), 1.25 inches (3.18 cm), 1.375 inches (3.49 cm), 1.5 inches (3.81 cm), 1.625 inches (4.12 cm), 1.75 inches (4.45 cm), 1.875 inches (4.76 cm), 2.0 inches (5.08 cm), 2.125 inches (5.40 cm), 2.25 inches (5.71 cm), 2.375 inches (6.03 cm), 2.5 inches (6.35 cm), 2.625 inches (6.67 cm), 2.75 inches (7.00 cm), 2.875 inches (7.30 cm), or 3.0 inches (7.62 cm) above a lowest point of the sole.

[0088] Cavity **1030** further comprises at least one channel **1039** (FIG. 10). In many embodiments, channel **1039** extends from heel region **1002** to toe region **1004**. A channel width **1032** (FIG. 12) can be substantially constant throughout channel **1039**. In some embodiments, channel width **1032** (FIG. 12) can be approximately 0.008 inch (0.2 mm) to approximately 1 inch (25 mm), or approximately 0.008 inch (0.2 mm) to approximately 0.31 inch (8 mm). For example, channel width **1032** can be approximately 0.008 inch (0.2 mm), 0.016 inch (0.4 mm), 0.024 inch (0.6 mm), 0.031 inch (0.8 mm), 0.039 inch (1.0 mm), 0.079 inch (2 mm), 0.12 inch (3 mm), 0.16 inch (4 mm), 0.20 inch (5 mm), 0.24 inch (6 mm), 0.28 inch (7 mm), 0.31 inch (8 mm), 0.39 inch (10 mm), 0.59 inch (15 mm), 0.79 inch (20 mm), or 0.98 inch (25 mm). In other embodiments, a channel toe region width of channel **1039** is smaller than a channel heel region width of channel.

In other embodiments, the channel heel region width is smaller than the channel toe region width. In other embodiments, a channel middle region width of channel 1039 can be smaller than at least one of the channel heel region width or the channel toe region width. In other embodiments, the channel middle region width can be greater than at least one of the channel heel region width or the channel toe region width. In some embodiments, channel 1039 is symmetrical. In other embodiments, channel 1039 is non-symmetrical. In other embodiments, channel 1039 can further comprise at least two partial channels. In some embodiments, channel 1039 can comprise a series of partial channels interrupted by one or more bridges. In some embodiments, the one or more bridges can be approximately the same thickness as the thickness of upper region 1011 of crown 1008.

[0089] The channel width 1032, as described herein, allows absorption of stress from strikeface 1012 on impact. A golf club head having a channel width less than the channel width described herein (e.g., a golf club head with a less pronounced cavity) would allow less stress absorption from the strikeface on impact (due to less material on the upper region 1011 of crown 1008), and therefore would experience less strikeface deflection than the golf club head 1000 described herein.

[0090] In many embodiments, cavity 1030 further comprises a back cavity angle 1035. Back cavity angle is measured between top wall 1017 and back wall 1019 of cavity 1030. In many embodiments, back cavity angle 1035 can be approximately 70 degrees to approximately 110 degrees. In some embodiments, back cavity angle 1035 can be approximately 80 degrees to approximately 100 degrees. In some embodiments, back cavity angle 1035 is approximately 70, 75, 80, 85, 90, 95, 100, or 110 degrees. In many embodiments, back cavity angle 1035 provides a buckling point or plastic hinge or targeted hinge at a top rail hinge point 1070, upon golf club head 1000 impacting the golf ball. In some embodiments, the wall thickness at top rail hinge point 1070 is thinner than at top wall 1017 of cavity 1030.

[0091] FIG. 13 illustrates a view of crown 1008 of the cross-section of golf club head 1000 of FIG. 12 alongside a similar cross-section of a golf club head 1200 without a cavity along a similar cross-sectional line XII-XII in FIG. 10. In many embodiments, golf club head 1000 comprises a rear angle 1040, a top rail angle 1045, and a strikeface angle 1050. Upper region angle 1040 is measured from top wall 1017 to rear wall 1023 of upper region 1011. In many embodiments, rear angle 1040 can be approximately 70 degrees to approximately 110 degrees. In some embodiments, rear angle 1040 is approximately 90 degrees. Top rail angle 1045 is measured from rear wall 1023 of upper region 1011 to top rail 1015. In many embodiments, top rail angle 1045 can be approximately 35 degrees to approximately 120 degrees or 70 degrees to approximately 110 degrees. In some embodiments, top rail angle 1045 can be approximately 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100, 105, 110, 115, or 120 degrees. Strikeface angle 1050 is measured from strikeface 1012 to top rail 1015. In many embodiments, strikeface angle 1050 can be approximately 70 degrees to approximately 160 degrees or 70 degrees to approximately 110 degrees. In some embodiments, strikeface angle 1050 is approximately 70, 75, 80, 85, 90, 95, 100, 105, 110, 115, 120, 125, 130, 135, 140, 145, 150, 155, or 160 degrees.

[0092] Referring to FIG. 13, in some embodiments, a minimum gap 1090 between strikeface 1012 and back wall 1019 is approximately 0.079 inch (2 mm) to approximately 0.39 inch

(10 mm). For example, the minimum gap 1090 between strikeface 1012 and back wall 1019 can be approximately 0.079 inch (2 mm), 0.16 inch (4 mm), 0.24 inch (6 mm), 0.31 inch (8 mm), or 0.39 inch (10 mm). In some embodiments, the minimum gap 1090 between the strikeface 1012 and back wall 1019 is less than approximately 0.55 inch (14 mm), less than approximately 0.47 inch (12 mm), less than approximately 0.39 inch (10 mm), less than approximately 0.31 inch (8 mm), less than approximately 0.24 inch (6 mm), or less than approximately 0.16 inch (4 mm). Further, in some embodiments, a maximum gap between strikeface 1012 and rear wall 1023 of upper region 1011 of golf club head 1000 is greater than minimum gap 1090. Further still, in some embodiments, a maximum gap between strikeface 1012 and bottom incline 1021 in lower region 1013 of golf club head 1000 is greater than minimum gap 1090 and maximum gap in upper region 1011.

[0093] FIG. 21 illustrates a cross-sectional view of golf club head 1000, similar to the cross-section of the golf club head 1000 illustrated in FIG. 12. Golf club head 1000 includes cavity 1030, upper region 1011, and lower region 1013. Upper region 1011 includes upper exterior rear wall 1023, cavity 1030 includes cavity exterior wall 1025, and lower region 1013 includes lower exterior wall 1027. In many embodiments, a maximum upper distance 1092 measured as the perpendicular distance from the strikeface 1012 to the rear wall 1023 of upper region 1011 can be approximately 0.20-0.59 inch (5-15 mm). For example, maximum upper distance 1092 can be approximately 0.20 inch (5 mm), 0.24 inch (6 mm), 0.28 inch (7 mm), 0.31 inch (8 mm), 0.35 inch (9 mm), 0.39 inch (10 mm), 0.43 inch (11 mm), 0.47 inch (12 mm), 0.51 inch (13 mm), 0.55 inch (14 mm), or 0.59 inch (15 mm). Further, a minimum cavity distance 1094 measured as the perpendicular distance from the strikeface 1012 to the cavity exterior wall 1025 can be approximately 0.16-0.47 inch (4-12 mm). For example, minimum cavity distance 1094 can be approximately 0.16 inch (4 mm), 0.20 inch (5 mm), 0.24 inch (6 mm), 0.28 inch (7 mm), 0.31 inch (8 mm), 0.35 inch (9 mm), 0.39 inch (10 mm), 0.43 inch (11 mm), or 0.47 inch (12 mm). Further still, a maximum lower distance 1096 measured as the perpendicular distance from the strikeface 1012 to the lower exterior wall 1027 can be approximately 0.98-1.57 inch (25-40 mm). For example, maximum lower distance 1096 can be approximately 0.98 inch (25 mm), 1.02 inch (26 mm), 1.06 inch (27 mm), 1.10 inch (28 mm), 1.14 inch (29 mm), 1.18 inch (30 mm), 1.22 inch (31 mm), 1.26 inch (32 mm), 1.30 inch (33 mm), 1.34 inch (34 mm), 1.38 inch (35 mm), 1.42 inch (36 mm), 1.46 inch (37 mm), 1.50 inch (38 mm), 1.54 inch (39 mm), 1.57 inch or (40 mm). In many embodiments, maximum lower distance 1096 is greater than maximum upper distance 1092, and maximum upper distance 1092 is greater than minimum cavity distance 1094.

[0094] In many embodiments, cavity 1030 can provide an increase in golf ball speed over golf club head 1200 or other standard golf club heads, can reduce the spin rate of standard hybrids club heads, and can increase the launch angle over both the standard hybrid and iron club heads. In many embodiments, the shape of cavity 1035 determines the level of spring and timing of the response of golf club head 1000. When the golf ball impacts strikeface 1012 of club head 1000 with cavity 1030, strikeface 1012 springs back like a drum, and crown 1008 bends in a controlled buckle manner. In many embodiments, top rail 1015 can absorb more stress over greater volumetric space than a top rail in a golf club head

without cavity **1030**. The length, depth and width of cavity **1030** can vary. These parameters provide control regarding how much spring back is present in the overall design of club head **1000**.

[0095] Upon impact with the golf ball, strikeface **1012** can bend inward at a greater distance than on a golf club without cavity **1030**. In some embodiments, strikeface **1012** has an approximately 10% to approximately 50% greater deflection than a strikeface on a golf club head without cavity **1030**. In some embodiments, strikeface **1012** has an approximately 5% to approximately 40% or approximately 10% to approximately 20% greater deflection than a strikeface on a golf club head without cavity **1035**. For example, strikeface **1012** can have an approximately 5%, 10%, 15%, 20%, 25%, 30%, 35% or 40% greater deflection than a strikeface on a golf club head without cavity **1035**. In many embodiments, there is both a greater distance of retraction by strikeface **1012** due to the hinge and bending of cavity **1030** over a standard strikeface that does not have a back portion of the club without the cavity.

[0096] In many embodiments, the face deflection is greater with club head **1000** having cavity **1030**, as a greater buckling occurs along top rail hinge point **1070** upon impact with the golf ball. Cavity **1030**, however, provides a greater dispersion of stress along top rail hinge point **1070** region of the top rail and the spring back force is transferred from cavity **1030** and top rail **1015** to strikeface **1012**. A standard top rail without a cavity does not have this hinge/buckling effect, nor does it absorb a high level of stress over a large volumetric area of the top rail. Therefore, the standard strikeface does not contract and then recoil as much as strikeface **1012**. Further, both a larger region of strikeface **1012** and top rail **1015** absorb more stress than the same crown region of a standard golf club head with a standard top rail and no cavity. In many embodiments, although there is greater stress along a greater area above cavity **1030** than the same area in a standard club without the cavity, the durability of the club head with and without the cavity is the same. By adding more spring to the back end of the club (due to the inward inclination of top wall **1017** toward strikeface **1012**), more force is displaced throughout the volume of the structure. The stress is observed over a greater area of strikeface **1012** and top rail **1015** of golf club head **1000**. Peak stresses can be seen in the standard top rail club head. However, more peak stresses are seen in golf club head **1000**, but distributed over a large volume of the material. The hinge and bend regions of golf club head **1000** (i.e., the region above cavity **1030** and cavity **1030** itself) will not deform as long as the stress does not meet the critical buckling threshold. Cavity **1030** and its placement can be design to be under the critical K value of the buckling threshold.

III. Golf Club Head with Cascading Sole and Back Cavity

[0097] In some embodiments, a golf club head with a back cavity can further comprise a cascading sole with tiered thin sections. FIG. 14 illustrates a cross-section of golf club head **1100**, which can be similar to golf club head **1000** (FIG. 10), along a similar cross-sectional line XII-XII in FIG. 10, according to an embodiment. Similar to golf club head **1000** (FIG. 10), golf club head **1100** comprises a body **1101**. Body **1101** comprises a strikeface **1112**, a sole **1106**, and a crown **1108**. Strikeface **1112** comprises a high region **1176**, a middle region **1174**, and a low region **1172**. Crown **1108** comprises an upper region **1111** and a lower region **1113**. Upper region **1111** comprises a top rail **1115**. In many embodiments, a cavity **1130** is located below top rail **1115**. Golf club head

1100 further comprises a cascading sole **1310**, similar to internal radius transition **310** (FIG. 3). Internal radius transition **1310** comprises a first tier **1315** at a first thickness, a second tier **1317** at a second thickness, and a tier transition region **1316**. In some embodiments, cascading sole **1310** can provide further pliability to top rail **1115**. In many embodiments, the back cavity combined with the cascading sole can provide an even greater spring effect on the strikeface. In some embodiments, the back cavity with the cascading sole allows approximately 3%-5% more energy in the deflection of the strikeface. The cascading sole **1310** can include any number of tiers greater than or equal to two tiers. For example, the cascading sole **1310** can have 2, 3, 4, 5, 6, or 7 tiers.

[0098] The golf club head **1100** having the cascading sole and the back cavity can provide a greater recoiling force to the strikeface than the golf club head having the cascading sole or back cavity alone. This is due to the combined increased recoiling force from both the internal radius transition and the back cavity, as discussed above. The increased recoiling force to the strikeface leads to greater deflection, which in turn increases the impact force applied to the golf ball thereby increasing the speed of the golf ball. In some embodiments, golf club head **1100** comprising both cavity **1130** and internal radius transition **1310** can increase ball speed, increase launch angle, and provide better distance control. In various embodiments, golf club head **1100** can increase ball speeds approximately 1% to approximately 4%. In some embodiments, golf club head **1100** can increase ball speeds approximately 1%, 2%, 3%, or 4%. In many embodiments, golf club head **1100** provides a larger increase in ball speeds when the golf ball impacts the strikeface in high region **1176**. In some embodiments, golf club head **1100** can increase the launch angle by approximately 0.5 degrees to approximately 1.1 degrees. In some embodiments, golf club head **1100** can increase the launch angle by approximately 0.5 degrees, 0.6 degrees, 0.7 degrees, 0.8 degrees, 0.9 degrees, 1.0 degrees, or 1.1 degrees.

[0099] An embodiment of golf club head **1100** having the cascading sole and the back cavity was tested. Overall, when compared to a control golf club head devoid of the cascading sole and the back cavity, the cavity golf club head showed an increase in golf ball speed and an increase in launch angle. The cavity golf club head showed the increase in golf ball speed and the increase in launch angle for all contact positions on the face due to the combined spring effect from the combination of cascading sole **1310** (FIG. 14) and cavity **1130** (FIG. 14). In some embodiments, a greater increase in golf ball speed and launch angle was observed on contact with high portions of the face, (e.g., high region **1076** (FIG. 12) or high region **1176** (FIG. 14)) due in part from the spring effect of cavity **1130** (FIG. 14). FIGS. 19-20 depicts results from the testing of the embodiment of golf club head **1100** (cavity golf club head) compared to a standard iron-type golf club head (control golf club head) with a closed back design and similar loft angle as the cavity golf club head. FIG. 19 shows an increase in golf ball speed in the cavity golf club head compared to the control golf club head when the golf ball impacts the high region of the strikeface, and FIG. 20 shows an increase in launch angle of the cavity golf club head compared to the control golf club head when the golf ball impacts the high region of the strikeface.

[0100] Specifically, FIG. 19 shows that golf ball speed is increased by approximately 1.9% (or approximately 2.5 mph) for the cavity golf club head when the golf ball impacts a

high-toe region of the strikeface, approximately 2.1% (or approximately 2.8 mph, or approximately 4.5 kph) when the golf ball impacts a high-center region of the strikeface, and approximately 1.5% (or approximately 2.0 mph, or approximately 3.2 kph) when the golf ball impacts a high-heel region of the strikeface (all of the cavity golf club head), when compared to the control golf club head. When the golf ball impacts the strikeface in the high-toe region of the control golf club head, the golf ball speed is approximately 132.5 mph (213.2 kph), while the golf ball reaches approximately 135.0 mph (217.3 kph) when it impacts the strikeface in the high-toe region of the cavity golf club head. When the golf ball impacts the strikeface in the high-center region of the control golf club head, the golf ball speed is approximately 133.4 mph (214.7 kph), while the golf ball reaches approximately 136.2 mph (219.2 kph) when it impacts the strikeface in the high-center region of the cavity golf club head. When the golf ball impacts the strikeface in the high-heel region of the control golf club head, the golf ball speed is approximately 134.0 mph (215.7 kph), while the golf ball reaches approximately 136.0 mph (218.9 kph) when it impacts the strikeface in the high-heel region of the cavity golf club head.

[0101] FIG. 20 shows that launch angle of the cavity golf club head is increased by approximately 4.2% (or approximately 0.6 degrees) when the golf ball impacts the high-toe region of the strikeface, approximately 4.8% (or approximately 0.7 degrees) when the golf ball impacts the high-center region of the strikeface, and approximately 6.4% (or approximately 0.9 degrees) when the golf ball impacts the high-heel region of the strikeface (all of the cavity golf club head), when compared with the control golf club head. When the golf ball impacts the strikeface in the high-toe region of the control golf club head, the launch angle is approximately 14.4 degrees, while the launch angle is approximately 15.0 degrees when it impacts the strikeface in the high-toe region of the cavity golf club head. When the golf ball impacts the strikeface in the high-center region of the control golf club head, the launch angle is approximately 14.5 degrees, while the launch angle is approximately 15.2 degrees when it impacts the strikeface in the high-center region of the cavity golf club head. When the golf ball impacts the strikeface in the high-heel region of the control golf club head, the launch angle is approximately 14.1 degrees, while the launch angle is approximately 15.0 degrees when it impacts the strikeface in the high-heel region of the cavity golf club head.

[0102] FIG. 17 illustrates method 1700 for manufacturing a golf club head. Method 1700 comprises providing a body (block 1705). Providing a body in block 1705 comprises the body having a strikeface, a heel region, a toe region opposite the heel region, a sole, and a crown. In many embodiments, the crown comprises an upper region and a lower region. In some embodiments, the upper region comprises a top rail. In many embodiments, a cavity is located below the top rail and is located above the lower region of the crown (block 1710). In some embodiments, the cavity is defined at least in part by the upper and lower regions of the crown. The cavity comprises a top wall, a back wall adjacent to the top wall, a bottom incline adjacent to the back wall, a back cavity angle measured between the top and back walls of the cavity, and at least one channel.

[0103] In some embodiments, method 1700 further comprises providing an insert at the lower region of the crown towards the toe region. In some embodiments, the insert is similar to insert 1062 (FIG. 10).

[0104] In some embodiments, providing the body in block 1705 further comprises the body having a cascading sole. The cascading sole comprises an internal radius transition region from the strikeface to the sole. In many embodiments, the internal radius transition region can be similar to internal transition region or cascading sole 1310 (FIG. 14). In some embodiments, the internal transition region comprises a first tier comprising a first thickness, a second tier comprising a second thickness smaller than the first thickness, and a tier transition region between the first tier and the second tier.

IV. Golf Club with Cascading Sole and Back Cavity

[0105] Turning to FIG. 15, FIG. 15 illustrates a golf club 1500 comprising a golf club head 1500 and a shaft 1590 coupled to golf club head 1500. In some embodiments, golf club head 1500 of golf club 15000 comprises a hybrid-type golf club head. In other embodiments, golf club head 1500 can be an iron-type golf club head or a fairway wood-type golf club head. In many embodiments, golf club head 1500 can be similar to golf club head 100 or golf club head 1000 (FIG. 10). Golf club head 1500 can be hollow-bodied and comprises a strikeface 1512, a heel region 1502, a toe region 1504 opposite heel region 1502, a sole 1506, and a crown 1508. Crown 1508 comprises an upper region 1511 and a lower region 1513. Upper region 1511 comprises a top rail 1515. Golf club head 1500 further comprises a cavity 1530 located below top rail 1515 and above lower region 1513 of crown 1508.

[0106] FIG. 16 illustrates a cross-section of golf club head 1500 along the cross-sectional line XVI-XVI in FIG. 15, according to one embodiment. In some embodiments, cavity 1530 can be defined at least in part by upper region 1511 and lower region 1513. In many embodiments, cavity 1530 comprises a top wall 1517, a back wall 1519, a bottom incline 1521, a back cavity angle 1535 measured between top wall 1517 and back wall 1519, and at least one channel 1539. In some embodiments, an apex of top wall 1517 is approximately 0.25 inch to approximately 1.25 inches below an apex of top rail 1515. In some embodiments, the apex of top wall 1517 is approximately 0.375 inch below the apex of top rail 1515. In some embodiments, bottom incline 1521 can be at least approximately 0.50 inch to approximately 2 inches below an apex of top rail 1515. In many embodiments, back cavity angle 1535 can be approximately 70 degrees to approximately 110 degrees. In some embodiments, back cavity angle 1535 can be approximately 90 degrees.

[0107] In many embodiments, upper region 1511 comprises the top and back walls of the cavity; and the lower region of the crown comprises the bottom incline of the cavity. In some embodiments, upper region 1511 further comprises a rear wall 1523 adjacent to top wall 1517 of cavity 1530 and a rear angle 1540 measured between top wall 1517 of cavity 1530 and rear wall 1523 of upper region 1511. In many embodiments, rear angle 1540 is approximately 70 degrees to approximately 110 degrees.

[0108] In another embodiment, the golf club head can comprise a hosel. The hosel can comprise a hosel notch. The hosel notch can allow for iron-like range of loft and lie angle adjustability. Although not illustrated in FIG. 16, golf club head 1500 also can have a cascading sole or an internal radius transition at the sole.

[0109] The golf club heads with energy storage characteristics discussed herein may be implemented in a variety of embodiments, and the foregoing discussion of these embodiments does not necessarily represent a complete description of all possible embodiments. Rather, the detailed description

of the drawings, and the drawings themselves, disclose at least one preferred embodiment of golf club heads with energy storage characteristics, and may disclose alternative embodiments of golf club heads with tiered internal thin sections.

[0110] Replacement of one or more claimed elements constitutes reconstruction and not repair. Additionally, benefits, other advantages, and solutions to problems have been described with regard to specific embodiments. The benefits, advantages, solutions to problems, and any element or elements that may cause any benefit, advantage, or solution to occur or become more pronounced, however, are not to be construed as critical, required, or essential features or elements of any or all of the claims, unless such benefits, advantages, solutions, or elements are expressly stated in such claims.

[0111] As the rules to golf may change from time to time (e.g., new regulations may be adopted or old rules may be eliminated or modified by golf standard organizations and/or governing bodies such as the United States Golf Association (USGA), the Royal and Ancient Golf Club of St. Andrews (R&A), etc.), golf equipment related to the apparatus, methods, and articles of manufacture described herein may be conforming or non-conforming to the rules of golf at any particular time. Accordingly, golf equipment related to the apparatus, methods, and articles of manufacture described herein may be advertised, offered for sale, and/or sold as conforming or non-conforming golf equipment. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

[0112] While the above examples may be described in connection with a driver-type golf club, the apparatus, methods, and articles of manufacture described herein may be applicable to other types of golf club such as a fairway wood-type golf club, a hybrid-type golf club, an iron-type golf club, a wedge-type golf club, or a putter-type golf club. Alternatively, the apparatus, methods, and articles of manufacture described herein may be applicable to other type of sports equipment such as a hockey stick, a tennis racket, a fishing pole, a ski pole, etc.

[0113] Moreover, embodiments and limitations disclosed herein are not dedicated to the public under the doctrine of dedication if the embodiments and/or limitations: (1) are not expressly claimed in the claims; and (2) are or are potentially equivalents of express elements and/or limitations in the claims under the doctrine of equivalents.

What is claimed is:

1. A golf club head comprising:
a hollow body comprising:
a strikeface;
a heel region;
a toe region opposite the heel region;
a sole;
and
a crown comprising:
an upper region comprising a top rail; and
a lower region;
wherein:
a cavity is located below the top rail, is located above the lower region of the crown, and is defined at least in part by the upper and lower regions of the crown;
and
the cavity comprises:
a top wall;
a back wall;

a bottom incline;
a back cavity angle measured between the top and back walls of the cavity;
and
at least one channel.

2. The golf club head of claim 1, wherein:
the upper region of the crown comprises the top and back walls of the cavity; and
the lower region of the crown comprises the bottom incline of the cavity.

3. The golf club head of claim 1, wherein:
the back cavity angle is approximately 70 degrees to approximately 110 degrees.

4. The golf club head of claim 1, wherein:
the upper region of the crown further comprises:
a rear wall adjacent to the top wall of the cavity; and
a rear angle measured between the top wall of the cavity and the rear wall of the upper region of the crown.

5. The golf club head of claim 4, wherein:
the rear angle is approximately 70 degrees to approximately 110 degrees.

6. The golf club head of claim 1, wherein:
the back wall of the cavity is substantially parallel to the strikeface.

7. The golf club head of claim 1, wherein:
an apex of the top wall is approximately 0.25 inch to approximately 1.25 inch below an apex of the top rail.

8. The golf club head of claim 7, wherein:
a second inflection point is at least approximately 0.5 inch to approximately 1.5 inches below an apex of the top rail.

9. The golf club head of claim 8, wherein:
the second inflection point is approximately 0.5 inches to approximately 2 inches above a lowest point of the sole.

10. The golf club head of claim 1, wherein:
the at least one channel extends from the heel region to the toe region.

11. The golf club head of claim 1, wherein:
a channel width of the at least one channel is substantially constant throughout the channel.

12. The golf club head of claim 1, wherein:
a channel toe region width of the at least one channel is smaller than a channel heel region width of the channel.

13. The golf club head of claim 1, further comprising:
a cascading sole;
wherein the cascading sole comprises an internal radius

transition region from the strikeface to the sole;
and the internal transition region comprises:

a first tier comprising a first thickness;
a second tier comprising a second thickness different than the first thickness; and
a tier transition region between the first tier and the second tier.

14. The golf club head of claim 13, wherein the internal transition region further comprises a third tier.

15. A golf club comprising:
a hollow-bodied golf club head comprising:
a strikeface;
a heel region;
a toe region opposite the heel region;
a sole;
and
a crown comprising:
an upper region comprising a top rail; and
a lower region;

and
a shaft coupled to the hollow-bodied golf club head;
wherein:
a cavity is located below the top rail, is located above the lower region of the crown, and is defined at least in part by the upper and lower regions of the crown;
and
the cavity comprises:
a top wall;
a back wall;
a bottom incline;
a back cavity angle measured between the top and back walls of the cavity;
and
at least one channel.

16. The golf club of claim **15**, wherein:
the upper region of the crown further comprises:
a rear wall adjacent to the top wall of the cavity; and
a rear angle measured between the top wall of the cavity and the rear wall of the upper region of the crown.

17. The golf club of claim **15**, further comprising:
a cascading sole;
wherein the cascading sole comprises an internal radius transition region from the strikeface to the sole;
and the internal transition region comprises:
a first tier comprising a first thickness;
a second tier comprising a second thickness different than the first thickness; and
a tier transition region between the first tier and the second tier.

18. A method for manufacturing a golf club head, comprising:
providing a body, the body having:
a strikeface;
a heel region;

and
a toe region opposite the heel region;
a sole;
and
a crown comprising:
an upper region comprising a top rail; and
a lower region;
wherein:
a cavity is located below the top rail, is located above the lower region of the crown, and is defined at least in part by the upper and lower regions of the crown;
and
the cavity comprises:
a top wall;
a back wall adjacent to the top wall;
a bottom incline adjacent to the back wall;
a back cavity angle measured between the top and back walls of the cavity;
and
at least one channel.

19. The method of claim **18**, wherein:
providing the body further comprises the body having a cascading sole;
wherein:
the cascading sole comprises an internal radius transition region from the strikeface to the sole;
and the internal transition region comprises:
a first tier comprising a first thickness;
a second tier comprising a second thickness different than the first thickness; and
a tier transition region between the first tier and the second tier.

20. The method of claim **19**, wherein the internal transition region further comprises a third tier.

* * * * *