



(51) International Patent Classification:
A61F 2/24 (2006.01)

(21) International Application Number:
PCT/US2020/018115

(22) International Filing Date:
13 February 2020 (13.02.2020)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
62/805,847 14 February 2019 (14.02.2019) US
62/944,325 05 December 2019 (05.12.2019) US

(71) Applicant: **EDWARDS LIFESCIENCES CORPORATION** [US/US]; One Edwards Way, Irvine, CA 92614 (US).

(72) Inventors: **DIXON, Eric, Robert**; Edwards Lifesciences, One Edwards Way, Legal Department, Irvine, CA 92614 (US). **FRESCHAUF, Lauren, R.**; Edwards Lifesciences, One Edwards Way, Legal Department, Irvine, CA 92614 (US). **FOREMAN, Rachel, Liat, David**; Edwards Lifesciences, One Edwards Way, Legal Department, Irvine, CA 92614 (US). **GOHRES, Rachel, Ann**; Edwards Lifesciences, One Edwards Way, Legal Department, Irvine, CA

92614 (US). **POPP, Michael, J.**; Edwards Lifesciences, One Edwards Way, Legal Department, Irvine, CA 92614 (US). **OKOS, Chris, J.**; Edwards Lifesciences, One Edwards Way, Legal Department, Irvine, CA 92614 (US). **OBERWISE, Eric, Michael**; Edwards Lifesciences, One Edwards Way, Legal Department, Irvine, CA 92614 (US). **FORD, Steven, M.**; Edwards Lifesciences, One Edwards Way, Legal Department, Irvine, CA 92614 (US). **KEPLINGER, Stefan, Florian**; Edisonstrasse 6, 85716 Unterschleissheim (DE).

(74) Agent: **RICHARDSON, Thomas, C.** et al.; Edwards Lifesciences, One Edwards Way, Irvine, CA 92614 (US).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW.

(54) Title: HEART VALVE SEALING DEVICES AND DELIVERY DEVICES THEREFOR

(57) Abstract: Valve repair devices and systems configured to detect proper valve leaflet insertion. The valve repair device can have an indicator that moves, is positioned, or otherwise changes in response to engagement with the valve leaflet. When the indicator indicates that the valve leaflet is properly positioned in the valve repair device, the valve repair device is closed.




FIG. 13



(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

- *with international search report (Art. 21(3))*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

HEART VALVE SEALING DEVICES AND DELIVERY DEVICES THEREFOR**BACKGROUND**

[0001] The present application claims the benefit of US Provisional Patent Application No. 62/805,847, filed on February 14, 2019, titled “Heart Valve Sealing Devices and Delivery Devices Therefor” and US Provisional Patent Application No. 62/944,325, filed on December 5, 2019, titled “Leaflet Depth Indicators,” which are incorporated herein by reference in their entirety for all purposes.

BACKGROUND

[0002] The native heart valves (i.e., the aortic, pulmonary, tricuspid, and mitral valves) serve critical functions in assuring the forward flow of an adequate supply of blood through the cardiovascular system. These heart valves can be damaged, and thus rendered less effective, by congenital malformations, inflammatory processes, infectious conditions, disease, etc. Such damage to the valves can result in serious cardiovascular compromise or death. Damaged valves can be surgically repaired or replaced during open heart surgery. However, open heart surgeries are highly invasive, and complications may occur. Transvascular techniques can be used to introduce and implant prosthetic devices in a manner that is much less invasive than open heart surgery. As one example, a transvascular technique useable for accessing the native mitral and aortic valves is the trans-septal technique. The trans-septal technique comprises advancing a catheter into the right atrium (e.g., inserting a catheter into the right femoral vein, up the inferior vena cava and into the right atrium). The septum is then punctured, and the catheter passed into the left atrium. A similar transvascular technique can be used to implant a prosthetic device within the tricuspid valve that begins similarly to the trans-septal technique but stops short of puncturing the septum and instead turns the delivery catheter toward the tricuspid valve in the right atrium.

[0003] A healthy heart has a generally conical shape that tapers to a lower apex. The heart is four-chambered and comprises the left atrium, right atrium, left ventricle, and right ventricle. The left and right sides of the heart are separated by a wall generally referred to as the septum. The native mitral valve of the human heart connects the left atrium to the left ventricle. The mitral valve has a very different anatomy than other native heart valves. The mitral valve includes an annulus portion, which is an annular portion of the native valve tissue surrounding the mitral valve orifice, and a pair of cusps, or leaflets, extending downward from the annulus into the left ventricle. The mitral valve annulus can form a “D”-

shaped, oval, or otherwise out-of-round cross-sectional shape having major and minor axes. The anterior leaflet can be larger than the posterior leaflet, forming a generally “C”-shaped boundary between the abutting sides of the leaflets when they are closed together.

[0004] When operating properly, the anterior leaflet and the posterior leaflet function together as a one-way valve to allow blood to flow only from the left atrium to the left ventricle. The left atrium receives oxygenated blood from the pulmonary veins. When the muscles of the left atrium contract and the left ventricle dilates (also referred to as “ventricular diastole” or “diastole”), the oxygenated blood that is collected in the left atrium flows into the left ventricle. When the muscles of the left atrium relax and the muscles of the left ventricle contract (also referred to as “ventricular systole” or “systole”), the increased blood pressure in the left ventricle urges the sides of the two leaflets together, thereby closing the one-way mitral valve so that blood cannot flow back to the left atrium and is instead expelled out of the left ventricle through the aortic valve. To prevent the two leaflets from prolapsing under pressure and folding back through the mitral annulus toward the left atrium, a plurality of fibrous cords called chordae tendineae tether the leaflets to papillary muscles in the left ventricle.

[0005] Valvular regurgitation involves the valve improperly allowing some blood to flow in the wrong direction through the valve. For example, mitral regurgitation occurs when the native mitral valve fails to close properly and blood flows into the left atrium from the left ventricle during the systolic phase of heart contraction. Mitral regurgitation is one of the most common forms of valvular heart disease. Mitral regurgitation can have many different causes, such as leaflet prolapse, dysfunctional papillary muscles, stretching of the mitral valve annulus resulting from dilation of the left ventricle, more than one of these, etc. Mitral regurgitation at a central portion of the leaflets can be referred to as central jet mitral regurgitation and mitral regurgitation nearer to one commissure (i.e., location where the leaflets meet) of the leaflets can be referred to as eccentric jet mitral regurgitation. Central jet regurgitation occurs when the edges of the leaflets do not meet in the middle and thus the valve does not close, and regurgitation is present.

SUMMARY

[0006] This summary is meant to provide some examples and is not intended to be limiting of the scope of the invention in any way. For example, any feature included in an example of this summary is not required by the claims, unless the claims explicitly recite the features.

Also, the features, components, steps, concepts, etc. described in examples in this summary and elsewhere in this disclosure can be combined in a variety of ways. Various features and steps as described elsewhere in this disclosure may be included in the examples summarized here.

[0007] In one example embodiment, a heart valve treatment device or system is configured to detect aspects pertaining to valve leaflet insertion (e.g., depth of leaflet insertion, thickness of leaflet tissue captured, etc.). The device/system can have an indicator that moves, is positioned, and/or changes shape in response to engagement with the valve leaflet. When the position of the indicator indicates that the valve leaflet is properly positioned in the device/system, the device/system can be closed.

[0008] In one example embodiment, a heart valve treatment device/system or valve repair device/system for repairing a native valve of a patient includes a clasp and a leaflet indicator. The clasp (e.g., all or a portion thereof) is moveable to form an opening or leaflet receiving area. The opening or leaflet receiving area can be formed between two portions of the clasp (e.g., a fixed arm and a movable arm, etc.), between the clasp or a portion thereof and another portion of the device, between the clasp and a paddle of the device, between the clasp and an anchor of the device, between a movable arm of the clasp and a paddle of the device, etc. The leaflet indicator is moveable, is re-positionable, and/or changes shape or configuration in the opening or receiving area to indicate whether a leaflet of the native valve is inserted into the opening or receiving area to at least a minimum desired insertion depth and/or a minimum desired tissue thickness. The leaflet indicator can be configured the same as or similar to any of the indicators shown in any of the figures or described anywhere in this disclosure. For example, the leaflet indicator can comprise one or more indicator arms, one or more radiopaque markers, one or more springs, one or more levers, one or more snap-through portions, one or more tabs, one or more pads, one or more coils, one or more deflectable portions, one or more hoops or hoop-shaped portions, one or more flattenable indicators, one or more indicator wings, etc.

[0009] The heart valve treatment device/system or valve repair device/system can include one or more of the features or components described with respect to other devices shown in any of the figures or described anywhere in this disclosure. For example, in some implementations, the device/system includes one or more of an anchor portion, anchor, coaption portion, coaption element, paddle, pair of paddles, plurality of paddles, delivery

sheath, delivery catheter, actuation element, shaft, actuation lines/sutures, cap, collar, cover, braided material, strip of material, etc.

[0010] In some implementations, the device/system comprises a shaft and a proximal portion (e.g., collar, coaption portion, coaption element, disk, cover, post, tube, etc.) that the shaft extends through, and a cap attached to the shaft such that the cap can be moved by the shaft away from the proximal portion. In some implementations, the device/system also includes a pair of paddles attached to the cap. The device/system can be configured such that movement of the cap toward the proximal portion causes the pair of paddles to move to the closed position, and movement of the cap away from the proximal portion causes the pair of paddles to move to the open position. In some implementations, the device/system further includes a coaption element configured to fill space between leaflets of a native valve.

[0011] In one example embodiment, a heart valve treatment device/system or valve repair device/system for repairing a native valve of a patient includes a clasp and a plurality of indicator arms. The clasp (e.g., all or a portion thereof) is moveable to form an opening or leaflet receiving area. The opening or leaflet receiving area can be formed between two portions of the clasp (e.g., a fixed arm and a movable arm, etc.), between the clasp or a portion thereof and another portion of the device, between the clasp and a paddle of the device, between the clasp and an anchor of the device, between a movable arm of the clasp and a paddle of the device, etc. In some implementations, the plurality of indicator arms have different lengths and are moveable in the opening or receiving area to indicate whether a leaflet of the native valve is inserted into the opening or receiving area to at least a minimum desired insertion depth and/or a minimum desired tissue thickness.

[0012] In one example embodiment, a heart valve treatment device/system or valve repair device/system for repairing a native valve of a patient includes a paddle, a hoop shaped clasp, and an indicator arm. The paddle and the clasp are moveable to form an opening between the clasp and the paddle. The indicator arm is disposed between two sides of the hoop shaped clasp and is moveable in the opening to indicate whether a leaflet of the native valve is inserted into the opening between the paddle and the clasp to at least a minimum desired insertion depth.

[0013] In one example embodiment, a heart valve treatment device/system or valve repair device/system for repairing a native valve of a patient includes a clasp and a flattenable indicator. The clasp (e.g., all or a portion thereof) is moveable to form an opening or receiving area. The opening or leaflet receiving area can be formed between two portions of

the clasp (e.g., a fixed arm and a movable arm, etc.), between the clasp or a portion thereof and another portion of the device, between the clasp and a paddle of the device, between the clasp and an anchor of the device, between a movable arm of the clasp and a paddle of the device, etc. The flattenable indicator is in the opening or receiving area to indicate whether a leaflet of the native valve is inserted into the opening or receiving area to at least a minimum desired insertion depth and/or a minimum desired tissue thickness.

[0014] In one example embodiment, a heart valve treatment device/system or valve repair device/system for repairing a native valve of a patient includes a hoop shaped clasp and an indicator (e.g., an indicator arm, spring, etc.). The clasp (e.g., all or a portion thereof) is moveable to form an opening or receiving area. The opening or leaflet receiving area can be formed between two portions of the clasp (e.g., a fixed arm and a movable arm, etc.), between the clasp or a portion thereof and another portion of the device, between the clasp and a paddle of the device, between the clasp and an anchor of the device, between a movable arm of the clasp and a paddle of the device, etc.

[0015] In one embodiment, the indicator spans the hoop shaped clasp and is deformable through the hoop shaped clasp to indicate whether a leaflet of the native valve is inserted into the opening or receiving area to at least a minimum desired insertion depth and/or a minimum desired tissue thickness.

[0016] In one embodiment, the indicator comprises an indicator arm disposed between two sides of the hoop shaped clasp. The indicator arm can have a curved portion that is moveable through the hoop shaped clasp to indicate whether a leaflet of the native valve is inserted into the opening or receiving area between the paddle and the clasp to at least a minimum desired insertion depth and/or a minimum desired tissue thickness.

[0017] In one embodiment, the indicator comprises a spring disposed or positionable in the opening or receiving area to indicate whether a leaflet of the native valve is inserted into the opening or receiving area between the paddle and the clasp to at least a minimum desired insertion depth and/or a minimum desired tissue thickness.

[0018] In one embodiment, the indicator comprises at least one indicator wing that extends outward from a side of the clasp at an angle to indicate whether a leaflet of the native valve is inserted into the opening or receiving area between the paddle and the clasp to at least a minimum desired insertion depth and/or a minimum desired tissue thickness.

[0019] In one embodiment, the indicator comprises a first leaflet indicator and a second leaflet indicator that are spaced apart when a leaflet of a native valve is inserted into the

opening between the paddle and the clasp to at least a minimum desired insertion depth. In one embodiment, the first leaflet indicator and the second leaflet indicator are in contact in the absence of a leaflet of the native valve in the opening or receiving area between the paddle and the clasp.

[0020] In one example embodiment, a heart valve treatment device/system or valve repair device/system for repairing a native valve of a patient includes a clasp and an indicator arm. The clasp (e.g., all or a portion thereof) is moveable to form an opening or leaflet receiving area. The opening or leaflet receiving area can be formed between two portions of the clasp (e.g., a fixed arm and a movable arm, etc.), between the clasp or a portion thereof and another portion of the device, between the clasp and a paddle of the device, between the clasp and an anchor of the device, between a movable arm of the clasp and a paddle of the device, etc. A single actuation line extends from a delivery device to the clasp and the indicator arm. In some implementations, the single actuation line is configured to separately actuates the clasp and the indicator arm.

[0021] In one example embodiment, a heart valve treatment device/system or valve repair device/system for repairing a native valve of a patient includes a clasp and a flexible indicator. The clasp (e.g., all or a portion thereof) is moveable to form an opening or leaflet receiving area. The opening or leaflet receiving area can be formed between two portions of the clasp (e.g., a fixed arm and a movable arm, etc.), between the clasp or a portion thereof and another portion of the device, between the clasp and a paddle of the device, between the clasp and an anchor of the device, between a movable arm of the clasp and a paddle of the device, etc. The flexible indicator is fixedly connected to one arm and slidably connected to the other arm.

[0022] In one example embodiment, a heart valve treatment device/system or valve repair device/system for repairing a native valve of a patient includes a clasp and at least one indicator. The clasp (e.g., all or a portion thereof) is moveable to form an opening or leaflet receiving area. The opening or leaflet receiving area can be formed between two portions of the clasp (e.g., a fixed arm and a movable arm, etc.), between the clasp or a portion thereof and another portion of the device, between the clasp and a paddle of the device, between the clasp and an anchor of the device, between a movable arm of the clasp and a paddle of the device, etc.

[0023] In one embodiment, the at least one indicator extends from the paddle into the opening or leaflet receiving area. In some implementations, the at least one indicator is

configured such that when the opening or leaflet receiving area is closed and the indicator is unobstructed, at least a portion of the at least one indicator extends through the clasp. In some implementations, the at least one indicator is also configured such that when the opening or leaflet receiving area is closed and the at least one indicator engages a valve leaflet, a portion of the at least one indicator extends through the paddle.

[0024] In one embodiment, the at least one indicator extends from one of the fixed arm and the paddle into the opening or receiving area. The at least one indicator can be configured such that when the opening or receiving area is closed and the indicator is unobstructed, at least a portion of the indicator extends through the moveable arm of the clasp. The at least one indicator can also be configured such that when the opening or receiving area is closed and the indicator engages a valve leaflet, a portion of the indicator extends through the fixed arm of the clasp.

[0025] In some implementations, when the opening or receiving area is closed and the at least one indicator engages a valve leaflet, a portion of the at least one indicator extends through a paddle of the device/system. In some implementations, no portion of the at least one indicator extends through the moveable arm of the clasp when the opening or receiving area is closed and the indicator engages a valve leaflet.

[0026] In some implementations, the at least one indicator has a fixed end connected to the paddle and a free end. In some implementations, the at least one indicator has a fixed end connected to the fixed arm and a free end. In some implementations, the at least one indicator is integrally formed with the fixed arm of the clasp. The at least one indicator can be curved, straight, angled, spherical, semi-spherical, and/or another shape.

[0027] In some implementations, a moveable arm of the clasp includes a cutout that the at least one indicator extends through when the opening or receiving area is closed and the indicator is unobstructed. In some implementations, the fixed arm of the clasp includes a cutout that the at least one indicator extends through. In some implementations, a paddle of the device/system includes a cutout that the at least one indicator extends through when the opening between the paddle and the moveable arm of the clasp is closed and the indicator engages a valve leaflet.

[0028] In some implementations, a smaller portion of the at least one indicator extends through the cutout of the paddle when the opening or receiving area (e.g., between a movable arm of the clasp and the paddle) is closed and the indicator is unobstructed, and a larger

portion of the at least one indicator extends through the cutout of the paddle when the opening or receiving area is closed and the indicator engages a valve leaflet.

[0029] In one example method of implanting a valve repair device an indicator of a clasp is engaged. The indicator is disengaged when a leaflet of the mitral valve is not contacted by the indicator. The clasp is closed when the indicator is engaged, and the leaflet is contacted by the indicator.

[0030] In one example method of implanting a valve repair device on a native valve (e.g., on a mitral valve, tricuspid valve, etc.) of a patient an indicator arm of a clasp is actuated. The indicator arm is returned to an unactuated position when a leaflet of the native valve is not engaged by the indicator arm. The clasp of the valve repair device is closed when the leaflet of the native valve is engaged by the actuated indicator arm. In some embodiments, one or more paddles of the valve repair device are closed to bring one or more leaflets of the native valve into contact with a coaption element of the valve repair device. In some embodiments, one or more paddles of the valve repair device are closed to bring the leaflets into contact with each other.

[0031] In one example method of implanting a valve repair device an indicator gauge of a clasp measures an engaged depth of a leaflet of the native valve. The indicator gauge is disengaged when the engaged depth is below a desired depth. The clasp is closed when the engaged depth is at least equal to the desired depth.

[0032] The above methods can be performed on a living animal or on a simulation, such as on a cadaver, cadaver heart, simulator (e.g. with the body parts, heart, tissue, etc. being simulated), etc.

[0033] In one example embodiment, a valve repair device includes a plurality of paddles, a plurality of clasps, and an insertion depth indicator. In some embodiments, the valve repair device can also include a coaption element. The plurality of paddles can be connected to the coaption element and/or another portion of the device. Each paddle has an inner portion and an outer portion. The paddles are moveable between an open position and a closed position. A clasp is attached to each of the plurality of paddles. Each clasp includes a fixed arm, a moveable arm, and a joint or hinge. The fixed arm is attached to the inner portion of the paddle and/or another portion of the valve repair device. The moveable arm and/or the fixed arm can optionally have one or more friction-enhancing portions, such as a barbed portion, ridged portion, textured portion, protrusion portion, etc. The hinge portion connects the moveable arm to the fixed arm. The insertion depth indicator indicates whether a leaflet of

the native valve is inserted into an opening of the clasp formed between the fixed and moveable arms to at least a minimum desired insertion depth.

[0034] In one example embodiment, a heart valve treatment device/system or valve repair device/system for repairing a native valve of a patient includes a plurality of paddles and a plurality of clasps. The plurality of paddles are moveable between an open position and a closed position. A clasp is attached to each of the paddles. The clasp includes a fixed arm, a moveable arm, a hinge portion, an indicator arm, and an indicator hinge portion. The moveable arm and/or the fixed arm can have one or more friction-enhancing portions, such as a barbed portion, ridged portion, textured portion, protrusion portion, etc. The hinge portion connects the moveable arm to the fixed arm. The indicator arm is connected to the fixed arm by the hinge portion.

[0035] In one example embodiment, a heart valve treatment device/system or valve repair device/system for repairing a native valve of a patient includes a plurality of paddles, a plurality of clasps, and a compressible indicator. The paddles are moveable between an open position and a closed position. A clasp is attached to each of the plurality of paddles. Each clasp has a fixed arm, a moveable arm, and a hinge portion. The fixed arm of each clasp is attached to the paddle and/or another portion of the valve repair device. The moveable arm is connected to the fixed arm by a hinge portion. The compressible indicator is configured to engage a leaflet of the native valve.

[0036] In one example embodiment, a heart valve treatment device/system or valve repair device/system for repairing a native valve of a patient includes a plurality of paddles, a plurality of clasps, a plurality of indicators, and a plurality of markers. The paddles are moveable between an open position and a closed position. A clasp is attached to each of the paddles. Each clasp includes a fixed arm, a moveable arm, and a hinge portion. The fixed arm of each clasp is attached to a paddle and/or another portion of the valve repair device. The moveable arm and/or the fixed arm can have one or more friction-enhancing portions, such as a barbed portion, ridged portion, textured portion, protrusion portion, etc. The hinge portion connects the moveable arm to the fixed arm. Each marker is attached to the indicator, the fixed arm, and/or the moveable arm.

[0037] In one example embodiment, a heart valve treatment device/system or valve repair device/system for repairing a native valve of a patient includes a pair of paddles, a pair of clasps, and an insertion depth gauge. The pair of paddles are moveable between an open position and a closed position. A clasp is attached to each of the paddles. Each clasp includes

a fixed arm, a moveable arm, and a hinge portion. The fixed arm is attached to the paddle and/or another portion of the valve repair device. The moveable arm and/or the fixed arm can have one or more friction-enhancing portions, such as a barbed portion, ridged portion, textured portion, protrusion portion, etc. The hinge portion connects the moveable arm to the fixed arm. The insertion depth gauge indicates an insertion depth of a leaflet of the native valve.

[0038] In one example embodiment, a heart valve treatment device/system or valve repair device/system for repairing a native valve of a patient includes a pair of paddles, a pair of clasps, an indicator arm, and an actuation suture. The pair of paddles are moveable between an open position and a closed position. A clasp is attached to each of the paddles. Each clasp includes a fixed arm, a moveable arm, and a hinge portion. The fixed arm is attached to the paddle and/or another portion of the valve repair device. The moveable arm and/or the fixed arm can have one or more friction-enhancing portions, such as a barbed portion, ridged portion, textured portion, protrusion portion, etc. The moveable arm is moveable between an open position and a closed position. The hinge portion connects the moveable arm to the fixed arm. An indicator hinge portion connects the indicator arm to the fixed arm of the clasp. In some implementations, the actuation suture extends from a delivery device to first and second moveable loops attached to the moveable clasp arm and the indicator arm, respectively. In some implementations, the moveable clasp arm and the indicator arm are separately actuatable with the single actuation suture.

[0039] In one example embodiment, a clasp for a heart valve treatment device/system or valve repair device/system comprises an indicator, such as an insertion depth indicator configured to provide an indication of an insertion depth and/or thickness of a leaflet of a native valve within or adjacent the clasp when the heart valve treatment device is implanted in a native heart valve. The indicator can be configured the same as or similar to any of the indicators shown in any of the figures or described anywhere in this disclosure. For example, the indicator can comprise one or more indicator arms, one or more radiopaque markers, one or more springs, one or more levers, one or more snap-through portions, one or more tabs, one or more pads, one or more coils, one or more deflectable portions, one or more hoops or hoop-shaped portions, one or more flattenable indicators, one or more indicator wings, etc.

[0040] In some implementations, the clasp further comprises a fixed arm attachable to the device/system (e.g., to a paddle, anchor, post, arm, extension, cover, etc. of the device/system) and a moveable arm. The fixed arm and/or the moveable arm can include a

friction-enhancing portion (e.g., a friction-enhancing element, barbs, protrusions, ridges, textured surface, sticky surface, etc.). A connection portion or hinge portion connects (e.g., jointedly, hingeably, etc.) the moveable arm to the fixed arm.

[0041] In some implementations, the indicator or insertion depth indicator is deformable, and a shape of the indicator indicates the insertion depth and/or thickness of the leaflet of the native valve.

[0042] In some implementations, the indicator is moveable, and a position of the indicator indicates the insertion depth and/or thickness of the leaflet of the native valve.

[0043] In some implementations, the relative position of the indicator and at least one of the fixed arm and the moveable arm indicates the insertion depth of the leaflet of the native valve.

[0044] In some implementations, the indicator comprises a plurality of flexible arms (e.g., 2, 3, 4, 5, 6, or more arms) attached to the moveable arm between the clasp hinge portion and the friction-enhancing portion. The insertion depth of the leaflet can be indicated by the number of flexible arms deformed by engagement with the leaflet.

[0045] In some implementations, the indicator comprises a plurality of flexible arms (e.g., 2, 3, 4, 5, 6, or more arms) attached to the fixed arm. The insertion depth of the leaflet can be indicated by the number of flexible arms deformed by engagement with the leaflet.

[0046] In some implementations, the indicator comprises an indicating pad arranged on at least one of the moveable arm and the fixed arm that is configured to deform when engaged by the leaflet of the native valve. The insertion depth and/or thickness of the leaflet can be indicated by a size of a deformed portion of the indicating pad.

[0047] In some implementations, the indicator is actuatable between undeployed and actuated positions. In some implementations, the indicator is actuated or actuatable when the clasp is at least partially open to determine the insertion depth of the leaflet of the native valve.

[0048] In some implementations, the insertion depth indicator intersects at least one of the fixed arm and the movable arm when the insertion depth indicator is in the actuated position.

[0049] In some implementations, the moveable arm is hoop-shaped, and the friction-enhancing portion comprises longitudinally staggered barbs.

[0050] In some implementation, the clasp(s) described above can be included in a heart valve treatment device/system or valve repair device/system. The heart valve treatment device/system or valve repair device/system can include one or more of the features or

components shown in any of the figures or described with respect to any of the devices/systems in this disclosure. For example, in some implementations, the device/system includes one or more of an anchor portion, anchor, coaption portion, coaption element, paddle, pair of paddles, plurality of paddles, delivery sheath, delivery catheter, actuation element, shaft, actuation lines/sutures, cap, collar, cover, braided material, strip of material, etc.

[0051] In some implementations, the device/system comprises a shaft and a proximal portion (e.g., collar, coaption portion, coaption element, disk, cover, post, tube, etc.) that the shaft extends through, and a cap attached to the shaft such that the cap can be moved by the shaft away from the proximal portion. In some implementations, the device/system also includes a pair of paddles attached to the cap. The device/system can be configured such that movement of the cap toward the proximal portion causes the pair of paddles to move to the closed position, and movement of the cap away from the proximal portion causes the pair of paddles to move to the open position. In some implementations, the device/system further includes a coaption element configured to fill space between leaflets of a native valve.

[0052] An understanding of the nature and advantages of the present invention are set forth in the following description and claims, particularly when considered in conjunction with the accompanying drawings in which like parts bear like reference numerals.

BRIEF DESCRIPTION OF THE DRAWINGS

[0053] Figures 1, 1A, and 2–6 show an implantable prosthetic device, in various stages of deployment;

[0054] Figures 7–12 show the implantable prosthetic device of Figures 1–6 being delivered and implanted within a native mitral valve;

[0055] Figures 13–13A show an implantable prosthetic device;

[0056] Figures 14–23, 23A, and 23B show an implantable prosthetic device being delivered and implanted within a native mitral valve;

[0057] Figures 24 and 25 show schematic views of an example embodiment of a clasp for an implantable prosthetic device;

[0058] Figures 24A and 25A show schematic views of an example embodiment of a clasp for an implantable prosthetic device;

[0059] Figures 26–29 show the example clasp of Figures 24–25 being deployed to engage with a leaflet of a native valve;

[0060] Figures 30-33 show front views of example embodiments of clasps for an implantable prosthetic device;

[0061] Figures 34-47 show an implantable prosthetic device having clasps with indicator arms being delivered and implanted within a native valve;

[0062] Figures 48-61 show an example embodiment of a clasp for an implantable prosthetic device;

[0063] Figures 62-66 show an example clasp (which can be configured to be the same as or similar to other barbed clasps herein) being deployed to engage with a leaflet of a native valve;

[0064] Figures 67 and 68 show an example embodiment of a laser cut clasp and indicator;

[0065] Figures 67A and 68A show an example embodiment of a laser cut clasp and indicator;

[0066] Figure 69 shows an example embodiment of a laser cut clasp with a plurality of indicators;

[0067] Figures 70-71 show an example embodiment of a clasp for an implantable prosthetic device;

[0068] Figures 70A-71A show an example embodiment of a clasp for an implantable prosthetic device;

[0069] Figures 72-75 show the example clasp of Figures 70-71 or Figures 70A-71A being deployed to engage with a leaflet of a native valve;

[0070] Figures 76-77 each show a moveable arm and indicator arms according to example embodiments of an implantable prosthetic device having a T-bar;

[0071] Figures 78-79 show an example embodiment of a clasp with indicator arms and a T-bar for an implantable prosthetic device;

[0072] Figures 80-83 show the example clasp of Figures 78-79 being deployed to engage with a leaflet of a native valve;

[0073] Figure 84 shows an example embodiment of a clasp having an indicator arm with a curved indicator, for an implantable prosthetic device;

[0074] Figures 85-86 show schematic views of the example clasp of Figure 84;

[0075] Figures 87-90 show the example clasp of Figures 85-86 being deployed to engage with a leaflet of a native valve;

[0076] Figures 91-92 show a schematic view of an example embodiment of a clasp having an indicator arm and a flexible curve in the fixed arm as an indicator, for an implantable prosthetic device;

[0077] Figures 93-96 show the example clasp of Figures 91-92 being deployed to engage with a leaflet of a native valve;

[0078] Figures 97-98 show a schematic view of an example embodiment of a clasp having a flexible curve indicator in the moveable arm, for an implantable prosthetic device;

[0079] Figures 99, 100, and 100A show the example clasp of Figures 97-98 being deployed to engage with a leaflet of a native valve;

[0080] Figures 101 and 102 show a schematic view of an example embodiment of a clasp having a flexible curve indicator in the fixed arm, for an implantable prosthetic device;

[0081] Figure 103 shows an example embodiment of a moveable arm and an indicator of a clasp;

[0082] Figures 103A-103D show example embodiments of a moveable arm of clasp having various example embodiments of indicators;

[0083] Figures 104-106 show schematic views of example embodiments of a clasp having a flexible curve in the fixed arm as an indicator, for an implantable prosthetic device;

[0084] Figures 107-109 show the example clasp of Figures 104-106 being deployed to engage with a leaflet of a native valve;

[0085] Figures 104A, 106A, 108A, and 109A show schematic views of an example embodiment of a clasp having flexible wing indicators on the moveable arm, for an implantable prosthetic device;

[0086] Figures 104B, 106B, 108B, and 109B show schematic views of an example embodiment of a clasp having flexible wing indicators on the moveable arm and a flexible indicator on the fixed arm, for an implantable prosthetic device;

[0087] Figures 104C, 106C, 108C, and 109C show schematic views of an example embodiment of a clasp having flexible bump indicators on the fixed and moveable arms, for an implantable prosthetic device;

[0088] Figures 104D, 106D, 108D, and 109D show schematic views of an example embodiment of a clasp having a flexible indicator, for an implantable prosthetic device;

[0089] Figures 104E, 106E, 108E, and 109E show schematic views of an example embodiment of a clasp having a flexible indicator, for an implantable prosthetic device;

[0090] Figure 110 shows an example embodiment of a moveable arm and fixed arm with flexible curve indicators of a clasp, for an implantable prosthetic device;

[0091] Figures 111-122 show an example embodiment of a clasp for an implantable prosthetic device having a flexible curved indicator;

- [0092] Figures 123 and 124 show schematic views of an example embodiment of a clasp having deflecting indicators on the moveable arm, for an implantable prosthetic device;
- [0093] Figures 123A and 124A show schematic views of an example embodiment of a clasp having deflecting indicators on the moveable arm, for an implantable prosthetic device;
- [0094] Figures 125, 126, and 127 show the example clasp of Figures 123 and 124 being deployed to engage with a leaflet of a native valve;
- [0095] Figures 125A, 126A, and 127A show the example clasp of Figures 123A and 124A being deployed to engage with a leaflet of a native valve;
- [0096] Figures 128, 129, and 129B show an example embodiment of a clasp with a spring indicator for an implantable prosthetic device;
- [0097] Figure 129C shows an example embodiment of a spring indicator for a clasp;
- [0098] Figures 129D and 129E show an example embodiment of a clasp with a spring indicator for an implantable prosthetic device;
- [0099] Figure 129F shows an example embodiment of a spring indicator for a clasp;
- [00100] Figures 129G and 129H show an example embodiment of a spring indicator for a clasp;
- [00101] Figures 129I and 129J show example embodiments of indicator elements for a spring indicator of a clasp;
- [00102] Figures 130, 131, and 132 show the example clasp of Figures 128 and 129 being deployed to engage with a leaflet of a native valve;
- [00103] Figures 128A and 129A show an example embodiment of a clasp with a spring indicator for an implantable prosthetic device;
- [00104] Figures 130A, 131A, and 132A show the example clasp of Figures 128A and 129A being deployed to engage with a leaflet of a native valve;
- [00105] Figures 133 and 134 show an example embodiment of a clasp with a spring indicator for an implantable prosthetic device;
- [00106] Figures 135, 136, and 137 show the example clasp of Figures 133 and 134 being deployed to engage with a leaflet of a native valve;
- [00107] Figures 133A and 134A show an example embodiment of a clasp with a spring indicator for an implantable prosthetic device;
- [00108] Figures 135A, 136A, and 137A show the example clasp of Figures 133A and 134A being deployed to engage with a leaflet of a native valve;

- [00109] Figures 133B and 134B show an example embodiment of a clasp with a spring indicator for an implantable prosthetic device;
- [00110] Figures 135B, 136B, and 137B show the example clasp of Figures 133B and 134B being deployed to engage with a leaflet of a native valve;
- [00111] Figures 138 and 139 show an example embodiment of a clasp with an indicator pad for an implantable prosthetic device;
- [00112] Figures 140, 141, and 142 show the example clasp of Figures 138 and 139 being deployed to engage with a leaflet of a native valve;
- [00113] Figures 138A and 139A show an example embodiment of a clasp with an indicator pad for an implantable prosthetic device;
- [00114] Figures 140A, 141A, and 142A show the example clasp of Figures 138A and 139A being deployed to engage with a leaflet of a native valve;
- [00115] Figures 143-152 show an example embodiment of a clasp for an implantable prosthetic device having suture holes;
- [00116] Figures 153-154 show the example clasp of Figure 143 being deployed to engage with a leaflet of a native valve;
- [00117] Figures 155-157 show an example actuation mechanism for use with implantable devices described herein;
- [00118] Figure 155A shows an example actuation mechanism for use with implantable devices described herein;
- [00119] Figures 158-160 show an example actuation mechanism for use with implantable devices described herein;
- [00120] Figures 161-163 show an example actuation mechanism for use with implantable devices described herein;
- [00121] Figures 164-166 show an example actuation mechanism for use with implantable devices described herein;
- [00122] Figures 164A and 164B show example actuation mechanisms for use with implantable devices described herein;
- [00123] Figures 167-168 show schematic views of an example embodiment of a clasp having a screw drive to capture tissue;
- [00124] Figures 169-171 show the example clasp of Figures 167-168 being deployed to engage with a leaflet of a native valve;

- [00125] Figures 172-173 show schematic views of an example embodiment of a clasp having a flexible indicator;
- [00126] Figures 174-176 show the example clasp of Figures 172-173 being deployed to engage with a leaflet of a native valve;
- [00127] Figures 177-178 show schematic views of an example embodiment of a clasp having a barbed wheel to capture tissue;
- [00128] Figures 179-181 show the example clasp of Figures 177-178 being deployed to engage with a leaflet of a native valve;
- [00129] Figures 182-183 show schematic views of an example embodiment of a clasp;
- [00130] Figures 184, 185, 186A, and 186B show the example clasp of Figures 182-183 being deployed to engage with a leaflet of a native valve;
- [00131] Figures 187-188 show schematic views of an example embodiment of a clasp with a belt;
- [00132] Figures 189-191 show the example clasp of Figures 187-188 being deployed to engage a leaflet of a native valve;
- [00133] Figures 192-193 show schematic views of an example embodiment of a clasp having an indicator;
- [00134] Figures 194-197 show the example clasp of Figures 192-193 being deployed to engage a leaflet of a native valve;
- [00135] Figures 198-199 show schematic views of an example embodiment of a clasp having an indicator;
- [00136] Figures 200-202 show the example clasp of Figures 198-199 being deployed to engage a leaflet of a native valve;
- [00137] Figure 202A illustrates an embodiment similar to Figure 202 where the indicator arm conforms to the shape of the valve leaflet;
- [00138] Figures 203-205 show an example actuation mechanism for use with implantable devices described herein;
- [00139] Figures 206-209 show an example embodiment of a clasp having an indicator with a shaped end;
- [00140] Figures 210-214 show schematic views of an example embodiment of a clasp having an indicator arm with a shaped end;
- [00141] Figures 215-216 show schematic views of an example embodiment of a clasp having an indicator;

- [00142] Figures 217-220 show the example clasp of Figures 215-216 being deployed to engage a leaflet of a native valve;
- [00143] Figures 221-222 show schematic views of an example embodiment of a clasp having an indicator and actuatable by a single suture line;
- [00144] Figures 223-225 show the example clasp of Figures 221-222 being deployed by using a single actuation line to engage a leaflet of a native valve;
- [00145] Figures 226-229 show a clasp having a flexible wire indicator according to an example embodiment, for an implantable prosthetic device;
- [00146] Figures 230-233 show a clasp having a flexible wire indicator according to an example embodiment, for an implantable prosthetic device;
- [00147] Figures 234-237 show a clasp having a flexible wire indicator according to an example embodiment, for an implantable prosthetic device;
- [00148] Figures 238-241 show a clasp having a flexible wire indicator according to an example embodiment, for an implantable prosthetic device;
- [00149] Figures 242-247 illustrate an example embodiment of a clasp with a leaflet insertion sensor;
- [00150] Figures 248-253 illustrate an example embodiment of a clasp with a leaflet insertion sensor;
- [00151] Figures 254-259 illustrate an example embodiment of a clasp with a leaflet insertion sensor;
- [00152] Figures 260-261 illustrate an example embodiment of a valve repair device with a leaflet insertion sensor;
- [00153] Figures 262-263 illustrate an example embodiment of a valve repair device with a leaflet insertion sensor;
- [00154] Figure 264 illustrates an example embodiment of a valve repair device with a leaflet insertion sensor;
- [00155] Figure 265 illustrates an example embodiment of a valve repair device with a leaflet insertion sensor;
- [00156] Figure 266 illustrates an example embodiment of a catheter for a valve actuation catheter;
- [00157] Figure 267 is a plot of current versus time of an example method for sensing leaflet capture;

- [00158] Figures 268 and 269 are plots of resistance versus time of an example method for sensing leaflet capture;
- [00159] Figures 270 and 271 are plots of capacitance versus time of an example method for sensing leaflet capture;
- [00160] Figures 272-274 are schematic illustrations of example embodiments of a curved indicator having a fixed end connected to an arm of a clasp and a free end;
- [00161] Figures 275-277 show the example indicator and example clasp of Figures 272-274 being deployed to engage with a leaflet of a native valve;
- [00162] Figures 278 and 279 illustrate an embodiment similar to the embodiment of Figures 272-274 where the curved indicator includes leaflet depth markers;
- [00163] Figures 278A and 279A are enlarged portions of Figures 278 and 279 as indicated by the circles in Figures 278 and 279;
- [00164] Figure 280 is an exploded perspective view of an example embodiment of a clasp and indicator;
- [00165] Figure 281 is a perspective view of the example clasp and example indicator of Figure 280 assembled with an inner paddle of a valve repair device;
- [00166] Figure 282 is a side view of the example clasp and example indicator of Figure 280 assembled with a paddle of a valve repair device;
- [00167] Figure 283 shows the example indicator and example clasp of Figure 282 with a native valve leaflet inserted into the clasp to a less than sufficient predetermined depth;
- [00168] Figures 284 shows the example indicator and example clasp of Figure 282 with a native valve leaflet inserted into the clasp to a sufficient predetermined depth;
- [00169] Figures 285–286 show an example embodiment of a clasp for an implantable prosthetic device;
- [00170] Figures 287–289 show the clasp of Figures 285–286 being deployed to engage with a leaflet of a native valve;
- [00171] Figures 290–291 show an example embodiment of a clasp for an implantable prosthetic device;
- [00172] Figures 292–294 show the clasp of Figures 290–291 being deployed to engage with a leaflet of a native valve;
- [00173] Figures 292A, 293A, and 294A show an example embodiment of a clasp for an implantable prosthetic device being deployed to engage with a leaflet of a native valve;

- [00174] Figures 295–296 show an example embodiment of a clasp for an implantable prosthetic device;
- [00175] Figures 297–299 show the clasp of Figures 295–296 being deployed to engage with a leaflet of a native valve;
- [00176] Figures 300–301 show an example embodiment of a clasp for an implantable prosthetic device;
- [00177] Figures 302–304 show the clasp of Figures 300–301 being deployed to engage with a leaflet of a native valve;
- [00178] Figures 305–306 show an example embodiment of a clasp for an implantable prosthetic device;
- [00179] Figure 306A shows an example embodiment of a clasp for an implantable prosthetic device;
- [00180] Figures 307–308 show an example embodiment of a clasp for an implantable prosthetic device;
- [00181] Figures 309–311 show the clasp of Figures 307–308 being deployed to engage with a leaflet of a native valve;
- [00182] Figures 309A, 310A, and 311A show an example embodiment of a clasp for an implantable prosthetic device being deployed to engage with a leaflet of a native valve;
- [00183] Figures 312–313 show an example embodiment of a clasp for an implantable prosthetic device;
- [00184] Figures 314–316 show the clasp of Figures 312–313 being deployed to engage with a leaflet of a native valve;
- [00185] Figures 314A, 315A, and 316A show an example embodiment of a clasp for an implantable prosthetic device being deployed to engage with a leaflet of a native valve;
- [00186] Figures 317–318 show an example embodiment of a clasp for an implantable prosthetic device;
- [00187] Figures 319–321 show the clasp of Figures 317–318 being deployed to engage with a leaflet of a native valve;
- [00188] Figures 319A, 320A, and 321A show an example embodiment of a clasp for an implantable prosthetic device being deployed to engage with a leaflet of a native valve;
- [00189] Figures 322–323 show an example embodiment of a clasp for an implantable prosthetic device;

- [00190] Figures 324–326 show the clasp of Figures 322–323 being deployed to engage with a leaflet of a native valve;
- [00191] Figures 324A, 325A, and 326A show an example embodiment of a clasp for an implantable prosthetic device being deployed to engage with a leaflet of a native valve;
- [00192] Figures 327–328 show an example embodiment of a clasp for an implantable prosthetic device;
- [00193] Figures 329–331 show the clasp of Figures 327–328 being deployed to engage with a leaflet of a native valve;
- [00194] Figures 332–333 show an example embodiment of a clasp for an implantable prosthetic device;
- [00195] Figures 334–336 show the clasp of Figures 332–333 being deployed to engage with a leaflet of a native valve;
- [00196] Figure 337 is a schematic illustration of a beam that exhibits snap-through buckling;
- [00197] Figure 338 is a graph of load versus displacement of a beam that exhibits snap-through buckling;
- [00198] Figure 339 is a profile view of an example embodiment of a clasp for an implantable prosthetic device;
- [00199] Figure 340 is a bottom view of the clasp of Figure 339;
- [00200] Figure 341 is a side view of the clasp of Figure 339;
- [00201] Figure 342 illustrates first and second stable states of a snap-through indicator of the clasp of Figure 339;
- [00202] Figures 343–345 show the clasp of Figures 339–342 being deployed to engage with a leaflet of a native valve;
- [00203] Figure 346 is a profile view of an example embodiment of a clasp for an implantable prosthetic device;
- [00204] Figure 347 is a bottom view of the clasp of Figure 346;
- [00205] Figure 348 is a side view of the clasp of Figure 346;
- [00206] Figure 349 illustrates first and second stable states of a snap-through indicator of the clasp of Figure 346;
- [00207] Figures 350–352 show the clasp of Figures 346–349 being deployed to engage with a leaflet of a native valve;
- [00208] Figure 353A illustrates an example embodiment of a flat part useable to make a snap-through indicator;

[00209] Figure 353B illustrates an example embodiment of a flat part useable to make a snap-through indicator;

[00210] Figure 353C illustrates an example embodiment of a flat part useable to make a snap-through indicator; and

[00211] Figure 353D illustrates bending of the flat parts of Figures 353A-353C to make snap-through indicators and the two stable states of the snap-through indicators.

DETAILED DESCRIPTION

[00212] As described herein, when one or more components are described as being connected, joined, affixed, coupled, attached, or otherwise interconnected, such interconnection may be direct as between the components or may be indirect such as through the use of one or more intermediary components. Also, as described herein, reference to a "member," "component," or "portion" shall not be limited to a single structural member, component, or element but can include an assembly of components, members, or elements. Also, as described herein, the terms "substantially" and "about" are defined as at least close to (and includes) a given value or state (preferably within 10% of, more preferably within 1% of, and most preferably within 0.1% of).

[00213] A prosthetic device can have a wide variety of different forms. For example, the prosthetic device can have any of the configurations disclosed by PCT Patent Application No. PCT/US2019/055320, filed October 9, 2019 and US Provisional Patent Application Serial No. 62/744031, filed on October 10, 2018, which are incorporated herein by reference in their entirety for all purposes. A prosthetic device can have an optional coaptation means or coaption element and at least one anchoring means or anchor. The coaption element is configured to be positioned within the native heart valve orifice to help fill the space between the leaflets and form a more effective seal between the native leaflets, thereby reducing or preventing regurgitation. The coaption element can have a structure that is impervious or resistant to blood and that allows the native leaflets to close around the coaption element during ventricular systole to block blood from flowing from the left or right ventricle back into the left or right atrium, respectively. The prosthetic device can be configured to seal against two or three native valve leaflets; that is, the device may be used in the native mitral (bicuspid) and tricuspid valves. The coaption element is sometimes referred to herein as a spacer because the coaption element can fill a space between improperly functioning native mitral or tricuspid leaflets that do not close completely.

[00214] The coaption element (e.g., spacer, coaptation element, etc.) can have various shapes. In some embodiments, the coaption element can have an elongated cylindrical shape having a round cross-sectional shape. In some embodiments, the coaption element can have an oval cross-sectional shape, a crescent cross-sectional shape, a rectangular cross-sectional shape, or various other non-cylindrical shapes. The coaption element can have an atrial portion positioned in or adjacent to the left atrium, a ventricular or lower portion positioned in or adjacent to the left ventricle, and a side surface that extends between the native leaflets. In embodiments configured for use in the tricuspid valve, the atrial or upper portion is positioned in or adjacent to the right atrium, and the ventricular or lower portion is positioned in or adjacent to the right ventricle, and the side surface that extends between the native tricuspid leaflets.

[00215] The anchor can be configured to secure the device to one or both of the native leaflets such that the coaption element is positioned between the two native leaflets. In embodiments configured for use in the tricuspid valve, the anchor is configured to secure the device to one, two, or three of the tricuspid leaflets such that the coaption element is positioned between the three native leaflets. In some embodiments, the anchor can attach to the coaption element at a location adjacent the ventricular portion of the coaption element. In some embodiments, the anchor can attach to an actuation element, such as a shaft or actuation wire, to which the coaption element is also attached.

[00216] The anchor of the implantable prosthetic device includes clasps to secure the native leaflet tissue between the anchor and the coaption element. Example clasps (e.g., barbed clasps, etc.) include a movable member or arm that is actuatable between open and closed positions relative to a fixed member or arm. The moveable arm is moved away from the fixed arm to form a gap or opening between the moveable and fixed arms for receiving a portion of the native leaflet tissue. Once the leaflet is captured within the gap, the moveable arm is actuated to pinch the leaflet tissue, thereby securing the leaflet within the clasp. Generally, positioning the leaflet further into the opening between the arms of the clasp before actuating the moveable arm to pinch the leaflet allows the moveable arm to engage more of the leaflet tissue. Not only is more of the tissue then engaged by the clasp, but any barbs or other securing members arranged at the distal ends of the moveable or fixed arms are positioned to engage thicker portions of the native leaflet tissue as the tissue is disposed further within the gap. Engaging more and thicker tissue with the clasps ensures a more secure grip on the native leaflet by the clasp.

[00217] Determining the depth of native leaflet engagement within the gap between the moveable and fixed arms is a challenge using current imaging technology. In particular, the leaflet tissue moves with each beat of the heart and may be translucent or be visually hard to distinguish from surrounding tissue. In contrast, the clasps (e.g., barbed clasps, etc.) formed from materials, such as metal, are easier to see with imaging devices. Therefore, a surgeon may look at the position and/or of the moveable arm of the clasp to determine whether the clasp has properly engaged the native leaflet. For example, the clasps can be configured so that the moveable arm bounces slightly with each beat of the heart to indicate that the leaflet is captured within the clasp.

[00218] Example implantable devices can include an indicator used to determine whether the native leaflet is sufficiently engaged by or within the clasp or barbed clasp during implantation of the implantable prosthetic device. The indicators are visible via imaging devices during implantation. The indicator shows the surgeon that the leaflet is inserted in the opening to a desired capture depth and/or that the leaflet has not reached the desired capture depth. The indicator may be actuatable between an undeployed or starting position and a plurality of actuated positions that are visually distinct so as to indicate to the surgeon whether or not the indicator has engaged the leaflet tissue, and/or the leaflet tissue has reached a desired position or engagement depth. Using an indicator allows the surgeon to look at the indicator and not to the bouncing of the moveable arm to determine that the leaflet is properly engaged. Thus, the pinching force of the clasps can be increased without reducing the ability of the surgeon to determine whether the leaflet is sufficiently engaged.

[00219] Referring now to Figures 1–6, an implantable prosthetic device 100 is shown in various stages of deployment. The device 100 and associated systems, methods, etc. are described in more detail in International Application Nos. PCT/US2018/028189 and PCT/US2019/055320, the disclosures of which are incorporated herein by reference in their entirety. The device 100 can include any other features for an implantable prosthetic device discussed in the present application, and the device 100 can be positioned to engage valve tissue (e.g., leaflets 20, 22) as part of any suitable valve repair system (e.g., any valve repair system disclosed in the present application).

[00220] The device 100 is deployed from a delivery sheath or other means for delivery and can include a coaptation portion or coaption portion 104 and/or an anchor portion 106. The device 100 can be deployed from a delivery sheath and/or can be deployed by a pusher tube or rod 81. In some embodiments, the coaptation portion or coaption portion 104 of the device

100 includes a coaption element 110 that is adapted to be implanted between the leaflets of a native valve (e.g., native mitral valve, native tricuspid valve, etc.) and is slidably attached to an actuation member or actuation element 112 (e.g., an actuation wire, shaft, tube, rod, line, suture, tether, etc.). The anchor portion 106 is actuatable between open and closed conditions and can take a wide variety of forms, such as, for example, paddles, gripping elements, or the like. Actuation of the actuation element or means for actuating 112 opens and closes the anchor portion 106 of the device 100 to grasp the native valve leaflets during implantation. The actuation element or other means for actuation 112 (as well as other actuation elements and means for actuation herein) can take a wide variety of different forms (e.g., as a wire, rod, shaft, tube, screw, suture, line, combination of these, etc.). As one example, the actuation element can be threaded such that rotation of the actuation element moves the anchor portion 106 relative to the coaption portion 104. Or, the actuation element can be unthreaded, such that pushing or pulling the actuation element 112 moves the anchor portion 106 relative to the coaption portion 104.

[00221] The anchor portion 106 and/or anchors of the device 100 include outer paddles 120 and inner paddles or gripping elements 122 that are, in some embodiments, connected between a cap 114 and the coaption element or means for coacting 110 by portions 124, 126, 128. The connection portions 124, 126, 128 can be jointed and/or flexible to move between all of the positions described below. The interconnection of the outer paddles 120, the inner paddles 122, the coaption element or means for coacting 110, and the cap 114 by the portions 124, 126, and 128 can constrain the device to the positions and movements illustrated herein.

[00222] In some implementations, the actuation member, actuation element, or other means for actuating 112 (e.g., actuation wire, actuation shaft, actuation tube, actuation rod, etc.) extends through the delivery sheath, the pusher tube/rod, and/or a coaption element 110 to the cap 114, e.g., at the distal connection of the anchor portion 106. Extending and retracting the actuation element 112 increases and decreases the spacing between a proximal end of the device and the cap 114 and/or between a coaption element 110 and the cap 114. An optional attaching means or collar (not shown) removably attaches the device and/or a coaption element 110 of the device to the pusher tube or rod 81 and/or delivery sheath 102 so that the actuation element 112 slides along the actuation element 112 during actuation to open and close the paddles 120, 122 of the anchor portion 106. After the device 100 is connected to valve tissue, if the device 100 needs to be removed from the valve tissue, a retrieval device can be used to connect to the collar 115 such that the actuation element can extend through

the collar 115 and any coaption element 110 to engage the anchor portion 106 to open the paddles 120, 122 and remove the device 100 from the valve tissue. Examples of retrieval devices that could be used are shown in PCT Application No. PCT/US2019/062391 filed November 20, 2019, which is incorporated herein by reference in its entirety.

[00223] Referring to Figure 3, the anchor portion and/or anchors include attachment portions for gripping members. The illustrated gripping members comprise clasps 130 that include a base or fixed arm 132, a moveable arm 134, optional barbs or other means for securing 136, and a joint, flex, or hinge portion 138. The fixed arms 132 are attached to the inner paddles 122. In some embodiments, the fixed arms 132 are attached to the inner paddles 122 with the joint, flex, hinge portion 138. disposed proximate a coaption element 110. The clasps or barbed clasps can have flat surfaces and do not fit in a recess of the inner paddle, but are disposed against the surface of the inner paddle 122. The joint, flex, or hinge portion 138 provides a spring force between the fixed and moveable arms 132, 134 of the clasp 130. The joint, flex, or hinge portion 138 can be any suitable flexible portion, joint, or hinge, such as a flexible hinge, a flexible joint, a spring hinge, a pivot hinge, etc. In some embodiments, the joint, flex, or hinge portion 138 is a flexible piece of material integrally formed with the fixed and moveable arms 132, 134. The fixed arms 132 are attached to the inner paddles 122 and remain stationary relative to the inner paddles 122 when the moveable arms 134 are opened to open the clasps 130 and expose the barbs, friction-enhancing elements, or other means for securing 136. In some embodiments, the clasps 130 are opened by applying tension to actuation lines 116 attached to the movable arms or ends of the moveable arms 134, thereby causing the moveable arms 134 to move, flex, and/or pivot on the joint, flex, or hinge portions 138.

[00224] During implantation, the paddles 120, 122 can be opened and closed, for example, to grasp or capture the native leaflets (e.g., native mitral valve leaflets, etc.) between the paddles 120, 122 and/or between the paddles 120, 122 and a coaption element or means for coapting 110. The clasps 130 can be used to grasp and/or further secure the native leaflets by engaging the leaflets with barbs, friction-enhancing elements, or means for securing 136 and pinching the leaflets between the moveable and fixed arms 134, 132. The barbs, friction-enhancing elements, or other means for securing 136 of the clasps or barbed clasps 130 increase friction with the leaflets or may partially or completely puncture the leaflets. The actuation lines 116 can be actuated independently so that each clasp 130 can be opened and closed independently. Independent operation allows one leaflet to be grasped or captured at a time,

or for the repositioning of a clasp 130 on a leaflet that was insufficiently grasped or captured, without altering a successful grasp on the other leaflet. The clasps 130 not only open and close independent from each other, but they can be opened and closed independent from the position of the inner paddle 122 thereby allowing leaflets to be grasped or captured in a variety of positions as the particular situation requires.

[00225] The clasps 130 can be opened independently/separately by pulling on an attached actuation line/suture or other actuation means 116 that extends through the delivery sheath or means for delivery 102 to the clasp 130. The actuation line 116 can take a wide variety of forms, such as, for example, a line, a suture, a wire, a rod, a catheter, or the like. The clasps 130 can be spring loaded or otherwise biased so that in the closed position the clasps 130 continue to provide a pinching force on the grasped or captured native leaflet. This pinching force remains constant regardless of the position of the inner paddles 122. Barbs, friction-enhancing elements, or other means for securing 136 of the clasps or barbed clasps 130 can pierce the native leaflets to further secure the leaflets.

[00226] Referring now to Figure 1, the device 100 is shown in an elongated or fully-open condition (also called fully-extended or full-bailout condition) for deployment from the delivery sheath. The device 100 is loaded in the delivery sheath in the fully open position, because the fully open position takes up the least space and allows the smallest catheter to be used (or the largest device 100 to be used for a given catheter size).

[00227] In some embodiments, the elongated condition the cap 114 is spaced apart from the coaption element or means for coapting 110 such that the paddles 120, 122 of the anchor portion 106 are fully open or extended. In some embodiments, an angle formed between the interior of the outer and inner paddles 120, 122 is approximately 180 degrees. The clasps 130 are kept in a closed condition during deployment through the delivery sheath or means for delivery 102 so that the barbs, friction-enhancing elements, or other means for securing 136 (Fig. 3) do not catch or damage the sheath or tissue in the patient's heart.

[00228] Referring now to Figure 1A, the device 100 is shown in an elongated detangling condition, similar to Figure 1, but with the clasps 130 in a fully open position, ranging from about 140 degrees to about 200 degrees, to about 170 degrees to about 190 degrees, or about 180 degrees between fixed and moveable portions of the clasps 130. Fully opening the paddles 120, 122 and the clasps 130 has been found to improve ease of detanglement or detachment from anatomy of the patient, such as the chordae tendineae, during implantation of the device 100.

[00229] Referring now to Figure 2, the device 100 is shown in a shortened or fully closed condition. The compact size of the device 100 in the shortened condition allows for easier maneuvering and placement within the heart. To move the device 100 from the elongated condition to the shortened condition, the actuation member or actuation element or other means for actuating 112 is retracted to pull the cap 114 towards a proximal end of the device and/or towards a coaption element 110. The connection portion(s) 126 (e.g., joint(s), hinge(s), flexible connection(s), etc.) between the outer paddle 120 and inner paddle 122 are limited or constrained in movement such that compression forces acting on the outer paddle 120 from the cap 114 being retracted towards the proximal end of the device and/or toward the coaption element 110 cause the paddles or gripping elements 120, 122 to move radially outward. During movement from the open to closed position, the outer paddles 120 maintain an acute angle with the actuation element 112. The outer paddles 120 can optionally be biased toward a closed position. The inner paddles 122 during the same motion move through a considerably larger angle as they are oriented away from the proximal end of the device and/or the coaption element 110 in the open condition and collapse toward the middle of the device in the closed condition (e.g., collapse along the sides of the coaption element 11). In some embodiments, the inner paddles 122 are thinner and/or narrower than the outer paddles 120, and the connection portions 126, 128 (e.g., joints, hinges, flexible connections, etc.) connected to the inner paddles 122 can be thinner and/or more flexible. For example, this increased flexibility can allow more movement than the connection portion 124 connecting the outer paddle 120 to the cap 114. In some embodiments, the outer paddles 120 are narrower than the inner paddles 122. The connection portions 126, 128 connected to the inner paddles 122 can be more flexible, for example, to allow more movement than the connection portion 124 connecting the outer paddle 120 to the cap 114. In some embodiments, the inner paddles 122 can be the same or substantially the same width as the outer paddles

[00230] Referring now to Figures 3–5, the device 100 is shown in a partially open, grasp-ready condition. To transition from the fully closed to the partially open condition, the actuation member or actuation element 112 (e.g., actuation wire, actuation shaft, etc.) is extended to push the cap 114 away from the proximal end of the device (e.g., away from a coaption element 110), thereby pulling on the outer paddles 120, which in turn pull on the inner paddles 122, causing the anchors or anchor portion 106 to partially unfold. The actuation lines 116 are also retracted to open the clasps 130 so that the leaflets can be captured or grasped. In some embodiments, the pair of inner and outer paddles 122, 120 are

moved in unison, rather than independently, by a single actuation element 112. Also, the positions of the clasps 130 may be dependent on the positions of the paddles 122, 120. For example, closing the paddles 122, 120 can also close the clasps. In some embodiments, the paddles 120, 122 can be independently controllable. For example, the device 100 can have two actuation elements and two independent caps, such that one independent wire and cap are used to control one paddle, and the other independent wire and cap are used to control the other paddle.

[00231] Referring now to Figure 4, one of the actuation lines 116 is extended to allow one of the clasps 130 to close. Referring now to Figure 5, the other actuation line 116 is extended to allow the other clasp 130 to close. Either or both of the actuation lines 116 can be repeatedly actuated to repeatedly open and close the clasps 130.

[00232] Referring now to Figure 6, the device 100 is shown in a fully closed and deployed condition. The delivery sheath or means for delivery 102 and actuation element or means for actuating 112 is/are retracted and the paddles 120, 122 and clasps 130 remain in a fully closed position. Once deployed, the device 100 can be maintained in the fully closed position with a mechanical latch or can be biased to remain closed through the use of spring materials, such as steel, other metals, plastics, composites, etc. or shape-memory alloys such as Nitinol. For example, the connection portions 124, 126, 128, the joint portion(s) 138, and/or the inner and outer paddles 122, 120 and/or an additional biasing component (see reference number 224 in Figure 13) can be formed of metals such as steel or shape-memory alloy, such as Nitinol—produced in a wire, sheet, tubing, or laser sintered powder—and are biased to hold the outer paddles 120 closed around the a center of the device or around a coaption element 110 and the clasps 130 pinched around native leaflets. Similarly, the fixed and moveable arms 132, 134 of the clasps 130 are biased to pinch the leaflets. In some embodiments, the attachment or connection portions 124, 126, 128, joint portion(s) 138, and/or the inner and outer paddles 122, 120 and/or an additional biasing component (see reference number 224 in Figure 13) can be formed of any other suitably elastic material, such as a metal or polymer material, to maintain the device in the closed condition after implantation.

[00233] Referring now to Figures 7–12, the implantable device 100 of Figures 1–6 is shown being delivered and implanted within a native valve or native mitral valve 40 of a heart 10. Referring now to Figure 7, the delivery sheath is inserted into the left atrium 20 through the septum and the device 100 is deployed from the delivery sheath in the fully open condition. The actuation element 112 is then retracted to move the device 100 into the fully closed

condition shown in Figure 8. As can be seen in Figure 9, the device 100 is moved into position within the mitral valve 40 into the ventricle 30 and partially opened so that the leaflets 42, 44 can be captured. Referring now to Figure 10, an actuation line 116 is extended to close one of the clasps 130, capturing a leaflet 42. Figure 11 shows the other actuation line 116 being then extended to close the other clasp 130, capturing the remaining leaflet 44. Lastly, as can be seen in Figure 12, the delivery sheath 102 and actuation element 112 are then retracted and the device 100 is fully closed and deployed in the native mitral valve 400.

[00234] Referring now to Figure 13, an implantable prosthetic device 200 is shown. The implantable device 200 is one of the many different configurations that the device 100 that is schematically illustrated in Figures 1–12 can take. The device 200 is deployed from a delivery sheath (not shown). The device 200 can include a coaption portion 204 and/or an anchor portion 206. The device 200 is loaded in the delivery sheath in the fully open position, because the fully open position takes up the least space and allows the smallest catheter to be used (or the largest device 200 to be used for a given catheter size).

[00235] In some embodiments, the coaption portion 204 of the device includes a coaption element 210 for implantation between native leaflets of a native valve that is slidably attached to an actuation element 212 (e.g., actuation wire, rod, shaft, tube, screw, suture, line, combination of these, etc.). The anchors of the device can include outer paddle portions and inner paddle portions. Actuation of the actuation element 212 opens and closes the anchor portion 206 of the device 200 to grasp or capture the native valve leaflets during implantation.

[00236] The anchor portion 206 of the device 200 includes outer paddles 220 and inner paddles 222 that are jointedly, flexibly, or hingeably connected to the cap 214 and/or the coaption element 210. The actuation element 212 extends through one, some, or all of the delivery sheath (not shown), a collar 211, and a coaption element 210, and extends to the cap 214 at the distal end of the anchor portion 206. In some embodiments, extending and retracting the actuation element 212 increases and decreases the spacing between the coaption element 210 and the cap 214, respectively.

[00237] The collar 211 optionally includes a collar seal 213 that forms a seal around the actuation element 212 during implantation of the device 200, and that seals shut when the actuation element 212 is removed to close or substantially close the device 200 to blood flow through the interior of the coaption element 210 after implantation. In some embodiments, the collar 2011 removably engages and attaches the coaption element 210 to the delivery

sheath so that the coaption element 210 slides along the actuation element 212 during actuation to open and close the paddles 220, 222 of the anchor portion 206. In some embodiments, the collar 2011 is held closed around the coaption element 210 by the actuation element 212, such that removal of the actuation element 212 allows fingers (not shown) of the collar to open, releasing the coaption element 210. In some embodiments, the cap 2014 optionally includes a seal 216 and/or an insert 218 that fit inside an opening 215 of the coaption element 210, the coaption element 210 having a hollow interior. The seal 216 and/or insert 218 maintain the coaption element 210 closed or substantially closed to blood flow when the actuation element 212 is withdrawn and the device 200 is implanted.

[00238] The coaption element 210 and/or paddles 220, 222 can comprise and/or be formed from a covering that can be a mesh, woven, braided, or formed in any other suitable way. The covering can be cloth, shape-memory alloy wire—such as Nitinol—to provide shape setting capability, or any other flexible material suitable for implantation in the human body. In some embodiments, paddle frames 224 provide pinching force between the inner paddles 222 and the coaption element 210 and assist in wrapping the leaflets around the sides of the coaption element 210 for a better seal between the coaption element 210 and the leaflets. In some embodiments, the covering extends around the paddle frames 224.

[00239] The clasps 230 include a base or fixed arm 232, a moveable arm 234, friction-enhancing elements or barbs 236, and a flex or hinge portion 238. The fixed arms 232 are attached to the inner paddles 222, with the flex or hinge portion 238 disposed proximate a center of the device and/or a coaption element 210. The fixed arms 232 are attached to the inner paddles 222 through holes or slots 233 with sutures (not shown). The fixed arms 232 can be attached to the inner paddles 222 or another portion of the device with any suitable means, such as screws or other fasteners, crimped sleeves, mechanical latches or snaps, welding, adhesive, or the like. The fixed arms 232 remain stationary or substantially stationary relative to the inner paddles 222 when the moveable arms 234 are opened to open the clasps 230 and expose the friction-enhancing elements or barbs 236. The clasps 230 are opened by applying tension to actuation lines (not shown) attached to holes 235 disposed at ends of the moveable arms 234, thereby causing the moveable arms 234 to move, flex, and/or pivot on the joint, flex, or hinge portions 238.

[00240] During implantation, the anchors and/or the paddles 220, 222 are opened and closed to capture the native mitral valve leaflets between the anchors and/or the paddles 220, 222 and/or between the anchors or paddles and a coaption element 210. In some embodiments,

the clasps 230 (e.g., barbed clasps, etc.) further secure the native leaflets by engaging the leaflets with friction-enhancing elements or barbs 236 and pinching the leaflets between the moveable and fixed arms 234, 232. In some embodiments, friction-enhancing elements or barbs 236 of the clasps 230 increase friction with the leaflets or may partially or completely puncture the leaflets. The actuation lines can be actuated independently so that each clasp 230 can be opened and closed independently. Independent operation allows one leaflet to be grasped/captured at a time, or for the repositioning of a clasp 230 on a leaflet that was insufficiently captured, without altering a successful grasp on the other leaflet. The clasps 230 not only open and close independent from each other but can be fully opened and closed independent from the position of the inner paddle 222, thereby allowing leaflets to be captured in a variety of positions as the particular situation requires.

[00241] Referring now to Figures 14–23, 23A, and 22B, an implantable device 300 is shown being delivered and implanted within the native mitral valve 40 of the heart 10. The methods and steps shown and/or discussed can be performed on a living animal or on a simulation, such as on a cadaver, cadaver heart, simulator (e.g. with the body parts, heart, tissue, etc. being simulated), etc.

[00242] The device 300 can be the same as or similar to implantable device 200 of Figure 13, though device 300 has a covering over the coaption element 310, clasps 330, inner paddles 322 and/or the outer paddles 320. The device 300 is deployed from a delivery sheath 302. The device can include a coaption portion 304 and/or an anchor portion 306 including a plurality of anchors (e.g., two in the illustrated embodiment, but can be more or less). In some embodiments, the coaption portion 304 of the device can include a coaption element 310 for implantation between the leaflets of a native valve. The coaption element 310 can be slidably attached to an actuation element 312 (actuation wire, actuation shaft, etc.). Actuation of the actuation element 312 opens and closes the anchor portion 306 of the device 300 to capture the native valve leaflets during implantation.

[00243] The anchor portion 306 of the device 300 includes outer paddles 320 and inner paddles 322 that are flexibly connected to the cap 314 and/or the coaption element 310. The actuation element 312 extends through one or more of a collar 303 (see Figure 20), delivery sheath 302, and coaption element 310 to the cap 314 at the distal end of the anchor portion 306. Extending and retracting the actuation element 312 increases and decreases the spacing between the proximal end of the device and the cap 314 and/or between a coaption element 310 and the cap 314. In some embodiments, fingers of the collar 303 removably attach the

coaption element 310 to the delivery sheath 302 so that the coaption element 310 slides along the actuation element 312 during actuation to open and close the paddles 320, 322 of the anchor portion 306. In some embodiments, the collar 303 is held closed around the coaption element 310 by the actuation element 312, such that removal of the actuation element 312 allows the fingers of the collar 303 to open, releasing the coaption element 310.

[00244] The coaption element 310 and/or paddles 320, 322 are formed from a flexible material that may be a mesh, woven, braided, or formed in any other suitable way. The flexible material can be cloth, shape-memory alloy wire—such as Nitinol—to provide shape setting capability, or any other flexible material suitable for implantation in the human body.

[00245] The clasps 330 (illustrated as barbed clasps) include a base or fixed arm 332, a moveable arm 334, and a connection portion or joint, flex, or hinge portion 338. The clasps can be configured as barbed clasps and include barbs 336 (see Figure 20), or the clasps can include another type of friction-enhancing element, securing element, or means for securing. The fixed arms 332 are attached to the inner paddles 322, with the connection portion or joint, flex, or hinge portion 338. In some embodiments, the connection portion or joint, flex, or hinge portion 338 is disposed proximate a coaption element 310. In some embodiments, sutures (not shown) attach the fixed arms 332 to the inner paddles 322. Though the fixed arms 332 can be attached to the inner paddles 322 with any suitable means, such as screws or other fasteners, crimped sleeves, mechanical latches or snaps, welding, adhesive, or the like. The fixed arms 332 remain stationary or substantially stationary when the moveable arms 334 are opened to open the barbed clasps 330 and expose the barbs 336. The barbed clasps 330 are opened by applying tension to actuation lines 316 attached to the ends of the moveable arms 334, thereby causing the moveable arms 334 to move, flex, and/or pivot on the connection portions or joint, flex, or hinge portions 338.

[00246] During implantation, the paddles 320, 322 are opened and closed to capture the native valve leaflets between the paddles 320, 322 and/or between the paddles 320, 322 and a coaption element 310. In some embodiments, the outer paddles 320 have a wide curved shape that fits around the curved shape of the coaption element 310 to more securely grip the leaflets. The curved shape and rounded edges of the outer paddle 320 also prohibits tearing of the leaflet tissue. The clasps 330 can be barbed clasps that further secure the native leaflets by engaging the leaflets with barbs 336 and pinching the leaflets between the moveable and fixed arms 334, 332. The barbs 336 (and/or other friction-enhancing elements) of the clasps 330 increase friction with the leaflets or may partially or completely puncture the leaflets.

The actuation lines can be actuated independently so that each clasp 330 can be opened and closed independently. Independent operation allows one leaflet to be captured at a time, or for the repositioning of a clasp 330 on a leaflet that was insufficiently captured, without altering a successful grasp on the other leaflet. The clasps 330 not only open and close independent from each other but can be fully opened and closed independent from the position of the inner paddle 322, thereby allowing leaflets to be grasped and/or captured in a variety of positions as the particular situation requires.

[00247] The device 300 is loaded in the delivery sheath in the fully open position, because the fully open position takes up the least space and allows the smallest catheter to be used (or the largest device 300 to be used for a given catheter size). Referring now to Figure 14, the delivery sheath is inserted into the left atrium 20 through the septum and the device 300 is deployed from the delivery sheath 302 in the fully open condition. The actuation element 312 is then retracted to move the device 300 into the fully closed condition shown in Figures 15–16 and then maneuvered towards the native valve, e.g., mitral valve 40 as shown in Figure 17. Referring now to Figure 18, when the device 300 is aligned with the native valve 40, the actuation element 312 is extended to open the paddles 320, 322 into the partially opened position and the actuation lines 316 are retracted to open the clasps or barbed clasps 330 to prepare for leaflet capture. Next, as shown in Figures 19–20, the partially open device 300 is inserted through the native valve or mitral valve 40 until leaflets are properly positioned in between the inner paddles 322 and the coaption element 310 and inside the open clasps 330. Figure 21 shows the device 300 with both clasps 330 closed, though the barbs 336 of one clasp 330 missed one of the leaflets 44 or where improperly positioned on the leaflets. As can be seen in Figures 22–23, the out of position clasp 330 is opened and closed again to properly capture the missed leaflet 44. When both leaflets 42, 44 are captured properly, the actuation element 312 is retracted to move the device 300 into the fully closed position shown in Figure 23A. Referring to Figure 23B, with the device 300 fully implanted in the native valve 40, the actuation element 312 is withdrawn to release the collar 303 from an upper end or plate 311 of the device 300 or of the coaption element 310 to leave the device 300 implanted on the native valve. Once deployed, the device 300 can be maintained in the fully closed position with a mechanical means such as a latch or can be biased to remain closed through the use of spring material, such as steel, and/or shape-memory alloys such as Nitinol. For example, the paddles 320, 322 can be formed of steel or Nitinol shape-memory alloy—produced in a wire, sheet, tubing, or laser sintered powder—and are biased to hold the outer paddles 320 closed,

e.g., around the coaption element 310, and the barbed clasps 330 pinching or securing the native leaflets.

[00248] Referring now to Figures 24-25, an example clasp 3500 configured as a barbed clasp for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. While depicted and described as a barbed clasp, the barbed portion 3540 could be substituted with another type of friction-enhancing portion. The clasp 3500 is configured to capture the native tissue when the implantable prosthetic device—e.g., any device described in the present application—is attached to the native tissue. Like the clasps described above, the barbed clasp 3500 includes a fixed arm 3510, a joint, flex, or hinge portion 3520, and a moveable arm 3530 having a barbed portion 3540. The clasp 3500 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the clasps described herein.

[00249] The clasp 3500 also includes an indicator arm 3550 adjacent to the moveable arm 3530 and extending from an indicator flex or hinge portion 3560. In an example embodiment, the indicator arm 3550 and/or the indicator flex or hinge portion 3560 are more resilient and/or flexible than the moveable arm 3530 and/or the moveable arm portion 3520. This increased resilience and/or flexibility allows the indicator arm to bounce, pulse or jump, while the moveable arm 3530 provides a firm grip on the leaflet tissue and does not bounce, pulse or jump. The bounce, pulse or jump of the indicator arm 3550 can be viewed using standard imaging equipment to determine that the clasp is correctly engaged with the leaflet tissue. As such, the indicator function of the indicator arm 3550 can be decoupled from the valve leaflet gripping and securing function of the moveable arm 3530. This decoupling can be applied to any of the embodiments described herein.

[00250] Referring to Figures 24 and 25, in an example embodiment the indicator flex or hinge portion 3560 allows the indicator arm 3550 to be actuated separately from the moveable arm 3530. The indicator flex or hinge portion 3560 can be formed from a portion of the indicator arm 3550 or can be formed from a series of cutouts.

[00251] The indicator arm 3550 can be separately actuated from the moveable arm 3530 to facilitate detection of the depth of engagement of the native leaflet between the moveable arm 3530 and the fixed arm 3510 of the clasp 3500. In the illustrated embodiment, the indicator arm 3550 is narrower than the moveable arm 3530 and has a length that is less than a distance from the joint, flex, or hinge portion 3520 to the barbed portion 3540. The indicator arm can have an optional barb(s) 3555 on it.

[00252] The length of the indicator arm 3550 is used to determine a desired minimum engagement depth as measured from the end of the moveable arm 3530 of the clasp 3500. Configuring the length of the indicator arm 3550 to be less than a distance from the joint, flex, or hinge portion 3520 to the barbed portion 3540 ensures that the barbed portion 3540 will engage a leaflet that is positioned at the minimum engagement depth as indicated by the indicator arm 3550. That is, if a native leaflet positioned within the clasp 3500 is engaged by the indicator arm 3550 when the indicator arm 3550 is actuated, then the leaflet will be engaged by the barbed portion 3540 of the moveable arm 3530. The opposite is also true. That is, if a native leaflet positioned within the clasp 3500 is not engaged by the indicator arm 3550 when the indicator arm 3550 is actuated, then the leaflet will not be engaged by the barbed portion 3540 of the moveable arm 3530.

[00253] Referring now to Figures 24A and 25A, an example embodiment of a clasp such as that illustrated in Figures 24 and 25 is shown, with the addition of a radiopaque marker 2410 on the indicator arm 3550. The radiopaque indicator can be printed directly on the bump, a coil wrapped around the bump, or printed on a fabric covering the bump, or otherwise fixed to the bump. The radiopaque indicator can be a platinum coil wrapped around the bump, or it can be radiopaque ink printed on it. In Figures 24A and 25A, no barb is shown on the indicator arm, but there can optionally be a barb on the indicator arm as shown in Figures 24 and 25.

[00254] Referring now to Figures 26-29, the example clasp or barbed clasp 3500 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 26, the barbed clasp 3500 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening of the barbed clasp 3500 formed between the fixed and moveable arms 3510, 3530. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the indicator arm 3550 can be actuated via an actuation line (not shown). Referring now to Figure 27, the clasp is shown in a closed configuration, closed on the leaflet 42, 44. The indicator arm 3550 has not yet been actuated.

[00255] Referring now to Figure 28, the indicator arm 3550 is shown in an actuated condition. The barb 3540 on the moveable arm 3530 has pierced the native leaflet. Because the leaflet 42, 44 is inserted into the opening of the clasp 3540 about half way between the barbed portion 3540 and the jointed, flexible, or hinged portion 3520 and is not inserted far enough into the clasp to overlap with the length of the indicator arm 3550, the indicator arm 3550

does not engage the leaflet 42, 44. Instead, the indicator arm swings toward the fixed arm 3510. The indicator arm's position is visible via imaging devices used to monitor implantation and deployment of the prosthetic device.

[00256] Referring now to Figure 29, the clasp is closed on the leaflet 42, 44, and the leaflet is positioned deep enough into the clasp 3500 such that it overlaps with the indicator arm 3550. The barb 3540 on the moveable arm 3530 has pierced the native leaflet. The indicator arm rests on the leaflet tissue, and the leaflet prevents the indicator arm from moving all the way toward the fixed arm 3510 of the clasp. The indicator arm as illustrated in Figure 29 has a barb 3540 to further secure the leaflet in place. In embodiments without a barb on the indicator arm, the indicator arm can bounce with the pulse of the heartbeat, which pulses the leaflet. This pulsing is visible by imaging techniques described above and can be used to indicate to the operator that the leaflet is positioned sufficiently deep into the clasp.

[00257] Referring now to Figures 30-37, a variety of example arrangements of moveable and indicator arms for clasps are shown. Referring now to Figure 30, an example clasp 3600, illustrated as a barbed clasp, for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the barbed clasp 3500 described above, the barbed clasp 3600 includes a fixed arm 3610, a joint, flex, or hinge portion 3620, a moveable arm 3630 having a barbed portion 3640 (though other friction-enhancing portions can be used), and an indicator arm 3650 connected to the joint, flex, or hinge portion 3620 via an indicator flex or hinge portion 3660. The clasp 3600 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00258] The indicator arm 3650 has a width that is about the same as a width of the moveable arm 3630, which is wider than the indicator arm 3550 of the clasp 3500, described above. Increasing the width of the indicator arm 3650 increases the area of the arm that can engage the native leaflet. A wider indicator arm 3650 can also help to pinch the native leaflet against the fixed arm when the clasp 3600 is closed. The indicator flex or hinge portion 3660 is similar to the patterned hinge portion 2120 described above which allows the indicator arm 3650 to bend further than the moveable arm 3630 in the closing direction and be shape set in a preloading or shape set position (not shown) to provide increased pinching force when in a closed or engaged position (not shown) in contact with the native leaflet tissue.

[00259] Referring now to Figure 31, an example clasp 3700 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500

described above, the clasp 3700 includes a fixed arm 3710, a joint, flex, or hinge portion 3720, a moveable arm 3730 having a barbed portion 3740 (though other friction-enhancing portions can be used), and an indicator arm 3750 connected to the joint, flex, or hinge portion 3720 via an indicator flex or hinge portion 3760. The clasp 3700 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00260] The moveable arm 3730 is formed in a hoop or loop shape having two side arms 3732 surrounding a central opening 3734 that extends from the joint, flex, or hinge portion 3720 to the barbed portion 3740 of the moveable arm 3730. The indicator arm 3750 is disposed in the central opening 3734 between the two side arms 3732. Because the moveable arm 3730 spans the full width of the clasp 3700, the barbed portion 3740 of the moveable arm 3730 is as wide as the clasp 3700 so that a larger area of the barbed portion 3740 engages with the native leaflet tissue.

[00261] Referring now to Figure 32, an example clasp 3800 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 3800 includes a fixed arm 3810, a joint, flex, or hinge portion 3820, a moveable arm 3830 having a barbed portion 3840 (though other friction-enhancing portions can be used), and an indicator arm 3850 connected to the joint, flex, or hinge portion 3820 via an indicator flex or hinge portion 3860. The clasp 3800 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00262] The moveable arm 3830 is formed from two side arms 3832 adjacent to a central opening 3834 that extends from the joint, flex, or hinge portion 3820 to the end of the moveable arm 3830. That is, the central opening 3834 separates the moveable arm 3830 into two independently actuatable side arms 3832 that each include a barbed portion 3840. The indicator arm 3850 is disposed in the central opening 3834 between the two side arms 3832. The barbed portions 3840 of the side arms 3832 span the full width of the clasp 3800 to provide a wide gripping area for the moveable arm 3830 to engage the native leaflet tissue. The side arms 3832 can be independently actuated to allow for lateral variations in thickness of the native leaflet tissue.

[00263] Referring now to Figure 33, an example clasp 3900 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 3900 includes a fixed arm 3910, a joint, flex, or hinge portion

3920, a moveable arm 3930 having a barbed portion 3940 (though other friction-enhancing portions can be used), and an indicator arm 3950 having a barbed portion 3970. The indicator arm 3950 is connected to the joint, flex, or hinge portion 3920 via an indicator flex or hinge portion 3960. The clasp 3900 is similar to the clasp 3500 described above, except for the addition of a barbed portion 3970 arranged at the end of the indicator arm 3950. The barbed portion 3970 allows the indicator arm 3950 to aid the moveable arm 3930 in pinching the native leaflet against the fixed arm (not shown). The clasp 3900 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00264] Referring now to Figures 34-37, example clasps are shown with indicator arms having a length based on percentage of a minimum engagement depth of the clasp. The minimum engagement depth of the clasp is the minimum length of native tissue that should be inserted into the clasp beyond the barbed portion, to ensure a reliable grip on the tissue by the clasp. That is, the minimum engagement depth is the distance between the barbed portion and the joint, flex, or hinge portion of the clasp. The minimum engagement depth for mitral valve tissue can vary depending on a variety of different factors, such as age of the patient, thickness of the tissue, health of the tissue, etc. As such, the minimum engagement depth can vary depending on the patient.

[00265] Referring now to Figure 34, an example clasp 4000 (illustrated as a barbed clasp) for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 4000 includes a fixed arm 4010, a joint, flex, or hinge portion 4020, a moveable arm 4030 having a barbed portion 4040 (though other friction-enhancing portions can be used), and an indicator arm 4050 connected to the joint, flex, or hinge portion 4020 via an indicator flex or hinge portion 4060. The indicator arm 4050 has a length that is about 25 percent of the maximum engagement depth measured between the joint, flex, or hinge portion 4020 and the barbed portion 4040. Thus, the indicator arm 4050 will not indicate that the native leaflet has reached a desired engagement depth until the leaflet is inserted to at least about 75 percent of the maximum engagement depth. The clasps 4000 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00266] Referring now to Figure 35, an example clasp 4100 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500

described above, the clasp 4100 includes a fixed arm 4110, a joint, flex, or hinge portion 4120, a moveable arm 4130 having a barbed portion 4140 (though other friction-enhancing portions can be used), and an indicator arm 4150 connected to the joint, flex, or hinge portion 4120 via an indicator flex or hinge portion 4160. The indicator arm 4150 has a length that is about 50 percent of the maximum engagement depth measured between the joint, flex, or hinge portion 4120 and the barbed portion 4140. Thus, the indicator arm 4150 will not indicate that the native leaflet has reached a desired engagement depth until the leaflet is inserted to at least about 50 percent of the maximum engagement depth. The clasps 4100 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00267] Referring now to Figure 36, an example clasp 4200 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 4200 includes a fixed arm 4210, a joint, flex, or hinge portion 4220, a moveable arm 4230 having a barbed portion 4240 (though other friction-enhancing portions can be used), and an indicator arm 4250 connected to the joint, flex, or hinge portion 4220 via an indicator flex or hinge portion 4260. The indicator arm 4250 has a length that is about 75 percent of the maximum engagement depth measured between the joint, flex, or hinge portion 4220 and the barbed portion 4240. Thus, the indicator arm 4250 will not indicate that the native leaflet has reached a desired engagement depth until the leaflet is inserted to at least about 25 percent of the maximum engagement depth. The clasps 4200 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00268] Referring now to Figure 37, an example clasp 4300 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 4300 includes a fixed arm 4310, a joint, flex, or hinge portion 4320, a moveable arm 4330 having a barbed portion 4340, and an indicator arm 4350 connected to the joint, flex, or hinge portion 4320 via an indicator flex or hinge portion 4360. The indicator arm 4350 has a length that is about 90 percent of the maximum engagement depth measured between the joint, flex, or hinge portion 4320 and the barbed portion 4340 (though other friction-enhancing portions can be used). Thus, the indicator arm 4350 will not indicate that the native leaflet has reached a desired engagement depth until the leaflet is inserted to at least about 10 percent of the maximum engagement depth. The clasps 4300 can

be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00269] Referring now to Figures 38-47, example clasps 3500 are shown attached to paddles of an implantable prosthetic device, such as devices 100, 200, 300, and being deployed within a native valve 40 and to secure the device to the native leaflets 42, 44. While the clasps 3500 are shown in Figures 93–102, the clasps 3600, 3700, 3800, 3900, 4000, 4100, 4200, and 4300 with indicator arms described above would be attached to the native leaflets in a similar manner as the clasps 3500. The clasps 3500 are attached to paddles 122 of the device 100 that can be moved between opened and closed positions to capture and secure the native leaflets 42, 44 within the device 100, as described above.

[00270] Referring now to Figure 39, the device 100 is shown deployed through the native mitral valve 40 and the paddles 122 are opened. The clasps 3500 are then opened by applying tension to actuating lines 3502, 3504 attached to the ends of the moveable arms 3530 and the indicator arms 3550, respectively. Opening the clasps 3500 and the paddles 122 as shown in Figure 39 allows the device 100 to be maneuvered such that the leaflets 42, 44 are at least partially disposed in the opening 3506 formed between the fixed and moveable arms 3510, 3530 of the clasps to facilitate the capture of the leaflets 42, 44 by the clasps 3500.

[00271] Referring now to Figure 39, the paddles 122 and clasps 3500 are partially closed to position the leaflets for detection by the indicating arms 3550 and eventual capture by the clasps 3500. The partially closed position of the paddles 122 and clasps 3500 allows the barbed portions 3540 of the moveable arms 3530 to pinch the leaflets 42, 44 against the fixed arms 3510 without stretching or moving the leaflets 42, 44 so far that the leaflets 42, 44 are pushed aside by the moveable arms 3530 or slip off of the barbed portions 3540 during an attempted leaflet capture.

[00272] Referring now to Figure 40, both indicator arms 3550 are actuated by releasing tension on the actuation lines 3504. Both indicator arms 3550 miss or slip off of the leaflets 42, 44 and move to a fully actuated position that is beyond the fixed arms 3510 of the clasps 3500. The indicator arms 3550 crossing the fixed arms 3510 forms an X-shape that is visible via imaging devices used to monitor implantation and deployment of the device.

[00273] Referring now to Figure 41, the indicator arms 3550 are retracted by applying tension to the actuation lines 3504 and the device 100 is repositioned so that the leaflets 42, 44 are more deeply inserted into the openings 3506 of the clasps 3500. One of the indicator arms 3550 is then allowed to close by releasing tension on one of the actuating lines 3504, as can

be seen in Figure 42. The indicator arm 3550 engages the leaflet 42 and pinches the leaflet 42 against the fixed arm 3510 and paddle 122. Figure 43 shows the same with the other indicator arm 3550 being actuated to engage the other leaflet 44 and pinch the leaflet 44 against the other fixed arm 3510 and paddle 122. Engagement with the leaflets 42, 44 prevents the indicator arms 3550 from moving past the fixed arms 3510 of the clasps 3500 to form the X-shape shown in Figure 40. Thus, the indicator arms 3550 indicate to an observer observing the installation via an imaging device that the leaflets 42, 44 are inserted into the openings 3506 beyond the minimum desired engagement depth that is determined by the length of the indicator arms 3550.

[00274] Referring now to Figures 44-47, once the indicator arms 3550 indicate that the leaflets 42, 44 are sufficiently inserted into the openings 3506, the moveable arms 3530 are actuated by releasing tension on the actuating lines 3502 so that the leaflets 42, 44 are pinched between the barbed portions 3540 and fixed arms 3510 of each clasp 3500. The paddles 122 are then moved to a fully closed position, shown in Figure 46, to secure the leaflets firmly within the device 100. The indicators 3550 can be monitored in any of the positions illustrated by Figures 42-46. For example, the indicators 3550 will pulse or jump as the heart beats. This pulsing or jumping can be visualized to confirm that the mitral valve repair device is correctly positioned. Since the indicators 3550 are flexible enough to flex or jump as the heart beats, the movable arms 3530 can be made stiff and/or close with a high enough force that closed moveable arms 3530 do not pulse or jump as the heart beats.

[00275] Referring now to Figure 47, one of the leaflets 44 is shown partially withdrawn from the device 100, which can occur because of movement of the leaflets 42, 44 during the beating of the heart. As can be seen in Figure 47, the leaflet 44 remains partially secured by the barbed portion 3540. However, the leaflet 44 is no longer secured at or beyond the minimum engagement depth as determined by the length of the indicator arm 3550. Withdrawal of the leaflet 44 allows the indicator arm 3550 to move beyond the fixed arm 3510, thereby forming an X-shape that is visible to an observer using an imaging device. In addition, or instead, the indicator arm 3550 that does not contact the valve leaflet does not pulse or jump as the heart beats. Thus, insufficient retention or slippage of the leaflets 42, 44 from the device 100 can be detected before the device 100 is detached from a delivery device (not shown). Once the slipped leaflet is detected, the clasps 3500 and paddles 122 can be opened and repositioned to better secure the slipped leaflet. In other example embodiments

(see Figures 221-225), a single actuation line can be used to raise and lower the moveable arm and indicator arm of a clasp.

[00276] In some example embodiments, a first moveable arm on a clasp can have a barb and be strong enough to hold the leaflet in place when the first moveable arm is lowered on to the leaflet. The first moveable arm can be raised again if the leaflet is not sufficiently positioned far enough within the leaflet. The barb on the first moveable arm is temporary so that the first moveable arm can be raised and lowered repeatedly until the leaflet is properly positioned. Once the location of the leaflet is sufficiently positioned within the clasp, one or more secondary moveable arms, having a barb or barb region, can be lowered to hold or capture the leaflets in place within the clasp.

[00277] Referring now to Figures 48-66, an example clasp 4400 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. The clasp 4400 has a fixed arm 4410, a patterned flex portion or patterned hinge portion 4420, a moveable arm 4430 formed in the shape of a hoop or loop, and a barbed portion 4440 of the moveable arm 4430. The clasp 4400 also includes an indicator arm 4450 extending from an indicator flex or hinge portion 4460 that joins the indicator arm to the patterned flex or hinge portion 4420. The clasp 4400 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein. For example, the clasp 4400 can be laser cut from a flat sheet or a tube of shape-memory alloy, such as Nitinol, and then shape-set into a desired shape.

[00278] The illustrated fixed arm 4410 has two tongue portions 4411 that each include holes 4412 for attaching the fixed arm 4410 to an implantable device. A central opening 4454 arranged between the tongue portions 4411 is wider than the indicator arm 4450 so that the indicator arm 4450 can pass through the fixed arm 4410 between the tongue portions 4411 to form an X-shape when viewed from the side (Figure 51) when the indicator arm 4450 does not engage the leaflet tissue.

[00279] The patterned flex portion or patterned hinge portion 4420 is formed from a plurality of spring segments 4422 and cutouts 4424. The two tongue portions 4411 of the fixed arm 4410 extend from one end of the patterned flex portion or patterned hinge portion 4420 and the moveable arm 4430 extends from the other end of the flex or hinge portion 4420.

[00280] The moveable arm 4430 of the clasp 4400 has a hoop-like shape. The hoop-shaped moveable arm 4430 includes side beams 4432 that are thinner and more flexible, particularly in the lateral direction. The side beams 4432 include a first flex portion or hinge portion 4434

arranged toward the proximate end of the moveable arm 4430 and a second flex portion or hinge portion 4436 arranged at the distal end of the moveable arm 4430. The first flex or hinge portion 4434 is formed by one or more bends in the side beams 4432. The second flex or hinge portion 4436 includes a thinner—and therefore more flexible—portion to reduce the force required to collapse the clasp 4400. The hoop-shape of the moveable arm 4430 and flexible side arms 4432 allow the moveable arm 4430 to be collapsed by merely retracting the clasp 4400 into a delivery sheath (not shown). In certain embodiments, the expansion and contraction of the clasp 4400 is controlled by actuation lines (not shown).

[00281] The hoop-like shape of the moveable arm 4430 provides for a wider barbed portion 4440 that can include more barbs 4442 with the same or greater lateral spacing than other clasps. The wider spacing of the barbs 4442 improves capture of the native leaflets. The barbs 4442 are also longitudinally staggered as a result of their position on the hoop-like shape of the moveable arm 4430. That is, two center barbs 4444 are arranged further away from the joint, flex, or hinge portion 4420 and two outer barbs 4446 are arranged closer to the joint, flex, or hinge portion 4420. The barbed portion 4440 of the moveable arm 4430 also includes holes 4448 for receiving an actuation suture (not shown). In certain embodiments, the hoop shape of the moveable arm 4430 is similar to the shape of wide outer paddles of an implantable device so that pinching forces of the paddles are spread out evenly on the barbs, further improving the retention of the native leaflets. The ends of the barbs 4442 can be further sharpened using any suitable sharpening means.

[00282] The indicator arm 4450 includes a beam 4451 that extends from the joint, flex, or hinge portion 4420 in the interior of the hoop-shaped moveable arm 4430 between the two side arms 4432 to a barbed portion 4456. The indicator arm 4450 includes a hole 4452 at the end for receiving an actuation line (not shown) for actuating the indicator arm 4450. The barbed portion 4456 is arranged at the end of the beam 4451 of the indicator arm 4450 and includes at least one barb 4456. The barbed portion 4456 helps the indicator arm 4450 secure the leaflet until the moveable arm 4430 is closed. The barb 4456 can be laser cut from the indicator arm 4450 and bent outwards so that it protrudes away from the indicator arm 4450 at about the same angle as the barbs 4442 protrude from the moveable arm 4430. In some embodiments, the indicator arm 4450 includes barbs that, like the barbs 2244 of the clasp 2200, are cut from a flat sheet of material and then rotated 90 degrees to protrude outward at an angle.

[00283] The barbed portion 4456 of the indicator arm 4450 is arranged at a distance from the joint, flex, or hinge portion 4420 such that the barb 4456 of the indicator arm 4450 is longitudinally arranged between the center barbs 4444 and the outer barbs 4446 of the barbed portion 4440. This arrangement ensures that the barbed portion 4440 will engage a leaflet that is engaged by the indicator arm 4450. That is, if a native leaflet positioned within the clasp 4400 is engaged by the barbed portion 4456 of the indicator arm 4450 when the indicator arm 4450 is actuated, then the leaflet will also be engaged by the barbed portion 4440 of the moveable arm 4430. The opposite is also true. That is, if a native leaflet positioned within the clasp 4400 is not engaged by the indicator arm 4450 when the indicator arm 4450 is actuated, then the leaflet will not be sufficiently engaged by the barbed portion 4440 of the moveable arm 4430.

[00284] The indicator flex or hinge portion 4460 allows the indicator arm 4450 to be actuated separately from the moveable arm 4430 to facilitate detection of the depth of engagement of the native leaflet arranged between the moveable arm 4430 and the fixed arm 4410 of the clasp 4400. The indicator flex or hinge portion 4460 is similar to the patterned flex/hinge portion 4420 and is formed from a series of spring segments 4462 and cutouts 4464. In some embodiments, the spring force of the indicator flex/hinge portion 4460 is less than the pinching force imparted to the moveable arm 4430 by the joint, flex, or hinge portion 4420 so that the indicator arm 4450 can be actuated many times to detect the position of the leaflet while the moveable arm 4430 with a stronger pinching force is actuated once the leaflet is with barbs is held in a desirable position by the indicator arm 4450. The lower pinching force of the indicator arm 4450 reduces the force imparted onto the leaflet tissue so that the indicator arm 4450 can be repositioned repeatedly and be less likely to puncture or otherwise damage the leaflet tissue. The lower pinching force also allows the indicator arm 4450 to pulse or jump as the heart beats.

[00285] Referring now to Figures 48-50, the clasp or clasp 4400 is shown in an open position. The moveable arm 4430 and indicator arm 4450 are biased or spring-loaded in a closing direction and are moved to and held in the open position by tension applied to actuation lines (not shown) attached to the holes 4448, 4452 in each of the moveable arm 4430 and indicator arm 4450, respectively.

[00286] Referring now to Figures 51-52, the clasp or barbed clasp 4400 is shown with the indicator arm 4450 in a fully deployed or actuated position, that is, the furthest extent that the indicator arm 4450 is capable of reaching when the indicator arm 4450 does not engage with

the leaflet tissue during actuation. The indicator arm 4450 is allowed to actuate in the closing direction when tension on actuation lines (not shown) attached to the hole 4452 in the end of the indicator arm 4450 is decreased. In the fully actuated position, the indicator arm 4450 forms an X-shape with the fixed arm 4410 that is visible via imaging devices so that the operator knows that the indicator arm 4450 has not engaged the leaflet.

[00287] Referring now to Figures 53-55, the clasp or barbed clasp 4400 is shown with the indicator arm 4450 in an engaged or closed position. That is, the position that the indicator arm 4450 would be in when the leaflet tissue has been engaged during actuation. The indicator arm 4450 is allowed to actuate in the closing direction when tension on actuation lines (not shown) attached to the hole 4452 in the end of the indicator arm 4450 is decreased. In the closed position, the indicator arm 4450 does not cross the fixed arm 4410 and does not form an X-shape with the fixed arm 4410. Thus, the operator knows that the indicator arm 4450 has engaged the leaflet tissue when the indicator arm 4450 has been actuated and no X-shape is visible when the clasp 4400 is viewed with an imaging device. In addition, or instead, the indicator arm 4450 can be optically monitored to detect pulsing or jumping of the indicator arm as the heart beats. This jumping or bouncing of the indicator arm indicates to the operator that the indicator arm has engaged leaflet tissue.

[00288] Referring now to Figures 56-58, the clasp or barbed clasp 4400 is shown with the moveable arm 4430 and the indicator arm 4450 both in a closed position. When the clasp 4400 is closed, the moveable arm 4430 and the indicator arm 4450 exert a pinching force that retains the native leaflet tissue to be secured within the clasp 4400. Additionally, a tortuous path for retaining the captured leaflet tissue is formed by the fixed arm 4410, the moveable arm 4430, and the barbed portion 4440. The clasp 4400 is biased in the closed direction by the shape-setting of the moveable arm 4430 and the indicator arm 4450 in preloading positions (Figures 59-61).

[00289] Referring now to Figures 59-61, the clasp 4400 is shown with the fixed arm 4410 and the indicator arm 4450 in a shape-setting or preloading position. As has been discussed with respect to other embodiments, shape-setting of the fixed arm 4410 and the indicator arm 4450 relative to the moveable arm 4430 forms a pinching force between the components of the clasp 4400 when the clasp 4400 is in the closed position.

[00290] Referring now to Figure 59, the fixed arm 4410 is shape set at an angle 4410A from the moveable arm 4430. In certain embodiments, the angle 4410A between the neutral and shape-set positions of the tongues 4411 of the fixed arm 4410 is between about 180 to about

270 degrees, or about 270 degrees. To move the fixed arm 4410 into the shape set position, the fixed arm 4410 is bent upward and the tongues 4411 of the fixed arm 4410 are passed through openings in the moveable arm 4430 formed between the side beams 4432 and the indicator arm 4450.

[00291] Referring again to Figure 59, the indicator arm 4450 is shape set at an angle 4450A from the moveable arm 4430. In certain embodiments, the angle 4450A between the neutral and shape-set positions of the beam 4451 of the indicator arm 4450 is between about 90 degrees to about 180 degrees, or between about 100 degrees and about 150 degrees, or about 135 degrees. The shape set position of the indicator arm 4450 is selected such that the indicator arm 4450 will pass between the tongues 4411 of the fixed arm 4410 to form the X-shape described above.

[00292] Referring now to Figures 62-66, the example clasp or barbed clasp 4400 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 62, the clasp 4400 is shown in an open condition with a native leaflet 42, 44 partially inserted into the opening 4406 of the clasp 4400 formed between the fixed and moveable arms 4410, 4430. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the indicator arm 4450 is actuated via actuation lines (see Fig. 41) as shown in Figures 63 and 65.

[00293] Referring now to Figure 63, the indicator arm 4450 is actuated by releasing tension on an actuation line (see Fig. 41) connected to the hole 4452 at the end of the indicator arm 4450. Because the leaflet 42, 44 is not at or beyond the minimum engagement depth the indicator arm 4450 misses or slips off of the leaflet 42, 44 and moves to a fully actuated position that is beyond the fixed arm 4410 of the clasps 4400. The indicator arm 4450 crosses the fixed arm 4410 to form an X-shape that is visible via imaging devices used to monitor implantation and deployment of the prosthetic device.

[00294] Referring now to Figure 64, the indicator arm 4450 is retracted by applying tension to the actuation line and the clasp 4400 is repositioned so that the leaflet 42, 44 is more deeply inserted into the opening 4406 of the clasp 4400. The indicator arm 4450 is then actuated by releasing tension on the actuating line, as can be seen in Figure 65. Because the leaflet 42, 44 has been inserted into the clasp 4400 at or beyond the minimum desired engagement depth, the indicator arm 4450 engages and pinches the leaflet 42, 44 against the fixed arm 4410. Engagement with the leaflet 42, 44 prevents the indicator arm 4450 from moving past the

fixed arm 4410 of the clasp 4400 to form the X-shape shown in Figure 63. In addition, or instead, the indicator arm 4450 can be optically monitored to detect pulsing or jumping of the indicator arm as the heart beats. This jumping or bouncing of the indicator arm indicates to the operator that the indicator arm has engaged leaflet tissue. Thus, the indicator arm 4450 indicates to an observer observing the installation via an imaging device that the leaflet 42, 44 is inserted into the opening 4406 beyond the minimum desired engagement depth that is determined by the length of the indicator arm 4450.

[00295] Referring now to Figure 66, once the indicator arm 4450 indicates that the leaflet 42, 44 is sufficiently inserted into the opening 4406, the moveable arm 4430 is actuated by releasing tension on the actuating line so that the leaflet 42, 44 is pinched between the barbed portion 4440 and the fixed arm 4410 to secure the leaflet 42, 44 firmly within the clasp 4400.

[00296] Referring now to Figures 84-102, example clasps (often illustrated as barbed clasps, though other friction-enhancing elements other than barbs can be used) are shown with indicating features that are altered by engagement with the native leaflet tissue. For example, the clasps may include bumps or protrusions that flatten when the native leaflet tissue is pressed against the bump. The bump is sufficient in size to be visible via imaging devices so that absence of the bump indicates that the bump has been pressed against the native leaflet tissue. Thus, the engagement depth of the native leaflet can be determined by the position of the bump and whether the bump is visible.

[00297] Referring now to Figure 84, an example embodiment of a portion of a laser cut clasp is illustrated. The clasp can have a moveable arm 4530, a barbed region 4540, and an indicator arm 4550. The moveable arm and the indicator arm each have flexible portions or hinge portions 4520, 4560, respectively. The flexible region 4520 of the moveable arm permits the clasp to be configured to the proper shape for implantation and/or to permit the moveable arm to close on to a fixed arm (see Figures 85-89). The flexible region 4560 of the indicator arm permits the indicator arm to drop onto the leaflet and/or to bounce on the leaflet. The indicator arm 4550 can have a flexible bump 4552 on it, that can be flattened to indicate that the leaflet is positioned a sufficient depth within the clasp. The bump 4552 can be positioned at a location on the indicator arm between the free end of the indicator arm and the flexible region 4560. The clasp of which a portion is illustrated in Figure 84 operates in the manner explained regarding Figures 85-89.

[00298] Referring now to Figures 85-86, an example clasp 4500 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp

3500 described above, the clasp 4500 includes a fixed arm 4510, a joint, flex, or hinge portion 4520, a moveable arm 4530 having a barbed portion 4540 (though other friction-enhancing portions can be used), and an indicator arm 4550 connected to the joint, flex, or hinge portion 4520 via an indicator flex or hinge portion 4560. The indicator arm 4550 includes an indicating feature or bump 4552 that deforms when pressed against the native leaflet tissue to indicate that the leaflet tissue has reached a desired engagement depth. Thus, the indicating feature 4552 will not indicate that the native leaflet has reached a minimum desired engagement depth until the leaflet is inserted at or beyond the location of the indicating feature 4552. Once the leaflet 42, 44 has reached the desired engagement depth, actuation of the indicator arm 4550 presses the indicating feature 4552 against the leaflet tissue 42, 44 to cause the indicating feature 4552 to flatten and thereby indicate that the leaflet 42, 44 has been inserted into the clasp 4500 at or beyond the desired engagement depth. The clasp 4500 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00299] Referring now to Figures 87-90, the example clasp 4500 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 87, the clasp 4500 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening 4506 of the clasp 4500 formed between the fixed and moveable arms 4510, 4530. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the indicator arm 4550 is actuated via actuation lines (see Fig. 133) as shown in Figures 88-89.

[00300] Referring now to Figure 88, when the indicator arm 4550 is actuated to press the leaflet 42, 44 against the fixed arm 4510, a portion of the indicator arm 4550 may contact the leaflet 42, 44 without contacting the indicating feature 4552 when the engagement depth of the leaflet 42, 44 is less than the minimum engagement depth. As can be seen in Figure 89, the indicating feature 4552 is deformed or flattened from contact with the leaflet 42, 44 when the leaflet is inserted into the clasp 4500 at or beyond the minimum engagement depth. Referring now to Figure 90, the indicating feature 4552 is deformed by the leaflet 42, 44 to indicate that the leaflet 42, 44 has been inserted at or beyond the minimum engagement depth. When the leaflet 42, 44 has been moved into the desired position, the moveable arm 4530 is actuated so that the leaflet 42, 44 can be secured within the barbed clasp 4500 by the barbed portion 4540.

[00301] Referring now to Figures 91-92, an example clasp 4600 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 4600 includes a fixed arm 4610, a joint, flex, or hinge portion 4620, a moveable arm 4630 having a barbed portion 4640 (though other friction-enhancing portions can be used), and an indicator arm 4650 connected to the joint, flex, or hinge portion 4620 via an indicator flex or hinge portion 4660. The fixed arm 4610 includes an indicating feature or bump 4612 that deforms when the native leaflet tissue is pressed against the indicating feature 4612 by the indicating arm 4650 to indicate that the leaflet tissue has reached a minimum desired engagement depth. Thus, the indicating feature 4612 will not indicate that the native leaflet has reached the desired engagement depth until the leaflet is inserted at or beyond the location of the indicating feature 4612. Once the leaflet 42, 44 has reached the desired engagement depth, actuation of the indicator arm 4650 presses the leaflet tissue 42, 44 against the indicating feature 4612 to cause the indicating feature 4612 to flatten and thereby indicate that the leaflet 42, 44 has been inserted into the clasp 4600 at or beyond the desired engagement depth. The clasp 4600 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00302] Referring now to Figures 93-94, the example clasp 4600 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 93, the clasp 4600 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening 4606 of the clasp 4600 formed between the fixed and moveable arms 4610, 4630. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the indicator arm 4650 is actuated via actuation lines (not shown) as shown in Figures 94-95.

[00303] Referring now to Figure 94, when the indicator arm 4650 is actuated to push the leaflet 42, 44 against the fixed arm 4610, the leaflet 42, 44 may contact a portion of the fixed arm 4610 without contacting the indicating feature 4612 when the engagement depth of the leaflet 42, 44 is less than the minimum engagement depth. As can be seen in Figure 95, the indicating feature 4612 is deformed or flattened from contact with the leaflet 42, 44 when the leaflet is inserted into the clasp 4600 at or beyond the minimum engagement depth and is pressed against the indicating feature 4612 by the indicating arm 4650. Referring now to Figure 96, the indicating feature 4612 is deformed by the leaflet 42, 44 to indicate that the leaflet 42, 44 has been inserted at or beyond the minimum engagement depth. When the

leaflet 42, 44 has been moved into the desired position, the moveable arm 4630 is actuated so that the leaflet 42, 44 can be secured within the barbed clasp 4600 by the barbed portion 4640.

[00304] Referring now to Figures 97-98, an example clasp 4700 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 4700 includes a fixed arm 4710, a joint, flex, or hinge portion 4720, and a moveable arm 4730 having a barbed portion 4740 (though other friction-enhancing portions can be used). The moveable arm 4730 also includes an indicating feature or bump 4732 disposed between the barbed portion 4740 and the joint, flex, or hinge portion 4720. The indicating feature 4732 deforms when the native leaflet tissue is pressed against the indicating feature 4732 by the fixed arm 4710 to indicate that the leaflet tissue has reached a minimum desired engagement depth. Thus, the indicating feature 4732 will not indicate that the native leaflet has reached the desired engagement depth until the leaflet is inserted at or beyond the location of the indicating feature 4732. Once the leaflet 42, 44 has reached the desired engagement depth, actuation of the moveable arm 4730 squeezes the leaflet tissue 42, 44 between the fixed arm 4710 and the indicating feature 4732 to cause the indicating feature 4732 to flatten and thereby indicate that the leaflet 42, 44 has been inserted into the clasp 4700 at or beyond the desired engagement depth. The clasp 4700 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00305] Referring now to Figures 99-100, the example barbed clasp 4700 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 99, the barbed clasp 4700 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening 4706 of the barbed clasp 4700 formed between the fixed and moveable arms 4710, 4730. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the moveable arm 4730 is actuated via actuation lines (not shown) as shown in Figures 100.

[00306] Referring Figure 100, when the moveable arm 4730 is actuated to push the leaflet 42, 44 against the fixed arm 4710, the leaflet 42, 44 may contact a portion of the moveable arm 4730 without contacting the indicating feature 4732 when the engagement depth of the leaflet 42, 44 is less than the minimum desired engagement depth.

[00307] As can be seen in Figure 100A, the indicating feature 4732 is deformed or flattened from contact with the leaflet 42, 44 when the leaflet 42, 44 is inserted into the clasp 4700 at or beyond the minimum engagement depth and is pressed against the indicating feature 4732. That is, the indicating feature 4732 is deformed by the leaflet 42, 44 to indicate that the leaflet 42, 44 has been inserted at or beyond the minimum engagement depth. In some embodiments, actuation of the moveable arm 4730 also causes the barbed portion 4740 to engage and secure the leaflet 42, 44 within the barbed clasp 4700. If the indicating feature 4732 indicates that the leaflet 42, 44 is not inserted to the desired depth, the clasp 4700 can be opened to allow for repositioning of the leaflet 42, 44.

[00308] Referring now to Figures 101–102, an example clasp 4800 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 4800 includes a fixed arm 4810, a joint, flex, or hinge portion 4820, and a moveable arm 4830 having a barbed portion 4840 (though other friction-enhancing portions can be used). The fixed arm 4810 also includes an indicating feature or bump 4812 disposed at a distance from the joint, flex, or hinge portion that is less than a distance between the barbed portion 4840 and the joint, flex, or hinge portion 4820. The indicating feature 4812 deforms when the native leaflet tissue is pressed against the indicating feature 4812 by the moveable arm 4830 to indicate that the leaflet tissue has reached a minimum desired engagement depth. Thus, the indicating feature 4812 will not indicate that the native leaflet 42, 44 has reached the desired engagement depth until the leaflet 42, 44 is inserted at or beyond the location of the indicating feature 4812. Once the leaflet 42, 44 has reached the desired engagement depth, actuation of the moveable arm 4830 squeezes the leaflet tissue 42, 44 against the indicating feature 4812 of the fixed arm 4810 to cause the indicating feature 4812 to flatten and thereby indicate that the leaflet 42, 44 has been inserted into the clasp 4800 at or beyond the desired engagement depth. The clasp 4800 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00309] Referring now to Figure 101, the clasp 4800 is shown with a native leaflet 42, 44 partially inserted into an opening 4806 of the clasp 4800 formed between the fixed and moveable arms 4810, 4830. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the moveable arm 4830 is actuated via actuation lines.

[00310] Referring now to Figure 101, when the moveable arm 4830 is actuated to push the leaflet 42, 44 against the fixed arm 4810, the leaflet 42, 44 may contact a portion of the fixed

arm 4810 without contacting the indicating feature 4812 when the engagement depth of the leaflet 42, 44 is less than the minimum desired engagement depth.

[00311] As can be seen in Figure 102, the indicating feature 4812 is deformed or flattened from contact with the leaflet 42, 44 when the leaflet 42, 44 is inserted into the clasp 4800 at or beyond the minimum engagement depth and is pressed against the indicating feature 4812 by the moveable arm 4830. That is, the indicating feature 4812 is deformed by the leaflet 42, 44 to indicate that the leaflet 42, 44 has been inserted at or beyond the minimum engagement depth. In some embodiments, actuation of the moveable arm 4830 also causes the barbed portion 4840 to engage and secure the leaflet 42, 44 within the barbed clasp 4800. If the indicating feature 4812 indicates that the leaflet 42, 44 is not inserted to the desired depth, the barbed clasp 4800 can be opened to allow for repositioning of the leaflet 42, 44.

[00312] Referring now to Figure 103, an example embodiment of a portion of a laser cut clasp is illustrated. In Figure 103, cut from one sheet is a clasp having a moveable arm 5230, a fixed arm 5210, and a flexible indicator 1031. The moveable arm 5230 has a cut-out opening 6730 and at least one barb 5240, and a flexible section 5220 that permits the moveable arm to bend at the flexible section, to shape set or otherwise position in in the proper configuration to form a clasp. The fixed arm 5210 has two cut-outs 6740 in it that each extend along a length of the fixed arm, and a flexible indicator that extends across a length of the fixed arm, in between the cut-outs 6740. The fixed arm 5210 also can have an optional flexible section 4470 that can be attached to a paddle portion or coaption or spacer portion to allow the paddle and the clasp to optionally be made from a single piece or the clasp and the coaption or spacer portion to optionally be made from a single piece. The flexible indicator 1031 can have an optional indicator element 1030 on it. The optional indicator element 1030 can be a radiopaque marker. The radiopaque marker can be an additional piece attached to the flexible indicator or it can be printed on the flexible indicator or applied to the flexible indicator in the manner of any of the embodiments described herein.

[00313] Referring now to Figures 104-106, schematic views of example embodiments of a clasp (illustrated as a barbed clasp) for use in an implantable prosthetic device, such as devices 100, 200, and 300 described above, are shown. Like the clasp 3500 described above, the clasp 5200 includes a fixed arm 5210, a joint, flex, or hinge portion 5220, and a moveable arm 5230 having a barbed portion 5240 (though other friction-enhancing portions can be used). The fixed arm 5210 also includes at least one flexible indicator 1031, positioned between cutouts 6740 as shown in Figures 103 and 110. Figure 104 illustrates a schematic

view of a clasp that has one flexible indicator 1031 on the fixed arm that fits through an opening 6730 in the moveable arm 5230. Figure 105 illustrates a schematic view of a clasp that has two flexible indicators 1031 on the fixed arm that fit between two cutout openings 6730 on the moveable arm. When there are a plurality of flexible indicators, the flexible indicators can be aligned or offset along the length of the fixed arm. The flexible indicators can be part of the laser cut clasp or can be attached to the laser-cut clasp frame by welding or rivets or other known means. Figure 106 illustrates a side schematic view of the embodiments illustrated in Figures 104 and 105. From the side view, the clasp appears the same, whether there is one flexible indicator 1031 or two, since the two indicators are aligned in the illustrated example. In Figure 106, the clasp is in an open position and the flexible indicator is curved into a “bump” configuration. Figures 106-109 also illustrates an optional radiopaque indicator 1030 on the flexible bump 1031. The radiopaque indicator can be printed or attached as a separate piece of material to the flexible bump 1031. For example, the radiopaque material can be a coil made of platinum or another radiopaque material. The radiopaque indicator is visible with fluoroscopy and/or other imaging techniques and can assist the user in determining whether the leaflet is properly positioned in the clasp.

[00314] The bump 1031 deforms and flattens when the native leaflet tissue is pressed against the bump 1031 by the moveable arm 5230 to indicate that the leaflet tissue has reached a minimum desired engagement depth. Thus, the bump 1031 will not indicate that the native leaflet 42, 44 has reached the desired engagement depth until the leaflet 42, 44 is inserted at or beyond the location of the bump 1031. Once the leaflet 42, 44 has reached the desired engagement depth, actuation of the moveable arm 5230 squeezes the leaflet tissue 42, 44 against the bump 1031 of the fixed arm 5210 to cause the bump 1031 to flatten and thereby indicate that the leaflet 42, 44 has been inserted into the clasp 5200 at or beyond the desired engagement depth. The clasp 5200 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00315] Referring now to Figures 107-109, the example clasp 5200 illustrated in Figures 104-106 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 107, the clasp 5200 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening of the clasp 5200 formed between the fixed and moveable arms 5210, 5230. In Figures 107-109, the bump 1031 can have an optional

radiopaque indicator on it. The radiopaque indicator can be printed directly on the bump, a coil wrapped around the bump, or printed on a fabric covering the bump, or otherwise fixed to the bump. The radiopaque indicator can be a platinum coil wrapped around the bump, or it can be radiopaque ink printed on it.

[00316] Referring now to Figure 108, when the moveable arm 5230 is actuated to push the leaflet 42, 44 against the fixed arm 5210, the leaflet 42, 44 may contact a portion of the fixed arm 5210 without contacting the bump 1031 when the engagement depth of the leaflet 42, 44 is less than the minimum engagement depth. As can be seen in Figure 109, the bump 1031 is deformed or flattened from contact with the leaflet 42, 44 when the leaflet is inserted into the clasp 4600 at or beyond the minimum engagement depth and is pressed against the bump 1031 by the moveable arm 5230.

[00317] Referring now to Figures 103A-103D, example embodiments of indicators 1031 having optional markers 1030 on a clasp such as the clasp illustrated in Figure 103, are illustrated. Referring to Figure 103A, the flexible indicator arms can be flexible “wing” indicators 1032, one attached to each side of the moveable arm 5230. In another example embodiment, a single wing is disposed on only one side of the clasp. The flexible wing indicators can be cut from the same sheet of material as a laser cut clasp or can be separately cut pieces that are attached to the clasp. As with other example embodiments described herein, the indicator arms can have a different thickness than the clasp to provide a different amount of flexibility. The flexible wing indicators can extend outward and inward at an angle from the moveable arm, similar to butterfly wings. The flexible wing indicators can be attached to the moveable arm or the fixed arm. The flexible wing indicators 1032 can each have an optional radiopaque indicator element 1030 on them. As with other example embodiments described herein, the indicator element can be radiopaque and can be printed or otherwise attached to the flexible wing indicators directly, or to fabric covering the flexible wing indicators. The flexible wing indicators extend at an angle from the moveable arm 5230 of the clasp, outwardly away from a longitudinal axis of the clasp, and in toward the center of the clasp toward the fixed arm. When a leaflet is captured by the clasp and applies a force to a flexible wing indicator 1032, the flexible wing indicator flexes back toward the moveable arm (see Figures 108A and 109A for schematic illustrations).

[00318] Referring now to Figure 103B, a flexible wire indicator 1031 can be positioned in the opening 6740 of the fixed arm 5210 of a clasp. This can be in addition to the flexible wing indicators 1032 or can be present without the flexible wing indicators. The flexible wire

indicator can be a wire extending along a longitudinal axis of the opening 6740 of the clasp, attached at one end closer to a flex or hinge portion 4470 and attached at the other end closer to the flex or hinge portion 5220. There can be an optional radiopaque marker 1030 positioned along the length of the flexible wire indicator 1031. The wire can be held in place by being secured at attachment points 1034. The attachment point can have the wire indicator attached by welding, suturing, or other known methods of attachment. Figures 108B and 109B illustrate schematic views of the example embodiment of the clasp in Figure 103B when a leaflet is positioned in the clasp a sufficient depth to force the indicators 1031, 1032, to flex. Figure 103D illustrates an example embodiment having only the flexible wire indicator 1031 without the flexible wing indicators. Figures 108D and 109D illustrate schematic views of the example embodiment of the clasp in Figure 103D when a leaflet is positioned in the clasp a sufficient depth to force the indicator 1031 to flex.

[00319] Referring now to Figure 103C, an example embodiment of a clasp having flexible wire indicators 1031 is illustrated. There can be a flexible wire indicator 1031 extending longitudinally across the opening 6740, having an optional radiopaque indicator 1030 positioned along the wire indicator 1031 and secured to the clasp at attachment points 1034. A flexible wire indicator 1031 can also be positioned longitudinally across the opening 6730 in the moveable arm 5230 in addition to or instead of, the flexible wire indicator in the opening 6740 of the fixed arm. The flexible wire indicator 1031 in the moveable arm opening 6730 can extend partway across the opening and be attached at one end near the flex or hinge portion 5220, and at its other end, at a cross-piece 1033 that extends horizontally across the opening 6740. The cross-piece can have an optional radiopaque indicator printed or attached to it. The flexible wire indicator can have an optional radiopaque marker 1030 positioned along its length. Figures 108C and 109C illustrate schematic views of the example embodiment of the clasp in Figure 103C when a leaflet is positioned in the clasp a sufficient depth to force the indicators 1031 to flex.

[00320] Referring now to Figures 104A and 106A, schematic views of example embodiments of a clasp for use in an implantable prosthetic device, such as the example embodiment shown in Figure 103A having flexible “wing” indicators 1032, one attached to each side of the moveable arm 5230, are illustrated. The flexible wing indicators can extend at an angle, laterally outward from the moveable arm and in toward an end of the fixed arm. While shown here attached to the moveable arm, the flexible wing indicators can optionally be attached to the fixed arm instead. The flexible wing indicators 1032 can each have an

optional indicator element 1030 on them. Figure 106A illustrates a side view of the embodiment illustrated in Figure 104A. In Figures 104A and 106A, the clasp is in an open position and the flexible wing indicators 1032 extend outward from the moveable arm as shown in Figure 104A and inward toward the portion of the clasp where the leaflet would be positioned as shown in Figure 106A. An optional radiopaque indicator 1030 on the flexible wing indicators is shown.

[00321] The flexible wing indicators 1032 deform and flatten when the native leaflet tissue is pressed against them as the clasp closes to indicate that the leaflet tissue has reached a minimum desired engagement depth in the clasp. In one example embodiment, if the leaflet is inserted off-center in the clasp, only one flexible wing indicator may flex and deform, while the other remains undeformed. The clasp 5200 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00322] Referring now to Figure 108A and 109A, use of the clasp of the example embodiment of Figure 103A is illustrated. Referring now to Figure 108A, when the moveable arm 5230 is actuated to push the leaflet 42, 44 against the fixed arm 5210, the leaflet 42, 44 may contact a portion of the fixed arm 5210 and a portion of the moveable arm 5230 without contacting the flexible wing indicators 1032 when the engagement depth of the leaflet 42, 44 is less than the minimum engagement depth. As can be seen in Figure 109A, the flexible wing indicators 1032 (only one flexible wing indicator is visible in Figure 109A because the other is directly behind it) are deformed or flattened from contact with the leaflet 42, 44 when the leaflet is inserted into the clasp 4600 at or beyond the minimum engagement depth and is pressed against the flexible wing indicators 1032 by the fixed arm 5210. The location of the optional radiopaque indicating elements 1030 can indicate to the user how much the flexible wing indicators have moved and thus determine the position of the leaflet.

[00323] Referring now to Figures 104B and 106B, schematic views of an example embodiment of a clasp (illustrated as a barbed clasp) for use in an implantable prosthetic device, such as the example embodiment shown in Figure 103B having flexible “wing” indicators 1032, one attached to each side of the moveable arm 5230, are illustrated. The flexible wing indicators can extend away from the moveable arm at an angle, and toward an open end of the clasp. While shown here attached to the moveable arm, the flexible wing indicators can optionally be attached to the fixed arm. The flexible wing indicators 1032 can each have an indicator element 1030 on them. Figure 106B illustrates a side schematic view

of the embodiments illustrated in Figure 104B. In Figures 104B and 106B, the clasp is in an open position and the flexible wing indicators 1032 extend outward from the moveable arm as shown in Figure 104B and inward toward the portion of the clasp where the leaflet would be positioned as shown in Figure 106B. The wire indicator 1031 that extends longitudinally has a bump configuration when in its resting uncompressed state, such as when the clasp is open. Optional radiopaque indicators 1030 on the flexible wing indicators and on the wire indicators 1031 are shown.

[00324] The flexible wing indicators 1032 deform and flatten when the native leaflet tissue is pressed against them as the clasp closes to indicate that the leaflet tissue has reached a minimum desired engagement depth and horizontal position along the clasp. In one example embodiment, if the leaflet is inserted off-center into the clasp, only one flexible wing indicator may flex and deform, while the other remains undeformed. The wire indicator 1031 also flattens and deforms due to the pressure exerted by a leaflet on it if the leaflet is positioned over it when the clasp is closed.

[00325] Referring now to Figure 108B, when the moveable arm 5230 is actuated to push the leaflet 42, 44 against the fixed arm 5210, the leaflet 42, 44 may contact a portion of the fixed arm 5210 and a portion of the moveable arm 5230 without contacting either the flexible wing indicators 1032 or the wire indicator 1031 when the engagement depth of the leaflet 42, 44 is less than the minimum engagement depth. As can be seen in Figure 109B, the flexible wing indicators 1032 (only one flexible wing indicator is visible in Figure 109B because the other is directly behind it) and the wire indicator 1031 have deformed or flattened from contact with the leaflet 42, 44 when the leaflet is inserted into the clasp 4600 at or beyond the minimum engagement depth and is pressed against the flexible wing indicators 1032 by the fixed arm 5210, and against the wire indicator 1031 by the moveable arm. The wire indicator can be a wire, or a laser cut sheet attached to the fixed arm, as described in other example embodiments having a flexible bump indicator described herein. The location of the optional radiopaque indicating elements 1030 can indicate to the user how much the flexible wing indicators have moved and thus determine the position of the leaflet.

[00326] Referring now to Figures 104C and 106C, schematic views of example embodiments of a clasp (illustrated as a barbed clasp) for use in an implantable prosthetic device, such as but not limited to the example embodiment shown in Figure 103C having flexible two wire indicators 1031. Each of the indicators has a bump configuration. One indicator is attached to the moveable arm and one indicator is attached to the fixed arm. The indicators that

extend along the moveable arm and the fixed arm can also be laser cut and attached to the arms, in some example embodiments. The wire indicators 1031, can have optional radiopaque indicator elements attached to them, printed on them, and/or wrapped around them. For example, the radiopaque indicator can be a coil made of a radiopaque material wrapped around at least a portion of the wire. Figure 106C illustrates a side schematic view of the embodiments illustrated in Figure 104C. In Figures 104C and 106C, the clasp is in an open position and the wire indicators 1031 have a bump configuration where the bump extends inward into the clasp toward where the leaflet would be inserted.

[00327] Referring now to Figure 108C, when the moveable arm 5230 is actuated to push the leaflet 42, 44 against the fixed arm 5210, the leaflet 42, 44 may contact a portion of the fixed arm 5210 and a portion of the moveable arm 5230 without contacting either of the wire indicators 1031 when the engagement depth of the leaflet 42, 44 is less than the minimum engagement depth. When the clasp is closed and the leaflet is not at a minimum engagement depth, or there is no leaflet within the clasp at all, the wire indicators 1031 flatten and deform as they press against each other, due to the pressure applied by each wire indicator against the other wire indicator. As is illustrated, the two optional radiopaque indicating elements 1030 become adjacent to one another to provide an indication that the leaflet has not been engaged.

[00328] Referring now to Figure 109C, the wire indicators 1031 deform and flatten against the leaflet when the native leaflet tissue is pressed against them as the clasp closes to indicate that the leaflet tissue has reached a minimum desired engagement depth and horizontal position along the clasp. If the leaflet is not centered over the wire indicator when the clasp is closed, the wire indicator 1031 retains its bump shape and passes through opening 6730 on the moveable arm of the clasp. As is illustrated, the two optional radiopaque indicating elements 1030 are spaced apart to indicate that the leaflet has been engaged.

[00329] Referring now to Figures 104D and 106D, schematic views of example embodiments of a clasp (illustrated as a barbed clasp) for use in an implantable prosthetic device, such as but not limited to the example embodiment shown in Figure 103D having a flexible indicator 1031 with a bump configuration, is illustrated. The flexible indicator can be a wire indicator. The indicator 1031 can also be laser cut and attached to one of the arms or integrally formed with one of the arms, in some example embodiments. The indicator 1031 can have an optional radiopaque indicator element 1030 attached to or wrapped around it. For example, the radiopaque indicator can be a coil made of a radiopaque material wrapped around at least a portion of the wire. The moveable arm 5230 can also have an optional radiopaque indicator

element 1030 on it. Figure 106D illustrates a side schematic view of the embodiments illustrated in Figure 104D. In Figures 104D and 106D, the clasp is in an open position and the indicator 1031 has a bump configuration where the bump extends into the clasp toward where the leaflet would be inserted.

[00330] Referring now to Figure 108D, when the moveable arm 5230 is actuated to push the leaflet 42, 44 against the fixed arm 5210, the leaflet 42, 44 may contact a portion of the fixed arm 5210 and a portion of the moveable arm 5230 without contacting the wire indicators 1031, when the engagement depth of the leaflet 42, 44 is less than the minimum engagement depth. When the clasp is closed and the leaflet is not at a minimum engagement depth, or there is no leaflet within the clasp at all, the wire indicator 1031 can at least partially flatten and deform due to the pressure applied by the moveable arm against it. In some example embodiments, the wire indicator 1031 can be attached to the moveable arm and is partially flattened by pressure applied to it by the fixed arm. As is illustrated, the two optional radiopaque indicating elements 1030 become adjacent to one another to provide an indication that the leaflet has not been engaged.

[00331] Referring now to Figure 109D, the wire indicator 1031 deforms and flattens against the leaflet when the native leaflet tissue is pressed against them as the clasp closes to indicate that the leaflet tissue has reached a minimum desired engagement depth and horizontal position along the clasp. As is illustrated, the two optional radiopaque indicating elements 1030 are spaced apart to indicate that the leaflet has been engaged.

[00332] Referring now to Figures 104E and 106E, schematic views of an example embodiment of a clasp (illustrated as a barbed clasp) for use in an implantable prosthetic device, having a flexible indicator 1031 with a bump configuration connected to the fixed arm 5210 and an opening 6730 in the moveable arm 5230, is illustrated. The flexible indicator can be a wire indicator. The flexible indicator can also be laser cut and attached to the arms, in some example embodiments. The indicator 1031 can have an optional radiopaque indicator element 1030 attached to or wrapped around it. For example, the radiopaque indicator can be a coil made of a radiopaque material wrapped around at least a portion of the wire. The moveable arm 5230 has an opening 6730 in it and can also have optional radiopaque indicator elements 1030 on the side arms of its frame. Figure 106E illustrates a side schematic view of the embodiment illustrated in Figure 104E. In Figures 104E and 106E, the clasp is in an open position and the indicator 1031 has a bump

configuration where the bump extends inward in the clasp toward where the leaflet would be inserted.

[00333] Referring now to Figure 108E, when the moveable arm 5230 is actuated to push the leaflet 42, 44 against the fixed arm 5210, the leaflet 42, 44 may contact a portion of the fixed arm 5210 and a portion of the moveable arm 5230 without contacting the indicator 1031, when the engagement depth of the leaflet 42, 44 is less than the minimum engagement depth. When the clasp is closed and the leaflet is not at a minimum engagement depth, or there is no leaflet within the clasp at all, the indicator 1031 remains unflattened or only partially flattened and the indicator 1031 can pass into or through the opening 6730 of the moveable arm when the leaflet is not properly inserted in the clasp. As is illustrated, the optional radiopaque indicating elements 1030 become aligned when the indicator 1031 moves into the opening in the moveable arm to provide an indication that the leaflet have not been engaged.

[00334] Referring now to Figure 109E, the wire indicator 1031 deforms and flattens against the leaflet when the native leaflet tissue is pressed against them as the clasp closes to indicate that the leaflet tissue has reached a minimum desired engagement depth in the clasp. As is illustrated, the two optional radiopaque indicating elements 1030 are spaced apart to indicate that the leaflet has been engaged.

[00335] Figures 226-229 illustrate a variation of the clasp 4400 illustrated by Figures 48-66. In the example illustrated by Figures 226-229, the clasp includes a flexible wire indicator 1031 extending longitudinally across the hoop shaped moveable arm 4430. One end of the flexible wire indicator 1031 is attached at or near the flex portion or hinge portion 4420 (See Figure 227), and the other end of the wire is attached at the opposite end of the moveable arm 4430, in between barbs 4444. The clasps 4400 can be used in implantable prosthetic devices, such as devices 100, 200, 300 described above or any other implantable prosthetic device.

[00336] The clasp 4400 illustrated by Figures 226-229 has a fixed arm 4410, a patterned flex portion or patterned hinge portion 4420, a moveable arm 4430 formed in the shape of a hoop or loop, and a barbed portion 4440 (though other friction-enhancing portions can be used) of the moveable arm 4430. In this embodiment, a leaflet depth indicator can be a flexible feature, that can be a wire indicator 1031 which remains flat in a straight configuration when the clasp is open and when there is no leaflet positioned to overlap it in the closed clasp. When a leaflet is present, the wire indicator 1031 is pressed through the hoop shaped moveable arm 4430. An optional radiopaque coil 1030 can be wrapped around the indicating wire 1031, and can be seen using imaging techniques, such as fluoroscopy. When the

indicating wire and coil are seen on the outer side of the moveable arm 4430 of the clasp, the amount of the indicating arm 1031 and/or coil 1030 that is visible indicates the depth of the leaflet to the operator.

[00337] The clasp 4400 can include any of the features or combinations of features of the other clasps described herein. The clasp 4400 can be laser cut from a flat sheet or a tube of shape-memory alloy, such as Nitinol, and then shape-set into a desired shape.

[00338] The illustrated fixed arm 4410 has two tongue portions 4411 that each include optional holes 4412 for attaching the fixed arm 4410 to an implantable device.

[00339] The flex portion or hinge portion 4420 can take a wide variety of different forms. In the illustrated example, the flex or hinge portion 4420 is formed from a plurality of spring segments 4422 and cutouts 4424. Tongue portions 4411 of the fixed arm 4410 extend from one end of the patterned flex portion or patterned hinge portion 4420 and the moveable arm 4430 extends from the other end of the flex or hinge portion 4420.

[00340] The moveable arm 4430 of the clasp 4400 has a hoop-like shape. The hoop-shaped moveable arm 4430 includes side beams 4432 that are thinner and more flexible, particularly in the lateral direction. The side beams 4432 include a first flex or hinge portion 4434 arranged toward the proximate end of the moveable arm 4430 and a second flex or hinge portion 4436 arranged at the distal end of the moveable arm 4430. The first flex or hinge portion 4434 is formed by one or more bends in the side beams 4432. The hoop-shape of the moveable arm 4430 and flexible side arms 4432 allow the moveable arm 4430 to be collapsed by merely retracting the clasp 4400 into a delivery sheath (not shown).

[00341] The hoop-like shape of the moveable arm 4430 provides for a wider barbed portion 4440 that can include more barbs 4442 with the same or greater lateral spacing than other clasps. The wider spacing of the barbs 4442 improves capture of the native leaflets. The barbs 4442 are also optionally longitudinally staggered as a result of their position on the hoop-like shape of the moveable arm 4430. That is, two center barbs 4444 are arranged further away from the flex or hinge portion 4420 and two outer barbs 4446 are arranged closer to the flex or hinge portion 4420. The barbed portion 4440 of the moveable arm 4430 also includes optional holes 4448 for receiving an actuation suture (not shown). In certain embodiments, the hoop shape of the moveable arm 4430 is similar to the shape of wide outer paddles of an implantable device so that pinching forces of the paddles are spread out evenly on the barbs, further improving the retention of the native leaflets. The ends of the barbs 4442 can be further sharpened using any suitable sharpening means.

[00342] Referring now to Figures 226 and 227, the clasp 4400 is shown in an open position. The moveable arm 4430 is biased or spring-loaded in a closing direction and are moved to and held in the open position by tension applied to actuation lines (not shown). The indicating wire 1031 is in a straight undeflected configuration because there is no leaflet engaged in the open clasp in Figures 226-227.

[00343] Referring now to Figure 228, the clasp 4400 is shown in a fully deployed or actuated position, without a leaflet in place. The indicating wire 1031 with optional radiopaque coil 1030 remains undeflected and is positioned on an interior side of the moveable arm 4430 and/or does not extend beyond an outer profile of the moveable arm 4430. The indicating wire 1031 and coil 1030 are not seen outside of the profile of the moveable arm 4430. The absence of the indicator arm outside of the profile of the clasp 4400 by imaging equipment indicates to the operator that a leaflet has not been captured.

[00344] Referring now to Figure 229, the clasp 4400 is shown with the moveable arm 4430 in a closed position. When the clasp 4400 is closed, the moveable arm 4430 and the indicator arm 4450 exert a pinching force that retains the native leaflet tissue to be secured within the clasp 4400. The clasp 4400 is biased in the closed direction by the shape-setting of the moveable arm 4430 in a preloading position. The closed clasp has captured a sufficient amount of leaflet tissue, that is, the depth of the leaflet in the clasp is sufficient for the clasp to be considered properly positioned, as indicated by the indicating wire 1031 and coil 1030 being deflected through the opening of the hoop shaped moveable arm, such that a portion of the indicating wire 1031 and/or the coil 1030 move past the outside profile of the moveable arm 4430 of the clasp 4400. The indicating wire 1031 and/or coil 1030 beyond the profile of the clasp can be seen on imaging equipment, such as fluoroscopy equipment as represented by Figure 229 to indicate that the valve leaflet has been properly captured by the clasp 4400.

[00345] Figures 230-233 illustrate a variation of the clasp 4400 illustrated by Figures 48-66. In the example illustrated by Figures 230-233, the clasp includes a flexible wire indicator 1031 extending horizontally across the hoop shaped moveable arm 4430. Each end of the wire is attached to a side arm 4432 of the moveable arm 4430. The wire indicator 1031 can be positioned at any location that indicates proper insertion of the native valve leaflets. In one example embodiment, the wire indicator is positioned closer to the flex or hinge region than the barbed region of the clasp. The clasps 4400 can be used in implantable prosthetic devices, such as devices 100, 200, 300 described above or any other implantable prosthetic device.

[00346] The clasp 4400 illustrated by Figures 230-233 has a fixed arm 4410, a patterned flex portion or patterned hinge portion 4420, a moveable arm 4430 formed in the shape of a hoop or loop, and a barbed portion 4440 of the moveable arm 4430. In this embodiment, a leaflet depth indicator can be a flexible feature, that can be a wire indicator 1031 which remains flat in a straight configuration when the clasp is open and when there is no leaflet positioned to overlap it in the closed clasp. When a leaflet is present, the wire indicator 1031 is pressed through the hoop shaped moveable arm 4430. An optional radiopaque coil 1030 can be wrapped around the indicating wire 1031, and can be seen using imaging techniques, such as fluoroscopy. When the indicating wire and coil are seen on the outer side of the moveable arm 4430 of the clasp, the amount of the indicating arm 1031 and/or coil 1030 that is visible indicates the depth of the leaflet to the operator.

[00347] Referring now to Figures 230 and 231, the clasp 4400 is shown in an open position. The moveable arm 4430 is biased or spring-loaded in a closing direction and are moved to and held in the open position by tension applied to actuation lines (not shown). The indicating wire 1031 is in a straight undeflected configuration because there is no leaflet engaged in the open clasp in Figures 230 and 231.

[00348] Referring now to Figure 232, the clasp 4400 is shown in a fully deployed or actuated position, without a leaflet in place. The indicating wire 1031 with optional radiopaque coil 1030 remains undeflected and is positioned on an interior side of the moveable arm and/or does not extend beyond an outer profile of the moveable arm 4430. The indicating wire 1031 and coil 1030 are not seen outside the profile of moveable arm 4430 in Figure 232. The absence of the indicator arm outside of the profile of the clasp 4400 by imaging equipment indicates to the operator that a leaflet has not been captured.

[00349] Referring now to Figure 233, the clasp 4400 is shown with the moveable arm 4430 in a closed position. When the clasp 4400 is closed, the moveable arm 4430 and the indicator arm 4450 exert a pinching force that retains the native leaflet tissue to be secured within the clasp 4400. The clasp 4400 is biased in the closed direction by the shape-setting of the moveable arm 4430 in a preloading position. The closed clasp has captured a sufficient amount of leaflet tissue, that is, the depth of the leaflet in the clasp is sufficient for the clasp to be considered properly positioned, as indicated by the indicating wire 1031 and coil 1030 being deflected through the opening of the hoop shaped moveable arm, such that a portion of the indicating wire 1031 and/or coil 1030 move past the outside profile of the moveable arm 4430 of the clasp 4400. The indicating wire 1031 and/or coil 1030 beyond the profile of the

clasp can be seen on imaging equipment, such as fluoroscopy equipment, as represented by Figure 233 to indicate that the valve leaflet has been properly captured by the clasp 4400.

[00350] Figures 234-237 illustrate a variation of the clasp 4400 illustrated by Figures 48-66. In the example illustrated by Figures 234-237, the clasp includes a flexible wire indicator 1031 extending longitudinally across the hoop shaped moveable arm 4430. One end of the flexible wire indicator 1031 is attached near the flex or hinge portion 4420. The other end of the wire is attached to a cross wire 1033 that extends horizontally across the opening of the moveable arm 4430. The crosswire 1033 can be positioned across the middle of the moveable arm, can be positioned closer to the barbed end than the flex or hinge portion, or can be positioned closer to the flex portion or hinged portion than the barbed portion, depending on the minimum leaflet insertion depth. The crosswire 1033 can be replaced with a laser cut sheet component, which can be integrally formed with the clasp or can be a separate piece that is attached to the clasp. The clasps 4400 can be used in implantable prosthetic devices, such as devices 100, 200, 300 described above or with any other implantable prosthetic device.

[00351] The clasp 4400 has a fixed arm 4410, a patterned flex portion or patterned hinge portion 4420, a moveable arm 4430 formed in the shape of a hoop or loop, and a barbed portion 4440 of the moveable arm 4430. In this embodiment, a leaflet depth indicator can be a flexible wire 1031 which remains flat in a straight configuration when the clasp is open and when there is no leaflet positioned to against the indicator in the closed clasp. When a leaflet is present, the wire indicator 1031 is pressed through the hoop shaped moveable arm 4430. An optional radiopaque coil 1030 can be wrapped around the indicating wire 1031 and can be seen using imaging equipment, such as fluoroscopy. The indicating wire 1031 and coil 1030 are extend past the periphery or edge on the outer side of the moveable arm 4430 of the clasp 4400 when the clasp is closed on a leaflet that is inserted to a sufficient depth in the clasp. The amount of the indicating arm 1031 and coil 1030 that is exposed past the periphery or outer edge of the moveable arm 4430 indicates the depth of the leaflet to the operator.

[00352] Referring now to Figures 234 and 235, the clasp 4400 is shown in an open position. The moveable arm 4430 is biased or spring-loaded in a closing direction and is moved to and held in the open position by tension applied to actuation lines (not shown). The indicating wire 1031 is in a straight undeflected configuration because there is no leaflet engaged in the open clasp in Figures 234 and 235.

[00353] Referring now to Figure 236, the clasp 4400 is shown in a fully deployed or actuated position, without a leaflet in place. The indicating wire 1031 with optional radiopaque coil

1030 remains undeflected and is positioned on an interior side of the moveable arm 4430. The indicating wire 1031 and coil 1030 are not seen outside of the profile of the moveable arm 4430. The absence of the indicator arm outside of the profile of the clasp by imaging equipment indicates to the operator that a leaflet has not been captured.

[00354] Referring now to Figure 237, the clasp 4400 is shown with the moveable arm 4430 in a closed position. When the clasp 4400 is closed, the moveable arm 4430 and the indicator arm 4450 exert a pinching force that retains the native leaflet tissue to be secured within the clasp 4400. The clasp 4400 is biased in the closed direction by the shape-setting of the moveable arm 4430 in a preloading position. The closed clasp has captured a sufficient amount of leaflet tissue. That is, the depth of the leaflet in the clasp is sufficient for the clasp to be considered properly positioned, as indicated by the indicating wire 1031 and coil 1030 being deflected through the hoop shaped moveable arm 4430, such that a portion of the indicating wire 1031 and/or the coil 1030 move past the outside profile of the moveable arm 4430 of the clasp 4400. The indicating wire 1031 and/or the coil 1030 beyond the profile of the clasp can be seen on imaging equipment, such as fluoroscopy equipment, as represented by Figure 237 to indicate that the valve leaflet has been properly captured by the clasp 4400.

[00355] Figures 238-241 illustrate a variation of the clasp 4400 illustrated by Figures 48-66. In the example illustrated by Figures 238-241, the clasp has a flexible wire indicator 1031 that loops through openings 2380 in the side beams 4432 of the moveable arm 4430 a plurality of times. The flexible wire indicator 1031 is “laced” or strung through the openings 2380. In the illustrated embodiment, the wire indicator 1031 passes across the hoop shape of the moveable arm with portions 1031a on the inside of the clasp and portions 1031b on the outside of the moveable arm 4430. The portions 1031a of the wire indicator curve and extend inward toward the interior of the clasp. In the illustrated example, the portions 1031b on the outside of the moveable arm extend straight or substantially straight across between the side beams 4432 when the clasp is open. However, in some example embodiments the portions 1031b can have the same or substantially the same shape as the portions 1031a. The clasps 4400 can be used in implantable prosthetic devices, such as devices 100, 200, 300 described above or any other implantable prosthetic device.

[00356] The clasp 4400 illustrated by Figures 238-241 has a fixed arm 4410, a patterned flex portion of patterned hinge portion 4420, and a moveable arm 4430 formed in the shape of a hoop or loop. In the illustrated embodiment, the interior curved portions 1031a are curved in a bump configuration and exterior portions 1031b are flat or substantially flat, positioned just

exterior to the moveable arm 4430 when the clasp 4400 is open and when there is no leaflet positioned to overlap the indicator when the clasp is closed. In the illustrated example, there are four inner portions 1031a and three outer portions 1031b. However, there can be any number of inner and outer portions. For example, there can be only one or two of each, or as many as 8-10 of each.

[00357] Referring to Figure 241, when a leaflet is present, the interior curved portions 1031a of the wire indicator 1031 are depressed and push the portions 1031b outward relative to the moveable arm 4430. The number of portions 1031b that are pressed out from the moveable arm 1031b indicate the depth of the leaflet to the operator.

[00358] Referring now to Figures 238 and 239, the clasp 4400 is shown in an open position. The moveable arm 4430 is biased or spring-loaded in a closing direction and are moved to and held in the open position by tension applied to actuation lines (not shown). The indicating wire 1031 is in an undeflected configuration because there is no leaflet engaged in the open clasp in Figures 238 and 239.

[00359] Referring now to Figure 240, the clasp 4400 is shown in a fully deployed or actuated position, without a leaflet in place. The indicating wire 1031 remains undeflected, and the interior portions 1031a remain positioned on an interior side of the fixed arm and the exterior portions 1031b are flush or substantially flush with the moveable arm 4430. The absence of the exterior portions 1031b extending outward from the moveable arm 4430 on imaging equipment indicates that a leaflet has not been captured.

[00360] Referring now to Figure 241, the clasp 4400 is shown with the moveable arm 4430 in a closed position. When the clasp 4400 is closed, the moveable arm 4430 exerts a pinching force that retains the native leaflet tissue within the clasp 4400. The clasp 4400 is biased in the closed direction by the shape-setting of the moveable arm 4430 in a preloading position. The closed clasp has captured a sufficient amount of leaflet tissue. That is, the depth of the leaflet in the clasp is sufficient for the clasp to be considered properly positioned. The indicating wire 1031 is deflected such that the portions 1031b extend outward from the moveable arm 4430. The outwardly extending portions 1031b can be seen using imaging equipment, such as fluoroscopy. That is, the interior portions 1031a are pressed towards the moveable 4430 arm by the pressure applied from the leaflet, thereby causing the exterior portions 1031b to extend further outward from the moveable arm 4430 of the clasp.

[00361] In the embodiments described herein, including but not limited to the embodiments described in Figures 226-241, the indicator can be a coil over a wire; a flexible, super elastic

member with an optional embedded radiopaque marker; protruding members from the clasp body which originate from the flex or hinge region cut from the same continuous sheet as the clasp; and/or a v-shaped radiopaque marker located near the flex or hinge region of the clasp. The indicator can be made of materials that are super-elastic or flexible; i.e., the materials do not undergo plastic deformation upon leaflet capture.

[00362] Referring now to Figure 110, a portion of an example embodiment of a laser cut clasp is illustrated. Similar to the embodiment illustrated in Figure 103, the clasp has a moveable arm 5230, a fixed arm 5210 and one or more flexible segments to permit shaping and bending of the laser cut sheet into a clasp shape. The moveable arm can have a barb 5240 at the end of it. The fixed arm can have three elongate cut-outs, and two flexible bumps 1031 that serve as indicators. Figure 105, described above, is the corresponding schematic view to an embodiment having two flexible bumps 1031 such as that in Figure 110. Thus, Figures 106-109 are also representative of operation of the embodiment illustrated in Figure 110, being positioned and deployed on a native leaflet.

[00363] Referring now to Figures 111-122, illustrate a variation of the clasp 4400 illustrated by Figures 48-66 that has a flexible feature, such as the illustrated bump 1031 that flattens when pressed against leaflet tissue. The clasps 4400 can be used in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. The clasp 4400 has a fixed arm 4410, a patterned flex portion or patterned hinge portion 4420, a moveable arm 4430 formed in the shape of a hoop or loop, and a barbed portion 4440 of the moveable arm 4430. The clasp 4400 also includes an indicator arm 4450 extending from an indicator flex or hinge portion 4460 that joins the indicator arm to the flex or hinge portion 4420. In this embodiment, the indicator arm 4450 can have a flexible feature, that can be a bump 1031 that flattens when pressed against leaflet tissue. The clasp 4400 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein. The clasp 4400 can be laser cut from a flat sheet or a tube of shape-memory alloy, such as Nitinol, and then shape-set into a desired shape.

[00364] The illustrated fixed arm 4410 has two tongue portions 4411 that each include optional holes 4412 for attaching the fixed arm 4410 to an implantable device. A central opening 4454 arranged between the tongue portions 4411 is wider than the indicator arm 4450 so that the indicator arm 4450 can pass through the fixed arm 4410 between the tongue

portions 4411 to form an X-shape when viewed from the side (Figure 106) when the indicator arm 4450 does not engage the leaflet tissue.

[00365] The patterned flex portion or patterned hinge portion 4420 is formed from a plurality of spring segments 4422 and cutouts 4424. The two tongue portions 4411 of the fixed arm 4410 extend from one end of the patterned flex/hinge portion 4420 and the moveable arm 4430 extends from the other end of the flex/hinge portion 4420.

[00366] The moveable arm 4430 of the clasp 4400 has a hoop-like shape. The hoop-shaped moveable arm 4430 includes side beams 4432 that are thinner and more flexible, particularly in the lateral direction. The side beams 4432 include a first flex or hinge portion 4434 arranged toward the proximate end of the moveable arm 4430 and a second flex or hinge portion 4436 arranged at the distal end of the moveable arm 4430. The first flex or hinge portion 4434 is formed by one or more bends in the side beams 4432. The second flex or hinge portion 4436 includes a thinner—and therefore more flexible—portion to reduce the force required to collapse the clasp 4400. The hoop-shape of the moveable arm 4430 and flexible side arms 4432 allow the moveable arm 4430 to be collapsed by merely retracting the clasp 4400 into a delivery sheath (not shown). In certain embodiments, the expansion and contraction of the clasp 4400 is controlled by actuation lines (not shown).

[00367] The hoop-like shape of the moveable arm 4430 provides for a wider barbed portion 4440 that can include more barbs 4442 with the same or greater lateral spacing than other clasps. The wider spacing of the barbs 4442 improves capture of the native leaflets. The barbs 4442 are also longitudinally staggered as a result of their position on the hoop-like shape of the moveable arm 4430. That is, two center barbs 4444 are arranged further away from the flex or hinge portion 4420 and two outer barbs 4446 are arranged closer to the flex or hinge portion 4420. The barbed portion 4440 of the moveable arm 4430 also includes holes 4448 for receiving an actuation suture (not shown). In certain embodiments, the hoop shape of the moveable arm 4430 is similar to the shape of wide outer paddles of an implantable device so that pinching forces of the paddles are spread out evenly on the barbs, further improving the retention of the native leaflets. The ends of the barbs 4442 can be further sharpened using any suitable sharpening means.

[00368] The indicator arm 4450 includes a beam 4451 that extends from the flex or hinge portion 4420 in the interior of the hoop-shaped moveable arm 4430 between the two side arms 4432 to a barbed portion 4456. The indicator arm 4450 includes a hole 4452 at the end for receiving an actuation line (not shown) for actuating the indicator arm 4450. The optional

barbed portion 4456 is arranged at the end of the beam 4451 of the indicator arm 4450 and includes at least one barb 4456 (when the optional barbed portion is included). The optional barbed portion 4456 helps the indicator arm 4450 secure the leaflet until the moveable arm 4430 is closed. The optional barb 4456 can be laser cut from the indicator arm 4450 and bent outwards so that it protrudes away from the indicator arm 4450 at about the same angle as the barbs 4442 protrude from the moveable arm 4430. In some embodiments, the indicator arm 4450 includes barbs that, like the barbs 2244 of the clasp 2200, are cut from a flat sheet of material and then rotated about 90 degrees to protrude outward at an angle.

[00369] The optional barbed portion 4456 of the indicator arm 4450 is arranged at a distance from the flex or hinge portion 4420 such that the barb 4456 of the indicator arm 4450 is longitudinally arranged between the center barbs 4444 and the outer barbs 4446 of the barbed portion 4440. This arrangement ensures that the barbed portion 4440 will engage a leaflet that is engaged by the indicator arm 4450. That is, if a native leaflet positioned within the clasp 4400 is engaged by the barbed portion 4456 of the indicator arm 4450 when the indicator arm 4450 is actuated, then the leaflet will also be engaged by the barbed portion 4440 of the moveable arm 4430.

[00370] In the example embodiment illustrated by Figures 111-122, when a native leaflet is properly positioned and engaged within the clasp, the bump 1031 will be flattened, to indicate proper depth placement of the leaflet. The opposite is also true. That is, if a native leaflet not properly positioned (i.e. not far enough) within the clasp 4400 the bump 1031 will not be flattened when the indicator arm 4450 is actuated. The bump 1031 can be positioned along the indicator arm at a position in the clasp that indicates the distance within the clasp that the native leaflet must extend to be properly positioned. Thus, the example embodiment illustrated by Figures 111-122 provides two indications. First, any engagement of the leaflet with a barb on the indicator arm indicates that the barbs 4444, 4446 will also engage the leaflet (but does not indicate proper insertion depth). Second, compression or flattening of the bump 1031 indicates proper leaflet insertion.

[00371] The indicator flex or hinge portion 4460 allows the indicator arm 4450 to be actuated separately from the moveable arm 4430 to facilitate detection of the depth of engagement of the native leaflet arranged between the moveable arm 4430 and the fixed arm 4410 of the clasp 4400. The indicator flex or hinge portion 4460 can be similar to the patterned flex or hinge portion 4420 and can be formed from a series of spring segments 4462 and cutouts 4464. In some embodiments, the spring force of the indicator flex or hinge portion 4460 is

less than the pinching force imparted to the moveable arm 4430 by the flex or hinge portion 4420 so that the indicator arm 4450 can be actuated many times to detect the position of the leaflet while the moveable arm 4430 with a stronger pinching force is actuated once the leaflet is held in a desirable position by the indicator arm 4450. The lower pinching force of the indicator arm 4450 reduces the force imparted onto the leaflet tissue so that the indicator arm 4450 can be repositioned repeatedly and be less likely to puncture or otherwise damage the leaflet tissue. The lower pinching force can also allow the indicator arm 4450 to pulse or jump as the heart beats.

[00372] Referring now to Figures 111-113, the clasp 4400 is shown in an open position. The moveable arm 4430 and indicator arm 4450 are biased or spring-loaded in a closing direction and are moved to and held in the open position by tension applied to actuation lines (not shown) that can be attached to the holes 4448, 4452 in each of the moveable arm 4430 and indicator arm 4450, respectively. The bump 1031 is in its curved bump configuration because there is no leaflet engaged in the open clasp in Figures 111-113.

[00373] Referring now to Figures 114-116, the clasp 4400 is shown with the indicator arm 4450 in a fully deployed or actuated position, that is, the furthest extent that the indicator arm 4450 is capable of reaching when the indicator arm 4450 does not engage with the leaflet tissue during actuation. The indicator arm 4450 is allowed to actuate in the closing direction when tension on actuation lines (not shown) is decreased. In the fully actuated position, the indicator arm 4450 forms an X-shape with the fixed arm 4410 that is visible via imaging devices so that the operator knows that the indicator arm 4450 has not engaged the leaflet at all. Because no leaflet is engaged in the clasp of Figure 114, the bump 1031 is also in its curved configuration.

[00374] Referring now to Figures 117-119, the clasp 4400 is shown with the indicator arm 4450 in an engaged or closed position. That is, the position that the indicator arm 4450 would be in when the leaflet tissue has been engaged during actuation. The indicator arm 4450 is allowed to actuate in the closing direction when tension on actuation lines (not shown) is decreased. In the closed position, the indicator arm 4450 does not cross the fixed arm 4410 and does not form an X-shape with the fixed arm 4410. In the closed position, the leaflet is only partially inserted into the clasp, and thus the bump 1031 on the indicator arm 4450 is not flattened but retains its curved configuration. Thus, the operator knows that the leaflet tissue has been engaged but is not yet positioned a sufficient distance within the clasp to be considered properly positioned.

[00375] Referring now to Figures 120–122, the clasp 4400 is shown with the moveable arm 4430 and the indicator arm 4450 both in a closed position. When the clasp 4400 is closed, the moveable arm 4430 and the indicator arm 4450 exert a pinching force that retains the native leaflet tissue to be secured within the clasp 4400. The clasp 4400 is biased in the closed direction by the shape-setting of the moveable arm 4430 and the indicator arm 4450 in preloading positions. The closed clasp has captured a sufficient amount of leaflet tissue, that is, the depth of the leaflet in the clasp is sufficient for the clasp to be considered properly positioned, as indicated by the bump 1031 on the indicator arm being flattened. In Figures 120–122, the portion of the indicator arm having the bump 1031 is not visible because the leaflet blocks the view of that portion of the indicator arm and because the bump is flattened by engagement with the leaflet.

[00376] Referring now to Figures 67A–68A, an example embodiment of a laser cut clasp 4400 is illustrated. Figure 67 illustrates a flat view of a portion of a laser cut clasp 4400, having a moveable arm 4430, a fixed arm 4410, and indicator arm 4450. In the example illustrated by Figures 67 and 68, a portion of a paddle 6720 is optionally also formed from the same piece of material as the clasp 4400. However, in some embodiments only the clasp is cut from the piece of material and the paddle portion 6720 is omitted. The moveable arm can have a cut-out section 6730 and barbs 4440 at the free end of the moveable arm, for securing to tissue of a native leaflet. The clasp can have flexible sections where bending of the clasp into a useable shape occurs. The flexible sections can each be a hinged portion, jointed portion, and/or an otherwise flexible portion. There is a flexible or hinged portion 4460 that permits the indicator arm to flex. There are also flex or hinge portions 4420 that permits dynamic flexing of the moveable arm 4430 relative to the fixed arm 4410. An optional flex or hinge portion 4470 allows flexing between the fixed arm 4410 and the optional paddle portion 6720. The clasp can also have optional feet 6710 extending outward from the sides of the clasp near the flexible portion 4420 between the moveable arm and the fixed arm. The feet 6710 can lock into a bushing type collar (not shown) or another connector. The connector can be attached to a spacer that coapts with native mitral valve leaflets. The clasp can be shape set so that its resting configuration has the indicator arm 4450 extending through or toward the opening 6730 of the moveable arm 4430.

[00377] Figure 68 illustrates the clasp 4400 in a partially open configuration. The clasp can be oriented to capture a valve leaflet. When the leaflet is inserted to a predetermined acceptable depth, the leaflet depresses the indicator arm 4450. The depression or flattening of the

indicator arm 4450 indicates that a sufficient amount of the leaflet is disposed in the clasp. Once a sufficient amount of the leaflet is in the clasp, the clasp can be closed to capture the leaflet. In the example illustrated by Figure 68, the indicator arm 4450 extends in the opposite or substantially the opposite direction of the moveable clasp arm 4430. Figure 68 also illustrates an optional suture loop 6810, in which suture or other actuating line(s) pass through and/or connect, to actuate the clasp.

[00378] The indicator arm has a flexible or hinged section 4460 to permit flexing of the clasp. The indicator can pass through the opening 6730 of the moveable arm (see Figure 67) when there is no leaflet captured. When there is a leaflet captured in the clasp, the indicator arm 4450 can sit on top of the leaflet. The length and/or the position of the indicator can be chosen to represent the minimum capture depth required for the device. The optional integral paddle 6720 can be used to approximate the leaflets and/or can be configured to allow elongation of the laser cut paddle. The flex or hinge regions 4420, 4470, and 4460 permit shape setting in a desired shape and/or facilitate relative flexing of the moveable clasp portion, the fixed clasp portion, the indicator arm, and/or the paddle portion 6720.

[00379] Referring now to Figures 67A and 68A, an example embodiment of the clasp similar to that in Figures 67 and 68 is illustrated. Figure 67A illustrates that the indicator arm 4450 is connected to the moveable arm 4430 at a flex or hinge region 4460. The indicator arm flexes toward the interior region of the clasp when there is no leaflet and the clasp is not yet closed, as illustrated in Figure 68A. When the clasp is closed, the indicator arm 4450 can pass through opening 6740 of the fixed arm when there is no leaflet positioned deep enough within the clasp to engage the indicator arm 4450. When a leaflet is positioned sufficiently deep within the clasp so as to engage the indicator arm, the indicator arm can flex at a flexible or hinged region 4460 toward and through opening 6730 of moveable arm 4430.

[00380] Referring now to Figure 69, a portion of an example laser cut clasp 4900 is illustrated. This laser cut clasp has a moveable arm 4930, a barbed portion 4940, and three indicator arms, 4954, 4956, and 4958. A fixed arm of the clasp 4900 is not illustrated in Figure 69. A fixed arm can be included as in other embodiments described herein or the fixed arm can be omitted in any of the embodiments and the moveable arm can extend from and/or be connected to a spacer or a paddle.

[00381] As with the example embodiment described above in Figures 67-68, there is a flexible section of the laser cut sheet to permit shape setting of the moveable arm and/or to form flexible portions or hinge portions 4920, 4960 to permit flexing of the moveable arm and/or

the indicator arms. The multiple indicators in the embodiment illustrated in Figure 69, as well as the moveable arm, are all cut from one sheet. The indicators can be cut from one sheet, which does not require them to be individually attached to the moveable arm.

[00382] Figures 70-71 and 70A-71A schematically illustrate examples of how the moveable arm with indicators of Figure 69 can be used in a clasp 4900. Figures 70-71 and 70A-71A illustrate that indicators having very different physical constructions can operate in the same or substantially the same manner. In the example of Figures 70A and 71A, each of the moveable clasp arm 4930 and the indicators 4952, 4954, 4956, 4958 are elongated and positioned adjacent to one another. In the example of Figures 70 and 71, the moveable clasp arm 4930 is disposed around the indicators and the indicators 4954, 4956, 4958, the indicator 4954 is disposed around the indicators 4956, 4958, and the indicator 4956 is disposed around the indicator 4958. The clasps illustrated by the schematic illustrations of Figures 70-75 can be, but are not required to be, laser cut from a flat sheet.

[00383] Referring now to Figures 70-71, an example clasp 4900 (illustrated as a barbed clasp) for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 4900 includes a fixed arm 4910, a flex or hinge portion 4920, and a moveable arm 4930 having a barbed portion 4940 (though other friction-enhancing portions can be used). The clasp 4900 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00384] The clasp 4900 also includes an indicator portion 4950 formed from first, second, and third indicator arms 4954, 4956, 4958 adjacent to the moveable arm 4930 and each extending from an indicator flex or hinge portion 4960. The indicator flex or hinge portions 4960 allow the indicator arms 4954, 4956, 4958 to be actuated individually and separately from the moveable arm 4930. The indicator flex or hinge portions 4960 can be formed from a portion of the indicator arms 4954, 4956, 4958, can be formed from a series of cutouts and/or the indicator flex or hinge portion 4960 can be part of the flex or hinge portion 4920.

[00385] The indicator arms 4954, 4956, 4958 can be separately actuated from the moveable arm 4930 and optionally from one another to facilitate detection of the depth of engagement of the native leaflet between the moveable arm 4930 and the fixed arm 4910 of the clasp 4900. In some example embodiments, the indicator arms 4954, 4956, 4958 are released from the valve tissue in unison (i.e. release or retraction of one indicator arm releases or retracts all of the indicator arms). In the illustrated embodiment, the indicator arms 4954, 4956, 4958 are

narrower than the moveable arm 4930 and have lengths that are each less than a distance from the flex or hinge portion 4920 to the barbed portion 4940. The first indicator arm 4954 can have a length that is about 75 percent to about 100 percent of the distance between the flex or hinge portion 4920 and the barbed portion 4940. The second indicator arm 4956 can have a length that is about 65 percent to about 95 percent of the distance between the flex or hinge portion 4920 and the barbed portion 4940. The third indicator arm 4958 can have a length that is about 50 percent to about 80 percent of the distance between the flex or hinge portion 4920 and the barbed portion 4940. In some embodiments, the first indicator arm 4954 has a length that is about 60 percent to about 100 percent of the distance between the flex or hinge portion 4920 and the barbed portion 4940. The second indicator arm 4956 has a length that is about 50 percent to about 75 percent of the distance between the flex or hinge portion 4920 and the barbed portion 4940. The third indicator arm 4958 has a length that is about 30 percent to about 60 percent of the distance between the flex or hinge portion 4920 and the barbed portion 4940. Any combination of the lengths of indicator arms can be used, as long as the length continues to decrease with each successive indicator arm, to provide indication of the depth the leaflet is positioned within the clasp. There can also be a fourth indicator arm (not shown). Any number of different indicator arms can be included.

[00386] The different lengths of the indicator arms 4954, 4956, 4958 are used to determine a desired minimum engagement depth as measured from the end of the moveable arm 4930 of the clasp 4900. Configuring the length of the first indicator arm 4954 to be less than a distance from the flex or hinge portion 4920 to the barbed portion 4940 ensures that the barbed portion 4940 will engage a leaflet that is positioned at the minimum engagement depth as indicated by the first indicator arm 4954. That is, if a native leaflet positioned within the clasp 4900 is engaged by the first indicator arm 4954 when the first indicator arm 4954 is actuated, then the leaflet will be engaged by the barbed portion 4940 of the moveable arm 4930. The opposite is also true. That is, if a native leaflet positioned within the clasp 4900 is not engaged by the first indicator arm 4954 when the first indicator arm is actuated, then the leaflet will not be adequately engaged by the barbed portion 4940 of the moveable arm 4930.

[00387] The second and third indicator arms 4956, 4958 are configured with decreasing lengths so that the surgeon to determine how far beyond the minimum engagement depth the native leaflet has been inserted into the clasp 4900. That is, whether or not the native leaflet is engaged by the second and third indicator arms 4956, 4958 indicates that the native leaflet has or has not reached the engagement depth measured by each of the second and third

indicator arms 4956, 4958. For example, if a native leaflet positioned within the clasp 4900 is engaged by the third indicator arm 4958 when the third indicator arm 4958 is actuated, then the leaflet has been inserted about 50 percent to about 80 percent of the distance from the barbed portion 4940 to the flex or hinge portion 4920, for example. The opposite is also true. That is, if a native leaflet positioned within the clasp 4900 is not engaged by the third indicator arm 4958 when the third indicator arm 4958 is actuated, then the leaflet has not reached about 50 percent of the distance between the barbed portion 4940 and the flex or hinge portion 4920.

[00388] Referring now to Figures 70A–71A, an example clasp 4900 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. The barbed clasp 4900 includes a fixed arm 4910, a hinge portion 4920, and a moveable arm 4930. Moveable arm 4930 can include a barbed portion 4940 and/or some other friction-enhancing portion(s). The clasp 4900 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the clasps or barbed clasps described herein.

[00389] The clasp 4900 also includes an indicator portion 4950 formed from first, second, third, and fourth indicator arms 4952, 4954, 4956, 4958 adjacent to the moveable arm 4930 and each extending from an indicator hinge portion 4960. The indicator hinge portions 4960 allow the indicator arms 4952, 4954, 4956, 4958 to be actuated individually and separately from the moveable arm 4930. The indicator hinge portions 4960 can be formed from a portion of the indicator arms 4952, 4954, 4956, 4958 or can be formed from a series of cutouts similar to the patterned hinge of the clasp 2100 described above.

[00390] The indicator arms 4952, 4954, 4956, 4958 can be separately actuated from the moveable arm 4930 to facilitate detection of the depth of engagement of the native leaflet between the moveable arm 4930 and the fixed arm 4910 of the clasp 4900. In the illustrated embodiment, the indicator arms 4952, 4954, 4956, 4958 are narrower than the moveable arm 4930 and have lengths that are each less than a distance from the hinge portion 4920 to the barbed portion 4940. In some embodiments, the first indicator arm 4952 has a length that is about 75 percent to about 100 percent of the length of a distance between the hinge portion 4920 and a barbed portion 4940. In some embodiments, the second indicator arm 4954 has a length that is about 65 percent to about 95 percent of the length of a distance between the hinge portion 4920 and the barbed portion 4940. In some embodiments, the third indicator arm 4956 has a length that is about 50 percent to about 80 percent of the length of a distance

between the hinge portion 4920 and the barbed portion 4940. In some embodiments, the fourth indicator arm 4958 has a length that is about 35 percent to about 65 percent of the length of a distance between the hinge portion 4920 and the barbed portion 4940.

[00391] The different lengths of the indicator arms 4952, 4954, 4956, 4958 are used to determine a desired minimum engagement depth as measured from the end of the moveable arm 4930 of the clasp 4900. In some embodiments, configuring the length of the first indicator arm 4952 to be less than a distance from the hinge portion 4920 to the barbed portion 4940 ensures that the barbed portion 4940 will engage a leaflet that is positioned at the minimum engagement depth as indicated by the first indicator arm 4952. That is, if a native leaflet positioned within the clasp 4900 is engaged by the first indicator arm 4952 when the first indicator arm 4952 is actuated, then the leaflet will be engaged by the barbed portion 4940 of the moveable arm 4930. The opposite is also true. That is, if a native leaflet positioned within the clasp 4900 is not engaged by the first indicator arm 4952 when the first indicator arm 4952 is actuated, then the leaflet will not be adequately engaged by the barbed portion 4940 of the moveable arm 4930.

[00392] The second, third, and fourth indicator arms 4954, 4956, 4958 are configured with decreasing lengths so that the surgeon to determine how far beyond the minimum engagement depth the native leaflet has been inserted into the clasp 4900. That is, whether or not the native leaflet is engaged by the second, third, and fourth indicator arms 4954, 4956, 4958 indicates that the native leaflet has or has not reached the engagement depth measured by each of the second, third, and fourth indicator arms 4954, 4956, 4958. For example, in some embodiments, if a native leaflet positioned within the clasp 4900 is engaged by the third indicator arm 4956 when the third indicator arm 4956 is actuated, then the leaflet has been inserted about 50 percent to about 80 percent of the distance from the barbed portion 4940 to the hinge portion 4920. The opposite is also true. That is, if a native leaflet positioned within the clasp 4900 is not engaged by the third indicator arm 4956 when the third indicator arm 4956 is actuated, then the leaflet has not reached about 50 percent of the distance between the barbed portion 4940 and the hinge portion 4920.

[00393] Figures 72-74 illustrate schematically illustrate the clasp 4900 of Figures 70-71 (or 70A-71A) being deployed to secure a native leaflet of a native valve (e.g., a native mitral valve, etc.). The example clasp 4900 is shown being deployed within the native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 72, the clasp 4900 is shown in an

open condition with a native leaflet 42, 44 partially inserted into an opening 4906 of the clasp 4900 formed between the fixed and moveable arms 4910, 4930. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the indicator arms 4954, 4956, 4958 are actuated, either individually or all at once, by one or more actuation lines (not shown in Figures 72-75) as shown in Figures 73 and 75.

[00394] Referring now to Figure 73, the indicator arms 4954, 4956, 4958 are shown in an actuated or released condition. Because the leaflet 42, 44 is inserted into the opening 4906 of the clasp 4900 about half way between the barbed portion 4940 and the flex or hinged portion 4920, the first indicator arm 4954 engages the leaflet while the second and third indicator arms 4956, 4958 miss or slip off of the leaflet 42, 44 to move to fully actuated positions at or beyond the fixed arm 4910. In the illustrated example, the second and third indicator arms 4956, 4958 form X or crossing shapes with the fixed arm that are visible via imaging devices used to monitor implantation and deployment of the prosthetic device. In an example embodiment, the second and third indicator arms would engage the fixed arm or a covering on the fixed arm, so that there would not be a crossing or X shape, but the lack of space between the indicator arms and the fixed arms would still indicate the lack of leaflet tissue. In addition, or instead, the indicator arms 4954, 4956 that engage the valve leaflet bounce or pulse as the heart beats, while the arm 4958 does not. This bouncing or pulsing can be seen on imaging. Thus, the depth of engagement can be determined from the relative positions of the indicator arms 4954, 4956, 4958 with respect to the fixed arm 4910 and/or the number of indicator arms that bounce or pulse versus the number that do not.

[00395] Referring now to Figure 74, the indicator arms 4954, 4956, 4958 are retracted by applying tension to the actuation line(s) and the clasp 4900 is repositioned so that the leaflet 42, 44 is more deeply inserted into the opening 4906 of the clasp 4900. However, in some cases engagement by only some of the indicator arms can indicate correct leaflet positioning. The indicator arms 4954, 4956, 4958 are then actuated by releasing tension on the actuating lines, as can be seen in Figure 75. Because the leaflet 42, 44 has been inserted into the clasp 4900 at or beyond the minimum desired engagement depth of the third indicator arm 4958, all three of the indicator arms 4954, 4956, 4958 engage and pinch the leaflet 42, 44 against the fixed arm 4910. Engagement with the leaflet 42, 44 prevents the indicator arms 4954, 4956, 4958 from moving to or past the fixed arm 4910 of the clasp 4900 to form the X-shapes shown in Figure 73 (or another shape indicating the lack of the presence of valve leaflet tissue). Thus, the indicator arms 4954, 4956, 4958 indicate to an observer observing the

installation via an imaging device that the leaflet 42, 44 is inserted into the opening 4906 beyond at least the depth established by the third indicator arm 4958.

[00396] Referring now to Figure 75, once the indicator arms 4954, 4956, 4958 indicate that the leaflet 42, 44 is sufficiently inserted into the opening 4906, the moveable arm 4930 is actuated by releasing tension on the actuating line (not shown) so that the leaflet 42, 44 is pinched between the barbed portion 4940 and the fixed arm 4910 to secure the leaflet 42, 44 firmly within the clasp 4900.

[00397] Referring now to Figures 76-77, the moveable arm 4930 and indicator arms 4954, 4956, and 4958 of a laser cut embodiment of a clasp 4900 are illustrated. The embodiments illustrated in Figures 76-77 are similar to that described above with respect to Figure 69, having a moveable arm 4930 with a cut-out opening 6730, and multiple indicator arms 4954, 4956, 4958 all cut from the same sheet, where the moveable arm and each of the indicator arms have a flexible section 4960 to permit bending and/or flexing relative to the fixed arm and/or to allow shape-setting of the unflexed position of the clasp. In these embodiments, the multiple indicators assist with identifying the depth of the leaflet.

[00398] The embodiments in Figures 76-77 further include a bar 7610 on the shortest indicator arm 4958 that forms the shape of a “T” with the shortest indicator arm 4958, referred to herein as a T-bar. The T-bar can allow the multiple indicators and optionally the movable clasp arm 4930 to be lifted together (i.e. opened relative to the fixed arm). The T-bar can be attached to the indicator arm 4958 by welding, attachment with a rivet, or other known means for attachment. In Figure 76, the T-bar extends all the way to the outermost layer of the moveable arm 4930, which can be a moveable arm with optional barbs (barbs not shown) that is closed after the leaflet is properly positioned within the clasp.

[00399] In Figure 77, an example embodiment is illustrated in which the T-bar 7610 extends outward to the outermost indicator arm 4954 but is positioned inside of the moveable. The indicator arms here increase in length as they move outward from the centrally located indicator arm 4958, being centrally located along the width of the moveable arm frame. The indicator arms 4956, 4958 having a longer length than the centrally located indicator arm can be “U” shaped or other shape where the indicator arm has sides 7620 and a distal end 7630.

[00400] The indicator arms can be pulled up or opened by the T-bar with a suture line attached to the T-bar or by another actuator means. The moveable arm can be pulled up or opened by another suture line or other actuator means. Similar to other embodiments having a suture line described herein, the suture line connected to the T-bar or the shortest indicator arm is

given slack prior to the suture line connected to the moveable arm. This slack allows the shortest indicator arm to fall towards the fixed arm (or leaflet if a leaflet is positioned within the clasp). The falling of the shortest indicator arm, and thus T-bar, permits the remaining indicator arms and optionally the moveable arm 4930 to fall towards the fixed arm as well. If the leaflet is partially captured, some of the indicator arms, but not those overlapping with the leaflet, will still fall past the leaflet. Figures 80-83 illustrate the falling of the indicator arms based on the position of the leaflet and are described below.

[00401] Referring now to Figures 78-79, an example clasp 4900 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 4900 includes a fixed arm 4910, a flex or hinge portion 4920, and a moveable arm 4930. As with Figures 76 and 77, the shortest indicator arm 4958 has a T-bar connected to it, to lift all the indicator arms together at the same time when positioning the clasp. The clasp 4900 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the clasps described herein. Although the example illustrated by Figures 78 and 79 does not illustrate barbs on the moveable arm 4930, the moveable arm can have one or more barbs in this or any other embodiment disclosed herein (see for example, barb 3540 in Figures 24-29).

[00402] The clasp 4900 also includes an indicator portion 4950 formed from first, second, and third indicator arms 4954, 4956, 4958 adjacent to the moveable arm 4930 and each extending from an indicator flex or hinge portion 4960. The indicator flex or hinge portions 4960 allow the indicator arms 4954, 4956, 4958 to be actuated individually and separately from the moveable arm 4930. The indicator flex or hinge portions 4960 can be formed from a portion of the indicator arms 4954, 4956, 4958, can be formed from a series of cutouts, and/or can be a portion of the flex or hinge portion 4920. The T-bar can be connected by welding, or using a rivet, or other known means. The T-bar can be made of the same material as the indicator arms. The T-bar is used to lift the indicator arms together. As explained below, during deployment of the clasp on a native leaflet, the indicator arms that fall to or beyond the fixed arm of the clasp indicate that the leaflet is not positioned within the clasp to the depth indicated by that particular indicator arm. The T-bar does not affect the functioning of the indicator arms, which operate, as explained below, similarly to the example embodiment described in Figures 70-75.

[00403] The indicator arms 4954, 4956, 4958 can be separately actuated from the moveable arm 4930 to facilitate detection of the depth of engagement of the native leaflet between the

moveable arm 4930 and the fixed arm 4910 of the clasp 4900. In the illustrated embodiment, the indicator arms 4954, 4956, 4958 are narrower than the moveable arm 4930 and have lengths that are each less than a distance from the flex or hinge portion 4920 to the barbed portion 4940. The first indicator arm 4954 has a length that is about 75 percent to about 100 percent of the distance between the flex or hinge portion 4920 and the barbed portion 4940. The second indicator arm 4956 has a length that is about 65 percent to about 85 percent of the length between the flex or hinge portion 4920 and the barbed portion 4940. The third indicator arm 4958 has a length that is about 50 percent to about 70 percent of the distance between the flex or hinge portion 4920 and the barbed portion 4940. Any combination of the lengths of indicator arms can be used, as long as the length continues to decrease with each successive indicator arm, to provide indication of the depth the leaflet is positioned within the clasp. There can also be a fourth indicator arm (not shown) or any number of indicator arms.

[00404] The different lengths of the indicator arms 4954, 4956, 4958 are used to determine a desired minimum engagement depth as measured from the end of the moveable arm 4930 of the clasp 4900. Configuring the length of the first indicator arm 4954 to be less than a distance from the flex or hinge portion 4920 to the barbed portion 4940 ensures that the barbed portion 4940 will engage a leaflet that is positioned at the minimum engagement depth as indicated by the first indicator arm 4954. That is, if a native leaflet positioned within the clasp 4900 is engaged by the first indicator arm 4954 when the first indicator arm is actuated, then the leaflet will be engaged by the barbed portion 4940 of the moveable arm 4930. The opposite is also true. That is, if a native leaflet positioned within the clasp 4900 is not engaged by the first indicator arm 4954 when the first indicator arm is actuated, then the leaflet will not be adequately engaged by the barbed portion 4940 of the moveable arm 4930.

[00405] The first, second, and third indicator arms 4954, 4956, 4958 are configured with decreasing lengths so that the surgeon can determine how far beyond the minimum engagement depth the native leaflet has been inserted into the clasp 4900. That is, whether or not the native leaflet is engaged by the second and third indicator arms 4956, 4958 indicates that the native leaflet has or has not reached the engagement depth measured by each of the first, second, and third indicator arms 4954, 4956, 4958. For example, if a native leaflet positioned within the clasp 4900 is engaged by the third indicator arm 4958 when the third indicator arm 4958 is actuated, then the leaflet has been inserted about 50 percent to about 80 percent of the distance from the barbed portion 4940 to the flex or hinge portion 4920. The opposite is also true. That is, if a native leaflet positioned within the clasp 4900 is not

engaged by the third indicator arm 4958 when the third indicator arm 4958 is actuated, then the leaflet has not reached about 50 percent of the distance between the barbed portion 4940 and the flex or hinge portion 4920.

[00406] Referring now to Figures 80-83, the example clasp 4900 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 80, the clasp 4900 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening 4906 of the clasp 4900 formed between the fixed and moveable arms 4910, 4930. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the indicator arms 4954, 4956, 4958 are individually actuated via a plurality of actuation lines (not shown) as shown in Figures 81 and 83. Or, a single actuation line can be connected to the indicator arm 4958 with the T-bar 7610, such that pulling on the single line opens all of the indicator arms 4954, 4956, 4958 with the T-bar 7610 and releasing the single line allows all of the indicator arms 4954, 4956, 4958 to fall or close.

[00407] Referring now to Figure 81, the indicator arms 4954, 4956, 4958 are shown in a released condition. Because the leaflet 42, 44 is inserted into the opening 4906 of the clasp 4900 about half way between the barbed portion 4940 and the flexible or hinged portion 4920, the first indicator arm 4954 engages the leaflet while the second and third indicator arms 4956, 4958 miss or slip off of the leaflet 42, 44 to move to fully actuated positions at or beyond the fixed arm 4910. The second and third indicator arms 4956, 4958 forms a shape with the fixed arm that is visible via imaging devices used to monitor implantation and deployment of the prosthetic device. In addition, or instead, the indicator arm 4954 that engages the valve leaflet bounce or pulse as the heart beats, while the arms 4956, 4958 do not. This bouncing or pulsing can be seen on imaging. Thus, the depth of engagement can be determined from the number of visible shapes formed by the indicator arms 4954, 4956, 4958 and the fixed arm 4910 and/or the number of indicator arms that bounce or pulse versus the number that do not.

[00408] Referring now to Figure 82, the indicator arms 4954, 4956, 4958 are retracted by applying tension to an actuation lines that is connected to the indicator arm 4958 with the T-bar 7610 and the clasp 4900 is repositioned so that the leaflet 42, 44 is more deeply inserted into the opening 4906 of the clasp 4900. (In the illustration, space is shown between the indicator arms 4958, 4956, 4954 so that they are visible in the drawing. However, in reality, the indicator arms 4956, 4954 rest on the T-bar 7610 and there is no space.) However, in

some cases engagement by only some of the indicator arms can indicate correct leaflet positioning. The indicator arms 4954, 4956, 4958 are then actuated by releasing tension on the actuating line (not shown) that is attached to the indicator arm 4958 or T-bar 7610, as can be seen in Figure 83. Because the leaflet 42, 44 has been inserted into the clasp 4900 at or beyond the minimum desired engagement depth of the third indicator arm 4958, all three of the indicator arms 4954, 4956, 4958 engage and pinch the leaflet 42, 44 against the fixed arm 4910. Engagement with the leaflet 42, 44 prevents the indicator arms, 4954, 4956, 4958 from moving past the fixed arm 4910 of the clasp 4900 to form the shapes shown in Figure 81. Thus, the indicator arms 4954, 4956, 4958 indicate to an observer observing the installation via an imaging device that the leaflet 42, 44 is inserted into the opening 4906 beyond at least the depth established by the third indicator arm 4958.

[00409] Referring now to Figure 83, once the indicator arms 4954, 4956, 4958 indicate that the leaflet 42, 44 is sufficiently inserted into the opening 4906, the moveable arm 4930 is actuated by releasing tension on the actuating line (not shown) so that the leaflet 42, 44 is pinched between the moveable arm 4930 and the fixed arm 4910 to secure the leaflet 42, 44 firmly within the clasp 4900.

[00410] Referring now to Figures 123 and 124, an example clasp 5000 (illustrated as a barbed clasp) for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 5000 includes a fixed arm 5010, a flex or hinge portion 5020, and a moveable arm 5030 having a barbed portion 5040 (though other friction-enhancing portions can be used). The moveable arm 5030 also includes an optional first indicating lever 1241 disposed at a distance from the flex portion or hinge that is greater than the distance of the barb 5040. The moveable arm 5030 also includes a second indicating lever 1242 disposed at a distance from the flex or hinge portion 5020 that is less than a distance between the barbed portion 5040 and the flex or hinge portion 5020. The indicating levers 1241, 1242 deform when the native leaflet tissue is pressed against the fixed arm 5010 by the moveable arm 5030 to indicate the engagement depth that the leaflet tissue has reached. The first indicating lever 1241 deforms when the native leaflet is partially inserted into the clasp. The second indicating lever 1242 deforms when the native leaflet has reached the minimum desired engagement depth. The clasp is not limited to two indicating levers but can have additional indicating levers, placed between the first and second indicating lever (as described in U.S. App. Serial No. 62/805847, filed on February 14, 2019, incorporated herein by reference in its entirety, and described below with reference to Figures

123A-127A). Thus, the second indicating lever 1242 will not indicate that the native leaflet 42, 44 has reached the desired engagement depth until the leaflet 42, 44 is inserted at or beyond the location of the second indicating lever 1242. Once the leaflet 42, 44 has reached the desired engagement depth, actuation of the moveable arm 5030 squeezes the leaflet tissue 42, 44 against the indicating lever 1242 to cause the indicating lever 1242 to flatten or flex against the valve leaflet and thereby indicate that the leaflet 42, 44 has been inserted into the clasp 5000 at or beyond the desired engagement depth. The clasp 5000 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00411] Referring now to Figures 125, 126, and 127, the example clasp 5000 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 125, the clasp 5000 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening of the clasp 5000 formed between the fixed and moveable arms 5010, 5030. With the clasp in the open condition, neither of the indicator levers, 1241, 1242 are flexed or flattened. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the moveable arm 5030 is actuated via actuation lines (not shown) as shown in Figures 126-127.

[00412] Referring now to Figure 126, when the moveable arm 5030 is actuated to push the leaflet 42, 44 against the fixed arm 5010, the leaflet 42, 44 may contact a portion of the moveable arm 5030, contacting only the first indicator lever 1241 but not the second indicating lever 1242 when the engagement depth of the leaflet 42, 44 is less than the minimum desired engagement depth. As can be seen in Figure 126, the first indicating lever 1241 is flexed out of the way of the moveable arm due to contact with the leaflet 42, 44 when the leaflet 42, 44 is partially inserted into the clasp 5000 and is pressed against the first indicating lever 1241 by the fixed arm 5010. That is, the first indicating lever 1241 is deformed by the leaflet 42, 44 to indicate that the leaflet 42, 44 has been partially inserted into the clasp. In some embodiments, actuation of the moveable arm 5030 also causes the barbed portion 5040 to engage and secure the leaflet 42, 44 within the barbed clasp 5000. Because the second indicating lever 1242 has not been flexed and/or flattened, this indicates to the operator that the leaflet has not been inserted into the clasp at or beyond a minimum engagement depth. If the indicating lever 1242 indicates that the leaflet 42, 44 is not inserted

to the desired depth, the clasp 5000 can be opened to allow for repositioning of the leaflet 42, 44.

[00413] Referring now to Figure 127, when the moveable arm 5030 is actuated to push the leaflet 42, 44 against the fixed arm 5010, the leaflet 42, 44 may contact a portion of the moveable arm 5030, contacting the first indicator lever 1241 and the second indicating lever 1242 when the engagement depth of the leaflet 42, 44 is greater than or equal to the minimum desired engagement depth. As can be seen in Figure 127, the first indicating lever 1241 and second indicating lever 1242 are both flexed out of the way of the moveable arm due to contact with the leaflet 42, 44 when the leaflet 42, 44 is inserted into the clasp 5000 at or beyond the minimum engagement depth and is pressed against both the first indicating lever 1241 and the second indicating lever 1242 by the fixed arm 5010. That is, the first indicating lever 1241 and the second indicating lever 1242 are each deformed by the leaflet 42, 44 to indicate that the leaflet 42, 44 has been inserted into the clasp at or beyond the minimum engagement depth. In some embodiments, actuation of the moveable arm 5030 also causes the barbed portion 5040 to engage and secure the leaflet 42, 44 within the barbed clasp 5200. The indicating lever 1241 is optional, and in some example embodiments, there is no indicating lever 1241 positioned above the barb 5040.

[00414] Referring now to Figures 123A-127A, an example clasp 5000 (illustrated as a barbed clasp) such as that shown in Figures 123-127, with a plurality of flexible indicating levers 1242, is illustrated. Referring to Figures 123A and 124A, an example clasp 5000 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown on any other implantable prosthetic device. Like the clasp 3500 described above, the clasp 5000 includes a fixed arm 5010, a flex or hinge portion 5020, and a moveable arm 5030 having a barbed portion 5040 (though other friction-enhancing portions can be used). The moveable arm 5030 also includes an optional first indicating lever 1241 disposed at a distance from the flexible portion or hinge that is greater than the distance of the barb 5040. The moveable arm 5030 also includes a plurality of additional indicating levers 1242 disposed at distances from the flex or hinge portion 5020 that are less than a distance between the barbed portion 5040 and the flex or hinge portion 5020. The indicating levers 1241, 1242 deform when the native leaflet tissue is pressed against the fixed arm 5010 by the moveable arm 5030 to indicate the engagement depth that the leaflet tissue has reached. The first indicating lever 1241 deforms when the native leaflet is partially inserted into the clasp. Each of the plurality of indicating

levers 1242 deform when the native leaflet has reached the engagement depth at which each indicating lever 1242 is positioned.

[00415] Once the leaflet 42, 44 has reached the desired engagement depth, actuation of the moveable arm 5030 squeezes the leaflet tissue 42, 44 against at least one indicating lever 1242 to cause the indicating lever 1242 to flatten or flex against the valve leaflet and thereby indicate that the leaflet 42, 44 has been inserted into the clasp 5000 at or beyond the desired engagement depth. The indicating levers 1242 can also be used to indicate whether the leaflet 42, 44 has been inserted too far into the clasp. For example, if the leaflet deforms the indicating lever 1242 closest to the flex or hinge portion 5020, this can indicate to the operator that the leaflet has been inserted too far into the clasp.

[00416] Referring now to Figures 125A, 126A, and 127A, the example clasp 5000 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 125A, the clasp 5000 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening of the clasp 5000 formed between the fixed and moveable arms 5010, 5030. With the clasp in the open condition, none of the indicator levers, 1241, 1242 are flexed or flattened. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the moveable arm 5030 is actuated as shown in Figures 126A and 127A.

[00417] Referring now to Figure 126A, when the moveable arm 5030 is actuated to push the leaflet 42, 44 against the fixed arm 5010, the leaflet 42, 44 may contact a portion of the moveable arm 5030, contacting only the first indicator lever 1241 but none of the plurality of indicating levers 1242 when the engagement depth of the leaflet 42, 44 is less than the minimum desired engagement depth. As can be seen in Figure 126A, the first indicating lever 1241 is flexed out of the way of the moveable arm due to contact with the leaflet 42, 44 when the leaflet 42, 44 is partially inserted into the clasp 5000 and is pressed against the first indicating lever 1241 by the fixed arm 5010. That is, the first indicating lever 1241 is deformed by the leaflet 42, 44 to indicate that the leaflet 42, 44 has been partially inserted into the clasp. In some embodiments, actuation of the moveable arm 5030 also causes the barbed portion 5040 to engage and secure the leaflet 42, 44 within the barbed clasp 5000. All of the indicating levers 1242 not being flexed and/or flattened indicates to the operator that the leaflet has not been inserted into the clasp at or beyond a minimum engagement depth. If the indicating levers 1242 indicate that the leaflet 42, 44 is not inserted to the desired depth, the clasp 5000 can be reopened to allow for repositioning of the leaflet 42, 44.

[00418] Referring now to Figure 127A, when the moveable arm 5030 is actuated to push the leaflet 42, 44 against the fixed arm 5010. In Figure 127A, the leaflet 42, 44 contacts the first indicator lever 1241 and the two indicating levers 1242. This indicates that the depth of the leaflet 42, 44 is greater than or equal to the minimum desired engagement depth. In Figure 127A, the two indicating levers 1242 closest to the flex or hinge region 5020 are not deformed, which can indicate to the operator that the leaflet is not inserted too far into the clasp. If the leaflet is inserted too far into the clasp, the clasp can be re-opened, and the leaflet can be repositioned. In some embodiments, actuation of the moveable arm 5030 also causes the barbed portion 5040 to engage and secure the leaflet 42, 44 within the barbed clasp 5200. The indicating lever 1241 is optional, and in some example embodiments, there is no indicating lever 1241 positioned above the barb 5040.

[00419] Referring now to Figures 128-129, an example clasp 5200 (illustrated as a barbed clasp) for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 5200 includes a fixed arm 5210, a flex or hinge portion 5220, and a moveable arm 5230 having a barbed portion 5240 (though other friction-enhancing portions can be used). The fixed arm 5210 also includes an indicating spring 5212 disposed at a distance from the flex or hinge portion that is less than a distance between the barbed portion 5240 and the flex or hinge portion 5220. In an example embodiment, the movable arm 5230 also includes an indicating spring 5212 disposed at a distance from the flex or hinge portion that is less than a distance between the barbed portion 5240 and the flex or hinge portion 5220. The indicating spring is schematically illustrated and can take a wide variety of different forms. For example, the indicating spring can be any resiliently deformable component. The indicating spring 5212 can include closed ends and/or can be covered with cloth or other material to prohibit damage to the leaflet tissue. The indicating spring 5212 deforms when the native leaflet tissue is pressed against the indicating spring 5212 by the moveable arm 5230 to indicate that the leaflet tissue has reached a minimum desired engagement depth. Thus, the indicating spring 5212 will not indicate that the native leaflet 42, 44 has reached the desired engagement depth until the leaflet 42, 44 is inserted at or beyond the location of the indicating spring 5212. Once the leaflet 42, 44 has reached the desired engagement depth, actuation of the moveable arm 5230 squeezes the leaflet tissue 42, 44 against the indicating spring 5212 of the fixed arm 5210 to cause the indicating spring 5212 to flatten and thereby indicate that the leaflet 42, 44 has been inserted into the clasp 5200 at or beyond the desired engagement depth. The clasp 5200 can be used in

any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00420] Referring now to Figures 130-132, the example clasp 5200 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 130, the clasp 5200 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening 5206 of the clasp 5200 formed between the fixed and moveable arms 5210, 5230. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the moveable arm 5230 is actuated via actuation lines (not shown) as shown in Figures 131-132.

[00421] Referring now to Figure 131, when the moveable arm 5230 is actuated to push the leaflet 42, 44 against the fixed arm 5210, the leaflet 42, 44 may contact a portion of the fixed arm 5210 without contacting the indicating spring 5212 when the engagement depth of the leaflet 42, 44 is less than the minimum desired engagement depth. As can be seen in Figure 132, the indicating spring 5212 is deformed or flattened from contact with the leaflet 42, 44 when the leaflet 42, 44 is inserted into the clasp 5200 at or beyond the minimum engagement depth and is pressed against the indicating spring 5212 by the moveable arm 5230. That is, the indicating spring 5212 is deformed by the leaflet 42, 44 to indicate that the leaflet 42, 44 has been inserted at or beyond the minimum engagement depth. In some embodiments, actuation of the moveable arm 5230 also causes the barbed portion 5240 to engage and secure the leaflet 42, 44 within the barbed clasp 5200. If the indicating spring 5212 indicates that the leaflet 42, 44 is not inserted to the desired depth, the clasp 5200 can be opened to allow for repositioning of the leaflet 42, 44.

[00422] Referring now to Figures 129B-129C, additional views and configurations of the clasp 5200 and indicator spring 5212 are illustrated. Figure 129B illustrated the indicator spring 5212 is attached to the fixed arm 5210. The spring 5212 can be depressed by a force as indicated by arrow 5214. The arrow 5214 represents the force of a leaflet 42, 44 pressed against the spring. The rings of the indicator spring 2512 stack on top of each other in the example embodiment of Figure 129B, because they are all the same or approximately the same size. Figure 129C illustrates a top view of the indicator spring 5212.

[00423] Referring now to Figures 129D-129F, an example clasp 5200 having a conical indicator spring 5213 is illustrated. Figure 129D illustrates a clasp 5200 in an open configuration having a conical indicator spring 5213 attached to the fixed arm 5210. In some

example embodiments, the conical indicator spring 5213 can be attached to the moveable arm 5230. Figure 129E illustrates the conical indicator spring 5213 in a compressed configuration. Arrow 5214 represents the force of a leaflet pressed against the spring. The outermost, widest diameter ring of the conical indicator spring 5213 is visible. The rest of the rings, in which the diameter decreases with each successive ring to form the conical shape, nest within each other, to form the concentric circles seen in the top-down view of the spring 5213 in Figure 129F. As a result, the spring 5212 is flat or substantially flat. In Figures 129D-129F, the conical indicator spring 5213 is positioned on the fixed arm 5230, but in some example embodiments, it can be fixed on the moveable arm.

[00424] Referring now to Figures 129G-129H, example embodiments of clasps having a supplemental indicator element 513 on a conical indicator spring 5213 are illustrated. Referring to Figure 129G and 129H, an indicator element 5215, or 5215 can be attached to the conical indicator spring 5213 at the free end of the spring 5213. When in a resting configuration as shown in Figure 129G, the indicator element 5215 extends downward from the free end of the spring 5213 towards the fixed arm 5210. When in a compressed configuration, as shown in Figure 129H, due to forces as indicated by arrow 5214, the spring 5213 flattens and indicating element 5215 extends through an opening 1291 in the fixed arm, so that the indicator element 5215 is visible on the exterior side of the fixed arm 5210.

[00425] Referring now to Figures 129I and 129J, example embodiments of the indicator element 5215 are illustrated. In Figure 129I, the indicator element 5215a is a conical spring or a conical spring portion having its greatest diameter coil attached to the free end of the conical indicator spring 5213 and its smallest diameter coil positioned closest to the fixed arm 5210. In one example embodiment, the spring 5213 and the conical spring indicator element 5213a are formed from a single piece of material, such as a single piece of wire. In the example illustrated by Figure 129J the indicator element 5213b is a piece of material that is secured to the free end of the conical indicator spring. The indicator element 5213b can take a wide variety of different forms. The indicator element 5213b can be a U-shaped, cup-shaped, or rod-shaped piece of radiopaque material that is secured to the free end of the conical indicator spring. In the illustrated example, the bottom curve of the “U” extends downward toward the fixed arm and the free ends of the “U” are attached to the conical indicator spring 5213. In some example embodiments, the indicator elements 5215 can be attached to a spring indicator having coils of the same diameter, and/or the spring indicator 5213 can be attached to the moveable arm. The indicating elements 5215 can be wrapped in

a radiopaque material, made of a radiopaque material, covered in a radiopaque fabric sheath and/or printed with radiopaque ink.

[00426] Referring now to Figures 128A, 129A, 130A, 131A, and 132A, an example clasp is shown, having similar features to the clasp illustrated in Figures 128-132. In Figures 128-132A, the clasp 5200 and indicating spring 5212 operate the same way as in the embodiment illustrated in Figures 128-132, with one difference. In Figures 128A, 129A, 130A, 131A, and 132A, the indicating spring 5213 is positioned on the moveable arm 5230.

[00427] Referring now to Figures 133-134, an example clasp 5200 having an indicator on the fixed arm is shown. The clasp can be used in implantable prosthetic devices, such as devices 100, 200, 300 described above. The clasp 5200 includes a fixed arm 5210, a flex or hinge portion 5220, and a moveable arm 5230 having a barbed portion 5240 (though other friction-enhancing portions can be used). The fixed arm 5210 also includes an indicating spring 5212 disposed at a distance between the flex or hinge 5220 portion and the barbed portion 5240. The indicating spring 5212 pictured in Figures 133-134 is one having coils aligned so that the spring extends longitudinally along the fixed arm. The indicating spring is schematically illustrated and can take a wide variety of different forms. For example, the indicating spring can be any resiliently deformable component. The indicating spring 5212 can include closed ends and/or can be covered with cloth or other material to prohibit damage to the leaflet tissue. The indicating spring 5212 deforms when the native leaflet tissue is pressed against the indicating spring 5212 by the moveable arm 5230 to indicate that the leaflet tissue has reached a minimum desired engagement depth. Thus, the indicating spring 5212 will not indicate that the native leaflet 42, 44 has reached the desired engagement depth until the leaflet 42, 44 is inserted at or beyond the location of the indicating spring 5212. Once the leaflet 42, 44 has reached the desired engagement depth, actuation of the moveable arm 5230 squeezes the leaflet tissue 42, 44 against the indicating spring 5212 or a portion of the indicating spring of the fixed arm 5210 to cause the indicating spring 5212 or a portion of the indicating spring to flatten and thereby indicate that the leaflet 42, 44 has been inserted into the clasp 5200 at or beyond the desired engagement depth. The indicating spring 5212 can also provide a precise visual indication of leaflet insertion, since the amount of the indicating spring that is depressed is directly related to the amount of leaflet insertion. The clasp 5200 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the clasps described herein.

[00428] Referring now to Figures 135-137, the example clasp 5200 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 135, the clasp 5200 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening 5206 of the clasp 5200 formed between the fixed and moveable arms 5210, 5230. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the moveable arm 5230 is actuated via actuation lines (not shown) as shown in Figures 136-137.

[00429] Referring now to Figure 136, when the moveable arm 5230 is actuated to push the leaflet 42, 44 against the fixed arm 5210, the leaflet 42, 44 may contact a portion of the fixed arm 5210 without contacting the indicating spring 5212 when the engagement depth of the leaflet 42, 44 is less than the minimum desired engagement depth. As can be seen in Figure 137, the indicating spring 5212 is deformed or flattened from contact with the leaflet 42, 44 when the leaflet 42, 44 is inserted into the clasp 5200 at or beyond the minimum engagement depth and is pressed against the indicating spring 5212 by the moveable arm 5230. That is, the indicating spring 5212 is deformed by the leaflet 42, 44 to indicate that the leaflet 42, 44 has been inserted at or beyond the minimum engagement depth. In some embodiments, actuation of the moveable arm 5230 also causes the barbed portion 5240 to engage and secure the leaflet 42, 44 within the barbed clasp 5200. If the indicating spring 5212 indicates that the leaflet 42, 44 is not inserted to the desired depth, the clasp 5200 can be opened to allow for repositioning of the leaflet 42, 44.

[00430] Referring now to Figures 133A, 134A, 135A, 136A, and 137A, in an example embodiment of a clasp, the indicating spring 5212 as illustrated in Figures 133-137 can be secured to the moveable arm 5230 rather than the fixed arm 5210. The indicating spring 5212 can be made from one or more materials visible with fluoroscopy. The indicating spring 5212 can be made with Nitinol or other material visible with fluoroscopy. The indicating spring can be fixed between the barb 5240 and the flex or hinge region 5220. The indicator spring 5212 secured to the moveable arm 5230 operates in the same way to indicate when a leaflet 42, 44 is inserted sufficiently into the clasp, as the indicator spring 5212 with regard to Figures 133-134.

[00431] Referring to Figures 133A and 134A, the clasp 5200 is in an open configuration with no leaflet positioned between the arms of the clasp. The indicating spring 5212 is secured to

the interior side of the moveable arm 5230 at a location between the barbed portion 5240 and the flex or hinge portion 5220.

[00432] Referring to Figure 135A, the leaflet 42, 44 is positioned partially within the clasp 5200 and the clasp is in an open configuration. Referring to Figure 136A, the clasp 5220 is closed on the leaflet 42, 44 and the indicating spring 5212 is not compressed because the leaflet 42, 44 is not inserted at or beyond the minimum depth in the clasp. Referring to Figure 137A, the indicating spring 5212 is partially compressed to indicate the depth of the leaflet within the clasp. The compression of the indicating spring 5212 can indicate that the leaflet is sufficiently engaged by the clasp. The barbed region 5240 can pierce the leaflet to hold it in place within the clasp. The clasp can be reopened so that the leaflet can be repositioned, until the leaflet is positioned at or beyond a minimum depth as desired by the operator.

[00433] In the example embodiments having a coil indicator, the coil can be Nitinol, a Nitinol wire with a platinum core, or Nitinol wrapped with a platinum wire. The coil can be any other combination of materials that can be visualized with fluoroscopy imaging techniques.

[00434] Referring now to Figures 133B, 134B, 135B, 136B, and 137B, in an example embodiment of a clasp, the indicating spring 5212 as illustrated in Figures 133-137 can be secured at or near the flex or hinge region 5220. The indicating spring is fixed to the clasp at one end of the indicating spring, and when in its resting state, extends away from the flex or hinge region toward the central region of the interior of the clasp, where a leaflet would be positioned, and the other end of the indicating spring is free and unattached. The indicating spring 5212 can be made from one or more materials visible with fluoroscopy. The indicating spring 5212 can be made with Nitinol or other material visible with fluoroscopy.

[00435] Referring to Figures 133B and 134B, the clasp 5200 is in an open configuration with no leaflet positioned between the arms of the clasp.

[00436] Referring to Figure 135B, the leaflet 42, 44 is positioned partially within the clasp 5200 and the clasp is in an open configuration. Referring to Figure 136B, the clasp 5220 is closed on the leaflet 42, 44 and the indicating spring 5212 is not compressed because the leaflet 42, 44 is not inserted at or beyond the minimum depth in the clasp. Referring to Figure 137B, the indicating spring 5212 is partially compressed to indicate the depth of the leaflet within the clasp. The compression of the indicating spring 5212 can indicate that the leaflet is sufficiently engaged by the clasp. The barbed region 5240 can pierce the leaflet to hold it in place within the clasp. The clasp can be reopened so that the leaflet can be

repositioned, until the leaflet is positioned at or beyond a minimum depth as desired by the operator.

[00437] Referring now to Figures 138-142, an example clasp 6400 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 6400 includes a fixed arm 6410, a flex or hinge portion 6420, and a moveable arm 6430 having a barbed portion 6440 (though other friction-enhancing portions can be used). The fixed arm 6410 also includes an indicating pad 6450 disposed at a distance from the flex or hinge portion that is less than a distance between the barbed portion 6440 and the flex or hinge portion 6420. The indicating pad 6450 can take a wide variety of different forms. For example, the indicating pad can comprise upstanding strands, (like carpet strands, toothbrush bristles, etc.), braided wire mesh, compressible foam, non-woven fabrics (such as spun bond, air laid, and/or lofted plastics, such as polyethylene terephthalate ("PET")), woven fabrics, etc. The indicating pad 6450 can be made from a radio opaque material, be covered with a radio opaque material and/or be partially made from a radio opaque material, such as PET and partially made from a non-radio opaque material. In some embodiments, the indicating pad 6450 can be formed by hoops of wire extending from the fixed arm 6410. In some embodiments, the indicating pad 6450 is arranged on the moveable arm 6430 instead of the fixed arm 6410. The clasp 6400 can also include a separate indicating arm (not shown) to press the leaflet 42, 44 against the indicating pad 6450 without actuating the movable arm 6430. An indicating pad can be included on any of the fixed arms, moveable arms, and or indicating arms disclosed herein.

[00438] Figures 138A and 139A illustrate an example clasp 6400 similar to that described above with reference to Figures 138 and 139. Like the clasp 3500 described above, the clasp 6400 includes a fixed arm 6410, a flex or hinge portion 6420, and a moveable arm 6430 having a barbed portion 6440 (though other friction-enhancing portions can be used). The fixed arm 6410 also includes an indicating pad 6450 disposed at a distance from the flex or hinge portion that is less than a distance between the barbed portion 6440 and the flex or hinge portion 6420. The moveable arm 6430 also includes an opening 6480 in which the indicating pad 6450 can pass through when the clasp is closed and the leaflet 42, 44 is not fully engaged.

[00439] The indicating pad 6450 is configured to deform, such as elastically deform, when engaged by the native leaflet tissue that is pressed against the indicating pad 6450 by the fixed and moveable arms 6410, 6430. When the tissue disengages the indicating pad 6450 the

indicating pad 6450 optionally returns to a neutral position. More specifically, the indicating pad 6450 deforms only in the areas that are engaged by the leaflet and the areas not engaged by the leaflet remain in substantially an initial or resting condition in one example embodiment. Thus, the indicating pad 6450 can indicate that the native leaflet 42, 44 has reached the desired engagement depth when a predetermined portion or the entirety of the indicating pad 6450 has been deformed by the leaflet 42, 44. Once the leaflet 42, 44 has reached the desired engagement depth, actuation of the moveable arm 6430 squeezes the leaflet tissue 42, 44 against the indicating pad 6450 of the fixed arm 6410 to cause the indicating pad 6450 to deform and thereby indicate that the leaflet 42, 44 has been inserted into the clasp 6400 at or beyond the desired engagement depth. The clasp 6400 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00440] Referring now to Figures 140-142, the example clasp 6400 having an indicating pad 6450 as a leaflet depth indicator is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Figures 141 and 142 illustrate an indicating pad 6450 that can deform or flatten upon contact with a leaflet. Referring now to Figure 140, the clasp 6400 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening 6406 of the clasp 6400 formed between the fixed and moveable arms 6410, 6430. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the moveable arm 6430 is actuated via actuation lines (not shown) as shown in Figures 141-142.

[00441] Referring now to Figure 141, when the moveable arm 6430 is actuated to push the leaflet 42, 44 against the fixed arm 6410, the leaflet 42, 44 may contact a portion of the fixed arm 6410 without contacting the indicating pad 6450 when the engagement depth of the leaflet 42, 44 is less than the minimum desired engagement depth.

[00442] Referring now to Figure 142, the indicating pad 6450 is deformed or flattened from contact with the leaflet 42, 44 when the leaflet 42, 44 is inserted into the clasp 6400 at or beyond the minimum engagement depth and is pressed against the indicating pad 6450 by the moveable arm 6430. That is, the portion of the indicating pad 6450 that is deformed by the leaflet 42, 44 indicates that the leaflet 42, 44 has been inserted at or beyond the minimum engagement depth. In some embodiments, actuation of the moveable arm 6430 also causes the barbed portion 6440 to engage and secure the leaflet 42, 44 within the barbed clasp 6400.

If the indicating pad 6450 indicates that the leaflet 42, 44 is not inserted to the desired depth, the clasp 6400 can be opened to allow for repositioning of the leaflet 42, 44.

[00443] Referring now to Figures 140A, 141A, and 142A, the indicating pad can pass through opening 6480 of the moveable arm 6430 when the clasp is closed, and the leaflet is not fully engaged. Referring to Figure 140A, similar to Figure 140, clasp 6400 is open and leaflet 42, 44 is partially inserted into the clasp. Referring to Figure 141A, clasp 6400 is closed and leaflet 42, 44 is not inserted at or beyond the minimum depth in the clasp. Indicating pad 6450 is not deformed, and instead passes through opening 6480 in moveable arm 6430. The indicating pad positioned through the opening 6480 is visible to the operator to indicate that the leaflet is not inserted at a sufficient depth in the clasp. Referring to Figure 142A, the indicating pad 6450 is deformed or flattened from contact with the leaflet 42, 44 when the leaflet 42, 44 is inserted into the clasp 6400 at or beyond the minimum engagement depth and is pressed against the indicating pad 6450 by the moveable arm 6430. That is, the portion of the indicating pad 6450 that is deformed by the leaflet 42, 44 indicates that the leaflet 42, 44 has been inserted at or beyond the minimum engagement depth. In some embodiments, actuation of the moveable arm 6430 also causes the barbed portion 6440 to engage and secure the leaflet 42, 44 within the barbed clasp 6400. A portion of the indicating pad 6450 that is not deformed or flattened by the leaflet 42, 44 extends through the opening 6480 of the moveable arm 6430 when the clasp is closed. If the indicating pad 6450 indicates that the leaflet 42, 44 is not inserted to the desired depth, the clasp 6400 can be opened to allow for repositioning of the leaflet 42, 44.

[00444] Referring now to Figures 143-154, an example clasp 4400 that is the same or substantially the same as the embodiment illustrated by Figures 48-66 or Figures 111-122, except the clasp is actively collapsible by lines, such as suture lines. Referring to Figures 144 and 145, the moveable arm 4430 includes side beams that are flexible, particularly in the lateral direction. The moveable arm 4430 includes holes 1431 for receiving one or more actuation sutures 2152 that are used to collapse the moveable arm 2130. For example, the sutures 2152 can be pulled on to pull the side beams inward of the moveable arm 4430 inward as the clasp is routed through the native valve, such as the native mitral valve and associated chordae tendineae. In the illustrated example, the lines 2152 are routed through the holes 1431 and through a hole 1433 in the indicator arm 4450. The hole 1433 in the indicator arm can be centered between the holes 1431 in the movable arm 4430 to efficiently and/or symmetrically pull the side beams of the moveable arm inward. For example, arranging the hole 1433 in the

indicator arm closer to the holes 1431 causes the forces applied to the clasp 4400 by the sutures 2152 to be directed in a more lateral rather than longitudinal direction.

[00445] The rounded hoop shape of the clasp 4400 allows the clasp 2100 to be collapse by merely retracting the clasp 2100 into the delivery sheath. In certain embodiments, the expansion and contraction of the clasp 4400 is controllable by the actuation sutures 2152.

[00446] The clasp illustrated by Figures 143-154 can be used in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. The clasp 4400 has a fixed arm 4410, a patterned flex portion or patterned hinge portion 4420, a moveable arm 4430 formed in the shape of a hoop or loop having side beams 4432, and a barbed portion 4440 of the moveable arm 4430. The clasp 4400 also includes an indicator arm 4450 extending from an indicator flex or hinge portion 4460 that joins the indicator arm to the flex or hinge portion 4420. The illustrated clasp also includes the suture holes 1431 positioned part-way down on the moveable arm 4430 and a suture hole 1433 in the indicator arm 4450. The suture holes can be positioned one on each of the side beams 4432 of the moveable arm, such that each suture hole is positioned at a location between the barb 4446 and the patterned flex portion or patterned hinge portion 4420. The suture holes 1431 are used for the actuation lines 2152, which can be suture lines. As mentioned above, the actuation lines are used to control the expansion and contraction of the clasp 4400. The same suture line can be used to raise and lower both the moveable arm and/or the indicator arm. The indicator arm can also have an optional suture hole 4452 at its free end (see Figure 144).

[00447] In one example embodiment, the actuation lines are attached to suture holes 1431 in the illustrated position on the side beams to reduce the moment arm, as compared to suture holes at the free end of the moveable arm side beams. This allows the operator to raise the moveable arm first, and then raise the indicator arm, when opening the clasp with a single suture line. Likewise, when closing the clasp, the indicator arm can will be lowered first before the moveable arm is lowered.

[00448] The clasp 4400 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein. For example, the clasp 4400 can be laser cut from a flat sheet or a tube of shape-memory alloy, such as Nitinol, and then shape-set into a desired shape.

[00449] The illustrated fixed arm 4410 has two tongue portions 4411 that each include holes 4412 for attaching the fixed arm 4410 to an implantable device. A central opening 4454 arranged between the tongue portions 4411 is wider than the indicator arm 4450 so that the

indicator arm 4450 can optionally pass through the fixed arm 4410 between the tongue portions 4411.

[00450] The patterned flex portion or patterned hinge portion 4420 is formed from a plurality of spring segments 4422 and cutouts 4424. The two tongue portions 4411 of the fixed arm 4410 extend from one end of the patterned flex/hinge portion 4420 and the moveable arm 4430 extends from the other end of the flex/hinge portion 4420.

[00451] The moveable arm 4430 of the clasp 4400 has a hoop-like shape. The hoop-shaped moveable arm 4430 includes side beams 4432 that are thinner and more flexible, particularly in the lateral direction. The side beams 4432 can optionally include a first flex or hinge portion 4434 arranged toward the proximate end of the moveable arm 4430 and a second flex or hinge portion 4436 arranged at the distal end of the moveable arm 4430. The first flex or hinge portion 4434 is formed by one or more bends in the side beams 4432. The second flex or hinge portion 4436 includes a thinner—and therefore more flexible—portion to reduce the force required to collapse the clasp 4400.

[00452] The hoop-like shape of the moveable arm 4430 provides for a wider barbed portion 4440 that can include more barbs 4442 with the same or greater lateral spacing than other clasps. The wider spacing of the barbs 4442 improves capture of the native leaflets. The barbs 4442 are also longitudinally staggered as a result of their position on the hoop-like shape of the moveable arm 4430. That is, two center barbs 4444 are arranged further away from the flex or hinge portion 4420 and two outer barbs 4446 are arranged closer to the flex or hinge portion 4420. The barbed portion 4440 of the moveable arm 4430 can include optional additional holes 4448 for receiving an additional actuation suture (not shown). In certain embodiments, the hoop shape of the moveable arm 4430 is similar to the shape of wide outer paddles of an implantable device so that pinching forces of the paddles are spread out evenly on the barbs, further improving the retention of the native leaflets. The ends of the barbs 4442 can be further sharpened using any suitable sharpening means.

[00453] The indicator arm 4450 includes a beam 4451 that extends from the flex or hinge portion 4420 in the interior of the hoop-shaped moveable arm 4430 between the two side arms 4432 to a barbed portion 4456. The indicator arm 4450 includes an optional hole 4452 at the end for receiving an optional actuation line (not shown) for actuating the indicator arm 4450. The optional barbed portion 4456 is arranged at the end of the beam 4451 of the indicator arm 4450 and can include at least one barb 4456. The barbed portion 4456 helps the indicator arm 4450 secure the leaflet until the moveable arm 4430 is closed. The barb 4456

can be laser cut from the indicator arm 4450 and bent outwards so that it protrudes away from the indicator arm 4450 at about the same angle as the barbs 4442 protrude from the moveable arm 4430. In some embodiments, the indicator arm 4450 includes barbs that, like the barbs 2244 of the clasp 2200, are cut from a flat sheet of material and then rotated 90 degrees to protrude outward at an angle.

[00454] The barbed portion 4456 of the indicator arm 4450 is arranged at a distance from the flex or hinge portion 4420 such that the optional barb 4456 of the indicator arm 4450 is longitudinally arranged between the center barbs 4444 and the outer barbs 4446 of the barbed portion 4440. This arrangement ensures that the barbed portion 4440 will engage a leaflet that is engaged by the indicator arm 4450. That is, if a native leaflet positioned within the clasp 4400 is engaged by the barbed portion 4456 of the indicator arm 4450 when the indicator arm 4450 is actuated, then the leaflet will also be engaged by the barbed portion 4440 of the moveable arm 4430. The opposite is also true. That is, if a native leaflet positioned within the clasp 4400 is not engaged by the indicator arm 4450 when the indicator arm 4450 is actuated, then the leaflet will not be sufficiently engaged by the barbed portion 4440 of the moveable arm 4430.

[00455] The indicator flex or hinge portion 4460 allows the indicator arm 4450 to be actuated separately from the moveable arm 4430 to facilitate detection of the depth of engagement of the native leaflet arranged between the moveable arm 4430 and the fixed arm 4410 of the clasp 4400. The indicator flex or hinge portion 4460 is similar to the patterned flex or hinge portion 4420 and is formed from a series of spring segments 4462 and cutouts 4464. In some embodiments, the spring force of the indicator flex or hinge portion 4460 is less than the pinching force imparted to the moveable arm 4430 by the flex or hinge portion 4420 so that the indicator arm 4450 can be actuated many times to detect the position of the leaflet while the moveable arm 4430 with a stronger pinching force is actuated once the leaflet is with barbs is held in a desirable position by the indicator arm 4450. The lower pinching force of the indicator arm 4450 reduces the force imparted onto the leaflet tissue so that the indicator arm 4450 can be repositioned repeatedly and be less likely to puncture or otherwise damage the leaflet tissue. The lower pinching force also allows the indicator arm 4450 to pulse or jump as the heart beats.

[00456] Referring now to Figures 143-145, the clasp 4400 is shown in an open position. The moveable arm 4430 and indicator arm 4450 are biased or spring-loaded in a closing direction and can be moved to and held in the open position by tension applied to the line 2152 routed

through the holes 1431, 1433 in each of the moveable arm 4430 and indicator arm 4450, respectively.

[00457] Referring now to Figures 146-148, the clasp 4400 is shown with the indicator arm 4450 in a fully deployed or actuated position, that is, the furthest extent that the indicator arm 4450 is capable of reaching when the indicator arm 4450 does not engage with the leaflet tissue during actuation. The indicator arm 4450 is allowed to close when tension on actuation lines 2152 is decreased. In the fully actuated position, the indicator arm 4450 forms an X-shape or other shape with the fixed arm 4410 that is visible via imaging devices so that the operator knows that the indicator arm 4450 has not engaged the leaflet.

[00458] Referring now to Figures 149-151, the clasp 4400 is shown with the indicator arm 4450 in an engaged or closed position. That is, the position that the indicator arm 4450 would be in when the leaflet tissue has been engaged during actuation. The indicator arm 4450 is allowed to close when tension on actuation line 2152 (not shown in Figures 149-151) is decreased. In the closed position, the indicator arm 4450 is spaced apart from the fixed arm 4410 and/or does not form an X-shape with the fixed arm 4410. Thus, the operator knows that the indicator arm 4450 has engaged the leaflet tissue when the indicator arm 4450 has been actuated when the clasp 4400 is viewed with an imaging device. In addition, or instead, the indicator arm 4450 can be optically monitored to detect pulsing or jumping of the indicator arm as the heart beats. This jumping or bouncing of the indicator arm indicates to the operator that the indicator arm has engaged leaflet tissue.

[00459] Referring now to Figures 152-154, the clasp 4400 is shown with the moveable arm 4430 and the indicator arm 4450 both in a closed position. The indicator arm and moveable arm are both closed by continued release of tension on the actuation line 2152. The initial release of tension releases the indicator arm so that it can close, and by continuing to release tension on the actuation line, the moveable arm then closes. The suture holes 1451 in the moveable arm can be positioned so that the indicator arm can close entirely before the moveable arm begins to close. In some embodiments, the suture holes 1451 can be positioned so that the indicator arm begins to close first but the moveable arm can begin to close before the indicator arm has tension on it released enough to allow it to fully close.

[00460] When the clasp 4400 is closed, the moveable arm 4430 and the indicator arm 4450 exert a pinching force that retains the native leaflet tissue to be secured within the clasp 4400. Additionally, a tortuous path for retaining the captured leaflet tissue is formed by the fixed arm 4410, the moveable arm 4430, and the barbed portion 4440. The clasp 4400 is biased in

the closed direction by the shape-setting of the moveable arm 4430 and the indicator arm 4450.

[00461] The effect of allowing the indicator arm to close first can be achieved in other embodiments as well. These embodiments permit semi-independent control of a weaker shorter indicator arm to close first and open second. For example, the actuator line can be pulled from an angle not parallel to the direction of motion, i.e., increasing the tension force required to lift the clasp. In another example, the suture loop can be doubled back through the clasp connection so that the suture tension force is doubled on the main clasp, causing it to lift first.

[00462] Referring now to Figures 215-216, schematic views of example embodiments of a clasp for use in an implantable prosthetic device, such as devices 100, 200, and 300 described above, are shown. Like the clasp 3500 described above, the clasp 5200 includes a fixed arm 5310, a flex or hinge portion 5320, and a moveable arm 5330 having a barbed portion 5340 (though other friction-enhancing portions can be used), an opening 5334, and two side arms 5332. In the example illustrated by Figure 215, the clasp has two flexible indicators 5350a, 5350b, positioned between side arms 5332 of the moveable arm 5330. Having two indicator arms 5350a, 5350b that are independently moveable with respect to each other, along the width of the moveable arm, can be used to indicate the proper rotational orientation of the clasp on the leaflet 42, 44. The flexible indicators can be part of the laser cut clasp or can be attached to the laser-cut clasp frame by welding or rivets or other known means.

[00463] Figure 216 illustrates a side schematic view of the embodiment illustrated in Figure 215. From the side view in the open configuration, only one flexible indicator is visible because both the flexible indicators, 5350a and 5350b are aligned with each other.

[00464] Referring now to Figures 217-220, the example clasp 5300 illustrated in Figures 215-216 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 217, the clasp 5300 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening of the clasp 5300 formed between the fixed and moveable arms 5310, 5330.

[00465] Referring now to Figure 218, when the moveable arm 5330 is actuated to push the leaflet 42, 44 against the fixed arm 5310, the leaflet 42, 44 may contact a portion of the fixed arm 5310 without contacting either indicator arm 5350a, 5350b when the engagement depth of the leaflet 42, 44 is less than the minimum engagement depth. As can be seen in Figure

219, the indicator arms 5350a, 5350b are moved by the pressure of the leaflet towards the moveable arm 5330. The indicator arms flex at the flex or hinge region 5360 of each indicator arm. The indicator arms can optionally have portions (not shown) that pass through the opening 5334 of the moveable arm to indicate to the operator that the leaflet is inserted into the clasp 5300 at or beyond the minimum engagement depth.

[00466] Referring now to Figure 220, one indicator arm 5350a is moved by the pressure of the leaflet towards the moveable arm 5330. The second indicator arm 5350b has fallen past the fixed arm 5310 of the clasp to indicate that the leaflet is not positioned over that indicator arm 5350b. The first indicator arm 5350a can indicate that the leaflet is positioned sufficiently far enough in towards the flex or hinge region 5320 of the clasp, but the position of the second indicator arm 5350b indicates that the leaflet is not sufficiently engaged by the clasp because the entire width of the clasp has not engaged the leaflet. This can occur due to incorrect orientation of the clasp relative to the leaflet (i.e. the clasp is tilted or canted relative to the valve leaflet). The clasp can be reopened to reposition the clasp to obtain a proper positioning both as to the depth of the leaflet within the clasp and to ensure that the clasp is properly oriented relative to the leaflet tissue. The indicator arms can be detected by fluoroscopy or other imaging techniques. In the embodiments described herein, the indicator arms 5350a, 5350b can be integrated with the clasp, such as in the embodiments formed from a laser-cut sheet. However, the indicator arm can also be a separate piece that is fixed to the clasp in the example embodiments described herein. The indicator arm can be formed from another laser cut sheet having a thickness different than that of the clasp; i.e., the indicator arm can be thinner than the clasp arms to create an indicator that is more flexible than the remainder of the clasp. The indicator arm can be connected via rivets, welding, and/or any other technique known in the art to secure two elements together.

[00467] Referring now to Figures 155, 155A, 156-164, 164A, 164B, and 203-205, example actuation mechanisms are shown for actuating clasps (e.g., barbed clasps, clasps with other friction enhancing elements, plain clasps, etc.); in particular, clasps with at least two actuatable portions such as the clasps with indicator arms described above. These actuation mechanisms employ one or more actuation lines or sutures to open and close the components of the clasps described herein. The actuation lines are removably attached to the clasps so that the actuation lines can be withdrawn through the delivery device once the implantable device has been deployed.

[00468] Figures 155A, 164A, and 164B illustrate delivery sheaths 102 with actuation lines for example actuation mechanisms for actuating clasps (e.g., barbed clasps, etc.) with at least two actuatable portions, such as the clasps with indicator arms described above. The delivery sheath 102 is connected to a collar or coupler 103 with moveable fingers 105 that couple to the device 100. The moveable fingers 105 are schematically illustrated in the outwardly spread or release configuration in Figures 155A, 164A, and 164B. In this condition, the device 100 is released from the collar or coupler 103. The actuation lines extend through lumens or openings 107 in the collar 103 and then through openings 109 in the moveable fingers 105 to engage the moveable arm 134, indicator arm 150, and/or loops attached to either or both of the moveable arm 134 and indicator arm 150.

[00469] Referring now to Figure 155A, an actuation mechanism 6500 is shown extending through the collar 103 and the moveable fingers 105. The actuation mechanism 6500 includes actuation lines 6502 that each include a one-way catch 6508. The one-way catch 6508 can be a knot in the actuation line 6502 or can be an object attached to the actuation line 6502, such as, for example, a bead threaded onto the actuation line 6502 and affixed in place by wrapping the actuation line 6502 around the bead or with any other suitable mechanical or adhesive means. As can be seen in Figure 155A, the one-way catch 6508 can have a conical shape so that it passes through a loop in a first direction and catches on the loop when moved in a second direction.

[00470] Referring now to Figures 164A and 164B, example actuation mechanisms are shown that use separate actuation lines to actuate the moveable and indicator arms, unlike the actuation mechanism shown in Figures 155A that uses a single actuation line to actuate both the moveable clasp and indicator arms. Referring now to Figure 164A, an example actuation mechanism 6600 is shown. The actuation mechanism 6600 includes first actuation lines 6602 and second actuation lines 6604. The first actuation lines 6602 are for actuating the moveable arms and the second actuation lines 6604 are for actuating the indicator arms. Each of the actuation lines 6602, 6604 can be separately actuated to control the moveable arms 134 and the indicator arms 150 of the device 100. As can be seen in Figure 164A, the first and second actuation lines 6602, 6604 are shown extending through the collar 103 and the moveable fingers 105. The first actuation lines 6602 extend through the lumens 107 in the collar 103 and the second actuation lines 6604 extend through secondary lumens 107A in the collar 103. Each of the first and second actuation lines 6602, 6604 extends from one lumen 107, 107A, respectively, and returns through a different lumen 107, 107A, respectively. In some

embodiments, the second actuation lines 6604 and the secondary lumens 107A have a smaller diameter than the first actuation lines 6602 and lumens 107, respectively.

[00471] Referring now to Figure 164B, an example actuation mechanism 6700 is shown. The actuation mechanism 6700 includes first actuation line(s) 6702 and second actuation line(s) 6704. The first actuation line(s) 6702 are for actuating the moveable arms (not shown) and the second actuation line(s) 6704 are for actuating the indicator arms (not shown). Each of the actuation lines 6702, 6704 can be separately actuated to control the moveable arms 134 and the indicator arms 150 of the device 100. As can be seen in Figure 164B, the first and second actuation lines 6702, 6704 are shown extending through the collar 103 and the moveable fingers 105. Unlike the collar 103 of Figure 164A, the collar 103 of Figure 225 does not have secondary lumens 107A. Thus, each of the first actuation line(s) 6702 extends from one lumen 107 and returns through a different lumen 107, while the second actuation line(s) 6704 extend from one lumen 107 alongside the first actuation line(s) 6702. In some embodiments, the second actuation line(s) 6704 have a smaller diameter than the first actuation line(s) 6702. In some embodiments, the actuation lines 6702, 6704 also extend through a secondary collar 103A and are pulled from beyond the secondary collar 103A so that friction between the actuation lines 6702, 6704 is reduced.

[00472] Referring now to Figures 203-205, actuation mechanisms using a single actuation line to actuate both the moveable and indicator arms are shown on device 100. For example, the embodiment of Figure 155A can optionally be used in the embodiment of Figures 203-205. The device 100 includes clasps 130 each having a fixed arm 132 and a moveable arm 134. The clasps 130 can include barbs, other friction-enhancing elements, etc. or optionally, not include these. The clasps 130 shown in Figures 155-160 also include an indicator arm 150, such as the indicator arms described herein. The actuation mechanisms described below are used to actuate the moveable arm 134 and indicator arm 150 of the clasps 130. The components of the clasps 130 are shown in an open position on the left side of the device 100 to clearly illustrate the relationship between the components (the indicator is partially open, so that it is visible), while the clasps 130 on the right side of the device 100 are shown in various stages of actuation.

[00473] Referring now to Figures 203-205, the actuation mechanism 6500 is shown attached to the device 100, which can be the device illustrated and described in Figures 143-154, having suture holes positioned between a flexible bend and a barbed end of the moveable arm. The actuation mechanism 6500 includes a single actuation line 6502 on each side of the

device, extending from the delivery sheath 102, through a first suture hole 1431 positioned on the moveable arm, a second suture hole 1433 positioned on the indicator arm 4450, and returning into the delivery sheath 102. The first and second suture holes 1431, 1433 are through or attached to the moveable arm 134 and indicator arm 150, respectively. The first suture hole 1431 is near a midpoint of the moveable arm 134. The second suture hole 4452 is near the end of the indicator arm 150 in the example illustrated by Figures 203-205. The actuation line 6502 and the suture holes 1431, 1433 can be formed from sutures, wires, or the like. In some embodiments, the suture holes are integrally formed with a cover that covers the clasps 130 and coaption element 110.

[00474] Still referring to Figures 203-205, in one example embodiment, a one-way catch or stop 6508 of the actuation line 6502 is unable to pass through the hole or loop 1431 while being able to pass through the hole or loop loop1431 (See Figure 155A). The optional one-way catch 6508 can be a knot in the actuation line 6502 or can be an object attached to the actuation line 6502, such as, for example, a bead threaded onto the actuation line 6502 and affixed in place by wrapping the actuation line 6502 around the bead or with any other suitable mechanical or adhesive means. In some embodiments, the one-way catch 6508 has a conical shape so that it passes through the first hole or loop 1431 in a first direction and catches on the first hole or loop 1431 when moved in a second direction. Consequently, the actuation line 6502 can be pulled so that the one-way catch 6508 engages the first hole or loop 1431 to actuate the moveable arm.

[00475] Referring now to Figure 203, the actuation line 6502 is relaxed on the right side of the device 100, and the clasp 130 on the right side is shown in a closed position. The clasp 130 is biased in a closing direction so that the clasp 130 will close when there is an absence of tension on the actuation lines 6502.

[00476] Referring now to Figure 204, tension is applied to the actuation line 6502 to actuate the moveable arm 134. This is done by pulling on the first end 6510 of the actuation line 6502 until the one-way catch 6508 engages the first hole or loop 1431. The pulling force applied to the actuation line 6502 is transferred to the first hole or loop 1431 via the one-way catch 6508 to cause the moveable arm 134 to open from the closed position shown in Figure 203 to the open position shown in Figure 204.

[00477] Referring now to Figure 205, tension is maintained on the first end of the actuation line 6502 to maintain the moveable arm 134 in the open position. Tension is then applied to the second end of the actuation line 6502 to cause the length of the loop of actuation line

6502 to shorten and to pull on the second moveable hole or loop 1431 of the indicator arm 150 to cause the indicator arm 150 to open from the closed position shown in Figure 204 to the open position shown in Figure 205.

[00478] Referring now to Figures 221-222, an example clasp 3500 (illustrated as a barbed clasp) for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. The clasp 3500 is configured to capture the native tissue when the implantable prosthetic device—e.g., any device described in the present application—is attached to the native tissue. Like the clasps described above, the clasp 3500 includes a fixed arm 5310, a flex or hinge portion 5320, and a moveable arm 5330 having a barbed portion 5340 (though other friction-enhancing portions can be used). The clasp 3500 also includes an indicator arm 5350 adjacent to the moveable arm 5330 and extending from an indicator flex or hinge portion 5360. The clasp 3500 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00479] The clasp 3500 of Figures 221-225 also includes a first suture hole, eyelet, loop, or ring 1431 positioned at the end of moveable arm 5330 and a second suture hole, eyelet, loop, or ring 1433 positioned at the end of the indicator arm 5350. A single actuation line 6502 can be threaded through both the first and second suture holes, eyelets, loops, or rings 1431, 1433. The single actuation line 6502 can be used to open and close both the moveable arm and the indicator arm. In one example embodiment, the indicator arm 5350 closes before the moveable clasp arm 5330 and the moveable clasp arm opens before the indicator arm. In an example embodiment, the moveable arm and indicator arm can be opened simultaneously. In an example embodiment, the indicator arm partially closes before the moveable clasp arm begins to close and the moveable clasp arm partially opens before the indicator arm begins to open. The actuation line can be a suture, thread, wire, a biocompatible filament, etc. that can be threaded through the suture holes 1431, 1433. A single actuation line can be used to open and close the moveable arm and indicator arm(s) on any of the example embodiments described herein. In one example embodiment, the single actuation line does not include a one-way knot, stop, cone, or other structure.

[00480] Referring now to Figures 223-225, the example clasp 3500 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 223, the clasp 3500 is shown in an open condition with a native leaflet 42, 44 partially

inserted into an opening of the clasp 5300 formed between the fixed and moveable arms 5310, 5330. The indicator arm 5350 and moveable arm 5330 are in a raised (or open) position due to the tension on the suture line 6502 caused by pulling both ends of the suture line towards the operator in a direction indicated by arrow 2221. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the indicator arm 3550 can be actuated by reducing tension on the actuation line 6502.

[00481] Referring now to Figure 224, the tension on the actuation line 6502 has been released, and the clasp is shown in a closed configuration, closed on the leaflet 42, 44. The indicator arm and moveable arm are actuated (i.e., lowered in the direction towards the fixed arm). Because the leaflet 42, 44 is inserted into the opening of the clasp 5300 about half way between the barbed portion 5340 and the flex or hinged portion 5320 and is not inserted far enough into the clasp to overlap with the length of the indicator arm 5350, the indicator arm 3550 does not engage the leaflet 42, 44. Instead, the indicator arm swings toward the fixed arm 3510. The indicator arm's position is visible via imaging devices used to monitor implantation and deployment of the prosthetic device. The actuation line can be pulled and released multiple times to open and close the clasp and/or indicator, so that the leaflet can be repositioned if needed.

[00482] Referring now to Figure 225, the clasp is closed on the leaflet 42, 44, by release of the tension on actuation line 6502, and the leaflet is positioned deep enough into the clasp 5300 such that it overlaps with the indicator arm 5350. The barb 5340 on the moveable arm 5330 has pierced the native leaflet. The indicator arm rests on the leaflet tissue, and the leaflet prevents the indicator arm from moving all the way toward the fixed arm 5310 of the clasp. Although the indicator arm as illustrated in Figures 221-225 does not have a barb on it, in some example embodiments, it can have a barb to further secure the leaflet in place.

[00483] As has been described above, because of the arrangement of the first and second suture holes 1431, 1433 and the one-way catch 6508 the moveable and indicator arms 134, 150 can be opened in sequence with a single looped actuation line. In an example embodiment, the one-way catch is omitted and the moveable and indicator arms 134, 150 are opened in sequence due to the combined effect of the relative flexibility of the flex or hinge portions of the moveable and indicator arms 134, 150 and the relative distances of the holes or loops 1431, 1433 to the flex or hinge portions of the moveable and indicator arms 134, 150. The moveable and indicator arms 134, 150 are closed in the reverse sequence when

tension on the actuation line 6502 is reduced. That is, the indicator arm 150 closes first, followed by the moveable arm 134.

[00484] Referring now to Figures 155-160, actuation mechanisms using a single actuation line to actuate both the moveable and indicator arms are shown on device 100. For example, the embodiment of Figure 155A can optionally be used in the embodiment of Figures 155- The device 100 includes clasps 130 each having a fixed arm 132 and a moveable arm 134. The clasps 130 shown in Figures 155-160 also include an indicator arm 150, such as the indicator arms described herein. The actuation mechanisms described below are used to actuate the moveable arm 134 and indicator arm 150 of the clasps 130. The components of the clasps 130 are shown in an open position on the left side of the device 100 to clearly illustrate the relationship between the components, while the clasps 130 on the right side of the device 100 are shown in various stages of actuation.

[00485] Referring now to Figures 155-157, the actuation mechanism 6500 is shown attached to the device 100. The actuation mechanism 6500 includes actuation lines 6502 extending at a first end 6510 from the delivery sheath 102, through a first loop 6504, a second loop 6506, and returning into the delivery sheath 102 at a second end 6512. The first and second loops 6504, 6506 are attached to the moveable arm 134 and indicator arm 150, respectively. The first loop 6504 is attached near the end of the moveable arm 134. The second loop 6506 is attached near the middle of the indicator arm 150. The actuation lines 6502 and the loops 6504, 65, can be formed from sutures, wires, or the like. In some embodiments, the loops 6504, 6506, are integrally formed with a cover that covers the clasps 130 and coaption element 110.

[00486] The one-way catch 6508 of the actuation lines 6502 is unable to pass through the first loop 6504 while being able to pass through the second loop 6506. The one-way catch 6508 can be a knot in the actuation line 6502 or can be an object attached to the actuation line 6502, such as, for example, a bead threaded onto the actuation line 6502 and affixed in place by wrapping the actuation line 6502 around the bead or with any other suitable mechanical or adhesive means. In some embodiments, the one-way catch 6508 has a conical shape so that it passes through the first loop 6504 in a first direction and catches on the first loop 6504 when moved in a second direction. Consequently, the actuation line 6502 can be pulled so that the one-way catch 6508 engages the first loop 6504 to actuate the moveable arm.

[00487] Referring now to Figure 155, the actuation line 6502 is relaxed on the right side of the device 100, and the clasp 130 on the right side is shown in a closed position. The clasp 130 is

biased in a closing direction so that the clasp 130 will close when there is an absence of tension on the actuation lines 5102.

[00488] Referring now to Figure 156, tension is applied to the actuation line 6502 to actuate the moveable arm 134. This is done by pulling on the first end 6510 of the actuation line 6502 until the one-way catch 6508 engages the first loop 6504. The pulling force applied to the actuation line 6502 is transferred to the first loop 6504 via the one-way catch 6508 to cause the moveable arm 134 to open from the closed position shown in Figure 155 to the open position shown in Figure 156.

[00489] Referring now to Figure 157, tension is maintained on the first end 6510 of the actuation line 6502 to maintain the moveable arm 134 in the open position. Tension is then applied to the second end 6512 of the actuation line 6502 to cause the length of the loop of actuation line 6502 to shorten and to pull on the second moveable loop 6506 attached to the indicator arm 150 to cause the indicator arm 150 to open from the closed position shown in Figure 156 to the open position shown in Figure 157.

[00490] As has been described above, because of the arrangement of the first and second moveable loops 6504, 6506 and the one-way catch 6508 the moveable and indicator arms 134, 150 can be opened in sequence with a single looped actuation line. The moveable and indicator arms 134, 150 are closed in the reverse sequence when tension on the actuation line 6502 is reduced. That is, the indicator arm 150 closes first, followed by the moveable arm 134. Similar concepts may be applied to clasps having two or more moveable portions, such as the clasp 2200 described above. In some embodiments, a plurality of catches of different sizes may interact with a plurality of loops of different sizes to control the opening and closing of a plurality of moveable portions of a clasp.

[00491] Referring now to Figures 158-160, the device 100 is shown with an actuation mechanism 6800. The actuation mechanism 6800 includes actuation lines 6802 extending at a first end 6810 from the delivery sheath 102, through a first moveable loop 6804, a first stationary loop 6814, a second stationary loop 6816, a second moveable loop 6806, and then back through the second stationary loop 6816, the first stationary loop 6814, the first moveable loop 6804, and returning into the delivery sheath 102 at a second end 6812. The first and second moveable loops 6804, 6806 are attached to the moveable arm 134 and indicator arm 150, respectively. The first loop 6804 is attached near the end of the moveable arm 134. The second loop 6806 is attached near the middle of the indicator arm 150.

[00492] In some embodiments, the first and second stationary loops 6814, 6816 are attached to the coaption element 110 of the device 100. The first stationary loop 6814 is attached near the proximal end of the coaption element 110. The second stationary loop 6816 is attached near the middle of the coaption element 110. The actuation lines 6802 and the loops 6804, 6806, 6814, 6816 can be formed from sutures, wires, or the like. In some embodiments, the loops 6804, 6806, 6814, 6816 are integrally formed with a cover that covers the clasps 130 and coaption element 110.

[00493] Referring now to Figure 158, the actuation line 6802 is relaxed on the right side of the device 100, and the clasp 130 on the right side is shown in a closed position. The clasp 130 is biased in a closing direction so that the clasp 130 will close when there is an absence of tension on the actuation lines 6802.

[00494] Referring now to Figure 159, tension is applied to the actuation line 6802 to actuate the moveable arm 134. This may be done by pulling on one end 6810, 6812 of the actuation line 6802 while holding the other end 6812, 6810 so that the length of the actuation line 6802 shortens or can be done by pulling on both ends 6810, 6812 simultaneously. As force is applied to the actuation line 6802, the actuation line 6802 is pulled through the moveable loops 6804, 6806 attached to the moveable arm 134 and indicator arm 150, respectively, and the stationary loops 6814, 6816 attached to the coaption element 110. In embodiments where both ends 6810, 6812 are pulled, the actuation line 6802 moves through the first moveable loop 6804 and does not move through the second moveable loop 6806. That is, the second moveable loop 6806 is located at the midpoint of the actuation line 6802 such that tension applied to both ends 6810, 6812 is transmitted to the second moveable loop 6806. Though an opening force is exerted on both of the first and second moveable loops 6804, 6806 by the actuation line 6802, the moveable arm 134 opens before the indicator arm 150 because of the greater mechanical advantage provided by the location of the first moveable loop 6804 near the end of the moveable arm 134. The routing of the actuation lines 6802 through the first moveable loop 6804 and the first stationary loop 6814 operates as a pulley that provides additional mechanical advantage. Thus, the moveable arm 134 moves from the closed position shown in Figure 158 to the open position shown in Figure 159.

[00495] Referring now to Figure 160, further tension is applied to one or both ends 6810, 6812 of the actuation line 6802 to cause the length of the loop of actuation line 6802 to shorten further and continue to pull on the first and second moveable loops 6804, 6806 and the first and second stationary loops 6814, 6816. The pulling force exerted by the actuation line 6802

is focused on the second moveable loop 6806 because the moveable arm 134 has already been moved to the open position, thereby causing the indicator arm 150 to open from the closed position shown in Figure 159 to the open position shown in Figure 160.

[00496] As has been described above, because of the arrangement of the first and second moveable loops 6804, 6806 at different distances from the flex, hinge, or pivot points of the moveable and indicator arms 134, 150, respectively, the opening of the moveable and indicator arms 134, 150 can be opened in sequence. The moveable and indicator arms 134, 150 are closed in the reverse sequence when tension on the actuation line 6802 is reduced. That is, the indicator arm 150 closes first, followed by the moveable arm 134.

[00497] The left sides of Figures 158-160 illustrate an embodiment where the moveable arm 134 and indicator arm 150 do not open and close in sequence. Rather, the force of the actuation line is shared between the moveable arm 134 and the indicator arm 150 and the moveable arm 134 and indicator arm 150 move at different rates. The relative rate at which the moveable arm 134 and indicator arm 150 open and close depends on the spring force of the moveable arm 134, the spring force of the indicator arm 150, and the positions of the loops 6814, 6816, 6806, and 6804.

[00498] In the embodiment illustrated by the left side of Figures 158-160, the moveable arm 134 opens more quickly than the indicator arm 150, but the indicator arm opens to some degree as the moveable arm opens. In this embodiment, the indicator arm 150 closes more quickly than the moveable arm 134, but the moveable arm closes to some degree as the indicator arm closes.

[00499] In the embodiment illustrated by the right side of Figures 158-160, the spring force of the moveable arm 134, the spring force of the indicator arm 150, and the positions of the loops 6814, 6816, 6806, and 6804 are selected such that the moveable arm 134 opens completely before the indicator arm 150 begins to open. In this embodiment, the indicator arm 150 closes completely before the moveable arm 134 begins to close.

[00500] The opening and closing sequence of the moveable and indicator arms 134, 150 can be changed by altering the spring force of the flex or hinge portions of the moveable and indicator arms 134, 150 and by changing the locations of the first and second loops 6804, 6806. That is, in certain embodiments, the indicator arm 150 can be caused to open first by moving the second loop 6806 to the end of the indicator arm 150 and the first loop 6804 closer to the coaption element 110, while also increasing the spring force applied to the moveable arm 134 and decreasing the spring force applied to the indicator arm 150.

Optionally, the actuation line 6802 could be routed through the second moveable loop 6806 before routing through the second stationary loop 6816 to provide a mechanical advantage when opening the indicator arm 150. Similar concepts may be applied to clasps having two or more moveable portions, such as the clasp 2200 described above.

[00501] Referring now to Figures 161-163, the device 100 is shown with an actuation mechanism 6900. The actuation mechanism 6900 includes actuation lines 6902 extending at a first end 6910 from the delivery sheath 102, passing through first and second loops 6904, 6906, and returning into the delivery sheath 102 at a second end 6912. The first and second loops 6904, 6906 are attached to the moveable arm 134 and indicator arm 150, respectively. The first loop 6904 is attached near the end of the moveable arm 134. The second loop 6906 is attached near the middle of the indicator arm 150. The actuation lines 6902 and the loops 6904, 6906 can be formed from sutures, wires, or the like. In some embodiments, the loops 6904, 6906 are integrally formed with a cover that covers the clasps 130.

[00502] Referring now to Figure 161, the actuation line 6902 is relaxed on the right side of the device 100, and the clasp 130 on the right side is shown in a closed position. The clasp 130 is biased in a closing direction so that the clasp 130 will close when there is an absence of tension on the actuation lines 6902.

[00503] Referring now to Figure 162, tension is applied to the actuation line 6902 to actuate the moveable arm 134. This may be done by pulling on one end 6910, 6912 of the actuation line 6902 while holding the other end 6912, 6910 so that the length of the actuation line 6902 shortens. For example, a pulling force can be applied to the first end 6910 of the actuation line 6902 while the second end 6912 is held in a fixed position. As force is applied to the actuation line 6902, the actuation line 6902 pulls against the loops 6904, 6906 attached to the moveable arm 134 and indicator arm 150, respectively. Though an opening force is exerted on both of the first and second loops 6904, 6906 by the actuation line 6902, the moveable arm 134 opens before the indicator arm 150 because of the greater mechanical advantage provided by the location of the first loop 6904 near the end of the moveable arm 134. Thus, the moveable arm 134 moves from the closed position shown in Figure 232 to the open position shown in Figure 162.

[00504] Referring now to Figure 163, further tension is applied to the first end 6910 of the actuation line 6902 to cause the length of the loop of actuation line 6902 to shorten and continue to pull on the loops 6904, 6906 attached to the moveable arm 134 and indicator arm 150, respectively. The pulling force exerted by the actuation line 6902 is focused on the

second loop 6906 because the moveable arm 134 has already been moved to the open position, thereby causing the indicator arm 150 to open from the closed position shown in Figure 162 to the open position shown in Figure 163.

[00505] The left sides of Figures 161-163 illustrate an embodiment where the moveable arm 134 and indicator arm 150 do not open and close in sequence. Rather, the force of the actuation line is shared between the moveable arm 134 and the indicator arm 150 and the movable arm 134 and indicator arm 150 move at different rates. The relative rate at which the moveable arm 134 and indicator arm 150 open and close depends on the spring force of the moveable arm 134, the spring force of the indicator arm 150, and the positions of the loops 6806, and 6804.

[00506] In the embodiment illustrated by the left side of Figures 161-163, the moveable arm 134 opens more quickly than the indicator arm 150, but the indicator arm opens to some degree as the moveable arm opens. In this embodiment, the indicator arm 150 closes more quickly than the movable arm 134, but the moveable arm closes to some degree as the indicator arm closes.

[00507] In the embodiment illustrated by the right side of Figures 161-163, the spring force of the moveable arm 134, the spring force of the indicator arm 150, and the positions of the loops 6806 and 6804 are selected such that the moveable arm 134 opens completely before the indicator arm 150 begins to open. In this embodiment, the indicator arm 150 closes completely before the movable arm 134 begins to close.

[00508] As has been described above, because of the arrangement of the loops 6904, 6906 at different distances from the flex, hinge, or pivot points of the moveable and indicator arms 134, 150, respectively, the opening of the moveable and indicator arms 134, 150 can be opened in sequence. The moveable and indicator arms 134, 150 are closed in the reverse sequence when tension on the actuation line 6902 is reduced. That is, the indicator arm 150 closes first, followed by the moveable arm 134. The opening and closing sequence of the moveable and indicator arms 134, 150 can be changed by altering the spring force of the flex or hinge portions of the moveable and indicator arms 134, 150 and by changing the locations of the first and second loops 6904, 6906. That is, in certain embodiments, the indicator arm 150 can be caused to open first by moving the second loop 6906 to the end of the indicator arm 150 and the first loop 6904 closer to the coaption element 110 while also increasing the spring force applied to the moveable arm 134 and decreasing the spring force applied to the

indicator arm 150. Similar concepts may be applied to clasps having two or more moveable portions, such as the clasp 2200 described above.

[00509] Referring now to Figures 164-166, the device 100 is shown with an actuation mechanism 7000. In the example illustrated by Figures 164-166, the moveable clasp arms and the indicator arms are each independently controllable by a separate actuation line 7002. In one example embodiment, the embodiments of Figures 164A or 164B can be used in the embodiment of Figures 164-166. The illustrated actuation mechanism 7000 includes an actuation line 7002 extending at a first end 7010 from the delivery sheath 102, passing through an actuation loop 7004 attached to one of the moveable or indicator arms 134, 150, forming a loop 7006 around the actuation element 112, passing through the loop 7004 again, and returning into the delivery sheath 102 at a second end 7012. The actuation lines 7002 and the loops 7004 can be formed from sutures, wires, or the like. In some embodiments, the loops 7004 are integrally formed with a cover that covers the clasps 130. Forming the loop 7006 around the actuation element 112 allows the actuation line 7002 to be decoupled from the moveable or indicator arms 134, 150 without releasing the first or second end 7010, 7012 and pulling the entire actuation line 7002 through the delivery sheath 102 from one end. That is, the actuation line 7002 can be disengaged from the moveable or indicator arm 134, 150 by retracting the actuation element 112 and withdrawing both the first and second ends 7010, 7012 of the actuation line 7002 a short distance to retract the loop 7006 into the delivery sheath 102.

[00510] Referring now to Figure 164, the actuation element 112 is secured to the cap 114 and the loops 7006 of the actuation lines 7002 are circled around the actuation element 112 between the coaption element 110 and the delivery sheath 102. To decouple the actuation lines 7002 from the device 100, the actuation element 112 is retracted into the delivery sheath 102 to form a gap between the actuation element 112 and the coaption element 110, as can be seen in Figure 165. The retraction of the actuation element 112 releases all of the retraction lines 7002 at once. When the retraction lines are released, all of the indicating arms 150 and moveable arms 134 close due to the closing spring force of the clasps.

[00511] Referring to Figure 165, both ends 7010, 7012 of the actuation lines 7002 are then withdrawn into the delivery sheath 102, causing the loops 7006 in the actuation lines 7002 to slide downward and off of the actuation element 112. Referring now to Figure 166, further retraction of the actuation lines 7002 disengages the actuation lines 7002 from the loops 7004 on the moveable and indicator arms 134, 150 so that the device 100 is decoupled from the

delivery sheath 102. The actuation mechanism 7000 can be used with any of the clasps and implantable prosthetic devices described herein. Similar concepts can also be applied to other actuation mechanisms described herein to reduce the time and effort required to decouple actuation lines from the implantable prosthetic device.

[00512] Referring now to Figures 192-193, an example clasp 5300 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 5300 includes a fixed arm 5310, a flex or hinge portion 5320, and a moveable arm 5330 having a barbed portion 5340. The clasp 5300 also includes an indicator arm 5350 extending from an indicator flex or hinge portion 5360 arranged toward the distal end of the moveable arm 5330. The indicator arm 5350 need not be actuated separately from the moveable arm 5330. The indicator flex or hinge portion 5360 can be formed from a portion of the indicator arm. The clasp 5300 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the clasps described herein.

[00513] The indicator arm 5350 can be moved relative to the moveable arm 5330 to facilitate detection of the depth of engagement of the native leaflet between the moveable arm 5330 and the fixed arm 5310 of the clasp 5300. The moveable arm 5330 is optionally formed in a hoop or loop shape having two side arms 5332 surrounding a central opening 5334 that extends from the flex or hinge portion 5320 to the barbed portion 5340 of the moveable arm 5330 as illustrated. In some embodiments, the moveable arm 5330 is not hoop shaped and the indicator arm 5350 is disposed next to a single moveable arm 5330. The indicator arm 5350 is disposed in the central opening 5334 between the two side arms 5332. In the illustrated example, because the moveable arm 5330 spans the full width of the clasp 5300, the barbed portion 5340 of the moveable arm 5330 is as wide as the clasp 5300 so that a larger area of the barbed portion 5340 engages with the native leaflet tissue.

[00514] As can be seen in Figures 192-193, the indicator flex or hinge portion 5360 is arranged near the barbed portion 5340 of the moveable arm 5330. The indicator flex or hinge portion 5360 is configured to bias the indicator arm 5350 at an angle from the moveable arm 5330 and toward the fixed arm 5310. The desired minimum engagement depth is determined by the angle of the indicator arm 5350 with respect to the moveable arm 5330, the distance between the indicator flex or hinge portion 5360 and the flex or hinge portion 5320, and the length of the indicator arm 5350. The minimum engagement depth decreases the further the flex or hinge portion 5360 is from the flex or hinge portion 5320, the greater the angle

between the indicator arm 5350 and the moveable arm 5330, and the greater the length of the indicator arm 5350. When the clasp 5300 is closed without the indicator arm 5350 being engaged by the leaflet, the indicator arm 5350 moves to or beyond the fixed arm 5310. The indicator arm 5350 reaching the fixed arm 5310 forms a shape that is visible via imaging devices used to monitor implantation and deployment of the device, as can be seen in Figure 195. When the leaflet is inserted into the clasp 5300 beyond the minimum desired engagement depth, the leaflet pushes the indicator arm 5350 back toward the moveable arm 5330 such that the indicator arm 5350 does not cross the fixed arm 5310 to form the indicating shape, such as the X-shape shown in Figure 195. In addition, or instead, the indicator arm bounces or pulses when engaged with the valve leaflet when the heart beats. Thus, the indicator arm 5350 indicates to an observer observing the installation via an imaging device that the leaflet is inserted into the opening 5306 beyond the minimum desired engagement depth.

[00515] Referring now to Figures 194-196, the example clasp 5300 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 194, the clasp 5300 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening 5306 of the clasp 5300 formed between the fixed and moveable arms 5310, 5330. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the moveable arm 5330 is actuated via actuation lines (not shown) as shown in Figures 195-196.

[00516] Referring now to Figure 195, when the moveable arm 5330 is actuated toward the fixed arm 5310, the leaflet 42, 44 may contact portions of the fixed and moveable arms 5310, 5330 without contacting the indicator arm 5350 when the engagement depth of the leaflet 42, 44 is less than the minimum desired engagement depth. Thus, the indicator arm 5350 extends to or beyond the fixed arm 5310 to form a shape with the fixed arm 5310 that indicates insufficient leaflet insertion. In addition, or instead, the indicator arm bounces or pulses when engaged with the valve leaflet when the heart beats.

[00517] As can be seen in Figure 196, the indicator arm 5350 is prevented from reaching or crossing the fixed arm 5310 when the leaflet 42, 44 is inserted far enough into the clasp 5300. That is, the indicator arm 5350 is deflected by the leaflet 42, 44 to indicate that the leaflet 42, 44 has been inserted at or beyond the minimum engagement depth. In some embodiments, actuation of the moveable arm 5330 also causes the barbed portion 5340 to engage and secure

the leaflet 42, 44 within the barbed clasp 5300. If the indicator arm 5350 indicates that the leaflet 42, 44 is not inserted to the desired depth, the clasp 5300 can be opened to allow for repositioning of the leaflet 42, 44. As can be seen in Figure 197, an indicator arm 5350A can optionally conform to the shape of the leaflet 42, 44 when engaged by the leaflet 42, 44 as the clasp 5300 is closed. This conforming to the shape of the leaflet can indicate the degree of insertion of the valve leaflet 42, 44 into the opening 5306.

[00518] Referring now to Figures 198-199, an example clasp 5400 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 5400 includes a fixed arm 5410, a flex or hinge portion 5420, and a moveable arm 5430 having a barbed portion 5440 (though other friction-enhancing portions can be used). The clasp 5400 also includes an indicator arm 5450 extending from an indicator flex or hinge portion 5460 arranged toward the distal end of the fixed arm 5410. The indicator arm 5450 need not be actuated separately from the fixed arm 5410. The indicator flex or hinge portion 5460 can be formed from a portion of the indicator arm 5450 or can be formed from a series of cutouts. The clasp 5400 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00519] The illustrated moveable arm 5430 is formed in a hoop or loop shape having two side arms 5432 surrounding a central opening 5434 that extends from the flex or hinge portion 5420 to the barbed portion 5440 of the moveable arm 5430. The indicator arm 5450 is disposed in the central opening 5434 between the two side arms 5432. Because the moveable arm 5430 spans the full width of the clasp 5400, the barbed portion 5440 of the moveable arm 5430 is as wide as the clasp 5400 so that a larger area of the barbed portion 5440 engages with the native leaflet tissue. In one embodiment, the moveable arm 5430 is not formed in a hoop shape. For example, the moveable arm 5430 can be a single arm.

[00520] As can be seen in Figure 199, the indicator flex or hinge portion 5460 is arranged near the distal end of the fixed arm 5410. Optionally, the indicator flex or hinge portion 5460 can be attached to a paddle (not shown) of the implantable prosthetic device. The indicator flex or hinge portion 5460 is configured to bias the indicator arm 5450 at an angle from the fixed arm 5410 and toward the moveable arm 5430. The desired minimum engagement depth is determined by the angle of the indicator arm 5450 with respect to the fixed arm 5410, the distance between the indicator flex or hinge portion 5460 and the flex or hinge portion 5420, and the length of the indicator arm 5450. The minimum engagement depth decreases the

further the flex or hinge portion 5460 is from the flex or hinge portion 5420, the greater the angle between the indicator arm 5450 and the fixed arm 5410, and the greater the length of the indicator arm 5450. When the clasp 5400 is closed without the indicator arm 5450 being engaged by the leaflet, the indicator arm 5450 moves beyond the moveable arm 5430. The indicator arm 5450 crossing the moveable arm 5430 forms a closed shape or an X-shape that is visible via imaging devices used to monitor implantation and deployment of the device, as can be seen in Figure 201. In addition, or instead, the indicator arm bounces or pulses when engaged with the valve leaflet when the heart beats. When the leaflet is inserted into the clasp 5400 beyond the minimum desired engagement depth, the leaflet pushes the indicator arm 5450 back toward the fixed arm 5410 such that the indicator arm 5450 does not reach or cross the moveable arm 5430 to form closed or the X-shape shown in Figure 201. Thus, the indicator arm 5450 indicates to an observer observing the installation via an imaging device that the leaflet is inserted into the opening 5406 beyond the minimum desired engagement depth.

[00521] Referring now to Figures 200-202, the example clasp 5400 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 200, the clasp 5400 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening 5406 of the clasp 5400 formed between the fixed and moveable arms 5410, 5430. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the moveable arm 5430 is actuated via actuation lines (not shown) as shown in Figures 201-202.

[00522] Referring now to Figure 201, when the moveable arm 5430 is actuated toward the fixed arm 5410, the leaflet 42, 44 may contact portions of the fixed and moveable arms 5410, 5430 without contacting the indicator arm 5450 when the engagement depth of the leaflet 42, 44 is less than the minimum desired engagement depth. Thus, the indicator arm 5450 extends to or beyond the moveable arm 5430 to form a closed shape or an X-shape with the moveable arm 5430. In addition, or instead, the indicator arm bounces or pulses when engaged with the valve leaflet when the heart beats. As can be seen in Figure 202, the indicator arm 5450 is prevented from crossing the moveable arm 5430 when the leaflet 42, 44 is inserted far enough into the clasp 5400. That is, the indicator arm 5450 is deflected by the leaflet 42, 44 to indicate that the leaflet 42, 44 has been inserted at or beyond the minimum engagement depth. In addition, or instead, the indicator arm bounces or pulses when engaged with the

valve leaflet when the heart beats. In some embodiments, actuation of the moveable arm 5430 also causes the barbed portion 5440 to engage and secure the leaflet 42, 44 within the barbed clasp 5400. If the indicator arm 5450 indicates that the leaflet 42, 44 is not inserted to the desired depth, the clasp 5400 can be opened to allow for repositioning of the leaflet 42, 44. As can be seen in Figure 202A, an indicator arm 5450A can optionally conform to the shape of the leaflet 42, 44 when engaged by the leaflet 42, 44 as the clasp 5400 is closed.

[00523] Referring now to Figures 206-214, an example clasp 5200 having an indicator arm 5250 with a shaped end 5260 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. The shaped end can have a variety of different shapes. For example, the shaped end can be round or coiled as illustrated, semi-circular, ovoid, polygonal, etc. Any shape that is visibly discernable from the remainder of the clasp can be used. Like the clasp 3500 described above, the clasp 5200 includes a fixed arm 5210, a flex or hinge portion 5220, a moveable arm 5230 having a barbed portion 5240 (though other friction-enhancing portions can be used), and an indicator arm 5220 connected to the moveable arm 5230 via an indicator flex or hinge portion 5290. The indicator arm 5250 includes a coil 5260 at its end opposite the indicator flex or hinge portion. The shaped end 5260 can have a laser cut pattern or other indicators, such as radiopaque indicators, to increase its visibility when being imaged. The indicator arm is used to indicate whether the leaflet has reached a desired depth. The moveable arm can have at least one opening 5280 in it, through which the indicator arm passes through. Thus, the shaped end 5260 of the indicating arm 5250 will not indicate that the native leaflet has reached a minimum desired engagement depth until the leaflet is inserted at or beyond the location of the shaped end 5260. Once the leaflet 42, 44 has reached the desired engagement depth, the indicator arm 5250 is pressed toward the moveable arm 5230 by the leaflet 42, 44, causing the shaped end 5260 of the indicator arm to pass through the opening 5280 of the moveable arm 5230. Thus, the shaped end 5260 positioned on the exterior of the moveable arm, as opposed to the interior space between the moveable and fixed arms 5230, 5210 of the clasp, indicates that the leaflet 42, 44 has reached a sufficient depth. The clasp 5200 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00524] Referring now to Figures 206 and 207, a clasp 5200 having an indicator arm 5250 with a shaped end 5260 in a resting state is illustrated. The clasp can be a laser cut clasp or any other embodiment of clasp described herein. The indicator arm 5250 can be made from a

flat sheet that is shape set to have a shaped end 5260. The flat sheet can be laser cut. In some example embodiments, the indicator arm can be braided wires and/or a bundle of wires, which are shape set. The indicator arm can be a separate piece attached to the clasp, as described in the example embodiment of Figures 206-214, or it can be laser cut from the same sheet of material as the clasp. As a separate piece, the indicator arm can have a base 5270 that is optionally a flex or hinge region of the indicator arm, at the end of the indicator arm that is attached to the moveable arm 5230. As is illustrated by Figure 207, the clasp is open, and the indicator arm is in a resting state. In its resting state, the shaped end 5260 is positioned on the side of the moveable arm facing the fixed arm.

[00525] Referring now to Figures 208-209, the clasp 5200 is in a closed position. In Figure 208, the clasp is closed without a leaflet between the moveable arm 5230 and the fixed arm 5210. Because there is no leaflet that has reached a sufficient depth within the clasp in Figure 208, the indicator arm 5250 is in its resting configuration, and the shaped end 5260 is inside the outer boundaries of the profile of the clasp. In Figure 209, a leaflet 42, 44 has been captured by the clasp. The leaflet is sufficiently deep within the clasp, as indicated by the shaped end 5260 of the indicator arm 5250 being positioned exterior to the profile of the moveable arm 5230 of the clasp. The leaflet has pushed the indicator arm towards the moveable arm, such that the indicator arm pivoted at the indicator arm hinge region 5230, and the shaped end 5260 has passed through the opening 5280 (visible in Figure 206) of the moveable arm 5230.

[00526] Referring now to Figures 210-214, schematic views of the example embodiment of a clasp having an indicator arm with a shaped end such as that illustrated in Figures 208-209, are shown. Figures 210-211 illustrate the clasp 5200 in an open position where the indicator arm 5250 having a shaped end 5260 is in a resting configuration, that can be shape set as explained above.

[00527] Referring now to Figures 212-214, the example clasp 5200 is shown being deployed within a native valve to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 212, the clasp 5200 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening of the clasp 5200 formed between the fixed and moveable arms 5210, 5230. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the moveable arm 5230 is actuated to close the clasp, such that the moveable arm and the fixed arm move closer together. The indicator arm is free to flex, move, or pivot about the

indicator flex or hinge portion 5290 when pressure is applied to the indicator arm, either by leaflet 42, 44 or the fixed arm 5210.

[00528] Referring now to Figure 213, when the moveable arm 5230 is actuated to close the clasp on the leaflet 42, 44, the indicator arm will not be forced out of its resting configuration if the leaflet is not sufficiently deep within the clasp. That is, when the leaflet is not positioned sufficiently deep within the clasp, the indicator arm and shaped end 5260 will remain in its resting configuration between the moveable arm and the fixed arm.

[00529] Referring now to Figure 214, the moveable arm 5230 has been actuated to close the clasp on the leaflet 42, 44, when the leaflet is positioned sufficiently deep within the clasp. The indicator arm 5250 and its shaped end 5260 indicate to the operator that the leaflet 42, 44 is sufficiently deep. When the leaflet is sufficiently deep and the moveable arm 5230 is actuated, the leaflet applies pressure to the indicator arm. This pressure moves the indicator arm 5250 towards the moveable arm such that the shaped end 5260 of the indicator arm 5250 passes through the opening 5280 of the moveable arm, to the side of the moveable arm facing away from the fixed arm.

[00530] Referring now to Figures 167-168, an example clasp 5200 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 5200 includes a fixed arm 5210, a flex or hinge portion 5220, and a moveable arm 5230 having a barbed portion 5240 (though other friction-enhancing portions can be used). The moveable arm can include an optional indicator 1672 that can be positioned between the flex or hinge portion 5220 and the barbed portion 5240. In one embodiment, the indicator 1672 can be positioned closer to the flex or hinge portion than the barbed portion.

[00531] The fixed arm 5210 can include a rotating component 1671 to draw the leaflet tissue into the clasp, in a direction towards the flex or hinge portion 5220. The rotating component 1671 can be positioned on the fixed arm (and/or the moveable arm) at a position that is between the flex or hinge portion and the end of the fixed arm farthest from the flex portion or hinged portion. The rotating component is schematically illustrated and can be a variety of different rotating components. In Figures 167-168, the rotating component 1671 is a gear such as a worm gear or a crank, that can rotate to pull the tissue in towards the flex portion or hinged portion of the clasp.

[00532] In operation, the leaflet is captured by closing the clasp on it. The optional indicator can be used to determine whether the leaflet is positioned at a sufficient depth within the

clasp. The leaflet is not sufficiently deep within the clasp if it is not contacting the indicator 1672. Thus, the indicator 1672 will not indicate that the leaflet 42, 44, has reached the desired engagement depth until the leaflet is inserted at or beyond the location of the indicator 1672.

[00533] The rotating component 1671 rotates and pulls in the leaflet tissue. After the clasp is closed onto leaflet tissue, the rotating component 1671 can be actuated without reopening the clasp to pull the leaflet tissue to the desired depth within the clasp by rotating the rotating component.

[00534] The rotating component 1671 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00535] Referring now to Figures 169-171, the example clasp 5200 having a rotating component 1671 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 169, the clasp 5200 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening 5206 of the clasp 5200 formed between the fixed and moveable arms 5210, 5230. To draw the leaflet in to the desired engagement depth once the clasp is closed, the rotating component is rotated to pull the leaflet in towards the indicator 1672 as shown in Figures 170-171.

[00536] Referring now to Figure 170, when the moveable arm 5230 is actuated to push the leaflet 42, 44 against the fixed arm 5210, the leaflet 42, 44 may contact a portion of the fixed arm 5210 and at least a portion of the rotating element 1671 without contacting the indicator 1672 when the engagement depth of the leaflet 42, 44 is less than the minimum desired engagement depth. As can be seen in Figure 171, the rotating component 1671 has been rotated to pull the leaflet tissue into the clasp. In Figure 171 the leaflet is pulled partially into the clasp. The leaflet is sufficiently pulled into the clasp by the rotating component when the leaflet contacts the indicator. In some embodiments, actuation of the moveable arm 5230 also causes the barbed portion 5240 to engage and secure the leaflet 42, 44 within the barbed clasp 5200. If the indicator is not contacted by the leaflet, as in Figure 171, the rotating component 1671 can be rotated more to pull the leaflet farther in to the desired depth within the clasp.

[00537] Referring now to Figures 172-173, an example clasp 5200 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp

3500 described above, the clasp 5200 includes a fixed arm 5210, a flex or hinge portion 5220, and a moveable arm 5230 having a barbed portion 5240 (though other friction-enhancing portions can be used). The clasp can include a flexible indicator 1731 connected to the fixed arm 5210 at a fixed end 1732 and slidably positioned at a moveable end 1733 on the moveable arm 5230. The flexible indicator can be connected to the fixed arm at a location between the barbed portion 5240 and the flex or hinge portion 5220, at the end farther away from the flex or hinge portion 5220. The flexible indicator can be slidably positioned on the moveable arm at a location anywhere from the flex portion or hinged portion 5220 to the barbed portion 5240. The flexible indicator can have a hammock-like configuration in that it is attached to the arms of the clasp and has a slack region in between its ends that are connected to the arms. The indicator can be a suture, a nitinol wire, cloth, and/or a nitinol hammock that the tissue moves as it is captured and moves deeper into the clasp. If the leaflet tissue is not captured at a sufficient depth, the hammock is not moved, and its moveable end does not glide along the moveable arm. As tissue is captured, the mobile end of the flexible indicator can slide along the arm towards the flex portion or hinged portion 5220 of the apex of the clasp. The sliding of the indicator indicates the depth of the leaflet that has been captured by the clasp. There can be a spring 1734 along the moveable arm between the mobile end of the flexible indicator and the flex portion or hinged portion of the clasp. The spring can return the flexible feature to its rest state if the clasp is reopened to reposition it on the native leaflet. In the schematic illustrations the spring is drawn as a coil spring around the exterior of the moveable arm. However, the spring can be any known spring, and can be positioned along the interior surface of the arm of the clasp along which it extends. In some example embodiments, the flexible indicator can be shape set to return to a resting state where its moveable end moves away from the flex portion or hinged portion 5220. In some example embodiments, the flexible indicator can be fixed to the moveable arm, and slidably positioned on the fixed arm.

[00538] Referring now to Figures 174-176, the example clasp 5200 having a flexible indicator 1731 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 174, the clasp 5200 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening 5206 of the clasp 5200 formed between the fixed and moveable arms 5210, 5230.

[00539] Referring now to Figure 175, when the moveable arm 5230 is actuated to push the leaflet 42, 44 against the fixed arm 5210, the leaflet 42, 44 may contact a portion of the fixed arm 5210 and at least a portion of the flexible indicator 1731 when the engagement depth of the leaflet 42, 44 is less than the minimum desired engagement depth. As can be seen in Figure 175, the flexible indicator has not been flexed by the leaflet in the direction of the flex portion or hinged portion 5220. This is indicated to the operator because the slidable end of the flexible indicator has not moved in a direction from the barbed portion 5240 to the flex or hinge portion 5220 of the clasp.

[00540] Referring now to Figure 176, the leaflet 42, 44 is pulled farther into the clasp 5200. The flexible feature is engaged by more of the leaflet tissue than in Figure 175, because the leaflet is farther into the clasp. This has pulled the moveable end 1733 of the flexible indicator 1731 down along the length of the moveable arm, in a direction from the barbed portion 5240 towards the flex or hinge portion 5220. The spring 1734 is compressed due to the sliding of the moveable end of the flexible feature. With the leaflet in this position, the barb 5240 is engaged with the leaflet tissue as well.

[00541] Referring now to Figures 177—178, a schematic view of an example clasp 5200 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 5200 includes a fixed arm 5210, a flex or hinge portion 5220, and a moveable arm 5230. At the free end of the moveable arm is a rotating wheel 1771 with directional barbs 5240. The wheel 1771 can rotate by a line loop, such as a suture loop, to help draw a native mitral valve leaflet into the clasp, toward the flex or hinge portion 5220. The suture loop operates similar to a conveyor roller and rotates the wheel. The wheel can be a cog wheel or a spool, and the suture line can be used to rotate the wheel and draw the leaflet into the clasp. The barbs 5240 on the wheel engage with the leaflet tissue, and when the wheel is rotated in a first direction, the barbs pull the leaflet into the clasp. Should the leaflet be pulled too far into the clasp, the wheel can be rotated in a second direction, opposite to the first direction, to decrease the depth of which the leaflet is inserted into the clasp.

[00542] The leaflet depth can be indicated by an echo evaluation of regurgitation through the valve. After at least one of the barbs on the wheel engages with the leaflet, the wheel is rotated in the direction of arrow 1781. The rotation of the wheel translates to a linear distance that can be used to indicate to the operator that there is adequate engagement of the leaflet within the clasp. In this way, the operator can determine how far the leaflet has been

pulled within the clasp by the number of rotations of the wheel. The wheel can have a clutch stop mechanism to provide a maximum distance and/or force into the clasp which the leaflet can be pulled.

[00543] Referring now to Figures 179-181, the example clasp having a barbed wheel 1771 is shown being deployed within a native valve to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44.

Referring now to Figure 179, the clasp 5200 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening 5206 of the clasp 5200 formed between the fixed and moveable arms 5210, 5230. To draw the leaflet in to the desired engagement depth once the clasp is closed, the wheel 1771 is rotated in the direction of arrow 1781 to pull the leaflet in towards the flex portion or hinged portion 5220 of the clasp, as shown in Figures 180-181. The wheel can be rotated in the direction of arrow 1781 by moving the actuating line in the direction of arrows 1782.

[00544] Referring now to Figure 180, when the moveable arm 5230 is actuated to push the leaflet 42, 44 against the fixed arm 5210, the leaflet 42, 44 may contact a portion of the fixed arm 5210 and at least a portion of the rotating element 1771 without contacting the (optional) indicator 1672 when the engagement depth of the leaflet 42, 44 is less than the minimum desired engagement depth. As can be seen in Figure 181, the rotating component 1771 has been rotated in the direction of arrow 1782 to pull the leaflet tissue into the clasp a sufficient distance as indicated by the indicator 1672. In Figure 180 the leaflet is pulled partially into the clasp. In one example embodiment, the leaflet is sufficiently pulled into the clasp by the rotating component when the leaflet contacts the indicator. In some embodiments, actuation of the moveable arm 5230 also causes the barbed portion 5240 to engage and secure the leaflet 42, 44 within the barbed clasp 5200. If the indicator is not contacted by the leaflet, as in Figure 180, the rotating component 1771 can be rotated more to pull the leaflet farther in to the desired depth within the clasp. Referring now to Figure 181, the leaflet is pulled farther into the clasp. If the operator wants to lessen the distance the leaflet has been pulled into the clasp, the operator can rotate the wheel 1771 in the opposite direction, by moving the actuating lines in the direction of arrows 1811.

[00545] Referring now to Figures 182-183, a schematic view of an example clasp 5200 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 5200 includes a fixed arm 5210, a flex or hinge portion 5220, and a moveable arm 5230. Positioned on the moveable arm is a hinged

barb(s) 5240 pivotally and/or slidably attached to the moveable arm. The hinged barb 5240 is further connected to a spring 1821. The hinged barb and spring pull the leaflet toward the flex portion or hinged portion 5220 and into the clasp. The barb(s) can move back and forth along the length of the clasp. The spring can be pulled on by a line 1822 to angle the barb(s) to disengage tissue and pulls the barb out to full length. That is, to the farthest point along the moveable arm away from the flex portion or hinged portion 5220. Releasing the suture line 1822 causes the spring to angle the barb to engage tissue and/or allow the spring to retract, pulling the tissue in to the clasp, towards the flex portion or hinged portion 5220. The barb(s) can be angled and positioned by applying tension to the suture line. Changing the angle of the barb 5240 permits the barb to atraumatically slide up the leaflet as the leaflet 42, 44 is positioned further into the clasp, towards the flex or hinge portion 5220. The changing angle of the barb 5240 changes when tension is applied to the leaflet in a direction away from the flex or hinge portion 5220, so that the barb engages the leaflet and can prevent it from being removed from the clasp. The change in the angle of the barb 5240 can be passive, and the angle can change to an angle that engages the leaflet by releasing the moveable arm 5230 on to the leaflet to close the clasp on the leaflet. The release of the moveable arm 5230 releases the tension in the spring 1821, thereby changing the angle of the barb.

[00546] There can be an optional second moveable arm 1831 that is connected to the clasp at the flex or hinge portion 5220 and is exteriorly positioned to the moveable arm 523 having the barb(s) and spring. The second moveable arm 1831 can be dropped and/or lowered onto the moveable arm 5230 once the tissue is pulled into the leaflet, thereby completing the process of securing the leaflet into the clasp.

[00547] Referring now to Figures 184-186B, the example clasp having optionally hinged barbs 5240 and a spring 1821 to provide a mechanism for drawing a leaflet in to the clasp. The clasp 5200 is shown being deployed within a native valve to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 184, the clasp 5200 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening 5206 of the clasp 5200 formed between the fixed and moveable arms 5210, 5230. Figure 185 illustrates the clasp 5200 in a closed position, where the barbs 5240 have engaged leaflet tissue. In this position, the suture line 1822 is taught and the spring 1821 extended by the line 1822.

[00548] Referring now to Figures 186A and 186B, the leaflet is pulled into the clasp towards the flex portion or hinged portion 5220 by relaxing the portion of the suture that is connected

to the spring, allowing the spring to pull the barb 5240 and leaflet into the clasp. In the illustrated example, the barb is optionally angled down towards the flex or hinge region of the clasp, holding the leaflet tissue in place. The suture line can be slackened and pulled taught as many times as is necessary to properly engage the leaflet in the clasp. Once the leaflet is engaged positioned, as illustrated in Figure 186B, the optional second moveable arm is lowered onto the first moveable arm, to further secure the leaflet.

[00549] Referring now to Figures 187-188, a schematic view of an example clasp 5200 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 5200 includes a fixed arm 5210, a flex or hinge portion 5220, and a moveable arm 5230. Positioned on the moveable arm is a set of mobile barbs 5230 attached to a belt 1871 or other rotating mechanism and are moveable in a conveyor belt fashion. The illustrated wheels 1872 are rotatably connected to the moveable arm 5240 of the clasp at two points. One of the wheels 1872 of the conveyor belt is rotatably connected to the moveable arm at a first point that is closer to the flex portion or hinged portion 5220 and the second wheel is attached to the moveable arm to the second point, which is closer to the free end of the moveable arm.

[00550] One of the wheels 1872 can be rotated by an actuator line (see Figures 177-181) to help draw a native mitral valve leaflet into the clasp, toward the flex portion or hinged portion 5220. Similar in operation to the embodiment described in Figures 177-181, the barbs 5240 on the belt 1871 engage with the leaflet tissue, and when the belt is rotated in a first direction, indicated by arrow 1881, the barbs pull the leaflet into the clasp. Should the leaflet be pulled too far into the clasp, the wheel can be rotated in a second direction, indicated by arrow 1882, opposite to the first direction, to decrease the depth of which the leaflet is inserted into the clasp.

[00551] The leaflet depth can be indicated by an echo evaluation of regurgitation through the valve. After at least one of the barbs on the wheel engages with the leaflet, the wheel is rotated. The rotation of the wheel and belt translates to a linear distance that can be used to indicate to the operator that there is adequate engagement of the leaflet within the clasp. In this way, the operator can determine how far the leaflet has been pulled within the clasp by the number of rotations of the wheel. At least one-wheel 1872 can have a clutch stop mechanism to provide a maximum distance into the clasp which the leaflet can be pulled.

[00552] Referring now to Figures 189-191, the example clasp having a rotating belt 1871 with barbs 5240 is shown being deployed within a native valve to secure an implantable device

(not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 179, the clasp 5200 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening 5206 of the clasp 5200 formed between the fixed and moveable arms 5210, 5230. To draw the leaflet into the desired engagement depth once the clasp is closed, the wheel 1872 is rotated in the direction of arrow 1881 to pull the leaflet in towards the flex portion or hinged portion 5220 of the clasp, as shown in Figures 190-191. The wheel can be rotated in the direction of arrow 1881 by moving an actuating line as explained with respect to the embodiment of Figures 177-181.

[00553] Referring now to Figure 190, when the moveable arm 5230 is actuated to push the leaflet 42, 44 against the fixed arm 5210, the leaflet 42, 44 may contact a portion of the fixed arm 5210 and at least a portion of the rotating belt 1871 when the engagement depth of the leaflet 42, 44 is less than the minimum desired engagement depth. As can be seen in Figure 191, the rotating component 1872 has been rotated in the direction of arrow 1881 to pull the leaflet tissue into the clasp a sufficient distance in Figure 190 the leaflet is pulled partially into the clasp. In some embodiments, actuation of the moveable arm 5230 also causes the barbed portion 5240 to engage and secure the leaflet 42, 44 within the barbed clasp 5200. The belt 1871 can be rotated more to pull the leaflet farther in to the desired depth within the clasp. Referring now to Figure 191, the leaflet is pulled farther into the clasp. If the operator wants to lessen the distance the leaflet has been pulled into the clasp, the operator can rotate the belt 1871 in the opposite direction, as indicated by arrow 1882.

[00554] In some example embodiments, a sensor 24200 can be used to determine whether a leaflet 20, 22 is sufficiently inserted into a clasp 130, which can be any of the clasps disclosed herein or any other clasp. The sensor 24200 can take a wide variety of different forms. The sensor 24200 can be a sensor that senses electrical, pressure, positional and/or optical characteristics of its surroundings. For example, an electrical sensor can sense resistance, capacitance, current, pressure, contact, opacity, and/or voltage. The sensor can be a wired sensor or a wireless sensor. The sensor 24200 can be configured to be removed from the device 100 and the patient or the sensor 24200 or a portion of the sensor can be configured to be left with the device 100 (See Figure 260) after the device 100 is implanted in a patient. The device 100 can be any of the devices disclosed herein or any valve repair device.

Figures 243-247 illustrate an example embodiment where sensors 24200 are provided on moveable arms 134 of the clasps 130. In Figure 242, paddle portions 122 and the clasps 130

are open. The clasps 130 are positioned to grasp the leaflets 20, 22, but not at a position where the leaflets are sufficiently inserted into the device. In Figure 243, the paddle portions 122 and the clasps are in a partially closed position. The leaflets 20, 22, are still not sufficiently inserted into the clasps. In Figure 244, one of the clasps 130 is closed and the sensor 24200 on the closed clasp is spaced apart from the leaflet 20. The sensor 24200 provides a signal (or no signal) in response to spacing between the sensor on the closed clasp and the leaflet 20. This signal indicates that the leaflet is not sufficiently inserted into the closed clasp 130. Referring to Figure 245, the clasp 130 is reopened and the positions of both clasps are adjusted, such that the leaflets 20, 22 become disposed in the clasps 130 at a sufficient depth. Referring to Figure 246, one of the clasps 130 is closed and the sensor 24200 on the closed clasp contacts the leaflet 20. The sensor 24200 provides a signal (or no signal) in response to contact between the sensor on the closed clasp and the leaflet 20. This signal indicates that the leaflet is sufficiently inserted into the closed clasp 130. Referring to Figure 247, the second clasp 130 is closed and the sensor 24200 on the second clasp contacts the leaflet 22. The sensor 24200 on the second clasp provides a signal (or no signal) in response to contact between the sensor on the second closed clasp and the leaflet 20. This signal indicates that the leaflet 22 is sufficiently inserted into the closed clasp 130. If the second sensor were spaced apart from the leaflet 22, the second sensor would provide a signal indicating that the second leaflet was not at an appropriate depth and the second clasp could be reopened and repositioned on the leaflet 22.

[00555] Figures 248-253 illustrate an example embodiment where sensors 24200 are provided on fixed arms 132 of the clasps 130. In Figure 248, paddle portions 122 and the clasps 130 are open. The clasps 130 are positioned to grasp the leaflets 20, 22, but not at a position where the leaflets are sufficiently inserted into the device. In Figure 249, the paddle portions 122 and the clasps are in a partially closed position. The leaflets 20, 22, are still not sufficiently inserted into the clasps. In Figure 250, one of the clasps 130 is closed and the sensor 24200 on the closed clasp is spaced apart from the leaflet 20. The sensor 24200 provides a signal (or no signal) in response to spacing between the sensor on the closed clasp and the leaflet 20. This signal indicates that the leaflet is not sufficiently inserted into the closed clasp 130. Referring to Figure 251, the clasp 130 is reopened and the positions of both clasps are adjusted, such that the leaflets 20, 22 become disposed in the clasps 130 at a sufficient depth. Referring to Figure 252, one of the clasps 130 is closed and the sensor 24200 on the closed clasp contacts the leaflet 20. The sensor 24200 provides a signal (or no signal) in response to contact between the sensor on the closed clasp and the leaflet 20. This

signal indicates that the leaflet is sufficiently inserted into the closed clasp 130. Referring to Figure 253, the second clasp 130 is closed and the sensor 24200 on the second clasp contacts the leaflet 22. The sensor 24200 on the second clasp provides a signal (or no signal) in response to contact between the sensor on the second closed clasp and the leaflet 20. This signal indicates that the leaflet 22 is sufficiently inserted into the closed clasp 130. If the second sensor were spaced apart from the leaflet 22, the second sensor would provide a signal indicating that the second leaflet was not at an appropriate depth and the second clasp could be reopened and repositioned on the leaflet 22.

[00556] Figures 254-259 illustrate an example embodiment where sensors 24200 are provided on fixed arms 132 and moveable arms of the clasps 130. In Figure 254, paddle portions 122 and the clasps 130 are open. The clasps 130 are positioned to grasp the leaflets 20, 22, but not at a position where the leaflets are sufficiently inserted into the device. In Figure 255, the paddle portions 122 and the clasps are in a partially closed position. The leaflets 20, 22, are still not sufficiently inserted into the clasps. In Figure 256, one of the clasps 130 is closed and two sensors 24200 on the closed clasp contact one another. The sensors 24200 provide a signal (or no signal) in response to the sensor-to-sensor contact. This signal indicates that the leaflet is not sufficiently inserted into the closed clasp 130. Referring to Figure 257, the clasp 130 is reopened and the positions of both clasps are adjusted, such that the leaflets 20, 22 become disposed in the clasps 130 at a sufficient depth. Referring to Figure 258, one of the clasps 130 is closed and the sensors 24200 on the closed clasp contact the leaflet 20 and/or are spaced apart by the leaflet 20. The sensors 24200 provide a signal (or no signal) in response to contact between the sensors on the closed clasp and the leaflet 20 and/or in response to the spacers being spaced apart. This signal indicates that the leaflet is sufficiently inserted into the closed clasp 130. Referring to Figure 259, the second clasp 130 is closed and the sensors 24200 on the second clasp contacts the leaflet 22 and/or the sensors are held apart by the leaflets. The sensors 24200 on the second clasp provide a signal (or no signal) in response to contact between the sensors on the second closed clasp and the leaflet 20 and/or in response to being spaced apart. This signal indicates that the leaflet 22 is sufficiently inserted into the closed clasp 130. If the sensors on the second clasp contacted one another, the second pair of sensors would provide a signal indicating that the second leaflet was not at an appropriate depth and the second clasp could be reopened and repositioned on the leaflet 22.

[00557] In one example embodiment, the sensors 24200 are connected to communication lines 26000, such as wires and/or optical fibers. The communication lines 26000 can be routed to the sensors in a wide variety of different ways. In the example illustrated by Figures 260 and 261, complimentary sensors 24200 are disposed on the moveable and fixed arms 134, 132 of the clasp 130. Communication lines 26000 that are connected to the sensors 24200 on the moveable arms 134, extend from the moveable arms and through the implant catheter 102. Communication lines 26000 that are connected to sensors on the fixed arms 132 extend from the fixed arms 132, through an optional coaption member 110, and through the implant catheter. The communication lines 26000 extend from the device, in the patient's heart, through the catheter 102, and out of the patient's body, so that proper leaflet insertion can be monitored. The sensors shown in Figures 260 and 261 can be used in the manner described by Figures 254-259 to detect proper insertion and/or capture of the leaflets 20, 22 in the clasp 130.

[00558] Figures 262 and 263 illustrates an example embodiment where sensors 24200 are connected to the moveable arms 130 and to the control wire or shaft 112. In this illustrated example, a communication line 26000 is connected to the sensor on the control wire or shaft 112 and extends through the coaption element 110, and through the catheter 102. Communication lines 26000 that are connected to the sensors 24200 on the moveable arms 134 extend from the moveable arms and through the implant catheter 102. The sensors 24200 can detect proper leaflet insertion based on the distances between the sensors on the moveable arms 134 and the sensor on the control wire 112.

[00559] In some example embodiments, multiple sensors 24200 can be included to determine how far the leaflets 20, 22 are inserted into the clasp. Figures 264 and 265 illustrate example embodiments that are similar to the embodiments illustrated by Figures 262 and 263 where the moveable arm 134 of the clasp 130 includes multiple sensors for detecting the insertion depth of the leaflets 20, 22 in the clasp 130. For example, each sensor on the movable arm 134 can be used to sense contact with a leaflet 20, 22 to indicate the insertion depth of the leaflet in the clasp.

[00560] Figure 266 illustrates an end of an implant catheter 102 and a coupler. Clasp actuation lines 116 extend through lumens 26600 in the catheter 102. The control wire or shaft 112 extends through a central lumen 26602 of the catheter. In one example embodiment, communication lines 26000 extend through the lumens 26600, 26602 to the sensors 24200. In one example embodiment, the control wire or shaft 112 is used as one of

the communication lines 26000. In one example embodiment, the clasp actuation lines 116 act as communication lines 26000 or act as part of a communication line.

[00561] As mentioned above, the sensors 24200 can take a wide variety of different forms and the leaflets 20, 22 can be detected in a wide variety of different ways. In one example embodiment, the sensors 24200 comprise electrodes. A short, subthreshold (nA - μ A), biphasic current can be applied via the electrodes incorporated in the implant to obtain a measurement of Impedance (R_z) and/or Capacitance (C). Impedance and/or capacitance changes before, during and after grasping of the leaflet with the device can be used to indicate the quality and quantity of the implant's grasp onto the leaflets.

[00562] In one example embodiment, Impedance can be measured by providing a known current ($R_z = U/I$) and monitoring the voltage with a current voltage converter. The capacitance (C) can be derived e.g. from the time constant (τ) of the voltage change ($C = \tau/R_z$) in response to the provided current I.

[00563] In one example embodiment, Impedance rise indicates that a predetermined amount of native valve leaflet, such as 6mm, is inserted into the clasp (See Figure 259). Impedance drop (or short circuit – See Figure 256) will indicate no or less than the predetermined amount of leaflet has been captured.

Capacitance increase indicates that the predetermined amount of native valve leaflet has been captured. In addition, the capacitance increase can be used to determine thickness of the captured leaflet. Detected thicknesses outside of an expected range can be used to identify a curled or rolled-in leaflet.

[00564] Referring back to Figures 260 and 261, in one example embodiment, the two sensors 24200 on the fixed arms 132 can be ground electrodes and the two sensors 24200 on the moveable arms 134 can be stimulation electrodes (or vice versa). The position of the stimulation electrodes is aligned with the positions of the ground or reference electrodes when the clasp is closed (See Figure 256). In one example embodiment, biphasic, subthreshold current flows from each stimulation electrode to each ground or reference electrode.

[00565] Referring back to Figures 262 and 263, two sensors 24200 on the moveable arms 134 can be stimulation electrodes and one sensor 24200 on the control wire 112 can be a ground electrode. That is, there is only a single ground or reference electrode in this embodiment. In the illustrated example, the ground or reference electrode is located at the distal or ventricular tip of the implant 100. In this example embodiment, the current flows from the

stimulation electrodes to the ground or reference electrode. This current can be monitored during deployment of the implant 100 to detect proper leaflet insertion and capture by the clasps.

[00566] In one example embodiment, the electrodes described with respect to Figures 260-263 are electrically isolated from a metal frame or backbone of the device. This isolation prevents short circuiting between the stimulation and ground electrodes when the stimulation and ground electrodes are spaced apart. The electrodes can take a wide variety of different forms. For example, the electrodes can be uninsulated ends of platinum wires (simply blunt or coiled up), discs, patches of platinum or another conductive material.

[00567] In one example embodiment, the current can be applied to the electrodes in phases. Referring to Figure 267, the current 26700 between the stimulation electrode(s) and the ground or reference electrodes can be biphasic. The phases can each last a few to hundreds of a milliseconds (msec) with an interphase interval 26702 and are equal in charge. An external amplifier including a current voltage converter (common commercial products e.g. like in a patch clamp amplifier) can be used to measure the voltage. As a result, the impedance can be calculated in real time. The amplitude of the current is subthreshold and can be in the range of 0.1 - 100 μ Ampere. The capacitance can be derived from the time (π) the voltage increases according to the formula:

$$C = R * \pi$$

Where C is capacitance, R is impedance, and π is rise time (of exponential function).

[00568] Referring to Figure 268, impedance changes can be observed depending on the configuration of the implant and the insertion length of the leaflet. In region 26800, the implant is ready to capture the native valve leaflet. In region 26802, if enough leaflet is inserted impedance will rise when the clasps are dropped. In region 26804, the impedance will further rise when the implant is closed and reaches a plateau. In regions 26806, the impedance will periodically change from this plateau according to the opening and closing of the mitral valve.

[00569] Referring to Figure 269, in region 26800, the implant is ready to capture the native valve leaflet. In region 26900, if the leaflet is not inserted enough, impedance will decrease when dropping the clasps. In region 26902, the impedance will even further decrease and reach a floor 26904 when the implant is subsequently closed. No or very little impedance fluctuation can be observed when the mitral valve is opening and closing. These impedance

changes therefore allow direct and instantaneous evaluation of the quality of the grasp or capture.

[00570] The second parameter besides impedance R that can be measured is the capacitance C between stimulation electrode and the ground or reference electrode. Referring to Figure 270, in region 26800 low capacitance is observed in the capture ready configuration. Low capacitance is also observed when no leaflet is between the stimulation and ground or reference electrodes. In region 27000, when the leaflet is captured by the clasps, the capacitance rises. In region 27002, the paddles are closed, and the capacitance continues to rise. In regions 27004, the capacitance will periodically change according to the opening and closing of the mitral valve. Figure 271 is the same or substantially the same as Figure 270, except the leaflet is thicker or has curled or folded upon itself when captured by the clasp. As can be seen by comparing Figures 270 and 271, thinner leaflet results in higher capacitance and thicker leaflets or leaflet curling in lower capacitance. The capacitance can be related to the leaflet thickness (or folded leaflet thickness) according to the formula:

$$C = \epsilon_0 * \frac{A}{d} \text{ where:}$$

C is Capacitance. A is the Area of the capacitor plate (i.e. the size of the electrode). d is the distance between the electrodes. And, ϵ_0 is the electrical field constant.

[00571] In one example embodiment, to judge thickness, and flattening of the leaflet between clasp and paddle, the measured capacitance can be compared to norm values measured for known different leaflet thicknesses. Large differences can indicate curling or folding of one of the leaflets.

[00572] Referring now to Figures 272-274, schematic views of example embodiments of a clasp for use in an implantable prosthetic device, such as devices 100, 200, and 300 described above, are shown. Like the clasp 3500 described above, the clasp 5200 includes a fixed arm 5210, a flex or hinge portion 5220, and a moveable arm 5230 having an optional barbed portion 5240 and/or other type of friction-enhancing portion. Figure 272 illustrates a schematic view of a clasp 5200 that has one flexible indicator 1031 on the fixed arm that fits through an opening 6730 in the moveable arm 5230. Figure 273 illustrates a schematic view of a clasp that has two flexible indicators 1031 on the fixed arm that fit between two cutout openings 6730 on the moveable arm. When there are a plurality of flexible indicators, the flexible indicators can be aligned or offset along the length of the fixed arm.

[00573] In the example illustrated by Figure 274, the flexible indicator 1031 has a fixed end 27402 attached to the fixed arm 5210 and a free end 27404. In the example illustrated by Figure 274, the fixed end 27402 is farther away from the flex or hinge portion 5220 than the free end 27404. However, this orientation can be reversed. In an example embodiment, the flexible indicator 1031 is attached to the moveable arm 5230.

[00574] The flexible indicators 1031 can be part of the laser cut clasp or can be attached to the laser-cut clasp frame by welding or rivets or other known means. Figure 274 illustrates a side schematic view of the embodiments illustrated in Figures 272 and 273. From the side view, the clasp appears the same, whether there is one flexible indicator 1031 or two, since the two indicators are aligned in the illustrated example. In Figure 274, the clasp is in an open position and the flexible indicator is curved or bent into a “bump” configuration. Figures 274-277 also illustrate optional radiopaque indicators 1030 on the indicator 1031. The radiopaque indicator can be printed or attached as a separate piece of material to the indicator 1031. For example, the radiopaque material can be a coil made of platinum or another radiopaque material. The radiopaque indicator can be printed directly on the bump, a coil wrapped directly around the bump, or printed on a fabric covering the bump, or otherwise fixed to the bump. The radiopaque indicator is visible with fluoroscopy and/or other imaging techniques and can assist the user in determining whether the leaflet is properly positioned in the clasp.

[00575] Referring to Figures 275-277, the indicator 1031 deforms and/or is pressed through the fixed arm 5210 when the native leaflet tissue 42 or 44 is pressed against the indicator 1031 by the moveable arm 5230 to indicate that the leaflet tissue has reached a minimum desired engagement depth. Thus, the indicator 1031 will not indicate that the native leaflet 42, 44 has reached the desired engagement depth until the leaflet 42, 44 is inserted at or beyond the location of the indicator 1031. Once the leaflet 42, 44 has reached the desired engagement depth, actuation of the moveable arm 5230 squeezes the leaflet tissue 42, 44 against the indicator 1031 on the fixed arm 5210 to cause the indicator 1031 to flatten and thereby indicate that the leaflet 42, 44 has been inserted into the clasp 5200 at or beyond the desired engagement depth. The clasp 5200 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00576] Referring now to Figures 275-277, the example clasp 5200 illustrated in Figures 272-274 is shown being deployed within a native valve 40 to secure an implantable device (only

portions of inner paddles 122 (or 222 or 322) and outer paddles 120 (or 220, 320), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring to Figure 275, the clasp 5200 is shown in an open condition with a native leaflet 42 or 44 partially inserted into an opening of the clasp 5200 formed between the fixed and moveable arms 5210, 5230. In the example illustrated by Figure 275, all or substantially all of the indicator 1031 is disposed in the space between the fixed arm 5210 and the moveable arm 5230 then the clasp 5200 is open.

[00577] Referring now to Figure 276, when the moveable arm 5230 is closed to push the leaflet 42 or 44 against the fixed arm 5210, the leaflet 42 or 44 contacts a portion of the fixed arm 5210, while not contacting the indicator 1031 or only contacting a small portion of the indicator. In the example illustrated by Figure 276, all or substantially all of the indicator 1031 remains positioned on the side of the fixed arm 5210 that faces away from the inner paddle portion 120. This indicates that the engagement depth of the leaflet 42 or 44 is less than the minimum engagement depth.

[00578] In the insufficient leaflet engagement example illustrated by Figure 276, the indicator 1031 extends through the moveable arm 5230. In this example, a marker 1030 on a middle portion of the indicator 1030 is disposed on a side of the moveable arm 5230 that faces away from the fixed arm 5210 and a marker 1030 on the free end 27404 is in the space between the fixed arm 5210 and the moveable arm 5230. However, the indicator 1031, clasp 5200, and/or optional markers can be configured to indicate insufficient leaflet engagement in a wide variety of different ways.

[00579] Referring now to Figure 277, when the moveable arm 5230 is closed to push the leaflet 42 or 44 against the fixed arm 5210, the leaflet 42 or 44 contacts a substantial portion of the indicator, such as $\frac{1}{4}$, $\frac{1}{2}$, or more of the indicator 1031. In the example illustrated by Figure 277, a portion of the indicator 1031 is flattened and/or a portion of the indicator is pressed through the fixed arm 5210. This indicates that the engagement depth of the leaflet 42 or 44 is greater than or equal to the minimum engagement depth.

[00580] In the sufficient leaflet engagement example illustrated by Figure 277, the indicator 1031 extends through the fixed arm 5210 and the inner paddle 122. In this example, the portion of the indicator 1031 that extends through the fixed arm 5210 is disposed in a space between the inner paddle 122 and the outer paddle 120. As such, the indicator 1031 is completely disposed inside the device, such as the device 100, 200, 300. In this example, the marker 1030 on a middle portion of the indicator 1030 becomes adjacent to the fixed arm

5210 and the marker 1030 on the free end 27404 moves toward the outer paddle 120, in the space between the inner paddle 122 and the outer paddle 120. However, the indicator 1031, clasp 5200, and/or optional markers can be configured to indicate sufficient leaflet engagement in a wide variety of different ways.

[00581] Referring to Figures 278, 278A, 279, and 279A, in some example embodiments, one or more secondary markers 27830 can be included to determine how far the leaflets 42 or 44 are inserted into the clasp. The secondary markers 27830 can be formed in any of the ways that the markers 1030 are formed or the secondary markers can take other forms. Figures 278, 278A, 279, and 279A illustrate example embodiments that are similar to the embodiments illustrated by Figures 272-277 where the indicator 1031 includes one or more additional markers 27830 that indicate the insertion depth of the leaflets 20, 22 in the clasp 130. For example, each additional marker 27830 will cross the fixed arm 5210 at a predetermined amount of leaflet insertion. In Figure 278 an additional indicator 27830 that is closest to the flex or hinge 5220 crosses the fixed arm 5210 to indicate a first insertion depth. In Figure 279 the next additional indicator 27830 crosses the fixed arm 5210 to indicate another, deeper insertion depth.

[00582] The indicators 1031 shown in and described with respect to Figures 272-277 can take a wide variety of different forms and can be used with a wide variety of different clasps. For example, the indicators shown in Figure 272-277 can include any of the features of any of the indicators shown and described herein and can be used with any of the clasps shown and described herein.

[00583] Figures 280 and 281 illustrate one of the many different configurations that the clasp and indicator of Figures 272-277 can take. In the example illustrated by Figures 280 and 281, an example clasp 28000 and an indicator 1031 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, are shown. The clasp 28000 has a fixed arm 28010, a patterned flex portion or patterned hinge portion 28020, a moveable arm 28030 formed in the shape of a hoop or loop with a barbed portion 28040.

[00584] In the example illustrated by Figures 280 and 281, the indicator 1031 is formed separately from the clasp 28000. The indicator 1031 can be connected to the clasp in a wide variety of different ways. In the example illustrated by Figures 281-284, both the fixed arm 28010 of the clasp and the indicator 1031 are attached to the inner paddle 122.

[00585] In the example illustrated by Figures 280 and 281, the indicator 1031 includes a connector 28002, a flex or hinge portion 28060, an indicator arm 28050, and a marker

support 28004. The flex or hinge portion 28060 extends from the connector 28002. The indicator arm 28050 extends from the indicator flex or hinge portion 28060. The marker support 28004 is connected to the indicator arm 28050 by an optional flex or hinge portion 28006. In some example embodiments, the marker support 28004 is connected directly to the indicator arm 28050 or is part of the indicator arm 28050.

[00586] The clasp 28000 and indicator 1031 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein. For example, the clasp 28000 can be laser cut from a flat sheet or a tube of shape-memory alloy, such as Nitinol, and then shape-set into a desired shape.

[00587] The illustrated fixed arm 28010 has two tongue portions 28011 that each include holes 28012 for attaching the fixed arm 28010 to a paddle of an implantable device (See Figure 281). A central opening 28054 arranged between the tongue portions 28011 is wider than the indicator arm 28050 so that the indicator arm 28050 can pass through the fixed arm 28010 between the tongue portions 28011. In the example illustrated by Figure 281, the inner paddle 122 also includes a cutout or slot 28102 that the indicator arm 28050 passes through.

[00588] The patterned flex portion or patterned hinge portion 28020 is formed from a plurality of spring segments 28022 and cutouts 28024. The two tongue portions 28011 of the fixed arm 28010 extend from one end of the patterned flex portion or patterned hinge portion 28020 and the moveable arm 28030 extends from the other end of the flex or hinge portion 28020.

[00589] The moveable arm 28030 of the clasp 28000 has a hoop-like shape. The hoop-like shape of the moveable arm 28030 provides for a wider barbed portion 28040 that can include more barbs 28042 with the same or greater lateral spacing than other clasps. The wider spacing of the barbs 28042 improves capture of the native leaflets. The barbs 28042 are also longitudinally staggered as a result of their position on the hoop-like shape of the moveable arm 28030. That is, two center barbs are arranged further away from the flex or hinge portion 28020 and two outer barbs are arranged closer to the flex or hinge portion 28020.

[00590] In the example illustrated by Figures 280 and 281, the flex or hinge portion 28060 is bent, a central portion 28052 of the indicator arm 28050 is bent, and the flex or hinge portion 28006 is bent to form an inverted “V” or other “bump” shape. Referring to Figure 281, the fixed arm 28010 of the clasp 28000 and the connector 28002 are aligned and connected to the inner paddle 122. Once the fixed arm 28010 and the connector 28002 are connected to the inner paddle, the indicator arm 28050 extends into the interior of the hoop-shaped moveable

arm 28030 when the clasp is closed, and the indicator is not obstructed. In the examples illustrated by Figures 272-284, the indicator arm is passive or automatic (i.e. separate actuation of the indicator 1031, such as by an actuation line, relative to the clasp is not required).

[00591] The indicator flex or hinge portion 28060 allows the indicator arm 28050 to move relative to the fixed arm 28010 and the moveable arm 28030. This facilitates detection of the depth of engagement of the native leaflet 42 or 44 arranged between the moveable arm 28030 and the fixed arm 28010 of the clasp 4400. The indicator flex or hinge portion 28060 can be similar to the patterned flex/hinge portion 28020 and can be formed from a series of spring segments 28062 and cutouts 28064 as illustrated. In some embodiments, the spring force of the indicator flex or hinge portion 28060 is less than the pinching force imparted to the moveable arm 28030 by the flex or hinge portion 4420.

[00592] Referring now to Figures 281-283, the clasp 28000 is shown with the indicator arm 28050 in a fully deployed or extended position. That is, the furthest extent that the indicator arm 28050 is capable of reaching when the indicator arm 28050 does not engage with the leaflet tissue during actuation. In the fully actuated position, the indicator arm 28050 crosses the moveable arm 28030 that is visible via imaging devices so that the operator knows that the indicator arm 28050 has not engaged the leaflet (Figure 282) or not properly engaged the leaflet (Figure 283).

[00593] Referring now to Figure 284, the clasp or barbed clasp 28000 is shown with the indicator arm 28050 in an engaged position. That is, the position that the indicator arm 28050 is moved by the leaflet 42 or 44. In the closed position, the indicator arm 28050 no longer crosses the moveable arm 28050 and extends past the fixed arm 28010 and into the space between the inner paddle 122 and the outer paddle 120. Thus, the operator knows that the indicator arm 28050 has engaged the leaflet tissue 42 or 44 when the indicator arm 28050 has been moved such that no indicator arm is visible past the clasp moveable arm 28030 and a portion of the moveable arm extends past the clasp fixed arm 28010 when the clasp 28000 is viewed with an imaging device. In addition, or instead, the indicator arm 28050 can be optically monitored to detect pulsing, jumping, and/or flexing of the indicator arm as the heart beats. This jumping, bouncing and/or flexing of the indicator arm indicates to the operator that the indicator arm has engaged leaflet tissue.

[00594] Still referring to Figure 284, the clasp 28000 is shown with the moveable arm 28030 in a closed position. When the clasp 28000 is closed, the moveable arm 28030 exerts a

pinching force that retains the native leaflet tissue within the clasp 28000. The clasp 28000 is biased in the closed direction by the shape-setting of the moveable arm 28030 in a preloading position.

[00595] The example clasp 28000 can be deployed within a native valve 40 to secure the implantable device, such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44 in any of the manners described herein. The clasp 28000 is opened with a native leaflet 42, 44 partially inserted into the opening of the clasp 28000 formed between the fixed and moveable arms 28010, 28030. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the clasp 28000 is closed or partially closed. In Figure 283, because the leaflet 42, 44 is not at or beyond the minimum engagement depth the indicator arm 28050 misses the leaflet 42, 44 and a portion of the indicator arm moves to a position that is beyond the movable arm 28010 of the clasps 28000. In Figure 284, because the leaflet 42, 44 has been inserted into the clasp 4400 at or beyond the minimum desired engagement depth, the indicator arm 28050 is engaged by the leaflet 42, 44 and a portion of the indicator arm is moved past the fixed arm 28010.

[00596] Referring now to Figures 285–286, an example clasp 5000 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 5000 includes a fixed arm 5010, a hinge portion 5020, and a moveable arm 5030 having a barbed portion 5040 (though other friction-enhancing portions can be used). The moveable arm 5030 also includes an indicating lever 5032 disposed at a distance from the hinge portion 5020 that is less than a distance between the barbed portion 5040 and the hinge portion 5020. The indicating lever 5032 deforms when the native leaflet tissue is pressed against the fixed arm 5010 by the moveable arm 5030 to indicate that the leaflet tissue has reached a minimum desired engagement depth. Thus, the indicating lever 5032 will not indicate that the native leaflet 42, 44 has reached the desired engagement depth until the leaflet 42, 44 is inserted at or beyond the location of the indicating lever 5032. Once the leaflet 42, 44 has reached the desired engagement depth, actuation of the moveable arm 5030 squeezes the leaflet tissue 42, 44 against the indicating lever 5032 to cause the indicating lever 5032 to flatten against the moveable arm 5030 and thereby indicate that the leaflet 42, 44 has been inserted into the clasp 5000 at or beyond the desired engagement depth. The clasp 5000 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00597] Referring now to Figures 287–289, the example clasp 5000 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 287, the clasp 5000 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening 5006 of the clasp 5000 formed between the fixed and moveable arms 5010, 5030. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the moveable arm 5030 is actuated via actuation lines (not shown) as shown in Figures 288–289.

[00598] Referring now to Figure 288, when the moveable arm 5030 is actuated to push the leaflet 42, 44 against the fixed arm 5010, the leaflet 42, 44 may contact a portion of the moveable arm 5030 without contacting the indicating lever 5032 when the engagement depth of the leaflet 42, 44 is less than the minimum desired engagement depth. As can be seen in Figure 289, the indicating lever 5032 is deformed or flattened from contact with the leaflet 42, 44 when the leaflet 42, 44 is inserted into the clasp 5000 at or beyond the minimum engagement depth and is pressed against the indicating lever 5032 by the fixed arm 5010. That is, the indicating lever 5032 is deformed by the leaflet 42, 44 to indicate that the leaflet 42, 44 has been inserted at or beyond the minimum engagement depth. In some embodiments, actuation of the moveable arm 5030 also causes the barbed portion 5040 to engage and secure the leaflet 42, 44 within the barbed clasp 5000. If the indicating lever 5032 indicates that the leaflet 42, 44 is not inserted to the desired depth, the clasp 5000 can be opened to allow for repositioning of the leaflet 42, 44.

[00599] Referring now to Figures 290–291, an example clasp 5100 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 5100 includes a fixed arm 5110, a hinge portion 5120, and a moveable arm 5130 having a barbed portion 5140 (though other friction-enhancing portions can be used). The fixed arm 5110 also includes an indicating lever 5112 disposed at a distance from the hinge portion that is less than a distance between the barbed portion 5140 and the hinge portion 5120. The indicating lever 5112 deforms when the native leaflet tissue is pressed against the indicating lever 5112 by the moveable arm 5130 to indicate that the leaflet tissue has reached a minimum desired engagement depth. Thus, the indicating lever 5112 will not indicate that the native leaflet 42, 44 has reached the desired engagement depth until the leaflet 42, 44 is inserted at or beyond the location of the indicating lever 5112. Once the leaflet 42, 44 has reached the desired engagement depth, actuation of the moveable arm

5130 squeezes the leaflet tissue 42, 44 against the indicating lever 5112 of the fixed arm 5110 to cause the indicating lever 5112 to flatten and thereby indicate that the leaflet 42, 44 has been inserted into the clasp 5100 at or beyond the desired engagement depth. The clasp 5100 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00600] Referring now to Figures 292–294, the example clasp 5100 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 292, the clasp 5100 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening 5106 of the clasp 5100 formed between the fixed and moveable arms 5110, 5130. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the moveable arm 5130 is actuated via actuation lines (not shown) as shown in Figures 293–294. As can be seen in Figures 292A, 293A, and 294A, the indicating lever 5112 can optionally extend from the distal end of the fixed arm 5110A or be formed from a distal portion of the fixed arm 5110A that is bent or biased towards the moveable arm.

[00601] Referring now to Figure 293, when the moveable arm 5130 is actuated to push the leaflet 42, 44 against the fixed arm 5110, the leaflet 42, 44 may contact a portion of the fixed arm 5110 without contacting the indicating lever 5112 when the engagement depth of the leaflet 42, 44 is less than the minimum desired engagement depth. As can be seen in Figure 294, the indicating lever 5112 is deformed or flattened from contact with the leaflet 42, 44 when the leaflet 42, 44 is inserted into the clasp 5100 at or beyond the minimum engagement depth and is pressed against the indicating lever 5112 by the moveable arm 5130. That is, the indicating lever 5112 is deformed by the leaflet 42, 44 to indicate that the leaflet 42, 44 has been inserted at or beyond the minimum engagement depth. In some embodiments, actuation of the moveable arm 5130 also causes the barbed portion 5140 to engage and secure the leaflet 42, 44 within the barbed clasp 5100. If the indicating lever 5112 indicates that the leaflet 42, 44 is not inserted to the desired depth, the clasp 5100 can be opened to allow for repositioning of the leaflet 42, 44.

[00602] Referring now to Figures 295–296, an example clasp 5500 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 5500 includes a fixed arm 5510, a hinge portion 5520, and a moveable arm 5530 having a barbed portion 5540 (though other friction-enhancing portions can be used). The moveable arm 5530 also includes a plurality of indicating levers 5532

arranged at intervals along the moveable arm 5530 between the hinge portion 5520 and the barbed portion 5540. The indicating levers 5532 deform when the native leaflet tissue is pressed against the fixed arm 5510 by the moveable arm 5530 to indicate that the leaflet tissue has reached a particular engagement depth depending on the number of indicating levers 5532 engaged by the leaflet. Thus, the engagement depth of the leaflet can be determined by the number of indicating levers 5532 engaged by the leaflet. The clasp 5500 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00603] Referring now to Figures 178–180, the example clasp 5500 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44.

[00604] Referring now to Figure 297, the clasp 5500 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening 5506 of the clasp 5500 formed between the fixed and moveable arms 5510, 5530. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the moveable arm 5530 is actuated via actuation lines (not shown) as shown in Figures 298–299.

[00605] Referring now to Figure 298, when the moveable arm 5530 is actuated to push the leaflet 42, 44 against the fixed arm 5510, the leaflet 42, 44 engages two out of the four of the indicating levers 5532, which may, depending on the patient, be less than a minimum desired engagement depth of three or more indicating levers 5532. However, engagement of two of the indicating levers can indicate that leaflet is inserted far enough for some patients.

[00606] As can be seen in Figure 299, all four of the indicating levers 5532 are deformed or flattened from contact with the leaflet 42, 44 when the leaflet 42, 44 is inserted into the clasp 5000 at or beyond the minimum engagement depth and is pressed against the indicating levers 5532 by the fixed arm 5510. In some embodiments, actuation of the moveable arm 5530 also causes the barbed portion 5540 to engage and secure the leaflet 42, 44 within the barbed clasp 5500. If the indicating levers 5532 indicate that the leaflet 42, 44 is not inserted to the desired depth, the clasp 5500 can be opened to allow for repositioning of the leaflet 42, 44.

[00607] Referring now to Figures 300–301, an example clasp 5600 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 5600 includes a fixed arm 5610, a hinge portion 5620, and a moveable arm 5630 having a barbed portion 5640 (though other friction-enhancing portions

can be used). The fixed arm 5610 also includes a plurality of indicating levers 5612 arranged at intervals along the length of the fixed arm 5610. The indicating levers 5612 deform when the native leaflet tissue is pressed against the fixed arm 5610 by the moveable arm 5630 to indicate that the leaflet tissue has reached a particular engagement depth depending on the number of indicating levers 5612 engaged by the leaflet. Thus, the engagement depth of the leaflet can be determined by the number of indicating levers 5612 engaged by the leaflet. The clasp 5600 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00608] Referring now to Figures 302–304, the example clasp 5600 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 302, the clasp 5600 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening 5606 of the clasp 5600 formed between the fixed and moveable arms 5610, 5630. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the moveable arm 5630 is actuated via actuation lines (not shown) as shown in Figures 303–304.

[00609] Referring now to Figure 303, when the moveable arm 5630 is actuated to push the leaflet 42, 44 against the fixed arm 5610, the leaflet 42, 44 engages two out of the four of the indicating levers 5612, which may, depending on the patient, be less than a minimum desired engagement depth of three or more indicating levers 5612. As can be seen in Figure 304, all four of the indicating levers 5612 are deformed or flattened from contact with the leaflet 42, 44 when the leaflet 42, 44 is inserted into the clasp 5000 at or beyond the minimum engagement depth and is pressed against the indicating levers 5612 by the moveable arm 5630. In some embodiments, actuation of the moveable arm 5630 also causes the barbed portion 5640 to engage and secure the leaflet 42, 44 within the barbed clasp 5600. If the indicating levers 5612 indicate that the leaflet 42, 44 is not inserted to the desired depth, the clasp 5600 can be opened to allow for repositioning of the leaflet 42, 44.

[00610] Referring now to Figures 305–306, an example clasp 5700 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 5700 includes a fixed arm 5710, a hinge portion 5720, and a moveable arm 5730 having a barbed portion 5740 (though other friction-enhancing portions can be used). The clasp 5700 also includes an indicator arm 5750 extending from an indicator

hinge portion 5760. The indicator hinge portion 5760 joins the indicator arm 5750 to an attachment portion 5752. Unlike the indicator arm 3550 of the clasp 3500, the indicator arm 5750 is formed from a separate piece of material than the rest of the clasp 5700. The indicator arm 5750 is attached to the clasp 5700 by welding or otherwise securing the attachment portion 5752 to the fixed arm 5710 of the clasp 5700. As can be seen in Figure 306A, the attachment portion 5752 can alternatively be attached to the moveable arm 5730 of the clasp 5700. While the indicator arm 5750 being formed from a separate piece of material from the remainder of the clasp is illustrated as being similar to the indicator arm 3550 described above, the concept of forming the indicator from a separate piece of material that is attached to the clasp can be applied to any of the indicating features described herein. In addition, while the separate indicator arm 5750 is illustrated as being positioned next to the moveable arm 5730, in other embodiments the indicator arm 5750 can overlap with and/or be aligned with the moveable arm in the view of Figure 305.

[00611] Referring now to Figures 307–336, example clasps for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, are shown. These clasps include indicators that provide improved visibility to the position of the leaflet within the clasp during implantation, particularly when the clasp is observed via imaging devices. The indicators can be similar to any of the indicators disclosed herein with the addition of one or more markers that enhance imaging. The markers can take a wide variety of different forms. Radio opaque markers are referred to in this application, but any type of marker that enhances imaging can be used. Any type of image enhancing marker can be substituted of a radio opaque marker when a radio opaque marker is referred to herein. In the examples illustrated by Figures 307–336, the markers are shown as discrete components that are attached to the indicators. However, indicators themselves can be made from or comprise a marker material, such as radio opaque marker material, and/or can have portions treated (such as by coating) to act as markers. In yet other example embodiments, indicators can be provided on the fixed arm and/or the moveable arm of any of the clasps disclosed herein. Discreet markers can be provided on the fixed arm and/or the moveable arm, all or a portion of the fixed arm and/or the moveable arm can be made from a marker material, or all or a portion of the fixed arm and/or the moveable arm can be made from a marker material.

[00612] Radio opaque markers are formed from a material that reflects the electromagnetic radiation of the imaging device. That is, the markers appear opaque when viewed via an imaging device, in contrast to the surrounding tissue and, in some embodiments, the material

of the clasps. Consequently, the markers appear as bright spots on the display of the imaging device and can be configured to provide improved visibility of the position of the leaflet within the clasp.

[00613] Referring now to Figures 307–308, an example clasp 5800 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 5800 includes a fixed arm 5810, a hinge portion 5820, and a moveable arm 5830 having a barbed portion 5840 (though other friction-enhancing portions can be used). The clasp 5800 also includes an indicator arm 5850 adjacent to the moveable arm 5830 and extending from an indicator hinge portion 5860. The indicator hinge portion 5860 allows the indicator arm 5850 to be actuated separately from the moveable arm 5830. The indicator hinge portion 5860 can be formed from a portion of the indicator arm 5830 or can be formed from a series of cutouts similar to the patterned hinge of the clasp 2100 described above. The indicator arm 5850 includes a radio opaque marker or other marker that enhances imaging 5852 at the distal end of the indicator arm 5850. The marker 5852 increases the visibility of the position of the indicator arm 5850 relative to the fixed and moveable arms 5810, 5830 when viewed through an imaging device. The clasp 5800 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein. A radio opaque marker, such as the marker 5852 shown in Figures 307–308 can be used on any clasp with an indicator arm disclosed herein.

[00614] The indicator arm 5850 can be separately actuated from the moveable arm 5830 to facilitate detection of the depth of engagement of the native leaflet between the moveable arm 5830 and the fixed arm 5810 of the clasp 5800. In the illustrated embodiment, the indicator arm 5850 is narrower than the moveable arm 5830 and has a length that is less than a distance from the hinge portion 5820 to the barbed portion 5840.

[00615] The length of the indicator arm 5850 is used to determine a desired minimum engagement depth as measured from the end of the moveable arm 5830 of the clasp 5800. Configuring the length of the indicator arm 5850 to be less than a distance from the hinge portion 5820 to the barbed portion 5840 ensures that the barbed portion 5840 will engage a leaflet that is positioned at the minimum engagement depth as indicated by the indicator arm 5850. That is, if a native leaflet positioned within the clasp 5800 is engaged by the indicator arm 5850 when the indicator arm 5850 is actuated, then the leaflet will be engaged by the barbed portion 5840 of the moveable arm 5830. The opposite is also true. That is, if a native

leaflet positioned within the clasp 5800 is not engaged by the indicator arm 5850 when the indicator arm 5850 is actuated, then the leaflet will not be adequately engaged by the barbed portion 5840 of the moveable arm 5830.

[00616] Referring now to Figures 309–311, the example clasp 5800 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 309, the clasp 5800 is shown in an open condition with a native leaflet 42, 44 partially inserted into the opening 5806 of the clasp 5800 formed between the fixed and moveable arms 5810, 5830. When the indicator arm 5850 is in the open condition the marker 5852 is proximate the moveable arm 5830 and spaced apart from the fixed arm 5810. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the indicator arm 5850 is actuated as shown in Figures 310 and 311, e.g., via actuation lines (not shown).

[00617] Referring now to Figure 310, the indicator arm 5850 can be actuated by releasing tension on an actuation line (not shown). Because the leaflet 42, 44 is not at or beyond the minimum engagement depth the indicator arm 5850 misses or slips off of the leaflet 42, 44 and moves to a fully actuated position that is beyond the fixed arm 5810 of the clasps 5800. The indicator arm 5850 crosses the fixed arm 5810 to form an X-shape that is visible via imaging devices used to monitor implantation and deployment of the prosthetic device. In the fully actuated position, the marker 5852 is disposed beyond the fixed arm 5810—i.e., outside of the opening 5806 formed between the fixed and moveable arms 5810, 5830—to clarify that the indicator arm 5850 has not engaged the leaflet 42, 44. In addition or instead, the marker 5852 does not bounce or jump with the beating of the heart when the indicator arm 5858 does not engage the leaflet.

[00618] Referring now to Figure 311, the leaflet 42, 44 has been inserted into the clasp 5800 at or beyond the minimum desired engagement depth, the indicator arm 5850 engages and pinches the leaflet 42, 44 against the fixed arm 5810. Engagement with the leaflet 42, 44 prevents the indicator arm 5850 from moving past the fixed arm 5810 of the clasp 5800 to form the X-shape shown in Figure 310. In addition or instead, the marker 5852 bounces or jumps with the beating of the heart when the indicator arm 5850 is engaged with the valve leaflet 42, 44. When the indicator arm 5850 is engaged by the leaflet 42, 44, the marker 5852 is located between the fixed and moveable arms 5810, 5830. Thus, the indicator arm 5850 and marker 5852 indicate to an observer observing the installation via an imaging device that the leaflet 42, 44 is inserted into the opening 5806 beyond the minimum desired engagement

depth that is determined by the length of the indicator arm 5850. Once the indicator arm 5850 indicates that the leaflet 42, 44 is sufficiently inserted into the opening 5806, the moveable arm 5830 is actuated by releasing tension on the actuating line (not shown) so that the leaflet 42, 44 is pinched between the barbed portion 5840 and the fixed arm 5810 to secure the leaflet 42, 44 firmly within the clasp 5800.

[00619] Referring now to Figures 309A, 310A, and 311A, the clasp 5800 is shown having a second marker 5854 that is arranged on the fixed arm 5810 of the clasp 5800 in addition to the first marker 5852 on the indicator arm 5850. Any number of markers can be included to facilitate proper insertion of the leaflet into the opening 5806. The second marker 5854 can be a different shape than the marker 5852 so that the second marker 5854 can be distinguished from the first marker 5852 when both are viewed via an imaging device. For example, as is shown in Figure 309A, the second marker 5854 can be longer than the first marker 5852. The combination of the first and second markers 5852, 5854 provides further information of the relative position of the indicator arm 5850 and the fixed arm 5810.

[00620] As can be seen in Figure 310A, the first marker 5852 is arranged to the left of the second marker 5854 because the leaflet 42, 44 was not engaged when the indicator arm 5850 was actuated. In other embodiments, the first marker 5852 can touch, be close to, or otherwise be positioned relative to the second marker to indicate that the leaflet tissue was not engaged. When the indicator arm 5850 engages the leaflet 42, 44, however, the first marker 5852 is arranged to the right of the second marker 5854, as can be seen in Figure 311A. In other embodiments, the first marker 5852 can be otherwise positioned relative to the second marker 5854 to indicate proper tissue engagement. Any detectable differences between the relative positions of the first and second markers 5852, 5854 when the indicator arm is in respective valve tissue engaged (Fig. 192A) and valve tissue not engaged (Fig. 191A) can be used to determine proper leaflet insertion into the opening 5806. Thus, the combination of the first and second markers 5852, 5854 provides an indication of the position of the leaflet 42, 44 without needing to directly ascertain the positions of the fixed arm 5810, moveable arm 5830, or indicator arm 5850. First and second radio opaque markers, such as the markers 5852, 5854 shown in Figures 309A, 310A, and 311A can be used on any clasp with an indicator arm disclosed herein.

[00621] Referring now to Figures 312–313, an example clasp 5900 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 5900 includes a fixed arm 5910, a hinge portion 5920, and a

moveable arm 5930 having a barbed portion 5940 (though other friction-enhancing portions can be used). The moveable arm 5930 also includes an indicating feature or bump 5932 disposed between the barbed portion 5940 and the hinge portion 5920. The indicating feature 5932 includes a marker 5934 at the location on the indicating feature 5932 that is furthest from the moveable arm 5930. The marker 5934 increases the visibility of the position of the indicating feature 5932 relative to the fixed and moveable arms 5910, 5930 when viewed through an imaging device.

[00622] The indicating feature 5932 deforms when the native leaflet tissue is pressed against the indicating feature 5932 by the fixed arm 5910 to indicate that the leaflet tissue has reached a minimum desired engagement depth. Thus, the indicating feature 5932 will not indicate that the native leaflet has reached the desired engagement depth until the leaflet is inserted at or beyond the location of the indicating feature 5932. Once the leaflet 42, 44 has reached the desired engagement depth, actuation of the moveable arm 5930 squeezes the leaflet tissue 42, 44 between the fixed arm 5910 and the indicating feature 5932 to cause the indicating feature 5932 to flatten and thereby indicate that the leaflet 42, 44 has been inserted into the clasp 5900 at or beyond the desired engagement depth. The clasp 5900 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein. A radio opaque marker, such as the marker 5934 shown in Figures 312–313 can be used on any clasp with an indicating feature disclosed herein.

[00623] Referring now to Figures 314–316, the example clasp 5900 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 314, the clasp 5900 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening 5906 of the clasp 5900 formed between the fixed and moveable arms 5910, 5930. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the moveable arm 5930 is actuated via actuation lines (not shown) as shown in Figures 315–316.

[00624] Referring now to Figure 315, when the moveable arm 5930 is actuated to push the leaflet 42, 44 against the fixed arm 5910, the leaflet 42, 44 may contact a portion of the moveable arm 5930 without contacting the indicating feature 5932 when the engagement depth of the leaflet 42, 44 is less than the minimum desired engagement depth. In this position, the marker 5934 is disposed in the opening 5906 between the fixed and moveable

arms 5910, 5930—i.e., the marker 5934 is not aligned with the moveable arm 5930—to clarify that the indicating feature 5932 has not engaged the leaflet 42, 44.

[00625] Referring now to Figure 316, the indicating feature 5932 is deformed or flattened from contact with the leaflet 42, 44 when the leaflet 42, 44 is inserted into the clasp 5900 at or beyond the minimum engagement depth and is pressed against the indicating feature 5932. That is, the indicating feature 5932 is deformed by the leaflet 42, 44 to indicate that the leaflet 42, 44 has been inserted at or beyond the minimum engagement depth. When the indicating feature 5932 is engaged by the leaflet 42, 44, the marker 5934 is pushed closer to the moveable arm 5930 and can align with the moveable arm 5930. Thus, the moveable arm 5930, indicating feature 5932, and marker 5934 indicate to an observer observing the installation via an imaging device that the leaflet 42, 44 is inserted into the opening 5906 beyond the minimum desired engagement depth that is determined by the length of the indicator 5950. In some embodiments, actuation of the moveable arm 5930 also causes the barbed portion 5940 to engage and secure the leaflet 42, 44 within the barbed clasp 5900. If the indicating feature 5932 indicates that the leaflet 42, 44 is not inserted to the desired depth, the clasp 5900 can be opened to allow for repositioning of the leaflet 42, 44.

[00626] Referring now to Figures 314A, 315A, and 316A, the clasp 5900 is shown with second markers 5936 that are arranged on the moveable arm 5930 of the clasp 5900 in addition to the first marker 5932 on the indicating feature 5932. In some embodiments, only one second marker 5934 is included. The second markers 5934 are located on both sides of the indicating feature 5932 in the illustrated embodiment. As the indicating feature 5932 is compressed or deformed by the leaflet 42, 44, the first marker 5932 moves relative to the second markers 5934, helping to distinguish the first and second markers 5932, 5934. In some embodiments, the second marker 5934 is a different shape than the first marker 5932 so that the second marker 5934 can be distinguished from the first marker 5932 when both are viewed via an imaging device.

[00627] The combination of the first and second markers 5932, 5934 provides further information of the relative position of the indicating feature 5932 and the moveable arm 5930. As can be seen in Figure 315A, the first marker 5932 is out of alignment with the second markers 5934 because the leaflet 42, 44 was not engaged when the moveable arm 5930 was actuated. When the indicating feature 5932 engages the leaflet 42, 44, however, the first marker 5932 moves into or close to alignment with the second markers 5934, as can be seen in Figure 316A. Thus, the combination of the first and second markers 5932, 5934

provides an indication of the position of the leaflet 42, 44 without needing to directly ascertain the positions of the fixed arm 5910, moveable arm 5930, or indicating feature 5932. First and second radio markers, such as the markers 5932, 5934 shown in Figures 314A, 315A, and 316A can be used on any clasp with an indicator disclosed herein.

[00628] Referring now to Figures 317–318, an example clasp 6000 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 6000 includes a fixed arm 6010, a hinge portion 6020, and a moveable arm 6030 having a barbed portion 6040 (though other friction-enhancing portions can be used). The moveable arm 6030 also includes an indicating lever 6032 disposed at a distance from the hinge portion 6020 that is less than a distance between the barbed portion 6040 and the hinge portion 6020. The indicating lever 6032 includes a radio opaque marker 6034 at the distal end of the indicating lever 6032. The marker 6034 increases the visibility of the position of the indicating lever 6032 relative to the fixed and moveable arms 6010, 6030 when viewed through an imaging device. The indicating lever 6032 deforms when the native leaflet tissue is pressed against the fixed arm 6010 by the moveable arm 6030 to indicate that the leaflet tissue has reached a minimum desired engagement depth. Thus, the indicating lever 6032 will not indicate that the native leaflet has reached the desired engagement depth until the leaflet is inserted at or beyond the location of the indicating lever 6032. Once the leaflet 42, 44 has reached the desired engagement depth, actuation of the moveable arm 6030 squeezes the leaflet tissue 42, 44 between the fixed arm 6010 and the indicating lever 6032 to cause the indicating lever 6032 to flatten against the moveable arm 6030 and thereby indicate that the leaflet 42, 44 has been inserted into the clasp 6000 at or beyond the desired engagement depth. The clasp 6000 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein. A radio opaque marker, such as the marker 6034 shown in Figures 317–318 can be used on any clasp with an indicating feature disclosed herein.

[00629] Referring now to Figures 319–321, the example clasp 6000 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 319, the clasp 6000 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening 6006 of the clasp 6000 formed between the fixed and moveable arms 6010, 6030. To determine whether the leaflet 42, 44 has reached the desired engagement

depth, the moveable arm 6030 is actuated via actuation lines (not shown) as shown in Figures 320–321.

[00630] Referring now to Figure 320, when the moveable arm 6030 is actuated to push the leaflet 42, 44 against the fixed arm 6010, the leaflet 42, 44 may contact a portion of the moveable arm 6030 without contacting the indicating lever 6032 when the engagement depth of the leaflet 42, 44 is less than the minimum desired engagement depth. In this position, the marker 6034 is disposed in the opening 6006 between the fixed and moveable arms 6010, 6030—i.e., the marker 6034 is spaced apart from the moveable arm 6030—to clarify that the indicating feature 6032 has not engaged the leaflet 42, 44.

[00631] Referring now to Figure 321, the indicating feature 6032 is deformed or flattened from contact with the leaflet 42, 44 when the leaflet 42, 44 is inserted into the clasp 6000 at or beyond the minimum engagement depth and is pressed against the indicating lever 6032 by the fixed arm 6010. That is, the indicating lever 6032 is deformed by the leaflet 42, 44 to indicate that the leaflet 42, 44 has been inserted at or beyond the minimum engagement depth. When the indicating lever 6032 is engaged by the leaflet 42, 44, the marker 6034 is pushed closer to the moveable arm 6030 and can align with the moveable arm 6030. Thus, the moveable arm 6030, indicating lever 6032, and marker 6034 indicate to an observer observing the installation via an imaging device that the leaflet 42, 44 is inserted into the opening 6006 beyond the minimum desired engagement depth that is determined by the length of the indicator arm 6050. In some embodiments, actuation of the moveable arm 6030 also causes the barbed portion 6040 to engage and secure the leaflet 42, 44 within the barbed clasp 6000. If the indicating lever 6032 indicates that the leaflet 42, 44 is not inserted to the desired depth, the clasp 6000 can be opened to allow for repositioning of the leaflet 42, 44.

[00632] Referring now to Figures 319A, 320A, and 321A, the clasp 6000 is shown with a second marker 6036 arranged on the moveable arm 6010 of the clasp 6000 in addition to the first marker 6034 on the indicating lever 6032. More than one additional marker 6036 can be included to indicate proper tissue insertion. In some embodiments, the second marker 6036 is arranged at the intersection of the moveable arm 6030 and indicating lever 6032. In some embodiments, the second marker 6036 is a different shape than the first marker 6034 so that the second marker 6036 can be distinguished from the first marker 6034 when both are viewed via an imaging device. The combination of the first and second markers 6034, 6036 provides further information of the relative position of the indicating lever 6032 and the moveable arm 6030. As can be seen in Figure 320A, the first marker 6034 is out of alignment

with the second marker 6036 because the leaflet 42, 44 was not engaged when the moveable arm 6030 was actuated. When the indicating lever 6032 engages the leaflet 42, 44, however, the first marker 6034 moves into or close to alignment with the second marker 6036, as can be seen in Figure 321A. Thus, the combination of the first and second markers 6034, 6036 provides an indication of the position of the leaflet 42, 44 without needing to directly ascertain the positions of the fixed arm 6010, moveable arm 6030, or indicating lever 6032. First and second radio opaque markers, such as the markers 6034, 6036 shown in Figures 319A, 320A, and 321A can be used on any clasp with an indicator arm disclosed herein.

[00633] Referring now to Figures 322–323, an example clasp 6100 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 6100 includes a fixed arm 6110, a hinge portion 6120, and a moveable arm 6130 having a barbed portion 6140 (though other friction-enhancing portions can be used). The clasp 6100 also includes an indicator arm 6150 extending from an indicator hinge portion 6160 arranged toward the distal end of the moveable arm 6130. The indicating arm 6150 includes a marker 6152 at the distal end of the indicating arm 6150. The marker 6152 increases the visibility of the position of the indicating arm 6150 relative to the fixed and moveable arms 6110, 6130 when viewed through an imaging device.

[00634] The indicator hinge portion 6160 allows the indicator arm 6150 to be actuated separately from the moveable arm 6130. The indicator hinge portion 6160 can be formed from a portion of the indicator arm 6150 or can be formed from a series of cutouts similar to the patterned hinge of the clasp 2100 described above. The clasp 6100 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein. A marker, such as the marker 6152 shown in Figures 322–323 can be used on any clasp with an indicating arm disclosed herein.

[00635] The indicator arm 6150 need not be separately actuated from the moveable arm 6130 to detect the depth of engagement of the native leaflet between the moveable arm 6130 and the fixed arm 6110 of the clasp 6100. The moveable arm 6130 is optionally formed in a hoop or loop shape having two side arms 6132 surrounding a central opening 6134 that extends from the hinge portion 6120 to the barbed portion 6140 of the moveable arm 6130. The indicator arm 6150 is optionally disposed in the central opening 6134 between the two side arms 6132. In another example embodiment, only a single side arm is included. In the illustrated embodiment, because the moveable arm 6130 spans the full width of the clasp

6100, the barbed portion 6140 of the moveable arm 6130 is as wide as the clasp 6100 so that a larger area of the barbed portion 6140 engages with the native leaflet tissue.

[00636] As can be seen in Figures 322–323, the indicator hinge portion 6160 is arranged near the barbed portion 6140 of the moveable arm 6130. The indicator hinge portion 6160 is configured to bias the indicator arm 6150 at an angle from the moveable arm 6130 and toward the fixed arm 6110. The desired minimum engagement depth is determined by the angle of the indicator arm 6150 with respect to the moveable arm 6130, the distance between the indicator hinge portion 6160 and the hinge portion 6120, and the length of the indicator arm 6150. The minimum engagement depth decreases the further the hinge portion 6160 is from the hinge portion 6120, the greater the angle between the indicator arm 6150 and the moveable arm 6130, and the greater the length of the indicator arm 6150.

[00637] When the clasp 6100 is closed without the indicator arm 6150 being engaged by the leaflet, the indicator arm 6150 moves beyond the fixed arm 6110. The indicator arm 6150 crossing the fixed arm 6110 forms an X-shape that is visible via imaging devices used to monitor implantation and deployment of the device, as can be seen in Figure 325. When the leaflet is inserted into the clasp 6100 beyond the minimum desired engagement depth, the leaflet pushes the indicator arm 6150 back toward the moveable arm 6130 such that the indicator arm 6150 does not cross the fixed arm 6110 to form the X-shape shown in Figure 325. Thus, the indicator arm 6150 indicates to an observer observing the installation via an imaging device that the leaflet is inserted into the openings 6106 beyond the minimum desired engagement depth.

[00638] Referring now to Figures 324–326, the example clasp 6100 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 324, the clasp 6100 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening 6106 of the clasp 6100 formed between the fixed and moveable arms 6110, 6130. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the moveable arm 6130 is actuated via actuation lines (not shown) as shown in Figures 325–326.

[00639] Referring now to Figure 325, when the moveable arm 6130 is actuated toward the fixed arm 6110, the leaflet 42, 44 may contact portions of the fixed and moveable arms 6110, 6130 without contacting the indicator arm 6150 when the engagement depth of the leaflet 42, 44 is less than the minimum desired engagement depth. Thus, the indicator arm 6150 can

extend beyond the fixed arm 6110 to form an X-shape with the fixed arm 6110. In this position, the marker 6152 is disposed beyond the fixed arm 6110—i.e., outside of the opening 6106 formed between the fixed and moveable arms 6110, 6130—to clarify that the indicator arm 6150 has not engaged the leaflet 42, 44.

[00640] Referring now to Figure 326, the indicator arm 6150 is prevented from crossing the fixed arm 6110 when the leaflet 42, 44 is inserted far enough into the clasp 6100. That is, the indicator arm 6150 is deflected by the leaflet 42, 44 to indicate that the leaflet 42, 44 has been inserted to or beyond the minimum engagement depth. When the indicator arm 6150 is engaged by the leaflet 42, 44, the marker 6152 is located between the fixed and moveable arms 6110, 6130. Thus, the indicator arm 6150 and marker 6152 indicate to an observer observing the installation via an imaging device that the leaflet 42, 44 is inserted into the opening 6106 beyond the minimum desired engagement depth that is determined by the length of the indicator arm 6150. In some embodiments, actuation of the moveable arm 6130 also causes the barbed portion 6140 to engage and secure the leaflet 42, 44 within the barbed clasp 6100. If the indicator arm 6150 indicates that the leaflet 42, 44 is not inserted to the desired depth, the clasp 6100 can be opened to allow for repositioning of the leaflet 42, 44.

[00641] Referring now to Figures 324A, 325A, and 326A, the clasp 6100 is shown having a second marker 6154 that is arranged on the fixed arm 6110 of the clasp 6100 in addition to the first marker 6152 on the indicator arm 6150. The second marker 6154 can be a different shape than the marker 6152 so that the second marker 6154 can be distinguished from the first marker 6152 when both are viewed via an imaging device. For example, as is shown in Figure 324A, the second marker 6154 can be longer than the first marker 6152. The combination of the first and second markers 6152, 6154 provides further information or more visibly clear information on an imaging device of the relative position of the indicator arm 6150 and the fixed arm 6110.

[00642] As can be seen in Figure 325A, the first marker 6152 is arranged to the left of the second marker 6154 because the leaflet 42, 44 was not engaged when the indicator arm 6150 was actuated. When the indicator arm 6150 engages the leaflet 42, 44, however, the first marker 6152 is arranged to the right of the second marker 6154, as can be seen in Figure 326A. Thus, the combination of the first and second markers 6152, 6154 provides an indication of the position of the leaflet 42, 44 without needing to directly ascertain the positions of the fixed arm 6110, moveable arm 6130, or indicator arm 6150. First and second

radio opaque markers, such as the markers 6152, 6154 shown in Figures 324A, 325A, and 326A can be used on any clasp with an indicator arm disclosed herein.

[00643] Referring now to Figures 327–328, an example clasp 6200 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 6200 includes a fixed arm 6210, a hinge portion 6220, and a moveable arm 6230 having a barbed portion 6240 (though other friction-enhancing portions can be used). The moveable arm 6230 also includes a plurality of indicating levers 6232 arranged at intervals along the moveable arm 6230 between the hinge portion 6220 and the barbed portion 6240. The indicating levers 6232 each include a marker 6234. The illustrated markers 6252 are disposed at the distal end of each indicating lever 6232. However, the markers 6252 can be provided at any moveable position on the indicating lever. The markers 6252 increase the visibility of the position of the indicating levers 6232 relative to the fixed and moveable arms 6210, 6230 when viewed through an imaging device. The indicating levers 6232 deform when the native leaflet tissue is pressed against the fixed arm 6210 by the moveable arm 6230 to indicate that the leaflet tissue has reached a particular engagement depth depending on the number of indicating levers 6232 engaged by the leaflet. Thus, the engagement depth of the leaflet can be determined by the number of indicating levers 6232 engaged by the leaflet. The clasp 6200 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00644] Referring now to Figures 329–331, the example clasp 6200 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 329, the clasp 6200 is shown in an open condition with a native leaflet 42, 44 partially inserted into an opening 6206 of the clasp 6200 formed between the fixed and moveable arms 6210, 6230. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the moveable arm 6230 is actuated via actuation lines (not shown) as shown in Figures 330–331.

[00645] Referring now to Figure 330, when the moveable arm 6230 is actuated to push the leaflet 42, 44 against the fixed arm 6210, the leaflet 42, 44 engages two out of the four of the indicating levers 6232, which may be less than a minimum desired engagement depth of three or more indicating levers 6232. The markers 6234 on each of the engaged indicating levers 6232 are moved close to or against the moveable arm 6230 while the markers 6234 on the

indicating levers 6232 that are not engaged by the leaflet 42, 44 remain spaced apart from the moveable arm 6230. The relative position of the markers 6234 provides a further indication that the leaflet 42, 44 has engaged only two of the four indicating levers 6232.

[00646] Referring now to Figure 331, all four of the indicating levers 6232 are deformed or flattened from contact with the leaflet 42, 44 when the leaflet 42, 44 is inserted into the clasp 6200 at or beyond the minimum engagement depth and is pressed against the indicating levers 6232 by the fixed arm 6210. When the indicating levers 6232 are engaged by the leaflet 42, 44, the markers 6234 are located close to or against the moveable arm 6230. Thus, the indicating levers 6232 and markers 6234 indicate to an observer observing the installation via an imaging device that the leaflet 42, 44 is inserted into the opening 6206 beyond the minimum desired engagement depth that is determined by the number of engaged indicating levers 6232. Thus, the relative position of the markers 6234 provides an indication of the position of the leaflet 42, 44 without needing to directly ascertain the positions of the fixed arm 6210, moveable arm 6230, or indicating levers 6232. In some embodiments, actuation of the moveable arm 6230 also causes the barbed portion 6240 to engage and secure the leaflet 42, 44 within the barbed clasp 6200. If the indicating levers 6232 indicate that the leaflet 42, 44 is not inserted to the desired depth, the clasp 6200 can be opened to allow for repositioning of the leaflet 42, 44. The markers 6234 shown in Figures 329–331 can be used on any clasp with multiple indicator arms or levers disclosed herein.

[00647] Referring now to Figures 332–333, an example clasp 6300 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. Like the clasp 3500 described above, the clasp 6300 includes a fixed arm 6310, a hinge portion 6320, and a moveable arm 6330 having a barbed portion 6340 (though other friction-enhancing portions can be used). The clasp 6300 also includes an indicator arm 6350 adjacent to the moveable arm 6330 and extending from an indicator hinge portion 6360. The indicator hinge portion 6360 allows the indicator arm 6350 to be actuated separately from the moveable arm 6330. The indicator hinge portion 6360 can be formed from a portion of the indicator arm 6330 or can be formed from a series of cutouts similar to the patterned hinge of the clasp 2100 described above. The clasp 6300 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00648] The indicator arm 6350 bends away from the moveable arm 6330 to form a protruding portion 6352. Beyond the rounded protruding portion 6352, the indicator arm 6350 bends

gradually toward the moveable arm 6330. A first radio opaque marker 6354 is attached to the protruding portion 6352 of the indicator arm 6350 and a second radio opaque marker 6356 is attached to the distal end of the indicator arm 6350. The markers 6354, 6356 increase the visibility of the position of the indicator arm 6350 relative to the fixed and moveable arms 6310, 6330 when viewed through an imaging device.

[00649] The indicator arm 6350 can be separately actuated from the moveable arm 6330 to facilitate detection of the depth of engagement of the native leaflet between the moveable arm 6330 and the fixed arm 6310 of the clasp 6300. In the illustrated embodiment, the indicator arm 6350 is narrower than the moveable arm 6330 and has a length that is less than a distance from the hinge portion 6320 to the barbed portion 6340.

[00650] The length of the indicator arm 6350 is used to determine a desired minimum engagement depth as measured from the end of the moveable arm 6330 of the clasp 6300. Configuring the length of the indicator arm 6350 to be less than a distance from the hinge portion 6320 to the barbed portion 6340 ensures that the barbed portion 6340 will engage a leaflet that is positioned at the minimum engagement depth as indicated by the indicator arm 6350. That is, if a native leaflet positioned within the clasp 6300 is engaged by the indicator arm 6350 when the indicator arm 6350 is actuated, then the leaflet will be engaged by the barbed portion 6340 of the moveable arm 6330. The opposite is also true. That is, if a native leaflet positioned within the clasp 6300 is not engaged by the indicator arm 6350 when the indicator arm 6350 is actuated, then the leaflet will not be engaged by the barbed portion 6340 of the moveable arm 6330.

[00651] Referring now to Figures 334–336, the example clasp 6300 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 334, the clasp 6300 is shown in an open condition with a native leaflet 42, 44 partially inserted into the opening 6306 of the clasp 6300 formed between the fixed and moveable arms 6310, 6330. When the indicator arm 6350 is in the open condition the first marker 6354 is arranged between the fixed and moveable arms 6310, 6330 and the second marker 6356 is arranged proximate the moveable arm 6330 and spaced apart from the fixed arm 6310. To determine whether the leaflet 42, 44 has reached the desired engagement depth, the indicator arm 6350 is actuated via actuation lines (not shown) as shown in Figures 335 and 336.

[00652] Referring now to Figure 335, the indicator arm 6350 is actuated by releasing tension on an actuation line (not shown). Because the leaflet 42, 44 is not at or beyond the minimum

engagement depth the indicator arm 6350 misses or slips off of the leaflet 42, 44 and moves to a fully actuated position that is beyond the fixed arm 6310 of the clasps 6300. In the fully actuated position, the first and second markers 6354, 6356 are disposed beyond the fixed arm 6310—i.e., outside of the opening 6306 formed between the fixed and moveable arms 6310, 6330—to clarify that the indicator arm 6350 has not engaged the leaflet 42, 44. In some embodiments, the leaflet 42, 44, while not inserted beyond the minimum engagement depth, is engaged by the distal end of the indicator arm 6350 so that the second marker 6356 is disposed between the fixed and moveable arms 6310, 6330 while the first marker 6354 is disposed beyond the fixed arm 6310 because of the first marker's position on the protrusion 6352 of the indicator arm 6350.

[00653] Referring now to Figure 336, the leaflet 42, 44 has been inserted into the clasp 6300 at or beyond the minimum desired engagement depth—that is, at or beyond the location of the protrusion portion 6352 of the indicator arm 6350—the indicator arm 6350 engages and pinches the leaflet 42, 44 against the fixed arm 6310. When the indicator arm 6350 is engaged by the leaflet 42, 44 at or beyond the protrusion portion 6352, the first and second markers 6354, 6356 are pressed against the moveable arm 6330. Thus, the indicator arm 6350 and markers 6354, 6356 indicate to an observer observing the installation via an imaging device that the leaflet 42, 44 is inserted into the opening 6306 beyond the minimum desired engagement depth that is determined by the length of the indicator arm 6350. Once the indicator arm 6350 indicates that the leaflet 42, 44 is sufficiently inserted into the opening 6306, the moveable arm 6330 is actuated by releasing tension on the actuating line (not shown) so that the leaflet 42, 44 is pinched between the barbed portion 6340 and the fixed arm 6310 to secure the leaflet 42, 44 firmly within the clasp 6300.

[00654] Referring to Figures 337-352, in some example embodiments an indicator 33750 can be configured to utilize snap-through buckling to enhance visualization of the leaflet engagement indication. For example, an indicator 33750 that is configured with snap-through buckling can create a greater deflection of the indicator than can be achieved by deflection only due to engagement with the native leaflet. In one example embodiment, an indicator 33750 uses snap-through buckling to create clear “leaflet sufficiently engaged” and “leaflet insufficiently engaged” regions. Such distinct regions can be easier to visualize or read and can prevent false positive leaflet engagement results.

[00655] Snap buckling, snap-through buckling, bifurcation buckling, and Euler buckling are all types of buckling that are referred to as snap-through buckling herein. Figures 337 and

338 illustrate the concept of snap-through buckling. In Figure 337, a beam 33700 has a first stable state 33702 and a second stable state 33704. In the example illustrated by Figure 337, the beam 33700 is bent and/or compressed to form an apex 33706. A load 33708 is applied to the beam 33700 at the apex 33706. While the apex 33706 remains above the horizontal (or other snap-through point), the compression in the beam 33700 resists buckling and the system is in the first stable state 33702. As soon as the apex drops a hair beneath the horizontal (or other snap-through point), however, the compression in the beam 33700 actually encourages buckling which takes place rapidly (the snap). The load on the beam 33700 decreases 33710 as the beam snaps from the first stable state 33702 to the second stable state 33704. The system eventually becomes stable again as the apex 33706 drops further and the beam goes into tension.

[00656] The beam 33700 can take a wide variety of different forms. For example, the beam 33700 can be fixed at both ends as illustrated. However, in some example embodiments, the beam 33700 can have any combination of fixed end(s), simply supported (pinned) end(s), a free end, and sliding end(s).

[00657] A snap-through indicator 33750 can take a wide variety of different forms, can be used on any of the clasps disclosed herein and can be used in place of any of the indicators disclosed herein. The snap-through indicator 33750 can be an integrally formed feature of the clasp or the snap-through indicator 33750 can be a separate component that is attached to the clasp.

[00658] Referring now to Figures 339–342, an example clasp 33900 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. The barbed clasp 33900 includes a fixed arm 33910, a hinge portion 33920, and a moveable arm 33930 having an optional barbed portion 33940 and/or other friction-enhancing portion. Figure 341 illustrates that the moveable arm 33930 can include an optional cutout 33915.

[00659] In the example illustrated by Figures 339–342, the fixed arm 33910 of the clasp 33900 includes a snap-through indicator 33750. In this example, the snap-through indicator 33750 is integrally formed with the fixed arm 33910. For example, the snap through indicator 33750 can be formed by a pair of spaced apart cutouts 33902 that leave a strip that forms the snap-through indicator 33750 (See Figure 340). The strip can be shape set to the first stable state 33702 to form the snap-through indicator 33750. The clasp 33900 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00660] In the first stable state 33702, the snap-through indicator 33750 bends away from the fixed arm 33910 to the apex 33706. The size and position of the snap-through indicator 33750 is configured to determine whether a desired minimum depth is reached by the native leaflet. In the illustrated embodiment, the snap-through indicator 33750 is closer to the hinge portion 33920 than the barbed portion 33940. This positioning ensures that the snap-through indicator 33750 will snap to the second stable state 33704 when the barbed portion 33940 engages a leaflet that is positioned at the minimum engagement depth. That is, if a native leaflet positioned within the clasp 33900 snaps the indicator to the second stable state 33704, then the leaflet will be engaged by or has been properly engaged by the barbed portion 33940. The opposite is also true. That is, if a native leaflet positioned within the clasp 33900 does not snap the indicator to the second stable state, then a sufficient amount of leaflet is not engaged by or will not be engaged by the barbed portion 33940 of the moveable arm 33930.

[00661] Referring now to Figures 343–345, the example clasp 33900 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 343, the clasp 33900 is shown in an open condition with a native leaflet 42, 44 partially inserted into the opening 33906 of the clasp 33900 formed between the fixed and moveable arms 33910, 33930.

[00662] Referring now to Figure 344, the clasp 33900 is closed, for example, by releasing tension on an actuation line (not shown). Because the leaflet 42, 44 is not at or beyond the minimum engagement depth the snap-through indicator 33750 misses or is not sufficiently engaged by the leaflet 42, 44 to snap the indicator 33750 from the first stable state 33702 to the second stable state 33704. As a result, the snap through indicator 33750 can be easily visualized in a “leaflet insufficiently engaged” zone between the fixed arm 33910 and the moveable arm 33930. The snap through indicator 33750 in the “leaflet insufficiently engaged zone” clearly indicates that the leaflet has not been properly grasped by the clasp.

[00663] Referring now to Figure 345, the leaflet 42, 44 has been inserted into the clasp 33900 at or beyond the minimum desired engagement depth—that is, at or beyond the location of the snap-through indicator 33750. The moveable arm 33930 engages and pinches the leaflet 42, 44 against the snap-through indicator 33750 and the fixed arm 33910. Because the leaflet 42, 44 is at or beyond the minimum engagement depth, the snap-through indicator 33750 is snapped from the first stable state 33702, through the fixed arm 33910, to the second stable state 33704. As a result, the snap through indicator 33750 can be easily visualized in a

“leaflet sufficiently engaged” zone outside the clasp 33900, on the side of the fixed arm 33910. The snap through indicator 33750 in the “leaflet sufficiently engaged zone” clearly indicates that the leaflet has been properly grasped by the clasp.

[00664] Referring now to Figures 346–349, an example clasp 34600 for use in implantable prosthetic devices, such as devices 100, 200, 300 described above, is shown. The clasp 34600 includes a fixed arm 33910, a hinge portion 33920, and a moveable arm 33930 having an optional barbed portion 33940 and/or other friction-enhancing portion. Figure 348 illustrates that the moveable arm 33930 can include an optional cutout 34615 that is used to form the barbed portion 33940 and/or other friction-enhancing portion.

[00665] In the example illustrated by Figures 346–349, the moveable arm 33930 of the clasp 33900 includes a snap-through indicator 33750. In this example, the snap-through indicator 33750 is integrally formed with the moveable arm 33930. For example, the snap through indicator 33750 can be formed by a pair of spaced apart cutouts 34602 that leave a strip that forms the snap-through indicator 33750 (See Figure 348). The strip can be shape set to the first stable state 33702 to form the snap-through indicator 33750. The clasp 34600 can be used in any of the implantable prosthetic devices of the present application and can include any of the features or combinations of features of the other clasps described herein.

[00666] In the first stable state 33702, the snap-through indicator 33750 bends away from the moveable arm 33930 to the apex 33706. The size and position of the snap-through indicator 33750 is configured to determine whether a desired minimum depth is reached by the native leaflet. In the illustrated embodiment, the snap-through indicator 33750 is closer to the hinge portion 33920 than the barbed portion 33940. This positioning ensures that the snap-through indicator 33750 will snap to the second stable state 33704 when the barbed portion 33940 engages a leaflet that is positioned at the minimum engagement depth. That is, if a native leaflet positioned within the clasp 34600 snaps the indicator to the second stable state 33704, then the leaflet will be properly engaged or has been properly engaged by the barbed portion 33940. The opposite is also true. That is, if a native leaflet positioned within the clasp 34600 does not snap the indicator to the second stable state, then a sufficient amount of leaflet is not engaged by or will not be engaged by the barbed portion 33940 of the moveable arm 33930.

[00667] Referring now to Figures 350–352, the example clasp 34600 is shown being deployed within a native valve 40 to secure an implantable device (not shown), such as the devices 100, 200, 300 described above, to one of the native leaflets 42, 44. Referring now to Figure 350, the clasp 34600 is shown in an open condition with a native leaflet 42, 44 partially

inserted into the opening 33906 of the clasp 34600 formed between the fixed and moveable arms 33910, 33930.

[00668] Referring now to Figure 351, the clasp 34600 is closed, for example, by releasing tension on an actuation line (not shown). Because the leaflet 42, 44 is not at or beyond the minimum engagement depth the snap-through indicator 33750 misses or is not sufficiently engaged by the leaflet 42, 44 to snap the indicator 33750 from the first stable state 33702 to the second stable state 33704. As a result, the snap through indicator 33750 can be easily visualized in a “leaflet insufficiently engaged” zone between the fixed arm 33910 and the moveable arm 33930. The snap through indicator 33750 in the “leaflet insufficiently engaged zone” clearly indicates that the leaflet has not been properly grasped by the clasp.

[00669] Referring now to Figure 352, the leaflet 42, 44 has been inserted into the clasp 34600 at or beyond the minimum desired engagement depth—that is, at or beyond the location of the snap-through indicator 33750. The fixed arm 33910 engages and pinches the leaflet 42, 44 against the snap-through indicator 33750 and the moveable arm 33930. Because the leaflet 42, 44 is at or beyond the minimum engagement depth, the snap-through indicator 33750 is snapped from the first stable state 33702, through the moveable arm 33930, to the second stable state 33704. As a result, the snap through indicator 33750 can be easily visualized in a “leaflet sufficiently engaged” zone outside the clasp 33900, on the side of the moveable arm 33930. The snap through indicator 33750 in the “leaflet sufficiently engaged zone” clearly indicates that the leaflet has been properly grasped by the clasp.

[00670] Figures 353A-353D illustrate example embodiments of snap-through indicators 33750 that can be attached to a clasp. For example, the snap-through indicators 33750 illustrated by Figures 353A-353D can be used on any of the clasps disclosed herein and/or in place of any of the indicators disclosed herein. In the examples of Figures 353A-353C, the snap-through indicators 33750 can be formed from a flat sheet, such as being cut from a flat sheet. In these examples, snap-through indicators 33750 include a beam 33700 that is fixed to attachment portions 35302.

[00671] The beam 33700 can take a wide variety of different forms. In the examples of Figures 353A and 353B, the beams 33700 are straight or substantially straight and have a constant rectangular cross-section, except at the apex 33706. In Figures 353A and 353B, the beam 33700 includes an optional circular disk 35310 with an optional central opening 35312. The disk 35310 can be radiopaque and/or a radiopaque insert can be provided in the central

opening. In an example embodiment, the disk 35310 is omitted and the beam has a constant or substantially constant rectangular cross-section.

[00672] In the example of Figure 353C, the beam 33700 extends in a straight line or a substantially straight line and includes a plurality of spaced apart notches 35320 that form spaced apart projections 35322. The spaced apart notches 35320 and projections 35322 can be configured to set the force 33708 (See Figure 337) at which the beam 33700 snaps from the first stable state 33702 to the second stable state 33704. That is, the size, shape, spacing, etc. of the notches 35320 and projections 35322 can be selected to create a beam 33700 with a desired snap-through force that corresponds to a force that will be applied to the beam when the clasp closes and presses the native valve leaflet against the beam 33700. In Figure 353C, the beam 33700 includes an optional central opening 35312. A radiopaque insert can be provided in the central opening 35312. In an example embodiment, the central opening is omitted and the notches 35320 and projections 35322 can be uniformly spaced apart.

[00673] The attachment portions 35302 can take a wide variety of different forms. The attachment portions 35302 can be tailored to the clasp that the snap-through indicator 33750 will be attached to. In the examples illustrated by Figures 353A-353C, the attachment portions 35302 are rectangular or substantially rectangular and extend transversely away from the beam 33700. Optional stress relief cutouts 35350 can be provided between the attachment portions 35302 and the beam 33700. The optional stress relief cutouts 35350 can be configured to allow the beam 33700 to twist relative to the attachment portions 35302. In the examples of Figures 353A and 353C, the stress relief cutouts 35350 are semi-circular cutouts. In the example of Figure 353B, the attachment portions 35302 taper inward to a stress relief radius 35350 between the attachment portion 35302 and the beam 33700. In the illustrated examples of Figures 353A-353C, the attachment portions 35302 include holes 35352 or other attachment features for connecting the attachment portions 35302 to the clasp.

[00674] Referring to Figure 353D, in one example embodiment the flat parts illustrated by Figures 353A-353C are compressed and/or bent such that the beam 33700 has an upwardly bent shape (as viewed in Figure 353D) and a corresponding first stable state 33702 to form the snap-through indicator 33750. In one example embodiment, the parts of Figures 353A-353C can be shape set such that the beam 33700 has the shape of the upper curved dashed line. In Figure 353D, the beam 33700 of the snap-through indicator 33750 has a first stable state 33702 and a second stable state 33704. A load is applied to the beam 33700 when the clasp is closed, and the beam is engaged by the native valve leaflet. While the apex 33706

remains above the horizontal (or other snap-through point), the compression in the beam 33700 resists buckling and the system is in the first stable state 33702. As soon as the native valve leaflet pushes the apex 33706 a hair beneath the horizontal (or other snap-through point), however, the compression in the beam 33700 actually encourages buckling which takes place rapidly (the snap). The load on the beam 33700 decreases as the beam snaps from the first stable state 33702 to the second stable state 33704.

[00675] The snap through indicators 33750 can be used with a clasp in a wide variety of different ways. For example, the beam 33700 of the snap through indicator 33750 can run along the length of the clasp (See Figures 339, 340, 346, and 348) or across the width of the clasp.

[00676] While various inventive aspects, concepts and features of the disclosures may be described and illustrated herein as embodied in combination in the example embodiments, these various aspects, concepts, and features may be used in many alternative embodiments, either individually or in various combinations and sub-combinations thereof. Unless expressly excluded herein all such combinations and sub-combinations are intended to be within the scope of the present application. Still further, while various alternative embodiments as to the various aspects, concepts, and features of the disclosures—such as alternative materials, structures, configurations, methods, devices, and components, alternatives as to form, fit, and function, and so on—may be described herein, such descriptions are not intended to be a complete or exhaustive list of available alternative embodiments, whether presently known or later developed. Those skilled in the art may readily adopt one or more of the inventive aspects, concepts, or features into additional embodiments and uses within the scope of the present application even if such embodiments are not expressly disclosed herein. For example, the various indicators herein can be used on any device that needs to indicate capture of something (e.g., tissue) therein.

[00677] Additionally, even though some features, concepts, or aspects of the disclosures may be described herein as being a preferred arrangement or method, such description is not intended to suggest that such feature is required or necessary unless expressly so stated. Still further, example or representative values and ranges may be included to assist in understanding the present application, however, such values and ranges are not to be construed in a limiting sense and are intended to be critical values or ranges only if so expressly stated.

[00678] Moreover, while various aspects, features and concepts may be expressly identified herein as being inventive or forming part of a disclosure, such identification is not intended to be exclusive, but rather there may be inventive aspects, concepts, and features that are fully described herein without being expressly identified as such or as part of a specific disclosure, the disclosures instead being set forth in the appended claims. Descriptions of example methods or processes are not limited to inclusion of all steps as being required in all cases, nor is the order that the steps are presented to be construed as required or necessary unless expressly so stated. Further, the treatment techniques, methods, operations, steps, etc. described or suggested herein can be performed on a living animal or on a non-living simulation, such as on a cadaver, cadaver heart, simulator (e.g. with the body parts, tissue, etc. being simulated), etc. The words used in the claims have their full ordinary meanings and are not limited in any way by the description of the embodiments in the specification.

CLAIMS:

1. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:
 - a paddle;
 - a clasp;
 - wherein the paddle and the clasp are moveable to form an opening between the clasp and the paddle;
 - a plurality of indicator arms having different lengths that are moveable in the opening to indicate whether a leaflet of the native valve is inserted into the opening between the paddle and the clasp to at least a minimum desired insertion depth.
2. The device of claim 1, further comprising a crossbar connected to a first of the indicator arms, wherein movement of the crossbar away from the paddle moves the plurality of indicator arms away from the paddle.
3. The device of claim 2, wherein the crossbar extends outwardly from the first indicator arm to the clasp, wherein the crossbar is configured to move the clasp and the plurality of indicator arms away from the paddle when the clasp is moved away from the paddle.
4. The device of any of the preceding claims wherein the indicator arms are moveable relative to the paddle separate from the clasp.
5. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:
 - a pair of paddles that are moveable between an open position and a closed position;
 - a clasp attached to each of the paddles, each clasp comprising:
 - a fixed arm attached to the paddle;
 - a moveable arm;
 - a clasp hinge portion hingeably connecting the moveable arm to the fixed arm; and
 - a plurality of indicator arms for indicating whether a leaflet of the native valve is inserted into an opening of the clasp formed between the fixed and moveable arms to at least a minimum desired insertion depth;

wherein each indicator arm has a different length.

6. The device of claim 5, wherein the plurality of indicator arms comprises a first indicator arm having a first side edge and a second side edge and wherein a first indicator arm of the plurality of indicator arms comprises a cross-bar extending outwardly on each side of the first indicator arm, in a direction perpendicular to a length of the first indicator arm.
7. The device of claim 6, wherein the cross-bar extends outwardly from the first and second side edges of the first indicator arm to a first and second side edge of the moveable arm, respectively, wherein the cross-bar is configured to lift the moveable arm and the plurality of indicator arms from a resting position to an open position when the clasp is opened.
8. The device of any of claims 6-7, wherein the cross-bar extends outwardly from the first and second side edges of the first indicator arm to a first and second side edge of a longest indicator arm, respectively, wherein the cross-bar is configured to lift the plurality of arms from a resting position to an open position when the clasp is opened.
9. The device of any of claims 5-8 wherein one of the indicator arms has a length that is about 65 percent to 90 percent of a maximum engagement depth measured between the barbed portion and the clasp hinge portion.
10. The device of any of claims 5-9, wherein one of the indicator arms has a length that is about 35 percent to 65 percent of a maximum engagement depth measured between the barbed portion and the clasp hinge portion.
11. The device of any of claims 5-10, wherein the indicator arms are actuatable between a resting position and an open position separate from the moveable arm of the clasp.
12. The device of any of claims 5-11, wherein each indicator arm is configured to return to the resting position in an absence of a native valve leaflet extending into the clasp beyond a free end of the indicator arm.

13. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:
 - a hoop shaped clasp;
 - wherein the hoop shaped clasp is moveable to form an opening or leaflet receiving area;
 - an indicator arm disposed between two sides of the hoop shaped clasp that is moveable in the opening to indicate whether a leaflet of the native valve is inserted into the opening or leaflet receiving area to at least a minimum desired insertion depth.
14. The device of claim 13, wherein the indicator arm is moveable independently from the clasp.
15. The device of any of claims 13-14, wherein the indicator arm includes a barb.
16. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:
 - a pair of paddles that are moveable between an open position and a closed position;
 - a clasp attached to each of the paddles, each clasp comprising:
 - a fixed arm attached to the paddle;
 - a hoop shaped moveable arm;
 - a clasp hinge portion hingeably connecting the hoop shaped moveable arm to the fixed arm; and
 - an indicator arm disposed between two sides of the hoop shaped moveable arm for indicating whether a leaflet of the native valve is inserted into an opening of the clasp formed between the fixed and hoop shaped moveable arms to at least a minimum desired insertion depth.
17. The device of claim 16, wherein the indicator arm is actuatable between a resting position and an open position separate from the hoop shaped moveable arm of the clasp.
18. The device of any of claims 16-17, wherein the indicator arm is configured to return to the resting position in an absence of a native valve leaflet extending into the clasp beyond a free end of the indicator arm.

19. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:
- a paddle;
 - a clasp;
 - wherein the paddle and the clasp are moveable to form an opening between the clasp and the paddle;
 - a flattenable indicator in the opening to indicate whether a leaflet of the native valve is inserted into the opening between the paddle and the clasp to at least a minimum desired insertion depth.
20. The device of claim 19, further comprising an indicator arm, wherein the flattenable indicator is disposed on at least one of the indicator arm, the clasp, a movable arm of the clasp, and a fixed arm of the clasp.
21. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:
- a pair of paddles that are moveable between an open position and a closed position;
 - a clasp attached to each of the paddles, each clasp comprising:
 - a fixed arm attached to the paddle;
 - a moveable arm;
 - a clasp hinge portion hingeably connecting the moveable arm to the fixed arm; and
 - a flattenable indicator bump for indicating whether a leaflet of the native valve is inserted into an opening of the clasp formed between the fixed and moveable arms to at least a minimum desired insertion depth.
22. The device of claim 21, further comprising an indicator arm, wherein the flattenable indicator bump is disposed on at least one of the indicator arm, the clasp, the movable arm of the clasp, and the fixed arm of the clasp.
23. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:
- a hoop shaped clasp;

wherein the hoop shaped clasp is moveable to open an opening or leaflet receiving area;

an indicator that spans the hoop shaped clasp and is deformable through the hoop shaped clasp to indicate whether a leaflet of the native valve is inserted into the opening or leaflet receiving area to at least a minimum desired insertion depth.

24. The device of claim 23, wherein the indicator extends from a first side of the clasp to a second side of the clasp.
25. The device of claim 23, wherein the indicator extends from a hinge portion of the clasp to an end of the clasp.
26. The device of any of claims 23-25, wherein the indicator comprises wire.
27. The device of any of claims 23-36, wherein the indicator comprises a spring.
28. The device of any of claims 23-25, wherein the indicator comprises a spring disposed over a wire.
29. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:
 - a pair of paddles that are moveable between an open position and a closed position;
 - a clasp attached to each of the paddles, each clasp comprising:
 - a fixed arm attached to the paddle;
 - a hoop shaped moveable arm;
 - a clasp hinge portion hingeably connecting the hoop shaped moveable arm to the fixed arm; and
 - an indicator that spans the hoop shaped moveable arm and is deformable through the hoop shaped moveable arm to indicate whether a leaflet of the native valve is inserted into an opening of the clasp formed between the fixed and hoop shaped moveable arms to at least a minimum desired insertion depth.

30. The device of claim 29, wherein the indicator extends from a first side of the clasp to a second side of the clasp.
31. The device of claim 29, wherein the indicator extends from a hinge portion of the clasp to an end of the clasp.
32. The device of any of claims 29-31, wherein the indicator comprises wire.
33. The device of any of claims 29-32, wherein the indicator comprises a spring.
34. The device of any of claims 29-31, wherein the indicator comprises a spring disposed over a wire.
35. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:
 - a hoop-shaped clasp;
 - wherein the hoop-shaped clasp is moveable to form an opening or receiving area between two portions of the hoop-shaped clasp or between the hoop-shaped clasp and another portion of the device;
 - an indicator arm disposed between two sides of the hoop shaped clasp having a curved portion that is moveable through the hoop shaped clasp to indicate whether a leaflet of the native valve is inserted into the opening or receiving area to at least a minimum desired insertion depth.
36. The device of claim 35, further comprising a paddle, wherein the indicator arm is moveable relative to the paddle separate from the clasp.
37. The device of any of claims 35-36, wherein the curved portion of the indicator arm is circular.
38. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:
 - a pair of paddles that are moveable between an open position and a closed position;
 - a clasp attached to each of the paddles, each clasp comprising:
 - a fixed arm attached to the paddle;

a hoop shaped moveable arm;

a clasp hinge portion hingeably connecting the hoop shaped moveable arm to the fixed arm; and

an indicator arm disposed between two sides of the hoop shaped moveable arm, wherein the indicator arm includes a curved portion that extends through the hoop shaped moveable arm to indicate that a leaflet of the native valve is inserted into an opening or receiving area of the clasp formed between the fixed arm and hoop shaped moveable arms to at least a minimum desired insertion depth.

39. The device of claim 38, wherein the indicator arm is actuatable between a resting position and an open position separate from the hoop shaped moveable arm of the clasp.
40. The device of any of claims 38-39, wherein the indicator arm is configured to return to the resting position in an absence of a native valve leaflet extending into the clasp beyond a free end of the indicator arm.
41. The device of any of claims 38-40, wherein the curved portion of the indicator arm is circular.
42. The device of any of claims 38-41, wherein the curved portion of the indicator arm only extends through the hoop shaped moveable arm when the indicator arm engages the leaflet of the native valve.
43. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:
a clasp;
wherein the clasp is moveable to form an opening or leaflet receiving area between two portions of the clasp or between the clasp and another portion of the device;
a spring in the opening or leaflet receiving area to indicate whether a leaflet of the native valve is inserted into the opening or leaflet receiving area to at least a minimum desired insertion depth.
44. The device of claim 43, wherein the spring extends away from the clasp.

45. The device of claim 43, wherein the spring extends along a length of the clasp.
46. The device of claim 43, wherein the spring extends at an angle from the clasp.
47. The device of any of claims 43-46, wherein the spring is at least one of cylindrical and conical.
48. The device of any of claims 43-47, wherein a portion of the spring is pressed through the clasp when engaged by the leaflet.
49. The device of any of claims 43-48, further comprising an indicator arm, wherein the spring is disposed on the indicator arm.
50. The device of any of claims 43-48, wherein the spring is disposed on at least one of a movable arm of the clasp and a fixed arm of the clasp.
51. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:
 - a pair of paddles that are moveable between an open position and a closed position;
 - a clasp attached to each of the paddles, each clasp comprising:
 - a fixed arm attached to the paddle;
 - a moveable arm;
 - a clasp hinge portion hingeably connecting the moveable arm to the fixed arm; and
 - a spring for indicating whether a leaflet of the native valve is inserted into an opening or receiving area of the clasp formed between the fixed and moveable arms to at least a minimum desired insertion depth.
52. The device of claim 51, wherein the spring extends away from the moveable arm of the clasp.
53. The device of claim 51, wherein the spring extends away from the fixed arm of the clasp.

54. The device of claim 51, wherein the spring extends along a length of the moveable arm of the clasp.
55. The device of claim 51, wherein the spring extends along a length of the fixed arm of the clasp.
56. The device of claim 51, wherein the spring extends at an angle from the fixed and moveable arms of the clasp.
57. The device of any of claims 51-56, wherein the spring is at least one of cylindrical and conical.
58. The device of any of claims 51-57, wherein a portion of the spring is pressed through the clasp when engaged by the leaflet.
59. The device of any of claims 51-58, further comprising an indicator arm, wherein the spring is disposed on the indicator arm.
60. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:
 - a clasp;
 - wherein the clasp is moveable to form an opening or receiving area between two portions of the clasp or between the clasp and another portion of the device;
 - at least one indicator wing extending outward from a side of the clasp at an angle to indicate whether a leaflet of the native valve is inserted into the opening between the paddle and the clasp to at least a minimum desired insertion depth.
61. The device of claim 60, wherein an indicator wing extends from each side of the clasp.
62. The device of any of claims 60-61, wherein the at least one indicator wing flexes laterally outward away from the clasp when the at least one indicator wing engages the leaflet of the native valve.

63. The device of any of claims 60-62, wherein the at least one indicator wing is disposed on at least one of a movable arm of the clasp and a fixed arm of the clasp.
64. The device of any of claims 60-63, wherein the at least one indicator wing is hoop shaped.
65. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:
a pair of paddles that are moveable between an open position and a closed position;
a clasp attached to each of the paddles, each clasp comprising:
a fixed arm attached to the paddle;
a moveable arm;
a clasp hinge portion hingeably connecting the moveable arm to the fixed arm; and
at least one indicator wing extending outward from a side of the clasp at an angle to indicate whether a leaflet of the native valve is inserted into an opening of the clasp formed between the fixed and moveable arms to at least a minimum desired insertion depth.
66. The device of claim 65, wherein an indicator wing extends from each side of the clasp.
67. The device of any of claims 65-66, wherein the at least one indicator wing flexes laterally outward away from the clasp when the at least one indicator wing engages the leaflet of the native valve.
68. The device of any of claims 65-67, wherein the at least one indicator wing is disposed on at least one of a movable arm of the clasp and a fixed arm of the clasp.
69. The device of any of claims 65-68, wherein the at least one indicator wing is hoop shaped.
70. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:
a clasp;
wherein the clasp is moveable to form an opening or leaflet receiving area between two portions of the clasp or between the clasp and another portion of the device;

a first leaflet indicator;

a second leaflet indicator;

wherein the first leaflet indicator and the second leaflet indicator are spaced apart such that a leaflet of a native valve can be inserted into the opening or leaflet receiving area to at least a minimum desired insertion depth;

wherein the first leaflet indicator and the second leaflet indicator are in contact in the absence of a leaflet of the native valve in the opening or leaflet receiving area.

71. The device of claim 70, wherein the first indicator comprises a flexible hoop.
72. The device of claim 70, wherein the first and second flexible indicators comprise flexible hoops.
73. The device of any of claims 70-72, wherein the flexible indicators are disposed in the opening or leaflet receiving area.
74. The device of any of claims 70-73, the first indicator is disposed on at least one of a movable arm of the clasp and a fixed arm of the clasp.
75. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:
- a pair of paddles that are moveable between an open position and a closed position;
 - a clasp attached to each of the paddles, each clasp comprising:
 - a fixed arm attached to the paddle;
 - a moveable arm;
 - a clasp hinge portion hingeably connecting the moveable arm to the fixed arm;
 - a first leaflet indicator;
 - a second leaflet indicator;
- wherein the first leaflet indicator and the second leaflet indicator are configured such that they are spaced apart when a leaflet of a native valve is inserted into an opening or receiving area between the paddle and the clasp to at least a minimum desired insertion depth;

wherein the first leaflet indicator and the second leaflet indicator are in contact in the absence of a leaflet of the native valve in the opening between the paddle and the clasp.

76. The device of claim 75, wherein the first indicator comprises a flexible hoop.
77. The device of claim 75, wherein the first and second flexible indicators comprise flexible hoops.
78. The device of any of claims 75-77 wherein the flexible indicators are disposed between the fixed and moveable arms.
79. The device of any of claims 75-78 the first indicator is disposed on at least one of the movable arm of the clasp and the fixed arm of the clasp.
80. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:
- a clasp;
 - wherein the clasp is moveable to open an opening or leaflet receiving area;
 - an indicator arm; and
 - a single actuation line extending from a delivery device to the clasp and to the indicator arm, wherein the single actuation line is configured to separately actuate the clasp and the indicator arm.
81. The valve repair device of claim 80, further comprising a one-way catch fixedly attached to the single actuation suture.
82. The valve repair device of claim 81, wherein the one-way catch is larger than a loop on the clasp or the indicator arm so that the one-way catch is prohibited from passing through the loop.
83. The valve repair device of claim 82, wherein the one-way catch is smaller than the second loop so that the one-way catch is capable of passing through the second loop.

84. The valve repair device of any of claims, 82-83, wherein the one-way catch is at least one of a rounded bead, cone-shaped, and barbed.

85. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:

a pair of paddles that are moveable between an open position and a closed position and are configured to attach to the native valve of the patient;

a clasp attached to each of the plurality of paddles, the clasp comprising:

a fixed arm attached to the paddle;

a moveable arm having a barbed portion, the moveable arm being moveable between an open position and a closed position;

a hinge portion hingeably connecting the moveable arm to the fixed arm;

an indicator arm; and

an indicator hinge portion hingeably connecting the indicator arm to the fixed arm;
and

a single actuation suture extending from a delivery device to first and second loops attached to the moveable and indicator arms, respectively, wherein the moveable and indicator arms are separately actuatable with the single actuation suture.

86. The valve repair device of claim 85, wherein the single actuation suture extends from the delivery device, through the first loop, through the second loop, and back into the delivery device.

87. The valve repair device of claim 86, wherein the single actuation suture extends from the delivery device, through the first loop, through a first fixed loop attached to a proximal end of the coaption element, through a second fixed loop attached to a midpoint of the coaption element, through the second loop, back through the second fixed loop, back through the first fixed loop, back through the first loop, and back into the delivery device.

88. The valve repair device of any of claims 86-87, wherein the first loop is attached proximate a mid-point of the indicator arm.

89. The valve repair device of any of claims 86-88, wherein the second loop is attached proximate a distal end of the moveable arm.
90. The valve repair device of any of claims 86-89, wherein the first loop is arranged between the hinge portion of the clasp and the second loop.
91. The valve repair device of claim 86-90, further comprising a one-way catch fixedly attached to the single actuation suture.
92. The valve repair device of claim 91, wherein the one-way catch is larger than the first loop so that the one-way catch is prohibited from passing through the first loop.
93. The valve repair device of any of claims 91-92, wherein the one-way catch is smaller than the second loop so that the one-way catch is capable of passing through the second loop.
94. The valve repair device of any of claims 91-93, wherein the one-way catch is at least one of a rounded bead, cone-shaped, and barbed.
95. The valve repair device of any of claims 85-94, wherein a first force required to open the moveable arm is less than a second actuation torque force to actuate the indicator arm.
96. The valve repair device of any of claims 85-95, wherein the first loop is attached proximate a mid-point of the indicator arm and the second loop is attached proximate a distal end of the moveable arm.
97. The valve repair device of any of claims 85-96, further comprising a base assembly that comprises:
 - a shaft;
 - a collar that the shaft extends through;
 - a cap attached to the shaft such that the cap can be moved by the shaft away from the collar;
 - wherein the pair of paddles are attached to the cap;
 - wherein movement of the cap toward the collar causes the pair of paddles to move to the closed position, and movement of the cap away from the collar causes the pair of paddles to move to the open position.

98. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:
- a pair of paddles that are moveable between an open position and a closed position;
 - a clasp attached to each of the paddles, the clasp comprising:
 - a fixed arm attached to the paddle;
 - a moveable arm having a barbed portion;
 - a clasp hinge portion hingeably connecting the moveable arm to the fixed arm;
 - and
 - a flexible indicator fixedly connected to one arm and slidably connected to the other arm.
99. The device of claim 98, wherein the flexible indicator is fixedly connected at a first end to the fixed arm closer to a free end of the fixed arm than the clasp hinge portion, and slidably connected at a second end to the moveable arm for sliding between the barbed portion and the clasp hinge portion.
100. The device of any of claims 98-99, wherein the flexible indicator comprises one or more of a suture, a wire comprised of a shape memory material, or a cloth.
101. The device of any of claims 98-100, wherein the flexible indicator comprises a slack region between the first and second ends, and
- a spring positioned along the moveable arm between the second end of the flexible indicator and the clasp hinge portion;
- wherein the flexible indicator is pulled taught and the second end slides along the moveable arm, compressing the spring, when engaged by a valve leaflet.
102. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:
- a paddle;
 - a clasp;
- wherein the paddle and the clasp are moveable to form an opening between the clasp and the paddle;

at least one indicator extending from the paddle into the opening between the clasp and the paddle;

wherein the indicator is configured such that:

when the opening between the paddle and the clasp is closed and the indicator is unobstructed, at least a portion of the indicator extends through the clasp;

when the opening between the paddle and the clasp is closed and the indicator engages a valve leaflet, a portion of the indicator extends through the paddle.

103. The device of claim 102, wherein no portion of the indicator extends through the clasp when the opening between the paddle and the clasp is closed and the indicator engages a valve leaflet.

104. The device of any of claims 102-103, wherein the indicator has a fixed end connected to the paddle and a free end.

105. The device of any of claims 102-104, wherein the indicator is curved.

106. The device of any of claims 102-105, wherein the clasp includes a cutout that the indicator extends through when the opening between the paddle and the clasp is closed and the indicator is unobstructed.

107. The device of any of claims 102-106, wherein the paddle includes a cutout that the indicator extends through when the opening between the paddle and the clasp is closed and the indicator engages a valve leaflet.

108. The device of claim 107, wherein a smaller portion of the indicator extends through the cutout of the paddle when the opening between the paddle and the clasp is closed and the indicator is unobstructed, and a larger portion of the indicator extends through the cutout of the paddle when the opening between the paddle and the clasp is closed and the indicator engages a valve leaflet.

109. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:

a paddle;

a clasp having a fixed arm attached to the paddle, a movable arm, a hinge that connects the moveable arm to the fixed arm;

wherein the moveable arm is movable away from the fixed arm to form an opening or receiving area between the moveable arm and the paddle;

at least one indicator extending from one of the fixed arm and the paddle into the opening or receiving area between the moveable arm of the clasp and the paddle;

wherein the indicator is configured such that:

when the opening or receiving area between the paddle and the moveable arm is closed and the indicator is unobstructed, at least a portion of the indicator extends through the moveable arm of the clasp;

when the opening or receiving area between the paddle and the moveable arm is closed and the indicator engages a valve leaflet, a portion of the indicator extends through the fixed arm of the clasp.

110. The device of claim 109, when the opening or receiving area between the paddle and the moveable arm of the clasp is closed and the indicator engages a valve leaflet, a portion of the indicator extends through the paddle.
111. The device of any of claims 109-110, wherein no portion of the indicator extends through the moveable arm of the clasp when the opening or receiving area between the paddle and the clasp is closed and the indicator engages a valve leaflet.
112. The device of any of claims 109-111, wherein the indicator has a fixed end connected to the paddle and a free end.
113. The device of any of claims 109-112, wherein the indicator has a fixed end connected to the fixed arm and a free end.
114. The device of claim 113, wherein the indicator is integrally formed with the fixed arm of the clasp.
115. The device of any of claims 109-114, wherein the moveable arm of the clasp includes a cutout that the indicator extends through when the opening or receiving area between the paddle and the clasp is closed and the indicator is unobstructed.

116. The device of any of claims 109-115, wherein the paddle includes a cutout that the indicator extends through when the opening between the paddle and the moveable arm of the clasp is closed and the indicator engages a valve leaflet.
117. The device of claim 116, wherein a smaller portion of the indicator extends through the cutout of the paddle when the opening between the paddle and the clasp is closed and the indicator is unobstructed, and a larger portion of the indicator extends through the cutout of the paddle when the opening between the paddle and the clasp is closed and the indicator engages a valve leaflet.
118. A method of implanting a valve repair device on a native valve of a patient, the method comprising:
- engaging an indicator of a clasp of the valve repair device;
 - disengaging the indicator when a leaflet of the native valve is not engaged by the indicator; and
 - closing the clasp of the valve repair device when the leaflet of the native valve is engaged by the indicator.
119. The method of claim 118, wherein the indicator is engaged by closing the clasp.
120. The method of any of claims 118-119, wherein the step of disengaging is performed by opening the clasp.
121. The method of any of claims 118-120, wherein the indicator is biased in an engaging direction.
122. The method of any of claims 118-121, wherein the indicator remains in the engaged position during the closing of the clasp.
123. A method of implanting a valve repair device on a native valve of a patient, the method comprising:
- actuating an indicator arm of a clasp of the valve repair device;

returning the indicator arm to an undeployed position when a leaflet of the native valve is not engaged by the indicator arm;

closing the clasp of the valve repair device when the leaflet of the native valve is engaged by the indicator arm.

124. The method of claim 123, further comprising closing a paddle of the valve repair device to bring the leaflet of the native valve into contact with a coaption element of the valve repair device.
125. The method of any of claims 123-124, wherein the indicator is actuated by closing the clasp, and wherein the step of returning is performed by opening the clasp.
126. The method of any of claims 123-125, wherein the indicator arm remains in the actuated position during the closing of the clasp.
127. A method of implanting a valve repair device on a native valve of a patient, the method comprising:
- engaging an indicator gauge of a clasp of the valve repair device to measure an engaged depth of a leaflet of the native valve;
 - disengaging the indicator gauge when the engaged depth is below a desired engaged depth;
 - closing the clasp of the valve repair device when the engaged depth is at least equal to the desired engaged depth; and
 - closing a paddle of the valve repair device.
128. The method of claim 127, further comprising partially closing the clasp prior to engaging the indicator gauge.
129. The method of any of claims 127-128, wherein the indicator gauge is engaged by closing the clasp and disengaging is performed by opening the clasp.
130. The method of claim any of claims 127-129, wherein the indicator gauge remains in the engaged position during the closing of the clasp.

131. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:
- a plurality of paddles, each paddle having an inner portion and an outer portion, wherein the paddles are moveable between an open position and a closed position and are configured to attach to the native valve of the patient;
 - a clasp attached to each of the plurality of paddles, the clasp comprising:
 - a fixed arm attached to the inner portion of the paddle;
 - a moveable arm having a friction-enhancing portion;
 - a clasp hinge portion hingeably connecting the moveable arm to the fixed arm; and
 - an insertion depth indicator for indicating whether a leaflet of the native valve is inserted into an opening or leaflet receiving area of the clasp formed between the fixed and moveable arms to at least a minimum desired insertion depth.
132. The valve repair device of claim 131, wherein the insertion depth indicator is deformable, and a shape of the insertion depth indicator indicates whether the leaflet has been inserted to the minimum desired insertion depth.
133. The valve repair device of any of claims 131-132, wherein the insertion depth indicator is moveable, and a position of the insertion depth indicator indicates whether the leaflet has been inserted to the minimum desired insertion depth.
134. The valve repair device of any of claims 131-133, wherein the relative position of the insertion depth indicator and at least one of the fixed arm and the movable arm indicates whether the leaflet has been inserted to the minimum desired insertion depth.
135. The valve repair device of any of claims 131-134, wherein the insertion depth indicator is actuatable between undeployed and actuated positions.
136. The valve repair device of claim 135, wherein the insertion depth indicator is actuated when the clasp is at least partially open to determine whether the leaflet has been inserted to the minimum desired insertion depth.

137. The valve repair device of claim 135, wherein the insertion depth indicator intersects at least one of the fixed arm and the moveable arm when the insertion depth indicator is in the actuated position.
138. The valve repair device of any of claims 131-137, wherein the insertion depth indicator comprises a friction-enhancing portion.
139. The valve repair device of any of claims 131-138, wherein the fixed arm comprises two tongue portions that surround a central opening.
140. The valve repair device of any of claims 131-139, wherein at least one of the indicator hinge portion and the clasp hinge portion is a patterned hinge.
141. The valve repair device of any of claims 131-140, wherein the moveable arm is hoop-shaped, and the friction-enhancing portion of the moveable arm comprises longitudinally staggered barbs.
142. The valve repair device of any of claims 131-141, further comprising a base assembly that comprises:
- a shaft;
 - a collar that the shaft extends through; and
 - a cap attached to the shaft such that the cap can be moved by the shaft away from the collar;
- wherein the pair of paddles are attached to the cap; and
- wherein movement of the cap toward the collar causes the pair of paddles to move to the closed position, and movement of the cap away from the collar causes the pair of paddles to move to the open position.
143. The valve repair device of any of claims 131-142, further comprising a coaption element configured to close a gap in the native valve of the patient when the valve repair device is attached to the native valve.
144. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:

a plurality of paddles that are moveable between an open position and a closed position and are configured to attach to the native valve of the patient; and

a clasp attached to each of the plurality of paddles, the clasp comprising:

a fixed arm attached to the paddle;

a moveable arm having a barbed portion;

a clasp hinge portion hingeably connecting the moveable arm to the fixed arm;

an indicator arm; and

an indicator hinge portion hingeably connecting the indicator arm to the fixed arm.

145. The valve repair device of claim 144, wherein the indicator arm is actuatable between undeployed and actuated positions separate from the moveable arm of the clasp.
146. The valve repair device of any of claims 144-145, wherein the indicator arm is the same width as or narrower than the moveable arm.
147. The valve repair device of any of claims 144-146, wherein the indicator arm comprises a barbed portion.
148. The valve repair device of any of claims 144-147, wherein the moveable arm is hoop-shaped and comprises first and second side arms that surround a central opening and wherein the indicator arm is arranged between the first and second side arms within the central opening.
149. The valve repair device of any of claims 144-148, wherein the moveable arm comprises first and second side arms that are separately actuatable and surround a central opening and wherein the indicator arm is arranged between the first and second side arms within the central opening.
150. The valve repair device of any of claims 144-149, wherein the indicator arm extends from the indicator hinge portion to an indicator arm length that is less than a distance between the clasp hinge portion and the barbed portion of the moveable arm.

151. The valve repair device of any of claims 144-150, wherein a maximum engagement depth is defined as a distance between the clasp hinge portion and the barbed portion.
152. The valve repair device of claim 151, wherein the indicator arm extends to a length that is at least one of about 25 percent of the maximum engagement depth, about 50 percent of the maximum engagement depth, about 75 percent of the maximum engagement depth, and about 90 percent of the maximum engagement depth.
153. The valve repair device of any of claims 144-152, wherein the fixed arm comprises two tongue portions that surround a central opening that is wider than a width of the indicator arm.
154. The valve repair device of any of claims 144-153, wherein at least one of the indicator hinge portion and the clasp hinge portion is a patterned hinge.
155. The valve repair device of any of claims 144-154, wherein the moveable arm is hoop-shaped, and the barbed portion of the moveable arm comprises longitudinally staggered barbs.
156. The valve repair device of claim 155, wherein a barbed portion of the indicator arm comprises a barb that is longitudinally staggered with the barbs of the moveable arm.
157. The valve repair device of any of claims 144-156, wherein the indicator arm is actuatable to a fully actuated position that is beyond the fixed arm.
158. The valve repair device of any of claims 144-157, wherein the indicator arm includes an indicating feature.
159. The valve repair device of claim 158, wherein the indicating feature is configured to be compressed by engagement with a leaflet of the native valve.
160. The valve repair device of any of claims 144-159, wherein the fixed arm includes an indicating feature.

161. The valve repair device of claim 160, wherein the indicating feature of the fixed arm is configured to be compressed by engagement with a leaflet of the native valve.
162. The valve repair device of any of claims 144-161, wherein the indicator hinge portion hingeably connects the indicator arm to an attachment portion, and wherein the attachment portion is attached to at least one of the fixed arm of the clasp and the moveable arm of the clasp.
163. The valve repair device of any of claims 144-162, wherein the indicator arm comprises a plurality of indicator arms.
164. The valve repair device of claim 163, wherein each of the plurality of indicator arms has a different length.
165. The valve repair device of claim 164, wherein one of the plurality of indicator arms has a length that is about 50 percent to about 80 percent of a maximum engagement depth measured between the barbed portion and the clasp hinge portion.
166. The valve repair device of claim 164, wherein one of the plurality of indicator arms has a length that is about 75 percent to about 100 percent of a maximum engagement depth measured between the barbed portion and the clasp hinge portion.
167. The valve repair device of any of claims 144-166, further comprising a base assembly that comprises:
- a shaft;
 - a proximal portion that the shaft extends through; and
 - a cap attached to the shaft such that the cap can be moved by the shaft away from the proximal portion;
- wherein the pair of paddles are attached to the cap; and
- wherein movement of the cap toward the proximal portion causes the pair of paddles to move to the closed position, and movement of the cap away from the proximal portion causes the pair of paddles to move to the open position.

168. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:
- a plurality of paddles that are moveable between an open position and a closed position and are configured to attach to the native valve of the patient; and
 - a clasp attached to each of the plurality of paddles, the clasp comprising:
 - a fixed arm attached to the paddle;
 - a moveable arm having a friction-enhancing portion;
 - a hinge portion hingeably connecting the moveable arm to the fixed arm; and
 - a compressible indicator configured to engage a leaflet of the native valve.
169. The valve repair device of claim 168, wherein the compressible indicator is formed as a portion of the moveable arm.
170. The valve repair device of claim 169, wherein the compressible indicator comprises a bump in the moveable arm that is configured to flatten when engaged with the leaflet of the native valve.
171. The valve repair device of any of claims 168, wherein the compressible indicator is formed as a portion of the fixed arm.
172. The valve repair device of claim 171, wherein the compressible indicator comprises a bump in the fixed arm that is configured to flatten when engaged with the leaflet of the native valve.
173. The valve repair device of any of claims 168-172, wherein the clasp further comprises an indicator arm extending from an indicator hinge portion that hingeably attaches the indicator arm to the fixed arm.
174. The valve repair device of claim 173, wherein the compressible indicator is formed as a portion of the indicator arm.
175. The valve repair device of any one of claims 173-174, wherein the moveable arm is a hoop-shaped moveable arm having first and second side arms that surround a central opening and

wherein the indicator arm is arranged within the central opening between the first and second side arms.

176. The valve repair device of claim 175, wherein the indicator arm is formed from a flexible material that conforms to the shape of a leaflet of the native valve when the leaflet is engaged by the indicator arm.
177. The valve repair device of any one of claims 175-176, wherein the indicator arm is capable of extending through the central opening between the first and second side arms.
178. The valve repair device of any of claims 168-177, wherein the compressible indicator comprises an indicating lever extending from at least one of the moveable arm and the fixed arm.
179. The valve repair device of any of claims 168-178, wherein the compressible indicator comprises an indicator spring attached to at least one of the fixed arm and the moveable arm.
180. The valve repair device of any of claims 168-179, further comprising a base assembly that comprises:
 - a shaft;
 - a collar that the shaft extends through; and
 - a cap attached to the shaft such that the cap can be moved by the shaft away from the collar;
 - wherein the pair of paddles are attached to the cap; and
 - wherein movement of the cap toward the collar causes the pair of paddles to move to the closed position, and movement of the cap away from the collar causes the pair of paddles to move to the open position.
181. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:
 - a pair of paddles that are moveable between an open position and a closed position and are configured to attach to the native valve of the patient; and
 - a clasp attached to each of the paddles, the clasp comprising:
 - a fixed arm attached to the paddle;

a moveable arm having a barbed portion;
a hinge portion hingeably connecting the moveable arm to the fixed arm;
an indicator; and
at least one marker attached to at least one of the indicator, the fixed arm, and the moveable arm.

182. The valve repair device of claim 181, further comprising at least one marker on the indicator and at least one indicator on the fixed arm.
183. The valve repair device of claim 182, wherein the at least one marker on the indicator is at least one of a different size and a different shape from the at least one marker on the fixed arm.
184. The valve repair device of any of claims 181, further comprising at least one marker on the indicator and a plurality of indicators on the fixed arm.
185. The valve repair device of claim 184, wherein at least one marker on the indicator is arranged between at least two of the markers on the fixed arm.
186. The valve repair device of any of claims 181-185, further comprising at least one marker on the indicator and at least one indicator on the moveable arm.
187. The valve repair device of claim 186, wherein the at least one marker on the indicator is at least one of a different size and a different shape from the at least one marker on the moveable arm.
188. The valve repair device of any of claims 181-185, further comprising at least one marker on the indicator and a plurality of indicators on the moveable arm.
189. The valve repair device of claim 188, wherein at least one marker on the indicator is arranged between at least two of the markers on the moveable arm.

190. The valve repair device of any of claims 181-189, wherein the at least one marker is formed from at least one of a radio opaque material and a radio reflective material.
191. The valve repair device of any of claims 181-190, wherein the at least one marker is a deformable pad attached to at least one of the fixed arm and the moveable arm.
192. The valve repair device of any of claims 181-191, further comprising:
an indicator arm; and
an indicator hinge portion hingeably connecting the indicator arm to the fixed arm;
wherein the at least one marker is arranged at a distal end of the indicator arm.
193. The valve repair device of claim 192, wherein the indicator arm includes a protrusion portion and at least one marker is arranged on the protrusion portion.
194. The valve repair device of any of claims 181-193, wherein the indicator is a compressible indicator configured to engage a leaflet of the native valve.
195. The valve repair device of claim 194, wherein the compressible indicator is formed as at least one of a portion of the moveable arm and a portion of the fixed arm.
196. The valve repair device of claim 195, wherein the compressible indicator comprises an indicating lever extending from at least one of the moveable arm and the fixed arm.
197. The valve repair device of any of claims 181-196, wherein the indicator is an insertion depth gauge comprising a plurality of flexible arms attached to the moveable arm between the clasp hinge portion and the barbed portion.
198. The valve repair device of any of claims 181-196, wherein the indicator is an insertion depth gauge comprising a plurality of flexible arms attached to the fixed arm.
199. The valve repair device of any of claims 181-198, further comprising a base assembly that comprises:
a shaft;
a collar that the shaft extends through; and

a cap attached to the shaft such that the cap can be moved by the shaft away from the collar;

wherein the pair of paddles are attached to the cap; and

wherein movement of the cap toward the collar causes the pair of paddles to move to the closed position, and movement of the cap away from the collar causes the pair of paddles to move to the open position.

200. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:

a pair of paddles that are moveable between an open position and a closed position and are configured to be attached to the native valve of the patient; and

a clasp attached to each of the plurality of paddles, the clasp comprising:

a fixed arm attached to the inner portion of the paddle;

a moveable arm having a barbed portion;

a hinge portion hingeably connecting the moveable arm to the fixed arm; and

an insertion depth gauge for indicating an insertion depth of a leaflet of the native valve.

201. The valve repair device of claim 200, wherein the insertion depth gauge is deformable, and a shape of the insertion depth gauge indicates the insertion depth of the leaflet of the native valve.

202. The valve repair device of any of claims 200-201, wherein the insertion depth gauge is moveable, and a position of the insertion depth gauge indicates the insertion depth of the leaflet of the native valve.

203. The valve repair device of any of claims 200-202, wherein the relative position of the insertion depth gauge and at least one of the fixed arm and the moveable arm indicates the insertion depth of the leaflet of the native valve.

204. The valve repair device of any of claims 200-203, wherein the insertion depth gauge comprises a plurality of flexible arms attached to at least one of the moveable arm and the fixed arm.

205. The valve repair device of claim 204, wherein the insertion depth of the leaflet is indicated by the number of flexible arms deformed by engagement with the leaflet.
206. The valve repair device of any of claims 200-205, wherein the insertion depth gauge comprises an indicating pad arranged on at least one of the moveable arm and the fixed arm that is configured to deform when engaged by the leaflet of the native valve.
207. The valve repair device of claim 206, wherein the insertion depth of the leaflet is indicated by a size of a deformed portion of the indicating pad.
208. The valve repair device of any of claims 200-207, wherein the insertion depth gauge is actuatable between undeployed and actuated positions.
209. The valve repair device of claim 208, wherein the insertion depth gauge is actuated when the clasp is at least partially open to determine the insertion depth of the leaflet of the native valve.
210. The valve repair device of claim 208, wherein the insertion depth gauge intersects at least one of the fixed arm and the movable arm when the insertion depth gauge is in the actuated position.
211. The valve repair device of any of claims 200-210, wherein the insertion depth gauge comprises a barbed portion.
212. The valve repair device of any of claims 200-211, wherein the fixed arm comprises two tongue portions that surround a central opening.
213. The valve repair device of any of claims 200-212, wherein the moveable arm is hoop-shaped, and the barbed portion comprises longitudinally staggered barbs.
214. The valve repair device of any one of claims 200-213, further comprising a base assembly that comprises:
a shaft;

a collar that the shaft extends through; and
a cap attached to the shaft such that the cap can be moved by the shaft away from the collar;

wherein the pair of paddles are attached to the cap; and

wherein movement of the cap toward the collar causes the pair of paddles to move to the closed position, and movement of the cap away from the collar causes the pair of paddles to move to the open position.

215. A valve repair device for repairing a native valve of a patient, the valve repair device comprising:

a pair of paddles that are moveable between an open position and a closed position and are configured to attach to the native valve of the patient;

a clasp attached to each of the plurality of paddles, the clasp comprising:

a fixed arm attached to the paddle;

a moveable arm having a barbed portion, the moveable arm being moveable between an open position and a closed position;

a hinge portion hingeably connecting the moveable arm to the fixed arm; and

an indicator configured to indicate capture of a leaflet of the native valve.

216. The valve repair device of claim 215, wherein the indicator comprises an indicator arm; and an indicator hinge portion hingeably connecting the indicator arm to at least one of the fixed arm and the movable arm.

217. The valve repair device of claim 216, further comprising a single actuation suture extending from a delivery device to first and second moveable loops attached to the moveable clasp and the indicator arm, respectively, wherein the moveable arm and the indicator arm are separately actuatable with the single actuation suture.

218. The valve repair device of claim 217, wherein the single actuation suture extends from the delivery device, through the first moveable loop, through the second moveable loop, and back into the delivery device.

219. The valve repair device of any of claims 217-218, wherein the single actuation suture extends from the delivery device, through the first moveable loop, through a first fixed loop attached to a proximal end of the coaption element, through a second fixed loop attached to a midpoint of the coaption element, through the second moveable loop, back through the second fixed loop, back through the first fixed loop, back through the first moveable loop, and back into the delivery device.
220. The valve repair device of any of claims 217-219, wherein the first moveable loop is attached proximate a mid-point of the indicator arm and the second moveable loop is attached proximate a distal end of the moveable arm.
221. The valve repair device of any of claims 217-220, wherein the first moveable loop is arranged between the hinge portion of the clasp and the second moveable loop.
222. The valve repair device of any of claims 217-221, wherein the single actuation suture comprises a one-way catch fixedly attached to the single actuation suture.
223. The valve repair device of claim 222, wherein the one-way catch is larger than the first moveable loop so that the one-way catch is prohibited from passing through the first moveable loop.
224. The valve repair device of claim 222, wherein the one-way catch is smaller than the second moveable loop so that the one-way catch is capable of passing through the second moveable loop.
225. The valve repair device of claim 222, wherein the one-way catch is at least one of a rounded bead, cone-shaped, and barbed.
226. The valve repair device of any of claims 216-225, wherein a spring force of the hinge portion is about the same as a spring force of the indicator hinge portion.
227. The valve repair device of any of claims 216-226, wherein a first actuation torque required to actuate the moveable arm is less than a second actuation torque required to actuate the indicator arm.

228. The valve repair device of any of claims 215-227, further comprising a base assembly that comprises:
- a shaft;
 - a collar that the shaft extends through; and
 - a cap attached to the shaft such that the cap can be moved by the shaft away from the collar;
- wherein the pair of paddles are attached to the cap; and
- wherein movement of the cap toward the collar causes the pair of paddles to move to the closed position, and movement of the cap away from the collar causes the pair of paddles to move to the open position.
229. A clasp for a heart valve treatment device comprising:
- a fixed arm attachable to the heart valve treatment device;
 - a moveable arm having a friction-enhancing portion;
 - a hinge portion hingeably connecting the moveable arm to the fixed arm; and
 - an insertion depth indicator configured to provide an indication of an insertion depth of a leaflet of a native valve between the fixed arm and the movable arm when the heart valve treatment device is implanted in a native heart valve.
230. The clasp of claim 229, wherein the insertion depth indicator is deformable, and a shape of the insertion depth indicator indicates the insertion depth of the leaflet of the native valve.
231. The clasp of any of claims 229-320, wherein the insertion depth indicator is moveable, and a position of the insertion depth indicator indicates the insertion depth of the leaflet of the native valve.
232. The clasp of any of claims 229-231, wherein the relative position of the insertion depth indicator and at least one of the fixed arm and the moveable arm indicates the insertion depth of the leaflet of the native valve.
233. The clasp of any of claims 229-232, wherein the insertion depth indicator comprises a plurality of flexible arms attached to the moveable arm between the clasp hinge portion and the friction-enhancing portion.

234. The clasp of claim 233, wherein the insertion depth of the leaflet is indicated by the number of flexible arms deformed by engagement with the leaflet.
235. The clasp of any of claims 229-234, wherein the insertion depth indicator comprises a plurality of flexible arms attached to the fixed arm.
236. The clasp of claim 235, wherein the insertion depth of the leaflet is indicated by the number of flexible arms deformed by engagement with the leaflet.
237. The clasp of any of claims 229-236, wherein the insertion depth indicator comprises an indicating pad arranged on at least one of the moveable arm and the fixed arm that is configured to deform when engaged by the leaflet of the native valve.
238. The clasp of claim 237, wherein the insertion depth of the leaflet is indicated by a size of a deformed portion of the indicating pad.
239. The clasp of any of claims 229-238, wherein the insertion depth indicator is actuatable between undeployed and actuated positions.
240. The clasp of claim 239, wherein the insertion depth indicator is actuated when the clasp is at least partially open to determine the insertion depth of the leaflet of the native valve.
241. The clasp of claim 239, wherein the insertion depth indicator intersects at least one of the fixed arm and the movable arm when the insertion depth indicator is in the actuated position.
242. The clasp of any of claims 229-241, wherein the insertion depth indicator comprises a friction-enhancing portion.
243. The clasp of any of claims 229-242, wherein the fixed arm comprises two tongue portions that surround a central opening.
244. The clasp of any of claims 229-243, wherein the moveable arm is hoop-shaped, and the friction-enhancing portion comprises longitudinally staggered barbs.

245. A heart valve treatment device comprising:
- the clasp of any one of claims 229-244;
 - a shaft;
 - a proximal portion that the shaft extends through; and
 - a cap attached to the shaft such that the cap can be moved by the shaft away from the proximal portion; and
 - a pair of paddles attached to the cap; and
- wherein the heart valve treatment device is configured such that movement of the cap toward the proximal portion causes the pair of paddles to move to the closed position, and movement of the cap away from the proximal portion causes the pair of paddles to move to the open position.




FIG. 1




FIG. 1A




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13






FIG. 13A



1400







FIG. 16






FIG. 18





FIG. 19



20
G^x
F






FIG. 21

22
G
L



23
G^x
FI




FIG. 23A




FIG. 23B




FIG. 25




FIG. 24




FIG. 25A




FIG. 24A




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 33

FIG. 32

FIG. 31

FIG. 30




FIG. 37

FIG. 36

FIG. 35

FIG. 34




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48





FIG. 49



55





FIG. 51






FIG. 53




FIG. 54




FIG. 55




FIG. 56





FIG. 57



50




FIG. 59




FIG. 60




FIG. 61




FIG. 62




FIG. 63




FIG. 64





FIG. 65



உள்ளே




FIG. 67




FIG. 68




FIG. 67A




FIG. 68A





FIG. 69






FIG. 71A




FIG. 71




FIG. 72




FIG. 73




FIG. 74




FIG. 75




FIG. 76




FIG. 77




FIG. 78




FIG. 79




FIG. 80




FIG. 81




FIG. 82




FIG. 83




FIG. 84




FIG. 85




FIG. 86




FIG. 87




FIG. 88




FIG. 89




FIG. 90




FIG. 91




FIG. 92




FIG. 93




FIG. 94




FIG. 95





FIG. 96






FIG. 99




FIG. 100




FIG. 100A




FIG. 101




FIG. 102




FIG. 103B

FIG. 103A

FIG. 103




FIG. 103D

FIG. 103C




FIG. 104




FIG. 105




FIG. 106




FIG. 107




FIG. 108




FIG. 109




FIG. 104A




FIG. 106A




FIG. 108A




FIG. 109A




FIG. 104B




FIG. 106B




FIG. 108B




FIG. 109B




FIG. 104C




FIG. 106C




FIG. 108C




FIG. 109C




FIG. 104D




FIG. 106D




FIG. 108D




FIG. 109D




FIG. 104E




FIG. 106E




FIG. 108E




FIG. 109E




FIG. 110




FIG. 111




FIG. 112




FIG. 113




FIG. 114




FIG. 115




FIG. 116




FIG. 117




FIG. 118




FIG. 119




FIG. 120




FIG. 121




FIG. 122




FIG. 123




FIG. 124




FIG. 125




FIG. 126




FIG. 127




FIG. 123A




FIG. 124A




FIG. 125A




FIG. 126A




FIG. 127A




FIG. 129

FIG. 128




FIG. 130




FIG. 131




FIG. 132




FIG. 129B




FIG. 129C




FIG. 129E








FIG. 129F






FIG. 128A




FIG. 129A




FIG. 130A




FIG. 131A




FIG. 132A




FIG. 133




FIG. 134




FIG. 135




FIG. 136




FIG. 137




FIG. 134A

FIG. 133A




FIG. 135A




FIG. 136A




FIG. 137A




FIG. 134B

FIG. 133B




FIG. 135B




FIG. 136B




FIG. 137B




FIG. 139

FIG. 138




FIG. 140




FIG. 141




FIG. 142




FIG. 139A

FIG. 138A




FIG. 140A




FIG. 141A




FIG. 142A




FIG. 143




FIG. 144




FIG. 145




FIG. 146




FIG. 147




FIG. 148




FIG. 149




FIG. 150




FIG. 151




FIG. 152




FIG. 153




FIG. 154




FIG. 155




FIG. 156




FIG. 157




FIG. 155A




FIG. 160

FIG. 159

FIG. 158




FIG. 161

FIG. 162

FIG. 163




FIG. 166

FIG. 165

FIG. 164




FIG. 164A




FIG. 164B




FIG. 167

FIG. 168




FIG. 169




FIG. 170




FIG. 171




FIG. 173

FIG. 172




FIG. 174




FIG. 175




FIG. 176




FIG. 177




FIG. 178




FIG. 179




FIG. 180




FIG. 181




FIG. 182




FIG. 183




FIG. 184




FIG. 185




FIG. 186A




FIG. 186B




FIG. 188




FIG. 187




FIG. 189




FIG. 190




FIG. 191




FIG. 193




FIG. 192




FIG. 194




FIG. 195




Fig. 196




FIG.197




FIG. 199




FIG. 198




FIG. 200




FIG. 201




FIG. 202




FIG. 202A




FIG. 205

FIG. 204

FIG. 203




FIG. 206




FIG. 207




FIG. 208




FIG. 209




FIG. 210




FIG. 211




FIG. 212




FIG. 213




FIG. 214




FIG. 216




FIG. 215




FIG. 217




FIG. 218




FIG. 219




FIG. 220




FIG. 221




FIG. 222




FIG. 223




FIG. 224




FIG. 225




FIG. 226




FIG. 227




FIG. 228




FIG. 229




FIG. 230




FIG. 231




FIG. 232





FIG. 233



234
G.
L




FIG. 235




FIG. 236





FIG. 237



F. G. 238




FIG. 239




FIG. 240




FIG. 241




FIG. 242




FIG. 243




FIG. 244




FIG. 245




FIG. 246




FIG. 247




FIG. 248




FIG. 249




FIG. 250




FIG. 251




FIG. 252




FIG. 253




FIG. 254




FIG. 255




FIG. 256




FIG. 257




FIG. 258




FIG. 259




FIG. 260








FIG. 261












FIG. 266




FIG. 267




FIG. 269

FIG. 268




FIG. 270




FIG. 271





FIG. 274

FIG. 273

FIG. 272







FIG. 276






FIG. 278




FIG. 279




FIG. 278A





FIG. 279A






Fig. 281






FIG. 282



**FIG. 284**




FIG. 286

FIG. 285






FIG. 287








FIG. 290






FIG. 291








FIG. 293




FIG. 293A




FIG. 294




FIG. 294A




FIG. 295




FIG. 296




FIG. 297




FIG. 298





FIG. 299






FIG. 302




FIG. 303




FIG. 304




FIG. 306




FIG. 305




FIG. 306A




FIG. 308




FIG. 307





FIG. 309






FIG. 310






FIG. 310A









FIG. 312

FIG. 313







FIG. 314A






FIG. 315A




FIG. 316




FIG. 316A





FIG. 318

FIG. 317






FIG. 319A




FIG. 320




FIG. 320A





FIG. 321






FIG. 323




FIG. 322




FIG. 324





FIG. 324A







FIG. 325A






FIG. 326A




FIG. 328

FIG. 327




FIG. 329




FIG. 330




FIG. 331






FIG. 333

FIG. 332








FIG. 336




FIG. 337




FIG. 338




FIG. 339




FIG. 341




FIG. 340




FIG. 342




FIG. 343




FIG. 344




FIG. 345




FIG. 346




FIG. 348




FIG. 347






FIG. 349








FIG. 352




FIG. 353A






FIG. 353B



INTERNATIONAL SEARCH REPORT

International application No.
PCT/US2020/018115

Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☒ Claims Nos.: 118-130
because they relate to subject matter not required to be searched by this Authority, namely:
Rules 39.1 (iv) and 67.IV PCT - Method for treatment of the human or animal body by surgery. The feature ""implanting a valve device in the valve of a patient"" in claims 118,123,127 implies surgery.
2. ☒ Claims Nos.: 5-118, 131-245
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
see FURTHER INFORMATION sheet PCT/ISA/210
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box No. III Observations where unity of invention is lacking (Continuation of Item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fees, this Authority did not invite payment of additional fees.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.
- ☐ The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.
- ☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2020/018115

A. CLASSIFICATION OF SUBJECT MATTER
INV. A61F2/24
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EP0-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2010/022823 A1 (GOLDFARB ERIC A [US] ET AL) 28 January 2010 (2010-01-28) paragraphs [0125], [0127] - [0129]; figures 35,37a,37,b -----	1-4
A	WO 2006/037073 A2 (EVALVE INC [US]; GOLDFARB ERIC A [US] ET AL.) 6 April 2006 (2006-04-06) paragraph [0117]; figure 30 -----	1-4
A	WO 2016/099650 A1 (ABBOTT CARDIOVASCULAR SYSTEMS [US]) 23 June 2016 (2016-06-23) paragraph [0091]; figure 9a -----	1-4



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

26 May 2020

Date of mailing of the international search report

05/06/2020

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Espuch, Antonio

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2020/018115

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2010022823 A1	28-01-2010	US 2010022823 A1	28-01-2010
		US 2012010461 A1	12-01-2012
		US 2014066693 A1	06-03-2014
		US 2019175203 A1	13-06-2019
-----	-----	-----	-----
WO 2006037073 A2	06-04-2006	AU 2005289474 A1	06-04-2006
		CA 2581852 A1	06-04-2006
		CA 2748617 A1	06-04-2006
		EP 1793745 A2	13-06-2007
		JP 5124274 B2	23-01-2013
		JP 2008514307 A	08-05-2008
		US 2007197858 A1	23-08-2007
		WO 2006037073 A2	06-04-2006
-----	-----	-----	-----
WO 2016099650 A1	23-06-2016	CN 107106176 A	29-08-2017
		EP 3232948 A1	25-10-2017
		EP 3628243 A1	01-04-2020
		JP 6685306 B2	22-04-2020
		JP 2017538510 A	28-12-2017
		JP 2020032197 A	05-03-2020
		US 2016174979 A1	23-06-2016
		US 2019133581 A1	09-05-2019
		WO 2016099650 A1	23-06-2016
-----	-----	-----	-----

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

Continuation of Box II.1

Claims Nos.: 118-130

Rules 39.1 (iv) and 67.IV PCT - Method for treatment of the human or animal body by surgery. The feature "implanting a valve device in the valve of a patient" in claims 118,123,127 implies surgery.

Continuation of Box II.2

Claims Nos.: 5-118, 131-245

1 The present application contains 245 claims, of which 27 are independent. There is no clear distinction between the independent claims because of overlapping scope. There are so many claims, and they are drafted in such a way that the claims as a whole are not in compliance with the provisions of clarity and conciseness of Article 6 PCT, as it is particularly burdensome for a skilled person to establish the subject-matter for which protection is sought. The non-compliance with the substantive provisions is to such an extent, that the search was performed taking into consideration the non-compliance in determining the extent of the search (PCT Guidelines 9.19 and 9.25).

2 The search was based on the subject-matter that, as far as can be understood, could reasonably be expected to be claimed later in the procedure, and the corresponding claims, namely claims 1-12, defining a valve repair device with a plurality of indicator arms of different length.

The applicant's attention is drawn to the fact that claims relating to inventions in respect of which no international search report has been established need not be the subject of an international preliminary examination (Rule 66.1(e) PCT). The applicant is advised that the EPO policy when acting as an International Preliminary Examining Authority is normally not to carry out a preliminary examination on matter which has not been searched. This is the case irrespective of whether or not the claims are amended following receipt of the search report or during any Chapter II procedure. If the application proceeds into the regional phase before the EPO, the applicant is reminded that a search may be carried out during examination before the EPO (see EPO Guidelines C-IV, 7.2), should the problems which led to the Article 17(2) declaration be overcome.