



US009168016B2

(12) **United States Patent**  
Ohta et al.

(10) **Patent No.:** US 9,168,016 B2  
(45) **Date of Patent:** \*Oct. 27, 2015

(54) **RADIOGRAPHIC IMAGE CAPTURING APPARATUS, RADIOGRAPHIC IMAGE CAPTURING SYSTEM, AND METHOD OF SUPPLYING ELECTRIC POWER TO RADIOGRAPHIC IMAGE CAPTURING APPARATUS**

(75) Inventors: **Yasunori Ohta**, Kanagawa-ken (JP);  
**Naoyuki Nishino**, Kanagawa-ken (JP);  
**Haruyasu Nakatsugawa**, Kanagawa-ken (JP)

(73) Assignee: **FUJIFILM CORPORATION**, Tokyo (JP)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1253 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **12/929,499**

(22) Filed: **Jan. 28, 2011**

(65) **Prior Publication Data**

US 2011/0186741 A1 Aug. 4, 2011

(30) **Foreign Application Priority Data**

Jan. 29, 2010	(JP)	2010-019628
Jan. 29, 2010	(JP)	2010-019629
Jan. 29, 2010	(JP)	2010-019630
Dec. 10, 2010	(JP)	2010-275181
Dec. 10, 2010	(JP)	2010-275183
Dec. 10, 2010	(JP)	2010-275184

(51) **Int. Cl.**  
**H05G 1/10** (2006.01)  
**H05G 1/64** (2006.01)

(Continued)

(52) **U.S. Cl.**  
CPC ..... **A61B 6/56** (2013.01); **A61B 6/4233** (2013.01); **A61B 6/4494** (2013.01); **A61B 6/548** (2013.01); **G01T 1/24** (2013.01); **H05G 1/10** (2013.01); **H05G 1/30** (2013.01); **H05G 1/32** (2013.01)

(58) **Field of Classification Search**  
CPC ..... H05G 1/10; H05G 1/26; H05G 1/30; H05G 1/32; A61B 6/4233; A61B 6/56; A61B 6/566  
USPC ..... 378/91, 98.8, 101, 102, 115, 116, 117, 378/189; 250/370.09  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,979,198 A	12/1990	Malcolm et al.
5,514,873 A	5/1996	Schulze-Ganzlin et al.

(Continued)

FOREIGN PATENT DOCUMENTS

JP	10-225450	8/1998
JP	11-104117	4/1999

(Continued)

OTHER PUBLICATIONS

National Institute of Advanced Industrial Science & Technology, "Development of Portable X-ray Sources Using Carbon Nanostructures" [online], Mar. 19, 2009, pp. 1-4.

(Continued)


*Primary Examiner* — Allen C. Ho

(74) *Attorney, Agent, or Firm* — Jean C. Edwards, Esq.; Edwards Neils PLLC

(57) **ABSTRACT**

A radiographic image capturing apparatus has a radiation source device including a radiation source for outputting radiation, and a detector device including a radiation detector for detecting radiation that is transmitted through a subject when the subject is irradiated with radiation by the radiation source, and converting the detected radiation into a radiographic image. At least one of the radiation source device and the detector device has an electric power supply limiting unit for limiting supply of electric power, and the electric power supply limiting unit controls supply of electric power between the radiation source device and the detector device, depending on timing of an image capturing process.

**17 Claims, 46 Drawing Sheets**



- (51) **Int. Cl.**  
*A61B 6/00* (2006.01)  
*H05G 1/32* (2006.01)  
*H05G 1/30* (2006.01)  
*G01T 1/24* (2006.01)

(56) **References Cited**  
 U.S. PATENT DOCUMENTS

5,844,961	A *	12/1998	McEvoy et al.	378/98.8
5,877,501	A *	3/1999	Ivan et al.	250/370.09
6,320,934	B1 *	11/2001	Carroll et al.	378/98.8
6,999,558	B2 *	2/2006	Okoda	378/102
7,015,478	B2 *	3/2006	Yamamoto	250/370.09
7,016,467	B2 *	3/2006	Brooks	378/102
7,356,121	B2 *	4/2008	Schwarz	378/101
7,545,914	B2 *	6/2009	Kito et al.	378/98.8
7,629,587	B2	12/2009	Yagi et al.	
7,664,228	B2 *	2/2010	Yi	378/101
7,768,002	B2	8/2010	Kitamura et al.	
7,785,005	B2 *	8/2010	Bettouyashiki et al.	378/189
7,847,258	B2	12/2010	Yaegashi et al.	
7,864,923	B2 *	1/2011	Ohta et al.	378/102
7,874,728	B2 *	1/2011	Fan	378/198
7,977,644	B2 *	7/2011	Kito	250/370.09
7,991,119	B2 *	8/2011	Yoshida et al.	378/114
8,053,738	B2 *	11/2011	Nishino et al.	250/370.09
8,080,802	B2 *	12/2011	Nishino et al.	250/370.08
8,193,509	B2 *	6/2012	Niekawa et al.	250/370.09
8,237,127	B2 *	8/2012	Yoshida et al.	250/370.09
8,265,225	B2 *	9/2012	Nishino et al.	378/98.5
8,292,504	B2 *	10/2012	Bettouyashiki et al.	378/189
8,345,820	B2 *	1/2013	Yoshida et al.	378/62
8,532,260	B2 *	9/2013	Takae et al.	378/102
8,546,777	B2 *	10/2013	Utsunomiya	250/580
8,552,595	B2 *	10/2013	Bohori et al.	307/104
8,798,235	B2 *	8/2014	Ohta et al.	378/102
8,798,236	B2 *	8/2014	Ohta et al.	378/102
8,861,678	B2 *	10/2014	Liu et al.	378/91
8,891,733	B2 *	11/2014	Liu et al.	378/91
8,929,510	B2 *	1/2015	Nishino et al.	378/62
2007/0135182	A1	6/2007	Hanif et al.	
2010/0163737	A1	7/2010	Masuda et al.	

FOREIGN PATENT DOCUMENTS

JP	2000-105297	4/2000
JP	2006-141777	6/2006
JP	2007-103016	4/2007
JP	2007-165960	6/2007
JP	2007-222604	9/2007
JP	2007-530979	11/2007
JP	2009-028449	* 2/2009
JP	2009-32854	2/2009
JP	2009-050689	3/2009
JP	2009-065347	3/2009
JP	2009-162491	7/2009
JP	2009-212389	9/2009
WO	WO 2006/101468 A1	9/2006
WO	WO-2008-146602	12/2008

OTHER PUBLICATIONS

Eisuke Hiro, et al., "Applying Pyroelectric Crystal to Small High Energy X-Ray Source", *Advances in X-Ray Chemical Analysis*, 2010, pp. 195-200, Japan, 41.

Dev. by the Univ. of Tokyo, partial Eng. translation of "Arrival of Contactless Power Transmission Sheet Expected to be Embedded in Walls . . ." [online], Dec 4, 2006, pp. 1-3.

Nikkei Electronics, partial Eng. translation of "Development of Wireless Power Transmission Technology, a 60-W Lamp Turned on in Experiment", Dec. 3, 2007, pp. 117-128.

Rejection of the Application issued by JPO on Jan. 28, 2014 in connection with corresponding Japanese Patent Application No. 2010-275183.

Rejection of the Application issued by JPO on Jan. 28, 2014 in connection with corresponding Japanese Patent Application No. 2010-275181.

Rejection of the Application issued by JPO on Feb. 4, 2014 in connection with corresponding Japanese Patent Application No. 2010-275184.

First Office Action issued by the State Intellectual Property Office of the People's Republic of China (SIPO) on Feb. 28, 2014, in connection with CN201110033502.0 I.

\* cited by examiner



FIG. 2





FIG. 3










FIG. 7





FIG. 8






FIG. 10







FIG. 12






FIG. 14




FIG. 15






FIG. 16








FIG. 18

FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25





FIG. 26







FIG. 27



FIG. 29






FIG. 31







FIG. 33







FIG. 34






FIG. 36



FIG. 38





FIG. 39






FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45





FIG. 46



**RADIOGRAPHIC IMAGE CAPTURING  
APPARATUS, RADIOGRAPHIC IMAGE  
CAPTURING SYSTEM, AND METHOD OF  
SUPPLYING ELECTRIC POWER TO  
RADIOGRAPHIC IMAGE CAPTURING  
APPARATUS**

**CROSS-REFERENCE TO RELATED  
APPLICATION**

This application is based upon and claims the benefit of priority from Japanese Patent Applications No. 2010-019628 filed on Jan. 29, 2010, No. 2010-019629 filed on Jan. 29, 2010, No. 2010-019630 filed on Jan. 29, 2010, No. 2010-275181 filed on Dec. 10, 2010, No. 2010-275183 filed on Dec. 10, 2010 and No. 2010-275184 filed on Dec. 10, 2010, of which the contents are incorporated herein by reference.

**BACKGROUND OF THE INVENTION**

**1. Field of the Invention**

The present invention relates to a radiographic image capturing apparatus, a radiographic image capturing system, and a method of supplying electric power to a radiographic image capturing apparatus. More particularly, the present invention concerns a radiographic image capturing apparatus preferably for use as a portable radiographic image capturing apparatus, which can be carried outdoors by an operator, a radiographic image capturing system, and a method of supplying electric power to a radiographic image capturing apparatus.

**2. Description of the Related Art**

In the medical field, there have widely been used radiographic image capturing apparatus, which apply radiation to a subject and guide radiation that has passed through the subject to a radiation conversion panel (radiation detector), which captures a radiographic image from such radiation. Known forms of radiation conversion panels include conventional radiation film for recording a radiographic image by way of exposure, and stimulable phosphor panels for storing radiation energy representing a radiographic image in a phosphor, and reproducing the radiographic image as stimulated light by applying stimulating light to the phosphor. Radiation film with the recorded radiographic image is supplied to a developing device to develop the radiographic image, or the stimulable phosphor panel is supplied to a reading device to read the radiographic image as a visible image.

In an operating room or the like, for the purpose of quickly and appropriately treating patients, it is necessary to read a recorded radiographic image immediately from a radiation conversion panel after the radiographic image has been captured. As a radiation detector which meets such a requirement, there have been developed a radiation detector of a direct conversion type (electronic cassette) having a solid-state detector for converting radiation directly into electric signals, and a radiation detector of an indirect conversion type (electronic cassette) having a scintillator for temporarily converting radiation into visible light and a solid-state detector for converting such visible light into electric signals (see U.S. Pat. No. 5,514,873).

Such radiographic image capturing apparatus are developed on the assumption that they will be used to capture radiographic images of patients in medical organizations.

There are potential demands for capturing radiographic images outside of medical organizations. To meet such demands, radiographic image capturing apparatus, which are mounted on motor vehicles used to perform medical checkups, have been proposed in the art. However, such proposed

radiographic image capturing apparatus, which are disposed on medical checkup motor vehicles, are relatively large in size. Needs have arisen for capturing radiographic images of persons who suffer from natural disasters at disaster sites, or persons who are receiving home-care services at their homes. However, existing medical checkup motor vehicles cannot be used in the former applications, since it is difficult to get to disaster sites. Although existing medical checkup motor vehicles may be driven to the homes of persons who are receiving home-care services, the image capturing process is highly burdensome to people to be imaged, because they have to be taken from their homes into the medical checkup motor vehicle in order to capture radiographic images of such people. Therefore, there have been demands for small-size portable radiographic image capturing apparatus for use at natural disaster sites or at homes receiving home-care services.

There has been developed a portable radiographic image capturing apparatus, which can be folded into a compact form in its entirety (see Japanese Laid-Open Patent Publication No. 2007-530979 (PCT)). In addition, radiation sources comprising field-electron-emission-type electron sources based on carbon nanotube (CNT) technology have also been developed (see Japanese Laid-Open Patent Publication No. 2007-103016, and AIST: Press Release, "Development of Portable X-ray Sources Using Carbon Nanostructures" [online], Mar. 19, 2009, National Institute of Advanced Industrial Science and Technology, Internet <URL:http://www.aist.go.jp/aistj/press\_release/pr2009/pr20090319/pr20090319.html> (hereinafter referred to as "Document 1")). It is expected that small-size, lightweight radiographic image capturing apparatus including radiation sources will become available in the art. Further, a portable size and high energy X-ray source was developed by using LiTaO<sub>3</sub> that is a typical pyroelectric crystal (see "Applying Pyroelectric Crystal to Small High Energy X-Ray Source", Advances in X-Ray Chemical Analysis, Japan, 41, 2010, pages 195-200 (hereinafter referred to as "Document 2"))).

Wireless electric power transmitting schemes are known from IEDM Plenary Talk, "Arrival of Contactless Power Transmission Sheet Expected to be Embedded in Walls and Floors, developed by the University of Tokyo" [online], Dec. 4, 2006, Internet <URL:http://techon.nikkeibp.co.jp/article/NEWS/20061204/124943/> (hereinafter referred to as "Document 3"), and Nikkei Electronics, "Development of Wireless Power Transmission Technology, a 60-W Lamp Turned on in Experiment," Dec. 3, 2007, pages 117-128 (hereinafter referred to as "Document 4"). The process disclosed in Document 3 transmits electric power based on electromagnetic induction from a primary coil embedded in a contactless power transmission sheet. The process disclosed in Document 4 is a wireless power transmission technology based on magnetic field resonance between two LC resonators.

If a small-size radiation source can be reduced in size as disclosed in Japanese Laid-Open Patent Publication No. 2007-530979 (PCT), Japanese Laid-Open Patent Publication No. 2007-103016, Document 1, and Document 2, then the radiation source may be combined with an electronic cassette as disclosed in U.S. Pat. No. 5,514,873 in order to reduce the size and weight of the radiographic image capturing apparatus, which includes a radiation source and an electronic cassette, thereby allowing the radiographic image capturing apparatus to be moved with ease. In other words, a portable radiographic image capturing apparatus can be realized.

However, since such a portable radiographic image capturing apparatus mainly is used outdoors, a problem arises as to

the availability of a power supply therefor. One solution would be to carry separate batteries together with the portable radiographic image capturing apparatus. More specifically, it is necessary to prepare a battery dedicated for the radiation source, a battery dedicated for the electronic cassette, and a battery dedicated for a controller (personal computer), etc., for use with the portable radiographic image capturing apparatus. In addition to such batteries, backup batteries also need to be carried, in case images have to be recaptured or additional images have to be captured. As a result, the entire radiographic image capturing system to be carried around is liable to be of an increased size and weight, thus reducing the ease (including portability) with which the radiographic image capturing system can be used.

#### SUMMARY OF THE INVENTION

An object of the present invention is to provide a radiographic image capturing apparatus, a radiographic image capturing system, and a method of supplying electric power to a radiographic image capturing apparatus which are capable of supplying electric power to a radiation source and a radiation detector even outdoors, reducing consumption of electric power, and minimizing the number batteries used therein, which can be used easily and efficiently outdoors or the like.

According to an aspect of the present invention, there is provided a radiographic image capturing apparatus comprising a radiation source device including a radiation source for outputting radiation, and a detector device including a radiation detector for detecting radiation that is transmitted through a subject when the subject is irradiated with radiation by the radiation source, and converting the detected radiation into a radiographic image, at least one of the radiation source device and the detector device having an electric power supply limiting unit for limiting supply of electric power, the electric power supply limiting unit controlling supply of electric power between the radiation source device and the detector device, depending on timing of an image capturing process.

In the radiographic image capturing apparatus, the electric power supply limiting unit supplies electric power between the radiation source device and the detector device, based on an electric power supply request made before the image capturing process.

In the radiographic image capturing apparatus, the electric power supply limiting unit supplies electric power between the radiation source device and the detector device, upon completion of the image capturing process.

In the radiographic image capturing apparatus, the electric power supply limiting unit comprises an electric power controller for supplying electric power between the radiation source device and the detector device, and an electric power supply limiter for limiting supply of the electric power by the electric power controller between the radiation source device and the detector device, during a period in which the radiographic image is being captured based on the radiation.

According to another aspect of the present invention, there is also provided a radiographic image capturing system comprising a radiation source device including a radiation source for outputting radiation, a detector device including a radiation detector for detecting radiation that is transmitted through a subject when the subject is irradiated with radiation by the radiation source, and converting the detected radiation into a radiographic image, and an electric power supply limiting unit controlling supply of electric power between the

radiation source device and the detector device, depending on timing of an image capturing process.

In the radiographic image capturing system, the electric power supply limiting unit supplies electric power between the radiation source device and the detector device, based on an electric power supply request made before the image capturing process.

In the radiographic image capturing system, the electric power supply limiting unit supplies electric power between the radiation source device and the detector device, upon completion of the image capturing process.

In the radiographic image capturing system, the electric power supply limiting unit comprises an electric power controller for supplying electric power between the radiation source device and the detector device, and an electric power supply limiter for limiting supply of the electric power by the electric power controller between the radiation source device and the detector device, during a period in which the radiographic image is being captured based on the radiation.

According to still another aspect of the present invention, there is also provided a method of supplying electric power to a radiographic image capturing apparatus comprising a radiation source device including a radiation source for outputting radiation, and a detector device including a radiation detector for detecting radiation that is transmitted through a subject when the subject is irradiated with radiation by the radiation source, and converting the detected radiation into a radiographic image, the method comprising the step of controlling supply of electric power between the radiation source device and the detector device, depending on timing of an image capturing process.

According to the present invention, the radiation source and the radiation detector can be supplied with electric power even if the radiographic image capturing apparatus is used outdoors. Also, electric power consumption can be reduced. Batteries that need to be included in the radiographic image capturing apparatus are minimized. Therefore, the radiographic image capturing apparatus is convenient for outdoor use or the like.

The above and other objects, features, and advantages of the present invention will become more apparent from the following description when taken in conjunction with the accompanying drawings in which preferred embodiments of the present invention are shown by way of illustrative example.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a radiographic image capturing apparatus (first radiographic image capturing apparatus) according to a first embodiment of the present invention;

FIG. 2 is a perspective view showing the manner in which the first radiographic image capturing apparatus is carried;

FIG. 3 is a horizontal cross-sectional view taken along line of FIG. 1;

FIG. 4 is a cross-sectional view of the first radiographic image capturing apparatus, showing a radiation source device separated from a cassette;

FIG. 5 is a cross-sectional view, shown partially in block form, of internal details of the radiation source device shown in FIG. 1;

FIG. 6 is an elevational view, partially in cross section, showing the manner in which the first radiographic image capturing apparatus captures a radiographic image;

FIG. 7 is an elevational view showing the manner in which the first radiographic image capturing apparatus is readied to capture radiographic images;

5

FIG. 8 is an elevational view showing the manner in which the first radiographic image capturing apparatus captures a radiographic image;

FIG. 9 is a schematic view showing a pixel array of a radiation detector of the first radiographic image capturing apparatus;

FIG. 10 is a block diagram of a circuit arrangement of the radiation detector disposed in the cassette;

FIG. 11 is a block diagram of the first radiographic image capturing apparatus;

FIG. 12 is a perspective view of a mobile terminal, which displays a radiographic image on a display unit thereof;

FIG. 13 is a block diagram of a battery unit;

FIG. 14 is a block diagram of a battery controller;

FIG. 15 is a block diagram of a power controller according to a first specific example;

FIG. 16 is a block diagram of a power controller (including a power manager) according to a second specific example;

FIG. 17 is a block diagram of a cassette selection activator and a cassette selector;

FIG. 18 is a block diagram of an integrated supply activator and an integrated supply;

FIG. 19 is a block diagram of a power manager;

FIG. 20 is a first flowchart of an operation sequence of the first radiographic image capturing apparatus, operated under supply timing conditions, which are free of timing controls;

FIG. 21 is a second flowchart of an operation sequence of the first radiographic image capturing apparatus, operated under supply timing conditions, which are free of timing controls;

FIG. 22 is a first flowchart of an operation sequence of the first radiographic image capturing apparatus, operated under supply timing conditions for supplying electric power before capturing of radiographic images;

FIG. 23 is a second flowchart of an operation sequence of the first radiographic image capturing apparatus, operated under supply timing conditions for supplying electric power before capturing of radiographic images;

FIG. 24 is a third flowchart of an operation sequence of the first radiographic image capturing apparatus, operated under supply timing conditions for supplying electric power before capturing of radiographic images;

FIG. 25 is a first flowchart of an operation sequence of the first radiographic image capturing apparatus, operated under supply timing conditions for supplying electric power after capturing of radiographic images;

FIG. 26 is a second flowchart of an operation sequence of the first radiographic image capturing apparatus, operated under supply timing conditions for supplying electric power after capturing of radiographic images;

FIG. 27 is a perspective view of a modification of the first radiographic image capturing apparatus;

FIG. 28 is a perspective view of another modification of the first radiographic image capturing apparatus;

FIG. 29 is a perspective view of still another modification of the first radiographic image capturing apparatus;

FIG. 30 is a perspective view of a radiographic image capturing apparatus (second radiographic image capturing apparatus) according to a second embodiment of the present invention;

FIG. 31 is a perspective view showing the manner in which the second radiographic image capturing apparatus is carried;

FIG. 32 is a horizontal cross-sectional view taken along line XXXII-XXXII of FIG. 30;

FIG. 33 is a plan view of the second radiographic image capturing apparatus, showing a radiation source device separated from a cassette shown in FIG. 30;

6

FIG. 34 is a cross-sectional view showing the manner in which the second radiographic image capturing apparatus captures a radiographic image;

FIG. 35 is a view showing in greater detail a source-to-image distance (SID) that is illustrated in FIG. 34;

FIG. 36 is a perspective view showing the manner in which the second radiographic image capturing apparatus is readied to capture radiographic images;

FIG. 37 is a perspective view showing the manner in which the second radiographic image capturing apparatus captures a radiographic image;

FIG. 38 is a perspective view of a radiographic image capturing apparatus (third radiographic image capturing apparatus) according to a third embodiment of the present invention;

FIG. 39 is a perspective view of the third radiographic image capturing apparatus;

FIG. 40 is a side elevational view of the third radiographic image capturing apparatus;

FIG. 41 is a perspective view showing the manner in which the third radiographic image capturing apparatus is carried;

FIG. 42 is a block diagram of a portion of a PC (Personal Computer), which is used with the third radiographic image capturing apparatus;

FIG. 43 is a block diagram of an electric power collector of the third radiographic image capturing apparatus;

FIG. 44 is a flowchart of an operation sequence of the power collector shown in FIG. 43;

FIG. 45 is a cross-sectional view schematically illustrating the structure of three pixel units of a radiation detector according to a modified example of the invention; and

FIG. 46 is a view schematically illustrating the structure of a TFT and a charge storage unit shown in FIG. 45.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

Like or corresponding parts are denoted by like or corresponding reference characters throughout the views.

As shown in FIGS. 1 and 2, a radiographic image capturing apparatus 10A according to a first embodiment of the present invention, which hereinafter will be referred to as a "first radiographic image capturing apparatus 10A," includes a cassette (detector device) 12 having a substantially rectangular outer contour shaped as a housing, and which is made of a material permeable to radiation 46 (see FIG. 5), and a cylindrical radiation source device 18 held in the cassette 12 by a pair of holders 16a, 16b, which project outwardly from opposite ends of one side 14a of the cassette 12.

The cassette 12 has crisscross guide lines 22 disposed on a surface (irradiated surface) 20 thereof, which serve as a reference for an image capturing area and an image capturing position. The cassette 12 also has a grip 24 on another side 14b thereof remote from the one side 14a. The cassette 12 has two other sides 14c, 14d extending perpendicular to and between the sides 14a, 14b, which are opposite to each other. On the side 14c, there are disposed a USB (Universal Serial Bus) terminal 28 as an interface means for sending information to and receiving information from an external device, a card slot 32 for insertion of a memory card 30 therein, and an unlocking button 34 to be described later. The side 14c also supports thereon a mobile terminal 42, which is detachable from the cassette 12. The mobile terminal 42 includes a display unit 36 and an operating unit 40 having a number of control buttons operable by a doctor or radiological technician (hereinafter referred to as an "operator") 38 who handles the first radiographic image capturing apparatus 10A. The

radiation source device **18** has an exposure switch **48**, which can be operated by the operator **38** in order to cause a radiation source **44** (see FIG. 5), which shall be described later, to start emitting radiation **46**.

FIGS. 1 and 2 show the first radiographic image capturing apparatus **10A**, which is carried by the operator **38**. When the first radiographic image capturing apparatus **10A** is carried, the radiation source device **18** and the cassette **12** are integrally joined to each other. The operator **38** grips the grip **24** and carries the first radiographic image capturing apparatus **10A** to a desired site, such as an accident site, a disaster site, a medical checkup site, or a home receiving home-care services outside of a medical organization. When the operator **38** arrives at the site, the operator **38** operates the first radiographic image capturing apparatus **10A** in order to capture radiographic images of a victim at the accident site or the disaster site, or an examinee at the medical checkup site, or a person receiving home-care services at home. The victim or person whose radiographic images are to be captured will hereinafter be referred to as a "subject" **50** (see FIG. 6).

When the radiation source device **18** and the cassette **12** are joined to each other integrally, they are secured together by a joining mechanism **82** (see FIG. 3), to be described later, so that the first radiographic image capturing apparatus **10A** can be carried by the operator **38**.

The portable first radiographic image capturing apparatus **10A**, which has been brought to a site such as an accident site or a disaster site outside of a medical organization, or to a home receiving home-care services outside of a medical organization, will be described below with reference to FIGS. 3 through 8.

As shown in FIG. 3, the sides **14a**, **14b**, **14c**, **14d** of the cassette **12** are constituted by respective side walls **52a**, **52b**, **52c**, **52d**. The USB terminal **28**, the card slot **32**, and the unlocking button **34** are provided on the side wall **52c**. The side wall **52c** has a recess **54**, which is defined between the card slot **32** and the unlocking button **34**. The mobile terminal **42** (see FIG. 2) can be placed in the recess **54**.

When the unlocking button **34** is pressed by the operator **38** (see FIG. 2), the unlocking button **34** is displaced along the side wall **52a** toward the side wall **52d**. A slide **56** projects along the side wall **52a** from a surface of the unlocking button **34** that faces the side wall **52d**, and a spring **60** acts between the slide **56** and a tooth **58** that projects inwardly from the side wall **52a**. The spring **60** normally biases the unlocking button **34** to move in a direction from the tooth **58** toward the side wall **52c**. The side wall **52a** has a through hole **62** defined in a portion thereof against which the slide **56** slides, the through hole **62** extending from an inner surface of the side wall **52a** to an outer surface thereof. The slide **56** has a hook **64**, which extends through the through hole **62**.

As shown in FIGS. 3 and 4, the radiation source device **18** has a through hole **66** defined therein at a location aligned with the through hole **62** of the cassette **12** when the radiation source device **18** is held in the cassette **12** by the holders **16a**, **16b**. The through hole **66** is of substantially the same size as the through hole **62**. When the hook **64** is displaced toward the side wall **52c** under the bias of the spring **60**, the hook **64** engages with an edge of the through hole **66** and locks the radiation source device **18** in place, thereby integrally joining the radiation source device **18** to the cassette **12** (see FIG. 3).

The radiation source device **18** has an electrically conductive connection terminal (first radiation source connection terminal) **68a** mounted on an end thereof that faces the holder **16a**, and also has an electrically conductive connection terminal (second radiation source connection terminal) **68b** mounted on another end thereof that faces the holder **16b**. The

first radiation source connection terminal **68a** is convex in shape toward the holder **16a**, whereas the second radiation source connection terminal **68b** is concave in shape toward the holder **16b**. The radiation source device **18** has a first energy input/output unit **300**, or a second energy input/output unit **302** (see FIG. 13) for inputting and outputting electric power through a wired or wireless link, for example. The first radiation source connection terminal **68a** and the second radiation source connection terminal **68b**, for example, constitute the first energy input/output unit **300** or the second energy input/output unit **302**, respectively, and may be electrically connected through a wireless link. The first energy input/output unit **300** or the second energy input/output unit **302** is mounted on a side wall of the radiation source device **18** (see FIG. 1).

The holder **16a** of the cassette **12** has an electrically conductive connection terminal (first cassette connection terminal) **70a** on a surface thereof that faces the radiation source device **18**. The holder **16b** of the cassette **12** has an electrically conductive connection terminal (second cassette connection terminal) **70b** on a surface thereof that faces the radiation source device **18**. The first cassette connection terminal **70a** is concave, complementary in shape to the convex first radiation source connection terminal **68a**, whereas the second cassette connection terminal **70b** is convex, complementary in shape to the concave second radiation source connection terminal **68b**. The cassette **12** has a first energy input/output unit **300** or a second energy input/output unit **302** (see FIG. 13) for inputting and outputting electric power through a wired or wireless link, for example. The first cassette connection terminal **70a** and the second cassette connection terminal **70b**, for example, constitute the first energy input/output unit **300** or the second energy input/output unit **302**, and may be electrically connected through a wireless link. The first energy input/output unit **300** or the second energy input/output unit **302** is mounted on the side **14c** of the cassette **12**.

As shown in FIG. 3, when the hook **64** engages the edge of the through hole **66** under the resiliency of the spring **60** in order to keep the radiation source device **18** and the cassette **12** joined integrally with each other, the convex first radiation source connection terminal **68a** and the concave first cassette connection terminal **70a** engage with each other, and the concave second radiation source connection terminal **68b** and the convex second cassette connection terminal **70b** engage with each other, respectively. Therefore, the radiation source device **18** and the cassette **12** are securely and integrally joined with each other. Consequently, the connection terminals **68a**, **68b**, **70a**, **70b** function as members for assisting the hook **64** and the through hole **66** in maintaining the radiation source device **18** and the cassette **12** in an integrally joined condition.

As shown in FIG. 4, when the operator **38** presses the unlocking button **34** to move the unlocking button **34** toward the side wall **52d** against the resiliency of the spring **60**, the hook **64** and the slide **56** are displaced toward the side wall **52d**, so as to bring the hook **64** out of engagement with the edge of the through hole **66**. While the hook **64** is kept out of engagement with the edge of the through hole **66**, i.e., while the operator **38** presses the unlocking button **34**, the operator **38** can remove or separate the radiation source device **18** from the cassette **12**, whereby the radiation source device **18** and the cassette **12** are released from each other.

The cassette **12** houses therein a tape measure **72** comprising a ribbon **76** marked with graduations **74**, which is coiled into a roll by a spring, not shown, in the tape measure **72**. The tape measure **72** is combined with a rotary encoder **78** on one side thereof, for detecting the length by which the ribbon **76**

is reeled out from the tape measure 72. The ribbon 76, which is reeled out from the tape measure 72, extends through a hole 80 that is defined in the side wall 52a at a location facing the tape measure 72, and a distal end of the ribbon 76 is fixed to the radiation source device 18 near the second connection terminal 68b.

When the radiation source device 18 and the cassette 12 are joined integrally with each other as shown in FIG. 3, most of the ribbon 76 is coiled into a roll inside the tape measure 72 under the resiliency of the spring. On the other hand, when the radiation source device 18 and the cassette 12 are not joined integrally with each other, as shown in FIGS. 4 through 8, the ribbon 76 can be pulled out of the tape measure 72 through the hole 80 by separating the radiation source device 18 away from the cassette 12 against the resiliency of the spring.

The unlocking button 34, the slide 56, the spring 60, the hook 64, the connection terminals 68a, 68b, 70a, 70b, and the tape measure 72 jointly make up a joining mechanism 82 for integrally joining the radiation source device 18 and the cassette 12 with each other when the first radiographic image capturing apparatus 10A is carried, and also for enabling the radiation source device 18 and the cassette 12 to be separated from each other when the first radiographic image capturing apparatus 10A is utilized to capture radiographic images.

The tape measure 72 comprises the ribbon 76, which is marked with graduations 74 in the illustrated embodiment. However, as a functional equivalent to the ribbon 76, the tape measure 72 may comprise a string marked with graduations 74.

As shown in FIGS. 3 and 6, the cassette 12 also houses therein a grid 84 for removing scattered rays of radiation 46 from the subject 50 when the radiation source 44 applies radiation 46 with respect to the subject 50, a radiation detector 86 for detecting radiation 46 that has passed through the subject 50, and a lead plate 88 for absorbing back scattered rays of radiation 46, which are successively arranged in this order from the irradiated surface 20 of the cassette 12. The irradiated surface 20 of the cassette 12 may also be constructed as the grid 84.

The radiation detector 86 may comprise a radiation detector (including a front surface reading type and a rear surface reading type) of an indirect conversion type, including a scintillator for converting radiation 46 that has passed through the subject 50 into visible light, and solid-state detectors (hereinafter also referred to as pixels) made of amorphous silicon (a-Si) or the like for converting the visible light into electric signals. A radiation detector of ISS (Irradiation Side Sampling) type as a front surface reading type, comprises solid-state detectors and a scintillator that are successively provided along an irradiation direction of the radiation 46. A radiation detector of PSS (Penetration Side Sampling) type as a rear surface reading type, comprises a scintillator and solid-state detectors that are successively provided along the irradiation direction of the radiation 46. As well as the above-described indirect conversion type, the radiation detector 86 may also comprise a radiation detector of a direct conversion type, comprising solid-state detectors made of amorphous selenium (a-Se) or the like for converting a dose of radiation 46 directly into electric signals.

As shown in FIG. 3, the cassette 12 also houses therein a battery unit 304 as a power supply for the cassette 12, a battery controller (electric power supply limiting unit) 306 for limiting and controlling supply of electric power to the battery unit 304, a cassette controller 92 for controlling the radiation detector 86 (see FIG. 6) with electric power supplied from the battery unit 304, and a transceiver 94 for sending and receiving signals including information concern-

ing radiation 46 that is detected by the radiation detector 86, to and from an external circuit. A plate of lead or the like should preferably be placed over the side surfaces of the cassette controller 92 and the transceiver 94 under the irradiated surface 20 in order to protect the cassette controller 92 and the transceiver 94 against damage, which would otherwise be caused if the cassette controller 92 and the transceiver 94 were irradiated with radiation 46.

The battery unit 304 supplies electric power to the rotary encoder 78, the radiation detector 86, the cassette controller 92, and the transceiver 94 in the cassette 12. The battery unit 304 can also charge the mobile terminal 42 when the mobile terminal 42 is placed in the recess 54. As shown in FIG. 13, the battery unit 304 includes, in addition to the first energy input/output unit 300 and the second energy input/output unit 302, a battery (electric power storage unit) 308, a first energy converter 310, and a second energy converter 312. The battery unit 304 can be supplied with (i.e., charged by) electric power from an external circuit, or can supply electric power to an external circuit, over a wired or wireless link via the first energy input/output unit 300 and/or the second energy input/output unit 302. A first switcher 314a is connected between the first energy input/output unit 300 and the first energy converter 310. A second switcher 314b is connected between the second energy input/output unit 302 and the second energy converter 312. Third through fifth switchers 314c through 314e are connected between the battery 308 and the first energy input/output unit 300 and the second energy input/output unit 302.

The first energy converter 310 comprises a first input converter 316 and a first output converter 318. The second energy converter 312 comprises a second input converter 320 and a second output converter 322. For inputting electric power via the first energy input/output unit 300, the first switcher 314a electrically connects the first energy input/output unit 300 and the first input converter 316 to each other, while the third switcher 314c and the fifth switcher 314e electrically connect the first input converter 316 and the battery 308 to each other. Conversely, for outputting electric power via the first energy input/output unit 300, the first switcher 314a electrically connects the first energy input/output unit 300 and the first output converter 318 to each other, while the third switcher 314c and the fifth switcher 314e electrically connect the first output converter 318 and the battery 308 to each other. Similarly, for inputting electric power via the second energy input/output unit 302, the second switcher 314b electrically connects the second energy input/output unit 302 and the second input converter 320 to each other, while the fourth switcher 314d and the fifth switcher 314e electrically connect the second input converter 320 and the battery 308 to each other. Conversely, for outputting electric power via the second energy input/output unit 302, the second switcher 314b electrically connects the second energy input/output unit 302 and the second output converter 322 to each other, while the fourth switcher 314d and the fifth switcher 314e electrically connect the second output converter 322 and the battery 308 to each other. The first through fifth switchers 314a through 314e are controlled by an electric power supply controller 374, to be described later, in order to make such connections.

The first energy input/output unit 300, the second energy input/output unit 302, the first energy converter 310, and the second energy converter 312 have different structures depending on the type of energy to be supplied (supplied energy).

For example, if electric energy is supplied through wired connections such as cables, connection terminals, etc., then the first energy input/output unit 300 comprises a connector,

which is connected to cables and connection terminals. The first input converter **316** comprises a voltage converter or the like for converting a voltage applied from the first energy input/output unit **300** through the first switcher **314a** into a voltage that is optimum for charging the battery **308**. The first output converter **318** comprises a voltage converter or the like for converting a voltage output from the battery **308** through the fifth switcher **314e** and the third switcher **314c** into a voltage that is optimum for power transmission. The second energy input/output unit **302** and the second energy converter **312** also are of a similar construction.

If electric energy is supplied by way of electromagnetic induction through a coil (primary coil or secondary coil) embedded in a contactless power transmission sheet, for example as disclosed in Document 3, then the first energy input/output unit **300** comprises a secondary coil or a primary coil, whereas the first input converter **316** comprises a voltage converter or the like for converting a voltage generated by the first energy input/output unit **300**, which functions as a secondary coil, into a voltage that is optimum for charging the battery **308**. Further, the first output converter **318** comprises a voltage-to-current converter for converting a voltage output from the battery **308** through the fifth switcher **314e** and the third switcher **314c** into a current that flows to the first energy input/output unit **300**, which functions as a primary coil. The second energy input/output unit **302** and the second energy converter **312** also are of a similar construction.

If electric energy is supplied by way of wireless power transmission technology based on magnetic resonance as disclosed in Document 4, then the first energy input/output unit **300** comprises a second LC resonator or a first LC resonator, which is combined with a first LC resonator or a second LC resonator of an electric power transmitter, whereas the first input converter **316** comprises a coil, i.e., a secondary coil combined with a primary coil as the coil of the second LC resonator, for converting electromagnetic energy generated by the first energy input/output unit **300**, which functions as the second LC resonator. Further, the first output converter **318** comprises a coil, i.e., a primary coil combined with a secondary coil as the coil of the first LC resonator, for outputting a voltage output from the battery **308** through the fifth switcher **314e** and the third switcher **314c** as electromagnetic energy from the first energy input/output unit **300**, which functions as the first LC resonator. The second energy input/output unit **302** and the second energy converter **312** also are of a similar construction.

The supplied energy may be optical energy or thermal energy. If the supplied energy is optical energy, then an energy receiver is provided, which comprises a photodetector for detecting optical energy, and an energy converter is provided, which comprises a photoelectric transducer (photoelectric converter) for converting the detected optical energy into electric power. If the supplied energy is thermal energy, then an energy receiver is provided, which comprises a thermal sensor for detecting thermal energy, and an energy converter is provided, which comprises a thermoelectric transducer, i.e., a thermoelectric transducer based on the Seebeck Effect, for converting the detected thermal energy into electric power.

The battery **308** may comprise a secondary battery, such as a nickel hydrogen battery, a nickel cadmium battery, a lithium battery, or the like, or a capacitor, such as a catalytic capacitor, an electric double-layer capacitor, a lithium ion capacitor, or the like. The battery **308** may be detachably mounted on the cassette **12**. The battery **308** may comprise a small-size built-in capacitor, which is capable of storing an amount of electric power required to capture at least one radiographic image.

Since the transceiver **94** is capable of sending signals to and receiving signals from an external circuit, the transceiver **94** can send signals to and receive signals from a transceiver **98** (see FIG. **11**) of the mobile terminal **42**, which is removed from the recess **54**, and also can send signals to and receive signals from a transceiver **100** of the radiation source device **18**, which is separated from the cassette **12**. Even when the cassette **12** and the radiation source device **18** are integrally coupled to each other and/or if the mobile terminal **42** is placed in the recess **54**, the transceiver **94** can send signals to and receive signals from the transceivers **98**, **100**.

As shown in FIG. **5**, the radiation source device **18** houses therein the radiation source **44**, a battery unit **304**, a battery controller **306** for controlling the battery unit **304**, a transceiver **100**, a radiation source controller **102** for controlling the radiation source **44**, and a laser pointer **104**. The first energy input/output unit **300** and the second energy input/output unit **302**, which are identical to those provided on the cassette **12**, are mounted on a side wall of the casing of the radiation source device **18**.

The radiation source **44** comprises a field-electron-emission-type radiation source, which is similar to the field-electron-emission-type radiation source disclosed in Japanese Laid-Open Patent Publication No. 2007-103016.

The radiation source **44** includes a disk-shaped rotary anode **110** mounted on a rotational shaft **108**, which can be rotated about its axis by a rotating mechanism **106**, an annular target layer **112** disposed on the surface of the rotary anode **110** and made up principally from a metallic element such as Mo or the like, a cathode **114** disposed in confronting relation to the rotary anode **110**, and a field-electron-emission-type electron source **116** disposed on the cathode **114** in confronting relation to the target layer **112**.

When the operator **38** operates the exposure switch **48**, the radiation source controller **102** controls the radiation source **44** to output radiation **46**. More specifically, when the radiation source **44** is controlled by the radiation source controller **102**, the rotating mechanism **106** rotates the rotational shaft **108** so as to rotate the rotary anode **110**. The battery unit **304** supplies electric power to a power supply **118**, which applies a negative voltage to the field-electron-emission-type electron source **116**. The battery unit **304** also supplies electric power to a power supply **120**, which applies a voltage between the rotary anode **110** and the cathode **114**. More specifically, a positive voltage is applied to the rotary anode **110**, whereas a negative voltage is applied to the cathode **114**. The field-electron-emission-type electron source **116** emits electrons, which are accelerated and bombard the target layer **112** due to the voltage applied between the rotary anode **110** and the cathode **114**. The electrons are focused onto a focus point **122** on the surface of the target layer **112**, and the bombarded surface of the target layer **112** emits radiation **46** from the focus point **122** at an intensity level depending on the applied electrons. As the radiation source **44**, a portable size and high energy X-ray source that is disclosed in Document 2 and uses a crystal of tourmaline,  $\text{LiNbO}_3$ ,  $\text{LiTaO}_3$ ,  $\text{ZnO}$ , and the like, may be employed. In this case, for example, about 100 kV voltage can be generated by using  $\text{LiNbO}_3$ , whose axial length is 1 cm.

For irradiating the subject **50** with radiation **46** in order to capture radiographic images of the subject **50**, it is necessary first to perform a preparatory procedure, thus readying the first radiographic image capturing apparatus **10A** for capturing radiographic images. The preparatory procedure includes a process for presetting a source-to-image distance (SID), which represents the distance (imaging distance) between the focus point **122** of the radiation source **44** and a position **124**

(see FIG. 6) on the radiation detector 86 located directly beneath the focus point 122, and a process for bringing the center of a range within which the irradiated surface 20 is irradiated with radiation 46 into alignment with a central position 126, i.e., a point of intersection, of the aforementioned crisscross guide lines 22.

The preparatory procedure is carried out as follows. As shown in FIGS. 6 and 7, while the radiation source device 18 is separated from the cassette 12, the operator 38 pulls the ribbon 76 from the tape measure 72 until the length of the ribbon 76, which is reeled out from the tape measure 72, is equal to a reeled-out length 11 that depends on the SID. The laser pointer 104 is controlled by the radiation source controller 102 to apply and focus a laser beam 128 on the irradiated surface 20, in order to display a crisscross mark 130 on the irradiated surface 20, which represents the center of a range within which the irradiated surface 20 is irradiated with radiation 46.

The SID, the reeled-out length 11 that depends on the SID, and a distance 12 between the position 124 or the central position 126 and the side 14a, which has the hole 80 through which the ribbon 76 is pulled out, are related to each other according to the equation  $SID \approx (11^2 - 12^2)^{1/2}$ . The distance 12 is constant.

After the ribbon 76 has been pulled out from the tape measure 72 by the reeled-out length 11, the operator 38 positionally adjusts the radiation source device 18 so as to bring the mark 130 displayed on the irradiated surface 20 into alignment with the central position 126. Thereafter, the operator 38 turns on the exposure switch 48 to cause the radiation source 44 to apply radiation 46 to the subject 50 on the irradiated surface 20, thereby capturing radiographic images of the subject 50, as shown in FIG. 8. In FIG. 8, an example is shown in which a radiographic image of a hand of the subject 50 is captured.

As shown in FIG. 9, the radiation detector 86 comprises a number of pixels 132 arrayed on a substrate, not shown, a number of gate lines 134 for supplying control signals to the pixels 132, and a number of signal lines 136 for reading electric signals output from the pixels 132.

A circuit arrangement of the radiation detector 86, which is of an indirect conversion type, for example, that is housed in the cassette 12, will be described in detail below with reference to FIG. 10.

As shown in FIG. 10, the radiation detector 86 comprises an array of thin-film transistors (TFTs) 140 arranged in rows and columns, and a photoelectric conversion layer 138 including the pixels 132, and made of a material such as amorphous silicon (a-Si) or the like for converting visible light into analog electric signals. The photoelectric conversion layer 138 is disposed on the array of TFTs 140. When radiation 46 is applied to the radiation detector 86, the pixels 132 generate electric charges by converting visible light into analog electric signals. Then, when the TFTs 140 are turned on one row at a time, electric charges are read from the pixels 132 as image signals.

The TFTs 140 are connected respectively to the pixels 132. The gate lines 134, which extend parallel to the rows, and the signal lines 136, which extend parallel to the columns, are connected to the TFTs 140. The gate lines 134 are connected to a line scanning driver 142, and the signal lines 136 are connected to a multiplexer 144. The gate lines 134 are supplied with control signals Von, Voff from the line scanning driver 142 for turning on and off the TFTs 140 along the rows. The line scanning driver 142 comprises a plurality of switches SW1 for switching between the gate lines 134, and an address decoder 146 for outputting a selection signal for selecting one

of the switches SW1 at a time. The cassette controller 92 supplies an address signal to the address decoder 146.

The signal lines 136 are supplied with electric charges stored by the pixels 132 through the TFTs 140 arranged in the columns. The electric charges supplied to the signal lines 136 are amplified by amplifiers 148, which are connected respectively to the signal lines 136. The amplifiers 148 are connected through respective sample and hold circuits 150 to the multiplexer 144. The multiplexer 144 comprises a plurality of switches SW2 for successively switching between the signal lines 136, and an address decoder 152 for outputting selection signals for selecting one of the switches SW2 at a time. The address decoder 152 is supplied with an address signal from the cassette controller 92. The multiplexer 144 has an output terminal connected to an A/D converter 154. Radiographic image signals, which are generated by the multiplexer 144 based on electric charges from the sample and hold circuits 150, are converted by the A/D converter 154 into digital image signals representing radiographic image information, which is supplied to the cassette controller 92.

The TFTs 140, which function as switching devices, may be combined with another image capturing device, such as a CMOS (Complementary Metal-Oxide Semiconductor) image sensor or the like. Alternatively, the TFTs 140 may be replaced with a CCD (Charge-Coupled Device) image sensor for shifting and transferring electric charges with shift pulses that correspond to gate signals in the TFTs.

FIG. 11 shows in block form the first radiographic image capturing apparatus 10A. Components of the first radiographic image capturing apparatus 10A, which have not been described above with reference to FIGS. 1 through 10, will mainly be described below with reference to FIG. 11.

The cassette controller 92 comprises an address signal generator 162, an image memory 164, and an SID determining unit (imaging distance determining unit) 168.

The address signal generator 162 supplies address signals to the address decoder 146 of the line scanning driver 142, as well as to the address decoder 152 of the multiplexer 144. The image memory 164 stores the radiographic image information detected by the radiation detector 86.

The SID determining unit 168 calculates the imaging distance between the focus point 122 and the position 124, at a time when the radiation source device 18 is tentatively placed over the irradiated surface 20 according to the present reeled-out length 11 of the ribbon 76, based on the reeled-out length 11 of the ribbon 76, which is input from the rotary encoder 78, and the stored distance 12.

If the calculated imaging distance agrees with the SID, the SID determining unit 168 controls the display unit 36 through the transceivers 94, 98, so as to display information representing the present reeled-out length of the ribbon 76 as the reeled-out length 11 that depends on the SID, and also to display information representing that the imaging distance agrees with the SID. The cassette 12 may include a mechanism for preventing (locking) the ribbon 76 from being reeled out further, when the reeled-out length 11 and the imaging distance have been determined to agree with the SID. If the calculated imaging distance does not agree with the SID, then the SID determining unit 168 controls the display unit 36 through the transceivers 94, 98 in order to display information representing the difference between the present reeled-out length and the reeled-out length 11, and also to display information representing that the imaging distance does not agree with the SID.

The SID determining unit 168, the rotary encoder 78, and the tape measure 72 jointly make up an imaging distance setting means 169.

15

The cassette controller **92** transmits cassette ID information of the cassette **12** and radiographic image information, which are stored in the image memory **164**, via the transceiver **94** to the mobile terminal **42** by way of wireless communications.

A preparatory procedure using the cassette **12** and the radiation source device **18**, as well as operations of the first radiographic image capturing apparatus **10A** to capture radiographic images, shall be described below.

First, the operator **38** performs an operation to ready the first radiographic image capturing apparatus **10A** for capturing radiographic images at a site where the first radiographic image capturing apparatus **10A** has been carried. The operator **38** operates the operating unit **40** of the mobile terminal **42** in order to register image capturing conditions including subject information (e.g., SID) of the subject **50** to be imaged.

At this time, the operator **38** operates the operating unit **40** while the mobile terminal **42** either is detached from or placed within the recess **54**. If the body region to be imaged and an image capturing method are known, then the operator **38** also operates the operating unit **40** in order to register the body region and the image capturing method as image capturing conditions. If details of the subject **50** are already known before the operator **38** carries the first radiographic image capturing apparatus **10A** to the imaging site, then the operator **38** may register the subject information including such details using the mobile terminal **42**, which is located at the medical organization, e.g., the hospital, where the subject **50** is being treated.

The registered image capturing conditions, including subject information of the subject **50**, are sent from the transceiver **98** of the mobile terminal **42** to the transceiver **94** of the cassette **12** by way of wireless communications, whereupon the image capturing conditions are registered in the cassette controller **92**.

When the operator **38** presses the unlocking button **34**, the hook **64** is displaced toward the side wall **52d** against the resiliency of the spring **60** until the hook **64** is brought out of engagement with the edge of the through hole **66**.

When the operator **38** detaches the radiation source device **18** from the cassette **12** while the hook **64** does not engage with the edge of the through hole **66**, i.e., while the operator **38** presses the unlocking button **34**, then the connection terminal **68a** becomes disengaged from the connection terminal **70a**, and the connection terminal **68b** becomes disengaged from the connection terminal **70b**, thereby releasing the radiation source device **18** and the cassette **12** from each other.

The operator **38** sets the imaging distance and then brings the mark **130**, which is displayed on the irradiated surface **20**, into alignment with the central position **126** of the guide lines **22**. Thereafter, the operator **38** places and positions the subject **50** between the irradiated surface **20** and the radiation source device **18**.

The operator **38** moves the radiation source device **18**, whereby the ribbon **76** is reeled out from the tape measure **72** until the actual reeled-out length of the ribbon **76** reaches the reeled-out length **11** that depends on the SID.

The ribbon **76** is reeled out from the tape measure **72** until the actual reeled-out length of the ribbon **76** reaches the reeled-out length **11**, in accordance with either of the two processes described below.

According to the first process, the SID determining unit **168** automatically determines whether or not the actual reeled-out length of the ribbon **76** has reached the reeled-out length **11**. Therefore, the operator **38** is able to reel out the

16

ribbon **76** from the tape measure **72** until the actual reeled-out length of the ribbon **76** reaches the reeled-out length **11** that depends on the SID.

In the first process, the rotary encoder **78** detects the actual reeled-out length of the ribbon **76**, and based on the detected reeled-out length, the SID determining unit **168** calculates the imaging distance between the focus point **122** and the position **124** when the radiation source device **18** is tentatively placed over the irradiated surface **20** in accordance with the present reeled-out length of the ribbon **76**.

If the imaging distance agrees with the SID, then the SID determining unit **168** controls the display unit **36** via the transceivers **94, 98** to display information representing the reeled-out length of the ribbon **76**, and also to display information representing that the imaging distance agrees with the SID. If the imaging distance does not agree with the SID, then the SID determining unit **168** controls the display unit **36** via the transceivers **94, 98** to display information representing the difference between the present reeled-out length and the reeled-out length **11**, and also to display information representing that the imaging distance does not agree with the SID.

The first process allows the operator **38** to set the imaging distance easily, because the operator **38** may reel out the ribbon **76** from the tape measure **72** according to the information displayed on the display unit **36**.

According to the second process, the reeled-out length **11** already is known, and the operator **38** reels out the ribbon **76** from the tape measure **72**, while observing the graduations **74**, until the present reeled-out length reaches the reeled-out length **11**.

After the ribbon **76** has been reeled out from the tape measure **72** until the present reeled-out length reaches the reeled-out length **11** that depends on the SID, the operator **38** moves the radiation source device **18** so as to confront (i.e., be placed in a facing relationship with) the irradiated surface **20**.

At this time, the radiation source controller **102** controls the laser pointer **104** to apply a laser beam **128** to the irradiated surface **20**. The crisscross mark **130**, which represents the center of a range within which the irradiated surface **20** is irradiated with radiation **46**, is displayed on the irradiated surface **20**. The operator **38** positionally adjusts the radiation source device **18** until the mark **130** and the central position **126** are aligned with each other.

After having adjusted the position of the radiation source device **18** until the mark **130** and the central position **126** are aligned with each other, the operator **38** places or positions the subject **50** on the irradiated surface **20**, so that the center of a body region of the subject **50** to be imaged is aligned with the central position **126**, i.e., is aligned with the position of the mark **130**.

After the above positional adjustment has been made, the radiation source device **18** is secured at the adjusted position by a holder, not shown, for example.

At a site such as a disaster site, due to limited space availability, the first radiographic image capturing apparatus **10A** may not be able to capture radiographic images with the desired SID. Therefore, the cassette controller **92** may recalculate image capturing conditions based on a new SID, which is different from the desired SID, and store the recalculated image capturing conditions together with the new SID in association with image data, or transmit the new SID and/or the recalculated image capturing conditions via a network to a data center such as a medical organization for confirmation.

After the subject **50** has been positioned, the operator **38** turns on the exposure switch **48** to begin capturing radiographic images of the subject **50**.

When the exposure switch **48** is turned on, the radiation source controller **102** sends a request for image capturing conditions to the cassette controller **92** by way of wireless communications. Based on such a request, the cassette controller **92** sends the image capturing conditions (control signals) with respect to the body region of the subject **50** to be imaged to the radiation source device **18**. When the radiation source controller **102** receives the image capturing conditions, the radiation source controller **102** controls the laser pointer **104** in order to stop emitting the laser beam **128**, and controls the radiation source **44** to apply radiation **46** at a predetermined dose to the subject **50**.

In the radiation source **44**, the rotating mechanism **106** is controlled by the radiation source controller **102** in order to rotate the rotational shaft **108** and the rotary anode **110**. The power supply **118** applies a negative voltage to the field-electron-emission-type electron source **116**, and the power supply **120** applies a voltage between the rotary anode **110** and the cathode **114**, based on electric power supplied from the battery unit **304**. The field-electron-emission-type electron source **116** emits electrons, which are accelerated by the voltage applied between the rotary anode **110** and the cathode **114**, and the electrons bombard the target layer **112**. The surface of the target layer **112**, which is bombarded with electrons, emits radiation **46** from the focus point **122**, the intensity of which depends on the applied electrons.

While the subject **50** is irradiated with radiation **46** for a given irradiation time based on the image capturing conditions, the radiation **46** passes through the subject **50** and reaches the radiation detector **86** of the cassette **12**.

Since the radiation detector **86** is of an indirect conversion type, the scintillator of the radiation detector **86** emits visible light having an intensity that depends on the intensity of the radiation **46**, and the pixels **132** of the photoelectric conversion layer **138** convert the visible light into electric charges and store the electric charges. The electric charges stored by the pixels **132**, which are representative of a radiographic image of the subject **50**, are read from the pixels **132** according to address signals, which are supplied from the address signal generator **162** of the cassette controller **92** to the line scanning driver **142** and the multiplexer **144**.

More specifically, in response to an address signal supplied from the address signal generator **162**, the address decoder **146** of the line scanning driver **142** outputs a selection signal in order to select one of the switches SW1, which supplies the control signal Von to the gates of the TFTs **140** that are connected to the gate line **134** corresponding to the selected switch SW1. In response to address signals supplied from the address signal generator **162**, the address decoder **152** of the multiplexer **144** outputs selection signals to successively turn on the switches SW2 so as to switch between the signal lines **136**, for thereby reading through the signal lines **136** the electric charges stored in the pixels **132** that are connected to the selected gate line **134**.

The electric charges, which are read from the pixels **132** connected to the selected gate line **134**, are amplified respectively by the amplifiers **148**, sampled by the sample and hold circuits **150**, and supplied to the multiplexer **144**. Based on the supplied electric charges, the multiplexer **144** generates and supplies radiographic image signals to the A/D converter **154**, which converts the radiographic image signals into digital signals. Digital signals representative of the radiographic image information are stored in the image memory **164** of the cassette controller **92**.

Similarly, the address decoder **146** of the line scanning driver **142** successively turns on the switches SW1 so as to switch between the gate lines **134** according to the address

signals supplied from the address signal generator **162**. Electric charges stored in the pixels **132** connected to the successively selected gate lines **134** are read through the signal lines **136**, processed by the multiplexer **144**, and converted into digital signals by the A/D converter **154**. The digital signals are stored in the image memory **164** of the cassette controller **92**.

Radiographic image information represented by the digital signals stored in the image memory **164** is transmitted through the transceiver **94** to the mobile terminal **42** by way of wireless communications. Radiographic image information transmitted to the mobile terminal **42** is received by the transceiver **98**, and is transmitted from the transceiver **98** to the display unit **36**, which displays a radiographic image based on the radiation image information, as shown in FIG. **12**. The operator **38** can determine whether or not the body region of the subject **50** to be imaged has been appropriately imaged by confirming the radiographic image displayed on the display unit **36**.

For example, if the radiographic image displayed on the display unit **36** does not include the body region of the subject **50** to be imaged, then the operator **38** judges that the subject **50** has not been appropriately imaged, and captures another radiographic image of the subject **50**. At this time, using the mobile terminal **42**, the operator **38** updates the number of captured images in the image capturing conditions, by incrementing the number with the number of recaptured images.

The radiographic image displayed on the display unit **36** may be of a quality that is sufficient enough to determine whether or not the subject **50** has been appropriately imaged. The displayed radiographic image may either be a radiographic image represented by the radiographic image information stored in the image memory **164**, an image of low data, or a relatively low resolution processed image.

As shown in FIG. **14**, the battery controller **306** comprises a memory **330**, an electric power supply activator **336** for activating an electric power controller **334** based on supply timing conditions, the electric power controller **334** for allowing electric power to be supplied between the batteries **308** (see FIG. **13**) in the devices, which are connected in a wired fashion, or between the devices that have entered into an area where they can be fed wirelessly, i.e., devices that are connected in a wireless fashion, an electric power supply limiter **338** for limiting operation of the electric power controller **334** only during periods in which radiographic images are being captured, and a pause processor **340** for temporarily shutting down the electric power controller **334** at a time when capturing of necessary radiographic images is completed, or when supply of electric power is terminated. The memory **330** stores ID information for identifying the devices incorporating the battery controller **306**, i.e., the cassette **12**, the radiation source device **18**, etc., and also stores various conditions. The memory **330** also temporarily stores various table information, which may be entered via a network, the mobile terminal **42**, etc.

Based on the turning on of the power, the electric power supply activator **336** is activated. If the supply timing conditions stored in the memory **330** are free of timing controls, then the electric power supply activator **336** of a device whose electric power supply switch has been operated activates the corresponding electric power controller **334** based on operation of the electric power supply switch. The electric power supply activator **336** may activate the electric power controller **334** without waiting for the electric power supply switch to be operated. In such a case, if an interlock process is not performed, then the electric power controllers **334** of all the devices whose power is turned on are activated, thus tending

to cause processing operations to interfere with each other. Therefore, the electric power supply activator **336** of each of the devices refers to interlock information registered in the memory **330**, i.e., the ID of the radiation source device **18** or the cassette **12** to be used in a preset image capturing process, and only the electric power supply activator **336** of a device whose ID is identical to the ID of the interlock information activates the corresponding electric power controller **334**. Thus, for example, only the electric power controller **334** of the radiation source device **18** that is used in the preset image capturing process is operated, while interference from the other devices is prevented.

If the supply timing conditions indicate supply of electric power before capturing of radiographic images, then the electric power controller **334** is activated based on the image capturing conditions (order) that are input from the mobile terminal **42**. In this case, only the electric power supply activator **336** of a device having an ID identical to that of the ID of the radiation source device **18** or the cassette **12** to be used to capture radiographic images, which is registered in advance in the image capturing conditions, activates the corresponding electric power controller **334**. If the supply timing conditions indicate supply of electric power after capturing of radiographic images, then the electric power controller **334** is activated based on an image capture completion signal supplied from an image capture completion determiner **386** (see FIG. **15**). In this case as well, only the electric power supply activator **336** of a device having an ID identical to that of the ID of the radiation source device **18** or the cassette **12** to be used to capture radiographic images, which is registered in advance in the image capturing conditions, activates the corresponding electric power controller **334**.

The electric power controller **334** is available in different configurations according to two specific examples, i.e., a first specific example and a second specific example. According to the first specific example, the battery **308** of the radiation source device **18** supplies electric power to the battery **308** of the cassette **12**, or the battery **308** of the radiation source device **18** controls supply of electric power to the battery **308** of the cassette **12**. As shown in FIG. **15**, the electric power controller **334** according to the first specific example comprises, as functional components thereof, a device connection detector **360**, a cassette selector activator **362**, a cassette selector **364**, an integrated supply activator **366**, an integrated supply **368**, an electric power supply route setting unit **370**, an amount-of-supplied-electric-power setting unit **372**, an electric power supply controller **374**, a remaining level detector **376**, an image capture interruption instructing unit **378**, a counter **380**, a re-supply instructing unit **382**, an image capture permission instructing unit **384**, an image capture completion determiner **386**, and an electric power supply completion output unit **388**.

According to the second specific example, the electric power controller **334** controls supply of electric power such that the remaining levels of electric power stored in the batteries **308** of the connected devices are utilized flexibly between the connected devices, based on preset battery charging conditions and image capturing conditions. As shown in FIG. **16**, the electric power controller **334** according to the second specific example comprises, in addition to the functional components, an electric power manager **390** and functional components ancillary to the electric power manager **390**, which include a remaining level prediction updater **392**, a usage history updater **394**, a remaining level information transfer unit **396**, and a usage history transfer unit **398**.

Flexible utilization of the remaining levels of electric power stored in the batteries **308** between the connected devices implies at least the following aspects:

(1) One or more devices, the batteries of which store an excessive remaining level of electric power, supply electric power to a device whose battery stores a remaining level of electric power that is not sufficient to capture radiographic images.

(2) One or more devices, which are not used to capture radiographic images, supply electric power required to capture radiographic images to the aforesaid device, which is used to capture radiographic images.

(3) One or more devices, which are not used to capture radiographic images, supply electric power required to capture radiographic images to the aforesaid device, which is used to capture radiographic images, while increasing the remaining level of electric power in the battery of the aforesaid device, i.e., the amount of electric power held by the aforesaid device, up to at least a level required to capture radiographic images.

As shown in FIG. **14**, the electric power controller **334** limits supply of electric power during a period in which the electric power controller **334** is supplied with a supply limit signal, which is input thereto from the electric power supply limiter **338**. Limiting supply of electric power refers to stopping supply of electric power, reducing the amount of electric power supplied per unit time, or controlling supply of electric power in a stepwise manner. To stop supply of electric power, as shown in FIG. **13**, the electric power controller **334** may output a stop signal to the electric power supply controller **374**, thereby causing the electric power supply controller **374** to control the first through fifth switchers **314a** through **314e** in order to change to neutral positions thereof, which are neither input positions nor output positions, for example. In order to reduce the amount of electric power supplied per unit time, the electric power controller **334** may output a supplied-amount reduction signal to the electric power supply controller **374**, thereby causing the electric power supply controller **374** to reduce the amount of electric power supplied per unit time to a preset level. In order to control the supply of electric power in a stepwise manner, as described later, the electric power controller **334** may stop supplying electric power while electric charges are being stored in the pixels in the cassette **12** and are converted from analog signals into digital signals, supply a small amount of electric power while image data are being transferred, and supply a large amount of electric power during an idling period after transferring of the image data is completed. The electric power controller **334** stops controlling supply of electric power based on a pause signal, which is input from the pause processor **340**, and waits to be activated at a subsequent time by the electric power supply activator **336**.

According to the first specific example, for example, as shown in FIG. **13**, the device connection detector **360** detects whether the device, i.e., the radiation source device **18** or the cassette **12**, is connected to at least one of the first energy input/output unit **300** and the second energy input/output unit **302** in a wired or wireless fashion. A wireless connection is detected by an obstacle sensor such as an ultrasonic sensor or the like, which determines whether the device, i.e., the radiation source device **18** or the cassette **12**, has entered into an area in which the device can be fed wirelessly from the first energy input/output unit **300** or the second energy input/output unit **302**.

As shown in FIG. **17**, the cassette selector activator **362** activates the cassette selector **364** when a condition concerning a route, from among battery charging conditions stored in

the memory 330, represents only supply of electric power from one cassette 12 to the radiation source device 18, the aforesaid device is the radiation source device 18, and connection of a plurality of cassettes 12 to the radiation source device 18 is detected.

The cassette selector 364 comprises a cassette ID acquirer 400, a cassette information acquirer 402, and a selector 404.

The cassette ID acquirer 400 sends a transfer request for requesting that the cassettes 12, which are connected to the radiation source device 18, transfer IDs thereof. The cassettes 12 output IDs to the radiation source device 18 based on the transfer request. The cassette ID acquirer 400 acquires the IDs and stores the IDs in the memory 330.

The cassette information acquirer 402 acquires cassette information tables, which contain information concerning defective pixels, etc., and usage history tables corresponding to the acquired IDs via the network.

The selector 404 selects a cassette 12 that matches selecting conditions from among the connected cassettes 12 based on the selecting conditions, the acquired cassette information tables, and the acquired usage history tables, which are stored in the memory 330. The selector 404 then outputs the ID of the selected cassette 12 to the electric power supply route setting unit 370.

The selecting conditions for selecting a cassette 12 include: (1-a) a large-size cassette 12;

This condition serves the purpose of discharging electric power from a large-size cassette 12 in a special environment where no large-size cassette 12 is used. The size of a cassette 12 is determined based on size information that is recorded in the cassette information table.

(1-b) a small-size cassette 12;

This condition serves the purpose of preferentially discharging electric power from a cassette 12 that is less versatile.

(1-c) a cassette 12 with many defective pixels;

This condition serves the purpose of preferentially discharging electric power from a cassette 12 that is less frequently used, thereby preventing the cassette 12 from becoming disabled substantially simultaneously. The number of defective pixels is determined based on information concerning defective pixels recorded in the cassette information table. The information concerning defective pixels, which is recorded in the cassette information table, is regularly or irregularly updated upon calibration or the like, for example.

(1-d) a cassette 12 with a small imaging area;

The size of an imaging area is calculated from information concerning defective pixels, which is recorded in the cassette information table, particularly positional information about the defective pixels.

(1-e) a cassette 12 with a highly deteriorated battery 308;

The level of deterioration of the battery 308 is determined based on the number of times that the cassette 12 has been used, which is recorded in the cassette information table.

(1-f) a cassette 12 with a lowly deteriorated battery 308;

(1-g) a cassette 12 that has been used many times;

The number of times that the cassette 12 has been used is determined based on a counted number of times that the cassette 12 has been used, which is recorded in the cassette information table, or based on information concerning an accumulated radiation dose, which is recorded in the cassette information table.

(1-h) a cassette 12 with a small remaining built-in memory capacity;

The remaining built-in memory capacity is determined based on a reply, which is sent from the cassette controller 92

in response to an inquiry as to the remaining built-in memory capacity sent to the cassette controller 92.

(1-i) a cassette 12 that is positioned a small distance from the radiation source device 18;

This condition serves the purpose of selecting a cassette 12 that can easily supply electric power over a small distance, thereby reducing the burden on the circuits involved. The distance from the radiation source device 18 to the cassette 12 is determined based on the information concerning present positions of the cassettes 12 acquired via GPS, or distance information from a range sensor such as an ultrasonic sensor, a three-dimensional magnetic sensor, or the like.

As shown in FIG. 18, the integrated supply activator 366 activates the integrated supply 368 when a condition concerning a route, from among the battery charging conditions stored in the memory 330, represents only supply of electric power from a plurality of cassettes 12 to the radiation source device 18, the aforesaid device is the radiation source device 18, and connection of a plurality of cassettes 12 to the radiation source device 18 is detected.

The integrated supply 368 comprises a cassette ID acquirer 400, a cassette information acquirer 402, and a weighting setting unit 406.

The cassette ID acquirer 400 sends a transfer request for requesting that cassettes 12 connected to the radiation source device 18 transfer IDs thereof. The cassettes 12 output IDs to the radiation source device 18 based on the transfer request. The cassette ID acquirer 400 acquires the IDs and stores the IDs in the memory 330.

The cassette information acquirer 402 acquires cassette information tables, which contain information concerning defective pixels, etc., and usage history tables corresponding to the acquired IDs via the network.

The weighting setting unit 406 sets weighting coefficients for respective amounts of electric power to be supplied from the cassettes 12 to the radiation source device 18, based on integrating conditions, the acquired cassette information tables, and the acquired usage history tables, which are stored in the memory 330. The weighting setting unit 406 then outputs the set weighting coefficients, together with corresponding ID information, to the amount-of-supplied-electric-power setting unit 372.

The integrating conditions include:

(2-a) The amount of supplied electric power is sorted depending on the amount of defective pixels;

As the number of defective pixels becomes greater, the weighting setting unit 406 sets a weighting coefficient for increasing the amount of supplied electric power. Conversely, as the number of defective pixels becomes smaller, the weighting setting unit 406 sets a weighting coefficient for reducing the amount of supplied electric power.

(2-b) The amount of supplied electric power is sorted depending on the imaging area;

As the imaging area becomes smaller, the weighting setting unit 406 sets a weighting coefficient for increasing the amount of supplied electric power. Conversely, as the imaging area becomes greater, the weighting setting unit 406 sets a weighting coefficient for reducing the amount of supplied electric power.

(2-c) The amount of supplied electric power is sorted depending on the level of deterioration of the battery 308;

As the level of deterioration of the battery 308 becomes greater, the weighting setting unit 406 sets a weighting coefficient for increasing the amount of supplied electric power. Conversely, as the level of deterioration of the battery 308

becomes smaller, the weighting setting unit **406** sets a weighting coefficient for reducing the amount of supplied electric power.

(2-d) The amount of supplied electric power is sorted depending on the number of times that the cassette **12** has been used;

As the number of times that the cassette **12** has been used becomes greater, the weighting setting unit **406** sets a weighting coefficient for increasing the amount of supplied electric power. Conversely, as the number of times that the cassette **12** has been used is smaller, the weighting setting unit **406** sets a weighting coefficient for reducing the amount of supplied electric power.

(2-e) The amount of supplied electric power is sorted depending on the remaining built-in memory capacity;

As the amount of supplied electric power becomes smaller, the weighting setting unit **406** sets a weighting coefficient for increasing the amount of supplied electric power. Conversely, as the amount of supplied electric power becomes greater, the weighting setting unit **406** sets a weighting coefficient for reducing the amount of supplied electric power.

(2-f) The amount of supplied electric power is sorted depending on the distance to the radiation source device **18**.

As the distance to the radiation source device **18** becomes smaller, the weighting setting unit **406** sets a weighting coefficient for increasing the amount of supplied electric power. Conversely, as the distance to the radiation source device **18** becomes greater, the weighting setting unit **406** sets a weighting coefficient for reducing the amount of supplied electric power.

Then, the electric power supply route setting unit **370** sets a route for supply of electric power based on a condition concerning the route from among the battery charging conditions stored in the memory **330**. For example, the electric power supply route setting unit **370** sets a route from the radiation source device **18** to the cassette **12**, or a route from the cassette **12** to the radiation source device **18**. If the electric power supply route setting unit **370** is supplied with an ID from the cassette selector **364**, then the electric power supply route setting unit **370** sets a route from the cassette **12** to the radiation source device **18** corresponding to the ID. If the electric power supply route setting unit **370** is supplied with a plurality of IDs from the integrated supply **368**, then the electric power supply route setting unit **370** sets routes from the cassettes **12** to the radiation source device **18** corresponding to such IDs. Route information representing the set IDs is displayed on a display screen of the mobile terminal **42**. The condition concerning the route is descriptive of at least one source of electric power. If the source of electric power is the radiation source device **18**, then the radiation source device **18** supplies electric power to the cassette **12**. If the source of electric power is the cassette **12**, then the cassette **12** supplies electric power to the radiation source device **18**. The condition concerning the route can be changed as desired by the mobile terminal **42**. If the re-supply instructing unit **382** provides a re-supply instruction, i.e., if the re-supply instructing unit **382** inputs a re-supply instruction signal to the electric power supply route setting unit **370**, then the electric power supply route setting unit **370** sets the route for supply of electric power based on battery charging conditions. If the operator **38** intends to additionally charge the battery of another device, e.g., the radiation source device **18** or the cassette **12**, then the operator **38** enters the route for supply of electric power to the other device, i.e., a route from the other device to the radiation source device **18** or the cassette **12** that is used to capture radiographic images, or a route from the radiation source device **18** or the cassette **12** that is used to

capture radiographic images to the other device, and also enters an amount of electric power to be supplied. Based on the entered route for supply of electric power, the electric power supply route setting unit **370** outputs a supply source instruction signal or a supply destination instruction signal to the electric power supply controller **374** of each device.

The amount-of-supplied-electric-power setting unit **372** sets an amount of electric power to be supplied based on a condition concerning the amount of electric power to be supplied, from among the battery charging conditions. At least items such as a full battery charge, an amount of electric power to be supplied that is required to capture a single radiographic image, etc., can be used as conditions concerning the amount of electric power to be supplied. One of such items, which is selected at present, is applicable as the condition concerning the amount of electric power to be supplied. An item to be applied can be selected as desired by the mobile terminal **42**. An amount of electric power to be supplied can be set as a numerical value by the mobile terminal **42**. If the amount-of-supplied-electric-power setting unit **372** is supplied with a plurality of IDs and corresponding coefficients from the integrated supply **368**, then the amount-of-supplied-electric-power setting unit **372** multiplies the amount of electric power to be supplied by such coefficients in order to set amounts of electric power to be supplied respectively from the cassettes **12** to the radiation source device **18**. If the re-supply instructing unit **382** provides a re-supply instruction, then the amount-of-supplied-electric-power setting unit **372** sets an amount of electric power to be supplied based on a condition concerning the amount of electric power to be supplied, from among the battery charging conditions. The amount of electric power to be supplied can also be changed as desired by the mobile terminal **42**. If batteries of devices are to be charged as well, then the amount-of-supplied-electric-power setting unit **372** also sets respective amounts of electric power to be supplied in order to charge the batteries, and supplies the set amounts of electric power to be supplied to the electric power supply controllers **374** of each of the respective devices.

As shown in FIG. **13**, if a supply source instruction signal is input to the electric power supply controller **374**, then the electric power supply controller **374** controls the battery **308** in order to output electric power. If a supply destination instruction signal is input to the electric power supply controller **374**, then the electric power supply controller **374** controls the battery **308** in order to receive electric power. Based on a remaining level of electric power in the battery **308**, which is detected by the remaining level detector **376**, the electric power supply controller **374** controls the battery **308** that is supplied with electric power at a constant charging rate, or controls the battery **308** to supply electric power at the constant discharging rate. Assuming that the amount of electric power to be supplied is small, then the electric power supply controller **374** can quickly charge or discharge the battery **308**. If the remaining level of electric power in the battery **308**, which is detected by the remaining level detector **376**, is insufficient to capture a single radiographic image, then the electric power supply controller **374** outputs an imaging disable signal, which includes the remaining level of electric power and the ID of the aforesaid device. When the supply of electric power to the battery **308** or the supply of electric power from the battery **308** is completed, the electric power supply controller **374** outputs a supply termination signal.

As described above, the remaining level detector **376** detects a remaining level of electric power in the battery **308**,

and sends a signal representative of the detected remaining level of electric power in the battery **308** to the electric power supply controller **374**.

The image capture interruption instructing unit **378**, as shown in FIG. **15**, outputs a message representing interruption of an image capturing process to the mobile terminal **42**, based on an imaging disabled signal input from the electric power supply controller **374**.

The counter **380** counts the number of times that the exposure switch **48** has been turned on. The counter **380** resets the count (count=0) based on an image capture completion signal, which is input from the image capture completion determiner **386**.

Based on the imaging disabled signal input from the electric power supply controller **374**, the re-supply instructing unit **382** outputs a re-supply instruction signal including the preset count of the counter **380**, the amount of electric power included in the imaging disabled signal, and the ID of the aforesaid device, respectively, to the electric power supply route setting unit **370**, the amount-of-supplied-electric-power setting unit **372**, and the electric power manager **390**. If electric power is supplied after capturing of radiographic images, since the electric power controller **334** itself is not activated, the re-supply instructing unit **382** of the radiation source device **18** or the cassette **12** that is used to capture radiographic images activates the electric power supply route setting unit **370**, the amount-of-supplied-electric-power setting unit **372**, and the electric power manager **390**, using an interrupt routine for emergency.

If the supply timing conditions recorded in the memory **330** are free of timing controls, or indicate supply electric power before capturing of radiographic images, then the image capture permission instructing unit **384** outputs an image capture permission message to the mobile terminal **42** based on supply termination signals, which are input from the electric power supply controllers **374** of all of the devices to which electric power is supplied.

The image capture completion determiner **386** compares the number of times that radiographic images have been captured in the image capturing conditions with the count of the counter **380**, and outputs an image capture completion signal when the number of times that radiographic images have been captured becomes equal to the count.

The electric power supply completion output unit **388** outputs an electric power supply completion signal based on supply termination signals, which are input from the electric power supply controllers **374** of all of the devices to which electric power is supplied.

The electric power supply limiter **338** shown in FIG. **14** determines whether or not a radiographic image of the subject **50** is being captured if the supply timing conditions recorded in the memory **330** include a condition indicating that "the supply of electric power is stopped while a radiographic image is being captured." If a radiographic image is being captured, then the electric power supply limiter **338** outputs a supply limit signal during the period in which a radiographic image is being captured. More specifically, when the exposure switch **48** is turned on, the electric power supply limiter **338** outputs a supply limit signal. Thereafter, when a predetermined period of time has elapsed, the electric power supply limiter **338** stops outputting the supply limit signal. The electric power controller **334** limits supply of electric power during the period in which the supply limit signal is input thereto.

The period during which the electric power supply limiter **338** outputs the supply limit signal should preferably be any one of a period (storage period) in which radiation **46** having passed through the subject **50** is applied to the radiation

detector **86** and converted by a scintillator (not shown) into visible light, and the visible light is converted at each pixel **132** into electric signals that are stored as electric charges (signal charges), a period (reading period) during which the stored electric charges are read, and a period (analog-to-digital conversion period) during which the read electric charges (analog signals) are converted into digital signals by the A/D converter **154**, a period which is a combination of the above periods, or a period that includes all the above periods. In the above three periods, the image signals (radiographic image information) are highly susceptible to noise. More specifically, in the storage period and the reading period, since the level of electric charge is very low, the radiographic image information is highly susceptible to noise. In the analog-to-digital conversion period, analog signals are less resistant to noise than digital signals, and any noise added to the analog signals tends to be converted into digital signals and appear in the image data.

The storage period includes a period during which the radiation source **44** emits radiation **46**. More specifically, after the storage period has started, the radiation source **44** begins to emit radiation **46** as quickly as possible, and after the radiation source **44** has stopped emitting radiation **46**, the stored electric charges are read immediately from the pixels. Any time lag associated with these processes should be reduced as much as possible in order to reduce dark current, and hence increase the quality of radiographic images that are generated. The reading period refers to a period during which the TFTs **140** are turned on, and signals are supplied through the amplifiers **148** to the A/D converter **154**. The reading period and the analog-to-digital conversion period occur substantially at the same time, although the reading time starts slightly earlier than the analog-to-digital conversion period.

The period during which the supply limit signal is output should extend from a time when the supply limit signal is output to a time when the radiation source device **18** stops emitting radiation **46**, or more preferably reside within the period during which the radiographic image is captured, so that the cassette **12** can detect radiation **46** with high quality. A predicted time, which is required to capture and display a radiographic image, may be preset and used as the period during which the supply limit signal is output. The degree to which the amount of supplied electric power is reduced per unit time may be set experimentally to a value for preventing noise from being added to the radiographic image, or for reducing any added noise to a level that is not detrimental to the quality of the radiographic image.

If the supply timing conditions recorded in the memory **330** are free of timing controls, or indicate supply of electric power before capturing of radiographic images, then the pause processor **340** shown in FIG. **14** outputs a pause signal to the electric power controller **334**, based on an image capture completion signal input from an image capture completion determiner **386**. If the supply timing conditions recorded in the memory **330** indicate supply of electric power after capturing of radiographic images, then the pause processor **340** outputs a pause signal to the electric power controller **334**, based on an electric power supply completion signal input from the electric power supply completion output unit **388**.

According to the second specific example, the electric power manager **390** shown in FIG. **16** gives the electric power supply controller **374** information for controlling supply of electric power, such that the remaining levels of electric power stored in the batteries **308** of the devices are utilized flexibly between the devices, based on preset battery charging conditions and image capturing conditions. The electric

power manager 390 is incorporated in the radiation source device 18 and/or the cassette 12. As shown in FIG. 19, the electric power manager 390 comprises an ID acquirer 410, an information acquirer 412 for acquiring various information, an amount-of-consumed-electric-power predictor 414, and an information updater 416.

The ID acquirer 410 sends a transfer request for requesting the device that incorporates the electric power manager 390 therein and another device that is connected to the device to transfer respective IDs thereof. Based on the transfer request, the devices output their IDs respectively to the electric power manager 390. The ID acquirer 410 acquires the IDs input thereto and registers the acquired IDs in the memory 330. If another radiation source device 18 or another cassette 12, in addition to the radiation source device 18 and the cassette 12 used to capture radiographic images, are connected or are present in an area in which they can be fed wirelessly, then the ID acquirer 410 also acquires IDs of the other radiation source device 18 and the cassette 12.

The information acquirer 412 for acquiring various information acquires present or previous image capturing conditions, which are input via the mobile terminal 42 or the network, remaining level-of-electric-energy information tables corresponding to the IDs, previous image capturing conditions corresponding to the IDs, and usage history tables corresponding to the IDs, and stores such information in the memory 330.

The amount-of-consumed-electric-power predictor 414 calculates amounts of electric power that are consumed by the radiation source device 18 and the cassette 12 used to capture radiographic images, from the battery charging conditions stored in the memory 330 and the present or previous image capturing conditions representative of the number of radiographic images to be captured, mAs values, etc. The amount-of-consumed-electric-power predictor 414 then corrects the calculated amounts of electric power by multiplying the calculated amounts by usage histories of the radiation source device 18 and the cassette 12, i.e., coefficients corresponding to the number of times that the radiation source device 18 and the cassette 12 have been used, thereby predicting amounts of electric power that will be consumed by the radiation source device 18 and the cassette 12 during the present image capturing process, or amounts of electric power consumed by the radiation source device 18 and the cassette 12 in the previous image capturing process. If a re-supply instruction is input from the re-supply instructing unit 382, then the amount-of-consumed-electric-power predictor 414 calculates amounts of electric power to be consumed by the respective devices indicated by the IDs, i.e., the radiation source device 18 and the cassette 12 to be re-supplied with electric power, from image capturing conditions for the image capturing process to be carried out, from which image capturing conditions for radiographic images already captured (indicated by the count) are excluded, which are among the present image capturing conditions representative of the number of radiographic images to be captured, mAs values, etc., and corrects the calculated amounts of electric power by multiplying the calculated amounts by usage histories of the radiation source device 18 and the cassette 12, i.e., coefficients corresponding to the number of times that the radiation source device 18 and the cassette 12 have been used, thereby predicting amounts of electric power that will be consumed by the devices of the IDs in the image capturing process to be carried out.

The information updater 416 subtracts the amount of supplied electric power from the remaining level of electric power of a device serving as an electric power supply source, and adds the amount of supplied electric power to the remain-

ing level of electric power of a device that serves as an electric power supply destination, in the remaining level-of-electric-energy information table. If the re-supply instructing unit 382 outputs a re-supply instruction, then the information updater 416 changes only the remaining levels of electric power of the respective devices indicated by the IDs. A value produced by adding the present amount of supplied electric power to the amount of electric power included in the re-supply instruction signal is recorded in the memory 330. Since this value reflects the amount of electric power from the electric power supply controller 374, an error in the remaining level of electric power, which is represented by only a predicted value, is corrected.

According to the second specific example, because the electric power controller 334 includes the electric power manager 390, the electric power supply route setting unit 370 and the amount-of-supplied-electric-power setting unit 372 operate differently from those of the electric power controller 334 according to the first specific example.

More specifically, the electric power supply route setting unit 370 according to the second specific example sets a route for supply of electric power based on the predicted amount of electric power, and the remaining levels of electric power in the batteries 308 of the radiation source device 18 and the cassette 12 (remaining level-of-electric-energy information tables). Typically, the electric power supply route setting unit 370 sets a route for supplying electric power to a device, the battery of which stores a remaining level of electric power that will almost be eliminated in the present image capturing process. Information concerning the set route is displayed on the display screen of the mobile terminal 42. If the re-supply instructing unit 382 outputs a re-supply instruction, then the electric power supply route setting unit 370 sets routes for supplying electric power to respective devices indicated by the IDs. If the operator 38 intends to supply electric power additionally from other devices, i.e., a radiation source device 18 and a cassette 12 that are not used to capture radiographic images, then the operator 38 enters routes for supplying electric power, and amounts of electric power, from the other devices, i.e., routes for supplying electric power from the other devices to the respective devices indicated by the IDs. If the operator 38 additionally intends to charge a battery using another device, i.e., a radiation source device 18 or a cassette 12, then the operator 38 enters a route for supplying electric power to or from the other device, i.e., a route from the other device to the radiation source device 18 or the cassette 12 that is used to capture radiographic images, or a route from the radiation source device 18 or the cassette 12 that is used to capture radiographic images to the other device, together with the amount of electric power to be supplied, and an order in which such electric power is supplied. Based on the entered route for supplying electric power, the electric power supply route setting unit 370 outputs a supply source instruction signal or a supply destination instruction signal to the electric power supply controller 374 of each of the devices.

The amount-of-supplied-electric-power setting unit 372 according to the second specific example sets the supplied amount of electric power based on the predicted amount of electric power and the remaining levels of electric power in the batteries 308 of the radiation source device 18 and the cassette 12 (remaining level-of-electric-energy information tables). Thus, at most, the predicted amount of electric power is supplied to a device, the battery of which stores a remaining level of electric power, which will almost be eliminated during the present image capturing process. The amount of electric power, which is supplied to such a device, may be one-half or one-third the predicted amount of electric power. The

information concerning the set amount of electric power is displayed on a display screen of the mobile terminal **42**. The set amount of electric power can also be changed as desired by the mobile terminal **42**. If the operator **38** additionally intends to charge a battery, then the amount-of-supplied-electric-power setting unit **372** also sets the amount of electric power to be supplied, so as to additionally charge the battery. The amount of electric power predicted based on previous image capturing conditions is supplied in order to supplement the amount of electric power consumed in the previous image capturing process. If the re-supply instructing unit **382** outputs a re-supply instruction, then the amount-of-supplied-electric-power setting unit **372** sets the amount of electric power to equal the predicted amount of electric power. The set amount of electric power can be changed as desired by the mobile terminal **42**. If the operator **38** additionally intends to charge a battery, then the amount-of-supplied-electric-power setting unit **372** also sets an amount of electric power to be supplied, so as to additionally charge the battery. The set amount of electric power then is supplied to the electric power supply controller **374** of the corresponding device.

Among functional components that are ancillary to the electric power manager **390**, the remaining level prediction updater **392** shown in FIG. **16** functions, assuming that the supply timing conditions recorded in the memory **330** indicate supply of electric power before capturing of radiographic images. Each time that the operator **38** turns on the exposure switch **48**, the remaining level prediction updater **392** updates, by way of subtraction, the remaining levels of electric power stored in the batteries that are recorded in the remaining level-of-electric-energy information tables, i.e., the remaining levels of electric power stored in the batteries **308** of the radiation source device **18** and the cassette **12**, which are used to capture radiographic images. More specifically, with respect to the radiation source device **18** and the cassette **12**, the remaining level prediction updater **392** calculates amounts of electric power consumed in order to capture radiographic images based on the image capturing conditions and the usage history tables, and subtracts the calculated amounts of electric power from the remaining levels of electric power stored in the batteries **308** of the radiation source device **18** and the cassette **12**, which are recorded in the remaining level-of-electric-energy information tables.

The usage history updater **394** adds to the usage counts recorded in the usage history tables the number of times that the exposure switch **48** has been turned on, i.e., the number of times that the radiation source device **18** and the cassette **12** have been used.

If the supply timing conditions recorded in the memory **330** indicate supply of electric power before capturing of radiographic images, then the remaining level information transfer unit **396** shown in FIG. **16** transfers the remaining level-of-electric-energy information tables via the network to the database of a data center, such as a medical organization or the like for updating, based on an image capture completion signal input from the image capture completion determiner **386**. If the supply timing conditions recorded in the memory **330** indicate supply of electric power after capturing of radiographic images, then the remaining level information transfer unit **396** transfers the remaining level-of-electric-energy information tables via the network to the database of the data center for updating, based on an electric power supply completion signal input from the electric power supply completion output unit **388**.

If the supply timing conditions recorded in the memory **330** indicate supply of electric power before capturing of

radiographic images, then the usage history transfer unit **398** transfers the usage history tables via the network to the database of the data center for updating, based on an image capture completion signal input from the image capture completion determiner **386**. If the supply timing conditions recorded in the memory **330** indicate supply of electric power after capturing of radiographic images, then the usage history transfer unit **398** transfers the usage history tables via the network to the database of the data center for updating, based on an electric power supply completion signal input from the electric power supply completion output unit **388**.

The first radiographic image capturing apparatus **10A** basically is constructed as described above. Operations of the first radiographic image capturing apparatus **10A** will be described below with reference to the flowcharts shown in FIGS. **20** through **26**.

First, an operation sequence of the first radiographic image capturing apparatus **10A**, if the supply timing conditions are free of timing controls, will be described below with reference to the flowcharts shown in FIGS. **20** and **21**.

In step **S1** shown in FIG. **20**, the electric power controller **334** is activated by the electric power supply activator **336** based on operation of the electric power supply switch. The electric power supply activator **336** may also activate the electric power controller **334** without waiting for operation of the electric power supply switch. At this time, the electric power supply activator **336** of each of the devices refers to interlock information registered in the memory **330**, i.e., an ID of the radiation source device **18** or the cassette **12** that is used in a preset image capturing process, and only the electric power supply activator **336** of the device having an ID is identical to that of the interlock information activates the corresponding electric power controller **334**.

In step **S2**, the device connection detector **360** detects whether or not the device, i.e., the radiation source device **18** or the cassette **12**, is connected to the first energy input/output unit **300** or to the second energy input/output unit **302**.

After the device connection detector **360** has detected the connection in step **S2**, the cassette selector activator **362** determines whether or not conditions are satisfied for activating the cassette selector **364** in step **S3**. More specifically, the cassette selector activator **362** activates the cassette selector **364** when a condition concerning a route, from among the battery charging conditions stored in the memory **330**, represents only supply of electric power from one cassette **12** to the radiation source device **18**, the aforesaid device is the radiation source device **18**, and connection of a plurality of cassettes **12** to the radiation source device **18** is detected.

In step **S4**, the cassette selector **364** selects a cassette **12** that matches the selecting conditions from among the connected cassettes **12**, based on a plurality of IDs that are acquired by the cassette ID acquirer **400**, selecting conditions stored in the memory **330**, and the cassette information tables and the usage history tables, which are acquired by the cassette information acquirer **402**. The cassette selector **364** then outputs the ID of the selected cassette **12** to the electric power supply route setting unit **370**.

After step **S4**, or if the cassette selector activator **362** judges that conditions are not satisfied for activating the cassette selector **364** in step **S3**, control proceeds to step **S5**, during which the integrated supply activator **366** determines whether conditions are not satisfied in order to activate the integrated supply **368**. More specifically, the integrated supply activator **366** activates the integrated supply **368** when a condition concerning a route, from among the battery charging conditions stored in the memory **330**, represents only supply of electric power from a plurality of cassettes **12** to the radiation

31

source device **18**, the aforesaid device is the radiation source device **18**, and connection of a plurality of cassettes **12** to the radiation source device **18** is detected.

In step S6, the integrated supply **368** sets weighting coefficients for the amounts of electric power to be supplied from the cassettes **12** to the radiation source device **18** based on a plurality of IDs that are acquired by the cassette ID acquirer **400**, integrating conditions stored in the memory **330**, the cassette information tables, and the usage history tables, which are acquired by the cassette information acquirer **402**. The integrated supply **368** then outputs the set weighting coefficients to the corresponding amount-of-supplied-electric-power setting unit **372**.

After step S6, or if the integrated supply activator **366** judges that conditions are not satisfied for activating the integrated supply **368** in step S5, then control proceeds to step S7, during which the electric power supply route setting unit **370** sets a route for supply of electric power, based on conditions concerning the route from among the battery charging conditions stored in the memory **330**. For example, the electric power supply route setting unit **370** sets a route from the radiation source device **18** to the cassette **12**, or a route from the cassette **12** to the radiation source device **18**. If the electric power supply route setting unit **370** is supplied with an ID from the cassette selector **364**, then the electric power supply route setting unit **370** sets a route from the cassette **12** identified by the ID to the radiation source device **18**. If the electric power supply route setting unit **370** is supplied with a plurality of IDs from the integrated supply **368**, then the electric power supply route setting unit **370** sets multiple routes from the cassettes **12** identified by the IDs to the radiation source device **18**. Thereafter, the electric power supply route setting unit **370** outputs information concerning the set route (route information) to the electric power supply controller **374**. More specifically, based on the set route for supply of electric power, the electric power supply route setting unit **370** outputs a supply source instruction signal, or a supply destination instruction signal, to the electric power supply controller **374** of each device. For example, it is assumed that the first energy input/output unit **300** of the radiation source device **18** is connected to the first energy input/output unit **300** of the cassette **12**. If the set route is a route for supplying electric power from the radiation source device **18** to the cassette **12**, then the electric power supply route setting unit **370** outputs a supply source instruction signal to the electric power supply controller **374** of the radiation source device **18**, and further outputs a supply destination instruction signal to the electric power supply controller **374** of the cassette **12**. If the set route is a route for supplying electric power from the cassette **12** to the radiation source device **18**, then the electric power supply route setting unit **370** outputs a supply destination instruction signal to the electric power supply controller **374** of the radiation source device **18**, and further outputs a supply source instruction signal to the electric power supply controller **374** of the cassette **12**.

In step S8, the amount-of-supplied-electric-power setting unit **372** sets an amount of electric power to be supplied (supplied amount of electric power) based on a condition concerning the amount of electric power to be supplied, from among the battery charging conditions. For example, the amount-of-supplied-electric-power setting unit **372** sets an amount of electric power to be supplied for a full battery charge, or for capturing a single radiographic image. If the amount-of-supplied-electric-power setting unit **372** is supplied with a plurality of IDs and corresponding coefficients from the integrated supply **368**, then the amount-of-supplied-electric-power setting unit **372** multiplies the amount of elec-

32

tric power to be supplied by such coefficients in order to set respective amounts of electric power to be supplied to the radiation source device **18** from the respective cassettes **12**. The amount-of-supplied-electric-power setting unit **372** outputs information concerning the set amounts of electric power to be supplied to the electric power supply controllers **374** of the corresponding devices.

In step S9, if the electric power supply controller **374** is supplied with a supply source instruction signal, then the electric power supply controller **374** controls the battery **308** in order to output electric power. Further, if the electric power supply controller **374** is supplied with a supply destination instruction signal, then the electric power supply controller **374** controls the battery **308** so as to be supplied with electric power. When supply of electric power to the battery **308** or supply of electric power from the battery **308** is completed, then the electric power supply controller **374** outputs a supply termination signal.

In step S10, the electric power supply completion output unit **388** outputs an electric power supply completion signal based on supply termination signals, which are input from the electric power supply controllers **374** of all of the devices to which electric power has been supplied.

In step S11, the image capture permission instructing unit **384** outputs a message representative of permission to capture an image to the mobile terminal **42**, based on the electric power supply completion signal input from the electric power supply completion output unit **388**.

In step S12, the operator **38** prepares the first radiographic image capturing apparatus **10A** for capturing radiographic images at a site where the first radiographic image capturing apparatus **10A** has been carried. This preparatory procedure has been described in detail above, and will not be described below.

When the subject **50** is positioned during the preparatory procedure, control proceeds to step S13 shown in FIG. **21**, in which the operator **38** turns on the exposure switch **48** to begin capturing radiographic images of the subject **50**. At this time, the counter **380** updates the count by incrementing the count by +1.

When the operator **38** turns on the exposure switch **48** in step S13, then in step S14, the electric power supply limiter **338** outputs a supply limit signal to the electric power controller **334** during the aforementioned period. During the period in which the electric power controller **334** is supplied with the supply limit signal, the electric power controller **334** temporarily interrupts the operation thereof to supply electric power.

In step S15, the electric power controller **334** determines whether or not electric power needs to be re-supplied, based on whether the electric power supply controller **374** of any device has output an imaging disabled signal. More specifically, if the remaining level of electric power stored in the battery **308** of the radiation source device **18** or the cassette **12** is insufficient to capture a single radiographic image, then the electric power supply controller **374** outputs an imaging disabled signal, including the remaining level of electric power and the ID of the aforesaid device to the re-supply instructing unit **382**, for thereby requesting the re-supply instructing unit **382** to re-supply electric power.

If the electric power controller **334** judges that electric power needs to be re-supplied, then control proceeds to step S16, in which the image capture interruption instructing unit **378** outputs a message indicating interruption of image capturing to the mobile terminal **42**. The mobile terminal **42** displays a message on a display screen thereof, and preferably

outputs an alarm sound, for prompting the operator **38** to interrupt the image capturing process.

Thereafter, in step **17**, the re-supply instructing unit **382** outputs a re-supply instruction signal to the electric power supply route setting unit **370**, as well as to the amount-of-supplied-electric-power setting unit **372**.

In step **S18**, the electric power supply route setting unit **370** sets a route for re-supplying electric power (re-supply route) based on the battery charging conditions, and based on the set re-supply route, outputs a supply source instruction signal or a supply destination instruction signal to the electric power supply controller **374** of each device.

In step **S19**, the amount-of-supplied-electric-power setting unit **372** sets an amount of electric power to be re-supplied (amount of re-supplied electric power) based on a condition concerning the supplied amount, from among the battery charging conditions, and supplies information concerning the set amount of re-supplied electric power to the electric power supply controller **374** of the corresponding device.

In step **S20**, if the electric power supply controller **374** is supplied with a supply source instruction signal, then the electric power supply controller **374** controls the battery **308** in order to output electric power. Further, if the electric power supply controller **374** is supplied with a supply destination instruction signal, then the electric power supply controller **374** controls the battery **308** so as to be supplied with electric power. When supply of electric power to the battery **308**, or supply of electric power from the battery **308** is completed, the electric power supply controller **374** outputs a supply termination signal.

In step **S21**, the electric power supply completion output unit **388** outputs an electric power supply completion signal, based on supply termination signals that are input from the electric power supply controllers **374** of all of the devices to which electric power is re-supplied.

In step **S22**, the image capture permission instructing unit **384** outputs a message representing permission to capture an image to the mobile terminal **42**, based on the electric power supply completion signal input from the electric power supply completion output unit **388**. Thereafter, control returns to step **S13** and steps subsequent thereto.

If the electric power controller **334** judges that no electric power needs to be re-supplied in step **S15**, then control proceeds to step **S23**, in which the image capture completion determiner **386** determines whether or not the image capturing process is completed, by comparing the number of times that radiographic images have been captured in the image capturing conditions with the count from the counter **380**. If the count is smaller than the number of times that radiographic images have been captured, then control returns to step **S13**, and step **S13** and steps subsequent thereto are repeated until the image capturing process is brought to an end. If the image capturing process is completed, control proceeds to step **S24**, in which the electric power controller **334** is temporarily shut down. More specifically, the image capture completion determiner **386** outputs an image capture completion signal. Based on the image capture completion signal input from the image capture completion determiner **386**, the pause processor **340** outputs a pause signal to the electric power controller **334**. Based on the pause signal input from the pause processor **340**, the electric power controller **334** stops controlling supply of electric power, and waits to be activated at a subsequent time by the electric power supply activator **336**. At this stage, the operation sequence of the first radiographic image capturing apparatus **10A** is brought to an

end. However, when the electric power supply switch is operated again or the power is turned on, step **S1** and steps subsequent thereto are repeated.

An operation sequence of the first radiographic image capturing apparatus **10A**, if the supply timing conditions indicate supply of electric power before capturing of radiographic images, will be described below with reference to the flowcharts shown in FIGS. **22** through **24**. Although the electric power manager **390** mainly is involved in the operation sequence to be described below, the cassette selector **364** and the integrated supply **368** may also be included in the operation sequence.

In step **S101** shown in FIG. **22**, a message for prompting the operator **38** to enter image capturing conditions is output to the mobile terminal **42**.

In step **S102**, the electric power supply activator **336** activates the electric power controller **334** based on the present image capturing conditions (order) entered from the mobile terminal **42**. At this time, only the electric power supply activator **336** of a device having an ID, which is the same as the ID of the radiation source device **18** or the cassette **12** used to capture radiation images, which has been registered in advance in the image capturing conditions, activates the corresponding electric power controller **334**. The present image capturing conditions may be input from the data center via the network and the mobile terminal **42**. The present image capturing conditions are stored in the memory **330**.

In step **S103**, the device connection detector **360** detects whether or not the device, i.e., the radiation source device **18** or the cassette **12**, is connected to the first energy input/output unit **300** or the second energy input/output unit **302**.

After the device connection detector **360** has detected the connection in step **S103**, control proceeds to step **S104**, in which the ID acquirer **410** of the electric power manager **390** shown in FIG. **19** acquires the ID of the connected device. More specifically, the ID acquirer **410** sends a transfer request requesting the connected device to transfer the ID thereof. The connected device outputs the ID to the electric power manager **390**, and the ID acquirer **410** acquires the ID and stores the ID in the memory **330**.

In step **S105**, the information acquirer **412** for acquiring various information acquires the present image capturing conditions, which already have been stored in the memory **330**, a remaining level-of-electric-energy information table corresponding to the ID, previous image capturing conditions corresponding to the ID, and a usage history table corresponding to the ID, and stores such information in the memory **330**.

In step **S106**, the amount-of-consumed-electric-power predictor **414** calculates amounts of electric power to be consumed by the radiation source device **18** and the cassette **12** that is used to capture radiographic images, from conditions concerning the amount of electric power to be supplied (stored in the memory **330**), and the present or previous image capturing conditions, which represent the number of radiographic images to be captured, mAs values, etc., from among the battery charging conditions. The amount-of-consumed-electric-power predictor **414** then corrects the calculated amounts of electric power by multiplying the calculated amounts by usage histories of the radiation source device **18** and the cassette **12**, i.e., by coefficients corresponding to the number of times that the radiation source device **18** and the cassette **12** have been used, thereby predicting amounts of electric power that are consumed by the radiation source device **18** and the cassette **12** during the present image capturing process, or amounts of electric power consumed by the radiation source device **18** and the cassette **12** during the

previous image capturing process. The condition concerning amount of electric power from among the battery charging conditions may be an amount of electric power required to capture radiographic images in the present image capturing process, an amount of electric power required to capture a single radiographic image, or an amount of electric power consumed during the previous image capturing process. If the condition concerning the amount of electric power is an amount of electric power required to capture radiographic images during the present image capturing process, then the amount-of-consumed-electric-power predictor **414** calculates amounts of electric power that are consumed by the radiation source device **18** and the cassette **12** used to capture radiographic images in the present image capturing process, and corrects the calculated amounts of electric power by multiplying the calculated amounts by usage histories of the radiation source device **18** and the cassette **12**, i.e., by coefficients corresponding to the number of times that the radiation source device **18** and the cassette **12** have been used, thereby predicting amounts of electric power that are consumed by the radiation source device **18** and the cassette **12** during the present image capturing process, or amounts of electric power consumed by the radiation source device **18** and the cassette **12** during the previous image capturing process. If the condition concerning amount of electric power is an amount of electric power consumed during the previous image capturing process, then the amount-of-consumed-electric-power predictor **414** calculates amounts of electric power consumed by the radiation source device **18** and the cassette **12** in the previous image capturing process, and corrects the calculated amounts of electric power by multiplying the calculated amounts by usage histories of the radiation source device **18** and the cassette **12**, i.e., by coefficients corresponding to the number of times that the radiation source device **18** and the cassette **12** have been used, thereby predicting amounts of electric power consumed by the radiation source device **18** and the cassette **12** during the previous image capturing process.

In step **S107**, the electric power supply route setting unit **370** sets a route for supply of electric power based on the predicted amounts of electric power, and the remaining levels of electric power in the batteries **308** of the radiation source device **18** and the cassette **12** (remaining level-of-electric-energy information tables). Typically, the electric power supply route setting unit **370** sets a route for supply of electric power to a device, the battery of which stores a remaining level of electric power that will be almost eliminated during the present image capturing process. Information concerning the set route is displayed on the display screen of the mobile terminal **42**. If the operator **38** intends to supply electric power additionally from other devices, i.e., a radiation source device **18** and a cassette **12** that are not used to capture radiographic images, then the operator **38** enters routes for supplying electric power from such other devices, i.e., routes for supplying electric power from the other devices to the devices having IDs, together with amounts of electric power. If the operator **38** intends to charge a battery as well using another device, i.e., a radiation source device **18** or a cassette **12**, then the operator **38** enters a route for supplying electric power to or from the other device, i.e., a route from the other device to the radiation source device **18** or the cassette **12** that is used to capture radiographic images, or a route from the radiation source device **18** or the cassette **12** that is used to capture radiographic images to the other device, together with an amount of electric power to be supplied and the order in which electric power is supplied. Based on the entered route for supplying electric power, the electric power supply route

setting unit **370** outputs a supply source instruction signal or a supply destination instruction signal to the electric power supply controller **374** of each of such devices.

In step **S108**, the amount-of-supplied-electric-power setting unit **372** sets an amount of electric power to be supplied (supplied amount of electric power) based on the predicted amount of electric power and the remaining levels of electric power in the batteries **308** of the radiation source device **18** and the cassette **12** (remaining level-of-electric-energy information tables). Thus, at most, the predicted amount of electric power is supplied to a device, the battery of which stores a remaining level of electric power that will be almost eliminated during the present image capturing process. The amount of electric power, which is supplied to such a device, may be one-half or one-third the predicted amount of electric power. The information of the set amount of electric power is displayed on a display screen of the mobile terminal **42**. The set amount of electric power also can be changed as desired by the mobile terminal **42**. If the operator **38** intends to charge a battery as well, then the amount-of-supplied-electric-power setting unit **372** also sets an amount of electric power to be supplied additionally to charge the battery. The amount of electric power, which is predicted based on the previous image capturing conditions, is supplied in order to supplement the amount of electric power consumed during the previous image capturing process. If the operator **38** intends to charge a battery as well, then the amount-of-supplied-electric-power setting unit **372** also sets an amount of electric power to be supplied additionally to charge the battery. The set amount of electric power is supplied to the electric power supply controller **374** of the corresponding device.

In step **S109**, if the electric power supply controller **374** is supplied with a supply source instruction signal, then the electric power supply controller **374** controls the battery **308** to output electric power. If the electric power supply controller **374** is supplied with a supply destination instruction signal, then the electric power supply controller **374** controls the battery **308** so as to be supplied with electric power. When supply of electric power to the battery **308** or supply of electric power from the battery **308** is completed, the electric power supply controller **374** outputs a supply termination signal.

In step **S110**, the information updater **416** of the electric power manager **390**, in the remaining level-of-electric-energy information table, subtracts the amount of supplied electric power from the remaining level of electric power of the device that serves as the electric power supply source, and adds the amount of supplied electric power to the remaining level of electric power of the device that serves as the electric power supply destination.

In step **S111**, the electric power supply completion output unit **388** outputs an electric power supply completion signal based on supply termination signals input from the electric power supply controllers **374** of all of the devices to which electric power has been supplied.

In step **S112**, the image capture permission instructing unit **384** outputs a message, which represents permission to capture an image, to the mobile terminal **42** based on the electric power supply completion signal input from the electric power supply completion output unit **388**.

In step **S113** shown in FIG. 23, the operator **38** prepares the first radiographic image capturing apparatus **10A** for capturing radiographic images, at a site to which the first radiographic image capturing apparatus **10A** has been carried. This preparatory procedure has already been described in detail above, and will not be described below.

37

In step S114, the operator 38 turns on the exposure switch 48 in order to start capturing radiographic images of the subject 50. At this time, the counter 380 updates the count thereof by incrementing the count by +1.

When the operator 38 turns on the exposure switch 48 in step S114, the electric power supply limiter 338 outputs a supply limit signal to the electric power controller 334, during the period referred to above in step S115. During the period in which the electric power controller 334 is supplied with the supply limit signal, the electric power supply operation of the electric power controller 334 is limited.

In step S116, the remaining level prediction updater 392 updates, by way of subtraction, the remaining levels of electric power stored in the batteries, which are recorded in the remaining level-of-electric-energy information tables, i.e., the remaining levels of electric power stored in the batteries 308 of the radiation source device 18 and the cassette 12, which are utilized for capturing radiographic images. More specifically, with respect to the radiation source device 18 and the cassette 12 that carry out capturing of radiographic images, the remaining level prediction updater 392 calculates the amounts of electric power consumed during each time the exposure switch 48 is turned on, based on the image capturing conditions and the usage history tables, and subtracts the calculated amounts of electric power from the remaining levels of electric power stored in the batteries 308 of the radiation source device 18 and the cassette 12, which are recorded in the remaining level-of-electric-energy information tables.

In step S117, the electric power controller 334 determines whether or not electric power needs to be re-supplied, based on whether the electric power supply controller 374 of any device has output an imaging disabled signal.

If the electric power controller 334 judges that electric power needs to be re-supplied, then control proceeds to step S118, in which the image capture interruption instructing unit 378 outputs a message indicative of an image capture interruption to the mobile terminal 42. The mobile terminal 42 displays the message on a display screen thereof, and preferably outputs an alarm sound, for prompting the operator 38 to interrupt the image capturing process.

Thereafter, in step S119, the re-supply instructing unit 382 outputs a re-supply instruction signal to the electric power supply route setting unit 370, the amount-of-supplied-electric-power setting unit 372, and the electric power manager 390.

In step S120, the electric power supply route setting unit 370 sets, as a re-supply route, a route for supplying electric power to the device having the ID included in the input re-supply instruction signal, and outputs a supply source instruction signal or a supply destination instruction signal to the electric power supply controller 374 of each device, based on the set re-supply route.

In step S121, the amount-of-consumed-electric-power predictor 414 calculates amounts of electric power to be consumed by the device having the aforementioned ID, i.e., the radiation source device 18 or the cassette 12 that is re-supplied with electric power, from among the image capturing conditions for an image capturing process to be carried out, and from which image capturing conditions for radiographic images already captured (indicated by the count) are excluded, among the battery charging conditions stored in the memory 330 and the present image capturing conditions representative of the number of radiographic images to be captured, mAs values, etc. The amount-of-consumed-electric-power predictor 414 also corrects the calculated amounts of electric power by multiplying the calculated amounts by the

38

usage history of the device having the ID, i.e., a coefficient corresponding to the number of times that the device of the ID has been used, thereby predicting an amount of electric power that will be consumed by the device of the ID in the image capturing process to be carried out.

In step S122, the amount-of-supplied-electric-power setting unit 372 sets the amount of electric power predicted by the amount-of-consumed-electric-power predictor 414, as an amount of re-supplied electric power, and supplies information concerning the set amount of re-supplied electric power to the electric power supply controller 374 of the corresponding device.

In step S123, if the electric power supply controller 374 is supplied with a supply source instruction signal, then the electric power supply controller 374 controls the battery 308 to output electric power. If the electric power supply controller 374 is supplied with a supply destination instruction signal, then the electric power supply controller 374 controls the battery 308 so as to be supplied with electric power. When supply of electric power to the battery 308 or supply of electric power from the battery 308 is completed, the electric power supply controller 374 outputs a supply termination signal.

In step S124, the electric power supply completion output unit 388 outputs an electric power supply completion signal, based on supply termination signals input from the electric power supply controllers 374 of all of the devices to which electric power has been re-supplied.

In step S125, the image capture permission instructing unit 384 outputs a message to the mobile terminal 42 representing permission to capture images, based on the electric power supply completion signal input from the electric power supply completion output unit 388. Thereafter, control returns to step S114 and steps subsequent thereto.

If the electric power controller 334 judges that no electric power needs to be re-supplied in step S117, then control proceeds to step S126 shown in FIG. 24, in which the image capture completion determiner 386 determines whether or not the image capturing process is completed by comparing the number of times that radiographic images have been captured in the image capturing conditions with the count of the counter 380. If the count is smaller than the number of times that radiographic images have been captured, then control returns to step S114 shown in FIG. 23, and step S114 and steps subsequent thereto are repeated until the image capturing process is brought to an end. If the image capturing process is completed, control proceeds to step S127 shown in FIG. 24, in which the usage history updater 394 adds the number of times that the exposure switch 48 has been turned on to the number of times recorded in the usage history table, i.e., the number of times that the radiation source device 18 and the cassette 12 have been used to capture radiographic images.

In step S128, the remaining level information transfer unit 396 transfers the remaining level information table via the network to the database of the data center for updating.

In step S129, the usage history transfer unit 398 transfers the usage history table via the network to the database of the data center for updating.

In step S130, the electric power controller 334 is temporarily shut down. More specifically, the image capture completion determiner 386 outputs an image capture completion signal. Based on the image capture completion signal input from the image capture completion determiner 386, the pause processor 340 outputs a pause signal to the electric power controller 334. Based on the pause signal input from the pause processor 340, the electric power controller 334

stops controlling supply of electric power, and waits to be activated at a subsequent time by the electric power supply activator 336. At this stage, the operation sequence of the first radiographic image capturing apparatus 10A is brought to an end. However, when image capturing conditions are input again, then step S102 shown in FIG. 22 and steps subsequent thereto are repeated.

An operation sequence of the first radiographic image capturing apparatus 10A, if the supply timing conditions indicate supply of electric power after capturing of radiographic images, will be described below with reference to the flowcharts shown in FIGS. 25 and 26. Although the electric power manager 390 mainly is involved in the operation sequence to be described below, the cassette selector 364 and the integrated supply 368 may also be included in the operation sequence.

In step S201 shown in FIG. 25, a message for prompting the operator 38 to enter image capturing conditions is output to the mobile terminal 42.

In step S202, the operator 38 prepares the first radiographic image capturing apparatus 10A for capturing radiographic images at a site where the first radiographic image capturing apparatus 10A has been carried. In step S203, the operator 38 turns on the exposure switch 48 to start capturing radiographic images of the subject 50.

In step S204, the electric power controller 334 determines whether or not electric power needs to be re-supplied, based on whether the electric power supply controller 374 of any given device has output an imaging disabled signal.

If the electric power controller 334 judges that electric power needs to be re-supplied, then control proceeds to step S205, in which the image capture interruption instructing unit 378 outputs a message indicating interruption of image capturing to the mobile terminal 42. Thereafter, in step S206, the re-supply instructing unit 382 outputs a re-supply instruction signal to the electric power supply route setting unit 370, the amount-of-supplied-electric-power setting unit 372, and the electric power manager 390, thereby activating the electric power supply route setting unit 370, the amount-of-supplied-electric-power setting unit 372, and the electric power manager 390 in an interrupt routine.

In step S207, the electric power supply route setting unit 370 sets a route for supplying electric power to the device having the ID included in the input re-supply instruction signal, as a re-supply route, and based on the set re-supply route, outputs a supply source instruction signal or a supply destination instruction signal to the electric power supply controller 374 of each device.

In step S208, the amount-of-consumed-electric-power predictor 414 calculates amounts of electric power that are consumed by the device having the ID, i.e., the radiation source device 18 or the cassette 12 that are re-supplied with electric power, from image capturing conditions for an image capturing process to be carried out, from which image capturing conditions for radiographic images already captured (indicated by the count) are excluded, from among the battery charging conditions stored in the memory 330, and the present image capturing conditions representative of the number of radiographic images to be captured, mAs values, etc. The amount-of-consumed-electric-power predictor 414 also corrects the calculated amounts of electric power by multiplying the calculated amounts by a usage history of the device of the ID, i.e., a coefficient corresponding to the number of times that the device of the ID has been used, thereby predicting an amount of electric power to be consumed by the device of the ID in the image capturing process to be carried out.

In step S209, the amount-of-supplied-electric-power setting unit 372 sets the amount of electric power predicted by the amount-of-consumed-electric-power predictor 414 as an amount of re-supplied electric power, and outputs the information concerning the set amount of re-supplied electric power to the electric power supply controller 374 of the corresponding device.

In step S210, if the electric power supply controller 374 is supplied with a supply source instruction signal, then the electric power supply controller 374 controls the battery 308 to output electric power. Further, if the electric power supply controller 374 is supplied with a supply destination instruction signal, then the electric power supply controller 374 controls the battery 308 so as to be supplied with electric power. When supply of electric power to the battery 308 or supply of electric power from the battery 308 is completed, then the electric power supply controller 374 outputs a supply termination signal.

In step S211, the electric power supply completion output unit 388 outputs an electric power supply completion signal based on supply termination signals, which are input from the electric power supply controllers 374 of all of the devices to which electric power has been re-supplied.

In step S212, the image capture permission instructing unit 384 outputs a message representing permission to capture an image to the mobile terminal 42, based on the electric power supply completion signal input from the electric power supply completion output unit 388. Thereafter, control returns to step S203 and steps subsequent thereto.

If the electric power controller 334 judges that no electric power needs to be re-supplied in step S204, then control proceeds to step S213, in which the image capture completion determiner 386 determines whether or not the image capturing process is completed. If the image capturing process is not completed, then control returns to step S203, and step S203 and steps subsequent thereto are repeated until the image capturing process is brought to an end. If the image capturing process has finished, control proceeds to step S214, in which the electric power supply activator 336 activates the electric power controller 334 based on an image capture completion signal input from the image capture completion determiner 386. At this time, only the electric power supply activator 336 of a device having an ID that is the same as the ID of the radiation source device 18 or the cassette 12 that is used to capture radiation images, which has been registered in advance in the image capturing conditions, activates the corresponding electric power controller 334.

In step S215 shown in FIG. 26, the device connection detector 360 detects whether or not the device is connected to the first energy input/output unit 300 or the second energy input/output unit 302.

After the device connection detector 360 has detected the connection in step S215, control proceeds to step S216, in which the ID acquirer 410 of the electric power manager 390 acquires the ID of the connected device. Thereafter, in step S217, the information acquirer 412 for acquiring various information acquires the present image capturing conditions, which have already been stored in the memory 330, a remaining level-of-electric-energy information table corresponding to the ID, previous image capturing conditions corresponding to the ID, and a usage history table corresponding to the ID, and stores such information in the memory 330.

In step S218, the amount-of-consumed-electric-power predictor 414 calculates amounts of electric power to be consumed by the radiation source device 18 and the cassette 12, which are used to capture radiographic images, from a condition concerning the amount of electric power to be supplied,

and the present or previous image capturing conditions representative of the number of radiographic images to be captured, mAs values, etc., from among the battery charging conditions.

In step S219, the electric power supply route setting unit 370 sets a route for supply of electric power, based on the predicted amounts of electric power and the remaining levels of electric power in the batteries 308 of the radiation source device 18 and the cassette 12 (remaining level-of-electric-energy information tables).

Thereafter, in step S220, the amount-of-supplied-electric-power setting unit 372 sets an amount of electric power to be supplied (supplied amount of electric power), based on the predicted amount of electric power, and the remaining levels of electric power in the batteries 308 of the radiation source device 18 and the cassette 12 (remaining level-of-electric-energy information tables).

In step S221, if the electric power supply controller 374 is supplied with a supply source instruction signal, then the electric power supply controller 374 controls the battery 308 to output electric power. Further, if the electric power supply controller 374 is supplied with a supply destination instruction signal, then the electric power supply controller 374 controls the battery 308 so as to be supplied with electric power. When supply of electric power to the battery 308 or supply of electric power from the battery 308 is completed, the electric power supply controller 374 outputs a supply termination signal.

In step S222, the information updater 416, in the remaining level-of-electric-energy information table, subtracts the amount of supplied electric power from the remaining level of electric power of the device that serves as an electric power supply source, and adds the amount of supplied electric power to the remaining level of electric power of the device that serves as an electric power supply destination.

In step S223, the electric power supply completion output unit 388 outputs an electric power supply completion signal, based on supply termination signals input from the electric power supply controllers 374 of all of the devices to which electric power has been supplied.

In step S224, the usage history updater 394 adds the number of times that the exposure switch 48 has been turned on to the number of times recorded in the usage history table, i.e., the number of times that the radiation source device 18 and the cassette 12 have been used to capture radiographic images.

In step S225, the remaining level information transfer unit 396 transfers the remaining level information table via the network to the database of the data center for updating. In step S226, the usage history transfer unit 398 transfers the usage history table via the network to the database of the data center for updating. Thereafter, in step S227, the pause processor 340 temporarily shuts down the electric power controller 334. At this stage, the operation sequence of the first radiographic image capturing apparatus 10A is brought to an end. However, when image capturing conditions are input again, step S202 shown in FIG. 25 and steps subsequent thereto are repeated.

Since in the first radiographic image capturing apparatus 10A, the timing at which electric power is supplied can be determined so as to supply electric energy before an image capturing process is carried out, electric power required to capture radiographic images can be ensured without wasteful electric power consumption. Since electric power required to capture radiographic images is predicted and supplied in accordance therewith, electric power is supplied efficiently. The first radiographic image capturing apparatus 10A

requires only the batteries 308 of the radiation source device 18 and the cassette 12 as power supplies thereof. Therefore, the first radiographic image capturing apparatus 10A is small in size and weight when carried, and is convenient to use (e.g., is portable). Since electric power required to capture radiographic images is predicted and supplied in accordance therewith, it is possible to save steps for electric power management.

Furthermore, since in the first radiographic image capturing apparatus 10A, the timing at which electric power is supplied can be determined in order to supply electric energy after an image capturing process has been performed, and the amount of electric power required to capture at least one radiographic image can be ensured, the first radiographic image capturing apparatus 10A can quickly be readied to perform a next image capturing process. Since the timing at which electric power is supplied can be determined, there is no wasteful electric power consumption. The first radiographic image capturing apparatus 10A requires only the batteries 308 of the radiation source device 18 and the cassette 12 as power supplies thereof. Therefore, the first radiographic image capturing apparatus 10A is small in size and weight when carried, and is convenient to use (e.g., is portable).

In the first radiographic image capturing apparatus 10A, supply of electric power is limited (i.e., supply of electric power is stopped or the amount of electric power supplied per unit time is reduced) during a period in which noise is likely to be added to radiographic image information being captured. Consequently, wasteful consumption of electric power is minimized for enabling low electric power consumption, while at the same time the quality of the radiographic image information is prevented from becoming degraded.

In the first radiographic image capturing apparatus 10A, since the electric power controller 334 controls electric power supplied only along a route from the radiation source device 18 to the cassette 12, only the batteries 308 of the radiation source device 18 and the cassette 12 are required as power supplies thereof. Therefore, the first radiographic image capturing apparatus 10A is small in size and weight when carried, and is convenient to use (e.g., is portable). A built-in capacitor may be used as the battery 308 of the cassette 12. In such a case, since a separate battery is not required as the battery 308 for the cassette 12, the user is able to carry the first radiographic image capturing apparatus 10A easily. Similarly, if the electric power controller 334 controls electric power so as to be supplied with power only along a route from the cassette 12 to the radiation source device 18, then a built-in capacitor may be used as the battery 308 of the radiation source device 18. In such a case, since a separate battery is not required as the battery 308 for the radiation source device 18, the user is able to carry the first radiographic image capturing apparatus 10A easily.

The radiation source device 18 is supplied with electric power preferentially from a cassette 12 that has been deteriorated greatly, or from a cassette 12 having a small remaining built-in memory capacity. Therefore, electric power stored in a cassette 12, which has not been deteriorated greatly, or in a cassette 12 having a large remaining built-in memory capacity, can be saved, thereby enabling the first radiographic image capturing apparatus 10A to be readily available for emergencies.

The radiation source device 18 is supplied with electric power preferentially from a cassette 12 that is located closer to the radiation source device 18. Therefore, the time required to supply electric power to the radiation source device 18 is shortened, thereby making the first radiographic image capturing apparatus 10A readily available for emergencies.

Similarly, the radiation source device **18** is supplied with electric power preferentially from a cassette **12** that is smaller in size. Therefore, electric power stored in a cassette **12**, which is larger in size and hence more versatile, can be saved, thereby making the first radiographic image capturing apparatus **10A** readily available for emergencies.

Since the first radiographic image capturing apparatus **10A** includes the electric power manager **390**, the level of electric power required to capture a desired number of radiographic images is managed, so as to supply electric power from a device, the battery of which stores excessive electric power to a device having a battery with insufficient electric power, for example, up to the level of the required electric power. Therefore, the radiation source device **18** and the cassette **12** can be supplied efficiently with electric power, thereby making the first radiographic image capturing apparatus **10A** readily available in an emergency and reducing consumption of electric power. Further, since electric power required to capture radiographic images can flexibly be supplied from another device, which is not used in the image capturing process, the first radiographic image capturing apparatus **10A** can be made readily available for emergencies. Also, since electric power management is made automatically, radiographic images can be captured quickly by skipping cumbersome steps such as battery checking. Further, the first radiographic image capturing apparatus **10A** requires only the batteries **308** of the radiation source device **18** and the cassette **12** as power supplies thereof. Therefore, the first radiographic image capturing apparatus **10A** is small in size and weight when carried, and is convenient to use (e.g., is portable).

When a need arises to capture radiographic images of examinees at accident sites, disaster sites, or on transport vehicles such as ambulances (while in movement or at rest), railway cars, ships, aircrafts, or the like, the first radiographic image capturing apparatus **10A** can be used quickly to start capturing radiographic images of an examinee, such as an accident victim or a disaster victim, without requiring the examinee to be moved unduly to a mobile medical checkup motor vehicle. While on a transport vehicle, the first radiographic image capturing apparatus **10A** can quickly begin capturing radiographic images of the examinee, without having to wait for the transport vehicle to arrive at a station, a port, or an airport. While on an ambulance, the first radiographic image capturing apparatus **10A** can send captured radiographic image information to a medical organization such as a hospital before the ambulance reaches the hospital. As a consequence, a doctor at the hospital can recognize the condition of the examinee in advance, and hence can quickly prepare the examinee for treatment.

It is possible to carry several first radiographic image capturing apparatus **10A** on a mobile medical checkup motor vehicle to perform periodic or temporary medical checkups at schools or large corporations where the number of examinees is large. Usually, since a single mobile medical checkup motor vehicle, which is equipped with a single ordinary radiographic image capturing apparatus, is dispatched to such locations, it has been customary for such examinees to have to wait a very long time before radiographic images of the examinees can be captured. According to the present invention, several first radiographic image capturing apparatus **10A** can be used simultaneously in order to minimize the waiting time before radiographic images of examinees can be captured.

Electric power can be supplied along a wired route or a wireless route. For example, electric power can be supplied along a route from a radiation source device **18** used in an image capturing process to a cassette **12** used in the image

capturing process, along a route from another radiation source device **18**, which is not used in an image capturing process, to the cassette **12** that is used in the image capturing process, or along a route from another cassette **12**, which is not used in an image capturing process, to the cassette **12** that is used in the image capturing process. In addition, electric power can be supplied along a route from a cassette **12** used in an image capturing process to a radiation source device **18** used in the image capturing process, or along a route from another radiation source device **18**, which is not used in an image capturing process, to the radiation source device **18** that is used in the image capturing process. Electric power can be supplied to a device, e.g., the radiation source device **18** or the cassette **12**, in a wireless fashion, when the device enters into an area enabling wireless feeding of power thereto.

If an electric power supply route is fixed to a route from the radiation source device **18** to the cassette **12**, or from the cassette **12** to the radiation source device **18**, then since a user is required to confirm only the level of electric power in the supply source, a preparatory process for supplying electric power can be simplified, and radiographic images can be captured quickly.

If the first energy input/output unit **300** is used via a wired connection and the second energy input/output unit **302** is used via a wireless connection, then composite connections are made available for supplying electric power. For example, electric power can be supplied along a route from the radiation source device **18** to the cassette **12** and another radiation source device **18**, along a route from the radiation source device **18** to the cassette **12** and another cassette **12**, along a route from the cassette **12** to the radiation source device **18** and another cassette **12**, or along a route from the cassette **12** to the radiation source device **18** and another radiation source device **18**.

In the above embodiment, the battery controller **306** is provided in each of the devices, e.g., the radiation source device **18** and the cassette **12**. However, among the components that make up the battery controller **306**, the electric power supply controller **374** and the remaining level detector **376** may be provided in each of the devices, whereas the other components thereof may be provided only in the radiation source device **18** or in the cassette **12** that is used in an image capturing process, e.g., in any one of a radiation source device **18**, a cassette **12**, and a PC **280**, which are used in an image capturing process of a third radiographic image capturing apparatus **10C**, to be described later. Among the components of the electric power controller **334**, only the electric power manager **390** may be provided in either one of the radiation source device **18** or the cassette **12** that is used in an image capturing process, e.g., in any one of the radiation source device **18**, the cassette **12**, and the PC **280**, which are used in an image capturing process of the third radiographic image capturing apparatus **10C**, to be described later.

While the first radiographic image capturing apparatus **10A** is transported, the radiation source device **18** and the cassette **12** are coupled integrally to each other by the joining mechanism **82**. While the first radiographic image capturing apparatus **10A** operates to capture radiographic images, the radiation source device **18** and the cassette **12** are separated from each other, and then the radiation source **44** of the radiation source device **18** emits radiation **46** that is applied to the subject **50**. Therefore, the first radiographic image capturing apparatus **10A** of a portable type, which is small in size and weight, can simply and quickly be readied for capturing radiographic images.

The radiation detector **86** may comprise a light readout type of radiation detector for acquiring radiographic image

information. When radiation is applied through a subject to solid-state detecting elements of the light readout type of radiation detector, the solid-state detecting elements store respective electrostatic latent images of the subject depending on the applied dose of the radiation. For reading the stored electrostatic latent images, reading light is applied to the radiation detector in order to cause the solid-state detecting elements to generate currents that depend on the stored electrostatic latent images. The generated currents are detected as representative of radiographic image information of the subject. Thereafter, erasing light is applied to the radiation detector in order to erase remaining electrostatic latent images from the solid-state detecting elements, so that the radiation detector can be reused. For details, reference should be made to Japanese Laid-Open Patent Publication No. 2000-105297.

The first radiographic image capturing apparatus 10A may comprise a water-resistant, hermetically sealed structure, thereby making the first radiographic image capturing apparatus 10A resistant to contamination by blood and bacteria. When necessary, the first radiographic image capturing apparatus 10A may be cleaned and sterilized for enabling repetitive use.

The first radiographic image capturing apparatus 10A may perform wireless communications with an external device by way of ordinary wireless communications using radio waves, or by way of optical wireless communications using infrared rays or the like.

In the first embodiment, as shown in FIG. 27, the first radiographic image capturing apparatus 10A may be devoid of the tape measure 72. Without the tape measure 72, the first radiographic image capturing apparatus 10A provides the same advantages offered by components thereof other than the tape measure 72.

As described above, major components of the joining mechanism 82 are provided in the cassette 12. However, the joining mechanism 82 may be provided in the radiation source device 18. Such a modification offers the same advantages as those referred to above.

The first radiographic image capturing apparatus 10A may be modified as described below.

FIG. 28 shows a first radiographic image capturing apparatus 10A according to a modification, in which the unlocking button 34, the hook 64, etc., are provided in the radiation source device 18.

As shown in FIG. 28, the side 14a of the cassette 12 does not include the aforementioned holders 16a, 16b, and the radiation source device 18 has a flat side, which faces the side 14a of the cassette 12. Opposite ends of the radiation source device 18 have respective unlocking buttons 34. The radiation source device 18 also has through holes 62 and hooks 64 provided in the flat side thereof, which faces the side 14a of the cassette 12, near opposite ends of the radiation source device 18. Connection terminals 68a, 68b are disposed on the flat side of the radiation source device 18 near one of the ends of the radiation source device 18.

The side 14a of the cassette 12 has through holes 66 defined therein, which are in alignment with the respective through holes 62 and connection terminals 70a, 70b, which in turn are in alignment with the connection terminals 68a, 68b.

The first radiographic image capturing apparatus 10A shown in FIG. 28 operates in the following manner. While the flat side of the radiation source device 18 and the side 14a of the cassette 12 face toward each other, the hooks 64 are inserted into the respective through holes 66, and the connection terminals 68a, 68b and the connection terminals 70a, 70b

are brought into engagement with each other. At this time, the radiation source device 18 and the cassette 12 are integrally joined to each other.

The first radiographic image capturing apparatus 10A shown in FIG. 28 offers the same advantages as the first radiographic image capturing apparatus 10A according to the first embodiment.

According to the modification shown in FIG. 28, since the unlocking buttons 34 are disposed on opposite ends of the radiation source device 18, an operator 38 can easily disconnect the radiation source device 18 from the cassette 12, simply by detaching the radiation source device 18 from the cassette 12 while pressing the unlocking buttons 34.

In the first embodiment, as shown in FIG. 29, a cradle 180 for charging the batteries 308 of the first radiographic image capturing apparatus 10A may be positioned at a desired location in the hospital. The cradle 180 is not only capable of charging the batteries 308, but may also have a wireless or wired communication function for sending and receiving necessary information to and from an external device in the hospital. Information sent from the cradle 180 may include radiation image information recorded in the first radiographic image capturing apparatus 10A, which is connected to the cradle 180.

The cradle 180 has a display unit 182 for displaying the charged state of the first radiographic image capturing apparatus 10A, which is connected to the cradle 180, and other necessary information, including radiation image information acquired from the first radiographic image capturing apparatus 10A.

A plurality of cradles 180 may be connected through a network, and charged states of respective first radiographic image capturing apparatus 10A, which are connected to the cradles 180, may be retrieved through the network, so that the user can confirm the locations of first radiographic image capturing apparatus 10A that are sufficiently charged, based on the retrieved charged states.

A radiographic image capturing apparatus 10B according to a second embodiment of the present invention, which will hereinafter be referred to as a "second radiographic image capturing apparatus 10B," will be described below with reference to FIGS. 30 through 37.

The second radiographic image capturing apparatus 10B essentially is identical in structure to the first radiographic image capturing apparatus 10A according to the first embodiment, but differs therefrom in that a detecting screen 250 is drawn out slightly from the cassette 12 through the side 14b thereof that is remote from the side 14a on which the holders 16a, 16b project, and a weight bar 252 is coupled to a distal end of the detecting screen 250. Among the other sides 14c, 14d of the cassette 12, side 14c has the first energy input/output unit 300 or the second energy input/output unit 302 (see FIG. 13) for inputting and outputting electric power through a wired or wireless link, for example, a USB terminal 28 that serves as an interface means for sending and receiving information to and from an external device, a card slot 32 for inserting the memory card 30 therein, and the unlocking button 34, to be described later. On an upper surface 254 of the cassette 12, the mobile terminal 42 is mounted, which is detachable from the cassette 12 and includes the display unit 36 and the operating unit 40, which is operated by the operator 38. The radiation source device 18 has an exposure switch 48, which can be operated by the operator 38 in order to cause the radiation source 44, which shall be described later, to start emitting radiation 46.

FIGS. 30 and 31 show the second radiographic image capturing apparatus 10B in a state of being carried by the

operator 38. When the second radiographic image capturing apparatus 10B is carried by the operator 38, the radiation source device 18 and the cassette 12 are joined integrally to each other.

When the second radiographic image capturing apparatus 10B is brought to a site, such as a disaster site, a home-care service site, or the like, the second radiographic image capturing apparatus 10B is expanded to result in the state shown in FIGS. 32 through 37.

As shown in FIG. 36, the upper surface 254 of the cassette 12 has the recess 54, which accommodates the mobile terminal 42 therein. As shown in FIGS. 32 and 34, the cassette 12 houses therein a storage box 256, accommodating therein a roll screen, which constitutes a rolled form of the detecting screen 250 and is made of a flexible material permeable to radiation 46. The storage box 256 supports on a side thereof a rotary encoder 258 for detecting the length by which the detecting screen 250 has been reeled out from the storage box 256. The side wall 52b of the cassette 12, which makes up the side 14b, has a slot 260 defined therein, through which the detecting screen 250 can be reeled out from the storage box 256.

When the operator 38 pulls the weight bar 252 in a direction away from the cassette 12, the detecting screen 250 is drawn or extended out from the storage box 256 through the slot 260. At times when the second radiographic image capturing apparatus 10B is being carried, the detecting screen 250 is rolled up inside the storage box 256. When the second radiographic image capturing apparatus 10B is operated to capture radiographic images, as shown in FIGS. 34, 36 and 37, the detecting screen 250 is drawn out or extended substantially flatwise underneath the radiation source device 18 by the operator 38 pulling the weight bar 252. The detecting screen 250 has gradations 262 on both side edges thereof along the direction in which the detecting screen 250 is pulled.

As shown in FIG. 35, the detecting screen 250 houses therein a grid 84 for removing scattered rays of radiation 46 from the subject 50 when the radiation source 44 applies radiation 46 to the subject 50, a radiation detector 86 for detecting radiation 46 that has passed through the subject 50, and a lead sheet 89 for absorbing back scattered rays of radiation 46, which are successively arranged in this order from the irradiated surface 20 of the detecting screen 250, i.e., the upper surface of the detecting screen 250, as shown in FIGS. 34 through 37. The irradiated surface 20 may be constructed as the grid 84. The grid 84, the radiation detector 86, and the lead sheet 89 are flexible.

For irradiating the subject 50 with radiation 46 in order to capture radiographic images of the subject 50, a preparatory procedure must first be performed for readying the second radiographic image capturing apparatus 10B for capturing radiographic images. Such a preparatory procedure includes a process for presetting a source-to-image distance (SID), which represents an distance (imaging distance) between the focus point 122 of the radiation source 44 and a position 124 (see FIG. 35) on the radiation detector 86 that lies straight below the focus point 122, and a process for bringing the central position 126 of the irradiated surface 20 of the detecting screen 250 into alignment with the center of a range within which the irradiated surface 20 is irradiated with radiation 46.

The preparatory procedure is carried out as follows. As shown in FIGS. 34 through 36, while the radiation source device 18 is separated from the cassette 12, the operator 38 pulls the ribbon 76 from the tape measure 72 until the length of the ribbon 76, which is reeled out from the tape measure 72,

becomes equal to the reeled-out length 11 depending on the SID. The laser pointer 104 is controlled by the radiation source controller 102 in order to apply a laser beam 128 to the irradiated surface 20, thereby displaying a crisscross mark 130 on the irradiated surface 20, which represents the center of a range within which the irradiated surface 20 is irradiated with radiation 46.

The operator 38 determines the central position of the irradiated surface 20 by observing the gradations 262 thereon. The SID, the reeled-out length 11 depending on the SID, and a distance 12 between the position 124 or the central position 126 and the side 14a having the hole 80 through which the ribbon 76 is pulled out, are related to each other according to the equation  $SID \approx (11^2 - 12^2)^{1/2}$ .

After the ribbon 76 has been pulled from the tape measure 72 by the reeled-out length 11, the operator 38 adjusts the position of the radiation source device 18 so as to bring the mark 130 displayed on the irradiated surface 20 into alignment with the central position 126. Thereafter, the operator 38 turns on the exposure switch 48 in order to enable the radiation source 44 to apply radiation 46 with respect to the subject 50 on the irradiated surface 20, thereby capturing radiographic images of the subject 50, as shown in FIG. 37. In FIG. 37, an example is shown in which a radiographic image of a hand of the subject 50 is captured.

The second radiographic image capturing apparatus 10B also operates according to the operation sequences shown in FIGS. 20 through 26. The second radiographic image capturing apparatus 10B is operated according to a preparatory procedure and an image capturing process as follows.

First, the operator performs operations to ready the second radiographic image capturing apparatus 10B for capturing radiographic images at a site where the second radiographic image capturing apparatus 10B has been carried. The operator 38 operates the operating unit 40 of the mobile terminal 42 in order to register image capturing conditions, including subject information (e.g., SID) of the subject 50 to be imaged.

The operator 38 pulls the weight bar 252 in order to draw or extend the detecting screen 250 from the storage box 256 by a given length (drawn-out length 13), which is required to capture radiographic images of a body region of the subject 50 to be imaged. The rotary encoder 258 detects the drawn-out length 13 of the detecting screen 250, and sends a signal representative of the detected drawn-out length 13 to the SID determining unit 168.

When the unlocking button 34 is pressed by the operator 38, the hook 64 and the slide 56 are displaced against the resiliency of the spring 60 and along the side wall 52a toward the side wall 52d, thereby bringing the hook 64 out of engagement with the edge of the through hole 66.

While the hook 64 is kept out of engagement with the edge of the through hole 66, i.e., while the operator 38 presses the unlocking button 34, the operator 38 removes or separates the radiation source device 18 from the cassette 12. The connection terminal 68a becomes disengaged from the connection terminal 70a, and the connection terminal 68b becomes disengaged from the connection terminal 70b, thereby releasing the radiation source device 18 and the cassette 12 from each other. The operator 38 sets the imaging distance and brings the mark 130, which is displayed on the irradiated surface 20, into alignment with the central position 126. Thereafter, the operator 38 places and positions the subject 50 between the irradiated surface 20 and the radiation source device 18. The operator 38 moves the radiation source device 18 in order to reel out the ribbon 76 from the tape measure 72, until the actual reeled-out length of the ribbon 76 reaches the reeled-out length 11 depending on the SID.

After having adjusted the position of the radiation source device **18** until the mark **130** and the central position **126** are aligned with each other, the operator **38** places or positions the subject **50** on the irradiated surface **20**, so that the center of a body region of the subject **50** to be imaged is aligned with the central position **126**, i.e., the position of the mark **130**.

After the above positional adjustment has been carried out, the radiation source device **18** is secured to the adjusted position by a holder, not shown, for example.

After the subject **50** is positioned, the operator **38** turns on the exposure switch **48** in order to start capturing radiographic images of the subject **50**.

The second radiographic image capturing apparatus **10B** offers the same advantages as the first radiographic image capturing apparatus **10A**.

While the second radiographic image capturing apparatus **10B** is transported, the radiation source device **18** and the cassette **12** are coupled to each other integrally by the joining mechanism **82**. While the second radiographic image capturing apparatus **10B** is operated to capture radiographic images, the radiation source device **18** and the cassette **12** are separated from each other, and the detecting screen **250** is drawn and extended from the cassette **12**. Thereafter, the radiation source **44** of the radiation source device **18** emits radiation **46**, which is applied to the subject **50**. Therefore, the second radiographic image capturing apparatus **10B** of a portable type, which is small in size and weight, can simply and quickly be readied for capturing radiographic images.

The storage box **256**, which is disposed in the cassette **12**, accommodates therein the detecting screen **250** in a rolled-up form, so as to be flexible and capable of being extended in sheet form. When the second radiographic image capturing apparatus **10B** is carried to a site, such as a disaster site, a home-care service site, or the like, the detecting screen **250** is stored in a rolled-up form inside the storage box **256**. When the second radiographic image capturing apparatus **10B** is operated to capture radiographic images, the detecting screen **250** is drawn out from the storage box **256** in a flat sheet form. Therefore, the second radiographic image capturing apparatus **10B** is small in overall size.

A portable radiographic image capturing apparatus according to a third embodiment of the present invention, which hereinafter will be referred to as a "third radiographic image capturing apparatus **10C**," will be described in detail below with reference to FIGS. **38** through **47**.

The third radiographic image capturing apparatus **10C** includes the radiation source device **18**, the cassette **12**, and a personal computer (controller, PC) **280**, which is electrically connected to the radiation source device **16** by a wired or wireless input/output unit, as well as being electrically connected to the cassette **12** by a wired or wireless input/output unit. Further, the third radiographic image capturing apparatus **10C** incorporates therein a digital camera **270** for capturing an image of a predetermined imaging area. The PC **280** can be operated by the operator **38** (see FIG. **41**) of the third radiographic image capturing apparatus **10C**. The PC **280** is capable of sending signals to and receiving signals from a medical organization to which the operator **38** belongs, by way of wireless communications via a network such as a public network or the like.

The cassette **12** includes the battery unit **304**, a battery controller **306**, a radiation detector **86**, a cassette controller **92**, and a transceiver **94**, which are identical to those shown in FIG. **11**. As shown in FIG. **38**, the cassette **12** has a first energy input/output unit **300** and a second energy input/output unit **302** located on a side wall of the casing. The radiation source device **18** includes a battery unit **304**, a battery controller **306**,

a transceiver **100**, a radiation source controller **102** for controlling the radiation source **44**, and a laser pointer **104**, which are identical to those shown in FIG. **11**. A first energy input/output unit **300** and a second energy input/output unit **302**, which are identical to those of the cassette **12**, are mounted respectively on a side wall and a circumferential wall of the casing of the radiation source device **18**, as shown in FIG. **38**.

As shown in FIG. **38**, the PC **280** comprises a notebook-shaped personal computer, including an operating unit **282** such as a keyboard, a mouse, or the like, and a display unit **284**. Alternatively, the PC **280** may be replaced with a mobile phone or a PDA (Personal Digital Assistant).

The PC **280** has a power supply switch, speakers, a microphone, and other accessories, similar to those of ordinary notebook-shaped personal computers. The PC **280** incorporates therein a transceiver **288** (see FIG. **42**) for sending information to and receiving information from an external device such as a network, the radiation source device **18**, the cassette **12**, or the like. The PC **280** also includes, on a side wall thereof, a first energy input/output unit **300**, and a second energy input/output unit **302**. In FIG. **38**, the first energy input/output unit **300** of the PC **280** is connected by a cable to the first energy input/output unit **300** of the radiation source device **18**, while the second energy input/output unit **302** of the PC **280** is connected by a cable to the first energy input/output unit **300** of the cassette **12**. However, the first energy input/output unit **300** and the second energy input/output unit **302** may be connected wirelessly.

As shown in FIG. **42**, the PC **280** includes a battery unit **304** and a battery controller **306**, which are identical to those of the radiation source device **18**.

FIG. **41** shows the manner in which the third radiographic image capturing apparatus **10C** is carried by an operator **38**.

When the third radiographic image capturing apparatus **10C** is carried by the operator **38**, the radiation source device **18**, the cassette **12**, and the folded PC **280** are electrically disconnected and housed in an attaché case **286**. The operator **38** can grip a grip **24** of the attaché case **286** and carry the attaché case **286** from the medical organization to a desired site, e.g., a disaster site or a home-care service site. At the site where the attaché case **286** has been carried, the operator **38** can take out the radiation source device **18**, the cassette **12**, and the folded PC **280** from the attaché case **286**, and assemble them into the configuration shown in FIGS. **38** through **40**. The operator **38** then can perform a preparatory procedure in order to ready the third radiographic image capturing apparatus **10C** for capturing radiographic images of a person at a disaster site or a home-care service site.

The third radiographic image capturing apparatus **10C** also operates according to the operation sequences shown in FIGS. **20** through **26**. In accordance with a preparatory procedure, the third radiographic image capturing apparatus **10C** operates in the following manner.

The operator **38** takes the radiation source device **18**, the cassette **12**, etc., out of the attaché case **286**, and electrically connects the radiation source device **18** and the cassette **12** to the PC **280** in a wired or wireless fashion. The operator **38** places the PC **280**, the radiation source device **18**, and the cassette **12** in the positional relationship shown in FIGS. **38** through **40**.

Then, the operator **38** starts up the PC **280**, thereby readying the third radiographic image capturing apparatus **10C** for capturing radiographic images. Thereafter, the operator **38** turns on the exposure switch **48** to begin capturing radiographic images.

Electric power may be supplied via the PC **280** according to a process that differs from the process carried out by the

first radiographic image capturing apparatus 10A and the second radiographic image capturing apparatus 10B. The different process comprises an electric power collecting process for collecting all or part of the electric power stored in the battery 308 of the radiation source device 18, and all or part of the electric power stored in the battery 308 of the cassette 12, for the battery unit 304 of the PC 280.

An electric power collector 420 for carrying out the above electric power collecting process will be described below with reference to FIGS. 43 and 44.

The electric power collector 420 is incorporated in the battery controller 306. The electric power collector 420 is activated by an operation made by the operator 38 in order to instruct collection of electric power, e.g., by left-clicking on an icon representing collection of electric power. As shown in FIG. 43, the electric power collector 420 comprises the device connection detector 360, an electric power collection ID acquirer 422, an electric power collection information acquirer 424, an electric power collection supply route setting unit 426, an electric power collection level setting unit 428, the electric power supply controller 374, the remaining level detector 376, an electric power collection remaining level updater 430, and an electric power collection remaining level information transfer unit 432.

Details of an operation sequence of the electric power collector 420 will be described below with reference to FIGS. 43 and 44.

In step S301 shown in FIG. 44, the device connection detector 360 detects devices, i.e., the radiation source device 18 and the cassette 12, which are connected to the first energy input/output unit 300 and the second energy input/output unit 302 of the PC 280.

The electric power collection ID acquirer 422 sends a transfer request to the connected devices for transferring IDs. Based on the transfer request, the connected devices output IDs thereof to the electric power collector 420. The electric power collection ID acquirer 422 acquires the IDs from the connected devices, and registers the IDs in the memory 330 (see FIG. 14) in step S302.

The electric power collection information acquirer 424 acquires remaining level information tables corresponding to the IDs, and stores the acquired remaining level information tables in the memory 330 in step S303.

The electric power collection supply route setting unit 426 sets a supply route from the device connected to the first energy input/output unit 300 to the PC 280, and a supply route from the device connected to the second energy input/output unit 302 to the PC 280. Based on the set supply routes, in step S304, the electric power collection supply route setting unit 426 outputs supply source instruction signals to the electric power supply controllers 374 of the respective devices.

In step S305, the electric power collection level setting unit 428 sets an electric power collection level using the operating unit 282, e.g., a keyboard or a mouse, of the PC 280. The electric power collection level represents the sum of a first electric power level to be supplied from the device connected to the first energy input/output unit 300 to the battery 308 of the PC 280, and a second electric power level to be supplied from the device connected to the second energy input/output unit 302 to the battery 308 of the PC 280. The first electric power level and the second electric power level are supplied respectively to the electric power supply controllers 374 of the respective devices.

Based on the supply source instruction signals, the electric power supply controllers 374 of the devices control the batteries 308 thereof to output electric power. Further, based on a supply source instruction signal, the electric power supply

controller 374 of the PC 280 controls the battery 308 thereof to input electric power in step S306. The electric power supply controllers 374 control the batteries 308 to supply electric power, and to be supplied with electric power, at a constant charging rate or at a discharging rate based on the remaining level sent from the remaining level detector 376. If the level of electric power to be supplied is low, then it is possible to charge and discharge the batteries 308 quickly.

In step S307, the electric power collection remaining level updater 430 updates the remaining battery level corresponding to the ID of the device that is connected to the first energy input/output unit 300, by subtracting the first electric power level from the remaining battery level. The electric power collection remaining level updater 430 also updates the remaining battery level corresponding to the ID of the device that is connected to the second energy input/output unit 302, by subtracting the second electric power level from the remaining battery level.

When the updating process of the electric power collection remaining level updater 430 is completed, then in step S308, the electric power collection remaining level information transfer unit 432 transfers the remaining level information tables via the network to the database of the data center for updating.

The electric power collector 420 may be activated by operations made by the operator 38 on the operating unit 282, for example, regardless of location and time. For example, when the third radiographic image capturing apparatus 10C is carried into a medical organization, the electric power collector 420 may be activated in order to collect electric power in the battery 308 of the PC 280. Then, when the third radiographic image capturing apparatus 10C is carried to a site outside of the medical organization, the radiation source device 18 and the cassette 12, which are used to capture radiographic images, may be supplied with electric power from the PC 280. At this time, the electric power manager 390 supplies an optimum electric power level for capturing radiographic images to the radiation source device 18 and to the cassette 12. Alternatively, the electric power collector 420 may be activated at a site outside of the medical organization, so as to collect into the PC 280 electric power from a radiation source device 18 and a cassette 12, which have deteriorated significantly and which cannot be used to capture radiographic images, and to supply the collected electric power to the radiation source device 18 and the cassette 12 that currently are being used to capture radiographic images.

Since the PC 280 can supply electric power to respective devices, it is possible to set a supply route from the PC 280 to a radiation source device 18 that is used to capture radiographic images, as well as a supply route from the PC 280 to a cassette 12 that is used to capture radiographic images. It also is possible to set a supply route from the PC 280 as a supply source to the aforesaid radiation source device 18, as well as a supply route from the PC 280 as a supply source to the aforesaid cassette 12. Furthermore, it is possible to set a supply route from the aforesaid radiation source device 18 via the PC 280 to the aforesaid cassette 12, as well as a supply route from the aforesaid cassette 12 via the PC 280 to the aforesaid radiation source device 18.

Since electric power can be supplied from the PC 280 to the radiation source device 18 and the cassette 12, or electric power can be supplied between the radiation source device 18 and the cassette 12 via the PC 280, the PC 280 can perform a centralized electric power management process for efficiently supplying electric power between the radiation source device 18 and the cassette 12. Inasmuch as electric power can be collected from one or more radiation source devices 18 and

one or more cassettes **12** into the PC **280**, the PC **280** can perform a battery function that enables efficient electric power management, so as to avoid power supply problems such as sudden power supply interruptions at times when electric power needs to be supplied to the radiation source device **18** and the cassette **12**.

Although certain preferred embodiments of the present invention have been shown and described in detail, it should be understood that various changes and modifications may be made to the embodiments without departing from the scope of the invention as set forth in the appended claims.

For example, the radiation detector **86** may be a radiation detector **600** according to a modified example shown in FIGS. **45** and **46**. FIG. **45** is a cross-sectional view schematically illustrating the structure of three pixel units of the radiation detector **600** according to a modified example of the invention.

The radiation detector **600** includes a signal output unit **604**, a sensor unit (photoelectric converter) **606**, and a scintillator **608** that are sequentially laminated on an insulating substrate **602**. The signal output unit **604** and the sensor unit **606** form a pixel unit. Plural pixel units are arranged in a matrix on the substrate **602**, such as an array of pixel units arranged in rows and columns. In each pixel unit, the signal output unit **604** and the sensor unit **606** are arranged so as to overlap each other.

The scintillator **608** is formed on the sensor unit **606** with a transparent insulating film **610** interposed therebetween, and has a phosphor film that converts radiation **46** incident from the upper side (the side opposite to the substrate **602**) into light and emits the light. It is preferable that the wavelength range of light emitted by the scintillator **608** be a visible light range (wavelength of 360 nm to 830 nm). It is more preferable that the wavelength range of light include a green wavelength range in order to capture a monochromatic image using the radiation detector **600**.

Specifically, in a case in which imaging is performed using X-rays as radiation **46**, it is preferable that the phosphor used for the scintillator **608** include cesium iodide (CsI). It is more preferable to use CsI(Tl) (thallium-added cesium iodide) having an emission spectrum of 420 nm to 700 nm during the emission of X-rays. The emission peak wavelength of CsI(Tl) in the visible light range is 565 nm.

The scintillator **608**, for example, may be formed on a vapor deposition substrate by vapor deposition of a columnar crystal of CsI(Tl). As such, in a case in which the scintillator **608** is formed by vapor deposition, an Al plate is generally used as the vapor deposition substrate in terms of the transmittance of X-rays and manufacturing costs, but the vapor deposition substrate is not limited to the Al plate. In a case in which GOS is used as the scintillator **608**, GOS may be applied onto the surface of a TFT active matrix substrate to form the scintillator **608**, without using the vapor deposition substrate. Alternatively, after the scintillator **608** is formed by applying GOS to a resin base, the scintillator **608** may be attached to a TFT active matrix substrate. In this case, even if the application of GOS failed, the TFT active matrix substrate would not be damaged.

The sensor unit **606** includes an upper electrode **612**, a lower electrode **614**, and a photoelectric conversion film **616** provided between the upper and lower electrodes **612**, **614**.

The upper electrode **612** needs to make light generated by the scintillator **608** incident on the photoelectric conversion film **616**. Therefore, it is preferable that the upper electrode **612** be made of a conductive material that is at least transparent with respect to the emission wavelength of the scintillator **608**. Specifically, it is preferable that the upper electrode **612**

be made of a transparent conducting oxide (TCO) having high transmittance with respect to visible light and a small resistance value. A metal thin film, such as an Au thin film, may be used as the upper electrode **612**. However, when the transmittance increases to 90% or more, the resistance value is likely to increase. Therefore, it is preferable that the upper electrode **612** be made of TCO. For example, it is preferable that the upper electrode **612** be made of ITO, IZO, AZO, FTO, SnO<sub>2</sub>, TiO<sub>2</sub>, ZnO<sub>2</sub>, etc. It is most preferable that the upper electrode **612** be made of ITO in terms of a simple process, low resistance, and transparency. One upper electrode **612** may be common to all pixel units, or the upper electrode **612** may be divided for each pixel unit.

The photoelectric conversion film **616** includes an organic photoconductor (OPC) and absorbs light emitted from the scintillator **608** and generates a charge corresponding to the absorbed light. When the photoelectric conversion film **616** includes an organic photoconductor (an organic photoelectric conversion material), it has a narrow absorption spectrum in the visible light range and absorbs little electromagnetic waves other than the light emitted from the scintillator **608**. Therefore, it is possible to effectively reduce noise generated due to the absorption of radiation **46** by the photoelectric conversion film **616**. For example, the photoelectric conversion film **616** may include amorphous silicon instead of an organic photoconductor. When the photoelectric conversion film **616** includes amorphous silicon, it has a wide absorption spectrum and can absorb light emitted from the scintillator **608** efficiently.

It is preferable that the absorption peak wavelength of the organic photoconductor forming the photoelectric conversion film **616** be close to the emission peak wavelength of the scintillator **608** in order to most effectively absorb light emitted from the scintillator **608**. It is ideal that the absorption peak wavelength of the organic photoconductor is equal to the emission peak wavelength of the scintillator **608**. However, when the difference between the absorption peak wavelength and the emission peak wavelength is small, it is possible to sufficiently absorb light emitted from the scintillator **608**. Specifically, the difference between the absorption peak wavelength of the organic photoconductor and the emission peak wavelength of the scintillator **608** with respect to the radiation **46** is preferably equal to or less than 10 nm and more preferably, equal to or less than 5 nm.

Examples of the organic photoconductor capable of satisfying the above-mentioned conditions include a quinacridone-based organic compound and a phthalocyanine-based organic compound. For example, the absorption peak wavelength of quinacridone in the visible light range is 560 nm. Therefore, when quinacridone is used as the organic photoconductor and CsI(Tl) is used as the material forming the scintillator **608**, it is possible to reduce the difference between the peak wavelengths to 5 nm or less and substantially maximize the amount of charge generated by the photoelectric conversion film **616**.

The sensor unit **606** includes an organic layer that is formed by laminating or mixing, for example, an electromagnetic wave absorption portion, a photoelectric conversion portion, an electron transport portion, a hole transport portion, an electron blocking portion, a hole blocking portion, a crystallization prevention portion, an electrode, and an interlayer contact improvement portion. It is preferable that the organic layer include an organic p-type compound (organic p-type semiconductor) or an organic n-type compound (organic n-type semiconductor).

The organic p-type semiconductor is a donor-type organic semiconductor (compound) whose representative example is

a hole-transport-type organic compound and means an organic compound which readily donates electrons. Specifically, in a case in which two organic materials are in contact with each other during use, one organic compound with low ionization potential is the organic p-type semiconductor. Therefore, any organic compound may be used as the donor-type organic compound as long as it has an electron donating property.

The organic n-type semiconductor is an acceptor-type organic semiconductor (compound) whose representative example is an electron-transport-type organic compound and means an organic compound which readily accepts electrons. Specifically, in a case in which two organic compounds are in contact with each other during use, one organic compound with high electron affinity is the organic n-type semiconductor. Therefore, any organic compound may be used as the acceptor-type organic compound as long as it has an electron accepting property.

Materials applicable to the organic p-type semiconductor and the organic n-type semiconductor and the structure of the photoelectric conversion film **616** have been described in detail in Japanese Laid-Open Patent Publication No. 2009-032854 and thus a detailed description thereof will be omitted. The photoelectric conversion film **616** may include fullerene or carbon nanotubes.

It is preferable that the thickness of the photoelectric conversion film **616** be as large as possible in terms of the absorption of light from the scintillator **608**. However, when the thickness of the photoelectric conversion film **616** is greater than a predetermined value, the intensity of the electric field of the photoelectric conversion film **616** generated by the bias voltage applied from both ends of the photoelectric conversion film **616** is reduced, which makes it difficult to collect charge. Therefore, the thickness of the photoelectric conversion film **616** is preferably from 30 nm to 300 nm, more preferably from 50 nm to 250 nm, and most preferably from 80 nm to 200 nm.

One photoelectric conversion film **616** is common to all pixel units. However, the photoelectric conversion film **616** may be divided for each pixel unit. The lower electrode **614** is a thin film that is divided for each pixel unit. However, one lower electrode **614** may be common to all pixel units. The lower electrode **614** may be appropriately made of a transparent or opaque conductive material, such as aluminum or silver. The thickness of the lower electrode **614** may be, for example, from 30 nm to 300 nm.

In the sensor unit **606**, a predetermined bias voltage can be applied between the upper electrode **612** and the lower electrode **614** to move one of the charges (a hole and an electron) generated from the photoelectric conversion film **616** to the upper electrode **612** and move the other charge to the lower electrode **614**. In the radiation detector **600** according to this modified example, a wiring line is connected to the upper electrode **612** and the bias voltage is applied to the upper electrode **612** through the wiring line. It is assumed that the polarity of the bias voltage is determined such that the electron generated in the photoelectric conversion film **616** is moved to the upper electrode **612** and the hole is moved to the lower electrode **614**. However, the polarity may be reversed.

The sensor unit **606** forming each pixel unit may include at least the lower electrode **614**, the photoelectric conversion film **616**, and the upper electrode **612**. In order to prevent an increase in dark current, it is preferable that at least one of electron blocking film **618** and hole blocking film **620** be provided, and it is more preferable that both the electron blocking film **618** and the hole blocking film **620** be provided.

The electron blocking film **618** may be provided between the lower electrode **614** and the photoelectric conversion film **616**. In a case in which the bias voltage is applied between the lower electrode **614** and the upper electrode **612**, it is possible to prevent an increase in the dark current due to the injection of electrons from the lower electrode **614** into the photoelectric conversion film **616**.

The electron blocking film **618** may be made of an electron donating organic material. In practice, the material used for the electron blocking film **618** may be selected according to a material forming an adjacent electrode and a material forming an adjacent photoelectric conversion film **616**. It is preferable that the material used for the electron blocking film **618** have an electron affinity (Ea) that is at least 1.3 eV higher than the work function (Wf) of the material forming the adjacent electrode and have an ionization potential (Ip) equal to or less than that of the material forming the adjacent photoelectric conversion film **616**. Materials applicable as the electron donating organic material have been described in detail in Japanese Laid-Open Patent Publication No. 2009-032854 and thus a detailed description thereof will be omitted.

The thickness of the electron blocking film **618** is preferably from 10 nm to 200 nm, more preferably from 30 nm to 150 nm, and most preferably from 50 nm to 100 nm in order to reliably obtain the effect of preventing the dark current and prevent a reduction in the photoelectric conversion efficiency of the sensor unit **606**.

The hole blocking film **620** may be provided between the photoelectric conversion film **616** and the upper electrode **612**. In a case in which the bias voltage is applied between the lower electrode **614** and the upper electrode **612**, it is possible to prevent an increase in the dark current due to the injection of holes from the upper electrode **612** into the photoelectric conversion film **616**.

The hole blocking film **620** may be made of an electron accepting organic material. The thickness of the hole blocking film **620** is preferably from 10 nm to 200 nm, more preferably from 30 nm to 150 nm, and most preferably from 50 nm to 100 nm in order to reliably obtain the effect of preventing the dark current and prevent a reduction in the photoelectric conversion efficiency of the sensor unit **606**.

In practice, the material used for the hole blocking film **620** may be selected according to a material forming an adjacent electrode and a material forming an adjacent photoelectric conversion film **616**. It is preferable that the material used for the hole blocking film **620** have an ionization potential (Ip) that is at least 1.3 eV higher than the work function (Wf) of the material forming the adjacent electrode and have an electron affinity (Ea) equal to or more than that of the material forming the adjacent photoelectric conversion film **616**. Materials applicable as the electron accepting organic material have been described in detail in Japanese Laid-Open Patent Publication No. 2009-032854 and thus a detailed description thereof will be omitted.

In a case in which the bias voltage is set such that, among the charges generated in the photoelectric conversion film **616**, holes are moved to the upper electrode **612** and electrons are moved to the lower electrode **614**, the positions of the electron blocking film **618** and the hole blocking film **620** may be reversed. In addition, it is not necessary to provide both the electron blocking film **618** and the hole blocking film **620**. When either the electron blocking film **618** or the hole blocking film **620** is provided, it is possible to a certain extent to obtain the effect of preventing the dark current.

As shown in FIG. **46**, the signal output unit **604** is provided on the surface of the substrate **602** so as to correspond to the lower electrode **614** of each pixel unit. The signal output unit

604 has a storage capacitor 622 that stores the charge moved to the lower electrode 614, and a TFT 624 that converts the charge stored in the storage capacitor 622 into an electric signal and outputs the electric signal. A region in which the storage capacitor 622 and the TFT 624 are formed has a portion that overlaps the lower electrode 614 in a plan view. In this way, the signal output unit 604 and the sensor unit 606 in each pixel unit overlap each other in the thickness direction. It is possible to minimize the plane area of the radiation detector 600 (pixel unit), when the signal output unit 604 is formed such that the storage capacitor 622 and the TFT 624 are completely covered with the lower electrode 614.

The storage capacitor 622 is electrically connected to the corresponding lower electrode 614 through a conductive line that is formed so as to pass through an insulating film 626 provided between the substrate 602 and the lower electrode 614. In this way, it is possible to move the charge captured by the lower electrode 614 to the storage capacitor 622.

The TFT 624 is formed by laminating a gate electrode 628, a gate insulating film 630, and an active layer (channel layer) 632 and providing a source electrode 634 and a drain electrode 636 on the active layer 632 with a predetermined gap therebetween. The active layer 632 may be made of, for example, amorphous silicon, an amorphous oxide, an organic semiconductor material, or carbon nanotubes. The material forming the active layer 632 is not limited thereto.

An oxide (for example, an In—O-based oxide) including at least one of In, Ga, and Zn is preferable as the amorphous oxide that can form the active layer 632. An oxide (for example, an In—Zn—O-based oxide, an In—Ga—O-based oxide, or a Ga—Zn—O-based oxide) including at least two of In, Ga, and Zn is more preferable as the amorphous oxide. An oxide including In, Ga, and Zn is most preferable as the amorphous oxide. As an In—Ga—Zn—O-based amorphous oxide, an amorphous oxide having a composition represented by  $\text{InGaO}_3(\text{ZnO})_m$  ( $m$  is a natural number smaller than 6) in a crystalline state is preferable, and  $\text{InGaZnO}_4$  is more preferable. The amorphous oxide that can form the active layer 632 is not limited thereto.

A phthalocyanine compound, pentacene, or vanadyl phthalocyanine may be given as an example of the organic semiconductor material that can form the active layer 632, but the organic semiconductor material is not limited thereto. The structure of the phthalocyanine compound has been described in detail in Japanese Laid-Open Patent Publication No. 2009-212389 and thus a detailed description thereof will be omitted.

When the active layer 632 of the TFT 624 is made of an amorphous oxide, an organic semiconductor material, or carbon nanotubes, radiation 46, such as X-rays, is not absorbed. Even if the radiation 46 is absorbed, the absorbed amount will be very small. Therefore, it is possible to effectively prevent the generation of noise in the signal output unit 604.

In a case in which the active layer 632 is made of carbon nanotubes, it is possible to improve the switching speed of the TFT 624 and form the TFT 624 with low light absorptance in the visible light range. In addition, in a case in which the active layer 632 is made of carbon nanotubes, even though a very small amount of metallic impurities is mixed with the active layer 632, the performance of the TFT 624 is significantly reduced. Therefore, it is necessary to separate and extract carbon nanotubes with very high purity using, for example, centrifugal separation and form the active layer 632 with the carbon nanotubes.

All of the amorphous oxide, the organic semiconductor material, the carbon nanotubes, and the organic photoconductor can be used to form a film at a low temperature. Thus, the

substrate 602 is not limited to a substrate with high heat resistance, such as a semiconductor substrate, a quartz substrate, or a glass substrate, but a flexible substrate, such as a plastic substrate, an aramid substrate, or a bio-nanofiber substrate may be used as the substrate 602. Specifically, for example, a flexible substrate made of the following materials may be used: polyester, such as polyethylene terephthalate, polybutylene phthalate, or polyethylene naphthalate, polystyrene, polycarbonate, polyether sulfone, polyarylate, polyimide, polycycloolefin, norbornene resin, and polychlorotrifluoroethylene. When such a flexible substrate made of plastic is used, it is possible to reduce the weight of the substrate. For example, this structure has an advantage in portability.

When the photoelectric conversion film 616 is formed of the organic photoconductor and the TFT 624 is formed of the organic semiconductor material, it is possible to form films of the photoelectric conversion film 616 and the TFT 624 at a low temperature with respect to a flexible substrate (substrate 602) of plastic. Also, it is possible to reduce the thickness and weight of the radiation detector 600 in its entirety, and thereby it is possible to reduce the thickness and weight of the cassette 12 housing the radiation detector 600. Accordingly, it is possible to improve convenience when used outside of a hospital. Further, a base material of the photoelectric conversion unit is made of a flexible material instead of glass that is commonly used. Thus, it is possible to enhance resistance to damage or the like when the radiographic image capturing apparatus is carried or used.

In addition, for example, an insulating layer for ensuring an insulating property, a gas barrier layer for preventing the penetration of water or oxygen, and an undercoating layer for improving flatness or the adhesion of, for example, the electrode may be provided on the substrate 602.

Since aramid can be applied to a high-temperature process of 200 degrees or more, a transparent electrode material can be cured at a high temperature to have low resistance, and the aramid can respond to the automatic mounting of a driver IC including a solder reflow process. In addition, the thermal expansion coefficient of aramid is close to that of ITO (indium tin oxide) or a glass substrate. Therefore, after an aramid substrate is manufactured, the warping of the aramid substrate is small and the aramid substrate is less likely to be cracked. In addition, aramid is capable of forming a substrate thinner than, for example, a glass substrate. Aramid may be laminated on a super-thin glass substrate to form the substrate 602.

The bio-nanofiber is a composite of a cellulose microfibril bundle (bacterial cellulose) generated by bacteria (*Acetobacter*, *Acetobacter Xylinum*) and a transparent resin. The cellulose microfibril bundle has a width of 50 nm, a size of one-tenth of the visible light wavelength, high strength, high elasticity, and a low thermal expansion coefficient. A transparent resin, such as an acrylic resin or an epoxy resin, is impregnated into the bacterial cellulose and is then cured to obtain bio-nanofiber that has a light transmittance of about 90% at a wavelength of 500 nm while including 60 to 70% of fiber. The bio-nanofiber has a low thermal expansion coefficient (3 to 7 ppm) equal to that of a silicon crystal, strength (460 MPa) similar to that of steel, high elasticity (30 GPa), and flexibility. Therefore, the bio-nanofiber is capable of forming a substrate 602 thinner than, for example, a glass substrate.

In this example, the signal output unit 604, the sensor unit 606, and the transparent insulating film 610 are sequentially formed on the substrate 602 and the scintillator 608 is bonded to the substrate 602 by an adhesive resin with low light absorptance, thereby forming the radiation detector 600.

In the radiation detector **600** according to the modified example, since the photoelectric conversion film **616** is made of an organic photoconductor and the active layer **632** of the TFT **624** is made of the organic semiconductor material, radiation **46** is hardly absorbed by the photoelectric conversion film **616** or the signal output unit **604**. Therefore, it is possible to prevent a reduction in sensitivity for the radiation **46**.

Both the organic semiconductor material forming the active layer **632** of the TFT **624** and the organic photoconductor forming the photoelectric conversion film **616** can be used to form a film at a low temperature. Therefore, the substrate **602** can be made of a plastic resin, aramid, or bio-nanofiber that absorbs a small amount of radiation **46**. Accordingly, it is possible to prevent a reduction in sensitivity for the radiation **46**.

For example, in a case in which the radiation detector **600** is adhered to the irradiated surface **20** of the housing and the substrate **602** is made of a plastic resin with high rigidity, aramid, or bio-nanofiber, it is possible to reduce the thickness of the irradiated surface **20** of the housing since the radiation detector **600** has high rigidity. In addition, in a case in which the substrate **602** is made of a plastic resin, aramid, or bio-nanofiber having high rigidity, the radiation detector **600** has flexibility. In case the substrate **602** is made of a plastic resin, aramid, or bio-nanofiber having high rigidity, even when an impact is applied to the irradiated surface **20**, the radiation detector **600** is less likely to be damaged due to its flexibility.

The radiation detector **600** according to the modified example is a so-called rear surface reading type (so-called PSS (Penetration Side Sampling) type) in which the light emitted from the scintillator **608** is converted by the sensor unit **606** (photoelectric conversion film **616**) into the electric charge for reading the radiographic image, while the sensor unit **606** is positioned on the side opposite to the radiation source **44**. The type of the radiation detector, however, is not limited thereto.

For example, a radiation detector may be a so-called front surface reading type (so-called ISS (Irradiation Side Sampling) type). In this case, the insulating substrate **602**, the signal output unit **604**, the sensor unit **606**, and the scintillator **608** are successively laminated along an irradiation direction of the radiation **46**. The light emitted from the scintillator **608** is converted by the sensor unit **606** into the electric charge for reading the radiographic image, while the sensor unit **606** is positioned on the same side as the radiation source **44**. Usually, the scintillator **608** emits light having higher intensity on a radiation-irradiated side by the radiation **46** than a back side. Therefore, in the radiation detector of the front surface reading type, the distance from the scintillator **608** to the photoelectric conversion film **616**, by which emitted light travels, can be shorter than in the radiation detector **600** of the rear surface reading type. Thus, it is possible to reduce the diffusion or attenuation of the light. As a result, the resolution of the radiographic image can be higher.

What is claimed is:

1. A portable radiographic image capturing apparatus comprising:

a radiation source device including an electric power storage unit and a radiation source for outputting radiation; and

a detector device including an electric power storage unit and a radiation detector for detecting radiation that is transmitted through a subject when the subject is irradiated with radiation by the radiation source, and converting the detected radiation into a radiographic image,

at least one of the radiation source device and the detector device having an electric power supply limiting unit for limiting supply of electric power,

the electric power supply limiting unit including:

an electric power controller that controls supply of electric power between the electric power storage unit of the radiation source device and the electric power storage unit of the detector device; and

an electric power supply limiter that limits supply of electric power between the electric power storage unit of the radiation source device and the electric power storage unit of the detector device, depending on timing of an image capturing process,

wherein the electric power controller supplies electric power only along a route from the electric power storage unit of the detector device to the electric power storage unit of the radiation source device, based on the electric power supply request made before the image capturing process.

2. The portable radiographic image capturing apparatus according to claim 1, wherein at least one of the electric power storage unit of the radiation source device and the electric power storage unit of the detector device is a capacitor.

3. The portable radiographic image capturing apparatus according to claim 1, wherein the electric power supply limiting unit further comprises a pause processor that temporarily stops supply of electric power between the electric power storage unit of the radiation source device and the electric power storage unit of the detector device from a start of the image capturing process after electric power has been supplied and until an electric power supply request is given before a next image capturing process.

4. The portable radiographic image capturing apparatus according to claim 1, wherein the electric power controller of the electric power supply limiting unit comprises an electric power manager for managing electric power required to capture a given number of radiographic images,

wherein the electric power manager supplies electric power from one of the radiation source device and the detector device, which has excessive electric power with respect to the required electric power, to the other of the radiation source device and the detector device, which has insufficient electric power with respect to the required electric power, up to the required electric power.

5. The portable radiographic image capturing apparatus according to claim 1, wherein the electric power supply limiter of the electric power supply limiting unit limits supply of the electric power between the electric power storage unit of the radiation source device and the electric power storage unit of the detector device, during a period in which the radiographic image is being captured based on the radiation.

6. The portable radiographic image capturing apparatus according to claim 1, wherein the electric power supply limiting unit further comprises a pause processor that temporarily stops supply of electric power between the electric power storage unit of the radiation source device and the electric power storage unit of the detector device after electric power has been supplied and until a next image capturing process is completed.

7. The portable radiographic image capturing apparatus according to claim 1, wherein the limitation of the supply of electric power by the electric power supply limiter is to deactivate supply of electric power by the electric power controller

## 61

between the electric power storage unit of the radiation source device and the electric power storage unit of the detector device.

8. The portable radiographic image capturing apparatus according to claim 1, wherein the limitation of the supply of electric power by the electric power supply limiter is to reduce an amount of electric power supplied per unit time by the electric power controller between the electric power storage unit of the radiation source device and the electric power storage unit of the detector device.

9. The portable radiographic image capturing apparatus according to claim 1, wherein the limitation of the supply of electric power by the electric power supply limiter is to control supply of electric power in a stepwise manner by the electric power controller between the electric power storage unit of the radiation source device and the electric power storage unit of the detector device.

10. The portable radiographic image capturing apparatus according to claim 1, wherein the electric power controller supplies electric power only along a route from the electric power storage unit of the radiation source device to the electric power storage unit of the detector device, based on an electric power supply request.

11. The portable radiographic image capturing apparatus according to claim 1, the radiation detector comprising:

a scintillator;

a photoelectric converter for absorbing light converted by the scintillator and generating a charge corresponding to the absorbed light; and

a signal output unit for outputting an electric signal that corresponds to radiographic image information, for the charge generated by the photoelectric converter,

wherein the photoelectric converter includes an organic photoconductor, and

the signal output unit includes a channel layer that comprises an organic semiconductor material.

12. A portable radiographic image capturing apparatus comprising:

a radiation source device including:

an electric power storage unit; and

a radiation source for outputting radiation; and

a detector device including:

an electric power storage unit; and

a radiation detector for detecting radiation that is transmitted through a subject when the subject is irradiated with radiation by the radiation source, and converting the detected radiation into a radiographic image,

wherein at least one of the radiation source device and the detector device has an electric power supply limiting unit for limiting supply of electric power,

the electric power supply limiting unit including:

an electric power controller that controls supply of electric power between the electric power storage unit of the radiation source device and the electric power storage unit of the detector device; and

an electric power supply limiter that limits supply of electric power between the electric power storage unit of the radiation source device and the electric power storage unit of the detector device, depending on timing of an image capturing process,

wherein the electric power controller of the electric power supply limiting unit supplies electric power only along a route from the electric power storage unit of the detector device to the electric power storage unit of the radiation source device, upon completion of the image capturing process.

## 62

13. The portable radiographic image capturing apparatus according to claim 12, wherein the electric power controller of the electric power supply limiting unit comprises an electric power manager for managing electric power required to capture a given number of radiographic images, and

wherein the electric power manager supplies electric power from one of the radiation source device and the detector device, which has excessive electric power with respect to the required electric power, to the other of the radiation source device and the detector device, which has insufficient electric power with respect to the required electric power, up to the required electric power.

14. The portable radiographic image capturing apparatus according to claim 12, wherein the electric power supply limiter of the electric power supply limiting unit limits supply of the electric power between the radiation source device and the detector device, during a period in which the radiographic image is being captured based on the radiation.

15. A portable radiographic image capturing apparatus comprising:

a radiation source device including:

an electric power storage unit; and

a radiation source for outputting radiation; and

a detector device including:

an electric power storage unit; and

a radiation detector for detecting radiation that is transmitted through a subject when the subject is irradiated with radiation by the radiation source, and converting the detected radiation into a radiographic image,

wherein at least one of the radiation source device and the detector device has an electric power supply limiting unit for limiting supply of electric power,

the electric power supply limiting unit including:

an electric power controller that controls supply of electric power between the electric power storage unit of the radiation source device and the electric power storage unit of the detector device; and

an electric power supply limiter that limits supply of electric power between the electric power storage unit of the radiation source device and the electric power storage unit of the detector device, depending on timing of an image capturing process,

wherein the electric power controller supplies electric power only along a route from the electric power storage unit of the detector device to the electric power storage unit of the radiation source device, based on an electric power supply request.

16. A radiographic image capturing system comprising:

a radiation source device including an electric power storage unit and a radiation source for outputting radiation;

a detector device including an electric power storage unit and a radiation detector for detecting radiation that is transmitted through a subject when the subject is irradiated with radiation by the radiation source, and converting the detected radiation into a radiographic image; and an electric power supply limiting unit,

wherein the electric power supply limiting unit includes:

an electric power controller that controls supply of electric power between the electric power storage unit of the radiation source device and the electric power storage unit of the detector device; and

an electric power supply limiter that limits supply of electric power between the electric power storage unit of the radiation source device and the electric power storage unit of the detector device, depending on timing of an image capturing process,

wherein the electric power controller supplies electric power only along a route from the electric power storage unit of the detector device to the electric power storage unit of the radiation source device, based on the electric power supply request made before the image capturing process. 5

17. The radiographic image capturing system according to claim 16, wherein the electric power controller of the electric power supply limiting unit supplies electric power between the electric power storage unit of the radiation source device and the electric power storage unit of the detector device, upon completion of the image capturing process. 10

\* \* \* \* \*