

**(12) STANDARD PATENT**  
**(19) AUSTRALIAN PATENT OFFICE**

(11) Application No. **AU 2004200548 B2**

(54) Title  
**Capsule magazine unit having a holding device for the capsule magazine unit, in particular of an espresso machine**

(51) International Patent Classification(s)  
**A47J 31/44** (2006.01) **A47J 31/36** (2006.01)  
**A47F 1/08** (2006.01) **A47J 31/40** (2006.01)  
**A47J 31/00** (2006.01)

(21) Application No: **2004200548** (22) Date of Filing: **2004.02.10**

(30) Priority Data

(31) Number (32) Date (33) Country  
**20302410.9** **2003.02.13** **DE**

(43) Publication Date: **2004.09.02**

(43) Publication Journal Date: **2004.09.02**

(44) Accepted Journal Date: **2009.09.24**

(71) Applicant(s)  
**Nestec S.A.**

(72) Inventor(s)  
**Fischer, Daniel**

(74) Agent / Attorney  
**Shelston IP, 60 Margaret Street, Sydney, NSW, 2000**

(56) Related Art  
**US6240832**  
**DE20121494**

Abstract:

5        Capsule magazine unit having a holding device for  
capsule magazine unit, into which the capsule  
magazine unit (1) can be releasably inserted, in  
particular of an espresso machine, the capsule  
magazine unit (1) comprising at least one  
essentially vertical capsule magazine tube  
(2 to 7) which is suitable for holding coffee  
10       capsules (12 to 14) stacked one above another and  
has a lateral capsule removal opening (8) at the  
bottom, characterized by a locking ring (15) which  
is arranged around the capsule magazine unit (1)  
and can be displaced essentially vertically with  
15       respect to the capsule magazine unit (1), and by  
at least one locking-ring lifting element (16,  
16a) on the holding device (9) for the capsule  
magazine unit, the said lifting element being  
suitable for acting on the locking ring (15).

Fig.1




Fig.2





Fig.3



# AUSTRALIA

-----  
PATENTS ACT 1990  
-----

## COMPLETE SPECIFICATION

FOR A STANDARD PATENT

### ORIGINAL

---

Name of Applicant/s: Nestec S.A.

Actual Inventor/s: Daniel Fischer

Address for Service: **Baldwin Shelston Waters**  
60 MARGARET STREET  
SYDNEY NSW 2000

CCN: 3710000352

Invention Title: CAPSULE MAGAZINE UNIT HAVING A HOLDING DEVICE FOR  
THE CAPSULE MAGAZINE UNIT, IN PARTICULAR OF AN  
ESPRESSO MACHINE

The following statement is a full description of this invention, including the best method of performing it known to me/us:-

File: 41669AUP00

**CAPSULE MAGAZINE UNIT HAVING A HOLDING DEVICE FOR  
THE CAPSULE MAGAZINE UNIT, IN PARTICULAR OF AN  
ESPRESSO MACHINE**

**5 DESCRIPTION**

The invention relates to a capsule magazine unit having a holding device for the capsule magazine unit, into which the capsule magazine unit can be releasably inserted, in particular of an espresso machine.

- 10 Any discussion of the prior art throughout the specification should in no way be considered as an admission that such prior art is widely known or forms part of common general knowledge in the field.

**BACKGROUND OF THE INVENTION**

- 15 Capsule magazine units of this type are already known, for instance in DE 200 159 03 U1, in order to keep capsules having the substance which is to be prepared, in particular different types of espresso coffee, ready in an organized and easily selectable manner. Accordingly, a plurality of capsule magazine tubes can be arranged in the shape of a circular ring or else in a linear row as the capsule
- 20 magazine unit. The capsule magazine unit is preferably a releasable part of an espresso machine, but may also be formed separately from the latter. The capsule magazine unit can be removed from the holding device for the capsule magazine unit for convenient fitting with the different coffee capsules and can then be re-inserted into it. Each capsule magazine tube which is part of the capsule magazine
- 25 unit has a lower capsule removal opening which is arranged laterally or radially outwards if the capsule magazine tubes are arranged in a circle. The lowermost capsule can be removed in each case manually from this capsule removal opening or - preferably if the holding device for the capsule magazine unit is integrated in an espresso machine - can be pushed out of the capsule removal opening by
- 30 mechanical means in order to convey it into a brewing position to prepare the espresso.

Although the capsule magazine units have made great progress in the simple and reliable preparation of drinks, in particular the preparation of espresso, it can be

perceived as being a drawback that, when the capsule magazine unit has been removed from the holding device for the capsule magazine unit, in particular of an espresso machine, the capsules may unintentionally slide out of the removal openings of the magazine tubes, in particular if the capsule magazine unit is tilted.

5

It is an object of the present invention to overcome or ameliorate at least one of the disadvantages of the prior art, or to provide a useful alternative.

### DISCLOSURE OF THE INVENTION

10 According to a first aspect of the present invention, there is provided a capsule magazine unit having a holding device for the capsule magazine unit, into which the capsule magazine unit can be releasably inserted, in particular of an espresso machine, the capsule magazine unit comprising at least one essentially vertical capsule magazine tube which is suitable for holding coffee capsules stacked one  
15 above another and has a lateral capsule removal opening at the bottom, wherein a locking ring which is arranged around the capsule magazine unit and can be displaced essentially vertically with respect to the capsule magazine unit, and by at least one locking-ring lifting element on the holding device for the capsule magazine unit, the said lifting element being suitable for acting on the locking ring.

20

Unless the context clearly requires otherwise, throughout the description and the claims, the words "comprise", "comprising", and the like are to be construed in an inclusive sense as opposed to an exclusive or exhaustive sense; that is to say, in the sense of "including, but not limited to".

25

According to another aspect of the present invention, there is provided a capsule magazine unit having a holding device for the capsule magazine unit, into which the capsule magazine unit can be releasably inserted, in particular of an espresso machine, the capsule magazine unit comprising at least one essentially vertical  
30 capsule magazine tube which is suitable for holding coffee capsules stacked one above another and has a lateral capsule removal opening at the bottom, wherein a locking ring which is arranged around the capsule magazine unit and can be displaced essentially vertically with respect to the capsule magazine unit and has at

least one locking-ring lifting element which protrudes outwards from the locking ring and is suitable for acting on the holding device for the capsule magazine unit.

Advantageously, the present invention at least in a preferred form provides a capsule magazine unit of the generic type mentioned at the beginning with the effect that the sliding of capsules out of the capsule magazine tubes of the capsule magazine unit which has been removed from the holding device for the capsule magazine unit is reliably avoided without complicating the handling. The technical means in order to achieve this are to be uncomplicated in terms of design.

In both variants of the invention, a locking ring is essential in order to prevent coffee capsules from falling out of the lateral capsule removal openings of the capsule magazine unit, the said locking ring, if the capsule magazine tubes are orientated vertically (as is customary), therefore likewise being displaceable vertically in the direction of these tubes. In a lower locking position, into which it automatically slides as a consequence of gravity if the capsule magazine unit has been removed from the holding device for the capsule magazine unit, the said locking ring covers the capsule removal openings of the capsule magazine tubes to an extent sufficient for them no longer to be able to fall out of the capsule removal opening. The essential means furthermore include at least one locking-ring lifting element which is designed in particular as a simple lug.

When the capsule magazine unit - as a rule filled with coffee capsules - is inserted into the holding device for the capsule magazine unit, the locking-ring lifting element causes the locking ring to be blocked relative to the sliding-down capsule magazine unit, which means that it reaches an upper release position in relation to the capsule removal opening, so that a lower capsule for preparing drinks can be removed in each case from the capsule removal opening.

Advantageously, special handling of the locking ring is therefore not required. On the contrary, its locking or retaining function for the separated capsule magazine unit occurs automatically, as does the release of the capsule removal openings

when the capsule magazine unit is introduced into the holding device for the capsule magazine unit.

5 Preferably, the shape of the locking ring is in principle as desired and is matched to the arrangement of the magazine tubes, so that their capsule removal openings can be essentially covered in the lower locking position of the locking ring and, on the other hand, the locking ring can be displaced along the capsule magazine tubes.

10 In the case of a particularly preferred, circular arrangement of the capsule magazine tubes, the locking ring is simply of circular-ring-shaped design. For guidance purposes during the vertical displacement with respect to the capsule magazine tubes, the said locking ring needs merely to rest linearly on the said tubes. The friction during displacement is therefore small.

15 Advantageously, the device is also uncomplicated because the locking-ring lifting element can be at least one simple, passive element which, in particular according to the preferred features of Claim 5, is a lug protruding inwards on the capsule magazine unit opening of the holding device for the capsule magazine unit. In the second variant according to Claim 2 and the preferred features of Claim 7, the  
20 locking-ring lifting element is integrated in the locking ring, for example as a lug which projects outwards from the locking ring or as an outer collar or by dimensioning the external diameter of the locking ring in relation to the capsule magazine unit opening in the holding device for the capsule magazine unit.

25 More specifically, the first variant of the capsule magazine unit according to the preferred features of Claim 5 has the features of the capsule magazine unit having a base on which the locking ring rests when the capsule magazine unit has been removed from the holding device for the capsule magazine unit, of at least one lug protruding essentially inwards into the holding device for the capsule magazine  
30 unit as the locking-ring lifting element on which the locking ring rests when the capsule magazine unit has been inserted into the holding device for the capsule magazine unit, and of the base of the capsule magazine unit having at least one outwardly open slot through which the lug of the holding device for the capsule

magazine unit can pass when the capsule magazine unit is pulled vertically out of the holding device for the capsule magazine unit. In this case, the base of the capsule magazine unit delimits the lower locking position into which the locking ring normally wants to move. In contrast, its release position is only reached if the

5 capsule magazine unit is inserted into the holding device for the capsule magazine unit and is lowered onto the lug. In this case, the locking ring is held above the capsule removal openings on the lug of the magazine holding device.

Although, in principle, one lug is sufficient for holding back and supporting the locking ring, the arrangement of at least two, preferably more lugs at a distance from one another is advantageous, so that the locking ring resting on them does not tilt. Co-ordinated with them, according to the preferred features of Claim 6, are a plurality of slots offset at a distance around the circumference of the base from the base of the capsule magazine unit, which base is round to give a circular

10 arrangement of a plurality of capsule magazine tubes, so that the base can be lowered past the lugs. In particular, the slots are arranged in the base in such a manner that, in every possible operational capsule removal position of the capsule magazine unit, the latter can be pulled out without rotation in the holding device for the capsule magazine unit, by corresponding slots being vertically aligned with

15 all of the lugs.

20

In contrast, in the second variant of the invention according to Claim 2 and the preferred features of Claim 7, slots in the base are not required and lugs on the locking ring can be arranged freely along the outer circumference thereof without

25 obstructing the removal of the capsule magazine unit from the holding device for the capsule magazine unit.

In addition, in both variants, the capsule magazine unit according to the preferred features of Claim 8 can have, at a vertical distance above the capsule removal openings, an upper stop which upwardly secures the locking ring against sliding

30 out of the capsule magazine unit. The stop can comprise a circular-ring-shaped collar of the capsule magazine unit at a sufficient distance above the capsule removal openings.

## BRIEF DESCRIPTION OF THE DRAWINGS

A respective exemplary embodiment of both variants of the invention will be explained below with reference to a drawing having five figures, in which:

5

Figure 1 shows a side view of a capsule magazine unit of the first variant, which unit is designed as a rotary magazine;

10

Figure 2 shows the capsule magazine unit according to Figure 1, but when it is inserted into a holding device for the capsule magazine unit, as part of an espresso machine body;

Figure 3 shows a plan view of the capsule magazine unit when detached from the holding device for the capsule magazine unit according to Figure 1;

Figure 4 shows a capsule magazine unit of the second variant when inserted into the holding device for the capsule magazine unit, and

15

Figure 5 shows the capsule magazine unit according to Figure 4 when detached, in a plan view.

In both variants, corresponding features are provided with the same reference numbers.

20

## PREFERRED EMBODIMENTS OF THE INVENTION

The capsule magazine unit referred to in general by 1 in Figures 1 and 3 comprises six essentially cylindrical capsule magazine tubes which are vertical in the operational position and are fitted in a circular arrangement on a round base 23.

25

Each capsule magazine tube, e.g. 6, has a capsule removal opening, e.g. 8, at the bottom above the base 23, the said opening being directed radially outwards with respect to a main axis (not shown) of the capsule magazine unit, so that the respectively lowermost of the coffee capsules stacked in the capsule magazine tube can be pushed out of the capsule magazine tube 6 at the capsule removal opening 8. For this purpose, in the present exemplary embodiment, since the capsule magazine unit 1 can be inserted in the operational position into a holding device 9 for the capsule magazine unit as part of an espresso machine body 10, use

30

is made of mechanical means (not illustrated in the drawing) which automatically remove the coffee capsule from a capsule magazine tube, which is rotated into a removal position, and convey this coffee capsule to a brewing position.

5 In order to fill the capsule magazine unit with coffee capsules of certain types of espresso coffee, which capsules are sorted for the different capsule magazine tubes 2 to 7, the capsule magazine unit is removed preferably from the holding device 9 for the capsule magazine unit, or from the espresso machine body 10 in order to be filled away from it. For this purpose, the coffee capsules are introduced into  
10 insertion mechanisms, e.g. 11, formed at the top of the capsule magazine tubes, and are stacked in the capsule magazine tubes. The insertion mechanisms are matched for this purpose to the essentially truncated-cylinder shape of the coffee capsules, so that the coffee capsules can be stacked only in the desired orientation with the base downwards. The coffee capsules which can be seen in Figures 1 and  
15 2 are referred to by 12 to 14. The capsule magazine unit 1 is preferably filled with coffee capsules only to an extent such that it is not possible for any coffee capsule, such as here the coffee capsule 12, to slide laterally counter to the insertion direction out of the insertion mechanism.

20 In order to avoid an undesirable sliding of the lower coffee capsules, e.g. 12, 13, out of the capsule removal openings, e.g. 8, if the detached capsule magazine unit 1 is held at an inclination, a circular-ring-shaped, vertically displaceable locking ring 15 is provided around the capsule magazine unit. The internal diameter of the locking ring is of sufficient size that the locking ring bears in a  
25 slideable manner against outer surface lines of the capsule magazine tubes 2 to 7. It is therefore guided by the capsule magazine tubes 2 to 7. Particularly if the locking ring has a smaller vertical extent than the height of the capsule removal openings 8, additional guide means (which are not shown in the drawing) may be provided in the region of the capsule removal openings.

30

In the lower locking position of the locking ring 15, which position is illustrated in Figure 1 and may also be referred to as the retaining position since the coffee capsules, e.g. 13, 14, are held back in it against sliding out of the magazine tubes,

the locking ring 15 rests on the base 23 of the capsule magazine unit. Without further actuating means, it is able to slide downwards onto the base only by means of gravity.

- 5 Without special manual actuation, the locking ring 15 passes from the lower locking position into an upper release position with respect to the capsule removal openings 8 by the capsule magazine unit 1 simply being introduced correctly from above into the holding device 9 for the capsule magazine unit, as illustrated in Figure 2, in which the locking ring is in the release position. It is held in the release position by locking-ring lifting elements 16, 16a which are orientated inwards towards the vertical main axis (not illustrated) of the holding device 9 for the capsule magazine unit or of the capsule magazine unit 1 inserted therein. The locking-ring lifting elements are arranged at equal distances in the circumferential direction of an upper holding opening (not designated) of the holding device 9 for the capsule magazine unit and are therefore suitable for holding the locking ring 15 in an untilted manner.

- The arrangement of slots 17 to 22 on the edge of the base 23 is matched, according to Figure 3, to the configuration of the locking-ring lifting elements. In detail, the slots are shaped from the base in such a manner that they permit the base to pass by the locking-ring lifting elements, e.g. 15, 16, when the capsule magazine unit 1 is inserted into the holding device 9 for the capsule magazine unit or is removed therefrom, specifically by a simple vertical movement during removal from any possible operational capsule removal position or latching position of the capsule magazine unit.

- Not illustrated on the capsule magazine unit 1 is an upper stop which prevents the locking ring 15 from unintentionally sliding out upwards over the capsule magazine tubes 2 to 7, so that the locking ring cannot be lost.

30

In Figure 2, the base 23 of the capsule magazine unit 1 rests on a base support 24 in the espresso machine body 10, which support can be designed as a revolving

magazine drawer and as such is described, for example, in PCT/EP 02/03281 by the applicant.

5 The embodiment of the second variant according to Figures 4 and 5 is distinguished by the fact that the locking-ring lifting elements 26-29 protrude from the outer edge of the locking ring 25, specifically the four locking-ring lifting elements, which are designed as lugs, protrude here uniformly over the circumference without being allocated to a capsule removal position or latching position of the capsule magazine unit 1a.

10

Its base 23a does not have to be outwardly slit here, since the removal of the capsule magazine unit cannot be obstructed by the locking-ring lifting elements 26-29. The latter rest, in Fig. 4, on the edge of the capsule magazine removal opening (not designated) and, during removal of the capsule magazine unit 1a, are  
15 lifted together with the locking ring 23a by means of the base 23a coming into contact with them.

**REFERENCE NUMBERS**

|    |         |                                                       |
|----|---------|-------------------------------------------------------|
|    | 1, 1a   | capsule magazine unit                                 |
| 5  | 2-7     | capsule magazine tube                                 |
|    | 8       | capsule removal opening                               |
|    | 9, 9a   | holding device for the capsule magazine unit          |
|    | 10      | espresso machine body                                 |
|    | 11      | capsule-magazine insertion mechanism                  |
| 10 | 12-14   | coffee capsule                                        |
|    | 15      | locking ring (first embodiment)                       |
|    | 16, 16a | locking-ring lifting element (lug, first embodiment)  |
|    | 17      | slot                                                  |
|    | 18      | slot                                                  |
| 15 | 19      | slot                                                  |
|    | 20      | slot                                                  |
|    | 21      | slot                                                  |
|    | 22      | slot                                                  |
|    | 23, 23a | base                                                  |
| 20 | 24      | base support                                          |
|    | 25      | locking ring (second embodiment)                      |
|    | 26      | locking-ring lifting element (lug, second embodiment) |
|    | 27      | locking-ring lifting element (lug, second embodiment) |
|    | 28      | locking-ring lifting element (lug, second embodiment) |
| 25 | 29      | locking-ring lifting element (lug, second embodiment) |

**THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:-**

1. A capsule magazine unit having a holding device for the capsule magazine unit, into which the capsule magazine unit can be releasably inserted, in particular  
5 of an espresso machine, the capsule magazine unit comprising at least one essentially vertical capsule magazine tube which is suitable for holding coffee capsules stacked one above another and has a lateral capsule removal opening at the bottom, wherein a locking ring which is arranged around the capsule magazine unit and can be displaced essentially vertically with respect to the capsule  
10 magazine unit, and by at least one locking-ring lifting element on the holding device for the capsule magazine unit, the said lifting element being suitable for acting on the locking ring.
2. A capsule magazine unit having a holding device for the capsule magazine  
15 unit, into which the capsule magazine unit can be releasably inserted, in particular of an espresso machine, the capsule magazine unit comprising at least one essentially vertical capsule magazine tube which is suitable for holding coffee capsules stacked one above another and has a lateral capsule removal opening at the bottom, wherein a locking ring which is arranged around the capsule magazine  
20 unit and can be displaced essentially vertically with respect to the capsule magazine unit and has at least one locking-ring lifting element which protrudes outwards from the locking ring and is suitable for acting on the holding device for the capsule magazine unit.
- 25 3. A capsule magazine unit according to Claim 1 or 2, wherein the locking ring can be displaced with respect to the capsule magazine unit in such a manner that, when the capsule magazine unit has been removed from the holding device for the capsule magazine unit, the said locking ring essentially covers the capsule removal opening in a lower locking position, and, when the capsule magazine unit  
30 has been inserted into the holding device for the capsule magazine unit, the said locking ring is held in an upper release position by the locking-ring lifting element, so that the capsule removal opening is released.

4. A capsule magazine unit according to at least one of Claims 1 to 3, wherein a circular arrangement of a plurality of capsule magazine tubes, the capsule removal openings of which are open radially outwards with respect to the arrangement, and by an essentially circular-ring-shaped locking ring which  
5 surrounds the arrangement and can be displaced.

5. A capsule magazine unit according to at least one of the preceding claims, wherein the capsule magazine unit has a base on which the locking ring rests when the capsule magazine unit has been removed from the holding device for the capsule magazine unit, in that at least one lug protrudes inwards into a capsule magazine unit opening of the holding device for the capsule magazine unit as the locking-ring lifting element on which the locking ring rests when the capsule magazine unit has been inserted into the holding device for the capsule magazine unit, and in that the base of the capsule magazine unit has at least one outwardly  
10 open slot through which the lug of the holding device for the capsule magazine unit can pass when the capsule magazine unit is pulled out of the holding device for the capsule magazine unit.

6. A capsule magazine unit according to Claim 5, wherein the base of the capsule magazine unit is round, in that it has a plurality of slots offset at a distance around the circumference of the base, and in that the holding device for the capsule magazine unit has at least two, preferably more, lugs which protrude inwards at a mutual distance and to which the arrangement of the slots in the base is matched.

7. A capsule magazine unit according to at least one of Claims 2 to 4, wherein the capsule magazine unit has a base on which the locking ring rests when the capsule magazine unit has been removed from the holding device for the capsule magazine unit, in that a capsule magazine unit opening of the holding device for the capsule magazine unit is dimensioned to be just large enough for at least the  
25 locking-ring lifting element to rest on the capsule magazine unit opening when the capsule magazine unit has been inserted into the holding device for the capsule magazine unit.

8. A capsule magazine unit according to at least one of the preceding claims, wherein it has, at a vertical distance above the capsule removal openings, an upper stop which secures the locking ring against sliding out of the capsule magazine unit.

5

9. A capsule magazine unit substantially as herein described with reference to any one of the embodiments of the invention illustrated in the accompanying drawings and/or examples.

Fig.1




Fig.2





Fig.3



**Fig. 4**




Fig. 5

