



(51) International Patent Classification:

F28D 21/00 (2006.01) F28D 9/00 (2006.01)

B01D 61/36 (2006.01) F28F 9/00 (2006.01)

B01D 63/08 (2006.01) F28F 9/007 (2006.01)

(21) International Application Number:

PCT/CA2022/051019

(22) International Filing Date:

24 June 2022 (24.06.2022)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

63/215,302 25 June 2021 (25.06.2021) US

(71) Applicant: NORTEK AIR SOLUTIONS CANADA, INC. [CA/CA]; 1502D QUEBEC AVENUE, SASKATOON, Saskatchewan S7K 1V7 (CA).

(72) Inventors: LEPOUDRE, Philip Paul; 153 MOUNT ALISON CRESCENT, SASKATOON, Saskatchewan S7H 4A4 (CA). NIROOMAND, Shirin; 1502D QUEBEC AV-

ENUE, SASKATOON, Saskatchewan S7K 1V7 (CA). CUI, Zheng; 1502D QUEBEC AVENUE, SASKATOON, Saskatchewan S7K 1V7 (CA).

(74) Agent: SMART & BIGGAR LLP; P.O. Box 2999, Station D., 900-55 Metcalfe Street, Ottawa, Ontario K1P 5Y6 (CA).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IQ, IR, IS, IT, JM, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ,

(54) Title: MEMBRANE ASSEMBLY FOR MEMBRANE ENERGY EXCHANGER




FIG. 1A

(57) Abstract: A membrane assembly includes a membrane film, and a plurality of tensile support members. The membrane film is configured to transfer heat and moisture between a liquid and air flowing through a LAMEE. The tensile support members are connected to the membrane or a substrate connected to the membrane. And, the tensile support members are in spaced relation to one another and oriented perpendicular to a direction of flow of liquid through the LAMEE.

UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

- *with international search report (Art. 21(3))*
- *in black and white; the international application as filed contained color or greyscale and is available for download from PATENTSCOPE*

MEMBRANE ASSEMBLY FOR MEMBRANE ENERGY EXCHANGER

5

CLAIM OF PRIORITY

[0001] This application claims priority to US Provisional Application Serial No. 63/215,302, filed on Jun 25, 2021, which is incorporated by reference herein its entirety, and the benefit of priority is claimed herein.

10

BACKGROUND

[0002] A liquid to air membrane energy exchanger (LAMEE) can transfer heat and/or moisture between a flow of liquid and an air stream to condition the temperature and/or humidity of the air or liquid flowing through the LAMEE. LAMEEs can be used in a variety of applications, for example, Heating Ventilation and Air Conditioning (HVAC) systems, dehumidification systems, evaporative cooling, industrial applications requiring treated air, energy recovery systems, and other systems for conditioning a fluid flowing through the LAMEE and/or for conditioning environmental conditions in an enclosed space. LAMEEs include membrane assemblies, each of which separates adjacent liquid and air channels and via which energy is exchanged between the liquid and the air in the exchanger.

SUMMARY

[0001] Examples according to this disclosure are directed to membrane assemblies, which may be employed in a variety of membrane exchangers, including, for example, LAMEEs. For example, a membrane assembly includes a membrane film, a substrate, and a plurality of tensile support members. Also, the membrane assembly can include a membrane film directly adhered to the plurality of tensile support members and without the substrate therebetween. The membrane film is configured to transfer heat and moisture between a liquid and air flowing through a LAMEE. The substrate can be connected to the membrane film. The tensile support members can be connected to the substrate or directly to the membrane film. And, the tensile support members are spaced in relation to one another and oriented perpendicular to a direction of flow of liquid through the LAMEE.

[0002] A LAMEE can include a series of alternating liquid and air channels separated by a membrane assembly including a membrane that is configured to

allow fluid vapor/molecules to pass through the membrane and prevent liquids or solids from passing through the membrane. In this manner, a LAMEE can exchange heat (sensible energy) and moisture (latent energy) between a liquid and air flowing through the exchanger. Typically, the pressure of the liquid through such liquid channels is higher than that of the air pressure flowing through the adjacent air channel(s). As such, the flexible membranes of the membrane assemblies can tend to bow or bulge into the airflow channel. Such membrane bulging can restrict airflow through the airflow channel and can degrade the capacity of the system to condition the air, the fluid, or both.

5 [0003] In some past LAMEE designs, to counteract membrane bulging, a support structure is arranged in the air channels between membranes. Additionally, in some previous LAMEE designs, a rigid woven mesh is included in the membrane assembly to provide additional structural support. However, a number of challenges with membrane assemblies having such a rigid mesh supporting the membrane film have been discovered.

15 [0004] The mesh can impede breathability of the membrane assembly as a whole and can reduce the surface area of the film available for heat and mass transfer by the air and liquid traveling through the exchanger including the membrane assembly. Further, the need to reinforce a membrane film and substrate laminate with a rigid mesh can increase the cost, complexity, and time to manufacture the membrane assembly. In cases in which the reinforcement mesh is a polymer, the membrane assembly can slowly move or deform permanently under the influence of persistent mechanical stresses due to degradation of the polymer. Such material creep can inhibit the longevity of the LAMEE (or other exchanger) within a conditioning system. Yet another challenge to the use of such rigid mesh supports can be the inadvertent creation of additional heat and mass transfer resistance or air side pressure drop across the LAMEE. The present inventors have recognized, among other things, that an unintrusive membrane assembly which is configured to carry the load of/oppose a force applied by liquid pressure of the liquid channel can be used to enhance the efficiency and conditioning capacity of LAMEEs or other membrane exchangers.

25 [0005] Examples according to this disclosure are directed to membrane assemblies, which include a membrane film that is configured to allow materials in a gas phase to pass through the membrane and to prevent materials in a liquid or solid phase from passing through the membrane. Example membrane assemblies also include a plurality of tensile support members, which are configured to carry the load

of/oppose the force/pressure of liquid flowing through liquid channels bounded by a pair of the membrane assemblies. In examples, the tensile support members can be elongated filaments spanning across the membrane film in spaced relation to one another and oriented perpendicular to the direction of air and liquid flow through the exchanger in which the membrane assembly is employed. Membrane assemblies in accordance with this disclosure can be employed in a variety of applications, including, for example, in a LAMEE.

[0006] For instance, a fluid conditioning system can include use of a LAMEE having a membrane assembly in accordance with this disclosure. In one example, several membrane assemblies can be arranged to separate a series of alternating liquid and air channels. Each membrane assembly can include or use a membrane film. The membrane film can be a semi-permeable or vapor permeable film, by which generally anything in a gas phase can pass through the membrane and anything in a liquid or solid phase cannot pass through the membrane. The membrane film can also include a micro-porous membrane that is similarly configured to allow gases but not liquids or solids to pass through the membrane. Additionally, the membrane film employed in membrane assemblies in accordance with this disclosure can be a non-porous film having selective permeability for, e.g., water vapor/molecules, but not for other constituents in vapor/gas form/state/phase.

[0007] Generally, the membrane film can be relatively thin and fragile. The film can therefore be coupled to a substrate to provide a baseline of support to the membrane film for transport and processing the membrane film into finished membrane assemblies. The substrate can further include or use or be attached to a plurality of tensile support members. The tensile members can be oriented perpendicular to a direction of flow of liquid through the liquid channel including the membrane assembly to inhibit or eliminate bulging of the membrane assembly into the air channel.

[0008] For example, in a LAMEE or other membrane exchanger in which liquid flows horizontally through the exchanger, the tensile members can be arranged vertically and spaced/offset from one another to provide adequate directional support while still allowing for substantial surface area of the membrane film to be exposed to the liquid and air that it separates. The tensile members can be coupled to a frame and/or struts, e.g., in the liquid and air flow channels, to transfer force from the liquid pressure through the tensile members to the frame and/or struts.

[0009] The present inventors have recognized, among other things, that such a membrane assembly can provide suitable strength and longevity while also enabling

sufficient contact of the liquid and air with the membrane film, which can enhance the ability of the LAMEE to efficiently exchange energy between fluid and air over longer periods of time between maintenance and/or replacement of the membrane assemblies. Further, the present inventors have recognized that the use of such a
5 membrane assembly can enable sufficient airflow through the air channels without the need for other structural components which could impede breathability of the membrane assembly.

[0010] This overview is intended to provide an overview of subject matter of the present patent application. It is not intended to provide an exclusive or exhaustive
10 explanation of the invention. The detailed description is included to provide further information about the present patent application.

BRIEF DESCRIPTION OF THE DRAWINGS

[0001] FIG. 1A is perspective view depicting a portion of a LAMEE including a
15 membrane assembly in accordance with examples of this disclosure.

[0002] FIG. 1B is a side view of the LAMEE of FIG. 1A.

[0003] FIG. 1C is a cross-sectional view of the membrane assembly of FIGS. 1A and 1B.

[0004] FIG. 1D is a perspective view of a portion of the membrane assembly of FIGS.
20 1A-1C.

[0005] FIG. 2 is a perspective view depicting an example LAMEE including membrane assemblies in accordance with this disclosure.

[0006] FIG. 3 is a cut-away view of liquid panels within an energy exchange cavity of the LAMEE of FIG. 2.

25 [0007] FIG. 4 is an exploded view of an energy exchange cavity of a LAMEE.

[0008] FIG. 5 is an elevation front view of a LAMEE.

[0009] And, FIG. 6 is a cross-sectional view of a membrane assembly of a LAMEE.

[0010] In the drawings, which are not necessarily drawn to scale, like numerals may describe similar components in different views. Like numerals having different
30 letter suffixes may represent different instances of similar components. The drawings illustrate generally, by way of example, but not by way of limitation, various embodiments discussed in the present document.

DETAILED DESCRIPTION

35 [0011] Examples according to this disclosure include membrane assemblies, which can be used in a liquid to air membrane energy exchanger (LAMEE) to exchange

energy between a liquid and air traveling through the exchanger. A LAMEE can be used in a variety of HVAC systems including, for example, air conditioner, liquid cooler, direct or indirect evaporative cooler, and regeneration systems. For example, a LAMEE can evaporatively cool a liquid passing through liquid channels of the LAMEE. As another example, a LAMEE can modulate the temperature and/or humidity of air passing through one or more airflow channels of the LAMEE. Example membrane assemblies in accordance with this disclosure are described in conjunction with use in LAMEEs. However, example membrane assemblies may also be advantageously used in other types of exchangers or other devices.

5
10
15
20
[0012] FIGS. 1A-1C depict a portion of an example LAMEE 100 including a membrane assembly 102 in accordance with this disclosure. The portion of the LAMEE 100 depicted in FIG. 1A includes membrane assembly 102, fluid channel 104, and air channel 106. The liquid channel 104 and the air channel 106 are arranged adjacent to each other and separated by the membrane assembly 102. Support struts or spacers 108 can be attached on either side of the membrane assembly 102 to form adjacent liquid and air channels 104, 106. The liquid and air flowing through the liquid channel 104 and the air channel 106 move in counterflow or, in other words, opposite directions. Other LAMEEs including membrane assemblies in accordance with this disclosure, however, could be configured for crossflow or cross-counterflow of liquid and air.

25
30
35
[0013] The liquid channel 104 and air channel 106 of LAMEE 100 are depicted in a somewhat simplified form and only a relatively small portion of the LAMEE 100 is depicted to emphasize various aspects of the membrane assembly 102. However, LAMEEs including membrane assemblies in accordance with this disclosure can include a variety of liquid and air channel configurations. For example, a LAMEE can include a stack of alternating liquid and air channels. The liquid channels can include a liquid panel assembly, which encases the liquid flowing through the liquid panel between a pair of membrane assemblies, and the air channels can include a spacer or other structure (e.g., including struts like the struts 108) between pairs of liquid panels to define and encase air flow through the air flow channels. Each liquid panel assembly can define a plurality of separated liquid flow channels through the panel such that the liquid passing through the liquid panel is distributed among individual, fluidically isolated liquid flow channels. The air flow channel spacers can include struts that span a major dimension of the LAMEE (for example, span the length of the LAMEE in the direction of/parallel with air flow through the LAMEE) and can

also include additional structures that modulate the flow of air through the LAMEE in one or more advantages ways.

[0014] Referring again to FIG. 1A, a liquid, e.g. water or a liquid desiccant flows through the liquid channel 104 and air flows through the air channel 106 of the LAMEE 100 in the opposite direction as the liquid. The liquid and air flowing through the LAMEE 100 are separated by the membrane assembly 102 and the LAMEE is configured to transfer heat and/or moisture between the fluid streams. As illustrated in FIG. 1A, the pressure of the liquid within the liquid channel 104 can deflect the membrane assembly 102 outward and into the air channel 106.

[0015] FIG. 1B is an elevation front view depicting the LAMEE 100, including the liquid channel 104, the air channel 106, and the membrane assembly 102 therebetween. FIG. 1B depicts the bulging of the membrane assembly 102 in more detail. Additionally, FIG. 1B depicts the LAMEE 100 in one possible orientation in which it may be operated with the liquid channel 104 and the air channel 106 oriented for horizontal liquid and air flow and the membrane assembly spanning the channels vertically between struts 108.

[0016] In examples, the membrane assembly 102 is a multi-layer laminate including, in the orientation of FIG. 1B, a plurality of vertically extending and horizontally spaced apart tensile support members 110. The tensile support members 110 can be filaments formed from a variety of materials and can be oriented perpendicular to direction of flow of liquid through liquid channel 104 and air through air channel 106. The orientation of tensile support members 110 relative to the direction of fluid flow through LAMEE 100 can be adapted to improve/optimize tensile strength of the membrane assembly 102 against a pressure force from the liquid flowing through liquid channel 104.

[0017] In examples, the tensile support members 110 are elongated filaments that function to transfer the force generated by liquid pressure in liquid channel 104 to the struts 108, which struts are coupled to a frame or housing of LAMEE 100. The tensile support members 110 span/extend the entire distance across the liquid and air channels 104, 106.

[0018] The loading of the membrane assembly 102 may be, in some applications including the example depicted in FIGS. 1A-1C, generally in a single direction and tensile support members 110 may therefore be configured and arranged to increase the strength of the membrane assembly 102 in this single loading direction. Thus, in some examples, the membrane assembly 102 can have a pre-determined directional strength that is configured to oppose the liquid pressure force from a first direction

while being relatively less capable of opposing other forces from other directions. In so doing, the membrane assembly 102 can provide useful rigidity/strength and can minimize displacement or bulging of the assembly 102 into the air channel 106, while eliminating the need for support material to provide rigidity in directions that do not experience forces from the liquid in the liquid channel 104 or other sources.

5 [0019] Thus, the membrane assembly 102, particularly the tensile support members 110, can provide a tailored, directional rigidity/strength against the pressure from the liquid in the liquid channel 104 while not substantially inhibiting permeability of the membrane assembly 102 or contact of the air and liquid with the

10 surface of a membrane film of the membrane assembly 102.

[0020] In FIG. 1B, two membrane assemblies 102 are arranged between the struts or spacers 108 to form the liquid channel 104 therebetween. The membrane assemblies 102 can each be attached to or held by the struts 108, which struts can apply or maintain tension of each of the membrane assemblies 102. A liquid flowing

15 through the liquid channel 104 exerts an outward or bulging pressure on each of the membrane assemblies 102, as indicated by the arrows in FIG. 1B. The membrane assemblies 102 include the tensile support members 110 (as depicted in FIG. 1A) to increase the rigidity/strength of the membrane assemblies 102 and to thereby decrease the displacement or bulging of either of the membrane assemblies 102 into

20 adjacent air channels 106. In reducing such restriction of the air channels 106, the membrane assembly 102 can reduce pressure drop across the LAMEE 100 and, for example, associated fan power needed to compensate for such pressure drop.

[0021] FIG. 1C is a cross-sectional view depicting an example of the multi-layer construction of example membrane assembly 102. The membrane assembly 104

25 can include or use a membrane film 112, a substrate 114, and the tensile support members 110. The membrane film 112 can be arranged in the layer superadjacent to the liquid channel 104 and the liquid flowing therethrough with the substrate 114 in the next layer over the membrane film 112 and, finally, the tensile support members 110 over the substrate 114.

30 [0022] The membrane film 112 can be a semi-permeable or vapor permeable film, by which generally anything in a gas phase can pass through the membrane and anything in a liquid or solid phase cannot pass through the membrane. The membrane film 112 can also include a micro-porous membrane that is similarly configured to allow gases but not liquids or solids to pass through the membrane.

35 Additionally, the membrane film employed in membrane assemblies in accordance with this disclosure can be a non-porous film having selective permeability, e.g., for

water vapor/molecules, but not for other constituents in vapor/gas form/state/phase. The membrane film 112 can be constructed of polytetrafluoroethylene (PTFE), polypropylene, polyethylene, or other suitable membrane materials.

5 [0023] The substrate 114 can be attached to the membrane film 112 to provide additional support to the membrane film 112. The substrate 114 can be configured and constructed to transfer a loading or force from liquid pressure on the membrane film 112 to the tensile support members 110. The substrate 114 can be contacted at a plurality of locations of the membrane film 112. The substrate 114 can be finely
10 spored and can be a coarse porous material. The substrate 114 can also be a highly breathable spunbound fabric, veil, or other fibrous material. The substrate 114 can be bonded to the membrane film by thermal lamination, chemical adhesive, ultraviolet-curable adhesive, radiofrequency welding, laser welding, solvent, or adhesive. The substrate 114 can cover or support the membrane film 112 such as
15 to prevent puncture or impact during manufacturing and operation. The substrate 114 can be permeable and breathable to allow air, vapor, or other gases to pass through the substrate and contact the membrane film 112. The substrate 114 can enhance the ability to join the components of the membrane assembly 102 together in manufacturing, because, for example, fine fibers in the substrate 114 may be
20 thermally laminated into pores of the membrane film 112. Further, the substrate 114 may be readily bondable to the tensile support members 110.

[0024] The tensile support member 110 can be oriented such as to carry the load of liquid pressure in an exchanger and to transfer this load to an external supporting structure, such as the struts 108, as described in detail above. The tensile support
25 member 110 can be formed from a variety of materials, including, for example, ceramic, metallic, and/or glass fibers, or synthetic polymers such as thermoplastics, thermosets, elastomers, or synthetic fibers. The tensile support member 110 can be a filament formed of polypropylene, polyester, Teflon fluorinated ethylene propylene, polyamide, polypropylene, Polyethylene, Polybutylene,
30 Polymethylpentene, Polycarbonate, Polytetrafluoroethylene, Polyether ether ketone, or other polymers. The tensile support member 110 can be single stranded, double stranded, or multi-stranded. In some examples, the tensile support member 110 can be formed of threads or other types of netting, mesh, woven, or extruded materials. The tensile support member 110 can be attached to the substrate 114 by
35 a variety of methods, including, for example, weaving, thermal lamination, chemical

adhesive, ultraviolet-curable adhesive, radiofrequency welding, ultrasonic welding, laser welding, solvent, and/or adhesive.

[0025] FIG. 1D shows a perspective view of a portion of example membrane assembly 102. In the example of FIG. 1D, the tensile support member is integrated with or woven into the substrate 114. The tensile support member 110 can be integrated into the substrate 114 by, for example, additive manufacturing processes such as 3D printing. The tensile support member 110 can be made from the same or different material as the substrate 114. Also, the tensile support member 110 can be integrated into the substrate 114 as a part of the process of substrate fabrication. As an example, and may be the case of the example depicted in FIG. 1D, woven substrate 114 incorporates supporting the tensile support member 110, which is an elongated filament interlaced into fibers or threads of the substrate 114.

[0026] In other examples, the tensile support members of membrane assemblies in accordance with this disclosure can be bound to a substrate as a separate layer. Alternatively or additionally, the tensile support members can be produced using methods to integrate the supporting members into the substrate by, for example, electrospinning to fabricate nanofiber fabrics or spun-bonding to fabricate non-woven fabrics.

[0027] FIGS. 2-4 illustrate an example LAMEE in which membrane assemblies in accordance with this disclosure may be employed. FIG. 2 is a perspective view depicting an example LAMEE 300 including membrane assemblies 378 (shown in FIG. 3) separating adjacent liquid and air channels through the device. The LAMEE 300 includes a housing 302 having a body 304. The body 304 includes an air inlet end 306 and an air outlet end 308. A top 310 extends between the air inlet end 306 and the air outlet end 308. A bottom 316 extends between the air inlet end 306 and the air outlet end 308.

[0028] An air inlet 322 is positioned at the air inlet end 306. An air outlet 324 is positioned at the air outlet end 308. Sides 326 extend between the air inlet 322 and the air outlet 324.

[0029] An energy exchange cavity 330 extends through the housing 302 of the LAMEE 300. The energy exchange cavity 330 extends from the air inlet end 306 to the air outlet end 308. An air stream 332 is received in the air inlet 322 and flows through the energy exchange cavity 330. The air stream 332 is discharged from the energy exchange cavity 330 at the air outlet 324. The energy exchange cavity 330 may include a plurality of panels 334, such as liquid panels, each of which is configured to receive a liquid and direct the flow of the liquid therethrough, for

example, via a plurality of individual, fluidically isolated liquid flow channels included in each liquid panel.

[0030] A liquid inlet reservoir 352 may be positioned on the top 310. The liquid inlet reservoir 352 may be configured to receive liquid, which may be stored in a storage tank. The liquid inlet reservoir 352 may include an inlet in flow communication with the storage tank. The liquid flowing through LAMEE 300 is received through the inlet. The liquid inlet reservoir 352 may also include an outlet that is in fluid communication with liquid channels 376 of the panels 334 in the energy exchange cavity 330. The liquid flows through the outlet into the liquid channels 376. The liquid flows along the panels 334 through the liquid channels 376 to a liquid outlet reservoir 354, which may be positioned at or proximate the bottom 316. Accordingly, the liquid may flow through the LAMEE 300 from top to bottom (and side-to-side). For example, the liquid may flow into the liquid channels 376 proximate the liquid inlet reservoir 352, down to and through horizontally oriented liquid channels 376, and out of the LAMEE 300 proximate to the liquid outlet reservoir 354. In an alternative embodiment, the liquid may flow through the LAMEE 300 from bottom to top.

[0031] FIG. 3 illustrates a cut-away front view of the panels 334 within the energy exchange cavity 330 of the LAMEE 300. The panels 334 may be solution or liquid panels configured to direct the flow of liquid therethrough. The panels 334 form a liquid flow path 376 that is confined by membrane assemblies 378 on either side and is configured to carry liquid therethrough. The membrane assemblies 378 are arranged in parallel to form air channels 336 with an average flow channel width of 337 and liquid channels 376 with an average flow channel width of 377. In one embodiment, the membrane assemblies 378 are spaced to form uniform air channels 336 and liquid channels 376. The air stream 332 (shown in FIG. 2) travels through the air channels 336 between the membrane assemblies 378. The liquid in each liquid channel 376 exchanges heat and/or moisture with the air stream 332 in the air channels 336 through the membrane assemblies 378. The air channels 336 alternate with the liquid channels 376. Except for the two side panels of the energy exchange cavity, each air channel 336 may be positioned between adjacent liquid channels 376.

[0032] In order to reduce the liquid channels 376 from outwardly bulging or bowing, the membrane assemblies 378 each may include a plurality of tensile support members, as described in the examples of FIGS. 1A-1D. Additionally, to further reduce the liquid channels 376 from outwardly bulging or bowing, support

assemblies may be positioned within the air channels 336. Such support assemblies can be configured to support the membrane assemblies 378, as well as promote turbulent air flow in the air channels 336.

[0033] FIG. 4 is an exploded view of an energy exchange cavity 400 of a LAMEE, e.g., LAMEE 300. The energy exchange cavity 400 may include a plurality of liquid panel assemblies 402 spaced apart from one another by support assemblies 404. The support assemblies 404 may reside in air channels 406. Airflow 408 is configured to pass through the air channels 406 between liquid panel assemblies 402. As shown, the airflow 408 may generally be aligned with a horizontal axis 410 of the energy exchange cavity 400. Thus, the airflow 408 may be horizontal with respect to the energy exchange cavity 400. Notably, however, the support assemblies 404 may include turbulence promoters configured to generate turbulence, eddies, and the like in the airflow 408 within the energy exchange cavity 400.

[0034] Each liquid panel assembly 402 may include a support frame 412 connected to an inlet member 414 at an upper corner 415 and an outlet member 416 at a lower corner 417 that may be diagonal to the upper corner 415. Further, membrane assemblies 418 in accordance with this disclosure are positioned on each side of the support frame 412. The membrane assemblies 418 sealingly engage the support frame 412 along outer edges in order to contain liquid within the liquid panel assembly 402.

[0035] Each inlet member 414 may include a liquid delivery opening 420, while each outlet member 416 may include a liquid passage opening 422. The liquid delivery openings 420 may be connected together through conduits, pipes, or the like, while the liquid passage openings 422 may be connected together through conduits, pipes, or the like. Optionally, the inlet members 414 and outlet members 416 may be sized and shaped to directly mate with one another so that a liquid-tight seal is formed therebetween. Accordingly, liquid may flow through the liquid delivery openings 420 and the liquid passage openings 422. The inlet members 414 and outlet members 416 may be modular components configured to selectively couple and decouple from other inlet members 414 and outlet members 416, respectively. For example, the inlet members 414 and outlet members 416 may be configured to securely mate with other inlet members 414 and outlet members 416, respectively, through snap and/or latching connections, or through fasteners and/or adhesives.

[0036] As shown, the liquid panel assemblies 402, the support assemblies 404, and the air channels 406 may all be vertically oriented. The liquid panel assemblies 402

may be flat plate exchangers that are vertically-oriented with respect to a base that is supported by a floor, for example, of a structure.

[0037] In operation, liquid flows into the liquid delivery openings 420 of the inlet members 414. For example, the liquid may be pumped into the liquid delivery openings 420 through a pump. The liquid then flows into the support frames 412 through a liquid path 424 toward the outlet members 416. As shown, the liquid path 424 includes a vertical descent 426 that connects to a horizontal, flow portion, such as a flow portion 428, which, in turn, connects to a vertical descent 430 that connects to the liquid passage opening 422 of the outlet member 416. The vertical descents 426 and 430 may be perpendicular to the horizontal, flow portion 428. As such, the liquid flows through the solution panel assemblies 402 from the top corners 415 to the lower corners 417. The horizontal flow portion 428 provides liquid that may counterflow with respect to the airflow 408. Alternatively, the flow portion may be a crossflow, cross-counterflow, parallel-aligned flow, or other such flow configurations.

[0038] The airflow 408 that passes between the liquid panel assemblies 402 exchanges energy with the liquid flowing through the liquid panel assemblies 402. The liquid may be water, a desiccant, refrigerant, or any other type of liquid that may be used to exchange energy with the airflow 408.

[0039] The energy exchange cavity 400 may include more or less liquid panel assemblies 402, support assemblies 404, and air channels 406 than those shown in FIG. 4. The inlet and outlet members 414 and 416 may be modular panel headers that are configured to selectively attach and detach from neighboring inlet and outlet members 414 and 416 to provide a manifold for liquid to enter into and pass out of the liquid panel assemblies 402. Sealing agents, such as gaskets, silicone gel, or the like, may be disposed between neighboring inlet members 414 and neighboring outlet members 416. At least a portion of the membrane assemblies 418 can sealingly engage the inlet and outlet members 414 and 416.

[0040] In manufacturing or fabrication of the membrane assembly, a fibrous substrate can be provided or obtained for production. The fibrous substrate can be supplied as a bolt of material, such as a roll of material. The fibrous substrate can be attached to a plurality of tensile members. In one example, the fibrous substrate can be supplied in the bolt or roll of material having previously been attached to, impregnated with, or woven with the plurality of tensile members. The fibrous substrate can be supplied on rolls having the tensile members running substantially parallel to the direction in which the material is rolled. Alternatively or additionally,

the fibrous substrate can be supplied on rolls having the tensile members running substantially perpendicular to the direction in which the material is rolled. Further, the fibrous substrate can have the tensile members running diagonal to the direction in which the material is rolled. The fibrous substrate can be cut to a predetermined height for suitable use in a liquid to air membrane energy exchanger (LAMEE). The fibrous substrate can be laminated, bonded, or attached to a membrane film.

[0041] FIGS. 5 depicts a portion of an example LAMEE 500 including a membrane assembly 502 in accordance with this disclosure. The LAMEE 500 includes membrane assembly 502 which are substantially similar to LAMEE 100 and membrane assembly 102, described above with reference to FIG. 1A-1D. The components, structures, configurations, functions, etc. of membrane assembly 502 can therefore be the same as or substantially similar to that described in detail with respect to membrane assembly 102. FIG. 5 is an elevation front view depicting the LAMEE 500, including the liquid channel 504, the air channel 506, and the membrane assembly 502 therebetween. FIG. 5 depicts the bulging of the membrane assembly 502. Additionally, FIG. 5 depicts the LAMEE 500 in one possible orientation in which it may be operated with the liquid channel 504 and the air channel 506 oriented for horizontal liquid and air flow and the membrane assembly spanning the channels and in the absence of struts, such as the struts 108 depicted in FIG. 1B. Alleviating a need for external struts can help reduce an airside pressure drop from an air channel 506 of a LAMEE 500 in operation or use as well as lower a manufacturing cost thereof. Further, a self-supporting membrane assembly 502, not needing external support from struts, stringers, or a frame, can allow for more flexible orientation of the LAMEE 500, e.g., allow for smaller or less-wide LAMEE 500 arrangements.

[0042] In examples, the membrane assembly 502 is a multi-layer laminate including a membrane film 508 and, in the orientation of FIG. 5, a plurality of vertically extending and horizontally spaced apart tensile support members 510 (e.g., substantially similar to tensile support members 110 of FIG. 1A). The tensile support members can be filaments formed from a variety of materials and can be oriented perpendicular to direction of flow of liquid through liquid channel 504 and air through air channel 506. The orientation of tensile support members relative to the direction of fluid flow through LAMEE 100 can be adapted to improve/optimize tensile strength of the membrane assembly 502 against a pressure force from the liquid flowing through liquid channel 504. For example, the tensile support members can be arranged such as to alleviate the need for struts for compressing

the membrane assembly 502 against a liquid pressure force within the liquid channel 504. For example, the membrane assembly can be arranged, such as including tensile support members, to bulge and withstand a liquid pressure force within the liquid channel 504 without the need for external supporting struts, stringers, frames, or other structures.

[0043] The tensile support members 510 can be formed from a variety of materials, including, for example, ceramic, metallic, and/or glass fibers, or synthetic polymers such as thermoplastics, thermosets, elastomers, or synthetic fibers. The tensile support members 510 can be a filament formed of polypropylene, polyester, Teflon fluorinated ethylene propylene, polyamide, polypropylene, Polyethylene, Polybutylene, Polymethylpentene, Polycarbonate, Polytetrafluoroethylene, Polyether ether ketone, or other polymers. The tensile support members 510 can be single stranded, double stranded, or multi-stranded. In some examples, the tensile support member 510 can be formed of threads or other types of netting, mesh, woven, or extruded materials.

[0044] For example, the tensile support members can be elongated filaments that function to transfer the force generated by liquid pressure in liquid channel 504 to an internal support 509 arranged between two membrane assemblies 502, and without the need to transfer the force generated by liquid pressure in the liquid channel 504 to external struts, such as struts 108 depicted in FIG. 1B. For example, a panel of a LAMEE 500 including two membrane assemblies 502 arranged opposite each other against at least one internal support 509 can be self-supporting, able to withstand liquid pressure within the liquid channel 504 without needing external support.

[0045] The membrane film 508 can be a semi-permeable or vapor permeable film, by which generally anything in a gas phase can pass through the membrane and anything in a liquid or solid phase cannot pass through the membrane. The membrane film 508 can also include a micro-porous membrane that is similarly configured to allow gases but not liquids or solids to pass through the membrane. Additionally, the membrane film employed in membrane assemblies in accordance with this disclosure can be a non-porous film having selective permeability, e.g., for water vapor/molecules, but not for other constituents in vapor/gas form/state/phase. The membrane film 508 can be constructed of

polytetrafluoroethylene (PTFE), polypropylene, polyethylene, or other suitable membrane materials.

[0046] In an example, the membrane assembly 502 can be attached to the internal support 509 by a physical adhesive or bond. For example, the membrane assembly
5 502 can be attached to the internal support 509 by an adhesive tape such as a 3M™ Acrylic Adhesive, a solvent based adhesive such as including one of polychloroprene, polyurethane, acrylic, silicone, or rubber and a solvent. Also, the membrane assembly 502 can be attached to the internal support 509 via a direct thermal bond such as a spot weld, a laser weld, or an ultrasonic (UT) weld. Other types of thermal
10 bonds can also be created such as by melting at a target bond location one of the internal support 509 or the membrane assembly 502 to create a bond.

[0047] The loading of the membrane assembly 502 may be, in some applications including the example depicted in FIG 5, generally in a single direction and tensile support members may therefore be configured and arranged to increase the
15 strength of the membrane assembly 502 in this single loading direction. Thus, in some examples, the membrane assembly 502 can have a pre-determined directional strength that is configured to oppose the liquid pressure force from a first direction while being relatively less capable of opposing other forces from other directions. In so doing, the membrane assembly 502 can provide useful rigidity/strength and
20 can minimize displacement or bulging of the assembly 502 into the air channel 506, while eliminating the need for support material to provide rigidity in directions that do not experience forces from the liquid in the liquid channel 502 or other sources.

[0048] Thus, the membrane assembly 502, particularly the tensile support members 510, can provide a tailored, directional rigidity/strength against the
25 pressure from the liquid in the liquid channel 504 while not substantially inhibiting permeability of the membrane assembly 502 or contact of the air and liquid with the surface of a membrane film of the membrane assembly 502.

[0049] In FIG. 5, two membrane assemblies 502 are arranged between the internal supports 509 to form the liquid channel 504 therebetween. The membrane
30 assemblies 502 can each be attached to or held by the internal supports 509. A liquid flowing through the liquid channel 504 exerts an outward or bulging pressure on each of the membrane assemblies 502, as indicated by the arrows in FIG. 5. The membrane assemblies 502 include the tensile support members (such as tensile support members 110 depicted in FIG. 1A) to increase the rigidity/strength of the
35 membrane assemblies 502 and to thereby decrease the displacement or bulging of either of the membrane assemblies 502 into adjacent air channels 506. In reducing

such restriction of the air channels 506, the membrane assembly 502 can reduce pressure drop across the LAMEE 500 and, for example, associated fan power needed to compensate for such pressure drop. Also, in alleviating the need for external struts to apply inward pressure or compression against the bulging, the membrane assembly 502 can reduce certain design restrictions, such as restrictions pertaining to LAMEE 500 component layout of certain membrane assemblies 502 relying on external struts to counteract the force generated by liquid pressure in the liquid channel 504.

[0050] FIG. 6 is a cross-sectional view depicting an example of the multi-layer construction of example membrane assembly 602. The membrane assembly 602 is substantially similar to membrane assembly 102, described above with reference to FIG. 1A-1D without a substrate layer between a membrane film 612 and tensile support members 610, thus forming a two-layer membrane assembly 602. The membrane film 612 can be arranged in the layer super adjacent to a liquid channel 604 and the liquid flowing therethrough with the tensile support members 610 in the next layer over the membrane film 612. For example, directly bonding the membrane film 612 and the tensile support members 610 (such as a tensile support member layer) can help allow for construction of a LAMEE without the need for external struts to support the membrane assembly and to counteract a liquid pressure force from the liquid channel, such as described above with respect to FIG. 5.

[0051] The membrane film 612 can be a semi-permeable or vapor permeable film, by which generally anything in a gas phase can pass through the membrane and anything in a liquid or solid phase cannot pass through the membrane. The membrane film 612 can also include a micro-porous membrane that is similarly configured to allow gases but not liquids or solids to pass through the membrane. Additionally, the membrane film employed in membrane assemblies in accordance with this disclosure can be a non-porous film having selective permeability, e.g., for water vapor/molecules, but not for other constituents in vapor/gas form/state/phase. The membrane film 612 can be constructed of polytetrafluoroethylene (PTFE), polypropylene, polyethylene, or other suitable membrane materials.

[0052] The tensile support members 610 can be oriented such as to carry the load of liquid pressure in an exchanger and to transfer this load to an external supporting structure, such as the struts 108, as described in detail above with respect to FIG. 1A-1D. The tensile support members 610 can be formed from a variety of materials,

including, for example, ceramic, metallic, and/or glass fibers, or synthetic polymers such as thermoplastics, thermosets, elastomers, or synthetic fibers. The tensile support members 610 can be a filament formed of polypropylene, polyester, Teflon fluorinated ethylene propylene, polyamide, polypropylene, Polyethylene, Polybutylene, Polymethylpentene, Polycarbonate, Polytetrafluoroethylene, Polyether ether ketone, or other polymers. The tensile support members 610 can be single stranded, double stranded, or multi-stranded. In some examples, the tensile support member 610 can be formed of threads or other types of netting, mesh, woven, or extruded materials.

10 [0053] The above description includes references to the accompanying drawings, which form a part of the detailed description. The drawings show, by way of illustration, specific embodiments in which the invention can be practiced. These embodiments are also referred to herein as “examples.” Such examples can include elements in addition to those shown or described. However, the present inventors
15 also contemplate examples in which only those elements shown or described are provided. Moreover, the present inventors also contemplate examples using any combination or permutation of those elements shown or described (or one or more aspects thereof), either with respect to a particular example (or one or more aspects thereof), or with respect to other examples (or one or more aspects thereof) shown
20 or described herein.

[0054] In the event of inconsistent usages between this document and any documents so incorporated by reference, the usage in this document controls.

[0055] In this document, the terms “a” or “an” are used, as is common in patent documents, to include one or more than one, independent of any other
25 instances or usages of “at least one” or “one or more.” In this document, the term “or” is used to refer to a nonexclusive or, such that “A or B” includes “A but not B,” “B but not A,” and “A and B,” unless otherwise indicated. In this document, the terms “including” and “in which” are used as the plain-English equivalents of the respective terms “comprising” and “wherein.” Also, in the following claims, the terms
30 “including” and “comprising” are open-ended, that is, a system, device, article, composition, formulation, or process that includes elements in addition to those listed after such a term in a claim are still deemed to fall within the scope of that claim. Moreover, in the following claims, the terms “first,” “second,” and “third,” etc.

are used merely as labels, and are not intended to impose numerical requirements on their objects.

[0056] Geometric terms, such as “parallel”, “perpendicular”, “round”, or “square”, are not intended to require absolute mathematical precision, unless the context indicates otherwise. Instead, such geometric terms allow for variations due to manufacturing or equivalent functions. For example, if an element is described as “round” or “generally round,” a component that is not precisely circular (e.g., one that is slightly oblong or is a many-sided polygon) is still encompassed by this description.

[0057] Method examples described herein can be machine or computer-implemented at least in part. Some examples can include a computer-readable medium or machine-readable medium encoded with instructions operable to configure an electronic device to perform methods as described in the above examples. An implementation of such methods can include code, such as microcode, assembly language code, a higher-level language code, or the like. Such code can include computer readable instructions for performing various methods. The code may form portions of computer program products. Further, in an example, the code can be tangibly stored on one or more volatile, non-transitory, or non-volatile tangible computer-readable media, such as during execution or at other times. Examples of these tangible computer-readable media can include, but are not limited to, hard disks, removable magnetic disks, removable optical disks (e.g., compact disks and digital video disks), magnetic cassettes, memory cards or sticks, random access memories (RAMs), read only memories (ROMs), and the like.

[0058] The above description is intended to be illustrative, and not restrictive. For example, the above-described examples (or one or more aspects thereof) may be used in combination with each other. Other embodiments can be used, such as by one of ordinary skill in the art upon reviewing the above description. The Abstract is provided to comply with 37 C.F.R. §1.72(b), to allow the reader to quickly ascertain the nature of the technical disclosure. It is submitted with the understanding that it will not be used to interpret or limit the scope or meaning of the claims. Also, in the above Detailed Description, various features may be grouped together to streamline the disclosure. This should not be interpreted as intending that an unclaimed disclosed feature is essential to any claim. Rather, inventive subject matter may lie in less than all features of a particular disclosed embodiment. Thus, the following claims are hereby incorporated into the Detailed Description as examples or embodiments, with each claim standing on its own as a separate

embodiment, and it is contemplated that such embodiments can be combined with each other in various combinations or permutations. The scope of the invention should be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled.

5

What is claimed is:

1. A membrane assembly for use in a liquid to air membrane energy exchanger (LAMEE), the membrane assembly comprising:
 - 5 a membrane film configured to transfer heat and moisture between a liquid and air flowing through the LAMEE;
 - a substrate connected to the membrane film; and
 - a plurality of tensile support members connected to the substrate, the plurality of tensile support members being in spaced relation to one
10 another and oriented perpendicular to a direction of flow of the liquid through the LAMEE.
2. The membrane assembly of claim 1, further comprising a plurality of struts oriented perpendicular to the plurality of tensile support members.
15
3. The membrane assembly of claim 2, wherein the plurality of tensile support members are configured to transfer a force from the liquid flowing through the LAMEE to a pair of struts of the plurality of struts.
- 20 4. The membrane assembly of claim 1, wherein the plurality of tensile support members are substantially parallel to one another.
5. The membrane assembly of claim 1, wherein each of the plurality of tensile support members spans entirely across a major dimension of the
25 membrane film.
6. The membrane assembly of claim 1, wherein each of the plurality of tensile support members comprises an elongated filament.
- 30 7. The membrane assembly of claim 1, wherein the plurality of tensile support members are configured to provide tensile strength against a force applied on the membrane assembly into an air flow channel of the LAMEE.

8. The membrane assembly of claim 1, wherein the plurality of tensile support members are configured to provide tensile strength to the membrane assembly in a direction perpendicular to the direction of flow of the liquid through the LAMEE.
- 5
9. The membrane assembly of claim 8, wherein the plurality of tensile support members are each curved to project into a liquid channel of the LAMEE.
- 10
10. The membrane assembly of claim 1, wherein each of the plurality of tensile support members comprise non-woven spun-bonded filament(s).
11. The membrane assembly of claim 1, wherein each of the plurality of tensile support members comprise spun-bonded nanofibers.
- 15
12. The membrane assembly of claim 1, wherein the membrane film comprises a microporous film.
13. The membrane assembly of claim 1, wherein the membrane film
- 20 comprises a low surface energy polymer.
14. The membrane assembly of claim 13, wherein the membrane film comprises polytetrafluoroethylene (PTFE).
- 25
15. A membrane assembly for use in a liquid to air membrane energy exchanger (LAMEE), the membrane assembly comprising:
a membrane film configured to transfer heat and moisture between a liquid and air flowing through the LAMEE; and
a plurality of tensile support members connected to the membrane film, the
- 30 plurality of tensile support members being in spaced relation to one another and oriented perpendicular to a direction of flow of the liquid through the LAMEE.

16. The membrane assembly of claim 15, wherein the plurality of tensile support members are substantially parallel to one another.
17. The membrane assembly of claim 15, wherein each of the plurality of
5 tensile support members spans entirely across a major dimension of the membrane film.
18. The membrane assembly of claim 15, wherein each of the plurality of
10 tensile support members comprises an elongated filament.
19. The membrane assembly of claim 15, wherein the plurality of tensile support members are configured to provide tensile strength against a force applied on the membrane assembly into an air flow channel of the LAMEE.
- 15 20. The membrane assembly of claim 15, wherein the plurality of tensile support members are configured to provide tensile strength to the membrane assembly in a direction perpendicular to the direction of flow of the liquid through the LAMEE.
- 20 21. The membrane assembly of claim 22, wherein the plurality of tensile support members are each curved to project into a liquid channel of the LAMEE.
22. The membrane assembly of claim 15, wherein each of the plurality of
25 tensile support members comprise non-woven spun-bonded filament(s).
23. The membrane assembly of claim 15, wherein each of the plurality of tensile support members comprise spun-bonded nanofibers.
- 30 24. The membrane assembly of claim 15, wherein the membrane film comprises a microporous film.

25. The membrane assembly of claim 15, wherein the membrane film comprises a low surface energy polymer.
26. The membrane assembly of claim 27, wherein the membrane film
5 comprises polytetrafluoroethylene (PTFE).
27. A liquid panel for use in a liquid to air membrane energy exchanger (LAMEE), the liquid panel comprising:
a support frame; and
a pair of membrane assemblies connected to opposing sides of the support
10 frame, wherein each membrane assembly comprises:
a membrane film configured to transfer heat and moisture between a
liquid and air flowing through the LAMEE; and
a plurality of tensile support members connected to the membrane
film, the plurality of tensile support members being in spaced
15 relation to one another and oriented perpendicular to a
direction of flow of the liquid through the LAMEE.
28. A liquid to air membrane energy exchanger (LAMEE) comprising:
a plurality of liquid panels, each of which forms a plurality of liquid flow
channels and comprises:
20 a support frame; and
a pair of membrane assemblies connected to opposing sides of the
support frame, wherein each membrane assembly comprises:
a membrane film configured to transfer heat and moisture
between a liquid and air flowing through the LAMEE;
25 and
a plurality of tensile support members connected to the
membrane film, the plurality of tensile support
members being in spaced relation to one another and
oriented perpendicular to a direction of flow of the
30 liquid through the LAMEE; and
a plurality of air channels,

wherein the plurality of liquid panels and plurality of air channels are stacked in alternating relation with a pair of liquid panels on opposing sides of each air channel.

1/9




FIG. 1A

2/9




FIG. 1B




FIG. 1C

4/9




FIG. 1D

5/9




FIG. 2

6/9




FIG. 3

7/9




FIG. 4

8/9




FIG. 5




FIG. 6

INTERNATIONAL SEARCH REPORT

International application No.

PCT/CA2022/051019

A. CLASSIFICATION OF SUBJECT MATTER

IPC: **F28D 21/00** (2006.01), **B01D 61/36** (2006.01), **B01D 63/08** (2006.01), **F28D 9/00** (2006.01),
F28F 9/00 (2006.01), **F28F 9/007** (2006.01)

CPC: , B01D 61/362 (2020.01), B01D 63/08 (2020.01), F28D 9/00 (2020.01),
F28D 21/0015 (2020.01), F28F 9/007 (2020.01)

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC: F28D 21/00 (2006.01), B01D 61/36 (2006.01), B01D 63/08 (2006.01), F28D 9/00 (2006.01), F28F 9/00 (2006.01), F28F 9/007 (2006.01)
CPC: B01D 61/362 (2020.01), B01D 63/08 (2020.01), F28D 9/00 (2020.01), F28D 21/0015 (2020.01), F28F 9/007 (2020.01)

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic database(s) consulted during the international search (name of database(s) and, where practicable, search terms used)

Intellect (Canadian Patent Database), Questel Orbit

search terms: membrane, tensile member, liquid, liquid to air, LAMEE, substrate, tensile, support.

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A Y	CA2300209 A1 (PEDERSEN et al.) 8 September 2001 (08-09-2001) *whole document*	1-14 15-28
A Y	US7128532 B2 (PETERVARY et al.) 31 October 2006 (31-10-2006) *whole document*	1-14 15-28
A	US20210010765 A1 (HAMASAKI) 14 January 2021 (14-01-2021) *whole document*	1-28
A	US9234665 B2 (ERB et al.) 12 January 2016 (12-01-2016) *whole document*	1-28
A	US10712024 B2 (LEPOUDRE et al.) 14 July 2020 (14-07-2021) *whole document*	1-28

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* “A” “D” “E” “L” “O” “P”	Special categories of cited documents: document defining the general state of the art which is not considered to be of particular relevance document cited by the applicant in the international application earlier application or patent but published on or after the international filing date document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) document referring to an oral disclosure, use, exhibition or other means document published prior to the international filing date but later than the priority date claimed	“T” “X” “Y” “&”	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art document member of the same patent family
---	---	--------------------------	--

Date of the actual completion of the international search
17 August 2022 (17-08-2022)

Date of mailing of the international search report
13 September 2022 (13-09-2022)

Name and mailing address of the ISA/CA
Canadian Intellectual Property Office
Place du Portage I, C114 - 1st Floor, Box PCT
50 Victoria Street
Gatineau, Quebec K1A 0C9
Facsimile No.: 819-953-2476

Authorized officer

Rafal Byczko (819) 639-4298

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.

PCT/CA2022/051019

Patent Document Cited in Search Report	Publication Date	Patent Family Member(s)	Publication Date
CA2300209A1	08 September 2001 (08-09-2001)	AT352524T AU3716101A CA2300719A1 DE60126356D1 DE60126356T2 EP1423338A2 EP1423338B1 US2002020666A1 US6558549B2 US2003150798A1 US6645374B2 US2004079692A1 US6908547B2 WO0166474A2 WO0166474A3	15 February 2007 (15-02-2007) 17 September 2001 (17-09-2001) 15 September 2001 (15-09-2001) 15 March 2007 (15-03-2007) 08 November 2007 (08-11-2007) 02 June 2004 (02-06-2004) 24 January 2007 (24-01-2007) 21 February 2002 (21-02-2002) 06 May 2003 (06-05-2003) 14 August 2003 (14-08-2003) 11 November 2003 (11-11-2003) 29 April 2004 (29-04-2004) 21 June 2005 (21-06-2005) 13 September 2001 (13-09-2001) 07 March 2002 (07-03-2002)
US10712024B2	14 July 2020 (14-07-2020)	US2016054012A1 AU2015306040A1 CA2958480A1 CN107249715A CN107249715B DK3183051T3 EP3183051A1 EP3183051A4 EP3183051B1 WO2016026042A1	25 February 2016 (25-02-2016) 06 April 2017 (06-04-2017) 25 February 2016 (25-02-2016) 13 October 2017 (13-10-2017) 06 November 2020 (06-11-2020) 02 June 2020 (02-06-2020) 28 June 2017 (28-06-2017) 18 April 2018 (18-04-2018) 29 April 2020 (29-04-2020) 25 February 2016 (25-02-2016)
US7128532B2	31 October 2006 (31-10-2006)	US2005045306A1 AU2004202946A1 AU2004202946B2 EP1500880A2 EP1500880A3 EP1500880B1 JP2005042721A JP5252672B2	03 March 2005 (03-03-2005) 10 February 2005 (10-02-2005) 12 May 2011 (12-05-2011) 26 January 2005 (26-01-2005) 30 December 2009 (30-12-2009) 07 September 2016 (07-09-2016) 17 February 2005 (17-02-2005) 31 July 2013 (31-07-2013)
US2021010765A1	14 January 2021 (14-01-2021)	CN111989534A EP3779348A1 EP3779348A4 JP6571894B1 JP2020118434A WO2019189516A1	24 November 2020 (24-11-2020) 17 February 2021 (17-02-2021) 22 December 2021 (22-12-2021) 04 September 2019 (04-09-2019) 06 August 2020 (06-08-2020) 03 October 2019 (03-10-2019)

INTERNATIONAL SEARCH REPORT

International application No.

PCT/CA2022/051019

Patent Document Cited in Search Report	Publication Date	Patent Family Member(s)	Publication Date
US9234665B2	12 January 2016 (12-01-2016)	US2013186121A1 AU2011268661A1 AU2011268661B2 AU2015101399A4 AU2015230799A1 AU2015230799B2 AU2018204774A1 AU2018204774B2 CA2801352A1 CA2801352C CA3046529A1 CN103069246A CN103069246B EP2585784A2 EP2585784A4 US2016084512A1 US10302317B2 US2019212020A1 US2022003436A1 WO2011161547A2 WO2011161547A3	25 July 2013 (25-07-2013) 10 January 2013 (10-01-2013) 26 November 2015 (26-11-2015) 05 November 2015 (05-11-2015) 15 October 2015 (15-10-2015) 29 March 2018 (29-03-2018) 19 July 2018 (19-07-2018) 16 July 2020 (16-07-2020) 29 December 2011 (29-12-2011) 16 July 2019 (16-07-2019) 29 December 2011 (29-12-2011) 24 April 2013 (24-04-2013) 03 February 2016 (03-02-2016) 01 May 2013 (01-05-2013) 24 February 2016 (24-02-2016) 24 March 2016 (24-03-2016) 28 May 2019 (28-05-2019) 11 July 2019 (11-07-2019) 06 January 2022 (06-01-2022) 29 December 2011 (29-12-2011) 12 April 2012 (12-04-2012)