



(86) Date de dépôt PCT/PCT Filing Date: 2007/04/19
(87) Date publication PCT/PCT Publication Date: 2007/11/01
(45) Date de délivrance/Issue Date: 2019/04/09
(85) Entrée phase nationale/National Entry: 2008/10/20
(86) N° demande PCT/PCT Application No.: US 2007/009633
(87) N° publication PCT/PCT Publication No.: 2007/124038
(30) Priorité/Priority: 2006/04/20 (US60/793,452)


(51) Cl.Int./Int.Cl. *A61C 5/40* (2017.01),
A61C 17/02 (2006.01), *A61C 5/50* (2017.01)

(72) Inventeurs/Inventors:
GHARIB, MORTEZA, US;
ADAMS, JOSHUA, US;
HARS, ERIK, US;
BERGHEIM, BJARNE, US;
STOCKS, KARL, US;
DOHERTY, LANCE, US

(73) Propriétaire/Owner:
SONENDO, INC., US

(74) Agent: FETHERSTONHAUGH & CO.

(54) Titre : APPAREIL ET PROCEDES POUR TRAITER DES CANAUX RADICULAIRES DE DENTS
(54) Title: APPARATUS AND METHODS FOR TREATING ROOT CANALS OF TEETH



(57) Abrégé/Abstract:

Apparatus and methods for endodontic treatment of teeth provide effective cleaning of organic material (such as pulp and diseased tissue) from the root canal system. In an embodiment, a compressor system generates high pressure liquid (e.g., water) that flows through an orifice to produce a high-velocity collimated jet of liquid. The high-velocity jet is directed toward a surface of a tooth, for example, an exposed dentinal surface, and impingement of the jet onto the surface generates an acoustic wave that propagates throughout the tooth. The acoustic wave effectively detaches organic material from dentinal surfaces and tubules. The detached organic material is flushed from the root canal system by the liquid jet and/or by additional irrigation.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
1 November 2007 (01.11.2007)

PCT

(10) International Publication Number
WO 2007/124038 A3(51) International Patent Classification:
A61C 5/02 (2006.01)(21) International Application Number:
PCT/US2007/009633

(22) International Filing Date: 19 April 2007 (19.04.2007)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/793,452 20 April 2006 (20.04.2006) US(71) Applicant (for all designated States except US): **DENTATEK CORPORATION** [US/US]; 26015 Merit Circle, Suite 104, Laguna Hills, California 92653 (US).

(72) Inventors; and


(75) Inventors/Applicants (for US only): **GHARIB, Morteza** [US/US]; 556 S. Berkeley Avenue, San Marino, CA 91108 (US). **ADAMS, Joshua** [US/US]; 400 N. El Molino Avenue, Apt. F, Pasadena, CA 91101 (US). **HARS, Erik** [US/US]; 26341 Marsala Way, Mission Viejo, CA 92692(US). **BERGHEIM, Bjarne** [NO/US]; 26362 Ibeza Road, Mission Viejo, CA 92692 (US). **STOCKS, Karl** [US/US]; 3568 Newland Road, Oceanside, CA 92056 (US). **DOHERTY, Lance** [US/US]; 17316 Moonglow Circle, Cerritos, CA 90703 (US).(74) Agent: **DELANEY, Karoline A.**; Knobbe, Martens, Olson & Bear, LLP, 2040 Main Street, 14th Floor, Irvine, California 92614 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: APPARATUS AND METHODS FOR TREATING ROOT CANALS OF TEETH



(57) Abstract: Apparatus and methods for endodontic treatment of teeth provide effective cleaning of organic material (such as pulp and diseased tissue) from the root canal system. In an embodiment, a compressor system generates high pressure liquid (e.g., water) that flows through an orifice to produce a high-velocity collimated jet of liquid. The high-velocity jet is directed toward a surface of a tooth, for example, an exposed dentinal surface, and impingement of the jet onto the surface generates an acoustic wave that propagates throughout the tooth. The acoustic wave effectively detaches organic material from dentinal surfaces and tubules. The detached organic material is flushed from the root canal system by the liquid jet and/or by additional irrigation.

WO 2007/124038 A3

WO 2007/124038 A3



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report*

(88) Date of publication of the international search report:

3 July 2008

APPARATUS AND METHODS FOR TREATING ROOT CANALS OF TEETH

BACKGROUND

Field of the Disclosure

The present disclosure generally relates to methods and apparatus for removing organic matter from a body location and, more particularly, to methods and apparatus for removing organic matter from a root canal system of a tooth.

Description of the Related Art

In conventional root canal procedures, an opening is drilled through the crown of a diseased tooth, and endodontic files are inserted into the root canal system to open the canal and remove organic material therein. The root canal is then filled with solid matter such as gutta percha, and the tooth is restored. However, this procedure will not remove all organic material from all canal spaces. The action of the file during the process of opening the canal creates a smear layer of dentinal filings and diseased organic material on the dentinal walls, which is extremely difficult to remove. The organic material and necrotic tissue that remain in the canal spaces after completion of the procedure often result in post procedure complications such as infections.

SUMMARY

Accordingly, in one aspect there is provided an apparatus for removing organic material from a tooth, comprising: a pressure wave generator arranged to generate a coherent energy beam to propagate pressure wave in supplied fluid of a treatment region of said tooth or a root canal of said tooth, wherein the pressure wave generator is configured to produce pressure waves in said supplied fluid having sufficient energy to cause organic material in the tooth to be detached from surrounding dentin including at locations remote from the pressure wave generator without requiring the coherent energy beam to impact the organic material to be detached.

There is also provided an apparatus for removing organic material from a tooth, comprising: a pressure wave generator configured to generate a coherent energy beam to

propagate pressure waves in supplied fluid at a treatment region of the tooth that provide vibration in at least a portion of the treatment region of the tooth or the root canal, wherein the pressure wave generator produces pressure waves in the supplied fluid having power sufficient to cause organic material in the portion of the tooth or the root canal to be detached from surrounding dentin using the vibration provided by the waves without requiring the coherent energy beam to impact the organic material to be detached, including at locations remote from the pressure wave generator.

There is also provided an apparatus for removing organic material from a tooth comprising: a pressure wave generator configured to generate a coherent energy beam to propagate pressure wave in supplied fluid at a treatment region of a portion of the tooth or a root canal, wherein the pressure wave generator is further configured to produce pressure waves having sufficient energy to cause cavitations in the supplied fluid within the portion of the tooth or the root canal such that organic material is detached from surrounding dentinal tissue without requiring the coherent energy beam to impact the organic material to be detached, including at locations remote from the pressure wave generator.

There is also provided an apparatus for removing organic material from a tooth comprising: a pressure wave generator configured to generate a coherent energy beam to propagate pressure waves through supplied fluid at a treatment region in a portion of the tooth or root canal, wherein the pressure wave generator is configured to produce pressure waves through the supplied fluid with sufficient energy to detach substantially all organic material from surrounding dentin throughout the treatment region of the portion of the tooth or the root canal without requiring the coherent energy beam to impact the substantially all organic material to be detached, including at locations remote from the pressure wave generator.

There is also provided an apparatus for treating a tooth, the apparatus comprising: a cap configured to be applied to the tooth to substantially retain fluid in a treatment region of the tooth; and a pressure wave generator having a distal portion, the distal portion being configured to be inserted through the cap into the treatment region, wherein the pressure wave generator is configured to generate a coherent energy beam through the retained fluid to produce pressure waves with sufficient energy to detach substantially all organic material from surrounding dentin throughout the treatment region without requiring the

coherent energy beam to impact the substantially all organic material to be detached, including at locations remote from the pressure wave generator.

There is also provided an apparatus for treating a tooth, the apparatus comprising: a degassed liquid source; a cap configured to be applied to a tooth, the cap including a fluid inlet through which degassed fluid from the degassed liquid source is delivered into a tooth chamber in the tooth; and a pressure wave generator configured to generate pressure waves through the degassed liquid, the pressure wave generator having an energy outlet configured to be disposed within the tooth chamber, the pressure wave generator configured to create at least some cavitation in the degassed fluid in the tooth chamber to detach organic material from the tooth, including at locations remote from the pressure wave generator.

There is also provided an apparatus for removing organic material from a treatment region of a tooth, comprising: a liquid jet assembly having a liquid pressurization portion which pressurizes a liquid; and a liquid beam forming portion in fluid communication with the pressurization portion, said beam forming portion comprising an orifice that receives the pressurized liquid, said orifice sized, shaped, and positioned to convert the pressurized liquid into a high velocity collimated beam that produces pressure waves within the tooth, the energy of said pressure waves causing organic material within the canal to be detached from dentin without requiring that the liquid beam impact the organic material to be detached, including at locations remote from the beam forming portion.

There is also provided an apparatus for removing organic material from a treatment region of a tooth, comprising: a pressure wave generator configured to generate a coherent energy beam to generate pressure waves in supplied fluid in the treatment region of the tooth; and a handpiece configured to direct the coherent energy beam into the treatment region of the tooth to generate pressure waves of sufficient energy to remove organic material from the treatment region of the tooth without requiring the coherent energy beam to impact the organic material to be removed, including at locations remote from the pressure wave generator, wherein the handpiece comprises a contact member configured to be positioned against a tooth to be treated.

In a further aspect, there is provided an apparatus for treating a treatment region of a tooth, the apparatus comprising: a pressure wave generator configured to direct an energy

beam through fluid in the treatment region of the tooth, wherein the apparatus positions the pressure wave generator such that, when the energy beam passes through the fluid, the energy beam generates pressure waves that propagate through the fluid, the apparatus is configured such that the generated pressure waves create at least some cavitation in the fluid sufficient to clean the treatment region, including at locations remote from the pressure wave generator.

There is also provided an apparatus for treating a tooth, the apparatus comprising: an enclosure configured to be attached to a treatment region of the tooth, the enclosure configured to define a chamber to be filled with a liquid when the enclosure is attached to the tooth; and a pressure wave generator coupled to the enclosure, the pressure wave generator to be at least partially submerged in the liquid, wherein the pressure wave generator is configured to generate pressure waves sufficient to clean the treatment region including at locations remote from the pressure wave generator, the pressure waves created adjacent to a portion of the pressure wave generator submerged in the liquid.

There is also provided an apparatus for treating a tooth, the apparatus comprising: a fluid inlet for supplying fluid to a treatment area of the tooth; and a pressure wave generator configured to generate pressure waves in the supplied fluid to clean the treatment area, including at locations remote from the pressure wave generator, wherein the apparatus positions the pressure wave generator such that the pressure waves generated in the supplied fluid comprise frequencies comprising widespread acoustic noise.

There is also provided an apparatus for removing organic material from a treatment region of a tooth, comprising: a fluid source arranged to deliver a substantially gas-free liquid to the treatment region; and a pressure wave generator configured to generate a coherent energy beam, the pressure wave generator arranged to propagate pressure waves through the liquid in the treatment region, wherein the pressure waves have sufficient energy to cause organic material in the treatment region to be detached from surrounding dentin in the presence of the substantially gas-free liquid, including at locations remote from the pressure wave generator.

There is also provided an apparatus for treating a tooth, the apparatus comprising: a pressure wave generator configured to direct a coherent energy beam through fluid in the tooth; and a pulse intensifier device that causes pulsations in the energy beam, wherein the

apparatus positions the pressure wave generator such that, when the pulsated energy beam passes through the fluid, the pulsated energy beam generates pressure waves that propagate through the fluid, the apparatus configured such that the generated pressure waves create at least some cavitation in the fluid sufficient to clean a treatment region of the tooth, including at locations remote from the pressure wave generator.

There is also provided an apparatus for cleaning a root canal of the tooth, the apparatus comprising: a handpiece configured to be positioned on a side surface of the tooth near an opening in the side surface of the tooth, the handpiece comprising a pressure wave generator, the pressure wave generator configured to propagate pressure waves in the tooth to substantially remove organic material from the root canal when the handpiece is positioned on the side surface of the tooth, including at locations remote from the pressure wave generator.

In a still further aspect, the disclosure describes use of a pressure wave generator and liquid substantially free of dissolved gases for creating cavitation at dentinal surfaces within a root canal system for removing organic material from a tooth.

In a still further aspect, the disclosure describes use of a pressure wave generator and liquid substantially free of dissolved gases for generating a high-velocity liquid jet for treatment of a tooth and for creating cavitation at dentinal surfaces within a root canal system for removing organic material from the tooth, including at locations remote from the pressure wave generator.

In a still further aspect, the disclosure describes use of a pressure wave generator to direct an energy beam through fluid to generate pressure waves through the fluid for creating at least some cavitation in the supplied fluid sufficient to clean a treatment area, including at locations remote from the pressure wave generator.

There is also provided a pressure wave generator for use in generating a coherent energy beam that creates cavitation for removing organic material from a chamber in a tooth without requiring the coherent energy beam to impact the organic material to be removed, including at locations remote from the pressure wave generator.

There is also provided an apparatus for treating a tooth, the apparatus comprising: an enclosure having a mounting surface configured to be positioned against a tooth surface over a treatment region of the tooth, the enclosure configured to define a chamber to be

filled with a liquid when the enclosure is positioned against the tooth; a pressure wave generator coupled with the enclosure and extending through at least a portion of the chamber of the enclosure, the pressure wave generator configured to direct an energy beam through the supplied fluid, wherein, when the energy beam passes through the supplied fluid, the energy beam generates pressure waves that propagate through the fluid, the apparatus configured such that the generated pressure waves create at least some cavitation in the supplied fluid, the generated pressure waves having sufficient energy to clean the treatment region.

There is also provided an apparatus for treating a tooth, the apparatus comprising: an enclosure having a mounting surface configured to be positioned against a tooth surface over a treatment region of the tooth, the enclosure configured to define a chamber to be filled with a liquid when the enclosure is positioned against to the tooth; and a pressure wave generator coupled to the enclosure, the pressure wave generator configured to direct a coherent energy beam into or onto the enclosure through the liquid to generate pressure waves having energy sufficient to clean the treatment region.

There is also provided an apparatus for treating a tooth, the apparatus comprising: an enclosure having a mounting surface configured to be positioned against a tooth surface over a treatment region of the tooth, the enclosure configured to define a chamber to be filled with a liquid when the enclosure is positioned against the tooth; and a pressure wave generator coupled with the enclosure, the pressure wave generator configured to generate pressure waves in the liquid to clean the treatment region, wherein the pressure waves generated in the liquid comprise frequencies comprising widespread acoustic noise

There is also provided an apparatus for removing organic material from a treatment region of a tooth, comprising: a fluid source arranged to deliver a substantially gas-free liquid to the treatment region; an enclosure having a mounting surface configured to be positioned against a tooth surface over the treatment region of the tooth, the enclosure configured to define a chamber to be filled with the substantially gas-free liquid when the enclosure is positioned against the tooth; and a pressure wave generator coupled with the enclosure, the pressure wave generator configured to direct a coherent energy beam, through the delivered liquid to propagate pressure waves through the delivered liquid, wherein the pressure waves have sufficient energy to cause organic material in the

treatment region to be detached from surrounding dentin when the substantially gas-free liquid is at the treatment region.

There is also provided an apparatus for treating an infected or decaying condition in a tooth, the apparatus comprising: a handpiece sized to be at least partially positioned within a mouth of a patient; a pressure wave generator supported at least in part by the handpiece, the pressure wave generator comprising a distal end sized to be positioned at a treatment region of a tooth and being configured to output energy for generating pressure waves; and a microprocessor communicating with the pressure wave generator to control the operation of the pressure wave generator, the handpiece being configured to position the pressure wave generator relative to the treatment region, the pressure wave generator and the microprocessor cooperating to generate a pulsed coherent energy beam, the handpiece supporting the pressure wave generator such that the pulsed coherent energy beam is directed through supplied liquid provided at a portion of the treatment region of the tooth, the pulsed coherent energy beam being of sufficient energy to generate pressure waves of sufficient energy to remove infected or decaying material from the tooth throughout the treatment region, including at locations remote from the portion of the treatment region at which the pulsed coherent energy beam is directed.

There is also provided an apparatus for treating a treatment region of a tooth with fluid supplied by a fluid source, the apparatus comprising: a handpiece sized to be at least partially positioned within a mouth of a patient and proximate to the treatment region; and a pressure wave generator supported at least in part by the handpiece, the handpiece configured to position the pressure wave generator relative to the treatment region so as to direct a coherent energy beam into the supplied fluid at a portion of the treatment region, the coherent energy beam being of sufficient energy to generate pressure waves of sufficient power to remove infected or decaying material throughout the treatment region of ~~from~~ the tooth, including at locations remote from the portion of the treatment region at which the coherent energy beam is directed.

There is also provided an apparatus for cleaning a root canal of the tooth, the apparatus comprising: a handpiece configured to be positioned on a side surface of the tooth near an opening in the side surface of the tooth, the handpiece comprising an acoustic energy generator, the acoustic energy generator configured to propagate acoustic waves in

the tooth to substantially remove organic material from the root canal when the handpiece is positioned on the side surface of the tooth.

There is also provided an apparatus for treating an infected or decaying condition in a tooth, the apparatus comprising: an enclosure having a mounting surface configured to be positioned against a tooth surface at or near a treatment region of the tooth to enclose the treatment region, and an access opening being disposed on the enclosure so as to be exposed to the treatment region when the mounting surface is positioned against the tooth surface; a fluid source having an outlet arranged to supply liquid to the treatment region through the access opening; and a flow pathway in communication with the fluid source, the flow pathway producing a swirling flow profile within at least the liquid passing through the access opening toward the treatment region.

There is also provided an apparatus for treating an infected or decaying condition in a tooth, the apparatus comprising: an enclosure having a mounting surface configured to be positioned against a tooth surface at or near a treatment region of the tooth to enclose the treatment region, and an access opening being disposed on the enclosure so as to be exposed to the treatment region when the mounting surface is positioned against the tooth surface; and a pressure wave generator configured to interact with the enclosure such that the pressure wave generator is disposed so as to be at least partially submerged in a liquid medium in the treatment region, wherein the pressure wave generator is configured to generate pressure waves within the liquid medium of sufficient power to remove infected or decaying material from the tooth at the treatment region.

For purposes of this summary, certain aspects, advantages, and novel features of the invention are described herein. It is to be understood that not necessarily all such advantages may be achieved in accordance with any particular embodiment of the invention. Thus, for example, those skilled in the art will recognize that the invention may be embodied or carried out in a manner that achieves one advantage or group of advantages as taught herein without necessarily achieving other advantages as may be taught or suggested herein.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGURE 1 is a cross-section view schematically illustrating a root canal system of a tooth.

FIGURE 2 is a scanning electron microscope photograph of a dentinal surface within a canal system in a tooth and shows numerous dentinal tubules on the dentinal surface.

FIGURE 3 is a block diagram schematically illustrating an embodiment of a compressor system adapted to produce a high-velocity liquid jet.

FIGURES 4 and 4A are cross-section views schematically illustrating an embodiment of a handpiece that can be used to maneuver the high-velocity liquid jet.

[0018] FIGURE 5A is cross-section view schematically illustrating a distal end of an embodiment of a handpiece configured to deliver a high-velocity liquid jet.

[0019] FIGURE 5B is a graph showing an example velocity profile of a coherent collimated jet.

[0020] FIGURE 6A is a cross-section view schematically showing an endodontic method in which a high-velocity jet is directed toward dentin through an opening in the top of a tooth.

[0021] FIGURE 6B is a cross-section view schematically showing another endodontic method in which the high-velocity jet is directed toward the dentin through an inlet opening in a side of the tooth and a relief opening in the top of the tooth is provided to reduce pressure buildup, if present, and to permit debridement.

[0022] FIGURE 6C is a cross-section view schematically illustrating an embodiment of a positioning member prior to adherence to a tooth.

[0023] FIGURE 6D is a cross-section view schematically illustrating an embodiment of a positioning member adhered to a side of a tooth and used to assist coupling the distal end of the handpiece to the side of the tooth so that the high-velocity jet may be directed through the inlet opening.

[0024] FIGURE 7 schematically illustrates production of an acoustic wave caused by impingement of a high-velocity liquid jet onto a dentinal surface.

[0025] FIGURE 8A is a cross-section view schematically illustrating cavitation bubbles formed near odontoblasts at the dentinal surface.

[0026] FIGURE 8B schematically illustrates collapse of a cavitation bubble and formation of a cavitation jet near a dentinal surface.

[0027] FIGURES 9A-9C are scanning electron microscope photographs of dentinal surfaces following treatment of the tooth with the high-velocity jet; FIGURE 9A shows dentinal tubules in an apical area of a mature tooth magnified 1000x; FIGURES 9B and 9C show dentin and dentinal tubules magnified 1000x in an inclusion area of a juvenile tooth (FIG. 9B) and in a medial area of a mature root (FIG. 9C). A bar at the top left of each photo indicates the linear scale (in microns) for each photograph.

[0028] FIGURES 10A-10H schematically illustrate embodiments of a cap that may be attached to a distal end of a handpiece and fitted onto a tooth. FIGURES 10A and 10C-10H are side views, and FIGURE 10B is a partially exploded cross-section view.

[0029] FIGURE 11 schematically illustrates a method for generating an acoustic wave using a piezoelectric transducer.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0030] The present disclosure provides various apparatus and methods for dental treatments that overcome possible disadvantages associated with conventional root canal treatments. In certain embodiments, endodontic treatment methods (e.g., root canal therapy) comprise directing a high-velocity liquid jet toward a tooth. Impact of the jet causes acoustic energy to propagate from a site of impact through the entire tooth, including the root canal system of the tooth. The acoustic energy is effective at detaching substantially all organic material in the root canal system from surrounding dentinal walls. In many embodiments, the detached organic material can be flushed from the root canal using low-velocity irrigation fluid. As used herein organic material (or organic matter) includes organic substances typically found in healthy or diseased root canal systems such as, for example, soft tissue, pulp, blood vessels, nerves, connective tissue, cellular matter, pus, and microorganisms, whether living, inflamed, infected, diseased, necrotic, or decomposed.

[0031] FIGURE 1 is a cross section schematically illustrating a typical human tooth 10, which comprises a crown 12 extending above the gum tissue 14 and at least one root 16 set into a socket (alveolus) within the jaw bone 18. Although the tooth 10 schematically depicted in FIGURE 1 is a molar, the apparatus and methods described herein may be used on any type of tooth such as an incisor, a canine, a bicuspid, or a molar. The hard tissue of the tooth 10 includes dentin 20 which provides the primary structure of the tooth 10, a very hard enamel layer 22 which covers the crown 12 to a cements/enamel junction 15 near the gum 14, and cementum 24 which covers the dentin 20 of the tooth 10 below the cements/enamel junction 15.

[0032] A pulp cavity 26 is defined within the dentin 20. The pulp cavity 26 comprises a pulp chamber 28 in the crown 11 and a root canal space 30 extending toward an apex 32 of each root 16. The pulp cavity 26 contains dental pulp, which is a soft, vascular

tissue comprising nerves, blood vessels, connective tissue, odontoblasts, and other tissue and cellular components. The pulp provides innervation and sustenance to the tooth through the epithelial lining of the pulp chamber 26 and the root canal space 30. Blood vessels and nerves enter/exit the root canal space 30 through a tiny opening, the apical foramen 32, near a tip of the apex 32 of the root 16.

[0033] FIGURE 2 depicts a pulpal surface of the dentin 20. The dentin 20 comprises numerous, closely-packed, microscopic channels called dentinal tubules 34 that radiate outwards from the interior walls of the canal space 30 through the dentin 20 toward the exterior cementum 24 or enamel 22. The tubules 34 run substantially parallel to each other and have diameters in a range from about 1.0 to 3.0 microns. The density of the tubules 34 is about 5,000 – 10,000 per mm^2 near the apex 32 and increases to about 15,000 per mm^2 near the crown.

[0034] The dentin 20 is continuously formed by specialized cells called odontoblasts that secrete a mineralized substance that hardens into dentin. Odontoblasts form a single layer of cells between the dentin 20 and the pulp. An odontoblast has a cell body that is located on the pulpal surface of the dentin 20 on a tubule 34 and a cytoplasmic portion, called the odontoblastic process, that extends into and substantially fills the associated tubule 34. The odontoblasts are connected to each other with interodontoblastic collagen, and collagen fibrils may attach the odontoblast layer to the pulp. As a person ages, the odontoblasts continue to form dentin, which causes the root canal space 30 to decrease in diameter.

[0035] FIGURE 3 is a block diagram that schematically illustrates a compressor system 38 adapted to generate a high-velocity jet of fluid for use in dental procedures. The compressor system 38 comprises a source of compressed gas 40 such as a pressurized air or gas source commonly available in dental service installations. The compressed gas 40 may be pressurized in a range from about 50 pounds per square inch (psi) to 150 psi including, for example, 100 psi. The compressed gas 40 may comprise any suitable commercially available gas including, for example, air, nitrogen, carbon dioxide, or a combination thereof. The compressed gas 40 is pneumatically connected to a pump 46 via a regulator 42. The regulator 42 can be used to regulate the pressure of the input gas to a desired pressure such

as, for example, 40 psi. In some embodiments, the pump 46 comprises an air-driven hydraulic pressure intensifier that uses the compressed gas 40 to increase the pressure of liquid received from a fluid source 44. For example, a pressure intensifier having a 330:1 pressure intensification ratio can increase the pressure of the liquid to about 13,200 psi using pressurized gas at 40 psi from the regulator 42. Different pressure intensification ratios may be used in different embodiments. By adjusting the gas pressure with the regulator 42, the pressure of the liquid output from the pump 46 can be selectably adjusted to a desired value or range of values. In some embodiments, the pressure of the liquid can be adjusted within a range from about 500 psi to about 50,000 psi. In certain embodiment, it has been found that a pressure range from about 2,000 psi to about 11,000 psi produces jets that are particularly effective for endodontic treatments.

[0036] The fluid source 44 may comprise a fluid container (e.g., an intravenous bag) holding sterile water, a medical-grade saline solution, an antiseptic or antibiotic solution, a solution with chemicals or medications, or any combination thereof. More than one fluid source may be used. In certain embodiments, it is advantageous for jet formation if the liquid provided by the fluid source 44 is substantially free of dissolved gases (e.g., less than 0.1% by volume) and particulates, which can act as nucleation sites for bubbles. In some embodiments, the fluid source 44 comprises degassed distilled water. A bubble detector (not shown) may be disposed between the fluid source 44 and the pump 46 to detect bubbles in the liquid and/or to determine whether liquid flow from the fluid source 44 has been interrupted or the container has emptied. The liquid in the fluid source 44 may be at room temperature or may be heated and/or cooled to a different temperature. For example, in some embodiments, the liquid in the fluid source 44 is chilled to reduce the temperature of the high velocity jet generated by the compressor system 38.

[0037] In the embodiment depicted in FIGURE 3, the high-pressure liquid from the pump 46 is fed to a regulator 48 and then to a handpiece 50, for example, by a length of high-pressure tubing 49. The regulator 48 may be operable with compressed gas from the source 40 and may be used to regulate the pressure of the liquid to a desired value. For example, in one embodiment, the regulator 48 reduces the 13,200 psi pressure from the pump 46 to about 12,000 psi. The regulator 48 may include water pressure sensors and bleed-off

valves (e.g., an air-driven needle valve) to provide the desired pressure and to permit an operator to actuate/deactuate water jet output from the handpiece 50.

[0038] The handpiece 50 receives the high pressure liquid and is adapted at a distal end to generate a high-velocity, coherent, collimated beam or jet 60 of liquid for use in dental procedures. The handpiece 50 may be sized and shaped to be maneuverable so that the jet 60 may be directed toward or away from various portions of the tooth 10.

[0039] The compressor system 38 may include a controller 51 that controls the operation of the components of the system 38. The controller 51 may comprise a microprocessor, a special or general purpose computer, a floating point gate array, and/or a programmable logic device. In one embodiment, the controller 51 is used to operate the regulators 42, 48 and the pump 46 so that the high-pressure liquid delivered to the handpiece 50 is at a suitable working pressure. The controller 51 may also be used to control safety of the system 38, for example, by limiting system pressures to be below safety thresholds and/or by limiting the time that the jet 60 is permitted to flow from the handpiece 50. In certain embodiments, the controller 51 may be used to vary or cycle the pressure of the liquid delivered to the handpiece 50, for example, by cycling pressures provided by one or both of the regulators 42, 48. In certain such embodiments, sinusoidal or sawtooth pressure variability may be used to provide corresponding variability in the speed of the jet 60. In certain embodiments, cycle time for the pressure variability may be in a range from about 0.1 seconds to about 5 seconds. Additionally and optionally, the controller 51 may regulate a pulse intensifier device (not shown), such as a piezoelectric transducer, that causes pulsations in the jet 60. For example, in certain embodiments, the jet 60 comprises a pulsed jet, which may include a series of discrete liquid pulses, a continuous stream of fluid having spatially varying pressure, velocity, and/or area, or a combination thereof. The controller 51 advantageously may control the amplitude and frequency of the pulsations in the jet 60. In certain embodiments, the amplitude of the pressure variation may be in a range from several hundred to several thousand psi. The pulse frequency may be in a range from about 0.1 Hz to about 10 MHz. For example, in some embodiments, a pulse frequency of about 1 MHz is applied to produce a jet comprising a series of droplets.

The system 38 may also include a user interface 53 that outputs relevant system data and accepts user input. In some embodiments, the user interface 53 comprises a touch screen graphics display. In some embodiments, the user interface 53 may display information including the working liquid pressure in the handpiece 50 and instructions and/or procedures for operating on different tooth types (e.g., incisors, bicuspid, or molars). The user interface 53 may accept user input such as a time setting that sets a maximum time during which the compressor system 38 will deliver the jet 60 and other useful endodontic treatment options. For example, some embodiments permit an operator to select a "ramp up" and/or "ramp down" option in which the working liquid pressure can be gradually increased or decreased, respectively. The ramp up option advantageously may be used for initial aiming of the jet 60 towards a suitable portion of the tooth 10, while the ramp down advantageously may be used if the jet 60 is moved toward a sensitive portion of the tooth 10 (e.g., the apex 32). The compressor system 38 may also include a storage medium (e.g., volatile or nonvolatile memory) configured to store system operating information and executable instructions, user preferences, preferred operating pressures and times, patient data, etc. In some embodiments, the storage medium comprises on-board memory of the controller 51 and/or additional random access or read-only memory, flash memory, removable memory cards, etc.

The compressor system 38 may include additional and/or different components and may be configured differently than shown in FIGURE 3. For example, the system 38 may include an aspiration pump that is coupled to the handpiece 50 (or an aspiration cannula) to perform aspiration of organic matter from the mouth or tooth 10. In other embodiments, the compressor system 38 may comprise other pneumatic and/or hydraulic systems adapted to generate the high-velocity beam or jet 60. For example, certain embodiments may utilize apparatus and systems described in U.S. Patent No. 6,224,378, issued May 1, 2001, entitled "METHOD AND APPARATUS FOR DENTAL TREATMENT USING HIGH PRESSURE LIQUID JET," and/or U.S. Patent No. 6,497,572, issued December 24, 2002, entitled "APPARATUS FOR DENTAL TREATMENT USING HIGH PRESSURE LIQUID JET".

[0042] Moreover, in other embodiments, the high-velocity jet 60 may be generated by systems other than the high-pressure compressor system 38, such as, for example, by a pump system. In one such embodiment, an electric motor drives a pump that is in fluid communication with a liquid reservoir. The pump increases the velocity of the liquid so as to provide a narrow beam of high-velocity liquid from the handpiece 50. In some embodiments, multiple pumps are used. As is well known from Bernoulli's law, the total pressure in a flowing fluid includes static (e.g., thermodynamic) pressure plus dynamic pressure (associated with fluid kinetic energy). A skilled artisan will recognize that static pressures in motor-driven pump systems may be less than static pressures in compressor systems, because the motor-driven pump primarily increases the dynamic pressure (e.g., the fluid velocity) of the liquid. The total pressures (static plus dynamic) achieved are comparable in many embodiments of compressor systems and pump systems.

[0043] FIGURES 4 and 4A are cross-section views that schematically illustrate one embodiment of the handpiece 50 adapted for forming the high-velocity jet 60. The handpiece 60 comprises an elongated tubular barrel 52 having a central passageway 54 extending axially therethrough. The handpiece 50 has a proximal end 56 that is adapted to engage tubing from the regulator 48 in order for the passageway 54 to be in fluid communication with the high pressure liquid delivered by the compressor system 38. The barrel 52 may include features 55 that enhance grasping the handpiece with the fingers and thumb of the operator. A distal end 58 of the barrel 52 (shown in closeup in FIG. 4A) includes a threaded recess adapted to engage complementary threads of an orifice mount 62, which is configured to hold an orifice jewel 64 at an end thereof. The orifice mount 62 is tightly screwed into the distal end 58 of the barrel 52 to secure the orifice jewel 64 adjacent to a distal end of the passageway 52.

[0044] The orifice jewel 64 may comprise a circular, disc-like element having a small, substantially central orifice 66 formed therein. The orifice jewel 64 may be fabricated from a suitably rigid material that resists deformation under high pressure such as, for example, synthetic sapphire or ruby. The orifice mount 62 advantageously secures the orifice jewel 64 substantially perpendicular to the passageway 54 so that high pressure liquid in the passageway 54 can flow through the orifice 66 and emerge as a highly collimated beam of

fluid traveling along a longitudinal jet axis 70 that is substantially coaxial with the barrel 52 of the handpiece 50. In some embodiments, the distal end 58 of the handpiece 50 may include additional components, for example, to assist guiding or directing the jet 60 and/or to provide aspiration. Also, as further described below, the distal end 58 of the handpiece 50 may be adapted to receive various end caps that assist guiding the jet 60 toward the pulp cavity 26.

[0045] FIGURE 5A is a cross-section schematically illustrating the distal end 58 of an embodiment of the handpiece 50 to further illustrate formation of the jet 60. The orifice jewel 64 is secured at the distal end of the handpiece 50 and forms a tight seal to prevent leakage of high-pressure liquid 68 contained in the passageway 54. In the depicted embodiment, the orifice jewel 64 has a proximal side that is substantially flat and a distal side that is concave (e.g., thinnest near the orifice 66). The orifice 66 has a substantially circular cross-section with a diameter "D." The axial length of sides 69 of the orifice 66 is "L." The diameter D may be in a range from about 5 microns to about 1000 microns. Other diameter ranges are possible. In various embodiments, the diameter D may be in a range from about 10 microns to about 100 microns, a range from about 100 microns to about 500 microns, or range from about 500 microns to about 1000 microns. In various preferred embodiments, the orifice diameter D may be in a range of about 40-80 microns, a range of about 45-70 microns, or a range of about 45-65 microns. In one embodiment, the orifice diameter D is about 60 microns. The ratio of axial length L to diameter D may be about 50:1, 20:1, 10:1, 5:1, 1:1, or less. In one embodiment, the axial length L is about 500 microns. In certain embodiments, the ratio of axial length L to diameter D is selected so that transverse width of any boundary layers that may form on the sides 69 of the orifice 66 have a transverse width that is sufficiently small, for example, much less than the diameter D.

[0046] In certain embodiments, the sides 69 of the orifice 66 are machined, polished, or otherwise processed to be substantially smooth in order to reduce or prevent formation of turbulence, cavitation, bubbles, fluid instabilities, or other effects that may interfere with substantially smooth, laminar flow of the liquid through the orifice 66. For example, in certain such embodiments, the sides 69 have a root-mean-square (rms) surface roughness less than about 10 microns, less than about 1 micron, or less than about 0.1

microns. In other embodiments, the rms surface roughness is much smaller than the diameter D of the orifice such as, for example, less than about 0.1 D, less than about 0.01 D, less than about 0.001 D, or less than about 0.0001 D. Additionally, highly demineralized liquids may be used to reduce buildup of impurities along the sides 69, which advantageously may increase the useful operating lifetime of the orifice jewel 64.

[0047] As schematically depicted in FIGURE 5A, the high pressure liquid 68 in the passageway 54 emerges through the orifice 66 as a high-velocity, collimated jet 60 traveling substantially along the jet axis 70 with a velocity, v. In some embodiments of the compressor system 38, the jet velocity is estimated to be proportional to $(P/\rho)^{1/2}$, where P is the liquid pressure in the passageway 54 and ρ is the density of the liquid. In certain embodiments, water pressurized to about 10,700 psi emerges from the orifice as a jet 60 having a velocity of about 220 m/s. By adjusting the liquid pressure delivered by the compressor system 38, the handpiece 50 can deliver jets having different velocities. In some embodiments, the user interface 53 permits the operator to selectively adjust system pressures so that the velocity of the jet is suitable for a particular dental treatment.

[0048] In certain embodiments of the system 38, the liquid used to form the jet 60 is substantially free from dissolved gases (e.g., less than about 0.1% per volume). If the dissolved gas content of the liquid is too high, bubbles may formed at the nozzle orifice 66 due to the pressure drop. Additionally, the pressure drop should preferably be sufficiently low to prevent formation of vapor at the distal end of the orifice 66. The presence of substantial vapor, gas or bubbles, or particle contaminants in the liquid may cause a significant portion of the energy of the liquid jet 60 to be depleted, and there may be insufficient kinetic energy (and/or momentum) to provide efficient cleaning of the root canal system.

[0049] The jet 60 emerges from the distal end of the orifice 66 as a beam of fluid traveling substantially parallel to the jet axis 70. Such jets are called "collimated" jets. In certain embodiments, the angular divergence of the jet 60 is less than about 1 degree, less than about 0.1 degree, or less than about 0.01 degree. In other embodiments, jet beams with different angular divergences may be used. In some embodiments, the jet 60 can travel as a collimated beam for a distance of about 1 to 3 inches before the jet 60 begins to disperse

(e.g., due to entrainment of air). In certain embodiments, the jet 60 may travel a distance at least several thousand times the jet diameter D before beginning to disperse.

[0050] As described above, it may be advantageous for the sides 69 of the orifice 66 to be sufficiently smooth that liquid flows through the orifice 66 in a substantially laminar manner. In certain embodiments, the transverse width of any boundary layers formed along the sides 69 of the orifice 66 is much smaller than the diameter D , and, away from the boundary layers, the speed of the jet 60 is substantially constant across the width of the orifice. FIGURE 5B is a graph schematically illustrating an example velocity profile of the jet 60 after it has emerged from the distal end of the orifice 66. The graph depicts flow velocity in the direction of the jet axis 70 versus a distance transverse (e.g., orthogonal) to the jet axis 70. In this example embodiment, away from narrow boundary layers near the outer surface of the jet 60 (e.g., near 0 and D on the graph), the jet velocity is substantially constant across the width of the jet. Jets having substantially constant velocity profiles are called “coherent” jets. In other embodiments, the velocity profile of the jet 60 is not substantially constant across the width of the jet 60. For example, the jet velocity profile in certain embodiments is a parabolic profile well-known from pipe flow.

[0051] In certain embodiments, the compressor system 38 is configured to deliver a coherent, collimated jet 60 of high-velocity liquid. A coherent, collimated jet will be denoted herein as a “CC jet.” The following example provides various representative properties of a CC jet 60 that can be generated using an embodiment of the system 38. In this example system, the diameter D and the axial length L of the orifice 66 are 60 microns and 500 microns, respectively. In one embodiment, the pressure of the liquid (degassed, distilled water) in the handpiece 50 is about 8,000 psi, which produces a jet velocity of about 190 m/s. The mass discharge rate of the jet is about 0.5 g/s, and the jet can produce a force of about 0.1 Newton when impacting a surface at normal incidence. The jet provides a kinetic power of about 10 Watts. If the jet is directed toward a tooth for about 10 seconds, the jet can deliver a momentum (or impulse) of about 1 kg m/s and an energy of about 100 Joules (about 23 calories).

[0052] In other embodiments, the CC jet is produced from liquid pressurized to about 2500 psi. The jet velocity is about 110 m/s, and volume flow rate is about 0.3 mL/s.

The CC jet can produce about 2 W of kinetic power. The jet 60 may remain substantially collimated over propagation lengths from about 1 cm to about 30 cm in various embodiments.

[0053] The energy flux produced by the liquid jet is the kinetic power of the jet divided by the transverse area of the jet beam. The energy flux may be in a range from about 1 kW/cm² to about 1000 kW/cm². In some embodiments, the energy flux is in a range from about 50 kW/cm² to about 750 kW/cm², including, for example, 70 kW/cm², 175 kW/cm², 350 kW/cm², and 550 kW/cm². In one experiment, a CC jet was directed toward a dentinal surface of a tooth, and widespread acoustic noise (possibly due to acoustic cavitation) was detected in the tooth when the energy flux of the jet exceeded about 75 kW/cm². At the onset of detectable acoustic noise, the CC jet had the following properties: velocity of about 110 m/s, kinetic power of about 2 W, and mass flow rate of about 0.3 g/s. The pressure producing the CC jet was about 2500 psi.

[0054] By using different fluid working pressures and/or orifice diameters, jets having different properties can be generated. For example, in certain embodiments, the mass discharge rate may be in a range from about 0.01 g/s to about 1 g/s, the jet velocity may be in range from about 50 m/s to about 300 m/s, the jet force may be in a range from about 0.01 N to about 1 N, and the jet power may be in a range from about 0.1 W to about 50 W. In various endodontic treatments, the jet is applied to a tooth for a time in a range from about 1 second to 120 seconds. Accordingly, in such treatments, the jet can deliver momentum (or impulse) in a range of about 0.01 kg m/s to about 100 kg m/s, and energy in a range of about 0.1 J to about 500 J. In some embodiments, an energy range from about 20 J to about 400 J may be effective at providing cleaning of the root canal system without causing substantial erosion of dentin. A person of ordinary skill will recognize that the compressor system 38 can be configured to provide liquid jets having a wide range of properties that may be different from the example values and ranges provided herein, which are intended to be illustrative and non-limiting.

[0055] In various dental treatments, the compressor system 38 delivers a jet 60, which advantageously may be a CC jet, that is directed toward one or more portions of a

tooth in order to, for example, excise and/or emulsify organic material, provide irrigation, and/or generate acoustic energy for delaminating organic matter from the pulp cavity 26.

[0056] FIGURE 6A schematically illustrates one embodiment of an endodontic treatment for diseased pulp in the tooth 10. A drill or grinding tool is initially used to make an opening 80 in the tooth 10. The opening 80 may extend through the enamel 22 and the dentin 20 to expose and provide access to pulp in the pulp cavity 26. The opening 80 may be made in a top portion of the crown 12 of the tooth 10 (as shown in FIG. 3) or in another portion such as a side of the crown 12 or in the root 16 below the gum 14. The opening 80 may be sized and shaped as needed to provide suitable access to the diseased pulp and/or some or all of the canal spaces 30. In some treatment methods, additional openings may be formed in the tooth 10 to provide further access to the pulp and/or to provide dental irrigation.

[0057] The handpiece 50 may be used to deliver a jet 60 of liquid to a portion of the tooth 10. The jet 60 advantageously may, but need not, be a CC jet. The jet 60 can be used to cut through organic material in the pulp chamber 28. Additionally, as will be further described below, the jet 60 may be directed toward hard surfaces of the tooth 10 (e.g., the dentin 20) to generate acoustic energy, which may propagate through the dentin 20, the dentinal tubule, and the organic material in the root canal space 30. The acoustic energy causes detachment of organic material from the dentin 20 without requiring that the jet directly impact the organic material. In certain embodiments, the acoustic energy has been found to be effective in causing detachment of the entire body of pulp (and other organic material) from within the pulp chamber 28 and/or root canal space 30, without the use of endodontic files. The jet 60 preferably should have insufficient energy, energy flux, and/or momentum to damage or substantially erode the dentin 20.

[0058] In some treatment methods, the operator can maneuver the handpiece 50 to direct the jet 60 around the pulp chamber 28 during the treatment process. The distal end of the handpiece 50 may be held about 1 inch from the tooth 10 so that the liquid impacts a portion of the tooth 10 as a substantially collimated coherent beam. The jet 60 may provide sufficient force to cut through and/or emulsify some or all of the organic material in the pulp chamber 28. The flow of liquid from the jet 60 may create sufficient swirling or turbulent

flow to remove the cut and/or emulsified organic material from the pulp cavity 26 so that it can be aspirated from the mouth of the patient. In other treatment embodiments, pulpal tissue in the pulp chamber 28 may be removed via conventional techniques prior to (and/or during) liquid jet treatment to expose a portion of the dentin 20. The jet 60 may then be directed to the exposed portion.

[0059] The jet 60 may be directed toward the floor 82 of the pulp chamber 28 (see, e.g., FIG. 7). In some methods, the jet 60 is directed toward the floor 82 (and/or walls) of the pulp chamber 28 advantageously at a substantial angle (e.g., 15-50 degrees) relative to the long axis of the root canal space 30 to ensure that the jet does not directly impact the apical portion of the canal space 30, thereby reducing a possibility that the force (and/or pressure) imparted by the jet 60 will cause damage to healthy tissue around the apical foramen 34. Accordingly, certain disclosed treatment methods advantageously may be used on "open apex" teeth having underdeveloped and/or enlarged apices, because impingement of the jet 60 in the pulp chamber 28 will not harm the periapical portion of the tooth 10. Additionally or optionally, the jet 60 can be directed toward one or more sides of the pulp chamber 28 so as to impact the dentin 20. In some embodiments, the jet is directed to several locations in or on the tooth 10. An advantage of some methods is that the impact of the jet 60 on the dentin 20 does not cause significant erosion or destruction of the dentin 20 within the tooth 10. Accordingly, such methods may be minimally invasive in comparison with conventional root canal procedures.

[0060] The pulp cavity 26 may fill with fluid during the treatment. For sufficiently high working pressures, the jet 60 will have sufficient velocity to impact submerged dentin 20 with enough force to provide effective treatment. In certain embodiments of the treatment method, one or more properties of the jet 60 are temporally varied during the treatment. For example, the working pressure may be varied to ramp up or ramp down the jet velocity or to cause the jet to alternate between high-speed flow and low-speed flow. The jet 60 may comprise a pulsed jet with pulsation amplitude and/or frequency selected to provide effective treatment. A combination of the above treatment methods may be used, serially or in alternation.

[0061] As noted above, detachment of the organic material within the root canal system from the surrounding dentin 20 does not require that the jet 60 impact the organic material in the root canal space 30. Rather, the jet 60 may be directed against a dentinal wall (e.g., in the pulp chamber 28), which couples acoustic energy to the tooth 10 so as to cause detachment of the organic material. In some methods, the detachment occurs relatively quickly after the jet 60 impinges on the dentinal wall (e.g., within a few seconds) and may occur substantially simultaneously throughout one or more root canal spaces 30 of the tooth 10.

[0062] In one presently preferred method schematically illustrated in FIGURE 6B, the jet beam 60 is introduced into an inlet opening 84 formed in the side (e.g., buccal or lingual surface) of the tooth 10 with a conventional dental drill. The opening 84 may be formed near the cementoenamel junction 15. In some procedures, a portion of the gum 14 is depressed to provide access to the intended position of the opening 84 near the cementoenamel junction 15. The opening 84 may have a diameter in a range from about 1 mm to about 2 mm and may extend from the exterior surface of the tooth 10 to the pulp chamber 28. In some embodiments, the diameter is about 1.2 mm. Different diameters may be used in other embodiments. The opening 84 is thus generally transverse to the long axis of any root canal space 30 and ensures that the energy of the jet 60 will not be directed down any canal spaces 30. A benefit of providing the opening 84 in the side of the tooth 10 is that less hard tissue of the tooth 10 is damaged than if the opening were formed through the occlusal surface of the tooth 10. Although it is presently preferred to use a single inlet opening 84 to reduce invasiveness of the procedure, in other methods, two or more inlet openings may be used.

[0063] FIGURES 6C and 6D are cross-section views schematically illustrating an embodiment of a positioning member 130 that may be used to assist coupling and orienting the distal end 58 of the handpiece 50 to the tooth 10 so that the high-velocity jet 60 is directed through the inlet opening 84 in the side of the tooth 10. In the illustrated embodiment, the positioning member 130 comprises a collar portion 134 that may be generally disk-like in shape. The collar portion 134 may have a width in a range from about 1 mm to about 10 mm. The collar portion 134 may have a substantially central opening 136

having a diameter approximately equal to the diameter of the inlet opening 84. In some embodiments, the collar portion 134 is formed from a flexible material (such as an elastomer) so that it can conform to the surface of the tooth 10. An adhesive (such as a light-cured orthodontic adhesive) may be included on a surface 134a of the collar portion 134 to enable the positioning member 130 to adhere to the tooth 10. In some embodiments, a detachable, elongated peg 138 may be used to position the position member 130 so that the central opening 136 in the collar portion 134 is aligned with the inlet opening 84 in the tooth 10. A distal end of the peg 138 may be sized to fit within the opening 84. When the positioning member 130 is in position on the tooth 10 and the adhesive has sufficiently cured, the peg 138 may be removed, leaving the positioning member 130 adhered to the side of the tooth 10 (see FIG. 6D). Additionally or alternatively, the collar portion 134 may include alignment guides disposed near the opening 136 to assist positioning the member 130 over the opening 84. For example, a circular ridge, having an outside diameter slightly smaller than the inside diameter of the opening 84, may be formed on the surface 134a around the opening 136 and used to align the openings 84 and 136.

[0064] The positioning member 130 may include mounting portions 132a configured to engage complementary mounting portions 132b disposed on the distal end 58 of the handpiece 50. For example, the mounting portions 132a, 132b may comprise a standard, quick-turn connector such as a Luer-lock. FIGURE 6D schematically illustrates the handpiece 50 before (or after) engagement with the positioning member 130. When engaged with the positioning member 130, the handpiece 50 advantageously is oriented so that the jet axis 70 is substantially longitudinally aligned with the inlet opening 84. Moreover, the positioning member 130 may stabilize the handpiece 50 against unwanted movement. Accordingly, upon actuation, the jet 60 will be directed through the opening 84 and into the pulp cavity 26. As further described below with reference to FIGURE 10B, the distal end 58 of the handpiece 50 may comprise one or more pressure sensors adapted to sense when the distal end 58 is securely engaged with the positioning member 130. In such embodiments, the system may not permit the jet 60 to be actuated until a sufficiently secure fit and proper alignment are indicated by signals from the pressure sensors.

[0065] When the distal end 58 of the handpiece 50 is engaged with the positioning member 130, the jet 60 may be directed through the inlet opening 84 so that it impacts the dentinal wall and causes detachment of the organic material in the root canal spaces 30. After the treatment is completed, the positioning member 130 may be removed from the tooth 10 using any well-known technique for releasing the adhesive. Remaining adhesive, if present, may function as bonding for restorative material used to close the defect.

[0066] To reduce possible buildup of fluid pressure within the pulp cavity 26, a relief opening 88 may be formed in the top side (e.g., occlusal surface) of the tooth 10. The relief opening 88 may be formed on a buccal or lingual surface. The diameter of the relief outlet or opening 88 may be larger than that of the inlet opening 84, for example, about 2 mm to about 3 mm. In some methods, the diameter of the relief opening 88 may be about the same as (or smaller than) the diameter of the inlet opening 84 (e.g., about 1.2 mm in one embodiment). The relief opening 88 also serves to facilitate debridement and evacuation of the detached organic material. The diameter of the relief opening 88 advantageously may be large enough to permit flushing out pulp fragments. In some methods, two or more relief openings 88 may be used.

[0067] Those skilled in dentistry will recognize that the inlet and relief openings 84, 88 are quite small relative to the openings required for conventional root canal procedures, thus preserving valuable tooth structure. For example, in some methods, even though two openings 84, 88 are used, less tooth material is removed than in a conventional root canal procedure using a single, standard-sized occlusal opening. Moreover, many patients have existing coronal defects (e.g., decay, restorations, preparations, etc.), and it may be possible to form one or both of the openings simply by removing material other than healthy tooth tissue, such as a filling. Fillings on one or more sides of the tooth 10 may also be used to form the openings 84, 88. In any event, once the jet has caused acoustically induced detachment of the organic material, low pressure flushing fluid (such as water) may be introduced into either or both the openings 84, 88 to irrigate the canal space 30 and flush out the organic material. Additionally and optionally, manual extraction of organic material may be performed with a dental instrument.

[0068] Certain teeth, particularly molars and/or wisdom teeth, may be difficult to access in conventional root canal therapies due to limited working space in the back of the mouth. Due to the difficulties or inconvenience of coronal access to these teeth in conventional root canal therapies, some of these teeth, which would otherwise be treatable, may instead be extracted. An advantage of some embodiments of the disclosed methods is that by permitting a wider range of access with the liquid jet 60 (e.g., on or through coronal, lingual, and/or buccal surfaces), the acoustic-induced detachment of organic material can save the tooth and reduce the likelihood of its extraction.

[0069] Without subscribing to any particular theory of operation, FIGURE 7 schematically illustrates an explanation for the effectiveness of the treatment methods described herein. FIGURE 7 depicts the jet 60 impacting the dentin 20 of the tooth 10. Upon impact, a portion of the energy and/or momentum carried by the jet 60 generates an acoustic pressure wave 100 that propagates through the body of the tooth 10. In addition to propagating through the dentin 20, the acoustic wave 100 may propagate through organic material in the root canal space 30 and in the tubules of the dentin 20. The acoustic wave 100 may include acoustic energy with acoustic frequencies in a range from about 1 Hz to above 5 MHz such as, for example, up to about 10 MHz. The acoustic wave 100 may have frequency components in the ultrasonic frequency range, e.g., above about 20 kHz. In some cases, the frequency range may include megasonic frequencies above about 1 MHz. The acoustic wave 100 may include other frequencies as well.

[0070] At the dentinal surfaces of the root canal space 30 and tubules, the acoustic wave 100 may cause surrounding liquid to cavitate. This cavitation may be a surface effect cavitation caused by conversion of the water (or other liquid) from a liquid state to a vapor state. If the acoustic energy in the wave 100 is sufficiently large, the cavitation processes may include inertial cavitation wherein sufficiently low pressures caused by the acoustic wave 100 induce formation and collapse of bubbles in liquid near the dentinal surfaces. For smaller acoustic energies, non-inertial (or gas) cavitation may play a more significant role. In such cases, dissolved gases, tissue debris, and impurities act as nucleation centers for the formation of cavitation bubbles. Cavitation may also occur at pore sites across the microporous surface of the dentin 20. The cavitation bubbles oscillate in response to the

acoustic wave 100, and amplitude of the oscillations may grow as additional gas is absorbed by the bubble.

[0071] Due to the relatively high energy required for formation of cavitation bubbles, collapse of the cavitation bubble occurs with great force against the surface of the dentin 20. Bubble collapse near a surface is known to occur asymmetrically and may result in formation of cavitation jets that radiate toward the surface and produce locally very high pressures and/or elevated temperatures. In some cases, the acoustic wave 100 may also generate fluid motions (acoustic streaming) that enhance disruption of organic matter. Acoustic streaming also may be effective at transporting or flushing detached organic matter out of the root canal space 30 and/or the tubules.

[0072] Accordingly, in certain methods, the acoustic wave 100 cleans the root canal system through processes including formation and collapse of cavitation bubbles, radiation of cavitation jets toward dentinal surfaces, acoustic streaming, or a combination thereof. In the process, the organic material may be broken into small pieces or particles, which can be irrigated from the pulp cavity 26. In some treatment methods, these cavitation processes may produce transient, localized high pressure and/or elevated temperature zones that disrupt, detach, and/or delaminate organic matter near root canal surfaces. For example, cavitation-induced effects may detach odontoblasts from the dentinal surface and effectively remove a portion of the odontoblastic process from the tubule. Cavitation-induced effects may also disrupt and/or detach the collagen fibrils that attach the odontoblast layer to the pulp in the interior of the canal space 30. Cavitation-induced effects may also occur in interior regions of the pulp cavity 26 (e.g., away from the dentinal surfaces) and may disrupt and/or loosen organic material in the interior regions, thereby making this material more readily removable from the pulp cavity 26.

[0073] Cavitation effects are believed to be formed everywhere the acoustic wave 100 propagates with sufficient energy. Accordingly, it is advantageous for the jet 60 to have sufficient energy and/or momentum to generate an acoustic wave 100 capable of causing cavitation effects throughout substantially the entire root canal system but without causing harm to the tooth 10. For example, if the jet diameter D is too small and the momentum of the jet beam too high, impact of the beam may cause significant dentinal erosion. On the

other hand, if the beam diameter D is too large and the momentum of the jet beam too low, the beam may have insufficient energy to produce an acoustic pressure wave 100 capable of causing cavitation. For example, in certain methods, the jet energy incident on the tooth is greater than about 20 J to provide effective cleaning but less than about 400 J to prevent dentinal erosion. In some methods, acoustic cavitation effects occur substantially throughout the root canal system when certain jet 60 properties are above threshold values. For example, in one experiment mentioned above, widespread acoustic noise (possibly caused by acoustic cavitation) was detected in a tooth only when the energy flux of the jet 60 was greater than about 75 kW/cm². At the onset of detectable acoustic noise, the jet had a power of about 2 W, a velocity of about 115 m/s, a mass flow rate of about 0.3 g/s, and provided a force of about 0.03 N. The efficiency of conversion of jet kinetic energy into acoustic energy was estimated to be about 2%.

[0074] A portion of the acoustic wave 100 may also propagate through tissue and bone adjacent the tooth 10. However, the energy carried by this portion of the acoustic wave 100 may be relatively small due to the acoustic impedance mismatch between the dentin 20 and nearby tissues and bone. Accordingly, cavitation-induced effects may be substantially reduced in tissues surrounding the tooth 10, and the endodontic methods described herein will not significantly damage the surrounding tissues.

[0075] FIGURES 8A and 8B are cross-section views that schematically illustrate some of the cavitation processes that clean a surface 104 of the dentin 20. As depicted in FIGURE 8A, odontoblasts 106 are located near the surface and the odontoblastic process extends into the tubules 108. The acoustic wave 100 induces oscillation and collapse of cavitation bubbles 110, which generates transient localized heat and/or pressure that disrupts and detaches the odontoblasts 106 from the dentinal surface 104. Cavitation bubbles may also form and collapse within the tubules 108, thereby causing disruption of the odontoblastic processes in the tubules 108. FIGURE 8B schematically depicts collapse of an initially spherical cavitation bubble 110 (shown in (i)) located near the body of organic matter 112 adjacent the dentinal surface 104 and filling the canal. In (ii), the side of the bubble 110 away from the surface 104 is perturbed from its spherical shape. In (iii), fluid 114 from the interior of the pulp cavity 26 penetrates the perturbed side of the bubble 110. In (iv) the fluid

114 has formed a cavitation jet 116 radiating toward the surface 104. The energy and momentum of the cavitation jet 116 breaks up and disperses the organic matter 112.

[0076] FIGURES 9A-9C are scanning electron microscope photographs of the dentinal surface showing the surprising effectiveness of the removal of organic matter by the acoustic effect. FIGURE 9A shows dentinal tubules in an apical area of a mature tooth magnified 1000x. FIGURES 9B and 9C show dentin and dentinal tubules magnified 1000x in an inclusion area of a juvenile tooth (FIG. 9B) and in a medial area of a mature root (FIG. 9C). A bar at the top left of each photo indicates the linear scale (in microns) for each photograph. As can be seen in FIGURES 9A-9C, the dentinal surfaces are almost entirely free from organic matter, which appears to have been literally ripped away from the dentin. Flow of liquid in the root canal space 30 flushes and irrigates the organic matter from substantially all the root canal space 30 and the tubules. Returning to FIGURE 2, this photograph shows an apical area of a mature tooth magnified 2000x and viewed at a slight slant from perpendicular to show that the tubules have been cleaned down to a distance of about 3 microns. FIGURES 2 and 9A-9C demonstrate that cleaning of the dentinal surface is very effective and that almost no remnants of organic material remain after treatment.

[0077] As mentioned previously, it has been found that the cleaning does not require that the liquid jet 60 be aimed down the root canal space 30, although that may be beneficial in certain isolated cases where the canal space 30 is very narrow and/or filled with dry material. Additionally, it has been found in some embodiments that the pulp cavity 26 need not be prepared or pre-treated (e.g., by removing root canal matter with one or more endodontic files) before application of the jet. Impingement of the jet 60 onto the dentin 20 in the pulp chamber 28 is sufficient in most cases to generate the acoustic wave 100 that causes the cleaning. Accordingly, in most cases, it is the acoustic wave 100 and not direct impact of the jet 60 that causes the cleaning, particularly for the dentinal surfaces near the apex of the root canal space 30, which are remote from the pulp chamber 28. For example, examination of FIGURES 2 and 9A-9C shows that organic material has been removed from apical dentinal tubules, which are not possible to reach directly with the liquid jet beam. In certain embodiments, the jet beam 60 is capable of delivering sufficient energy to the tooth 10 to remove at least 90 percent of the organic material from the root canal system. In other

embodiments, at least 95 percent of the organic material is removed. Preferably, the jet beam should be capable of removing substantially all the organic material from the root canal space 30 and from at least a portion of the tubules. The treatment time during which the high-velocity jet is directed toward the tooth 10 may range from about 1 second to about 120 seconds. In some embodiments, the treatment time is from about 10 seconds to about 30 seconds. In other embodiments, the treatment time is no more than 10 seconds such as, for example, less than about 5 seconds, less than about 2 seconds, less than about 1 second, less than about 0.5 second, or less than about 0.1 second.

[0078] The high-velocity jet 60 may produce significant mechanical power (e.g., tens of Watts in some embodiments). When the jet 60 is directed toward the tooth 10, a fraction of this mechanical power may go toward heating the tooth 10 as well as nearby teeth and gums. To avoid discomfort to the patient, in some embodiments, excess heat, if present, may be removed by, for example, irrigating the tooth under treatment with a stream of liquid (e.g., water at room temperature or cooler). The stream of liquid can absorb and carry away some or all of the excess heat, if present, that may be produced by the jet 60. The stream of liquid may be aspirated from the patient's mouth.

[0079] The methods described herein may be used as standalone treatments for root canal procedures, or they may be used in conjunction with other dental treatments (which may or may not involve liquid jet methods).

[0080] The high-velocity jet treatment methods described herein may be particularly effective in certain system operating ranges. For example, a jet having an energy flux greater than about 75 kW/cm^2 may be particularly effective.

[0081] The apparatus and methods described above may include additional devices and components configured to provide additional functionality to the endodontic treatment system. FIGURES 10A-10H schematically illustrate embodiments of a contact member configured as a cap 120 that may be attached to and detached from the distal end 58 of the handpiece 50. In some embodiments, the cap 120 may have threads that engage complimentary threads on the distal end 58 of the handpiece 50 (see, e.g., FIG. 10B). The cap 120 can be fitted around the crown 12 of the tooth 10 and used to orient the jet 60 toward a suitable opening into the pulp chamber 26. The cap 120 may be used to orient the distal

end 58 of the handpiece 50 so that the liquid jet 60 is directed obliquely at a dentinal surface on the floor 82 (and/or sides) of the pulp cavity 26 and not directly down any of the canal space 30. The cap 120 may be formed from a transparent or translucent material and may be sufficiently flexible to fit around teeth having a range of sizes. In some embodiments, the distal end 58 of the handpiece 50 may be rotatable and/or extendable with respect to the cap 120 so that the jet 60 may be moved closer to or further from a desired tooth portion. The cap 120 may include an outflow opening to permit organic material and liquid to be evacuated from the tooth 10. In certain embodiments, the distal end 58 of the handpiece 50 may include multiple orifices which provide multiple jets, and the cap 120 may be used to orient the handpiece 50 such that jets are directed not only at the floor 82 (and/or sides) of the pulp chamber 28, but also towards entrances to the canal spaces 30. In some embodiments, the handpiece 50 may also be tilted and rotated to allow the jet 60 to be aimed axially into all canal openings.

[0082] As schematically shown in FIGURES 10C-10H, a plurality of caps 120 may be configured to fit over teeth of different sizes and shapes. Advantageously, each different cap 120 may be color coded to permit easy selection by the dentist during a treatment procedure. The cap 120 may also be sized and shaped to fit within an opening formed in the tooth 10 at the beginning of certain endodontic procedures (such as the openings 80, 84, and 88; see FIGS. 6A-6C), rather than fitting over or around the exterior of the tooth 10.

[0083] As depicted in the partially exploded cross-section view shown in FIGURE 10B, the distal end 58 of the handpiece 50 may include one or more pressure sensors 124. As the cap 120 is urged onto a tooth (or into an opening in the tooth), the pressure sensor 124 provides a signal that indicates when a sufficiently "tight" fit has been achieved. The pressure sensor 124 may be electrically connected to the controller 52, and enables the jet 60 to operate only when the sensor senses contact. A suitable audible, visible, and/or tactile signal may be output (e.g., by the user interface 54 or by an output device on the handpiece 50) to indicate that the cap 120 is in position on the tooth 10.

[0084] The system may also include a distance sensor to indicate the distance between the distal end 58 of the handpiece 50 and a surface of the tooth 10. The distance

sensor may provide an audible, tactile, and/or visible indication when the distal end 58 is at a suitable distance from the surface for operation of the liquid jet 60 (e.g., not too close to damage the tooth and not too far for the jet to be ineffective). In one embodiment, the distance sensor comprises a pair of optical elements mounted on the handpiece and spaced from each other. Each optical element directs an optical beam that intersects the other beam a predetermined distance away from the handpiece 50. The operator of the handpiece 50 can maneuver the handpiece 50 until the intersecting beams illuminate a desired portion of the tooth 10 and then actuate the liquid jet 60. The optical elements may comprise light-emitting diodes (LEDs) and/or lasers. In some embodiments, more than two optical elements may be used (e.g., to indicate a range of distances).

[0085] A person of ordinary skill will recognize that a wide variety of sensors may be used in addition to or instead of the pressure sensor 124 and/or the distance sensor. For example, certain embodiments utilize one or more electric, magnetic, acoustic, and/or optical sensors to determine position and/or orientation of the handpiece 50 (or portions thereof) in the mouth. For example, proximity sensors, including capacitive sensors, ultrasonic sensors, light reflectance sensors, magnetic inductance sensors, and so forth, may be used. Certain embodiments may comprise one or more orientation sensors (e.g., accelerometers) configured to sense the orientation of the longitudinal jet axis 70 relative to one or more reference landmarks in the mouth (e.g., a portion of the tooth 10 such as the openings 80, 84, 88). The system may include a timer configured to deactuate the jet 60 after a predetermined time interval to reduce likelihood of damage to the tooth 10 and/or root canal system. Systems comprising one or more such sensors advantageously may provide increased safety. For example, certain such embodiments may prevent (or inhibit) an operator from actuating the liquid jet 60 until the distal end 58 of the handpiece 50 is suitably positioned and/or oriented adjacent the tooth 10.

[0086] As described herein, acoustic energy capable of producing cavitation may be particularly effective at cleaning the root canal system. It has been found that this acoustic energy may be efficiently produced by directing a high-velocity beam of liquid onto a portion of the tooth. However, the scope of the present disclosure is not limited to methods using high-velocity jets. In other embodiments, the acoustic energy is generated by vibrating

mechanical devices (e.g., a piezoelectric transducer), ultrasonic (or megasonic) generators (e.g., an ultrasonic and/or a megasonic horn), or any other component capable of producing acoustic vibrations. FIGURE 11 schematically illustrates one method for generating the acoustic wave 100 using a piezoelectric transducer 144. In this method, an enclosure 142 is attached to the tooth 10. The enclosure 142 comprises a chamber 140 filled with a liquid (e.g., water). The transducer 144 is disposed in or on the chamber 140. When actuated, the transducer 144 vibrates, which causes the acoustic wave 100 to propagate through the surrounding fluid and the tooth 10. The acoustic wave 100 cleans the root canal system substantially as described above. Because the vibrating transducer 144 is not in direct contact with the tooth 10, possible damage to the tooth 10 is reduced or eliminated. Although in FIGURE 11 a mechanical transducer 144 is used to generate the acoustic wave 100, in other embodiments, the acoustic wave 100 may be produced by, for example, directing the high-velocity liquid jet into or onto the enclosure 142. In such embodiments, the enclosure 142 acts as an "acoustic waveguide" converting jet kinetic energy into acoustic energy that propagates through the tooth 10 as the acoustic wave 100. Beneficially, the liquid in the chamber 140 may absorb excess mechanical energy which may otherwise produce unwanted heat in the tooth 10. In another embodiment, an ultrasonic horn is disposed near the enclosure 142 and used to generate the acoustic wave 100.

[0087] Any of the procedures described herein may be carried out with the use of a rubber dam. Further although the tooth 10 depicted in the figures is a molar, one of ordinary skill in the art will appreciate that the procedures may be performed on any type of tooth such as an incisor, a canine, a bicuspid, or a molar. Also, the disclosed methods are capable of cleaning root canal spaces having a wide range of morphologies, including highly curved root canal spaces which are difficult to clean using conventional dental techniques. Moreover, the disclosed methods may be performed on human teeth (including children's teeth) and/or on animal teeth.

[0088] The foregoing description sets forth various preferred embodiments and other illustrative but non-limiting embodiments of the inventions disclosed herein. The description provides details regarding combinations, modes, and uses of the disclosed inventions. Other variations, combinations, modifications, equivalents, modes, uses,

implementations, and/or applications of the disclosed features and aspects of the embodiments are also within the scope of this disclosure, including those that become apparent to those of skill in the art upon reading this specification. Additionally, certain objects and advantages of the inventions are described herein. It is to be understood that not necessarily all such objects or advantages may be achieved in any particular embodiment. Thus, for example, those skilled in the art will recognize that the inventions may be embodied or carried out in a manner that achieves or optimizes one advantage or group of advantages as taught herein without necessarily achieving other objects or advantages as may be taught or suggested herein. Also, in any method or process disclosed herein, the acts or operations making up the method/process may be performed in any suitable sequence and are not necessarily limited to any particular disclosed sequence.

[0089] Accordingly, the scope of the inventions disclosed herein is to be determined according to the following claims and their equivalents.

**THE EMBODIMENTS OF THE INVENTION IN WHICH AN EXCLUSIVE
PROPERTY OR PRIVILEGE IS CLAIMED ARE DEFINED AS FOLLOWS:**

1. An apparatus for removing organic material from a tooth, comprising:

a pressure wave generator arranged to generate a coherent energy beam to propagate pressure wave in supplied fluid of a treatment region of said tooth or a root canal of said tooth,

wherein the pressure wave generator is configured to produce pressure waves in said supplied fluid having sufficient energy to cause organic material in the tooth to be detached from surrounding dentin including at locations remote from the pressure wave generator without requiring the coherent energy beam to impact the organic material to be detached.
2. The apparatus of Claim 1, wherein the pressure wave generator is adapted to generate cavitation adjacent a surface of the dentinal tissue within a root canal system of the tooth.
3. The apparatus of any one of Claims 1 to 2, wherein said pressure wave produced by the pressure wave generator having sufficient energy to detach substantially all organic material from surrounding dentin throughout a root canal system of the tooth.
4. The apparatus of any one of Claims 1 to 3, wherein a portion of the pressure wave generator is configured to be positioned within the tooth.
5. The apparatus of any one of Claims 1 to 4, wherein the pressure wave generator comprises a liquid jet system.
6. The apparatus of any one of Claims 1 to 5, further comprising a cap configured to be applied to the tooth to substantially retain fluid in a tooth chamber in the tooth.

7. The apparatus of any one of Claims 5 to 6, wherein the liquid jet system comprises a liquid pressurization portion which pressurizes a liquid and a liquid beam forming portion in fluid communication with the pressurization portion, said beam forming portion comprising an orifice that receives the pressurized liquid, said orifice sized and shaped to convert the pressurized liquid into a high velocity collimated beam that generates the pressure wave within the treatment region.

8. The apparatus of Claim 7, further comprising a handpiece configured to support the beam forming portion of the liquid jet system.

9. An apparatus for removing organic material from a tooth, comprising:

a pressure wave generator configured to generate a coherent energy beam to propagate pressure waves in supplied fluid at a treatment region of the tooth that provide vibration in at least a portion of the treatment region of the tooth or the root canal,

wherein the pressure wave generator produces pressure waves in the supplied fluid having power sufficient to cause organic material in the portion of the tooth or the root canal to be detached from surrounding dentin using the vibration provided by the waves without requiring the coherent energy beam to impact the organic material to be detached, including at locations remote from the pressure wave generator.

10. The apparatus of Claim 9, wherein the pressure wave generator comprises a liquid jet assembly.

11. The apparatus of Claim 10, wherein the liquid jet assembly comprises a liquid pressurization portion which pressurizes a liquid and a liquid beam forming portion in fluid communication with the pressurization portion, said beam forming portion comprising an orifice that receives the pressurized liquid, said orifice sized and shaped to convert the pressurized liquid into a high velocity collimated beam that generates the pressure waves within the tooth.

12. The apparatus of any one of Claims 9 to 11, further comprising a handpiece configured to support the beam forming portion of the liquid jet assembly.

13. The apparatus of any one of Claims 9 to 12, wherein a portion of the pressure wave generator is configured to be positioned within the tooth.

14. An apparatus for removing organic material from a tooth comprising:

a pressure wave generator configured to generate a coherent energy beam to propagate pressure wave in supplied fluid at a treatment region of a portion of the tooth or a root canal,

wherein the pressure wave generator is further configured to produce pressure waves having sufficient energy to cause cavitations in the supplied fluid within the portion of the tooth or the root canal such that organic material is detached from surrounding dentinal tissue without requiring the coherent energy beam to impact the organic material to be detached, including at locations remote from the pressure wave generator.

15. The apparatus of Claim 14, said pressure wave generator is configured to produce sufficient energy to detach substantially all organic material from surrounding dentinal tissue throughout the root canal system.

16. The apparatus of any one of Claims 14 to 15, wherein the pressure wave generator comprises a liquid jet assembly.

17. The apparatus of any one of Claims 14 to 16, wherein a portion of the pressure wave generator is configured to be positioned within the tooth.

18. An apparatus for removing organic material from a tooth comprising:

a pressure wave generator configured to generate a coherent energy beam to propagate pressure waves through supplied fluid at a treatment region in a portion of the tooth or root canal,

wherein the pressure wave generator is configured to produce pressure waves through the supplied fluid with sufficient energy to detach substantially all organic material from surrounding dentin throughout the treatment region of the portion of the tooth or the root canal without requiring the coherent energy beam to impact the

substantially all organic material to be detached, including at locations remote from the pressure wave generator.

19. The apparatus of Claim 18, wherein the pressure wave generator comprises a liquid jet assembly.

20. The apparatus of any one of Claims 18 to 19, wherein a portion of the pressure wave generator is configured to be positioned within the tooth.

21. An apparatus for treating a tooth, the apparatus comprising:

a cap configured to be applied to the tooth to substantially retain fluid in a treatment region of the tooth; and

a pressure wave generator having a distal portion, the distal portion being configured to be inserted through the cap into the treatment region,

wherein the pressure wave generator is configured to generate a coherent energy beam through the retained fluid to produce pressure waves with sufficient energy to detach substantially all organic material from surrounding dentin throughout the treatment region without requiring the coherent energy beam to impact the substantially all organic material to be detached, including at locations remote from the pressure wave generator.

22. The apparatus of Claim 21, wherein the pressure wave generator is configured to generate pressure wave in the treatment region, said pressure waves having sufficient energy to cause organic material in the tooth to be detached from surrounding dentin.

23. The apparatus of any one of Claims 21 to 22, wherein the cap comprises an outflow opening to permit organic material and liquid to be evacuated from the tooth.

24. The apparatus of any one of Claims 21 to 23, wherein the apparatus further comprises a handpiece.

25. The apparatus of any one of Claims 21 to 24, wherein the pressure wave generator is configured to generate pressure waves, and wherein the cap is configured to

retain sufficient fluid within the tooth chamber to permit the pressure waves to propagate within the fluid.

26. The apparatus of Claim 25, wherein a substantial amount of the pressure waves generated by the pressure wave generator retains sufficient energy to create at least some surface effect cavitation within the treatment region

27. The apparatus of any one of Claims 21 to 20, wherein the cap is configured to be positioned around the treatment region such that the cap substantially closes an access opening into a tooth chamber of the treatment region.

28. The apparatus of any one of Claims 21 to 27, wherein the pressure wave generator is configured to create at least some surface effect cavitation in the treatment region.

29. The apparatus of any one of Claims 21 to 28, wherein the pressure wave generator comprises a liquid jet device.

30. The apparatus of any one of Claims 21 to 29, wherein the pressure wave generator comprises a vibrating mechanical device.

31. The apparatus of Claim 30, wherein the vibrating mechanical device comprises a piezoelectric transducer.

32. The apparatus of any one of Claims 21 to 31, wherein the pressure wave generator comprises an ultrasonic or megasonic generator.

33. An apparatus for treating a tooth, the apparatus comprising:

a degassed liquid source;

a cap configured to be applied to a tooth, the cap including a fluid inlet through which degassed fluid from the degassed liquid source is delivered into a tooth chamber in the tooth; and

a pressure wave generator configured to generate pressure waves through the degassed liquid, the pressure wave generator having an energy outlet configured to be

disposed within the tooth chamber, the pressure wave generator configured to create at least some cavitation in the degassed fluid in the tooth chamber to detach organic material from the tooth, including at locations remote from the pressure wave generator.

34. The apparatus of Claim 33, wherein the degassed liquid source is configured to deliver degassed fluid to clear organic material from the tooth.

35. The apparatus of any one of Claims 33 to 34, wherein the pressure wave generator is in fluid communication with the fluid inlet and the degassed liquid source.

36. Use of a pressure wave generator and liquid substantially free of dissolved gases for creating cavitation at dentinal surfaces within a root canal system for removing organic material from a tooth, including at locations remote from the pressure wave generator.

37. The use of claim 36, wherein the concentration of dissolved gases is less than 0.1% by volume.

38. Use of a pressure wave generator and liquid substantially free of dissolved gases for generating a high-velocity liquid jet for treatment of a tooth and for creating cavitation at dentinal surfaces within a root canal system for removing organic material from the tooth, including at locations remote from the pressure wave generator.

39. The use of claim 38, wherein the concentration of dissolved gases is less than 0.1% by volume.

40. An apparatus for removing organic material from a treatment region of a tooth, comprising:

a liquid jet assembly having a liquid pressurization portion which pressurizes a liquid; and

a liquid beam forming portion in fluid communication with the pressurization portion,

said beam forming portion comprising an orifice that receives the pressurized liquid, said orifice sized, shaped, and positioned to convert the pressurized liquid into a high velocity collimated beam that produces pressure waves within the tooth, the energy of said pressure waves causing organic material within the canal to be detached from dentin without requiring that the liquid beam impact the organic material to be detached, including at locations remote from the beam forming portion.

41. The apparatus of Claim 40, wherein the organic material is detached along a length of the canal, the detachment extending to an apical opening of the tooth.

42. The apparatus of any one of Claims 40 to 41, further comprising a reservoir for said liquid, wherein said liquid is substantially free of dissolved gases.

43. The apparatus of any one of Claims 40 to 42, further comprising a reservoir for said liquid, wherein said liquid is substantially mineral free.

44. The apparatus of any one of Claims 40 to 43, where said orifice has a transverse width in a range from about 10 microns to about 200 microns.

45. The apparatus of any one of Claims 40 to 44, where said orifice has an axial length in a range from about 50 microns to about 1000 microns.

46. The apparatus of any one of Claims 40 to 45, comprising a positioning member configured to position said orifice relative to an opening into a pulp cavity of the tooth such that the high velocity beam passes through said opening.

47. The apparatus of Claim 46, wherein said orifice is disposed in a distal end portion of a handpiece.

48. The apparatus of Claim 47, wherein the positioning member comprises a contact member on the distal end of the handpiece, said contact member configured to contact the tooth and stabilize the handpiece against unwanted movement relative to the tooth.

49. The apparatus of Claim 48, further comprising a pressure sensor which senses pressure on said contact member and a switch which enables said liquid beam only when pressure is sensed by said pressure sensor.

50. The apparatus of any one of Claims 48 to 49, wherein the contact member comprises a cap which fits around the tooth.

51. The apparatus of any one of Claims 48 to 50, further comprising a plurality of contact members of different sizes adapted to be attached to and detached from the handpiece.

52. The apparatus of any one of Claims 40 to 51, wherein the kinetic energy of said liquid jet is oscillatory over time.

53. The apparatus of Claim 52, wherein said liquid jet assembly further comprises a pulse intensifier configured to produce said oscillations.

54. The apparatus of any one of Claims 52 to 53, wherein the oscillations have a frequency in a range from about 1 Hz to about 10 MHz

55. The apparatus of any one of Claims 40 to 54, comprising a controller for ramping up or ramping down the pressure of the pressurized liquid.

56. The apparatus of any one of Claims 40 to 55, wherein the high velocity beam has a velocity in a range from about 50 m/s to about 300 m/s.

57. An apparatus for removing organic material from a treatment region of a tooth, comprising:

a pressure wave generator configured to generate a coherent energy beam to generate pressure waves in supplied fluid in the treatment region of the tooth; and

a handpiece configured to direct the coherent energy beam into the treatment region of the tooth to generate pressure waves of sufficient energy to remove organic material from the treatment region of the tooth without requiring the coherent energy beam to

impact the organic material to be removed, including at locations remote from the pressure wave generator,

wherein the handpiece comprises a contact member configured to be positioned against a tooth to be treated.

58. The apparatus of Claim 57, wherein the pressure waves have sufficient energy to create surface effect cavitation at dentinal surfaces with a root canal system to detach organic material from surrounding dentin in the tooth.

59. The apparatus of any one of Claims 57 to 58, wherein the pressure wave generator comprises a liquid jet apparatus, and wherein the handpiece is configured to direct the liquid jet.

60. The apparatus of Claim 59, further comprising a sensor configured to sense contact of the contact member with the tooth, wherein the liquid jet apparatus is configured to activate only after said contact is sensed by the sensor.

61. A pressure wave generator for use in generating a coherent energy beam that creates cavitation for removing organic material from a chamber in a tooth without requiring the coherent energy beam to impact the organic material to be removed, including at locations remote from the pressure wave generator.

62. The pressure wave generator of claim 61, wherein the pressure wave generator comprises a high-velocity liquid jet device.

63. An apparatus for treating a treatment region of a tooth, the apparatus comprising:

a pressure wave generator configured to direct an energy beam through fluid in the treatment region of the tooth,

wherein the apparatus positions the pressure wave generator such that, when the energy beam passes through the fluid, the energy beam generates pressure waves that propagate through the fluid, the apparatus is configured such that the generated pressure

waves create at least some cavitation in the fluid sufficient to clean the treatment region, including at locations remote from the pressure wave generator.

64. The apparatus of Claim 63, wherein the energy beam comprises a coherent energy beam.

65. The apparatus of Claim 64, wherein the energy beam comprises a liquid jet.

66. Use of a pressure wave generator to direct an energy beam through fluid to generate pressure waves through the fluid for creating at least some cavitation in the supplied fluid sufficient to clean a treatment area, including at locations remote from the pressure wave generator.

67. An apparatus for treating a tooth, the apparatus comprising:

an enclosure configured to be attached to a treatment region of the tooth, the enclosure configured to define a chamber to be filled with a liquid when the enclosure is attached to the tooth; and

a pressure wave generator coupled to the enclosure, the pressure wave generator to be at least partially submerged in the liquid,

wherein the pressure wave generator is configured to generate pressure waves sufficient to clean the treatment region including at locations remote from the pressure wave generator, the pressure waves created adjacent to a portion of the pressure wave generator submerged in the liquid.

68. The apparatus of Claim 67, wherein the pressure wave generator comprises a liquid jet device which directs a high-velocity liquid jet into or onto the enclosure.

69. An apparatus for treating a tooth, the apparatus comprising:

a fluid inlet for supplying fluid to a treatment area of the tooth; and

a pressure wave generator configured to generate pressure waves in the supplied fluid to clean the treatment area, including at locations remote from the pressure wave generator,

wherein the apparatus positions the pressure wave generator such that the pressure waves generated in the supplied fluid comprise frequencies comprising widespread acoustic noise.

70. An apparatus for removing organic material from a treatment region of a tooth, comprising:

a fluid source arranged to deliver a substantially gas-free liquid to the treatment region; and

a pressure wave generator configured to generate a coherent energy beam, the pressure wave generator arranged to propagate pressure waves through the liquid in the treatment region,

wherein the pressure waves have sufficient energy to cause organic material in the treatment region to be detached from surrounding dentin in the presence of the substantially gas-free liquid, including at locations remote from the pressure wave generator.

71. An apparatus for treating a tooth, the apparatus comprising:

a pressure wave generator configured to direct a coherent energy beam through fluid in the tooth; and

a pulse intensifier device that causes pulsations in the energy beam,

wherein the apparatus positions the pressure wave generator such that, when the pulsated energy beam passes through the fluid, the pulsated energy beam generates pressure waves that propagate through the fluid, the apparatus configured such that the generated pressure waves create at least some cavitation in the fluid sufficient to clean a treatment region of the tooth, including at locations remote from the pressure wave generator.

72. The apparatus of any one of Claims 63 to 65, wherein the pressure wave generator comprises a liquid jet device, an ultrasonic or megasonic generator, or a vibrating mechanical device.

73. The apparatus of any one of Claims 67 to 72, wherein the pressure wave generator comprises a liquid jet device configured to form a liquid jet.

74. The apparatus of Claims 73, wherein the liquid jet device comprises a liquid pressurization portion which pressurizes a liquid and a liquid beam forming portion in fluid communication with the pressurization portion, said beam forming portion comprising an orifice that receives the pressurized liquid, said orifice sized and shaped to convert the pressurized liquid into the liquid jet, the liquid jet comprising a high velocity collimated beam that produces pressure wave within the tooth, the energy of said wave causing organic material to be detached from dentin.

75. The apparatus of Claim 74, wherein said orifice has a transverse width in a range from about 10 microns to about 200 microns.

76. The apparatus of any one of Claims 74 to 75, wherein said orifice has an axial length in a range from about 50 microns to about 1000 microns.

77. The apparatus of any one of Claims 74 to 76, wherein the diameter of the orifice is in a range from about 10 microns to about 100 microns.

78. The apparatus of Claim 77, wherein the diameter of the orifice is in a range from about 45 microns to about 65 microns.

79. The apparatus of any one of Claims 74 to 78, wherein sides of the orifice have a root-mean-square surface roughness less than about 10 microns.

80. The apparatus of any one of Claims 73 to 79, wherein a pressure of the liquid used to produce the liquid jet is in a range from about 2,000 psi to about 11,000 psi.

81. The apparatus of any one of Claims 73 to 80, wherein a pressure of the liquid used to produce the liquid jet is in a range from about 7,000 psi to 15,000 psi.

82. The apparatus of any one of Claims 73 to 81, wherein the liquid jet has an energy flux in a range from about 50 kW/cm² to about 1000 kW/cm².

83. The apparatus of any one of Claims 73 to 82, wherein the liquid jet has a velocity in a range from about 50 m/s to about 300 m/s.

84. The apparatus of any one of Claims 1 to 8, 14 to 20, 22 to 34, and 57 to 64, wherein the pressure waves comprise frequencies comprising widespread acoustic noise.

85. The apparatus of any one of Claims 9 to 13 and 40 to 56, wherein the pressure waves comprise frequencies comprising widespread acoustic noise.

86. The apparatus of any one of Claims 63 to 65, 67 to 68, and 70, wherein the pressure wave comprises frequencies comprising widespread acoustic noise.

87. The apparatus of any one of Claims 69 and 84 to 86, wherein the frequencies comprise frequencies in a range from about 1 Hz to about 10 MHz.

88. The apparatus of any one of Claims 9 to 20, 63 to 65 and 67 to 87, further comprising a cap configured to be applied to the tooth to substantially retain fluid in a tooth chamber in the tooth.

89. The apparatus of any one of Claims 33 to 35 and 88, the cap further including an outflow opening to permit organic material and liquid to be evacuated from the tooth.

90. The apparatus of any one of Claims 21 to 35, 88 or 89, wherein the cap includes a suction port configured to remove fluid from the tooth at substantially the same rate that it is introduced.

91. The apparatus of any one of Claims 1 to 35, 40 to 60, 63 to 65 and 69 to 87, further comprising an enclosure configured to be attached to the tooth, the enclosure including a chamber configured to be filled with the liquid.

92. The apparatus of any one of Claims 67 and 91, wherein the pressure wave generator is disposed in or on the chamber and configured to cause pressure waves to propagate through the fluid.

93. The apparatus of any one of Claims 67 and 91 to 92, wherein the enclosure comprises a contact member on a distal end of a handpiece, said contact member configured to contact the tooth and stabilize the handpiece against unwanted movement relative to the tooth.

94. The apparatus of any one of Claims 63 to 65 and 67 to 93, further comprising a controller in operable communication with the pressure wave generator.

95. Use of a liquid jet for removing organic material from a root canal by directing a liquid jet into a pulp chamber of a tooth through an opening in a side of the tooth at a substantial angle to a long axis of the root canal, including the removal of organic material from locations remote from the location(s) at which the liquid jet is directed.

96. An apparatus for cleaning a root canal of the tooth, the apparatus comprising:

a handpiece configured to be positioned on a side surface of the tooth near an opening in the side surface of the tooth, the handpiece comprising a pressure wave generator,

the pressure wave generator configured to propagate pressure waves in the tooth to substantially remove organic material from the root canal when the handpiece is positioned on the side surface of the tooth, including at locations remote from the pressure wave generator.

97. The apparatus of Claim 96, wherein the pressure wave generator comprises a liquid jet device.

98. The apparatus of Claim 97, wherein the liquid jet device is configured to direct a liquid jet through the opening.

99. The apparatus of any one of Claims 96 to 98, wherein the pressure wave generator is configured to propagate pressure waves in the tooth to substantially remove organic material from the root canal when the pressure wave generator is activated outside the tooth.

100. The apparatus of any one of Claims 96 to 99, further comprising a positioning member configured to be coupled to the side surface of the tooth, the positioning member configured to engage a distal portion of the handpiece.

101. The apparatus of Claim 100, wherein the positioning member comprises a central opening configured to provide fluid communication between the opening in the side surface of the tooth and a distal portion of the handpiece.

102. The apparatus of any one of Claims 96 to 101, further comprising a reservoir of liquid that is substantially free of dissolved gases, the reservoir configured to be in fluid communication with the handpiece.

103. The apparatus of any one of Claims 96 to 102, wherein the pressure wave generator is configured to generate pressure waves in the tooth with frequencies in a range of about 1 Hz to about 10 MHz.

104. The apparatus of any one of Claims 96 to 103, wherein the pressure wave generator is configured to direct energy through the opening in the side surface of the tooth.

105. The apparatus of any one of Claims 96 to 104, further comprising an enclosure coupled with the handpiece, the enclosure configured to be positioned on the side surface of the tooth to at least partially define a chamber.

106. The apparatus of any one of Claims 96 to 105, wherein the pressure wave generator is disposed at least partially within the chamber defined by the enclosure.

107. The apparatus of Claim 97, further comprising a pump configured to pressurize the liquid that forms the liquid jet.

108. The apparatus of any one of Claims 1 to 32, 40 to 60, 63 to 68 and 71 to 107, further comprising a fluid source arranged to deliver a substantially gas-free liquid to the tooth.

109. The apparatus of Claim 69, wherein the fluid inlet is arranged to deliver a substantially gas-free liquid to the tooth.

110. The apparatus of any one of Claims 33, 70, 102, and 108 to 109, wherein the substantially gas-free liquid includes less than 1% dissolved gases by volume.

111. The apparatus of any one of Claims 33, 70, 102, and 108 to 110, wherein said apparatus generates pressure waves sufficient to cause organic material to be detached from surrounding dentinal tissue when the substantially gas-free liquid is in the tooth.

112. The apparatus of any one of Claims 1 to 8, 9 to 20, 57 to 66, and 70, further comprising a pulse intensifier that causes pulsations in the energy beam.

113. The apparatus of any one of Claims 63 to 65, 69, and 71 to 94, further comprising a fluid inlet for supplying fluid to the tooth.

114. An apparatus for treating a tooth, the apparatus comprising:

an enclosure having a mounting surface configured to be positioned against a tooth surface over a treatment region of the tooth, the enclosure configured to define a chamber to be filled with a liquid when the enclosure is positioned against the tooth;

a pressure wave generator coupled with the enclosure and extending through at least a portion of the chamber of the enclosure, the pressure wave generator configured to direct an energy beam through the supplied fluid,

wherein, when the energy beam passes through the supplied fluid, the energy beam generates pressure waves that propagate through the fluid, the apparatus configured such that the generated pressure waves create at least some cavitation in the supplied fluid, the generated pressure waves having sufficient energy to clean the treatment region.

115. The apparatus of Claim 114, wherein the energy beam comprises a coherent energy beam.

116. The apparatus of Claim 115, wherein the pressure wave generator comprises a liquid jet device and the energy beam comprises a liquid jet.

117. The apparatus of Claim 116, wherein the liquid jet device comprises a liquid pressurization portion which pressurizes the liquid and a liquid beam forming portion in fluid communication with the pressurization portion, said beam forming portion comprising an orifice that receives the pressurized liquid, said orifice sized and shaped to convert the pressurized liquid into the liquid jet, the liquid jet comprising a high velocity

collimated beam that produces an acoustic wave upon impact with a surface, the energy of said wave causing organic material to be detached from dentin.

118. The apparatus of Claim 117, wherein said orifice has a transverse width in a range from about 10 microns to about 200 microns.

119. The apparatus of Claim 117, wherein said orifice has an axial length in a range from about 50 microns to about 1000 microns.

120. The apparatus of Claim 117, wherein a diameter of the orifice is in a range from about 10 microns to about 100 microns.

121. The apparatus of Claim 120, wherein the diameter of the orifice is in a range from about 45 microns to about 65 microns.

122. The apparatus of Claim 117, wherein sides of the orifice have a root-mean-square surface roughness less than about 10 microns.

123. The apparatus of Claim 116, wherein a pressure of the liquid used to produce the liquid jet is in a range from about 2,000 psi to about 11,000 psi.

124. The apparatus of Claim 116, wherein a pressure of the liquid used to produce the liquid jet is in a range from about 7,000 psi to 15,000 psi.

125. The apparatus of Claim 116, wherein the liquid jet has an energy flux in a range from about 50 kW/cm² to about 1000 kW/cm².

126. The apparatus of Claim 116, wherein the liquid jet has a velocity in a range from about 50 m/s to about 300 m/s.

127. The apparatus of Claim 116, further comprising a pump configured to pressurize the liquid that forms the liquid jet.

128. The apparatus of Claim 114, wherein the pressure waves comprises frequencies comprising widespread acoustic noise.

129. The apparatus of Claim 114, wherein the frequencies comprise frequencies in a range from about 1 Hz to about 10 MHz.

130. The apparatus of Claim 114, wherein the enclosure comprises a cap configured to be applied to the tooth to substantially retain the fluid in a tooth chamber in the tooth.

131. The apparatus of Claim 130, the cap further including an outflow opening to permit organic material and liquid to be evacuated from the tooth.

132. The apparatus of Claim 130, wherein the cap includes a suction port configured to remove fluid from the tooth at substantially the same rate that it is introduced.

133. The apparatus of Claim 114, further comprising a suction port configured to remove liquid from the chamber of the enclosure.

134. The apparatus of Claim 133, wherein a distal end of the pressure wave generator is disposed in the chamber.

135. The apparatus of Claim 133, wherein the enclosure comprises a contact member on a distal end of a handpiece, said contact member configured to contact the tooth and stabilize the handpiece against unwanted movement relative to the tooth.

136. An apparatus for treating a tooth, the apparatus comprising:

an enclosure having a mounting surface configured to be positioned against a tooth surface over a treatment region of the tooth, the enclosure configured to define a chamber to be filled with a liquid when the enclosure is positioned against to the tooth; and

a pressure wave generator coupled to the enclosure, the pressure wave generator configured to direct a coherent energy beam into or onto the enclosure through the liquid to generate pressure waves having energy sufficient to clean the treatment region.

137. The apparatus of Claim 136, wherein the pressure wave generator and the enclosure cooperate to generate liquid motion in the treatment region of the tooth.

138. The apparatus of Claim 136, wherein the pressure wave generator comprises a liquid jet device, and wherein the coherent energy beam comprises a liquid jet.

139. The apparatus of Claim 138, wherein the liquid jet device comprises a liquid pressurization portion which pressurizes the liquid and a liquid beam forming portion in fluid communication with the pressurization portion, said beam forming portion comprising an orifice that receives the pressurized liquid, said orifice sized and shaped to convert the pressurized liquid into the liquid jet, the liquid jet comprising a high velocity collimated beam that produces an acoustic wave upon impact with a surface, the energy of said wave causing organic material to be detached from dentin.

140. The apparatus of Claim 138, further comprising a pump configured to pressurize the liquid that forms the liquid jet.

141. The apparatus of Claim 136, wherein the pressure waves comprises frequencies comprising widespread acoustic noise.

142. The apparatus of Claim 141, wherein the frequencies comprise frequencies in a range from about 1 Hz to about 10 MHz.

143. The apparatus of Claim 136, further comprising a suction port configured to remove fluid from the treatment region.

144. The apparatus of Claim 136, further comprising a controller in operable communication with the pressure wave generator.

145. The apparatus of Claim 136, further comprising a fluid source configured to be filled with and to deliver a substantially gas-free liquid to the tooth.

146. The apparatus of Claim 145, wherein the substantially gas-free liquid includes less than 1% dissolved gases by volume.

147. An apparatus for treating a tooth, the apparatus comprising:

an enclosure having a mounting surface configured to be positioned against a tooth surface over a treatment region of the tooth, the enclosure configured to define a chamber to be filled with a liquid when the enclosure is positioned against the tooth; and

a pressure wave generator coupled with the enclosure, the pressure wave generator configured to generate pressure waves in the liquid to clean the treatment region,

wherein the pressure waves generated in the liquid comprise frequencies comprising widespread acoustic noise.

148. The apparatus of Claim 147, wherein the pressure wave generator comprises a liquid jet device, an ultrasonic or megasonic generator, or a vibrating mechanical device.

149. The apparatus of Claim 148, wherein the pressure wave generator comprises a liquid jet device.

150. The apparatus of Claim 149, wherein the liquid jet device comprises a liquid pressurization portion which pressurizes the liquid and a liquid beam forming portion in fluid communication with the pressurization portion, said beam forming portion comprising an orifice that receives the pressurized liquid, said orifice sized and shaped to convert the pressurized liquid into the liquid jet, the liquid jet comprising a high velocity collimated beam that produces an acoustic wave upon impact with a surface, the energy of said wave causing organic material to be detached from dentin.

151. The apparatus of Claim 148, wherein the frequencies comprise frequencies in a range from about 1 Hz to about 10 MHz.

152. The apparatus of Claim 149, further comprising a pump configured to pressurize the liquid that forms the liquid jet.

153. An apparatus for removing organic material from a treatment region of a tooth, comprising:

a fluid source arranged to deliver a substantially gas-free liquid to the treatment region;

an enclosure having a mounting surface configured to be positioned against a tooth surface over the treatment region of the tooth, the enclosure configured to define a chamber to be filled with the substantially gas-free liquid when the enclosure is positioned against the tooth; and

a pressure wave generator coupled with the enclosure, the pressure wave generator configured to direct a coherent energy beam, through the delivered liquid to propagate pressure waves through the delivered liquid,

wherein the pressure waves have sufficient energy to cause organic material in the treatment region to be detached from surrounding dentin when the substantially gas-free liquid is at the treatment region.

154. The apparatus of Claim 153, wherein the pressure wave generator comprises a liquid jet device.

155. The apparatus of Claim 154, wherein the liquid jet device comprises a liquid pressurization portion which pressurizes the liquid and a liquid beam forming portion in fluid communication with the pressurization portion, said beam forming portion comprising an orifice that receives the pressurized liquid, said orifice sized and shaped to convert the pressurized liquid into the liquid jet, the liquid jet comprising a high velocity collimated beam that produces an acoustic wave upon impact with a surface, the energy of said wave causing organic material to be detached from dentin.

156. The apparatus of Claim 153, wherein the pressure waves comprises frequencies comprising widespread acoustic noise.

157. The apparatus of Claim 156, wherein the frequencies comprise frequencies in a range from about 1 Hz to about 10 MHz.

158. The apparatus of Claim 153, further comprising a suction port to remove liquid from the chamber of the enclosure.

159. An apparatus for treating an infected or decaying condition in a tooth, the apparatus comprising:

a handpiece sized to be at least partially positioned within a mouth of a patient;

a pressure wave generator supported at least in part by the handpiece, the pressure wave generator comprising a distal end sized to be positioned at a treatment region of a tooth and being configured to output energy for generating pressure waves; and

a microprocessor communicating with the pressure wave generator to control the operation of the pressure wave generator, the handpiece being configured to position the pressure wave generator relative to the treatment region, the pressure wave generator and the microprocessor cooperating to generate a pulsed coherent energy beam, the handpiece supporting the pressure wave generator such that the pulsed coherent energy beam is directed through supplied liquid provided at a portion of the treatment region of the tooth, the pulsed coherent energy beam being of sufficient energy to generate pressure waves of sufficient energy to remove infected or decaying material from the tooth throughout the treatment region, including at locations remote from the portion of the treatment region at which the pulsed coherent energy beam is directed.

160. The apparatus of Claim 159, wherein the microprocessor is configured to control amplitude and frequency of the pulsed coherent energy beam.

161. The apparatus of Claim 159, additionally comprising a user interface.

162. The apparatus of Claim 159, wherein the pressure wave generator comprises a liquid jet device that generates the pulsed coherent energy beam as a pulsed collimated, coherent liquid jet.

163. The apparatus of Claim 162, further comprising a pump configured to pressurize the liquid that forms the pulsed collimated, coherent liquid jet.

164. The apparatus of Claim 159, additionally comprising a cap configured to be applied to the tooth to substantially retain fluid.

165. The apparatus of Claim 164, wherein the cap further includes an outflow opening to permit organic material and liquid to be evacuated from the treatment region.

166. The apparatus of Claim 159, further comprising a fluid source arranged to supply a substantially gas-free liquid to the tooth.

167. An apparatus for treating a treatment region of a tooth with fluid supplied by a fluid source, the apparatus comprising:

a handpiece sized to be at least partially positioned within a mouth of a patient and proximate to the treatment region; and

a pressure wave generator supported at least in part by the handpiece, the handpiece configured to position the pressure wave generator relative to the treatment region so as to direct a coherent energy beam into the supplied fluid at a portion of the treatment region, the coherent energy beam being of sufficient energy to generate pressure waves of sufficient power to remove infected or decaying material throughout the treatment region of ~~from~~ the tooth, including at locations remote from the portion of the treatment region at which the coherent energy beam is directed.

168. The apparatus of Claim 167, wherein the pressure wave generator comprises a liquid jet device.

169. An apparatus for cleaning a root canal of the tooth, the apparatus comprising:

a handpiece configured to be positioned on a side surface of the tooth near an opening in the side surface of the tooth, the handpiece comprising an acoustic energy generator,

the acoustic energy generator configured to propagate acoustic waves in the tooth to substantially remove organic material from the root canal when the handpiece is positioned on the side surface of the tooth.

170. The apparatus of Claim 169, wherein the acoustic energy generator comprises a liquid jet device.

171. The apparatus of Claim 170, wherein the liquid jet device is configured to direct a liquid jet through the opening.

172. The apparatus of Claim 169, wherein the acoustic energy generator is configured to propagate acoustic waves in the tooth to substantially remove organic material from the root canal when the acoustic energy generator is activated outside the tooth.

173. The apparatus of Claim 169, further comprising a positioning member configured to be coupled to the side surface of the tooth, the positioning member configured to engage a distal portion of the handpiece.

174. The apparatus of Claim 173, wherein the positioning member comprises a central opening configured to provide fluid communication between the opening in the side surface of the tooth and a distal portion of the handpiece.

175. The apparatus of Claim 169, further comprising a reservoir of liquid that is substantially free of dissolved gases, the reservoir configured to be in fluid communication with the handpiece.

176. The apparatus of Claim 169, wherein the acoustic energy generator is configured to generate acoustic energy in the tooth in a range of about 1 Hz to about 10 MHz.

177. The apparatus of Claim 169, wherein the acoustic energy generator is configured to direct energy through the opening in the side surface of the tooth.

178. The apparatus of Claim 169, further comprising an enclosure coupled with the handpiece, the enclosure configured to be positioned on the side surface of the tooth to at least partially define a chamber.

179. The apparatus of claim 178, wherein the acoustic energy generator is disposed at least partially within the chamber defined by the enclosure.

180. The apparatus of Claim 170, further comprising a pump configured to pressurize the liquid that forms the liquid jet.

181. An apparatus for treating an infected or decaying condition in a tooth, the apparatus comprising:

an enclosure having a mounting surface configured to be positioned against a tooth surface at or near a treatment region of the tooth to enclose the treatment region, and an access opening being disposed on the enclosure so as to be exposed to the treatment region when the mounting surface is positioned against the tooth surface;

a fluid source having an outlet arranged to supply liquid to the treatment region through the access opening; and

a flow pathway in communication with the fluid source, the flow pathway producing a swirling flow profile within at least the liquid passing through the access opening toward the treatment region.

182. The apparatus of Claim 181, further comprising an outflow opening in the enclosure to permit liquid and organic material to be evacuated from the treatment region.

183. The apparatus of Claim 181, wherein the fluid source comprises a liquid jet device configured to generate a liquid jet.

184. The apparatus of Claim 183, wherein a pressure of the liquid used to produce the liquid jet is in a range from about 2,000 psi to about 11,000 psi.

185. The apparatus of Claim 183 additionally comprising a pump configured to pressurize the liquid that forms the liquid jet.

186. The apparatus of Claim 183, wherein the fluid source is configured to direct a plurality of liquid jets through the access opening.

187. The apparatus of Claim 181, wherein the outflow opening is sufficiently large so as to remove liquid at substantially the same rate as the liquid is supplied.

188. The apparatus of Claim 181, wherein the fluid source is arranged to supply the liquid at an oblique angle to a long axis of a root canal of the tooth.

189. The apparatus of Claim 181, wherein an interior wall of the flow pathway comprises one or more angled portions shaped to alter the flow profile within at least the liquid passing through the access opening towards the treatment region.

190. The apparatus of Claim 181, wherein the flow pathway comprises a guide tube.

191. The apparatus of Claim 190, wherein the guide tube comprises an interior bore provided with a helical surface.

192. The apparatus of Claim 181, wherein the fluid source is configured to supply an abrasive solution to the treatment region.

193. The apparatus of Claim 181, wherein the enclosure comprises a cap that tapers distally.

194. The apparatus of Claim 181, wherein the fluid source is adjustable to a plurality of positions relative to the enclosure.

195. The apparatus of Claim 181, wherein the fluid source is configured to deliver substantially gas-free liquid to the treatment region.

196. The apparatus of Claim 195, wherein the substantially gas-free liquid includes less than 1% dissolved gases by volume.

197. An apparatus for treating an infected or decaying condition in a tooth, the apparatus comprising:

an enclosure having a mounting surface configured to be positioned against a tooth surface at or near a treatment region of the tooth to enclose the treatment region, and an access opening being disposed on the enclosure so as to be exposed to the treatment region when the mounting surface is positioned against the tooth surface; and

a pressure wave generator configured to interact with the enclosure such that the pressure wave generator is disposed so as to be at least partially submerged in a liquid medium in the treatment region,

wherein the pressure wave generator is configured to generate pressure waves within the liquid medium of sufficient power to remove infected or decaying material from the tooth at the treatment region.

198. The apparatus of Claim 197, wherein the pressure wave generator is configured to direct a coherent energy beam through the liquid medium at the treatment region.

199. The apparatus of Claim 198, wherein the pressure wave generator comprises a liquid jet device that generates the coherent energy beam as a collimated, coherent liquid jet.

200. The apparatus of Claim 197 additionally comprising a fluid source having an outlet arranged to supply liquid to the treatment region through the access opening of the enclosure.

201. The apparatus of Claim 197, further comprising an outflow opening in the enclosure to permit liquid and organic materials to be evacuated from the treatment region.

202. The apparatus of Claim 200, wherein the fluid source is configured to deliver a substantially gas-free liquid to the treatment region.

1 / 16




FIG. 1

2/16





FIG. 2

3/16

FIG. 3

38



4/16

FIG. 4









FIG. 4A





7/16



8/16





FIG. 6D

FIG. 6C

9/16

FIG. 7



10/16

FIG. 8A





FIG. 8B



11/16




FIG. 9A

12/16




FIG. 9B

13/16












FIG. 9C

14/16



15/16

FIG. 10D*FIG. 10E**FIG. 10F**FIG. 10G**FIG. 10H**FIG. 10C*

16/16

FIG. 11

