




(72) UEDA, KATSUNORI, JP

(72) TAKEHANA, YOSHIYASU, JP

(72) SEARASHI, SHUNICHI, JP


(71) NICHIAS CORPORATION, JP

(51) Int.Cl.⁷ F16J 15/12, F02F 11/00

(30) 1998/12/25 (10-370391) JP

(54) **STRUCTURE D'ETANCHEITE DE JOINT A TROIS ELEMENTS**

(54) **SEALING STRUCTURE OF A JOINT FOR THREE MEMBERS**



(57) In order to improve a sealing structure of a joint for three members, in which the three members butt against each other and a joint portion has a T-shape, in the sealing structure of a joint for three members, in which the three members, i.e. a first, a second and a third member, butt against each other and a joint portion has a T-shape, at least one plate-shaped gasket, in which rubber layers are formed on two surfaces of a metal plate, is disposed between surfaces to be jointed where the second and the third member are butted against the first member. An opening is formed in the plate-shaped gasket at a portion, which is opposite to a T-shaped portion, and filled with paste-like liquid gasket sealing the T-shaped portion.

ABSTRACT OF THE DISCLOSURE

In order to improve a sealing structure of a joint for three members, in which the three members butt against each other and a joint portion has a T-shape, in the sealing structure of a joint for three members, in which the three members, i.e. a first, a second and a third member, butt against each other and a joint portion has a T-shape, at least one plate-shaped gasket, in which rubber layers are formed on two surfaces of a metal plate, is disposed between surfaces to be jointed where the second and the third member are butted against the first member. An opening is formed in the plate-shaped gasket at a portion, which is opposite to a T-shaped portion, and filled with paste-like liquid gasket sealing the T-shaped portion.

SEALING STRUCTURE OF A JOINT
FOR THREE MEMBERS

5 FIELD OF THE INVENTION

The present invention relates to an improvement of a sealing structure of a joint for three members, at which three members butt against each other and a joint therefor has a shape of T.

10 DESCRIPTION OF THE PRIOR ART

Concerning the sealing structure of a joint for three members, JP-A-Hei 10-231935 discloses a sealing structure of a joint for three members, at which a cylinder block (second member) is jointed to a cylinder head (first member) in a motor and a timing cover (third member) is jointed to end surfaces of the first two members.

The sealing structure of a joint for three members is characterized in that liquid gasket product is put between the end surfaces of the first and second members and the third member, that a plate-shaped gasket is disposed between the first and the second members, and that the sealing property is improved by suppressing bulge-out of the liquid gasket product from a T-shaped joint portion of the three members owing to a protruding portion formed on an end surface of the gasket.

In the sealing structure of a joint for three members described above only the liquid gasket product serves as sealing material used on the third member side.

That is, it is assumed that seal outside of the T-shaped portion relies also on the liquid gasket.

For example, in case where an oil inlet and outlet section is in the joint portion of the third member, depending on the construction of the motor, since the liquid gasket is unsuitable for high pressure seal (because of blow-off), it is necessary to dispose separately a rubber O-ring.

Further, although the liquid gasket is an excellent material for filling a gap having a not plain shape such as a T-shape, it has an inconvenience that utilization environments or conditions outside of the T-shaped portion are fairly restricted.

SUMMARY OF THE INVENTION

The present invention has been made in order to overcome the drawback of the sealing structure of a joint for three members disclosed in the publication and a main object thereof is to provide a sealing structure, which can be used for a joint for three members, without using any liquid gasket outside of the T-shaped portion.

In order to achieve the above object, the present invention is characterized in that in a sealing structure of a joint for three members, in which a second member and a third member are butted against a first member in common so that a joint portion has a T-shape, at least one plate-shaped gasket, in which rubber layers are formed on two surfaces of a metal plate, is disposed at least between surfaces to be jointed where the second and the third member are butted against the first member in common and an opening is formed in the plate-shaped gasket at a portion, which is opposite to a T-shaped portion, the opening being filled with a liquid gasket sealing the T-shaped portion.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1(a) is a block diagram showing a mounted construction of a sealing structure of a joint for three members according to an embodiment of the present invention;

Fig. 1(b) is a plan view of a plate-shaped gasket G_1 used in the sealing structure indicated in Fig. 1(a);

Fig. 2 is an enlarged cross-sectional view of the plate-shaped gasket G_1 along a line A-A in Fig. 1(b);

Fig. 3 is an enlarged cross-sectional view of the plate-shaped gasket G_1 along a line B-B in Fig. 1(b);

Fig. 4 is a perspective view showing a concrete

example of construction of the sealing structure of a joint for three members;

Fig. 5(a) is a block diagram showing a mounted construction of a sealing structure of a joint for three members according to another embodiment of the present invention;

Fig. 5(b) is a plan view of a plate-shaped gasket G_3 used in the sealing structure indicated in Fig. 5(a);

Fig. 6 is an enlarged cross-sectional view of the plate-shaped gasket G_3 along a line A-A in Fig. 5(b);

Fig. 7 is an enlarged cross-sectional view of the plate-shaped gasket G_3 along a line B-B in Fig. 5(b);

Fig. 8 is a perspective view showing another example of construction of the sealing structure of a joint for three members;

Fig. 9 is a plan view showing a state where a joint portion is sealed by using a plate-shaped gasket;

Fig. 10 is an enlarged cross-sectional view of the plate-shaped gasket along a line X-X in Fig. 9;

Fig. 11 is an enlarged cross-sectional view of the plate-shaped gasket along a line Y-Y in Fig. 9;

Fig. 12 is a plan view showing another example where a joint portion is sealed by using a plate-shaped gasket;

Fig. 13 is an enlarged cross-sectional view of the plate-shaped gasket along a line X-X or Y-Y in Fig. 12; and

Fig. 14 is an enlarged cross-sectional view of the plate-shaped gasket along a line Z-Z in Fig. 12.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

As a preferable mode of realization of the present invention, as indicated in Figs. 1 to 3, in a sealing structure of a joining for three members, in which three members, i.e. a cylinder block 1, a cylinder head 2 and a timing cover 3 in a motor are butted against each other so that a joint portion has a T-shape, a plate-shaped gasket G_1 consisting of a metal plate on both the surfaces of which

rubber layers are formed, is disposed between joint surfaces of the timing cover 3 as well as the cylinder block 1 and the cylinder head 2, against which the first two are butted in common, and an opening is formed in the plate-shaped gasket at a portion, which is opposite to a T-shaped portion, the opening being filled with paste-like liquid gasket g_1 sealing the T-shaped portion.

Fig. 1(a) is a diagram showing a mounted construction of a sealing structure of a joint for three members according to the present invention and Fig. 1(b) is a plan view of a plate-shaped gasket G_1 . Fig. 2 is an enlarged cross-sectional view of the plate-shaped gasket G_1 along a line A-A, while Fig. 3 is an enlarged cross-sectional view thereof along a line B-B in Fig. 1(b).

In the figures reference numeral 1 is a cylinder block; 2 is a cylinder head; 3 is a timing cover; 4 is a head cover; and 5 is an oil pan in a motor. G_1 and G_2 represent plate-shaped gaskets, in each of which rubber layers are formed on both the surfaces of a metal plate. Hereinbelow items cited by reference numerals 1, 2, 3, 4 and 5 are called simply members.

A stainless steel plate (SUS), a cold pressed steel plate (SPCC), an aluminium plate, etc. can be used for the metal plate constituting the plate-shaped gasket G_1 or G_2 . However it is not restricted thereto.

Silicone rubbers, nitril rubber, acryl rubber, fluorocarbon rubber, etc. can be used for the rubber layers. However other rubber materials may be arbitrarily selected to be used. Further, for the rubber layers, foam rubber layers, in which a number of independent bubbles are formed, can be used.

It is preferable that the metal plate is 0.2 to 0.3mm thick and that the rubber layers are about 20 to 100 μ m thick.

Opening portions such as cut-off portions, perforated portions, etc. are formed in the plate-shaped gasket G_1 at a

portion, which is opposite to the T-shaped joint portion for the members 1, 2, 3, 4 and 5. These are filled with liquid gaskets g_1 , g_2 and g_3 adjusted so as to be paste-like so that sealing portions by the liquid gaskets are formed.

5 The liquid gasket g_1 is used for sealing the T-shaped joint portion formed by the members 1, 2 and 3; the liquid gasket g_2 is used for sealing the T-shaped joint portion formed by the members 1, 5 and 3; and the liquid gasket g_3 is used for sealing the T-shaped joint portion formed by the
10 members 2, 3 and 4. n represents a hole for a clamping bolt.

In case where the member 1 has a step H with respect to the member 2 in the T-shaped joint portion for the members 1, 2 and 3, as indicated in Fig. 2, a plate-shaped gasket having a bead fitted to that step is used.

15 Fig. 4 shows a concrete example of construction thereof. It has a construction substantially identical to that indicated in Fig. 2. That is, in case where the member 1 has a step H with respect to the member 2 in the T-shaped joint portion for the members 1, 2 and 3, a plate-shaped
20 gasket G_1 having a half bead is used and a cut-off portion m is formed at a portion, which is opposite to the T-shaped joint portion, so that the cut-off portion m can be filled with paste-like liquid gasket g_1 .

Fig. 5(a) is a diagram showing a mounted construction
25 of another sealing structure of a joint for three members according to the present invention and Fig. 5(b) shows a gasket G_3 used therein.

Fig. 6 is an enlarged cross-sectional view of the gasket G_3 along a line A-A, while Fig. 7 is an enlarged cross-sectional view thereof along a line B-B in Fig. 5(b).
30

In the figures, the member 1 is a cylinder block; the member 2 is a cylinder head; the member 3 is a timing cover; G_3 is a plate-shaped gasket; and g_4 is a paste-like liquid gasket.

35 Since the member 1 has a step H with respect to the

member 3 also in the present example of construction, it is so constructed that a plate-shaped gasket G_3 having a bead is used and that the cut-off portion is filled with the liquid gasket g_4 .

5 Fig. 8 shows an example of construction, in which the sealing structure for three members indicated in Fig. 2 has an improved sealing property in the T-shaped portion owing to a liquid gasket pool 3a formed in the member 3.

10 Figs. 9 to 11 show still another example of construction, in which beads of plate-shaped gaskets are fitted according to steps between different members.

 Fig. 9 shows an example of construction, a plate-shaped gasket G_1 is disposed on the members 1 and 2 having different steps. Fig. 10 is an enlarged cross-sectional view of the plate-shaped gasket along a line X-X, while Fig. 11 is an enlarged cross-sectional view thereof along a line Y-Y in Fig. 9.

 In the present example of construction, balance in superficial pressure on the members 1 and 2 is improved by varying half beads therefore in the height, in case where the step H_2 for the member 2 is greater than the step H_1 for the member 1, viewed from the plate-shaped gasket G_1 .

25 Figs. 12 to 14 show still another example of construction, in which beads of a plate-shaped gasket having a long bolt pitch are fitted, depending on steps of the different members.

 Fig. 12 shows an example of construction, in which a plate-shaped gasket G_1 is disposed on the members 1 and 2 having different steps, ℓ representing a distance between two bolt holes n . Fig. 13 is an enlarged cross-sectional view of the plate-shaped gasket along a line X-X or Y-Y, while Fig. 14 is an enlarged cross-sectional view thereof along a line Z-Z in Fig. 12.

35 The present example of construction shows a construction, in which balance in superficial pressure is improved

by disposing a counterbead (extra bead) f apart from the half bead on the plate-shaped gasket G_1 .

As described in detail in the above, according to the present invention, since a sealing structure of a joint for
5 three members is constructed by using liquid gasket for sealing a T-shaped portion and at least one plate-shaped gasket, in which rubber layers are formed on both the surfaces of a metal plate for sealing other joint surfaces, following effects can be obtained.

10 1) Since the liquid gasket is used only on the T-shaped portion in the joint portion for three members, drawbacks such as function loss of other parts, etc. due to application tact compression or bulge-out of the liquid gasket can be significantly reduced.

15 2) The sealing property can be maintained also for great steps or gaps, which any conventional gasket made of rubber or any gasket having beads formed by printing on a joint sheet base plate cannot deal with.

20 3) The liquid gasket has a property to be easily broken, if itself is thin. On the contrary, since the plate-shaped gasket itself is thick, it is suppressed that the liquid gasket itself is broken.

25 4) Since the liquid gasket is strongly adhered to an end surface (metal part) of the plate-shaped gasket, a sealing property at contact surfaces can be satisfactorily maintained and at the same time it is possible to provide gaskets capable of being used most widely by using liquid gaskets, which can follow any form such as steps or gaps on the contact surfaces, together therewith.

30 5) Since plate-shaped gaskets, in each of which rubber layers are formed on a metal plate, are used, it is possible to vary liquid gasket pools by varying the thickness thereof and to increase freedom for taking measures to deal with steps or gaps (depth). That is, since it is possible to
35 increase design freedom, a sealing structure having a good

balance in superficial pressure can be obtained.

WHAT IS CLAIMED IS:

1. A sealing structure of a joint for three members having a T-shaped joint portion, in which a second and a third member butt against a first member, comprising:
5 at least one plate-shaped gasket disposed between joint surfaces of said first, said second and said third member in said T-shaped joint portion, said gasket being constructed by forming rubber layers on two surfaces of a metal plate and having an opening at a portion, which is
10 opposite to said T-shaped joint portion, said opening being filled with liquid gasket for sealing said T-shaped joint portion.
- 15 2. A sealing structure of a joint for three members according to Claim 1, wherein said rubber layers in said plate-shaped gasket are foam rubber layers.
- 20 3. A sealing structure of a joint for three members according to Claim 1 or 2, wherein said opening formed in said plate-shaped gasket is a cut-off portion or a perforated portion.
- 25 4. A sealing structure of a joint for three members according to either one of Claims 1 to 3, wherein said plate-shaped gasket has a bead corresponding to a step between said second member and said third member.
- 30 5. A sealing structure of a joint for three members according to Claim 4, wherein said plate-shaped gasket has a counterbead.
- 35 6. A sealing structure of a joint for three members according to Claim 1, wherein a liquid gasket pool is formed in said third member at a portion, which is opposite to said

opening.

7. A sealing structure of a joint for three members
according to Claim 1, wherein said metal plate is 0.2 to
5 0.3mm thick and said rubber layers are 20 to 100µm thick.

FIG. 1(b)




FIG. 1(a)




FIG. 2




FIG. 3




FIG. 4




FIG. 5(a)




FIG. 5(b)




FIG. 6




FIG. 7



FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14

