



US00RE44034E

(19) **United States**
(12) **Reissued Patent**
Van Der Valk

(10) **Patent Number:** **US RE44,034 E**
(45) **Date of Reissued Patent:** ***Mar. 5, 2013**

(54) **IDENTITY CARD, INFORMATION CARRIER AND HOUSING DESIGNED FOR ITS APPLICATION**

(75) Inventor: **Robert Willem Van Der Valk**, Gronsvelderweg (NL)

(73) Assignee: **Chiptec International Ltd.**, Curacao (AN)

(*) Notice: This patent is subject to a terminal disclaimer.

(21) Appl. No.: **13/220,521**

(22) Filed: **Aug. 29, 2011**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **6,382,506**
Issued: **May 7, 2002**
Appl. No.: **09/230,343**
PCT Filed: **Jul. 24, 1997**
PCT No.: **PCT/NL97/00443**
§ 371 (c)(1), (2), (4) Date: **Dec. 9, 1999**
PCT Pub. No.: **WO98/03941**
PCT Pub. Date: **Jan. 29, 1998**

U.S. Applications:

(63) Continuation of application No. 10/841,424, filed on May 7, 2004, now Pat. No. Re. 43,333.

(30) **Foreign Application Priority Data**

Jul. 24, 1996 (NL) 1003666
Aug. 14, 1996 (NL) 1003802

(51) **Int. Cl.**
G06K 5/00 (2006.01)

(52) **U.S. Cl.** **235/380; 235/492; 902/3; 902/25; 902/26; 902/5; 902/4**

(58) **Field of Classification Search** **235/379, 235/380, 792, 492; 902/3-4, 25-26, 5; 705/18**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,095,739 A 6/1978 Fox et al.
4,135,147 A 1/1979 Rignati et al.
4,238,853 A 12/1980 Ehrsam et al.
4,253,086 A 2/1981 Szwarcbier
4,582,985 A 4/1986 Lofberg
4,709,136 A 11/1987 Watanabe
4,754,487 A 6/1988 Newmuis
4,790,564 A 12/1988 Larcher et al.
4,802,218 A 1/1989 Wright et al.

(Continued)

FOREIGN PATENT DOCUMENTS

DE 36 32 294 A1 4/1988
DE 37 06 465 A1 9/1988

(Continued)

OTHER PUBLICATIONS

Asai, Ko et al., "Fingerprint Identification System," Second USA-Japan Computer Conference, 1975, pp. 30-35.


(Continued)

Primary Examiner — Kristy A Haupt
(74) *Attorney, Agent, or Firm* — Finnegan, Henderson, Farabow, Garrett & Dunner, L.L.P.

(57) **ABSTRACT**

An identity card comprises an easy-to-use, more specifically card-shaped, information carrier provided with an electronically readable memory capable of digitally storing personal user data, including data concerning the user's physical features. The information carrier is installed in and can be removed from an input unit of a housing of comfortable dimensions. The housing has been provided with reading equipment which is capable of reading the personal data stored in the memory of the information carrier. Moreover, the housing has been provided with a screen for representing the data read.

26 Claims, 2 Drawing Sheets



U.S. PATENT DOCUMENTS

4,816,653	A	3/1989	Anderl et al.
4,837,422	A	6/1989	Dethloff et al.
4,864,614	A	9/1989	Crowth
4,870,604	A	9/1989	Tatsuno
4,897,874	A	1/1990	Lidnsky et al.
4,900,903	A	2/1990	Wright et al.
4,972,476	A	11/1990	Nathans
4,975,969	A	12/1990	Tal
4,993,068	A	2/1991	Piosenka et al.
5,010,237	A	4/1991	Kawana
5,015,830	A	5/1991	Masuzawa et al.
5,048,085	A	9/1991	Abraham et al.
5,055,658	A	10/1991	Cockburn
5,144,680	A	9/1992	Kobayashi et al.
5,150,409	A	9/1992	Elsner
5,227,615	A	7/1993	Oogita
5,259,025	A	11/1993	Monroe et al.
5,321,765	A	6/1994	Costello
5,337,358	A	8/1994	Axelrod et al.
5,420,924	A	5/1995	Berson et al.
5,432,864	A	7/1995	Lu et al.
5,514,862	A	5/1996	Salzano
5,526,428	A	6/1996	Arnold
5,528,222	A	6/1996	Moskowitz et al.
5,563,400	A	10/1996	Le Roux
5,578,808	A	11/1996	Taylor
5,754,675	A	5/1998	Valadier
5,787,186	A	7/1998	Schroeder
5,941,711	A	8/1999	Iida
6,011,858	A	1/2000	Stock et al.
6,213,391	B1	4/2001	Lewis
6,213,403	B1	4/2001	Bates, III
6,237,848	B1	5/2001	Everett
6,298,441	B1	10/2001	Handelman et al.
6,592,031	B1	7/2003	Klatt
6,628,814	B1	9/2003	Shapiro
6,631,201	B1	10/2003	Dickinson et al.
6,681,034	B1	1/2004	Russo
6,719,200	B1	4/2004	Wiebe

FOREIGN PATENT DOCUMENTS

DE	37 06 466	A1	9/1988	
DE	296 04 012	U1	6/1996	
DE	19648767	A1	6/1997	
EP	0 159 539	A1	10/1985	
EP	0 271 835	A2	6/1988	
EP	0 292 249	A2	11/1988	
EP	0 385 290	A1	9/1990	
EP	0 407 882	A1	1/1991	
EP	0 413 822	A1	2/1991	
EP	0 661 675	A2	7/1995	
WO	WO 82/03286		9/1982	
WO	WO 94/23399		10/1994	
WO	WO 98/03941	A1	1/1998	
WO	WO 98/10363	*	12/1998 235/487
WO	WO 98/10363		3/1999	

OTHER PUBLICATIONS

- "4. Exclusive Use Equipment," NEC Res. & Develop., No. 96, Mar. 1990, pp. 143-159.
- "Finger ID Progress Stirs Biometrics," Security, May 1996, p. 62.
- "Smart Card + Access = Applications, Opportunities," Security, May 1996, p. 21.
- "The Smart Card," Wharton Report, No. 104, Apr. 1987, pp. 1-9.
- "Border crossing simplified with INS system," *Access Control*, 38(6):31-33, May 1995.
- "New Applications, Fingerprint analysis system points the way to security," *Computer*, IEEE Computer Society, 103, Apr. 1985.
- Draper, Stephen, "Security Aspects of Smart Cards," *Computer Security in the Age of Information*, William J. Caelli, Editor, Proceedings of the Fifth IFIP International Conference on Computer Security, Gold Coast, Queensland, Australia, May 19-21, 1988, pp. 51-61.
- Kiernan, Vincent, "Automation takes a hand in passport control," *New Scientist*, vol. 140, No. 1895, Oct. 16, 1993, p. 10.

- Lisimaque, Gilles, "Workshop on ID Cards," Gemplus, Carnegie Mellon University, 9 pages, Nov. 2001.
- Masuda, I., "Individual Identification Technique for Security," *Systems, Control and Information*, vol. 35, No. 7, Jul. 1991, pp. 431-439, (Abstract only in English).
- Miller, Benjamin, "Vital signs of identity," *IEEE Spectrum*, vol. 31, No. 2, Feb. 1994, pp. 22-30.
- Nordin, Bjorn, "Match-on-Card Technology", *Precise Biometrics*, Apr. 2004.
- Nilsson, Jonas et al., "Match-on-Card for Java Cards", *Precise Biometrics*, Apr. 2004.
- News, U.S. National—Reuters, "Officials Urge Extension of Passport Changes," Yahoo! News, <http://news.yahoo.com/news>, Apr. 21, 2004, 2 pages.
- Pettersson, Magnus et al., "Ensuring integrity with fingerprint verification," *Precise Biometrics White Paper*, Lund, Sweden, Nov. 1-5, 2001.
- Pettersson, Magnus et al., "How secure is your biometric solution?" *Precise Biometrics White Paper*, Lund Sweden, Feb. 1-6, 2002.
- Piller, Ernst, "Card-Holder Controlled Access to Multiapplication Smart-Cards," *Smart Card 2000: The Future of IC Cards*, D. Chaum et al., Editors, Elsevier Science Publishers B.V., The Netherlands, C 1989, Proceedings of the IFIP WG 11.6 International Conference, Amsterdam, The Netherlands, 1989, pp. 159-163.
- Press Release, "ActivCard partners with Precise Biometrics to deliver first ever Open Platform On-Card biometric authentication," <http://cws.huginonline.com>, 3 pages, May 2001.
- Rinkenberger, Glenn et al., "Non-Forgeable Personal Identification System Using Cryptography and Biometrics," National Institute of Standards and Technology, 13th National Computer Security Conference, Washington, D.C., Oct. 1-4, 1990, vol. 1, pp. 80-89.
- Simmons, Gustavus J., "A Survey of Information Authentication," *Proceedings of the IEEE*, 76(5):603-620, May 1988.
- Sims, Dave, "Biometric Recognition: Our Hands, Eyes, and Faces Give Us Away," *IEEE Computer Graphics and Applications*, vol. 14, No. 5, Sep. 1994, pp. 14-15.
- Wolfgang Rankl, et al., *Handbuch der Chipkarten*, "11.2 Krankenversichertenkarte," © Carl Hanser Verlag Munchen Wien, 1995 (Translation in English provided), pp. 253-256.
- EP 97 934 782.0-2207, patent prosecution; EP Office examination results, 4 pages, Apr. 30, 2001.
- EP 97 934 782.0-2207, patent prosecution; Response to Office Action and Request for Extension of Time, 6 pages, Feb. 13, 2002.
- EP 97 934 782.0-2207, patent prosecution; EP Office examination results, 5 pages, Sep. 27, 2002.
- EP 97 934 782.0-2207, patent prosecution; Response to Office Action, Request for Extension of Time, and Request for Oral Proceeding, 5 pages, Jul. 15, 2003.
- EP 97 934 782.0-2207, patent prosecution; EP Office Summons to Attend Oral Proceedings, 7 pages, Feb. 17, 2004.
- EP 97 934 782.0-2207, patent prosecution; EP Office Result of Consultation, 7 pages, Sep. 27, 2004.
- EP 97 934 782.0-2207, patent prosecution; EP Office Submissions at the Oral Proceedings, 14 pages, Oct. 1, 2004.
- EP 97 934 782.0-2207, patent prosecution; EP Office Decision to Refuse a European Patent Application, 11 pages, Jan. 5, 2005.
- EP 97 934 782.0-2207, patent prosecution; Appeal from the Decision of the Examining Division to Refuse the Application, 20 pages, May 17, 2005.
- EP Appeal No. T 0781/05-3.4.03, EP Patent Application 97 934 782.0; Annex to the Summons to Oral Proceedings, Article 11(1) RPBA, 4 pages.
- EP Appeal No. T 0781/05-3.4.03, EP Patent Application 97 934 782.0; Response to Oral Proceedings, Amended main request and two auxiliary requests, Dec. 27, 2007, 13 pages.
- EPO Preliminary Opinion of the Examining Division dated Mar. 5, 2009, in related European Patent Application No. 08150792.3.
- Office Action for U.S. Appl. No. 10/841,424, dated Jun. 18, 2007.
- Office Action for U.S. Appl. No. 10/841,424, dated Jan. 28, 2008.
- Office Action for U.S. Appl. No. 10/841,424, dated Jan. 23, 2009.
- Office Action for U.S. Appl. No. 10/841,424, dated Dec. 17, 2009.
- Office Action for U.S. Appl. No. 10/841,424, dated Jan. 19, 2011.
- Office Action for U.S. Appl. No. 10/841,424, dated Oct. 11, 2011.

* cited by examiner





FIG. 1






Fig. 2

**IDENTITY CARD, INFORMATION CARRIER
AND HOUSING DESIGNED FOR ITS
APPLICATION**

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

Notice: More than one reissue application has been filed for the reissue of U.S. Pat. No. 6,382,506. The first reissue application is application Ser. No. 10/841,424. This reissue application is a continuation of application Ser. No. 10/841,424 filed May 7, 2004, which is now RE43,333.

BACKGROUND OF THE INVENTION

The present invention concerns an identity card comprising an easy-to-use, more specifically a card-shaped, information carrier provided with an electronically readable memory which is capable of digitally storing personal user data including the user's physical characteristics.

At present, an identity card is usually a document issued by the government, such as a passport or a driving licence, or a proof of identity which is applied within a specific business environment or for a particular professional group. In all these cases, the identity card comprises a representation in the form of a passport photograph of a user in combination with the printed personal data of the user,

However, this type of identity card has the disadvantage of being susceptible to fraud. After all, the picture on the photo is the only indication that the data on the card belong to its user. The comparison between this picture and the actual appearance of the user is based on the subjective interpretation of the controlling officer, which may also be affected by the user's changes in appearance after the identity card was issued. In addition, this regular type of identity cards are to a varying degree susceptible to forgery, as well as to loss and theft.

Nowadays there are also identity cards known, which are based on memory cards, which may or may not be smart cards, as information carriers. An example of this has been described in U.S. Pat. No. 4,993,068. In this the external characteristics of the card user are written to the card's memory in encrypted form. In case of an access control the user's characteristics are recorded and compared with the information stored on the card by means of a central processing unit. Only if the data match is the desired access granted.

Although this means of identification in itself is highly reliable and fraud-proof, nevertheless a disadvantage lies in the fact that the implementation requires relatively advanced and specifically suited equipment which will not be generally available everywhere. This makes this type of identity card only suitable for a closed circuit of users, e.g. a specific professional group or employees/co-workers within a particular business environment or (government) institution. This type of identity card, however, is less suitable as a travelling document because, for instance, it leaves no room for making notes, such as is required for visa, and, moreover, because the required equipment will not be available worldwide.

SUMMARY OF THE INVENTION

The present invention intends to provide for an identity card of the type as referred to in the introduction, which is

highly fraud-proof and, nevertheless, has general applications, such as a travelling document which can be used worldwide without advanced ancillary equipment being absolutely required.

In order to achieve the intended objective a type of identity card according to the present invention, is characterised in that a removable information carrier has been installed in an input unit of a housing which is also easy to handle, that housing has been provided with reading equipment capable of reading the personal data stored in the memory of the information carrier and in that the housing is provided with representation means in order to represent the data read.

In this type of identity card the actual personal information and identification data are located in the memory of the information carrier. The identification data include, at least among others, the physical characteristics of a user, such as e.g. his picture, fingerprint, voice, iris etc. which are digitally stored in the memory. Provided that the appropriate equipment is available, a fully electronic comparison can be made with a digitised registration of the user by means of, for instance, a camera, a sensor (system) or another type of registration means which has been connected to an electronic identification system. To this end, the information carrier is removed from its housing and entered into reading equipment provided for in this identification system. In this way a fully automatic identification may take place in which the subjective interpretation of a controlling officer is avoided and the probability of mistakes related to this is eliminated. However, if this equipment is not available, e.g. in case of apprehension of the user on the street or in a country in which the infrastructure required for automatic identification is not up to standard, the housing of the identity card at least provides for the primary reading and representation means in order to be able to at least establish the alleged identity of its user. In this way the invention provides for an identity card which is compatible with both modern, progressive identification methods and a more conventional method of identification.

In addition, a special embodiment of the identity card is according to the present invention characterised in that a sheet which may or may not be folded, is attached to the information carrier, so that the identity card is also suited as international travelling document just as the present-day passport. In addition, the folder also leaves room for notes and stamps of the authorised government institutions such as visa and the like, possibly in combination with a printed version of the personal data as also registered in the memory of the information carrier, and a passport photograph of the user. In countries which have or will acquire a fully electronic identification system for their cross-border traffic, such as for instance described in this patent application these notes and visa, if desired, can be entered directly into the memory of the information carrier which will then make a folder superfluous. The folder, however, ensures that the identity card remains compatible with the identification procedures as presently applied worldwide.

A further elaboration of the above-mentioned special embodiment of the identity card according to the present invention is characterised in that the information carrier is accompanied by a second information carrier with a sheet attached to it which may or may not be folded, in that both information carriers have been incorporated collectively in the input unit of the housing and in that both information carriers contain a unique encrypted code in a memory which can be electronically read, and in that means are present in order to establish a correspondence between the codes of both information carriers and signal a difference, if any, between both codes by means of the representation installation.

In this case, the primary identity card is formed by the first information carrier which is separated from the second information carrier, the latter is mainly intended to house the folder with notes and visa of the competent authorities, possibly in combination with a printed version of the personal data as also stored in the memory of the first information carrier, together with a passport photograph. In the case of internal identification and also in the case of cross-border traffic of persons without a visa being required, the first information carrier will normally suffice. However, for those countries which require a written visa or other written notifications before access within the boundaries is granted, the second information carrier which contains a folder for written notes may be used. The unique codes of both information carriers ensure that the second information carrier can only be used in combination with the accompanying first information carrier. Attempted malversation in this respect can be punished by means of a signal from the housing of the identity card itself, or, if necessary, by means of rendering the second information carrier, whether or not permanently, defective if this carrier is linked to the housing of another information carrier than the appropriate first information carrier.

The second information carrier may just as the first information carrier be equipped with a central processing unit in combination with an electronically readable memory. A further embodiment of the identity card is according to the present invention characterised in that the first information carrier, in addition to an electronically readable memory, also comprises a central processing unit and in that the second information carrier only contains an electronically readable memory. In this case, the second information carrier is only equipped with an electronically readable memory which results in considerable costs-saving. It is possible, for instance, to register all personal data in the memory of the second information carrier or only the unique code which indicates to which first information carrier the second one belongs.

In order to make it even more fraud-proof a further embodiment of the identity card according to the invention is characterised in that the information carrier is provided with one or more authenticity features. These authenticity features may for instance include characters punched through the card or other signs in the information carrier, and, for instance, a hologram on the card. In this way the genuineness of the identity card can be guaranteed even more and abuse can be combated.

A comparison of physical characteristics which are registered on site and stored in the information carrier of the identity card can be carried out in a fully electronic and automatic manner. In view of this a special embodiment of the identity card according to the invention is characterised in that the information carrier includes a central processing unit which has been provided with means for electric data transfer with a terminal unit of an identification system, and in that the central processing unit, which is fed with an effective programming code from the memory, is capable of comparing the stored external characteristics of the user with the external characteristics of the user registered on site. This type of identity card itself contains the processing unit required for the comparison to be carried out, and arithmetical ability, so that the identification system does not have to provide for this. The identification system will then only comprise registration means in order to incorporate specific physical characteristics of a user of the identity card, which registration means are linked up to the above-mentioned terminal unit from which the recorded data can be read by the processing unit of the identity card and subsequently, can be compared with the

stored data in the identity card itself. This does not only simplify the infrastructure required at the check point location, but is also beneficial to the processing speed if various checks which otherwise possibly were to be managed by one processing unit only, are now executed in a parallel manner.

In order to avoid error messages as a result of external changes of the user as well as to enhance the processing speed of the comparison referred to above, a preferred embodiment of the identity card according to the present invention is characterised in that the personal data comprise the user's physical characteristics in parameters. Storage in parameters does not in the first place involve a picture of the user, but rather characteristic features like e.g. the eye to eye distance, the angles enclosed between eyes and nose or mouth, etc. Obviously, these external parameters of the user are less subject to changes than e.g. wearing spectacles, beard and hair growth or the presence of make up, enabling a more reliable comparison.

In addition, other physical characteristics of the user, such as specific length and width measurements and fingerprint data, may also be registered in this manner, whether or not in combination with these. By means of combining and storing these in themselves independent physical features and checking these, a virtually 100% airtight access control may be achieved. In this respect a special embodiment of the identity card is characterised in that, among others, the voice of the user is also stored digitally therein.

In order to protect the privacy and also in order to avoid forgery and falsification, the various data in the information carrier's memory are preferably stored in encrypted form. The data are thus protected against access by third parties and encryption by means of present-day encryption techniques may be also executed in such a complicated manner that falsification or forgery of identity proof is almost impossible without specific knowledge of the applied key. Moreover, the data are preferably protected by means of a unique access code. Only the rightful user of the identity card knows this unique access code, e.g. in the form of a personal identification number (PIN), which makes it impossible for a subsequent holder to use the identity card and read the data without knowledge of the access code.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will now be explained in further detail by means of an embodiment and an accompanying drawing. The drawing consists of:

FIG. 1 showing a schematic view of a possible embodiment of an identity card according to the present invention; and

FIG. 2 which shows a schematic elaboration of an exemplary embodiment of an identification system for the application of an identity card according to the present invention.

DETAILED DESCRIPTION OF THE INVENTION

The drawing as a matter of fact is purely schematic and not drawn to scale. Particularly, for clarity's sake, some dimensions have been represented in a strongly exaggerated manner. Corresponding parts have been indicated in the figure with the same reference number as much as possible.

The identity card of FIG. 1 comprises a card-shaped, synthetic housing 100 with an input unit 101 for entering an information carrier 107 which, in this case, is also card-shaped just as the housing. The interior of the input unit 101 of the housing has been equipped with electric contacts which are able to cooperate with similarly applied contact surfaces 109 of an integral circuit 108 which has been connected to or

5

installed in the information carrier **107**. In addition, the housing comprises an electric feeding which, among others, takes care of the necessary electricity supply to the card by means of some of the above-mentioned contacts. Moreover, the housing **100** contains an installation for image representation linked to a screen **103** and reading equipment by means of which the data stored in the memory of the information carrier **107** can be read to be represented on the screen. If desired, one may, for that matter, opt for an audio representation instead of or in addition to the visual representation.

In practice, a number of personal data in combination with one or more of the user's physical characteristics will be stored in the memory of the information carrier **107** enabling the personal data to be represented on the screen **103** without the necessary ancillary equipment. This makes it possible to apply the identity card world-wide. By means of a command key **104** installed on the housing for this purpose the various personal data can be checked one by one, so that a relatively small screen will suffice for the representation of all relevant personal data.

The identity card in this example comprises in addition to the first information carrier **107**, also a second information carrier **207** which has been provided with a folded sheet **210** suited for making notes. This sheet leaves room for notes by the competent authorities e.g. visa, so that the identity card according to the present invention is also suitable as a valid travelling document. During use both information carriers are collectively entered into the housing which has been designed with the appropriate internal dimensions. The second information carrier also comprises an integral circuit **208** with at least an electronically readable memory. In this memory a unique code has been stored in encrypted form; this code is also present in the memory of the first information carrier. The identity card will only function if the codes in both information carriers **107**, **207** fully correspond; in case of any differences this will be represented in the screen **103** as an error code. If desired, the processing unit on the first information carrier **107** may also be programmed in such a way that a faulty second information order to immediately combat any fraudulent attempts.

An electronically readable memory in the second information carrier in itself suffices and it is not necessary to also provide for a central processing unit. In order to save costs, the second information carrier in this case has therefore been designed with an electrically programmable memory only, a so-called PROM, whereas the first information carrier also contains a full microprocessor in order to execute the identity control and activate the screen **103** of the housing.

An identification system to be used in combination with the identity card according to the invention has been schematically represented in FIG. **2** this identification system comprises a central processing unit in the form of a computer **1** which has been connected to both a screen **2** and registration tools in order to register the features, either external or not, of a person to be identified **6**. In this example the registration tools comprise a camera **3** and a microphone **4**, as well as a sensor **9** by means of which a fingerprint can be read. In addition to this, a terminal unit **5** has been connected to the computer **1**.

In order to identify a person **6**, this person's picture is recorded with a camera **3** and this person's voice is recorded with a microphone **4**. Moreover, a fingerprint is taken electronically by means of the sensor **9** and then digitised. The analogue signal which is emitted from microphone **4**, is digitised and analysed by computer **1** after which the digital voice data are sent to terminal unit **5**. The picture registered by the camera, whether or not processed, is sent by the central com-

6

puter **1** to terminal **5** in a similar fashion. In this case, a digital camera **3** is assumed, but within the framework of the invention an analogue camera may just as well be applied in which case its picture is digitised by means of well-known techniques such as a frame grabber in combination with an analogue-digital converter.

The person to be identified **6** has an identity card according to the invention consisting of a card-shaped information carrier **7** of handy credit card dimensions, of the type as referred to above. The information carrier **7** has been manufactured from synthetic material and contains an integral circuit linked to an electronically readable memory. Such a carrier is generally referred to as chip card, smart card or similar names. The memory of the card **7** contains the personal data of the user **6** recorded in digital form, including data concerning the physical features and in this case, in addition to a digital passport photograph and personal data, the user's voice and fingerprint as well. The information carrier **7** is manually entered into the slot of the terminal unit after which the data from the computer **1** are transferred to the card **7**. These data are processed in the card by means of the integral circuit and compared to the stored personal characteristics. To this end, the integral circuit comprises a central processing unit which is activated by an appropriate program code which is loaded onto the card from the memory. In addition to this, the circuit comprises reading equipment in order to read the personal data stored in the memory of the card. Thus card **7** comprises all means for fully executing the actual identification on the card itself. The results of the identification procedure may be represented visually, e.g. on screen **2**, acoustically or both acoustically and visually. Screen **2** may also serve to represent the user's passport photograph **6** as read from card **7**, so that the controlling officer of service is also able to execute a manual identification control.

For that matter, the various personal data of card holder **6**, such as name, address and permanent domicile or place of residence, as well as birth register data, eye colour, length, etc., possibly in combination with a passport photograph may, in addition to registration in the card's memory, of course also be registered on the card **7** in the conventional way enabling a quick identity control of the user on the basis of these data. Furthermore, the card may also be provided with e.g. an indication of the country or company, whether or not in combination with the according logo and authenticity features, such as for instance particularly a hologram or characters punched into the card, in order to combat forgery.

The personal data in the card's memory **7** comprise various characteristic external features in parameters, particularly concerning the user's external features **6**, in order to minimise the influence of cosmetic changes in the user's external features **6** and to enhance the processing speed. These features may include the eye to eye distance, the enclosed (tri)angle between eyes on the one hand, and nose, mouth or chin on the other hand, the relative position of the ears and the like. Characteristic features like these are not or hardly influenced by the use of make up changing beard or hair growth, glasses and other cosmetic external changes which often considerably hinder a conventional identification.

In order to protect the stored personal data, especially in the case of loss or theft, the card **7** can be linked to a unique access code which the user **6** is to enter first before identification takes place and the personal data are made accessible. Entering this access code may take place by means of the key board **8** of the computer unit **1** or the system may be expanded with a separate input unit designed for this use. For increased protection the personal data are stored in encrypted form so that the data cannot be read outside of the integral circuit of

the card. The present-day encryption techniques allow for encryption which is so adequate that decoding without knowledge of the encryption key applied is virtually impossible.

In this way the invention provides for a highly efficient and reliable identification system, using an identity card according to the present invention which can be applied on a large scale, not only as official travelling documents such as a passport, driving licence, visa, etc. but also within secured institutions such as company premises and, last but not least, military premises.

Although the invention has been clarified by means of this exemplary embodiment only, it goes without saying that the invention is by no means restricted to this one embodiment. On the contrary, many variations and embodiments can be realised by an average professional in this area without him being required to go beyond the scope of the invention. If desired, the invention may in this way be expanded by further registration tools in order to establish features, whether or not external, of the person to be identified, or the registration tools may, for instance, be restricted to only a camera or sensor (system) in order to record the picture, the fingerprint or eye characteristics. Instead of a more advance chip card, it is also possible to use, less complex card-shaped or otherwise shaped body as information carrier which, however, may contain a memory which can only be read by means of the terminal. Processing and comparing the to personal data will in this case entirely take place outside of the card itself, e.g. in the system's central computer unit as described above.

The data transfer in the terminal may take place by means of physical contact between the electrical contacts on the card on the one hand and in the terminal on the other hand. However, it is also possible to transfer the data without the contacts. In which case the transfer for instance, takes place optically, by means of radiography or induction.

The invention may also be applied more broadly than within the strict sense of person identification only, which use is restricted to obtaining the user's identity. The invention may for instance be incorporated in credit cards, cash cards and the like, for the purpose of verifying the data of its rightful user. To this end, the card in question will not only be equipped with data and/or software enabling the desired payments to be made, but also with digital personal data and characteristics in accordance with the invention. If the card is used, the identity of the user will then be determined, e.g. on the basis of a scan or the fingerprint or a recording of the external characteristics, and the payments can only be made after this has been electronically confirmed. In this way the invention provides for a virtually fraud-proof means of payment, which, among others, is not susceptible to loss or theft and the like. More over the identity card according to the present invention can also be programmed in such a way that it is suited as multiple identity card for various environments. For instance as travelling document, driving licence, and proof of access for one or more company premises or events. Moreover, the housing of the identity card according to the present invention is not restricted to the example given. It may for instance be expanded by a sound generator in order to enable an audio, or even spoken representation or signaling. One may also apply a more sophisticated screen in order to e.g. fully represent a passport photograph stored in the memory of the information carrier. In addition, the single command key may be replaced by a number of similar keys or even a full numeric or alphanumeric key board for the purpose of making the control of the identity card even more comfortable.

In short, the invention provides for an intelligent identity card which has no or hardly any restrictions when it comes down to ease of operation, protection against fraud and usability.

What is claimed is:

[1. An identity system comprising:

a card-shaped information carrier having an electronically readable memory capable of storing a user's personal data in digital form including data concerning physical characteristics of the user;

a housing having (a) an input unit for receiving the information carrier, (b) reading means capable of reading the personal data stored in the memory of the information carrier and (c) representation means for representing the data read; and

a second information carrier having a sheet attached, both information carriers jointly accommodated in the input unit of the housing, and a unique encrypted code stored in both carriers in an electronically readable memory, and means available to establish code correspondence of both information carriers and to signal the difference by means of a representation installation.]

[2. The system according to claim 1 wherein the card-shaped information carrier in addition to an electronically readable memory, also comprises a central processing unit and that the second information carrier only contains an electronically readable memory.]

[3. The system according to claim 1 wherein the personal data comprise the user's external characteristics in parameters.]

[4. The system according to claim 1 wherein the personal data have been protected by means of a unique access code.]

[5. The system according to claim 1 wherein the card-shaped information carrier further comprises further comprises one or more authenticity features.]

[6. The system according to claim 1 wherein the card-shaped information carrier comprises a central processing unit having means for electric data transfer with a terminal unit of an identification system, and in that the central processing unit, activated by means of an adequate program code from the memory, is capable of comparing the user's external features as stored in the memory to the user's external features recorded on site.]

[7. The identity system of claim 1, wherein the housing is approximately the same size as the card-shaped information carrier.]

8. A portable information carrier device, comprising: a memory to store personal characteristics parameter data of a user; and

processing circuitry executing instructions to compare personal characteristics parameter data derived from externally generated personal characteristics data with the stored personal characteristics parameter data within the portable information carrier device and to provide a result for indicating if the stored personal characteristics parameter data matches the generated personal characteristics parameter data, wherein personal characteristics parameter data is derived from personal characteristics data utilizing knowledge of a type of characteristic depicted in the personal characteristics data.

9. The portable information carrier device of claim 8, wherein at least one of the generated personal characteristics parameter data and stored personal characteristics parameter data is encrypted.

10. The portable information carrier device of claim 9, wherein encrypted stored personal characteristics parameter data is maintained in the portable information carrier device and cannot be read out of the portable information carrier device.

11. The portable information carrier device of claim 9, wherein encrypted stored personal characteristics parameter data can be read out of the portable information carrier device with an access key or code.

12. The portable information carrier device of claim 8, further comprising:

an interface to receive externally generated personal characteristics data or personal characteristics parameter data derived from the externally generated personal characteristics data.

13. The portable information carrier device of claim 11, wherein the generated personal characteristics parameter data or the externally generated personal characteristics data is communicated through a wired or wireless medium to the portable information carrier device.

14. The portable information carrier device of claim 8, wherein the processing circuitry compares the stored personal characteristics parameter data with the derived personal characteristics parameter data and provides a result for indicating that the stored personal characteristics parameter data matches the derived personal characteristics parameter data.

15. The portable information carrier device of claim 14, wherein the processing circuitry further provides a result for a user detectable indication or a machine readable indication if the stored personal characteristics parameter data matches the derived personal characteristics parameter data.

16. The portable information carrier device of claim 8, wherein the processing circuitry includes digital logic.

17. The portable information carrier device of claim 8, wherein the processing circuitry includes digital logic and optionally includes one or more microprocessors.

18. An information carrier device, comprising:

a memory to store user related personal characteristic parameter data for identifying the user;

integrated circuitry to determine an identity of the user by comparing stored personal characteristics parameter data of the user with personal characteristics parameter data derived from externally generated personal characteristics data and to provide an indication if the identity is the user; and

a sheet attached to the information carrier device, the sheet providing user related information,

wherein personal characteristics parameter data is derived from personal characteristics data utilizing knowledge of a type of characteristic depicted in the personal characteristics data.

19. The information carrier device of claim 18, wherein the stored user related personal characteristic parameter data is encrypted.

20. The information carrier device of claim 18, wherein the information carrier device is a travel document.

21. The information carrier device of claim 18, wherein the sheet includes space for notes, stamps, or photographs.

22. A portable information carrier device, comprising:

a memory to store personal user data comprising personal characteristic parameter data of the user, characterized in that said personal user data comprises personal characteristic parameter data derived from personal characteristic data of the user; and

processing circuitry which executes instructions to compare derived personal characteristic parameter data derived from externally generated personal characteristic data with said personal characteristic parameter data of the user which is stored in said memory and to provide a result indicating if the stored personal characteristic parameter data matches the externally generated derived personal characteristic parameter data, wherein personal characteristics parameter data is derived from personal characteristics data utilizing

knowledge of a type of characteristic depicted in the personal characteristics data.

23. The portable information carrier device according to claim 22 characterized in that the externally generated personal characteristic data were generated by a camera, and in that the personal characteristic parameter data includes at least one of the following parameters: the eye to eye distance, the enclosed (tri)angle between eyes on the one hand, and nose, mouth or chin on the other hand and the relative position of the ears.

24. The portable information carrier device according to claim 22, wherein the personal user data comprises encrypted data.

25. The portable information carrier device according to claim 22, wherein a portion of the personal user data stored in said memory are protected by an access key or code.

26. The portable information carrier device according to claim 22, wherein the portable information carrier comprises an interface to exchange data with an external identification system.

27. The portable information carrier device according to claim 26, wherein the derived personal characteristics parameter data is communicated through a wireless medium to the portable information carrier device.

28. A travel document, comprising:

a sheet; and

a portable information carrier device permanently attached to said sheet,

wherein the sheet provides user related information identifying the user and the information carrier device comprises a memory to store personal user data, including

personal characteristic data of the user, characterized in that said personal characteristic data comprises personal characteristic parameter data derived from personal characteristic data of the user, and in that the information carrier device comprises processing circuitry which executes instructions to compare derived

personal characteristic parameter data derived from externally generated personal characteristic data with said personal characteristic parameter data of the user which is stored in said memory and to provide a result

indicating if the stored personal characteristic parameter data matches the externally generated derived personal characteristic parameter data,

wherein personal characteristics parameter data is derived from personal characteristics image data utilizing knowledge of a type of characteristic depicted in the personal characteristics data.

29. The travel document according to claim 28, wherein the externally generated personal characteristic data were generated by a camera, and in that the personal characteristic parameter data includes at least one of the following parameters: the eye to eye distance, the enclosed (tri)angle between eyes on the one hand, and nose, mouth or chin on the other hand and the relative position of the ears.

30. The travel document according to claim 28, wherein the personal user data comprises encrypted data.

31. The travel document according to claim 28, wherein a portion of the personal user data stored in said memory are protected by means of an access key or code.

32. The travel document according to claim 28, wherein the portable information carrier comprises an interface to exchange data with an external identification system.

33. The travel document according to claim 32, wherein the externally generated personal characteristic parameter data is communicated through wireless medium to the portable information carrier device.