

(10) **Pub. No.: US 2010/0134563 A1**  
(43) **Pub. Date: Jun. 3, 2010**

2003, now Pat. No. 6,899,480, which is a continuation of application No. 09/662,210, filed on Sep. 15, 2000, now Pat. No. 6,612,240.

### Publication Classification

(51) **Int. Cl.**  
*B41J 2/14* (2006.01)

(52) **U.S. Cl.** ..... **347/49**


(57) **ABSTRACT**

A modular printer includes a housing having an upper and lower cover, a first side wall having an air duct with an air inlet, and a second side wall defining air exit vents, the air duct, air inlet and air vent facilitating ducting of warm air over print media passing through the housing; entry and exit media feed roller assemblies located at opposite ends of the housing for feeding the print media through the housing, each roller assembly having a pair of rollers with a print media feed path interposed between the rollers; and a print engine having two opposing printhead assembly, each printhead assembly having two arcuate printheads. Each printhead has a radius of curvature approximating a radius of the rollers.

(22) Filed: **Dec. 29, 2009**

### Related U.S. Application Data

(63) Continuation of application No. 11/965,718, filed on Dec. 27, 2007, now Pat. No. 7,648,294, which is a continuation of application No. 11/650,553, filed on Jan. 8, 2007, now Pat. No. 7,329,061, which is a continuation of application No. 10/982,844, filed on Nov. 8, 2004, now Pat. No. 7,217,046, which is a continuation of application No. 10/636,280, filed on Aug. 8,






FIG. 1




FIG. 2

FIG. 4




FIG. 3




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9






FIG. 10




FIG. 11




FIG. 12




FIG. 13






FIG. 15




FIG. 16





FIG. 17





## MODULAR PRINTER WITH ARCUATE PRINTHEADS

### CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] The present application is a Continuation of U.S. application Ser. No. 11/965,718 filed Dec. 27, 2007, which is a Continuation of U.S. application Ser. No. 11/650,553 filed on Jan. 8, 2007, now issued U.S. Pat. No. 7,329,061, which is a Continuation of U.S. application Ser. No. 10/982,844 filed on Nov. 8, 2004, now issued U.S. Pat. No. 7,217,046, which is a Continuation of U.S. application Ser. No. 10/636,280 filed on Aug. 8, 2003, now issued U.S. Pat. No. 6,899,480, which is a Continuation of U.S. application Ser. No. 09/662,210 filed on Sep. 15, 2000, now issued U.S. Pat. No. 6,612,240 all of which are herein incorporated by reference.

### FIELD OF THE INVENTION

[0002] This invention relates to a modular printer. The invention relates particularly, but not necessarily exclusively, to a modular commercial printer for effecting high speed, digital, photographic quality, commercial printing. The invention relates specifically to drying equipment for a printer for aiding drying of a printed image on a web of print media.

### BACKGROUND TO THE INVENTION

[0003] In high speed printing, large printing presses are daisy-chained together to print predetermined pages of publications which are then secured together to form the publications. Such printing presses occupy an extremely large volume and are very expensive.

[0004] The applicant has also proposed a commercial printer using a number of floor mounted printers having page-width print heads. This commercial printer is intended for extremely high production rates such as up to five 180 page documents per second.

[0005] To achieve such high production rates, large quantities of consumables need to be readily available for the printers. Thus, once again, such a commercial printer needs to occupy an extremely large volume although the cost of such a printer is considerably lower than equivalent high end, commercial printers which do not use the applicant's Memjet (Memjet is a trade mark of Silverbrook Research Pty Ltd) technology.

[0006] The applicant has recognised a need for a commercial printer which occupies a smaller volume and which has a lower through put rate but of the same quality as the applicant's previously proposed Memjet commercial printer.

### SUMMARY OF THE INVENTION

[0007] According to an aspect of the present disclosure, a modular printer includes a housing having an upper and lower cover, a first side wall having an air duct with an air inlet, and a second side wall defining air exit vents, the air duct, air inlet and air vent facilitating ducting of warm air over print media passing through the housing; entry and exit media feed roller assemblies located at opposite ends of the housing for feeding the print media through the housing, each roller assembly having a pair of rollers with a print media feed path interposed between the rollers; and a print engine having two opposing printhead assembly, each printhead assembly having two

arcuate printheads. Each printhead has a radius of curvature approximating a radius of the rollers.

### BRIEF DESCRIPTION OF THE DRAWINGS

[0008] The invention is now described by way of example with reference to the accompanying drawings in which:—

[0009] FIG. 1 shows a three dimensional view of a printer, in accordance with the invention;

[0010] FIG. 2 shows a plan view of the printer;

[0011] FIG. 3 shows a side view of the printer;

[0012] FIG. 4 shows an end view of the printer;

[0013] FIG. 5 shows a three dimensional view of a printer stack, in accordance with one embodiment of the invention;

[0014] FIG. 6 shows a three dimensional view of a printer stack, in accordance with another embodiment of the invention;

[0015] FIG. 7 shows a three dimensional view of the printer including its fluid connections;

[0016] FIG. 8 shows a detailed, three dimensional view of part of the printer;

[0017] FIG. 9 shows a three dimensional, exploded view of the printer;

[0018] FIG. 10 shows a three dimensional view of a print engine of the printer;

[0019] FIG. 11 shows a sectional end view of the print engine;

[0020] FIG. 12 shows, on an enlarged scale, part of the print engine;

[0021] FIG. 13 shows a three dimensional view of one of the print head assemblies of the print engine;

[0022] FIG. 14 shows a three dimensional, exploded view of one of the print head assemblies;

[0023] FIG. 15 shows a sectional side view of a print media loading mechanism of the printer, in its loading configuration;

[0024] FIG. 16 shows a sectional side view of the loading mechanism of the printer in its open, non-loading configuration;

[0025] FIG. 17 shows a three dimensional view of the loading mechanism in its non-loading configuration; and

[0026] FIG. 18 shows a three dimensional, exploded view of the loading mechanism in its loading configuration.

### DETAILED DESCRIPTION OF THE DRAWINGS

[0027] Referring to the drawings, reference numeral 10 generally designates a printer, in accordance with the invention. The printer 10 is a modular printer to be used in combination with other, identical printers, as will be described in greater detail below for effecting high speed, digital, photographic quality, commercial printing. Arrays of the printers 10 can be combined to provide scalable printing systems. However, single printers 10 may also be used individually, if desired.

[0028] The printer 10 comprises a housing 12. The housing 12 is made up of an upper cover 14, a lower cover 16 (FIG. 9), a first side wall 18 and a second, opposed side wall 20 (FIG. 9). Each side wall 18, 20 terminates in an end cap or cheek molding 22. Each cheek molding 22 is the same to reduce the costs of production of the printer 10. Each cheek molding 22 has a slot in which an application-specific insert 24 is received.

[0029] The housing 12 surrounds a frame 26. Internal components of the printer 10 are supported on the frame 26.

[0030] Opposed cheek moldings 22 at each end of the housing 12 support a guide roller 28 adjustably between them. Thus, each cheek molding 22 defines an arcuate slot 30 within which an axle of its associated roller 28 is received.

[0031] As described above, it is intended that, for commercial printing applications, a plurality of the printers 10 will be used together. As illustrated in FIGS. 5 and 6 of the drawings, the printers 10 are stacked together to form a stack 40. In the embodiment illustrated at FIG. 5, the stack 40 is arranged on a support table 42. A lowermost printer 10 in the stack 40 is locked to the table 42 by means of locking feet 44 of the printer 10. The locking feet 44 of each subsequent printer 10 in the stack 40 are received in associated holes 46 in a top of a subjacent printer 10. Each locking foot 44 has a bayonet fitting so that, when the foot 44 is inserted into one of the holes 46 of the subjacent printer or the table 42, as the case may be, a quarter turn of the foot 44 locks the upper printer 10 with respect to the subjacent printer 10 or the table 42.

[0032] As illustrated in FIG. 5 of the drawings, the printers 10, when stacked horizontally, may be offset with respect to each other by locking the locking feet 44 of one printer 10 into the appropriate holes 46 of the subjacent printer. Hence, a plurality of serially aligned holes 46 is arranged adjacent each cheek molding 22. By appropriate selection of the holes 46, the requisite degree of offset, if any, can be achieved.

[0033] The offset stacking of the printers 10 allows print media, such as paper 48, to be fed from unwinders (not shown) into each of the printers 10 at a predetermined angle and to be fed out of the printers 10 at a suitable exit angle. If the paper 48 is to be fed in and out of the printers 10 horizontally, the printers 10 of the stack 40 are vertically aligned with respect to each other.

[0034] In FIG. 6, another embodiment of the stack 40 is shown. In this embodiment, the printers 10 are arranged vertically and are spaced horizontally with respect to each other. In the example illustrated, paper 48 is fed into each printer 10 at an upper end of the printer and is fed out, after printing, through a bottom of each printer 10. The stack 40 is supported on a framework 49 with the printer at one end of the stack 40 being locked to an end plate 51 of the framework 49 via its locking feet 44. Adjacent printers 10 in the stack 40 are locked together by inserting the locking feet 44 of one printer 10 into the appropriate holes 46 of the adjacent printer 10. A control console 54 is provided for controlling operation of the printer stack 40.

[0035] Each printer 10 communicates with its controller and with other printers in the stack 40 via a USB2 connection 50 received in a double USB port arrangement 52. The port arrangement 52 has an inlet port and an outlet port for enabling the printers 10 of the stack 40 to be daisy-chained together and to communicate with each other.

[0036] Each printer includes a print engine 56 made up of a pair of opposed print head assemblies 54 for enabling double-sided printing to be effected. The print head assembly 54 (FIG. 11) of the print engine 56 of the printer 10 can print in up to twelve colors. As will be described in greater detail below, each print head assembly 54 is a duplexed print head so that, if desired, six colors, duplicated, can be printed by each print head assembly 54. Ink is fed to the print engine 56 via an ink coupling box 58. The coupling box 58 supports twelve ink couplings 60 thereon. Ink hoses 64 are coupled to the coupling box 58 via the couplings 60 and communicate with the print head assemblies 54 of the print engine 56 via an ink connector 62 (FIG. 9). A power connection port 66 is also

supported on the ink coupling. The port 66 is received through an opening 68 in one of the inserts 24 of one of the cheek moldings 22. The same insert 24 supports an air coupling 70. An air hose 72 (FIG. 7) feeds air to the print head assemblies 54 of the print engine 56 to maintain print head nozzles (not shown) of the print head assemblies 54 free of debris and foreign matter.

[0037] A roller assembly 74 is mounted at an inlet end of the printer 10. The roller assembly 74 includes a drive roller 76 and a driven roller 78. The drive roller 76 is driven by a drive motor 80 supported on a metal bracket 82. The metal bracket 82 is mirrored by a corresponding bracket 84 at an opposed end of the roller assembly 74. The brackets 82 and 84 are supported on the frame 26.

[0038] In addition, a similar, exit roller assembly 86 is provided at an outlet end of the printer 10. Once again, the roller assembly 86 has a drive roller 88 driven by a drive motor 90 and a driven roller 92. The rollers 86 and 92 are supported between metal brackets 94 and 96. The brackets 94 and 96 are secured to the frame 26. The bracket 94 also supports the motor 90.

[0039] The drive roller 76 drives the driven roller 78 via a set of helical gears 132. A similar arrangement applies in respect of the roller 88 and 92 of the roller assembly 86.

[0040] The cheek molding 22, at the inlet end of the printer 10, opposite the molding 22 supporting the air coupling 70, also supports a USB control PCB 98.

[0041] The print engine 56 is supported by a chassis comprising a pair of opposed metal brackets 100, 102 mounted downstream (in a direction of feed of the paper) of the roller assembly 74. Each metal bracket 100, 102 supports one of the print head assemblies 54 of the print engine 56.

[0042] The print engine 56 is shown in greater detail in FIGS. 10 to 12 of the drawings. As described above, the print engine 56 comprises two print head assemblies 54. The print head assemblies 54 are arranged in opposed relationship to enable double sided printing to be effected. In other words, the paper 48 passes between the print head assemblies 54. The brackets 100, 102 support the print head assemblies 54 and position the print head assemblies 54 approximately 0.75 mm apart from the web of paper 48. This distance is automatically adjusted by the brackets 100, 102 to maintain constant spacing with varying paper thickness.

[0043] In addition, as will be described in greater detail below, print heads of the print head assemblies 54 are so designed as to allow for close proximity to the rollers 76 and 78 resulting in a closely controlled paper to print head gap.

[0044] Each print head assembly 54 comprises a first print head 104 and a second, adjacent print head 106. Each print head 104, 106, further, is made up of two modules 104.1 and 104.2 and 106.1 and 106.2, respectively.

[0045] The modules 104.1 and 106.1 are coupled together and are controlled by a first printed circuit board (PCB) 108. Similarly, the modules 104.2 and 106.2 are coupled together and are controlled by a second printed circuit board (PCB) 110. PCB's 108 and 110 communicate with print head chips 112 of the print heads 104 and 106 via flex PCB's 114. These flex PCB's 114 terminate in terminal pads 116 on moldings 118 of the modules 104.1, 104.2, 106.1 and 106.2 of the print heads 104 and 106. The terminal pads 116 communicate with corresponding pads (not shown) of the PCB's 108, 110.

[0046] It is to be noted that the moldings 118 are mirror images of each other, each having ink inlets 120 at a free end thereof. Ink is fed in at one end of interconnected moldings

**118** only so that the inlets **120** not being used are plugged by appropriate plugs. Also, the PCB's **108**, **110** are mirror images of each other. This reduces the cost of production of the printer **10** and also enables rapid and easy assembly of the printer **10**. The PCB's **108** and **110** communicate with each other via a serial cable **122**. One of the PCB's **108**, **110** is connected via a connector **124** to the USB circuit board **98**.

**[0047]** Each PCB **108**, **110** includes two print engine controllers (PEC's) **126** and associated memory devices **128**. The memory devices **128** are dynamic random access memory (DRAM) devices.

**[0048]** The molding **118** of each print head assembly **54** is supported on the frame **100**, **102** via an end plate **130** (FIG. 13).

**[0049]** The print engine **56** is shown in greater detail in FIG. 11 of the drawings. The print engine **56** comprises the two print head assemblies **54**. As previously described, each print head assembly **54** comprises two print heads **104**, **106**. Each print head **104**, **106** has a print head chip **112** associated therewith. The print head chips **112** of the print heads **104**, **106** are supported along a longitudinal edge portion of the moldings **118**. The edge portion of each molding **118** which carries the print head chip **112** is arcuate. The arcuate portion of each molding **118** has a radius of curvature which approximates that of the radius of the rollers **76**, **78**. This design of the print heads **104**, **106** allows for close proximity of the print head chips **112** to the rollers **76**, **78** resulting in a closely controlled paper to print head gap. In so doing the printhead chip **112** prints in a portion of the paper, which is taut, resulting in a more accurate deposition of ink drops on the paper **48**.

**[0050]** As illustrated more clearly in FIG. 12 of the drawings, an air channel **138** is arranged adjacent each print head chip **112** for feeding air to the print head chip **112** from the air hose **72**.

**[0051]** With this arrangement of print head assemblies **54**, either six colors or twelve colors can be printed. Where six colors are to be printed, these are duplicated in the print heads **104**, **106** of each assembly **54** by having the appropriate colored ink or related matter (referred to for convenience as "colors") in the relevant galleries **136** of the moldings **118**. Instead, each print head assembly **54** can print the twelve "colors" having the appropriate "colors" charged into the galleries **136** of the print heads **104**, **106**. Where six "colors" are to be printed, these are normally cyan, magenta, yellow and black. The remaining galleries **136** then have an ink fixative and a varnish. Where twelve "colors" are to be printed, the "colors" are cyan, magenta, yellow, black, red, green, blue, either three spot colors or two spot colors and infrared ink, and the fixative and the varnish.

**[0052]** The printer **10** is designed so that, where six "colors" are to be printed, the printer can print at a printing speed of up to 1,360 pages per minute at a paper speed of 1.6 m/s. Where twelve "colors" are to be printed, the printer **10** is designed to operate at a printing speed of up to 680 pages per minute at a paper speed of 0.8 m/s.

**[0053]** The high speed is achieved by operating the nozzles of the print head chips **112** at a speed of 50,000 drops per second.

**[0054]** Each print head module **104.1**, **104.2**, **106.1**, **106.2** has six nozzle rows per print head chip **112** and each print head chip **112** comprises 92,160 nozzles to provide 737,280 nozzles per printer. It will be appreciated that, with this number of nozzles, full 1600 dpi resolution can be achieved on a

web width of 18.625 inches. The provision of a web width of this dimension allows a number of pages of a document to be printed side-by-side.

**[0055]** In addition, matter to be printed is locally buffered and, as a result, complex documents can be printed entirely from the locally buffered data.

**[0056]** It is also intended that the amount of memory **128** installed on each board **108**, **110** is application dependent. If the printers **10** are being used for unchanging pages, for example, for offset press replacement, then 16 megabytes per memory module is sufficient. If the amount of variability on each page is limited to text, or a small range of variable images, then 16 megabytes is also adequate. However, for applications where successive pages are entirely different, up to 1 gigabyte may need to be installed on each board **108**, **110** to give a total of 4 gigabytes for the print engine **56**. This allows around 2,000 completely different pages to be stored digitally in the print engine **56**. The local buffering of the data also facilitates high speed printing by the printers **10**.

**[0057]** The spacing between the print engine **56** and the exit roller assembly **86** is approximately one metre to allow for a one second warm-set ink drying time at a web speed of the paper **48** of approximately 0.8 metres per second. To facilitate drying of the printed images on the paper **48** the fixative is used in one of the ink galleries **136**. In addition, warm air is blown into the interior of the printer **10** from a source (not shown) connected to an air inlet **140** (FIG. 1) via an air hose **142**. The air inlet communicates with a metal air duct **144** (FIG. 9) which blows the warm air over the paper **48** exiting the print engine **56**. Warm air is exhausted from the interior of the printer by means of vents **146** in the side wall **20** of the housing **12** of the printer **10**.

**[0058]** The printer **10** includes a print media loading mechanism **150** for loading the paper **48** into the interior of the printer **10**. The loading mechanism **150**, comprises a pair of opposed endless belts **152** (shown more clearly in FIGS. 15 to 18 of the drawings). Although not illustrated as such, these belts **152** are foraminous to enable the warm air ducted in through the duct **144** to be blown through the belts **152** over both surfaces of the paper **48**, after printing, in use. Each belt **152** passes around a pair of spaced rollers **154**. The rollers **154** are held captive to be vertically slidable in slides **156**. The slides **156** are mounted on the frame **26** of the printer **10**.

**[0059]** Each roller **154** is mounted at one end of an arm **158**. The opposed end of each arm **158** is connected at a common pivot point **160** to a traverser block **162** so that the arms **158** are connected to their associated traverser block **162** scissors-fashion. The traverser block **162** is, in turn, mounted on a lead or worm screw **164**. The worm screw **164** is rotatably driven by a motor **166** supported on a bracket **168**.

**[0060]** The rollers **154** are driven by a motor **170** (FIG. 18). When it is desired to load paper **48** into the printer **10**, the mechanism **150** is operated by a paper load button **172** (FIGS. 1 and 8). This causes the roller motor **170** to be activated as well as the motor **166**. Rotation of the motor **166** causes the traverser blocks **162** to move in the direction of arrows **174** to bring the belts **152** into abutment with each other. A leading edge of the paper **48** is fed between the belts **152**, is grabbed by the belts **152** and is fed through the printer **10** to exit through the exit roller assembly **86**. Once the paper **48** has been loaded, the direction of the motor **166** is reversed so that the traverser blocks move in directions opposite to that of arrows **174** causing the belts **152** to move to the position

shown in FIG. 16 of the drawings. Thus, during printing, the belts 152 are spaced from, and do not bear against, surfaces of the paper 48.

[0061] Accordingly, by means of the invention, a modular printer which can print at commercial printing speeds is provided for the printing of documents. Several modules can be arrayed in combination with inserting machines for published documents, such as magazines, with variable paper weights. In addition, print module redundancy allows paper splicing on a stopped web with no down time as the other printer modules in the stack 40 take up printing of the pages which would normally be printed by the out of operation printer 10. [0062] Each printer 10 is provided with its document printing requirements over the USB2 communications network (or optional Ethernet) from a work station such as the console 54.

[0063] Also, due to memory capacity of each printer 10, tens of thousands of images and text blocks can be stored in memory allowing completely arbitrary selections on a page by page basis. This allows the printing of matter such as catalogues and magazines which are highly customised for each reader.

[0064] It will be appreciated by persons skilled in the art that numerous variations and/or modifications may be made to the invention as shown in the specific embodiments without departing from the spirit or scope of the invention as broadly described. The present embodiments are, therefore, to be considered in all respects as illustrative and not restrictive.

I/We claim:

1. A modular printer comprising:

a housing having an upper and lower cover, a first side wall having an air duct with an air inlet, and a second side wall defining air exit vents, the air duct, air inlet and air

vent facilitating ducting of warm air over print media passing through the housing;

entry and exit media feed roller assemblies located at opposite ends of the housing for feeding the print media through the housing, each roller assembly having a pair of rollers with a print media feed path interposed between the rollers; and

a print engine having two opposing printhead assembly, each printhead assembly having two arcuate printheads, wherein

each printhead has a radius of curvature approximating a radius of the rollers.

2. The modular printer of claim 1, further comprising a print media loading mechanism including a pair of opposed endless belts between the entry and exit media feed rollers.

3. The modular printer of claim 2, wherein the belts are foraminous to enable warm air ducted through the duct to be blown through the belts over both surfaces of the print media after printing.

4. The modular printer of claim 2, wherein each belt passes around a pair of spaced rollers held captive and operatively vertically displaceable in slides mounted on a frame of the printer.

5. The modular printer of claim 4, wherein each roller is mounted at one end of an arm with opposed ends of each arm connected at a common pivot point to a traverser block, so that the arms are connected to their associated traverser block scissors-fashion.

6. The modular printer of claim 5, wherein each traverser block is mounted on a worm screw rotatably driven by a motor.

\* \* \* \* \*