



(22) Date de dépôt/Filing Date: 1997/02/03  
(41) Mise à la disp. pub./Open to Public Insp.: 1997/08/16  
(45) Date de délivrance/Issue Date: 2007/05/29  
(30) Priorités/Priorities: 1996/02/16 (DE196 05 810.4);  
1996/09/12 (DE196 37 195.3)

(51) Cl.Int./Int.Cl. *C10J 3/08* (2006.01),  
*C10B 53/00* (2006.01), *C10J 3/57* (2006.01)  
(72) Inventeur/Inventor:  
KISS, GUNTER H., CH  
(73) Propriétaire/Owner:  
THERMOSELECT AG, LI  
(74) Agent: MCFADDEN, FINCHAM

(54) Titre : METHODE DE FONCTIONNEMENT D'UN REACTEUR A HAUTE TEMPERATURE POUR LE TRAITEMENT  
DES DECHETS  
(54) Title: METHOD OF OPERATING A HIGH-TEMPERATURE REACTOR FOR TREATMENT OF WASTE MATERIAL

(57) **Abrégé/Abstract:**

The invention relates to a method of operating a high-temperature reactor for treating heterogeneous waste materials, in which the waste materials are introduced via an intake point into the reactor and form beneath the intake point a loose-piled gasification bed, in which the inorganic or organic components are subjected to fusion or gasification and homogenisation by oxygen and above the intake point the gaseous gasification products are subjected to high-temperature treatment with added oxygen in order to form and stabilise synthesis gas, water-cooled oxygen lances being used for high-temperature treatment.



2196649

5

ABSTRACT

The invention relates to a method of operating a high-  
temperature reactor for treating heterogeneous waste  
10 materials, in which the waste materials are introduced  
via an intake point into the reactor and form beneath  
the intake point a loose-piled gasification bed, in  
which the inorganic or organic components are subjected  
to fusion or gasification and homogenisation by oxygen  
15 and above the intake point the gaseous gasification  
products are subjected to high-temperature treatment  
with added oxygen in order to form and stabilise  
synthesis gas, water-cooled oxygen lances being used  
for high-temperature treatment.

20

**Method of Operating a High-Temperature Reactor  
For Treatment of Waste Material**

5

The invention relates to a method of operating a high-temperature reactor for treating waste materials, in which these waste materials, such for example as domestic and/or industrial wastes, are subjected to a high-temperature treatment in a reactor, specially aligned oxygen lances being used for high-temperature treatment not only of the gaseous and liquid components but also of the solid components.

15 The most various methods and devices for high-temperature treatment of waste materials such as domestic and industrial wastes of all types are known from prior art. A method in which the waste materials of all types are firstly condensed and then, proceeding from this point, all the further process steps such as drying, de-gasification, gasification and melting are carried out without interruption, is known in specialist circles under the title "Thermoselect process" (DE 41 30 416, and literature source of

Gunther Hasler: "Thermoselect, the new way of treating residual wastes in an environmentally appropriate manner" Verlag Karl Goerner, Karlsruhe, 1995).

5 In this method, the thermally pre-treated waste materials are continuously introduced via an intake point into the high-temperature reactor. The waste materials thermally pre-treated in this manner form a gas-permeable pile in the reactor itself. By means of  
10 the addition of oxygen or of air enriched with oxygen to the piled column of the gasification bed, the carbon ingredients present are oxidised or gasified at the temperatures of more than 2000°C obtaining in the core of the gasification bed. The CO<sub>2</sub> occurring is reduced  
15 in a moderation chamber above the pile, i.e. in the top region of the high-temperature reactor, above the gasification bed, at temperatures of at least 1200°C, predominantly forming CO. At these temperatures the reaction equilibrium (producer-gas equilibrium) is  
20 moved towards CO. Due to the moisture in waste also introduced into the high-temperature reactor, the reaction  $H_2O + C \rightarrow CO + H_2$  (water gas reaction) takes place in parallel with the producer-gas equilibrium reaction. The synthesis gas resulting in all, which is

extremely economically usable in terms of material  
and/or energy, at such temperature guidance  
predominantly consists of CO, H<sub>2</sub> and small quantities  
of CO<sub>2</sub>. Organic contaminants, in particular also the  
5 highly toxic dioxins or furanes, are no longer stable  
in the temperature range in question and are reliably  
cracked. The metallic and/or mineral components of the  
waste on the other hand are fused in the lower burner  
zone and are withdrawn from the high-temperature  
10 reactor.

Provision is also made for homogenisation of the  
melted-down inorganic components with simultaneous  
separation of the minerals from the metals with phase  
15 separation in a temperature range of approximately  
1600°C to above 2000°C, before the melted and  
homogenised inorganic components harden after shock  
cooling with water jets. Cracking of the contaminants  
in the free gas space, the so-called moderation chamber  
20 above the gasification bed of the high temperature  
reactors, requires at that point precisely defined  
temperature conditions in each chamber sector, and  
specific delay times.

There are in particular two conditions which can impair the process. Firstly due to the possible extremely variable waste composition (above all with a high moisture content), the temperature of the synthesis gas in the delay chamber above the gasification bed can drop temporarily, and secondly, in the delay chamber above the gasification bed, laminar flow areas can form, which reduce the delay time of the synthesis gas for partial areas. This so-called lane or lane skin formation must under all circumstances be avoided in the moderation chamber. In both cases it cannot be excluded that traces of contaminants will remain in the synthesis gas and be released when it is exploited.

The possibility that ungasified carbon, for example in the form of fine particles brought in, will be located in the synthesis gas in the moderation chamber should be mentioned, in order to provide grounds for the necessity of secondary gasification in the gas chamber.

20

It is known from DE 195 12 249.6 that for the method described above for melting down the inorganic components, specially-designed oxygen lances are used. These oxygen lances are equipped with a permanently

burning pilot flame with a high flame temperature and a high combustion speed in such a way that the lance oxygen is accelerated at least approximately to the speed of sound. This is intended to achieve an improvement in melting. However, it is insufficient, in order to solve all problems occurring in the high temperature reactor, above all for optimising the process configurations in the moderation area above the pile, to improve only the conditions in the pile beneath the intake point.

The high-temperature treatment of waste materials is subject to exacting demands due to the heterogeneity of the supplied waste. Even the lances described above cannot provide complete assistance here, so that no optimal operating conditions for operating such a high-temperature reactor could be achieved with these lances, in particular with respect to the gasification in the upper reactor portion.

20

Proceeding from this point the object of the present invention is therefore further to develop the method described in detail above in such a way that as far as

possible optimum conversion both of the inorganic and of the gaseous components can be achieved.

It is in particular also a feature of one embodiment of the present invention to exclude loading of the synthesis gases with organic contaminants, and to improve the quality of the mineral residues.

In accordance with one embodiment of the present invention there is provided a method of operating a high-temperature reactor with an outlet for synthesis gas on a head and an outlet end for melted materials for treating heterogeneous waste materials, in which the waste materials are thermally pre-treated and/or compressed and introduced into the reactor via an intake point, and form beneath the intake point a loose, piled gasification bed, in which inorganic or organic components are subjected by oxygen to fusion, gasification and homogenisation, and above the intake point the gasification products are subjected in a free gas space of the high-temperature reactor to high-temperature treatment with supplied oxygen in order to form and stabilize a synthesis gas. The method is characterized in that water-cooled oxygen lances are used for high-temperature treatment, at least two oxygen lances being disposed beneath the intake point in such a way that they reinforce a flow direction of the fusing and melted materials, and in that above the intake point there are disposed at least two oxygen lances in such a way that they inhibit flow of ascending gaseous components.

Thus it is proposed according to the invention to carry out both high-temperature gasification of the gasifiable components in the upper region of the reactor, and also to carry out melting or fusion of the inorganic components in the lower part of the reactor by means of oxygen lances, the oxygen lances in the lower area being so aligned that they reinforce the flow direction of the melting or fused inorganic components, and in the upper region in such a way that they are opposed to the flow direction of the gasification components, so that an inhibition occurs.

The combination of combustion/oxygen lance is preferably so designed that a partial quantity of the oxygen necessary for combustion of the heating gas flows through the oxygen lances. In this way the nozzle of the lance, exposed to the highest temperature, is continuously cooled by this oxygen flow, even if no lance oxygen were necessary. By means of this measure the burner is protected from damage or from fouling of the UV monitoring glass, the back flow or diffusion of the pressurised gas of the high-temperature reactor being excluded in the interior of the oxygen lance, where otherwise an explosive mixture forms when the lance is out of operation.

By virtue of the fact that, in the upper area of the reactor, i.e. above the intake point, the oxygen lances are disposed contrary to the flow direction of the gasifying component, i.e. the ascending flow of the synthesis gases is braked, their delay time in the moderation zone is increased, so that both secondary gasification of any carbon components still brought in becomes possible, and the decomposition of all organic contaminants is ensured.

The oxygen lances, oriented in the flow direction of the mineral and metal components to be melted out within the pile in the reactor area beneath the intake point, at that point favour the desired separation of  
5 components, particularly when oxygen is used at a high flow velocity.

By virtue of the fact that oxygen is additionally introduced into the moderation zone in the form of a  
10 free gas chamber of the high-temperature reactor, under temperature control in such partial quantities, the temperature at this point can be kept absolutely constant by a partial combustion of the synthesis gas. The introduction of additional oxygen in addition  
15 offers the opportunity of subjecting the gas flow in the high temperature area to turbulence in such a way that laminar flow areas, which can form the so-called "through roads" for contaminants, no longer occur. An additional turbulence can be achieved in a simple way  
20 in that a plurality of oxygen nozzles for introducing the partial quantity of oxygen are used, which are axially and/or radially inclined. By means of the use of the oxygen lances in conjunction with turbulence of the gasifiable components, at the same time partially

non- or incompletely-gasified components are likewise subjected to gasification. It has become apparent that in operation of the reactor it cannot be excluded that there can be carried into the upper reactor portion, along with the pure gaseous components, also such components which are not yet or are only partially gasified. These components are now subjected to turbulence by the alignment of the lances according to the invention, are taken up and oxidatively converted and gasified by the supplied oxygen lances. In this way the combustion process is further optimised and progressed in the direction of a total formation of synthesis gas. It has become apparent that by means of this alignment according to the invention of the oxygen lances, not only does a "secondary gasification" of partially still ungasified or not-yet-completely gasified components takes place, but there also occurs, simultaneously under these operational conditions, a cracking of residual traces of organic contaminants still present in the gasification area. This also further contributes to optimum formation of synthesis gas. For high-temperature gasification at least two oxygen lances are aligned in the way described above.

Naturally it is also possible to provide more than two oxygen lances; a number of the oxygen lances can have an alignment which is different from that described above. For this purpose the oxygen lances need not be  
5 disposed in one plane; they may rather be spatially distributed over the gasification area.

If oxygen lances with at least one permanently burning adjustable pilot flame are used, the temperature  
10 necessary for removal of contaminants can in every case be maintained, independently of other parameters.

These oxygen lances are preferably stoichiometrically operated with synthesis gas inherent in the process, or  
15 even with externally-supplied fuels, so that they can be adjusted to the minimum temperature necessary for the respective high-temperature treatment. For high-temperature gasification, the reactor space above the intake point is kept at greater than 1000°C.

20 Dimensions of the reactor space are such that up to the reactor outlet there remains a delay time sufficient for adjustment of the equilibrium ratio, until the synthesis gas is shock cooled in order to avoid the new formation of organic compounds.

The oxygen lances in the lower area, i.e. for fusion or melting down of the inorganic components, are aligned according to the invention in such a way that they

5 reinforce the flow direction of the outflowing melt. Here also it is necessary according to the present invention that at least two lances be aligned in this direction. The procedure in this case is preferably such that a plurality of lances are provided to follow

10 the contour of the ellipsoid reactor base. The lances used for this purpose substantially correspond to the lances known from DE 195 12 249.6. Therefore express reference is made to the disclosed content of this document. The essential factor is that the lance

15 oxygen is accelerated at least approximately to the speed of sound, so that it is also capable of penetrating with sufficient pressure into the inorganic components to be fused or melted down. Due to the high velocity, clogging of the oxygen lance is also

20 prevented. This high-temperature treatment is preferably carried out at temperatures beneath 2000°C.

In a further development there is provision, in addition to the oxygen lances described above, to

dispose further burners in the homogenisation area, in the region of fusion and melting-down. In the method according to the invention there is provision to design the area for homogenisation in such a way that an

5 almost complete homogenisation of the fused inorganic components can be effected. In support there is provision for disposing in the homogenising portion of the reactor at the outlet end additional burners, these burners not necessarily being fitted with oxygen

10 lances, but being possibly burners of a previously known type. These burners are so disposed that they are aligned contrary to the flow direction of the outflowing melt. This achieves a situation in which any solid agglomerates still present are forced back by

15 the aligned burner or are prevented from flowing, so that there is a sufficiently long delay time to achieve a fusion and thus homogenisation also of these residual solid agglomerates still present. According to the invention, therefore the shock-type cooling of the melt

20 for hardening by means of water jets is undertaken only when, in the way described above, complete homogenisation of the melt has occurred.

If at least one burner is operated in the area of melt homogenisation in a manner leaner than stoichiometric, i.e. with excess oxygen, then homogenisation takes place in an oxidising atmosphere. The stability of the melted-out minerals is improved in this way by secondary oxidation.

In the method according to the invention, the supply of oxygen to the oxygen lances and/or the supply of fuel to the pilot flames is regulated in dependence on the calorific value of the waste materials in such a way that in each case an almost constant synthesis gas composition and/or quantity results. This procedure thus compensates for differing calorific values of the waste materials supplied via the inlet aperture. As already shown in prior art, the method according to the invention also proceeds from heterogeneous wastes. The calorific values of heterogeneous wastes however vary very intensely, as on the one hand the waste can contain a large number of organic components and thus have a high calorific value, or more inorganic components or moisture, thus having a lower calorific value. In the method according to the invention the procedure is such that, at the outlet on the gas side,

the composition of the synthesis gas mixture is respectively determined, and the oxygen supply to the oxygen lances is regulated in dependence on the calorific value, i.e. the oxygen lances are operated in such a way that a constant synthesis gas composition is achieved at the gas outlet.

10

15

20

THE EMBODIMENTS OF THE INVENTION IN WHICH AN EXCLUSIVE PROPERTY OR PRIVILEGE IS CLAIMED ARE DEFINED AS FOLLOWS:

1. A method of operating a high-temperature reactor with an outlet for synthesis gas on a head and an outlet end for melted materials for treating heterogeneous waste materials, in which the waste materials are thermally pre-treated and/or compressed and introduced into the reactor via an intake point, and form beneath the intake point a loose, piled gasification bed, in which inorganic or organic components are subjected by oxygen to fusion, gasification and homogenisation, and above the intake point the gasification products are subjected in a free gas space of the high-temperature reactor to high-temperature treatment with supplied oxygen in order to form and stabilize a synthesis gas,  
characterized in that  
water-cooled oxygen lances are used for high-temperature treatment, at least two oxygen lances being disposed beneath the intake point in such a way that they reinforce a flow direction of the fusing and melted materials, and in that above the intake point there are disposed at least two oxygen lances in such a way that they inhibit flow of ascending gaseous components.
2. The method according to claim 1, wherein the oxygen, under temperature control, is introduced into the free gas space of the high-temperature reactor which is formed as a delay zone, in such quantities that partial combustion of the synthesis gas is rendered possible and the temperature above the gasification bed is maintained constantly above 1000°C, and wherein introduction of the oxygen is such that it creates turbulence in the gases, eliminating the formation of lanes or skeins, and a totally homogenous gas mixture is formed.

3. The method according to claim 1 or 2, wherein additional heat is supplied to the high-temperature reactor to maintain minimum temperatures of thermal processes through the use of oxygen lances having at least one permanently burning pilot flame which is operated by synthesis gases inherent in the process and/or externally supplied fuels, in a stoichiometric manner.
4. The method according to any one of claims 1 to 3, wherein the oxygen lances are operated in such a way that gasification of partially non-gasified or partially incompletely-gasified components is effected and/or in that residual traces of organic contaminants are cracked out of the gasification process.
5. The method according to claim 4, wherein the high-temperature treatment is carried out at temperatures greater than 1000°C.
6. The method according to any one of claims 1 to 5, wherein the oxygen of the oxygen lances disposed beneath the intake point is accelerated to at least approximately the speed of sound.
7. The method according to any one of claims 1 to 6, wherein a partial quantity of the oxygen flows continuously through the oxygen lances so that a nozzle of the lance is cooled by this oxygen flow and is protected from fouling, even if no lance oxygen were necessary.
8. The method according to claim 7, wherein the high-temperature treatment is carried out at temperatures up to above 1600°C.

9. The method according to any one of claims 1 to 8, wherein the free gas space above the intake point is dimensioned to provide a sufficient delay period before the gas outlet to set an equilibrium ratio of components of the synthesis gas, until the synthesis gas is shock cooled in order to prevent new formation of organic compounds.
10. The method according to any one of claims 1 to 9, wherein the reactor is designed beneath the intake point in such a way that there is a homogenisation area at the outlet end, said homogenisation area dimensioned to enable total homogenisation and phase separation of melted materials flowing out before the melted materials cool and harden.
11. The method according to claim 10, wherein the temperature in the homogenisation area is held at greater than 1500°C by at least one additional burner, the at least one additional burner being aligned such that its flame is directed contrary to the flow direction of the melted material flowing out.
12. The method according to claim 11, wherein the at least one additional burner has a flame operated in a manner leaner than stoichiometric such that an oxidizing atmosphere results in the homogenisation area.
13. The method according to any one of claims 1 to 12, wherein the oxygen supply to the oxygen lances is regulated such that an almost constant amount and composition of synthesis gas results.